DIETZ IRRIGATION

Engineers and Contractors

Serving Agriculture and Industry

CA Lic. #638281 WA Lic. DIETZI*020MB

REPORT

OF

EXCAVATION & TREATMENT

OF

HYDROCARBON AFFECTED SOIL

208 Jackson Street Oakland, California

November 30, 1998

208 Jackson Street Oakland, California Page One

Table of Contents

Background	2
Purpose	3
Preparation for Remediation	3
Excavation and Stabilization	4
Soil Treatment	5
Backfill and Compaction	6
Monitoring Wells	6
Remaining Work to be Completed	7
Figures	
Tables	
Appendix	
Remediation Plan	1
Alameda County Environmental Local Oversite Program Correspondence	2
City of Oakland and Air Board Permits	3
Laboratory Data	4
Soil Data	5
Monitoring Well Permits	6

208 Jackson Street Oakland, California Page Two

BACKGROUND

In early 1998 SNK Realty Group, located at 185 Berry Street, Suite 1200, San Francisco, California 94107-1729, was considering purchase of property located at 208 Jackson Street, Oakland, California, which was being operated as the Wo Lee Food Company. The objective was to redevelop the site which consists of a city block bounded by Jackson Street to the north, Madison Street to the south, Second Street to the west and Third Street to the east. The property was to be demolished and redeveloped for apartments and retail businesses. The legal name of the development is SNK Allegro @ JLS LLC. SNK authorized The San Joaquin Company Inc. to prepare a Remediation Plan for petroleum hydrocarbons (both diesel and gasoline) which existed in the soils and groundwater beneath the south-west corner of the property resulting from underground storage tank or piping leaks. The tanks were removed in 1990 by a former owner of the property, East Bay Packing Company, prior to their bankruptcy. The prior owner of the property, Wo Lee Foods had performed limited characterization of the site and had conducted very limited excavation in the area of the formerly installed storage tanks.

The Remediation Plan, prepared by The San Joaquin Company Inc., was submitted to the Alameda County Environmental Local Oversite Program which is the lead agency for this site. The Remediation Plan was approved with minor revisions requested. The following cleanup standards were established for soils at this site.

For Excavated Soil Remaining In Situ:

Total Petroleum hydrocarbons quantified as diesel (TPHd):	1000 mg/Kg
Total Petroleum hydrocarbons quantified as gasoline (TPHg):	100 mg/Kg
Benzene	0,016 mg/Kg

For Treated Soil Returned to Remedial Excavation:

Total Petroleum hydrocarbons quantified as diesel (TPHd):	1000 mg/Kg
Polynuclear Aromatic Compounds (PNAs):	ND
Total Petroleum hydrocarbons quantified as gasoline (TPHg):	100 mg/Kg
Benzene:	$N\!D$
Toluene:	ND
Ethylbenzene:	$N\!D$
Total Xylene Isomers:	ND

The Remediation Plan was revised by The San Joaquin Company to incorporate the Alameda County comments and was reissued on October 12,1998. The Remediation Plan is included as Appendix 1. This revised plan was approved by Alameda County (see Appendix 2).

208 Jackson Street Oakland, California Page Three

SNK selected Dietz Irrigation, a licensed general engineering contractor (License #638281) with a hazardous waste sub license, to perform the remediation. After close of escrow remediation was started in late August of 1998.

PURPOSE

The purpose of this report is to provide a regulatory status report of the remediation at 208 Jackson Street as requested by Alameda County in Appendix 2. This report documents the results of sampling from the bottom of the excavation and includes the sample data showing that the hydrocarbon affected soil has been excavated and the remaining soil in the site meets the cleanup standards established in the approved Remediation Plan. This report also provides documentation that the hydrocarbon affected soil from the excavation has been successfully treated to achieve the cleanup standards permitting beneficial reuse as backfill on site.

Another purpose of this report is provide the documentation to reach agreement with Alameda County that the on site remediation work has been completed. The hydrocarbon affected soil has been excavated and treated to achieve the site cleanup standards which will then permit site construction to proceed. Monitoring of replacement monitoring wells will continue during the construction phase and will provide the necessary data to justify site closure. This report does not include the results of the monitoring of the replacement monitoring wells. A separate report will be prepared by The San Joaquin Company Inc. when monitoring well data is available to provide adequate documentation and justification to request site closure by Alameda County and the Bay Area Regional Water Quality Control Board.

PREPARATION FOR REMEDIATION

The prior property owner, Wo Lee Food Company had removed a significant amount of obsolete food processing equipment from the site by close of escrow but a considerable amount of debris remained. Approximately 200 to 300 cubic yards of soil previously excavated were stockpiled on the site. Two steel structures were also located in the area to be excavated.

In preparation for the start of remediation, equipment consisting of a Komatsu PC200LC-5 excavator with a 1½ yard bucket, a Case Model 821 front loader with a 4 cubic yard bucket, a Case 580 K backhoe and a Landini GE 85 tractor with soil treatment equipment was mobilized to the job site. The trash was removed from the property and shipped to a Class III landfill in debris dumpsters. Concrete and asphalt was shipped to a concrete recycler for beneficial reuse. Permits were obtained for the demolition of the steel structures. Copies of the City of Oakland permits and Air Board permits are included in Appendix 3. A pre-demolition asbestos survey was conducted by The San

208 Jackson Street Oakland, California Page Four

Joaquin Company Inc. No asbestos was present in either of the steel structures to be demolished. Once the trash was removed from the site, the previously excavated soil was placed in the open excavation to permit demolition of the steel structure located at the intersection of Madison Street and Second Street. Dumpsters were mobilized to the job site for recycling of the steel following demolition of the building. After demolition of the building and removal of the debris, the asphalt and concrete covering the area to be excavated was removed and shipped to a concrete recycler for beneficial use as aggregate base.

Test pits were excavated and soil samples analyzed to aid in definition of the lateral and vertical extent of the hydrocarbon affected soil. During excavation of these test pits it was discovered that the site contained flowing sands which necessitated the use of a special excavation technique to prevent subsidence of the adjacent streets. This technique consisted of excavation of cells approximately 25 feet by 25 feet up to 7 feet below the water table and immediately backfilled with 6 inch drain rock to maintain stability. The flowing sands had the consistency of wet concrete. It was necessary, once the excavation started, to be ready to immediately backfill with large drain rock to maintain stability of the excavated area.

EXCAVATION AND STABILIZATION

Prior to the start of excavation the Bay Area Air Quality Management District was notified in accordance with their requirements. The excavation proceeded from the south-west corner of the site which is the intersection of Madison and Second Streets. The excavated soil was shuttled in several steps by the excavator to a location where it could be picked up by the front loader and stockpiled. Soil samples were taken from the excavation bottom on a 25 feet by 25 feet grid pattern. Additional samples were taken when approaching the limits of the hydrocarbon affected soil particularly along the east and north excavation walls. The limits of the excavation and the samples taken are visually presented in Figure 1. Table 1 lists the samples taken and laboratory results in tabular form. The laboratory data including the Chain of Custody is included in its entirely in Appendix 4.

The special 6 inch drain rock used to stabilize the excavation was added periodically to maintain a level just above the water table. Fortunately, the water flowed into the excavation very slowly which permitted the rock to be brought over a several week time period. Over 900 tons of rock were used to stabilize the excavation which was ultimately brought to just above the top of the water table (approximately 5 feet below the level of the sidewalk).

208 Jackson Street Oakland, California Page Five

The cleanup standards established prior to the start of this project were achieved in the area excavated in all but one location. In one location the benzene concentration in the soil was 0.17 mg/Kg. The laboratory results trailed the excavation by approximately five days. Rock had already been added to the hole to stabilize the excavation when this concentration of benzene exceeding the cleanup standard was reported. It was not considered appropriate to re-open the excavation because the residual concentration of benzene in this small area was very low and the stability of the street could be adversely affected. Verbal agreement was obtained from the Alameda County representative, Mr. Larry Seto, that re-excavation would not be required.

During the course of the excavation it became evident that the hydrocarbon affected soil extended somewhat beneath the second steel shed which was located on Madison Street between Second and Third. In order to effectively excavate and later treat soil this structure was demolished. The City of Oakland demolition permit is included in Appendix 3.

The soil stockpiles were sampled and analyzed to comply with Bay Area Air Quality Management District requirements to obtain representative concentrations of hydrocarbons in the soil which dictated the rate soil may be moved from the stockpile to the treatment area.

SOIL TREATMENT

The processes used for treatment of hydrocarbon affected soil were aeration of gasoline and benzene, toluene, ethyl benzene and xylene plus natural bio remediation of diesel. The soil was moved from the stockpile and spread in the treatment area 12 to 18 inches deep using the front loader. The quantity of soil which could be spread was regulated by the Bay Area Air Quality Management District specifications. Once the soil was spread using the front loader, a tractor equipped with a 6 foot rotivator was used to aerate and oxygenate the soil. This was conducted, depending on weather conditions, several times a day or at intervals of several days. To complete the treatment of the affected soil three distinct batches which ranged from 500 to 700 cubic yards were required. These were labeled LDS-1, LDS-2 and LDS-3. Treatment was conducted during the period from mid September to early November of 1998. Once the treatment had proceeded until no olfactory indications could be detected from the spread, sampling was conducted. Table 2A shows the results of sampling for LDS-1 which was conducted on September 29, 1998; Table 2B shows the results of analysis of samples taken from LDS-2 on October 15, 1998 and Table 2C shows the sample results of from LDS-3 sampled on November 10, 1998. See Figures 2A, 2B and 2C for the sample locations on each of these spreads.

208 Jackson Street Oakland, California Page Six

The samples were taken on a random basis using a random number generator to locate the samples. The complete laboratory data including Chain of Custody is included in Appendix 4.

All sample results showed that the treated soil had achieved the cleanup standards. All of the samples were non detect for gasoline, benzene, toluene, ethyl benzene and xylenes. The highest concentration for Total Petroleum Hydrocarbons as diesel was 270 mg/Kg which is well below the cleanup standard of 1000 mg/Kg. Approval was requested from Alameda County to use this material as backfill on the site. See Appendix 2 for copies of the County approval for use of the treated soil as backfill.

Upon successful treatment of the hydrocarbon affected soil, the soil was stockpiled in separate stockpiles pending use as site backfill.

BACKFILL AND COMPACTION

The 6 inch drain rock was smoothed and carefully compacted to provide a firm base prior to the start of soil backfill. Some soft areas were encountered during the vibratory compaction and additional rock was imported to stabilize these areas and to bring the top of rock above the water table. A 66 inch pad foot vibratory compactor was used for the compaction.

A representative soil sample was taken to obtain a moisture density curve which is necessary to enable nuclear gauge testing of the compacted soils and verify that the desired compaction level had been achieved. The compaction standard established for this site was 90 percent relative density as measured by nuclear gauge testing. It was necessary to have at least 12 inches of compacted soil in place before testing to avoid interference from the large drain rock underlying the area being backfilled. The soil was moved from the stockpile area and spread in preparation for compaction in approximately 6 to 8 inch lifts. The material was compacted using the vibratory compactor and periodically tested with a nuclear gauge. See Appendix 5 for the moisture density curve and compaction data. The standard of 90 percent relative density was easily achieved using the treated soil. The grade was established at 2 feet below the sidewalk as previously agreed to by the SNK Project Manager, Mr. Scott Johnson. The remaining soil was stockpiled on top of the compacted fill in the area of the excavation until site grading plans are prepared.

MONITORING WELLS

Five monitoring wells had been previously installed on the site. Monitoring well 1 was destroyed during over excavation in the tank pit several years ago. Monitoring wells 2 and 3 were approved for closure by the Alameda County Public Health prior to purchase

208 Jackson Street Oakland, California Page Seven

of the property by SNK. In preparation for the site remediation Alameda County permits were obtained for closure of monitoring wells 2 and 3 by grouting and closure of monitoring wells 4 and 5 by over excavation. The permits are included in Appendix 6.

To provide sufficient data to obtain site closure by Alameda County and the Regional Water Quality Control Board, two replacement monitoring wells for monitoring wells 4 and 5 called MW4R and MW5R are to be installed in the parking areas of Second and Madison Streets. The well locations are shown in the Remediation Plan included in Appendix 1.


Monitoring wells 4 and 5 were removed by over excavation during excavation of the hydrocarbon affected soil. Monitoring wells 2 and 3 were grouted by Gregg Drilling on November 23, 1998. At that time it was also planned to install the two replacement monitoring wells and permits were obtained from Alameda County. For installation of the two new monitoring wells a minor encroachment permit and an excavation permit were obtained from the City of Oakland. Copies of these permits for the replacement monitoring wells are included in Appendix 6. USA Alert was requested to identify utilities in the area. Monitoring well installation was initiated but stopped due to thick concrete located beneath the asphalt in the street. It will be necessary to core drill the concrete prior to installation of these monitoring wells. This will be scheduled as soon as a drill rig is available.

REMAINING WORK TO BE COMPLETED

Excavation and treatment of hydrocarbon affected soil has been completed in accordance with the approved Remediation Plan. The remaining work to be done to obtain regulatory closure of this site is:

- Complete the installation of monitoring wells MW4R and MW5R.
- Prepare Remediation Report.
- Sample for four quarters and prepare quarterly reports.
- Prepare a report justifying site closure.

Since the hydrocarbon affected soil has been removed from the site it is expected that the concentrations of hydrocarbons in the groundwater will decrease showing natural attenuation with time.



The San Joaquin Company, Inc.

FIG 1

Project Number: 9401.114

Drawn by: GNM | Date: 11/25/98

Phillippi Engineering (04/11/98) Project: A.L.T.A. Survey Block 13 & Portions of 35 & 36 Sheet Title: S.N.K. Realty Group Third Street Transformer Ε D C В Gate 1 ND Tph(d) 38 2 ND Tph(d) 120 **Madison Street** 3 ND Tph(d) 140 ND Tph(d) 31 4 ND ● Tph(d) 270: 5 **EXPLANATION** Analytes of concern Sampling Location (all concentrations in mg/kg) Tph(d) - diesel N.D. No analytes of concern detected above the applicable MDL except as noted Tph(g) - gasoline B - Benzene **Property Boundary** 50 T - Tolulene NOTE: Refer to Table 2a for complete data results E - Ethylbenzene X - Xylenes Scale in Feet PNA - Polynuclear Aeromatics SAMPLE LOCATIONS IN TREATED SOIL SPREAD LDS 1 208 Jackson Street, Oakland, California

FIG 2a The San Joaquin Company, Inc.

Based on:

Project Number: 9401.114

Drawn by: GNM | Date: 11/25/98

Phillippi Engineering (04/11/98) Project: A L.T.A. Survey Block 13 & Portions of 35 & 36 Sheet Title: S.N.K. Realty Group Third Street Transformer Ε D C В Gate 1 ND Tph(d) 260 ND Tph(d) 110 ND **•** Tph(d) 220 2 Madison Street 3 ND Tph(d) 190 ND Tph(d) 120 5 **EXPLANATION** Analytes of concern Sampling Location (all concentrations in mg/kg) Tph(d) - diesel N.D. No analytes of concern detected above the applicable MDL except as noted Tph(g) - gasoline B - Benzene **Property Boundary** 50 T - Tolulene NOTE: Refer to Table 2b for complete data results E - Ethylbenzene X - Xylenes Scale in Feet PNA - Polynuclear Aeromatics SAMPLE LOCATIONS IN TREATED SOIL SPREAD LDS 2 208 Jackson Street, Oakland, California

FIG 2b

Based on:

The San Joaquin Company, Inc.

Project Number: 9401.114

Date: 11/25/98 Drawn by: GNM




FIG 2c The San Joaquin Company, Inc.

Project Number: 9401.114

Drawn by: GNM Date: 11/25/98

TABLE 1

RESULTS OF ANALYSES OF SOIL SAMPLES RECOVERED FROM THE BOTTOM OF THE REMEDIAL EXCAVATION

Location Number (on Figure 1)	Sample Number	Sample Depth ft	Date Sampled	TPHd (Diesel) mg/Kg	TPHg Gasoline mg/Kg	Benzen e) mg/Kg	Toluene mg/Kg	Ethyl- benzene mg/Kg	Total Xylenes mg/Kg
1	CON 00	8	8-Sep-98	N.D.	2.5	0.015	0.0067	0.19	0.98
2	CON W25	12	8-Sep-98	N.D.	N.D.	N.D.	N.D.	0.0087	N.D.
3	CON S25	10	8-Sep-98	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
4	CON S25-W25	7	8-Sep-98	4.4	1.8	0.17	N.D.	0.46	0.023
5	CON S50	10	8-Sep-98	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
6	CON S60	7	8-Sep-98	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
7	CON W50	9	10-Sep-98	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
8	CON W50-S25	10	10-Sep-98	N.D.	N.D.	N.D.	N.D.	0.023	0.029
9	CON W50-S50	12	10-Sep-98	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
10	CON W75(10)	10	10-Sep-98	N.D.	N.D.	N.D.	N.D.	N.D.	ND.
11	CON S75 W25	10	14-Sep-98	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
12	CON S75 W50	9	14-Sep-98	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
13	CON W75-S25	9	14-Sep-98	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
14	CON W75-S50	8	14-Sep-98	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
15	CON W75-S75	7	14 - Sep-98	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
16	CON S75-W100	7	14-Sep-98	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
17	CON W100	5	15-Sep-98	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
18	CON W100-S25	5	15-Sep-98	2.3	N.D.	N.D.	N.D.	N.D.	N.D.
19	CON S50-W100	6	15-Sep-98	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
20	CON \$70-W100	5	15-Sep-98	N.D.	29	N.D.	N.D.	N.D.	12
21	CON E25-\$80	7	18-Sep-98	360	N.D.	N.D.	N.D.	0.0074	0.072
22	CON E45-S80	8	18-Sep-98	4.3	N.D.	N.D.	N.D.	N.D.	N.D.
23	CON E60-S80	7	18-Sep - 98	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.

Notes: (1) N D = Not Detected above the Method Detection Limit (MDL).

TABLE 2A

RESULTS OF ANALYSES OF SAMPLES
FROM TREATED SOIL SPREAD LDS-1

Sample	Date Sampled	TPHd	TPHg	Benzene	Toluene	Ethyl- benzene	Total Xylenes
No.	•	mg/Kg	mg/Kg	mg/Kg	mg/Kg	mg/Kg	
A4	09/29/98	38	ND	ND	ND	ND	ND
B2	09/29/98	120	ND	ND	ND	ND	ND
D3	09/29/98	140	ND	ND	ND	ND	ND
E1	09/29/98	270	ND	ND	ND	ND	ND
E4	09/29/98	31	ND	ND	ND	ND	ND

Notes:

⁽¹⁾ A composite of all 5 soil samples listed above was tested for Polynuclear Aromatic Hydrocarbons (PNAs). None were detected

⁽²⁾ ND = Not Detected above the Method Detection Limit (MDL).

TABLE 2B

RESULTS OF ANALYSES OF SAMPLES
FROM TREATED SOIL SPREAD LDS-2

Sample No.	Date Sampled	TPHd (diesel) mg/Kg	TPHg (gasoline) mg/Kg	Benzene mg/Kg	Toluene mg/Kg	Ethyl- benzene mg/Kg	Total Xylenes mg/Kg
A-2	10/15/98	220	ND	ND	ND	ND	ND
C-1	10/15/98	260	ND	ND	ND	ND	ND
C-2	10/15/98	110	ND	ND	ND	ND	ND
C-3	10/15/98	190	ND	ND	ND	ND	ND
E-4	10/15/98	120	ND	ND	ND	ND	ND
E-5	10/15/98	45	ND	ND	ND	ND	0.0057

Notes:

⁽¹⁾ A composite of all 6 soil samples listed above was tested for Polynuclear Aromatic Hydrocarbons (PNAs). None were detected.

⁽²⁾ ND = Not Detected above the Method Detection Limit (MDL).

TABLE 2C

RESULTS OF ANALYSES OF SAMPLES FROM TREATED SOIL SPREAD LDS-3

Sample No.	Date Sampled	TPHd (diesel) mg/Kg	TPHg (gasoline) mg/Kg	Benzene mg/Kg	Toluene mg/Kg	Ethyl- benzene mg/Kg	Total Xylenes mg/Kg
A-4	11/10/98	8.8	N.D.	N.D.	N.D.	N.D.	N.D.
B-1	11/10/98	9.1	N.D.	N.D.	N.D.	N.D.	N.D.
C-2	11/10/98	140	N.D.	N.D.	N.D.	N.D.	N.D.
D-3	11/10/98	36	N.D.	N.D.	N.D.	N.D.	N.D.
G-8	11/10/98	18	N.D.	N.D.	N.D.	N.D.	N.D.
G-5	11/10/98	49	N.D.	N.D.	N.D.	N.D.	N.D.

Notes:

- (1) ND = Not Detected above the Method Detection Limit (MDL).
- (2) A composite of all 6 soil samples listed above was tested for Polynuclear Aromatic Hydrocarbons (PNAs). None were detected.

THE SAN JOAQUIN COMPANY INC.

8617 ETCHEVERRY DRIVE, TRACY, CALIFORNIA 95376

October 12, 1998

Alameda County Health Care Services Agency Environmental Health Services Environmental Protection 1131 Harbor Bay Parkway, Suite 250 Alameda, CA 94502-6577

Attention: Mr. Larry Seto

Subject: Remediation at 208 Jackson Street, Oakland, California

Dear Mr. Seto:

Attached is a revised Remediation Plan incorporating the following:

- o Revisions to clean-up standards directed in your letter to Mr. Johnson dated August 3, 1998 and
- The location of replacement wells for monitoring wells 4 and 5 destroyed during the excavation which we agreed upon at our site meeting on October 8, 1998. This is per your request in your letter of September 17, 1998.

This plan is submitted for documentation purposes only.

If you have any questions please contact me at (209) 832-2910 or on my mobile at (209) 482-7769.

Sincerely,

H. B. Dietz

HBD/gwd

cc: Scott Johnson, SNK

THE SAN JOAQUIN COMPANY INC.

8617 ETCHEVERRY DRIVE, TRACY, CALIFORNIA 95376

REMEDIATION PLAN

208 JACKSON STREET OAKLAND, CALIFORNIA

Prepared for:

SNK Development Inc. 185 Berry Street, Suite 1200 San Francisco, California 94107

June 1998

Revision 1 - October 1998

Project No. 9401.112

TABLE OF CONTENTS

Page
PROFESSIONAL CERTIFICATION AND LIMITATIONS1
INTRODUCTION
BACKGROUND2
o Site History o Underground Storage Tank Removal o Planned Use For Site o Geology and Hydrology
SITE CHARACTERIZATION RESULTS
o Soil Sampling During Tank Removal o Results Of Soil Borings o Ground Water Monitoring
PLAN FOR REMEDIATION3
o Replacement Monitoring Wells o Close Existing Monitoring Wells o Demolition of Steel Building o Site Paving o Excavate Clean and Hydrocarbon Affected soil o Soil Treatment o Site Restoration o Request for Closure o Release for Construction
HEALTH AND SAFETY PLAN6
DEPENDINGES 6

TABLE OF CONTENTS

	Page
Site Location	8
Site Plan	9
Groundwater Gradient	10
Soil Boring Locations	11
• -	
Area Planned for Excavation and Soil Treatment	16
Monitoring Well Sample Results	17
Soil Boring Soil Sample Results	19
	Site Location. Site Plan. Groundwater Gradient. Soil Boring Locations. Iso Concentration Map for TPHd. Iso Concentration Map for TPHg. Iso Concentration Map for Benzene. Proposed Location of Replacement Monitoring wells. Area Planned for Excavation and Soil Treatment. Monitoring Well Sample Results. Groundwater Gradient Data. Soil Boring Soil Sample Results From Soil Borings. Groundwater Depth Information.

PROFESSIONAL CERTIFICATION AND LIMITATIONS

This plan was prepared under the direction of the engineers whose seals and signatures appear below. The work was performed in accordance with generally accepted standards of engineering practice based on information available to us at the time of its preparation and within the limits of the scope of work directed by the client. No other representation, express or implied, and no warranty or guarantee is included or intended as to professional opinions, recommendations, or field or laboratory data provided.

D. J. Watkins, Ph.D., P.E. Georgechnical Engineer

The San Joaquin Company Inc.

H. B. Dietz REA

The San Joaquin Company Inc.

No 05077

INTRODUCTION

Extensive investigation, characterization and remediation planning has been conducted by a variety of consultants on the site at 208 Jackson Street, Oakland, California (See Figure 1 for location). The work was of good quality and has formed the basis for development of this remediation plan. Key information has been extracted from that prior work for preparation of this plan and its source has been referenced. These reports have been previously sent to the regulatory agencies. It would serve no useful purpose to redo the work which has already been done. Since the site is scheduled for redevelopment it is now time to cease the studies, investigations and characterization work and immediately proceed with remediation to achieve site closure.

BACKGROUND

Site History

The site (See Figure 2) which incorporates the block between 2nd and 3rd Streets and Jackson and Madison Street was originally developed in the early 1890's for residential housing. The neighborhood remained residential until about 1911 at which time the Union Pacific Railroad began acquiring the area for use as a rail yard. The residential nature of the neighborhood rapidly changed to a rail yard and industrial area by 1930. A trucking company occupied the south-west corner of the site. A meat packing facility was constructed on the remainder of the property. Earliest maps available show residential housing in 1911 and the trucking company and meat packing plant present in 1950. It is not known when the four tanks previously located on the site, (See Figure 2) were installed. Sometime after 1945 the John Morrell and Company built a meat packing plant occupying the majority of the site. In 1990 the site owner, East Bay Packing Company, who by this time occupied the entire block, sold the property and just prior to the sale removed four underground storage tanks, two diesel and two gasoline tanks. The tank sizes are as follows: 8,000 gallon, 2,000 gallon, 10,000 gallon and 10,000 gallon. At the time of tank removal, the site was identified as a site of leaking underground storage tanks. The San Francisco Bay Regional Water Quality Control Board file number for this site is 01-0533.

Planned Use For The Site

SNK Development Inc intends to demolish the present structures and construct a multi story office building on the site.

GEOLOGY AND HYDROLOGY

The site is situated on the eastern side of San Francisco Bay in the California Coast Ranges section of the Pacific Border physiographic province. Immediately beneath the man made surface is the Pleistocene-age Merritt sand, which has an estimated thickness of approximately 50 feet. The Merritt sand is composed of fine-grained, silty, clayey sand with lenses of sandy clay and clay.

The water table at the site is encountered at 4 to 6 feet beneath the ground surface and below the top of the Merritt sands. The general down gradient flow direction is south toward the Oakland estuary. Soils with the grain size and gradational properties of the fine Merritt sands commonly have hydraulic conductivities in the range of 10 - 10 cm/sec. It is likely that the hydraulic conductivity of the natural soils beneath the site may be as low as 10 cm/sec.

SITE CHARACTERIZATION RESULTS

At the time of underground storage tank removal in 1990, soil samples from beneath the tanks revealed the presence of Total Petroleum Hydrocarbon (TPH) as gasoline and TPH as diesel in the soil and in a grab sample of the groundwater. In May of 1990 three groundwater monitoring wells and in June 1994 two additional monitoring wells were installed. See Figure 2. The results from the groundwater monitoring well sampling are reproduced in Table 1.

These monitoring wells also provided the ability to determine the groundwater gradient. See Table 2 and Figure 3. In 1995 soil borings were performed to further characterize the site. The location of these soil borings are shown in Figure 4. The sample results from the soil borings are shown in Tables 3 and 4. Based on the results of the soil borings and groundwater monitoring, estimated contours for concentrations of components of fuel hydrocarbons affecting groundwater were developed. These are reproduced in Figures 5, 6 and 7.

The results of the site characterization indicate the presence of hydrocarbon affected soil in the south-west corner of the site which is providing a source for hydrocarbons in groundwater. Since the depth to groundwater from the surface varies between 4 to 6 feet (See Table 5) the principal zone of hydrocarbon affected soil generally would not be deeper than 7 feet.

PLAN FOR REMEDIATION

Install Replacement Monitoring Wells

Two replacement monitoring wells will be installed in the street pending City of Oakland approval (encroachment permit) and their exact location will be dependent upon the presence of underground utilities. These new wells which replace MW4 and MW5 will be used to monitor improvements to the groundwater quality achieved by removal of the source term. See Figure 8 for location of proposed new monitoring wells. It is anticipated that these wells would be monitored for four quarters and then formally closed.

Close Existing Monitoring Wells

The Alameda County Public Health Services Department (ACPHSD) has approved closure of two (MW2 and MW3) of the existing upgradient monitoring wells (see Reference 1) because they have been monitored for a significant period of time and have shown no impact from the previously identified hydrocarbon release from the leaking underground storage tanks. These two wells will be closed by grouting. One well (MW-1) which was originally installed was

destroyed during over excavation of the tank pit. The remaining two wells (MW-4 and MW-5) will be destroyed during excavation of the hydrocarbon affected soil and, therefore, must be formally closed prior to the start of excavation.

Demolition of Steel Buildings on South-west Corner of Site

A demolition permit will be obtained from the City of Oakland prior to demolition of the metal buildings located on the south-west corner of the site. These buildings are steel frame covered with galvanized siding. A pre-demolition asbestos survey performed in April 1998 (see Reference 2) determined that there is no asbestos present in these buildings. Removal is necessary to permit excavation of the soil beneath the buildings which has been affected by hydrocarbons from the previously installed gasoline and diesel underground storage tanks. The demolition debris will be removed from the site.

Site Paving Removal

The concrete floor and footings from the steels building to be demolished, the reinforced concrete located in the yard, the asphalt paving and any other debris in the yard will be removed prior to the start of soil remediation. The clean concrete and asphalt will be shipped off site for recycling.

Excavate Clean and Hydrocarbon Affected Soil

The anticipated area to be excavated is shown on Figure 9. The procedure will be as follows:

1) Excavate the clean soil and stockpile in one area of the site. 2) Excavate hydrocarbon affected soil, which is expected to be present up to 7 feet beneath the surface, and 3) stockpile in preparation for aeration and bioremediation soil treatment on site. The cleanup standard with respect to soil remaining in the excavation will be 100 mg/Kg (parts per million - ppm) for TPH as gasoline, 1000 ppm TPH as diesel and 0.016 mg/Kg for benzene.

Sampling will proceed in conjunction with excavation, and when the in situ soil remaining in the excavation meets the cleanup standards, excavation in the area will cease. The depth of the excavation will also be limited if, in the opinion of the professional engineer in charge of the work, further deepening of the remediation pit would pose a threat of bottom heave, sand liquifaction or other geotechnical phenomenon that might render the site or adjacent streets unstable. It is expected that the walls of the excavation will not approach closer than 5 feet to the back of the sidewalks on Madison and Second Streets.

Soil Treatment

Prior to the start of soil treatment, the San Francisco Bay Area Air Quality Management District (SFBAAQMD) will be notified. The hydrocarbon affected soil containing TPH as gasoline and TPH as diesel will be treated by a combination of aeration and bioremediation. Based on

SFBAAQMD permitted concentrations in the stockpile, the soil will be spread on the site to a thickness of approximately 12 to 18 inches.

A farm tractor equipped with a large rotivator will be used for soil conditioning during the aeration and bioremediation. Depending on the concentration of diesel in the affected soil a sprinkler system using micro sprinklers may be installed for moisture control. The naturally occurring biota in the soil will be used for the bioremediation. The proper amounts of moisture and fertilizer will be added. Oxygen will be supplied by aeration using the soil treatment equipment. If moisture is required water will be pumped from the excavation and stored in a 20,000 gallon Baker tank which will be maintained on the site. This will also assist in reducing the hydrocarbon concentration in the groundwater by actually using hydrocarbon affected groundwater for moisture control during bioremediation. Based on the concentrations, temperature and aggressiveness of the treatment samples will be periodically taken. The clean up standard for soil will be less than 100 ppm TPH as gasoline, 1000 ppm TPH as diesel and non detectable for benzene, toluene, ethyl benzene or xylene.

When the treated soil is free of visual or olfactory indicators of fuel hydrocarbons, samples will be recovered from randomly selected locations in the spread material and analyzed for TPHg, TPHd, benzene, toluene, ethylbenzene and total xylene isomers. Computation of the number of samples required, the procedures for selecting the random sampling locations, and the statistical methods employed to demonstrate that the aeration and bioremediation has reduced the concentrations of fuel hydrocarbons to less than the proposed cleanup levels will adhere to the guidelines published in the technical document: Methods of Evaluating the Attainment of cleanup standards, Vol. 1: Soils and Solid Media, published by the United States Environmental Protection Agency. (Ref. 3)

If the results from the first sampling of the aerated and bioremediated soil show that the concentration of any analyte of concern exceeds the established cleanup criteria, the spread soil will be further bioremediated and re-sampled until sampling demonstrates that the cleanup criteria have been met.

Site Restoration

Once the soil removed for treatment has attained the clean up standard and approved by Alameda County, the excavation will be readied for soil placement. To insure stability in the excavation, rock will be added to stabilize the hole to the water line. The rock will be compacted to provide a firm base for soil compaction. The soil removed from the surface will be conditioned to achieve proper moisture content, placed in the hole and compacted to achieve an 90 percent relative density. Compaction test results will be included in the final report. The final grade will be determined by the new building foundation design.

Request for Closure

A report documenting the results of the site remediation that will include a Risk Based Correction Action Assessment in accordance with American Society of Testing and Materials (ASTM E 1739-95) will be prepared for submittal to Alameda County Health Care Services, the responsible regulatory authority. This report together with the results of a round of sampling in the newly installed monitoring wells will provide the basis for site closure.

RELEASE FOR CONSTRUCTION

The site will be released for construction following completion of the removal of the hydrocarbon source, the treatment of the soil and restoration of the site. Additional groundwater monitoring in the relocated monitoring wells may be required for four quarters to verify continuing natural attenuation due to removal of the hydrocarbon source.


HEALTH AND SAFETY PLAN

Work will be performed in accordance with the Site Specific Health and Safety Plan attached.

REFERENCES

- 1. Letter from Alameda County Health Care Services Agency, Environmental Protection Division (ACHCSA) Former East Bay Packing Site, cka Wo Lee Foods, 208 Jackson Street, Oakland, California 94607 dated September 24, 1997.
- 2. M. F. Lundeen Company Asbestos Material Survey, 208 Jackson Street, Oakland, California, prepared for The San Joaquin Company, April, 1998.
- 3. United States Environmental Protection Agency (1989): Methods of Evaluating the Attainment of Cleanup Standards, Vol. 1: Soils and Solid Media. Report No. EPA 230/02-89-042, February, 1989.
- 4. ACC Environmental Consultants Corrective Action Plan Wo Lee Food 208 Jackson Street, Oakland, California dated July 9, 1996.
- 5. ACC Environmental Consultants *Biannual Groundwater Monitoring Report* dated October 24, 1997.
- 6. Letter from Alameda County Health Care Services Agency, Environmental Protection Division (ACHCSA) Former East Bay Packing Site, cka Wo Lee Foods, 208 Jackson Street, Oakland, California 94607 dated March 17, 1997.
- 7. Subsurface Consultants, Inc. Additional Recommendations Environmental Engineering Services 208 Jackson Street, Oakland, California dated January 13, 1994.

- 8. ACC Environmental Consultants Stockpiled Soil Sampling Wo Lee Food Company 208 Jackson Street, Oakland, California dated April 4, 1997.
- 9. American Society for Testing and Materials (ASTM). November 1995. Standard Guide for Risk Based Corrective Action Applied at Petroleum Release Sites. Designation: E 1739-95. ASTM, 100 Barr Harbor Drive, West Conshohocken, PA 19428.
- 10. Subsurface Consultants, Inc. July 12, 1994. Groundwater Contamination Assessment, 208 Jackson Street, Oakland, California. Project Number886.001.
- 11. ACC Environmental Consultants, Inc. May 22, 1995. Subsurface Environmental Investigation, 208 Jackson Street, Oakland, California. Project Number 95-6238-1.0. Prepared for Wo Lee Foods.



SITE LOCATION

208 Jackson Street, Oakland, California

FIG 1

The San Joaquin Company, Inc.

Project Number: 9401.112

Drawn by: GNM Date: 05/20/98

Figure 2

Subsurface Consultants

208 JACKSON STREET - OAKLAND, CA

1/5/94

JOB NUMBER

885 001

PLATE

APPROVED




Figure 3
Groundwater Gradient




Figure 4
Location of Soil Borings




Figure 6

ACC Environmental Consultants • 1000 Atlantic Avenue, Suite 110 • Alameda, CA 94501 • (510) 522-8188 Fax: (510) 865-5731




Figure 7






Figure 8 Location of replacement monitoring wells



Madison Street

THE SAN JOAQUIN COMPANY, INC. 8617 Etcheverry Drive Tracy, CA 95376



Title: SITE Plan

208 Jackson Street

Oakland, California

Figure No: 2 Scale: 1" = 40'

Drawn By: JYC/DRD Date: 3/30/97

Project No: 6249-001.00

ACC Environmental Consultants, Inc.
7977 Capwell Drive, State 100

Oakland, CA 94621

(510)638-8400 Fax (510)638-8404

Figure 9:
Area Planned for Excavation

TABLE 1 - MONITORING WELL SAMPLE RESULTS

Taken from Reference 5

Well No.	Date Sampled	TPHg (μg/L)	Benzene (μg/L)	Toluene (μg/L)	Ethyl- benzene (µg/L)	Xylenes (μg/L)	TPHd (µg/L)	MTBE (μg/L)
MW-1	05/21/90	25,000	400	440	330	650	5,500	
(destroyed)								
MW-2	05/21/90	< 50	<1.0	<1.0	<1.0	<1.0	< 50	
	01/06/94	< 50	< 0.5	< 0.5	< 0.5	< 0.5	< 50	
} *	09/04/96	< 50	< 0.5	< 0.5	< 0.5	< 0.5	< 50	< 5.0
	03/21/97	< 50	< 0.5	< 0.5	< 0.5	< 0.5	< 50	< 5.0
	10/01/97							
MW-3	05/21/90	< 50	<1.0	< 1.0	<1.0	<1.0	< 50	
	01/06/94	< 50	< 0.5	< 0.5	< 0.5	< 0.5	< 50	
	06/03/94	< 50	< 0.5	< 0.5	< 0.5	< 0.5	230 ⁽¹⁾	
	09/04/96	< 50	< 0.5	< 0.5	< 0.5	< 0.5	< 50	< 50
	03/21/97	< 50	< 0.5	<0.5	< 0.5	< 0.5	< 50	<5
	10/01/97							
MW-4	06/03/94	210,00	7,600	28,000	3,700	24,000	9,800	
	09/04/96	0	5,100	4,600	4,100	14,000	< 50	< 500
	03/21/97	45,000	5,000	6,300	4,600	14,000	< 50	<250
	10/01/97	58,000	5,000	3,800	3,900	12,000	< 260	< 250
		48,000				_		
MW-5	06/03/94	7,800	3.8	6.2	10	16	4,600	
	09/04/96	1,600	14	3.6	9.7	13	< 50	< 5
	03/21/97	430	4.2	< 0.5	1.4	0.62	690 ⁽²⁾	< 5
	10/01/97	1,100	0.7	1.1	1.2	1.9	1,800 ⁽²⁾	< 5

Notes: (1) Reported to be an anomalous result from one chromatogram peak

(2) Hydrocarbon reported does not match laboratory diesel standard

THE SAN JOAQUIN COMPANY, INC. 8617 Etcheverry Drive Tracy, CA 95376

TABLE 2 - GROUNDWATER GRADIENT DATA
Taken from Reference 5

Date Monitored	Average Gradient (foot/foot)	Direction
September 9, 1995	0.004	south-southeast
October 27, 1995	0.003	south
November 30, 1995	0.003	south
September 4, 1996	0.003	south
March 21, 1997	0.007	south
October 1, 1997	0.003	south

THE SAN JOAQUIN COMPANY, INC. 8617 Etcheverry Drive Tracy, CA 95376

TABLE 3 - SOIL BORING SOIL SAMPLE RESULTS Taken from Reference 4

Sample # - depth	Date Collected	TPHg (mg/kg)	Benzene (mg/kg)	Toluene (mg/kg)	Ethyl- benzene (mg/kg)	Xylenes (mg/kg)	TPHd (mg/kg)
B1-4.0	3/21/95	< 1	< 0.005	< 0.005	< 0.005	< 0.005	1.3
	3/21/95	<1	< 0.005	< 0.005	< 0.005	< 0.005	5.4
B2-4.0		<1	< 0.005	< 0.005	< 0.005	0.013	<1
B3-4.0	3/21/95	<1	< 0.005	< 0.005	< 0.005	0.014	<1
B4-4.0	3/21/95	<1	< 0.005	< 0.005	< 0.005	0.019	<1
B5-4.0	3/21/95		< 0.005	< 0.005	< 0.005	0.013	<1
B6-4.0	3/21/95	<1	0.040	· 0:011	0.0074	0.029	< 1
B7-4.0	3/21/95	1.7		0.012	0.030	0.091	⁻ 94
B8-4.0	3/21/95	2.9	0.026		< 0.005	< 0.005	<1
B9-3.5	3/21/95	<1	< 0.005	< 0.005			71
B10-3.5	3/21/95	2,300	5.3	26	40	200	
B11-3.5	3/22/95	<1	< 0.005	< 0.005	< 0.005	< 0.005	1.4
B12-3.5	3/22/95	22	0.023	0.43	0.21	3.6	_ 1,100
}	3/22/95	2,700	1.9	3.9	34	210	66
B13-3.5		4.2	< 0.005	0.044	0.024	0.25	< 1
B14-3.5	3/22/95		1.5	0.40	1.3	7.6	5.6
B15-3.5	3/22/95	710			9.6	59	1,200
B16-3.5	3/22/95	270	2.2	25			

Notes: mg/kg = mittigram per kilogram, approximately equal to parts per million (ppm)

< = Less than detection limit indicated

THE SAN JOAQUIN COMPANY, INC. 8617 Etcheverry Drive Tracy, CA 95376

TABLE 4 - GRAB GROUNDWATER SAMPLE RESULTS FROM SOIL BORINGS
Taken from Reference 4

Sample No.	Boring Number	TPHg (μg/L)	Benzene (μg/L)	Toluene (μg/L)	Ethyl- benzene (μg/L)	Xylenes (μg/L)	TPHd (μg/L)
W1	B1	< 50	< 0.5	< 0.5	< 0.5	<0.5	< 50
W2	B2	53	0.56	< 0.5	< 0.5	1.4	170
W3	B3	< 50	< 0.5	< 0.5	< 0.5	< 0.5	140
W4	B4	< 50	< 0.5	< 0.5	< 0.5	< 0.5	< 50
w5	B5	< 50	< 0.5	< 0.5	< 0.5	< 0.5	170
W6	B6	< 50	< 0.5	< 0.5	< 0.5	< 0.5	160
W7	B7	< 50	1.0	0.52	< 0.5	1.2	< 50
W8	B8	< 50	< 0.5	<0.5	< 0.5	< 0.5	320
W9	B9	78	2.1	< 0.5	< 0.5	5.3	
W10	B10	140,000	2,100	7,700	4,600	27,000	
W11	B11	46,000	55	36	570	3,500	33,000
W12	B12	330,000	1,200	27,000	9,700	61,000	100,000
W12	B13	150,000	1,100	5,500	6,200	37,000	38,000
1	B14	200,000	2,700	61,000	5,900	37,000	84,000
W14	B15	72,000	2,300	3,600	5,200	27,000	5,500
W15	B15	200,000	22,000	69,000	6,300	39,000	6,200

Notes: < = Less than detection limit indicated

THE SAN JOAQUIN COMPANY, INC. 8617 Etcheverry Drive Tracy, CA 95376

TABLE 5 - GROUNDWATER DEPTH INFORMATION
Taken from Reference 5

Weil Number	Date Measured	Casing Elevation (MSL)	Groundwater Depth (feet)	Groundwater Elevation (MSL)
MW-2	09/26/95	6.64	5.20	1.44
2.2.1	10/27/95		5.11	1.53
	11/30/95		5.19	1.45
•	09/04/96		5.05	1.59
•	03/21/97		4.31	2.33
	10/01/97		5.18	1.46
MW-3	09/26/95	7.71	5.71	2.00
*.2	10/27/95		5.81	1.90
	11/30/95		5 .90	1.81
	09/04/96		5.64	2.07
	03/21/97		5.03	2.68
	10/01/97		5.84	1.87
MW-4	09/26/95	6.74	5.39	1.35
4.2	10/27/95		5.43	1.31
	11/30/95		5.51	1.23
	09/04/96		5.28	1.46
	03/27/97		· 4.67	2.07
	10/01/97		5.46	1.28
MW-5	09/26/95	6.73	5.14	1.59
474.17	10/27/95		5.17	1.56
	11/30/95		5.26	1.47
	09/04/96		5.11	1.62
	03/21/97		4.32	2.41
	10/01/97		5.23	1.50

Notes: All measurements in feet relative to MSL

THE SAN JOAQUIN COMPANY, INC...
8617 Etcheverry Drive
Tracy, CA 95376

PROJECT - SPECIFIC HEALTH AND SAFETY PLAN

Project Name: Remediation - 208 Jackson Street, Oakland California

Project No.: 9401.112

Client: SNK Development Inc

Contractor's

Project Manager: H. B. Dietz, REA

Telephone: (209) 832-2910

(209) 482-7769 - Site Mobile Phone

Project Location: 208 Jackson Street, Oakland, California

Project Description:

Remediation of soil affected by gasoline and diesel will be performed by Dietz Irrigation, a licensed general engineering contractor with a hazardous waste sub license. The scope of work includes closure of monitoring wells, installation of replacement monitoring wells, excavation of gasoline and diesel affected soil, on site treatment of affected soil by aeration and bioremediation, backfilling of remedial excavation and compaction during backfill in preparation for site redevelopment. The work will be performed in accordance with the *Remediation Plan-208 Jackson Street, Oakland, California* to which this Site Specific Health and Safety Plan is an attachment. The remediation plan including the Dietz Irrigation master Health and Safety Plan have been submitted to the Oakland Fire Department who is the controlling agency for this remediation. The location of the remedial excavation and areas where contaminated soil may be stockpiled and treated are shown on Figure 9 of the *Remediation Plan*.

Known Hazards:

The principal hazards that are expected to be encountered on this project are those common to demolition of a small steel framed, sheet metal clad building, shallow excavation and general construction work. It is expected that low to moderate concentrations of components of gasoline and diesel fuel will be present in the excavated soil. Underground utilities will be disconnected on site prior to the start of work but underground utilities in the area of the installation of replacement monitoring wells must be carefully located and avoided.

Specific Constructions Hazards

The construction hazards expected to be encountered on this work are those normally associated with demolition of a small steel framed metal clad building, shallow excavation work and the operation of heavy machinery. They include the potential for trauma by suffocation due to burial if the excavation were to collapse, traumatic injury by impact from trucks or heavy machinery, pinching injuries of the extremities, entanglement of extremities and clothing in rotating machinery, injury from falling objects, exposure to noise from machinery, tripping hazards and strains due to lifting heavy objects.

Chemical Hazards

Soil in the subsurface beneath parts of the subject property have been contaminated by a release of fuel hydrocarbons. Local concentrations of total petroleum hydrocarbons quantified as diesel (TPHd) in soil in the subsurface were measured at 1100mg./Kg. (ppm) and concentrations of hydrocarbons quantified as gasoline (TPHg) in soil were measured at 2700mg./Kg. (ppm).

Specific Health and Safety Requirements:

The work required for this project does not involve special hazards beyond those covered by the requirements of the Dietz Irrigation Master Health and Safety Plan that is incorporated herein by reference and a copy of the current edition of which has been submitted to the Oakland Fire Department. All Work will be conducted in compliance with the applicable policies, safety rules and safe working practices set out in the Master Plan. However, for emphasis, the following specific requirements are cited:

Security of Underground Utilities

All utilities in and around the area to be excavated or where monitoring wells will be installed will be located by USA Alert before work is started. The utilities supplying the site will be turned off and secured before any remediation work begins.

Excavation Safety

No personnel shall enter any excavation that has a depth greater than five feet, unless it has been properly shored in compliance with OSHA regulations, or its sides have been sloped back and the excavation approved for entry by a California licensed geotechnical engineer. No spoil or construction materials shall be stockpiled within five feet of the edge of any excavation. The remedial excavation will be restored by backfilling as soon as possible after soil treatment has been completed. During soil treatment the excavation will be backfilled with rock to slightly above the surface of the water table for excavation stability.

Site Access Control

The site is on industrial property that has been vacated and is fenced around its perimeter with chain link fencing. Access to the site will be controlled by lockable gates six foot high and a chain link fence 6 foot high. No persons, vehicles or equipment other than those directly engaged in the work or authorized representatives of the client, project engineers or regulatory agencies shall be permitted to enter the operating area while the work is in progress. All persons entering the work area shall comply with the applicable requirements of the *Master Health and Safety Plan*.

Protective Clothing and Equipment

Based on the hazards known to be present, personal protective requirements for this project correspond to Level D as defined in the *Master Health and Safety Plan*. The following clothing and protective equipment will be used by personnel engaged in the work:

Non conductive safety hat (except when inside equipment).

Steel toed boots.

Safety glasses when performing any operation in which hazards to the eyes exists. Examples are: metal cutting or burning.

Strong non-slip gloves.

(Note - Gloves need not be worn when no identified risk to the hands or chemical injury to the skin exists, or risks due to absorption of a chemical through the skin is known to be present, or when wearing gloves could cause a greater risk).

Lightweight cotton or cotton and synthetic fiber work shirt and pants.

(Note - Neckties, scarves or any loose clothing that might become caught in machinery will not be permitted).

Sanitary Facilities

Portable toilets with hand wash capabilities will be maintained on site.

ALAMEDA COUNTY

FROM : ALAMEDA CO EHS HAZ-OPS

HEALTH CARE SERVICES





DAVID J. KEARS, Agency Director

August 3, 1998

ENVIRONMENTAL HEALTH SERVICES ENVIRONMENTAL PROTECTION 1131 Harbor Bay Parks ay, Suite 250 Alameda, CA 94502-65; 7 (510) 567-6700

Mr. Scott Johnson SNK Development Inc. 185 Berry Street, Suite 1200 San Francisco, CA 94107 STID 3707

RE: 208 Jackson Street, Oakland, CA 94607

Dear Mr. Johnson:

I have reviewed your Remediation Plan dated June 1998 that was prepared by The San Joaquin Company Inc. It is acceptable with the following conditions:

- 1) The cleanup standard with respect to soil remaining in the excavation shall contain a maximum of 0.016 ppm benzene
- 2) Impacted soil treated by aeration and/or bioremediation shall not contain more than 1,000 ppm TPH (diesel), and no PNA's if it is to be returned to the excavation as fill
- 3) Soil samples results must be submitted to this office for review, and prior approval before remediated soil is returned to the excavation as fill
- 4) Remediation progress report must be submitted at a minimum of a quarterly basis
- Alameda County Environment Health, Local Oversite Program is the responsible regulatory authority overseeing this cleanup. The results of the site remediation that will include a RBCA should be sent to this office.

If you have any questions, please contact me at (510) 567-6774.

-15-15

Larry Seto

Sr. Hazardous Materials Specialist

Cc. Bernic Dietz, The San Joaquin Company, 1400 Solano Avenue, Suite 12, Albany, CA 94706-2149

Dai Watkins, The San Joaquin Company. 1400 Solano Avenue, Suite 12, Albany, CA 94706-2149

Leroy Griffin, City of Oakland, Fire Department Files

'ALAMEDA COUNTY

HEALTH CARE SERVICES





DAVID J. KEARS, Agency Director

October 21, 1998

ENVIRONMENTAL HEALTH SERVICES ENVIRONMENTAL PROTECTION (LOP) 113" Harbor Bay Parkway. Suite 250 Alameda, CA 94502-6577 1510) 567-6700 FAX (510) 337-9335

Mr. Scott Johnson SNK Development Inc. 185 Berry Street Suite 1200 San Francisco, CA 94107 STID 3707

RE: 208 Jackson Street, Oakland, CA 94607

Dear Mr. Johnson:

I have reviewed your revised Remediation Plan – Revision 1 – October 1998 for the above site. Included in this Plan are the proposed locations for replacement monitoring wells for MW-4 and MW-5 that were destroyed during the excavation. This revised Plan is acceptable with the understanding that the monitoring wells be monitored a minimum of four quarters during a year of normal rainfall. When this is accomplished, your monitoring program can be re-evaluated.

If you have any questions, please contact me at (510) 567-6774.

Sincerely,

Larry Seto

Sr. Hazardous Materials Specialist

Cc: Bernie Dietz, The San Joaquin Company, 1400 Solano Avenue, Suite 12, Albany, CA 94706-2149

Dai Watkins, The San Joaquin Company, 1400 Solano Avenue, Suite 12, Albany, CA 94706-2149

Leroy Griffin, City of Oakland, Fire Department

HEALTH CARE SERVICES





DAVID / KEARS April ()

ENVIRONMENTAL HEALTH SERVICES

ENVIRONMENTAL PROTECTION (COST 1331 Haltier Bay Parkway, State 250 Aramedric CA 34502-9977 5101-967-970 FAX (5311-331-9335

October 8, 1998

Mr. Bernie Dietz The San Joaquin Company 1400 Solano Avenue, Suite 12 Albany, CA 94706-2149 STID 3707

RE: 208 Jackson Street, Oakland, CA 94607

Dear Mr. Dietz

I have reviewed the laboratory analysis of the aerated soil from stockpile LDS #1. The five samples were non-detect for THP(gas) BTEX and PNA's. TPH (diesel) concentration ranged from 31 to 270 PPM.

It is acceptable to put this soil back into the excavation.

If you have any questions, please contact me at (510) 567-6774.

Sincerely

Larry Seto

Sr Hazardous Materials Specialist

Cc: Mr. Scott Johnson, SNK Development Inc., 185 Berry Street, Suite 1200, San Francisco, CA 94107

ALAMEDA COUNTY

HEALTH CARE SERVICES





DAVID J KEARS. -

October 29, 1998

ENVIRONMENTAL HEALTH SERVICES

ENVIRONMENTAL PROTECTION (LOP) 1131 Harbor Bay Parkway Suite 250 Hameda I GA 94502-6577 111 no.7-6770 FAX: 51 / 1017-9353

Mr. Bernie Dietz The San Joaquin Company 1400 Solano Avenue, Suite 12 Albany, CA 94706-2149 STID 3707

RE:

208 Jackson Street, Oakland, CA 94607

Dear Mr. Dietz:

I have reviewed the laboratory analysis of the aerated soil from stockpile LDS#2. The six samples were non-detect for TPH(gas), BTEX and PNA's. TPH(diesel) concentration ranged from 45 to 260 ppm.

It is acceptable to put this soil back into the excavation.

If you have any questions, please contact me at (510) 567-6774.

Sincerely,

Larry Seto

Sr. Hazardous Materials Specialist

Cc: Mr. Scott Johnson, SNK Development Inc., 185 Berry Street, Suite 1200,

San Francisco, CA 94107

ALAMEDA COUNTY

HEALTH CARE SERVICES







1131 Harbor Bay Parkway Suite 250 Arameda, CA 94502-6577 November 19, 1998

510) 567-6700 FAX (510) 337-9335

ENVIRONMENTAL HEALTH SERVICES ENVIRONMENTAL PROTECTION (LOP)

Mr. Bernie Dietz The San Joaquin Company 1400 Solano Avenue, Suite 12 Albany, CA 94706-2149

RE:

208 Jackson Street, Oakland, CA 94607

Dear: Mr. Dietz:

I have reviewed the laboratory analysis of the aerated soil from stockpile LDS#3. The six samples were non-detect for TPH(gas), BTEX and PNA's. TPH (diesel) concentration ranged from 8.8 to 140 ppm.

It is acceptable to put this soil back into the excavation.

If you have nay questions, please contact me at (510) 567-6774.

Sincerely

Larry Seto

Sr. Hazardous Materials Specialist

Cc. Mr Scott Johnson, SNK Development Inc., 185 Berry Street, Sutie 1200, San Francisco, CA 94107

CITY OF OAKLAND • Office of Planning and Building

1330 Broadway, 2nd Floor, Oakland, CA 94612 • Phone: (510) 238-3443 • FAX (510) 238-2263 PERMIT

Jo	b Site Descr		MADISON 2800 s.		storage	Parcel#	, এ	,		Peri To	trict: mit Is: schedu	pp1# B99 BD-INS0 sued 08, le insp 510) 23	P 02 /04/98 ection	
Wor 31dg Est	k Type Sq Ft Value	DEMOLI 2,800	ITION	#Sto	Jnits ori e s	Soi	anicai: Plans Survey Report	E	Plum nergy struct Occup Z	Calcs Codes oning	isselfe for the second	Classes		
Arc		DIETZ	EVELOPME IRRIGAT ETCHEVER	ION	RACY, CA,	X	(415)4; (209)8;	33-0701	Company of the state of the sta	Market Street		% 94		
	\$232.0 \$232.0 \$.0 \$.0	38 TOTA 00 App 00 Prod 00 Beda 00 Adda 00 SMIR 00 Fire	lic cess coom ress	\$ \$ \$ \$	FILING .00 State .00 School .00 Plot .00 Elect .00 Mechal	ol Plan ric () nical		\$.00 T	OTAL F	EES PA	ID AT	ISSUANC	E	DIST
lans	\$379. \$.0 \$.0	90 Peri 00 Invi 00 Othi 00 Zone	mit stg er a mag e Insp a	\$28 \$37 \$ \$ \$.49 Recd .99 Gen F .00 F1d C .00 Proc	Mgmt Plan Chk	Permit	Issued	ВУ			ate	4-93	ST:ADDRESS
oeci		that f am exemple	from the Contractor		e following reason (Se		I hereby affirm uno	ler penalty of pen	inales	B.V.	D	ate		BSS:—
DER.	structure, pnor to pursuant to the plusmess and Prof Section 7031 i, as owner structure is not adoes not apply this own employs.	o its issuance, all provisions of the provisions Code, 5 by any applical of the property, intended or offere to an Owner of provided the eas, eas, eas, eas, eas, eas, eas, eas,	so requires the applic Contractor's License or that he is exempt at for a permit subject or my employees with kil for sale (Sec. 7044 moperty who builds of a such improvements	cent for such permit to Law Chapter 9 (commit therefrom and the ba- ts the applicant to a crith wages as their soli, Business and Profes r improves thereon, at a are not intended or o	ruct, alter, improve, der, file a signed statemen senoing with Sec. 7000 sis for the alleged exen of penalty of not more to a compensation, will do allege to the Code: The Coding of the Codi	nt that he is licensed of the solution 3 of the inpition. Any violation han \$500) of the work, and the actor's License Law k himself or through ever, the building or	Section 3700 of the	e Labor Code, fo sii mauntain worke	r the performance or's compensatio	e of the work for the insurance, as a	which this permit required by Sect	mpensation, as pri is issued. ion 3700 of the Lai ri insurance carrier	bor Code, for rand policy	OBKER'S
OWNER/BUILD	build or improve It, as owner principal place to the residence to subdivision on in Professions Cool It, as owner of Business and Primproves thereouted business Law)	of the property, of residence or a or the 12 months more than two state) of the 12 months more than two state) of the property, a rofessions Code on, and who cor	of saie). am exempt from the popurenances thereto is proof to the comple nuctures more than completely contract. The Contractor's Loutracts for such projects.	sale requirements of the work will be po- tion of the work, and once during any three- ting with licensed con- cense Law does not a	the above due to: 1) endomed pnor to sale, 141 I have not claime year penod (Section rectors to construct the pply to an owner of prof(s) licensed pursuant	t am improving my 3) I have resided in d exemption in this 7044, Business and is project (Sec 7044, sparty who builds or	anner, so as to b	the performance ecome subject to er's compensatio	e of the work for the worker's com in provisions of S in's compensation outsand dollars (5	which this permit mpensation laws dection 3700 of th in is untawful, and \$100,000-), in ad-	is issued, I shall of California, and e-Labor Code, I i shall subject an dition to the cost	d dallars (\$100 il not employ any p l agree that if I shot shall forthwith comi d employer to comi	D-) or less) person, in any uid become ply with those	COMPENSATION
			honzed Agent		Da		Signature of Owne	r or Authorized A	gent			Oate		
	COMPLY WITH ALL UNDER PENALTY PROPERTY FOR I THE NATURE OF OFFICIAL, UNDER OR WORK AUTHO SECTION 9-2 18 C	I, LOGAL ORDINAN OF LAW 1 HEREI INSPECTION PURPI THE PROJECT OB ITHE PROVISIONS INIZED BY SUCH PE OF THIS CHAPTER	CES AND STATE LAWS BY AUTHORIZE REPREI DSES, EXCEPT IN THOS EIRS THESE UMITATIO OF THIS CODE SHALL FRAIT (OUES NOT RECEI WITHIN 180 DAYS FOL	RELATING TO BUILDING: SENTATIVES OF THIS O SENTATIVES OF THIS O SE CONSTRUCTION PROJ NS TO SE UNREASONAE EXPINE BY LUNTATION A VE AN APPROVAL OF A LOWING THE ISSUANCE	ON GIVEN IS TRUE AND C CONSTRUCTION, AND I MU TY TO ENTER UPON THE ECTS WHERE THE BUILDI ILE EVERY PERMIT ISSU NO BECOME MULL AND I MAJOR INSPECTION AS FL DATE OF SUCH PERMIT	AKE THIS STATEMENT E ABOVE MENTIONED ING OFFICIAL, DUE TO ED BY THE BUILDING JOID IF THE BUILDING HITHER IDENTIFIED IN OR FOLLOWING THE	the work for which the work for which the Lender's Name				uction lending a	gency for the perio	ir Ir	ה האות
APPLIC	APPROVAL DATE IS INSPECTED AN RE REQUIRED A	OF A PREVIOUS M ID THE INSPECTION IT LEAST 24 HOURS to save, defend, from all actions in consequence in otherwise by vi-	AUOR INSPECTION DO P I IS RECORDED ON THE IN ADVANCE OF THE IN	NOT CONCEAL OF COVER BRACK OF THE JOB COP BPECTION.	ANY CONSTRUCTION UP OF THIS PERMIT ALL IN akland and its officers, ings, including those is se or occupancy of an imply with the condition	SPECTION REQUESTS	City I hereby affirm) commencing w ny Ikanse is ii	rith Section (3
¥	Q Owner	Signature of C	Contractor or Owner of	IETZ	I	Date	License # and Class			City Busines	5	····	5	NTRA
	Authorized Age	nt for C	Contractor	Also PRINT NAME	Qo	uner	Contractor's Name				0.1	tone	Š	3

TELEPHONE

Date

CITY

STATE

ZIP

CITY OF OAKLAND • Office of Planning and Building

1330 Broadway, 2nd Floor, Oakland, CA 94612 • Phone: (510) 238-3443 • FAX (510) 238-2263
PERMIT

	Site Descr	207 Demo.	MADISC 50x60 s		storage	Parcel#	xt to 205 Ma	adison	District: B Permit Issu To schedule	ed 08/19/98	3
Scope Wor Bldg Est	k Type Sq Ft Value	Buildi DEMOLI 3,000	ing: YES ITION	Electric #Ur #Stom Const I	nits Ties Type	Soil	anical: NO Plans Survey Report		lics lics des		
Arc	ractor h/Engr Agent	DIETZ	EVELOPME IRRIGAT ETCHEVEF		ACY, CA,	Applent X 95376	Phone# (415)433-01 (209)832-29	701 .	-License C1	asses	
Plans	\$41.0 \$232.0 \$.0 \$.0 \$.0 \$.0 \$.0 \$.0 \$.0 \$.0	O App O Prod O Bedi O Addi O SMIF O Peri O Invo O Cone	lic cess room ress e mit stg	\$.(\$.(\$.(\$.9.(\$39.(\$37.(OO State OO Schoo OO Plot OO Elect OO Mecha OO Plumb OO Recd OO Fld OO Fld OO Proc	Plan ric nical ing Mgmt Tan Coord	\$.00 Permit Issue	o TOTAL FEE		SUANCE = 8-498	DIST: ADDRE
	and Professions C structure prior to i pursuant to the pro Business and Prof of Section 7031 5 i	it I am exempt ode Any city of its issuance also invisions of the C essions Code, of by any applican	from the Contractor r country which red to requires the appli Contractor's License or that he is exempt t for a permit subject	r's License Law for the fo pres a permit to construct, cant for such permit to file Law Chapter 9 (comment; therefrom and the basis it to the applicant to a crivil p	alter, improve, demo a signed statement to long with Sec. 7000) of or the alleged exemple natry of not more that	bish, or repair any that he is licensed of Dryision 3 of the billon Any violation an \$500).	Section 3700 of the Labor Coo	a comment of present to te, for the performance of the worker's compensation insu-	g declarations: senf-insure for worker's ঠুটাৰুছাৰ work for which this permit is is rance, as required by sciolon 37 i. My worker's compensation inst	ued. 700 of the Labor Code, for	SS: WORKE
OWNER/BUILDE	structure is not initiodes not apply to his own employee improvement is abuild of improve to build of improve to principal place of interested not on mo Professions Code! But as owner of the inition o	anded or offerse an Owner of prise. In Owner of prise, provided that id within one yet if the purpose of the property. It may be streamful to the property and the streamful the property, and esseen and who con and who con	a for sale (Sec. 704- openty who builds of I such improvement, air of the completion of sale) am exempt from the point is the complex point to the complex prior to the complex p	ith wages as their sole oc 4, Business and Profession in Improves thereon, and visit a firm of the control of offer in the owner-builder will have a sale requirements of this, 21 the work will be perfet elton of the work, and 4) once during any three-yearting with licensed contractions. Law does not apply exits with a contractions. 8 8 P.C.	ns code. The control was the code to sale if hower with burden of provide a bove due to: 11.1 owned prior to sale.31 I have not claimed if pend (Section 17 to sale owner of proping the sale of the sal	ctor's License Law himself or through yer, the building or ing that he did not am improving my I have resided in exemption in this 044 Business and project (Sec 7044, lefty who builds or	Carner (This section need not to be come subject to the worker's competence.) WARNING Pailure to secure	be completed if the permance of the work for which ect to the worker's compens sation provisions of Section worker's compensation is unled thousand dollars (\$100 or thousand	Policy Number rmit is for one hundred do this permit is issued, I shall not alion laws of California, and agre 3700 of the Labor Code, I shall i lawful, and shall subject and emy 000-), in addition to the cost of or	ollars (\$100-) or less) employ any person, in any e that if I should become forthwith comply with those	R'S COMPENSATION
APPLIC	I CERTIFY THAT I H. COMPLY WITH ALL I UNDER PENALTY CO PROPERTY FOR HIS THE MATURE OF TO OR WORK AUTHOR SECTION 9-2 18 OF APPROVAL DATE OF THE REQUIRED AT I THE REPORT	AVE READ THIS A LOCAL ORDINAM F LAW I HEREB PECTION PURPO RE PROJECT DE REPROJECT D REPROJECT DE REPROJECT D REPROJE	ILS AND STATE LAWS Y AUTHORIZE REPRIS PSES EXCEPT IN THO EMB THESE LIMITATE OF THIS COOK SHALL RIMY DOES NOT RECE WITHIN I BU CAYS FO LUCH INSPECTION DO IS RECORDED ON THE IN ADVANCE OF THE II MOTANIC OF THE II MOTANIC OF THE II OTHER THE	TE THAT THE INFORMATION. RELATING TO BOLDONG CON- SEMIATIVES OF TOUGHTY SE CONSTITUCTION PROJECTS TOWNS TO BE UNREASONABLE EXPINE BY UNITATION AND IVE AM APPROVAL OF A MAKE LLOWING THE ISSUANCE DO INSPECTION. BUTCH THE YOR COPY OF INSPECTION. INS	ISTRUCTION AND I MAN'TO ENTER UPON THE S WHERE THE BUILDING EVERY PERMIT ISSUED BECOME NAJ. AND VC PRINSPECTION AS FUR TE OF SUCH PERMIT CAU THIS PERMIT ALL, INSE THIS PERMIT ALL, INSE and and IIS officers. 8 s. Including liness for occupancy of any	RRECT I AGREE TO KE THIS STATEMENT ABOVE MENTIONER 3 OFFICIAL, DUE TO DO IT WE BUILDING DO IT WE BUILDING THER BU	the work for which this permit is Lander's Name Lander's Address City I hereby affirm that I ar 7000) of Division 3 of 1 and effect. License #	enalty of penury, that there is issued (Sec 3097, Civ C) State Z In licensed under provide Business and Pro	isions of Chapter 9 (completesions Code, and my II) mencing with Section cense is in full force	LENDER CONTRAC
	Owner Authorized Agent Address of Agent	for C	Contractor	DIEIZ AND PRINT NAME	3 // om	198 ner	and Class Contractor's Name	R Nut			ACTOR



removal amounts

SEP 24, 1998

square ft. friable acm

Dietz Irrigation 8617 Etcheverry Dr Tracy, Ca 95376

ACKNOWLEDGEMENT

Bay Area Air Quality Management I Renovation Plan described as:	District acknowledges receipt of your Asbestos Demolition/ Demolition
site address	205 Madison Street Oakland, CA 94607
start date	Aug 3, 1998
completion date	Aug 10, 1998

linear ft.

immediately send a copy to the District by fax or by mail. Do not revise notifications which are

0

exempt or for which you have not yet received acknowledgement.

Should it become necessary to revise this plan, please do so in the spaces provided below and

0

NOTE: This form is not intended as a verification of either the completeness of your original notification or of its compliance with District Regulation 11-2.

Environmental Services (SDB)

September 16, 1998

Submission #: 9809113

DIETZ IRRIGATION

Atten: Bernie Dietz

Project: SNK OAKLAND

Received: September 9, 1998

re: 3 samples for TPH - Diesel analysis.

Method: EPA 8015M

Matrix: SOIL

Extracted: September 11, 1998

Sampled: September 8, 1998 Analyzed: September 12, 1998 Run#: 14844

REPORTING BLANK BLANK DILUTION SPIKE FACTOR DIESEL LIMIT RESULT (mg/Kg) (mg/Kg) CLIENT SPL ID (mg/Kg) (%) 205137 CON S-60

Matrix: SOIL Extracted: September 11, 1998 Sampled: September 8, 1998 Run#: 14844 Analyzed: September 15, 1998

REPORTING BLANK BLANK DILUTION DIESEL LIMIT RESULT SPIKE FACTOR CLIENT SPL ID (mq/Kq)(mg/Kg) (mg/Kg)

N.D.

Matrix: SOIL Extracted: September 11, 1998

Sampled: September 9, 1998 Run#: 14844 Analyzed: September 15, 1998

REPORTING BLANK BLANK DILUTION DIESEL LIMIT RESULT SPIKE (mg/Kq) CLIENT SPL ID (mg/Kg) (mq/Kq) 205138 SP-2A, 2B, 2C, 2D 37 10 N.D.

Note: Hydrocarbon reported is in the late Diesel Range and does not match our Diesel Standard. Surrogate Recoveries biased high due to Hydrocarbon co-

205136 CON S-50

Bruce Hava

Analyst

Environmental Services (SDB)

September 15, 1998

Submission #: 9809113

DIETZ IRRIGATION

Atten: Bernie Dietz

Project: SNK OAKLAND

Received: September 9, 1998

re: One sample for Gasoline BTEX analysis.

Method: SW846 8020A Nov 1990 / 8015Mod

Client Sample ID: CON S-50

Spl#: 205136

Matrix: SOIL

Sampled: September 8, 1998

Run#:14815

Analyzed: September 10, 1998

ANALYTE	RESULT (mg/Kg)	REPORTING LIMIT (mg/Kg)	BLANK RESULT (mg/Kg)	BLANK SPIKE (%)	DILUTION FACTOR
GASOLINE BENZENE TOLUENE ETHYL BENZENE XYLENES	N.D. N.D. N.D. N.D. N.D.	1.0 0.0050 0.0050 0.0050 0.0050	N.D. N.D. N.D. N.D. N.D.	86 95 91 90	1 1 1 1

Vincent Vancil

Analyst

Michael Verona

Environmental Services (SDB)

September 15, 1998

Submission #: 9809113

DIETZ IRRIGATION

Atten: Bernie Dietz

Project: SNK OAKLAND

Received: September 9, 1998

re: One sample for Gasoline BTEX analysis.

Method: SW846 8020A Nov 1990 / 8015Mod

Client Sample ID: CON S-60

Sampled: September 8, 1998 Run#:14882 Analyzed: September 10, 1998

ANALYTE	RESULT (mg/Kg)	REPORTING LIMIT (mg/Kg)	BLANK RESULT (mg/Kg)	BLANK SPIKE (%)	DILUTION FACTOR
GASOLINE	N.D.	1.0	N.D.	82	1
BENZENE	N.D.	0.0050	N.D.	100	1
TOLUENE	N.D.	0.0050	N.D.	98	1
ETHYL BENZENE	N.D.	0.0050	N.D.	98	1
XYLENES	N.D.	0.0050	N.D.	98	1.

Vincent Vancil

Analyst

Michael Verona

Environmental Services (SDB)

September 15, 1998

Submission #: 9809113

DIETZ IRRIGATION

Atten: Bernie Dietz

Project: SNK OAKLAND

Received: September 9, 1998

re: One sample for Gasoline BTEX analysis.

Method: SW846 8020A Nov 1990 / 8015Mod

Client Sample ID: SP-2A,2B,2C,2D

Spl#: 205138 Matrix: SOIL

Sampled: September 9, 1998 Run#:14815 Analyzed: September 10, 1998

ANALYTE	RESULT (mg/Kg)	REPORTING LIMIT (mg/Kg)	BLANK RESULT (mg/Kg)	BLANK SPIKE (%)	DILUTION FACTOR
GASOLINE	N.D.	1.0	N.D.	86	1
BENZENE	N.D.	0.0050	N.D.	95	1
TOLUENE	N.D.	0.0050	N.D.	90	1
ETHYL BENZENE	N.D.	0.0050	N.D.	91	1
XYLENES	N.D.	0.0050	N.D.	90	1

∜incent Vancil

Analyst

Michael Verona

41872

CHROMALAB, INC.

海护的 井。 5.40万月3 放射性 化

Chain of Custody

Environmental Services (SDB) (DOHS 1094)

ULIBHE'S LIETZ 49 16798

DATE 2-1 78 _____ PAGE _____ OF ____ EFT MASSETT **ANALYSIS REPORT** COMPANY DIETZ IRRIGATION PURGEABLE AROMATICS
BTEX (EPA 602, 8020)
PURGEABLE HALOCARBONS
(EPA 601, 8010) SAMPLERS (SIGNATURE) 209-832-2910 (PHONE NO.) ź CONTAINERS BASE/NEUTRALS, ACIDS (EPA 625/627, 8270, 525) VOLATILE ORGANICS (EPA 624, 8240, 524.2) TOTAL OIL & GREASE (EPA 5520, 8+F, E+F) (EPA 608, 8080) LUFT METALS: Cd, C P NUMBER SAMPLE ID. MATRIX PRESERV. 7-8 98 434720 Soil None X 1N 5-60 1-8-98 3:13/19 5P - 2A 7-9-58 1:13 119 X 57 = 2B 5, - 20 2. 7.98 2:60 1/13 5/2 20 7-7-18 214/1 RELINQUISHED BY H.B. Duety PROJECT INFORMATION RELINQUISHED BY RELINQUISHED BY SAMPLE RECEIPT PROJECT NAME

JNK Oakland TOTAL NO OF CONTAINERS (SIGNATURE) (TIME) (SIGNATURE) PROJECT NUMBER **HEAD SPACE** 9/9A REC'D GOOD CONDITION/COLD DICTZ IRR (PRINTED NAME) (PRINTED NAME) (DATE) P.O. # CONFORMS TO RECORD STANDARD (COMPANY) OTHER RECEIVED BY (LABORATORY) 3

When fauly 524

(SKINATURE)

HELANDE Tavels 9/9/4

(PRINTEDNAME)

CHICKEN (DATE) RECEIVED BY RECEIVED BY composite 572 A, B, C, D (SIGNATURE) (SIGNATURE) (TIME) (IME) (PRINTED NAME) (PRINTED NAME) (COMPANY) (COMPANY)

Environmental Service (SDB)

Sample Receipt Checklist

Client Name: DIETZ IRRIGATION	Date/Tim	ne Rece	eived:	09/0	9/98	115	21
Reference/Submis: 41872 9809113	Received	d by: _	AP			·	
Checklist completed by: Vignature	1598 Date	Rev	riewed	by: .	Ap	9/15	1/98
1	name: CA	~=>				ats t	eace .
Shipping container/cooler in good condition?		Yes L	No			ent .	
Custody seals intact on shipping container/cooler?		Yes	No	errore desired ha		ent .	شد
Custody seals intact on sample bottles?		Yes	No		Not Pres	ent .	_
Chain of custody present?				Yes		No _	
Chain of custody signed when relinquished and receiv	ed?			Yes		No _	
Chain of custody agrees with sample labels?				Yes		No _	
Samples in proper container/bottle?				Yes		No _	
Sample containers intact?				Yes		No _	
fficient sample volume for indicated test?				Yes		No _	
All samples received within holding time?				Yes		No _	
Container/Temp Blank temperature in compliance?		Temp:	<u>-1</u> °c	Yes		No _	<u></u>
Water - VOA vials have zero headspace? No VO	A vials su	bmitted		Yes		No _	
Water - pH acceptable upon receipt? Adju	sted?	Che	cked by		-bomio# d	Fan VOA	
Any No and/or NA (not applicable) response must be d	etailed in	the co	mments a	sectio	n belo	w.	
Client contacted: Date contacted:	<u>.</u>	Person	contac	ted:			
Contacted by: Regarding:			····				
Comments: 50mple received out of stan 2-6 °C.	ndand t	tenne	alter	110	ank	6/	
2-6°C. 1		/			J	0	
	······································						
							
Corrective Action:							

Environmental Services (SDB)

September 22, 1998

Submission #: 9809148

DIETZ IRRIGATION

Atten: Bernie Dietz

Project: SNK-OAKLAND

Received: September 11, 1998

re: One sample for Gasoline BTEX analysis.

Method: SW846 8020A Nov 1990 / 8015Mod

Client Sample ID: CON W-50

Spl#: 205510 Matrix: SOIL Sampled: September 10, 1998 Run#:14883

Analyzed: September 15, 1998

ANALYTE	RESULT (mg/Kg)	REPORTING LIMIT (mg/Kg)	BLANK RESULT (mg/Kg)	BLANK SPIKE (%)	DILUTION FACTOR
GASOLINE	N.D.	1.0	N.D.	85	1
BENZENE	N.D.	0.0050	N.D.	97	1
TOLUENE	N.D.	0.0050	N.D.	94	1
ETHYL BENZENE	N.D.	0.0050	N.D.	97	1
XYLENES	N.D.	0.0050	N.D.	94	1

Vincent Vancil

Analyst

Michael Verona

Environmental Services (SDB)

September 22, 1998

Submission #: 9809148

DIETZ IRRIGATION

Atten: Bernie Dietz

Project: SNK-OAKLAND

Received: September 11, 1998

re: One sample for Gasoline BTEX analysis.

Method: SW846 8020A Nov 1990 / 8015Mod

Client Sample ID: CON W-50-S25

Analyzed: September 15, 1998

		REPORTING	BLANK	BLANK	DILUTION
	RESULT	LIMIT	RESULT	SPIKE	FACTOR
ANALYTE	(mg/Kg)	(mg/Kg)	(mg/Kg)	(%)	
GASOLINE	N.D.	1.0	N.D.	85	1
BENZENE	N.D.	0.0050	N.D.	97	1
TOLUENE	N.D.	0.0050	N.D.	94	1
ETHYL BENZENE	0.023	0.0050	N.D.	97	1
XYLENES	0.029	0.0050	N.D.	94	1.

Vincent Vancil

Analyst

Michael Verona

Environmental Services (SDB)

September 22, 1998

DIETZ IRRIGATION

Atten: Bernie Dietz

Project: SNK-OAKLAND

Received: September 11, 1998

re: One sample for Gasoline BTEX analysis.

Method: SW846 8020A Nov 1990 / 8015Mod

Client Sample ID: CON W-50-S50

Spl#: 205512 Matrix: SOIL

Sampled: September 10, 1998 Run#:14927 Analyzed: September 15, 1998

ANALYTE	RESULT (mg/Kg)	REPORTING LIMIT (mg/Kg)	BLANK RESULT (mg/Kg)	BLANK : SPIKE (%)	DILUTION FACTOR
GASOLINE	N.D.	1.0	N.D.	83	1
BENZENE	N.D.	0.0050	N.D.	104	1
TOLUENE	N.D.	0.0050	N.D.	102	1
ETHYL BENZENE	N.D.	0.0050	N.D.	99	1
XYLENES	N.D.	0.0050	N.D.	104	1

Vincent Vancil

Analyst

Michael Verona

Operations Manager

Submission #: 9809148

Environmental Services (SDB)

September 22, 1998

Submission #: 9809148

DIETZ IRRIGATION

Atten: Bernie Dietz

Project: SNK-OAKLAND

Received: September 11, 1998

re: One sample for Gasoline BTEX analysis.

Method: SW846 8020A Nov 1990 / 8015Mod

Client Sample ID: CON S75 W-25

Spl#: 205513

Matrix: SOIL

Sampled: September 10, 1998 Run#:14883

Analyzed: September 15, 1998

	RESULT	REPORTING LIMIT	BLANK RESULT	BLANK I SPIKE	DILUTION FACTOR
ANALYTE	(mg/Kg)	(mg/Kg)	(mg/Kg)	(왕)	
GASOLINE	N.D.	1.0	N.D.	85	1
BENZENE	N.D.	0.0050	N.D.	97	1
TOLUENE	N.D.	0.0050	N.D.	94	1
ETHYL BENZENE	N.D.	0.0050	N.D.	97	1
XYLENES	N.D.	0.0050	N.D.	94	1

Vincent Vancil

Analyst

Verona

Environmental Services (SDB)

September 22, 1998

Submission #: 9809148

DIETZ IRRIGATION

Atten: Bernie Dietz

Project: SNK-OAKLAND

Received: September 11, 1998

re: One sample for Gasoline BTEX analysis.

Method: SW846 8020A Nov 1990 / 8015Mod

Client Sample ID: CON W-75/7'

Spl#: 205514 Matrix: SOIL

Sampled: September 10, 1998 Run#:15007 Analyzed: September 21, 1998

ANALYTE	RESULT (mg/Kg)	REPORTING LIMIT (mg/Kg)_	BLANK RESULT (mg/Kg)	BLANK SPIKE (%)	DILUTION FACTOR
GASOLINE	N.D.	1.0	N.D.	107	1
BENZENE	1.4	0.62	N.D.	88	1
TOLUENE	1.3	0.62	N.D.	84	1
ETHYL BENZENE	0.94	0.62	N.D.	81	1
XYLENES	2.3	0.62	N.D.	90	1

Note: Hydrocarbon found in Gasoline Range is uncharacteristic of Gasoline

Profile. If quantified using Gasoline's response factor, concentration

would equal 860mg/Kg.

Vincent Vancil

Analyst

Michael Verona

Environmental Services (SDB)

September 22, 1998

Submission #: 9809148

DIETZ IRRIGATION

Atten: Bernie Dietz

Project: SNK-OAKLAND

Received: September 11, 1998

re: One sample for Gasoline BTEX analysis.

Method: SW846 8020A Nov 1990 / 8015Mod

Client Sample ID: CON W-75/10'

Spl#: 205515 Matrix: SOIL

Sampled: September 10, 1998 Run#:14883 Analyzed: September 15, 1998

ANALYTE	RESULT (mg/Kg)	REPORTING LIMIT (mg/Kg)	BLANK RESULT (mg/Kg)	BLANK SPIKE (%)	DILUTION FACTOR
GASOLINE	N.D.	1.0	N.D.	85	1
BENZENE	N.D.	0.0050	N.D.	97	1
TOLUENE	N.D.	0.0050	N.D.	94	1
ETHYL BENZENE	N.D.	0.0050	N.D.	97	1
XYLENES	N.D.	0.0050	N.D.	94	1

Hydrocarbon found in Gasoline Range is uncharacteristic of Gasoline Profile. If quantified using Gasoline's response factor, concentration

would equal 1.0mg/Kg.

Vincent'Vancil

Analyst

Environmental Services (SDB)

September 18, 1998

Submission #: 9809148

DIETZ IRRIGATION

Atten: Bernie Dietz

Project: SNK-OAKLAND

Received: September 11, 1998

re: 6 samples for TPH - Diesel analysis.

Method: EPA 8015M

Matrix: SOIL

Extracted: September 16, 1998

Sampled: September 10, 1998 Run#: 14916 Analyzed: September 16, 1998

REPORTING BLANK BLANK DILUTION LIMIT DIESEL RESULT SPIKE FACTOR CLIENT SPL ID (mg/Kg) (mg/Kg) (mg/Kg) (%) 205514 CON W-75/7' 16000 500 500 N.D. 83.6

Note: Hydrocarbon reported does not match the pattern of our Diesel Standard.

Surrogate diluted out.

Matrix: SOIL

Extracted: September 16, 1998

Sampled: September 10, 1998 Run#: 14916 Analyza

Analyzed: September 18, 1998

	DIESEL	REPORTING LIMIT	BLANK RESULT	BLANK SPIKE	DILUTION FACTOR
Spl# CLIENT SPL ID	(mq/Kg)	(mg/Kg)	(mg/Kg)	(%)	
205510 CON W-50	N.D.	1.0	N.D.	83.6	1
205511 CON W-50-S25	N.D.	1.0	N.D.	83.6	1
205512 CON W-50-S50	N.D.	1.0	N.D.	83.6	1
205513 CON S75 W-25	N.D.	1.0	N.D.	83.6	1
205515 CON W-75/10'	N.D.	1.0	N.D.	83.6	1

Carolyn House

Analyst

Bruce Havlik

Analyst

Environmental Services (SDB)

September 16, 1998

Submission #: 9809148

DIETZ IRRIGATION

Atten: Bernie Dietz

Project: SNK-OAKLAND

Received: September 11, 1998

re: One sample for Reactivity, Corrositivity, and Ignitability (RCI)

analysis.

Method: CA TITLE 22 SEC 66261.21-.24

Client Sample ID: BT

Spl#: 205516

Matrix: SOIL

Sampled: September 10, 1998 Run#:

14922

Analyzed: September 16, 1998

Dampied, Deptember 10, 15	JO παπη.	1,720 E	maxy acc.	CCPCCIIICCL	10, 2000
-		REPORTING	BLANK	BLANK	DILUTION
	RESULT	LIMIT	RESULI	: SPIKE	FACTOR
ANALYTE	(N/A)	(N/A)	(N/A)	(%)	
REACTIVITY	NO	N/A	NO		
CORROSIVITY	6.27	0.1	6.81		
IGNITABILITY	NO	N/A	NO		

Lulu Frazier

Analvst

Michael Verona

Chain of Custody

CHROMALAB, INC. DATE 9-16 58 PAGE / OF F Environmental Services (SDB) (DOHS 1094) ANALYSIS REPORT PROJ MGR _ # 15 Die 12 PURGEABLE HALOCARBONS (EPA 601, 8010) Ż. BASE/NEUTRALS, ACIDS (EPA 625/627, 8270, 525) PRIORITY POLLUTANT METALS (13) TPH - Diesel, TEPH (EPA 3510/3550, 8015) VOLATILE ORGANICS (EPA 624, 8240, 524.2) TOTAL OIL & GREASE (EPA 5520, 8+F, E+F) LUFT METALS: Cd, Cr, Pb, CAM METALS (17) PCB (EPA 608, 8080) PESTICIDES (EPA 608, 8080) EXTRACTION (TCLP, STLC) TOTAL LEAD (PHONE NO.) (FAX NO.) DATE TIME MATRIX PRESERV. SAMPLE IU. CLN 16-31 7-16 88 8.52 pm 50.1 160 45-525 91-18 936 AM Del Con a so- Sie 7-0.98 16 2611 7011 Cer 5-75 Un-21 9-12-76 12-111 Suil BT 9-10-12 3.00701 Selid CON 4-1/ 7-7-72 9,00 m 101/ Cod 11-15 1-11 96 4.60 mm Sol Y642 2 RELINQUISHED BY PROJECT INFORMATION 1 RELINDUISHED BY SAMPLE RECEIPT PROJECT NAME TOTAL NO OF CONTAINERS SNK - GAKIAN & (SIGNATURE) (TIME) (SIGNATURE) DATE PRINTED NAMES

9-11-98 Chymalab

1:47 1917 (COMPANY) **HEAD SPACE** MATE PRINTED NAME REC'D GOOD CONDITION/COLD P.O. # CONFORMS TO RECORD (COMPANY) STANDARD 72 OTHER 2 RECEIVED BY (LABORATORY) SPECIAL INSTRUCTIONS/COMMENTS Salimpen (TIME) (SIGNATURE) (TIME) (SIGNATURE) Saliniferia (PHINTED NAME) (DATE) (PRINTED NAME) Magralah 9/11/98 9.53 COMPANY

Environmental Services (SDB)

November 12, 1998

Submission #: 9809198

DIETZ IRRIGATION

Atten: Bernie Dietz

Project: SNK OAKLAND

Received: September 15, 1998

re: One sample for Gasoline BTEX analysis.

Method: SW846 8020A Nov 1990 / 8015Mod

Client Sample ID: CON S75-100W

Spl#: 206093 Matrix: SOIL

Sampled: September 14, 1998 Run#:14942

Analyzed: September 17, 1998

	RESULT	REPORTING LIMIT	BLANK RESULT	BLANK SPIKE	DILUTION FACTOR
ANALYTE	(mg/Kg)	(mg/Kg)	(mg/Kg)	(%)	
GASOLINE	N.D.	1.0	N.D.	86	1
BENZENE	N.D.	0.0050	N.D.	102	1
TOLUENE	N.D.	0.0050	N.D.	99	1
ETHYL BENZENE	N.D.	0.0050	N.D.	99	1
XYLENES	N.D.	0.0050	N.D.	100	1

Vincent Vancil

Analyst

Michael Verona

Environmental Services (SDB)

November 12, 1998

Submission #: 9809198

DIETZ IRRIGATION

Atten: Bernie Dietz

Project: SNK OAKLAND

Received: September 15, 1998

re: One sample for Gasoline BTEX analysis.

Method: SW846 8020A Nov 1990 / 8015Mod

Client Sample ID: CON W75-50

Spl#: 206094 *Matrix:* SOIL Sampled: September 15, 1998 Run#:14942

Analyzed: September 17, 1998

ANALYTE	RESULT (mg/Kg)	REPORTING LIMIT (mg/Kg)	BLANK RESULT (mg/Kg)	BLANK SPIKE (%)	DILUTION FACTOR
GASOLINE	N.D.	1.0	N.D.	86	1
BENZENE	N.D.	0.0050	N.D.	102	1
TOLUENE	N.D.	0.0050	N.D.	99	1
ETHYL BENZENE	N.D.	0.0050	N.D.	99	1
XYLENES	N.D.	0.0050	N.D.	100	1

Vincent Vancil

Analyst

Michael Verona

Environmental Services (SDB)

November 12, 1998

Submission #: 9809198

DIETZ IRRIGATION

Atten: Bernie Dietz

Project: SNK OAKLAND

Received: September 15, 1998

re: One sample for Gasoline BTEX analysis.

Method: SW846 8020A Nov 1990 / 8015Mod

Client Sample ID: CON S70-W100

Sampled: September 15, 1998 Run#:15007 Analyzed: September 22, 1998

	RESULT	REPORTING LIMIT	BLANK RESULT	BLANK I SPIKE	DILUTION FACTOR
ANALYTE	(mg/Kg)	(mg/Kg)	(mg/Kg)	(%)	
GASOLINE	29	10	N.D.	107	1
BENZENE	N.D.	0.62	N.D.	88	1
TOLUENE	N.D.	0.62	N.D.	84	1
ETHYL BENZENE	N.D.	0.62	N.D.	81	1
XYLENES	1.2	0.62	N.D.	90	1

Vincent Vancil

Analyst

Michael Verona Operations Manager

209-833-1288

Environmental Services (SDB)

November 12, 1998

Submission #: 9809198

DIETZ IRRIGATION

Atten: Bernie Dietz

Project: SNK OAKLAND

Received: September 15, 1998

re: One sample for Gasoline BTEX analysis.

Method: SW846 8020A Nov 1990 / 8015Mod

Client Sample ID: CON \$50-W100

Spl#: 206096 Matrix: SOIL

Sampled: September 15, 1998 Run#:14944 Analyzed: September 17, 1998

		REPORTING	BLANK	BLANK	DILUTION
	RESULT	LIMIT	RESULT	SPIKE	FACTOR
ANALYTE	(mg/Kg)	(mg/Kg)	(mg/Kg)	(%)	
GASOLINE	N.D.	1.0	N.D.	84	1
BENZENE	N.D.	0.0050	N.D.	96	1
TOLUENE	N.D.	0.0050	N.D.	91	1
ETHYL BENZENE	N.D.	0.0050	N.D.	92	1
XYLENES	N.D.	0.0050	N.D.	90	1.

Vincent Vancil

Analyst

Michael Verona

Environmental Services (SDB)

November 12, 1998

Submission #: 9809198

DIETZ IRRIGATION

Atten: Bernie Dietz

Project: SNK OAKLAND

Received: September 15, 1998

re: One sample for Gasoline BTEX analysis.

Method: SW846 8020A Nov 1990 / 8015Mod

Client Sample ID: CON W100-S25

Matrix: SOIL Spl#: 206097 Sampled: September 15, 1998 Run#:15015

Analyzed: September 17, 1998

		REPORTING	BLANK	BLANK :	DILUTION
	RESULT	LIMIT	RESULT	SPIKE	FACTOR
ANALYTE	(mg/Kg)	(mg/Kg)	(mg/Kg)	(%)	
GASOLINE	N.D.	1.0	N.D.	90	1
BENZENE	N.D.	0.0050	N.D.	103	1
TOLUENE	N.D.	0.0050	N.D.	101	1
ETHYL BENZENE	N.D.	0.0050	N.D.	101	1
XYLENES	N.D.	0.0050	N.D.	102	1

Vincent Vancil

Analyst

Michael Verona Operations Manager

Environmental Services (SDB)

November 12, 1998

Submission #: 9809198

DIETZ IRRIGATION

Atten: Bernie Dietz

Project: SNK OAKLAND

Received: September 15, 1998

re: One sample for Gasoline BTEX analysis.

Method: SW846 8020A Nov 1990 / 8015Mod

Client Sample ID: CON W100

Spl#: 206098 Mat

Matrix: SOIL

Sampled: September 15, 1998 Run#:14944

Analyzed: September 17, 1998

ANALYTE	RESULT (mg/Kg)	REPORTING LIMIT (mg/Kg)	BLANK RESULT (mg/Kg)	BLANK SPIKE (%)	DILUTION FACTOR
GASOLINE	N.D.	1.0	N.D.	84	1
BENZENE	N.D.	0.0050	N.D.	96	1
TOLUENE	N.D.	0.0050	N.D.	91	1
ETHYL BENZENE	N.D.	0.0050	N.D.	92	1
XYLENES	N.D.	0.0050	N.D.	90	1

Vincent Vancil

Analyst

Michael Verona

1401198/206 50 3- 10

CHROMALAB, INC.

Chain of Custody

Environmental Services (SDB) (DOLIS 1094) itz IRRIGATION C PESTICIAL CONTROL OF STATE O SÁPÍ LÍ ÚŠ (SIGHAÍÐING) ;; 6; 3.00 1.00 BATE TIME MATRIX PRESERV. ПI Wite 5 25 73-8 1017 Am Seil 9-11 12 11.44/m M.B. Du NEEMONISHED BY TOTAL NO OF CONTAINENS SNK O. AL. I HEAD SPACE PUNITED HAVES P () # DWARE CONTRACT COM ORMS TO RECORD KIDSTATE) DIHER RECEIVED BY Report II Boutles Hisvel 7 Hisvel 1 Ulaval 4 SPECIAL INSTRUCTIONS/COMMENTS

Environmental Services (SDB)

September 22, 1998

Submission #: 9809198

DIETZ IRRIGATION

Atten: Bernie Dietz

Project: SNK OAKLAND

Received: September 15, 1998

re: 6 samples for TPH - Diesel analysis.

Method: EPA 8015M

Matrix: SOIL Extracted: September 17, 1998

Sampled: September 14, 1998 Run#: 14938 Analyzed: September 21, 1998

Matrix: SOIL Extracted: September 17, 1998

Sampled: September 15, 1998 Run#: 14938 Analyzed: September 19, 1998

		DIESEL	REPORTING LIMIT	BLANK RESULT	BLANK SPIKE	DILUTION FACTOR
Spl#	CLIENT SPL ID	(mg/Kg)	(mg/Kg)	(mg/Kg)	(%)	
206096	CON S50-W100	N.D.	1.0	N.D.	75.6	1
206098	CON W100	N.D.	1.0	N.D.	75.6	1

Matrix: SOIL Extracted: September 17, 1998

Sampled: September 15, 1998 Run#: 14938 Analyzed: September 21, 1998

Spl# CLIENT SPL	DIESEL ID (mg/Kg)	REPORTING LIMIT	BLANK RESULT	SPIKE	DILUTION FACTOR
PDIH CUIFNI PER	ID (mq/Kq)	(mg/Kg)	(mg/Kg)	(%)	
206094 CON W75-50	N.D.	1.0	N.D.	75.6	1
206095 CON S70-W10	00 N.D.	1.0	N.D.	75.6	1
206097 CON W100-S2	25 2.3	1.0	N.D.	75.6	1

Note: Hydrocarbon reported does not match the pattern of our Diesel Standard.

Carolyn House

Ana//yst

Bruce Havlik Analyst

Environmental Services (SDB)

September 22, 1998

Submission #: 9809198

DIETZ IRRIGATION

Atten: Bernie Dietz

Project: SNK OAKLAND

Received: September 15, 1998

re: One sample for BTEX analysis.

Method: SW846 8020A Nov 1990

Client Sample ID: CON W100

Spl#: 206098 Sampled: September 15, 1998 Run#:14944

Matrix: SOIL

Analyzed: September 17, 1998

ANALYTE	RESULT (mg/Kg)	REPORTING LIMIT (mg/Kg)	BLANK RESULT (mg/Kg)	SPIKE (%)	DILUTION FACTOR
BENZENE	N.D.	0.0050	N.D.	96	1
TOLUENE	N.D.	0.0050	N.D.	91	1
ETHYL BENZENE	N.D.	0.0050	N.D.	92	1
XYLENES	N.D.	0.0050	N.D.	90	1

Vincent Vancil

Analyst

Michael Verona

Environmental Services (SDB)

September 22, 1998

Submission #: 9809198

DIETZ IRRIGATION

Atten: Bernie Dietz

Project: SNK OAKLAND

Received: September 15, 1998

re: One sample for BTEX analysis.

Method: SW846 8020A Nov 1990

Client Sample ID: CON W100-S25

Sp1#: 206097

Matrix: SOIL

Sampled: September 15, 1998 Run#:15015 Analyzed: September 17, 1998

ANALYTE	RESULT (mg/Kg)	REPORTING LIMIT (mg/Kg)	BLANK RESULT (mg/Kg)	BLANK DESPIKE DESPIKE DESPIKE DESPIKE DESPIKE DESPIES	ILUTION FACTOR
BENZENE	N.D.	0.0050	N.D.	103	1
TOLUENE	N.D.	0.0050	N.D.	101	1
ETHYL BENZENE	N.D.	0.0050	N.D.	101	1
XYLENES	N.D.	0.0050	N.D.	102	1

Vincent Vancil

Analyst

Michael Verona

Operations Manager

VINCE 15:03

Environmental Services (SDB)

September 22, 1998

Submission #: 9809198

DIETZ IRRIGATION

Atten: Bernie Dietz

Project: SNK OAKLAND

Received: September 15, 1998

re: One sample for BTEX analysis.

Method: SW846 8020A Nov 1990

Client Sample ID: CON S50-W100

Spl#: 206096

Matrix: SOIL

Sampled: September 15, 1998 Run#:14944

Analyzed: September 17, 1998

ANALYTE	RESULT (mg/Kg)	REPORTING LIMIT (mg/Kg)	BLANK RESULT (mg/Kg)	BLANK SPIKE (%)	DILUTION FACTOR
BENZENE	N.D.	0.0050	N.D.	96	1
TOLUENE	N.D.	0.0050	N.D.	91	1
ETHYL BENZENE	N.D.	0.0050	N.D.	92	1
XYLENES	N.D.	0.0050	N.D.	90	1

Vincent Vancil

Analyst

Michael Verona

Environmental Services (SDB)

September 22, 1998

Submission #: 9809198

DIETZ IRRIGATION

Atten: Bernie Dietz

Project: SNK OAKLAND

Received: September 15, 1998

re: One sample for BTEX analysis.

Method: SW846 8020A Nov 1990

Client Sample ID: CON S70-W100

Spl#: 206095

Matrix: SOIL

Sampled: September 15, 1998 Run#:15007

Analyzed: September 22, 1998

ANALYTE	RESULT (mg/Kg)	REPORTING LIMIT (mg/Kg)	BLANK RESULT (mg/Kg)	BLANK SPIKE (%)	FACTOR
BENZENE	N.D.	0.62	N.D.	88	1
TOLUENE	N.D.	0.62	N.D.	84	1
ETHYL BENZENE	N.D.	0.62	N.D.	81	1
XYLENES	1.2	0.62	N.D.	90	1

Vincent Vancil

Analyst

Michael Verona

Environmental Services (SDB)

September 22, 1998

Submission #: 9809198

DIETZ IRRIGATION

Atten: Bernie Dietz

Project: SNK OAKLAND

Received: September 15, 1998

re: One sample for BTEX analysis.

Method: SW846 8020A Nov 1990

Client Sample ID: CON S75-100W

Sp1#: 206093

Matrix: SOIL

Sampled: September 14, 1998 Run#:14942

Analyzed: September 17, 1998

ANALYTE	RESULT (mg/Kg)	REPORTING LIMIT (mg/Kg)	BLANK RESULT (mg/Kg)	BLANK : SPIKE (%)	DILUTION FACTOR
BENZENE	N.D.	0.0050	N.D.	102	1
TOLUENE	N.D.	0.0050	N.D.	99	1
ETHYL BENZENE	N.D.	0.0050	N.D.	99	1
XYLENES	N.D.	0.0050	N.D.	100	1

Vincent Vancil

Analyst

Operations Manager

VINCE 15:03

Environmental Services (SDB)

September 22, 1998

Submission #: 9809198

DIETZ IRRIGATION

Atten: Bernie Dietz

Project: SNK OAKLAND

Received: September 15, 1998

re: One sample for BTEX analysis.

Method: SW846 8020A Nov 1990

Client Sample ID: CON W75-50

Spl#: 206094

Matrix: SOIL

Sampled: September 15, 1998 Run#:14942 Analyzed: September 17, 1998

ANALYTE	RESULT (mg/Kg)	REPORTING LIMIT (mg/Kg)	BLANK RESULT (mg/Kg)	BLANK I SPIKE (%)	FACTOR
BENZENE	N.D.	0.0050	N.D.	102	1
TOLUENE	N.D.	0.0050	N.D.	99	1
ETHYL BENZENE	N.D.	0.0050	N.D.	99	1.
XYLENES	N.D.	0.0050	N.D.	100	1

Vincent Vancil

Analyst

Michael Verona

Operations Manager

VINCE 15:03

9909198/206 893-99

CHROMALAB, INC.

3000 7. 600104 FM 16 Grands Bull 62 37 02007 02780 Reference #: Y984

Chain of Custody

Environmental Services (SDB) (DOHS 1094) PROJEMOR CAM 17 METALS (EPA 5010/7470/747) PNA's by C 8270 C Seec. SÁMPLÉRIS ISIGNATURET ¥ E.T aп MATHIX PRESERV. 00 αa 7 11 18 7 5 pm W 12 5 25 7 8 18 27.00 - 1 // 48/m MELINOUISHED BY DELINIOUSSIED UY RELINQUISHED BY TOTAL HO OF CONTAINEDS 3NK a. /1. i HIMEL. HEAD SPACE PRINTED HAVES DAMILED HAMEL POF DIETT IRR COM ONMS TO RECOND STANDARD 72 DIMER 5 UAY **RECEIVED BY** HECEINED BY ILABORATORY) NECENED BY Report: 13 Routine Ulavel 2 | 1) Level 3 Ulavel 4 SPECIAL INSTRUCTIONS/COMMENTS PONATHIE Dexander Paveler

Environmental Services (SDB)

September 24, 1998

Submission #: 9809266

DIETZ IRRIGATION

Atten: Bernie Dietz

Project: SNK-OAKLAND

Received: September 18, 1998

re: One sample for Gasoline BTEX analysis.

Method: SW846 8020A Nov 1990 / 8015Mod

Client Sample ID: CON E60-S80

Spl#: 206768

Matrix: SOIL

Sampled: September 18, 1998 Run#:15052

Analyzed: September 21, 1998

ANTA I APPE	RESULT (mg/Kg)	REPORTING LIMIT (mg/Kg)	BLANK RESULT (mg/Kg)	BLANK SPIKE (%)	DILUTION FACTOR
ANALYTE GASOLINE BENZENE TOLUENE ETHYL BENZENE XYLENES	N.D. N.D. N.D. N.D. N.D.	1.0 0.0050 0.0050 0.0050 0.0050	N.D. N.D. N.D. N.D.	90 93 89 92 91	1 1 1 1

Vincent Vancil

Analyst

Michael Verona

Environmental Services (SDB)

September 24, 1998

DIETZ IRRIGATION

Atten: Bernie Dietz

Project: SNK-OAKLAND

Received: September 18, 1998

re: One sample for Gasoline BTEX analysis.

Method: SW846 8020A Nov 1990 / 8015Mod

Client Sample ID: CON E45-S80

Spl#: 206767

Matrix: SOIL

Sampled: September 18, 1998 Run#:15052

Analyzed: September 21, 1998

Submission #: 9809266

3 3 7 3 7 TUTE	RESULT (mg/Kg)	REPORTING LIMIT (mg/Kg)	BLANK RESULT (mg/Kg)	BLANK DI SPIKE F (%)	ACTOR
ANALYTE GASOLINE BENZENE TOLUENE ETHYL BENZENE XYLENES	N.D. N.D. N.D. N.D. N.D.	1.0 0.0050 0.0050 0.0050 0.0050	N.D. N.D. N.D. N.D. N.D.	90 93 89 92 91	1 1 1 1

Vincent Vancil

Analyst

Operations Manager

VINCE 10:07

Environmental Services (SDB)

September 24, 1998

Submission #: 9809266

DIETZ IRRIGATION

Atten: Bernie Dietz

Project: SNK-OAKLAND

Received: September 18, 1998

re: One sample for Gasoline BTEX analysis.

Method: SW846 8020A Nov 1990 / 8015Mod

Client Sample ID: CON E25-S80

Sp1#: 206766 Matrix: SOIL

Sampled: September 18, 1998 Run#:15052 Analyzed: September 21, 1998

A 272 F 37000	RESULT (mg/Kg)	REPORTING LIMIT (mg/Kg)	BLANK RESULT (mg/Kg)	BLANK SPIKE (%)	FACTOR
ANALYTE GASOLINE BENZENE TOLUENE ETHYL BENZENE	N.D. N.D. N.D. N.D.	1.0 0.0050 0.0050 0.0050	N.D. N.D. N.D. N.D.	90 93 89 92	1 1 1 1
XYLENES	0.072	0.0050	N.D.	91	1

Note:

Hydrocarbon found in Gasoline Range is uncharacteristic of Gasoline Profile. If quantified using Gasoline's response factor, concentration

would equal 53mg/Kg.

Vincent Vancil

Analyst

Michael Verona

Environmental Services (SDB)

September 28, 1998

Submission #: 9809266

DIETZ IRRIGATION

Atten: Bernie Dietz

Project: SNK-OAKLAND

Received: September 18, 1998

re: 3 samples for TPH - Diesel analysis.

Method: EPA 8015M

Matrix: SOIL Extracted: September 22, 1998

Sampled: September 18, 1998 Run#: 15002 Analyzed: September 22, 1998

		DIESEL	REPORTING LIMIT	BLANK RESULT	BLANK SPIKE	DILUTION FACTOR
Spl# CLIE	ENT SPL ID	(mg/Kg)	(mg/Kg)	(mg/Kg)	(%)	
206766 CON		360	1.0	N.D.	113	1
Note:		reported does not				
	Standard.Sur	crogate Recoveries	biased high d	lue to Hydrod	arbon	co-elution.
206767 CON		4.3	1.0	N.D.	113	1
Note:	Hydrocarbon	reported does not	match the pat	tern of our	Diesel	Standard.
06768 CON	E60-S80	N.D.	1.0	N.D.	113	1

Carolyn House

Analyst

Bruce Havlik Analyst 73092 in 1000/00-69

CHROMALAB, INC.

STATE THE STATE OF (1) 13 (173 - 7 351 Zelja 1 9 1 11 11 11 11

Nelerence #: 42056

Chain of Custody

Environn	—— mntal Servi	lons (SVV)	(DOHS 10	94)	ì	15.	. (:	••								DAT	r <u></u>	-/	8-9	<u> </u>	PAGT			н	<u></u>
rnoj nga	-1	· · · · · · · · · · · · · · · · · · ·				A					,		AN	LYSIS	HEP	1Ht									ļ
PHOT HGH	······································	2 - 1 -	· · · · ·			l _{v7}			SNS			tu	18.11											İ	
COMPANY 7 6 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7		ک انت	<u></u>		12 38 F	E	£ 23	N. O	ARB(▼ 82	n		EASE F)	H 4	30801				-							II U
. ,	<u></u>		- 6		802(10M	801	5X.	9 6	ANIC 260)		е <u>п</u>	RABI S (E)	801	55	, P	5	LS 7471							7
SÁNÍFLÉRÍS (SIGNATURE)			(f)	IONÉ NO I	8015.3020)	14 A	EPA	801 001	HAI	ORG 8 A'	II E	AND	BON	S (EP	ig W	35.0	NI.S	ETA 7470/	04		ch.				0
•				X 110.)	A X	PURGEABLE AROMATICS BTEX (EPA 8020)	TPH-Diesel (EPA 8015M)	TEPH (EPA 8015M)	PURGEABLE HALOCARBONS (HVOC*) (EPA8010 bv 8260)	VOLATILE ORGANICS (VOCS) (EPA 8260)	GLA 2701	TOTAL OIL AND GREA ISM 5520 B - F. E - F)	TOTAL RECOVERABLE HYDROCARBONS (EPA	C PESTICIDES(EPA 8 CI PCS'S (EPA 9080)	PNA's by C 8270	pH C Spec. Cand	Cd. Cr. Pb. Ni. Zn	CAM 17 METALS (EPA 6010/7470/74	TOTAL LEAD	H _a	ides to			ļ	E E
					TPH-IEPA	I SE X	Ä	T S	RGE VOC	40	PA 8	N S	TAL	P. S. S.	NA.	Hg 7 SST	JFT !	₹ 4 d	oTo.	W.E.T	10			İ	¥C)¥8£
SAMPLE ID.	HATE	TIME	MATRIX	PRESERV.	<u> </u>	ā. ⁽¹⁾	F-	FÖ	3.5	2 <	SE	ĻΩ	보	00	<u> </u>	00	50		<u></u>	<u>,</u>				·	
CON E23-580	911-91	1/-11/1/11	5:/	 	χ		X													10	r †				
CW / 61.50		1	1		X		×												<i>.</i> ;	10	- <i>4</i>				/
CAN E60.30					*		*									<u>.</u>			7	1/20	1				
Corles Floor	9/11/0	2116				-			 																7
4,400,400,	7/0/7	1 (14)			 -										<u> </u>	ļ									
	ļ	<u> </u>		77.7	ļ	<u> </u>			 	<u> </u>				ļ		<u> </u>			ļ	ļ					
																	Ì								
				ı																					
	<u> </u>				1	1		-		ļ	 	ļ 				 	1				<u> </u>				
PHUJEST INFUHA	ATION	<u> </u>	HAM F	le Hecei	3		RELI	HOUISI	IED BY	<u></u>	1	<u></u>	I I IIE	rman	SHEDI]	<u> </u>	L	/ 2 1	TE L HOO	DISHED	l IIY			<u></u> /
HED LECT INFORM THE REST HAVE	\sim	JATOL	no or co			3		H.3	DIZ	K	3	10							I I	_	_ `		•	٠, ٠	, , ,
The section of the se	, _\	HEAD	SPACE				(SIGH	AJUNE	٦.,			linu	1 150	(PIATO)	ti		,	 	iui)	ranakti	<u>пт)</u>	7 1	<u> </u>	<u> </u>	गर्जा
PO F	· · · · · · · · · · · · · · · · · · ·	1	ERATURE								- 4/	N/9 3)	witton	ÁME I	<u> </u>		171	A111	10000	HANT)	1.11	1.1	به بر ب برین	र र कर्मा
		com	onus to n	conv			Di	ÉT2	1/2	R						1		11,7	1	-	<u></u>			.415	-31
TAT STANDARD 5 DAY	1	ĺ	24	18 72	01	пеп		l'Attrij			-))Kff*Aff#]						COMPAN	(1)				
Report: U Routine U Lev	ret 2 Illes	vel 3 U te	val 4		1		HECE	NED B	14 ////	//	Ź,		. I NE	CEMEU	BY				2 1	ieceivi <i>12.</i>	ם) אמונו: א	ABORA Ž	1001	17	· (')
SPECIAL INSTRUCTIONS/C	OMMENTS:	ł	10%	. 10					100	14/		S (Ind	<u>/</u> 1, हिण्ट	JIAKIT V	·			, <u>, , , , , , , , , , , , , , , , , , </u>	ikiti t		$\frac{\sqrt{f^2}}{\sqrt{1+f^2}}$	/we	Ken_		
		7		/ ₩			_/>	, , ′	* 1	- 11/	91	<u> </u>								Ale		ave.	lej	9/18	1/90
		./	5.frebe	2-			(()	IED HAN	(E) (75)	10/	:/	31Ach	' V"	MIĘD N	ME)			(i)	(III) p	101111)	HALIET Lanc	nl			(ATE)
							1000			ביין ביי	J		/	:;					- 1	ناس	-	0			- 1

Environmental Services (SDB)

September 18, 1998

Submission #: 9809090

DIETZ IRRIGATION

Atten: H.B.DIETZ

Project: SNK OAKLAND

Received: September 8, 1998

re: One sample for Gasoline BTEX analysis.

Method: SW846 8020A Nov 1990 / 8015Mod

Client Sample ID: CON-00

Spl#: 204780

Matrix: SOIL

Sampled: September 8, 1998 Run#:14973

Analyzed: September 8, 1998

ANALYTE	RESULT (mg/Kg)	REPORTING LIMIT (mg/Kg)	BLANK RESULT (mg/Kg)	BLANK SPIKE (%)	DILUTION FACTOR	
GASOLINE	2.5	1.1	N.D.	87	1	
BENZENE	0.015	0.0050	N.D.	96	1	
TOLUENE	0.0067	0.0050	N.D.	93	1	
ETHYL BENZENE	0.19	0.0050	N.D.	95	1	
XYLENES	0.98	0.0050	N.D.	94	1	

Vincent Vancil

Analyst

Michael Verona

Operations Manager

VINCE 18 07

Environmental Services (SDB)

September 18, 1998

Submission #: 9809090

DIETZ IRRIGATION

Atten: H.B.DIETZ

Project: SNK OAKLAND

Received: September 8, 1998

re: One sample for Gasoline BTEX analysis.

Method: SW846 8020A Nov 1990 / 8015Mod

Client Sample ID: CON-S25

Spl#: 204781 Sampled: September 8, 1998 Matrix: SOIL

Run#:14737

Analyzed: September 8, 1998

ANALYTE	RESULT (mg/Kg)	REPORTING LIMIT (mg/Kg)	BLANK RESULT (mg/Kg)	SPIKE (%)	DILUTION FACTOR
GASOLINE	N.D.	1.0	N.D.	96	1
BENZENE	N.D.	0.0050	N.D.	97	1
TOLUENE	N.D.	0.0050	N.D.	94	1
ETHYL BENZENE	N.D.	0.0050	N.D.	97	1
XYLENES	N.D.	0.0050	N.D.	94	1

Vincent Vancil

Analyst

Michael Verona

Environmental Services (SDB)

September 18, 1998

DIETZ IRRIGATION

Atten: H.B.DIETZ

Project: SNK OAKLAND

Received: September 8, 1998

re: One sample for Gasoline BTEX analysis.

Method: SW846 8020A Nov 1990 / 8015Mod

Client Sample ID: CON-W25

Spl#: 204782 Sampled: September 8, 1998 Matrix: SOIL

Run#:14800 Analyzed: September 8, 1998

ANALYTE	RESULT (mg/Kg)	REPORTING LIMIT (mg/Kg)	BLANK RESULT (mg/Kg)	BLANK SPIKE (%)	DILUTION FACTOR
GASOLINE	N.D.	1.0	N.D.	88	1
BENZENE	N.D.	0.0050	N.D.	99	1
TOLUENE	N.D.	0.0050	N.D.	95	1
ETHYL BENZENE	0.0087	0.0050	N.D.	96	1
XYLENES	N.D.	0.0050	N.D.	95	1

Vincent Vancil

Analyst

Michael Verona/

Operations Manager

Submission #: 9809090

Environmental Services (SDB)

September 9, 1998

Submission #: 9809090

DIETZ IRRIGATION

Atten: H.B.DIETZ

Project: SNK OAKLAND

Received: September 8, 1998

re: One sample for Gasoline BTEX analysis.

Method: SW846 8020A Nov 1990 / 8015Mod

Client Sample ID: CON-S25-W25

Analyzed: September 8, 1998

ANALYTE	RESULT (mg/Kg)	REPORTING LIMIT (mg/Kg)	BLANK RESULT (mg/Kg)	BLANK : SPIKE (%)	DILUTION FACTOR
GASOLINE	1.8	1.0	N.D.	87	1
BENZENE	0.17	0.0050	N.D.	96	1
TOLUENE	N.D.	0.0050	N.D.	104	1
ETHYL BENZENE	0.46	0.0050	N.D.	94	ī
XYLENES	0.023	0.0050	N.D.	94	ī

Vincent Vancil

Analyst

Michael Verona

Environmental Services (SDB)

September 15, 1998

Submission #: 9809090

DIETZ IRRIGATION

Atten: H.B.DIETZ

Project: SNK OAKLAND

Received: September 8, 1998

re: 4 samples for TPH - Diesel analysis.

Method: EPA 8015M

Matrix: SOIL

Extracted: September 9, 1998

Analyzed: September 9, 1998

Sampled: September 8, 1998 Run#:

Run#: 14763

REPORTING BLANK BLANK DILUTION DIESEL LIMIT RESULT SPIKE FACTOR (mg/Kg) (mg/Kg) Spl# CLIENT SPL ID (mq/Kq)(%) 63.9204783 CON-S25-W25 N.D.

Note: Hydrocarbon reported is in the early Diesel Range and does not match our

Diesel Standard.

Matrix: SOIL

Extracted: September 9, 1998

Sampled: September 8, 1998 Run#: 14763 Analyzed: September 12, 1998

•				REPORTING	BLANK		DILUTION
Spl#	CLIENT SPL	ID	DIESEL (mg/Kg)	LIMIT (mg/Kg)	RESULT (mg/Kg)	SPIKE (%)	FACTOR
204780	CON-00		N.D.	1.0	N.D.	63.9	1
204781	CON-S25		N.D.	1.0	N.D.	63.9	1
204782	CON-W25		N.D.	1.0	N.D.	63.9	1

Carolyn House

Anályst

Bruce Havlik

Analyst

Environmental Services (SDB)

September 10, 1998

Submission #: 9809090

DIETZ IRRIGATION

Atten: H.B.DIETZ

Project: SNK OAKLAND

Received: September 8, 1998.

re: 1 sample for TPH - Diesel analysis.

Method: EPA 8015M

Matrix: SOIL Ex

Extracted: September 9, 1998

Sampled: September 8, 1998 Run#: 14763 Analyzed: September 9, 1998

REPORTING BLANK BLANK DILUTION DIESEL RESULT LIMIT SPIKE FACTOR CLIENT SPL ID (mg/Kg) (mg/Kg)(mg/Kg) (%) 204783 CON-S25-W25 4.41.0 N.D.

Note: Hydrocarbon reported is in the early Diesel Range and does not match our Diesel Standard.

Carolyn/House

Analyst

Bruce Havlik

Analyst

9809090 1 204780-104783

1/1832

CHROMALAB, INC.

Environmental Services (SDB) (DOHS 1094)

Chain of Custody

DATE 9-2-51 PAGE 1 OF 1 **ANALYSIS REPORT** H.B DIETZ COMPANY DIETZ IRRIGATION ADDRESS S617 Etchevery Dr Tracy CA 95376 NUMBER OF CONTAINERS LUFT WETALS: Cd, Cr, Pb, SAMPLERS (SIGNATURE) 209 - 832 - 2910 (PHONE NO.) DATE TIME MATRIX PRESERV. 209- 28531288(FAX NO.) SAMPLE ID. (cm 2: 7-2 75 9:45 PM Sey/ ON -00 CON - 528 5-8-88 167800 2011 Vere CON -525 Con - 16 25 1.898/1,000 Soil 668-528 6 15 8 X X // Billy Soll 1 RELINQUISHED BY **PROJECT INFORMATION** SAMPLE RECEIPT RELINQUISHED BY 2 RELINQUISHED BY FRINTED NAME)

DIETZ

FRINTED NAME)

THE SIGNATURE)

FRINTED NAME)

THE SAN JOSEPH (PRINTED NAME)

THE SAN JOSEPH (PRINTED NAME) TOTAL NO OF CONTAINERS SNK Oakland PROJECT NUMBER **HEAD SPACE** REC'D GOOD CONDITION/COLD PRINTED NAME) (DATE) P.O. # CONFORMS TO RECORD (COMPANY) STANDARD 2 REGEIVED BY (LABORATORY) 3

LICE Consider Parely 125

(TIME) (SIGNATURE) TUMES

HEXALIZED NAME) (DATE)

CONTROL LAB OTHER 5-DAY RECEIVED BY RECEIVED BY SPECIAL INSTRUCTIONS/COMMENTS Sample - CON \$ 525-W25 (SIGNATURE) (SIGNATURE) TAT = 24 hrs. all other IDATE) (PRINTED NAME) PRINTED NAME Samples Standard TAT (COMPANY) (COMPANY)

Environmental Services (SDB)

September 21, 1998

Submission #: 9809174

DIETZ IRRIGATION

Atten: Bernie Dietz

Project: SNK OAKLAND

Received: September 14, 1998

re: 4 samples for TPH - Diesel analysis.

Method: EPA 8015M

Matrix: SOIL Extracted: September 16, 1998

Sampled: September 11, 1998 Run#: 14916 Analyzed: September 19, 1998

REPORTING BLANK BLANK DILUTION DIESEL LIMIT RESULT SPIKE FACTOR CLIENT SPL ID (mg/Kg) (mg/Kg) (mg/Kg) 205870 CON S75-W25

Extracted: September 16, 1998 Matrix: SOIL

Sampled: September 14, 1998 Run#: 14916 Analyzed: September 19, 1998

p1#	CLIENT SPL ID	DIESEL (mg/Kg)	REPORTING LIMIT (mg/Kg)	BLANK RESULT (mg/Kg)	BLANK SPIKE (%)	DILUTION FACTOR
205871	CON W75-S25	N.D.	1.0	N.D.	83.6	1
205872	CON S75-W50	N.D.	1.0	N.D.	83.6	<u></u>
205873	CON W75-S75	N.D.	1.0	N.D.	83.6	ī

Analyst

Environmental Services (SDB)

September 16, 1998

Submission #: 9809174

DIETZ IRRIGATION

Atten: Bernie Dietz

Project: SNK OAKLAND

Received: September 14, 1998

re: One sample for Gasoline BTEX analysis.

Method: SW846 8020A Nov 1990 / 8015Mod

Client Sample ID: CON W75-S75

Spl#: 205873 *Matrix:* SOIL

Sampled: September 14, 1998 Run#:14882 Analyzed: September 15, 1998

		REPORTING	BLANK		DILUTION
	RESULT	LIMIT	RESULT	SPIKE	FACTOR
ANALYTE	(mg/Kg)	(mg/Kg)	(mg/Kg)	(%)	
GASOLINE	N.D.	1.0	N.D.	82	1
BENZENE	N.D.	0.0050	N.D.	100	1
TOLUENE	N.D.	0.0050	N.D.	98	1
ETHYL BENZENE	N.D.	0.0050	N.D.	98	1
XYLENES	N.D.	0.0050	N.D.	98	1

Vincent Vancil

Analyst

Operations Manager

VINCE 14:11

Environmental Services (SDB)

September 16, 1998

Submission #: 9809174

DIETZ IRRIGATION

Atten: Bernie Dietz

Project: SNK OAKLAND

Received: September 14, 1998

re: One sample for Gasoline BTEX analysis.

Method: SW846 8020A Nov 1990 / 8015Mod

Client Sample ID: CON S75-W50

Analyzed: September 15, 1998

		REPORTING	BLANK	BLANK D	ILUTION
	RESULT	LIMIT	RESULT	SPIKE	FACTOR
ANALYTE	(mg/Kg)	(mg/Kg)	(mg/Kg)	(%)	
GASOLINE	N.D.	1.0	N.D.	82	1
BENZENE	N.D.	0.0050	N.D.	100	1.
TOLUENE	N.D.	0.0050	N.D.	98	1
ETHYL BENZENE	N.D.	0.0050	N.D.	98	1
XYLENES	N.D.	0.0050	N.D.	98	1

Vincent Vancil

Analyst

Michael Verona

Environmental Services (SDB)

September 16, 1998

Submission #: 9809174

DIETZ IRRIGATION

Atten: Bernie Dietz

Project: SNK OAKLAND

Received: September 14, 1998

re: One sample for Gasoline BTEX analysis.

Method: SW846 8020A Nov 1990 / 8015Mod

Client Sample ID: CON W75-S25

Analyzed: September 15, 1998

	DWCIII W	REPORTING LIMIT	BLANK RESULT	BLANK SPIKE	DILUTION FACTOR
ANALYTE	RESULT (mg/Kg)	(mg/Kg)	(mg/Kg)	(%) PLIVE	FACIOR
GASOLINE	N.D.	1.0	N.D.	82	1
BENZENE	N.D.	0.0050	N.D.	100	1.
TOLUENE	N.D.	0.0050	N.D.	98	1
ETHYL BENZENE	N.D.	0.0050	N.D.	98	1
XYLENES	N.D.	0.0050	N.D.	98	1

Vincent Vancil

Analyst

Michael Verona

Environmental Services (SDB)

September 16, 1998

Submission #: 9809174

DIETZ IRRIGATION

Atten: Bernie Dietz

Project: SNK OAKLAND

Received: September 14, 1998

re: One sample for Gasoline BTEX analysis.

Method: SW846 8020A Nov 1990 / 8015Mod

Client Sample ID: CON S75-W25

Matrix: SOIL Sp1#: 205870 Sampled: September 11, 1998 Run#:14882

Analyzed: September 15, 1998

ANALYTE	RESULT (mg/Kg)	REPORTING LIMIT (mg/Kg)	BLANK RESULT (mg/Kg)	BLANK SPIKE (%)	DILUTION FACTOR
GASOLINE	N.D.	1.0	N.D.	82	1
BENZENE	N.D.	0.0050	N.D.	100	1
TOLUENE	N.D.	0.0050	N.D.	98	1
ETHYL BENZENE	N.D.	0.0050	N.D.	98	1
XYLENES	N.D.	0.0050	N.D.	98	1

Vincent Vancil

Analyst

41952

Chain of Custody

Environmental Service	es (SDB) (DOHS 1094)			98	09.	104	L				DATE	<u>- 11 - 5</u>	<u>y</u>		PAGE _		(or/	_
PROJ MGR COMPANY 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	32-2910 (PHONE 33:1288 (FAX NO TIME MATHIX PRES	TPH - Casoline (EPA 5030, 8015)	FPH - Casoline (5030, 8013) W/BTEX (EPA 602, 8020) TPH - Diesel, TEPH	(EPA 3510/3550, 8015) PURGEABLE AROMATICS BTEX (EPA 602, 8020)	PURGEABLE HALOCARBONS (EPA 601, 8010)	(EPA 624, 8240, 524.2) 8ASE/NEUTRALS, ACIDS FPA 625/627, 8270, 525)	TOTAL OIL & GREASE (EPA 5520, 8+F, E+F)		PESTICIDES (EPA 608, 8080) 65	TOTAL RECOVERABLE HYDROCARBONS (EPA 418.1)	LUFT METALS: Cd, Cr, Pb, Zn, Ni	CAM METALS (17)	PRIORITY POLLUTANT METALS (13)	TOTAL LEAD	EXTRACTION (TCLP, STLC)				
Con 575-4-5 3-11-78 1			γ· >												1,	é C 7			_
Car (125-52) 7-14-98 1	i i		× ;	\times				- 1							9	Fee	+		_
Cin 575 - w 56 7-14 98														<u> </u>	۶	Fee	£		
Low Wiss-> 75 9-18-92			V												7	f & &	+		
																			_
																<u> </u>			
PROJECT INFORMATION	SAMPLE F		A RE	LINOUISH	ED BY	-	, 1		LINOUIS	SHED BY	,		12	HELINC	DUISHE	D BY	·	, 75	
PROJECT NAME SUK OUKLAND. FROJECT NUMBER	HEAD SPACE	News .	- is	H.B. GNATUREI H.B. FINITED HAN DICT	× D		(TIME	i) (SK	GNATURE	<u> </u>			(JME)	ISIONAT	กันย	<u> </u>		· · · · · · · · · · · · · · · · · · ·	1
P.O. *	REC'D GOOD CONDITIO	DN/COLD		H · D .	SURY IEI /RR		(DATE		AN LED HY	AME)	-		DATE)	PPINTE	D NAME)	5/1	مبري	6 / 11 The state of the state o)
Total Page 1	CONFORMS TO RECOR		I (C	DICTE OMPANY	/KK	-	<u> </u>	· ;	OMPANY	 ,	/			COMPA	INT	7/1	,/	<u></u> -	_
SPECIAL INSTRUCTIONS/COMMENTS	24 48	72 OTH	ER	ECEIVED B	Y		· 1	BE	CENED	ВУ					VED BY				
			rs	GNATURE)	<u> </u>	P. C.	TIME	(S)	GNATURE	()			(TIME)	FERREST		<u> 2021</u> D	Jan D	elin	1
,			_	FINTED HAN	ME) (J.	<u> 18 57.</u>	(DATE		DINTED N	AME)			(BIAO)		D NAME		rave	de	,
			- - -	OMPANY	62 -	not the		-/ [OMPANY					(LAB)	con	ala	6		-

Environmental Services (SDB)

October 7, 1998

Submission #: 9809423

DIETZ IRRIGATION

Atten: Bernie Dietz.

Project: SNK OAKLAND

Received: September 29, 1998

re: 5 samples for TPH - Diesel analysis.

Method: EPA 8015M

Matrix: SOIL Extracted: October 1, 1998

Sampled: September 29, 1998 Run#: 15183 Analyzed: October 1, 1998

REPORTING BLANK BLANK DILUTION DIESEL LIMIT RESULT SPIKE FACTOR Spl# CLIENT SPL ID (mg/Kg) (ma/Ka) (mg/Kg) 208214 LDS-1 E4 31 1.0 N.D. 69.4

Note: Hydrocarbon reported does not match the pattern of our Diesel Standard.

Matrix: SOIL Extracted: October 1, 1998 Sampled: September 29, 1998 Run#: 15183 Analyzed: October 2, 1998

REPORTING BLANK BLANK DILUTION

 Spl#
 CLIENT SPL ID
 (mg/Kg)
 (mg/Kg)
 (mg/Kg)
 (mg/Kg)
 (mg/Kg)
 (%)

 208213
 LDS-1
 D3
 140
 1.0
 N.D.
 69.4
 1

Note: Hydrocarbon reported does not match the pattern of our Diesel Standard. 208215 LDS-1 B2 120 1.0 N.D. 69.4 1

Note: Hydrocarbon reported does not match the pattern of our Diesel Standard.

Surrogate high due to matrix interference.

208216 LDS-1 A4 38 1.0 N.D. 69.4 1 Note: Hydrocarbon reported does not match the pattern of our Diesel Standard.

208217 LDS-1 El 270 1.0 N.D. 69.4 1

Note: Hydrocarbon reported does not match the pattern of our Diesel Standard.

Carolyn House

Analyst

Bruce Havlik

Analyst

Environmental Services (SDB)

October 6, 1998

Submission #: 9809423

DIETZ IRRIGATION

Atten: Bernie Dietz.

Project: SNK OAKLAND

Received: September 29, 1998

re: One sample for Gasoline BTEX analysis.

Method: SW846 8020A Nov 1990 / 8015Mod

Client Sample ID: LDS-1 D3

Spl#: 208213 Matrix: SOIL

Sampled: September 29, 1998 Run#:15194 Analyzed: September 30, 1998

		REPORTING	BLANK	BLANK	DILUTION
	RESULT	LIMIT	RESULT	SPIKE	FACTOR
ANALYTE	(mg/Kg)	(mg/Kg)	(mg/Kg)	(%)	
GASOLINE	N.D.	1.0	N.D.	93	1
BENZENE	N.D.	0.0050	N.D.	111	1
TOLUENE	N.D.	0.0050	N.D.	109	1
ETHYL BENZENE	N.D.	0.0050	N.D.	112	1
XYLENES	N.D.	0.0050	N.D.	111	1

Vincent Vancil

Analyst

Michael Verona

Environmental Services (SDB)

October 6, 1998

Submission #: 9809423

DIETZ IRRIGATION

Atten: Bernie Dietz.

Project: SNK OAKLAND

Received: September 29, 1998

re: One sample for Gasoline BTEX analysis.

Method: SW846 8020A Nov 1990 / 8015Mod

Client Sample ID: LDS-1 E4

Spl#: 208214 Matrix: SOIL

Sampled: September 29, 1998 Run#:15194 Analyzed: September 30, 1998

ANALYTE	RESULT (mg/Kg)	REPORTING LIMIT (mg/Kg)	BLANK RESULT (mg/Kg)	BLANK SPIKE (%)	DILUTION FACTOR
GASOLINE	N.D.	1.0	N.D.	93	1.
BENZENE	N.D.	0.0050	N.D.	111	1
TOLUENE	N.D.	0.0050	N.D.	109	1.
ETHYL BENZENE	N.D.	0.0050	N.D.	112	1
XYLENES	N.D.	0.0050	N.D.	111	1
		Λ Λ Λ			

Vincent Vancil

Analyst

Michael Verona

Environmental Services (SDB)

October 6, 1998

Submission #: 9809423

DIETZ IRRIGATION

Atten: Bernie Dietz.

Project: SNK OAKLAND

Received: September 29, 1998

re: One sample for Gasoline BTEX analysis.

Method: SW846 8020A Nov 1990 / 8015Mod

Client Sample ID: LDS-1 B2

Analyzed: September 30, 1998

ANALYTE	RESULT (mg/Kg)	REPORTING LIMIT (mg/Kg)	BLANK RESULT (mg/Kg)	BLANK SPIKE (%)	DILUTION FACTOR
GASOLINE	N.D.	1.0	N.D.	93	1
BENZENE	N.D.	0.0050	N.D.	111	1
TOLUENE	N.D.	0.0050	N.D.	109	1
ETHYL BENZENE	N.D.	0.0050	N.D.	112	1
XYLENES	N.D.	0.0050	N.D.	111	1

Note: Surrogate Recoveries demonstrate Matrix interference.

Vincent Vancil

Analyst

Michael Verona

Environmental Services (SDB)

October 6, 1998

Submission #: 9809423

DIETZ IRRIGATION

Atten: Bernie Dietz.

Project: SNK OAKLAND

Received: September 29, 1998

re: One sample for Gasoline BTEX analysis.

Method: SW846 8020A Nov 1990 / 8015Mod

Client Sample ID: LDS-1 A4

Analyzed: September 30, 1998

ANALYTE	RESULT (mg/Kg)	REPORTING LIMIT (mg/Kg)	BLANK RESULT (mg/Kg)	BLANK SPIKE (%)	DILUTION FACTOR
GASOLINE	N.D.	1.0	N.D.	92	1
BENZENE	N.D.	0.0050	N.D.	100	1
TOLUENE	N.D.	0.0050	N.D.	97	1
ETHYL BENZENE	N.D.	0.0050	N.D.	98	1
XYLENES	N.D.	0.0050	N.D.	97	1

Note: Surrogate Recoveries demonstrate Matrix interference.

Vincent Vancil

Analyst

Michael Verona

Environmental Services (SDB)

October 6, 1998

Submission #: 9809423

DIETZ IRRIGATION

Atten: Bernie Dietz.

Project: SNK OAKLAND

Received: September 29, 1998

re: One sample for Gasoline BTEX analysis.

Method: SW846 8020A Nov 1990 / 8015Mod

Client Sample ID: LDS-1 E1

Analyzed: September 30, 1998

	RESULT	REPORTING LIMIT	BLANK RESULT	BLANK SPIKE	DILUTION FACTOR
ANALYTE	(mg/Kg)	(mg/Kg)	(mq/Kg)	(%)	
GASOLINE	N.D.	1.0	N.D.	93	1
BENZENE	N.D.	0.0050	N.D.	111	1
TOLUENE	N.D.	0.0050	N.D.	109	1
ETHYL BENZENE	N.D.	0.0050	N.D.	112	1
XYLENES	N.D.	0.0050	N.D.	111	1

Note: Surrogate Recoveries demonstrate Matrix interference.

Vincent Vancil

Analyst

Michael Verona

Environmental Services (SDB)

October 5, 1998

Submission #: 9809423

DIETZ IRRIGATION

Atten: Bernie Dietz.

Project: SNK OAKLAND

Received: September 29, 1998

re: One sample for Polynuclear Aromatic Hydrocarbons (PAHs) analysis.

Method: SW846 Method 8270A Nov 1990

Client Sample ID: LDS-1 D3, E4, B2, A4, E1

Spl#: 208212 Matrix: SOIL Extracted: October 2, 1998 Sampled: September 29, 1998 Run#: 15220 Analyzed: October 2, 1998

ANALYTE	RESULT	REPORTING LIMIT (mg/Kg)	BLANK RESULT (mg/Kg)	BLANK : SPIKE (%)	DILUTION FACTOR
NAPHTHALENE	N.D.	0.10	N.D.		1
ACENAPHTHYLENE	N.D.	0.10	N.D.		ī
ACENAPHTHENE	N.D.	0.10	N.D.	86.5	$\bar{1}$
FLUORENE	N.D.	0.10	N.D.		<u> </u>
PHENANTHRENE	N.D.	0.10	N.D.		ī
ANTHRACENE	N.D.	0.10	N.D.		ī
FLUORANTHENE	N.D.	0.10	N.D.		ī
PYRENE	N.D.	0.10	N.D.	91.8	ī
BENZO (A) ANTHRACENE	N.D.	0.10	N.D.		ī
CHRYSENE	N.D.	0.10	N.D.		1
BENZO (B) FLUORANTHENE	N.D.	0.10	N.D.		1
BENZO (K) FLUORANTHENE	N.D.	0.20	N.D.		1
BENZO (A) PYRENE	N.D.	0.050	N.D.		ī
INDENO(1,2,3-CD)PYRENE	N.D.	0.20	N.D.		1
DIBENZO (A, H) ANTHRACENE	N.D.	0.20	N.D.		1
BENZO (GHI) PERYLENE	N.D.	0.20	N.D.		ī

Michael Lee Analyst Michael Verona

9809423 Juge 17-17

THE SAN JOAQUIN COMPANY Inc.

8617 Etcheverry Drive, Tracy, CA 95376 Voice: (209)-832-2910 Fax. (209)-833-1288

☐ 1400 Solano Ave No. 12, Albany CA 94706 Voice (510)-444-1248 Fax: (510)-444-1296 SUBM #: 9809423 REP: GCLEV2

CLIENT: SANJOAQINCO

JE: 10/06/98

REF #:42239

REQUEST FOR ANALYSIS RECORD

Project: SNK Dapland Project No.: Sampling Team: Dietz/Miller Bryant				Laboratory: Chr.em.del Carrier: NA D.G. IRR Waybill No.: N/A							
Sample No.	Туре	Sampling Locati	on I	Date Sampled	Time Sampled		nalyses Requeste		Lab. No.		
LD3-7 BJ	Soil	Treation to	ed	9/17	1.55 pm	TPhy+01	Ex Tohd				
DS/ E4	-				2:00p.				2 1		
051 BZ					1:470						
USI EI				<u> </u>	1:430		-				
		·									
LDS/ Comp	2 Te					PNA S	82U				
note	C02-42524	Lu 5 sample 1 s	i alovi	·							
	120										
Sample Hazards	. 5 no 10	les ack				TAT: Routi	ne 🔯 Expe	dited 🗆	Special 🗆		
Notes.							-				
CUSTODY RE		Print Name	Company		red Time Received			shed Signat	ture		
Originator:	1	17 Dista	Deta IRA	C. 9-29-9.	8 15:37	9-29-98	/ 5 3 7	1/- 1/- 1/- 1/-	my		
Received/ Relin	iquished by.	J. BRYPHT JR	· · · · · · · · · · · · · · · · · · ·	4	1535	·	· · · · · · · · · · · · · · · · · · ·	1274	Ingat fr.		
Received/ Relin	nquished by										
Received/ Relin	nquished by.	*** -									
Received at	oratory by:			4							

Environmental Services (SDB)

October 19, 1998

Submission #: 9810254

DIETZ IRRIGATION

Atten: Bernie Dietz

Project: SNK OAKLAND

Received: October 15, 1998

re: 6 samples for TPH - Diesel analysis.

Method: EPA 8015M

Matrix: SOIL Extracted: October 16, 1998 Sampled: October 15, 1998 Run#: 15434 Analyzed: October 16, 1998

REPORTING

DIESEL LIMIT RESULT SPIKE CLIENT SPL ID (mq/Kq)(mg/Kg)Spl# (mq/Kg) 220 N.D.

Hydrocarbon reported does not match the pattern of our Diesel Standard.

Surrogate Recoveries biased high due to Hydrocarbon co-elution. 210667 LDS2 C-1 260 1.0 N.D.

Hydrocarbon reported is in the early Diesel Range and does not match our Note: Diesel Standard.

10668 LDS2 E-5 45 1.0 N.D. 85.5

Note: Hydrocarbon reported does not match the pattern of our Diesel Standard. 210669 LDS2 E-4 120 1.0 N.D. 85.5

Hydrocarbon reported does not match the pattern of our Diesel Standard.

Surrogate Recoveries biased high due to Hydrocarbon co-elution.

210670 LDS2 C-2 110 1.0 N.D.

Note: Hydrocarbon reported does not match the pattern of our Diesel Standard. 210671 LDS2 C-3 N.D. 190 1.0

Note: Hydrocarbon reported does not match the pattern of our Diesel Standard.

Surrogate Recoveries biased high due to Hydrocarbon co-elution.

BLANK

BLANK DILUTION

Analyst

Environmental Services (SDB)

October 22, 1998

Submission #: 9810254

DIETZ IRRIGATION

Atten: Bernie Dietz

Project: SNK OAKLAND

Received: October 15, 1998

re: One sample for Polynuclear Aromatic Hydrocarbons (PAHs) analysis.

Method: SW846 Method 8270A Nov 1990

Client Sample ID: LDS2 COMPOSITE

 Spl#: 210672
 Matrix: SOIL
 Extracted: October 16, 1998

 Sampled: October 15, 1998
 Run#: 15442
 Analyzed: October 21, 1998

ANALYTE	RESULT (mg/Kg)	REPORTING LIMIT (mg/Kg)	BLANK RESULT (mg/Kg)	BLANK SPIKE (%)	DILUTION FACTOR
NAPHTHALËNE	N.D.	0.50	N.D.		5
ACENAPHTHYLENE	N.D.	0.50	N.D.		5
ACENAPHTHENE	N.D.	0.50	N.D.	84.0	5
FLUORENE	N.D.	0.50	N.D.		5
PHENANTHRENE	N.D.	0.50	N.D.		5
ANTHRACENE	N.D.	0.50	N.D.		5
TLUORANTHENE	N.D.	0.50	N.D.		5
YRENE	N.D.	0.50	N.D.	82.9	5
BENZO (A) ANTHRACENE	N.D.	0.50	N.D.		5
CHRYSENE	N.D.	0.50	N.D.		5
BENZO (B) FLUORANTHENE	N.D.	0.50	N.D.		5
BENZO (K) FLUORANTHENE	N.D.	1.0	N.D.		5
BENZO (A) PYRENE	N.D.	0.25	N.D.		5
INDENO(1,2,3-CD)PYRENE	N.D.	1.0	N.D.		5
DIBENZO (A, H) ANTHRACENE	N.D.	1.0	N.D.		5
BENZO (GHI) PERYLENE	N.D.	1.0	N.D.		5

Note: Reporting limits raised due to matrix interference.

Michael Lee

Analyst

Michael Verona

Environmental Services (SDB)

October 16, 1998

Submission #: 9810254

DIETZ IRRIGATION

Atten: Bernie Dietz

Project: SNK OAKLAND

Received: October 15, 1998

re: One sample for Gasoline BTEX analysis.

Method: SW846 8020A Nov 1990 / 8015Mod

Client Sample ID: LDS2 C-1

Spl#: 210667

Matrix: SOIL

Sampled: October 15, 1998

Run#:15438

Analyzed: October 16, 1998

ANALYTE	RESULT (mg/Kg)	REPORTING LIMIT (mg/Kg)	BLANK RESULT (mg/Kg)	BLANK SPIKE (%)	DILUTION FACTOR
GASOLINE	N.D.	1.0	N.D.	105	1
BENZENE	N.D.	0.0050	N.D.	100	1
TOLUENE	N.D.	0.0050	N.D.	9'7	1
ETHYL BENZENE	N.D.	0.0050	N.D.	98	1
XYLENES	N.D.	0.0050	N.D.	97	1.

Vincent Vancil

Analyst

Michael Verona

Environmental Services (SDB)

October 16, 1998

Submission #: 9810254

DIETZ IRRIGATION

Atten: Bernie Dietz

Project: SNK OAKLAND

Received: October 15, 1998

re: One sample for Gasoline BTEX analysis.

Method: SW846 8020A Nov 1990 / 8015Mod

Client Sample ID: LDS2 E-5

Spl#: 210668

Matrix: SOIL

Sampled: October 15, 1998

Run#:15438

Analyzed: October 16, 1998

ANALYTE	RESULT (mg/Kg)	REPORTING LIMIT (mg/Kg)	BLANK RESULT (mg/Kg)	BLANK SPIKE (%)	DILUTION FACTOR
GASOLINE	N.D.	1.0	N.D.	105	1
BENZENE	N.D.	0.0050	N.D.	100	1
TOLUENE	N.D.	0.0050	N.D.	97	1.
ETHYL BENZENE	N.D.	0.0050	N.D.	98	1
XYLENES	0.0057	0.0050	N.D.	97	1

Note:

Hydrocarbon found in Gasoline Range is uncharacteristic of Gasoline Profile. If quantified using Gasoline's response factor, concentration

would equal 1.9mg/Kg.

Vincent Vancil

Analyst

Environmental Services (SDB)

October 16, 1998

Submission #: 9810254

DIETZ IRRIGATION

Atten: Bernie Dietz

Project: SNK OAKLAND

Received: October 15, 1998

re: One sample for Gasoline BTEX analysis.

Method: SW846 8020A Nov 1990 / 8015Mod

Client Sample ID: LDS2 E-4

Spl#: 210669

Matrix: SOIL

Sampled: October 15, 1998

Run#:15438

Analyzed: October 16, 1998

ANALYTE	RESULT (mg/Kg)	REPORTING LIMIT (mg/Kg)	BLANK RESULT (mg/Kg)	BLANK SPIKE (%)	DILUTION FACTOR	
GASOLINE	N.D.	1.0	N.D.	105	1	
BENZENE	N.D.	0.0050	N.D.	100	1	
TOLUENE	N.D.	0.0050	N.D.	97	1	
ETHYL BENZENE	N.D.	0.0050	N.D.	98	1	
XYLENES	N.D.	0.0050	N.D.	97	1	

Vincent Vancil

Analyst

Michael Verona

Environmental Services (SDB)

October 16, 1998

Submission #: 9810254

DIETZ IRRIGATION

Atten: Bernie Dietz

Project: SNK OAKLAND

Received: October 15, 1998

re: One sample for Gasoline BTEX analysis.

Method: SW846 8020A Nov 1990 / 8015Mod

Client Sample ID: LDS2 C-2

Sp1#: 210670

Matrix: SOIL

Sampled: October 15, 1998

Run#:15438

Analyzed: October 16, 1998

ANALYTE	RESULT	REPORTING LIMIT (mg/Kg)	BLANK RESULT (mg/Kg)	SPIKE (%)	FACTOR
GASOLINE BENZENE TOLUENE ETHYL BENZENE XYLENES	N.D. N.D. N.D. N.D. N.D.	1.0 0.0050 0.0050 0.0050 0.0050	N.D. N.D. N.D. N.D. N.D.	105 100 97 98 97	1 1 1 1

Vincent Vancil

Analyst

Michael Verona

Environmental Services (SDB)

October 16, 1998

Submission #: 9810254

DIETZ IRRIGATION

Atten: Bernie Dietz

Project: SNK OAKLAND

Received: October 15, 1998

re: One sample for Gasoline BTEX analysis.

Method: SW846 8020A Nov 1990 / 8015Mod

Client Sample ID: LDS2 C-3

Spl#: 210671

Matrix: SOIL

Sampled: October 15, 1998

Run#:15438

Analyzed: October 16, 1998

ANALYTE	RESULT (mg/Kg)	REPORTING LIMIT (mg/Kg)	BLANK RESULT (mg/Kg)	BLANK SPIKE (%)	DILUTION FACTOR	
GASOLINE	N.D.	1.0	N.D.	105	1	
BENZENE	N.D.	0.0050	N.D.	100	1	
TOLUENE	N.D.	0.0050	N.D.	• 97	1	
ETHYL BENZENE	N.D.	0.0050	N.D.	98	1	
XYLENES	N.D.	0.0050	N.D.	97	1	

Vincent Vancil

Analyst

Michael Verona

Environmental Services (SDB)

October 16, 1998

DIETZ IRRIGATION

Atten: Bernie Dietz

Project: SNK OAKLAND

Received: October 15, 1998

re: One sample for Gasoline BTEX analysis.

Method: SW846 8020A Nov 1990 / 8015Mod

Client Sample ID: LDS2 A-2

Spl#: 210666

Matrix: SOIL

Sampled: October 15, 1998

Run#:15438

Analyzed: October 16, 1998

Submission #: 9810254

ANALYTE	RESULT (mg/Kg)	REPORTING LIMIT (mg/Kg)	BLANK RESULT (mg/Kg)	BLANK SPIKE (%)	DILUTION FACTOR
GASOLINE BENZENE TOLUENE ETHYL BENZENE	N.D. N.D. N.D. N.D.	1.0 0.0050 0.0050 0.0050	N.D. N.D. N.D.	105 100 97 98	1 1 1
XYLENES	N.D.	0.0050	N.D.	9 7	1

Vincent Vancil

Analyst

Environmental Services (SDB) (DOHS 1094)

1220 Quarry Lane • Pleasanton, California 94566-4756 510/484-1919 • Facsimile 510/484-1096

Reference #: 2574
Chain of Custod

DATE 10/15/95 PAGE 1

Environmental Service	95 (200) (00H2 109	4)												DAT	F/	<u>U/7 J</u>	110		PAGE .			OI	
PROJUGA A B. DIETZ	<u>, </u>				البب						AN	ALYSIS	HEP(HT		ļ.							
COMPANY DIETE Se	rejetin		1	9	'	_ !	Z.	1 '	,										H20)				l
COMPANY DIETE SU ADDRESS SE17 Etc.	Revery Dr		O) ATBE	PURGEABLE AROMATICS BTEX (EPA 8020)	TPH-Diesel (EPA 8015M)	TEPH (EPA 8015M) OKarosene, ODiesel, OM.O.	PURGEABLE HALOCARBONS (HVOCs) (EPA 8010)	18 _	1	TOTAL OIL AND GREASE (SM 5520 B+F, E+F)		80)				_			E 5				1
Truey . C.	A		805 E 202	BLE AROM	80	5M)	010 010 010	ANIC 260	_	E +		A 80 80)	5 25		Zn	LS 7471			romi				1
SAMPLERS (SIGNATURE)	HID CO. T. CO.	ONE NO I	015, BTE	E A E	EPA	801 10ie	PA 8	ORG A 8		ANE + F.		S(EP	82,	- ×	LS: Ni, 7	ETA 9707	9	TLC	진				[3
4.8. Dut	209 832 -25	10	N A	ABL	les	EPA	ABLE S) (E	빌	12 (07.2	20 E		CIDE	by X	Con	ETA Pb.	7 MI	g	r. (S.	valen 4 hr				{
SAMPLE ID. DATE	7 8331238 PA	X NO.)	TPH-(EPA 8015,8020) Gas w/M BTEX DMTBE	PURGE	- Q	PH (I	RGE	VOLATILE ORGANICS (VOCs) (EPA 8260)	SEMIVOLATILES (EPA 8270)	TAL		C PESTICIDES(EPA 8080)	PNA's by 20'8270	O Spec. Cond.	LUFT METALS: Cd. Cr. Pb. Ni. 7	CAM 17 METALS (EPA 6010/7470/7471	TOTAL LEAD	OWET. (STLC) OTCLP	☐ Hexavalent Chronutu			1	
SAMPLE ID. DATE	TIME MATRIX	PRESERV.		1 <u>5 8</u> 1	횬	品具] EE	الخركا	SE GE	T0.		0 0	o N		CG.	QH	2		0		1		
LDS 2 A-2 19/5/98	1100 Busch	NA	X		X																		
	1:03 pm		×		×	1				7	ut.	2						-					-
			×		1					4			<u></u>		-	7-		-	 -	_		 	<u> </u> -
	1:06pm	,!		<u> </u>	<u> </u>	1	1	 	<u> </u> !		Lon	pos	12 1	Sin	Tall		ļ	<u> </u>	 	 	 	ļ.—	_
LDS 2 E-4 /	1309pm	ļ 	X	1	X	11	1 }	1	}		an	e ri	en 7	PVA	64				127				
LDS 2 C-2 /	1:11 por		X		X						8	270	en	the				F)		15	3/	177	
	1:13 pm		X		X		1					270 Co	pes	te				 			Į į		
				1		1		1	 				<u> </u>			\	ļ		 	 		 	-
1209		!	1	1	 	11		 									<u> </u>	-	 	ļ	 		_
LDS 2 Composite		·—	1	 		 		<u> </u>	<u> </u> '				X		 				<u> </u>				
PROJECT INFORMATION		LE RECEIP			RELIN	VOUISHE	ED BY			1	REL	INQUIS	HED B	γ			2 7	RELINO	UISHED	BY			^
PHOJECT NAME SNK Caplind THOJECT NUMBER	TOTAL NO OF CON	TAINERS		6	7.	ATURE)	Dry	<u>c-1</u>	<u> </u>	<u> </u>	<u> </u>												
PROJECT NUMBER	HEAD SPACE				ET	R_{2J}	a. 1	In		(JIME)) (SIG	NATURE)			(th	IME) (SIGNATU	IRE)				Ĺl.
P.O. #	CONFORMS TO REC	~~~~			[PRINTI	BRYA ED NAME	ξ)			(DATE) Lista	NTED NA	(ME)			(DA	NTE) (F	PRINTED	NAME)				Ю
TAT (STANDARD)	-'- -		T-L		COMP	ZIZ	? R. GA	1100	. <u></u>	61,98	<u> </u>	MPANY							41.4				-
5-DAY	24 48	72	ОТН	ER		NED BY						CEIVED	BY					COMPAN		AROR	NAULT		
Report: □ Routine □ Level 2 □ Level 3 □ SPECIAL INSTRUCTIONS/COMMENTS:	D Level 4 D Electronic	c Report		- 1	a	lex	2 W	we	ĿS.	1443							1	1000		310011	,		
of Lorde morniography of the control	_				(SIGNA)	TURE	Dar	200		пир) (SIGI	NATURE				ηn	ME) IS	SIGNATU	RE)				7
				J	[PPINT	ED NAME	E) 00			O/S/G	A GERT	NIED NA	MFI			/DA	(TE) (F	PRINTED	*****				
				1		uen	ula	8_								ĮU-	161	Anteren	NAMEJ				(t)
					(COMP)	ANY					(CO	MPANY)					0	LAB)					_

Environmental Services (SDB)

November 18, 1998

Submission #: 9811157

DIETZ IRRIGATION

Atten: Bernie Dietz

Project: SNK OAKLAND

Received: November 10, 1998

re: 1 sample for TPH - Diesel analysis.

Method: EPA 8015M

Matrix: SOIL

Extracted: November 12, 1998

Sampled: November 10, 1998 Run#: 15933 Analyzed: November 14, 1998

BLANK BLANK DILUTION REPORTING DIESEL LIMIT RESULT SPIKE FACTOR Spl# CLIENT SPL ID (mg/Kg) (mg/Kg) (mg/Kg) (%) 90.8 214975 LDS#3 B-1 9.1 1.0 N.D.

Note: Hydrocarbon reported does not match the pattern of our Diesel Standard.

Bruce Havlik

Analyst

Environmental Services (SDB)

November 17, 1998

Submission #: 9811157

DIETZ IRRIGATION

Atten: Bernie Dietz

Project: SNK OAKLAND

Received: November 10, 1998

re: 5 samples for TPH - Diesel analysis.

Method: EPA 8015M

Matrix: SOIL Extracted: November 12, 1998 Sampled: November 10, 1998 Run#: 15933 Analyzed: November 14, 1998

		REPORTING	BLANK	BLANK	DILUTION
	DIESEL	LIMIT	RESULT	SPIKE	FACTOR
Spl# CLIENT SPL ID	(mg/Kg)	(mg/Kg)	(mq/Kq)	(%)	
214974 LDS#3 A-4	8.8	- · · -	N.D.		
Note: Hydrocarbon	reported does not i	match the patt	ern of our	Diesel	Standard.
214976 LDS#3 C-2		10			10
Note: Hydrocarbon	reported is in the	early Diesel	Range and	does not .	match our
Diesel Standa	ard.				
<i>214977</i> LDS#3 D-3		1.0			1
Note: Hydrocarbon:	reported is in the	early Diesel	Range and	does not	match our
Diesel Standa	ard.				
<i>214978</i> LDS#3 G-8	18	1.0	N.D.	90.8	1
Note: Hydrocarbon:	reported does not a	match the patt	ern of our	Diesel	Standard.
<i>214979</i> LDS#3 G-5	49	- • •	N.D.		1
Note: Hydrocarbon	reported does not :	match the patt	ern of our	Diesel	Standard.

Analyst

Environmental Services (SDB)

November 17, 1998

Submission #: 9811157

DIETZ IRRIGATION

Atten: Bernie Dietz

Project: SNK OAKLAND

Received: November 10, 1998

re: One sample for Polynuclear Aromatic Hydrocarbons (PAHs) analysis.

Method: SW846 Method 8270A Nov 1990

Client Sample ID: LDS#3A4,B1,C2,D3,G8,G5

 Sp1#: 214980
 Matrix: SOIL
 Extracted: November 12, 1998

 Sampled: November 10, 1998
 Run#: 15940
 Analyzed: November 17, 1998

		REPORTING	BLANK	BLANK I	DILUTION
	RESULT	LIMIT	RESULT	SPIKE	FACTOR
ANALYTE	(mq/Kq)	(mg/Kg)	(mg/Kg)	(%)	
NAPHTHALENE	N.D.	0.50	N.D.		5
ACENAPHTHYLENE	N.D.	0.50	N.D.		5
ACENAPHTHENE	N.D.	0.50	N.D.	62.5	5
FLUORENE	N.D.	0.50	N.D.		5
PHENANTHRENE	N.D.	0.50	N.D.		5
ANTHRACENE	N.D.	0.50	N.D.		5
FLUORANTHENE	N.D.	0.50	N.D.		5
YRENE	N.D.	0.50	N.D.	63.7	5
ENZO (A) ANTHRACENE	N.D.	0.50	N.D.		5
CHRYSENE	N.D.	0.50	N.D.		5
BENZO(B) FLUORANTHENE	N.D.	0.50	N.D.		5
BENZO (K) FLUORANTHENE	N.D.	1.0	N.D.		5
BENZO (A) PYRENE	N.D.	0.25	N.D.		5
INDENO(1,2,3-CD)PYRENE	N.D.	1.0	N.D.	- -	5
DIBENZO (A, H) ANTHRACENE	N.D.	1.0	N.D.		5
BENZO (GHI) PERYLENE	N.D.	1.0	N.D.		5

Note: Reporting limits raised due to matrix interference.

Michael Lee

Analyst

Michael Verona

Environmental Services (SDB)

November 17, 1998

Submission #: 9811157

DIETZ IRRIGATION

Atten: Bernie Dietz

Project: SNK OAKLAND

Received: November 10, 1998

re: One sample for Gasoline BTEX analysis.

Method: SW846 8020A Nov 1990 / 8015Mod

Client Sample ID: LDS#3 A-4

Spl#: 214974 Matrix: SOIL Sampled: November 10, 1998 Run#:15965

Run#:15965 Analyzed: November 12, 1998

ANALYTE	RESULT (mg/Kg)	REPORTING LIMIT (mg/Kg)	BLANK RESULT (mg/ <u>Kg</u>)	BLANK SPIKE (%)	DILUTION FACTOR
GASOLINE	N.D.	1.0	N.D.	99	1
BENZENE	N.D.	0.0050	N.D.	88	1.
TOLUENE	N.D.	0.0050	N.D.	84	1
ETHYL BENZENE	N.D.	0.0050	N.D.	82	1
XYLENES	N.D.	0.0050	N.D.	81	1

Note: Surrogate Recoveries demonstrate Matrix interference.

Craig Huntzinger

Analyst

Michael Verona

Laboratory Operations Manager

Environmental Services (SDB)

November 17, 1998

Submission #: 9811157

DIETZ IRRIGATION

Atten: Bernie Dietz

Project: SNK OAKLAND

Received: November 10, 1998

re: One sample for Gasoline BTEX analysis.

Method: SW846 8020A Nov 1990 / 8015Mod

Client Sample ID: LDS#3 B-1

Spl#: 214975 Sampled: November 10, 1998 Run#:15937

Matrix: SOIL

Analyzed: November 12, 1998

	RESULT	REPORTING LIMIT	BLANK RESULT	SPIKE	DILUTION FACTOR
ANALYTE	(mg/Kg)	(mg/Kg)	(mg/Kg)	(%)	
GASOLINE	N.D.	1.0	N.D.	93	1
BENZENE	N.D.	0.0050	N.D.	91.	1
TOLUENE	N.D.	0.0050	N.D.	86	1
ETHYL BENZENE	N.D.	0.0050	N.D.	85	1
			• ·	83	1
XYLENES	N.D.	0.0050	N.D.	03	上

Note: Surrogate Recoveries demonstrate Matrix interference.

Vincent Vancil

Analyst

Michael Verona

Environmental Services (SDB)

November 17, 1998

Submission #: 9811157

DIETZ IRRIGATION

Atten: Bernie Dietz

Project: SNK OAKLAND

Received: November 10, 1998

re: One sample for Gasoline BTEX analysis.

Method: SW846 8020A Nov 1990 / 8015Mod

Client Sample ID: LDS#3 C-2

Spl#: 214976 Sampled: November 10, 1998

Matrix: SOIL
Run#:15937

Analyzed: November 12, 1998

ANALYTE	RESULT (mg/Kg)	REPORTING LIMIT (mg/Kg)	BLANK RESULT (mg/Kg)	BLANK SPIKE (%)	DILUTION FACTOR
GASOLINE	N.D.	1.0	N.D.	93	1.
BENZENE	N.D.	0.0050	N.D.	91	1
TOLUENE	N.D.	0.0050	N.D.	86	1
ETHYL BENZENE	N.D.	0.0050	N.D.	85	1
XYLENES	N.D.	0.0050	N.D.	83	1

Vincent Vancil

Analyst

Michael Verona

Environmental Services (SDB)

November 17, 1998

Submission #: 9811157

DIETZ IRRIGATION

Atten: Bernie Dietz

Project: SNK OAKLAND

Received: November 10, 1998

re: One sample for Gasoline BTEX analysis.

Method: SW846 8020A Nov 1990 / 8015Mod

Client Sample ID: LDS#3 D-3

Spl#: 214977

Matrix: SOIL

Sampled: November 10, 1998

Run#:15937

Analyzed: November 12, 1998

ANALYTE	RESULT (mg/Kg)	REPORTING LIMIT (mg/Kg)	BLANK RESULT (mg/Kg)	BLANK SPIKE (%)	DILUTION FACTOR
GASOLINE	N.D.	1.0	N.D.	93	1
BENZENE	N.D.	0.0050	N.D.	91	1
TOLUENE	N.D.	0.0050	N.D.	86	1
ETHYL BENZENE	N.D.	0.0050	N.D.	85	1
XYLENES	N.D.	0.0050	N.D.	83	

Note: Surrogate Recoveries demonstrate Matrix interference.

Vincent Vancil

Analyst

Michael Verona

Environmental Services (SDB)

November 17, 1998

Submission #: 9811157

DIETZ IRRIGATION

Atten: Bernie Dietz

Project: SNK OAKLAND

Received: November 10, 1998

re: One sample for Gasoline BTEX analysis.

Method: SW846 8020A Nov 1990 / 8015Mod

Client Sample ID: LDS#3 G-8

Spl#: 214978 Sampled: November 10, 1998

Matrix: SOIL Run#:15937

Analyzed: November 12, 1998

ANALYTE	RESULT (mg/Kg)	REPORTING LIMIT (mg/Kg)	BLANK RESULT (mg/Kg)	BLANK SPIKE (%)	FACTOR
GASOLINE	N.D.	1.0	N.D.	93	1
BENZENE	N.D.	0.0050	N.D.	91	1
TOLUENE	N.D.	0.0050	N.D.	86	1
ETHYL BENZENE	N.D.	0.0050	N.D.	85	1
XYLENES	N.D.	0.0050	N.D.	83	1

Note: Surrogate Recoveries demonstrate Matrix interference.

Vincent Vancil

Analyst

Michael Verona

Environmental Services (SDB)

November 17, 1998

Submission #: 9811157

DIETZ IRRIGATION

Atten: Bernie Dietz

Project: SNK OAKLAND

Received: November 10, 1998

re: One sample for Gasoline BTEX analysis.

Method: SW846 8020A Nov 1990 / 8015Mod

Client Sample ID: LDS#3 G-5

Spl#: 214979 Sampled: November 10, 1998 Run#:15937

Matrix: SOIL

Analyzed: November 12, 1998

ANALYTE	RESULT (mg/Kg)	REPORTING LIMIT (mg/Kg)	BLANK RESULT (mg/Kg)	BLANK SPIKE (%)	DILUTION FACTOR
GASOLINE	N.D.	1.0	N.D.	93	1
BENZENE	N.D.	0.0050	N.D.	91	1
TOLUENE	N.D.	0.0050	N.D.	86	1
ETHYL BENZENE	N.D.	0.0050	N.D.	8.5	1
XYLENES	N.D.	0.0050	N.D.	83	1

Note: Surrogate Recoveries demonstrate Matrix interference.

Vincent Vancil

Analyst

Michael Verona

Environmental Services (SDB) (DOHS 1094)

SURM #: 9811157 REP: GC

CLIENT: DIETZ

DUE: 11/17/98

REF #:43057

Reference #: 4557

Chain of Custody

11.3	2 X 12 /1-						4	4	4	4	4	411	AN	ALYSIS	SIREP	ORT			47		47			4	7
PROJ MGR _ H. &	- UKIO	· 							-				a in	-					1		e e				ı
COMPANY DIET	E /KM				۳ ا	SS	€	0.	No No		,	in in	1	1	240	'	1	()	t	,	- 1120)	1	,]	ļ	rn i
COMPANY Dieto ADDRESS 8617	1 Etc	Kever	447	Or	o ž	IF T	15N	¥.	ARB	SS		القيا	1	(080	25	1 '		(₌)	t	1	H of	1 1		} ′	4€.RS
_ Try	ucu (1/4	<i>,</i>		802	020 020	80	Sel.	OCC.	ANI 260	ر ا ا	В п	1 /	A 80	000	1	ا ح	S 747	ĺ		ti i	1	,		TAIN
					15.E	A B	PA	1015 1Die	HAL PA 8	RG/ A 8′	LES	S + 1	'	(EP/	827		S: Z	14 7 jo	1 0	15	[호흥]	[]		1	SO.
SAMPLERS (SIGNATURE)		20'	9 832	(PHONE NO)	8 🛪		<u> = </u>	4 ° 8 □	E E	EP/	1 F 6	D P P P P P P P P P P P P P P P P P P P	'	DES	X.	puo,	P Z	ME V	Ä	(ST	hr h	1 1	,		OF C
					EPA /w	× EA)ies	Sen EP	S.S.	12 2	. 27 27 '	L 0	1	TICI 3'S (s b	S C C	₹ ¥	17	الا الا	E.T.	(24	1	,	1	EB (
AAAAA DII			853/		TPH-(EPA 8015,8020)	PURGEABLE AROMATICS BTEX (EPA 8020)	TPH-Diesel (EPA 8015M)	TEPH (EPA 8015M) OKerosene, ODiesel, OM.O.	PURGEABLE HALOCARBONS (HVOCs) (EPA 8010)	VOLATILE ORGANICS (VOCs) (EPA 8260)	SEMIVOLATILES (EPA 8270)	TOTAL OIL AND GREASE (SM 5520 B+F, E+F)	.] '	☐ PESTICIDES(EPA 8080)	PNA's by 2 8270	☐ Spec. Cond. ☐ TSS ☐ TDS	LUFT METALS: Cd, Cr, Pb, Ni, Zn	CAM 17 METALS (EPA 6010/7470/747	TOTAL LEAD	U W.E.T. (STLC) O TCLP	☐ Hexavalent Chromium ☐ pH (24 hr hold time for	1	('	NUMBER OF CONTAINERS
SAMPLE ID.	DATE			X PRESERV.	\$ PX	<u>∤ā</u> —	<u> </u>	F0	A C	ء خرا	등 교	1 5 3	<u> </u>	00'	<u> </u>	00,	اء ما	ا ۳	<u> -</u>						ž
L.U.S 3 AA	-1- 1	- {- }	Soil	N/A	X	<u> </u>	X																		
LD.5#3 B-1	11/10/98	11:08A			X	'	X	.]			<u>'</u>			200	Six 5	sompl	ks.								
LDS#3 C-2		11:13Am			χ		X			1>	+ Cos	mpon	1201	VA	X										
LDS#3 D-3	11/10/98	11:20A			X	,	X			\prod	ana	lne				,			<u> </u>	,					
LDS#3 G.8	11/10/98	11:2917	HI		X		X			1	{ }								1						
LDS#3G-5	11/10/98	8 11:40A	4		X		X		1	厂			!												
	,	1							1						1	1							,		
		 		-	-	 		1			-	 	!	'	 	 '		 				$\hspace{-1em} \longleftarrow \hspace{-1em} \downarrow$	-		
	 /	ļJ	 	-	-	'		. /	1		- '	41	 '		ļ	<u> </u>		11	ļ	-	.[]	1			
	!	1				<u> </u>			1		'	1_1	_'	_ '		_'	1 1	1	1	'	1	1			
PROJECT INFORM	ATION	Aquin		PLE RECEI	T		RELIN	NOUISH	ED BY		1 0	\overline{I}	I RE!	LINQUIS	SHED P	3Y			2 R	RELINGU	UISHED	BY			3
PROJECT NAME SNK Oak	land.	TOTAL	NO OF CO	ONTAINERS		6	M	elle	18	101	ulli	11											1		
PROJECT NUMBER		HEAD S	SPACE			,1	ISIGN	ATURE)	ربنيده	, ,	m,	TIME	- 2	GNATURE	<u></u>	,,,,,,,,,,,,		/ (11)	IME) (S	(SIGNATUR	/RE)			<u></u>	TIME)
P O, #		ТЕМРГ	ERATURE			, — 1	IP BIN	TED NAME	162	21	11/14	LEK	<u> </u>	UNTED NA	*****		/								
		CONFO	ORMS TO R	IECORD			1//	RTZ	-1	501	1111L 1-10- GA	TIG	الله المالة	NIEUm	₩ E j			(UA:	VIEL L	PRINTED I	NAME)			(DA	DATE)
TAT STANDARD 5-DAY			24	48 72	OT	HER	СОМР	ZANY)		<u> </u>	: <u>/</u>	// <u></u>		OMPANY)			7		 	COMPANY	m /				
Report: Routine Level	L	3 ⊓Level ¢					RECE	NED BY	Tree		1	1	REC	CEIVED	BY	7	<u>,</u>		2 P	RECEIVE	Ξ D/ BΥ (Ι	ABORA	TORY)		3
SPECIAL INSTRUCTIONS/CO		:				,	1	("	W[]	U.U	Ky					/				/	/				
	***************************************	4.	.300			,	ISIGNA	ATURE)		7.	T_I	4:3/	.) ISIG	SNATURE)	3	1		(TII)	ME) (S	SIGNATUR	AE)				TIME)
		6-:	.30C	L.		1	INDIAN.	TED NAME	<i>\$</i> \$U	M.	711		1	NTED NA	/				_						
		K / /	her.)		J		(/	" <u></u>	. 1	1.101	9 gain	1 1000	MEUAA	MEI			(DAI	1E) (*	PRINTEDA	HAME			AG)	ATE)
							СОМР	'ANY) t					(CO.	MPANY)					- 7	LAB)					



INSPECTION CONSULTANTS, LP

Job Name 208	TACKSON	Date 10/21/98	ICI Jub No. 182-114
lob Address	TACKSON		City OAK IAN d
Permit No.		Issued by	
Contractor		Subcontractor DIETZ IRA	liga fia-
Material Description (t	ype, grade, source)	1276 1 0	
Tochnician/Inspector			Page 10 f /
Dept of Building & Sai	ety / City Of	Building	Inspector
Type of Inspection Required	☐ Reinforced Concrete ☐ Post Tensioned Concrete ☐ Reinforced Masonry	☐ Structural Steel Assembly ☐ Fire Proofing ☐ Epoxy Anchors	y □-Earthwork □ Quality Control □ Other
Inspection Summary		work performed, number, type & id	ems, progress, remarks, etc. Includes information entification numbers of test samples taken: Structural
Comments: Compoch Soil Tes of fle will Re 1 86.09 2 9509 3 90.7 4 95.0 5 88.7	Material to Twen peets (5) test peets comprat & to	20 me d (2) p 25 f 2 f /2 fe 2. 4	a, b placed and . several Nucleur 10us locations 10us locati
I hereby certify that I hall of the above report	ON OF COMPLIANCE have inspected to the best of my knowled ed work unless other noted. I have found	Billing Code Balling Cod	
applicable sections of	th the approved plans, specifications, and the governing building codes. Non-senoted were brought to the attention of: Compliance	All inspections based on a mir addition, any inspection extend	nimum of 4 hours and over 4 hours - 8 hour min. In ding past noon hour will be an 8 hour min.
Inspec	tor a res	IAO	Onom Addition Addition

2999 - A GOLD CANAL DRIVE ◆ RANCHO CORDOVA, CALIFORNIA 95670-6128 ◆ (916) 635-2972 ◆ (916) 635-6457 FAX

844 66th AVENUE ◆ OAKLAND, CALIFORNIA 94621-2716 ◆ (510) 635-9211 ◆ (510) 635-0989 FAX



INSPECTION CONSULTANTS, LP

Project Name	Client or Owner	- [Job No.			
General Location of Work	Owner or Clients Repre	sentative	982 -// / Date-Day of W			
DAKIAND			10/26/91			
General Contractor DIETZ IRRIGATION	Subcontractor		Project Engine	er		
Type of Work Nuclear Soil Test	Subcontractor's Superin	tendent or Fore	man	Permit No.		
Assignment Cancelled By:	Page / 0 f 4	Weather SUNNY		Technician/		
Daily Field Report Lipon			,	•		
and backfill pa	d. Nuclear S.	ail Test	were p	restermed		
at various locat			/	/ / 1		
test were within job quidelines and specifications.						
Deusity M	. с	CAMPECT.	Dep	th.		
1 //7./		470	- 1	Retest		
2 116.9 8	4 5	14	-1	ReTosT		
3 /2/.3 7	<u> </u>	7	-1			
4 122.5 7.	7 9	8	-1	RetesT		
5 117.6 Y	.5- 9	4	٠ ك			
6 /21·1 7	.9 9	7	- 2			
7 122.3	7.5 ,9	8	GD			
8 120.5	8.1 9	4	GD			
9 121.7	a 6 A	CI.	GD			
3" = a	T.7 PRAWING	for To.	T Lon	A Tracks 13		
	Conforman					
Non-compliance conditions noted we	re brought to the attention	of				
for corrective action. Work observed was to the best of my knowledge, in conformance with the (approved) project plans						
specification, and applicable standard	· ·		erns noted above	9 .		
Comments Attached	Inspector	Cand oft	جري			

2999 GOLD CANAL DRIVE. SUITE A ◆ RANCHO CORDOVA, CALIFORNIA 95670 ◆ (916) 635-2972 ◆ (916) 635-6457 FAX 844 66th AVENUE ◆ OAKLAND, CALIFORNIA 94621 ◆ (510) 635-9211 ◆ (510) 635-0988 FAX

Lu



INSPECTION CONSULTANTS, LP

Project Name		Client or Owner Job No. 982-//9						
Cos JACK General Location	of Work	Owner or Clients Represe	entative	Date, Day of W	/eek			
DAKLAND				10/26/98				
General Contracto		Subcontractor		Project Engine	er			
Type of Work	BRIGATIONS	Subcontractor's Superinte	andent or Eor	Yman .	Permit No.			
Nucleur So.	· TosT	Subcontractor 5 Superint	SIMBIR OF FOR	2113Q11	Femiliao.			
Assignment Canc	elled By:	Page	Weather		Technician, C. Hells			
20f2 Sunny C. Hills								
Daily Field Report								
				··· <u> </u>				
	0							
			M					
1		<i>''</i>	<i>—</i>	1				
Ŋ	1							
3				V	\ <u>\</u>			
6:50W		(2)						
		(4)		٧	3			
b W					1			
	(A)							
	6		(e					
Conformance								
Non-compliance conditions noted were brought to the attention of								
□ Comments Attached Inspector Low ###								


2999 GOLD CANAL DRIVE, SUITE A ◆ RANCHO CORDOVA, CALIFORNIA 95670 ◆ (916) 635-2972 ◆ (916) 635-6457 FAX 844 66th AVENUE ◆ DAKLAND, CALIFORNIA 94621 ◆ (510) 635-9211 ◆ (510) 635-0986 FAX

PECTION CONSULTANTS INC. PHONE NO. : 510 635 0988 NOV. 30 1998 05:07PM P4
SOIL AGGREGATE - MOISTURE DENSITY RELATIONS FROM : INSPECTION CONSULTANTS INC.

PROJECT NAME: 208 JACKSON St.	PROJECT NO .: 982-114
SAMPLE DESCRIPTION: GRSY GRAVELLY SIND	1100201 110.
LOCATION:	SAMPLE NO. 0/362

A. Wl. moid+soil	10158	1240	6362	12/11
B. Wt. mold	4295	0	2000	6571
C. Wt. wet soil (A-B)	1863	1953	2067	2046
D.Factor: 4"mold=0.06614 6"mold=0.02939	06614			20 / 4
E. Wet Density (CxD)	123.2	129.2	1367	/35 3
F. Water added	+0	+50	+100	+150
G. Pan+wet soil	454	452	450	450
H. Pan+dry soil	434	426	414	406
l. Pan Tare	48 -			700
J. Dry soil (H-I)	386	378	366	35%
K. Moisture loss (G-H)	20	26	36	44
L. % Moisture (K/J x 100)	5.2	6.9	9.8	12.3
M. Dry Density $\left(\frac{E}{1+\frac{L}{100}}\right)$	117.1	120.9	124.5	120.4

1,05.2 106.9 104.8



JUL 20 1998 09149 FR ALA CO PUB WK HZO RES

510 TC 912098331288

P.02/02



ALAMEDA COUNTY PUBLIC WORKS AGENCY

YVATER RESOURCES SECTION
951 TURNER COURT, SUITE 300, HAYWARD, CA 84646-2651
PHONE (510) 670-5578 ANDREAS GODFREY FAX (510) 670-5162
(510) 670-5146 ALVIN KAN

DRILLING PERM	IT APPLICATION
for applicant to complete	FOR OFFICE USE
OCATION OF PROJECT 208 JACKSON S.F	PERMIT NUMBER
· CAKLAND CA	WELL NUMBER
(3) Illiamia Coordinates Source	PERMIT CONDITIONS
IPN SEE ATTACHED SITE PLAN	Circled Permit Requirements Apply
MIENT MANY SCHOOL CONFERM TO THE STATE OF	A. GENERAL
Same SNK DEVELOPPIENT INC SOILE IN	1. A permit application should be submitted to as to
Address 185 8ERR Y 5T Phone 415 896-1186	active at the ACPWA office-five days prior to
Tity SAN APANSISCO ZID 94107	proposed starting data.
	2. Submit to ACPWA within 60 days after completion of
NAME DIETZ IRRIGATION	permitted work the original Department of Water
Name DIELT INTERPRED	Resources Water Wall Drillars Report or equivalent for
Fax 209 833 / 288	well projects, or drilling logs and location akeren for
Address 8617 Etcheverry Phone 209 833 1288 Notice 129 129 100 100 100 100 100 100 100 100 100 10	geotechnical projects.
21p 95376	3) Permit is void if project not begun withm 90 days of
and or and in on	approval date. B. WATER SUPPLY WELLS
YPE OF PROJECT	1. Minimum surface real thickness is two inches of
Well Construction Geotechnical Investigation	
Cathodic Protection C General C	cament grout placed by tremie.
Water Supply 🖟 Contemination 🗇	2. Minimum scal depth is 30 feet for municipal and
Monitoring D Well Desituetion	industrial wells or 20 feet for domestic and impation
	wells unless a lesser depth is specially approved.
PROPOSED WATER SUPPLY WELL USE	C. GROUNDWATER MONITORING WELLS
New Domestic 🗸 Replacement Domestic 🗖	including piezometers
Municipal I Irrigation (1)	l. Minimum zurface seat thickness is two inches of
Industrial C Other E	coment grout placed by trents.
	• • •
ORILLING METHOD:	2. Minimum scal depth for monitoring wells is the
Stable - Sta	maximum depth practicable or 20 feet.
Cable B Other > PRESSUR	D. GEOTECHNICAL
Cause of Officer	GROUT Backfill bore hole with compacted cuttings or heavy
DRILLER'S LICENSE NO. C 57 # 485/65 MW	2 2 3 bentohite and upper two feet with compacted material
WIECEW 2 FICEWSE MO	tu gress of known at suspensed cottry tillumput neumen
YELL PROJECTS	coment grout shall be used in place of comparted cuttings.
	E. CATHODIC
Drill, Hole Diamotor 11 in. Maximum Casing Diameter 2 in. Depth 15 is	Fill hole above anoce zone with concrete placed by tremit.
Casing Diameter Z in. Depth 15 16	(F.) WELL DESTRUCTION
Surface Seal Depth (t. Number	See attached.
GEOTECHNICAL PROJECTS	G. SPECIAL CONDITIONS
Number of Borings Maximum	,
Hole Districtor In. Depth n.	A 1 200 3
ISTIMATED STARTING DATE 8/10/98	//
ESTIMATED COMPLETION DATE \$ 1,500	APPROVED - 7/30/5
1/3 / //	APPROVED DATE DATE
* / · - / · *	
hereby agree to comply with all requirements of this parmit and	M. 1 A L P. 10-16.11
lameda County Ordinance No 73-68.	Ullaneda Country I where wealth
	Cale & Con C. L. L. D.
	consider rang sens men when we
APPLICANT'S U.Z. 2/20/00	
IONATURE H. B. Outs DATE 7/29/98	alaneda Country Public Health Contact Lawy Sito FOR APPROVAL 570 - 567-6700

510 TC 912098331238

P.82/82



ALAMEDA COUNTY PUBLIC WORKS AGENCY

WATER RESOURCES SECTION 951 TURNER COURT, SUITE 300, HAYWARD, CA 94545-2651 PHONE (510) 670-5575 ANDREAS GODFREY FAX (510) 670-5242 (510) 670-5248 ALVIN KAN

DRILLING PERMIT APPLICATION

DESTINATED STARTING DATE DATE TO START DOING SUPERIOR SATE STARTING DATE DESTINATED STARTING DATE DESTINATED STARTING DATE DESTINATED STARTING DATE DESTINATED STARTING DATE DESTINATED STARTING DATE DATE TO STARTING DATE D		FOR OFFICE USE
### PERMIT CONDITIONS Content of the property of the proper	for applicant to complete	<u>_</u>
ARLAND CARLAND CARE SUPPLY WELL USE New Robinstein Continuous New Part Conditions Well Properties of Continuous Continuou	CCATION OF PROJECT 208 JACKSON	PERMIT NUMBER 98W2314
Altiformia Coordinates Source (I. Acquiracy 2 ft. CTE Acquiracy 2	OAKLAND CA	
Creled Permit Requirements Apply LIENT SUK WILLOPHENT INC SUTE 1200 A GENERAL LIENT SUK WILLOPHENT INC SUM STATE SUPPLY WILL SE ROPE Contamination Cathodic Frotestion C		APN
Circled Permit Requirements Apply LIENT SUK DEFENDENT INC SUTE 1200 Agency Superior Superio	Tatifornia Coordinates Source ft. Agguracy 2 ft	PERMIT CONDITIONS
ACTION OF PROJECT Well Construction Choice Protection Chomodic Pr	CON L CCE L CL	•
Applicant State States 18	IPN See affacted site plan	Circled Permit Requirements Apply
Address 735 MANCE OF CONTROL OF STATE O	MENT SUR XEVELOPMENT INC. SWIF 12	MO (A) GENERAL
APPLICANT APPLICANT APPLICANT APPLICANT APPLICANT APPLICANT ATTER APPLICANT APPLI	121710	- 1. W herritte abbetraduelt attention an anniversal an an
APPLICANT Agency Control of Cont	Address 133 CERPOT ST PROPE 413 870110 G	
APPLICANT APPROVED APPLICATION APPROVED APPLICANT APPROVED A	-119 3 400 Program 219 219 219 219	2) Submit to ACPWA within 60 days after coinciction of
Rejources Water Well Drillers Report as equivalent for well projects, or drilling logs and location skerth for grotechnical projects. Confining logs and location skerth for any location of the well projects of the well projects. Company date. 8. WATER SUPPLY WELLS. 8. WATER SUPPLY WELLS. 1. Immirrum surfact stall hickness is two inches of cement grout placed by termit. Industrial wells used to 21 feet for domestic and irrigation wells untest a losser driph is specially approved. 9. C. CROUNDWATER MONITORING WELLS. Now Domestic O Replacement Domestic O Confusion of Con	, DEL 10 x NT	nermitted work the arreinal Denarment of Walter
well projects or drilling logs and location skerth for georethrical projects. YELL PROJECT Well Construction Content or General Well project or General Well Construction General Well project or General Sprow of General Well project or General We	1 1 1 cm 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
September of Borlass Dameter 2 in Depth 6. STECTECHNICAL PROJECTS Described by Rouse 1 in Depth 6. STECTECHNICAL PROJECTS Described by Rouse 1 in Depth 6. STECTECHNICAL PROJECTS Nember of Borlass 1 in Depth 6. STECTECHNICAL PROJECTS Nember of Borlass 1 in Depth 6. STECTECHNICAL PROJECTS Nember of Borlass 1 in Depth 6. STECTECHNICAL PROJECTS Nember of Borlass 1 in Depth 6. STECTECHNICAL PROJECTS Nember of Borlass 1 in Depth 6. STECTECHNICAL PROJECTS Nember of Borlass 1 in Depth 6. STECTECHNICAL PROJECTS Nember of Borlass 1 in Depth 6. STECTECHNICAL PROJECTS Nember of Borlass 1 in Depth 6. STECTECHNICAL PROJECTS Nember of Borlass 1 in Depth 6. STECTECHNICAL PROJECTS Nember of Borlass 1 in Depth 6. STECTECHNICAL PROJECTS Nember of Borlass 1 in Depth 6. STECTECHNICAL PROJECTS Nember of Borlass 2 in Depth 6. STECTECHNICAL PROJECTS Nember of Borlass 3 in Depth 6. STECTECHNICAL PROJECTS Nember of Borlass 3 in Depth 6. STECTECHNICAL PROJECTS Nember of Borlass 3 in Depth 6. STECTECHNICAL PROJECTS Nember of Borlass 5 in Depth 6. STECTECHNICAL PROJECTS Nember of Borlass 5 in Depth 6. STECTECHNICAL PROJECTS Nember of Borlass 6 in Depth 6. STECTECHNICAL PROJECTS Nember of Borlass 6 in Depth 6. STECTECHNICAL PROJECTS Nember of Borlass 6 in Depth 6. STECTECHNICAL PROJECTS Nember of Borlass 7 in Depth 6. STECTECHNICAL PROJECTS Nember of Borlass 7 in Depth 6. STECTECHNICAL PROJECTS Nember of Borlass 7 in Depth 6. STECTECHNICAL PROJECTS Nember of Borlass 7 in Depth 6. STECTECHNICAL PROJECTS Nember of Borlass 7 in Depth 6. STECTECHNICAL PROJECTS Nember of Borlass 7 in Depth 6. STECTECHNICAL PROJECTS Nember of Borlass 7 in Depth 6. STECTECHNICAL PROJECTS Nember of Borlass 7 in Depth 6. STECTECHNICAL PROJECTS Nember of Borlass 7 in Depth 6. STECTECHNICAL PROJECTS Nember 7 in Depth 7 in Depth 6. STECTECHNICAL PROJECTS Nember 8 in Depth 6 in Depth 6 in Depth 6 in Depth 6 in Depth 6 in Depth 6 in Depth 6 in Depth 6 in Depth 6 in Depth 6 in Depth 6 in Depth 6 in Depth 6 in Depth 6 in Depth 6 in Depth 6	Fax 209 835/288	
TYPE OF PROJECT Well Construction Cathodic Protection Cathodic Protec	Address 8017 ETCKEVEFFY Phone 209 832 2010	- geotechnical projects.
Approval date. Well Construction Cathodic Protection Cathodic Pro	Y TRACH 200 95376	(1) Permit is void if project not begun within 90 days of
Well Construction Cathodic Protection Cathodic		
Cathodic Protection Water Supply Contamination Water Supply Contamination Water Supply Contamination Well Destruction PROPOSED WATER SUPPLY WELL USE New Domestic Replacement Domestic Intreation Industrial Contamination Contamination Well Destruction Well Destruction Well Destruction Well Destruction Well Destruction Well Unless a lesser depth is specially approved. C. GROUNDWATER MONITORING WELLS New Domestic Intreation Industrial Contamination Intreation Industrial Contamination Intreation Intreation Industrial Contamination Intreation Interest Contamination Intreation Intre	• • • • • •	
Water Supply Monitaring O Well Destruction Including PEZOMETERS New Domestic C. GROUNDWATER MONITORING WELLS INCLUDING PEZOMETERS	Weil Construction Geotechnical Investigation	Minimum surface seal interness is two inches of
Monitaring Well Destruction Replacement Demestic Replacement De		
PROPOSED WATER SUPPLY WELL USE New Domestic G Replacement Domestic G Municipal G Irregution G Industrial G Other G Ot	Water Supply U Contamination C	7. Minimum seal depth is 50 feet for municipal and
PROPOSED WATER SUPPLY WELL USE New Domestic C Replacement Domestic C Municipal C Integration C Industrial C Other C Other C Conference C C Conference C C Conference C C Conference C C Conference C C Conference C C Conference C C Conference C C Conference C C Conference C C Conference C C Conference C C Conference C C Conference C C Conference C C Conference C C Conference C C C C C C C C C C C C C C C C C C C	Montaining U Well Destruction & DI UNE	
New Domestic C Replacement Domestic C Municipal C Integration C Integration C Integration C Integration C Integration C Integration C Other C Configuration C Configuration C Configuration C Configuration C Configuration C Configuration C Configuration C Configuration C Configuration C C C Configuration C C C C C C C C C C C C C C C C C C C	SPANACED WATER CITION WAVES & TICK	
Municipal G Irrigation G Industrial C Other G		
industrial C Other O centent grout placed by memie. 2. Minimum seal depth for manitoring wells is the maximum depth proceduable or 20 feet. Mud Rotary C Air Rotary D Auger O Coble O Other C Confection Reco D Backfill bore hole with compacted cuttings or heavy bentonite and upper two feet with compacted cuttings or heavy bentonite and upper two feet with compacted cuttings. MELL PROJECTS Drill Hole Diameter On Maximum Casing Olameter On Number On Number On Number Of Borings Olameter On Number On Nu		
2. Minimum seal depth for monitoring wells is the maximum depth practicable or 20 feet. Mud Rotary G Air Rotary G Auger G Geole Golden G Confront of Gaze Geole G Other G Confront of Gaze Geole G Other G Confront of Gaze Geole Golden G Geole Golden G Geole G G Geole G G G G G G G G G G G G G G G G G G G	· · · · · · · · · · · · · · · · · · ·	
Mud Rotary G Air Rotary G Auger G Confactors Auger G Detternion Auger G Confactors Auger G Detternion Auger G Confactors Auger G Detternion August Detternite and upper two feet with compacted cuttings or heavy bencomite and upper two feet with compacted cuttings or heavy bencomite and upper two feet with compacted cuttings. Nell PROJECTS Drill Hole Diameter in Maximum Depth S It Surface Seal Depth R. Number G. SPECIAL CONDITIONS Set attached. G. SPECIAL CONDITIONS DATE 7/30/98 Pereby agree to comply with all requirements of this permit and Confact Aury Set of Journal August Set Official Confact Aury Set of Journal August Set Official Confact Aury Set of Journal August Set Official Confact Aury Set of Journal August Set Official Confact Aury Set of Journal August Set Official Confact Aury Set of Journal August Set Official Confact Confact Aury Set of Journal August Set Official Confact Confac	indostriat C Other	
Mud Rotary G Air Rotary G Other C Confection accided to the Confection accidence accided to the Confection accidence accid	TRILLING METHOD:	
DRILLER'S LICENSE NO. A - HAZ 63828/ DRILLER'S LICENSE NO. A - HAZ 63828/ DRILLER'S LICENSE NO. A - HAZ 63828/ DRILLER'S LICENSE NO. A - HAZ 63828/ DRILLER'S LICENSE NO. A - HAZ 63828/ DRILLER'S LICENSE NO. A - HAZ 63828/ DRILLER'S LICENSE NO. A - HAZ 63828/ DRILLER'S LICENSE NO. A - HAZ 63828/ DRILLER'S LICENSE NO. A - HAZ 63828/ DRILLER'S LICENSE NO. A - HAZ 63828/ Drill PROJECTS Drill Hole Diameter in Maximum Depth 5 ft F. WELL DESTRUCTION See attached. G. SPECIAL CONDITIONS DATE 7/30/98		· ·
DRILLER'S LICENSE NO. A - HAZ 638281 DRILLER'S LICENSE NO. A - HAZ 638281 NELL PROJECTS Drill Hole Dismoster in Maximum Casing Diameter 2 in Depth 15 ft Number 6 Borings Maximum See allocked. GEOTECHNICAL PROJECTS Number of Borings Maximum Hole Diameter in Depth 6. SESTIMATED STARTING DATE 8/10/98 ESTIMATED COMPLETION DATE 8/10/98 ESTIMATED COMPLETION DATE 8/10/98 LESTIMATED COM		
DRILLER'S LICENSE NO. How of suspected contamination, tremted econent grout shall be used in place of compasted curings. Drill Hole Dismoster		,
Casing Diameterin	DRILLER'S LICENSE NO. A- HAVE 638281	
Drill Hole Dismerer in Maximum Casing Diameter 2 in Depth 15 ft Surface Scal Depth ft. Number George Projects Number of Borings Maximum Hole Diameter in Depth ft. D		
Casing Diameter 2 in. Depth 15 ft Surface Scal Depth		
Surface Seal Depth		
SECTECHNICAL PROJECTS Number of Borings Neximum Hole Diameter in. Depth Depth APPROVED DATE 7/30/98 APPROVED DATE APPROVED APPROVED APPROVED Confact Confact Lawy Seto for apparvel APPROVED Confact Confact Lawy Seto for apparvel		(F.) WELL DESTRUCTION
Number of Borings in. Depth ft. ESTIMATED STARTING DATE st. Depth ft. ESTIMATED COMPLETION DATE st. St. St. St. St. St. St. St. St. St. S	Surface Seat DepthR. Number	
Number of Borings Maximum Hole Diameter in. Depth n. ESTIMATED STARTING DATE 8/10/98 ESTIMATED COMPLETION DATE 8/15/98 hereby agree to comply with all requirements of this permit and Alameda County Ordinance No. 73-69. Confact Larry Seto for apparel	SECTECHNICAL OPERIECTS	G. SPECIAL CONDITIONS
Hole Diameter in. Depth 1. ESTIMATED STARTING DATE 8/10/98 ESTIMATED COMPLETION DATE 8/15/98 hereby agree to comply with all requirements of this permit and liameda County Ordinance No. 73-69. Confact Larry Seto for approvel	Number of Borings Maximum	
APPROVED DATE 8/10/98 APPROVED DATE 1/30/98 hereby agree to comply with all requirements of this permit and lameda Country Ordinance No. 73-69. Contact Lawy Seto for approved	0.1 5	۸
hereby agree to comply with all requirements of this permit and . Alameda County Public Health	2/ 1/20	/\
hereby agree to comply with all requirements of this permit and . Alameda County Public Health	ESTIMATED STARTING DATE 8/10/98	1/12/1/20
hereby agree to comply with all requirements of this permit and Clameda County Ordinance No. 73-63. Confact Larry Seto for apparel SPLICANT'S H. B. Duty TONATURE H. B. Duty TONATURE 10. Duty TONATU	SIMATED COMPLETION DATE	APPROVED DATE / / PO(1)
Contact Larry Seto for against 1000 TO 527-6700	hereby Agree to comply with all requirements of this account	Al- A Part A Part Hard
OPPLICANT'S H.B. Duty 1/29/98 Contact larry Seto for apparel	Ulameda County Ordinance No. 73-69.	Wanida Como Tanto mater
PRICANT'S H. B. Duty 7/29/98 510-527-6700		Contact Rang Seto for againel
	INNATURE H.B. Dut	510-527-6700

DATE 7/29/98

JUL ED 1982 GBICS FR ALA CO FUB WK HAD REA

210 LO 213028221568

p,02/02



ALAMEDA COUNTY PUBLIC WORKS AGENCY

n Ayward, ca 64246-2641 Godfrey fax (5) FAX (\$10) 610-8262

ų į	8.7.公康
	7 -

PUBLIC WORKS	VATER RESOURCES SECTION 141 TURNER COURT, SUITE 100. H. PHONE (510) 670-3373 ANDREAS ((510) 670-3348 ALVIN KAN
--------------	--

DRILLING PERMI	T APPLICATION
	for office van
FOR APPLICANT TO COMPLETE	PERMIT NUMBER 98 WIZ 352
	HERMIT NUMBER
EATION OF PROJECT 208 Jackson	WELL HUMBER
Och B	APN
	PERMIT CONDITIONS
ilomis Coordinates Source II. Accuracy = II. N. CCS II. Attacte & Sefe Place	Circled Permit Requirements Apply
N Sic attacked Site Plans	
	A.) GENERAL 1. A permit application should be submitted so as to
18NT SNK Development she Suite 1200	arrive at the ACPWA office five days prior to the
me 185 Bear 7 St Phone 415 - 876-1186	and complete date.
y Same Francisco CA 219 94107	A William A COM A Within 60 days after completion of
	- transfer the continual Health Will Transfer
PRICANT 'C , A n	Description Well Dellers Report of adelyticit in
PRICANDietz Jugation Fix 209 833 1288	well projects, or drilling logs and location sketch for
* * * * * * * * * * * * * * * * * * *	managhareal aroings.
ddress \$6/7 etalswerry Dr Phone 201832-29/0	3. Permit is void if project not begun within 90 days of
ly TANGE CA CA CID 475 3 76	approval date.
, J	B. WATER SUPPLY WELLS
PE OF PROJECT Geolechnical Investigation	1. Minimum surface seal thickness is two inches of
WEN CONSTRUCTION	cement grout placed by fremie.
Cathodic Franceiton	2. Minimum seal depth is 50 feet for municipal and
Water supply	industrial wells or 20 feet for domestic and irrigation
Monitorins Well Destruction G	wells unless a lesser depth is specially approved.
ROPOSED WATER SUPPLY WELL USE	C. GROUNDWATER MONITORING WELLS
New Domestic O Replacement Domestic C	INCLUDING PIEZOMETERS
	1. Minimum surface seal thickness is two inches of
	coment grout pieced by wentle.
THE STATE OF THE S	2. Minimum seal depth for monitoring wells is the maximum depth practicable or 20 feet.
RILLING METHOD: Mud Romry G Air Rotary G Auger 🔀	b. GEOTECHNICAL
Mud Rowry G Air Rowry G Auger PA Cable G Other C	Backfill bore hale with compacted cuttings or heavy
	benionite and upper two fact with compacted material.
DRILLER'S LICENSE NO. C-57 # 485/65	In areas of known or suspected contamination, tremied
Michael O Diduction in the	content grout shall be used in place of compacted durings
VELL PROJECTS 5"	E. CATHODIC
Drill Hole Dismeter O in. Maximum	Fill hole above anode zone with concrete placed by wemi
Casing Diameter 2 in. Depth 12	F. WELL DESTRUCTION
Surface Scal Depth 6 ft. Number 3	See attached.
	G. SPECIAL CONDITIONS
leotechnical projects	
Number of Barings Maximum	λ
Hole Diameter in Depth fi.	\bigwedge) 1 \rightarrow
ISTIMATED STARTING DATE 8/24/98	APPROVED DATE 8 8
SIMA (EU SIAKINA DA) E	APPROVED DATE DATE
STIMATED COMPLETION DATE \$ /26/58	

** YOTAL PAGE.02 **

.PPLICANT'S

Ismeda County Ordinance No. 73+08

DEVELOPMENT SERVICES DEPARTMENT • 1330 BROADWAY • OAKLAND, CALIFORNIA 94612

TDD 839-6451

10/22/98

REC'D NOV 02 1998

SNK Development Inc. 185 Berry Street, Suite 1200 San Francisco, CA 94107-1729 Attn: Stewart Gruendl

RE: MINOR ENCROACHMENT PERMIT FOR MONITORING WELLS ADJACENT TO

SECOND AND MADISON STREET, OAKLAND, CALIFORNIA

Dear Mr. Gruendl:

Enclosed is a Minor Encroachment Permit and Agreement allowing you to install two monitoring wells on Second and Madison Street right of way adjacent to the property at 208 Jackson Street, Oakland.

Before the permit will become effective, however, it must be signed by the owner of the property. The signature must be properly notarized, as described on the attached notice. The signed and notarized document should then be returned to this office to the attention of Kha T. Hoang for recordation.

If you have any questions, please call Kha T. Hoang at 238-6320 any weekday from 9:00 A.M. to 1:00 P.M.

Sincerely,

CALVIN N. WONG
Chief of Building Services

By:

PHILIP A. GRUBSTICE

Engineering Services Manager

Enclosures

Recording Requested by: CITY OF OAKLAND

When Recorded Mail to:
City of Oakland
Community & Economic
Development Agency
Building Services Division,
Engineering Information
250 Frank H. Ogawa Plaza, 2nd Floor
Oakland, CA 94612

TAX ROLL PARCEL NUMBER (ASSESSOR'S REFERENCE NUMBER)

001	159	006	
MAP	BLOCK	PARCEL	SUB

Address:

208 Jackson Street Oakland, California

Space Above for Recorder's Use Only

MINOR ENCROACHMENT PERMIT AND AGREEMENT

SNK Allegro at JLS LLC, the owner of certain real property described in the Grant Deed number 98243358, dated July 10th, 1998, commonly known as 208 Jackson Street, Oakland, Alameda County, California is hereby granted a Conditional Revocable Permit to encroach into the public right-of-way of Madison Street and Second Street in Oakland with ground-water monitoring wells. The location of said encroachments shall be as delineated in Exhibit 'A' attached hereto and made a part hereof.

The permittee agrees to comply with and be bound by the conditions for granting an Encroachment Permit attached hereto and made a part hereof.

This agreement shall be binding upon the undersigned, the present owner of the property described above, and their successors in interest thereof.

	resident of SNK Allegro at JLS LLC, have set my signature this
day of November , 1998	·
(SNK ALLEGRO AT JLS LLC
	STEWART GRUENWAY Stuart Gruendl
	Executive Vice President of SNK JLS Inc., Managing Member
Dated:	Den
Data.	Bv:

CALVIN N. WONG

Chief of Building Services

For:

WILLIAM E. CLAGGETT
Director of Community & Economic
Development Agency

0

TO EXCAVATE IN STREETS OR OTHER SPECIFIED WORK

CIVIL ENGINEERING

PAGE 2 of 2

APPOON START DATE APPOON END DATE 2-HOUR EMERCENCY PHONE NUMBER OF SECURITY 3/96 CITY BURNESS AX # ATTENTION State from read in execution from the Continuence in the first for the following reason (for CITY) and a moving flow before exervings. This permit is easy will uncare applicately but secured an equity from the continuence intended by CIA. The USA attendance number is 1 3001 outcomed. The CITY BURNESS AX # Burness prior to starting work, YOU MUST CALL (\$10) 238-3651 TO SCHEDULE AN INSPECTION. OWNESS/BURLESS 1 Benches prior to starting work, YOU MUST CALL (\$10) 238-3651 TO SCHEDULE AN INSPECTION. OWNESS/BURLESS 1 Benches prior to starting work, YOU MUST CALL (\$10) 238-3651 TO SCHEDULE AN INSPECTION. OWNESS/BURLESS 1 Benches prior to starting work, YOU MUST CALL (\$10) 238-3651 TO SCHEDULE AN INSPECTION. OWNESS/BURLESS 1 Benches prior to starting work, YOU MUST CALL (\$10) 238-3651 TO SCHEDULE AN INSPECTION. OWNESS/BURLESS 1 Benches prior to starting work, YOU MUST CALL (\$10) 238-3651 TO SCHEDULE AN INSPECTION. OWNESS/BURLESS 1 Benches prior to starting the Continuence in the prior to the p	PERNAT NUMBER	SITE ADDRESS/LOCATION	
CTY BUSINESS TAX # CTYPHON State how requires that the occuration owner tail **Indept pound for the color of the color o	1 25. 5 V	208 TALKERY STEERT NEAR COUNTY	
CTY DESIRES TAX # CTY DESIRES TAX # CTY DESIRES TAX # CTY DESIRES TAX # CTY DESIRES TAX # CTY DESIRES TAX # CTY DESIRES TAX # CTY DESIRES TAX # CTY DESIRES TAX # CTY DESIRES TAX # ATTENTION State low requires that the consenseror word and **/independent Service Air** / 1/5/10 and nonecoding date before excession from the consenseror is used by 15/3. The UPA attention contact of the content of the Content of the UPA attention of the UPA attention of the Content of the UPA attention of the Content of t	PROOF STATE DATE	24 HOUR EMERGENCY PHONE NUMBER OF SECOND ST +	
CTY DESIRES TAX # CTY DESIRES TAX # CTY DESIRES TAX # CTY DESIRES TAX # CTY DESIRES TAX # CTY DESIRES TAX # CTY DESIRES TAX # CTY DESIRES TAX # CTY DESIRES TAX # CTY DESIRES TAX # ATTENTION State low requires that the consenseror word and **/independent Service Air** / 1/5/10 and nonecoding date before excession from the consenseror is used by 15/3. The UPA attention contact of the content of the Content of the UPA attention of the UPA attention of the Content of the UPA attention of the Content of t		(Permit not valid without 24-Hour number) MADISON	
ATTENTION D. Size how requires that the continuous rated by USA. The USA alephone number is 1700 602-2044. UNDERGROUND SERVICE ALERT (USA) if SCENCY 4 23. As hours prior to starting work, YOU MUST CALL (S10) 238-3651 TO SCHEDULE AN INSPECTION. CALLED 1 1 200 602-2044. UNDERGROUND SERVICE ALERT (USA) if SCENCY 4 24. Bretty allow that I an except from the Contraint's Lorent Low for the following reason (for, III) 3 Business and Frontenions Color. App one county which requires a permit to construct, their, majority, described, or report any quantity, prior is to attacked. It is required to the property of the contract, their, majority, described, or report any quantity, prior is to attacked. The prior to the contract, their, majority, described, or report any quantity or property of the District of the Contract, their, majority, or any majority or approach for a permit to the work, and the structure is not another to the interpretation of the Contract, and the structure of the contract to chiral property of the contract of the property, or any employers with single at the structure of the property, or any employers with single at the structure of the property, or any employers with single at the structure of the property, or any employers with a supple of state. Professional Contract of the property, or any employers with a supple of the state of the property, or any employers with a structure of the property, or any employers with the structure of the property, or any employers with the state of the property, or any employers with the state of the property, or any employers with the state of the property, or any employers with the state of the property, or any employers with the state of the property, or any employers with the state of the property, or any employers with the state of the property, or any employers with the state of the property, or any employers with the state of the property, or any employers with the state of the property, ore any employers with the state of the property, or any employers			
ATTENTION District from recurrent that the containstant amount will Made spround Survey after all Std man working slave before excerving. This permit is not which under a applicate has secured an analyzi introduction number is smoothly U.S The U.S. adoptions number in 1.300 one-244. UNDEROROUND SERVICE ALERT (U.S.) of SCECO 44 3. 48 hours prior to startling work, YOU MUST CALL (510) 238-3651 TO SCHEDULE AN INSPECTION. CALLOU U.S. A security of the containing of the Conta			
State his motives that the contrasted sweet stall "Industry and Survey Africa" (ISA) is a worker of professor and an analysis of the USA africance survey by USA. The USA africance survey of USA is USA africance survey of USA is USA africance survey of USA is USA africance survey. The USA africance survey of USA is USA africance survey of USA is USA africance survey. The USA africance survey of USA is USA africance survey of USA is USA africance survey of USA is USA africance survey. According to the USA africance survey of USA is USA africance survey of USA is USA africance survey. According to the USA africance survey of USA is USA africance survey of USA is USA africance survey. According to the USA africance survey of USA is USA africance survey of USA is USA africance survey. According to USA africance survey of USA is USA africance survey of USA is USA africance survey. According to USA africance survey of USA is USA africance survey of USA africance survey of USA is USA africance survey. According to USA africance survey of USA africance su			
OWNERSONATION Interch willing well an exempt from the Contention's Learne Law for the following reason (Sec. 7011.3 Business and Professions). Code: Any only or county which requires a permit to institute, where inspired, elementary with the contention of the contention's Lieument that the a timesed possition of the contention's Lieument than the attemption. Any violation of Section 7031.5 by any represent of the contention's Lieument law (Lieument) and the 2000 for Contention's Lieument law (Lieument) and the 2000 for a permit subject the epiticate or a crist genus and Treatment and the secrety theoretical description. Any violation of Section 7031.5 by any represent of the epiticate ecomption. Any violation of Section 7031.5 by any represent of the property, and the day of the contention of the contention of Section 7031.5 by any represent of the epiticate of the property on any completers with Angels as their solic contention, will not be work and the contention of the property and the day of the property and the property of the property and property of the property and property of the property of the property of the property of the property of the property of the property of the property of the property of the property of the property of the property of the property of the property of the property of the property of the	1) State law requires that the contrastor/owner :all Underground Se moduly identification number tasked by USA. The USA relephon	ac dilinoer is 1 - 5001 042-2443. On Obligation October 15 1 - 5001 042-2443.	
OWNERSONATION Interch willing well an exempt from the Contention's Learne Law for the following reason (Sec. 7011.3 Business and Professions). Code: Any only or county which requires a permit to institute, where inspired, elementary with the contention of the contention's Lieument that the a timesed possition of the contention's Lieument than the attemption. Any violation of Section 7031.5 by any represent of the contention's Lieument law (Lieument) and the 2000 for Contention's Lieument law (Lieument) and the 2000 for a permit subject the epiticate or a crist genus and Treatment and the secrety theoretical description. Any violation of Section 7031.5 by any represent of the epiticate ecomption. Any violation of Section 7031.5 by any represent of the property, and the day of the contention of the contention of Section 7031.5 by any represent of the epiticate of the property on any completers with Angels as their solic contention, will not be work and the contention of the property and the day of the property and the property of the property and property of the property and property of the property of the property of the property of the property of the property of the property of the property of the property of the property of the property of the property of the property of the property of the property of the property of the	25 48 hours prior to starting work, YOU MI	UST CALL (510) 238-3651 TO SCHEDULE AN INSPECTION.	
Therethy stifting dust if an executed from the Continuous's Longer Law for the following reason (Sec. 2011). Business and Professional Code: Any only or county which requires a permit to construct, stars, suprove, danielith, or reper any steadants, prior to its instance, star requires the applicated for the permit subject of continuous and continuous Codes on the business and Professional Codes. or that he is exempt therefore, and the best for the target according to the Continuous Codes on the business and Professional Codes. or that he is exempt therefore, and the best for the target according to the permit subject of the permit subject of the permit subject of the permit subject and permit subject to the work, and the structure's not intraded or offered for all its continuous codes and work manual for strongly and subject or strongly can be all the Study or any page of the permit subject to the work, and the structure's not intraded or offered for all its continuous codes and work manual for strongly into one employees. The permit subject of property when the permit or the permit subject of property and he did not bound or suprove the purpose of the permit subject of property and the loss of the permit subject of property and the loss of the permit subject of permit subject or permit subject on the work, and the structures more than one carries for the size requirements of the above one to subject to the property, and extensively continuous of the above one complete to the property who boulds or supposed to the permit subject to the property and permit subject to the work, and the time research of the Information of the property and permit subject to the work of the property and permit subject to the work. See Total property who boulds or represent subject to the work of the property and permit subject to the work of the property and permit subject to the permit subject to the permit subject to the permit subject to the permit subject to the permit subject to the permit subject to the permit subject to the p	AWNERHIII DER	-	
Policy #	thereby stilling that I am exempt from the Constantor's Loense Law for the following reason (Sec. 703) 5 Business and Professions Code: Any city or county which requires a permit to constant, after, improve, demolish, or repair any structure, prior to its issuance, also requires the applicant for such permit to file a signed statement that he is themseld puissant to the provisions of the Contractor's License Law (Lingter 2 feormencing with Sec. 7000) of Divisions of the Business and Professions Code, or that he is exempt therefrom and the basis for the provisions of the Contractor's License Law (Lingter 2 feormencing with Sec. 7000) of Divisions of the Business and Professions Code, or that he is exempt therefrom and the basis for the provisions of the Contractor's License Law deed or a permit adjust to a permit subjects the applicant to a civil penalty of not more than \$5000:		
Policy #	WORKER'S COMPENSATION		
Policy #	I hereby affirm that I have a ceruit and of themselves of 4 cer	ruffeste of Worker's Compensation Insurance, or a certified copy thereof (Sec. 3700). Labor Code)	
1 Seruty that in the performance of the work for which this points is issued, I shall not employ any person in any manner so as to become subject to the Worker's Compensation Laws of California finite required for work valued at one fundred dollars (\$100) or less) NOTICE TO APPLICANT. If, after making this Comficate of Exemption, you should become subject to the Worker's Compensation provisions of the Labor Gode, you must forthwith comply with such prevailable to decrease revocate. This permit is used pursuant to all provisions of Title 12 Chapter 12.12 of the Oakland Municipal Code. It is granted upon the express condition that the permits and be responsible for all claurs and institutes arising out of work performed under the permit or arising out of permitters to defined, administry, save and hold harmless the Clay, its officers and employees from and sgainst any and all suits, claims, as accounts by any person for or on account of any bodily injuried, discass or illuses or damage to persons and/or propert and employees from and sgainst any and all suits, claims, as accounts by any person for or on account of any bodily injuried, discass or illuses or damage to persons and/or propert and employees from and sgainst any and all suits, claims, as accounts by any person for or on account of any bodily injuried, discass or illuses or damage to persons and/or propert and employees from and sgainst any and all suits, claims, as accounts by any person for or on account of any bodily injuried, discass or illuses or damage to persons and/or propert and employees from and sgainst any and all suits, claims, as accounts by any person for or on account of any bodily injuried, discass or illuses are damage to persons and/or propert and employees from the construction of the work persons and or on account of any bodily injuried, discass or illuses are damage to persons and/or propert and employees from the construction of the construction of the construction of the construction of the construction of the construction of th	Police # Company Na	mc	
comply with such previation of this permit shall be deemed revocate. This permit we all claims and liabilities arising out of work performed ladder the permit or arising out of permittee is failure to granted upon the capters condition that the permittee shall, and by acceptance of the permit agrees to defined, indemnify, save and bold harmlers the City, its officers and employees from and against any and all suits, claims. As actions brought by any person for or on account of any boddy injuries, disease or illness or damage to persons and/or propert sustaines or arising in the construction of the work performed under the permit or in consequence of permittee's failure to perform the colligations with respect to stress maintenance. This permit is and 30 days from the date of satisfies an extension is granted by the Director of the Office of Planuing and Building. I hereby affirm that then increased under approximant of Chapter 9 of Division 3 of the Business and Professions Code and my literate is in full force and effect (if contractor) that I have reason permit and agree to its well-increased, and that the spove information is true and correct under penalty of law. Sugnation of Permittee Agent for the Contractor of Owner Date Date Date Libert HD OPERATION AREA? REQUIRED? Date 3 NO (NOV) - IAN I) Sayes and (TAM-SAM & 4PM-6PM) Sayes of NOV 1-IAN I) DATE ISSUED	On the surface in the performance of the work for which this points is issued, I shall not employ any person in any marker so as to become subject to the Worker's Compensation Laws		
Suprantice in Permittee	comply with such previous or this permit shall be decrized revocat. This permit shall shall see product a provision shall be decrized revocat. This permit shall shall see a same out of work performed ander the permit or arising out of permitted to granted upon the capress condition that the permitted shall be responsible for all claims and liabilities arising out of work performed andersuify, save and hold harmless the City, its officers perform the obligations with respect to street maintenance. The permitted shall, and by acceptance of the permitted of any bodily injuried, disease or illness or damage to persons and/or property and employees from and against any and all suits, claims, or account by any person for or on account of any bodily injuried, disease or illness or damage to persons and/or property and employees from and against any and all suits, claims, or account to property and employees from and against any and all suits, claims, or account of the permitted of any bodily injuried, disease or illness or damage to persons and/or property and employees.		
DATE SCREAT LAST SPECIAL PAYING DETAIL HOLDAY RESTRICTION? REQUIRED? 0 YES 7 NO (NOV) - JAN 1) SYES S NO (TAM-9AM & 4PM-6PM) SYES ONO ISSUED BY	11/20/98		
ABSURFACED REQUIRED? DYES 7 NO (NOV 1 - JAN 1) 2 YES 2 NO (TAM-9AM & 4PM-4PM) 2 YES 0 NO (SSUED)		Title 1	
ISSIGN BY DATE ISSUED		THE ACT AND THE C NO	
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1			