

## Detterman, Mark, Env. Health

---

**From:** Evans, Charlotte [Cevans@croworld.com]  
**Sent:** Wednesday, March 17, 2010 10:54 AM  
**To:** Detterman, Mark, Env. Health  
**Subject:** RE: RO 143 / Harrison St - Risk Assessment - A Couple of Questions  
**Attachments:** 9-0020 Risk Tables - Shallow Soil.pdf; 9-0020 Risk Tables - Deep Soil.pdf

Hi Mark,

Here are the responses to your questions:

Is there a reason that an adult non-cancer hazard was not calculated? Typically it is both that I've seen before. Only the child was calculated (while both adult and child cancer risks were calculated for the letter report). This is a question, not a request (at this point).

Hazard evaluation of a potential child resident receptor, i.e., estimation of noncancer hazard, is more conservative for child residents than adult residents. By nature of the way hazard indices are calculated, the lower average body weight and exposure duration for children always result in a hazard index equal to or higher than that that would be calculated for an adult resident. This would not impact the conclusions of the assessment.

I also noticed that the "data entry sheet" and the "intermediate calculations sheet" for the TPH portion of the calcs were not included in the attachment. And there's a similar issue for all the deep soil calculations. I presume both should be? (A side question, do the "intermediate" sheets allow for user input, or are they program calculations?)

Originally, the TPH fraction tables were not included (an oversight), but are now attached. The correct pages that should have been included from the SG-SCREEN model in the assessment are the "DATAENTER" and "INTERCALCS" pages. In general, the "DATAENTER" page contains all of the site-specific input values including among others: COPC, concentration of COPC in soil gas, depth below grade to bottom of enclosed space floor, soil gas sampling depth below grade, soil type and soil parameters. The "INTERCALCS" page provides the predicted indoor air concentration (infinite source building concentration) based on the site-specific input parameters entered into the spreadsheet. The infinite source building concentration (from the "INTERCALCS" page) was post-processed in a separate risk/hazard spreadsheet that is more transparent by providing the exact exposure parameters that were used in the assessment (Table 3), and the most recent toxicity criteria that were used (in this case from the CalEPA OEHHA Toxicity Criteria Database and USEPA Integrated Risk Information System as shown in Table 4). This is a typical approach used by risk assessors.

And finally the "Exposure Frequency" input looks to be 250 days and not 350 days as cited in Table 3 (in this and the Dec 30<sup>th</sup> report). With luck these were just the wrong printouts? Guess I shoulda noted this earlier...

Use of the 350 days/year and 30 years for noncancer averaging time and exposure duration does not impact the infinite source building concentration. They are independent of each other. As it stands, the estimates presented in Tables 5 and 6 are correct. To avoid confusion, attached are all revised tables with the resident exposure parameters inserted. This will not impact the conclusions of the assessment.

If you would like me to resubmit the Revised Risk Assessment, I can. Or let me know if you have any additional questions.

Thanks.


---

**Charlotte Evans**  
**Conestoga-Rovers & Associates (CRA)**

Tel: 510-420-3351

Email: [cevans@croworld.com](mailto:cevans@croworld.com)

Perform every task the safe way, the right way, every time!

Think before you print 

---

**From:** Detterman, Mark, Env. Health [mailto:Mark.Detterman@acgov.org]

**Sent:** Friday, March 12, 2010 11:33 AM

**To:** Evans, Charlotte

**Subject:** RO 143 / Harrison St - Risk Assessment - A Couple of Questions

Hi Charlotte,

I was trying to do a speedy review of your recent submittal, but ran into a few questions. Hopefully they are somewhat simple to respond to, but they may not be.

Is there a reason that an adult non-cancer hazard was not calculated? Typically it is both that I've seen before. Only the child was calculated (while both adult and child cancer risks were calculated for the letter report). This is a question, not a request (at this point).

I also noticed that the "data entry sheet" and the "intermediate calculations sheet" for the TPH portion of the calcs were not included in the attachment. And there's a similar issue for all the deep soil calculations. I presume both should be? (A side question, do the "intermediate" sheets allow for use input, or are they program calculations?)

And finally the "Exposure Frequency" input looks to be 250 days and not 350 days as cited in Table 3 (in this and the Dec 30<sup>th</sup> report). With luck these were just the wrong printouts? Guess I shoulda noted this earlier...

Hopefully these are just simple oversights. Let me know what you find; you might initially just email the items here for a quicker review, but then ultimately put together a revised risk assessment (once we both figure the best route forward)?

Thanks,

*Mark Detterman*

*Hazardous Materials Specialist, PG, CEG*

*Alameda County Environmental Health*

*1131 Harbor Bay Parkway*

*Alameda, CA 94502*

*Direct: 510.567.6876*

*Fax: 510.337.9335*

*Email: [mark.detterman@acgov.org](mailto:mark.detterman@acgov.org)*

*PDF copies of case files can be downloaded at:*

*<http://www.acgov.org/aceh/lop/ust.htm>*

DATA ENTRY SHEET

Table A-1. Maximum Benzene Shallow Soil Vapor Concentration

DTSC  
Vapor Intrusion Guidance  
Interim Final 12/04  
(last modified 2/4/09)

SG-SCREEN  
PA Version 2.0; 04/

Reset to  
Defaults

Soil Gas Concentration Data				
ENTER Chemical CAS No. (numbers only, no dashes)	ENTER Soil gas conc., $C_g$ ( $\mu\text{g}/\text{m}^3$ )	OR	ENTER Soil gas conc., $C_g$ (ppmv)	Chemical
71432	3.70E+01			Benzene

MORE  
↓

ENTER Depth below grade to bottom of enclosed space floor, $L_F$ (15 or 200 cm)	ENTER Soil gas sampling depth below grade, $L_s$ (cm)	ENTER Average soil temperature, $T_s$ ( $^{\circ}\text{C}$ )	ENTER Vadose zone SCS soil type (used to estimate soil vapor permeability)	OR	ENTER User-defined vadose zone soil vapor permeability, $k_v$ ( $\text{cm}^2$ )
15	152.4	24	S		

MORE  
↓

ENTER Vadose zone SCS soil type Lookup Soil Parameters	ENTER Vadose zone soil dry bulk density, $\rho_b^A$ ( $\text{g}/\text{cm}^3$ )	ENTER Vadose zone soil total porosity, $n^V$ (unitless)	ENTER Vadose zone soil water-filled porosity, $\theta_w^V$ ( $\text{cm}^3/\text{cm}^3$ )	ENTER Average vapor flow rate into bldg. (Leave blank to calculate) $Q_{\text{soil}}$ (L/m)
S	1.83	0.324	0.279	5

MORE  
↓

ENTER Averaging time for carcinogens, $AT_C$ (yrs)	ENTER Averaging time for noncarcinogens, $AT_{NC}$ (yrs)	ENTER Exposure duration, ED (yrs)	ENTER Exposure frequency, EF (days/yr)
70	30	30	350

END

INTERMEDIATE CALCULATIONS SHEET

Table A-2. Maximum Benzene Shallow Soil Vapor Concentration

Source- building separation, $L_T$ (cm)	Vadose zone soil air-filled porosity, $\theta_a^v$ (cm <sup>3</sup> /cm <sup>3</sup> )	Vadose zone effective total fluid saturation, $S_{1e}$ (cm <sup>3</sup> /cm <sup>3</sup> )	Vadose zone soil intrinsic permeability, $k_i$ (cm <sup>2</sup> )	Vadose zone soil relative air permeability, $k_{rg}$ (cm <sup>2</sup> )	Vadose zone soil effective vapor permeability, $k_v$ (cm <sup>2</sup> )	Floor- wall seam perimeter, $X_{crack}$ (cm)	Soil gas conc., $C_{soil}$ (µg/m <sup>3</sup> )	Bldg. ventilation rate, $Q_{building}$ (cm <sup>3</sup> /s)
137.4	0.045	0.834	1.02E-07	0.055	5.62E-09	4,000	3.70E+01	3.39E+04

Area of enclosed space below grade, $A_B$ (cm <sup>2</sup> )	Crack- to-total area ratio, $\eta$ (unitless)	Crack depth below grade, $Z_{crack}$ (cm)	Enthalpy of vaporization at ave. soil temperature, $\Delta H_{v,TS}$ (cal/mol)	Henry's law constant at ave. soil temperature, $H_{TS}$ (atm·m <sup>3</sup> /mol)	Henry's law constant at ave. soil temperature, $H'_{TS}$ (unitless)	Vapor viscosity at ave. soil temperature, $\mu_{TS}$ (g/cm-s)	Vadose zone effective diffusion coefficient, $D_v^{eff}$ (cm <sup>2</sup> /s)	Diffusion path length, $L_d$ (cm)
1.00E+06	5.00E-03	15	7,977	5.29E-03	2.17E-01	1.80E-04	3.36E-05	137.4

Convection path length, $L_p$ (cm)	Source vapor conc., $C_{source}$ (µg/m <sup>3</sup> )	Crack radius, $r_{crack}$ (cm)	Average vapor flow rate into bldg., $Q_{soil}$ (cm <sup>3</sup> /s)	Crack effective diffusion coefficient, $D^{crack}$ (cm <sup>2</sup> /s)	Area of crack, $A_{crack}$ (cm <sup>2</sup> )	Exponent of equivalent foundation Peclet number, $\exp(Pe^f)$ (unitless)	Infinite source indoor attenuation coefficient, $\alpha$ (unitless)	Infinite source bldg. conc., $C_{building}$ (µg/m <sup>3</sup> )
15	3.70E+01	1.25	8.33E+01	3.36E-05	5.00E+03	#NUM!	7.19E-06	2.66E-04

Unit risk factor, URF (µg/m <sup>3</sup> ) <sup>-1</sup>	Reference conc., RFC (mg/m <sup>3</sup> )
2.9E-05	3.0E-02

END

DATA ENTRY SHEET

Table A-3. Maximum Chloroform Shallow Soil Vapor Concentration

DTSC  
Vapor Intrusion Guidance  
Interim Final 12/04  
(last modified 2/4/09)

SG-SCREEN  
PA Version 2.0; 04/

Reset to  
Defaults

Soil Gas Concentration Data				
ENTER Chemical CAS No. (numbers only, no dashes)	ENTER Soil gas conc., $C_g$ ( $\mu\text{g}/\text{m}^3$ )	OR	ENTER Soil gas conc., $C_g$ (ppmv)	Chemical
67663	1.00E+01			Chloroform

MORE  
↓

ENTER Depth below grade to bottom of enclosed space floor, $L_F$ (15 or 200 cm)	ENTER Soil gas sampling depth below grade, $L_s$ (cm)	ENTER Average soil temperature, $T_s$ ( $^{\circ}\text{C}$ )	ENTER Vadose zone SCS soil type (used to estimate soil vapor permeability)	OR	ENTER User-defined vadose zone soil vapor permeability, $k_v$ ( $\text{cm}^2$ )
15	152.4	24	S		

MORE  
↓

ENTER Vadose zone SCS soil type Lookup Soil Parameters	ENTER Vadose zone soil dry bulk density, $\rho_b^A$ ( $\text{g}/\text{cm}^3$ )	ENTER Vadose zone soil total porosity, $n^V$ (unitless)	ENTER Vadose zone soil water-filled porosity, $\theta_w^V$ ( $\text{cm}^3/\text{cm}^3$ )	ENTER Average vapor flow rate into bldg. (Leave blank to calculate) $Q_{\text{soil}}$ (L/m)
S	1.83	0.324	0.279	5

MORE  
↓

ENTER Averaging time for carcinogens, $AT_C$ (yrs)	ENTER Averaging time for noncarcinogens, $AT_{NC}$ (yrs)	ENTER Exposure duration, ED (yrs)	ENTER Exposure frequency, EF (days/yr)
70	30	30	350

END

INTERMEDIATE CALCULATIONS SHEET

Table A-4. Maximum Chloroform Shallow Soil Vapor Concentration

Source-building separation, $L_T$ (cm)	Vadose zone soil air-filled porosity, $\theta_a^v$ ( $\text{cm}^3/\text{cm}^3$ )	Vadose zone effective total fluid saturation, $S_{te}$ ( $\text{cm}^3/\text{cm}^3$ )	Vadose zone soil intrinsic permeability, $k_i$ ( $\text{cm}^2$ )	Vadose zone soil relative air permeability, $k_{rg}$ ( $\text{cm}^2$ )	Vadose zone soil effective vapor permeability, $k_v$ ( $\text{cm}^2$ )	Floor-wall seam perimeter, $X_{crack}$ (cm)	Soil gas conc., $(\mu\text{g}/\text{m}^3)$	Bldg. ventilation rate, $Q_{building}$ ( $\text{cm}^3/\text{s}$ )
137.4	0.045	0.834	1.02E-07	0.055	5.62E-09	4,000	1.00E+01	3.39E+04

Area of enclosed space below grade, $A_B$ ( $\text{cm}^2$ )	Crack-to-total area ratio, $\eta$ (unitless)	Crack depth below grade, $Z_{crack}$ (cm)	Enthalpy of vaporization at ave. soil temperature, $\Delta H_{v,TS}$ (cal/mol)	Henry's law constant at ave. soil temperature, $H_{TS}$ (atm- $\text{m}^3/\text{mol}$ )	Henry's law constant at ave. soil temperature, $H'_{TS}$ (unitless)	Vapor viscosity at ave. soil temperature, $\mu_{TS}$ (g/cm-s)	Vadose zone effective diffusion coefficient, $D_v^{eff}$ ( $\text{cm}^2/\text{s}$ )	Diffusion path length, $L_d$ (cm)
1.00E+06	5.00E-03	15	7,407	3.51E-03	1.44E-01	1.80E-04	4.19E-05	137.4

Convection path length, $L_p$ (cm)	Source vapor conc., $C_{source}$ ( $\mu\text{g}/\text{m}^3$ )	Crack radius, $r_{crack}$ (cm)	Average vapor flow rate into bldg., $Q_{soil}$ ( $\text{cm}^3/\text{s}$ )	Crack effective diffusion coefficient, $D^{crack}$ ( $\text{cm}^2/\text{s}$ )	Area of crack, $A_{crack}$ ( $\text{cm}^2$ )	Exponent of equivalent foundation Peclet number, $\exp(Pe^f)$ (unitless)	Infinite source indoor attenuation coefficient, $\alpha$ (unitless)	Infinite source bldg. conc., $C_{building}$ ( $\mu\text{g}/\text{m}^3$ )
15	1.00E+01	1.25	8.33E+01	4.19E-05	5.00E+03	#NUM!	8.96E-06	8.96E-05

Unit risk factor, URF ( $\mu\text{g}/\text{m}^3$ ) <sup>-1</sup>	Reference conc., RFC ( $\text{mg}/\text{m}^3$ )
5.3E-06	3.0E-01

END

DATA ENTRY SHEET

Table A-5. Maximum Ethylbenzene Shallow Soil Vapor Concentration

DTSC  
Vapor Intrusion Guidance  
Interim Final 12/04  
(last modified 2/4/09)

SG-SCREEN  
PA Version 2.0; 04/

Reset to  
Defaults

Soil Gas Concentration Data				
ENTER Chemical CAS No. (numbers only, no dashes)	ENTER Soil gas conc., $C_g$ ( $\mu\text{g}/\text{m}^3$ )	OR	ENTER Soil gas conc., $C_g$ (ppmv)	Chemical
100414	1.70E+02			Ethylbenzene

MORE  
↓

ENTER Depth below grade to bottom of enclosed space floor, $L_F$ (15 or 200 cm)	ENTER Soil gas sampling depth below grade, $L_s$ (cm)	ENTER Average soil temperature, $T_s$ ( $^{\circ}\text{C}$ )	ENTER Vadose zone SCS soil type (used to estimate soil vapor permeability)	OR	ENTER User-defined vadose zone soil vapor permeability, $k_v$ ( $\text{cm}^2$ )
15	152.4	24	S		

MORE  
↓

ENTER Vadose zone SCS soil type Lookup Soil Parameters	ENTER Vadose zone soil dry bulk density, $\rho_b^A$ ( $\text{g}/\text{cm}^3$ )	ENTER Vadose zone soil total porosity, $n^V$ (unitless)	ENTER Vadose zone soil water-filled porosity, $\theta_w^V$ ( $\text{cm}^3/\text{cm}^3$ )	ENTER Average vapor flow rate into bldg. (Leave blank to calculate) $Q_{\text{soil}}$ (L/m)
S	1.83	0.324	0.279	5

MORE  
↓

ENTER Averaging time for carcinogens, $AT_C$ (yrs)	ENTER Averaging time for noncarcinogens, $AT_{NC}$ (yrs)	ENTER Exposure duration, ED (yrs)	ENTER Exposure frequency, EF (days/yr)
70	30	30	350

END

INTERMEDIATE CALCULATIONS SHEET

**Table A-6. Maximum Ethylbenzene Shallow Soil Vapor Concentration**

Source- building separation, $L_T$ (cm)	Vadose zone soil air-filled porosity, $\theta_a^v$ ( $\text{cm}^3/\text{cm}^3$ )	Vadose zone effective total fluid saturation, $S_{te}$ ( $\text{cm}^3/\text{cm}^3$ )	Vadose zone soil intrinsic permeability, $k_i$ ( $\text{cm}^2$ )	Vadose zone soil relative air permeability, $k_{rg}$ ( $\text{cm}^2$ )	Vadose zone soil effective vapor permeability, $k_v$ ( $\text{cm}^2$ )	Floor- wall seam perimeter, $X_{crack}$ (cm)	Soil gas conc., $C_{soil}$ ( $\mu\text{g}/\text{m}^3$ )	Bldg. ventilation rate, $Q_{building}$ ( $\text{cm}^3/\text{s}$ )
137.4	0.045	0.834	1.02E-07	0.055	5.62E-09	4,000	1.70E+02	3.39E+04

Area of enclosed space below grade, $A_B$ ( $\text{cm}^2$ )	Crack- to-total area ratio, $\eta$ (unitless)	Crack depth below grade, $Z_{crack}$ (cm)	Enthalpy of vaporization at ave. soil temperature, $\Delta H_{v,TS}$ (cal/mol)	Henry's law constant at ave. soil temperature, $H_{TS}$ (atm- $\text{m}^3/\text{mol}$ )	Henry's law constant at ave. soil temperature, $H'_{TS}$ (unitless)	Vapor viscosity at ave. soil temperature, $\mu_{TS}$ (g/cm-s)	Vadose zone effective diffusion coefficient, $D_v^{eff}$ ( $\text{cm}^2/\text{s}$ )	Diffusion path length, $L_d$ (cm)
1.00E+06	5.00E-03	15	9,994	7.43E-03	3.05E-01	1.80E-04	2.69E-05	137.4

Convection path length, $L_p$ (cm)	Source vapor conc., $C_{source}$ ( $\mu\text{g}/\text{m}^3$ )	Crack radius, $r_{crack}$ (cm)	Average vapor flow rate into bldg., $Q_{soil}$ ( $\text{cm}^3/\text{s}$ )	Crack effective diffusion coefficient, $D^{crack}$ ( $\text{cm}^2/\text{s}$ )	Area of crack, $A_{crack}$ ( $\text{cm}^2$ )	Exponent of equivalent foundation Peclet number, $\exp(Pe^f)$ (unitless)	Infinite source indoor attenuation coefficient, $\alpha$ (unitless)	Infinite source bldg. conc., $C_{building}$ ( $\mu\text{g}/\text{m}^3$ )
15	1.70E+02	1.25	8.33E+01	2.69E-05	5.00E+03	#NUM!	5.76E-06	9.79E-04

Unit risk factor, URF ( $\mu\text{g}/\text{m}^3$ ) <sup>-1</sup>	Reference conc., RFC ( $\text{mg}/\text{m}^3$ )
2.5E-06	1.0E+00

**END**



DATA ENTRY SHEET

Table A-7. Maximum Naphthalene Shallow Soil Vapor Concentration

DTSC  
Vapor Intrusion Guidance  
Interim Final 12/04  
(last modified 2/4/09)

SG-SCREEN  
PA Version 2.0; 04/

Reset to Defaults

Soil Gas Concentration Data				
ENTER Chemical CAS No. (numbers only, no dashes)	ENTER Soil gas conc., $C_g$ ( $\mu\text{g}/\text{m}^3$ )	OR	ENTER Soil gas conc., $C_g$ (ppmv)	Chemical
91203	1.10E+02			Naphthalene

MORE  
↓

ENTER Depth below grade to bottom of enclosed space floor, $L_F$ (15 or 200 cm)	ENTER Soil gas sampling depth below grade, $L_s$ (cm)	ENTER Average soil temperature, $T_s$ ( $^{\circ}\text{C}$ )	ENTER Vadose zone SCS soil type (used to estimate soil vapor permeability)	OR	ENTER User-defined vadose zone soil vapor permeability, $k_v$ ( $\text{cm}^2$ )
15	152.4	24	S		

MORE  
↓

ENTER Vadose zone SCS soil type Lookup Soil Parameters	ENTER Vadose zone soil dry bulk density, $\rho_b^A$ ( $\text{g}/\text{cm}^3$ )	ENTER Vadose zone soil total porosity, $n^V$ (unitless)	ENTER Vadose zone soil water-filled porosity, $\theta_w^V$ ( $\text{cm}^3/\text{cm}^3$ )	ENTER Average vapor flow rate into bldg. (Leave blank to calculate) $Q_{\text{soil}}$ (L/m)
S	1.83	0.324	0.279	5

MORE  
↓

ENTER Averaging time for carcinogens, $AT_C$ (yrs)	ENTER Averaging time for noncarcinogens, $AT_{NC}$ (yrs)	ENTER Exposure duration, ED (yrs)	ENTER Exposure frequency, EF (days/yr)
70	30	30	350

END

INTERMEDIATE CALCULATIONS SHEET

Table A-8. Maximum Naphthalene Shallow Soil Vapor Concentration

Source-building separation, $L_T$ (cm)	Vadose zone soil air-filled porosity, $\theta_a^v$ ( $\text{cm}^3/\text{cm}^3$ )	Vadose zone effective total fluid saturation, $S_{te}$ ( $\text{cm}^3/\text{cm}^3$ )	Vadose zone soil intrinsic permeability, $k_i$ ( $\text{cm}^2$ )	Vadose zone soil relative air permeability, $k_{rg}$ ( $\text{cm}^2$ )	Vadose zone soil effective vapor permeability, $k_v$ ( $\text{cm}^2$ )	Floor-wall seam perimeter, $X_{crack}$ (cm)	Soil gas conc., ( $\mu\text{g}/\text{m}^3$ )	Bldg. ventilation rate, $Q_{building}$ ( $\text{cm}^3/\text{s}$ )
137.4	0.045	0.834	1.02E-07	0.055	5.62E-09	4,000	1.10E+02	3.39E+04

Area of enclosed space below grade, $A_B$ ( $\text{cm}^2$ )	Crack-to-total area ratio, $\eta$ (unitless)	Crack depth below grade, $Z_{crack}$ (cm)	Enthalpy of vaporization at ave. soil temperature, $\Delta H_{v,TS}$ (cal/mol)	Henry's law constant at ave. soil temperature, $H_{TS}$ (atm- $\text{m}^3/\text{mol}$ )	Henry's law constant at ave. soil temperature, $H'_{TS}$ (unitless)	Vapor viscosity at ave. soil temperature, $\mu_{TS}$ (g/cm-s)	Vadose zone effective diffusion coefficient, $D_v^{eff}$ ( $\text{cm}^2/\text{s}$ )	Diffusion path length, $L_d$ (cm)
1.00E+06	5.00E-03	15	12,768	4.48E-04	1.84E-02	1.80E-04	7.38E-05	137.4

Convection path length, $L_p$ (cm)	Source vapor conc., $C_{source}$ ( $\mu\text{g}/\text{m}^3$ )	Crack radius, $r_{crack}$ (cm)	Average vapor flow rate into bldg., $Q_{soil}$ ( $\text{cm}^3/\text{s}$ )	Crack effective diffusion coefficient, $D^{crack}$ ( $\text{cm}^2/\text{s}$ )	Area of crack, $A_{crack}$ ( $\text{cm}^2$ )	Exponent of equivalent foundation Peclet number, $\exp(Pe^f)$ (unitless)	Infinite source indoor attenuation coefficient, $\alpha$ (unitless)	Infinite source bldg. conc., $C_{building}$ ( $\mu\text{g}/\text{m}^3$ )
15	1.10E+02	1.25	8.33E+01	7.38E-05	5.00E+03	#NUM!	1.58E-05	1.73E-03

Unit risk factor, URF ( $\mu\text{g}/\text{m}^3$ ) <sup>-1</sup>	Reference conc., RFC ( $\text{mg}/\text{m}^3$ )
3.4E-05	3.0E-03

END

DATA ENTRY SHEET

Table A-9. Maximum Toluene Shallow Soil Vapor Concentration

DTSC  
Vapor Intrusion Guidance  
Interim Final 12/04  
(last modified 2/4/09)

SG-SCREEN  
PA Version 2.0; 04/

Reset to Defaults

Soil Gas Concentration Data				
ENTER Chemical CAS No. (numbers only, no dashes)	ENTER Soil gas conc., $C_g$ ( $\mu\text{g}/\text{m}^3$ )	OR	ENTER Soil gas conc., $C_g$ (ppmv)	Chemical
108883	6.00E+02			Toluene

MORE  
↓

ENTER Depth below grade to bottom of enclosed space floor, $L_F$ (15 or 200 cm)	ENTER Soil gas sampling depth below grade, $L_s$ (cm)	ENTER Average soil temperature, $T_s$ ( $^{\circ}\text{C}$ )	ENTER Vadose zone SCS soil type (used to estimate soil vapor permeability)	OR	ENTER User-defined vadose zone soil vapor permeability, $k_v$ ( $\text{cm}^2$ )
15	152.4	24	S		

MORE  
↓

ENTER Vadose zone SCS soil type Lookup Soil Parameters	ENTER Vadose zone soil dry bulk density, $\rho_b^A$ ( $\text{g}/\text{cm}^3$ )	ENTER Vadose zone soil total porosity, $n^V$ (unitless)	ENTER Vadose zone soil water-filled porosity, $\theta_w^V$ ( $\text{cm}^3/\text{cm}^3$ )	ENTER Average vapor flow rate into bldg. (Leave blank to calculate) $Q_{\text{soil}}$ (L/m)
S	1.83	0.324	0.279	5

MORE  
↓

ENTER Averaging time for carcinogens, $AT_C$ (yrs)	ENTER Averaging time for noncarcinogens, $AT_{NC}$ (yrs)	ENTER Exposure duration, ED (yrs)	ENTER Exposure frequency, EF (days/yr)
70	30	30	350

END

INTERMEDIATE CALCULATIONS SHEET

**Table A-10. Maximum Toluene Shallow Soil Vapor Concentration**

Source- building separation, $L_T$ (cm)	Vadose zone soil air-filled porosity, $\theta_a^v$ (cm <sup>3</sup> /cm <sup>3</sup> )	Vadose zone effective total fluid saturation, $S_{te}$ (cm <sup>3</sup> /cm <sup>3</sup> )	Vadose zone soil intrinsic permeability, $k_i$ (cm <sup>2</sup> )	Vadose zone soil relative air permeability, $k_{rg}$ (cm <sup>2</sup> )	Vadose zone soil effective vapor permeability, $k_v$ (cm <sup>2</sup> )	Floor- wall seam perimeter, $X_{crack}$ (cm)	Soil gas conc., $C_{soil}$ (µg/m <sup>3</sup> )	Bldg. ventilation rate, $Q_{building}$ (cm <sup>3</sup> /s)
137.4	0.045	0.834	1.02E-07	0.055	5.62E-09	4,000	6.00E+02	3.39E+04

Area of enclosed space below grade, $A_B$ (cm <sup>2</sup> )	Crack- to-total area ratio, $\eta$ (unitless)	Crack depth below grade, $Z_{crack}$ (cm)	Enthalpy of vaporization at ave. soil temperature, $\Delta H_{v,TS}$ (cal/mol)	Henry's law constant at ave. soil temperature, $H_{TS}$ (atm·m <sup>3</sup> /mol)	Henry's law constant at ave. soil temperature, $H'_{TS}$ (unitless)	Vapor viscosity at ave. soil temperature, $\mu_{TS}$ (g/cm-s)	Vadose zone effective diffusion coefficient, $D_v^{eff}$ (cm <sup>2</sup> /s)	Diffusion path length, $L_d$ (cm)
1.00E+06	5.00E-03	15	9,001	6.29E-03	2.58E-01	1.80E-04	3.17E-05	137.4

Convection path length, $L_p$ (cm)	Source vapor conc., $C_{source}$ (µg/m <sup>3</sup> )	Crack radius, $r_{crack}$ (cm)	Average vapor flow rate into bldg., $Q_{soil}$ (cm <sup>3</sup> /s)	Crack effective diffusion coefficient, $D^{crack}$ (cm <sup>2</sup> /s)	Area of crack, $A_{crack}$ (cm <sup>2</sup> )	Exponent of equivalent foundation Peclet number, $\exp(Pe^f)$ (unitless)	Infinite source indoor attenuation coefficient, $\alpha$ (unitless)	Infinite source bldg. conc., $C_{building}$ (µg/m <sup>3</sup> )
15	6.00E+02	1.25	8.33E+01	3.17E-05	5.00E+03	#NUM!	6.78E-06	4.07E-03

Unit risk factor, URF (µg/m <sup>3</sup> ) <sup>-1</sup>	Reference conc., RFC (mg/m <sup>3</sup> )
NA	3.0E-01

**END**

DATA ENTRY SHEET

Table A-11. Maximum Xylenes Soil Vapor Concentration

DTSC  
Vapor Intrusion Guidance  
Interim Final 12/04  
(last modified 2/4/09)

SG-SCREEN  
PA Version 2.0; 04/

Reset to Defaults

Soil Gas Concentration Data				
ENTER Chemical CAS No. (numbers only, no dashes)	ENTER Soil gas conc., $C_g$ ( $\mu\text{g}/\text{m}^3$ )	OR	ENTER Soil gas conc., $C_g$ (ppmv)	Chemical
106423	5.30E+02			p-Xylene

MORE  
↓

ENTER Depth below grade to bottom of enclosed space floor, $L_F$ (15 or 200 cm)	ENTER Soil gas sampling depth below grade, $L_s$ (cm)	ENTER Average soil temperature, $T_s$ ( $^{\circ}\text{C}$ )	ENTER Vadose zone SCS soil type (used to estimate soil vapor permeability)	OR	ENTER User-defined vadose zone soil vapor permeability, $k_v$ ( $\text{cm}^2$ )
15	152.4	24	S		

MORE  
↓

ENTER Vadose zone SCS soil type Lookup Soil Parameters	ENTER Vadose zone soil dry bulk density, $\rho_b^A$ ( $\text{g}/\text{cm}^3$ )	ENTER Vadose zone soil total porosity, $n^V$ (unitless)	ENTER Vadose zone soil water-filled porosity, $\theta_w^V$ ( $\text{cm}^3/\text{cm}^3$ )	ENTER Average vapor flow rate into bldg. (Leave blank to calculate) $Q_{\text{soil}}$ (L/m)
S	1.83	0.324	0.279	5

MORE  
↓

ENTER Averaging time for carcinogens, $AT_C$ (yrs)	ENTER Averaging time for noncarcinogens, $AT_{NC}$ (yrs)	ENTER Exposure duration, ED (yrs)	ENTER Exposure frequency, EF (days/yr)
70	30	30	350

END

INTERMEDIATE CALCULATIONS SHEET

**Table A-12. Maximum Xylenes Soil Vapor Concentration**

Source- building separation, $L_T$ (cm)	Vadose zone soil air-filled porosity, $\theta_a^v$ ( $\text{cm}^3/\text{cm}^3$ )	Vadose zone effective total fluid saturation, $S_{1e}$ ( $\text{cm}^3/\text{cm}^3$ )	Vadose zone soil intrinsic permeability, $k_i$ ( $\text{cm}^2$ )	Vadose zone soil relative air permeability, $k_{rg}$ ( $\text{cm}^2$ )	Vadose zone soil effective vapor permeability, $k_v$ ( $\text{cm}^2$ )	Floor- wall seam perimeter, $X_{crack}$ (cm)	Soil gas conc., $C_{soil}$ ( $\mu\text{g}/\text{m}^3$ )	Bldg. ventilation rate, $Q_{building}$ ( $\text{cm}^3/\text{s}$ )
137.4	0.045	0.834	1.02E-07	0.055	5.62E-09	4,000	5.30E+02	3.39E+04

Area of enclosed space below grade, $A_B$ ( $\text{cm}^2$ )	Crack- to-total area ratio, $\eta$ (unitless)	Crack depth below grade, $Z_{crack}$ (cm)	Enthalpy of vaporization at ave. soil temperature, $\Delta H_{v,TS}$ (cal/mol)	Henry's law constant at ave. soil temperature, $H_{TS}$ (atm- $\text{m}^3/\text{mol}$ )	Henry's law constant at ave. soil temperature, $H'_{TS}$ (unitless)	Vapor viscosity at ave. soil temperature, $\mu_{TS}$ (g/cm-s)	Vadose zone effective diffusion coefficient, $D_v^{eff}$ ( $\text{cm}^2/\text{s}$ )	Diffusion path length, $L_d$ (cm)
1.00E+06	5.00E-03	15	10,083	7.22E-03	2.96E-01	1.80E-04	2.79E-05	137.4

Convection path length, $L_p$ (cm)	Source vapor conc., $C_{source}$ ( $\mu\text{g}/\text{m}^3$ )	Crack radius, $r_{crack}$ (cm)	Average vapor flow rate into bldg., $Q_{soil}$ ( $\text{cm}^3/\text{s}$ )	Crack effective diffusion coefficient, $D^{crack}$ ( $\text{cm}^2/\text{s}$ )	Area of crack, $A_{crack}$ ( $\text{cm}^2$ )	Exponent of equivalent foundation Peclet number, $\exp(Pe^f)$ (unitless)	Infinite source indoor attenuation coefficient, $\alpha$ (unitless)	Infinite source bldg. conc., $C_{building}$ ( $\mu\text{g}/\text{m}^3$ )
15	5.30E+02	1.25	8.33E+01	2.79E-05	5.00E+03	#NUM!	5.97E-06	3.16E-03

Unit risk factor, URF ( $\mu\text{g}/\text{m}^3$ ) <sup>-1</sup>	Reference conc., RFC ( $\text{mg}/\text{m}^3$ )
NA	1.0E-01
<b>END</b>	

DATA ENTRY SHEET

Table A-13. Maximum Hexane (C5-C8 Aliphatics) Soil Vapor Concentration

DTSC  
Vapor Intrusion Guidance  
Interim Final 12/04  
(last modified 2/4/09)

SG-SCREEN  
PA Version 2.0; 04/

Reset to  
Defaults

Soil Gas Concentration Data				
ENTER Chemical CAS No. (numbers only, no dashes)	ENTER Soil gas conc., $C_g$ ( $\mu\text{g}/\text{m}^3$ )	OR	ENTER Soil gas conc., $C_g$ (ppmv)	Chemical
110543	1.28E+04			Hexane

MORE  
↓

ENTER Depth below grade to bottom of enclosed space floor, $L_F$ (15 or 200 cm)	ENTER Soil gas sampling depth below grade, $L_s$ (cm)	ENTER Average soil temperature, $T_s$ ( $^{\circ}\text{C}$ )	ENTER Vadose zone SCS soil type (used to estimate soil vapor permeability)	OR	ENTER User-defined vadose zone soil vapor permeability, $k_v$ ( $\text{cm}^2$ )
15	152.4	24	S		

MORE  
↓

ENTER Vadose zone SCS soil type Lookup Soil Parameters	ENTER Vadose zone soil dry bulk density, $\rho_b^A$ ( $\text{g}/\text{cm}^3$ )	ENTER Vadose zone soil total porosity, $n^V$ (unitless)	ENTER Vadose zone soil water-filled porosity, $\theta_w^V$ ( $\text{cm}^3/\text{cm}^3$ )	ENTER Average vapor flow rate into bldg. (Leave blank to calculate) $Q_{\text{soil}}$ (L/m)
S	1.83	0.324	0.279	5

MORE  
↓

ENTER Averaging time for carcinogens, $AT_C$ (yrs)	ENTER Averaging time for noncarcinogens, $AT_{NC}$ (yrs)	ENTER Exposure duration, ED (yrs)	ENTER Exposure frequency, EF (days/yr)
70	30	30	350

END

INTERMEDIATE CALCULATIONS SHEET

**Table A-14. Maximum Hexane (C5-C8 Aliphatics) Soil Vapor Concentration**

Source- building separation, $L_T$ (cm)	Vadose zone soil air-filled porosity, $\theta_a^v$ ( $\text{cm}^3/\text{cm}^3$ )	Vadose zone effective total fluid saturation, $S_{te}$ ( $\text{cm}^3/\text{cm}^3$ )	Vadose zone soil intrinsic permeability, $k_i$ ( $\text{cm}^2$ )	Vadose zone soil relative air permeability, $k_{rg}$ ( $\text{cm}^2$ )	Vadose zone soil effective vapor permeability, $k_v$ ( $\text{cm}^2$ )	Floor- wall seam perimeter, $X_{crack}$ (cm)	Soil gas conc. ( $\mu\text{g}/\text{m}^3$ )	Bldg. ventilation rate, $Q_{building}$ ( $\text{cm}^3/\text{s}$ )
137.4	0.045	0.834	1.02E-07	0.055	5.62E-09	4,000	1.28E+04	3.39E+04

Area of enclosed space below grade, $A_B$ ( $\text{cm}^2$ )	Crack- to-total area ratio, $\eta$ (unitless)	Crack depth below grade, $Z_{crack}$ (cm)	Enthalpy of vaporization at ave. soil temperature, $\Delta H_{v,TS}$ (cal/mol)	Henry's law constant at ave. soil temperature, $H_{TS}$ (atm- $\text{m}^3/\text{mol}$ )	Henry's law constant at ave. soil temperature, $H'_{TS}$ (unitless)	Vapor viscosity at ave. soil temperature, $\mu_{TS}$ (g/cm-s)	Vadose zone effective diffusion coefficient, $D_v^{eff}$ ( $\text{cm}^2/\text{s}$ )	Diffusion path length, $L_d$ (cm)
1.00E+06	5.00E-03	15	7,549	1.59E+00	6.53E+01	1.80E-04	6.24E-05	137.4

Convection path length, $L_p$ (cm)	Source vapor conc., $C_{source}$ ( $\mu\text{g}/\text{m}^3$ )	Crack radius, $r_{crack}$ (cm)	Average vapor flow rate into bldg., $Q_{soil}$ ( $\text{cm}^3/\text{s}$ )	Crack effective diffusion coefficient, $D^{crack}$ ( $\text{cm}^2/\text{s}$ )	Area of crack, $A_{crack}$ ( $\text{cm}^2$ )	Exponent of equivalent foundation Peclet number, $\exp(Pe^f)$ (unitless)	Infinite source indoor attenuation coefficient, $\alpha$ (unitless)	Infinite source bldg. conc., $C_{building}$ ( $\mu\text{g}/\text{m}^3$ )
15	1.28E+04	1.25	8.33E+01	6.24E-05	5.00E+03	#NUM!	1.33E-05	1.71E-01

Unit risk factor, URF ( $\mu\text{g}/\text{m}^3$ ) <sup>-1</sup>	Reference conc., RFC ( $\text{mg}/\text{m}^3$ )
NA	7.0E-01

**END**



Table A-15. Maximum Toluene (C9-C18 Aliphatics) Shallow Soil Vapor Concentration

DTSC  
Vapor Intrusion Guidance  
Interim Final 12/04  
(last modified 2/4/09)

SG-SCREEN  
PA Version 2.0; 04

Reset to Defaults

Soil Gas Concentration Data				
ENTER Chemical CAS No. (numbers only, no dashes)	ENTER Soil gas conc., $C_g$ ( $\mu\text{g}/\text{m}^3$ )	OR	ENTER Soil gas conc., $C_g$ (ppmv)	Chemical
108883	1.28E+04			Toluene

MORE  
↓

ENTER Depth below grade to bottom of enclosed space floor, $L_F$ (15 or 200 cm)	ENTER Soil gas sampling depth below grade, $L_s$ (cm)	ENTER Average soil temperature, $T_s$ ( $^{\circ}\text{C}$ )	ENTER Vadose zone SCS soil type (used to estimate soil vapor permeability)	OR	ENTER User-defined vadose zone soil vapor permeability, $k_v$ ( $\text{cm}^2$ )
15	152.4	24	S		

MORE  
↓

ENTER Vadose zone SCS soil type Lookup Soil Parameters	ENTER Vadose zone soil dry bulk density, $\rho_b^A$ ( $\text{g}/\text{cm}^3$ )	ENTER Vadose zone soil total porosity, $n^V$ (unitless)	ENTER Vadose zone soil water-filled porosity, $\theta_w^V$ ( $\text{cm}^3/\text{cm}^3$ )	ENTER Average vapor flow rate into bldg. (Leave blank to calculate) $Q_{\text{soil}}$ (L/m)
S	1.83	0.324	0.279	5

MORE  
↓

ENTER Averaging time for carcinogens, $AT_C$ (yrs)	ENTER Averaging time for noncarcinogens, $AT_{NC}$ (yrs)	ENTER Exposure duration, ED (yrs)	ENTER Exposure frequency, EF (days/yr)
70	30	30	350

END

INTERMEDIATE CALCULATIONS SHEET

**Table A-16. Maximum Toluene (C9-C18 Aliphatics) Shallow Soil Vapor Concentration**

Source- building separation, $L_T$ (cm)	Vadose zone soil air-filled porosity, $\theta_a^v$ (cm <sup>3</sup> /cm <sup>3</sup> )	Vadose zone effective total fluid saturation, $S_{te}$ (cm <sup>3</sup> /cm <sup>3</sup> )	Vadose zone soil intrinsic permeability, $k_i$ (cm <sup>2</sup> )	Vadose zone soil relative air permeability, $k_{rg}$ (cm <sup>2</sup> )	Vadose zone soil effective vapor permeability, $k_v$ (cm <sup>2</sup> )	Floor- wall seam perimeter, $X_{crack}$ (cm)	Soil gas conc. ( $\mu\text{g}/\text{m}^3$ )	Bldg. ventilation rate, $Q_{building}$ (cm <sup>3</sup> /s)
137.4	0.045	0.834	1.02E-07	0.055	5.62E-09	4,000	1.28E+04	3.39E+04

Area of enclosed space below grade, $A_B$ (cm <sup>2</sup> )	Crack- to-total area ratio, $\eta$ (unitless)	Crack depth below grade, $Z_{crack}$ (cm)	Enthalpy of vaporization at ave. soil temperature, $\Delta H_{v,TS}$ (cal/mol)	Henry's law constant at ave. soil temperature, $H_{TS}$ (atm·m <sup>3</sup> /mol)	Henry's law constant at ave. soil temperature, $H'_{TS}$ (unitless)	Vapor viscosity at ave. soil temperature, $\mu_{TS}$ (g/cm-s)	Vadose zone effective diffusion coefficient, $D_v^{eff}$ (cm <sup>2</sup> /s)	Diffusion path length, $L_d$ (cm)
1.00E+06	5.00E-03	15	9,001	6.29E-03	2.58E-01	1.80E-04	3.17E-05	137.4

Convection path length, $L_p$ (cm)	Source vapor conc., $C_{source}$ ( $\mu\text{g}/\text{m}^3$ )	Crack radius, $r_{crack}$ (cm)	Average vapor flow rate into bldg., $Q_{soil}$ (cm <sup>3</sup> /s)	Crack effective diffusion coefficient, $D^{crack}$ (cm <sup>2</sup> /s)	Area of crack, $A_{crack}$ (cm <sup>2</sup> )	Exponent of equivalent foundation Peclet number, $\exp(Pe^f)$ (unitless)	Infinite source indoor attenuation coefficient, $\alpha$ (unitless)	Infinite source bldg. conc., $C_{building}$ ( $\mu\text{g}/\text{m}^3$ )
15	1.28E+04	1.25	8.33E+01	3.17E-05	5.00E+03	#NUM!	6.78E-06	8.70E-02

Unit risk factor, URF ( $\mu\text{g}/\text{m}^3$ ) <sup>-1</sup>	Reference conc., RFC (mg/m <sup>3</sup> )
NA	3.0E-01
<b>END</b>	

Table A-17. Maximum C9-C16 Aromatics Shallow Soil Vapor Concentration

DTSC  
Vapor Intrusion Guidance  
Interim Final 12/04  
(last modified 2/4/09)

SG-SCREEN  
PA Version 2.0; 04/

Reset to Defaults

Soil Gas Concentration Data				
ENTER Chemical CAS No. (numbers only, no dashes)	ENTER Soil gas conc., $C_g$ ( $\mu\text{g}/\text{m}^3$ )	OR	ENTER Soil gas conc., $C_g$ (ppmv)	Chemical
91576	1.28E+04			2-Methylnaphthalene

MORE  
↓

ENTER Depth below grade to bottom of enclosed space floor, $L_F$ (15 or 200 cm)	ENTER Soil gas sampling depth below grade, $L_s$ (cm)	ENTER Average soil temperature, $T_s$ ( $^{\circ}\text{C}$ )	ENTER Vadose zone SCS soil type (used to estimate soil vapor permeability)	OR	ENTER User-defined vadose zone soil vapor permeability, $k_v$ ( $\text{cm}^2$ )
15	152.4	24	S		

MORE  
↓

ENTER Vadose zone SCS soil type Lookup Soil Parameters	ENTER Vadose zone soil dry bulk density, $\rho_b^A$ ( $\text{g}/\text{cm}^3$ )	ENTER Vadose zone soil total porosity, $n^V$ (unitless)	ENTER Vadose zone soil water-filled porosity, $\theta_w^V$ ( $\text{cm}^3/\text{cm}^3$ )	ENTER Average vapor flow rate into bldg. (Leave blank to calculate) $Q_{\text{soil}}$ (L/m)
S	1.83	0.324	0.279	5

MORE  
↓

ENTER Averaging time for carcinogens, $AT_C$ (yrs)	ENTER Averaging time for noncarcinogens, $AT_{NC}$ (yrs)	ENTER Exposure duration, ED (yrs)	ENTER Exposure frequency, EF (days/yr)
70	30	30	350

END

INTERMEDIATE CALCULATIONS SHEET

Table A-18. Maximum C9-C16 Aromatics Shallow Soil Vapor Concentration

Source- building separation, $L_T$ (cm)	Vadose zone soil air-filled porosity, $\theta_a^v$ ( $\text{cm}^3/\text{cm}^3$ )	Vadose zone effective total fluid saturation, $S_{te}$ ( $\text{cm}^3/\text{cm}^3$ )	Vadose zone soil intrinsic permeability, $k_i$ ( $\text{cm}^2$ )	Vadose zone soil relative air permeability, $k_{rg}$ ( $\text{cm}^2$ )	Vadose zone soil effective vapor permeability, $k_v$ ( $\text{cm}^2$ )	Floor- wall seam perimeter, $X_{crack}$ (cm)	Soil gas conc. ( $\mu\text{g}/\text{m}^3$ )	Bldg. ventilation rate, $Q_{building}$ ( $\text{cm}^3/\text{s}$ )
137.4	0.045	0.834	1.02E-07	0.055	5.62E-09	4,000	1.28E+04	3.39E+04

Area of enclosed space below grade, $A_B$ ( $\text{cm}^2$ )	Crack- to-total area ratio, $\eta$ (unitless)	Crack depth below grade, $Z_{crack}$ (cm)	Enthalpy of vaporization at ave. soil temperature, $\Delta H_{v,TS}$ (cal/mol)	Henry's law constant at ave. soil temperature, $H_{TS}$ (atm- $\text{m}^3/\text{mol}$ )	Henry's law constant at ave. soil temperature, $H'_{TS}$ (unitless)	Vapor viscosity at ave. soil temperature, $\mu_{TS}$ (g/cm-s)	Vadose zone effective diffusion coefficient, $D_v^{eff}$ ( $\text{cm}^2/\text{s}$ )	Diffusion path length, $L_d$ (cm)
1.00E+06	5.00E-03	15	16,057	4.72E-04	1.93E-02	1.80E-04	7.07E-05	137.4

Convection path length, $L_p$ (cm)	Source vapor conc., $C_{source}$ ( $\mu\text{g}/\text{m}^3$ )	Crack radius, $r_{crack}$ (cm)	Average vapor flow rate into bldg., $Q_{soil}$ ( $\text{cm}^3/\text{s}$ )	Crack effective diffusion coefficient, $D^{crack}$ ( $\text{cm}^2/\text{s}$ )	Area of crack, $A_{crack}$ ( $\text{cm}^2$ )	Exponent of equivalent foundation Peclet number, $\exp(Pe^f)$ (unitless)	Infinite source indoor attenuation coefficient, $\alpha$ (unitless)	Infinite source bldg. conc., $C_{building}$ ( $\mu\text{g}/\text{m}^3$ )
15	1.28E+04	1.25	8.33E+01	7.07E-05	5.00E+03	#NUM!	1.51E-05	1.94E-01

Unit risk factor, URF ( $\mu\text{g}/\text{m}^3$ ) <sup>-1</sup>	Reference conc., RFC ( $\text{mg}/\text{m}^3$ )
NA	1.4E-02
<b>END</b>	

DATA ENTRY SHEET

Table A-19. Maximum Benzene Deep Soil Vapor Concentration

DTSC  
Vapor Intrusion Guidance  
Interim Final 12/04  
(last modified 2/4/09)

SG-SCREEN  
PA Version 2.0; 04/

Reset to Defaults

Soil Gas Concentration Data				
ENTER Chemical CAS No. (numbers only, no dashes)	ENTER Soil gas conc., $C_g$ ( $\mu\text{g}/\text{m}^3$ )	OR	ENTER Soil gas conc., $C_g$ (ppmv)	Chemical
71432	2.80E+02			Benzene

MORE  
↓

ENTER Depth below grade to bottom of enclosed space floor, $L_F$ (15 or 200 cm)	ENTER Soil gas sampling depth below grade, $L_s$ (cm)	ENTER Average soil temperature, $T_s$ ( $^{\circ}\text{C}$ )	ENTER Vadose zone SCS soil type (used to estimate soil vapor permeability)	OR	ENTER User-defined vadose zone soil vapor permeability, $k_v$ ( $\text{cm}^2$ )
15	304.8	24	S		

MORE  
↓

ENTER Vadose zone SCS soil type Lookup Soil Parameters	ENTER Vadose zone soil dry bulk density, $\rho_b^A$ ( $\text{g}/\text{cm}^3$ )	ENTER Vadose zone soil total porosity, $n^V$ (unitless)	ENTER Vadose zone soil water-filled porosity, $\theta_w^V$ ( $\text{cm}^3/\text{cm}^3$ )	ENTER Average vapor flow rate into bldg. (Leave blank to calculate) $Q_{\text{soil}}$ (L/m)
S	1.83	0.324	0.279	5

MORE  
↓

ENTER Averaging time for carcinogens, $AT_C$ (yrs)	ENTER Averaging time for noncarcinogens, $AT_{NC}$ (yrs)	ENTER Exposure duration, ED (yrs)	ENTER Exposure frequency, EF (days/yr)
70	30	30	350

END

INTERMEDIATE CALCULATIONS SHEET

**Table A-20. Maximum Benzene Deep Soil Vapor Concentration**

Source- building separation, $L_T$ (cm)	Vadose zone soil air-filled porosity, $\theta_a^v$ ( $\text{cm}^3/\text{cm}^3$ )	Vadose zone effective total fluid saturation, $S_{1e}$ ( $\text{cm}^3/\text{cm}^3$ )	Vadose zone soil intrinsic permeability, $k_i$ ( $\text{cm}^2$ )	Vadose zone soil relative air permeability, $k_{rg}$ ( $\text{cm}^2$ )	Vadose zone soil effective vapor permeability, $k_v$ ( $\text{cm}^2$ )	Floor- wall seam perimeter, $X_{crack}$ (cm)	Soil gas conc., $C_{soil}$ ( $\mu\text{g}/\text{m}^3$ )	Bldg. ventilation rate, $Q_{building}$ ( $\text{cm}^3/\text{s}$ )
289.8	0.045	0.834	1.02E-07	0.055	5.62E-09	4,000	2.80E+02	3.39E+04

Area of enclosed space below grade, $A_B$ ( $\text{cm}^2$ )	Crack- to-total area ratio, $\eta$ (unitless)	Crack depth below grade, $Z_{crack}$ (cm)	Enthalpy of vaporization at ave. soil temperature, $\Delta H_{v,TS}$ (cal/mol)	Henry's law constant at ave. soil temperature, $H_{TS}$ (atm- $\text{m}^3/\text{mol}$ )	Henry's law constant at ave. soil temperature, $H'_{TS}$ (unitless)	Vapor viscosity at ave. soil temperature, $\mu_{TS}$ (g/cm-s)	Vadose zone effective diffusion coefficient, $D_v^{eff}$ ( $\text{cm}^2/\text{s}$ )	Diffusion path length, $L_d$ (cm)
1.00E+06	5.00E-03	15	7,977	5.29E-03	2.17E-01	1.80E-04	3.36E-05	289.8

Convection path length, $L_p$ (cm)	Source vapor conc., $C_{source}$ ( $\mu\text{g}/\text{m}^3$ )	Crack radius, $r_{crack}$ (cm)	Average vapor flow rate into bldg., $Q_{soil}$ ( $\text{cm}^3/\text{s}$ )	Crack effective diffusion coefficient, $D^{crack}$ ( $\text{cm}^2/\text{s}$ )	Area of crack, $A_{crack}$ ( $\text{cm}^2$ )	Exponent of equivalent foundation Peclet number, $\exp(Pe^f)$ (unitless)	Infinite source indoor attenuation coefficient, $\alpha$ (unitless)	Infinite source bldg. conc., $C_{building}$ ( $\mu\text{g}/\text{m}^3$ )
15	2.80E+02	1.25	8.33E+01	3.36E-05	5.00E+03	#NUM!	3.42E-06	9.56E-04

Unit risk factor, URF ( $\mu\text{g}/\text{m}^3$ ) <sup>-1</sup>	Reference conc., RFC ( $\text{mg}/\text{m}^3$ )
2.9E-05	3.0E-02

**END**

DATA ENTRY SHEET

Table A-21. Maximum Chloroform Deep Soil Vapor Concentration

DTSC  
Vapor Intrusion Guidance  
Interim Final 12/04  
(last modified 2/4/09)

SG-SCREEN  
PA Version 2.0; 04

Reset to Defaults

Soil Gas Concentration Data				
ENTER Chemical CAS No. (numbers only, no dashes)	ENTER Soil gas conc., $C_g$ ( $\mu\text{g}/\text{m}^3$ )	OR	ENTER Soil gas conc., $C_g$ (ppmv)	Chemical
67663	4.30E+00			Chloroform

MORE  
↓

ENTER Depth below grade to bottom of enclosed space floor, $L_F$ (15 or 200 cm)	ENTER Soil gas sampling depth below grade, $L_s$ (cm)	ENTER Average soil temperature, $T_s$ ( $^{\circ}\text{C}$ )	ENTER Vadose zone SCS soil type (used to estimate soil vapor permeability)	OR	ENTER User-defined vadose zone soil vapor permeability, $k_v$ ( $\text{cm}^2$ )
15	304.8	24	S		

MORE  
↓

ENTER Vadose zone SCS soil type Lookup Soil Parameters	ENTER Vadose zone soil dry bulk density, $\rho_b^A$ ( $\text{g}/\text{cm}^3$ )	ENTER Vadose zone soil total porosity, $n^V$ (unitless)	ENTER Vadose zone soil water-filled porosity, $\theta_w^V$ ( $\text{cm}^3/\text{cm}^3$ )	ENTER Average vapor flow rate into bldg. (Leave blank to calculate) $Q_{\text{soil}}$ (L/m)
S	1.83	0.324	0.279	5

MORE  
↓

ENTER Averaging time for carcinogens, $AT_C$ (yrs)	ENTER Averaging time for noncarcinogens, $AT_{NC}$ (yrs)	ENTER Exposure duration, ED (yrs)	ENTER Exposure frequency, EF (days/yr)
70	30	30	350

END

INTERMEDIATE CALCULATIONS SHEET

Table A-22. Maximum Chloroform Deep Soil Vapor Concentration

Source- building separation, $L_T$ (cm)	Vadose zone soil air-filled porosity, $\theta_a^v$ ( $\text{cm}^3/\text{cm}^3$ )	Vadose zone effective total fluid saturation, $S_{te}$ ( $\text{cm}^3/\text{cm}^3$ )	Vadose zone soil intrinsic permeability, $k_i$ ( $\text{cm}^2$ )	Vadose zone soil relative air permeability, $k_{rg}$ ( $\text{cm}^2$ )	Vadose zone soil effective vapor permeability, $k_v$ ( $\text{cm}^2$ )	Floor- wall seam perimeter, $X_{crack}$ (cm)	Soil gas conc., $C_{soil}$ ( $\mu\text{g}/\text{m}^3$ )	Bldg. ventilation rate, $Q_{building}$ ( $\text{cm}^3/\text{s}$ )
289.8	0.045	0.834	1.02E-07	0.055	5.62E-09	4,000	4.30E+00	3.39E+04

Area of enclosed space below grade, $A_B$ ( $\text{cm}^2$ )	Crack- to-total area ratio, $\eta$ (unitless)	Crack depth below grade, $Z_{crack}$ (cm)	Enthalpy of vaporization at ave. soil temperature, $\Delta H_{v,TS}$ (cal/mol)	Henry's law constant at ave. soil temperature, $H_{TS}$ (atm- $\text{m}^3/\text{mol}$ )	Henry's law constant at ave. soil temperature, $H'_{TS}$ (unitless)	Vapor viscosity at ave. soil temperature, $\mu_{TS}$ (g/cm-s)	Vadose zone effective diffusion coefficient, $D_v^{eff}$ ( $\text{cm}^2/\text{s}$ )	Diffusion path length, $L_d$ (cm)
1.00E+06	5.00E-03	15	7,407	3.51E-03	1.44E-01	1.80E-04	4.19E-05	289.8

Convection path length, $L_p$ (cm)	Source vapor conc., $C_{source}$ ( $\mu\text{g}/\text{m}^3$ )	Crack radius, $r_{crack}$ (cm)	Average vapor flow rate into bldg., $Q_{soil}$ ( $\text{cm}^3/\text{s}$ )	Crack effective diffusion coefficient, $D^{crack}$ ( $\text{cm}^2/\text{s}$ )	Area of crack, $A_{crack}$ ( $\text{cm}^2$ )	Exponent of equivalent foundation Peclet number, $\exp(Pe^f)$ (unitless)	Infinite source indoor attenuation coefficient, $\alpha$ (unitless)	Infinite source bldg. conc., $C_{building}$ ( $\mu\text{g}/\text{m}^3$ )
15	4.30E+00	1.25	8.33E+01	4.19E-05	5.00E+03	#NUM!	4.26E-06	1.83E-05

Unit risk factor, URF ( $\mu\text{g}/\text{m}^3$ ) <sup>-1</sup>	Reference conc., RFC ( $\text{mg}/\text{m}^3$ )
5.3E-06	3.0E-01

END



DATA ENTRY SHEET

Table A-23. Maximum Ethylbenzene Deep Soil Vapor Concentration

DTSC  
Vapor Intrusion Guidance  
Interim Final 12/04  
(last modified 2/4/09)

SG-SCREEN  
PA Version 2.0; 04/

Reset to  
Defaults

Soil Gas Concentration Data				
ENTER Chemical CAS No. (numbers only, no dashes)	ENTER Soil gas conc., $C_g$ ( $\mu\text{g}/\text{m}^3$ )	OR	ENTER Soil gas conc., $C_g$ (ppmv)	Chemical
100414	1.90E+02			Ethylbenzene

MORE  
↓

ENTER Depth below grade to bottom of enclosed space floor, $L_F$ (15 or 200 cm)	ENTER Soil gas sampling depth below grade, $L_s$ (cm)	ENTER Average soil temperature, $T_s$ ( $^{\circ}\text{C}$ )	ENTER Vadose zone SCS soil type (used to estimate soil vapor permeability)	OR	ENTER User-defined vadose zone soil vapor permeability, $k_v$ ( $\text{cm}^2$ )
15	304.8	24	S		

MORE  
↓

ENTER Vadose zone SCS soil type Lookup Soil Parameters	ENTER Vadose zone soil dry bulk density, $\rho_b^A$ ( $\text{g}/\text{cm}^3$ )	ENTER Vadose zone soil total porosity, $n^V$ (unitless)	ENTER Vadose zone soil water-filled porosity, $\theta_w^V$ ( $\text{cm}^3/\text{cm}^3$ )	ENTER Average vapor flow rate into bldg. (Leave blank to calculate) $Q_{\text{soil}}$ (L/m)
S	1.83	0.324	0.279	5

MORE  
↓

ENTER Averaging time for carcinogens, $AT_C$ (yrs)	ENTER Averaging time for noncarcinogens, $AT_{NC}$ (yrs)	ENTER Exposure duration, ED (yrs)	ENTER Exposure frequency, EF (days/yr)
70	30	30	350

END

INTERMEDIATE CALCULATIONS SHEET

**Table A-24. Maximum Ethylbenzene Deep Soil Vapor Concentration**

Source- building separation, $L_T$ (cm)	Vadose zone soil air-filled porosity, $\theta_a^v$ ( $\text{cm}^3/\text{cm}^3$ )	Vadose zone effective total fluid saturation, $S_{1e}$ ( $\text{cm}^3/\text{cm}^3$ )	Vadose zone soil intrinsic permeability, $k_i$ ( $\text{cm}^2$ )	Vadose zone soil relative air permeability, $k_{rg}$ ( $\text{cm}^2$ )	Vadose zone soil effective vapor permeability, $k_v$ ( $\text{cm}^2$ )	Floor- wall seam perimeter, $X_{crack}$ (cm)	Soil gas conc. ( $\mu\text{g}/\text{m}^3$ )	Bldg. ventilation rate, $Q_{building}$ ( $\text{cm}^3/\text{s}$ )
289.8	0.045	0.834	1.02E-07	0.055	5.62E-09	4,000	1.90E+02	3.39E+04

Area of enclosed space below grade, $A_B$ ( $\text{cm}^2$ )	Crack- to-total area ratio, $\eta$ (unitless)	Crack depth below grade, $Z_{crack}$ (cm)	Enthalpy of vaporization at ave. soil temperature, $\Delta H_{v,TS}$ (cal/mol)	Henry's law constant at ave. soil temperature, $H_{TS}$ (atm- $\text{m}^3/\text{mol}$ )	Henry's law constant at ave. soil temperature, $H'_{TS}$ (unitless)	Vapor viscosity at ave. soil temperature, $\mu_{TS}$ (g/cm-s)	Vadose zone effective diffusion coefficient, $D_v^{eff}$ ( $\text{cm}^2/\text{s}$ )	Diffusion path length, $L_d$ (cm)
1.00E+06	5.00E-03	15	9,994	7.43E-03	3.05E-01	1.80E-04	2.69E-05	289.8

Convection path length, $L_p$ (cm)	Source vapor conc., $C_{source}$ ( $\mu\text{g}/\text{m}^3$ )	Crack radius, $r_{crack}$ (cm)	Average vapor flow rate into bldg., $Q_{soil}$ ( $\text{cm}^3/\text{s}$ )	Crack effective diffusion coefficient, $D^{crack}$ ( $\text{cm}^2/\text{s}$ )	Area of crack, $A_{crack}$ ( $\text{cm}^2$ )	Exponent of equivalent foundation Peclet number, $\exp(Pe^f)$ (unitless)	Infinite source indoor attenuation coefficient, $\alpha$ (unitless)	Infinite source bldg. conc., $C_{building}$ ( $\mu\text{g}/\text{m}^3$ )
15	1.90E+02	1.25	8.33E+01	2.69E-05	5.00E+03	#NUM!	2.73E-06	5.19E-04

Unit risk factor, URF ( $\mu\text{g}/\text{m}^3$ ) <sup>-1</sup>	Reference conc., RFC ( $\text{mg}/\text{m}^3$ )
2.5E-06	1.0E+00

**END**

DATA ENTRY SHEET

Table A-25. Maximum Naphthalene Deep Soil Vapor Concentration

DTSC  
Vapor Intrusion Guidance  
Interim Final 12/04  
(last modified 2/4/09)

SG-SCREEN  
PA Version 2.0; 04/

Reset to Defaults

Soil Gas Concentration Data				
ENTER Chemical CAS No. (numbers only, no dashes)	ENTER Soil gas conc., $C_g$ ( $\mu\text{g}/\text{m}^3$ )	OR	ENTER Soil gas conc., $C_g$ (ppmv)	Chemical
91203	9.00E+02			Naphthalene

MORE  
↓

ENTER Depth below grade to bottom of enclosed space floor, $L_F$ (15 or 200 cm)	ENTER Soil gas sampling depth below grade, $L_s$ (cm)	ENTER Average soil temperature, $T_s$ ( $^{\circ}\text{C}$ )	ENTER Vadose zone SCS soil type (used to estimate soil vapor permeability)	OR	ENTER User-defined vadose zone soil vapor permeability, $k_v$ ( $\text{cm}^2$ )
15	304.8	24	S		

MORE  
↓

ENTER Vadose zone SCS soil type Lookup Soil Parameters	ENTER Vadose zone soil dry bulk density, $\rho_b^A$ ( $\text{g}/\text{cm}^3$ )	ENTER Vadose zone soil total porosity, $n^V$ (unitless)	ENTER Vadose zone soil water-filled porosity, $\theta_w^V$ ( $\text{cm}^3/\text{cm}^3$ )	ENTER Average vapor flow rate into bldg. (Leave blank to calculate) $Q_{\text{soil}}$ (L/m)
S	1.83	0.324	0.279	5

MORE  
↓

ENTER Averaging time for carcinogens, $AT_C$ (yrs)	ENTER Averaging time for noncarcinogens, $AT_{NC}$ (yrs)	ENTER Exposure duration, ED (yrs)	ENTER Exposure frequency, EF (days/yr)
70	30	30	350

END

INTERMEDIATE CALCULATIONS SHEET

Table A-26. Maximum Naphthalene Deep Soil Vapor Concentration

Source-building separation, $L_T$ (cm)	Vadose zone soil air-filled porosity, $\theta_a^v$ ( $\text{cm}^3/\text{cm}^3$ )	Vadose zone effective total fluid saturation, $S_{Te}$ ( $\text{cm}^3/\text{cm}^3$ )	Vadose zone soil intrinsic permeability, $k_i$ ( $\text{cm}^2$ )	Vadose zone soil relative air permeability, $k_{rg}$ ( $\text{cm}^2$ )	Vadose zone soil effective vapor permeability, $k_v$ ( $\text{cm}^2$ )	Floor-wall seam perimeter, $X_{crack}$ (cm)	Soil gas conc., ( $\mu\text{g}/\text{m}^3$ )	Bldg. ventilation rate, $Q_{building}$ ( $\text{cm}^3/\text{s}$ )
289.8	0.045	0.834	1.02E-07	0.055	5.62E-09	4,000	9.00E+02	3.39E+04

Area of enclosed space below grade, $A_B$ ( $\text{cm}^2$ )	Crack-to-total area ratio, $\eta$ (unitless)	Crack depth below grade, $Z_{crack}$ (cm)	Enthalpy of vaporization at ave. soil temperature, $\Delta H_{v,TS}$ (cal/mol)	Henry's law constant at ave. soil temperature, $H_{TS}$ (atm- $\text{m}^3/\text{mol}$ )	Henry's law constant at ave. soil temperature, $H'_{TS}$ (unitless)	Vapor viscosity at ave. soil temperature, $\mu_{TS}$ (g/cm-s)	Vadose zone effective diffusion coefficient, $D_v^{eff}$ ( $\text{cm}^2/\text{s}$ )	Diffusion path length, $L_d$ (cm)
1.00E+06	5.00E-03	15	12,768	4.48E-04	1.84E-02	1.80E-04	7.38E-05	289.8

Convection path length, $L_p$ (cm)	Source vapor conc., $C_{source}$ ( $\mu\text{g}/\text{m}^3$ )	Crack radius, $r_{crack}$ (cm)	Average vapor flow rate into bldg., $Q_{soil}$ ( $\text{cm}^3/\text{s}$ )	Crack effective diffusion coefficient, $D^{crack}$ ( $\text{cm}^2/\text{s}$ )	Area of crack, $A_{crack}$ ( $\text{cm}^2$ )	Exponent of equivalent foundation Peclet number, $\exp(Pe^f)$ (unitless)	Infinite source indoor attenuation coefficient, $\alpha$ (unitless)	Infinite source bldg. conc., $C_{building}$ ( $\mu\text{g}/\text{m}^3$ )
15	9.00E+02	1.25	8.33E+01	7.38E-05	5.00E+03	#NUM!	7.49E-06	6.74E-03

Unit risk factor, URF ( $\mu\text{g}/\text{m}^3$ ) <sup>-1</sup>	Reference conc., RFC ( $\text{mg}/\text{m}^3$ )
3.4E-05	3.0E-03

END

DATA ENTRY SHEET

Table A-27. Maximum Toluene Deep Soil Vapor Concentration

DTSC  
Vapor Intrusion Guidance  
Interim Final 12/04  
(last modified 2/4/09)

SG-SCREEN  
PA Version 2.0; 04/

Reset to  
Defaults

Soil Gas Concentration Data				
ENTER	ENTER	OR	ENTER	Chemical
Chemical CAS No. (numbers only, no dashes)	Soil gas conc., $C_g$ ( $\mu\text{g}/\text{m}^3$ )		Soil gas conc., $C_g$ (ppmv)	
108883	1.00E+03			Toluene

MORE  
↓

ENTER	ENTER	ENTER	ENTER	OR	ENTER
Depth below grade to bottom of enclosed space floor, $L_F$ (15 or 200 cm)	Soil gas sampling depth below grade, $L_s$ (cm)	Average soil temperature, $T_s$ ( $^{\circ}\text{C}$ )	Vadose zone SCS soil type (used to estimate soil vapor permeability)		User-defined vadose zone soil vapor permeability, $k_v$ ( $\text{cm}^2$ )
15	304.8	24	S		

MORE  
↓

ENTER	ENTER	ENTER	ENTER	ENTER
Vadose zone SCS soil type Lookup Soil Parameters	Vadose zone soil dry bulk density, $\rho_b^A$ ( $\text{g}/\text{cm}^3$ )	Vadose zone soil total porosity, $n^V$ (unitless)	Vadose zone soil water-filled porosity, $\theta_w^V$ ( $\text{cm}^3/\text{cm}^3$ )	Average vapor flow rate into bldg. (Leave blank to calculate) $Q_{\text{soil}}$ (L/m)
S	1.83	0.324	0.279	5

MORE  
↓

ENTER	ENTER	ENTER	ENTER
Averaging time for carcinogens, $AT_C$ (yrs)	Averaging time for noncarcinogens, $AT_{NC}$ (yrs)	Exposure duration, ED (yrs)	Exposure frequency, EF (days/yr)
70	30	30	350

END

INTERMEDIATE CALCULATIONS SHEET

Table A-28. Maximum Toluene Deep Soil Vapor Concentration

Source-building separation, $L_T$ (cm)	Vadose zone soil air-filled porosity, $\theta_a^v$ ( $\text{cm}^3/\text{cm}^3$ )	Vadose zone effective total fluid saturation, $S_{te}$ ( $\text{cm}^3/\text{cm}^3$ )	Vadose zone soil intrinsic permeability, $k_i$ ( $\text{cm}^2$ )	Vadose zone soil relative air permeability, $k_{rg}$ ( $\text{cm}^2$ )	Vadose zone soil effective vapor permeability, $k_v$ ( $\text{cm}^2$ )	Floor-wall seam perimeter, $X_{crack}$ (cm)	Soil gas conc., ( $\mu\text{g}/\text{m}^3$ )	Bldg. ventilation rate, $Q_{building}$ ( $\text{cm}^3/\text{s}$ )
289.8	0.045	0.834	1.02E-07	0.055	5.62E-09	4,000	1.00E+03	3.39E+04

Area of enclosed space below grade, $A_B$ ( $\text{cm}^2$ )	Crack-to-total area ratio, $\eta$ (unitless)	Crack depth below grade, $Z_{crack}$ (cm)	Enthalpy of vaporization at ave. soil temperature, $\Delta H_{v,TS}$ (cal/mol)	Henry's law constant at ave. soil temperature, $H_{TS}$ (atm- $\text{m}^3/\text{mol}$ )	Henry's law constant at ave. soil temperature, $H'_{TS}$ (unitless)	Vapor viscosity at ave. soil temperature, $\mu_{TS}$ (g/cm-s)	Vadose zone effective diffusion coefficient, $D_v^{eff}$ ( $\text{cm}^2/\text{s}$ )	Diffusion path length, $L_d$ (cm)
1.00E+06	5.00E-03	15	9,001	6.29E-03	2.58E-01	1.80E-04	3.17E-05	289.8

Convection path length, $L_p$ (cm)	Source vapor conc., $C_{source}$ ( $\mu\text{g}/\text{m}^3$ )	Crack radius, $r_{crack}$ (cm)	Average vapor flow rate into bldg., $Q_{soil}$ ( $\text{cm}^3/\text{s}$ )	Crack effective diffusion coefficient, $D^{crack}$ ( $\text{cm}^2/\text{s}$ )	Area of crack, $A_{crack}$ ( $\text{cm}^2$ )	Exponent of equivalent foundation Peclet number, $\exp(Pe^f)$ (unitless)	Infinite source indoor attenuation coefficient, $\alpha$ (unitless)	Infinite source bldg. conc., $C_{building}$ ( $\mu\text{g}/\text{m}^3$ )
15	1.00E+03	1.25	8.33E+01	3.17E-05	5.00E+03	#NUM!	3.22E-06	3.22E-03

Unit risk factor, URF ( $\mu\text{g}/\text{m}^3$ ) <sup>-1</sup>	Reference conc., RFC ( $\text{mg}/\text{m}^3$ )
NA	3.0E-01
<b>END</b>	

DATA ENTRY SHEET

Table A-29. Maximum Xylenes Deep Soil Vapor Concentration

SG-SCREEN  
PA Version 2.0; 04/

Reset to  
Defaults

DTSC  
Vapor Intrusion Guidance  
Interim Final 12/04  
(last modified 2/4/09)

Soil Gas Concentration Data				
ENTER Chemical CAS No. (numbers only, no dashes)	ENTER Soil gas conc., $C_g$ ( $\mu\text{g}/\text{m}^3$ )	OR	ENTER Soil gas conc., $C_g$ (ppmv)	Chemical
106423	6.30E+02			p-Xylene

MORE  
↓

ENTER Depth below grade to bottom of enclosed space floor, $L_F$ (15 or 200 cm)	ENTER Soil gas sampling depth below grade, $L_s$ (cm)	ENTER Average soil temperature, $T_s$ ( $^{\circ}\text{C}$ )	ENTER Vadose zone SCS soil type (used to estimate soil vapor permeability)	OR	ENTER User-defined vadose zone soil vapor permeability, $k_v$ ( $\text{cm}^2$ )
15	304.8	24	S		

MORE  
↓

ENTER Vadose zone SCS soil type Lookup Soil Parameters	ENTER Vadose zone soil dry bulk density, $\rho_b^A$ ( $\text{g}/\text{cm}^3$ )	ENTER Vadose zone soil total porosity, $n^V$ (unitless)	ENTER Vadose zone soil water-filled porosity, $\theta_w^V$ ( $\text{cm}^3/\text{cm}^3$ )	ENTER Average vapor flow rate into bldg. (Leave blank to calculate) $Q_{\text{soil}}$ (L/m)
S	1.83	0.324	0.279	5

MORE  
↓

ENTER Averaging time for carcinogens, $AT_C$ (yrs)	ENTER Averaging time for noncarcinogens, $AT_{NC}$ (yrs)	ENTER Exposure duration, ED (yrs)	ENTER Exposure frequency, EF (days/yr)
70	30	30	350

END

INTERMEDIATE CALCULATIONS SHEET

Table A-30. Maximum Xylenes Deep Soil Vapor Concentration

Source- building separation, $L_T$ (cm)	Vadose zone soil air-filled porosity, $\theta_a^v$ ( $\text{cm}^3/\text{cm}^3$ )	Vadose zone effective total fluid saturation, $S_{te}$ ( $\text{cm}^3/\text{cm}^3$ )	Vadose zone soil intrinsic permeability, $k_i$ ( $\text{cm}^2$ )	Vadose zone soil relative air permeability, $k_{rg}$ ( $\text{cm}^2$ )	Vadose zone soil effective vapor permeability, $k_v$ ( $\text{cm}^2$ )	Floor- wall seam perimeter, $X_{crack}$ (cm)	Soil gas conc., $C_{soil}$ ( $\mu\text{g}/\text{m}^3$ )	Bldg. ventilation rate, $Q_{building}$ ( $\text{cm}^3/\text{s}$ )
289.8	0.045	0.834	1.02E-07	0.055	5.62E-09	4,000	6.30E+02	3.39E+04

Area of enclosed space below grade, $A_B$ ( $\text{cm}^2$ )	Crack- to-total area ratio, $\eta$ (unitless)	Crack depth below grade, $Z_{crack}$ (cm)	Enthalpy of vaporization at ave. soil temperature, $\Delta H_{v,TS}$ (cal/mol)	Henry's law constant at ave. soil temperature, $H_{TS}$ (atm- $\text{m}^3/\text{mol}$ )	Henry's law constant at ave. soil temperature, $H'_{TS}$ (unitless)	Vapor viscosity at ave. soil temperature, $\mu_{TS}$ (g/cm-s)	Vadose zone effective diffusion coefficient, $D_v^{eff}$ ( $\text{cm}^2/\text{s}$ )	Diffusion path length, $L_d$ (cm)
1.00E+06	5.00E-03	15	10,083	7.22E-03	2.96E-01	1.80E-04	2.79E-05	289.8

Convection path length, $L_p$ (cm)	Source vapor conc., $C_{source}$ ( $\mu\text{g}/\text{m}^3$ )	Crack radius, $r_{crack}$ (cm)	Average vapor flow rate into bldg., $Q_{soil}$ ( $\text{cm}^3/\text{s}$ )	Crack effective diffusion coefficient, $D^{crack}$ ( $\text{cm}^2/\text{s}$ )	Area of crack, $A_{crack}$ ( $\text{cm}^2$ )	Exponent of equivalent foundation Peclet number, $\exp(Pe^f)$ (unitless)	Infinite source indoor attenuation coefficient, $\alpha$ (unitless)	Infinite source bldg. conc., $C_{building}$ ( $\mu\text{g}/\text{m}^3$ )
15	6.30E+02	1.25	8.33E+01	2.79E-05	5.00E+03	#NUM!	2.83E-06	1.79E-03

Unit risk factor, URF ( $\mu\text{g}/\text{m}^3$ ) <sup>-1</sup>	Reference conc., RFC ( $\text{mg}/\text{m}^3$ )
NA	1.0E-01
<b>END</b>	



DATA ENTRY SHEET

Table A-31. Maximum Hexane (C5-C8 Aliphatics) Deep Soil Vapor Concentration

DTSC  
Vapor Intrusion Guidance  
Interim Final 12/04  
(last modified 2/4/09)

SG-SCREEN  
PA Version 2.0; 04/

Reset to Defaults

Soil Gas Concentration Data				
ENTER Chemical CAS No. (numbers only, no dashes)	ENTER Soil gas conc., $C_g$ ( $\mu\text{g}/\text{m}^3$ )	OR	ENTER Soil gas conc., $C_g$ (ppmv)	Chemical
110543	9.00E+05			Hexane

MORE  
↓

ENTER Depth below grade to bottom of enclosed space floor, $L_F$ (15 or 200 cm)	ENTER Soil gas sampling depth below grade, $L_s$ (cm)	ENTER Average soil temperature, $T_s$ ( $^{\circ}\text{C}$ )	ENTER Vadose zone SCS soil type (used to estimate soil vapor permeability)	OR	ENTER User-defined vadose zone soil vapor permeability, $k_v$ ( $\text{cm}^2$ )
15	304.8	24	S		

MORE  
↓

ENTER Vadose zone SCS soil type Lookup Soil Parameters	ENTER Vadose zone soil dry bulk density, $\rho_b^A$ ( $\text{g}/\text{cm}^3$ )	ENTER Vadose zone soil total porosity, $n^V$ (unitless)	ENTER Vadose zone soil water-filled porosity, $\theta_w^V$ ( $\text{cm}^3/\text{cm}^3$ )	ENTER Average vapor flow rate into bldg. (Leave blank to calculate) $Q_{\text{soil}}$ (L/m)
S	1.83	0.324	0.279	5

MORE  
↓

ENTER Averaging time for carcinogens, $AT_C$ (yrs)	ENTER Averaging time for noncarcinogens, $AT_{NC}$ (yrs)	ENTER Exposure duration, ED (yrs)	ENTER Exposure frequency, EF (days/yr)
70	30	30	350

END

INTERMEDIATE CALCULATIONS SHEET

**Table A-32. Maximum Hexane (C5-C8 Aliphatics) Deep Soil Vapor Concentration**

Source-building separation, $L_T$ (cm)	Vadose zone soil air-filled porosity, $\theta_a^v$ ( $\text{cm}^3/\text{cm}^3$ )	Vadose zone effective total fluid saturation, $S_{te}$ ( $\text{cm}^3/\text{cm}^3$ )	Vadose zone soil intrinsic permeability, $k_i$ ( $\text{cm}^2$ )	Vadose zone soil relative air permeability, $k_{rg}$ ( $\text{cm}^2$ )	Vadose zone soil effective vapor permeability, $k_v$ ( $\text{cm}^2$ )	Floor-wall seam perimeter, $X_{crack}$ (cm)	Soil gas conc., ( $\mu\text{g}/\text{m}^3$ )	Bldg. ventilation rate, $Q_{building}$ ( $\text{cm}^3/\text{s}$ )
289.8	0.045	0.834	1.02E-07	0.055	5.62E-09	4,000	9.00E+05	3.39E+04

Area of enclosed space below grade, $A_B$ ( $\text{cm}^2$ )	Crack-to-total area ratio, $\eta$ (unitless)	Crack depth below grade, $Z_{crack}$ (cm)	Enthalpy of vaporization at ave. soil temperature, $\Delta H_{v,TS}$ (cal/mol)	Henry's law constant at ave. soil temperature, $H_{TS}$ (atm- $\text{m}^3/\text{mol}$ )	Henry's law constant at ave. soil temperature, $H'_{TS}$ (unitless)	Vapor viscosity at ave. soil temperature, $\mu_{TS}$ (g/cm-s)	Vadose zone effective diffusion coefficient, $D_v^{eff}$ ( $\text{cm}^2/\text{s}$ )	Diffusion path length, $L_d$ (cm)
1.00E+06	5.00E-03	15	7,549	1.59E+00	6.53E+01	1.80E-04	6.24E-05	289.8

Convection path length, $L_p$ (cm)	Source vapor conc., $C_{source}$ ( $\mu\text{g}/\text{m}^3$ )	Crack radius, $r_{crack}$ (cm)	Average vapor flow rate into bldg., $Q_{soil}$ ( $\text{cm}^3/\text{s}$ )	Crack effective diffusion coefficient, $D^{crack}$ ( $\text{cm}^2/\text{s}$ )	Area of crack, $A_{crack}$ ( $\text{cm}^2$ )	Exponent of equivalent foundation Peclet number, $\exp(Pe^f)$ (unitless)	Infinite source indoor attenuation coefficient, $\alpha$ (unitless)	Infinite source bldg. conc., $C_{building}$ ( $\mu\text{g}/\text{m}^3$ )
15	9.00E+05	1.25	8.33E+01	6.24E-05	5.00E+03	#NUM!	6.34E-06	5.70E+00

Unit risk factor, URF ( $\mu\text{g}/\text{m}^3$ ) <sup>-1</sup>	Reference conc., RFC ( $\text{mg}/\text{m}^3$ )
NA	7.0E-01

**END**

DATA ENTRY SHEET

Table A-33. Maximum Toluene (C9-C18 Aliphatics) Deep Soil Vapor Concentration

DTSC  
Vapor Intrusion Guidance  
Interim Final 12/04  
(last modified 2/4/09)

SG-SCREEN  
PA Version 2.0; 04

Reset to Defaults

Soil Gas Concentration Data				
ENTER Chemical CAS No. (numbers only, no dashes)	ENTER Soil gas conc., $C_g$ ( $\mu\text{g}/\text{m}^3$ )	OR	ENTER Soil gas conc., $C_g$ (ppmv)	Chemical
108883	9.00E+05			Toluene

MORE  
↓

ENTER Depth below grade to bottom of enclosed space floor, $L_F$ (15 or 200 cm)	ENTER Soil gas sampling depth below grade, $L_s$ (cm)	ENTER Average soil temperature, $T_s$ ( $^{\circ}\text{C}$ )	ENTER Vadose zone SCS soil type (used to estimate soil vapor permeability)	OR	ENTER User-defined vadose zone soil vapor permeability, $k_v$ ( $\text{cm}^2$ )
15	304.8	24	S		

MORE  
↓

ENTER Vadose zone SCS soil type Lookup Soil Parameters	ENTER Vadose zone soil dry bulk density, $\rho_b^A$ ( $\text{g}/\text{cm}^3$ )	ENTER Vadose zone soil total porosity, $n^V$ (unitless)	ENTER Vadose zone soil water-filled porosity, $\theta_w^V$ ( $\text{cm}^3/\text{cm}^3$ )	ENTER Average vapor flow rate into bldg. (Leave blank to calculate) $Q_{\text{soil}}$ (L/m)
S	1.83	0.324	0.279	5

MORE  
↓

ENTER Averaging time for carcinogens, $AT_C$ (yrs)	ENTER Averaging time for noncarcinogens, $AT_{NC}$ (yrs)	ENTER Exposure duration, ED (yrs)	ENTER Exposure frequency, EF (days/yr)
70	30	30	350

END

INTERMEDIATE CALCULATIONS SHEET

**Table A-34. Maximum Toluene (C9-C18 Aliphatics) Deep Soil Vapor Concentration**

Source-building separation, $L_T$ (cm)	Vadose zone soil air-filled porosity, $\theta_a^v$ ( $\text{cm}^3/\text{cm}^3$ )	Vadose zone effective total fluid saturation, $S_{te}$ ( $\text{cm}^3/\text{cm}^3$ )	Vadose zone soil intrinsic permeability, $k_i$ ( $\text{cm}^2$ )	Vadose zone soil relative air permeability, $k_{rg}$ ( $\text{cm}^2$ )	Vadose zone soil effective vapor permeability, $k_v$ ( $\text{cm}^2$ )	Floor-wall seam perimeter, $X_{crack}$ (cm)	Soil gas conc., ( $\mu\text{g}/\text{m}^3$ )	Bldg. ventilation rate, $Q_{building}$ ( $\text{cm}^3/\text{s}$ )
289.8	0.045	0.834	1.02E-07	0.055	5.62E-09	4,000	9.00E+05	3.39E+04

Area of enclosed space below grade, $A_B$ ( $\text{cm}^2$ )	Crack-to-total area ratio, $\eta$ (unitless)	Crack depth below grade, $Z_{crack}$ (cm)	Enthalpy of vaporization at ave. soil temperature, $\Delta H_{v,TS}$ (cal/mol)	Henry's law constant at ave. soil temperature, $H_{TS}$ (atm- $\text{m}^3/\text{mol}$ )	Henry's law constant at ave. soil temperature, $H'_{TS}$ (unitless)	Vapor viscosity at ave. soil temperature, $\mu_{TS}$ (g/cm-s)	Vadose zone effective diffusion coefficient, $D_v^{eff}$ ( $\text{cm}^2/\text{s}$ )	Diffusion path length, $L_d$ (cm)
1.00E+06	5.00E-03	15	9,001	6.29E-03	2.58E-01	1.80E-04	3.17E-05	289.8

Convection path length, $L_p$ (cm)	Source vapor conc., $C_{source}$ ( $\mu\text{g}/\text{m}^3$ )	Crack radius, $r_{crack}$ (cm)	Average vapor flow rate into bldg., $Q_{soil}$ ( $\text{cm}^3/\text{s}$ )	Crack effective diffusion coefficient, $D^{crack}$ ( $\text{cm}^2/\text{s}$ )	Area of crack, $A_{crack}$ ( $\text{cm}^2$ )	Exponent of equivalent foundation Peclet number, $\exp(Pe^f)$ (unitless)	Infinite source indoor attenuation coefficient, $\alpha$ (unitless)	Infinite source bldg. conc., $C_{building}$ ( $\mu\text{g}/\text{m}^3$ )
15	9.00E+05	1.25	8.33E+01	3.17E-05	5.00E+03	#NUM!	3.22E-06	2.90E+00

Unit risk factor, URF ( $\mu\text{g}/\text{m}^3$ ) <sup>-1</sup>	Reference conc., RFC ( $\text{mg}/\text{m}^3$ )
NA	3.0E-01

**END**

DATA ENTRY SHEET

Table A-35. Maximum C9-C16 Aromatics Deep Soil Vapor Concentration

DTSC  
Vapor Intrusion Guidance  
Interim Final 12/04  
(last modified 2/4/09)

SG-SCREEN  
PA Version 2.0; 04/

Reset to  
Defaults

Soil Gas Concentration Data				
ENTER Chemical CAS No. (numbers only, no dashes)	ENTER Soil gas conc., $C_g$ ( $\mu\text{g}/\text{m}^3$ )	OR	ENTER Soil gas conc., $C_g$ (ppmv)	Chemical
91576	9.00E+05			2-Methylnaphthalene

MORE  
↓

ENTER Depth below grade to bottom of enclosed space floor, $L_F$ (15 or 200 cm)	ENTER Soil gas sampling depth below grade, $L_s$ (cm)	ENTER Average soil temperature, $T_s$ ( $^{\circ}\text{C}$ )	ENTER Vadose zone SCS soil type (used to estimate soil vapor permeability)	OR	ENTER User-defined vadose zone soil vapor permeability, $k_v$ ( $\text{cm}^2$ )
15	304.8	24	S		

MORE  
↓

ENTER Vadose zone SCS soil type Lookup Soil Parameters	ENTER Vadose zone soil dry bulk density, $\rho_b^A$ ( $\text{g}/\text{cm}^3$ )	ENTER Vadose zone soil total porosity, $n^V$ (unitless)	ENTER Vadose zone soil water-filled porosity, $\theta_w^V$ ( $\text{cm}^3/\text{cm}^3$ )	ENTER Average vapor flow rate into bldg. (Leave blank to calculate) $Q_{\text{soil}}$ (L/m)
S	1.83	0.324	0.279	5

MORE  
↓

ENTER Averaging time for carcinogens, $AT_C$ (yrs)	ENTER Averaging time for noncarcinogens, $AT_{NC}$ (yrs)	ENTER Exposure duration, ED (yrs)	ENTER Exposure frequency, EF (days/yr)
70	30	30	350

END

INTERMEDIATE CALCULATIONS SHEET

**Table A-36. Maximum C9-C16 Aromatics Deep Soil Vapor Concentration**

Source-building separation, $L_T$ (cm)	Vadose zone soil air-filled porosity, $\theta_a^v$ (cm <sup>3</sup> /cm <sup>3</sup> )	Vadose zone effective total fluid saturation, $S_{te}$ (cm <sup>3</sup> /cm <sup>3</sup> )	Vadose zone soil intrinsic permeability, $k_i$ (cm <sup>2</sup> )	Vadose zone soil relative air permeability, $k_{rg}$ (cm <sup>2</sup> )	Vadose zone soil effective vapor permeability, $k_v$ (cm <sup>2</sup> )	Floor-wall seam perimeter, $X_{crack}$ (cm)	Soil gas conc., ( $\mu\text{g}/\text{m}^3$ )	Bldg. ventilation rate, $Q_{building}$ (cm <sup>3</sup> /s)
289.8	0.045	0.834	1.02E-07	0.055	5.62E-09	4,000	9.00E+05	3.39E+04

Area of enclosed space below grade, $A_B$ (cm <sup>2</sup> )	Crack-to-total area ratio, $\eta$ (unitless)	Crack depth below grade, $Z_{crack}$ (cm)	Enthalpy of vaporization at ave. soil temperature, $\Delta H_{v,TS}$ (cal/mol)	Henry's law constant at ave. soil temperature, $H_{TS}$ (atm·m <sup>3</sup> /mol)	Henry's law constant at ave. soil temperature, $H'_{TS}$ (unitless)	Vapor viscosity at ave. soil temperature, $\mu_{TS}$ (g/cm-s)	Vadose zone effective diffusion coefficient, $D_v^{eff}$ (cm <sup>2</sup> /s)	Diffusion path length, $L_d$ (cm)
1.00E+06	5.00E-03	15	16,057	4.72E-04	1.93E-02	1.80E-04	7.07E-05	289.8

Convection path length, $L_p$ (cm)	Source vapor conc., $C_{source}$ ( $\mu\text{g}/\text{m}^3$ )	Crack radius, $r_{crack}$ (cm)	Average vapor flow rate into bldg., $Q_{soil}$ (cm <sup>3</sup> /s)	Crack effective diffusion coefficient, $D^{crack}$ (cm <sup>2</sup> /s)	Area of crack, $A_{crack}$ (cm <sup>2</sup> )	Exponent of equivalent foundation Peclet number, $\exp(Pe^f)$ (unitless)	Infinite source indoor attenuation coefficient, $\alpha$ (unitless)	Infinite source bldg. conc., $C_{building}$ ( $\mu\text{g}/\text{m}^3$ )
15	9.00E+05	1.25	8.33E+01	7.07E-05	5.00E+03	#NUM!	7.18E-06	6.46E+00

Unit risk factor, URF ( $\mu\text{g}/\text{m}^3$ ) <sup>-1</sup>	Reference conc., RFC (mg/m <sup>3</sup> )
NA	1.4E-02

**END**