



**CONESTOGA-ROVERS  
& ASSOCIATES**

10969 Trade Center Drive, Suite 107  
Rancho Cordova, California 95670  
Telephone: (916) 889-8900 Fax: (916) 889-8999  
www.CRAworld.com

## TRANSMITTAL

DATE: August 12, 2011 REFERENCE NO.: 611951

Former Chevron Station 9-3864  
(RO351)

PROJECT NAME:

TO: Mr. Mark Detterman, P.G., C.E.G.  
Alameda County Environmental Health  
1131 Harbor Bay Parkway, Suite 250  
Alameda, CA 94502-6577

**RECEIVED**  
  
11:48 am, Aug 19, 2011  
Alameda County  
Environmental Health

Please find enclosed:  Draft  Final  
 Originals  Other  
 Prints

Sent via:  Mail  Same Day Courier  
 Overnight Courier  Other ACEH FTP Site Electronic Upload

QUANTITY	DESCRIPTION
1	Case Closure Request

As Requested  For Review and Comment  
 For Your Use

COMMENTS:

Copy to: Ms. Olivia Skance, Chevron  
Mr. Howard Schindler  
Mr. John Gwynn

Completed by: James P. Kiernan  
[Please Print]

Signed: 

Filing: **Correspondence File**



**Olivia Skance**  
Team Lead  
Marketing Business Unit

**Chevron Environmental  
Management Company**  
6101 Bollinger Canyon Road  
San Ramon, CA 94583  
Tel (925) 790-6521

August 12, 2011

Alameda County Environmental Health  
1131 Harbor Bay Parkway, Suite 250  
Alameda, CA 94502-6577

Re: Chevron Facility # 9-3864

Address: 5101 Telegraph Avenue, Oakland, California

I have reviewed the attached report titled Case Closure Request and dated August 12, 2011.

I agree with the conclusions and recommendations presented in the referenced report. The information in this report is accurate to the best of my knowledge and all local Agency/Regional Board guidelines have been followed. This report was prepared by Conestoga-Rovers & Associates, upon whose assistance and advice I have relied.

This letter is submitted pursuant to the requirements of California Water Code Section 13267(b)(1) and the regulating implementation entitled Appendix A pertaining thereto.

I declare under penalty of perjury that the foregoing is true and correct.

Sincerely,

A handwritten signature in blue ink that reads "Olivia Skance".

Olivia Skance  
Project Manager

Enclosure: Report



## **CASE CLOSURE REQUEST**

**Former Chevron Service Station 9-3864  
5101 Telegraph Avenue  
Oakland, California  
Case No. RO0000351**

**Prepared for:**

**Mr. Mark Detterman, P.G., C.E.G.  
Alameda County Environmental Health  
1131 Harbor Bay Parkway, Suite 250  
Alameda, California 94502-6577**

**Prepared by:  
Conestoga-Rovers  
& Associates**

10969 Trade Center Drive, #107  
Rancho Cordova, California  
U.S.A. 95670

Office: (916) 889-8900  
Fax: (916) 889-8999

web: <http://www.CRAworld.com>

**AUGUST 12, 2011  
REF. NO. 611951 (6)**

This report is printed on recycled paper.



## CASE CLOSURE REQUEST

**Former Chevron Service Station 9-3864  
5101 Telegraph Avenue  
Oakland, California  
Case No. RO0000351**

---

**Christopher J. Benedict**

---

**James P. Kiernan, P.E.**



**Prepared by:  
Conestoga-Rovers  
& Associates**

10969 Trade Center Drive, #107  
Rancho Cordova, California  
U.S.A. 95670

Office: (916) 889-8900  
Fax: (916) 889-8999

web: <http://www.CRAworld.com>

**AUGUST 12, 2011**

**REF. NO. 611951 (6)**

This report is printed on recycled paper.



TABLE OF CONTENTS

	<u>Page</u>
1.0 INTRODUCTION .....	1
2.0 SITE DESCRIPTION AND BACKGROUND .....	1
2.1 NEARBY KNOWN RELEASES.....	2
3.0 SITE CHARACTERISTICS.....	3
3.1 GEOLOGY AND HYDROGEOLOGY .....	3
3.2 NEARBY WELLS AND SENSITIVE RECEPTORS.....	3
4.0 CONSTITUENTS OF CONCERN.....	4
4.1 SOIL.....	4
4.2 GROUNDWATER.....	4
5.0 PETROLEUM HYDROCARBON SOURCES AND DISTRIBUTION.....	5
5.1 RELEASE SOURCE AND VOLUME.....	5
5.2 POTENTIAL OFFSITE SOURCES.....	5
5.3 PETROLEUM HYDROCARBONS IN SOIL.....	5
5.4 PETROLEUM HYDROCARBONS IN GROUNDWATER.....	6
6.0 RISK EVALUATION .....	7
6.1 NEARBY WELLS AND SENSITIVE RECEPTORS.....	7
6.2 POTENTIAL EXPOSURE PATHWAYS.....	8
6.2.1 SOIL.....	8
6.2.2 GROUNDWATER.....	8
6.2.3 SURFACE WATER.....	8
6.2.4 VAPOR INTRUSION.....	9
6.3 COMPARISON TO ENVIRONMENTAL SCREENING LEVELS.....	9
6.3.1 SOIL.....	9
6.3.2 GROUNDWATER.....	10
6.3.3 SOIL VAPOR.....	11
7.0 LOW-RISK GROUNDWATER CRITERIA.....	12
7.1 THE LEAK HAS BEEN STOPPED AND ONGOING SOURCES, INCLUDING LNAPL, HAVE BEEN REMOVED OR REMEDIATED .....	12
7.2 THE SITE HAS BEEN ADEQUATELY CHARACTERIZED .....	13
7.3 THE DISSOLVED HYDROCARBON PLUME IS STABLE, DECREASING, AND NOT MIGRATING .....	13
7.4 NO WATER WELLS, DEEPER DRINKING WATER AQUIFERS, SURFACE WATER, OR OTHER SENSITIVE RECEPTORS ARE LIKELY TO BE IMPACTED .....	13
7.5 THE SITE PRESENTS NO SIGNIFICANT RISK TO HUMAN HEALTH OR THE ENVIRONMENT.....	14
8.0 CONCLUSIONS AND RECOMMENDATIONS .....	14

LIST OF FIGURES  
(Following Text)

FIGURE 1	VICINITY MAP
FIGURE 2	SITE PLAN
FIGURE 3	TPHG GROUNDWATER ISOCONCENTRATION MAP - MARCH 14, 2011
FIGURE 4	TPHG GROUNDWATER ISOCONCENTRATION MAP - DECEMBER 11, 1996

LIST OF TABLES  
(Following Text)

TABLE 1	SOIL SAMPLE ANALYTICAL RESULTS
TABLE 2	GROUNDWATER SAMPLE ANALYTICAL RESULTS

LIST OF APPENDICES

APPENDIX A	SUMMARY OF ENVIRONMENTAL INVESTIGATION AND REMEDIATION
APPENDIX B	HISTORICAL BORING LOGS
APPENDIX C	WELL SURVEY INFORMATION AND TEMESCAL CREEK MAP
APPENDIX D	PREVIOUS SITE PLANS
APPENDIX E	FIRST SEMI-ANNUAL 2011 GROUNDWATER MONITORING REPORT
APPENDIX F	HISTORICAL ISOCONCENTRATION MAPS AND NEARBY GROUNDWATER DATA
APPENDIX G	CONCENTRATION VERSUS TIME AND TREND GRAPHS AND DEGRADATION CALCULATIONS
APPENDIX H	PREVIOUS RISK ASSESSMENT RESULTS

## 1.0 INTRODUCTION

Conestoga-Rovers & Associates (CRA) is submitting this *Case Closure Request* on behalf of Chevron Environmental Management Company (Chevron) for former Chevron service station 9-3864 located at 5101 Telegraph Avenue in Oakland, California. Based on our review of the site background and conditions, this site meets the San Francisco Bay Regional Water Quality Control Board (RWQCB) criteria for closure as a low-risk groundwater case, as described in their January 5, 1996 memorandum entitled *Interim Guidance on Required Cleanup of Low-Risk Fuel Sites*. Please note that this closure request supersedes the June 26, 2009 *Site Status and Revised Work Plan* (work plan), to which a response was not received from Alameda County Environmental Health (ACEH), however, in our opinion the proposed work therein is no longer warranted. Presented below are the site description and background, site conditions and discussion of remaining impacts, an evaluation of potential risk, rationale for closure based on the low-risk criteria, and our conclusions and recommendations.

## 2.0 SITE DESCRIPTION AND BACKGROUND

The triangular site is located between 51<sup>st</sup> Street, 52<sup>nd</sup> Street, and Telegraph Avenue (Figure 1), and is currently developed with two, one- and two-story commercial buildings and associated parking and landscaping areas (known as Temescal Triangle); the buildings are occupied by various retail businesses and a restaurant. Land use in the vicinity of the site is mixed commercial and residential.

The site was occupied by a Chevron service station from approximately 1970 to 1991. Former station facilities included two 10,000-gallon and one 5,000-gallon steel gasoline underground storage tanks (USTs), a 1,000-gallon steel used-oil UST, and associated dispensers and piping. The station was demolished in 1991 and all aboveground and belowground facilities were removed. The site remained vacant until redevelopment with the existing buildings in the late-1990s. Current and former site features are shown on Figure 2.

Environmental work has been ongoing since 1990, and has included the installation of monitoring wells C-1 through C-4 and MW-1 through MW-5; the drilling of exploratory borings TC-1 through TC-5; and confirmation soil sampling during UST removals. In 1998, ownership of MW-4 was transferred to the responsible party at the upgradient former Autopro facility (5200 Telegraph Avenue) and it was re-named MW-5. Wells C-1, C-2, and C-4 were destroyed in 1996 and 1997 to facilitate site redevelopment. Remedial activities have included excavation and offsite disposal or aeration of

hydrocarbon-bearing soil (approximately 600 cubic yards), and the placement of Oxygen Release Compound® (ORC) in wells C-3 and MW-3. A summary of the environmental work is presented in Appendix A. The historical soil and groundwater sample analytical results are presented in Tables 1 and 2, respectively. The approximate well and boring locations are shown on Figure 2.

## **2.1 NEARBY KNOWN RELEASES**

Based on our review of available documents, there are several known petroleum hydrocarbon releases in the nearby site vicinity. These releases and work performed are summarized below. Most of these facilities are shown on Figure 2.

### ***Former Autopro***

This upgradient facility (current smog test shop) was formerly an auto repair facility and Shell station with documented releases of gasoline (and related constituents), diesel, and waste oil. Elevated concentrations of total petroleum hydrocarbons as gasoline (TPHg) and diesel (TPHd) historically have been detected in wells MW-3 and MW-4 at the facility. During the most recent event in March 2011, these wells contained up to 6,900 micrograms per liter ( $\mu\text{g}/\text{L}$ ) TPHg, 8,400  $\mu\text{g}/\text{L}$  TPHd, and 18,000  $\mu\text{g}/\text{L}$  TPH as motor oil (TPHmo). Elevated concentrations of TPHg (up to 26,000  $\mu\text{g}/\text{L}$ ) and TPHd (up to 4,500  $\mu\text{g}/\text{L}$ ) were also historically detected in well MW-5 (former Chevron MW-4) in Telegraph Avenue adjacent to the facility. A groundwater sample collected in 2004 adjacent to a storm drain line in Telegraph Avenue downgradient of the facility contained 57,000  $\mu\text{g}/\text{L}$  TPHg and 29,000  $\mu\text{g}/\text{L}$  TPHd. Additional investigation to further evaluate the downgradient extent of contamination and potential preferential pathways is planned. Groundwater containing petroleum hydrocarbons has migrated from this facility beneath the subject site, and is discussed further in Section 5.4.

### ***5239 Telegraph Avenue***

Elevated concentrations of TPHg (up to 17,000  $\mu\text{g}/\text{L}$ ) were detected in groundwater in 2007 beneath this property to the north (cross- to upgradient) of the subject site (Figure 2). The property is occupied by a vacant restaurant building; with no likely source of the contamination identified. As such, the case was closed by ACEH and the contamination attributed to the former Autopro facility.

### ***Former Berkeley Land Company***

The property to the south/southwest of the site across 51st Street (existing Temescal Plaza shopping center) was previously known as the Berkeley Land Company property at 5100 Telegraph Avenue, and was formerly occupied by a street car storage and

maintenance facility with several USTs. Numerous borings were drilled and several wells installed on the property (Figure 2), and soil and groundwater were found to be impacted with petroleum hydrocarbons, chlorinated solvents, and metals. Undocumented fill material (as deep as 17.5 feet below grade [fbg]) was also observed. Remediation was conducted and the case was closed in 1999 by ACEH; however, it was noted that petroleum hydrocarbons and chlorinated solvents remained in soil and/or groundwater.

#### *Former Marshall Steel Cleaners*

This former large dry cleaning facility (now Telegraph Business Park at 5427 Telegraph Avenue) located approximately 500 feet north-northeast (upgradient) of the site has documented releases of TPHg and Stoddard solvent; 17 USTs were removed from the property in 1992. In December 2010, up to 2,000 µg/L TPHg and 12,000 µg/L Stoddard solvent were detected in wells at the facility, and investigation is ongoing.

### 3.0 SITE CHARACTERISTICS

#### 3.1 GEOLOGY AND HYDROGEOLOGY

The site is located on a gently sloping plane west of the Piedmont Hills, approximately 2 miles east of San Francisco Bay. The soil in the site vicinity consists of Late Pleistocene alluvium consisting of weakly consolidated, slightly weathered, poorly sorted, irregularly interbedded clay, silt, sand and gravel. Soil encountered during drilling at the site was reported to consist of interbedded layers of silt, clay, sand, and gravel with varying amounts of one or more of the other soil types within each layer. Copies of the historical boring logs are presented in Appendix B.

Groundwater was encountered during drilling at depths of approximately 12.5 to 17.5 fbg. Depth to groundwater in the wells has ranged from approximately 4.5 to 17.5 feet below top of casing (TOC), but typically fluctuates between 12 and 15 feet below TOC. The groundwater flow direction is generally to the southwest following the local topography (see rose diagram on Figure 2).

#### 3.2 NEARBY WELLS AND SENSITIVE RECEPTORS

CRA reviewed California Department of Water Resources (DWR) and Alameda County Public Works Agency (ACPWA) files to identify any water-supply wells within 2,000 feet of the site. Seven wells were identified within the search radius (excluding monitoring wells): an industrial well approximately 750 feet north (cross- to upgradient), four

cathodic protection wells approximately 1,150 feet southeast (crossgradient), an irrigation well at Children's Hospital approximately 1,500 feet west (crossgradient), and a domestic well approximately 1,900 feet north-northeast (upgradient). The well survey results and a figure showing the identified well locations are presented in Appendix C.

There do not appear to be any sensitive receptors within 2,000 feet of the site in the downgradient direction with the exception of some residential areas at least 600 feet from well MW-3. The local water supply is provided by East Bay Municipal Utility District (EBMUD); the source is the Mokelumne River Basin in the Sierra Nevada range. Shallow groundwater in the site area is not likely to be used as a drinking water source in the foreseeable future. The nearest surface water body is Temescal Creek, which appears to flow in an underground culvert through the property to the south of the site across 51<sup>st</sup> Street. A map showing the creek location is presented in Appendix C.

#### **4.0 CONSTITUENTS OF CONCERN**

##### **4.1 SOIL**

Based on the historical data, the primary constituent of concern (COC) in remaining soil (i.e. not excavated) is TPHg; however, it was not detected in the majority of the soil samples (not considering borings TC-4 and MW-4 drilled adjacent to the Autopro facility). The samples with TPHg detections generally contained only low concentrations (up to 270 milligrams per kilogram [mg/kg]); higher concentrations (up to 980 mg/kg) were detected in the samples collected at 15.5 fbg (groundwater interface) from the sidewalls of the gasoline UST excavation, which was excavated to 18 fbg at which depth the soil no longer appeared to be impacted. Benzene, toluene, ethylbenzene, and xylenes (BTEX) are less significant COCs in soil, as they were only detected in a few samples at low concentrations (benzene detected in six samples at a maximum of only 0.069 mg/kg). Other constituents were not detected and therefore are not COCs in soil. Copies of previous site plans showing the excavation areas and confirmation sample locations are presented in Appendix D.

##### **4.2 GROUNDWATER**

Based on the monitoring results, and as with soil, the primary COC remaining in groundwater is TPHg. Ethylbenzene and xylenes are present in groundwater, but are insignificant COCs as only low concentrations (up to 1 µg/L) remain in one or two wells. Benzene is no longer detected and methyl tertiary butyl ether (MTBE) has not been

detected for at least several years. Therefore, these constituents are not COCs in groundwater.

## **5.0 PETROLEUM HYDROCARBON SOURCES AND DISTRIBUTION**

### **5.1 RELEASE SOURCE AND VOLUME**

Based on previous investigations and UST/piping removal confirmation sampling, the primary source(s) of the petroleum hydrocarbons appears to be the former UST system. Although the volume of released hydrocarbons is unknown, approximately 600 cubic yards of impacted soil was excavated and disposed or treated. This remedial action has adequately mitigated the release as evidenced by generally decreasing hydrocarbon concentrations in groundwater.

### **5.2 POTENTIAL OFFSITE SOURCES**

Based on the historical data, the upgradient former Autopro facility appears to be contributing to the impacts at the site. This facility is discussed further in Section 5.4 below.

### **5.3 PETROLEUM HYDROCARBONS IN SOIL**

Based on the analytical data, soil with residual COCs likely remains in the area of the former gasoline USTs and dispensers; however, concentrations are generally low. The COCs were also detected in the soil sample collected just above groundwater from the boring for upgradient well C-1, indicating that petroleum hydrocarbons were migrating beneath the site from an offsite source. The remedial excavations ranged from approximately 5 to 18 fbg, and appear to have removed the majority of hydrocarbon mass source in soil. Based on the analytical results and excavation activities, the extent of petroleum hydrocarbons in soil is adequately defined, and no further investigation is warranted. It should be noted that since the soil samples were collected in the early 1990s, concentrations likely have further decreased over time due to natural attenuation processes as evidenced by decreasing hydrocarbon concentrations in groundwater. The historical soil sample analytical results are presented in Table 1 (samples collected from areas that were later excavated are shaded).

## 5.4 PETROLEUM HYDROCARBONS IN GROUNDWATER

Groundwater has been monitored since 1990. Onsite well C-3 and downgradient well MW-3 are currently sampled semi-annually, and offsite perimeter wells MW-1, MW-2 and MW-5 are sampled annually. The COCs only remain in C-3 or MW-3 and generally have not been detected in MW-1, MW-2, or MW-5 throughout the course of monitoring. A copy of the first semi-annual 2011 groundwater monitoring report is presented in Appendix E.

Based on the monitoring results, groundwater containing the COCs remains beneath the site in the area of well C-3 downgradient of the former USTs and dispensers, as well as downgradient beneath 51<sup>st</sup> Street in the area of well MW-3. Groundwater containing the COCs also likely remains beneath the site upgradient of C-3; however, as previously mentioned, impacted groundwater is migrating beneath the site from the upgradient Autopro facility. Prior to its destruction in 1996, upgradient well C-1 consistently contained TPHg (up to 7,700 µg/L), BTEX (benzene up to 170 µg/L), and MTBE (up to 87 µg/L) (Appendix E). Groundwater samples collected in 1996 from Autopro borings AP-2 and AP-3 located upgradient of the subject site (Figure 2) contained up to 74,000 µg/L TPHd, 14,000 µg/L TPHg, and 130 µg/L benzene (Appendix F). Historical groundwater isoconcentration maps (prepared by others) incorporating the monitoring results at both sites are presented in Appendix F; these include maps of TPH as diesel (TPHd) and motor oil (TPHmo), which were not COCs at the subject site, but show the extent of the impacts from Autopro. Although the last analytical data in C-1 was from 1996, based on the current concentrations in groundwater at the Autopro facility, the contribution to impacts at the subject site likely remains significant. A current isoconcentration map of TPHg in groundwater is presented on Figure 3, which includes data from the Autopro facility. A TPHg isoconcentration map prepared using data from 1996 which was the last time all the site and Autopro wells were sampled is presented on Figure 4. As an upgradient source is contributing to the impacts beneath the site, it is not possible to accurately estimate the dissolved TPHg mass remaining.

Based on the perimeter borings and wells, the lateral extent of hydrocarbons in groundwater is adequately defined. The downgradient extent of dissolved hydrocarbons is defined by previous groundwater monitoring data from wells at the Berkeley Land Company property downgradient of the site across 51<sup>st</sup> Avenue (Appendix F), as was presented in the above-mentioned June 26, 2009 work plan.

Graphs of TPHg and benzene concentrations over time in wells C-3 and MW-3 are presented in Appendix G. As shown in the graphs, the TPHg concentrations in C-3 have remained relatively stable over the past 10 years, which, as source removal at the site



occurred 20 years ago, is indicative of continuing offsite contributions. Conversely, the TPHg concentrations in MW-3 are declining, indicating the plume has reached its maximum extent and is decreasing in size and mass due to natural attenuation. A comparison of the historical maximum and most recent TPHg, benzene, and MTBE concentrations in the wells is presented in Table A below.

<b>TABLE A</b> <b>COMPARISON OF MAXIMUM AND MOST RECENT CONCENTRATIONS IN</b> <b>GROUNDWATER</b> <b>(concentrations in µg/L)</b>						
Well ID	TPHg		Benzene		MTBE <sup>a</sup>	
	Max Conc.	Most Recent Conc.	Max Conc.	Most Recent Conc.	Max Conc.	Most Recent Conc.
C-3	34,000 (12-6-94)	3,400 (3-14-11)	390 (12-21-92)	<0.5 (3-14-11)	10 (9-15-04)	<0.5 (3-14-11)
MW-1	350 (6-17-94)	<50 (3-14-11)	1.2 (6-17-94)	<0.5 (3-14-11)	<0.5 (all)	<0.5 (3-14-11)
MW-2	330 (6-17-94)	<50 (3-14-11)	1.4 (6-17-94)	<0.5 (3-14-11)	<0.5 (all)	<0.5 (3-14-11)
MW-3	13,000 (12-6-94)	1,300 (3-14-11)	610 (12-6-94)	<0.5 (3-14-11)	<0.5 (all)	<0.5 (3-14-11)
MW-5	1,000 (8-29-94)	<50 (3-14-11)	25 (9-20-93)	<0.5 (3-14-11)	<0.5 (all)	<0.5 (3-14-11)
a	Only results obtained using EPA Method 8260 reported					
<	Not detected at or above stated laboratory reporting limit					

## 6.0 RISK EVALUATION

To evaluate potential risks to human health or the environment associated with the residual petroleum hydrocarbons in soil and groundwater, CRA evaluated the presence of wells and potential sensitive receptors in the site vicinity, evaluated potential receptor exposure pathways, and performed a screening-level risk evaluation. We also relied on the results of a previous risk assessment (dated December 29, 1992) prepared for the site. The findings of the risk evaluation are presented below.

### 6.1 NEARBY WELLS AND SENSITIVE RECEPTORS

As described in Section 3.2, although several water-supply wells were identified within 2,000 feet, none were located in the downgradient direction and thus are unlikely to be impacted by petroleum hydrocarbons from the site. The local drinking water supply is obtained from distant surface water.

The site is in commercial use and therefore no sensitive receptors exist at the site. Some residential areas are located at least 600 feet downgradient from the site. However, drinking water is supplied by EBMUD.

Based on this information, there do not appear to be any wells or sensitive receptors that would likely be impacted by petroleum hydrocarbons from the site.

## **6.2 POTENTIAL EXPOSURE PATHWAYS**

### **6.2.1 SOIL**

As the site is generally capped with the existing development, potential exposure to any residual hydrocarbon-bearing soil beneath the site by the general public is de minimis. Therefore, the only identified potential exposure pathway is direct exposure by construction workers during trenching or excavation activities. However, the residual hydrocarbon concentrations in soil at shallow depths where a construction worker could be exposed were low and limited in extent. Additionally, the previous risk assessment indicated no significant risk to potential construction workers or hypothetical site residents. A copy of the previous risk assessment results is presented in Appendix H.

### **6.2.2 GROUNDWATER**

The extent of impacted groundwater appears to be adequately defined, not migrating, and no water supply wells appear likely to be impacted. Therefore, no complete groundwater ingestion pathways exist and none are likely to exist in the foreseeable future based on the current municipal water supply. Based on the depth to groundwater encountered in the borings and excavations, it is unlikely any typical construction activities would encounter groundwater.

### **6.2.3 SURFACE WATER**

The nearest surface water body appears to be Temescal Creek approximately 200 feet downgradient of the site. However, this section of the creek is confined to an underground culvert, and thus unlikely to be impacted by hydrocarbons from the site.

#### **6.2.4 VAPOR INTRUSION**

Remedial excavation was performed to remove/treat secondary hydrocarbon source soil. Benzene, considered the primary risk driver for vapor intrusion as it is a known human carcinogen, is no longer detected in groundwater indicating limited residual source in soil. Although TPHg remains in groundwater beneath the site, at least a portion appears to be originating from the upgradient Autopro facility. The previous risk assessment indicated no significant vapor intrusion risk, even under the most conservative residential land use scenario (Appendix H), and residual TPHg concentrations were higher at this time and benzene was present. Based on this information, potential vapor intrusion is not a concern.

#### **6.3 COMPARISON TO ENVIRONMENTAL SCREENING LEVELS**

The maximum residual COC concentrations in soil and groundwater were compared to the corresponding environmental screening levels (ESLs) established by the RWQCB in May 2008. The ESLs are for use as screening levels in determining if further evaluation is warranted, in prioritizing areas of concern, in establishing cleanup goals, and in estimation of potential health risks. As stated by the RWQCB, the ESLs are considered to be conservative. The presence of a chemical at a concentration above an ESL does not necessarily indicate that adverse impacts to human health or the environment are occurring; rather exceeding ESLs indicates that the potential for impacts may exist and that additional evaluation may be needed. Under most circumstances, the presence of a chemical in soil, groundwater, or soil gas at concentrations below the corresponding ESL can be assumed to not pose a significant, long-term (chronic) threat to human health and the environment. For soil vapor, the most recent groundwater concentrations were compared to the ESLs for evaluation of potential vapor intrusion concerns, where established.

##### **6.3.1 SOIL**

The only complete potential exposure pathway to residual hydrocarbons in soil is direct exposure by construction workers during trenching or excavation activities. Table B below presents a comparison of the maximum COC concentrations detected in remaining soil to the respective ESLs associated with construction/trench worker direct exposure concerns. The results were also compared to the shallow or deep soil ESLs (values are identical) for groundwater protection (soil leaching) at commercial sites where groundwater is a current or potential drinking water source.

<b>TABLE B. COMPARISON OF MAXIMUM RESIDUAL SOIL CONCENTRATIONS TO ESLs (concentrations in mg/kg)</b>			
<i>Constituent</i>	<i>Highest Detected Concentration Remaining in Soil</i>	<i>ESL for Construction/Trench Worker Exposure<sup>1</sup></i>	<i>ESL for Groundwater Protection<sup>2</sup></i>
TPHg	980 (#4; 15.5 fbq; 9/26/91)	4,200	83
Benzene	0.069 (#2; 5 fbq; 9/26/91) (#3; 15.5 fbq; 9/26/91)	12	0.044
Toluene	2.7 (#4; 15.5 fbq; 9/26/91)	650	2.9
Ethylbenzene	2.5 (#4; 15.5 fbq; 9/26/91)	210	3.3
Xylenes	5.5 (#4; 15.5 fbq; 9/26/91)	420	2.3
<ol style="list-style-type: none"> <li>1. ESLs from Table K-3, Direct Exposure Soil Screening Levels, Construction/Trench Worker Exposure Scenario, in <i>Screening for Environmental Concerns at Sites with Contaminated Soil and Groundwater</i>, RWQCB-May 2008</li> <li>2. ESLs from Table A-2, Shallow Soil Screening Levels, Commercial/Industrial Land Use, Groundwater is a current or potential source of drinking water, in <i>Screening for Environmental Concerns at Sites with Contaminated Soil and Groundwater</i>, RWQCB-May 2008</li> </ol>			

As shown above, the maximum detected COC concentrations in remaining soil are well below the respective ESLs for construction/trench worker exposure. The historical maximum TPHg, benzene, and xylenes concentrations (1991) slightly exceed the ESLs associated with groundwater protection; however, concentrations in groundwater are generally declining (benzene no longer detected) and therefore any residual impacted soil does not appear to be acting as a significant continuing source of hydrocarbons that would reverse overall improving trends. In addition, as these samples were collected 20 years ago, concentrations have likely decreased due to natural attenuation. To be conservative, the results were compared to the ESLs associated with sites where groundwater is a potential drinking water source; however, at this site drinking water is provided by EBMUD and groundwater is not likely to be used as a resource in the foreseeable future. Therefore, the residual hydrocarbons in soil do not appear to pose a significant threat to human health or the environment, as indicated in the previous risk assessment.

### 6.3.2 GROUNDWATER

As described above, there were no identified complete groundwater ingestion pathways. However, the most recent COC concentrations detected in groundwater were compared to the ESLs at sites where groundwater is a current or potential source of drinking water. The comparison is presented in Table C below.

<b>TABLE C. COMPARISON OF MOST RECENT MAXIMUM GROUNDWATER CONCENTRATIONS TO ESLs (concentrations in µg/L)</b>		
<i>Constituent</i>	<i>Highest Detected Concentration Remaining in Groundwater</i>	<i>Groundwater ESL<sup>1</sup></i>
TPHg	3,400	100
Ethylbenzene	0.6	30
Xylenes	1	20
1. ESLs from Table C, ESLs for Deep Soils, groundwater is a current or potential drinking water resource, <i>Screening for Environmental Concerns at Sites with Contaminated Soil and Groundwater</i> , RWQCB-May 2008		

As shown above, the maximum detected TPHg concentration in groundwater exceeds the ESL. However, the source has been removed, and the plume is stable, decreasing, and not migrating, and no wells or sensitive receptors are likely to be impacted. Additionally, at least a portion of the detected TPHg is likely due to an offsite source. Therefore, the residual petroleum hydrocarbons in groundwater at the site do not appear to pose a significant threat to human health or the environment.

Degradation trend analysis estimates that the TPHg concentration in MW-3 will reach the ESL by February 2037 (Appendix G), which is a reasonable amount of time given the municipal water supply. An analysis was not performed for C-3 due to the offsite contributing source.

### 6.3.3 SOIL VAPOR

The most recent residual COC concentrations in groundwater were compared to the groundwater ESLs for evaluation of potential vapor intrusion concerns at residential sites (most conservative). However, as shown in Table D below, the only remaining COCs with corresponding ESLs are ethylbenzene and xylenes.

<b>TABLE D. COMPARISON OF MOST RECENT MAXIMUM GROUNDWATER CONCENTRATIONS TO ESLs ASSOCIATED WITH VAPOR INTRUSION CONCERNS (concentrations in µg/L)</b>		
<i>Constituent</i>	<i>Highest Detected Concentration Remaining in Groundwater</i>	<i>ESL<sup>1</sup></i>
Ethylbenzene	0.6	170,000
Xylenes	1.0	160,000
1. ESLs from Table E-1, Groundwater Screening Levels for Evaluation of Potential Vapor Intrusion Concerns, in <i>Screening for Environmental Concerns at Sites with Contaminated Soil and Groundwater</i> , RWQCB-May 2008		

As shown above, the residual concentrations in groundwater are well below the corresponding ESLs and thus do not pose a significant threat to human health. Regardless, as previously discussed, potential vapor intrusion does not appear to be a concern and no further work appears warranted.

## 7.0 LOW-RISK GROUNDWATER CRITERIA

The site meets the RWQCB criteria for classification as a low-risk groundwater case. As described in the RWQCB memorandum, a low-risk groundwater case has the following general characteristics:

- The leak has been stopped and ongoing sources, including light non-aqueous phase liquid (LNAPL), have been removed or remediated.
- The site has been adequately characterized.
- The dissolved hydrocarbon plume is not migrating.
- No water wells, deeper drinking water aquifers, surface water, or other sensitive receptors are likely to be impacted.
- The site presents no significant risk to human health or the environment.

Each low-risk groundwater case criteria, as it pertains to the site, is discussed below.

### 7.1 THE LEAK HAS BEEN STOPPED AND ONGOING SOURCES, INCLUDING LNAPL, HAVE BEEN REMOVED OR REMEDIATED

All original potential sources of the petroleum hydrocarbons from the subject site (former USTs, dispensers, and piping) were removed in 1991. The remedial excavation removed

the majority of the hydrocarbon mass from the original source areas. As previously described, hydrocarbons are migrating beneath the site from an offsite source, and likely contributing to the stable TPHg concentrations in C-3. Otherwise, concentrations in groundwater are decreasing, indicating any residual hydrocarbons in soil are not acting as a significant continuing source that would reverse these trends. LNAPL has not been observed in any of the wells. Based on this information, the leak has been stopped and ongoing sources have been removed.

## **7.2 THE SITE HAS BEEN ADEQUATELY CHARACTERIZED**

Soil sample analytical results and excavation activities indicate that the extent of impacted soil has been adequately defined. Groundwater monitoring has been performed since 1990. The plume appears to be stable and the extent adequately defined. Concentrations are expected to continue to decrease over time due to natural attenuation.

Although soil vapor sampling has not been performed, potential vapor intrusion does not appear to be a concern at the site based on the lack of benzene in soil and groundwater and the results of the previous risk assessment. Based on this information, the extent of impact has been defined to the degree necessary to demonstrate that the site does not present a significant threat to human health or the environment, and no further work is warranted.

## **7.3 THE DISSOLVED HYDROCARBON PLUME IS STABLE, DECREASING, AND NOT MIGRATING**

Based on the monitoring results, the plume appears stable, shrinking, and not migrating. Natural attenuation is expected to continue to reduce the remaining concentrations to background levels. The TPHg concentration in MW-3 is estimated to reach the ESL by 2037.

## **7.4 NO WATER WELLS, DEEPER DRINKING WATER AQUIFERS, SURFACE WATER, OR OTHER SENSITIVE RECEPTORS ARE LIKELY TO BE IMPACTED**

No water wells, surface water or other sensitive receptors were identified that are likely to be impacted by petroleum hydrocarbons from the site.

## **7.5 THE SITE PRESENTS NO SIGNIFICANT RISK TO HUMAN HEALTH OR THE ENVIRONMENT**


The site is generally capped with the existing development, thus potential exposure to any residual impacted soil by the general public is precluded. Regardless, the previous risk assessment indicated no significant risk to either construction workers or hypothetical residents. The maximum residual detected concentrations in soil of a few COCs exceeded the ESLs associated with groundwater protection; however, concentrations in groundwater are generally decreasing indicating the lack of a significant continuing soil source. Although impacted groundwater remains beneath the site, and an upgradient source is contributing to the impacts, natural attenuation is expected to continue to decrease concentrations to background levels over time. No sensitive receptors appear likely to be impacted given the plume appears stable, decreasing in size and mass, and is limited in extent. Potential vapor intrusion has been shown to not be a significant concern. Based on this information, the site does not pose a significant risk to human health or the environment.

## **8.0 CONCLUSIONS AND RECOMMENDATIONS**

Based on the site conditions and analytical data, the site satisfies the RWQCB criteria for classification as a low-risk groundwater case. The extent of hydrocarbons in soil and groundwater has been adequately defined and no further work is warranted. The dissolved hydrocarbon plume is stable, decreasing, and an upgradient source is contributing to site impacts. The residual petroleum hydrocarbons in soil and groundwater at the site do not pose a significant threat to human health or the environment. The site is expected to remain in commercial use for the foreseeable future. Therefore, on behalf of Chevron, CRA respectfully requests the site be considered for low-risk case closure.



## FIGURES




SOURCE: TOPO! MAPS.


figure 1

VICINITY MAP  
 FORMER CHEVRON SERVICE STATION 9-3864  
 5101 TELEGRAPH AVENUE  
 Oakland, California





SOURCE: GETTLER-RYAN INC.



HISTORICAL GROUNDWATER FLOW DIRECTION

**LEGEND**

- CHEVRON MONITORING WELL LOCATION
- CHEVRON EXPLORATORY BORING LOCATION
- ⊕ AUTOPRO WELL LOCATION
- ⊠ AUTOPRO EXPLORATORY BORING LOCATION
- ⊡ AUTOPRO TRENCH EXPLORATORY BORING LOCATION
- ⊞ 5239 TELEGRAPH EXPLORATORY BORING LOCATION
- ⊞ FORMER BERKELEY LAND CO. EXPLORATORY BORING LOCATION
- ⊞ ABANDONED CHEVRON WELL LOCATION
- ⊞ FORMER BERKELEY LAND CO. WELL LOCATION
- STM --- STORM DRAIN LINE
- SAN --- SANITARY SEWER LINE






figure 2  
**SITE PLAN**  
 FORMER CHEVRON STATION 9-3864  
 5101 TELEGRAPH AVENUE  
 Oakland, California






SOURCE: GETTLER-RYAN INC.



HISTORICAL GROUNDWATER FLOW DIRECTION




**LEGEND**

- CHEVRON MONITORING WELL LOCATION
- CHEVRON EXPLORATORY BORING LOCATION
- ⊕ AUTOPRO WELL LOCATION
- ⊠ AUTOPRO EXPLORATORY BORING LOCATION
- ⊡ AUTOPRO TRENCH EXPLORATORY BORING LOCATION
- ⊞ 5239 TELEGRAPH EXPLORATORY BORING LOCATION
- ⊞ FORMER BERKELEY LAND CO. EXPLORATORY BORING LOCATION
- ⊞ ABANDONED CHEVRON WELL LOCATION
- ⊞ FORMER BERKELEY LAND CO. WELL LOCATION
- STM --- STORM DRAIN LINE
- SAN --- SANITARY SEWER LINE
- (1,200) TPHg CONCENTRATIONS ARE IN MICROGRAMS PER LITER (µg/L)
- 100- TPHg CONCENTRATION CONTOUR DASHED WHERE INFERRED
- \* DATA FROM PSI SAMPLING EVENT ON MARCH 2, 2011
- (NS) NOT SAMPLED


figure 3

TPHg GROUNDWATER ISOCONCENTRATION MAP - MARCH 14, 2011  
 FORMER CHEVRON STATION 9-3864  
 5101 TELEGRAPH AVENUE  
 Oakland, California






SOURCE: GETTLER-RYAN INC.



HISTORICAL GROUNDWATER FLOW DIRECTION



**LEGEND**

- CHEVRON MONITORING WELL LOCATION
- CHEVRON EXPLORATORY BORING LOCATION
- ⊕ AUTOPRO WELL LOCATION
- ⊠ AUTOPRO EXPLORATORY BORING LOCATION
- ⊡ AUTOPRO TRENCH EXPLORATORY BORING LOCATION
- ⊞ 5239 TELEGRAPH EXPLORATORY BORING LOCATION
- ⊞ FORMER BERKELEY LAND CO. EXPLORATORY BORING LOCATION
- ⊞ ABANDONED CHEVRON WELL LOCATION
- ⊞ FORMER BERKELEY LAND CO. WELL LOCATION
- STM --- STORM DRAIN LINE
- SAN --- SANITARY SEWER LINE
- (1,200) TPHg CONCENTRATIONS ARE IN MICROGRAMS PER LITER (µg/L)
- 100- TPHg CONCENTRATION CONTOUR DASHED WHERE INFERRED
- \* MW-5 WAS KNOWN AS FORMER CHEVRON WELL MW-4. TRANSFERRED TO AUTOPRO AND NAME CHANGED TO MW-5 IN 1998.

figure 4

TPHg GROUNDWATER ISOCONCENTRATION MAP - DECEMBER 11, 1996  
 FORMER CHEVRON STATION 9-3864  
 5101 TELEGRAPH AVENUE  
 Oakland, California



## TABLES

TABLE 1

**SOIL SAMPLE ANALYTICAL RESULTS  
FORMER CHEVRON SERVICE STATION 9-3864  
5101 TELEGRAPH AVENUE  
OAKLAND, CA**

<i>Boring/ Sample ID</i>	<i>Sample Date</i>	<i>Sample Depth (fbg)</i>	<i>TPHd</i>	<i>TPHg</i>	<i>TOG</i>	<i>concentrations in milligrams per kilogram (mg/kg)</i>				
						<i>Benzene</i>	<i>Toluene</i>	<i>Ethylbenzene</i>	<i>Xylenes</i>	<i>HVOCs</i>
<b>Exploratory and Monitoring Well Borings</b>										
C-1	11/14/90	15.5	NA	<b>48</b>	NA	<0.025	<b>0.29</b>	<b>0.28</b>	<b>0.6</b>	NA
C-2	11/14/90	10.5	NA	<1	NA	<0.005	<0.005	<0.005	<0.005	NA
	11/14/90	15.5	NA	<b>25</b>	NA	<b>0.04</b>	<b>0.092</b>	<b>0.18</b>	<b>0.4</b>	NA
C-3	11/15/90	10.5	NA	<1	NA	<b>0.006</b>	<b>0.016</b>	<b>0.006</b>	<b>0.021</b>	NA
	11/15/90	15.5	NA	<b>270</b>	NA	<0.25	<b>0.87</b>	<b>1.5</b>	<b>3.4</b>	NA
C-4	11/15/90	10.5	NA	<1	<50	<0.005	<0.005	<0.005	<0.005	ND
	11/15/90	15.5	NA	<1	<50	<0.005	<0.005	<0.005	<0.005	ND
TC-1	11/30/92	10	NA	<0.3	NA	<0.005	<0.005	<0.005	<0.005	NA
	11/30/92	15	NA	<0.3	NA	<0.005	<0.005	<0.005	<0.005	NA
TC-2	11/30/92	10	NA	<0.3	NA	<0.005	<0.005	<0.005	<0.005	NA
	11/30/92	15	NA	<0.3	NA	<0.005	<0.005	<0.005	<0.005	NA
TC-3	11/30/92	10	NA	<0.3	NA	<0.005	<0.005	<0.005	<0.005	NA
	11/30/92	15	NA	<0.3	NA	<0.005	<0.005	<0.005	<0.005	NA
TC-4	12/1/92	7	NA	<0.3	NA	<0.005	<0.005	<0.005	<0.005	NA
	12/1/92	10	NA	<b>4.4</b>	NA	<0.005	<b>0.019</b>	<b>0.013</b>	<b>0.019</b>	NA
	12/1/92	13	NA	<b>46</b>	NA	<0.05	<b>0.18</b>	<b>0.12</b>	<b>0.07</b>	NA
	12/1/92	16	NA	<b>0.7</b>	NA	<0.005	<0.005	<0.005	<0.005	NA

TABLE 1

**SOIL SAMPLE ANALYTICAL RESULTS  
FORMER CHEVRON SERVICE STATION 9-3864  
5101 TELEGRAPH AVENUE  
OAKLAND, CA**

Boring/ Sample ID	Sample Date	Sample Depth (fbg)	TPHd	TPHg	TOG	Benzene	Toluene	Ethylbenzene	Xylenes	HVOCs
			←———— concentrations in milligrams per kilogram (mg/kg) —————→							
TC-5	12/1/92	10	NA	<0.3	NA	<0.005	<0.005	<0.005	<0.005	NA
	12/1/92	16	NA	<0.3	NA	<0.005	<0.005	<0.005	<0.005	NA
B-1 (MW-1)	9/16/93	6.5	NA	<1	NA	<0.005	<0.005	<0.005	<0.015	NA
	9/16/93	10.8	NA	<1	NA	<0.005	<0.005	<0.005	<0.015	NA
B-2 (MW-2)	9/20/93	6	NA	<1	NA	<0.005	<0.005	<0.005	<0.015	NA
	9/20/93	11.3	NA	<1	NA	<0.005	<0.005	<0.005	<0.015	NA
B-3 (MW-3)	9/16/93	6.3	NA	<1	NA	<0.005	<0.005	<0.005	<0.015	NA
	9/16/93	11.4	NA	<1	NA	<0.005	<0.005	<0.005	<0.015	NA
	9/16/93	14.5	NA	<1	NA	<0.005	<0.005	<0.005	<0.015	NA
	9/16/93	16.3	NA	<b>1</b>	NA	<b>0.007</b>	<b>0.01</b>	<b>0.005</b>	<b>0.017</b>	NA
B-4 (MW-4)	9/15/93	6.3	NA	<1	NA	<0.005	<0.005	<0.005	<0.015	NA
	9/15/93	11.3	NA	<b>300</b>	NA	<0.025	<b>0.53</b>	<b>0.15</b>	<b>1.8</b>	NA
B-5 (MW-5)	9/16/93	6.5	NA	<1	NA	<0.005	<0.005	<0.005	<0.015	NA
	9/16/93	11.5	NA	<1	NA	<0.005	<0.005	<0.005	<0.015	NA
	9/16/93	14.5	NA	<1	NA	<0.005	<0.005	<0.005	<0.015	NA
<b>Gasoline UST Excavation</b>										
#1	9/18/91	13.5	NA	<1	NA	<0.005	<0.005	<0.005	<0.005	NA
#2	9/18/91	13.5	NA	<b>1,300</b>	NA	<0.25	<b>2.3</b>	<b>2.8</b>	<b>7.6</b>	NA
#3	9/18/91	13.5	NA	<b>46</b>	NA	<b>0.1</b>	<b>0.07</b>	<b>0.21</b>	<b>0.18</b>	NA
#4	9/18/91	13.5	NA	<b>160</b>	NA	<0.12	<0.12	<b>1.6</b>	<b>3.2</b>	NA
#5	9/18/91	13.5	NA	<b>64</b>	NA	<b>0.04</b>	<b>0.04</b>	<b>0.13</b>	<b>0.32</b>	NA



TABLE 1

**SOIL SAMPLE ANALYTICAL RESULTS**  
**FORMER CHEVRON SERVICE STATION 9-3864**  
**5101 TELEGRAPH AVENUE**  
**OAKLAND, CA**

Boring/ Sample ID	Sample Date	Sample Depth (fbg)	TPHd	TPHg	TOG	concentrations in milligrams per kilogram (mg/kg)				
						Benzene	Toluene	Ethylbenzene	Xylenes	HVOCs
#6	9/18/91	13.5	NA	190	NA	0.33	0.38	0.81	1.8	NA
#7	9/18/91	10	NA	<1	NA	<0.005	<0.005	<0.005	<0.005	NA
#8	9/18/91	10	NA	<1	NA	<0.005	<0.005	<0.005	<0.005	NA
#9	9/18/91	10	NA	<1	NA	<0.005	<0.005	<0.005	0.007	NA
<b>Dispenser and Product Line Excavation</b>										
#10	9/18/91	2	NA	<1	NA	<0.005	<0.005	<0.005	<0.005	NA
#11	9/18/91	3	NA	<1	NA	0.008	0.009	<0.005	0.01	NA
#12	9/18/91	2	NA	<1	NA	<0.005	<0.005	<0.005	<0.005	NA
#13	9/18/91	2	NA	53	NA	0.9	3.5	1.2	6.9	NA
<b>Used-Oil UST Excavation</b>										
#14	9/18/91	11	<10	<1	<50	<0.005	<0.005	<0.005	<0.005	ND
#15	9/18/91	11.5	<10	<1	<50	<0.005	<0.005	<0.005	<0.005	ND
<b>Gasoline UST Over-Excavation</b>										
#1	9/26/91	15.5	NA	580	NA	<0.12	1.4	1.5	3.9	NA
#3	9/26/91	15.5	NA	71	NA	0.069	0.12	0.22	0.57	NA
#4	9/26/91	15.5	NA	980	NA	<0.12	2.7	2.5	5.5	NA
#5	9/26/91	15.5	NA	330	NA	<0.12	0.81	1	2.7	NA
#6	9/26/91	15.5	NA	460	NA	<0.12	0.92	1.3	3	NA
<b>Product Line Over-Excavation</b>										
#2	9/26/91	5	NA	2	NA	0.069	0.092	0.022	0.18	NA

TABLE 1

**SOIL SAMPLE ANALYTICAL RESULTS**  
**FORMER CHEVRON SERVICE STATION 9-3864**  
**5101 TELEGRAPH AVENUE**  
**OAKLAND, CA**

<i>Boring/ Sample ID</i>	<i>Sample Date</i>	<i>Sample Depth (fbg)</i>	<i>TPHd</i>	<i>TPHg</i>	<i>TOG</i>	<i>Benzene</i>	<i>Toluene</i>	<i>Ethylbenzene</i>	<i>Xylenes</i>	<i>HVOCs</i>
			←————— concentrations in milligrams per kilogram (mg/kg) —————→							
<b>Samples of Excavated Soil Aerated and Used as Backfill</b>										
#7	10/10/91	N/A	NA	<1	NA	<0.005	<0.005	<0.005	<0.005	NA
#8	10/10/91	N/A	NA	<1	NA	<0.005	<0.005	<0.005	<0.005	NA
#9	10/10/91	N/A	NA	<1	NA	<0.005	<0.005	<0.005	<0.005	NA
#10	10/10/91	N/A	NA	<1	NA	<0.005	<0.005	<0.005	<0.005	NA
#11	10/10/91	N/A	NA	<1	NA	<0.005	<0.005	<0.005	<0.005	NA
#12	10/10/91	N/A	NA	<1	NA	<0.005	<0.005	<0.005	<0.005	NA
#13	10/10/91	N/A	NA	<1	NA	<0.005	<0.005	<0.005	<0.005	NA
#14	10/10/91	N/A	NA	<1	NA	<0.005	<0.005	<0.005	<0.005	NA
#15	10/10/91	N/A	NA	<1	NA	<0.005	<0.005	<0.005	<0.005	NA
#16	10/10/91	N/A	NA	<1	NA	<0.005	<0.005	<0.005	<0.005	NA
#17	10/10/91	N/A	NA	<1	NA	<0.005	<0.005	<0.005	<0.005	NA
#18	10/10/91	N/A	NA	<1	NA	<0.005	<0.005	<0.005	<0.005	NA
#19	10/10/91	N/A	NA	<1	NA	<0.005	<0.005	<0.005	<0.005	NA
#20	10/10/91	N/A	NA	<1	NA	<0.005	<0.005	<0.005	<0.005	NA
#21	10/10/91	N/A	NA	<1	NA	<0.005	<0.005	<0.005	<0.005	NA

**Notes/Abbreviations:**

TPHd/TPHg = Total petroleum hydrocarbons as diesel/gasoline

TOG = Total oil and grease

HVOCs = Halogenated volatile organic compounds by EPA Method 8010

fbg = feet below grade

NA = Not analyzed

&lt; = Not detected at or above laboratory reporting limit

ND = Not detected; reporting limits vary

N/A = Not applicable

Note: Shaded samples were collected from soil that was later excavated

TABLE 2

**GROUNDWATER SAMPLE ANALYTICAL RESULTS  
FORMER CHEVRON SERVICE STATION 9-3864  
5101 TELEGRAPH AVENUE  
OAKLAND, CA**

<i>Boring ID</i>	<i>Sample Date</i>	<i>TPHg</i>	<i>Benzene</i>	<i>Toluene</i>	<i>Ethylbenzene</i>	<i>Xylenes</i>
Concentrations reported in micrograms per liter (ug/L)						
TC-1	11/30/92	<50	<0.4	<0.3	<0.3	<0.4
TC-2	11/30/92	<50	<0.4	<0.3	<0.3	<0.4
TC-3	11/30/92	<50	<0.4	<0.3	<0.3	<0.4
TC-4	12/1/92	<b>120,000</b>	<200	<200	<b>500</b>	<b>400</b>
TC-5	12/1/92	<b>2,400</b>	<2	<2	<2	<b>3</b>

**Abbreviations:**

TPHg = Total petroleum hydrocarbons as gasoline

&lt; = Not detected at or above stated laboratory reporting limit

APPENDIX A

SUMMARY OF ENVIRONMENTAL INVESTIGATION AND REMEDIATION

**SUMMARY OF ENVIRONMENTAL INVESTIGATION AND REMEDIATION  
FORMER CHEVRON SERVICE STATION 9-3864  
5101 TELEGRAPH AVENUE, OAKLAND, CALIFORNIA**

***November 1990 Monitoring Well Installations***

GeoStrategies, Inc. (GSI) installed onsite monitoring wells C-1 through C-4. Soil samples collected from the well borings at 10.5 and/or 15.5 feet below grade (fbg) contained up to 270 milligrams per kilogram (mg/kg) total petroleum hydrocarbons as gasoline (TPHg) and 0.04 mg/kg benzene. Details were presented in GSI's January 17, 1991 *Well Installation Report*.

***September 1991 Station Demolition and Underground Storage Tank (UST) Removal***

Blaine Tech Services, Inc. (Blaine Tech) oversaw the removal of three (two 10,000-gallon and one 5,000-gallon) steel gasoline USTs, a 1,000-gallon steel used-oil UST, dispensers, and product piping during station demolition. Soil samples collected beneath the gasoline USTs (13.5 fbg) and from the excavation sidewalls (10 fbg) contained up to 1,300 mg/kg TPHg and 0.33 mg/kg benzene. Soil samples collected at 2 or 3 fbg from the piping trenches contained up to 53 mg/kg TPHg and 0.9 mg/kg benzene. No hydrocarbons were detected in soil samples collected beneath the former used-oil UST.

The gasoline UST excavation was subsequently deepened to 17.5 to 18 fbg and the former piping trench was deepened to 5 fbg. Additional soil samples collected at 15.5 fbg from the sidewalls of the UST excavation contained up to 980 mg/kg TPHg and 0.069 mg/kg benzene. An additional soil sample collected at 5 fbg from the product line trench contained 2 mg/kg TPHg and 0.069 mg/kg benzene. Approximately 600 cubic yards of soil were removed; 300 cubic yards were disposed offsite and 300 were aerated, sampled, and re-used as backfill material. Details were presented in Blaine Tech's October 28, 1991 *Multiple Event Sampling Report*.

***November/December 1992 Subsurface Investigation***

Pacific Environmental Group, Inc. (PEG) advanced exploratory borings TC-1 through TC-5. Boring TC-4 was located adjacent to an upgradient former Shell service station to evaluate this potential offsite source. Soil samples collected at depths of 7 to 16 fbg contained up to 46 mg/kg TPHg, but no benzene. Groundwater samples were also collected from each boring. TPHg was only detected in the samples collected from TC-4 (120,000 micrograms per liter [ $\mu\text{g/L}$ ]) and TC-5 (2,400  $\mu\text{g/L}$ ); no benzene was detected in the samples. Details were presented in PEG's untitled letter report dated December 18, 1992.

***December 1992 Risk Assessment***

Geraghty & Miller, Inc. (G&M) performed a risk assessment. The results indicated no significant threat to human health from residual petroleum hydrocarbons under a residential or commercial land use scenario, thus it was concluded no further remediation was necessary. Details were presented in G&M's December 29, 1992 *Risk-Based Analysis for the Former Chevron Service Station #9-3864*.

***September 1993 Monitoring Well Installations***

RESNA Industries (RESNA) installed offsite wells MW-1 through MW-5 adjacent to previous borings TC-1 through TC-5. Soil samples collected at depths of 6 to 16.3 fbg from the well borings contained up to 300 mg/kg TPHg and 0.007 mg/kg benzene (one sample). A well and

offsite source survey were also conducted. Details were presented in RESNA's October 18, 1993 *Report-Additional Subsurface Investigation*.

***December 1996 and January 1997 Well Destructions***

Gettler-Ryan Inc. (G-R) destroyed wells C-1, C-2, and C-4 to accommodate site redevelopment. Details were presented in G-R's January 14, 1997, and March 7, 1997 *Well Abandonment* reports.

***1999-2004 Oxygen Release Compound® (ORC) Enhanced Oxygenation***

ORC socks were placed in wells C-3 and MW-3 to reduce petroleum hydrocarbon concentrations in groundwater via enhanced biodegradation.

APPENDIX B  
HISTORICAL BORING LOGS

MAJOR DIVISIONS					TYPICAL NAMES
COARSE-GRAINED SOILS MORE THAN HALF IS COARSER THAN NO. 200 SIEVE	GRAVELS MORE THAN HALF COARSE FRACTION IS LARGER THAN NO. 4 SIEVE SIZE	CLEAN GRAVELS WITH LITTLE OR NO FINES	GW		WELL GRADED GRAVELS WITH OR WITHOUT SAND, LITTLE OR NO FINES
			GP		POORLY GRADED GRAVELS WITH OR WITHOUT SAND, LITTLE OR NO FINES
		GRAVELS WITH OVER 15% FINES	GM		SILTY GRAVELS, SILTY GRAVELS WITH SAND
			GC		CLAYEY GRAVELS, CLAYEY GRAVELS WITH SAND
	SANDS MORE THAN HALF COARSE FRACTION IS SMALLER THAN NO. 4 SIEVE SIZE	CLEAN SANDS WITH LITTLE OR NO FINES	SW		WELL GRADED SANDS WITH OR WITHOUT GRAVEL, LITTLE OR NO FINES
			SP		POORLY GRADED SANDS WITH OR WITHOUT GRAVEL, LITTLE OR NO FINES
		SANDS WITH OVER 15% FINES	SM		SILTY SANDS WITH OR WITHOUT GRAVEL
			SC		CLAYEY SANDS WITH OR WITHOUT GRAVEL
FINE-GRAINED SOILS MORE THAN HALF IS FINER THAN NO. 200 SIEVE	SILTS AND CLAYS LIQUID LIMIT 50% OR LESS	ML		INORGANIC SILTS AND VERY FINE SANDS, ROCK FLOUR, SILTS WITH SANDS AND GRAVELS	
		CL		INORGANIC CLAYS OF LOW TO MEDIUM PLASTICITY, CLAYS WITH SANDS AND GRAVELS, LEAN CLAYS	
		OL		ORGANIC SILTS OR CLAYS OF LOW PLASTICITY	
	SILTS AND CLAYS LIQUID LIMIT GREATER THAN 50%	MH		INORGANIC SILTS, MICACEOUS OR DIATOMACEOUS, FINE SANDY OR SILTY SOILS, ELASTIC SILTS	
		CH		INORGANIC CLAYS OF HIGH PLASTICITY, FAT CLAYS	
		OH		ORGANIC SILTS OR CLAYS OF MEDIUM TO HIGH PLASTICITY	
HIGHLY ORGANIC SOILS		PT		PEAT AND OTHER HIGHLY ORGANIC SOILS	

- LL - Liquid Limit (%)
- PI - Plastic Index (%)
- PID - Volatile Vapors in ppm
- MA - Particle Size Analysis
- 2.5 YR 6/2 - Soil Color according to Munsell Soil Color Charts (1975 Edition)
- 5 GY 5/2 - GSA Rock Color Chart

- No Soil Sample Recoverd
- "Undisturbed" Sample
- Bulk or Classification Sample
- First Encountered Ground Water Level
- Piezometric Ground Water Level
- Penetration - Sample drive hammer weight - 140 pounds falling 30 inches. Blows required to drive sampler 1 foot are indicated on the logs



GeoStrategies Inc.

Unified Soil Classification - ASTM D 2488-85  
and Key to Test Data



Field location of boring:  (See Plate 2)	Project No.: 7277	Date: 11/14/90	Boring No:
	Client: Chevron Service Station No. 3864		C-1
	Location: 5101 Telegraph Avenue		Sheet 1
	City: Oakland, California		of 2
	Logged by: RCM	Driller: Bayland	
Casing installation data:			

Drilling method: Hollow Stem Auger	(See Well Construction Detail)
Hole diameter: 8-Inches	Top of Box Elevation: 117.45 Datum: MSL

PID (ppm)	Blows/ft. or Pressure (psi)	Type of Sample	Sample Number	Depth (ft.)	Sample	Well Detail	Soil Group Symbol (USCS)	Description
				0				
				1				PAVEMENT SECTION - 1.0 feet.
				2				
				3				
				4				
0	500	S&H push	C-1-5.0	5				SILT (ML) - very dark gray (10YR 3/1), damp, medium stiff, low plasticity; 75% silt; 10% clay; 10% sand; 5% fine gravel; rootholes; organic matter.
				6				
				7				
				8				
				9				
0	11	S&H	C-1-10.5	10				SAND (SW) - brownish yellow (10YR 6/6), damp, medium dense; 85% sand; 10% fine gravel; 5% silt; Fe-oxide staining.
	13			11				
				12				
				13				
				14				
808	11	S&H	C-1-15.5	15				CLAYEY GRAVEL with SAND (GC) - dark greenish gray (5GY 4/1), saturated, medium dense; 65% gravel; 20% sand; 15% clay.
	15			16				
				17				
				18				
				19				

Remarks:


Field location of boring:  (See Plate 2)	Project No.: 7277	Date: 11/14/90	Boring No:
	Client: Chevron Service Station No. 3864	C-1	
	Location: 5101 Telegraph Avenue	Sheet 2	
	City: Oakland, California	of 2	
	Logged by: RCM	Driller: Bayland	

Drilling method: Hollow Stem Auger	Top of Box Elevation:	Datum:
Hole diameter: 8-Inches	Water Level	
	Time	
	Date	

PTD (ppm)	Blows/ft. or Pressure (psi)	Type of Sample	Sample Number	Depth (ft.)	Sample	Well Detail	Soil Group Symbol (USCS)	Description	
	7								
14.2	8	S&H	C-1-	20				CLAYEY SAND (SC) - light olive brown (2.5Y 6/6), saturated, medium dense; 75% sand; 15% clay; 10% gravel.	
	6		20.5	21				CLAYEY SILT (ML/CL) - yellowish brown (10YR 5/6), saturated, stiff; 65% silt; 25% clay; 10% fine sand.	
				22					
				23					
				24					
42.8	7			25				SAND with CLAY (SW-SC) - dark yellowish brown (10YR 4/4), saturated, medium dense; 85% coarse sand; 10% clay; 5% gravel.	
	10	S&H	C-1-	26					
	19		25.5	27					
				28					
				29					
19.0	4			30				SANDY CLAY (CL) - dark yellowish brown (10YR 4/6), damp, very stiff, medium plasticity; 70% clay; 25% sand; 5% silt.	
	7	S&H	C-1-	31					
	12		30.5	32					
				33					
	7			34				COLOR CHANGE to strong brown (7.5YR 4/6), hard; increasing sand to 30% at 33.5 feet.	
	16	SPT		35					
	29			36				Bottom of sample at 34.5 feet.	
				37				Bottom of boring at 34.5 feet.	
				38				11/14/90	
				39					

Remarks:

# WELL CONSTRUCTION DETAIL



- A Total Depth of Boring 34.5 ft.
- B Diameter of Boring 8 in.  
Drilling Method Hollow Stem Auger
- C Top of Box Elevation 117.45 ft.  
 Referenced to Mean Sea Level  
 Referenced to Project Datum
- D Casing Length 30 ft.  
Material Schedule 40 PVC
- E Casing Diameter 2 in.
- F Depth to Top Perforations 10 ft.
- G Perforated Length 19.5 ft.  
Perforated Interval from 10 to 29.5 ft.  
Perforation Type Factory Slotted  
Perforation Size 0.020 in.
- H Surface Seal from 0 to 1.5 ft.  
Seal Material Concrete
- I Backfill from 1.5 to 6 ft.  
Backfill Material Concrete
- J Seal from 6 to 8 ft.  
Seal Material Bentonite Pellets
- K Gravel Pack from 8 to 30 ft.  
Pack Material Lonestar #2/12 Sand
- L Bottom Seal 4.5 ft.  
Seal Material Bentonite Pellets
- M Vault box with locking cap, lock and cover.

Note: Depths measured from initial ground surface.



GeoStrategies Inc.

Well Construction Detail

WELL NO.

**C-1**

JOB NUMBER  
7277

REVIEWED BY RG/CEG  
DHP

DATE  
11/90

REVISED DATE

REVISED DATE

Field location of boring:  (See Plate 2)	Project No.: 7277	Date: 11/14/90	Boring No:
	Client: Chevron Service Station No. 3864	C-2	
	Location: 5101 Telegraph Avenue		
	City: Oakland, California	Sheet 1	
	Logged by: RCM	Driller: Bayland	of 2

Drilling method: Hollow Stem Auger	(See Well Construction Detail)
Hole diameter: 8-Inches	Top of Box Elevation: 116.16 Datum: MSL

PID (ppm)	Blows/ft. or Pressure (psi)	Type of Sample	Sample Number	Depth (ft.)	Sample	Well Detail	Soil Group Symbol (USCS)	Description
				0				
				1				PAVEMENT SECTION - 1.0 feet.
				2				CLAYEY SILT (ML/CL) - very dark gray (10YR 3/1), moist, medium stiff, medium plasticity; 60% silt; 40% clay.
				3				
				4				
0	200	S&H	C-2-	5				Increasing sand to 10%; gravel to 5%; organic matter at 5.5 feet.
	200	push	5.5					
				6				
				7				
				8				
				9				
0	3	S&H	C-2-	10				CLAYEY SAND (SC) - dark yellowish brown (10YR 4/4), moist, medium dense; 70% sand; 20% clay; 10% gravel
	4		10.5					COLOR CHANGE to olive (5Y 4/4); increasing silt to 5% at 10.5 feet.
				11				
				12				
				13				
				14				
914	6	S&H	C-2-	15				GRAVEL with CLAY and SAND (GW-GC) - greenish gray (5G 5/1), saturated; medium dense; 65% gravel; 25% sand; 10% clay; strong chemical odor.
	8		15.5					
	11			16				
				17				
				18				
				19				

Remarks:


Field location of boring:  (See Plate 2)	Project No.: 7277	Date: 11/14/90	Boring No:
	Client: Chevron Service Station No. 3864		C-2
	Location: 5101 Telegraph Avenue		
	City: Oakland, California		Sheet 2
	Logged by: RCM	Driller: Bayland	of 2
Casing installation data:			

Drilling method: Hollow Stem Auger	Top of Box Elevation:	Datum:
Hole diameter: 8-Inches		

FD (ppm)	Blows/ft. or Pressure (ps)	Type of Sample	Sample Number	Depth (ft.)	Sample	Well Detail	Soil Group Symbol (USCS)	Water Level				Description	
	6												
86.5	14	S&H	C-2-	20								GRAVEL with SAND (GW) - olive (5Y 4/4), saturated, dense; 60% gravel; 35% sand; 5% silt; Fe-oxide staining.	
	17		20.5	21									
				22									
				23									
				24									
	0			25									
	0	S&H		25									Very loose at 25.5 feet.
	1			26									
				27									
				28									
				29									
5.0	14		C-2-	30								SAND with CLAY and GRAVEL (SW-SC) - dark yellowish brown (10YR 4/4), saturated, medium dense; 55% sand; 35% gravel; 10% clay.	
	11	S&H	30.0	30								SANDY CLAY (CL) - brownish yellow (10YR 6/6), damp, very stiff, medium plasticity; 65% clay; 35% sand.	
	12			31									
				32									
				33									
				34								Bottom of sample at 30.5 feet. Bottom of boring at 30.5 feet. 11/14/90	
				35									
				36									
				37									
				38									
				39									

Remarks:

# WELL CONSTRUCTION DETAIL



- A Total Depth of Boring \_\_\_\_\_ 30.5 ft.
- B Diameter of Boring \_\_\_\_\_ 8 in.  
Drilling Method \_\_\_\_\_ Hollow Stem Auger
- C Top of Box Elevation \_\_\_\_\_ 116.16 ft.  
 Referenced to Mean Sea Level  
 Referenced to Project Datum
- D Casing Length \_\_\_\_\_ 30 ft.  
Material \_\_\_\_\_ Schedule 40 PVC
- E Casing Diameter \_\_\_\_\_ 2 in.
- F Depth to Top Perforations \_\_\_\_\_ 10 ft.
- G Perforated Length \_\_\_\_\_ 19.5 ft.  
Perforated Interval from \_\_\_\_\_ 10 to \_\_\_\_\_ 29.5 ft.  
Perforation Type \_\_\_\_\_ Factory Slotted  
Perforation Size \_\_\_\_\_ 0.020 in.
- H Surface Seal from \_\_\_\_\_ 0 to \_\_\_\_\_ 1.5 ft.  
Seal Material \_\_\_\_\_ Concrete
- I Backfill from \_\_\_\_\_ 1.5 to \_\_\_\_\_ 6 ft.  
Backfill Material \_\_\_\_\_ Concrete
- J Seal from \_\_\_\_\_ 6 to \_\_\_\_\_ 8 ft.  
Seal Material \_\_\_\_\_ Bentonite Pellets
- K Gravel Pack from \_\_\_\_\_ 8 to \_\_\_\_\_ 30 ft.  
Pack Material \_\_\_\_\_ Lonestar #2/12 Sand
- L Bottom Seal \_\_\_\_\_ 0.5 ft.  
Seal Material \_\_\_\_\_ Bentonite Pellets
- M \_\_\_\_\_ Vault box with locking cap, lock and cover.

Note: Depths measured from initial ground surface.



GeoStrategies Inc.

Well Construction Detail

WELL NO.

C-2

JOB NUMBER  
7277

REVIEWED BY RG/CEG  
DHR

DATE  
11/90

REVISED DATE

REVISED DATE

Field location of boring:  (See Plate 2)	Project No.: 7277	Date: 11/15/90	Boring No:
	Client: Chevron Service Station No. 3864		C-3
	Location: 5101 Telegraph Avenue		Sheet 1
	City: Oakland, California		of 2
	Logged by: RCM	Driller: Bayland	

Drilling method: Hollow Stem Auger	(See Well Construction Detail)
Hole diameter: 8-Inches	Top of Box Elevation: 115.70 Datum: MSL

PID (ppm)	Blows/ft. or Pressure (psf)	Type of Sample	Sample Number	Depth (ft.)	Sample	Well Detail	Soil Group Symbol (USCS)	Water Level		Time		Date		Description
								15.5'	17.1'	10:05	15:30	11/15/90	11/15/90	
				0										
				1										PAVEMENT SECTION - 1.0 feet.
				2										CLAYEY SILT (ML/CL) - very dark brown (10YR 2/2), damp, medium plasticity; 60% silt; 35% clay; 5% fine sand.
				3										
0	500	S&H push	C-3-4.5	4										
				5										Medium stiff, damp; organic matter at 4.5 feet.
				6										
				7										
				8										
				9										
0	7 15 17	S&H	C-3-10.5	10										SAND with SILT (SW-SM) - dark yellowish brown (10YR 3/4), damp, dense; 85% sand; 10% silt; 5% fine gravel; organic matter; Fe-oxide staining.
				11										
				12										
				13										
				14										
890	7 14 16	S&H	C-3-15.5	15										CLAYEY SAND with GRAVEL (SC) - dark greenish gray (5GY 4/1), saturated, dense; 65% sand; 20% clay; 15% fine gravel.
				16										
995	8 13 16	SPT		16										
				17										
				18										
				19										

Remarks:

Field location of boring:  (See Plate 2)	Project No.: 7277	Date: 11/15/90	Boring No:
	Client: Chevron Service Station No. 3864		C-3
	Location: 5101 Telegraph Avenue		
	City: Oakland, California		Sheet 2
	Logged by: RCM	Driller: Bayland	of 2
Casing installation data:			


Drilling method: Hollow Stem Auger	Top of Box Elevation:	Datum:
Hole diameter: 8-Inches		

PID (ppm)	Blows/ft. or Pressure (psf)	Type of Sample	Sample Number	Depth (ft.)	Sample	Well Detail	Soil Group Symbol (USCS)	Water Level			Description
								Time			
	2										
32.8	5	S&H	C-3-20.5	20							SILTY SAND (SM) - yellowish brown (10YR 5/4), saturated, medium dense; 65% sand; 30% silt; 5% fine gravel; gray green staining to 20.0 feet.
	10			21							CLAYEY GRAVEL with SAND (GC) - dark yellowish brown (10YR 3/4), saturated, medium dense; 55% gravel; 25% sand; 20% clay.
				22							
				23							
				24							
24.1	8										
	15	S&H	C-3-25.5	25							Dense at 25.5 feet.
	18			26							
				27							
				28							
				29							CLAYEY SAND (SC) - brownish yellow (10YR 6/6), damp, dense; 70% sand; 30% clay.
9.0	8										
	15	S&H	C-3-30.5	30							SANDY CLAY (CL) - brownish yellow (10YR 6/6), damp, hard; 65% clay; 30% sand; 5% silt.
	18			31							
				32							Bottom of sample at 30.5 feet.
				33							Bottom of boring at 30.5 feet.
				34							11/15/90
				35							
				36							
				37							
				38							
				39							

Remarks:



# WELL CONSTRUCTION DETAIL



- A Total Depth of Boring \_\_\_\_\_ 30.5 ft.
- B Diameter of Boring \_\_\_\_\_ 8 in.  
Drilling Method \_\_\_\_\_ Hollow Stem Auger
- C Top of Box Elevation \_\_\_\_\_ 115.70 ft.  
 Referenced to Mean Sea Level  
 Referenced to Project Datum
- D Casing Length \_\_\_\_\_ 30 ft.  
Material \_\_\_\_\_ Schedule 40 PVC
- E Casing Diameter \_\_\_\_\_ 2 in.
- F Depth to Top Perforations \_\_\_\_\_ 10 ft.
- G Perforated Length \_\_\_\_\_ 19.5 ft.  
Perforated Interval from \_\_\_\_\_ 10 to \_\_\_\_\_ 29.5 ft.  
Perforation Type \_\_\_\_\_ Factory Slotted  
Perforation Size \_\_\_\_\_ 0.020 in.
- H Surface Seal from \_\_\_\_\_ 0 to \_\_\_\_\_ 1.5 ft.  
Seal Material \_\_\_\_\_ Concrete
- I Backfill from \_\_\_\_\_ 1.5 to \_\_\_\_\_ 6 ft.  
Backfill Material \_\_\_\_\_ Concrete
- J Seal from \_\_\_\_\_ 6 to \_\_\_\_\_ 8 ft.  
Seal Material \_\_\_\_\_ Bentonite Pellets
- K Gravel Pack from \_\_\_\_\_ 8 to \_\_\_\_\_ 30 ft.  
Pack Material \_\_\_\_\_ Lonestar #2/12 Sand
- L Bottom Seal \_\_\_\_\_ 0.5 ft.  
Seal Material \_\_\_\_\_ Bentonite Pellets
- M \_\_\_\_\_ Vault box with locking cap, lock and cover.

Note: Depths measured from initial ground surface.



GeoStrategies Inc.

Well Construction Detail

WELL NO.

**C-3**

JOB NUMBER  
7277

REVIEWED BY RG/CEG  
DHP

DATE  
11/90

REVISED DATE

REVISED DATE

Field location of boring: (See Plate 2)

Project No.: 7277 Date: 11/15/90 Boring No: C-4

Client: Chevron Service Station No. 3864

Location: 5101 Telegraph Avenue

City: Oakland, California Sheet 1 of 2

Logged by: RCM Driller: Bayland

Casing installation data: (See Well Construction Detail)

Drilling method: Hollow Stem Auger

Hole diameter: 8-Inches

Top of Box Elevation: 116.10 Datum: MSL

PID (ppm)	Blows/ft or Pressure (psf)	Type of Sample	Sample Number	Depth (ft.)	Sample	Well Detail	Soil Group Symbol (USCS)	Description
				0				
				1				PAVEMENT SECTION - 1.0 feet.
				2				CLAYEY SILT (ML/CL) - very dark grayish brown (10YR 3/2), damp, medium plasticity; 65% silt; 35% clay; trace fine gravel.
				3				
				4				
0	300 500 500	S&H push	C-4 5.5	5				Medium stiff; organic matter; Fe-oxide staining at 5.5 feet.
				6				
				7				
				8				
				9				
0	6 6 13	S&H	C-4 10.5	10				CLAYEY SAND with GRAVEL (SC) - yellowish brown (10YR 5/4), damp, medium dense; 60% sand; 25% clay; 15% gravel; Fe-oxide staining.
				11				
				12				
				13				
				14				
0	8 17 19 15	S&H	C-4 15.5	15				Increasing gravel to 25%; dense at 15.5 feet.
				16				
0	16 18	S&H	C-4 17.0	17				Saturated at 16.5 feet.
				18				
				19				

Remarks:


Field location of boring:  (See Plate 2)	Project No.: 7277	Date: 11/15/90	Boring No:
	Client: Chevron Service Station No. 3864	C-4	
	Location: 5101 Telegraph Avenue	Sheet 2	
	City: Oakland, California	of 2	
Logged by: RCM		Driller: Bayland	
Casing installation data:			

Drilling method: Hollow Stem Auger	Top of Box Elevation:	Datum:
Hole diameter: 8-Inches		

PID (ppm)	Blows/ft. or Pressure (psf)	Type of Sample	Sample Number	Depth (ft.)	Sample	Well Detail	Soil Group Symbol (USCS)	Water Level				Description	
								Time	Date				
	3												
0	7	S&H	C-4	20									SILTY SAND (SM) - yellowish brown (10YR 5/4), saturated, medium dense; 65% sand; 35% silt; slight gray green discoloration.
	12		20.5	21									
				22									
				23									
				24									Increasing gravel to 25% at 24.5 feet.
	7												
0	18	S&H	C-4	25									SAND (SW) - pale yellow (2.5Y 7/6), saturated, dense; 95% sand; 5% silt.
	29		25.5	26									
				27									
				28									
				29									
	4												
0	13	S&H	C-4	30									CLAY with SAND (CL) - light gray (5Y 7/1), damp, very stiff, medium to high plasticity; 70% clay; 20% sand; 10% silt.
	11		30.5	31									
				32									
				33									
				34									
	7												
0	8	S&H	C-4	35									Increasing sand to 30% at 35.5 feet.
	8		35.5	36									
				37									Bottom of sample at 35.5 feet.
				38									Bottom of boring at 35.5 feet.
				39									11/15/90

Remarks:

# WELL CONSTRUCTION DETAIL



- A Total Depth of Boring 35.5 ft.
- B Diameter of Boring 8 in.  
Drilling Method Hollow Stem Auger
- C Top of Box Elevation 116.10 ft.  
 Referenced to Mean Sea Level  
 Referenced to Project Datum
- D Casing Length 30 ft.  
Material Schedule 40 PVC
- E Casing Diameter 2 in.
- F Depth to Top Perforations 10 ft.
- G Perforated Length 19.5 ft.  
Perforated Interval from 10 to 29.5 ft.  
Perforation Type Factory Slotted  
Perforation Size 0.020 in.
- H Surface Seal from 0 to 1.5 ft.  
Seal Material Concrete
- I Backfill from 1.5 to 6 ft.  
Backfill Material Concrete
- J Seal from 6 to 8 ft.  
Seal Material Bentonite Pellets
- K Gravel Pack from 8 to 30 ft.  
Pack Material Lonestar #2/12 Sand
- L Bottom Seal 5.5 ft.  
Seal Material Bentonite Pellets
- M Vault box with locking cap, lock and cover.

Note: Depths measured from initial ground surface.



GeoStrategies Inc.

Well Construction Detail

WELL NO.

**C-4**

JOB NUMBER  
7277

REVIEWED BY RG/CEG  
DHP

DATE  
11/90

REVISED DATE

REVISED DATE

# WELL LOG KEY TO ABBREVIATIONS

## Drilling Method

HSA - Hollow stem auger  
CFA - Continuous flight auger  
Air - Reverse air circulation

## Gravel Pack

CA - Coarse aquarium sand

## Sampling Method

Cal. Mod. - California modified split-spoon sampler (2" inner diameter) driven 18" by a 140-pound hammer having a 30" drop. Where penetration resistance is designated "P", sampler was instead pushed by drill rig.  
Disturbed - Sample taken from drill-return materials as they surfaced.  
Shelby - Shelby Tube thin-walled sampler (3" diameter), where sampler is pushed by drill-rig.

## Moisture Content

Dry - Dry  
Dp - Damp  
Mst - Moist  
Wt - Wet  
Sat - Saturated

## Sorting

PS - Poorly sorted  
MS - Moderately sorted  
WS - Well sorted

## Plasticity



L - Low  
M - Moderate  
H - High

## H-NU (ppm)

ND - No detection

## Symbols

▽ - First encountered ground water  
▼ - Static ground water level



## Density (Blows/Foot - Cal Mod Sampler)

### Sands and gravels

0 - 5 - Very Loose  
5 - 13 - Loose  
13 - 38 - Medium dense  
38 - 63 - Dense  
over 63 - Very dense

### Silts and Clays

0 - 2 - Very Soft  
2 - 4 - Soft  
4 - 9 - Firm  
9 - 17 - Stiff  
17 - 37 - Very Stiff  
37 - 72 - Hard  
over 72 - Very Hard
















## GRAIN - SIZE SCALE

### GRADE LIMITS

U.S. Standard

### GRADE NAME


inch	sieve size	
12.0		Boulders
3.0	3.0 in.	Cobbles
0.19	No. 4	Gravels
0.08	No. 10	coarse
	No. 40	medium
	No. 200	fine
		Silt
		Clay Size

Primary Divisions		Group Symbol/Graphic		Typical Names
<b>COARSE GRAINED SOILS</b>  more than half is larger than #200 sieve	<b>GRAVELS</b>  half of coarse fraction larger than #4 sieve	<b>CLEAN GRAVELS</b>  (less than 5% fines)	GW 	Well graded gravels, gravel-sand mixtures; little or no fines
			GP 	Poorly graded gravels or gravel-sand mixtures; little or no fines
		<b>GRAVEL WITH FINES</b>	GM 	Silty gravels, gravel-sand-silt mixtures
			GC 	Clayey gravels, gravel-sand-clay mixtures
	<b>SANDS</b>  half of coarse fraction smaller than #4 sieve	<b>CLEAN SANDS</b>  (less than 5% fines)	SW 	Well graded sands, gravelly sands, little or no fines
			SP 	Poorly graded sands or gravelly sands; little or no fines
		<b>SANDS WITH FINES</b>	SM 	Silty sands, sand-silt mixtures
			SC 	Clayey sands, sand-clay mixtures, plastic fines
<b>FINE GRAINED SOILS</b>  more than half is smaller than #200 sieve	<b>SILTS AND CLAYS</b>  liquid limit less than 50%		ML 	Inorganic silts and very fine sand, rock flour, silty or clayey fine sands or clayey silts, with slight plasticity
			CL 	Inorganic clays of low to medium plasticity, gravelly clays, sandy clays, silty clays, lean clays
			OL 	Organic silts and organic silty clays of low plasticity
	<b>SILTS AND CLAYS</b>  liquid limit more than 50%		MH 	Inorganic silts, micaceous or diatomaceous fine sandy or silty soils, elastic silts
			CH 	Inorganic clays of high plasticity, fat clays
			OH 	Organic clays of medium to high plasticity, organic silts
<b>HIGHLY ORGANIC SOILS</b>			Pt 	Peat and other highly organic soils



PACIFIC ENVIRONMENTAL GROUP, INC.

## Unified Soil Classification System




**PACIFIC ENVIRONMENTAL GROUP, INC.**

BORING NO. TC-1  
PAGE 1 OF 1

PROJECT NO. 325-17.01  
 LOGGED BY: AW  
 DRILLER: PRECISION  
 DRILLING METHOD: HYDRAULIC  
 SAMPLING METHOD: CONTINUOUS  
 CASING TYPE: NA  
 SLOT SIZE: NA  
 GRAVEL PACK: NA

CLIENT: CHEVRON  
 DATE DRILLED: 11-30-92  
 LOCATION: Telegraph-Oakland  
 HOLE DIAMETER: 2.5"  
 HOLE DEPTH: 19'  
 WELL DIAMETER: NA  
 WELL DEPTH: NA  
 CASING STICKUP: NA

WELL COMPLETION	MOISTURE CONTENT	PID	PENETRATION (BLOWS/FT)	DEPTH (FEET)	RECOVERY SAMPLE INTERVAL	GRAPHIC	SOIL TYPE	LITHOLOGY / REMARKS
Back Filled With Grout				1		[Hatched pattern]		ASPHALT ROAD BASE TO APPROXIMATELY 3'
				2		[Hatched pattern]		
				3		[Diagonal lines]	SC	CLAYEY SAND: medium brown; 30-40% fines; very fine sand; no product odor; very little recovery in 5-7' sample.
				4		[Diagonal lines]		
				5		[Diagonal lines]		
		Mst		6		[Diagonal lines]		
				7		[Diagonal lines]		
				8		[Diagonal lines]		
				9		[Diagonal lines]		
		Mst		10		[Diagonal lines]		@10': very little recovery; chert.
				11		[Diagonal lines]		
		Mst		12		[Diagonal lines]	CL	SANDY CLAY: medium brown with gray mottling; low plasticity; 10-15% very fine to fine sand; iron oxide staining; small rootholes; no product odor.
				13		[Diagonal lines]	ML	SANDY SILT: blue gray; low plasticity; 10-20% very fine sand; brown mottling; shell material; sulfur odor; no product odor.
				14		[Diagonal lines]		
		Mst-Wt		15		[Dotted pattern]		LANDSLIDE DEPOSITS: mixture of sand, gravel and clay.
				16		[Dotted pattern]	ML	SILT: light to medium brown; low plasticity; trace very fine to fine sand; mottled light gray to medium brown tan; no product odor.
				17		[Dotted pattern]		
		Wt		18		[Dotted pattern]		
				19		[Dotted pattern]		BOTTOM OF BORING AT 19'



**PACIFIC ENVIRONMENTAL GROUP, INC.**

BORING NO. TC-2  
PAGE 1 OF 1

PROJECT NO. 325-17.01  
 LOGGED BY: AW  
 DRILLER: PRECISION  
 DRILLING METHOD: HYDRAULIC  
 SAMPLING METHOD: CONTINUOUS  
 CASING TYPE: NA  
 SLOT SIZE: NA  
 GRAVEL PACK: NA

CLIENT: CHEVRON  
 DATE DRILLED: 11-30-92  
 LOCATION: Telegraph-Oakland  
 HOLE DIAMETER: 2.5"  
 HOLE DEPTH: 21'  
 WELL DIAMETER: NA  
 WELL DEPTH: NA  
 CASING STICKUP: NA

WELL COMPLETION	MOISTURE CONTENT	PID	PENETRATION (BLOWS/FT)	DEPTH (FEET)	RECOVERY SAMPLE INTERVAL	GRAPHIC	SOIL TYPE	LITHOLOGY / REMARKS
Back Filled With Grout				1				ASPHALT ROADBASE
				2			CL	CLAY: gray black.
				3			SM	SILTY SAND: no recovery 3-8.5'.
				4				
				5				
				6				
				7				
				8				
				9				@8.5': very dark brown; 20-30% fines; dual classification sandy silt; high moisture content; very soft; no product odor.
		Mst-Wt		10				
				11			CL	CLAY: medium to light gray; low plasticity; iron oxide mottling; trace-10% very fine to fine sand; dense; no product odor.
		Mst		12				
				13				
		Mst		14				
				15				
		Mst		16				
				17				
		Mst		18				
				19				@19': increase in medium to coarse sand.
		Mst-Wt		20			GM	SILTY GRAVEL: medium to light brown; 20-30% fines; 10-20% very fine to fine sand; angular coarse sand and gravel.
				21				
				22				BOTTOM OF BORING AT 21'





LOCATION MAP



NORTHING EASTING ELEVATION

PACIFIC ENVIRONMENTAL GROUP, INC.

BORING NO. TC-4  
PAGE 1 OF 1


PROJECT NO. 325-17.01  
 LOGGED BY: AW  
 DRILLER: PRECISION  
 DRILLING METHOD: HYDRAULIC  
 SAMPLING METHOD: CONTINUOUS  
 CASING TYPE: NA  
 SLOT SIZE: NA  
 GRAVEL PACK: NA

CLIENT: CHEVRON  
 DATE DRILLED: 12-1-92  
 LOCATION: Telegraph-Oakland  
 HOLE DIAMETER: 2.5"  
 HOLE DEPTH: 22'  
 WELL DIAMETER: NA  
 WELL DEPTH: NA  
 CASING STICKUP: NA

WELL COMPLETION	MOISTURE CONTENT	PI D	PENETRATION (BLOWS/FT)	DEPTH (FEET)	RECOVERY SAMPLE INTERVAL	GRAPHIC	SOIL TYPE	LITHOLOGY / REMARKS
Back Filled With Grout				1				CONCRETE ROADBASE
				2				
		Dp	280				CL	CLAY: very dark brownish black; low plasticity; 10-20% fine to medium sand; trace to coarse sand; iron oxide staining; faint to medium product odor.
				3				
				4				
				5				
				6				
		Dp	134					@7': faint to moderate product odor.
				7				
				8				
		Dp	88.8				GC	CLAYEY GRAVEL: medium dark grayish brown; angular coarse sand and fine gravel; subrounded to well rounded clasts; blue gray staining; moderate to strong product odor.
				9				
				10				
				11				
		Mst	180					@13': strong product odor.
				12				
				13				
		Wt	389					@16': discolored; strong product odor.
				14				
				15				
		Wt	22.3					@19': no to faint product odor.
				16				
			17					
			18					
			19					
			20				ML SILT: sandy; light to medium brown; low plasticity; 20-30% fine sand; trace gravel at 20'; no product odor.	
			21					
			22					

BOTTOM OF BORING AT 22'

LOCATION MAP



NORTHING EASTING ELEVATION

PACIFIC ENVIRONMENTAL GROUP, INC.




BORING NO. TC-5  
PAGE 1 OF 1

PROJECT NO. 325-17.01  
 LOGGED BY: AW  
 DRILLER: PRECISION  
 DRILLING METHOD: HYDRAULIC  
 SAMPLING METHOD: CONTINUOUS  
 CASING TYPE: NA  
 SLOT SIZE: NA  
 GRAVEL PACK: NA

CLIENT: CHEVRON  
 DATE DRILLED: 12-1-92  
 LOCATION: Telegraph-Oakland  
 HOLE DIAMETER: 2.5"  
 HOLE DEPTH: 22'  
 WELL DIAMETER: NA  
 WELL DEPTH: NA  
 CASING STICKUP: NA


WELL COMPLETION	MOISTURE CONTENT	PID	PENETRATION (BLOWS/FT)	DEPTH (FEET)	RECOVERY SAMPLE INTERVAL	GRAPHIC	SOIL TYPE	LITHOLOGY / REMARKS
Back Filled With Grout				1				CONCRETE
				2				ROADBASE
				3			CL	CLAY: dark brown; low plasticity; 10-20% very fine to fine sand; roots; organics; no product odor.
				4				
				5			ML	SILT: medium; dark brown; low plasticity; 20-30% very fine to fines and; no product odor.
		Dp	261	6				
				7				
				8				
				9				
		Dp	99	10				@10': increase in fine sand; no product odor.
				11				
				12				
				13				
				14				
				15				
				16				@16': little recovery; no product odor.
		Mst	110	17				
		Wt	142	18			GC	CLAYEY GRAVEL: medium brownish gray; 20-40% fines; subrounded to angular gravels; iron oxide staining; saturated; faint to no product odor.
				19				
				20				
				21				
				22				

BOTTOM OF BORING AT 22'



**GRAPHIC LOG**

**DESCRIPTION**



continues

EXPLANATION	
	Recovered drill sample
	Sample sealed for chemical analysis
	Sieve sample
	Grab sample
	Core sample
est K	Estimated permeability (hydraulic conductivity) 1K = primary 2K = secondary
NR	No recovery
	Water level during drilling
	Water level in completed well
CONTACTS:	
	Solid where certain
	Dotted where approximate
	Dashed where uncertain
	Hatched where gradational

Logged by:	Erich Neupert
Project Mgr:	Justin Power
Dates Drilled:	9/16/93
Drilling Company:	Kvilhaug
Drilling Method:	8" Hollow Stem Auger
Driller:	Paul Santos
Well Head Completion:	Christy box & locking cap
Type of Sampler:	1 1/2" & 2 1/2" split spoon
TD (Total Depth):	26.5 feet




**BORING LOG—Boring B-1 (Monitoring Well MW-1)**  
 Former Chevron Service Station No. 9-3864  
 5101 Telegraph Avenue  
 Oakland, California

**BORING  
 B-1**

PROJECT NO. 17075.01

10/93



EXPLANATION		CONTACTS:	
	Recovered drill sample	—	Solid where certain
	Sample sealed for chemical analysis	.....	Dotted where approximate
	Sieve sample	- - -	Dashed where uncertain
	Grab sample	////	Hachured where gradational
	Core sample		
est K	Estimated permeability (hydraulic conductivity)		
NR	No recovery		
1K = primary 2K = secondary			
W	Water level during drilling		
W	Water level in completed well		






**BORING LOG—Boring B-1 (Monitoring Well MW-1)**  
 Former Chevron Service Station No. 9-3864  
 5101 Telegraph Avenue  
 Oakland, California

**BORING**  
**B-1**


PROJECT NO. 17075.01

10/93



**GRAPHIC LOG**

**DESCRIPTION**



continues

**EXPLANATION**

- Recovered drill sample      est K      Estimated permeability (hydraulic conductivity) 1K = primary 2K = secondary
- Sample sealed for chemical analysis
- Sieve sample      NR      No recovery
- Grab sample      ∇      Water level during drilling
- Core sample      □      Water level in completed well

**CONTACTS:**

- Solid where certain
- Dotted where approximate
- Dashed where uncertain
- Hachured where gradational

Logged by: Erich Neupert  
 Project Mgr: Justin Power  
 Dates Drilled: 9/20/93

Drilling Company: Kvilhaug  
 Drilling Method: 8" Hollow Stem Auger  
 Driller: Paul Santos

Well Head Completion: Christy box & locking cap  
 Type of Sampler: 1 1/2" & 2 1/2" split spoon  
 TD (Total Depth): 26.5 feet




**BORING LOG—Boring B-2 (Monitoring Well MW-2)**  
 Former Chevron Service Station No. 9-3864  
 5101 Telegraph Avenue  
 Oakland, California

**BORING  
 B-2**

PROJECT NO. 17075.01

10/93



EXPLANATION	
	Recovered drill sample
	Sample sealed for chemical analysis
	Sieve sample
	Grab sample
	Core sample
est K	Estimated permeability (hydraulic conductivity)
NR	No recovery
▼	Water level during drilling
▽	Water level in completed well
CONTACTS:	
—	Solid where certain
.....	Dotted where approximate
- - -	Dashed where uncertain
////	Hachured where gradational







PROJECT NO. 17075.01

10/93

**BORING LOG—Boring B-2 (Monitoring Well MW-2)**  
 Former Chevron Service Station No. 9-3864  
 5101 Telegraph Avenue  
 Oakland, California

BORING  
**B-2**



continues

EXPLANATION		CONTACTS:	
	Recovered drill sample	—	Solid where certain
	Sample sealed for chemical analysis	.....	Dotted where approximate
	Sieve sample	- - -	Dashed where uncertain
	Grab sample	////	Hachured where gradational
	Core sample		
est K	Estimated permeability (hydraulic conductivity)		
NR	No recovery		
	Water level during drilling		
	Water level in completed well		
1K = primary	2K = secondary		

Logged by:	Erich Neupert
Project Mgr:	Justin Power
Dates Drilled:	9/16/93
Drilling Company:	Kvilhaug
Drilling Method:	8" Hollow Stem Auger
Driller:	Paul Santos
Well Head Completion:	Christy box & locking cap
Type of Sampler:	2 1/2" split spoon
TD (Total Depth):	28.0 feet



**BORING LOG—Boring B-3 (Monitoring Well MW-3)**  
 Former Chevron Service Station No. 9-3864  
 5101 Telegraph Avenue  
 Oakland, California

**BORING  
 B-3**

PROJECT NO. 17075.01


10/93




2/12 sand  
 2" sch 40  
 PVC casing  
 with .01" slots

Measured Depth (feet)  
 Blow Counts  
 PID (ppmv)

GRAPHIC LOG DESCRIPTION



9-21-93 09:25  
 9-16-93 16:00  
 9-16-93 15:45



Gravelly CLAY (CL); same as above  
 Gravelly SILT (ML); brown; moist; stiff to very stiff  
 Gravelly SILT (ML); gray; moist  
 Gravelly SILT (ML); same as above; with fine- to coarse-grained gravel; stiff to very stiff  
 Silty GRAVEL (GM), fine- to medium-grained; gray; wet; medium dense to dense  
 Silty GRAVEL (GM); gray; wet; medium dense; odor  
 SILT (ML); brown; wet  
 SILT (ML); same as above; soft to stiff

continues

EXPLANATION		CONTACTS:	
	Recovered drill sample	—	Solid where certain
	Sample sealed for chemical analysis	.....	Dotted where approximate
	Sieve sample	- - -	Dashed where uncertain
	Grab sample	////	Hachured where gradational
	Core sample		
est K	Estimated permeability [hydraulic conductivity]		
1K = primary 2K = secondary			
NR	No recovery		
	Water level during drilling		
	Water level in completed well		




BORING LOG—Boring B-3 (Monitoring Well MW-3)  
 Former Chevron Service Station No. 9-3864  
 5101 Telegraph Avenue  
 Oakland, California


BORING  
**B-3**

PROJECT NO. 17075.01

10/93




Inch Radius 0 2 4 6



GRAPHIC LOG

DESCRIPTION



SILT (ML); brown; wet; soft to stiff  
 SILT (ML) with trace fine-grained gravel; brown; damp  
 TD @ 28.0 ft.

EXPLANATION

- Recovered drill sample
- Sample sealed for chemical analysis
- Sieve sample
- Grab sample
- Core sample
- est K Estimated permeability (hydraulic conductivity)  
1K = primary 2K = secondary
- NR No recovery
- Water level during drilling
- Water level in completed well

CONTACTS:

- Solid where certain
- Dotted where approximate
- Dashed where uncertain
- Hachured where gradational





**BORING LOG—Boring B-3 (Monitoring Well MW-3)**  
 Former Chevron Service Station No. 9-3864  
 5101 Telegraph Avenue  
 Oakland, California

BORING  
**B-3**



PROJECT NO. 17075.01

10/93



**GRAPHIC LOG**

**DESCRIPTION**



∇ 9-21-93  
09:33

continues

Logged by:	Erich Neupert
Project Mgr:	Justin Power
Dates Drilled:	9/15/93
Drilling Company:	Kvilhaug
Drilling Method:	8" Hollow Stem Auger
Driller:	Paul Santos
Well Head Completion:	Christy box & locking cap
Type of Sampler:	1 1/2" & 2 1/2" split spoon
TD (Total Depth):	23.0 feet

EXPLANATION		CONTACTS:
	Recovered drill sample	— Solid where certain
	Sample sealed for chemical analysis	..... Dotted where approximate
	Sieve sample	- - - Dashed where uncertain
	Grab sample	////// Hachured where gradation
	Core sample	
est K	Estimated permeability (hydraulic conductivity) 1K = primary 2K = secondary	
NR	No recovery	
∇	Water level during drilling	
∇	Water level in completed well	




**BORING LOG—Boring B-4 (Monitoring Well MW-4)**  
Former Chevron Service Station No. 9-3864  
5101 Telegraph Avenue  
Oakland, California




**BORING  
B-4**

PROJECT NO. 17075.01

10/93



9-15-93  
 14:13  
 9-15-93  
 14:00



EXPLANATION		
	est: K	Estimated permeability (hydraulic conductivity)
	1K = primary 2K = secondary	
	NR	No recovery
	▼	Water level during drilling
	▽	Water level in completed well
CONTACTS:		
	Solid where certain	
	Dotted where approximate	
	Dashed where uncertain	
	Hachured where gradational	






**BORING LOG—Boring B-4 (Monitoring Well MW-4)**  
 Former Chevron Service Station No. 9-3864  
 5101 Telegraph Avenue  
 Oakland, California

BORING  
**B-4**


PROJECT NO. 17075.01

10/93



**GRAPHIC LOG**

**DESCRIPTION**



continues

EXPLANATION		CONTACTS:	
	est K	Estimated permeability (hydraulic conductivity)	— Solid where certain
		1K = primary 2K = secondary	..... Dotted where approximate
	NR	No recovery	- - - Dashed where uncertain
		Water level during drilling	////// Hachured where gradational
		Water level in completed well	

Logged by:	Erich Neupert
Project Mgr:	Justin Power
Dates Drilled:	9/16/93
Drilling Company:	Kvilhaug
Drilling Method:	8" Hollow Stem Auger
Driller:	Paul Santos
Well Head Completion:	Christy box & lacking cap
Type of Sampler:	1 1/2" & 2 1/2" split spoon
TD (Total Depth):	22.0 feet





**BORING LOG—Boring B-5 (Monitoring Well MW-5)**  
 Former Chevron Service Station No. 9-3864  
 5101 Telegraph Avenue  
 Oakland, California

**BORING  
 B-5**

PROJECT NO. 17075.01

10/93



- ▼ 9-16-93 11:15
- ▼ 9-16-93 8:45
- ▼ 9-16-93 8:35


Measured Depth (Feet)  
 12  
 13  
 14  
 15  
 16  
 17  
 18  
 19  
 20  
 21  
 22  
 23  
 24  
 25  
 26

Blow Counts  
 3  
 4  
 16  
 20  
 20  
 25

PID (ppmv)  
 0.6  
 453

GRAPHIC LOG

DESCRIPTION



SILT (ML) with trace fine-grained gravel and fine-grained sand; brown; wet; soft to stiff

Clayey GRAVEL with sand (GC); gray; wet; dense; odor

Clayey GRAVEL with sand (GC); same as above; loose to dense; no odor

TD @ 22.0 ft.

EXPLANATION

- Recovered drill sample
- Sample sealed for chemical analysis
- Sieve sample
- Grab sample
- Core sample
- est K Estimated permeability (hydraulic conductivity)  
1K = primary 2K = secondary
- NR No recovery
- Water level during drilling
- Water level in completed well

CONTACTS:

- Solid where certain
- Dotted where approximate
- Dashed where uncertain
- Hachured where gradational



PROJECT NO. 17075.01

10/93

BORING LOG—Boring B-5 (Monitoring Well MW-5)  
 Former Chevron Service Station No. 9-3864  
 5101 Telegraph Avenue  
 Oakland, California

BORING

**B-5**


APPENDIX C

WELL SURVEY INFORMATION AND TEMESCAL CREEK MAP

**WELL SURVEY RESULTS  
FORMER CHEVRON STATION 9-3864  
5101 TELEGRAPH AVENUE  
OAKLAND, CALIFORNIA**

<i>Well No./ Figure ID</i>	<i>Well Owner</i>	<i>Well Address Street</i>	<i>City</i>	<i>Total Well Depth (ft)</i>	<i>Date Installed</i>	<i>Distance/Direction from Site (ft) (approx)</i>	<i>Well Use</i>
1	Children's Hospital	747 52nd Street 49th Street and	Oakland	125	1/20/1992	1,500 W	Irrigation
2	Pacific Gas & Electric	Webster 49th Street and	Oakland	120	2/19/1976	1,150 SE	Cathodic Protection
3	EBMUD	Webster 49th Street and	Oakland	13	12/1/1997	1,150 SE	Cathodic Protection
4	EBMUD	Webster	Oakland	53	5/1/1975	1,150 SE	Cathodic Protection
5	EBMUD	Webster	Oakland	53	5/1/1975	1,150 SE	Cathodic Protection
6	Angela Delucchi	5629 Vincente Street	Oakland	75	Unknown	1,900 NE	Domestic
7	Marshall Steel Co.	5427 Telegraph	Oakland	40	Unknown	750 N	Industrial





SOURCE: TOPO! MAPS.


WELL SURVEY MAP  
 FORMER CHEVRON SERVICE STATION 9-3864  
 5101 TELEGRAPH AVENUE  
*Oakland, California*



LEGEND

- APPROXIMATE WELL LOCATION








APPENDIX D  
PREVIOUS SITE PLANS

# TANK REMOVAL DIAGRAM


September 18, 1991 / 910918-C-1

## DIAGRAM ONE



MAP REF: THOMAS BROS  
ALAMEDA COUNTY  
P.4 C-6

LEGEND: F = FILL PIPE END



SAMPLING PERFORMED BY GLEN BENNETT  
DIAGRAM PREPARED BY LI PAN

	13.5 ft	15.5 ft
1	ND	580
2	1300	
3		71
4		980
5	64	330
6	190	460


# TANK REMOVAL DIAGRAM

September 18, 1991 / 910918-C-1

# DIAGRAM TWO



MAP REF: THOMAS BROS.  
ALAMEDA COUNTY  
P.4 C-6





SAMPLING PERFORMED BY GLEN BENNETT  
DIAGRAM PREPARED BY LI PAN

# ADDITIONAL EXCAVATION DIAGRAM

September 26, 1991 / 910926-C-1



MAP REF: THOMAS BROS.  
ALAMEDA COUNTY  
P.4 C-6



SAMPLING PERFORMED BY GLEN BENNETT  
DIAGRAM PREPARED BY LI PAN

APPENDIX E

FIRST SEMI-ANNUAL 2011 GROUNDWATER MONITORING REPORT




# GETTLER-RYAN Inc.



## TRANSMITTAL

May 4, 2011  
G-R #386358

TO: Mr. James Kiernan  
Conestoga-Rovers & Associates  
10969 Trade Center Drive, Suite 107  
Rancho Cordova, CA 95670

FROM: Deanna L. Harding   
Project Coordinator  
Gettler-Ryan Inc.  
6747 Sierra Court, Suite J  
Dublin, California 94568

RE: **Former Chevron Service Station  
#9-3864 (MTI)  
5101 Telegraph Avenue  
Oakland, California  
RO 0000351**

WE HAVE ENCLOSED THE FOLLOWING:

COPIES	DATED	DESCRIPTION
1	April 29, 2011	Groundwater Monitoring and Sampling Report First Semi-Annual Event of March 14, 2011

### COMMENTS:

Pursuant to your request, we are providing you with copies of the above referenced report for **your use and distribution to the following (including PDF submittal of the entire report to GeoTracker):**

Enclosures



## WELL CONDITION STATUS SHEET

Client/Facility #: Chevron #9-3864  
 Site Address: 5101 Telegraph Avenue  
 City: Oakland, CA

Job # 386358  
 Event Date: 3-14-11  
 Sampler: Joe

WELL ID	Vault Frame Condition	Gasket/O-Ring (M)missing	BOLTS (M) Missing (R) Replaced	Bolt Flanges B= Broken S= Stripped R=Retap	APRON Condition C=Cracked B=Broken G=Gone	Grout Seal (Deficient) inches from TOC	Casing (Condition prevents tight cap seal)	REPLACE LOCK Y/N	REPLACE CAP Y/N	WELL VAULT Manufacture/Size/ # of Bolts	Pictures Taken Yes / No
C-3	O.K	O.K	1-S	O.K	O.K	O.K	O.K	N	N	12" EMCO/2	No
MW-1	↓	↓	1-S	↓	↓	↓	↓	↓	↓	8" EMCO/2	↓
MW-2	↓	↓	1-S	↓	↓	↓	↓	↓	↓	8" EMCO/2	↓
MW-3	↓	↓	3-S	↓	↓	↓	↓	↓	↓	8" Boact-L. /3	↓
MW-5	↓	↓	O.K	↓	↓	↓	↓	↓	↓	8" EMCO/2	↓

Comments Installed gasket - mw-3



# GETTLER-RYAN Inc.

April 29, 2011  
G-R Job #386358

Ms. Stacie H. Frerichs  
Chevron Environmental Management Company  
6111 Bollinger Canyon Road, Room 3596  
San Ramon, CA 94583

**RE: First Semi-Annual Event of March 14, 2011**  
Groundwater Monitoring & Sampling Report  
Former Chevron Service Station #9-3864  
5101 Telegraph Avenue  
Oakland, California

Dear Ms. Frerichs:

This report documents the most recent groundwater monitoring and sampling event performed by Gettler-Ryan Inc. (G-R) at the referenced site. All field work was conducted in accordance with G-R Standard Operating Procedure - Groundwater Sampling (attached). A joint groundwater monitoring and sampling event was conducted on a different date with the former Autopro, located at 5200 Telegraph Avenue, Oakland, California, however data was not received.

Static groundwater levels were measured and the wells were checked for the presence of separate-phase hydrocarbons. Static water level data, groundwater elevations, and separate-phase hydrocarbon thickness (if any) are presented in the attached Table 1. A Potentiometric Map is included as Figure 1.


Groundwater samples were collected from the monitoring wells and submitted to a state certified laboratory for analyses. The field data sheets for this event are attached. Analytical results are presented in the table(s) listed below. The chain of custody document and laboratory analytical report are also attached. All groundwater and decontamination water generated during sampling activities was removed from the site, per the Standard Operating Procedure.

Please call if you have any questions or comments regarding this report. Thank you.

Sincerely,

Deanna L. Harding  
Project Coordinator

Douglas J. Lee  
Senior Geologist, P.G. No. 6882





- Figure 1: Potentiometric Map
- Table 1: Groundwater Monitoring Data and Analytical Results
- Table 2: Dissolved Oxygen Concentrations
- Table 3: Groundwater Analytical Results - Oxygenate Compounds
- Attachments: Standard Operating Procedure - Groundwater Sampling  
Field Data Sheets  
Chain of Custody Document and Laboratory Analytical Reports

**EXPLANATION**

- ◆ Groundwater monitoring well
- ◆ Groundwater monitoring well, Tri-Star Partnership (Former Chevron Well)
- ✖ Abandoned well
- \* Discontinued from monitoring/sampling program

99.99 Groundwater elevation in feet referenced to Mean Sea Level

--99.99-- Groundwater elevation contour, dashed where inferred



Source: Figure modified from drawing provided by RRM engineering contracting firm.

**GETTLER - RYAN INC.**  
 6747 Sierra Court, Suite J  
 Dublin, CA 94568 (925) 551-7555

**POTENTIOMETRIC MAP**  
 Former Chevron Service Station #9-3864  
 5101 Telegraph Avenue  
 Oakland, California

FIGURE  
**1**

PROJECT NUMBER  
**386358**

REVIEWED BY

DATE  
 March 14, 2011

REVISED DATE

**Table 1**  
**Groundwater Monitoring Data and Analytical Results**  
Former Chevron Service Station #9-3864  
5101 Telegraph Avenue  
Oakland, California

WELL ID/ DATE	TOC (ft.)	GWE (msl)	DTW (ft.)	TPH-GRO (µg/L)	B (µg/L)	T (µg/L)	E (µg/L)	X (µg/L)	MTBE (µg/L)
<b>C-3</b>									
12/06/90	115.70	98.84	16.86	210	2.0	<0.5	<0.5	1.0	--
12/06/90 (D)	--	--	--	220	2.0	0.6	<0.5	2.0	--
06/06/91	115.70	100.01	15.69	6,400	310	21	16	21	--
09/16/92	115.70	99.81	15.89	7,100	130	26	12	30	--
12/04/91	115.70	100.32	15.38	5,100	120	18	17	20	--
06/02/92	115.70	100.30	15.40	6,700	140	44	17	37	--
12/21/92	115.70	101.79	13.91	13,000	390	360	100	410	--
03/11/93	115.70	101.95	13.75	5,100	86	20	12	23	--
06/11/93	115.70	101.03	14.67	7,200	91	38	19	38	--
09/13/93	115.70	100.17	15.53	6,800	100	52	41	75	--
12/14/93	115.70	101.30	14.40	8,600	74	23	18	36	--
03/16/94	115.70	101.44	14.26	6,000	100	42	27	30	--
06/17/94	115.70	100.60	15.10	15,000	170	120	120	270	--
08/29/94	115.70	100.30	15.40	26,000	51	<0.5	58	107	--
12/06/94	115.70	101.90	13.80	34,000	88	140	98	390	--
03/31/95	115.70	102.91	12.79	2,800	42	<5.0	<5.0	6.6	--
06/24/95	115.70	100.84	14.86	5,200	34	<10	<10	13	--
09/12/95	115.70	100.76	14.94	7,000	45	<10	28	42	--
12/29/95	115.70	102.12	13.58	5,100	20	<10	<10	19	<50
02/29/96	115.70	102.88	12.82	2,600	15	<5.0	17	16	<25
06/26/96	115.70	101.32	14.38	4,400	<10	<10	<10	<10	<50
09/12/96	115.70	100.75	14.95	5,800	73	22	18	17	61
12/11/96	115.70	103.08	12.62	8,800	81	<20	<20	37	200
03/31/97	115.70	100.70	15.00	8,100	38	62	30	42	38
06/29/97	115.70	100.08	15.62	5,800	<10	<10	<10	67	<50
09/30/97	115.70	100.70	15.00	6,200	<10	28	21	27	130
12/12/97	115.70	103.68	12.02	330	1.6	1.1	<1.0	3.4	<5.0
02/19/98	115.70	103.26	12.44	110	1.7	<0.5	<0.5	0.51	<2.5
06/16/98	115.70	102.29	13.41	7,400	63	16	<10	<10	170
08/31/98	115.70	101.70	14.00	4,400	6.4	<2.5	5.4	16	15
12/23/98	115.70	102.91	12.79	11,000	83	37	69	76	86
03/09/99	115.70	102.70	13.00	6,500	45	38	17	30	110
06/23/99 <sup>1</sup>	115.70	101.92	13.78	--	--	--	--	--	--
09/30/99	115.70	99.70	16.00	3,870	29.7	8.72	7.08	7.75	<50
02/29/00	115.70	102.14	13.56	2,660	22.5	<5.0	11.2	11.6	<50

**Table 1**  
**Groundwater Monitoring Data and Analytical Results**  
Former Chevron Service Station #9-3864  
5101 Telegraph Avenue  
Oakland, California

WELL ID/ DATE	TOC (ft.)	GWE (msl)	DTW (ft.)	TPH-GRO (µg/L)	B (µg/L)	T (µg/L)	E (µg/L)	X (µg/L)	MTBE (µg/L)
<b>C-3 (cont)</b>									
09/18/00 <sup>3</sup>	115.70	103.25	12.45	740 <sup>4</sup>	6.0	4.5	<2.5	6.0	<13
03/21/01 <sup>3</sup>	115.70	102.05	13.65	1,700 <sup>4</sup>	21	12	14	19	59
09/04/01 <sup>3</sup>	115.70	101.09	14.61	4,100	<10	4.8	6.5	14	<5.0/<2 <sup>5</sup>
03/22/02 <sup>3,6</sup>	115.70	102.49	13.21	3,600	<5.0	<5.0	6.1	<15	<2.5
09/16/02 <sup>3</sup>	115.70	100.39	15.31	4,000	<10	<5.0	4.3	<10	7.9
03/28/03 <sup>3</sup>	115.70	101.38	14.32	2,400	<2.5	<2.5	5.5	<7.5	<13
09/02/03 <sup>3,7</sup>	115.70	101.33	14.37	2,800	1	0.9	0.9	4	<0.5
03/18/04 <sup>7,8</sup>	115.70	101.56	14.14	5,300	<0.5	<0.5	<0.5	<0.5	<0.5
09/15/04 <sup>7</sup>	115.70	101.50	14.20	3,200	0.8	0.8	1	3	10
03/11/05 <sup>7</sup>	115.70	102.79	12.91	4,200	0.6	0.5	1	3	<0.5
09/29/05 <sup>7</sup>	115.70	101.13	14.57	4,900	0.6	0.5	2	3	<0.5
03/24/06	115.70	INACCESSIBLE - VEHICLE PARKED OVER WELL			--	--	--	--	--
09/12/06 <sup>7</sup>	115.70	101.29	14.41	5,900	<1	<1	<1	2	<1
03/05/07 <sup>7</sup>	115.70	102.81	12.89	4,600	<0.5	<0.5	0.8	2	<0.5
09/21/07 <sup>7</sup>	115.70	101.39	14.31	5,000	<0.5	<0.5	0.6	1	<0.5
03/06/08 <sup>7</sup>	115.70	102.15	13.55	3,600	<0.5	<0.5	1	1	<0.5
09/05/08 <sup>7</sup>	115.70	101.00	14.70	2,700	<0.5	<0.5	0.9	1	<0.5
03/30/09 <sup>7</sup>	115.70	102.28	13.42	4,200	<0.5	<0.5	0.8	3	<0.5
09/15/09 <sup>7</sup>	115.70	100.55	15.15	4,700	<0.5	<0.5	<0.5	1	<0.5
03/02/10 <sup>7</sup>	115.70	102.22	13.48	3,600	<0.5	<0.5	<0.5	1	<0.5
09/09/10 <sup>7</sup>	115.70	100.73	14.97	3,800	<0.5	<0.5	<0.5	1	<0.5
03/14/11 <sup>7</sup>	115.70	102.20	13.50	3,400	<0.5	<0.5	0.6	1	<0.5
<b>MW-1</b>									
09/20/93	115.05	102.37	12.68	<50	<0.5	<0.5	<0.5	<1.5	--
12/14/93	115.05	105.01	10.04	<50	<0.5	<0.5	<0.5	<0.5	--
03/16/94	115.05	103.10	11.95	<50	<0.5	1.7	<0.5	2.1	--
06/17/94	115.05	102.51	12.54	350	1.2	3.7	2.0	12	--
08/29/94	115.05	101.98	13.07	<50	<0.5	<0.5	<0.5	<0.5	--
12/06/94	115.05	104.45	10.60	140	0.9	2.8	1.1	4.2	--
03/31/95	115.05	104.74	10.31	<50	<0.5	<0.5	<0.5	<0.5	--
06/24/95	115.05	102.44	12.61	<50	<0.5	<0.5	<0.5	<0.5	--
09/12/95	115.05	102.00	13.05	<50	<0.5	<0.5	<0.5	<0.5	--
02/02/96	115.05	106.19	8.86	<50	<0.5	<0.5	<0.5	<0.5	<2.5

**Table 1**  
**Groundwater Monitoring Data and Analytical Results**  
Former Chevron Service Station #9-3864  
5101 Telegraph Avenue  
Oakland, California

WELL ID/ DATE	TOC (ft.)	GWE (msl)	DTW (ft.)	TPH-GRO (µg/L)	B (µg/L)	T (µg/L)	E (µg/L)	X (µg/L)	MTBE (µg/L)
<b>MW-1 (cont)</b>									
02/29/96	115.05	105.39	9.66	<50	<0.5	<0.5	<0.5	<0.5	<2.5
06/26/96	115.05	102.85	12.20	<50	<0.5	<0.5	<0.5	<0.5	<2.5
09/12/96	115.05	101.55	13.50	<50	<0.5	<0.5	<0.5	<0.5	<2.5
12/11/96	115.05	105.90	9.15	<50	<0.5	<0.5	<0.5	<0.5	<2.5
03/31/97	115.05	102.30	12.75	<50	<0.5	<0.5	<0.5	<0.5	<2.5
06/29/97	115.05	102.01	13.04	<50	<0.5	<0.5	<0.5	<0.5	<2.5
09/30/97	115.05	101.80	13.25	<50	<0.5	<0.5	<0.5	<0.5	<2.5
12/12/97	115.05	106.06	8.99	<50	<0.5	<0.5	<0.5	<0.5	<2.5
02/19/98	115.05	105.64	9.41	<50	<0.5	<0.5	<0.5	<0.5	<2.5
06/16/98	115.02	103.48	11.54	<50	<0.5	<0.5	<0.5	<0.5	2.6
08/31/98	115.02	102.51	12.51	<50	<0.5	<0.5	<0.5	<0.5	<2.5
12/23/98	115.02	103.03	11.99	<50	<0.5	<0.5	<0.5	<0.5	<2.5
03/09/99	115.02	104.57	10.45	<50	<0.5	<0.5	<0.5	<0.5	<2.5
09/30/99	115.02	102.07	12.95	SAMPLED ANNUALLY	--	--	--	--	--
02/29/00	115.02	105.90	9.12	<50	<0.5	0.816	<0.5	<0.5	<5.0
09/18/00	115.02	104.14	10.88	--	--	--	--	--	--
03/21/01	115.02	104.01	11.01	<50	<0.50	<0.50	<0.50	<0.50	<2.5
09/04/01	115.02	103.60	11.42	--	--	--	--	--	--<2 <sup>5</sup>
03/22/02 <sup>6</sup>	115.02	104.68	10.34	100	<0.50	24	0.80	4.9	15
09/16/02	115.02	102.35	12.67	SAMPLED ANNUALLY	--	--	--	--	--
03/28/03	115.02	103.29	11.73	<50	<0.50	<0.50	<0.50	<1.5	<2.5
09/02/03	115.02	102.74	12.28	SAMPLED ANNUALLY	--	--	--	--	--
03/18/04 <sup>7</sup>	115.02	103.11	11.91	<50	<0.5	<0.5	<0.5	<0.5	<0.5
09/15/04	115.02	101.89	13.13	SAMPLED ANNUALLY	--	--	--	--	--
03/11/05 <sup>7</sup>	115.02	104.29	10.73	<50	<0.5	2	<0.5	<0.5	<0.5
09/29/05	115.02	101.97	13.05	SAMPLED ANNUALLY	--	--	--	--	--
03/24/06 <sup>7</sup>	115.02	104.61	10.41	<50	<0.5	<0.5	<0.5	<0.5	<0.5
09/12/06	115.02	101.91	13.11	SAMPLED ANNUALLY	--	--	--	--	--
03/05/07 <sup>7</sup>	115.02	103.93	11.09	<50	<0.5	<0.5	<0.5	<0.5	<0.5
09/21/07	115.02	102.07	12.95	SAMPLED ANNUALLY	--	--	--	--	--
03/06/08 <sup>7</sup>	115.02	102.92	12.10	<50	<0.5	<0.5	<0.5	<0.5	<0.5
09/05/08	115.02	102.54	12.48	SAMPLED ANNUALLY	--	--	--	--	--
03/30/09 <sup>7</sup>	115.02	103.64	11.38	<50	<0.5	<0.5	<0.5	<0.5	<0.5
09/15/09	115.02	102.06	12.96	SAMPLED ANNUALLY	--	--	--	--	--

**Table 1**  
**Groundwater Monitoring Data and Analytical Results**  
Former Chevron Service Station #9-3864  
5101 Telegraph Avenue  
Oakland, California

WELL ID/ DATE	TOC (ft.)	GWE (msl)	DTW (ft.)	TPH-GRO (µg/L)	B (µg/L)	T (µg/L)	E (µg/L)	X (µg/L)	MTBE (µg/L)
<b>MW-1 (cont)</b>									
03/02/10 <sup>7</sup>	115.02	103.27	11.75	<50	<0.5	<0.5	<0.5	<0.5	<0.5
09/09/10	115.02	102.24	12.78	SAMPLED ANNUALLY		--	--	--	--
03/14/11 <sup>7</sup>	115.02	103.37	11.65	<50	<0.5	<0.5	<0.5	<0.5	<0.5
<b>MW-2</b>									
09/20/93	112.08	99.93	12.15	<50	<0.5	<0.5	<0.5	<1.5	--
12/14/93	112.08	97.36	14.72	<50	<0.5	<0.5	<0.5	<0.5	--
03/16/94	112.08	100.92	11.16	<50	<0.5	1.1	<0.5	0.9	--
06/17/94	112.08	100.41	11.67	330	1.4	3.3	1.9	11	--
08/29/94	112.08	100.08	12.00	<50	<0.5	<0.5	<0.5	<0.5	--
12/06/94	112.08	102.57	9.51	<50	<0.5	<0.5	<0.5	<0.5	--
03/31/95	112.08	103.24	8.84	<50	<0.5	<0.5	<0.5	<0.5	--
06/24/95	112.08	100.44	11.64	<50	<0.5	<0.5	<0.5	<0.5	--
09/12/95	112.08	100.00	12.08	<50	<0.5	<0.5	<0.5	<0.5	--
12/29/95	112.08	101.58	10.50	<50	<0.5	<0.5	<0.5	<0.5	<2.5
02/29/96	112.08	104.08	8.00	<50	<0.5	<0.5	<0.5	<0.5	<2.5
06/26/96	112.08	100.58	11.50	<50	<0.5	<0.5	<0.5	<0.5	<2.5
09/12/96	112.08	99.81	12.27	<50	<0.5	<0.5	<0.5	<0.5	<2.5
12/11/96	112.08	104.17	7.91	<50	<0.5	<0.5	<0.5	<0.5	<2.5
03/31/97	112.08	100.20	11.88	<50	<0.5	<0.5	<0.5	<0.5	<2.5
06/29/97	112.08	99.89	12.19	<50	<0.5	<0.5	<0.5	<0.5	<2.5
09/30/97	112.08	99.46	12.62	<50	<0.5	<0.5	<0.5	<0.5	<2.5
12/12/97	112.08	102.85	9.23	<50	<0.5	<0.5	<0.5	<0.5	<2.5
02/19/98	112.08	104.87	7.21	<50	<0.5	<0.5	<0.5	<0.5	<2.5
06/16/98	112.03	101.10	10.93	<50	<0.5	<0.5	<0.5	<0.5	<2.5
08/31/98	112.03	99.69	12.34	<50	<0.5	<0.5	<0.5	<0.5	<2.5
12/23/98	112.03	100.59	11.44	<50	<0.5	<0.5	<0.5	<0.5	<2.5
03/09/99	112.03	103.23	8.80	<50	<0.5	<0.5	<0.5	<0.5	<2.5
09/30/99	112.03	101.22	10.81	SAMPLED ANNUALLY		--	--	--	--
02/29/00	112.03	105.12	6.91	<50	<0.5	<0.5	<0.5	<0.5	<5.0
09/18/00	112.03	101.00	11.03	--	--	--	--	--	--
03/21/01	112.03	101.61	10.42	<50	<0.50	<0.50	<0.50	<0.50	<2.5
09/04/01	112.03	101.04	10.99	--	--	--	--	--	--/ <2 <sup>5</sup>
03/22/02	112.03	102.14	9.89	<50	<0.50	<0.50	<0.50	<1.5	<2.5



**Table 1**  
**Groundwater Monitoring Data and Analytical Results**  
Former Chevron Service Station #9-3864  
5101 Telegraph Avenue  
Oakland, California

WELL ID/ DATE	TOC (ft.)	GWE (msl)	DTW (ft.)	TPH-GRO (µg/L)	B (µg/L)	T (µg/L)	E (µg/L)	X (µg/L)	MTBE (µg/L)
<b>MW-2 (cont)</b>									
09/16/02	112.03	100.02	12.01	SAMPLED ANNUALLY		--	--	--	--
03/28/03	112.03	101.23	10.80	<50	<0.50	<0.50	<0.50	<1.5	<2.5
09/02/03	112.03	100.15	11.88	SAMPLED ANNUALLY		--	--	--	--
03/18/04 <sup>7</sup>	112.03	101.04	10.99	<50	<0.5	<0.5	<0.5	<0.5	<0.5
09/15/04	112.03	99.15	12.88	SAMPLED ANNUALLY		--	--	--	--
03/11/05 <sup>7</sup>	112.03	102.13	9.90	<50	<0.5	<0.5	<0.5	<0.5	<0.5
09/29/05	112.03	99.33	12.70	SAMPLED ANNUALLY		--	--	--	--
03/24/06 <sup>7</sup>	112.03	103.04	8.99	<50	<0.5	<0.5	<0.5	<0.5	<0.5
09/12/06	112.03	98.97	13.06	SAMPLED ANNUALLY		--	--	--	--
03/05/07 <sup>7</sup>	112.03	101.57	10.46	<50	<0.5	<0.5	<0.5	<0.5	<0.5
09/21/07	112.03	99.35	12.68	SAMPLED ANNUALLY		--	--	--	--
03/06/08 <sup>7</sup>	112.03	100.98	11.05	<50	<0.5	<0.5	<0.5	<0.5	<0.5
09/05/08	112.03	99.22	12.81	SAMPLED ANNUALLY		--	--	--	--
03/30/09 <sup>7</sup>	112.03	101.23	10.80	<50	<0.5	<0.5	<0.5	<0.5	<0.5
09/15/09	112.03	98.84	13.19	SAMPLED ANNUALLY		--	--	--	--
03/02/10 <sup>7</sup>	112.03	101.34	10.69	<50	<0.5	<0.5	<0.5	<0.5	<0.5
09/09/10	112.03	99.00	13.03	SAMPLED ANNUALLY		--	--	--	--
03/14/11 <sup>7</sup>	112.03	100.14	11.89	<50	<0.5	<0.5	<0.5	<0.5	<0.5
<b>MW-3</b>									
09/20/93	113.67	97.25	16.42	6,600	400	11	32	23	--
12/14/93	113.67	98.95	14.72	8,400	390	9.4	13	<2.5	--
03/16/94	113.67	98.45	15.22	6,900	260	30	32	27	--
06/17/94	113.67	97.62	16.05	10,000	190	61	58	190	--
08/29/94	113.67	97.44	16.23	7,200	74	9.8	26	24	--
12/06/94	113.67	99.35	14.32	13,000	610	86	88	140	--
03/31/95	113.67	99.98	13.69	4,300	120	<10	12	<10	--
06/24/95	113.67	98.02	15.65	6,200	210	24	29	12	--
09/12/95	113.67	97.68	15.99	7,200	190	<20	<20	<20	--
12/29/95	113.67	99.67	14.00	7,100	200	<10	45	24	<50
02/29/96	113.67	100.91	12.76	1,200	30	<5.0	<5.0	<5.0	<25
06/26/96	113.67	98.44	15.23	7,900	180	<20	35	28	240
09/12/96	113.67	97.73	15.94	11,000	150	<5.0	35	28	170
12/11/96	113.67	99.86	13.81	7,500	75	8.8	30	45	110



**Table 1**  
**Groundwater Monitoring Data and Analytical Results**  
Former Chevron Service Station #9-3864  
5101 Telegraph Avenue  
Oakland, California

WELL ID/ DATE	TOC (ft.)	GWE (msl)	DTW (ft.)	TPH-GRO (µg/L)	B (µg/L)	T (µg/L)	E (µg/L)	X (µg/L)	MTBE (µg/L)
<b>MW-3 (cont)</b>									
03/31/97	113.67	98.23	15.44	8,700	100	<10	20	23	50
06/29/97	113.67	97.99	15.68	9,300	120	28	22	19	150
09/30/97	113.67	97.76	15.91	8,200	78	<10	22	25	96
12/12/97	113.67	100.82	12.85	68	1.8	<0.5	<0.5	<0.5	<2.5
02/19/98	113.67	100.41	13.26	220	5.6	1.5	<0.5	<0.5	6.1
06/16/98	113.63	99.12	14.51	7,500	97	21	21	27	160
08/31/98	113.63	98.62	15.01	7,600	24	<2.5	9.5	16	38
12/23/98	113.63	100.03	13.60	5,800	69	<50	<50	<50	<250
03/09/99	113.63	99.59	14.04	5,300	<10	<10	16	20	88
06/23/99 <sup>1</sup>	113.63	--	--	--	--	--	--	--	--
07/19/99 <sup>1</sup>	113.63	--	--	--	--	--	--	--	--
09/30/99	113.63	96.74	16.89	8,660	53.7	16.9	17	19.6	132
02/29/00	113.63	INACCESSIBLE	--	--	--	--	--	--	--
09/18/00 <sup>3</sup>	113.63	100.41	13.22	2,400 <sup>4</sup>	14	6.8	4.7	7.4	28
03/21/01 <sup>3</sup>	113.63	98.88	14.75	7,600 <sup>4</sup>	41	30	<25	50	160
09/04/01	113.63	INACCESSIBLE - CAR PARKED OVER WELL			--	--	--	--	--
03/22/02 <sup>3</sup>	113.63	99.46	14.17	7,600	<10	4.2	11	<25	<5.0
09/16/02 <sup>3</sup>	113.63	97.34	16.29	5,900	<20	<10	7.7	<15	21
03/28/03 <sup>3</sup>	113.63	98.67	14.96	3,500	<20	3.3	7.3	10	<13
09/02/03 <sup>3,7</sup>	113.63	98.20	15.43	4,500	3	2	2	5	<0.5
03/18/04 <sup>7,8</sup>	113.63	98.91	14.72	5,300	3	1	3	4	<0.5
09/15/04	113.63	INACCESSIBLE - CAR PARKED OVER WELL			--	--	--	--	--
03/11/05 <sup>7</sup>	113.63	99.72	13.91	4,500	2	1	2	4	<0.5
09/29/05 <sup>7</sup>	113.63	98.06	15.57	5,300	3	1	2	4	<0.5
03/24/06 <sup>7</sup>	113.63	100.10	13.53	3,300	1	0.6	1	2	<0.5
09/12/06 <sup>7</sup>	113.63	98.16	15.47	6,100	2	1	2	4	<0.5
03/05/07 <sup>7</sup>	113.63	99.69	13.94	4,000	1	0.6	0.8	2	<0.5
09/21/07 <sup>7</sup>	113.63	98.24	15.39	5,900	2	1	1	4	<0.5
03/06/08 <sup>7</sup>	113.63	99.02	14.61	3,900	2	0.8	2	3	<0.5
09/05/08 <sup>7</sup>	113.63	98.13	15.50	5,100	1	0.7	2	3	<0.5
03/30/09 <sup>7</sup>	113.63	99.13	14.50	4,800	2	0.7	1	3	<0.5
09/15/09	113.63	INACCESSIBLE	--	--	--	--	--	--	--
03/02/10 <sup>7</sup>	113.63	99.41	14.22	<50	<0.5	<0.5	<0.5	<0.5	<0.5
09/09/10 <sup>7</sup>	113.63	98.32	15.31	4,000	1	0.5	0.7	3	<0.5
03/14/11 <sup>7</sup>	113.63	99.46	14.17	1,300	<0.5	<0.5	<0.5	0.6	<0.5

**Table 1**  
**Groundwater Monitoring Data and Analytical Results**  
Former Chevron Service Station #9-3864  
5101 Telegraph Avenue  
Oakland, California

WELL ID/ DATE	TOC (ft.)	GWE (msl)	DTW (ft.)	TPH-GRO (µg/L)	B (µg/L)	T (µg/L)	E (µg/L)	X (µg/L)	MTBE (µg/L)
<b>MW-5</b>									
09/20/93	116.74	101.43	15.31	590	25	1.8	0.6	2.0	--
12/14/93	116.74	102.19	14.55	210	11	6.3	2.3	6.1	--
03/16/94	116.74	101.77	14.97	270	12	16	4.8	17	--
06/17/94	116.74	101.36	15.38	220	24	17	6.7	28	--
08/29/94	116.74	101.54	15.20	1,000	<0.5	<0.5	<0.5	<0.5	--
12/06/94	116.74	102.09	14.65	110	9.2	9.7	2.2	11	--
03/31/95	116.74	103.04	13.70	<50	<0.5	<0.5	<0.5	<0.5	--
06/24/95	116.74	101.95	14.79	<50	<0.5	<0.5	<0.5	<0.5	--
09/12/95	116.74	102.15	14.59	<50	<0.5	<0.5	<0.5	<0.5	--
12/29/95	116.74	101.76	14.98	<50	<0.5	<0.5	<0.5	<0.5	<2.5
02/29/96	116.74	103.07	13.67	<50	<0.5	<0.5	<0.5	<0.5	<2.5
06/26/96	116.74	102.50	14.24	<50	<0.5	<0.5	<0.5	<0.5	<2.5
09/12/96	116.74	102.12	14.62	<50	<0.5	<0.5	<0.5	<0.5	<2.5
12/11/96	116.74	102.93	13.81	<50	<0.5	<0.5	<0.5	<0.5	<2.5
03/31/97	116.74	101.29	15.45	<50	<0.5	<0.5	<0.5	<0.5	<2.5
06/29/97	116.74	102.07	14.67	<50	<0.5	<0.5	<0.5	<0.5	<2.5
09/30/97	116.74	101.89	14.85	<50	<0.5	<0.5	<0.5	<0.5	<2.5
12/12/97	116.74	102.99	13.75	<50	<0.5	<0.5	<0.5	<0.5	<2.5
02/19/98	116.74	103.68	13.06	<50	<0.5	<0.5	<0.5	<0.5	<2.5
06/16/98	116.70	102.35	14.35	<50	<0.5	<0.5	<0.5	<0.5	<2.5
08/31/98	116.70	101.54	15.16	<50	<0.5	<0.5	<0.5	<0.5	<2.5
12/23/98	116.70	102.15	14.55	<50	<0.5	<0.5	<0.5	<0.5	<2.5
03/09/99	116.70	102.63	14.07	<50	<0.5	<0.5	<0.5	<0.5	<2.5
09/30/99	116.70	100.80	15.90	SAMPLED ANNUALLY	--	--	--	--	--
02/29/00	116.70	103.40	13.30	<50	<0.5	<0.5	<0.5	<0.5	<5.0
09/18/00	116.70	101.62	15.08	--	--	--	--	--	--
03/21/01	116.70	102.04	14.66	<50	<0.50	<0.50	<0.50	<0.50	<2.5
09/04/01	116.70	101.26	15.44	--	--	--	--	--	--<2 <sup>5</sup>
03/22/02 <sup>6</sup>	116.70	101.99	14.71	<50	<0.50	<0.50	<0.50	<1.5	<2.5
09/16/02	116.70	101.02	15.68	SAMPLED ANNUALLY	--	--	--	--	--
03/28/03	116.70	101.65	15.05	<50	<0.50	<0.50	<0.50	<1.5	<2.5
09/02/03	116.70	101.34	15.36	SAMPLED ANNUALLY	--	--	--	--	--
03/18/04 <sup>7</sup>	116.70	102.14	14.56	<50	1	0.7	1	3	<0.5
09/15/04	116.70	101.30	15.40	SAMPLED ANNUALLY	--	--	--	--	--
03/11/05 <sup>7</sup>	116.70	102.50	14.20	<50	<0.5	<0.5	<0.5	<0.5	<0.5

**Table 1**  
**Groundwater Monitoring Data and Analytical Results**  
Former Chevron Service Station #9-3864  
5101 Telegraph Avenue  
Oakland, California

WELL ID/ DATE	TOC (ft.)	GWE (msl)	DTW (ft.)	TPH-GRO (µg/L)	B (µg/L)	T (µg/L)	E (µg/L)	X (µg/L)	MTBE (µg/L)
<b>MW-5 (cont)</b>									
09/29/05	116.70	101.23	15.47	SAMPLED ANNUALLY		--	--	--	--
03/24/06 <sup>7</sup>	116.70	102.77	13.93	<50	<0.5	<0.5	<0.5	<0.5	<0.5
09/12/06	116.70	102.03	14.67	SAMPLED ANNUALLY		--	--	--	--
03/05/07 <sup>7</sup>	116.70	102.03	14.67	<50	<0.5	<0.5	<0.5	<0.5	<0.5
09/21/07	116.70	101.10	15.60	SAMPLED ANNUALLY		--	--	--	--
03/06/08 <sup>7</sup>	116.70	102.20	14.50	<50	<0.5	<0.5	<0.5	<0.5	<0.5
09/05/08	116.70	101.24	15.46	SAMPLED ANNUALLY		--	--	--	--
03/30/09 <sup>7</sup>	116.70	101.90	14.80	<50	<0.5	<0.5	<0.5	<0.5	<0.5
09/15/09	116.70	100.83	15.87	SAMPLED ANNUALLY		--	--	--	--
03/02/10 <sup>7</sup>	116.70	102.40	14.30	<50	<0.5	<0.5	<0.5	<0.5	<0.5
09/09/10	116.70	101.00	15.70	SAMPLED ANNUALLY		--	--	--	--
03/14/11 <sup>7</sup>	116.70	102.51	14.19	<50	<0.5	<0.5	<0.5	<0.5	<0.5
<b>C-1</b>									
12/06/90	117.45	102.11	15.34	1,900	17	11	3.0	21	--
06/06/91	117.45	102.83	14.62	3,400	21	15	11	18	--
12/04/91	117.45	102.97	14.48	2,700	22	16	13	23	--
06/02/92	117.45	102.92	14.53	1,900	170	170	13	83	--
09/16/92	117.45	102.52	14.93	810	5.8	5.7	2.0	6.3	--
12/21/92	117.45	103.72	13.73	75	2.4	2.9	1.4	4.7	--
03/11/93	117.45	103.62	13.83	150	2.4	20	3.3	23	--
06/11/93	117.45	103.26	14.19	400	4.3	2.3	1.0	3.5	--
09/13/93	117.45	102.85	14.60	4,100	62	43	34	57	--
12/14/93	117.45	103.67	13.78	3,100	9.5	4.5	1.2	11	--
03/16/94	117.45	103.44	14.01	410	6.3	3.1	1.3	4.5	--
06/17/94	117.45	102.90	14.55	3,700	100	42	30	91	--
08/29/94	117.45	102.96	14.49	2,600	15	<0.5	6.7	9.7	--
12/06/94	117.45	104.04	13.41	510	2.0	2.2	1.7	9.4	--
03/31/95	117.45	105.33	12.12	5,440	9.0	2.3	2.0	3.6	--
06/24/95	117.45	103.45	14.00	260	5.8	1.0	0.94	0.88	--
09/12/95	117.45	103.42	14.03	650	14	1.1	1.6	2.4	--
12/29/95	117.45	104.50	12.95	990	32	6.3	4.0	3.2	46
02/29/96	117.45	105.27	12.18	840	2.5	<1.0	2.6	7.3	<5.0

**Table 1**  
**Groundwater Monitoring Data and Analytical Results**  
Former Chevron Service Station #9-3864  
5101 Telegraph Avenue  
Oakland, California

WELL ID/ DATE	TOC (ft.)	GWE (msl)	DTW (ft.)	TPH-GRO (µg/L)	B (µg/L)	T (µg/L)	E (µg/L)	X (µg/L)	MTBE (µg/L)
<b>C-1</b>									
06/26/96	117.45	103.72	13.73	290	3.6	0.73	1.0	1.1	9.9
09/12/96	117.45	103.32	14.13	1,200	17	1.8	4.0	4.4	24
12/11/96	117.45	104.66	12.79	7,700	<10	53	19	44	87
ABANDONED									
<b>C-2</b>									
12/06/90	116.16	100.82	15.34	210	140	9.0	2.0	11	--
06/06/91	116.16	101.54	14.62	4,800	340	23	19	23	--
12/04/91	116.16	100.73	15.43	3,900	85	15	9.1	15	--
06/02/92	116.16	101.74	14.42	3,300	76	9.2	14	15	--
09/16/92	116.16	101.35	14.81	3,000	16	15	3.4	7.5	--
12/21/92	116.16	102.79	13.37	2,200	21	12	7.1	15	--
03/11/93	116.16	102.69	13.47	2,200	33	24	12	25	--
06/11/93	116.16	102.18	13.98	2,600	21	25	11	26	--
09/13/93	116.16	101.61	14.55	2,100	31	25	18	39	--
12/14/93	116.16	102.46	13.70	3,800	<2.5	24	12	20	--
03/16/94	116.16	102.51	13.65	2,600	12	15	10	17	--
06/17/94	116.16	102.87	13.29	2,400	17	19	28	71	--
08/29/94	116.16	111.60	4.56	3,000	29	15	20	4.2	--
12/06/94	116.16	102.98	13.18	1,900	7.9	30	14	31	--
03/31/95	116.16	104.10	12.06	890	<1.3	<1.3	2.6	<1.3	--
06/24/95	116.16	102.19	13.97	730	4.8	<0.5	5.4	0.96	--
09/12/95	116.16	102.28	13.88	1,600	<2.5	<2.5	5.4	<2.5	--
12/29/95	116.16	103.31	12.85	1,000	9.1	2.7	8.7	2.7	19
02/29/96	116.16	104.09	12.07	850	<2.5	<2.5	8.7	11	<12
06/26/96	116.16	102.50	13.66	2,500	14	<5.0	13	6.3	<25
09/12/96	116.16	102.25	13.91	1,800	26	19	17	31	37
12/11/96	116.16	103.82	12.34	2,800	<5.0	34	14	<5.0	41
ABANDONED									
<b>C-4</b>									
12/06/90	116.10	98.42	17.68	<50	<0.5	<0.5	<0.5	<0.5	--
12/18/90	116.10	--	--	<50	<0.5	<0.5	<0.5	<0.5	--
06/06/91	116.10	99.61	16.49	<50	1.0	1.0	<0.5	0.7	--
12/04/91	116.10	99.28	16.82	70	6.5	9.8	1.7	8.6	--

**Table 1**  
**Groundwater Monitoring Data and Analytical Results**  
Former Chevron Service Station #9-3864  
5101 Telegraph Avenue  
Oakland, California

WELL ID/ DATE	TOC (ft.)	GWE (msl)	DTW (ft.)	TPH-GRO (µg/L)	B (µg/L)	T (µg/L)	E (µg/L)	X (µg/L)	MTBE (µg/L)
<b>C-4 (cont)</b>									
06/02/92	116.10	99.18	16.92	70	3.0	4.4	1.8	9.0	--
09/16/92	116.10	98.39	17.71	<50	1.4	1.8	<0.5	1.1	--
12/21/92	116.10	100.74	15.36	<50	0.6	0.7	<0.5	1.5	--
03/11/93	116.10	100.61	15.49	<50	<0.5	<0.5	<0.5	<1.5	--
06/11/93	116.10	99.83	16.27	52	0.9	3.1	0.7	3.8	--
09/13/93	116.10	98.92	17.18	64	0.9	1.0	<0.5	1.7	--
12/14/93	116.10	101.03	15.07	<50	<0.5	0.8	<0.5	0.7	--
03/16/94	116.10	100.19	15.91	<50	<0.5	1.0	<0.5	0.8	--
06/17/94	116.10	99.46	16.64	230	0.6	2.2	2.2	11	--
08/29/94	116.10	99.05	17.05	<50	<0.5	<0.5	<0.5	<0.5	--
12/06/94	116.10	101.52	14.58	<50	<0.5	<0.5	<0.5	<0.5	--
03/31/95	116.10	102.26	13.84	<50	<0.5	<0.5	<0.5	<0.5	--
06/24/95	116.10	100.05	16.05	<50	<0.5	<0.5	<0.5	<0.5	--
09/12/95	116.10	99.87	16.23	<50	<0.5	<0.5	<0.5	<0.5	--
12/29/95	116.10	101.35	14.75	<50	<0.5	<0.5	<0.5	<0.5	<2.5
02/29/96	116.10	102.40	13.70	<50	<0.5	<0.5	<0.5	<0.5	<2.5
06/26/96	116.10	100.30	15.80	<50	<0.5	<0.5	<0.5	<0.5	<2.5
09/12/96	116.10	99.67	16.43	<50	<0.5	<0.5	<0.5	<0.5	<2.5
12/11/96	116.10	103.18	12.92	<50	<0.5	<0.5	<0.5	<0.5	<2.5
ABANDONED									
<b>MW-4</b>									
09/20/93	118.10	107.17	10.93	5,800	16	4.2	35	48	--
12/14/93	118.10	108.33	9.77	7,100	19	6.5	24	35	--
03/16/94	118.10	107.99	10.11	8,500	83	43	60	70	--
06/17/94	118.10	107.20	10.90	21,000	150	20	140	350	--
08/29/94	118.10	107.28	10.82	10,000	86	71	44	85	--
12/06/94	118.10	108.70	9.40	13,000	68	56	67	110	--
03/31/95	118.10	109.31	8.79	6,700	100	9.4	26	23	--
06/24/95	118.10	107.60	10.50	6,300	<20	<20	<20	24	--
09/12/95	118.10	107.90	10.20	7,100	65	16	<10	21	--
12/29/95	118.10	108.86	9.24	3,300	<10	<10	12	14	720
02/29/96	118.10	111.85	6.25	5,100	<10	37	23	21	85
06/26/96	118.10	107.92	10.18	6,800	<20	<20	<20	<20	<100
09/12/96	118.10	107.53	10.57	13,000	150	<10	38	35	240

**Table 1**  
**Groundwater Monitoring Data and Analytical Results**  
Former Chevron Service Station #9-3864  
5101 Telegraph Avenue  
Oakland, California

WELL ID/ DATE	TOC (ft.)	GWE (msl)	DTW (ft.)	TPH-GRO (µg/L)	B (µg/L)	T (µg/L)	E (µg/L)	X (µg/L)	MTBE (µg/L)
<b>MW-4 (cont)</b>									
12/11/96	118.10	109.39	8.71	26,000	<20	<20	<20	170	<100
03/31/97	118.10	107.18	10.92	12,000	120	74	45	70	240
06/29/97	118.10	106.43	11.67	8,800	24	<10	35	36	62
09/30/97	118.10	107.20	10.90	10,000	<10	<10	37	35	72
12/12/97	118.10	105.16	12.94	4,600	95	41	20	25	91
02/19/98	118.10	110.33	7.77	5,400	87	16	32	31	110
06/16/98 <sup>2</sup>	118.08	107.82	10.26	10,000	<20	<20	35	37	150
NOT MONITORED/SAMPLED									
<b>TRIP BLANK</b>									
12/06/90	--	--	--	<50	<0.5	<0.5	<0.5	<0.5	--
12/18/90	--	--	--	<50	<0.5	<0.5	<0.5	<0.5	--
06/06/91	--	--	--	<50	<0.5	<0.5	<0.5	<0.5	--
12/04/91	--	--	--	<50	<0.5	<0.5	<0.5	<0.5	--
06/02/92	--	--	--	<50	<0.5	<0.5	<0.5	<0.5	--
09/16/92	--	--	--	<50	<0.5	<0.5	<0.5	<0.5	--
12/21/92	--	--	--	<50	<0.5	<0.5	<0.5	<0.5	--
03/11/93	--	--	--	<50	<0.5	<0.5	<0.5	<1.5	--
06/11/93	--	--	--	<50	<0.5	<0.5	<0.5	<1.5	--
09/13/93	--	--	--	<50	<0.5	<0.5	<0.5	<1.5	--
12/14/93	--	--	--	<50	<0.5	<0.5	<0.5	<0.5	--
03/16/94	--	--	--	<50	<0.5	<0.5	<0.5	<0.5	--
06/17/94	--	--	--	<50	<0.5	<0.5	<0.5	<0.5	--
08/29/94	--	--	--	<50	<0.5	<0.5	<0.5	<0.5	--
12/06/94	--	--	--	<50	<0.5	<0.5	<0.5	<0.5	--
03/31/95	--	--	--	<50	<0.5	<0.5	<0.5	<0.5	--
06/24/95	--	--	--	<50	<0.5	<0.5	<0.5	<0.5	--
09/12/95	--	--	--	<50	<0.5	<0.5	<0.5	<0.5	--
12/29/95	--	--	--	<50	<0.5	<0.5	<0.5	<0.5	--
02/29/96	--	--	--	<50	<0.5	<0.5	<0.5	<0.5	<2.5
06/26/96	--	--	--	<50	<0.5	<0.5	<0.5	<0.5	<2.5
09/12/96	--	--	--	<50	<0.5	<0.5	<0.5	<0.5	--
12/11/96	--	--	--	<50	<0.5	<0.5	<0.5	<0.5	<2.5
03/31/97	--	--	--	<50	<0.5	<0.5	<0.5	<0.5	<2.5

**Table 1**  
**Groundwater Monitoring Data and Analytical Results**  
Former Chevron Service Station #9-3864  
5101 Telegraph Avenue  
Oakland, California

WELL ID/ DATE	TOC (fl.)	GWE (msl)	DTW (fl.)	TPH-GRO (µg/L)	B (µg/L)	T (µg/L)	E (µg/L)	X (µg/L)	MTBE (µg/L)
<b>TRIP BLANK (cont)</b>									
06/29/97	--	--	--	<50	<0.5	<0.5	<0.5	<0.5	<2.5
09/30/97	--	--	--	<50	<0.5	<0.5	<0.5	<0.5	<2.5
12/12/97	--	--	--	<50	<0.5	<0.5	<0.5	<0.5	<2.5
02/19/98	--	--	--	<50	<0.5	<0.5	<0.5	<0.5	<2.5
06/16/98	--	--	--	<50	<0.5	<0.5	<0.5	<0.5	<2.5
08/31/98	--	--	--	<50	<0.5	<0.5	<0.5	<0.5	<2.5
12/23/98	--	--	--	<50	<0.5	<0.5	<0.5	<0.5	2.9
03/09/99	--	--	--	<50	<0.5	<0.5	<0.5	<0.5	<2.5
09/30/99	--	--	--	<50	<0.5	<0.5	<0.5	<0.5	<5.0
02/29/00	--	--	--	<50	<0.5	<0.5	<0.5	<0.5	<5.0
09/18/00	--	--	--	<50	<0.50	<0.50	<0.50	<0.50	<2.5
03/21/01	--	--	--	<50	<0.50	<0.50	<0.50	<0.50	<2.5
09/04/01	--	--	--	<50	<0.50	<0.50	<0.50	<1.5	<2.5
<b>QA</b>									
03/22/02	--	--	--	<50	<0.50	<0.50	<0.50	<1.5	<2.5
09/16/02	--	--	--	<50	<0.50	<0.50	<0.50	<1.5	<2.5
03/28/03	--	--	--	<50	<0.50	<0.50	<0.50	<1.5	<2.5
09/02/03 <sup>7</sup>	--	--	--	<50	<0.5	<0.5	<0.5	<0.5	<0.5
03/18/04 <sup>7</sup>	--	--	--	<50	<0.5	<0.5	<0.5	<0.5	<0.5
09/15/04 <sup>7</sup>	--	--	--	<50	<0.5	<0.5	<0.5	<0.5	<0.5
03/11/05 <sup>7</sup>	--	--	--	<50	<0.5	<0.5	<0.5	<0.5	<0.5
09/29/05 <sup>7</sup>	--	--	--	<50	<0.5	<0.5	<0.5	<0.5	<0.5
03/24/06 <sup>7</sup>	--	--	--	<50	<0.5	<0.5	<0.5	<0.5	<0.5
09/12/06 <sup>7</sup>	--	--	--	<50	<0.5	<0.5	<0.5	<0.5	<0.5
03/05/07 <sup>7</sup>	--	--	--	<50	<0.5	<0.5	<0.5	<0.5	<0.5
09/21/07 <sup>7</sup>	--	--	--	<50	<0.5	<0.5	<0.5	<0.5	<0.5
03/06/08 <sup>7</sup>	--	--	--	<50	<0.5	<0.5	<0.5	<0.5	<0.5
09/05/08 <sup>7</sup>	--	--	--	<50	<0.5	<0.5	<0.5	<0.5	<0.5
03/30/09 <sup>7</sup>	--	--	--	<50	<0.5	<0.5	<0.5	<0.5	<0.5
DISCONTINUED									

**Table 1**  
**Groundwater Monitoring Data and Analytical Results**  
Former Chevron Service Station #9-3864  
5101 Telegraph Avenue  
Oakland, California

---

---

**EXPLANATIONS:**

Groundwater monitoring data and laboratory analytical results prior to February 9, 2000, were compiled from reports prepared by Blaine Tech Services, Inc.

TOC = Top of Casing

(ft.) = Feet

GWE = Groundwater Elevation

(msl) = Mean sea level

DTW = Depth to Water

TPH = Total Petroleum Hydrocarbons

GRO = Gasoline Range Organics

B = Benzene

T = Toluene

E = Ethylbenzene

X = Xylenes

MTBE = Methyl Tertiary Butyl Ether

(µg/L) = Micrograms per liter

-- = Not Measured/Not Analyzed

(D) = Duplicate

QA = Quality Assurance/Trip Blank

<sup>1</sup> ORC installed.

<sup>2</sup> Transfer of title to Tri-Star Partnership, Inc. effective July 14, 1998.

<sup>3</sup> ORC in well.

<sup>4</sup> Laboratory report indicates gasoline C6-C12.

<sup>5</sup> MTBE by EPA Method 8260.

<sup>6</sup> Split samples taken by Harding ESE.

<sup>7</sup> BTEX and MTBE by EPA Method 8260.

<sup>8</sup> ORC removed from well.



**Table 2**  
**Dissolved Oxygen Concentrations**  
Former Chevron Service Station #9-3864  
5101 Telegraph Avenue  
Oakland, California

WELL ID	DATE	PRE-PURGE (mg/L)	POST-PURGE (mg/L)
C-3 <sup>1</sup>	09/18/00	3.64	--
	03/21/01	1.00	--
	09/04/01	1.40	--
	03/22/02	1.10	--
	09/16/02	1.20	--
	03/28/03 <sup>2</sup>	--	--
	09/02/03	0.80	--
	03/18/04 <sup>3</sup>	0.56	--
MW-3 <sup>1</sup>	09/18/00	4.01	--
	03/21/01	1.30	--
	09/04/01	INACCESSIBLE - CAR PARKED OVER WELL	
	03/22/02	1.30	--
	09/16/02	1.00	--
	03/28/03 <sup>2</sup>	--	--
	09/02/03	0.90	--
	03/18/04 <sup>3</sup>	1.21	--

**EXPLANATIONS:**

(mg/L) = Milligrams per liter

-- = Not Measured

<sup>1</sup> ORC in well.

<sup>2</sup> Meter inoperable; unable to take Dissolved Oxygen measurements

<sup>3</sup> ORC removed from well.

**Table 3**  
**Groundwater Analytical Results - Oxygenate Compounds**  
Former Chevron Service Station #9-3864  
5101 Telegraph Avenue  
Oakland, California

WELL ID	DATE	TBA (µg/L)	MTBE (µg/L)	DIPE (µg/L)	ETBE (µg/L)	TAME (µg/L)	1,2-DCA (µg/L)	EDB (µg/L)	
C-3	09/04/01	<100	<2	<2	<2	<2	<2	<2	
	09/02/03	--	<0.5	--	--	--	--	--	
	03/18/04	--	<0.5	--	--	--	--	--	
	09/15/04	--	10	--	--	--	--	--	
	03/11/05	--	<0.5	--	--	--	--	--	
	09/29/05	--	<0.5	--	--	--	--	--	
	03/24/06	INACCESSIBLE - CAR PARKED OVER WELL							
	09/12/06	--	<1	--	--	--	--	--	
	03/05/07	--	<0.5	--	--	--	--	--	
	09/21/07	--	<0.5	--	--	--	--	--	
	03/06/08	--	<0.5	--	--	--	--	--	
	09/05/08	--	<0.5	--	--	--	--	--	
	03/30/09	--	<0.5	--	--	--	--	--	
	09/15/09	--	<0.5	--	--	--	--	--	
	03/02/10	--	<0.5	--	--	--	--	--	
	09/09/10	--	<0.5	--	--	--	--	--	
03/14/11	--	<0.5	--	--	--	--	--		
MW-1	09/04/01	<100	<2	<2	<2	<2	<2	<2	
	03/18/04	--	<0.5	--	--	--	--	--	
	09/15/04	SAMPLED ANNUALLY							
	03/11/05	--	<0.5	--	--	--	--	--	
	03/24/06	--	<0.5	--	--	--	--	--	
	03/05/07	--	<0.5	--	--	--	--	--	
	03/06/08	--	<0.5	--	--	--	--	--	
	03/30/09	--	<0.5	--	--	--	--	--	
	03/02/10	--	<0.5	--	--	--	--	--	
	03/14/11	--	<0.5	--	--	--	--	--	
MW-2	09/04/01	<100	<2	<2	<2	<2	<2	<2	
	03/18/04	--	<0.5	--	--	--	--	--	
	09/15/04	SAMPLED ANNUALLY							
	03/11/05	--	<0.5	--	--	--	--	--	
	03/24/06	--	<0.5	--	--	--	--	--	

**Table 3**  
**Groundwater Analytical Results - Oxygenate Compounds**  
Former Chevron Service Station #9-3864  
5101 Telegraph Avenue  
Oakland, California

WELL ID	DATE	TBA (µg/L)	MTBE (µg/L)	DIPE (µg/L)	ETBE (µg/L)	TAME (µg/L)	1,2-DCA (µg/L)	EDB (µg/L)
MW-2 (cont)	03/05/07	--	<0.5	--	--	--	--	--
	03/06/08	--	<0.5	--	--	--	--	--
	03/30/09	--	<0.5	--	--	--	--	--
	03/02/10	--	<0.5	--	--	--	--	--
	03/14/11	--	<0.5	--	--	--	--	--
MW-3	09/02/03	--	<0.5	--	--	--	--	--
	03/18/04	--	<0.5	--	--	--	--	--
	09/15/04	INACCESSIBLE - CAR PARKED OVER WELL			--	--	--	--
	03/11/05	--	<0.5	--	--	--	--	--
	09/29/05	--	<0.5	--	--	--	--	--
	03/24/06	--	<0.5	--	--	--	--	--
	09/12/06	--	<0.5	--	--	--	--	--
	03/05/07	--	<0.5	--	--	--	--	--
	09/21/07	--	<0.5	--	--	--	--	--
	03/06/08	--	<0.5	--	--	--	--	--
	09/05/08	--	<0.5	--	--	--	--	--
	03/30/09	--	<0.5	--	--	--	--	--
	09/15/09	INACCESSIBLE	--	--	--	--	--	--
	03/02/10	--	<0.5	--	--	--	--	--
	09/09/10	--	<0.5	--	--	--	--	--
	03/14/11	--	<0.5	--	--	--	--	--
MW-5	09/04/01	<100	<2	<2	<2	<2	<2	<2
	03/18/04	--	<0.5	--	--	--	--	--
	09/15/04	SAMPLED ANNUALLY			--	--	--	--
	03/11/05	--	<0.5	--	--	--	--	--
	03/24/06	--	<0.5	--	--	--	--	--
	03/05/07	--	<0.5	--	--	--	--	--
	03/06/08	--	<0.5	--	--	--	--	--

**Table 3**  
**Groundwater Analytical Results - Oxygenate Compounds**  
 Former Chevron Service Station #9-3864  
 5101 Telegraph Avenue  
 Oakland, California

WELL ID	DATE	TBA (µg/L)	MTBE (µg/L)	DIPE (µg/L)	ETBE (µg/L)	TAME (µg/L)	1,2-DCA (µg/L)	EDB (µg/L)
MW-5 (com)	03/30/09	--	<0.5	--	--	--	--	--
	03/02/10	--	<0.5	--	--	--	--	--
	03/14/11	--	<0.5	--	--	--	--	--

**Table 3**  
**Groundwater Analytical Results - Oxygenate Compounds**  
Former Chevron Service Station #9-3864  
5101 Telegraph Avenue  
Oakland, California

---

---

**EXPLANATIONS:**

TBA = t-Butyl alcohol  
MTBE = Methyl Tertiary Butyl Ether  
DIPE = di-Isopropyl ether  
ETBE = Ethyl t-butyl ether  
TAME = t-Amyl methyl ether  
1,2-DCA = 1,2-Dichloroethane  
EDB = 1,2-Dibromoethane  
( $\mu\text{g/L}$ ) = Micrograms per liter  
-- = Not Analyzed

**ANALYTICAL METHOD:**

EPA Method 8260 for Oxygenate Compounds

## STANDARD OPERATING PROCEDURE - GROUNDWATER SAMPLING

Gettler-Ryan Inc. (GR) field personnel adhere to the following procedures for the collection and handling of groundwater samples prior to analysis by the analytical laboratory. All work is performed in accordance with the GR Health & Safety Plan and all client-specific programs. The scope of work and type of analysis to be performed is determined prior to commencing field work.

Prior to sampling, the presence or absence of free-phase hydrocarbons is determined using an interface probe. Product thickness, if present, is measured to the nearest 0.01 foot and is noted in the field notes. In addition, all depth to water level measurements are collected with a static water level indicator and are also recorded in the field notes, prior to purging and sampling any wells.

After water levels are collected and prior to sampling, if purging is to occur, each well is purged a minimum of three well casing volumes of water using pre-cleaned pumps (stack, peristaltic or Grundfos), or disposable bailers. Temperature, pH and electrical conductivity are measured a minimum of three times during the purging (additional parameters such as dissolved oxygen, oxidation reduction potential, turbidity may also be measured, depending on specific scope of work.). Purging continues until these parameters stabilize.

Groundwater samples are collected using disposable bailers. The water samples are transferred from the bailer into appropriate containers. Pre-preserved containers, supplied by analytical laboratories, are used. When pre-preserved containers are not available, the laboratory is instructed to preserve the sample as appropriate. Duplicate samples are collected for the laboratory to use in maintaining quality assurance/quality control standards, as directed by the scope of work. The samples are labeled to include the job number, sample identification, collection date and time, analysis, preservation (if any), and the sample collector's initials. The water samples are placed in a cooler, maintained at 4°C for transport to the laboratory. Once collected in the field, all samples are maintained under chain of custody until delivered to the laboratory.

The chain of custody document includes the job number, type of preservation, if any, analysis requested, sample identification, date and time collected, and the sample collector's name. The chain of custody is signed and dated (including time of transfer) by each person who receives or surrenders the samples, beginning with the field personnel and ending with the laboratory personnel.

As requested by Chevron Environmental Management Company, the purge water and decontamination water generated during sampling activities is transported by IWM to Chemical Waste Management located in Kettleman Hills, California.



# GETTLER-RYAN INC.

## WELL MONITORING/SAMPLING FIELD DATA SHEET

Client/Facility#: Chevron #9-3864 Job Number: 386358  
 Site Address: 5101 Telegraph Avenue Event Date: 3-14-11 (inclusive)  
 City: Oakland, CA Sampler: Joe

Well ID: C-3  
 Well Diameter: 2 in.  
 Total Depth: 29.10 ft.  
 Depth to Water: 13.50 ft.  
15.60 xVF 0.17 = 2.65

Date Monitored: 3-14-11

Volume	3/4"= 0.02	1"= 0.04	2"= 0.17	3"= 0.38
Factor (VF)	4"= 0.66	5"= 1.02	6"= 1.50	12"= 5.80

Check if water column is less than 0.50 ft.

Depth to Water w/ 80% Recharge [(Height of Water Column x 0.20) + DTW]: 16.62

Time Started:	_____ (2400 hrs)
Time Completed:	_____ (2400 hrs)
Depth to Product:	_____ ft
Depth to Water:	_____ ft
Hydrocarbon Thickness:	_____ ft
Visual Confirmation/Description:	_____
Skimmer / Absorbant Sock (circle one)	_____
Amt Removed from Skimmer:	_____ gal
Amt Removed from Well:	_____ gal
Water Removed:	_____ gal
Product Transferred to:	_____

**Purge Equipment:**  
 Disposable Bailer \_\_\_\_\_  
 Stainless Steel Bailer \_\_\_\_\_  
 Stack Pump \_\_\_\_\_  
 Suction Pump \_\_\_\_\_  
 Grundfos \_\_\_\_\_  
 Peristaltic Pump \_\_\_\_\_  
 QED Bladder Pump \_\_\_\_\_  
 Other: \_\_\_\_\_

**Sampling Equipment:**  
 Disposable Bailer \_\_\_\_\_  
 Pressure Bailer \_\_\_\_\_  
 Discrete Bailer \_\_\_\_\_  
 Peristaltic Pump \_\_\_\_\_  
 QED Bladder Pump \_\_\_\_\_  
 Other: \_\_\_\_\_

Start Time (purge): 0720 Weather Conditions: Rain  
 Sample Time/Date: 0850 3-14-11 Water Color: clear Odor: PI N moderate  
 Approx. Flow Rate: \_\_\_\_\_ gpm. Sediment Description: none  
 Did well de-water? no If yes, Time: \_\_\_\_\_ Volume: \_\_\_\_\_ gal. DTW @ Sampling: 13.80

Time (2400 hr.)	Volume (gal.)	pH	Conductivity (µmhos/cm - (S))	Temperature (C / F)	D.O. (mg/L)	ORP (mV)
<u>0726</u>	<u>3</u>	<u>7.21</u>	<u>846</u>	<u>17.5</u>	_____	_____
<u>0732</u>	<u>5</u>	<u>7.36</u>	<u>841</u>	<u>17.2</u>	_____	_____
<u>0738</u>	<u>8</u>	<u>7.27</u>	<u>849</u>	<u>17.3</u>	_____	_____

### LABORATORY INFORMATION

SAMPLE ID	(#) CONTAINER	REFRIG.	PRESERV. TYPE	LABORATORY	ANALYSES
<u>C-3</u>	<u>6</u> x voa vial	<u>YES</u>	<u>HCL</u>	<u>LANCASTER</u>	<u>TPH-GRO(8015)/BTEX+MTBE(8260)</u>

COMMENTS: \_\_\_\_\_

Add/Replaced Lock: \_\_\_\_\_ Add/Replaced Plug: \_\_\_\_\_ Add/Replaced Bolt: \_\_\_\_\_



# GETTLER-RYAN INC.

## WELL MONITORING/SAMPLING FIELD DATA SHEET

Client/Facility#: Chevron #9-3864 Job Number: 386358  
 Site Address: 5101 Telegraph Avenue Event Date: 3-14-11 (inclusive)  
 City: Oakland, CA Sampler: Joc

Well ID: MW-1  
 Well Diameter: 2 in.  
 Total Depth: 21.61 ft.  
 Depth to Water: 11.65 ft.  
9.96 xVF 0.17 = 1.69

Date Monitored: 3-14-11

Volume	3/4"= 0.02	1"= 0.04	2"= 0.17	3"= 0.38
Factor (VF)	4"= 0.66	5"= 1.02	6"= 1.50	12"= 5.80

Check if water column is less than 0.50 ft.

x3 case volume = Estimated Purge Volume: 5.5 gal.

Depth to Water w/ 80% Recharge [(Height of Water Column x 0.20) + DTW]: 13.64

### Purge Equipment:

Disposable Bailer   
 Stainless Steel Bailer \_\_\_\_\_  
 Stack Pump \_\_\_\_\_  
 Suction Pump \_\_\_\_\_  
 Grundfos \_\_\_\_\_  
 Peristaltic Pump \_\_\_\_\_  
 QED Bladder Pump \_\_\_\_\_  
 Other: \_\_\_\_\_

### Sampling Equipment:

Disposable Bailer   
 Pressure Bailer \_\_\_\_\_  
 Discrete Bailer \_\_\_\_\_  
 Peristaltic Pump \_\_\_\_\_  
 QED Bladder Pump \_\_\_\_\_  
 Other: \_\_\_\_\_

Time Started: \_\_\_\_\_ (2400 hrs)  
 Time Completed: \_\_\_\_\_ (2400 hrs)  
 Depth to Product: \_\_\_\_\_ ft  
 Depth to Water: \_\_\_\_\_ ft  
 Hydrocarbon Thickness: \_\_\_\_\_ ft  
 Visual Confirmation/Description: \_\_\_\_\_  
 Skimmer / Absorbant Sock (circle one)  
 Amt Removed from Skimmer: \_\_\_\_\_ gal  
 Amt Removed from Well: \_\_\_\_\_ gal  
 Water Removed: \_\_\_\_\_  
 Product Transferred to: \_\_\_\_\_

Start Time (purge): 1015 Weather Conditions: Rain  
 Sample Time/Date: 1038 13-14-11 Water Color: clear Odor: Y1N  
 Approx. Flow Rate: \_\_\_\_\_ gpm. Sediment Description: none  
 Did well de-water? no If yes, Time: \_\_\_\_\_ Volume: \_\_\_\_\_ gal. DTW @ Sampling: 11.78

Time (2400 hr.)	Volume (gal.)	pH	Conductivity (µmhos/cm - 45)	Temperature (°C / °F)	D.O. (mg/L)	ORP (mV)
<u>1020</u>	<u>1.5</u>	<u>7.48</u>	<u>1315</u>	<u>16.9</u>		
<u>1024</u>	<u>3.5</u>	<u>7.43</u>	<u>1292</u>	<u>17.0</u>		
<u>1028</u>	<u>5.5</u>	<u>7.36</u>	<u>1287</u>	<u>17.1</u>		

### LABORATORY INFORMATION

SAMPLE ID	(#) CONTAINER	REFRIG.	PRESERV. TYPE	LABORATORY	ANALYSES
<u>MW-1</u>	<u>x voa vial</u>	<u>YES</u>	<u>HCL</u>	<u>LANCASTER</u>	<u>TPH-GRO(8015)/BTEX+MTBE(8260)</u>

COMMENTS: \_\_\_\_\_

Add/Replaced Lock: \_\_\_\_\_

Add/Replaced Plug: \_\_\_\_\_

Add/Replaced Bolt: \_\_\_\_\_





# GETTLER-RYAN INC.

## WELL MONITORING/SAMPLING FIELD DATA SHEET

Client/Facility#: Chevron #9-3864 Job Number: 386358  
 Site Address: 5101 Telegraph Avenue Event Date: 3-14-11 (inclusive)  
 City: Oakland, CA Sampler: Joe

Well ID: MW-2  
 Well Diameter: 2 in.  
 Total Depth: 24.38 ft.  
 Depth to Water: 11.89 ft.  
12.49 xVF = 0.17 = 2.12

Date Monitored: 3-14-11

Volume	3/4"= 0.02	1"= 0.04	2"= 0.17	3"= 0.38
Factor (VF)	4"= 0.66	5"= 1.02	6"= 1.50	12"= 5.80

Check if water column is less than 0.50 ft.

Depth to Water w/ 80% Recharge [(Height of Water Column x 0.20) + DTW]: 14.38

x3 case volume = Estimated Purge Volume: 6.5 gal.

### Purge Equipment:

- Disposable Bailer
- Stainless Steel Bailer
- Stack Pump
- Suction Pump
- Grundfos
- Peristaltic Pump
- QED Bladder Pump
- Other:

### Sampling Equipment:

- Disposable Bailer
- Pressure Bailer
- Discrete Bailer
- Peristaltic Pump
- QED Bladder Pump
- Other:

Time Started: \_\_\_\_\_ (2400 hrs)  
 Time Completed: \_\_\_\_\_ (2400 hrs)  
 Depth to Product: \_\_\_\_\_ ft  
 Depth to Water: \_\_\_\_\_ ft  
 Hydrocarbon Thickness: \_\_\_\_\_ ft  
 Visual Confirmation/Description: \_\_\_\_\_  
 Skimmer / Absorbent Sock (circle one)  
 Amt Removed from Skimmer: \_\_\_\_\_ gal  
 Amt Removed from Well: \_\_\_\_\_ gal  
 Water Removed: \_\_\_\_\_ gal  
 Product Transferred to: \_\_\_\_\_

Start Time (purge): 1050 Weather Conditions: Rain  
 Sample Time/Date: 1115 13-14-11 Water Color: clear Odor: Y-1(N)  
 Approx. Flow Rate: \_\_\_\_\_ gpm. Sediment Description: none  
 Did well de-water? no If yes, Time: \_\_\_\_\_ Volume: \_\_\_\_\_ gal. DTW @ Sampling: 12.16

Time (2400 hr.)	Volume (gal.)	pH	Conductivity (µmhos/cm - µS)	Temperature (°C / °F)	D.O. (mg/L)	ORP (mV)
<u>1056</u>	<u>2</u>	<u>7.25</u>	<u>1161</u>	<u>17.4</u>		
<u>1100</u>	<u>4</u>	<u>7.30</u>	<u>1147</u>	<u>17.7</u>		
<u>1104</u>	<u>6.5</u>	<u>7.32</u>	<u>1154</u>	<u>17.5</u>		

### LABORATORY INFORMATION

SAMPLE ID	(#) CONTAINER	REFRIG.	PRESERV. TYPE	LABORATORY	ANALYSES
<u>MW-2</u>	<u>6</u> x voa vial	<u>YES</u>	<u>HCL</u>	<u>LANCASTER</u>	<u>TPH-GRO(8015)/BTEX+MTBE(8260)</u>

COMMENTS: \_\_\_\_\_



# GETTLER-RYAN INC.

## WELL MONITORING/SAMPLING FIELD DATA SHEET

Client/Facility#: Chevron #9-3864 Job Number: 386358  
 Site Address: 5101 Telegraph Avenue Event Date: 3-14-11 (inclusive)  
 City: Oakland, CA Sampler: Joc

Well ID MW-3  
 Well Diameter 2 in.  
 Total Depth 26.79 ft.  
 Depth to Water 14.17 ft.  
12.62 xVF 0.17 = 2.15

Date Monitored: 3-14-11

Volume	3/4"= 0.02	1"= 0.04	2"= 0.17	3"= 0.38
Factor (VF)	4"= 0.66	5"= 1.02	6"= 1.50	12"= 5.80

Check if water column is less than 0.50 ft.

Depth to Water w/ 80% Recharge [(Height of Water Column x 0.20) + DTW]: 16.69

Estimated Purge Volume: 6.4 gal.

### Purge Equipment:

- Disposable Bailer
- Stainless Steel Bailer
- Stack Pump
- Suction Pump
- Grundfos
- Peristaltic Pump
- QED Bladder Pump
- Other:

### Sampling Equipment:

- Disposable Bailer
- Pressure Bailer
- Discrete Bailer
- Peristaltic Pump
- QED Bladder Pump
- Other:

Time Started:	_____ (2400 hrs)
Time Completed:	_____ (2400 hrs)
Depth to Product:	_____ ft
Depth to Water:	_____ ft
Hydrocarbon Thickness:	_____ ft
Visual Confirmation/Description:	_____
Skimmer / Absorbent Sock (circle one)	
Amt Removed from Skimmer:	_____ gal
Amt Removed from Well:	_____ gal
Water Removed:	_____ gal
Product Transferred to:	_____

Start Time (purge): 0900 Weather Conditions: Rain  
 Sample Time/Date: 0930 13-14-11 Water Color: clear Odor: ⊕IN light  
 Approx. Flow Rate: \_\_\_\_\_ gpm. Sediment Description: none  
 Did well de-water? no If yes, Time: \_\_\_\_\_ Volume: \_\_\_\_\_ gal. DTW @ Sampling: 14.46

Time (2400 hr.)	Volume (gal.)	pH	Conductivity (µmhos/cm - µS <sub>V</sub> )	Temperature (°F)	D.O. (mg/L)	ORP (mV)
<u>0906</u>	<u>1.5</u>	<u>6.77</u>	<u>753</u>	<u>17.6</u>		
<u>0912</u>	<u>3.5</u>	<u>6.84</u>	<u>761</u>	<u>17.4</u>		
<u>0917</u>	<u>5.5</u>	<u>6.85</u>	<u>760</u>	<u>17.3</u>		

### LABORATORY INFORMATION

SAMPLE ID	(#) CONTAINER	REFRIG.	PRESERV. TYPE	LABORATORY	ANALYSES
<u>MW-3</u>	<u>6</u> x voa vial	<u>YES</u>	<u>HCL</u>	<u>LANCASTER</u>	<u>TPH-GRO(8015)/BTEX+MTBE(8260)</u>

COMMENTS: \_\_\_\_\_

Add/Replaced Lock: \_\_\_\_\_

Add/Replaced Plug: \_\_\_\_\_

Add/Replaced Bolt: \_\_\_\_\_



# GETTLER-RYAN INC.

## WELL MONITORING/SAMPLING FIELD DATA SHEET

Client/Facility#: **Chevron #9-3864**  
 Site Address: **5101 Telegraph Avenue**  
 City: **Oakland, CA**

Job Number: **386358**  
 Event Date: **3-14-11** (inclusive)  
 Sampler: **Jor**

Well ID: **MW-5**  
 Well Diameter: **2** in.  
 Total Depth: **21.65** ft.  
 Depth to Water: **14.19** ft.  
**7.46** xVF **0.17 = 1.27**

Date Monitored: **3-14-11**

Volume	3/4"= 0.02	1"= 0.04	2"= 0.17	3"= 0.38
Factor (VF)	4"= 0.66	5"= 1.02	6"= 1.50	12"= 5.80

Check if water column is less than 0.50 ft.

Depth to Water w/ 80% Recharge [(Height of Water Column x 0.20) + DTW]: **15.68** gal.

### Purge Equipment:

Disposable Bailer   
 Stainless Steel Bailer \_\_\_\_\_  
 Stack Pump \_\_\_\_\_  
 Suction Pump \_\_\_\_\_  
 Grundfos \_\_\_\_\_  
 Peristaltic Pump \_\_\_\_\_  
 QED Bladder Pump \_\_\_\_\_  
 Other: \_\_\_\_\_

### Sampling Equipment:

Disposable Bailer   
 Pressure Bailer \_\_\_\_\_  
 Discrete Bailer \_\_\_\_\_  
 Peristaltic Pump \_\_\_\_\_  
 QED Bladder Pump \_\_\_\_\_  
 Other: \_\_\_\_\_

Time Started: \_\_\_\_\_ (2400 hrs)  
 Time Completed: \_\_\_\_\_ (2400 hrs)  
 Depth to Product: \_\_\_\_\_ ft  
 Depth to Water: \_\_\_\_\_ ft  
 Hydrocarbon Thickness: \_\_\_\_\_ ft  
 Visual Confirmation/Description: \_\_\_\_\_  
 Skimmer / Absorbant Sock (circle one)  
 Amt Removed from Skimmer: \_\_\_\_\_ gal  
 Amt Removed from Well: \_\_\_\_\_ gal  
 Water Removed: \_\_\_\_\_ gal  
 Product Transferred to: \_\_\_\_\_

Start Time (purge): **0942** Weather Conditions: **Rain**  
 Sample Time/Date: **1005 3-14-11** Water Color: **clear** Odor: **YIP**  
 Approx. Flow Rate: \_\_\_\_\_ gpm. Sediment Description: **none**  
 Did well de-water? **no** If yes, Time: \_\_\_\_\_ Volume: \_\_\_\_\_ gal. DTW @ Sampling: **14.30**

Time (2400 hr.)	Volume (gal.)	pH	Conductivity (µmhos/cm - µS)	Temperature (°C / F)	D.O. (mg/L)	ORP (mV)
<b>0947</b>	<b>1.5</b>	<b>7.63</b>	<b>1097</b>	<b>16.9</b>		
<b>0951</b>	<b>3</b>	<b>7.38</b>	<b>1125</b>	<b>17.4</b>		
<b>0955</b>	<b>4</b>	<b>7.42</b>	<b>1129</b>	<b>17.8</b>		

### LABORATORY INFORMATION

SAMPLE ID	(#) CONTAINER	REFRIG.	PRESERV. TYPE	LABORATORY	ANALYSES
<b>MW-5</b>	<b>6</b> x voa vial	<b>YES</b>	<b>HCL</b>	<b>LANCASTER</b>	<b>TPH-GRO(8015)/BTEX+MTBE(8260)</b>

COMMENTS: \_\_\_\_\_

Add/Replaced Lock: \_\_\_\_\_

Add/Replaced Plug: \_\_\_\_\_

Add/Replaced Bolt: \_\_\_\_\_





2425 New Holland Pike, PO Box 12425, Lancaster, PA 17605-2425 • 717-656-2300 Fax: 717-656-2681 • www.lancasterlabs.com

# Analysis Report

## ANALYTICAL RESULTS

Prepared by:

Lancaster Laboratories  
2425 New Holland Pike  
Lancaster, PA 17605-2425

Prepared for:

Chevron c/o CRA  
Suite 107  
10969 Trade Center Dr  
Rancho Cordova CA 95670

March 21, 2011

Project: 93864

Submittal Date: 03/15/2011

Group Number: 1237309

PO Number: 93864

Release Number: MTI

State of Sample Origin: CA

RECEIVED

MAR 21 2011

GETTLER-RYAN INC.  
GENERAL CONTRACTORS

Client Sample Description

C-3-W-110314 Grab Water  
MW-1-W-110314 Grab Water  
MW-2-W-110314 Grab Water  
MW-3-W-110314 Grab Water  
MW-5-W-110314 Grab Water

Lancaster Labs (LLI) #

6229978  
6229979  
6229980  
6229981  
6229982

The specific methodologies used in obtaining the enclosed analytical results are indicated on the Laboratory Sample Analysis Record.

ELECTRONIC     Gettler-Ryan, Inc.  
COPY TO  
ELECTRONIC     Chevron c/o CRA  
COPY TO  
ELECTRONIC     Chevron  
COPY TO

Attn: Rachelle Munoz  
Attn: Report Contact  
Attn: Anna Avina



## ***Analysis Report***

2425 New Holland Pike, PO Box 12425, Lancaster, PA 17605-2425 • 717-656-2300 Fax: 717-656-2681 • www.lancasterlabs.com

Questions? Contact your Client Services Representative  
Jill M Parker at (717) 656-2300 Ext. 1241

Respectfully Submitted,

A handwritten signature in black ink that reads "Maria S. Lord".

**Maria S. Lord**  
**Senior Specialist**



# Analysis Report

2425 New Holland Pike, PO Box 12425, Lancaster, PA 17605-2425 • 717-656-2300 Fax: 717-656-2681 • www.lancasterlabs.com

Sample Description: C-3-W-110314 Grab Water

Facility# 93864 Job# 386358 MTI# 61H-1951 GRD  
5101 Telegraph-Oakland T0600100343 C-1

LLI Sample # WW 6229978  
LLI Group # 1237309  
Account # 12099

Project Name: 93864

Collected: 03/14/2011 08:50 by JA

Chevron c/o CRA  
Suite 107

Submitted: 03/15/2011 09:30

10969 Trade Center Dr

Reported: 03/21/2011 11:59

Rancho Cordova CA 95670

TOC1-

CAT No.	Analysis Name	CAS Number	As Received Result	As Received Method Detection Limit	Dilution Factor
<b>GC/MS Volatiles SW-846 8260B</b>					
10943	Benzene	71-43-2	N.D.	0.5 ug/1	1
10943	Ethylbenzene	100-41-4	0.6	0.5	1
10943	Methyl Tertiary Butyl Ether	1634-04-4	N.D.	0.5	1
10943	Toluene	108-88-3	N.D.	0.5	1
10943	Xylene (Total)	1330-20-7	1	0.5	1
<b>GC Volatiles SW-846 8015B</b>					
01728	TPH-GRO N. CA water C6-C12	n.a.	3,400 ug/1	50 ug/1	1

General Sample Comments

State of California Lab Certification No. 2501  
Trip blank vials were not received by the laboratory for this sample group.

All QC is compliant unless otherwise noted. Please refer to the Quality Control Summary for overall QC performance data and associated samples.

Laboratory Sample Analysis Record

CAT No.	Analysis Name	Method	Trial#	Batch#	Analysis Date and Time	Analyst	Dilution Factor
10943	BTEX/MTBE 8260 Water	SW-846 8260B	1	P110762AA	03/17/2011 04:01	Holly Berry	1
01163	GC/MS VOA Water Prep	SW-846 5030B	1	P110762AA	03/17/2011 04:01	Holly Berry	1
01728	TPH-GRO N. CA water C6-C12	SW-846 8015B	1	11076A07A	03/18/2011 23:53	Katrina T Longenecker	1
01146	GC VOA Water Prep	SW-846 5030B	1	11076A07A	03/18/2011 23:53	Katrina T Longenecker	1



# Analysis Report

2425 New Holland Pike, PO Box 12425, Lancaster, PA 17605-2425 • 717-656-2300 Fax: 717-656-2681 • www.lancasterlabs.com

Page 1 of 1

**Sample Description:** MW-1-W-110314 Grab Water  
 Facility# 93864 Job# 386358 MTI# 61H-1951 GRD  
 5101 Telegraph-Oakland T0600100343 MW-1

LLI Sample # WW 6229979  
 LLI Group # 1237309  
 Account # 12099

**Project Name:** 93864

Collected: 03/14/2011 10:38 by JA Chevron c/o CRA  
 Suite 107  
 Submitted: 03/15/2011 09:30 10969 Trade Center Dr  
 Reported: 03/21/2011 11:59 Rancho Cordova CA 95670

**TOMW1**

CAT No.	Analysis Name	CAS Number	As Received Result	As Received Method Detection Limit	Dilution Factor
<b>GC/MS Volatiles</b>			ug/l	ug/l	
10943	Benzene	71-43-2	N.D.	0.5	1
10943	Ethylbenzene	100-41-4	N.D.	0.5	1
10943	Methyl Tertiary Butyl Ether	1634-04-4	N.D.	0.5	1
10943	Toluene	108-88-3	N.D.	0.5	1
10943	Xylene (Total)	1330-20-7	N.D.	0.5	1
<b>GC Volatiles</b>			ug/l	ug/l	
01728	TPH-GRO N. CA water C6-C12	n.a.	N.D.	50	1

**General Sample Comments**

State of California Lab Certification No. 2501  
 Trip blank vials were not received by the laboratory for this sample group.

All QC is compliant unless otherwise noted. Please refer to the Quality Control Summary for overall QC performance data and associated samples.

**Laboratory Sample Analysis Record**

CAT No.	Analysis Name	Method	Trial#	Batch#	Analysis Date and Time	Analyst	Dilution Factor
10943	BTEX/MTBE 8260 Water	SW-846 8260B	1	P110762AA	03/17/2011 04:28	Holly Berry	1
01163	GC/MS VOA Water Prep	SW-846 5030B	1	P110762AA	03/17/2011 04:28	Holly Berry	1
01728	TPH-GRO N. CA water C6-C12	SW-846 8015B	1	11076A07A	03/18/2011 18:15	Katrina T Longenecker	1
01146	GC VOA Water Prep	SW-846 5030B	1	11076A07A	03/18/2011 18:15	Katrina T Longenecker	1





# Analysis Report

2425 New Holland Pike, PO Box 12425, Lancaster, PA 17605-2425 • 717-656-2300 Fax: 717-656-2681 • www.lancasterlabs.com

**Sample Description:** MW-2-W-110314 Grab Water  
 Facility# 93864 Job# 386358 MTI# 61H-1951 GRD  
 5101 Telegraph-Oakland T0600100343 MW-2

LLI Sample # WW 6229980  
 LLI Group # 1237309  
 Account # 12099

**Project Name:** 93864

Collected: 03/14/2011 11:15 by JA Chevron c/o CRA  
 Suite 107  
 Submitted: 03/15/2011 09:30 10969 Trade Center Dr  
 Reported: 03/21/2011 11:59 Rancho Cordova CA 95670

**TOMW2**

CAT No.	Analysis Name	CAS Number	As Received Result	As Received Method Detection Limit	Dilution Factor
<b>GC/MS Volatiles</b>			ug/l	ug/l	
10943	Benzene	71-43-2	N.D.	0.5	1
10943	Ethylbenzene	100-41-4	N.D.	0.5	1
10943	Methyl Tertiary Butyl Ether	1634-04-4	N.D.	0.5	1
10943	Toluene	108-88-3	N.D.	0.5	1
10943	Xylene (Total)	1330-20-7	N.D.	0.5	1
<b>GC Volatiles</b>			ug/l	ug/l	
01728	TPH-GRO N. CA water C6-C12	n.a.	N.D.	50	1

**General Sample Comments**

State of California Lab Certification No. 2501  
 Trip blank vials were not received by the laboratory for this sample group.

All QC is compliant unless otherwise noted. Please refer to the Quality Control Summary for overall QC performance data and associated samples.

**Laboratory Sample Analysis Record**

CAT No.	Analysis Name	Method	Trial#	Batch#	Analysis Date and Time	Analyst	Dilution Factor
10943	BTEX/MTBE 8260 Water	SW-846 8260B	1	F110761AA	03/17/2011 06:59	Anita M Dale	1
01163	GC/MS VOA Water Prep	SW-846 5030B	1	F110761AA	03/17/2011 06:59	Anita M Dale	1
01728	TPH-GRO N. CA water C6-C12	SW-846 8015B	1	11076A07A	03/18/2011 19:13	Katrina T Longenecker	1
01146	GC VOA Water Prep	SW-846 5030B	1	11076A07A	03/18/2011 19:13	Katrina T Longenecker	1



# Analysis Report

2425 New Holland Pike, PO Box 12425, Lancaster, PA 17605-2425 • 717-656-2300 Fax: 717-656-2681 • www.lancasterlabs.com

Page 1 of 1

Sample Description: MW-3-W-110314 Grab Water

Facility# 93864 Job# 386358 MTI# 61H-1951 GRD  
5101 Telegraph-Oakland T0600100343 MW-3

LLI Sample # WW 6229981

LLI Group # 1237309

Account # 12099

Project Name: 93864

Collected: 03/14/2011 09:30 by JA

Chevron c/o CRA

Suite 107

Submitted: 03/15/2011 09:30

10969 Trade Center Dr

Reported: 03/21/2011 11:59

Rancho Cordova CA 95670

## TOMW3

CAT No.	Analysis Name	CAS Number	As Received Result	As Received Method Detection Limit	Dilution Factor
<b>GC/MS Volatiles SW-846 8260B</b>					
10943	Benzene	71-43-2	N.D.	0.5 ug/l	1
10943	Ethylbenzene	100-41-4	N.D.	0.5	1
10943	Methyl Tertiary Butyl Ether	1634-04-4	N.D.	0.5	1
10943	Toluene	108-88-3	N.D.	0.5	1
10943	Xylene (Total)	1330-20-7	0.6	0.5	1
<b>GC Volatiles SW-846 8015B</b>					
01728	TPH-GRO N. CA water C6-C12	n.a.	1,300	50 ug/l	1

## General Sample Comments

State of California Lab Certification No. 2501

Trip blank vials were not received by the laboratory for this sample group.

All QC is compliant unless otherwise noted. Please refer to the Quality Control Summary for overall QC performance data and associated samples.

## Laboratory Sample Analysis Record

CAT No.	Analysis Name	Method	Trial#	Batch#	Analysis Date and Time	Analyst	Dilution Factor
10943	BTEX/MTBE 8260 Water	SW-846 8260B	1	P110762AA	03/17/2011 04:56	Holly Berry	1
01163	GC/MS VOA Water Prep	SW-846 5030B	1	P110762AA	03/17/2011 04:56	Holly Berry	1
01728	TPH-GRO N. CA water C6-C12	SW-846 8015B	1	11076A07A	03/18/2011 19:39	Katrina T Longenecker	1
01146	GC VOA Water Prep	SW-846 5030B	1	11076A07A	03/18/2011 19:39	Katrina T Longenecker	1



# Analysis Report

2425 New Holland Pike, PO Box 12425, Lancaster, PA 17605-2425 • 717-656-2300 Fax: 717-656-2681 • www.lancasterlabs.com

Sample Description: MW-5-W-110314 Grab Water

Facility# 93864 Job# 386358 MTI# 61H-1951 GRD  
5101 Telegraph-Oakland T0600100343 MW-5

LLI Sample # WW 6229982  
LLI Group # 1237309  
Account # 12099

Project Name: 93864

Collected: 03/14/2011 10:05 by JA

Chevron c/o CRA

Suite 107

Submitted: 03/15/2011 09:30

10969 Trade Center Dr

Reported: 03/21/2011 11:59

Rancho Cordova CA 95670

**TOMW5**

CAT No.	Analysis Name	CAS Number	As Received Result	As Received Method Detection Limit	Dilution Factor
<b>GC/MS Volatiles SW-846 8260B</b>					
10943	Benzene	71-43-2	N.D.	0.5 ug/l	1
10943	Ethylbenzene	100-41-4	N.D.	0.5	1
10943	Methyl Tertiary Butyl Ether	1634-04-4	N.D.	0.5	1
10943	Toluene	108-88-3	N.D.	0.5	1
10943	Xylene (Total)	1330-20-7	N.D.	0.5	1
<b>GC Volatiles SW-846 8015B</b>					
01728	TPH-GRO N. CA water C6-C12	n.a.	N.D.	50 ug/l	1

**General Sample Comments**

State of California Lab Certification No. 2501  
Trip blank vials were not received by the laboratory for this sample group.

All QC is compliant unless otherwise noted. Please refer to the Quality Control Summary for overall QC performance data and associated samples.

**Laboratory Sample Analysis Record**

CAT No.	Analysis Name	Method	Trial#	Batch#	Analysis Date and Time	Analyst	Dilution Factor
10943	BTEX/MTBE 8260 Water	SW-846 8260B	1	F110761AA	03/17/2011 07:21	Anita M Dale	1
01163	GC/MS VOA Water Prep	SW-846 5030B	1	F110761AA	03/17/2011 07:21	Anita M Dale	1
01728	TPH-GRO N. CA water C6-C12	SW-846 8015B	1	11076A07A	03/18/2011 20:04	Katrina T Longenecker	1
01146	GC VOA Water Prep	SW-846 5030B	1	11076A07A	03/18/2011 20:04	Katrina T Longenecker	1

## Quality Control Summary

 Client Name: Chevron c/o CRA  
 Reported: 03/21/11 at 11:59 AM

Group Number: 1237309

Matrix QC may not be reported if site-specific QC samples were not submitted. In these situations, to demonstrate precision and accuracy at a batch level, a LCS/LCSD was performed, unless otherwise specified in the method.

### Laboratory Compliance Quality Control

Analysis Name	Blank Result	Blank MDL	Report Units	LCS %REC	LCSD %REC	LCS/LCSD Limits	RPD	RPD Max
Batch number: F110761AA	Sample number(s): 6229980, 6229982							
Benzene	N.D.	0.5	ug/l	99		79-120		
Ethylbenzene	N.D.	0.5	ug/l	97		79-120		
Methyl Tertiary Butyl Ether	N.D.	0.5	ug/l	95		76-120		
Toluene	N.D.	0.5	ug/l	98		79-120		
Xylene (Total)	N.D.	0.5	ug/l	95		80-120		
Batch number: P110762AA	Sample number(s): 6229978-6229979, 6229981							
Benzene	N.D.	0.5	ug/l	100	100	79-120	0	30
Ethylbenzene	N.D.	0.5	ug/l	96	96	79-120	0	30
Methyl Tertiary Butyl Ether	N.D.	0.5	ug/l	101	103	76-120	2	30
Toluene	N.D.	0.5	ug/l	98	98	79-120	1	30
Xylene (Total)	N.D.	0.5	ug/l	95	96	80-120	0	30
Batch number: 11076A07A	Sample number(s): 6229978-6229982							
TPH-GRO N. CA water C6-C12	N.D.	50.	ug/l	100	109	75-135	9	30

### Sample Matrix Quality Control

Unspiked (UNSPK) = the sample used in conjunction with the matrix spike  
 Background (BKG) = the sample used in conjunction with the duplicate

Analysis Name	MS %REC	MSD %REC	MS/MSD Limits	RPD	RPD MAX	BKG Conc	DUP Conc	DUP RPD	Dup RPD Max
Batch number: F110761AA	Sample number(s): 6229980, 6229982 UNSPK: 6229982								
Benzene	102	103	80-126	1	30				
Ethylbenzene	101	101	71-134	1	30				
Methyl Tertiary Butyl Ether	95	97	72-126	2	30				
Toluene	101	101	80-125	0	30				
Xylene (Total)	99	100	79-125	0	30				

### Surrogate Quality Control

Surrogate recoveries which are outside of the QC window are confirmed unless attributed to dilution or otherwise noted on the Analysis Report.

 Analysis Name: UST VOCs by 8260B - Water  
 Batch number: F110761AA

Dibromofluoromethane    1,2-Dichloroethane-d4    Toluene-d8    4-Bromofluorobenzene

\*- Outside of specification

- (1) The result for one or both determinations was less than five times the LOQ.
- (2) The unspiked result was more than four times the spike added.

## Quality Control Summary

Client Name: Chevron c/o CRA  
Reported: 03/21/11 at 11:59 AM

Group Number: 1237309

### Surrogate Quality Control

6229980	95	100	100	92
6229982	94	100	99	92
Blank	95	100	100	92
LCS	94	100	99	95
MS	94	102	99	97
MSD	93	101	99	96

---

Limits: 80-116      77-113      80-113      78-113

Analysis Name: UST VOCs by 8260B - Water  
Batch number: P110762AA

	Dibromofluoromethane	1,2-Dichloroethane-d4	Toluene-d8	4-Bromofluorobenzene
6229978	99	98	97	99
6229979	100	98	100	92
6229981	101	99	99	96
Blank	100	99	99	91
LCS	101	102	97	93
LCSD	101	101	98	94

---

Limits: 80-116      77-113      80-113      78-113

Analysis Name: TPH-GRO N. CA water C6-C12  
Batch number: 11076A07A  
Trifluorotoluene-F

6229978	118
6229979	86
6229980	84
6229981	115
6229982	85
Blank	90
LCS	95
LCSD	96

---

Limits: 63-135

\*- Outside of specification

- (1) The result for one or both determinations was less than five times the LOQ.
- (2) The unspiked result was more than four times the spike added.

# Explanation of Symbols and Abbreviations

The following defines common symbols and abbreviations used in reporting technical data:

<b>RL</b>	Reporting Limit	<b>BMQL</b>	Below Minimum Quantitation Level
<b>N.D.</b>	none detected	<b>MPN</b>	Most Probable Number
<b>TNTC</b>	Too Numerous To Count	<b>CP Units</b>	cobalt-chloroplatinate units
<b>IU</b>	International Units	<b>NTU</b>	nephelometric turbidity units
<b>umhos/cm</b>	micromhos/cm	<b>ng</b>	nanogram(s)
<b>C</b>	degrees Celsius	<b>F</b>	degrees Fahrenheit
<b>meq</b>	milliequivalents	<b>lb.</b>	pound(s)
<b>g</b>	gram(s)	<b>kg</b>	kilogram(s)
<b>ug</b>	microgram(s)	<b>mg</b>	milligram(s)
<b>ml</b>	milliliter(s)	<b>l</b>	liter(s)
<b>m3</b>	cubic meter(s)	<b>ul</b>	microliter(s)
<b>&lt;</b>	less than - The number following the sign is the <u>limit of quantitation</u> , the smallest amount of analyte which can be reliably determined using this specific test.		
<b>&gt;</b>	greater than		
<b>J</b>	estimated value – The result is $\geq$ the Method Detection Limit (MDL) and $<$ the Limit of Quantitation (LOQ).		
<b>ppm</b>	parts per million - One ppm is equivalent to one milligram per kilogram (mg/kg), or one gram per million grams. For aqueous liquids, ppm is usually taken to be equivalent to milligrams per liter (mg/l), because one liter of water has a weight very close to a kilogram. For gases or vapors, one ppm is equivalent to one microliter of gas per liter of gas.		
<b>ppb</b>	parts per billion		
<b>Dry weight basis</b>	Results printed under this heading have been adjusted for moisture content. This increases the analyte weight concentration to approximate the value present in a similar sample without moisture. All other results are reported on an as-received basis.		

## U.S. EPA CLP Data Qualifiers:

Organic Qualifiers	Inorganic Qualifiers
<b>A</b> TIC is a possible aldol-condensation product	<b>B</b> Value is $<$ CRDL, but $\geq$ IDL
<b>B</b> Analyte was also detected in the blank	<b>E</b> Estimated due to interference
<b>C</b> Pesticide result confirmed by GC/MS	<b>M</b> Duplicate injection precision not met
<b>D</b> Compound quantitated on a diluted sample	<b>N</b> Spike sample not within control limits
<b>E</b> Concentration exceeds the calibration range of the instrument	<b>S</b> Method of standard additions (MSA) used for calculation
<b>N</b> Presumptive evidence of a compound (TICs only)	<b>U</b> Compound was not detected
<b>P</b> Concentration difference between primary and confirmation columns $>$ 25%	<b>W</b> Post digestion spike out of control limits
<b>U</b> Compound was not detected	<b>*</b> Duplicate analysis not within control limits
<b>X,Y,Z</b> Defined in case narrative	<b>+</b> Correlation coefficient for MSA $<$ 0.995

Analytical test results meet all requirements of NELAC unless otherwise noted under the individual analysis.


Measurement uncertainty values, as applicable, are available upon request.

Tests results relate only to the sample tested. Clients should be aware that a critical step in a chemical or microbiological analysis is the collection of the sample. Unless the sample analyzed is truly representative of the bulk of material involved, the test results will be meaningless. If you have questions regarding the proper techniques of collecting samples, please contact us. We cannot be held responsible for sample integrity, however, unless sampling has been performed by a member of our staff. This report shall not be reproduced except in full, without the written approval of the laboratory.

**WARRANTY AND LIMITS OF LIABILITY** - In accepting analytical work, we warrant the accuracy of test results for the sample as submitted. THE FOREGOING EXPRESS WARRANTY IS EXCLUSIVE AND IS GIVEN IN LIEU OF ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED. WE DISCLAIM ANY OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING A WARRANTY OF FITNESS FOR PARTICULAR PURPOSE AND WARRANTY OF MERCHANTABILITY. IN NO EVENT SHALL LANCASTER LABORATORIES BE LIABLE FOR INDIRECT, SPECIAL, CONSEQUENTIAL, OR INCIDENTAL DAMAGES INCLUDING, BUT NOT LIMITED TO, DAMAGES FOR LOSS OF PROFIT OR GOODWILL REGARDLESS OF (A) THE NEGLIGENCE (EITHER SOLE OR CONCURRENT) OF LANCASTER LABORATORIES AND (B) WHETHER LANCASTER LABORATORIES HAS BEEN INFORMED OF THE POSSIBILITY OF SUCH DAMAGES. We accept no legal responsibility for the purposes for which the client uses the test results. No purchase order or other order for work shall be accepted by Lancaster Laboratories which includes any conditions that vary from the Standard Terms and Conditions, and Lancaster hereby objects to any conflicting terms contained in any acceptance or order submitted by client.


APPENDIX F

HISTORICAL ISOCONCENTRATION MAPS AND NEARBY GROUNDWATER DATA



**LEGEND**

- MW-1 GROUND WATER MONITORING WELLS INSTALLED BY QST
- MW-1 GROUND WATER MONITORING WELLS INSTALLED FOR CHEVRON
- C-1 SOIL BORING BY QST
- AP-1 SOIL BORING BY QST
- x - FENCE
- T T T CONCENTRATION ISOPLETH



51544009.DWG, 1.0  
20020520.1005

CHEVRON SITE BASE MAP FROM CAMBRIA ENVIRONMENTAL TECHNOLOGY, INC.



**Harding ESE**  
A MACTEC COMPANY

**TPH-G Plume**

Autopro Inc.  
5200 Telegraph Avenue  
Oakland, California

DRAWN SS  
JOB NUMBER 51644 030


APPROVED  
DATE 04/02

FIGURE

**4**


REVISED DATE





**LEGEND**

- MW-1 GROUND WATER MONITORING WELLS INSTALLED BY QST
- MW-1 GROUND WATER MONITORING WELLS INSTALLED FOR CHEVRON
- C-1 GROUND WATER MONITORING WELLS INSTALLED FOR CHEVRON
- AP-1 SOIL BORING BY QST
- x - FENCE
- T T T CONCENTRATION ISOPLETH



51644010.DWG 1.0  
20020520.1006

CHEVRON SITE BASE MAP FROM CAMBRIA ENVIRONMENTAL TECHNOLOGY, INC.




**Harding ESE**  
A MACTEC COMPANY

**TPH-D Plume**  
March 22, 2002  
Autopio Inc.  
5200 Telegraph Avenue  
Oakland, California


DRAWN SS	JOB NUMBER 51644 030	APPROVED	DATE 04/02	REVISED DATE
-------------	-------------------------	----------	---------------	--------------

FIGURE  
**5**



**LEGEND**

- MW-1 ⊕ GROUND WATER MONITORING WELLS INSTALLED BY QST
- MW-1 ● GROUND WATER MONITORING WELLS INSTALLED FOR CHEVRON
- C-1 ●
- AP-1 ⊗ SOIL BORING BY QST
- x- FENCE
- T T T CONCENTRATION ISOPLETH



51644011.DWG 1.0  
20020520.1006

CHEVRON SITE BASE MAP FROM CAMBRIA ENVIRONMENTAL TECHNOLOGY, INC.



**Harding ESE**  
A MACTEC COMPANY

**TPH-MO Plume**  
Autopro Inc.  
5200 Telegraph Avenue  
Oakland, California

DRAWN SS	JOB NUMBER 51644 030	APPROVED	DATE 04/02	REVISION DATE
-------------	-------------------------	----------	---------------	---------------

TABLE 2

## ANALYTICAL RESULTS FOR GRAB GROUND WATER SAMPLES

Tri-Star Partnership  
Autopro Facility  
5200 Telegraph Avenue  
Oakland, California

Sample I.D.	Date Sampled	TPH-D (µg/L)	TPH-G (µg/L)	TPH-MO (µg/L)	Benzene (µg/L)	Toluene (µg/L)	Ethylbenzene (µg/L)	Total Xylenes (µg/L)	MTBE (µg/L)
AP-1	07/02/96	190 <sup>g1</sup>	1,400 <sup>b,1</sup>	<250	<0.5	2.9	<0.5	3.1	<5.0
AP-2	07/02/96	74,000 <sup>d,h,1</sup>	7,900 <sup>b,d,h,1</sup>	<250	69	12	20	43	60
AP-3	07/02/96	47,000 <sup>d,h,1</sup>	14,000 <sup>b,d,h,1</sup>	<250	130	16	45	44	100
AP-4	07/02/96	<50	<50	<250	<0.5	<0.5	<0.5	<0.5	<5.0
AP-5	07/02/96	<50	<50	<250	<0.5	<0.5	<0.5	<0.5	<5.0
AP-6	07/02/96	410 <sup>g,1</sup>	<50	1,900	<0.5	<0.5	<0.5	<0.5	<5.0
AP-7	07/02/96	<50	<50	<250	<0.5	<0.5	<0.5	<0.5	<5.0
MCL	--	--	--	--	1.0	150	700	1,750	35*

## Notes:

TPH-D = Total Petroleum Hydrocarbons as Diesel.

TPH-G = Total Petroleum Hydrocarbons as Gasoline.

TPH-MO = Total Petroleum Hydrocarbons as Motor Oil.

MTBE = methyl tertiary butyl ether.

µg/L = micrograms per liter or parts per billion (ppb).

&lt; = less than listed detection limit.

-- = not applicable.

\* = DHS Action Level.

MCL = primary Maximum Contaminant Limit as defined by the California Department of Health Services (DHS) Drinking Water Standards.

<sup>b</sup> = heavier gasoline-range compounds are significant (aged gasoline?).<sup>d</sup> = gasoline-range compounds having broad chromatographic peaks are significant; biologically altered gasoline?<sup>g</sup> = strongly aged gasoline or diesel-range compounds are significant.<sup>h</sup> = lighter than water immiscible sheen is present.<sup>1</sup> = liquid sample that contains greater than ~ 5 vol. % sediment.<sup>l</sup> = no recognizable pattern.

**TABLE 3**

**GROUNDWATER ANALYTICAL RESULTS - UTILITY TRENCH BACKFILL BORING**


**Autopro Facility  
5200 Telegraph Avenue  
Oakland, California**

Boring ID	Date Sampled	TPHd (µg/L)	TPHmo (µg/L)	TPHg (µg/L)	Benzene (µg/L)	Toluene (µg/L)	Ethylbenzene (µg/L)	Total Xylenes (µg/L)	MTBE (µg/L)	Oxygenates (µg/L)
SB-1	08/07/04	29,000	<2,500	57,000	9.5	11	36	29	<5.0	ND*
MCL					10	50	50	750	3	

**Notes:**

- TPHd = Total Petroleum Hydrocarbons as Diesel
- TPHmo = Total Petroleum Hydrocarbons as Motor Oil
- TPHg = Total Petroleum Hydrocarbons as Gasoline
- MTBE = methyl tertiary butyl ether.
- MCL = (Maximum Contaminant Level) -
- ND\* = Not detected for all oxygenates
- µg/L = micrograms per liter or parts per billion (ppb).
- < = less than listed detection limits.

Checked GAL  
Approved [Signature]



EXPLORATORY BORING AND MONITORING WELL LOCATION MAP

KAPREALIAN ENGINEERING  
INCORPORATED

BERKELEY FARMS  
51ST STREET & TELEGRAPH AVE.  
OAKLAND, CALIFORNIA

FIGURE  
**2**

**Table 9**  
 Summary of Laboratory Analyses  
 Water

Date	Well	EPA 161		EPA 162		EPA 163		Toluene	Benzene	Xylene
		Kerosene	Gasoline	Gasoline	Gasoline	Gasoline	Gasoline			
11/25/96	MW1	<del>WELL WAS INACCESSIBLE</del>		ND	ND	ND	ND	ND	ND	
	MW2	--	ND	ND	ND	ND	ND	ND	ND	
	MW4	WELL WAS INACCESSIBLE								
	MW5	ND	ND	ND	ND	ND	ND	ND	ND	
8/30/96	MW1	--	ND	ND	ND	ND	ND	ND	ND	
	MW2	--	ND	ND	ND	ND	ND	ND	ND	
	MW4	WELL WAS INACCESSIBLE								
	MW5	64	ND	ND	ND	ND	ND	ND	ND	
5/21/96	MW1	--	ND	ND	ND	ND	ND	ND	ND	
	MW2	--	ND	ND	ND	ND	ND	ND	ND	
	MW3	WELL WAS DESTROYED ON FEBRUARY 29, 1996								
	MW4	WELL WAS INACCESSIBLE								
	MW5	200+	ND	ND	ND	ND	ND	ND	ND	
2/19/96	MW1	--	ND	ND	1.0	6.2	0.60	3.9		
	MW2	--	ND	ND	0.82	4.8	0.52	3.5		
	MW3	--	ND	ND	1.4	8.1	0.73	4.4		
	MW4	WELL WAS INACCESSIBLE								
	MW5	ND	ND	ND	1.1	6.7	0.63	4.2		
10/6/95	MW1	--	ND	69+	ND	ND	ND	ND		
	MW2	--	ND	ND	ND	ND	ND	ND		
	MW3	--	ND	ND	ND	ND	ND	ND		
	MW4	--	ND	ND	ND	ND	ND	ND		
	MW5	--	ND	ND	ND	ND	ND	ND		
9/18/95**	MW1	--	ND	81+	ND	ND	ND	ND		
	MW2	--	ND	ND	ND	ND	ND	ND		
	MW3	--	ND	ND	ND	ND	ND	ND		
	MW4	--	ND	ND	ND	ND	ND	ND		
	MW5	--	ND	ND	ND	ND	ND	ND		
8/24/95**	MW1	--	--	63	ND	1.1	ND	0.86		
	MW2	--	--	ND	ND	0.57	ND	0.56		
	MW3	--	--	ND	ND	0.50	ND	0.70		
	MW4	--	--	ND	ND	0.53	ND	0.60		
	MW5	--	--	ND	ND	0.81	ND	0.72		

**Table 4**  
 Summary of Laboratory Analyses  
 Water

Date	Well	TPH as Kerosene	TOG	EPA as Gasoline	Benzene	Toluene	EPA Benzene	Xylenes
5/23/95	MW1	--	ND	100♦	ND	ND	ND	ND
	MW2	--	ND	ND	ND	ND	ND	ND
	MW3	--	ND	ND	ND	ND	ND	ND
	MW4	--	ND	ND	ND	ND	ND	ND
	MW5	--	ND	ND	ND	ND	ND	ND
2/25/95	MW1	--	ND	81♦	ND	ND	ND	ND
	MW2	--	ND	ND	ND	ND	ND	ND
	MW3	--	ND	ND	ND	ND	ND	ND
	MW4	--	ND	ND	ND	ND	ND	ND
	MW5	--	ND	ND	ND	ND	ND	ND
6/29/93	MW1*	--	ND	76♦	ND	ND	ND	ND
	MW2*	--	ND	ND	ND	ND	ND	ND
	MW3*	--	ND	ND	ND	ND	ND	ND
	MW4*	--	ND	ND	ND	ND	ND	ND
	MW5*	--	ND	ND	0.64	ND	ND	ND

♦ Sequoia Analytical Laboratory reported that the hydrocarbons detected did not appear to be gasoline.

\* TPH as diesel and all EPA method 8270 constituents were non-detectable.

\*\* TOG was sampled on September 8, 1995, instead of August 24, 1995. Furthermore, the analytical results of the ground water samples (toluene and xylenes) collected on August 24, 1995, were inconsistent with the previous analytical results for these wells.

+ Sequoia Analytical Laboratory reported that the hydrocarbons detected appeared to be a kerosene and non-kerosene mixture.

ND = Non-detectable.

-- Indicates analysis was not performed.

Results are in micrograms per liter (µg/L), except for TOG, which is in milligrams per liter (mg/L).

**Table 10**  
 Summary of Laboratory Analyses

~~SO<sub>2</sub>~~ WATER

Date	Sample Number	1,1-Dichloro-ethane	Tetrachloro-ethene	Trichloro-ethene	Vinyl Chloride	Chloroform
5/29/97	MW1	WELL WAS INACCESSIBLE				
	MW2	ND	18	0.88	ND	1.4
	MW4	WELL WAS INACCESSIBLE				
	MW5	10	86	17	ND	ND
2/27/97	MW1	ND	450	10	ND	ND
&	MW2♦♦	ND	17	68	ND	2.0
3/19/97	MW4	WELL WAS INACCESSIBLE				
	MW5	0.57	14	1.4	ND	ND
11/25/96	MW1	ND	18	60	ND	2.6
	MW2	ND	16	0.54	ND	2.8
	MW4	WELL WAS INACCESSIBLE				
	MW5	ND	ND	ND	ND	0.8
8/30/96	MW1	2.1	ND	4.4	ND	ND
	MW2	ND	10	1.1	ND	ND
	MW4	WELL WAS INACCESSIBLE				
	MW5♦	7.0	12	6.0	ND	ND
5/21/96	MW1+	4.1	ND	4.8	ND	53
	MW2++	ND	10	ND	ND	16
	MW3	WELL WAS DESTROYED ON FEBRUARY 29, 1996				
	MW4	WELL WAS INACCESSIBLE				
	MW5+++	14	15	8.3	ND	13
2/19/96	MW1	ND	8.7	ND	ND	2.9
	MW2	ND	8.0	ND	ND	2.6
	MW3	ND	ND	ND	ND	ND
	MW4	WELL WAS INACCESSIBLE				
	MW5	2.1	9.3	1.9	ND	ND
10/6/95	MW1	1.7	19	3.7	ND	1.3
	MW2	ND	8.9	1.0	ND	5.9
	MW3	5.7	13	6.2	ND	1.1
	MW4	5.4	12	6.1	ND	0.53
	MW5	9.1	8.2	5.3	ND	ND
8/24/95	MW1	3.4	240	5.0	ND	3.2
	MW2*	ND	28	1.1	ND	15
	MW3**	5.1	50	9	ND	0.78
	MW4	ND	9.7	ND	ND	2.4
	MW5**	17	49	11	ND	ND
8/26/97	MW-1	WELL WAS INACCESSIBLE				
	MW-2	ND	18	0.88	ND	1.4
	MW-4	WELL WAS INACCESSIBLE				
	MW-5	WELL OBSTRUCTED AT 420 FT R...				



**Table 30**  
 Summary of Laboratory Analyses  
 Soil WATER

Date	Sample Number	cis-1,2-Dichloroethene	Tetrachloroethene	Trichloroethene	Vinyl Chloride	Chloroform
5/23/95	MW1	ND	450	ND	ND	ND
	MW2	ND	45	ND	ND	ND
	MW3	5.1	74	9.1	ND	ND
	MW4	ND	8.8	ND	ND	ND
	MW5	16	58	11	ND	ND
2/25/95	MW1	ND	360	ND	ND	ND
	MW2	ND	41	1.9	ND	ND
	MW3	6.9	52	9.4	ND	ND
	MW4	ND	6.4	ND	ND	ND
	MW5	8.3	25	6.6	ND	ND
6/29/93	MW1	ND	250	ND	ND	ND
	MW2	ND	78	ND	ND	ND
	MW3	5.5	130	11	ND	ND
	MW4	ND	16	0.68	ND	ND
	MW5	24	17	5.9	3.0	ND


All EPA method 8010 constituents were non-detectable, except for the above compounds.

- ♦ Trans-1,2-Dichloroethene was detected at a concentration of 0.60 µg/L.
- ♦♦ Chloroform was detected at a concentration of 7.0 µg/L.
- \* 1,1,1-Trichloroethane was detected at a concentration of 0.73 µg/L.
- \*\* Trans-1,2-Dichloroethene was detected at concentrations of 0.59 µg/L and 0.76 µg/L in MW3 and MW5, respectively.
- + Bromodichloromethane was detected at 19 µg/L and Dibromochloromethane at 5.7 µg/L.
- ++ Bromodichloromethane was detected at 5.8 µg/L and Dibromochloromethane at 3.3 µg/L.
- +++ Bromodichloromethane was detected at 5.0 µg/L and Dibromochloromethane at 4.3 µg/L.
- ND = Non-detectable.

Results are in micrograms per liter (µg/L), unless otherwise indicated.

APPENDIX G

CONCENTRATION VERSUS TIME AND TREND GRAPHS AND  
DEGRADATION CALCULATIONS




**Graph G-1**

FORMER CHEVRON STATION 9-3864  
 5101 TELEGRAPH AVENUE  
 OAKLAND, CALIFORNIA



C-3: TPHg AND BENZENE  
 CONCENTRATIONS OVER  
 TIME



**Graph G-2**

FORMER CHEVRON STATION 9-3864  
 5101 TELEGRAPH AVENUE  
 OAKLAND, CALIFORNIA



MW-3: TPHg AND BENZENE  
 CONCENTRATIONS OVER  
 TIME


PREDICTED TIME TO REACH TPHg ESL IN MW-3  
 FORMER CHEVRON STATION 9-3864  
 5101 TELEGRAPH AVENUE  
 OAKLAND, CALIFORNIA

$$y = b e^{ax} \quad \implies \quad x = \ln(y/b) / a$$

where: y = concentration in  $\mu\text{g/L}$                       a = decay constant  
 b = concentration at time (x)                      x = time in days

Given	Constituent	Total Petroleum Hydrocarbons as Gasoline (TPHg)
ESL:	y	100
Constant:	b	5.00E+10
Constant:	a	-4.00E-04
Starting date for current trend:		6/24/1995

Calculate		
Attenuation Half Life (years):	$(-\ln(2)/a)/365.25$	4.74
Estimated Date to Reach ESL:	$(x = \ln(y/b) / a)$	Feb 2037



FORMER CHEVRON STATION 9-3864  
 5101 TELEGRAPH AVENUE  
 OAKLAND, CALIFORNIA



MW-3: TPHg CONCENTRATION vs. TIME

APPENDIX H

PREVIOUS RISK ASSESSMENT RESULTS

Table 8-1. Comparison of Calculated Health-Based Remediation Goals to Site-Related Concentrations, Former Chevron Service Station #9-3864, 5101 Telegraph Avenue, Oakland, California.

Constituent	Calculated HBGs				Site-Related Concentrations			Does Site Exceed HBG ?
	Construction Worker	Adult Resident	Child Resident	Minimum HBG	Current Data		Historical Maximum	
					UCL	Maximum		
<u>SOIL</u>								
<u>VOCs</u>								
Benzene	20	0.53	0.56	0.53	0.022	0.069	NA	No
Ethylbenzene	800	2,400	480	480	0.39	2.5	NA	No
Toluene	1,300	960	190	190	0.34	2.7	NA	No
Xylenes	700	8,100	1,700	700	0.93	5.5	NA	No
<u>TPH</u>								
TPH as diesel	5,600	14,000	1,900	1,900	#N/A	78	NA	No
TPH as gasoline	63,000	11,000	1,700	1,700	130	980	NA	No
<u>Metal</u>								
Lead *	340	1,600	200	200	0.43	0.60	NA	No
<u>GROUND WATER</u>								
<u>VOCs</u>								
Benzene	NE	190	200	190	0.11	0.13	0.34	No
Ethylbenzene	NE	89,000	19,000	19,000	0.011	0.012	0.019	No
Toluene	NE	87,000	19,000	19,000	0.025	0.026	0.17	No
Xylenes	NE	20,000	4,400	4,400	0.026	0.030	0.083	No
TPH as Gasoline	NE	310	70	70	6.5	7.1	7.1	No

Footnotes appear on page 2.

Table 8-1. Comparison of Calculated Health-Based Remediation Goals to Site-Related Concentrations, Former Chevron Service Station #9-3864, 5101 Telegraph Avenue, Oakland, California.

---

Soil concentrations are reported in milligrams per kilogram (mg/kg); ground-water concentrations are reported in milligrams per liter (mg/L).

*	HBGs for lead were calculated using the biokinetic/uptake model.
HBG	Health-based remediation goal.
NA	Historical maximum concentrations are not relevant for soil, only for ground water.
NE	Not evaluated. Ground water exposure was not evaluated for the construction worker since the residential exposure is a more significant potential exposure scenario.
TPH	Total petroleum hydrocarbons.
UCL	Upper 95 percent confidence limit on the mean.
VOCs	Volatile organic compounds.