

FIRST QUARTER 2002  
GROUNDWATER SAMPLING REPORT/UPDATE STATUS  
WITH  
WASTEWATER DISCHARGE REPORT (APPENDIX I)

AT

FORMER DESERT SITE DP 793  
4035 PARK BLVD.  
OAKLAND, CA.

FOR

DESERT PETROLEUM

**March 13, 2002**

BY

-WEGE-  
WESTERN GEO-ENGINEERS  
1386 E. BEAMER STREET  
WOODLAND, CALIFORNIA 95776  
(530) 668-5300

APR 15 2002

## TABLE OF CONTENTS

1.0 SITE LOCATION AND NUMBERS.....	3
2.0 LOCAL GEOLOGY.....	3
2.1 Geomorphology.....	3
2.2 Stratigraphy.....	3
2.1.1 Station Property.....	3
2.1.2 Backyard Sewer Lateral Route.....	4
2.1.3 Brighton Avenue.....	4
3.0 COLLECTION AND ANALYSIS OF GROUNDWATER SAMPLES.....	4
3.1 Depth to Water Measurements.....	4
4.0 RESULTS OF QUARTERLY GROUNDWATER MONITORING.....	4
4.1 Groundwater Gradient and Flow Direction.....	4
4.2 Results of Certified Analysis of Groundwater Samples.....	5
5.0 WEEKLY PURGING OF RECEPTOR TRENCH.....	6
6.0 PUMPING ON-SITE WELL RS-5.....	6
7.0 BIODEGRADATION OF HYDROCARBONS.....	6
7.1 Dissolved Oxygen.....	7
7.2 Sulfate.....	7
7.3 Nitrate.....	7
7.4 Ferrous Iron.....	7
8.0 SUMMARY.....	8
9.0 LIMITATIONS.....	9

### List of Tables

1. Groundwater Elevation and Certified Analytical Results
2. Groundwater Elevations and Electron Acceptor Results
3. Wastewater Discharge
4. Groundwater Removal
5. Pounds of Hydrocarbons

### List of Figures

1. Area Base Map "Geotracker"
2. Portion of USGS Oakland East 7.5 Minute Quadrangle
3. Sample Location Figure
4. Groundwater Gradient, February 19, 2002
5. Groundwater Plume, TPHg & Benzene, August 26, 1999
6. Groundwater Plume, TPHg & Benzene, May 31, 2001
7. Groundwater Plume, TPHg & Benzene, December 18, 2001
8. Groundwater Plume, TPHg & Benzene, February 19, 2002.
9. Cross Section From Site Along Sewer Route Backyards
10. Cross Section of Receptor Trench, Brighton Avenue

Table of Contents Continued

List of Appendices

- A. METHODS AND PROCEDURES, QA/QC WITH FIELD NOTES
- B. GROUNDWATER ELEVATION CHART
- C. LABORATORY REPORT
- D. MtBE GRAPH, TPHg AND BENZENE CHARTS - WELLS
- E. HACK SPECTROPHOTOMETER FIELD TEST METHODS
  - 7. Dissolved Oxygen, December 18, 2001
  - 7-1 Dissolved Oxygen, August 26, 1999
  - 8 Sulfate in Groundwater, December 18, 2001
  - 8-1 Sulfate in Groundwater, August 26, 1999
  - 9 Nitrate in Groundwater, December 18, 2001
  - 9-1 Nitrate in Groundwater, August 26, 1999
  - 10 Ferrous Iron in Groundwater, December 18, 2001
  - 10-1 Ferrous Iron in Groundwater, August 26, 1999
- F. NOVEMBER 13, 2001 MEETING
- G. REGENESIS ORC CALCULATIONS
- H. WEGE HYDROGEN PEROXIDE CALCULATIONS
- I. WASTEWATER DISCHARGE REPORT



**WESTERN  
GEO-ENGINEERS**  
CALIF. CONTRACTOR #513857  
REGISTERED GEOLOGISTS

1386 EAST BEAMER STREET  
WOODLAND CA 95776-6003  
(530) 668-5300.  
FAX (530) 662-0273  
wege@mother.com

Mr. Bill Thompson  
Desert Petroleum  
P.O. Box 1601  
Oxnard, California 93032  
(805) 644-6784 FAX (805) 654-0720

March 13, 2002

Dear Mr. Thompson:

The following report documents the first quarter 2002 sampling at DP793, 4035 Park Blvd., Oakland, California. Also included is a discussion on the present site conditions and the cost to enhance dissolved oxygen within the groundwater plume.

## **1.0 SITE LOCATION AND NUMBERS**

Former Desert Petroleum #793 is a non-active service station, located on the northwest corner of the intersection of Park Boulevard and Hampel Street at 4035 Park Blvd., Oakland, California (Figure 1). The site is located in projected section 32; T1S; R3W; MDB&M at an approximate elevation of 210 feet above mean sea level (Figure 2).

East Bay Municipal Utility District - Sewer Discharge Permit #50435501  
Alameda County Local Oversight STID 1248  
San Francisco Bay Regional Board (Region 2) Case # 01-0170  
Facility/Leak Site ID# T0600100158

## **2.0 LOCAL GEOLOGY**

### ***2.1 Geomorphology***

The site is located on the western slope of the Berkeley Hills. The Berkeley Hills are a northwest-southeast trending range within the Coastal Range Province of California. Erosion of the Coastal Ranges has filled the valleys within and bordering the Coastal Range with sequences of gravels, silts, sands, and clays.

### ***2.2 Stratigraphy***

#### **2.1.1 Station Property**

The native soil from surface to 13 feet below ground surface (BGS) consists of dark brown silty clay. The dark brown clay is underlain by light brown stiff clay that includes subrounded to rounded metavolcanic gravel. This clay extends to approximately 23 feet BGS at the northwest

corner of the site. A fine to medium sand, clayey sand, and silty sand underlies the gravel and clay.

### 2.1.2 Backyard Sewer Lateral Route

Assessments performed along the sewer lateral as it leaves the site and routes through the residential area towards Brighton Avenue show the subsurface to consist of fill from a couple of inches thick to two feet thick. Beneath the fill is a sequence of clay formations that vary from light brown to dark gray to approximately the 6 foot depth. Silty clay then extends to approximately the 14-foot depth. Beneath the silty clay is sand with occasional gravel. This sand is 11 feet thick at RS5 and is underlain by silty clay, see Figure 11.

### 2.1.3 Brighton Avenue

Construction of the receptor trench along the eastern curb area of Brighton Avenue revealed two separate sequences of lithology. North of the storm drain catch basin the sequence consists of; clay to the four foot depth, silty clay to the seven foot depth, fine silty sand to the 9 foot depth, medium sand to the 10 foot depth, silty caly to the 11 ½ foot depth, gravel to the 12 foot depth underlain by clay to the 16 foot depth. South of the storm catch basin is a sequence of silty clays and clays to depth, see Figure 12.

## 3.0 COLLECTION AND ANALYSIS OF GROUNDWATER SAMPLES

Groundwater samples were collected on February 19, 2002. Samples were analyzed for Total Petroluem Hydrocabons as gasoline, Benzene, Toluene, Ethylbenzene, Xylenes and Methyl tert-Butal Alcohol using EPA method 8260B, see Table 1. Figure 3 shows the positions of the groundwater monitoring wells, the receptor trench and previous sample locations.

### 3.1 *Depth to Water Measurements*

On February 19, 2002 depth to water was measured at each well using a product/water interface probe. Measurements are referenced to the surveyed elevation at the top of casing at each well. Table 1 shows the elevation of groundwater with respect to mean sea level for all wells through February 19, 2002.

## 4.0 RESULTS OF QUARTERLY GROUNDWATER MONITORING

### 4.1 *Groundwater Gradient and Flow Direction*

Figure 4 shows the groundwater elevation gradients and flow direction that were derived from the depth to water measurements of the monitor wells on February 19, 2002, prior to purging the wells

for sampling, see Table 1 and Appendix A. On February 15, 2001 submersible pump was placed into onsite well RS-5 to try and capture contaminated groundwater beneath the site and adjoining properties. The pump rate was set at approximately 2 gpm. As shown on groundwater elevation chart generated for each well, pumping from RS5 lowered the water levels in RS-8 and RS-10, see Appendix B. Table 1 shows the groundwater elevations for the wells during the assessment of this site.

The current flow direction is northwest to west. The hydraulic gradient averages 0.09 feet/linear foot downgradient of RS-8 to the receptor trench well T1, see Figure 4. The present flow direction and hydraulic gradient are consistent with previous determinations by WEGE. Also evident on Figure 4 is the rain induced groundwater high mound that accumulates in the previously excavated former UST and product dispensing areas.

#### ***4.2 Results of Certified Analysis of Groundwater Samples***

The results of the certified analyses of groundwater samples collected on February 19, 2002 are shown in Table 1.

TPH-G concentrations in water samples from the eight monitor wells, the receptor trench well and three recovery wells ranged from a maximum of 64 mg/l at trench well T1, to below laboratory lower detection limits of 50 ug/L in wells MW1, RS2, RS6, RS9, RS10, R1 and R3 respectively.

Benzene concentrations ranged from a maximum of 8.6 mg/L in T1 to below the laboratory lower detection limits (0.5 ug/L) at wells MW1, RS2, RS6, RS9, RS10, R1 and R3, see Appendix C - Laboratory Report.

Analysis results for Oxygenant Methyl-t-Butyl Ether (MTBE) was below the laboratory lower detection limit in wells MW1, RS2, RS5, RS6, RS8, RS9, RS10, R1, R2, and R3. **The wells located within Brighton Street, RS7 and the trench well T1, contained 11 and 55 ug/L MTBE respectively.** This indicates that the MtBE source(s) are the cars parked along Brighton Street. During the September 16, 1998 all Fuel Oxygenants; MTBE, Di-isopropyl Ether (DIPE), tertiary Butyl Alcohol (TBA), Ethyl-t-Butyl Ether (ETBE) and t-Amyl Methyl Ether (TAME) were confirmed with EPA Method 8260. These analytes were below laboratory lower detection limits.

Figure 5 (August 26, 1999) shows the lateral distribution of the hydrocarbon plume with benzene distinction in groundwater prior to pumping from RS-5 and T1.

Figure 6 (May 31, 2001) shows the lateral distribution of the hydrocarbon plume with benzene distinction in groundwater during pumping from RS-5 and T1.

Figure 7 (December 18, 2001) shows the lateral distribution of the hydrocarbon plume with benzene distinction in groundwater as determined from groundwater samples after termination of pumping from RS-5 and T1.

Figure 8 (February 19, 2002) shows the most recent lateral distribution of the hydrocarbon plume with benzene distinction in groundwater as determined from groundwater samples, no pumping from RS-5 and T1.

Appendix D contains charts developed for wells MW1, RS2, RS5, RS6, RS7, RS8, RS9, RS10 and trench well T1 showing TPHg & Benzene concentration reductions with time, with the exception of T1 which showed an increase in both TPHg and Benzene for the February 19, 2002 sampling.

## **5.0 WEEKLY PURGING OF RECEPTOR TRENCH**

Commencing on May 4, 2000, weekly pumping of the receptor trench has been performed for approximately 4 hours per week, see Table 3. During purging the depth to water within the trench is lowered an average of one foot. Immediately after purging ceases, the water level in the trench recovers to its original depth. Weekly purging of the receptor trench was suspended on July 19, 2001 at the request of Desert Petroleum. 62,511 gallons of contaminated groundwater had been removed from the trench, processed through two, in series, activated carbon water scrubs and discharged to the sanitary sewer, see Table 3.

## **6.0 PUMPING ON-SITE WELL RS-5**

On February 15, 2001 a submersible pump with a pump bypass was placed into RS-5. The pump rate was adjusted to 1.5 gpm and allowed to continuously pump from RS-5 for one week. 3223 gallons were pumped from RS-5 through the two in series water carbon units and discharged to the sewer. On February 22, 2001 the pump was inspected and showed a slimy growth covering the pump and discharge line that was below the water level. The pump was cleaned and placed back into RS-5 and continued to discharge from RS-5 through the water carbon units to sewer until July 19, 2001. On July 19, 2001 Desert Petroleum requested suspension of further pumping at the site. The pump was removed and the site secured. From February 15 through July 19, 2001, 78,919 gallons of gasoline contaminated groundwater was recovered from RS-5 and treated through carbon before being discharged to the sewer, see Table 3.

The pumping from RS-5 lowered the groundwater at this well by at least 15 feet, when compared to the previous water measurements. This created a cone of influence out to offsite wells RS-8 and RS-10, see Chart - Appendix B. Recirculating the pumped groundwater, before it leaves the well (RS-5) has increased the dissolved oxygen in RS-5 from 0.7 mg/L (August 26, 1999) to 3.1 mg/L (March 8, 2001). This should aid in the biodegradation of the hydrocarbon plume, see Table 2.

## **7.0 BIODEGRADATION OF HYDROCARBONS**

During the December 18, 2001 sampling of wells, field measurements were obtained to determine the availability of electron receptors to aid in the natural attenuation of the hydrocarbon plume. Along with pH, temperature and electrical conductivity, dissolved oxygen, nitrate, sulfate and ferrous iron were also measured. Water samples were obtained after the wells were purged and allowed to recovery and analyzed in the field using a Hach DR/2000 Spectrophotometer, see Appendix E. The following methods were used:

Dissolved Oxygen, high range (0 to 13 mg/L O<sub>2</sub>) - Method 8166 for water and wastewater.  
Nitrate, high range (0 to 30 mg/L NO<sub>3</sub>) - Method 8039 for water, wastewater and seawater.  
Sulfate, (0 to 70 mg/L SO<sub>4</sub>) - Method 8051 for water and wastewater.  
Ferrous Iron, (0 to 3.00 mg/L Fe<sub>2</sub>) - Method 8146 for water, wastewater and seawater.

Table 2 represents the results of electron acceptor field analysis obtained December 18, 2001 compared to results obtained August 26, 1999.

### ***7.1 Dissolved Oxygen***

Readings for dissolved oxygen obtained prior to pumping the receptor trench and RS5 indicated two areas of oxygen depletion (<1 mg/L), the entire north half of the site (4035 Park Avenue) and the area excavated for the receptor trench along the eastern curb of Brighton Avenue, see Figure 7-1. Readings obtained during the December 18, 2001 monitoring round show that dissolved oxygen has increased substantially and even exceeds 5 mg/L in the over-excavated area on site. The lowest Dissolved Oxygen level encountered is associated with well RS5 at 1.4 mg/L, compared to 0.7 mg/L at RS5 in August 1999. All other dissolved oxygen measurements were at 2.5 mg/L or greater, see Appendix E - Figure 7.

### ***7.2 Sulfate***

Appendix E - Figure 8 represents sulfate measurements obtained during the December 18, 2001 quarterly monitoring. Comparing sulfate measurements obtained in August 1999, Appendix E - Figure 8-1, to the December 2001 measurements, Appendix E-Figure 8, the sulfate has been depleted at the receptor trench and beneath Brighton Avenue, but is being replenished at well location RS8.

### ***7.3 Nitrate***

Appendix E-Figure 9 represents nitrate measurements obtained during the December 18, 2001 quarterly monitoring. Comparing nitrate measurements obtained in August 1999, Appendix E-Figure 9-1, to the December 2001 measurements, Appendix E-Figure 9, the nitrate is being replenished all along the petroleum plume area.

### ***7.4 Ferrous Iron***

Appendix E-Figure 10 represents ferrous iron measurements obtained during the December 18, 2001 quarterly monitoring. The measurements obtained in August 1999, Appendix E-Figure 10-1, and the December 2001 measurements, Appendix E-Figure 10, indicate that ferrous iron is oxidized, as the site becomes more aerobic.



## 8.0 SUMMARY

Since the installation and weekly purging of the receptor trench (T1) the TPHg concentrations in down gradient wells RS-7 and RS-9 have decreased, see Table 1 with charts RS-7. The weekly purging of the receptor trench was limited to a maximum daily discharge of 5 gpm, thus removing approximately 1200 to 2000 gallons per week. Although this does lower the water level in the trench, after pumping has ceased the water level rebounds to its original depth allowing for the gradient migration of TPHg contaminated groundwater to continue.

Pumping from RS-5 has shown to create a cone of influence off-site downgradient out to RS-8 and RS-10. Pumping has increased the dissolved oxygen in RS-5 and hydrocarbon concentrations have declined in R1, R3, RS-5, RS-8 and RS-10.

The lowest hydrocarbon concentrations were observed while the weekly pumping of the trench well and the continuous pumping of RS5 was occurring, Figure 6 (May 31, 2001). The most recent sampling, Figure 8 (February 19, 2001) shows a continue decrease in hydrocarbons upgradient, at the site, but an increase in hydrocarbon concentrations associated with the receptor trench and Brighton Avenue excavation wells, T1 and RS7 respectively. The most down gradient well, RS9 is now below laboratory lower detection limits, indicating a barrier for lateral migration along Brighton Avenue.

Previous sampling, September 2, 1999, showed that aerobic bacteria (hydrocarbon degraders) exist in the groundwater associated with the hydrocarbon plume. A workplan to augment the groundwater with oxygen (air sparging) and nutrients (phosphate and ammonium sulfate) dated August 29, 2000 was presented with the August 29, 2000, Third Quarter 2000 report. This workplan along with the May 31, 2001 conditions were discussed during a meeting at Alameda County Health that involved Mr. Thompson, Desert Petroleum, Mr. Seery, Alameda County Health and Mr. Converse, Western Geo-Engineers on November 13, 2001. The meeting concluded that nutrient augmentation was not necessary at this time, but enhanced dissolved oxygen was needed. Due to neighborhood concerns, i.e. residential homes and apartments, air sparging and/or using a mechanical delivery device would create too much noise and a more passive oxygen delivery system was warranted, i.e. hydrogen peroxide or Oxygen Release Compound (ORC), see Appendix F. An amended workplan was presented in Appendix G of the 4<sup>th</sup> Quarter 2001 report, dated January 7, 2002 and suggested that ORC would be the most beneficial means of enhancing dissolved oxygen in the groundwater plume. Western Geo-Engineers then requested Regensis Inc. to perform a basic model using ORC to determine how to apply and the amount needed. The Regensis model indicated that a one-time application (would last approximately one year) of approximately 9,690 pounds of ORC would be needed, at a cost of \$77,520.00 for materials, which does not include installation costs. Upon receipt of the Regensis model, WEGE projected how much hydrogen peroxide would be necessary to increase the dissolved oxygen in the plume from 2 mg/L to 8 mg/L. This simple model indicated that 18 gallons of 35% solution hydrogen peroxide would be necessary per application, at a cost of \$1,160.00 per monthly application or \$13,920.00 for one year, see Appendix H.

Further communications from Mr. Scott Seery with Mr. Converse occurred during the week of February 25 - March 1, 2002. Mr. Seery suggested another meeting to discuss remediation options prior to approving the amended workplan presented with the January 7, 2002 report.

## 9.0 LIMITATIONS

This report is based upon the following:


- A. The observations of field personnel.
- B. The results of laboratory analyses performed by a state certified laboratory.
- C. Referenced documents.
- D. Our understanding of the regulations of the State of California, Alameda County and the City of Oakland.
- E. Changes in groundwater conditions can occur due to variations in rainfall, temperature, local and regional water use, and local construction practices.
- F. In addition, variations in the soil and groundwater conditions could exist beyond the points explored in this investigation.

State Certified Laboratory analytical results are included in this report. This laboratory follows EPA and State of California approved procedures; however, WEGE is not responsible for errors in these laboratory results. Western Geo-Engineers is a corporation under California Registered Geologist #3037 and/or Contractors License #513857. The services performed by Western Geo-Engineers have been conducted in a manner consistent with the level of care and skill ordinarily exercised by members of our profession currently practicing under similar conditions in the State of California and the Oakland area. Our work and/or supervision of remediation and/or abatement operations, active or preliminary, at this site is in no way meant to imply that we are owners or operators of this site. Known or suspected contamination of soil and/or groundwater must be reported to the appropriate agencies in a timely manner. No other warranty, expressed or implied, is made.

Sincerely,



George Converse  
Geologist



Jack E. Napper  
Ca. Reg. Geologist #3037

cc: Mr. Scott O. Seery, Alameda County Health (510) 567-6783  
Mr. Leroy Griffin, Oakland Fire Dept.

TABLE 1  
 GROUNDWATER ELEVATIONS AND CERTIFIED ANALYTICAL LABORATORY RESULTS FROM WATER SAMPLES  
 DESERT PETROLEUM, INC. SITE #793  
 4035 PARK BOULEVARD, OAKLAND, CALIFORNIA

ID#	(All concentrations in parts per billion [ug/L. ppb]) (AMSL = Above mean sea level)									
	DATE SAMPLED	WELL CASING ELEVATION (FEET AMSL)	DEPTH TO GROUND WATER (FEET)	GROUND WATER ELEVATION (FEET AMSL)	TPH-G (UG/L)	BENZENE (UG/L) (1)	TOLUENE (UG/L) (150)	ETHYL-BENZENE (UG/L) (300)	XYLENES (UG/L) (1800)	MTBE (UG/L) (13)
(CALIFORNIA PUBLIC HEALTH GOAL)										
RS-1	12/14/89	228.15	24.25	203.9	19000	2600	2700	200	1200	
RS-1	12/90				15000	3500	330	170	760	
RS-1	2/91				6900	910	200	39	540	
RS-1	6/91				1600	56	180	12	26	
RS-1	9/91				4100	730	7.6	5.1	24	
RS-1	12/91				8300	950	160	71	190	
RS-1	11/9/92	228.15	17.05	211.1	1700	730	9.6	16	14	
RS-1	4/7/94	228.15	13	215.15	860	84	12	16	110	
RS-1	6/19/94	228.15	13.37	214.78	1400	150	12	52	87	
RS-1	9/17/94	228.15	16.33	211.82	310	30	1.8	2.8	3.9	
RS-1	3/12/95	228.15	4.66	223.49	ND	ND	ND	ND	ND	
DESTROYED BY OVER-EXCAVATION OF UST-DISPENSER AREAS ( 8/14/95)										
REPLACED WITH MW-1 9/5/95.										
MW-1	10/4/95	229.5	12.38	217.12	ND	ND	ND	ND	ND	
MW-1	12/21/95	229.5	13.40	216.1	< 50	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5
MW-1	03/27/96	229.5	5.53	223.97	< 50	< 0.5	< 0.5	< 0.5	< 2	< 50
MW-1	06/11/96	229.5	9.02	220.48	< 50	< 0.5	< 0.5	< 0.5	< 2	< 50
MW-1	09/04/96	229.5	11.84	217.66	< 50	< 0.5	< 0.5	< 0.5	< 2	< 5
MW-1	12/11/96	229.5	12.98	216.52	< 50	< 0.5	0.9	< 0.5	< 1	< 0.5
MW-1	2/21/97	229.5	9.50	220	< 50	< 0.5	0.9	< 0.5	< 1	< 0.5
MW-1	5/28/97	229.5	11.18	218.32	< 50	3	3	< 0.5	< 1	< 0.5
MW-1	9/2/97	229.5	13.00	216.5	< 50	5	< 0.5	< 0.5	< 1	< 0.5
MW-1	11/24/97	229.5	14.12	215.38	< 50	5	< 0.5	< 0.5	< 1	< 0.5
MW-1	2/25/98	229.5	6.41	223.09	< 50	< 0.5	< 0.5	< 0.5	< 1	< 0.5
MW-1	7/8/98	229.5	7.28	222.22	< 50	< 0.5	< 0.5	< 0.5	< 1	< 1
MW-1	9/16/98	229.5	10.96	218.54	< 50	< 0.5	< 0.5	< 0.5	< 1	< 1
MW-1	11/24/98	229.5	12.24	217.26	52	2.3	5.2	< 0.5	5.4	11
MW-1	2/23/99	229.5	7.14	222.36	< 50	< 0.5	5	< 0.5	< 1	< 0.5
MW-1	5/5/99	229.5	7.00	222.5	< 50	2	< 0.5	< 0.5	< 1	8
MW-1***	8/26/99	229.5	11.41	218.09	< 50	4.1	< 0.5	< 0.5	< 1	< 1
MW-1	11/10/99	229.5	13.27	216.23	< 50	< 0.5	< 0.5	< 0.5	< 1	< 0.5
MW-1	2/9/00	229.5	13.76	215.74	< 50	< 0.5	< 0.5	0.5	< 1	0.5
MW-1	6/30/00	229.5	10.63	218.87	< 50	< 0.5	< 0.5	< 0.5	< 1	< 0.5
MW-1	8/8/00	229.5	11.77	217.73	62	1	2	< 0.5	2	< 0.5
MW-1	11/16/00	229.5	13.33	216.17	< 50	< 0.5	< 0.5	< 0.5	< 1	< 0.5
MW-1	3/8/01	229.5	12.30	217.2	< 50	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5
MW-1	5/31/01	229.5	11.88	217.62	< 50	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5
MW-1	12/18/01	229.5	13.74	215.76	< 50	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5
MW-1	2/19/02	229.5	14.42	215.08	< 50	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5

TABLE 1  
 GROUNDWATER ELEVATIONS AND CERTIFIED ANALYTICAL LABAORATAORY RESULTS FROM WATER SAMPLES  
 DESERT PETROLEUM, INC. SITE #793  
 4035 PARK BOULEVARD, OAKLAND, CALIFORNIA

ID#	(All concentrations in parts per billion [ug/L, ppb]) (AMSL = Above mean sea level)									
	DATE SAMPLED	WELL CASING ELEVATION (FEET AMSL)	DEPTH TO GROUND WATER (FEET)	GROUND WATER ELEVATION (FEET AMSL)	TPH-G (UG/L)	BENZENE (UG/L) (1)	TOLUENE (UG/L) (150)	ETHYL-BENZENE (UG/L) (300)	XYLENES (UG/L) (1800)	MTBE (UG/L) (13)
RS-2	12/14/89	227.39								
RS-2	6/19/94	227.39	10.89	216.50						
RS-2	3/12/95	227.39	5.26	222.13	ND	ND	ND	ND	ND	
RS-2	10/4/95	227.39	15.05	212.34	ND	ND	ND	ND	ND	
RS-2	12/21/95	227.39	9.95	217.44	< 50	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5
RS-2	03/27/96	227.39	6.28	221.11	< 50	< 0.5	< 0.5	< 0.5	< 2	< 50
RS-2	06/11/96	227.39	8.00	219.39	< 50	1.2	2.8	< 0.5	< 2	< 50
RS-2	09/04/96	227.39	9.89	217.50	< 50	< 0.5	< 0.5	< 0.5	< 2	< 5
RS-2	12/11/96	227.39	8.38	219.01	< 50	< 0.5	< 0.5	< 0.5	< 1	6
RS-2	2/21/97	227.39	6.96	220.43	< 50	< 0.5	< 0.5	< 0.5	< 1	< 0.5
RS-2	5/28/97	227.39	10.02	217.37	< 50	3	3	< 0.5	< 1	< 0.5
RS-2	9/2/97	227.39	11.46	215.93	< 50	< 0.5	< 0.5	< 0.5	< 1	< 0.5
RS-2	11/24/97	227.39	10.43	216.96	< 50	< 0.5	1	< 0.5	3	< 0.5
RS-2	2/25/98	227.39	3.57	223.82	< 50	< 0.5	< 0.5	< 0.5	< 1	< 0.5
RS-2	7/8/98	227.39	8.83	218.56	< 50	< 0.5	< 0.5	< 0.5	< 1	< 1
RS-2	9/16/98	227.39	10.60	216.79	< 50	< 0.5	< 0.5	< 0.5	< 1	< 1
RS-2	11/24/98	227.39	13.27	214.12	140	2.8	19	2.6	3.3	15
RS-2	2/23/99	227.39	4.06	223.33	< 50	< 0.5	< 0.5	< 0.5	< 1	< 0.5
RS-2	5/5/99	227.39	7.70	219.69	< 50	0.7	< 0.5	< 0.5	< 1	6
RS-2***	8/26/99	227.39	11.42	215.97	200	15	23	1.7	23	9
RS-2	11/10/99	227.39	15.94	211.45	< 50	< 0.5	< 0.5	< 0.5	< 1	< 0.5
RS-2	2/9/00	227.39	8.91	218.48	< 50	< 0.5	< 0.5	< 0.5	< 1	< 0.5
RS-2	6/30/00	227.39	9.79	217.60	52	2	< 0.5	< 0.5	< 1	< 0.5
RS-2	8/8/00	227.39	10.71	216.68	60	< 0.5	< 0.5	< 0.5	< 1	< 0.5
RS-2	11/16/00	227.39	10.39	217.00	< 50	< 0.5	< 0.5	< 0.5	< 1	< 0.5
RS-2	3/8/01	227.39	6.62	220.77	< 50	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5
RS-2	5/31/01	227.39	10.09	217.30	< 50	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5
RS-2	12/18/01	227.39	6.99	220.40	< 50	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5
RS-2	2/19/02	227.39	8.08	219.31	< 50	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5

TABLE 1  
GROUNDWATER ELEVATIONS AND CERTIFIED ANALYTICAL LABAORATAORY RESULTS FROM WATER SAMPLES  
DESERT PETROLEUM, INC. SITE #793  
4035 PARK BOULEVARD, OAKLAND, CALIFORNIA

ID#	(All concentrations in parts per billion [ug/L. ppb]) (AMSL = Above mean sea level)									
	DATE SAMPLED	WELL CASING ELEVATION (FEET AMSL)	DEPTH TO GROUND WATER (FEET)	GROUND WATER ELEVATION (FEET AMSL)	TPH-G (UG/L)	BENZENE (UG/L) (1)	TOLUENE (UG/L) (150)	ETHYL-BENZENE (UG/L) (300)	XYLENES (UG/L) (1800)	MTBE (UG/L) (13)
RS-5	12/14/89	227.61	25.97	201.64	57000	3100	4300	670	3400	
RS-5	2/91	227.61	FLOATING PRODUCT							
RS-5	6/91	227.61	FLOATING PRODUCT							
RS-5	9/91	227.61	FLOATING PRODUCT							
RS-5	12/91	227.61	FLOATING PRODUCT							
RS-5	11/9/92	227.61	20.73	206.88	50000	650	4800	1100	15000	
RS-5	4/7/94	227.61	18.16	209.45	27000	5000	8700	550	2800	
RS-5	6/19/94	227.61	18.11	209.5	20000	2100	5300	470	2500	
RS-5	9/17/94	227.61	19.63	207.98	9300	230	340	110	700	
RS-5	3/12/95	227.61	14.54	213.07	93000	6400	2000	19000	10000	
RS-5	10/4/95	227.61	17.53	210.08	16000	420	2100	320	1800	
RS-5	12/21/95	227.61	17.47	210.14	48000	3500	9200	840	4800	56
RS-5	03/27/96	227.61	13.51	214.1	68000	4900	18000	1700	11000	< 3000
RS-5	06/11/96	227.61	14.25	213.36	66000	6300	20000	2100	12000	< 3000
RS-5	09/04/96	227.61	16.50	211.11	31000	2100	11000	1100	6800	400
RS-5	12/11/96	227.61	15.88	211.73	85000	7000	21000	1800	8900	570
RS-5	2/21/97	227.61	13.76	213.85	sh 100000	5000	22000	1700	7300	<0.5 *
RS-5	5/28/97	227.61	15.77	211.84	52000	4500	19000	2100	10000	<0.5 *
RS-5	9/2/97	227.61	17.47	210.14	38000	2200	9400	1300	5800	<0.5 *
RS-5	11/24/97	227.61	18.67	208.94	45000	4000	16000	1900	9700	<0.5 *
RS-5	2/25/98	227.61	10.53	217.08	160000	2700	31000	5300	28000	<0.5 *
RS-5	7/8/98	227.61	13.75	213.86	45000	2800	12000	2000	8500	<10 *
RS-5	9/16/98	227.61	15.80	211.81	49000	1400	7500	1700	8600	<5 *
RS-5	11/24/98	227.61	16.64	210.97	89000	5300	15000	2800	13000	<10 *
RS-5	2/23/99	227.61	12.36	215.25	19000	1900	11000	2500	4800	<25 *
RS-5	5/5/99	227.61	12.78	214.83	78000	2000	10000	3000	15000	540 *
RS-5***	8/26/99	227.61	16.06	211.55	35000	870	4000	1900	8300	<1 *
RS-5	11/10/99	227.61	17.54	210.07	40000	1000	5600	1800	8100	<0.5 *
RS-5	2/9/00	227.61	16.31	211.3	46000	1400	6900	2700	11000	<0.5 *
RS-5	6/30/00	227.61	15.15	212.46	37000	810	5200	2200	9100	<2.5 *
RS-5	8/8/00	227.61	16.10	211.51	14000	330	500	1400	6500	<0.5 *
RS-5	11/16/00	227.61	17.38	210.23	23000	430	2300	1100	4800	<0.5 *
RS-5	3/8/01	227.61	27.72	199.89	11000	360	260	140	1500	2.6 *****
RS-5	5/31/01	227.61	22.96	204.65	7500	26	11	38	470	<5 *****
RS-5	12/18/01	227.61	15.61	212	12000	610	1200	100	1500	<5 *****
RS-5	2/19/02	227.61	14.80	212.81	22000	460	1700	680	4000	<5 *****

TABLE 1  
GROUNDWATER ELEVATIONS AND CERTIFIED ANALYTICAL LABORATORY RESULTS FROM WATER SAMPLES  
DESERT PETROLEUM, INC. SITE #793  
4035 PARK BOULEVARD, OAKLAND, CALIFORNIA

ID#	DATE SAMPLED	WELL CASING ELEVATION (FEET AMSL)	DEPTH TO GROUND WATER (FEET)	(All concentrations in parts per billion [ug/L, ppb]) (AMSL = Above mean sea level)						
				GROUND WATER ELEVATION (FEET AMSL)	TPH-G (UG/L)	BENZENE (UG/L) (1)	TOLUENE (UG/L) (150)	ETHYL-BENZENE (UG/L) (300)	XYLENES (UG/L) (1800)	MTBE (UG/L) (13)
RS-6	12/14/89	227.22	22.52	204.7	11000	1400	1700	160	860	
RS-6	2/91	227.22	FLOATING PRGDUCT							
RS-6	6/91	227.22			95000	4200	4200	650	3700	
RS-6	9/91	227.22	FLOATING PRODUCT							
RS-6	12/91	227.22			64000	3700	2300	730	4100	
RS-6	11/9/92	227.22	19.43	207.79	19000	1600	710	500	1600	
RS-6	4/7/94	227.22	14.42	212.8	16000	1200	1300	290	1100	
RS-6	6/19/94	227.22	14.45	212.77	23000	1300	2200	590	2200	
RS-6	9/17/94	227.22	19.52	207.7	24000	630	790	250	1100	
RS-6	3/12/95	227.22	8.90	218.32	3200	450	13	82	230	
RS-6	10/4/95	227.22	17.78	209.44	3700	170	250	38	290	
RS-6	12/21/95	227.22	14.98	212.24	3100	120	30	16	150	58
RS-6	03/27/96	227.22	10.00	217.22	6900	180	440	79	360	< 300
RS-6	06/11/96	227.22	12.00	215.22	7400	220	150	30	100	<1000
RS-6	09/04/96	227.22	15.00	212.22	1400	68	2.6	7.7	9.2	14
RS-6	12/11/96	227.22	12.36	214.86	1800	39	16	10	18	< 0.5
RS-6	2/21/97	227.22	10.00	217.22	2100	71	85	25	40	< 0.5
RS-6	5/28/97	227.22	13.56	213.66	1700	34	12	11	16	< 0.5
RS-6	9/2/97	227.22	16.35	210.87	940	34	71	9	55	< 0.5
RS-6	11/24/97	227.22	15.72	211.5	490	9	6	1	7	< 0.5
RS-6	2/25/98	227.22	6.26	220.96	1400	22	47	5	52	< 0.5
RS-6**	7/8/98	227.22	11.41	215.81	1500	83	9	84	2	<10
RS-6	7/30/98	227.22			<50	<0.5	<0.5	<0.5	<1	
RS-6	9/16/98	227.22	13.42	213.8	990	23	<0.5	<0.5	<1	<1
RS-6	11/24/98	227.22	15.91	211.31	3400	5.3	<0.5	<0.5	14	<0.5
RS-6	2/23/99	227.22	7.00	220.22	1000	3.4	3.2	1.6	7.3	<0.5
RS-6	5/5/99	227.22	10.29	216.93	1100	50	10	80	15	2
RS-6***	8/26/99	227.22	13.72	213.5	690	44	2.5	30	31	<5
RS-6	11/10/99	227.22	13.90	213.32	1800	2	2	0.9	16	< 0.5
RS-6	2/9/00	227.22	12.77	214.45	410	3	3	4	7	< 0.5
RS-6	6/30/00	227.22	12.69	214.53	660	7	2	5	6	< 0.5
RS-6	8/8/00	227.22	14.72	212.5	660	2	3	2	6	< 0.5
RS-6	11/16/00	227.22	15.28	211.94	560	1	2	1	5	< 0.5
RS-6	3/8/01	227.22	10.10	217.12	2200	<0.5	<0.5	<0.5	<0.5	<0.5
RS-6	5/31/01	227.22	12.96	214.26	630	<0.5	<0.5	<0.5	<0.5	<5
RS-6	12/18/01	227.22	10.88	216.34	56	0.53	<0.5	<0.5	0.56	<0.5
RS-6	2/19/02	227.22	11.08	216.14	<50	<0.5	<0.5	0.6	<0.5	<0.5

TABLE 1  
GROUNDWATER ELEVATIONS AND CERTIFIED ANALYTICAL LABORATORY RESULTS FROM WATER SAMPLES  
DESERT PETROLEUM, INC. SITE #793  
4035 PARK BOULEVARD, OAKLAND, CALIFORNIA

ID#	(All concentrations in parts per billion [ug/L, ppb]) (AMSL = Above mean sea level)									
	DATE SAMPLED	WELL CASING ELEVATION (FEET AMSL)	DEPTH TO GROUND WATER (FEET)	GROUND WATER ELEVATION (FEET AMSL)	TPH-G (UG/L)	BENZENE (UG/L) (1)	TOLUENE (UG/L) (150)	ETHYL-BENZENE (UG/L) (300)	XYLENES (UG/L) (1800)	MTBE (UG/L) (13)
RS-7	12/14/89	195.99								
RS-7	7/90	195.99			5600000	24000	210000	50000	740000	
RS-7	2/91	195.99	FLOATING PRODUCT							
RS-7	6/91	195.99	FLOATING PRODUCT							
RS-7	9/91	195.99	FLOATING PRODUCT							
RS-7	12/91	195.99			270000	11000	22000	2000	13000	
RS-7	11/9/92	195.99	4.62	191.37	81000	12000	16000	1900	13000	
RS-7	4/7/94	195.99	4.03	191.96	74000	16000	16000	1400	8500	
RS-7	6/19/94	195.99	4.07	191.92	83000	22000	19000	1500	9500	
RS-7	9/17/94	195.99	4.05	191.94	270000	13000	15000	2100	1100	
RS-7	3/12/95	195.99	3.72	192.27	35000	5100	560	6300	3600	
RS-7	10/4/95	195.99	4.03	191.96	96000	14000	14000	1300	7000	
RS-7	12/21/95	195.99	3.95	192.04	70000	9300	12000	860	5600	210
RS-7	03/27/96	195.99	3.80	192.19	64000	8900	14000	1100	8300	< 3000
RS-7	06/11/96	195.99	3.79	192.2	65000	12000	17000	1600	9700	<5000
RS-7	09/04/96	195.99	3.99	192	20000	4900	2100	670	4400	100
RS-7	12/11/96	195.99	3.78	192.21	17000	4400	7500	570	4600	180
RS-7	2/21/97	195.99	3.82	192.17	93000	31000	47000	3800	23000	<0.5
RS-7	5/28/97	195.99	3.82	192.17	52000	12000	8200	2000	11000	<0.5
RS-7	9/2/97	195.99	3.96	192.03	28000	6100	2800	950	3800	<50
RS-7	11/24/97	195.99	3.76	192.23	18000	4300	5900	600	2900	<0.5
RS-7	2/25/98	195.99	3.70	192.29	13000	4300	7100	1100	5800	<0.5
RS-7**	7/8/98	195.99	3.76	192.23	45000	10000	3400	2000	8000	<10
RS-7	7/30/98	195.99			72000	12000	2100	2000	9100	
RS-7	9/16/98	195.99	3.83	192.16	5000	6500	160	<2.5	500	<5
RS-7	11/24/98	195.99	3.77	192.22	19000	2100	1100	500	2100	<0.5
RS-7	2/23/99	195.99	3.70	192.29	83000	6500	9900	1200	7000	<10
RS-7	5/5/99	195.99	3.88	192.11	47000	7400	4800	1300	7400	540
RS-7***	8/26/99	195.99	4.16	191.83	15000	3400	91	950	970	<5
RS-7	11/10/99	195.99	4.12	191.87	10000	2900	170	630	1200	<0.5
RS-7	2/9/00	195.99	3.98	192.01	9400	1400	120	480	600	<0.5
RS-7	6/30/00	195.99	4.04	191.95	8200	3300	190	430	540	<0.5
RS-7	8/8/00	195.99	4.06	191.93	11000	2300	150	430	520	<0.5
RS-7	11/16/00	195.99	4.04	191.95	5400	1500	40	240	200	<0.5
RS-7	3/8/01	195.99	3.94	192.05	12000	3300	260	480	850	17
RS-7	5/31/01	195.99	4.01	191.98	10000	1900	120	320	620	<100
RS-7	12/18/01	195.99	4.81	191.18	2700	450	21	86	120	2.3
RS-7	2/19/02	195.99	3.91	192.08	20000	2600	360	570	1900	11

TABLE 1  
GROUNDWATER ELEVATIONS AND CERTIFIED ANALYTICAL LABACRATAORY RESULTS FROM WATER SAMPLES  
DESERT PETROLEUM, INC. SITE #793  
4035 PARK BOULEVARD, OAKLAND, CALIFORNIA

ID#	(All concentrations in parts per billion [ug/L. ppb]) (AMSL = Above mean sea level)									
	DATE SAMPLED	WELL CASING ELEVATION (FEET AMSL)	DEPTH TO GROUND WATER (FEET)	GROUND WATER ELEVATION (FEET AMSL)	TPH-G (UG/L)	BENZENE (UG/L) (1)	TOLUENE (UG/L) (150)	ETHYL-BENZENE (UG/L) (300)	XYLENES (UG/L) (1800)	MTBE (UG/L) (13)
	(CALIFORNIA PUBLIC HEALTH GOAL)									
RS-8	12/14/89									
RS-8	09/04/96									
RS-8	12/11/96									
RS-8	2/21/97									
RS-8	5/28/97									
RS-8	9/2/97									
RS-8	11/24/97									
RS-8	2/25/98									
RS-8	7/8/98									
RS-8	9/16/98									
RS-8	11/24/98									
RS-8	2/23/99									
RS-8	5/5/99									
RS-8***	8/26/99	214.67	7.25	207.42	160000	24000	35000	4200	24000	<5
RS-8	11/10/99	214.67	8.69	205.98	150000	21000	29000	3000	14000	<0.5
RS-8	2/9/00	214.67	7.23	207.44	14000	1900	3200	270	2300	<0.5
RS-8	6/30/00	214.67	3.99	210.68	6400	570	870	150	770	<0.5
RS-8	8/8/00	214.67	7.52	207.15	100000	24000	40000	2300	9900	<0.5 *
RS-8	11/16/00	214.67	6.14	208.53	110000	14000	21000	2100	9600	<20 *
RS-8	3/8/01	214.67	9.40	205.27	10000	740	840	220	990	<2 *****
RS-8	5/31/01	214.67	6.83	207.84	730	11	29	4.2	31	<5 *****
RS-8	12/18/01	214.67	7.14	207.53	4500	230	370	77	750	<0.5 *****
RS-8	2/19/02	214.67	7.69	206.98	730	33	21	5.1	45	<0.5 *****



TABLE 1  
GROUNDWATER ELEVATIONS AND CERTIFIED ANALYTICAL LABACRATAORY RESULTS FROM WATER SAMPLES  
DESERT PETROLEUM, INC. SITE #793  
4035 PARK BOULEVARD, OAKLAND, CALIFORNIA

ID#	(All concentrations in parts per billion [ug/L. ppb]) (AMSL = Above mean sea level)									
	DATE SAMPLED	WELL CASING ELEVATION (FEET AMSL)	DEPTH TO GROUND WATER (FEET)	GROUND WATER ELEVATION (FEET AMSL)	TPH-G (UG/L)	BENZENE (UG/L) (1)	TOLUENE (UG/L) (150)	ETHYL-BENZENE (UG/L) (300)	XYLENES (UG/L) (1800)	MTBE (UG/L) (13)
(CALIFORNIA PUBLIC HEALTH GOAL)										
RS-9	12/14/89									
RS-9***	09/04/96									
RS-9***	12/11/96									
RS-9***	2/21/97									
RS-9***	5/28/97									
RS-9***	9/2/97									
RS-9***	11/24/97									
RS-9***	2/25/98									
RS-9***	7/8/98									
RS-9***	9/16/98									
RS-9***	11/24/98									
RS-9***	2/23/99									
RS-9***	5/5/99									
RS-9***	8/26/99	195.63	7.46	188.17	17000	3500	1200	360	1600	180
RS-9	11/10/99	195.63	7.91	187.72	2800	520	62	46	130	<0.5
RS-9	2/9/00	195.63	6.09	189.54	3400	650	74	64	130	<0.5
RS-9	6/30/00	195.63	6.77	188.86	3000	600	79	74	120	<0.5
RS-9	8/8/00	195.63	7.32	188.31	4900	500	430	160	530	<0.5
RS-9	11/16/00	195.63	6.33	189.3	3000	350	220	90	220	<0.5
RS-9	3/8/01	195.63	4.93	190.7	<50	3.4	<0.5	<0.5	<0.5	<0.5
RS-9	5/31/01	195.63	4.01	191.62	510	96	6	6.2	9.1	5.5
RS-9	12/18/01	195.63	4.81	190.82	210	11	1.8	3.9	7.6	<0.5
RS-9	2/19/02	195.63	4.99	190.64	<50	<0.5	<0.5	<0.5	<0.5	<0.5

TABLE 1  
 GROUNDWATER ELEVATIONS AND CERTIFIED ANALYTICAL LABORATORY RESULTS FROM WATER SAMPLES  
 DESERT PETROLEUM, INC. SITE #793  
 4035 PARK BOULEVARD, OAKLAND, CALIFORNIA

ID#	(All concentrations in parts per billion (ug/L, ppb)) (AMSL = Above mean sea level)									
	DATE SAMPLED	WELL CASING ELEVATION (FEET AMSL)	DEPTH TO GROUND WATER (FEET)	GROUND WATER ELEVATION (FEET AMSL)	TPH-G (UG/L)	BENZENE (UG/L) (1)	TOLUENE (UG/L) (150)	ETHYL-BENZENE (UG/L) (300)	XYLENES (UG/L) (1800)	MTBE (UG/L) (13)
RS-10	12/14/89									
RS-10***	09/04/96									
RS-10***	12/11/96									
RS-10***	2/21/97									
RS-10***	5/28/97									
RS-10***	9/2/97									
RS-10***	11/24/97									
RS-10***	2/25/98									
RS-10***	7/8/98									
RS-10***	9/16/98									
RS-10***	11/24/98									
RS-10***	2/23/99									
RS-10***	5/5/99									
RS-10***	8/26/99	208.46	3.76	204.7	5100	160	340	190	1000	32 *
RS-10	11/10/99	208.46	3.83	204.63	500	7	2	2	4	<0.5
RS-10	2/9/00	208.46	0.31	208.15	100	4	3	1	6	<0.5
RS-10	6/30/00	208.46	2.22	206.24	640	5	2	4	2	<0.5
RS-10	8/8/00	208.46	2.46	206	460	2	2	2	7	<0.5
RS-10	11/16/00	208.46	2.46	206	360	1	1	2	<1	<0.5
RS-10	3/8/01	208.46	2.82	205.64	53	<0.5	<0.5	<0.5	<0.5	<0.5 *****
RS-10	5/31/01	208.46	4.93	203.53	210	<0.5	<0.5	1.5	5	<5 *****
RS-10	12/18/01	208.46	2.10	206.36	<50	<0.5	<0.5	<0.5	<0.5	<0.5 *****
RS-10	2/19/02	208.46	2.29	206.17	<50	<0.5	<0.5	<0.5	<0.5	<0.5 *****

TABLE 1  
GROUNDWATER ELEVATIONS AND CERTIFIED ANALYTICAL LABORATORY RESULTS FROM WATER SAMPLES  
DESERT PETROLEUM, INC. SITE #793  
4035 PARK BOULEVARD, OAKLAND, CALIFORNIA

ID#	(All concentrations in parts per billion [ug/L, ppb]) (AMSL = Above mean sea level)									
	DATE SAMPLED	WELL CASING ELEVATION (FEET AMSL)	DEPTH TO GROUND WATER (FEET)	GROUND WATER ELEVATION (FEET AMSL)	TPH-G (UG/L)	BENZENE (UG/L) (1)	TOLUENE (UG/L) (150)	ETHYL-BENZENE (UG/L) (300)	XYLENES (UG/L) (1800)	MTBE (UG/L) (13)
R1	12/14/89									
R1	09/04/96	227.69	15.00	212.69	1800	1100	3	29	< 10	< 30
R1	12/11/96	227.69	10.30	217.39	<50	<0.5	< 0.5	< 0.5	< 1	4
R1	2/21/97	227.69	11.88	215.81	2500	670	9	3	13	<0.5
R1	5/28/97	227.69	14.03	213.66	24000	4300	36	2000	370	<0.5
R1	9/2/97	227.69	14.98	212.71	4400	320	6	340	72	20
R1	11/24/97	227.69	14.06	213.63	100	39	1	18	10	<0.5
R1	2/25/98	227.69	8.93	218.76	1200	400	8	13	150	<0.5
R1	7/8/98	227.69	11.36	216.33	68	14	< 0.5	< 0.5	< 1	<1
R1	9/16/98	227.69	13.30	214.39	16000	3400	92	< 0.5	410	<1
R1	11/24/98	227.69	10.72	216.97	340	19	1.6	35	9.7	<0.5
R1	2/23/99	227.69	9.34	218.35	60	16	0.6	5.6	1.2	<0.5
R1	5/5/99	227.69	11.30	216.39	1300	290	3	150	1	15
R1	8/26/99	227.69	13.97	213.72	6500	630	<0.5	1300	<1	<1
R1	11/10/99	227.69	13.73	213.96	480	12	4	22	9	<0.5
R1	2/9/00	227.69	13.10	214.59	<50	8	<0.5	1	<1	<0.5
R1	6/30/00	227.69	13.42	214.27	2600	350	35	1900	220	<0.5
R1	8/8/00	227.69	14.25	213.44	10000	910	76	2100	390	<0.5
R1	3/8/01	227.69	13.72	213.97	<50	<0.5	<0.5	<0.5	<0.5	<0.5
R1	3/8/01	227.69	13.72	213.97	<50	<0.5	<0.5	<0.5	<0.5	<0.5
R1	5/31/01	227.69	15.77	211.92	3800	400	16	470	67	<5
R1	12/18/01	227.69	9.90	217.79	<50	<0.5	<0.5	1.5	<0.5	<0.5
R1	2/19/02	227.69	10.86	216.83	<50	<0.5	<0.5	<0.5	<0.5	<0.5

TABLE 1  
GROUNDWATER ELEVATIONS AND CERTIFIED ANALYTICAL LABAORATAORY RESULTS FROM WATER SAMPLES  
DESERT PETROLEUM, INC. SITE #793  
4035 PARK BOULEVARD, OAKLAND, CALIFORNIA

ID#	(All concentrations in parts per billion [ug/L, ppb] (AMSL = Above mean sea level))									
	DATE SAMPLED	WELL CASING ELEVATION (FEET AMSL)	DEPTH TO GROUND WATER (FEET)	GROUND WATER ELEVATION (FEET AMSL)	TPH-G (UG/L)	BENZENE (UG/L) (1)	TOLUENE (UG/L) (150)	ETHYL-BENZENE (UG/L) (300)	XYLENES (UG/L) (1800)	MTBE (UG/L) (13)
R2	12/14/89									
R2	09/04/96	230.68	13.44	217.24	14000	7600	<10	170	190	<100
R2	12/11/96	230.68	12.42	218.26	488	300	1	< 0.5	30	16
R2	2/21/97	230.68	10.50	220.18	5700	2100	5	2	10	3 *
R2	5/28/97	230.68	13.10	217.58	36000	14000	63	260	220	<0.5 *
R2	9/2/97	230.68	14.16	216.52	30000	12000	330	1000	790	47 *
R2	11/24/97	230.68	14.71	215.97	41000	15000	830	1500	4200	<0.5 *
R2	2/25/98	230.68	7.39	223.29	800	400	<0.5	<0.5	15	<0.5 *
R2	7/8/98	230.68	11.27	219.41	290	31	< 0.5	1	< 1	2 *
R2	9/16/98	230.68	13.73	216.95	6600	11000	24	<0.5	35	<1 *
R2	11/24/98	230.68	11.67	219.01	6100	<0.5	36	<0.5	21	<0.5 *
R2	2/23/99	230.68	7.55	223.13	1100	310	3	2	26	<0.5 *
R2	5/5/99	230.68	10.89	219.79	11000	5300	7	36	7	6 *
R2	8/26/99	227.28	13.14	214.14	6700	940	33	190	240	<1 *
R2	11/10/99	227.28	14.42	212.86	5100	2600	160	1800	8100	<0.5 *
R2	2/9/00	227.28	12.45	214.83	4700	1400	110	130	340	<0.5 *
R2	6/30/00	227.28	12.94	214.34	7100	3200	110	300	480	<0.5 *
R2	8/8/00	227.28	13.58	213.7	30000	13000	250	1000	2700	<0.5 *
R2	11/16/00	227.28	14.33	212.95	44000	17000	230	790	3600	<0.5 *
R2	3/8/01	227.28	11.15	216.13	2300	640	8.6	61	170	<2 *****
R2	5/31/01	227.28	13.38	213.9	2200	580	12	72	100	<25 *****
R2	12/18/01	227.28	12.35	214.93	4900	2000	120	44	280	<5 *****
R2	2/19/02	227.28	11.32	215.96	2100	1200	<5	14	<5	<5 *****



TABLE 1  
 GROUNDWATER ELEVATIONS AND CERTIFIED ANALYTICAL LABACRATAORY RESULTS FROM WATER SAMPLES  
 DESERT PETROLEUM, INC. SITE #793  
 4035 PARK BOULEVARD, OAKLAND, CALIFORNIA

ID#	(All concentrations in parts per billion [ug/L, ppb]) (AMSL = Above mean sea level)									
	DATE SAMPLED	WELL CASING ELEVATION (FEET AMSL)	DEPTH TO GROUND WATER (FEET)	GROUND WATER ELEVATION (FEET AMSL)	TPH-G (UG/L)	BENZENE (UG/L) (1)	TOLUENE (UG/L) (150)	ETHYL-BENZENE (UG/L) (300)	XYLENES (UG/L) (1800)	MTBE (UG/L) (13)
T 1	12/14/89									
T 1	09/04/96									
T 1	12/11/96									
T 1	2/21/97									
T 1	5/28/97									
T 1	9/2/97									
T 1	11/24/97									
T 1	2/25/98									
T 1	7/8/98									
T 1	9/16/98									
T 1	11/24/98									
T 1	2/23/99									
T 1	5/5/99									
T 1***	8/26/99	195.11	2.44	192.67	40000	7200	5000	950	8100	53 *
T 1	11/10/99	195.11	2.23	192.88	46000	5600	3600	910	6500	<0.5
T 1	2/9/00	195.11	2.22	192.89	35000	2900	5700	720	6600	<0.5
T 1	6/30/00	195.11	2.22	192.89	30000	3400	3200	950	4600	<5
T 1	8/8/00	195.11	2.73	192.38	8900	1600	760	260	870	<5
T 1	11/16/00	195.11	2.72	192.39	4000	1300	92	80	290	<0.5
T 1	3/8/01	195.11	2.12	192.99	25000	4400	3400	770	3200	26 *****
T 1	5/31/01	195.11	2.30	192.81	8900	940	210	340	1500	<50 *****
T 1	12/18/01	195.11	2.20	192.91	48000	3700	5500	1200	5300	24 *****
T 1	2/19/02	195.11	1.96	193.15	64000	8600	6000	1700	6800	55 *****

ND BELOW LABORATORY DETECTION LIMITS  
 TPH-G TOTAL PETROLEUM HYDROCARBONS AS GASOLINE  
 \* MTBE results confirmed by EPA Method 8260 (GC/MS)  
 \*\* LAB REPORT HAD RS-6 AND RS-7 MISLABELED, RESAMPLE ON 7/30/98 CONFIRMED.  
 \*\*\* WELL CASING ELEVATION SURVEY 8-27-99, WADE HAMMOND No.6163, BENCH MARK CITY OF OAKLAND  
 \*\*\*\* SAMPLES ANALYZED USING EPA METHOD 8260B

TABLE 2  
 GROUNDWATER ELEVATIONS AND ELECTRON ACCEPTOR RESULTS FROM WATER SAMPLES  
 DESERT PETROLEUM, INC. SITE #793  
 4035 PARK BOULEVARD, OAKLAND, CALIFORNIA

ID#	DATE SAMPLED	WELL CASING ELEVATION (FEET AMSL)	DEPTH TO GROUND WATER (FEET)	GROUND WATER ELEVATION (FEET AMSL)	FIELD MEASUREMENTS						CERTIFIED LABORATORY RESULTS DISSOLVED IN WATER					
					DISSOLVED OXYGEN (MG/L)	SULFATE SO4 (MG/L)	NITRATE NO3 (MG/L)	FERROUS IRON FE2 (MG/L)	TEMPERATURE (F)	pH	TOTAL PETROCARBONS GASOLINE (MG/L)	CARBON DIOXIDE CO2 (MG/L)	METHANE CH4 (MG/L)	AEROBIC HYDROCARBON DEGRADING BACTERIA CFU/ML	ORTHO-PHOSPHATE PO4 (MG/L)	AMMONIA as NITROGEN (MG/L)
KW-1	8/26/99	229.57	11.41	218.16	4.9	35	0	0.25	75.4	6.55	<0.05					
	9/2/99	229.57	11.65	217.92					72.9	8.16	0.13	<0.00001	10	<1	<0.5	
	3/8/01	229.57	12.30	217.27	4.9				67.6	7.33	<0.05					
	12/18/01	229.57	13.74	215.83	4.4	61	7.6	0	67.1	7.63	<0.05					
RS-2	8/26/99	227.39	11.42	215.97	0.7	46	2.7	0.65	80.9	6.97	0.2					
	9/2/99	227.39	12.00	215.39								nm	nm	nm	nm	nm
	12/18/01	227.39	6.99	220.4	4.6	>77	11.4	0.07	67.6	7.75	<0.05					
RS-5	8/26/99	227.61	16.06	211.55	0.7	31	1.3	0.92	71.7	7.08	35					
	9/2/99	227.61	16.26	211.35					68.4	7.15		0.16	0.00021	3000	<1	<0.5
	3/8/01	227.61	27.72	199.89	3.1				59.7	7.46	11					
	12/18/01	227.61	15.61	212	1.4	37	8.2	>3.3	66.6	6.83	12					
RS-6	8/26/99	227.22	13.72	213.5	1.2	76	0.3	>3.3	77.8	6.66	0.69					
	9/2/99	227.22	14.14	213.08					69	6.69		0.36	<0.00001	400	<1	<0.5
	12/18/01	227.22	10.88	216.34	4.3	>77	0	0	66.7	6.84	0.056					
RS-7	8/26/99	195.99	4.16	191.83	0.3	>77	0.8	1.27	73.4	6.99	15					
	9/2/99	195.99	4.14	191.85								nm	nm	nm	nm	nm
	12/18/01	195.99	4.81	191.18	2.5	1	6	0.87	68.1	6.82	2.7					
RS-8	8/26/99	214.67	7.25	207.42	2.6	0	0	0.54	69.2	6.7	160					
	9/2/99	214.67	7.38	207.29					71.7	5.74		0.058	0.000018	6600	<1	<0.5
	3/8/01	214.67	9.40	205.27	2.2				63.3	6.97	10					
	12/18/01	214.67	7.14	207.53	4.2	49	9.2	0.08	67.3	6.98	0.23					
RS-9	8/26/99	195.63	7.46	188.17	2.1	7	0	0.59	73.5	6.95	17					
	9/2/99	195.63	7.61	188.02					70.9	6.98		0.25	0.0021	10000	<1	<0.5
	3/8/01	195.63	4.93	190.7	8.1				62.7	6.89	<0.05					
	12/18/01	195.63	4.81	190.82	WATER TO CLOUDY, LIGHT GREY				68.3	6.8	0.21					
RS-10	8/26/99	208.46	3.76	204.7	4.2	nm	nm	nm	70.9	8.03	5.1					
	9/2/99	208.46	3.96	204.5					73.3	7.24		0.1	0.000037	8600	<1	<0.5
	3/8/01	208.46	2.82	205.64	3.5				61.5	6.16	0.053					
	12/18/01	208.46	2.10	206.36	4.3	46	4.1	0	66.9	6.54	<0.05					
R1	8/26/99	227.69	13.97	213.72	0.4	9	0	>3.3	70.6	6.38	6.5					
	9/2/99	227.69	14.18	213.51								nm	nm	nm	nm	nm
	12/18/01	227.69	9.90	217.79	5.2	14	4.2	0	66.4	7.24	<0.05					
R2	8/26/99	227.28	13.14	214.14	0.4	>77	0.8	0.3	72.7	6.65	6.7					
	9/2/99	227.28	13.23	214.05								nm	nm	nm	nm	nm
	12/18/01	227.28	12.35	214.93	2.8	>77	1.3	0.07	66.5	6.69	4.9					
R3	8/26/99	230.32	10.76	219.56	2.5	>77	0.7	0.05	75	6.95	<0.05					
	9/2/99	230.32	10.87	219.45								nm	nm	nm	nm	nm
	12/18/01	230.32	6.78	223.53	5.5	>77	6.2	0	67.1	6.91	<0.05					
T 1	8/26/99	195.11	2.44	192.67	0.8	32	0.5	0.03	75.3	7.29	40					
	9/2/99	195.11	2.20	192.91					78.1	7.57		0.11	0.00019	1300	<1	<0.5
	3/8/01	195.11	2.18	192.93	3.1						25					
	12/18/01	195.11	2.20	192.91	2.8	0	4.3	0.6	66.3	6.52	48					

22

TABLE 2  
GROUNDWATER ELEVATIONS AND ELECTRON ACCEPTOR RESULTS FROM WATER SAMPLES  
DESERT PETROLEUM, INC. SITE #793  
4035 PARK BOULEVARD, OAKLAND, CALIFORNIA

ID#	(All concentrations in parts per million [mg/L, ppm] unless otherwise noted) (AMSL - Above mean sea level)															
	DATE SAMPLED	WELL CASING ELEVATION (FEET AMSL)	DEPTH TO GROUND WATER (FEET)	GROUND WATER ELEVATION (FEET AMSL)	FIELD MEASUREMENTS						CERTIFIED LABORATORY RESULTS DISSOLVED IN WATER					
					DISSOLVED OXYGEN O2 (MG/L)	SULFATE SO4 (MG/L)	NITRATE NO3 (MG/L)	FERROUS IRON FE2 (MG/L)	TEMP-ERATURE (F)	pH	TOTAL PETROLEUM HYDROCARBONS GASOLINE (MG/L)	CARBON DI OXIDE CO2 (MG/L)	METHANE CH4 (MG/L)	AEROBIC HYDROCARBON DEGRADING BACTERIA CFU/ML	ORTHO-PHOSPHATE PO4 (MG/L)	AMMONIA as NITROGEN N (MG/L)
T 2	8/26/99	195.3	CAR		nm	nm	nm	nm	nm	nm	NA	nm	nm	nm	nm	nm
	9/2/99	195.3	CAR													
T 3	8/26/99	202.38	CAR		nm	nm	nm	nm	nm	nm	NA	nm	nm	nm	nm	nm
	9/2/99	202.38	CAR													
T 4	8/26/99	197.48	CAR		nm	nm	nm	nm	nm	nm	NA	nm	nm	nm	nm	nm
	9/2/99	197.48	CAR													
LF-1	8/26/99	226.59	CAR		nm	nm	nm	nm	nm	nm	NA	nm	nm	nm	nm	nm
	9/2/99	226.59	CAR													

NA NOT ANALYZED  
nm NOT MEASURED  
CAR CAR PARKED OVER WELL. NO ACCESS

MG/L milligrams per liter (ppm)  
F degrees Fahrenheit  
CFU/ML colony forming units per mill

AMSL ABOVE MEAN SEA LEVEL  
< below laboratory lower detection limits.



TABLE 3  
 WASTEWATER DISCHARGE PERMIT # 5043550 1  
 FORMER DP #793  
 4035 PARK BLVD., OAKLAND, CALIFORNIA

WASTEWATER SOURCE ID	DATE	METER READING	NEW METER	GALLONS DISCHARGED	ACCUMULATIVE GALLONS DISCHARGED	AVERAGE DISCHARGE PER MINUTE IN GALLONS	EPA METHOD 624			7420	
		#35635668 314110	#47083426	BETWEEN VISITS			BENZENE ug/L	TOLUENE ug/L	ETHYL-BENZENE ug/L	XYLENES ug/L	LEAD ug/L
BAKER TANK	1/25/00	314110		0	0	0.00					
BAKER TANK	1/26/00	315050		940	940	0.65	<1	<1	<1	<1	<50
BAKER TANK	1/28/00	321120	1098330	6070	7010	2.11					
BAKER TANK	2/2/00		1102560	4230	11240	0.59					
BAKER TANK	2/3/00		1107482.2	4922	16162	3.42	<1	<1	<1	<1	<50
BAKER TANK	2/7/00		1107482.2	0	16162	0.00					
BAKER TANK AND 1/4LY SAMPLES	2/9/00		1109680	2198	18360	0.76	EPA METHOD 624			239.2	
F1 (PSP No. 1)	3/23/00		1109720	40	18400	0.00	<1	<1	<1	<2	<5
F1 (PSP No. 1)	5/4/00		1110780	1060	19460	0.02					
F1 (PSP No. 1)	5/12/00		1111700	920	20380	0.08					
F1 (PSP No. 1)	5/18/00		1113359	1659	22039	0.19					
F1 (PSP No. 1)	5/25/00		1113840	481	22520	0.05					
F1 (PSP No. 1)	5/31/00		1115111	1271	23791	0.15					
F1 (PSP No. 1)	6/16/00		1115823	712	24503	0.03					
F1 (PSP No. 1)	6/28/00		1116293	470	24973	0.03					
F1 (PSP No. 1)	6/30/00		1116303	10	24983	0.00	EPA METHOD 624			200.7	
F1 (PSP No. 1)	7/5/00		1116313	10	24993	0.00	<1	<1	<1	<2	<2
F1 (PSP No. 1)	7/13/00		1117816	1503	26496	0.13					
F1 (PSP No. 1)	7/20/00		1118892	1076	27572	0.11					
F1 (PSP No. 1)	7/27/00		1118892	0	27572	0.00					
F1 (PSP No. 1)	8/3/00		1120336	1444	29016	0.14					
F1 (PSP No. 1)	8/10/00		1121041	705	29721	0.07					
F1 (PSP No. 1)	8/17/00		1121041	0	29721	0.00					
F1 (PSP No. 1)	8/24/00		1121860	819	30540	0.08	EPA METHOD 624			200.7	
F1 (PSP No. 1)	8/30/00		1122720	860	31400	0.10	<1	<2	<1	<2	<2
F1 (PSP No. 1)	9/7/00		1123270	550	31950	0.05					
F1 (PSP No. 1)	9/14/00		1123819	549	32499	0.05					
F1 (PSP No. 1)	9/21/00		1123819	0	32499	0.00					
F1 (PSP No. 1)	10/5/00		1124153	334	32833	0.02					
F1 (PSP No. 1)	10/12/00		1124660	507	33340	0.05					
F1 (PSP No. 1)	10/19/00		1125904.3	1244	34584	0.12					
F1 (PSP No. 1)	10/26/00		1127167	1263	35847	0.13					
F1 (PSP No. 1)	11/9/00		1128367.2	1200	37047	0.06					
F1 (PSP No. 1)	11/16/00		1129779.5	1412	38460	0.14					
F1 (PSP No. 1)	11/22/00		1130940.5	1161	39621	0.13					
F1 (PSP No. 1)	12/1/00		1134147	3207	42827	0.25	EPA METHOD 624			200.7	
F1 (PSP No. 1)	12/7/00		1134289	142	42969	0.02	<1	<1	<1	<2	<2

21

TABLE 3  
WASTEWATER DISCHARGE PERMIT # 5043550 1  
FORMER DP #793  
4035 PARK BLVD., OAKLAND, CALIFORNIA

WASTEWATER SOURCE ID	DATE	METER READING	NEW METER	GALLONS DISCHARGED	ACCUMULATIVE GALLONS DISCHARGED	AVERAGE DISCHARGE PER MINUTE	EPA METHOD 624 BENZENE	TOLUENE	ETHYL-BENZENE	XYLENES	7420 LEAD
		IN GALLONS #35635668	IN GALLONS #47083426	BETWEEN VISITS	IN GALLONS	IN GALLONS	IN GALLONS	ug/L	ug/L	ug/L	ug/L
		314110									
F1 (PSP No. 1)	12/14/00		1134431	142	43111	0.01					
F1 (PSP No. 1)	12/21/00		1134573	142	43253	0.01					
F1 (PSP No. 1)	12/28/00		1134714.8	142	43395	0.01					
F1 (PSP No. 1)	1/11/01		1134714.8	0	43395	0.00	no discharge, could not access trench well				
F1 (PSP No. 1)	1/18/01		1135243.8	529	43924	0.05					
F1 (PSP No. 1)	1/25/01		1136144	900	44824	0.09					200.7
F1 (PSP No. 1)	2/8/01		1136659	515	45339	0.03					<2
F1 (PSP No. 1)	2/15/01		1137441.4	782	46121	0.08					
F1 (PSP No. 1)	2/22/01		1141123.6	3682	49804	0.37	start discharge from RS5				
F1 (PSP No. 1)	3/1/01		1150736.5	9613	59417	0.95	EPA METHOD 624				
F1 (PSP No. 1)	3/8/01		1158901.1	8165	67581	0.81	<1	<1	<1	<2	
F1 (PSP No. 1)	3/14/01		1162321.2	3420	71001	0.40					
F1 (PSP No. 1)	3/21/01		1162321.4	0	71001	0.00	no discharge, pump removed for repair				
F1 (PSP No. 1)	4/4/01		1163471.7	1150	72152	0.06					
F1 (PSP No. 1)	4/12/01		1164723.5	1252	73404	0.11	EPA METHOD 8260B				
F1 (PSP No. 1)	4/19/01		1173267	8544	81947	0.85	<0.5	<0.5	<0.5	<0.5	
F1 (PSP No. 1)	5/3/01		1181423.5	8157	90104	0.40					
F1 (PSP No. 1)	5/10/01		1188209.3	6786	96889	0.67					
F1 (PSP No. 1)	5/16/01		1189899.1	1690	98579	0.20					
F1 (PSP No. 1)	5/24/01		1198018.4	8119	106698	0.70					
F1 (PSP No. 1)	5/31/01		1199647.8	1629	108328	0.16					
F1 (PSP No. 1)	6/6/01		1204217.2	4569	112897	0.53					
F1 (PSP No. 1)	6/14/01		1210661.4	6444	119341	0.56					
F1 (PSP No. 1)	6/21/01		1214600	3939	123280	0.39					
F1 (PSP No. 1)	6/28/01		1219387.7	4788	128068	0.47					
F1 (PSP No. 1)	7/5/01		1223625.4	4238	132305	0.42					
F1 (PSP No. 1)	7/12/01		1228500	4875	137180	0.48	EPA METHOD 8260B				
F1 (PSP No. 1)	7/19/01		1232750.7	4251	141431	0.42	<0.5	<0.5	<0.5	<0.5	
REMOVE PUMP AND DISCONTINUE SEWER DISCHARGE ON July 19, 2001, COMMENCE 1/4LY DISCHARGE											
F1 (PSP No. 1) 1/4LY SAMPLES	12/18/01			238	137418	5.00	<0.5	<0.5	<0.5	<0.5	<0.5
F1 (PSP No. 1) 1/4LY SAMPLES	2/19/02			246	141677	5.00	<0.5	<0.5	<0.5	<0.5	<0.5

< BELOW LABORATORY LOWER DETECTION LIMITS

ug/L micrograms per liter (parts per billion)

Note: water meter #47083426 did not function during initial test, substitute meter #35635668 used until cleaned and tested. Re-installed January 28, 2000.  
WATER DISCHARGED TO SEWER IS FROM WEEKLY PURGING OF T1, CONTINUOUS DISCHARGE FROM WELL RS5 AND PURGED WATER FROM 1/4LY SAMPLING.

TABLE 4  
 RECEPTOR TRENCH GROUNDWATER REMOVAL  
 FORMER DP #793  
 4035 PARK BLVD., OAKLAND, CALIFORNIA

PURGING BY	DATE PURGED	METER READING IN GALLONS RS5	METER READING IN GALLONS TRENCH	DEPTH TO TOP OF WATER IN FEET	GALLONS PURGED T1	ACCUMULATED GALLONS REMOVED FROM TRENCH GALLONS	Accumulated gallons removed from RS5 Gallons	TOTAL GALLONS REMOVED	RECEPTOR TRENCH WATER ANALYSIS EPA METHOD 8020						
									TPHg	BENZENE	TOLUENE	ETHYL-BENZENE	XYLENES	MTBE	
									ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	
WEGE	8/9/99			6.47	200	200									
WEGE	8/10/99			5.02	1730	1930									
WEGE	8/11/99			7.89	960	2890									
WEGE	8/12/99			8.12	800	3690									
WEGE	8/13/99			8.87	600	4290									
WEGE	9/2/99			2.2	3600	7890			40000	7200	5000	950	8100	53	
WEGE	9/16/99			2.27	5131	13021									
WEGE	9/23/99			4.26	3351	16372									
WEGE	9/30/99			4.69	1734	18106									
WEGE	10/7/99			4.78	293	18400									
WEGE	1/25/00				0	18400									
WEGE	1/26/00				0	18400									
WEGE	1/28/00		1098330.0		0	18400									
WEGE	2/23/00		1102560.0		0	18400			35000	2900	5700	720	6600	<0.5	
WEGE	2/29/00		1109680.0	2.22	0	18400									
WEGE	3/23/00		1109720.0		0	18400				1020	6500	1010	5090		
WEGE	5/4/00		1110780.0		1060	19460									
WEGE	5/12/00		1111700.0	2.19	920	20380									
WEGE	5/18/00		1113359.0	2.18	1659	22039									
WEGE	5/25/00		1113840.0		481	22520									
WEGE	5/31/00		1115111.0	2.15	1271	23791									
WEGE	6/16/00		1115823.0		712	24503									
WEGE	6/28/00		1116293.0	2.22	470	24973									
WEGE	6/30/00		1116303.0		10	24983			30000	3400	3200	950	4600	<5	
WEGE	7/5/00		1116313.0		10	24993									
WEGE	7/6/00		1116313.0		0	24993									
WEGE	7/13/00		1117816.0		1503	26496									
WEGE	7/20/00		1118892.0	2.29	1076	27572									
WEGE	7/27/00		1118892.0	2.21	0	27572									
WEGE	8/3/00		1120336.0	2.9	1444	29016									
WEGE	8/10/00		1121041.0	2.75	705	29721			8900	1600	760	260	870	<5	
WEGE	8/17/00		1121041.0	2.73	0	29721									
WEGE	8/24/00		1121860.0	2.75	819	30540									
WEGE	8/30/00		1122720.0	2.75	860	31400									
WEGE	9/7/00		1123270.0	2.78	550	31950									
WEGE	9/14/00		1123810.0	2.79	540	32490									
WEGE	9/21/00		1123810.0		0	32490									
WEGE	10/5/00		1124253.0	2.81	443	32933									
WEGE	10/12/00		1124660.0	2.4	407	33340									
WEGE	10/19/00		1125904.3		1244	34584									

TABLE 4  
 RECEPTOR TRENCH GROUNDWATER REMOVAL  
 FORMER DP #793  
 4035 PARK BLVD., OAKLAND, CALIFORNIA

PURGING BY	DATE PURGED	METER READING IN GALLONS RSS	METER READING IN GALLONS TRENCH	DEPTH TO TOP OF WATER IN FEET	GALLONS PURGED T1	ACCUMULATED GALLONS REMOVED FROM TRENCH GALLONS	Accumulated gallons removed from RS5 Gallons	RECEPTOR TRENCH WATER ANALYSIS EPA METHOD 8020								
								TOTAL GALLON: REMOVED	TPH <sub>g</sub> ug/L	BENZENE ug/L	TOLUENE ug/L	ETHYL-BENZENE ug/L	XYLENES ug/L	MTBE ug/L		
WEGE	10/26/00		1127167.0	2.22	1263	35847										
WEGE	11/9/00		1128367.2	2.87	1200	37047										
WEGE	11/16/00		1129779.5		1412	38459			4000	1300	92	80	290		<0.5	
WEGE	11/22/00		1130940.5	2.72	1161	39620										
WEGE	12/1/00		1132147.0	2.21	1207	40827										
WEGE	12/7/00		1132147.0	2.21	0	40827										
WEGE	12/14/00		1132823.0	2.55	676	41503										
WEGE	12/21/00		1134087.4	2.3	1264	42767										
WEGE	12/28/00		1134714.8	2.32	627	43394										
WEGE	1/11/01		1134714.8	2.32	0	43394										
WEGE	1/18/01		1135243.8	2.3	529	43923										
WEGE	1/25/01		1136144.0	2.46	900	44824										
WEGE	2/8/01		1136659.0	2.3	515	45339										
WEGE	2/15/01		1137441.4	2.38	782	46121										
WEGE	2/22/01	1140664.5	1141123.6	2	459	46580	3223.1									
WEGE	3/1/01	1150033.2	1150736.5	2.18	703	47283	12132.7									
WEGE	3/8/01	1158270.7	1158901.1	2.18	630	47914	19666.9		25000	4400	3400	770	3200		26	
WEGE	3/14/01	1161991.1	1162321.2	2.49	330	48244	22756.9									
WEGE	3/21/01	1162321.4	1162321.4	2.49	0	48244	22757.1									
WEGE	4/4/01	1162321.4	1163471.7	2.54	1150	49394	22757.1									
WEGE	4/12/01	1163471.7	1164723.5	2.16	1252	50646	22757.1									
WEGE	4/19/01	1172032.3	1173267.0	2.45	1235	51881	30065.9									
WEGE	4/26/01	1179315.2	1180276.0	2.25	961	52841	36114.1									
WEGE	5/3/01	1180334.5	1181423.5	2.3	1089	53930	36172.6									
WEGE	5/10/01	1188209.3	1188209.3	2.29	0	53930	42958.4									
WEGE	5/16/01	1188209.3	1189899.1	2.29	1690	55620	42958.4									
WEGE	5/24/01	1197065.0	1198018.4	2.13	953	56574	50124.3									
WEGE	5/31/01	1198878.6	1199647.3	2.3	769	57342	50984.5		8900	940	210	340	1500		<50	
WEGE	6/6/01	1203366.1	1204217.2	2.32	831	58173	54723.3									
WEGE	6/14/01	1210661.4	1210661.4	2.31	0	58173	61167.5									
WEGE	6/21/01	1214124.2	1214600.0	3.41	476	58649	64630.3									
WEGE	6/28/01	1218305.1	1219387.7	2.37	1083	59732	68335.4									
WEGE	7/5/01	1222739.6	1223625.4	3.5	886	60618	71687.3									
WEGE	7/12/01	1227553.1	1228500.0	3	947	61565	75615.0									
WEGE	7/19/01	1231804.3	1232750.7	3.61	946	62511	78919.3									
WEGE	12/18/01	purged water from 1/4ly				238		137417.5	48000	3700	5500	1200	5300		24	
WEGE	2/19/02	purged water from 1/4ly				30		141460.2	64000	8600	6000	1700	6800		55	

< BELOW LABORATORY LOWER DETECTION LIMITS

mg/Kg milligrams per kilogram (parts per million)

TPH<sub>g</sub> TOTAL PETROLEUM HYDROCARBONS GASOLINE RANGE

MTBE METHYL TERTIARY BUTYL ETHER

\* SAMPLED ON AUGUST 26, 1999

per liter (parts per billion)

ppm per liter (parts per million)

WESTERN GEO-ENGINEERS

TABLE 5 POUNDS HYDROCARBONS

DP 793

4035 PARK BLVD, OAKLAND, CA

Pounds TPHg in soil and in groundwater AUGUST 1999.

		soil density=		1.9						pounds per interval
Square Feet	Thickness feet	Cubic feet	Upper mg/kg	Lower mg/kg	Average con mg/kg	kg Soil	mg TPHg	pounds TPHg		
TPHg in soil 5 - 10 foot depth 8/99										
2165	5	10825	50	1	25.5	582409.9	14851452.39	32.7		
1945	5	9725	100	50	75	523227.4	39242052.56	86.5		
700	5	3500	290	100	195	188308.1	36720069.75	81.0		
325	5	1625	1000	100	550	87428.74	48085805.63	106.0		
100	5	500	2000	1000	1500	26901.15	40351725	89.0		
440	5	2200	4000	1000	2500	118365.1	295912650	652.4	1047.6	
TPHg in soil 10-15 foot depth AUGUST 1999										
5006	5	25030	50	1	25.5	1346672	34340125.01	75.7		
1599	5	7995	100	50	75	430149.4	32261204.14	71.1		
2815	5	14075	1000	100	550	757267.4	416497054.9	918.2		
240	5	1200	1200	1000	1100	64562.76	71019036	156.6	1221.6	
TPHg in soil 15-20 foot depth AUGUST 1999										
1926	5	9630	50	1	25.5	518116.1	13211961.8	29.1		
1044	5	5220	100	50	75	280848	21063600.45	46.4		
1250	5	6250	1000	100	550	336264.4	184945406.3	407.7	483.3	
TPHg in soil 20-25 foot depth AUGUST 1999										
2900	5	14500	10	1	5.5	780133.4	4290733.425	9.5	9.5	
TPHg in soil 25-30 foot depth AUGUST 1999										
410	5	2050	50	1	25.5	110294.7	2812515.233	6.2		
175	5	875	100	50	75	47077.01	3530775.938	7.8		
145	5	725	1000	100	550	39006.67	21453667.13	47.3		
80	5	400	1600	1000	1300	21520.92	27977196	61.7	123.0	
Total pounds TPHg in Soil AUGUST 1999									2884.9	
MASS GROUNDWATER CONTAMINATION AUGUST 1999										
		PORES		0.3						
Square Feet	Thickness feet	Cubic feet	Upper mg/l	Lower mg/l	Average con mg/l	LITERS water	mg TPHg	pounds TPHg		
10520	16	168320	1	0.05	0.525	1429895	750695	1.66		
8650	16	138400	10	1	5.5	1175722	6466470	14.26		
2000	16	32000	40	10	25	271843	6796080	14.98		
2550	16	40800	100	10	55	346600	19063004	42.03		
750	16	12000	160	100	130	101941	13252356	29.22		
Total Calculated Mass TPHg in Groundwater AUGUST 1999									102.14	

MASS GROUNDWATER CONTAMINATION DECEMBER 2001									
		PORES	0.3						
Square	Thickness	Cubic	Upper	Lower	Average con	LITERS	mg	pounds	
Feet		feet	mg/l	mg/l	mg/l	water	TPHg	TPHg	
4825	16	77200	1	0.05	0.525	655822	344306	0.76	
4984	16	79744	10	1	5.5	677433	3725883	8.21	
120	16	1920	12	10	11	16311	179417	0.40	
1240	16	19840	48	10	29	168543	4887741	10.78	
495	10	4950	48	48	48	42051	2018436	4.45	

trench

Total Calculated Mass TPHg in Groundwater DECEMBER 2001								24.59
---	--	--	--	--	--	--	--	-------

MASS BENZENE GROUNDWATER CONTAMINATION AUGUST 1999									
assumption: free product contains 287 mg/L of benzene									
		PORES	0.3						
Square	Thickness	Cubic	Upper	Lower	Average con	LITERS	mg	pounds	
Feet		feet	mg/l	mg/l	mg/l	water	Benzene	Benzene	
6775	16	108400	0.1	0.0005	0.05025	920869	46274	0.10	
7800	16	124800	1	0.1	0.55	1060188	583104	1.29	
2000	16	32000	7.2	1	4.1	271843	1114557	2.46	
2000	16	32000	10	1	5.5	271843	1495138	3.30	
1200	16	19200	24	10	17	163106	2772801	6.11	

Total Calculated Mass Benzene in Groundwater 1999								13.25
---	--	--	--	--	--	--	--	-------

MASS BENZENE GROUNDWATER CONTAMINATION DECEMBER 2001									
assumption: free product contains 287 mg/L of benzene									
		PORES	0.3						
Square	Thickness	Cubic	Upper	Lower	Average con	LITERS	mg	pounds	
Feet		feet	mg/l	mg/l	mg/l	water	Benzene	Benzene	
3940	16	63040	0.001	0.0005	0.00075	535531	402	0.00	
5265	16	84240	0.5	0.001	0.2505	715627	179265	0.40	
2170	16	34720	1	0.5	0.75	294950	221212	0.49	
450	16	7200	2	1	1.5	61165	91747	0.20	
970	16	15520	3.7	1	2.35	131844	309833	0.68	
495	10	4950	3.7	3.7	3.7	42051	155588	0.34	

trench

ESTIMATED POUNDS GROUNDWATER TPHg REDUCTION FROM 1999 TO 2001 77.5

ESTIMATED POUNDS GROUNDWATER BENZENE REDUCTION FROM 1999 TO 2001 11.1

ESTIMATED % REDUCTION TPHg 75.9

ESTIMATED % REDUCTION BENZENE 84.1

Cost Estimate per treatment	unit cost	amount	subtotal	ORC cost	peroxide treatments
liters of groundwater treated		1781168			
53 gallon drum 35% peroxide pump truck	\$514.62	1	\$514.62	\$77,520.0	150.63
Geotechnichain	\$175.00	6	\$330.00		
PPE	\$25.00	1	\$25.00		
DTW	10	1	\$10.00		
ph,Cond, Temp	10	1	\$10.00		
Dissolved Oxygen	20	6	\$120.00	\$1,184.62	

To raise depleted oxygen from 2 ppm to 8 ppm - 1,781,168 liters (no reactions calculated) with 35% hydrogen peroxide ratio O to H2O2 2.125  
 killograms Oxygen 10.6870057  
 killogram peroxide 22.7098871  
 litter peroxide 16.3380483  
 35 percent sol 46.680138  
 gallons peroxide 12.3492428 treatment per drum 4.3




FIGURE 1  
 GEOTRACKER  
 AREA WELL & LUST MAP  
 DP 793  
 4035 PARK BLVD.  
 OAKLAND, CA

- LUST SITES
- WELLS







FIGURE 2  
PORTION OF OAKLAND EAST 7.5 MINUTE USGS TOPOGRAPHIC MAP








**FIGURE 3-SAMPLE LOCATIONS  
SEWER AND FREE PRODUCT  
INVESTIGATION FOR  
DP793, 4035 PARK BLVD.  
OAKLAND, CALIFORNIA**

- 10 SPS SAMPLE POINT
- SOIL SAMPLE POINT
- SOIL BORING
- RECEPTOR TRENCH SAMPLE POINT
- RS2 GROUNDWATER MONITORING WELL
- RS1 DESTROYED MONITORING WELL


0' 20' 50'  
SCALE: 1 INCH=50 FEET





**FIGURE 4**  
 DP 793, 4035 PARK BLVD.  
 OAKLAND, CALIFORNIA  
 GROUNDWATER ELEVATION  
 2/19/02.

CONTOURS ARE  
 FEET ABOVE SEA  
 LEVEL




0' 20' 50'  
SCALE: 1 INCH = 50 FEET



**FIGURE 5**  
**GROUNDWATER**  
**PLUME**  
**08/26/99**

DP 793, 4035 PARK BLVD.  
OAKLAND, CALIFORNIA

- RS3 SOIL BORING
- ┆ TRENCH SAMPLE POINT
- RS2
- GROUNDWATER MONITORING WELL
- Benzene > 1000 ug/L
- Benzene > 500 ug/L
- Benzene > 1 ug/L
- TPHg Groundwater Plume



0' 20' 50'  
SCALE: 1 INCH = 50 FEET




**FIGURE 6**  
**GROUNDWATER**  
**PLUME**  
**05/31/01**

DP 793, 4035 PARK BLVD.  
OAKLAND, CALIFORNIA

- RS3 SOIL BORING
- ┆ TRENCH SAMPLE POINT
- RS2
- GROUNDWATER MONITORING WELL
- Benzene > 1000 ug/L
- Benzene > 500 ug/L
- Benzene > 1 ug/L
- TPHg Groundwater Plume






0' 20' 50'  
SCALE: 1 INCH = 50 FEET

NORTH

**FIGURE 7  
GROUNDWATER  
PLUME  
12/18/01**

DP 793, 4035 PARK BLVD.  
OAKLAND, CALIFORNIA

- RS3 SOIL BORING
- ┆ TRENCH SAMPLE POINT
- RS2
- GROUNDWATER MONITORING WELL
- Benzene > 1000 ug/L
- Benzene > 500 ug/L
- Benzene > 1 ug/L
- TPHg Groundwater Plume



**FIGURE 8  
GROUNDWATER  
PLUME  
2/19/02**

DP 793, 4035 PARK BLVD.  
OAKLAND, CALIFORNIA

- RS3 SOIL BORING
- ⊥ TRENCH SAMPLE POINT
- ⊙ RS2
- ⊙ GROUNDWATER MONITORING WELL
- Benzene > 1000 ug/L
- Benzene > 500 ug/L
- Benzene > 1 ug/L
- TPHg Groundwater Plume

230 feet above mean sea level

- BK BLACK
- LB LIGHT BROWN
- DB DARK BROWN
- DG DARK GRAY

Retaining wall

RS5

LB

sewer

LB


LB

LB

LB

LB

LB



GRAVEL

CLAY

CLAY


CLAY

SILTY CLAY

SAND


SILTY CLAY

GROUNDWATER  
JUNE, 1996






NORTH

**FIGURE 9**  
**CROSS SECTION**  
**FREE PRODUCT INVESTIGATION**  
**SEWER ROUTE FROM SITE ALONG FENCE LINE BACKYARDS**  
**DP793, 4035 PARK BLVD.**  
**OAKLAND, CALIFORNIA**



### EXPLANATION

#### UNDERGROUND UTILITIES DISCOVERED

-  SEWER UTILITY HOUSE LATERAL
-  GAS UTILITY HOUSE LATERAL
-  WATER UTILITY HOUSE LATERAL

0' 10' 30' 60'  
SCALE: 1 INCH = 30 FEET

5' 10'  
SCALE: 1 INCH = 5 FEET



**FIGURE 10**  
**CROSS SECTION**  
**AS BUILT RECEPTOR TRENCH**  
**FOR FREE PRODUCT AND GROUNDWATER RECOVERY**  
**DP793, 4035 PARK BLVD.**  
**OAKLAND, CALIFORNIA**  
**SEPTEMBER 9, 1999**



# APPENDIX A

QA/QC  
METHODS  
&  
PROCEDURES

## APPENDIX A.

### METHODS AND PROCEDURES, QA/QC

This Appendix documents the specific methods, procedures, and materials used to collect and analyze ground water samples.

#### Gauging and Measuring Monitor Wells.

Prior to sampling a well, WEGE personnel obtain two measurements: the depth to ground water and the product thickness using a battery powered depth to water-product interface probe and or by using a specially designed bailer. The probe is lowered into the well casing until the instrument signals that the top of water has been reached. The distance from the top of water to the top of casing is read from the tape calibrated in 0.01 foot intervals for accuracy to 0.01 foot, that is attached to the probe. The measured distance is subtracted from the established elevation at the top of casing to determine the elevation of ground water with respect to mean sea level.

The probe is washed with TSP and rinsed in distilled water before each measurement. WEGE has designed and built bailers that will collect a sample of the contents of a well to show the exact thickness of any floating product.

#### Purging Standing Water from Monitor Wells

If no product is present, WEGE personnel purge the well. This is accomplished by removing ground water from the well until the water quality parameters (temperature, pH, and conductivity) stabilize, or until the well is emptied of water. Periodic measurements of ground water temperature, pH, and conductivity were taken with a Hydac Monitor or other meter and recorded along with the volume of ground water removed from the well. Purging is done by one or more methods singularly or in combination. Bailers, pneumatic or electric sample pumps, or vacuum pump tanks or trucks may be used. The usual amount of water removed is three well volumes. The water collected during purging is either safely stored onsite for later disposition, transported to an approved onsite or offsite sewer discharge system, or an approved onsite or offsite treatment system.

#### Collection of Water Sample for Analysis

The well is allowed to recover after purging and a ground water sample is collected. A fresh bailer is used to collect enough water for the requirements of the laboratory for the analyses needed or required. The water samples are decanted from the bailer into the appropriate number and size containers. These containers are furnished pre-cleaned to exact EPA protocols, with and without preservatives added, by the analytical laboratory or a chemical supply company. The bottles are filled, with no headspace, and then capped with plastic caps with teflon liners.

# WELL SAMPLING DATA SHEET

SITE DP 793	DATE 2-19-02	TIME 920	
WELL MW1	SAMPLED BY. BROADWAY		
WELL ELEVATION			
PRODUCT THICKNESS			
DEPTH TO WATER	14.42	DTB	18.32
FLUID ELEVATION	215.08		
BAILER TYPE	Disposable Bailer		
PUMP	David Pittman		

WELL PURGING RECORD				
TIME	VOLUME REMOVED	TEMP. F°	pH	COND. X1000
927	1 Bailer	66.1	6.78	.18
933	3 gal	<del>69.7</del>	6.74	.20
935	1	69.7	6.57	.21
937	1	69.7	6.45	.21
939	1	68.6	6.44	.21

FINAL VOLUME PURGED	6 gal
TIME SAMPLED	940
SAMPLE ID.	MW1
SAMPLE CONTAINERS	3/40cc VOA's
ANALYSIS TO BE RUN	TP11g BTEX / MTBE
LABORATORY	USE KITT
NOTES:	1 <sup>st</sup> Bailer CLEAR No Odor

## WELL SAMPLING DATA SHEET

SITE DP 793	DATE 2-19-02	TIME 9:45
WELL RS-2	SAMPLED BY. BROADWAY	
WELL ELEVATION		
PRODUCT THICKNESS		
DEPTH TO WATER	8.08	DTB 18.4
FLUID ELEVATION	219.31	
BAILER TYPE	Disposable Bailer	
PUMP	David Pittman	

WELL PURGING RECORD				
TIME	VOLUME REMOVED	TEMP. F°	pH	COND. X1000
950	1 Bailer	63.1	7.53	.72
955	12 gal	65.8	7.46	.86
957	1	66.8	7.38	.88
959	1	66.8	7.39	.88

FINAL VOLUME PURGED	14 gal
TIME SAMPLED	1000
SAMPLE ID.	RS-2
SAMPLE CONTAINERS	3/40cc VOA's
ANALYSIS TO BE RUN	TPLIG BTEX / MTBE
LABORATORY	NSC Kiff
NOTES:	1st Bailer stained No Drip

## WELL SAMPLING DATA SHEET

SITE	DP 793	DATE	2-19-02	TIME	1034
WELL	RS-5	SAMPLED BY.	BROADWAY		
WELL ELEVATION					
PRODUCT THICKNESS					
DEPTH TO WATER		14.8	DTB		39.2
FLUID ELEVATION		<del>213.64</del>	212.81		
BAILER TYPE		Disposable Bailer			
PUMP		David Pittman			

WELL PURGING RECORD				
TIME	VOLUME REMOVED	TEMP. F°	pH	COND. X1000
1036	1 Bailer	63.8		.52
1050	70 gal	63.7	7.75	.48
1052	1	65.2	7.61	.37
1054	1	66.0	7.51	.37
1056	1	65.9	7.50	.37

FINAL VOLUME PURGED	73 gal
TIME SAMPLED	1105
SAMPLE ID.	RS-5
SAMPLE CONTAINERS	3/40cc VOA's
ANALYSIS TO BE RUN	TP11g BTEX / MTBE
LABORATORY	<del>AST</del> Kiff
NOTES:	1st Bailer Turbid Some Odor

## WELL SAMPLING DATA SHEET

SITE DP 793	DATE 2-19-02	TIME 1002
WELL RS-6	SAMPLED BY. BROADWAY	
WELL ELEVATION		
PRODUCT THICKNESS		
DEPTH TO WATER	11.08	DTB 34.02
FLUID ELEVATION	216.14	
BAILER TYPE	Disposable Bailer	
PUMP	DAVID PITTMAN	

WELL PURGING RECORD				
TIME	VOLUME REMOVED	TEMP. F°	pH	COND. X1000
1004	1 Bailer	69.4	7.61	50
1013	40 gal	64.7	7.22	48
1015	1	65.5	7.24	.50
1017	1	65.7	7.24	.50

FINAL VOLUME PURGED	42 gal
TIME SAMPLED	1018
SAMPLE ID.	RS-6
SAMPLE CONTAINERS	3/40cc VORs
ANALYSIS TO BE RUN	TP11g BTEX / MTBE
LABORATORY	USE Kiff
NOTES:	1 <sup>ST</sup> Bailer Stained No Cd

## WELL SAMPLING DATA SHEET

SITE	DP 793	DATE	2-19-02	TIME	12:10
WELL	R57	SAMPLED BY.	BROADWAY		
WELL ELEVATION					
PRODUCT THICKNESS					
DEPTH TO WATER		5.91	DTB		7.0
FLUID ELEVATION		192.08			
BAILER TYPE		Disposable Bailer			
PUMP		David Pittman			

WELL PURGING RECORD				
TIME	VOLUME REMOVED	TEMP. F°	pH	COND. X1000
12:21	1 Bailer	64.0	7.18	.35
12:23	8 gal	64.2	7.15	.34
12:28	1	64.6	7.09	.35
12:29	1	64.4	7.10	.35

FINAL VOLUME PURGED	10 gal
TIME SAMPLED	12:30
SAMPLE ID.	R57
SAMPLE CONTAINERS	3/40cc VOA's
ANALYSIS TO BE RUN	TP116 BTEX/MTBE
LABORATORY	<del>NSF</del> Kiff
NOTES:	1 <sup>st</sup> Bailer Turbid Strong Odor

## WELL SAMPLING DATA SHEET

SITE <i>DP 793</i>	DATE <i>2-19-02</i>	TIME <i>1146</i>
WELL <i>RS8</i>	SAMPLED BY. <i>BROADWAY</i>	
WELL ELEVATION		
PRODUCT THICKNESS		
DEPTH TO WATER <i>7.69 DTB 14.4</i>		
FLUID ELEVATION <i>206.98</i>		
BAILER TYPE <i>Disposable Bailer</i>		
PUMP <i>David Pittman</i>		

WELL PURGING RECORD				
TIME	VOLUME REMOVED	TEMP. F°	pH	COND. X1000
<i>1148</i>	<i>1 Bailer</i>	<i>63.1</i>	<i>7.52</i>	<i>.39</i>
<i>1149</i>	<i>4 gal</i>	<i>63.7</i>	<i>7.45</i>	<i>.40</i>
<i>1150</i>	<i>1</i>	<i>64.2</i>	<i>7.36</i>	<i>.41</i>
<i>1151</i>	<i>1</i>	<i>64.3</i>	<i>7.34</i>	<i>.41</i>

FINAL VOLUME PURGED <i>3 gal</i>
TIME SAMPLED <i>1152</i>
SAMPLE ID. <i>RS8</i>
SAMPLE CONTAINERS <i>3/40cc VOA's</i>
ANALYSIS TO BE RUN <i>TP11g BTEX/MTBE</i>
LABORATORY <i>USE KIFF</i>
NOTES: <i>1st Bailer sitty slight odor</i>



## WELL SAMPLING DATA SHEET

SITE <i>DP 793</i>	DATE <i>2-19-02</i>	TIME <i>1206</i>
WELL <i>RS9</i>	SAMPLED BY. <i>BROADWAY</i>	
WELL ELEVATION		
PRODUCT THICKNESS		
DEPTH TO WATER	<i>4.99</i>	DTB <i>12.3</i>
FLUID ELEVATION	<del><i>190.64</i></del>	
BAILER TYPE	<i>Disposable Bailer</i>	
PUMP	<i>David Pittman</i>	

WELL PURGING RECORD				
TIME	VOLUME REMOVED	TEMP. F°	pH	COND. X1000
<i>1206</i>	<i>1 Bailer</i>	<i>63.2</i>	<i>7.58</i>	<i>.38</i>
<i>1209</i>	<i>4 gal</i>	<i>63.7</i>	<i>7.49</i>	<i>.36</i>
<i>1210</i>	<i>1</i>	<i>64.1</i>	<i>7.41</i>	<i>.36</i>
<i>1211</i>	<i>1</i>	<i>64.3</i>	<i>7.40</i>	<i>.36</i>

FINAL VOLUME PURGED	<i>6 gal</i>
TIME SAMPLED	<i>1212</i>
SAMPLE ID.	<i>RS9</i>
SAMPLE CONTAINERS	<i>3/40cc VORs</i>
ANALYSIS TO BE RUN	<i>TP11g BTEX / MTBE</i>
LABORATORY	<i>USE Kiff</i>
NOTES:	<i>1st Bailer Silty No Odor</i>

## WELL SAMPLING DATA SHEET

SITE	OP 793	DATE	2-19-02	TIME	1200
WELL	RS10	SAMPLED BY.	BROADWAY		
WELL ELEVATION					
PRODUCT THICKNESS					
DEPTH TO WATER	2.29	DTB	9.6		
FLUID ELEVATION	206.17				
BAILER TYPE	Disposable Bailer				
PUMP	DAVID PITTMAN				

WELL PURGING RECORD				
TIME	VOLUME REMOVED	TEMP. F°	pH	COND. X1000
1201	1 Bailer	63.5	7.77	.30
1202	4 gal	63.7	7.67	.29
1203	1	63.9	7.58	.29
1204	1	64.0	7.59	.29

FINAL VOLUME PURGED	3 gal
TIME SAMPLED	1205
SAMPLE ID.	RS10
SAMPLE CONTAINERS	3/40cc VOA's
ANALYSIS TO BE RUN	TP116 BTEX / MTBE
LABORATORY	NSC Kiff
NOTES:	1 <sup>st</sup> Bailer Silty Strong Odor

## WELL SAMPLING DATA SHEET

SITE <i>OP 793</i>	DATE <i>2-19-02</i>	TIME <i>1110</i>
WELL <i>R1</i>	SAMPLED BY. <i>BROADWAY</i>	
WELL ELEVATION		
PRODUCT THICKNESS		
DEPTH TO WATER	<i>10.86</i>	DTB <i>16.92</i>
FLUID ELEVATION	<i>216.83</i>	
BAILER TYPE	<i>Disposable Bailer</i>	
PUMP	<i>DAVID PITTMAN</i>	

WELL PURGING RECORD				
TIME	VOLUME REMOVED	TEMP. F°	pH	COND. X1000
<i>1112</i>	<i>1 Bailer</i>	<i>62.2</i>	<i>7.42</i>	<i>.15</i>
<i>1118</i>	<i>24 gal</i>	<i>64.1</i>	<i>7.66</i>	<i>.15</i>
<i>1120</i>	<i>1</i>	<i>64.2</i>	<i>7.52</i>	<i>.15</i>
<i>1122</i>	<i>1</i>	<i>64.1</i>	<i>7.43</i>	<i>.15</i>
<i>1124</i>	<i>1</i>	<i>64.1</i>	<i>7.42</i>	<i>1.5</i>

FINAL VOLUME PURGED	<i>27 gal</i>
TIME SAMPLED	<i>1125</i>
SAMPLE ID.	<i>R1</i>
SAMPLE CONTAINERS	<i>3/40cc VOA's</i>
ANALYSIS TO BE RUN	<i>TP11g BTEX/MTBE</i>
LABORATORY	<i>USE KIPP</i>
NOTES:	<i>1<sup>ST</sup> Bailer Clear Some Odor</i>

## WELL SAMPLING DATA SHEET

SITE	DP 793	DATE	2-19-02	TIME	1020
WELL	R2	SAMPLED BY.	BROADWAY		
WELL ELEVATION					
PRODUCT THICKNESS					
DEPTH TO WATER		11.32	DTB	16.8	
FLUID ELEVATION		215.96			
BAILER TYPE		Disposable Bailer			
PUMP		David Pittman			

WELL PURGING RECORD				
TIME	VOLUME REMOVED	TEMP. F°	pH	COND. X1000
1022	1 Bailer	64.0	7.23	.64
1027	16 gal	64.1	7.19	.66
1029	1	64.2	7.26	.66

FINAL VOLUME PURGED	17 gal
TIME SAMPLED	1030
SAMPLE ID.	R2
SAMPLE CONTAINERS	3/40cc VOA's
ANALYSIS TO BE RUN	TP11g BTEX/MTBE
LABORATORY	USE Kiff
NOTES:	1 <sup>st</sup> Bailer CLEAR No ODR

## WELL SAMPLING DATA SHEET

SITE DP 793	DATE 2-19-02	TIME 1127
WELL R3	SAMPLED BY. BROADWAY	
WELL ELEVATION		
PRODUCT THICKNESS		
DEPTH TO WATER	7.86	DTB 11.24
FLUID ELEVATION	219.39	
BAILER TYPE	Disposable Bailer	
PUMP	David Pittman	

WELL PURGING RECORD				
TIME	VOLUME REMOVED	TEMP. F°	pH	COND. X1000
1128	1 Bailer	64.4	7.03	.60
1134	12 gal	65.6	7.02	.65
1136	1	65.1	7.08	.75
1138	1	66.0	7.19	.76
1140	1	66.1	7.20	.76

FINAL VOLUME PURGED	15 gal
TIME SAMPLED	1141
SAMPLE ID.	R3
SAMPLE CONTAINERS	3/40cc VOA's
ANALYSIS TO BE RUN	TP11g BTEX/MTRE
LABORATORY	USE Kiff
NOTES:	1 <sup>ST</sup> Bailer CLEAR slight odor


## WELL SAMPLING DATA SHEET

SITE DP 793	DATE 2-19-02	TIME
WELL T1	SAMPLED BY. BROADWAY	
WELL ELEVATION		
PRODUCT THICKNESS		
DEPTH TO WATER	1.96	DTB 14.4
FLUID ELEVATION	193.15	
BAILER TYPE	Disposable Bailer	
PUMP	David Pittman	

WELL PURGING RECORD				
TIME	VOLUME REMOVED	TEMP. F°	pH	COND. X1000
	1 Bailer	62.7	7.51	.52
	30 gal	63.5	7.44	.67
		64.1	7.39	.68
		64.2	7.37	.68

FINAL VOLUME PURGED	gal
TIME SAMPLED	12:35
SAMPLE ID.	T1
SAMPLE CONTAINERS	3/40cc VOA's
ANALYSIS TO BE RUN	TP16 BTEX/MTBE
LABORATORY	USE Kiff
NOTES:	1 <sup>st</sup> Bailer Turbid Strong Odor

TAXES




- MW1 = 18.32
- RS2 = 13.40
- R3 = ~~11.74~~
- R2 = 16.8
- RS5 = 37.20
- R1 = 16.92
- RS6 = 34.02
- RS7 = 7.0
- RS8 = 14.4
- RS9 = 12.3
- RS10 = 9.6

FIGURE 3

SITE BASE MAP

DESERT PETROLEUM STATION #793  
 4035 PARK BLVD..  
 OAKLAND, CALIFORNIA 94602



30-113 → 24 Approved

28 29



720 Olive Drive, Suite D  
 Davis, CA 95616  
 Lab: 530.297.4800  
 Fax: 530.297.4803

Lab No. \_\_\_\_\_ Page 1 of 2

Project Contact (Hardcopy or PDF To):  
*George Casanova*

EDF Report?  Yes  No

**Chain-of-Custody Record and Analysis Request**

Company/Address:  
*1396 E. Deane St. Woodland*

Recommended but not mandatory to complete this section:  
 Sampling Company Log Code: \_\_\_\_\_

Phone No.: *530 609 5300* FAX No.: *530 622 6200*

Global ID: \_\_\_\_\_

Project Number: *DI 793* P.O. No.: \_\_\_\_\_

EDF Deliverable To (Email Address):  
*weje@ngoh.com*

Project Address:  
*4155 Hank Blvd Oak*

Sampler Signature:  
*[Signature]*

Project Name:  
*DI 793*

Sample Designation	Sampling		40 ml VOA	SLEEVE	Container	Preservative				Matrix		BTEX (8021B)	BTEX/TPH Gas/MTBE (8021B/M8015)	TPH as Diesel (M8015)	TPH as Motor Oil (M8015)	TPH Gas/BTEX/MTBE (8260B)	5 Oxygenates/TPH Gas/BTEX (8260B)	7 Oxygenates/TPH Gas/BTEX (8260B)	5 Oxygenates (8260B)	7 Oxygenates (8260B)	Lead Scav. (1,2 DCA & 1,2 EDB - 8260B)	EPA 8260B (Full List)	Volatile Halocarbons (EPA 8260B)	Lead (7421/239.2) TOTAL (X) W.E.T. (X)	TAT	12 hr/24 hr/48 hr/72 hr/96 hr	For Lab Use Only			
	Date	Time				HCl	HNO <sub>3</sub>	ICE	NONE	WATER	SOIL																			
<i>R1</i>	<i>2/17/02</i>	<i>1125</i>	<i>3</i>																											
<i>R2</i>		<i>1030</i>																												
<i>R3</i>		<i>1141</i>																												
<i>MW1</i>		<i>940</i>																												
<i>R52</i>		<i>1000</i>																												
<i>R55</i>		<i>1105</i>																												
<i>R56</i>		<i>1218</i>																												
<i>R57</i>		<i>1230</i>																												
<i>R58</i>		<i>1202</i>																												
<i>R59</i>		<i>1551</i>																												

Relinquished by: *[Signature]* Date: *2/21/02* Time: *1125*

Received by: \_\_\_\_\_

Remarks:

Relinquished by: \_\_\_\_\_ Date: \_\_\_\_\_ Time: \_\_\_\_\_

Received by: \_\_\_\_\_

Relinquished by: \_\_\_\_\_ Date: *022102* Time: *1205*

Received by Laboratory: *[Signature]* KIFF ANALYTICAL

Bill to:





720 Olive Drive, Suite D  
 Davis, CA 95616  
 Lab: 530.297.4800  
 Fax: 530.297.4803

Lab No. \_\_\_\_\_ Page 2 of 2

Project Contact (Hardcopy or PDF To):

*George Converse*

EDF Report?  Yes  No

**Chain-of-Custody Record and Analysis Request**

Company/Address:

*1326 E. Bender*

Recommended but not mandatory to complete this section:

Sampling Company Log Code: \_\_\_\_\_

Phone No.:

*530-662-5300*

FAX No.:

Global ID:

Project Number:

P.O. No.:

EDF Deliverable To (Email Address):

Project Address:

*4035 Park Blvd*

Sampler Signature:

*[Signature]*

Project Name:

*12P 793*

Sampling

Container

Preservative

Matrix

**Sample Designation**

Date

Time

40 ml VOA

SLEEVE

HCl

HNO<sub>3</sub>

ICE

NONE

WATER

SOIL

BTEX (8021B)

BTEX/TPH Gas/MTBE (8021B/M8015)

TPH as Diesel (M8015)

TPH as Motor Oil (M8015)

TPH Gas/BTEX/MTBE (8260B)

5 Oxygenates/TPH Gas/BTEX (8260B)

7 Oxygenates/TPH Gas/BTEX (8260B)

5 Oxygenates (8260B)

7 Oxygenates (8260B)

Lead Scav. (1,2 DCA & 1,2 EDB - 8260B)

EPA 8260B (Full List)

Volatile Halocarbons (EPA 8260B)

Lead (7421/239.2) TOTAL (X) W.E.T. (X)

TAT

12 hr/24 hr/48 hr/72 hr/1 wk

For Lab Use Only

*RS10*  
*T1*  
*Carton Discharge*

*2/19/02* *1212*  
*1* *1235*  
*1* *1100*

Relinquished by:

*[Signature]*

Date

*2/21/02*

Time

*1605*

Received by:

\_\_\_\_\_

Remarks:

Relinquished by:

\_\_\_\_\_

Relinquished by:

\_\_\_\_\_

Date

*022102*

Time

*1605*


Received by Laboratory:

*[Signature]* / **KIFF ANALYTICAL**

Bill to:

APPENDIX B.  
GROUNDWATER ELEVATION CHART

### Groundwater Elevation





Report Number : 24919

Date : 3/6/02

George Converse  
Western Geo-Engineers  
1386 East Beamer St.  
Woodland, CA 95776

Subject : 13 Water Samples  
Project Name : DP793  
Project Number : DP793

Dear Mr. Converse,

Chemical analysis of the samples referenced above has been completed. Summaries of the data are contained on the following pages. Sample(s) were received under documented chain-of-custody. US EPA protocols for sample storage and preservation were followed.

Kiff Analytical is certified by the State of California (# 2236). If you have any questions regarding procedures or results, please call me at 530-297-4800.

Sincerely,



Joel Kiff




Report Number : 24919

Date : 3/6/02

Subject : 13 Water Samples  
Project Name : DP793  
Project Number : DP793

## Case Narrative

Matrix Spike/Matrix Spike Duplicate Results associated with samples R1, R3, RS8, RS6, RS10, CARBON DISCHARGE, MW1, RS2, RS9, T1, RS5, RS7, R2 for the analytes Benzene, Toluene were affected by the analyte concentrations already present in the un-spiked sample.

Approved By:  \_\_\_\_\_  
Joel Kiff

720 Olive Drive, Suite D Davis, CA 95616 916-297-4800



Report Number : 24919

Date : 3/6/02

Project Name : DP793

Project Number : DP793

Sample : R1

Matrix : Water

Lab Number : 24919-01

Sample Date :2/19/02

Parameter	Measured Value	Method Reporting Limit	Units	Analysis Method	Date Analyzed
<b>Benzene</b>	< 0.50	0.50	ug/L	EPA 8260B	3/3/02
<b>Toluene</b>	< 0.50	0.50	ug/L	EPA 8260B	3/3/02
<b>Ethylbenzene</b>	< 0.50	0.50	ug/L	EPA 8260B	3/3/02
<b>Total Xylenes</b>	< 0.50	0.50	ug/L	EPA 8260B	3/3/02
<b>Methyl-t-butyl ether (MTBE)</b>	< 0.50	0.50	ug/L	EPA 8260B	3/3/02
<b>TPH as Gasoline</b>	< 50	50	ug/L	EPA 8260B	3/3/02
Toluene - d8 (Surr)	102		% Recovery	EPA 8260B	3/3/02
4-Bromofluorobenzene (Surr)	103		% Recovery	EPA 8260B	3/3/02

Sample : R2

Matrix : Water

Lab Number : 24919-02

Sample Date :2/19/02

Parameter	Measured Value	Method Reporting Limit	Units	Analysis Method	Date Analyzed
<b>Benzene</b>	1200	5.0	ug/L	EPA 8260B	3/5/02
<b>Toluene</b>	< 5.0	5.0	ug/L	EPA 8260B	3/5/02
<b>Ethylbenzene</b>	14	5.0	ug/L	EPA 8260B	3/5/02
<b>Total Xylenes</b>	< 5.0	5.0	ug/L	EPA 8260B	3/5/02
<b>Methyl-t-butyl ether (MTBE)</b>	< 5.0	5.0	ug/L	EPA 8260B	3/5/02
<b>TPH as Gasoline</b>	2100	500	ug/L	EPA 8260B	3/5/02
Toluene - d8 (Surr)	101		% Recovery	EPA 8260B	3/5/02
4-Bromofluorobenzene (Surr)	101		% Recovery	EPA 8260B	3/5/02

Approved By:  Joel Kiff



Report Number : 24919

Date : 3/6/02

Project Name : DP793

Project Number : DP793

Sample : R3

Matrix : Water

Lab Number : 24919-03

Sample Date :2/19/02

Parameter	Measured Value	Method Reporting Limit	Units	Analysis Method	Date Analyzed
Benzene	< 0.50	0.50	ug/L	EPA 8260B	3/3/02
Toluene	< 0.50	0.50	ug/L	EPA 8260B	3/3/02
Ethylbenzene	< 0.50	0.50	ug/L	EPA 8260B	3/3/02
Total Xylenes	< 0.50	0.50	ug/L	EPA 8260B	3/3/02
Methyl-t-butyl ether (MTBE)	< 0.50	0.50	ug/L	EPA 8260B	3/3/02
TPH as Gasoline	< 50	50	ug/L	EPA 8260B	3/3/02
Toluene - d8 (Surr)	102		% Recovery	EPA 8260B	3/3/02
4-Bromofluorobenzene (Surr)	103		% Recovery	EPA 8260B	3/3/02

Sample : MW1

Matrix : Water

Lab Number : 24919-04

Sample Date :2/19/02

Parameter	Measured Value	Method Reporting Limit	Units	Analysis Method	Date Analyzed
Benzene	< 0.50	0.50	ug/L	EPA 8260B	3/4/02
Toluene	< 0.50	0.50	ug/L	EPA 8260B	3/4/02
Ethylbenzene	< 0.50	0.50	ug/L	EPA 8260B	3/4/02
Total Xylenes	< 0.50	0.50	ug/L	EPA 8260B	3/4/02
Methyl-t-butyl ether (MTBE)	< 0.50	0.50	ug/L	EPA 8260B	3/4/02
TPH as Gasoline	< 50	50	ug/L	EPA 8260B	3/4/02
Toluene - d8 (Surr)	106		% Recovery	EPA 8260B	3/4/02
4-Bromofluorobenzene (Surr)	99.8		% Recovery	EPA 8260B	3/4/02

Approved By:  Joel Kiff

720 Olive Drive, Suite D Davis, CA 95616 530-297-4800



Report Number : 24919

Date : 3/6/02

Project Name : DP793

Project Number : DP793

Sample : RS2

Matrix : Water

Lab Number : 24919-05

Sample Date :2/19/02

Parameter	Measured Value	Method Reporting Limit	Units	Analysis Method	Date Analyzed
Benzene	< 0.50	0.50	ug/L	EPA 8260B	3/4/02
Toluene	< 0.50	0.50	ug/L	EPA 8260B	3/4/02
Ethylbenzene	< 0.50	0.50	ug/L	EPA 8260B	3/4/02
Total Xylenes	< 0.50	0.50	ug/L	EPA 8260B	3/4/02
Methyl-t-butyl ether (MTBE)	< 0.50	0.50	ug/L	EPA 8260B	3/4/02
TPH as Gasoline	< 50	50	ug/L	EPA 8260B	3/4/02
Toluene - d8 (Surr)	106		% Recovery	EPA 8260B	3/4/02
4-Bromofluorobenzene (Surr)	98.5		% Recovery	EPA 8260B	3/4/02

Sample : RS5

Matrix : Water

Lab Number : 24919-06

Sample Date :2/19/02

Parameter	Measured Value	Method Reporting Limit	Units	Analysis Method	Date Analyzed
Benzene	460	5.0	ug/L	EPA 8260B	3/5/02
Toluene	1700	5.0	ug/L	EPA 8260B	3/5/02
Ethylbenzene	680	5.0	ug/L	EPA 8260B	3/5/02
Total Xylenes	4000	5.0	ug/L	EPA 8260B	3/5/02
Methyl-t-butyl ether (MTBE)	< 5.0	5.0	ug/L	EPA 8260B	3/5/02
TPH as Gasoline	22000	500	ug/L	EPA 8260B	3/5/02
Toluene - d8 (Surr)	102		% Recovery	EPA 8260B	3/5/02
4-Bromofluorobenzene (Surr)	105		% Recovery	EPA 8260B	3/5/02

Approved By:  Joel Kiff

720 Olive Drive, Suite D Davis, CA 95616 530-297-4800





Report Number : 24919

Date : 3/6/02

Project Name : DP793

Project Number : DP793

Sample : RS6

Matrix : Water

Lab Number : 24919-07

Sample Date :2/19/02

Parameter	Measured Value	Method Reporting Limit	Units	Analysis Method	Date Analyzed
Benzene	< 0.50	0.50	ug/L	EPA 8260B	3/3/02
Toluene	< 0.50	0.50	ug/L	EPA 8260B	3/3/02
Ethylbenzene	0.60	0.50	ug/L	EPA 8260B	3/3/02
Total Xylenes	< 0.50	0.50	ug/L	EPA 8260B	3/3/02
Methyl-t-butyl ether (MTBE)	< 0.50	0.50	ug/L	EPA 8260B	3/3/02
TPH as Gasoline	< 50	50	ug/L	EPA 8260B	3/3/02
Toluene - d8 (Surr)	104		% Recovery	EPA 8260B	3/3/02
4-Bromofluorobenzene (Surr)	99.2		% Recovery	EPA 8260B	3/3/02


Sample : RS7

Matrix : Water

Lab Number : 24919-08

Sample Date :2/19/02

Parameter	Measured Value	Method Reporting Limit	Units	Analysis Method	Date Analyzed
Benzene	2600	10	ug/L	EPA 8260B	3/5/02
Toluene	360	10	ug/L	EPA 8260B	3/5/02
Ethylbenzene	570	10	ug/L	EPA 8260B	3/5/02
Total Xylenes	1900	10	ug/L	EPA 8260B	3/5/02
Methyl-t-butyl ether (MTBE)	11	10	ug/L	EPA 8260B	3/5/02
TPH as Gasoline	20000	1000	ug/L	EPA 8260B	3/5/02
Toluene - d8 (Surr)	101		% Recovery	EPA 8260B	3/5/02
4-Bromofluorobenzene (Surr)	102		% Recovery	EPA 8260B	3/5/02

Approved By:  Joel Kiff

720 Olive Drive, Suite D Davis, CA 95616 530-297-4800



Report Number : 24919

Date : 3/6/02

Project Name : DP793

Project Number : DP793

Sample : RS8

Matrix : Water

Lab Number : 24919-09

Sample Date :2/19/02

Parameter	Measured Value	Method Reporting Limit	Units	Analysis Method	Date Analyzed
<b>Benzene</b>	33	0.50	ug/L	EPA 8260B	3/3/02
<b>Toluene</b>	21	0.50	ug/L	EPA 8260B	3/3/02
<b>Ethylbenzene</b>	5.1	0.50	ug/L	EPA 8260B	3/3/02
<b>Total Xylenes</b>	45	0.50	ug/L	EPA 8260B	3/3/02
<b>Methyl-t-butyl ether (MTBE)</b>	< 0.50	0.50	ug/L	EPA 8260B	3/3/02
<b>TPH as Gasoline</b>	780	50	ug/L	EPA 8260B	3/3/02
Toluene - d8 (Surr)	102		% Recovery	EPA 8260B	3/3/02
4-Bromofluorobenzene (Surr)	102		% Recovery	EPA 8260B	3/3/02

Sample : RS9

Matrix : Water

Lab Number : 24919-10

Sample Date :2/19/02

Parameter	Measured Value	Method Reporting Limit	Units	Analysis Method	Date Analyzed
<b>Benzene</b>	< 0.50	0.50	ug/L	EPA 8260B	3/3/02
<b>Toluene</b>	< 0.50	0.50	ug/L	EPA 8260B	3/3/02
<b>Ethylbenzene</b>	< 0.50	0.50	ug/L	EPA 8260B	3/3/02
<b>Total Xylenes</b>	< 0.50	0.50	ug/L	EPA 8260B	3/3/02
<b>Methyl-t-butyl ether (MTBE)</b>	< 0.50	0.50	ug/L	EPA 8260B	3/3/02
<b>TPH as Gasoline</b>	< 50	50	ug/L	EPA 8260B	3/3/02
Toluene - d8 (Surr)	102		% Recovery	EPA 8260B	3/3/02
4-Bromofluorobenzene (Surr)	100		% Recovery	EPA 8260B	3/3/02

Approved By:  Joel Kiff



Report Number : 24919

Date : 3/6/02

Project Name : DP793

Project Number : DP793

Sample : RS10

Matrix : Water

Lab Number : 24919-11

Sample Date :2/19/02

Parameter	Measured Value	Method Reporting Limit	Units	Analysis Method	Date Analyzed
<b>Benzene</b>	< 0.50	0.50	ug/L	EPA 8260B	3/3/02
<b>Toluene</b>	< 0.50	0.50	ug/L	EPA 8260B	3/3/02
<b>Ethylbenzene</b>	< 0.50	0.50	ug/L	EPA 8260B	3/3/02
<b>Total Xylenes</b>	< 0.50	0.50	ug/L	EPA 8260B	3/3/02
<b>Methyl-t-butyl ether (MTBE)</b>	< 0.50	0.50	ug/L	EPA 8260B	3/3/02
<b>TPH as Gasoline</b>	< 50	50	ug/L	EPA 8260B	3/3/02
Toluene - d8 (Surr)	105		% Recovery	EPA 8260B	3/3/02
4-Bromofluorobenzene (Surr)	98.9		% Recovery	EPA 8260B	3/3/02


Sample : T1

Matrix : Water

Lab Number : 24919-12

Sample Date :2/19/02

Parameter	Measured Value	Method Reporting Limit	Units	Analysis Method	Date Analyzed
<b>Benzene</b>	8600	50	ug/L	EPA 8260B	3/5/02
<b>Toluene</b>	6000	50	ug/L	EPA 8260B	3/5/02
<b>Ethylbenzene</b>	1700	50	ug/L	EPA 8260B	3/5/02
<b>Total Xylenes</b>	6800	50	ug/L	EPA 8260B	3/5/02
<b>Methyl-t-butyl ether (MTBE)</b>	55	50	ug/L	EPA 8260B	3/5/02
<b>TPH as Gasoline</b>	64000	5000	ug/L	EPA 8260B	3/5/02
Toluene - d8 (Surr)	97.7		% Recovery	EPA 8260B	3/5/02
4-Bromofluorobenzene (Surr)	103		% Recovery	EPA 8260B	3/5/02

Approved By:  Joel Kiff

720 Olive Drive, Suite D Davis, CA 95616 530-297-4800



Report Number : 24919

Date : 3/6/02

Project Name : DP793

Project Number : DP793

Sample : CARBON DISCHARGE

Matrix : Water

Lab Number : 24919-13

Sample Date : 2/19/02

Parameter	Measured Value	Method Reporting Limit	Units	Analysis Method	Date Analyzed
Benzene	< 0.50	0.50	ug/L	EPA 8260B	3/3/02
Toluene	< 0.50	0.50	ug/L	EPA 8260B	3/3/02
Ethylbenzene	< 0.50	0.50	ug/L	EPA 8260B	3/3/02
Total Xylenes	< 0.50	0.50	ug/L	EPA 8260B	3/3/02
Methyl-t-butyl ether (MTBE)	< 0.50	0.50	ug/L	EPA 8260B	3/3/02
TPH as Gasoline	< 50	50	ug/L	EPA 8260B	3/3/02
Toluene - d8 (Surr)	105		% Recovery	EPA 8260B	3/3/02
4-Bromofluorobenzene (Surr)	98.8		% Recovery	EPA 8260B	3/3/02

Approved By:  Joel Kiff

720 Olive Drive, Suite D Davis, CA 95616 530-297-4800

Report Number : 24919

Date : 3/6/02

**QC Report : Method Blank Data**

Project Name : **DP793**

Project Number : **DP793**

<u>Parameter</u>	<u>Measured Value</u>	<u>Method Reporting Limit</u>	<u>Units</u>	<u>Analysis Method</u>	<u>Date Analyzed</u>
Benzene	< 0.50	0.50	ug/L	EPA 8260B	3/1/02
Toluene	< 0.50	0.50	ug/L	EPA 8260B	3/1/02
Ethylbenzene	< 0.50	0.50	ug/L	EPA 8260B	3/1/02
Total Xylenes	< 0.50	0.50	ug/L	EPA 8260B	3/1/02
Methyl-t-butyl ether (MTBE)	< 0.50	0.50	ug/L	EPA 8260B	3/1/02
TPH as Gasoline	< 50	50	ug/L	EPA 8260B	3/1/02
Toluene - d8 (Surr)	102		%	EPA 8260B	3/1/02
4-Bromofluorobenzene (Surr)	97.8		%	EPA 8260B	3/1/02

<u>Parameter</u>	<u>Measured Value</u>	<u>Method Reporting Limit</u>	<u>Units</u>	<u>Analysis Method</u>	<u>Date Analyzed</u>
------------------	-----------------------	-------------------------------	--------------	------------------------	----------------------

KIFF ANALYTICAL, LLC

720 Olive Drive, Suite D Davis, CA 95616 530-297-4800

Approved By: Joel Kiff  


Report Number : 24919

Date : 3/6/02

QC Report : Matrix Spike/ Matrix Spike Duplicate


Project Name : DP793

Project Number : DP793

Parameter	Spiked Sample	Sample Value	Spike Level	Spike Dup. Level	Spiked Sample Value	Duplicate Spiked Sample Value	Units	Analysis Method	Date Analyzed	Spiked Sample Percent Recov.	Duplicate Spiked Sample Percent Recov.	Relative Percent Diff.	Spiked Sample Percent Recov. Limit	Relative Percent Diff. Limit
Benzene	24919-09	33	18.7	20.0	41.7	44.3	ug/L	EPA 8260B	3/1/02	44.3	54.2	20.0	70-130	25
Toluene	24919-09	21	18.7	20.0	30.7	33.6	ug/L	EPA 8260B	3/1/02	50.6	62.0	20.1	70-130	25
Tert-Butanol	24919-09	<5.0	93.6	100	87.7	90.6	ug/L	EPA 8260B	3/1/02	93.6	90.5	3.44	70-130	25
Methyl-t-Butyl Ether	24919-09	<0.50	18.7	20.0	18.3	15.6	ug/L	EPA 8260B	3/1/02	97.8	78.0	22.6	70-130	25

KIFF ANALYTICAL, LLC

720 Olive Drive, Suite D Davis, CA 95616 530-297-4800

Approved By:  Joel Kiff

Report Number : 24919

Date : 3/6/02

QC Report : Laboratory Control Sample (LCS)

Project Name : DP793

Project Number : DP793

Parameter	Spike Level	Units	Analysis Method	Date Analyzed	LCS Percent Recov.	LCS Percent Recov. Limit
Benzene	20.0	ug/L	EPA 8260B	3/2/02	95.6	70-130
Toluene	20.0	ug/L	EPA 8260B	3/2/02	91.3	70-130
Tert-Butanol	100	ug/L	EPA 8260B	3/2/02	88.8	70-130
Methyl-t-Butyl Ether	20.0	ug/L	EPA 8260B	3/2/02	97.4	70-130

KIFF ANALYTICAL, LLC

720 Olive Drive, Suite D Davis, CA 95616 530-297-4800

Approved By:  \_\_\_\_\_  
Joel Kiff







720 Olive Drive, Suite D  
 Davis, CA 95616  
 Lab: 530.297.4800  
 Fax: 530.297.4803

Lab No. 24919

Page 2 of 2

Project Contact (Hardcopy or PDF To): George Converse

Company/Address: 1386 E. Beamer

Phone No.: 530-668-5300 FAX No.: \_\_\_\_\_

Project Number: \_\_\_\_\_ P.O. No.: \_\_\_\_\_

EDF Report?  Yes  No

Recommended but not mandatory to complete this section:  
 Sampling Company Log Code: \_\_\_\_\_

Global ID: \_\_\_\_\_

EDF Deliverable To (Email Address): \_\_\_\_\_

**Chain-of-Custody Record and Analysis Request**

Project Address: 4035 Park Blvd

Project Name: DP 793

Sampler Signature: [Signature]

Analysis Request												TAT											
Sample Designation	Date	Time	40 ml VOA	SLEEVE	Container	Preservative	Matrix	BTEX (8021B)	BTEX/TPH Gas/MTBE (8021B/MB015)	TPH as Diesel (MB015)	TPH as Motor Oil (MB015)	TPH Gas/BTEX/MTBE (8260B)	5 Oxygenates/TPH Gas/BTEX (8260B)	7 Oxygenates/TPH Gas/BTEX (8260B)	5 Oxygenates (8260B)	7 Oxygenates (8260B)	Lead Scav. (1,2 DCA & 1,2 EDB - 8260B)	EPA 8260B (Full List)	Volatile Halocarbons (EPA 8260B)	Lead (7421/239.2) TOTAL (X) W.E.T. (X)	12 hr / 24 hr / 48 hr / 72 hr	For Lab Use Only	
RS10	2/19/02	1212	3																				-11
TL		1235																					-12
Carbon Discharge		1100																					13

Relinquished by: [Signature] Date: 2/21/02 Time: 1605

Relinquished by: \_\_\_\_\_ Date: \_\_\_\_\_ Time: \_\_\_\_\_

Relinquished by: \_\_\_\_\_ Date: 022102 Time: 1605

Received by: \_\_\_\_\_

Received by: \_\_\_\_\_

Received by Laboratory: [Signature] / KIFF ANALYTICAL


Remarks:

Bill to:


APPENDIX D.

MtBE, TPHg AND BENZENE CHARTS


# MTBE IN WELLS




R-1




R-2




R-3



# RS-1/MW-1 TPHg




# RS-2 TPHg




TPHg  
BENZENE




RS-5




RS-6




RS-7




RS-8




RS-9



RS-10





T-1



APPENDIX E  
HACH SPECTROPHOTOMETER  
FIELD TEST METHODS  
FIGURES  
DISSOLVED OXYGEN  
SULFATE  
NITRATE  
FERROUS IRON









**FIGURE 8**  
 DP 793, 4035 PARK BLVD.  
 OAKLAND, CALIFORNIA  
 GROUNDWATER ELEVATION  
 WITH SULFATE  
 12/18/01.


CONTOURS ARE  
 FEET ABOVE SEA  
 LEVEL

 SO4 < 40 mg/L




0' 20' 50'  
 SCALE: 1 INCH=50 FEET

SO4 35 SULFATE IN PARTS PER MILLION




**FIGURE 9**  
 DP 793, 4035 PARK BLVD.  
 OAKLAND, CALIFORNIA  
 GROUNDWATER ELEVATION  
 WITH NITRATE  
 12/18/01.

CONTOURS ARE  
 FEET ABOVE SEA  
 LEVEL

 NO3 < 2 mg/L


0' 20' 50'  
 SCALE: 1 INCH=50 FEET




0' 20' 50'  
SCALE: 1 INCH=50 FEET

**FIGURE 10**  
DP 793, 4035 PARK BLVD.  
OAKLAND, CALIFORNIA  
GROUNDWATER ELEVATION  
WITH FERROUS IRON  
12/18/01.

CONTOURS ARE  
FEET ABOVE SEA  
LEVEL

 Fe2 > 0.0 mg/L



**FIGURE 10-1**  
**DP 793, 4035 PARK BLVD.**  
**OAKLAND, CALIFORNIA**  
**FEROUS IRON (FE2)**  
**IN GROUNDWATER 8/26/99.**

FE2 FERROUS IRON  
 0.05 IN PARTS PER MILLION

APPENDIX F

November 28, 2001 Letter  
Alameda County Health  
Reference to November 13, 2001 meeting.

ALAMEDA COUNTY  
HEALTH CARE SERVICES

AGENCY  
DAVID J. KEARS, Agency Director



ENVIRONMENTAL HEALTH SERVICES  
ENVIRONMENTAL PROTECTION  
1131 Harbor Bay Parkway, Suite 250  
Alameda, CA 94502-6577  
(510) 567-6700  
FAX (510) 337-9335

November 28, 2001

STID 1248

Mr. Bill Thompson  
Desert Petroleum, Inc.  
P.O. Box 1601  
Oxnard, CA 93032

Re: (former) Desert Petroleum #793, 4035 Park Boulevard, Oakland

Dear Mr. Thompson:

This letter is sent in the wake of our November 13<sup>th</sup> meeting. Your consultant, George Converse of Western Geo-Engineers (WEGE), presented a summary of the current project status and brief history of this case. The scope of the August 29, 2000 WEGE corrective action plan (CAP) proposal was also discussed.

We agreed that the scope of the cited CAP should be revised to reflect positive changes in groundwater impacts observed both on- and off-site over the last two years. For example, reported groundwater concentrations of Benzene in well RS8 have dropped from the 24,000 micrograms per liter(ug/l) observed in August 1999, to 11 ug/l in May 2001. Similar generalized decreases in dissolved-phase concentrations have been observed in all sampled wells, as well as those observed within the Brighton Avenue receptor trench.

As we discussed, the CAP scope now envisioned will still include the introduction of oxygen to the subsurface to support aerobic biodegradation. We discussed the use of batched or metered H<sub>2</sub>O<sub>2</sub>, or oxygen-releasing compounds (ORC) in lieu of air sparging or other engineered approaches. Nutrient augmentation does not appear necessary at this time. In addition, periodic pumping from either the on-site wells or Brighton Avenue receptor trench is also not requested at this time pending evaluation of groundwater impacts after several quarters of oxygen supplementation.

Please submit a revised CAP workplan that reflects the issues presented above, as discussed during the November 13<sup>th</sup> meeting. This workplan is due for submittal within 45 days of the date of this letter.

1/14/02



Mr. Thompson  
Re: 4035 Park Blvd., Oakland  
November 28, 2001  
Page 2 of 2

In addition, quarterly sampling, monitoring, and reporting are to be reinstated beginning the 4<sup>th</sup> quarter 2001.

Please call me at 510/567-6783 should you have any questions.

Sincerely,



Scott O. Seery, CHMM  
Hazardous Materials Specialist

c: Chuck Headlee, RWQCB  
Heron Gomez, Oakland Fire Department  
Steve Marquez, SWRCB UST Fund  
Keith Carson, Board of Supervisors, Alameda County  
Danny Wan, Council Member, City of Oakland  
✓ George Converse, Western Geo-Engineers  
1386 E. Beamer St., Woodland, CA 95776-6003  
Toni Razi, 3609 E. 14<sup>th</sup> St., Oakland, CA 94601  
Alireza Shirazian, 2 Anchor Drive, #F-386, Emeryville, CA 94608  
Derrick Williams, 4032 Brighton Ave., Oakland, CA 94602  
Michael Gabriel, Glenview Neighborhood Assoc.  
4200 Park Blvd., Box 111, Oakland, CA 94602

APPENDIX G

REGENESIS ORC COST CALCULATIONS TO INCREASE  
DISSOLVED OXYGEN IN GROUNDWATER PLUME

February 14, 2002

George Converse  
Western Geo-Engineers  
1386 East Beamer Street  
Woodlands, CA 95776

Phone: 530-668-5300 Fax: 530-668-0273

Subject: Acceleration of Natural Attenuation at the Park Blvd. site - Proposal No. 2510 revision

Dear Mr. Converse:

We have reviewed the information that you provided for the above-referenced site. In the following sections, we provide design and cost information for a potential site remediation approach. This proposal was based upon information provided by your firm. If site conditions have changed significantly please let us know. A new proposal may need to be generated.

### **Use of ORC to Accelerate Bioremediation**

Oxygen Release Compound (ORC) is used to provide terminal electron acceptors to support the oxidative biodegradation of many types of petroleum-based hydrocarbons as well as chlorinated hydrocarbons such as dichloroethenes and vinyl chloride. ORC is a proprietary formulation of magnesium peroxide, designed to provide a timed release of oxygen. ORC is manufactured as a powder, which can be (1) mixed with water for slurry injection into the saturated zone, (2) included in excavation backfill material, or (3) enclosed in specially designed socks for placement in monitoring wells.

The use of ORC for groundwater remediation offers a comparatively simple and cost effective remediation alternative for sites that would otherwise require unacceptably long periods of time for natural attenuation or the high levels of capital investment and operating expense associated with active remediation technologies.

### **Design/Proposal Assumptions**

Using the information you provided, we have made the following assumptions to estimate system design variables and dose amounts.

#### **Area 1**

- Area requiring treatment: 10 feet x 15 feet
- Representative contaminant concentration: 2.7 ppm TPH

- Contaminated saturated zone thickness requiring treatment: 10 feet (top 10 feet of the aquifer)

#### Area 1a

- Area requiring treatment: 165 feet x 15 feet
- Representative contaminant concentration: 48 ppm TPH
- Contaminated saturated zone thickness requiring treatment: 10 feet (top 10 feet of the aquifer)

#### Area 2

- Area requiring treatment: 60 feet x 45 feet
- Representative contaminant concentration: 4.9 ppm TPH
- Contaminated saturated zone thickness requiring treatment: 10 feet (top 10 feet of the aquifer)

#### Area 3

- Area requiring treatment: 60 feet x 45 feet
- Representative contaminant concentration: 12 ppm TPH
- Contaminated saturated zone thickness requiring treatment: 10 feet (top 10 feet of the aquifer)

The design specifications and costs provided below represent a design for an accelerated bioremediation project. This design may need to be adjusted as detailed design and regulatory oversight issues are finalized. For instance, the following design variables may need to be adjusted prior to the implementation:

- Treatment areas may need to be increased or decreased depending on the overall site remediation strategy.
- Exact delivery locations should be selected in the final design process. Delivery locations may need to be adjusted to take into account site features such as underground utilities and other site structures.

<b>ORC Grid Treatment – Area 1</b>	
<b>Design Feature</b>	<b>Specification</b>
Saturated thickness requiring treatment	10 feet
Treatment Area	10 feet x 15 feet
Delivery Pt. Spacing and Configuration	Place into existing wells

ORC dose rate in lbs/vertical foot of injection	N/a
Material requirement	120 pounds
Material cost at \$8.00/lb	\$960

<b>ORC Grid Treatment - Area 1a</b>	
<b>Design Feature</b>	<b>Specification</b>
Saturated thickness requiring treatment	10 feet
Treatment Area	165 feet x 15 feet
Delivery Pt. Spacing and Configuration	Place into existing wells/trench
ORC dose rate in lbs/vertical foot of injection	N/a
Material requirement	6,750 pounds
Material cost at \$8.00/lb	\$54,000

<b>ORC Grid Treatment - Area 2</b>	
<b>Design Feature</b>	<b>Specification</b>
Saturated thickness requiring treatment	10 feet
Treatment Area	60 feet x 45 feet
Delivery Pt. Spacing and Configuration	48 points spaced 8 feet on center throughout the treatment zone
ORC dose rate in lbs/vertical foot of injection	2 lbs/ft (20 lbs/pt)
Material requirement	48 pts. x 10 ft. x 2 lbs/ft = 960 lbs
Material cost at \$8.00/lb	\$7,680

<b>ORC Grid Treatment - Area 3</b>	
<b>Design Feature</b>	<b>Specification</b>
Saturated thickness requiring treatment	10 feet
Treatment Area	60 feet x 45 feet
Delivery Pt. Spacing and Configuration	48 points spaced 8 feet on center throughout the treatment zone
ORC dose rate in lbs/vertical foot of injection	3.9 lbs/ft (39 lbs/pt)

Material requirement	48 pts. x 10 ft. x 3.9 lbs/ft = 1,860 lbs
Material cost at \$8.00/lb	\$14,880

### **ORC Oxygen Barrier**

A 100 foot oxygen barrier would require 400 pounds of ORC to construct. The construction of the barrier would require two rows of 10 geoprobe points. Each row would be 100 feet long and the points within the row would be spaced 10 feet on center. The two rows would be 10 feet apart and offset by 5 feet. Each point would be injected with 20 pounds of ORC throughout the 10 foot contaminated saturated zone. The cost of each application of the barrier is \$3,200.

### **Total Project Cost**

The total cost of an accelerated bioremediation project can be estimated as the sum of the following items:

- ORC material and shipping costs.
- ORC compound application fieldwork costs. Customers are responsible for selecting a local injection/application subcontractor.
- Groundwater monitoring well construction (if necessary to monitor project performance).
- Periodic groundwater sampling and analysis.
- Consultant oversight and reporting. Regensis data evaluation and technical support are provided free of charge.

The costs provided in this letter apply to time release material costs for one application. The need for re-applications will depend on your plume management strategy, site specific biodegradation performance, remedial goals for the site, and other technical or regulatory considerations. For plume area treatments, one to two re-applications could be necessary over the course of the project, although each re-application would most likely be done over a reduced area and dose amount compared to the initial application. For barrier-based designs, re-applications will be necessary every one to two years as long as there is a need to prevent contaminant migration.

### **ORC Delivery to Contaminated Zone**

Typically, ORC is applied using direct push hydraulic equipment. Drive rods are pushed to the bottom of the contaminated saturated zone and then an ORC/water slurry is injected as the rods are withdrawn.

For sites where direct push technology is not feasible, auger-based equipment can be used to deliver ORC; and, for cases where repeated injections will be necessary, the use of permanent,

small diameter re-injection wells may be a more cost-effective approach. Technical support personnel at Regenesiis are available to discuss the suitability of other delivery methods.

The ORC/water slurry mixture is typically 20% to 40% ORC solids by weight. An average ORC solids content is 30%, but this value may need to be adjusted in the field so that the required mass of ORC can be injected at each location. For example, tighter soil types may require a higher ORC solids content since less slurry volume can be injected per location.

The volume of water per injection location can be calculated from the following equation:

$$\text{Volume of water (gallons/injection point)}: \frac{\text{ORC lbs/hole}}{(8.34 \text{ lbs/gal water})(\% \text{ ORC solids})} [1 - (\% \text{ ORC solids})]$$

Most geoprobe contractors are equipped with grout pumps capable of injecting ORC. Typical pump specifications call for a pumping rate of 1 to 5 gpm and injection pressures from 100 to 500 psig.

Costs for ORC injection should be obtained from local subcontractors. Regenesiis can assist in locating ORC injection subcontractors. Budgetary cost estimates for direct push-based injection range from \$1,000 to \$2,000 per day. Typically, two to three ORC injection points can be completed per hour and from 20 to 30 points can be completed per day, depending on soil type, depths of injection, and subcontractor experience.

### **Recommended Groundwater Monitoring Program for Pilot/Full Scale Treatment**

Monitoring of selected wells should be conducted to validate the enhancement of natural attenuation processes. Also, an initial or "baseline" round of sampling should be performed to identify pre-remediation groundwater conditions. After delivery of ORC to the subsurface, samples can be collected every 2 to 3 months. After the initial biodegradation and geochemical trends have been identified, the monitoring frequency can be decreased to a semiannual or annual program. The monitoring program should employ low flow groundwater sampling techniques and include the measurement of the following field/chemical parameters:

- all contaminants of concern
- field redox parameters: ORP, pH, dissolved oxygen, and ferrous iron
- biochemical oxygen demand (5 day) and chemical oxygen demand at selected wells within treatment area


Ideally, samples should be collected from the following site locations:

- an upgradient or background location to identify groundwater conditions outside the treatment area
- inside the treatment area

- an appropriate distance downgradient of the treatment area to identify potential residence time requirements for complete biodegradation
- downgradient compliance point to confirm offsite migration is not occurring

Regenesis appreciates the opportunity to provide this information for your project. If you have any questions about this proposal please contact me at (616) 344-2617 or your local sales manager Pat Randall (805) 375-0961.

Sincerely,

A handwritten signature in black ink, appearing to read 'Brittain Griffiths', written over a horizontal dashed line.

Brittain Griffiths  
Applications Engineer



2510 Revision

\* The ORC Barrier can be placed where you see fit.





FIGURE 5-1 GROUNDWATER PLUME 12/18/01

DP 793, 4035 PARK BLVD. OAKLAND, CALIFORNIA





WESTERN  
GEO-ENGINEERS  
CALIF. CONTRACTOR #513857  
REGISTERED GEOLOGISTS

1386 EAST BEAMER STREET  
WOODLAND CA 95776-6003  
(530) 668-5300.  
FAX (530) 662-0273  
wege@mother.com

FROM: George Converse DATE: Feb. 5, 2002

TO: Brittain Griffiths FAX #: (616) 373-1078

(616) 344-2617

Regenesis

TOTAL PAGES  
INCLUDING THIS PAGE

2

COMMENTS: DP 793, 4035 PARK BLVD., OAKLAND, CA.

PROPOSAL No. 2510

Brittain, I have enclosed a better - clearer copy of the plume extent figure. I think you got confused on concentrations from various sample points.

Area 1 2.7 ppm is well RS7, in the middle of Brighton Avenue.


Area 1a 48 ppm is the receptor trench along the eastern gutter of Brighton Avenue.

Area 2 4.9 ppm is as you interpreted.

Area 3 12 ppm is as you interpreted.

Please revise your estimates

Thanks George



February 4, 2002

George Converse  
Western Geo-Engineers  
1386 East Beamer Street  
Woodlands, CA 95776  
Phone: 530-668-5300 Fax: 530-662-0273

Subject: Park Blvd. site - Proposal No. 2510

Dear Mr. Converse:

We have reviewed the information that you provided for the above-referenced site. In the following sections, we provide design and cost information for a potential site remediation approach. This proposal is based on information provided by your firm. If site conditions have changed significantly please let us know, a new proposal may need to be generated.

### Use of ORC to Accelerate Bioremediation

Oxygen Release Compound (ORC) is used to provide terminal electron acceptors to support the oxidative biodegradation of many types of petroleum-based hydrocarbons as well as chlorinated hydrocarbons such as dichloroethenes and vinyl chloride. ORC is a proprietary formulation of magnesium peroxide, designed to provide a timed release of oxygen. ORC is manufactured as a powder, which can be (1) mixed with water for slurry injection into the saturated zone, (2) included in excavation backfill material, or (3) enclosed in specially designed socks for placement in monitoring wells.

*will eventually be cement*

The use of ORC for groundwater remediation offers a comparatively simple and cost effective remediation alternative for sites that would otherwise require unacceptably long periods of time for natural attenuation or the high levels of capital investment and operating expense associated with active remediation technologies.

### Design/Proposal Assumptions

Using the information you provided, we have made the following assumptions to estimate system design variables and dose amounts.

Area 1 = RS-7 *not Trench*

- Plume area requiring treatment: 2,840 square feet
- Representative contaminant concentration: 2.7 ppm TPH

- Contaminated saturated zone thickness requiring treatment: 10 feet (top 10 feet of the aquifer)

Area 1a *is Trench*

- Plume area requiring treatment: 400 square feet *2840 ft<sup>2</sup>*
- Representative contaminant concentration: 48 ppm TPH
- Contaminated saturated zone thickness requiring treatment: 10 feet (top 10 feet of the aquifer)

Area 2 *condo building → RS2*

- Plume area requiring treatment: 60 x 45 feet
- Representative contaminant concentration: 4.9 ppm TPH
- Contaminated saturated zone thickness requiring treatment: 10 feet (top 10 feet of the aquifer)

Area 3 *RS-5*

- Plume area requiring treatment: 60 x 45 feet
- Representative contaminant concentration: 12 ppm TPH
- Contaminated saturated zone thickness requiring treatment: 10 feet (top 10 feet of the aquifer)

The design specifications and costs provided below are designed as an accelerated bioremediation project. This design may need to be adjusted as detailed design and regulatory oversight issues are finalized. For instance, the following design variables may need to be adjusted prior to the implementation:

- Treatment areas may need to be increased or decreased depending on the overall site remediation strategy.
- Exact delivery locations should be selected in the final design process. Delivery locations may need to be adjusted to take into account site features such as underground utilities and other site structures.

ORC Grid Treatment - Area 1	
Design Feature	Specification
Saturated thickness requiring treatment	10 feet
Treatment Area	2,840 square feet
Delivery Pt. Spacing and Configuration	Place into existing wells.

ORC dose rate in lbs/vertical foot of injection	N/A
Material requirement	435 lbs
Material cost at \$9/lb	\$3,915 plus shipping and applicable sales tax

ORC Grid Treatment - Area 1a	
Design Feature	Specification
Saturated thickness requiring treatment	10 feet
Treatment Area	400 square feet
Delivery Pt. Spacing and Configuration	Place into existing well.
ORC dose rate in lbs/vertical foot of injection	N/A
Material requirement	1,090 lbs
Material cost at \$9/lb	\$8,640 plus shipping and applicable sales tax

ORC Grid Treatment - Area 2	
Design Feature	Specification
Saturated thickness requiring treatment	10 feet
Treatment Area	60 feet x 45 feet
Delivery Pt. Spacing and Configuration	48 points spaced 8 feet on center throughout the treatment area
ORC dose rate in lbs/vertical foot of injection	2 lbs/ft (20 lbs/pt)
Material requirement	48 pts. x 10 feet x 2 lbs/ft = 960 lbs
Material cost at \$9/lb	\$8,640 plus shipping and applicable sales tax

ORC Grid Treatment - Area 3	
Design Feature	Specification
Saturated thickness requiring treatment	10 feet
Treatment Area	60 feet x 45 feet
Delivery Pt. Spacing and Configuration	48 points spaced 8 feet on center throughout the treatment area

ORC dose rate in lbs/vertical foot of injection	3.9 lbs/ft (39 lbs/pt)
Material requirement	48 pts. x 10 feet x 3.9 lbs/ft = 1,860 lbs
Material cost at \$9/lb	\$16,740 plus shipping and applicable sales tax

**ORC IS PRICED ON A VOLUME DISCOUNT STRUCTURE.**

**ORC Oxygen Barrier**

A 100 foot oxygen barrier would require 400 pounds of ORC to construct. The construction of the barrier would require two rows of 10 geoprobe points. Each row would be 100 feet long and the points within the row would be spaced 10 feet on center. The two rows would be 10 feet apart and offset by 5 feet. Each point would be injected with 20 pounds of ORC throughout the 10 foot contaminated saturated zone. The cost for each application of the barrier is \$3,600.

**ORC Cost**

The total amount of ORC required for this proposal is 4,735 pounds. At \$9/lb the total cost is \$42,615 plus shipping and sales tax.

**Total Project Cost**

The total cost of an accelerated bioremediation project can be estimated as the sum of the following items:

- Time release compound material and shipping costs.
- Time release compound application fieldwork costs. Customers are responsible for selecting a local injection/application subcontractor.
- Groundwater monitoring well construction (if necessary to monitor project performance).
- Periodic groundwater sampling and analysis.
- Consultant oversight and reporting. Regensis data evaluation and technical support are provided free of charge.

The costs provided in this letter apply to time release material costs for one application. The need for re-applications will depend on your plume management strategy, site specific biodegradation performance, remedial goals for the site, and other technical or regulatory considerations. For plume area treatments, one to two re-applications could be necessary over the course of the project, although each re-application would most likely be done over a reduced area and dose amount compared to the initial application.

**ORC Delivery to Contaminated Zone**

Typically, ORC is applied using direct push hydraulic equipment. Drive rods are pushed to the bottom of the contaminated saturated zone and then an ORC/water slurry is injected as the rods are withdrawn.

For sites where direct push technology is not feasible, auger-based equipment can be used to deliver ORC; and, for cases where repeated injections will be necessary, the use of permanent, small diameter re-injection wells may be a more cost-effective approach. Technical support personnel at Regenesi are available to discuss the suitability of other delivery methods.

The ORC/water slurry mixture is typically 20% to 40% ORC solids by weight. An average ORC solids content is 30%, but this value may need to be adjusted in the field so that the required mass of ORC can be injected at each location. For example, tighter soil types may require a higher ORC solids content since less slurry volume can be injected per location.

The volume of water per injection location can be calculated from the following equation:

$$\text{Volume of water (gallons/injection point)} = \frac{\text{ORC lbs/hole}}{(8.34 \text{ lbs/gal water}) \times (\% \text{ ORC solids})} [1 - (\% \text{ ORC solids})]$$

Most geoprobe contractors are equipped with grout pumps capable of injecting ORC. Typical pump specifications call for a pumping rate of 1 to 5 gpm and injection pressures from 100 to 500 psig.

Costs for ORC injection should be obtained from local subcontractors. Regenesi can assist in locating ORC injection subcontractors. Budgetary cost estimates for direct push-based injection range from \$1,000 to \$2,000 per day. Typically, two to three ORC injection points can be completed per hour and from 20 to 30 points can be completed per day, depending on soil type, depths of injection, and subcontractor experience.

### Recommended Groundwater Monitoring Program

Monitoring of selected wells should be conducted to validate the enhancement of natural attenuation processes. Also, an initial or "baseline" round of sampling should be performed to identify pre-remediation groundwater conditions. After delivery of ORC to the subsurface, samples can be collected every 2 to 3 months. After the initial biodegradation and geochemical trends have been identified, the monitoring frequency can be decreased to a semiannual or annual program. The monitoring program should employ low flow groundwater sampling techniques and include the measurement of the following field/chemical parameters:

- all contaminants of concern
- field redox parameters: ORP, pH, dissolved oxygen, and ferrous iron
- biochemical oxygen demand (5 day) and chemical oxygen demand at selected wells within treatment area

Ideally, samples should be collected from the following site locations:

- an upgradient or background location to identify groundwater conditions outside the treatment area
- inside the treatment area



- an appropriate distance downgradient of the treatment area to identify potential residence time requirements for complete biodegradation
- downgradient compliance point to confirm offsite migration is not occurring

Regensis appreciates the opportunity to provide this information for your project. If you have any questions about this proposal please feel free to contact me at 616-344-2617 or your local sales manager Jack Peabody at 925-944-5566.

Sincerely,



Brittain Griffiths  
Applications Engineer

#2510

Area 1 = 3240 sq ft  
- (400 sq ft)  
-----  
2840 sq ft

Area 1a  
= 20 x 20 x 10  
= 4000 sq ft

Area 3  
6x4x5

Area 4  
4x4




FIGURE 6-1  
GROUNDWATER  
PLUME  
12/18/01

DP 793, 4025 PARK BLVD  
OAKLAND, CALIFORNIA

SCALE 1 INCH = 40 FEET

● R58 SOIL BORING  
 1 TRENCH SAMPLE POINT  
 ● R63 GROUNDWATER MONITORING WELL  
 TOTAL PETROLEUM HYDROCARBONS, GASOLINE  
 ■ TPHg > 10 MG/L  
 ■ TPHg > 1 MG/L  
 ■ TPHg > 0.05 MG/L

APPENDIX H  
WEGE HYDROGEN PEROXIDE COST CALCULATIONS  
TO INCREASE DISSOLVED OXYGEN IN GROUNDWATER PLUME



WESTERN  
GEO-ENGINEERS

CALIF. CONTRACTOR #513857  
REGISTERED GEOLOGISTS

1386 EAST BEAMER STREET  
WOODLAND CA 95776-6003

(530) 668-5300,  
FAX (530) 662-0273  
wege@mother.com

February 21, 2002

Mr. Bill Thompson  
Desert Petroleum  
P.O. Box 1601  
Oxnard, California 93032  
(805) 644-6784 FAX (805) 654-0720

Dear Mr. Thompson:

Mr. Scott Seary, Alameda County Health, is still in the process of reviewing our workplan to augment the groundwater with oxygen at former Desert Petroleum Station #793. I recently received the cost analysis from Regensis to use ORC to elevate the oxygen level in the groundwater. Their calculations indicate that we would need an estimated 9,690 pounds of ORC at \$8.00/lb = \$77,520.00. This does not include delivery of the ORC into the groundwater (push points) and monitoring to insure that the ORC is working.

WEGE has used hydrogen pyroxide to increase the oxygen in groundwater at a site in Watsonville. I calculated the amount of hydrogen pyroxide that would be required to increase the oxygen from 2 mg/L to 8 mg/L within the groundwater plume (17 gallons at 35% by volume). The estimated cost to provide monthly treatments with 35% hydrogen pyroxide including application and monitoring would be \$1,160.00, or \$13,920.00/year, see Table. You will notice that the cost estimate for monitoring is different for the ORC application as compared to the hydrogen pyroxide. With the hydrogen pyroxide we will also be performing a monthly application, so personnel hours are divided between the application and monitoring, along with mobilization cost.

I suggest we try the hydrogen pyroxide treatment once we get approval from Alameda County Health.

Sincerely yours,

George Converse  
Project Geologist

COST COMPARISON ORC TO HYDROGEN PYROXIDE

	AMOUNT			DOSE	MATERIAL COST
	LITERS	GALLONS	POUNDS		
GROUNDWATER PLUME	1781168	470586			
ORC				9690 YEARLY	\$77,520.00
HYDROGEN PYROXIDE 35%		53		MONTHLY	\$515.00

	COST	AMOUNT	SUBTOTAL	TOTAL
<b>ORC -YEARLY COST</b>				
ONE APPLICATION	\$5,000.00	1	\$5,000.00	
MATERIAL	\$77,520.00	1	\$77,520.00	
MONITORING	\$535.00	12	\$6,420.00	\$88,940.00
<b>HYDROGEN PYROXIDE</b>				
MONTHLY APPLICATION	\$340.00	12	\$4,080.00	
MATERIAL	\$515.00	12	\$6,180.00	
MONITORING	\$305.00	12	\$3,660.00	\$13,920.00

TABLE 5 POUNDS HYDROCARBONS

DP 793

4035 PARK BLVD, OAKLAND, CA

Pounds TPHg in soil and in groundwater AUGUST 1999.

		soil density=		1.9					
Square Feet	Thickness	Cubic feet	Upper mg/kg	Lower mg/kg	Average con mg/kg	kg Soil	mg TPHg	pounds TPHg	
TPHg in soil 5 - 10 foot depth 8/99									
2165	5	10825	50	1	25.5	582409.9	14851452.39	32.7	
1945	5	9725	100	50	75	523227.4	39242052.56	86.5	
700	5	3500	290	100	195	188308.1	36720069.75	81.0	
325	5	1625	1000	100	550	87428.74	48085805.63	106.0	
100	5	500	2000	1000	1500	26901.15	40351725	89.0	
440	5	2200	4000	1000	2500	118365.1	295912650	652.4	
1047.6									
TPHg in soil 10-15 foot depth AUGUST 1999									
5006	5	25030	50	1	25.5	1346672	34340125.01	75.7	
1599	5	7995	100	50	75	430149.4	32261204.14	71.1	
2815	5	14075	1000	100	550	757267.4	416497054.9	918.2	
240	5	1200	1200	1000	1100	64562.76	71019036	156.6	
1221.6									
TPHg in soil 15-20 foot depth AUGUST 1999									
1926	5	9630	50	1	25.5	518116.1	13211961.8	29.1	
1044	5	5220	100	50	75	280848	21063600.45	46.4	
1250	5	6250	1000	100	550	336264.4	184945406.3	407.7	
483.3									
TPHg in soil 20-25 foot depth AUGUST 1999									
2900	5	14500	10	1	5.5	780133.4	4290733.425	9.5	
9.5									
TPHg in soil 25-30 foot depth AUGUST 1999									
410	5	2050	50	1	25.5	110294.7	2812515.233	6.2	
175	5	875	100	50	75	47077.01	3530775.938	7.8	
145	5	725	1000	100	550	39006.67	21453667.13	47.3	
80	5	400	1600	1000	1300	21520.92	27977196	61.7	
123.0									
Total pounds TPHg in Soil AUGUST 1999								2884.9	
MASS GROUNDWATER CONTAMINATION AUGUST 1999									
		PORES		0.3					
Square Feet	Thickness	Cubic feet	Upper mg/l	Lower mg/l	Average con mg/l	LITERS water	mg TPHg	pounds TPHg	
10520	16	168320	1	0.05	0.525	1429895	750695	1.66	
8650	16	138400	10	1	5.5	1175722	6466470	14.26	
2000	16	32000	40	10	25	271843	6796080	14.98	
2550	16	40800	100	10	55	346600	19063004	42.03	
750	16	12000	160	100	130	101941	13252356	29.22	
Total Calculated Mass TPHg in Groundwater AUGUST 1999								102.14	

MASS GROUNDWATER CONTAMINATION DECEMBER 2001									
		PORES	0.3						
Square	Thickness	Cubic	Upper	Lower	Average con	LITERS	mg	pounds	
Feet		feet	mg/l	mg/l	mg/l	water	TPHg	TPHg	
4825	16	77200	1	0.05	0.525	655822	344306	0.76	
4984	16	79744	10	1	5.5	677433	3725883	8.21	
120	16	1920	12	10	11	16311	179417	0.40	
1240	16	19840	48	10	29	168543	4887741	10.78	
495	10	4950	48	48	48	42051	2018436	4.45 trench	

Total Calculated Mass TPHg in Groundwater DECEMBER 2001									24.59
---	--	--	--	--	--	--	--	--	-------

MASS BENZENE GROUNDWATER CONTAMINATION AUGUST 1999									
assumption: free product contains 287 mg/L of benzene									
		PORES	0.3						
Square	Thickness	Cubic	Upper	Lower	Average con	LITERS	mg	pounds	
Feet		feet	mg/l	mg/l	mg/l	water	Benzene	Benzene	
6775	16	108400	0.1	0.0005	0.05025	920869	46274	0.10	
7800	16	124800	1	0.1	0.55	1060188	583104	1.29	
2000	16	32000	7.2	1	4.1	271843	1114557	2.46	
2000	16	32000	10	1	5.5	271843	1495138	3.30	
1200	16	19200	24	10	17	163106	2772801	6.11	
Total Calculated Mass Benzene in Groundwater 1999									13.25

MASS BENZENE GROUNDWATER CONTAMINATION DECEMBER 2001									
assumption: free product contains 287 mg/L of benzene									
		PORES	0.3						
Square	Thickness	Cubic	Upper	Lower	Average con	LITERS	mg	pounds	
Feet		feet	mg/l	mg/l	mg/l	water	Benzene	Benzene	
3940	16	63040	0.001	0.0005	0.00075	535531	402	0.00	
5265	16	84240	0.5	0.001	0.2505	715627	179265	0.40	
2170	16	34720	1	0.5	0.75	294950	221212	0.49	
450	16	7200	2	1	1.5	61165	91747	0.20	
970	16	15520	3.7	1	2.35	131844	309833	0.68	
495	10	4950	3.7	3.7	3.7	42051	155588	0.34 trench	
Total Calculated Mass Benzene in Groundwater 2001									2.11

ESTIMATED POUNDS GROUNDWATER TPHg REDUCTION FROM 1999 TO 2001 77.5

ESTIMATED POUNDS GROUNDWATER BENZENE REDUCTION FROM 1999 TO 2001 11.1

ESTIMATED % REDUCTION TPHg 75.9

ESTIMATED % REDUCTION BENZENE 84.1

Cost Estimate per treatment	unit cost	amount	subtotal	ORC cost
liters of groundwater treated		1781168		
53 gallon drum 35% peroxide	\$514.62	1	\$514.62	\$77,520.0
pump truck	\$175.00	1	\$175.00	150.63
Geotechnichain	\$55.00	6	\$330.00	
DTW	10	1	\$10.00	
ph,Cond, Temp	10	1	\$10.00	
Dissolved Oxygen	20	6	\$120.00	\$1,159.62

To raise depleted oxygen from 2 ppm to 8 ppm - 1,781,168 (no reactions calculated) with 35% hydrogen peroxide  
 ratio O to H2O2 2.125  
 killograms Oxygen 10.6870057  
 killogram peroxide 22.70988712  
 litter peroxide 16.33804829  
 35 percent sol 65.35219314  
 gallons peroxide 17.28893998

APPENDIX I.

WASTEWATER DISCHARGE REPORT



Molly Ong.  
Source Control Division  
East Bay Municipal Utility District  
P.O. Box 24055, MS 702  
Oakland, CA 94623  
(510) 287-1618  
Fax (510) 287-0621

March 13, 2002

RE: Wastewater Discharge Quarterly Sampling for Permit #5043550 1.

Dear Ms. Ong:

The enclosed table and certified laboratory report represents the sampling for wastewater Discharge Permit #5043550 1 for the period between December 18, 2001 and March 13, 2002. Continues discharge from pumping at RS-5 was discontinued on July 19, 2001. Currently the treated water discharged to the sewer is produced from purging monitor wells associated with this site, to obtain groundwater samples on a quarterly basis. A sample of the water discharged to sewer was obtained on February 19, 2002 and analyzed for TPHg, BTEX and MtBE using EPA method 8260B.

All discharge conditions have been met.

CERTIFICATION East Bay Municipal Utility District, Permit #5043550 1

*I certify under penalty of law that this document and all attachments were prepared under my direction of supervision in accordance with a system designed to assure that the qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations.*


  
Signature Bill Thompson


  
date

WASTEWATER DISCHARGE PERMIT # 5043550 1  
 FORMER DP #793  
 4035 PARK BLVD., OAKLAND, CALIFORNIA

WASTEWATER SOURCE ID	DATE	METER READING IN GALLONS #35635668	NEW METER IN GALLONS #47083426	GALLONS DISCHARGED BETWEEN VISITS	ACCUMULATIVE GALLONS DISCHARGED	AVERAGE DISCHARGE PER MINUTE IN GALLONS	EPA METHOD 624				7420 LEAD ug/L
							BENZENE ug/L	TOLUENE ug/L	ETHYL-BENZENE ug/L	XYLENES ug/L	
BAKER TANK	1/25/00	314110		0	0	0.00					
BAKER TANK	1/26/00	315050		940	940	0.65	<1	<1	<1	<1	<50
BAKER TANK	1/28/00	321120	1098330	6070	7010	2.11					
BAKER TANK	2/2/00		1102560	4230	11240	0.59					
BAKER TANK	2/3/00		1107482.2	4922	16162	3.42	<1	<1	<1	<1	<50
BAKER TANK	2/7/00		1107482.2	0	16162	0.00					
BAKER TANK AND 1/4LY SAMPLES	2/9/00		1109680	2198	18360	0.76	EPA METHOD 624				239.2
F1 (PSP No. 1)	3/23/00		1109720	40	18400	0.00	<1	<1	<1	<2	<5
F1 (PSP No. 1)	5/4/00		1110780	1060	19460	0.02					
F1 (PSP No. 1)	5/12/00		1111700	920	20380	0.08					
F1 (PSP No. 1)	5/18/00		1113359	1659	22039	0.19					
F1 (PSP No. 1)	5/25/00		1113840	481	22520	0.05					
F1 (PSP No. 1)	5/31/00		1115111	1271	23791	0.15					
F1 (PSP No. 1)	6/16/00		1115823	712	24503	0.03					
F1 (PSP No. 1)	6/28/00		1116293	470	24973	0.03					
F1 (PSP No. 1)	6/30/00		1116303	10	24983	0.00	EPA METHOD 624				200.7
F1 (PSP No. 1)	7/5/00		1116313	10	24993	0.00	<1	<1	<1	<2	<2
F1 (PSP No. 1)	7/13/00		1117816	1503	26496	0.13					
F1 (PSP No. 1)	7/20/00		1118892	1076	27572	0.11					
F1 (PSP No. 1)	7/27/00		1118892	0	27572	0.00					
F1 (PSP No. 1)	8/3/00		1120336	1444	29016	0.14					
F1 (PSP No. 1)	8/10/00		1121041	705	29721	0.07					
F1 (PSP No. 1)	8/17/00		1121041	0	29721	0.00					
F1 (PSP No. 1)	8/24/00		1121860	819	30540	0.08	EPA METHOD 624				200.7
F1 (PSP No. 1)	8/30/00		1122720	860	31400	0.10	<1	<2	<1	<2	<2
F1 (PSP No. 1)	9/7/00		1123270	550	31950	0.05					
F1 (PSP No. 1)	9/14/00		1123819	549	32499	0.05					
F1 (PSP No. 1)	9/21/00		1123819	0	32499	0.00					
F1 (PSP No. 1)	10/5/00		1124153	334	32833	0.02					
F1 (PSP No. 1)	10/12/00		1124660	507	33340	0.05					
F1 (PSP No. 1)	10/19/00		1125904.3	1244	34584	0.12					
F1 (PSP No. 1)	10/26/00		1127167	1263	35847	0.13					
F1 (PSP No. 1)	11/9/00		1128367.2	1200	37047	0.06					
F1 (PSP No. 1)	11/16/00		1129779.5	1412	38460	0.14					
F1 (PSP No. 1)	11/22/00		1130940.5	1161	39621	0.13					
F1 (PSP No. 1)	12/1/00		1134147	3207	42827	0.25	EPA METHOD 624				200.7


Figure 1(Revised December 5, 2001)  
Activity: GROUNDWATER RECOVERY AND DISCHARGE SYSTEM  
FORMER DESERT PETROLEUM SITE DP 793.





**WASTEWATER DISCHARGE**

DP 793, 4035 PARK BLVD.  
 OAKLAND, CALIFORNIA  
 BUILDING LAYOUT AND LOCATION OF  
 RECEPTOR TRENCH  
 OCTOBER 29, 1999.



NORTH

- MW1 GROUNDWATER MONITORING WELL
- ① PROCESS NUMBER
- WATER METER



Report Number : 24919

Date : 3/6/02

George Converse  
Western Geo-Engineers  
1386 East Beamer St.  
Woodland, CA 95776

Subject : 13 Water Samples  
Project Name : DP793  
Project Number : DP793

Dear Mr. Converse,

Chemical analysis of the samples referenced above has been completed. Summaries of the data are contained on the following pages. Sample(s) were received under documented chain-of-custody. US EPA protocols for sample storage and preservation were followed.

Kiff Analytical is certified by the State of California (# 2236). If you have any questions regarding procedures or results, please call me at 530-297-4800.

Sincerely,

  
Joel Kiff




Report Number : 24919

Date : 3/6/02

Subject : 13 Water Samples  
Project Name : DP793  
Project Number : DP793

## Case Narrative

Matrix Spike/Matrix Spike Duplicate Results associated with samples R1, R3, RS8, RS6, RS10, CARBON DISCHARGE, MW1, RS2, RS9, T1, RS5, RS7, R2 for the analytes Benzene, Toluene were affected by the analyte concentrations already present in the un-spiked sample.

Approved By:   
Joel Kiff

720 Olive Drive, Suite D Davis, CA 95616 916-297-4800



Report Number : 24919

Date : 3/6/02

Project Name : DP793

Project Number : DP793

Sample : CARBON DISCHARGE

Matrix : Water

Lab Number : 24919-13

Sample Date :2/19/02

Parameter	Measured Value	Method Reporting Limit	Units	Analysis Method	Date Analyzed
Benzene	< 0.50	0.50	ug/L	EPA 8260B	3/3/02
Toluene	< 0.50	0.50	ug/L	EPA 8260B	3/3/02
Ethylbenzene	< 0.50	0.50	ug/L	EPA 8260B	3/3/02
Total Xylenes	< 0.50	0.50	ug/L	EPA 8260B	3/3/02
Methyl-t-butyl ether (MTBE)	< 0.50	0.50	ug/L	EPA 8260B	3/3/02
TPH as Gasoline	< 50	50	ug/L	EPA 8260B	3/3/02
Toluene - d8 (Surr)	105		% Recovery	EPA 8260B	3/3/02
4-Bromofluorobenzene (Surr)	98.8		% Recovery	EPA 8260B	3/3/02

Approved By:  Joel Kiff

QC Report : Method Blank Data

Project Name : DP793

Project Number : DP793

Report Number : 24919

Date : 3/6/02

<u>Parameter</u>	<u>Measured Value</u>	<u>Method Reporting Limit</u>	<u>Units</u>	<u>Analysis Method</u>	<u>Date Analyzed</u>
Benzene	< 0.50	0.50	ug/L	EPA 8260B	3/1/02
Toluene	< 0.50	0.50	ug/L	EPA 8260B	3/1/02
Ethylbenzene	< 0.50	0.50	ug/L	EPA 8260B	3/1/02
Total Xylenes	< 0.50	0.50	ug/L	EPA 8260B	3/1/02
Methyl-t-butyl ether (MTBE)	< 0.50	0.50	ug/L	EPA 8260B	3/1/02
TPH as Gasoline	< 50	50	ug/L	EPA 8260B	3/1/02
Toluene · d8 (Surr)	102		%	EPA 8260B	3/1/02
4-Bromofluorobenzene (Surr)	97.8		%	EPA 8260B	3/1/02

<u>Parameter</u>	<u>Measured Value</u>	<u>Method Reporting Limit</u>	<u>Units</u>	<u>Analysis Method</u>	<u>Date Analyzed</u>
------------------	-----------------------	-------------------------------	--------------	------------------------	----------------------

KIFF ANALYTICAL, LLC

720 Olive Drive, Suite D Davis, CA 95616 530-297-4800

Approved By: Joel Kiff



Report Number : 24919

Date : 3/6/02

QC Report : Matrix Spike/ Matrix Spike Duplicate

Project Name : DP793

Project Number : DP793

Parameter	Spiked Sample	Sample Value	Spike Level	Spike Dup. Level	Spiked Sample Value	Duplicate Spiked Sample Value	Units	Analysis Method	Date Analyzed	Spiked Sample Percent Recov.	Duplicate Spiked Sample Percent Recov.	Relative Percent Diff.	Spiked Sample Percent Recov. Limit	Relative Percent Diff. Limit
Benzene	24919-09	33	18.7	20.0	41.7	44.3	ug/L	EPA 8260B	3/1/02	44.3	54.2	20.0	70-130	25
Toluene	24919-09	21	18.7	20.0	30.7	33.6	ug/L	EPA 8260B	3/1/02	50.6	62.0	20.1	70-130	25
Tert-Butanol	24919-09	<5.0	93.6	100	87.7	90.6	ug/L	EPA 8260B	3/1/02	93.6	90.5	3.44	70-130	25
Methyl-t-Butyl Ether	24919-09	<0.50	18.7	20.0	18.3	15.6	ug/L	EPA 8260B	3/1/02	97.8	78.0	22.6	70-130	25

KIFF ANALYTICAL, LLC

720 Olive Drive, Suite D Davis, CA 95616 530-297-4800

Approved By:  Joel Kiff

QC Report : Laboratory Control Sample (LCS)

Report Number : 24919

Date : 3/6/02

Project Name : DP793


Project Number : DP793

Parameter	Spike Level	Units	Analysis Method	Date Analyzed	LCS Percent Recov.	LCS Percent Recov. Limit
Benzene	20.0	ug/L	EPA 8260B	3/2/02	95.6	70-130
Toluene	20.0	ug/L	EPA 8260B	3/2/02	91.3	70-130
Tert-Butanol	100	ug/L	EPA 8260B	3/2/02	88.8	70-130
Methyl-t-Butyl Ether	20.0	ug/L	EPA 8260B	3/2/02	97.4	70-130

KIFF ANALYTICAL, LLC

720 Olive Drive, Suite D Davis, CA 95616 530-297-4800

Approved By:

  
Joel Kiff



