

SEPTEMBER 2011
SEMI ANNUAL
GROUNDWATER SAMPLING REPORT
WITH THIRD QUARTER 2011 UPDATE STATUS OF PUMP AND TREATMENT

FORMER DESERT SITE DP 793
4035 PARK BLVD.
OAKLAND, CA.

FOR

DESERT PETROLEUM

September 30, 2011

BY

-WEGE-
WESTERN GEO-ENGINEERS
1386 E. BEAMER STREET
WOODLAND, CALIFORNIA 95776
(530) 668-5300

TABLE OF CONTENTS

1.0 SITE LOCATION AND IDENTIFICATION NUMBERS.....	3
2.0 SITE INVESTIGATION/REMEDIATION CHRONOLOGY	3
3.0 LOCAL GEOLOGY	8
3.1 Geomorphology.....	8
3.2 Stratigraphy	8
Station Property.....	8
Backyard Sewer Lateral Route.....	8
Brighton Avenue	8
4.0 WORK PERFORMED, June 29, - September 23, 2011.	8
5.0 COLLECTION AND ANALYSIS OF GROUNDWATER SAMPLES	9
4.1 Depth to Water Measurements	9
5.0 RESULTS OF GROUNDWATER MONITORING.....	9
5.1 Groundwater Gradient and Flow Direction.....	9
5.2 Results of Certified Analysis of Groundwater Samples	10
Total Petroleum Hydrocarbons - gasoline.....	10
Benzene.....	10
MtBE.....	10
Toluene	10
Ethylbenzene.....	10
Xylenes	11
6.0 PURGING/PUMPING OF RECEPTOR (INTERCEPT) TRENCH.....	11
7.0 PUMPING ON-SITE WELL RS05	11
8.0 FREE PHASE FLOATING PRODUCT REMOVAL.....	12
9.0 SUMMARY	12
10.0 RECOMMENDATIONS.....	14
11.0 TIME FRAME.....	14
12.0 LIMITATIONS.....	14

List of Tables

1. Groundwater Elevation and Certified Analytical Results
2. Groundwater Pumped and Treated
3. Groundwater TPHg Removal

List of Figures

1. Area Base Map "Geotracker"
2. Portion of USGS Oakland East 7.5 Minute Quadrangle
3. Sample Location Figure
- 4A Groundwater Gradient, August 19, 2011
- 4B. Groundwater Gradient, August 31, 2011
- 4C Groundwater Gradient, September 14, 2011
5. Groundwater Plume, TPHg & Benzene, September 14, 2011
6. Groundwater Plume, TPHg & MtBE, September 14, 2011

List of Appendices

- A. Methods and Procedures, QA/QC with Field Notes
- B. Charts
- C. Laboratory Report s
- D. Correspondence from Alameda County Health

Mr. Bill Thompson
Desert Petroleum
3781 Telegraph Road
Ventura, CA 93003
(805) 644-6784 FAX (805) 654-0720

September 30, 2011

Dear Mr. Thompson:

The following report documents the Third Quarter 2011 update status with Semi Annual sampling at DP793, 4035 Park Blvd., Oakland, California.

1.0 SITE LOCATION AND IDENTIFICATION NUMBERS

Former Desert Petroleum #793 is a non-active service station (USTs and associated piping removed June 23, 1994), located on the northwest corner of the intersection of Park Boulevard and Hampel Street at 4035 Park Blvd., Oakland, California (Figure 1). The site is located in projected section 32; T1S; R3W; MDB&M at an approximate elevation of 210 feet above mean sea level (Figure 2).

East Bay Municipal Utility District - Sewer Discharge Permit #50435501,
Alameda County Local Oversight STID 1248
San Francisco Bay Regional Board (Region 2) Case # 01-0170
Facility/Leak Site ID# T0600100158

2.0 SITE INVESTIGATION/REMEDIATION CHRONOLOGY

November 30, 1989	Alameda County Health Department (Mr. Ariu Levi) notified Desert Petroleum that gasoline was trickling into a sewer on Brighton Avenue through a crack in the bottom of the sewer access. Desert Petroleum's area manager sent to site to reconstruct and audit tank inventories and sales records. The audit indicated overages on all tanks.
December 1, 1989	Desert Petroleum contacted the station tenant, Mr. Jason Gopad, and advised him to test the fuel tanks and associated piping.
December 5, 1989	The retail fueling facility was closed.
December 6, 1989	Mr. Gopad had the underground storage tanks tested. The test results were inconclusive.
December 7, 1989	All fuel was removed from the underground storage tanks. The product lines were tested by Walton Engineering. The regular leaded and super unleaded lines passed. The regular unleaded line failed. A 1/2 inch hole in the 2 inch unleaded supply line was located beneath the eastern pump island. An ultrasound investigation was conducted to determine the location of the onsite sewer line. An onsite soil gas survey was conducted and indicated contamination associated with the pump islands and the sewer line on the western edge of the property.

December 8, 1989 Desert Petroleum submitted Unauthorized Release Report, drilling permits for site assessment obtained from Alameda County Flood Control and Water Conservation District, Zone 7, Underground Service Alert was notified.

December 11, 1989 Onsite drilling/sampling and well installation initiated, i.e., sample borings RS-1, RS-2, RS-3, RS-5 and RS-4. Groundwater monitoring wells installed into borings RS-1, RS-5, and RS-6. Vapor extraction well installed into boring RS-2.

December 12, 1989 Encroachment permit secured from the City of Oakland for assessment work in Brighton Avenue. Sample boring RS-4 drilled and sampled just east of the sewer access in Brighton Avenue to the 10 foot depth.

December 13, 1989 The area northeast of the sewer access was excavated with a backhoe. Gasoline appeared to be seeping from the backfill around the sewer line. A water supply line was inadvertently broke (USA markings incorrectly marked the location of this line). A vacuum truck was used to pump out the water/product from the excavation. Approximately 7,200 gallons of water/gasoline was manifested and sent to H & H Shipyard for treatment and disposal. The water line was repaired, perforated 4 inch PVC pipe was placed vertically into the excavation and the excavation backfilled with pea gravel from approximately the 8 foot depth to sub-grade, well RS-7. A portable vapor extraction unit connected to the sewer and RS-7 (operated during daylight hours).

December 15, 1989 RSI S.A.V.E. vapor extraction system installed and connected to onsite wells RS01, RS02, RS05 and RS06. It operated continuously for one week, then during daylight hours thereafter due to noise complaints from neighbors. Length of vapor extraction and amounts of hydrocarbons removed not documented.

July 24, 1990 Soil boring/sampling investigations near the sewer lateral in residential backyard 1227 Hampel Avenue.

August 21, 1990 Soil boring/sampling investigations near the sewer lateral in residential backyards 4006 Brighton Avenue and 4010/4012 Brighton Avenue.

December 1990 Commenced quarterly groundwater monitoring.

September 8, 1993 Levine - Fricke, conducted soil boring/sampling investigation at residences 4003 Park Blvd. and 4006 Brighton Avenue. Constructed monitor well at 4003 Park Blvd for property owner of 4003 Park Blvd (not a part of 4035 Park Blvd. site assessment/investigation).

June 23, 1994 Removed all USTs and associated piping from 4035 Park Blvd.

August 14, 1995 Over-excavated UST and dispenser areas at 4035 Park Blvd 1700 cubic yards of non-hazardous soil transported to and disposed at Forward Landfill, Stockton, California. Installed excavation well R3 (6 inch slotted PVC to 15 feet below surface) south of building, backfill excavation to 5 1/2 feet below surface with 1/4 inch pea gravel. Excavating removed monitor well RS-1.

August 16, 1995 Excavated and removed hydraulic hoists from station building.

August 31, 1995 Exploratory excavation at waste oil UST area, north of building and exploratory excavation west of building to 17 feet below surface. Installed excavation wells R1 in west excavation and R2 in north excavation.

September 5, 1995 Drill/sampled and installed replacement well for RS01 (MW01).

May 2, 1996 Soil Probe Survey and soil sample borings along sewer route from 4035 Park Blvd. through back yards, to Brighton Avenue. Temporary casing set in hand augered borings BH-1, BH-2, BH-3, BH-4 and BH-5. Conducted slug tests on BH-1, BH-2, BH-3 and BH-5. Not enough water entry into BH-4 to conduct test. The following hydraulic conductivities (k) were calculated; BH-1 = 0.15 ft/day, BH-2 = 2.9 ft/day, BH-3 = 0.11 ft/day, and BH-5 = 4.8 ft/day.

January 17, 1997 Soil Probe Survey Brighton Avenue
August 12, 1999 Installed receptor trench, Brighton Avenue. 148 cubic yards non hazardous gasoline contaminated soil transported and disposed of at Vacaville Landfill, Vacaville, California. Installed wells RS08, RS09 and RS10.

October 7, 1999 Pumped 19,451 gallons of gasoline contaminated groundwater from receptor trench, stored in above ground 22,000 gallon Baker tank.

January 24, 2000 Obtained sewer discharge permit from East Bay Municipal Utility District, started discharge of water stored in Baker tank to city sewer.

May 4, 2000 Started weekly purging of receptor trench well T1 (4 hours once per week). Discharged purged water through water carbon and then to sewer.

February 15, 2001 Set submersible pump in RS05 to pump continuously, continued once a week purging of receptor well T1 (46,121 gallons removed from receptor trench well).

July 19, 2001 Ceased pumping of RS05 and weekly purging of T1; 62,511 gallons removed from T1 and 78,919 gallons removed from RS05 (total 141,430 gallons of gasoline contaminated groundwater treated and disposed to sewer).

March 21, 2002 Resumed pumping at RS05.
August 6, 2002 246,849 gallons of gasoline contaminated groundwater pumped, treated and disposed to sewer.

November 20, 2002 Commenced weekly hand bailing of free phase product from well RS08.
December 12, 2002 Purged receptor trench of 1432 gallons gasoline tainted groundwater.
January 9, 2003 Purged receptor trench of 1349 gallons gasoline tainted groundwater.
January 30, 2003 Purged receptor trench of 1624 gallons gasoline tainted groundwater.
March 13, 2003 Purged receptor trench of 1413 gallons gasoline tainted groundwater.
April 3, 2003 Purged receptor trench of 1305 gallons gasoline tainted groundwater.
April 9, 2003 Demolished existing service station building.
April 15, 2003 Replaced RS05 groundwater recovery pump with WEGE pump, while RS05 pump is serviced.

May 1, 2003 Reinstalled RS05 groundwater recovery pump.
Submitted Workplan to Investigate Contaminated Soils Above and Below the Water Table at the Former Area of the Station Building, 4035 Park Blvd., Oakland, CA.

May 6, 2003 Purged receptor trench of 1589 gallons gasoline tainted groundwater.
May 21, 2003 Purged receptor trench of 2544 gallons gasoline tainted groundwater.
June 25, 2003 Purged receptor trench of 1796 gallons gasoline tainted groundwater.
July 17, 2003 Purged receptor trench of 1560 gallons gasoline tainted groundwater.
July 31, 2003 Notice to initiate Workplan submitted May 1, 2003

August 6, 2003 Alameda County Health, Scott Seery, phoned Western Geo-Engineers, notifying them not to proceed with workplan.

August 13, 2003 Purged receptor trench of 1574 gallons gasoline tainted groundwater.

September 4, 2003 Purged receptor trench of 1477 gallons gasoline tainted groundwater.

October 3, 2003 Purged receptor trench of 1285 gallons gasoline tainted groundwater.

October 16, 2003 Removed water carbon unit #1, placed new water carbon in #2 position and moved #2 water carbon into #1 position.

November 20, 2003 Purged receptor trench of 1303 gallons gasoline tainted groundwater.

December 18, 2003 Purged receptor trench of 1303 gallons gasoline tainted groundwater.

January 22, 2004 Purged receptor trench of 1175 gallons gasoline tainted groundwater.

February 26, 2004 Purged receptor trench of 102 gallons gasoline tainted groundwater.

March 30, 2004 Purged receptor trench of 975 gallons gasoline tainted groundwater.

April 29, 2004 Purged receptor trench of 1406 gallons gasoline tainted groundwater.

May 13, 2004 Turned pumping system off, removed lid from #1 carbon and removed scaling from top of carbon, replaced lid and restarted pump.

May 27, 2004 Purged receptor trench of 1647 gallons gasoline tainted groundwater.

June 30, 2004 Purged receptor trench of 1759 gallons gasoline tainted groundwater.

July 29, 2004 No electrical power to treatment compound; has been disconnected.

September 24, 2004 New power panel at site, need 100 feet extension cord to connect pump controller to power for RS05.

September 28, 2004 Restarted pumping at RS05. Performed 1/4ly well samplings. Purged receptor trench of 1911 gallons.

September 30, 2004 Containment berm full of water, inspected carbon #1, leaking from bottom. Turned system off and removed carbon from system.

October 15, 2004 Took delivery of new water carbon placed #2 carbon into #1 position, new carbon into #2 position, restarted pumping system.

December 8, 2004 Performed 1/4ly well samplings.

December 9-16, 2004 Direct push/cored 12 borings to obtain groundwater and soil samples.

March 8, 2005 Published Conceptual Model

March 23, 2005 Performed 1/4ly well samplings.

June 1, 2005 Performed 1/4ly well samplings.

September 21, 2005 Performed 1/4ly well samplings.

December 7, 2005 Performed 1/4ly well samplings.

February 13, 2006 Published Work Plan to: Over-excavate benzene contaminated soils; to connect the receptor trench to treatment compound; further define TPHg groundwater plume.

March 28, 2006 Performed 1/4ly well samplings.

June 21, 2006 Performed 1/4ly well samplings.

September 13, 2006 Performed 1/4ly well samplings.

October 19, 2006 Installed new water meter at carbon effluent, Meter # 82773286.

November 27, 2006 Destroyed monitor wells MW01, RS02 and RS06. Conducted hand auger soil and groundwater sampling downgradient of RS09.

December 21, 2006 Performed 1/4ly well samplings.

March 12, 2007 Performed 1/4ly well samplings.

June 20, 2007 Performed 1/4ly well samplings

September 26, 2007 Performed 1/4ly well samplings

October 5, 2007	Signed Proposal and Contract Agreement to connect intercept trench
December 18, 2007	Performed 1/4ly well samplings
February 28, 2008	Turned off groundwater pump and treatment system, pinhole leak in #1 water carbon.
March 3, 2008	Removed #1 water carbon, set-up #2 water carbon into #1 position and newly delivered water carbon into #2 position. Restarted groundwater pump and treatment system.
March 12, 2008	Cleaned and inspected RS5 pump, Performed 1/4ly well sampling
June 25, 2008	Obtained sewer discharge sample with EBMUD, monitored and sampled groundwater wells for 2 nd ¼ 2008 monitoring report.
September 17, 2008	Performed 1/4ly sampling of wells.
September 25, 2008	Pulled pump from RS05, needed extensive cleaning and service.
October 10, 2008	Reinstalled pump into RS05.
February 26, 2009	Clean #1 water carbon unit of bio film.
June 19, 2009	Obtained sewer discharge sample with EBMUD. Pulled pump from RS5, needed extensive cleaning and service.
September 1, 2009	Reinstalled pump into RS05
September 9, 2009	Receive/install new water carbon unit. Semi-Annual well samples.
December 19, 2009	Obtained sewer discharge sample as per EBMUD requirements.
March 24, 2010	Obtained semiannual monitor well samples.
June 30, 2010	Obtained sewer discharge sample and suspend sewer discharge. Removed groundwater pump from RS05 and pump controller. Pump needs cleaning.
September 16, 2010	Obtained semiannual monitor well samples.
December 30, 2010	New wastewater discharge permit from EBMUD (permit #5043550 1).
February 23, 2011	Finish construction of treatment compound and conveyance pipe from T1.
March 8, 2011	Issued City of Oakland Temporary Discharge Permit into City Sewer Line.
March 30, 2011	Delivery of water carbon units, connect filters, meters and carbons for groundwater treatment. PG&E connected electrical to new treatment compound.
April 6, 2011	Semiannual groundwater samples and start up of treatment compound, pumping from wells RS5 and T1.
July 28, 2011	Change out groundwater pumps T1 and RS05 for cleaning, clogged with orange bio.
August 8, 2011	Remove water carbon units 1 and 2 from system. Take delivery of two new water carbon units. Place #3 into #1 position, Place #4 into #2 position and place two new carbons into #3 and #4 positions.
August 24, 2011	PG&E power off to treatment compound, mistake in billing.
August 31, 2011	Turn groundwater recovery pumps RS05 and T1 back on after obtaining depth to water measurements.
September 14, 2011	Semi Annual monitor well samples and depth to water measurements.

3.0 LOCAL GEOLOGY

3.1 Geomorphology

The site is located on the western slope of the Berkeley Hills. The Berkeley Hills are a northwest-southeast trending range within the Coastal Range Province of California. Erosion of the Coastal Ranges has filled the valleys within and bordering the Coastal Range with sequences of gravels, silts, sands, and clays.

3.2 Stratigraphy

Station Property

The native soil from surface to 13 feet below ground surface (BGS) consists of dark brown silty clay. The dark brown clay is underlain by light brown stiff clay that includes subrounded to rounded metavolcanic gravel. This clay extends to approximately 23 feet BGS at the northwest corner of the site. A fine to medium sand, clayey sand, and silty sand underlies the gravel and clay.

Backyard Sewer Lateral Route

Assessments performed along the sewer lateral as it leaves the site and routes through the residential area towards Brighton Avenue show the subsurface to consist of fill from a couple of inches thick to two feet thick. Beneath the fill is a sequence of clay formations that vary from light brown to dark gray to approximately the 6 foot depth. Silty clay then extends to approximately the 14-foot depth. Beneath the silty clay is sand with occasional gravel. This sand is 11 feet thick at RS05 and is underlain by silty clay.

Brighton Avenue

Construction of the receptor trench along the eastern curb area of Brighton Avenue revealed two separate sequences of lithology. North of the storm drain catch basin the sequence consists of; clay to the four foot depth, silty clay to the seven foot depth, fine silty sand to the 9 foot depth, medium sand to the 10 foot depth, silty clay to the 11 ½ foot depth, gravel to the 12 foot depth underlain by clay to the 16 foot depth. South of the storm catch basin is a sequence of silty clays and clays to depth.

Sandier sequence of sediments north of the storm water catch basin at Brighton Avenue compared to the sediments south of the storm water catch basin, indicate a facies change or a fault remnant striking east/west near the storm drain catch basin. A topographic lineation along the 200 foot contour is located in this area, see Figure 2.

4.0 WORK PERFORMED, June 29, - September 23, 2011.

During this time frame, Western Geo-Engineers performed monthly depth to water measurements to evaluate the pumping effects from T1 and RS05, obtained the required semi-annual monitor

wells samples and changed out two water carbon units with the necessary operations and maintenance checks.

5.0 COLLECTION AND ANALYSIS OF GROUNDWATER SAMPLES

Groundwater samples were collected on September 14, 2011. Samples were analyzed for Total Petroleum Hydrocarbons as gasoline, Benzene, Toluene, Ethylbenzene, Xylenes, the fuel oxygenant Methyl tert-Butal Alcohol (MtBE) using EPA method 8260B, see Table 1. Figure 3 shows the positions of the groundwater monitoring wells, the receptor trench and previous sample locations.

4.1 Depth to Water Measurements

On August 10 and 31 and September 14, 2011 depth to water was measured at each well using a product/water interface probe. Measurements are referenced to the surveyed elevation at the top of casing at each well. Table 1 shows the elevation of groundwater with respect to mean sea level for all wells through September 16, 2010.

5.0 RESULTS OF GROUNDWATER MONITORING

5.1 Groundwater Gradient and Flow Direction

Figure 4A shows the groundwater elevation gradients and flow direction that were derived from the depth to water measurements of the monitor wells on August 10, 2011, prior to purging the wells for sampling. Groundwater pumping was occurring from wells RS05 and T1. The gradient from trench well T2 to monitor well RS08 was 0.138 ft/ft to the west. Figure 4B shows the groundwater elevation gradients and flow directions derived from the depth to water measurements of the monitor wells on August 31, 2011. There was no groundwater pumping for at least one week prior to these depth to water measurements, power was turned off to the treatment compound by PG&E. The gradient from trench well T2 to RS05 was 0.111 ft/ft again flowing to the west. Figure 4C shows the groundwater elevation gradients and flow direction that were derived from the depth to water measurements of the monitor wells on September 14, 2011, prior to purging the wells for sampling. Groundwater pumping was occurring from wells RS05 and T1. The gradient from trench well T2 to monitor well RS08 was 0.130 ft/ft to the west, see Table 1 and Appendix A.

The prior non pumping influence, flow direction is to the west northwest. The hydraulic gradient averaged 0.095 feet/linear foot down gradient from well RS10 to the intercept trench well T1. The current pumping gradients show a slight increase in slope (cone of influence) towards the pumping wells. The present flow direction and hydraulic gradient are consistent with previous determinations by WEGE. Well LF1 has been removed by the property owner of 4003 Park Blvd. and is no longer available for sampling and/or depth to water measurements. Previous depth to water measurements showed that the groundwater gradient has a steep slope that extends south of RS05 and RS08 out to well LF1. This Northwest lineation is seen in previous groundwater gradient determinations and could be continuous to the change in lithology noted during the excavation of the intercept trench. The excavation south of T1 contained clay and the area north of T1 contained sands.

5.2 Results of Certified Analysis of Groundwater Samples

The results of the certified analyses of groundwater samples collected on September 14, 2011 are shown in Table 1. Groundwater samples were obtained from monitor wells R1, R2, RS05, RS07, RS08, RS09, RS10 and trench well T1. RS05 and T1 wells contained submersible pumps, samples were obtained from the sample port of the influent of the first water carbon for these wells, see Appendix A Methods and Procedures.

Total Petroleum Hydrocarbons - gasoline

Total Petroleum Hydrocarbons-gasoline range (TPHg) has a laboratory lower detection limit (LLDL) of 50 ug/L. TPH-G concentrations above the LLDL were found in water samples from monitor wells R1, R2, RS05, RS07, RS08, RS09 and the receptor trench well (T1) ranged from 19000 ug/L at well RS08, to 240 ug/L at well RS09. Well RS10 was below LLDL and well R3 was not sampled due to lack of groundwater, see Figure 5 and Appendix C – Laboratory Report.

Benzene

Benzene has a LLDL of 0.5 ug/L. The recommended CPHG (California Public Health Goal) for Benzene is 1.5 ug/L. Benzene concentrations were found in wells; R1 at 3.5 ug/L, R2 at 130 ug/L, RS05 at 7.6 ug/L, trench well T1 at 10 ug/L, RS07 at 0.76 ug/L, RS08 at 130 ug/L and RS09 at 0.52 ug/L. RS10 was below laboratory lower detection limits of 0.5 ug/L, see Figure 5 and Appendix C - Laboratory Report.

MtBE

MtBE has a LLDL of 0.5 ug/L. The recommended CPHG for MtBE is 13 ug/L. Analytical results for Fuel Oxygenant MtBE were below laboratory lower detection limits in wells R1, R2, RS05, RS07, RS08, RS10 and trench well T1 at 0.5 ug/L. Well RS09 contained 1.2 ug/L, see Figure 6 and Appendix C – Laboratory Report.

Toluene

Toluene has a LLDL of 0.5 ug/L. The recommended CPHG for toluene is 150 ug/L. Toluene was detected in wells RS05, RS08, R1, R2 and T1, ranging from a low of 0.63 ug/L at well R1 to a high of 60 ug/L at well RS08. Wells RS07, RS09 and RS10 were below LLDL of 0.5 ug/L.

Ethylbenzene

Ethylbenzene has a LLDL of 0.5 ug/L. The recommended CPHG for Ethylbenzene is 300 ug/L. Ethylbenzene was detected in wells RS05, RS07, RS08, R1, R2 and T1, ranging from a low of 3.2 ug/L at wells RS07 and R1 to a high of 86 ug/L at well RS08.

Xylenes

Xylenes have a LLDL of 0.5 ug/L. The recommended CPHG for Xylenes is 1800 ug/L. Xylenes were detected in wells RS05, RS07, RS08, R1, R2 and T1, ranging from a low of 0.67 ug/L at well RS07 to a high of 1300 ug/L at well RS08, see Table 1 and Appendix C - Laboratory Report.

6.0 PURGING/PUMPING OF RECEPTOR (INTERCEPT) TRENCH

The last purging of the receptor (intercept) trench occurred on June 30, 2004. A total of 93,553 gallons of groundwater had been pumped from the receptor trench and purged from the groundwater monitoring wells, see Table 2.

A 4 inch submersible grundfos pump was installed into trench well T1 on March 30, 2011. Pumping commenced from well T1 after depth to water measurements and groundwater samples were obtained from all of the monitor wells on April 6, 2011. The system was turned off on April 10, 2011 when leaks were noticed in the compound, no pumped water left the spill containment from the compound. All leaks were removed/repared. The leaked water drained to a sump inside the spill containment and was pumped through 4 carbon units prior to be discharged to the sanitary sewer. A pressure reducer and valve regulator was installed at the T1 well head on April 13, 2011 and pumping was resumed. As of September 23, 2011 113,700 gallons of water has been pumped from T1 since resuming pumping. This water is treated through a sediment filter and 4 in series carbon units prior to discharge to sewer. As of September 23, 2011 207,386 gallons of contaminated groundwater has been pumped from T1 and purged from monitor wells, see Table 2. Along with a calculated removal of TPHg as dissolved gasoline in water of 1.25 gallons, see Table 3.

7.0 PUMPING ON-SITE WELL RS05

On February 15, 2001 a submersible pump with a pump bypass was placed into RS05. The pump rate was adjusted to 1.5 gpm and allowed to continuously pump from RS-5 for one week. 3223 gallons were pumped from RS05 through the two, in series, water carbon units and discharged to the sewer. On February 22, 2001 the pump was inspected and showed a slimy growth covering the pump and discharge line that was below the water level. The pump was cleaned and placed back into RS05 and continued to discharge from RS05 through the water carbon units to sewer until July 19, 2001. On July 19, 2001 Desert Petroleum requested suspension of further pumping at the site. The pump was removed and the site secured. From February 15 through July 19, 2001, 78,919 gallons of gasoline contaminated groundwater was recovered from RS05 and treated through carbon before being discharged to the sewer. Pumping from RS05 was resumed on March 21, 2002. A site visit was conducted on June 30, 2010 to remove the pump from RS05 for inspection and cleaning and to obtain a discharge sample prior to suspension of the sewer discharge permit. As of June 30, 2010, 1,714,572 gallons of groundwater have been discharged to the sewer of which 1,620,974 gallons was pumped from RS5 and treated through two, in series, water carbon units prior to being discharge to the sanitary sewer.

On April 6, 2011, a 4 inch submisable grundos pump was installed into RS05. After depth to water measurements and samples were obtained from all of the monitor wells, the pump was turned on. The system was turned off on April 10, 2011 when leaks were noticed in the compound, no

pumped water left the spill containment from the compound. The leaks were repaired/eliminated. The leaked water drained to a sump inside the spill containment and was pumped through 4 carbon units prior to be discharged to the sanitary sewer. On April 13, 2011 pumping was resumed. As of September 23, 2011 98,327 gallons of water has been pumped from RS05 since resuming pumping. This water is treated through a sediment filter and 4 in series carbon units prior to discharge to sewer. As of September 23, 2011 1,719,301 gallons of contaminated groundwater has been pumped from RS05, see Table 2. Along with a calculated removal of TPHg as dissolved gasoline in water of 13.98 gallons, see Table 3.

The pumping from RS05 has lowered the groundwater at this well by at least 12 feet, when compared to non pumping water measurements, see Charts - Appendix B. This creates a cone of influence out to offsite wells RS08 and RS10.

8.0 FREE PHASE FLOATING PRODUCT REMOVAL

Yellow Free Phase Floating Product was discovered in well RS8, 0.04 feet in thickness on August 6, 2002. Since all product storage and dispensing systems have been removed from the site (June 1994), it is thought that the product found in RS08, is residual from the November 1989 release and groundwater pumping at RS05 was retrieving this residual product. Weekly bailing of the floating product from November 20, 2002 through December 12, 2002, (the last noted detection of free phase product in RS8) removed 0.014 gallons of degraded gasoline. This recovered degraded gasoline was stored on site in a 55 gallon 17H drum. Inspection of the 55 gallon drum on June 21, 2006 showed that the recovered gasoline had evaporated; the drum was empty. This 55 gallon drum was removed from the site on February 23, 2011

9.0 SUMMARY

The lowest hydrocarbon concentrations were observed May 31, 2001 while the weekly pumping of the trench well and the continuous pumping of RS05 were occurring; pumping from RS05 was discontinued between June 19, 2001 and March 21, 2002 and on June 30, 2010. Groundwater pumping was resumed after securing a new sewer discharge permit from EBMUD. Pumping commenced from wells T1 (interecept trench) and RS05 on April 6, 2011. The most recent sampling, September 14, 2011 shows a dramatic decrease in hydrocarbon concentrations in wells RS5, RS7, RS9, and T1, see Table 1 and Charts in Appendix B.

Previous sampling on September 2, 1999, showed that aerobic bacteria (hydrocarbon degraders) exist in the groundwater associated with the hydrocarbon plume.

Soil core samples obtained from drilling activities December 2004 at 4035 Park Blvd showed high concentrations of TPHg and BTEX existed in the soils and shallow groundwater (8 ft to 32 ft below ground surface) beneath the area that was previously occupied by the station building. Soil samples obtained during drilling for geotechnical grading permit/excavation stability study on January 24, 2011 showed reductions in the soil contamination near previously core sample boring C6 (natural attenuation), see Tables 5 and 6. These reductions were calculated for TPHg of 55%, Benzene of

99.5%, Toluene of 98% and Ethylbenzene of 60%. Water sampling of the December 2004 borings showed slow drainage, indicating low hydraulic conductivity in the silty clay and the clayey conglomerate formations. Previous slug test on temporary piezometers installed downgradient of the site, in the backyard of the surrounding residences, showed groundwater velocities ranging between 4 and 385 feet per year. Previous pumping (June 30, 2010) showed RS5 produced approximately 500 gallons per day (<0.5 gpm). To further slow the migration of the contaminants of concern, organic carbon analysis showed total organic carbon in the water bearing formations to range between 340 and 5700 mg/Kg. Along with the organic carbon, natural attenuation is occurring as evident from analysis for the electron acceptors (dissolved oxygen, nitrate, sulfate and ferric iron), the January 24, 2011 soil sample results along with the presence of biological indicators (carbon dioxide, methane, aerobic hydrocarbon degrading bacteria, and reduced nutrients ortho phosphate and ammonia as nitrogen).

Alameda County Health, in a letter dated November 16, 2005 concurred with the recommendations to remove the remaining on-site hydrocarbon source (based on the December 2004 sample results), continue existing groundwater extraction from well RS05 and to conduct continuous groundwater extraction from the intercept trench (T1 well). These procedures were recommended by Western Geo-Engineers in their March 8, 2005 report "Soil and Groundwater Investigation with Conceptual Model

A Work Plan detailing the above activities was approved. The destruction of on-site monitoring wells MW01, RS02 and RS06 was completed in November 2006 along with the soil and groundwater sampling downgradient of monitor wells RS09. The encroachment permit agreement with the City of Oakland, necessary for the construction of a conveyance pipe from the Brighton Avenue trench to a soon to be constructed treatment compound at 4035 Park Blvd. has been finalized. RAH had obtaining all necessary permits from The City of Oakland. A conveyance piping system was installed and connects intercept trench wells T1, T2 and T4 to a newly installed treatment compound. Pumping from wells T1 and RS05 was initiated on April 6, 2011. A revised work plan that focused on the onsite excavation work was generated and approved by Alameda County Environmental Health. This work was scheduled to commence in August 2010, but due to lack of funding, the necessary geotechnical study could not be completed along with lack of assurance for funding the excavation work was postponed. The geotechnical study necessary for the excavation design and grading permit is currently being performed by GTC GeoTrinity Consultants, Inc.

Since the April 6, 2011 monitor well samples, which occurred prior groundwater recovery from wells T1 and RS05, this latest sampling has shown a dramatic decline in contaminants of concern. Pumping well T1 has decreased in concentrations from TPHg 41,000 ug/L to 1,200 ug/L, Benzene has decreased in concentrations from 12,000 ug/L to 10 ug/L, Toluene has decreased in concentrations from 3,000 ug/L to 5.7 ug/L, Ethylbenzene has decreased in concentrations from 1,200 ug/L to 8.6 ug/L, Xylenes have decreased in concentration from 3,300 ug/L to 85 ug/L and MtBE has decreased in concentration from 30 ug/L to <0.5 ug/L. Likewise pumping well RS05 showed substantial decreases of TPHg from 4,800 ug/L to 1,200 ug/L, Benzene from 100 ug/L to 7.6 ug/L, Toluene from 31 ug/L to 4.7 ug/L, Ethylbenzene from 200 ug/L to 180 ug/L and Xylenes from 370 ug/L to 74 ug/L. The following wells showed similar reductions; RS07 and RS09. Wells

R1, R2 and RS08 showed increases, most likely due to the pumping well RS05 capturing and pulling coc's past these wells.

10.0 RECOMMENDATIONS

- Finalize geotechnical study necessary for the proposed excavation.
- Revise Excavation Plan and Submit to Alameda County Health.
- Develop a timeline to complete the excavation work by no later than September 1, 2012.

11.0 TIME FRAME

December 2011	Completion of geotechnical investigation needed for permitting of excavation work.
December 2011	4 th Quarter 2011 Update Status Report

12.0 LIMITATIONS

This report is based upon the following:


- A. The observations of field personnel.
- B. The results of laboratory analyses performed by a state certified laboratory.
- C. Referenced documents.
- D. Our understanding of the regulations of the State of California, Alameda County and the City of Oakland.
- E. Changes in groundwater conditions can occur due to variations in rainfall, temperature, local and regional water use, and local construction practices.
- F. In addition, variations in the soil and groundwater conditions could exist beyond the points explored in this investigation.

State Certified Laboratory analytical results are included in this report. This laboratory follows EPA and State of California approved procedures; however, WEGE is not responsible for errors in these laboratory results. The services performed by Western Geo-Engineers have been conducted in a manner consistent with the level of care and skill ordinarily exercised by members of our profession currently practicing under similar conditions in the State of California and the Oakland area. Our work and/or supervision of remediation and/or abatement operations, active or preliminary, at this site is in no way meant to imply that we are owners or operators of this site. Known or suspected contamination of soil and/or groundwater must be reported to the appropriate agencies in a timely manner. No other warranty, expressed or implied, is made.

Sincerely,



George Converse
Project Geologist



Jack E. Napper
Ca. Reg. Geologist #3037

cc: Mr. J. Wickham, Alameda County Health (510) 567-6791
Mr. Kin Man Li, property owner (510) 599-7000

TABLE 1
GROUNDWATER ELEVATIONS AND CERTIFIED ANALYTICAL LABAORATAORY RESULTS FROM WATER SAMPLES
DESERT PETROLEUM, INC. SITE #793
4035 PARK BOULEVARD, OAKLAND, CALIFORNIA

ID#	DATE SAMPLED	(All concentrations in parts per billion [ug/L, ppb]) (AMSL = Above mean sea level)									
		WELL CASING ELEVATION (FEET AMSL)	DEPTH TO GROUND WATER (FEET)	GROUND WATER ELEVATION (FEET AMSL)	free phase prod. ft	TPH-G (UG/L)	BENZENE (UG/L) (1.5)	TOLUENE (UG/L) (150)	ETHYL-BENZENE (UG/L) (300)	XYLENES (UG/L) (1800)	MTBE (UG/L) (13)
(CALIFORNIA PUBLIC HEALTH GOAL)											
RS-01	12/14/1989	228.15	24.25	203.9		19000	2600	2700	200	1200	
RS-01	12/90					15000	3500	330	170	760	
RS-01	2/91					6900	910	200	39	540	
RS-01	6/91					1600	56	180	12	26	
RS-01	9/91					4100	730	7.6	5.1	24	
RS-01	12/91					8300	950	160	71	190	
RS-01	11/9/1992	228.15	17.05	211.1		1700	730	9.6	16	14	
RS-01	4/7/1994	228.15	13	215.15		860	84	12	16	110	
RS-01	6/19/1994	228.15	13.37	214.78		1400	150	12	52	87	
RS-01	9/17/1994	228.15	16.33	211.82		310	30	1.8	2.8	3.9	
RS-01	3/12/1995	228.15	4.66	223.49		ND	ND	ND	ND	ND	
RS-01	8/14/1995	DESTROYED BY OVER-EXCAVATION OF UST-DISPENSER AREAS (8/14/95)									
RS-01	9/5/1995	REPLACED WITH MW-1 9/5/95.									
MW-01	10/4/1995	229.5	12.38	217.12		ND	ND	ND	ND	ND	
MW-01	12/21/95	229.5	13.40	216.1		< 50	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5
MW-01	03/27/96	229.5	5.53	223.97		< 50	< 0.5	< 0.5	< 0.5	< 2	< 50
MW-01	06/11/96	229.5	9.02	220.48		< 50	< 0.5	< 0.5	< 0.5	< 2	< 50
MW-01	09/04/96	229.5	11.84	217.66		< 50	< 0.5	< 0.5	< 0.5	< 2	< 5
MW-01	12/11/96	229.5	12.98	216.52		< 50	< 0.5	0.9	< 0.5	< 1	< 0.5
MW-01	2/21/97	229.5	9.50	220		< 50	< 0.5	0.9	< 0.5	< 1	< 0.5
MW-01	5/28/97	229.5	11.18	218.32		< 50	3	3	< 0.5	< 1	< 0.5
MW-01	9/2/1997	229.5	13.00	216.5		< 50	5	< 0.5	< 0.5	< 1	< 0.5
MW-01	11/24/1997	229.5	14.12	215.38		< 50	5	< 0.5	< 0.5	< 1	< 0.5
MW-01	2/25/1998	229.5	6.41	223.09		< 50	< 0.5	< 0.5	< 0.5	< 1	< 0.5
MW-01	7/8/1998	229.5	7.28	222.22		< 50	< 0.5	< 0.5	< 0.5	< 1	< 1
MW-01	9/16/1998	229.5	10.96	218.54		< 50	< 0.5	< 0.5	< 0.5	< 1	< 1
MW-01	11/24/1998	229.5	12.24	217.26		52	2.3	5.2	< 0.5	5.4	11
MW-01	2/23/1999	229.5	7.14	222.36		< 50	< 0.5	5	< 0.5	< 1	< 0.5
MW-01	5/5/1999	229.5	7.00	222.5		< 50	2	<0.5	< 0.5	< 1	8
MW-01	8/26/1999	229.5	11.41	218.09		<50	4.1	<0.5	< 0.5	< 1	<1
MW-01	11/10/1999	229.5	13.27	216.23		<50	<0.5	<0.5	< 0.5	< 1	<0.5
MW-01	2/9/2000	229.5	13.76	215.74		<50	<0.5	<0.5	0.5	< 1	0.5
MW-01	6/30/2000	229.5	10.63	218.87		<50	<0.5	<0.5	< 0.5	< 1	< 0.5
MW-01	8/8/2000	229.5	11.77	217.73		62	1	2	< 0.5	2	< 0.5
MW-01	11/16/2000	229.5	13.33	216.17		<50	<0.5	<0.5	< 0.5	< 1	< 0.5
MW-01	3/8/2001	229.5	12.30	217.2		<50	<0.5	<0.5	< 0.5	< 0.5	< 0.5
MW-01	5/31/2001	229.5	11.88	217.62		<50	<0.5	<0.5	< 0.5	< 0.5	< 0.5
MW-01	12/18/2001	229.5	13.74	215.76		<50	<0.5	<0.5	< 0.5	< 0.5	< 0.5
MW-01	2/19/2002	229.5	14.42	215.08		<50	<0.5	<0.5	< 0.5	< 0.5	< 0.5
MW-01	5/7/2002	229.5	10.78	218.72		<50	<0.5	<0.5	< 0.5	< 0.5	< 0.5
MW-01	8/6/2002	229.5	12.70	216.8		<50	<0.5	<0.5	< 0.5	< 0.5	< 0.5
MW-01	11/5/2002	229.5	15.00	214.5		<50	<0.5	<0.5	< 0.5	< 0.5	< 0.5
MW-01	12/12/2002	229.5	15.46	214.04							
MW-01	3/13/2003	229.5	14.51	214.99		<50	<0.5	<0.5	< 0.5	< 0.5	< 0.5
MW-01	5/6/2003	229.5	11.06	218.44		<50	<0.5	<0.5	< 0.5	< 0.5	< 0.5
MW-01	8/13/2003	229.5	13.13	216.37		<50	<0.5	<0.5	< 0.5	< 0.5	< 0.5
MW-01	11/20/2003	229.5	14.85	214.65		<50	<0.5	<0.5	< 0.5	< 0.5	< 0.5
MW-01	1/22/2004	229.5	13.65	215.85							
MW-01	3/30/2004	229.5	11.68	217.82		<50	<0.5	<0.5	< 0.5	< 0.5	< 0.5
MW-01	6/10/2004	229.5	13.08	216.42		<50	<0.5	<0.5	< 0.5	< 0.5	< 0.5
MW-01	9/28/2004	229.5	14.33	215.17		<50	<0.5	<0.5	< 0.5	< 0.5	< 0.5
MW-01	12/8/2004	229.5	14.67	214.83		<50	<0.5	<0.5	< 0.5	< 0.5	< 0.5
MW-01	3/23/2005	229.5	9.60	219.9		<50	<0.5	<0.5	< 0.5	< 0.5	< 0.5
MW-01	6/1/2005	229.5	8.64	220.86		<50	<0.5	<0.5	< 0.5	< 0.5	< 0.5
MW-01	9/21/2005	229.5	11.81	217.69		<50	1.3	<0.5	< 0.5	< 0.5	< 0.5
MW-01	12/7/2005	229.5	13.02	216.48		<50	1.7	<0.5	0.63	0.76	< 0.5
MW-01	3/28/2006	229.5	5.94	223.56		<50	<0.5	<0.5	< 0.5	< 0.5	< 0.5
MW-01	6/21/2006	229.5	7.63	221.87		<50	<0.5	<0.5	< 0.5	< 0.5	< 0.5
MW-01	9/13/2006	229.5	11.40	218.1		<50	<0.5	<0.5	< 0.5	< 0.5	< 0.5
MW-01	11/27/2006	well destroyed, Alameda County Public Works Permit #W2006-0971									
RS-02	12/14/1989	227.39									
RS-02	6/19/1994	227.39	10.89	216.50							

TABLE 1
GROUNDWATER ELEVATIONS AND CERTIFIED ANALYTICAL LABAORATAORY RESULTS FROM WATER SAMPLES
DESERT PETROLEUM, INC. SITE #793
4035 PARK BOULEVARD, OAKLAND, CALIFORNIA

ID#	DATE SAMPLED	(All concentrations in parts per billion [ug/L, ppb]) (AMSL = Above mean sea level)									
		WELL CASING ELEVATION (FEET AMSL)	DEPTH TO GROUND WATER (FEET)	GROUND WATER ELEVATION (FEET AMSL)	free phase prod. ft	TPH-G (UG/L)	BENZENE (UG/L) (1.5)	TOLUENE (UG/L) (150)	ETHYL-BENZENE (UG/L) (300)	XYLENES (UG/L) (1800)	MTBE (UG/L) (13)
(CALIFORNIA PUBLIC HEALTH GOAL)											
RS-02	3/12/1995	227.39	5.26	222.13		ND	ND	ND	ND	ND	
RS-02	10/4/1995	227.39	15.05	212.34		ND	ND	ND	ND	ND	
RS-02	12/21/95	227.39	9.95	217.44		< 50	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5
RS-02	03/27/96	227.39	6.28	221.11		< 50	< 0.5	< 0.5	< 0.5	< 2	< 50
RS-02	06/11/96	227.39	8.00	219.39		< 50	1.2	2.8	< 0.5	< 2	< 50
RS-02	09/04/96	227.39	9.89	217.50		< 50	< 0.5	< 0.5	< 0.5	< 2	< 5
RS-02	12/11/96	227.39	8.38	219.01		< 50	< 0.5	< 0.5	< 0.5	< 1	6
RS-02	2/21/97	227.39	6.96	220.43		< 50	< 0.5	< 0.5	< 0.5	< 1	< 0.5
RS-02	5/28/97	227.39	10.02	217.37		< 50	3	3	< 0.5	< 1	< 0.5
RS-02	9/2/1997	227.39	11.46	215.93		< 50	< 0.5	< 0.5	< 0.5	< 1	< 0.5
RS-02	11/24/1997	227.39	10.43	216.96		< 50	< 0.5	1	< 0.5	3	< 0.5
RS-02	2/25/1998	227.39	3.57	223.82		< 50	< 0.5	< 0.5	< 0.5	< 1	< 0.5
RS-02	7/8/1998	227.39	8.83	218.56		< 50	< 0.5	< 0.5	< 0.5	< 1	< 1
RS-02	9/16/1998	227.39	10.60	216.79		< 50	< 0.5	< 0.5	< 0.5	< 1	< 1
RS-02	11/24/1998	227.39	13.27	214.12		140	2.8	19	2.6	3.3	15
RS-02	2/23/1999	227.39	4.06	223.33		< 50	< 0.5	< 0.5	< 0.5	< 1	< 0.5
RS-02	5/5/1999	227.39	7.70	219.69		< 50	0.7	< 0.5	< 0.5	< 1	6
RS-02	8/26/1999	227.39	11.42	215.97		200	15	23	1.7	23	9
RS-02	11/10/1999	227.39	15.94	211.45		< 50	<0.5	<0.5	<0.5	< 1	<0.5
RS-02	2/9/2000	227.39	8.91	218.48		< 50	<0.5	<0.5	<0.5	< 1	<0.5
RS-02	6/30/2000	227.39	9.79	217.60		52	2	<0.5	<0.5	< 1	<0.5
RS-02	8/8/2000	227.39	10.71	216.68		60	<0.5	<0.5	<0.5	< 1	<0.5
RS-02	11/16/2000	227.39	10.39	217.00		< 50	<0.5	<0.5	<0.5	< 1	<0.5
RS-02	3/8/2001	227.39	6.62	220.77		< 50	<0.5	<0.5	<0.5	<0.5	<0.5
RS-02	5/31/2001	227.39	10.09	217.30		< 50	<0.5	<0.5	<0.5	<0.5	<0.5
RS-02	12/18/2001	227.39	6.99	220.40		< 50	<0.5	<0.5	<0.5	<0.5	<0.5
RS-02	2/19/2002	227.39	8.08	219.31		< 50	<0.5	<0.5	<0.5	<0.5	<0.5
RS-02	5/7/2002	227.39	9.27	218.12		< 50	<0.5	<0.5	<0.5	<0.5	<0.5
RS-02	8/6/2002	227.39	11.38	216.01		< 50	<0.5	<0.5	<0.5	<0.5	<0.5
RS-02	11/5/2002	227.39	17.09	210.30		< 50	<0.5	<0.5	<0.5	<0.5	<0.5
RS-02	12/12/2002	227.39	13.19	214.20							
RS-02	3/13/2003	227.39	8.93	218.46		< 50	<0.5	<0.5	<0.5	<0.5	<0.5
RS-02	5/6/2003	227.39	8.05	219.34		< 50	<0.5	<0.5	<0.5	<0.5	<0.5
RS-02	8/13/2003	227.39	11.16	216.23		< 50	<0.5	<0.5	<0.5	<0.5	<0.5
RS-02	11/20/2003	227.39	17.62	209.77		< 50	<0.5	<0.5	<0.5	<0.5	<0.5
RS-02	1/22/2004	227.39	7.40	219.99							
RS-02	3/30/2004	227.39	7.95	219.44		< 50	<0.5	<0.5	<0.5	<0.5	<0.5
RS-02	6/10/2004	227.39	10.56	216.83		< 50	<0.5	<0.5	<0.5	<0.5	<0.5
RS-02	9/28/2004	227.39	17.02	210.37		< 50	<0.5	<0.5	<0.5	<0.5	<0.5
RS-02	12/8/2004	227.39	9.80	217.59		< 50	<0.5	<0.5	<0.5	<0.5	<0.5
RS-02	3/23/2005	227.39	5.05	222.34		< 50	<0.5	<0.5	<0.5	<0.5	<0.5
RS-02	6/1/2005	227.39	8.60	218.79		< 50	<0.5	<0.5	<0.5	<0.5	<0.5
RS-02	9/21/2005	227.39	11.45	215.94		< 50	1.4	<0.5	<0.5	<0.5	<0.5
RS-02	12/7/2005	227.39	10.82	216.57		< 50	<0.5	<0.5	<0.5	<0.5	<0.5
RS-02	3/28/2006	227.39	3.85	223.54		< 50	<0.5	<0.5	<0.5	<0.5	<0.5
RS-02	6/21/2006	227.39	8.86	218.53		< 50	<0.5	<0.5	<0.5	<0.5	<0.5
RS-02	9/13/2006	227.39	11.25	216.14		< 50	<0.5	<0.5	<0.5	<0.5	<0.5
RS-02	11/27/2006	well destroyed, Alameda County Public Works Permit #W2006-0972									
RS-05	12/14/1989	227.61	25.97	201.64		57000	3100	4300	670	3400	
RS-05	2/91	227.61			sheen						
RS-05	6/91	227.61			sheen						
RS-05	9/91	227.61			sheen						
RS-05	12/91	227.61			sheen						
RS-05	11/9/1992	227.61	20.73	206.88		50000	650	4800	1100	15000	
RS-05	4/7/1994	227.61	18.16	209.45		27000	5000	8700	550	2800	
RS-05	6/19/1994	227.61	18.11	209.5		20000	2100	5300	470	2500	
RS-05	9/17/1994	227.61	19.63	207.98		9300	230	340	110	700	
RS-05	3/12/1995	227.61	14.54	213.07		93000	6400	2000	19000	10000	
RS-05	10/4/1995	227.61	17.53	210.08		16000	420	2100	320	1800	
RS-05	12/21/95	227.61	17.47	210.14		48000	3500	9200	840	4800	56
RS-05	03/27/96	227.61	13.51	214.1		68000	4900	18000	1700	11000	< 3000
RS-05	06/11/96	227.61	14.25	213.36		66000	6300	20000	2100	12000	< 3000

TABLE 1
GROUNDWATER ELEVATIONS AND CERTIFIED ANALYTICAL LABAORATAORY RESULTS FROM WATER SAMPLES
DESERT PETROLEUM, INC. SITE #793
4035 PARK BOULEVARD, OAKLAND, CALIFORNIA

ID#	DATE SAMPLED	(All concentrations in parts per billion [ug/L, ppb]) (AMSL = Above mean sea level)									
		WELL CASING ELEVATION (FEET AMSL)	DEPTH TO GROUND WATER (FEET)	GROUND WATER ELEVATION (FEET AMSL)	free phase prod. ft	TPH-G (UG/L)	BENZENE (UG/L) (1.5)	TOLUENE (UG/L) (150)	ETHYL-BENZENE (UG/L) (300)	XYLENES (UG/L) (1800)	MTBE (UG/L) (13)
(CALIFORNIA PUBLIC HEALTH GOAL)		227.61	16.50	211.11		31000	2100	11000	1100	6800	400
RS-05	09/04/96	227.61	16.50	211.11		31000	2100	11000	1100	6800	400
RS-05	12/11/96	227.61	15.88	211.73		85000	7000	21000	1800	8900	570
RS-05	2/21/97	227.61	13.76	213.85	sheen	100000	5000	22000	1700	7300	<0.5
RS-05	5/28/97	227.61	15.77	211.84		52000	4500	19000	2100	10000	<0.5
RS-05	9/2/1997	227.61	17.47	210.14		38000	2200	9400	1300	5800	<0.5
RS-05	11/24/1997	227.61	18.67	208.94		45000	4000	16000	1900	9700	<0.5
RS-05	2/25/1998	227.61	10.53	217.08		160000	2700	31000	5300	28000	<0.5
RS-05	7/8/1998	227.61	13.75	213.86		45000	2800	12000	2000	8500	<10
RS-05	9/16/1998	227.61	15.80	211.81		49000	1400	7500	1700	8600	<5
RS-05	11/24/1998	227.61	16.64	210.97		89000	5300	15000	2800	13000	<10
RS-05	2/23/1999	227.61	12.36	215.25		19000	1900	11000	2500	4800	<25
RS-05	5/5/1999	227.61	12.78	214.83		78000	2000	10000	3000	15000	540
RS-05	8/26/1999	227.61	16.06	211.55		35000	870	4000	1900	8300	<1
RS-05	11/10/1999	227.61	17.54	210.07		40000	1000	5600	1800	8100	<0.5
RS-05	2/9/2000	227.61	16.31	211.3		46000	1400	6900	2700	11000	<0.5
RS-05	6/30/2000	227.61	15.15	212.46		37000	810	5200	2200	9100	<2.5
RS-05	8/8/2000	227.61	16.10	211.51		14000	330	500	1400	6500	<0.5
RS-05	11/16/2000	227.61	17.38	210.23		23000	430	2300	1100	4800	<0.5
RS-05	3/8/2001	227.61	27.72	199.89		11000	360	260	140	1500	2.6
RS-05	5/31/2001	227.61	22.96	204.65		7500	26	11	38	470	<5
RS-05	12/18/2001	227.61	15.61	212		12000	610	1200	100	1500	<5
RS-05	2/19/2002	227.61	14.80	212.81		22000	460	1700	680	4000	<5
RS-05	5/7/2002	227.61	31.77	195.84		700	150	10	19	67	5.2
RS-05	8/6/2002	227.61	31.77	195.84		< 50	<0.5	<0.5	<0.5	<0.5	<0.5
RS-05	11/5/2002	227.61	31.77	195.84		12000	150	360	21	890	<2
RS-05	12/12/2002	227.61	21.53	206.08							
RS-05	3/13/2003	227.61	36.70	190.91		240	5.5	1.9	2.3	9.6	1.4
RS-05	5/6/2003	227.61	14.52	213.09							
RS-05	8/13/2003	227.61	31.77	195.84		310	1.4	<0.5	1	2.9	<0.5
RS-05	11/20/2003	227.61	32.00	195.61		17000	150	720	240	1800	0.72
RS-05	1/22/2004	227.61	25.30	202.31							
RS-05	3/30/2004	227.61	21.90	205.71		4000	370	59	13	380	2.6
RS-05	6/10/2004	227.61	35.00	192.61		120	7	0.88	1.3	4.3	1.3
RS-05	9/28/2004	227.61	19.05	208.56		2600	110	89	75	56	<0.5
RS-05	12/8/2004	227.61	25.00	202.61		< 50	<0.5	<0.5	<0.5	<0.5	<0.5
RS-05	3/23/2005	227.61	26.05	201.56		7400	890	280	180	940	5.1
RS-05	6/1/2005	227.61	25.40	202.21		3500	380	85	59	360	3
RS-05	9/21/2005	227.61	19.00	208.61		790	34	4.7	0.86	99	<0.5
RS-05	12/7/2005	227.61	27.50	200.11		2200	65	30	24	200	1.3
RS-05	3/28/2006	227.61	19.60	208.01		5000	370	130	70	550	2.4
RS-05	6/21/2006	227.61	16.70	210.91		990	42	6.5	2.4	110	<0.5
RS-05	9/13/2006	227.61	31.00	196.61		240	11	3.2	1.2	11	0.85
RS-05	12/21/2006	227.61	28.00	199.61		4800	140	120	130	440	0.78
RS-05	3/12/2007	227.61	30.00	197.61		4300	160	130	110	600	1.5
RS-05	6/20/2007	227.61	30.00	197.61		160	7.5	3	2.2	13	0.58
RS-05	9/26/2007	227.61	22.80	204.81		2300	80	57	19	350	0.59
RS-05	12/18/2007	227.61	24.65	202.96		570	15	6.8	7.8	42	<0.5
RS-05	3/12/2008	227.61	20.50	207.11		4600	330	110	98	440	1.9
RS-05	6/25/2008	227.61	34.00	193.61		74	3.7	<0.5	0.5	2	0.7
RS-05	9/17/2008	227.61	23.45	204.16		280	4.4	1.5	0.55	18	<0.5
RS-05	12/17/2008	227.61	28.20	199.41		450	2.3	1.2	1.8	13	<0.5
RS-05	3/31/2009	227.61	34.00	193.61		800	120	14	2	54	2.7
RS-05	9/8/2009	227.61	22.30	205.31		1100	6.3	1	3.9	24	1.4
RS-05	3/24/2010	227.61	33.50	194.11		1700	200	29	10	110	2.6
RS-05	6/30/2010	227.61	16.03	211.58		280	6.3	1.1	<0.5	19	<0.5
RS-05	9/16/2010	227.61	17.02	210.59		8400	110	31	180	640	<0.5
RS-05	4/6/2011	227.61	12.62	214.99		4800	100	31	200	370	<0.9
RS-05	6/29/2011	227.61	20.22	207.39		1600	110	31	180	640	<0.5
RS-05	9/14/2011	227.61	18.70	208.91		1200	7.6	4.7	6.6	74	<0.5
RS-06	12/14/1989	227.22	22.52	204.7		11000	1400	1700	160	860	
RS-06	2/91	227.22			sheen						
RS-06	6/91	227.22				95000	4200	4200	650	3700	

TABLE 1
GROUNDWATER ELEVATIONS AND CERTIFIED ANALYTICAL LABAORATAORY RESULTS FROM WATER SAMPLES
DESERT PETROLEUM, INC. SITE #793
4035 PARK BOULEVARD, OAKLAND, CALIFORNIA

ID#	(All concentrations in parts per billion [ug/L, ppb]) (AMSL = Above mean sea level)										
	DATE SAMPLED	WELL CASING ELEVATION (FEET AMSL)	DEPTH TO GROUND WATER (FEET)	GROUND WATER ELEVATION (FEET AMSL)	free phase prod. ft	TPH-G (UG/L)	BENZENE (UG/L) (1.5)	TOLUENE (UG/L) (150)	ETHYL-BENZENE (UG/L) (300)	XYLENES (UG/L) (1800)	MTBE (UG/L) (13)
(CALIFORNIA PUBLIC HEALTH GOAL)											
RS-06	9/91	227.22			sheen						
RS-06	12/91	227.22				64000	3700	2300	730	4100	
RS-06	11/9/1992	227.22	19.43	207.79		19000	1600	710	500	1600	
RS-06	4/7/1994	227.22	14.42	212.8		16000	1200	1300	290	1100	
RS-06	6/19/1994	227.22	14.45	212.77		23000	1300	2200	590	2200	
RS-06	9/17/1994	227.22	19.52	207.7		24000	630	790	250	1100	
RS-06	3/12/1995	227.22	8.90	218.32		3200	450	13	82	230	
RS-06	10/4/1995	227.22	17.78	209.44		3700	170	250	38	290	
RS-06	12/21/95	227.22	14.98	212.24		3100	120	30	16	150	58
RS-06	03/27/96	227.22	10.00	217.22		6900	180	440	79	360	< 300
RS-06	06/11/96	227.22	12.00	215.22		7400	220	150	30	100	<1000
RS-06	09/04/96	227.22	15.00	212.22		1400	68	2.6	7.7	9.2	14
RS-06	12/11/96	227.22	12.36	214.86		1800	39	16	10	18	< 0.5
RS-06	2/21/97	227.22	10.00	217.22		2100	71	85	25	40	< 0.5 *
RS-06	5/28/97	227.22	13.56	213.66		1700	34	12	11	16	< 0.5 *
RS-06	9/2/1997	227.22	16.35	210.87		940	34	71	9	55	< 0.5 *
RS-06	11/24/1997	227.22	15.72	211.5		490	9	6	1	7	< 0.5 *
RS-06	2/25/1998	227.22	6.26	220.96		1400	22	47	5	52	< 0.5 *
RS-06	7/8/1998	227.22	11.41	215.81		1500	83	9	84	2	<10 *
RS-06	7/30/1998	227.22				<50	<0.5	<0.5	<0.5	<1	
RS-06	9/16/1998	227.22	13.42	213.8		990	23	<0.5	<0.5	<1	<1 *
RS-06	11/24/1998	227.22	15.91	211.31		3400	5.3	<0.5	<0.5	14	<0.5
RS-06	2/23/1999	227.22	7.00	220.22		1000	3.4	3.2	1.6	7.3	<0.5
RS-06	5/5/1999	227.22	10.29	216.93		1100	50	10	80	15	2
RS-06	8/26/1999	227.22	13.72	213.5		690	44	2.5	30	31	<5
RS-06	11/10/1999	227.22	13.90	213.32		1800	2	2	0.9	16	< 0.5
RS-06	2/9/2000	227.22	12.77	214.45		410	3	3	4	7	< 0.5
RS-06	6/30/2000	227.22	12.69	214.53		660	7	2	5	6	< 0.5
RS-06	8/8/2000	227.22	14.72	212.5		660	2	3	2	6	< 0.5
RS-06	11/16/2000	227.22	15.28	211.94		560	1	2	1	5	< 0.5
RS-06	3/8/2001	227.22	10.10	217.12		2200	<0.5	<0.5	<0.5	<0.5	<0.5 ****
RS-06	5/31/2001	227.22	12.96	214.26		630	<0.5	<0.5	<0.5	<0.5	<5 ****
RS-06	12/18/2001	227.22	10.88	216.34		56	0.53	<0.5	<0.5	0.56	<0.5 ****
RS-06	2/19/2002	227.22	11.08	216.14		<50	<0.5	<0.5	0.6	<0.5	<0.5 ****
RS-06	5/7/2002	227.22	12.31	214.91		240	<0.5	<0.5	<0.5	<0.5	<0.5 ****
RS-06	8/6/2002	227.22	14.23	212.99		130	<0.5	<0.5	<0.5	<0.5	3 ****
RS-06	11/5/2002	227.22	17.99	209.23		<50	<0.5	<0.5	<0.5	<0.5	<0.5 ****
RS-06	12/12/2002	227.22	17.57	209.65							
RS-06	3/13/2003	227.22	11.82	215.4		120	<0.5	<0.5	<0.5	<0.5	<0.5 ****
RS-06	5/6/2003	227.22	10.10	217.12		<50	<0.5	<0.5	<0.5	<0.5	<0.5 ****
RS-06	8/13/2003	227.22	13.88	213.34		<50	<0.5	<0.5	<0.5	<0.5	<0.5 ****
RS-06	11/20/2003	227.22	18.62	208.6		<50	<0.5	<0.5	<0.5	<0.5	<0.5 ****
RS-06	1/22/2004	227.22	11.24	215.98							
RS-06	3/30/2004	227.22	10.72	216.5		<50	<0.5	<0.5	<0.5	<0.5	<0.5 ****
RS-06	6/10/2004	227.22	13.52	213.7		<50	<0.5	<0.5	<0.5	<0.5	<0.5 ****
RS-06	9/28/2004	227.22	17.95	209.27		<50	<0.5	<0.5	<0.5	<0.5	<0.5 ****
RS-06	12/8/2004	227.22	14.80	212.42		<50	<0.5	<0.5	<0.5	<0.5	<0.5 ****
RS-06	3/23/2005	227.22	7.62	219.6		<50	<0.5	<0.5	<0.5	<0.5	<0.5 ****
RS-06	6/1/2005	227.22	10.72	216.5		<50	<0.5	<0.5	<0.5	<0.5	<0.5 ****
RS-06	9/21/2005	227.22	13.22	214		<50	1.5	<0.5	<0.5	<0.5	<0.5 ****
RS-06	12/7/2005	227.22	14.02	213.2		74	0.63	<0.5	<0.5	<0.5	<0.5 ****
RS-06	3/28/2006	227.22	6.03	221.19		<50	<0.5	<0.5	<0.5	<0.5	<0.5 ****
RS-06	6/21/2006	227.22	10.40	216.82		100	<0.5	<0.5	<0.5	<0.5	<0.5 ****
RS-06	9/13/2006	227.22	12.82	214.4		<50	<0.5	<0.5	<0.5	<0.5	<0.5 ****
RS-06	11/27/2006	well destroyed, Alameda County Public Works Permit #W2006-0973									
RS-07	12/14/1989	195.99									
RS-07	7/90	195.99				5600000	24000	21000	50000	740000	
RS-07	2/91	195.99			shhen						
RS-07	6/91	195.99			sheen						
RS-07	9/91	195.99			sheen						
RS-07	12/91	195.99				270000	11000	22000	2000	13000	
RS-07	11/9/1992	195.99	4.62	191.37		81000	12000	16000	1900	13000	

TABLE 1
GROUNDWATER ELEVATIONS AND CERTIFIED ANALYTICAL LABAORATAORY RESULTS FROM WATER SAMPLES
DESERT PETROLEUM, INC. SITE #793
4035 PARK BOULEVARD, OAKLAND, CALIFORNIA

ID#	DATE SAMPLED	(All concentrations in parts per billion [ug/L, ppb]) (AMSL = Above mean sea level)									
		WELL CASING ELEVATION (FEET AMSL)	DEPTH TO GROUND WATER (FEET)	GROUND WATER ELEVATION (FEET AMSL)	free phase prod. ft	TPH-G (UG/L)	BENZENE (UG/L) (1.5)	TOLUENE (UG/L) (150)	ETHYL-BENZENE (UG/L) (300)	XYLENES (UG/L) (1800)	MTBE (UG/L) (13)
(CALIFORNIA PUBLIC HEALTH GOAL)		195.99	4.03	191.96		74000	16000	16000	1400	8500	
RS-07	4/7/1994	195.99	4.03	191.96		74000	16000	16000	1400	8500	
RS-07	6/19/1994	195.99	4.07	191.92		83000	22000	19000	1500	9500	
RS-07	9/17/1994	195.99	4.05	191.94		270000	13000	15000	2100	1100	
RS-07	3/12/1995	195.99	3.72	192.27		35000	5100	560	6300	3600	
RS-07	10/4/1995	195.99	4.03	191.96		96000	14000	14000	1300	7000	
RS-07	12/21/95	195.99	3.95	192.04		70000	9300	12000	860	5600	210
RS-07	03/27/96	195.99	3.80	192.19		64000	8900	14000	1100	8300	< 3000
RS-07	06/11/96	195.99	3.79	192.2		65000	12000	17000	1600	9700	<5000
RS-07	09/04/96	195.99	3.99	192		20000	4900	2100	670	4400	100
RS-07	12/11/96	195.99	3.78	192.21		17000	4400	7500	570	4600	180
RS-07	2/21/97	195.99	3.82	192.17		93000	31000	47000	3800	23000	<0.5
RS-07	5/28/97	195.99	3.82	192.17		52000	12000	8200	2000	11000	<0.5
RS-07	9/2/1997	195.99	3.96	192.03		28000	6100	2800	950	3800	<50
RS-07	11/24/1997	195.99	3.76	192.23		18000	4300	5900	600	2900	<0.5
RS-07	2/25/1998	195.99	3.70	192.29		13000	4300	7100	1100	5800	<0.5
RS-07	7/8/1998	195.99	3.76	192.23		45000	10000	3400	2000	8000	<10
RS-07	7/30/1998	195.99				72000	12000	2100	2000	9100	
RS-07	9/16/1998	195.99	3.83	192.16		5000	6500	160	<2.5	500	<5
RS-07	11/24/1998	195.99	3.77	192.22		19000	2100	1100	500	2100	<0.5
RS-07	2/23/1999	195.99	3.70	192.29		83000	6500	9900	1200	7000	<10
RS-07	5/5/1999	195.99	3.88	192.11		47000	7400	4800	1300	7400	540
RS-07	8/26/1999	195.99	4.16	191.83		15000	3400	91	950	970	<5
RS-07	11/10/1999	195.99	4.12	191.87		10000	2900	170	630	1200	<0.5
RS-07	2/9/2000	195.99	3.98	192.01		9400	1400	120	480	600	<0.5
RS-07	6/30/2000	195.99	4.04	191.95		8200	3300	190	430	540	<0.5
RS-07	8/8/2000	195.99	4.06	191.93		11000	2300	150	430	520	<0.5
RS-07	11/16/2000	195.99	4.04	191.95		5400	1500	40	240	200	<0.5
RS-07	3/8/2001	195.99	3.94	192.05		12000	3300	260	480	850	17
RS-07	5/31/2001	195.99	4.01	191.98		10000	1900	120	320	620	<100
RS-07	12/18/2001	195.99	4.81	191.18		2700	450	21	86	120	2.3
RS-07	2/19/2002	195.99	3.91	192.08		20000	2600	360	570	1900	11
RS-07	5/7/2002	195.99	3.97	192.02		9200	1400	120	360	780	6.6
RS-07	8/6/2002	195.99	4.06	191.93		8300	1300	71	250	480	<10
RS-07	11/5/2002	195.99	4.11	191.88		9300	1500	90	330	680	<10
RS-07	12/12/2002	195.99	4.13	191.86							
RS-07	3/13/2003	195.99	4.02	191.97		5500	990	51	180	330	6.1
RS-07	5/6/2003	195.99	3.98	192.01		4800	740	36	160	310	4.7
RS-07	8/13/2003	195.99	4.09	191.9		9400	1300	65	310	620	6.1
RS-07	11/20/2003	195.99	4.10	191.89		4800	700	13	110	110	<5
RS-07	1/22/2004	195.99	4.12	191.87							
RS-07	3/30/2004	195.99	4.05	191.94		3800	540	33	140	210	3.4
RS-07	6/10/2004	195.99	4.12	191.87		4000	740	22	82	130	2.8
RS-07	9/28/2004	195.99	4.18	191.81		5000	640	20	110	130	2.8
RS-07	12/8/2004	195.99	3.92	192.07		3700	290	18	130	190	0.56
RS-07	3/23/2005	195.99	4.00	191.99		4600	220	17	100	170	2.4
RS-07	6/1/2005	195.99	4.11	191.88		4700	660	41	140	290	3.7
RS-07	9/21/2005	195.99	4.14	191.85		4600	360	18	67	130	3.6
RS-07	12/7/2005	195.99	4.13	191.86		3400	160	10	89	86	1.2
RS-07	3/28/2006	195.99	3.93	192.06		1400	170	10	30	49	1.5
RS-07	6/21/2006	195.99	4.11	191.88		4800	570	27	100	150	5.2
RS-07	9/13/2006	195.99	4.13	191.86		4700	570	15	70	73	6
RS-07	12/21/2006	195.99	4.08	191.91		1600	100	3.7	37	30	1.1
RS-07	3/12/2007	195.99	3.98	192.01		1500	220	3.7	40	35	2.6
RS-07	6/20/2007	195.99	4.10	191.89		3700	530	18	52	69	3.2
RS-07	9/26/2007	195.99	4.13	191.86		2300	240	5.1	30	22	2.9
RS-07	12/18/2007	195.99	3.83	192.16		1800	66	2.4	43	20	0.56
RS-07	3/12/2008	195.99	3.99	192		2300	190	5.4	63	39	1.9
RS-07	6/25/2008	195.99	4.13	191.86		3000	320	17	36	90	3.1
RS-07	9/17/2008	195.99	4.22	191.77		1400	38	2.2	40	12	<0.5
RS-07	12/17/2008	195.99	4.12	191.87		1700	76	3	73	21	<0.5
RS-07	3/31/2009	195.99	4.10	191.89		2400	190	3.6	96	27	2.5
RS-07	9/8/2009	195.99	4.18	191.81		2700	140	7.3	42	14	2
RS-07	3/24/2010	195.99	4.11	191.88		2100	130	5.8	66	14	1.6

TABLE 1
GROUNDWATER ELEVATIONS AND CERTIFIED ANALYTICAL LABAORATAORY RESULTS FROM WATER SAMPLES
DESERT PETROLEUM, INC. SITE #793
4035 PARK BOULEVARD, OAKLAND, CALIFORNIA

ID#	DATE SAMPLED	(All concentrations in parts per billion [ug/L, ppb]) (AMSL = Above mean sea level)									
		WELL CASING ELEVATION (FEET AMSL)	DEPTH TO GROUND WATER (FEET)	GROUND WATER ELEVATION (FEET AMSL)	free phase prod. ft	TPH-G (UG/L)	BENZENE (UG/L) (1.5)	TOLUENE (UG/L) (150)	ETHYL-BENZENE (UG/L) (300)	XYLENES (UG/L) (1800)	MTBE (UG/L) (13)
(CALIFORNIA PUBLIC HEALTH GOAL)											
RS-07	6/30/2010	195.99	4.08	191.91		no sample					
RS-07	9/16/2010	195.99	4.12	191.87		3500	490	9	56	12	3.5
RS-07	4/6/2011	195.99	4.12	191.87		2000	190	3.7	46	17	2.2
RS-07	6/29/2011	195.99	4.18	191.81		no sample					
RS-07	9/14/2011	195.99	4.30	191.69		460	0.76	<0.5	3.2	0.67	<0.5
RS-08	12/14/1989										
RS-08	09/04/96										
RS-08	12/11/96										
RS-08	2/21/97										
RS-08	5/28/97										
RS-08	9/2/1997										
RS-08	11/24/1997										
RS-08	2/25/1998										
RS-08	7/8/1998										
RS-08	9/16/1998										
RS-08	11/24/1998										
RS-08	2/23/1999										
RS-08	5/5/1999										
RS-08	8/26/1999	214.67	7.25	207.42		160000	24000	35000	4200	24000	<5
RS-08	11/10/1999	214.67	8.69	205.98		150000	21000	29000	3000	14000	<0.5
RS-08	2/9/2000	214.67	7.23	207.44		14000	1900	3200	270	2300	<0.5
RS-08	6/30/2000	214.67	3.99	210.68		6400	570	870	150	770	<0.5
RS-08	8/8/2000	214.67	7.52	207.15		100000	24000	40000	2300	9900	<0.5
RS-08	11/16/2000	214.67	6.14	208.53		110000	14000	21000	2100	9600	<20
RS-08	3/8/2001	214.67	9.40	205.27		10000	740	840	220	990	<2
RS-08	5/31/2001	214.67	6.83	207.84		730	11	29	4.2	31	<5
RS-08	12/18/2001	214.67	7.14	207.53		4500	230	370	77	750	<0.5
RS-08	2/19/2002	214.67	7.69	206.98		780	33	21	5.1	45	<0.5
RS-08	5/7/2002	214.67	7.82	206.85		24000	1500	1800	830	2700	<10
RS-08	8/6/2002	214.67	13.46	201.21	0.04						
RS-08	11/5/2002	214.67	13.96	200.71	0.40						
RS-08	12/12/2002	214.67	14.38	200.29	0.08						
RS-08	3/13/2003	214.67	10.99	203.68		90000	1100	14000	2500	12000	<50
RS-08	5/6/2003	214.67	5.35	209.32		1600	6.7	46	21	170	<0.5
RS-08	8/13/2003	214.67	11.96	202.71		100000	1200	10000	2500	13000	<50
RS-08	11/21/2003	214.67	12.30	202.37		100000	1700	10000	1700	12000	<25
RS-08	1/22/2004	214.67	9.63	205.04							
RS-08	3/30/2004	214.67	8.70	205.97		18000	69	110	130	1200	<5
RS-08	6/10/2004	214.67	10.65	204.02		33000	210	350	360	2300	<5
RS-08	9/28/2004	214.67	9.00	205.67		6000	59	20	100	170	<1
RS-08	12/8/2004	214.67	4.50	210.17		1100	<0.5	<0.5	<0.5	0.66	<0.5
RS-08	3/23/2005	214.67	3.65	211.02		<50	<0.5	<0.5	<0.5	<0.5	<0.5
RS-08	6/1/2005	214.67	9.70	204.97		4700	330	210	250	330	<0.5
RS-08	9/21/2005	214.67				could not locate, under landscaping.					
RS-08	12/7/2005	214.67	12.76	201.91		30000	1100	1500	810	2800	<5
RS-08	3/28/2006	214.67	3.42	211.25		<50	<0.5	<0.5	<0.5	<0.5	<0.5
RS-08	6/21/2006	214.67	7.03	207.64		6300	630	710	310	720	<0.5
RS-08	9/13/2006	214.67	11.13	203.54		29000	1600	2800	1300	4000	<2.5
RS-08	12/21/2006	214.67	10.67	204		60000	1900	2000	1300	5200	<7
RS-08	3/12/2007	214.67				dog in backyard, could not access well					
RS-08	6/20/2007	214.67	11.19	203.48		23000	480	540	780	2600	<2.5
RS-08	9/26/2007	214.67				dog in backyard, could not access well					
RS-08	12/18/2007	214.67				could not unlach side gate to enter backyard					
RS-08	3/12/2008	214.67	9.36	205.31		18000	81	41	51	560	<4
RS-08	6/25/2008	214.67	12.28	202.39		26000	480	870	430	2800	<4
RS-08	9/17/2008	214.67	12.13	202.54		30000	680	880	630	3400	<4
RS-08	12/17/2008	214.67				dogs in backyard, could not access well					
RS-08	3/31/2009	214.67				dogs in backyard, could not access well					
RS-08	9/8/2009	214.67				dogs in backyard, could not access well					
RS-08	3/24/2010	214.67	7.78	206.89		2500	48	3	26	130	<0.5
RS-08	6/30/2010	214.67				dogs in backyard, could not access well					
RS-08	9/16/2010	214.67	8.98	205.69		17000	260	140	240	1600	<0.5

TABLE 1
GROUNDWATER ELEVATIONS AND CERTIFIED ANALYTICAL LABAORATAORY RESULTS FROM WATER SAMPLES
DESERT PETROLEUM, INC. SITE #793
4035 PARK BOULEVARD, OAKLAND, CALIFORNIA

ID#	DATE SAMPLED	(All concentrations in parts per billion [ug/L, ppb]) (AMSL = Above mean sea level)										
		WELL CASING ELEVATION (FEET AMSL)	DEPTH TO GROUND WATER (FEET)	GROUND WATER ELEVATION (FEET AMSL)	free phase prod. ft	TPH-G (UG/L)	BENZENE (UG/L) (1.5)	TOLUENE (UG/L) (150)	ETHYL-BENZENE (UG/L) (300)	XYLENES (UG/L) (1800)	MTBE (UG/L) (13)	
(CALIFORNIA PUBLIC HEALTH GOAL)		214.67	3.63	211.04		570	29	0.58	<0.5	6.2	<0.5	****
RS-08	4/6/2011	214.67	3.63	211.04		570	29	0.58	<0.5	6.2	<0.5	****
RS-08	6/29/2011	214.67	10.20	204.47		no sample						
RS-08	9/14/2011	214.67	10.51	204.16		19000	130	60	86	1300	<0.5	****
RS-09	12/14/1989											
RS-09	09/04/96											
RS-09	12/11/96											
RS-09	2/21/97											
RS-09	5/28/97											
RS-09	9/2/1997											
RS-09	11/24/1997											
RS-09	2/25/1998											
RS-09	7/8/1998											
RS-09	9/16/1998											
RS-09	11/24/1998											
RS-09	2/23/1999											
RS-09	5/5/1999											
RS-09	8/26/1999	195.63	7.46	188.17		17000	3500	1200	360	1600	180	*
RS-09	11/10/1999	195.63	7.91	187.72		2800	520	62	46	130	<0.5	
RS-09	2/9/2000	195.63	6.09	189.54		3400	650	74	64	130	<0.5	
RS-09	6/30/2000	195.63	6.77	188.86		3000	600	79	74	120	<0.5	
RS-09	8/8/2000	195.63	7.32	188.31		4900	500	430	160	530	<0.5	
RS-09	11/16/2000	195.63	6.33	189.3		3000	350	220	90	220	<0.5	
RS-09	3/8/2001	195.63	4.93	190.7		<50	3.4	<0.5	<0.5	<0.5	<0.5	****
RS-09	5/31/2001	195.63	4.01	191.62		510	96	6	6.2	9.1	5.5	****
RS-09	12/18/2001	195.63	4.81	190.82		210	11	1.8	3.9	7.6	<0.5	****
RS-09	2/19/2002	195.63	4.99	190.64		<50	<0.5	<0.5	<0.5	<0.5	<0.5	****
RS-09	5/7/2002	195.63	6.08	189.55		130	7.9	<0.5	1.2	<0.5	0.67	****
RS-09	8/6/2002	195.63	6.93	188.7		380	29	1.2	2.3	2.9	3.1	****
RS-09	11/5/2002	195.63	7.53	188.1		1800	240	9	27	110	8.6	****
RS-09	12/12/2002	195.63	7.23	188.4								
RS-09	3/13/2003	195.63	5.73	189.9		410	30	3	6	9.5	3.3	****
RS-09	5/6/2003	195.63	4.83	190.8		910	72	15	9.2	26	5.5	****
RS-09	8/13/2003	195.63	8.24	187.39		810	20	<0.5	2.4	1.6	3.6	****
RS-09	11/20/2003	195.63	6.99	188.64		3600	920	5.3	6.1	20	30	****
RS-09	1/22/2004	195.63	5.43	190.2								
RS-09	3/30/2004	195.63	5.07	190.56		1900	360	9.3	19	48	21	****
RS-09	6/10/2004	195.63	6.18	189.45		950	180	3	8.4	14	8.7	****
RS-09	9/28/2004	195.63	6.94	188.69		4900	1800	5.9	5	16	31	****
RS-09	12/8/2004	195.63	4.42	191.21		74	<0.5	<0.5	<0.5	<0.5	<0.5	****
RS-09	3/23/2005	195.63	4.10	191.53		540	99	1.1	1.1	4.5	3.6	****
RS-09	6/1/2005	195.63	5.12	190.51		3300	170	14	77	87	12	****
RS-09	9/21/2005	195.63	6.60	189.03		330	1.2	<0.5	<0.5	0.58	1.8	****
RS-09	12/7/2005	195.63	5.92	189.71		88	<0.5	<0.5	<0.5	0.58	1.2	****
RS-09	3/28/2006	195.63	3.76	191.87		360	11	0.72	3.6	2.5	7.1	****
RS-09	6/21/2006	195.63	5.40	190.23		860	23	2.9	7.2	21	7.4	****
RS-09	9/13/2006	195.63	6.45	189.18		350	2.4	<0.5	1.1	4.2	2.9	****
RS-09	12/21/2006	195.63	5.82	189.81		85	<0.5	<0.5	<0.5	<0.5	0.81	****
RS-09	3/12/2007	195.63	5.08	190.55		1000	25	12	14	40	7.5	****
RS-09	6/20/2007	195.63	6.67	188.96		1300	130	4.4	6	20	7.2	****
RS-09	9/26/2007	195.63	7.45	188.18		1800	310	2.3	5	24	6.3	****
RS-09	12/18/2007	195.63	6.05	189.58		97	2.5	<0.5	0.56	1.4	0.51	****
RS-09	3/12/2008	195.63	5.43	190.2		82	1.6	<0.5	<0.5	<0.5	<0.5	****
RS-09	6/25/2008	195.63	7.03	188.6		2500	450	14	20	81	2.8	****
RS-09	9/17/2008	195.63	7.81	187.82		3100	830	4.9	7.7	37	4.7	****
RS-09	12/17/2008	195.63	6.87	188.76		51	1.7	<0.5	<0.5	<0.5	<0.5	****
RS-09	3/31/2009	195.63	5.64	189.99		72	1	<0.5	<0.5	<0.5	<0.5	****
RS-09	9/8/2009	195.63	7.45	188.18		2800	700	2.9	5.4	21	2.7	****
RS-09	3/24/2010	195.63	5.26	190.37		57	3.7	<0.5	<0.5	0.58	<0.5	****
RS-09	6/30/2010	195.63	6.17	189.46		no samples						
RS-09	9/16/2010	195.63	7.09	188.54		1800	410	2.5	3.5	17	1.6	****
RS-09	4/6/2011	195.63	4.72	190.91		6400	1900	6.6	20	83	4.3	****
RS-09	6/29/2011	195.63	7.00	188.63		no samples						

TABLE 1
GROUNDWATER ELEVATIONS AND CERTIFIED ANALYTICAL LABAORATAORY RESULTS FROM WATER SAMPLES
DESERT PETROLEUM, INC. SITE #793
4035 PARK BOULEVARD, OAKLAND, CALIFORNIA

ID#	DATE SAMPLED	(All concentrations in parts per billion [ug/L, ppb]) (AMSL = Above mean sea level)										
		WELL CASING ELEVATION (FEET AMSL)	DEPTH TO GROUND WATER (FEET)	GROUND WATER ELEVATION (FEET AMSL)	free phase prod. ft	TPH-G (UG/L)	BENZENE (UG/L) (1.5)	TOLUENE (UG/L) (150)	ETHYL-BENZENE (UG/L) (300)	XYLENES (UG/L) (1800)	MTBE (UG/L) (13)	
(CALIFORNIA PUBLIC HEALTH GOAL)		195.63	7.93	187.7		240	0.52	<0.5	<0.5	<0.5	1.2	****
RS-10	12/14/1989											
RS-10	09/04/96											
RS-10	12/11/96											
RS-10	2/21/97											
RS-10	5/28/97											
RS-10	9/2/1997											
RS-10	11/24/1997											
RS-10	2/25/1998											
RS-10	7/8/1998											
RS-10	9/16/1998											
RS-10	11/24/1998											
RS-10	2/23/1999											
RS-10	5/5/1999											
RS-10	8/26/1999	208.46	3.76	204.7		5100	160	340	190	1000	32	*
RS-10	11/10/1999	208.46	3.83	204.63		500	7	2	2	4	<0.5	
RS-10	2/9/2000	208.46	0.31	208.15		100	4	3	1	6	<0.5	
RS-10	6/30/2000	208.46	2.22	206.24		640	5	2	4	2	<0.5	
RS-10	8/8/2000	208.46	2.46	206		460	2	2	2	7	<0.5	
RS-10	11/16/2000	208.46	2.46	206		360	1	1	2	<1	<0.5	
RS-10	3/8/2001	208.46	2.82	205.64		53	<0.5	<0.5	<0.5	<0.5	<0.5	****
RS-10	5/31/2001	208.46	4.93	203.53		210	<0.5	<0.5	1.5	5	<5	****
RS-10	12/18/2001	208.46	2.10	206.36		<50	<0.5	<0.5	<0.5	<0.5	<0.5	****
RS-10	2/19/2002	208.46	2.29	206.17		<50	<0.5	<0.5	<0.5	<0.5	<0.5	****
RS-10	5/7/2002	208.46	2.92	205.54		<50	<0.5	<0.5	<0.5	<0.5	<0.5	****
RS-10	8/6/2002	208.46	4.11	204.35		<50	<0.5	0.7	<0.5	1.6	<0.5	****
RS-10	11/5/2002	208.46	4.05	204.41		54	<0.5	1.2	<0.5	1.1	<0.5	****
RS-10	12/12/2002	208.46	6.81	201.65								
RS-10	3/13/2003	208.46	3.00	205.46		<50	<0.5	<0.5	<0.5	<0.5	<0.5	****
RS-10	5/6/2003	208.46	2.55	205.91		<50	<0.5	<0.5	<0.5	<0.5	<0.5	****
RS-10	8/13/2003	208.46	3.68	204.78		<50	<0.5	<0.5	<0.5	<0.5	<0.5	****
RS-10	11/20/2003	208.46	4.45	204.01		<50	<0.5	<0.5	<0.5	<0.5	<0.5	****
RS-10	1/22/2004	208.46										
RS-10	3/30/2004	208.46	3.05	205.41		<50	<0.5	<0.5	<0.5	<0.5	<0.5	****
RS-10	6/10/2004	208.46	4.85	203.61		<50	<0.5	<0.5	<0.5	<0.5	<0.5	****
RS-10	9/28/2004	208.46	6.75	201.71		<50	4.6	<0.5	<0.5	<0.5	<0.5	****
RS-10	12/8/2004	208.46	1.74	206.72		<50	<0.5	<0.5	<0.5	<0.5	<0.5	****
RS-10	3/23/2005	208.46	1.85	206.61		<50	<0.5	<0.5	<0.5	<0.5	<0.5	****
RS-10	6/1/2005	208.46	2.88	205.58		<50	<0.5	<0.5	<0.5	<0.5	<0.5	****
RS-10	9/21/2005	208.46	4.35	204.11		<50	<0.5	<0.5	<0.5	<0.5	<0.5	****
RS-10	12/7/2005	208.46	3.38	205.08		<50	<0.5	<0.5	<0.5	<0.5	<0.5	****
RS-10	3/28/2006	208.46	1.75	206.71		<50	<0.5	<0.5	<0.5	<0.5	<0.5	****
RS-10	6/21/2006	208.46	2.91	205.55		350	110	0.73	2.8	1.9	<0.5	****
RS-10	9/13/2006	208.46	4.18	204.28		<50	0.86	<0.5	<0.5	<0.5	<0.5	****
RS-10	12/21/2006	208.46	2.78	205.68		<50	0.86	<0.5	<0.5	<0.5	<0.5	****
RS-10	3/12/2007	208.46	2.80	205.66		<50	<0.5	<0.5	<0.5	<0.5	<0.5	****
RS-10	6/20/2007	208.46	4.25	204.21		<50	<0.5	<0.5	<0.5	<0.5	<0.5	****
RS-10	9/26/2007	208.46	4.38	204.08		150	<0.5	<0.5	2.8	16	<0.5	****
RS-10	12/18/2007	208.46	4.38	204.08		220	<0.5	<0.5	0.64	8.4	<0.5	****
RS-10	3/12/2008	208.46	2.97	205.49		<50	<0.5	<0.5	<0.5	<0.5	<0.5	****
RS-10	6/25/2008	208.46	6.93	201.53		360	0.82	1.1	<0.5	1	<0.5	****
RS-10	9/17/2008	208.46	6.97	201.49		120	1.1	<0.5	0.78	<0.5	<0.5	****
RS-10	12/17/2008	208.46	3.72	204.74		<50	<0.5	<0.5	<0.5	<0.5	<0.5	****
RS-10	3/31/2009	208.46	3.05	205.41		<50	<0.5	<0.5	<0.5	<0.5	<0.5	****
RS-10	9/8/2009	208.46	7.80	200.66		77	5.6	<0.5	<0.5	<0.5	<0.5	****
RS-10	3/24/2010	208.46	2.92	205.54		<50	<0.5	<0.5	<0.5	<0.5	<0.5	****
RS-10	6/30/2010	208.46				no access						
RS-10	9/16/2010	208.46	5.78	202.68		53	4.4	3.6	0.8	1.4	<0.5	****
RS-10	4/6/2011	208.46	2.34	206.12		no sample						
RS-10	6/29/2011	208.46	2.40	206.06		no sample						
RS-10	9/14/2011	208.46	5.97	202.49		<50	<0.5	<0.5	<0.5	<0.5	<0.5	****

TABLE 1
GROUNDWATER ELEVATIONS AND CERTIFIED ANALYTICAL LABAORATAORY RESULTS FROM WATER SAMPLES
DESERT PETROLEUM, INC. SITE #793
4035 PARK BOULEVARD, OAKLAND, CALIFORNIA

ID#	DATE SAMPLED	(All concentrations in parts per billion [ug/L, ppb]) (AMSL = Above mean sea level)											
		WELL CASING ELEVATION (FEET AMSL)	DEPTH TO GROUND WATER (FEET)	GROUND WATER ELEVATION (FEET AMSL)	free phase prod. ft	TPH-G (UG/L)	BENZENE (UG/L) (1.5)	TOLUENE (UG/L) (150)	ETHYL-BENZENE (UG/L) (300)	XYLENES (UG/L) (1800)	MTBE (UG/L) (13)		
(CALIFORNIA PUBLIC HEALTH GOAL)													
R1	12/14/1989												
R1	09/04/96	227.69	15.00	212.69		1800	1100	3	29	< 10	< 30		
R1	12/11/96	227.69	10.30	217.39		<50	<0.5	< 0.5	< 0.5	< 1	4		
R1	2/21/97	227.69	11.88	215.81		2500	670	9	3	13	<0.5 *		
R1	5/28/97	227.69	14.03	213.66		24000	4300	36	2000	370	<0.5 *		
R1	9/2/1997	227.69	14.98	212.71		4400	320	6	340	72	20		
R1	11/24/1997	227.69	14.06	213.63		100	39	1	18	10	<0.5		
R1	2/25/1998	227.69	8.93	218.76		1200	400	8	13	150	<0.5		
R1	7/8/1998	227.69	11.36	216.33		68	14	< 0.5	< 0.5	< 1	<1 *		
R1	9/16/1998	227.69	13.30	214.39		16000	3400	92	< 0.5	410	<1 *		
R1	11/24/1998	227.69	10.72	216.97		340	19	1.6	35	9.7	<0.5		
R1	2/23/1999	227.69	9.34	218.35		60	16	0.6	5.6	1.2	<0.5		
R1	5/5/1999	227.69	11.30	216.39		1300	290	3	150	1	15		
R1	8/26/1999	227.69	13.97	213.72		6500	630	<0.5	1300	<1	<1		
R1	11/10/1999	227.69	13.73	213.96		480	12	4	22	9	<0.5		
R1	2/9/2000	227.69	13.10	214.59		<50	8	<0.5	1	<1	<0.5		
R1	6/30/2000	227.69	13.42	214.27		2600	350	35	1900	220	<0.5		
R1	8/8/2000	227.69	14.25	213.44		10000	910	76	2100	390	<0.5		
R1	3/8/2001	227.69	13.72	213.97		<50	<0.5	<0.5	<0.5	<0.5	<0.5 **		
R1	3/8/2001	227.69	13.72	213.97		<50	<0.5	<0.5	<0.5	<0.5	<0.5 ****		
R1	5/31/2001	227.69	15.77	211.92		3800	400	16	470	67	<5 ****		
R1	12/18/2001	227.69	9.90	217.79		<50	<0.5	<0.5	1.5	<0.5	<0.5 ****		
R1	2/19/2002	227.69	10.86	216.83		<50	<0.5	<0.5	<0.5	<0.5	<0.5 ****		
R1	5/7/2002	227.69	16.17	211.52		53	3.3	<0.5	1	<0.5	<0.5 ****		
R1	8/6/2002	227.69	16.83	210.86		<50	<0.5	<0.5	<0.5	<0.5	<0.5 ****		
R1	11/5/2002	227.69	16.92	210.77	dry, groundwater deeper than 210.77 foot elevation								
R1	12/12/2002	227.69	16.94	210.75									
R1	3/13/2003	227.69	15.69	212		<50	4.5	<0.5	<0.5	<0.5	<0.5 ****		
R1	5/6/2003	227.69	10.75	216.94		<50	<0.5	<0.5	<0.5	<0.5	<0.5 ****		
R1	8/13/2003	227.69	16.04	211.65		430	17	<0.5	1.4	1.1	<0.5 ****		
R1	11/20/2003	227.69		dry									
R1	1/22/2004	227.69	14.40	213.29									
R1	3/30/2004	227.69	14.05	213.64		<50	2.8	<0.5	<0.5	<0.5	<0.5 ****		
R1	6/10/2004	227.69	15.85	211.84		3200	85	2.6	38	8.3	<0.5 ****		
R1	9/28/2004	227.69	15.06	212.63		2000	35	2.2	12	4.4	<0.5 ****		
R1	12/8/2004	227.69	9.70	217.99		<50	<0.5	<0.5	<0.5	<0.5	<0.5 ****		
R1	3/23/2005	227.69	8.58	219.11		<50	<0.5	<0.5	<0.5	<0.5	<0.5 ****		
R1	6/1/2005	227.69	13.30	214.39		330	12	<0.5	1.6	1.4	<0.5 ****		
R1	9/21/2005	227.69	14.92	212.77		3400	20	1.3	13	4.4	<0.5 ****		
R1	12/7/2005	227.69	15.50	212.19		1100	4.2	0.65	1.5	0.94	<0.5 ****		
R1	3/28/2006	227.69	8.82	218.87		<50	<0.5	<0.5	<0.5	<0.5	<0.5 ****		
R1	6/21/2006	227.69	11.35	216.34		<50	<0.5	<0.5	<0.5	<0.5	<0.5 ****		
R1	9/13/2006	227.69	13.55	214.14		<50	<0.5	<0.5	<0.5	<0.5	<0.5 ****		
R1	12/21/2006	227.69	14.35	213.34		<50	<0.5	<0.5	<0.5	<0.5	<0.5 ****		
R1	3/12/2007	227.69	11.76	215.93		<50	<0.5	<0.5	<0.5	<0.5	<0.5 ****		
R1	6/20/2007	227.69	13.48	214.21		<50	<0.5	<0.5	<0.5	<0.5	<0.5 ****		
R1	9/26/2007	227.69	15.08	212.61		<50	<0.5	<0.5	<0.5	<0.5	<0.5 ****		
R1	12/18/2007	227.69	15.25	212.44		<50	<0.5	<0.5	<0.5	<0.5	<0.5 ****		
R1	3/12/2008	227.69	12.62	215.07		<50	<0.5	<0.5	<0.5	<0.5	<0.5 ****		
R1	6/25/2008	227.69	15.92	211.77		<50	<0.5	<0.5	<0.5	<0.5	<0.5 ****		
R1	9/17/2008	227.69			no sample water in shoe of casing, not representative								
R1	12/17/2008	227.69			no sample water in shoe of casing, not representative								
R1	3/31/2009	227.69	12.85	214.84		<50	<0.5	<0.5	<0.5	<0.5	<0.5 ****		
R1	9/8/2009	227.69	15.60	212.09		<50	<0.5	<0.5	<0.5	<0.5	<0.5 ****		
R1	3/24/2010	227.69	12.40	215.29		<50	<0.5	<0.5	<0.5	<0.5	<0.5 ****		
R1	6/30/2010	227.69	14.03	213.66		no samples							
R1	9/16/2010	227.69	14.56	213.13		<50	<0.5	<0.5	<0.5	<0.5	<0.5 ****		
R1	4/6/2011	227.69	9.90	217.79		<50	<0.5	<0.5	<0.5	<0.5	<0.5 ****		
R1	6/29/2011	227.69	14.52	213.17		no samples							
R1	9/14/2011	227.69	14.95	212.74		1900	3.5	0.63	3.2	1.7	<0.5 ****		
R2	12/14/1989												
R2	09/04/96	230.68	13.44	217.24		14000	7600	<10	170	190	<100		

TABLE 1
GROUNDWATER ELEVATIONS AND CERTIFIED ANALYTICAL LABAORATAORY RESULTS FROM WATER SAMPLES
DESERT PETROLEUM, INC. SITE #793
4035 PARK BOULEVARD, OAKLAND, CALIFORNIA

ID#	DATE SAMPLED	(All concentrations in parts per billion [ug/L, ppb]) (AMSL = Above mean sea level)									
		WELL CASING ELEVATION (FEET AMSL)	DEPTH TO GROUND WATER (FEET)	GROUND WATER ELEVATION (FEET AMSL)	free phase prod. ft	TPH-G (UG/L)	BENZENE (UG/L) (1.5)	TOLUENE (UG/L) (150)	ETHYL-BENZENE (UG/L) (300)	XYLENES (UG/L) (1800)	MTBE (UG/L) (13)
(CALIFORNIA PUBLIC HEALTH GOAL)											
R2	12/11/96	230.68	12.42	218.26		488	300	1	< 0.5	30	16
R2	2/21/97	230.68	10.50	220.18		5700	2100	5	2	10	3
R2	5/28/97	230.68	13.10	217.58		36000	14000	63	260	220	<0.5
R2	9/2/1997	230.68	14.16	216.52		30000	12000	330	1000	790	47
R2	11/24/1997	230.68	14.71	215.97		41000	15000	830	1500	4200	<0.5
R2	2/25/1998	230.68	7.39	223.29		800	400	<0.5	<0.5	15	<0.5
R2	7/8/1998	230.68	11.27	219.41		290	31	< 0.5	1	< 1	2
R2	9/16/1998	230.68	13.73	216.95		6600	11000	24	<0.5	35	<1
R2	11/24/1998	230.68	11.67	219.01		6100	<0.5	36	<0.5	21	<0.5
R2	2/23/1999	230.68	7.55	223.13		1100	310	3	2	26	<0.5
R2	5/5/1999	230.68	10.89	219.79		11000	5300	7	36	7	8
R2	8/26/1999	227.28	13.14	214.14		6700	940	33	190	240	<1
R2	11/10/1999	227.28	14.42	212.86		5100	2600	160	1800	8100	<0.5
R2	2/9/2000	227.28	12.45	214.83		4700	1400	110	130	340	<0.5
R2	6/30/2000	227.28	12.94	214.34		7100	3200	110	300	480	<0.5
R2	8/8/2000	227.28	13.58	213.7		30000	13000	250	1000	2700	<0.5
R2	11/16/2000	227.28	14.33	212.95		44000	17000	230	790	3600	<0.5
R2	3/8/2001	227.28	11.15	216.13		2300	640	8.6	61	170	<2
R2	5/31/2001	227.28	13.38	213.9		2200	580	12	72	100	<25
R2	12/18/2001	227.28	12.35	214.93		4900	2000	120	44	280	<5
R2	2/19/2002	227.28	11.32	215.96		2100	1200	<5	14	<5	<5
R2	5/7/2002	227.28	13.15	214.13		2500	660	7.5	170	26	<2.5
R2	8/6/2002	227.28	14.51	212.77		6300	1800	150	220	340	<5
R2	11/5/2002	227.28	15.46	211.82		11000	3000	140	57	620	<20
R2	12/12/2002	227.28	15.70	211.58							
R2	3/13/2003	227.28	12.96	214.32		580	200	1.2	5.4	3.8	<1
R2	5/6/2003	227.28	11.14	216.14		70	25	<0.5	<0.5	1.3	<0.5
R2	8/13/2003	227.28	14.01	213.27		1800	340	8	49	12	<2
R2	11/20/2003	227.28	15.35	211.93		8000	1400	46	57	490	<5
R2	1/22/2004	227.28	12.10	215.18							
R2	3/30/2004	227.28	11.48	215.8		<50	3	<0.5	<0.5	<0.5	<0.5
R2	6/10/2004	227.28	13.95	213.33		77	7.7	<0.5	<0.5	<0.5	<0.5
R2	9/28/2004	227.28	14.80	212.48		500	120	2	25	2.7	0.71
R2	12/8/2004	227.28	12.25	215.03		100	8.5	<0.5	<0.5	5	<0.5
R2	3/23/2005	227.28	7.82	219.46		57	8.4	<0.5	<0.5	<0.5	<0.5
R2	6/1/2005	227.28	12.14	215.14		85	5.2	<0.5	<0.5	<0.5	<0.5
R2	9/21/2005	227.28	13.97	213.31		900	120	1.3	2.5	4.8	<0.5
R2	12/7/2005	227.28	14.51	212.77		150	8.4	<0.5	<0.5	0.5	<0.5
R2	3/28/2006	227.28	7.30	219.98		<50	7.7	<0.5	<0.5	<0.5	<0.5
R2	6/21/2006	227.28	11.90	215.38		68	4.7	<0.5	<0.5	<0.5	<0.5
R2	9/13/2006	227.28	13.66	213.62		54	0.52	<0.5	<0.5	<0.5	<0.5
R2	12/21/2006	227.28	14.43	212.85		<50	<0.5	<0.5	<0.5	<0.5	<0.5
R2	3/12/2007	227.28	12.37	214.91		210	63	<0.5	1.8	<0.5	<0.5
R2	6/20/2007	227.28	14.08	213.2		1300	250	3.6	2.7	4.1	<0.5
R2	9/26/2007	227.28	15.41	211.87		230	28	<0.5	<0.5	2.5	<0.5
R2	12/18/2007	227.28	15.87	211.41		98	<0.5	<0.5	<0.5	2.5	<0.5
R2	3/12/2008	227.28	11.45	215.83		<50	0.59	<0.5	<0.5	<0.5	<0.5
R2	6/25/2008	227.28	14.98	212.3		79	11	<0.5	<0.5	<0.5	<0.5
R2	9/17/2008	227.28	16.03	211.25		87	1.8	<0.5	5.6	0.92	<0.5
R2	12/17/2008	227.28				no sample water in shoe of casing, not representative					
R2	3/31/2009	227.28	11.42	215.86		<50	5.5	<0.5	<0.5	<0.5	<0.5
R2	9/8/2009	227.28	15.50	211.78		56	<0.5	<0.5	<0.5	<0.5	<0.5
R2	3/24/2010	227.28	11.10	216.18		140	16	<0.5	<0.5	<0.5	<0.5
R2	6/30/2010	227.28	13.30	213.98		no samples					
R2	9/16/2010	227.28	14.28	213		54	0.68	<0.5	<0.5	<0.5	<0.5
R2	4/6/2011	227.28	9.15	218.13		170	16	<0.5	<0.5	<0.5	<0.5
R2	6/29/2011	227.28	13.12	214.16		no samples					
R2	9/14/2011	227.28	14.15	213.13		1900	130	4.9	11	5.4	<0.5
R3	12/14/1989										
R3	09/04/96	230.32	9.90	220.42		<50	<0.5	<0.5	<0.5	<2	<5
R3	12/11/96	230.32	8.18	222.14		<50	<0.5	<0.5	<0.5	<1	5
R3	2/21/97	230.32	6.76	223.56		340	35	59	8	54	<0.5

TABLE 1
GROUNDWATER ELEVATIONS AND CERTIFIED ANALYTICAL LABAORATAORY RESULTS FROM WATER SAMPLES
DESERT PETROLEUM, INC. SITE #793
4035 PARK BOULEVARD, OAKLAND, CALIFORNIA

ID#	DATE SAMPLED	(All concentrations in parts per billion [ug/L, ppb]) (AMSL = Above mean sea level)									
		WELL CASING ELEVATION (FEET AMSL)	DEPTH TO GROUND WATER (FEET)	GROUND WATER ELEVATION (FEET AMSL)	free phase prod. ft	TPH-G (UG/L)	BENZENE (UG/L) (1.5)	TOLUENE (UG/L) (150)	ETHYL-BENZENE (UG/L) (300)	XYLENES (UG/L) (1800)	MTBE (UG/L) (13)
(CALIFORNIA PUBLIC HEALTH GOAL)		195.11									
T 1	11/24/1997										
T 1	2/25/1998										
T 1	7/8/1998										
T 1	9/16/1998										
T 1	11/24/1998										
T 1	2/23/1999										
T 1	5/5/1999										
T 1	8/26/1999	195.11	2.44	192.67		40000	7200	5000	950	8100	53 *
T 1	11/10/1999	195.11	2.23	192.88		46000	5600	3600	910	6500	<0.5
T 1	2/9/2000	195.11	2.22	192.89		35000	2900	5700	720	6600	<0.5
T 1	6/30/2000	195.11	2.22	192.89		30000	3400	3200	950	4600	<5
T 1	8/8/2000	195.11	2.73	192.38		8900	1600	760	260	870	<5
T 1	11/16/2000	195.11	2.72	192.39		4000	1300	92	80	290	<0.5
T 1	3/8/2001	195.11	2.12	192.99		25000	4400	3400	770	3200	26 ****
T 1	5/31/2001	195.11	2.30	192.81		8900	940	210	340	1500	<50 ****
T 1	12/18/2001	195.11	2.20	192.91		48000	3700	5500	1200	5300	24 ****
T 1	2/19/2002	195.11	1.96	193.15		64000	8600	6000	1700	6800	55 ****
T 1	5/7/2002	195.11	2.22	192.89		41000	9200	910	2000	6200	62 ****
T 1	8/6/2002	195.11	2.32	192.79		28000	5500	240	1300	2600	32 ****
T 1	11/5/2002	195.11	2.52	192.59		11000	3000	65	660	610	18 ****
T 1	12/12/2002	195.11	2.55	192.56							
T 1	3/13/2003	195.11	2.23	192.88		930	150	17	23	60	2.6 ****
T 1	5/6/2003	195.11	2.37	192.74		6800	1000	230	310	820	10 ****
T 1	8/13/2003	195.11	2.41	192.7		9600	1500	110	440	910	10 ****
T 1	11/20/2003	195.11	2.50	192.61		10000	1800	120	520	510	11 ****
T 1	1/22/2004	195.11									
T 1	3/30/2004	195.11				15000	1800	660	610	2000	8.6 ****
T 1	6/10/2004	195.11	2.40	192.71		5500	570	2	240	130	2.7 ****
T 1	9/28/2004	195.11	2.52	192.59		8700	2600	100	450	15	15 ****
T 1	12/8/2004	195.11	1.96	193.15		2900	820	32	14	47	6.9 ****
T 1	3/23/2005	195.11	car			2800	220	3	120	76	1.7 ****
T 1	6/1/2005	195.11	2.25	192.86		46000	14000	650	1900	2900	54 ****
T 1	9/21/2005	195.11	2.42	192.69		17000	4500	81	620	200	28 ****
T 1	12/7/2005	195.11	2.26	192.85		18000	4000	480	780	1100	25 ****
T 1	3/28/2006	195.11	car			27000	4400	1600	890	2700	20 ****
T 1	6/21/2006	195.11	2.48	192.63		14000	5200	310	270	680	19 ****
T 1	9/13/2006	195.11	2.43	192.68		12000	5100	88	230	320	22 ****
T 1	12/21/2006	195.11	2.28	192.83		18000	4600	620	850	2000	21 ****
T 1	3/12/2007	195.11	2.24	192.87		19000	4700	750	870	2300	16 ****
T 1	6/20/2007	195.11	2.47	192.64		12000	4300	130	170	250	18 ****
T 1	9/26/2007	195.11	2.52	192.59		10000	4200	63	45	68	14 ****
T 1	12/18/2007	195.11	1.75	193.36		12000	3000	450	360	480	15 ****
T 1	3/12/2008	195.11	2.23	192.88		22000	6600	1200	960	2300	25 ****
T 1	6/25/2008	195.11	2.55	192.56		13000	5200	160	300	280	18 ****
T 1	9/17/2008	195.11	3.12	191.99		8600	3400	47	29	81	9.4 ****
T 1	12/17/2008	195.11	2.32	192.79		5600	1500	130	140	310	4.9 ****
T 1	3/31/2009	195.11	2.32	192.79		24000	5800	830	1300	3700	16 ****
T 1	9/8/2009	195.11	2.90	192.21		7900	2700	57	50	180	7.8 ****
T 1	3/24/2010	195.11	2.25	192.86		22000	5800	640	1200	2500	18 ****
T 1	6/30/2010	195.11				no access, parked cars					
T 1	9/16/2010	195.11	2.34	192.77		13000	5100	58	110	110	<15 ****
T 1	4/6/2011	195.11	2.00	193.11		41000	12000	3000	1200	3300	30 ****
T 1	6/29/2011	195.11	8.08	187.03		3500	500	300	65	520	2.8 ****
T 1	9/14/2011	195.11	12.00	183.11		1200	10	5.7	8.6	85	<0.5 ****
T 2	1/22/2004	195.3	2.54	192.76		see T1 for sample results					
T 2	3/30/2004	195.3	2.50	192.8		see T1 for sample results					
T 2	6/10/2004	195.3	2.60	192.7		see T1 for sample results					
T 2	9/28/2004	195.3	car			see T1 for sample results					
T 2	12/8/2004	195.3	2.04	193.26		see T1 for sample results					
T 2	3/23/2005	195.3	car			see T1 for sample results					
T 2	6/1/2005	195.3	car			see T1 for sample results					
T 2	9/21/2005	195.3	car			see T1 for sample results					

TABLE 1
GROUNDWATER ELEVATIONS AND CERTIFIED ANALYTICAL LABAORATAORY RESULTS FROM WATER SAMPLES
DESERT PETROLEUM, INC. SITE #793
4035 PARK BOULEVARD, OAKLAND, CALIFORNIA

ID#	(All concentrations in parts per billion [ug/L, ppb]) (AMSL = Above mean sea level)										
	DATE SAMPLED	WELL CASING ELEVATION (FEET AMSL)	DEPTH TO GROUND WATER (FEET)	GROUND WATER ELEVATION (FEET AMSL)	free phase prod. ft	TPH-G (UG/L)	BENZENE (UG/L) (1.5)	TOLUENE (UG/L) (150)	ETHYL-BENZENE (UG/L) (300)	XYLENES (UG/L) (1800)	MTBE (UG/L) (13)
(CALIFORNIA PUBLIC HEALTH GOAL)											
T2	12/7/2005	195.3	car			see T1 for sample results					
T2	3/28/2006	195.3	2.00	193.3		see T1 for sample results					
T2	6/21/2006	195.3	car			see T1 for sample results					
T2	9/13/2006	195.3	car			see T1 for sample results					
T2	12/21/2006	195.3	car			see T1 for sample results					
T2	3/12/2007	195.3	car			see T1 for sample results					
T2	6/20/2007	195.3	car			see T1 for sample results					
T2	9/26/2007	195.3	car			see T1 for sample results					
T2	12/18/2007	195.3	car			see T1 for sample results					
T2	3/12/2008	195.3	car			see T1 for sample results					
T2	6/25/2008	195.3	car			see T1 for sample results					
T2	9/17/2008	195.3	car			see T1 for sample results					
T2	12/17/2008	195.3	car			see T1 for sample results					
T2	3/31/2009	195.3	car			see T1 for sample results					
T2	9/8/2009	195.3	car			see T1 for sample results					
T2	3/24/2010	195.3	car			see T1 for sample results					
T2	6/30/2010	195.3	car								
T2	9/16/2010	195.3	car								
T2	6/29/2011	195.3	8.18	187.12		see T1 for sample results					
T2	9/14/2011	195.3	10.97	184.33		see T1 for sample results					
T3	1/22/2004	202.38				see T1 for sample results					
T3	6/10/2004	202.38	9.80	192.58		see T1 for sample results					
T3	9/28/2004	202.38	9.90	192.48		see T1 for sample results					
T3	12/8/2004	202.38	9.24	193.14		see T1 for sample results					
T3	3/23/2005	202.38	car			see T1 for sample results					
T3	6/1/2005	202.38	car			see T1 for sample results					
T3	9/21/2005	202.38	car			see T1 for sample results					
T3	12/7/2005	202.38	car			see T1 for sample results					
T3	3/28/2006	202.38	car			see T1 for sample results					
T3	6/21/2006	202.38	car			see T1 for sample results					
T3	9/13/2006	202.38	car			see T1 for sample results					
T3	12/21/2006	202.38	car			see T1 for sample results					
T3	3/12/2007	202.38	car			see T1 for sample results					
T3	6/20/2007	202.38	car			see T1 for sample results					
T3	9/26/2007	202.38	car			see T1 for sample results					
T3	12/18/2007	202.38	car			see T1 for sample results					
T3	3/12/2008	202.38	car			see T1 for sample results					
T3	6/25/2008	202.38	car			see T1 for sample results					
T3	9/17/2008	202.38	car			see T1 for sample results					
T3	12/17/2008	202.38	car			see T1 for sample results					
T3	3/31/2009	202.38	car			see T1 for sample results					
T3	9/8/2009	202.38	car			see T1 for sample results					
T3	3/24/2010	202.38	car			see T1 for sample results					
T3	6/30/2010	202.38	car								
T3	9/16/2010	202.38	car			see T1 for sample results					
T3	6/29/2011	202.38	11.20	191.18		see T1 for sample results					
T3	9/14/2011	202.38	11.37	191.01		see T1 for sample results					
T4	1/22/2004	197.48	4.70	192.78		see T1 for sample results					
T4	3/30/2004	197.48	4.66	192.82		see T1 for sample results					
T4	6/10/2004	197.48	4.76	192.72		see T1 for sample results					
T4	9/28/2004	197.48	4.86	192.62		see T1 for sample results					
T4	12/8/2004	197.48	4.21	193.27		see T1 for sample results					
T4	3/23/2005	197.48	4.35	193.13		see T1 for sample results					
T4	6/1/2005	197.48	car			see T1 for sample results					
T4	9/21/2005	197.48	car			see T1 for sample results					
T4	12/7/2005	197.48	car			see T1 for sample results					
T4	3/28/2006	197.48	car			see T1 for sample results					
T4	6/21/2006	197.48	car			see T1 for sample results					
T4	9/13/2006	197.48	car			see T1 for sample results					
T4	12/21/2006	197.48	car			see T1 for sample results					
T4	3/12/2007	197.48	car			see T1 for sample results					

TABLE 1
GROUNDWATER ELEVATIONS AND CERTIFIED ANALYTICAL LABAORATAORY RESULTS FROM WATER SAMPLES
DESERT PETROLEUM, INC. SITE #793
4035 PARK BOULEVARD, OAKLAND, CALIFORNIA

ID#	(All concentrations in parts per billion [ug/L, ppb]) (AMSL = Above mean sea level)										
	DATE SAMPLED	WELL CASING ELEVATION (FEET AMSL)	DEPTH TO GROUND WATER (FEET)	GROUND WATER ELEVATION (FEET AMSL)	free phase prod. ft	TPH-G (UG/L)	BENZENE (UG/L) (1.5)	TOLUENE (UG/L) (150)	ETHYL-BENZENE (UG/L) (300)	XYLENES (UG/L) (1800)	MTBE (UG/L) (13)
(CALIFORNIA PUBLIC HEALTH GOAL)											
T4	6/20/2007	197.48	car			see T1 for sample results					
T4	9/26/2007	197.48	car			see T1 for sample results					
T4	12/18/2007	197.48	car			see T1 for sample results					
T4	3/12/2008	197.48	car			see T1 for sample results					
T4	6/25/2008	197.48	car			see T1 for sample results					
T4	9/17/2008	197.48	car			see T1 for sample results					
T4	12/17/2008	197.48	car			see T1 for sample results					
T4	3/31/2009	197.48	car			see T1 for sample results					
T4	9/8/2009	197.48	car			see T1 for sample results					
T4	3/24/2010	197.48	car			see T1 for sample results					
T4	6/30/2010	197.48	car			see T1 for sample results					
T4	9/16/2010	197.48	car			see T1 for sample results					
T4	6/29/2011	197.48	car			see T1 for sample results					
T4	9/14/2011	197.48	car			see T1 for sample results					
LF 1	1/22/2004	226.59	29.12	197.47							
LF 1	3/30/2004	226.59	26.45	200.14		<50	<0.5	<0.5	<0.5	<0.5	<0.5
LF 1	6/10/2004	226.59	27.57	199.02		<50	<0.5	<0.5	<0.5	<0.5	<0.5
LF 1	9/28/2004	226.59	28.72	197.87		<50	<0.5	<0.5	<0.5	<0.5	<0.5
LF 1	12/8/2004	226.59	car								
LF 1	3/23/2005	226.59	car								
LF 1	6/1/2005	226.59	car								
LF 1	9/21/2005	226.59	car								
LF 1	12/7/2005	226.59	26.67	199.92		<50	<0.5	<0.5	<0.5	<0.5	<0.5
LF 1	3/28/2006	226.59	25.25	201.34		<50	<0.5	<0.5	<0.5	<0.5	<0.5
LF 1	6/21/2006	226.59	23.05	203.54		<50	<0.5	<0.5	<0.5	<0.5	<0.5
LF 1	9/13/2006	226.59	29.23	197.36		<50	<0.5	<0.5	<0.5	<0.5	<0.5
LF 1	12/21/2006	226.59	32.12	194.47		<50	<0.5	<0.5	<0.5	<0.5	<0.5
LF 1	3/12/2007	226.59	31.47	195.12		<50	<0.5	<0.5	<0.5	<0.5	<0.5
LF 1	6/20/2007	226.59	32.72	193.87		<50	<0.5	<0.5	<0.5	<0.5	<0.5
LF 1	9/26/2007	226.59	31.82	194.77		<50	<0.5	<0.5	<0.5	<0.5	<0.5
LF 1	12/18/2007	226.59			car						
LF 1	3/12/2008	226.59	32.06	194.53		<50	<0.5	<0.5	<0.5	<0.5	<0.5
LF 1	6/25/2008	226.59			well is no longer there						

ND BELOW LABORATORY DETECTION LIMITS
TPH-G TOTAL PETROLEUM HYDROCARBONS AS GASOLINE
* MTBE results confirmed by EPA Method 8260 (GC/MS)
** LAB REPORT HAD RS-6 AND RS-7 MISLABELED, RESAMPLE ON 7/30/98 CONFIRMED.
WELL CASING ELEVATION SURVEY 8-27-99, WADE HAMMOND No.6163, BENCH MARK CITY OF OAKLAND #2814
**** SAMPLES ANALYZED USING EPA METHOD 8260B

TABLE 2
GROUNDWATER REMOVAL
FORMER DP #793
4035 PARK BLVD., OAKLAND, CALIFORNIA

Date	Meter Reading in Gallons RS5	Meter Reading in Gallons T1	Depth to top water in feet T1	Depth to top water in feet RS05	Gallons Purged T1 and/or 1/4ly samples	Accumulated gallons removed from T1 & wells in Gallons	Accumulated gallons removed from RS5 Gallons	Total Gallons Removed wells	pump rate gallons/minute RS5/EX	pump rate gallons/minute T1/T2	INFLUENT CONCENTRATIONS EPA METHOD 8020 - 8260B						Sample Location	Date Sampled
											TPHg ug/L	BENZENE ug/L	TOLUENE ug/L	ETHYL-BENZENE ug/L	XYLENES ug/L	MTBE ug/L		
6/30/2010	2808417.9	2808417.9			0	93553	1621019.3	1714572.1			280	6.3	1.1	<0.5	19	<0.5	RS-5	
6/30/2010	turn system on to obtain samples, then turn system off, remove pump and pump controller. suspend sewer discharge																	
9/16/2010	2808417.9	2808448.5			31	93583	1621019.3	1714602.7			discharged purged monitor well water through carbon to sewer							
9/16/2010	2808417.9	2808448.5			31	93614	1620988.7	1714602.7										
New discharge permit with continuous pumping T1 and RS5/excavation well																		
	meter# 52122813.0	meter # 52122836.0																
3/30/2011	1.0	1.0			0	93614	1620988.7	1714602.7			connected pumps, carbons and filters, no pumping, start-up 4/6/2011							
4/6/2011	4.8	137.0	2	12.62	65	93815	1620992.5	1714807.3	0.0	0.0	41000	12000	3000	1200	3300	30	T1	4/6/2011
4/10/2011	6146.2	7063.8				100742	1627133.9	1727875.5	1.1	1.2	4800	100	31	200	370	<0.9	RS5	4/6/2011
4/13/2011	6171.5	7135.0				100813	1627159.2	1727972.0	0.0	0.0	restart system							
4/20/2011	12537.0	16587.5				110265	1633524.7	1743790.0	0.6	0.9								
4/27/2011	21394.0	24802.0	11	28.7		118480	1642381.7	1760861.5	0.9	0.8								
5/4/2011	29362.0	31025.0	10.96	22.9		124703	1650349.7	1775052.5	0.8	0.6								
5/12/2011	37504.0	36838.0	10.98	29.4		130516	1658491.7	1789007.5	0.7	0.5								
5/19/2011	44813.0	36848.0	3.4	27.2		130526	1665800.7	1796326.5	0.7	0.0	increase pumpage from T1							
5/26/2011	49334.0	45685.0	11	20.12		139363	1670321.7	1809684.5	0.4	0.9								
6/8/2011	56383.0	56453.0	7.5	18.95		150131	1677370.7	1827501.5	0.4	0.6								
6/22/2011	66933.0	66344.5	8.7	21		160022	1687920.7	1847943.0	0.5	0.5	3500	500	300	65	520	2.8	T1	6/29/2011
6/29/2011	70928.5	71396.5	8.08	20.22		165074	1691916.2	1856990.5	0.4	0.5	1600	99	55	11	130	1.3	RS5	6/29/2011
7/14/2011	77761.0	81449.0	10.92	18.5		175127	1698748.7	1873875.5	0.3	0.5								
7/28/2011	84613.0	88197.0	12.5	21.75		181875	1705600.7	1887475.5	0.3	0.3								
8/10/2011	88284.0	94011.5	10.3	17.85		187689	1709271.7	1896961.0	0.2	0.3								
8/24/2011	92163.0	100769.0	10.3	17.85		194447	1713150.7	1907597.5	0.2	0.3	electrical power off to compound, call PG&E							
8/31/2011	92163.0	100769.0	4.97	16.1		194447	1713150.7	1907597.5	0.0	0.0	turn pumps back on after power restored.							
9/8/2011	94360.0	106875.0	10.96	32.7		200553	1715347.7	1915900.5	0.2	0.5								
9/14/2011	96014.0	109744.0	4.97	16.1	25	203447	1717001.7	1920448.2	0.2	0.3	1200	10	5.7	8.6	85	<0.5	T1	9/14/2011
9/23/2011	98327.5	113700.0	11.4	19		207403	1719315.2	1926717.7	0.2	0.3	1200	7.6	4.7	6.6	74	<0.5	RS5	9/14/2011

ug/L micrograms per liter (parts per billion) < BELOW LABORATORY LOWER DETECTION LIMITS * SAMPLED ON AUGUST 26, 1999
 mg/Kg milligrams per kilogram (parts per million) T1 Receptor Trench Well

TABLE 2
GROUNDWATER REMOVAL
FORMER DP #793
4035 PARK BLVD., OAKLAND, CALIFORNIA

Date	Meter Reading in Gallons RS5	Meter Reading in Gallons T1	Depth to top water in feet T1	Depth to top water in feet RS05	Gallons Purged T1 and/or 1/4ly samples	Accumulated gallons removed from T1 & wells in Gallons	Accumulated gallons removed from RS5 Gallons	Total Gallons Removed wells	pump rate gallons/minute RS5/EX	pump rate gallons/minute T1/T2	INFLUENT CONCENTRATIONS EPA METHOD 8020 - 8260B						Sample Location	Date Sampled
											TPHg ug/L	BENZENE ug/L	TOLUENE ug/L	ETHYL-BENZENE ug/L	XYLENES ug/L	MTBE ug/L		

mg/L milligrams per liter (parts per million)
WESTERN GEO-ENGINEERS

0 | _____ |
TPHg TOTAL PETROLEUM HYDROCARBONS GASOLINE RANGE
MTBE METHYL TERTIARY BUTYL ETHER

RS5 Monitor Well RS5 (pumping well)

Desert Petroleum DP 793
4035 Park Blvd., Oakland, CA

TABLE 3
CARBON INFLUENT (TPHg removed)

Date	Time	Meter Reading	Gallons Discharged Between Readings	Gallons pumped other sources	Cumulative Gallons pumped	Method 8260								
						TPHg mg/L	TPHg REMOVED gallons	TPHg accumulative gallons	Benzene ug/L	Toluene ug/L	Ethyl-benzene ug/L	Xylenes ug/L	MtBE ug/L	
6/20/2007	12.00	2340026.5	53507	51	1147987.5	0.16	0.16	13.06	7.5	3	2.2	13	0.058	
9/26/2007	12.00	2390013.5	49987	63	1197974.5	2.3	0.22	13.28	80	57	19	350	0.059	
12/18/2007	12.00	2412728.5	22715	13	1220689.5	0.57	0.01	13.29	15	6.8	7.8	42	<0.5	
3/12/2008	12.00	2424303.0	11574.5	0	1232264	4.6	0.05	13.34	330	110	98	440	1.9	
6/25/2008	12.00	2488868.5	64565.5	85	1296829.5	0.074	0.03	13.37	3.7	<0.5	0.05	2	0.7	
9/5/2008	12.00	2524336.5	35468	0	1332297.5	0.28	0.12	13.48	4.4	1.5	0.55	18	<0.5	
12/17/2008	12.00	2560523.5	36187	0	1368484.5	0.45	0.01	13.50	2.3	1.2	1.8	13	<0.5	
3/31/2009	12.00	2606106.5	45583	51	1414067.5	0.8	0.03	13.53	120	14	2	54	2.7	
9/8/2009	12.00	2662647.5	56541	24	1470608.5	1.1	0.06	13.59	6.3	1	3.9	24	1.4	
3/24/2010	12.00	2768886.5	106239	55	1576847.5	1.7	0.18	13.77	200	29	10	110	2.6	
6/30/2010	12.00	2808417.9	39531.4	0	1616378.9	0.28	0.04	13.80	6.3	1.1	<0.5	19	<0.5	
9/16/2010	12.00	2808417.9	0	0	1616378.9	8.4	0.00	13.80	110	31	180	640	<0.5	
New meter for RS5														
52122813.0														
3/30/2011		1.0			1616378.9			13.80						
4/6/2011		4.8	3.8		1616382.7	4.8	0.00	13.80	100	31	200	370	<0.9	
6/29/2011		70928.5	70923.7		1687306.4	1.6	0.08	13.88	99	55	11	130	1.3	
9/14/2011		96014.0	25085.5		1712391.9	1.2	0.10	13.98	7.6	4.7	6.6	74	<0.5	
New meter for T1/T2														
52122836.0														
gallons pump T1/T2														
3/30/2011		1.0			0									
4/6/2011		4.8	3.8		3.8	41	0.00	0.00	12000	3000	1200	3300	30	
6/29/2011		71396.5	71391.7		71395.5	3.5	0.17	0.17	500	300	65	520	2.8	
9/14/2011		109744.0	38347.5		109743	1.2	1.08	1.25	10	5.7	8.6	85	<0.5	

< LESS THAN LABORATORY LOWER DETECTION LIMITS





FIGURE 1
 GEOTRACKER
 AREA WELL & LUST MAP
 DP 793
 4035 PARK BLVD.
 OAKLAND, CA

- LUST SITES
- WELLS





FIGURE 2
PORTION OF OAKLAND EAST 7.5 MINUTE USGS TOPOGRAPHIC MAP





- 10 SPS SAMPLE POINT
 - SOIL SAMPLE POINT
 - SOIL BORING
 - ⋮ RECEPTOR TRENCH SAMPLE POINT
 - RS9 GROUNDWATER MONITORING WELL
 - RS1 DESTROYED MONITORING WELL
 - ⊗ 3968-1 HAND AUGER SOIL/GROUNDWATER SAMPLE POINTS (11/27/2006)
- 0' 20' 50'
- SCALE: 1 INCH=50 FEET

FIGURE 3-SAMPLE LOCATIONS INVESTIGATION FOR DP793, 4035 PARK BLVD. OAKLAND, CALIFORNIA (revised 4/5/2011)



ST ST G

CONVEYANCE PIPE PARK BLVD.

HAMPEL AVENUE

BRIGHTON AVENUE

4000 GREENWOOD

4008 GREENWOOD

1201 HAMPEL AVE.

1205 HAMPEL AVE.

3984 Greenwood

3992
3990
Greenwood

3976 Greenwood

3968 Greenwood

3960 Greenwood

3956 Greenwood

4038 BRIGHTON AVE.

1211 HAMPEL AVE.

4031 BRIGHTON AVE.

4032 BRIGHTON AVE.

1215 HAMPEL AVE.

4026 BRIGHTON AVE.

1221 HAMPEL AVE.

4010/4012 BRIGHTON AVE.

1227 HAMPEL AVE.
Rick Campbell
510-834-8610

4006 BRIGHTON AVE.
Georgena King
415-939-4150

4003 PARK BLVD.

4035 PARK BLVD.

GARAGE

GARAGE

GARAGE

GARAGE

GARAGE

GARAGE

GARAGE

GARAGE

GARAGE

GARAGE

GARAGE

GARAGE

GARAGE

GARAGE

GARAGE

GARAGE

GARAGE

GARAGE

GARAGE

GARAGE

GARAGE

GARAGE

GARAGE

GARAGE

GARAGE

GARAGE

GARAGE

GARAGE

GARAGE

GARAGE

GARAGE


GARAGE

GARAGE

GARAGE

GARAGE

GARAGE



RS9 ● GROUNDWATER MONITORING WELL
 RS1 ● DESTROYED MONITORING WELL
 3968-1 ⊗ HAND AUGER SOIL/GROUNDWATER SAMPLE POINTS (11/27/2006)
 0' 20' 50'
 SCALE: 1 INCH=50 FEET

FIGURE 4A
GROUNDWATER ELEVATIONS
DP793, 4035 PARK BLVD.
OAKLAND, CALIFORNIA
(08/10/2011)



HAMPEL AVENUE

ST ST G

PARK BLVD.

BRIGHTON AVENUE

1201 HAMPEL AVE.

1205 HAMPEL AVE.

1211 HAMPEL AVE.

1215 HAMPEL AVE.

1221 HAMPEL AVE.

1227 HAMPEL AVE.

213.58

RS2

212.64

216.70

MW1

4000 GREENWOOD

4008 GREENWOOD

3984 Greenwood

3992
3990
Greenwood

3976
Greenwood

3968
Greenwood

3960
Greenwood

3956
Greenwood

3968-1

3976-1

3984-1

SB 3990-1
188.11

191.69

RS7

RS9

84.80

84.85

INTERCEPTOR TRENCH

4038
BRIGHTON AVE.

4032
BRIGHTON AVE.

4026
BRIGHTON AVE.

4010/4012
BRIGHTON AVE.

4006
BRIGHTON AVE.

4003
PARK BLVD.

RS10

GARAGE

GARAGE

DECK

R2

RS5

R1

GARAGE

R3

WATER UTILITY
GAS UTILITY


SEWER


SEWER

SEWER

SEWER

SEWER





- RS9 GROUNDWATER MONITORING WELL
 - RS1 DESTROYED MONITORING WELL
 - 3968-1 HAND AUGER SOIL/GROUNDWATER SAMPLE POINTS (11/27/2006)
- 0' 20' 50'
- SCALE: 1 INCH=50 FEET

**FIGURE 4C
GROUNDWATER ELEVATIONS**

**DP793, 4035 PARK BLVD.
OAKLAND, CALIFORNIA
(09/14/2011)**



ST ST

G

HAMPEL AVENUE

PARK BLVD.

BRIGHTON AVENUE

4035 PARK BLVD.

MW1

RS2

RS6

R2

RS5

R1

RS8

DECK

R3

212.74

216.30

GARAGE

208.91

204.16

4006 BRIGHTON AVE.

4010/4012 BRIGHTON AVE.

4026 BRIGHTON AVE.

GARAGE

202.49

RS10

210'

205'

200'

195'

190'

184.33

183.11

191.69

RS7

SEWER

403 BRIGHTON AVE.

SEWER

4038 BRIGHTON AVE.

INTERCEPTOR TRENCH

4008 GREENWOOD

4000 GREENWOOD

191.01

(T3)

WATER UTILITY

GAS UTILITY

SEWER

1221 HAMPEL AVE.

1227 HAMPEL AVE.

1215 HAMPEL AVE.

1211 HAMPEL AVE.

1205 HAMPEL AVE.

1201 HAMPEL AVE.

3968 Greenwood

3960 Greenwood

3956 Greenwood

3968-1

3976-1

3984-1

SB 3990-1

187.70

SEWER

3984 Greenwood


3992 Greenwood

3990 Greenwood

3976 Greenwood

Sump

GREENWOOD



- ⊗ HAND AUGER SAMPLE BORINGS SAMPLED ON 11/27/2006
- RS3 SOIL BORING
- ⊖ TRENCH SAMPLE POINT
- ⊕ RS2 GROUNDWATER MONITORING WELL
- Benzene > 1000 ug/L
- Benzene > 500 ug/L
- Benzene > 1 ug/L
- TPHg Groundwater Plume

0' 20' 50'
SCALE: 1 INCH=50 FEET



**FIGURE 5
GROUNDWATER
PLUME
9/14/11
DP 793, 4035 PARK BLVD.
OAKLAND, CALIFORNIA**

Monitor wells (MW1, RS2 and RS6) were destroyed on November 27, 2006.

RS7
TPHg = 460 ug/L
BEN = 0.76 ug/L

RS9
TPHg = 240 ug/L
BEN = 0.52 ug/L

RECOVERY WELL (T1)
TPHg = 1200 ug/l
BEN = 10 ug/L

RS10
TPHg = <50 ug/L
BEN = <0.5 ug/L

TPHg = 1900 ug/L
BEN = 130 ug/L

RS8
TPHg = 19000 ug/L
BEN = 130 ug/L


TPHg = 1200 ug/L
BEN = 7.6 ug/L

TPHg = 1900 ug/L
BEN = 3.5 ug/L

LF1
could not locate

NS
R3

MW1



APPENDIX A.

METHODS AND PROCEDURES, QA/QC

This Appendix documents the specific methods, procedures, and materials used to collect and analyze ground water samples.

Gauging and Measuring Monitor Wells.

Prior to sampling a well, WEGE personnel obtain two measurements: the depth to ground water and the product thickness using a battery powered depth to water-product interface probe and or by using a specially designed bailer. The probe is lowered into the well casing until the instrument signals that the top of water has been reached. The distance from the top of water to the top of casing is read from the tape calibrated in 0.01 foot intervals for accuracy to 0.01 foot, that is attached to the probe. The measured distance is subtracted from the established elevation at the top of casing to determine the elevation of ground water with respect to mean sea level.

The probe is washed with TSP and rinsed in distilled water before each measurement. WEGE has designed and built bailers that will collect a sample of the contents of a well to show the exact thickness of any floating product.

Purging Standing Water from Monitor Wells

If no product is present, WEGE personnel purge the well. This is accomplished by removing ground water from the well until the water quality parameters (temperature, pH, and conductivity) stabilize, or until the well is emptied of water. Periodic measurements of ground water temperature, pH, and conductivity were taken with a Hydac Monitor or other meter and recorded along with the volume of ground water removed from the well. Purging is done by one or more methods singularly or in combination. Bailers, pneumatic or electric sample pumps, or vacuum pump tanks or trucks may be used. The usual amount of water removed is three well volumes. The water collected during purging is either safely stored onsite for later disposition, transported to an approved onsite or offsite sewer discharge system, or an approved onsite or offsite treatment system.

Collection of Water Sample for Analysis After Purging Well

The well is allowed to recover after purging and a ground water sample is collected. A fresh bailer is used to collect enough water for the requirements of the laboratory for the analyses needed or required. The water samples are decanted from the bailer into the appropriate number and size containers. These containers are furnished pre-cleaned to exact EPA protocols, with and without preservatives added, by the analytical laboratory or a chemical supply company. The bottles are filled, with no headspace, and then capped with plastic caps with teflon liners.

The vials or bottles containing the ground water samples are labeled with site name, station, date, time, sampler, and analyses to be performed, and documented on a chain of custody form. They were placed in ziplock bags and stored in a chest cooled to 4°C with ice. The preserved samples are chain of custody delivered to the chosen laboratory.

Collection of Water Sample for Analysis From Pumping Well

Wells that are being utilized for groundwater recovery are sampled after approximately 3 well volumes have been observed pumped from the well. pH, Temperature and Conductivity readings are obtained from the water being pumped from the well. The water samples are collected from the sample port of the well or prior to the first water carbon and slowly fill the appropriate number and size containers. These containers are furnished pre-cleaned to exact EPA protocols, with and without preservatives added, by the analytical laboratory or a chemical supply company. The bottles are filled, with no headspace, and then capped with plastic caps with teflon liners.

The vials or bottles containing the ground water samples are labeled with site name, station, date, time, sampler, and analyses to be performed, and documented on a chain of custody form. They were placed in ziplock bags and stored in a chest cooled to 4°C with ice. The preserved samples are chain of custody delivered to the chosen laboratory.

Analytical Results

TPH is the abbreviations used for Total Petroleum Hydrocarbons used by the laboratories for water and soil analyses. The letter following TPH indicates a particular distinction or grouping for the results. The letters "g", "d", "k", or "o" indicates gasoline, diesel, kerosene, or oil, respectively, ie. TPH-d for diesel range TPH.

BTEX or MTBE are acronyms or abbreviations used for Benzene, Toluene, Ethylbenzene and all of the Xylenes (BTEX) and Methyl Tertiary Butyl Ether (MTBE), respectively.

MBTEX is the designation for the combination of the above five compounds.

The less than symbol, <, used with a "parts per value" indicates the lower detection limit for a given analytical result and the level, if present, of that particular analyte is below or less than that lower detection limit.

Other abbreviations commonly used are ppm, ppb, mg/Kg, ug/Kg, ml/l and ul/l are parts per million, parts per billion, milligrams per kilogram, micrograms per kilogram, milliliters per liter, microliters per liter, respectively.

Chain of Custody Documentation

All water samples that are collected by WEGE and transported to a certified analytical laboratory are accompanied by chain-of-custody (COC) documentation. This documentation is used to record

the movement and custody of a sample from collection in the field to final analysis and storage. Samples to be analyzed at the certified laboratory were logged on the COC sheet provided by the laboratory. The same information provided on the sample labels (site name, sample location, date, time, and analysis to be performed) is also noted on the COC form. Each person relinquishing custody of the sample set signs the COC form indicating the date and time of the transfer to the recipient. A copy of the COC follows the samples or their extracts throughout the laboratory to aid the analyst in identifying the samples and to assure analysis within holding times.

Copies of the COC documentation are included with the laboratory results in Appendix B of this report.

FORMER DESERT PETROLEUM SITE DP 793
 4035 PARK BLVD.
 OAKLAND, CALIFORNIA 94602
 WASTE WATER DISCHARGE PERMIT NUMBER 5043550 1

WASTE WATER PRETREATMENT, 2 IN SERIES CARBON WATER SCRUB UNITS
 PEAK HOURLY DISCHARGE 2 GPM, DAILY 2880 GALLONS

DATE 6-29-11

REASON FOR SITE VISIT monthly
weekly odm, DTW (Carbon In last sample)

TRENCH WELL T1				
TIME	PID	DTW	pH	TEMP. COND.
		8.08		

orange particles in top water
rec'd 18700
DTW = 18700
29" DTW
measure to 30" DTW

TRENCH WELL T2				
TIME	PID	DTW	pH	TEMP. COND.
		8.18		

18712

TRENCH WELL T3				
TIME	PID	DTW	pH	TEMP. COND.
		11.20		

bottom
11/20
19.18 "in shoe"

TRENCH WELL T4				
TIME	PID	DTW	pH	TEMP. COND.

18700

TIME	RS1	RS2	RS5	RS6
	X	X	20.22	X

20.134

TIME	RS7	RS8	RS9	RS10
	4.18	10.20	7.0	2.46

15.24
18.63
20.06

TIME	R1	R2	R3
	44.52	13.12	9.46

21.17
21.46
21.85

TIME	PID	DTW	pH	TEMP.	COND.

COMMENTS cloudy rain. DTW all wells. in lower levels than 18510. DTW cloudy + higher 1858. Test Sample 18510

Feeder filter cartridge 1851
 ELECTRIC METER

RS05 WATER METER 0070928.5 PSI 12 / 10
 T1 WATER METER 0071396.5 PSI 14 / 10 fill check
 discharge WATER METER 07435.73.0

SAMPLES T1, RS05 + C1
 supern pump check good, clean inlet at leaving

SITE MONITORED BY Converse

WASTEWATER INFLUENT	
TIME	
pH	
Conductivity	
Temperature	
PID	

WATER TREATMENT
 RS5 FLOW RATE _____ GALLONS/ _____ MINUTES
 T1 FLOW RATE _____ GALLONS/ _____ MINUTES
 T2 FLOW RATE _____ GALLONS/ _____ MINUTES
 GALLONS PURGED _____
 GALLONS PURGED _____

PRESSURE WATER CARBONS #1 8.0 PSI, #2 X PSI,
 #3 1.5 PSI, #4 0 PSI

WATER PHASE CARBON UNITS INSPECTION COMMENTS good
 CONDITION OF COMPOUND COMMENTS good

Acceptance of water phase carbon units only if completely flooded with water yes no - return to carbon manufacture
 Acceptance of water phase carbon units only if pH is less than 8.5 and containers are in good condition yes no - return to carbon manufacture

FORMER DESERT PETROLEUM SITE DP 793
 4035 PARK BLVD.
 OAKLAND, CALIFORNIA 94602
 WASTE WATER DISCHARGE PERMIT NUMBER 5043550-1

WASTE WATER PRETREATMENT, 2 IN SERIES CARBON WATER SCRUB UNITS
 PEAK HOURLY DISCHARGE 2 GPM, DAILY 2300 GALLONS

DATE 7-14-11

REASON FOR SITE VISIT o/m of treatment system

TRENCH WELL T1					
TIME	PID	DTW	pH	TEMP.	COND.
		1			
		10' pump			
		dry			

TRENCH WELL T2				
PID	DTW	pH	TEMP.	COND.
		10.97		
		out of range		

TRENCH WELL T3				
PID	DTW	pH	TEMP.	COND.

TRENCH WELL T4				
PID	DTW	pH	TEMP.	COND.

DEPTH TO WATER

TIME	RW1	R52	R55	R58
			18.50	
			ground	
			water	

R57	R58	R59	R510

R1	R2	R3

COMMENTS Re Change out filter cartridges T1 & R505

ELECTRIC METER _____ RS05 WATER METER 77761.0 PSI 10
 _____ T1 WATER METER 81449.0 PSI 10
 _____ discharge WATER METER 760407.0

SAMPLE(s) C3-out
 9 ppm
 20 ppm pump check good

SITE MONITORED BY: George Conner

WASTEWATER INFLUENT	
TIME	
pH	
Conductivity	
Temperature	
PID	

WATER TREATMENT
 R55 FLOW RATE _____ GALLONS/ MINUTES
 T1 FLOW RATE _____ GALLONS/ MINUTES
 T2 FLOW RATE _____ GALLONS/ MINUTES

GALLONS PURGED _____
 GALLONS PURGED _____

PRESSURE WATER CARBONS #1 8.0 PSI, #2 X PSI,
 #3 0 PSI, #4 X PSI

WATER PHASE CARBON UNITS INSPECTION COMMENTS good
 CONDITION OF COMPOUND COMMENTS good

Acceptance of water phase carbon units only if completely flooded with water yes no - return to carbon manufacturer
 Acceptance of water phase carbon units only if pH is less than 8.5 and containers are in good condition yes no - return to carbon manufacturer

FORMER DESERT PETROLEUM SITE DP 793
 4035 PARK BLVD.
 OAKLAND, CALIFORNIA 94602
 WASTE WATER DISCHARGE PERMIT NUMBER 5040550 1

WASTE WATER PRETREATMENT, 2 IN SERIES CARBON WATER SCRUB UNITS
 PEAK HOURLY DISCHARGE 2 GPM, DAILY 2000 GALLONS

DATE 7-28-11

REASON FOR SITE VISIT Concess

TRENCH WELL T1					
TIME	PID	DTW	pH	TEMP.	COND.
12:30		12.5			
11:45		11.50			

TRENCH WELL T2				
PID	DTW	pH	TEMP.	COND.
	12.5			

TRENCH WELL T3				
PID	DTW	pH	TEMP.	COND.

TRENCH WELL T4				
PID	DTW	pH	TEMP.	COND.

DEPTH TO WATER

TIME	MWT1	RS2	RS5	RS6
11:00			21.75	
11:30			19.40	

RS7	RS8	RS9	RS10

R1	R2	R3

COMMENTS RS08 Concret TB foot print 1.8' x 1.4' circular x 12" to place lid at soil/gas line. Change out pumps for cleaning/inspection.

ELECTRIC METER 2472

RS05 WATER METER 0084613 PSI 10

T1 WATER METER 0088197 PSI 20 well 22

discharge WATER METER 0774005

SAMPLES None

SITE MONITORED BY: Converse

WASTEWATER INFLUENT	
TIME	
pH	
Conductivity	
Temperature	
PID	

slip pump check good

WATER TREATMENT		
RS5 FLOW RATE	GALLONS/	MINUTES
T1 FLOW RATE	GALLONS/	MINUTES
T2 FLOW RATE	GALLONS/	MINUTES

GALLONS PURGED _____
 GALLONS PURGED _____

PRESSURE WATER CARBONS #1 6.8 PSI, #2 X PSI,
 #3 3.0 PSI, #4 _____ PSI

WATER PHASE CARBON UNITS INSPECTION COMMENTS _____

CONDITION OF COMPOUND COMMENTS _____

Acceptance of water phase carbon units only if completely flooded with water yes no - return to carbon manufacture)
 Acceptance of water phase carbon units only if pH is less than 8.5 and containers are in good condition yes no - return to carbon manufacture

RS05 filter should send bucket - pulled pump some, change out pump for cleaned.
T1 filter dk qty via T1 well over bottom, change out pump for cleaning
press 60 PSI / filter 30 PSI open bytest pump 30 PSI follow 25 PSI

after cleaning Carbons
#1 3.0 #3 20.0

FORMER DESERT PETROLEUM SITE DP 793

4035 PARK BLVD.
OAKLAND, CALIFORNIA 94602
WASTE WATER DISCHARGE PERMIT NUMBER 5043550 1

WASTE WATER PRETREATMENT, 2 IN SERIES CARBON WATER SCRUB UNITS
PEAK HOURLY DISCHARGE 2 GPM, DAILY 2800 GALLONS

DATE 8-10-11

REASON FOR SITE VISIT Carbon check out - site monitor

TRENCH WELL T1					
TIME	PID	DTW	pH	TEMP.	COND.
		10.30			
		10.45			

TRENCH WELL T2					
TIME	PID	DTW	pH	TEMP.	COND.
		10.45			

TRENCH WELL T3					
TIME	PID	DTW	pH	TEMP.	COND.
		NA			

TRENCH WELL T4					
TIME	PID	DTW	pH	TEMP.	COND.
		NA			

DEPTH TO WATER

11:25

TIME	MW1	RS2	RS5	RS8
	X	X	17.85	X

RS7	RS8	RS9	RS10
14.30	8.90	7.92	NA

R1	R2	R3
15.05	13.75	10.55

TIME	PID	DTW	pH	TEMP.	COND.

COMMENTS Spill contained 4 1/2" water. Top pump pump-out working. Trench well pumps off. Recover 51 #2 carbon

ELECTRIC METER 2647

RS05

WATER METER 0088284 PSI 9

T1

WATER METER 0094011.5 PSI 10

discharge

WATER METER 0.783590.5

SITE MONITORED BY: Carl...

WASTEWATER INFLUENT

TIME	pH	Conductivity	Temperature	PID

SAMPLES None

supm pump check - but really shop check

WATER TREATMENT

RS5 FLOW RATE _____ GALLONS/ _____ MINUTES
T1 FLOW RATE _____ GALLONS/ _____ MINUTES
T2 FLOW RATE _____ GALLONS/ _____ MINUTES

GALLONS PURGED _____
GALLONS PURGED _____

PRESSURE WATER CARBONS #1 6 PSI, #2 X PSI
#3 105 PSI, #4 X PSI

WATER PHASE CARBON UNITS INSPECTION COMMENTS

CONDITION OF COMPOUND COMMENTS

Acceptance of water phase carbon units only if completely flooded with water yes no - return to carbon manufacturer
Acceptance of water phase carbon units only if pH is less than 8.5 and containers are in good condition yes no - return to carbon manufacturer

32
Tie 24 filter #14
24 filter #10

PG&E: 800 743-5000

Desert Pet. 805 654 8084

FORMER DESERT PETROLEUM SITE DP 793
 4035 PARK BLVD.
 OAKLAND, CALIFORNIA 94602
 WASTE WATER DISCHARGE PERMIT NUMBER 9043550 1

WASTE WATER PRETREATMENT, 2 IN SERIES CARBON WATER SCRUB UNITS
 PEAK HOURLY DISCHARGE 2 OPM, DAILY 2980 GALLONS

DATE 8-24-11

REASON FOR SITE VISIT Review

TRENCH WELL T1					
TIME	PID	DTW	pH	TEMP.	COND.

TRENCH WELL T2				
PID	DTW	pH	TEMP.	COND.

TRENCH WELL T3				
PID	DTW	pH	TEMP.	COND.

TRENCH WELL T4				
PID	DTW	pH	TEMP.	COND.

DEPTH TO WATER

TIME	NW1	RS2	RS5	RS8

RS7	RS8	RS9	RS10

R1	R2	R3

COMMENTS No power to Elec. Box pumps off. Need to pay bill-P&E

ELECTRIC METER 2848
120V

RS06
 T1
 discharge

WATER METER 0092163 PSI
 WATER METER 0100769 PSI
 WATER METER 0792267

SAMPLE(s) No
 sump pump check in ball used sump pump

SITE MONITORED BY: Converse

WASTEWATER INFLUENT

TIME	
pH	
Conductivity	
Temperature	
PID	

WATER TREATMENT
 RS5 FLOW RATE _____ GALLONS/ _____ MINUTES
 T1 FLOW RATE _____ GALLONS/ _____ MINUTES
 T2 FLOW RATE _____ GALLONS/ _____ MINUTES

GALLONS PURGED _____
 GALLONS PURGED _____

PRESSURE WATER CARBONS #1 _____ PSI, #2 _____ PSI
 #3 _____ PSI, #4 _____ PSI

WATER PHASE CARBON UNITS INSPECTION COMMENTS _____

CONDITION OF COMPOUND COMMENTS _____

Acceptance of water phase carbon units only if completely flooded with water _____ yes _____ no - return to carbon manufacture
 Acceptance of water phase carbon units only if pH is less than 8.5 and containers are in good condition _____ yes _____ no - return to carbon manufacture

FORMER DESERT PETROLEUM SITE DP 793

4035 PARK BLVD.
OAKLAND, CALIFORNIA 94602
WASTE WATER DISCHARGE PERMIT NUMBER 5043550 1

WASTE WATER PRETREATMENT, 2 IN SERIES CARBON WATER SCRUB UNITS
PEAK HOURLY DISCHARGE 2 GPM, DAILY 2880 GALLONS

DATE 8-31-11

REASON FOR SITE VISIT turn pumps on after power outage

W. Etk

RS5 211.51

RS7 141.64

RS8 205.04

RS9 188.38

RS10 203.79

R1 212.97

R2 213.35

R3 216.47

T1 140.14

T2 140.19

T3 191.11

T4 NA

AST

TRENCH WELL T1					
TIME	PID	DTW	pH	TEMP.	COND.
11:26		4.97			
11:28		5.10		28	
11:30				26	

TRENCH WELL T2					
PID	DTW	pH	TEMP.	COND.	
	5.11				

TRENCH WELL T3					
PID	DTW	pH	TEMP.	COND.	
	11.27				

TRENCH WELL T4					
PID	DTW	pH	TEMP.	COND.	

DEPTH TO WATER

TIME	MW1	RS2	RS5	RS6
	X	X	16.10	X
11:38			32.1	

RS7	RS8	RS9	RS10
4.35	5.10	7.25	4.67
	Riser		

R1	R2	R3
14.72	13.43	10.78

↓ need 60 cc sample w/ tubing to remove leak in T16.

COMMENTS Power to Compound. Scum Pump pulls to many amps - trigger TGF, DTW walk prior to turning on pumps.

ELECTRIC METER 2898

11:38 70092207 PSI

WATER METER 0092180 PSI

WATER METER 000819 PSI 12

WATER METER 0792326

RS5
11:35
discharge

SITE MONITORED BY: Converse

WASTEWATER INFLUENT

TIME	
pH	
Conductivity	
Temperature	
PID	

SAMPLE(s) NA

scum pump check - pulls to many amps

WATER TREATMENT
RS5 FLOW RATE _____ GALLONS/ _____ MINUTES
T1 FLOW RATE _____ GALLONS/ _____ MINUTES
T2 FLOW RATE _____ GALLONS/ _____ MINUTES

GALLONS PURGED _____
GALLONS PURGED _____

PRESSURE WATER CARBONS #1 4 PSI, #2 X PSI,
#3 0 PSI, #4 X PSI

WATER PHASE CARBON UNITS INSPECTION COMMENTS good

CONDITION OF COMPOUND COMMENTS good

Acceptance of water phase carbon units only if completely flooded with water yes no - return to carbon manufacture
Acceptance of water phase carbon units only if pH is less than 8.5 and containers are in good condition yes no - return to carbon manufacture

Desert Pet. Pub. Tribble 805 654 8084, ext 204

FORMER DESERT PETROLEUM SITE DP 793

4035 PARK BLVD.
OAKLAND, CALIFORNIA 94602
WASTE WATER DISCHARGE PERMIT NUMBER 5043550 1

WASTE WATER PRETREATMENT, 2 IN SERIES CARBON WATER SCRUB UNITS
PEAK HOURLY DISCHARGE 2 GPM, DAILY 2380 GALLONS

DATE 9-8-11

REASON FOR SITE VISIT weekly adm notify property owners of min sample next week

TRENCH WELL T1					
TIME	PID	DTW	pH	TEMP.	COND.
		<u>Top Screen</u>			
		<u>20 psi</u>			

TRENCH WELL F2				
PID	DTW	pH	TEMP.	COND.
		<u>10.96</u>		

TRENCH WELL T3				
PID	DTW	pH	TEMP.	COND.

TRENCH WELL T4				
PID	DTW	pH	TEMP.	COND.

DEPTH TO WATER

TIME	RSW1	RS2	RS5	RS6
	X	X	<u>32.0</u>	X

RS7	RS8	RS9	RS10

R1	R2	R3

COMMENTS

ELECTRIC METER 3025

RS05

WATER METER 0094360 PSI 8

F1

WATER METER 0106875 PSI 8

discharge

WATER METER 0799990

SITE MONITORED BY: Conner

SAMPLE(s) _____

supra pump check _____

WATER TREATMENT
RS5 FLOW RATE _____ GALLONS/ MINUTES
T1 FLOW RATE _____ GALLONS/ MINUTES
T2 FLOW RATE _____ GALLONS/ MINUTES

GALLONS PURGED _____
GALLONS PURGED _____

PRESSURE WATER CARBONS #1 6 PSI, #2 X PSI,
#3 1.5 PSI, #4 X PSI

WASTEWATER INFLUENT	
TIME	
pH	
Conductivity	
Temperature	
PID	

WATER PHASE CARBON UNITS INSPECTION COMMENTS good

CONDITION OF COMPOUND COMMENTS good

Acceptance of water phase carbon units only if completely flooded with water _____ yes _____ no - return to carbon manufacturer
Acceptance of water phase carbon units only if pH is less than 8.5 and containers are in good condition _____ yes _____ no - return to carbon manufacturer

FORMER DESERT PETROLEUM SITE OP 793

4005 PARK BLVD.
 OAKLAND, CALIFORNIA 94602
 WASTE WATER DISCHARGE PERMIT NUMBER 5043560 1

WASTE WATER PRETREATMENT, 2 IN SERIES CARBON WATER SCRUB UNITS
 PEAK HOURLY DISCHARGE 2 GPM, DAILY 2980 GALLONS

DATE 9-14-11

REASON FOR SITE VISIT Semi Annual Well Samples

TIME	TRENCH WELL T1				
	PID	DTW	pH	TEMP.	COND.

TIME	TRENCH WELL T2				
	PID	DTW	pH	TEMP.	COND.

TIME	TRENCH WELL T3				
	PID	DTW	pH	TEMP.	COND.

TIME	TRENCH WELL T4				
	PID	DTW	pH	TEMP.	COND.

DEPTH TO WATER

TIME	RS1	RS2	RS5	RS8

TIME	RS7	RS3	RS9	RS10

TIME	R1	R2	R3

TIME			

COMMENTS

System not pumping on ground - wells pumped down.

ELECTRIC METER 3101 1600hrs

RS05

WATER METER 0096014 PSI 10

T1

WATER METER 0109744 PSI 10

discharge

WATER METER 0804087

SAMPLES Semi Annual well sample "8"

SITE MONITORED BY:

Converse

suprn pump check good

	WASTEWATER INFLUENT
TIME	
pH	
Conductivity	
Temperature	
PID	

WATER TREATMENT

RS5 FLOW RATE _____ GALLONS/ _____ MINUTES
 T1 FLOW RATE _____ GALLONS/ _____ MINUTES
 T2 FLOW RATE _____ GALLONS/ _____ MINUTES

GALLONS PURGED _____
 GALLONS PURGED _____

PRESSURE WATER CARBONS #1 6.75 PSI, #2 _____ PSI,
 #3 0 PSI, #4 _____ PSI

WATER PHASE CARBON UNITS INSPECTION COMMENTS good

CONDITION OF COMPOUND COMMENTS good

Acceptance of water phase carbon units only if completely flooded with water _____ yes _____ no - return to carbon manufacturer
 Acceptance of water phase carbon units only if pH is less than 8.5 and containers are in good condition _____ yes _____ no - return to carbon manufacturer

FORMER DESERT PETROLEUM SITE DP 703
 4035 PARK BLVD.
 OAKLAND, CALIFORNIA 94602
 WASTE WATER DISCHARGE PERMIT NUMBER 5043550 1

WASTE WATER PRETREATMENT, 2 IN SERIES CARBON WATER SCRUB UNITS
 PEAK HOURLY DISCHARGE 2 GPM, DAILY 2000 GALLONS

DATE 9-23-11

REASON FOR SITE VISIT o/m of system

TRENCH WELL T1					
TIME	PID	DTW	pH	TEMP.	COND.
		11.4 ft			
		Point turned off after			
		2.5 gpm			
		0013702.5			

TRENCH WELL T2				
PID	DTW	pH	TEMP.	COND.
		10.9 ft		

TRENCH WELL T3				
PID	DTW	pH	TEMP.	COND.

TRENCH WELL T4				
PID	DTW	pH	TEMP.	COND.

TIME	RS1	RS2	RS3	RS4
		19.0		
		Point turned off		
		35.5'		
		2 gpm		
		0098329.5		

RS7	RS8	RS9	RS10

R1	R2	R3

COMMENTS System not pumping on arrival - wells pumped down. Check out Filter Controls. inspect carbon
function pumps down pump down; inspect T1 & T2
 ELECTRIC METER 32.11

RS05 WATER METER 00983275 PSI 11.0
 T1 WATER METER 0113700 PSI 9.75
 discharge WATER METER 0809668.5

SAMPLE(s) NO
 sump pump check good

SITE MONITORED BY: Converse

WASTEWATER INFLUENT	
TIME	
pH	
Conductivity	
Temperature	
PID	

WATER TREATMENT
 R25 FLOW RATE _____ GALLONS/ MINUTES
 T1 FLOW RATE _____ GALLONS/ MINUTES
 T2 FLOW RATE _____ GALLONS/ MINUTES

GALLONS PURGED _____
 GALLONS PURGED _____

PRESSURE WATER CARBONS #1 10.5 PSI, #2 X PSI,
 #3 0 PSI, #4 X PSI

WATER PHASE CARBON UNITS INSPECTION COMMENTS good - 2 used carbon on site
 CONDITION OF COMPOUND COMMENTS good

Acceptance of water phase carbon units only if completely flooded with water _____ yes _____ no - return to carbon manufacturer
 Acceptance of water phase carbon units only if pH is less than 9.5 and containers are in good condition _____ yes _____ no - return to carbon manufacturer



**WESTERN
GEO-ENGINEERS**
CALIF. CONTRACTOR #513857
REGISTERED GEOLOGISTS

1386 EAST BEAMER STREET
WOODLAND CA 95776-6003
(530) 668-5300
FAX (530) 662-0273
wege@cal.net

**GROUNDWATER ELEVATION DATA
AND PRODUCT THICKNESS MEASUREMENTS**

SITE DP 793, 4035 Park Blvd., Oakland, CA.

DATE September 14, 2011

START TIME _____

MEASURED BY George Converse

DTW METER USED Solinst Model 122

WELL ID	Casing Elevation In feet	DEPTH OF WELL feet below top of casing (fhtc)	DEPTH TO WATER (fhtc)	DEPTH TO TOP OF FLUID (fhtc)	Free Phase Bonding (feet)	WATER COLUMN IN FEET	Water Elevation
RS05	227.61	39.20	18.70	18.70	NO	not pumping	208.91
RS07	195.99	7.25	4.30	4.30	NO		191.69
RS08	214.67	14.50	10.51	10.51	NO		204.16
RS09	195.63	15.50	7.93	7.93	NO		187.70
RS10	208.46	9.80	5.97	5.97	NO		202.49
RO1	227.69	16.8	14.95	14.95	NO		212.74
RO2	227.28	16.92	14.15	14.15	NO		213.13
RO3	227.25	11.74	10.95	10.95	NO		216.30
T01	195.11	10	12.00	12.00	pumping NO		183.11
T02	195.30	10	10.97	10.97	NO		184.33
T03	202.38	10	11.37	11.37	NO		191.01
T04	197.48	10	Car	---	---		

ground gallons pumped
5.25
2.25
4.25
2.50
5.25
5.25
24.75
pumping

NOTES Global ID# T0600100158 Sampling Co. Log Code: WGEW



**WESTERN
GEO-ENGINEERS**
CALIF. CONTRACTOR #513857
REGISTERED GEOLOGISTS

1386 EAST BLAVER STREET
WOODLAND CA 95776-6003
(530) 668-5300
FAX (530) 662-0273
wege@cal.net

WELL SAMPLE DATA SHEET

SITE DP 793, 4035 PARK BLVD., OAKLAND, CA.

DATE September 14, 2011

WELL ID# RS05

CASING ELEVATION, IN FEET 227.61

CASING TOTAL DEPTH, IN FEET 39.20

CASING DIAMETER IN INCHES 4"

DEPTH TO TOP OF FLUID 18.70

DEPTH TO TOP OF WATER _____

TOP OF WATER ELEVATION _____

PUMP TYPE Grundfoss 4" submersible

DTW METER USED SOLINST MODEL 122

START TIME _____

SAMPLE BY CONVERSE

WATER COLUMN, IN FEET _____

G/L PURGE ONE CASING VOLUME _____

(CASING MULTIPLIERS: 2 INCH = 0.165 g/ FT

2" = 0.625 L/FT

4 INCH = 0.65 g/ FT

4" = 2.46 L/FT

6 INCH = 1.47 g/FT)

FT³ WATER 7.48 GALLONS (G)/28.3 LITERS(L)

FREE PHASE PRODUCT THICKNESS _____

PUMP RATE _____

pH, Cond, Temp meter used HANNA HI 99130

TIME	INTAKE DEPTH	RATE GPM/LPM	CUM. VOL GAL. METERS	TEMP (°C)	pH (units)	Specific Electrical Conductance (uS/cm)	Total Dissolved Solids (ppm)	Dissolved Oxygen (mg/L)	Remarks (color, odor, etc.)
14:09			Recovery well						
				23.3	6.47	383	150		clear
			meter @			009598	9.0		no odor

FINAL VOLUME PURGED _____

TIME SAMPLED 14:09

SAMPLE ID# RS05

NOTES Act Recovery clarity DTW

ANALYSIS INCLUDES: 8260B TPHg, BTEX, MIBE

SAMPLE CONTAINERS 3-HCl PRESERVED 40CC VOA'S

LABORATORY USED KIFF Analytical

purge down to 30.0 in 2 minutes



**WESTERN
GEO-ENGINEERS**
CALIF. CONTRACTOR #518857
REGISTERED GEOLOGISTS

1386 EAST BEAMER STREET
WOODLAND CA 95776-6003
(530) 668-5300.
FAX (530) 662-0273
wego@cal.net

WELL SAMPLE DATA SHEET

SITE DP 793, 4035 PARK BLVD., OAKLAND, CA.

DATE September 14, 2011

START TIME _____

WELL ID# RS08

SAMPLE BY CONVERSE

CASING ELEVATION, IN FEET 214.67

WATER COLUMN, IN FEET 4.6

CASING TOTAL DEPTH, IN FEET 14.5

G/L PURGE ONE CASING VOLUME 0.66 gal

CASING DIAMETER IN INCHES 2"

(CASING MULTIPLIERS: 2 INCH = 0.165 g/ FT

DEPTH TO TOP OF FLUID 10.51

2" = 0.625 L/FT 4 INCH = 0.65 g/ FT

4" = 2.46 L/FT 6 INCH = 1.47 g/FT)

DEPTH TO TOP OF WATER 10.51

FT³ WATER 7.48 GALLONS (G)/28.3 LITERS(L)

TOP OF WATER ELEVATION _____

FREE PHASE PRODUCT THICKNESS _____

PUMP TYPE DISPOSABLE BAILER

PUMP RATE _____

DTW METER USED SOLINST MODEL 122

pH, Cond, Temp meter used HANNA HI 99130

TIME	INTAKE DEPTH	RATE GPM/ MIN	CUM. VOL GAL. LITERS	TEMP (°C)	pH (units)	Specific Electrical Conductance (uS/cm)	Total Dissolved Solids (ppm)	Dissolved Oxygen (mg/L)	Remarks (color, odor, etc.)
11:30			1.0	18.6	6.58	653	376	—	sl cloudy Turbid
11:40			1.0	17.6	6.45	638	320	—	no color
11:45			1.5	17.3	6.45	639	320		small particles on bottom
11:50			2.0	17.1	6.53	647	320		fine sand on bottom

FINAL VOLUME PURGED 2.25 gal

ANALYSIS INCLUDES: 8260B TPH_g, BTEX,

TIME SAMPLED 11:52

McBE

SAMPLE ID# RS08

SAMPLE CONTAINERS 3-HCl PRESERVED

NOTES _____

40CC VOA'S

LABORATORY USED KIFF Analytical

22
.165
4
660

D.T.W. = 12.80



WESTERN
GEO-ENGINEERS
CALIF. CONTRACTOR #513857
REGISTERED GEOLOGISTS

1386 EAST BEAMER STREET
WOODLAND CA 95776-6003
(530) 668-5300.
FAX (530) 662-0273
wege@cal.net

WELL SAMPLE DATA SHEET

SITE **DP 793, 4035 PARK BLVD., OAKLAND, CA.**

DATE **September 14, 2011**

START TIME _____

WELL ID# **RS09**

SAMPLE BY **CONVERSE**

CASING ELEVATION, IN FEET **195.63**

WATER COLUMN, IN FEET **7.57**

CASING TOTAL DEPTH, IN FEET **15.50**

G/L PURGE ONE CASING VOLUME **1.25 gals**

CASING DIAMETER IN INCHES **2"**

(CASING MULTIPLIERS: 2 INCH = 0.165 g/FT

2" = 0.625 L/FT 4 INCH = 0.65 g/FT

4" = 2.46 L/FT 6 INCH = 1.47 g/FT)

DEPTH TO TOP OF FLUID **7.93**

FT³ WATER **7.48 GALLONS (G)/28.3 LITERS(L)**

DEPTH TO TOP OF WATER _____

FREE PHASE PRODUCT THICKNESS _____

TOP OF WATER ELEVATION _____

PUMP TYPE **DISPOSABLE BAILER**

PUMP RATE _____

DTW METER USED **SOLINST MODEL 122**

pH, Cond, Temp meter used **HANNA HI 99130**

TIME	INTAKE DEPTH	RATE GPM/ MIN	CUM. VOL GAL. LITERS	TEMP (°C)	pH (units)	Specific Electrical Conductance (uS/cm)	Total Dissolved Solids (ppm)	Dissolved Oxygen (mg/L)	Remarks (color, odor, etc.)
1250			1.0 liter	18.4	6.66	238	119		C 1000 No color
1255			1.0	18.1	6.59	235	117		SI Touched 1 add, 1/2 bacc
1258			2.0	17.9	6.56	240	120		
1300			3.0	17.8	6.50	280	140		SI Touched bacc on
1303			4.0	17.8	6.52	320	160		no color hobby sticker on bacc on
							DTW =		11.20

FINAL VOLUME PURGED **4.25**

ANALYSIS INCLUDES: **8260B TPHg, BTEX, MIBE**

TIME SAMPLED **1305**

SAMPLE CONTAINERS **3-HCl PRESERVED**

SAMPLE ID# **RS09**

40CC VOA'S

NOTES _____

LABORATORY USED **KIFF Analytical**



**WESTERN
GEO-ENGINEERS**
CALIF. CONTRACTOR #S13857
REGISTERED GEOLOGISTS

1386 EAST BEAMER STREET
WOODLAND CA 95776-6003
(530) 668-5300.
FAX (530) 662-0273
wege@cal.net

WELL SAMPLE DATA SHEET

SITE DP 793, 4035 PARK BLVD., OAKLAND, CA.

DATE September 14, 2011

START TIME _____

WELL ID# RI

SAMPLE BY CONVERSE

CASING ELEVATION, IN FEET 227.69

WATER COLUMN, IN FEET 1.85

CASING TOTAL DEPTH, IN FEET 16.80

G/L PURGE ONE CASING VOLUME 2.85

CASING DIAMETER IN INCHES 6"

(CASING MULTIPLIERS: 2 INCH = 0.165 g/ FT

4" = 2.46 L/FT

4 INCH = 0.65 g/ FT

6" = 5.56 L/FT

6 INCH = 1.47 g/FT)

DEPTH TO TOP OF FLUID 14.95

FT³ WATER 7.48 GALLONS (G)/28.3 LITERS(L)

DEPTH TO TOP OF WATER 14.95

FREE PHASE PRODUCT THICKNESS _____

PUMP TYPE Hand Bail

PUMP RATE _____

DTW METER USED SOLINST MODEL 122

pH, Cond, Temp meter used HANNA HI 99130

TIME	INTAKE DEPTH	RATE GPM/LPM	CUM. VOL GAL. LITERS	TEMP (°C)	pH (units)	Specific Electrical Conductance (uS/cm)	Total Dissolved Solids (ppm)	Dissolved Oxygen (mg/L)	Remarks (color, odor, etc.)
15:14			1 Bail	18.7	6.99	450	226		clear - ph glass
15:27			2.0	18.5	6.61	420	209		stabilize on bottom
15:30			3.0	18.5	6.62	412	206		clear
15:34			4.0	18.5	6.62	412	206		}
15:37			5.0	18.5	6.64	412	206		

DTW = 15.10

FINAL VOLUME PURGED 5.25

ANALYSIS INCLUDES: 8260B TPHg, BTEX,

MtBE

TIME SAMPLED 15:40

SAMPLE CONTAINERS 3-HCl PRESERVED

40CC VOA'S

SAMPLE ID# RI

LABORATORY USED KIFF Analytical

NOTES _____

~~1.85~~
1.9
1.47
13.9
76
1.9
2.793



**WESTERN
GEO-ENGINEERS**
CALIF. CONTRACTOR #513857
REGISTERED GEOLOGISTS

1386 EAST BEAMER STREET
WOODLAND CA 95776-6003
(530) 668-5300
FAX (530) 662-0273
wege@geal.net

WELL SAMPLE DATA SHEET

SITE DP 793, 4035 PARK BLVD., OAKLAND, CA.

DATE September 14, 2011

START TIME _____

WELL ID# R2

SAMPLE BY CONVERSE

CASING ELEVATION, IN FEET 227.28

WATER COLUMN, IN FEET 2, 77

CASING TOTAL DEPTH, IN FEET 16.92

G/L PURGE ONE CASING VOLUME 5.25 ~~3.15~~

CASING DIAMETER IN INCHES 6"

(CASING MULTIPLIERS: 2 INCH = 0.165 gal/ FT

4" = 2.46 L/FT 4 INCH = 0.65 gal/ FT

6" = 5.56 L/FT 6 INCH = 1.47 gal/FT)

DEPTH TO TOP OF FLUID 14.15

DEPTH TO TOP OF WATER 14.15

FT³ WATER 7.48 GALLONS (G)/28.3 LITERS(L)

TOP OF WATER ELEVATION _____

FREE PHASE PRODUCT THICKNESS _____

PUMP TYPE Hand Ball

PUMP RATE _____

DTW METER USED SOLINST MODEL 122

pH, Cond, Temp meter used HANNA HI 99130

TIME	INTAKE DEPTH	RATE GPM/LPM	CUM. VOL GAL. LITERS	TEMP (°C)	pH (units)	Specific Electrical Conductance (uS/cm)	Total Dissolved Solids (ppm)	Dissolved Oxygen (mg/L)	Remarks (color, odor, etc.)
1455			1 liter	22.6	6.40	699	348		clear
1502			2.0	19.8	6.44	698	349		}
15:06			4.0	19.2	6.52	687	343		
1508			5.0	19.1	6.54	690	345		
									DTW = 14.23

FINAL VOLUME PURGED 5.25

ANALYSIS INCLUDES: 8260B TPHg, BTEX, MiBE

TIME SAMPLED 15:14

SAMPLE CONTAINERS 3-HCl PRESERVED

SAMPLE ID# R2

40CC VOA'S

NOTES _____

LABORATORY USED KIEF Analytical



**WESTERN
GEO-ENGINEERS**
CALIF. CONTRACTOR #313857
REGISTERED GEOLOGISTS

1386 EAST BEAMER STREET
WOODLAND CA 95776-6003
(530) 668-5300.
FAX (530) 662-0273
wego@cal.net

WELL SAMPLE DATA SHEET

SITE DP 793, 4035 PARK BLVD., OAKLAND, CA.
 DATE September 14, 2011 START TIME _____
 WELL ID# RECEPTOR TRENCH T1, T2, T3, T4 SAMPLE BY CONVERSE
 CASING ELEVATION, IN FEET T1=195.11 WATER COLUMN, IN FEET _____
 CASING TOTAL DEPTH, IN FEET 14.5 G/L PURGE ONE CASING VOLUME _____
 CASING DIAMETER IN INCHES 4" (CASING MULTIPLIERS: 2 INCH = 0.165 g/ FT
 DEPTH TO TOP OF FLUID _____ 2" = 0.625 L/FT 4 INCH = 0.65 g/ FT
 4" = 2.46 L/FT 6 INCH = 1.47 g/FT)
 DEPTH TO TOP OF WATER _____ FT³ WATER 7.48 GALLONS (G); 28.3 LITERS (L)
 TOP OF WATER ELEVATION _____ FREE PHASE PRODUCT THICKNESS _____
 PUMP TYPE Grundfoss 4" submersible PUMP RATE _____
 DTW METER USED SOLINST MODEL 122 pH, Cond, Temp meter used HANNA HI 99130


TIME	INTAKE DEPTH	RATE GPM/ LPM	CUM. VOL GAL. LITERS	TEMP (°C)	pH (mits)	Specific Electrical Conductance (uS/cm)	Total Dissolved Solids (ppm)	Dissolved Oxygen (mg/L)	Remarks (color, odor, etc.)
		<i>Empty well</i>							
		<i>meter @</i>		<i>01</i>	<i>09</i>	<i>652.0</i>			
				<i>24.2</i>	<i>6.47</i>	<i>397</i>	<i>197</i>		<i>Clear no color</i>

FINAL VOLUME PURGED *Empty* ANALYSIS INCLUDES: 8260B TPHg, BTEX, MtBE
 TIME SAMPLED *1420* SAMPLE CONTAINERS 3-HCl PRESERVED
 SAMPLE ID# T1 40CC VOA'S
 LABORATORY USED KIFF Analytical
 NOTES _____


APPENDIX B.

GROUNDWATER ELEVATION CHART
TPHg, Benzene & MtBE IN WELLS CHARTS

MTBE IN WELLS



Groundwater Elevation



APPENDIX C.
LABORATORY REPORTS



Report Number : 78779

Date : 09/22/2011

Laboratory Results

George Converse
Western Geo-Engineers
1386 East Beamer St.
Woodland, CA 95776

Subject : 8 Water Samples
Project Name : DP793
Project Number : Sept. 2011

Dear Mr. Converse,

Chemical analysis of the samples referenced above has been completed. Summaries of the data are contained on the following pages. Sample(s) were received under documented chain-of-custody. US EPA protocols for sample storage and preservation were followed. Testing procedures comply with the 2003 NELAC standard. All soil samples are reported on a total weight (wet weight) basis unless noted otherwise in the case narrative. Laboratory results relate only to the samples tested. This report may be freely reproduced in full, but may only be reproduced in part with the express permission of Kiff Analytical, LLC. Kiff Analytical, LLC is certified by the State of California under the National Environmental Laboratory Accreditation Program (NELAP), lab # 08263CA. If you have any questions regarding procedures or results, please call me at 530-297-4800.

Sincerely,



Joel Kiff



Report Number : 78779

Date : 09/22/2011

Project Name : **DP793**

Project Number : **Sept. 2011**

Sample : **RS05**

Matrix : Water

Lab Number : 78779-01

Sample Date :09/14/2011

Parameter	Measured Value	Method Reporting Limit	Units	Analysis Method	Date/Time Analyzed
Benzene	7.6	0.50	ug/L	EPA 8260B	09/20/11 02:00
Toluene	4.7	0.50	ug/L	EPA 8260B	09/20/11 02:00
Ethylbenzene	6.6	0.50	ug/L	EPA 8260B	09/20/11 02:00
Total Xylenes	74	0.50	ug/L	EPA 8260B	09/20/11 02:00
Methyl-t-butyl ether (MTBE)	< 0.50	0.50	ug/L	EPA 8260B	09/20/11 02:00
TPH as Gasoline	1200	50	ug/L	EPA 8260B	09/20/11 02:00
1,2-Dichloroethane-d4 (Surr)	99.3		% Recovery	EPA 8260B	09/20/11 02:00
Toluene - d8 (Surr)	98.0		% Recovery	EPA 8260B	09/20/11 02:00

Sample : **RS07**

Matrix : Water

Lab Number : 78779-02

Sample Date :09/14/2011

Parameter	Measured Value	Method Reporting Limit	Units	Analysis Method	Date/Time Analyzed
Benzene	0.76	0.50	ug/L	EPA 8260B	09/20/11 02:35
Toluene	< 0.50	0.50	ug/L	EPA 8260B	09/20/11 02:35
Ethylbenzene	3.2	0.50	ug/L	EPA 8260B	09/20/11 02:35
Total Xylenes	0.67	0.50	ug/L	EPA 8260B	09/20/11 02:35
Methyl-t-butyl ether (MTBE)	< 0.50	0.50	ug/L	EPA 8260B	09/20/11 02:35
TPH as Gasoline	460	50	ug/L	EPA 8260B	09/20/11 02:35
1,2-Dichloroethane-d4 (Surr)	102		% Recovery	EPA 8260B	09/20/11 02:35
Toluene - d8 (Surr)	98.1		% Recovery	EPA 8260B	09/20/11 02:35



Report Number : 78779

Date : 09/22/2011

Project Name : **DP793**

Project Number : **Sept. 2011**

Sample : **RS08**

Matrix : Water

Lab Number : 78779-03

Sample Date :09/14/2011

Parameter	Measured Value	Method Reporting Limit	Units	Analysis Method	Date/Time Analyzed
Benzene	130	0.50	ug/L	EPA 8260B	09/19/11 07:16
Toluene	60	0.50	ug/L	EPA 8260B	09/19/11 07:16
Ethylbenzene	86	0.50	ug/L	EPA 8260B	09/19/11 07:16
Total Xylenes	1300	2.5	ug/L	EPA 8260B	09/21/11 04:48
Methyl-t-butyl ether (MTBE)	< 0.50	0.50	ug/L	EPA 8260B	09/19/11 07:16
TPH as Gasoline	19000	250	ug/L	EPA 8260B	09/21/11 04:48
1,2-Dichloroethane-d4 (Surr)	95.4		% Recovery	EPA 8260B	09/19/11 07:16
Toluene - d8 (Surr)	97.6		% Recovery	EPA 8260B	09/19/11 07:16

Sample : **RS09**

Matrix : Water

Lab Number : 78779-04

Sample Date :09/14/2011

Parameter	Measured Value	Method Reporting Limit	Units	Analysis Method	Date/Time Analyzed
Benzene	0.52	0.50	ug/L	EPA 8260B	09/20/11 03:10
Toluene	< 0.50	0.50	ug/L	EPA 8260B	09/20/11 03:10
Ethylbenzene	< 0.50	0.50	ug/L	EPA 8260B	09/20/11 03:10
Total Xylenes	< 0.50	0.50	ug/L	EPA 8260B	09/20/11 03:10
Methyl-t-butyl ether (MTBE)	1.2	0.50	ug/L	EPA 8260B	09/20/11 03:10
TPH as Gasoline	240	50	ug/L	EPA 8260B	09/20/11 03:10
1,2-Dichloroethane-d4 (Surr)	102		% Recovery	EPA 8260B	09/20/11 03:10
Toluene - d8 (Surr)	96.6		% Recovery	EPA 8260B	09/20/11 03:10



Report Number : 78779

Date : 09/22/2011

Project Name : **DP793**

Project Number : **Sept. 2011**

Sample : **RS10**

Matrix : Water

Lab Number : 78779-05

Sample Date :09/14/2011

Parameter	Measured Value	Method Reporting Limit	Units	Analysis Method	Date/Time Analyzed
Benzene	< 0.50	0.50	ug/L	EPA 8260B	09/19/11 20:35
Toluene	< 0.50	0.50	ug/L	EPA 8260B	09/19/11 20:35
Ethylbenzene	< 0.50	0.50	ug/L	EPA 8260B	09/19/11 20:35
Total Xylenes	< 0.50	0.50	ug/L	EPA 8260B	09/19/11 20:35
Methyl-t-butyl ether (MTBE)	< 0.50	0.50	ug/L	EPA 8260B	09/19/11 20:35
TPH as Gasoline	< 50	50	ug/L	EPA 8260B	09/19/11 20:35
1,2-Dichloroethane-d4 (Surr)	103		% Recovery	EPA 8260B	09/19/11 20:35
Toluene - d8 (Surr)	97.9		% Recovery	EPA 8260B	09/19/11 20:35

Sample : **R1**

Matrix : Water

Lab Number : 78779-06

Sample Date :09/14/2011

Parameter	Measured Value	Method Reporting Limit	Units	Analysis Method	Date/Time Analyzed
Benzene	3.5	0.50	ug/L	EPA 8260B	09/19/11 20:38
Toluene	0.63	0.50	ug/L	EPA 8260B	09/19/11 20:38
Ethylbenzene	3.2	0.50	ug/L	EPA 8260B	09/19/11 20:38
Total Xylenes	1.7	0.50	ug/L	EPA 8260B	09/19/11 20:38
Methyl-t-butyl ether (MTBE)	< 0.50	0.50	ug/L	EPA 8260B	09/19/11 20:38
TPH as Gasoline	1900	50	ug/L	EPA 8260B	09/19/11 20:38
1,2-Dichloroethane-d4 (Surr)	93.5		% Recovery	EPA 8260B	09/19/11 20:38
Toluene - d8 (Surr)	93.3		% Recovery	EPA 8260B	09/19/11 20:38



Report Number : 78779

Date : 09/22/2011

Project Name : **DP793**

Project Number : **Sept. 2011**

Sample : **R2**

Matrix : Water

Lab Number : 78779-07

Sample Date :09/14/2011

Parameter	Measured Value	Method Reporting Limit	Units	Analysis Method	Date/Time Analyzed
Benzene	130	0.50	ug/L	EPA 8260B	09/19/11 20:47
Toluene	4.9	0.50	ug/L	EPA 8260B	09/19/11 20:47
Ethylbenzene	11	0.50	ug/L	EPA 8260B	09/19/11 20:47
Total Xylenes	5.4	0.50	ug/L	EPA 8260B	09/19/11 20:47
Methyl-t-butyl ether (MTBE)	< 0.50	0.50	ug/L	EPA 8260B	09/19/11 20:47
TPH as Gasoline	1900	50	ug/L	EPA 8260B	09/19/11 20:47
1,2-Dichloroethane-d4 (Surr)	97.5		% Recovery	EPA 8260B	09/19/11 20:47
Toluene - d8 (Surr)	95.7		% Recovery	EPA 8260B	09/19/11 20:47

Sample : **T1**

Matrix : Water

Lab Number : 78779-08

Sample Date :09/14/2011

Parameter	Measured Value	Method Reporting Limit	Units	Analysis Method	Date/Time Analyzed
Benzene	10	0.50	ug/L	EPA 8260B	09/20/11 03:45
Toluene	5.7	0.50	ug/L	EPA 8260B	09/20/11 03:45
Ethylbenzene	8.6	0.50	ug/L	EPA 8260B	09/20/11 03:45
Total Xylenes	85	0.50	ug/L	EPA 8260B	09/20/11 03:45
Methyl-t-butyl ether (MTBE)	< 0.50	0.50	ug/L	EPA 8260B	09/20/11 03:45
TPH as Gasoline	1200	50	ug/L	EPA 8260B	09/20/11 03:45
1,2-Dichloroethane-d4 (Surr)	102		% Recovery	EPA 8260B	09/20/11 03:45
Toluene - d8 (Surr)	98.9		% Recovery	EPA 8260B	09/20/11 03:45

QC Report : Method Blank DataProject Name : **DP793**Project Number : **Sept. 2011**

Parameter	Measured Value	Method Reporting Limit	Units	Analysis Method	Date Analyzed	Parameter	Measured Value	Method Reporting Limit	Units	Analysis Method	Date Analyzed
Total Xylenes	< 0.50	0.50	ug/L	EPA 8260B	09/21/2011	Benzene	< 0.50	0.50	ug/L	EPA 8260B	09/19/2011
TPH as Gasoline	< 50	50	ug/L	EPA 8260B	09/21/2011	Ethylbenzene	< 0.50	0.50	ug/L	EPA 8260B	09/19/2011
Benzene	< 0.50	0.50	ug/L	EPA 8260B	09/19/2011	Toluene	< 0.50	0.50	ug/L	EPA 8260B	09/19/2011
Ethylbenzene	< 0.50	0.50	ug/L	EPA 8260B	09/19/2011	Total Xylenes	< 0.50	0.50	ug/L	EPA 8260B	09/19/2011
Toluene	< 0.50	0.50	ug/L	EPA 8260B	09/19/2011	Methyl-t-butyl ether (MTBE)	< 0.50	0.50	ug/L	EPA 8260B	09/19/2011
Total Xylenes	< 0.50	0.50	ug/L	EPA 8260B	09/19/2011	TPH as Gasoline	< 50	50	ug/L	EPA 8260B	09/19/2011
Methyl-t-butyl ether (MTBE)	< 0.50	0.50	ug/L	EPA 8260B	09/19/2011	1,2-Dichloroethane-d4 (Surr)	101		%	EPA 8260B	09/19/2011
TPH as Gasoline	< 50	50	ug/L	EPA 8260B	09/19/2011	Toluene - d8 (Surr)	101		%	EPA 8260B	09/19/2011
1,2-Dichloroethane-d4 (Surr)	102		%	EPA 8260B	09/19/2011						
Toluene - d8 (Surr)	99.0		%	EPA 8260B	09/19/2011						
Benzene	< 0.50	0.50	ug/L	EPA 8260B	09/18/2011						
Ethylbenzene	< 0.50	0.50	ug/L	EPA 8260B	09/18/2011						
Toluene	< 0.50	0.50	ug/L	EPA 8260B	09/18/2011						
Methyl-t-butyl ether (MTBE)	< 0.50	0.50	ug/L	EPA 8260B	09/18/2011						
1,2-Dichloroethane-d4 (Surr)	99.5		%	EPA 8260B	09/18/2011						
Toluene - d8 (Surr)	99.4		%	EPA 8260B	09/18/2011						
Benzene	< 0.50	0.50	ug/L	EPA 8260B	09/19/2011						
Ethylbenzene	< 0.50	0.50	ug/L	EPA 8260B	09/19/2011						
Toluene	< 0.50	0.50	ug/L	EPA 8260B	09/19/2011						
Total Xylenes	< 0.50	0.50	ug/L	EPA 8260B	09/19/2011						
Methyl-t-butyl ether (MTBE)	< 0.50	0.50	ug/L	EPA 8260B	09/19/2011						
TPH as Gasoline	< 50	50	ug/L	EPA 8260B	09/19/2011						
1,2-Dichloroethane-d4 (Surr)	100		%	EPA 8260B	09/19/2011						
Toluene - d8 (Surr)	98.1		%	EPA 8260B	09/19/2011						

QC Report : Matrix Spike/ Matrix Spike DuplicateProject Name : **DP793**Project Number : **Sept. 2011**

Parameter	Spiked Sample	Sample Value	Spike Level	Spike Dup. Level	Spiked Sample Value	Duplicate Spiked Sample Value	Units	Analysis Method	Date Analyzed	Spiked Sample Percent Recov.	Duplicate Spiked Sample Percent Recov.	Relative Percent Diff.	Spiked Sample Percent Recov. Limit	Relative Percent Diff. Limit
P + M Xylene	78812-01	16	39.8	39.4	58.5	54.3	ug/L	EPA 8260B	9/20/11	107	97.8	9.28	76.8-120	25
Benzene	78779-07	130	40.0	40.0	161	160	ug/L	EPA 8260B	9/19/11	86.3	84.2	2.49	80-120	25
Ethylbenzene	78779-07	11	40.0	40.0	51.3	51.4	ug/L	EPA 8260B	9/19/11	99.7	99.8	0.0791	80-120	25
Methyl-t-butyl ether	78779-07	<0.50	40.2	40.2	40.8	41.9	ug/L	EPA 8260B	9/19/11	102	104	2.57	69.7-121	25
P + M Xylene	78779-07	4.4	40.0	40.0	43.2	43.3	ug/L	EPA 8260B	9/19/11	97.1	97.3	0.240	76.8-120	25
Toluene	78779-07	4.9	40.0	40.0	42.0	42.4	ug/L	EPA 8260B	9/19/11	92.6	93.6	1.08	80-120	25
Benzene	78785-03	<0.50	40.0	40.0	36.2	36.8	ug/L	EPA 8260B	9/18/11	90.5	92.0	1.62	80-120	25
Ethylbenzene	78785-03	<0.50	40.0	40.0	37.8	38.8	ug/L	EPA 8260B	9/18/11	94.6	97.1	2.58	80-120	25
Methyl-t-butyl ether	78785-03	<0.50	40.2	40.2	34.9	36.4	ug/L	EPA 8260B	9/18/11	86.9	90.5	4.01	69.7-121	25

QC Report : Matrix Spike/ Matrix Spike DuplicateProject Name : **DP793**Project Number : **Sept. 2011**

Parameter	Spiked Sample	Sample Value	Spike Level	Spike Dup. Level	Spiked Sample Value	Duplicate Spiked Sample Value	Units	Analysis Method	Date Analyzed	Spiked Sample Percent Recov.	Duplicate Spiked Sample Percent Recov.	Relative Percent Diff.	Spiked Sample Percent Recov. Limit	Relative Percent Diff. Limit
Toluene	78785-03	<0.50	40.0	40.0	36.3	37.1	ug/L	EPA 8260B	9/18/11	90.7	92.8	2.34	80-120	25
Benzene	78779-05	<0.50	40.0	40.0	39.2	36.8	ug/L	EPA 8260B	9/19/11	98.0	92.0	6.35	80-120	25
Ethylbenzene	78779-05	<0.50	40.0	40.0	41.5	38.4	ug/L	EPA 8260B	9/19/11	104	96.0	7.80	80-120	25
Methyl-t-butyl ether	78779-05	<0.50	40.2	40.2	38.7	36.1	ug/L	EPA 8260B	9/19/11	96.4	89.9	6.98	69.7-121	25
P + M Xylene	78779-05	<0.50	40.0	40.0	41.0	38.4	ug/L	EPA 8260B	9/19/11	102	96.1	6.44	76.8-120	25
Toluene	78779-05	<0.50	40.0	40.0	39.6	36.9	ug/L	EPA 8260B	9/19/11	99.0	92.2	7.04	80-120	25
Benzene	78779-06	3.5	40.0	40.0	40.3	40.2	ug/L	EPA 8260B	9/19/11	92.0	91.9	0.132	80-120	25
Ethylbenzene	78779-06	3.2	40.0	40.0	42.8	44.7	ug/L	EPA 8260B	9/19/11	98.9	104	4.81	80-120	25
Methyl-t-butyl ether	78779-06	<0.50	40.2	40.2	36.9	37.8	ug/L	EPA 8260B	9/19/11	91.9	94.0	2.28	69.7-121	25

QC Report : Matrix Spike/ Matrix Spike DuplicateProject Name : **DP793**Project Number : **Sept. 2011**

Parameter	Spiked Sample	Sample Value	Spike Level	Spike Dup. Level	Spiked Sample Value	Duplicate Spiked Sample Value	Units	Analysis Method	Date Analyzed	Spiked Sample Percent Recov.	Duplicate Spiked Sample Percent Recov.	Relative Percent Diff.	Spiked Sample Percent Recov. Limit	Relative Percent Diff. Limit
P + M Xylene	78779-06	1.1	40.0	40.0	41.4	43.0	ug/L	EPA 8260B	9/19/11	101	105	3.89	76.8-120	25
Toluene	78779-06	0.63	40.0	40.0	37.5	39.7	ug/L	EPA 8260B	9/19/11	92.1	97.8	6.01	80-120	25

QC Report : Laboratory Control Sample (LCS)Project Name : **DP793**Project Number : **Sept. 2011**

Parameter	Spike Level	Units	Analysis Method	Date Analyzed	LCS Percent Recov.	LCS Percent Recov. Limit
P + M Xylene	40.0	ug/L	EPA 8260B	9/20/11	102	76.8-120
Benzene	40.0	ug/L	EPA 8260B	9/19/11	99.0	80-120
Ethylbenzene	40.0	ug/L	EPA 8260B	9/19/11	102	80-120
Methyl-t-butyl ether	40.2	ug/L	EPA 8260B	9/19/11	109	69.7-121
P + M Xylene	40.0	ug/L	EPA 8260B	9/19/11	102	76.8-120
TPH as Gasoline	500	ug/L	EPA 8260B	9/19/11	109	70.0-130
Toluene	40.0	ug/L	EPA 8260B	9/19/11	99.1	80-120
Benzene	40.1	ug/L	EPA 8260B	9/18/11	92.6	80-120
Ethylbenzene	40.1	ug/L	EPA 8260B	9/18/11	95.5	80-120
Methyl-t-butyl ether	40.3	ug/L	EPA 8260B	9/18/11	88.4	69.7-121
Toluene	40.1	ug/L	EPA 8260B	9/18/11	93.2	80-120
Benzene	40.1	ug/L	EPA 8260B	9/19/11	98.6	80-120
Ethylbenzene	40.1	ug/L	EPA 8260B	9/19/11	102	80-120
Methyl-t-butyl ether	40.3	ug/L	EPA 8260B	9/19/11	95.9	69.7-121
P + M Xylene	40.1	ug/L	EPA 8260B	9/19/11	101	76.8-120
TPH as Gasoline	501	ug/L	EPA 8260B	9/19/11	91.8	70.0-130
Toluene	40.1	ug/L	EPA 8260B	9/19/11	98.4	80-120

QC Report : Laboratory Control Sample (LCS)Project Name : **DP793**Project Number : **Sept. 2011**

Parameter	Spike Level	Units	Analysis Method	Date Analyzed	LCS Percent Recov.	LCS Percent Recov. Limit
Benzene	39.9	ug/L	EPA 8260B	9/19/11	101	80-120
Ethylbenzene	39.9	ug/L	EPA 8260B	9/19/11	102	80-120
Methyl-t-butyl ether	40.1	ug/L	EPA 8260B	9/19/11	95.9	69.7-121
P + M Xylene	39.9	ug/L	EPA 8260B	9/19/11	104	76.8-120
TPH as Gasoline	500	ug/L	EPA 8260B	9/19/11	115	70.0-130
Toluene	39.9	ug/L	EPA 8260B	9/19/11	103	80-120

Project Contact (Hardcopy or PDF To): George Conner California EDF Report? Yes No

Company / Address: 1386 E Beamer St Sampling Company Log Code:

Phone Number: 530 668 5300 Global ID:

Fax Number: 530 662 EDF Deliverable To (Email Address):

Project #: Sept. 2011 P.O. #:

Project Name: DP793 Bill to: rd ch# 3612

Sampler Print Name: George Conner

Sampler Signature: [Signature]

Project Address: Oakland

Sampling Container Preservative Matrix

Sample Designation	Date	Time	40 ml VOA	Container				Preservative			Matrix			
				Sleeve	Poly	Glass	Tedlar	HCl	HNO ₃	None	Water	Soil	Air	
RS05	9-14-11	1405	3					X				X		
RS07		1335												
RS08		1152												
RS09		1305												
RS10		1230												
R1		1540												
R2		1514												
T1		1420												

Chain-of-Custody Record and Analysis Request

Analysis Request												TAT
CIRCLE METHOD												For Lab Use Only
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	24 hr
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	48hr
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	72hr
<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	1 wk

Relinquished by: [Signature] Date: 9-15-11 Time: 1330 Received by: _____
 Relinquished by: _____ Date: _____ Time: _____ Received by: _____
 Relinquished by: _____ Date: 091511 Time: 1330 Received by Laboratory: [Signature]

Remarks: Paid by check #3612 for \$528.00 on 091511 1350 [Signature]

APPENDIX D.

Correspondence from Alameda
County Health



ENVIRONMENTAL HEALTH SERVICES
ENVIRONMENTAL PROTECTION
1131 Harbor Bay Parkway, Suite 250
Alameda, CA 94502-6577
(510) 567-6700
FAX (510) 337-9335

July 11, 2011

Mr. William Thompson
Desert Petroleum
3781 Telegraph Road
Ventura, CA 93003-3420

Mr. Kin Man Li et al.
P.O. Box 348
Oakland, CA 94604

Mr. Tony Razi
3609 East 14th Street
Oakland, CA 94601

Jason Golpad & Mojtaba Karimabadi
c/o Matt Haley
1633 San Pablo Avenue
Oakland, CA 94608

Subject: Rejection of Natural Attenuation Work Plan for Fuel Leak Case No. RO0000429 and GeoTracker Global ID T0600100158, Desert Petroleum Site DP793, 4035 Park Boulevard, Oakland, CA 94602

Dear Mr. Thompson, Li, Razi, and Haley:

Alameda County Environmental Health (ACEH) staff has reviewed the case file for the above referenced fuel leak case including the most recently submitted document entitled, "*Work Plan, Natural Attenuation Soil Sampling*," dated June 8, 2011 and received by ACEH on June 23, 2011. The Work Plan, which was prepared on your behalf by Western Geo-Engineers, proposes advancing four soil borings within two feet of soil borings previously advanced in 2004. The Work Plan indicates that the purpose of the soil borings is to verify the degree of natural attenuation.

The document entitled, "*Work Plan Natural Attenuation Soil Sampling*," dated June 8, 2011 and the proposed scope of work was not requested by ACEH. We do not believe this work is justified, particularly given the long history of lack of planning, lack of compliance, and extended delays on implementing remediation for this case. If the natural attenuation sampling is performed, the work will be done without ACEH approval and should not be reimbursed by the UST Cleanup Fund.

Although some natural attenuation can be expected to occur over a seven year period, advancing soil borings in the same locations as borings advanced seven years ago does not appear to provide sufficient information to justify further delaying excavation. This release occurred more than 20 years ago. A review of groundwater monitoring results indicates that groundwater concentrations in several wells have increased between 2004 and 2011. Natural attenuation does not appear to be a viable alternative for this site.

In a Notice to Comply dated September 8, 2010, ACEH notified you that this site is out of compliance with directives from this agency and requested that the proposed excavation be implemented in accordance with a Compliance Schedule provided in the September 8, 2010 correspondence. The Compliance Schedule and the progress made to date are noted below:

COMPLIANCE SCHEDULE

In correspondence dated, September 8, 2010, ACEH provided a list of actions with due dates that must be implemented to return the site to compliance:

- **November 18, 2010** – Resume groundwater extraction from well RS-5
- **November 30, 2010** – Complete permitting process for excavation and submit a schedule for ACEH review for planning and implementing excavation with excavation start date no later than May 30, 2011
- **December 6, 2010** – Begin construction of treatment compound for intercept trench
- **January 6, 2011** – Treatment compound operational

PROGRESS ON COMPLIANCE SCHEDULE

The following is a summary of the progress to date on the actions required in the Compliance Schedule:

1. **Resume Groundwater Extraction from Well RS-5.**
Requested Date: November 18, 2010
Actual Date: April 6, 2011

Without ACEH concurrence or approval, pumping of on-site well RS-5 was suspended and the submersible pump, pump controller, and water totalizing meter removed from the site. Pumping from RS-5 had influenced off-site water levels and may have been effective in reducing off-site impacts. The equipment was reinstalled and pumping from well RS-5 was resumed on April 6, 2011.

2. **Complete Permitting Process for Excavation and Submit a Schedule for ACEH Review for Planning and Implementing Excavation with Excavation Start Date No Later than May 30, 2011**
Requested Date: November 30, 2010
Actual Date: Not completed

Excavation of soils in the source area was proposed in a Work Plan dated February 13, 2006 and approved by ACEH in correspondence dated April 4, 2006. Since 2006, the plans for excavation have been modified in response to alternate proposals from Western Geo-Engineers, ACEH technical comments, and comments from concerned members of the public. However, excavation has not been implemented to date. Most recently, the remedial excavation was scheduled to begin in August 2010 but was postponed apparently because funds were not available. Due to the long-term and repeated delays in proceeding with excavation, this fuel leak case is currently out of compliance with directives from this agency. In order to avoid the repeated delays over the past two years that have occurred in proceeding with excavation, we requested that permitting for the excavation be completed by November 30, 2010 with an excavation start date no later than May 31, 2011. The permitting

Attachment 1

Responsible Party(ies) Legal Requirements / Obligations

REPORT REQUESTS

These reports are being requested pursuant to California Health and Safety Code Section 25296.10. 23 CCR Sections 2652 through 2654, and 2721 through 2728 outline the responsibilities of a responsible party in response to an unauthorized release from a petroleum UST system, and require your compliance with this request.

ELECTRONIC SUBMITTAL OF REPORTS

ACEH's Environmental Cleanup Oversight Programs (LOP and SLIC) require submission of reports in electronic form. The electronic copy replaces paper copies and is expected to be used for all public information requests, regulatory review, and compliance/enforcement activities. Instructions for submission of electronic documents to the Alameda County Environmental Cleanup Oversight Program FTP site are provided on the attached "Electronic Report Upload Instructions." Submission of reports to the Alameda County FTP site is an addition to existing requirements for electronic submittal of information to the State Water Resources Control Board (SWRCB) GeoTracker website. In September 2004, the SWRCB adopted regulations that require electronic submittal of information for all groundwater cleanup programs. For several years, responsible parties for cleanup of leaks from underground storage tanks (USTs) have been required to submit groundwater analytical data, surveyed locations of monitoring wells, and other data to the GeoTracker database over the Internet. Beginning July 1, 2005, these same reporting requirements were added to Spills, Leaks, Investigations, and Cleanup (SLIC) sites. Beginning July 1, 2005, electronic submittal of a complete copy of all reports for all sites is required in GeoTracker (in PDF format). Please visit the SWRCB website for more information on these requirements (http://www.waterboards.ca.gov/water_issues/programs/ust/electronic_submittal/).

PERJURY STATEMENT

All work plans, technical reports, or technical documents submitted to ACEH must be accompanied by a cover letter from the responsible party that states, at a minimum, the following: "I declare, under penalty of perjury, that the information and/or recommendations contained in the attached document or report is true and correct to the best of my knowledge." This letter must be signed by an officer or legally authorized representative of your company. Please include a cover letter satisfying these requirements with all future reports and technical documents submitted for this fuel leak case.

PROFESSIONAL CERTIFICATION & CONCLUSIONS/RECOMMENDATIONS

The California Business and Professions Code (Sections 6735, 6835, and 7835.1) requires that work plans and technical or implementation reports containing geologic or engineering evaluations and/or judgments be performed under the direction of an appropriately registered or certified professional. For your submittal to be considered a valid technical report, you are to present site specific data, data interpretations, and recommendations prepared by an appropriately licensed professional and include the professional registration stamp, signature, and statement of professional certification. Please ensure all that all technical reports submitted for this fuel leak case meet this requirement.

UNDERGROUND STORAGE TANK CLEANUP FUND

Please note that delays in investigation, later reports, or enforcement actions may result in your becoming ineligible to receive grant money from the state's Underground Storage Tank Cleanup Fund (Senate Bill 2004) to reimburse you for the cost of cleanup.

AGENCY OVERSIGHT

If it appears as though significant delays are occurring or reports are not submitted as requested, we will consider referring your case to the Regional Board or other appropriate agency, including the County District Attorney, for possible enforcement actions. California Health and Safety Code, Section 25299.76 authorizes enforcement including administrative action or monetary penalties of up to \$10,000 per day for each day of violation.

Alameda County Environmental Cleanup Oversight Programs (LOP and SLIC)	REVISION DATE: July 20, 2010
	ISSUE DATE: July 5, 2005
	PREVIOUS REVISIONS: October 31, 2005; December 16, 2005; March 27, 2009; July 8, 2010
SECTION: Miscellaneous Administrative Topics & Procedures	SUBJECT: Electronic Report Upload (ftp) Instructions

The Alameda County Environmental Cleanup Oversight Programs (LOP and SLIC) require submission of all reports in electronic form to the county's ftp site. Paper copies of reports will no longer be accepted. The electronic copy replaces the paper copy and will be used for all public information requests, regulatory review, and compliance/enforcement activities.

REQUIREMENTS

- Please **do not** submit reports as attachments to electronic mail.
- Entire report including cover letter must be submitted to the ftp site as a **single portable document format (PDF) with no password protection**.
- It is **preferable** that reports be converted to PDF format from their original format, (e.g., Microsoft Word) rather than scanned.
- **Signature pages and perjury statements must be included and have either original or electronic signature.**
- **Do not password protect the document.** Once indexed and inserted into the correct electronic case file, the document will be secured in compliance with the County's current security standards and a password. **Documents with password protection will not be accepted.**
- Each page in the PDF document should be rotated in the direction that will make it easiest to read on a computer monitor.
- Reports must be named and saved using the following naming convention:

RO#_Report Name_Year-Month-Date (e.g., RO#5555_WorkPlan_2005-06-14)

Submission Instructions

- 1) Obtain User Name and Password
 - a) Contact the Alameda County Environmental Health Department to obtain a User Name and Password to upload files to the ftp site.
 - i) Send an e-mail to deh.loptoxic@acgov.org
 - b) In the subject line of your request, be sure to include "**ftp PASSWORD REQUEST**" and in the body of your request, include the **Contact Information, Site Addresses, and the Case Numbers (RO# available in Geotracker) you will be posting for.**
- 2) Upload Files to the ftp Site
 - a) Using Internet Explorer (IE4+), go to <ftp://alcoftp1.acgov.org>
 - (i) Note: Netscape, Safari, and Firefox browsers will not open the FTP site as they are NOT being supported at this time.
 - b) Click on Page located on the Command bar on upper right side of window, and then scroll down to Open FTP Site in Windows Explorer.
 - c) Enter your User Name and Password. (Note: Both are Case Sensitive.)
 - d) Open "My Computer" on your computer and navigate to the file(s) you wish to upload to the ftp site.
 - e) With both "My Computer" and the ftp site open in separate windows, drag and drop the file(s) from "My Computer" to the ftp window.
- 3) Send E-mail Notifications to the Environmental Cleanup Oversight Programs
 - a) Send email to deh.loptoxic@acgov.org notify us that you have placed a report on our ftp site.
 - b) Copy your Caseworker on the e-mail. Your Caseworker's e-mail address is the entire first name then a period and entire last name @acgov.org. (e.g., firstname.lastname@acgov.org)
 - c) The subject line of the e-mail must start with the RO# followed by **Report Upload**. (e.g., Subject: RO1234 Report Upload) If site is a new case without an RO#, use the street address instead.
 - d) If your document meets the above requirements and you follow the submission instructions, you will receive a notification by email indicating that your document was successfully uploaded to the ftp site.