



West Coast Office
Suite 370
3250 Ocean Park Blvd.
Santa Monica, CA 90405
Phone: 213-452-5078
FAX: 213-450-5787

SOIL AND GROUND WATER INVESTIGATION FOR:


ARATEX SERVICES
FACILITY #516 LOCATED AT
330 CHESTNUT STREET
OAKLAND, CALIFORNIA

AUG 1989

PREPARED BY:
RMT INC.

AUGUST 1989

Mark A. Lyverse
Project Manager/Hydrogeologist



Zoran Batchko, P. E.
Project Engineer

TABLE OF CONTENTS

	<u>Page</u>
1.0 INTRODUCTION	1
1.1 Background	1
1.2 Purpose and Scope	1
2.0 FINDINGS AND CONCLUSIONS	1
3.0 HYDROGEOLOGIC ASSESSMENT	3
3.1 Site Location and Setting	3
3.2 Local Geology and Hydrogeology	3
3.3 Site Geology	3
3.4 Site Hydrogeology	3
3.4.1 Ground Water Occurrence and Flow Direction	3
3.5 Area of Ground Water Use	7
3.6 Laboratory Analyses of Soil Samples	7
3.7 Ground Water Quality	7
4.0 OVERALL ASSESSMENT	10
5.0 REFERENCES	10

LIST OF FIGURES

Figure 1 -- Location of Aratex Facility #516, Oakland California	4
Figure 2 -- Direction of Ground Water Flow, June 16, Aratex #516	5

LIST OF TABLES

Table 3-1 -- Water Table Elevations	6
Table 3-2 -- Analytical Results of Soil Samples	8
Table 3-3 -- Summary of Laboratory Results on Ground Water	9

1622.01:ARAOAK.rpt:RMTcmn





ARATEX SERVICES, Inc.

1834 WALDEN OFFICE SQUARE SUITE #450 SCHAUMBURG, IL 60173-4299 / 312-397-9500

October 23, 1989

Mr. Dennis Byrne
Hazardous Materials Specialist
Alameda County Health Agency
Department of Environmental Health
80 Swan Way, Room 200
Oakland, California 94621

Subject: Report Describing a Site Investigation at Aratex Services, Inc.
330 Chestnut Street, Oakland, California

Dear Mr. Byrne:

Enclosed is the Site Investigation report for the Aratex Services facility in Oakland, California. The report, prepared by RMT, was completed as required by the Alameda County Health Agency to address residual concentrations of diesel fuel remaining in the subsurface following removal of a 2,000 gallon diesel fuel tank.

An update to the report is needed in reference to the statement (page 2) that "Floating product was noted in well RAO-3, but the thickness was not measurable on June 9." Product thickness was subsequently measured on September 13, 1989 and found to be 0.58 feet in this well. The thickness was measured using a clear PVC bailer.

RMT is currently preparing a proposal and work plan for Aratex for the remediation of this floating product. The plan will be sent to you following Aratex approval.

Should you have any questions about the content of this report or any other matter related to this site, please call me at (312) 397-9500.

Sincerely,

Rebecca J. Whitsett
Environmental Engineer

Mark Lyverse
RMT, Project Manager

RJW:uz\ACHADB.516
Encl.

cc: F. Pfizenmayer

42
10/20/89

TABLE OF CONTENTS
(Continued)

List of Appendices

- Appendix A - Field Methodology
- Appendix B - Log of Test Boring and Well Construction
- Appendix C - Laboratory Data
- Appendix D - Well Permits

1.0 INTRODUCTION

what about the piping?

A subsurface investigation into potential diesel contamination of soils and ground water at the Aratex facility at 330 Chestnut Street, Oakland, California, was required by the Alameda County Health Care Services Agency (HCSA). The source of potential contamination was a 2,000 gallon diesel tank that was removed on December 16, 1988. RMT, Inc. (RMT) was retained by Aratex to conduct the subsurface investigation and prepare this documentation report upon completion of initial field activities. A total of four ground water monitoring wells were installed on June 7 and 8, 1989. Ground water levels were measured and water samples were taken on June 9.

1.1 Background

A previous investigation at this site included the collection of two soil samples during removal of the 2,000 gallon tank. Laboratory analyses concluded that one sample, taken from the vent end of the tank contained 6,900 mg/kg Total Petroleum Hydrocarbons as diesel (TPH-D) and 3,000 mg/kg oil and grease (O&G). The second sample, taken from the fill end of the tank contained 8,100 mg/kg of TPH-D and 3,700 mg/kg O&G.

Ground water monitoring and additional soil sampling was allowed by the HCSA in recognition that the tank site was in close proximity to an existing building (Aratex's facility), gas lines, and a sidewalk and that substantive soil removal might result in collapse or damage to these features.

1.2 Purpose and Scope

The purpose of the investigation and this report is to assess and describe the lateral and vertical extent of contamination in the area of the removed underground storage tank and to meet requirements of the HCSA that the investigation be implemented and documented.

RMT's documentation is based on the following:

- Telephone and in-person conversations with the HCSA.
- On-site supervision of drilling activities, geologic logging of the drilled boreholes, collection of soil samples and performing all activities related to ground water monitoring.
- Copies of permits, chain-of-custodies and laboratory results.

2.0 FINDINGS AND CONCLUSIONS

1. The site appears to be located in the Merritt Sand Unit of the East Bay Plain Area. Hickenbottom and Muir (1988) describe this unit as being permeable and comprised of loose, well-sorted, fine to medium grained sand and silt with lenses of sandy clay and clay. The Unit supports an unconfined aquifer, but is not considered a primary source of drinking water by these authors because of its limited area distribution and thickness.

2. Soils encountered during drilling and sampling were predominantly fine to medium grained clayey sands with some clay stringers.
3. Ground water was detected at levels from 8 to 9 feet below ground surface. Ground water elevations may fluctuate in response to seasonal and tidal influences.
4. The local ground water flow direction was found to be to the south or towards the San Francisco Bay Area. Ground water gradients at the time of measurement were in the order of 0.004, southward, towards the Oakland Inner Harbor.
5. All soil samples from borings RAO-1, RAO-2 and RAO-4 showed nondetectable concentrations of diesel fuel range hydrocarbons (TPH-D) and oil and grease (at detection limits of 100 mg/kg). Diesel contamination of 22,529 mg/kg was found in boring RAO-3 at a depth of 8 ft, which was advanced through the former tank pit. The same soil sample from this borehole also showed concentrations of toluene to be 75 ppb, ethylbenzene 840 ppb, and xylene 2700 ppb. Benzene was not detected at a detection limit of 10 mg/kg. Concentrations of oil and grease in soil at 8 ft from RAO-3 were measured at 8200 mg/kg.

The contaminants appear to be localized to the area where the underground storage tank was located. Samples from boring RAO-3 suggest that concentrations of hydrocarbons, BTX&E and oil and grease in the soil decrease substantially with depth and that these contaminants are not detectable in the soils upgradient (ROA-2) or downgradient (RAO-1 and RAO-4) of the tank pit.

- when?
6. Ground water samples obtained from monitoring wells RAO-1, RAO-2 and RAO-4 did not contain detectible levels of total petroleum hydrocarbons or benzene, toluene, ethylbenzene or xylenes. A concentration of 132.8 mg/l of TPH-D and 3.4 ppb of benzene, 0.9 ppb of toluene, 38 ppb ethylbenzene and 86 ppb xylenes was detected in ground water sampled from well RAO-3. (Floating product was noted in well RAO-3, but the thickness was not measurable on June 9.)

132.8 ppm
= 132,800 ppb
TPH-d

Results indicate that ground water directly beneath the former tank pit has been impacted by diesel fuel contamination. Contaminants in the water sample from RAO-3 occur at the water table which is located approximately 1.5 to 2.0 ft. beneath the former pit bottom. As mentioned in the "Background" section, two soil samples collected from the bottom of the pit at the time the tank was removed were contaminated with diesel fuel as well. In reference to the hydraulic gradients and flow direction, discussed in a later section, ground water directly downgradient of the former tank pit has apparently not been impacted from the diesel fuel at the time measurements were made and samples were collected.

3.0 HYDROGEOLOGIC ASSESSMENT

3.1 Site Location and Setting

The Aratex facility is located in Western Alameda County at 330 Chestnut Street in Oakland, California (Figure 1). Topography across the site is generally flat. The facility is located about 2,000 feet north of the Oakland Inner Harbor and about 1 mile east of the San Francisco Bay. The area is generally industrial with some residential areas to the north and east.

3.2 Local Geology and Hydrogeology

The Aratex facility is located in the Merritt Sand Unit of the East Bay Plain Area. According to published information (Hickenbottom and Muir; 1988) the Merritt Sand is a loose well-sorted, fine to medium grained sand and silt with a maximum thickness of about 65 ft. It is permeable, with the permeability decreasing with increasing depth as a result of consolidation.

Ground water occurs in all geologic units in the East Bay Plain area. However, the Merritt Sand contains smaller amounts of ground water than the deeper, older, alluvium and generally only produces enough water for domestic use. Water from the Unit is not considered by the Alameda County Flood Control and Water Conservation District (ACFC) to be a source of drinking water because its relative shallowness and permeability makes it susceptible to surface or near surface sources of contamination (i.e., sewer systems, street, runoff, leaking underground tanks, etc.). ACFC suggests that water from this Unit be limited to use for only non-potable uses, such as lawn and garden irrigation.

3.3 Site Geology

The site geology was evaluated by drilling four soil borings and collecting soil samples at 5-foot intervals. The drilling and soil sampling procedures are described in Appendix A. Holes were drilled using a B-34 Mobile Drill rig. The location of the monitoring wells are shown in Figure 2. The logs of each boring are presented in Appendix B.


Subsurface materials encountered in the soil borings generally consisted of fine-to-medium grained sand, silt, and clay. The sand component of the material encountered was generally well sorted and at times contained some fine gravel. These materials are consistent with the regional geologic information reviewed.

3.4 Site Hydrogeology

3.4.1 Ground Water Occurrence and Flow Direction

Four 2-inch PVC ground water monitoring wells were installed on the property in the locations shown on Figure 2, using the methodology described in Appendix A. Well construction diagrams are presented in Appendix B.

The water table occurs at a depth of approximately 8 to 9 feet below ground surface. Ground water levels were measured at the completion of drilling and well construction on June 9 and on June 16, 1989, and are summarized in Table 3-1. A water table map has been prepared and shows the ground water



QUADRANGLE LOCATION

FIGURE 1
LOCATION OF ARATEX
FACILITY #510,
OAKLAND, CAL.




SOURCE: USGS OAKLAND
 WEST QUADRANGLE MAP,
 7.5 MIN. SERIES.




SCALE: 1"=2000'

	PUR BY: SRC
	DATE: 7/89
	PROJ: 1022.01

LEGEND

-  DIRECTION OF GROUNDWATER FLOW
-  GROUNDWATER WELL
-  11.0 WATERTABLE ELEVATION



SCALE
1" = 20 ft. (Approx.)

FIGURE 2. DIRECTION OF GROUNDWATER FLOW, JUNE 16, 1989, ARATEX #516 SITE, OAKLAND, CAL.


	OWN BY: SRC
	DATE: 7/89
	PROJ. #: 1622.01

FIGURE 2

TABLE 3-1
WATER TABLE ALTITUDES

<u>Well ID</u>	<u>*Reference Elevation</u>	<u>Depth (ft) 06/09/89</u>	<u>Water Table Elevation (ft) 06/09/89</u>	<u>Depth (ft) 06/16/89</u>	<u>Water Table Elevation (ft) 06/16/89</u>
RAO-1	19.08	8.05	11.03	8.17	10.91
RAO-2	19.57	7.78	11.79	8.17	11.40
RAO-3	19.30	8.03	11.27	8.16	11.14
RAO-4	19.30	8.31	10.99	8.47	10.83

* Reference elevation is arbitrary and not related to mean sea level.

beneath the site flows to the south toward the Oakland Inner Harbor of San Francisco Bay. Based on water level measurements obtained on June 16, 1989, a hydraulic gradient of approximately 0.004 existed across the site.

3.5 Area of Ground Water Use

According to published information (Hickenbottom and Muir, 1988), approximately 13 wells exist within a 1 mile radius of the Aratex site. It is not known whether these wells are domestic, industrial, or monitoring wells. Screened intervals for the wells are also unknown.

3.6 Laboratory Analyses of Soil Samples

A total of 12 soil samples were collected for laboratory analyses. All soil samples were obtained from the four soil borings shown on Figure 2. Only one soil sample was collected above the water table from each borehole because the water table was relatively shallow (8 or 9 feet below ground surface). Soil samples were also collected at depths below the ground water table to provide additional information about:

1. Contamination at deeper depths in the aquifer that may have been the result of fluctuating water levels, and
2. Off-site sources that may be or have been contributing to contamination in the tank pit area.

The results of sample analyses for TPH-D and BTX&E are summarized in Table 3-2, and laboratory reports and chain-of-custodian are included in Appendix C. In general, the following conditions were observed:

- Diesel range hydrocarbons, toluene, ethylbenzene, xylene, and oil and grease were detected in samples from boring RAO-3. This boring is located near the center of the tank pit.
- No hydrocarbons, BTX&E or oil and grease were detected in soil samples from borings RAO-1, RAO-2 or RAO-4 (see Table 3-2 for detection limits).

3.7 Ground Water Quality

All four soil borings were completed as ground water monitoring wells. Well permits are shown in Appendix D. Ground water samples were collected from each of the four wells and were analyzed for TPH-D by EPA Method 8015M (modified) and BTX&E by EPA Method 8020. The monitoring wells were sampled in accordance with the procedures outlined in Appendix A. The results of the analyses are summarized below and in Table 3-3; and the original laboratory data sheets are included in Appendix C. In general, the following conditions were observed:

- TPH-D were detected in a ground water sample collected from monitoring well RAO-3. No hydrocarbons were detected in ground water samples from wells RAO-1, RAO-2 and RAO-4.

TABLE 3-2

ANALYTICAL RESULTS OF SOIL SAMPLES

Boring Number	Sample Depth (Feet)	TPH-D ¹ Diesel Range (mg/kg)	Aromatic Volatile Hydrocarbons ² (ug/kg)				Oil ³ and Grease (mg/kg)
			Benzene	Toluene	Ethylbenzene	Xylenes	
RAO-1	5	ND	ND	ND	ND	ND	ND
RAO-1	10	ND	ND	ND	ND	ND	ND
RAO-1	20	ND	ND	ND	ND	ND	ND
RAO-2	5	ND	ND	ND	ND	ND	ND
RAO-2	10	ND	ND	ND	ND	ND	ND
RAO-2	15	ND	ND	ND	ND	ND	ND
RAO-2	20	ND	ND	ND	ND	ND	ND
RAO-3	8	22,529	ND	75	840	2,700	8,200
RAO-3	15	ND	ND	ND	ND	ND	ND
RAO-3	20	3	ND	ND	ND	ND	ND
RAO-4	5	ND	ND	ND	ND	ND	ND
RAO-4	10	ND	ND	ND	ND	ND	ND

1 TPH-D - Total Petroleum Hydrocarbons as diesel; analyses performed by EPA Method 8015M (modified). Detection limits of 2 mg/kg.

ND - Not detected at the limit of detection.

2 Aromatic Volatile Hydrocarbons (BTX&E) analyses performed by EPA Method 8020. Detection limits of 0.3 ug/kg.

3 Oil and grease analyses performed by EPA Method 503. Detection limits of 100 mg/kg.

TABLE 3-3

SUMMARY OF LABORATORY RESULTS ON GROUND WATER

<u>Parameter</u>	<u>Sample Point</u>			
	<u>RAO-1</u>	<u>RAO-2</u>	<u>RAO-3</u>	<u>RAO-4</u>
Total Petroleum Hydrocarbons - as Diesel (mg/l)	ND	ND	132.8	ND
Benzene (ug/l)	ND	ND	3.4	ND
Toluene (ug/l)	ND	ND	0.9	ND
Ethylbenzene (ug/l)	ND	ND	38.0	ND
Xylenes (ug/l)	ND	ND	86.0	ND

ND - Not detected at the limit of detection.

TPH analyses performed by EPA Method 8015M. Minimum detection limits of 0.04 mg/l except for RAO-4 which had a minimum detection limit of 0.57 mg/l.

Benzene, toluene, ethylbenzene and xylenes analyses performed by EPA method 8020. Minimum detection limits of 0.3 ug/l.



- Benzene, toluene, ethybenze and xylenes were detected in a ground water sample collected from monitoring well RAO-3.
- No BTX&E was detected in ground water samples collected from monitoring wells RAO-1, RAO-2, and RAO-4 (detection limits of 0.3 ug/l).

4.0 OVERALL ASSESSMENT

This investigation has shown that both the subsurface soils and ground water in the immediate vicinity of the former underground diesel fuel storage tank contain hydrocarbons in excess of DOHS limits. At the time of this report, it does not appear that ground water approximately 16 feet downgradient from the former tank pit has been impacted by the diesel contamination. Also, ground water upgradient of the pit showed no detectable concentrations of TPH-D or BTX&E. Contamination concentrations in the soils from boring RAO-3 directly beneath the tank pit decreases to non-detectable levels between 8 and 15 ft. below ground surface. This observation indicates that fluctuations in water level that result from nearby tidal changes or seasonal effects or vertical migration of ground water, have not resulted in contamination being transported to deeper soils.

5.0 REFERENCES

Hickenbottom, K., and Muir, Kenneth, 1988, Geohydrology and Ground Water Quality Overview, of the East Bay Plain Area, Alameda County, California, 205(j) Report, Alameda County Flood Control and Water Conservation District, 83 p.

United States Geological Survey, 1980, Oakland West Quadrangle - California, 7.5 minute series topographical map; United States Department of the Interior.

APPENDIX A
FIELD METHODOLOGY

1622.01.ARAOAK.rpt:RMTcmn



Soil Borings

The soil borings were drilled using hollow-stem augers to avoid introducing drilling fluids into the formation and to minimize intraborehole cross-contamination. Logs of each borehole were prepared at the time of drilling and amended later, as necessary. All soil cuttings were drummed in 55-gallon drums and left on-site.

Precautions were taken to minimize cross-contamination between borings. Special cleaning procedures were followed to clean the drill equipment, and split-spoon soil samplers. The drilling equipment was steam-cleaned prior to drilling. In addition, the drilling equipment was steam-cleaned between borings. Water generated from steam cleaning the contaminated borehole was contained as best as possible in 55-gallon drums and left on-site.

The split-spoon soil sampler was cleaned prior to its first use on-site and between samples. Cleaning procedures involved:

- Scraping away soil material with a soils knife;
- Washing with hot water and tri-sodium phosphate (TSP); and
- Rinsing with de-ionized water (twice).

Soil samples were collected at 5-foot intervals during the drilling operation with a split-spoon sampler lined with brass rings. The rings were cleaned in the same manner as described for the sampler. The soil samples were visually examined to classify the subsurface materials.

The monitoring wells were developed by using a bailer as a surge mechanism. Water and sediments were then removed from the wells using the bailer. Water was removed from the well until the turbidity of the water being removed from the well had visually stabilized to a constant relatively turbid free sample. A minimum of 50 gallons of water was removed from each well. Purged water was stored in 55-gallon drums on-site.

The elevation of all the site monitoring wells were vertically surveyed to the nearest 0.01 foot and are referenced to a temporary benchmark. Horizontal locations were determined by taping distances from the building.

Well Installation

Ground water monitoring wells were installed in all four of the borings drilled at the site. The wells were constructed of 2-inch diameter threaded coupling PVC screens and pipe.

The pipe and screens were assembled and lowered into the borehole. The wells had either 17.5 or a 20 foot long screens with 0.010-inch slots. A medium to coarse sand pack was placed approximately 1 foot below to 1 foot above the top of the screen. A 1- to 2-foot bentonite seal was then installed above the sand layer, and the monitoring wells were grouted to within 2 feet of the ground surface. Flush-mount Christy boxes were installed over the wells for protection. These boxes were set in concrete. Diagrams illustrating the completed well installation details are presented in Appendix B.

Ground Water Sampling

Ground water samples were collected from the site monitoring wells by an RMT hydrogeologist and ground water sampling technician. The monitoring wells were sampled several hours following the development of each well. The wells were sampled with a teflon or stainless steel bailer.

APPENDIX B

LOG OF TEST BORINGS AND WELL CONSTRUCTION

1622.01:ARAOAK.rpt:RMTcmn



LEGEND FOR GRAPHIC LOG:

	CLAY (CL OR CH)		SILT (ML OR MH)		SAND (SP OR SW)		GRAVEL (GP OR GW)		SANDSTONE
	SILTY CLAY (CL-ML)		CLAYEY SILT		CLAYEY SAND (SC)		CLAYEY GRAVEL (GC)		SHALE
	SANDY CLAY (CL OR CH)		SANDY SILT (ML OR MH)		SILTY SAND (SM)		SILTY GRAVEL (GM)		CRYSTALLINE ROCK
	GRAVELLY CLAY (CL OR CH)		GRAVELLY SILT (ML OR MH)		GRAVELLY SAND (SP OR SW)		SANDY GRAVEL (GW OR GP)		LIMESTONE
	TOPSOIL		MADE LAND * (FILL)		CONCRETE OR ASPHALT		WASTE MATERIAL*		DOLOSTONE
	CUTTINGS OR GRAB SAMPLE		SPLIT-BARREL SAMPLER		THIN-WALLED TUBE SAMPLER		CORE SAMPLER		

* DETAILS INCLUDED UNDER VISUAL CLASSIFICATION AND GENERAL OBSERVATIONS.

LEGEND FOR WELL CONSTRUCTION:

	WELL CASING		FILTERPACK		GRANULAR BACKFILL		CONCRETE SURFACE SEAL
	WELL SCREEN		BENTONITE SEAL		GROUT		

* SEE RMT FORMS F-17, MONITORING WELL DIAGRAM, FOR CONSTRUCTION DETAILS.

ABBREVIATIONS:

HSA - HOLLOW STEM AUGER

SSA - SOLID STEM AUGER

CR - CLEAR WATER ROTARY

MR - MUD ROTARY

AR - AIR ROTARY

DC - DRIVE CASING

SC - SPIN CASING

SS - 2" SPLIT-BARREL SAMPLER

SS3 - 3" SPLIT-BARREL SAMPLER

ST - 2" THIN-WALLED TUBE SAMPLER

PS - PISTON SAMPLER

AS - AUGER CUTTINGS SAMPLE

RS - ROTARY CUTTINGS SAMPLE

tr. - TRACE

ltf. - LITTLE

f. - FINE

m. - MEDIUM

c. - COARSE

v. - VERY

l. - LIGHT

dk. - DARK

br. - BROWN

gr. - GREY

yl. - YELLOW

gr. - GREEN



LOG OF TEST BORING

F-203 (R 01-87)

BORING NO. RA01
 SHEET NO. 1 OF 1
 PROJECT NO. 1622.01
 INSTALLATION 6/7/89
 SURFACE ELEV. _____
 BOREHOLE DIA. 8 IN.

PROJECT NAME ARATEX - OAKLAND
 LOCATION 3RD & CHESTNUT ST. OAKLAND, CA
 CONTRACTOR ANDERSON GEOTECH.
 DRILLING METHOD HSA

SAMPLING NOTES

INTERVAL NO.	TYPE	RECOVERY		MOISTURE	DEPTH	VISUAL CLASSIFICATION AND GENERAL OBSERVATIONS	GENERAL WELL CONSTRUCT.
		N	IN				
						Fill material, (peat), organic, loose, dark brown.	
5	SS	49	11		5	Very fine to fine SAND, moderate brown, moist.	
10	SS	48	12		10	Medium Clayey SAND, moderate yellowish brown, trace organics, moist.	
					15	Medium SAND, dark-yellowish brown.	
					18	CLAY.	
20	SS	95	12		20	Medium Clayey SAND, dark-yellowish brown, trace organics, soft.	
					25	EOB at about 25.0 ft.	
					30		
					35		

GENERAL NOTES

DATE STARTED 7 JUN 89
 DATE COMPLETED 7 JUN 89
 RIG MOBILE B-34
 CREW CHIEF SWARTOUT
 LOGGED LYVERSE CHECKED _____

WATER LEVEL OBSERVATIONS

WHILE DRILLING 7 9.0 FT.
 AT COMPLETION 7 8.1 FT.
 AFTER DRILLING
 GAVE-IN: DATE/TIME _____ DEPTH _____
 WATER: DATE/TIME 6/8/89@07:45 DEPTH 7.90 FT.



LOG OF TEST BORING

F-203 (R 01-87)

BORING NO. RA02
 SHEET NO. 1 OF 1
 PROJECT NO. 1622.01
 INSTALLATION 6/8/89
 SURFACE ELEV. _____
 BOREHOLE DIA. 8 IN.

PROJECT NAME ARATEX - OAKLAND
 LOCATION 3RD & CHESTNUT ST. OAKLAND, CA
 CONTRACTOR ANDERSON GEOTECH.
 DRILLING METHOD HSA

SAMPLING NOTES

INTERVAL		RECOVERY		MOISTURE		VISUAL CLASSIFICATION AND GENERAL OBSERVATIONS	GENERAL WELL CONSTRUCT.
NO.	TYPE	N	IN	DEPTH			
						Organic (peat) FILL material, dusky brown.	
5	SS	57	12			Fine to medium SAND, moderate yellowish brown, some fine gravel (5mm).	
10	SS	58	12			Same as above, but with some clay. Clayey SAND, moderate brown, some iron stain.	
15	SS	36	12			Above grades to CLAY and SAND, grayish, stiff.	
20	SS	100	10			Same as above.	
						EOB at 27 ft.	

GENERAL NOTES

DATE STARTED 7 JUN 89
 DATE COMPLETED 7 JUN 89
 RIG MOBILE B-34
 CREW CHIEF SWARTOUT
 LOGGED LYVERSE CHECKED _____

WATER LEVEL OBSERVATIONS

WHILE DRILLING 9.0 FT.
 AT COMPLETION 8.1 FT.
 AFTER DRILLING
 GAGE-IN: DATE/TIME _____ DEPTH _____
 WATER: DATE/TIME 6/8/89 07:45 DEPTH 8.00 FT.



LOG OF TEST BORING

F-203 (R 21-37)

BORING NO. RA03
 SHEET NO. 1 OF 1
 PROJECT NO. 1622.01
 INSTALLATION 6/8/89
 SURFACE ELEV. _____
 BOREHOLE DIA. 8 IN.

PROJECT NAME ARATEX - OAKLAND
 LOCATION 3RD & CHESTNUT ST. OAKLAND, CA
 CONTRACTOR ANDERSON GEOTECH.
 DRILLING METHOD HSA

SAMPLING NOTES

INTERVAL NO.	RECOVERY TYPE	RECOVERY MOISTURE		DEPTH	VISUAL CLASSIFICATION AND GENERAL OBSERVATIONS	GENERAL WELL CONSTRUCT.
		N	IN			
				0	FILL material (tank pit). Medium to coarse SAND, brownish to black, little gravel.	
8	SS	67	10	10	Estimated bottom of tank pit (change in auger rotation). Clayey SAND, gray, hydrocarbon odor and staining.	
15	SS	35	8	15	Same as above, but pale yellowish brown, less clay than above.	
20	SS	42	5	20	Medium Clayey SAND, dark yellowish brown, some organic streaks, soft.	
				25	Boring terminated at 24.0 ft.	
				30		
				35		

GENERAL NOTES

DATE STARTED 8 JUN 89
 DATE COMPLETED 8 JUN 89
 RIG MOBILE B-34
 CREW CHIEF SWARTOUT
 LOGGED LYVERSE CHECKED _____

WATER LEVEL OBSERVATIONS

WHILE DRILLING ∇ 10.0 FT.
 AT COMPLETION ∇ _____
 AFTER DRILLING
 GAGE-IN: DATE/TIME _____ DEPTH _____
 WATER: DATE/TIME 6/8/89 12:20 DEPTH 8.35 FT.



LOG OF TEST BORING

F-203 (R 01-87)

BORING NO. RA04
 SHEET NO. 1 OF 1
 PROJECT NO. 1622.01
 INSTALLATION 6/8/89
 SURFACE ELEV. _____
 BOREHOLE DIA. 8 IN.

PROJECT NAME ARATEX - OAKLAND
 LOCATION 3RD & CHESTNUT ST. OAKLAND, CA
 CONTRACTOR ANDERSON GEOTECH.
 DRILLING METHOD HSA

SAMPLING NOTES

INTERVAL NO.	RECOVER TYPE	RECOVER Y MOISTURE		DEPTH
		N	IN	

VISUAL CLASSIFICATION AND GENERAL OBSERVATIONS

GENERAL WELL CONSTRUCT.

INTERVAL NO.	RECOVER TYPE	N	IN	DEPTH	VISUAL CLASSIFICATION AND GENERAL OBSERVATIONS	GENERAL WELL CONSTRUCT.
				0	FILL material, peat, loose, dark brown.	
5	SS	74	10	5	Very fine to fine SAND, moderate brown.	
10	SS	37	8	10	Medium SAND, moderate yellowish brown, some clay. CLAY, stiff, moist.	
				15	Medium SAND, dark yellowish brown.	
				20		
				25		
				27	EOB at 27 ft.	
				30		
				35		

GENERAL NOTES

WATER LEVEL OBSERVATIONS

DATE STARTED 8 JUN 89
 DATE COMPLETED 8 JUN 89
 RIG MOBILE B-34
 CREW CHIEF SWARTOUT
 LOGGED LYVERSE CHECKED _____

WHILE DRILLING 10.0 FT.
 AT COMPLETION _____
 AFTER DRILLING _____
 GAGE IN: DATE/TIME _____ DEPTH _____
 WATER: DATE/TIME 6/8/89 15:20 DEPTH 8.36 FT.

APPENDIX C
LABORATORY DATA

1622 01.ARAOAK.rpt.RMTcmn



ANALYTICAL RESULTS REPORT

RMT, INC.
 3250 Ocean Park Blvd.
 Suite 370
 Santa Monica, Ca. 90405

July 3, 1989
 Client Reference: 1622.01
 TMA Reference: 6607-2
 Sampling Date 6-9-89

Attention: Mark Lyverse

TMA ID	Client ID		Oil & Grease	
-5	F.BLANK	—	<100 mg/kg	—
-6	RA01-5	—	<100 mg/kg	—
-7	RA01-10	—	<100 mg/kg	—
-8	RA01-20	—	<100 mg/kg	—
-9	RA02-5	—	<100 mg/kg	—
-10	RA02-10	—	<100 mg/kg	—
-11	RA02-15	—	<100 mg/kg	—
-12	RA02-20	—	<100 mg/kg	—
-13	RA03-5	—	8200 mg/kg	—
-14	RA03-15	—	<100 mg/kg	—
-15	RA03-20	—	<100 mg/kg	—
-16	RA04-5	—	<100 mg/kg	—
-17	RA04-10	—	<100 mg/kg	—

JUL 05 1989

EPA METHOD 8020
TARGET ANALYTE RESULTS

Client: RMT, INC
Client Sample ID: RA01
TMA/Norcal SAMPLE ID: 6607-2-1

Date Received: 6/09/89
Date Analyzed: 6/20/89

<u>CAS. No</u>	<u>COMPOUND</u>	<u>RESULTS</u> <u>(ug/L)</u>	<u>DETECTION LIMITS</u> <u>(ug/L)</u>
71-43-2	benzene	< <u>0.3</u>	0.3
108-88-3	toluene	< <u>0.3</u>	0.3
100-41-4	ethylbenzene	< <u>0.3</u>	0.3
108-38-3	xylene	< <u>0.3</u>	0.3

C. D. Smith
Analyst

Stadion
Data Release Authorized By

JUL 05 1989

EPA METHOD 8020
 TARGET ANALYTE RESULTS

Client: RMT, INC
 Client Sample ID: RA02
 TMA/Norcal SAMPLE ID: 6607-2-2

Date Received: 6/09/89
 Date Analyzed: 6/20/89

CAS. No	COMPOUND	RESULTS (ug/L)	DETECTION LIMITS (ug/L)
71-43-2	benzene	< 0.3	0.3
108-88-3	toluene	< 0.3	0.3
100-41-4	ethylbenzene	< 0.3	0.3
108-38-3	xylene	< 0.3	0.3

C. A. Smith
 Analyst

Harold Jones
 Data Release/Authorized By

JUL 05 89

ENVIRONMENTAL
 ESTABLISHMENT

EPA METHOD 8020
TARGET ANALYTE RESULTS

Client: RMT, INC
Client Sample ID: RA03
TMA/Norcal SAMPLE ID: 6607-2-3

Date Received: 6/09/89
Date Analyzed: 6/20/89

<u>CAS. No</u>	<u>COMPOUND</u>	<u>RESULTS</u> <u>(ug/L)</u>	<u>DETECTION LIMITS</u> <u>(ug/L)</u>
71-43-2	benzene	<u>3.4</u>	0.3
108-88-3	toluene	<u>0.9</u>	0.3
100-41-4	ethylbenzene	<u>38.</u>	0.3
108-38-3	xylenes	<u>86.</u>	0.3

G. P. Smith
Analyst

Yardines
Data Release Authorized By

JUL 0 5 89

EPA METHOD 8020
TARGET ANALYTE RESULTS

Client: RMT, INC
Client Sample ID: RA04
TMA/Norcal SAMPLE ID: 6607-2-4

Date Received: 6/09/89
Date Analyzed: 6/20/89

<u>CAS. No</u>	<u>COMPOUND</u>	<u>RESULTS (ug/L)</u>	<u>DETECTION LIMITS (ug/L)</u>
71-43-2	benzene	< 0.3	0.3
108-88-3	toluene	< 0.3	0.3
100-41-4	ethylbenzene	< 0.3	0.3
108-38-3	xylenes	< 0.3	0.3

C. P. Smith
Analyst

Hardman
Data Release Authorized By

JUL 0 5 1989

EPA METHOD 8020
TARGET ANALYTE RESULTS

Client: RMT, INC
Client Sample ID: FIELD BLANK
TMA/Norcal SAMPLE ID: 6607-3-5

Date Received: 6/09/89
Date Analyzed: 6/20/89

<u>CAS. No</u>	<u>COMPOUND</u>	<u>RESULTS</u> <u>(ug/L)</u>	<u>DETECTION LIMITS</u> <u>(ug/L)</u>
71-43-2	benzene	< 0.3	0.3
108-88-3	toluene	< 0.3	0.3
100-41-4	ethylbenzene	< 0.3	0.3
108-38-3	xylene	< 0.3	0.3

C. D. Smith
Analyst

Robert Jones
Data Release Authorized By

EPA METHOD 8020
TARGET ANALYTE RESULTS

Client: RMT, INC
Client Sample ID: RA01-5
TMA/Norcal SAMPLE ID: 6607-2-3

Date Received: 6/09/89
Date Analyzed: 6/20/89

<u>CAS. No</u>	<u>COMPOUND</u>	<u>RESULTS</u> <u>(ug/kg)</u>	<u>DETECTION LIMITS</u> <u>(ug/kg)</u>
71-43-2	benzene	< 10	10
108-88-3	toluene	< 10	10
100-41-4	ethylbenzene	< 10	10
108-38-3	xylene	< 10	10

C. Smith
Analyst

[Signature]
Data Release Authorized By

EPA METHOD 8020
TARGET ANALYTE RESULTS

Client: RMT, INC
Client Sample ID: RA01-10
TMA/Norcal SAMPLE ID: 6607-2-7

Date Received: 6/09/89
Date Analyzed: 6/20/89

<u>CAS. No</u>	<u>COMPOUND</u>	<u>RESULTS</u> <u>(ug/kg)</u>	<u>DETECTION LIMITS</u> <u>(ug/kg)</u>
71-43-2	benzene	< 10	10
108-88-3	toluene	< 10	10
100-41-4	ethylbenzene	< 10	10
108-38-3	xylenes	< 10	10

A. S. Smith
Analyst

[Signature]
Data Release Authorized By

JUL 3 5

EPA METHOD 8020
TARGET ANALYTE RESULTS

Client: RMT, INC
Client Sample ID: RA01-20
TMA-Norcal SAMPLE ID: 6607-2-3

Date Received: 6/09/89
Date Analyzed: 6/20/89

<u>CAS. No</u>	<u>COMPOUND</u>	<u>RESULTS</u> (ug/kg)	<u>DETECTION LIMITS</u> (ug/kg)
71-43-2	benzene	< 10	10
108-88-3	toluene	< 10	10
100-41-4	ethylbenzene	< 10	10
108-38-3	xylenes	< 10	10

C. D. Smith
Analyst

David Jones
Data Release Authorized By

EPA METHOD 8020
TARGET ANALYTE RESULTS

Client: RMT, INC
Client Sample ID: RA02-5
TMA/Norcal SAMPLE ID: 6607-1-9

Date Received: 6/09/89
Date Analyzed: 6/20/89

<u>CAS. No</u>	<u>COMPOUND</u>	<u>RESULTS</u> <u>(ug/kg)</u>	<u>DETECTION LIMITS</u> <u>(ug/kg)</u>
71-43-2	benzene	< 10	10
108-88-3	toluene	< 10	10
100-41-4	ethylbenzene	< 10	10
108-38-3	xylenes	< 10	10

A.P. Smith
Analyst

[Signature]
Data Release Authorized By

RECEIVED
JUL 0 5

EPA METHOD 8020
TARGET ANALYTE RESULTS

Client: RMT, INC
Client Sample ID: RA02-10
TMA/Norcal SAMPLE ID: 6607-2-10

Date Received: 5/09/89
Date Analyzed: 6/20/89

<u>CAS. No</u>	<u>COMPOUND</u>	<u>RESULTS</u> <u>(ug/kg)</u>	<u>DETECTION LIMITS</u> <u>(ug/kg)</u>
71-43-2	benzene	< <u>10.</u>	10
108-88-3	toluene	< <u>10.</u>	10
100-41-4	ethylbenzene	< <u>10.</u>	10
108-38-3	xylene	< <u>10.</u>	10

A.D. Smith
Analyst

Phil Jones
Data Release Authorized By

JUL 0 5

RMT, INC

EPA METHOD 8020
TARGET ANALYTE RESULTS

Client: RMT, INC
Client Sample ID: RA02-15
TMA/Normal SAMPLE ID: 6607-2-11

Date Received: 6/09/89
Date Analyzed: 6/20/89

<u>CAS. No</u>	<u>COMPOUND</u>	<u>RESULTS</u> <u>(ug/kg)</u>	<u>DETECTION LIMITS</u> <u>(ug/kg)</u>
71-43-2	benzene	< 10.	10
108-88-3	toluene	< 10.	10
100-41-4	ethylbenzene	< 10.	10
108-38-3	xylene	< 10.	10

A. P. Smith
Analyst

David Jones
Data Release Authorized By

JUL 0 5

EPA METHOD 8020
TARGET ANALYTE RESULTS

Client: RMT, INC
Client Sample ID: RA02-20
TMA/Norcal SAMPLE ID: 6607-2-12

Date Received: 6/09/89
Date Analyzed: 6/21/89

<u>CAS. No</u>	<u>COMPOUND</u>	<u>RESULTS</u> <u>(ug/kg)</u>	<u>DETECTION LIMITS</u> <u>(ug/kg)</u>
71-43-2	benzene	< <u>10.</u>	10
108-88-3	toluene	< <u>10.</u>	10
100-41-4	ethylbenzene	< <u>10.</u>	10
108-38-3	xylene	< <u>10.</u>	10

C.V. Smith
Analyst

[Signature]
Data Release Authorized By

JUL 0 5

EPA METHOD 8020
 TARGET ANALYTE RESULTS

Client: RMT, INC
 Client Sample ID: RA03-8
 TMA/Norcal SAMPLE ID: 6607-2-13

Date Received: 6/09/89
 Date Analyzed: 6/21/89

CAS. No	COMPOUND	RESULTS (ug/kg)	DETECTION LIMITS (ug/kg)
71-43-2	benzene	< 10.	10
108-88-3	toluene	75.	10
100-41-4	ethylbenzene	840.	10
108-38-3	xylene	2700.	10

G. J. [Signature]
 Analyst

[Signature]
 Data Release Authorized By

JUL 05 89
 10
 11
 12
 13
 14
 15
 16
 17
 18
 19
 20
 21
 22
 23
 24
 25
 26
 27
 28
 29
 30
 31
 32
 33
 34
 35
 36
 37
 38
 39
 40
 41
 42
 43
 44
 45
 46
 47
 48
 49
 50
 51
 52
 53
 54
 55
 56
 57
 58
 59
 60
 61
 62
 63
 64
 65
 66
 67
 68
 69
 70
 71
 72
 73
 74
 75
 76
 77
 78
 79
 80
 81
 82
 83
 84
 85
 86
 87
 88
 89
 90
 91
 92
 93
 94
 95
 96
 97
 98
 99
 100
 101
 102
 103
 104
 105
 106
 107
 108
 109
 110
 111
 112
 113
 114
 115
 116
 117
 118
 119
 120
 121
 122
 123
 124
 125
 126
 127
 128
 129
 130
 131
 132
 133
 134
 135
 136
 137
 138
 139
 140
 141
 142
 143
 144
 145
 146
 147
 148
 149
 150
 151
 152
 153
 154
 155
 156
 157
 158
 159
 160
 161
 162
 163
 164
 165
 166
 167
 168
 169
 170
 171
 172
 173
 174
 175
 176
 177
 178
 179
 180
 181
 182
 183
 184
 185
 186
 187
 188
 189
 190
 191
 192
 193
 194
 195
 196
 197
 198
 199
 200
 201
 202
 203
 204
 205
 206
 207
 208
 209
 210
 211
 212
 213
 214
 215
 216
 217
 218
 219
 220
 221
 222
 223
 224
 225
 226
 227
 228
 229
 230
 231
 232
 233
 234
 235
 236
 237
 238
 239
 240
 241
 242
 243
 244
 245
 246
 247
 248
 249
 250
 251
 252
 253
 254
 255
 256
 257
 258
 259
 260
 261
 262
 263
 264
 265
 266
 267
 268
 269
 270
 271
 272
 273
 274
 275
 276
 277
 278
 279
 280
 281
 282
 283
 284
 285
 286
 287
 288
 289
 290
 291
 292
 293
 294
 295
 296
 297
 298
 299
 300
 301
 302
 303
 304
 305
 306
 307
 308
 309
 310
 311
 312
 313
 314
 315
 316
 317
 318
 319
 320
 321
 322
 323
 324
 325
 326
 327
 328
 329
 330
 331
 332
 333
 334
 335
 336
 337
 338
 339
 340
 341
 342
 343
 344
 345
 346
 347
 348
 349
 350
 351
 352
 353
 354
 355
 356
 357
 358
 359
 360
 361
 362
 363
 364
 365
 366
 367
 368
 369
 370
 371
 372
 373
 374
 375
 376
 377
 378
 379
 380
 381
 382
 383
 384
 385
 386
 387
 388
 389
 390
 391
 392
 393
 394
 395
 396
 397
 398
 399
 400
 401
 402
 403
 404
 405
 406
 407
 408
 409
 410
 411
 412
 413
 414
 415
 416
 417
 418
 419
 420
 421
 422
 423
 424
 425
 426
 427
 428
 429
 430
 431
 432
 433
 434
 435
 436
 437
 438
 439
 440
 441
 442
 443
 444
 445
 446
 447
 448
 449
 450
 451
 452
 453
 454
 455
 456
 457
 458
 459
 460
 461
 462
 463
 464
 465
 466
 467
 468
 469
 470
 471
 472
 473
 474
 475
 476
 477
 478
 479
 480
 481
 482
 483
 484
 485
 486
 487
 488
 489
 490
 491
 492
 493
 494
 495
 496
 497
 498
 499
 500
 501
 502
 503
 504
 505
 506
 507
 508
 509
 510
 511
 512
 513
 514
 515
 516
 517
 518
 519
 520
 521
 522
 523
 524
 525
 526
 527
 528
 529
 530
 531
 532
 533
 534
 535
 536
 537
 538
 539
 540
 541
 542
 543
 544
 545
 546
 547
 548
 549
 550
 551
 552
 553
 554
 555
 556
 557
 558
 559
 560
 561
 562
 563
 564
 565
 566
 567
 568
 569
 570
 571
 572
 573
 574
 575
 576
 577
 578
 579
 580
 581
 582
 583
 584
 585
 586
 587
 588
 589
 590
 591
 592
 593
 594
 595
 596
 597
 598
 599
 600
 601
 602
 603
 604
 605
 606
 607
 608
 609
 610
 611
 612
 613
 614
 615
 616
 617
 618
 619
 620
 621
 622
 623
 624
 625
 626
 627
 628
 629
 630
 631
 632
 633
 634
 635
 636
 637
 638
 639
 640
 641
 642
 643
 644
 645
 646
 647
 648
 649
 650
 651
 652
 653
 654
 655
 656
 657
 658
 659
 660
 661
 662
 663
 664
 665
 666
 667
 668
 669
 670
 671
 672
 673
 674
 675
 676
 677
 678
 679
 680
 681
 682
 683
 684
 685
 686
 687
 688
 689
 690
 691
 692
 693
 694
 695
 696
 697
 698
 699
 700
 701
 702
 703
 704
 705
 706
 707
 708
 709
 710
 711
 712
 713
 714
 715
 716
 717
 718
 719
 720
 721
 722
 723
 724
 725
 726
 727
 728
 729
 730
 731
 732
 733
 734
 735
 736
 737
 738
 739
 740
 741
 742
 743
 744
 745
 746
 747
 748
 749
 750
 751
 752
 753
 754
 755
 756
 757
 758
 759
 760
 761
 762
 763
 764
 765
 766
 767
 768
 769
 770
 771
 772
 773
 774
 775
 776
 777
 778
 779
 780
 781
 782
 783
 784
 785
 786
 787
 788
 789
 790
 791
 792
 793
 794
 795
 796
 797
 798
 799
 800
 801
 802
 803
 804
 805
 806
 807
 808
 809
 810
 811
 812
 813
 814
 815
 816
 817
 818
 819
 820
 821
 822
 823
 824
 825
 826
 827
 828
 829
 830
 831
 832
 833
 834
 835
 836
 837
 838
 839
 840
 841
 842
 843
 844
 845
 846
 847
 848
 849
 850
 851
 852
 853
 854
 855
 856
 857
 858
 859
 860
 861
 862
 863
 864
 865
 866
 867
 868
 869
 870
 871
 872
 873
 874
 875
 876
 877
 878
 879
 880
 881
 882
 883
 884
 885
 886
 887
 888
 889
 890
 891
 892
 893
 894
 895
 896
 897
 898
 899
 900
 901
 902
 903
 904
 905
 906
 907
 908
 909
 910
 911
 912
 913
 914
 915
 916
 917
 918
 919
 920
 921
 922
 923
 924
 925
 926
 927
 928
 929
 930
 931
 932
 933
 934
 935
 936
 937
 938
 939
 940
 941
 942
 943
 944
 945
 946
 947
 948
 949
 950
 951
 952
 953
 954
 955
 956
 957
 958
 959
 960
 961
 962
 963
 964
 965
 966
 967
 968
 969
 970
 971
 972
 973
 974
 975
 976
 977
 978
 979
 980
 981
 982
 983
 984
 985
 986
 987
 988
 989
 990
 991
 992
 993
 994
 995
 996
 997
 998
 999
 1000

EPA METHOD 8020
TARGET ANALYTE RESULTS

Client: RMT, INC
Client Sample ID: RA03-15
TMA/Norcal SAMPLE ID: 6607-1-14

Date Received: 6/09/89
Date Analyzed: 6/21/89

<u>CAS. No</u>	<u>COMPOUND</u>	<u>RESULTS</u> <u>(ug/kg)</u>	<u>DETECTION LIMITS</u> <u>(ug/kg)</u>
71-43-2	benzene	< <u>10.</u>	10
108-88-3	toluene	< <u>10.</u>	10
100-41-4	ethylbenzene	< <u>10.</u>	10
108-38-3	xylene	< <u>10.</u>	10

E. D. Smith
Analyst

[Signature]
Data Release Authorized By

RECEIVED
JUL 0 5

EPA METHOD 8020
TARGET ANALYTE RESULTS

Client: RMT, INC
Client Sample ID: RA03-20
TMA/Normal SAMPLE ID: 6607-2-15

Date Received: 6/09/89
Date Analyzed: 6/21/89

<u>CAS. No</u>	<u>COMPOUND</u>	<u>RESULTS</u> <u>(ug/kg)</u>	<u>DETECTION LIMITS</u> <u>(ug/kg)</u>
71-43-2	benzene	< <u>10.</u>	10
108-88-3	toluene	< <u>10.</u>	10
100-41-4	ethylbenzene	< <u>10.</u>	10
108-38-3	xylene	< <u>10.</u>	10

G. V. Smith
Analyst

[Signature]
Data Release Authorized By

JUL 0 3
RMT, INC
WEST COAST

EPA METHOD 8020
TARGET ANALYTE RESULTS

Client: RMT, INC
Client Sample ID: RA04-5
TMA/Norcal SAMPLE ID: 6607-2-16

Date Received: 6/09/89
Date Analyzed: 6/21/89

<u>CAS. No</u>	<u>COMPOUND</u>	<u>RESULTS</u> <u>(ug/kg)</u>	<u>DETECTION LIMITS</u> <u>(ug/kg)</u>
71-43-2	benzene	< 10.	10
108-88-3	toluene	< 10.	10
100-41-4	ethylbenzene	< 10.	10
108-38-3	xylenes	< 10.	10

A. D. Smith
Analyst

David Jones
Data Release Authorized By

JUL 0 3
EPA
LABORATORY

EPA METHOD 8020
TARGET ANALYTE RESULTS

Client: RMT, INC
Client Sample ID: RA04-10
TMA/Norcal SAMPLE ID: 6007-2-17

Date Received: 6/09/89
Date Analyzed: 6/21/89

<u>CAS. No</u>	<u>COMPOUND</u>	<u>RESULTS</u> <u>(ug/kg)</u>	<u>DETECTION LIMITS</u> <u>(ug/kg)</u>
71-43-2	benzene	< 10.	10
108-88-3	toluene	< 10.	10
100-41-4	ethylbenzene	< 10.	10
108-38-3	xylene	< 10.	10

C. D. Smith
Analyst

David Jones
Data Release Authorized By

=====

DATE: 6-14-89
TIME: 10:00 AM
CITY: ...
STATE: ...

*date sampled
6-14-89?*

lab?

METHOD: GC-FID METHOD: 8112

FUEL CALCULATED AS DIESEL

TIME/MODAL I.D.	CUSTOMER I.D.	COMPOUND	RESULTS	MDL
0007-1-1	RA01	DIESEL	0.04 mg/L	0.04 mg/L
0007-1-2	RA02	DIESEL	0.04 mg/L	0.04 mg/L
0007-1-3	RA03	DIESEL	132.8 mg/L	0.04 mg/L
0007-1-4	RA04	DIESEL	0.57 mg/L	0.57 mg/L
0007-1-5	FIELD BLANK	DIESEL	0.04 mg/L	0.04 mg/L
0007-1-6	RA01-5	DIESEL	12 mg/kg	2 mg/kg
0007-1-7	RA01-10	DIESEL	12 mg/kg	2 mg/kg
0007-1-8	RA01-20	DIESEL	12 mg/kg	2 mg/kg
0007-1-9	RA02-5	DIESEL	12 mg/kg	2 mg/kg
0007-1-10	RA01-10	DIESEL	12 mg/kg	2 mg/kg
0007-1-11	RA02-15	DIESEL	12 mg/kg	2 mg/kg
0007-1-12	RA01-20	DIESEL	12 mg/kg	2 mg/kg
0007-1-13	RA01-5	DIESEL	12229 mg/kg	2 mg/kg

JUL 0 5

00070001	00070002	00070003	00070004	00070005
00070006	00070007	00070008	00070009	00070010
00070011	00070012	00070013	00070014	00070015
00070016	00070017	00070018	00070019	00070020

*** SAMPLE # 0007-014 CONTAINED ONLY 1ML OF WATER.
 DETECTION LIMITS ARE HIGHER BECAUSE OF THE LOW VOLUME.

RAW DATA IN CHROMATOGRAM FILE.

ANALYZED BY: *John Deane*

DATA RELEASED BY: *Victoria J. Miller 6-22-87*



1000 1st St NW
 Washington, DC 20001
 Phone (608) 331-4444
 FAX (608) 331-3334

F-268 (R2/88)
 (Use Black Ink Only)

CHAIN OF CUSTODY RECORD

Sample Type: (GW) WW, SW, Soil, Other 005261

Bottles Prepared by: RMT Date/Time: 6/9/89 1420 Office Code: (State)
 Project No: 102201 Client: (RMT) A.C.L.A.N.D #1516

Total Number Of Containers	Container Inventory			Filtered (Yes/No)	Preserved (Code)	Refrigerated (Yes/No)	Code: A - None B - HNO3 C - H2SO4 D - NaOH E - _____	Comments:
	ESTY 46	7PH-2821	02-1-1102					
	X	Y	X					
	X	X	Y					
	X	Y	X					
	X	X	Y					
	X	X	Y					

RMT Lab NO	Yr	Date	Time	Sample Station ID
	89	6/11		RA01
		6/11		RA02
		6/9		RA03
		6/9		RA04
		6/11		Field Blank

SAMPLER	Date/Time	Received by (Sig.)	Date/Time
Relinquished by (Sig.) ① <u>Matt A. Green</u>	<u>6/1/89 1440</u> 6/9/89	② <u>[Signature]</u> Shipper Name & #	<u>6/1/1 1440</u>
Relinquished by (Sig.) ③		④ Shipper Name & #	
Relinquished by (Sig.) ⑤		⑥ Shipper Name & #	

HAZARDOUS ASSOCIATED WITH SAMPLES
RA03 - strong chemical odor

(For Lab Use Only)

Receipt Temp _____ Receipt pH _____
 Client P.O. Number _____
 Subsequent Analysis: _____ (Check)

Seal # _____ at'chd by Recvd. Intact by Seal # _____ at'chd by Recvd. Intact by Date Resubmitted _____

APPENDIX D
WELL PERMITS

1622.01 ARAOAK.rpt.RMTcmn





ALAMEDA COUNTY FLOOD CONTROL AND WATER CONSERVATION DISTRICT

1887 BLISSIDE DRIVE, PLEASANTON, CALIFORNIA 94566 TEL. (415) 384-2600

GROUNDWATER PROTECTION ORDINANCE PERMIT APPLICATION

FOR APPLICANT TO COMPLETE

FOR OFFICE USE

1) LOCATION OF PROJECT 330 Chestnut street, Oakland, California

PERMIT NUMBER 39242, LOCATION NUMBER

CLIENT Name Ararax Services, Inc., Address 1834 Walden Office, Phone (312) 397-9500, City Suite 450, Zip 60173-4299, Schaumburg, Ill.

PERMIT CONDITIONS

Circled Permit Requirements Apply

3) APPLICANT Name RMT, Inc., Suite 370, Address 3250 Ocean Park Blvd, Phone (213) 452-5078, City Santa Monica, CA, Zip 90405

4) DESCRIPTION OF PROJECT Water Well Construction X, Geotechnical Investigation, Cathodic Protection General, Well Destruction Contamination

5) PROPOSED WATER WELL USE Domestic, Industrial, Irrigation, Municipal, Monitoring X, Other

6) PROPOSED CONSTRUCTION Drilling Method: Mud Rotary, Air Rotary, Auger X, Cable, Other

DRILLER'S LICENSE NO. C57554979

WELL PROJECTS Drill Hole Diameter 6 3/4 in., Maximum Casing Diameter 2 in., Depth 40 ft., Surface Seal Depth 5 ft., Number 4

GEOTECHNICAL PROJECTS Number of Borings 2, Maximum Hole Diameter 6 3/4 in., Depth 20 ft.

ESTIMATED STARTING DATE May 1, 1989, ESTIMATED COMPLETION DATE June 15, 1989

I hereby agree to comply with all requirements of this permit and Alameda County Ordinance No. 73-68.

APPLICANT'S SIGNATURE [Signature] Date April 20, 1989

- A. GENERAL 1. A permit application should be submitted so as to arrive at the Zone 7 office five days prior to proposed starting date. 2. Submit to Zone 7 within 60 days after completion of permitted work the original Department of Water Resources Water Well Drillers Report or equivalent for well projects, or drilling logs and location sketch for geotechnical projects. 3. Permit is void if project not begun within 90 days of approval date. B. WATER WELLS, INCLUDING PIEZOMETERS 1. Minimum surface seal thickness is two inches of cement grout placed by tremie. 2. Minimum seal depth is 50 feet for municipal and industrial wells or 20 feet for domestic, irrigation, and monitoring wells unless a lesser depth is specially approved. C. GEOTECHNICAL. Backfill bore hole with compacted cuttings or heavy bentonite and upper two feet with compacted material. In areas of known or suspected contamination, tremied cement grout shall be used in place of compacted cuttings. D. CATHODIC. Fill hole above anode zone with concrete placed by tremie. E. WELL DESTRUCTION. See attached.

Approved [Signature] Date 24 Apr 89, Wyman Hong