

Rec'd 2/27/01

QUARTERLY GROUND WATER
SAMPLING AND ANALYSIS

2075 WILLIAMS STREET
SAN LEANDRO
CALIFORNIA

FOR

BLUE WATER SERVICES, INC.
OAKLAND
CALIFORNIA



FEBRUARY 7, 2001
99-ENV187E



February 7, 2001
99-ENV187E

Mr. Chris Kirschenheuter
Blue Water Services, Inc.
727 77th Avenue
Oakland, California 94621

Subject: Quarterly Ground Water Sampling and Analysis Report
2075 Williams Street
San Leandro, California 94577

Dear Mr. Kirschenheuter:

This report describes the Quarterly Ground Water Sampling and Analysis at the site located at 2075 Williams Street, San Leandro, California.

One of the four copies is for your file. The other three copies should be forwarded to Roger Brewer (Regional Water Quality Control Board), Eva Chu (Alameda County Environmental Health) and Michael Bakaldin (City of San Leandro). Their addresses can be found on the site contacts page in the report.

Should you have any questions regarding this report, please contact the undersigned.

Sincerely,

Basics Environmental

A handwritten signature in black ink, appearing to read "Donovan G. Tom", written over a circular scribble.

Donavan G. Tom, M.B.A., R.E.A.
Principal Consultant

GW.LTR

SITE CONTACTS

Site Name: Former Freight Terminals Facility

Site Address: 2075 Williams Street
San Leandro, California 94577

Owner: Chris Kirschenheuter
Bluewater Services Inc.
727 77th Avenue
Oakland, California 94621
(800) 536-6702

Owner's Consultant: Basics Environmental
116 Glorietta Boulevard
Orinda, California 94563
(925) 258-9099

Project Manager: Donovan G. Tom

Former Owner: Michael D. Kevitch
Watkins Motor Lines, Inc.
1144 W. Griffin Road
Lakeland, Florida 33804-5002

Former Owner's Consultant: Atlantic Geosciences, Inc.
1300 S. Rossiter Terrace
Watkinsville, Georgia 30677
(706) 310-0319

Regulatory Oversight:

1. Roger Brewer
Regional Water Quality Control Board
San Francisco Bay Region
1515 Clay Street, Suite 1400
Oakland, California 94612
(510) 622-2374
2. Eva Chu
Alameda County
Environmental Health Department
1131 Harbor Bay Parkway, 2nd Floor
Alameda, California 94502
(510) 567-6770
3. Michael Bakaldin
City of San Leandro
San Leandro Environmental Services
835 East 14th Street, Suite 200
San Leandro, California 94577
(510) 577-3319 ext. 31

TABLE OF CONTENTS

PROFESSIONAL CERTIFICATION

1.0	INTRODUCTION.....	1-1
1.1	Purpose of Investigation.....	1-1
1.2	Background.....	1-1
1.3	Site Geology and Hydrogeology.....	1-3
2.0	GROUND WATER SAMPLING.....	2-1
2.1	Field Activities.....	2-1
3.0	CHEMICAL ANALYSES AND RESULTS.....	3-1
3.1	Chemical Analyses.....	3-1
3.2	Analytical Results.....	3-1
	Table 1: Ground Water Monitoring Data.....	3-2
4.0	FINDINGS.....	4-1
4.1	Discussion	4-1

List of Drawings

Drawing 1: Site Location

Drawing 2: Site Plan Showing Monitoring Well Location

Drawing 3: Ground Water Sample Analytical Results

Appendices

APPENDIX A: Field Documents

APPENDIX B: Laboratory Analytical Results and Chain of Custody

PROFESSIONAL CERTIFICATION

REPORT
QUARTERLY GROUND WATER
SAMPLING AND ANALYSIS
BLUEWATER SERVICES, INC.
2075 WILLIAMS STREET
SAN LEANDRO, CALIFORNIA
99-ENV187E
FEBRUARY 7, 2001

This report has been prepared by the staff of Basics Environmental (Basics) under the professional supervision of the Principal Consultant whose seal and signature appears hereon. The findings, interpretations of data, recommendations, specifications or professional opinions are presented within the limits prescribed by available information at the time the report was prepared, in accordance with generally accepted professional engineering and geologic practice and within the requirements by the Client. There is no other warranty, either expressed or implied.

The data and findings of this report are based on the data and information obtained from the agreed upon scope of work between Basics and the Client. Because contamination is not necessarily evenly distributed across the property's soils and ground water, it can easily remain undetected. Additional scope of services (at greater cost) may or may not disclose information which may significantly modify the findings of this report. We accept no liability on completeness or accuracy of the information presented and or provided to us, or any conclusions and decisions which may be made by the Client or others regarding the subject site.

This report was prepared solely for the benefit of Basic's Client. Basics consents to the release of this report to third parties involved in the evaluation of the property for which the report was prepared, including without limitation, lenders, title companies, public institutions, attorneys, and other consultants. However, any use of or reliance upon this report shall be solely at the risk of such party and without legal recourse against Basics, or its subcontractors, affiliates, or their respective employees, officers, or directors, regardless of whether the action in which recovery of damage is sought is based upon contract, tort (including the sole, concurrent or other negligence and strict liability of Basics), statute or otherwise. This report shall not be used or relied upon by a party that does not agree to be bound by the above statements.



Donovan G. Tom, M.B.A., R.E.A. II
Principal Consultant

1.0 INTRODUCTION

1.1 Purpose of Investigation

Basics Environmental (Basics) has performed this Ground Water Well Monitoring for Blue Water Services, Inc. pursuant to our letter of engagement signed January 16, 2001. The "subject site" is at 2075 Williams Street, San Leandro, California (See Drawing 1).

1.2 Background

On June 23 1995, a Phase I Environmental Site Assessment was performed by Blymer Engineers for Freight Terminals, Inc. Potential environmental concerns were indicated at the property located at 2075 Williams Street in San Leandro, CA. As a result, Blymer Engineers performed a Subsurface Investigation which included the drilling of four soil borings (B-1 through B-4) by geoprobe and the collection of both soil and ground water samples. Ground water was encountered at an approximate depth of 16 feet in each of the borings. Two of the ground water samples were selected for analytical testing. Both ground water samples detected the presence of Trichloroethylene (TCE) and Tetrachloroethylene (PCE). The concentrations were elevated along the eastern boundary of the site which is presumed to be the up gradient portion of the site. The source of the TCE and PCE was not known but was thought to be from an off-site source.

On February 5, 1997 Atlantic Geoscience, Inc. (AGI) performed an preliminary investigation which included the drilling of six additional soil borings (SB-1 through SB-6) by geoprobe and the collection of both soil and ground water samples to further evaluate the possible source and extent of contamination at the site. Five of the six borings were converted to ground water monitoring wells (MW-1, MW-2, MW-3, MW-4 and MW-6). The investigation determined that the direction of ground water flow was to the west, towards the San Francisco Bay at a depth of approximately 15 feet. The plume was found to extend beyond the property boundaries in both the up-gradient and down gradient directions. Soils were analyzed and found to contain low concentrations of both PCE and TCE with the most elevated concentrations detected up gradient from the site property. However, the most elevated PCE and TCE concentrations in the ground water were detected near the center of the site. The report concluded that the origin of the source for the contaminants was unknown and that a more thorough investigation would be required.

AGI submitted a second work plan to the Regional Water Quality Control Board (RWQCB). This plan included a review of data from the adjacent PRINTPAC property, located down gradient from the site. The PRINTPAC data indicated that the extent of the plume was near the center of their property and that the ground water gradient was also generally to the west. In addition, the PRTNTPAC data indicated that the ground water velocity was approximately 1 ft/day. AGI then submitted a revised work plan to further evaluate the horizontal and vertical extent of the contaminant plume. This report is a summary of the second investigation.

On November 30, 1998, AGI performed additional investigation under an approved work plan submitted to the RWQCB. This investigation included the drilling of four additional geoprobe wells and the collection of both soil and ground water samples at various depths. Two borings (SB-11 and SB-13) were drilled on the adjacent up gradient property (Crane Valve Co.) with two borings (SB-10 and SB-12) drilled on the Freight Terminals property. One of the four borings was converted to a ground water monitoring well (MW-10). Prior to drilling, the drilling materials were cleaned using an Alconox solution. As the drilling advanced, soil samples were collected at 5', 10', and 15' intervals by use of a previously cleaned tube sampler and described by a site geologist. Borings SB-10 and SB-11 were drilled to an approximate depth of 50 feet while borings B-12 and B-13 were drilled to an approximate depth of 18 feet. Water samples were collected from each of the borings at a depth of 18 feet. In addition a water sample from borings B-12 and B-13 were also collected at depths of 33 feet and 50 feet. After drilling operations, the borings were sealed with bentonite and a concrete plug was place at the surface. In addition to the drilling program, AGI also collected ground water samples from the existing wells MW-3, MW-4, and MW-6 to evaluate the contaminant plume shape and change over time.

In June and September 2000, AGI implemented an interim remedial action plan under an approved work plan submitted to the RWQCB. This plan included the drilling of seven additional geoprobe wells (SB-3a, SB-10a, SB-14, SB-15, SB-15a, SB-16 and SB-16a) and the collection of both soil and ground water samples at various depths. All of the seven of the borings were converted to ground water monitoring wells (MW-3a, MW-10a, MW-14, MW-15, MW-15a, MW-16 and MW-16a). MW-3a, MW-10a, MW-15a and MW-16a are 1-inch wells specifically installed to address the impact to ground water within the deeper sand zone at the subject site. In addition, 19 passive vapor extraction wells were installed in a perimeter surrounding the terminal building

where the bulk of the contaminants appear to be located. The passive wells were constructed using slotted 2-inch PVC pipe from a depth of 41 feet to 42 feet with 31 feet the most common. However, in vapor well/monitoring MW-15 the sand was encountered at a depth of 42 to 59 feet. As such the vapor well was extended to a depth of 60 feet in this location. A 1/4-inch vapor vent was installed to allow the vapors to discharge.

1.3 Site Geology and Hydrogeology

The site is located San Francisco Bay region approximately 3000 ft. east of San Francisco Bay. The area is characterized by a flat lying terrain with a relief on the order of 50 feet (elev. 0 + to elev. 50 ±). The site is at approximate elev. 20. The land slopes to the south and southwest towards San Francisco Bay.

The San Francisco Bay area is a northwest-southeast trending region within the Coast Range Province. Rocks within the region range from Jurassic aged sedimentary, metamorphic, and plutonic basement rocks to Holocene alluvium. The geologic structure of the region is controlled by several fault systems. The San Andreas system is located on the western side of the bay while the Hayward system is on the east side of the bay. These faults are a result of the tectonic forces that uplifted the Coast Range and dropped the section now covered by San Francisco Bay and associated alluvium deposits.

The site is located on Quaternary Alluvium. This Alluvium includes the Temescal Formation overlying the San Antonio Formation. These formations generally consist of unconsolidated gravel, sand and clay. Soils at the site include the Danville silty clay loam. Ground water in the area is a part of the San Leandro Cone Subarea. The direction of ground water flow is usually to the west or southwest towards San Francisco Bay under unconfined conditions.

The materials encountered in the borings varied from location to location. In general the materials included dark gray, dark brown and medium brown slightly silty clay to approximately 10 feet. A shallow sand lense was encountered in MW-4 from 10 to 19.5 feet; MW-6, MW-10, and MW-11 from 27 to 28 feet; MW-13 from the surface to a depth of at least 15 feet; MW-15 from 10 to 59 feet. A deeper sand lense was encountered MW-3a from 50 to 56 feet; MW-10a from 28 to 42 feet; MW-6a from 30-42 feet;. Clay was then encountered in the borings.

Ground water historically has been encountered at an approximate depth of 12 to 15 feet in each boring. The top of each well was surveyed in 1997 as to relative elevation based on an assigned instrument elevation of 100 ft. The ground water gradient was calculated by AGI in 1997 and found to flow to the west at a gradient of 0.67 ft/ft.

2.0 GROUND WATER SAMPLING

2.1 Field Activities

On January 25 and January 29, 2001, the following scope of work was completed.

- The ground water in wells MW-3, MW-3A, MW-6, MW-10, MW-10A, MW-14, MW-15, MW-15A, MW-16 and MW-16A was monitored for floating product, and the depth to water in the well was measured with an optical interface probe and recorded on well gauging data sheets, which are included in Appendix A.
- Prior to sampling, the wells were purged using PVC pipes connected to a truck mounted vacuum pump. At least three casing volumes were extracted from each well. Temperature, pH, conductivity, and visual observations of the ground water for the well was recorded on a well monitoring data sheet, which is included in Appendix A.
- A ground water sample was collected from each of the wells and submitted to McCampbell Analytical, a California-certified laboratory, for petroleum hydrocarbon analysis to quarterly reporting requirements.

The ground water samples were collected using disposable bailers. The water samples were transferred from the bailers into appropriate pre-preserved containers supplied by the analytical laboratory. The samples were labeled to include the job number, sample identification, collection date and time, analysis, preservation (if any), and the sample collector's initials. The water samples were then placed in a cooler, maintained at 4° C for transport to the laboratory. Once collected in the field, the samples were maintained under chain of custody until delivered to the laboratory.

The chain of custody document includes the job number, type of preservation, if any, analysis requested, sample identification, date and time collected, and sample collector's name. The chain of custody was signed and dated (including time of transfer) by each person who received or surrendered the sample, beginning with the field personnel and ending with the laboratory personnel.

3.0 CHEMICAL ANALYSES AND RESULTS

3.1 Chemical Analyses

The ground water sample taken from the monitoring well was analyzed for the following:

- Volatile Halocarbons (California EPA Method 8010).

3.2 Analytical Results

Results of chemical analyses on ground water sample collected on January 25, 2001 and January 29, 2001 are presented in **boldface** type in Table 1, along with previous results. Certified laboratory reports are presented in Appendix B, including chain-of-custody record data.

TABLE I GROUNDWATER MONITORING DATA
2077 WILLIAMS STREET, SAN LEANDRO, CALIFORNIA, 2001

Well No.	Screen (ft)	Date	Casing		Depth to Groundwater		Concentration ($\mu\text{g/L}$)	
			Elevation (ft msl)		Water (ft)	Elevation (ft msl)	Tetrachloroethene (PCE)	Trichloroethene (TCE)
B-1	-	Feb-97	NM		12.19		ND	ND
B-2	-	Feb-97	NM		12.16		ND	ND
MW-3	15-30	Feb-97	NM		15.08		5,400	58
		Nov-98	NM		-		2,000	110
		May-00	NM		-		1,000	160
		Sep-00	NM		25		ND	ND
		Jan-01	NM		16.36		880	120
MW-3A	2-60	Sep-00	NM		60		15	ND
		Jan-01	NM		15.98		ND	ND
MW-4	13-28	Feb-97	NM		12.69		1,900	130
		Nov-98	NM		-		510	180
		Jan-01	NM		-		NS	NS
MW-6	13-27	Feb-97	NM		11.86		65	10
		Nov-98	NM		-		53	13
		May-00	NM		-		44	18
		Sep-00	NM		25		38	19
		Jan-01	NM		13.53		35	20
B-10		Nov-98	NM		33		4,600	120
MW-10	10-25	May-00	NM		-		7,300	590
		Sep-00	NM		25		11,000	ND
		Jan-01	NM		15.29		4,100	520
B-10A		Nov-98	NM		50		150	ND
MW-10A	2-42	Sep-00	NM		40		390	ND
		Jan-01	NM		15.47		830	110
B-11	-	Nov-98	NM		33		200	49
B-12		Nov-98	NM		16		ND	90
B-13		Nov-98	NM		14.7		240	ND
MW-14	10-25	May-00	NM		16		36	75
		Sep-00	NM		50		71	118
		Jan-01	NM		15.61		48	74

TABLE 1 (CONT.) GROUNDWATER MONITORING DATA
2077 WILLIAMS STREET, SAN LEANDRO, CALIFORNIA, 2001

Well No.	Screen (ft)	Date	Casing		Depth to Groundwater		Concentration ($\mu\text{g/L}$)	
			Elevation (ft msl)	Water (ft)	Elevation (ft msl)	Tetrachloroethene (PCE)	Trichloroethene (TCE)	
SB-15 MW-15	?-60	Feb-97	NM	16	--	1,000	160	
		Sep-00	NM	60	--	130	9.4	
		Jan-01	NM	16.47	--	310	38	
MW-15A	?-36	Sep-00	NM	40	--	1,000	160	
		Jan-01	NM	16.69	--	410	69	
MW-16	10-25	May-00	NM	16	--	10	ND	
		Sep-00	NM	25	--	90	ND	
		Jan-01	NM	13.91	--	38	ND	
MW-16A	?-38	Sep-00	NM	40	--	100	ND	
		Jan-01	NM	13.82	--	3,600	160	
Trip		Feb-97				<0.5	<0.5	
Blank		Nov-98				<0.5	<0.5	

B-# Grab water samples from boring.
 MW-# Ground water sample from monitoring well.
 ND Analyte NOT DETECTED at or above the reporting limit (<0.5)
 NS Not sampled.
 NM Not measured.
 -- Not analyzed.
 $\mu\text{g/L}$ Micrograms per liter.
 ft msl Feet relative to mean sea level.

4.0 FINDINGS

4.1 Discussion

According to AGI, the source of the PCE contamination appears to be from a pre-1977 metal plating operation conducted within a former building located at the subject site. In addition, AGI believes the plume appears to have sunk by gravity downward into a coarse sand horizon.

Source Identification - Based on the soil test borings within the previous investigations, no substantial impact to the shallow subsurface soil has been identified. However, analytical results from shallow surface soil samples collected within the vicinity of MW-4, MW-10 and MW-13 indicate the highest concentrations of PCE (0.420 mg/kg, 0.690 mg/kg and 0.400 mg/kg, respectively). Based on this data, no significant amount of residual source material appear to exist within the vadose zone at the subject site. These levels may have decreased over time due to natural degradation or have sunk through the subsurface.

According to AGI, MW-10 may represent the original area of release due to the significant concentration of PCE (300 mg/kg) found within the soil at 15 feet below ground surface. However, MW-10 soil concentrations between 1 and 10 feet below ground surface were similar to those concentrations detected in the vicinity of MW-4 and MW-13. Due to the saturated zone fluctuating from 12 to 15 feet below ground surface, the elevated levels of PCE within the soil sample collected within MW-10 at 15 feet below ground surface may be due to the influence of the PCE ground water plume.

This reasoning suggests that the original area of release may be a combination of impacts to the subsurface within the vicinity of MW-4, MW-10 and MW-13. MW-4 and MW-13 are located within the adjacent up gradient site (Crane Valve Services). Since comparable levels of PCE have been discovered within the shallow subsurface soil samples collected within the adjacent up gradient site suggest a high probability that the original area of release may be a combination of impacts to the subsurface from the subject site and Crane Valve Services. As such, Crane Valve Services may also be a responsible party liable for ground water remediation.

According to AGI, the shape of the plume suggests that the ground water flow is not a large driving force to move the contaminant plume. In addition, AGI believes the plume appears to radiating outward primarily by dispersion. Based on the documents reviewed, significant levels of

PCE ($>200\mu\text{g/L}$) have been detected within MW-3, MW-4, MW-10, MW-11, MW-13, W-3, W-5, and W-6. The highest levels of PCE ($>2000\mu\text{g/L}$) were detected in MW-3, MW-10 and W-5.


W-3, W-5 and W-6 are located on the adjacent down gradient site (James River Site). Additional breakdown components of PCE (TCE, DCA and VC) were also detected within the down gradient wells (W-3, W-5 and W-6), however, analytical results from soil samples collected at the adjacent down gradient James River site have not detected any levels of PCE.

At the time of these reports 1995-1998, the migration of ground water impacted with PCE and its derivatives were attributed to up gradient sources (1964 Williams Street and Caterpillar Tractor), however, recent ground water data suggests off-site migration of the PCE plume is generated from the vicinity of MW-4, MW-10 and MW-13. In addition, this data suggests the plume is influenced by the ground water flow.

The most recent ground water data collected (January 2001) has shown significant levels of PCE ($>200\mu\text{g/L}$) have been detected within MW-3, MW-10, MW-10a, MW-15, MW-15a and MW-16a. The highest level of PCE ($4,100\mu\text{g/L}$) was detected only in MW-10. However, high levels of PCE ($3,600\mu\text{g/L}$) were also detected in MW-16a. Recent off site ground water data was not available.

Interim Remedial Actions - Based on the information reviewed, the residual source material (original area of release to soil) has decreased over time due to natural degradation or has sunk through the subsurface. The ground water data suggest the passive remediation system appears to be decreasing the concentrations of PCE in the ground water. Based on this information, Basics recommends continued quarterly ground water monitoring to evaluate the progress of the passive ground water remediation system.

DATE 2/5/01
REVIEWED BY
PREPARED BY DGT



Site Location



Quarterly Ground Water Sampling and Analysis
2075 Williams Street
San Leandro, California


PROJECT NO.
99-ENV187E

DRAWING NO.
1

DATE 2/5/01

REVIEWED BY

PREPARED BY DGT



Ground Water Monitoring Well Locations



Quarterly Ground Water Sampling and Analysis
2075 Williams Street
San Leandro, California

PROJECT NO.
99-ENV187E

DRAWING NO.

2


TBLCK (6/28/92)

DATE 2/5/01

REVIEWED BY

DGT

PREPARED BY



PCE Concentrations in Ground Water ($\mu\text{g/L}$)



Quarterly Ground Water Sampling and Analysis
2075 Williams Street
San Leandro, California

PROJECT NO.
99-ENV187E

DRAWING NO.
3

TBLCK (6/28/92)

APPENDIX A

WELL GAUGING DATA

Project # 010125-171 Date 1/25/01 Client Basic Environmental

Site 2075 Williams St. San Leandro Ca

Well ID	Well Size (in.)	Sheen / Odor	Depth to Immiscible Liquid (ft.)	Thickness of Immiscible Liquid (ft.)	Volume of Immiscibles Removed (ml)	Depth to water (ft.)	Depth to well bottom (ft.)	Survey Point: TOB or TOC
MW-3	2"					16.36	29.31 ^{25'}	
MW-3A	1"					15.98 59.68	60'	
MW-6	2"					13.53	26.46 ^{25'}	
MW-10	2"					15.29	29.55 ^{25'}	
MW-10A	1"					15.47	42.28 ^{40'}	
MW-14	2"					15.61	24.12 ^{50'}	
MW-15	2"					11.97 59.69	60'	
MW-15A	1"					16.69	35.69 ^{40'}	
MW-16	2"					13.91	24.61 ^{25'}	
MW-16A	1"					13.82	37.81 ^{40'}	→

WELL MONITORING DATA SHEET

Project #: 010125-A1	Client: Basic Environmental
Sampler: DA	Start Date: 1/25/01
Well I.D.: MW-3	Well Diameter: <u>2</u> 3 4 6 8
Total Well Depth: 29.31	Depth to Water: 16.36
Before: After:	Before: After:
Depth to Free Product:	Thickness of Free Product (feet):
Referenced to: <u>PVC</u> Grade	D.O. Meter (if req'd): YSI HACH

Purge Method:

- Bailer
- Disposable Bailer
- Middleburg
- Electric Submersible
- Waterra
- Peristaltic
- Extraction Pump
- Other _____

Sampling Method:

- Bailer
- Disposable Bailer
- Extraction Port
- Dedicated Tubing
- Other: _____

2	(Gals.) X	3	=	10	Gals.
1 Case Volume		Specified Volumes		Calculated Volume	

Well Diameter	Multiplier	Well Diameter	Multiplier
1"	0.04	4"	0.65
<u>2</u>	0.16	6"	1.47
3"	0.37	Other	radius ² * 0.163

Time	Temp (°F)	pH	Cond.	Turbidity	Gals. Removed	Observations
1202	65.4	7.7	507	>200	2	
1206	66.3	6.9	511	>200	4	
1210	66.0	6.9	513	>200	6	

Did well dewater? Yes No Gallons actually evacuated: 6

Sampling Time: 1215 Sampling Date: 1/25/01

Sample I.D.: MW-3 Laboratory: McCambell

Analyzed for: TPH-G BTEX MTBE TPH-D Other: VOC's By 8010

Equipment Blank I.D.: @ Time Duplicate I.D.:

Analyzed for: TPH-G BTEX MTBE TPH-D Other:

D.O. (if req'd):	Pre-purge:	mg/L	Post-purge:	mg/L
ORP (if req'd):	Pre-purge:	mV	Post-purge:	mV

WELL MONITORING DATA SHEET

Project #: 010125-A1	Client: Basic Environmental
Sampler: DA	Start Date: 1/25/01
Well I.D.: MW-6	Well Diameter: <u>2</u> 3 4 6 8
Total Well Depth: 26.46	Depth to Water: 13.53
Before: After:	Before: After:
Depth to Free Product:	Thickness of Free Product (feet):
Referenced to: <u>PVC</u> Grade	D.O. Meter (if req'd): YSI HACH

Purge Method:

- Bailer
- Disposable Bailer
- Middleburg
- Electric Submersible
- Waterra
- Peristaltic
- Extraction Pump
- Other _____

Sampling Method:

- Bailer
- Disposable Bailer
- Extraction Port
- Dedicated Tubing
- Other: _____

2.0	(Gals.) X	3	=	6	Gals.
1 Case Volume		Specified Volumes		Calculated Volume	

Well Diameter	Multiplier	Well Diameter	Multiplier
2"	0.04	4"	0.65
<u>3"</u>	0.16	6"	1.47
3"	0.37	Other	radius ² * 0.163

Time	Temp (°F)	pH	Cond.	Turbidity	Gals. Removed	Observations
955	69.5	6.6	966	>200	2	
958	66.2	6.7	980	>200	4	
1001	65.0	6.7	98.4	>200	6	

Did well dewater? Yes No Gallons actually evacuated: 6

Sampling Time: 1005 Sampling Date: 1/25/01

Sample I.D.: MW-6 Laboratory: Mc Campbell

Analyzed for: TPH-G BTEX MTBE TPH-D Other: VOC's By 8010

Equipment Blank I.D.: @ _____ Time Duplicate I.D.:

Analyzed for: TPH-G BTEX MTBE TPH-D Other:

D.O. (if req'd):	Pre-purge:	mg/L	Post-purge:	mg/L
ORP (if req'd):	Pre-purge:	mV	Post-purge:	mV

WELL MONITORING DATA SHEET

Project #: 010125-A1	Client: Basic Environmental
Sampler: DL	Start Date: 1/25/01
Well I.D.: MW-10	Well Diameter: <input checked="" type="radio"/> 3 <input type="radio"/> 4 <input type="radio"/> 6 <input type="radio"/> 8
Total Well Depth: 24.55	Depth to Water: 15.29
Before: After:	Before: After:
Depth to Free Product:	Thickness of Free Product (feet):
Referenced to: <input checked="" type="radio"/> PVC <input type="radio"/> Grade	D.O. Meter (if req'd): YSI HACH

Purge Method:	Sampling Method: Bailer
Bailer	Disposable Bailer <input checked="" type="checkbox"/>
Disposable Bailer <input checked="" type="checkbox"/>	Extraction Port
Middleburg	Dedicated Tubing
Electric Submersible	Other: _____
Watera	
Peristaltic	
Extraction Pump	
Other: _____	

1.4	(Gals.) X	3	=	4.2	Gals.
I Case Volume		Specified Volumes		Calculated Volume	

Well Diameter	Multiplier	Well Diameter	Multiplier
1"	0.04	4"	0.63
<input checked="" type="radio"/> 3"	0.16	6"	1.47
3"	0.37	Other	radius ² * 0.163

Time	Temp (°F)	pH	Cond.	Turbidity	Gals. Removed	Observations
1135	64.1	6.8	835	< 200	1.5	
1140 1140	65.1	6.9	773	< 200	3	
1145	65.0	6.9	775	< 200	4.5	

Did well dewater? Yes No Gallons actually evacuated: 4.5

Sampling Time: 1150 Sampling Date: 1/25/01

Sample I.D.: MW-10 Laboratory: Mc Campbell

Analyzed for: TPH-G BTEX MTBE TPH-D Other: VOC's by 8010

Equipment Blank I.D.: @ Time Duplicate I.D.:

Analyzed for: TPH-G BTEX MTBE TPH-D Other:

D.O. (if req'd):	Pre-purge:	mg/L	Post-purge:	mg/L
ORP (if req'd):	Pre-purge:	mV	Post-purge:	mV

WELL MONITORING DATA SHEET

Project #: 010125-A1	Client: Basic Environmental
Sampler: DA	Start Date: 1/25/01
Well I.D.: MW-14	Well Diameter: <input checked="" type="radio"/> 3 <input type="radio"/> 4 <input type="radio"/> 6 <input type="radio"/> 8
Total Well Depth: 29.12	Depth to Water: 15.61
Before: After:	Before: After:
Depth to Free Product:	Thickness of Free Product (feet):
Referenced to: <input checked="" type="radio"/> PVC <input type="radio"/> Grade	D.O. Meter (if req'd): YSI HACH

Purge Method:

- Bailer
- Disposable Bailer
- Middleburg
- Electric Submersible
- Watera
- Peristaltic
- Extraction Pump
- Other: _____

Sampling Method:

- Bailer
- Disposable Bailer
- Extraction Port
- Dedicated Tubing
- Other: _____

1.3	(Gals.) X	3	=	3.9	Gals.
1 Case Volume		Specified Volumes		Calculated Volume	

Well Diameter	Multiplier	Well Diameter	Multiplier
1"	0.04	4"	0.65
<input checked="" type="radio"/> 3"	0.16	6"	1.47
5"	0.37	Other	radius ² * 0.163

Time	Temp (°F)	pH	Cond.	Turbidity	Gals. Removed	Observations
1018	65.5	7.2	903	>200	1.5	
1021	66.5	6.9	898	>200	3	
1024	65.7	6.9	895	>200	4	

Did well dewater? Yes No Gallons actually evacuated: 4

Sampling Time: 1030 Sampling Date: 1/25/01

Sample I.D.: MW-14 Laboratory: Mc Campbell

Analyzed for: TPH-G BTEX MTBE TPH-D Other: VOC's By 8010

Equipment Blank I.D.: @ Time Duplicate I.D.:

Analyzed for: TPH-G BTEX MTBE TPH-D Other:

D.O. (if req'd):	Pre-purge:	mg/L	Post-purge:	mg/L
------------------	------------	------	-------------	------

ORP (if req'd):	Pre-purge:	mV	Post-purge:	mV
-----------------	------------	----	-------------	----

WELL MONITORING DATA SHEET

Project #: 010125-A1	Client: Basic Environmental
Sampler: DL	Start Date: 1/25/01
Well I.D.: MW-15	Well Diameter: <u>2</u> 3 4 6 8
Total Well Depth: 59.69	Depth to Water: 16.47
Before: After:	Before: After:
Depth to Free Product:	Thickness of Free Product (feet):
Referenced to: <u>PVC</u> Grade	D.O. Meter (if req'd): YSI HACH

Purge Method:

- Bailer
- Disposable Bailer
- Middleburg
- Electric Submersible
- Waterra
- Peristaltic
- Extraction Pump
- Other _____

Sampling Method:

- Bailer
- Disposable Bailer
- Extraction Port
- Dedicated Tubing
- Other: _____

<u>69</u>	(Gals.) X	<u>3</u>	=	<u>20.7</u>	Gals.
I Case Volume		Specified Volumes		Calculated Volume	

Well Diameter	Multiplier	Well Diameter	Multiplier
1"	0.04	4"	0.65
<u>2"</u>	0.16	6"	1.47
3"	0.37	Other	radius ² * 0.165

Time	Temp (°F)	pH	Cond.	Turbidity	Gals. Removed	Observations
1105	61.8	7.1	714	>200	7	
1111	62.6	7.0	712	>200	14	
1118	60.4	7.0	711	>200	21	

Did well dewater? Yes No Gallons actually evacuated: 21

Sampling Time: 1123 Sampling Date: 1/25/01

Sample I.D.: MW-15 Laboratory: Mc Campbell

Analyzed for: TPH-G BTEX MTBE TPH-D Other: VOC's By 8010

Equipment Blank I.D.: @ Time Duplicate I.D.:

Analyzed for: TPH-G BTEX MTBE TPH-D Other:

D.O. (if req'd):	Pre-purge:	mg/L	Post-purge:	mg/L
ORP (if req'd):	Pre-purge:	mV	Post-purge:	mV

WELL MONITORING DATA SHEET

Project #: 010125-41	Client: Basic Environmental
Sampler: 04	Start Date: 1/25/01
Well I.D.: MW-16	Well Diameter: <u>6</u> 3 4 6 8
Total Well Depth: 24.61	Depth to Water: 13.91
Before: After:	Before: After:
Depth to Free Product:	Thickness of Free Product (feet):
Referenced to: <u>PVC</u> Grade	D.O. Meter (if req'd): YSI HACH

Purge Method:

- Bailer
- Disposable Bailers
- Middleburg
- Electric Submersible
- Waterra
- Peristaltic
- Extraction Pump
- Other _____

Sampling Method:

- Bailer
- Disposable Bailers
- Extraction Port
- Dedicated Tubing
- Other: _____

$$\frac{1.7}{1 \text{ Case Volume}} \text{ (Gals.) } \times \frac{3}{\text{Specified Volumes}} = \frac{5.0}{\text{Calculated Volume}} \text{ Gals.}$$

Well Diameter	Multiplier	Well Diameter	Multiplier
1"	0.04	4"	0.65
<u>3"</u>	0.16	6"	1.47
	0.37	Other	radius ² * 0.163

Time	Temp (°F)	pH	Cond.	Turbidity	Gals. Removed	Observations
1040	61.5	7.0	409	172	1.5	
1043	62.9	6.9	421	182	3	
1046	63.1	6.9	427	190	5	

Did well dewater? Yes Gallons actually evacuated: 5

Sampling Time: 1050 Sampling Date: 1/25/01

Sample I.D.: MW-16 Laboratory: Mc Campbell

Analyzed for: TPH-G BTEX MTBE TPH-D Other: VOC's BY 8010

Equipment Blank I.D.: Duplicate I.D.:

Analyzed for: TPH-G BTEX MTBE TPH-D Other:

D.O. (if req'd):	Pre-purge:	mg/L	Post-purge:	mg/L
ORP (if req'd):	Pre-purge:	mV	Post-purge:	mV

WELL MONITORING DATA SHEET

Project #: <u>010129-H1</u>	Client: <u>Basics Env.</u>
Sampler: <u>MH</u>	Start Date: <u>1/29/01</u>
Well I.D.: <u>MW-3A</u>	Well Diameter: 2 3 4 6 8 <u>1</u>
Total Well Depth: <u>57.65</u>	Depth to Water: <u>15.77</u>
Before: _____ After: _____	Before: _____ After: _____
Depth to Free Product: _____	Thickness of Free Product (feet): _____
Referenced to: <u>PVC</u> Grade _____	D.O. Meter (if req'd): _____ YSI _____ HACH _____

Purge Method:

- Bailer
- Disposable Bailer
- Middleburg
- Electric Submersible
- Waterra
- Peristaltic
- Extraction Pump
- Other _____

Sampling Method:

- Bailer
- Disposable Bailer
- Extraction Port
- Dedicated Tubing
- Other: _____

<u>1.7</u> (Gals.) X <u>3</u>	=	<u>5.2</u> Gals.
1 Case Volume	Specified Volumes	Calculated Volume

Well Diameter	Multiplier	Well Diameter	Multiplier
1"	0.04	4"	0.65
2"	0.16	6"	1.47
3"	0.37	Other	radius ² * 0.163

Time	Temp (°F)	pH	Cond.	Turbidity	Gals. Removed	Observations
<u>1345</u>	<u>66.0</u>	<u>6.8</u>	<u>697</u>	<u>7200</u>	<u>2</u>	
<u>1347</u>	<u>66.0</u>	<u>6.6</u>	<u>693</u>	<u>7200</u>	<u>4</u>	
<u>1349</u>	<u>65.8</u>	<u>6.6</u>	<u>692</u>	<u>7200</u>	<u>6</u>	

Did well dewater? Yes No Gallons actually evacuated: 6

Sampling Time: 1351 Sampling Date: 1/29

Sample I.D.: MW-3A Laboratory: McCampbell

Analyzed for: TPH-G BTEX MTBE TPH-D Other: VOC's

Equipment Blank I.D.: _____ @ _____ Time Duplicate I.D.: _____

Analyzed for: TPH-G BTEX MTBE TPH-D Other: _____

D.O. (if req'd):	Pre-purge:	mg/L	Post-purge:	mg/L
	ORP (if req'd):	Pre-purge:	mV	Post-purge:

WELL MONITORING DATA SHEET

Project #: <u>010129-H1</u>	Client: <u>Rosics Env.</u>
Sampler: <u>MH</u>	Start Date: <u>1/29/01</u>
Well I.D.: <u>MW-10A</u>	Well Diameter: 2 3 4 6 8 <u>7</u>
Total Well Depth: <u>42.35</u>	Depth to Water: <u>15.22</u>
Before: After:	Before: After:
Depth to Free Product:	Thickness of Free Product (feet):
Referenced to: <u>PVC</u> Grade	D.O. Meter (if req'd): YSI HACH

Purge Method:

- Bailer
- Disposable Bailer
- Middleburg
- Electric Submersible
- Waterra
- Peristaltic
- Extraction Pump
- Other _____

Sampling Method:

- Bailer
- Disposable Bailer
- Extraction Port
- Dedicated Tubing
- Other: _____

<u>1.0</u>	(Gals.) X	<u>3</u>	=	<u>3.2</u>	Gals.
1 Case Volume		Specified Volumes		Calculated Volume	

Well Diameter	Multiplier	Well Diameter	Multiplier
1"	0.04	4"	0.65
2"	0.16	6"	1.47
3"	0.37	Other	radius ² * 0.163

Time	Temp (°F)	pH	Cond.	Turbidity	Gals. Removed	Observations
<u>1325</u>	<u>66.4</u>	<u>6.9</u>	<u>743</u>	<u>7200</u>	<u>1</u>	
<u>1326</u>	<u>66.7</u>	<u>6.8</u>	<u>751</u>	<u>7200</u>	<u>2</u>	
<u>1328</u>	<u>66.9</u>	<u>6.8</u>	<u>756</u>	<u>7200</u>	<u>3.5</u>	

Did well dewater? Yes No Gallons actually evacuated: 3.5

Sampling Time: 1350 Sampling Date: 1/29

Sample I.D.: MW-10A Laboratory: McC Campbell

Analyzed for: TPH-G BTEX MTBE TPH-D Other: VOC's

Equipment Blank I.D.: @ Duplicate I.D.:

Analyzed for: TPH-G BTEX MTBE TPH-D Other:

D.O. (if req'd):	Pre-purge:	mg/L	Post-purge:	mg/L
ORP (if req'd):	Pre-purge:	mV	Post-purge:	mV

WELL MONITORING DATA SHEET

Project #: <u>01029-141</u>	Client: <u>Basics Env</u>
Sampler: <u>AAA</u>	Start Date: <u>1/29/01</u>
Well I.D.: <u>AW-15A</u>	Well Diameter: 2 3 4 6 8 <u>1</u>
Total Well Depth: <u>34.95</u>	Depth to Water: <u>16.39</u>
Before: After:	Before: After:
Depth to Free Product:	Thickness of Free Product (feet):
Referenced to: <u>PVC</u> Grade	D.O. Meter (if req'd): YSI HACH

Purge Method:	Sampling Method:
Bailer	Bailer
Disposable Bailer	Disposable Bailer
Middleburg	Extraction Port
Electric Submersible	<u>Dedicated Tubing</u>
<u>Water</u>	Other: _____
Peristaltic	
Extraction Pump	
Other: _____	

$$0.7 \text{ (Gals.)} \times 3 = 2.2 \text{ Gals.}$$
 I Case Volume Specified Volumes Calculated Volume

Well Diameter	Multiplier	Well Diameter	Multiplier
1"	0.04	1"	0.65
2"	0.16	6"	1.47
3"	0.37	Other	radius ² * 0.165

Time	Temp (°F)	pH	Cond.	Turbidity	Gals. Removed	Observations
1311	66.4	6.8	693	>200	1	
1312	66.8	6.9	699	>200	2	
1313	66.9	6.9	703	>200	3	

Did well dewater? Yes No Gallons actually evacuated: 3

Sampling Time: 1315 Sampling Date: 1/29

Sample I.D.: AW-15A Laboratory: Mc Campbell

Analyzed for: TPH-G BTEX MTBE TPH-D Other: VOC's

Equipment Blank I.D.: _____ @ _____ Time Duplicate I.D.: _____

Analyzed for: TPH-G BTEX MTBE TPH-D Other: _____

D.O. (if req'd):	Pre-purge:	mg/L	Post-purge:	mg/L
ORP (if req'd):	Pre-purge:	mV	Post-purge:	mV

WELL MONITORING DATA SHEET

Project #: <u>010129-41</u>		Client: <u>Basics Env.</u>	
Sampler: <u>10H</u>		Start Date: <u>1/29/01</u>	
Well I.D.: <u>MW-16A</u>		Well Diameter: 2 3 4 6 8 <u>1</u>	
Total Well Depth: <u>37.85</u>		Depth to Water: <u>13.64</u>	
Before:	After:	Before:	After:
Depth to Free Product:		Thickness of Free Product (feet):	
Referenced to: <u>PVC</u> Grade		D.O. Meter (if req'd): YSI HACH	

Purge Method:

- Bailer
- Disposable Bailer
- Middleburg
- Electric Submersible
- Waterra
- Peristaltic
- Extraction Pump
- Other _____

Sampling Method:

Bailer

- Disposable Bailer
- Extraction Port
- Dedicated Tubing

Other: _____

<u>0.9</u>	(Gals.) X	<u>3</u>	=	<u>2.9</u>	Gals.
1 Case Volume		Specified Volumes		Calculated Volume	

Well Diameter	Multiplier	Well Diameter	Multiplier
1"	0.04	4"	0.65
2"	0.16	6"	1.47
3"	0.37	Other	radius ² * 0.163

Time	Temp (°F)	pH	Cond.	Turbidity	Gals. Removed	Observations
1300	65.5	6.3	665	7200	1	
1301	65.9	6.3	667	7200	2	
1302	65.9	6.4	669	7200	3	

Did well dewater? Yes No Gallons actually evacuated: 3

Sampling Time: 1304 Sampling Date: 1/29

Sample I.D.: MW-16A Laboratory: Mc Carbell

Analyzed for: TPH-G BTEX MTBE TPH-D Other: VOCs

Equipment Blank I.D.: @ _____ Time Duplicate I.D.: _____

Analyzed for: TPH-G BTEX MTBE TPH-D Other: _____

D.O. (if req'd):	Pre-purge:	mg/L	Post-purge:	mg/L
	ORP (if req'd):	Pre-purge:	mV	Post-purge:

APPENDIX B



McCAMPBELL ANALYTICAL INC.

 110 2nd Avenue South, #D7, Pacheco, CA 94553-5560
 Telephone : 925-798-1620 Fax : 925-798-1622
<http://www.mccampbell.com> E-mail: main@mccampbell.com

Basics Environmental 116 Gloreitta Boulevard Orinda, CA 94563	Client Project ID: #010129-H1	Date Sampled: 01/29/01
		Date Received: 01/30/01
	Client Contact: Donovan Tom	Date Extracted: 01/31-02/02/01
	Client P.O.:	Date Analyzed: 01/31-02/02/01

Volatile Halocarbons

EPA method 601 or 8010


Lab ID	59043	59044	59045	59046
Client ID	MW-3A	MW-10A	MW-15A	MW-16A
Matrix	W	W	W	W
Compound	Concentration			
Bromodichloromethane	ND	ND<10	ND<25	ND<50
Bromoform ^(b)	ND	ND<10	ND<25	ND<50
Bromomethane	ND	ND<10	ND<25	ND<50
Carbon Tetrachloride ^(c)	ND	ND<10	ND<25	ND<50
Chlorobenzene	ND	ND<10	ND<25	ND<50
Chloroethane	ND	ND<10	ND<25	ND<50
2-Chloroethyl Vinyl Ether ^(d)	ND	ND<10	ND<25	ND<50
Chloroform ^(e)	ND	ND<10	ND<25	ND<50
Chloromethane	ND	ND<10	ND<25	ND<50
Dibromochloromethane	ND	ND<10	ND<25	ND<50
1,2-Dichlorobenzene	ND	ND<10	ND<25	ND<50
1,3-Dichlorobenzene	ND	ND<10	ND<25	ND<50
1,4-Dichlorobenzene	ND	ND<10	ND<25	ND<50
Dichlorodifluoromethane	ND	ND<10	ND<25	ND<50
1,1-Dichloroethane	ND	ND<10	ND<25	ND<50
1,2-Dichloromethane	ND	ND<10	ND<25	ND<50
1,1-Dichloroethene	ND	ND<10	ND<25	ND<50
cis 1,2-Dichloroethene	ND	28	ND<25	ND<50
trans 1,2-Dichloroethene	ND	ND<10	ND<25	ND<50
1,2-Dichloropropane	ND	ND<10	ND<25	ND<50
cis 1,3-Dichloropropene	ND	ND<10	ND<25	ND<50
trans 1,3-Dichloropropene	ND	ND<10	ND<25	ND<50
Methylene Chloride ^(f)	ND	ND<10	ND<25	ND<210
1,1,2,2-Tetrachloroethane	ND	ND<10	ND<25	ND<50
Tetrachloroethene	ND	830	410	3600
1,1,1-Trichloroethane	ND	ND<10	ND<25	ND<50
1,1,2-Trichloroethane	ND	ND<10	ND<25	ND<50
Trichloromethene	ND	110	69	160
Trichlorofluoromethane	ND	ND<10	ND<25	ND<50
Vinyl Chloride ^(g)	ND	ND<10	ND<25	ND<50
% Recovery Surrogate	110	98	96	99
Comments				

* water and vapor samples and all TCLP & SPLP extracts are reported in ug/L. soil and sludge samples in ug/kg. wipe samples in ug/wipe
 Reporting limit unless otherwise stated: water/TCLP/SPLP extracts, ND<0.5ug/L; soils and sludges, ND<5ug/kg; wipes, ND<0.2ug/wipe
 ND means not detected above the reporting limit; N/A means analyte not applicable to this analysis

(b) tribromomethane; (c) tetrachloromethane; (d) (2-chloroethoxy) ethene; (e) trichloromethane; (f) dichloromethane; (g) chloroethene; (h) a lighter than water immiscible sheen is present; (i) liquid sample that contains greater than --5 vol. % sediment; (j) sample diluted due to high organic content.

DHS Certification No. 1644

Edward Hamilton, Lab Director


 McCAMPBELL ANALYTICAL INC.	110 2nd Avenue South, #D7, Pacheco, CA 94553-5560 Telephone: 925-798-1620 Fax: 925-798-1622 http://www.mccampbell.com E-mail: main@mccampbell.com	
---	---	--

Basics Environmental 116 Gioveitta Boulevard Orinda, CA 94563	Client Project ID: #010125-A1	Date Sampled: 01/25/01
		Date Received: 01/26/01
	Client Contact: Donovan Tom	Date Extracted: 01/26-02/01/01
	Client P.O:	Date Analyzed: 01/26-02/01/01

Volatile Halocarbons				
EPA method 601 or 8010				
Lab ID	58811	58812	58813	58814
Client ID	MW-6	MW-14	MW-16	MW-15
Matrix	W	W	W	W
Compound	Concentration			
Bromodichloromethane	ND	ND<1.0	ND<1.0	ND<5.0
Bromoform ^(h)	ND	ND<1.0	ND<1.0	ND<5.0
Bromomethane	ND	ND<1.0	ND<1.0	ND<5.0
Carbon Tetrachloride ^(c)	ND	ND<1.0	ND<1.0	ND<5.0
Chlorobenzene	ND	ND<1.0	ND<1.0	ND<5.0
Chloroethane	ND	ND<1.0	ND<1.0	ND<5.0
2-Chloroethyl Vinyl Ether ^(h)	ND	ND<1.0	ND<1.0	ND<5.0
Chloroform ^(h)	ND	ND<1.0	ND<1.0	ND<5.0
Chloromethane	ND	ND<1.0	ND<1.0	ND<5.0
Dibromochloromethane	ND	ND<1.0	ND<1.0	ND<5.0
1,2-Dichlorobenzene	ND	ND<1.0	ND<1.0	ND<5.0
1,3-Dichlorobenzene	ND	ND<1.0	ND<1.0	ND<5.0
1,4-Dichlorobenzene	ND	ND<1.0	ND<1.0	ND<5.0
Dichlorodifluoromethane	ND	ND<1.0	ND<1.0	ND<5.0
1,1-Dichloroethane	ND	ND<1.0	ND<1.0	ND<5.0
1,2-Dichloroethane	ND	ND<1.0	ND<1.0	ND<5.0
1,1-Dichloroethene	ND	ND<1.0	ND<1.0	ND<5.0
cis 1,2-Dichloroethene	0.70	1.4	ND<1.0	7.4
trans 1,2-Dichloroethene	ND	ND<1.0	ND<1.0	ND<5.0
1,2-Dichloropropane	ND	ND<1.0	ND<1.0	ND<5.0
cis 1,3-Dichloropropene	ND	ND<1.0	ND<1.0	ND<5.0
trans 1,3-Dichloropropene	ND	ND<1.0	ND<1.0	ND<5.0
Methylene Chloride ^(d)	ND	ND<1.0	ND<1.0	ND<5.0
1,1,2,2-Tetrachloroethane	ND	ND<1.0	ND<1.0	ND<5.0
Tetrachloroethene	35	48	35	310
1,1,1-Trichloroethane	ND	ND<1.0	ND<1.0	ND<5.0
1,1,2-Trichloroethane	ND	ND<1.0	ND<1.0	ND<5.0
Trichloroethene	20	74	ND<1.0	38
Trichlorofluoromethane	ND	ND<1.0	ND<1.0	ND<5.0
Vinyl Chloride ^(d)	ND	ND<1.0	ND<1.0	ND<5.0
% Recovery Surrogate	109	98	109	98
Comments	i	i		

* water and vapor samples and all TCLP & SPLP extracts are reported in ug/L. soil and sludge samples in ug/kg. wipe samples in ug/wipe
 Reporting limit unless otherwise stated: water/TCLP/SPLP extracts, NI<0.5ug/L; soils and sludges, ND<5ug/kg; wipes, ND=0.2ug/wipe
 ND means not detected above the reporting limit; N/A means analyte not applicable to this analysis

(b) tribromomethane; (c) tetrachloromethane; (d) (2-chloroethoxy) ethene; (e) trichloromethane; (f) dichloromethane; (g) chloroethene; (h) a lighter than water immiscible sheen is present; (i) liquid sample that contains greater than - 5 vol. % sediment; (j) sample diluted due to high organic content.

 McCAMPBELL ANALYTICAL INC.	110 2nd Avenue South, #107, Pacheco, CA 94553-5560 Telephone : 925-798-1620 Fax : 925-798-1622 http://www.mccampbell.com E-mail: main@mccampbell.com
---	--

Basics Environmental 116 Glorietta Boulevard Orinda, CA 94563	Client Project ID: #010125-A1	Date Sampled: 01/25/01
		Date Received: 01/26/01
	Client Contact: Donavan Tom	Date Extracted: 01/26-02/01/01
	Client P.O:	Date Analyzed: 01/26-02/01/01

Volatile Halocarbons			
EPA method 601 or 8010			
Lab ID	58815	58816	
Client ID	MW-10	MW-3	
Matrix	W	W	
Compound	Concentration		
Bromodichloromethane	ND<50	ND<50	
Bromoform ^(b)	ND<50	ND<50	
Bromomethane	ND<50	ND<50	
Carbon Tetrachloride ^(c)	ND<50	ND<50	
Chlorobenzene	ND<50	ND<50	
Chloroethane	ND<50	ND<50	
2-Chloroethyl Vinyl Ether ^(d)	ND<50	ND<50	
Chloroform ^(e)	ND<50	ND<50	
Chloromethane	ND<50	ND<50	
Dibromochloromethane	ND<50	ND<50	
1,2-Dichlorobenzene	ND<50	ND<50	
1,3-Dichlorobenzene	ND<50	ND<50	
1,4-Dichlorobenzene	ND<50	ND<50	
Dichlorodifluoromethane	ND<50	ND<50	
1,1-Dichloroethane	ND<50	ND<50	
1,2-Dichloroethane	ND<50	ND<50	
1,1-Dichloroethene	ND<50	ND<50	
cis 1,2-Dichloroethene	170	ND<50	
trans 1,2-Dichloroethene	ND<50	ND<50	
1,2-Dichloropropane	ND<50	ND<50	
cis 1,3-Dichloropropene	ND<50	ND<50	
trans 1,3-Dichloropropene	ND<50	ND<50	
Methylene Chloride ^(f)	ND<90	ND<90	
1,1,2,2-Tetrachloroethane	ND<50	ND<50	
Tetrachloroethene	4100	RR0	
1,1,1-Trichloroethane	ND<50	ND<50	
1,1,2-Trichloroethane	ND<50	ND<50	
Trichloroethene	520	120	
Trichlorofluoromethane	ND<50	ND<50	
Vinyl Chloride ^(g)	ND<50	ND<50	
% Recovery Surrogate	108	96	
Comments			

* water and vapor samples and all TCLP & SPLP extracts are reported in ug/L, soil and sludge samples in ug/kg, wipe samples in ug/wipe
 Reporting limit unless otherwise stated; water/TCLP/SPLP extracts, ND<0.5ug/L; soils and sludges, ND<5ug/kg; wipes, ND<0.2ug/wipe
 ND means not detected above the reporting limit; N/A means analyte not applicable to this analysis
 (b) tribromomethane; (c) tetrachloromethane; (d) (2-chloroethoxy) ethane; (e) trichloromethane; (f) dichloromethane; (g) chloromethane; (h) a lighter than water immiscible sheen is present; (i) liquid sample that contains greater than ~5 vol. % sediment; (j) sample diluted due to high organic content.

DHS Certification No. 1644

 Edward Hamilton, Lab Director

BLAINE

TECH SERVICES, INC

1660 ROGERS AVENUE
SAN JOSE, CALIFORNIA 95112-1108
FAX (408) 573-7771
PHONE (408) 573-0555

CONDUCT ANALYSIS TO DETECT

LAB

McC Campbell

DHS #

ALL ANALYSES MUST MEET SPECIFICATIONS AND DETECTION LIMITS SET BY CALIFORNIA DHS AND

- EPA
 LIA
 OTHER
 RWQCB REGION

SPECIAL INSTRUCTIONS

Invoice and Report to : Basics Environmental

Attn: Donovan Tom

Confirm Analysis Requested before Running

CHAIN OF
BTS # D10125-A1

CLIENT
Basics Environmental

SITE
2075 Williams Street

San Leandro, CA

C = COMPOSITE ALL CONTAINERS

SAMPLE I.D.	DATE	TIME	MATRIX		CONTAINERS		EPA 8010
			S=SOIL W=H ₂ O		TOTAL		

SW MW-6	1/25/01	1005	W		3	Hcl/Vol ¹³	X
SW MW-19		1030					X
SW MW-16		1050					X
SW MW-15		1123					X
SW MW-10		1150					X
SW MW-3		1215					X

ADD'L INFORMATION	STATUS	CONDITION	LAB SAMPLE #
			58811
			58812
			58813
			58814
			58815
			58816

ICE/GOOD CONDITION/HEAD SPACE ABSENT

PRESERVATION APPROPRIATE CONTAINERS

VOAS/DAG/METALS/OTHER

SAMPLING COMPLETED
DATE: 1/25/01
TIME: 1030
SAMPLING PERFORMED BY: Oscar Angulo

RESULTS NEEDED
NO LATER THAN 5 day TAT

RELEASED BY: O. Angulo
DATE: 1/26/01
TIME: 1030

RECEIVED BY: Ultra Ex # 138
DATE: 1/26/01
TIME: 1030

RELEASED BY: Ultra Ex # 138
DATE: 1/26/01
TIME: 1159

RECEIVED BY: G. Bryder
DATE: 1/26/01
TIME: 4:20 PM

RELEASED BY: G. Bryder

SHIPPED VIA: ULTRA EXPRESS
DATE SENT: 1/26/01
TIME SENT: 1030

RECEIVED BY: G. Bryder / Maria Nunez
DATE: 1/26/01
TIME: 4:20 PM

ent By: McCampbell Analytical; 925 798 1620; Feb-6-01 3:29PM; Page 2

