

10/92

MATERIAL SAFETY DATA SHEET

SECTION I - IDENTIFICATION

SUPPLIERS NAME: ALDRAN MANUFACTURING, INC DATE: OCT 5, 1992

EMERGENCY PHONE NO: 415-952-0568

ADDRESS: 391 FORBES BLVD
SOUTH SAN FRANCISCO, CA 94080

PRODUCT NAME: JUST GREAT

CHEMICAL FAMILY: ACID CLEANER

FORMULA: PROPRIETARY

ALDRAN CODE# A118

SECTION II - HAZARDOUS INGREDIENTS AND/OR THOSE SUBJECT TO REPORTING REQUIREMENTS OF TITLE III SEC 313 OR 40 CFR 372

CAS#	MATERIAL OR COMPONENT	EXPOSURE LIMIT VALUES		
		TLV	TWA	OTHER/REMARKS
1341-49-7	AMMONIUM HYDROGEN FLUORIDE	35 ppm	OSHA PEL	25 ppm

ENVIRONMENTAL PROTECTION

NO TOXIC CHEMICALS SUBJECT TO THE REPORTING REQUIREMENTS OF SEC 313 TITLE III AND OF 40 CFR 372 ARE PRESENT.

CONTAINS NO MATERIALS ON THE "THRESHOLD LIMIT VALUES & BIOLOGICAL EXPOSURE INDICES FOR 1989-90" of ACGIH EXCEPT AS INDICATED ABOVE.

THIS INFORMATION MUST BE INCLUDED IN ALL MSDS THAT ARE COPIED AND DISTRIBUTED FOR THIS MATERIAL.

SECTION III - PHYSICAL DATA

INITIAL BOILING POINT: 212 deg F FLASH POINT: NONE

DENSITY: 1.0 VAPOR PRESSURE: LIKE WATER

pH: 2.0-4.0

VAPOR DENSITY (air=1): HEAVIER SOLUBILITY IN WATER (% by vol): COMPLETE

EVAPORATION RATE: SLOW

APPEARANCE AND ODOR: WATER CLEAR LIGHTLY TINTED VIS. FA. ODO. NONE

SECTION IV - FIRE AND EXPLOSION DATA

FLASH POINT (CLOSED CUP): NONE

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL, WATER SOG

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: N/A UPPER: N/A

SPECIAL FIREFIGHTING PROCEDURES: Fire fighters should wear self-contained breathing apparatus and full protective clothing. Use water spray to cool nearby containers and structures exposed to the fire.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Extinguish all nearby sources of ignition since flammable hydrogen gas may be liberated from contact with some metals.

SECTION V - REACTIVITY DATA

STABILITY: Stable

CONDITIONS TO AVOID: excessive heat and contamination of any kind.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong acids or alkalis; etches glass.

ENVIRONMENTAL PROTECTION

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: GLISTEN
CONTACTS: NA

DATE: JAN 23, 1994

*****SECTION 1 - PRODUCT IDENTITY AND SOURCE*****
 CHEMICAL DESCRIPTION: Alkaline, low surface tension water based cleaner
 SUPPLIERS NAME: ALDRAN CHEMICAL, INC
 ADDRESS: 391 FORBES BLVD., SO. SAN FRANCISCO, CA 94080
 TO REORDER: 415-952-3378
 CHEMICAL FAMILY: WATER BASED CLEANER FORMULA: PROPRIETARY

*****SECTION 2- COMPOSITION AND INGREDIENT INFORMATION*****

REPORTING REQUIRED BY TITLE III SEC 313 OR 40 CFR 372 (*)

EXPOSURE LIMIT VALUES

CAS#	MATERIAL OR COMPONENT	%	TLV*	TWA	OTHER/REMARKS
------	-----------------------	---	------	-----	---------------

CONTAINS NO HAZARDOUS INGREDIENTS ACCORDING TO THESE LISTS

NO COMPONENTS ARE LISTED IN "THRESHOLD LIMIT VALUES AND BIOLOGICAL EXPOSURE INDICES FOR 1992-1993" FROM AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS (ACGIH) EXCEPT AS ABOVE.

*****SECTION 3 - HAZARDS IDENTIFICATION*****
 EMERGENCY OVERVIEW

No unusual fire or spill hazard. Avoid contact with skin and eyes.

HHS RATINGS: ACUTE HEALTH 0 FIRE 0 REACTIVITY 0 OTHER NA

HAZARD RATINGS: LEAST:0, SLIGHT:1, MODERATE:2, HIGH:3, EXTREME:4

THRESHOLD LIMIT VALUE: Not established on product.

EFFECTS OF CHRONIC OVER EXPOSURE:

SKIN: Can cause irritation, redness, from defatting skin.

EYES: Can cause severe irritation, redness, tearing, blurred vision.

INHALATION: not a likely source of exposure

INGESTION: Can cause gastrointestinal irritation, nausea, vomiting, and diarrhea.

REPRODUCTIVE IMPLICATIONS:..X..None

INGREDIENT ON CANCER LISTS:..X..NONEOSHA.....NTP....IARC

*****SECTION 4 - FIRST AID MEASURES*****

EMERGENCY AND FIRST AID PROCEDURE:

SKIN: Flush with water until gone.

EYES: Flush with water for at least 15 min.

INHALATION: If affected, remove individual to fresh air.

INGESTION: Do not induce vomiting. Give victim large amounts of water. If vomiting does occur, give water again. Get medical attention immediately. Never give anything by mouth to an unconscious or convulsing person.

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: QUICK & EASY
CONTACTS: NA

ISSUE DATE: JAN 17, 1994
TO ORDER: (415)-952-3378

*****SECTION 1 - PRODUCT IDENTITY AND SOURCE*****

CHEMICAL DESCRIPTION: Neutral pH, low surface tension water based cleaner
SUPPLIERS NAME: ALDRAN CHEMICAL, INC
ADDRESS: 391 FORBES BLVD., SO. SAN FRANCISCO, CA 94080

CHEMICAL FAMILY: Water based cleaner FORMULA: Proprietary

*****SECTION 2- COMPOSITION AND INGREDIENT INFORMATION*****

REPORTING REQUIRED BY TITLE III SEC 313 OR 40 CFR 372 (*)

CAS#	MATERIAL OR COMPONENT	%	EXPOSURE LIMIT VALUES		
			TLV*	TWA	OTHER/REMARKS

CONTAINS NO HAZARDOUS INGREDIENTS ACCORDING TO THESE LISTS

NO COMPONENTS ARE LISTED IN "THRESHOLD LIMIT VALUES AND BIOLOGICAL EXPOSURE INDICES FOR 1992-1993" FROM AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS (ACGIH) EXCEPT AS ABOVE.

*****SECTION 3 - HAZARDS IDENTIFICATION*****

EMERGENCY OVERVIEW

No unusual fire or spill hazard. Avoid contact with skin and eyes.

HMS RATINGS: ACUTE HEALTH 0 FIRE 0 REACTIVITY 0 OTHER NA

HAZARD RATINGS: LEAST:0, SLIGHT:1, MODERATE:2, HIGH:3, EXTREME:4

THRESHOLD LIMIT VALUE: Not established on product.

EFFECTS OF CHRONIC OVER EXPOSURE:

SKIN: Can cause irritation, redness, from defatting skin.

EYES: Can cause severe irritation, redness, tearing, blurred vision.

INHALATION: not a likely exposure, but could irritate nasal passages.

INGESTION: Can cause gastrointestinal irritation, nausea, vomiting, and diarrhea.

REPRODUCTIVE IMPLICATIONS: .X..None

INGREDIENT ON CANCER LISTS: .X..NONEOSHA.....NTP....IARC

*****SECTION 4 - FIRST AID MEASURES*****

EMERGENCY AND FIRST AID PROCEDURE:

SKIN: Flush with water until gone.

EYES: Flush with water for at least 15 min.

INHALATION: If affected, remove individual to fresh air.

INGESTION: Do not induce vomiting. Give victim large amounts of water
If vomiting does occur, give water again. Get medical attention immediately. Never give anything by mouth to an unconscious or convulsing person.

Material Safety Data Sheet

PAGE: 1

SECTION 1: PRODUCT INFORMATION

NAME: SUN GLOW
 DESCRIPTION: STYRENE ACRYLIC EMULSION
 USE: FLOOR FINISH
 MSDS NUMBER: #4140
 APPEARANCE AND ODOR: WHITE LIQUID
 EMERGENCY TELEPHONE: 800-255-3924
 PRODUCT INFORMATION: 415-952-3378
 EFFECTIVE DATE: 11/18/91
 SUPERCEDES DATE: 11/04/91

SECTION 2: HAZARDOUS INGREDIENTS

A HAZARD EVALUATION OF THIS PRODUCT HAS BEEN PERFORMED. THE COMPONENTS LISTED BELOW ARE IDENTIFIED AS HAZARDOUS CHEMICALS UNDER THE CRITERIA OF THE OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200).

COMMON NAME/CHEMICAL NAME	CAS NUMBER	APPROXIMATE %
TRIBUTOXYETHYL PHOSPHATE	78-51-3	5 - 10
DIETHYLENE GLYCOL DIMETHYL ETHER	111-90-0	5 - 10
DIETHYLENE GLYCOL MONOMETHYL ETHER		
DIETHYLENE GLYCOL		
DIETHYLENE GLYCOL CARBOXYLATE COMPOUND	38714-47-5	1 - 5

SECTION 3: EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT:
 FLUSH EYES WITH WATER FOR AT LEAST 15 MINUTES. IF IRRITATION DEVELOPS, CONSULT A PHYSICIAN.

SKIN CONTACT:
 REMOVE CONTAMINATED CLOTHING AND SHOES. WASH AFFECTED AREA WITH SOAP AND WATER. IF IRRITATION DEVELOPS, CONSULT A PHYSICIAN. WASH CONTAMINATED CLOTHING SEPARATELY BEFORE REUSE.

INHALATION:
 REMOVE TO FRESH AIR. IF SYMPTOMS DEVELOP, SEEK IMMEDIATE MEDICAL ATTENTION. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION, PREFERABLY MOUTH TO MOUTH.

INGESTION:
 SEEK MEDICAL ATTENTION. UNLESS ADVISED OTHERWISE, INDUCE VOMITING BY GIVING EITHER SYRUP OF IPECAC FOLLOWED BY 2 GLASSES OF WATER OR BY STICKING FINGER DOWN THROAT.

DO NOT GIVE ANYTHING BY MOUTH IF THE PERSON IS DROWSY, UNCONSCIOUS, OR HAS NO GAG REFLEX.

ALDRAN CHEMICAL, INC. 391 Forbes Blvd. So. San Francisco, CA 94080

415-952-3378

Material Safety Data Sheet

PAGE: 2

NOTE TO PHYSICIAN:
 TREATMENT SHOULD BE DIRECTED AT PREVENTING ABSORPTION, ADMINISTERING TO THE SYMPTOMS AS THEY OCCUR, AND PROVIDING SUPPORTIVE THERAPY.

SECTION 4: HEALTH EFFECTS SUMMARY

PRIMARY ROUTE(S) OF EXPOSURE: EYE - YES SKIN - YES INHALATION - YES

EYE CONTACT:
 CAN CAUSE MILD TO MODERATE IRRITATION.

SKIN CONTACT:
 IRRITATION CAN OCCUR FOLLOWING PROLONGED OR REPEATED CONTACT.

INHALATION:
 CAN BE IRRITATING TO MUCOUS MEMBRANES, ESPECIALLY FOLLOWING PROLONGED EXPOSURE TO MISTS AND/OR VAPORS.

INGESTION:
 CAN CAUSE NAUSEA, VOMITING, AND GASTROINTESTINAL UPSET.

ADDITIONAL EFFECTS:
 DEPENDING ON THE ROUTE, FREQUENCY, AND DURATION OF EXPOSURE, TOXICITY MAY EFFECT IN THE FOLLOWING ORGANS AND/OR SYSTEMS:
 RESPIRATORY SYSTEM.
 EYE.

AGGRAVATION OF EXISTING CONDITIONS:
 SOME OF THE COMPONENTS IN THIS PRODUCT MAY AGGRAVATE EXISTING MEDICAL CONDITIONS. INDIVIDUALS WITH MEDICAL CONDITIONS INVOLVING THE FOLLOWING ORGAN(S) AND/OR SYSTEM(S) SHOULD TAKE APPROPRIATE PRECAUTIONS WHEN HANDLING THIS PRODUCT:
 SKIN.

ALWAYS WEAR APPROPRIATE PROTECTIVE EQUIPMENT, AS RECOMMENDED BY YOUR INDUSTRIAL HYGIENE OR SAFETY PERSONNEL, WHEN EXPOSURE TO THIS PRODUCT CAN OCCUR.

SECTION 5: TOXICOLOGIC INFORMATION

THE INFORMATION IN THIS SECTION, THOUGH DETAILED, CAN BE SUBJECT TO MISINTERPRETATION. THEREFORE, IT IS ESSENTIAL THE FOLLOWING INFORMATION BE INTERPRETED BY INDIVIDUALS TRAINED IN ITS EVALUATION.

TRIBUTOXYETHYL PHOSPHATE

TOXIC EFFECTS:
 LIQUID AND MIST CONTACTING THE OCULAR TISSUES CAN PRODUCE IRRITATION. CAN CAUSE SKIN IRRITATION FOLLOWING PROLONGED CONTACT.

ALDRAN CHEMICAL, INC. 391 Forbes Blvd. So. San Francisco, CA 94080

415-952-3378

ALDRAN CHEMICAL, INC.

391 Forbes Blvd.

50. SAN FRANCISCO, CA 94080

(415) 952-3378 (408) 280-1799

Outside CA 800 332-2244

DATE REVISED: 4/19/89
SUPERSEDES : CURRENT

PAGE 1 OF 3

SECTION I

PRODUCT IDENTIFICATION

PRODUCT NAME: Put Down
MANUFACTURED FOR: ALDRAN CHEMICAL
HAZARD CLASS: NONE

IN CASE OF EMERGENCY: (415) 786-456
OR 24 HOUR PAGER (415) 942-110

SECTION II

HAZARDOUS INGREDIENTS

CHEMICAL	CAS#	AMOUNT	LEVELS ON A 100% BASIS		
			FORMULA	TLV	PEL (TWA)

APPLICABLE

SEE PAGE 3 FOR ADDITIONAL REGULATORY INFORMATION ON THIS CHEMICAL.

SECTION III

PHYSICAL DATA

MELTING POINT: NOT APPLICABLE
VAPOR PRESSURE: NON-VOLATILE
DENSITY (AIR = 1): NON-VOLATILE
SPECIFIC GRAVITY: NOT APPLICABLE
APPEARANCE: WHITE POWDER

VOLATILES: NON-VOLATILE
SOLUBILITY IN WATER: COMPLETE
EVAPORATION RATE (WATER=1): NON-VOLATILE
PH (1% SOL.): NEUTRAL

SECTION IV

FIRE AND EXPLOSION HAZARDS

FLASH POINT: NON-COMBUSTIBLE
AUTO-IGNITION: NOT APPLICABLE
EXTINGUISHING MEDIA: WILL NOT SUPPORT COMBUSTION
FIRE OR EXPLOSIVE HAZARDS: NONE

FLAMMABLE LIMITS LEL/UEL: N.A.

SECTION V

HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE

CONTACT: CAN CAUSE MODERATE TO SEVERE IRRITATION. PROLONGED CONTACTS MAY RESULT IN REDNESS AND TEARING OF THE EYE.
INHALATION: SPRAY AND DUST CAN BE IRRITATING TO THE UPPER RESPIRATORY TRACT.
INGESTION: CAN CAUSE NAUSEA, VOMITING, AND ABDOMINAL PAIN.
SKIN CONTACT: PROLONGED AND REPEATED CONTACT MAY CAUSE IRRITATION TO THE SKIN.

MATERIAL SAFETY DATA SHEET

essentially similar to form OSHA-174

KELLY-MOORE PAINT CO., INC.
1015 COMMERCIAL ST., SAN CARLOS CA 94070

EMERGENCY PHONE: 800-424-9300(Chemtrec) INFORMATION PHONE: 415-592-8537

I - PRODUCT IDENTIFICATION

PRODUCT NAME	PRODUCT NUMBER	HMIS CODES:			
		H	F	R	PP
KEL-GUARD RUST INHIBITIVE ENAMEL	1700-series(all colors)	1	2	0	I

II - HAZARDOUS INGREDIENTS

INGREDIENT	CAS REG #	WT PCT	TLV-ACGIH	PEL-OSHA	VAPOR PRESSURE	
					MM HG	AT DEG F
AROMATIC 100	64742-95-6	<5%	not est.	100 ppm	3-5	/ 100
MINERAL SPIRITS	Mixture	40-60%	100 ppm	500 ppm	2.0	/ 68

*A commercial mixture of naphthenes, paraffins and aromatic hydrocarbons which includes CAS #64742-47-8, CAS #64742-95-6 and CAS #68515-25-3.

NOTE: This product contains no substances listed by IARC, OSHA or NTP as carcinogenic. It may contain pigments such as titanium dioxide, mineral silicates and calcium carbonate that may be nuisance dust hazards in their original dry powder form but are not hazardous in wet paint.

III - PHYSICAL PROPERTIES

BOILING RANGE: above 300 deg F DENSITY: 7-11 #/gal VAPOR DENSITY: heavier than air
PERCENT VOLATILE: 50-65% EVAPORATION RATE: slower than ether
(by volume)

IV - FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION: Combustible liquid/class II

FLASH POINT: >100 deg F LEL: 1.0% UEL: n/a

EXTINGUISHING MEDIA: Use approved class B fire extinguisher or extinguishing agents such as CO2, foam etc.

FIRE AND EXPLOSION HAZARDS: Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Closed containers may explode when exposed to extreme heat. Do not apply to hot surfaces. Vapors may travel along the ground and be ignited at distant locations with possible flashback to the handling site.

SPECIAL FIREFIGHTING PROCEDURES: Full protective equipment including self-contained breathing apparatus should be used. Water may be used to cool closed container to prevent pressure buildup. Water spray or water fog should be used carefully in fire fighting. This product will float on water and can be ignited on the water surface.

PREPARED BY:

John Schaefer

DATE: 7/12/91

SII

MATERIAL SAFETY DATA SHEET

essentially similar to form OSHA-174

KELLY-MOORE PAINT CO., INC.
1015 COMMERCIAL ST., SAN CARLOS CA 94070

EMERGENCY PHONE: 800-424-9500(Chemtrec) INFORMATION PHONE: 415-592-8537

I - PRODUCT IDENTIFICATION

PRODUCT NAME	PRODUCT NUMBER	HMIS CODES:			
		H	F	R	PP
ACRY-LUSTRE ACRYLIC SEMI-GLOSS 1250-series (all colors)		1	0	0	E

II - HAZARDOUS INGREDIENTS

INGREDIENT	CAS REG #	WT PCT	TLV-ACGIH	PEL-OSHA	VAPOR PRESSURE MM HG AT DEG F
TEXANOL	25265-77-4	<5%	not established		0.04 / 68
HEXYLENE GLYCOL	107-41-5	<5%	25 mg/l	25 ppm	0.05 / 68

NOTE: This product contains no substances listed by IARC, OSHA or NTP as carcinogenic. It contains pigments such as iron oxide or titanium dioxide that may be dust hazards in their original dry powder form but are not hazardous in wet paint. A paint preservative (CAS #62-38-4) has been added to control microorganisms at levels not considered hazardous.

III - PHYSICAL PROPERTIES

BOILING POINT: 212 deg F(water) DENSITY: 8-11 #/gal VAPOR DENSITY: lighter than air(water vapor)
PERCENT VOLATILE: 60-75% (by volume) EVAPORATION RATE: slower than ether

IV - FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION: Not regulated
FLASH POINT: >200 deg F FLAMMABLE LIMITS: n/a EXTINGUISHING MEDIA: n/a
FIRE AND EXPLOSION HAZARDS: Closed containers may explode(due to the build-up of steam pressure) when exposed to extreme heat.
SPECIAL FIREFIGHTING PROCEDURES: None

V - REACTIVITY DATA

STABILITY: Stable CONDITIONS TO AVOID: n/a
INCOMPATIBILITY(MATERIALS TO AVOID): Strong oxidizing agents
HAZARDOUS DECOMPOSITION PRODUCTS: May produce hazardous fumes when heated to decomposition as in welding.

PREPARED BY:

Julian Schaffer

DATE: 7/23/91

WI

MATERIAL SAFETY DATA SHEET

essentially similar to form OSHA-174

KELLY-MOORE PAINT CO., INC.
1015 COMMERCIAL ST., SAN CARLOS, CA 94070

EMERGENCY PHONE: 800-424-9300 (Chemtrec) INFORMATION PHONE: 415-592-8357

I - PRODUCT IDENTIFICATION

PRODUCT NAME	PRODUCT NUMBER	HMIS CODES: H F R PP
ACRY-SHIELD ACRYLIC FLAT FINISH 1240-Series (all colors)		0 0 0 E

II - HAZARDOUS INGREDIENTS

INGREDIENT	CAS REG #	WT PCT	TLV-ACGIH	PEL-OSHA	VAPOR PRESSURE MM HG AT DEG F
BARIUM METABORATE	13701-59-1	0-2%	0.5 mg/M3	0.5 mg/M3	none
ETHYLENE GLYCOL	107-21-1	<5%	50 ppm	50 ppm	0.1 / 68
SILICA crystalline	14464-45-1	10-15%	0.05 mg/M3	n/a	none
TEXANOL	25265-77-4	<5%	not established		0.04 / 68

NOTE: This product contains pigments such as mineral silicates, silicon dioxide and titanium dioxide, which are not hazardous in wet paint but may reach hazardous levels in dusts generated from sanding or grinding of dried paint. Like most naturally occurring minerals, the pigments contain some crystalline silica. IARC has determined that there is limited evidence for the carcinogenicity of crystalline silica to humans, with the risk depending on the duration and level of exposure. This product contains no other substances listed by OSHA, IARC or NTP as carcinogenic. A paint preservative (CAS #62-38-4) has been added to control microorganisms at levels not considered hazardous.

III - PHYSICAL PROPERTIES

BOILING POINT: 212 deg F (water) DENSITY: 11-12#/gal VAPOR DENSITY: lighter than air (water vapor)
PERCENT VOLATILE: 55-60% (by volume) EVAPORATION RATE: slower than ether

IV - FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION: Not regulated
FLASH POINT: >200 deg F FLAMMABLE LIMITS: n/a EXTINGUISHING MEDIA: n/a
FIRE AND EXPLOSION HAZARDS: Closed containers may explode (due to the build-up of steam pressure) when exposed to extreme heat.
SPECIAL FIREFIGHTING PROCEDURES: None

V - REACTIVITY DATA

STABILITY: Stable CONDITIONS TO AVOID: n/a
INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizing agents
HAZARDOUS DECOMPOSITION PRODUCTS: May produce hazardous fumes when heated to decomposition as in welding.
HAZARDOUS POLYMERIZATION: Will Not Occur. CONDITIONS TO AVOID: n/a

PREPARED BY:

G. Schaefer

DATE:

5/15/91

WII

MATERIAL SAFETY DATA SHEET

Manufacturer: ALDRAN CHEMICAL, INC.

391 Forbes Blvd.

Emergency Phone: (415) 952-3378

1... SO. SAN FRANCISCO, CA 94080

2... (415) 952-3378 (408) 280-1799

1/Zip: Outside CA 800 332-2244

Location: N/A

Locations

Trade Name/Synonyms: Top Coat

Chemical Name/Synonyms: N/A

Chemical Family: N/A

Formula: N/A

Product Code: 55120

***** HAZARDOUS INGREDIENTS *****

Does product contain hazardous ingredients? (Y,N,N/A,N/I): YES
Chemical/Common Name CAS-Number PEL-OSHA TLV-ACGIH
OPANOL 67-63-0 5-10 200 PPM 400 PPM

Does product contain carcinogens? (NTP IARC OSHA) (Y,N,N/A,N/I): NO

***** HEALTH HAZARD DATA *****

Health Effects (Acute and Chronic)
S- MAY IRRITATE EYES. INGESTION- MAY IRRITATE GASTROINTESTINAL TRACT.

Routes of entry
Exposure conditions aggravated by exposure

Emergency first aid procedures
ONLY FOLLOW DIRECTIONS BELOW: CALL A POISON CONTROL CENTER OR PHYSICIAN.
QUICK MEDICAL ATTENTION IF ANY ILL EFFECTS CONTINUE OR DEVELOP LATER.
EYES- FLUSH EYES WITH PLENTY OF WATER WHILE REMOVING ANY CONTACT LENSES. THEN HOLD EYELIDS OPEN AND CONTINUE FLUSHING FOR 15 MINUTES.
INGESTION- IF UNCONSCIOUS VICTIM- IMMEDIATELY RINSE MOUTH WITH WATER. SPIT OUT RINSE, THEN SWALLOW A GLASSFUL OF WATER. GET IMMEDIATE MEDICAL ATTENTION.

***** CHEMICAL DATA *****

Boiling Point (F) 210 Specific Gravity (Water=1) 1.13
Vapor Pressure (MMHG) 19 Melting Point (F) N/A
Vapor Density (air=1) <1 Evap Rate (9: ACETATE) <1
Solubility in Water COMPLETE
Appearance and Odor Information
CLEAR, YELLOW LIQUID PLEASANTLY SCENTED.

***** PHYSICAL HAZARD DATA *****

Flash Point (Method Used) 102 F (TCC) Flammable Limits-LEL= 2 UEL= 12
Extinguishing Media

Special Fire Fighting Procedures
None Required
Usual Fire and Explosion Hazards

***** REACTIVITY DATA *****

Compatibility (Materials to Avoid)
None
Hazardous Decomposition Products
GASES OF CARBON MAY BE FORMED UPON COMBUSTION.
Does hazardous polymerization occur?

Conditions to avoid/polymerization
None
Is the product stable?
None
Conditions to avoid/stability

MATERIAL SAFETY DATA SHEET

ALDRAN CHEMICAL

JULY 1, 1989

CHEMICAL NAME: BIG-A
SYNONYMS: BIG-A
FORMULA: PROPRIETARY
TRADE NAME AND SYNONYM: BIG-A
CHEMICAL FAMILY: NONE
CAS NUMBER #: NONE FOR MIX

SECTION 1 MANUFACTURER OR SUPPLIER
&
EMERGENCY NUMBER

ALDRAN CHEMICAL 391 FORBES BLVD SOUTH SAN FRANCISCO, CA 94080

(415) 952-3378

SECTION 2 PHYSICAL DATA

PHYSICAL STATE AT STP: LIQUID
BOILING POINT: F 200
SPECIFIC GRAVITY: H2O=1 1.1
VAPOR DENSITY: AIR=1 NOT AVAILABLE
EVAPORATION RATE: 1

APPEARANCE & ODOR: CLEAR
PERCENT VOLATILE: 95%
VAPOR PRESSURE: 700
SOLUBILITY IN WATER: 100 X
MELTING POINT: F NOT AVAILABLE

SECTION 3 HAZARDOUS COMPONENTS

MATERIAL:
NONE

CAS #: EXPOSURE LIMITS IN AIR:
 ACGIH TLV: OSHA PEL:



ALDRAN CHEMICAL, INC.
MANUFACTURERS-COMPOUNDERS-DISTRIBUTORS

391 Forbes Blvd. So. San Francisco, CA 94080
 (415)952-3378. (800)969-3378. FAX#(415)952-0568

PRODUCT RED OIL FURNITURE POLISH

HAZARD RATING

N	4 - EXTREME
F	3 - HIGH
P	2 - MODERATE
A	1 - SLIGHT
	0 - INSIGNIFICANT

0 1 0
0 0 0

Reacts Toxicity Special

SECTION I

1	ALDRAN CHEMICAL, INC.	
2	391 Forbes Blvd. SO. SAN FRANCISCO, CA 94080	
3	CHEMICAL NAME OR FAMILY PETROLEUM OIL, NF	FORMULA A mix of liquid hydrocarbons refined from petroleum.
	EMERGENCY TELEPHONE (504) 366-728 MANUFACTURER (415) 756-2210 CHEM TREC 1-(800) 424-9300	

SECTION II CHEMICAL AND PHYSICAL PROPERTIES

HAZARDOUS DECOMPOSITION PRODUCTS		CHEMICAL	PHYSICAL
4	Upon combustion, CO ₂ and CO are generated.		FORM Viscous liquid
5	INCOMPATIBILITY (KEEP AWAY FROM) Keep away from flame, heat (150°F max.), and strong oxidizing agents.		ODOR None
6	LIST ALL TOXIC AND HAZARDOUS INGREDIENTS None		APPEARANCE RED
7			COLOR None
			SPECIFIC GRAVITY (WATER = 1) < 1.0 @ 15°C

SECTION III FIRE AND EXPLOSION DATA

8	SPECIAL FIRE FIGHTING PROCEDURES Self-contained breathing apparatus is recommended for firefighters. Water-spray must be used with caution to prevent spread of flames.	FLASH POINT (METHOD USED) ASTM D-92 25 > 120 °C > 250 °F	FORM IBP
9	UNUSUAL FIRE AND EXPLOSION HAZARDS None	FLAMMABLE LIMITS % NDA	MELTING PT. NA °C
10		EXTINGUISHING AGENTS <input checked="" type="checkbox"/> DRYCHEMICAL <input checked="" type="checkbox"/> CO ₂ <input checked="" type="checkbox"/> WATERSPRAY <input checked="" type="checkbox"/> FOAM <input checked="" type="checkbox"/> WATERFOG <input checked="" type="checkbox"/> SAND/EARTH	SOLUBILITY IN WATER AT 25 °C Negligible
11		OTHER	% VOLATILE (BY WT %) Nil @ 25°C
12			EVAP. RATE Nil @ 25°C
13			VAPOR PRESSURE (mm Hg at 20°C) < .5mm
14			VAPOR DENSITY (AIR = 1) NA
15			pH AS IS NA
16			STRONG ACID _____
17			STRONG BASE _____
18			STABLE _____
19			UNSTABLE _____
20			VISCOSITY SUS AT 100 °F < 100 & 100 OR > C
21			CAS #8042-47-5

SECTION IV HEALTH HAZARD DATA

22	PERMISSIBLE CONCENTRATIONS (AIR) See Section IX - COMMENTS.
23	EFFECTS OF OVEREXPOSURE NDA
24	TOXICOLOGICAL PROPERTIES NDA
25	EMERGENCY FIRST AID PROCEDURES
26	EYES - Flush with water. If irritation exists consult a physician.
27	SKIN CONTACT - NA
28	INHALATION - NA
29	IF SWALLOWED - Do not induce vomiting. Call a physician.

NA = NOT APPLICABLE

NOA = NO DATA AVAILABLE

< = LESS THAN

> = MORE THAN

Material Safety Data Sheet

LM

Section I

Manufacturer's Name Darworth Company		Emergency Telephone No. 1-203-677-7721	
Address (Number, Street, City, State, Zip Code) P.O. Box K, Tower Lane; Avon, CT 06001			
Chemical Name & Synonyms N/A		Trade Name & Synonyms Cuprinol® Semi-transparent Stain & Wood Preservative-Water Cleanup	
Chemical Family Linseed Oil Based Stain	Formula N/A	C.A.S. Number N/A	

CODIOL GREEN

Section II - Hazardous Ingredients

Ingredient	CAS#	Percent
2-BUTOXYETHANOL	111-76-2	3.3
T.L.V.*: 25 ppm, 120 mg/m ³ -SKIN		P.E.L.: 50 ppm, 240mg/m ³ -SKIN (OSHA)
Ingredient	CAS #	Percent
TETRACHLOROISOPHTHALONITRILE	1897-45-6	0.70-0.86
T.L.V.: N/A		P.E.L.: N/A
Ingredient	CAS#	Percent
BIS-(TRI-N-BUTYL TIN) OXIDE	56-35-9	0.54
T.L.V.*: 0.1 mg Tin/m ³ -SKIN		P.E.L.: N/A

* THRESHOLD LIMIT VALUE - TWA, ACGIH

Section III - Physical Data

Boiling Point: 212-343° F**	Specific Gravity: 1.04
Vapor Pressure: 0.6 mm Hg @ 20° C ***	Percent Volatile: 79.5 (vol.)

Section III continued on Page 2

** of 2-BUTOXYETHANOL AND WATER
*** of 2-BUTOXYETHANOL

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: TUFFY LIQUID
CONTACTS: NA

DATE: JAN 23, 1994

*****SECTION 1 - PRODUCT IDENTITY AND SOURCE*****

CHEMICAL DESCRIPTION: Slightly alkaline water based cleaner
SUPPLIERS NAME: ALDRAN CHEMICAL, INC
ADDRESS: 391 FORBES BLVD., SO. SAN FRANCISCO, CA 94080
EMERGENCY PHONE: NA
CHEMICAL FAMILY: WATER BASED CLEANER FORMULA: PROPRIETARY
TO REORDER: 415-952-3378

*****SECTION 2- COMPOSITION AND INGREDIENT INFORMATION*****

REPORTING REQUIRED BY TITLE III SEC 313 OR 40 CFR 372 (*)

CAS#	MATERIAL OR COMPONENT	%	EXPOSURE LIMIT VALUES		
			TLV*	TWA	OTHER/REMARKS

CONTAINS NO HAZARDOUS INGREDIENTS ACCORDING TO THESE LISTS

NO COMPONENTS ARE LISTED IN "THRESHOLD LIMIT VALUES AND BIOLOGICAL EXPOSURE INDICES FOR 1992-1993" FROM AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS (ACGIH) EXCEPT AS ABOVE.

*****SECTION 3 - HAZARDS IDENTIFICATION*****
EMERGENCY OVERVIEW

No unusual fire or spill hazard. Avoid contact with skin and eyes.

HMS RATINGS: ACUTE HEALTH 0 FIRE 0 REACTIVITY 0 OTHER NA
HAZARD RATINGS: LEAST:0, SLIGHT:1, MODERATE:2, HIGH:3, EXTREME:4

THRESHOLD LIMIT VALUE: Not established on product.

EFFECTS OF CHRONIC OVER EXPOSURE:

SKIN: Can cause irritation, redness, from defatting skin.
EYES: Can cause severe irritation, redness, tearing, blurred vision.
INHALATION: not a likely source of exposure
INGESTION: Can cause gastrointestinal irritation, nausea, vomiting, and diarrhea.

REPRODUCTIVE IMPLICATIONS:..X..None

INGREDIENT ON CANCER LISTS:..X..NONEOSHA.....NTP....IARC

*****SECTION 4 - FIRST AID MEASURES*****

EMERGENCY AND FIRST AID PROCEDURE:

SKIN: Flush with water until gone.
EYES: Flush with water for at least 15 min.
INHALATION: If affected, remove individual to fresh air.
INGESTION: Do not induce vomiting. Give victim large amounts of water. If vomiting does occur, give water again. Get medical attention immediately. Never give anything by mouth to an unconscious or convulsing person.

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: ~~STRIP IT~~

ISSUE DATE: JAN 20, 1994

CONTACTS: CHEM-TEL 800-255-3924: IDENTIFICATION CODE A-120

*****SECTION 1 - PRODUCT IDENTITY AND SOURCE*****

CHEMICAL DESCRIPTION: Alkaline pH, low surface tension water based cleaner
SUPPLIERS NAME: ALDRAN CHEMICAL, INC
ADDRESS: 391 FORBES BLVD., SO. SAN FRANCISCO, CA 94080
EMERGENCY PHONE: (800)-255-3924 CODE A-120
CHEMICAL FAMILY: Water based cleaner FORMULA: Proprietary
TO REORDER: 415-952-3378

*****SECTION 2- COMPOSITION AND INGREDIENT INFORMATION*****

REPORTING REQUIRED BY TITLE III SEC 313 OR 40 CFR 372 (*)

CAS#	MATERIAL OR COMPONENT	%	EXPOSURE LIMIT VALUES		
			TLV*	TWA	OTHER/REMARKS
141-43-5	Ethanol amine	3-5%		3 ppm	
1310-58-3	Potassium Hydroxide	3-5%		C2 AIRBORNE	

NO COMPONENTS ARE LISTED IN "THRESHOLD LIMIT VALUES AND BIOLOGICAL EXPOSURE INDICES FOR 1992-1993" FROM AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS (ACGIH) EXCEPT AS ABOVE.

*****SECTION 3 - HAZARDS IDENTIFICATION*****

EMERGENCY OVERVIEW:

No unusual fire or spill hazard. Avoid contact with skin and eyes.

HMS RATINGS: ACUTE HEALTH 2 FIRE 0 REACTIVITY 0 OTHER NA
HAZARD RATINGS: LEAST:0, SLIGHT:1, MODERATE:2, HIGH:3, EXTREME:4

THRESHOLD LIMIT VALUE: Not established on product.

EFFECTS OF CHRONIC OVER EXPOSURE:

- SKIN: Can cause irritation, redness, from defatting skin.
- EYES: Can cause severe irritation, redness, tearing, blurred vision.
- INHALATION: not a likely exposure, but could irritate nasal passages.
- INGESTION: Can cause gastrointestinal irritation, nausea, vomiting, and diarrhea.

REPRODUCTIVE IMPLICATIONS:..X..None

INGREDIENT ON CANCER LISTS:..X..NONEOSHA.....NTP....IARC

*****SECTION 4 - FIRST AID MEASURES*****

EMERGENCY AND FIRST AID PROCEDURE:

- SKIN: Flush with water until gone.
- EYES: Flush with water for at least 15 min.
- INHALATION: If affected, remove individual to fresh air.
- INGESTION: Do not induce vomiting. Give victim large amounts of water. If vomiting does occur, give water again. Get medical attention immediately. Never give anything by mouth to an unconscious or convulsing person.

MATERIAL SAFETY DATA SHEET

SCRUBLESS SPECIAL

5/94
CODE 1047

MANUFACTURERS NAME AND ADDRESS:
ALDRAN CHEMICAL, INC.
391 Forbes Blvd.
So. San Francisco, CA 94080

INFORMATION PH#: 415-952-3378
EMERGENCY PH#: 800-255-3924 I.D. Code# A116

SIGNATURE:

DATE PREPARED: 10/20/93

SECTION I - PRODUCT IDENTIFICATION

PRODUCT: **SCRUBLESS SPECIAL**
DESCRIPTION, CHEMICAL MIXTURE: DETERGENT

SECTION II - HAZARDOUS INGREDIENTS

CAS NUMBER	CHEMICAL COMPONENT	%	TLV (Units)	HAZARD DATA
6834-92-0	Sodium Metasilicate	<35		Severely irritating eyes, skin and mucous membranes.
1886-81-3	Sodium Dodecylbenzene Sulfonate	<5		

SECTION III - PHYSICAL DATA

SOLID: X LIQUID: APPEARANCE AND ODOR: Off-White, granular powder with mild soap odor

SPECIFIC GRAVITY: 52.5 lbs/ft3 pH at 25°C: (4% solution) 12.4

SOLUBILITY IN WATER: Complete FREEZING POINT: N/A

PERCENT VOLATILES (By Weight) None PHOSPHORUS: 12.4% P

SECTION IV - FIRE AND EXPLOSIVE HAZARD DATA

FLASH POINT (method): N/A FLAMMABLE LIMITS: Not Combustible

LFL: UFL:

EXTINGUISHING MEDIA: Water, water fog.

SPECIAL FIRE HAZARDS AND EQUIPMENT REQUIRED: Product makes alkaline solution when dissolved in water. Good fire fighting practice dictates the use of self-contained breathing apparatus and turn-out gear for fires in the areas where product is stored.

SECTION V - REACTIVE HAZARDS

PRODUCT REACTIVE: Yes UNSTABLE AT: °F °C

HAZARDOUS POLYMERIZATION: None

CONDITIONS TO AVOID: Do not mix with acids. Will release heat.

INCOMPATIBILITY (MATERIALS TO AVOID): Avoid mixing with acids.

MATERIAL SAFETY DATA SHEET
SECTION I

SUPPLIERS NAME: ALDRAN MANUFACTURING, INC.

415-952-3378

ADDRESS: 391 FORBES BLVD. , SO SAN FRANCISCO, CA 94080

EMERGENCY PHONE: 800-255-3924

PRODUCT NAME: ELIMINATOR

HMIS

HEALTH.....	1
FLAMMABILITY.....	2
REACTIVITY.....	0
PROTECTION.....	G

CHEMICAL FAMILY: CITRUS TERPENES

FORMULA: PROPRIETARY
ALDRAN CODE: A112

SHIPPING CLASSIFICATIONS:

Proper Shipping Name: Terpene Hydrocarbons , N.O.S.

Hazard Class: 3

Identification Number: UN 2319

Packaging Group: III

Label/Placard (exemption § 173.150(f) applies):

Highway/Rail: per require. for COMBUSTIBLE LIQUIDS

Air/Ship: per require. for FLAMMABLE LIQUIDS

SECTION II - HAZARDOUS INGREDIENTS AND/OR THOSE SUBJECT TO REPORTING
*REQUIREMENTS OF TITLE III SEC 313 OR 40 CFR 372

EXPOSURE LIMIT VALUES

~~D-LIMONENE~~

CAS# 5989-27-5

TLV

TWA

OTHER/REMARKS

CONTAINS NO MATERIALS ON THE "THRESHOLD LIMIT VALUES & BIOLOGICAL EXPOSURE INDICES FOR 1989-90" OF ACIGH EXCEPT AS INDICATED ABOVE. *THIS INFORMATION MUST BE INCLUDED IN ALL MSDS's THAT ARE COPIED AND DISTRIBUTED FOR THIS MATERIAL. D-LIMONENE (SOLVENT) IS THE MAJOR COMPONENT (TECHNICAL GRADE 95%) WITH BALANCE OTHER TERPENE HYDROCARBONS AND OXYGENATED COMPOUNDS. PRODUCT IS A BY-PRODUCT OF CITRUS, ENTIRELY OF NATURAL ORIGIN, AND THO THE BEST OF OUR KNOWLEDGE AND BELIEF CONTAINS NO ARTIFICIAL FLAVORS, SULFITES, NITRITES, OR PESTICIDE RESIDUE EXCEEDING TOLERANCES ESTABLISHED BY THE FDA.

SECTION III - PHYSICAL DATA

BOILING POINT:	310°F	FLASH POINT:	115°F
DENSITY:	<1	VAPOR PRESSURE:	2mm Hg @ 20°C
VAPOR DENSITY (AIR=1):	>1	SOLUBILITY IN WATER, %:	NIL
SPECIFIC GRAVITY:	0.838-0.843 @ 25°C	SELF EMULSIFYING:	NO
%VOLATILES BY VOLUME:	95+%	EVAPORATION RATE (nBA=1):	<1
pH:	NOT APPLICABLE FOR OILS	VISCOSITY @ 25°C:	WATER THIN

APPEARANCE AND ODOR: WATER WHITE LIQUID WITH A CITRUS ODOR

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: ~~PENTECT BULK~~ ISSUE DATE: FEB 28, 1994
CONTACTS: EMERGENCY PHONE: (800)-255-3924 CHEM-TEL CODE: A128

TO ORDER: (415)-952-3378

*****SECTION 1 - PRODUCT IDENTITY AND SOURCE*****

CHEMICAL DESCRIPTION: Corrosien protective coating
SUPPLIERS NAME: ALDRAN CHEMICAL, INC
ADDRESS: 391 FORBES BLVD., SO. SAN FRANCISCO, CA 94080
EMERGENCY PHONE: (800)-255-3924
CHEMICAL FAMILY: Petroleum solvent base FORMULA: Proprietary

*****SECTION 2- COMPOSITION AND INGREDIENT INFORMATION*****

REPORTING REQUIRED BY TITLE III SEC 313 OR 40 CFR 372 (*)

CAS#	MATERIAL OR COMPONENT	EXPOSURE LIMIT VALUES	TLV* TWA OTHER/REMARKS
64742-88-7	Petroleum solvent	100ppm	OSHA PEL: 500ppm

NO COMPONENTS ARE LISTED IN "THRESHOLD LIMIT VALUES AND BIOLOGICAL EXPOSURE INDICES FOR 1992-1993" FROM AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS (ACGIH) EXCEPT AS ABOVE.

*****SECTION 3 - HAZARDS IDENTIFICATION*****
EMERGENCY OVERVIEW

Typical combustibile liquid fire hazard. Avoid contact with skin and eyes

EHIS RATINGS: ACUTE HEALTH 0 FIRE 2 REACTIVITY 0 OTHER NA
HAZARD RATINGS: LEAST:0, SLIGHT:1, MODERATE:2, HIGH:3, EXTREME:4

THRESHOLD LIMIT VALUE: Not established on product.

- EFFECTS OF CHRONIC OVER EXPOSURE:
- SKIN: Can cause irritation, redness, from defatting skin.
- EYES: Can cause irritation, redness, tearing, blurred vision.
- INHALATION: extended exposure can produce headaches, nausea, possible unconsciousness and asphyxiation.
- INGESTION: Can cause gastrointestinal irritation, nausea, vomiting, and diarrhea. Aspiration into lungs can cause chemical pneumonitis which can be fatal.
- REPRODUCTIVE IMPLICATIONS: .X..None
- INGREDIENT ON CANCER LISTS: .X..NONEOSHA.....NTP.....IARC

*****SECTION 4 - FIRST AID MEASURES*****

- EMERGENCY AND FIRST AID PROCEDURE:
- SKIN: Wash with soap and water until product washes away.
- EYES: Flush with water for at least 15 min. See a physician.
- INHALATION: If affected, remove individual to fresh air.
- INGESTION: Do not induce vomiting. Give victim large amounts of water. If vomiting does occur, give water again. Get medical attention immediately. Never give anything by mouth to an unconcious or convulsing person.

ALDRAN MANUFACTURING, INC.

CUSTOMER INVOICE : 4613426

184613426
PAGE 1
38-0030207

MATERIAL SAFETY DATA SHEET
FOR COATINGS, RESINS, AND RELATED MATERIALS
COMPLIES WITH 29CFR 1910.1200 (THE HAZARD COMMUNICATION STANDARD)

DATE OF PREP:
8-20-88 L

#721

MANUFACTURER'S NAME: Aldran Chemical, Inc.

STREET ADDRESS: 391 Forbes Blvd.

CITY, STATE, ZIP CODE: SO. SAN FRANCISCO, CA 94080

EMERGENCY: (800) 255-3924

INFORMATION TELEPHONE NO.:

(415) 952-3378

SECTION I - PRODUCT IDENTIFICATION

PRODUCT NAME: **K-Seal**

PRODUCT CLASS: FLOOR FINISH CONC.

SECTION II - HAZARDOUS INGREDIENTS

INGREDIENT	CAS-NO.	WT.	OCCUPATIONAL EXPOSURE LIMITS			VAPOR PRESSURE @68 F
			PEL	PPM	TLV	
ETHYLENE GLYCOL	107-21-1	2	NE		50	NA
METHYL CARBITOL	111-77-3	6	NE		NE	0.25
DIBUTYL PHTHALATE	84-74-2	2	5.00		5.00	0.01
MG/H3						

NE = NOT ESTABLISHED

NA = NOT APPLICABLE

NK = NOT KNOWN

SECTION III - PHYSICAL DATA

BOILING RANGE: ABOVE 212 F PH: 9 VAPOR DENSITY: ---HEAVIER---X--- LIGHTER THAN AIR

EVAPORATION RATE: ---FASTER---X--- SLOWER THAN ETHER

% VOLATILE BY VOLUME: 66 WEIGHT PER GALLON: 8.76 LBS. APPEARANCE AND OOR: MILKY LIQUID WITH SWEET OOR

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION: OSHA NONE DOT: NOT REGULATED
FLASH POINT: NA LEL: NA

EXTINGUISHING MEDIA: NONE REQUIRED.

UNUSUAL FIRE AND EXPLOSION HAZARDS: CLOSED CONTAINERS MAY EXPLODE (DUE TO BUILD-UP OF STEAM PRESSURE) WHEN EXPOSED TO EXTREME HEAT.

SPECIAL FIREFIGHTING PROCEDURES: WATER MAY BE USED TO COOL CONTAINERS TO PREVENT PRESSURE BUILD-UP AND POSSIBLE EXPLOSION WHEN EXPOSED TO EXTREME HEAT.

SECTION V - HEALTH HAZARD DATA

PERMISSIBLE EXPOSURE LEVEL - SEE SECTION II

THRESHOLD LIMIT VALUE - SEE SECTION II