

RECEIVED

By Alameda County Environmental Health 9:42 am, Dec 14, 2015

Project No. **7828.000.001**

December 11, 2015

Mr. Jerry Wickham Alameda County Environmental Health 1131 Harbor Bay Parkway Alameda, CA 94502-6577

Subject: Jordan Ranch Parcel H – Former Leaking Underground Storage Tank

Dublin, California

ACEH Case No. R00002918

MONITORING WELL ABANDONMENT LETTER

Dear Mr. Wickham:

We prepared this letter to document the abandonment of the eight groundwater monitoring wells and six soil gas wells located at the Jordan Ranch Parcel H (site).

The abandonment was performed by a C-57 driller on December 10, 2015. The abandonment was completed by removing the well boxes and grouting the borings in accordance with the approved permit from Zone 7 Water Agency. The well specifications are provided below.

Well ID	Total Depth (feet)	Screen Zone (feet)	Casing Diameter (inches)
MW-1	30	15 - 30	2
MW-2	30	15 - 30	2
MW-4	30	15 - 30	2
MW-5	30	15 - 30	2
MW-6A	29	9-29	2
MW-6B	30	20-30	2
MW-7A	29	9-29	2
MW-7B	30	20-30	2
SG-1	6	5.9-6	1/4
SG-2	6	5.9-6	1/4
SG-3	6	5.9-6	1/4
SG-4	6	5.9-6	1/4
SG-5	6	5.9-6	1/4
SG-6	6	5.9-6	1/4

No. HG 413

CERTIFIED
HYDROGEOLOGIST

REPORTING

We prepared well completion reports (attached) documenting the well destruction specifications. The original hard copies will be sent to Department of Water Resources, Central District Office.

GEOTRACKER

We reviewed the GeoTracker case file for completeness and performed the necessary data file uploads for the project including: EDF, GEO_XY, GEO_Z, GEO_MAP, GEO_REPORT, GEO_WELL, FIELD_POINTS. To date, all applicable data has been uploaded to the GeoTracker case file.

If you have any questions regarding this letter or need assistance with the no further action (NFA) determination, please contact us.

Shawn Munger, CHG

Sincerely,

ENGEO Incorporated

Morgán Johnson mj/sm/bvv

Attachments: Figures

DWR Well Completion Reports Zone 7 Water Agency Permit

Perjury Statement



FIGURES

Figure 1 Vicinity Map Figure 2 Site Map







BASE MAP SOURCE: GOOGLE EARTH MAPPING SERVICE



COPYRIGHT

VICINITY MAP JORDAN RANCH - PARCEL H DUBLIN, CALIFORNIA

PROJECT NO.: 7828.000,001 DATE: AS SHOWN CHECKED BY: SM DRAWN BY: SRP

FIGURE NO.





DWR Well Completion Reports

STATE OF CALIFORNIA DWR WELL COMPLETION REPORT (WELL LOGS)

STATE OF CALIFORNIA DWR WELL COMPLETION REPORT (WELL LOGS)

STATE OF CALIFORNIA DWR WELL COMPLETION REPORT (WELL LOGS)

STATE OF CALIFORNIA DWR WELL COMPLETION REPORT (WELL LOGS)

STATE OF CALIFORNIA DWR WELL COMPLETION REPORT (WELL LOGS)

STATE OF CALIFORNIA DWR WELL COMPLETION REPORT (WELL LOGS)

STATE OF CALIFORNIA DWR WELL COMPLETION REPORT (WELL LOGS)

STATE OF CALIFORNIA DWR WELL COMPLETION REPORT (WELL LOGS)



Zone 7 Water Agency Permit

ZONE 7 WATER AGENCY

100 NORTH CANYONS PARKWAY, LIVERMORE, CALIFORNIA 94551 VOICE (925) 454-5000 FAX (925) 245-9306 E-MAIL whong@zone7water.com

DRILLING PERMIT APPLICATION

FOR APPLICANT TO COMPLETE	FOR OFFICE USE
LOCATION OF PROJECT 4233 Fallon Rd	PERMIT NUMBER 2015159
Dublin, CA	WELL NUMBER MW-1 to MW-5, MW6A, 6B, 7A & 7E APN 985-0098-006-00
Coordinates Sourceft. AccuracyVft. LAT: 37.711293	PERMIT CONDITIONS (Circled Permit Requirements Apply)
CLIENT BJP-ROF Jordan Ranch, LLC Address 5000 Hopyard Rd, 170 Phone 925-467-9900 City Pleasanton. CA Zip 94588 APPLICANT Name Same as above Email Ravi@missionvalleyhomes.com Fax Address Phone City Zip	A. GENERAL 1. A permit application should be submitted so as to arrive at the Zone 7 office five days prior to your proposed starting date. 2. Submit to Zone 7 within 60 days after completion of permitted work the original Department of Water Resources Water Well Drillers Report (DWR Form 188), signed by the driller. 3. Permit is void if project not begun within 90 days of approval date. 4. Notify Zone 7 at least 24 hours before the start of work.
TYPE OF PROJECT: Well Construction	 WATER SUPPLY WELLS Minimum surface seal diameter is four inches greater than the well casing diameter and six inches for public wells. Minimum seal depth is 50 feet for municipal and industrial wells or 20 feet for domestic and irrigation wells unless a lesser depth is specially approved. Grout placed by tremie. An access port at least 0.5 inches in diameter is required on the wellhead for water level measurements. A sample port is required on the discharge pipe near the wellhead.
DRILLING METHOD: Mud Rotary Air Rotary Hollow Stem Auger Cable Tool Direct Push X Other Grout only and remove DRILLING COMPANY Cascade Drilling well boxe DRILLER'S LICENSE NOC57-938110	The second secon
WELL SPECIFICATIONS: Drill Hole Diameter in. Maximum 30 Casing Diameter 2 in. Depth 30 Surface Seal Depth tt. Number 9 groundwater and 6 soil gas	D. GEOTECHNICAL. Backfill bore hole with compacted cuttings or heavy bentonite and upper two feet with compacted material. In areas of known or suspected contamination, tremied cement grout shall be used in place of compacted cuttings.
SOIL BORINGS: Number of Borings Maximum Hole Diameter in. Depth ft.	E. CATHODIC. Fill hole above anode zone with concrete placed by tremie.
ESTIMATED STARTING DATE 12/10/15 ESTIMATED COMPLETION DATE 12/10/15	F. WELL DESTRUCTION. See attached.
I hereby agree to comply with all requirements of this permit and Alameda County Ordinance No. 73-68.	G. SPECIAL CONDITIONS. Submit to Zone 7 within 60 days after completion of permitted work the well installation report including all soil and water laboratory analysis results.
APPLICANT'S SIGNATURE Date	Approved My Approved Date 12/9/15 Wyman Hong

Zone 7 Water Resources Engineering Groundwater Protection Ordinance

BJP-ROF Jordan Ranch, LLC 4233 Fallon Road Dublin Wells MW-1 to MW-5, MW-6A, MW-6B, MW-7A, MW-7B and 6 soil gas wells Permit 2015159

Destruction Requirements:

- 1. Remove from the well any pump, appurtenances, debris, or other materials.
- 2. Sound the well as deeply as practicable and record for your report.
- 3. Fill casing with neat cement or cement grout sealing material to two feet below the finished grade and pressurize to 25 psi and maintain for 5 minutes, forcing the sealing material through the existing perforations and into the surrounding formation.
- 4. Release the pressure and refill the empty portion of the casing with grouting material allowing it to spill over the top of the casing to form a cap.
- 5. Cut and remove any casing(s) to two feet below the finished grade or original ground, whichever is the lower elevation (optional).
- 6. After the seal has set, backfill the remaining hole with compacted material.



12/8/2015

© 2014 Digital Map Products. All rights reserved.



Perjury Statement

Subject:

Jordan Ranch Property - Former Leaking Underground Storage Tank

Dublin, California

PERJURY STATEMENT

"I declare, that to the best of my knowledge at the present time, the information and/or recommendations contained in the attached document are true and correct."

Submitted by Responsible Party:

ROBERT RADADOVICH

BJP-ROF Jordan Ranch, LLC 5000 Hopyard Road, #170

Pleasanton, CA 94588