

ALAMEDA COUNTY
HEALTH CARE SERVICES
AGENCY

COLLEEN CHAWLA, Agency Director



DEPARTMENT OF ENVIRONMENTAL HEALTH
LOCAL OVERSIGHT PROGRAM (LOP)
For Hazardous Materials Releases
1131 HARBOR BAY PARKWAY
ALAMEDA, CA 94502
(510) 567-6700
FAX (510) 337-9335

August 28, 2018

USL Pleasant Lakes, L.P.
c/o Steven Dunn
4000 East Third Avenue, Suite 500
Foster City, CA 94404-4805
(Sent via E-mail to SDUNN@steelwavellc.com)

**Subject: Conditional Approval of Soil Import Management Plan
Site Cleanup Program Case No. RO0002941, RO0002952, & RO0003228
GeoTracker Global ID SLT19719376, SL0600101555, & T100000009398
Hanson Aggregates Radum Plant, Hanson Aggregates Legacy Radum Facility, & USL Pleasanton Lakes
3000 Busch Road, Pleasanton, CA 94566**

Dear Mr. Dunn

Alameda County Department of Environmental Health (ACDEH) has reviewed the case files associated with the above referenced property (the Site), including the *Soil Import Management Plan* dated August, 2018 (the "SIMP") prepared by Haley Aldrich on behalf of USL Pleasanton Lakes L.P. (USL Pleasanton) . Based on ACDEH's review of the case file and the SIMP, ACDEH issued an informal conditional approval of the SIMP in an email correspondence from ACDEH dated July 25, 2018. This directive letters is intended to serve as formal conditional approval for implementation of the SIMP. **Section I** of this letter presents ACDEH's Conditions of Approval. **Section II** presents ACDEH's request for deliverables.

I. CONDITIONS OF APPROVAL

As a condition of approval, ACDEH requires that the SIMP incorporate the following technical comments:

1. The submittal requirements of Section 2.4 of the SIMP must include the reporting elements described in Section 3 of ACDEH's *Fill Material Characterization Guidance* dated August 1, 2018 (the "FMCG").
2. The reporting requirements of Section 3 of the SIMP must include the reporting elements described in Section 4 of the FMCG. .

II. DELIVERABLES AND TECHNICAL REPORTS REQUEST

Please submit the following technical reports and deliverables to ACDEH (Attention: Jonathan Sanders) in accordance with the compliance dates provided below and the *Responsible Party(ies) Legal Requirements/Obligations* and the *File Names for Electronic Reports* which are included as **Attachment A** and **Attachment B** respectively.

1. **Soil Import Summary Report**
Compliance Date: January 30, 2019 and every 6 months thereafter in which fill import is conducted.

Please submit a Soil Import Summary Report documenting the import of fill materials during the previous operational period. Operational periods are semi-annual with the first operational period spanning from January to June and the second operational period spanning from July to December of each year. This report must include each of the elements identified in Section 4 of the FMCG. A copy of the FMCG is included as **Attachment C**.

III. CLOSING

ACDEH looks forward to continuing to work with you and your consultants to advance the case toward closure. Should you have any questions regarding this correspondence or your case, please contact the primary caseworker, Jonathan Sanders who can be reached by phone at (510)567-6791 or by email at jonathan.sanders@acgov.org.

Sincerely,



Dilan Roe, P.E. C73703
Chief
Land & Water Division



Jonathan Sanders
Senior Hazardous Materials Specialist
Local Oversight and Site Cleanup Program

IV. ENCLOSURES:

- Attachment A Responsible Party(ies) Legal Requirements / Obligations
- Attachment B File Names for Electronic Reports
- Attachment C Fill Material Characterization Guidance

V. DISTRIBUTION LIST:

Electronic File, GeoTracker

Dilan Roe, ACDEH, Chief Land & Water Division (Sent via E-mail to: dilan.roe@acgov.org)

Jonathan Sanders, ACDEH, Senior Hazardous Materials Specialist (Sent via E-mail to: jonathan.sanders@acgov.org)

Jason Grant, Haley Aldrich, Senior Project Manager (sent via E-mail to: JGrant@haleyaldrich.com)

ATTACHMENT A

Responsible Party(ies) Legal Requirements / Obligations

Alameda County Environmental Cleanup Oversight Programs (LOP and SCP)	REVISION DATE: December 14, 2017
	ISSUE DATE: July 25, 2012
	PREVIOUS REVISIONS: September 17, 2013, May 15, 2014, December 12, 2016
SECTION: ACDEH Procedures	SUBJECT: Responsible Party(ies) Legal Requirements / Obligations

REPORT & DELIVERABLE REQUESTS

Alameda County Department of Environmental Health (ACDEH) Cleanup Oversight Programs, Local Oversight Program (LOP) and Site Cleanup Program (SCP) require submission of all reports in electronic form to the State Water Board's (SWB) GeoTracker website in accordance with California Code of Regulations, Chapter 30, Division 3, Title 23 and Division 3, Title 27.

Leaking Underground Fuel Tank (LUFT) Cases

Reports and deliverable requests are pursuant to California Health and Safety Code Section 25296.10. 23 CCR Sections 2652 through 2654, and 2721 through 2728 outline the responsibilities of a responsible party (RP) in conjunction with an unauthorized release from a petroleum underground storage tank (UST) system.

Site Cleanup Program (SCP) Cases

For non-petroleum UST cases, reports and deliverables requests are pursuant to California Health and Safety Code Section 101480.

ELECTRONIC SUBMITTAL OF REPORTS

A complete report submittal includes the PDF report and all associated electronic data files, including but not limited to GEO_MAP, GEO_XY, GEO_Z, GEO_BORE, GEO_WELL, and laboratory analytical data in Electronic Deliverable Format™ (EDF). Additional information on these requirements is available on the State Water Board's website (http://www.waterboards.ca.gov/water_issues/programs/ust/electronic_submittal/)

- Do not upload draft reports to GeoTracker
- Rotate each page in the PDF document in the direction that will make it easiest to read on a computer monitor.

GEOTRACKER UPLOAD CERTIFICATION

Each report submittal is to include a GeoTracker Upload Summary Table with GeoTracker valid values¹ as illustrated in the example below to facilitate ACDEH review and verify compliance with GeoTracker requirements.

GeoTracker Upload Table Example

Report Title	Sample Period	PDF Report	GEO_MAPS	Sample ID	Matrix	GEO_Z	GEO_XY	GEO_BORE	GEO_WELL	EDF
2016 Subsurface Investigation Report	2016 S1	✓	✓	Effluent	SO	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	✓
2012 Site Assessment Work Plan	2012	✓	✓			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
2010 GW Investigation Report	2008 Q4	✓	✓	SB-10	W	✓	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	✓
				SB-10-6	SO	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	✓
				MW-1	WG	✓	✓	✓	✓	✓
				SW-1	W	✓	✓	✓	✓	✓

¹ GeoTracker Survey XYZ, Well Data, and Site Map Guidelines & Restrictions, CA State Water Resources Control Board, April 2005

Alameda County Environmental Cleanup Oversight Programs (LOP and SCP)	REVISION DATE: NA
	ISSUE DATE: December 14, 2017
	PREVIOUS REVISIONS: September 17, 2013, May 15, 2014, December 12, 2016
SECTION: ACDEH Procedures	SUBJECT: Responsible Party(ies) Legal Requirements / Obligations

ACKNOWLEDGEMENT STATEMENT

All work plans, technical reports, or technical documents submitted to ACDEH must be accompanied by a cover letter from the responsible party that states, at a minimum, the following: "I have read and acknowledge the content, recommendations and/or conclusions contained in the attached document or report submitted on my behalf to the State Water Board's GeoTracker website." This letter must be signed by the Responsible Party, or legally authorized representative of the Responsible Party.

PROFESSIONAL CERTIFICATION & CONCLUSIONS/RECOMMENDATIONS

The California Business and Professions Code (Sections 6731, 6735, and 7835) requires that work plans and technical or implementation reports containing geologic or engineering evaluations and/or judgments be performed under the direction of an appropriately licensed or certified professional and include the professional registration stamp, signature, and statement of professional certification. Additional information is available on the Board of Professional Engineers, Land Surveyors, and Geologists website at: <http://www.bpelsg.ca.gov/laws/index.shtml>.

UNDERGROUND STORAGE TANK CLEANUP FUND

For LUFT cases, RP's non-compliance with these regulations may result in ineligibility to receive grant money from the state's Underground Storage Tank Cleanup Fund (Senate Bill 2004) to reimburse the cost of cleanup. Additional information is available on the internet at: https://www.waterboards.ca.gov/water_issues/programs/ustcf/

AGENCY OVERSIGHT

Significant delays in conducting site assessment/cleanup or report submittals may result in referral of the case to the Regional Water Board or other appropriate agency, including the County District Attorney, for possible enforcement actions. California Health and Safety Code, Section 25299.76 authorizes enforcement including administrative action or monetary penalties of up to \$10,000 per day for each day of violation.

ATTACHMENT B

File Name for Electronic Reports

Alameda County Environmental Cleanup Oversight Programs (LOP and SCP)	REVISION DATE: April 4, 2018
	PREVIOUS REVISIONS: April 4, 2018, July 17, 2017, November 8, 2016, December 15, 2015, December 16, 2014, June 19, 2013, June 15, 2011, March 26, 2009, April 29, 2008
	ISSUE DATE: June 16, 2006
SECTION: Miscellaneous Administrative Topics & Procedures	SUBJECT: File Names for Electronic Reports

Format: REPORT_NAME_R_YYYY-MM-DD
Ex: SWI_R_VOL1_2006-05-25

LOP and SCP (VRAP) INCOMING REPORTS AND LETTERS	
Document Name	Abbreviation File Name= Abbreviation + Date (yyyy- mm-dd)
Abandoned Well Information/Water Supply Well Information	ABWELLINF_R
Addendum	ADEND_R (added after report name)
Additional Information Report	ADD_R
Analytical Reports (Loose data sheets not in report)	ANALYT_R
As Built Drawings (or Plans)	AS_BUILT
Case File Scanned By OFD	CASE_FILE
Cleanup and Abatement Report	CAO_R
Case Transfer Form (from CUPA)	CASE_TRNSFR_F
Conduit Study/Well Search/Sensitive Receptor/Well Survey/Preferential Pathway Study	COND_WELL_R
Corrective Action Plan (CAP)	CAP_R
Correspondence	CORRES_L
Court Injunctions	INJ_L
Development Entitlement	DEV_ENTITLE
Development Plans (Includes Plan Set, Cross-sections, and Related Drawings)	DEV_PLAN
Development Schedule (Project Schedule, Gant Chart, etc.)	DEV_SCHD
DWR Confidential Well Logs (Report containing)	report name_R_CONFIDENTIAL_YYYY-MM-DD (Ex: SWI_R_CONFIDENTIAL_YYYY-MM-DD)
DWR Well Completion Report-Confidential (Loose well logs)	DWR_WELL_CONFIDENTIAL_YYYY-MM-DD (Date of Well Log)
ESI/DAR (Environmental Site Investigation, Data Assessment Report)	ESI_R
Excavation Report	EX_R
Extension Request Letter	EXT_RQ_L

Fact Sheet	FACT_SHT
Feasibility Study	FEASSTUD_R
Groundwater Monitoring/Quarterly Summary Report	GWM_R
Financial Assurance/Letter of Credit	FNCL_ASSRNC_LOC
Interim Remedial Action Plan	IRAP_R
Interim Remediation Results (Includes Pilot Test Reports, Vapor Mitigation Reports, Soil Management Reports, Free Product Removal Reports, & Dual-Phase Extraction Reports)	IR_R
Lawsuit	LAWSUIT_R
Migration Control Report	MIG_R
Miscellaneous Report/Soil Sample	MISC_R
Miscellaneous Sample Report (analytical results)	MISC_SAMP_R
Notification Letter	NOT_L
NPDES Miscellaneous Reports	NPDES_R
Operations & Maintenance Plan	OM_P
Operations & Maintenance Report	OM_R
Pay for Performance	PFP_R
Petition	PETITION_R
Phase 1 Environmental Assessment Report	PHASE1_R
Photos	PHOTO
Preliminary Site Assessment Report/Phase 2 (historic reports only)	PSA_R
Remedial Action Plan	RAP_R
Remedial Design & Implementation Plan	RDIP_R
Remediation Progress Report	REM_R
Request for Closure	RFC(_L or _R)
Risk Assessment Report	RISK_R
Risk Based Corrective Action	RBCA_R
List of Landowners Forms	LNDOWNR_F
SB2004 Letter of Commitment	LOC_L
Site Conceptual Model/Conceptual Site Model	SCM_R
Site Health & Safety Plan	SFTY_PLAN_R
Site Management	SITE_MANAGE_R_
Acknowledgement Statement for Site Management Plan	SMP_ACK_L
Site Management Plan	SMP_R
Site Summary Report	SITE_SUM_R

Soil and Water Investigation Report (Includes soil gas/vapor reports, indoor, additional site investigation, well installation, site characterization, cross section, indoor air, additional onsite investigation, Phase II/preliminary site assessment)	SWI_R
Soil Disposal Report	SOIL_DSPL_R
Source Area Characterization	SOURCAREA_R
State Information	STATE_INFO (no date)
Status Report(monthly remediation status reports addressed to sanitary district requires no stamp/perjury letter)	STAT_R
Tank/Tank System Removal Report	TNK_R
Tentative Order Report	TENT_R
Unauthorized Release Form	URF_R
UST Sampling Report	UST_SAMP_R
USTCF 5 Year Review	USTCF_5YR
USTCF issued Public Notice	USTCF_PP_L
Well Construction Report (limited to water supply wells)	WELL_CST_R
Well Decommissioning Report/Letter (well destruction/abandonment)	WELL_DCM_R
Work Plan	WP_R

ATTACHMENT C

Fill Material Characterization Guidance

ALAMEDA COUNTY DEPARTMENT OF ENVIRONMENTAL HEALTH LOCAL OVERSIGHT PROGRAM	Revision Date: NA
	ISSUE DATE: August 1, 2018
	Previous Revisions: NA
SUBJECT: Fill Material Characterization Guidance	

INTRODUCTION:

This document has been prepared by Alameda County Department of Environmental Health (ACDEH) to provide guidance regarding the characterization of fill materials to determine: (a) the suitability of the fill material for import to sites within Alameda County, including but not limited to agricultural lands, redevelopment sites, and environmental cleanup sites, and (b) the suitability of the fill material for export from environmental cleanup sites regulated by ACDEH and re-use at other locations.

The use of imported fill material has recently come under scrutiny in Alameda County due to the identification of agricultural properties in rural portions of the county that have been importing large volumes of fill material. These areas have a diverse natural environment including biological habitats, aquatic environments, wetlands, and critical groundwater basins, which require protection and have the potential to be adversely impacted from contaminated fill material.

There are currently no established standards in the statutes or regulations that address environmental requirements for imported fill material. However, regulatory guidance documents have been developed by the California Environmental Protection Agency (CalEPA), Department of Toxic Substances Control (DTSC) and the San Francisco Regional Water Quality Control Board (the “Regional Water Board”) regarding the characterization and sourcing of imported fill material. The CalEPA guidance documents were prepared to address fill material being imported to active environmental cleanup sites, however, are also applicable to other sites where imported fill material may pose a risk to sensitive receptors and the environment.

This guidance document has been prepared by ACDEH to ensure that unsuitable fill material is not introduced onto properties with sensitive land uses and to provide clarification of the process of evaluating the suitability of fill material. This document addresses both human health and ecological risk associated with exposure pathways to fill material and identifies fill sources which are unsuitable for use as fill material based on current and historic land use activities as discussed in the CalEPA guidance documents and as required by other authorities specific to Alameda County. The protocols and criteria presented in this document are intended to be sufficiently conservative to be applicable to all sites regardless of land use or other site characteristics. Alternative criteria for fill characterization and suitability may be proposed for consideration by ACDEH via submittal of a site-specific soil import management plan and associated supporting technical documents.

This guidance document was prepared based on the following:

- (1) Regulatory guidance documents adopted by the DTSC and Regional Water Board;
- (2) Applicable risk based screening levels;
- (3) Regional background levels;
- (4) Other criteria provided to ACDEH by designated Groundwater Basin Managers within Alameda County; and
- (5) Accepted industry practices.

FILL MATERIAL CHARACTERIZATION GUIDANCE

August 1, 2018

Section 1 of this guidance document discusses criteria for assessing and identifying potentially suitable fill material sources. **Section 2** discusses the evaluation of the suitability of potential fill material. **Section 3** discusses ACDEH's fill material import suitability determination process. **Section 4** describes the conditions and reporting requirements for importing suitable fill material.

1. ASSESSMENT OF POTENTIALLY SUITABLE FILL MATERIAL SOURCES

Suitable fill materials are materials that will not have an adverse effect on human health or the environment when imported. Prior to collecting analytical data to confirm suitability of potential fill material, potential source areas should be screened based on historical land use and material composition.

Historic and current land use at, and in the vicinity of, the parcel containing the proposed fill material should be evaluated for environmental impacts to determine the applicable laboratory analysis that should be conducted to characterize the fill material. This assessment consists of the review of historical records and typically consists of conducting a phase one environmental site assessment (Phase I ESA) or preliminary environmental assessment (PEA) within six months of the assessment. The assessment should be sufficient to identify Recognized Environmental Conditions (RECs). RECs are typically associated with the production, use, storage, transport, recycling, or disposal of hazardous materials or waste at or in the vicinity of the parcel being evaluated and are used to determine what potential contaminants may be present and therefore should be analyzed for.

Fill material from parcels with the following conditions are not suitable for use as a proposed fill material source without additional evaluation and approval from ACDEH beyond what is required in this guidance:

- a. Regulated environmental cleanup sites; or
- b. Unaddressed or insufficiently addressed RECs; or
- c. Current or historic industrial land uses; or
- d. Current or historic unacceptable commercial land uses. Unacceptable commercial land uses are operations that generate revenue through, or that significantly involve:
 - i. Manufacturing, repairing, or restoring operations; or
 - ii. Providing maintenance services; or
 - iii. The use, storage, transport, or disposal of hazardous materials or waste.
- e. Materials containing animal or human waste or debris such as lumber, metal, or refuse

2. EVALUATION OF FILL MATERIAL SUITABILITY

Proposed fill material source areas that are considered potentially suitable based on the initial screening of historic and current land use must be sampled, analyzed, and meet applicable environmental and human health risk levels before a final determination of the suitability of the proposed fill material can be made. Sampling protocols and strategies, and laboratory analyses vary based on conditions at the location being sampled, the type of compounds that are being evaluated, and the volume of fill material. Samples must be collected and analyzed in a manner sufficient to characterize the lateral and vertical extents of the proposed fill material source area. Minimum sampling and analysis requirements to evaluate the suitability of a proposed fill material source area are derived from various regulatory guidance documents, industry best practices, and requirements from designated Groundwater Basin Managers within Alameda County which are described in further detail below.

2.1. Minimum Analytical Requirements

Minimum analytical requirements for characterization of potentially suitable fill material proposed for import to a destination (a) outside of the jurisdiction of Zone 7 Water Agency (Zone 7); or (b) within the jurisdiction of Zone 7

are provided in Table 1a and Table 1b, respectively. Sampling and laboratory analysis must be conducted in accordance with the following requirements:

- A. All analysis must be performed in accordance with the United States Environmental Protection Agency's (USEPA's) SW-864 Compendium;
- B. Analysis of samples must be completed and reported by an analytical laboratory accredited by the California State Environmental Laboratory Accreditation Program and the National Environmental Laboratory Accreditation Program;
- C. The laboratory reporting limits must not exceed the screening levels adopted by ACDEH as described in Section 2.4 below;
- D. The laboratory reporting limits must be reported on a dry-weight basis; and
- E. The results of the laboratory analysis must be reported in a standard laboratory data package, including a summary of the quality control and quality assurance sample results and chain of custody documentation.

2.2. Minimum Sampling Requirements

Sampling for the characterization of potentially suitable fill material must be conducted under the direct charge of a professional engineer or geologist licensed in the state of California and in accordance with industry best practices including, but not limited to those discussed in the subsections below.

2.2.1. Vapor Forming Compounds

Vapor forming compounds consist of volatile organic compounds (VOCs) and semi-volatile organic compounds (SVOCs) that readily form a vapor when exposed to air. In order to minimize volatilization of VOCs and SVOCs during sample collection, and ensure that analytical results are representative of the proposed fill material, discrete samples must be collected and analyzed in accordance with United States Environmental Protection Agency (USEPA) Method 5035. Composite sampling is not acceptable for the evaluation of VOCs and SVOCs.

2.2.2. Composite Sampling

Composite sampling is acceptable under the following conditions:

1. Analysis is for non-vapor forming chemicals;
2. The composite sample is comprised of no more than 4 discrete samples;
3. The composite sample is comprised of roughly equivalent masses of each of the discrete samples;
4. Sufficient mass of discrete samples from each of the composited locations are submitted so as to allow for analysis of the discrete samples; and
5. Each of the discrete samples that comprise the composite sample must be analyzed in the event that the composite sample exceeds 25% of the applicable screening level.

2.2.3. In Situ Characterization

Pre-excavation (e.g., In Situ) characterization of potentially suitable fill materials must meet the minimum requirements for provided in Table 2a (for import to a destination outside of the jurisdiction of Zone 7 Water Agency's jurisdiction) and Table 2b (for import to a destination within the Zone 7 Water Agency's jurisdiction). Additional requirements include:

- Characterization of soil lithology in the proposed source area using the Unified Soil Classification System from the ground surface to the total depth of the proposed excavation for the fill material. The

characterized soil lithology at each sample location must be presented as a soil boring log and must be reviewed and stamped by a registered geologist.

- Collection and analysis of at least one sample from each sample location for every five feet below ground surface that the proposed fill area extends.
- Characterization of layers of proposed fill material that exhibit significantly different geological characteristics or lithologies as separate sources. For example, if soil at a site generally consists of clay from the ground surface to a depth of 3 feet below ground surface with interbedded silts and sands beyond, the clay layer should be characterized and managed one source and the interbedded silts and sands should be characterized as a second source.
- Use of direct push technology for sample collection and analyses for VOCs and SVOCs. Samples collected for analysis of non-vapor forming compounds may be collected using direct push technology, augers, or from a bucket, sidewall, or base sample from “pot hole” excavations.

2.2.4. Stockpile Characterization

The minimum sample quantities for the characterization of potentially suitable fill materials that have been excavated and stockpiled are based on the total volume of the stockpiled fill material and are summarized in Table 3. Stockpiles must be generated from the same source area, must be segregated by fill material composition, and be located on the parcel generating the proposed fill material. Samples being analyzed for VOCs and SVOCs must be collected from at least 1 foot below the exposed surface of the stockpile.

2.3. Conditions Requiring Additional Sampling and Analysis

In addition to the minimum sampling requirements identified above, the following conditions, if present, require additional sampling and analysis as indicated:

1. **Evidence of Contamination** – Samples must be collected and analyzed from any locations where there is evidence of contamination such as strong odors, staining, observable sheen or free product, stressed vegetation, and/or elevated responses from field screening instruments such as a photoionization detector.
2. **Contaminants Associated with Surface Deposition** – When characterization for contaminants associated with surface deposition (e.g., pesticides, herbicides, fungicides, asbestos, and lead) are required for fill material characterization, representative samples must be collected from surface and near surface soils in accordance with the following:
 - For in situ characterization, one sample should be collected from each of the following intervals from each sample location: 0 to 6 inches below ground surface; 6 inches to 2 feet below ground surface; and 2 feet to 3 feet below ground surface; and
 - For stockpiled fill materials, fill material from the surface and near surface (0 to 3 feet below ground surface) must be segregated from other fill material and characterized as a separate potential fill source.
3. **Groundwater and Saturated Soil** – If groundwater or saturated soil is encountered during fill characterization or excavation, the following additional samples must be collected and analyzed:
 - One soil sample per sample location from immediately above the saturated soil (i.e., the capillary fringe); and
 - One groundwater sample from each soil boring, excavation, or dewatering well in which groundwater is encountered.

4. **Dewatering** – If dewatering is conducted to support excavation of potentially suitable fill material, characterization of the fill material must be conducted after dewatering has been implemented and soil is no longer saturated.

2.4. Screening Levels

To be considered suitable fill material, analytical results of the fill characterization sampling must be less than applicable environmental and human health risk based screening levels.

2.4.1. Default Screening Levels

ACDEH has adopted the Regional Water Board's Tier 1 Environmental Screening Levels dated February 2016 (ESLs) as default screening levels for all constituents with the following exception:

- **Arsenic:** the screening level for arsenic adopted by ACDEH is 11.00 milligrams of arsenic per kilogram of sample. This concentration based on the upper estimate (99th percentile) for regional background levels of arsenic in the urbanized San Francisco bay region³.

The use of Tier 1 ESLs as a default screening level is applicable to all sites regardless of land use or other site characteristics.

2.4.2. Alternative Screening Levels

In the event that fill characterization fails the default screening levels, alternative screening levels may be proposed for consideration by ACDEH via submittal of a site-specific soil import management plan. The soil import management plan must include a site-specific risk assessment for the receiving location and associated supporting technical documents.

The use of hazardous waste characteristic of toxicity levels (California Code of Regulations Title 22 Section 66261.24) as a screening level to evaluate the suitability of the import of soils is unacceptable for all sites except for appropriately designed and permitted treatment, storage, disposal, or recycling facilities.

3. ACDEH FILL MATERIAL IMPORT SUITABILITY DETERMINATION PROCESS

To obtain a determination from ACDEH that a proposed fill material is suitable, ACDEH requires submittal of a technical report (the "Fill Material Characterization Report") documenting the characterization of the proposed fill material. This technical report must contain, at a minimum, the following element:

- A. A cover letter from the owner of the proposed fill source material with the following statement: "I have read and acknowledge the content, recommendations, an/or conclusions contained in the attached document or report submitted on my behalf to ACDEH". This cover letter must be signed by the owner of the proposed fill source material or a legally authorized representative of the owner of the proposed fill source material;
- B. A statement that fill material characterization was conducted under the responsible charge of a registered professional with licensure in the state of California. This statement must be accompanied by the signed and dated seal of the licensed registered professional with responsible charge;
- C. Narrative identifying and summarizing the following elements:
 - a. The location, assessor's parcel number, and physical address of the proposed fill material source area;
 - b. A summary of historical land uses and operations conducted at and in the vicinity of the proposed fill material source area with citations for supporting documentation;

FILL MATERIAL CHARACTERIZATION GUIDANCE

August 1, 2018

- c. Identification and description of any identified RECs;
 - d. A summary of fill material characterization efforts conducted, including a description of sampling and analysis and applicable geology and hydrogeology within the proposed fill material source area;
 - e. A summary of the results of analytical sampling; and
 - f. Recommendations and conclusions for the suitability of proposed fill material.
- D. Tables summarizing the site characterization analytical data;
- E. A completed Proposed Fill Material Source Characterization Summary Form. A copy of this form is provided in pdf in Attachment A. An excel spreadsheet of this form is available on request;
- F. Figure(s) depicting the following elements:
- a. Sample locations;
 - b. Parcel lines and parcel numbers;
 - c. Lateral extent(s) and depth(s) of the proposed fill material source area(s);
 - d. Location of any identified RECs;
 - e. Location of known current and historic infrastructure including structures, roadways, utilities, and any above ground or below ground storage tanks.
- G. Boring logs depicting the geology, sample depths, and any encountered groundwater from each sample location;
- H. Copies of laboratory analytical data;
- I. Copies of supporting environmental documents such as Phase I ESA, PEA, or historic subsurface investigation reports.

The Fill Material Characterization Report and supporting documentation must be submitted to ACDEH via email to deh.loptoxic@acgov.org and upload to the State Water Board's GeoTracker database. ACDEH will review the Fill Material Characterization Report and will issue a directive letter that (a) determines that the proposed fill material is suitable for import; (b) requests additional characterization; or (c) determines that the proposed fill material is not suitable for import. ACDEH's determination will include conditions described in Section 4 and may include additional conditions or requirements.

4. CONDITIONS OF ACDEH FILL MATERIAL IMPORT SUITABILITY DETERMINATION

As a condition of import, a technical report be submitted to ACDEH via email and uploaded to GeoTracker documenting the import of soil (the "Soil Import Summary Report"). The report must be uploaded to the GeoTracker information repositories for both the fill material source area and the destination. Please note that for locations importing soil from multiple sources, a single report can be submitted that documents import from multiple sources. For locations in which soil import activities last more than one year, a Soil Import Summary Report must be submitted on a semi-annual basis for the duration of import activities. The Soil Import Summary Report must contain the following elements at a minimum:

- A. A cover letter from the owner of the proposed fill source material that states, at a minimum, the following: "I have read and acknowledge the content, recommendations, and/or conclusions contained in the attached document or report submitted on my behalf to ACDEH." This cover letter must be signed by the

FILL MATERIAL CHARACTERIZATION GUIDANCE

August 1, 2018

owner of the proposed fill source material or a legally authorized representative of the owner of the proposed fill source material;

- B. The technical report must include a statement that fill material characterization was conducted under the responsible charge of a registered professional with licensure in the state of California. This statement must be accompanied by the signed and dated seal of the licensed registered professional with responsible charge;
- C. Summary tables of soil import logs. These logs must include the following information for each delivery of fill material: arrival date, manifest number or truck tag, quantity of fill material delivered, originating facility, and profile number;
- D. A figure depicting the location and depth of imported soil. If fill material from multiple sources has been imported, the location and depth of imported soil from each source must be distinguished;
- E. Copies of all manifests or other documentation of soil import as an appendix; and
- F. Copies of all fill characterization profiles as an appendix.

5. CLOSING

If you have questions or comments regarding the requirements and guidance presented in this document, please do not hesitate to contact ACDEH. This document was prepared by, or under the direction of, the undersigned.



Dilan Roe, P.E. C73703
Chief
Land Water Division



Jonathan Sanders
Senior Hazardous Materials Specialist
Local Oversight and Site Cleanup Program

FILL MATERIAL CHARACTERIZATION GUIDANCE

August 1, 2018

ENCLOSURES

Tables

Table 1a	Minimum Required Analyses for Characterization of Fill Material for Off-Site Reuse for Receiving Facilities Located outside of Zone 7 Water Agency Jurisdictional Boundaries
Table 1b	Minimum Required Analyses for Characterization of Fill Material for Off-Site Reuse for Receiving Facilities Located within Zone 7 Water Agency Jurisdictional Boundaries
Table 2a	Minimum Required Sample Density and Spacing for In Situ (Pre-excavation) Characterization of Proposed Fill Material Sources for Receiving Facilities Located outside of Zone 7 Water Agency's Jurisdictional Boundaries
Table 2b	Minimum Required Sample Density and Spacing for In Situ (Pre-excavation) Characterization of Proposed Fill Material Sources for Receiving Facilities Located within Zone 7 Water Agency's Jurisdictional Boundaries
Table 3	Minimum Required Sample Density and Spacing for Stockpile (Post-Excavation) Characterization of Proposed Fill Material Sources

Appendices

Appendix A	Proposed Fill Material Source Characterization Summary Form
------------	---

REFERENCES

1. DRAFT Technical Reference Document: Characterization and Reuse of Petroleum Hydrocarbon Impact Soil as Inert Waste. San Francisco Bay Regional Water Quality Control Board. October 2006.
2. Environmental Screening Levels (ESLs) revision 3. San Francisco Bay Regional Water Quality Control Board. February 2016.
3. Establishing Background Arsenic in Soil of the Urbanized San Francisco Bay Region. Duverge. December 2011
4. Information Advisory: Clean Imported Fill Material. Department of Toxic Substances Control (DTSC). October 2001.
5. Interim Guidance for Sampling Agricultural Properties revision 3. Department of Toxic Substances Control. August 7, 2008.
6. Preliminary Endangerment Assessment Guidance Manual. Department of Toxic Substances Control. January 1994. Revised October 2015.

TABLES

Table 1a
Minimum Required Analyses for Characterization of Fill Material for Off-Site Reuse
for Receiving Facilities Located outside of Zone 7 Water Agency Jurisdictional Boundaries

Laboratory Analysis ⁽¹⁾	Analytical Method	Current and Historic Land Use At or Within 500 Feet of Fill Source Area			Current and Historic Land Use at Parcel(s) Containing Fill Source Area			
		Major Roadway or Freeway	Mining Area or Rock Quarry	Regulated Cleanup Site and RECs	Agricultural	Residential / Acceptable Commercial ⁽²⁾	Existing Historic Engineered Fill ⁽³⁾	Industrial / Unacceptable Commercial
California Title 22 Metals ⁽⁴⁾	USEPA 6010B and/or USEPA 7471A	X (Lead Only)	X	Additional As Required	X	X	X ⁽⁵⁾	N/A
Asbestos	PLM or OSHA 191		X (PLM)	Additional As Required		X (OSHA 191)	X ⁽⁵⁾	N/A
pH	USEPA 9045D		X	Additional As Required			X ⁽⁵⁾	N/A
Pesticides	USEPA 8141A; and USEPA 8151A; and USEPA 8081A or 8080A			Additional As Required	X		X ⁽⁵⁾	N/A
VOCs	USEPA 8260B with collection by USEPA 5035			Additional As Required		X	X ⁽⁵⁾	N/A
SVOCs & PAHs	USEPA 8270C SIM	X (PAHs Only)		Additional As Required		X	X ⁽⁵⁾	N/A
TPH	USEPA 8015M	X ⁽⁵⁾	X ⁽⁵⁾	Additional As Required	X ⁽⁵⁾	X	X ⁽⁵⁾	N/A
PCBs	USEPA 8082 or 8080A			Additional As Required		X	X ⁽⁵⁾	N/A

Adapted from Department of Toxic Substances Control's Information Advisory Clean Imported Fill Material dated October 2001.

Notes:

- (1) All analysis should be performed in accordance with USEPA SW-846 methods. A standard laboratory data package, including a summary of the QA/QC (Quality Assurance/Quality Control) sample results must accompany all analytical reports;
- (2) Acceptable commercial land use excludes any commercial use that generates revenue from manufacturing, repair/restoration, maintenance/cleaning, or the storage/transport of hazardous materials;
- (3) Existing homogeneous engineered fill. Fill containing waste or debris or that is heterogeneous is not acceptable for off-site reuse.
- (4) Include when Hexavalent Chromium analysis required by USEPA method 7199
- (5) Analysis required by Alameda County Department of Environmental Health;

Abbreviations:

- USEPA -United States Environmental Protection Agency
- N/A – Not Acceptable for off-site re-use
- PLM – Polarized Light Microscopy
- OSHA – Occupational Safety and Health Administration Testing Method Number
- SIM – Selected Ion Monitoring
- VOCs – Volatile Organic Compounds
- SVOCs – Semi-Volatile Organic Compounds
- PAHs – Poly Aromatic Hydrocarbons
- TPH – Total Petroleum Hydrocarbons as reported for gasoline range, diesel range, and motor oil range
- PCBs – Polychlorinated Biphenyls;

Table 1b
Minimum Required Analyses for Characterization of Fill Material for Off-Site Reuse
for Receiving Facilities Located within Zone 7 Water Agency Jurisdictional Boundaries

Laboratory Analysis ⁽¹⁾	Analytical Method	Current and Historic Land Use At or Within 500 Feet of Fill Source Area			Current and Historic Land Use at Parcel(s) Containing Fill Source Area			
		Major Roadway or Freeway	Mining Area or Rock Quarry	Regulated Cleanup Site and RECs	Agricultural	Residential / Acceptable Commercial ⁽²⁾	Existing Historic Engineered Fill ⁽³⁾	Industrial / Unacceptable Commercial
California Title 22 Metals ⁽⁴⁾	USEPA 6010B and/or USEPA 7471A	X (Lead Only)	X	Additional As Required	X	X	X ^(5, 6)	N/A
Asbestos	PLM or OSHA 191		X (PLM)	Additional As Required		X (OSHA 191)	X ^(5, 6)	N/A
pH	USEPA 9045D		X	Additional As Required			X ^(5, 6)	N/A
Pesticides	USEPA 8141A; and USEPA 8151A; and USEPA 8081A or 8080A	X ⁽⁶⁾	X ⁽⁶⁾	Additional As Required	X	X ⁽⁶⁾	X ^(5, 6)	N/A
VOCs	USEPA 8260B with collection by USEPA 5035			Additional As Required		X	X ^(5, 6)	N/A
SVOCs & PAHs	USEPA 8270C SIM	X (PAHs Only)		Additional As Required		X	X ^(5, 6)	N/A
TPH	USEPA 8015M	X ^(5, 6)	X ^(5, 6)	Additional As Required	X ^(5, 6)	X	X ^(5, 6)	N/A
PCBs	USEPA 8082 or 8080A			Additional As Required		X	X ^(5, 6)	N/A

Adapted from Department of Toxic Substances Control's Information Advisory Clean Imported Fill Material dated October 2001.

Notes:

- (1) All analysis should be performed in accordance with USEPA SW-846 methods. A standard laboratory data package, including a summary of the QA/QC (Quality Assurance/Quality Control) sample results must accompany all analytical reports;
- (2) Acceptable commercial land use consist excludes any commercial use that generates revenue from manufacturing, repair/restoration, maintenance/cleaning, or the storage/transport of hazardous materials;
- (3) Existing homogeneous engineered fill. Fill containing waste or debris or that is heterogeneous is not acceptable for off-site reuse.
- (4) Include when Hexavalent Chromium analysis required by USEPA method 7199
- (5) Analysis required by Alameda County Department of Environmental Health;
- (6) Analysis required by Zone 7 Water Agency

Abbreviations:

USEPA - United States Environmental Protection Agency

N/A - Not Acceptable for off-site re-use

PLM - Polarized Light Microscopy

OSHA - Occupational Safety and Health Administration Testing Method Number

SIM - Selected Ion Monitoring

VOCs - Volatile Organic Compounds

SVOCs - Semi-Volatile Organic Compounds

PAHs - Poly Aromatic Hydrocarbons

TPH - Total Petroleum Hydrocarbons as reported for gasoline range, diesel range, and motor oil range

PCBs - Polychlorinated Biphenyls;

Table 2a

Minimum Required Sample Density and Spacing for In Situ (Pre-excitation) Characterization of Proposed Fill Material Sources for Receiving Facilities Located outside of Zone 7 Water Agency's Jurisdictional Boundaries

Requirements	Size of Contiguous Fill Source	Minimum Lateral Sample Distribution	Minimum Vertical Sample Distribution
<p>(1) Additional lateral sample locations may be required to address identified RECs;</p> <p>(2) Additional samples must be collected from fill material that exhibits signs of potential contamination (e.g., strong odor, staining, presence of sheen or free product, stressed vegetation in the vicinity, elevated response from photo-ionization detector);</p> <p>(3) Fill source area cannot be located on parcel(s) with historic industrial or unacceptable commercial land uses or parcel(s) associated with regulated environmental cleanup sites unless approved by regulatory oversight agency;</p>	<p>≤2.0 acres</p>	<p>4 sample locations.</p> <p>AND</p> <p>Sample Locations must be distributed throughout the fill material source area.</p>	<p>1 sample collected and analyzed per sample location.</p> <p>AND</p> <p>1 sample collected and analyzed for every 5 feet bgs.</p> <p>AND</p> <p>1 sample collected from each layer exhibiting different geological characteristics or lithology encountered.</p>
<p>(4) Samples that are collected, but not planned for analysis must be submitted with the samples planned for analysis under chain of custody to an appropriately certified analytical laboratory. The samples that are not planned for analysis must remain on hold with the laboratory until ACDEH has issued a determination regarding the suitability of fill material for import and released the un-analyzed samples for disposal;</p> <p>(5) When contaminants associated with surface deposition (e.g. pesticides, asbestos, and lead) are required to be evaluated, ACDEH requires the following additional samples be collected from each sample location: One sample from 0 to 6 inches bgs, One sample from 6 inches to 2 feet bgs, One sample from 2 feet to 3 feet bgs. One of these samples must be selected for analysis for each sample location;</p>	<p>≥2.0 acres <4.0 acres</p>	<p>1 sample location per 0.5 acre.</p> <p>AND</p> <p>Sample Locations must be distributed throughout the fill material source area.</p>	<p>1 sample collected and analyzed per sample location.</p> <p>AND</p> <p>1 sample collected and analyzed for every 5 feet bgs.</p> <p>AND</p> <p>1 sample collected from each layer exhibiting different geological characteristics or lithology encountered.</p>
<p>(6) If groundwater is encountered, ACDEH requires the following additional samples be collected and analyzed: One sample per Sample Location from immediately above the saturated fill material (i.e., the capillary fringe); One groundwater samples must be collected and analyzed for each boring, excavation, or dewatering well in which groundwater is encountered.</p>	<p>≥4 acres <10.0 acres</p>	<p>8 sample locations.</p> <p>AND</p> <p>Sample Locations must be distributed throughout the fill material source area.</p>	<p>1 sample collected and analyzed per sample location.</p> <p>AND</p> <p>1 sample collected and analyzed for every 5 feet bgs.</p> <p>AND</p> <p>1 sample collected from each layer exhibiting different geological characteristics or lithology encountered.</p>
<p>(7) If dewatering will be conducted to support excavation below an existing water table, ACDEH requires that, historically saturated fill material be samples after dewatering is in effect.</p> <p>(8) Composite sampling may or may not be appropriate, depending on the quality and homogeneity of the source/borrow area and compounds of concern.</p>	<p>≥10.0 acres</p>	<p>8 sample locations.</p> <p>AND</p> <p>Sample Locations must be distributed throughout the fill material source area.</p>	<p>4 sample collected and analyzed per sample location.</p> <p>AND</p> <p>1 sample collected and analyzed for every 5 feet bgs.</p> <p>AND</p> <p>1 sample collected from each layer exhibiting different geological characteristics or lithology encountered.</p>

Table 2b

Minimum Required Sample Density and Spacing for In Situ (Pre-excitation) Characterization of Proposed Fill Material Sources for Receiving Facilities Located within Zone 7 Water Agency’s Jurisdictional Boundaries

Requirements	Size of Contiguous Fill Source	Minimum Lateral Sample Distribution	Minimum Vertical Sample Distribution
<p>(1) Additional lateral sample locations may be required to address identified RECs</p> <p>(2) Additional samples must be collected from fill material that exhibits signs of potential contamination (e.g., strong odor, staining, presence of sheen or free product, stressed vegetation in the vicinity, elevated response from photo-ionization detector)</p> <p>(3) Fill source area cannot be located on parcel(s) with historic industrial or unacceptable commercial land uses or parcel(s) associated with regulated environmental cleanup sites unless approved by regulatory oversight agency;</p>	<p>≤2.0 acres</p>	<p>8 sample locations.</p> <p>AND</p> <p>Sample Locations must be distributed throughout the fill material source area.</p>	<p>1 sample collected and analyzed per sample location.</p> <p>AND</p> <p>1 sample collected and analyzed for every 5 feet bgs.</p> <p>AND</p> <p>1 sample collected from each layer exhibiting different geological characteristics or lithology encountered.</p>
<p>(4) Samples that are collected, but not planned for analysis must be submitted with the samples planned for analysis under chain of custody to an appropriately certified analytical laboratory. The samples that are not planned for analysis must remain on hold with the laboratory until ACDEH has issued a determination regarding the suitability of fill material for import and released the un-analyzed samples for disposal;</p> <p>(5) When contaminants associated with surface deposition (e.g. pesticides, asbestos, and lead) are required to be evaluated, ACDEH requires the following additional samples be collected from each sample location: One sample from 0 to 6 inches bgs; One sample from 6 inches to 2 feet bgs; and One sample from 2 feet to 3 feet bgs. One of these samples must be selected for analysis for each sample location;</p>	<p>≥2.0 acres <4.0 acres</p>	<p>1 sample location per 0.25 acre.</p> <p>AND</p> <p>Sample Locations must be distributed throughout the fill material source area.</p>	<p>1 sample collected and analyzed per sample location.</p> <p>AND</p> <p>1 sample collected and analyzed for every 5 feet bgs.</p> <p>AND</p> <p>1 sample collected from each layer exhibiting different geological characteristics or lithology encountered.</p>
<p>(6) If groundwater is encountered, ACDEH requires the following additional samples be collected and analyzed: One sample per Sample Location from immediately above the saturated fill material (i.e., the capillary fringe); One groundwater samples must be collected and analyzed for each boring, excavation, or dewatering well in which groundwater is encountered.</p>	<p>≥4 acres <10.0 acres</p>	<p>16 sample locations.</p> <p>AND</p> <p>Sample Locations must be distributed throughout the fill material source area.</p>	<p>1 sample collected and analyzed per sample location.</p> <p>AND</p> <p>1 sample collected and analyzed for every 5 feet bgs.</p> <p>AND</p> <p>1 sample collected from each layer exhibiting different geological characteristics or lithology encountered.</p>
<p>(7) If dewatering will be conducted to support excavation below an existing water table, ACDEH requires that, historically saturated fill material be samples after dewatering is in effect.</p> <p>(8) Composite sampling may or may not be appropriate, depending on the quality and homogeneity of the fill material and compounds of concern.</p>	<p>≥10.0 acres</p>	<p>16 sample locations.</p> <p>AND</p> <p>Sample Locations must be distributed throughout the fill material source area.</p>	<p>4 sample collected and analyzed per sample location.</p> <p>AND</p> <p>1 sample collected and analyzed for every 5 feet bgs.</p> <p>AND</p> <p>1 sample collected from each layer exhibiting different geological characteristics or lithology encountered.</p>

Table 3

**Minimum Required Sample Density and Spacing for Stockpile (Post-Excavation)
Characterization of Proposed Fill Material Sources for Receiving Facilities**

Requirements	Size of Fill Source	Minimum Number of Fill Material Samples to be Collected
<p>(1) Top Soil (0 to 6 inches bgs) and near surface soil (6 inches to 3 feet bgs) must be stockpiled separately if sampling for contaminants associated with surface deposition (e.g. pesticides, asbestos, and lead) (0-6 inches below ground surface) is required;</p> <p>(2) 4-point composite samples may be used in lieu of discrete samples for analysis other than VOCs and SVOCs, however, the total number of samples must be preserved;</p> <p>(3) VOC and SVOC samples are to be collected from fill material at least 1 foot into the stockpile;</p>	<p>≤1,000 yd³</p>	<p>1 sample collected and analyzed per 250 cubic yards of stockpiled fill material.</p>
	<p>>1,000 yd³ & <5,000 yd³</p>	<p>4 samples collected and analyzed for first 1,000 cubic yards AND 1 sample for each additional 500 cubic yards.</p>
	<p>≥5,000 yd³</p>	<p>12 samples collected and analyzed for first 5,000 cubic yards AND 1 sample for each additional 1,000 cubic yards.</p>

ATTACHMENT A

Proposed Fill Material Source Characterization Summary Form

Proposed Fill Material Source Characterization Summary Form

Associated APN	Phase 1 ESA or PEA Conducted Undeveloped Agricultural Residential Acceptable Commercial ⁽¹⁾ Unacceptable Commercial ⁽²⁾ Industrial Existing Historic Fill Regulated Environmental Cleanup Site ⁽³⁾ Major Roadway / Freeway ⁽³⁾ Mining Area or Rock Quarry ⁽³⁾	Cell ID	Excavation Width (feet)	Excavation Length (feet)	Excavation Depth (feet)	Number of Soil Layers Identified	Stockpile ID	Stockpile Volume (yd ³)	Soil Pit Quarry Construction Site Stockpile Yard Recycling Facility	Soil Aggregate (sand and/or gravel) Crushed Asphalt Crushed Concrete Construction Debris	Unknown Property within jurisdiction of Zone 7 Property within jurisdiction of ACWD Property outside Zone 7 or ACWD jurisdiction Permitted TSDF	Minimum Required Sampling ⁽⁴⁾ / Actual Number of samples collected							
												California Title 22 Metals	Asbestos	pH	Pesticides	VOCs	SVOCs	PAHs	TPH
												/	/	/	/	/	/	/	/
												/	/	/	/	/	/	/	/
												/	/	/	/	/	/	/	/
												/	/	/	/	/	/	/	/
												/	/	/	/	/	/	/	/
												/	/	/	/	/	/	/	/
												/	/	/	/	/	/	/	/

Are RECs, CRECs, or HRECs associated with any parcels? If so, what parcels, and what are the associated COCs?	
If Fill Source Area is a regulated environmental cleanup site, provide case identification information and regulatory oversight agency soil export requirements	

- Notes:
- (1) Commercial activities that do not meet the Unacceptable Commercial critier. Typically, Acceptable Commercial facilities are retail, restaurants or service providers (professional, legal, integrated technology, ect.).
 - (2) Commercial activities that generate revenue through or that significantly involve manufacturing, repairing, restoring, or providing maintenance services or the transport, storage, and disposal of hazardous materials.
 - (3) Land use at, or within 500 feet of the parcel(s) containing the fill source
 - (4) Does not include additional sampling that may be required by the regulatory oversight agency overseeing the environmental cleanup site where the fill source is located
 - * Fill inappropriate or not proposed for off-site reuse at this time and must be disposed of at a permitted TSDF. Please consult with a permitted TSDF for sampling requirements for acceptance by the TSDR.
- ACWD Alameda County Water District
 APN Assesors Parcel Number
 AR As required by accepting permitted TSDR
 CRECs Controlled Recognized Environmental Condition as defined in ASTM E1527-13
 HREC Historic Recognized Environmental Condition as defined in ASTM E1527-13
 REC Recognized Environmental Condition as defined in ASTM E1527-13
 TSDF Treatment, Storage, or Disposal Facility, deinfed as a "Designated Facility" inTitle 22, Section 66260.10 of the California Code of Regulations.
 Zone 7 Zone 7 Water Agency