

Soil Remediation Activities Report Former Ransome Property Yerba Buena Project Site Emeryville, California

> December 21, 1992 1649.07

VOLUME I OF III

Prepared for:

Catellus Development Corporation 201 Mission Street San Francisco, California



LEVINE-FRICKE



ENGINEERS, HYDROGEOLOGISTS & APPLIED SCIENTISTS

December 21, 1992

1649.07

Ms. Susan Hugo Alameda County Health Care Services Agency 80 Swan Way, Suite 200 Oakland, California 94621

Subject:

Soil Remediation Activities Report

Former Ransome Property Yerba Buena Project Site Emeryville, California

Dear Ms. Hugo:

Levine Fricke has prepared the enclosed report for your review. This report presents the results of the soil remediation activities conducted by Levine Fricke at the former Ransome Company Property in Emeryville, California. In addition, the work performed by Aqua Resources, Inc. (ARI), on behalf of the Ransome Company has been summarized.

As you are aware, approximately 25,000 cubic yards (excavated volume) currently area stockpiled either on the Ransome Company Property or on the adjacent Yerba Buena Project Site.

The stockpiled soils generally contain less than 2,000 parts per million (ppm) total petroleum hydrocarbons (TPH) as diesel and oil, and include soil successfully aerated to established criteria for TPH as gasoline and benzene, toluene, ethylbenzene, and xylenes. These petroleum-affected soils will be contained on site in accordance with the approved March 10, 1992 Containment Plan (Levine Fricke, 1992a). Petroleum-affected soil will be placed beneath low permeability asphalt paving in parking areas proposed for portions of the Yerba Buena Project Site, to minimize possible exposure to the affected soils and mitigate future effects to shallow ground water by reducing surface infiltration through the soil.

Based on observations of soil remediation activities conducted by ARI and on laboratory data for verification samples collected from the sidewalls and floors of excavations completed by ARI and Levine. Fricke, no additional soil remediation activities are recommended or proposed for the Ransome Company Property.

> 1900 Powell Street, 12th Floor Emeryville, California 94608 (510) 552-4500 Fax (510) 552-2246

To monitor potential future effects of petroleum-affected soils on ground water beneath the Site, ground-water samples collected from selected monitoring wells located at the Yerba Buena Project Site during periodic monitoring activities will be analyzed for TPH as oil and diesel.

If you have any questions or to provide your comments, please do not hesitate to call either of the undersigned or Jim Levine.

Sincerely,

Seatty
Jenifer Beatty

Project Hydrogeologist

Jenja Beary for Cynthia Barclay

Senior Project Geologist

Enclosure

cc: Don Marini, Catellus (Volume I only)
Ric Notini, Catellus (Volume I only)

Pat Cashman, Catellus (Volume I only)

Kimberly Brandt, Catellus Lester Feldman, RWQCB

CONTENTS

		PAGE
VOLUI	ME I	
LIST	OF TABLES	iv
LIST	of figures	v
1.0	INTRODUCTION	1 2 2 3
2.0	ACTIVITIES CONDUCTED AT THE PROPERTY BEFORE SEPTEMBER 1991	4 4 6 8 9
3.0	ACTIVITIES CONDUCTED AT THE PROPERTY AFTER SEPTEMBER 1991	12 12 12 14 14 17 17 18
4.0	CONTAINMENT PLAN	22 22 23
5.0	SUMMARY AND CONCLUSIONS	24
ומקמם	PENCES	26

CONTENTS (continued)

TABLES

FIGURES

APPENDICES:

- A CORRESPONDENCE FROM THE ALAMEDA COUNTY HEALTH CARE SERVICES AGENCY TO RANSOME COMPANY, DATED FEBRUARY 1991, CORRESPONDENCE FROM THE ALAMEDA COUNTY HEALTH CARE SERVICES AGENCY TO CATELLUS DEVELOPMENT CORPORATION, DATED MARCH 5, 1991, AND CORRESPONDENCE FROM THE REGIONAL WATER QUALITY CONTROL BOARD TO LEVINE FRICKE, DATED JUNE 24, 1992
- B SAMPLING PROCEDURES
- C GEOTECHNICAL ENGINEERING FIELD SERVICES (BACKFILL AND COMPACTION PROCEDURES)
- D REMEDIATION CERTIFICATE AND CERTIFICATES OF ANALYSIS, PORT COSTA MATERIALS, PORT COSTA, CALIFORNIA
- E FIELD PROCEDURES, SOIL BORING INSTALLATION
- F H & H MANIFESTS
- G AERATION BED CONSTRUCTION AND SAMPLING PROCEDURES
- H SW-846 ANALYSIS FOR SOIL SAMPLES COLLECTED FROM AERATION BEDS

VOLUME II

I LABORATORY CERTIFICATES - AQUA RESOURCES, INC., AND LEVINE • FRICKE, INC. VERIFICATION SAMPLES

CONTENTS (continued)

VOLUME III

0

SAMPLES

LABORATORY CERTIFICATES - IMPORTED BACKFILL
MATERIALS USED BY AQUA RESOURCES, INC.

K LABORATORY CERTIFICATES - CHARACTERIZATION OF AQUA
RESOURCES, INC., AERATION BEDS

LABORATORY CERTIFICATES - TEST PITS AND SOIL
BORINGS

M LABORATORY CERTIFICATES - VERIFICATION SAMPLES,
NORTHERN AREA

N LABORATORY CERTIFICATES - CHARACTERIZATION OF AQUA
RESOURCES, INC., STOCKPILE SOILS

LABORATORY CERTIFICATES - LEVINE • FRICKE AERATION

LIST OF TABLES

NAME	TITLE								
1	Analytical Results of Verification Soil Samples								
2	Analytical Results of Soil Samples Collected from Aeration Beds								
3	Analytical Results of Soil Samples Collected from Test Pits and Soil Borings								
4	Analytical Results of Final Verification Soil Samples Collected from the Northern Area Excavation								
5	Analytical Results of Characterization Soil Samples Collected from Soils Stockpiled by Aqua Resources Inc.								
6	Analytical Results of Soil Samples Collected from Aeration Beds								
<u>APPENDI</u>	x c								
C-1	Results of Laboratory Compaction Tests								
C-2	Results of Field Compaction Tests								
<u>APPENDI</u>	х н								
H-1	Statistical Analysis of Aerated Soils, Ransome Property, Emeryville, California								

LIST OF FIGURES

NAME	TITLE
1	Site Location Map
2	Site Plan and Monitoring Well Locations, Yerba Buena Project Site
3	Verification Soil Sample Locations for Areas Excavated by Aqua Resources, Inc.
4	Aqua Resources, Inc., Approximate Stockpile Locations and Aeration Beds
5	Analytical Results for Test Pits and Soil Borings
6	Approximate Extent of Excavations Completed by Levine·Fricke - Northern Area
7	Final Verification Soil Sample Locations and Results - Northern Area Excavation
8	Approximate Locations of Aeration Beds and Stockpiles
9	Historical Ground-Water Quality Data
<u>APPENDI</u>	<u>x c</u>
C-1	Site Plan Showing Field Compaction Test Areas for Backfilled Areas Excavated by Aqua Resources and Levine•Fricke
C-2	Site Plan Showing Field Compaction Test Areas for Northern Area

December 21, 1992

LF 1649.07

SOIL REMEDIATION ACTIVITIES REPORT FORMER RANSOME PROPERTY, YERBA BUENA PROJECT SITE EMERYVILLE AND OAKLAND, CALIFORNIA

1.0 INTRODUCTION

This report presents the results of the soil remediation activities conducted at the former Ransome Company Property ("the Property") in Emeryville, California. The Property is located in the northwestern portion of Area B of the Yerba Buena Project Site ("the YBP Site") in Emeryville and Oakland, California (Figures 1 and 2).

During the period from October 1990 through September 1992, various remedial activities have been conducted at the Property. Portions of this work were conducted by Aqua Resources, Inc. (ARI) of Berkeley, California, on behalf of the Ransome Company, former Property occupant and operator. Other portions of the work were conducted by Levine Fricke on behalf of Catellus Development Corporation ("Catellus"), the Property owner.

ARI prepared a July 15, 1990 "Draft Workplan for Initial Subsurface Investigation and Site Closure" (ARI, 1990a) and a January 16, 1991 "Remedial Investigation and Site Closure Plan" (ARI, 1991a). The Site Closure Plan was approved by the Alameda County Health Care Services Agency (ACHA) in a letter dated February 4, 1991, from Mr. Dennis Byrne of the ACHA to Mr. Kinear Smith of the Ransome Company (Appendix A). Soil remediation activities for the Property were conducted in accordance with these plans by ARI between June 1991 and September 1991 and Levine Fricke between October 1991 and September 1992.

In addition, Levine Fricke prepared a Site Remedial Plan (SRP) dated February 11, 1991 (Levine Fricke, 1991a) and a Containment Plan for Petroleum Hydrocarbon-Affected Soils ("the Containment Plan"), dated March 10, 1992 (Levine Fricke, 1992a), on behalf of Catellus. The ACHA reviewed Levine Fricke's SRP and subsequently approved it in a March 5, 1992 letter to Mr. Ric Notini of Catellus (ACHA 1991; Appendix A). The plan for containing soils affected by total

petroleum hydrocarbons (TPH) at the YBP Site was verbally approved by the ACHA and the Regional Water Quality Control Board (RWQCB) on June 22, 1992, and in a letter dated June 24, 1992, from the RWQCB to Levine. Fricke (Appendix A).

This report has been prepared for the use of Catellus Development Corporation. Any use of this report by a third party shall be at such third party's own risk.

1.1 Site Description

The Ransome Company ("Ransome"), a construction firm and former asphalt batch plant, reportedly occupied the Property for more than 50 years, from approximately 1938 to 1990. Reportedly, Ransome's operations included asphalt concrete mixing, metal working, automobile repair, and assembly of torch and burner equipment (KJC, 1989).

Kennedy/Jenks/Chilton (KJC) of San Francisco, California, conducted a Baseline Environmental Assessment of the Property in 1989 (KJC, 1989). At that time, the Property yard contained seven structures, including an office, a machine/maintenance shop, four sheds, a steam cleaning shed, and a lavatory. In addition, KJC reportedly found four underground fuel storage tanks (USTs), one waste-oil tank that was partially underground, and an aboveground liquid asphalt oil tank at the Property.

In December 1989, KJC reportedly removed the USTs and submitted a tank removal report, dated April 9, 1990, to the ACHA. According to KJC, petroleum hydrocarbon staining of the underlying soil was observed at the time of tank removal. Oil stains on soil and surface structures were observed throughout the Property, especially in the machine shop, in the vicinity of the oil storage shed, near the waste-oil tank, and near the liquid asphalt oil tank (Levine Fricke, 1990).

The buildings at the Property were demolished in June 1990 pursuant to the lease agreement between the Ransome Company and Catellus (see Figure 2).

1.2 Previous Investigation Activities

Aqua Resources, Inc. (ARI) conducted Phase I remedial investigations for the Property on behalf of Ransome during the period from October 1990 to December 1990 in accordance with its July 25, 1990 "Draft Workplan for Initial Subsurface Investigation and Site Closure" (ARI, 1990a). This Workplan was amended in an addendum dated August 23, 1990 (ARI, 1990b),

and approved by the ACHA in a letter dated September 14, 1990 (Appendix A). The results of this investigation were presented in a report prepared by ARI, dated January 16, 1991 (ARI, 1991a).

ARI concluded from the results of its investigation that soil quality at the Property had been affected by the release of various petroleum hydrocarbons, including diesel, waste oils, and gasoline. Results indicated concentrations of diesel and oil up to 2,700 ppm and 6,700 ppm, respectively. Gasoline reportedly was detected at concentrations of 9.3 ppm or less.

As part of its investigation, ARI also installed three shallow ground-water monitoring wells on the Property in November 1990. Ground-water quality results indicated concentrations of total petroleum hydrocarbons (TPH) as gasoline (TPHg) up to 0.460 parts per million (ppm) and benzene up to 0.260 ppm.

Based on soil-quality results observed during its investigation, ARI initiated soil removal activities in accordance with its site closure plan dated January 16, 1991 (ARI, 1991a).

1.3 Objectives of Soil Remediation Activities

The objectives of soil remediation activities conducted for the Property by ARI and Levine-Fricke were to further characterize and assess the extent of petroleum-affected soil at the Property, and reduce concentrations of petroleum compounds in soils to concentrations approved by the ACHA. To achieve these objectives, ARI and Levine-Fricke conducted soil excavation, verification sampling and analysis, backfilling, compaction, and characterization and treatment of excavated soils. Criteria for evaluating remedial efforts were developed based on the activity being conducted: excavation, backfilling, or aeration. These criteria are discussed below.

1.3.1 Excavation Criteria

ARI proposed that affected soils be removed from the excavations until sidewall and floor samples indicated that remaining soils contained concentrations of less than 10 ppm TPHg, 100 ppm TPH as diesel (TPHd), and 0.005 ppm for combined benzene, toluene, ethylbenzene, and xylenes (BTEX compounds). ARI proposed these "excavation criteria" in its January 1991 report. However, following discussions between Mr. Dennis

Byrne of the ACHA and representatives of Levine. Fricke and ARI, the excavation criteria adopted for soils at the Property were 10 ppm TPHg, 100 ppm TPHd, 1 ppm BTEX compounds (combined), and 1,000 ppm oil and grease.

1.3.2 Aeration Criteria

When ARI aerated soils on site, aeration criteria were the same as criteria used for the backfill materials as discussed in Section 1.3.3.

Soils aerated by Levine Fricke contained low concentrations (less than 2,000 ppm) of diesel and oil. Following discussion among the ACHA, the RWQCB, and Levine Fricke on February 13, 1992, 10 ppm TPHg, 1 ppm for total ethylbenzene, toluene, and xylenes, and below laboratory detection limits for benzene were agreed upon as aeration criteria for gasoline— and BTEX compound—affected soils. In accordance with the Containment Plan, following aeration of affected soils to below these concentrations, the soils were to be contained on site.

1.3.3 Backfill Criteria

ARI proposed and the ACHA approved 10 ppm TPHg, 10 ppm TPHd, 500 ppm oil and grease, and less than the detection limit for combined BTEX compounds as backfill criteria for the Property. Soils excavated at the Property and treated to residual concentrations of these compounds below these levels could be used as backfill materials.

2.0 ACTIVITIES CONDUCTED AT THE PROPERTY BEFORE SEPTEMBER 1991

This section describes soil remediation activities conducted by ARI for the Property during the period from June 1991 to September 1991.

2.1 Soil Removal Activities

ARI initiated soil removal activities on June 6, 1991, at the Property by excavating and stockpiling some of the petroleum-affected soil on site, in accordance with recommendations presented in its January 16, 1991 report. ARI's work included excavating and removing diesel- and oil-affected soils for off-site treatment, aerating gasoline-affected soils on site for possible reuse as backfill in excavations, and stockpiling soil on the Property and adjacent YBP Site.

H.K. Grading Contractors, Inc., of Livermore, California, was the excavation contractor working under the direction of ARI. A Levine Fricke geologist or engineer was on site continuously during excavation activities to observe work on behalf of Catellus and to collect split soil samples (split samples), when appropriate, to verify soil analytical results. Visual observations indicated the work was performed by ARI in compliance with the Site Health and Safety Plan included in ARI's July 25, 1990 Workplan and in accordance with recommendations included in the ARI January 1991 report (ARI, 1990a and 1991a).

Apparently using soil-quality data obtained during its subsurface investigation, ARI marked the approximate areal boundaries of affected soils before excavation commenced. Affected soils were then excavated using a track-mounted excavator. A water truck was used for dust control purposes during excavation.

As excavation progressed, Levine Fricke observed ARI personnel periodically monitoring the soil with a photoionization detector (PID) for the approximate concentrations of volatile organic compounds (VOCs) in the soil vapor. When excavation approached the proposed boundaries, PID readings were recorded by ARI for soil collected from the excavation sidewalls and floor. These readings reportedly were used by ARI personnel to assess whether petroleum-affected soil had been removed.

Excavated petroleum-affected soils were top loaded onto a front-end loader and deposited in stockpiles on plastic sheeting located on the Property and the adjacent YBP Site, or on aeration beds. Levine. Fricke observed ARI's contractor placing soils suspected to be affected by gasoline and BTEX compounds (based on PID readings, observations, and analytical data obtained during remedial investigations) on aeration beds located on the YBP Site, adjacent to the Property.

Ultimately, ARI estimated that approximately 17,200 cubic yards (in-place volume based on calculations from excavation diagrams) of petroleum-affected soils were excavated from several areas at the Property under ARI's supervision. The approximate extent of ARI excavations are shown on Figure 3.

During soil removal in excavations K and L in August 1992 (Figure 3), ARI and its contractor encountered two concrete vaults, two concrete pads, and a concrete trough. The first concrete vault, which measured approximately 7 feet by 3 feet by 1.5 feet deep, was encountered on August 15, 1991, in excavation L at approximately 3 to 4 feet below ground surface

(bgs). The second concrete vault, which measured approximately 14 feet by 16 feet by 3 feet deep, was encountered by ARI on August 19, 1991, in the southwest corner of excavation K at approximately the same depth.

Levine Fricke personnel observed that both vaults were filled with oily soil.

The two concrete pads were encountered by ARI on August 2 and 6, 1991, in excavations L and K, respectively, at approximately 0.5 and 2 feet bgs, respectively. The pad in excavation L measured approximately 14 feet by 16 feet. The pad in excavation K measured approximately 39 feet by 12.5 feet.

The concrete trough was encountered by ARI on August 26, 1991, adjacent to the south wall of excavation K. The trough was observed to be approximately 29 feet long, 8 to 9 feet wide, and 3 feet deep, and the top of the trough was approximately 5 feet bgs.

The concrete structures discussed above were broken into smaller pieces, with the excavator operated by H. K. Grading as directed by ARI. The concrete rubble was then excavated from the Property and transported off site, reportedly to a Class III landfill. The oily soil was observed to be excavated from the vaults and stockpiled on site.

In September 1991, ARI and its contractor encountered a third concrete vault, which measured approximately 9 feet by 9 feet by 9 feet by 9 feet by 9 feet deep, adjacent to the east wall of excavation A'. Levine Fricke personnel observed that the vault was filled with oily water, soil, and debris. ARI personnel pumped the water (approximately 40 gallons) out of the vault and into a 55-gallon drum for temporary on-site storage. The soil and debris were observed to be excavated and stockpiled on site; however, the vault was not removed at that time.

2.2 Verification Sampling and Analysis

To verify that soils containing concentrations of petroleum hydrocarbons exceeding excavation criteria had been removed, ARI personnel collected soil samples for chemical analysis from the sidewalls and floor of each excavation. In areas where analytical results indicated the presence of petroleum hydrocarbons in excess of the approved excavation criteria, additional soil was excavated and additional samples were observed to be collected from the newly excavated sidewalls and/or floor of the excavation. This process of excavating and resampling was reportedly repeated until laboratory

results indicated concentrations of petroleum hydrocarbons below the excavation criteria for the Property. A Levine Fricke engineer or geologist was on site to observe excavation and resampling activities.

In excavations more than 5 feet deep, ARI obtained soil samples from the sidewalls and floor of the excavation using an excavator bucket. Soil samples were collected directly from the bucket by pounding 2-inch-diameter brass tubes into the bucket with a rubber mallet. In excavations that were less than 5 feet deep, ARI personnel entered the excavations and collected soil samples directly from the excavation sidewall or floor using the same technique. After the tube was filled with soil, the ends of the tube were capped with aluminum foil and plastic caps and sealed with tape. The samples were individually labeled, and placed into a chilled ice chest for transportation to Curtis & Tompkins, Ltd., Analytical Laboratories of Berkeley, California, reportedly following chain-of-custody protocol.

Soil samples were submitted to the analytical laboratory for analysis of total volatile hydrocarbons (TVH) as gasoline and extractable petroleum hydrocarbons (EPH) as kerosene and diesel using modified EPA Method 8015, BTEX using EPA Method 8020, and oil and grease using Standard Methods 5520e and f. Laboratory analysis conducted for each sample varied depending on the where the soil sample was collected and the contaminants suspected in that location based on previous analytical results. Reportedly, samples generally were submitted on a 5-day turnaround for analysis.

Levine Fricke personnel collected soil samples from the same sampling locations as were selected by ARI personnel (split samples). Levine Fricke's soil sampling procedures are described in Appendix B. Levine Fricke sent its soil samples by courier to Quanteq Laboratories (formerly Med-Tox Associates), Inc. of Pleasant Hill, California, for laboratory analysis, following chain-of-custody protocol. Approximately 25% of the collected split-samples were analyzed to verify the analytical results reported by ARI.

A total of 222 verification soil samples were collected by ARI and Levine. Fricke from the final floor and sidewalls of the completed excavations, as indicated on Figure 3. ARI collected and analyzed 185 verification soil samples and Levine. Fricke collected and analyzed 37 final soil samples. A summary of the analytical results for verification samples is presented in Table 1. Laboratory data sheets are presented in Volume II, Appendix I.

7

ARI did not achieve the cleanup goals set forth in its closure plan (ARI, 1991b). Analytical results for verification samples from the ARI excavation activities indicated TPHg at concentrations exceeding excavation criteria (10 ppm) in 4 of the 185 samples (concentrations ranging from 11 ppm to 120 BTEX compound concentrations also were detected above the combined 1 ppm excavation criterion in 2 of the 185 samples. Soil in the vicinity of these sample locations (FW-6-5, FN-3-3, and KN-1-8, JN-55-9.5; Figure 3) were later excavated by Levine Fricke (see Section 3.0). Concentrations of diesel and oil and grease were below excavation criteria in all samples collected and analyzed. The analytical results for split-samples collected by Levine. Fricke generally were in agreement with results reported by ARI, with the exception of sample JN-53-9.5, which indicated TPHg at 32 ppm and a BTEX compound combined concentration of 6.95 ppm. The soil in the vicinity of this sample location was later excavated by Levine Fricke.

2.3 Backfilling and Compaction

Under the direction of ARI, H.K. Grading backfilled completed excavations (areas A1, A2, B2, B3, and portions of areas D, J-1, and J-2; Figure C-1) during the period from September 3 through September 13, 1991 (Phase I). A Levine Fricke engineer or geologist was continuously on site to observe backfilling and compaction activities and to conduct field compaction tests on behalf of Catellus. A detailed description of backfill and compaction procedures is included in Appendix C.

Completed excavations were backfilled with clean imported fill material and soils from the Property that were characterized as suitable for backfill material based on the established criteria. Imported fill material was supplied by Port Costa Materials from its quarry. To check that imported material met backfill criteria, ARI reportedly collected one soil sample per day from the backfill material for chemical analysis. Analytical results for these soil samples are contained in Volume III, Appendix J. Backfill material specifications and compaction requirements were presented in ARI's reports entitled "Proposed Excavation Backfill Procedure, 4030 Hollis Street, Emeryville," dated July 26, 1991 and "Response to Levine. Fricke Backfill Letter, Proposed Excavation Backfill Procedure, 4030 Hollis Street, Emeryville," dated August 26, 1991.

Ransome retained Construction Materials Testing, Inc. (CMT), of Concord, California, to conduct field compaction services from September 3 through 13, 1992. All backfill materials were submitted to Woodward-Clyde Consultants of Pleasant Hill, California, for laboratory compaction testing ASTM D1557. Results of these tests are presented in Table C-1 (Phase I) in Appendix C.

Figure C-1 presents the approximate extent of completed excavations backfilled and compacted as directed by ARI. Results of the field compaction tests, conducted by Levine. Fricke to monitor compaction activities, are presented in Table C-2 in Appendix C.

Based on observations made by Levine-Fricke personnel, monitoring, and the results of field density compaction tests conducted by a Levine-Fricke geotechnical engineer, it appears that the soil compaction work was conducted in accordance with the specifications and requirements outlined in the ARI reports discussed above.

2.4 Characterization, Treatment, and Containment of Excavated Soils

Reportedly, based on visual observations of soils during excavation, PID readings, and previous soils data obtained for the Property, soils excavated by ARI were either placed on aeration beds for on-site treatment of gasoline-affected soils (approximately 5,480 cubic yards [estimated based on stockpile volume]), transported off site for thermal treatment (approximately 4,100 cubic yards [stockpile volume]), or stockpiled on plastic sheeting (approximately 12,500 cubic yards [stockpile volume]). The locations of aeration beds and stockpiled soils are shown in Figure 4.

Under ARI's direction, approximately 5,480 cubic yards of gasoline-affected soil were aerated on site in accordance with recommendations included in ARI's 1991 report and approved by the ACHA. A Levine Fricke engineer or geologist monitored aeration activities on behalf of Catellus. Aeration was observed to be conducted in accordance with Bay Area Air Quality Management District (BAAQMD) Regulation 8, Rule 40.

Aeration bed SP-10 reportedly was constructed on the adjacent YBP Site by placing 6 inches of sand on the native soil and covering the sand with 6-mil visquine. A second layer of sand

was placed over the visquine before placement of gasoline-affected soils. Aeration bed SP-19, constructed in the eastern portion of the Site, was observed to be constructed by placing visquine directly on the asphalt in that area (Figure 4).

Soils were placed in approximately 2-foot-thick lifts on aeration bed SP-10, and in approximately 3-foot-thick lifts on aeration bed SP-19. Levine Fricke personnel observed that the soils placed on the aeration beds were turned periodically using a roto-tiller, tractor, and excavator to enhance the aeration process. ARI collected samples from the aeration beds when PID readings for the aerated soil indicated reduced concentrations of VOCs. The process of turning the soil and resampling the aeration beds for analysis was repeated until concentrations of gasoline and BTEX were below aeration criteria. ARI personnel collected soil samples in accordance with sampling procedures discussed in Section 2.2, except that in some instances a trowel was used to pack the soil into the brass tube.

Soil samples were submitted to Curtis & Tompkins, Ltd., on a 48-hour turnaround for analysis. The samples were composited by the analytical laboratory before analysis. ARI personnel collected soil samples from aerated soils to assess whether these soils could be used as backfill material. To assess whether the aerated soil had been adequately characterized by ARI, Levine Fricke evaluated analytical results of soil samples obtained by ARI (see Section 3.5). Based on that evaluation, 11 additional discrete soil samples were collected by Levine Fricke for chemical analysis. The analytical results for soils aerated by ARI, some of which were subsequently used for backfill material (approximately 2,500 cubic yards [stockpiled volume]) by Levine Fricke following additional analysis, are presented in Table 2. Laboratory certificates are contained in Volume III, Appendix K.

Soils that ARI suspected contained concentrations of diesel and/or oil and grease exceeding the approved backfill criteria (based on visual observations during excavation and soil-quality data from previous investigations) reportedly were transported off site to Port Costa Materials in Port Costa, California, for thermal treatment. Approximately 4,100 cubic yards (stockpiled volume) of soil reportedly were transported off site. The Remediation Certificate and Certificates of Analysis for the treated soils are contained in Appendix D.

Approximately 15,400 cubic yards (stockpiled volume) of petroleum-affected soils excavated by ARI currently are stockpiled at the Property. These soils will be contained on the YBP Site in accordance with the approved Containment Plan (Levine-Fricke, 1992a).

2.5 Summary

ARI conducted a Phase I subsurface investigation of the Property between October and December 1990. Using results from this investigation, ARI proposed soil remedial activities for the Property to reduce residual petroleum concentrations in soils.

ARI initiated soil removal in June 1991 on behalf of Ransome. ARI and its subcontractor, H. K. Grading Contractors, Inc., excavated a total of approximately 17,200 cubic yards (inplace volume [estimated by ARI]) from the areas indicated on Figure 3. Approximately 4,100 cubic yards (stockpiled volume) of this soil were transported off site for thermal treatment, approximately 5,480 cubic yards (stockpiled volume) were aerated on site to aeration criteria, and approximately 12,500 cubic yards (stockpiled volume) were stockpiled either on site or on the adjacent YBP Site. ARI stopped work at the Property in September 1991 before the remediation was completed.

During Ransome's partial remediation efforts, Levine. Fricke observed ARI's soil removal activities on behalf of Catellus. This afforded Levine. Fricke the opportunity to identify areas that required further investigation or remedial efforts. When Ransome directed ARI to stop work, Catellus instructed Levine. Fricke to complete remedial efforts at the Property. At that time, Levine. Fricke was aware that the cleanup criteria had not been met in the following areas:

- one concrete vault, which previously had been filled with oily soil and/or oily water and debris, was present adjacent to the east wall of excavation A' (Figure 3)
- soils containing chemical concentrations above excavation criteria were still present in the northern portion of the Property
- stockpiled soils, including aerated soils, had not been adequately characterized, treated, or disposed of

The activities Levine Fricke conducted at the Property to address these areas of concern and other project-specific development areas are discussed in Section 3.0.

3.0 ACTIVITIES CONDUCTED AT THE PROPERTY AFTER SEPTEMBER 1991

This section describes soil investigation and remediation activities conducted by Levine. Fricke during the period from October 1991 to September 1992.

3.1 Objectives

Levine Fricke conducted further soil remedial activities at the Property to accomplish the following:

- assess the extent of petroleum-affected soil in the northern portion of the Property ("the Northern Area"),
- reduce concentrations of petroleum compounds in soil to ACHA-approved concentrations by continuing soil removal activities
- characterize excavated soils for subsequent treatment and/or containment in accordance with the approved Containment Plan (Levine-Fricke 1992a).

3.2 Soil Investigation - Northern Area

To complete the remediation work begun by ARI and to further evaluate the lateral and vertical extent of petroleum hydrocarbons in soils at the Property and just north of the Property, Levine Fricke directed the excavation of 18 test pits at various locations on the Property, and drilling of 2 soil borings on the Property and 10 soil borings north of the Property along the northern fence (Figure 5).

ARI previously had excavated eight test pits in the Northern Area in July 1991. The analytical results for the samples collected from ARI's test pits are presented on Figure 5 and in Table 3. The results indicated that ARI had not yet defined the extent of soils containing chemicals exceeding cleanup criteria along the northern border of the excavation area.

Test pits TP-1 through TP-5 and TP-8 through TP-13 were excavated between October 16 and 21, 1991. Test pits TP-14 through TP-20 were excavated on January 21, 1992, and February 4, 1992, to assess the lateral and vertical extent of petroleum hydrocarbons in the vicinity of the concrete vault in excavation A'. Test pits corresponding to designations TP6 and TP7 were not excavated. Test pits were excavated under the supervision of a Levine Fricke engineer or geologist. The vault had been observed to be filled with oily water, soil,

and debris. To assess whether petroleum-affected water in the vault had affected soils in the vicinity, test pits were excavated on the three sides of the vault not previously excavated (Excavation A'; Figure 5). Off-site soil borings SB1 through SB10 and on-site borings SB12 and SB14 were drilled under the supervision of a Levine-Fricke engineer on November 7 and 8, 1991.

Field Procedures

Field procedures used during soil boring drilling are described in Appendix E. Soil samples were collected in accordance with procedures contained in Appendix B. Soil samples were submitted to Precision Analytical Laboratory (PAL), Inc. of Richmond, California, for analysis of TPHG, TPHG, and TPH as oil (TPHO) using Modified EPA Method 8015; BTEX compounds using EPA Method 8020; and total hydrocarbons using Standard Method 5520f, 17th Edition. Soil samples were submitted to the laboratory on a 48-hour turnaround for analysis.

Analytical Results

Analytical results for soil samples collected from test pits by Levine Fricke and ARI and from soil borings by Levine Fricke are presented in Table 3 and on Figure 5. Results for samples collected from soil borings located off site, north of the northern Ransome fence, indicated that this area does not appear to have been significantly affected by petroleum hydrocarbon releases at the Property.

As indicated on Figure 5, petroleum compounds were detected above the excavation criteria in seven of the on-site test pits and in soil boring SB14. A summary of analytical results is presented below:

- TPHg was detected in soil samples collected from TP2, TP3, TP5, and SB14 at concentrations ranging from 12 ppm to 220 ppm, which exceeded the excavation criterion of 10 ppm.
- BTEX compounds were detected in TP1, TP2, TP3, TP4, TP5, and SB 14 at combined concentrations ranging from 1.19 ppm to over 150 ppm, which exceeded excavation criterion of 1 ppm (combined).
- TPHo was detected in TP14 and TP18 at concentrations up to 1,400 ppm, which exceeded the excavation criterion for oil and grease of 1,000 ppm.

 TPHd was detected in TP18 at concentrations up to 160 ppm, which exceeded the excavation criterion of 100 ppm.

Soils located in the vicinity of test pits TP1, TP2, TP3, TP4, TP5, and SB14 appeared to be primarily affected by gasoline and BTEX compounds. The depth of affected soil generally ranged from 8 feet bgs to 11.5 feet bgs. Diesel- and oil-affected soil was generally located in the vicinity of test pits TP14 and TP18 at depths ranging from 4 to 8 feet bgs. Laboratory certificates are contained in Volume III, Appendix L.

3.3 Soil Removal Activities - Northern Area

Soil removal activities were conducted during the period from December 16, 1991 through March 5, 1992, by Plant Reclamation of Richmond, California, as directed by a Levine Fricke geologist or geotechnical engineer. The work was performed in accordance with ARI's 1990 Workplan (ARI, 1990a) and the Site Health and Safety Plan prepared by Levine Fricke (Levine Fricke, 1991a). As stated previously, the objective of soil excavation activities was to remove soils from the Property that contained concentrations of petroleum hydrocarbons above excavation criteria approved by the ACHA (discussed in Section 1.3.1). Approximately 9,600 cubic yards of additional petroleum-affected soils were excavated from the Northern Area under the observation of Levine Fricke. The approximate areal extent of soil excavated in the Northern Area is shown on Figure 6.

3.3.1 Soil Excavation

Site preparation before soil excavation consisted of marking the proposed excavation limits based on soil-quality data obtained during previous investigations and preparing areas for placement of excavated soils. Two areas located on the western end of the Property, near the proposed excavation boundaries, were graded smooth and lined with 6-mil plastic sheets to prevent petroleum-affected soil from contacting unaffected soil on the YBP Site. During excavation, two additional areas on the eastern portion of the YBP Site were prepared for stockpiling soils. To inhibit possible stormwater runoff, the perimeter of the YBP Site was bermed using hay bales and imported soil. Hay bales also were placed around a storm drain located in the central portion of Area B of the YBP Site to inhibit surface runoff from entering the storm drain.

Soil was excavated using a track-mounted excavator and excavated soils were top loaded onto ten-wheel dump trucks and deposited on plastic lining in stockpiles. Excavation continued until PID readings for excavated soil approached zero, visual observations indicated reduced petroleum hydrocarbon concentrations, and/or backfill material from excavations completed by ARI were encountered. Soil samples were then collected for laboratory analyses from the excavation sidewalls and/or floor to confirm the PID readings. Soil samples were collected in accordance with field procedures described in Appendix B.

Soil samples were submitted to PAL for TPHg, TPHd, and TPHo using Modified EPA Method 8015; BTEX compounds using EPA Method 8020; and total hydrocarbons using Standard Method 5520f, 17th Edition. Samples were generally submitted to the laboratory on a 48-hour turnaround for analysis. Areas were excavated further if soil samples indicated concentrations of petroleum hydrocarbons above the excavation criteria. The process of excavating and sampling was repeated until laboratory results indicated that residual concentrations were below excavation criteria. Analytical results for verification soil samples collected in the Northern Area are discussed in Section 3.3.2.

Abandonment of ARI Monitoring Wells W-1, W-2, and W-3

The three monitoring wells (W-1, W-2, and W-3) installed by ARI in November 1990 were destroyed during subsequent soil remediation activities. Wells W-1 and W-2 were abandoned on October 22 and 23, 1991, by carefully excavating soils surrounding the wells using a backhoe. Soils were excavated to a depth of 20 feet bgs and the well casing was pulled out of the ground using a rope tied to the backhoe bucket and around the well casing. The bore hole from the depth of the well (24 feet bgs) to 20 feet bgs was filled with clean imported soil and compacted. The remaining excavation was backfilled and compacted as described in Section 3.5.

During grading at the Property conducted by Ransome and ART, soil was deposited in the vicinity of monitoring well W-3, burying the well and concealing its location. On May 4, 1992, a backhoe operated by Plant Reclamation and directed by a Levine. Fricke geologist, moved soils in the approximate location of well W-3 to expose the well. The well was observed to be damaged and appeared to be filled with dirt. On May 6, 1992, the well was abandoned using hollow-stem-auger drilling equipment. Well construction activities involved

drilling out the well materials and sealing the evacuated boring by pumping a cement-bentonite slurry through a tremie pipe from the bottom of the boring to the ground surface (Levine Fricke, 1992c).

Concrete Structures Encountered During Excavation

On December 26, 1991, a concrete trough was encountered along the northern Ransome fence. The trough (approximately 52 feet long and 8 feet deep) was oriented in a north-south direction, with the northern end of the trough adjacent to the northern Ransome fence. Soil was excavated from the sides of the trough and the concrete was broken in January 1992 using a pneumatic hammer attached to the excavator operated by Plant Reclamation. The concrete rubble was subsequently excavated and stockpiled on the YBP Site on plastic sheeting. The perimeter of the concrete stockpile was bermed to minimize surface runoff.

Because of heavy precipitation during December 1991 and January 1992, surface runoff, apparently facilitated by the sloped excavation walls, ponded in the Northern Area in the vicinity of the concrete trough, west of Excavation H. A sheen was observed on the surface of the water, presumably from contact with gasoline-affected soil not yet excavated from the northern wall of the excavation or from beneath the concrete trough. H & H Ship Service Company (H&H) of San Francisco, California, pumped approximately 15,000 gallons of water out of the excavation and into a vacuum truck for transportation to a recycling facility on January 27 and 29, 1992. Hazardous waste manifests are attached in Appendix F.

In February 1992, Plant Reclamation used a pneumatic hammer to break a concrete vault located adjacent to excavation A' that had been encountered by ARI in September 1991 (Section 2.1). The concrete rubble was subsequently excavated and is currently stockpiled on the Property.

Because of heavy precipitation during February 1992, surface water ponded in the vicinity of the former concrete vault in excavation A'. A sheen was observed on the ponded water, presumably from contact with petroleum-affected soil not yet excavated in this area. On March 4, 1992, H&H pumped 2,600 gallons of water from this area into a vacuum truck for transportation to a recycling facility.

Manifests for water transported by H&H are contained in Appendix F.

3.3.2 Verification Sampling and Analysis

To verify that the Northern Area excavation was complete and that petroleum-affected soil had been removed, one sidewall soil sample was collected by Levine Fricke approximately every 20 linear feet, and one floor sample was collected approximately every 400 square feet. A total of 57 sidewall samples and 37 floor samples were collected by Levine Fricke for chemical analysis of TPHg, TPHd, and TPHo using Modified EPA Method 8015, BTEX compounds using EPA Method 8020, and total hydrocarbons using Standard Method 5520f, 17th Edition. Analytical results for these samples are presented in Table 4. Laboratory certificates are presented in Volume III, Appendix M.

Soil samples were not collected along the northern border of former ARI excavations H and J because clean backfill material from those excavations was encountered.

Soil was then removed from the excavation in the vicinity of 21 sampling locations where TPHg and BTEX concentrations were above the excavation criteria. A total of 73 samples represent the final excavation boundaries. Final verification soil sample locations and analytical results are presented on Figure 7.

Of the 73 samples collected, TPHg was detected at concentrations above the excavation criteria in 3 samples (SW-38, SW-41, and SW-42) collected from the northern boundary of the Property at concentrations ranging from 45 ppm to 90 ppm (Figure 6). Concentrations of benzene ranged from 0.08 ppm to 0.70 ppm and toluene, ethylbenzene, and xylene concentrations ranged from 14 ppm to 20.6 ppm in the same three samples. Based on the proximity of the 3 sample locations to an existing parking lot structure located immediately north of the Property, and the possibility that additional excavation could potentially undermine the existing structure, the soil was left in place.

3.4 Characterization and Management of Excavated Soil

Section 3.4.1 describes methods used by Levine Fricke to characterize soil excavated from the Northern Area under the direction of Levine Fricke and from other areas on the Property under the direction of Aqua Resources. Section 3.4.2 describes aeration of gasoline-affected soils excavated from the Northern Area.

3.4.1 Characterization of Excavated Soil

Soils Excavated by Levine · Fricke

Characterization of soils excavated from the Northern Area by Levine-Fricke was completed at the time of excavation. The soil excavated from the Northern Area was characterized as primarily gasoline-affected based on PID readings, observations during excavation, analytical data for soil samples submitted to the laboratory on a "rush" turnaround time, and previous analytical data obtained during excavation activities conducted by ARI and Levine-Fricke in adjacent areas.

PID readings were used to facilitate segregation of soil during excavation. Soils registering less than 100 ppm on PID (generally from depths of 4 feet bgs or less) were considered "lesser-affected" soil and were placed in two stockpiles: one on the Property and one on the east portion of the adjacent YBP Site. Soils registering greater than 100 ppm on the PID (generally from depths ranging between 5 and 11 feet) were considered to be affected by gasoline and also were placed in two stockpiles that were separated from the lesser affected soil: one on the Property and one on the eastern portion of the YBP Site.

Gasoline-affected soil excavated from the Northern Area by Levine-Fricke were subsequently aerated on site, as discussed in Section 3.4.2.

Soil Excavated by Aqua Resources

To characterize approximately 15,000 cubic yards (stockpiled volume) of soil previously stockpiled on the Property under the direction of ARI, Levine Fricke personnel collected 321 soil samples during the period from October 15 through November 7, 1991.

The soil samples submitted for chemical analysis were composites of three to four individual samples placed into one brass tube. One composite sample was submitted for approximately 50 cubic yards of soil. Soil samples were collected and prepared for transportation to the analytical laboratory by Levine. Fricke personnel according to the standard methods and protocols presented in Appendix B.

The soil samples were submitted to PAL for analysis of TPHg, TPHd, and TPHo using modified EPA Method 8015; total oil and grease using EPA Method 5520e; and TPH using Standard Method 503E, 16th Edition. Twenty of these samples also were analyzed for BTEX compounds using EPA Method 8020.

A summary of analytical results for soil samples collected from ARI stockpiles are presented in Table 5. The analytical results of stockpiled soils indicate that soils excavated by ARI and currently stockpiled on the Property contain concentrations of diesel and oil exceeding backfill criteria (Section 1.3.3).

Diesel was detected in 54 samples at concentrations ranging from 10 ppm to 2,000 ppm, which is above backfill criteria of 10 ppm. Oil was detected in 13 samples at concentrations exceeding the backfill criteria of 500 ppm, ranging from 560 ppm to 2,500 ppm. However, results for oil analysis using EPA Method 8015 represent only the petroleum component of oil. In response to ACHA requests that soil be analyzed using an analytical method that screens for total oil and grease compounds (including animal fat and/or vegetable oil components of oil), nine soil samples were randomly selected for oil and grease analysis using EPA Standard Method 5520 for total oil and grease. Oil and grease were detected in 8 of the 9 samples at concentrations ranging from 200 ppm to 17,000 ppm. Laboratory certificates are contained in Volume III, Appendix N.

Based on these results, the soils excavated from the Property were characterized as oil- and diesel-affected. Therefore, these soils will be contained on site in accordance with the approved Containment Plan, as discussed in Section 4.0.

3.4.2 Aeration of Gasoline-Affected Soil Excavated from the Northern Area

Based on PID measurements, observations, and analytical results for soil samples collected from previous excavations completed by ARI, open aeration was chosen as the best method for remediation of gasoline-affected soil excavated from the Northern Area. Aeration of soils was conducted in compliance with BAAQMD Rule 8, Regulation 40. The gasoline-affected soils were aerated on site to reduce gasoline and BTEX concentrations to aeration criteria of 10 ppm TPHg, 1 ppm for total ethylbenzene, toluene, and xylenes, and below laboratory detection limits for benzene, which had been verbally approved by the ACHA and the RWQCB in a meeting with Levine-Fricke and Catellus on February 13, 1992 (Section 1.3.2).

Field Procedures

Plant Reclamation conducted the on-site aeration activities. To accommodate aeration beds, Plant Reclamation moved stockpiles SP-10 and SP-19 (former ARI aeration beds) to new locations (Figures 4 and 8) between May 11 and May 15, 1992. As shown in Figure 8, six aeration beds were constructed on the Property. Stockpiled soils that registered greater than 100 ppm on the PID at the time of excavation were placed on aeration beds 1, 2, 4 and 6. The remaining soil was placed on aeration beds 3 and 5. Aeration bed construction is described in Appendix G.

Aeration activities were initiated on May 15, 1992, and approximately 9,600 cubic yards of soil were aerated. Soils were turned periodically using two excavators with "grappler" extensions to enhance the aeration process. The aeration process periodically was monitored using a PID.

One sample for every 50 cubic yards of aerated soil was collected in accordance with procedures described in Appendix B and using a "grid approach" as described in Appendix F. A total of 218 soil samples were collected from the six aeration beds. Soil samples (SS-1 through SS-50) were collected in May 1991, and of these samples, 30 (SS-1 through SS-30) were analyzed. Based on the results for these samples, soils were turned for further aeration. When PID readings of the aerated soils indicated that the concentrations of VOCs had dropped significantly, the remaining 168 samples (SS-51 through SS-218) were collected. The sampling occurred during the period from July 17 to August 28, 1992.

Samples were delivered by courier to PAL for analysis of TPHg and BTEX using EPA Methods 8015/8020. Soil sample SS-154-7D is a duplicate sample and was not analyzed. Samples SS-1 through SS-30 also were analyzed for TPHd and TPHo using Modified EPA Method 8015. Analytical results are discussed below.

Analytical Results

Analytical results for 196 soil samples collected from the aeration beds and submitted for chemical analysis are summarized in Table 6. Analysis of soil samples collected from aerated soils indicated the following:

• TPHg exceeding 10 ppm was detected in only eight samples (at concentrations ranging from 11 ppm to 110 ppm)

- Benzene exceeding the excavation criterion of 0.005 ppm was reported in only eight samples at concentrations ranging from 0.009 ppm to 0.045 ppm.
- The combined concentration of toluene, ethylbenzene, and xylenes exceeding the aeration criterion of 1 ppm was detected in only one sample (sample SS-8-7A) at 4.95 ppm.
- The highest concentrations of TPHg and BTEX were detected in samples collected during May 1992 before final soil mixing.

These sample results were evaluated using guidelines outlined in Chapter 9 of the Environmental Protection Agency Office of Solid Waste Management Document SW-846, Test Methods for Evaluating Solid Waste (hereafter "EPA SW-846"), as described in Appendix H. The results of this evaluation indicate that a sufficient number of samples have been collected from the aeration beds to adequately characterize (with an 80 percent confidence level) the aerated soils as suitable for backfill material with respect to gasoline and BTEX concentrations. Laboratory certificates are contained in Volume III, Appendix O.

3.5 Backfill and Compaction

Excavations completed by ARI and Levine Fricke were backfilled by Plant Reclamation, of Richmond, California, during the period from October 15, 1991 through May 29, 1992 (Phases II, III and IV). A Levine Fricke field engineer was on site during backfill and compaction activities to monitor fill placement and compaction, and to conduct field compaction tests. A detailed description of backfill and compaction procedures is included in Appendix C. Figures C-1 and C-2 show the approximate locations of completed excavations backfilled and compacted as directed by ARI and Levine Fricke.

Clean imported fill and 2,500 cubic yards of the 5,480 cubic yards of soil aerated by ARI were used as backfill in completed excavations. Backfill material specifications and compaction requirements are discussed in Section 2.3.

To assess whether the aerated soil had been adequately characterized by ARI, Levine. Fricke evaluated analytical results for soils samples previously collected from aeration beds using EPA SW-846. Based on this evaluation, it was determined that 11 additional confirmatory soil samples needed to be collected and analyzed. These samples were collected

4.1 Soils

In accordance with the Containment Plan, petroleum-affected soil will be contained on site beneath proposed building pads and/or in areas to be covered with asphalt or concrete (parking lots). Specifically, diesel- and oil-affected soil excavated from the Property and currently stockpiled on the Property and the YBP Site will be placed in parts of the Property to be covered by asphalt parking areas proposed for east of Hollis Street (see Figure 4 of the Containment Plan). Placement of the soils beneath asphalt and/or concrete will minimize possible exposure to the affected soils and mitigate future effects to shallow ground water by reducing surface infiltration through the soil. It is anticipated that the soils will be placed beneath the parking lots at the time of site development. To inhibit possible surface runoff before site development, the stockpiled soils are currently being covered using 10-mil plastic sheeting and bermed appropriately.

4.2 Ground-Water Monitoring

To assess the effects on shallow ground water of petroleumaffected soils at the Property, a ground-water investigation was conducted for the Property in accordance with the Work Plan prepared by Levine Fricke dated April 15, 1992 (Levine Fricke, 1992b). Results of the investigation indicated that shallow ground water beneath the Property has not been significantly affected by petroleum hydrocarbons. Monitoring well locations and ground-water quality results for wells installed by Levine•Fricke and ARI are presented on Figure 9. As indicated on Figure 9, no TPHg was detected in any of the wells installed by Levine. Fricke during two rounds of sampling conducted in May 1992. Benzene was detected at a very low concentration (0.0004 ppm) in wells LF-25 and LF-27 during the first round of sampling, but was below detection limits in the second round. TPHo and total recoverable hydrocarbons were detected in well LF-25 and off-site well LF-16 at concentrations of 6.6 ppm or less.

In accordance with the Containment Plan, ground-water samples will be collected on a quarterly basis from selected wells in Area B of the YBP Site for analysis of TPHo and TPHd to monitor potential future effects of petroleum-affected soils on ground water beneath the Property. Quarterly monitoring of selected wells in Area B will be conducted for a minimum of one year, beginning in October 1992 (Levine Fricke, 1992d).

Additionally, ground-water samples are currently collected on a semiannual basis from selected wells in Area A of the YBP Site for analysis of TPHd and TPHo, in accordance with the Sampling and Analysis Plan implemented in January 1992 for Area A of the YBP Site (Levine Fricke, 1991d).

5.0 SUMMARY AND CONCLUSIONS

Approximately 26,800 cubic yards (estimated in-place volume) of petroleum-affected soil were excavated during remedial activities conducted for the Property by ARI and Levine. Fricke. Soils were excavated to criteria approved by the ACHA and completed excavations were backfilled using clean imported fill or excavated soil that contained petroleum hydrocarbon compounds at concentrations below the backfill criteria approved by the ACHA. The backfill material generally was compacted to 90% as confirmed by laboratory and field compaction tests.

Approximately 4,100 cubic yards (estimated stockpile volume) of excavated diesel- and oil-affected soils were transported off site for thermal treatment, as directed by ARI.

Approximately 2,500 cubic yards (estimated stockpile volume) of gasoline-affected soils excavated by ARI were successfully aerated on site by ARI in accordance with recommendations included in ARI's 1991 report and criteria approved by the ACHA. The successfully aerated soil was used as backfill material for the Property. Approximately 9,600 cubic yards (stockpile volume) of gasoline-affected soil excavated by Levine-Fricke were successfully aerated on site by Levine-Fricke for gasoline and BTEX compounds but contain concentrations of diesel and oil above backfill criteria.

A total of approximately 25,000 cubic yards of soil, generally containing less than 2,000 ppm TPHd and TPHo, currently are stockpiled on site. This total includes soil successfully aerated to established criteria for TPHg and BTEX compounds. These petroleum-affected soils will be contained on site in accordance with the approved Containment Plan (Levine Fricke, 1992a). Petroleum-affected soil will be placed beneath low permeability asphalt paving in parking areas proposed for portions of the YBP Site, to minimize possible exposure to the affected soils and mitigate future effects to shallow ground water by reducing surface infiltration through the soil.

Based on observations of soil remediation activities conducted by ARI and on laboratory data for verification samples collected from the sidewalls and floors of excavations completed by ARI and Levine. Fricke, no additional soil remediation activities are recommended or proposed for the Property.

Ground-water samples will be collected from selected monitoring wells located on the Site during periodic monitoring activities and will be analyzed for petroleum hydrocarbons as oil and diesel to verify that no significant leaching of TPH is occurring at the Property.

REFERENCES

- Alameda County Health Care Services Agency (ACHA). 1991. | Correspondence to Mr. Ric Notini of Catellus Development Corporation. Subject: site remedial plan. March 5.
- Aqua Resources, Inc. (ARI). 1990a. Draft workplan for initial subsurface investigation and site closure, 4030 Hollis Street, Emeryville, California. July 25.
- _____. 1990b. Addendum number 1, draft workplan for initial subsurface investigation and site closure, 4030 Hollis Street, Emeryville, California. August 23.
- former corporation yard site, 4030 Hollis Street, Emeryville, California. January 16.
- Hollis Street, Emeryville. July 26.
- proposed excavation backfill procedure, 4030 Hollis Street, Emeryville. August 26.
- California Regional Water Quality Control Board (RWQCB).
 1990. Tri-regional board staff recommendations for
 preliminary evaluation and investigation of underground
 tank sites. August 10.
- Kennedy/Jenks/Chilton (KJC). 1989. Baseline environmental assessment report. October.
- Levine Fricke, Inc. 1990. Phase I and phase II environmental investigation, Yerba Buena Project Site, Emeryville and Oakland, California. August 15 (REVISED October 26, 1990).
- Emeryville and Oakland, California. February 11.
- ——. 1991b. Health and safety plan for soil remediation activities, Yerba Buena Project Site, Oakland and Emeryville, California. May 8.
- remediation activities, Yerba Buena Project Site, Oakland and Emeryville, California. October 28.

1991d. Sampling and analysis plan for quarterly ground-water monitoring in Area A and the south-central portion of Area B of the Yerba Buena Project Site, Emeryville and Oakland, California. December 6. Containment plan for petroleum hydrocarbonaffected soils, Yerba Buena Project Site, Emeryville and Oakland, California. March 10. Work plan for ground-water investigations, former Ransome property, Yerba Buena project site, Emeryville, California. Report. Emeryville, California. April 15. 1992c. Ground-water investigation, Former Ransome Property, Yerba Buena Project Site, 4030 Hollis Street, Emeryville, California. August 4. 1992d. Work plan to install one ground-water monitoring well and conduct quarterly ground-water monitoring, Former Ransome Property, Yerba Buena Project Site, 4030 Hollis Street, Emeryville, California.

September 15.

TABLE 1 ANALYTICAL RESULTS OF VERIFICATION SOIL SAMPLES FORMER RANSOME PROPERTY, EMERYVILLE, CALIFORNIA (Concentrations in parts per million)

	*****	2224444	=======			*********	=======	=========	======	=======================================	====	∮=== :
	Sample											
Sample	Depth			ETHYL-					OIL &			
Designation	(feet)	BENZENE	TOLUENE	BENZENE	XYLENE	GASOLINE	DIESEL	KEROSENE	GREASE	HYDROCARBONS	OIL	+
Detection L	imita.	<0.005	<0.005	<0.005	<0.005	<1.0	<1.0	<1.0	<50	<10	-20	ļ
(unless other			(0.005	CO.003	10.003	×1.0	11.0	1.0	130	<10	<20	ľ
AB-1-8.5	8.5	ND	0.0055	ND	ND	ND	ND	ND	ND			
AE-2-3	3	ND	0.0095	ND	ND	ND	ND	ND	ND			
AN-3-5.5	5.5	ND	ND	ND	МD	ND	ND	ND	ND	•••		
AS-5-3.5	3.5	ND	ND	ND	ND	ND	ND	ND	ND	ND		
AS-5-3.5*	3.5	ND	ND	ND	ND	ND	ND		10	ND		ND
AW-4-6	6	ND	0.0055	ND	ND	NĐ	ND	ND	ND		+	
4 =	_	416			416		1.15					1
A'B-1-7 A'E-2-3	7 3	ND	ND	ND	ND	ND	ND ND	ND	ND ND		1	
A'N-3-4.5	4.5		•••				ND	ND ND	ND]	
A'S-4-2.5	2.5			•	•••		ND	ND	60	•••]	
A W-5-5	5	ND	ND	ND	ND	ND	ND	ND	ND	•••	ļ	ļ
	•		""		110	112		110				I
88-3-5.5	5.5	ND	0.011	ND	ND	ND	ND	ND	ND			ND
BB-3-5.5*	5.5	ND	ND	ND	ND	ND	ND	***	ND	• • •	-	
BB-4-5	5	ND	0.0083	ND	ND	ND	ND	ND	ND	•••	,	
BB-5-4	4	ND	0.010	ND	ПD	ND	ND	ND	ND	•••	ł	
BE-8-3	3	ND	ND	ND	ND	NO	ND	ND	ND	•••	ļ	
BB-8-3*	3	ND	ND	ND	ND	ND	ND		ND	ND		ND
BS-6-3	3	ND	0.035	ND	ND	ND	ND	ND	ND		ŀ	
8S-6-3*	3	ND	ND	ND	ND	ND	ND		20	ND		ND
BW-1-1.5	1.5	ND	0.016	ND	ND	ND	ND	ND	ND	* * *	İ	
BW-1-1.5*	1.5	ND	ND 0.0073	ND	ND	ND	ND	HO.	ND	ND		ND
8W-2-3 8W-7-2.5	3 2.5	ND DN	ND	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND		Ī	
DM-1-6.3	2.5	RU	NU	NU	RD	NO	AD	ND	NU			
B 1 1 B - 3 - 9	9	ND	ND	ND	ND	ND	ND	ND	ND			
8'1E-5-6	6	ND	ND	ND	ND	ND	ND	ND	ND			
B'1E-5-6*	6	ND	ND	ND	ND	ND	ND		ND	ND		ND
8 1N-1-7.5	7.5	ND	ND	ND	ND	ND	ND	ND	ND		Ļ	
B118-4-7	7	ND	ND	ND	ND	ND	ND	ND			- 4	
B+1W-2-5.5	5.5	ND	ND	ND	ND	ND	1.3	ND			,	
CB-1-6.5	6.5	ND	ND	ND	ФИ	ND	ND	ND	ND			
CB-1-6.5*	6.5	ND	ND	ND	ND	ND	ND		20	10		ND
CE-3-3	3	ND	0.064	ND	ND	ND	ND	ND	ND	• • •	ŀ	
CE-3-3*	3	ND	ND	ND	ND	ND	ND		20	10		ND
cs-2-3	3	ND	ND	ND	ND	ND	ND	ND	ND	• • •	•	
20.24	,	MB	NB	NO.	NO	MD	ND.	110	М			
DB-2-4 DB-3-5.5	5. 5	ND ND	ND ND	ND ND	NO	ND ND	ND ND	ND ND	ND ND			
DB-8-6	5.5	ND	ND	ND	0.0067		ND	25	ND			
DB-19-5.5	5.5	ND	ND	ND	ND	ND	ND	ND	ND			
0B-19-5.5*	5.5	ND	ND	ND	ND	ND	ND		10	ND		ND
08-24-5.5	5.5	ND	ND	ND	ND	ND	ND	ND	ND	•••	١.	
08-34-8.5	8.5	ND	ND	ND	0.017		ND	ND	ND		.	
B-35-9.5	9.5	ND	ND	ND	ND	ND	ND	ND	ND	•••	.	
DB-35-9.5*	9.5	ND	0.007	ND	100	4	ND		ND	ND		ND
8-36-10	10	ИĎ	ND	ND	ND	ND	ND	ND	ND		-	
B-36-10*	10	ИĎ	ND	ND	ND	ND	ND		ND	ND		ND
B-37-10	10	ND	ND	ND	ND	ND	ND	ND	ND			
8-37-10*	10	ND	ND	ND	0.005		ND		40	40		10
08-38-10	10	ND	ND	ND	ND	ND	ND	ND	ND		-	
08-46-10.5	10.5	ND	ND	ND	ND	ND	3.8	ND		•••		
E-6-4	4	ND	ND	ND	ND	NO	ND	3.4	ND	•••		
E-16-2.5	2.5	ND	ND	ND	ND	ND	ND	ND	ND			
DE-21-4	4	ND	ND	ND	ND	ND	МÐ	ND	ND			
E-25-2	2	ND	ND	ND	ND	ND	ND	ND	ND			
E-39-6	6	ND	ND	ND	ND	ND	ND	ND	ND			
DE-40-5.5	5.5	ND	ND	ND	ND	ND	ND	ND	ND			
DE-45-5	5 3	ND ND	ND 0.032	ND	ND	ND	4.8	ND	ND	~ • •		
วท-1-3			11 (147	ND	ND	ND	MD		ND		1.	

TABLE 1 ANALYTICAL RESULTS OF VERIFICATION SOIL SAMPLES FORMER RANSOME PROPERTY, EMERYVILLE, CALIFORNIA (Concentrations in parts per million)

=======================================	sample		=======================================	**===##	======	******	#======		======		
Sample	Depth			ETHYL-					OIL &		
Designation	(feet)	BENZENE	TOLUENE	BENZENE	XYLENE	GASOL INE	DIESEL	KEROSENE	GREASE	HYDROCARBONS	011
D	_!	-0.005	-0.00E	40 AAE	40. 00E	-4.0	-4.0	-4.0	4E0	-40	-20
Detection Li (unless othe		<0.005	<0.005	<0.005	<0.005	<1.0	<1.0	<1.0	<50	<10	<20
Cultiess offic											
DN-1-3*	3	ND	ND	ND	ND	ND	ND		40	20	ND
DN-4-3	3	ND	ND	ND	ND	ND	2.1	ND	ND		•••
DN-9-3	3	ND	ND	ND	ND	ND	ND	ND	ND	***	
DN-9-3*	3 2.75	ND	ND 	ND	ND 	0.4	ND ND	ND	20 220	ND ~	ND
DN-22-2.75 DN-26-4	4.15	ND	ND	ND	ND	ND	ND	ND CM	ND	*	[
DN-29-4.5	4.5	ND	ND	ND	ND	ND	ND	ND		'	
DN-30-6.5	6.5	ND	ND	ND	ND	ND	ND	ND	ND		
DN-31-5	5	ND	ND	ND	ND	ND	ND	ND		***	
DS-5-5	5	ND	ND	ND	ND	ND	ND	ND	ND		• • •
DS-14-5	5	ND	ND	ND	ND	ND	ND	ND	ND Zoo	***	
0\$-20-3 0\$-27-2.75	3 2.75	ND	ND	ND	ND	ND 	ND ND	ND ND	700 ND		
DS-41-4	4						ND	ND	ND	•••	
DS-47-6	6	ND	ND	ND	ND	ND					
DW-11-5	5	ND	ND	ND	ND	ND	ND	ND	ND	***	
DW-11-5*	5	ND	ND	ND	ND	ND	ND		ND	ND	ND
DW-32-4.5	4.5	ND	ND	ND	ND	NO	ND	ND	ND	•••	
DW-32-4.5*	4.5	ND	ND	ND	ND	ND	ND		ND	ND	ND
DW-33-5	5 5	ND	ND	ND	0.017		ND	ND		•••	
DW-42-5 DW-43-3.5	3.5	ND	ND	ND	ND	ND ND	ND ND	ND ND	ND	***	
DW-44-6	3.5					ND	ND	ND		•••	
0W 44 0	•					.,					
EB-5-10	10	ND	ND	ND	ND	ND	ND	ND	ND		
EE-1-3.5	3.5	ND	ND	ND	ND	ND	ND	ND	130		
ES-4-2	2						ND	ND	110		•••
EW-3-3	3	ND	ND	ND	ND	ND	ND	ND	ND		
FB-5-11	11	ND	ND	ND	ND	ND	ND	ND	ND	***	
FN-3-3	3	0.0098	0.0071	0.190	0.470	<u>(12)</u>	<10	<10	130		• • •
FS-4-6	6	ND	ND	ND	ND	ND	ND	ND	ND		
FW-6-5	5	0.270	0.0053	0.032	0.170	(12)			ND	•••	
_											
GB-2-6.5	6.5	ND	ND	ND	ND	ND	ND	ND	ND		
GB-5-11.5	11.5	ND	ND	ND	ND	ND	ND	ND		110	
GB-5-11.5*	11.5 11	ND ND	ND	ND ND	ND Da	ND ND	ND ND	ND	ND ND	ND	ND
GB-6-11 GE-8-7	7	ND	ND ND	ND	ND	ND	ND ND	ND	ND	•••	
GN-1-3	3	ND	ND	ND	ND	ND	ND	ND	660	•••	
	_					- · -					
JB-4-11	11	ND	ND	ND	ND	ND	ND	ND	ND		
JB-7-13.5	13.5	ND	ND	ND	ND	ND	ND	NO	ND	•••	
JB-9-4.5	4.5	ND	ND	ND	ND	ND	ND	ND	ND	• • •	
JB-10-6.5 JB-11-6.5	6.5 6.5						ND ND	ND ND			
JB-12-13.5	13.5	ND	ND	ND	ND	ND	NU				
JB-12-13.5*	13.5	ND	0.001	NO	ND	ND	NO		ND	ND	ND
JB-13-13.5	13.5	ND	ND.	ND	ND	ND	ND	ND	ND	***	
J8-14-14	14	ND	ND	ND	ND	ND	ND	ND '	ND		
JB-15-14	14	ND	ND	ЯD	ND	MD	ND	ND	ND		
JB-16-14	14	ND	ND	ND	ND	ND	ND	ND	ND	•	
JB-17-14	14	ND	ND	NO	NO	ND				***	
JB-18-14	14	ND 0.004	ND	ND	ND	ND	ND	ND	ND		
JB-19-14	14	0.006	ND	ND	ND ND	ND ON	ND	ND	ND		
JB-20-14 JB-20-14*	14 14	ND 0.002	ND 0.002	ND ND	ND 0.008	ND ND	ND		ND	ND	ND
JB-21-14	14	ND	ND	NO	ND	ND	ND		ND	ND	ND CM
JB-22-14	14	ND	ND DN	ND	ND	ND				*	
JB-23-14	14	ND	ND	ND	ND	ND	ND	ND	ND	•••	
JB-24-14	14	ND	ND	ND	ND	ND					
JB-25-14	14	ND	ND	ND	ND	ND	ND	ND	ND		

TABLE 1 ANALYTICAL RESULTS OF VERIFICATION SOIL SAMPLES FORMER RANSOME PROPERTY, EMERYVILLE, CALIFORNIA (Concentrations in parts per million)

Sample ETHYL -A 110 Sample Depth Designation (feet) RENZENE TOLUENE BENZENE XYLENE GASOLINE DIESEL KEROSENE GREASE HYDROCARBONS OIL <50 <0.005 <0.005 <0.005 <0.005 <1.0 <1.0 <1.0 <10 <20 Detection Limits: (unless otherwise noted) ND JB-26-14 ND ND JB-27-13 ND ND 0.007 ---13 MП ND __ NĐ JB-28-13 13 0.011 ND ND ND ND ND ND ---JB-28-13* 0.014 ND ND ND ND ND ND 13 ND ---ND ND ND ---JB-29-13 13 ND ND ND ---------ND --JB-30-13 ND ND ND ND ND ND ND 13 JB-31-13 13 ND ND ND ND ND ND ND ND ---٠. ND ---ND ND JB-31-13* 13 ND ND ND ND ND ND NĐ ND JB-33-9 9 ND ND ND ND ND ND ---Q ND 0.0075 0.0073 ND 2.6 ------- - ----- -JB-34-9 0.059 0.015 ___ ---------JB-35-8.5 8.5 ND ND 0.003 ND ND ND ---٠. JB-35-8.5* 8.5 ND ND ND ND ND ND --------------J8-36-8.5 8.5 ND ND ND ND ND ND ND ND ND JB-56-12 12 ND ND JB-65-13 13 ND ND ND NO ------------٠. ND ND ND ND - - -. . JB-67-13 13 ND ND ND ND ND - - -ND NÖ ND ND ND ND JE-1-7 ND ND JE-2-6 ND ND ND ND ND ND ND ND --------- -JE-44-9 ND ND ND ND ND ND ND ND JE-49-8 ND ND ND ---8 ND NĐ ND ND ND JN-8-8.5 8.5 ND ND ND ND ND ND ND ND ------ND ND ------JN-48-8.5 8.5 ND ND ND - - -JN-50-7 ND ND ND ND ND ------------JN-51-9.5 9.5 ND ND ND ND ND ND ND ND - -MD ND MΩ ---JN-52-7 ND ND ND ND ND JN-53-9.5 9.5 ND ND 0.032 ND ND ND ND ---. _ _ 5.0 (32) 30 0.044 0.015 1.90 ND 30 ND JN-53-9.5* 9.5 0.053 0.024 0.011 2.5 ND ND ND ---JN-54-7 7 ND JN-54-7* 0.350 0.007 0.320 0.340 5.5 ND 10 ND ND 7 JN-55-9.5 9.5 0.084 0.130 2.0 7.7 120 ND ND ND ---- -JN-57-10 10 ND ND ND ND 3.8 ND ND ND JN-58-9.5 9.5 ND ND ND ND ___ ------- - -ND ND ND ND 10 ND ND JN-62-6 6 ND ND JS-3-4 4 ND ND ND ND ND ND ND ND ---. . . JS-42-7 ND ND ND ND ND ND ND ND 0.0054 JS-59-8 8 0.0092 ND ND 1.7 ---------- - -------8 ND ND ND 1.3 1.1 ND ND NÖ JS-63-8 JS-64-7.5 7.5 ND ND ND ND ND ---- - ----- - -ND ---ND JS-64-7.5* 7.5 ND ND ND ND ND 20 JS-66-8 8 ND ND ND ND ND ND ND ND ---- - -9 ND ND ND ---------------JS-68-9 ND ND ND ND 20 ND JS-68-9* MD NO ND NO NO 1.9 JS-70-7 ND ND ND ND ND ND ---- - -ND ------ND ND ND ND ND ND ND 6 ND JW-5-6 ---ND ND JW-6-7 ND ND ND ND ND ND JW-37-10 10 ND NĐ ND ND ND ------------- - -0.0087 ---- - -JW-38-9 ND ND 9 ND NO - - -JW-69-6.5 6.5 ND ND ND ND ND ND ND ND ---KB-2-11.5 11.5 ND ND ND ND ND ND ND ND ------**KB-2-11.5*** ND 11.5 ND ND MD ND ND NO ------KB-8-11.5 11.5 ND NO ND 0.025 ND 16 ND 90 ---. . . KB-13-11.5 5.5 ND ND ND - - -ND 0.011 ND ND ND ND KB-20-11 11 ND 0.004 0.001 ND 0.003 ND ND ---ND ND ---KB-20-11* 11 KB-29-10.5 ND ND ND ND ND 10.5 ND ND ND - - -KB-32-11 ND NĐ ND ND 1.2 ND NO ---11 ND ------KB-35-8.5 8.5 ND ND ND ND ND ND ND ND ------KB-36-7.5 7.5 ND ND ND ND ND ND ND ND - - ----0.035 ND ND ND ND ND KE-4-5.5 5.5 ND 1.1 - - -- - -KE-30-6.5 6.5 ND ND ND ND ND 1.2 ND ND ND ND ND ND 1.0 ND ND NO KE-31-7

TABLE 1 ANALYTICAL RESULTS OF VERIFICATION SOIL SAMPLES FORMER RANSOME PROPERTY, EMERYVILLE, CALIFORNIA (Concentrations in parts per million)

Depth ETHYL-OIL & Samole Designation (feet) BENZENE TOLUENE BENZENE XYLENE GASOLINE DIESEL KEROSENE GREASE HYDROCARBONS OIL Detection Limits: <0.005 <0.005 <0.005 <0.005 <50 <1.0 <1.0 <1.0 <10 <20 (unless otherwise noted) 0.005 41 KN-1-8 8 0.024 0.093 0.170 ND ND ... KN-9-6.5 6.5 ND ND 0.0059 0.0087 1.3 3.8 ND ND KN-9-6.5* 6.5 ND ND ND ND ND ND ---ND ND ND KN-23-6 ND ND ND ND ND 1.0 ND 6 KN-23-6* ND ND ND ND ---ND ND 6 NO ND KS-11-5.5 ND ND ND 1.1 ND --5.5 ND ND ND ... KS-24-6 ND ND ND ND ND ND ND 6 KS-24-6* מע ND 10 ND 6 ND מע ND NO ---KS-27-7 ND ND ND 1.1 ND ---ND ND ND ND KS-28-6.5 6.5 ND ND ND ND 1.1 ND ND ---ND KS-33-5 ND NO ND ND ND ND ND ---KS-33-5* 5 NO ND ND ND ND ND ---ND ND KW-14-6 ND ND ND ND ND ND ---6 ND ---7.5 KW-22-7.5 ND ND 0.110 0.037 2.8 1.4 ND ------KW-34-6.5 6.5 ND ND ND ND ND ND ND ND 6.5 ND ND ND ND ND ND ND ND ---LB-4-6.5 ND ND ND ND ND ND ND LB-4-6.5* 6.5 ND ND LB-15-10.5 10.5 ND ND ND ND ND 1.1 ND ND -----LB-20-10.5 ND ND ND ND ND 10.5 ND ND 1.4 ND LB-20-10.5* 10.5 ND ND ND ND 1.4 ND ---10 ND ND ND ND 1.2 ND ___ LB-24-12.5 12.5 ND ND ND --LB-44-10.5 10.5 ND NO ND ND ND ND ND ND LB-45-10.5 10.5 ND ND ND ND ND ND ND ND ---. - -LE-1-3.5 - -ND ND ND 3.5 ND LE-6-5 ND ND ND ND ------------. . . LE-18-7 7 ND ND ND ND ND ND ND ND 0.012 LE-25-9 9 ND ND ND 1.1 ND ND ND ---- -LE-40-4.5 4.5 ND ND ND ND ND NĐ ND ND LE-40-4.5 4.5 ND ND ND ND ND NO ND ND . . . LE-41-5 ND ND ND ND 1.1 ND ND NĐ LN-27-6 ND ND NO ND ND ND ND - -6 ---LN-34-3.5 3.5 0.011 ND 0.0057 0.035 3.5 ND ND . . . ------LS-2-3 3.3 76 - - -ND ---3 0.033 0.0093 3.3 LS-10-4 ND ND 73 ND 510 ---LS-30-4 ND ND ND ND ND 1.9 ND ND ---LS-36-4 4 ND ND ND ND ND 2.4 ND ------LS-36-4* ND ND ND ND ND ND 30 ND ---ND LS-43-6.5 6.5 ------ND ------. . . NĐ ND ND ND ND ND ND ------- - -LS-47-7 LS-47-7* ND ND ND ND ND ND ND ND LW-3-5 ND ND ND ND ND ND NĎ ND ND ... LW-3-5* ND ND ND ND HD ND ND ND ND ND LW-28-4 ND ND ND ND 2.1 ND ND -----0.014 0.140 0.093 ___ 20 10 LW-28.1-8** 8 ND ND ND LW-35-4 MO MD NO NO ND ND ---ND ND ND 0.0063 1.3 ND ND LW-39-4.5

NOTES:

Samples collected by Aqua Resources, Inc. were analyzed by Curtis & Tompkins, Ltd., Analytical Laboratories. Samples were analyzed for total volatile hydrocarbons (TVH) as gasoline, and extractable petroleum hydrocarbons (EPH) as kerosene and diesel using modified EPA Method. 8015, BTEX using EPA Method 8020, and oil and grease by Standard Method 5520e and total recoverable hydrocarbons by 5520f. Samples collected by Levine-Fricke were analyzed by Quanteq Laboratories (formerly Med-Tox Associates, Inc.) using the same methods as Aqua Resources, Inc. Several samples also were analyzed for oil using modified EPA Method 8015.

^{*} Duplicate sample collected by Levine-Fricke Inc.

^{**} Sample collected by Levine-Fricke Inc. only.

ND = not detected

TABLE 2 ANALYTICAL RESULTS OF SOIL SAMPLES COLLECTED FROM AQUA RESOURCES! AERATION BEDS (concentrations in parts per million [ppm])

Sample ID	Stockpile	Benzene	Toluene	Ethyl - benzene	Xylenes	Gasoline	Diesel	Oil & Grease	Oil (EPA 8015)
Samples c	ollected I	y Aqua R	esources,	Inc. *:				~~~~~	
A 1-2		ND	ND	ND	ND	ND	ND	590	NS
A 3-6		ND	ND	ND	ND	ND	ND	480	NS
B 1-4		ND	ND	ND	ND	ND	ND	330	NS
B 5-8		ND	ND	ND	ND	ND	ND	500	NS
C 1-2		ND	ND	ND ND	ND ND	ND ON	2.9	1100	NS
C 3-6 C 7		ND	ND	ND	NU	NO	ND	500	NS NS
0 1-3		ND	ND	ND	ND	ND	ND		NS NS
D 4-7		ND	ND	ND	ND	ND	35	600	NS
0 4-7 0 8-11				4D				400	NS
0 21-4		ND	ND	ND	ND	2.1	ND	510	NS
D 25-8			7D					610	NS
02 17-20		ND	0.014	0.0075	0.022	3.2	ND	370	NS
02 29-32				0.00/5				630	NS
02 40-43		ND	ND	ND	ND	ND	ND	560	NS
D2 44-47		ND	ND	0.0064	0.028	1.8	160	490	NS
02 52-53		ND	ND	ND	2.5	1.8	27	1100	NS
02 54-55		ND	ND	ND	0.0069	ND	13	620	NS
F 1-3		ND	ND	ND	ND	ND	ND	620	NS
F 4-6		ND	ND	ND	ND	ND	ND	380	NS
J 1-4		ND	ND	ND	ND	ND	28	ND	NS
J 5-8		NO	ND	ND	ND	ND	36	88	NS
J 9-12		ND	ND	ND	ND	ND	6.6	ND	NS
J 13-16		ND	ND	ND	ND	ND	6.3	ND	NS
J 17-20		ND	ND	ND	ND	ND	5.8	66	NS
J 21-24						ND	11	ND	NS
J 25-28						ND	13	ND	NS
J 29-30		ND	ND	ND	ND	ND	6.5	110	NS
J 31-34		ND	ND	ND	ND	ND	12	270	NS
JT 1-4								230	NS
JP 1-4						- 4		400	NS
z 1-4		ND	ND	ND	ND	ND	170	630	NS
Confirmat	ory sample	es collec	ted by Le	vine-Fric	:ke**:				
R-110	1	ND	ND	ND	0.005	<10	<10	NA	54
R-192	ż	ND	ND	ND	0.009	<10	<10	NA	60
R-542	6	ND	ND	ND	ND	<10	<10	NA	<50
R-694	6	ND	ND	ND	0.008	<10	<10	NA	59
R-906	6	ND	ND	ND	0.006	<10	<10	NA	59
R-1460	8	ND	ND	ND	ND	<10	<10	NA	<50
R-1519	8	ND	ND	ND	ND	<10	<10	NA	<50
R-1891	9	ND	ND	ND	ND	<10	<10	NA ·	<50
R-2303	9	ND	ND	ND	ND	<10	10	NA	83
	ý	ND	ND	ND	0.022	<10	<10	NA	54
R-2451									

NOTES:

^{*} Soil samples collected by Aqua Resources were submitted to Curtis & Tompkins, Ltd.,

Analytical Laboratories of Berkeley, California

** Soil samples collected by Levine-Fricke were submitted to Precision Analytical
Laboratory, Inc. of Richmond, California.

All soil samples were analyzed for gasoline and BTEX using Modified EPA Method 8015/8020; diesel using Modified EPA Method 8015; and oil and grease using EPA Method 5520e and f.

ND = not detected NA = not analyzed

TABLE 3

ANALYTICAL RESULTS OF SOIL SAMPLES COLLECTED FROM
TEST PITS AND SOIL BORINGS

(Composite the part of the policy policy)

(concentrations in parts per million [ppm])

=========		:======================================		========	=======	:====			=======	=======	=======
			Total							CALI	Tabul
0	Date	Lab Analysis	Recoverable Hydrocarbons	Diocal	oil	0/6	Gasoline	Ponzono	Toluone	Ethyl-	Total
Sample ID	Sampled	Return Date	nydrocarbons	Dieset				Del IZel IC		Delizerie	
PHASE I							•				
TP1-4	16-0ct-91	18-0ct-91	NA	<10	<50	NA	<10	0.028		0.015	
TP1-8	16-0ct-91	18-0ct-91	NA	<10	<50	NA		0.06	-		<0.005
TP1-12	16-0ct-91	18-0ct-91	NA	<10	<50	NA	<10	<0.005	<0.005	<0.005	<0.005
					***		4.6				
TP2-4	16-0ct-91	18-0ct-91	NA	<10	<50	NA		0.360	0.012	0.040	
TP2-8	16-0ct-91	18-0ct-91	NA	60	<50	NA		2.700		21	100
TP2-11	16-0ct-91	18-0ct-91	NA	<10	<50	NA	12	0.090	<0.03	1.30	4.20
TP3-4	17-0ct-91	21-0ct-91	NA	<10	<50	NA	<10	0.028	0.006	<0.005	0.027
TP3-8	17-0ct-91	21-0ct-91	NA NA	<10	₹ 50	NA		0.080		<0.03	
TP3-11	17-0ct-91	21-Oct-91	NA	23	<50	NA		0.460		4.20	
TP4-4	17-0ct-91	21-0ct-91	NA	<10	<50	NA	<10	0.070	0.005	0.390	
TP4-8	17-0ct-91	21-0ct-91	NA	<10	<50	NA	<10	0.230		0.230	
TP4-11	17-0ct-91	21-0ct-91	NA	<10	<50	NA	<10	0.10	0.010	0.480	0.600
		54.5		-40	4F0		40	0 (0	0.007	0.600	0.4/0
TP5-5	17-0ct-91	21-0ct-91	NA	<10	<50 <50	NA		0.40		11	-
TP5-8	17-0ct-91	21-0ct-91	NA.	<10 <10	<50	NA NA		2.70 3.30		15	
TP5-11.5	17-0ct-91	21-0ct-91	NA.	<10	130	NA	220	3.30	دي	13	12
TP8-4	17-0ct-91	21-0ct-91	NA	<10	<50	NA	<10	<0.005	0.009	<0.005	0.027
TP8-8.5	17-0ct-91	21-Oct-91	NA	<10	<50	NA	<10	<0.005	<0.005	0,030	0.009
TP8-12	17-0ct-91	21-0ct-91	NA	<10	<50	NA	<10	<0.005	<0.005	<0.005	0.009
TP9-4	21-0ct-91	23-0ct-91	NA	<10	<50	NA		<0.005		1	<0.005
TP9-8	21-0ct-91	23-0ct-91	NA	<10	<50	NA	<10	<0.005	<0.005	<0.005	<0.005
		n= - 04	***	-40	4E0	на	410	40 00E	40. OOE	-0 00E	40.005
TP10-4	21-0ct-91	23-0ct-91	NA	<10	<50	NA		<0.005			<0.005
TP10-8	21-0ct-91	23-0ct-91	NA	<10	<50	NA	<10	<0.005	<0.005	<0.005	<0.005
TP11-5	21-0ct-91	23-0ct-91	NA	<10	<50	NA	<10	<0.005	<0.005	<0.005	0.040
TP11-8	21-0ct-91	23-0ct-91	, nn NA	<10	<50	NA NA		<0.005			<0.005
TP11-12	21-0ct-91	23-0ct-91	NA NA	55	90	NA		<0.005		-	0.230
1711-12	21-000 91	25 000 71	NA.	-	,,	,,,,		.0,005	10,005	10002	01200
TP12-4	21-Oct-91	23-0ct-91	NA	<10	<50	NA	<10	<0.005	<0.005	<0.005	<0.005
TP12-8	21-0ct-91	23-0ct-91	NA	<10		NA			<0.005		<0.005
TP12-12	21-0ct-91	23-0ct-91	NA	<10	<50	NA	<10	<0.005	<0.005	<0.005	<0.005
TP13-4	21-0ct-91	23-Oct-91	NA	<10		NA					<0.005
TP 13-8	21-0ct-91	23-0ct-91	NA	<10		NA					<0.005
TP13-12	21-0ct-91	23-0ct-91	NA	<10	<50	NA	<10	<0.005	<0.005	<0 -009	<0.005
			g /40.00	400	4 /00	AI A	-10	-0 00F	-0.00F	-0 005	<0.005
TP14-4	21-Jan-92	23-Jan-92	1,630	100	•						<0.005
TP14-8	21-Jan-92			80 <10	680 <50	NA NA		<0.005 <0.005			<0.005
TP14-12	21-Jan-92	23-Jan-92	<50	< +U	\ 00	NA	. 10	·0.003	~0.003	\U.UU3	0.003
TP15-4	21-Jan-92	23-Jan-92	<50	<10	<50	NA	<10	<0.005	<0.005	<0.005	<0.005
TP15-7.5	21-Jan-92		<50	<10		NA		<0.005			<0.005
TP15-12	21-Jan-92	23-Jan-92	<50	<10		NA					<0.005
	,,,			•							

TABLE 3

ANALYTICAL RESULTS OF SOIL SAMPLES COLLECTED FROM
TEST PITS AND SOIL BORINGS
(concentrations in parts per million [ppm])

______ Total Lab Analysis Recoverable Ethyl-Total Date Sampled Return Date Hydrocarbons Diesel Oil O/G Gasoline Benzene Toluene benzene Xylenes Sample ID 240 <10 <0.005 <0.005 <0.005 <0.005 31-Jan-92 03-Feb-92 <50 40 NA TP16-14 <0.005 <0.005 <10 <0.005 <0.005 04-Feb-92 06-Feb-92 <50 <10 <50 NA TP17-12 <0.005 <0.005 <10 <0.005 <0.005 130* 800 TP18-3.5 04-Feb-92 06-Feb-92 2,650 NA <10 <0.005 <0.005 <0.005 <0.005 160*)4-Feb-92 06-Feb-92 2,000 1,300 NA TP18-8 <0.005 <0.005 <0.005 <0.005 06-Feb-92 <50 <10 <50 NA <10 TP19-4 04-Feb-92 06-Feb-92 <50 <10 <50 NA <10 <0.005 <0.005 <0.005 <0.005 TP20-4 04-Feb-92 PHASE II <10 08-Nov-91 18-Nov-91 NA <10 <50 NA NA NA NA NA SB1-4 <50 NA <10 NA NA NA 08-Nov-91 18-Nov-91 NA <10 NA SB1-8 18-Nov-91 <50 NA <10 NA NA SB1-12 08-Nov-91 NA <10 NA NA <50 <10 NA NA SB2-4 08-Nov-91 18-Nov-91 NA <10 NA NA NA 18-Nov-91 <10 <50 NA <10 NA NA NA NA SB2-8 08-Nov-91 NA <10 <50 <10 NA NA 08-Nov-91 18-Nov-91 NA NA NA NA SB2-12 <50 <10 <0.005 0.023 0.010 0.034 12-Nov-91 NA <10 NA 08-Nov-91 SB3-2 12-Nov-91 <10 <50 NA <10 <0.005 <0.005 <0.005 <0.005 08-Nov-91 ΝA SB3-6 08-Nov-91 12-Nov-91 MA <10 <50 NA <10 <0.005 <0.005 <0.005 <0.005 S83-10 <10 <50 <10 <0.005 0.009 <0.005 <0.005 08-Nov-91 12-Nov-91 NA NA SB4-2 <50 <10 <0.005 <0.005 <0.005 <0.005 08-Nov-91 12-Nov-91 <10 NA SB4-6 NA <10 <0.005 <0.005 <0.005 <0.005 12-Nov-91 <10 <50 NA NA \$84-10 08-Nov-91 <50 <10 <0.005 0.015 <0.005 <0.005 12-Nov-91 NA <10 NA SB5-2 08-Nov-91 <10 <50 <10 <0.005 < 0.005 <0.005 <0.005 SB5-6 08-Nov-91 12-Nov-91 NA NA <0.005 <0.005 <0.005 <0.005 <10 <50 <10 08-Nov-91 12-Nov-91 NA NA SB5-10 <10 <0.005 <0.005 <0.005 <50 0.007 SB6-2 08-Nov-91 12-Nov-91 NA <10 NA <0.005 <0.005 <0.005 <0.005 12-Nov-91 <10 <50 NA <10 SR6-6 08-Nov-91 NA <10 <50 <10 <0.005 <0.005 <0.005 <0.005 08-Nov-91 12-Nov-91 NA NA SB6-10 <0.005 <0.005 <0.005 0.015 18-Nov-91 NA <10 <50 NA <10 07-Nov-91 SB7-2 <10 <50 <10 0.080 <0.005 0.210 0.220 18-Nov-91 NA NA SB7-6 07-Nov-91 <0.005 0.031 0.150 <10 <0.005 <50 07-Nov-91 18-Nov-91 NA <10 NA SB7-10 <0.005 18-Nov-91 NA <10 <50 <10 <0.005 <0.005 <0.005 SB8-2 07-Nov-91 NA <10 <0.005 <0.005 <0.005 <0.005 07-Nov-91 18-Nov-91 NA <10 <50 NA SB8-6 <10 <50 NA <10 <0.005 <0.005 <0.005 <0.005 07-Nov-91 18-Nov-91 NA SB8-10 18-Nov-91 NA <10 <50 <10 <0.005 <0.005 <0.005 <0.005 SB9-2 07-Nov-91 NA <0.005 <0.005 <50 <10 <0.005 <0.005 SB9-6 07-Nov-91 18-Nov-91 NA <10 NA <0.005 <0.005 07-Nov-91 18-Nov-91 NA <10 <50 NA <10 <0.005 <0.005 SB9-10 <0.005 <0.005 <10 <0.005 <0.005 18-Nov-91 NA <10 <50 NA SB10-2 07-Nov-91 <0.005 <0.005 <0.005 <0.005 18-Nov-91 NA <10 <50 NA <10 SB10-6 07-Nov-91 <0.005 <0.005 07-Nov-91 18-Nov-91 NA <10 <50 NA <10 <0.005 <0.005 SB10-10

TABLE 3
ANALYTICAL RESULTS OF SOIL SAMPLES COLLECTED FROM
TEST PITS AND SOIL BORINGS

(concentrations in parts per million [ppm])

	Date	Lab Analysis	Total Recoverable							Ethyl-	Total
Sample ID	Sampled	Return Date	Hydrocarbons	Diesel	Oil	0/G	Gasoline	Benzene	Toluene	- 1	xylenes
SB12-4	08-Nov-91	12-Nov-91	NA.	<10	<50	NA	<10	0.006	<0.005	<0.00	<0.005
SB12-8	08-Nov-91	12-Nov-91	NA	<10	<50	NA	<10	<0.005	<0.005	<0.00	<0.005
SB12-12	08-Nov-91	12-Nov-91	NA	<10	<50	NA	<10	<0.005	<0.005	<0.00	<0.005
SB14-4	08-Nov-91	12-Nov-91	NA	21	<50	NA	<10	<0.005	<0.005	<0.00	5 0.015
SB14-8	08-Nov-91	12-Nov-91	NA	25.9	<50	NA	41.0	2.400	0.530	1	1 7
SB14-12	08-Nov-91	12-Nov-91	NA	<10	<50	NA	<10	0.230	0.036	2.4	0.70
Test pits e	xcavated by A	iqua Resources:		-							
TP-J-1	26-Jul-91	02-Aug-91	NA	NA	NA	NA	60	0.130	0.034	1.4	2.80
TP-J-2	26-Jul-91	02-Aug-91	NA	NA	NA	NA	270	0.82	<0.080	3.6	2.50
TP-J-3	26-Jul-91	02-Aug-91	NA	NA	NA	NA	640	3.30	8.80	17.	76.0
TP-J-4	30-Jul -91	06-Aug-91	NA	4.4	NA	72	<1	<0.005	<0.005	<0.00	<0.005
TP-J-5	30-Jul-91	06-Aug-91	NA	9.6	NA	410	29	0.076	<0.010	0.03	4 0.043
TP-J-6	30-Jul-91	06-Aug-91	NA	500	NA	330	11000	9.50	<4.0	180.	780.0
TP-J-7	30-Jul-91	06-Aug-91	NA	<1	NA	<50	1.6	<0.005	<0.005	<0.00	5 0.0091
TP-J-8	30-Jul-91	06-Aug-91	NA	<1	NA	<50	<1	<0.005	<0.005	<0,00	5 0.0061

NOTES:

* In diesel range not characteristic of diesel.

O/G - Oil and grease

NA - Not analyzed

Soil samples collected by Levine-Fricke were submitted to Precision Analytical Laboratory, Inc. of Richmond, California, for analysis of gasoline using Modified EPA Method 8015; BTEX compounds using EPA Method 8020; diesel and oil using EPA Method 8015; and total recoverable hydrocarbons using Standard Method 5520f.

Soil samples collected by Aqua Resources were submitted to Curtis & Tompkins, Ltd., of Berkeley, California, for analysis of gasoline and BTEX compounds using EPA Methods 5030/8020; diesel using Modified EPA Method 8015; and oil and grease using Standard Method 5520e and f.

TABLE 4

ANALYTICAL RESULTS OF FINAL VERIFICATION SOIL SAMPLES

COLLECTED FROM NORTHERN AREA EXCAVATION*

(results in parts per million [ppm])

amole	Sample Depth	Date	Laboratory Analysis	Total Recoverable	TP# as	TP# as	TPH as				Total
ID	(feet)	Sampled	Return Date		Oil	Diesel	Gasoline	Benzene	Toluene	Ethylbenzene	Xylenes
s-1	13	12/17/01	12/19/91	<50	<50	<10	<10	<0.005	<0.005	<0.005	<0.005
ร-เ ร-2	12	12/17/91 12/17/91	12/19/91	<50	<50	<10	<10	<0.005	<0.005	<0.005	<0.005
s-3	11	12/17/91	12/19/91	<50	<50	<10	<10	<0.005	<0.005	<0.005	<0.005
S-4	12	12/19/91	12/23/91	<50	<50	<10	<10	<0.005	<0.005	<0.005	0.021
S-5	12	12/19/91	12/23/91	<50	<50	<10	<10	<0.005	0.006	<0.005	0.008
IS-6	12	12/20/91	12/23/91	<50	<50	<10	<10	<0.005	<0.005	<0.005	<0.005
s-7	12	12/23/91	12/26/91	<50	<50	<10	<10	<0.005	<0.005	<0.005	<0.005
s-8	13	12/23/91	12/26/91	<50	<50	<10	<10	<0.005	<0.005	<0.005	<0.005
s-9	12.5	12/23/91	12/26/91	<50	<50	<10	<10	<0.005	<0.005	0.047	<0.005
S-10	13	12/26/91	12/30/91	<50	<50	<10	<10	<0.005	<0.005	<0.005	<0.005
s-11	13	12/26/91	12/30/91	<50	<50	<10	<10	<0.005	<0.005	<0.005	<0.00
S-12	14	12/26/91	12/30/91	<50	<50	<10	<10	<0.005	<0.005	<0.005	<0.00
IS-13	. 13	12/26/91	12/30/91	<50	<50	<10	<10	<0.005	<0.005	<0.005	<0.00
s-14	11.5	12/27/91	12/31/91	<50	<50	<10	<10	<0.005	0.006	<0.005	0.00
s-15	12	12/27/91	12/31/91	<50	<50	<10	<10	<0.005	0.006	<0.005	0.00
s-16	12.5	01/03/92	01/06/92	<50	<50	<10	<10	0.006	<0.005	0.007	<0.00!
s-17	12	01/03/92	01/06/92	<50	<50	<10	<10	<0.005	<0.005	<0.005	<0.00
s-18	13	01/10/92	01/14/92	<50	<50	<10	<10	<0.005	<0.005	<0.005	<0.00
S-19	12.5	01/10/92	01/14/92	<50	<50	<10	<10	<0.005	<0.005	<0.005	<0.00
S-20	13	01/14/92	01/17/92	<50	<50	<10	<10	<0.005	<0.005	<0.005	<0.00
IS-21	13	01/14/92	01/17/92	<50	<50	<10	<10	<0.005	<0.005	<0.005	<0.005
IS-22	12.5	01/15/92	01/17/92	<50	<50	<10	<10	<0.005	<0.005	<0.005	<0.005
s-23	12.5	01/16/92	01/20/92	<50	<50	<10	<10	<0.005	<0.005	<0.005	<0.00
s-24	13	01/17/92	01/20/92	<50	<50	<10	<10	<0.005	<0.005	<0.005	<0.00
S-25	11.5	01/20/92	01/22/92	<50	<50	<10	<10	<0.005	<0.005	<0.005	<0.00
s-26	13	01/21/92	01/23/92	<50	<50	<10	<10	0.013	<0.005	<0.005	0.010
S-30	12	01/23/92	01/24/92	<50	<50	<10	<10	<0.005	<0.005	0.047	0.028
s-31	14	01/23/92	01/24/92	<50	<50	<10	<10	0.090	0.010	0.053	0.040
s-32	13	01/24/92	01/27/92	<50	<50	<10	<10 ·	<0.005	<0.005	<0.005	0.01

TABLE 4

ANALYTICAL RESULTS OF FINAL VERIFICATION SOIL SAMPLES

COLLECTED FROM NORTHERN AREA EXCAVATION*

(results in parts per million [ppm])

	Sample		Laboratory	Total	TPH	TPH	TPH				Total
ampte ID	Depth (feet)	Date Sampled	Analysis Return Date	Recoverable Hydrocarbons	as Oil	as Diesel	as Gasoline	Benzene	Toluene	Ethylbenzene	Xyl en es
			00/44/00				-40	-A 00¢	<0.005	<0.085	<0.005
s-33	11	02/07/92	02/11/92	<50	<50	<10	<10	<0.005			
S-34	11	02/07/92	02/11/92	<50 -50	<50 -50	<10	<10	<0.005	<0.005	<0.005	<0.005
s-35	9	02/14/92	02/19/92	<50 .50	<50	<10	<10	<0.005	<0.005	<0.005	<0.005
s-36	8	03/03/92	03/05/92	<50	<50	<10	<10	<0.005	<0.005	<0.005	<0.005
s-37	11	03/03/92	03/05/92	<50	<50	<10	<10	<0.005	<0.005	<0.005	<0.005
W-1	8	12/17/91	12/19/91	<50	<50	<10	<10	<0.005	<0.005	<0.005	<0.005
W-2	8	12/17/91	12/19/91	<50	<50	<10	<10	<0.005	<0.005	<0.005	<0.005
W-3	8.5	12/19/91	12/23/91	<50	<50	<10	<10	<0.005	0.005	<0.005	0.007
W-5	9	12/20/91	12/23/91	<50	<50	<10	<10	<0.005	<0.005	<0.005	<0.005
W-6	8	12/20/91	12/23/91	<50	<50	<10	<10	<0.005	<0.005	<0.005	<0.005
W-7	8	12/20/91	12/23/91	<\$0	<50	<10	<10	<0.005	<0.005	<0.005	<0.005
₩-8	9	12/20/91	12/23/91	<50	<50	<10	<10	<0.005	<0.005	<0.005	<0.005
W-9	10	12/20/91	12/23/91	<\$0	<50	<10	<10	<0.005	<0.005	<0.005	<0.005
W-10	9	12/23/91	12/26/91	<50	<50	<10	<10	<0.005	<0.005	<0.005	<0.005
W-11	8	12/23/91	12/26/91	<50	<50	<10	<10	<0.005	<0.005	<0.005	<0.005
W-15	8.5	01/10/92	01/14/92	<50	<50	<10	<10	<0.005	<0.005	<0.005	<0.005
W-16	11	01/14/92	01/17/92	<50	<50	<10	<10	0.120>	0.008	0.10	(0.075
W-17	11	01/15/92	01/17/92	<50	<50	<10	<10	<0.005	<0.005	<0.005	<0.005
W-18	12	01/15/92	01/17/92	<50	<50	<10	<10	<0.005	<0.005	<0.005	<0.005
¥-19	11	01/16/92	01/20/92	[*] <50	<50	<10	<10	<0.005	<0.005	<0.005	<0.005
W-20	11	01/16/92	01/20/92	<50	<50	<10	<10	<0.005	<0.005	<0.005	<0.005
W-21	9	01/17/92	01/20/92	<50	<50	<10	<10	<0.005	0.006	<0.005	<0.005
₩-22	10	01/17/92	01/20/92	<50	<50	<10	<10	<0.005	<0.005	<0.005	<0.005
W-24	9	01/20/92	01/23/92	<50	<50	<10	<10	<0.005	<0.005	<0.005	<0.005
W-25	10	01/20/92	01/23/92	<50	<50	<10	<10	<0.005	<0.005	<0.005	<0.005
W-26	9	01/20/92	01/23/92	<50	<50	<10	<10	<0.005	<0.005	<0.005	<0.005
W-28	10	01/21/92	01/23/92	50	<50	<10	<10	<0.005	<0.005	<0.005	<0.005
W-36	9	01/27/92	01/29/92	<50	<50	<10	<10	<0.005	<0.005	<0.005	<0.005
w-37	9	01/27/92	01/29/92	<50	<50	<10	<10	<0.005	<0.005	≤0. .0 05	<0.005
u-38	10	01/29/92	01/31/92	<50	<50	<10	(45)	0.70	<0.03	6.6	(14)

TABLE 4

ANALYTICAL RESULTS OF FINAL VERIFICATION SOIL SAMPLES

COLLECTED FROM NORTHERN AREA EXCAVATION*

(results in parts per million [ppm])

Cample.	Sample	Data.	Laboratory	Total	TPH	TPH	TPH				Total
ID	Depth (feet)	Date Sampled	Analysis Return Date	Recoverable Hydrocarbons	as Oil	as Diesel	as Gasoline	Benzene	Toluene	Ethylbenzene	Total Xylenes
sw-39	10	01/29/92	01/31/92	<50	<50	<10	<10	<0.005	<0.005	<0.005	<0.005
SW-40	10	01/29/92	01/31/92	<50	<50	<10	<10	<0.005	<0.005	<0.005	<0.005
SW-41	10	01/30/92	02/03/92	<50	<50	11	(90)	0.63	<0.03	(4)	(19)
SW-42	10	_01/30/92	02/03/92	<50	<50	<10	70	0.08	<0.03	2.4	(13)
SW-43	7.5	01/30/92	02/03/92	<50	<50	<10	<10	<0.005	<0.005	<0.005	<0.005
SW-46	10	02/07/92	02/11/92	<50	<50	<10	<10	(0.006)	<0.005	(0.061	0.123
SW-47	9	02/07/92	02/11/92	<50	<50	<10	<10	<0.005	<0.005	<0.005	0.006
SW-49	9	02/07/92	02/11/92	<50	<50	<10	<10	<0.005	<0.005	<0.005	0.007
sw-50	4	02/14/92	02/19/92	<50	<50	<10	<10	<0.005	<0.005	<0.005	<0.005
SW-51	4	02/14/92	02/19/92	<50	<50	<10	<10	<0.005	<0.005	<0.005	<0.005
sw-52	4	02/14/92	02/19/92	<50	<50	<10	<10	<0.005	<0.005	<0.005	<0.005
SW-53	4	03/03/92	03/05/92	<50	<50	<10	<10	<0.005	<0.005	<0.005	<0.005
SW-55	4	03/04/92	03/06/92	<50	<50	<10	<10	<0.005	<0.005	<0.005	<0.005
SW-56	4	03/05/92	03/06/92	<50	<50	<10	<10	<0.005	<0.005	<0.005	<0.005
SW-57	5	03/05/92	03/06/92	<50	<50	<10	<10	<0.005	<0.005	<0.005	<0.005

^{*} All samples analyzed by Precision Analytical Laboratories Inc. of Richmond, California. Samples were analyzed for total petroleum hydrocarbons (TPH) as oil, diesel, and gasoline using Modified EPA Method 8015; benzene, toluene, ethylbenzene, and xylene using Modified EPA Method 8020; and total hydrocarbons using Standard Method 5520f, 17th Edition.

TABLE 5 ANALYTICAL RESULTS OF CHARACTERIZATION SOIL SAMPLES COLLECTED FROM SOILS STOCKPILED BY AQUA RESOURCES INC. EMERYVILLE, CALIFORNIA
(all data in parts per million [ppm])

Sample ID	Date Sampled	Lab analysis return date	TPH	Diesel	0i l	O/G	Gasoline	Benzene	Toluene	Ethylbenzene	Tota Xylene
P1-1	15-0ct-91	17-0ct-91	NA	<10	180	NA	<10	NA	NA	NA	N.
P2-1	15-0ct-91	17-0ct-91	NA	<10	80	NA	<10	NA	NA	NA	N
P3-1	15-0ct-91	17-0ct-91	NA	<10	576	NA		NA	NA	NA	N
P3-2	23-0ct-91	28-0ct-91	NA	17	320	NA	<10	NA	NA	NA	N
P3-3	23-0ct-91	28-0ct-91	NA	13	690	17,000	<10	NA	NA	NA	N
P4-1	15-0ct-91	17-0ct-91	NA	<10	560	NA		NA	NA	NA	
P4-2	17-0ct-91	21-0ct-91	NA	<10	590	NA	<10	NA	NA	NA NA	ı
P4-3	17-0ct-91	21-0ct-91	NA	<10	1100	NA	<10	NA	NA	NA	
P4-4	23-0ct-91	28-Oct-91	NA	<10	255	NA	<10	NA	NA	NA	•
P4-5	23-0ct-91	28-0ct-91	NA	11	160	NA	<10	NA	NA	NA	1
SP4-6	23-0ct-91	28-0ct-91	NA	10	260	NA	<10	NA	NA	NA	I
SP4-7	23-0ct-91	28-0ct-91	NA	<10	170	NA	<10	NA	NA	NA	ı
P4-8	23-Oct-91	28-Oct-91	NA	<10	210	NA	<10	NA	NA	NA	1
P4-9	23-0ct-91	28-Oct-91	NA	<10	175	NA	<10	NA	NA	NA	I
P4-10	23-0ct-91	28-Oct-91	NA	<10	220	NA		NA	NA	NA	I
P4-11	23-0ct-91	28-0ct-91	NA	<10	130	NA		NA	NA	NA	
P4-12	23-0ct-91	28-0ct-91	NA.	<10	180	NA		NA	NA	NA	
P4-13	23-Oct-91	28-0ct-91	NA	<10	320	NA		NA	NA	NA	
P4-14	23-0ct-91	29-0ct-91	NA.	<10	<50	NA		NA	NA	NA	
P4-15	23-0ct-91	29-0ct-91	NA.	<10	55	NA		NA	NA	NA	
P4-16	23-0ct-91	29-0ct-91	NA NA	10	70	NA		<0.005	<0.005	<0.005	0.0
P4-17	23-0ct-91	29-0ct-91	NA NA	16	<50	NA NA		NA	NA.	NA NA	1
P4-18	23-0ct-91	29-0ct-91	NA NA	<10	<50	NA NA		NA.	NA.	NA NA	
6P4-19	23-0ct-91	29-0ct-91	NA NA	<10	50	NA		NA.	NA.	NA	
P4-20	23-0ct-91	31-0ct-91	NA NA	<10	<50	NA		NA	NA NA	NA	i
P4-21	23-0ct-91	31-0ct-91	NA NA	<10	71	NA		NA	NA.	NA NA	j
P4-22	23-0ct-91	31-0ct-91	NA NA	<10	<50	NA		NA.	NA.	NA NA	
P4-23	23-0ct-91	31-0ct-91	NA NA	<10	<50	NA		NA NA	NA NA	NA NA	
3P4-23 3P4-24				<10	<50	NA NA		NA NA	NA NA	NA NA	
P4-25	23-0ct-91 23-0ct-91	31-0ct-91	NA NA	<10	<50	NA NA		NA NA	NA	NA NA	
3P4-25	23-0ct-91	31-0ct-91 31-0ct-91	NA NA	<10	<50	NA NA		NA NA	NA NA	NA NA	
			NA NA	<10	<50	NA NA		NA NA	NA NA	NA NA	
P4-27	23-0ct-91	31-Oct-91		<10	<50	NA NA		NA NA	NA NA	NA NA	
P4-28	23-0ct-91	31-0ct-91	ŅĄ	<10	<50			NA NA	NA NA	NA NA	
P4-29	23-0ct-91	31-0ct-91	NA	<10		NA		NA NA	NA NA	NA NA	
P4-30	23-0ct-91	31-0ct-91	NA		<50	NA					
P4-31	23-0ct-91	31-0ct-91	NA	<10	<50 -50	NA		NA.	NA.	NA NA	
P4-32	23-0ct-91	31-0ct-91	NA	<10	< 50	NA		NA	NA	NA NA	
P4-33	23-0ct-91	31-0ct-91	NA	<10	<50	NA		NA NA	NA.	NA NA	
P4-34	23-0ct-91	31-0ct-91	NA	<10	<50	NA		NA	NA.	NA NA	
P4-35	23-0ct-91	31-0ct-91	NA	<10	<50	NA		NA	NA.	NA.	
P4-36	23-0ct-91	30-0ct-91	NA	<10	<50	NA		NA	NA.	NA NA	
SP4-37	23-0ct-91	30-0ct-91	NA	<10	73	NA		NA 10. OOF	NA O OOE	-0.00E	0.0
SP4-38	23-0ct-91	30-0ct-91	NA	10	60	NA		<0.005	<0.005	<0.005	0.0
P4-39	23-0ct-91	30-0ct-91	NA	<10	70	NA		NA	NA	NA	
P4-40	23-0ct-91	30-0ct-91	NA	<10	<50	NA	<10	NA	NA	NA	

TABLE 5 ANALYTICAL RESULTS OF CHARACTERIZATION SOIL SAMPLES COLLECTED FROM SOILS STOCKPILED BY AQUA RESOURCES INC. EMERYVILLE, CALIFORNIA (all data in parts per million [ppm])

Total Xylenes	Ethylbenzene	Toluene	Benzene	Gasoline	0/G	Oil	Diesel	TPH	Lab analysis return date	Date Sampled	Sample ID
N/	NA	NA	NA	<10	NA.	<50	<10	NA	30-0ct-91	23-Oct-91	SP4-41
N/	NA	NA	NA	<10	NA	<50	<10	NA	30-0ct-91	23-0ct-91	SP4-42
N/	NA	NA	NA	<10	NA	80	10	NA	30-Oct-91	23-0ct-91	P4-43
N/	NA	NA	NA	<10	NA	60	10.5	NA	30-0ct-91	23-0ct-91	P4-44
N/	NA	NA	NA	<10	NA	70	<10	NA	30-0ct-91	23-0ct-91	P4-45
N/	NA	NA	NA	<10	NA	<50	<10	NA	30-0ct-91	23-0ct-91	P4-46
N/	NA	NA	NA	<10	NA	<50	<10	NA	30-Oct-91	23-0ct-91	P4-47
N/	NA	NA	NA	<10	NA	60	10	NA	30-0ct-91	23-0ct-91	P4-48
N/	NA	NA	NA	<10	NA	<50	<10	NA	30-Oct-91	23-0ct-91	SP4-49
N/	NA	NA	NA	<10	NA	60	<10	NA	30-0ct-91	23-0ct-91	P4-50
0.034	0.006	0.012	<0.005	1.3	NA	NA	NA	NA	15-Nov-91	07-Nov-91	SP4-51
0.024	<0.005	0.006	<0.005	3.5	NA	NA	NA	NA	15-Nov-91	07-Nov-91	SP4-52
N/	NA	NA	NA	<10	NA	51	<10	NA	17-0ct-91	15-0ct-91	SP5-1
N/	NA	NA	NA	<10	NA	110	<10	NA	17-0ct-91	15-0ct-91	SP6-1
N	NA	NA	NA	<10	NA	100	<10	NA	17-0ct-91	15-0ct-91	SP7-1
N	NA	NA	NA	<10	NA	130	<10	NA	17-0ct-91	15-0ct-91	SP8-1
N	NA	NA	NA	<10	NA	80	<10	NA	17-0ct-91	15-0ct-91	SP8-2
N/	NA	NA	NA	<10	NA	480	<10	NA	17-0ct-91	15-0ct-91	SP9-1
N.	NA	NA	NA	<10	NA	360	<10	NA	17-0ct-91	15-0ct-91	SP9-2
N/	NA	NA	NA	<10	NA	80	<10	NA	28-0ct-91	23-0ct-91	P9-1
N/	NA	NA	NA	<10	NA	10	<10	NA	28-Oct-91	23-0ct-91	SP9-2
N/	NA	NA	NA	<10	NA	270	<10	NA	28-0ct-91	23-0ct-91	P9-3
N/	NA	NA	NA	<10	NA	110	<10	NA	28-0ct-91	23-0ct-91	P9-4
N/	NA	NA	NA	<10	NA	200	<10	NA	28-0ct-91	23-0ct-91	SP9-5
N/	NA	NA	NА	<10	NA	<50	<10	NA	28-0ct-91	23-0ct-91	SP9-6
N/	NA	NA	NA	<10	NA	<50	<10	NA	28-0ct-91	23-0ct-91	P9-7
N/	NA	NA	МA	<10	NA	230	<10	NA	28-0ct-91	23-0ct-91	P9-8
N/	NA	NA	NA	<10	NA	140	<10	NA	28-0ct-91	23-0ct-91	P9-9
N/	NA	NA	NA	<10	NA	130	<10	NA	28-0ct-91	23-0ct-91	P9-10
N/	NA	NA	NA	<10	NA	215	<10	NA	28-0ct-91	23-0ct-91	P9-11
N/	NA	NA	NA	<10	NA	260	<10	NA	28-Oct-91	23-0ct-91	P9-12
N/	NA	NA	NA	<10	NA	85	<10	NA	28-Oct-91	23-Oct-91	P9-13
N/	NA	NA	NA	<10	NA	160	<10	NA	28-0ct-91	23-0ct-91	P9-14
N/	NA	NA	NA	<10	NA	110	<10	NA	28-0ct-91	23-0ct-91	P9-15
N/	NA	NA	NA	<10	NA	80	<10	NA	28-Oct-91	23-Oct-91	P9-16
N/	NA	NA	NA	<10	NA	225	<10	NA	28-0ct-91	23-Oct-91	P9-17
N/	NA	NA	NÀ	<10	NA	125	<10	NA	28-Oct-91	23-Oct-91	P9-18
N/	NA	NA	NA	<10	NA	60	<10	NA	28-0ct-91	23-0ct-91	P9-19
N/	₩A	NA	NA	<10	NA	<50	<10	NA	28-0ct-91	23-0ct-91	P9-20
N/	NA	NA	NA NA	<10	NA	66	~10	NA	28-0ct-91	23-0ct-91	P9-21
N/	NA	NA	NA	<10	NA	276	<10	NA	28-0ct-91	23-0ct-91	P9-22
N/	NA	NA	NA	<10	NA	<50	<10	NA	28-0ct-91	23-0ct-91	SP9-23
N/	NA	NA	NA	<10	NA	88	<10	NA	28-Oct-91	23-0ct-91	SP9-24

TABLE 5
ANALYTICAL RESULTS OF CHARACTERIZATION SOIL SAMPLES
COLLECTED FROM SOILS STOCKPILED BY AQUA RESOURCES INC.
EMERYVILLE, CALIFORNIA
(all data in parts per million [ppm])

Sample ID	Date Sampled	Lab analysis	ТРН		Oil			Benzene		Ethylbenzene	Tot
	Sampled	return date		Diesel		0/G	Gasoline	Benzene	Totuene	Ethytbenzene	Xylen
P10-1	15-0ct-91	17-0ct-91	NA	<10	<50	NA	18	NA	NA	NA	
P10-2	15-0ct-91	17-0ct-91	NA	<10	<50	NA	<10	NA	NA	NA	
P10-3	15-0ct-91	17-0ct-91	NA	<10	<50	NA	<10	NA	NA	NA	
10-4	15-0ct-91	17-0ct-91	NA	<10	<50	NA	<10	NA	NA	NA	
10-5	15-0ct-91	17-0ct-91	NA	<10	<50	NA.	<10	NA.	NA	NA NA	
10-6	07-Nov-91	15-Nov-91	255	<10	<50	595	1.1	<0.005	0.011	<0.005	0.8
10-7	07-Nov-91	15-Nov-91	220	<10	<50	445	<1.0	<0.005	0.010	<0.005	0.0
10-8	07-Nov-91	15-Nov-91	1190	<10	<50	2570	6.5	<0.005	0.019	0.010	0.0
10-9	07-Nov-91	15-Nov-91	<50	<10	<50	<50	<1.0	<0.005	0.005	<0.005	0.6
11-1	16-0ct-91	18-0ct-91	NA	40	170	NA	<10	NA	NA	NA	
12-1	16-0ct-91	18-0ct-91	NA	430	2500	NA	<10				
12-2	24-0ct-91	11-Nov-91	NA	72	113	NA	<10	NA	NA	NA	
12-3	24-0ct-91	11-Nov-91	NA	53	134	NA	<10	NA	NA	NA	
12-4	24-0ct-91	11-Nov-91	NA	43.5	231	NA	<10	NA	NA	NA	
12-5	24-0ct-91	11-Nov-91	NA	22.9	89	NA	<10	NA	NA	NA	
12-6	24-Oct-91	11-Nov-91	NA	2000	1430	16,300	<10	NA	NA	NA	
12-7	24-0ct-91	11-Nov-91	NA	36.9	96.6	NA	<10	NA	NA	NA	
13-1	16-0ct-91	18-0ct-91	NA	19	880	NA	<10	NA	NA	NA	
13-2	25-0ct-91	14-0ct-91	NA	<10	<50	NA	<10	NA	NA	NA	
13-3	25-0ct-91	14-0ct-91	NA	<10	<50	NA	<10	NA	NA	NA	
13-4	25-0ct-91	14-0ct-91	NA	<10	93	NA	<10	NA	NA	NA	
13-5	25-0ct-91	14-0ct-91	NA	13	113	NA	<10	NA	NA	NA	
13-6	25-Oct-91	14-0ct-91	NA	<10	77	NA	<10	NA	NA	NA	
13-7	25-Oct-91	14-0ct-91	NA.	13.5	134	NA.	<10	NA	NA	NA	
13-8	25-0ct-91	14-0ct-91	NA.	<10	70	NA	<10	NA	NA	NA	
13-9	25-0ct-91	14-0ct-91	NA NA	<10	<50	NA NA	<10	NA	NA.	NA NA	
13-10	25-0ct-91	14-0ct-91	NA NA	<10	<50	NA NA	<10	NA NA	NA NA	NA NA	
13-11	25-0ct-91	14-0ct -91	NA NA	<10	<50	NA NA	<10	NA NA	NA NA	NA	
13-12	25-0ct-91	14-0ct 91	NA NA	13.7	104	NA	<10	NA NA	NA NA	NA NA	
13-12	25-0ct-91	14-0ct-91	NA NA	<10	56	NA NA	<10	NA NA	NA NA	NA NA	
13-14	25-0ct-91	14-0ct-91	NA NA	26	185	NA NA	<10	NA NA	NA NA	NA NA	
13-14 47-15								NA NA	NA NA	NA NA	
13-15 13-16	25-0ct-91 25-0ct-91	14-0ct-91 14-0ct-91	NA NA	22.8 <10	237 <50	na Na	<10	NA NA	NA NA	NA NA	
14-1	16-0ct-91	18-0ct-91	NA	<10	90	NA	<10	NA	NA	NA	
15-1	16-0ct-91	18-0ct-91	NA	<10	<50	NA	<10	NA	NA	NA	
15-2	16-0ct-91	18-0ct-91	NA	<10	<50	NA	<10	NA	NA	NA	
16-1D,2D,3	16-0ct-91	18-0ct-91	NA	<10	<50	NA	<10	NA	NA	NA	
16-4D,5D,6		18-Oct-91	NA	17	100	NA	17	NA	NA	NA	
16-70.80 9	16-0ct-91	18-0ct-91	NA	<10	<50	NA	<10	NA	NA	NA	
16-9D	18-0ct-91	21-0ct-91	NA	60	150	NA	390	NA	NA	NA	
16-10D	18-0ct-91	21-0ct-91	NA	<10	<50	NA	<10	NA	NA	NA	
16-11	25-Oct-91	11-Nov-91	NA.	<10	<50	NA	<10	NA	NA	NA.	

TABLE 5 ANALYTICAL RESULTS OF CHARACTERIZATION SOIL SAMPLES COLLECTED FROM SOILS STOCKPILED BY AQUA RESOURCES INC. EMERYVILLE, CALIFORNIA (all data in parts per million [ppm])

Tota Xylene	Ethylbenzene	Toluene	Benzene	Gasoline	O/G	oil	Dieset	TPH	Lab analysis return date	Date Sampled	Sample ID
0.01	<0.005	0.008	<0.005	<10	NA.	<50	<10	NA NA	11-Nov-97	25-0ct-91	SP16-12
N.	NA	NA.	NA	<10	NA	<50	<10	NA	11-Nov-91	25-0ct-91	SP16-13
N,	NA	NA.	NA.	<10	NA.	<50	<10	NA	11-Nov-91	25-0ct-91	SP16-14
N.	NA	NA.	NA	<10	NA	<50	<10	NA	11-Nov-91	25-Oct-91	SP16-15
N.	NA	NA	NA	<10	NA	537	40	NA	11-Nov-91	25-0ct-91	P16-16
N.	NA	NA	NA	<10	NA	73	<10	NA	11-Nov-91	25-0ct-91	SP16-17
N.	NA	NA	NA	<10	NA.	<50	<10	NA	11-Nov-91	25-0ct-91	SP16-18
N.	NA	NA	NA	<10	NA	65	<10	NA	11-Nov-91	25-0ct-91	P16-19
N.	NA	NA	NA NA	<10	NA	<50	<10	NA	11-Nov-91	25-0ct-91	P16-20
N.	NA	NA	NA.	<10	NA.	119	<10	NA.	11-Nov-91	25-0ct-91	P16-21
N	NA	NA	NA.	<10	NA	<50	<10	NA	11-Nov-91	25-0ct-91	P16-22
N.	NA	NA.	NA.	<10	NA.	116	<10	NA.	11-Nov-91	25-0ct-91	SP16-23
N.	KA	NA.	NA	<10	NA.	54	<10	NA	11-Nov-91	25-0ct-91	SP16-24
N.	NA	NA	NA	<10	NA	<50	<10	NA	11-Nov-91	25-0ct-91	SP16-25
N	NA	NA.	NA	<10	NA.	<50	<10	NA.	11-Nov-91	25-Oct-91	P16-26
N.	NA	NA	NA	<10	NA	<50	<10	NA	12-Nov-91	25-0ct-91	SP16-27
Ñ.	NA.	NA.	NA.	<10	NA NA	<50	<10	NA	12-Nov-91	25-0ct-91	SP16-28
N.	NA	NA	NA	<10	5680	245	<10	NA.	12-Nov-91	25-0ct-91	P16-29
N.	NA NA	NA	NA NA	<10	NA	68	<10	NA.	12-Nov-91	25-0ct-91	P16-30
0.00	<0.005	<0.005	<0.005	<10	NA NA	71	<10	NA	12-Nov-91	25-0ct-91	P16-31
N.	NA	NA.	NA	<10	NA	<50	<10	NA	12-Nov-91	25-0ct-91	P16-32
N.	NA.	NA.	NA	<10	NA NA	<50	<10	NA.	12-Nov-91	25-0ct-91	P16-33
N	NA NA	NA.	NA	<10	NA NA	190	11.8	NA	12-Nov-91	25-Oct-91	P16-34
N	NA.	NA.	NA	<10	NA NA	<50	<10	NA.	12-Nov-91	25-0ct-91	P16-35
N.	NA.	NA	NA	<10	NA NA	<50	<10	NA.	12-Nov-91	25-0ct-91	P16-36
N	NA.	NA	NA	<10	NA NA	<50	<10	NA	12-Nov-91	25-0ct-91	SP16-37
N	NA	NA.	NA.	<10	NA NA	<50	<10	NA.	12-Nov-91	25-0ct-91	P16-38
N	NA.	NA	NA	<10	NA.	102	<10	NA	12-Nov-91	25-0ct-91	SP16-39
N	NA	NA.	NA	<10	NA NA	<50	<10	NA.	12-Nov-91	25-0ct-91	SP16-40
Ň	NA	NA.	NA.	<10	NA	<50	<10	NA.	12-Nov-91	25-0ct-91	P16-41
N	NA	NA	NA.	<10	NA NA	<50	<10	NA	12-Nov-91	25-0ct-91	P16-42
N	NA	NA	NA.	<10	NA.	51	<10	NA.	14-Nov-91	25-Oct-91	P16-43
N	NA.	NA.	NA	<10	NA	<10	<10	NA.	14-Nov-91	25-0ct-91	P16-44
N	NA	NA.	NA	<10	NA.	<10	<10	, NA	14-Nov-91	25-0ct-91	P16-45
Ň	NA NA	NA.	NA NA	<10	NA.	<10	<10	, NA	14-Nov-91	25-0ct-91	P16-46
N.	NA	NA.	NA	<10	NA.	<10	<10	NA	14-Nov-91	25-0ct-91	P16-47
N	NA	NA.	NA.	<10	NA	<10	<10	NA	14-Nov-91	25-Oct-91	P16-48
N.	NA NA	NA.	NA.	<10	NA.	<10	<10	NA NA	14-Nov-91	25-0ct-91	P16-49
N	NA	NA.	NA.	45	NA.	<10	<10	NA	14-Nov-91	25-0ct-91	P16-50
0.02	<0.005	0.011	0.006	<1.0	NA NA	NA	NA	NA	15-Nov-91	07-Nov-91	P16-51
0.08	0.012	0.024	0.009	1.1	NA	NA	NA NA	NA NA	15-Nov-91	07-Nov-91	P16-52
N.	NA	NA.	NA	<10	NA	130	<10	NA	17-0ct-91	15-0ct-91	P17-1
N	NA	NA.	NA.	<10	NA.	1260	100				
N:	MM	NA.	NA.	<10	NA NA	239		NA NA	21-0ct-91	18-0ct-91	P18-1
							37.2	,	11-Nov-91	24-0ct-91	SP18-2
N.	NA	NA	NA	<10	NA	<50	<10	NA	18-0ct-91	16-0ct-91	P19-1
N.	NA	NA	NA	<10	NA	<50	<10	NA	18-0ct-91	16-0ct-91	SP19-2

TABLE 5
ANALYTICAL RESULTS OF CHARACTERIZATION SOIL SAMPLES
COLLECTED FROM SOILS STOCKPILED BY AQUA RESOURCES INC.
EMERYVILLE, CALIFORNIA
(all data in parts per million [ppm])

==== = ==		=======			======		=======	======			
Tota Xylene:	Ethylbenzene	Toluene	Benzene	Gasoline	0/G	0i l	Diesel	TPH	Lab analysis return date	Date Sampled	Sample ID
N/	NA	NA	NA NA	<10	NA	<50	<10	NA	18-0ct-91	16-0ct-91	SP19-3
N/	NA	NA	NA	<10	NA	<50	<10	NA	18-0ct-91	16-0ct-91	SP19-4
0.045	0.007	0.012	<0.005	2.0	200	NA	NA	150	15-Nov-91	07-Nov-91	SP19-5
0.02	<0.005	0.008	<0.005		265	NA	NA	245	15-Nov-91	07-Nov-91	SP19-6
N.	NA	NA	NA	<10	NA	110	<10	NA	18-0ct-91	16-0ct-91	SP20-1D,3D c
N.	NA	NA	NA	<10	NA	1230	<10	NA	21-0ct-91	18-0ct-91	SP20-2D
N:	NA	NA	NA	<10	NA	300	<10	NA	18-0ct-91	16-0ct-91	SP20-4D,5D c
N.	NA	NA	NA		NA	560	12	NA	21-0ct-91	18-0ct-91	SP20-6D
Na	NA	NA	NA		NA	810	<10	NA	21-0ct-91	18-0ct-91	SP20-7D
N.	NA	NA	NA	15	NA	300	<10	NA	21-0ct-91	18-0ct-91	SP20-8D
N/	NA	NA	NA	<10	NA	51	<10	NA	21-0ct-91	18-0ct-91	SP20-9D
N.	NA	NA	NA	<10	NA	<10	<10	NA	01-Nov-91	24-0ct-91	SP20-10
N	NA	NA	NA	<10	NA	<10	<10	NA	01-Nov-91	24-0ct-91	SP20-11
N.	NA	NA	NA	<10	NA	<10	<10	NA	01-Nov-91	24-0ct-91	SP20-12
N.	NA	NA	NA	<10	NA	<10	<10	NA	01-Nov-91	24-0ct-91	SP20-13
N.	NA	NA	NA	<10	NA	<10	<10	NA	01-Nov-91	24-0ct-91	SP20-14
N.	NA	NA	NA	<10	NA	<10	<10	NA	01-Nov-91	24-0ct-91	SP20-15
N.	NA	NA	NA	<10	NA	<10	<10	NA	01-Nov-91	24-0ct-91	SP20-16
N.	NA	NA	NA	<10	NA	<10	<10	NA	01-Nov-91	24-0ct-91	SP20-17
N.	NA	NA	NA		NA	<10	<10	NA	01-Nov-91	24-0ct-91	SP20-18
N.	₩A	NA	RA		NA	<10	<10	NA	01-Nov-91	24-0ct-91	SP20-19
N.	NA	NA	NA		NA	<10	<10	NА	01-Nov-91	24-0ct-91	SP20-20
N.	NA	NA	NA		NA	<10	<10	NA	01-Nov-91	24-0ct-91	SP20-21
N.	NA	NA	RA		NA	<10	<10	NA	01-Nov-91	24-0ct-91	SP20-22
N.	NA	NA	KA		NA	<10	<10	NA	01-Nov-91	24-0ct-91	SP20-23
N.	NA	NA	KA	<10	NA	<10	<10	₩A	01-Nov-91	24-0ct-91	SP20-24
N/	NA	NA	NA		NA	<50	<10	НA	01-Nov-91	24-0ct-91	SP20-25
N.	NA	NA	NA	<10	NA	<50	<10	NA	04-Nov-91	24-0ct-91	SP20-26
0.01	<0.005	<0.005	<0.005		NA	<50	<10	NA	04-Nov-91	24-0ct-91	SP20-27
N.	NA	NA	NA.	<10	NA	<50	<10	NA	04-Nov-91	24-0ct-91	SP20-28
N.	NA	NA	NA	<10	NA	<50	<10	NA	04-Nov-91	24-0ct-91	SP20-2 9
N.	NA	NA	NA		NA	<50	<10	NA	04-Nov-91	24-0ct-91	SP20-30
N/	NA	NA	NA	<10	NA	<50	<10	NA	04-Nov-91	24-0ct-91	SP20-31
N/	NA	NA	NA	<10	NA	<50	<10	NA	04-Nov-91	24-0ct-91	SP20-32
N/	NA	NA	NA		NA	<50	<10	NA	04-Nov-91	24-0ct-91	SP20-33
N/	NA	NA	NA	<10	NA	<50	<10	NA	04-Nov-91	24-0ct-91	SP20-34
N/	NA	NA	NA	<10	NA	<50	<10	NA	04-Nov-91	24-0ct-91	SP20-35
N	NA	NA	NA		NA	<50	<10	NA	04-Nov-91	24-0ct-91	SP20-36
N.	NA	NA	NA		NA	<50	<10	NA	04-Nov-91	24-0ct-91	SP20-37
N/	NA	NA	NA	<10	NA	<50	<10	NA	04-Nov-91	24-0ct-91	SP20-38
N	NA	NA	NA	<10	NA	<50	<10	NA	04-Nov-91	24-0ct-91	SP20-39
N	NA	NA	NA	<10	NA	<50	<10	NA	04-Nov-91	24-0ct-91	SP20-40
N/	NA.	NA	NA	<10	NA	<50	<10	NA	04-Nov-91	24-0ct-91	SP20-41
N/	NA	NA	NA	<10	NA	<50	<10	NA	05-Nov-91	24-0ct-91	SP20-42
0.00	<0.005	<0.005	<0.005		NA	<50	<10	NA	05-Nov-91	24-0ct-91	SP20-43
N/	NA	NA	NA		NA	<50	<10	NA	05-Nov-91	24-0ct-91	SP20-44
N/	NA	NA	NA		NA	<50	<10	NA	05-Nov-91	24-0ct-91	SP20-45
N/	NA.	NA	NA	<10	NA	<50	<10	NA	05-Nov-91	24-0ct-91	SP20-46

TABLE 5
ANALYTICAL RESULTS OF CHARACTERIZATION SOIL SAMPLES
COLLECTED FROM SOILS STOCKPILED BY AQUA RESOURCES INC.
EMERYVILLE, CALIFORNIA
(all data in parts per million [ppm])

Total Xylenes	Ethylbenzene	Toluene	Benzene	Gasoline	0/G	Oil	Diesel	TPH	Lab analysis return date	Date Sampled	Sample ID
N/	NA	NA.	NA		NA	<50	<10	NA	05-Nov-91	24-0ct-91	SP20-47
NA	NA	NA	NA		NA	<50	<10	NA	05-Nov-91	24-0ct-91	SP20-48
N#	NA NA	NA	NA		NA	<50	<10	NA	05-Nov-91	24-0ct-91	SP20-49
NA	NA NA	NA	NA		NA	<50	<10	NA	05-Nov-91	24-0ct-91	SP20-50
N/	NA	NA	NA		NA	<50	<10	NA	05-Nov-91	24-0ct-91	SP20-51
N <i>A</i>	NA	NA	NA		NA	<50	<10	NA	05-Nov-91	24-0ct-91	SP20-52
NA.	NA	NA	NA		NA	<50	<10	NA	05-Nov-91	24-0ct-91	SP20-53
N/	NA	NA	NA		NA	<50	<10	NA	05-Nov-91	24-0ct-91	SP20-54
NA.	NA	NA	ÑA		NA	<50	<10	NA	05-Nov-91	24-0ct-91	SP20-55
N/	NA	NA	NA		NA	<50	<10	NA	05-Nov-91	24-0ct-91	SP20-56
N/	NA NA	NA	NA		NA	<50	<10	NA	05-Nov-91	24-0ct-91	SP20-57
N/	NA	NA	NA		NA	305	13	NA	06-Nov-91	24-0ct-91	SP20-58
N/	NA	NA	NA		NA	280	16	NA	06-Nov-91	24-0ct-91	SP20-59
N/	NA	NA	NA	<10	NA	<50	<10	NA	06-Nov-91	24-0ct-91	SP20-60
N/	NA	NA	NA	<10	NA	86	<10	NA	06-Nov-91	24-0ct-91	SP20-61
N/	NA	NA	NA		NA	<50	<10	NA	06-Nov-91	24-0ct-91	SP20-62
N/	NA	NA	NA	<10	NA	91	<10	NA	06-Nov-91	24-0ct-91	SP20-63
N/	NA	NA	NA	<10	NA	<50	<10	NA	06-Nov-91	24-0ct-91	SP20-64
N/	NA	NA	NA	<10	NA	<50	<10	NA	06-Nov-91	24-0ct-91	SP20-65
N/	NA	NA	NA	<10	NA	83	10	NA	06-Nov-91	24-0ct-91	SP20-66
N/	NA	NA	NA	<10	NA	300	<10	NA	06-Nov-91	24-0ct-91	SP20-67
N/	NA	NA	NA	<10	NA	57	10	NA	06-Nov-91	24-0ct-91	SP20-68
N/	NA	NA	NA	<10	NA	150	<10	NA	06-Nov-91	24-0ct-91	SP20-69
N/	NA	NA	NA	<10	NA	90	<10	NA	06-Nov-91	24-0ct-91	SP20-70
N/	NA	NA	NA	<10	NA	<50	<10	NA	06-Nov-91	24-0ct-91	SP20-71
N/	NA	NA	NA	<10	NA	110	<10	NA	06-Nov-91	24-0ct-91	SP20-72
N/	NA	NA	NA	<10	NA	83	10	NA	06-Nov-91	24-0ct-91	SP20-73
N/	NA	NA	NA	<10	NA	115	<10	NA	07-Nov-91	24-0ct-91	SP20-74
N/	NA	NA	NA	<10	NA	50	<10	NA	07-Nov-91	24-0ct-91	SP20-75
N/	NA	NA	NA	<10	NA	84	<10	NA	07-Nov-91	24-0ct-91	SP20-76
N/	NA	NA	NA	<10	NA	<50	<10	NA	07-Nov-91	24-0ct-91	SP20-77
N/	NA	NA	NA	<10	NA	67	<10	NA	07-Nov-91	24-0ct-91	SP20-78
N/	NA	NA	NA	<10	NA	50	<10	NA	07-Nov-91	24-0ct-91	SP20-79
N/	NA.	NA	NA	<10	NA	130	<10	NA	07-Nov-91	24-0ct-91	SP20-80
N#	NA	NA	NA	<10	NA	<50	<10	NA	07-Nov-91	24-0ct-91	SP20-81
N/	NA	NA	NA	<10	NA	<50	1 9	NA	07-Nov-91	24-0ct-91	SP20-82
N/	NA	NA	NA	<10	NA	70	<10	NA	07-Nov-91	24-0ct-91	SP20-83
N/	NA	NA	NA	<10	NA	210	16	NA	07-Nov-91	24-0ct-91	SP20-84
N#	NA	NA	NA	<10	NA	120	16	NA	07-Nov-91	24-0ct-91	SP20-85
N/	NA	NA	NA	<10	NA	100	<10	NA	07-Nov-91	24-0ct-91	SP20-86
N/	NA	NA	NA	<10	NA	56	<10	NA	07-Nov-91	24-0ct-91	SP20-87
N/		NA	NA	<10	NA	225	<10	NA	07-Nov-91	24-0ct-91	SP20-88
N/	NA NA	NA	NA	<10	NA	90	<10	NA	07-Nov-91	24-0ct-91	SP20-89
N/	NA NA	NA	NA	<10	NA	94	<10	NA	08-Nov-91	24-0ct-91	SP20-90
N/		NA	NA		NA	<50	15	NA	08-Nov-91	24-0ct-91	SP20-91
N/	NA	NA	NA NA	<10	NA	<50	15.6	NA	08-Nov-91	24-0ct-91	SP20-92
N#	NA	NA	NA	<10	NA	<50	<10	NA	08-Nov-91	24-0ct-91	SP20-93
N/	NA	NA	NA	<10	NA	<50	12	NA	08-Nov-91	24-Oct-91	SP20-94
N/A	NA	NA	NA	<10	NA	229	15.9	NA	08-Nov-91	24-0ct-91	SP20-95

TABLE 5
ANALYTICAL RESULTS OF CHARACTERIZATION SOIL SAMPLES
COLLECTED FROM SOILS STOCKPILED BY AQUA RESOURCES INC.
EMERYVILLE, CALIFORNIA

(all data in parts per million [ppm])

Sample ID	Date Sampled	Lab analysis return date	TPH	Diesel	Oil	0/G	Gasoline	Benzene	Toluene	Ethylbenzene	Total Xylenes
sp20-96	24-0ct-91	08-Nov-91	NA.	19	93	NA	<10	NA	NA.	NA	NA
SP20-97	24-0ct-91	08-Nov-91	NA	11	90	NA		NA	NA	NA	NA
SP20-98	24-0ct-91	08-Nov-91	NA	<10	140	NA		NA	NA	NA	NA
SP20-99	24-0ct-91	08-Nov-91	NA	<10	71	HA		NA	NA	NA	NA
SP20-100	24-0ct-91	08-Nov-91	NA	<10	60	NA	<10	NA	NA	NA	NA
SP20-101	24-0ct-91	08-Nov-91	NA	<10	<50	NA		NA	NA	NA	NA
SP20-102	24-0ct-91	08-Nov-91	NA	11	86	NA		NA	NA	NA	NA
SP20-103	24-0ct-91	08-Nov-91	NA	<10	51	NA		NA	NA	NA	NA
SP20-104	24-0ct-91	08-Nov-91	NA	<10	<50	NA		NA	NA	NA	NA
SP20-105	24-0ct-91	08-Nov-91	NA	<10	<58	NA		HA	NA	NA	NA
SP20-106	24-0ct-91	12-Nov-91	NA	<10	56	NA		NA	NA	NA	NA
SP20-107	24-0ct-91	12-Nov-91	NA	<10	<50	NA		NA	NA	NA	NA
SP20-108	24-0ct-91	12-Nov-91	NA	13	84	NA		NA	NA	NA	NA
SP20-109	24-0ct-91	12-Nov-91	NA	<10	<50	NA		NA	NA	NA	NA
SP20-110	24-0ct-91	12-Nov-91	NA	<10	90	NA		NA	NA	NA NA	NA
SP20-111	24-0ct-91	12-Nov-91	NA	<10	<50	NA		NA	NA	NA	NA
SP20-112	24-0ct-91	12-Nov-91	NA	<10	<50	NA		NA	NA	NA	NA
SP20-113	24-0ct-91	12-Nov-91	NA	<10	<50	NA		NA	NA	NA	NA
SP20-114	24-0ct-91	12-Nov-91	NA	13.6	68	NA		NA	NA	NA	NA
SP20-115	24-0ct-91	12-Nov-91	NA	<10	<50	NA		NA	NA	NA	NA
SP20-116	24-0ct-91	12-Nov-91	NA	<10	<50	NA		NA	NA	NA	NA
SP20-117	24-0ct-91	12-Nov-91	NA	12.7	174	NA		NA	AA	na	NA
SP20-118	24-0ct-91	12-Nov-91	NA	<10	<50	NA		NA	NA	NA	NA
SP29-119	24-0ct-91	12-Nov-91	NA	10	131	NA		NA	NA	NA	NA
SP20-120	24-0ct-91	12-Nov-91	NA	<10	<50	NA		NA	NA	NA	NA
SP20-121	24-0ct-91	12-Nov-91	NA	<10	<50	NA		NA	NA	NA	NA
SP20-122	24-0ct-91	11-Nov-91	NA	<10	<50	NA		NA	NA	NA	NA
SP20-123	24-0ct-91	11-Nov-91	NA	<10	61	NA		NA	NA	NA	NA.
SP20-124	24-0ct-91	11-Nov-91	NA	<10	<50	NA		NA	NA	NA	NA
SP20-125	24-0ct-91	11-Nov-91	NA	<10	<50	NA		NA	NA	NA	NA
SP20-126	24-0ct-91	11-Nov-91	NA	12	145	NA		NA	NA	NA	NA
SP20-127	24-0ct-91	11-Nov-91	NA	<10	<50	NA		NA	NA	NA	NA
SP20-128	24-0ct-91	11-Nov-91	NA	<10	<50	NA		NA	NA	NA	NA
SP20-129	24-0ct-91	11-Nov-91	NA	<10	<50	NA		NA	NA	NA	NA
SP20-130	24-0ct-91	11-Nov-91	NA	<10	<50	HA		NA	NA	NA	NA
SP20-131	24-0ct-91	11-Nov-91	NA	<10	<50	NA		NA	NA	NA	NA.
SP20-132	24-0ct-91	11-Nov-91	NA	<10	<50	NA		NA	NA	NA	NA
SP20-133	24-0ct-91	11-Nov-91	NA	65	<50	NA		NA	NA	NA	NA
SP20-134	24-0ct-91	11-Nov-91	NA	<10	<50	NA		NA	NA	NA	NA
SP20-135	24-0ct-91	11-Nov-91	NA	<10	<50	NA		NA	NA	NA	NA 0.013
SP20-136	07-Nov-91	15-Nov-91	NA	NA	NA	NA		<0.005	0.006	<0.005	0.012
SP20-137	07-Nov-91	15-Nov-91	NA	NA	NA	NA	<1.0	<0.005	0.003	<0.005	0.012
SP21-1	16-0ct-91	18-0ct-91	NA	<10	<50	NA	<10	NA	NA	NA	NA

TABLE 5 ANALYTICAL RESULTS OF CHARACTERIZATION SOIL SAMPLES COLLECTED FROM SOILS STOCKPILED BY AQUA RESOURCES INC. EMERYVILLE, CALIFORNIA

(all data in parts per million [ppm])

Sample ID	Date Sampled	Lab analysis return date	TPH	Diesel	Oil	0/G	Gasoline	Benzene	Toluene	Ethylbenzene	Total Xylenes
SP22-1 SP22-2 SP22-3 SP22-4 SP22-5	16-0ct-91 16-0ct-91 25-0ct-91 25-0ct-91 25-0ct-91	18-0ct-91 18-0ct-91 14-Nov-91 14-Nov-91 14-Nov-91	NA NA NA NA	17 <10 <10 14 <10	280 110 <50 112 <50	NA NA NA NA	<10 <10 <10 <10 <10	NA NA NA NA NA	NA NA NA NA	NA NA NA NA	NA NA NA NA

NOTES:

O/G = Total oil and grease

TPH = Total petroleum hydrocarbons

NA = not analyzed

All samples analyzed by Precision Analytical Laboratories, Inc. of Richmond, California.

Analysis performed using Modified EPA Method 8015 for TPH as gasoline, diesel, oil; EPA Method 8020 for BTEX compounds; Standard Method 5520 for total oil and grease; and Standard Method, 16th Edition, 503E for total hydrocarbon analysis.

TABLE 6

ANALYTICAL RESULTS OF SOIL SAMPLES

COLLECTED FROM AERATION BEDS*

(results in parts per million [ppm])

Sample TPH TPH Laboratory TPH Sample Depth Date Analysis Total as as as 10 (inches) Sampled Return Date Oil Diesel Gasoline Benzene Toluene Ethylbenzene Xylenes SS-1-3A 6 05/20/92 05/21/92 <10 <0.005 <0.005 <0.005 0.008 <50 <10 SS-2-3A <10 <10 <0.005 <0.005 <0.005 0.040 6 05/20/92 05/21/92 <50 SS-3-1A 05/22/92 05/28/92 <50 <10 <10 <0.005 <0.005 <0.005 < 0.005 < 0.005 0.008 0.031 SS-4-2A 05/22/92 05/28/92 100 <10 <10 <0.005 SS-5-5A 05/22/92 05/28/92 <50 <10 <10 <0.005 <0.005 <0.005 <0.005 05/22/92 05/28/92 SS-6-4A <50 <10 13 0.045 <0.005 0.080 0.200 <0.005 05/22/92 05/28/92 0.020 0.090 0.110 SS-7-6A <50 <10 11 05/22/92 05/28/92 16 110 0.120 0.030 0.320 4.600 SS-8-7A <50 SS-9-1C 05/26/92 05/29/92 <50 <10 <10 <0.005 <0.005 <0.005 < 0.005 <10 <0.005 < 0.005 <0.005 <0.005 SS-10-1B 05/26/92 05/29/92 <50 <10 05/26/92 05/29/92 <10 <10 < 0.005 <0.005 <0.005 < 0.005 SS-11-2C <50 0.006 <0.005 <0.005 0.006 SS-12-2B 05/26/92 05/29/92 <50 <10 <10 ss-13-3c 05/26/92 05/29/92 <10 <10 <0.005 <0.005 <0.005 <0.005 <50 SS-14-3B 05/26/92 05/29/92 <50 <10 <10 <0.005 <0.005 < 0.005 <0.005 < 0.005 <0.005 0.095 SS-15-4C 16 05/26/92 05/29/92 <10 12 0.014 <50 < 0.005 SS-16-4B 05/26/92 05/29/92 <50 <10 <10 <0.005 <0.005 <0.005 0.060 SS-17-5C 05/26/92 05/29/92 <50 <10 12 0.017 < 0.005 0.029 <0.005 <0.005 < 0.005 SS-18-58 05/26/92 05/29/92 <50 <10 <10 <0.005 SS-19-68 05/26/92 05/29/92 <10 <10 <0.005 <0.005 <0.005 <0.005 <50 <0.005 <0.005 <0.005 < 0.005 SS-20-6C 05/26/92 05/29/92 <50 <10 <10 <0.005 <0.005 <0.005 <0.005 SS-21-7C 8 05/26/92 05/29/92 <50 <10 <10 <0.005 <0.005 < 0.005 SS-22-7B 05/26/92 05/29/92 <50 <10 <10 <0.005 SS-23-8C 16 05/26/92 05/29/92 <50 <10 <10 <0.005 < 0.005 <0.005 <0.005 <0.005 < 0.005 <0.005 <0.005 05/26/92 05/29/92 <10 <10 SS-24-8B <50 <0.005 <0.005 SS-25-9B 12 05/26/92 05/29/92 <10 <10 <0.005 <0.005 <50 < 0.005 <0.005 <0.005 <10 < 0.005 SS-26-9C 12 05/26/92 05/29/92 <50 <10 0.080 SS-27-10C 14 05/26/92 05/29/92 60 21 31 0.024 < 0.005 0.037 <10 <10 <0.005 <0.005 0.058 0.350 SS-28-10B 05/26/92 05/29/92 <50 <10 <0.005 0.011 0.021 10 05/26/92 05/29/92 <10 <0.005 SS-29-10A <50

TABLE 6

ANALYTICAL RESULTS OF SOIL SAMPLES

COLLECTED FROM AERATION BEDS*

(results in parts per million [ppm])

Comple	Sample	Dana	Laboratory	TPH	TPH	TPH				Total
Sample	Depth	Date	Analysis	as Oil	as Diesel	as Cocolino	Ponzono	Toluene	Ethylbenzene	Xylenes
10	(inches)	29ubrea	Return Date	U11	Dieset	Gasoline	Benzene	iotuene	Ethytbenzene	Ay Lenes
SS-30-9A	12	05/26/92	05/29/92	<50	<10	<10	0.024	<0.005	0.020	0.057
SS-51-1A	12	07/17/92	07/30/92	NA	NA	<1.0	<0.005	<0.005	<0.005	<0.005
SS-52-2A	. 12	07/17/92	07/30/92	NA	NA	2.3	<0.005	<0.005	<0.005	<0.005
SS-53-1B	12	07/17/92	07/30/92	NA	NA	1.8	<0.005	<0.005	<0.005	<0.005
SS-54-3A	18	07/17/92	07/30/92	NA	NA	3.2	<0.005	<0.005	<0.005	<0.005
SS-55-2B	18	07/17/92	07/30/92	NA	NA	1.7	<0.005	<0.005	<0.005	<0.005
SS-56-10	18	07/17/92	07/30/92	NA	NA	1.6	<0.005	<0.005	<0.005	<0.005
SS-57-3B	12	07/17/92	07/30/92	NA	NA	2.5	<0.005	<0.005	<0.005	<0.005
SS-58-10	18	07/17/92	07/30/92	NA	NA	1.0	<0.005	0.008	<0.005	<0.005
SS-59-20	16	07/17/92	07/30/92	NA	NA	<1.0	<0.005	<0.005	<0.005	<0.005
SS-60-2D	12	07/17/92	07/30/92	NA	NA	2.7	<0.005	<0.005	<0.005	<0.005
ss-61-30	12	07/17/92	07/30/92	NA	NA	1.4	<0.005	<0.005	<0.005	<0.005
ss-62-30	18	07/17/92	07/30/92	NA	NA	1.4	<0.005	0.006	<0.005	<0.005
ss-63-40	18	07/17/92	07/30/92	NA	NA	2.8	<0.005	<0.005	<0.005	<0.005
SS-64-4D	12	07/17/92	07/30/92	NA	NA	1.1	<0.005	<0.005	<0.005	<0.005
SS-65-4B	12	07/17/92	07/30/92	NA	NA	1.7	<0.005	<0.005	<0.005	<0.005
SS-66-5D	18	07/17/92	07/30/92	NA	NA	3.9	<0.005	0.006	<0.005	0.016
SS-67-4A	12	07/17/92	07/31/92	NA	NA	<1.0	<0.005	<0.005	<0.005	<0.005
SS-68-60	18	07/17/92	07/31/92	NA	NA	1.9	<0.005	<0.005	<0.005	<0.005
SS-69-5A	13	07/17/92	07/31/92	NA	NA	17	<0.005	<0.005	<0.005	<0.005
SS-70-6A	24	07/17/92	07/31/92	NA	NA	2.3	<0.005	<0.005	<0.005	<0.005
SS-71-58	20	07/17/92	07/31/92	NA	NA	2.4	<0.005	0.006	<0.005	<0.005
SS-72-10	12	07/17/92	07/31/92	NA	NA	1.7	<0.005	0.007	<0.005	<0.005
SS-73-20	18	07/17/92	07/31/92	NA	NA	1.6	<0.005	<0.005	<0.005	<0.005
SS-74-20	18	07/17/92	07/31/92	NA	NA	3.0	<0.005	<0.005	<0.005	<0.005
SS-75-10	12	07/17/92	07/31/92	NA	NA	8.8	<0.005	<0.005	<0.005	<0.005
SS-76-28	12	07/17/92	07/31/92	NA	NA	<1.0	<0.005	<0.005	<0.005	<0.005
SS-77-18	18	07/17/92	07/31/92	NA	NA	2.4	<0.005	<0.005	<0.005	<0.005
SS-78-2A		07/17/92		NA	NA	1.0	<0.005	<0.005	<0.005	<0.005
SS-79-1A			07/31/92	NA	NA	<1.0	<0.005	0.007	<0.005	<0.005

TABLE 6
ANALYTICAL RESULTS OF SOIL SAMPLES
COLLECTED FROM AERATION BEDS*
(results in parts per million [ppm])

	Sample		Laboratory	TPH	TPH	TPH				
ample	Depth	Date	Analysis	as	as	as				Total
ID	(inches)	Sampled	Return Date	Oil	Diesel	Gasoline	Benzene	Toluene	Ethylbenzene	Xylenes
s-80-3A	12	07/17/92	07/31/92	NA	NA	1.9	<0.005	<0.005	<0.005	<0.005
S-81-4A	12	07/17/92	07/31/92	NA	NA	1.7	<0.005	0.006	<0.005	0.017
s-82-3B	14	07/17/92	07/31/92	NA	NA	<1.0	<0.005	0.006	<0.005	<0.005
S-83-48	12	07/17/92	07/22/92	KA	NA	<1.0	<0.005	<0.005	<0.005	0.02
s-84-3C	18	07/17/92	07/22/92	NA	NA	<1.0	<0.005	<0.005	<0.005	0.01
s-85-4C	18	07/17/92	07/22/92	NA	NA	1.5	<0.005	0.020	0.120	0.64
s-86 -3 d	16	07/17/92	07/22/92	NA	NA	<1.0	<0.005	<0.005	<0.005	0.007
S-87-4D	18	07/17/92	07/22/92	NA	NA	<1.0	<0.005	<0.005	<0.005	0.014
S-88-5A	12	07/21/92	08/05/92	NA	NA	1.0	<0.005	<0.005	<0.005	<0.00
S-89-5B	18	07/21/92	08/05/92	AH	NA	3.9	<0.005	<0.005	<0.005	<0.00
s-90-5C	15	07/21/92	08/05/92	NA	NA	<1.0	<0.005	<0.005	<0.005	<0.00
S-91-5D	14	07/21/92	08/05/92	NA	NA	1.1	<0.005	<0.005	<0.005	<0.00
s-92-60	12	07/21/92	08/05/92	NA	AK	1.2	<0.005	<0.005	<0.005	<0.00
s-93-6C	12	07/21/92	08/05/92	NA	NA	3.4	<0.005	<0.005	<0.005	<0.00
s-94-6C	20	07/21/92	08/05/92	NA	NA	1.3	<0.005	<0.005	<0.005	<0.00
s-95-8C	18	07/21/92	08/05/92	NA	NA	<1.0	<0.005	<0.005	<0.005	<0.00
s-96-7C	16	07/21/92	08/05/92	NA	NA	<1.0	<0.005	<0.005	<0.005	<0.00
s-97-6C	18	07/21/92	08/05/92	NA	NA	<1.0	<0.005	<0.005	<0.005	<0.00
s-98-5D	14	07/21/92	08/05/92	NA	NA	12.0	<0.005	<0.005	0.068	0.25
S-99-5E	16	07/21/92	08/05/92	NA	NA	<1.0	<0.005	<0.005	<0.005	<0.00
s-100-4	E 12	07/21/92	08/05/92	NA	NA	<1.0	<0.005	<0.005	<0.005	<0.00
S-101-4	20	07/21/92	08/05/92	NA	NA	1.3	<0.005	<0.005	0.009	0.01
s-102-3	D 20	07/21/92	08/05/92	NA	NA	<1.0	<0.005	<0.005	<0.005	0.00
s-103-3	E 12	07/21/92	08/05/92	NA	NA	9.7	<0.005	<0.005	0.040	0.09
s-104-2	E 16	07/21/92	08/03/92	NA	NA	<1.0	<0.005	<0.005	<0.005	<0.00
s-105-2	D 12	07/21/92	08/03/92	NA	NA	2.6(1)	<0.005	<0.005	<0.005	0.00
s-106-1	D 18	07/21/92	08/03/92	NA	NA	<1.0	<0.005	<0.005	<0.005	<0.00
s-107-1	E 14	07/21/92	08/03/92	NA	NA	<1.0	<0.005	<0.005	<0.005	<0.005
s-108-8	E 12	08/10/92	08/13/92	NA	NA	<1.0	<0.005	<0.005	<0.005	<0.005
s-10 9-1	A 12	08/10/92	08/13/92	NA	NA	<1.0	<0.005	<0.005	<0.005	<0.00

TABLE 6

ANALYTICAL RESULTS OF SOIL SAMPLES

COLLECTED FROM AERATION BEDS*

(results in parts per million [ppm])

Sample TPH Laboratory TPH TPH Sample Depth Date Analysis as as as Total IĐ (inches) Sampled Return Date Gasol ine Toluene Ethyl benzene **Xylenes** Oit Diesel Benzene <0.005 14 08/10/92 08/13/92 <0.005 <0.005 <0.005 SS-110-60 NA 3.1 SS-111-1A 08/10/92 08/13/92 <1.0 <0.005 < 0.005 <0.005 <0.005 NA NA 08/10/92 08/13/92 SS-112-4C NA 9.4 < 0.005 0.015 0.040 0.280 NA 08/18/92 08/28/92 < 0.005 < 0.005 <0.005 <0.005 SS-113-8D <1.0 NA NA SS-114-8D 08/18/92 08/28/92 NA <1.0 < 0.005 < 0.005 <0.005 <0.005 NA <0.005 <0.005 SS-115-7D 08/18/92 08/28/92 <1.0 < 0.005 <0.005 NA NA <0.005 SS-116-70 18 08/18/92 08/28/92 NA 1.3(1) < 0.005 < 0.005 <0.005 NA SS-117-6D 08/18/92 08/28/92 3.2(1)< 0.005 <0.005 <0.005 0.010 NA NA 12 08/18/92 08/28/92 < 0.005 < 0.005 <0.005 0.030 SS-118-60 NA NA 3.0(1)08/18/92 08/28/92 <1.0 < 0.005 < 0.005 <0.005 <0.005 SS-119-5D NA NA 0.005 SS-120-4D 08/18/92 08/28/92 NA NA <1.0 < 0.005 <0.005 <0.005 SS-121-5D 08/18/92 08/28/92 <1.0 < 0.005 <0.005 <0.005 <0.005 NA NA 08/18/92 08/28/92 < 0.005 <0.005 <0.005 <0.005 SS-122-3D <1.0 NA NA <0.005 <0.005 <0.005 <0.005 SS-123-4D 08/18/92 08/28/92 NA <1.0 NA <0.005 0.008 <0.005 <0.005 SS-124-3D 08/18/92 08/28/92 NA <1.0 NA <0.005 <0.005 SS-125-2D 08/18/92 08/28/92 NA <1.0 < 0.005 <0.005 NA 08/18/92 08/28/92 <1.0 <0.005 <0.005 <0.005 <0.005 SS-126-2D NA NA <0.005 ss-127-1C 08/20/92 09/02/92 1.7(1) <0.005 <0.005 <0.005 NA NA 0.005(2)SS-128-18 08/20/92 09/02/92 <1.0 <0.005 <0.005 <0.005 NA NA <0.005 <1.0 <0.005 < 0.005 <0.005 SS-129-1B 08/20/92 09/02/92 NA NA 0.012 SS-130-1C 08/20/92 09/02/92 NA 1.5(1)< 0.005 < 0.005 0.005 NA <0.005 < 0.005 0.005 SS-131-2C 08/20/92 09/02/92 NA 2.2(1) <0.005 NA <0.005 <0.005 <0.005 08/20/92 09/02/92 <1.0 <0.005 SS-132-2B NA NA <0.005 <0.005 ss-133-2C 08/20/92 09/02/92 NA 2.2(1) <0.005 <0.005 18 NA 0.009 < 0.005 0.008(2)SS-134-2B 08/20/92 09/02/92 NA NA <1.0 < 0.005 1.3(1) < 0.005 <0.005 <0.005 <0.005 ss-135-3C 12 08/20/92 09/02/92 NA NA <0.005 0.006(2)<1.0 <0.005 <0.005 SS-136-3B 10 08/20/92 09/02/92 NA NA <0.005 <0.005 <0.005 <0.005 <1.0 SS-137-3C 9 08/20/92 09/02/92 NA NA <0.005 <1.0 <0.005 < 0.005 <0.005 SS-138-3B 08/20/92 09/02/92 NA NA <0.005 SS-139-4C 12 08/20/92 09/02/92 NA 1.9(1) < 0.005 <0.005 < 0.005 NA

TABLE 6

ANALYTICAL RESULTS OF SOIL SAMPLES

COLLECTED FROM AERATION BEDS*

(results in parts per million [ppm])

TPH Sample Laboratory TPH TPH Sample Depth **Analysis** as as Total Date as ID (inches) Sampled Return Date Oil Diesel Gasol ine Benzene Toluene Ethylbenzene **Xylenes** SS-140-4B 14 08/20/92 09/02/92 <0.005 <0.005 NA <1.0 <0.005 <0.005 NA <0.005 SS-141-4C 12 08/20/92 09/02/92 NA <1.0 <0.005 <0.005 <0.005 NA SS-142-4B 20 08/20/92 09/02/92 NA NA 4.8(1) <0.005 <0.005 <0.005 0.006 SS-143-5C 08/20/92 08/31/92 1.5(1) < 0.005 0.006 0.009 0.05 NA NA SS-144-5C 14 08/20/92 08/31/92 <1.0 <0.005 < 0.005 NA NA < 0.005 < 0.005 SS-145-5B 08/20/92 08/31/92 1.8(1) <0.005 0.005 0.005 0.020 ΝA NA SS-146-6C 08/20/92 08/31/92 2.6(1) 0.009 <0.005 0.020 0.100 NA NA SS-147-58 08/20/92 08/31/92 NA 1.9(1)<0.005 < 0.005 0.009 0.030 NA 08/20/92 08/31/92 1.5(1) <0.005 <0.005 0.024 SS-148-6C NA 0.006 NA <0.005 <0.005 SS-149-6B 08/20/92 08/31/92 <1.0 <0.005 <0.005 NA NA 0.030 0.090 SS-150-7C 9 08/20/92 08/31/92 2.3(1)0.013 0.009 NA NA SS-151-6B 08/20/92 08/31/92 NA 1.7(1) <0.005 <0.005 <0.005 0.016 NA SS-152-7C 12 08/20/92 08/31/92 NA <1.0 <0.005 <0.005 <0.005 0.006 NA 0.010 0.024 08/20/92 08/31/92 1.4(1) <0.005 <0.005 SS-153-7B NA NA SS-154-70 08/20/92 08/31/92 NA NA NA NA NA NA NA 0.010 1.7(1) < 0.005 <0.005 SS-155-7B 08/20/92 08/31/92 NA NA < 0.005 SS-156-8C 08/20/92 08/31/92 NA 1.0(1) <0.005 <0.005 <0.005 <0.005 NA <0.005 0.017 SS-157-8C 08/20/92 08/31/92 NA 1.3(1) <0.005 <0.005 NA <0.005 <0.005 SS-158-88 08/20/92 08/31/92 NA NA <1.0 <0.005 <0.005 <0.005 <0.005 <0.005 0.006 SS-159-8B 08/20/92 08/31/92 NA <1.0 NA <0.005 0.006 SS-160-8A 08/20/92 08/31/92 NA NA <1.0 <0.005 < 0.005 <1.0 <0.005 <0.005 <0.005 <0.005 SS-161-6A 08/20/92 08/31/92 NA NA < 0.005 <1.0 <0.005 < 0.005 < 0.005 SS-162-8A 08/20/92 08/31/92 NA NA < 0.005 0.008 <1.0 <0.005 < 0.005 SS-163-6A 08/20/92 08/31/92 NA NA <0.005 0.006 <1.0 <0.005 <0.005 SS-164-7A 08/20/92 08/31/92 NA NA < 0.005 SS-165-5A 08/24/92 09/02/92 NA <1.0 <0.005 <0.005 <0.005 NA 08/24/92 09/02/92 < 0.005 < 0.005 <0.005 < 0.005 SS-166-5A NA <1.0 NA <1.0 <0.005 <0.005 <0.005 <0.005 SS-167-6A 08/24/92 09/02/92 NA NA 0.016 < 0.005 0.006 SS-168-6A 08/24/92 09/02/92 NA 1.4(1) <0.005 NA < 0.005 <0.005 < 0.005 SS-169-7A 10 08/24/92 09/02/92 NA NA 3.3(1) <0.005

TABLE 6

ANALYTICAL RESULTS OF SOIL SAMPLES

COLLECTED FROM AERATION BEDS*

(results in parts per million [ppm])

Sample Laboratory TPH TPH TPH Sample Depth Date Analysis as as Total as Xylenes ΙĐ (inches) Sampled Return Date Oil Diesel Gasoline Benzene Toluene Ethylbenzene SS-170-1D 12 08/24/92 09/02/92 NA <1.0 <0.005 < 0.005 < 0.005 <0.005 NA 0.011 SS-171-1D 08/24/92 09/02/92 1.3(1) <0.005 <0.005 < 0.005 NA NΑ SS-172-70 12 08/24/92 09/02/92 1.2(1) < 0.005 < 0.005 <0.005 NA NA <0.005 SS-173-60 08/24/92 09/02/92 NA NA 1.3(1) <0.005 <0.005 <0.005 <0.005 SS-174-5D 18 08/24/92 09/02/92 <1.0 < 0.005 <0.005 <0.005 <0.005 NA NA <0.005 SS-175-4D 08/24/92 09/02/92 <1.0 <0.005 < 0.005 < 0.005 NA NA SS-176-1D 08/24/92 09/02/92 NA <1.0 <0.005 <0.005 < 0.005 < 0.005 NA <1.0 <0.005 <0.005 <0.005 SS-177-20 08/24/92 09/02/92 NA NA <0.005 SS-178-3D 08/24/92 09/02/92 NA <1.0 <0.005 <0.005 <0.005 < 0.005 NA SS-179-10 08/24/92 09/02/92 <1.0 <0.005 <0.005 <0.005 < 0.005 NA NA SS-180-2C 08/27/92 09/10/92 <1.0 < 0.005 <0.005 <0.005 <0.005 NA NA <1.0 <0.005 <0.005 < 0.005 <0.005 SS-181-3C 08/27/92 09/10/92 NA NA SS-182-4C 08/27/92 09/10/92 NA NA <1.0 <0.005 <0.005 <0.005 <0.005 SS-183-4B 08/27/92 09/10/92 <1.0 <0.005 <0.005 <0.005 < 0.005 NA NA < 0.005 SS-184-3B 16 08/27/92 09/10/92 NA NA <1.0 <0.005 <0.005 <0.005 <0.005 <0.005 <0.005 SS-185-2B 08/27/92 09/10/92 <1.0 <0.005 NA NA <0.005 SS-186-1B 08/27/92 09/10/92 NA NA <1.0 <0.005 <0.005 <0.005 SS-187-1A <1.0 <0.005 <0.005 <0.005 <0.005 08/27/92 09/10/92 NA NA <0.005 <0.005 < 0.005 <1.0 <0.005 SS-188-2A 08/27/92 09/10/92 NA NA < 0.005 SS-189-3A 08/27/92 09/10/92 <1.0 <0.005 < 0.005 < 0.005 NA NA <0.005 <0.005 <1.0 < 0.005 <0.005 SS-190-4A 08/27/92 09/10/92 NA NA SS-191-5A 08/27/92 09/10/92 <1.0 <0.005 <0.005 <0.005 <0.005 NA NA <0.005 <0.005 < 0.005 SS-192-5B 08/27/92 09/10/92 <1.0 <0.005 NA NA <0.005 <0.005 <0.005 <0.005 ss-193-5c 08/27/92 09/10/92 <1.0 NA NA <0.005 <0.005 <0.005 <0.005 SS-194-6A 08/28/92 09/15/92 <1.0 NA NA < 0.005 < 0.005 SS-195-7A 08/28/92 09/15/92 NA <1.0 <0.005 < 0.005 <1.0 <0.005 <0.005 <0.005 <0.005 SS-196-7B 08/28/92 09/15/92 NA NA <0.005 SS-197-68 12 08/28/92 09/15/92 NA <1.0 <0.005 <0.005 <0.005 NA <0.005 2.7(1) <0.005 <0.005 <0.005 SS-198-7A 08/28/92 09/15/92 NA ΝA <0.005 <0.005 SS-199-6A 18 08/28/92 09/15/92 NA <1.0 <0.005 <0.005 NA

TABLE 6
ANALYTICAL RESULTS OF SOIL SAMPLES
COLLECTED FROM AERATION BEDS*
(results in parts per million [ppm])

Laboratory TPH TPH Sample Total Sample Depth Date Analysis as as as Ethylbenzene Xylenes ID (inches) Sampled Return Date Oil Diesel Gasol ine Benzene Toluene <1.0 <0.005 <0.005 <0.005 <0.005 SS-200-4A 16 08/28/92 09/15/92 NA <0.005 <1.0 <0.005 <0.005 <0.005 08/28/92 09/15/92 NA SS-201-5A <0.005 <1.0 <0.005 18 08/28/92 09/15/92 NA <0.005 <0.005 SS-202-3A <1.0 <0.005 <0.005 <0.005 < 0.005 SS-203-1B 14 08/28/92 09/15/92 NA 18 08/28/92 09/15/92 NA <1.0 <0.005 <0.005 <0.005 <0.005 SS-204-2A <0.005 <0.005 1.4(1) < 0.005 < 0.005 SS-205-1C 08/28/92 09/15/92 NA <0.005 <0.005 <1.0 <0.005 <0.005 SS-206-2B 16 08/28/92 09/15/92 NA NA <0.005 <0.005 08/28/92 09/15/92 <1.0 < 0.005 < 0.005 SS-207-4A NA NA <0.005 <0.005 ss-208-2C 08/28/92 09/15/92 NA NA <1.0 < 0.005 < 0.005 6.4(1) <0.005 <0.005 <0.005 0.015 08/28/92 09/15/92 NA SS-209-4B NA <0.005 <0.005 08/28/92 09/15/92 NA <1.0 <0.005 <0.005 ss-210-3C NA <0.005 0.008 < 0.005 3.8(1) < 0.005 SS-211-5C 08/28/92 09/15/92 NA NA <0.005 <0.005 <0.005 SS-212-58 14 08/28/92 09/15/92 NA NA 4.5(1) < 0.005 <0.005 <0.005 12 08/28/92 09/15/92 NA <1.0 <0.005 <0.005 SS-213-3B NA <0.005 <0.005 <0.005 <1.0 <0.005 SS-214-5A 20 08/28/92 09/15/92 NA NA <0.005 <0.005 <0.005 <1.0 <0.005 SS-215-3A 18 08/28/92 09/15/92 NA <0.005 <0.005 <0.005 <1.0 <0.005 SS-216-6A 16 08/28/92 09/15/92 NA <0.005 <0.005 <0.005 16 08/28/92 09/15/92 <1.0 < 0.005 SS-217-68 <1.0 < 0.005 <0.005 <0.005 <0.005 18 08/28/92 09/15/92 SS-218-6C NA

NOTES:

NA = not analyzed

^{*} All samples analyzed by Precision Analytical Laboratories Inc. of Richmond, California. Samples were analyzed for total petroleum hydrocarbons (TPH) as oil, diesel, and gasoline using Modified EPA Method 8015; and benzene, toluene, ethylbenzene, and xylenes using Modified EPA Method 8020.

^{**} Duplicate sample not analyzed

Weathered gasoline

² Confirmed by laboratory by second column








Figure 1: SITE LOCATION MAP YERBA BUENA PROJECT SITE

Project No. 1649

LEVINE • FRICKE CONSULTING ENGINEERS AND HYDROGEOLOGISTS

1649ALS-SFEB91+172





DEEPER (62 FEET)
MONITORING WELL LOCATION

ABANDONED SHALLOW MONITORING WELL (INSTALLED BY LEVINE-FRICKE)

ABANDONED SHALLOW MONITORING WELL (INSTALLED BY AQUA RESOURCES, INC.)

PROPOSED MONITORING WELL LOCATION


LOCATION OF FORMER BUSINESSES


0 150 300 FEET


Figure 2 :


SITE PLAN AND
MONITORING WELL LOCATIONS
YERBA BUENA PROJECT SITE
EMERYVILLE, CALIFORNIA


Project No. 1649.07 LEVINE-FRICKE ENGINEERS, HYDROGEOLOGISTS, & APPLIED SCIENTISTS

















APPENDIX A

CORRESPONDENCE FROM THE ALAMEDA COUNTY HEALTH CARE SERVICES
AGENCY TO RANSOME COMPANY, DATED FEBRUARY 1991

AND

CORRESPONDENCE FROM THE ALAMEDA COUNTY HEALTH CARE SERVICES TO CATELLUS DEVELOPMENT CORPORATION

DATED MARCH 5, 1991

AND

CORRESPONDENCE FROM THE REGIONAL WATER QUALITY CONTROL BOARD TO LEVINE*FRICKE, DATED JUNE 24, 1992

ALAMEDA COUNTY HEALTH CARE SERVICES

AGENCY



DAVID J. KEARS, Agency Director

4 February 1991

DEPARTMENT OF ENVIRONMENTAL HEA Hazardous Materials Program 60 Swan Way, Rm. 200 Oakland, CA 94621 (415)

S. Kinear Smith Ransome Company P.O. Box 8506 4030 Hollis Street Emeryville, CA 94662

Subject: Soil and Groundwater Investigation being conducted at the former Ransome Company site, 4030 Hollis Street, Emeryville.

Dear Mr. Smith:

Thank you for the report prepared by Aqua Resources Incorporated, dated 16 January, 1991, and submitted to this office for review. This agency is satisfied in the quality of the soil investigation conducted at this site and approval is granted for the expavation of contaminated regions of the property as proposed in the Aqua Resources report. Please ensure that verification samples are collected in each excavation zone to ensure that no hydrocarbon contamination in excess of 1,000 parts per million remains. The absence of this verification sampling will hinder a final closure of the project in accordance with guidelines established by the Regional Board.

In the Aqua Resources report various options for the treatment of contaminated soil are proposed. The options specified include:

The on-site aeration of gasoline contaminated soil.

The on-site bioremediation of diesel and oil contaminated soil.

The transport of diesel and oil contaminated soil to an offsite location for bioremediation treatment.

The off-site transport of contaminated soil for landfill disposal.

This agency has no objection to the pursuit of these four options, however, please be awars that the involvement of other regulatory agencies may be involved and that prior to this office granting approval for the implementation of a specific treatment process assurance will be required that all appropriate requirements of other agencies are being met.

S. Kinnear Smith
Ransome Company
P.O. Box 8506
4030 Hollis Street
Emeryville, CA 94662
Re. 4030 Hollis, Emeryville
4 February 1991
Page 2 of 3

The on-site aeration of gasoline contaminated soil may require the issuance of a permit from the Bay Area Air Quality Management District. Following the issuance of this permit or the granting of a waiver for the need for such a permit, approval for the implementation of this process will ensue.

The off-site transportation of contaminated soil for treatment at another location or landfill disposal will first require that this soil be characterized in accordance with § 66700 and § 66702 of Title 22 of the California Code of Regulations. Should this soil constitute hazardous waste, transport off-site will require adherence to the uniform hazardous waste manifest provisions of Title 13 of the CCR. An off-site location treating hazardous wastes must be licensed by the state as a hazardous waste treatment, storage and disposal facility.

If testing results determine that this soil constitutes hazardous waste, on-site treatment may proceed provided that a permit for the treatment is obtained from the Department of Health Services or that the Permit by Rule provisions of § 66392 of Title 22 of the CCR are strictly followed. If the soil constitutes non-hazardous waste than no such permit will be required for treatment. The specific classification of this soil must be completed prior to this agency granting approval for the implementation of a specific treatment proposal outlined in the Aqua Resources report.

Approval is granted for the installation of an additional groundwater monitoring well in the vicinity of the former fuel pump island. It is our understanding that this installation will take place following the completion of further soil excavation in this region.

As recommended in the Aqua Resources report, further groundwater monitoring is required at this site. Please be aware that further investigative actions may be required if a groundwater problem necessitating greater clarification is detected during this monitoring program. You can anticipate a minimum of one year of quarterly monitoring as being the minimum necessary to fulfill the requirements of the San Francisco Bay Regional Water Quality Control Board. The frequency of or need for further monitoring will be based upon the data derived during this first year.

s. Kinnear Smith Ransome Company P.O. Box 8506 4030 Hollis Street Emeryville, CA 94662 Re. 4030 Hollis Emeryville 4 February 1991 Page 3 of 3

If you have any questions concerning this matter or the steps which must now be taken, please contact me at (415)271-4320. The contents of this letter have been discussed with Mark Milani of Aqua Resources Incorporated.

Sincerely,

Jani of Byra

Dennis J. Byrne Senior Hazardous Materials Specialist

Amanda Spencer, Levine-Fricke

Lester Feldman, SFBRWQCB cc: Howard Hatayama, DOHS Rafat Shahid, Assistant Director, Alameda County Department of Environmental Health. Ric Notini, Catellus Development Corporation Mark Milani, Aqua Resources Inc.

DEPARTMENT OF ENVIRONMENTAL HEALTH Hazardous Materials Program 80 Swan Way, Rm. 200 Oakland, CA 94621 (415)

5 March 1991

Rick Notini Catellus Development Corporation 201 Mission Street Suite 250 San Francisco, CA 94105

Subject: Remedial Plan for the Yerba Buena Project in Oakland.

Dear Mr. Notini:

Thank you for the remedial plan, dated 11 February 1991, prepared by Levine-Fricke and submitted to this office. A review of this plan has been completed and approval is granted for implementation of the following components:

- * The physical excavation of lead and zinc contaminated soils for disposal as hazardous waste.
- * The physical excavation of PCB contaminated soil to a residue of no greater than one part per million.
- * The installation of a French Drain along the west side of Hollis Street for the collection of ground water.
- * The installation of additional ground water monitoring wells.

Approval of the proposed encapsulation of hydrocarbon contaminated soil as described in the remedial plan will be granted upon the completion of the fish bioassay study and submittal of this data for review.

Rick Notini
Catellus Development Corp.
201 Mission Street
Suite 250
San Francisco, CA 94105
Re. Yerba Buena Remedial Plan
5 March 1991
Page 2 of 2

The contents of this letter have been discussed with Amanda Spencer of Levine-Fricke. If you have any questions concerning this matter, please contact me at (415)271-4320.

Sincerely,

Dennis J. Byrne


Senior Hazardous Materials Specialist

CC: Lester Feldman, SFBRWQCB
Tom Gandesbery, SFBRWQCB
Howard Hatayama, DOHS
Rafat Shahid, Assistant Director, Alameda County Department
of Environmental Health.

Don Marini, Catellus Development Corp. Amanda Spencer, Levine-Fricke

CALIFORNIA REGIONAL WATER QUALITY CONTROL BOARD SAN FRANCISCO BAY REGION

2101 WEBSTER STREET, SUITE 500 OAKLAND, CA 94612





June 24, 1992 File No. 2223.09(LF)

Amanda Spencer Senior Hydrogeologist Levine Fricke 1900 Powell Street, 12th Floor Emeryville, CA 94608

SUBJECT: Catellus - Yerba Buena Project, Emeryville

Dear Ms. Spencer:

This letter is written in follow-up to your meeting of June 22 with Lester Feldman of my staff concerning the subject proposed development project. I understand that Dennis Byrne of Alameda County Health Care Services Agency has been acting as lead in resolving soil and groundwater pollution issues for the sites involved. I also understand that the overall project involves identification and remediation of volatile organics in the groundwater at one location, verification of hydrocarbon cleanup in the groundwater at several locations, the closure of several underground fuel tanks, remediation of hydrocarbon contaminated soils related to former underground tanks, and the relocation of some hydrocarbon contaminated soils within the project boundaries.

As indicated by Mr. Feldman, this Regional Board staff has no objection to the relocation of hydrocarbon contaminated soils within the project area as proposed in the Draft Plan dated March 10, 1992. This Draft Plan should be re-named the Soils Management Plan and be amended to include specific guidance language providing for the maintenance of the proposed encapsulations to protect water quality. As indicated by Mr. Feldman and Mr. Byrne any future activity on the site which necessitates excavation of the soils of concern should be managed in such a way as to mitigate any water quality problem which could arise (e.g., polluted surface runoff)

Additional concerns which should be addressed for the subject site prior to any leased business occupancy or sale include the following:

- 1. A Notice is to be placed on the recorded deed(s) whenever soils containing elevated levels of pollutants are contained on any affected parcel.
- 2. An Self-Monitoring Program shall be in place at all times acceptable to the Alameda County Health Agency or the Regional Board staff. This program shall provide for monitoring of all groundwater under active remediation, and shall provide for verification of all completed cleanups. An Annual Report shall be filed with both agencies.

3. Completion of any groundwater cleanup will be considered by the Board based upon a recommendation for Closure by the Alameda County Health Agency per Board guidelines.

Please direct any questions to Lester Feldman of my staff at (510) 464-1332.

Sincerely,

Steven R. Ritchie, Executive Officer

cc: Dennis Byrne, Alameda County Health Agency Don Marini, Catellus Ric Notini, Catellus Jim Levine, Levine Fricke

SOIL SAMPLING PROCEDURES

Sampling Procedures

Soil samples were collected for chemical analysis to provide data to evaluate the extent of chemicals in soils at the Site. Soil samples were collected in the field by driving a precleaned brass tube into the soil using a clean rubber mallet. Where access was limited or hazardous to Levine Fricke personnel, soil was collected from the bucket of the excavator. Approximately 3 inches of soil were scraped off the top of the soil in the bucket and a brass tube was driven into the representative soil in the bucket using a rubber mallet. The sample tubes were filled completely to minimize headspace and loss of volatile compounds, if present. The ends of the tubes were covered with aluminum foil, and capped with air-tight plastic caps to prevent possible moisture and chemical loss.

After being sealed and labeled, soil samples were immediately placed in a chilled cooler containing ice for delivery to the analytical laboratory under strict chain-of-custody protocols.

Decontamination Procedures

All equipment used for collecting soil samples during the investigation was properly decontaminated before and after each use, and before initial use at the Site. This was accomplished through steam cleaning and/or washing with Alconox (a laboratory grade detergent) and rinsing with deionized, distilled, or fresh water.

APPENDIX C

GEOTECHNICAL ENGINEERING FIELD SERVICES (BACKFILL AND COMPACTION PROCEDURES)

GEOTECHNICAL ENGINEERING FIELD SERVICES (BACKFILL AND COMPACTION PROCEDURES)

Geotechnical engineering field services were conducted at the Ransome property ("the Property") at the Yerba Buena Project site in Emeryville and Oakland, California, following excavation of petroleum hydrocarbon-affected soils.

Specifically, Levine Fricke observed backfilling activities conducted at the property in four phases (Phase I, II, III, and IV) during the period from September 1991 through May 1992. A Levine Fricke field engineer was on site during the four phases to monitor fill placement, compaction activities, and to conduct field density tests.

H. K. Grading Contractors Inc., of Livermore, California, conducted Phase I activities during the period from September 3 through September 13, 1991, under the direction of Aqua Resources, Inc. (ARI). Plant Reclamation of Richmond, California, conducted Phase II, III, and IV of the backfilling activities during the period from October 1991 to May 1992 under the direction of Levine Fricke personnel.

Backfill material specifications and compaction requirements were presented in ARI's reports entitled "Proposed Excavation Backfill Procedure, 4030 Hollis Street, Emeryville, California," dated July 26, 1991, and "Response to the Levine Fricke Backfill Letter, Proposed Excavation Backfill Procedure, 4030 Hollis Street, Emeryville, California," dated August 26, 1991.

All backfill materials were submitted to Woodward-Clyde Consultants of Pleasant Hill, California, for laboratory compaction testing ASTM D1557 (see Table C-1). Backfill materials included on-site material (TP1 and TP2), on-site successfully aerated soil excavated stockpiles (AS and BS), and imported backfill material (SP, BM, and IB). Field and laboratory compaction test curves are included in this appendix.

Imported materials were supplied by Rogers Trucking and Equipment, Inc., of South San Francisco, California. Soils were placed in thin lifts not to exceed 8 inches in loose thickness and moisture conditioned to within 3 percent of optimum moisture content. Soils were compacted by a minimum of nine passes of the compactor to achieve at least 90 percent relative compaction as determined by the ASTM D1557 Laboratory

LEVINE-FRICKE

Compaction Test. Field and laboratory compaction test curves are included in this appendix.

Field compaction tests were conducted using a nuclear density/moisture testing instrument after the lifts of fill were placed, moisture conditioned, and compacted. Fill areas were tested to meet the 90 percent relative compaction. Table C-2 presents the field compaction test results. Field compaction test locations were selected on the basis of random sampling, with emphasis on areas with high moisture contents. The fill was recompacted and retested until test results indicated 90% compaction.

Benches measuring 0.5- to 1-foot wide were excavated every 3 vertical feet in the zone where the backfill was compacted, except in areas where the excavation was adjacent to sidewalks, fences, or other surface structures.

For excavations that extended below the ground-water table (approximately 12 feet bgs), clean imported gravel was placed to a depth of approximately 1 to 2 feet above the ground-water level. The actual level of the gravel was determined by the field engineer. The imported gravel was Type B Class II Permeable Material with approximately 70 percent of the material coarser than 1/2 inch. Geotextile fabric was laid on top of the gravel to act as a separator before placing the backfill material.

DRAFT

TABLE C-1 RESULTS OF LABORATORY COMPACTION TESTS* FIELD GEOTECHNICAL SERVICES RANSOME SOIL REMEDIATION EMERYVILLE/OAKLAND, CALIFORNIA

Sample ID	Sample Name	Backfill Material	Color and Description	Maximum Dry Density (pcf)**	Optimum Moisture Content (% Dry Wt.)
ARI PHASE I	<u>.</u>				
1) Test Pit 1	TP1	On-site Soil	Dark gray silt	103.1	18.7
2) Test Pit 2	TP2	On-site Soil	Light brown	114.7	13.5
3) Stockpile	SP	Imported Clean Fill***	Gray lean clay	117.3	13.7
4) Aeration Stockpile	AS	Aerated Soil	Gray lean sandy clay	123.5	10.7
Levine•Fricke PHASE II	,				
5) Backfill Material	ВМ	Imported Clean Fill****	Brown clayey sand	129.8	9.0
PHASE III					
6) Backfill Stockpile	BS	Aerated Soil	Brown sandy clay	122.9	11.5
7) Import Backfill	18	Imported Clean Fill	Gray-brown clayey sand	132.0	7.9

NOTES:

- * Laboratory compaction tests conducted by Woodward-Clyde Consultants of Pleasant Hill, California using Test Method ASTM 1557.
- ** pcf pounds per cubic foot
- *** Backfill material supplied by Port Costa Materials, Inc. of Port Costa, California.
- **** Backfill material supplied by Rogers Trucks & Equipment, Inc. of South San Francisco, California.

	To-+		1)	Approximate Elevation Below Final Grade	Dry Density	Moisture Content	Percent Relative Compaction (% of Max.		Specified Percent Relative
)ate	Test Number	Sample Name	Location	(ft.)	(pcf)	(% Dry Wt.)	Dry Density)	Retest	Compacti
AREA A1									
Phase 1									
04-Sep-91	1	TP2 (2)	A 1	5.5	104.8	15.10	91		90
04-Sep-91	2	SP	A1	5.0	105.9	18.04	90		90
04-Sep-91	3	SP	A1	4.5	107.6	16.26	92		90
05 - Sep - 91	4	SP	A1	3.5	108.6	15.76	93		90
AREA A2				***************************************					
Phase I									
05-Sep-91	1	SP	A2	5.0	106.6	16.23	91		90
05-Sep-91	2	SP	A2	4.5	112.0	14.39	95		90
05-Sep-91	3	SP	A2	3.5	110.8	15.91	94		90
06-Sep-91	4	SP	A2	2.5	106.8	17.27	91		- 90
06-Sep-91	5	SP	A2	1.5	103.3	12.86	90		90
			Top of Ex	isting Fill Elevatio	n**				
AREA B1					******				
Phase I									
03-Sep-91	1	AS	W-1	4.5	108.6	14.12	88		90
03 · Sep · 91	2	AS	E-1	4.5	112.8	11.93	91		90
03 - Sep - 91	3	AS	E-2	4.5	98.00	10.18	79		90
03 - Sep - 91	4	AS	E-2	4.5	102.3	14.50	83	retest of	3 90
03-Sep-91	5	AS	E-2	4.5	104.3	15.20	84	retest of	3 90
03-Sep-91	6	A\$	W-2	4.5	103.6	15.39	. 84		90
03-Sep-91	7	AS	W-2	4.5	112.3	14.91	9 1	retest of	6 90
03-Sep-91	8	TP1 (2)	€-2	4.5	99.70	14.35	97	retest of	3 90
03-Sep-91	9	TP1 (2)	₩-1	4.5	110.3	13.73	107	retest of	1 90
04 - Sep - 91	10	SP	€-1	4.0	106.4	16.29	9 1		90
04-Sep-91	11	SP	E-2	4.0	108.9	16.86	93		90
04-Sep-91	12	SP	W-1	4.0	105.4	16.44	90		90
04-Sep-91	13	SP	W-2	4.0	114.1	16.17	97		90
04-Sep-91	14	SP	W-1	3.5	109.2	15.60	93		90
04-Sep-91	15	SP	W-2	3.5	106.2	17.32	91		90
04-Sep-91	16	SP	E-1	3.5	106.0	16.50	90		90
04-Sep-91	17	SP	£-2	3.5	109.6	16.50	93		90
04 Sep 71	18	SP	€-1	2.5	106.8	15.61	91		90
04-Sep-91	19	SP	£-2	2.5	109.2	15.08	93		90
04-Sep-91	20	SP SP	W-1	2.5	114.4	15.46	98		90
	21.	SP	W-2	2.5	107.0	16.68	91		90
04-Sep-91		SP SP	W-2 E-2	2.0	110.9	16.74	95		90
04 - Sep - 91 04 - Sep - 91	22 23	SP SP	E-2 E-1	2.0	108.0	17.34	92		90
									, 7U

		((1)	Approximate Elevation	Dry	Moisture	Percent Relative Compaction		Specified Percent
	Test	Sample		Below Final Grade	Density	Content	(% of Max.		Relative
Date	Number	Name	Location	(ft.)	(pcf)	(% Dry Wt.)		Retest	Compaction
04-\$ep-91	25	SP	W-2	2.0	111.7	15.23	95		90
05-Sep-91	26	SP	E-1	1.5	111.1	16.74	95		90
05-Sep-91	27	SP	W-1	1.5	109.5	17.64	93		90
			Top of Ex	isting Fill Elevatio	n 				
AREA B2									
Phase I									
04-Sep-91	1	SP	82	4.0	105.9	16.20	90		90
04-Sep-91	2	SP	B2	3.5	109.2	17,10	93		90
05-Sep-91	3	SP	B2	2.5	98.10	17.84	84	_	90
05-Sep-91	4	SP	82	2.5	111.8	16.55	95	retest of	
05-Sep-91	5	SP	82	2.0	107.1	16.00	91		90
05-Sep-91	6	SP	82	1.5	107.1	15.96	91		90
			Top of Ex	isting Fill Elevatio	n				
AREA D									
Phase I									
04-Sep-91	1	SP	N-1	8.0	112.9	14.96	96		90
04 - Sep - 91	2	SP	N-2	8.0	106.2	16.75	91		90
04-Sep-91	3	SP	S-1	8.0	116.0	12.97	99		90
04 - Sep - 91	4	SP	s-2	8.0	108.5	16.31	93		90
04 - Sep - 91	5	SP	N-1	7.5	106.3	16.23	91		90
04-Sep-91	6	SP	N-1	7.5	109.0	15.35	93		90
04 · Sep · 91	7	SP	N-2	7.5	105.7	17.21	90		90
04-Sep-91	8	SP	N-2	7.5	106.9	17.65	91		90
04-Sep-91	9	SP	N-1	6.5	103.9	17.79	89 25		90
04-Sep-91	10	SP	N-2	6.5	111.5	16.18	95		90
04-Sep-91	11	SP SP	N-1	6.5	109.9	15.98	94 90	retest of	1
04 - Sep - 91	12	SP	N-1 N-1	6.5	105.7 113.1	16.88		retest of	1
05 - Sep - 91 05 - Sep - 91	13 14	SP SP	N-1 N-1	6.0 6.0	116.6	12.57 12.97	96 , 99		90 90
05-Sep-91	15	SP	S-1	7.0	112.4	15.28	96		90
05-Sep-91	16	SP	S-2	7.0	108.9	16.23	93		90
05-Sep-91	17	SP	5-2 C+1	8.0	109.9	14.96	94		90
05-Sep-91	18	SP	C-1	7.0	116.6	14.28	99		90
05-Sep-91	19	SP	S-1	6.0	108.9	16.70	93		90
05-Sep-91	20	SP	C-1	6.0	109.7	16.64	93		90
05-Sep-91	21	SP	\$-2	6.0	107.7	16.48	92		90
05-Sep-91	22	SP	C-1	5.0	116.6	14.28	99		90
05-Sep-91	23	SP	N-1	5.0	116.6	12.97	99		90
05-Sep-91	24	SP	S-2	5.0	107.3	16.48	92		90
11-Sep-91	25	SP	C-1	4.0	114.2	14.39	97		90

TABLE C-2
RESULTS OF FIELD COMPACTION TESTS*
SOIL REMEDIATION ACTIVITIES
FORMER RANSOME PROPERTY
EMERYVILLE, CALIFORNIA

				Approximate			Percent Relative		Specified
			(1)	Elevation	Dry	Moisture	Compaction		Percent
	Test	Sample	,	Below Final Grade	Density	Content	(% of Max.		Relative
ate	Number	Name	Location	(ft.)	(pcf)	(% Dry Wt.)	Dry Density)	Retest	Compactio
					117.0	47 70	400		200
11-Sep-91	·26	SP	S-1	4.0 4.0	117.8 109.6	13.38 13.24	100 93		90
11-Sep-91	27	SP	พ-1	4.0	109.0	. 13.24	93		90
Phase II	•								
24-0ct-91	28	BM	s-1	3.0	113.1	14.76	87		90
24-0ct-91	29	BM	พ-1	3.0	117.4	13.98	90		90
24-0ct-91	30	ВМ	s-1	3.0	117.3	15.67	90		90
Phase III									
11-Dec-91	31	88	N-2	2.5	104.7	13.03	85		90
11-Dec-91	32	8\$	Ç-2	2.5	105.1	14.62	86		90
11-Dec - 91	33	BŞ	s-2	2.5	101.9	9,43	83		90
11-Dec-91	34	BS	N-1	2.5	107.2	14.58	87	retest of	31 90
11-Dec-91	35	BS	C-1	2.5	115.5	13.40	94	retest of	32 90
11-Dec-91	36	88	S-1	2.5	114.6	12.78	93	retest of	33 90
11-Dec-91	37	BS	N-1	2,5	107.3	14.49	87	retest of	31 90
11-Dec-91	38	BS	N-1	2.5	116.8	13.13	95	retest of	31 90
11-Dec-91	39	BS	N-2	1.5	118.9	11.67	97		90
11-Dec-91	40	88	C-2	1.5	110.4	11.18	90		90
11-Dec-91	41	BS	s-2	1.5	119.0	12.17	97		90
			Top of Ex	cisting Fill Elevatio	n				
REA J-1									
Phase 1									
10-Sep-91	1	SP	E-1	10.0	111.8	15.93	95 05		90
10-Sep-91	2	SP	E-2	10.0	110.9	15.79	95 05		90
10-Sep-91	3	SP	C-2	10.0	111.5	14.46	95		90
10-Sep-91	4	SP	E-1	10.0	107.1	15.56	91		90
10-Sep-91	5	SP	E-1	9.0	113.0	14.86	96		90
11-Sep-91	6	SP	C-1	9.0	113.2	13.92	97		90
11-Sep-91	7	SP	₩-1	9.0	112.3	13.47	96		90
11-Sep-91	8	SP	C-2	9.0	113.2	13.05	97		90
11-Sep-91	9	SP	E-2	9.0	114.0	15.16	97 27		90
11-Sep-91	10	SP	E-1	8.0	114.0	12.59	97 04		90
11-Sep-91	11	SP	E-2	8.0	112.8	14.44	96		90
11-Sep-91	12	SP	W-1	8.0	108.5	13.54	93		90
11-Sep-91	13	SP	C-1	8.0	114.1	14.80	97		90
11-Sep-91	14	SP	E-2	7.5	118.5	14.40	101		90
11-Sep-91	15	SP	C-2	7.5	109.9	16.36	94		90
11-Sep-91	16	SP	M-5	7.5	115.1	13.88	98		90
11-Sep-91	17	SP	E-1	7.5	115.2	13.89	98		90
11-Sep-91	18	SP	C-1	7.5	109.5	15.17	93		90
									1

				Approximate			Relative		Specified
			(1)	Elevation	Dry	Moisture	Compaction		Percent
	Test	Sample		Below Final Grade	Density	Content	(% of Max.		Relative
ate	Number	Name	Location	(ft.)	(pcf)	(% Dry Wt.)	Dry Density)	Retest	Compaction
44 0 04	10	00	111	7.5	112.3	14.55	96		90
11-Sep-91	19	SP	W-1 E-2	7.0	113.4	13.77	96 97		90
11-Sep-91	20 21	SP SP	C-2	7.0	111.2	13.28	95		90
11-Sep-91	22	SP	W-2	7.0	114.4	14.52	98		90
11-Sep-91 11-Sep-91	23	SP SP	₩-2 E-1	6.0	117.4	14.05	100		90
11-Sep-91	24	SP	C-1	6.0	114.5	13.87	98		90
11-Sep-91	25	\$P	W-1	6.0	108.0	14.89	92		90
Phase II									
17-0ct-91	26	вм	E-1	5.5	116.3	11.09	90		90
17-0ct-91	27	ВМ	C-1	5.5	115.2	12.06	89		90
17-0ct-91	28	BM	W-1	5.5	104.3	10.25	80		90
17-0ct · 91	29	BM	C-1	5.5	112.5	10.27	87	retest of	Τ
17-0ct-91	30	ВМ	C-1	5.5	117.1	10.43	90	retest of	
17-0ct-91	31	BM	W-1	5.5	112.5	9.32	87	retest of	
17-0ct-91	32	BM	W-1	5.5	119.1	11.09	92	retest of	
17-0ct-91	33	BM	E-1	5.0	124.6	12.77	96		90
17-0ct-91	34	ВМ	C-1	5.0	125.5	11.62	97 25		90
17-0ct-91	35	8M	W-1	5.0	122.9	11.59	95		90
17-0ct-91	36	BM	E-2	5.0	124.9	11.18	96		90
18-0ct-91	37	BM	C-2	5.0	122.8	10.10	95 01		90
18-0ct-91	38	BM	W-2	5.0	118.0	11.28	91		90
21-0ct-91	39	BM	E-1	4.5	121.8	10.77	94		90
21-0ct-91	40	BM	C-2	4.5	122.9	11.12	95 24		90
21-0ct-91 21-0ct-91	41 42	BM BM	C-1 W-2	4.0 4.0	121.9 121.6	12.94 11.47	94 94		90
21-001-91	42	DM				11.41	74		
		• • • •	Top of Ex	isting Fill Elevatio	n 	••••			
REA J·2 Phase I									
06-Sep-91	1	SP	N	10.0	106.5	14.96	91		90
06 · Sep - 91	2	SP	\$	10.0	105.4	14.77	90		90
06-Sep-91	3	SP	N	9.0	110.3	15.23	94		90
06-Sep-91	4	SP	S	9.0	103.6	15.23	88		90
06-Sep-91	5	SP	\$ 	9.0	108.9	15.43	93 01	retest of	4 90 90
09-Sep-91	6	SP	N	8.0	106.6	15.86	91 04		
09-Sep-91	7	\$P	S	8.0	112.5	14.35	96		90 90
09-Sep-91	8	SP	S	7.0	106.3	15.64	91 93		90
09-Sep-91	9	SP	N	7.0	108.7	17.21			90
15-Apr-92	10	IB	N	6.0	126.8	10.91	96 93		90
15-Apr-92	11	IB	S	6.0	123.3	11.96			90
15-Apr-92 15-Apr-92	12 13	1B 1B	N S	5.0 5.0	116.6 126.2	13.32 11.56	88 96		90

TABLE C-2
RESULTS OF FIELD COMPACTION TESTS*
SOIL REMEDIATION ACTIVITIES
FORMER RANSOME PROPERTY
EMERYVILLE, CALIFORNIA

		((1)	Approximate Elevation	Dry	Moisture	Percent Relative Compaction		Specified Percent
	Test	Sample		Below Final Grade	Density	Content	(% of Max.	.	Relative
)ate 	Number	Name	Location	(ft.)	(pcf)	(% Dry Wt.)	Dry Density)	Retest	Compaction
15-Apr-92	14	18	N	5.0	122	12.3	92		90
15-Apr-92	15	IB	N	4.0	124.3	10.66	94		90
15-Apr-92	16	IB	S	4.0	126.2	11.54	96		90
Phase II									
21-0ct-91	10	ВМ	s	6.0	115.8	13.80	89		90
21-0ct-91	11	8M	Ş	6.0	120.0	12.29	92		90
21-0ct-91	12	8M	N	5.0	115.5	15.47	89		90
REA K									
Phase II									
21-0ct-91	1	ВМ	N-1	8.0	123.2	11.14	95		90
21-0ct-91	2	BM	s-1	8.0	121.6	11.47	94		- 90
21-0ct-91	3	BM	S-1	7.0	127.7	9.81	98		90
22-0ct-91	4	BM	N-1	6.0	121.7	9.11	94		90
22-0ct-91	5	BM	s-1	5.0	128.0	11.04	99		90
22-0ct-91	6	BM	N-1	4.5	116.3	12.36	90		90
22-0ct-91	7	BM	พ-1	4.5	130.6	10.00	100		90
22-0ct-91	8	BM	\$-1	4.0	119.7	11.30	92		90
24-Oct-91	9	BM	N-1	3.5	121.5	10.85	94		90
24-0ct-91	10	ВМ	s-1	3.5	128.2	10.81	99		90
24-0ct-91	11	ВМ	N-1	3.0	120.7	13.03	93		90
24-0ct-91	12	BM	S-1	2.5	116.5	16.15	90		90
Phase III									
11-Dec-91	13	BS	N-1	2.5	108.2	13.26	88		90
11-Dec-91	14	BS	S-1	2.5	109.5	11.55	89		90
11-Dec-91	15	BS	N-1	2.5	110.8	13.15	90	retest of	13 90
11-Dec-91	16	BS	\$-1	2.5	122.2	11.61	99	retest of	14 90
11-Dec-91	17	BS	N-1	1.5	111.9	11.19	91		90
11-Dec-91	18	BS	S-1	1.5	117.5	12.42	96		90

TABLE C-2
RESULTS OF FIELD COMPACTION TESTS*
SOIL REMEDIATION ACTIVITIES
FORMER RANSOME PROPERTY
EMERYVILLE, CALIFORNIA

			(1)	Approximate Elevation	Dry	Moisture	Percent Relative Compaction		Specified Percent
Date	Test Number	Sample Name	Location	Below Final Grade (ft.)	Density (pcf)	Content (% Dry Wt.)	(% of Max. Dry Density)	Retest	Relative Compaction

AREA L Phase II									
23-0ct-91	1	вм	N-1	8.0	118.6	12.09	91		90
23-0ct-91	2	ВМ	C-1	8.0	116.5	12.11	90		90
23-0ct-91	3	BM	s-1	8.0	114.1	14.12	88		90
23-0ct-91	4	BM	S-1	8.0	119.1	12.00	92	retest of	3 90
23-0ct-91	5	BM	S-1	7.0	120.0	11.83	92		90
23-0ct-91	6	BM	C-1	7.0	121.1	9.23	93		90
23-0ct-91	7	BM	พ-1	7.0	118.0	10.04	91		90
24-0ct-91	8	BM	s-1	6.0	123.5	10.04	95		90
24-0ct-91	9	BM	C-1	6.0	121.6	10.71	94		90
24-0ct-91	10	BM	N-1	6.0	118.8	9.66	92		90
24-0ct-91	11	ВМ	s-1	5.0	121.5	8.95	94		90
24-0ct-91	12	ВМ	N-1	5.0	120.0	12.90	92		- 90
15-Apr-92	13	18	N-1	4.0	125.7	10.12	95		90
15-Apr-92	14	18	s-1	4.0	133.6	9.24	101		90
05-Feb-92 05-Feb-92	1 2	1B 1B	s s	4.0 4.0	123.5 129.8	10.8 10.35	96 98		90 90
NORTHERN ARE	A N			***************************************		••••••			
05 - Feb - 92	1	18	N	4.0	125.9	9.88	95		90
05-Feb-92	2	18	N	4.0	123.6	11.1	94		90
NORTHERN ARE	A E		• • • • • •						
05-Feb-92	1	18	E	4.0	127.5	10.92	97		90
05-Feb-92	2	ΙB	Ε	4.0	121.5	11.97	92		90
19-May-92	3	ΙB		2.0	131.0	8.95	99		90
19-May-92	4	IB	Ε	2.0	129.3	8.39	98		90
19-May-92	5	18	E	2.0	129.3	9.05	98		90
NORTHERN ARE	A W1								
05 - Feb - 92	1	IB	₩1	4.0	129.2	9.53	98		90
05-Feb-92	2	18	W1	4.0	127.9	10.32	97		90
19-May-92	3	18	W1	2.0	123.2	8.73	93		90
19-May-92	4	18	W1	2.0	128.0	9.61	97		90

Page 6


	Test	Sample	(1)	Approximate Elevation Below final Grade	Dry Density	Moisture Content	Percent Relative Compaction (% of Max.		Specified Percent Relative
Date	Number	Name	Location	(ft.)	(pcf)	(% Dry Wt.)	-	Retest	Compaction
NORTHERN ARE	1	IB	W2	2.0	125.2	7.87	95		90
29-May-92 29-May-92	2 3	18 18	W2 W2	2.0 2.0	115.1 117.0	9.17 9.71	87 89		90 90
29-May-92 29-May-92	4 5	81 81	M5 M5	2.0 2.0	118.4 119.2	7.96 9.66	90 90		90 90
29-May-92 29-May-92	6 7	IB IB	W2 W2	2.0 2.0	122.3 121.5	8.51 7.51	9 3 92	retest of a	
29-May-92	8	18	W2	2.0	119.6	9.72	91	retest of	4 90

^{*} All tests conducted in the field by a Levine-Fricke geotechnical engineer using a nuclear density/moisture testing instrument after lifts of fill were placed, moisture conditioned, and compacted. Soils were placed in thin lifts not to exceed 8 inches.

^{**} Backfill compacted to engineering fill depth (1.5 ft bgs).

⁽¹⁾ See Table C-1 for explanation of sample type.

⁽²⁾ Refers to compaction curve only.



Field and Laboratory Compaction Test Curves

ឆ្ទៈ 4ៈឆ្ ながしょがしゅう はらて

189	,	T	
			-


CONSTRUCTION MATERIALS TESTING, INC.

11 . 5	Job No
Job Name: 4030 Hours	Sample No:
Sample Description:	Date: <u>8.9.9</u> /
Source:	Sampled: CC Tested: 43 74
Client No:	


COMPACTION CURVE

% Retained		./	- 7	0	Group Symbol:
Trial No.		- 7			4" MOLD
Wet Weight	1834	1865	1856	1825	Wet Den. = .06614 x Wet Wt.
Wet Den.					Dry Den. = Wt Den. 100 + % H ₂ O
Dry Weight	1566	,	A Share	66	e Molò
Moisture					Wet Den. = .02839 x Wet Wit
% Moisture		The second secon			Dry Den. = Wt Den.
Dry Den.		المدوري مرويته			

Sammle



MOISTURE RANGE	LAB DATA
10W high 95% 13.6 24.0 90% 11.5 27.5 85% 9.9 31.5 80% 8.5 35.9	dens mois 1 102.9 17.9 2 102.6 20.2 3 100.0 22.8 4 97.0 24.5



08-12-91 MON 08:4:


CONSTRUCTION MATERIALS TESTING, INC.

W. C.	Job No. <u>90353</u>
Job Name: 4030 Hocc (5)7	Sample No: 2
Sample Description: LTOL BR CLSO	Date: 8-9.91
Source: TEST PIT THE LEGISLATION OF THE STREET PIT	Sampled: BC Tested: C
Client No:	


COMPACTION CURVE

% Retained		0	+50	+100	Group Symbol:
nai ivo.	-50	-		·····	4" MOLD
Net Weight	1826	1938	1977	1944	Wet Den. = .06614 x Wet Wt.
Wet Den.					Dry Den. = Wt Den. 100 + % H ₂ O
Dry Weight	1661	1721	1725	1664	e MOLD
Moisture					Wet Den. = .02839 x Wet Wt.
% Moisture					Dry Den. = Wt Den. 100 + % H ₂ O
Dry Den.			1.00		\$ 14

Sample



MOISTURE RANGE	LAB DATA
10W hish	dens mais
95% 10.1 17.4	1. 109.9 9.9
98% 8.7 20.6	2. 113.8 12.6
85% 7.6 24.1	3. 114.1 14.6
80% 6.7 28.1	4. 110.1 16.8






CONSTRUCTION MATERIALS TESTING, INC.


Job Name: 403 Hollis	· 5+	Job No 90353
Sample Description: o/ BR~		Sample No: 3
Source: stock o, h		Date: 8-30-5/
Client No:		Sampled: BC Tested: 45 m.
	COMPACTION CURVE	
% Retained on 2/4".	ACTM DIEET A (48 14)	

70 T Ctallies	1 011 0/4 .	ASTNID	1337 A 74" ma	old) ASIM D	1557 B C or D (6" mold)
Trial No.	٥	+50	fioo	+150	Group Symbol:
Wet Weight	1922	2001	2003	1976	4" MOLD
Wet Den.					- Wet Den. = .06614 x Wet Wt.
Dry Weight	1724	1770	1734	1680	Dry Den. = <u>Wt Den.</u> 100 + % H ₂ O
Moisture		1	7	76 00	6" MOLD
% Moisture	,	:			Wet Den. = .02939 x Wet Wt. Dry Den. = <u>Wt Den.</u> 100 + % H ₂ O
Dry Den.					100 + % H ₂ O

Sample



MOISTURE RANGE	LAB DATA
low high 95% 10.8 17.3 90% 9.5 20.4 85% 8.6 23.9 80% 7.8 27.8	dens mois 1. 114.0 11.5 2. 117.1 13.1 3. 114.7 15.5 4. 111.1 17.6



Boring No. : AP-1

Sample No. : AP-1


Tested by : R. TARAYA

Fileneme : LFAP-1

Project : LEVINE FRICKE 2035 YERBA BUENA-RANSOME BACKFILL

Project No.: 16148A Location: YERBA BEUNA Date: Tue Jul 23 1991

COMPACTION



Sample Description

Compaction Test Designation

Maximum Dry Density

Optimum Moisture Content

: GRAY BROWN GRAVELLY SANDY CLAY

: ASTM D1557-C

: 123.5 PCF

: 10.7 %

Filename : LFAP-1 Elevation :

Tested by : R. TARAYA

Checked by : S. CAPPS

Tue Jul 23 09:10:19 1991

Page : 1

GEOTECHNICAL LABORATORY TEST DATA

Project : LEVINE FRICKE 2035 YERBA BUENA-RANSOME BACKFILL

Project No. : 16148A

Baring No. : AP-1 Sample No. : AP-1

Test Date : 07/22/91 Test Nethod : 01557-780

Location : YERBA BEUNA

Soil Description 1 GRAY EROWN GRAVELLY SANDY CLAY

COMPACTION TEST

Hold ID

: ASTM D1557-C Hethod Used Valume of Hold : 0.0751 ft^3 Maps of Hold : 2769.8 gm

: 2

Specific Gravity : 2.7

Moisture Content ID	Mass of Container (gm)	Mass of Container + Moist Boil (BM)	Mass of Container + Dry Seil (gm)	+ Specimen + Specimen (am)	Content (%)	Density (PCF)
	-44000					
	0.00	4112.30	3889.40	6679.10	5.7	114.1
	0.00	4496.80	4137.10	7261.10	8.7	121.3
	0.00	4674.80	4187.90	7441.60	11.6	122.9
	0.00	4438.90	38 73 .40	7214,60	14.6	113.9

= 123.5 PCF Optimum Dry Density Optimum Maisture Content # 10.7 %

Baring No. : 1

Sample No.: 1

Tested by : S. CAPPS


Filename : 1649-01 Project : LEVINE FRICKE 1649.01

Project No.: 16148A

Location:

Date: Tue Oct 15 1991





Sample Description

: BROWN CLAYEY SAND TO SANDY CLAY WITH SMALL GRAVEL

Compaction Test Designation

: ASTM D1557-A

Maximum Dry Density

: 129.8 PCF

Optimum Moisture Content

: 9.0 %

Figure 1

Tue Oct 15 08:08:13 1991

Page: 1

GEOTECHNICAL LABORATORY TEST DATA

Project : LEVINE FRICKE 1649.01

Project No.: 16148A

Depth:

Filename : 1649-01 Elevation :

Boring No. : 1 Sample No. : 1 Test Date : 10/14/91 Test Method : D1557-78A

Tested by : S. CAPPS Checked by : C. WASON

Location:

Soil Description : BROWN CLAYEY SAND TO SANDY CLAY WITH SMALL GRAVEL

Remarks:

COMPACTION TEST

Mold ID : 1

Method Used : ASTM D1557-A
Volume of Mold : 0.0333 ft^3
Mass of Mold : 1882.1 gm
Specific Gravity : 2.7

Moisture Content ID	Mass of Container (gm)	Mass of Container + Moist Soil (gm)	Mass of Container + Dry Soil (gm)	Mass of Mold + Specimen (gm)	Moisture Content (%)	Dry Density (pcf)
	0.00	1882.40	1797.10	3766.60	4.7	119.1.
	0.00	2073.70	1930.80	3958.90	7.4	128.0
	0.00	2141.70	1936.20	4025.00	10.6	128.3
	0.00	2022.10	1779.70	3923.00	13.6	118.9

Optimum Dry Density = 129.8 pcf Optimum Moisture Content = 9.0 %

Boring No. : BACKFILL

Sample No. : STOCKPILE

Tested by : D. WEBER

Filename : BACKFILL


Project : LEVINE FRICKE 1649.07

Project No.: 16148A

Location: YERBA BUENA-RANSONE

Date: Thu Dec 05 1991

COMPACTION



Sample Description

: BROWN SANDY CLAY

Compaction Test Designation

: ASTM D1557-A

Maximum Dry Density

: 122.9 PCF -

Optimum Moisture Content

: 11.5 %

Figure 1

Thu Dec 05 08:58:07 1991

Page: 1

GEOTECHNICAL LABORATORY TEST DATA

Project : LEVINE FRICKE 1649.07 Project No. : 16148A Boring No. : BACKFILL Sample No. : STOCKPILE Location : YERBA BUENA-RANSONE

Soil Description : BROWN SANDY CLAY

Remarks :

Depth: Test Date : 12/04/91

Test Method: D1557-78A

Filename : BACKFILL

Elevation:

Tested by : D. WEBER Checked by : S. CAPPS

COMPACTION TEST

Mold ID : 1

Method Used : ASTM 01557-A Volume of Mold : 0.0333 ft^3 Mass of Mold : 1888.3 gm Specific Gravity : 2.7

Moisture	Mass of	Mass of Container	Mass of Container	Mass of Mold
Content	Container	+ Moist Soil	+ Dry Soil	+ Specimen
ID	(gm)	(gm)	(gm)	(gm)
	0.00	1840.50	1702.80	3722.40
	0.00	2061.40	1857.80	3942.90
	0.00	2038.60	1784.90	3920.40

1840.50 2061.40 2038.60 0.00 Optimum Dry Density = 122.9 PCF Optimum Moisture Content = 11.5 %

Moisture Dry Content Density (%) (PCF)

112.3 122.6 8.1 11.0 14.2 117.8

Boring No. : COLMA

Sample No. : COLMA Tested by : C. WASON


Filename : COLMA

Project : LEVINE FRICKE LF 1649.07

Project No.: 16148A Location : COLMA

Date: Wed Feb 05 1992

COMPACTION



Sample Description

Compaction Test Designation

Maximum Dry Density

Optimum Moisture Content

: GRAY BROWN CLAYEY GRAVELLY SILTY SAND

: ASTM D1557-C

: 132.0 PCF

: 7.9 %

Wed Feb 05 07:54:58 1992

Page: 1

GEOTECHNICAL LABORATORY TEST DATA

Project : LEVINE FRICKE LF 1649.07

Project No.: 1614BA

Depth:

Filename : COLMA

h: Elevation:

Test Date: 02/04/92 Tested by: C. WASON
Test Method: D1557-78C Checked by: C. CAPPS

Sample No. : COLMA Location : COLMA

Boring No. : COLMA

Soil Description : GRAY BROWN CLAYEY GRAVELLY SILTY SAND

Remarks:

COMPACTION TEST

Motd ID

Method Used

: 2

: ASTM D1557-C

Volume of Mold : 0.0751 ft³
Mass of Mold : 2755.3 gm

Specific Gravity: 2.7

Moisture	Mass of	Mass of Container	Mass of Container	Mass of Mold	Moisture	Dry
Content	Container	+ Moist Soil	+ Dry Soil	+ Specimen	Content	Density
ID	(gm)	(gm)	(gm)	(gm)	(%)	(PCF)
	0.00	3959.80	3784.40	7126.80	4.6	122.6
	0.00	4783.20	4449.90	7582.00	7.5	131.8
	0.00	4785.90	4335.80	7556.70	10.4	127.7

Optimum Dry Density = 132.0 PCF Optimum Moisture Content = 7.9 %

APPENDIX D

REMEDIATION CERTIFICATE AND CERTIFICATES OF ANALYSIS PORT COSTA MATERIALS, PORT COSTA, CALIFORNIA

Port Costa Materials, Inc. Sutter Square 1800 Sutter Street, Suite 570 Concord, CA 94520

415/602-1200 800/323-2922 Fax: 415/687-1848

AQUA RESOURCES, INC RECEIVED

JAN 2 1 1992

IOB I	VO	
FILE		

January 17, 1992

Certified Mail Return Receipt Requested

Aqua Resources 2030 Addison Street Berkeley, CA 94704

Enclosed is the Remediation Certificate for Lot #000151A, Ransome Company, 4030 Hollis Street, Emeryville, California.

Also included are the Certificates of Analysis from an Independent Laboratory indicating no detectable hydrocarbons in the remediated product.

Dusaw King.

Susan King Admin. Assist.

CERTIFICATE

Remediation of Hydrocarbon Contaminated Soils

Supplier:

Generator:

Certificate Number: 0110 Dated: January 16, 1992

Aqua Resources 2030 Addison Street Berkeley, CA 94704 Ransome Co. 4030 Bollis Street Emeryville, California

PORT COSTA MATERIALS, INC., a California corporation ("Company"), located at and the operator of the above "Facility" hereby certifies as follows:

- 1. The Company has received from the above "Generator" Ransome Co., 3,698.88 tons of hydrocarbon contaminated soil ("AC \Soil") as transported by or on behalf of Generator by Aqua Resources, contracted through H & K Grading Contractors to such facility, and referred to as lot number 000151A, which EC Soil was received at the Facility on August 1 through 23, 1991, (as part of a shipment consisting of 6,990.4 tons in total). The Company operates its Facility and processes such EC Soil pursuand to permits issued by applicable governmental authorities.
- 2. In receiving and processing the HC Soil and in providing this Certificate, the Company has relied upon and is relying on (a) the representation of the Generator that the HC Soil does not contain any materials classified as, and is not classified as. "hazardous waste" under the applicable provisions of the Federal and California law and has been managed and may be treated as other than "hazardous waste" and (b) the Generator has independent written certifications from applicable governmental agencies or certified independent testing laboratories that the HC Soil does not contain any materials classified as, and is not classified as, "hazardous waste" under said applicable law.
- 3. The HC Soil has been treated by being introduced into the manufacturing process at the Pacility (in which it may be blended with a mixture of natural shale) feeding into a rotary kiin in which at high temperature the contaminants are consumed by chernal processing and inert materials are produced. The HC Soil was processed in this manner during the periods of October 9, 1991, October 11 through 26, 1991 and November 8 thru 10, 1991, and all of the HC Soil covered by this Certificate was completely processed on November 10, 1991. In the treatment of the HC Soil, releases and emissions have been in accordance with the requirements of the applicable operating permits of the Facility.
- 4. Upon completion of the treatment, the HC Soil has been remediated, and the end product is an inert substance which does not constitute a "hazardous waste" under the applicable provisions of the Federal and California law.
- 5. The Company shall indemnify, defend and hold harmless the Generator from and against any enforcement actions by any governmental authority in the event that any of the representations by the Company set forth in this Certificate are naterially inaccurate.

This Certificate is executed on this 16th day of January, 1992

PORT COSTA MATERIALS, INC.

By:

Vice President Operations



Superior Precision Analytical, Inc.

825 Arnold Drive, Suite 114 • Martinez, California 94553 • (510) 229-1512 / fax (510) 229-1526

CERTIFICATE OF ANALYSIS

LABORATORY NO.: 84365

CLIENT: Port Costa Materials CLIENT JOB NO.: 11/08/91

DATE RECEIVED: 11/13/91 DATE REPORTED: 11/20/91 DATE SAMPLED: 11/08/91

ANALYSIS FOR TOTAL PETROLEUM HYDROCARBONS by Modified EPA SW-846 Method 8015

LAB		Concentration (mg/Kg)				
#	Sample Identification	Gasoline Range	Diesel Range			
1	0400	ND<10	ND<10			
2	0800	ND<10	ND<10			
3	1200	ND<10	ND<10			
4	2400	ND<10	ND<10			

mg/Kg - parts per million (ppm)

Method Detection Limit for Gasoline in Soil: 10 mg/Kg Method Detection Limit for Diesel in Soil: 10 mg/Kg

QAQC Summary:

Daily Standard run at 200mg/L: RPD Gasoline = 1 % RPD Diesel = 12 % MS/MSD Average Recovery =110/107 %: Duplicate RPD = 3

Richard Srna, Ph.D.

Laboratory Director

Certified Laboratories



825 Arnold Drive, Suite 114 • Martinez, California 94553 • (510) 229-1512 / fax (510) 229-1526

CERTIFICATE OF ANALYSIS

LABORATORY NO.: 84365

CLIENT: Port Costa Materials

CLIENT JOB NO.: 11/08/91

DATE RECEIVED:11/13/91
DATE REPORTED:11/20/91

DATE SAMPLED :11/08/91

ANALYSIS FOR TOTAL OIL AND GREASE by STANDARD METHODS 5520F

LAB #	Sample Identification	Concentration(mg/Kg) Oil & Grease
		and their was then some ones was been often about about their similar some
1	0400	ND<50
2	0800	ND<50
3	1200	ND<50
4	2400	ND<50

mg/kg - parts per million (ppm)

Method Detection Limit for Oil and Grease in Soil: 50 mg/Kg

QAQC Summary: MS/MSD Average Recovery: 96%

Duplicate RPD: 0

Richard Srna, Ph.D.



825 Arnold Drive, Suite 114 • Martinez, California 94553 • (510) 229-1512 / fax (510) 229-1526

CERTIFICATE OF ANALYSIS

LABORATORY NO.: 84366

CLIENT: Port Costa Materials

CLIENT JOB NO.: 11/09/91

DATE RECEIVED: 11/13/91

DATE REPORTED: 11/20/91

DATE SAMPLED : 11/09/91

ANALYSIS FOR TOTAL PETROLEUM HYDROCARBONS by Modified EPA SW-846 Method 8015

LAB		Concentration (mg/Kg)	
#	Sample Identification	Gasoline Range	Diesel Range
1	0400	ND<10	ND<10
2	0800	ND<10 .	ND<10
3	1200	ND<10	ND<10
4	1600	ND<10	ND<10
5	2000	ND<10	ND<10
6	2400	ND<10	ND<10

mg/Kg - parts per million (ppm)

Method Detection Limit for Gasoline in Soil: 10 mg/Kg Method Detection Limit for Diesel in Soil: 10 mg/Kg

QAQC Summary:

Daily Standard run at 200mg/L: RPD Gasoline =12

RPD Diesel = 1

MS/MSD Average Recovery =110/107 %: Duplicate RPD =3

Richard Srna, Ph.D.



825 Arnold Drive, Suite 114 • Martinez, California 94553 • (510) 229-1512 / fax (510) 229-1526

CERTIFICATE OF ANALYSIS

LABORATORY NO.: 84366

CLIENT: Port Costa Materials

CLIENT JOB NO.: 11/09/91

DATE RECEIVED:11/13/91 DATE REPORTED:11/20/91

DATE SAMPLED : 11/09/91

ANALYSIS FOR TOTAL OIL AND GREASE by STANDARD METHODS 5520F

LAB · #	Sample Identification	Concentration(mg/Kg) Oil & Grease
1	0400	ND<50
2	0800	ND<50
3	1200	ND<50
4	1600	ND<50
5	2000	ND<50
6	2400	ND<50

mg/kg - parts per million (ppm)

Method Detection Limit for Oil and Grease in Soil: 50 mg/Kg

QAQC Summary: MS/MSD Average Recovery:96/96%

Duplicate RPD:0

Richard Srna, Ph.D.

Aaboratory Director



825 Arnold Drive, Suite 114 • Martinez, California 94553 • (510) 229-1512 / fax (510) 229-1526

CERTIFICATE OF ANALYSIS

LABORATORY NO.: 84367

CLIENT: Port Costa Materials

CLIENT JOB NO.: 11/10/91

DATE RECEIVED: 11/13/91

DATE REPORTED: 11/20/91

DATE SAMPLED : 11/10/91

ANALYSIS FOR TOTAL PETROLEUM HYDROCARBONS by Modified EPA SW-846 Method 8015

LAB		Concentration (mg/Kg)	
· #	Sample Identification	Gasoline Range	Diesel Range
1	0400	ND<10	ND<10
2	0800	ND<10	ND<10
3	1200	ND<10	ND<10
4	1600	ND<10	ND<10
5	2000	ND<10	ND<10
6	2400	ND<10	ND<10

mg/Kg - parts per million (ppm)

Method Detection Limit for Gasoline in Soil: 10 mg/Kg Method Detection Limit for Diesel in Soil: 10 mg/Kg

QAQC Summary:

Daily Standard run at 200mg/L: RPD Gasoline = 12

RPD Diesel = 1

MS/MSD Average Recovery = 110/107%: Duplicate RPD = 3

Richard Srna, Ph.D.

Laboratory Director



825 Arnold Drive, Suite 114 • Martinez, California 94553 • (510) 229-1512 / fax (510) 229-1526

CERTIFICATE OF ANALYSIS

LABORATORY NO.: 84367

CLIENT: Port Costa Materials CLIENT JOB NO.: 11/10/91

DATE RECEIVED: 11/13/91 DATE REPORTED: 11/20/91 DATE SAMPLED :11/10/91

ANALYSIS FOR TOTAL OIL AND GREASE by STANDARD METHODS 5520F

LAB · #	Sample Identification	Concentration(mg/Kg) Oil & Grease
1	0400	ND<50
2	0800	ND<50
3	1200	ND<50
4	1600	ND<50
5	2000	ND<50
6	2400	ND<50

mg/kg - parts per million (ppm)

Method Detection Limit for Oil and Grease in Soil: 50 mg/Kg

QAQC Summary: MS/MSD Average Recovery: 64/65%

Duplicate RPD: 2

Richard Srna, Ph.D.

825 Arnold Drive, Suite 114 • Martinez, California 94553 • (510) 229-1512 / fax (510) 229-1526

CERTIFICATE OF ANALYSIS

LABORATORY NO.: 84108

CLIENT: Port Costa Materials

CLIENT JOB NO.: 10/10/91

DATE RECEIVED: 10/11/91

DATE REPORTED: 10/18/91 DATE SAMPLED: 10/10/91

σ

ANALYSIS FOR TOTAL PETROLEUM HYDROCARBONS by Modified EPA SW-846 Method 8015

# 	Sample Identification	Concentratio Gasoline Range	n (mg/Kg) Diesel Range
1	10/10/91 1600	ND <10	ND <10

mg/Kg - parts per million (ppm)

Method Detection Limit for Gasoline in Soil: 10 mg/Kg Method Detection Limit for Diesel in Soil: 10 mg/Kg

QAQC Summary:

Daily Standard run at 200mg/L: RPD Gasoline = 3

RPD Diesel = 12

MS/MSD Average Recovery = 93%: Duplicate RPD = 4

Richard Srna, Ph.D.



825 Arnold Drive, Suite 114 • Martinez, California 94553 • (510) 229-1512 / fax (510) 229-1526

CERTIFICATE OF ANALYSIS

LABORATORY NO.: 84108

CLIENT: Port Costa Materials

CLIENT JOB NO.: 10/10/91

DATE RECEIVED:10/11/91
DATE REPORTED:10/18/91
DATE SAMPLED: 10/18/91

59

ANALYSIS FOR TOTAL OIL AND GREASE by STANDARD METHODS 5520F

LAB # 	Sample Identification	Concentration(mg/kg) Oil & Grease	
1	10/10/91 1600	ND <50	

mg/Kg - parts per million (ppm)

Method Detection Limit for Oil and Grease in Soil: 50 mg/Kg

QAQC Summary: MS/MSD Average Recovery: 84%

Duplicate RPD: 0

Richard Srna, Ph.D.



825 Arnold Drive, Suite 114 • Martinez, California 94553 • (510) 229-1512 / fax (510) 229-1526

CERTIFICATE OF ANALYSIS

LABORATORY NO.: 84121

CLIENT: Port Costa Materials CLIENT JOB NO.: 10/11/91

DATE RECEIVED: 10/14/91 DATE REPORTED: 10/18/91 DATE SAMPLED: 10/11/91

ANALYSIS FOR TOTAL OIL AND GREASE by STANDARD METHODS 5520F

LAB # 	Sample Identification	Concentration (mg/Kg) Oil & Grease	
1	1200	ND<50	
2	1600	ND<50	
3	2000	ND<50	

mg/Kg - parts per million (ppm)

Method Detection Limit for Oil and Grease in Soil: 50 mg/Kg

QAQC Summary: MS/MSD Average Recovery: 76/71%

Duplicate RPD: 7

Richard Srna, Ph.D.

825 Arnold Drive, Suite 114 • Martinez, California 94553 • (510) 229-1512 / fax (510) 229-1526

CERTIFICATE OF ANALYSIS

LABORATORY NO.: 84121

CLIENT: Port Costa Materials

CLIENT JOB NO.: 10/11/91

DATE RECEIVED: 10/14/91

DATE REPORTED: 10/18/91 DATE SAMPLED: 10/11/91

ANALYSIS FOR TOTAL PETROLEUM HYDROCARBONS by Modified EPA SW-846 Method 8015

LAB		Concentration (mg/Kg)		
#	Sample Identification	Gasoline Range	Diesel Range	
1	1200	ND<10	ND< 1 0	
2	1600	ND<10	ND<10	
3	2000	ND<10	ND< 10	

mg/Kg - parts per million (ppm)

Method Detection Limit for Gasoline in Soil: 10 mg/Kg Method Detection Limit for Diesel in Soil: 10 mg/Kg

QAQC Summary:

Daily Standard run at 200mg/L: RPD Gasoline = 3

RPD Diesel = 12

MS/MSD Average Recovery = 95/91%: Duplicate RPD = 4

Richard Srna, Ph.D.

Laboratory Director



825 Arnold Drive, Suite 114 • Martinez, California 94553 • (510) 229-1512 / fax (510) 229-1526

CERTIFICATE OF ANALYSIS

LABORATORY NO.: 84120

CLIENT: Port Costa Materials

CLIENT JOB NO.: 10/12/91

DATE RECEIVED: 10/14/91

DATE REPORTED: 10/21/91 DATE SAMPLED: 10/12/91

ANALYSIS FOR TOTAL PETROLEUM HYDROCARBONS by Modified EPA SW-846 Method 8015

LAB		Concentration (mg/kg)		
#	Sample Identification	Gasoline Range	Diesel Range	
1	0400	ND <10	ND <10	
2	0800	ND <10	ND <10	
3	1200	ND <10	ND <10	
4	1600	ND <10	ND <10	
5	2400	ND <10	ND < 10.	

mg/Kg - parts per million (ppm)

Method Detection Limit for Gasoline in Soil: 10 mg/Kg Method Detection Limit for Diesel in Soil: 10 mg/Kg

QAQC Summary:

Daily Standard run at 200mg/L: RPD Gasoline = 2

RPD Diesel = 9

MS/MSD Average Recovery = 95%: Duplicate RPD = 2

Richard Srna, Ph.D.



825 Arnold Drive, Suite 114 • Martinez, California 94553 • (510) 229-1512 / fax (510) 229-1526

CERTIFICATE OF ANALYSIS

LABORATORY NO.: 84120

CLIENT: Port Costa Materials

CLIENT JOB NO.: 10/12/91

DATE RECEIVED:10/14/91
DATE REPORTED:10/21/91
DATE SAMPLED: 10/12/91

ANALYSIS FOR TOTAL OIL AND GREASE by STANDARD METHODS 5520F

LAB #	Sample Identification	Concentration(mg/Kg) Oil & Grease
1	0400	ND <50
2	0800	ND <50
3	1200	ND <50
4	1600	ND <50
5	2400	ND <50

mg/Kg - parts per million (ppm)

Method Detection Limit for Oil and Grease in Soil: 50 mg/Kg

QAQC Summary: MS/MSD Average Recovery: 68%

Duplicate RPD: 7

Richard Srna, Ph.D.



825 Arnold Drive, Suite 114 • Martinez, California 94553 • (510) 229-1512 / fax (510) 229-1526

CERTIFICATE OF ANALYSIS

LABORATORY NO.: 84119

CLIENT: Port Costa Materials CLIENT JOB NO.: 10/13/91

DATE RECEIVED: 10/14/91 DATE REPORTED: 10/21/91 DATE SAMPLED: 10/13/91

ANALYSIS FOR TOTAL PETROLEUM HYDROCARBONS by Modified EPA SW-846 Method 8015

LAB		Concentration (mg/Kg)	
#	Sample Identification	Gasoline Rang	e Diesel Range
1	0400	ND <10	ND <10
2	0800	ND <10	ND <10
3	1200	ND <10	ND <10
4	1600	ND <10	ND <10
5	2000	ND <10	ND <10
6	2400	ND <10	ND ∢ 10

mg/Kg - parts per million (ppm)

Method Detection Limit for Gasoline in Soil: 10 mg/Kg Method Detection Limit for Diesel in Soil: 10 mg/Kg

QAQC Summary:

Daily Standard run at 200mg/L: RPD Gasoline = 3

RPD Diesel = 12

MS/MSD Average Recovery = 93%: Duplicate RPD = 4

Richard Srna, Ph.D.



825 Arnold Drive, Suite 114 - Martinez, California 94553 - (510) 229-1512 / fax (510) 229-1526

CERTIFICATE OF ANALYSIS

LABORATORY NO.: 84119

CLIENT: Port Costa Materials

CLIENT JOB NO.: 10/13/91

DATE RECEIVED: 10/14/91 DATE REPORTED: 10/21/91 DATE SAMPLED: 10/13/91

ANALYSIS FOR TOTAL OIL AND GREASE by STANDARD METHODS 5520F

LAB		Concentration(mg/Kg)
#	Sample Identification	Oil & Grease

1	0400	ND <50
2	0800	ND <50
3	1200	ND <50
4	1600	ND <50
5	2000	ND <50
6	2400	ND <50

mg/Kg - parts per million (ppm)

Method Detection Limit for Oil and Grease in Soil: 50 mg/Kg

QAQC Summary: MS/MSD Average Recovery: 68%

Duplicate RPD: 7

Richard Srna, Ph.D.



825 Arnold Drive, Suite 114 • Martinez, California 94553 • (510) 229-1512 / fax (510) 229-1526

CERTIFICATE OF ANALYSIS

LABORATORY NO.: 84127

CLIENT: Port Costa Materials

CLIENT JOB NO.: 10/14/91

DATE RECEIVED: 10/15/91 DATE REPORTED: 10/21/91

DATE SAMPLED : 10/14/91

ANALYSIS FOR TOTAL PETROLEUM HYDROCARBONS by Modified EPA SW-846 Method 8015

LAB		Concentra	tion (mg/Kg)
#	Sample Identification	Gasoline Range	Diesel Range
1	0400	ND <10	ND <10
2	0800	ND <10	ND K10
3	1200	ND <10	ND K10
4	200	ND <10	ND K10
5	2000	ND <10	ND <10

mg/Kg - parts per million (ppm)

Method Detection Limit for Gasoline in Soil: 10 mg/Kg Method Detection Limit for Diesel in Soil: 10 mg/Kg

QAQC Summary:

Daily Standard run at 200mg/L: RPD Gasoline = 3

RPD Diesel = 12

MS/MSD Average Recovery = 93%: Duplicate RPD = 4

Richard Srna, Ph.D.



825 Arnold Drive, Suite 114 • Martinez, California 94553 • (510) 229-1512 / fax (510) 229-1526

CERTIFICATE OF ANALYSIS

LABORATORY NO.: 84127

CLIENT: Port Costa Materials

CLIENT JOB NO.: 10/14/91

DATE RECEIVED:10/15/91 DATE REPORTED: 10/21/91 DATE SAMPLED: 10/14/91

ANALYSIS FOR TOTAL OIL AND GREASE by STANDARD METHODS 5520F

LAB #	Sample Identification	Concentration(mg/Kg) Oil & Grease
		حدة هند عدد عدد مدد نده هند هده هد مدد عدد مدد عدد مدد
1	0400	ND <50
2	0800	ND <50
3	1200	ND <50
4	200	ND <50
5	2000	ND <50

mg/Kg - parts per million (ppm)

Method Detection Limit for Oil and Grease in Soil: 50 mg/Kg

QAQC Summary: MS/MSD Average Recovery: 68%

Duplicate RPD: 7

Richard Srna, Ph.D.



CERTIFICATE OF ANALYSIS

LABORATORY NO.: 84143 CLIENT: Port Costa Materials CLIENT JOB NO.: 10/15/91 DATE RECEIVED: 10/16/91 DATE REPORTED: 10/28/91 DATE SAMPLED: 10/15/91

ANALYSIS FOR TOTAL PETROLEUM HYDROCARBONS by Modified EPA SW-846 Method 8015

LAB		Concentrati	on (mg/Kg)
- #	Sample Identification	Gasoline Range	Diesel Range
1	10/15/91 0400	ND <10	ND <10
2	10/15/91 0800	ND <10	ND < 10
3	10/15/91 1200	ND <10	ND <10
4	10/15/91 1600	ND <10	ND <10
5	10/15/91 2000	ND <10	ND < 10
6	10/15/91 2400	ND <10	ND <10

mg/Kg - parts per million (ppm)

Method Detection Limit for Gasoline and Diesel in Soil: 10 mg/Kg QAQC Summary:

Daily Standard run at 200mg/L: RPD Gasoline = 3

RPD Diesel = 2

MS/MSD Average Recovery = 114%: Duplicate RPD = 4

Richard Srna, Ph.D.



825 Arnold Drive, Suite 114 Martinez, California 94553 (510) 229-1512 / fax (510) 229-1526

CERTIFICATE OF ANALYSIS

LABORATORY NO.: 84143

CLIENT: Port Costa Materials

CLIENT JOB NO.: 10/15/91

DATE RECEIVED:10/16/91 DATE REPORTED:10/28/91

DATE SAMPLED :10/15/91

ANALYSIS FOR TOTAL OIL AND GREASE by STANDARD METHODS 5520F

LAB #	Sample Identification	Concentration(mg/Kg) Oil & Grease
1	10/15/91 0400	ND <50
2	10/15/91 0800	ND <50
3	10/15/91 1200	ND <50
4	10/15/91 1600	ND <50
5	10/15/91 2000	ND <50
6	10/15/91 2400	ND <50

mg/Kg - parts per million (ppm)

Method Detection Limit for Oil and Grease in Soil: 50 mg/Kg

QAQC Summary: MS/MSD Average Recovery: 68%

Duplicate RPD: 7

Richard Srna, Ph.D.



825 Arnold Drive, Suite 114 * Martinez, California 94553 * (510) 229-1512 / fax (510) 229-1526

CERTIFICATE OF ANALYSIS

LABORATORY NO.: 84147

CLIENT: Port Costa Materials CLIENT JOB NO.: 10/16/91

DATE RECEIVED: 10/17/91
DATE REPORTED: 10/25/91
DATE SAMPLED: 10/16/91

ANALYSIS FOR TOTAL OIL AND GREASE by STANDARD METHODS 5520F

LAB #	Sample Identification	Concentration(mg/Kg) Oil & Grease
1	1600	ND <50
2	2000	ND <50

mg/Kg - parts per million (ppm)

Method Detection Limit for Oil and Grease in Soil: 50 mg/Kg

QAQC Summary: MS/MSD Average Recovery: 68%

Duplicate RPD: 7

Richard Srna, Ph.D.



825 Arnold Drive, Suite 114 • Martinez, California 94553 • (510) 229-1512 / fax (510) 229-1526

CERTIFICATE OF ANALYSIS

LABORATORY NO.: 84147

CLIENT: Port Costa Materials

CLIENT JOB NO.: 10/16/91

DATE RECEIVED: 10/17/91

DATE REPORTED: 10/25/91

DATE SAMPLED : 10/16/91

ANALYSIS FOR TOTAL PETROLEUM HYDROCARBONS by Modified EPA SW-846 Method 8015

LAB		Concentration	on (mg/kg)
#	Sample Identification	Gasoline Range	Diesel Range
1	1600	ND <10	ND k10
2	2000	ND <10	ND k10

mg/Kg - parts per million (ppm)

Method Detection Limit for Gasoline in Soil: 10 mg/Kg Method Detection Limit for Diesel in Soil: 10 mg/Kg

QAQC Summary:

Daily Standard run at 200mg/L: RPD Gasoline = 3

RPD Diesel = 2

MS/MSD Average Recovery = 114%: Duplicate RPD = 4

Richard Srna, Ph.D.



825 Arnold Drive, Suite 114 • Martinez, California 94553 • (510) 229-1512 / fax (510) 229-1526

CERTIFICATE OF ANALYSIS

LABORATORY NO.: 84158

CLIENT: Port Costa Materials

CLIENT JOB NO.: 10/17/91

DATE RECEIVED: 10/18/91

DATE REPORTED: 10/28/91 DATE SAMPLED: 10/17/91

ANALYSIS FOR TOTAL PETROLEUM HYDROCARBONS by Modified EPA SW-846 Method 8015

L.	AB		Concentrati	on (mg/Kg)
•	#	Sample Identification	Gasoline Range	Diesel Range
-				
	1	0400	ND <10	ND <10
	2	1600	ND <10	ND < 10
	3	2000	ND <10	ND < 10
	4	2400	ND <10	ND <10

mg/Kg - parts per million (ppm)

Method Detection Limit for Gasoline in Soil: 10 mg/Kg Method Detection Limit for Diesel in Soil: 10 mg/Kg

QAQC Summary:

Daily Standard run at 200mg/L: RPD Gasoline = 5

RPD Diesel = 10

MS/MSD Average Recovery = 114%: Duplicate RPD = 4

Richard Srna, Ph.D.



825 Arnold Drive, Suite 114 * Martinez, California 94553 • (510) 229-1512 / fax (510) 229-1526

CERTIFICATE OF ANALYSIS

LABORATORY NO.: 84172

CLIENT: Port Costa Materials

CLIENT JOB NO.: 10/18/91

DATE RECEIVED: 10/21/91 DATE REPORTED: 10/28/91

DATE SAMPLED : 10/18/91

ANALYSIS FOR TOTAL PETROLEUM HYDROCARBONS by Modified EPA SW-846 Method 8015

	LAB		Concentrat	tion (mg/Kg)
•	#	Sample Identification	Gasoline Range	Diesel Range
	1	0400	ND <10	ND <10
	2	0800	ND <10	ND < 10
	3	1200	ND <10	ND < 10
	4	1600	ND <10	ND <10
	5	2000	ND <10	ND <10
	6	2400	ND <10	ND <10

mg/Kg - parts per million (ppm)

Method Detection Limit for Gasoline in Soil: 10 mg/Kg Method Detection Limit for Diesel in Soil: 10 mg/Kg

QAQC Summary:

Daily Standard run at 200mg/L: RPD Gasoline = 5

RPD Diesel = 10

MS/MSD Average Recovery = 117%: Duplicate RPD = 6

Richard Srna, Ph.D.

O

825 Arnold Drive, Suite 114 - Martinez, California 94553 - (510) 229-1512 / fax (510) 229-1526

CERTIFICATE OF ANALYSIS

LABORATORY NO.: 84172

CLIENT: Port Costa Materials

CLIENT JOB NO.: 10/18/91

DATE RECEIVED: 10/21/91

DATE REPORTED: 10/28/91 DATE SAMPLED: 10/18/91

ANALYSIS FOR TOTAL OIL AND GREASE by STANDARD METHODS 5520F

LAB #	Sample Identification	Concentration (mg/Kg) Oil & Grease
~	الله الله الله الله الله الله الله الله	
1	0400	ND <50
2	0800	ND <50
3	1200	ND <50
4	1600	ND <50
5	2000	ND <50
6	2400	ND <50

mg/Kg - parts per million (ppm)

Method Detection Limit for Oil and Grease in Soil: 50 mg/Kg

QAQC Summary: MS/MSD Average Recovery: 78%

Duplicate RPD: 9

Richard Srna, Ph.D.

Laboratory Director



825 Arnold Drive, Suite 114 • Martinez, California 94553 • (510) 229-1512 / fax (510) 229-1526

CERTIFICATE OF ANALYSIS

LABORATORY NO.: 84173

CLIENT: Port Costa Materials

CLIENT JOB NO.: 10/19/91

DATE RECEIVED: 10/21/91

DATE REPORTED: 10/28/91

DATE SAMPLED : 10/19/91

ANALYSIS FOR TOTAL PETROLEUM HYDROCARBONS by Modified EPA SW-846 Method 8015

LAB		Concentration (mg/Kg)	
#	Sample Identification	Gasoline Range Diesel Rang	е
	AB		_
1	0400	ND <10 ND <10	
2	0800	ND <10 ND <10	
3	1200	ND <10 ND <10	
4	1600	ND <10 ND <10	
5	2000	ND <10 ND <10	
6	2400	ND <10 ND <10	

mg/Kg - parts per million (ppm)

Method Detection Limit for Gasoline in Soil: 10 mg/Kg Method Detection Limit for Diesel in Soil: 10 mg/Kg

QAQC Summary:

Daily Standard run at 200mg/L: RPD Gasoline = 10

RPD Diesel = 11

MS/MSD Average Recovery = 108%: Duplicate RPD = 8

Richard Srna, Ph.D.



825 Arnold Drive, Suite 114 • Martinez, California 94553 • (510) 229-1512 / fax (510) 229-1526

CERTIFICATE OF ANALYSIS

LABORATORY NO.: 84173

CLIENT: Port Costa Materials

CLIENT JOB NO.: 10/19/91

DATE RECEIVED: 10/21/91 DATE REPORTED: 10/28/91 DATE SAMPLED: 10/19/91

ANALYSIS FOR TOTAL OIL AND GREASE by STANDARD METHODS 5520F

	LAB		Concentration(mg/Kg)
,	#	Sample Identification	Oil & Grease
			الله مثلة فضا بعد نبية جين مين _{حين وج} ي بين جين بنية فيذ مثلة الله عليه والله عليه الله الله الله الله الله الله
	1	0400	ND <50
	2	0800	ND <50
	3	1200	ND <50
	4	1600	ND <50
	5	2000	ND <50
	6	2400	ND <50

mg/Kg - parts per million (ppm)

Method Detection Limit for Oil and Grease in Soil: 50 mg/Kg

QAQC Summary: MS/MSD Average Recovery: 78%

Duplicate RPD: 9

Richard Srna, Ph.D.



825 Arnold Drive, Suite 114 • Martinez, California 94553 • (510) 229-1512 / fax (510) 229-1526

CERTIFICATE OF ANALYSIS

LABORATORY NO.: 84174

CLIENT: Port Costa Materials

CLIENT JOB NO.: 10/20/91

DATE RECEIVED: 10/21/91

DATE REPORTED: 10/28/91

DATE SAMPLED : 10/20/91

ANALYSIS FOR TOTAL PETROLEUM HYDROCARBONS by Modified EPA SW-846 Method 8015

LAB		Concentration (mg/Kg)		
#	Sample Identification	Gasoline Range	Diesel Range	
1	0400	ND <10	ND <10	
2	1600	ND <10	ND < 10	
3	2000	ND <10	ND <10	
4	2400	ND <10	ND <10	

mg/Kg - parts per million (ppm)

Method Detection Limit for Gasoline in Soil: 10 mg/Kg Method Detection Limit for Diesel in Soil: 10 mg/Kg

QAQC Summary:

Daily Standard run at 200mg/L: RPD Gasoline = 5

RPD Diesel = 10

MS/MSD Average Recovery = 117%: Duplicate RPD = 6

Richard Srna, Ph.D.



825 Arnold Drive, Suite 114 • Martinez, California 94553 • (510) 229-1512 / fax (510) 229-1526

CERTIFICATE OF ANALYSIS

LABORATORY NO.: 84174

CLIENT: Port Costa Materials

CLIENT JOB NO.: 10/20/91

DATE RECEIVED:10/21/91 DATE REPORTED:10/28/91 DATE SAMPLED: 10/20/91

ANALYSIS FOR TOTAL OIL AND GREASE by STANDARD METHODS 5520F

LAB		Concentration(mg/Kg)
#	Sample Identification	Oil & Grease
1	0400	ND <50
2	1600	ND <50
3	2000	ND <50
4	2400	ND <50

mg/Kg - parts per million (ppm)

Method Detection Limit for Oil and Grease in Soil: 50 mg/Kg

QAQC Summary: MS/MSD Average Recovery: 68%

Duplicate RPD: 7

Richard Srna, Ph.D.



825 Arnold Drive. Suite 114 Martinez, California 94553 (510) 229-1512 / fax (510) 229-1526

CERTIFICATE OF ANALYSIS

LABORATORY NO.: 84583

CLIENT: Port Costa Materials

CLIENT JOB NO.: 10/21/91

DATE RECEIVED: 12/10/91

DATE REPORTED: 12/17/91 DATE SAMPLED: 10/21/91

ANALYSIS FOR TOTAL PETROLEUM HYDROCARBONS by Modified EPA SW-846 Method 8015

LAB		Concentration (mg/kg)		
#	Sample Identification	Gasoline Range	Diesel Range	
1	10/21/91 0400	ND<10	ND<10	
2	10/21/91 2000	ND<10	ND<10	
3	10/21/91 2400	ND<10	ND<10	

mg/kg - parts per million (ppm)

Method Detection Limit for Gasoline in Soil: 10 mg/kg Method Detection Limit for Diesel in Soil: 10 mg/kg

QAQC Summary:

Daily Standard run at 200mg/L: RPD Gasoline = 5

RPD Diesel = 3

MS/MSD Average Recovery = 116%: Duplicate RPD = 0

Richard Srna, Ph.D.

Laboratory Director



825 Arnold Orive, Suite 114 = Martinez, California 94553 = (510) 229-1512 / fax (510) 229-1526

CERTIFICATE OF ANALYSIS

LABORATORY NO.: 84583

CLIENT: Port Costa Materials

CLIENT JOB NO.: 10/21/91

DATE RECEIVED:12/10/91 DATE REPORTED:12/17/91 DATE SAMPLED: 10/21/91

ANALYSIS FOR TOTAL OIL AND GREASE by STANDARD METHODS 5520F

Sample Identification	Concentration(mg/kg) Oil & Grease	
10/21/91 0400	ND<50	
10/21/91 2000	ND<50	
10/21/91 2400	ND<50	
	10/21/91 0400 10/21/91 2000	

mg/kg - parts per million (ppm)

Method Detection Limit for Oil and Grease in Soil: 50 mg/kg

QAQC Summary: MS/MSD Average Recovery: 67/65%

Duplicate RPD: 3

Richard Srna, Ph.D.

Spaneh Salimpourfor Alaboratory Director



825 Arnold Drive, Suite 114 • Martinez, California 94553 • (510) 229-1512 / fax (510) 229-1526

CERTIFICATE OF ANALYSIS

LABORATORY NO.: 84185

CLIENT: Port Costa Materials CLIENT JOB NO.: 10/22/91

DATE RECEIVED: 10/23/91 DATE REPORTED: 11/02/91

DATE SAMPLED : 10/22/91

ANALYSIS FOR TOTAL OIL AND GREASE by STANDARD METHODS 5520F

LAB #	Sample Identification	Concentration (mg/Kg) Oil & Grease	
1	0800	ND <50	
2	1200	ND <50	
3	1600	ND <50	
4	2000	ND <50	
5	2400	ND <50	

mg/Kg - parts per million (ppm)

Method Detection Limit for Oil and Grease in Soil: 50 mg/Kg

QAQC Summary: MS/MSD Average Recovery: 78%

Duplicate RPD: 9

Richard Srna, Ph.D.

Laboratory Director



825 Arnold Drive, Suite 114 Martinez, California 94553 (510) 229-1512 / fax (510) 229-1526

CERTIFICATE OF ANALYSIS

LABORATORY NO.: 84185

CLIENT: Port Costa Materials

CLIENT JOB NO.: 10/22/91

DATE RECEIVED: 10/23/91

DATE REPORTED: 11/02/91 DATE SAMPLED: 10/22/91

ANALYSIS FOR TOTAL PETROLEUM HYDROCARBONS by Modified EPA SW-846 Method 8015

LAB		Concentration (mg/Kg)		
#	Sample Identification	Gasoline Range	Diesel Range	
1	0800	ND <10	ND €10	
2	1200	ND <10	ND <10	
3	1600	ND <10	ND <10	
4	2000	ND <10	ND <10	
5	2400	ND <10	ND <10	

mg/Kg - parts per million (ppm)

Method Detection Limit for Gasoline in Soil: 10 mg/Kg Method Detection Limit for Diesel in Soil: 10 mg/Kg

QAQC Summary:

Daily Standard run at 200mg/L: RPD Gasoline = 14

RPD Diesel = 4

MS/MSD Average Recovery = 114%: Duplicate RPD = 3

Richard Srna, Ph.D.

Laboratory Director

825 Arnold Drive, Suite 114 - Martinez, California 94553 - (510) 229-1512 / fax (510) 229-1526

CERTIFICATE OF ANALYSIS

LABORATORY NO.: 84197

CLIENT: Port Costa Materials

CLIENT JOB NO.: 10/23/91

DATE RECEIVED: 10/24/91

DATE REPORTED: 11/04/91 DATE SAMPLED: 10/23/91

ANALYSIS FOR TOTAL OIL AND GREASE by STANDARD METHODS 5520F

LAB # 	Sample Identification	Concentration (mg/Kg) Oil & Grease
1	0400	ND <50
ż	0800	ND <50
3	1200	ND <50
4	2000	ND <50

mg/Kg - parts per million (ppm)

Method Detection Limit for Oil and Grease in Soil: 50 mg/Kg

QAQC Summary: MS/MSD Average Recovery: 78%

Duplicate RPD: 9

Richard Srna, Ph.D.



825 Arnold Drive, Suite 114 * Martinez, California 94553 * (510) 229-1512 / fax (510) 229-1526

CERTIFICATE OF ANALYSIS

LABORATORY NO.: 84197

CLIENT: Port Costa Materials

CLIENT JOB NO.: 10/23/91

DATE RECEIVED: 10/24/91

DATE REPORTED: 11/04/91

DATE SAMPLED : 10/23/91

ANALYSIS FOR TOTAL PETROLEUM HYDROCARBONS by Modified EPA SW-846 Method 8015

LAB		Concentration (mg/Kg) Gasoline Range Diesel Range		
. # 	Sample Identification	Gasoline Range	Diese i Range	
1	0400	ND <10	ND <10	
2	0800	ND <10	ND <10	
3	1200	ND <10	ND <10	
4	2000	ND <10	ND <10	

mg/Kg - parts per million (ppm)

Method Detection Limit for Gasoline in Soil: 10 mg/Kg Method Detection Limit for Diesel in Soil: 10 mg/Kg

QAQC Summary:

Daily Standard run at 200mg/L: RPD Gasoline = 14

RPD Diesel =

MS/MSD Average Recovery = 114%: Duplicate RPD = 2

Richard Srna, Ph.D.



825 Arnold Drive, Suite 114 • Martinez, California 94553 • (510) 229-1512 / fax (510) 229-1526

CERTIFICATE OF ANALYSIS

LABORATORY NO.: 84206

CLIENT: Port Costa Materials

CLIENT JOB NO.: 10/24/91

DATE RECEIVED: 10/25/91

DATE REPORTED: 11/05/91

DATE SAMPLED : 10/24/91

ANALYSIS FOR TOTAL PETROLEUM HYDROCARBONS by Modified EPA SW-846 Method 8015

. LAB		Concentration (mg/Kg)		
#	Sample Identification	Gasoline Range	Diesel Range	
1	0400	ND<10	ND<10	
2	2400	ND<10	ND<10	

mg/Kg - parts per million (ppm)

Method Detection Limit for Gasoline in Soil: 10 mg/Kg Method Detection Limit for Diesel in Soil: 10 mg/Kg

QAQC Summary:

Daily Standard run at 200mg/L: RPD Gasoline = 7%

RPD Diesel = 2%

MS/MSD Average Recovery = 102/103%: Duplicate RPD = 1

Richard Srna, Ph.D.



825 Arnold Drive, Suite 114 • Martinez, California 94553 • (510) 229-1512 / fax (510) 229-1526

CERTIFICATE OF ANALYSIS

LABORATORY NO.: 84227

CLIENT: Port Costa Materials

CLIENT JOB NO.: 10/25/91

DATE RECEIVED:10/28/91 DATE REPORTED:11/05/91 DATE SAMPLED: 10/25/91

ANALYSIS FOR TOTAL OIL AND GREASE by STANDARD METHODS 5520F

LAB #	Sample Identification	Concentration(mg/Kg) Oil & Grease
		الله الله الله عند عند ينه بناء الله الله الله عنه بنية الله الله الله الله الله الله الله الل
1	0400	ND<50
2	0800	ND<50
3	1200	ND<50
4	1600	ND<50
5	2000	ND<50
6	2400	ND<50

mg/kg - parts per million (ppm)

Method Detection Limit for Oil and Grease in Soil: 50 mg/Kg

QAQC Summary: MS/MSD Average Recovery: 86/79%

Duplicate RPD: 9

Richard Srna, Ph.D.

Laboratory Director



825 Arnold Drive, Suite 114 • Martinez, California 94553 • (510) 229-1512 / fax (510) 229-1526

CERTIFICATE OF ANALYSIS

LABORATORY NO.: 84206

CLIENT: Port Costa Materials

CLIENT JOB NO.: 10/24/91

DATE RECEIVED: 10/25/91

DATE REPORTED: 11/05/91

DATE SAMPLED : 10/24/91

ANALYSIS FOR TOTAL OIL AND GREASE by STANDARD METHODS 5520F

+ 	Sample Identification	Concentration (mg/Kg) Oil & Grease
1	0400	ND<50
2	2400	ND<50

mg/kg - parts per million (ppm)

Method Detection Limit for Oil and Grease in Soil: 50 mg/Kg

QAQC Summary: MS/MSD Average Recovery: 74/81%

Duplicate RPD: 9%

Richard Srna, Ph.D.



825 Arnold Drive, Suite 114 Martinez, California 94553 (510) 229-1512 / fax (510) 229-1526

CERTIFICATE OF ANALYSIS,

LABORATORY NO.: 84229

CLIENT: Port Costa Materials

CLIENT JOB NO.: 10/26/91

DATE RECEIVED: 10/28/91

DATE REPORTED: 11/05/91

DATE SAMPLED: 10/26/91

ANALYSIS FOR TOTAL PETROLEUM HYDROCARBONS by Modified EPA SW-846 Method 8015

Concentration (mg/Kg)		
esel Range		
ND<10		
ND<10		
ND<10		

mg/Kg - parts per million (ppm)

Method Detection Limit for Gasoline in Soil: 10 mg/Kg Method Detection Limit for Diesel in Soil: 10 mg/Kg

QAQC Summary:

Daily Standard run at 200mg/L: RPD Gasoline = 13

RPD Diesel = 5

MS/MSD Average Recovery = 103/102%: Duplicate RPD = 1

Richard Srna, Ph.D.



Superior Precision Analytical, Inc.

825 Arnold Drive, Suite 114 Martinez, California 94553 (510) 229-1512 / fax (510) 229-1526

CERTIFICATE OF ANALYSIS

LABORATORY NO.: 84229

CLIENT: Port Costa Materials

CLIENT JOB NO.: 10/26/91

DATE RECEIVED:10/28/91
DATE REPORTED:11/05/91

DATE SAMPLED: 10/26/91

ANALYSIS FOR TOTAL OIL AND GREASE by STANDARD METHODS 5520F

LAB # 	Sample Identification	Concentration(mg/Kg) Oil & Grease
1	0400	ND<50
2	2000	ND<50
3	2400	ND<50

mg/kg - parts per million (ppm)

Method Detection Limit for Oil and Grease in Soil: 50 mg/Kg

QAQC Summary: MS/MSD Average Recovery: 86/79%

Duplicate RPD: 9

Richard Srna, Ph.D.

Laboratory Director

Certified Laboratories

APPENDIX E

FIELD PROCEDURES
SOIL BORING INSTALLATION

FIELD PROCEDURES SOIL BORING INSTALLATION

On November 7 and 8, 1992, LRA Engineering of Sacramento, California, a licensed well-drilling contractor, drilled 12 soil borings (SB1 through SB14) under the direction of a Levine. Fricke engineer (Figure 5). Soil borings were drilled using a truck-mounted drill rig equipped with 8-inch-outside-diameter hollow augers to depths of 10 or 12 feet below ground surface (bgs).

During drilling, soil samples were collected for chemical analysis by driving an 18-inch-long split-spoon sampler ahead of the auger into undisturbed soil. The sampler was lined with three clean, 2-inch-diameter, 6-inch-long brass tubes. Soil samples were collected at 2, 6, and 10 feet bgs in the 10-foot deep borings and at 4, 8, and 12 feet bgs in the 12-foot deep borings.

Soil samples were immediately covered with aluminum foil, capped with tight-fitting plastic caps, sealed with tape, labeled, and placed in an ice-chilled cooler for transportation to the analytical laboratory. The samples were submitted for chemical analysis under strict chain-of-custody procedures to Precision Analytical Laboratory, Inc. of Richmond, California.

All drilling and sampling equipment was steam cleaned before use at each drilling location. Soil cuttings from each borehole were stockpiled on site.

APPENDIX F H & H MANIFESTS

ate of California—Health and Welfare Agency
lease print or type. Form designed for use on eithe (12-pitch typewriter).

1	UNIFORM HAZARDOUS WASTE MANIFEST	1. Generator's US		Manifest Documen		2. Page 1		n in the shaded areas ired by Federal law.
ŀ	3. Generator's Name and Malling Address	. 31	13151815171416	<u>01 91 91</u>	A sicil	of 1 Manifest Document	Number	1509080
,	CATELLUS DEVELOPMENT CON			* ***	B. Storie	Generators ID	·	TANDOON
ľ	201 Mission Street, Suit	1 Ba		A. 94105			1014	1.41
	5. Transporter I Company Name 974 461		6. US EPA ID Number	/		Transporters ID	3000	
ı	H & H Ship Service Comp 7. Transporter 2 Company Name	าลหน	8. USEPA1D Number 4	711160	*********	porters Phone Transporters ID	428)	
				<u> </u>	1974.	orier's Phone	14 14 14 14 14 14 14 14 14 14 14 14 14 1	
	9. Designated Facility Name and Site Address		10. US EPA ID Number		100 0 110 110 110	Footity's IO		
l	H & H Ship Service Comp 220 China Basin Street San Francisco, CA 9410	any			H. Focilit	ysPhone		
]		CADO 047	1 7 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	iners (1 3 Å3. TOTON - 4 C	-14' Unit	
1	11. US DOT Description (including Proper Shipping a.	Name, Hazard Clas	s, and ID Number)	No.	Туре	Quantity	Wt/Vol	I. Woste Number
G					ŀ			State
E	OIL AND WATER NON-RCRA HAZARDOUS WAST	P TTOUTS		010 5	m 1 m	ale la la la		EPA/Cither! % . L
Ë	b,	e- urăna		11 11 11	7 7	યે. ફે. તો . છે. તે	5	State
R					ı			EPAVOIher
A T				1 1		1 1 1 1		State
O.			- 1		"		1	
K.		,```	•		, 1]	EPAJOther
	. d.							Sicile
ş.	第18 00 年 100 年 100 年 100 年 100 年 100 日 1							EPA/Other
ľ	J. Additional Descriptions for Moterials Listed Abov	•		1 I 2653531881;15354111	l K: Handlit	1 1	Listed Abo	Ve.
١,	FUEL, OIL AND WATER				9 0000		b.	
ļ. ·							d	
Ì	15. Special Handling Instructions and Additional In	formation					. 33.2.**	
	JOB #9942			TOO OYES	m. 17	-111- 41-		,
*	1	t: HAH	#(415) 543-48	JOB SIT. 35		ollis Stre meryville,		
	· APPROPRIATE PROTECTIVE	CLOTHING A	AND RESPIRATOR	,				
١,	 GENERATOR'S CERTIFICATION: 1 hereby decided packed, marked, and labeled, and are in all remarks. 	re that the content	s of this consignment are fu andition for transport by high	ty and accurately d	escribed e	above by proper st	nipping nor	ne and are classified,
	If I am a large quantity generator, I certify the	nat I have a progra	m in place to reduce the v	volume and toxicity	of waste :	generated to the a	lagraa I ha	va dataminad to be
	economically practicable and that I have sell threat to human health and the environment;	ected the practical OR, if I am a small o	ble method of treatment, sta Quantify generator, I have ma	rage, or disposal cui ade a good faith eff	rrently avo	xilable to me which mize my waste gene	minimizes to	ha present and future select the best worke
	management method that is available to me	and that I can affor	d.					1
	Printed/Typed Name	, , , , ,	Signature	11.		······································	Month	Day Year
	William Madison -Le	Vipe-13.CA	d Unth	1-1-1				
<u>/</u>	17. Transporter 1 Acknowledgement of Receipt of		I PUMA.	/ - / - / (lace .		وانزا	1.17151
R A	Printed/Typed Name		Signature				Month	Day Year
A N S	l annima a sussessi		1 1 / La destro	" form	مدود ر ضی د :			
S P	ROBERT S. HANSEN 18. Transporter 2 Acknowledgement of Receipt of	Materials	1 S. P. Marie J.	10				12 17 19 12
Š	Printed/Typed Name		Signature				Month	Day Year
Ē			;					
R	19. Discrepancy indication Space						1	1 1 1 1
F	,							
ç		٠						
ij	20 Exalify Ounget of Country of	a a f h			-			
	20. Facility Owner or Operator Certification of rece Printed/Typed Name	ipi ot nazardous ma	aterials covered by this manif Signature	est except as noted	in item 19.		, Month	Day Year
Ý							'	
	· · · · · · · · · · · · · · · · · · ·		· · · · · · · · · · · · · · · · · · ·			· · · · · · · · · · · · · · · · · · ·		~

ate of California—Health and Welfare Agency

e pr	int or type.	- Form designed for use on eite (12	-pitch typewriter).							Sacramento, C	California .
		IFORM HAZARDOUS WASTE MANIFEST	1. Generator's US C: A: D: 9:8	EPA 10 No. 3 5 8 5 7 4		est Documer		2. Page 1 of 1		n in the shaded are ired by Federal law	
i,	LATELI	CUSTREVELOPMENT CO	RPORATION					Monfest Documen	at Number	ired by Federal law	
;	201 H	ission Street, Sui	t e 25 0, Sa	n Francisco,	CA. 9	4105		Burgan de la Caractería d	10 April 1931		
	5. Transport	er I Company Name		6. US EPA ID Number		,	C. State	total in the transporters iD	3000		
		Ship Service Com	pany	C_A_D_0_0_4_1	$7_{1}7_{1}1$	11 6 8	D. Iron	porters Phone	(412)	2013-0033	
	7. ironsport	er 2 Company Name .		1 1 1 1 1 1		1/11	F. Ironst	orters Phone	gasta sebusia Panganan	-1,5085 persent	\$677.07 \$675.51
	9. Designate	ed Esculty Notes and Site Address	pany	10, US EPA ID Number			© State	Foolity's ID	4 7 7	1,1,6,6	
	San F	hina Basin Street rancisco, CA 941	97	C1A1D1010141	7,7,1		H Focili	y's Phone 15 743 44	83%.		
	11. US DOT D	escription (including Proper Shipping	Name, Hazard Cla	s, and ID Number)		12. Conto No.	iners Type	13. Total Quantity	14, Unit Wt/Vol	I. Woste Numbe	8.00
	a. OII. à	ND WATER								State 1	**
G E		CRA HAZARDOUS WAS	TE LIQUID			0 0 L	T,T	0,5,0,0,0	G	EPA/Other	
N E	Ь.		<u> </u>					<u> </u>		State	
R A						, ,				EPA/Other	
T	C,	-				1 1	'	 		State	
O R	```									EPA/Other	
	d.					1 1	. !	<u>, </u>		State	
										EPA/Other	
	J. Additional	Descriptions for Maleitas Listed Abo Of L. AND WATER	Ve				K. Handi	udicogei toliMüst	es Listed Ab		(\$84%)959- 1848)38595
	rent	ATT AND AVIEW					9 0		b.		
	***************************************	16 #A1529					C.		d		
	15. Special H JUB	andling Instructions and Additional I 19942	nformation			iob sit	E;	ollis Str	eat &	40th	
	24 Hx	. Emergency Conta			835	i i		Smeryville		fornia	٠,
		PRIATE PROTECTIVE				6			,	,	
		IOR'S CERTIFICATION: I hereby deci marked, and labeled, and are in all									
		i large quantity generator, I certify loally practicable and that I have so									
	threat to	human health and the environmen ment method that is available to me	t; OR, if i am a small	quantity generator, I have							
	Printed/Type			Signature	1	∂			Mont	Day	Year
	Willia	Markey - Las	But Ent	1 dieles	I_{los}	Knowle.	, .		0.1	 [2 ^ [4	
	17. Transport	er 1 Acknowledgement of Receipt of	714.f: /∄; (scar /	- 10 Mg	Vi.		["["	*	- 1
R A N	Printed/Type	d Name		Signature		11			Mont) Day	Year
7 S P	ROBER	RT S. HANSEN		12000	30/	Kylm Z			0 1	12 7 19	12
O R	18. Transporte Printed/Type	er 2 Acknowledgement of Receipt of	f Materials	Signeflyre	· · ·				Mont	n Day	Year
Ť E	11111	Internal !	· p /	TITOA	4	D.				1	
<u>R</u> .	W7/16	etu Madistus Le	hae frick	Att Plut	1.	-Etra	<u> </u>	·····	1 1	<u> </u>	
F	ir, biscreptr	ky atukutostopuku		1.0						: 	
C		•									
L		wner or Operator Certification of rec	ceipt of hazardous m		unifest exc	cept as note	d in item 1	٥.			
Ť Y	Printed/Type	d Name		Signature					Mont	h Doy	Year
•									1	1 1	1
				NOT WRITE RELOV					1	 • • • • • • • • • • • • • • • • • • •	

,	ATT OF TYPE. FORTH COST PROGRAM (12	• · · · · · · · · · · · · · · · · · · ·					İ	Sacramento, Call	omic
1	UNIFORM HAZARDOUS WASTE MANIFEST	1.Generator's US	EPA ID No.	Manifest Documen		2. Page 1	is not read	n in the shaded areas ired by Federal law.	
	3. Generators Name and Making Address CATELLUS DEVELOPMENT CO.				A Store	Monitest Document	Neumber	150903	2
	201 Mission Street, Sui: 4 Generator's Phone (415) 974-461:	te 250, Sa 7	•	A. 94105	p. Stote	Generator's ID	\$16.984 8 \$		
	5. Transporter I Company Name H & H Ship Service Com		6. US EPA ID Number		C State	Transporter's ID	- 3000		
	7. Transporter 2 Company Name	- can y	8. US EPA ID Number	<u> </u>	E. Stafe	Tronsponers ID	(415)	541-4835	21843 2003 2003
	9. Designated Facility Name and Site Address		1 1 1 1 1 1 10. US EPA ID Number	1111	G State	corter's Phone Footsity's ID			
	H & H Ship Service Com 220 China Basin Street San Francisco, CA 9410	pany 07	ما برای ایران ام		H. Focik	યું કું કાં તાં કાં bysPhone	(1919)	AT Y TALLS	
	11. US DOT Description (including Proper Shipping		16 to 20 to 35 to	12. Confa	iners Type	13. Tofal	14. Unit Wt/Vol	L Worte Number	
Ĭ	a.				.,,,,,,	GGGTIIIY	11770	Sicile	
E	OIL AND WATER HON-RORA HAZARIVHIS WASS	<u>ee liouid</u>		n in h	ரா(ஷ	ALS IN IN IN	~	EPA/Citier*	
N E	b.						,,-	Sicile	
R				1 1		1 1 1 1		EPA/Other	
0	С.							State	
R.	a			1 1	I.	, <u> " </u>		EPA/Other	
	4							State	
ļ	J. Additional Descriptions for Materials Listed Abov	76 * (8: 8: 8: 8: 8: 8: 8: 8: 8: 8: 8: 8: 8: 8			l Katheredia	I I I I		EPA/Other	
	FUEL, CIL AND WATER				G 23 / 200		b.	vo	
	PROFILE #A1520						đ		
	15. Special Handling Instructions and Additional In JOB #9942	formation		aco aco	m . · .	, , , , , , , , , , , , , , , , , , ,			
	. 24 Hr. Emergency Contac	t: H&H	#(415) 543-48	35		ollis Stre Meryville,			,
	APPROPRIATE PROTECTIVE 16. GENERATOR'S CERTIFICATION: I hereby decided	***			los orth a d	_b., a b.,			
	packed, marked, and labeled, and are in all r If I am a large quantity generator, I certify the	respects in proper c	ondition for transport by high	iway according to at	plicable	international and no	ational gove	 anoitaluger triemme 	-
	economically practicable and that I have sel threat to human health and the environment:	lected the practical	ble method of treatment, sta	omae, or disposal cui	renth av	ulable to me which	minimizae H	an amenat and fidure	
	management method that is available to me Printed/Typed Name	and that I can affor	rd. Signature			, 4010	··-		
	latin A. I	م ا	1.11	1			Month	Day Year	<i>'</i>
Y T	17. Transporter 1 Acknowledgement of Receipt of	LVV.AG-17.5	M MENIN	1 my you			011	1217191	2
RAN	Printed/Typed Name		Signature	and specific			Month	Day Year	\exists
S P	ROBERT S. HANSEN		12 miles	Jeffen.			011	12 +7 1 9 1	2
R T	18. Transporter 2 Acknowledgement of Receipt of Printed/Typed Name	Materials	Signature				Month	Day Year	7,
Ē							1.	1 . 1 .	
F	19. Discrepancy Indication Space				·			<u> </u>	\dashv
A C								! ! 	Ì
f I	20. Facility Owner or Operator Certification of rece	ipt of hazardous ma	aterials covered by this man	fest except as noted	in item 19				
Ť Y	Printed/Typed Name		Signature .	,			Month	Day Year	-
	·							i ! ! ! 1	ļ
						* * * * * * * * * * * * * * * * * * * *	<u> </u>	<u> </u>	

state of California—Health and Welfare Agency

See Instructions on back of page 6. Form designed for use on eithe (12-pitch typewriter). Sacramento, California UNIFORM HAZARDOUS WASTE MANIFEST 1, Generator's US EPA ID No. 🚟 Manifest Document No. 2. Page 1 Information in the shaded areas CININIOIRISIRIRISITIALE OF ALCOLO 3. Generator's Name and Mailing Address of the Park Strategy of the Park is not required by Federal law. CATELLUS DEVELOPMENT CORPORATION 201 Mission Street, Suite 250, San Francisco, CA. 94105 B. State Generator's D 5. Transporter I Company Name 6. US EPA ID Number G. State Transponers ID 300080 H & H Ship Service Company 6. US EPAID Number 7. Transporter 2 Company Name E. State Transporter's ID F. Ingreporters Phone 9. Designated Facility Name and Site Address 10. US EPA ID Number H & H Ship Service Company 220 China Basin Street San Francisco, CA 94107 G. State Facility's ID: CLARD DIOLECTIVE FEETERS H Foolity's Phone 12. Containers 11. US DOT Description (including Proper Shipping Name, Hazard Class, and ID Number) 13. Total '14, Unit No Type Wt/Vol Quantity OIL AND WATER NON-RORA HAZARDOUS WASTE LIQUID ត គេ ጥነጥ EPA/Olher Staté 11.45 4.30 288 . 6 EPA/Othe Additional Descriptions for Materials Listed Abov. K. Handling Codes for Wastes Listed Above FURL OIL AND WATER PROPTING Special Handling Instructions and Additional Information JOB #9942 JOB SITE: Hollis Street & 40th 24 Hr. Emergency Contact 10 H & A H # (415) 543-4835 Emeryville California APPROPRIATE PROTECTIVE CLOTHING AND RESPIRATOR 16. GENERATOR'S CERTIFICATION: I hereby declare that the contents of this consignment are fully and accurately described above by proper shipping name and are classified, packed, marked, and labeled, and are in all respects in proper condition for transport by highway according to applicable international and national government regulations. If I am a large quantity generator, I certify that I have a program in place to reduce the volume and toxicity of waste generated to the degree I have determined to be economically practicable and that I have selected the practicable method of treatment, storage, or disposal currently available to me which minimizes the present and future threat to human health and the environment; OR, if I am a small quantity generator, I have made a good faith effort to minimize my waste generation and select the best waste management method that is available to me and that I can offord. embil bequitbeinh Month 19 10 10 10 17. Transporter 1 Acknowledgement of Receipt of Materials Printed/Typed Name Signature Month ROBERT S. HANSEN 12 19 19 12 18. Transporter 2 Acknowledgement of Receipt of Materials Printed/Typed Name Month 19. Discrepancy Indication Space

DO NOT WRITE BELOW THIS LINE.

Signature -

20. Facility Owner or Operator Certification of receipt of hazardous materials covered by this manifest except as noted in item 19.

hinted/Typed Name.

Year

Month

te of Collomia—Health and Welfare Agency
use print of type. Form designed for use on ellie (12-pitch typewriter). UNIFORM HAZARDOUS 2. Page 1 1. Generator's US EPA ID No. Manifest Document No. Information in the shaded areas

٠. 	WASTE MANIFEST . CIA ID 19 18 13	15 18 15 17 14 16 0	<u>lalal</u>	01.1	of 1	is not requi	ed by Fede	ral law.
	3. Generator's Name and Mailing Address CATELLUS DEVELOPMENT CORP.			A Stafe	of 1 Monfest Document	AnupaD	1508	3378
X	201 Mission Street, Suite 250, San 4 Generators Phone (415) 974-4617	Prancisco, CA. S	94195		Generator's ID			
٠.	5. Transporter 1 Company Name 6.	. US EPA ID Number	7:		TANKS AND AND MADE IN	masr	80.9938	
	H & H Ship Service Company	12 10 10 14 17 17 14		a distriction of	sporter's Phone	(496)	543_41	
	7. Transporter 2 Company Name 8.	.USEPAIDYNumber* / * 4		11100 000000	Tromporter's IC corter's Phone	o ya ganga Wasan ya Ma		
	**************************************	. US EPA ID Number		G. Stufe	Foelity's ID			
	H & H Ship Service Company 220 China Basin Street				la printina. tys Phone	(7)7.0	11 16 13	X
		12 10 10 14 17 17 11	12. Confo	iner \	^{A 5} 713. Tolar ** ^O	Tal. Unvt		
	1). US DOT Description (including Proper Shipping Name, Hazard Class, or	nd ID Number)	No.	Туре	Quantity	Wt/Vol	. l. Woste N	lumber .
	a						State	
:	OIL AND WATER NON-RCRA HAZARDOUS WASTE LIQUID		0 0 1	es (es	02600		EPA/Other	V
!	b.	^		7 14			State	
2	,					1	EPA/Other	
	c.		 				State	
•			,		:	. <u>L</u>		
•		,		1	.1.1.1.1		EPA/Other	
	d.						State	
	, ,						EPA/Olher	
!	J. Additional Descriptions for Materials Listed Above			IX: Hand	ing Codes for Wastes.	isled Abo	/e	
į	FUEL, OTL AND WATER			a.		b		
-	PROPILE #A1537			9				2,000
	15. Special Handling Instructions and Additional Information		2 200 200 200 2	10.66.30		- 329 3-41 5	\$ 1262 50 180 \$ 1	
	JOB #19208	J	ob sit	E: C	ATELLUS DE	VELOPN	ent	
5	24.Hr. Emergency Contact: 4 H & H #		54 ; A		ollis Stre			,
	APPROPRIATE PROTECTIVE CLOTHING AN. 16. GENERATOR'S CERTIFICATION: 1 hereby declare that the contents of				meryville.			
	packed, marked, and labeled, and are in all respects in proper conc							
	If I am a large quartify generator, I certify that I have a program economically practicable and that I have selected the practicable							
	threat to human health and the environment; OR, if I am a small qua management method that is available to me and that I can afford.							
		Signature 77	 			Month	Dav	Year
	1111 1. 1.	17/01/12	7 · · · · · · · · · · · · · · · · · · ·	, ,				
	William Madifa they go Crichia	DOCKE LO	Artigan	, ·	- 1	0 3	10 14	1917
	17. Transporter 1 Acknowledgement of Receipt of Materials Printed/Typed Name	Signature		·		Month	Day	Year
		CA	1	•	ر د د د د د د د د د د د د د د د د د د د			
,	PSTERAN M PENALVED	646	Min		السيار السيار	0 13	lo 14	19 12
)	18. Transporter 2 Acknowledgement of Receipt of Materials Printed/Typed Name	Signature				Month	Day	Year
						1	1 1	1
	19. Discrepancy Indication Space							
							i	
		· . · · · · · · · · · · · · · · · · · ·						
. 1	20. Facility Owner or Operator Certification of receipt of hazardous mate		cept as noted	a in item t	٧.]	
,	Printed/Typed Name	Signature				Month	Day	Year
•	Printed/Typed Name	Signature				Month	Day	Year

DO NOT WRITE BELOW THIS LINE.

APPENDIX G AERATION BED CONSTRUCTION AND SAMPLING PROCEDURES

AERATION BED CONSTRUCTION AND SAMPLING PROCEDURES

Construction

Aeration beds 1, 3, 4, 5, and 6 were constructed by lining graded and bermed areas with two layers of 6-mil visquine. Aeration bed 2 was constructed by ARI in June 1991 (SP-10; Figure 4) using 6 inches of sand covered with one layer of 6-mil visquine and topped with another 6 inches of sand. Soil was generally placed on aeration beds in 12-inch to 18-inch loose lifts using front loaders operated by Plant Reclamation.

An agricultural disc was used to turn the soil on bed 1 for aeration; however, the discs became clogged with soil and did not effectively turn the soil. Two excavators with "grappler" extensions were used to turn and mix the soil on the remaining aeration beds. Soil on the aeration beds was turned and mixed two to three times before final soil samples were collected.

Sampling

Soil samples were collected from the aeration beds using a "grid approach": one soil sample was collected from every 50 cubic yards of aerated soil. Levine Fricke personnel collected one to two soil samples (depending on the size of the grid) from random locations within each cell at depths ranging from 6 to 20 inches below the top surface of the aerated soils. A total of 197 soil samples was collected from the 6 aeration beds. Of the first 50 samples collected (\$S-1 through \$S-50) in May 1992, only 30 were analyzed (\$S1 through \$S-30). Based on the results for these samples, soils were turned once more to further aerate the soil.

When PID readings of the aerated soils indicated that the concentrations of volatile organic compounds (VOCs) had dropped significantly, the remaining 168 samples (SS-51 through SS-218) were collected. This sampling occurred during the period from July 17 to August 28, 1992. Laboratory analytical results for samples collected from the aerated soils are summarized in Table 8.

Soil samples were collected in accordance with procedures described in Appendix B. Samples were delivered by courier to Precision Analytical Laboratory, Inc. for analysis of total petroleum hydrocarbons (TPH) as gasoline and benzene, toluene, ethylbenzene, and xylenes using EPA Methods 8015/8020. Thirty samples also were analyzed for TPH as diesel and oil using Modified EPA Method 8015.



SW-846 ANALYSIS FOR SOIL SAMPLES COLLECTED FROM AERATION BEDS

SW-846 ANALYSIS FOR SOIL SAMPLES COLLECTED FROM AERATION BEDS

Aeration bed sample results were analyzed using guidelines outlined in Chapter 9 of the Environmental Protection Agency Office of Solid Waste Management Document SW-846, Test Methods for Evaluating Solid Waste (hereafter referred to as "EPA SW-846"). The results of this analysis indicate that a sufficient number of samples have been collected from the aeration beds to adequately characterize the aerated soils. A description of this method and the results of this analysis are presented below.

The statistical approach presented in EPA SW-846 suggests a random sampling process. The application of the simple random sampling process described in EPA SW-846 for aeration beds of petroleum-affected soils consists of the following protocol:

- Divide the lateral and vertical extent of the stockpile into an imaginary three dimensional block of uniformly sized cells.
- 2. Assign a series of consecutive numbers to the cells.
- 3. Compute the mean and variance of the available representative laboratory analytical results of soil samples of the excavated petroleum-affected soils using equations listed in Table 9-1 of EPA SW-846.
- 4. Compute the appropriate number of samples to be collected using equation 8 of Table 9-1 in EPA SW-846.
- 5. Select the cells to be sampled through the use of a random-number generator/table.

Based on the SW-846 analysis of analytical results for the soils aerated as directed by Levine Fricke personnel, it was determined that a sufficient number of soil samples had been collected to characterize the aerated soils. Calculations and results of SW-846 analysis on soils aerated by Levine Fricke personnel are presented below and in Table H-1.

Statistical Analysis of Soil Sampling Results Using EPA SW-846

Statistical analysis (EPA SW-846) was used to assess the number of additional samples (N) required to characterize the soil concentrations with an 80% confidence level.

Equation 8 of Table 9-1 (EPA SW-846):

$$N = t_{0.2}^2 s^2 / (c-x)^2$$

Parameters:

- N Appropriate number of samples to collect from a soil waste
- s Standard deviation of sample
- s² Variance of sample
- x Mean measurements generated by sample
- t t value tabulated for various degrees of freedom confidence intervals and probabilities
- n Degrees of freedom
- c concentration criterion for constituent in soils proposed for use as backfill

Where, for example, for TPHg in aerated soils (using data presented in Table H-1):

$$s^2 = 70.56$$

$$x = 2.79$$

 $t_{0.2} = (0.842 \text{ for } n > 120 \text{ and a probability of } 0.20)$

$$c = 10 ppm$$

$$\mathbf{N} = \mathbf{t_{0,2}}^2 \mathbf{s^2} / (\mathbf{c-x})^2 = (0.842)^2 (70.56) / (10 - 2.79)^2$$

= less than 1

No additional samples are required to characterize the quality (with an 80% confidence level) of TPHg-affected soils proposed for use as backfill at the Ransome Site.

TABLE H-1
STATISTICAL ANALYSIS OF AERATED SOILS
RANSONE PROPERTY, EMERYVILLE, CALIFORNIA

	Compound							
	TPHg	Benzene	Toluene	Ethylbenzene	Xylenes			
Count	196	196	196	196	196			
Average	2.79E+00	3.68E-03	3.09E-03	7.43E-03	4.01E-02			
Standard Deviation	8.4	0.009	0.003	0.027	0.33			
80% UCL	3.79E+00	4.76E-03	3.41E-03	1.06E-02	7.94E-02			
Maximum Value	1.10E+02	1.20E-01	3.00E-02	3.20E-01	4.60E+00			
N	<1.0	<1.0	<1.0	<1.0	<1.0			

Count = Number of soil samples

Average = Average concentration, presented in parts per million (50% of detection limits used as the concentration for samples with below method detection limit results).

UCL = Upper confidence level

Maximum Value = Maximum detected concentration, presented in parts per million

N = Additional samples to be collected from a solid waste using the methods described in EPA SW-846 (with an 80 percent confidence level)

TPHg = Total petroleum hydrocarbons as gasoline