2030 Addison Street, Suite 500 • Berkeley, California 94704 • 415 540-6954

March 11, 1992

Mr. Barney M. Chan Alameda County Health Care Services Agency 80 Swan Way, Room 200 Oakland, CA 94612

690262.2

Subject: PG&E Tank Cluster Area, 4930 Coliseum Way, Oakland, CA

Dear Mr. Chan:

Aqua Resources Inc. is pleased to submit, for your review and acceptance, the enclosed closure report for the above site, formerly contaminated with petroleum hydrocarbons.

Please do not hesitate to call if you have any questions.

Very truly yours,

AQUA RESOURCES INC.

Voytek Bajsarowicz, R.E

Project Engineer

90262.2\clos-rpt.ltr

VB:blw

CC: Wally Pearce (w/enc)

SITE REMEDIATION AND CLOSURE REPORT

PG&E ENCON-GAS
Transmission and Distribution Construction Yard
Former Tank Cluster Area
4930 Coliseum Way
Oakland, California

Submitted to:

Alameda County Health Care Services Agency Department of Environmental Health Division of Hazardous Materials

Prepared by:

AQUA RESOURCES INC. a wholly owned subsidiary of The Earth Technology Corporation 2030 Addison Street, Suite 500 Berkeley, California 94704

February 1992

Disk: 90262.2 File: closure.rpt

TABLE OF CONTENTS

1.0	INTRODUCTION 1.1 STATEMENT OF PURPOSE 1.2 REPORT ORGANIZATION	1 1 3
2.0	SITE BACKGROUND 2.1 SITE DESCRIPTION 2.2 PREVIOUS INVESTIGATIONS 2.3 SITE HISTORY	4 4 6 8
3.0	SITE GEOLOGY AND HYDROGEOLOGY 3.1 REGIONAL GEOLOGY 3.2 SITE GEOLOGY 3.3 SITE HYDROGEOLOGY	9 9 10
4.0	4.1 REMEDIAL EXCAVATION 4.2 FATE OF REMOVED MATERIALS 4.2.1 Preliminary Bioassay Screening 4.2.2 Fate of Removed Soil 4.2.3 Fate of Removed Debris 4.2.4 Fate of Removed Water 4.3 IN-SITU CONFIRMATORY SAMPLING 4.4 BACKFILL AND COMPACTION OF REPLACEMENT MATERIAL 4.5 PROTECTION OF NEIGHBORING PROPERTY DURING REMEDIATION 4.6 PROTECTION OF CLEAN BACKFILL FROM RESIDUAL HYDROCARBONS 4.6.1 Northeast Excavation Boundary 4.6.2 Northwest Excavation Boundary	111 12 15 17 18 19 20 21 28 32 35 35 36 38
5.0	5.1 DESCRIPTION AND CHARACTERIZATION OF TAR FILLED PIPES 5.2 RESULTS OF FIELD RECONNAISSANCE	40 43 43 45
6.0	6.1 SOILS	47 47 47
70	LIMITATIONS	48

LIST OF TABLES

TABLE 4-1 WORKING SOIL CLEANUP LEVELS	11
TABLE 4-2 RESULTS OF CALIFORNIA HAZARDOUS WASTE BIOASSAY	18
SCREENING TABLE 4-3 SOLUBLE LEAD CONCENTRATIONS IN SOIL FROM SUMP AREA	19
TABLE 4-3 SOLUBLE LEAD CONCENTRATIONS IN SOIL FROM SOME ARLA TABLE 4-4 SUMMARY OF DETECTED HYDROCARBON COMPOUNDS IN WATER	13
REMOVED FROM EXCAVATION (SAMPLE WA-1)	20
TABLE 4-5 SUMMARY OF DETECTED VOLATILE (EPA 8010 AND 8020)	
COMPOUNDS IN WATER REMOVED FROM EXCAVATION (SAMPLE WA-1)	21
TABLE 4-6 SUMMARY OF CONFIRMATORY SOIL SAMPLE ANALYSES	23
TABLE 4-7 PETROLEUM HYDROCARBONS DETECTED IN CONFIRMATORY SOIL	
SAMPLES	24
TABLE 4-8 SUMMARY OF VOLATILE (EPA 8010/8020) ORGANIC COMPOUNDS	
IN TWO CONFIRMATORY SOIL SAMPLES	28
TABLE 4-9 SUMMARY OF NATIVE SOIL PROPERTIES AT TWO DEPTHS	30
TABLE 4-10 SUMMARY OF ORGANIC HYDROCARBON COMPOUND ANALYSES	
ON RECYCLED AB BACKFILL MATERIAL (COMPOSITE OF SAMPLES ABE-1,	
ABW-1, ABS-1 AND ABN-1)	31
TABLE 4-11 SUMMARY OF FINAL COMPACTION TEST RESULTS	32
TABLE 4-12 RESULTS OF SETTLEMENT MONITORING ON METALCAST	35
ENGINEERING BUILDING	პე
	42
SAMIFEE E-FIFE-2 AND GOIE SAMIFEES E-0 AND D-FT	72
LIST OF FIGURES	
FIGURE 1-1 SITE LOCATION MAP	0
FIGURE 2-1 SITE PLAN	
FIGURE 2-2 MONITORING WELL LOCATIONS	
FIGURE 4-1 APPROXIMATE AREA OF ELEVATED TPH CONCENTRATIONS IN SOIL	13
FIGURE 4-2 INITIAL EXCAVATION LIMITS	14
FIGURE 4-3 FINAL EXCAVATION LIMITS	16
FIGURE 4-4 INITIAL CONFIRMATORY SAMPLES	25
FIGURE 4-5 FINAL CONFIRMATORY SAMPLES	27
FIGURE 4-6 FINAL EXCAVATION DEPTHS	29
FIGURE 4-7 SHEET PILING REINFORCEMENT LOCATION	34
FIGURE 4-8 BACKFILL PROTECTION MEASURES	37
FIGURE 4-9 NEARBY MONITORING WELL LOCATIONS	39
FIGURE 5-1 KNOWN TOXIC AND FUEL LEAK CASES	46

APPENDICES

APPENDIX A ANALYTICAL RESULTS

APPENDIX B MANIFEST DOCUMENTATION

APPENDIX C COMPACTION TESTING RESULTS

APPENDIX D SETTLEMENT MONITORING RESULTS

APPENDIX E BORING LOGS


1.0 INTRODUCTION

1.1 STATEMENT OF PURPOSE

This report presents a summary of the activities performed by, and findings of, Aqua Resources Incorporated (ARI) associated with the remedial excavation of petroleum hydrocarbon impacted soil in the vicinity of a former underground tank cluster, a former sump, and a former vehicle maintenance shop location at the Pacific Gas and Electric (PG&E) ENCON-GAS Transmission and Distribution (T&D) construction yard. This work was complies with the scope of the general agreement between PG&E and ARI and was performed under the authority of PG&E. The site is located at 4930 Coliseum Way in the City of Oakland, California. The Site Location Map, Figure 1-1, shows the location of the site.

All sample analyses, manifest documentation, compaction testing results and settlement monitoring results are included as appendices to this report. The soil excavation, stockpiling and excavation backfilling was performed by STAMCO under the supervision of PG&E. ARI provided field engineering oversight, environmental sampling and consultation to PG&E during the conduct of the work.

The results of the herein described remedial effort and the associated conclusions and recommendations indicate that the extent of soil hydrocarbon contamination on PG&E property, in the vicinity of the former shop and tank cluster, has been remediated to levels below target concentrations established for the site by the Alameda County Health Care Agency. These site-specific targets were derived and are consistent with the procedures described in the Leaking Underground Fuel Tank Manual (LUFT) and the Tri-Regional Board Staff Recommendations for Preliminary Evaluation and Investigation of Underground Tank Sites.



1.2 REPORT ORGANIZATION

The Site Remediation and Closure Report consists of the following elements:

- Site Background
- Site Geology and Hydrogeology
- Description of Remediation Activities
- Potential Sources of Upgradient Contamination
- Conclusions and Recommendations of the Remedial Effort
- Limitations of the Evaluation

2.0 SITE BACKGROUND

2.1 SITE DESCRIPTION


The ENCON-GAS T&D Construction Gas Yard is wholly owned by PG&E and is used as a vehicle, materials, and equipment storage and distribution facility. Historically, the site was also used as a vehicle service center and aboveground natural gas storage facility.

The site is surrounded by industrial properties. Immediately to the northeast of the site is AAA Equipment Co., a junkyard and metal recycling operation; to the northwest is the Metalcast Engineering shop (a plaster casting company), a pattern company and a metal foundry; to the west and southwest (across Coliseum Way) are two motels and a recreational vehicle sales facility; to the southeast (across 50th Street) is a trucking facility.

Figure 2-1 shows the site layout prior to remediation, including the former tank cluster, sump, welding shop and well OW-3 locations. The welding shop was previously used as a vehicle repair and maintenance garage. An office building, material storage warehouse, and a petroleum, oil and lubricant (POL) storage shed are located on-site. Except for an asphalt parking lot at the most southeastern end of the site and concrete pads underlying the onsite structures, most of the site was graveled prior to remediation.

Five underground tanks were formerly located on-site. Four of the tanks (three 500-gallon tanks and one 350 gallon tank) were located in a cluster near at the approximate location shown in Figure 2-1. These tanks were thought to be used to store waste oils. The bottoms of these tanks rested on a concrete pad buried approximately 7 feet below the ground surface.

On the north side of the welding shop, about 50 feet northeast of the former tank cluster location, was a cast iron grill indicating a possible buried sump. During excavation however, disturbed soils were uncovered at this location but no sump was found.




2.2 PREVIOUS INVESTIGATIONS

Soil and groundwater conditions related to the removal of five underground storage tanks at the site were investigated by the Technical and Ecological Services Department of PG&E in 1987 and 1988. The activities performed, along with laboratory results, were presented in the July 1988, Underground Tank Investigation Report # 402.331-88.32 (internal PG&E document). In December 1987, the contents of the five tanks were analyzed by PG&E's Department of Engineering Research chemical laboratory. Two of the tanks in the cluster were found to contain mineral spirits (paint thinner and water) and three tanks contained heavy oil (diesel and/or hydraulic oil). PCBs were not detected in any of the tanks. The five tanks were removed and disposed of on January 13, 1988 by Universal Engineering, Inc.

In March and May 1988 four shallow monitoring wells (OW-1 through OW-4) were installed by PG&E to investigate the groundwater quality and to determine the groundwater flow direction and gradient. The locations of the monitoring wells are shown in Figure 2-2. Well OW-3 was located hydraulically downgradient of the former tank cluster location, and well OW-1 is located downgradient of the former diesel tank. From October 1989 to January 1991 quarterly groundwater samples were collected by PG&E's Technical and Ecological Services Department to monitor the distribution of waste oil, solvents, and fuel compounds in the uppermost aquifer beneath the northern part of the yard, near the former site of the five underground storage tanks. ARI has performed quarterly groundwater monitoring since that time and installed the fifth monitoring well, OW-5, in April of 1991. Well OW-3 was destroyed in October, 1991 and wells OW-6 and OW-7 were installed in December of 1991 following remediation activities. The results of the groundwater monitoring program have been presented in quarterly reports to the Alameda County Health Care Services Agency, Department of Environmental Health, Division of Hazardous Materials (Alameda Co. Health).

In November 1990, and April and May 1991, ARI investigated soil and groundwater conditions at the PG&E ENCON-GAS Transmission and Distribution Construction Yard. The main goal of the investigation activities was to determine the extent of elevated levels of petroleum hydrocarbons in soil and possibly in groundwater related to the former tank cluster



in the northern part of the yard. The former tank cluster, the concrete sump with possible connecting piping, the welding shop, and POL storage shed were considered as possible on-site sources for elevated levels of chemicals in soil and groundwater. The results of this investigation were reported to Alameda Co. Health on July 23, 1991 in a Remedial Investigation Report (RI).

Based upon the results of the previous investigations, ARI performed a Feasibility Study and prepared a Site Closure Plan (FS/SCP) which was also submitted to Alameda Co. Health on July 23, 1991. The FS/SCP outlined the remediation program performed and reported in this document and were approved by Alameda County Health.

2.3 SITE HISTORY

The earliest aerial photographs made available to ARI at the California Division of Mines and Geology (DMG) photo library that cover the site area were taken in August of 1939. These photos showed that the area was already heavily developed. Very large commercial/industrial buildings existed along both sides of San Leandro Street between High Street and 50th Avenue. A large round tank, a multistory former above ground gas holder tank (GHT), was in place on the PG&E site; however, the shadow of the tank prevented determining if any structures existed on the site of the present-day scrap metal business. There were large buildings east of the railroad track and west of San Leandro Street. There were no large buildings at 4700-4800 Coliseum Way. Some small buildings were in place around Coliseum Way and 46th Avenue. The East Creek Slough drainage penetrated farther inland to the south and east of the site than it does at present. The only other aerial photograph available for this area was taken in March of 1984. It showed the site in approximately the same condition as it is at present.

Historical topographic maps for the Oakland East Quadrangle were also reviewed at the DMG. These maps were dated 1949, 1959, and 1968 (photo revision of 1959 map). Each of these maps used a pink coloration to designate a developed area, rather than showing individual buildings. The only structure at the site shown on these maps was the GHT.

3.0 SITE GEOLOGY AND HYDROGEOLOGY

3.1 REGIONAL GEOLOGY

Geologic maps of the region prepared by the DMG (1961) and by Goldman (1969) show the site is underlain by Quaternary marine and marsh deposits. These sediments consist predominantly of highly plastic, blue-grey Bay Mud interbedded with grey, organic-rich silty sands and clayey marsh deposits.

3.2 SITE GEOLOGY

During excavation the following general lithology was observed in the shallow soils underlying the site. Black or brown gravelly sand backfill was observed from the ground surface to a depth of about 3 to 4 feet. In the vicinity of the former shop location scattered debris including sheet metal, metal buckets, tin cans, lumber, milk, medicine and beverage bottles were found within the fill. This amount of debris in the fill generally increased towards the northeast. Some of the lumber and sheet metal removed appeared visibly burned, indicating that perhaps a previous structure here had burned down and the resulting debris had been covered with backfill. Much of the debris contained oil or was oil stained. Underlying this unit was 3 to 4 feet of variously dark brown to blue green silts and clays with an occasional small percentage of sand and gravel. This unit extended to an approximate depth of 6 to 7 feet below grade. Below this to the base of the deepest excavation point at 9 1/2 feet a brown sand and gravel unit containing up to about 50% clay was observed.

The boring logs from the monitoring wells installed by ARI at the site (OW-5, OW-6 and OW-7) indicate that the clayey sand and gravel unit extends to an approximate depth of 14 to 15 feet. Below this to the bottom depth of the wells, about 18 1/2 feet, yellowish silty clays with trace sand were observed with occasional interbedded thin gravel lenses. Copies of the boring logs are presented in Appendix E.

3.3 SITE HYDROGEOLOGY

The topography of the area in the vicinity of the site is relatively flat. Regional surface water flow is to the southwest (toward San Leandro Bay). Surface water bodies nearest the site include San Leandro Bay (located approximately one third of a mile south of the site) and a canal that extends north from San Leandro Bay (located about one half of a mile west of the site). The potentiometric surface of the uppermost water bearing zone beneath the site was found in December, 1991 to be an average of about 7 1/2 feet below ground surface in monitoring wells OW-6 and OW-7.

Groundwater surface elevations in OW-1, OW-2, and OW-5 confirm the general regional groundwater flow direction to the southwest across the site at a December gradient of 0.0038 ft/ft, as was shown in Figure 2-2. However, groundwater elevations in OW-3, later replaced by OW-6, and OW-4 are anomalously high and may indicate the presence of an artificial water source, such as a leaking pipe, in this area. Water samples collected from four wells constructed on-site showed typical conductivity levels of 1,000 to 1,500 microsiemens per centimeter. Conductivity in microsiemens is generally about one-half the value of Total Dissolved Solids (TDS) in mg/L. A water sample collected from well OW-3 was found to have a TDS value of 780 mg/L.

4.0 REMEDIATION ACTIVITIES

The remediation activities at the site occurred during a period from mid-November to mid-December of 1991. During this time, an area, which had been determined in the project Feasibility Study and Site Closure Plan prepared by ARI in July 1991 and approved by Alameda County Health to require remediation due to the presence of petroleum hydrocarbons, was excavated and the removed material was offhauled to a soil recycling facility. During the excavation, confirmatory soil samples were taken along the sidewalls and bottom of the excavation to determine if the full extent of soils impacted by hydrocarbons above the regulatory limit had been removed. Once samples at the excavation boundaries demonstrated levels of petroleum hydrocarbons below those proposed and approved by Alameda County Health for the site in the project Feasibility Study and Site Closure Plan (FS/SCP) the excavation was backfilled with replacement soil and compacted to a level exceeding that of the surrounding native material. The soil cleanup levels used are presented in Table 4-1 below.

TABLE 4-1 WORKING SOIL CLEANUP LEVELS

Constituent	Concentration
TPH as gasoline	10 mg/kg
TPH as diesel	100 mg/kg
TPH as kerosene	100 mg/kg
Hydrocarbon Oil and Grease	1000 mg/kg
BTEX (cumulative)	5 ug/kg


The excavation extent was taken approximately to the edge of the PG&E property line along two of the excavation boundaries. A number of confirmatory samples along these boundaries indicated levels of petroleum hydrocarbon contamination on the neighboring properties which exceeded the proposed cleanup levels and had to be left in place. Protective measures were taken to minimize the potential for future hydrocarbon migration along these boundaries into the clean backfill.


Once the remedial work was completed two monitoring wells, in addition to the four already on site, were installed to provide for future groundwater quality monitoring. Each of these remediation activities is described in detail in the sections which follow.

4.1 REMEDIAL EXCAVATION

Prior to the remedial excavation, PG&E retained a demolition contractor to remove existing structures from the remediation area, including a welding shop and its associated concrete pad. The initial remedial excavation limits were then staked out in the field by ARI personnel based upon the findings of the RI and the approximate area of elevated hydrocarbons presented in the FS/SCP. The location of the welding shop, concrete pad and expected initial excavation limits (based on the RI and FS/SCP) are shown in Figure 4-1. A bermed soil stockpile cell was constructed by spreading two layers of 6 mil plastic sheeting over a base of sand. The construction of this cell as well as the excavation, compaction and offhauling work was performed by STAMCO, Inc. under the supervision of PG&E ENCON Gas, Transmission and Distribution. ARI provided engineering oversight and consultation to PG&E and collected environmental samples during the conduct of the work.

Excavation began on November 18, 1991 using an excavator and loader tandem to remove soil from the ground and transport it to the nearby stockpile cell. An iterative approach was taken to determining excavation limits based upon confirmatory analytical soil samples, the results of which are described in Section 4.2. The initial excavation limits were those indicated in Figure 4-2, with the depth of initial excavation being either that of the underlying water table, found at about 8 to 8 1/2 feet, or some shallower depth in areas where sample results reported in the RI indicated that the vertical extent of hydrocarbon impacted soils did not reach the depth of the water table. Once the initial limit had been excavated, the sidewalls and bottom of the excavation were inspected for hydrocarbon contamination using visual indicators, organic vapor concentration readings and any detectable odors. Based on the inspection a decision was then made whether to continue excavation or to take a






confirmatory sample. Confirmatory soil samples were analyzed, by and large, on a rush basis so that in the event that the sample results indicated petroleum hydrocarbon concentrations in excess of the cleanup levels, further excavation could then be performed without much delay.

Approximately 1,760 cubic (in-situ) yards of soil were removed in reaching the final excavation limits shown in Figure 4-3. The northwest excavation face was taken approximately to the neighboring property line as recommended in the FS/SCP. The northeast excavation face was extended beyond that recommended in the FS/SCP, to within about two feet of the assumed property line in this direction due to the presence of petroleum hydrocarbons. A two foot width of native material was left here to protect the integrity of a 10-foot high fence which lies between PG&E and the neighboring property. In some areas the total excavation depth was taken to about 1 foot below the water table due to the presence of petroleum hydrocarbons in initial confirmatory samples.

Two metal pipelines containing a heavy viscous of or tar were uncovered during excavation along the northeast side of the PG&E property. Once exposed the tar began to slowly ooze from each pipeline. The two pipes, one 12 inches in diameter with a smaller 4 inch diameter inner pipe and the other an 8 inch diameter metal corrugated line, were found buried at depths of 2 and 2 1/2 feet below grade, respectively. The pipes were exposed to within approximately 2 feet of the property line and were found to continue some unknown distance below the AAA Equipment Co. yard. These two pipes were sealed at the excavation boundary as described in Section 4.6.1. The characterization of the oil which they contained is described in Section 5.0, Potential Sources of Upgradient Contamination.

4.2 FATE OF REMOVED MATERIALS

During the remedial excavation, the generated soil was stockpiled on-site in bermed, double 6 mil visqueen lined stockpiles until its disposal could be arranged. This soil was then transported under non-hazardous manifests to Gibson Oil & Refining Co. (GORC) in Bakersfield, California for recycling. Generated metal and concrete debris, as well as spent absorbent pads, was separately stockpiled. Because much of this debris contained heavy,



oily product or was oil stained, it was not acceptable for Class III landfill disposal and was instead transported under manifest as a non-RCRA hazardous waste to the Class I Chemical Waste Management Inc. (CWMI) facility in Kettleman Hills, California. One small sub-section of the remediation area, centered on the former sump location, was separately excavated and stockpiled due to a concern for possible high concentrations of lead. Later stockpile sampling indicated that lead concentrations were below regulatory levels and this soil was also transported to Bakersfield for recycling.

4.2.1 Preliminary Bioassay Screening

Prior to initiating remedial activities, four soil samples and one water sample were collected from the subject area and submitted to Brown & Caldwell Analytical laboratory for a California hazardous waste assessment bioassay screening. The purpose of these samples was to determine if the soil and underlying groundwater met the aquatic toxicity requirements for non-hazardous waste. The soil samples were collected at a depth of 5 1/2 feet by boring to this depth. The samples were collected using a split-spoon sampler at 4 locations around the perimeter of the former tank cluster location. Each of these soil samples, identified as SB-23-1, SB-24-1, SB-25-1 and SB-26-1, were composited into a single sample for the purpose of analysis. The water sample, OW-4-1, was collected from well OW-4, immediately downgradient of the anticipated excavation limits. The results of the bioassay screening, shown in Table 4-2, indicated that the soil and groundwater did not exhibit the aquatic toxicity characteristic of a hazardous waste.

TABLE 4-2 RESULTS OF CALIFORNIA HAZARDOUS WASTE BIOASSAY SCREENING

Bioassay	Time		Dilution in Water					
Conditions	(hrs)	250 mg/L	250 mg/L	750 mg/L	750 mg/L			
Composite of Soil Samples SB-23,24,25,& 26-1								
Percent	Start	100	100	100	100			
of fathead	24	100	100	100	100			
minnows	48	100	100	100	100			
surviving	72	100	100	100	100			
	96	100	100	100	100			
		<u> </u>	Water Sam	nple OW-4-1				
Percent	Start	100	100	100	100			
of fathead	24	100	100	100	100			
minnows	48	100	100	100	100			
surviving	72	100	100	100	100			
	96	100	100	100	100			

4.2.2 Fate of Removed Soil

The 32 boring samples collected during the RI in characterizing the area to be remediated indicated that concentrations of all of the compounds tested in the soil were below regulatory hazardous levels with only one exception: a sample collected near the former sump location (SB-1-1b) indicated that elevated concentrations of soluble lead may exist in its vicinity. During remediation this area and the balance of the excavated soil were separately excavated and discretely stockpiled.

The initial sump area excavation measured 16 1/2 feet (N-S) by 11 1/2 feet (E-W) by 5 1/2 feet deep approximately centered on the former sump location. This area lay interior to the balance of the remedial excavation area. In order to characterize the soluble lead in the 39 cubic yards of soil which were removed from this area, two samples, LSP-1 and LSP-2, were collected from the stockpile and composited for soluble lead analysis. Next, to verify that the full extent of potentially lead impacted soil had been removed, one sample was collected from each wall of the sump area excavation (LN-1, LS-2, LW-3 and LE-4) and these too were composited and analyzed for soluble lead. The laboratory results, shown in Table 4-3,

indicated that soluble lead concentration in both the stockpile and the sidewalls was below the CCR Title 26 Soluble Threshold Limit Concentration (STLC) of 5.0 mg/L.

TABLE 4-3 SOLUBLE LEAD CONCENTRATIONS IN SOIL FROM SUMP AREA

Sample ID	Sample Location	Sample Depth (ft)	Soluble Lead in Composite (mg/L)
LSP-1,	Sump Area	0.7	1.32
LSP-2	Stockpile	2.3	
LN-1,	North, South,	4.5	4.23
LS-2,	East, and West	4.0	
LW-3,	Walls of Sump	4.0	
LE-4	Area Excavation	3.0	

The soil from both the excavation area at large and the former sump sub-area was transported to GORC in Bakersfield, California for recycling. A total of 2,275 tons of excavated soil was offhauled and recycled.

4.2.3 Fate of Removed Debris

Two truckloads, approximately 40 tons, of metal and concrete debris were removed from the subgrade of the remedial excavation area. The concrete was generated during the break up of a concrete tie-down pad underlying the former tank cluster at a depth of about 8 feet. The metal debris consisted primarily of lengths of various diameter metal pipes: some from an uncovered former natural gas line and others from the heavy oil-filled pipes described in Section 4.1. Other items contained in the debris included: sheet metal; two enameled metal signs reading "CYCO Motor Oil"; several crushed, oil-stained, metal buckets; small diameter PVC electrical conduit; tin cans; and a number of old milk, medicine and beverage bottles. Approximately 200 ERGON Inc. sorbent pads used to absorb floating oil droplets observed on uncovered groundwater and used 6 mil visqueen from stockpiles were also contained in this debris. Much of the debris showed visible hydrocarbon staining and was deemed unfit for disposal to a Class III landfill. This debris was taken in two truckloads under manifests to the CWMI Class I facility in Kettleman Hills, California under an existing PG&E non-RCRA hazardous waste profile for oil contaminated debris. A copies of these manifests can be found in Appendix B.

4.2.4 Fate of Removed Water

The groundwater exposed during excavation at the western end of the northern excavation strip was observed to have a dark oily sheen with visible floating oil droplets. An attempt was made to remove the floating oil using absorbent pads. While this removed many of the larger oil droplets, the sheen remained and it was determined that skimming the water with a vacuum truck would be more effective in removing any remaining product. Prior to skimming, samples of the water were collected and analyzed for petroleum hydrocarbons (TEH) as gasoline (EPA 5030/8015) and as diesel and kerosene (EPA 3510/8015), for total oil and grease (SMWW 17:5520 E&F), and for purgeable halocarbons (EPA 8010) and purgeable aromatics (EPA 8020). The results are shown in Tables 4-4 and 4-5. About 755 gallons of water were then removed from the excavation while skimming with a vacuum truck. Based on the analytical results, California constituent Maximum Contaminant Levels (MCLs) for drinking water were slightly exceeded for benzene, 1,1 dichloroethane, and 1,4 dichlorobenzene. However, no constituents were found at hazardous waste concentrations. The water was then taken to the GORC recycling facility in Redwood City, California under a non-hazardous waste manifest,

TABLE 4-4 SUMMARY OF DETECTED HYDROCARBON COMPOUNDS IN WATER REMOVED FROM EXCAVATION (SAMPLE WA-1)

Gasoline (mg/L)	Diesel (mg/L)	Kerosene (ug/L)	Oil & Grease (mg/L)	Benzene (ug/L)	Toluene (ug/L)	Ethyl Benzene (ug/L)	Total Xylenes (ug/L)
21	23	< 50	42	q. 7	2.8	20	220

TABLE 4-5 SUMMARY OF DETECTED VOLATILE (EPA 8010 AND 8020) COMPOUNDS IN WATER REMOVED FROM EXCAVATION (SAMPLE WA-1)

Detected Compound	Concentration (ug/L)
1,1 Dichloroethane	16
1,1,1 Trichloroethane	3.5
Trichloroethylene	1.2
1,4 Dichlorobenzene	14
Benzene	1.8
Toluene	18
Ethylbenzene	26
Total Xylenes	170

4.3 IN-SITU CONFIRMATORY SAMPLING

In order to confirm that the petroleum hydrocarbon concentrations in soil had been removed to below the target limits, soil samples were collected at the excavation limits. Each of these samples was analyzed for TEH-gasoline, BTEX compounds, TEH-diesel and kerosene, and total oil and grease. On average, samples were dollected at a frequency of every twenty linear feet along sidewalls and every 625 square feet across the bottom of the excavation. In general, when selecting a sample location, the viginity of the potential sample was screened for signs of hydrocarbon contamination visually, by odor, and for volatile compounds using a photoionization detector equipped organic vapor meter (OVM). The precise sample location was that where the screening methods indicated the highest possibility of hydrocarbon contamination.

Samples collected along the northwestern wall of the remediation area were collected using a slightly different procedure from that described in the previous paragraph. Along the length of this excavation boundary sheet pilings were driven into the ground in order to protect the integrity of the neighboring structure, as described in Section 4.5. Placement of the sheet pilings precluded collection of soil samples once the face of this wall was exposed during excavation. Instead samples along this wall were collected prior to sheet piling placement by potholing with a small backhoe every 20 feet along the boundary and collecting samples

directly from the backhoe bucket. Visual, odor, and OVM screening was then used on the soil in the backhoe bucket to select the sample location.

A two part sample reference (ID) of the form <L>ocation-<N>umber, e.g. N-2, was used to identify the collected confirmatory samples. The letters N, S, E, W and B were used in the ID prefix to denote the sample location as being from the north, south, east, west or bottom excavation boundary. The compass directions refer to site directions, e.g. site-north, with the true northwestern property line considered to lie due north in the site orientation. The ID suffix is simply the numerical order of the sample along a specific boundary. For example, sample S-2 was the second sample collected from the site-south excavation wall. A number of miscellaneous samples were taken in addition to the confirmatory wall and bottom samples. In general these samples follow the same ID pattern except that the location prefix used is longer, usually including a descriptive acronym. For example a sample taken from the east side of the aggregate base import material stockpile was given the ID: ABE-1.

A summary of analyses performed on each collected confirmatory wall and bottom sample is provided in Table 4-6. The analytical results are presented in Tables 4-7 and 4-8. A discussion of results is presented in the text which follows.

As described in Section 4.1, excavation and confirmatory sampling was performed iteratively: if an initial confirmatory sample indicated hydrocarbon concentrations exceeding the soil cleanup targets, further excavation, if possible, was performed in the vicinity of the offending sample. The locations and summary of results for samples which failed the cleanup targets in the preliminary round of excavation are shown as filled circles in Figure 4-4. The locations of samples which passed the cleanup targets are indicated with an overlying cross and circle.

All of the soil samples collected along both the site-north and east excavation boundaries were found to contain hydrocarbon concentrations in excess of the soil cleanup targets. Along the north wall, gasoline, BTEX compounds, diesel, kerosene, and oil and grease were each observed in elevated concentrations. Along the east wall diesel, xylenes and oil & grease were each observed in elevated concentrations. Because the excavation extended to within about 1 to 2 feet of the PG&E property line in these directions, further excavation was


TABLE 4-6
SUMMARY OF CONFIRMATORY SOIL SAMPLE ANALYSES
RELATED TO THE EXCAVATION OF THE FORMER DIESEL TANK AREA

SAMPLE	SAMPLE Location	SAMPLE Depth	SAMPLE Date	TVHg	втех	TPHd	O&G	EPA 8010	EPA 8020
B-1	Exc. Bottom	4.5'	11/19/91	Х		Х	Х	Х	Х
B-2	Exc. Bottom	7'	11/19/91	X	~	x	×	1 ^	^
B-3	Exc. Bottom	5.5'	11/20/91	x	X	x	×]	
B-4	Exc. Bottom	3.3 8'	11/20/91	x	x	x	×]	
B-5	Exc. Bottom	7.5'	11/20/91	X	^	x	x	x	х
B-6	Exc. Bottom	7.3 8'	11/22/91	x	Х	x	x	^	^
B-7	Exc. Bottom	8.5'	11/22/91	X	X	x	x		
B-8	Exc. Bottom	8.5'		X		X			
B-9		6'	11/23/91	,	X X		X		
II.	Exc. Bottom	1 1	11/23/91	X :		X	X	:	
B-10	Exc. Bottom	8.5'	11/23/91	X	X	X	X		
B-11	Exc. Bottom	8.5'	11/23/91	X	X	X	X		
B-13	Exc. Bottom	9.5'	12/02/91	X	X	Х	X	-	
B-14	Exc. Bottom	9.5'	12/05/91	X	Х	X	Х		
E-1	East Wall	3.5'	11/20/91	X	Х	Х	Х		
E-2	East Wall	1.5'	11/21/91	X	X	Х	Х		
E-3	East Wall	4.5'	11/22/91	X	X	Х	Х		
E-4	East Wall	8.5'	11/23/91	X	Χ	Χ	Х		
E-5	East Wall	5'	11/23/91	X	Х	Χ	Х		
N-1	North Wall	4.5'	11/19/91	Х	X	Χ	Χ		į
N-2	North Wall	4.5'	11/19/91	Х	Х	Χ	X	:	
N-3	North Wall	5.5'	11/19/91	Х	Χ	Χ	X	1	
N-4	North Wall	5.5'	11/19/91	Х	Х	Х	X		
N-5	North Wall	5.5'	11/19/91	Х	X	Χ	Х		
N-6	North Wall	5'	11/19/91	Х	Х	Χ	Х		
S-1	South Wall	3.5'	11/19/91	Х	Χ	Х	Х		
S-2	South Wall	5'	11/19/91	Х	Х	Χ	Х		
S-3	South Wall	4.5'	11/20/91	Х	Χ	Χ	Х		
S-4	South Wall	5'	11/22/91	Х	Х	Χ	Х		
S-5	South Wall	4.5'	11/23/91	Х	Х	Χ	Х		
S-6	South Wall	4.5'	11/23/91	X	Х	Х	X		
S-7	South Wall	4.5'	11/23/91	X	Х	Х	Х		
S-8	South Wall	5'	12/02/91	Х	Χ	Х	X		
W-1	West Wall	4'	11/19/91	X	X	X	X		
W-2	West Wall	4'	11/20/91	X	Х	X	X		
W-3	West Wall	5.5'	11/20/91	X	X	X	X		
W-4	West Wall	4'	11/20/91	X	X	x	X	'	
W-5	West Wall	5'	11/22/91	X	x	X	x]	
W-6	West Wall	4'	11/23/91	X	x	X	X		. [

TABLE 4-7
PETROLEUM HYDROCARBONS DETECTED IN CONFIRMATORY SOIL SAMPLES
RELATED TO THE FORMER DIESEL TANK AREA

	nple D.	Sample Depth	TPH as Gasoline (mg/kd)	TPH as Kerosene (mg/kg)	TPH as Diesel (mg/kg)	Benzene (ug/kg)	Toluene (ug/kg)	Ethyl- Benzene (ug/kg)	Xylenes (ug/kg)	O&G (mg/kg)
B-1		4.5'	ND	ND	ND	N/R	N/R	N/R	N/R	ND
B-2		7'	ND	ND	ND	ND	ND	DИ	ND	ND
B-3]	5.5'	ND	ND	ND -	ND	ND	ND	ND	ND
B-4		8'	290	ПO	130	10	21	900	6900	3300
B- 5		7.5'	ND	ND	ND	ND	ND	ND	ND	740
B -6		8'	ND	МD	ND	ND	ND	DN	ND	ND
B -7		8.5'	ND	ND	ND	ND	ND	ND	ND	ND
B-8	j	8.5'	ND	ND	ND	ND	ND	ND	ND	ND
B-9		6'	ND	ND	27	ND	ND	ND	ND	670
B-10		8.5'	1.6	ND	ND	ND	ND	ND	. 8.3	33
B-11		8.5'	ND	ND	130	ND	ND	ND	ND	1600
B -13		9.5'	ND	ND	ND	ND	ND	ND	ND	ND
B-14		9.5'	ND	ND	ND	ND	ND	ND	ND	ND
E-1		3.5'	ND	ND	ND	ND	ND	DN	ND	1600
E-2		1.5'	ND	NĐ	ND	ND	ND	ND	ND	1100
E -3		4.5'	ND	ND	1500	ND	ND	ND	ND	5600
E-4		8.5'	1.9	ND	51.7	ND	ND	ND	9	1200
E-5		5'	6.3	ND	5000	14	8	13	76	5300
■ N-1		4.5'	340	ND	340	ND	140	110	4500	8800
N-2		4.5'	ND	ND	410	ND	ND	ND	25	18000
N-3		5.5	45	ND	1200	ND	77	160	410	5100
N-4		5.5'	73	ND	2500	ŅD	110	77	920	8300
N-5		5.5'	120	6500	ND	12	140	61	1200	34000
N-6		5'	65	6000	ND	19	65	170	690	13000
S-1		3.5	ND	ND	ND	ND	ND	ND	ND	ND
S-2		5'	ND	ND	ND	ND	ND	ND	ND	100
S-3		4.5	ND	ND	21	ND	ND	ND	8.5	240
S-4		5'	ND	ND	ND	ND	ND	ND	ND	16
S-5		4.5'	ND	ND	ND	ND	ND	ND	ND	ND
S-6		4.5'	ND	ND	ND 700	ND	ND	ND	ND	300
S-7 S-8		4.5¹ 5'	15 ND	ND	730	ND	9.5	30	68	4000
		l	ND	ND	ND	ND	ND	ND	ND	ND
W-1 ₩-2		4' 4'	ND ND	ND	ND	ND	ND	ND	ND	ND
W-3		5.5'	ND ND	ND ND	ND	ND	ND	ND	ND	ND ND
W-4		3.5 4'	ND ND	ND ND	ND	ND	ND ND	ND	ND	ND 70
W-5		5'	ND ND	ND ND	15 ND	ND	ND	ND ND	ND	72 ND
W-6		4'	17	ND ND	1100	ND 53	ND	ND	ND 70	ND 4500
144-0		· · · · · · · · · · · · · · · · · · ·	1/	חאח	1100	5.3	11	33	79	4500





OW-4

QUIPMENT CO. YARD TAL RECYCLER)

LEGEND

Approximate PG 8

Limits of Excavat


Observation Well

Soil Sample Failing

Soil Sample Passir

•

G-10 Constituents Excer D-100 0-1000 Gas, Diesel, Oil & B-5, T-5 Benzene, Toluene, E-5, X-5





AQUA RESOURCES, INC. BERKELEY, CALIFORNIA

PG &E ENCON - GAS YARD

Initial Confirmatory Samples

JOB NO. 90262.2

Figure 4-4

DATE: February 1992


TABLE 4-8 SUMMARY OF VOLATILE (EPA:8010/8020) ORGANIC COMPOUNDS IN TWO CONFIRMATORY SOIL SAMPLES (IN UG/KG)

Detected Compound	B-1 (at 4.5 feet)	B-1 (Method Blank)	B-5 (at 7.5 feet)
methylene chloride	36	69	< 5.0
1,1-dichloroethane	< 5.0	< 5.0	< 5.0
1,1,1-trichloroethane	< 5.0	< 5.0	< 5.0
benzene	< 5.0	< 5.0	< 5.0
toluene	< 5.0	< 5.0	< 5.0
ethylbenzene	< 5.0	< 5.0	< 5.0
total xylenes	< 5.0	5.0	< 5.0

4.4 BACKFILL AND COMPACTION OF REPLACEMENT MATERIAL

Once remedial excavation was complete, the area shown in Figure 4-6 was backfilled and compacted from the indicated depth to the ground surface. Where excavations extended below the free groundwater level, gravel was placed to a level approximately 2 feet above the water level which was found at about 7 1/2 to 8 feet below ground surface. The gravel consisted of drain rock purchased from Gallagher & Burke that met the specifications of being similar to Type B Class 1 Permeable Material (Caltrans Standard Specification 68-1.025) having a maximum size of 2 inches in longest dimension. Class II aggregate base (AB) material was then used as backfill up to the finished grade.

To reduce the potential for the fine fraction in the AB to migrate into the permeable material, a filter fabric, Supac 4NP (Phillips Fibers Corporation), was used to separate the gravel and AB material. This fabric has an Equivalent Opening Size (EOS) of between 150 to 350 microns (50-100 sieve size), a minimum Mullen Burst Strength of 220 psi and minimum Puncture Resistance of 85 pounds. In addition, this geotextile is compatible with the organic contaminants found in the underlying groundwater.



Prior to backfilling, the exposed subgrade material was tested at two depths to determine the properties and in-situ relative compaction of the native materials at the site. All of the soils and compaction testing was performed by Construction Materials Testing Inc. The in-situ native soil test results are summarized in Table 4-9. Prior to backfilling the excavation areas, the native soil in areas of the excavation shallower than 7 feet was compacted to a measured relative compaction of 92%. In areas of the excavation originally 7 feet or deeper, no compaction could be performed due to the presence of groundwater and instead gravel was used to bring the bottom depth up to about 5 1/2 feet in total depth in order to form a solid base upon which to compact.

TABLE 4-9 SUMMARY OF NATIVE SOIL PROPERTIES AT TWO DEPTHS (prior to compaction)

Sample Depth (feet)	Soil Description	Optimum Moisture Content (%)	Maximum Dry Density (lb/ft ³)	In-Situ Moisture Content (%)	In-Situ Relative Compaction (% of max)
4.5	Sandy Clay w/Gravel	9.6	123.7	19.3	86
7.0	Clayey Sand w/Gravel	8.9	129.1	15.7	87

A sample was also collected of the AB backfill material and tested to determine the properties necessary to monitor the degree of compaction achieved during backfill and compaction activities. These tests found that the maximum dry density of the AB used was 134.5 lb/ft³ and its optimum moisture content was 6.7%. Because the supplied AB material was recycled, containing visible pieces of asphalt, representative samples were also collected to determine its petroleum hydrocarbon content. These results, shown in Table 4-10, indicated that although oil and grease was present in concentrations exceeding the established cleanup level of 1,000 mg/kg for this constituent, the chromatogram matched that of an asphalt standard. Because asphalt is not considered hazardous and does not contain constituents which are significantly soluble in groundwater, this material was approved for use as backfill.

TABLE 4-10 SUMMARY OF ORGANIC HYDROCARBON COMPOUND ANALYSES ON RECYCLED AB BACKFILL MATERIAL (COMPOSITE OF SAMPLES ABE-1, ABW-1, ABS-1 AND ABN-1)

G (/)	D (/)	K (/)	& G (/)	B (/)	(/;)	E B (/)	(/)	C (E A 8270)
< 1.0	< 1.0	< 1.0	2900*	< 5.0	< 5.0	< 5.0	< 5.0	All < 0.25

^{*} Oil and Grease confirmed as asphaltic compound

Once the gravel and geotextile fabric were in place, lifts of AB approximately 9 to 12 inches in uncompacted height were spread in the excavation area, compacted to a thickness of about 6 to 9 inches, and then tested for relative compaction. In order to pass the compaction specifications each lift which lie at depths greater than 3 feet below grade was required to reach 90% relative compaction, and each lift at 3 feet or shallower was required to reach at least 95% relative compaction. If a lift failed to reach sufficient compaction when tested, that lift was reworked and then retested until it passed the compaction specification. The final compaction test results are listed below in Table 4-11. Copies of the original field compaction test results can be found in Appendix C.

TABLE 4-11 SUMMARY OF FINAL COMPACTION TEST RESULTS

CMT Test Number	Depth of Test (feet)	Relative AB Compaction (%)
12	5.0	95
5	4.5	95
13	4.0	97
14	4.0	96
32	4.0	92
6	3.5	98
10	3.5	95
26	3.5	91
7	3.0	95
16	3.0	98
22	3.0	95
29	3.0	95
21	2.0	95
23	2.0	95
33	2.0	99
24	1.5	97
35	1.5	97
25	1.0	95
28	1.0	95
31	1.0	95
27	0.5	95
34	0.5	97
30	0.0	98
36	0.0	96
37	0.0	99

4.5 PROTECTION OF NEIGHBORING PROPERTY DURING REMEDIATION


The remedial excavation design called for excavation of soils near two neighboring properties, one to the northwest occupied by Metalcast Engineering, and one to the north east occupied by AAA Equipment Co. No buildings stand near the AAA Equipment and PG&E property line except for fence separating the two properties. During excavation a

buffer of 2 feet was established between the excavation wall and this fence in order to protect the fence's integrity. Near the Metalcast and PG&E property line however stands the Metalcast Engineering Co. building, a tall single story concrete structure, separated from the PG&E property by a fence. The building's location relative to the remediation area is shown in plan view on Figure 4-7. Since the area targeted for remedial excavation extended to the northwest property line, just a few feet from the edge of the Metalcast building, protective measures were taken to minimize the possibility for settlement of soil beneath the foundation of this building.

First an effort was made to establish the proximity of the PG&E property line to the Metalcast building. Using assessor parcel maps and other record information obtainable from the Alameda County Records Department along with field measurements at the site, TETRAD Engineering Inc. determined that the property line lay approximately 1 ±1/2 feet outside of the fence separating the two properties. This fence, torn down and later replaced at the conclusion of the remediation effort, lay within 2 1/2 feet of the Metalcast building. This places the property line approximately 1 1/2 ±1/2 feet southeast of the building.

Then, the initial state of integrity of the Metalcast building was recorded on videotape and benchmarks were established on all of the building panels which stand near the remediation area. Altogether, six panels were marked. The elevations of these benchmarks were then surveyed by TETRAD in order to establish a baseline for the purposes of monitoring any settlement the wall experienced during the remediation effort.

Following this, steel sheet pilings were driven to a depth of about 15 feet in a line approximately 3 feet southeast of the Metalcast building in the area shown on Figure 4-7. The purpose of the pilings was to prevent the subgrade below the building from collapsing during the adjacent remedial excavation. The length of this line of sheeting extended from a point about 10 feet from the north PG&E property corner to a point about 125 feet southwest of this corner, running parallel to the building wall.



Finally, following excavation, backfill and compaction activities, the sheet pilings were removed and the wall panel benchmarks resurveyed to determine if any settlement had occurred. The survey results, shown in Table 4-12, indicated that there was no settlement. A copy of the original TETRAD settlement monitoring report can be found in Appendix D.

TABLE 4-12 RESULTS OF SETTLEMENT MONITORING ON METALCAST ENGINEERING BUILDING

:		CHOMALLIMA	G DOILDING			
Panel Benchmark Number		Elevation on 11/19/91 (feet)*	Elevation on 1/9/92 (feet)*	Apparent Settlement (feet)		
	1	103.73	103.73	0		
	2	103.73	103.73	0		
	3	103.74	103.74	0		
	4	103.74	103.74	0		
	5	103.75	103.75	0		
	6	103.75	103.75	0		

^{*} Elevations are based upon an assumed datum and are not absolute elevations.

4.6 PROTECTION OF CLEAN BACKFILL FROM RESIDUAL HYDROCARBONS

During excavation, soil samples indicated that hydrocarbon concentrations were below the target levels along all excavation boundaries interior to PG&E property, however, elevated concentrations of hydrocarbons were found in the final excavation walls adjacent to both the northwest and northeast property lines. Along the northeast property line, two buried pipes containing a heavy black tarry product were uncovered which appeared to continue in extent beyond the PG&E property line. In order to protect the clean backfill placed into the excavations, measures were taken to reduce the mobility of the contaminants from these two properties.

4.6.1 Northeast Excavation Boundary

Soil concentrations above the cleanup targets for oil and grease, diesel, and xylenes were observed along the northeastern excavation wall bordering the AAA Equipment Co. yard. Tar was observed in several locations to seep out of the old fill which extends to a depth of 3 to 4 feet along this boundary. In addition, the two tar filled pipes were exposed along this wall buried at a depths of approximately 2 and 2 1/2 feet below grade and protruding about 2


feet into the excavation. In order to protect the clean backfill from contamination from these sources, two measures were taken.

First, two 120 foot long layers of 20 mil PVC plastic sheeting was suspended along this excavation wall to separate the clean backfill from the contaminated soil in the area shown on Figure 4-8. This was accomplished by folding one 20 foot width of sheeting in half over a 140 foot length of heavy rope, then dangling the doubled sheet from the neighboring fence with suspension lines tied to the sheet's rope spine. The PVC sheeting covered the adjacent soil to a depth of about 6 feet along the excavation wall.

Finally, the ends of the two tar filled pipes were covered in several layers of 6 mil visqueen, which was wire wrapped to hold it in place. Then, once the new backfill was placed and compacted up to the level of the old backfill, about 1 1/2 feet below the pipes, a plastic form was placed around the protruding pipe ends and a cement slurry was poured to effectively seal the pipe ends from leaking.


4.6.2 Northwest Excavation Boundary

Soil concentrations above the cleanup targets for gasoline, BTEX, diesel, kerosene, and oil and grease were observed in soil samples collected along the northwest excavation boundary bordering the property occupied by Metalcast Engineering. Due to the sheet pilings in place along all but the most northeastern 10 feet of this boundary, a plastic liner could not be draped on the wall since removing the pilings after backfilling would likely tear out the liner. Instead, only the 10 foot unpiled section was draped with plastic (as part of the measures described in Section 4.6.1), and the remaining excavation length was backfilled normally. However, in order to reduce the mobility of the boundary soil contaminants from precipitative leaching through the soil left in place, the overlying soil was covered with approximately 5 inches of asphaltic concrete. The remainder of the remediation area was also paved and graded to drain to the southwest as indicated in Figure 4-8.



4.7 MONITORING WELL INSTALLATION

Former monitoring well OW-3 was destroyed prior to excavation activities since it lay within the bounds of the remediation area. Following the remedial work, two new 2 inch diameter monitoring wells were installed. Well OW-6 was installed in the vicinity of the former tank cluster location to serve as well OW-3's replacement for monitoring the quality of groundwater underlying the subject area. The other new monitoring well, OW-7, was installed at the northeastern end of the remediation area, in the vicinity of the two tar-filled pipes, to gauge the likelihood of upgradient contamination in the shallow groundwater underlying the PG&E site. The locations of these new wells were approved by Alameda County Health. Figure 4-9 presents the locations of the present monitoring wells near the remediation area. Wells OW-1 and OW-2, not shown on this figure, lie nearer Coliseum Way on PG&E property and are shown in Figure 2-2.



5.0 POTENTIAL SOURCES OF UPGRADIENT CONTAMINATION

ARI conducted a limited Phase I preliminary site assessment of the Coliseum Way facility in November and December 1990. The purpose of this assessment was to attempt to determine if potential sources of groundwater contamination may exist upgradient from the Coliseum facility. The site assessment consisted of the following activities:

- 1) field reconnaissance of the site and surrounding area,
- 2) a file search of selected regulatory agencies,
- 3) a review of available maps and aerial photographs.

During the remedial excavation, two tar or heavy oil filled pipes were uncovered which appeared to originate from beyond the PG&E property line to the northeast. The contents of these pipes were characterized and found to be similar in character to some of the contaminants observed in the remediated soils. A discussion of the pipes and their content as well as the results of the first two activities performed in the preliminary site assessment are described below. The results of the map and photograph review were described in Section 2.3, Site History.

5.1 DESCRIPTION AND CHARACTERIZATION OF TAR FILLED PIPES

Two metal pipelines containing a heavy viscous oil or tar were uncovered during excavation along the northeast side of the PG&E property. Each pipeline was oriented approximately perpendicular to the northeastern property line. Once exposed, the tar began to slowly ooze from each pipe. The two pipes, one 12 inches in diameter with a smaller 4 inch diameter inner pipe and the other an 8 inch diameter corrugated line, were found buried at depths of 2 and 2 1/2 feet below grade, respectively. They were separated horizontally by a distance of about 2 feet.

The 4 inch inner pipeline was the first uncovered. Its terminus was discovered about 20 feet from the AAA Equipment Co. property at a depth of about 2 1/2 feet. It is unknown whether this pipe was intact in-situ or if it lay in broken sections as several lengths came out of the ground easily during excavation. Each of these lengths contained viscous tar or heavy oil and the soil surrounding the pipe was contaminated with a tar similar in appearance down to

the depth of the water table in the vertical direction and at least 10 feet laterally in either direction away from the pipe.

The outer pipe was first discovered about 5 feet from the AAA property line. At this exposure it appeared that most of the tar lie in the annular space between the two pipes. By attaching a chain to the inner pipe of the 12 inch line and tie pulling with the excavator bucket a 12 foot length of the inner pipe was removed, meaning this pipe, and presumably the outer pipe extends at least 7 feet under the AAA yard. The appearance of the two pipes with product in their annulus seems to indicate that this was a process pipeline at one time. Commonly, viscous fluids are heated in order to induce flow through a pipeline and this is sometimes accomplished by passing steam or hot water through an inner line to heat the fluid in the annular space.

The 8 inch diameter corrugated (culvert-type) pipe terminus was uncovered about 3 feet from the AAA property line and it too contained the heavy oil or tar. Visual inspection indicated that this pipeline may continue some unknown distance beyond the property line. Each of the two pipes were sealed at the excavation boundary as described in Section 4.6.1.

Another technique used historically to induce flow of a viscous petroleum product is the addition of solvents to reduce viscosity. In order to determine if the product found in the pipe contained solvents a sample (E-PiPE-2) of the product was collected from the 12 inch diameter pipe and analyzed for halogenated volatile organics, semivolatile organics and BTEX compounds, by EPA methods 8010, 8270 and 8020 respectively. This sample was additionally analyzed for petroleum hydrocarbons as gasoline, kerosene, diesel and motor oil. The results of these analyses, shown in Table 5-1, indicate that xylene, at low concentration of 11 ug/kg, was the only volatile compound detected of those tested. There was however a significant concentration of diesel, 7000 mg/kg or 0.7%, contained in the product and a number of polynuclear aromatic hydrocarbons (PAHs) were also detected in the tens of parts per million range.

TABLE 5-1 COMPARISON OF DETECTED COMPOUNDS IN PRODUCT SAMPLE E-PIPE-2 AND SOIL SAMPLES E-6 AND B-11

Detected	Analysis		Sample ID	
Compound	Method (EPA #)	E-PIPE-2	E-6	B-11
Xylene	¹ 8240, ² 8020	11 ug/kg ²	< 5 ug/kg ¹	< 5 ug/kg ¹
Chlorobenzene	¹ 8240, ² 8010	< 5 ug/kg	< 5 ug/kg ¹	130 ug/kg ¹
1,3-Dichlorobenzene	¹ 8240, ² 8010	< 5 ug/kg	< 5 ug/kg ¹	1100 ug/kg ¹
1,4-Dichlorobenzene	¹ 8240, ² 8010	< 5 ug/kg	< 5 ug/kg ¹	1800 ug/kg ¹
1,2-Dichlorobenzene	¹ 8240, ² 8010	< 5 ug/kg	< 5 ug/kg ¹	160 ug/kg ¹
Naphthalene	8270	< 5 mg/kg	0.5 mg/k g	< 1 mg/kg
Acenaphthene	8270	13 mg/kg	< 0.5 mg/kg	< 1 mg/kg
Fluorene	8270	52 mg/kg	0.9 mg/k g	< 1 mg/kg
Phenanthrene	8270	76 mg/kg	1.8 mg/k g	< 1 mg/kg
Anthracene	8270	13 mg/kg	< 0.5 mg/kg	< 1 mg/kg
Fluoranthene	8270	13 mg/kg	< 0.5 mg/kg	< 1 mg/kg
Pyrene	8270	72 mg/kg	3.0 mg/k g	1.9 mg/kg
Benzo(a)anthracene	8270	44 mg/kg	< 0.5 mg/kg	< 1 mg/kg
Chrysene	8270	30 mg/kg	< 0.5 mg/kg	< 1 mg/kg
Benzo(a)pyrene	8270	16 mg/kg	< 0.5 mg/kg	< 1 mg/kg
Gasoline	5030-8015	< 1 mg/kg	NA	< 1 mg/kg
Kerosene	3510-8015	< 1 mg/kg	< 1 mg/kg	< 1 mg/kg
Diesel	3510-8015	7000 mg/kg	3500 mg/kg	130 mg/kg
Motor Oil	3510-8015	< 10 mg/kg	6700 mg/kg	NA
Oil & Grease	5520 E&F	NA	NA	1600

Notes: NA = Not Analyzed

In order to determine whether or not the two pipelines were the source of contaminants found in neighboring soils, the EPA 8270 analysis for semivolatile organics was repeated on two soil samples obtained from the vicinity of the pipelines. Sample E-6 was collected approximately 2 1/2 feet below the 12 inch diameter pipe from the excavation sidewall. Sample B-11 was collected at a depth of 8 1/2 feet approximately 35 feet from the observed original terminus of the 12 inch diameter pipe. These samples were additionally analyzed for volatile organic compounds by EPA 8240 and TEH as diesel. Total oil and grease was also tested in sample

B-11. Both of these soil samples contained a visible tar product similar in appearance to that in the pipelines. A comparison of the results for samples E-PIPE-2, E-6 and B-11 is shown in Table 5-1. The soil in the vicinity of sample B-11 was later excavated due to the hydrocarbons present.

The results of the 8270 analysis for the product sample indicated that a number of PAHs are present in the pipeline product. Three of these PAHs were also detected in sample E-6 and one, Pyrene, was detected in all three of the samples. Diesel was also detected in all three samples. This may suggest that the heavier fraction of hydrocarbons present in the wall and bottom samples is of a similar nature to the pipeline product. Sample B-11 contained concentrations of chlorobenzene and the dichlorobenzenes which were not detected in the other two samples, indicating a probable volatile halocarbon source other than the pipelines.

5.2 RESULTS OF FIELD RECONNAISSANCE

The nearby area bounded by Coliseum Way and San Leandro Street, 45th Avenue and 54th Avenue, is presently occupied by industrial and commercial businesses, primarily concerned with metal processing and finishing, scrap metal sales, and auto service and body work.

The yard of the scrap metal dealer immediately adjacent to the site on the northeast contains various types of electrical equipment and machinery, hydraulic equipment, welding equipment, air conditioning equipment, transformers, drums marked battery fluid, paint cans, and oil soaked wood and a trailer. The metal finishing operations appear to include chrome plating, anodizing, and industrial plating. CIM Inc., a construction materials firm, is located at 833 47th Avenue. Chevron has a large facility on San Leandro Street between 45th and 46th Avenues which includes several large aboveground storage tanks.

5.3 AGENCY DATA

A city directory from 1969 at the Oakland Public Library shows that similar industries were in the area at that time. In addition, the Titanium Pigment Corporation, Division of the National Lead Co., a paint manufacturing company, was located at 4825 San Leandro Street in 1969. Superior Products Co., sealing compounds, occupied 833 47th Avenue in 1969.

The East Slough drainage is currently west and south of the PG&E property. The information provided by PG&E (Underground Tank Investigation Report, July 1988: Figure 9—
"Potentiometric Contour Map for July 21, 1988") indicates that the groundwater gradient at that time was toward the southwest. There are several sites which have been investigated by the Regional Water Quality Control Board (RWQCB) in the vicinity of the subject site, but none of them is located within 1000 feet of the site and upgradient (north to east). Figure 5-1 shows the locations of several sites with reported toxic or fuel spills in the vicinity of the PG&E site.

Learner Company at 768 46th Avenue is approximately 1100 feet from the site to the northwest. The soil under this site is contaminated with petroleum hydrocarbons and PCBs; however, it is unknown at the present time if the groundwater is contaminated. L&M Plating at 920 54th Avenue is approximately 1200 feet east of the property. The report at the RWQCB states that the groundwater under L&M has not been significantly impacted; however, the California Department of Toxic Substances Control is considering reopening the case.

Peterson Properties at 1066 47th Avenue is approximately 1500 feet north of the site. The Chevron Asphalt Terminal at 4525 San Leandro Street is approximately 1700 feet north of the site. The groundwater under both the Peterson site and the Chevron site has been reportedly contaminated with 560 ppb and 590 ppb total petroleum hydrocarbons respectively.

F&K Investment at 1259 48th Avenue is approximately 2000 feet northeast of the site. The groundwater under this site has been tested and had contamination levels of 46,000 ppb total petroleum hydrocarbons. It is unknown whether or not the contamination has migrated off site. AAA Equipment Co. at 765 50th Avenue is southeast of the site, across 50th Avenue; however, this site is so close to the property that if the groundwater has been affected by the diesel contamination on that site, and if there is any variation in the groundwater gradient, it may affect the PG&E property. The RWQCB has no information at this time regarding the status of the groundwater at this site.

The California Department of Toxic Substances Control makes available various sources of information to assist in site investigations. The following sources were reviewed:

CERCLIS - the Environmental Protection Agency's computerized database

ASPIS — the Abandoned Site Program Information System used to track potential historical and present day hazardous waste sites

Cortese List — data received from the State Water Resources Control Board, the California Integrated Waste Management Board, and the California Department of Toxic Substances Control


Bond Expenditure Plan — list of sites for which State bond funds will be spent for cleanup or oversight. These sites are also known as State "Superfund" sites.

The CERCLIS list included NL Industries Inc., Pigments and Chemical Division, at 4701 San Leandro Street. We have contacted the local office of the U.S. Environmental Protection Agency which has the CERCLIS files. The reply we received stated that the NL Industries Inc. site was put on the CERCLIS list by error and there does not appear to be an uncontrolled hazardous waste problem at the site.

The ASPIS list also included the NL Industries site, noting that the plant is inactive and that no file was found at California Department of Toxic Substances Control.

5.4 CONCLUSIONS

The information provided by agencies and agency personnel was used as reported. Although we have not found any agency file documentation that contaminated groundwater has migrated to the PG&E site, results of soil and groundwater samples indicate that an off-site, upgradient fuel leak may have occurred.



6.0 CONCLUSIONS

6.1 SOILS

Approximately 1,760 cubic yards of soil contaminated with petroleum hydrocarbons above the site specific cleanup levels have been removed from the subject property. Limits of excavation were determined by confirmatory in-situ sampling and by the property boundaries. Sampling of the northeastern and northwestern boundaries indicates that soil outside the PG&E property is contaminated with hydrocarbons. Northeastern boundaries is upgradient of the site. New backfill material at the site has been temporarily protected from possible contamination from the offsite sources by placing PVC lining along northeastern site to the depth of about 6 feet from the ground surface. Currently applied protection of the backfill material at the PG&E property is temporary only.

The type and extent of contamination at the offsite upgradient property needs to be investigated and further action can be determined based on the results of such investigation.

Input from the regulatory agency is required to initiate such investigation.

6.2 GROUNDWATER

It can be expected that the removal of contaminated soil will result in the improvement of the groundwater quality at the site. Consistent with the agreement with Alameda County Health it is recommended to monitor the groundwater for a period of one year. Sampling should be performed quarterly. Wells which are directly impacted by this remediation action are OW-1, OW-4, OW-6, and OW-7. These wells should be monitored for TVH as gasoline, BTXE, TPH as diesel, total oil and grease, and total lead. Well OW-7 is located near the upgradient end of the remediation area.

7.0 LIMITATIONS

The excavation limits were based on visual examination, vapor screening with an organic vapor detector, and detectable odor screening in the field. Soil samples obtained for chemical analyses represent conditions encountered at a specific point where taken. Chemical laboratory analyses were performed under the direction of others. Although a responsible effort has been made by ARI to test soil samples for likely contaminants in the areas that have been excavated, ARI cannot provide a guarantee either express or implied that other hazardous contaminants are not present at this site.

This report specifically does not address the issues associated with surface soil lead contamination from paint chip residues associated with the former gas holder tank. These issues are described separately in the ARI report "Preliminary Site Assessment and Workplan for Additional Investigation ... Former Gas Holder Tank Area".

AQUA RESOURCES, INC PECEIVED

DEC - 0 1991



B C Analytical

1255 POWELL STREET • EMERYVILLE, CA 94608 • (415) 428-2300 • Fax (415) 547-3643

FILE Anal Results / Report Backup

Log No.:

E91-11-009-2

Date Sampled:

11/01/91

Date Received:

11/01/91

Date Mailed:

Report To:

ATTN: Mr. Mark Milani

Aqua Resources Inc.

Berkeley, CA 94704

CALIFORNIA HAZARDOUS WASTE ASSESSMENT BIOASSAY: SCREEN

2030 Addison Street, Suite 500

est Organisa		Pimeph									Sou	rce			Fish		
ution Wate	r	Fresh	1			Source	_ Emer	yvill	e Dech	lori	nated	Temp	perature	Range _	19.2	- 19	<u>5</u> ∘c
							Tap	Water	with	Matr:	ix Modi	fier	S	_			
eration:	Air X	Oxyge	n	None		Test init	iated	11.0	8.91		_ Con	rol initi	al hardne	ess	43 m	g/L	
Bioassay	Time,	Cor	ntrol			7 750	IT	727			ution						
Conditions	Hrs	<u> </u>		,	mg/L	 	mg/L		mg/L		0 mg/L		r	ļ			,
		No. 10	% 100	No. 10	% 100	No. 10	% 100	No.	% 100	No.	%	No.	%	No.	%	No.	%
	Start	10	100	10	100	10		10		10	<u>t</u> .						
■ Organisms	24	10	100	10	100	10	100 100	10	100	10							
_Surviving	48	10	100	10	100	1	100			10	100					ļ	
Ĭ	72	10	100	10	100	10	100	10	100 100	10	i — — —						
ļ	96	1 19	8.8	!	8.8	1		10	0.0	10	9.0			<u> </u>			
	Start		9.0	9.1		9.1										ŀ	
Dissolved	24	-	8.5	}	8.8			1	.0	·····	7.1						
Oxygen mg/L	48	ļ	8.6	8.8		9.0				9.2							
■ mg/L	72		8.5		8.9		.9	l	.1 .9		8.8						
	96	ļ	7.9	!	7.8		.8		.8		9.0			 		ļ	
	Start	-	7.3	<u></u>	7.3	<u> </u>	.2		1.1		7.8			1		<u> </u>	
	24		7.3	L	7.9		.3		3.2		8.2						
pН	48		7.6		7.6		.3 .7	l	.7		7.6			 		 	
	72		7.7		7.7		<u>.,</u>		- /		7.7	···-		 		<u> </u>	
	96	+ 1	19.3		9.3	19				-	19.2			-			
	Start		19.5		$\frac{9.5}{9.5}$	19		L	.5		19.5			-		 	
	24	[19.3	l	9.3	19			.2		19.2			-			
mperature	48 72	ł	9.5		9.4	19			.2		19.3			+			
•	96	1	19.5	1	9.4	19		1	.2		19.3			-		1	
<u> </u>	90	>750				1		1	5% confi		19.3		D		-1.7-	<u> </u>	——
RESULTS	TL _{m*}	- 750	ш6, п	_ Toxic	ity Units			li	mits of TI	aence -m Not	Estab	Lish	erce dundiluع	nt surviv ited sam	ai in ple <u>No t</u>	Appl	i cab (
Len	gth of fish,	cm: Max	· · · · · · · · · · · · · · · · · · ·	4.1			3.4			3.7	7				<u></u>		
	ght of fish,			0.7			0.3		ean				as where 96 h least one d ished.				

D.L. Pulliam

B C Analytical 1255 POWELL STREET • EMERYVILLE, CA 94608 • (415) 428-2300 • Fax (415) 547-3643

Report To:

AQUA RESOURCES, INC **RECEIVED**

NOV 2:0 1991

JOB NO.	90262.	02
FILE_Lo	90262. 6 result	2

TOXICITY BIOASSAY

Log No.:

E91-11-009-1

Date Sampled:

11/01/91

11/01/91

Date Received: Date Mailed:

NOV 1 8 1991

CALIFORNIA HAZARDOUS WASTE ASSESSMENT BIOASSAY: **SCREEN**

2030 Addison Street, Suite 500

Aqua Resources Inc.

Berkeley, CA 94704

ATTN: Mr. Mark Milani

est Organisr	n	<u>Pimepb</u>	nales_	prome	<u>las, f</u>	athea	d minn	lOW			Sou	rce	1	'homas	Fish	Compa	ny
ution Wate	r	Fresh	1			Source								Range _	18.7	19	_4 °C
											x Modi						
veration:	Air X	Oxyger	n	None		Test init	iated	11.1	1.91		Cont	rol initi	al hardne	ess	43 п	ıg/L	·
Bioassay	Time,	Cor	ntral		Dilution												
Conditions	Hrs	Coi	iti Oi	250	mg/L	250	mg/L	750	mg/L	750	mg/L						
		No.	%	No.	%	No.	%	No.	%	No.	%	No.	%	No.	%	No.	9/0
	Start	10	100	10	100	10	100	10	100	10	100						
	24	10	100	10	100	10	100	10	100	10	100						
Organisms Surviving	48	10	100	10	100	10	100	10	100	10	100						
Surviving	72	10	100	10	100	10	100	10	100	10	100						
	96	10	100	10	100	10	100	10	100	10	100						
_	Start		8.9	,	8.9	8	.7	8	.6		9.1						
Dissolved	24		8.6		9.6	8	.5	8	.2		8.7						
Oxygen	48		8.4		8.6	8	.5	8	.5		9.6					 	
mg/L	72	10.9		1	1.6	11	.8	10	.8	1	0.9			i			
	96	1	.0.8	1	1.3	11	.3		.8		1.1				10 ALA		
	Start	7.6			7.6	7	.7	7	.6		7.6						
	24		7.6		7.7	7.6		7	7.6 7.7					T			
pН	48		7.7		7.7		.7	7	.7	•	7.7					1	
	72	İ	7.7		7.7	7	.7		.7		7.7						
	96		7.6		7.6	7	. 6	7	.5		7.6					1	
	Start	1	9.3	1	9.3	19	.2	19	.3	1	9.2						
	24	1	9.2	1	9.3	19	.3		. 4		9.4						
perature	48	1	9.1	1	9.2	19		19			9.3						
	72	1	9.3	1	9.3	19		19			9.4						
	96	1	8.7	1	8.8	18		1.8		-	8.8				-	†	
RESULTS	TL _{m*}	>750	mg/L	_ Toxic	N ity Units		_1:1	1 - 0	cn/ andi-	J	Estab	lishe	Perce d undilu	nt surviv	al in ple <u>Not</u>	Appl	icab
				4.1			3.4			3.7	•						
		ish, g.: Max		Min 0.79 Min 0.3						In cases where 96 hour mortality does not equal or exceed 50% in at least one dilution of the sample, no TL _m value is established.							

D.L. Pulliam

· · · · · · · · · · · · · · · · · · ·	AQU	4 RES	OURC	ES, INC.				SHIPME	NT NO.:_	<u> </u>
. •	<u></u>			CUSTODY		RD -		PAGE_	or	1
	460							DATE	11/119	71
	PROJEC	T NAME:	PG+6	= - Colis	eum	way.	 :			1
	PROJEC	т ио.:	9026	7						
Sample Number	Location	Type of	Sample	Type of Con	tainer		of Preserva Chemi		Analysis	Required
	(Depth)	Material	Method			t4°C	<u> </u>	1	Some	posite
<u>5B-73-1</u>	5-51/2	50.1	Dreve.	BrassTu	<u> 2€</u>	11		Ţ	and n	un
SB-24-1	l II	- ((- 11	11		1,1			Bioas	ray for
58-25-1	11		7)	11		11				WASTE
58-26-1	11									· · ·
DW-4-1	Wellow 4	Water	Bailer	500 ml A	mber	±4°C			Rioa	SSay
								_:	ļ	
						ļ			<u> </u>	
				_		-			<u> </u>	
		<u> </u>		_						
			ļ .	_		-	l			
		 		<u> </u>		-				
				_						
	<u> </u>		_							
	_	 							_	
		- -				_				
						_	\ <u>-</u>		-	
	_\ 					<u> </u>	-			
Total Number of	Samples Si	ipped: 🔑	Sampl	er's Signature:		<u>u</u>				Date
Relinquished By:	-17.	<l=< td=""><td></td><td>Received Signatur</td><td>34: Xa</td><td>els</td><td>3BU-</td><td><u>~</u></td><td></td><td>11/1/8]</td></l=<>		Received Signatur	34: Xa	els	3BU-	<u>~</u>		11/1/8]
Signature Printed Name_	Agran	てんしょうせ	SSMGN	Printed	Name	<u> </u>		ien.		Time
Company Fla	un Ro	<u>50 L.CCC-</u>	S INC.	Compan	Y	$2 \subset A_1$	~~~~,T	- C. 		11:00
Reason For		115		Received	Bv:					Date
Relinquished By: Signature				Signatur	e					\ <u>-</u>
Printed Name_										Time".
Сотрапу				Complex	1					<u></u>
Reason										
REMARKS:					d					
Norm	al 2	Wee	k Tur	naround	*\	L 6	51A)	540	o-74	-96
FAX	copy	of r	esults	s to Vo	yy te	ي لا /	コペノ	1		, -
		•								
	121	OA-1	4A7	SCREE	7/					
Special Shipmer										
Special dispersion		- •								
								-		



Curtis & Tompkins, Ltd., Analytical Laboratories, Since 1878

2323 Fifth Street, Berkeley, CA 94710, Phone (415) 486-0900

DATE RECEIVED: 11/19/91 DATE REPORTED: 11/22/91

> AQUA RESOURCES, INC RECEIVED

> > NOV 2 6 1991

JOB NO._____

LABORATORY NUMBER: 105830

CLIENT: AQUA RESOURCES

PROJECT ID: 90262.2

LOCATION: PG&E: ENCON

RESULTS: SEE ATTACHED

QA/QC Approval

Final A

Berkeley

Wilmington

Los Angeles



LABORATORY NUMBER: 105830 CLIENT: AQUA RESOURCES PROJECT ID: 90262.2 LOCATION: PG&E: ENCON DATE RECEIVED: 11/19/91
DATE EXTRACTED: 11/20/91
DATE ANALYZED: 11/21/91
DATE REPORTED: 11/22/91

Extractable Petroleum Hydrocarbons in Soils & Wastes California DOHS Method LUFT Manual October 1989

LAB ID	SAMPLE ID	KEROSENE RANGE (mg/Kg)	DIESEL RANGE (mg/Kg)	REPORTING LIMIT* (mg/Kg)
105830-1	S - 1	ND	ND	10
105830-2	B - 1	ND	ND	10
105830-3	S - 2	ND	ND	10
105830-4	B - 2	ND	ND	10
105830-5	W - 1	ND	ND	10

ND = Not Detected at or above reporting limit.

*Reporting limit applies to all analytes.

QA/QC SUMMARY

RPD, %		1 0
RECOVERY, %	•	8 9



LABORATORY NUMBER: 105830 CLIENT: AQUA RESOURCES

PROJECT ID: 90262.2 LOCATION: PG&E: ENCON DATE RECEIVED: 11/19/91
DATE ANALYZED: 11/21/91
DATE REPORTED: 11/21/91

ANALYSIS: HYDROCARBON OIL AND GREASE

METHOD: SMWW 17:5520 E&F

LAB ID	SAMPLE	ID	RESULT	UNITS	REPORTING LIMIT
105830-1	S - 1		ND	mg/Kg	5 0
105830 - 2	B - 1		ND	mg/Kg	5 0
105830-3	S - 2		100	mg/Kg	50
105830-4	B - 2		ND	mg/Kg	5 0
105830-5	W- 1		ND	mg/Kg	5 0

ND = Not detected at or above reporting limit

QA/QC SUMMARY

	•
RPD, %	?
RECOVERY, %	95
	75



LABORATORY NUMBER: 105830 CLIENT: AQUA RESOURCES PROJECT ID: 90262.2 LOCATION: PG&E: ENCON

DATE RECEIVED: 11/19/91
DATE ANALYZED: 11/20/91
DATE REPORTED: 11/21/91

Total Volatile Hydrocarbons with BTXE in Soils & Wastes
TVH by California DOHS Method/LUFT Manual October 1989
BTXE by EPA 5030/8020

LAB ID	SAMPLE ID	TVH AS GASOLINE (mg/Kg)	BENZENE (ug/Kg)	TOLUENE	ETHYL BENZENE (ug/Kg)	TOTAL XYLENES (ug/Kg)
105830-1	S-1	ND(1.0)	ND(5.0)	ND(5.0)	ND(5,0)	ND(5.0)
105830 - 2	B - 1	ND(1.0)	N/R	N/R	N/R	N/R
105830 - 3	S - 2	ND(1.0)	ND(5.0)	ND(5,0)	ND(5,0)	ND(5.0)
105830 - 4	B - 2	ND(1.0)	ND(5.0)	ND(5.0)	ND(5.0)	ND(5.0)
105830 - 5	W- 1	ND(1.0)	ND(5.0)	ND(5.0)	ND(5.0)	ND(5.0)

N/R = Not Requested

ND = Not detected at or above reporting limit; Reporting limit indicated in parentheses.

QA/QC SUMMARY



DATE RECEIVED: 11/19/91

DATE ANALYZED: 11/21/91

DATE REPORTED: 11/22/91

LABORATORY NUMBER: 105830-2

CLIENT: AQUA RESOURCES PROJECT ID: 90262.2 LOCATION: PG&E: ENCON

COCATION; PORE; E

SAMPLE ID: B-1

EPA 8010: Volatile Halocarbons in Soil & Wastes Extraction Method: EPA 5030 - Purge & Trap

~		REPORTING
Compound	RESULT	LIMIT
	ug/Kg	ug/Kg
Chloromethane	ND	10
Bromome thane	ND	10
Vinyl chloride	ND	10
Chloroethane	ND	10
Methylene chloride	3 6	5.0
Trichlorofluoromethane	ND	5.0
l, l-Dichloroethene	ND	5.0
l, l-Dichloroethane	ND	5.0
cis-1,2-Dichloroethene	ND	5.0
trans-1,2-Dichloroethene	ND	5.0
Chloroform	ND	5.0
Freen 113	ND	5.0
l, 2-Dichloroethane	ND	5.0
1,1,1-Trichloroethanc	ND	5.0
Carbon tetrachloride	ND	5.0
Bromodichloromethane	ND	5.0
1,2-Dichloropropane	ND	5.0
cis-1,3-Dichloropropene	ND	5.0
Trichloroethylene	ND	5.0
1,1,2-Trichloroethane	ND	5.0
trans-1,3-Dichloropropene	ND	5.0
Dibromochloromethane	ND	5.0
2-Chloroethylvinyl ether	ND	10
Bromoform	ND	5.0
Tetrachloroethylene	ND	5.0
1, 1, 2, 2-Tetrachloroethane	ND	5.0
Chlorobenzene	ND	5.0
l, 3-Dichlorobenzene	ND	5.0
1,2-Dichlorobenzene	ND	5.0
l, 4 - Dichlorobenzene	. ND	5.0

ND = Not detected at or above reporting limit.

QA/QC SUMMARY



LABORATORY NUMBER: 105830-2

CLIENT: AQUA RESOURCES PROJECT ID: 90262.2

LOCATION: PG&E: ENCON

SAMPLE ID: B-1

DATE RECEIVED: 11/19/91 DATE ANALYZED: 11/21/91

DATE REPORTED: 11/22/91

EPA 8020: Volatile Aromatic Hydrocarbons in Soils & Wastes Extraction Method: EPA 5030 - Purge & Trap

COMPOUND	Resul ug/Kg	Reporting Limit ug/Kg
Benzene	. ND	5.0
Toluene	. ND	5.0
Ethyi Benzene	. ND	5.0
Total Xylenes	ND	5.0
Chlorobenzene	. ND	5.0
1,4-Dichlorobenzene	. ND	5.0
1,3-Dichlorobenzene	. ND	5.0
1,2-Dichlorobenzene	. ND	5.0
ND = Not detected at or above reporting limit.		•
QA/QC SUMMARY		
% SURROGATE RECOVERY	======	100



LABORATORY NUMBER: 105830-METHOD BLANK

CLIENT: AQUA RESOURCES

PROJECT 1D: 90262.2 LOCATION: PG&E: ENCON DATE ANALYZED: 11/21/91 DATE REPORTED: 11/22/91

EPA 8010: Volatile Halocarbons in Soil & Wastes Extraction Method: EPA 5030 - Purge & Trap

		REPORTING
Compound	RESULT	LIMIT
	ug/Kg	ug/Kg
Chloromethane	ND	10
Bromomethane	ND	10
Vinyl chloride	ND	10
Chloroethane	ND	$\hat{1}$ $\hat{0}$
Methylene chloride	69	5.0
Trichlorofluoromethane	ND	5.0
I, l-Dichloroethene	ND	5.0
l, l-Dichloroethane	ND	5.0
cis-l,2-Dichloroethene	ND	5.0
trans-1,2-Dichloroethene	ND	5.0
Chloroform	ND	5.0
Freon 113	ND	5.0
l, 2-Dichloroethane	ND	5.0
l, l, l-Trichloroethane	ND	5.0
Carbon tetrachloride	ND	5.0
Bromodichloromethane	ND	5.0
l, 2-Dichloropropane	ND	5.0
cis-1,3-Dichloropropene	ND	5.0
Trichloroethylene	NĐ	5.0
l, l, 2-Trichloroethane	ND	5.0
trans-1,3-Dichloropropene	ND	5.0
Dibromochloromethane	ND	5.0
2-Chloroethylvinyl ether	ND	10
Bromoform	ND	5.0
Tetrachloroethylene	ND	5.0
l, l, 2, 2-Tetrachloroethane	ND	5.0
Chlorobenzene	ND	5.0
l, 3-Dichlorobenzene	ND	5.0
l, 2-Dichlorobenzene	ND	5.0
l, 4-Dichlorobenzene	ND	5.0

ND = Not detected at or above reporting limit.

QA/QC SUMMARY



LABORATORY NUMBER: 105830-METHOD BLANK

CLIENT: AQUA RESOURCES

PROJECT ID: 90262.2 LOCATION: PG&E: ENCON DATE ANALYZED: 11/21/91 DATE REPORTED: 11/22/91

EPA 8020: Volatile Aromatic Hydrocarbons in Soils & Wastes Extraction Method: EPA 5030 - Purge & Trap

COMPOUND	Resulug/Kg	Reporting Limit ug/Kg
Benzene	. ND	5.0
Toluene	. ND	5.0
Ethyl Benzene	. ND	5.0
Total Xylenes	. 5.0	5.0
Chlorobenzene	. ND	5.0
1,4-Dichlorobenzene	. ND	5.0
1,3-Dichlorobenzene	. ND	5.0
1,2-Dichlorobenzene	. ND	5.0
ND = Not detected at or above reporting limit.		
QA/QC SUMMARY		
% SURROGATE RECOVERY	100	



MS/MSD SUMMARY SHEET FOR EPA 8010\8020

Operator: Analysis date: ΑV

Spike file: 324W/X002

Sample type:

11/20/91 SOIL

Spike dup file: 324W/X003 Instrument: GC12

Sample ID:

105802-26

Sequence Name: NOV 20

8010 MS/MSD DATA (spiked at 20 ppb)

SPIKE COMPOUNDS		READING	RECOVERY	STATUS	LIMITS	
1,1-Dichloroet	hene	21.53	108	% OK	59 -	172
Trichloroethen	e	19.10	96	% OK	62 -	137
Chlorobenzene		19.66	98	% OK	60 -	133
SPIKE DUP COMPOUN	DS .					
1,1-Dichloroet	hene	20.12	101	% OK	59 -	172
Trichloroethen	e	18.57	93	% OK	62 -	137
Chlorobenzene		18.80	94	% OK	60 -	133
SURROGATES						
BROMOBENZENE (MS)	106.00	106	% OK	70 -	120
BROMOBENZENE (MSD)	105.00	105	% OK	70 -	120
Chlorobenzene SPIKE DUP COMPOUN 1,1-Dichloroet Trichloroethen Chlorobenzene SURROGATES BROMOBENZENE (DS hene e MS)	19.66 20.12 18.57 18.80	98 101 93 94	% OK % OK % OK %	59 - 62 - 60 -	13 17 13 13

8020 MS/MSD DATA (spiked at 20 ppb)

SPIKE COMPOUNDS	READING	RECOVERY	STATUS	LIMITS	
Benzene	19.66	98 %	OK	66 -	142
Toluene	19.13	96 %	OK	59 -	139
Chlorobenzene	19.08	95 %	OK	60 -	133
SPIKE DUP COMPOUNDS				•	
Benzene	18.90	95 %	OK	66 -	142
Toluene	22.01	110 %	OK	59 -	139
Chlorobenzene	18.20	91 %	OK	60 -	133
SURROGATES					
BROMOBENZENE (MS)	100.00	100 %	OK	70 -	120
BROMOBENZENE (MSD)	100.00	100 %	OK	70 -	120

RPD DATA

8010 COMPOUNDS	SPIKE	SPIKE DUP		RE	D	STATUS	LIMITS	
1,1-Dichloroethene	21.53	20.12		7	8	OK	<=	22
Trichloroethene	19.10	18.57		3	%	OK	<=	23
Chlorobenzene	19.66	18.80		4	૪	OK	<=	21
8020 COMPOUNDS								
Benzene	19.66	18.90		4	%	OK	<=	21
Toluene	19.13	22.01	:	14	%	OK	<=	21
Chlorobenzene	19.08	18.20		5	[%]	OK	<=	21

CHAIN OF PG & E PG & E PG Z 6 Of Sample Method Drive II II II S.Hama Drive S.Hanae Drive	Type of Container Brass Tube II II II III III	Type of Pr	DATE	OF	
PG&E 9026 of Sample 1 Method Drive 11 11 11 S.Hamas Drive 5.Hanne	: ENCON 2.2 Type of Container BrassTube 11 11 11 11 11	Type of Pr Temp C +4°C u ii ii ii ii	eservation	Analysis Requi	
9026 of Sample I Method Drive II II II II S.Hama Drive S.Hanne Drive	Type of Container Brass Tube 11 11 11 11 11	Temp C +4°C	eservation	Analysis Requi	
of Sample Method Drive 11 11 11 11 S.Hame Drive S.Hame Drive	Type of Container Brass Tube II II II III III	Temp C +4°C		+ + + + +	ired
Method Drive 11 11 11 S.Hama Drive S. Hanne Drive	Brass Tube	Temp C +4°C		+ + + + +	
Drive 11 11 11 11 S.Hama Drive S.Hanne	11 11 11 11 11 11 11 11 11 11 11 11 11	±4°C] +] +] +	
S.Hames Drive S. Hanne	11 11 11 11 11 11 11 11 11 11 11 11 11	11 02 11 11 11 11 11 11 11 11 11 11 11 11 11) + 	
S.Hame Drive S.Hanne	1) 1) 1) 1) 1)	11] - - - - - - - - -	
S.Hamas Drive S.Hanne Drive	1) 	11		1+ .	
S.Hame Drive S.Hanne Drive	11	11			
S.Hamas Drive S.Hanne Drive	11	11		1 1	
Drive 5. Hanne Drive	11	_			
Drive 5. Hanne Drive	11	11		<u></u>	
5. Hanne Drive	11			1 *	
Drive		11		1*	
	11			<u> </u>	
13	41	11			
		_			
	_	_			
	_				
		_			
	-				
II Sampi	er's Signature:	M./	1) ate
<u></u>	Received By:	1-10	B	lil/	19 1
3100000	Signature Printed Name	Lourna	groun	; • • · · · · · · · · · · · · · · · · ·	
ros -	Company_C	* T Y De	Dear	16	Time [0](
					Date
	Printed Name				Time"
	Сотряпу				
	Printed Name Company			\ <u>-/</u>	_
	TEHD,	Received By: Signature Printed Name Company TEHD, O&G (TEH	Received By: Signature Printed Name Company	Company (+T Kenta) Received By: Signature Printed Name Company TEHD, OFG (TEH - 10ppm)	Company C+1 Volume 16 Received By: Signature Printed Name Company



Curtis & Tompkins, Ltd., Analytical Laboratories, Since 1878

2323 Fifth Street, Berkeley, CA 94710, Phone (415) 486-0900

DATE RECEIVED: 11/19/91 DATE REPORTED: 12/03/91

OUA RESOURCES, INC

-EO 🤠 🤄 1991

BORTO:

LABORATORY NUMBER: 105833

CLIENT: AQUA RESOURCES, INC.

PROJECT 1D: 90262.2

LOCATION: PG&E: ENCON

RESULTS: SEE ATTACHED

QA/QC Approval

Final Appl



LABORATORY NUMBER: 105833 CLIENT: AQUA RESOURCES, INC.

PROJECT ID: 90262.2

LOCATION: PG&E: ENCON

DATE RECEIVED: 11/19/91

DATE ANALYZED: 11/29-12/01/91

DATE REPORTED: 12/03/91

Total Volatile Hydrocarbons with BTXE in Soils & Wastes TVH by California DOHS Method/LUFT Manual October 1989 BTXE by EPA 5030/8020

LAB ID	SAMPLE ID	TVH AS GASOLINE	BENZENE	TOLUENE	ETHYL BENZENE	TOTAL XYLENES
	.	(mg/Kg)	(u g / Kg)	(u g / Kg)	(ug/Kg)	(ug/Kg)
·						
105833-1	N - 1	340	ND(80)	140	110	4,500
105833-2	N - 2	ND(2.0)	ND(10)	ND(10)	ND(10)	25
105833-3	N - 3	4.5	ND(10)	77	160	410
105833-4	N - 4	7 3	ND(10)	110	7.7	920
105833-5	N - 5	120	12	140	61	1,200
105833-6	N - 6	6 5	19	6.5	170	690

ND = Not detected at or above reporting limit; Reporting limit indicated in parentheses.

QA/QC SUMMARY

RPD. %		
· · ·	•	8
RECOVERY, %	1.0	2
		_
		==



LABORATORY NUMBER: 105833 CLIENT: AQUA RESOURCES, INC.

PROJECT ID: 90262.2 LOCATION: PG&E: ENCON DATE RECEIVED: 11/19/91 DATE EXTRACTED: 11/27/91 DATE ANALYZED: 12/03/91 DATE REPORTED: 12/03/91

Extractable Petroleum Hydrocarbons in Soils & Wastes California DOHS Method LUFT Manual October 1989

LAB ID SAMPLE ID	KEROSENE RANGE (mg/Kg)	DIESEL RANGE (mg/Kg)	REPORTING LIMIT* (mg/Kg)
	· · · · · · · · · · · · · · · · · · ·	· • • • •	
105833-1 N-1	ND	340	100
105833-2 N-2	ND	410	100
105833-3 N-3	ND	$1, \overline{200}$	100
105833-4 N-4	ND	2.500	100
105833-5 N-5	6,500	ND	100
105833-6 N-6	6,000	ND	100

ND = Not Detected at or above reporting limit.

*Reporting limit applies to all analytes.

QA/QC SUMMARY

RECOVERY, %

LABORATORY CONTROL SAMPLE



Client: Aqua Resources

Laboratory Login Number: 105833

Project Name: PG&E: ENCON Project Number: 90262.2

Report Date: 03 December 91

ANALYSIS: Hydrocarbon Oil & Grease (Gravimetric) METHOD: SMWW 17:5520EF

Lab ID	Sample ID	Matrix	Sampled	Received	Analyzed	Result	Units	RL.	Analyst	QC Batch
105833-001	N-1	Soil	19-NOV-91	19-NOV+91	27-NOV-91	8800	mg/Kg	50	TR	3513
105833-002	N+2	Soil	19-NOV-91	19-NOV-91	27-NOV-91	18000	mg/Kg	50	TR	3513
105833-003	N-3	Soil	19-NOV-91	19-NOV-91	27-NOV-91	5100	mg/Kg	50	TR	3513
105833-004	N-41 Common de la	Soil	19-NOV-91	19-NOV-91	27-NOV-91	8300	mg/Kg	50	TR	3513
105833-005	N-5	Soil	19-NOV-91	19-NOV+91	27-NOV-91	34000	mg/Kg	250	TR	3513
105833-006	N-6	Soil	19-NOV-91	19-NOV-91	27-NOV-91	13000	mg/Kg	50	TR	3513
		· ·								
		s.								
		00 00 00 00 00 00 00 00 00				0.000000000000000000000000000000000000				
) }:								
		90 5 W 80 80 80								
ı.										

ND = Not Detected at or above Reporting Limit (RL).

QC Batch Report

Client:

Aqua Resources

Project Name:

PG&E: ENCON

Project Number: 90262.2

Laboratory Login Number: 105833

Report Date:

03 December 91

ANALYSIS: Hydrocarbon Oil & Grease (Gravimetric) QC Batch

Number:

3513

Blank Results

Sample ID Result

 \mathtt{MDL} Units Method

Date Analyzed

BLANK

ND

30 mg/Kg SMWW 17:5520EF

27-NOV-91

Spike/Duplicate Results

Sample ID Recovery

Method

Date Analyzed

BS

85%

SMWW 17:5520EF

27-NOV-91

BSD

89%

SMWW 17:5520EF

27-NOV-91

Average Spike Recovery Relative Percent Difference

87% 4.7%

Control Limits 80% - 120%

< 20%

	PROJEC	T NAME:	1045	: ENCON				
	PROJE	CT NO.:	90267	2.2			Т	
Sample Number	Location		l Sample	Type of Container	Type	of Preservation Chemical	Analysis	Required
	(Depth)	Material	Drive	BrassTube	±4°C		1+	
N-I	4 1/2	Soil	Deige	De or 22 inch a	ч		<u></u>	
<u>N-Z</u>	41/2'	34	11	11	31		1+-	
N-3 N-4	51/2	11	13	18	.,,		 +	
7-5	5 V2'	11	11	11	- 1		1+	
N-6	5'	11	<u> </u>				1 7	
	_{-				11			
<u> 5-1 </u>	31/2	11	S.Hammer Drive	u			1 *	
<u>B-1</u>	41/2	11	5. Hanner		11		1 *	
5-2	5' 7'	11	Drive	11	13		*	
B-2 W-1	4'_	(1)	11	33			*	
10 - 1	 				_			
					_			<u>-</u> -
		_			_			
	_				_			
	_	- 	_					<u> </u>
Total Number of	Samples S	lipped: 1	Sample	r's Signature:	_N.			Date
Relinquished By:		11/2	<i></i>	Received By:	<u> </u>	12 B.		11/19
Signature	her-	27	e-Gman	Signatur Printed Name	Lourn	ador Brown	<u> </u>	Time
Printed Name Company A	Hacon Gua K	25000	V.S	Сопірапу С	<u>+T Y</u>	Carles 1		16:0
Reason Ea	~ Anal	يخنخ						Date
Relinquished By		•		Received 8y: Signature				
Signature				Printed Name_				Tim
Signature Printed Name Printed Name Company Company Company Printed Name Printed								
Company				- <u></u>			-	



Curtis & Tompkins, Ltd., Analytical Laboratories, Since 1878

2323 Fifth Street, Berkeley, CA 9471O, Phone (415) 486-0900

DATE RECEIVED: 11/20/91 DATE REPORTED: 11/22/91

LABORATORY NUMBER: 105845

CLIENT: AQUA RESOURCES, INC.

PROJECT ID: 90262.2

LOCATION: PG&E: ENCON

RESULTS: SEE ATTACHED

QA/QC Approval

Final Appa



LABORATORY NUMBER: 105845 CLIENT: AQUA RESOURCES, INC.

PROJECT ID: 90262.2 LOCATION: PG&E: ENCON DATE RECEIVED: 11/20/91
DATE ANALYZED: 11/21,22/91

DATE REPORTED: 11/22/91

Total Volatile Hydrocarbons with BTXE in Soils & Wastes TVH by California DOHS Method/LUFT Manual October 1989 BTXE by EPA 5030/8020

LAB ID	SAMPLE ID	TVH AS GASOLINE	BENZENE	TOLUENE	ETHYL BENZENE	TOTAL XYLENES
		(mg/Kg)	(ug/Kg)	(ug/Kg)	(ug/Kg ¹)	(ug/Kg)
						
105845-1	B - 3	ND(1,0)	ND(5.0)	ND(5.0)	ND(5.0)	ND(5,0)
105845-2	W-2	ND(1.0)	ND(5.0)	ND(5.0)	ND(5,0)	ND(5.0)
105845-3	B - 4	290	10	2 1	900	6,900
105845-4	S - 3	ND(1.0)	ND(5.0)	ND(5.0)	ND(5.0)	8.5
105845-5	W-3	ND(1.0)	ND(5.0)	ND(5.0)	ND(5.0)	ND(5,0)
105845-6	W-4	ND(1,0)	ND(5.0)	ND(5.0)	ND(5.0)	ND(5.0)

ND = Not detected at or above reporting limit; Reporting limit indicated in parentheses.

QA/QC SUMMARY



LABORATORY NUMBER: 105845 CLIENT: AQUA RESOURCES, INC.

PROJECT ID: 90262.2 LOCATION: PG&E: ENCON DATE RECEIVED: 11/20/91
DATE EXTRACTED: 11/21/91
DATE ANALYZED: 11/21,22/91
DATE REPORTED: 11/22/91

Extractable Petroleum Hydrocarbons in Soils & Wastes California DOHS Method LUFT Manual October 1989

LAB ID	SAMPLE ID	KEROSENE RANGE (mg/Kg)	DIESEL RANGE (mg/Kg)	REPORTING LIMIT* (mg/Kg)
105845-1	B - 3	ND	ND	10
105845-2	W- 2	ND	ND	10
105845-3	B - 4	ND	130	15
105845-4	S - 3	ND	2 1	10
105845-5	W- 3	ND	ND	10
105845-6	W- 4	ND	15	10

ND = Not Detected at or above reporting limit.

*Reporting limit applies to all analytes.

QA/QC SUMMARY

	=======================================
RPD, %	<1
RECOVERY, %	9 4



Client: Aqua Resources

Project Number: 90262.2

Laboratory Login Number: 105845

Project Name: PG&E: ENCON

Report Date:

22 November 91

ANALYSIS: Hydrocarbon Oil & Grease (Gravimetric)

METHOD: SMWW 17:5520EF

Lab ID	Sample 10	Matrix	Sampled	Received	Analyzed	Result	Units	RL	Analyst	QC Batch
105845-001	B+3	Soil	20-NOV-91	20-NOV-91	22-NOV-91	ND.	mg/Kg	50	AY	3447
105845-002	w-2	: Soil	20-NOV-91	20-NOV-91	22-NOV-91	ND	mg/Kg	50	AY	3447
105845-003	8-4	Soil	20-NOV-91	20-NOV-91	22-NOV-91	3300	mg/Kg	50	AY	3447
105845-004	s-3	Soil	20-NOV-91	20-NOV-91	22-NOV-91	240	mg/Kg	50	AY	3447
05845-005	W-3	Soil	20-NOV-91	20-NOV-91	22-NOV-91	ND	mg/Kg	50	AY	3447
05845-006		Soil	20-NOV-91	20-NOV-91	22-NOV-91	72.	mg/Kg	50	AY	344

ND = Not Detected at or above Reporting Limit (RL).



QC Batch Report

Client:

Aqua Resources

Laboratory Login Number: 105845

Project Name:

PG&E: ENCON

Report Date: 22 November 91

Project Number: 90262.2

ANALYSIS: Hydrocarbon Oil & Grease (Gravimetric)

QC Batch

Number:

3447

Blank Results

Sample ID Result

MDL Units Method

Date Analyzed

BLANK

ND

30 mg/Kg SMWW 17:5520EF

22-NOV-91

Spike/Duplicate Results

Sample ID Recovery

Method

Date Analyzed

BS

SMWW 17:5520EF

22-NOV-91

BSD

91% 90%

SMWW 17:5520EF

22-NOV-91

Average Spike Recovery Relative Percent Difference

91% 1.1% Control Limits 80% - 120%

< 20%

	AQU	A RES	SOURC	ES, INC.		5HIPM	IENT NO.	2			
ı	2	· · · · (CHAIN O	F CUSTODY RECO	ORD		OF	1			
	ACP		Dr L	E: ENCON		. DATE	11/2	0/91			
	PROJEC	T NAME:	704	2 1 2 10 W K		 .					
	PROJEC		9026	6 - km			-				
Sample Number	(Coph) Material Method Temp Chemical										
E-1	32	Soil	Drive	BrassTube	1±4°C	<u>. </u>	1+	(02844-			
B-3	51/2'	11	1 11	11	1)		14	102812-			
W-2	4.	ξl	11	11	11		1*				
B-4	8	11	11	11	11		1-*	 [,			
5-3	41/2 51/2	- 11	i i	11	11.		1 *				
W-3	5 1/2	11	(1	3 (14		175	<u> </u>			
W-4	4	- 11		11	16		1 8				
	- 				- 	·	 				
<u> </u>	- 	ļ			-						
	 			<u> </u>	-						
			· -								
	-		 		- 						
<u> </u>		<u> </u>	 		-	l					
		 			-						
	-						-				
	<u> </u>										
	<u> </u>	ļ			-	 	-				
		 	-	.	_	· 					
			-	-	_		-				
	<u></u>			o's Simonum P	-11						
Total Number of	Samples Sh	ipped: 4	Sample	r's Signature: Received By:	7	-		Date			
Relinquished By Signature		? . ST.		Signature	·			/ /			
Printed Name	laron 1	5. Stee	sman	Printed Name				Time			
Company Aq	na Ros	owes.		Conipany							
Reason For	Analys	<u>. 5</u>		Received By:	1/-	1 =		Date			
Relinquished By: Signature				Signature	Tim	4		11/20/91			
Printed Name				Printed Name	70	JUHN POR	TE	Time*			
Company				Company	CURT	S. TOMPKI	<u> </u>	17151			
Reason					_						
REMARKS:		,		ī	t						
1 =	TPHD !	(10 ppr	n),T	NHE & BLEX	086	>					
				48 hour t							
. ~ - '						-		ļ			
+ =	2 We	cok to	arnara	ound							
1								Ì			
Special Shipment	/ Handling	/ Storage	Requiremen	ts:							
		•			1		7				
				Chi Divo	uc	-0-C W/	1055	745			



Curtis & Tompkins, Ltd., Analytical Laboratories, Since 1878

2323 Fifth Street, Berkeley, CA 94710, Phone (415) 486-0900

DATE RECEIVED: 11/20/91 DATE REPORTED: 12/02/91

AQUA RESOURCES, INC

JOENO.

LABORATORY NUMBER: 105844

CLIENT: AQUA RESOURCES, INC.

PROJECT ID: 90262.2

LOCATION: PG&E: ENCON

RESULTS: SEE ATTACHED

QA/QC Approval

Fina

Berkeley

Wilmington

Los Angeles



LABORATORY NUMBER: 105844 CLIENT: AQUA RESOURCES, INC.

PROJECT ID: 90262.2 LOCATION: PG&E: ENCON DATE RECEIVED: 11/20/91 DATE ANALYZED: 11/29/91 DATE REPORTED: 12/02/91

Total Volatile Hydrocarbons with BTXE in Soils & Wastes
TVH by California DOHS Method/LUFT Manual October 1989
BTXE by EPA 5030/8020

LAB ID	SAMPLE ID	TVH AS GASOLINE	BENZENE	TOLUENE		TOTAL XYLENES
		(mg/Kg)	(u g / Kg)	(u g / K g)	(ug/Kg)	(ug/Kg)
105844-1	E - 1	ND(1.0)	ND(5.0)	ND(5.0)	ND(5,0)	ND(5,0)

 $ND = Not\ detected\ at\ or\ above\ reporting\ limit;\ Reporting\ limit\ indicated\ in\ parentheses.$

QA/QC SUMMARY

RPD, % 18
RECOVERY, % 102



LABORATORY NUMBER: 105844 CLIENT: AQUA RESOURCES, INC.

PROJECT ID: 90262.2 LOCATION: PG&E: ECON DATE RECEIVED: 11/20/91 DATE EXTRACTED: 11/27/91 DATE ANALYZED: 12/01/91 DATE REPORTED: 12/02/91

Extractable Petroleum Hydrocarbons in Soils & Wastes
California DOHS Method
LUFT Manual October 1989

LAB ID	SAMPLE ID	KEROSENE RANGE (mg/Kg)	DIESEL RANGE (mg/Kg)	REPORTING LIMIT* (mg/Kg)
105844-1	E - 1	ND	ND	10

ND = Not Detected at or above reporting limit.

*Reporting limit applies to all analytes.



Client: Aqua Resources

Laboratory Login Number: 105844

Project Name: PG&E: ENCON Project Number: 90262.2

Report Date:

02 December 91

ANALYSIS: Hydrocarbon Oil & Grease (Gravimetric) METHOD: SMWW 17:5520EF

ab ID	Sample ID	Matrix	Sampled	Received	Analyzed	Result	Units	RL	Analyst	QC Batc
		• :			4				į	
05844-001	E-1	Soil	20-NOV-91	20-NOV-91	27-NOV-91	1600	mg/Kg	50	TR	351

						1000 000 000 1000 000 000 1000 000 000				
						10000000000000000000000000000000000000				
						0.0000000000000000000000000000000000000				
						0.0000000000000000000000000000000000000				
						2000 000 000 2000 000 000 2000 000 000				
						1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1				
						1.101.604.66				
						20 2 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0				
						0.000 000 000 0.000 000 000 0.000 000 00				
						70.20 (0.00				
						37.50				
	Angelia de la Companya de la Company					29 / 12 / 12 / 12 / 12 / 12 / 12 / 12 /				
						00000000000000000000000000000000000000				

ND = Not Detected at or above Reporting Limit (RL).



QC Batch Report

Client:

Aqua Resources

Laboratory Login Number: 105844

Project Name: PG&E: ENCON

Report Date: 02 December 91

Project Number: 90262.2

ANALYSIS: Hydrocarbon Oil & Grease (Gravimetric) QC Batch

Number:

3513

Blank Results

Sample ID Result

MDL Units

Method

Date Analyzed

BLANK

ND

30

mg/Kg SMWW 17:5520EF

27-NOV-91

Spike/Duplicate Results

Sample ID Recovery

Method

Date Analyzed

BS

85%

SMWW 17:5520EF

27-NOV-91

BSD

89%

SMWW 17:5520EF

27-NOV-91

Average Spike Recovery Relative Percent Difference

87% 4.7%

Control Limits 80% - 120%

< 20%

	AQU	A RES	OURC	ES, INC.		ŞHIPMI	ENT NO.:	2_
				CUSTODY RECO	מאכ		OF	
	AF		PGE	E: ENCON		DATE.	11/20	5/91
	PROJEC	T NAME:	9026	2.2				
a h Nambae	Location		Sample	Type of Container		/ Preservation Chemical	Analysis	Required
Sample Number	(Depth)	Material	Method	BrassTube	Temo	Greating	1+	102844-
<u> </u>	5/2	501	11	11	IJ		🗶	102812
W-2	4'	Li	- 11	11	11		1+	- [:
B-4	8	- 11	н	11	11		1*	1
5-3	4/2	11	(i	11	14		1*	
W-3 W-4	4'	- 11	(1	11	<u> </u>		1-*	
44								
		ļ	 					
							_	
				_			 	
					-			
		1					 -	
					_		-	
			_		_			
								·
Total Number o		hipped:	Sampl	er's Signature	-11	<i></i>		Date
Relinquished By		7.0		Received By:				1 1
Signature Printed Name_	Aaron	N. Ste	ssman	Printed Name_				Time
Company	ana ma	gow-ce		Company				
Reason		5.5		Received By:	Va			11/90 91
Signature				Signature Printed Name	Tuy.	CHIN GOY	578	Time'
Printed Name_				Сотрапу	CURT	S. TOMPE	<u> 214</u>	1715
Reason								1
REMARKS:		1	\ -	aug Larrey	0 5 B	_		
1 =	TPHD	(10 pp	m), [LAHE & BLEX	ا م ک	,		
* =	842in	cture	angula	£ 48 hour	turna	mand		•
	~ ·	:- \ (20 V - 1	turna	round				
) , + =	L 11	; C D, F -		- -		4		
Special Shipme	nt / Mandii	ng / Storage	Requirem	ents:				
20eciai 20irbine	11. 7 / 19110/11	g - 2.00 - 2g						
				1 • • •	1		11	س این
				chi200	ial c	-0-0 6	7 (°S	842

CHROMALAB, INC.

Analytical Laboratory (E694)

November 22, 1991

1191227 ChromaLab File No.:

AQUA RESOURCES, INC.

Attn: Aaron N. Stessman

RE: Two rush soil samples for Gasoline/BTEX, TEPH, and Oil & Grease analyses

Project Name: PG&E ENCON Project Number: 90262.2

Date Sampled: Nov. 21, 1991 Date Submitted: Nov. 21, 1991 Date Extracted: Nov. 22, 1991 Date Analyzed: Nov. 22, 1991

RESULTS:

Sample I.D.	Gasoline (mg/kg)		Benzene (µg/kg)					
B-5 E-2	N.D. N.D.	N.D. N.D.	N.D.	N.D.	N.D. N.D.	N.D.	740 1100	N.D. N.D.
BLANK SPIKE REC. DET. LIMIT METHOD OF ANALYSIS	N.D. 98.0% 1.0 5030/ 8015	N.D. 92.6% 1.0 3550/ 8015	N.D. 103.4% 5.0	N.D. 106.4% 5.0	N.D. 108.9% 5.0	N.D. 107.9% 5.0	N.D. 10 5520 E&F	N.D. 1.0 3550/ 8015

ChromaLab, Inc.

David Duong

Chief Chemist

ErreTam (by PD)

Eric Tam Laboratory Director

Analytical Laboratory (E694)

November 22, 1991

ChromaLab File # 1191227 B

Client: Aqua Resources, Inc. Date Sampled: Nov. 21, 1991

Attn: Aaron Stessman

Date Analyzed: Nov. 22, 1991

Date Submitted: Nov. 21, 1991

Project Number: 90262.2 Project Name: PG&E Encon

Sample I.D.:

B-5

Method of Analysis: 8010 & 8020

Detection Limit: $5.0 \mu g/kg$

COMPOUND NAME	ug/kg	Spike Recovery
CHLOROMETHANE	N.D.	
VINYL CHLORIDE	N.D.	
BROMOMETHANE	N.D.	-
CHLOROETHANE	N.D.	
TRICHLOROFLUOROMETHANE	N.D.	
1,1-DICHLOROETHENE	N.D.	90.5% 91.0%
METHYLENE CHLORIDE	N.D.	
1,2-DICHLOROETHENE (TOTAL)	N.D.	
1,1-DICHLOROETHANE	N.D.	
CHLOROFORM	N.D.	
1,1,1-TRICHLOROETHANE	N.D.	
CARBON TETRACHLORIDE	N.D.	
1,2-DICHLOROETHANE	N.D.	
BENZENE	N.D.	92.3% 91.5%
TRICHLOROETHENE	N.D.	
1,2-DICHLOROPROPANE	N.D.	
BROMODICHLOROMETHANE	N.D.	- - - -
2-CHLOROETHYLVINYLETHER	N.D.	
TRANS-1,3-DICHLOROPROPENE	N.D.	
TOLUENE	N.D.	91.0% 95.5%
CIS-1,3-DICHLOROPROPENE	N.D.	
1,1,2-TRICHLOROETHANE	N.D.	
TETRACHLOROETHENE	N.D.	~ ~ ~
DIBROMOCHLOROMETHANE	N.D.	
CHLOROBENZENE	N.D.	93.7% 94.2%
ETHYLBENZENE	N.D.	
BROMOFORM	N.D.	
	N.D.	
1,3-DICHLOROBENZENE	N.D.	
1,4-DICHLOROBENZENE	N.D.	
1,2-DICHLOROBENZENE	N.D.	
TOTAL XYLENES	N.D.	

ChromaLab. inc.

David Duong

Senior Chemist

Eric Tam Lab Director

r		<u> </u>	A DES	OURC	ES, INC.	ORDE	4278				
1		AGO:					PAGE	ı Ve	<u>.1</u>		
u Oljsi		$\mathcal{A}(\mathcal{O})$			CUSTODY RECC	IKU		11 15 1	191		
. [700150	T NAME:	DGGE	ENCON		DATE		\ 		
		PROJEC	T NO.	026	2.2						
		1	Type of		Type of Container	Туре	of Preservation	Analysis	Required		
	Sample Number	Location (Material	Method		Temp	Chemical	die 1	1		
F	E-2_	11/21	Soil	Drive	Brass Tube	24°C		7.2			
	B-5	71/2	- 11	1)	71						
]_						-					
-											
-								_\			
						_		-			
				<u> </u>		_	<u> </u>				
						-					
		-		 				_			
-								_			
Ì						_			<u> </u>		
				<u> </u>	-	_					
1			- 	<u>-}</u>	_	_					
` 				<u> </u>							
!					_						
		_				7					
	Total Number of	Samples Si	nipped: 2	Sampl	er's Signature:	-1	1.57		Date		
	Relinquished By	2 10	.00		Received By: Signature	Cary	Cook		11/21 191		
	Signature Printed Name	Haron	J. 51es	5 man	Printed Name_	Gush	1 COO/E		Time		
	Company Aq	LA BOSON	nrcas		Сопірапу	(wow	n vau		15,00		
			3 (5		Received By:				Date , ,		
	Relinquished By: Signature				Signature				\ <u>-//-</u>		
	Printed Name_				Printed Name				Time'.		
	Company										
	REMARKS:				1 Tung & B	TEX	026				
	+ 1 = TE	HD (10)	pm det.	limit OK	1), 1010 45	(1,7,	- - -				
		JEPH)~	Diesel F	Karosene	I an these	e san	noles				
	124 Ho	iur t	urna	ironn	d on these		1 740				
	1 ~ ^ \ \	-اساندر سـ	· 45	ハシオル	たん しつり	ノウベ	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	6			
	17-0	翌~1~ /	(Q07)	<u> </u>	3 TEPH-	DέK,	TVH6,	086			
_	T 4 - 6	\mathcal{I}	000	ー 1							

Special Shipment / Handling / Storage Requirements:

CHROMALAB, INC.

Analytical Laboratory (E694)

November 25, 1991

ChromaLab File No .:

1191247 1191252

AQUA RESOURCES, INC.

1191254

Attn: Aaron N. Stessman

RE: Eleven rush soil samples for Gasoline/BTEX, TEPH, and Oil & Grease analyses

Project Name: PG&E - ENCON Project Number: 90262.2

Date Sampled: N/A Date Extracted: Nov. 24-25,1991

Date Submitted:Nov. 22-23,1991 Date Analyzed: Nov. 24-25,1991

RESULTS:

Sample I.D.	Gasoline (mg/kg)	Diesel (mg/kg)	Benzene (µg/kg)	Toluene (μg/kg)	Ethyl Benzene (µg/kg)	Total Xylenes (µg/kg)	Oil & Grease (mg/kg)	
B-8 B-9 S-5	N.D. N.D.	N.D. 27	N.D. N.D.	N.D. N.D.	N.D. N.D.	N.D.	N.D.	N.D.
S-5 S-6	N.D.	N.D.	N.D. N.D.	N.D.	N.D.	N.D.	670 N.D.	N.D.
B-11 S-7	N.D. 15	130 730	N.D.	N.D.	N.D.	N.D.	300 1600	N.D. N.D.
W-5	N.D. 17	N.D.	N.D. N.D.	9.5 N.D.	30 N.D.	68 N.D.	4000 N.D.	N.D. N.D.
W-6 B-6 S-4	N.D.	1100 N.D.	5.3 N.D.	11 N.D.	33 N.D.	79 N.D.	4500 N.D.	N.D. N.D.
B-7 BLANK	N.D.	N.D.	N.D.	N.D.	N.D. N.D.	N.D. N.D.	16 N.D.	N.D. N.D.
SPIKE REC.	N.D. 93.8%	N.D. 92.6%	N.D. 103.4%		N.D. 108.9%		N.D.	N.D.
DUP SPIKE REC DET. LIMIT METHOD OF	1.0	88.0%	85.7% 5.0	98.9% 5.0	105.4% 5.0	106.9% 5.0	10	1.0
ANALYSIS	5030/ 80 1 5	3550/ 8015	8020	8020	8020	8020	5520 E&F	3550/ 8015

ChromaLab, Inc.

David Duong Chief Chemist

Erretan (by Do)

Eric Tam

CHROMALAB, INC.

Analytical Laboratory (E694)

December 3, 1991

ChromaLab File No.: 1191247

AQUA RESOURCES, INC.

Attn: Aaron Stessman

RE: One soil sample for Gasoline/BTEX, TEPH, and Oil & Grease analyses

Project Name: PG&E - ENCON Project Number: 90262.2

Date Sampled: Nov. 22, 1991 Date Submitted: Nov. 22, 1991 Date Extracted: Nov. 29, 1991 Date Analyzed: Nov. 29, 1991

RESULTS:

Sample I.D.	Gasoline (mg/kg)	Diesel (mg/kg)			Ethyl Benzene (µg/kg)			Kerosene (mg/kg)
E-3	N.D.	1500	N.D.	N.D.	N.D.	N.D.	5600	N.D.
BLANK _SPIKE REC.	N.D. 99.3%	N.D. 92.6%	N.D. 82.8%	N.D. 94.2%	N.D. 107.4%	N.D. 106.7%	N.D.	N.D.
DET. LIMIT METHOD OF	1.0 5030/	1.0 3550/	5.0	5.0	5.0	5.0	10 5520	1.0 3550/
_ ANALYSIS	8015	8015	8020	8020	8020	8020	E&F	8015

ChromaLab, Inc.

David Duong

Chief Chemist

Errtam (by D)

Eric Tam

5 DAYS TURNAROUND

Analytical Laboratory (E694)

December 2, 1991

ChromaLab File No.:

AQUA RESOURCES, INC.

Attn: Aaron N. Stessman

RE: Two composite soil samples for STLC Lead analysis

Project Name: PG&E - ENCON Project Number: 90262.2

Date Sampled: Nov. 22, 1991 Date Submitted: Nov. 22, 1991 Date Extracted: Nov. 27, 1991 Date Analyzed: Nov. 27, 1991

RESULTS:

Sample I.D.	STLC Lead (mg/l)
LSP 1 & 2 Composite LN-1, LS-2, LW-3, LE-4 Composite	1.32 4.23
BLANK	N.D.
SPIKED RECOVERY	111%
DUPLICATE SPIKED RECOVERY	110%
DETECTION LIMIT	0.05
METHOD OF ANALYSIS	6010

ChromaLab, Inc.

Ketant R. Manders Refaat A. Mankarious

Inorganics Supervisor

Eric Tam

Analytical Laboratory (E694)

December 3, 1991

ChromaLab File No.: 1191252

AQUA RESOURCES, INC.

Attn: Aaron Stessman

 $\underline{\mathtt{RE:}}$ One soil sample for Gasoline/BTEX, TEPH, and Oil&Grease analysis

Project Name: PGE-ENCON Project Number: 90262.2

Date Sampled: Nov. 23, 1991
Date Extracted: Nov. 29, 1991

Date Submitted: Nov. 23, 1991 Date Analyzed: Nov. 29, 1991

RESULTS:

Sample	Gasoline	Diesel	Benzene			Total Xvlenes		Kerosene
	(mg/kg)							
E-4	1.9	51.7	N.D.	N.D.	N.D.	9.0	1200	N.D.

BLANK N	.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
SPIKE REC.	99.3%	92.6%	82.8%	94.2%	107.4%	106.7%		
DET. LIMIT	1.0	1.0	5.0	5.0	5.0	5.0	10	1.0
METHOD OF	5030/	3550/					5520	3550/
ANALYSIS	8015	8015	8020	8020	8020	8020	E&F	8015

ChromaLab, Inc.

David Duong Chief Chemist Erictam (by DO)

Eric Tam

CHROMALAB, INC.

Analytical Laboratory (E694)

December 4, 1991

ChromaLab File No.: 1191254

AQUA RESOURCES, INC.

Attn: Aaron Stessman

RE: Two soil samples for Gasoline/BTEX, TEPH, and Oil & Grease analyses

Project Name: PG&E - ENCON Project Number: 90262.2

Date Sampled: Nov. 23, 1991
Date Extracted: 11/29-12/2/91

Date Submitted: Nov. 23, 1991 Date Analyzed: 11/29-12/2/91

RESULTS:

Sample I.D.	Gasoline (mg/kg)				Ethyl Benzene (µg/kg)		Grease	Kerosene (mg/kg)
8-10	1.6	N.D.	N.D.	N.D.	N.D.	8.3	33	N.D.
E-5	6.3	5000	14	8.0	13	76	5300	N.D.
BLANK	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
SPIKE REC.	99.3%	93.2%	91.3%	91.9%	94.0%	93.5%		
DET. LIMIT	1.0	1.0	5.0	5.0	5.0	5.0	10	1.0
METHOD OF ANALYSIS	5030/ 8015	3550/ 8015	8020	8020	8020	8020	5520 E&F	3550/ 8015

ChromaLab, Inc.

David Duong Chief Chemist

Eric Tam

	AQU.	A RES	OURC	ES, INC.				7
	20			CUSTODY RECC	ORD	PAGE	1_0F_	191
	PROJEC	T NAME:_	PGSE	E - ENCON		 .	. <u> </u>	
		T NO.:	9026	52.2				
Sample Number	Location (Depth)	Type of Material	Sample Method	Type of Container	Temp	Of Preservation Chemical	Analysis	Required
50 1	911	Soil/Ter	Drive	Brass Tube	=4°C		- 3-2	*
5P-1 5P-2	23"	50:1	11	Brass Tube				
Ni.—1	4/2	50:1	11	Glass Jar	-		72*	
5-2	4	t1_	11		-			
Wi-3	4-'	1 11	11	- N	-11			
LE-4	3′	11	<u> </u>	Brass Tybe		·		
		<u> </u>		11			*	
B-6	3'	- (1	\ ``	13	il		17	
<u>5-4</u>	5'	11	111	11	11		14	
W-5_	5'	1)	1.1	1)	11		<u> 🔻 </u>	
B-7	34,	11	1,	11	11	<u></u>		
E-3	4-1/2	(1			_	\		
	_	_			_			
		_						
	_	_	<u> </u>		[
	_			_				
	_\		_{	_	,			
		Nignast: 1	Samp	ler's Signature:		7 5-		Flata
Total Number of		mppeu.	1-100//	Received By:	01 1	1		11/2Z
Relinquished By: Signature				Signature Printed Name	Z EAN	LIALSEY		
2/1/2000	Aanan	N. 5 15	SC MC(V)	Printed Name Company	MONIAL	AG.		1405
Company 👫	CHA KE	<u> </u>	<u> </u>	Company				-
	- Angl	1/5		Received By:				Date
Relinquished By	:			Signature				\ <u></u>
Signature Printed Name_				Printed Name				Time
Company				Company				_
							. 1	1.1-2
REMARKS:		.6. (1.	- 1 '·	nID sampled 11/2	22 4-	Spm, Others	simpled	11120
SAMPLE.	s with	12, 15 1	(gr. <u>L. </u>	A Secretary		1		
1		شرون		TVHGER	したとした) Y G		
							n Compo	site
1 2 = Co	mposit	e Draici	40 HEU 5	camples and re	1. L. A	homa lau	0 \ 540 -	7496
★ = 2	A hou	ir tur	naron	nd tax nesu	(12)	and phone		
: L =	1 33700	\prime TWV $^{\prime}$	1000000	and as possib	······································	L		
Special Shipme	nt / Handi	ing / Storat	e Requirer	nents:				
- I Special Smorn	111 1 110		•					

	AQU	A RES	OURCI	<u>ES, I</u>	<u>1C. </u>			ENT NO.:	
": :	<u></u>				ODY RECO	RD	PAGE_	OF	101
ı	ALL	T NAME:					DATE	11/23	141
	PROJEC	T NAME:_	9026	2.2			• •		
	, 	Type of			of Container		of Preservation	Analysis	Required
Sample Number	Location (Depth)	Material	Method			Temp	Chemical	14	
5-5	41/2	Soil	Drive	Dree	saTube	11		1*	
<u>B-3</u>	31/2	H	11	,	1	1 1		1 3	
5-6 7-9	6	11	11	.}	11	- (1		1 **	
2-4	81/2		- (1		11	- 			
				<u> </u>				_	
						-	. <u></u>		
	<u> </u>	<u> </u>	<u> </u>	-		-			
		-		_				_	
				_				_	
		<u> </u>				_			
			-	-				_	
		-		_		_			
				_		_			
				_		_			
<u> </u>			_	-					
Total Number o	Samples 5	hipped:	Samp	ler's Sign		<u> </u>	12 m		Date
Relinquished By		11 4			caived By: Signature	Gar	Carlo	:	11/23/91
Signature Printed Name	Aaron		KINGIN		Signature Printed Name. Company	COWD	nalich		7 Time 9125
Company Reason	ar Anal	4547005	<u> </u>	`	,Ompany				Date
Relinquished By					eceived By: Signature				
Signature					Printed Name				Time".
Printed Name, Company					Company				J
Reason						· // / 1712	ernight W	Gest 19	e-adderlinan.
REMARKS:	5-5, 8	1-8 tak	con 11/2	27	Kapt on	ادات عام المصري	ernight W		
Samples 1 = TEI	PH - Die	sel & Ka	rosenej	TVH	6+BIE	$X_{j} \mathcal{O}_{j}^{x}$.0		
	, , , , , , , , , , , , , , , , , , ,								
			۸ . میم،		.				
*=1	WEEK	ten hen	YON われ ・	_ ئسو	ا اساما	e Mant	ay arm. to Acu	on (510)540-7498
X = 20	t hour	turna	.round	<u></u>	X 125417	2 L.S.J.K.K	<u> </u>		
Special Shipm	ent / Flandl	ing / Storag	ge Requiren	nents:		ه در م ه د	WONDAY	11/25	
A Anali	IZE IN	nm edict	ely:	Du	e at h	JOEN	MONDAY	- 7	
	٦.		٦.						

					CPDER	J LA F	31234
		• <u>Б</u> Е	OUDC	ES INC	7 4056	4308	4
	<u>AQU</u>	4 HES	OUNC	ES, INC.			
				CUSTODY RECC	RD	PAGE.	11/23/91
	PROJEC	T NAME:	PGE	- ENCON		DATE	
	PROJEC	T NO.:	9026	2.2			T .
ample Number	Location	Type o	Sample Method	Type of Conitainer	Type	of Preservation Chemical	Analysis Require
	(Depth)	Material	Drive	BraseTubs	±4°C		
= - 5	5,	50(1	11	11	31		1*
N-6	4	11	1	, 1	11		<u> </u>
<u>5 – 7 – </u>	4-1/2		_	11	11		1*
3-10_	21/21	11	11	11	(1		<u> - x</u>
3 <u>- 11</u>	81/2'	11	1 11	· · · · · · · · · · · · · · · · · · ·			_
	<u> </u>	 		-			_
	<u>-</u>	 	 				
		.	_				_
	-\ 	 					
	_			-			
	<u> </u>	- 	_				
	_			_			
	_	 -			_		
		_			_		
	_		_			-	
				_	_}-	_	
		_		_		-	
	_						
	-				<u></u>		
Total Number o	Samples S	hipped: 2	Samp	ler's Signature:		A Page	Da
Relinquished By:			1 _	Received By:	Gar	y Coots	((1/2
Signature	1 1	7.5	<u> </u>	Signature			Tin
Printed Name	Accor	NET	<u> </u>	Printed Name	Cho	ome Wal-	16:
Company	1914a-K	23000 10000	<u> </u>				
Signature Printed Name Company Reason	- HMA	1 1 51-3		Received By:			Da /
Relinquished By	:			Signature			
Signature Printed Name_				Printed Name			Tir
Company				Company			
Reason							
REMARKS:				ne, TVH6+		066	
TEMATICO.	- C	Sacal	Korose	20- LINHOY	らして入	, 5 7 6	•
1	1/11/	3.63.5	100,000	· • }			

★ = HUDH (Monacy results)

FAX Rosults to Aaron (510) 540-7496 W/copy of COC

Special Shipment / Handling / Storage Requirements:

Analytical Laboratory (E694)

December 11, 1991

ChromaLab File # 1191254 C

Client: Aqua Resources, Inc. Date Sampled: Nov. 23, 1991

Attn: Aaron Stessman Date Submitted: Nov. 23, 1991

Date of Analysis: Dec. 06, 1991

Project Number: Project Name:

90262.2 PG&E-ENCON

Sample I.D.:

B-11 75

Method of Analysis: EPA 8240

Detection Limit: 5.0 μ g/kg

COMPOUND NAME	μq/kg	Spike Recovery
CHLOROMETHANE	N.D.	
VINYL CHLORIDE	N.D.	
BROMOMETHANE	N.D.	
CHLOROETHANE	N.D.	
TRICHLOROFLUOROMETHANE	N.D.	
1.1-DICHLOROETHENE	N.D.	91.6% 93.5%
METHYLENE CHLORIDE	N.D.	
1,2-DICHLOROETHENE (TOTAL)	N.D.	
1,1-DICHLOROETHANE	N.D.	
CHLOROFORM	N.D.	
1,1,1-TRICHLOROETHANE	N.D.	
CARBON TETRACHLORIDE	N.D.	
1,2-DICHLOROETHANE	N.D.	
BENZENE	N.D.	
TRICHLOROETHENE	N.D.	94.1% 93.7%
1.2-DICHLOROPROPANE	N.D.	
BROMODICHLOROMETHANE	N.D.	
2-CHLOROETHYLVINYLETHER	N.D.	
TRANS-1, 3-DICHLOROPROPENE	N.D.	
TOLUENE	N.D.	
CIS-1,3-DICHLOROPROPENE	N.D.	
1,1,2-TRICHLOROETHANE	N.D.	
TETRACHLOROETHENE	N.D.	86.4% 89.1%
DIBROMOCHLOROMETHANE	N.D.	
CHLOROBENZENE	130	#=#
ETHYL BENZENE	N.D.	
BROMOFORM	N.D.	
1,1,2,2-TETRACHLOROETHANE	N.D.	87.6% 90.2%
1,3-DICHLOROBENZENE	1100	
1,4-DICHLOROBENZENE	1800	
1,2-DICHLOROBENZENE	160	
TOTAL XYLENES	N.D.	
ACETONE	N.D.	
METHYL ETHYL KETONE	N.D.	
METHYL ISOBUTYL KETONE	N.D.	

ChromaLab, Inc.

David Duong Chief Chemist Eric Tam Lab Director

Analytical Laboratory (E694)

December 13, 1991

ChromaLab File # 1291254 C

Aqua Resources, Inc.

Attn: Aaron Stessman

One soil sample for PAH analysis

Project Number: 90262.2 Project Name: PG&E ENCON

Date Sampled: Nov. 23, 1991 Date Extracted: Dec. 06, 1991 Date Submitted: Nov. 23, 1991 Date Analyzed: Dec. 12, 1991

POLYNUCLEAR AROMATIC HYDROCARBONS by GC/MS

Method of Analysis: EPA 8270

Matrix: soil

	Sample	MDL	_ Spike
COMPOUND NAME	mg/Kg	mg/Kg	Recovery
NAPHTHALENE	N.D.	1.0	
ACENAPHTHYLENE	N.D.	1.0	
ACENAPHTHENE	N.D.	1.0	89.1%
FLUORENE	N.D.	1.0	
PHENANTHRENE	N.D.	1.0	90.2%
ANTHRACENE	N.D.	1.0	
FLUORANTHENE	N.D.	1.0	
PYRENE	1.9	1.0	
BENZO (A) ANTHRACENE	N.D.	1.0	
CHRYSENE	N.D.	1.0	82.6%
BENZO (B) FLUORANTHENE	N.D.	1.0	
BENZO (K) FLUORANTHENE	N.D.	1.0	
BENZO (A) PYRENE	N.D.	1.0	
INDENO(1,2,3 C,D)PYRENE	N.D.	1.0	
DIBENZO(A, H) ANTHRACENE	N.D.	1.0	
BENZO(G,H,I)PERYLENE	N.D.	1.0	

ChromaLab, Inc.

David Duong

Senior Chemist

Eric Tam

Lab Director

5 DAYS TURNAROUND

Analytical Laboratory (E694)

December 5, 1991

ChromaLab File No.: 1191274

AQUA RESOURCES, INC.

Attn: Aaron Stessman

RE: One soil sample for TEPH analysis

Project Name: PGE-ENCON Project Number: 90262.2

Date Sampled: Nov. 26, 1991

Date Submitted: Nov. 26, 1991

Date Extracted: Dec. 3, 1991

Date Analyzed: Dec. 3, 1991

RESULTS:

Sample	Kerosene	Diesel	Motor Oil
I.D.	(mg/kg)	(mg/kg)	(mg/kg)
E-6	N.D.	3500	6700

BLANK	N.D.	N.D.	N.D.
SPIKE RECOVERY		93.2%	
DETECTION LIMIT	1.0	1.0	10
METHOD OF	3550/	3550/	3550/
ANALYSIS	8015	8015	8015

ChromaLab, Inc.

David Duong Chief Chemist Entam (by DD)

Eric Tam Laboratory Director

Analytical Laboratory (E694) December 10, 1991

ChromaLab File # 1191274

Aqua Resources, Inc. Client: Nov. 26, 1991

Date Sampled:

Dec. 08, 1991 Date of Analysis:

Aaron Stessman Attn:

Date Submitted: Nov. 26, 1991

Project Number:

90262.2 PG&E-ENCON

Project Name: Sample I.D.:

E-6

EPA 8240 Method of Analysis:

Detection Limit: 5.0 μ g/kg

	μg/kg	Spike Recovery
COMPOUND NAME	<u>μαγκα</u> Ν.D.	
CHLOROMETHANE	N.D.	
VINYL CHLORIDE	N.D.	
BROMOMETHANE	N.D.	
CHLOROETHANE	N.D.	
TRICHLOROFLUOROMETHANE	N.D.	92.8% 95.6%
1,1-DICHLOROETHENE		
METHYLENE CHLORIDE	N.D.	
1,2-DICHLOROETHENE (TOTAL)	N.D.	
1,1-DICHLOROETHANE	N.D.	
CHLOROFORM	N.D.	
1,1,1-TRICHLOROETHANE	N.D.	
CARBON TETRACHLORIDE	N.D.	
1,2-DICHLOROETHANE	N.D.	
BENZENE	N.D.	93.2% 95.5%
TRICHLOROETHENE	N.D.	93.28 95.58
1,2-DICHLOROPROPANE	N.D.	
BROMODICHLOROMETHANE	N.D.	
2-CHLOROETHYLVINYLETHER	N.D.	→ ~
TRANS-1,3-DICHLOROPROPENE	N.D.	
TOLUENE	N.D.	
CIS-1,3-DICHLOROPROPENE	N.D.	
1,1,2-TRICHLOROETHANE	N.D.	
TETRACHLOROETHENE	N.D.	93.7% 98.2%
DIBROMOCHLOROMETHANE	N.D.	
CHLOROBENZENE	N.D.	
ETHYL BENZENE	N.D.	
BROMOFORM	N.D.	
1,1,2,2-TETRACHLOROETHANE	N.D.	96.0% 99.2%
1,3-DICHLOROBENZENE	N.D.	
1,4-DICHLOROBENZENE	N.D.	
1,2-DICHLOROBENZENE	N.D.	
TOTAL XYLENES	N.D.	
ACETONE	N.D.	·
METHYL ETHYL KETONE	N.D.	
METHYL ISOBUTYL KETONE	N.D.	

ChromaLab, Inc.

David Duong Chief Chemist, Eric Tam Lab Director

Analytical Laboratory (E694)

December 10, 1991

ChromaLab File # 1191274

Aqua Resources, Inc. Client:

Attn: Aaron Stessman

Nov. 26, 1991 Date Sampled:

Date Submitted: Nov. 26, 1991

Dec. 08, 1991 Date of Analysis:

Project Number:

90262.2

Project Name:

PG&E-ENCON E-6

Sample I.D.: Method of Analysis: EPA 8270

Matrix: soil

	Commit a	MDL	Spike
	Sample	mg/Kg	Recovery
COMPOUND NAME	mg/Kg N.D.	0.5	
PHENOL	N.D.	0.5	103.6%
BIS(2-CHLOROETHYL) ETHER	N.D.	0.5	103.00
2-CHLOROPHENOL		0.5	
1,3-DICHLOROBENZENE	N.D.	0.5	
1,4-DICHLOROBENZENE	N.D.	1.0	
BENZYL ALCOHOL	N.D.	0.5	
1,2-DICHLOROBENZENE	N.D.	0.5	
2-METHYLPHENOL	N.D.	0.5	
BIS(2-CHLOROISOPROPYL)ETHER	N.D.		
4-METHYLPHENOL	N.D.	0.5	
N-NITROSO-DI-N-PROPYLAMINE	N.D.	0.5	
HEXACHLOROETHANE	N.D.	0.5	
NITROBENZENE	N.D.	0.5	
ISOPHORONE	N.D.	0.5	
2-NITROPHENOL	N.D.	0.5	
2,4-DIMETHYLPHENOL	N.D.	0.5	
BENZOIC ACID	N.D.	2.5	101.5%
BIS (2-CHLOROETHOXY) METHANE	N.D.	0.5	101.5%
2,4-DICHLOROPHENOL	N.D.	0.5	
1,2,4-TRICHLOROBENZENE	N.D.	0.5	
NAPHTHALENE	0.5	0.5	
4-CHLOROANILINE	N.D.	1.0	
HEXACHLOROBUTADIENE	N.D.	0.5	
4-CHLORO-3-METHYLPHENOL	N.D.	1.0	
2-METHYLNAPHTHALENE	N.D.	0.5	
HEXACHLOROCYCLOPENTADIENE	N.D.	0.5	
2,4,6-TRICHLOROPHENOL	N.D.	0.5	
2,4,5-TRICHLOROPHENOL	N.D.	0.5	
2-CHLORONAPHTHALENE	N.D.	0.5	
2-NITROANILINE	N.D.	2.5	
DIMETHYL PHTHALATE	N.D.	0.5	
ACENAPHTHYLENE	N.D.	0.5	
3-NITROANILINE	N.D.	2.5	
ACENAPHTHENE	N.D.	0.5	100.8%
2,4-DINITROPHENOL	N.D.	2.5	
4-NITROPHENOL	N.D.	2.5	
DIBENZOFURAN	N.D.	0.5	
(continued on next page)			

Analytical Laboratory (E694)

Page 2

ChromaLab File # 1191274

Project Number:

90262.2

Project Name:

PG&E-ENCON

Sample I.D.:

E-6

Method of Analysis:

EPA 8270

Matrix: soil

		145.7	and the
	Sample	MDL	Spike
COMPOUND NAME	mg/Kg	mg/Kg	Recovery
2,4-DINITROTOLUENE	N.D.	0.5	
2,6-DINITROTOLUENE	N.D.	0.5	93.0%
DIETHYL PHTHALATE	N.D.	0.5	
4-CHLORO-PHENYL PHENYL ETHER	N.D.	0.5	
FLUORENE	0.9	0.5	
4-NITROANILINE	N.D.	2.5	
4,6-DINITRO-2-METHYL PHENOL	N.D.	2.5	
N-NITROSODIPHENYLAMINE	N.D.	0.5	
4-BROMOPHENYL PHENYL ETHER	N.D.	0.5	
HEXACHLOROBENZENE	N.D.	0.5	
PENTACHLOROPHENOL	N.D.	2.5	114.9%
PHENANTHRENE	1.8	0.5	
ANTHRACENE	N.D.	0.5	
DI-N-BUTYL PHTHALATE	N.D.	0.5	
FLUORANTHENE	N.D.	0.5	
PYRENE	3.0	0.5	
BUTYLBENZYLPHTHALATE	N.D.	0.5	
3,3'-DICHLOROBENZIDINE	N.D.	1.0	
BENZO (A) ANTHRACENE	N.D.	0.5	
BIS (2-ETHYLHEXYL) PHTHALATE	N.D.	0.5	
CHRYSENE	N.D.	0.5	99.1%
DI-N-OCTYLPHTHALATE	N.D.	0.5	
BENZO (B) FLUORANTHENE	N.D.	0.5	
BENZO (K) FLUORANTHENE	N.D.	0.5	
BENZO (A) PYRENE	N.D.	0.5	
INDENO(1,2,3 C,D)PYRENE	N.D.	0.5	
DIBENZO (A, H) ANTHRACENE	N.D.	0.5	
BENZO(G,H,I)PERYLENE	N.D.	0.5	92.2%

ChromaLab, Inc.

David Duong

Senior Chemist

Eric Tam

Lab Director

	AQU.	A RES	OURC	ES, INC.		SHIPM	ENT NO.:	6
				CUSTODY RECO	ORD		l_or	191
	460		PGE.	-ENCON		DATE	11/26	171
	PROJEC	T NAME:	90262	2.7			_ ₁	
Sample Number	Location	Type of	Sample	Type of Container	Type	of Preservation Chemical	Analysis	Required
	(oupth)	Material	Method Grab	BlassJar			2	
- PIPE	(Depth)				±4°C		1	
5-6	4'	Freductison(Drive	Brass Ince	_		_	
					_			
		<u> </u>			_			
					_			
			1		_			
	-	-					_	
			<u> </u>	1				
	_							
			-					
Total Number o	Samples	Shipped: Z	Samp	ler's Signature:	2	A		Date 126,91
Relinquished By Signature		1. A.		Received By: Signature	V	VALLETA CS	9	1 /26/11 Time
Printed Marne.	Aaran	e source	<u>sman</u>	Printed Name Company	CHRO	MALAB		1440
Company_A	Anal	45		Peceived By:				Date
Relinquished By Signature	/:			Signature	· 			Time'.
Printed Name				Printed Name Company				-
Company Reason				(Diesel, Ke	rosene	F) ,	Ø = Å .	<u> </u>
REMARKS:	0			Anneum Asoha	$\omega r \circ \nabla$	21 1 P = 12 (1.2)	,840	OHROLING ORDI
1 - PNA	IS (PA	HS J		standard	fac	TEPH as	phault	7. DE
0-13	e as	aspha	ulti-	STANDANA	<i>1</i>		•	;za ;
1			المد					* 2
11 week		71000 B	ank i	fany conf	rusior	1		W
Speek	to b	ary u						Ö
Special Shipm	ent / Hand	ling / Stora <u>c</u>	ie Hedriten	1127+13+				
i	•							<u> </u>

CHROMALAB, INC.

Analytical Laboratory (E694)

December 2, 1991

ChromaLab File No.: 1191265

Total Oil &

AQUA RESOURCES, INC.

Attn: Aaron Stessman

RE: One rush composited soil sample for Gasoline/ BTEX, TEPH, and Oil & Grease analysis

Project Name: P G & E-ENCON Project Number: 90262-2

Date Sampled: Nov. 25, 1991 Date Submitted: Nov. 26, 1991 Date Extracted: Nov. 27-28, 1991 Date Analyzed: Nov.27-28,1991

RESULTS:

Sample I.D.	Gasoline (mg/kg)	Diesel (mg/kg)	Benzene (µg/kg)		Benzene (µg/kg)	Xylenes Gr (µg/kg) ((erosene (mg/kg)
ABE-1, ABW-1, ABS-1, ABN-1	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	2900	N.D.
BLANK SPIKE RE DET. LIM METHOD C ANALYSI	OF 5030/	N.D. 87.3% 1.0 3550/ 8015	N.D. 85.7% 5.0	N.D. 93.9% 5.0 8020	N.D. 100.8% 5.0 8020	N.D. 106.6% 5.0 8020	N.D. 10 5520 E&F	N.D. 1.0 3550/ 8015

ChromaLab, Inc.

David Duong

Chief Chemist

EizTam (by 10)

Eric Tam

Laboratory Director

Ethyl

Analytical Laboratory (E694)

December 2, 1991

ChromaLab File # 1191265

Aaron Stessman

Client: Aqua Resources, Inc. Date Sampled: Nov. 25, 1991

Attn: Aaron
Date Submitte

Date Submitted: Nov. 26, 1991

Date Extracted: Nov. 27,

Nov. 27, 1991 Date Analyzed:

Nov. 27, 1991

Project No.:

90262.2

Project Name: PG&E-ENCON ABW-1, ABS-1, & ABN-1

Sample I.D.: COMPOSITE OF ABE-1, Method of Analysis: EPA 8270

Matrix: soil

	Sample	MDL	Spike
COMPOUND NAME	mg/Kg	mg/Kg	Recovery
PHENOL	N.D.	0.05	
BIS(2-CHLOROETHYL) ETHER	N.D.	0.05	91.5% 89.2%
2-CHLOROPHENOL	N.D.	0.05	
1,3-DICHLOROBENZENE	N.D.	0.05	
1,4-DICHLOROBENZENE	N.D.	0.05	
BENZYL ALCOHOL	N.D.	0.10	
1,2-DICHLOROBENZENE	N.D.	0.05	
2-METHYLPHENOL	N.D.	0.05	
BIS(2-CHLOROISOPROPYL)ETHER	N.D.	0.05	
4-METHYLPHENOL	N.D.	0.05	
N-NITROSO-DI-N-PROPYLAMINE	N.D.	0.05	
HEXACHLOROETHANE	N.D.	0.05	
NITROBENZENE	N.D.	0.05	
SOPHORONE	N.D.	0.05	
2-NITROPHENOL	N.D.	0.05	
2,4-DIMETHYLPHENOL	N.D.	0.05	
BENZOIC ACID	N.D.	0.25	
BIS(2-CHLOROETHOXY)METHANE	N.D.	0.05	91.5% 93.2%
2,4-DICHLOROPHENOL	N.D.	0.05	- -
1,2,4-TRICHLOROBENZENE	N.D.	0.05	
NAPHTHALENE	N.D.	0.05	
4-CHLOROANILINE	N.D.	0.10	
HEXACHLOROBUTADIENE	N.D.	0.05	
4-CHLORO-3-METHYLPHENOL	N.D.	0.10	
2-METHYLNAPHTHALENE	N.D.	0.05	
HEXACHLOROCYCLOPENTADIENE	N.D.	0.05	
2,4,6-TRICHLOROPHENOL	N.D.	0.05	
2,4,5-TRICHLOROPHENOL	N.D.	0.05	
2-CHLORONAPHTHALENE	N.D.	0.05	
2-NITROANILINE	N.D.	0.25	
DIMETHYL PHTHALATE	N.D.	0.05	
ACENAPHTHYLENE	N.D.	0.05	
3-NITROANILINE	N.D.	0.25	
ACENAPHTHENE	N.D.	0.05	87.5% 88.2%
2,4-DINITROPHENOL	N.D.	0.25	
4-NITROPHENOL	N.D.	0.25	
DIBENZOFURAN	N.D.	0.05	
(continued on next page)			

Analytical Laboratory (E694)

Page 2

ChromaLab File # 1191265

Project No.:

90262.2

Project Name: PG&E-ENCON

Sample I.D.: COMPOSITE OF ABE-1, ABW-1, ABS-1, & ABN-1 Method of Analysis: EPA 8270

Matrix: soil

	Sample	MDL	Spike
COMPOUND NAME	mg/Kg	mg/Kg	Recovery
2,4-DINITROTOLUENE	N.D.	0.05	
2,6-DINITROTOLUENE	N.D.	0.05	89.1% 87.1%
DIETHYL PHTHALATE	N.D.	0.05	
4-CHLORO-PHENYL PHENYL ETHER	N.D.	0.05	
FLUORENE	N.D.	0.05	** - ** **
4-NITROANILINE	N.D.	0.25	
4,6-DINITRO-2-METHYL PHENOL	N.D.	0.25	
N-NITROSODIPHENYLAMINE	N.D.	0.05	
4-BROMOPHENYL PHENYL ETHER	N.D.	0.05	
HEXACHLOROBENZENE	N.D.	0.05	
PENTACHLOROPHENOL	N.D.	0.25	
PHENANTHRENE	N.D.	0.05	
ANTHRACENE	N.D.	0.05	
DI-N-BUTYL PHTHALATE	N.D.	0.05	
FLUORANTHENE	N.D.	0.05	
PYRENE	N.D.	0.05	
BUTYLBENZYLPHTHALATE	N.D.	0.05	
3,3'-DICHLOROBENZIDINE	N.D.	0.10	
BENZO(A)ANTHRACENE	N.D.	0.05	
BIS(2-ETHYLHEXYL)PHTHALATE	N.D.	0.05	
CHRYSENE	N.D.	0.05	86.1% 85.1%
DI-N-OCTYLPHTHALATE	N.D.	0.05	
BENZO(B)FLUORANTHENE	N.D.	0.05	
BENZO(K)FLUORANTHENE	N.D.	0.05	
BENZO(A)PYRENE	N.D.	0.05	
INDENO(1,2,3 C,D)PYRENE	N.D.	0.05	
DIBENZO(A,H)ANTHRACENE	N.D.	0.05	
BENZO(G,H, I)PERYLENE	N.D.	0.05	

ChromaLab, Inc.

David Duong Senior Chemist

Eric Tam Lab Director

	AQUA	RES	OURC	ES, INC.		SHIPME	NT NO.: 5
		c	HAIN OF	CUSTODY RECO		PAGE_	11/25/91
	AFR		P6 6	E-ENCO	<u> </u>	DATE_	11/2014
	PROJEC	T NAME:_	9026	7 7			
	PROJEC				Type	of Preservation	Analysis Required
ample Number	Location	Type of Material	Sample Method	Type of Container	Temp	Chemical	
			Drive_	Brass Tube	144)	HOLD
BE-	Class	<u>.901 </u>	1,	(1	1	Compositi	13
BW-	Import		11	1)	1 11	101	11
B3-1	Pile	1)		17	- 11	<u> </u>	
FDN-1	(Depth)				_		11 (HOLD)
3-12	91/2	11	1 0	<u> </u>	- 11		
			 		-		
	\ \		-		-		
		<u> </u>	 	·	-		
	_						
	_	.	-				_
	_	 					_
·	_	 	 				
			_				
		-					
						_	
	- 	-				_	
	-		_				
Total Number o	L f Samples S	hipped: 5	Sampl	er's Signature:			Date
Relinguished By			1	Received By:	SHO	P1	11/25
Signature	12.		ie cs na	Signature Printed Name	SEAN	MALSER	Time
Printed Name		SOUNCE	+	Printed Name Company	HILOM	ALAIS	3:00
Company A	Anal	4515					Date
Relinquished By				Received By: Signature			
Signature				Printed Name			Time
Printed Name.				Company			
Reason							· ·
HEMARKS:			,	enc), TVH6	1	~ ~ 6/-	8270 PRDE
	EDU I	Diesel	É Karosi	ine), TVH6	i Bte	XJOYEJ	OR OR
1 - 1	> F 17 \	, 1	•	,	_	30.	DE.
ΓΔΥ	Openl-	ts to	Auror	(510) 54	0-7	476	70
~~~	~~ / · · ·	_ ,-					#
1 We	ob To	x en a	NAW NO	(			7
1 1 600	CO I	~ ,(0)	. 540.0	1			
1						1 .1 / -4	<i>1 1 1 1</i>
·						I I III MI OU	/C 1 N
Special Shipme	ant / Handli	ng / Stora	ge Requiren	ients: 24 hv	~ TAI,	due Wed pe	<i>ye</i>
Special Shipme	ent / Handli	ng / Stora	ge Requiren	ients: 24 hr	~ TA1,	due Wed per Aaro	126/91

### CHROMALAB, INC.

Analytical Laboratory (E694)

December 3, 1991

ChromaLab File No.: 1291007

AQUA RESOURCES, INC.

Attn: Aaron Stessman

Project Name: PG&E - ENCON Project Number: 90262.2

Date Sampled: Dec. 2, 1991 Date Submitted: Dec. 2, 1991 Date Extracted: Dec. 2-3, 1991 Date Analyzed: Dec. 2-3, 1991

### RESULTS:

Sample I.D.	Gasoline (mg/kg)						Grease	Kerosene (mg/kg)
S-8	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
BLANK SPIKE REC.	N.D. 99.3%	N.D. 92.6%	N.D. 82.8%	N.D. 94.2%	N.D. 107.4%	N.D. 106.7%	N.D.	N.D.
DET. LIMIT METHOD OF	1.0 5030/	1.0 3550/	5.0	5.0	5.0	5.0	10 5520	1.0 3550/
_ ANALYSIS	8015	8015	8020	8020	8020	8020	E&F	8015

ChromaLab, Inc.

David Duong

Chief Chemist

Eric Tam

Analytical Laboratory (E694)

**5 DAYS TURNAROUND** 

December 9, 1991

ChromaLab File No.: 1291007

AQUA RESOURCES, INC.

Attn: Aaron Stessman

Project Name: PG&E - ENCON Project Number: 90262.2 Date Sampled: Dec. 2, 1991 Date Extracted: Dec. 6, 1991

Date Submitted: Dec. 2, 1991
Date Analyzed: Dec. 6, 1991

RESULTS:

Sample I.D.	Gasoline (mg/kg)				Ethyl Benzene (µg/kg)			Kerosene (mg/kg)
B-13	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
BLANK SPIKE REC. DUP SPIKE REC	N.D. 98.6%	N.D. 85.2%	N.D. 99.0%	N.D. 93.5%	N.D. 84.7%	N.D. 81.0%	N.D.	N.D.
TDET. LIMIT	1.0	86.2% 1.0	87.0% 5.0	79.8% 5.0	81.4% 5.0	81.4% 5.0	10	5.0
METHOD OF ANALYSIS	5030/ 8015	3550/ 8015	8020	8020	8020	8020	5520 E&F	3550/ 8015

ChromaLab, Inc.

David Duong Chief Chemist

Eric Tam

# CHROMALAB FILE # 1291007 ORDER # 4382

	d Fr.		DGEE	Ξ-	ENCON	<u> </u>	DATE	12/2	<u> </u>
	PROJEC	T NAME:	9026	.2.	2				
	<del></del>		Sample		pe of Container		of Preservation	Analysi	s Required
ample Number	Location (	Material	Method	L		Temp	Chemical	1	
5-8	5',	Soil	Drive	150	rass Tube	1-11-		*	
-13	91/2	201	<del>                                     </del>			_		_	
	·	- <del></del>				_			· .
						_		-	
				-\					
	<u> </u>	<u> </u>		-\					
			-	-				_	
								_	
				_ -			_	_	
			_	_		_	-		
		<u> </u>	_						
		<u> </u>		-					
			_		?				
			_	_		_			
		-				\			
		1							
						9	1/2		
Total Number o	/ Samples S	hipped:	Samp	ler's	Signature: Received By:		71)		Date
Relinquished By		7. £			Signature	Jary	Carri Cock		- 12/2
Signature. Printed Name	Agres	J. Ste	55MW		Printed Name	ار ایسی ارا می	comelab		Time
Company	An - LE	<u> </u>			Company				15:1
Reason For		<u>, S</u>			Received By:				Date /
Relinquished By Signature	<b>':</b>				Signature Printed Name				Time
Printed Name.					Company				
Company									
Reason					_		,		
REMARKS:	/	t	e Verst	( ينسه	TVHER	BTEX	, OF 6		
1 = -	reph (	Diegen	F Kind of	ı	, TVHGE	145 4	Acron (5	io)540	- 7496
*=	14 ho	ur the	-NACOW	4	FA / 1-3		Acron (5		
× =	i We	zk Tu	rn avo	\ <b>\</b> \	١,				
	. , ,,	·			,				
1			ge Requirer		<del></del>				

**5 DAYS TURNAROUND** 

Analytical Laboratory (E694)

December 6, 1991

ChromaLab File No.: 1291041

AQUA RESOURCES, INC.

Attn: Aaron Stessman

Project Name: PG&E - ENCON Project Number: 90262.2

Date Sampled: Dec. 5, 1991 Date Submitted: Dec. 5, 1991 Date Extracted: Dec. 5-6, 1991 Date Analyzed: Dec. 5-6, 1991

#### RESULTS:

Sample I.D.	Gasoline (mg/l)		Benzene (µg/l)			Total Xylenes (μg/l)	Grease	Kerosene (μg/l)
WA-1	21	23	0.7	2.8	20	220	42	N.D.
BLANK SPIKE REC. DET. LIMIT	N.D. 94.4% 1.0	N.D. 86.2% 1.0	N.D. 102.5% 0.5	N.D. 94.7% 0.5	N.D. 101.7% 0.5	N.D. 95.2% 0.5	N.D.  0.5	N.D.  50
METHOD OF ANALYSIS	5030/ 8015	3510/ 8015	602	602	602	602	5520 B&F	3510/ 8015

ChromaLab, Inc.

David Duong Chief Chemist Eric Tam

**5 DAYS TURNAROUND** 

Analytical Laboratory (E694)

December 12, 1991

ChromaLab File No.: 1291041

AQUA RESOURCES, INC.

Attn: Aaron Stessman

RE: One soil sample for Gasoline/BTEX, TEPH, and Oil &
 Grease analyses

Project Name: PG&E - ENCON Project Number: 90262.2

Date Sampled: Dec. 5, 1991 Date Submitted: Dec. 5, 1991
Date Extracted: Dec. 10, 1001 Date Analyzed: Dec. 12, 1991

RESULTS:

Ethyl Total Oil & Gasoline Diesel Benzene Toluene Benzene Xylenes Grease Kerosene I.D. (mg/Kg) (mg/Kg)  $(\mu g/Kq)$   $(\mu g/Kq)$   $(\mu g/Kq)$  (mg/Kq) (mg/Kq)  $(\mu g/Kq)$ B-14 N.D. N.D. N.D. N.D. N.D. N.D. N.D. N.D. BLANK N.D. N.D. N.D. N.D. N.D. N.D. N.D. N.D. SPIKE REC. 97.0% 88.6% 98.0% 97.0% 94.7% 93.6% 91.3% DUP SPIKE REC. 97.7% 87.5% 95.1% 94.2% ----85.7% 102.5% 93.3% DET. LIMIT 1.0 1.0 5.0 5.0 5.0 5.0 10 1.0 METHOD OF 5030/ 3550/ 3550/ 5520 ANALYSIS 8015 8015 8020 8020 8020 8020 8015 D&F

ChromaLab, Inc.

David Duong Chief Chemist

Eric Tam

Laboratory Director

Analytical Laboratory (E694)

December 6, 1991

ChromaLab File # 1291041 B

Client: Aqua Resources, Inc. Date Sampled: Dec. 05, 1991

Attn: Aaron Stessman
Date Submitted: Dec. 05, 1991

Date Analyzed: Dec. 06, 1991

Project Number: 90262.2 Sample I.D.: WA-1 Project Name: PG&E-ENCON

Method of Analysis: 601 & 602

Detection Limit: 0.5 µg/1

COMPOUND NAME	µg/l	Spike Recovery
CHLOROMETHANE	N.D.	Ph 409 dag
VINYL CHLORIDE	N.D.	
BROMOMETHANE	N.D.	<del></del>
CHLOROETHANE	N.D.	
TRICHLOROFLUOROMETHANE	N.D.	
1,1-DICHLOROETHENE	N.D.	91.8% 93.5%
METHYLENE CHLORIDE	N.D.	
1,2-DICHLOROETHENE (TOTAL)	N.D.	- <del></del>
1,1-DICHLOROETHANE	16	<b></b>
CHLOROFORM	N.D.	
1,1,1-TRICHLOROETHANE	3.5	
CARBON TETRACHLORIDE	N.D.	
1,2-DICHLOROETHANE	N.D.	
BENZENE	1.8	94.7% 96.0%
TRICHLOROETHENE	1.2	<del></del>
1,2-DICHLOROPROPANE	N.D.	
BROMOD!CHLOROMETHANE	N.D.	
2-CHLOROETHYLVINYLETHER	N.D.	<del></del>
TRANS-1,3-DICHLOROPROPENE	N.D.	but made
TOLUENE	18	92.5% 93.6%
CIS-1,3-DICHLOROPROPENE	N.D.	
1,1,2-TRICHLOROETHANE	N.D.	
TETRACHLOROETHENE	N.D.	
DIBROMOCHLOROMETHANE	N.D.	
CHLOROBENZENE	N.D.	91.0% 91.8%
ETHYLBENZENE	26	en we em
BROMOFORM	N.D.	
1,1,2,2-TETRACHLOROETHANE	N.D.	
1,3-DICHLOROBENZENE	N.D.	
1,4-DICHLOROBENZENE	14	
1,2-DICHLOROBENZENE	N.D.	
TOTAL XYLENES	170	

ChromaLab, Inc.

David Duong Senior Chemist

Eric Tam Lab Director

						, ( ~ 1		@
	AQU	A RES	OURC	ES, INC.		<del></del>	<i>i</i>	2
÷.	$\overline{\mathcal{M}}$			CUSTODY RECC	RD		OF	
	ALU					,, DATE	12-5	-91
	PROJEC	T NAME:	1646	E-ENCON		<del></del> .		
	PROJEC	T NO.:		T	Type	of Preservation	Analysis	Required
Sample Number	Location	Type of Material	Sample Method	Type of Container	Temp	Chemical		
B-14	91/2	Seil	Drive	BrassTube	±4°C	<u> </u>	1 +	
B~ )-T	1.2				-		2 2 1	
WA-I	West	Water	1	1 2 Ambar	-		3 - 2 - 🗙	
WA-I	FXC.	- ' '	1 h	A +	,,		7 24	· · · · · · · · · · · · · · · · · · ·
WA-1	Hand. Water	**	1)	11	9		3	
WA-1 WA-1	with	• • •	11	VOA			<del>547</del>	<u> </u>
WA-L	oily	**	1.	<u> </u>	-		2 =	<u>.                                    </u>
WA-I	Sheen	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	- 11	1)	17		53	
WA-I		<del>  ``</del>					_	
	- <del> </del>				_			
		_	_	. :				
·			-					
		_						
				_				<del></del>
		Princed: <	2	iler's Signature:	· -11.	the		
Total Number o		hipped:	2 Saint	Received By:	Par	M SOR		Date 12/5 91
Relinquished By Signature	~	11.56		Signature	Cycer	y Cook		Time
Painted Mame	Aaron	10 7 5 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4	C55 Mar	Company	Chro	a hab		15100
Company_A	Anal	4515						Date
Relinquished By				Received By: Signature				
Signature Printed Name				Printed Name				Time .
Company				Company				<u> </u>
Reason						1		
REMARKS:	#CD:	ulne	k) '	TVHG & BTE	$\mathbf{x}, \mathbf{o}$	46		
1=	. 157	73 C	17/2	TVH6 & BTE				
1 9-	= TEF	$\Delta H$ ( $\Delta$	(K)	سا	a 71	thr R week t	USHI	(FAX)
7	= ०५	G		AX .	<i>ـــ ـــ</i>	د است. با ملیی		annd
1	= 11/1	46		+	= 1	week T	W TWI	301
1 7	= 60	1607	_					
Special Shipm	ent / Handl	ing / Stora	ge Requires	nents:				
Special Sulphi	2014 1 1 Marian	-					•	

5 DAYS TURNAROUND

Analytical Laboratory (E694)

December 30, 1991

ChromaLab File No.: 1291164

AQUA RESOURCES, INC.

Attn: Aaron Stessman

RE: One soil sample for Gasoline/BTEX analysis

Project Name: PG&E - ENCON Project Number: 90262.2

Date Sampled: Dec. 18, 1991
Date Extracted: Dec. 26, 1991

Date Submitted: Dec. 19, 1991
Date Analyzed: Dec. 26, 1991

#### RESULTS:

Sample I.D.	Gasoline Be (mg/Kg) (/		Toluene (µg/Kg)	Ethyl Benzene (µg/Kg)	Total Xylenes (µg/Kg)	
E-PIPE-2	N.D.	N.D.	N.D.	N.D.	11	
BLANK SPIKE RECOVERY DETECTION LIMIT METHOD OF ANALYSIS	N.D. 93% 1.0 5030/8015	N.D. 98% 5.0 8020	N.D. 97% 5.0 8020	N.D. 99% 5.0 8020	N.D. 98% 5.0 8020	

ChromaLab, Inc.

Charles Woolley

Analytical Chemist

Charle Do. Wolly

Eric Tam

Laboratory Director

Analytical Laboratory (E694)

December 27, 1991

ChromaLab File #

Client: Aqua Resources, Inc. Attn: Aaron Stessman

Dec. 18, 1991 Date Sampled:

Date Submitted: Dec. 19, 1991

Date of Analysis: Dec. 26, 1991

Project Name: PG&E-ENCON Project Number: 90262.2 Sample I.D.: E-PIPE-2

Method of Analysis: EPA 8010 Detection Limit: 5.0  $\mu$ g/kg

COMPOUND NAME	μq/kq	Spike Recovery
CHLOROMETHANE	N.D.	
VINYL CHLORIDE	N.D.	<b></b> :
BROMOMETHANE	N.D.	
CHLOROETHANE	N.D.	
TRICHLOROFLUOROMETHANE	N.D.	
1,1-DICHLOROETHENE	N.D.	92.5% 90.8%
METHYLENE CHLORIDE	N.D.	
1,2-DICHLOROETHENE (TRANS)	N.D.	فلله خنچه وسي
1,1-DICHLOROETHANE	N.D.	
CHLOROFORM	N.D.	
1,1,1-TRICHLOROETHANE	N.D.	
CARBON TETRACHLORIDE	N.D.	
1,2-DICHLOROETHANE	N.D.	
TRICHLOROETHENE	N.D.	94.2% 91.7%
1,2-DICHLOROPROPANE	N.D.	
BROMODICHLOROMETHANE	N.D.	<del></del>
2-CHLOROETHYLVINYLETHER	N.D.	<del>+</del>
TRANS-1,3-DICHLOROPROPENE	N.D.	
CIS-1,3-DICHLOROPROPENE	N.D.	
1,1,2-TRICHLOROETHANE	N.D.	<b></b>
TETRACHLOROETHENE	N.D.	88.6% 85.4%
DIBROMOCHLOROMETHANE	N.D.	
CHLOROBENZENE	N.D.	
BROMOFORM	N.D.	
1,1,2,2-TETRACHLOROETHANE	N.D.	92.3% 91.0%
1,3-DICHLOROBENZENE	N.D.	<del></del>
1,4-DICHLOROBENZENE	N.D.	·
1,2-DICHLOROBENZENE	N.D.	

ChromaLab, Inc.

Yiu Tam

Analytical Chemist

Eric Tam

Lab Director

	AQU	A RES	OURC	ES,	INC.				NT NO.:_	_
		C	HAIN OF	cus	STODY RECC	RD			1_0F_ 12/19	
	PROJEC	T NAME:_	1076	<u>- E</u> 2.7	NCON_					
Sample Number	Location	Type of	Sample	7	e of Container	Type	of Preservati Chemica		Analysis	Required
-PIPE-Z	i	Material Product	Method Grap	Gla	SSJAR	±4°C			1	
1 14 1 14		/55		-		-				
				-						
						_				
						_		·		
						_				
		_		_					\	
									ļ	
			_							
				_			_			
				- -						
				_ _		_	\		_	
			_				- (-t)	7		
Total Number o	Samples S	Shipped:	Samp	oler's S	Received BY:	ا مرس	1	,.		Date 12/19 9
Relinquished By Signature		11. Te			Signature/	SEA		us E	Z	Time
Printed Name	<u>Harun</u> Re	12 C	SMCV-		Company	NROY	MALAIS			1000
Reason_ ro	יון מכינא	sis			Received By:					Date /
Relinquished B					Signature Printed Name					Time.
Printed Name Company					Company					1
					1 1 C.	_				ORD
1 = 5	ample	and a	nalyza	- P.C	oduct fo					· 17
	TVHG	4- RIE	^ , •	<b>.</b>	)					<b>ب</b> خ
, ,	ormal	Turna	.round	(						456
			<del></del>							<u> </u>
Special Shipm	ent / Handl	ing / Stora	je Requirer	men ls:	·					
		÷					•			

٠.

**5 DAYS TURNAROUND** 

Analytical Laboratory (E694)

January 13, 19921

ChromaLab File No.: 1291164

AQUA RESOURCES, INC.

Attn: Aaron Stessman

RE: One soil sample for TEPH analysis

Project Name: PG&E - ENCON Project Number: 90262.2

Date Sampled: Dec. 18, 1991 Date Extracted: Jan. 2, 1992

Date Submitted: Dec. 19, 1991 Date Analyzed: Jan. 7, 1992

#### RESULTS:

Sample _I.D.	Kerosene (mg/Kg)	Diesel (mg/Kg)	Motor Oil
E-PIPE-2	N.D.	7000	N.D.
BLANK	N.D.	N.D.	N.D.
SPIKE RECOVERY		91%	
DUP SPIKE RECOVERY		89%	
DETECTION LIMIT	1.0	1.0	10
METHOD OF	3550/	3550/	3550/
ANALYSIS	8015	8015	8015

ChromaLab, Inc.

Yiu Tam

Analytical Chemist

Eric Tam

Laboratory Director

Analytical Laboratory (E694)

January 13, 1992

ChromaLab File # 1291164

Client: Aqua Resources, Inc. Date Sampled: Dec. 18, 1991 Date Extracted: Dec. 31, 1991

Attn: Aaron Stessman Date Submitted: Dec. 18, 1991 Date Analyzed: Jan. 10, 1992

Project Name: PG&E-ENCON Sample I.D.: E-PIPE-2

Project Number: 90262.2

Method of Analysis: EPA 8270

Matrix: soil

	Ø=	<b></b>	,
COMPOUND NAME	Sample	MDL	Spike
COMPOUND NAME	mq/Kq	mg/Kg	Recovery
PHENOL PROPERTY AND THE PROPERTY OF THE PROPER	N.D.	5.0	
BIS(2-CHLOROETHYL) ETHER	N.D.	5.0	103.6%
2-CHLOROPHENOL	N.D.	5.0	
1,3-DICHLOROBENZENE	N.D.	5.0	
1,4-DICHLOROBENZENE	N.D.	5.0	
BENZYL ALCOHOL	N.D.	10	
1,2-DICHLOROBENZENE	N.D.	5.0	
2-METHYLPHENOL	N.D.	5.0	
BIS (2-CHLOROISOPROPYL) ETHER	N.D.	5.0	
4-METHYLPHENOL	N.D.	5.0	
N-NITROSO-DI-N-PROPYLAMINE	N.D.	5.0	
HEXACHLOROETHANE	N.D.	5.0	
NITROBENZENE	N.D.	5.0	
ISOPHORONE	N.D.	5.0	
2-NITROPHENOL	N.D.	5.0	
2,4-DIMETHYLPHENOL	N.D.	5.0	
BENZOIC ACID	N.D.	25	
BIS (2-CHLOROETHOXY) METHANE	N.D.	5.0	101.5%
2,4-DICHLOROPHENOL	N.D.	5.0	
1,2,4-TRICHLOROBENZENE	N.D.	5.0	** ** ** **
NAPHTHALENE	N.D.	5.0	
4-CHLOROANILINE	N.D.	10	
HEXACHLOROBUTADIENE	N.D.	5.0	
4-CHLORO-3-METHYLPHENOL	N.D.	10	
2-METHYLNAPHTHALENE	N.D.	5.0	
HEXACHLOROCYCLOPENTADIENE	N.D.	5.0	
2,4,6-TRICHLOROPHENOL	N.D.	5.0	
2,4,5-TRICHLOROPHENOL	N.D.	5.0	
2-CHLORONAPHTHALENE	N.D.	5.0	
2-NITROANILINE	N.D.	- 25	
DIMETHYL PHTHALATE	N.D.	5.0	
ACENAPHTHYLENE	N.D.	5.0	
3-NITROANILINE	N.D.	25	
ACENAPHTHENE	13	5.0	100.8%
2,4-DINITROPHENOL	N.D.	25	100.0%
4-NITROPHENOL	N.D.	25	
DIBENZOFURAN	N.D.	5.0	
(continued on next page)	14 • 17 •	J. U	<del></del>
(concernated on next hade)			

Analytical Laboratory (E694)

Page 2

1291164 ChromaLab File #

Project Name: PG&E-ENCON Sample I.D.:

E-PIPE-2

Project Number:

90262.2

Method of Analysis: Matrix: soil EPA 8270

Sample	MDL	Spike
mq/Kq	mg/Kg	Recovery
N.D.	5.0	
N.D.	5.0	93.0%
N.D.	5.0	
N.D.	5.0	
52	5.0	
N.D.	25	
N.D.	25	
N.D.	5.0	
N.D.	5.0	
N.D.	5.0	
N.D.	25	114.9%
76	5.0	
13	5.0	
N.D.	5.0	
13	5.0	
72	5.0	
N.D.	5.0	
N.D.	10	
44	5.0	
N.D.	5.0	
30	5.0	99.1%
N.D.	5.0	
N.D.	5.0	
N.D.	5.0	
16	5.0	
N.D.	5.0	
N.D.	5.0	
N.D.	5.0	92.2%
	N.D. N.D. N.D. N.D. N.D. N.D. N.D. N.D. 13 72 N.D. N.D. 144 N.D. 30 N.D. 16 N.D.	mg/Kg         mg/Kg           N.D.         5.0           N.D.         5.0           N.D.         5.0           N.D.         25           N.D.         25           N.D.         5.0           N.D.         5.0

ChromaLab, Inc.

Yiu Tam

Analytical Chemist

Eric Tam

Lab Director

	AQU	A RES	OURC	ES, INC.			HPMENT NO.:	
THAIN OF CUSTODY RECORD					P/	GE   OF_	1	
	ALL	•	700 d 0	- ENCON	)	D	ATE 12/31	191
	PROJEC	CT NAME:	7520	<u> </u>				
	PROJE		9026		Type	of Preservation	n Analysis	Required
Sample Number	Location	Type of Material	Sample Method	Type of Container	Temp	Chemical		
PT96 - 7		Soil	11100	BrassTube				
-PIPE-Z								
					_			
			<u> </u>			<u> </u>		· · ·
	.	<del> </del>	<del> </del>					
	-	1						
	-  <del></del>	<del> </del>	-			_		
	1				_			
					_			
			_	ļ				
	_					- <del> </del>		
	_							
	_	_			_			
	_			-				
	<del>-</del>	_	}	-				
		<u> </u>				_		. — —
	_						l	
Total Number o	Samples 5	hipped:	Sampl	er's Signature:				Date
Relinguished By:				Received By: Signature				1 1
Signature Printed Name_				Printed Name				Time
Printed Name				Company				<u>-</u>
Reason				- Buttered But	<u>-</u>			Date
Relinquished By				Received By: Signature				
Signature Printed Name_				Printed Name	·			Time-
Company				Company				<u> </u>
Reason			aje tu	rently hold			cb, submit	led 12/18
REMARKS:	בו פימו		3720 1000	and TEPH	10 K+1	motoroil)		
1-11	ease	ada e	0210	una lorn	(-)		وا در	1191
		<	rea ue	st given o	ver t	the pho	ne 1413	11 , ,
10.5	C. Mai	7	- L	J		12 1	1. St.	
					4	/ hand		•
Special Shipme	nt / Handli	ng / Storag	e Requirem	ents:				
Special Shipme		•						

Celease # 12854	
ENERATOR	
	•
1)	(2)
PGEE ENCON Gas Yard	WASTE TO BE DISPOSED
	Description of Waste
4930 Coliseum Way Oakland, CA	Soil Contaminated with Petroleum
EL: (415) 973-5615	Hudrocarbons
rder placed by:	7000
Wally Pierce Troy Einger	OTT. 3846045 Bbls Gal Cu/Yd 20
3)	Wear gloves, goggles and protective clothing.
ESIGNATED FACILITY	wear groves, goggres and protective crothing.
Gibson 0.1	This is to certify that the above named
3300 Truxtun Ave.	materials are properly classified.
Bakersfield, CA 43301	Control of the Contro
EL: (805) 327-0413	1- tinjel 12/3/9
PA CAD 980893177	Signature of Authorized Agent (Date
Release # 12854	
XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX	*************
RANSPORTER	
TANCO INCORDORATED	JOB NO. 1226/ UNIT NO. 2569
TAMCO, INCORPORATED.	•
7.0. Box 150	Pick-Up Date 12/3/9/ Time
2475-A Llagas Avenue	11ck-up bacc /2//3//11
an Martin, CA 95046 TL: (498) 268-1196	NOTE: This form is to be used in lieu of th
1 440 200-1130	California Department of Health Services
115/	Hazardous Waste Manifest for NON-HAZARDOUS
Signature of Authorized Agent	WASTES only.
12/3/91	
(Data)	
Date	
***************************************	******************************
DISPOSAL FACILITY	,
***************************************	•
ty. Received:	Bbis Gal Cu/Yd Tons
Date:	
Time:	,
3.	
DISPOSAL METHOD	
Surface Impoundment	Signature of Authorized Agent (Date
Injection	· •
Landfill	
Other	
	****************************

P.O. BOX 150 BAN MARTIN, CA 95046

Soil Disposal Manifest 1 of 128 (Typical)

GENERATOR		
(1)	(2)	
PGEE ENCON: Gas Yard	WASTE TO BE DISPOSED	A
4930 Coliseum Way	Description of Waste	
Oakland, CA 94601	. Groundwater contaminate	d with
TEL: (418)535-0600	· petroleum hydrocarbo	
Order placed by:		
Troufinger	OTY. 755 90   Bbls Gal Co	1/Ag ——
(3)		
DESIGNATED FACILITY	Wear gloves, goggles and protective	e clothin
and the second of the second o	A Company of the Comp	
Gibson Oil	This is to certify that the above i	named
475 Seaport Blud:	materials are properly classified.	marine see of the
TEL: (415) 368-5611	1- stonge	12/6/0
EPA + CAD 043260702	Signature of Authorized Agent	/ (Dat
Release #12878		4
VEIGG # 1 58 48		XXXXXXXX
XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX	*******	
TRANSPORTER	Truel	L#-
P.O. Box 150 2140 0'Too 12475-A Llagas Avenue SAN JOSE, CA San Martin, CA 95046 SAN JOSE, CA	e Ave Pick-Up Date 12/6/91 Time 9'2	00 am
12475-A Llasas Avenue SAN JOSE, CA San Martin, CA 95046 SAN JOSE, CA TEL: (408) 268-1196 (408) 988-23:	Pick-Up Date 12/6/91 Time 9'25 S13 NOTE: This form is to be used in California Department of Health Se Hazardous Waste Manifest for NON-H	∞am lieu of t rvices
P.O. Box 150 2140 0'Too 12475-A Llagas Avenue SAN JOSE, CA San Martin, CA 95046 SAN JOSE, CA	Pick-Up Date  2/6/9  Time 9'2 513 NOTE: This form is to be used in California Department of Health Se	∞am lieu of t rvices
P.O. Box 150 2140 0'Too 12475-A Llagas Avenue SAN JOSE, CA San Martin, CA 95046 SAN JOSE, CA TEL: (408) 268-1196 (408) 988-23:	Pick-Up Date 12/6/91 Time 9'25 S13 NOTE: This form is to be used in California Department of Health Se Hazardous Waste Manifest for NON-H	∞am lieu of t rvices
P.O. Box 150  12475-A Llagas Avenue San Martin, CA 95046  TEL: (408) 268-1196  (408) 988-23:  Signature of Authorized Agent  12/6/9(	Pick-Up Date 12/6/91 Time 9'25 S13 NOTE: This form is to be used in California Department of Health Se Hazardous Waste Manifest for NON-H	○ am lieu of t rvices
P.O. Box 150 2140 0'Too 12475-A Llagas Avenue SAN JOSE, CA San Martin, CA 95046 SAN JOSE, CA TEL: (408) 268-1196 (408) 988-23:	Pick-Up Date 12/6/91 Time 9'25 S13 NOTE: This form is to be used in California Department of Health Se Hazardous Waste Manifest for NON-H	∞am lieu of t rvices
P.O. Box 150 12475-A Llagas Avenue San Martin, CA 95046 TEL: (408) 268-1196  (408) 988-23: Signature of Authorized Agent  12/6/9( (Date)	Pick-Up Date  2/6/9  Time 9'2  \$13 NOTE: This form is to be used in  California Department of Health Se Hazardous Waste Manifest for NON-H WASTES only.	○○ ← m lieu of to rvices AZARDOUS
P.O. Box 150 12475-A Llagas Avenue San Martin, CA 95046 TEL: (408) 268-1196  (408) 988-23: Signature of Authorized Agent  12/6/9( (Date)	Pick-Up Date 12/6/91 Time 9'25 S13 NOTE: This form is to be used in California Department of Health Se Hazardous Waste Manifest for NON-H	○○ Am lieu of to rvices AZARDOUS
P.O. Box 150 12475-A Llagas Avenue San Martin, CA 95046 TEL: (408) 268-1196  (408) 988-23: Signature of Authorized Agent  12/6/9( (Date)	Pick-Up Date  2/6/9  Time 9'2  \$13 NOTE: This form is to be used in  California Department of Health Se Hazardous Waste Manifest for NON-H WASTES only.	○○ ← m lieu of to rvices AZARDOUS
P.O. Box 150  12475-A Llagas Avenue San Martin, CA 95046  TEL: (408) 268-1196  (408) 988-23:  Signature of Authorized Agent  12/6/9( (Date)	Pick-Up Date  2/6/9  Time 9'2  \$13 NOTE: This form is to be used in  California Department of Health Se Hazardous Waste Manifest for NON-H WASTES only.	○○ Am lieu of to rvices AZARDOUS
P.O. Box 150  12475-A Llagas Avenue San Martin, CA 95046  TEL: (408) 268-1196  (408) 988-23:  Signature of Authorized Agent  12/6/9(  (Date)  DISPOSAL FACILITY	Pick-Up Date  2/6/9  Time 9/2  513 NOTE: This form is to be used in California Department of Health Se Hazardous Waste Manifest for NON-H WASTES only.	CO AM lieu of trices AZARDOUS
P.O. Box 150  12475-A Llagas Avenue San Martin, CA 95046  TEL: (408) 268-1196  (408) 988-23:  Signature of Authorized Agent  12/6/9(  (Date)  DISPOSAL FACILITY  Qty. Received:	Pick-Up Date  2/6/9  Time 9'2  \$13 NOTE: This form is to be used in  California Department of Health Se Hazardous Waste Manifest for NON-H WASTES only.	CO AM lieu of trices AZARDOUS
P.O. Box 150  12475-A Llagas Avenue San Martin, CA 95046  TEL: (408) 268-1196  (408) 988-23:  Signature of Authorized Agent  (Date)  Oty. Received: Date:	Pick-Up Date  2/6/9  Time 9/2  513 NOTE: This form is to be used in California Department of Health Se Hazardous Waste Manifest for NON-H WASTES only.	CO AM lieu of trices AZARDOUS
P.O. Box 150  12475-A Llagas Avenue San Martin, CA 95046  TEL: (408) 268-1196  (408) 988-23:  Signature of Authorized Agent  12/6/9(  (Date)  DISPOSAL FACILITY  Qty. Received:	Pick-Up Date  2/6/9  Time 9/2  513 NOTE: This form is to be used in California Department of Health Se Hazardous Waste Manifest for NON-H WASTES only.	CO AM lieu of trices AZARDOUS
P.O. Box 150  12475-A Llagas Avenue San Martin, CA 95046  TEL: (408) 268-1196  (408) 988-23:  Signature Authorized Agent    2   6   9    (Date)  DISPOSAL FACILITY  Qty. Received: Date: Time:	Pick-Up Date  2/6/9  Time 9/2  \$13 NOTE: This form is to be used in California Department of Health Se Hazardous Waste Manifest for NON-H WASTES only.	Cons
P.O. Box 150  12475-A Llagas Avenue San Martin, CA 95046  TEL: (408) 268-1196  (408) 988-23:  Signature Authorized Agent  12/6/9( (Date)  DISPOSAL FACILITY  Qty. Received: Date: Time:	Pick-Up Date  2/6/9  Time 9/2  \$13 NOTE: This form is to be used in California Department of Health Se Hazardous Waste Manifest for NON-H WASTES only.	CO AM lieu of trices AZARDOUS
P.O. Box 150  12475-A Llagas Avenue San Martin, CA 95046  TEL: (408) 268-1196  (408) 988-23:  Signature of Authorized Agent  12/6/9( (Date)  Oty. Received: Date: Time:  DISPOSAL METHOD: Surface Impoundment	Pick-Up Date  2/6/9  Time 9/2  513 NOTE: This form is to be used in California Department of Health Se Hazardous Waste Manifest for NON-H WASTES only.	Cons
P.O. Box 150  12475-A Llagas Avenue San Martin, CA 95046  TEL: (408) 268-1196  (408) 988-23:  Signature Authorized Agent  12/6/9( (Date)  DISPOSAL FACILITY  Qty. Received: Date: Time:	Pick-Up Date  2/6/9  Time 9/2  \$13 NOTE: This form is to be used in California Department of Health Se Hazardous Waste Manifest for NON-H WASTES only.	Cons

P.O. BOX 150 BAN MARTIN, CA 95046 ate of California—Hearth and Wefare Agency

pri	nt or type. Form designed for use on eite (12-pitch typewnier).						Sacramento, California
٠		71.41.7.8454	2 0 i	611	2. Page 1		in in the shoded dreat: lited by federal law.
	HO. Box 7033, oaklant Ca 90	1601		*****	Marsfest Document	) Periment	
	4 Generators Phone (50) 535-0600			Total or bearing	Y.H.aJ.L	110101	8.79.8
	5. iranscorrer I Company Name	Jus EPA ID Number		೧೦೦ ವರ್ಷಕ	ironsporters D 🗸	43	764-7
	Stamco Inc	CADIO1635141	7.9.96	D. Tions	conters Phone 4	08	262-1196
ĺ	7, Transparrer 2 Company Name	3. US EPA ID NUMBER		E Store	Transporter's ID		
- }	2 Company of Considerations and State Original	10, US EPA IO Number	1 1 1		corter's Phone:		
	Libergrand facility warms and ste degrees a regiment	TO SEPAID NOTICE			rdicii	1 1 1	-10010-1
Ì	29=7 77 c. to Ca 93239	CaTIOIOIDIBHIL	11117	H.Foca	1-800-3	722-	-1964
	11, US DOT Description (including Proper Shipping Name, Hazard Cla		12, Como	X14/3	13. force	14. Unst	
	an on - HCRA Hazara		No.	yoe	Quantity	Wt/Vox	Stose Store
.	= 1 / Old = 1/ Gill = ================================	12 3 AUG. 1 COCK					کہلے
			6001	ו אום ו	00000	Y	PAGINE RCEA
	a,	· · · · · · · · · · · · · · · · · · ·		-		/	Sicrex
					-		EACING:
			1 1	,	1   1		
	G.	•					Stores: y
	,						⊕A/Othek
	<b>a</b> .			,	1 1 1 1		Sicie
	•						
			, ,				EA/Cites
<i>/</i> `	LACOTORIO Descriptore for Agreement special Above  ON CONTORNIA MATERIA DED			(c) tana	ng Codes for Worke	Listed Abo	<b>1V0</b>
	CIL Conformated Dec	74		d.		D.	
				<b>C</b>		<b>a</b>	····
	15. Separate Mean first trattor trata cost Adaptions Information			**********			
	15. Sources Handling Instructions and Adaptional Information. Chem Waste Profit.	=== F921/46					
	In Case of Emergen		. (	7.	540-0	5954	1 7586 75
-	T V C335 0+ 5 monday	my call mare	,- (	נים י		,	3/
	16. GENERATOR'S CERTIFICATION: I hereby decide that the conter	ns of this consignment are fully and	cocurcien o	XMCTD9CI	above by proper st	noong na	ne and are assisted.
	pactied, marked, and labeled, and are in all respects in proper of	· -	_			_	-
	if I am a large quantity generator, I certify that I have a progression economically practicable and that I have selected the practical						
	threat to human health and the environment; OR, if I am a small management method that it available to me and that I can arts		the ritical boos	on to min	unipa usk weste debe	eration and	select the pest woste
	Printed/Typed Name	Signature	,			Mont	l Day feat
ĺ	•						, 50y /602
,	Trov E. FWGER		Mia	$\sigma/ $		11.2	11,819,11
•	17. Transporter 1 Adknowledgement of Receipt of Materials	<del>-                                    </del>	<del>- J</del>				-: ; O: 111 <u>.</u>
	Printed/Typed Name	Signature				Monm	i ⊃ony Yexon
	man / 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	1-1-1-10 l	( ) .	0 1	7	_	1
,	PICARE INACSA	8//	00			1 2	- 1 3017 1
	Ironsporter 2 Acknowledgement of Receipt of Materials     Printed/Typed Name	Signature				Month	Day Year
			•			1	
					•	_ ]	1 i 1 i
	19, Discrepancy indication Space	<u> </u>					
	• •						
-	20. Focalty Owner or Operator Cartification of receipt of hazardous re	CONTRACTS COVERED BY THIS INCOMEST EXC	ect os notec	indem 19	7.		
r	Рипеа/Гуреа Name	Sgrature-				Молл	Day Year
<b>'</b>					للمعلى منتمي		
			,		· 		<u> </u>

e of California -- Health and Welfare Agency See instructions on back of page 6. Form designed for use on eite (12-pitch typewriter). Socromento, Catifornia 2, Page 1 information in the shaded areas UNIFORM HAZARDOUS WASTE MANIFEST Pa Box 7013, OAKLAND, CA 94101 A: Skate-Moorlest Document Humber 1:51729 i Sicre Generators (C. 4. Generators Phone (SVO ) H 44016001798 535-0600 5. Transcorter I Company Name US EPA ID Number AD10163151417191916 JAMCO INC 7, Transporter 2 Company Norte 8. US EPA IO NUMBER F. Tronsporter's Phon Chemical Commence on the Action Commence of the Commence of th IO. US EPA ID Number G. State Foreity's Dis-POBOLITA CT, CA 95039 CAT10,0016,4161117 12. Conformers US DOT Description (including Proper Shipping Name, Hazard Class and 10 Number) VO Wt/Vol Questity Wate Number · non-HCRA HAZOLOOUS WASTE SOLID 0,01 Dit a 0,0,20 EPA/C/h EPA/Other Strategy OH Contaminated Delecis KeHanding Codes for Wastes Listed Abov 0.000 15. Social Handing instructions and Additional information—
Chem WASTE Profile F92746 In CASE of Emergercy CALL ABROW (510) 540-6954 16, GENERATOR'S CEXTRICATION; I hereby declare that the contents of this consignment are fully and accurately described above by proper shapping name and are cassified. packed, marked, and labered, and are in all respects in proper condition for transport by nighway according to applicable international and inational government requiations. If I arm a large augustity generator, I centry that I have a program in place to reduce the volume and taxicity of waste generated to the degree I have determined to be aconomically practicable and that I have selected the practicable method of freatment, storage, or disposal currently available to the which minimizes the present and future threat to numan heath and the environment CR, Y I am a small augstify generator, I have made a good faith erfort to minimas my waste generation and select the best waste management method that is available to me and that I can afford. Printed/Typed Name Signature 17. Transporter I Acknowledgement of Re Printed/Typed Nome Printed/Ivped Name Sanature Moore 19. Discrepancy Indication Space 20. Focally Owner or Operator Centrication of receipt of hazardous materials covered by this manifest except as noted in rem 19. Signature error/Typea Name Month 

) 852 -	2840			•	;	**	W.		JOB NO.	or P O NO.
•		D/	AILY	FIEL	D RE	EPOF	RT	· .	9 D	5.03
		<u> </u>								l or/
PROJECT NAME	// 1	CLIENT OR	11	$\mathbf{i}^{-1}$	,			DAILY FIEL	LD REPORTS	EQUENCE NO.
GENERAL LOCATION	Yerd ON OF WORK	OWNER OF	CLIENT'S PI	タイプ <b>モル</b> EPRESENTAT	NE .			DATE		DAY OF WEEK
Dolf of GENERAL CONTRA		Agu		Soul	ees-	A115-		15-11	1-91	Thurs
GENERAL CONTRA	ACTOR		CONTRACTO	A				PROJECT	ENGINEER	
TYPE OF WORK		GRADING (	CONTRACTO		7 C C	FOREMAN		SUPERVIS	OR	
- 1	sample		٠						ron	
SOURCE AND DES	SCRIPTION OF MALERIAL	(IMP	ORT OR SITE		W	EATHER		TECHNICA	M //	veira
DESCRIBE EQUIP	MENT USED FOR HAULING, SPRI	EADING, WATI	ERING, CONC	OFFIONING, AN	ID COMPACT			1 00000	<u> </u>	
	<u> </u>		_ <del></del>		IELD TESTIM			FERENCE CU		
TEST NUMBER	TEST LOCATION		ELEV (feet)	DRY DENSITY	MOISTURE CONTENT	% OF MAXIMUM	COMP CURVE	DRY	MOISURE	COMMENT
1				itos /cu. it.	%	DRY DENSITY	NO.	DENSITY lbs /cu. ft.	CONTENT %	
1 128	est side of east s	trip-01	-4.5	106.4	19.3	86	/	125.7	9.6	
~ F0	est side of east s	strip-Od	5-7	112	15.7	87	2	129.1	2.9	
		•		<del> </del>					1	
									· software Fig.	(C)
										A. 700
					<u> </u>			<del> </del>		<del> </del>
							ļ	1		
<del></del>										
				T		[				
	<del></del>		<u> </u>	ļ	ļ. <u></u>	<del>                                     </del>	+	+	· <del> </del>	
MOTES (Describ	e wrote commissed during the day ar	ny problems an	d their solution	ns)						
NOTES (Describe	e work completed during the day, ar	ny problems an	d their solution	ns)			<u> </u>			
			d their solution		the	exc	avet	red o	rea	o +
I	took towo		<del></del>		the	exc	avet			
I the	took towo	t.	<del></del>	in th	e /	exc of,	Nor	th of	the 1.	0 + P6 + E
I	took towo	side sk	ests z		e la mple	exc st,	Nor		the 1.	
I the	took towo	side sk	<del></del>	in th	e /	exc s +,	Nor	th of	the 1.	
I the	took towo	side sk	ests z	in th	e la mple	exc s t,	Nor	th of	the 1.	
I the	took towo	side sk	ests z	in th	e la mple	exc st,	Nor	th of	the 1.	
I the	took towo	side sk	ests z	in th	e la mple	exc s +,	Nor	th of	the 1.	
I the	took towo	side sk	ests z	in th	e la mple	exc s t, s	Nor	th of	the 1.	
I the	took towo	side sk	ests z	in th	e la mple	exc s +,	Nor	th of	the 1.	
I the	took towo	side sk	ests z	in th	e la mple	exc T	Nor	th of	the 1.	
I the	took towo	side sk	ests z	in th	e la mple	exc st, s	Nor	th of	the 1.	
I the	took towo	side sk	ests z	in th	e la mple	exc s +, s	Nor	th of	the 1.	
I the	took towo	side sk	ests z	in th	e la mple	exc s t, s	Nor	th of	the 1.	
I the	took towo	side sk	ests z	in th	e la mple		Nor	th of	the 1.	
I the	took towo	side sk	ests z	in th	e la mple	exc T	Nor	th of	the 1.	
I f the e yord. two	took towo	side sk	ests z	in th	e la mple	T	Nor	th of	the 1.	
I f the e yord. two	book towo pest (recr) T to different	side sk	ests z	in th	e la mple		Nor	th of	the 1.	PGTE
I f the e yord. two	book towo pest (recr) T to different	side sk	ests 2 pils	in th	e /c		Nor	th of	the 1.	

Aquo Reg. Fox 540-7496

Voytek



## CONSTRUCTION MATERIALS TESTING, INC.

 Job Name:
 P6-b2
 OAKCAND
 Job No.
 90553

 Sample Description:
 VY DK CK S D CCMY W/6RHUEL
 Sample No:
 /

 Source:
 -4.5'
 Date:
 //-22-9/


 Client No:
 AQVA RESOVECES
 Sampled:
 35
 Tested:
 4

#### COMPACTION CURVE


% Retained on 3/4": ASTM D1557 (A* mold) ASTM D1557 B C or D (6* mold)

% Retained	UII 3/4 .	70111101	7 7 7 7 110	7.0, 7.0 7.1. 2	1337 13 0 01 13 (6 11616)
Trial No.	-100	-50	0	+50	Group Symbol:
Wet Weight	1879	2005	2057	2044	4" MOLD  Wet Den. = .06614 x Wet Wt.
Wet Den.	·	·			Dry Den. = <u>Wt Den.</u> 100 + % H ₂ O
Dry Weight	1766	1856	1868	1828	
Moisture					6" MOLD  Wet Den. = .02939 x Wet Wt.
% Moisture	6.4	.8.0	10.1	11.8	Dry Den. = <u>Wt Den.</u> 100 + % H ₂ O
Dry Den.					

#### Sample



MOISTURE RANGE	LAB DATA
low hish   95% 6.3 13.3   90% 4.9 16.3   85% 3.9 19.6   80% 3.0 23.3	dens mois 1. 116.8 6.4 2. 122.8 8.0 3. 123.5 10.1 4. 120.9 11.8






### CONSTRUCTION MATERIALS TESTING, INC.

Jo	ob Name:	PG+2			Job	No. 90553
		iption: Dic 4 c	BK CL SAN	W/GRAVEL	AND A REAL PROPERTY.	nple No: 2
S	ource:	-7'		era 🕻 — er Medera i	Dat	e: //-22-9/
	lient No:		e Karana		Sar	mpled: Tested: <u>\$2</u>
· \$1. ·	er a salah beraran	en in the same	the state of the s	MPACTION CU		
	% Retaine	ed on 3/4":	ASTM D1	557 A (4" mo	ld) ASTM D1	1557 B or D (6" mold)
	Trial No.	0	+100	1200	+200	Group Symbol:
	Wet Weight	4430	4657	4798	4614	4" MOLD  Wet Den. = .06614 x Wet Wt.
-	Wet Den.					Dry Den. = Wt Den. 100 + % H ₂ O
	Dry Weight	4156	4307	4361	4109	
,	Moisture					6" MOLD  Wet Den. = .02939 x Wet Wt.
٠	% Moisture					Dry Den. = Wt Den. 100 + % H ₂ O
	Dry Den.					





MOISTURE RANGE	LAB DATA
10W high 95% 7.0 11.8 90% 6.3 14.7 85% 5.7 17.8 80% 5.2 21.4	dens mois 1. 122.1 6.6 2. 126.6 8.1 3. 128.2 10.0 4. 120.8 12.3



90553

OJECT NAME	Yard		CLIENT OF	oyte	L				DAILY FIEL	2	JUENCE NO.	
VERAL LOCAT	ION OF WORK	·	OWNER O	RCLIENTSA	EPRESENTAT				DATE			
Dal	TION OF WORK		Agu	G R	esour	ردع	11-22-91 FRI					
	ERAL CONTRACTOR GRADING CONTRACTOR								PROJECTI	ENGINEER		
			PA.	e s	Tame	20			ļ		2	
PE OF WORK	pling		GRADING	CONTRACTO	OR'S SUPERIN	SUPERVISOR						
URCE AND DE	SCRIPTION OF FILL	MATERIAL	(IMF	PORT OR SIT	E)	¥	EATHER Zefy		J. Musser			
SCRIBE EQUIF	PMENT USED FOR H	AULING, SPRE	ADING, WAT	ERING, CONI	DITIONING, A							
						4						
		•				IELD TESTIN			FERENCE CU			
TEST UMBER	TEST L	OCATION		ELEV (feet)	DRY DENSITY Ibs /Cu. It.	MOISTURE CONTENT %	% OF MAXIMUM DRY DENSITY	COMP CURVE NO.	MAXIMUM DRY DENSITY Ibs /cu. ft.	OPTIMUM MOISURE CONTENT %	COMMENTS	
					-37							
					<u> </u>	<u> </u>			<u> </u>			
	<del></del>								-			
	<u> </u>								<del>                                     </del>			
							1	1				
										<del>-</del>		
•	os work completed dur											
•	·					f in please	Recy 1 F	relec	/ / /e.	AB rious		
,	Picked Les,					f please	Recy 1 f.	relections #3	/ / /c.	AB rious		
,	·					on please	Recy d F.	clections #3	/ / /c.	AB rious		
,	·					f please	Recy 1 f.	relections #3	Ve.	AB rious		
,	·					f please	Recy 1 F.	clectom #3	/ /c.	AB rious		
,	·					f please	Recy 1 f.	relections #3	Ve.	AB rious		
•	·					f please	Recy 1 F	relections #3	/ / / Vc.	AB rious		
Fer pi	·					e plea Curi	Recy 1 f.	relections #3	/ / / / / / / / / / / / / / / / / / /	AB rious		
Fer p	·					f please	Recy 1 F	relections #3	/ /c.	AB rious		
Fer p	·					F please	Recy 1 f.	relections #3	/ / / / / / / / / / / / / / / / / / /	AB rious		
Fer pi	·					f please	Recy 1 F	relections #3	/ /c.	AB rious		
Fer p	·					Fuple	Recy 1 f.	relections #3	/ /c.	AB rious		
Fer p	·					F please	Recy 1 F	relections #3	/ /c.	A/B rious		
Fer pi	·					Fuples	Recy 1 F.	relections #3	/ /e.	A/B rious		
Fer p	·					Finple	Recy 1 F	relections #3	/ /e.	AB rious		
Fer pi	·	up Curv This		mple I					y ve.		CONTINUED	

## CONSTRUCTION MATERIALS TESTING, INC.

 Job Name:
 P & E E
 Job No.
 9053

 Sample Description:
 DK 90 BRN Puly c/s I
 Sample No:
 3

 Source:
 Date:
 1/-22-9/

 Client No:
 Sampled:
 Testedit

#### **COMPACTION CURVE**


% Retained on 3/4": ASTM D1557 A (4" mold) ASTM D1557 B C or D (6" mold)

Trial No.	-/00	0	+100	+200	Group Symbol:
Wet Weight	4464	4699	4893	4794	4" MOLD  Wet Den. = .06614 x Wet Wt.
Wet Den.			·		Dry Den. = Wt Den. 100 + % H ₂ O
Dry Weight	. 433/	4447	4553	4382	
Moisture		UQA	RESOURCE	s, INC	6" MOLD  Wet Den. = .02939 x Wet Wt.
% Moisture		•	LER J 9 198	£	Dry Den. = <u>Wt Den.</u> 100 + % H ₂ O
Dry Den.		JOB	NO		

#### Sample

Maximum Dens: 134.5 pcf Optimum Mois: 6.7 %

MOISTURE RANGE	LAB DATA
10w hish 95% 4.1 9.8 90% 3.0 12.5 85% 2.2 15.5 80% 1.5 19.0	dens mois 1. 127.3 3.1 2. 130.7 5.7 3. 133.8 7.5 4. 128.8 9.4



	115				İ			9-14		
0	115 3479 12-12:30							*		OF P O NO.
198-	72:30	D/	AILY	FIEL	D RE	POF	<u>₹T</u>		PAGE	553
OJECT NA	12 ME	CLIENT OR	OWNER					DAILY FIEL	D REPORT SE	OF /
P6+	CATION OF WORK	Vo	ytek	EPRESENTAT	· .				3	DAY OF WEEK
		OWNEROF	YCLIENT'S R	EPRESENTAT	A c			//- 2:	3-9/	
NERAL CO	ontractor							PROJECTE	NGINEER	<u> </u>
PE OF WO	ABK.	GRADING	CONTRACTO	R'S SUPERIN	C &	FOREMAN		SUPERVIS	OR ·	<del></del>
	of Back Fill DDESCRIPTION OF FILL MATERIAL									
URCE AN	DIDESCRIPTION OF FILL MATERIAL	(IMP	ORT OR SITE	9)	W	ATHER		To b.	· Olic	reira
SCRIBE E	QUIPMENT USED FOR HAULING, SPRE	EADING, WAT	ERING, CONI	DITIONING, A				<u> </u>		
				F	RELD TESTIN	·	RE	FERENCE CU	RVE	
TEST UHBER	TEST LOCATION		ELEV (feet)	DRY DENSITY Ibs /cu. ft.	MOISTURE CONTENT %	% C/F MAXIMUM DRY DENSITY	COMP CURVE NO.	DRY DENSITY lbs/cu.ti.	OPTIMUM MOISURE CONTENT %	COMMENTS
	none taken									
		-			<u> </u>					<del></del>
								<u> </u>		<u> </u>
				1	ļ			ł		
			[."	<u> </u>	<del>                                     </del>			<del> </del>		
OTES (D	escribe work completed during the day, ar	ny problems an	d their solution	ns)			_			
	escribe work completed during the day, and the chor short				action	y +1	íc v	otius	501	
					action x eco	٠, ,	0102	efius	soi Le Co	mpretor
				he e		٠, ,	0102	. Tl	50i	1
			Karl of t	the e	X CCU	sted	0100	. Tl	ne lo	1
		ted /	Kasi of t proble book	he e  klilli  roin	so ig- rock	not	0100	. Tl	ne lo	/
		ted /	Soul of the book the d	he e he e kfills	x eeu (	not	0100	. Tl	ne lo	1
	the southern e had mechanic -plished as formed the areas the	ted of side of laid	proble book	he e he e kfills	so ig- rock	not	0100	. Tl	ne lo	1
	nfrector stern the southern e had mechanic -plished as formed	ted of side of laid	Soul of the book the d	he e he e kfills	so ig- rock	not	0100	. Tl	ne lo	1
	the southern e had mechanic -plished as formed the areas the	ted of side of laid	proble book	he e he e kfills	so ig- rock	not	0100	. Tl	ne lo	1
	the southern e had mechanic -plished as formed the areas the	ted of side of laid	proble book	he e he e kfills	so ig- rock	not	0100	. Tl	ne lo	1
	the southern e had mechanic -plished as formed the areas the	ted of side of laid	proble book	he e he e kfills	so ig- rock	not	0100	. Tl	ne lo	1
	the southern e had mechanic -plished as formed the areas the	ted of side of laid	proble book	he e he e kfills	so ig- rock	not	0100	. Tl	ne lo	1
	the southern e had mechanic -plished as formed the areas the	ted of side of laid	proble book	he e he e kfills	so ig- rock	not	0100	. Tl	ne lo	1
	the southern e had mechanic -plished as formed the areas the	ted of side of laid	proble book	he e he e kfills	so ig- rock	not	0100	. Tl	ne lo	/
	the southern e had mechanic -plished as formed the areas the	ted of side of laid	proble book	he e he e kfills	so ig- rock	not	0100	. Tl	ne lo	1
	he southern  he had mechanic  plished as formed  the areas the  sc IT AB A	ted of side of laid	Basi of the book the de re e	he e he e kfills	so ig- rock , ote d	not	0100	. Tl	ne lo	/

JOB NO. or P O NO.
905-3
PAGE

		T							2 - 2 2 2 2 7 6	
PROJECT N		CLIENTOR		/ ,	•			DAILY FIEL		EQUENCE NO.
4648	2 yord	<u> </u>	Voy t	REPRESENTAT	:			1		<u> </u>
_	OCATION OF WORK	OWNER OF	CLIENTSF	REPRESENTAT	TVE					DAY OF WEEK
1)0	klond	l		Arra	- Agu	o Rese	NV e + 1	1/-2	4-91	Sun
	ONTRACTOR	GRADING (	CONTRACTO	OR .				PROJECT	ENGINEER	
		1 5	femo	- ^				,		
TYPE OF WO	OPIK	GRADING (	CONTRACTO	OR'S SUPERIN	TENDENT OF	FOREMAN		SUPERVIS	OR	
Tto		-								
POLIBOR AN	ND DESCRIPTION OF FILL MATERIAL	1MP	OR) OR SIT	(E)	W	EATHER		TECHNICIA	AN	
Λ.	- D. 4 Class	, 711		1 46			r+		Olive	100
DESCRIBE!	EQUIPMENT USED FOR HAULING, SPR	READING, WAT	ERING, CON	DITIONING, A	ND COMPACT	ING	, ,		1000	1/-4
2114	votor, looder, s	·lant	ent.	1 rate	- de4					
excou	10tor 1000er , 5	( Person	<i>5011</i>	1 40	FIELD TESTIN	<b>~</b>	RE	FERENCE CU	OVE	1
TEST	TEST LOCATION	J	ELEV	DRY	MOISTURE	<del>,</del>	COMP	MAXIMUM		COMMENTS
NUMBER		J	(feet)	DENSITY	CONTENT	MAXIMUM	CURVE	DRY	MOISURE	1
!	1	J	1	los /cu. ft.	*	DRY	NO.	DENSITY tos/cu. ft.	CONTENT %	!
	<del>                                     </del>		<del></del>	1	1		<del></del>			
3	native soil		-5	118.6	14.9	92	2_	129.1	8.9	
r.i	South 1400 West C	125+C	<u> </u>	<u> </u>	1		<u></u>	<del>                                     </del>	<u> </u>	
4	81+00 WO+20		-45	170.3		96	3	134.5	6.7	Failed
5	Refest #4		Γ	127.2	6.7	95	3	1	/	RTop
6	50195, WO+30		-3/2	131.6	7.7	98	3		Γ	
7	50+80, WO+15		-3-	128.3	+	95	3			
	JUTOU, WU.		<del>  =</del>	1000	1	+-	<del> </del>	<del> </del>		
			<del> </del>		<del> </del>	+	<del>                                     </del>	+		+
			<del> </del>	+	<del> </del>	<del> </del>	<del> </del>	<del> </del>	<del> </del>	<del>                                     </del>
			<del> </del>	+	<del> </del>	<del> </del>	<del> </del>	<del> </del>	<del> </del>	<del>                                     </del>
	<u> </u>			<del> </del>	<del>                                     </del>	<b></b>	<del> </del>	<u> </u>	<u> </u>	ļ
			<u> </u>			ļ			ļ	
						[	I			
NOTES (D	Describe work completed during the day, a	iny problems and	d their solutio	ins)		,			. ,	
lon	treetor compos	ted 1	460	notio	ر ح	· //	,≠ <u> </u>	5-0	levoti	in ou
the	south end o				_			<u> </u>	<u>/ 4</u>	05
Lake	en out in	the	-11	1 0.	ort.	. f	160	licle	to	æ
	_			,				<i>I</i>		·
900	roximote dep	th c	<u>&gt; +</u>	<u>- ) [.</u>		is 1	5 62	here	the	<del></del>
1/2:	in rock is	alac.		de	A	+ 0	10 10	ximot.	6/2	2 -
aroi	H /OCK	<del>-10,5\\</del>	<del> </del>	<u> </u>	- <del> </del>	<del>′                                    </del>	pp		<del>-/7</del>	<u> </u>
thic	-k. Fobric	will	<u> 6e</u>	Ale	red	000	2UC	<u> +401</u>	<u> </u>	from
- /		that	11.	/ ^/	/.1	/	Locia	/		. /
/n T	ormed me	7 11 27	<u> </u>	<u> </u>	415	<u> </u>	**/*/	<del>-/~/</del>	USFIE	
Was	s not class T	T:_1	<u>در ک</u>	95 3	soid	<u>+0</u>	6c_	<u> </u>	111	-
1	.//	1/4			1	4.4		/		-1
HIE	m colled 10	ytek.	0-1	d go	+ cf	prove	2/7	5 05	<u> </u>	<i></i>
۱ ،	to within		´ a	I B	Lini.	1 0		0.	Cles	c (
· · ·	10 00 11 47 6	<del></del>		<del></del>	<del></del>	<del>, ,</del>	<u> </u>		<del></del>	<u> </u>
$\mathcal{I}$	AR is mon	ditory	A	ove	that	<u>′</u>	<del></del>			
İ		7								
Wor	-k is expecte	d to	185	one	Mono	dou L	shen	the	4 98	/
01	7	,			./	7			7-0	
ر دط م	ic on sity.	Accom	( ( )	11 0	c/ _			<del></del>	<del></del>	
	, , , , , , , , , , , , , , , , , , ,	~				***********	<del></del>	<del></del>		
					<del></del>				<u> </u>	
TIME BILL	LED 4 HRS.,		1	NO. OF VISITS	e					CONTINUED
1802			<u> </u>							
DECEMEN	A 8V				CODY	GIVEN TO				

JOB NO. or P O NO. 90553 PAGE

										/ OF '	1	
NECT N		CLIENT OF	,		- 1			DAILY FIEL		QUENCE NO.	1	
P.C. & E. GALD ENERALLOCATION OF WORK ON			OWNER OR CLIENT'S REPRESENTATIVE									
			OWNER OR CLIENT'S REPRESENTATIVE APLOW - AGUA RESOLUCES						DATE, DAY OF WEEK			
OAKLANID			401/-	Haus	g KER	11/25/	4/25/91 Mo					
ERAL CO	ONTRACTOR	GRADING	CONTRACTO	R			PROJECT ENGINEER					
		-	SIE	mco								
E OF WE	ORK	GRADING	CONTRACTO	OR'S SUPERIN	TENDENT OR	FOREMAN		SUPERVIS	OR		7	
TA	10			*.								
FICE AN	ND.DESCRIPTION OF FILL MATERIAL	(Mi	PORT OR SIT	Έ)	W	EATHER		TECHNICIA	W		1	
	•				F.	AIR		B. C	LECTOR	·/	1	
CRIBE E	EQUIPMENT USED FOR HAULING, SP	READING, WAT	FERING, CON	DITIONING, A	ND COMPACT	ING					7	
BomA	49 LOADER HZO.	truck	EXCA	944907C								
			1		TELD TESTIN		REF	ERENCE CU	RVE		7	
TEST_	TEST LOCATION		ELEV	DRY	MOISTURE		COMP	MAXIMUM	OPTIMUM MOISURE	COMMENTS	i	
MBER			(feet)	DENSITY lbs/cu.ft.	CONTENT %	MAXIMUM DRY	CURVE NO.	DRY DENSITY	CONTENT		1	
l						DENSITY		los /cu. ft.	%		1	
7	51+20 410+	25	-32	125.5	17.8	93	134.7	6.5		MEASURM NYI CORN SUBGX.	ani	
0	RT#9		<del>                                     </del>	127.2		95	3		óK	NY/ CORA	16	
7	50+50 W 0+40	<u> </u>	-5'	124.5		93	3		(E)	SUBEN	1	
-	87 # /1	<u>/</u>	- 3	127.2	+	95	3	-	OK.	JUN OK.	1	
2	K   -11	<del></del>	+	107.6	2-3	72			<i>67</i> ~		1	
			<del> </del>	+	<del>                                     </del>	i			<u> </u>		1	
	<u> </u>	<del></del>	+	-	<del> </del>	-		<del> </del>			$\dashv$	
				<del> </del>	ļ						-{	
	I		1	ļ	ļ—			<del></del>			4	
								i .	1	l .		
			<u> </u>		<u> </u>						4	
											_	
res (D	Describe work completed during the day,	any problems ar	nd their solution	ns)							1	
		<del>.,</del>				10.14			7 1			
	Describe work completed during the day,	<del>.,</del>			suc	bey d	ou ou	24 8	7 10	mer_		
		<del>.,</del>			Aur.	sex d	au Su Si	Lecu De	7 Jo + 1 ge	rner Herêg		
	retisetor conten	They	to su	fill have	ilg 1	sex d	au Suff	es &	7 Jo	mer tine		
		They	to su		ilg 1	sey d	Se for	ea steen the	1 Jo	men teris		
Co reli	retisetor conten	They	to su	fill have	ilg 1	sey'd	Su fi	ra e	7 Joseph	ture tests		
Co reli	retisetor contra Oline shap, su moisture	They	to su	fill have	ilg 1	sey'd	su su su su su su su su su su su su su s	Leculti	J Jo	men tenis,		
Co reli	retisetor contra Oline shap, su moisture	They	to su	fill have	ilg 1	sey'd	Su fo	leculli res	J Jo	tuig tests		
Co reli	retisetor contra Oline shap, su moisture	They	to su	fill have	ilg 1	sex d	July State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the State of the	ra s leculti	1 Jo	men teng		
Co reli	retisetor contra Oline shap, su moisture	They	to su	fill have	ilg 1	sey d	le su	ra s Veculti	1 Jo	men ting		
Co reli	retisetor contra Oline shap, su moisture	They	to su	fill have	ilg 1	bey d	July	ra o	I Jo	mer terie		
Co reli	retisetor contra Oline shap, su moisture	They	to su	fill have	ilg 1	sey'd	Su fg	ra &	I for	ture,		
Co reli	retisetor contra Oline shap, su moisture	They	to su	fill have	ilg 1	sey'd	Su fg	Lecu Al	t ge	men tenis,		
Co reli	retisetor contra Oline shap, su moisture	They	to su	fill have	ilg 1	sey'd	Su fg	La de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la constante de la const	t ge	tuis,		
Co reli	retisetor contra Oline shap, su moisture	They	to su	fill have	ilg 1	sey &	Su fi	A OIL	t ge	Conves, IN		
Co reli	retisetor contra Oline shap, su moisture	They	to su	fill have	ilg 1	sey de de de de de de de de de de de de de	Su fi	A OIL	t ge	Conves, IN		
Co reli	retisetor contra Oline shap, su moisture	They	to su	fill have	ilg 1	sex d	Je for	A OIL	t ge	SUPPLES, IN		
Co reli	retisetor contra Oline shap, su moisture	They	to su	fill have	ilg 1	sex d	July July July July July July July July	A OIL	t ge	thing tests  Since S, IN		
Co sell esay	retisetor contra Oline shap, su moisture	They	to su	fill have	ilg 1	sey d	Se f	೨೯ ಇ೦.	A DEC	Conves, IN		
Co reli	retisetor contra Oline shap, su moisture	They	to su	fill have	ilg 1	sey d	Se f		A DEC	thing tests  Comoss, IN  ENVED		
Co sell esay	retisetor contra Oline shap, su moisture	They	to su	fill have	ilg 1	sey d	Se f	೨೯ ಇ೦.	A DEC	Conves, IN		
Co reli	retisetor contra Oline shap, su moisture	They	to su	fill have	ilg 1	sey d	Se f	೨೯ ಇ೦.	A DEC	Strues, IN		
Co reli	retisetor contra Oline shap, su moisture	They	to su	fill have	ilg 1	sey &	Se f	೨೯ ಇ೦.	A DEC	Conoes, IN		
Co reli	retisetor contra Oline shap, su moisture	They	to su	fill have	ilg 1	sey &	Se f	೨೯ ಇ೦.	A DEC	Conves, IN		
Co reli	retiretor centere deing shop, see moesture e 8k.	They for	to and	fill have	de so	sey d	Se f	೨೯ ಇ೦.	A DEC	CONTINUED C		

JOB NO. or P O NO.	
90553	
PAGE	

										/ OF /
ROJECT N	AME	CLIENT OR OV	MNER				1 /1			EQUENCE NO.
P.6 E	E YALD OCATION OF WORK	44.5.5	VOYT	ECH -	Aque	Resource	ces	higher W.	·	DAY OF WEEK
ENERAL L	OCATION OF WORK	OWNERORC	LENTSR	EPRESENTAT	DATE		DAY OF WEEK			
DAK	CLAND	A	Llow	,	1/26/91 Tue					
ENERAL C	CONTRACTOR	GRADING COM	VITRACTO	NR .	PROJECT	ENGINEER				
			ST	mco						
YPE OF W	ORK	GRADING CON	NTRACTO	SUPERVIS	OR					
TS	10		<u> </u>							
OURCE AN	7 0 ND.DESCRIPTION OF FILL MATERIAL	(MPORT OR SITE) WEATHER						TECHNICIAN		
						AIR		B. C	LECTOR	<u></u>
ESCRIBE	EQUIPMENT USED FOR HAULING, SPF	READING, WATERI	NG, CON	DITIONING, AI	ND COMPACT	ING				
	T	<del></del>		_						
TEST	TEST LOCATION		ELEV	DRY	HELD TESTING	G % OF	COMP	FERENCE CU MAXIMUM		COMMENTS
WUMBER	1201 2001/101		(feet)	DENSITY lbs /cu. ft.		MAXIMUM DRY DENSITY		DRY DENSITY tos /cu, ft.	MOISURE CONTENT	OOMAZHIO
77				-		,				·
13	50135 W0+20			1309	1	97		1345	6.4	
14	S0+15 W0+25	<del></del>	4	128.7		96	3			
·5	50+50 W 07 10	-	- 3	125.0		93	3			<u> </u>
16	RT#15			132.0	6.0	98	3			0K
					<del> </del> -					
				<del> </del>	<del> </del>				<u> </u>	
					<del> </del>					
					-			·		
					<del> </del>					
				•			1	i .	1 1	
					<del> </del>			<u> </u>		
							-			
,	Describe work completed during the day, a	•		•						
•	, , ,	•		•	10 A	eaby.	J a	ela .	es/close tims	n T
•	, , ,	•		•	ell a	n tin	I a	ua .	u/clos tims	n T
•	rescribe work completed during the day, a continue tractor continue clad S.B. In	•		•	1 d	eaber ten	J a	la pere	u/close tiens	n.
•	, , ,	•		•		eaby.	Ja	ela .	u/clos tims	n
•	, , ,	•		•	11 c	eabez.	J a	ea opera	es close tims	en.
•	, , ,	•		•	1 . A	n ten	J a	yere	uf close tims	er.
•	, , ,	•		•		n ten	J a	yere	w/class	o T
•	, , ,	•		•		eaber ten	J a	la pere	u/close tions	n
•	, , ,	•		•		eabez.	Ja	ela .	u/clos tims	n T
•	, , ,	•		•		n ten	J a	ela .	uf class tions	n.
•	, , ,	•		•		n tin	J a	yene	u/close tims	en.
•	, , ,	•		•		eaber ten	Ja a	yere	w/close tins	n.
•	, , ,	•		•		eabez ten	J a	ua pere	u/close tiens	n
•	, , ,	•		•		n ten	J a	la pere	w/close tims	n
•	, , ,	•		•		eabez.	J a	ela	u/clos tims	n .
•	, , ,	•		•		eaby.	Ja a	ela .	u/clos tims	n.
,	, , ,	•		•		eaber tin	Ja a	ea pere	w/class	en .
•	, , ,	•		•		eaber ten	Ja a	yen	u/clad	n.
•	, , ,	•		•		eaber ten	Ja a	la pere	tions.	n.
,	, , ,	•		•		eaber ten	J de	ela opera	tions.	
Nos	ntacta contin	to ok		•		eaby.	J a	la pere	tions.	
•	ntacta contin	•		•		eaby.	Ja a	ela .	u/clos tims	CONTINUES

JOB NO. or P O NO.
9055 3
PAGE

OJECT N											
		CLIENT OR	OWNER	DAILY FIEL	Y FIELD REPORT SEQUENCE NO.						
3.6.8	BAKO	1/2	YTECH	· - /4	DATE	7					
NERAL LO	OCATION OF WORK	OWNER OR CLIENT'S REPRESENTATIVE  ACRON							<i>i</i> .	DAY OF WEEK	
	CARDO	ļ.			12/2/		Mo				
NERAL CO	ONTRACTOR	GRADING (	CONTRACTO	A	PROJECT	ENGINEER					
		STEME O GRADING CONTRACTOR'S SUPERINTENDENT OR FOREMAN									
PE OF WO	DRIK	GRADING (	CONTRACTO	SUPERVIS	OR	•					
TI	0	<u> </u>									
JURCE AN	ID.DESCRIPTION OF FILL MATERIAL	(MP	ORT OR SITI	E)	t	EATHER		TECHNICIA	N LEETON		
	FOR HENCE LOCK CORTINUE BYC. COR	READING, WATERING, CONDITIONING, AND CO				EMR		10, C	-CECTON	<u> </u>	
ESCHIBE E	ie 1/20 truck pa	e to	Dicar	a 86 -	La-e	117.3					
7000	C. 1+20 DOCK 1-0				ELD TESTIN		DE1	FERENCE CU	OVE	<del></del>	
TEST	TEST LOCATION		ELEV		MOISTURE		COMP	MAXIMUM		COMMENTS	
UNBER			(feet)	DENSITY lbs /cu. ft.	CONTENT	MAXIMUM DRY	CURVE NO.	DRY DENSITY	CONTENT		
				ICS /CU. IC.	<b>79</b>	DENSITY	140.	lbs/cu. it.	%		
7.	C - 1.35		-Z	122.8	<u> </u>	91	3	134.5	6.7	E	
7	S0175 W 0 +15			22.8	<del></del>	91		704	-	E	
8	50+20 W0+20		-3	124.6	6.5	93	<u>3</u> उ		<del>                                     </del>	6	
	RT#17					90	3			Ø OK oK	
	RT# 18	-		128.3	7.6	95	3				
	R1 * 19					95	3				
7	87 4 70 50+57 WO+2	<del>,</del>				95	3				
3	SOIST WOLL	· l	- 2	164-6	F-" F	79	<u> </u>	<del> </del>			
	1		<u> </u>	<u> </u>				<del>                                     </del>			
					<del> </del>			<del> </del>			
			<u> </u>	ļ	<b></b>			<u> </u>	1	<del></del>	
								ļ			
			<u></u>	1	<u></u>		L	<u> </u>		L	
	escribe work completed during the day, a										
					su b	bex'd	su actor	a D	we do	Jan Joseph	
					l su b	bej d Costi ntiel	see actor	a d)	we do	Leng Greatly	
	n tractor contension of class to make the contension of class to make the market of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section of the section				B.	bej d Costi ntiel	su actor	a d)	we di	Jan Jaculty	
					su bi	bej d Conti ntiel	see actor	a D	weding di	Localty	
					B:	bes d Control	su acta	a d)	we dig di	Jan Jaculty	
					su b:	bes d Conti- ntial	see actor	a D	we dig	Jaculty	
					B.	Costs Costs ntiel	actor.	a s)	we die	Jane Jacuty	
					Bi e ro	bej d Conti ntial	gue actor	a s)	ing St	Live ty	
					B:	bes d Conti- ntial	su actor	a d)	we dig	Jan Jaculty	
					Bi	bes d Control	acta	a D	we dig di	Jaculty	
					B.	bes d Costs ntial					
					se re						
					B.				URCE:		
					B.		\QUA	RESO REUE	URCE:		
					Bi po		\QUA	RESO REUE			
					B.		\QUA	RESO REUE	URCE:		
					B.		\QUA	RESO REUE	URCE:		
					B.	, , , , , , , , , , , , , , , , , , ,	AQUA E	RESO REUE	URCE:		
					B. co	, , , , , , , , , , , , , , , , , , ,	\QUA	RESO REUE	URCE:		
					B. co	, , , , , , , , , , , , , , , , , , ,	AQUA E	RESO REUE	URCE:		
					B. co	, , , , , , , , , , , , , , , , , , ,	AQUA E	RESO REUE	URCE:		
	nteactor contenies  w/ close to  mpaction due to  tourn; Some	se pon	toe			, , , , , , , , , , , , , , , , , , ,	AQUA E	RESO REUE	URCE:		

JOB NO. of P O NO. 90553 PAGE

6

	IAME		CLIENT OR OWNER		DAILY FIELD REPORT SEQUENCE NO.					
26.8	E. YARD	. <u> </u>	Agu.	n RESON	i segal					
ÉNERAL L	OCATION OF WORK		OWNER OR CLIENT	S REPRESENTAT	TVE	<del></del>	1 25.	DATE /		DAY OF WEEK
OAI	RLAND		GRADING CONTRAC	AARON	12/5/		TH.			
	CONTRACTOR		GRADING CONTRAC	TOA	PROJECT ENGINEER					
				STRUM O						
YPE OF WO			GRADING CONTRAC	TOR'S SUPERIN		SUPERVISI	OR-			
	10									
OURCE AN	ND DESCRIPTION OF	FILL MATERIAL	(IMPORT OR	SITE)	,	EATHER		TECHNICIA	IN LEETON	1
			The state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the s	A CHARLES		AVR		B. C.	LEETON	
ESCRIBE :	EQUIPMENT USED IN	OR HAULING, arms	EADING, WATERING, O	ONUI HORING, A.	ND COmmon.	ING.				
	<del>,</del>				FIELD TESTIN		RE	FERENCE CUI	₽VE	
TEST	TE	EST LOCATION	ELEN	DRY	MOISTURE	% OF	COMP	MAXIMUM	OPTIMUM	COMMENTS
NUMBER		All books	(feet)				CURVE NO.	DRY DENSITY Ibs/cu. ft.	MOISURE	
24	50+42	05+0 w	-12			37	3	1345	6.7	
<del>25</del>	50+94	WOTZI	-1	127.8	9.9	95	3			
26	50+15	W 0+54	3 5			91	3	<u> </u>	<b></b>	ole.
27	\$ 1400	W0+15	05	128,6		95	3	<u> </u>	ļ	
28	50+50	WU+10	-/	127.6		95	3	<u> </u>		
29		WOTED	<u>-3</u>	127.4	9.5	95	3	<del> </del>		
					<u> </u>		<b></b>	<del></del>	<del>                                     </del>	
		<u> </u>			<del> </del>	ļ		<u> </u>	<del> </del>	
					<u> </u>	<del> </del>		<b></b>		,
	<u> </u>				ľ	1			<u> </u>	
				<del></del>	+	+	<del></del>	+	Т.	1
		and devices the right are	arablams and their so	iding)						
•			ny problems and their sol							
•					'selfe	W.	nubl	il a	lea	w/cla
•					'adje	W.	rubl	- j'/ a	usa	w/cla
•			tours and their sol		'adje	Ul ,	subs	<i>ii</i> a	ua	w/cla
	Intractor A.B.	ta con Zerts	tening	+ + ok +						
	Intractor A.B.	ta con Zerts	tening	+ + ok +						
	S.B.	ta con Zerts left fl		+ + ok +						
	S.B.	ta con Zerts	tening	+ + ok +						
	S.B.	ta con Zerts left fl	tening	+ + ok +						
	S.B.	ta con Zerts left fl	tening	+ + ok +						
	S.B.	ta con Zerts left fl	tening	+ + ok +						
	S.B.	ta con Zerts left fl	tening	+ + ok +						
	S.B.	ta con Zerts left fl	tening	+ + ok +						
	S.B.	ta con Zerts left fl	tening	+ + ok +		enig ,	lest		vere	Ok.
	S.B.	ta con Zerts left fl	tening	+ + ok +		enig ,	lest		vere	Ok.
	S.B.	ta con Zerts left fl	tening	+ + ok +		enig ,	lest		vere	Ok.
	S.B.	ta con Zerts left fl	tening	+ + ok +		enig ,	Cest	ESOU'	ROES. VED	Ok.
	S.B.	ta con Zerts left fl	tening	+ + ok +		enig ,	Cest		ROES. VED	OK.
	S.B.	ta con Zerts left fl	tening	+ + ok +			Cest Cust	ESOU'	ROES. VED	OK.
	S.B.	ta con Zerts left fl	tening	+ + ok +			Cest	ESOU'	ROES. VED	Ok.
	S.B.	ta con Zerts left fl	tening	+ + ok +			Cest Cust	ESOU'	ROES. VED	OK.
	S.B.	ta con Zerts left fl	tening	+ + ok +			Cest Cust	ESOU'	ROES. VED	Ok.
	S.B.	ta con Zerts left fl	tening	+ + ok +			Cest Cust	ESOU'	ROES. VED	OK.
	Intractor S. B.	ta con Zerts left fl	tening	+ + ok +	16		Cest Cust	ESOU'	ROES. VED	OK.

#### JOB NO. of P O NO. DAILY FIELD REPORT CLIENT OR OWNER DAILY FIELD REPORT SEQUENCE NO. PROJECT NAME 9 OWNER OR CLIENT'S REPRESENTATIVE P.G. E. YDAD DAY OF WEEK GENERAL LOCATION OF WORK 12/6/91 ERI DAKLMID AARON PROJECT ENGINEER GRADING CONTRACTOR GENERAL CONTRACTOR STEMES GRADING CONTRACTOR'S SUPERINTENDENT OR FOREMAN TYPE OF WORK SUPERVISOR TIO (IMPORT OR SITE) WEATHER TECHNICIAN SOURCE AND DESCRIPTION OF FILL MATERIAL "CLEETON DESCRIBE EQUIPMENT USED FOR HAULING, SPREADING, WATERING, CONDITIONING, AND COMPACTING FIELD TESTING REFERENCE CURVE % OF MAXIMUM DRY COMP CURVE NO. MAXIMUM DRY DENSITY OPTIMUM MOISURE CONTENT COMMENTS TEST TEST LOCATION ELEV MOISTURE NUMBER DENSITY CONTENT lbs/cu.ft. DENSITY lbs /cu, ft. 6.7 30 5 1410 F.G 131.1 6.5 98 3 134.5 W O+25 127.2 95 3 6.5 31 -1 50+15 WO+60 123.1 92 ok 32 4.7 3 50+20 41+10 NOTES (Describe work completed during the day, any problems and their solutions)

AQUA RESOURCES, INC

DEC 1 1 1991

JOB NO._____

TIME BILLED 7 HRS., / NO. OF VISITS CONTINUED CONTINUED CONTINUED

CNT-1

·/.	AME	CLIENTORO		Ω =	· ·		ا ا			QUENCE NO.
<u>ع. د </u>	YAKO	OWNERORO	HQU	A KESO	ulces		The state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the s			DAY OF WEEK
	OCATION OF WORK					• • • • • • •	The second			_
	KLAND.	GRADING CO	HALO:	<i>y</i>		12/9/91 No.				
ERALC	CONTRACTOR	1				PHOJECTI	NUNCER			
		GRADING CO	<u>S7</u>	EMCO				A		
	ORK	GRADING CO	NTRACTO	RYS SUPERIN	TENDENT OR	FOREMAN		SUPERVIS	UR	
1	10	<u> </u>							-	
ARCE AN	ND DESCRIPTION OF FILL MATERIAL	(MPOF	IT OR SITE	E)	1	EATHER		TECHNICIA	M /	· Inti
		EADING, WATERING, CONDITIONING, AND COMPACTING						1/3×1·	~ LEE.	pr Oliv
CRIBE!	EQUIPMENT USED FOR HAULING, SPH	EADING, WATER	and, cont	ULI KUNNING, AT	SU COMPACI.	IIW.3				· ·
	· · · · · · · · · · · · · · · · · · ·	<del></del>	·	,	IFI D TECTOR			FERENCE CU	DUE .	
FEOT	TEST LOCATION		ELEV	DRY	MOISTURE		COMP	MAXIMUM	OPTIMUM	COMMENTS
Test Haber	IEST COMINM		(feet)	DENSITY	CONTENT	MAXIMUM	CURVE	DRY	MOISURE	
				lbs /cu. fl.	<b>%</b>	DENSITY	NO:	DENSITY tos /cu. ft.	CONTENT	
				<del>  </del>						
3	50+25 W1+05			133.1		99	3	1345	6.7	-
4	50+25 W0+75		<u>- 1/5                                   </u>	1308	سی سی	97			<u> </u>	
5	50+70 WO+9	75 -	1/2	130.0	51	97		ļ		
				<u> </u>						
				l						
				† · · · · ·						
				<del>                                     </del>	<del>                                     </del>	-		1		
				<del> </del>	<del>                                     </del>	<del> </del>	<del> </del>	+	<del>                                     </del>	
				<del> </del>	<del> </del>	<del> </del>	<b></b>	<del> </del>	-	
					<del> </del>	<del> </del>	<del></del>	+	<u> </u>	
	1	1		1	}	1				<u></u>
res (C	Describe work completed during the day, a	ny problems and if	heir solution	ns)						
					,	D 51		bed .	Z	st was
					M	D 57	au	bef.	Za	ot was
					, Lyl	9 57	_au	bef.	Za	ot was
					· lys	D 5)	_ <u>su</u>	bef.	<u> </u>	ne was
					. enc	9 0 0	_au	bef. looke	Za d g	od was
					, sens	9 0 0 150/1		bef.	Za d g	od was
	Describe work completed during the day, as steel light plant of course of didn't find				, enc	9 0 0	Is .	bef. looke	Za d g	ood
					. en	D 37	<u>su</u> L _s .	bef. lio ke	Jo	ood
					re	. g . s. v / i		bef. looke	Jo d g.	od was
					re	D 37		bef. looke		od was
					re	D 37		bef. looke		od o
					re	D 37	Ls .	bef. looke		od o
					- Cert	D 37	-su	bef.		od was
						D 57		bef.		od was
					re		JA RES	SOUR	CES. IN	
					re		JA RES		CES. IN	
					re		JA RE	SOUR	CES, IN	
					re		JA RE	SOUR	CES, IN	
					re	AQU	JA BE: RE	SOUR	CES, IN	
					re	AQU	JA RE: RE DEC	SOUR	CES, IN	
					re	AQU	JA RE: RE DEC	SOUR	CES, IN	
					re	AQU	JA RE: RE DEC	SOUR	CES, IN	
					re	AQU	JA RE: RE DEC	SOUR	CES, IN	`
					- Cent	AQU	JA RE: RE DEC	SOUR	CES, IN	

RECEIVED BY

#### JOB NO. or P O NO. DAILY FIELD REPORT DAILY FIELD REPORT SEQUENCE NO. CLIENT OR OWNER PROJECT NAME OWNER OR CLIENT'S REPRESENTATIVE P. G. E. Yaved GENERAL LOCATION OF WORK DATE DAY OF WEEK 12/10/91 TUE DAKLAND Anenl PROJECT ENGINEER GRADING CONTRACTOR GENERAL CONTRACTOR Stemes SUPERVISOR GRADING CONTRACTOR'S SUPERINTENDENT OR FOREMAN TYPE OF WORK TESTING (IMPORT OR SITE) WEATHER TECHNICIAN SOURCE AND DESCRIPTION OF FILL MATERIAL ( CLEEPUL DESCRIBE EQUIPMENT USED FOR HAULING, SPREADING, WATERING, CONDITIONING, AND COMPACTING FIELD TESTING REFERENCE CURVE OPTIMUM MOISURE CONTENT % OF MAXIMUM DRY COMP CURVE NO. COMMENTS MOISTURE MAXIMUM TEST LOCATION ELEV DRY TEST DAY DENSITY NUMBER (feet) DENSITY lbs/cu.ft. DENSITY los /cu. ft. 34 NO. OF VISITS CONTINUED TIME BILLED HRS.,

COPY GIVEN TO

5

RECEIVED BY

JOB NO. or P O NO. 90553 PAGE

PROJECT N	/ /	~ D	CLIENT OF		7-		DAILY FIELD REPORT SEQUENCE NO.				
GENERAL I	OCATION OF WORK	7.0	OWNERO	RCLIENT'S R	EPRESENTAT	IVE	<u>- C J </u>		DATE	<u>,</u>	DAY OF WEEK
	AKLAND			AAR					12-11	-91	WED
	ONTRACTOR		GRADING	CONTRACTO	R	PROJECT					
}			[	57	noico						
TYPE OF W	ORK	<del> </del>	GRADING	CONTRACTO	PANCO R'S SUPERIN	SUPERVIS	OR				
72	31		·								
	ID DESCRIPTION OF	FILL MATERIAL	(IMF	(MPORT OR SITE) WEATHER		,	TECHNICA	W,			
						بكر	INNY P	1160		NICHOL	- <i>ン</i>
DESCRIBE	EQUIPMENT USED FO	OR HAULING, SPRI	EADING, WAT	ERING, CON	ationing, an	ID COMPACT	i iNG				
						IELO TESTIN			FERENCE CU		
TEST NUMBER	TE	ST LOCATION		ELEV (feet)	DRY DENSITY lbs /cu. ft.	MOISTURE CONTENT %	% OF MAXIMUM DRY DENSITY	COMP CURVE NO.	MAXIMUM DRY DENSITY lbs/cu., ft.	OPTIMUM MOISURE CONTENT %	COMMENTS
36	5.0+20	درا ا	1+00	F.6,	129.1	5.7	96	3	134.5	6.7	
37	5-0+20			66.	132.8		99	14	14	,,	
									L		
							ļ				
<u>.</u>											
				ļ	ļ				ļ		
				<u> </u>	<b>_</b>	<del> </del>	<del> </del>		1		
				<del>                                     </del>		<del> </del>	<del>                                     </del>		<u> </u>	<del>  -  </del>	
				1	<u> </u>	<u> </u>		<u></u>	<del> </del>	-	
NOTES (D	Describe work complete	d during the day, an	ry problems an	d their solution	I /	λ		\	<del></del>		e Va
1.10	24 4	10 - I	<u> </u>	S t	0		<u> </u>	~~~~	. )e. ^	ALL	2222-1
to	SLE	un	unt	. /1	vid	P.M.	<u> </u>	<del>zwe</del> z	er.	73 (	Centon
ئد اس ا	-t	101	00 1	Q _n	4.14		Rot	Λ 44 . 6	0 7	. , ,	an d
+, 1	tod -1	. 0	9.	1 m al	· H	<del></del>	LA	H.	Q _c	<del>اد د.</del>	1
10	stine 1		·		×			1 40-62			0
<u> </u>									W.		
<u> </u>	<del>-</del>										
							··				
									•		
						•					
	···						,	AQUA		URCE	s, INC
									DEC 1	उ <del>1991</del>	
											· · · · · · · · · · · · · · · · · · ·
						(	F	ILE			
TIME BILL	ED 4	HRS.,		1	NO. OF VISITS	2					CONTINUED .
RECEIVED	BY					COPY	GIVEN TO				



AQUA RESOURCES, INC RECEIVED

NOV 2:0 1991

JOBNO. 90262.2 FILE reports

NOVEMBER 19, 1991

VOYTEK BAYSAROWICZ AQUA RESOURCES 2030 ADDISON STREET, SUITE 500 BERKELEY, CALIFORNIA 94704

RE: ARI JOB# 90262.2-OAKLAND PG&E PROPERTY

DEAR VOYTEK,

PURSUANT TO YOUR REQUEST OUR OFFICE HAS CONDUCTED A PRELIMINARY BOUNDARY SITE ASSESSMENT FOR THE SUBJECT PROPERTY FRONTING COLISEUM WAY IN OAKLAND, CALIFORNIA. OUR SCOPE OF SERVICES WAS LIMITED TO EVALUATING THE POSITION OF THE EXISTING FENCE LINE RELATIVE TO THE ASSESSOR PARCEL MAP LINE. TIMING CONSTRAINTS BEYOND OUR CONTROL OUR PRELIMINARY EVALUATION RELIED UPON ASSESSOR PARCEL MAPS AND OTHER RECORD INFORMATION THAT WAS OBTAINABLE FROM THE ALAMEDA COUNTY RECORDS DEPARTMENT AND A THREE HOUR ONE MAN SITE VISIT. NO PRELIMINARY TITLE REPORT WAS PROVIDED BY YOUR OFFICE. BASED UPON THIS LIMITED AMOUNT OF BACKGROUND RESEARCH AND FIELD RECON IT IS THIS OFFICES CONCLUSION THAT THE EXISTING FENCE LINE IS APPROXIMATELY 1' INSIDE THE "ANTICIPATED" PROPERTY LINE. THE TOLERANCE OF OUR SURVEY IS APPROXIMATELY 0.5'. IT IS OUR UNDERSTANDING THAT THIS TOLERANCE LEVEL IS ACCEPTABLE TO YOUR OFFICE. IF A MORE RESTRICTIVE TOLERANCE IS REQUIRED ADDITIONAL FIELD WORK AND RELATED EXPENSES WILL BE REQUIRED.

I TRUST THAT THIS PROVIDES YOU WITH THE INFORMATION THAT YOU REQUIRE.

YOURS TRULY

MICHAEL E. MILANI GENERAL MANAGER

TETRAD ENGINEERING, INC.

1500 12-31-95 01030000

# SETTLEMENT MONITORING 4930 COLISCUM WAY, OAKLAND Panels on Building

# ELEVATIONS (Assumed Datum)


-	11 10 01 / / / / / / / /	
PANEL	11-19-91 1/19/9/1/09/92	
1	<del>103,73</del> 103,73 103,73	
2	103.73 103.73 103.73	
3	103.73 103.74 103.74	
• 4	103,73 103,74 103,74	_
5	103.73 103.75 103.75	·
6	103.73 103.75 103.75	

## APPARENT MOVEMENT

PANEL	11-19-91	11-19-914	1/09/92				
- 1	W.A.	N.A.	<b>\$</b>		·		
2		и	<b>•</b>				
3		18	<b>→</b>				
4	ـــناــــ	и	-			·	
5		29	-0				
. 6	-#	4	-0-				

A Level Not in Adjustment on 11/19/91, 50 this column gives adjusted elevs

Job 287





#### ALAMEDA COUNTY FLOOD CONTROL AND WATER CONSERVATION DISTRICT

5997 PARKSIDE DRIVE

PLEASANTON, CALIFORNIA 94588

(510) 484-2600

25 October 1991

AQUA RESGURCES, ING RECEIVED

OCT 2 8 1991

Aqua Resources, Inc. 2030 Addison Street, Ste. 500 Berkeley, CA 94704 JOENO. 90262.1 FILE permits

#### Gentlemen:

Enclosed is Drilling permit 91619 for the destruction of well 2S/3W 17B80 at 4930 Coliseum Way in Oakland for Pacific Gas and Electric Company.

Please note that permit condition A-2 requires that a well destruction report be submitted after completion of the work. The report should include a description of methods and materials used to destroy the well, location sketch, date of destruction, and permit number.

If you have any questions, please contact Craig Mayfield or me at 484-2600.

Very truly yours,

Wyman Hong

Water Resources Technician

WH:mm Enc.



### ALAMEDA COUNTY FLOOD CONTROL AND WATER CONSERVATION DISTRICT

5997 PARKSIDE DRIVE

PLEASANTON, CALIFORNIA 94566

(415) 484-2600

#### GROUNDWATER PROTECTION ORDINANCE PERMIT APPLICATION

FOR APPLICANT TO COMPLETE		FOR OFFICE USE
LOCATION OF PROJECT 4930 Coliseum Way,	PERMIT NUMBER	91619
Oakland, CA	LOCATION NUMBER	
CLIENT Name PG&E		PERMIT CONDITIONS
Address 4930 Coliseum Way Phone 973-5615		1 FIGHT GOND HI JOHD
City Oakland Zip	Circ	cled Permit Requirements Apply
APPL ICANT		
Name Aqua Resources Inc. (Mr. Voytek Bajsarowi	CEA. GENERAL	
The Earth Technology Corp.	•	application should be submitted so as to
Address 2030 Addison, #500 Phone 540-6954		the Zone 7 office five days prior t
City Berkeley, CA Zip 94704		starting date.
- DESAN INVIAL OF THE ISSUE		Zone 7 within 60 days after completio
DESCRIPTION OF PROJECT	•	tted work the original Department o
Water Well Construction Geotechnical Investigation Cathodic Protection General		wources Water Well Drillers Report of t for well projects, or drilling log
	•	ion sketch for geotechnical projects.
Well Destruction X Contemination		vold if project not begun within 9
PROPOSED WATER WELL USE	days of a	pproval date.
Domestic Industrial Irrigation	B. WATER WELLS,	INCLUDING PIEZOMETERS
Municipal Honitoring Other		surface seal thickness is two inches o out placed by tremie.
PROPOSED CONSTRUCTION	2. Minimum s	eal depth is 50 feet for municipal an
Drilling Method:	Industria	I wells or 20 feet for domestic, irriga
Mud Rotary Air Rotary Auger _X_	flon, and	monitoring wells unless a lesser dept
Cable Other		Ity approved.
<b>.</b>		Backfill bore hole with compacted cut
DRILLER'S LICENSE NO. C 604 987		y bentonite and upper two feet with com
		lal. In areas of known or suspecte
WELL PROJECTS		, tremled cement grout shall be used I
Drill Hole Diameter in. Maximum	·	acted cuttings.
Casing Diameter 2 in. Depth 20ft.		Il hole above anode zone with concret
Surface Seal Depth ft. Number	placed by tree	
CENTECHNICAL BOOLECTS	E. HELL DESTRUCT	ION. See attached.
GEOTECHNICAL PROJECTS  Number of Borings Haximum		
Hole Diameter In. Depth ft.		
tit: bobiti		
ESTIMATED STARTING DATE 10/31/91		
ESTIMATED COMPLETION DATE 10/31/91		•
	,11	11
I hereby agree to comply with all requirements of this	Approved Will	man Nona Date 24 Oct 91
permit and Alameda County Ordinance No. 73-68.		lyman Hong
	V W	, y man 110 ng
APPLICANT'S \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \		$\mathbf{c}$

# ZONE 7 WATER RESOURCES ENGINEERING DRILLING ORDINANCE

PACIFIC GAS AND ELECTRIC
4930 COLISEUM WAY
OAKLAND
WELLS 2S/3W 17B80
PERMIT 91619

#### Destruction Requirements

- 1 Drill out the well so that the inner casing, seal, and gravel pack are removed to the bottom of the well.
- 2. Using a tremie pipe, fill the hole to 2 feet below the lower of finished grade or original ground with neat cement.
- 3. After seal has set, backfill the remaining hole with compacted material.

These destruction requirements as proposed by Voytek Bajsarowicz of Aqua Resources meet or exceed the Zone 7 minimum requirements.



# AND AQUA RESOURCES, INC.


## OBSERVATION WELL INSTALLATION REPORT

•	DOLE				. Woll ≠	
olect	PG&E			4601		•
cation	4930 Colls	eum Wav, Oal	ur <u>(Land</u>	W Drilling	· · · · · · · · · · · · · · · · · · ·	
pe of file	CME 55	Instal	lod by	M DITTILL	4/16/91	
le Started	7, 1					
pe of Observ	ation Well	water	Ground E	nv	Cnallin T	op, Elov:
L1	7, 1		Ground E	Type of  Type of  bence	cking cap and Chaling2  Tackillics	.020 inch
•*• '				— Diamata	r of Boring	8 inches
		,	•			
Hernorks						<del></del>
			<u>·                                      </u>			

Observed by .----

AQUA FIL	<u> </u>	いしにら、	1110.		LOCATION JOS NAME POSE JUGO NO. 2
(M)	BORING	LOG			Oakland
alto.					UNICLING COMPANY Exceltech/Resna BORING NO. OW-6
LOCATION & NO	TES				DRILLEN'S NAME DON JEHRHIS  LI Solid Flight August BIEET, 2
_	•				
					SAMPLEN TYPE: A 2.6" TO SPIN BANKE TO SO IN START FINISH
					TIME AM 8.5/AM
					11ME 12/19/91 DATE
					12/19/91
NUTUM: [] Me	isii Sea Lovil	[X] Other	• OW-2		ELEVATION 3.37 FEET FIELD ENGINEER MARK Peterson
		<b>-</b>			Graded surface of agregate to base rock, nearly
SLOWS PER HALF FOOT	BLCMS/III.	osy unit weight (sell	DEPTH IN	USCS CLASSIFI- CATION	Graded surface of agregate to base fock, and level - Since installation of well the surface
84	G S	7 HD 19 W 19 (a)	DE7	মুনুর	has been paved with AC.
육구				_	
<b></b>			0 -	-[]	
		_		.	
			.	-	
		-	1 -	-	
	_	_	-	-	
				-	
<b>■</b>			2 -	_	
		_}			
_			}.	-	
<b>■</b> {		_	a -	-	
<b>-</b>			] . <u> </u>	_	
				_	
		_	4 -	-	
				-	
<b>■</b>   <del>                                 </del>			-	_	
		_	5 _	_	
				-	
<del> </del>	<del></del>	_  <del></del>	1 -		
			6	_]	
		_	-	-	•
-				-	
<b>.</b>			7 -	_	
			.  _	-	
				-	
	<del> </del>	-	В		Water on top end of sampler with slight sheen
16   '	<u> </u>			GC	Gravel with interstitial silty clay, olive brown (2.5Y 4/3), saturated. Gravel backfill that penetra-
18				ΗЗ	ted saturated native soil.
	<del> </del>	_	g -		
20	38				Gravelly sand, brown (10YR 4/3), saturated, medium
			] [	-	dence fine to coarse grained said, poolly solice,
			. 10 _	- SP	subangular gravel up to 3/4" across.
				-	

$\sqrt{C}$	AUV I	ESC	DUFI	CES,	ING.		
- M	)	n io n	n M G	LOG			LOCATION JOB NAME PG&E 90262.2
A(6	<i>)</i> .	50.					DHILLING COMPANY Exceltech/Resna Boning NO.
LOCA	TION & NOIT	STES					OMILEN'S NAME DON JENKINS OW-O
		•					Z OF Z
							SAMPLER TYPE: 1   2,5"   D Spitt Darrel   1 2.0"   D Shalby Tube     SPT
							DRIVE WEIGHT LB. CALL
R							PM I'M
							DATE 12/19/91
							CASING DEFIN (FEET)  ELEVATION FEET FIELD ENGINEER MARK PETERSON
ואט	UMI [] M	n.311 34n		[ ] Othe	·	<del>- </del>	
<b>5</b>	SLOWS PER HALF FOOT	ďñ.	MOISTURE CONTENT %	DRY UNIT WEIGHT (pell	NI ETER	טאט . באאר בי האסהדאט מסהדאט	SUMFACE CONDITIONS.
	885 2	eudwarfi.		۲۲ ر آوان آودا	F. 6.	25.54	, ,
	3L( HA	<u> </u>	₹8	ō*	ă	750	
				·	<u> </u>	-	
<b>.</b>			<u></u>		10 -		
20		[				-	
<b>-</b>	<u>'                                     </u>				-	]	
20		<b> </b>		<u> </u>	11	<b>-</b>	
15		35				-	
						_]	
		<del></del>		]	12	-	
					}	-	
-	i				- -		
	<u></u>				13	]	
						-	
_			<u> </u>		-	-	
						-	
•	!	<del> </del>			14	- GM	Increased gravel at 14' to 15'
13							
9						-	
-		<b></b>	<del> </del>		15 _	-	Silty clay with minor very fine grained sand, light
6		15				-	yellowish brown (2.3Y5/3), wet, medium still to still,
	<del></del>				1 1	CL/	
					16 -	CH	
		]		] ' [		-	
<b> </b>	<u> </u>	-			-  -	-	
					17 -	]	
	-				"	_	
2		<u> </u>	<u> </u>		<u> </u>	-	
7	. ]				18	_	
	SPT					_	
4	7	<b> </b>	<del> </del>	<b> </b>	•-	-	Bottom at $18\frac{1}{2}$
						-	ם מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מינים מיני
<b>!</b>	<u> </u>	·	<del> </del>		19 -	-	
		<u>                                     </u>	<u> </u>	<u> </u>	_[		
					] .	-	
<b> </b>	<u> </u>	·	·		20 _	-	
						-	
	, ,					_!!	. I



### OBSERVATION WELL INSTALLATION REPORT

•	Walt # OW-6
Project PG&E	Weli ≠
4020 Colingum May Oakland CA 0/60	01
Type of Rig Mobile B61 Installed by F	
Date Started 12/19/91 D	ate Finished 12/19/91
	d Elev Casing Top, Elev
	•
•	
L22	
<del>- 1</del>	cap locking cap and sealed well cover
T-11971 L5	2" PVC
	Type of Casing
L1 18 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Type of Backfill cement grout
L2 ½ foot	
L3 7½ feet L7	
L4 10 feet	— Type of Seal Material bentonite pellets
½ foot	
L6 5 feet	
1 foot	
17 100c 4 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	0.020
L8 12½ feet	Size of Openings 0.020
L4	2/12
	Type of Filter Material 2/12 sand
	,
	Dlameter of Boring 8 inches
. 1 1	
•	
Remarks	

M. Peterson/A. Stessman

Observed by

BORING LOG  Oakland PG&E 90262.2  DRILLING COMPANY Exceltech/Resna DON Jenkins OW-7  ORILLING NAME DON JENKINS OW-7  ORILLING (I Solid Flight August 1 Protary Wish 1 OF 2  SAMPLER TYPE: M 2.5" ID Split Darrel [1 20" 10 Straity Tube [1 5rt]  SAMPLER TYPE: M 2.5" ID Split Darrel [1 20" 10 Straity Tube [1 5rt]	ΛΟυΛ Π	ESC	ווטכ	CES,	ING.		ties un
DUNI-LINE COMPANY   Row   Second   Gravel   Back   Second   Gravel   Gravel   Back   Gravel   Gra	<u></u>						LOCATION JOB NAME JOB NO 90262.2
OATUM 1   Many tentered	AND.	1100	iii G	LUG			DRILLING COMPANY Exceltech/Resna BORING NO.
SATURN	LOCATION & NO	ores					1 0111 C C C C C C C C C C C C C C C C C
SATURN		•					OF 2
SATURN 1) Mean Set Laved (80 out of OW-2)    Total   T	]						SAMPLEN TYPE: A 2.5" 10 Split Barrel ( ) 2.5" 10 Shally Tube ( ) 5.
DATUM I   Mages See Lord   \$\tilde{\mathbb{R}} \tilde{\mathbb{Omes}} \tilde{\mathbb{OMEs}} \tilde{\mathbb{OMEs}} \tilde{\mathbb{OMEs}} \tilde{\mathbb{OMEs}} \tilde{\mathbb{N}} \							
DATUM							10:00am 9:55rm 1M
SATURN I   Mean See Lord   \$\text{N}  of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the							DATE 12/19/91 12/10/01
A. Stessman  Graded surface of aggregate to base rock, nearly level - since well installation the surface has been payed with AC.  NOTE: No OVM = OVM reading of 0.0  NOTE: No OVM = OVM reading of 0.0  Cravel backfill material  Cravel backfill material  Cravelly sand with minor silt and clay, greyish green (564/2), medium dense, wet, fine to coarse grained coarse grained coarse grained coarse grained coarse payed. Note tarry						_	CASING DEPTH (FEET)
Surface consistency of aggregate to base rock, nearly level - since well installation the surface has been paved with AC.  NOTE: No OVM = OVM reading of 0.0  NOTE: No OVM = OVM reading of 0.0  Cravel backfill material  20  Cravel backfill material  23  Cravelly sand with minor silt and clay, greyish green (564/2), medium dense, wet, fine to coarse grained (564/2), medium dense, wet, fine to coarse grained (564/2), medium dense, wet, fine to coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grai	DATUMI I I M	nan 544	Loval	XI Oins	· OW-	$\frac{2}{1}$	
NOTE: No OVM = OVM reading of 0.0  NOTE: No OVM = OVM reading of 0.0  NOTE: No OVM = OVM reading of 0.0  Cravel backfill material  SEP/ SC Gravelly sand with minor silt and clay, greyish green (5G4/2), medium dense, wet, fine to coarse grained (5G4/2), medium dense, wet, fine to coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grai	of the	يز	w st	<u>+</u>	<u>z</u> .	1 1 2	- andrewate
NOTE: No OVM = OVM reading of 0.0  NOTE: No OVM = OVM reading of 0.0  NOTE: No OVM = OVM reading of 0.0  Cravel backfill material  SEP/ SC Gravelly sand with minor silt and clay, greyish green (5G4/2), medium dense, wet, fine to coarse grained (5G4/2), medium dense, wet, fine to coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grai	5 S	125	Ž,	555	렚곀	22.25	Graded surface of aggregate to base rock, nearly
NOTE: No OVM = OVM reading of 0.0  NOTE: No OVM = OVM reading of 0.0  NOTE: No OVM = OVM reading of 0.0  Cravel backfill material  SEP/ SC Gravelly sand with minor silt and clay, greyish green (5G4/2), medium dense, wet, fine to coarse grained (5G4/2), medium dense, wet, fine to coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grained coarse grai	\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \	ירם	25. 21.50	문학교	υ. 	332	level - since well installation the surface has
Gravel backfill material  20  Gravelly sand with minor silt and clay, greyish green (504/2), medium dense, wet, filme to coarse grained subangular gravel. Note tarry	8元		ن جـ		<del></del> -,		been paved with AC.
Gravel backfill material  20  Gravelly sand with minor silt and clay, greyish green (504/2), medium dense, wet, filme to coarse grained subangular gravel. Note tarry		!					NOWE No OWN - OWN roading of 0 0
Gravel backfill material  SP/ Gravelly sand with minor silt and clay, greyish green (564/2), medium dense, wet, fine to coarse grained and coard, properly sorted, submapular gravel. Note tarry		<u> </u>		<del></del>	• -		MOIE: MO OAL - OAL LEAGING OF O.O.
Gravel backfill material  SP/ Gravelly sand with minor silt and clay, greyish green (564/2), medium dense, wet, fine to coarse grained and coard, properly sorted, submapular gravel. Note tarry						-	
Gravel backfill material  SP/ Gravelly sand with minor silt and clay, greyish green (564/2), medium dense, wet, fine to coarse grained and coard, properly sorted, submapular gravel. Note tarry						-	
Gravel backfill material  SP/ SC (504/2), medium dense, wet, fine to coarse grained cared poorly sorted, supangular gravel. Note tarry					1	-	
Gravel backfill material  SP/ SC (504/2), medium dense, wet, fine to coarse grained cared poorly sorted, supangular gravel. Note tarry			}			~	
Gravel backfill material  SP/ SC (504/2), medium dense, wet, fine to coarse grained cared poorly sorted, supangular gravel. Note tarry	1-1-				1		
Gravel backfill material  SP/ SC (504/2), medium dense, wet, fine to coarse grained cared poorly sorted, supangular gravel. Note tarry					2		
Gravel backfill material  SP/ SC Gravelly sand with minor silt and clay, greyish green (564/2), medium dense, wet, fine to coarse grained and propriy sorted, subangular gravel. Note tarry				:	-		
Gravel backfill material  SP/ SC Gravelly sand with minor silt and clay, greyish green (564/2), medium dense, wet, fine to coarse grained and propriy sorted, subangular gravel. Note tarry	1 1						
Gravel backfill material  SP/ SC Gravelly sand with minor silt and clay, greyish green (564/2), medium dense, wet, fine to coarse grained and propriy sorted, subangular gravel. Note tarry		İ			ļ	-	
Gravel backfill material  20  SP/ SC (564/2), medium dense, wet, fine to coarse grained cand proprly sorted, subangular gravel. Note tarry	<del>  </del>		·		3 -		
Gravel backfill material  20  SP/ SC (564/2), medium dense, wet, fine to coarse grained cand proprly sorted, subangular gravel. Note tarry						-	
Gravel backfill material  20  SP/ SC (564/2), medium dense, wet, fine to coarse grained cand proprly sorted, subangular gravel. Note tarry					-		
Gravel backfill material  20  SP/ SC (564/2), medium dense, wet, fine to coarse grained cand proprly sorted, subangular gravel. Note tarry							
Gravel backfill material  SP/ Gravelly sand with minor silt and clay, greyish green (5G4/2), medium dense, wet, fine to coarse grained cand poorly sorted, subangular gravel. Note tarry			}		,		
Gravel backfill material  SP/ Gravelly sand with minor silt and clay, greyish green (5G4/2), medium dense, wet, fine to coarse grained cand poorly sorted, subangular gravel. Note tarry	-  -	-	<u> </u>	<b></b> _	-		
Gravel backfill material  SP/ Gravelly sand with minor silt and clay, greyish green (5G4/2), medium dense, wet, fine to coarse grained cand poorly sorted, subangular gravel. Note tarry						-	
Gravel backfill material  SP/ Gravelly sand with minor silt and clay, greyish green (5G4/2), medium dense, wet, fine to coarse grained cand poorly sorted, subangular gravel. Note tarry		}			5 -	-{	
Gravel backfill material  SP/ Gravelly sand with minor silt and clay, greyish green (5G4/2), medium dense, wet, fine to coarse grained cand poorly sorted, subangular gravel. Note tarry						-	
Gravel backfill material  SP/ Gravelly sand with minor silt and clay, greyish green (5G4/2), medium dense, wet, fine to coarse grained cand poorly sorted, subangular gravel. Note tarry	<del>  </del>					_}	
Gravel backfill material  SP/ Gravelly sand with minor silt and clay, greyish green (5G4/2), medium dense, wet, fine to coarse grained cand poorly sorted, subangular gravel. Note tarry					8 -		
Gravel backfill material  SP/ Gravelly sand with minor silt and clay, greyish green (5G4/2), medium dense, wet, fine to coarse grained cand poorly sorted, subangular gravel. Note tarry				'			
Gravel backfill material  SP/ Gravelly sand with minor silt and clay, greyish green (5G4/2), medium dense, wet, fine to coarse grained cand poorly sorted, subangular gravel. Note tarry				]	•	-	
Gravel backfill material  SP/ Gravelly sand with minor silt and clay, greyish green (5G4/2), medium dense, wet, fine to coarse grained cand poorly sorted, subangular gravel. Note tarry						-	
Gravel backfill material    12	1-1-			· ·	7 -	[]	
Gravel backfill material    12				ļ			:
Gravel backfill material    12						<u> </u>	
12   SP/ Gravelly sand with minor silt and clay, greyish green   SC (5G4/2), medium dense, wet, fine to coarse grained   sand poorly sorted, subangular gravel. Note tarry		ļ	<del> </del>		. 8 _	-	
12   SP/ Gravelly sand with minor silt and clay, greyish green (5G4/2), medium dense, wet, fine to coarse grained cand poorly sorted, subangular gravel. Note tarry	20					-1	Gravel backfill material
SP/ Gravelly sand with minor silt and clay, greyish green (5G4/2), medium dense, wet, fine to coarse grained cand poorly sorted, subangular gravel. Note tarry	1 1		<del></del> -		•	[-]	
11 23 SP/ Gravelly sand with minor silt and clay, greyish green (5G4/2), medium dense, wet, fine to coarse grained coard poorly sorted, subangular gravel. Note tarry	12						
11   23   - SC (5G4/2), medium dense, wet, fine to coarse grained	l i i				8 -	SP/	Gravelly sand with minor silt and clay, greyish green
	11	23			_		/ (EC//2) modium dense, wet, fine to coarse grained
product visible. No OVM, slight hydrocarbon odor.		1				-	l cond poorly sorted, subangular gravel. Note tarry
		.		<b></b>	10 _	-	product visible. No OVM, slight hydrocarbon odor.
						-	



# AQUA RESOURCES, INC.

PG&E   PG&E	n Way, Oakland CA 946	
le Started 12/19/91	t	Date Finished <u>12/19/91</u>
pe of Observation Well	Water Grou	nd Elev Casing Top, Elev:
		•
	•	
	Lan	.*
· ·	<del></del>	cap locking cap and sealed well cover
	1 1 1 1 45	2" PVC
		Type of Casing
,		
18 feet	_	Type of Backilli cement grout
1 6	43	Type of Backini
L2 ½ foot	-	
L3 7½ feet	-	
10.5		Type of Seal Material
L4 <u>10 feet</u>		bentonite pellets
L5 foot		
		•
Le 5 feet	-	
L7 1 foot		
	一口。	0.020
L8	-	Size of Openings 0.020
	L4 18 18 L8	
		Type of Filter Material 2/12 sand
		Dlameter of Boring 8 inches
•		Diginates of policia
•		

Observed by -

# CONFIDENTIAL

STATE OF CALIFORNIA DWR WELL COMPLETION REPORT (WELL LOGS)

**REMOVED** 

# CONFIDENTIAL

STATE OF CALIFORNIA DWR WELL COMPLETION REPORT (WELL LOGS)

**REMOVED**