September 19, 2003

UST Local Oversight Program
Alameda County Health Agency
Department of Environmental Health
1131 Harbor Bay Parkway
Alameda, CA 94502-6577

Attention:

1.4

Barney Chan


Subject:

Report of Soil and Groundwater Investigation

3838 West Street UST Site

Oakland, California

GA Project No. 140-01-02 LOP Site ID No.: 4262





### Ladies and Gentlemen:

Gribi Associates is pleased to submit this report on behalf of Mr. Johnny Houston documenting a recently-completed soil and groundwater investigation at the 3838 West Street underground storage tank (UST) site in Oakland, California (see Figure 1 and Figure 2). This investigation included the installation and sampling of two water monitoring wells, MW-2 and MW-3, adjacent to a gasoline UST formerly located at the project site. The purpose of these activities are to further assess soil and groundwater quality adjacent to the former UST in order to address regulatory site closure.

### Background

One 550-gallon gasoline UST, which apparently had been unused for at least 20 years, was removed from the project site on January 8, 1992. Prior to removing the UST, approximately 650 gallons of water was pumped from the tank. Following removal of the UST, the Alameda County Department of Environmental Health inspector noted holes in the tank, and hydrocarbon odors and sheens in the excavation. Two soil samples collected at about eight feet in depth in the UST excavation cavity contained no detectable gasoline constituents and low levels of lead. One four-point composite soil sample collected from the excavated soil stockpile contained 4.3 parts per million (ppm) of TPH-G, with low levels of BTEX constituents and 32 ppm of Total Lead. A grab groundwater sample collected from the UST excavation cavity following tank removal contained 16 ppm of TPH-G, with low or no detectable levels of BTEX constituents.

In August 1998, Gribi Associates drilled and sampled one soil boring, IB-1, immediately southeast from the former site UST, and drilled, installed, and sampled one temporary groundwater monitoring well, MW-1, immediately southwest from the former site UST. Well MW-1 was purged and sampled on August 19, 1998, March 24, 1999, and September 1, 1999. Results of these activities have indicated the presence of aged gasoline-range hydrocarbons in soil and groundwater immediately southeast and southwest from the former site UST.

On June 9, 2003, Alameda County Environmental Health, Local Oversight Program (ACEH), issued a letter requesting additional groundwater assessment at the site. In response to this request, Gribi Associates submitted a workplan to ACEH on June 17, 2003 proposing the installation of two groundwater monitoring wells at the site. This workplan was approved by ACEH on June 24, 2003.

### LIMITATIONS

. .

The services provided under this contract as described in this report include professional opinions and judgments based on data collected. These services have been provided according to generally accepted environmental protocol. The opinions and conclusions contained in this report are typically based on information obtained from:

- 1. Observations and measurements made by our field staff.
- 2. Contacts and discussions with regulatory agencies and others.
- 3. Review of available hydrogeologic data.

### DESCRIPTION OF FIELD ACTIVITIES

Two groundwater monitoring wells were drilled and installed by Gribi Associates on July 18, 2003. Soil samples were collected from specified depths during well installation. On September 8, 2003, a representative from Gribi Associates purged and sampled groundwater in the two newly-installed wells, MW-2 and MW-3, and existing well MW-1.

### **Prefield Activities**

Prior to beginning field activities, Gribi Associates marked proposed boring locations and notified Underground Services Alert (USA). In addition, Gribi Associates obtained a drilling permit from Alameda County Public Works Department. A copy of this permit is contained in Appendix A.

### Location of Soil Borings and Monitoring Wells

Locations of the two newly-installed groundwater monitoring wells, MW-2 and MW-3, are shown on Figure 2. Well MW-2 is located immediately southeast of the former site UST, and MW-3 is located southwest from the former site UST, near the western property line.

### **Drilling and Sampling of Well Borings**

Well borings MW-2 and MW-3 were drilled to a depth of about 16 feet below surface grade using direct-push coring equipment. During drilling, retrieved soil cuttings were logged by Mr. Jim Gribi, a California-registered geologist. Boring logs for the two borings are contained in Appendix B. All sampling equipment was thoroughly cleaned and decontaminated between each sample collection by triple rinsing first with water, then with dilute tri-sodium phosphate solution, and finally with distilled water.

Soil samples were collected from the two borings at depths of about seven feet, nine feet, and 11.5 feet below surface grade. Each of the soil samples was collected using the following method: (1) Exposed soil was scraped away; (2) A clean 2-inch by 6-inch brass tube was completely filled with undisturbed soil, taking care to minimize excess void in the tube; (3) The tube was then quickly sealed with aluminum foil and plastic end caps, wrapped tightly with tape and labeled; and (4) The sealed tube was immediately placed in cold storage for transport to the laboratory.

### Installation and Sampling of Groundwater Monitoring Wells

Groundwater monitoring wells MW-2 and MW-3 were constructed using 1-1/4 inch diameter Schedule 40 threaded PVC casing according to the following specifications: (1) 0.020-inch slotted well casing was placed from approximately 15.0 feet to 5.0 feet in depth; (2) Filter sand was placed around the casing to a depth of about 4.0 feet below grade; (3) A bentonite seal was placed around the casing from 4.0 feet to 3.0 feet in depth; and (4) The remaining annulus was grouted using a cement/sand slurry (bentonite less than 5 percent). The top of each well was enclosed in a traffic rated locking box set in concrete slightly above grade. Well construction specifications for each well are shown on the boring logs, which are contained in Appendix B.

After allowing the cement seal to cure for at least 48 hours, wells MW-2 and MW-3 were developed and sampled on September 8, 2003, using clean disposable PVC bailers. Well development consisted of purging the well of at least three well volumes before sampling. During well development, groundwater was periodically monitored for the presence of free-floating product and odor, pH, specific conductance, temperature and visible clarity. Groundwater sampling data sheets for MW-1, MW-2 and MW-3 are contained in Appendix C. After these parameters had stabilized, groundwater was sampled directly from the bailer in the following manner: (1) Three 40-ml glass VOA vials were completely filled directly from the bailer with a minimum of agitation; (2) After making sure that no air bubbles were present, each container was tightly sealed with a teflon-lined septum; and (3) Each container was labeled and placed in cold storage for transport to the analytical laboratory under formal chain-of-custody. All sampling equipment was thoroughly cleaned and decontaminated between each sample collection by triple rinsing as described previously in this report.

Wellhead top of casing elevations were surveyed to an arbitrary datum for each of the three wells on September 10, 2003.

### Laboratory Analysis of Soil and Groundwater Samples

A total of six soil samples and three groundwater samples were analyzed for the following parameters:

USEPA 8015M Total Petroleum Hydrocarbons as Gasoline (TPH-G)
USEPA 8020/602 Benzene, Toluene, Ethylbenzene, Xylenes (BTEX)
USEPA 8260B Oxygenates & Lead Scavengers (TBA, MTBE, DIPE, ETBE, TAME)

All laboratory analyses were conducted by SunStar Laboratories, Inc., a California-certified analytical laboratory, with standard turn around on lab results.

### RESULTS OF INVESTIGATION

### **General Subsurface Conditions**

Subsurface soils in the two well borings were generally similar, consisting primarilly of interbedded silts, sand, and gravels down to about 12 feet in depth, followed by reddish brown silty clays down to total depth. Slight to moderate hydrocarbon odors were noted in soils between about eight feet and 11 feet in depth in the two well borings.

### **Hydrologic Conditions**

Groundwater flow gradient, as depicted on Figure 3, is to the south at about 0.20 ft/ft. Purged groundwater from MW-1 exhibited a slight hydrocarbon odor with no hydrocarbon sheen, and purged water from MW-3 exhibited a moderate hydrocarbon odor. Purged groundwater from MW-2 exhibited no hydrocarbon odors or sheen.

### Results of Laboratory Analyses

Soil and water analytical results are summarized in Table 1. Laboratory data reports for soil and water samples are contained in Appendix D.

	Table 1 SUMMARY OF SOIL AND GROUNDWATER ANALYTICAL RESULTS 3838 West Street UST Site											
Sample	Sample	Sample			Constitu	uent (parts pe	r million)	<del></del>				
Ti i	Date	Depth	TPH-G	В	T	E	X	MTBE	OXYG			
Soil S	Samples								i			
IB-1.1	08/13/98	7.0 ft	1201	< 0.10	<0.10	0.19	0.22	<1.0				
MW-1.1	08/13/98	6.5 ft	190¹	<0.25	<0.25	0.77	0.53	<2.5				
MW-2-7.5	07/18/03	7.5 ft.	<0.5	< 0.005	< 0.005	< 0.005	<0.010	< 0.020	<del></del>			
MW-2-9.0	07/18/03	9.0 ft.	30.0	< 0.005	<0 005	< 0.005	< 0.010	< 0.020				
MW-2-11.5_	07/18/03	11.5 ft.	<0.5	<0.005	< 0.005	< 0.005	< 0.010	< 0.020	<u></u>			
MW-3-7.5	07/18/03	7.5 ft.	12.0	< 0.005	<0.005	< 0.005	< 0.010	< 0.020				
MW-3-9.0	07/18/03	9.0 ft.	19.0	< 0.005	< 0.005	< 0.005	< 0.010	< 0.020				
MW-3-11.5	07/18/03_	11.5 ft.	<0.5_	<0.005	< 0.005	< 0.005	< 0.010	<0 020	, a t-			

	SUMMA	RY OF S		Table GROUND 8 West Stre	WATER A	ANALYTIC	AL RESU	LTS	
Sample	Sample	Sample			Constitu	uent (parts pe	r million)		
เช่	Date	Depth	TPH-G	B	<u></u>	E	X	MTBE	OXYG
Gro	undwater San	iples DTW							
IB-IW	08/19/98	- <del></del> -	26	< 0.025	0.085	0.180	0.058	<0.250	
MW-1	08/19/98	7.83 ft	1.8	0.0028	0.011	0.0059	0.0027	< 0.025	
<20.00>	03/24/99	4.52 ft	2.6	0.0058	0.048	0.026	0.024	< 0.050	
	09/01/99	7.23 ft	6.01	< 0.0025	0.028	0.061	0.025	< 0.025	
	09/08/03	7.38 ft_	1.4	<0.001	< 0.001	< 0.001	< 0.001	<0.002	< 0.002
MW-2	09/08/03	9.45 ft	< 0.050	< 0.001	< 0.001	< 0.001	< 0.001	< 0.002	< 0.002
<20.64>									
MW-3	09/08/03	9.40 ft	<0.050	< 0.001	< 0.001	< 0.001	< 0.001	< 0.002	< 0.002
<19.54>									

TPH-G = Total Petroleum Hydrocarbons as Gasoline

B = Benzene, T = Toluene, E = Ethylbenzene, X = Xylenes

MTBE = Methyl-t-butyl Ether

OXYG = Oxygenates (except MTBE), including Ter-Butyl Alcohol (TBA), Di-tsopropyl Ether (DIPE), Ethyl-t-butyl Ether (ETBE), and Tert-amyl Methyl Ether (TAME).

<0.10 = Not detected above the expressed value.

<20.00> = Top of casing elevation. Measured to an arbitrary datum.

I = Acculabs, Inc. laboratory report states "Product is not typical gasoline."

#### 4.0 CONCLUSIONS

Soil and groundwater laboratory analytical results from this and previous investigations clearly show no significant impacts to both soil and groundwater beneath the site. While there are some detectable concentrations of TPH-G in some soil and groundwater samples, there are no significant concentrations of BTEX or oxygenate constituents, indicating considerable degradation of any gasoline releases. Further, it appears likely based on these results that residual gasoline constituents present in soil and groundwater beneath the site do not pose a significant risk to potential indoor air receptors at the site.

Based on these conclusions, we recommend that Alameda County UST Local Oversight Program review this site for regulatory case closure.


We appreciate the opportunity to provide these services for you. Please call if you have questions or require additional information.

Very truly yours,


James E. Gribi Registered Geologist California No. 5843

JEG/ct Enclosures

File: GA-23/jh-west.rp1



Shawn Hanson Geologist FIGURES



DESIGNED BY: CHECKED BY:

DRAWN BY: SH SCALE: 1"=0.6 MILES

SITE VICINITY MAP


3838 WEST STREET OAKLAND, CALIFORNIA


DATE: 10/9/03

FIGURE: 1

**GRIBI Associates** 

PROJECT NO: 140-01-01





# APPENDIX A ALAMEDA COUNTY DRULLING PERMIT



### ALAMEDA COUNTY PUBLIC WORKS AGENCY

WATER RESOURCES SECTION
19) TLMHUSET ST. HAYWARD CA. M5141395 PHONE (510) 678-6635 June 1 Yes FAX (510) 712-1939

Applicants: Please attach a bite map for all druling permit applications destruction of wells over 45 feet requires a separate permit application

#### DRILLING PERMIT APPLICATION for applicant to complete FOR OFFICE USE 3838 user LOCATION OF PROJECT PERMIT NUMBER WELL NUMBER APN PERMIT CONDITIONS Circled Permit Requirements Apply CLIDA Nant A. GENERAL Yedu 847-5465 I. A parmit application should be submitted to as to arrive at the ACPWA office five days prior to nanoused starting date. 2. Submit to ACPWA within 60 days after completion of permitted original Dapartment of Water Resources—Well Completion Report. APPLICANT Name of the Address | St. of t ASSEC. FM\_747-7 3. Permit is void if project hot begun within 90 days of approved date B. WATER SUPPLY WELLS I. Minimum nuclear soul thickness is two inches of TYPE OF PROJECT coment grout placed by treasie. Well Consequetion Georgianal Investigation 2. Minimum year depth is 50 feet for manicipal and Cathodic Protestion Caneral industrial wells of 20 feet for demostic and irrigulate Wictor Supply Wolle unloss a lesser depth is specially approved. Contamination Montering Well Doungtion C. GROUNDWATER MONITORING WELLS INCLUDING FIEZOMETERS Proposed water supply well use I. Minimum surface seal thickness is two inches of New Demonic Ľ conent grout placed by treats. Replacement Democris Municipal Turken ou 2. Minimum seal depth for meditoring wells is the industrial Other MONITATION rescintum depth granicable or 10 feet. D. GEOTECHNICAL DRILLING METHORS Beakful bore hale by wente with coment grous or coment grouvessed mixture. Upper two-times feet replaced in kind Mud Rolary AIT RULLY Other or with companied suffings. E, CATHODIC DRILLER'S HAME Fill hole anode zone who concrete placed by tretties. WELL DESTRUCTION DRILLER'S LICTIVISE NO. Sond a map of work site. A separate permit is required for wells deeper then 45 feet. for wells deeper was a first one of the constitutions of the constitution of the constitut Well Projects Drill Hole Disarter NOTE: One application must be submitted for each well or well Caring Diameter destruction. Multiple borings on one application are secuentials Surfece Seel Dapet Owner's Well Number\_ for gootochnical and contambination inventerious. GEOTECHNICAL PROJECTS Number of Barmas Maximum ilala Disenster Depth 7-18-03 STARTING DATE COMPLETION DATE APPROVED I hereby agree to comply with all exquirements of this permit and charries County Ordinance No. 73-68. APPLICANT'S HONATURE PLEARE PRINT NAME Rev. 9-18-02

GRIDI ASSOCIATES

707 748 7763

PUBLIC

### ALAMEDA COUNTY PUBLIC WORKS AGENCY

WATER RESOURCES SECTION
399 ELMHURST ST. HAYWARD CA. 94544-1395
PHONE (5/0) 678-6693 James You
PAY (1/0) 781-1838

PAX (519) 781-1939
APPLICANTS: PLEASE ATTACH A SITE MAP FOR ALL DRILLING PERMIT APPLICATIONS DESTRUCTION OF WELLS OVER 4F FEET REQUIRES A SEPARATE PERMIT APPLICATION

DRILLING PERMIT APPLICATION

for applicant to complete	FOR OFFICE USE
LOCATION OF PROJECT 3832 LOCAT STIFFET	PERMIT NUMBER NOS COST
DAKLAND CA 94608	WELL NUMBER
The same of the sa	APH
	PERMIT CONDITIONS
CLIENT	Circled Parmit Requirements Apply
Norm JAHANY HUSTON	A. GENERAL
Address States Wash T are Phone Etto Ett 74 5465	1. A permit application should be substitled so us to
Chy Phis ALIA CA Zh The Deboth	perior of the ACPWA office five days prior to
APPLICANT	2. Submit to ACPWA within 60 days after completion of
Nuso a len (9.710)	committed original Department of Water Resources
Address 1980 Hayes at 60 of Phone 207-740-7745	Well Completion Report.  3. Permit is vold if project not bugan within 90 days of
Address 1980 Haves at 60 old Phone 307-749-7745 City Real City A 219 94-610	7. Litting is Add it bioloct ups toked Assitt AA oxia ox
	B. WATER SUPPLY WELLS
TYPE OF PROJECT	<ol> <li>Minimum surface seal thickness is two inches of coursest grout placed by trouts.</li> </ol>
Wall Continuous Oversubpical Investigation	2. Minimum scal depth is 50 feet for municipal and
Cathodic Protection :1 Canoral	industrial wollin or 20 fact for domestic and irrigation
Water Supply D Contamination  Montoring Well Description	wells wheth a lower doph is specially approved. C. GROUNDWATER MONITORING WELLS
No contraction	\ Including Piezometera
Proposed water supply well use	1. Minimum surface seat thickness is two inches of
New Domostiu () Replacement Domestic () Musleined () Irritation ()	cement grout placed by memic.  2. Winimum soal depth for monkering wells in the
Industrial ii Other Maniffactor	maximum dupih practicable or 20 foot.
DRILLING METHOD:	D. GEOTRCHNICAL
Mud Rolley D Air Routy Q Auger 1	Dackfill bore hale by tremie with coment grout or coment grout/seed maxture. Upper two-three fort replaced in kind
Calle 11 Other X DIPPET Push	of with compacted cuttings.
DRILLER'S NAME COREGE DO 11 NO.	CATHODIC     Fill hele areas zone with constate placed by rania.
DATE DAY ANAMA	F. WELL DESTRUCTION
DRILLER'S LICENSE NO.	Send a map of work shall separate sermit is required
425-16-	for wells desper than 45 feet.
WELL PROJECTS	31/0104 /
Drill Hole Diameter - 3/2 in. Massimum	NOTE: One application must be submitted for each well or well
Casing Clarimiter Mar in. Dupth 3 h. Surface Scal Depth 6 R. Owner's Wall Number Mu - 3	degraction. Multiple begings on one application are acceptable for acceptable for acceptable investigations.
	(b) The second of the second o
GROTECHNICAL PROJECTA  Number of Beringt Maximum	مسر
Holo Dismoter in Depth 9.	
STARTING DATE 7-18-0.3	
STARTINO DATE 7 18 03	Darage Contraction
COMPLETION DATE 7-18:3	1750
1	APPROVED DATE
I homby serve to comply with all requirements of this parmit and his appropriate County Ordin	18000 No. 73-68.
	14-03 / /
APPLICANT'S SIGNATURE DATE	············ /
PLEASE PRINT NAME - 1194 GILL ROWS	-18-02
<b>y</b>	(

# APPENDIX B SOIL BORING LOGS

BORING NUMBER: MW-2

### LOG OF SOIL BORING

### SHEET 1 OF 1

BORING LOCATION: NEAR NW CORNER

OF BUILDING

BORING TYPE: MONITORING WELL

PROJECT NAME: 3838 WEST STREET FORMER UST SITE

GAPROJECT NUMBER: 140-01-02

### **GRIBI** Associates

START DATE: 07/18/03

COMPLETION DATE: 07/18/03

DRILLING CONTRACTOR: GREGG DRILLING


DRILLING METHOD: GEOPROBE

**BOREHOLE DIAMETER: 2.5 INCHES** 

COMPLETION METHOD: MONITORING WELL

BORING TOTAL DEPTH: 16.0 FEET

GROUNDWATER DEPTH: 9.45 FEET



BORING NUMBER: MW-3

LOG OF SOIL BORING

### **GRIBI** Associates

SHEET 1 OF 1

DRILLING CONTRACTOR: GREGG DRILLING

DRILLING METHOD: GEOPROBE

**BOREHOLE DIAMETER: 2.5 INCHES** 

COMPLETION METHOD: MONITORING WELL

BORING TOTAL DEPTH: 16.0 FEET

GROUNDWATER DEPTH: 9.40 FEET

### BORING TYPE: MONITORING WELL

PROJECT NAME: 3838 WEST STREET FORMER UST SITE

BORING LOCATION: NEAR STREET

GA PROJECT NUMBER: 140-01-02

START DATE: 07/18/03 COMPLETION DATE: 07/18/03

DEPTH SCALE (FEET)	SAMPLE NO.	SAMPLE DEPTH	INTERVAL	PID READING BLOW COUNTS PINITIAL PINAL	USCS	LOG OF MATERIAL	PIEZOMETERI WELL INSTALLATION
5 -	MW-3-7.5 MW-3-9.0 MW-3-11.5	9.0 FT.		¥ - FINAL		O.0 - 5.0 ft. Grey brown clayey, sandy GRAVEL, loose, no odor or staining.  5.0 - 7.0 ft. Red brown clayey GRAVEL, moist, loose to firm, no odor or staining.  7.0 - 8.0 ft. Red brown silty CLAY, firm, locally gravelly, no odor or staining.  8.0 - 10.5 ft. Grey green sandy medium GRAVEL, loose to firm, moist to wet, moderate hydrocarbon odor.  10.5 - 16.0 ft. Red brown silty CLAY, locally gravelly, firm and wet, no odor or staining.  TOTAL DEPTH: 16.0 FEET GROUNDWATER DEPTH: 9.40 FEET  WELL SPECIFICATIONS	
			] 			A - WELL SCREEN DEPTH: 5.04 FT CASING TYPE: SCH 40 PVC B - WELL SCREEN LENGTH: 10.00 FT CASING SIZE: 1.25" C - DEPTH TO TOP OF SAND. 4.0 FT SLOT SIZE: 0.02" D - DEPTH BENTONITE SEAL: 3.0 FT	

### APPENDIX C GROUNDWATER SAMPLING DATA SHEET

GROUNDWATER SAMPLING RECORD	GRIBI Associate						
Well No. MW-1	Well Loc.						
Project Name 3838 West St., Oakland	Project No.						
Date 9/8/03 Time	TOC Elevation GW Elevation						
Depth to Water 7.38 ft.	Well Depth 12.25 Ft Well Diameter 1"						
Purge Water, 2": Wtr Column X 0.163 X 3 =	Purge Water, 4": Wtr Column X 0.653 X 3 =						
Purge/Sample Method peristattic pump	Lab Analyses						
Weather Conditions clear & warm	Laboratory						

Time	Volume Purged	Temp.	Cond.	рН	Visual
1128	250 mL	23-2	142	6.56	odor 1 clear /colorless
1130	500 mL	23.2	120	6.44	
1136	750 mL	23-7	142	6.41	
1145	1 _	24.8	138	6.38	·
1148	1.25 L	24.0	141	6-32	
1150	1.50 L	23.9	143	6.28	
1152	2-50 L	23-8	143	6.26	
1154	3.50 L	23.8	142	6.25	
				·	
		,			,

Remarks

Sampled @ 1158

GROUNDWATER SAMPLING RECORD	GRIBI Associate						
Well No. MW-2	Well Loc.						
Project Name 3838 West St., Oakland	Project No.						
Date 9 8 03 Time	TOC Elevation GW Elevation						
Depth to Water 9.45 ft	Well Depth 15.20 ft Well Diameter 3/4"						
Purge Water, 2": Wtr Column X 0.163 X 3 =	Purge Water, 4": Wtr Column X 0.653 X 3 =						
Purge/Sample Method Peristal hic pump	Lab Analyses						
Weather Conditions Clear & worm	Laboratory						

Time	Volume Purged	Temp.	Cond. µS	рН	Visual
1054	500 mL	21.9	174	7-73	Brown / turbid
1056	750 mL	21.8	160	7.32	
1057	100 L	21.5	155	7.20	
1058	1-25 L	21.2	143	6.91	Dried
1103	1.50 L	21.3	144	6.90	
					·
					·
			•		

Remarks

Sampled @ 1115

3vol = 1.52

$$\frac{\sqrt{2}}{\sqrt{2}} = \frac{\sqrt{4}}{4} = \frac{\sqrt{6}}{4} = 7.1$$

$$\frac{(2)^{2}}{(2)^{2}} = \frac{\sqrt{4}}{4} = \frac{\sqrt{6}}{9} = 7.1$$

$$\frac{(34)^{2}}{\sqrt{7.1}} = \frac{\sqrt{6}}{\sqrt{6}} = 7.1$$

$$\frac{\sqrt{63}}{\sqrt{7.1}} = 0.022$$

$$\frac{\sqrt{63}}{\sqrt{7.1}} = 0.022$$

$$\frac{\sqrt{63}}{\sqrt{63}} = 0.022 \times 3 = 0.37 \text{ gal} = 1.42$$

$$(34)^{2} = \sqrt{63} = 0.792$$

**GRIBI** Associates **GROUNDWATER SAMPLING RECORD** MW-3 Well Loc. Well No. St., Oakland West Project Name 3838 Project No. 9/8/03 Time Date **TOC Elevation GW Elevation** Well Diameter 3/4 " Well Depth 14-98 ft Depth to Water 9.40 Purge Water, 2": Wtr Column X 0.163 × 3 = Purge Water, 4": Wtr Column X 0.653 X 3 = peristaltic pump Purge/Sample Method Lab Analyses Clear & warm Weather Conditions Laboratory

Time	Volume Purged	Temp.	Cond.	рH	Visual
1219	250 mL	24.2	172	6.40	Lightbrown/slight odor/
1221	500 mL	24.0	126	6.29	turbid
1223	750 mL	23.8	172	6.29	
1225	1.00 L	23.4	134	6.28	DRIED
				·	
					·
					,
<del></del>		<del>~_~</del> ~			

Remarks

Sampled @ 1245

3 casings = 1.4-l

# APPENDIX D LABORATORY DATA REPORTS



# SunStar Laboratories, Inc.

24 July 2003

Jim Gribi Gribi Associates 1350 Hayes St. -- Suite C-14 Benicia, CA 94510

RE: Johnny Huston Site

Enclosed are the results of analyses for samples received by the laboratory on 07/20/03 10:20. If you have any questions concerning this report, please feel free to contact me.

Sincerely,

Jennifer Dahl

PM. Chemist III

unstar Laboratories, Inc.									Lab Number						
3002 Dow Avenue, Suite 212 Tustin, CA 92780 1-800-781-6777		300	7	90	/	)			Rep Due	ort Dat	e:				
Client Gribi Ass	ociates						C	Date				7/2	0/200	3	
	res Street, Ste C-14						F	Project Name Johnny Huston Site				Site			
	CA 94510							Collec	tor's Nar	ne		lim G	ribi		
Contact Jim Gribi							(	Client's	s Projec	t Num	ber				
							Batch Number								
	07/748-7743							on (City)			 Takla	nd, C	Δ		
Fax 707/748-	48-7763										Jailla	ria, o.		<del></del>	
P.O. Number SAMPLE TYPE	Email Resi		N Section	Page	1 Ans	of lyses		ropo:	sal Num	ber /	7	7	/ /	7	/ /
DW = drinking water  WW = waste water  MW = monitoring well  HW = hazardous waste  TURNAROUND TIME	rei blank Compi id Monit V	iance oring N	S in male	00=-=-	ŀ	restec	1		/	//	//	//		//	
Standard	Lab Di		Ť	n e	,	(0)	/ /	/ /	′ /	/ ,	/ /	/ /		/ /	/ /
RUSH	Appr	oval	¥		/:	25			//	' /			/ /	/ /	
Special			p e	3 <b>3</b> 3 3 3 3	/E			Ι.	/ /			/ /	′ /		LAIC
CLIENT'S SAMPLE ID/LOCA	TION Date	Time			<u> </u>	7/	{			<del>/</del> -			{	<del></del> 1	Spl. No.
MW-2-7.5	7/18/2003	1025	S	1						-				-	0)
MW-2-9.0	7/18/2003	1035	S	1	_					<del>                                     </del>	-			-	03 03
MW-2-11.5	7/18/2003	1035	S	1							-		<del> </del>	╂─┤	04
MW-3-7.5	7/18/2003	1135 1145	S	1					_	<del>                                     </del>		-			05
MW-3-9.0 MW-3-11.5	7/18/2003	1145	S	1	<del> </del>			一十	_					1	Ōб
Instructions/Comments/Special F	Requirements:							Detec	tion Le	vels	<del></del>	Soil		Wat	9.5
								TPH-	G&D			1.0 ppi	m	50.0	ррь
					·			BTEX	UMTBE/	VOCs		0.005	pm	0.5	opb
								0&G			reservation of	50.0 p	pm	5.0	opm
SAMPLE RECEIPT	Date	Time		<b>, j</b> amp	les l	(ejjn	gaïŝ	hed I	3)/		Sa	mple:	Rer	ived	By
	1 (3c) 7-200	1020	1	Janu	Δ_(	10	Ō	2			15	U f	Aus	w	<u> </u>
Custody Seals Y	1/		/												
	v)														
No. of Containers	6												***************************************	<del>,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,</del>	
		30000												ara di Mana	

Gribi Associates 1350 Hayes St. -- Suite C-14 Project: Johnny Huston Site

Reported:

Benicia CA, 94510

Project Number: [none]
Project Manager: Jim Gribi

7/24/03

### ANALYTICAL REPORT FOR SAMPLES

Sample ID	Laboratory ID	Matrix	Date Sampled	Date Received
MW-2-7.5	T300790-01	Soil	7/18/03	7/20/03
MW-2-9.0	T300790-02	Soil	7/18/03	7/20/03
MW-2-11.5	T300790-03	Soil	7/18/03	7/20/03
MW-3-7.5	T300790-04	Soil	7/18/03	7/20/03
MW-3-9.0	T300790-05	Soil	7/18/03	7/20/03
MW-3-11.5	T300790-06	Soil	7/18/03	7/20/03

SunStar Laboratories, Inc.

1350 Hayes St. -- Suite C-14

Benicia CA, 94510

Project: Johnny Huston Site

Project Number: [none] Project Manager: Jim Gribi Reported:

7/24/03

## Volatile Organic Compounds by EPA Methods 8021B/8015M SunStar Laboratories, Inc.

Analyte	Result	Limit	Units	Dilution	Batch	Prepared	Analyzed	Method	Note
MW-2-7.5 (T300790-01) Soil Sai	mpled: 07/18/03	10:25 Re	ceived:	07/20/03	10:20				
Methyl tert-butyl ether	ND	20	ug/kg	1	3072303	07/22/03	07/22/03	EPA 8021B/8015	
Benzene	ND	5.0	fr	11	ft	ti	n	m "	
Coluene	ND	5.0	u				 Ji	n	
Ethylbenzene	ND	5.0	**		H	**	II	n	
n,p-Xylene	ND	10	**	IJ	H	44	n	ų	
-Xylene	ND	5.0	11	IJ	11	н	U	u	
Gasoline Range Hydrocarbons	ND	500	ш			) <sub>"</sub>	(r	H	
Surrogate: 4-Bromofluorobenzene	112	76.0 %	65-	-135	"	#	,,	"	
					10-20				
MW-2-9.0 (T300790-02) Soil Sai	-	10:35 Re		0 //20/03 ]	10:20				
Aethyl tert-butyl ether	ND	20	ug/kg	l	3072303	07/22/03	07/23/03	EPA 8021B/8015	
Benzene	ND	5.0	11	п	II.	u	n	m	
Foluene	ND	5.0	ıı	"	u	"	11	н	
Ethylbenzene	ND	5.0	11	"	11	)i	ij	Jt.	
n,p-Xylene	ИD	10	œ	,		"	II	o.	
-Xylene	ND	5.0	11	n	1)		11	u	
Gasoline Range Hydrocarbons	30000	2000	10	4	ı)	lf .	**	n	
Surrogate: 4-Bromofluorobenzene	30000	82,4 %	65-	.135	"	"	"	85	
AW-2-11.5 (T300790-03) Soil Sa	mpled: 07/18/0	3 10:35 R	eceived	: 07/20/03	10:20				
Methyl tert-butyl ether	ДИ	20	ug/kg	1	3072303	07/22/03	07/23/03	EPA 8021B/8015	
Benzene	ИD	5.0	n	п	11	"	н	m	
Coluene	ND	5.0	н	u	u	19:	н	R	
Sthylbenzene	ND	5.0		0	u	,,	н	W	
n,p-Xylene	ND	10	IJ		u	н	0	IF.	
-Xylene	ND	· 5.0	п	fr	H	н	ij	IF.	
Gasoline Range Hydrocarbons	ND	500	45	rr	n	ч	n	11	
SHOOTING AND	, , ,	200							

SunStar Laboratories, Inc.

Benicia CA, 94510

Associates

1350 Hayes St. -- Suite C-14

Project: Johnny Huston Site

Project Number: [none]

Reported:

7/24/03

Project Manager: Jim Gribi

### Volatile Organic Compounds by EPA Methods 8021B/8015M SunStar Laboratories, Inc.

Analyte	Result	Reporting Limit	Units	Dilution	Batch	Prepared	Analyzed	Method	Notes
MW-3-7.5 (T300790-04) Soil	Sampled: 07/18/03	11:35 Re	ceived:	07/20/03	10:20				·
Methyl tert-butyl ether	ND	20	ug/kg	I	3072303	07/22/03	07/22/03	EPA 8021B/8015 m	
Benzene	ND	5.0		17	**	17	п	111	
Toluene	ND	5.0	n	Ħ	11	pt .	rr	u	
Ethylbenzene	ND	5.0	fr	10	n	ţl.	n	U U	
m,p-Xylene	ND	10	78	н	II	d	II.	"	
o-Xylene	ND	5.0	н		II	ţţ	U	II	
Gasoline Range Hydrocarbons		500	35	n	tt	7"	п	ŋ	
Surrogate: 4-Bromofluorobenzen		71.0 %	65-	-135	u	"	,,	"	
MW-3-9.0 (T300790-05) Soil	Sampled: 07/18/03	11:45 Re	ceived:	07/20/03	10:20				
Methyl tert-butyl ether	ND	20	ug/kg	1	3072303	07/22/03	07/23/03	EPA 8021B/8015	
Benzene	ND	5.0	19	U	u	jt.	**	m "	
Foluene	ND	5.0		er er	**	ţ!	n	#	
Ethylbenzene	ND	5.0		**	ıı	ţl.	U	ij	
m,p-Xylene	ND	10	18	н	ıı .	10	11	u	
o-Xylene	ND	5.0	19		tt	н	10		
Gasoline Range Hydrocarbons		500	U	(f	13	d	n	U	
Surrogate: 4-Bromofluorobenzen		72.0 %	65-	-135	"	"	"	и	
MW-3-11.5 (T300790-06) Soil	Sampled: 07/18/0	3 11:45 R	eccived	: 07/20/03	10:20				
Methyl tert-butyl ether	ND	20	ug/kg	1	3072303	07/22/03	07/23/03	EPA 8021B/8015	
Benzene	ND	5.0	ıı	u	**	ţţ.	n	m "	
Toluene	ND	5.0		u	n	t)	н	u	
Ethylbenzene	ND	5.0	"	n	19	**	11	n	
m,p-Xylene	ND	10	u	**	u,	r	II	11	
o-Xylene	ND	, 5.0	10	n	Iţ	μ	15	19	
Gasoline Range Hydrocarbons	ND	500	н	n	re	(f	II.	u	
Surrogate: 4-Bromofluorobenzen		71.9 %	65	-135	#	"	"	,,	
Bui rogaie. T-Di omojinoi obenzen		11.770	0,5-	100					

SunStar Laboratories, Inc.

1350 Hayes St. -- Suite C-14

Benicia CA, 94510

Project: Johnny Huston Site

Project Number: [none] Project Manager: Jim Gribi Reported:

7/24/03

## Volatile Organic Compounds by EPA Methods 8021B/8015M - Quality Control SunStar Laboratories, Inc.

Analyte	Result	Reporting Limit Units	Spike Level	Source Result	%REC	%REC Limits	RPD	RPD Limit	Notes
Batch 3072303 - EPA 5030 Soil GC				***	~				
Blank (3072303-BLK1)			Prepare	d & Analy	vzed: 07/2	23/03			
Methyl tert-butyl ether	ND	20 ug/kg			,				
Benzene	ND	5.0 "							
Toluene	ND	5.0 "							
Ethylbenzene	ND	5.0 "							
n,p-Xylene	ND	10 "							
o-Xylene	ND	5.0 "				1			
Gasoline Range Hydrocarbons	ND	500 "							
Surrogate: 4-Bromofluorobenzene	85.8	n	125		68.6	65-135			
LCS (3072303-BS1)			Prepare	d & Analy	zed: 07/2	23/03			
Benzone	215	5.0 ug/kg	200		108	70-130			
Toluene	1040	5.0 "	928		112	70-130			
Ethylbenzene	243	5.0 "	218		111	70-130			
m,p-Xylene	898	10 "	750		120	70-130			
o-Xylene	344	5.0 "	302		114	70-130			
Surrogate: 4-Bromofluorobenzene	127	"	125		102	65-135			
Matrix Spike (3072303-MS1)	Source:	T300789-01	Prepare	d & Analy	zed: 07/2	23/03			
Benzene	213	5.0 ug/kg	200	ND .	106	70-130			
Toluene	1000	5.0 "	928	ND	108	70-130			
Ethylbenzene	214	5.0 "	218	ND	98.2	70-130			
n,p-Xylene	785	10 "	750	ND	105	70-130			
o-Xylene	302	5.0 "	302	ND	100	70-130			
Surrogate: 4-Bromofluorobenzene	127	u	125		102	65-135			
Matrix Spike Dup (3072303-MSD1)	Source:	T300789-01	Prepare	Prepared & Analyzed: 07/23/03					
Benzene	208	5.0 ug/kg	200	ND	104	70-130	2.38	20	
Toluene	1000	5.0 "	928	ND	108	70-130	0.00	20	
Ethylbenzene	207	5.0 "	218	ND	95.0	70-130	3.33	20	
n,p-Xylene	761	10 "	750	ND	101	70-130	3.10	20	
o-Xylene	292	5.0 "	302	ND	96.7	70-130	3.37	20	
Surrogate: 4-Bromofluorobenzene	133	ti	125		106	65-135			

SunStar Laboratories, Inc.

Gribi Associates
Project: Johnny Huston Site

1350 Hayes St. -- Suite C-14
Project Number: [none]
Reported:

Benicia CA, 94510
Project Manager: Jim Gribi
7/24/03

#### Notes and Definitions

DET Analyte DETECTED

ND Analyte NOT DETECTED at or above the reporting limit

NR Not Reported

dry Sample results reported on a dry weight basis

RPD Relative Percent Difference

SunStar Laboratories, Inc.



# SunStar Laboratories, Inc.

16 September 2003

Jim Gribi Gribi Associates 1350 Hayes St. -- Suite C-14 Benicia, CA 94510

RE: Johnny Huston Site

Enclosed are the results of analyses for samples received by the laboratory on 09/11/03 10:20. If you have any questions concerning this report, please feel free to contact me.

Sincerely,

Ben Beauchaine For John Shepler

**Laboratory Director** 

#### Sunstar Laboratories, Inc. 3002 Dow Avenue, Suite 212 Tustin, CA 92780 1-800-781-6777 9/11/2003 Date Client **Gribi Associates** Johnny Huston Site 1350 Hayes Street, Ste C-14 Project Name Address Jim Gribi Collector's Name Benicia, CA 94510 City, State & Zip Client's Project Number Jim Gribi Contact Batch Number 707/748-7743 Phone Oakland, CA 707/748-7763 Location (City) Fax Page Email Results ( Proposal Number P.O. Number SAMPLE TYPE CODES Analyses ¢ S TB = travel blank Compliance Requested DW = drinking water o SD = solid Monitoring WW ≠ waste water m n SO = soil MW ≈ monitoring well Υ SL = sludge HW = hazardous waste æ TURNAROUND TIME REQUESTED Lab Director Standard 4 e Approval RUSH Les To Special CLIENT'S SAMPLE ID/LOCATION Spl-No. Date Time 01 W 3 MW-1 9/8/2003 зIX 26 W MW-2 9/8/2003 зIX W 03 MW-3 9/8/2003 Instructions/Comments/Special Requirements: **Detection Levels** Soil Water TPH-G&D 1.0 ppm 50.0 ppb BTEX/MTBE/VOCs 0.005 ppm 0.5 ppb 0&G 50,0 ppm 5.0 ppm Samples Relinguished By Date Time SAMPLE RECEIPT 30 io ZD Received Cold **Custody Seals** Seals Intact No. of Containers

Lab Number

Gribi Associates 1350 Hayes St. -- Suite C-14 Benicia CA, 94510 Project: Johnny Huston Site

Project Number: [none] Project Manager: Jim Gribi Reported: 9/16/03

### ANALYTICAL REPORT FOR SAMPLES

Sample ID	Laboratory ID	Matrix	Date Sampled	Date Received
MW-1	T300979-01	Water	9/8/03	9/11/03
MW-2	T300979-02	Water	9/8/03	9/11/03
MW-3	T300979-03	Water	9/8/03	9/11/03

SunStar Laboratories, Inc.

< DD

1350 Hayes St. -- Suite C-14 Benicia CA, 94510 Project: Johnny Huston Site

Project Number: [none]
Project Manager: Jim Gribi

Reported: 9/16/03

### Volatile Organic Compounds by EPA Method 8260B

### SunStar Laboratories, Inc.

Analyte	Result	Reporting Limit	Units	Dilution	Batch	Prepared	Analyzed	Method	Note
MW-1 (T300979-01) Water Sample	ed: 09/08/03 0	0:00 Rece	ived: 0	9/11/03 10	:20				
Gasoline Range Hydrocarbons	1400	50	ug/l	i	3091502	09/12/03	09/14/03	EPA 8260B	
Benzene	ND	1.0	п	H	n	11	11	п	
Toluene	ND	1.0	**	u u	II .	D	II .	11	
Ethylbenzene	ND	1.0	U	19	Ħ	11	10	u	
m,p-Xylene	ND	1.0	n	IJ	н	U	a	H	
o-Xylene	ND	1.0	н	#	п	u	n	n	
Methyl tert-butyl ether	ND	2.0	11	H	19	Ð	п	и	
Ethyl tert-butyl ether	ND	2.0	4	u	u	70	Ħ	1)	
Tert-amyl methyl ether	ND	2.0	IJ	"	11	10	H	11	
Di-isopropyl ether	ND	2.0	u	n	n	u	п	10	
Tert-butyl alcohol	ND	10	и	ti-	н	ft	"	a	
Surrogate: Dibromofluoromethane		106 %	86-	-118	"	"	"	"	
Surrogate: Toluene-d8		95.8 %	86-	-115	μ	"	Ħ	"	
Surrogate: 4-Bromofluorobenzene		91.8 %	86-	-115	ø	11	#	u	
MW-2 (T300979-02) Water Sample	ed: 09/08/03 0	0:00 Rece	ived: 09	9/11/03 10	:20				
Gasoline Range Hydrocarbons	ND	50	ug/l	1	3091502	09/12/03	09/14/03	EPA 8260B	
Benzene	ND	1.0	v	II .	U	10	11	Ø	
Toluene	ND	1.0	n	**	14	II.	II .	n	
Ethylbenzene	ND	1.0	**	II	ti .	Ħ	10	U	
n,p-Xylene	ND	1.0	IJ	n	**	H	u	12	
o-Xylene	ND	1.0	11	U	n	*1	**	0	
Methyl tert-butyl ether	ND	2.0	ij	п	"	11	II.	н	
Ethyl tert-butyl ether	ND	2.0	U	38	D	11	19	u	
Tert-amyl methyl ether	ND	2.0	**	II	U	ц	u	n	
Di-isopropyl ether	ND	2.0	II	11	**	1)	11	n	
Tert-butyl alcohol	ИD	10	u	11	u	**	n	ш	
Surrogate: Dibromofluoromethane		104 %	86-	118	"	t!	"	rr .	
Surrogate: Toluene-d8		96.0 %	86-	115	"	ø	"	#	
		93.2 %		115			"		

SunStar Laboratories, Inc.

Project: Johnny Huston Site

1350 Hayes St. -- Suite C-14 Benicia CA, 94510 Project Number: [none]

Project Manager: Jim Gribi

Reported: 9/16/03

### Volatile Organic Compounds by EPA Method 8260B

### SunStar Laboratories, Inc.

Analyte	Rep Result	orting Limit	Units	Dilution	Batch	Prepared	Analyzed	Method	Notes
MW-3 (T300979-03) Water S	ampled: 09/08/03 00:00	Rece	ived: 09	9/11/03 10	):20				
Gasoline Range Hydrocarbons	ND	50	ug/l	1	3091502	09/12/03	09/14/03	EPA 8260B	
Benzene	ND	1.0	11	**	et .	11	II	ų	
Toluene	ND	1.0	11	II.	н	u	11	14	
Ethylbenzene	ND	1.0	**	u	II .	H	II.	U	
m,p-Xylene	DИ	1.0		11	)ę	u	n	14	
o-Xylene	ND	1.0	**	п	п	11	n	II .	
Methyl tert-butyl ether	ND	2.0	п	10	"	u	**	R	
Ethyl tert-butyl ether	ИД	2.0	n	п	n .	١"	IJ	n .	
Tert-amyl methyl ether	ND	2.0	IF	10	**	**	Ħ	H	
Di-isopropyl ether	ND	2.0	н	п	IJ	n n	ij	ij	
Tert-butyl alcohol	ND	10	r r	11	II.	11	W	II .	
Surrogate: Dibromofluorometha	ne ,	105%	86-	118	ıı.	"	n	H	
Surrogate: Toluene-d8	9	7.2 %	86-	115	n	n	n	"	
Surrogate: 4-Bromofluorobenzen	ne 9	3.2 %	86-	115	"	"	,,	#	

SunStar Laboratories, Inc.

1350 Hayes St. -- Suite C-14 Benicia CA, 94510 Project: Johnny Huston Site

Project Number: [none]
Project Manager: Jim Gribi

Reported:

9/16/03

## Volatile Organic Compounds by EPA Method 8260B - Quality Control SunStar Laboratories, Inc.

Analyte	Result	Reporting Limit Units	Spike Level	Source Result	%REC	%REC Limits	RPD	RPD Limit	Notes
Batch 3091502 - EPA 5030 Water	MS								
Blank (3091502-BLK1)			Prepare	d: 09/12/0	3 Analy	zed: 09/14/03			
Gasoline Range Hydrocarbons	ND	50 ug/l	•						
Benzene	ND	1.0 "							
Toluene	ND	1.0 "							
Ethylbenzene	ND	1.0 "							
m,p-Xylene	ND	10"							
o-Xylene	ND	1.0 "				``			
Methyl tert-butyl ether	ND	2.0 "							
Ethyl tert-butyl ether	ND	2.0 "							
Tert-amyl methyl ether	ND	2.0 "							
Di-isopropyl ether	ND	2.0 "							
Tert-butyl alcohol	ND	LQ "							
Surrogate: Dibromofluoromethane	42.0	ıı ı	40.0		105	86-118			
Surrogate: Toluene-d8	38.0	"	40.0		95.0	86-115			
Surrogate: 4-Bromofluorobenzene	37.4	"	40.0		93.5	86-115			
LCS (3091502-BS1)			Prepare	d: 09/12/0	3 Analy:	zed: 09/14/03			
Benzene	112	1.0 ug/l	100		112	75-125			
Toluene	98.7	1.0 "	100		98,7	75-125			
Surrogate: Toluene-d8	38.7	"	40.0		96.8	86-115			
Surrogate: 4-Bromofluorobenzene	38.9	"	40.0		97.2	86-115			
Surrogate: Dibromofluoromethane	39.5	#	40.0		98.8	86-118			
Surrogate: Dibromofluoromethane	39.5	"	40.0		98.8	86-118			
Surrogate: Toluene-d8	38.7	"	40.0		96.8	86-115			
Surrogate: 4-Bromofluorobenzene	38.9	"	40.0		97.2	86-115			
Matrix Spike (3091502-MS1)	Source	T300979-02	Prepare	d: 09/12/0:	3 Analy:	zed: 09/14/03			
Benzene	89.2	1.0 ug/l	100	ND	89.2	75-125			•
Toluene	91.5	1.0 "	100	ND	91.5	75-125			
Surrogate: Toluene-d8	38.4	,	40.0		96.0	86-115			
Surrogate: 4-Bromofluorobenzene	36.5	"	40.0		91.2	86-115			
Surrogate: Dibromofluoromethane	40.2	#	40.0		100	86-118			
Surrogate: Dibromofluoromethane	40.2	"	40.0		100	86-118			
Surrogate: Toluene-d8	38.4	"	40.0		96.0	86-115			
Surrogate: 4-Bromofluorobenzene	36.5	#	40.0		91,2	86-115			

SunStar Laboratories, Inc.

chain of custody document. This analytical report must be reproduced in its entirety.

The results in this report apply to the samples analyzed in accordance with the

1350 Hayes St. -- Suite C-14 Benicia CA, 94510 Project: Johnny Huston Site

Project Number: [none] Project Manager: Jim Gribi Reported:

9/16/03

## Volatile Organic Compounds by EPA Method 8260B - Quality Control SunStar Laboratories, Inc.

	Reporting		Spike Source			%REC	RPD				
Analyte	Result					%REC			Limit	Notes	
Batch 3091502 - EPA 5030 Water M	<b>4</b> S										
Matrix Spike Dup (3091502-MSD1)	Source:	Т300979-	02	Prepare	d: 09/12/03	3 Analyz	zed: 09/14/03				
3enzene	87.9	1.0	ug/l	100	ND	87.9	75-125	1.47	20		
Foluene .	89.1	1.0	II.	100	ND	89.1	75-125	2.66	20		
Surrogate: Toluene-d8	38.9		n	40.0		97.2	86-115				
Surrogate: 4-Bromofluorobenzene	37.4		"	40.0		93.5	86-115				
Surrogate: Dibromofluoromethane	39.6		#	40.0		99.0	86-118				
Surrogate: Dibromofluoromethane	39.6		44	40.0		99.0	86-118				
Surrogate: Toluene-d8	38.9		"	40.0		97.2	86-115				
Surrogate: 4-Bromofluorobenzene	37.4		"	40.0		93.5	86-115				

SunStar Laboratories, Inc.

Benicia CA, 94510

Project: Johnny Huston Site

1350 Hayes St. -- Suite C-14

Project Number: [none] Project Manager: Jim Gribi Reported:

9/16/03

### Notes and Definitions

DET

Analyte DETECTED

ND

Analyte NOT DETECTED at or above the reporting limit

NR

Not Reported

dry

Sample results reported on a dry weight basis

RPD

Relative Percent Difference

SunStar Laboratories, Inc.

< 155 ···