Ro 243



June 16, 2004

TRC Project No. 42016501

Mr. Don Hwang Alameda County Health Services 1131 Harbor Bay Parkway Alameda, California 94502-6577



RE: Quarterly Status Report - Second Quarter 2004

76 Service Station #0018, 6201 Claremont Avenue, Oakland, California

Alameda County

Dear Mr. Hwang:

On behalf of ConocoPhillips Company (ConocoPhillips), TRC is submitting the Second Quarter 2004 Quarterly Status Report for the subject site, shown on the attached Figures 3 through 5.

PREVIOUS ASSESSMENTS

The subject site is an active service station located on the northern corner of the intersection of Claremont and College Avenues in Oakland, California. The nearest surface water is Claremont Creek, approximately 0.1 mile northeast of the site.

March 1997: Karpealian Engineering Inc. (KEI) collected soil and grab groundwater samples during underground storage tank (UST) and product line replacement activities. A groundwater sample collected from the former gasoline UST excavation contained 6,100 parts per billion (ppb) total petroleum hydrocarbons as gasoline and 54 ppb benzene.

March 1998: Tosco was issued a Notice of Responsibility by the Alameda County Health Care Services Agency.

December 2000: Gettler-Ryan Inc. installed three groundwater monitoring wells to depths of 30 to 30.5 feet below ground surface (bgs). Groundwater samples contained low maximum concentrations of total petroleum hydrocarbons calculated as gasoline, benzene, and methyl tertiary butyl ether (MTBE).

October 2003: Site environmental consulting responsibilities were transferred to TRC.

SENSITIVE RECEPTORS

Surface water Claremont Creek is located 0.1 miles northeast of the site. A sensitive receptor survey has not been performed for this site.

QSR –Second Quarter 2004 76 Service Station #0018, Oakland, California June 16, 2004 Page 2

MONITORING AND SAMPLING

Three onsite wells are currently monitored quarterly. The groundwater gradient and flow direction were 0.01 foot/foot to the southwest. The groundwater gradient and flow direction were generally consistent with recent historical data.

CHARACTERIZATION STATUS

Total purgeable petroleum hydrocarbons (TPPH) were detected in monitoring well MW-1 at a concentration of 180 micrograms per liter (µg/l). TPPH was not detected above the reporting limit in the other wells sampled this quarter. These levels were consistent with recent historical data.

Benzene was not detected above the reporting limit in any of the wells sampled this quarter. These levels were generally consistent with recent historical data.

MTBE was detected in two of three monitoring wells, with a maximum concentration of 25 µg/l in monitoring well MW-1. These levels were generally consistent with recent historical data.

REMEDIATION STATUS

Remediation is not currently being conducted at the site.

RECENT CORRESPONDENCE

No correspondence this quarter.

CURRENT QUARTER ACTIVITIES

May 7, 2004: TRC performed groundwater monitoring and sampling. Wastewater generated from well purging and equipment cleaning was stored at TRC's groundwater monitoring facility in Concord, California, and transported by Onyx to the ConocoPhillips Refinery in Rodeo, California, for treatment and disposal.

NEXT QUARTER ACTIVITIES

Await agency directives for additional assessment work, if any.

Continue quarterly monitoring and sampling to assess plume stability and concentration trends at key wells.



QSR –Second Quarter 2004 76 Service Station #0018, Oakland, California June 16, 2004 Page 3

If you have any questions regarding this report, please call Roger Batra at (925) 688-2466.

Sincerely,

TRC

Roger Batra

Senior Project Manager

Roger Pratra

Barbara Moed, R.G. Senior Project Geologist

Attachments:


Figure 3 – Dissolved Phase TPPH Concentrations Map, May 7, 2004, from Second Quarter 2004 Fluid Level Monitoring and Sampling Report, dated June 4, 2004 by TRC.

Figure 4 – Dissolved Phase Benzene Concentrations Map, May 7, 2004, from Second Quarter 2004 Fluid Level Monitoring and Sampling Report, dated June 4, 2004 by TRC.

Figure 5 – Dissolved Phase MTBE Concentrations Map, May 7, 2004, from Second Quarter 2004 Fluid Level Monitoring and sampling Report, dated June 4, 2004 by TRC.

cc: Thomas Kosel, ConocoPhillips (hard copy and electronic upload)





CLAREMONT AVENUE

0 4

NOTES:

Contour lines are interpretive and based on laboratory analysis results of groundwater samples. TPPH = total purgeoble petroleum hydrocarbons.
µg/l = micrograms per liter. ND = not detected at limit indicated on official laboratory report.
UST = underground storage tank. Results obtained using EPA Method 8260B.

TRC

LEGEND

Dissolved—Phase TPPH Contour (µg/I)


DISSOLVED-PHASE TPPH CONCENTRATIONS MAP May 7, 2004

SCALE (FEET)


76 Station 0018 6201 Claremont Avenue Oakland, California

FIGURE 3

THE CONTRACTOR AND A SECOND



CLAREMONT AVENUE



NOTES:

B = benzene. µg/l = micrograms per liter.

ND = not detected at limit indicated on official laboratory report. UST = underground storage tank.

Results obtained using EPA Method 8260B.

3 9000 000

TRC

LEGEND

MW-3
Monitoring Well with
Dissolved—Phase
Benzene Concentrations
(µg/1)


DISSOLVED-PHASE BENZENE CONCENTRATIONS MAP May 7, 2004

76 Station 0018 6201 Claremont Avenue Oakland, California

FIGURE 4

Graphics on Ir1(Ii;)\GRAPHICS\Projects By...\20-xxxx\20-0400\x-0000\0018\0018+/0018qms.dwg 5/27/05 dml

1.1 0018 001



CLAREMONT AVENUE

SCALE (FEET)

NOTES:

Contour lines are interpretive and based on laboratory analysis results of groundwater samples. MTBE = methyl tertiory butyl ether. $\mu g/l = \text{micrograms per liter.}$ ND = not detected at limit indicated on official laboratory report. UST = underground storage lank. Results obtained using EPA Method 8260B.

TRC

LEGEND

MW-3

Monitoring Well with
Dissolved-Phase
MTBE Concentrations
(μg/l)

Dissolved—Phase
MTBE Contour (µg/l)

DISSOLVED-PHASE MTBE CONCENTRATIONS MAP May 7, 2004

76 Station 0018 6201 Claremont Avenue Oakland, California

FIGURE 5

Graphics on Ir1(ii:)\GRAPHICS\Projects By...\20-xxxx\20-0400\x-0000\0018\0018+/0018qms.dwg 5/27/05 dml

网络拉拉 法基础分配



March 10, 2004

ConocoPhillips Company 76 Broadway Sacramento, CA 95818

ATTN:

MR. THOMAS H. KOSEL

SITE:

76 STATION 0018

6201 CLAREMONT AVENUE OAKLAND, CALIFORNIA

RE:

QUARTERLY MONITORING REPORT JANUARY THROUGH MARCH 2004

Dear Mr. Kosel:

Please find enclosed our Quarterly Monitoring Report for 76 Station 0018, located at 6201 Claremont Avenue, Oakland, California. If you have any questions regarding this report, please call us at (949) 753-0101.

Sincerely,

TRC

Anju Farfan

QMS Operations Manager

CC:

Mr. Don Huang, Alameda County Health Care Service Division

Barbara Moed, TRC

Enclosures

20-0400/0018R02.QMS





FIRST QUARTER 2004 FLUID LEVEL MONITORING AND GROUNDWATER SAMPLING REPORT

March 10, 2004

76 STATION 0018 6201 Claremont Avenue Oakland, California

Prepared For:

Mr. Thomas H. Kosel CONOCOPHILLIPS COMPANY 76 Broadway Sacramento, California 95818

By:

Senior Project Geologist, Irvine Operations

GROUNDWATER MONITORING REPORT

	LIST OF ATTACHMENTS
Summary Sheet	Summary of Gauging and Sampling Activities
Tables	Table Key Table 1: Summary of Groundwater Levels and Chemical Analysis Results Table 2: Historic Groundwater Levels and Chemical Analysis Results Table 3: Summary of Additional Chemical Analysis Results
Figures	Figure 1: Vicinity Map Figure 2: Groundwater Elevation Contour Map Figure 3: Dissolved-Phase Hydrocarbon Concentration Map
Graphs	Benzene Concentrations vs. Time Hydrographs
Field Activities	General Field Procedures Groundwater Sampling Field Notes
Laboratory Reports	Official Laboratory Reports Quality Control Reports Chain of Custody Records
Statements	Purge Water Transport and Disposal Limitations

Summary of Gauging and Sampling Activities January 2004 through March 2004 76 Station 0018 6201 Claremont Boulevard Oakland, CA

Oakiand, CA	
formation:	
Site:	76 Station 6201 Claremont Boulevard Oakland, CA
Project Coordinator/Phone Number:	Thomas H. Kosel/916-558-7666
Groundwater wells onsite:	3
Groundwater wells offsite:	0
ctivity:	
Sampling consultant:	TRC
Date(s) sampled:	1/29/2004
Groundwater wells gauged:	3
Groundwater wells sampled:	3
Purging method:	diaphragm pump
Treatment/disposal method during sampling event:	Onyx/Rodeo Unit 100
Free product pumpouts other than sampling event:	No
Treatment/Disposal method during free product pumpouts:	N/A
rdrogeology:	
Minimum depth to groundwater (feet bgs):	17.51
Maximum depth to groundwater (feet bgs):	18.73
Average groundwater elevation (feet relative to mean sea level):	191.12
Average change in groundwater elevations since previous event (feet):	4.15
Groundwater gradient and flow direction:	0.012 ft/ft, Southwest
Previous gradient and/or flow direction (and date):	0.008 ft/ft, Southwest (11/13/2003)
twater Condition (Benzene Maximum Contaminant Level [MCL] = 1.0 με	g/l)
Wells with benzene concentrations below MCL:	3
Wells with benzene concentrations at or above MCL:	0
Minimum benzene concentration (ug/l):	ND
Minimum benzene concentration (µg/l): Maximum benzene concentration (µg/l):	ND 0.5
Maximum benzene concentration (μg/l):	0.5
Maximum benzene concentration (μg/l): Minimum MTBE concentration (μg/l):	0.5 ND
Maximum benzene concentration (µg/l): Minimum MTBE concentration (µg/l): Maximum MTBE concentration (µg/l):	0.5
Maximum benzene concentration (µg/l): Minimum MTBE concentration (µg/l): Maximum MTBE concentration (µg/l): Minimum TPPH concentration (µg/l):	0.5 ND
Maximum benzene concentration (µg/l): Minimum MTBE concentration (µg/l): Maximum MTBE concentration (µg/l):	0.5 ND 44
Maximum benzene concentration (µg/l): Minimum MTBE concentration (µg/l): Maximum MTBE concentration (µg/l): Minimum TPPH concentration (µg/l):	0.5 ND 44 ND
Maximum benzene concentration (μg/l): Minimum MTBE concentration (μg/l): Maximum MTBE concentration (μg/l): Minimum TPPH concentration (μg/l): Maximum TPPH concentration (μg/l):	0.5 ND 44 ND 520 (MW-1)

This report presents the results of groundwater monitoring and sampling activities performed by TRC. Please contact the primary consultant for other specific information on this site.

Additional Information:

TABLES

TABLE KEY

ABBREVIATIONS / SYMBOLS

LPH = liquid-phase hydrocarbons

 $\mu g/l$ = micrograms per liter mg/l = milligrams per liter

ND = not detected at or above laboratory detection limit

DTSC = Department of Toxic Substances Control

N/A = not applicable

Trace = less than 0.01 foot of LPH in well

USTs = underground storage tanks

-- e not analyzed, measured, or collected

TPH-G = total petroleum hydrocarbons with gasoline distinction
BTEX = benzene, toluene, ethylbenzene, and total xylenes
TPH-D = total petroleum hydrocarbons with diesel distinction

TRPH = total recoverable petroleum hydrocarbons

MTBE = methyl tertiary butyl ether
TAME = tertiary amyl methyl ether
ETBE = ethyl tertiary butyl ether

DIPE = di-isopropyl ether
TBA = tertiary butyl alcohol
1,1-DCA = 1,1-Dichloroethane
1,2-DCA = 1,2-Dichloroethane
1,1-DCE = 1,1-Dichloroethene

1,2-DCE = cis- and trans-1,2-Dichloroethene

PCE = tetrachloroethene TCA = trichloroethane TCE = trichloroethene

PCB = polychlorinated biphenyls

TPPH = total purgeable petroleum hydrocarbons

NOTES

Elevations are in feet above mean sea level.

Groundwater elevation for wells with LPH is calculated as follows:

Surface elevation – depth to water + (0.75 x LPH thickness).

Concentration Graphs have been modified to plot non-detect results at the reporting limit stated in the official laboratory report. All non-detect results prior to the Second Quarter 2000 were plotted at $0.1 \,\mu g/l$ for graphical display.

J = estimated concentration, value is between the Method Detection Limit (MDL) and the Practical Quantitation Limit (PQL)

REFERENCE

TRC began groundwater monitoring and sampling activities in October 2003. Historical data for 76 Station 0018 was provided by Gettler-Ryan Inc., Dublin, California, in an excel table received in September 2003.

Table 1
SUMMARY OF GROUNDWATER LEVELS AND CHEMICAL ANALYSIS RESULTS
January 29, 2004
76 Station 0018

Date Sampled	TOC Elevation	Depth to Water	LPH Thickness		Change in Elevation	TPH-G	TPPH 8260B	Benzene	Toluene	Ethyl- benzene	Total Xylenes	MTBE 8021B	MTBE 8260B	Comments
				Elevation										
	(feet)	(feet)	(feet)	(feet)	(feet)	(µg/l)	(µg/l)	(μg/l)	(μg/l)	(μg/l)	(μg/l)	(µg/l)	(μg/l)	
MW-1		(Screen I	nterval in fe	et: 10.0-3	0.0)									
1/29/04	208.15	17.51	0.00	190.64	4.01		520	ND<0.50	ND<0.50	ND<0.50	ND<1.0		44	
MW-2		(Screen I	nterval in fe	et: 10.0-3	0.0)									
1/29/04	210.27	18.73	0.00	191.54	4.29		ND<50	0.50	ND<0.50	ND<0.50	ND<1.0		ND<2.0	
MW-3		(Screen I	nterval in fe	et: 10.0-3	0.0)									
1/29/04	208.98	17.79	0.00	191.19	4.14		ND<50	ND<0.50	ND<0.50	ND<0.50	ND<1.0		ND<2.0	

Table 2
HISTORIC GROUNDWATER LEVELS AND CHEMICAL ANALYSIS RESULTS
August 2000 Through January 2004

76 Station 0018

Date Sampled	TOC Elevation	Depth to Water	LPH Thickness		Change in Elevation	TPH-G	TPPH 8260B	Benzene	Toluene	Ethyl- benzene	Total Xylenes	MTBE 8021B	MTBE 8260B	Comments
	(feet)	(feet)	(feet)	(feet)	(feet)	(μg/l)	(µg/1)	$(\mu g/l)$	(μg/l)	$(\mu g/l)$	$(\mu g/l)$	(μg/l)	(μg/l)	
MW-1	(3)	Screen Inte	erval in feet	t: 10.0-30.	0)				, ,					
2/9/0	208.15	20.16	0.00	187.99		330		1.3	ND	1.0	4.6	140	150	
5/11/0	1 208.15	17.68	0.00	190.47	2.48	1250		ND	ND	ND	ND	145	122	
8/10/0	1 208.15	20.38	0.00	187.77	-2.70	580		ND<0.50	ND<0.50	ND<0.50	ND<0.50	110	150	
11/7/0	1 208.15	22.68	0.00	185.47	-2.30	250		ND<0.50	1.5	ND<0.50	ND<0.50	120	100	
2/6/02	2 208.15	16.20	0.00	191.95	6.48	790		ND<2.5	12	8.8	ND<2.5	90	72	
5/8/02	208.15	17.54	0.00	190.61	-1.34	890		ND<2.5	ND<2.5	ND<2.5	ND<2.5	87	81	
8/9/02	208.15	20.21	0.00	187.94	-2.67	450		ND<0.50	ND<0.50	ND<0.50	ND<1.0	100	100	
11/29/0	208.15	22.33	0.00	185.82	-2.12	110		ND<0.50	ND<0.50	ND<0.50	ND<1.0	72	72	
2/3/03	208.15	16.41	0.00	191.74	5.92	540		ND<0.50	ND<0.50	ND<0.50	ND<1.0	4 0	40	
5/5/03	208.15	16.09	0.00	192.06	0.32	670		ND<2.5	ND<2.5	ND<2.5	ND<5.0	57	57	
9/4/03		21.46	0.00	186.69	- 5.37									No analysis; past holding time
11/13/0		21.52	0.00	186.63	-0.06	•••	97	ND<0.50	5.0	0.82	3.5		29	
1/29/0	4 208.15	17.51	0.00	190.64	4.01		520	ND<0.50	ND<0.50	ND<0.50	ND<1.0		44	
MW-2			erval in feet	: 10.0-30.	0)									
8/24/0		19.69	0.00	190.58	••	ND		ND	ND	ND	ND	ND	ND	
11/16/0		21.61	0.00	188.66	-1.92	ND		ND	ND	ND	ND	ND	ND	
2/9/01				188.75	0.09	ND		ND	ND	ND	ND	ND	ND	
5/11/0				191.51	2.76	ND		ND	ND	ND	ND	ND	ND	
8/10/0				188.62	-2.89	ND<50		ND<0.50	ND<0.50	ND<0.50		ND<5.0	ND<2.0	
11/7/0				186.02	-2.60	ND<50			ND<0.50		ND<0.50	ND<5.0	ND<1.0	
2/6/02				192.05	6.03	ND<50				ND<0.50		ND<2.5		
5/8/02				191.64		ND<50				ND<0.50		ND<5.0		
8/9/02				188.74		ND<50			ND<0.50		ND<1.0	ND<2.0	ND<2.0	
11/29/0				186.54		ND<50			ND<0.50		ND<1.0	ND<2.0	ND<2.0	
2/3/03	210.27	17.43	0.00	192.84	6.30	ND<50		ND<0.50	ND<0.50	ND<0.50	ND<1.0	ND<2.0	ND<2.0	

Page 1 of 2

Date Sampled	TOC Elevation	Depth to Water	LPH Thickness	Ground- water Elevation	Change in Elevation	TPH-G	TPPH 8260B	Benzene	Toluene	Ethyl- benzene	Total Xylenes	MTBE 8021B	MTBE 8260B	Comments -
	(feet)	(feet)	(feet)	(feet)	(feet)	(μg/l)	(µg/l)	(µg/l)	(μg/l)	(μg/l)	(µg/l)	(μ g /l)	$(\mu g/I)$	
	continued													
5/5/03	210.27	17.15	0.00	193.12	0.28	ND<50		ND<0.50	ND<0.50	ND<0.50	ND<1.0	ND<2.0	ND<2.0	
9/4/03	210.27	22.75	0.00	187.52	-5.60				'					No analysis; past holding time
11/13/0	3 210.27	23.02	0.00	187.25	-0.27		ND<50	ND<0.50	ND<0.50	ND<0.50	ND<1.0		ND<2.0	
1/29/04	4 210.27	18.73	0.00	191.54	4.29	 ,	ND<50	0.50	ND<0.50	ND<0.50	ND<1.0		ND<2.0	
MW-3	(S	creen Inte	erval in feet	: 10.0-30.0))									
8/24/00	208.98	18.68	0.00	190.30		ND		ND	ND	ND	ND	4.7/2.32	2.3	
11/16/0	0 208.98	20.56	0.00	188.42	-1.88	ND		ND	ND	ND	ND	ND	ND	
2/9/01	208.98	20.45	0.00	188.53	0.11	ND		ND	ND	ND	ND	ND	ND	
5/11/01	208.98	17.75	0.00	191.23	2.70	ND		ND	ND	ND	ND	ND	ND	
8/10/01	208.98	20.70	0.00	188.28	-2.95	ND<50		ND<0.50	ND<0.50	ND<0.50	ND<0.50	ND<5.0	ND<2.0	
11/7/01	208.98	23.02	0.00	185.96	-2.32	ND<50		ND<0.50	ND<0.50	ND<0.50	ND<0.50	ND<5.0	1.5	
2/6/02	208.98	17.19	0.00	191.79	5.83	ND<50		ND<0.50	ND<0.50	ND<0.50	ND<0.50	ND<2.5		
5/8/02	208.98	17.59	0.00	191.39	-0.40	ND<50		ND<0.50	ND<0.50	ND<0.50	ND<0.50	ND<5.0		
8/9/02	208.98	20.48	0.00	188.50	-2.89	ND<50		ND<0.50	ND<0.50	ND<0.50	ND<1.0	ND<2.0	ND<2.0	
11/29/0	2 208.98	22.64	0.00	186.34	-2.16	ND<50		ND<0.50	ND<0.50	ND<0.50	ND<1.0	ND<2.0	ND<2.0	
2/3/03	208.98	16.46	0.00	192.52	6.18	ND<50		ND<0.50	ND<0.50	ND<0.50	ND<1.0	ND<2.0	ND<2.0	
5/5/03	208.98	16.16	0.00	192.82	0.30	ND<50		ND<0.50	ND<0.50	ND<0.50	ND<1.0	2.6	2.6	
9/4/03	208.98	21.71	0.00	187.27	-5.55									No analysis; past holding time
11/13/0	3 208.98	21.93	0.00	187.05	-0.22		ND<50	ND<0.50	ND<0.50	ND<0.50	ND<1.0		ND<2.0	
1/29/04	4 208.98	17.79	0.00	191.19	4.14	**	ND<50	ND<0.50	ND<0.50	ND<0.50	ND<1.0		ND<2.0	


Table 3
SUMMARY OF ADDITIONAL CHEMICAL ANALYSIS RESULTS
76 Station 0018

Date Sampled	EDC	EDB	TAME 8260B	TBA 8260B	DIPE 8260B	ETBE 8260B	Ethanol 8015B	Ethanol 8260B	1,2 DCE		
	(μg/l)	(µg/l)	(μg/l)	(µg/l)	(µg/l)	(μg/l)	(mg/l)	(μg/l)	(µg/l)		
MW-1											
2/9/01		ND	ND	ND	ND	ND		ND	ND		
5/11/01		ND	ND	ND	ND	ND		ND	ND		
8/10/01		ND<2.0	ND<2.0	ND<100	ND<2.0	ND<2.0		ND<1,000	ND<2.0		
11/7/01		ND<1.0	ND<1.0	ND<20	ND<1.0	ND<1.0		ND<500	ND<1.0		
2/6/02		ND<2.0	ND<2.0	ND<100	ND<2.0	ND<2.0		ND<500	ND<2.0		
5/8/02		ND<2.0	ND<2.0	ND<100	ND<2.0	ND<2.0		ND<500	ND<2.0		
8/9/02		ND<2.0	ND<2.0	ND<100	ND<2.0	ND<2.0		ND<500	ND<2.0		
11/29/02		ND<2.0	ND<2.0	ND<100	ND<2.0	ND<2.0		ND<500	ND<2.0		
2/3/03		ND<2.0	ND<2.0	ND<100	ND<2.0	ND<2.0		ND<500	ND<2.0		
5/5/03		ND<10	ND<10	ND<500	ND<10	ND<10		ND<2,500	ND<10		
11/13/03	ND<2.0	ND<2.0	ND<2.0	ND<100	ND<2.0	ND<2.0		ND<500			
1/29/04	ND<2.0	ND<2.0	ND<2.0	ND<100	ND<2.0	ND<2.0		ND<500			
MW-2											
8/24/00			ND	ND	ND	ND		ND			
11/16/00			ND	ND	ND	ND		ND			
2/9/01		ND	ND	ND	ND	ND		ND	ND		
5/11/01		ND	ND	ND	ND	ND		ND	ND		
8/10/01		ND<2.0	ND<2.0	ND<100	ND<2.0	ND<2.0		ND<1,000	ND<2.0		
11/7/01		ND<1.0	ND<1.0	ND<20	ND<1.0	ND<1.0		ND<500	ND<1.0		
8/9/02											
11/29/02				•==							
2/3/03											
5/5/03		••					pa 46-				
11/13/03		••					**	ND<500			
1/29/04			••					ND<500	••		

MW-3

Date Sampled	EDC	EDB	TAME 8260B	TBA 8260B	DIPE 8260B	ETBE 8260B	Ethanol 8015B	Ethanol 8260B	1,2 DCE
	(μg/l)	(µg/l)	(μg/l)	(μg/l)	(µg/l)	(μg/l)	(mg/l)	(µg/l)	(µg/l)
MW-3	continued								
8/24/00			ND	ND	ND	ND	ND		
11/16/00	**		ND	ND	ND	ND	ND		
2/9/01		~-	ND	ND	ND	ND	ND	-	
5/11/01			ND	ND	ND	ND	ND		
8/10/01		**	ND<2.0	ND<100	ND<2.0	ND<2.0	ND<1,000		**
11/7/01			ND<1.0	ND<20	ND<1.0	ND<1.0	ND<500		
8/9/02		ND		**					ND
11/29/02		ND							ND
2/3/03		ND<2.0							ND<2.0
5/5/03		ND<1.0							ND<1.0
11/13/03		**						ND<500	
1/29/04								ND<500	ri m

FIGURES





SOURCE:


United States Geological Survey 7.5 Minute Topographic Map: Oakland East & Oakland West Quadrangles






SCALE 1: 24,000

QUADRANGLE LOCATION



76 Station 0018 6201 Claremont Avenue Oakland, California

FIGURE 1



SCALE (FEET)

NOTES:

Contour lines are interpretive and based on fluid levels measured in monitoring wells. Elevations are in feet above mean sea level. UST = underground storage tank.



LEGEND

Mw-3 Monitoring Well with Groundwater Elevation (feet)


191.30 — Groundwater Elevation Contour

General Direction of Groundwater Flaw

GROUNDWATER ELEVATION CONTOUR MAP January 29, 2004

76 Station 0018 6201 Claremont Avenue Oakland, California

FIGURE 2



NOTES:

TPPH = total purgeable petroleum hydrocarbons.

B = benzene. MTBE = methyl tertiary butyl ether.

µg/l = micrograms per liter. ND = not detected at limit indicated on official laboratory report.

UST = underground storage tank. Results abtained using EPA Method 8260B.



Well No. TPPH µg/l B µg/l MTBE µg/l MTBE µg/l LEGEND Monitoring Well with Dissolved-Phase Hydrocarbon Concentrations (µg/l)


DISSOLVED-PHASE HYDROCARBON CONCENTRATIONS MAP January 29, 2004

> 76 Station 0018 6201 Claremont Avenue Oakland, California


> > FIGURE 3

GRAPHS

Graph 1
Benzene Concentrations vs. Time
76 Station 0018



Graph 2 Hydrograph 76 Station 0018



GENERAL FIELD PROCEDURES

Groundwater Monitoring and Sampling Assignments

For each site, TRC technicians are provided with a Technical Service Request (TSR) that specifies activities required to complete the groundwater monitoring and sampling assignment for the site. TSRs are based on client directives, instructions from the primary environmental consultant for the site, regulatory requirements, and TRC's previous experience with the site.

Fluid Level Measurements

Initial site activities include determination of well locations based on a site map provided with the TSR. Well boxes are opened and caps are removed. Indications of well or well box damage, or of pressure buildup in the well are noted.

Fluid levels in each well are measured using a coated cloth tape equipped with an electronic interface probe, which distinguishes between liquid phase hydrocarbon (LPH) and water. The depth to LPH (if it is present), to water, and to the bottom of the well are measured from the top of the well casing (surveyors mark or notch if present) to the nearest 0.01 foot. Unless otherwise instructed, a well with less than 0.67 foot between the measured top of water and the measured bottom of the well casing is considered dry, and is not sampled. If the well contains 0.67 foot or more of water, an attempt is made to bail and/or sample as specified on the TSR.

Wells that are found to contain LPH are not purged or sampled. Instead, one casing volume of fluid is bailed from the well and the well is re-sealed. Bailed fluids are placed in a container separate from normal purge water, and properly disposed.

Purging and Groundwater Parameter Measurement

TSR instructions may specify that a well not be purged (no-purge sampling), be purged using low-flow methods, or be purged using conventional pump and/or bail methods. Conventional purging generally consists of pumping or bailing until a minimum of three casing volumes of water have been removed or until the well has been pumped dry. Pumping is generally accomplished using submersible electric or pneumatic diaphragm pumps.

During conventional purging, three groundwater parameters (temperature, pH, and conductivity) are measured after removal of each casing volume. Stabilization of these parameters, to within 10 percent, confirm that sufficient purging has been completed. In some cases, the TSR indicates that other parameters are also to be measured during purging. TRC commonly measures dissolved oxygen (DO), oxidation-reduction potential (ORP), and/or turbidity. Instruments used for groundwater parameter measurement are calibrated daily according to manufacturer's instructions.

Low-flow purging utilizes a bladder or peristaltic pump to remove water from the well at a low rate. Groundwater parameters specified by the TSR are measured continuously until they become stable in general accordance with EPA guidelines.

Purge water is generally collected in labeled drums for disposal. Drums may be left on site for disposal by others, or transported to a collection location for eventual transfer to a licensed treatment or recycling facility. In some cases, purge water may be collected directly from the site by a licensed vacuum truck company, or may be treated on site by an active remediation system, if so directed.

Groundwater Sample Collection

After wells are purged, or not purged, according to TSR instructions, samples are collected for laboratory analysis. For wells that have been purged using conventional pump or bail methods, sampling is conducted after the well has recovered to 80 percent of its original volume or after two hours if the well does not recover to at least 80 percent. If there is insufficient recharge of water in the well after two hours, the well is not sampled.

Samples are collected by lowering a new, disposable, ½-inch to 4-inch polyethylene bottom-fill bailer to just below the water level in the well. The bailer is retrieved and the water sample is carefully transferred to containers specified for the laboratory analytical methods indicated by the TSR. Particular care is given to containers for volatile organic analysis (VOAs) which require filling to zero headspace and fitting with Teflon-sealed caps.

After filling, all containers are labeled with project number (or site number), well designation, sample date, and the samplers initials, and placed in an insulated chest with ice. Samples remain chilled prior to and during transport to a state-certified laboratory for analysis. Sample container descriptions and requested analyses are entered onto a chain-of-custody form in order to provide instructions to the laboratory. The chain-of-custody form accompanies the samples during transportation to provide a continuous record of possession from the field to the laboratory. If a freight or overnight carrier transports the samples, the carrier is noted on the form.

For wells that have been purged using low-flow methods, sample containers are filled from the effluent stream of the bladder or peristaltic pump. In some cases, if so specified by the TSR, samples are taken from the sample ports of actively pumping remediation wells.

Sequence of Gauging, Purging, and Sampling

The sequence in which monitoring activities are conducted are specified on the TSR. In general, wells are gauged beginning with the least-affected well and ending with the well that has highest concentration based on previous analytic results. After all gauging for the site is completed, wells are purged and/or sampled from the least-affected well to the most-affected well.

Decontamination

In order to reduce the possibility of cross-contamination between wells, strict isolation and decontamination procedures are observed. Portable pumps are not used in wells with LPH. Technicians wear nitrile gloves during all gauging, purging and sampling activities. Gloves are changed between wells and more often if warranted. Any equipment that could come in contact with fluids are either dedicated to a particular well, decontaminated prior to each use, or discarded after a single use. Decontamination consists of washing in a solution of Liqui-nox and water and rinsing twice. The final rinse is in deionized water.

Exceptions

Additional tasks or non-standard procedures, if any, that may be requested or required for a particular site, and noted on the site TSR, are documented in field notes on the following pages.

FIELD MONITORING DATA SHEET

6 74 4	101011	<u></u>	ъ.	24	Rades	Docs 1		Date:	1 /
Site#	0018		Project	: Manager	FXX. DGL	A MIDER		rage	0,
Weil #	Grade	тос	Total Depth	Depth to Water	Depth to Product	Product Thickness (feet)	Time Sampled		/ell Notes
MW-1		V	29.98	17.51	0	0	1128	211	
NW-2				18.73		ර	1153	2."	
mW -3		1	30.18	17.79	0	Ö	1132	2"	
	-								
	1		. 30	- 14 T					
									•
			Ì						
									• • • • • • • • • • • • • • • • • • • •
				,					
<u>.</u>	 			<u> </u>	-				
	•			<u> </u>					
					1		1		**
					1			1	· · · · · · · · · · · · · · · · · · ·
			1						
								1	
		1		 			<u> </u>		
IELD DATA	A COMPL	ETE	QA/QXC	<u> </u>	C9C	V V	VELL BOX	CONDITION S	HEETS

GROUNDWATER SAMPLING FIELD NOTES Technician: Date: //29/04 DOIF Site: Project No.: Well No.: Purge Method: D Depth to Water (feet): Depth to Product (feet): Total Depth (feet): LPH & Water Recovered (gallons): 2" Water Column (feet):__ Casing Diameter (Inches): 80% Recharge Depth (feet): 1 Well Volume (gallons): Time Depth Conduc-Temperature Time Volume рΗ D.O. Start Stop To Water Purged tivity Turbidity (F,C) (feet) (gallons) (uS/cm) 7.47 1057 2 7.00 1100 7.15 Static at Time Sampled Time Sampled Total Gallons Purged 1128 Comments: mw -Well No.: Purge Method: Depth to Water (feet): 0 Depth to Product (feet): LPH & Water Recovered (gallons): O Total Depth (feet): Water Column (feet): Casing Diameter (Inches): 80% Recharge Depth (feet): 1 Well Volume (gallons):_ Conduc-Temperature Time Time Depth Volume Start Stop To Water Purged tivity pΗ Turbidity D.O. (F(C) (gallons) (feet) (uS/cm) 11.57 1110 6.96 Static at Time Sampled Total Gallons Purged Time Sampled 132 10°-00 Comments:

GROUNDWATER SAMPLING FIELD NOTES

Well No.: Purge Method: Depth to Water (feet): Depth to Product (feet): Total Depth (feet): LPH & Water Recovered (gallons): Water Column (feet): Casing Diameter (Inches):	Site: 0618
Note	
Depth to Water (feet)	Veli No.: MA
Column (feet)	
Value Valu	otal Depth (feet):
1 Well Volume (gallons) 1 Mell Volume (gallons)	Water Column (feet):
Time Start Stop To Water Purged twity (us/cm) (F.C) pH Turbidity D.O. 11 3 9	30% Recharge Depth
Start Stop To Water (feet) (gallons) (uS/cm) (F.C) pH Turbidity D.O	
11 5 9	Start Sto
Static at Time Sampled Total Gallons Purged Time Sampled 1/5.8	
Static at Time Sampled Total Gallons Purged Time Sampled T	
Static at Time Sampled Total Gallons Purged Time Sampled 1/6-5-6 1/6-5	1) 7
Static at Time Sampled	11 -
Comments: Well No.: Purge Method: Depth to Water (feet): Depth to Product (feet): Total Depth (feet): LPH & Water Recovered (gallons): Water Column (feet): Casing Diameter (Inches): 80% Recharge Depth (feet): 1 Well Volume (gallons): Time Time Depth Volume Start Stop To Water Purged tivity pH Turbidity D.C	· · · · · · ·
Well No.: Purge Method: Depth to Water (feet): Depth to Product (feet): Total Depth (feet): LPH & Water Recovered (gallons): Water Column (feet): Casing Diameter (Inches): 80% Recharge Depth (feet): 1 Well Volume (gallons): Time	Static at Tim
Well No.: Purge Method: Depth to Water (feet): Depth to Product (feet): Total Depth (feet): LPH & Water Recovered (gallons): Water Column (feet): Casing Diameter (Inches): 80% Recharge Depth (feet): 1 Well Volume (gallons): Time	18.8
Total Depth (feet): LPH & Water Recovered (gallons): Water Column (feet): Casing Diameter (Inches): 80% Recharge Depth (feet): 1 Well Volume (gallons): Time	Well No.:
Water Column (feet): Casing Diameter (Inches): 80% Recharge Depth (feet): 1 Well Volume (gallons): Time Time Depth Volume Conductory Start Stop To Water Purged tivity pH Turbidity D.C. (feet) (gallons) (uS/cm) (F,C)	Depth to Water (feet):
80% Recharge Depth (feet):	Total Depth (feet):
Time Time Depth Volume Conductor Temperature Start Stop To Water Purged tivity pH Turbidity D.C. (feet) (gallons) (uS/cm) (F,C)	Water Column (feet):
Start Stop To Water Purged tivity pH Turbidity D.C (feet) (gallons) (uS/cm) (F,C)	80% Recharge Depth
	2.3 September 12 (2.36)
	: :
	<u>'</u>
Static at Time Sampled Total Gallons Purged Time Sampled	
	Static at Tin
Comments:	
	Static at Tin



TRC Alton Geoscience

February 12, 2004

21 Technology Drive Irvine, CA 92718

Attn.:

Anju Farfan

Project#: 41050001FA20

Project:

Conoco Phillips #0018

Site:

6201 Claremont Blvd., Oakland

Attached is our report for your samples received on 01/30/2004 15:17 This report has been reviewed and approved for release. Reproduction of this report is permitted only in its entirety.

Please note that any unused portion of the samples will be discarded after 03/15/2004 unless you have requested otherwise.


We appreciate the opportunity to be of service to you. If you have any questions, please call me at (925) 484-1919.

You can also contact me via email. My email address is: dsharma@stl-inc.com

Sincerely,

Dimple Sharma **Project Manager**

Laema





TRC Alton Geoscience

Attn.: Anju Farfan

21 Technology Drive Irvine, CA 92718

Phone: (949) 341-7440 Fax: (949) 753-0111

Project: 41050001FA20


Conoco Phillips #0018

Received: 01/30/2004 15:17

Site: 6201 Claremont Blvd., Oakland

Samples Reported

Sample Name	Date Sampled	Matrix	Lab#
MVV-1	01/29/2004 11:28	Water	1
MW-2	01/29/2004 11:53	Water	2
MW-3	01/29/2004 11:32	Water	3





TRC Alton Geoscience

Attn.: Anju Farfan

21 Technology Drive Irvine, CA 92718

Phone: (949) 341-7440 Fax: (949) 753-0111

Project: 41050001FA20

Conoco Phillips #0018

Received: 01/30/2004 15:17

Site: 6201 Claremont Blvd., Oakland

Prep(s):

5030B

Test(s):

8260FAB

Sample ID: MW-1

Lab ID:

2004-01-0820 - 1

Sampled:

01/29/2004 11:28

Extracted:


2/9/2004 23:16

Matrix:

Water

QC Batch#: 2004/02/09-2B.69

Compound	Conc.	RL	Unit	Dilution	Analyzed	Flag
Gasoline	520	50	ug/L	1.00	02/09/2004 23:16	g
Benzene	ND	0.50	ug/L	1.00	02/09/2004 23:16	
Toluene	ND	0.50	ug/L	1.00	02/09/2004 23:16	
Ethylbenzene	ND	0.50	ug/L	1.00	02/09/2004 23:16	
Total xylenes	ND	1.0	ug/L	1.00	02/09/2004 23:16	
tert-Butyl alcohol (TBA)	ND	100	ug/L	1.00	02/09/2004 23:16	
Methyl tert-butyl ether (MTBE)	44	2.0	ug/L	1.00	02/09/2004 23:16	
Di-isopropyl Ether (DIPE)	ND	2.0	ug/L	1.00	02/09/2004 23:16	
Ethyl tert-butyl ether (ETBE)	ND	2.0	ug/L	1.00	02/09/2004 23:16	
tert-Amyl methyl ether (TAME)	ND	2.0	ug/L	1.00	02/09/2004 23:16	
1,2-DCA	ND	2.0	ug/L	1.00	02/09/2004 23:16	
EDB	ND	2.0	ug/L	1.00	02/09/2004 23:16	
Ethanol	ND	500	ug/L	1.00	02/09/2004 23:16	
Surrogate(s)						
Toluene-d8	98.4	88-110	%	1.00	02/09/2004 23:16	
1,2-Dichloroethane-d4	108.9	76-114	%	1.00	02/09/2004 23:16	





TRC Alton Geoscience

Attn.: Anju Farfan

21 Technology Drive Irvine, CA 92718

Phone: (949) 341-7440 Fax: (949) 753-0111

Project: 41050001FA20

Conoco Phillips #0018

Received: 01/30/2004 15:17

Site: 6201 Claremont Blvd., Oakland

Prep(s): 5030B

Test(s):

8260FAB

Sample ID: MW-2

Lab ID:

2004-01-0820 - 2

Sampled: 01/29/2004 11:53


Extracted:

2/9/2004 23:35

Matrix: Water

QC Batch#: 2004/02/09-2B.69

Compound	Conc.	RL	Unit	Dilution	Analyzed	Flag
Gasoline	ND	50	ug/L	1.00	02/09/2004 23:35	
Benzene	0.50	0.50	ug/L	1.00	02/09/2004 23:35	
Toluene	ND	0.50	ug/L	1.00	02/09/2004 23:35	
Ethylbenzene	ND	0.50	ug/L	1.00	02/09/2004 23:35	
Total xylenes	ND	1.0	ug/L	1.00	02/09/2004 23:35	
Methyl tert-butyl ether (MTBE)	ND	2.0	ug/L	1.00	02/09/2004 23:35	
Ethanol	ND	500	ug/L	1.00	02/09/2004 23:35	
Surrogate(s)						
Toluene-d8	95.9	88-110	%	1.00	02/09/2004 23:35	
1,2-Dichloroethane-d4	108.8	76-114	%	1.00	02/09/2004 23:35	





TRC Alton Geoscience

Attn.: Anju Farfan

21 Technology Drive Irvine, CA 92718

Phone: (949) 341-7440 Fax: (949) 753-0111

Project: 41050001FA20

Conoco Phillips #0018

Received: 01/30/2004 15:17

Site: 6201 Claremont Blvd., Oakland

Prep(s): 5030B

Sample ID: MW-3

Sampled: 01/29/2004 11:32

Matrix:

Water

Test(s):

8260FAB

Lab ID: Extracted: 2004-01-0820 - 3 2/11/2004 12:51

QC Batch#: 2004/02/11-1A.65

Compound	Conc.	RL	Unit	Dilution	Analyzed	Flag
Gasoline	ND	50	ug/L	1.00	02/11/2004 12:51	
Benzene	ND	0.50	ug/L	1.00	02/11/2004 12:51	
Toluene	ND	0.50	ug/L	1.00	02/11/2004 12:51	
Ethylbenzene	ND	0.50	ug/L	1.00	02/11/2004 12:51	
Total xylenes	ND	1.0	ug/L	1.00	02/11/2004 12:51	
Methyl tert-butyl ether (MTBE)	ND	2.0	ug/L	1.00	02/11/2004 12:51	
Ethanol	ND	500	ug/L	1.00	02/11/2004 12:51	
Surrogate(s)						
Toluene-d8	97.3	88-110	%	1.00	02/11/2004 12:51	
1,2-Dichloroethane-d4	106.4	76-114	%		02/11/2004 12:51	



Gas/BTEX Fuel Oxygenates by 8260B

TRC Alton Geoscience Attn.: Anju Farfan

21 Technology Drive Irvine, CA 92718

Phone: (949) 341-7440 Fax: (949) 753-0111

Project: 41050001FA20

Conoco Phillips #0018

Received: 01/30/2004 15:17

Site: 6201 Claremont Blvd., Oakland

Batch QC Report

Prep(s): 5030B Method Blank

MB: 2004/02/09-2B.69-008

Water

Test(s): 8260FAB QC Batch # 2004/02/09-2B.69

Date Extracted: 02/09/2004 18:08

Compound	Conc.	RL	Unit	Analyzed	Flag
Gasoline	ND	50	ug/L	02/09/2004 18:08	
Benzene	ND	0.5	ug/L	02/09/2004 18:08	
Toluene	ND	0.5	ug/L	02/09/2004 18:08	
Ethylbenzene	ND	0.5	ug/L	02/09/2004 18:08	
Total xylenes	ND	1.0	ug/L	02/09/2004 18:08	
tert-Butyl alcohol (TBA)	ND	100	ug/L	02/09/2004 18:08	
Methyl tert-butyl ether (MTBE)	ND	2.0	ug/L	02/09/2004 18:08	
Di-isopropyl Ether (DIPE)	ND	2.0	ug/L	02/09/2004 18:08	
Ethyl tert-butyl ether (ETBE)	ND	2.0	ug/L	02/09/2004 18:08	
tert-Amyl methyl ether (TAME)	ND	2.0	ug/L	02/09/2004 18:08	
1,2-DCA	ND	2.0	ug/L	02/09/2004 18:08	
EDB	ND	2.0	ug/L	02/09/2004 18:08	
Ethanol	ND	500	ug/L	02/09/2004 18:08	
Surrogates(s)	1				
1,2-Dichloroethane-d4	95.3	76-114	1 %	02/09/2004 18:08	
Toluene-d8	96.3	88-110	%	02/09/2004 18:08	



Gas/BTEX Fuel Oxygenates by 8260B

TRC Alton Geoscience Attn.: Anju Farfan

21 Technology Drive Irvine, CA 92718

Phone: (949) 341-7440 Fax: (949) 753-0111

Project: 41050001FA20

Conoco Phillips #0018

Received: 01/30/2004 15:17

Site: 6201 Claremont Blvd., Oakland

Batch QC Report

Prep(s): 5030B Method Blank

Water

Test(s): 8260FAB QC Batch # 2004/02/11-1A.65

MB: 2004/02/11-1A.65-030

Date Extracted: 02/11/2004 11:30

Compound	Conc.	RL	Unit	Analyzed	Flag
Gasoline	ND	50	ug/L	02/11/2004 11:30	
tert-Butyl alcohol (TBA)	ND	100	ug/L	02/11/2004 11:30	
Methyl tert-butyl ether (MTBE)	ND	2.0	ug/L	02/11/2004 11:30	
Di-isopropyl Ether (DIPE)	ND	2.0	ug/L	02/11/2004 11:30	
Ethyl tert-butyl ether (ETBE)	ND	2.0	ug/L	02/11/2004 11:30	
tert-Amyl methyl ether (TAME)	ND	2.0	ug/L	02/11/2004 11:30	
1,2-DCA	ND	2.0	ug/L	02/11/2004 11:30	
EDB	ND	2.0	ug/L	02/11/2004 11:30	
Benzene	ND	0.5	ug/L	02/11/2004 11:30	
Toluene	ND	0.5	ug/L	02/11/2004 11:30	
Ethylbenzene	ND	0.5	ug/L	02/11/2004 11:30	
Total xylenes	ND	1.0	ug/L	02/11/2004 11:30	
Ethanol	ND	500	ug/L	02/11/2004 11:30	
Surrogates(s)					
1,2-Dichloroethane-d4	109.6	76-114	%	02/11/2004 11:30	
Toluene-d8	100.8	88-110	%	02/11/2004 11:30	



Gas/BTEX Fuel Oxygenates by 8260B

TRC Alton Geoscience Attn.: Anju Farfan

21 Technology Drive Irvine, CA 92718

Phone: (949) 341-7440 Fax: (949) 753-0111

Project: 41050001FA20

Conoco Phillips #0018

Received: 01/30/2004 15:17

Site: 6201 Claremont Blvd., Oakland

Batch QC Report

Water

Prep(s): 5030B

Test(s): 8260FAB

Laboratory Control Spike

2004/02/09-2B.69-031

QC Batch # 2004/02/09-2B.69

LCSD

2004/02/09-28.69-031

Extracted: 02/09/2004 Extracted: 02/09/2004 Analyzed: 02/09/2004 17:31 Analyzed: 02/09/2004 17:49

Compound	Conc. ug/L		Exp.Conc.	Recovery %		RPD	Ctrl.Limits %		Flags	
•	LCS	LCSD		LCS	LCSD	%	Rec.	RPD	LCS	LCSD
Benzene Toluene Methyl tert-butyl ether (MTBE)	22.6 23.1 26.7	24.8 25.1 28.5	25 25 25	90.4 92.4 106.8	99.2 100.4 114.0	9.3 8.3 6.5	69-129 70-130 65-165	20 20 20		
Surrogates(s) 1,2-Dichloroethane-d4 Toluene-d8	460 477	459 474	500 500	92.0 95.4	91.8 94.8		76-114 88-110			



Gas/BTEX Fuel Oxygenates by 8260B

TRC Alton Geoscience

Attn.: Anju Farfan

21 Technology Drive Irvine, CA 92718

Phone: (949) 341-7440 Fax: (949) 753-0111

Project: 41050001FA20

Conoco Phillips #0018

Received: 01/30/2004 15:17

Site: 6201 Claremont Blvd., Oakland

Batch QC Report

Prep(s): 5030B

Test(s): 8260FAB

Laboratory Control Spike

Water

QC Batch # 2004/02/11-1A.65

LCS

2004/02/11-1A.65-045

Extracted: 02/11/2004

Analyzed: 02/11/2004 10:45

LCSD 2004/02/11-1A.65-007

Extracted: 02/11/2004

Analyzed: 02/11/2004 11:07

Compound	Conc. ug/L		Exp.Conc.	Recovery %		RPD	Ctrl.Limits %		Flags	
	LCS	LCSD		LCS	LCSD	%	Rec.	RPD	LCS	LCSD
Methyl tert-butyl ether (MTBE) Benzene Toluene	24.0 21.6 23.2	23.7 22.4 23.4	25 25 25	96.0 86.4 92.8	94.8 89.6 93.6	1.3 3.6 0.9	65-165 69-129 70-130	20 20 20		
Surrogates(s) 1,2-Dichloroethane-d4 Toluene-d8	519 525	507 507	500 500	103.8 105.0	101.4 101.4		76-114 88-110			



Gas/BTEX Fuel Oxygenates by 8260B

TRC Alton Geoscience

Attn.: Anju Farfan

21 Technology Drive Irvine, CA 92718

Phone: (949) 341-7440 Fax: (949) 753-0111

Project: 41050001FA20

Conoco Phillips #0018

Received: 01/30/2004 15:17

Site: 6201 Claremont Blvd., Oakland

Legend and Notes

Result Flag

g

Hydrocarbon reported in the gasoline range does not match our gasoline standard.

STL-San Francisco 4-01-0820 ConocoPhillips Chain Of Custody Record ConocoPhillips Site Manager: ConocoPhillips Work Order Number 1220 Quarry Lane INVOICE REMITTANCE ADDRESS: CONOCOPHILLIPS Pleasanton, CA 94566 Attn: Dee Hutchinson ConocoPhillips Cost Object 3611 South Harbor, Suite 200 (925) 484-1919 (925) 484-1096 fax Santa Ana, CA. 92704 SAMPLING COMPANY: Valld Value ID: TRC TOGOOLOZZ31 ADDRESS: 21 Technology Drive, Irvine CA 92618 6201 Claremont Blvd. Oakland PROJECT CONTACT (Hardcopy or PDF Report to): Aniu Farfan LAB USE ONLY TELEPHONE: Peter Thomson, TRC 949-341-7408 949-341-7440 949-753-0111 afarfan@trcsolutions.com pthomson@tresolutions.com SAMPLER NAME(S) (Print): Lyde// CONSULTANT PROJECT NUMBER **REQUESTED ANALYSES** Max Eckstein 41050001/FA20 TURNAROUND TIME (CALENDAR DAYS): 2 14 DAYS ☐ 7 DAYS ☐ 72 HOURS ☐ 48 HOURS ☐ 24 HOURS ☐ LESS THAN 24 HOURS 8015M / 8021B - TPHg/BTEX/MtBE DSTLC OTCLP FIELD NOTES: SPECIAL INSTRUCTIONS OR NOTES: CHECK BOX IF EDD IS NEEDED 8260B - TPHg/BTEX/MtBE Container/Preservative 8270C - Semi-Volatiles or PID Readings or Laboratory Notes Total * Field Point name only required if different from Sample ID Lead Sample Identification/Field Point SAMPLING NO. OF TEMPERATURE ON RECEIPT C° CONT. Name* DATE TIME Received by: (Signature) Received by: (Signature)

STATEMENTS

Purge Water Transport and Disposal

Non-hazardous groundwater produced during purging and sampling was accumulated at TRC's groundwater monitoring facility at Concord, California, for transportation by Onyx Transportation, Inc., to the ConocoPhillips Refinery at Rodeo, California. Disposal at the Rodeo facility was authorized by ConocoPhillips in accordance with "ESD Standard Operating Procedures – Water Quality and Compliance", as revised on February 7, 2003. Documentation of compliance with ConocoPhillips requirements is provided by an ESD Form R-149, which is on file at TRC's Concord Office. Purge water suspected of containing potentially hazardous material, such as liquid-phase hydrocarbons, was accumulated separately in a drum for transportation and disposal by Filter Recycling, Inc.

Limitations

The fluid level monitoring and groundwater sampling activities summarized in this report have been performed under the responsible charge of a California Registered Geologist or Registered Civil Engineer and have been conducted in accordance with current practice and the standard of care exercised by geologists and engineers performing similar tasks in this area. No warranty, express or implied, is made regarding the conclusions and professional opinions presented in this report. The conclusions are based solely upon an analysis of the observed conditions. If actual conditions differ from those described in this report, our office should be notified.