### cook

271 Las Juntas Way, Walnut Creek, CA 94597 Phone 925.937.1759 Cell 925.787.6869 cookenvironmental@att.net

June 12, 2006

Don Hwang
Alameda County Environmental Health
1311 Harbor Bay Pkwy, Ste 250
Alameda, California 94502-6577

Subject: Response to Technical Comments and Work Plan for Additional Lite Investigation

Express Cas & Mart 2951 High Street Oakland Express Gas & Mart, 2951 High Street, Oakland LOP Case No. 1038

Dear Mr. Hwang:

Enclosed is the Response to Technical Comments and Work Plan for Additional Site Investigation for the subject LUFT site. This report is submitted in response to your May 5, 2006 letter to Mr. Aziz Kandahari, the former owner and responsible party, requesting additional information to review case closure.

A Quarterly Monitoring Report will be submitted under separate cover documenting the most recent groundwater sampling event on May 24, 2006. One minor omission was made from the enclosed report. In technical comment #2 you requested the date the current tank system became operational. The current tank system became operation in October 2001.

We are prepared to implement the work plan to drill three soil borings downgradient of the existing UST as soon as you grant approval. Please call me at (925) 937-1759 if you have any questions in regard to this report.

Very truly yours,

Cook Environmental Services, Inc.

Tim Cook, P.E., CEG

Principal

cc: Aziz Kandahari, Express Gas & Mart Mark Owens, UST Cleanup Fund Cherie McCaulou, San Francisco Bay RWQCB

Jennifer Rice, Esq.

F.3

### cook

271 Las Juntas Way, Walnut Creek, CA 94597 Phone 925.937.1759 Cell 925.787.6869 cookenvironmental@att.net

## RESPONSE TO TECHNICAL COMMENTS AND WORK PLAN FOR ADDITIONAL SITE INVESTIGATION

PROJECT SITE:

Express Gas & Mart 2951 High Street Oakland, California 94619

PREPARED FOR:

The Manage County

Mr. Aziz Kandahari Himalaya Trading Company 2951 High Street Oakland, California 94619

SUBMITTED TO:

Alameda County Health Care Services Environmental Health Services 1131 Harbor Bay Parkway, Suite 250 Alameda, California 94502

PREPARED BY:

Cook Environmental Services, Inc. 271 Las Juntas Way Walnut Creek, California 94597

Project No. 1004

June 12, 2006

#### PROFESSIONAL CERTIFICATION

## RESPONSE TO TECHNICAL COMMENTS AND WORK PLAN FOR ADDITIONAL SITE INVESTIGATION

Express Gas & Mart 2951 High Street Oakland, California 94619

Cook Environmental Services, Inc. Project No. 1004 June 12, 2006

This document has been prepared by Cook Environmental Services, Inc. under the supervision of the licensed professional whose signature appears below. No warranty, either expressed or implied, is made as to the professional advice presented in this document. The data analysis, conclusions, and recommendations contained in this document are based upon site conditions at the time of our investigation. Site conditions are subject to change with time, and such changes may invalidate the interpretations and conclusions in this document.

The conclusions presented in this document are professional opinions based solely upon the stated scope of work and the interpretation of available information as described herein. Such information may include third party data that either has not, or could not be independently verified. Cook Environmental Services, Inc. recognizes that the limited scope of services performed in execution of this investigation may not be appropriate to satisfy the needs or requirements of other potential users, including public agencies not directly involved. Any use or reuse of this document or the findings, conclusions, and recommendations presented herein is at the sole risk of said user.

Tim Cook, P.E., CEG

Principal

#### INTRODUCTION

This report responds to requests for information from the Alameda County Environmental Health (ACEH) regarding the Request for Case Closure on Fuel Leak Case RO0000261 for Express Gas & Mart located at 2951 High Street in Oakland, California (the "Site"). In a letter dated May 5, 2006 to Mr. Aziz Kandahari, the former owner and responsible party, the ACEH requested additional information to review case closure. Eleven technical comments were provided in this letter. We will attempt to respond to these comments in the order that they were presented.

#### ACEH TECHNICAL COMMENTS

1. Analytical reports and results of soil sample by MW-1 collected September 27, 2001 not provided – During most recent groundwater monitoring event on October 4, 2005, 400 ug/l MTBE was detected in MW-1. The data requested may determine if the source of the MTBE is from this area. Please submit.

Cook Environmental Services, Inc. (CES) conducted a thorough file review for the site at ACEH on May 18, 2006. Base on information found in remediation report by W.A. Craig, Inc., two four point composite soils samples (SP1-4 and SP 5-8) were collected from near well MW-1 on September 27, 2001. MtBE was detected at 73 ug/kg in SP 1-4 and 56 ug/kg in SP 5-8. These results indicate that MtBE was present in shallow soils (<12 ft). These soils were excavated and disposed of appropriately offsite. The lab reports for these two soil samples and a map showing the approximate locations of the samples is provided in **Appendix A**.

2. Additional groundwater sampling — During the most recent groundwater monitoring event on October 4, 2005, 490 ug/l MTBE was detected in MW-10. Please propose groundwater sampling to determine if active tanks or dispensers are responsible for MTBE found in MW-10. Please indicate on the site map the proposed groundwater sampling locations and the active tanks and dispensers. Also, indicate when the current tank system became operational.

Groundwater and soil samples will be collected from three temporary borings located downgradient of the new tank system. Borings will be advanced using a Geoprobe drilling rig. One soil sample will be collected from each boring at the groundwater interface (approximately 6 feet below surface). A groundwater sample will be collected from the first groundwater encountered. The sample will be collected in a temporary well constructed of ¾" diameter PVC. The water sample will be collected using a factory clean disposable bailer and placed into three laboratory clean 40 ml VOA vials preserved with concentrated hydrochloric acid. All samples will be collected under chain of custody control and transported to the lab at 4 degrees Celsius. The samples will be delivered to the lab within 8 hours of collection. The proposed location of the temporary borings is provided on **Figure 1** in **Appendix B**. Boring permits will be obtained

from the Alameda County Department of Public Works and a utility location survey will be conducted by USA Alert prior to commencement of field work.

3. Historical hydraulic gradients – Please show using a rose diagram with magnitude and direction; include cumulative groundwater gradients in all future reports submitted for this site.

While we agree there is some benefit in reviewing historical groundwater gradients, the rose diagram is not the most beneficial way to review these gradients. Rose diagrams will only give the triangulated direction of groundwater flow between three points. The flow direction at this site is more complex in that the gradient and the flow direction change across the site. The most beneficial way to review historical groundwater gradients is to review the hydraulic gradient map for historical groundwater sampling events. We have accumulated historical groundwater gradient maps from February 23, 1995 to October 4, 2005. These gradient maps are provided in **Appendix C**. While the early gradient maps incorrectly identified the groundwater flow direction as to the north, later gradient maps using more wells correctly identified the flow direction as southwesterly, following the regional topography.

4. Analytical results for groundwater samples incomplete – Omitted were MW-2 (STMW-2), MW-4 analyses for TPHD and TOG for MW-1 (STMW-1) and MW-3 (STMW-3). Please include these results in your table.

Analytical results for all the above have been addend to the historical groundwater analytical results. This table is provided in **Appendix D**.

5. Soil and groundwater contaminant concentration site maps — Please show soil and groundwater contaminant concentration sample locations data on site maps. Include dates of sample collection and for soil samples, depth at which sample was collected. In addition to items featured, include previously installed monitoring wells and dispensers.

W.A. Craig, Inc. provided complete tables and figures covering all soil and groundwater samples collected during the removal of contaminated soil from the site from May to September 2001. A figure is included for each sampling date. Soil sample tables contain the sample date, sample depth, sample ID and sample results. The same sample IDs are shown on the accompanying figures. These tables and figures are provided in **Appendix E**. This same appendix also contains a map showing the location of previously installed monitoring wells (MW-2 and MW-4). The present day dispensers shown on the amp are in the same location as the former dispensers.

6. Preferential Pathway Survey – We request that you perform a preferential pathway study that details the potential for migration pathways and potential conduits (wells, utilities,

pipelines, etc.) for horizontal and vertical migration that may be present in the vicinity of the site.

a) Utility Survey- Please submit map(s) and cross-sections showing the location and depth of all utility lines and trenches (including sewers, storm drains, pipelines, trench backfill etc. within and near the site and plume area(s). Evaluate the probability of the contaminant plumes encountering preferential pathways and conduits that could spread the contamination.

CES contacted Underground Service Alert (USA) on May 19, 2006 and requested that all buried public utilities on and near the site be located. PG&E located gas and electrical lines, SBC/ATT located buried phone lines, and EBMUD located water mains. The City of Oakland did not respond to the USA call even after several calls, however, buried storm drain lines and sewer lines were located by CES using manhole covers, cleanout lid covers, storm drain catch basins. This preferential pathway survey was performed on ay 24, 2006. Buried utilities located during this survey are shown on the figure provided in Appendix F. The survey indicated there are many buried utilities, however, in order for buried utilities to provide a preferential pathway the following conditions must be met: 1) they must be located hydraulically downgradient of the contaminant plume(s); 2) the trench they are buried in must be at least as deep as the highest recorded groundwater elevation; and 3) the trenches must be backfilled with a material that is more permeable than the native soil. Based on the first criteria, we can eliminate all buried utilities in the vicinity of the site except the EBMUD water main, the PG&E gas main, the City of Oakland sewer and the City of Oakland storm drain all of which run beneath High Street. Based on the second criteria, the bottom of a utility trench must be at least as deep as the highest recorded groundwater in wells MW-8 and MW-10 (wells closest to High Street). The shallowest recorded groundwater depth in these wells was 4.40 feet below top of casing in well MW-8 on January 3, 2005 and on March 4, 2005.

The storm drain catch basin at the corner of Penniman and High Streets is within 23 feet of MW-8. The invert for this catch basin is 3.6 feet below grade. Thus the trench containing the storm drain is above the groundwater static level at all times. We can eliminate the storm drain trench as a potential pathway.

A call was made to PG&E to determine the depth of the trench containing the 4-inch diameter steel natural gas transmission line (4" STL). PG&E stated the exact depth of this trench is unknown since settling, regarding and repaving may have occurred since the line was placed. In general PG&E places 3 feet of cover over their gas lines. The gas lines are covered top and bottom with sand. If the line is buried with 3 feet of cover, the pipe is 4" diameter and is on top of an 8" thick sand bed, the base of the gas line trench is at approximately 4 feet below grade. Thus the bottom of this trench is 0.4 feet above the highest recorded groundwater level and we can eliminate the gas line as a preferential pathway.

A call was made to EBMUD to determine the depth of the trench containing the 8-inch diameter cast iron water main beneath High Street. EBMUD stated that this water main was installed in the 1950s and was typically covered with 36 inches (3 feet) of native soil. Bedding sand or pea

gravel was not used on cast iron pipes during this period. If the line is buried with 3 feet of cover, the pipe is 8" diameter and there is no bedding sand or gravel, the base of the water line trench is at approximately 3.7 feet below grade. Thus the bottom of this trench is 0.7 feet above the highest recorded groundwater level and we can eliminate the water main as a preferential pathway.

A call was made to the City of Oakland Public Works Department, Sewer Maintenance Division to determine the depth of the trench containing the sewer lines running down High Street. There are two sewer trunk lines running down High Street in the vicinity of the site; one runs down the east side, the other runs down the west side of High Street. Both sewer lines are approximately 6 to 8 feet deep. The sewer lines are more than 50 years old. At that time, native soils were used as bedding material. Based on this information the sewer lines are deeper than the highest recorded groundwater elevation. The sewer lines could provide a preferential pathway if they were backfilled with a higher permeability material such as pea gravel or sand. In fact, the sewer lines are backfilled with native soils which do not necessarily have a higher permeability than the surrounding soil. Based on the existing information, it is unlikely that the sewer lines provide a preferential pathway for the offsite migration of MtBE or other contaminants from the site.

7. Well survey – Locate wells within a quarter mile radius of the site. Show the location of the wells and the site on a map and tabulate well construction details for each well. Please submit with the Work Plan requested below.

This sensitive receptor survey includes a water well search and a field survey to locate recorded wells within 1/4 mile of the Site that have been identified through California Department of Water Resources (DWR) well records. A thorough walking survey was also conducted to locate water wells and other potential receptors located within 1/4 mile of the Site to search for wells which may exist but were not identified in DWR well records. Well locations are depicted on a 7.5' USGS Quad map with the 1/4 mile radius clearly marked. CES conducted a review of recorded drillers' logs for the area at the DWR office in Sacramento on May 16, 2006. Wells logs for two sites within 1/4 mile of the subject site were discovered. The first site is located at 3315 High Street and was a former Mobil Oil gas station. Three monitoring wells were installed to depths ranging from 30 to 35 feet. The purpose of these wells is to delineate the extent of hydrocarbon contamination from an onsite UST release. These wells are located hydraulically upgradient of the subject site. These wells are not sensitive receptors and can be eliminated from further analysis. The second site is located at 2627 Minna Street. This well is a domestic well drilled to a depth of 211 feet. The well casing is perforated from 115 to 155 feet and from 178 to 211 feet. The screened section of this well intercepts clay and gravel. A well test was performed but the results are not legible. A chemical analysis shows that water from the well contains 3.64 grams per gallon (961 mg/l) of chloride. The secondary maximum contaminant level (MCL) for chloride in drinking water is 250 mg/l. The site is located 1/4 mile west (i.e., downgradient) of the subject site. A field survey for wells that are not recorded with the DWR was conducted on May 24, 2006. The survey involved walking the area within 1/4 mile radius to visually locate any well heads, pumps, pump houses or other evidence of well water systems. No wells were located during this

reconnaissance, however, one are homeowner mentioned that she had a private hand dug well on her property that is not recorded with the county or the DWR. When questioned further, she would not divulge the address of her property. A tabulation of well construction detail, a map showing the locations wells within a ¼ radius of the subject site and driller's logs for these wells are provided in **Appendix G**.

8. Groundwater monitoring well sampling – Reinstate at least for another quarter.

All eight groundwater monitoring wells were sampled on May 24, 2006. The results of this sampling event are included in a separate report entitled *Quarterly Monitoring Report, Second Quarter 2006.* 

9. Inactive groundwater monitoring wells – Please determine if STMW-2 [MW-2] and MW-4 have been properly decommissioned.

MW-2 and MW-4 were removed during excavation of contaminated soil from the site from May to September 2001. The bottom of the excavation was approximately 12 feet below grade. The well casings were broken off at this depth and the remainder of the well was filled with neat cement to seal this potential pathway. This engineer witnessed these well abandonments. A call to the Alameda County Department of Public Works (ACPW) revealed that a complete well abandonment permit has not been issued for these wells. At present, CES is providing ACPW with DWR well logs and other information needed to process decommissioning of these wells.

10. Plume velocity -Please determine for the hydrocarbon dissolved phase groundwater plume.

There is no aquifer test data available to determine the site specific hydraulic conductivity or transmissivity of the water-bearing unit. A range of values for gravelly clay soil is available in several text books (Freeze & Cherry, 1979, Fetter, 1965, Driscoll, 1986). An average hydraulic conductivity value was calculated using site specific data. MtBE is the constituent of concern at this site. MtBE is not easily adsorbed by the soil matrix thus no adsorption was assumed in the calculation of the plume velocity. The initial calculation of plume velocity assumes the plume velocity is controlled by the primary porosity of the soil matrix and is not based on secondary porosity through fractures, fissures, and other preferential pathways. Based on these assumptions the MtBE plume velocity is approximately 0.30 feet per year. However, field examination of soil cores and transects in the excavation indicate that the soil is partially lithified with significant secondary fractures and fissures. Due to this secondary porosity, we apply a multiplier of 60x to the hydraulic conductivity value obtained from the literature. This assumption results in a plume velocity of 18 feet per year. A check was performed using field calibration data from MtBE concentration in well MW-10. This well is located 128 feet downgradient from the nearest source area (the former dispensers in front of the market). If we assume that MtBE began leaking from the dispensers at the time MtBE was first widely used as


an octane booster (late 1970s) the resulting plume velocity is approximately 5 feet per year. Thus, we estimate the MtBE plume velocity is in the range of 5 to 18 feet per year. Plume velocity calculations are provided in **Appendix H**.


11. Analytical results for soil samples – Tabulation of soil samples [sic] results required. Please submit.

Please see Appendix E.

### **APPENDIX A**

Laboratory Analytical Reports and Map for Composite Soil Samples near MW-1







W.A. CRAIG, INC.

6940 TREMONT ROAD DIXON, CAUFORNIA 95620 PH를 (707) 693-2929 UC를 455752 Project Name and Address

EXPRESS GAS & MART 2951 HIGH STREET DAKLAND, CA JOB # 3936 FIGURE #

5-10-01



#### McCAMPBELL ANALYTICAL INC.

110 2nd Avenue South. #D7, Pacheco, CA 94553-5560 Telephone: 925-798-1620 Fax: 925-798-1622 http://www.mccampbell.com E-mail: main@mccampbell.com

|                                |                  |  |             |             | 1          |                 |        |
|--------------------------------|------------------|--|-------------|-------------|------------|-----------------|--------|
| W. A. Craig, Inc.              | Client Project 1 | Client Project ID: #3936; High Street Date Sampled: 09/27/ |             |             |            |                 |        |
| 6940 Tremont Road              |                  |  | Date Receiv | ed: 09/27/  | 01         | <del>-</del> ,- |        |
| Dixon, CA 95620-9603           | Client Contact:  | Tim Cook   |             | Date Extrac | ted: 09/27 | 01              | ·      |
|                                | Client P.O:      | ······································                     | <del></del> | Date Analyz | ed: 09/27  | 01              |        |
| EPA method 8260 modified       | Seven Oxygenated | l Volatile Org   | anics By G  | C/MS        |            | - W             |        |
| Lub ID                         | 79615            | 79616  |             |             |            | <del> </del>    |        |
| Client ID                      | SP-1-4           | SP-5-8   |             | Rep         |            | orting Limit    |        |
| Matrix                         | s                | · s  |             |             | S          | 7 ;             | R'     |
| Compound                       |                  | Concer   | itration*   |             | ug/kg      | ivg             | /L     |
| Di-isopropyl Ether (DIPE)      | ND<50            | ND<50  |             |             | 5.0        | L               | o      |
| Ethyl tert-Butyl Ether (ETBE)  | ND<50            | ND<50  |             |             | 5.0        | 1.9             | 0      |
| Methyl tert-Butyl Ether (MTBE) | 73 ;             | 56   |             |             | 5.0        | . 1.0           | 0      |
| tert-Amyl Methyl Ether (TAME)  | ND<50            | ND<50  |             |             | 5,0        |                 | o .    |
| tert-Butanol                   | ND<250           | ND<250   |             |             | 25         | 5.              | o<br>o |
| Methanol                       | ND<25,000        | ND<25,000  |             |             | 2500       | .50             | 0 .    |
| Ethanol                        | ND<2500          | ND<2500  |             |             | 250        | 50              | )      |
| Surragate Recoveries (%)       |                  |  |             |             |            |                 |        |
| Dibromofluoromethuse           | 95               | 89   |             |             |            |                 |        |
| Comments:                      |                  |  |             |             |            |                 |        |
| <del></del>                    | <u></u>          |  | <u> </u>    |             |            |                 |        |


<sup>\*</sup> water samples are reported in ug/L, soil and sludge samples in ug/kg, wipes in ug/wipe and all TCLP / STLC / SPLP extracts in ug/L ND means not detected above the reporting limit; N/A means surrogate not applicable to this analysis

DHS Certification No. 1644

Jun -

Edward Hamilton, Lab Director

<sup>(</sup>h) lighter than water immiscible sheen is present; (i) liquid sample that contains greater than -5 vol % sediment; (j) sample diluted due high organic content



110 2nd Avenue South, #D7, Pacheco, CA 9453-5560 Telephone: 925-798-1620 Fax: 925-798-1622 http://www.mccampbell.com/E-mail: main@mccampbell.com/

| W. A. Craig, Inc. Client Project II   |   | oject ID: #3936; High Street | Date Sampled:    | 09/27/01       |  |  |
|---------------------------------------|---|------------------------------|------------------|----------------|--|--|
| 6940 Tremo                            | nt Road   | t Road                       |                  | Date Received  | : 09/27/01                                       |  |
| Dixon, CA 9                           | )5620-9603  | Client Co                    | ontact: Tim Cook | Date Extracted | l: 09/ <b>27/</b> 01                             |  |
| 1                                     |   | Client P.                    |                  | Date Analyzed  |  |  |
| EPA method 82                         | Ethylene Dibromide (1,2-Dibromoethane) and 1,2-Dichloroethane (1,2-DCA) |                              |                  |                |  |  |
| Lab ID                                | Client ID   | Matrix                       | EDB              | 1,2-0CA        | % Recovery<br>Surrogate                          |  |
| 79615                                 | SP-1-4  | s                            | ND<50.j          | ND<50          | 95   |  |
| 79616                                 | SP-5-8  | s                            | ND<50,j          | ND<50          | 89   |  |
|                                       |   |                              |                  |                |  |  |
|                                       |   |                              |                  |                |  |  |
|                                       |   |                              |                  |                |  |  |
|                                       |   |                              |                  |                |  |  |
|                                       |   |                              |                  |                |  |  |
| · · · · · · · · · · · · · · · · · · · |   | <del> </del>                 |                  |                | 1  |  |
|                                       |   |                              |                  |                |  |  |
|                                       |   |                              |                  |                |  |  |
| ·                                     |   |                              |                  |                |  |  |
|                                       |   |                              |                  |                | <del>                                     </del> |  |
|                                       |   |                              |                  | <del> </del>   |  |  |
| Reporting Li                          | mit unless otherwise  | W                            | 1.0 ug/T,        | 1.0            |  |  |
| stated; ND mo                         | ans not detected above<br>eporting limit                                | S                            | 5.0 ugʻilg       | 5.0            | <del>-</del>                                     |  |

water and vapor samples are reported in ug/L, soll and sludge samples in ug/kg, wipes in ug/wipe and all TCLP / SPLP extracts in ug/L

h) lighter than water immiscrible sheem is present; i) liquid sample that contains greater than ~5 rel. % sediment; j) sample differed due to high organic content.

DHS Certification No. 1644



Edward Hamilton, Lab Director

110 2nd Avenue South, #D7, Pacheco, CA 94553-5560
Telephone: 925-798-1620 Fax: 925-798-1622
http://www.mccampbell.com E-mail: main@mcqampbell.com

| W. A. Cr | aig, Inc.  |               | Client Project ID: #3936; High Street Date Sampled: 09:2 |              |  |          | oled: 09/27/      | /01          |                         |
|----------|--|---------------|--|--------------|--|----------|-------------------|--------------|-------------------------|
|          | mont Road  |               | Date Receiv  |              |  |          |                   |              | <b>1</b> 01             |
| Dixon, C | A 95620-960  | 3             | Client Cor   | ıtact: Tim   | Cook                                   |          | Date Extra        | <del> </del> |                         |
|          |  |               | Client P.O   | :            | ······································ |          | Date Anal         |              |                         |
|          | e Range (C6  |               |  |              |  |          | -                 | -            | & BTEX*                 |
| Lab ID   | Client ID  | Matrix        | ТРН(g) <sup>+</sup>                                      | MTBE         | Вепиепе                                | Toluenc  | Ethyl-<br>benzene | Xylenes      | % Recovery<br>Surrogate |
| 79615    | SP-1-4   | S             | 110,b.j  | 0.33         | 0.20                                   | 0.78     | 1.3               | 6.6          | *                       |
| 79616    | SP-5-8   | S             | 78,bj  | 0.44         | 0.28                                   | 0.84     | 1.4               | 6.7          | e                       |
|          |  |               | <del> · i</del>  | -            |  |          |                   |              |                         |
| ·        |  | <del>  </del> |  |              |  | <u> </u> |                   |              | 1                       |
|          |  |               |  |              |  |          |                   |              |                         |
|          |  |               |  | <u> </u>     |  |          |                   |              | <u> </u>                |
|          |  |               | <del></del>  | <del> </del> |  |          |                   |              | <u> </u>                |
|          |  |               |  | <del></del>  |  | }        |                   | 1            | <u> </u>                |
|          |  |               |  |              | }                                      |          |                   |              |                         |
|          | And the second s |               |  |              | 1                                      |          | ļ                 |              | <del> </del>            |
|          |  | , ,           | 1  | <b>\</b>     |  | 1        | }                 | !            | 1                       |

\* water and vapor samples are reported in ug/L, wipe samples in ug/wipe, soil and studge samples in mg/kg, and all TCY.P and SPt.P extracts in ug/L

0.5

0.005

. 0.5

0.005

0.5

0.005

0.5

0.005

5.0

0.05

W

S

50 ug/L

1.0 mg/kg

Reporting Limit unless

ntherwise stated; ND means not detected above

the reporting limit

<sup>\*</sup>cluttered chromatogram; sample peak coefutes with surrogate peak

The following descriptions of the TPH chromatogram are cursory in nature and McCampbell Analytical is not responsible for their interpretation: a) unmodified or weakly modified gasoline is significant; b) heavier gasoline range compounds are significant; and interpretation: b) lighter gasoline range compounds (the most mobile fraction) are significant; d) gasoline range compounds having broad chromatographic peaks are significant; biologically altered gasoline?; e) TPH pattern that does not appear to be derived from gasoline (?); f) one to a few isolated peaks present; g) strongly aged gasoline or diesel range compounds are significant, h) lighter than water immissible sheen is present; i) liquid sample that contains greater than ~5 vol. % sediment; j) no recognizable pattern.



#### McCAMPBELL ANALYTICAL INC.

110 2nd Avenue South, #D7, Pacheco, CA 9453-5560
Telephone: 925-798-1620 Fax: 925-798-1622
http://www.mccampbell.com B-mail: main@mccampbell.com

| W. A. Craig, Inc.<br>6940 Tremont Road |  | Client Project ID: #3936; High Street |                     | Date Sampled: 09/27/0 |       | 01                   |  |
|--|--|---------------------------------------|---------------------|-----------------------|-------|----------------------|--|
| Dixon, CA 9                            | 5620-9603  | Client Co                             | ntact: Tim Cook     | Date Extracted: 09    | 9/27/ | )1<br>               |  |
|  |  | Client P.C                            | <b>)</b> :          | Date Analyzed: 09     | 9/27/ | ) i                  |  |
| EFA næthods rr                         | Diesel Range (C10-C23) Extractable Hydrocarbons as Diesel *  EPA methods modified 8015, and 3550 or 3510; California RWQCH (SF Bu) Region) method GCFID(3530) or GCFID(3510) |                                       |                     |                       |       |                      |  |
| Lab ID                                 | Client ID  | Matrix                                | TPH(d) <sup>+</sup> |                       |       | Recovery<br>urrogate |  |
| 79615                                  | SP-1-4   | S                                     | 49,d,g              |                       |       | 97                   |  |
| 79616                                  | SP-5-8   | s                                     | 63,d,g              |                       |       | 97                   |  |
|  |  |                                       |                     |                       |       |                      |  |
|  |  |                                       |                     | ·                     |       |                      |  |
|  |  |                                       |                     |                       |       |                      |  |
|  |  |                                       |                     |                       |       |                      |  |
| •                                      |  |                                       |                     |                       |       |                      |  |
|  |  |                                       |                     | •                     |       | ·                    |  |
|  |  |                                       |                     |                       |       |                      |  |
|  |  |                                       |                     |                       |       |                      |  |
|  |  |                                       |                     |                       |       |                      |  |
|  |  |                                       |                     |                       |       |                      |  |
| ·                                      |  |                                       |                     |                       |       |                      |  |
|  |  |                                       |                     |                       |       |                      |  |
|  | imit unless otherwise  | w                                     | 50 ug/L             |                       |       |                      |  |
|  | eans not desected above  | c.                                    | 1 0 000/64          |                       |       |                      |  |

4

<sup>\*</sup> water and vapor samples are reported in ug/L, wipe samples in ug/wipe, soil and studge samples in mg/kgl and all TCLP / SPLC / SPLP extracts in ug/L

<sup>&</sup>quot;cluttered chromatogram resulting in coeluted surrogate and sample peaks, or; surrogate peak is on elevated baseline, or; surrogate has be diminished by dilution of original extract.

The following descriptions of the TPH chromatogram are cursory in nature and McCampbell Analytical is not responsible for the interpretation: a) unmodified or weakly modified diesel is significant; b) diesel range compounds are significant; no recognizable pattern; aged diesel? is significant; d) gasoline range compounds are significant; e) medium boiling point pattern that does not much diesel (?), one to a few isolated peaks present; g) oil range compounds are significant; h) lighter than water immissible sheen is present; i) liquid sample that contains greater than ~5 vol. % sediment.



#### McCAMPBELL ANALYTICAL INC.

110 2nd Avenue South, #D7, Pacheco, CA 94553-5560 Telephone: 925-798-1620 Fax: 925-798-1622 http://www.mccampbell.com E-mail: main@mccampbell.com


| W. A. Craig, Inc. |  | Client | Client Project ID: #3936; High Street                    |               | Date Sampled                          |             | ··   |
|-------------------|--|--------|--|---------------|---------------------------------------|-------------|------|
| 6940 Tremoi       | nt Road  |        |  | Date Received | i: 09/27∤01                           | 01          |      |
| Dixon, CA 9       | 5620-9603                                      | Client | Contact: Tim C   | ook           | Date Extracte                         | d: 09/27 01 |      |
|                   |  | Client | P.O:   |               | Date Analyze                          | d: 09/27/01 |      |
| EPA analytical 1  | methods 6010/200.7, 239                        | 0.2*   | Lea  | d*            | ····                                  |             |      |
| Lab ID            | Client ID                                      | Matrix | Extraction °   |               | Lead*                                 | % Recove    |      |
| 79615             | SP-1-4   | 5      | TTLC   | 8.2           |                                       | 103         | Line |
| 79616             | SP-5-8   | s      | TTLC   |               | 9.4                                   | 103         |      |
|                   |  |        |  |               |                                       |             |      |
|                   |  |        |  |               |                                       |             |      |
|                   |  |        | \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ |               |                                       |             |      |
|                   |  |        |  |               |                                       |             |      |
|                   |  |        |  |               |                                       |             |      |
|                   |  |        |  |               | <del></del>                           |             |      |
|                   |  |        |  |               | <del></del>                           |             |      |
| <u>}</u>          |  |        |  | <u> </u>      |                                       |             |      |
| }                 |  | i      |  | ]             |                                       |             |      |
|                   | <u> </u>                                       |        |  |               |                                       |             |      |
|                   | <u> </u>                                       | }      |  |               | · · · · · · · · · · · · · · · · · · · |             |      |
|                   |  | · .    | · · · · · · · · · · · · · · · · · · ·                    | ·             | - h.c                                 |             |      |
|                   |  | S      | TTLC   |               | U mg/kg                               |             |      |
| stated; ND mea    | mit unless otherwise<br>ans not detected above | w      | TTLC   | <u> </u>      | .005 mg/L                             |             |      |
| the re            | porting limit                                  |        | STLC,TCLP  |               | 0.2 mg/L                              |             |      |

- \* soil and sludge samples are reported in mg/kg, wipe samples in ug/wipe, and water samples and all STLC / SPLP / TCLP extracts in mg/L "Load is analysed using EPA method 6010 (ICP) for soils, studges, STLC & TCT.P extracts and method 239.2 (AA Furbace) for water samples
- 26. DISTLC extractions are performed using STLC methodology except that defonized water is substituted for citric acid huffer as the extraction fluid. DISTLC results are not applicable to STLC regulatory limits.
- FEPA extraction methods 1311(TCLP), 3010/3020(water,TTLC), 3040(organic matrices,TTLC), 3050(notids,TTLC); STLC ∮ CA Fitle 22.
- surrogate diluted out of range; N/A means surrogate not applicable to this analysis
- \* reporting limit raised due matrix interference
- i) liquid sample that contains greater than -2 vol. % sediment; this sediment is extracted with the liquid, in accordance with EP methodologies and can significantly effect reported metal concentrations.

Hdward Hamilton, Lab Director

### **APPENDIX B**

**Proposed Temporary Boring Locations** 



Cook Environmental Services, Inc.


271 Las Juntas Way Walnut Creek, CA 94597 (925) 937-1759 work (925) 937-6869 cell cookenvironmental@att.net


### **Proposed Boring Locations**


| Project #: 1004 | Figure: |
|-----------------|---------|
| Date: 6/06/06   | 1       |
| Scale: 1"=30'   | 1       |


## APPENDIX C

Historical Groundwater Gradient Maps












6940 Tremont Road LIC# 455752 Dixon, California 95620-9603 PH# (707) 693-2929 Fax# (707) 693-2922

July 16, 2003 Express Gas & Mart 2951 High Street Oakland, California

Project #: 3936

Date: 7/16/03

Scale: 1"=30'






6940 Tremont Road LIC# 455752 Dixon, California 95620-9603 PH# (707) 693-2929 Fax# (707) 693-2922

October 28, 2003 Express Gas & Mart 2951 High Street Oakland, California

| Project #: 3936 | Figure: |
|-----------------|---------|
| Date: 11/7/03   | 1 7     |
| Scale: 1"=30'   |         |






6940 Tremont Road LIC# 455752 Dixon, California 95620-9603 PH# (707) 693-2929 Fax# (707) 693-2922

## **April 29, 2004**


| Project #: 3936 | Figure: |
|-----------------|---------|
| Date: 4/29/04   | 7       |
| Scale: 1"=30'   |         |





6940 Tremont Road LIC# 455752 Dixon, California 95620-9603 PH# (707) 693-2929 Fax# (707) 693-2922

| Project #: 3936 | Figure: |
|-----------------|---------|
| Date: 7/8/04    | 1 3     |
| Scale: 1"=30'   |         |






6940 Tremont Road LIC# 455752 Dixon, California 95620-9603 PH# (707) 693-2929 Fax# (707) 693-2922

## October 1, 2004

| Project #: 3936 | Figure: |
|-----------------|---------|
| Date: 10/1/04   | 7 1     |
| Scale: 1"=30'   | 7 J     |




GOOK ENVIRONMENTAL

271 Les Juntes Way, Walnut Creek, CA 34532 Phone 925,937 1759 Cell 925 787 6269 ende virenne tal Garane

## **January 3, 2005**

| Project #: 1004 | Figure: |
|-----------------|---------|
| Date: 2/10/05   | 3       |
| Scale: 1"=30'   |         |




300 CERVICES INC

Eff Los Junton May, Welle: Creat CA 84597 Phone Gas 837 1759 Call GBA 787 8663 Ecology communications.

## Groundwater Elevations on April 5, 2005

| Project #: 1004 | Figure: |
|-----------------|---------|
| Date: 4/5/05    | 7       |
| Scale: 1"=30'   |         |




300 K ENV HOUMEN AL

271 Let Junioù Way, Yeanu: Creek, SA. 94597 Phone Gad, 637, 1759 Cell, 998,797, 8960 ctoksevi: semental Gatt, ne:

## **Groundwater Elevations on July 6, 2005**

| Project #: 1004 | Figure: |
|-----------------|---------|
| Date: 7/22/05   | 1       |
| Scale: 1"=30'   |         |



#### Cook Environmental Services, Inc.

271 Las Juntas Way Walnut Creek, CA 94597 (925) 937-1759 work (925) 937-6869 cell cookenvironmental@att.net

#### Groundwater Elevations on October 4, 2005

| Project #: 1004 | Figure: |
|-----------------|---------|
| Date: 10/20/05  | 13      |
| Scale: 1"=30'   |         |

### **APPENDIX D**

**Historical Groundwater Data** 

# Table 3 Analytical Results for Groundwater Samples 2951 High Street Oakland, California

| Well ID  | Date     | TPH-g   | benzene | toluene | ethyl-<br>benzene | xylenes | MtBE   | DIPE  | EtBE | tAME | tBA  | methanol | ethanol | EDB  | DCA   |
|----------|----------|---------|---------|---------|-------------------|---------|--------|-------|------|------|------|----------|---------|------|-------|
| MW-1     | 02/23/95 | <50     | <0.5    | <0.5    | <0.5              | <0.5    | NT     | NT    | NT   | NT   | NT   | NT       | NT      | NT   | NT    |
|          | 05/26/95 | <50     | <0.5    | <0.5    | <0.5              | <0.5    | NT     | NT    | NT   | NT   | NT   | NT       | NT      | NT   | NT    |
|          | 08/23/95 | <50     | <0.5    | <0.5    | <0.5              | <0.5    | NT     | NT    | NT   | NT   | NT   | NT       | NT      | NT   | NT    |
|          | 04/04/03 | <50     | <0.5    | <0.5    | <0.5              | <0.5    | 270    | <5    | <5   | <5   | <50  | <5,000   | <500    | <5   | <5    |
|          | 07/16/03 | <50     | <0.5    | <0.5    | <0.5              | <0.5    | 420    | <10   | <10  | <10  | <100 | <10,000  | <1,000  | <10  | ` <10 |
|          | 10/28/03 | <50     | <0.5    | <0.5    | <0.5              | <0.5    | 1,200  | <50   | <50  | <50  | <500 | <50,000  | <5,000  | <50  | <50   |
|          | 01/13/04 | 58      | 0.85    | <0.5    | 3.1               | 8.4     | 380    | <0.5  | <0.5 | <0.5 | <5.0 | <50      | <5      | <0.5 | <0.5  |
| *        | 04/29/04 | <50     | <0.5    | <0.5    | <0.5              | <0.5    | 260    | <5    | <5   | <5   | <50  | <5,000   | <500    | <5   | <5    |
|          | 07/08/04 | <50     | <0.5    | <0.5    | <0.5              | <1.0    | 341    | <0.5  | <1   | <1   | <10  | NT       | <100    | <1.0 | <0.5  |
|          | 10/01/04 | <50     | <0.5    | <0.5    | <0.5              | <0.5    | 1.7    | <0.5  | <0.5 | <0.5 | <5.0 | <500     | <50     | <0.5 | <0.5  |
|          | 01/03/05 | <50     | <0.5    | <0.5    | <0.5              | <0.5    | 33     | <0.5  | <0.5 | <0.5 | <5.0 | <500     | <50     | <0.5 | <0.5  |
|          | 04/05/05 | <50     | <0.5    | <0.5    | <0.5              | <0.5    | 44     | < 0.5 | <0.5 | <0.5 | 6.8  | <500     | <50     | <0.5 | <0.5  |
|          | 07/06/05 | <50     | <0.5    | <0.5    | <0.5              | <0.5    | 270    | <5    | <5   | <5   | <50  | <5,000   | <500    | <5   | <5    |
|          | 10/04/05 | <50     | <0.5    | <0.5    | <0.5              | <0.5    | 400    | <5    | <5   | <5   | <50  | <5,000   | <500    | <5   | <5    |
| MW-2     | 02/23/95 | 3,300   | 10      | 13      | 8                 | 28      | NT     | NT    | NT   | NT   | NT   | NT       | NT      | NT   | NT    |
| į        | 05/26/95 | 4,600   | 39      | 18      | 21                | 39      | NT     | NT    | NT   | NT   | NT   | NT       | NT      | NT   | NT    |
|          | 08/23/95 | <50     | 15      | 6       | 10                | 15      | NT     | NT    | NT   | NT   | NT   | NT       | NT      | NT   | NT    |
| 1        | 12/13/96 | 1,900   | 110     | 110     | 120               | 330     | 65     | NT    | NT   | NT   | NT   | NT       | NT      | NT   | NT    |
| -        | 03/27/97 | 3,900   | 34      | 20      | 86                | 140     | 200    | NT    | NT   | NT   | NT   | NT       | NT      | NT   | NT    |
| <u> </u> | 06/27/97 | 2,400   | 18      | <5      | 6                 | 8.8     | 2,000  | NŦ    | NT   | NT   | NT   | NT       | NT      | NT   | NT    |
| 1        | 09/22/97 | <5,000  | 8       | 20      | 33                | 100     | 3,900  | NT    | NT   | NT   | NT   | NT       | NT      | NT   | NT    |
| ļ        | 12/06/97 | 3,000   | 33      | 40      | 40                | 140     | 2,300  | NT    | NT   | NT   | NT   | NT       | NT      | NT   | NT    |
| ļ        | 03/23/98 | 220     | 3       | 3       | 5.8               | 13      | 18     | NT    | NT   | NT   | NT   | NT       | NT      | NT   | NT    |
| 1        | 06/10/98 | 3,400   | 120     | 64      | 160               | 200     | 1,900  | NT    | NT   | NT   | NT   | NT       | NT      | NT   | NT    |
|          | 07/23/98 | 6,000   | 340     | 54      | 280               | 390     | 3,300  | NT    | NT   | NT   | NT   | NT       | NT      | NT   | NT    |
| 1        | 09/16/98 | 3,700   | 77      | <25     | 80                | 69      | 5,500  | NT    | NT   | NT   | NT   | NT       | NT      | NT   | NT    |
| L        |          | <10,000 | <100    | 150     | <100              | 180     | 9,100  | NT    | NT   | NT   | NT   | NT       | NT      | NT   | NT    |
| <u> </u> | 03/05/99 | 1,000   | 20      | 31      | 38                | 100     | 510    | NT    | NT   | NT   | NT   | NT       | NT      | NT   | NT    |
| 1        |          | <10,000 | 110     | 38      | 79                | 140     | 4,200  | NT    | NT   | NT   | NT   | NT       | NT      | NT   | NT    |
| 1        | 09/15/99 | 20,000  | <100    | <100    | <100              | <100    | 20,000 | NT    | NT   | NT   | NT   | NT       | NT      | NT   | NT    |
| ļ        | 12/09/99 | 25,000  | <130    | <130    | <130              | <130    | 28,000 | NT    | NT   | NT   | NT   | NT       | NT      | NT   | NT    |
|          | 03/06/00 | <50     | <0.5    | <0.5    | <0.5              | <0.5    | 85     | NT    | NT   | NT   | NT   | NT       | NT      | NT   | NT    |
| Ļ        | 06/07/00 |         | 74      | 37      | 98                | 220     | 9,200  | NT    | NT   | NT   | NT   | NT       | NT      | NT   | NT    |
|          | 09/18/00 | 9,400   | <50     | <50     | <50               | <50     | 19,000 | NT    | NT   | NT   | NT   | NT       | NT      | NT   | NT    |

Table 3
Analytical Results for Groundwater Samples
2951 High Street
Oakland, California

| Well ID | Date     | TPH-g  | benzene | toluene | ethyl-<br>benzene | xylenes | MtBE   | DIPE | EtBE  | tAME | tBA  | methanol | ethanol | EDB      | DCA   |
|---------|----------|--------|---------|---------|-------------------|---------|--------|------|-------|------|------|----------|---------|----------|-------|
| MW-3    | 02/23/95 | <50    | <0.5    | <0.5    | <0.5              | <0.5    | NT     | NT   | NT    | NT   | NT   | NT       | NT      | NT       | NT    |
|         | 05/26/95 | <50    | <0.5    | <0.5    | <0.5              | <0.5    | NT     | NT   | NT    | NT   | NT   | NT       | NT      | NT       | NT    |
|         | 08/23/95 | <50    | <0.5    | <0.5    | <0.5              | <0.5    | NT     | NT   | NT    | NT   | NT   | NT       | NT      | NT       | NT    |
|         | 04/04/03 | <50    | <0.5    | <0.5    | <0.5              | <0.5    | 1,600  | <25  | <25   | <25  | <250 | <25,000  | <2,500  | <25      | <25   |
|         | 07/16/03 | <50    | <0.5    | <0.5    | <0.5              | <0.5    | 1,200  | <50  | <50   | <50  | <500 | <50,000  | <5,000  | <50      | <50   |
| *       | 10/28/03 | <50    | <0.5    | <0.5    | <0.5              | <0.5    | 1,400  | <50  | <50   | <50  | <500 | <50,000  | <5,000  | <50      | <50   |
|         | 01/13/04 | <200   | <2      | <2      | <2                | <2      | 790    | <2   | <2    | <2   | <20  | <200     | <20     | <2       | <2    |
|         | 04/29/04 | <50    | <0.5    | <0.5    | <0.5              | <0.5    | 140    | <5   | <5    | <5   | <50  | <5,000   | <500    | <u> </u> | <5    |
|         | 07/08/04 | <50    | <0.5    | <0.5    | <0.5              | <1.0    | 24.3   | <0.5 | <1    | <1   | <10  | NT       | <100    | <1.0     | <1.0  |
| İ       | 10/01/04 | <50    | <0.5    | <0.5    | <0.5              | <0.5    | 4.0    | <0.5 | <0.5  | <0.5 | <5.0 | <500     | <50     | <0.5     | < 0.5 |
|         | 01/03/05 | <50    | <0.5    | <0.5    | <0.5              | <0.5    | 49     | <1.0 | <1.0  | <1.0 | <10  | <1000    | <100    | <1.0     | <1.0  |
|         | 02/03/05 | <50    | <0.5    | <0.5    | <0.5              | <0.5    | 4.9    | <0.5 | <0.5  | <0.5 | <5.0 | <500     | <50     | <0.5     | <0.5  |
|         | 03/04/05 | <50    | <0.5    | <0.5    | <0.5              | <0.5    | 32     | <0.5 | <0.5  | <0.5 | <5.0 | <500     | <50     | <0.5     | 1.5   |
|         | 04/05/05 | <50    | <0.5    | <0.5    | <0.5              | <0.5    | 12     | <0.5 | <0.5  | <0.5 | <5.0 | <500     | <50     | <0.5     | <0.5  |
|         | 07/06/05 | <50    | <0.5    | <0.5    | <0.5              | <0.5    | 44     | <1.0 | <1.0  | <1.0 | <10  | <1000    | <100    | <1.0     | <1.0  |
|         | 10/04/05 | <50    | <0.5    | <0.5    | <0.5              | <0.5    | 2.5    | <0.5 | < 0.5 | <0.5 | <5.0 | <500     | <50     | <0.5     | <0.5  |
| MW-4    | 02/03/95 | 2,500  | 230     | 64      | 99                | 110     | 5,700  | NT   | NT    | NT   | NT   | NT       | NT      | NT       | NT    |
|         | 03/27/97 | 6,200  | 300     | 150     | 160               | 310     | 7,100  | NT   | NT    | NT   | NT   | NT       | NT      | NT       | NT    |
|         | 09/18/00 | 10,000 | 320     | <50     | 150               | 460     | 13,000 | NT   | NT    | NT   | NT   | NT       | NT      | NT       | NT    |

# Table 3 Analytical Results for Groundwater Samples 2951 High Street Oakland, California

| Well ID | Date     | TPH-g   | benzene | foluene | ethyl-<br>benzene | xylenes | MtBE   | DIPE  | EtBE  | tAME  | tBA    | methanol | ethanol | EDB  | DCA  |
|---------|----------|---------|---------|---------|-------------------|---------|--------|-------|---|---|--------|----------|---------|------|------|
| MW-5    | 12/13/96 | 3,600   | 180     | 350     | 81                | 510     | 430    | NT    | NT  | NT  | NT     | NT       | NT      | NT   | NT   |
|         | 03/27/97 | 120,000 | 28,000  | 16,000  | 2,600             | 10,000  | 64,000 | NT    | NT  | NT  | NT     | NT       | NT      | NT   | NT   |
| **      | 06/27/97 | 6,300   | 10,000  | 2,400   | 290               | 4,500   | 43,000 | NT    | NT  | NT  | NT     | NT       | NT      | NT   | NT   |
|         | 09/22/97 | <50,000 | 7.9     | 3.3     | 0.6               | 3.3     | 30,000 | NT    | NT  | NT  | NT     | NT       | NT      | NT   | NT   |
| [       | 12/06/97 | <5,000  | 33      | 12      | <5                | 7.3     | 33,000 | NT    | NT  | NT  | NT     | NT       | NT      | NT   | NT   |
|         | 03/23/98 | 29,000  | 150     | 160     | 130               | 320     | 34,000 | NT    | NT  | NT  | NT     | NT       | NT      | NT   | NT   |
|         | 06/10/98 | 53,000  | 7,000   | 2,400   | 540               | 3,400   | 67,000 | NT    | NT  | NT  | NT     | NT       | NT      | NT   | NT   |
|         | 07/23/98 | 36,000  | 1,000   | 270     | <120              | 740     | 51,000 | NT    | NT  | NT  | NT     | NT       | NT      | NT   | NT   |
| ***     | 09/16/98 | 56,000  | 3,400   | 1,300   | 430               | 1,800   | 84,000 | NT    | NT  | NT  | NT     | NT       | NT      | NT   | NT   |
|         | 11/23/98 | 63,000  | 5,700   | 2,900   | 500               | 2,200   | 87,000 | NT    | NT  | NT  | NT     | NT       | NT      | NT   | NT   |
| j       | 03/05/99 | 42,000  | <250    | <250    | <250              | <250    | 38,000 | NT    | NT  | NT  | NT     | NT       | NT      | NT   | NT   |
|         | 06/17/99 | 37,000  | 510     | 85      | 5.6               | 89      | 61,000 | NT :  | NT  | NT  | NT     | NT       | NT      | NT   | NT   |
|         | 09/15/99 | 54,000  | 8,500   | 1,800   | 420               | 2,400   | 55,000 | NT    | NT  | NT  | NT     | NT       | NT      | NT   | NT   |
|         | 12/09/99 | 34,000  | 1,600   | 230     | 130               | 570     | 33,000 | NT    | NT  | NT  | NT     | NT       | NT      | NT   | NT   |
|         | 03/06/00 | 21,000  | 7,800   | 870     | 440               | 2,100   | 30,000 | NT    | NT  | NT  | NT     | NT       | NT      | NT   | NT   |
| [       | 06/07/00 | <50,000 | 11,000  | 890     | 570               | 3,000   | 68,000 | NT    | NT  | NT  | NT     | NT       | NT      | NT   | NT   |
| [       | 09/18/00 | 40,000  | 4,900   | <250    | <250              | 1,700   | 46,000 | NT    | NT  | NT  | NT     | NT       | NT      | NT   | NT   |
| [       | 04/04/03 | 1,800   | 560     | <5.0    | <5.0              | 30      | 19,000 | <330  | <330  | <330  | <3,300 | <330,000 | <33,000 | <330 | <330 |
| [       | 07/16/03 | 2,800   | 1,000   | <5      | 10                | 80      | 16,000 | <200  | <200  | <200  | <2,000 | <200,000 | <20,000 | <200 | <200 |
|         | 10/28/03 | 740     | 290     | <5.0    | <5.0              | 7.2     | 14,000 | <170  | <170  | <170  | <1,700 | <170,000 | <17,000 | <170 | <170 |
|         | 01/13/04 | <500    | 48      | <5      | <5                | <5      | 2,000  | <5    | <5  | <5  | <50    | <500     | <50     | <5   | <5   |
|         | 04/14/04 | 6,600   | 2,700   | <50     | <50               | 260     | 20,000 | <500  | <500  | <500  | <5,000 | <500,000 | <50,000 | <500 | <500 |
| *       | 04/29/04 | <500    | 6.3     | <5      | <5                | 7.8     | 11,000 | <250  | <250  | <250  | <2,500 | <250,000 | <25,000 | <250 | <250 |
|         | 05/13/04 | <50     | <0.5    | <0.5    | <0.5              | <0.5    | 3,000  | <50   | <50   | <50   | <500   | <50,000  | <5,000  | <50  | <50  |
|         | 05/26/04 | <50     | <0.5    | < 0.5   | < 0.5             | <0.5    | 460    | <10   | <10   | <10   | <100   | <10,000  | <1,000  | <10  | <10  |
|         | 06/10/04 | <50     | < 0.5   | <0.5    | < 0.5             | <0.5    | 38     | <0.5  | <0.5  | <0.5  | <5.0   | <50      | <5.0    | <0.5 | <0.5 |
|         | 07/08/04 | <50     | 1.5     | <0.5    | <0.5              | <1.0    | 9.6    | <0.5  | <i< td=""><td><i< td=""><td>&lt;10</td><td>NT</td><td>&lt;100</td><td>&lt;1.0</td><td>&lt;0.5</td></i<></td></i<> | <i< td=""><td>&lt;10</td><td>NT</td><td>&lt;100</td><td>&lt;1.0</td><td>&lt;0.5</td></i<> | <10    | NT       | <100    | <1.0 | <0.5 |
| Ī       | 10/01/04 | <50     | <0.5    | <0.5    | <0.5              | <0.5    | 1.7    | < 0.5 | <0.5  | <0.5  | <5.0   | <500     | <50     | <0.5 | <0.5 |
| Ī       | 01/03/05 | <50     | <0.5    | <0.5    | <0.5              | <0.5    | 2.2    | <0.5  | <0.5  | <0.5  | <5.0   | <500     | <50     | <0.5 | <0.5 |
| Ī       | 02/03/05 | <50     | <0.5    | <0.5    | <0.5              | <0.5    | 4.2    | <0.5  | <0.5  | <0.5  | <5.0   | <500     | <50     | <0.5 | <0.5 |
| Ī       | 03/04/05 | <50     | <0.5    | <0.5    | < 0.5             | <0.5    | 1.8    | <0.5  | <0.5  | <0.5  | <5.0   | <500     | <50     | <0.5 | <0.5 |
| Ī       | 04/05/05 | <50     | <0.5    | <0.5    | <0.5              | <0.5    | 14     | <0.5  | <0.5  | <0.5  | <5.0   | <500     | <50     | <0.5 | <0.5 |
| Ī       | 07/06/05 | <50     | <0.5    | <0.5    | <0.5              | <0.5    | 6.2    | <0.5  | <0.5  | <0.5  | <5.0   | <500     | <50     | <0.5 | <0.5 |
|         | 10/04/05 | <50     | <0.5    | <0.5    | <0.5              | <0.5    | 4.4    | <0.5  | <0.5  | <0.5  | <5.0   | <500     | <50     | <0.5 | <0.5 |

Table 3
Analytical Results for Groundwater Samples
2951 High Street
Oakland, California

| Well ID | Date     | ТРН-g | benzene | toluene | ethyl-<br>benzene | xylenes | MtBE | DIPE | ÈtBE | tAME  | tBA  | methanol | ethanol | EDB  | DCA   |
|---------|----------|-------|---------|---------|-------------------|---------|------|------|------|-------|------|----------|---------|------|-------|
| MW-6    | 01/13/97 | <50   | <0.5    | <0.5    | <0.5              | <0.5    | <5   | NT   | NT   | NT    | NT   | NT       | NT      | NT   | NT    |
|         | 03/27/97 | <50   | <0.5    | <0.5    | <0.5              | <0.5    | <5   | NT   | NT   | NT    | NT   | NT       | NT      | NT   | NT    |
|         | 06/27/97 | <50   | <0.5    | <0.5    | <0.5              | <0.5    | <5   | NT   | NT   | NT    | NT   | NT       | NT      | NT   | NT    |
|         | 09/22/97 | <50   | <0.5    | <0.5    | <0.5              | <0.5    | 24   | NT   | NT   | NT    | NT   | NT       | NT      | NT   | NT    |
|         | 12/06/97 | 94    | <0.5    | <0.5    | <0.5              | <0.5    | <5   | NT   | NT   | NT    | NT   | NT       | NT      | NT   | NT    |
|         | 03/23/98 | <50   | <0.5    | <0.5    | <0.5              | <0.5    | <5   | NT   | NT   | NT    | NT   | NT       | NT      | NT   | NT    |
|         | 06/10/98 | <50   | <0.5    | <0.5    | <0.5              | <0.5    | <5   | NT   | NT   | NT    | NT   | NT       | NT      | NT   | NT    |
|         | 07/23/98 | <50   | <0.5    | <0.5    | <0.5              | <0.5    | <5   | NT   | NT   | NT    | NT   | NT       | NT      | NT   | NT    |
|         | 09/16/98 | <50   | <0.5    | <0.5    | <0.5              | <0.5    | <5   | NT   | NT   | NT    | NT   | NT       | NT      | NT   | NT    |
|         | 03/05/99 | 55    | <0.5    | 0.92    | 0.5               | 1.3     | <5   | NT   | NT   | NT    | NT   | NT       | NT      | NT   | NT    |
|         | 06/17/99 | <50   | <0.5    | <0.5    | <0.5              | <0.5    | 8.0  | NT   | NT   | NT    | NT   | NT       | NT      | NT   | NT    |
|         | 09/15/99 | <50   | <0.5    | <0.5    | <0.5              | <0.5    | <5   | NT   | NT   | NT    | NT   | NT       | NT      | NT   | NT    |
|         | 12/09/99 | <50   | <0.5    | <0.5    | <0.5              | <0.5    | <5   | NT   | NT   | NT    | NT   | NT       | NT      | NT   | NT    |
|         | 03/06/00 | <50   | <0.5    | <0.5    | <0.5              | <0.5    | <5   | NT   | NT   | NT    | NT   | NT       | NT      | NT   | NT    |
|         | 06/07/00 | <50   | <0.5    | <0.5    | <0.5              | <0.5    | <5   | NT   | NT   | NT    | NT   | NT       | NT      | NT   | NT    |
|         | 04/04/03 | <50   | <0.5    | <0.5    | <0.5              | <0.5    | <0.5 | <0.5 | <0.5 | <0.5  | <5.0 | <500     | <50     | <0.5 | <0.5  |
|         | 07/16/03 | <50   | <0.5    | <0.5    | <0.5              | <0.5    | 0.54 | <0.5 | <0.5 | <0.5  | <5   | <500     | <50     | <0.5 | <0.5  |
|         | 10/28/03 | <50   | <0.5    | <0.5    | <0.5              | < 0.5   | <0.5 | <0.5 | <0.5 | <0.5  | <5   | <500     | <50     | <0.5 | <0.5  |
| j       | 01/13/04 | <50   | <0.5    | <0.5    | <0.5              | <0.5    | <0.5 | <0.5 | <0.5 | <0.5  | <5   | <50      | <5      | <0.5 | <0.5  |
| *       | 04/29/04 | <50   | <0.5    | <0.5    | <0.5              | <0.5    | <0.5 | <0.5 | <0.5 | <0.5  | <5   | <500     | <50     | <0.5 | <0.5  |
|         | 07/08/04 | <50   | <0.5    | <0.5    | <0.5              | <1.0    | <0.5 | <0.5 | <1   | <1    | <10  | NT       | <100    | <1.0 | <0.5  |
|         | 10/01/04 | <50   | <0.5    | <0.5    | <0.5              | <0.5    | <0.5 | <0.5 | <0.5 | <0.5  | <5   | <500     | <50     | <0.5 | <0.5  |
| ĺ       | 01/03/05 | <50   | <0.5    | <0.5    | <0.5              | <0.5    | <0.5 | <0.5 | <0.5 | < 0.5 | <5   | <500     | <50     | <0.5 | <0.5  |
| ļ       | 04/05/05 | <50   | <0.5    | <0.5    | <0.5              | <0.5    | <0.5 | <0.5 | <0.5 | <0.5  | <5   | <500     | <50     | <0.5 | <0.5  |
|         | 07/06/05 | <50   | <0.5    | <0.5    | <0.5              | <0.5    | <0.5 | <0.5 | <0.5 | <0.5  | <5   | <500     | <50     | <0.5 | < 0.5 |
|         | 10/04/05 | <50   | <0.5    | <0.5    | <0.5              | <0.5    | <0.5 | <0.5 | <0.5 | <0.5  | <5   | <500     | <50     | <0.5 | <0.5  |

## Table 3 Analytical Results for Groundwater Samples 2951 High Street Oakland, California

| Well-ID | Date     | TPH-g  | benzene | toluene | ethyl-<br>benzene | xylenes | MtBE   | DIPE | EtBE | tAME  | tBA    | methanol | ethanol | EDB  | DCA  |
|---------|----------|--------|---------|---------|-------------------|---------|--------|------|------|-------|--------|----------|---------|------|------|
| MW-7    | 04/04/03 | 1,400  | 54      | 27      | 15                | 180     | 26,000 | <500 | <500 | <500  | <5,000 | <500,000 | <50,000 | <500 | <500 |
|         | 07/16/03 | 18,000 | 1,100   | 630     | 1,100             | 2,000   | 13,000 | <200 | <200 | <200  | <2,000 | <200,000 | <20,000 | <200 | <200 |
|         | 10/28/03 | 10,000 | 750     | 370     | 750               | 1,000   | 17,000 | <500 | <500 | <500  | <5,000 | <500,000 |         | <500 | <500 |
|         | 01/13/04 | 7,200  | 430     | 150     | 560               | 550     | 22,000 | <50  | <50  | <50   | <500   | <5000    | <500    | <50  | <50  |
|         | 04/14/04 | 8,900  | 520     | 360     | 640               | 1,100   | 21,000 | <500 | <500 | <500  | <5,000 | <500,000 | <50,000 | <500 | <500 |
| *       | 04/29/04 | <500   | <5      | <5      | <5                | 12      | 12,000 | <250 | <250 | <250  | <2,500 | <250,000 | <25,000 | <250 | <250 |
|         | 05/13/04 | 660    | <5.0    | 28      | 25                | 120     | 10,000 | <170 | <170 | <170  | <1,700 | <170,000 | <17,000 | <170 | <170 |
|         | 05/26/04 | 380    | <2.5    | 15      | 15                | 79      | 7,600  | <200 | <200 | <200  | <2,000 | <200,000 | <20,000 | <200 | <200 |
|         | 06/10/04 | <1,000 | <10     | <10     | <10               | <10     | 4,900  | <10  | <10  | <10   | 300    | <10,000  | <100    | <10  | <10  |
|         | 07/08/04 | 67     | <0.5    | <0.5    | 1.3               | 10      | 1,040  | <0.5 | <1   | <1    | <10    | NT       | <100    | <1.0 | <0.5 |
|         | 10/01/04 | 85     | <0.5    | <0.5    | 0.63              | 6.0     | 2,300  | <50  | <50  | <50   | <500   | <50,000  | <5,000  | <50  | <50  |
|         | 01/03/05 | <50    | <0.5    | <0.5    | <0.5              | <0.5    | 130    | <2.5 | <2.5 | <2.5  | <25    | <2500    | <250    | <2.5 | 3.2  |
|         | 02/03/05 | <50    | <0.5    | <0.5    | <0.5              | <0.5    | 4.5    | <0.5 | <0.5 | < 0.5 | <5     | <500     | <50     | <0.5 | 2.9  |
|         | 03/04/05 | <50    | <0.5    | <0.5    | <0.5              | <0.5    | 21     | <0.5 | <0.5 | <0.5  | <5     | <500     | <50     | <0.5 | <0.5 |
|         | 04/05/05 | <50    | <0.5    | <0.5    | <0.5              | < 0.5   | 6.7    | <0.5 | <0.5 | <0.5  | <5     | <500     | <50     | <0.5 | 3.2  |
|         | 07/06/05 | <50    | <0.5    | <0.5    | <0.5              | <0.5    | 18     | <0.5 | <0.5 | <0.5  | <5     | <500     | <50     | <0.5 | 2.0  |
|         | 10/04/05 | <50    | <0.5    | <0.5    | <0.5              | <0.5    | 18     | <0.5 | <0.5 | <0.5  | <5     | <500     | <50     | <0.5 | 1.1  |
| MW-8    | 04/04/03 | <50    | <0.5    | <0.5    | <0.5              | <0.5    | 230    | <5   | <5   | <5    | <50    | <5,000   | <500    | <5   | <5   |
|         | 07/16/03 | <50    | <0.5    | <0.5    | <0.5              | <0.5    | 340    | <5   | <5   | <5    | <50    | <5,000   | <500    | <5   | <5   |
|         | 10/28/03 | <50    | <0.5    | <0.5    | <0.5              | <0.5    | 250    | <5.0 | <5.0 | <5.0  | <50    | <5,000   | <500    | <5   | <5.0 |
| ļ       | 01/13/04 | <50    | <0.5    | <0.5    | <0.5              | <0.5    | 140    | <0.5 | <0.5 | <0.5  | <5.0   | <50      | <5      | <0.5 | <0.5 |
|         | 04/14/04 | <50    | <0.5    | <0.5    | <0.5              | <0.5    | 260    | <5   | <5   | <5    | <50    | <5,000   | <500    | <5   | <5   |
| *       | 04/29/04 | <50    | <0.5    | <0.5    | <0.5              | <0.5    | 130    | <5   | <5   | <5    | <50    | <5,000   | <500    | <5   | <5   |
|         | 05/13/04 | <50    | <0.5    | <0.5    | <0.5              | <0.5    | 110    | <2.5 | <2.5 | <2.5  | <25    | <2,500   | <250    | <2.5 | <2.5 |
|         | 05/26/04 | <50    | <0.5    | <0.5    | <0.5              | <0.5    | 150    | <2.5 | <2.5 | <2.5  | <25    | <2,500   | <250    | <2.5 | <2.5 |
| ļ       | 06/10/04 | <50    | < 0.5   | <0.5    | <0.5              | <0.5    | 290    | <0.5 | <0.5 | <0.5  | <5.0   | <50      | <5.0    | <0.5 | <0.5 |
|         | 07/08/04 | <50    | <0.5    | <0.5    | <0.5              | <1.0    | 395    | <0.5 | <1   | <1    | <10    | NT       | <100    | <1.0 | <0.5 |
| ļ       | 10/01/04 | <50    | <0.5    | <0.5    | <0.5              | <0.5    | 450    | <10  | <10  | <10   | <100   | <10,000  | <5.0    | <0.5 | <0.5 |
|         | 01/03/05 | <50    | <0.5    | <0.5    | <0.5              | <0.5    | 330    | <5   | <5   | <5    | <50    | <5,000   | <500    | <5   | <5   |
| ļ       | 02/03/05 | <50    | <0.5    | <0.5    | <0.5              | <0.5    | 360    | <5   | <5   | <5    | 53     | <5,000   | <500    | <5   | <5   |
| Ļ       | 03/04/05 | <50    | <0.5    | <0.5    | <0.5              | <0.5    | 180    | <5   | <5   | <5    | 53     | <5,000   | <500    | <5   | <5   |
| 1       | 04/05/05 | <50    | <0.5    | <0.5    | <0.5              | <0.5    | 140    | <2.5 | <2.5 | <2.5  | 29     | <2500    | <250    | <2.5 | <2.5 |
| Ĺ       | 07/06/05 | <50    | <0.5    | <0.5    | <0.5              | <0.5    | 160    | <2.5 | <2.5 | <2.5  | 29     | <2500    | <250    | <2.5 | <2.5 |
|         | 10/04/05 | <50    | <0.5    | <0.5    | <0.5              | <0.5    | 320    | <5   | <5   | <5    | <50    | <5,000   | <500    | <5   | <5   |

Table 3 **Analytical Results for Groundwater Samples** 2951 High Street Oakland, California

| S 04 N T    | Fried Zan  | AND THE RESERVE | 1       |         |                   | - Oan       | uand, Ca            | annorma | :         |             |              |               |              |                  |              |
|-------------|--|-----------------|---------|---------|-------------------|-------------|---------------------|---------|-----------|-------------|--------------|---------------|--------------|------------------|--------------|
| Well ID     | Date   | TPH-g           | benzene | toluene | ethyl-<br>benzene | xylenes     | MtBE                | DIRE    | EtBE      | tAME        | tBA          | methanol      | ethanol      | EDB              | DCA          |
| MW-9        | 04/04/03   |                 | <0.5    | <0.5    | <0.5              | <0.5        | 85                  | <1.5    | <1.5      | <1.5        | <12          | 41.000        | a Same para  | Marine de Ad     | and the same |
|             | 07/16/03   |                 | <0.5    | <0.5    | <0.5              | <0.5        | 170                 | <2.5    | <2.5      | 3           | 27           | <1,200        | <120         | <1.5             | 2            |
|             | 10/28/03   |                 | <0.5    | <0.5    | <0.5              | <0.5        | 230                 | <5.0    | <5.0      | <5.0        | 57           | <2,500        | <250         | <2.5             | <2.5         |
|             | 01/13/04   |                 | <0.5    | <0.5    | <0.5              | <0.5        | 55                  | <0.5    | <0.5      | 0.72        | 5.8          | <5,000        | <500         | <5.0             | <5.0         |
|             | 04/14/04   |                 | <0.5    | <0.5    | <0.5              | <0.5        | 58                  | <1      | <1        | <1          |              | <50           | <5           | <0.5             | 1            |
| * [         | 04/29/04   | <50             | <0.5    | <0.5    | <0.5              | <0.5        | 4.7                 | <0.5    | <0.5      | <0.5        | <10<br><5    | <1,000        | <100         | <1               | <u> </u>     |
| Ĺ           | 05/13/04   | <50             | <0.5    | <0.5    | <0.5              | <0.5        | 5.9                 | <0.5    | <0.5      | <0.5        | <del></del>  | <500          | <50          | <0.5             | 0.63         |
| -           | 05/26/04   | <50             | <0.5    | <0.5    | <0.5              | <0.5        | 2.5                 | <0.5    | <0.5      | <0.5        | <5.0         | <50           | <5.0         | <0.5             | 0.66         |
| 1           | 06/10/04   | <50             | <0.5    | <0.5    | <0.5              | <0.5        | 14                  | <0.5    | <0.5      | <del></del> | <5.0         | <500          | <50          | <0.5             | 0.53         |
| Į           | 07/08/04   | <50             | <0.5    | <0.5    | <0.5              | <1.0        | 7.3                 | <0.5    | <1        | <0.5        | <5.0         | <50           | <5.0         | <0.5             | 0.60         |
| L           | 10/01/04   | <50             | <0.5    | <0.5    | <0.5              | <0.5        | 2.1                 | <0.5    | <0.5      | <1<br><0.5  | <10          | NT            | <100         | <1.0             | <0.5         |
| L           | 01/03/05   | <50             | <0.5    | <0.5    | <0.5              | <0.5        | 4.0                 | <0.5    | <0.5      | <0.5        | <5.0         | <500          | <50          | <0.5             | <0.5         |
| L           | 04/05/05   | <50             | <0.5    | <0.5    | <0.5              | <0.5        | 48                  | <0.5    | <0.5      | 0.75        | <5.0         | <500          | <50          | <0.5             | <0.5         |
| <u></u>     | 07/06/05   | <50             | <0.5    | <0.5    | <0.5              | <0.5        | 18                  | <0.5    | <0.5      | <0.5        | 13           | <500          | <50          | <0.5             | <0.5         |
|             | 10/04/05   | <50             | <0.5    | <0.5    | <0.5              | <0.5        | 19                  | <0.5    | <0.5      | <0.5        | <5.0<br><5.0 | <500          | <50          | <0.5             | <0.5         |
| 1W-10       | 04/23/03   | 79              | <0.5    | <0.5    | <0.5              | < 0.5       | 1,900               | <25     | <25       | 58          |              | <500          | <50          | <0.5             | <0.5         |
|             | 07/16/03   | 73              | 20      | <0.5    | <0.5              | <0.5        | 1,100               | <20     | <20       | 39          | <250         | <25,000       | <2,500       | <25              | _<25         |
| <u>-</u> -  | 10/28/03   | 76              | <0.5    | <0.5    | <0.5              | <0.5        | 1,900               | <50     | <50       | <50         | <200         | <20,000       | <2,000       | <20              | <20          |
| <del></del> | 01/13/04   | <500            | <5      | <5      | <5                | <5          | 2,300               | <5      | <5        | 72          | <500         | <50,000       | <5,000       | <50              | <50          |
|             | 04/29/04   | 54              | <0.5    | <0.5    | <0.5              | <0.5        | 1,000               | <17     | <17       | 24          | <50          | <500          | <50          | <5               | <5           |
| L.          | 07/08/04   | 76              | <0.5    | <0.5    | <0.5              | <1.0        | 1,650               | <0.5    | <1        | 37          | <170         | <17,000       | <1,700       | <17              | <17          |
|             | 10/01/04   | 67              | <0.5    | <0.5    | <0.5              | <0.5        | 1,500               | <50     | <50       | <50         | 211          | NT            | <100         | <1.0             | <0.5         |
|             | 01/03/05   | 62              | <0.5    | <0.5    | <0.5              | <0.5        | 1,700               | <25     | <25       | <25         | <500         |               | <5,000       | <50              | <50          |
| Ľ           | 04/05/05   | <50             | <0.5    | <0.5    | <0.5              | <0.5        | 520                 | <17     | <17       | <17         | <250         |               | <2,500       | <25              | <25          |
| <u> </u>    | 07/06/05   | <50             | <0.5    | <0.5    | <0.5              | <0.5        | 420                 | <5      | <5        | 12          | 230          |               | <1,700       | <17              | <17          |
|             | 10/04/05   | <50             | <0.5    | <0.5    | <0.5              | <0.5        |                     |         |           |             | <50          | <5,000        | <500         | <5               | <5           |
| SSTL        | is a second seco | NE              | 34      | 270     |                   |             |                     |         |           |             |              |               |              |                  | <10          |
| SSTE        | (37 ) VPV (326 (36) 83<br>(37 ) VPV (326 (36) 83<br>(37 ) VPV (326 (36) 83   | NE              | 3/4     |         | <0.5<br>180       | <0.5<br>470 | 490<br><b>8,400</b> | <10 NE  | <10<br>NE | <10<br>NE   | <100<br>NE   | <10,000<br>NE | <1,000<br>NE | <10<br><b>NE</b> |              |

SSTLs are site-specific target levels developed for the site by Aqua Science Engineers, Inc. in 1997. Bold concentrations exceed the SSTL.

Concentrations are micrograms per liter (ug/L). NE, SSTL not established for this compound. NT, analyte not tested.

Data prior to April 2003 are from Groundwater Monitoring Report for September 2000 Sampling by Aqua Science Engineers, Inc. dated 11/14/2000.

- First sampling event after the OS system was started up on April 14, 2004.
- \*\* Oxygen Release Compound (ORC) was injected into borings on the south side of MW-5 in late June 1997.
- ORC socks were placed in MW-5 in August 1998 and removed in September 2000.

TPH-g total petroleum hydrocarbons as gasoline MtBE methyl tert-butyl ether

ethyl tert-butyl ether EtBE tAME tert-amyl methyl ether

ethylene dibromide (1,2-dibromoethane) **EDB** DCA 1,2-dichloroethane


DIPE di-isopropyl ether

tBA tert-butyl alcohol

## **APPENDIX E**

Historical Groundwater and Soil Sample

Tables and Figures




Cook Environmental Services, Inc.

271 Las Juntas Way Walnut Creek, CA 94597 (925) 937-1759 work (925) 937-6869 cell cookenvironmental@att.net

### **Site Features**

Express Gas & Mart 2951 High Street Oakland, California

| Project #: 1004 | Figure: |
|-----------------|---------|
| Date: 6/1/06    | 7       |
| Scale: 1"=30'   |         |




DAKLAND, CA

JDB # 3936

**6940 TREMONT ROAD** 

DIXON, CALIFORNIA 95620 PH# (707) 693-2929 LIC# 455752



Site Мар

ENVIRONMENTAL CONSULTING AND CONTRACTING




W.A. CRAIG, INC.

6940 TREMONT ROAD DIXON, CALIFORNIA 95620 PH# (707) 693-2929 LIC# 455752

Project Name and Address

EXPRESS GAS & MART 2951 HIGH STREET DAKLAND, CA JDB # 3936

FIGURE #



ENVIRONMENTAL CONSULTING AND CONTRACTING




W.A. CRAIG, INC.

6940 TREMONT ROAD DIXON, CALIFORNIA 95620 PH# (707) 693-2929 UC# 455752

EXPRESS GAS & MART 2951 HIGH STREET DAKLAND, CA JOB # 3936

5-9-01



ENVIRONMENTAL CONSULTING AND CONTRACTING





W.A. CRAIG, INC.

6940 TREMONT ROAD DIXON, CALIFORNIA 95620 PH# (707) 693-2929 LIC# 455752 Project Name and Address

EXPRESS GAS & MART 2951 HIGH STREET DAKLAND, CA JOB # 3936 FIGURE #

5-10-01





Project Name and Address

EXPRESS GAS & MART


2951 HIGH STREET

DAKLAND, CA

JOB # 3936

FIGURE # 5-15-01

DATE: 5-16-01 Collect samples e1-sw-w (8' deep sidewall) e2-sw-s (8' deep sidewall) e3-sw-e (9' deep sidewall) e4-sw-n (8' deep sidewall) EXISTING UNDERGROUND TANKS 2-5,000 GALLON AND 2-4,000 GALLON PENNIMAN DRIVEWAY SIDEWALK DRIVEWAY 2951 HIGH STREET 3-5V-E 2-4V-S 4-SW-N 1-SV-V BUILDING DISPENSER (TYP) APPROX 19'-0" DRIVE SLAB AND DISPENSER ISLANDS LANDSCAPE Excavation and sampling Site Map






W.A. CRAIG, INC.

6940 TREMONT ROAD DIXON, CALIFORNIA 95620 PH# (707) 693-2929 LIC# 455752 Project Name and Address

EXPRESS GAS & MART 2951 HIGH STREET DAKLAND, CA JOB # 3936 FIGURE # 5-16-01




ENVIRONMENTAL CONSULTING AND CONTRACTING



W.A. CRAIG, INC.

6940 TREMONT ROAD DIXON, CALIFORNIA 95620 PH# (707) 693-2929 UC# 455752 Project Name and Address

EXPRESS GAS & MART 2951 HIGH STREET DAKLAND, CA JOB # 3936 FIGURE # 5-18-01




CONSULTING AND CONTRACTING

W.A. CRAIG, INC.

4940 TREMONT ROAD TIXON, CALIFORNIA 95620 MI (707) 693-2929 424 455752 Project Name and Address

EXPRESS GAS & MART 2951 HIGH STREET DAKLAND, CA JOB # 3936 FIGURE # 5-31-01



WRONMENTAL CONSULTING AND CONTRACTING




W.A. CRAIG, INC.

6940 TREMONT ROAD DIXON, CALIFORNIA 95620 PH# (707) 693-2929 UC# 455752

EXPRESS GAS & MART 2951 HIGH STREET DAKLAND, CA JDB # 3936

6-11-01




MENTAL CONSULTING AND CONTRACTING

W.A. CRAIG, INC.

6940 TREMONT ROAD DIXON, CALIFORNIA 95620 PH# (707) 693-2929 UC# 455752 Project Name and Address

EXPRESS GAS & MART 2951 HIGH STREET DAKLAND, CA JOB # 3936 FIGURE # 7-19-01



W.A. CRAIG, INC.

40 TREMONT ROAD

CON, CALIFORNIA 95620

(707) 693-2929

455752

Project Name and Address


EXPRESS GAS & MART 2951 HIGH STREET DAKLAND, CA JDB # 3936


Excavation Date: 8-27-01
11' X 25' X 14' (150 Yards)
Date: 8-28-01 soil sample

PB-1 (14' DEEP PIT BUT) no odor or color

SW-1 Side wall samples
9'-0' below grade strong pet hyd odor

SP-1-4 (1) 4 PUINT CUMPUSITE STUCKPILE










W.A. CRAIG, INC.

6940 TREMONT ROAD DIXON, CALIFORNIA 95620 PH# (707) 693-2929 LIC# 455752 Project Name and Address

EXPRESS GAS & MART 2951 HIGH STREET DAKLAND, CA JDB # 3936 figure # 8-28-01







JDB # 3936

PH# (707) 693-2929

UC# 455752

## TABLE 1 Boring Analytical Data High Street Station Oakland, CA

| Sample<br>ID | Date     | Media | Depth (fbg) | ТРН-g  | MtBE   | TAME    | benzene | toluene | ethyl-<br>benzen<br>e | xylenes |
|--------------|----------|-------|-------------|--------|--------|---------|---------|---------|-----------------------|---------|
| S-1          | 02/28/01 | soil  | 3           | 180    | 4      | 0.17    | 0.14    | 5.8     | 3.2                   | 22      |
| S-2          | 02/28/01 | soil  | 3           | 71     | 6.8    | 0.19    | 0.2     | 2.8     | 1.7                   | 6.2     |
| S-3          | 02/28/01 | soil  | 3           | 370    | 2.9    | 0.13    | 0.26    | 2.1     | 2.5                   | 15      |
| S-4          | 02/28/01 | soil  | 3           | 180    | 0.3    | < 0.01  | 0.12    | 0.95    | 1.3                   | 16      |
| S-5          | 02/28/01 | soil  | 3           | 3,600  | 2.3    | <1      | 2,6     | 15      | 49                    | 340     |
| S-6          | 02/28/01 | soil  | 3           | 730    | 85     | 4.7     | 4       | 49      | 8.6                   | 62      |
| TB-1         | 04/26/01 | soil  | 5           | 320    | 2.3    | < 0.050 | 0.57    | 1.3     | 5.4                   | 30      |
| TB-1         | 04/26/01 | soil  | 10          | 39     | 2.4    | 0.042   | 0.045   | 0.2     | 0.71                  | 3,3     |
| TB-2         | 04/26/01 | soil  | 5           | 34     | 0.38   | 0.024   | 0.031   | 0.19    | 0.5                   | 1.5     |
| TB-2         | 04/26/01 | soil  | 10          | 2.8    | 3.1    | 0.071   | 0.025   | 0.012   | 0.14                  | 0.11    |
| TB-3         | 04/26/01 | soil  | 5           | 4,000  | 4      | < 0.5   | 0.88    | 21      | 82                    | 410     |
| TB-3         | 04/26/01 | soil  | 10          | <1     | 4.3    | 0.054   | < 0.005 | <0.005  | < 0.005               | 0.014   |
| TB-4         | 04/26/01 | soil  | 5           | 21     | 0.24   | < 0.005 | <0.005  | 0.11    | 0.032                 | 0.21    |
| TB-4         | 04/26/01 | soil  | 10          | 2.9    | 1.8    | 0.039   | 0.01    | 0.014   | 0.055                 | 0.056   |
| TB-6         | 04/26/01 | soil  | 5           | 9.3    | <0.005 | <0.005  | <0.005  | 0.052   | 0.02                  | < 0.005 |
| TB-6         | 04/26/01 | soil  | 10          | 840    | 12     | <0.35   | 14      | 7.7     | 17                    | 76      |
| TB-9         | 04/26/01 | soil  | 5           | <1     | 4      | 0.037   | < 0.005 | <0.005  | < 0.005               | < 0.005 |
| TB-9         | 04/26/01 | soil  | 10          | 1.1    | 1.5    | 0.044   | <0.005  | <0.005  | < 0.005               | < 0.005 |
| SSTL         |          | soil  |             | 100    | 9.7    | NE      | 2.6     | 1.6     | 1.9                   | 2.8     |
| TB-1         | 04/26/01 | water | NA          | 78,000 | 37,000 | 1,500   | 880     | 490     | 3,200                 | 15,000  |
| TB-3         | 04/26/01 | water | NA          | 44,000 | 52,000 | <1,700  | 390     | 53      | 2,600                 | 8,900   |
| SSTL         |          | water |             | NE     | 8,400  | NE      | 200     | 270     | 180                   | 470     |

Notes: Soil sample units are mg/kg

Groundwater sample units are ug/l Results higher than SSTLs are in **bold** 

## TABLE 2 Remediation Soil Samples High Street Station

| Sample ID   | Date     | ТРН-д | TPH-d | MtBE  | benzene | toluene | ethyl-<br>benzene | xylenes | lead |
|-------------|----------|-------|-------|-------|---------|---------|-------------------|---------|------|
| S-7         | 05/09/01 | ND    | NT    | 3.8   | ND      | ND      | ND                | ND      | NT   |
| S-8         | 05/09/01 | ND    | NT    | 1.3   | 0.011   | ND      | 0.024             | 0.037   | NT   |
| <b>S-</b> 9 | 05/09/01 | ND    | NT    | 1     | 0.006   | 0.005   | 0.07              | 0.011   | NT   |
| S-10        | 05/09/01 | ND    | NT    | 1     | 0.007   | 0.005   | 0.018             | 0.043   | NT   |
| S-11        | 05/09/01 | ND    | NT    | 0.84  | ND      | ND      | ND                | ND      | NT   |
| S-12        | 05/09/01 | ND    | NT    | 0.55  | ND      | ND      | ND                | ND      | NT   |
| S-13        | 05/10/01 | ND    | NT    | 0.076 | 0.014   | ND      | ND                | ND      | NT   |
| S-14        | 05/10/01 | ND    | NT    | 2     | ND      | ND      | ND                | ND      | NT   |
| S-15        | 05/10/01 | ND    | NT    | ND    | ND      | ND      | ND                | ND      | NT   |
| SP 1-4      | 05/10/01 | 790   | NT    | ND    | 2       | 20      | 12                | 73      | 16   |
| SP 5-8      | 05/10/01 | 860   | NT    | ND    | 4       | 22      | 15                | 69      | 36   |
| SP 9-12     | 05/10/01 | 170   | NT    | ND    | ND      | 3.1     | 1.9               | 12      | 12   |
| SP 13-16    | 05/15/01 | 110   | 71    | ND    | ND      | 0.34    | 0.19              | 3.1     | 20   |
| SP 17-20    | 05/15/01 | 1100  | 200   | ND    | 0.41    | 8       | 3,3               | 67      | 16   |
| SP 21-24    | 05/15/01 | 1100  | 260   | ND    | 0.6     | 9.8     | 2                 | 120     | 19   |
| SP 25-28    | 05/15/01 | 930   | 190   | ND    | 3,7     | 28      | 10                | 100     | 16   |
| SP 29-32    | 05/15/01 | 760   | 220   | ND    | ND      | 3.2     | 1.4               | 45      | 20   |
| SP 33-36    | 05/15/01 | 57    | 16    | ND    | 0.45    | 0.35    | 2                 | 2       | 14   |
| 1-SW-W      | 05/16/01 | 1700  | NT    | ND    | 10      | 28      | 34                | 170     | 7.6  |
| 2-SW-S      | 05/16/01 | 460   | NT    | ND    | 2.4     | 20      | 7.7               | 44      | 10   |
| 3-SW-E      | 05/16/01 | 170   | NT    | 3,5   | 3.8     | 8.8     | 3,4               | 19      | 5,9  |
| 4-SW-N      | 05/16/01 | 350   | NT    | ND    | 2.6     | 2.7     | 17                | 2.5     | 9.1  |
| PB-1        | 05/18/01 | 1.3   | NT    | 0.93  | 0,3     | ND      | 0.017             | ND      | NT   |
| PB-2        | 05/18/01 | ND    | NT    | 0.55  | ND      | ND      | ND                | ND      | NT   |
| PB-3        | 05/18/01 | 2.5   | NT    | 33    | 0.9     | 0.049   | 0.035             | 0.059   | NT   |
| SW-1-E      | 05/18/01 | 17    | NT    | 5.6   | 2       | 0.085   | 1.3               | 0.98    | NT   |
| SW-2-W      | 05/18/01 | 590   | NT    | 7.4   | 16      | 47      | 18                | 97      | NT   |
| SW-3-W      | 05/18/01 | 700   | NT    | ND    | 4.3     | 9.9     | 14                | 59      | NT   |
| SW-4-W      | 05/18/01 | 56    | NT    | ND    | 0.68    | 0.35    | 1.4               | 4.9     | NT   |
| SW-5-N      | 05/18/01 | 74    | NT    | 12    | 2.2     | 4.4     | 1.7               | 9.8     | NT   |
| SP-1        | 05/31/01 | 100   | 11    | ND    | 0.033   | 0.45    | 0.67              | 2.6     | 6.9  |
| SP-2        | 05/31/01 | 41    | 25    | ND    | 0.029   | 0.21    | 0.25              | 1.5     | 7.8  |
| SP-3        | 05/31/01 | 120   | 13    | ND    | 0,044   | 0,41    | 0.94              | 5.4     | 6.3  |
| SP-4        | 05/31/01 | 46    | 7.2   | ND    | 0.029   | 0.18    | 0.3               | 1.3     | 5    |
| SP-5        | 05/31/01 | 35    | 9.2   | ND    | 0.071   | 0.23    | 0.32              | 1.3     | 12   |
| SP-6        | 05/31/01 | 15    | 8.8   | ND    | 0.12    | 0.1     | 0.35              | 1.2     | 6    |
| PB-1        | 05/31/01 | 2.7   | NT    | 0.061 | ND      | 0.021   | 0.008             | 0.009   | NT   |
| PB-2        | 05/31/01 | ND    | NT    | 0.11  | ND      | ND      | ND                | ND      | NT   |

60088881111

TABLE 2
Remediation Soil Samples
High Street Station

| Sample<br>ID | Date     | ТРН-д | TPH-d | MtBE | benzene | toluene | ethyl-<br>benzene | xylenes | lead |
|--------------|----------|-------|-------|------|---------|---------|-------------------|---------|------|
| SW-1         | 05/31/01 | 74    | NT    | ND   | 0.65    | 0.43    | 1.2               | 3       | NT   |
| SW-2         | 05/31/01 | 13    | NT ·  | 0.5  | 0.032   | 0.19    | 0.081             | 0.11    | NT   |
| SW-3         | 05/31/01 | 320   | NT    | ND   | 0.55    | 9.2     | 7.3               | 39      | NT   |
| SW-4         | 05/31/01 | 48    | NT    | 1.5  | 0.54    | 0.22    | 1.7               | 6.5     | NT   |
| SP 1-4       | 06/11/01 | 63    | 280   | ND   | 0.033   | 0.42    | 0.091             | 0.47    | 7.5  |
| SP 5-8       | 06/11/01 | 2.3   | 10    | ND   | ND      | 0.008   | 0.01              | 0.035   | ND   |
| SP 9-12      | 06/11/01 | 40    | 53    | 0.47 | 0.047   | 0.22    | 0.48              | 2.2     | 3.2  |
| PB-21        | 06/11/01 | ND    | NT    | 0.83 | ND      | ND      | ND                | ND      | NT   |
| PB-22        | 06/11/01 | ND    | NT    | ND   | ND      | ND      | ND                | ND      | NT   |
| SW-20        | 06/11/01 | 190   | NT    | ND   | 0.59    | ND      | 4.8               | 4.7     | NT   |
| SW-22        | 06/11/01 | 4     | NT    | 1.1  | ND      | 0.044   | 0.013             | 0.13    | NT   |
| PB-1         | 07/19/01 | ND    | NT    | 3.1  | ND      | ND      | ND                | ND      | NT   |
| PB-2         | 07/19/01 | ND    | NT    | 1.6  | 0.14    | ND      | 0.011             | 0.02    | NT   |
| SW-1         | 07/19/01 | 360   | NT    | ND   | 0.66    | 1,6     | 4.5               | 26      | NT   |
| SP 1-4       | 07/19/01 | 52    | NT    | ND   | 0.18    | 0.38    | 0.54              | 2.9     | 8.8  |
| SP 5-8       | 07/19/01 | 130   | NT    | ND   | 0.42    | 1.1     | 1.2               | 6.3     | 7.8  |
| SP 9-12      | 07/19/01 | 42    | NT    | ND   | 0.073   | 0.3     | 0.34              | 2       | 1.3  |
| PB-1         | 08/10/01 | ND    | ND    | 2.1  | ND      | ND      | ND                | ND      | ND   |
| SP 1-4       | 08/10/01 | 49    | 32    | ND   | ND      | 0.21    | 0.17              | 1.2     | ND   |
| SP 5-8       | 08/10/01 | 67    | 80    | ND   | ND      | 0.2     | 0.12              | 1       | 5.1  |
| SP 9-12      | 08/10/01 | 110   | 92    | ND   | 0.13    | 1.9     | 1.2               | 8.9     | 4.7  |
| SP 1-4       | 08/28/01 | 100   | 170   | 0.2  | 0.18    | 0.85    | 0.64              | 5       | 18   |
| PB-1         | 08/28/01 | ND    | ND    | 4.8  | ND      | ND      | ND                | ND      | NT   |
| SW-1         | 08/28/01 | 3100  | 410   | ND   | 30      | 27      | 55                | 250     | NT   |
| SW-H         | 09/04/01 | 170   | NT    | ND   | ND      | 0.48    | 0.36              | 0.38    | NT   |
| SW-P         | 09/04/01 | 2.1   | NT    | ND   | 0.045   | 0.005   | ND                | 0.005   | NT   |
| PB-M         | 09/04/01 | ND    | NT    | 1.4  | ND      | ND      | ND                | ND      | NT   |
| SP 1-4       | 09/04/01 | 86    | NT    | 7.8  | 4.5     | 0.14    | 0.45              | 1.5     | 11   |
| SP 5-8       | 09/04/01 | 240   | NT    | ND   | 0.37    | 0.74    | 4.7               | 15      | 11   |
| PB-12'       | 09/13/01 | 1.4   | NT    | 6.1  | 0.006   | 0.012   | ND                | 0.024   | 6.2  |
| SW-Penn      | 09/13/01 | 230   | NT    | <.30 | 0.1     | 0.055   | 0,38              | 0.75    | 7.7  |
| SP 1-4       | 09/13/01 | 290   | 80    | <1.0 | 0.39    | 1,9     | 2.2               | 12      | 5.7  |
| SP 5-8       | 09/13/01 | 130   | 39    | 0.63 | 0.72    | 0.76    | 1.3               | 5.5     | 8.4  |

Page 2 of 3


TABLE 2

### **Remediation Soil Samples**

**High Street Station** 

|            |          | TPHC | 784D | MTBE | B     |       |      |       |     |
|------------|----------|------|------|------|-------|-------|------|-------|-----|
| PB 11 1/2' | 09/18/01 | ND   | NT   | 9    | ND    | 0.006 | ND   | 0.015 | 11  |
| SW 1-7'    | 09/18/01 | 2200 | NT   | <2.0 | 13    | 120   | 44   | 260   | 15  |
| SW 2-6'    | 09/18/01 | 730  | NT   | <10  | 6.4   | 13    | 12   | 66    | 12  |
| SW 3-8'    | 09/18/01 | 90   | NT   | <.20 | 0.12  | ND    | 0.29 | 0.64  | 7.2 |
| SP 1-4     | 09/18/01 | 100  | 36   | <1.0 | 1.7   | 4.3   | 2    | 11    | 9.5 |
| 9-24-1     | 09/24/01 | 35   | NT   | ND   | 0.009 | 0.04  | ND   | 0.013 | NT  |
| 9-24-2     | 09/24/01 | 2000 | NT   | ND   | 10    | 14    | 35   | 210   | NT  |
| 9-24-3     | 09/24/01 | 2100 | NT   | ND   | 12    | 14    | 33   | 180   | NT  |
| SP 1-4     | 09/27/01 | 110  | 49   | 0.33 | 0.2   | 0.78  | 1.3  | 6.6   | 8.2 |
| SP 5-8     | 09/27/01 | 78   | 63   | 0.44 | 0.28  | 0.84  | 1.4  | 6.7   | 9.4 |


# APPENDIX F Preferential Pathway Survey



# APPENDIX G Sensitive Receptor Survey

# Appendix F Well Construction Details Sensitive Receptor Survey Oakland, California

| Well ID        | Site Address     | Date<br>Installed | Casing<br>Diameter<br>(inches) | Total<br>Depth<br>(fbg) | Screened<br>Interval<br>(fbg) | Water-Bearing<br>Unit         | Comments        |
|----------------|------------------|-------------------|--------------------------------|-------------------------|-------------------------------|-------------------------------|-----------------|
| Dr. Montgomery | 2627 Minna St.   | unknown           | 8<br>6                         | 211                     | 115-155<br>178-211            | Clay and Gravel               | domestic well   |
| MW-1           | 3315 High Street | 7/29/86           | unknown                        | 35                      | unknown                       | Clayey Gravel,<br>Clayey Sand | monitoring well |
| MW-2           | 3315 High Street | 7/30/86           | unknown                        | 30                      | unknown                       | Clayey Gravel                 | monitoring well |
| MW-3           | 3315 High Street | 7/30/86           | unknown                        | 30                      | unknown                       | Clayey Gravel<br>Silty Clay   | monitoring well |



Cook Environmental Services, Inc. 271 Las Juntas Way Walnut Creek, CA 94597

(925) 937-1759 work (925) 937-6869 cell cookenvironmental@att.net

### **Sensitive Receptor Map**

Express Gas & Mart 2951 High Street Oakland, California



| Project #: 1004 | Figure: |  |
|-----------------|---------|--|
| Date: 6/6/06    | 1       |  |
| Scale: as shown | 1 1     |  |

Job #1752. Dr. Montgomery, 2627 Minna Stres

#### LOG OF WELL.

| Top soil   | feet   |
|--|--------|
| TATTOM GTSA & SLSAGT                                       | 17     |
| red cray & ardaet  | 11     |
| Rock herd 20 " 52  | n .    |
| Yellow clay, broken rock 52 " 66                           | 17     |
| Red clay, broken rock 66 " 78                              | 11 A a |
| nard Yellow sand   | 11 4   |
| mara sand, making a little water 80 m of                   | и ј    |
| 1011UW 00 DICOWN 01877 *********************************** | π,     |
| Hard rock104 " 112   | 4 113  |
| Tellow Gray With broken rock                               | 11     |
| 19110W Clay With gravel 192 # 7/0                          | Ħ      |
| Yellow clay with broken rock 140. " 211                    | Ħ      |

155 ft. 8" No. 14 R. H. Collar Casing with starter 14' and 1/2" x 4" Shoe, 40 ft. perforations.
66 feet of 6" No. 16 R. H. Collar Casing in sections, 33' perforated and one 6" No. 10 Reband.

Well Tests () G.P.M.

Water tests } | gr. per U. S. Gal. Ohlorine Salts.

PERMIT # 86210 NOV

+10/40 fuglested &


25/3W FK1-3



#### KAPREALIAN ENGINEERING, INC.

Consulting Engineers
535 Main Street
Martinez, Ca. 94553
(415) 372-5444

OAKLAND



MW (MONITORING WELL)

. DRILLER! EXPLORATION DRICLING SERVICES SAN VOVE

|   |                  | ,                   | INVI | /,            |                                      | ć                         | 51-177                  | A           |
|---|------------------|---------------------|------|---------------|--------------------------------------|---------------------------|-------------------------|-------------|
| A P6210   | )                |                     | AD.  | <u> </u>      | 7                                    | /3 W                      |                         |             |
| DRILLRIG Hollow Stem  | SURFAC           | E ELEVATION         |      | . gab 140<br> | <del></del>                          | ED BY                     |                         |             |
| DEPTH TO GROUNDWATER As noted   | BORING           | DIAMETER            | 811  | <del> 1</del> | 1 - "                                | DRILLE                    |                         | 86          |
| DESCRIPTION AND CLASSIFIC   | ATION            |                     |      | DEPTH         | SAMPLER<br>UNCONFINED<br>COMPRESSIVE | SF)                       | DRY<br>DENSITY<br>(PGF) | CRATIC      |
| DESCRIPTION AND REMARKS   | COLO             | R CONSIST           | SOIL | (FEET)        | SANCO                                | STRENGT<br>(KSF)<br>WATER |                         | PENE        |
| ASPHALT, BASE ROCK AND FILL   |                  |                     |      |               |                                      |                           |                         |             |
| SILTY CLAY with rock fragments; dry   | tan              | stiff               | Cr   |               | :                                    |                           |                         |             |
| Cobbles; damp   |                  |                     |      | 5 -           |                                      |                           |                         |             |
| Grading to clayey gravel; damp  | tan<br>to<br>bro |                     | CL   |               | (                                    | 5.0 =                     | <u>Z</u>                |             |
| GRAVELLY CLAY, with some fine sand; damp to moist No product odor           |                  | stiff<br>ght<br>own | CI   | +             |                                      |                           |                         |             |
| Increasing clay at 17 feet, moist; no product odor                          |                  |                     |      | -15           |                                      |                           |                         |             |
|   | 1                | E                   | (PLO | RATOR         | Y BOF                                | RING                      | _QG                     | Jv          |
| HAZARDOUS MATERIALS MITIGATION PROFESSIONALS, INC.                          |                  |                     |      | L OIL         |                                      |                           |                         |             |
| 1450 Koll Circle, Suite 114, San Jose, CA 9511<br>Telephone: (408) 286-7868 | 2                | ジジ/も<br>PROJECT N   |      | STREE         |                                      |                           | IING                    | <del></del> |
| · · · • · · · · · • • · · · • • · · · ·                                     | r                | H182-21             |      | 8/8           |                                      |                           | io. MW-1                | -           |

#86210

25/3W4K1

| DESCRIPTION AND CLASSIFICATION  DESCRIPTION AND REMARKS  COLOR CONSIST. SOLL TYPE CHEEN BY SEED TO THE DRINKED TO THE DRINKED CLASSIFICATION  DESCRIPTION AND REMARKS  COLOR CONSIST. SOLL TYPE CHEEN BY SEED TO THE DRINKED CLASSIFICATION  DESCRIPTION AND REMARKS  COLOR CONSIST. SOLL TYPE CHEEN BY SEED TO THE DRINKED CLASSIFICATION  DESCRIPTION AND REMARKS  COLOR CONSIST. SOLL TYPE CHEEN BY SEED TO THE DRINKED CAN BE SEED TO  | ILL RIG Hollow Stem SURFACE ELEVATION LOGGED BY YOM |                |                           |              |               |       |                         |             |              |         |  |
|--|---|----------------|---------------------------|--------------|---------------|-------|-------------------------|-------------|--------------|---------|--|
| DESCRIPTION AND CLASSIFICATION  DESCRIPTION AND REMARKS  COLOR CONSIST. SOLL FREET OF STATE O | 11011.0H OCCIN                                      |                | <del></del>               |              | LOGGED BY JCW |       |                         |             |              |         |  |
| CLAYEY GRAVEL; wet, no  CLAYEY SAND; grading to sandy clay  CLAYEY |   |                |                           |              |               |       |                         | <del></del> |              |         |  |
| CLAYEY GRAVEL; wet, no  CLAYEY SAND; grading to sandy clay  CLAYEY | DESCRIPTION AND CLASSIFI                            | CATION         |                           |              | DEPTH         | EB EB | SSIVE                   | 7 (%)       | <u>, ¥</u> _ | NOE NO  |  |
| CLAYEY GRAVEL; wet, no  CLAYEY SAND; grading to sandy clay  CLAYEY | DESCRIPTION AND REMARKS                             | COLOR          | CONSIST.                  | SOIL<br>TYPE |               | SAMP  | COMPRE<br>STREN<br>(KSI | WATE        | DENS:        | PENETRA |  |
| CLAYEY SAND; grading to sandy clay  CLAYEY SAND; grading to brown  CLAYEY SAND; grading to brown  CLAYEY SAND; grading to sandy clay  CLAYEY SAND; grading to brown  EXPLORATORY BORING LOG  MITIGATION PROFESSIONALS, INC.  1450 KOIl Circle, Suite 114, San Jose, CA 95112 Telephone: (408) 286-7868  EXPLORATORY BORING LOG  MOBIL OIL CORPORATION  2315- HIGH STREET, OAKLAND  PROJECT NO.  DATE BORING  | GRAVELLY CLAY (CONTD)                               |                | to<br>very                | CL           |               |       |                         |             |              |         |  |
| TOTAL DEPTH = 35.0 feet  HAZARDOUS MATERIALS MITIGATION PROFESSIONALS, INC.  1450 Koli Circle, Suite 114, San Jose, CA 95112 Telephone: (408) 286-7868  Brown dense  EXPLORATORY BORING LOG  MOBIL OIL CORPORATION 33/5 HIGH STREET, OAKLAND PROJECT NO. DATE BORING   | CLAYEY GRAVEL; wet, no product odor                 | light<br>brown | dense                     | GC           |               |       |                         | ·           |              |         |  |
| FOTAL DEPTH = 35.0 feet  HAZARDOUS MATERIALS MITIGATION PROFESSIONALS, INC.  1450 Koll Circle, Suite 114, San Jose, CA 95112 Telephone: (408) 286-7868  EXPLORATORY BORING LOG  MOBIL OIL CORPORATION  33/5 HIGH STREET, OAKLAND  PROJECT NO. DATE BORING  | CLAYEY SAND; grading to sandy clay                  | light<br>brown |                           | sc           |               |       |                         |             |              |         |  |
| MITIGATION PROFESSIONALS, INC.  1450 Koll Circle, Suite 114, San Jose, CA 95112 Telephone: (408) 286-7868  MOBIL OIL CORPORATION  33/5 HIGH STREET, OAKLAND  PROJECT NO. DATE BORING   | TOTAL DEPTH = 35.0 feet                             |                |                           |              | -             |       |                         |             |              |         |  |
| MITIGATION PROFESSIONALS, INC.  1450 Koll Circle, Suite 114, San Jose, CA 95112 Telephone: (408) 286-7868  MOBIL OIL CORPORATION  33/5 HIGH STREET, OAKLAND  PROJECT NO. DATE BORING   |   |                |                           |              |               |       |                         |             |              |         |  |
| 1450 Koll Circle, Suite 114, San Jose, CA 95112 Telephone: (408) 286-7868 PROJECT NO. DATE BORING  | HAZARDOUS MATERIALS MITIGATION PROFESSIONALS INC.   |                |                           |              |               |       |                         |             |              |         |  |
| PROJECT NO. DATE BORING  | 1450 Koll Circle, Suite 114, San Jose, CA 95112     |                | 33/5 HIGH STREET, OAKLAND |              |               |       |                         |             |              |         |  |
| H182-21 8/86 NO. MW-1  | истерноле: (408) 286-786 <u>8</u>                   |                |                           | -            | DATE<br>/86   |       |                         |             | MW-1         |         |  |

A86210

AD.

01-177 B 25/3W4K2

|  |   | ······                |              |                    | _        | 20/  | SW?              | <u> </u>      |   |  |
|--|---|-----------------------|--------------|--------------------|----------|--|------------------|---------------|---|--|
| DRILL RIG HOLLOW Stem                              | SURFACE                                   | ELEVATION             |              |                    | L        | OGGED  | JCW              |               |   |  |
| DEPTH TO GROUNDWATER As Noted                      | BORING DI                                 | BORING DIAMETER 811   |              |                    |          | ATE DR   | 7/30/86          |               |   |  |
| DESCRIPTION AND CLASSIFIC                          | CATION                                    | _                     |              | DEPTH              | 띮        | SSIVE  | 8                | <u></u>       | £ 20 € 20 € 20 € 20 € 20 € 20 € 20 € 20 |  |
| DESCRIPTION AND REMARKS                            | COLOR                                     | CONSIST.              | SOIL<br>TYPE | (FEET)             | SAMPLER  | UNCONFINED<br>COMPRESSIVE<br>STRENGTH<br>(KSF) | WATER<br>CONTENT | DRY<br>DENSIT | PENETRA                                 |  |
| ASPHALT AND BASE ROCK                              |   |                       |              |                    | $\top$   |  |                  |               |   |  |
| SILTY CLAY with rock fragments; dry                | tan                                       | stiff                 | CL.          |                    |          |  |                  |               |   |  |
| Large rock fragments                               |   |                       |              | 5 —                |          |  |                  |               |   |  |
| Damp; no product odor                              | motld<br>tan<br>to<br>gray<br>to<br>brown |                       |              | <br>   <br>   <br> |          |  |                  |               |   |  |
| Decreasing rock fragments                          |   |                       |              | -10-               |          |  |                  |               |   |  |
| Slightly sandy<br>No product odor                  |   |                       | CL-          | -15                |          |  |                  |               |   |  |
| CLAYEY GRAVBL                                      | light<br>brown                            | dense                 | GC           | -20                |          | 160  |                  |               |   |  |
|  | EXPLORATORY BORING LOG                    |                       |              |                    |          |  |                  |               |   |  |
| HAZARDOUS MATERIALS MITIGATION PROFESSIONALS, INC. | -   | MOBIL OIL CORPORATION |              |                    |          |  |                  |               |   |  |
| 1450 Koll Circle, Suite 114, San Jose, CA 95112    | HIGH STREET, OAKLAND                      |                       |              |                    |          |  |                  |               |   |  |
| Telephone: (408) 286-7868                          |   | DJECT NO.             | <u> </u>     | DATE               |          | BOI  | N 48 -           |               |   |  |
| RICLER! EXPLORATION DRICL                          | 11170                                     | 1-4J.                 |              | 8/86               | ******** |  | VO.              | MW-2          |   |  |

#86210

25/3W4K2

|   | BORING DI                   | LEVATION<br>AMETER                              | 8"           | -            | -       | LOGGED   | вү Ј(                | 7/30/            |                              |
|---|-----------------------------|---|--------------|--------------|---------|--|----------------------|------------------|------------------------------|
| DESCRIPTION AND CLASSIFICA DESCRIPTION AND REMARKS    | ATION                       | AMETER  | 8"           | <del>,</del> |         | DATE DR  | ILLED                | 7/30             | 196                          |
| DESCRIPTION AND REMARKS                               | <del></del>                 |   |              |              |         |  | TE DRILLED           |                  | <u>vv</u>                    |
|   | COLOR                       |   |              | DÉPTH        | LER     | FINED<br>SSIVE<br>GTH                          | ∓<br>7<br>(%)        | È                | TION<br>NOCE<br>/FT.         |
| CLAYEY GRAVEL (CONTD)                                 |                             | CONSIST.  | SOIL<br>TYPE |              | SAMPLER | UNCONFINED<br>COMPRESSIVE<br>STRENGTH<br>(KSF) | WATER<br>CONTENT (%) | DENSITY<br>(PCF) | PENETRA<br>RESISTA<br>(BLOWS |
|   | light<br>brown<br>to<br>tan | dense   | GC           |              |         |  |                      |                  |                              |
| Large gravel  |                             | dense<br>to<br>very<br>dense                    |              | - 30         |         |  |                      |                  | 21                           |
| TOTAL DEPTH = 30.0 feet                               |                             |   |              |              |         |  |                      |                  |                              |
| HAZARDOUS MATERIALS<br>MITIGATION PROFESSIONALS, INC. |                             |   | -            | TORY         |         |  |                      |                  |                              |
| 1450 Koll Circle, Suite 114, San Jose, CA 95112       | -  .                        | MOBIL OIL CORPORATION 33/6-HIGH STREET, OAKLAND |              |              |         |  |                      |                  |                              |
| Telephone: (408) 286-7868                             | PRO                         | DJECT NO.                                       | T            | DATE<br>8/86 |         | ВО   | RING<br>NO. MY       | I-2              |                              |

01-177 C

\$ 56210

AD.

LOGGED BY JCW SURFACE ELEVATION DRILL RIG Hollow Stem DATE DRILLED DEPTH TO GROUNDWATER **BORING DIAMETER** As Noted 811 7/30/86 **DESCRIPTION AND CLASSIFICATION** WATER CONTENT ( DEPTH (FEET) SOIL TYPE **DESCRIPTION AND REMARKS** COLOR CONSIST. ASPHALT AND BASE ROCK stiff SILTY CLAY with rock fragtan CLments; dry to brown Large rock fragments GC Decreasing rock fragments SILTY CLAY, damp No product odor stiff CLtan to gray very stiff  $\nabla$ Wet; no product odor EXPLORATORY BORING LOG HAZARDOUS MATERIALS MOBIL OIL CORPORATION MITIGATION PROFESSIONALS, INC. HIGH STREET, OAKLAND 1450 Koll Circle, Suite 114, San Jose, CA 95112 Telephone: (408) 286-7868 PROJECT NO. DATE BORING H182-21 8/86 NO. MW-3

| DRILL RIG Hollow Stem  | T                 | FACE ELEVATION                                  |          |                 |   | LOGGED BY JCW                                  |                      |                  |  |  |  |
|--|-------------------|---|----------|-----------------|---|--|----------------------|------------------|--|--|--|
| DEPTH TO GROUNDWATER As Noted  | <del> </del>      | RING DIAMETER 8"                                |          |                 |   | DATE DRILLED 7/30/86                           |                      |                  |  |  |  |
| DESCRIPTION AND CLASSIFICATION   |                   |   |          |                 | <del>-1-</del>                                | SSIVE  | £ 5                  |                  |  |  |  |
| DESCRIPTION AND REMARKS  | COLOR             | CONSIST,  | SOIL     | DEPTH<br>(FEET) | SAMPLER                                       | UNCONFINED<br>COMPRESSIVE<br>STRENGTH<br>(KSF) | WATER<br>CONTENT (%) | DENSITY<br>(POF) | PENETRATION<br>RESISTANCE<br>(BLOWS/FT.)       |  |  |
| SILTY CLAY (CONTD)   | tan<br>to<br>gray | very<br>stiff -                                 | CL<br>GC |                 |   |  | 0                    |                  |  |  |  |
| CLAYEY GRAVEL; wet   | light<br>brown    |   |          |                 |   |  |                      |                  |  |  |  |
| SILTY CLAY   | light<br>brown    | very<br>stiff<br>to<br>hard                     | CL       | 25 -            |   |  |                      |                  |  |  |  |
| CLAYEY GRAVEL  | light<br>brown    | dense<br>to ver                                 | GC       |                 |   |  |                      |                  | j.:  |  |  |
| TOTAL DEPTH = 30.0 feet  |                   |   |          |                 |   |  |                      |                  | وروستان در |  |  |
|  |                   |   |          |                 |   |  |                      |                  |  |  |  |
|  |                   |   |          |                 |   |  |                      |                  |  |  |  |
| ,  |                   |   |          |                 |   |  |                      |                  | :  |  |  |
| HAZARDOUS MATERIALS<br>MITIGATION PROFESSIONALS, INC.                        |                   | EXPLORATORY BORING LOG  MOBIL OIL CORPORATION . |          |                 |   |  |                      |                  |  |  |  |
| 1450 Koll Circle, Suite 114, San Jose, CA 9511.<br>Telephone: (408) 286-7868 | <u> </u>          |   |          | STREET          | <u>,                                     </u> | OAKLA  | ND                   | -                | · · ·  |  |  |
|  |                   | 182-21  |          | 8/86            |   | B  | ORING<br>NO.         | MW-3             |  |  |  |

## **APPENDIX H**

MtBE Plume Velocity Calculations

```
CALCULATE MEBE plume velocity
  Given Gravelly clay agu Hez
   Hydractic gradien = dh/d1
    historic hydradic gradients
     0.032 7/8/04
     0.024 10/1/04
     0,038
                 1/3/05
     0.035
     0.040
                1/6/05
     0.007
     0.029 Avg value
 Hydraulic Conductivity
Assume No adsorption of MEBE TO Clay
  V = K \frac{dh}{dl}

upper range = (1 \times 10^{5})(.029) = 2.9 \times 10^{-7}

lower range = (1 \times 10^{-7})(.029) = 2.9 \times 10^{-7}

(0.029) = 2.9 \times 10^{-7}

(0.029) = 2.9 \times 10^{-7}

(0.029) = 2.9 \times 10^{-7}
Assume worse case. 2,9 × 10 cm/sec
        = (2.9 × 10 ch/sec) (60 sec) ( bomin) (2hos) (365dm)
       = 0.30 ft/4R
Howard, based on inspection of soil in hand sample, soil is
 portrally I mified with SISNI HONTH FRACTURE PLANES. Secondary
porosity Through franciures is believed to be primary 62
plume movement. Apply a mutaplier of ± 60X
    K = 4264 × 10-9 cm/sec
```

 $V_{E} = 6 \times 10^{4} \text{ cm/sec} \times 0.029 = 1.74 \times 10^{-5} \text{ cm/sec}$   $1.74 \times 10^{5} \text{ cm/sec} \qquad \frac{f_{T}}{30.48 \text{ cm}} \qquad \frac{31,536,000 \text{ sec}}{\text{Ye}}$ 

189/yr

Check This Against distance of MW-10 to Dispuser Pumps in front of gas started (neadest sourcever). Assuming MtBE began leaking in late 1970's when MtBE was first used widely as comme booster

Distance of MW-10 to front disposed pumps 128ft Time of peak MtBE conc in MW-10 1/13/04 Estimated to for MtBE feak 1978 Est Travel Time 26 years 128ft = 4.9 ft/yr

We estimate the plume velocity to range from 5-18 ft/4R.