
ALCO HAZMAT 94 MAR 22 PM 1: 30





ENVIRONMENTAL SERVICES AND REMEDIATION CONTRACTING



February 28, 1994

SITE CLOSURE REPORT

a t
The Oliver Rubber Company
1200 65th Street
Emeryville, California

for:

The Oliver Rubber Company 1200 65th Street Emeryville, CA 94608

submitted by:

AQUA SCIENCE ENGINEERS, INC. 2411 Old Crow Canyon Road, #4 San Ramon, CA 94583 (510) 820-9391

TABLE OF CONTENTS

Introduction	Page 1
Site Description	Page 2
Previous Work	Page 2
Investigative Methods	Page 3
Drilling and Soil Borings	Page 3
Soil Sampling Procedures	Page 3
Construction of Monitoring Wells	Page 3
Well Development	Page 4
Groundwater Sampling	Page 4
Analytical Methods	Page 4
Soil Samples	Page 4
Groundwater Samples	Page 5
Extent of Hydrocarbon Presence in Soil and Groundwater	Page 5
Soil	Page 5
Groundwater	Page 5
Hydrology	Page 6
Regional Hydrology	Page 6
Site Hydrology	Page 6
Groundwater Gradient	Page 6
Seasonal Variations of Groundwater	Page 6
Aquifer Characteristics	Page 6
Beneficial Uses of Groundwater	Page 6
Well Inventory	Page 6
Contaminant Fate Transport	Page 7
Sources of Drinking Water Determination	Page 7
Remediation Activities and Effectiveness	Page 7
Summary and Conclusions	Page 7
Recommendations	Page 7
References Cited	Page 7
Report Limitations	Page 8

TABLES

Table One - Soil Sample Analyses Results

Table Two - Groundwater Sample Analyses Results
Table Three - Summary of Groundwater Elevation Data

FIGURES

Figure 1 - Site Location Map

Figure 2 - Site Plan

Figure 3 - Groundwater Gradient Map - October 1, 1992
Figure 4 - Groundwater Gradient Map - January 18, 1993
Figure 5 - Groundwater Gradient Map - April 16, 1993
Figure 6 - Groundwater Gradient Map - July 14, 1993

APPENDICIES

APPENDIX A - Tank Removal Report - December 5, 1991

APPENDIX B - Tank Removal Report - July 16, 1992

APPENDIX C - Environmental Site Assessment - October 28, 1992

APPENDIX D - Overexcavation Report - December 22, 1992

APPENDIX E - Quarterly Monitoring Report - January 29, 1993

APPENDIX F- Quarterly Monitoring Report - May 3, 1993

APPENDIX G - Quarterly Monitoring Report - July 27, 1993

APPENDIX H - Area Well Survey

INTRODUCTION

Site Location (Site), See Figure 1, Site Location Map 1200 65th Street Emeryville, California

Property Owner
The Oliver Rubber Company
1200 65th Street
Emeryville, California
Contact: Mr. Ron Kessler
(510) 654-7711

Environmental Consulting Firm
Aqua Science Engineers, Inc.
2411 Old Crow Canyon Road, #4
San Ramon, CA 94583
Contact: Robert Kitay, Project Manager
(510) 820-9391

Agency Review
Alameda County Health Care Services Agency (ACHCSA)
80 Swan Way, Room 350
Oakland, CA 94621
Contact: Ms. Susan Hugo

RWQCB, San Francisco Bay Region 2101 Webster Street, Fourth Floor Oakland, CA 94612 Contact: Mr. Rich Hiett

Please accept the following information as a formal application for "Site Closure" at 1200 65th Street, Emeryville, California. Aqua Science Engineers, Inc. (ASE) has been contracted by the property owner, The Oliver Rubber Company, to perform the necessary tasks essential for obtaining site closure.

SITE DESCRIPTION

The site is located at the corner of 65th Street at Hollis Street within the city limits of Emeryville, California. The site is approximately 1/16 mile east of Interstate 80, and 1/2 mile north of Highway 580 (Figures 1 and 2). The site is currently used as a manufacturing plant for rubber products. The topography of the immediate area is relatively flat and located at approximately 20 feet above mean sea level. Local drainage is primarily controlled by storm drains.

PREVIOUS WORK

On November 1, 1991, ASE removed two 8,000-gallon underground, non-halogenated solvent storage tanks from the site. Total petroleum hydrocarbons as gasoline (TPH-G) and volatile organic compound (VOC) concentrations were detected in the sidewalls of both excavations. Approximately 250 cubic yards of soil were removed from the site following overexcavation activities, and a total of 3790 gallons of water were removed from the tank pits on November 5 and 14, 1991. Only 27 parts per million (ppm) TPH-G remained in the excavation sidewalls following the overexcavation. The report documenting the underground tank removals and related activities is included as Appendix A.

On July 24, 1992, ASE removed one 1,000-gallon underground bunker oil storage tank from the site and removed approximately 36 cubic yards of soil from the tank area. Up to 490 ppm total petroleum hydrocarbons as diesel (TPH-D) and 1,500 ppm oil and grease (O&G) were detected in the excavation sidewalls. The report documenting the underground tank removal and related activities is included as Appendix B.

In October 1992, three groundwater monitoring wells were installed, developed and sampled. The report documenting this investigation is included as Appendix C.

In December 1992, ASE overexcavated approximately 50 cubic yards of hydrocarbon bearing soil in the vicinity of the former bunker oil tank. Confirmation soil samples were collected at the direction of Ms. Susan Hugo of the ACHCSA. Only 48 parts per million (ppm) O&G and 30 ppm TPH-D remained. The report documenting the overexcavation is included as Appendix D.

The groundwater monitoring wells were again sampled in January, May and July of 1993. No hydrocarbons or solvents were detected during any of the groundwater sampling periods. The quarterly groundwater monitoring reports are included as Appendices E through G.

INVESTIGATIVE METHODS

All work was conducted after workplans were approved by the ACHCSA and RWQCB, and all wells were installed under permit from the Alameda County Flood Control and Water Conservation District (Zone 7).

Drilling and Soil Borings

On October 1, 1992, ASE drilled three soil borings at the site which were converted into monitoring wells MW-1, MW-2 and MW-3 as well as borings SB-1 and SB-2. The borings were drilled using a CME-75 drill rig equipped with 8-inch outside diameter (O.D.) continuous flight hollow-stem augers. All drilling equipment was steam-cleaned prior to use and between borings.

Soil Sampling Procedures

Undisturbed soil samples were collected at 5 and 10 foot depths in the boring for well MW-1 and at 5, 10 and 15 foot depths in the borings for wells MW-2 and MW-3. Samples were collected at 10 foot depth only in boring SB-1 and SB-2. The samples were collected using a 2-inch diameter split-barrel drive sampler lined with pre-cleaned brass tubes. The sampler was advanced ahead of the auger tip by successive blows from a 140 lb. hammer dropped 30-inches. The samples to be analyzed at a certified analytical laboratory were immediately trimmed, capped with double thickness aluminum foil, plastic end caps and tape, labeled, and placed in an ice chest containing ice for transport to the analytical laboratory under chain of custody. The remaining tubes were used for visual soils classification and field screening for volatile compounds using an organic vapor meter (OVM). The sampler was cleaned prior to use and between sampling intervals with a TSP solution and rinsed with tap water.

Construction of Monitoring Wells

The wells were constructed using 2-inch diameter, 0.020-inch slotted, flush All three wells were threaded, schedule 40 well screen and blank casing. screened between 5 and 25-feet below ground surface (bgs) to monitor the The casing was lowered through the first water bearing zone encountered. augers and #3 Monterey sand was placed in the annular space between the borehole and the casing from the bottom of the borehole to approximately one Two feet of bentonite pellets were foot above the top of the well screen. placed above the sand and were hydrated with tap water. The remainder of the borings were filled to near original grade with cement/bentonite grout. The wells were completed with water-tight locking wellplugs and flush The well installation report is included as mounted, traffic-rated well boxes. Appendix C.

Well Development

On October 2, 1992, each well was developed using surge block agitation and PVC bailer evacuation. Approximately 50 gallons of water were removed from each well during development. All equipment used in the well was steam-cleaned prior to use. Development purge water was contained in 55-gallon DOT 17H steel drums pending analytical results.

Groundwater Sampling

Groundwater samples were collected from the wells on October 5, 1992 and January 18, April 16 and July 14, 1993. After checking for free-floating hydrocarbons and measuring the depth to water in each well, each well was purged of a least five well casing volumes of groundwater using steam-cleaned pumps or bailers. After the appropriate amount of water was removed from each well, ASE collected groundwater samples from the wells using disposable polyethylene bailers. Water was decanted from the bailers into 40-ml volatile organic analysis (VOA) vials and 1-liter amber glass bottles. Samples were preserved with acid as necessary, labeled and stored on ice for transport to the certified analytical laboratory under chain of custody.

Analytical Methods

Soil Samples

Confirmation soil samples collected after the solvent tank removal and overexcavation activities were analyzed by Chromalab, Inc. of San Ramon, California (CDHS #E694) for TPH-G by EPA Method 5030/8015, TPH-D by EPA Method 3550/8015, and volatile organic compounds (VOCs) by EPA Method 8240.

Confirmation soil samples collected after overexcavation activities in the former bunker fuel tank area were analyzed by Priority Environmental Labs of Milpitas, California (CDHS #1708) for TPH-D by EPA Method 3550/8015, benzene, toluene, ethylbenzene and total xylenes (BTEX) by EPA Method 8020 and O&G by EPA Method 5520 D&F.

During the drilling operation, soil samples for analyses were collected in the boring for well MW-1 at 10-feet bgs, in the boring for well MW-2 at 5, 10 and 15-feet bgs, in the boring for well MW-3 at 5 and 15-feet bgs. The soil samples were submitted to and analyzed by Priority Environmental Labs of Milpitas, California. The samples from MW-1, SB-1 and SB-2 were analyzed for TPH-D by EPA Method 3350/8015, BTEX by EPA Method 8020, VOCs by EPA Method 8010 and O&G by EPA Method 5520 E&F. In addition, the sample from 15-feet bgs in MW-1 was analyzed semi-volatile organic compounds

(SVOCs) by EPA Method 8270. The soil samples from MW-2 and MW-3 were analyzed for VOCs by EPA Methods 8010, 8020 and 8240. Analytical results for soil are included in Table 1.

Groundwater Samples

All groundwater samples were submitted to and analyzed by Priority Environmental Labs of Milpitas, California.

Groundwater samples were analyzed for all or a combination of the following: total petroleum hydrocarbons as gasoline (TPH-G) by EPA Method 5030/8015, TPH-D by EPA Method 3510/8015, BTEX by EPA Method 602, O&G by EPA Method 5520D&F, VOCs by EPA Method 8240, SVOCs by EPA Method 8270, pH by EPA Method 9045 and conductivity by EPA Method 120.1. All analytical results for groundwater are tabulated in Table 2.

EXTENT OF HYDROCARBON PRESENCE IN SOIL AND GROUNDWATER

Soil

Confirmation soil samples collected after the overexcavation in the former solvent tank area indicated that up to 27 ppm TPH-G remained in excavation sidewalls following overexcavation activities.

Confirmation soil samples collected after the overexcavation in the former bunker fuel tank area indicated that 2.9 ppm TPH-D, 0.0084 ppm benzene, 0.014 ppm toluene, 0.0073 ppm ethylbenzene, 0.024 ppm total xylenes, and 48 ppm O&G were in the northern sidewall and 30 ppm TPH-D, 0.0066 ppm ethylbenzene and 0.012 ppm total xylenes were in the western sidewall. No hydrocarbons were detected in the southern sidewall.

Only 0.013 ppm trichlorofloromethane was detected in the 5-foot sample from MW-2, and 0.0029 ppm 1,1-dichloroethene and 11 ppm chloroform were detected in the 15-foot sample from MW-2. No other hydrocarbons or VOCs were detected in any analyzed soil sample collected during the drilling operation.

Groundwater

No hydrocarbons or VOCs have been detected in groundwater samples collected from any site well during the four quarters sampled.

HYDROLOGY

Regional Hydrology

The site lies in the East Bay Plain groundwater basin. The East Bay Plain groundwater basin is generally characterized by a very thick alluvial sequence. The basin extends from the base of the Berkeley Hills in the east to the San Francisco Bay in the west. Groundwater generally flows from the hills in the east toward the bay in the west.

Site Hydrology

The soils encountered as drilling progressed were logged by an ASE geologist using the Unified Soil Classification System (USCS). In general, the borings consist of low permeability clay and silty clay.

Groundwater Gradient

Groundwater has consistently flowed to the west beneath the site at a gradient of between 0.009 and 0.02 feet/foot. The wells were surveyed by ASE relative to a project datum at the time of the well installation. Survey information, depths to groundwater and groundwater elevations relative to the project datum are presented in Table 3. Groundwater elevation contour maps for each quarter are presented as Figures 3 through 6.

Seasonal Variations of Groundwater

There was approximately a 4-foot seasonal variation in groundwater elevations with groundwater being at its lowest during the October 1992 measurements and at its highest during the January 1993 measurements.

Aquifer Characteristics

The wells appear to be screened in clay and silty clay units of very low to low permeability.

BENEFICIAL USES OF GROUNDWATER

Well Inventory

ASE contacted Alameda County Public Works Agency for a listing of registered wells within one-half mile of the site (Appendix H). There are 77 registered wells within one-half mile of the site. Of these wells, 74 are listed as monitoring or test wells, one is listed as a domestic well, one is listed as an irrigation well, one is listed as a cathodic protection well and two are of

unknown uses. Both the domestic and irrigation wells are on properties that contain monitoring wells and are not likely water production wells.

Contaminant Fate Transport

Contaminant fate transport is not applicable since groundwater has not been impacted.

Sources of Drinking Water Determination

The City of Emeryville receives their water from the East Bay Municipal Utility District (EBMUD). EBMUD imports the majority of their water from the Mokelumne River system. EBMUD does not utilize groundwater for its water supply (Alameda County Flood Control and Water Conservation District, 1988).

REMEDIATION ACTIVITIES AND EFFECTIVENESS

Remediation was limited to the removal of the underground fuel storage tanks, the overexcavation and removal/disposal of over 300 cubic yards of hydrocarbon bearing soil from the site and the removal/disposal of a total of 3790 gallons of water from the tank pits.

SUMMARY AND CONCLUSIONS

After analytical results indicated that elevated hydrocarbon concentrations were present in soil samples collected beneath the former location of several fuel and solvent tanks at the time the tank removals, ASE overexcavated and disposed of over 300 cubic yards of hydrocarbon bearing soil from the site and installed three groundwater monitoring wells. The wells were sampled on a quarterly basis for four consecutive quarters. No hydrocarbons or VOCs were detected in any groundwater sample.

RECOMMENDATIONS

Since no hydrocarbons have been detected in any site well for four consecutive quarters, Aqua Science Engineers recommends that site closure be granted, and that the three monitoring wells be properly destroyed.

REFERENCES CITED

Alameda County Flood Control and Water Conservation District, Geohydrology and Groundwater - Quality Overview, East Bay Plain Area, Alameda County, California, 205(J) Report, June 1988.

REPORT LIMITATIONS

The results of this investigation represent conditions at the time of the groundwater monitoring well installation, sampling and for the specific locations at which the samples were collected, and for the specific parameters analyzed for by the laboratory.

It does not fully characterize the site for contamination resulting from unknown sources or for parameters not analyzed for by the laboratory. All of the laboratory work cited in this report was prepared under the direction of independent CSDHS certified laboratory. The independent laboratory is solely responsible for the contents and conclusions of the chemical analysis data.


Should you have any questions or comments regarding this report, please feel free to call us at (510) 820-9391.


Respectfully submitted,


AQUA SCIENCE ENGINEERS, INC.


Robert E. Kitay, R.E.A. Project Geologist



















TABLE ONE Soil Sample Analyses Results Hydrocarbons and VOCs (parts per million)

Well#/ Sample Depth	TPH-D	Benzene	Toluene	Ethyl Benzene	Total Xylenes	Oil and Grease	Other VOCs
MW-1- 10' MW-1- 15'	<1.0	<0.0050	<0.0050	<0.0050	<0.0050	<10	N.D.a
MW-2- 5'				 <0.0050	<0.0050		ь
MW-2- 10' MW-2- 15'		<0.0050 <0.0050	<0.0050 <0.0050	<0.0050	<0.0050		c
MW-3- 5' MW-3- 10' MW-3- 15'		<0.0050 <0.0050	<0.0050 <0.0050	<0.0050 <0.0050	<0.0050 <0.0050		N.D. N.D.
SB-1-10'	<1.0	<0.0050	<0.0050	<0.0050	<0.0050	<10	
SB-2-10'	<1.0	<0.0050	<0.0050	<0.0050	< 0.0050	<10	

^{--- =} Not analyzed

N.D. = Not detected at detection limits

a = No semi-volatile organic compounds (SVOCs) detected at detection limits

b = 0.013 ppm trichlorofloromethane detected by EPA Method 8240; no other compounds detected

c = 0.0029 ppm 1,1-dichloroethene and 0.011 ppm chloroform detected by EPA Method 8010; no other compounds detected

TABLE TWO Groundwater Sample Analyses Results (parts per billion)

Well #	TPH-G_	TPH-D	Benzene	Toluene	Ethyl Benzene	Total Xylenes	Oil & Grease	VOCs
VIOIL II	*****		<u> Donnono</u>					
MW-1								
10-05-92		<50	<0.5	<0.5	<0.5	< 0.5	<500	
01-18-93		< 5 0	<0.5	<0.5	<0.5	<0.5	<500	
04-16-93		<50	<0.5	<0.5	<0.5	<0.5	<500	
07-14-93		<50	<0.5	<0.5	<0.5	<0.5	<500	
07-14-25		~0	-0.5	.0.5				
MW-2								
10-05-92				~ ~ ~				N.D.
01-18-93	<50		<0.5	<0.5	<0.5	<0.5		N.D.
04-16-93	<50							N.D.
07-14-93	<50							N.D.
Q1-14-75	~0							
MW-3								
10-05-92						~~~		N.D.
01-18-93	<50		<0.5	<0.5	<0.5	<0.5		N.D.
04-16-93	<50							N.D.
07-14-93	<50							N.D.
07-14-35	~ 00	_						- ,
Analytical Method	5030/ 8015	3510/ 8015	602	602	602	602	5520 B&F	624


--- = Not analyzed N.D. = Not detected at analytical detection limit

TABLE THREE
Summary of Groundwater Elevation Data

Well I.D.	Date of Measurement	Top of Casing Elevation (relative to project datum)	Depth to Water (feet)	Groundwater Elevation (project data)
MW-1	10-01-92	20.00	8.08	11.92
	01-18-93		4.00	16.00
	04-16-93		5.10	14.90
	07-14-93		6.82	13.18
MW-2	10-01-92	19.21	7.45	11.76
	01-18-93		3.80	15.41
	04-16-93		4.62	14.59
	07-14-93		6.20	13.01
MW-3	10-01-92	19.80	7.44	12.36
	01-18-93		3.46	16.34
	04-16-93		4.60	15.20
	07-14-93		6.11	13.69

APPENDIX A

Tank Removal Report December 5, 1991



December 5, 1991

PROJECT REPORT
UNDERGROUND STORAGE TANK CLOSURE
at
Oliver Rubber Company
1200 65th Street, Emeryville, CA.

Prepared for:

The Oliver Rubber Co. 1200 65th Street, Oakland, CA.

Submitted by:

AQUA SCIENCE ENGINEERS, INC. 1041 Shary Circle CONCORD, CA

TABLE OF CONTENTS

1.0	INTRODUCTION
2.0	PERMITS
3.0	MOBILIZATION, EXCAVATION AND REMOVAL
4.0	SAMPLING AND ANALYSIS
5.0	DISPOSAL OF CONTAMINATED SOIL
6.0	BACKFILLING AND RESURFACING
7.0	DISCUSSION AND CONCLUSIONS
FIGUR	E 1 - SITE MAP
FIGUR	E 2 - PARTIAL SITE PLAN
APPEN	IDIX A - PERMITS
APPEN	IDIX B - HAZARDOUS WASTE MANIFEST and CERTIFICATE OF DISPOSAL

APPENDIX C - LABORATORY ANALYSIS and

CHAIN OF CUSTODY

1.0 INTRODUCTION

This report documents the removal and related activities of the underground storage tank closure performed for the Oliver Rubber Company located at 1200 65th Street in Emeryville, Calif. (FIGURE 1). The following tanks were removed from the site; two (2) 8,000 gallon tanks. The tanks previously contained non-halogenated organic solvents. The scope of services provided by Aqua Science Engineers, Inc. (ASE) is in accordance with ASE proposal No. 91-179 and includes the following tasks:

- o Obtain permits from the Alameda County Health Care Services Agency, City of Emeryville Fire Department and City of Emeryville Building Department.
- o Notify Cal-OSHA and the Bay Area Air Quality Management District.
- o Remove and dispose of residual liquids from the tanks.
- o Remove and dispose of the underground storage tanks.
- o Sample native soil and groundwater adjacent the tanks.
- o Prepare a report of methods and findings.

2.0 PERMITS

The application for permits to remove the underground storage tank were obtained from the Alameda County Health Care Services Agency, Emeryville Fire Department and Emeryville Building Department. Notice of construction was given to the Bay Area Air Quality Management District and CAL-OSHA. Copies of the permits and notification documents are contained in Appendix A.

3.0 MOBILIZATION

ASE mobilized for on-site work on October 24, 1991, commencing with removal of concrete surface materials and installation of soil shoring in the form of soldier piles. Project personnel included: David Prull-Project Engineer, Steve DeHope- Construction Manager, Tom McMullen-Driller and Craig Barr-Technical Labor.

Soil borings conducted in preparation for soldier piles revealed the soil cross-section in the area of the tanks to be of clayey silts with some fine sand and an increased content of fine sand to the depth of groundwater, approximately 9.5 feet below grade.

3.1 EXCAVATION

The services of the Underground Service Alert network were utilized to identify primary utilities in the work area. Representatives of Pacific Gas and Electric were contacted regarding procedures used to negotiate a 1" natural gas line in the work area.

Excavation of the storage tanks was initiated on October 30, 1991. A concrete vault surrounding the tanks on all sides and bottom was exposed in the process of excavation (Figure 2: Partial Site Plan). Soil was removed along the outside perimeter of the vault to a depth of approximately 10 feet below grade. Maximum depth of excavation was 11.0 feet below grade.

Cleaning of the tanks and removal of residual liquid waste from the tanks was commenced on October 31. Approximately 260 gallons of residual liquid and tank rinsate was removed by Waste Oil Recovery Systems and disposed of at the Demenno Kerdoon facility in Compton, CA. A copy of the Hazardous Waste Manifest is appended to this report.

Fill piping consisting of 4" Dia. galvanized steel was removed from locations above the tanks. Product supply piping consisted of 1.5" Dia. galvanized steel pipe contained in 4" clay tile pipe casing. Vent lines consisted of 1.5" Dia. galvanized steel pipe contained in 4" clay tile pipe casing. The location of product ping is shown on the partial site plan, (Figure 2: Partial Site Plan). All piping appeared in good condition with no hole or defects noted. No overspill protection devices were in place at the fill locations.

Native material outside the perimeter of the UGST containment vaults consisted of a light brown clayey silt with some medium/fine sand and little medium/fine gravel to a depth of approximately 4 feet below grade. Light grey clayey silts with increasing content of fine sand was encountered in the elevations between 4 feet and 11 feet below grade. Groundwater was encountered during the excavation at a depth of approximately 9.5 feet below grade. Tank backfill material inside the concrete vaults was classified as an imported 3/8" crushed gravel with fines.

Air quality sampling was conducted at the edge of the excavation using an organic vapor analyzer model 580A by TEI. Volatile organic vapors were not detected in the air near the edge of the excavation. Mild petroleum odors were noted periodically during soil removal operations.

All tank piping was observed intact with no obvious holes or weakness. No overspill protection devices where in place. All excavated materials were placed on 10 ml. plastic sheeting and covered.

3.2 REMOVAL

Prior to tank removal on the morning of November 1, 1991, ASE inerted the tanks by adding dry ice at the rate of at least 1.5 pounds per 100 gallons of tank volume. After verifying a safe LEL of the tank atmosphere, the tanks were removed from the excavation. The tank removal operations were witnessed by the City of Emeryville Fire Department, Alameda Health Care Services Agency Inspector-Susan Hugo, David Prull of ASE, and Robert Flynn of Oliver Rubber. The tanks were transported by Erickson Trucking Inc. and Trident Truck Lines to the Erickson Tank Disposal Facility in Richmond, CA, on the date of removal. Copies of the Hazardous Waste Manifests and Tank Disposal Certificates are contained in Appendix B.

The tanks were constructed of a single ply 1/4" plate steel. No protective coatings were evident on the tank exterior. No holes, cracks or defects in the exterior of either tank were noted.

4.0 SAMPLING AND ANALYSIS

Soil samples were collected from the excavation along the outside perimeter of the tank vaults (approximately 11:00 AM, 11/5/91) by Civil Engineer, David Prull (ASE) trained in sampling protocol. Soil sampling was at the direction of the Alameda County Health Care Services Agency Inspector- Susan Hugo.

Six soil sample were collected from the walls of the excavation in the native material approximately 6" above groundwater. Samples were collected by driving a precleaned brass sample sleeve into the soil using a hand driven slide hammer and sample shoe. All samples were secured using aluminum foil, teflon caps and sealed with duct tape. The sample was immediately placed in a cooler with dry ice and delivered to the laboratory within 24 hours. A copy of the Chain of Custody is appended to this report.

A sample of groundwater was secured from the standing groundwater outside the containment vaults. Prior to sampling, approximately 1290 gallons of groundwater were removed from the excavation and groundwater allowed to recharge. Groundwater was removed by Waste Oil Recovery systems and transported as hazardous waste to the Demmeno Kerdoon recycling facility in Compton, CA. A copy of the Hazardous Waste Manifest is appended to this report. Groundwater in the excavation was allowed to regenerate before a sample was collected with a PVC bailer. The sample was carefully transfered into 40 ml VOA vials with care taken to preclude entrained air. Additional sample All samples were material was collected in 1 liter amber bottles. labeled, placed in a cooler with ice and transported to the analyzing laboratory within 24 hours. A copy of the Chain of Custody is appended to this report.

All samples were submitted for analysis to the state certified laboratory, Chromalab, Inc. in San Ramon, California (415) 831-1788. The samples taken were analyzed for Total Petroleum Hydrocarbons as Gasoline and Diesel, and Volatile Organics. Soil samples were chemically analyzed for Lead. The results of the sampling are partially tabulated as TABLE 1: Analytical Results of Soil and Groundwater Sampling. Copies of signed laboratory data sheets are found in Appendix C.

TABLE 1: ANALYTICAL RESULTS
SOIL AND GROUNDWATER SAMPLING
Oliver Rubber Company, Emeryville, CA 11/5/91

SAMPLE I.D.	TPH GASOLINE ppm	TPH DIESEL ppm	n-Heptane	Methyl Cyclohexane ppb	Trimethyl Cyclopentanes ppb
S-1 S-2 S-3 S-4 S-5 S-6	250 1.8 27 N.D. 18 N.D.	N.D. N.D. N.D. N.D. N.D. N.D.	690 120 2300 21 1500 12	10000 340 4400 56 3400 53	2800 320 5200 63 3700 26
SAMPLE I.D.	TPH GASOLINE ppb	TPH DIESEL ppb	n-Heptane ppb	Methyl Cyclohexane ppb	Trimethyl Cyclopentanes ppb
GW-1	1900	2900	30	380	160

On November 14,1991 approximately 15 cubic yards of soil were removed from the area of soil sample S-1. Excavation of soils was conducted to a depth of approximately 10.0 feet below grade. Soil samples S-7 and S-8 were secured from the walls of the newly excavated area. The location of soil samples are shown on the partial site plan (FIGURE 2: Partial Site Plan). The results of the soil sample results are tabulated in Table 2: Analytical Results of Soil and Groundwater Sampling.

On November 14, 1991 approximately 2500 gallons of groundwater was removed from the excavation and vaults. The water was transported by Kern Vacuum Service under non-hazardous manifest to the McKittrick Waste Disposal Site, McKittrick, CA. A copy of the manifest is provided in Appendix B. A sample of groundwater was obtained subsequent to groundwater removal and recharge. The results of the water sample results are tabulated in Table 2: Analytical Results of Soil and Groundwater Sampling.

All remaining soil inside the concrete vaults was removed on November 14, 1991. The soil was placed on visqueen and covered with visqueen. The depth to the concrete bottom of the vaults is approximately 12 feet below grade.

TABLE 2: ANALYTICAL RESULTS
SOIL AND GROUNDWATER SAMPLING
Oliver Rubber Company, Emeryville, CA 11/14/91

SAMPLE I.D.	TPH GASOLINE ppm	TPH DIESE ppm	L	8240 Compour	ıds
S-7 S-8	1.3 N.D.	N.D. N.D.		N.D. N.D.	
SAMPLE I.D.			Methyl, Propyl CycloPentane ppb	-	· · · · · · · · · · · · · · · · · · ·
GW-2	1600	N.D.	30	100	50

6.0 BACKFILLING AND RESURFACING

Subsequent to cleaning the concrete vaults and over-excavating the Southwest corner of the tank pit, backfilling the work area was initiated. Backfill consisted of clean quarried material procured from the EBX facility in Hayward, CA. Soil backfill was classified as mill fine or 1/4" gravel with fines. Soil backfill was placed in one foot lifts and compacted from an elevation of approximately 12'-0" below grade to 1'-0" below grade. A subbase material consistent with a Class II AB road base was compacted in the elevations between 1'-0" and 0'-4" below grade. Portland concrete and asphaltic concrete were used to complete the restoration.

All soil removed from the tank excavation is was profiled for disposal. Copies of the analytical test data for stockpiles numbered 1 through 5 (STKP 1-5) appear in Appendix C

7.0 DISCUSSION AND CONCLUSIONS

Two underground storage tank and related plumbing were removed from the site of the Oliver Rubber Co. in Emeryville, CA. The size of the tanks was noted at 8,000 gallons each, constructed of a single layer steel plate and last contained non-halogenated organic solvents. Subsequent to tank removal the tanks were inspected for signs of leaks, holes or weaknesses; none were found.


Analytical testing of soil samples and groundwater samples in the tank excavation revealed detectable concentrations of volatile organics. All soil removed from the excavation and subsequent over-excavated (approx. 250 cubic yards) were disposed of at Class II and Class III landfill facilities as determined by profiling. All side wall soil samples taken from the overexcavated tank pit were reported to maintain concentrations of total petroleum hydrocarbons as gasoline at less than 27 parts per million. A groundwater sample collected from standing groundwater in the tank excavation prior to backfilling was reported to maintain concentrations of total petroleum hydrocarbons as gasoline at 1.6 parts per million.

The tank excavation was backfilled with clean quarried fill material and resurfaced to match surroundings.

FIGURE 1 - SITE MAP



FIGURE 2 - PARTIAL SITE PLAN



APPENDIX A - PERMITS

ALAMEDA COUNTY HEALTH CARE SERVICES AGENCY DEPARTMENT OF ENVIRONMENTAL HEALTH HAZARDOUS MATERIALS DIVISION 80 SWAN WAY, ROOM 200 OAKLAND, CA 94621 NO. 415/271-4320 PHONE

ACCEPTED

DEPARTMENT OF ENVIRONMENTAL HEALTH 470 . 2/th Streat, Third Floor Tolephone: (4.5) 874-7237 Oakland, CA 94512

able and essentially most the requirements of State and These plans have been reviewed and found to be acceptlocal health laws. Changes to your plans indicated in average to all contractors and craftimen invocad Department are to assure compliance with State en laws. The project or council trunk reference for ance of any rodding building parmits for constraint One copy of these acropted plans on at be on the the removal.

Notify this Dispuritional at loast 48 hours prior to the Any thange or alterations of those plans and anactic times must be sebratived to the Department and to the fire cos Building Inspirition Dup stoned to describing if sect changes man the requirements of State and local laws. following required in spections:

Runcyal of Tank and Piping -Sampling

pliance with accepted plans and all applicable laws aim Issuance of a pormit to operate is dependent on "Finel Propertion

:00

THERE IS A FINANCIAL PENALTY FOR HOT OBTAINING THESE INSPECTIONS. regulations:

UNDERGROUND TANK CLOSURE PLAN Complete according to attached instructions

_	Business Name OLIVER RUBBER CO.
1.	Business Name ULIVER AUSBER CO.
	Business Owner STANDARD PRODUCTS CO.
2.	Site Address
	City EMMER YVILLE CA. Zip 94608 Phone (510) 654-7711
3.	Mailing Address PO. Box 8447
	City <u>OAKLAND</u> , <u>CA</u> zip <u>3466</u> Z Phone <u>(510)654-7711</u>
4.	Land Owner OLIVER RUBBER
	Address 1200 65th ST. city, State EMMERYVILLE, (A zip 94608
5.	Generator name under which tank will be manifested
	OLIVER RUBBER CO.
	EPA I.D. No. under which tank will be manifested <u>CAC 000 644 4</u> 16
	-1 - 10/8/91 Good FOR 90 DAYS

ERYVILLE FIRE DEPARTMENT E PREVENTION BUREAU D3 HOLLIS STREET MERYVILLE, CA 94608 .55-7678

CITY OF EMERYVILLE

Nº 1153 ·

FIRE CODE PERMIT

TIRE CODE PERMIT	
RMISSION IS HEREBY GRANTED Aqua Scienge Engineers, Inc.	
8PERATE	F.P.B. Permit No
AKKINGKIK Remove 2 UG tanks	Due Date:
PREMISES LOCATED AT 1200-65th Street, (Oliver Rubber)	Original X
PREMISES LOCATED AT	Renewal
RIODIC INSPECTIONS ARE A CONDITION OF THIS PERMIT WHICH IS ISSUED IN ACCORDANCE	
TH UNIFORM FIRE CODE, AS SPECIFIED IN SECTION 4.108 OF SAID CODE.	20/07/04
DITION REQUIREMENTS EFD requires 48-hr notice prior to rem-	Date: 10/07/91 Fee: \$50.00 p/tank
oval; Alameda County representative to be present on	
site.	5. Cash Ck. No
G. CO. DISTRICT #NA EXPIRATION DATE: 11/11/91	Received by:
THIS PERMIT MUST BE PERMIT APPROVED BY	n -
POSTED WITH BUSINESS	- 0014013 7 2 checks 2014037 2 Tenks
LICENSE JOHN 10/11/7/	(2)014037 5 Tenter
Plans submitted? Checked by:(GROUP-TYPE)	
Occupancy Group? Other Occupancies in Building?	AND AREA)
Floor to be Used: Area to be Used? sq. ft. Previous Occupancy?	
BUILDING: Height Stories,ft. Type of Construction? I	s there a basement?
Location-Exterior Wall Openings?Type of Protection	
Is there 20 sq. ft. of Opening In every 50' on one exterior wall in—Cellar? Base	ement? Story?
Distance from Property Line on North? South? East?	West?
EXITS: Number? Total Width? How far Apart? Do Exits Lead to S	treet?
Number of Exits from Hazardous Area (over 200 sq. ft.)? Pa	anic Bars?
Do Doors Swing Out? Exit Signs? Illuminated?	
Number of Stairways? Width? Open or Enclosed?	
Exterior Stairway or Fire Escape? Where Located? Distance fro	om Street?
(WHICH) FIRE PROTECTION: Standpipes: Wet? Dry? Sprinklers?	
Number and Type of Extinguishers?	
Other Fire Protection?	
Is Flameproofing Required? Is it Satisfactory?	
DATE OF INSPECTION:	and Alamaha Conta
REMARKS: EFO requires 48-how notice organ to sen	10 val rolameda County
Environmentel Health representative to be on-	rito.
Nonz. Oh - AAA	
Signed Aleric Marre	TOR No

Removal of Underground Storage Tanks NOTIFICATION FORM Removal or Replacement of Tanks Excavation of Contaminated Soil
FORMATION GROSE
ZIP 94608
Tolk on the north of the of (5th Co.
valk on the north side of 65th St., cross St.; Holli
CONTAMINATED SOIL EXCAVATION SCHEDULED STARTUP DATE
STOCKPILES WILL BE COVERED? YES NO
ALTERNATIVE METHOD OF AERATION (DESCRIBE BELOW):
(DESCRIBE BELOW).
(MAY REQUIRE PERMIT)
ACTOR INFORMATION
CONTACT David Prull, Project Manager
PHONE (510) 685-6700
ILTANT INFORMATION (IF APPLICABLE)
CONTACT David Prull, Project Manager
PHONE (510) 685-6700
BY /)
(init.)
(init.)
DATE
OATEBY
DATA ENTRY 10 · 11 · 91 (init.)

HEGGENTION O, MULE 40

Permit Application and Job Notification Form



Construction Demolition Tranches Excavations Buildings Structures Falsawork Scattelding

State of California Bepartment of Industrial Relations Division of Occupational Safety & Health	District (Name) OAKLAND Date 10-7-91 No. 544356- ANNUAL
Sections 6500-6501 and 6502 of the California Labor Code require that certain activities which by their nature involve substantial risk of injury may not be performed without a permit issued by DOSH. The Labor Code requires that the applicant	the worksite subject to permit requirements. A permit will not be issued until evidence
"Applicant" refers to the employer applying for the Permit	
EmployerAQUA SCIENCE ENGINEERS	Project Salety Contact MICHAEL DIRK Employer's Representative GERALD SASSE, VP Title & Phone No VP 1-800-678-9391 Employer's State Contractor's License No. 487000
Check Applicable Items: "Applicant" refers to the employer applying t	for the Permit
Applicant is General Building Contractor X General Engineering Contractor Specialty Contractor Specialty Contractor Type Other	General Contractor Option Initial this blank if applicant elects to assume responsibility for obtaining a single permit to cover one multi-employer project e.g., a high-rise construction project. The duties of employers at the site to obey safety and health laws are not changed by this election. A list of employers on site will be attached by the Division to this application and the list will be updated as necessary.
Type of Permit Sought.	·
AnnualSingle ProjectJob Start Motification Only	Multiple Project: (If projects to be covered are similar in all important aspects, work is performed by the same employer, and information concerning each project covered is provided.)
For Construction of Building Structure Building Structure X Trench and or Excavation Tower Crane Erection Dismanting	
Scattolding and/or Falsework and or Vertical Shoring	
Any permit based on this application is issued with the understanding that the applicant has knowledge of occupational safety and health orders applicable to the projectist described in this application and attachments, and that the applicant ansupervising personnel will take special care to insure compliance with safety order reviewed with the applicant by the Division in the application process. Issuance of the permit is also conditioned upon the following. 1) Upon initiation of any new project not described in this application, the holder of a annual permit will provide the Division with a completed Project Description Form describing the new project prior to the start of work, preferably at least one week is advance of start-up date. A phone call may be used to meet the deadline but will not be considered valid notice unless followed in writing by mailing a completed Project Description Form. 2) The applicant has implemented a writen accident prevention program and Code of Safe Practices which meet the requirements of 8 California Administrative Code Section 1509.	inspections by authorized personner for the purpose of verifying that holders of permits are meeting their obligation to provide a safe work place for their employees. The Division reserves the right to revoke a permit if it unable to promptly verify compliance with the terms and conditions of the permit and its issuance. 5) The applicant understands that failure to comply with any of the above listed conditions for obtaining a permit could result in denial suspension or revocation of the permit. Employers may appear these actions to the Director of the Department of industrial Relations (California Labor Code. Section 6500 et. seq., and 8 California Administrative Code. Section 341). Is the applicant conducting any activities to be covered by this permit application in partnership or joint venture with any other persons or corporations conducting activities requiring permits? Yes
 The Division will be notified of significant changes in information provided with the application it such changes might affect the safety of the activity. 	been applied for or octained? Yes _X No 't yes when 1/91 from what district officeCONCORD in whose name _MDTRK

`

rermit Application and Joo nothication form (Continued)

Specific jobsite location 1200 65t		Field phone <u>N/A</u> Office phone <u>(510)</u> 685-6700
Nearest major cross streetHOLLI		No. of employees3
City EMERYVILLE		Starting date 10-21-91
County ALAMEDA		Anticipated completion date 11-1-91
Name and title of jobsite supervisor		High Voltage Lines in Proximity X No Yes
	PROJECT MGR.	nigh voltage Lines in Floximity 165
in or check off blanks where appro	ppriate	F JOB n knowledgeable about the project, for each jobsile to be covered by a permit. Please full Steel Frame Tiered Concrete
- ·	Liftslab F	Precast Slip Form Depth No. of Stories
	equire design by California Reg	Metal Wood Metal over 125 ft stered Civil Engineer, plans at site) [CSO 1643, 1644(c)(7)]
Job description		
•	Maximum Height	Maximum Span Material
	city Make an his site designed/constructed ction proceeds (see CSO Section	
Steel frame Wood frame	me Concrete	Height No of Stories Demolition Ball Clam Explosives
Ground Protection Method: Shoring X	Sloping	Width range (min /max) 0'-13' Total Length 50' Trench Shield Alternate TORAGE TANKS IN THE SAME LOCATION
Division Use Only	I/the applicant have knowled	it of my knewledge, the above information and assertions are true and correct and that ge of and will comply with the foregoing.
For	milD?	al l
Pald	Signatura:	
Approved	This: HEALTH &	-
Conference	Date 10-7-91	
Other	l	

APPENDIX B - HAZARDOUS WASTE MANIFEST and CERTIFICATE OF DISPOSAL

See Instructions on Back of Page 6 and Front of Page 7

Department of Health Services Toxic Substances Control Division Sacramento, California

WASTE MANIFEST WAR IN IS	. 17 1 170/01 11 17 1 1	ument No.	, of (Information in the shaded a is not required by Federal !
3. Generator's Name and Mailing Address	UBBOK SO	٨	State Manifest	Document Number 903815
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	1131	B:	State General	or's ID
13 Carrier & Ohno		4.14	1/4	149444
5. Transporter 1 Company Name	6. US EPA ID Number	7	State Transpo	
7. Transporter 2 Company Name	8 US EPA ID Number	<u> </u>	Transporter's	
7. Transporter 2 Company Name	8. US EPA ID Number	L	State Transporter's	
9. Designated Facility Name and Site Address	10. US EPA ID Number	<u> </u>	State Facility	·
J111 1100 41 800 10			4.64	
Commence MARMA H		н	Facility's Pho	ne ,
and the second second	1 1/4/ 101/2/01/11		7/2	
11. US DOT Description (Including Proper Shipping Name, Ha	zard Class, and ID Number)	12. Contain	Qua	antity Unit
		No. T	ype	Wt/Vol State
The Color of the record	111312 (16)		٠,	, <u>2</u>
The Thirty I was	1. K. 1 7.	1/1/	1/ + 1	EPA/Othe
b			*	State
				EPA/Othe
				State
c.				, Sizie
				EPA/Othe
d.		+++	1 1 1	State
			1	EPA/Othe
			1 1 1	
15. Special Handling Instructions and Additional Information	<u>, , , , , , , , , , , , , , , , , , , </u>		<u> </u>	
				* * * * * * * * * * * * * * * * * * * *
16. GENERATOR'S CERTIFICATION: 1 hereby declare that	t the contents of this consignment a	re fully and acci	rately describe highway accord	d above by proper shipping ding to applicable internation
and are classified, packed, marked, and labeled, and ar national government regulations. If I am a large quantity generator, I certify that I have a	e in all respects in proper condition	ne and toxicity of	of waste genera	
and are classified, packed, marked, and labeled, and are national government regulations.	e in all respects in proper condition program in place to reduce the voluing the practicable method of treatmen powers: OR. if I am a small quantity	ne and toxicity of t, storage, or dis generator, i hav	of waste genera	
and are classified, packed, marked, and labeled, and ar national government regulations. If I am a large quantity generator, I certify that I have a to be economically practicable and that I have selected properties of uture threat to human health and the environment.	e in all respects in proper condition program in place to reduce the voluing the practicable method of treatmen powers: OR. if I am a small quantity	ne and toxicity t, storage, or di generator, I hav I can afford.	of waste genera	
and are classified, packed, marked, and labeled, and ar national government regulations. If I am a large quantity generator, I certify that I have a property to be economically practicable and that I have selected present and future threat to human health and the envirgeneration and select the best waste management method. Printed/Typed Name	e in all respects in proper condition or ogram in place to reduce the voluing the practicable method of treatmen onment; OR, if I am a small quantity and that is available to me and that Signature	ne and toxicity of t, storage, or dis generator, i hav	of waste genera	faith effort to minimize my v
and are classified, packed, marked, and labeled, and ar national government regulations. If I am a large quantity generator, I certify that I have a to be economically practicable and that I have selected present and future threat to human health and the envir generation and select the best waste management method. Printed/Typed Name	e in all respects in proper condition program in place to reduce the voluithe practicable method of treatmen onment; OR, if I am a small quantity and that is available to me and that	ne and toxicity t, storage, or di generator, I hav I can afford.	of waste genera	faith effort to minimize my v
and are classified, packed, marked, and labeled, and ar national government regulations. If I am a large quantity generator, I certify that I have a property to be economically practicable and that I have selected present and future threat to human health and the envirgeneration and select the best waste management method. Printed/Typed Name	e in all respects in proper condition or ogram in place to reduce the voluing the practicable method of treatmen onment; OR, if I am a small quantity and that is available to me and that Signature	ne and toxicity t, storage, or di generator, I hav I can afford.	of waste genera	faith effort to minimize my v
and are classified, packed, marked, and labeled, and are national government regulations. If I am a large quantity generator, I certify that I have a to be economically practicable and that I have selected present and future threat to human health and the envir generation and select the best waste management mett. Printed/Typed Name 17. Transporter 1 Acknowledgement of Receipt of Materials. Printed/Typed Name	e in all respects in proper condition program in place to reduce the voluithe practicable method of treatmen onment; OR, if I am a small quantity tood that is available to me and that Signature Signature	ne and toxicity t, storage, or di generator, I hav I can afford.	of waste genera	faith effort to minimize my v
and are classified, packed, marked, and labeled, and ar national government regulations. If I am a large quantity generator, I certify that I have a to be economically practicable and that I have selected present and future threat to human health and the envir generation and select the best waste management method. Typed Name 17. Transporter 1 Acknowledgement of Receipt of Materials Printed/Typed Name 18. Transporter 2 Acknowledgement of Receipt of Materials	e in all respects in proper condition program in place to reduce the voluithe practicable method of treatmen pament; OR, if I am a small quantity and that is available to me and that Signature	ne and toxicity t, storage, or di generator, I hav I can afford.	of waste genera	faith effort to minimize my v
and are classified, packed, marked, and labeled, and are national government regulations. If I am a large quantity generator, I certify that I have a to be economically practicable and that I have selected present and future threat to human health and the envir generation and select the best waste management mett. Printed/Typed Name 17. Transporter 1 Acknowledgement of Receipt of Materials. Printed/Typed Name	e in all respects in proper condition program in place to reduce the voluithe practicable method of treatmen onment; OR, if I am a small quantity tood that is available to me and that Signature Signature	ne and toxicity t, storage, or di generator, I hav I can afford.	of waste genera	faith effort to minimize my v
and are classified, packed, marked, and labeled, and ar national government regulations. If I am a large quantity generator, I certify that I have a to be economically practicable and that I have selected present and future threat to human health and the envir generation and select the best waste management method. Typed Name 17. Transporter 1 Acknowledgement of Receipt of Materials Printed/Typed Name 18. Transporter 2 Acknowledgement of Receipt of Materials	e in all respects in proper condition program in place to reduce the voluithe practicable method of treatmen pament; OR, if I am a small quantity and that is available to me and that Signature	ne and toxicity t, storage, or di generator, I hav I can afford.	of waste genera	faith effort to minimize my v Month Month Month Month
and are classified, packed, marked, and labeled, and are national government regulations. If I am a large quantity generator, I certify that I have a to be economically practicable and that I have selected present and future threat to human health and the envirogeneration and select the best waste management mett. Printed/Typed Name 17. Transporter 1 Acknowledgement of Receipt of Materials. Printed/Typed Name 18. Transporter 2 Acknowledgement of Receipt of Materials. Printed/Typed Name	e in all respects in proper condition program in place to reduce the voluithe practicable method of treatmen pament; OR, if I am a small quantity and that is available to me and that Signature	ne and toxicity t, storage, or di generator, I hav I can afford.	of waste genera	faith effort to minimize my v
and are classified, packed, marked, and labeled, and are national government regulations. If I am a large quantity generator, I certify that I have a to be economically practicable and that I have selected present and future threat to human health and the envirogeneration and select the best waste management mett. Printed/Typed Name 17. Transporter 1 Acknowledgement of Receipt of Materials. Printed/Typed Name 18. Transporter 2 Acknowledgement of Receipt of Materials. Printed/Typed Name	e in all respects in proper condition program in place to reduce the voluithe practicable method of treatmen parent; OR, if I am a small quantity and that is available to me and that Signature Signature	ne and toxicity t, storage, or di generator, I hav I can afford.	of waste genera	faith effort to minimize my v Month Month Month Month
and are classified, packed, marked, and labeled, and ar national government regulations. If I am a large quantity generator, I certify that I have a property to be economically practicable and that I have selected present and future threat to human health and the envirogeneration and select the best waste management method. Typed Name 17. Transporter 1 Acknowledgement of Receipt of Materials Printed/Typed Name 18. Transporter 2 Acknowledgement of Receipt of Materials Printed/Typed Name 19. Discrepancy Indication Space	e in all respects in proper condition program in place to reduce the voluithe practicable method of treatmen onment; OR, if I am a small quantity tood that is available to me and that Signature Signature Signature	ne and toxicity t, storage, or di generator, I hav i can afford:	of waste general sposal currently e made a good	Month Month Month Month
and are classified, packed, marked, and labeled, and are national government regulations. If I am a large quantity generator, I certify that I have a to be economically practicable and that I have selected present and future threat to human health and the envirogeneration and select the best waste management method. Typed Name 17. Transporter 1 Acknowledgement of Receipt of Materials Printed/Typed Name 18. Transporter 2 Acknowledgement of Receipt of Materials Printed/Typed Name	e in all respects in proper condition program in place to reduce the voluithe practicable method of treatmen onment; OR, if I am a small quantity tood that is available to me and that Signature Signature Signature	ne and toxicity t, storage, or di generator, I hav i can afford:	of waste general sposal currently e made a good	Month Month Month Month

Do Not Write Below This Line

DHS 8022 A EPA 8700—22 (Rev. 8-89) Previous editions are obsolete.

EPA 8700-22 (Rev. 6-89) Previous editions are obsolete. Do Not Write Below This Line

SENDS THIS COPY

İ					<u>'} </u>				-
THIS	MEMO	RANDUM		and the second					
is on odinor	riedgment that a bill unliants covering the	of locking has been issued and is not if property named herein, and is intend	he Original Bill of Lading, nor ad solub for Silon or more!	·		Shipper	's No _	<u> 219</u>	
1	-,,	brakeri) moment inner i e e e e e e e e e e e e e e e e e e						010	
CARR	IER: E-	ickson. Trucking	ř-a	SCA	2	Carrier	S No Date	019	
Ό:		C Corp.	IIIC+	FROM:	Erickso	n Inc.			
U: L ∪onsig		O So. 4th St.		Shipper	255 Par				
Street		chmond, Ca. 9480	5	Street		d, Ca. 94	301		
Destin	ation		Zip -	Origin			Zip)	
l Dames	_						nicle	nn./	/
Route		Kind of Dealman, Description	of Makinton		J.D.		mber 1	724/st	70_
Shipping , Units	HM (IF	Kind of Packages, Description HAZARDOUS MATERIALS – PROPE		HAZARD CLASS	.o., dauk	ferbicat to	RATE	LABELS REQUI	
5	NON-	-D.O.T. Regualte	d Material No	n-Hazardous,	Gas Free			<u>-</u>	
"	lind	erground Storage	Tooks For So						
	CHet	ergroung atorage	Tauks FUI DC	NONE_	N/	N/A	N/A	NONE	
	0/-	70//-1	~ ~ ~ ~ ~	7		7			
"	10	174-744	<u>3/-/45</u>	<i>/</i>	_/				
	2/~	(10) - 2(19	70-			. //		,	•
│ ├── ┼	1/1/1/1	000 17-	2			/	 		
-	7/-8	110-7489	17/08-30	-7482		7			
Remit	C.O.D. to:	, UAVE. ,	/ 9 3 = +	1			/ C.	O.D. FEI	E:
Addre	ss:			CO	n .		/ Pre	paid 🔲	
City:		State:	Zip:	ՄՄ	U Amt	\$	/ Col	llect 🔲	\$
		pendent on value, shippers are re the of the property. The agreed or de		Ch. WITTE Subject to Section 7 of the us the assessment the consumer that The corner shall not make defi-	nghisma, if this physicant is to Luigh the full-rains, sections of My of this physicant cultural pay	رمانونست به به انجامانگه مه مرکز سامر که عبد انجامان به سب	Achanges	REIGHT CHAR	(GES
is hereby st	pecifically stated by	the shipper to be not exceeding \$	Per	(Speaker of Company)	erribad abous in ann				COLLECT
of pack under	rages unknown), marke the contract) agrees to	ssifications and lawfully filed tariffs in ad, consigned, and destined as indicated carry to its usual place of delivery at or any portion of said route to destina	above which said carrier (the w said destination, if on its route,	ord carrier being understood the otherwise to deliver to anothe	roughout this contract carrier on the route	t as regening any pers to said destination. It	on or corporation in p	essession of the pro	at or
Shippe	r hereby certifies that	in the governing classification on the dat the is familiar with all the bill of lading	a or snipment						
his assi		of materials are properly classified, describe of for transportation according to the applicat	d, packaged, marked ble regulations of the PLAC	000 1/1=		DIACADDA	U YES U NO-	FURNISHED BY CA	PRIFE
repartment o	transportation. Per .	LOALOSS	REQU				DRIVER SIGNATURE:		
SHIPP	ER:	Lekson, Inc.		CARRIE	R: E /	ricksen			
PER:	— Bor	Rosson	<u> </u>	PER:	Tout		<u> </u>		
DATE:			1-41	DATE:	7/17	14			
	ENCY RESPON ONE NUMBER:			Monitored at al incidental to trail	I times the Har- rsportation (172		is in transportat	ion including	storage
				•			•		-BLS-A3
					•		;	. (Re	ev. 9/90)
							•		
				HMASTER CERTIFICATE				**************************************	
Chapter 7 (con	HITHY that the tolic nmencing with Section	owing described commodity was w on 12700) of Division 5 of the Calif	eighed, measured or counted ornia Business and Profession	by a weighmaster whose s ns Code, administered by the	ignature is on this e Division of Measi	certificate who is a rement Standards of	recognized authority the California Depa	tment of Food ar	nd Agricult
	me i	METALS							
A DIVISIO		VIETALO USA CORPORATION					TTCK	ET# 655	554
Ì	600 SOUTH 4th STRE RICHMOND, CAUFOR	ET NA 94804	MATI.10	201-1 UNP			1101	, E (n = 00)	
}	(415) 236-0806		PRICE /			PAY WEI	GHT: 90	60	
ACCOL	JNT:2216	8801	TOTAL P	•					
ERICK	SON INC	•		ADJUSTMENT:			ENT: * * * *	:* %	
255 F	PARR BLV	D.	INBO	UND WEIGHT:	40780	Lbs.			
RICHM			, CA				OENGE WE		
CASH	I.D.:		BBTHE	TRUCK N	1U -	LI	CENSE NO	i •	
4676	20 (14)	Cman 11 *=1.44	DRIVE		EDT	CODE:1	/ ሶብፍፕ•ቀ	0.0	а
4078		Gross Weight Tare Weight				الرابع الرابع	/ / ·	9.80 クメコール	,
906		Net Weight	Lbs. 11/0/	731- 0:09	$ \chi$ 7	751.11	//		
, Jul	· •	ner werdir	LUJ.			- I KIKU		~~~	
<u> </u>					MUNE OF SELE	ROPERSTAIN 1			
OR SALVAGE VE	HICLE SALES HOLD	DATALESS SACREDIENT SHE WI	BELIOF SALE (warrant stat)	II Tel come (c)	MURE OF SALE		\subset		
OR SALVAGE VE ereby Confliction scient, Walterpy can classed for re Department of	HICLE S(LES.) HOLD inches person of extens sock have decimally with aftern Medical waters	HATALESS NETECHENT, Sales of any and had buyer language from the design of the sales of the sale	SEL OF SALE (Searce) that I count a searce state of the country of		METALS WEIGHM	ASTER ASTER	<u></u>	2-1162	3

THIS SHI	PPING ORDER must	be legibly filled in, in lak, in Indelibl Carbon, and retained by the A	le Pencil, or in gent.	 ス	Shipper's	No	
			$Q^{+}J$				019
CARRIER:	Frickson, Trucking	Inc	SCAC		Carrier's L	No Date	
TO:	LMC Corp.		* *******	ickson,		•	•
Consignee Street	600 So. 4th St. Richmond, Ca. 9480	5	Street Ric	Parr I	(a. 948)	01	 -
Destination	Mathematical Control	Zip	Origin		Vehi	cle	Zip
Route:					Num		
No. Shipping Units	Kind of Packages. Description (IF HAZARDOUS MATERIALS - PROPE		HAZARD Class	I.D. Number	WEIGHT (subject to correction)	RATE	LABELS REQUIRED [or exemption]
4	NON-D.O.T. Regualte	d Material Non-Ha	zardous, Gas	Free			
	Underground Storage	Tanks For Scrap.	NONE	N/A	N/A_	_N/A	NONE
	X0818-7466	7465					
7	16787-744	7					
	7/dda)-74	60					
Remit C.O.D.	to:	\	OOD:				C.O.D. FEE:
Address: City:	State:	Zip:	COD	Amt:	\$		Collect \$
ing the agreed or decla	ate is dependent on value, shippers are re ared value of the property. The agreed or de	equired to state specifically in writ	wheet to Section 7 of the constant, if the he consugate, the consegner shall find the fulle he corner shall not make default of the ships	1	world to the compares with respire and all wher lawful o		FREIGHT CHARGES
RECEIVED, subject t	stated by the shipper to be not exceeding \$ to the classifications and lawfully filed tariffs in m), marked, consigned, and destined as indicate	effect on the date of issue of this Bill of L	ading, the property discribed as	his contract as	good order, except meaning any person	as noted (con or corporatio	tents and condition of contents
under the contract)	m) marked, consigned, and destined as indicate agrees to carry to its usual place of delivery at ty over all or any portion of said route to destin conditions in the governing classification on the da- tifies that he is familiar, with all the bill of lading	said destination, it on its route, otherwise		that every s	enrice to be nerfore	ned bereunder	shall be subject to all the bill
、 his assigns.	above-named majorists are properly classified describ- ter condition for transportation according to the applica-		1/6		CARDS	YES D	O — FURNISHED BY CARRIER
Department of Transportation	~ ~ Won Los	SOM REQUIRED	0400150	รบ	PPLIED	RIVER SIGNA	TOKE:
SHIPPER:	Erickson, Inc.		CARRIER: PER:	7	Jallat	· (X	1x (0,000)
DATE:	Don Rosson.	1-4-91	DATE:)	
EMERGENCY RE		•	incidental to transporta	tion (172.604	}.		portation including storage
				 Agent must dete 	ich and retain this Sh	ipping Order at	ad must sign the Original Bill of Loding. 9-BLS-A3 (Rev. 9/90)
	the following described commodity was w	WEIGHMASTER	-kanadar udaca cianatura i	is on this certifi	cate who is a red	ognized aut	hority of accuracy as prescribed
thapter 7 (commencing wi	the following described commodity was with Section 12700) of Division 5 of the Calif	ornia Business and Professions Code,	administered by the Division	of Measuremen	nt Standards of th	ne Catifornia	Department of Food and Agricultu
	4		-				
A DIVISION OF SIMS	METALS METALUSA CORPORATION					т т	CKET# 65266
800 SQUTH	1 4th STREET D. CALIFORNIA 94804	MATL.10201-	-1 UNP			, 1	CKLT# OOL
(4.0) 200-0		PRICE / TON	1:\$	P A	Y WEIG	HT: 1	5560
ACCOUNT:2		TOTAL PRICE WEIGHT ADJU		Ø	PERCE	NT:**	****
ERICKSON 255 PARR		INBOUND	WEIGHT: 44				
RICHMOND		, CA	~5.11.5% N.S			ENCE	NΩ
CASH I.D.	:	DRIVER:1	TRUCK NO.		LIL	ENSE /	NO.
44200 (M) Gross Weight	Lbs. 11/04/91-	- 14:23 F	RT. CO	DE:1 C	057:\$	9.00
28640	Tare Weight	Lbs. 11/04/91-	- 15:01	ψ			0
~15560	Net Weight	Lbs.	SIGNATURE	OF SELLER OF	AGENT A	-	dun-
OR SALVAGE VEHICLE SALES preby certify, under penalty	S. I HOLD HARMLESS AGREEMENT: Seller will indemnify and hold buyer harmless from damage:	BLL OF SALE: I warrant that I are the own owner's representative) of the material design bereon and have the right to self same.	cribed	\$	(D)	· \	
erjury, that any vehicles sold ha een cleared for dismantling w se Department of Motor Vehicle	ave demands and liabilities, including reasonable with attorney's fees, resulting from the breach of and is, warranty hereunder and driver agrees to b	contains no hazardous material as defin	ed by DMC METALS	WEIGHMASTE			2-11401

DAY OR NIGHT TELEPHONE (510) 235-1393

REPRESENTATIVE

CERTIFICATE

CERTIFIED SERVICES COMPANY

255 Parr Boulevard - Richmond, California 94801

NO.07209

CUSTOM		
AQUA	SCI	
JOB NO.		
		76662

FOR: Erickson, Inc. TANK NO. 7459
LOCATION: Richmond DATE: 11/06/91 TIME: 12:57:37
TEST METHOD Visual Gastech/1314 SMPN LAST PRODUCT SOL
This is to certify that I have personally determined that this tank is in accordance with the American Petroleum Institute and have found the condition to be in accordance with its assigned designation. This certificate is based on conditions existing at the time the inspection herein set forth was completed and is issued subject to compliance with all qualifications and instructions.
8000 Gallon Tank SAFE FOR FIRE CONDITION
REMARKS:
LOWER EXPLOSIVE LIMIT LESS THAN 0.1%
"ERICKSON INC. HEREBY CERTIFIES THAT THE ABOVE NUMBERED TANK HAS BEEN
CUT OPEN, PROCESSED, AND THEREFORE DESTROYED AT OUR PERMITTED HAZARDOUS
WASTE FACILITY."
In the event of any physical or atmospheric changes affecting the gas-free conditions of the above tanks, or if in any doubt, immediately stop all hot work and contact the undersigned. This permit is valid for 24 hours if no physical or atmospheric changes occur.
STANDARD SAFETY DESIGNATION
SAFE FOR MEN: Means that in the compartment or space so designated (a) The oxygen content of the atmosphere is at least 19.5 percent by volume; and that (b) Toxic materials in the atmosphere are within permissable concentrations; and (c) In the judgment of the Inspector, the residues are not capable of producing toxic materials under existing atmospheric conditions while maintained as directed on the Inspector's certificate.
SAFE FOR FIRE: Means that in the compartment so designated (a) The concentration of flammable materials in the atmosphere is below 10 percent of the lower explosive limit; and that (b) In the judgment of the Inspector, the residues are not capable of producing a higher concentration that permitted under existing atmospheric conditions in the presence of fire and while maintained as directed on the Inspector's certificate, and further, (c) All adjacent spaces have either been cleaned sufficiently to prevent the spread of fire, are satisfactorily inerted, or in the case of fuel tanks, have been treated as deemed necessary by the Inspector.
The undersigned representative acknowledges receipt of this certificate and understands the conditions and limitations under

TITLE

INSPECTOR

DAY OR NIGHT TELEPHONE (510) 235-1393

which it was issued.

REPRESENTATIVE

CERTIFICATE

CERTIFIED SERVICES COMPANY

255 Parr Boulevard - Richmond, California 94801

NO. 07208	
CUSTOMER]
JOHNO SCI	

FOR: Erickson, Inc. TANK NO. 7460
LOCATION: Richmond DATE: 11/04/91 TIME: 12:44:13
EST METHOD Visual Gastech/1314 SMPN LAST PRODUCT SOL
This is to certify that I have personally determined that this tank is in accordance with the American Petroleum Institute and have found the condition to be in accordance with its assigned designation. This certificate is based on conditions existing at the time the inspection herein set forth was completed and is issued subject to compliance with all qualifications and instructions.
TANK SIZE 8000 Gallon Tank CONDITION SAFE FOR FIRE
REMARKS:OXYGEN 20.9% LOWER EXPLOSIVE LIMIT LESS THAN 0.1%
"ERICKSON INC. HEREBY CERTIFIES THAT THE ABOVE NUMBERED TANK HAS BEEN CUT OPEN. PROCESSED, AND THEREFORE DESTROYED AT OUR PERMITTED HAZARDOUS WASTE FACILITY."
In the event of any physical or atmospheric changes affecting the gas-free conditions of the above tanks, or if in any doubt, immediately stop all hot work and contact the undersigned. This permit is valid for 24 hours if no physical or atmospheric changes occur.
STANDARD SAFETY DESIGNATION SAFE FOR MEN: Means that in the compartment or space so designated (a) The oxygen content of the atmosphere is at least 19.5 percent by volume; and that (b) Toxic materials in the atmosphere are within permissable concentrations; and (c) In the judgment of the Inspector, the residues are not capable of producing toxic materials under existing atmospheric conditions while maintained as directed on the Inspector's certificate.
SAFE FOR F(RE: Means that in the compartment so designated (a) The concentration of flammable materials in the atmosphere is below 10 percent of the lower explosive limit; and that (b) in the judgment of the Inspector, the residues are not capable of producing a higher concentration that permitted under existing atmospheric conditions in the presence of fire and while maintained as directed on the Inspector's certificate, and further, (c) All adjacent spaces have either been cleaned sufficiently to prevent the spread of fire, are satisfactorily inerted, or in the case of fuel tanks, have been treated as deemed necessary by the Inspector.

The undersigned representative acknowledges receipt of this certificate and understands the conditions and limitations under

TITLE

INSPECTOR

WASTE MANIFEST 3. Generator's Name and Malifest 4. Generator's Name and Malifest 5. Transporter 1 Company Name 6. US CPA ID Number 7. Transporter 2 Company Name 8. US CPA ID Number 8. US CPA ID Number 9. State Transporter's D 7. Transporter 2 Company Name 9. US CPA ID Number 10. US CPA ID Number 11. US DOT Description (Including Project Shapping Name, Nazard Class, and ID Number) 11. US DOT Description (Including Project Shapping Name, Nazard Class, and ID Number) 12. Containing 13. Transporter's D 14. Additional Descriptions for Materials Listed Above 15. Special Handling instructions and Additional Internation 16. Generator's Project Section of Coding to Project Shapping Name, Nazard Class, and ID Number) 17. Transporter 3 Company Name 18. Individual Coding for Waster Listed Nave 19. Special Handling instructions and Additional Internation 19. Transporter 1 Authorited Annual Project Special Project Condition for transport by Information on applicable International and national government republishes. 19. In a large quantity generator, I certify that I have a program in place to endeted the volume and touchy of waste generated to the Adjessed handling information of programment project Special Proje	print or type. (Form designed for use on elit					Sacramento, Cel
8. Spale Geography Name 9. US EPA ID Number 10. US EPA ID Number 11. US EPA ID Number 12. Containing Prince 13. Transporter 2 Company Name 9. US EPA ID Number 14. Facility's Prince 15. Transporter 3 Epaster Epaster Transporter 3 Epaster Epa	1					
A. Gelherator's Project S. Transporter's Company Name O. U.S. EPA ID Number D. Pransporter's Project Transporter's Project C. State Transporter's D Transporter's Project D. Pransporter's Project D. State Transporter's Project Project D. State Transporter's Project	(11)	RR MACK TO.	1 . 1	.~	~ 4 ~ 4	Number 1628
5. Transporter 1 Company Name 6. US EPA ID Number 7. Transporter 2 Company Name 8. US EPA ID Number 8. US EPA ID Number 8. US EPA ID Number 9. Designated Facility Name and Site Address 10. US EPA ID Number 11. US DOT Description (including Project Shipping Name, Hazarid Class, and ID Number) 12. Containers 13. Transporter's Prone 13. Transporter's Prone 14. Lick 15. Transporter's Prone 15. Transporter's Prone 16. State Transporter's ID 17. Transporter's Prone 17. Transporter's Prone 18. State Transporter's ID 18. Facility is ID 19. Transporter's Prone 19. US EPA ID Number 19. Transporter's Prone 19. Transporter's Pr	4. Generator's Phone (8. S	tate-Generat	ors ID	2014 416
9. Designated Facility Name and Site Address 10. US DPA 10 Number 13. State Facility a 10 14. Facility Phone 15. Transporter's Phone 16. State Facility a 10 17. US DOT Description deciding Proper Shipping Name, Hexard Class, and I0 Nomber) 17. US DOT Description deciding Proper Shipping Name, Hexard Class, and I0 Nomber) 18. State 19. S	• •	•	C. S	tate Transpo	orter's ID	04/53
9. Designated Facility Nates and Site Address 10. US EPA ID Number 11. US DOT Description (Including Projec Shipping Name, Hazard Glass, and ID Namber) 12. Containers 13. Total 14. Waste No. 15. Total 16. Special Handling instructions for Materials Listed Above 17. Additional Descriptions for Materials Listed Above 18. Special Handling instructions and Additional Information 19. General Handling instructions and Additional Information 19. Special Handling instructions and Additional Information 19. Transporter 1 Acknowledgement of Proceeps of Materials 19. Transporter 1 Acknowledgement of Receipt of Materials 19. Transporter 1 Acknowledgement of Receipt of Materials 19. Disorepancy Indication Space 19. Disorepancy Indication Space	7. Transporter 2 Company Name	8. US EPA ID Number	<u> </u>		7	033307
H. Facility's Photos 11. US DOT Description (tecluding Proper Shipping Name, Hazard Class, and ID Number) 12. Containers No. Type 13. 73.5 3.7 7/OU 14. Waste No. 15. State EPA/Other 5. State EPA/Other 6. State EPA/Other 6. State EPA/Other 16. Special Handling Matructions and Additional Information 16. Special Handling Matructions and Additional Information 17. Special Handling Matructions and Additional Information 18. Special Handling Matructions and Additional Information 19. Transporter of Materials 19. Transporter 1 Additional Proper of Materials Printed/Typed Name Signature Month Day 19. Transporter 2 Additional Operator Certification of receipt of Materials Fortied/Typed Name Signature Month Day 19. Discrepancy Indication Space			_ 			
11. US DOT Description (including Proper Shipping Name, Hazard Class, and ID Number) 12. Containers 13. Total 14. Waste No. 15. Total 16. Special Handling instructions and Additional Information 16. Special Handling instructions and Additional Information 17. Special Handling instructions and Additional Information 18. Special Handling instructions and Additional Information 19. OENERATOR'S CERTIFICATION: I horsely declare that the contents of this consignment are fully and accurately described above by proper shipping name and are classified, packed, marked, and labeled, and are in all respects in proper condition for transport by highway seconding to applicable internetional and authors allowed in the contents of this consignment are fully and accurately described above by proper shipping name and are classified, packed, marked, and labeled, and are in all respects in proper condition for transport by highway seconding to applicable internetional and authority and applicable internetional and authority growth and accurately described above by proper shipping name and are classified, packed, marked, and labeled, and are in all respects in proper condition for transport by highway seconding to applicable internetional and authority growth and applicable internetional and authority growth and applicable internetional and authority growth and applicable internetional and authority of westle exercised to the depter I have determined to be accompanied to a proper condition for transport by highway seconding to applicable internetional and authority growth and applicable internetional and authority growth and applicable internetional and authority growth and applicable in the authority growth and appl		,	G. \$	tate Facility	's ìD	
11. US DOT Description (including Proper Shipping Name, Hazard Class, and ID Number) 12. Containers 13. Total 14. Waste No. 15. Type 16. State 17. State 18. Additional Descriptions for Materials Listed Above 16. Special Handling instructions and Additional Information 17. Special Handling instructions and Additional Information 18. Special Handling instructions and Additional Information 19. Description of the Additional Information in the Information in Information in Information in Information in Information Info	11 6 1 1 A 1100	ヒング	. 1	_		
6. GENERATOR'S CERTIFICATION: I hereby declare that the contents of this consignment are fully and accurately described above by proper shipping name and are dissatiled, packed, marked, and labeled, and are in all respects in proper condition of transport by highways according to applicable international and authors of programment regulations. I certify that I have specified in a large quantity generator, learning that these program in pieces to represent and future threat to future threat of have program in piece to reflect whether and to represent and future threat to future threat of the survey of the present and future threat to future threat of the present and the certification of the present and selected to the degree I have program in piece to reflect the piece to reflect the period of treatment and selected to the degree I have present and future threat to future threat to the present and that have careful to a present and the certification of the present and selected to the degree I have program in the present and future threat to make the present and the service of the present and future threat to make the present and the service of the present and selected to the degree I have present and the service and to treatment, according to applicable to se which entire threat to the present and the service and to treatment, according to applicable to see which entire threat to the present and the service and to the service and to the present and the service and to the service and to the service and to the service and the service and the service and the service and to the service and to the service and to the service and the servic		•		13. To	tai	
EPA/Other C. G. G. G. G. G. G. G. G. G.						t/Vol
5. State EPA/Other G. J. Additional Descriptions for Materials Listed Above K. Handling Codes for Wastes Listed Above K. Handling Codes for Wastes Listed Above Softman Con's Certrelications and Additional Information 16. GENERATOR'S CERTREICATION: I hereby declare that the contents of this consignment are fully and accurately described above by proper shipping name and are classified, packed, marked, and labeled, and are in all respects in proper condition for transport by highway according to applicable international and actional government requisible and that I have a program in place to reduce the volume and toxicity of waste generated to the degree I have determined to be economically practicable and that I have a program in place to reduce the volume and toxicity of waste generated to the degree I have determined to be economically practicable and that I have a program in place to reduce the volume and toxicity of waste generated to the degree I have determined to be economically practicable and that I have a program in place to reduce the volume and toxicity of waste generated to the degree I have determined to be economically practicable and that I have a program in place to reduce the volume and toxicity of waste generated to the degree I have determined to be economically practicable and that I have a program of the p						221
d. I. Additional Descriptions for Materials Listed Above I. Additional Descriptions for Materials Listed Above I. Additional Descriptions for Materials Listed Above I. Special Handling Instructions and Additional Information I. Special Handling Instructions and Additional Information I. Special Handling Instructions and Additional Information I. Additional Descriptions for Materials Listed Above I. Special Handling Instructions and Additional Information I. I	b.	<u> </u>	TV TV	+VV	AKI	/ State
d. State EPA/Other J. Additional Descriptions for Materials Listed Above K. Handling Codes for Westers Listed Above K. Handling Codes for Westers Listed Above J. Additional Descriptions for Materials Listed Above K. Handling Codes for Westers Listed Above K. Handling Codes for Westers Listed Above J. Additional Information 16. GENERATOR'S CERTIFICATION: I hereby declare that the contents of this consignment are fully and accurately described above by groper shapping name and are classified, packed, marked, and labeled, and are in all respects in proper condition for fransport by highway according to applicable internetional and national government regulations. If I am a large quantity generator, I certify that I have a program in place to reduce the volume and toxicity of waste generated to the degree have determined to be economically practicable and that I have selected the practicable method of treatment, storage, or disposal currently available to me which minimizes the present and truter threat to human health and the environment OR, if I am a simal quantity generator, I have made a good faith effort to minimize the present and truter threat to human health and the environment OR, if I am a simal quantity generator, I have made a good faith effort to minimize the present and truter threat to human health and the environment OR, if I am a simal quantity generator, I have made a good faith effort to minimize the present and the environment of the present and the						EPA/Other
d. 3. Additional Descriptions for Materials Listed Above K. Handling Codes for Wastes Listed Above K. Handling Codes for Wastes Listed Above S. Special Handling Instructions and Additional Information 16. GENERATOR'S CERTIFICATION: I hereby declare that the contests of this consignment are fully and accurately described above by proper shipping name and are classified, packed, marked, and labeled, and are in all respects in proper condition for transport by highway scoording to applicable international government regulations. If I am a large quantity generator, I certify that I have a program in place to reduce the volume and toxicity of waste generated to the degree I have determined to be economically practicable and that I have selected the practicable method of treatment, storage, or disposal currently available to me which minimizes the present and future threat to human health and the environment. OR, if I am a small quantity pencentor, I have made a good faith effort to minimize my waste generation and select the best waste management method that is available to me and that I can afford. Printed/Typed Name Signature Month Day 17. Transporter 2 Acknowledgement of Receipt of Materials Printed/Typed Name Signature Month Day 18. Transporter 2 Acknowledgement of Receipt of Materials Printed/Typed Name Signature Month Day 19. Discrepancy Indication Space	c.	<u> </u>	+	 		State
J. Additional Descriptions for Materials Listed Above K. Handling Codes for Westes Listed Above K. Handling Codes for Westes Listed Above G. Special Handling Instructions and Additional Information 16. GENERATOR'S CERTIFICATION: I hereby declare that the contents of this consignment are fully and accurately described above by proper shipping name and are classified, packed, marked, and labeled, and are in all respects in proper condition for transport by highway according to applicable international and national government regulations. If I am a targe quantity generator, I certify that I have a program in place to reduce the volume and toxicity of waste generated to the degree I have determined to be economically practicable and that I have selected the practicable method of treatment, storage, or disposal currently available to me which nitimizes the present and future threat to human health and the environment. OR, if an a small quantity generator, I have made a good faith effort to minimize my waste present and future threat to human health and the environment. OR, if an a small quantity generator, I have made a good faith effort to minimize my waste present and future threat to human health and the environment. OR, if an a small quantity generator, I have made a good faith effort to minimize my waste present and future threat to human health and the environment. OR, if an a small quantity generator, I have made a good faith effort to minimize my waste my made and the present and health of the manufactor of the present and health of the present of the degree I have determined to be economically of the present of the degree I have determined to the health of						EPA/Other
J. Additional Descriptions for Materials Listed Above K. Handling Codes for Waster Listed Above 15. Special Handling Instructions and Additional Information 16. GENERATOR'S CERTIFICATION: I hereby declare that the contents of this consignment are fully and accurately described above by proper shipping name and are classified, packed, marked, and labeled, and are in all respects in proper condition for transport by highway according to applicable internetional and national government regulations. If I am a large quantity generator, I certify that I have a program in place to reduce the volume and toxicity of waste generated to the degree I have determined to be economically practicable and that I have selected the practicable method of treatment, storage, or disable to the which minimizes the present and future threat to human health and the environment; OR, if I am a small quantity generator, I have made a good faith effort to minimize my waste generation and select the best waste management method that is evalible to me which minimizes the present and the program of the program	d.		 	 	- 	N 20 34 42.4
15. Special Handling Instructions and Additional Information 16. GENERATOR'S CERTIFICATION: I hereby declare that the contents of this consignment are fully and accurately described above by proper shipping name and are classified, packed, marked, and labeled, and are in all respects in proper condition for transport by highway according to applicable international and netional government regulations. If I am a large quantity generator, I certify that I have a program in place to reduce the volume and toxicity of waste generated to the degree I have determined to be sconomically practicable and that I have selected the practicable method of treatment, storage, or disposal currently available to me which intrinsizes the present and future threat to human health and the environment; OR, II am a small quantity generator, I have made a good faith effort to minimize my waste generators and select the best waste management method that is available to me and that I can affort. 17. Transporter 1 Acknowledgement of Receipt of Materials Printed/Typed Name Signature Month Day 18. Transporter 2 Acknowledgement of Receipt of Materials Printed/Typed Name Signature Month Day 19. Discrepancy Indication Space				1 1		
15. Special Handling Instructions and Additional Information 16. GENERATOR'S CERTIFICATION: I hereby declare that the contents of this consignment are fully and accurately described above by proper shipping name and are classified, packed, marked, and labeled, and are in all respects in proper condition for transport by highway according to applicable interactional and national government regulations. If I am a large quantity generator, I certify that I have a program in place to reduce the volume and toxicity of waste generated to the degree I have determined to be economically practicable and that I have selected the practicable method of treatment, storage, or disposal currently available to me which minimizes the present and future threat to human health and the environment; OR, if I am a small quantity generator, I have made a good faith effort to minimize my waste generation and select the best waste management method that is available to me and that I can afford. Printed/Typed Name Signature Month Day 17. Transporter 1 Acknowledgement of Receipt of Materials Printed/Typed Name Signature Month Day 19. Discrepancy Indication Space	J. Additional Descriptions for Materials Liste	d Above	K. I	landling Cod	les for Was	tes:Listed Aboves
16. GENERATOR'S CERTIFICATION: I hereby declare that the contents of this consignment are fully and accurately described above by proper shipping name and are classified, packed, marked, and labeled, and are in all respects in proper condition for transport by highway according to applicable international government regulations. If I am a large quantity generator, I certify that I have a program in place to reduce the volume and toxicity of waste generated to the degree I have determined to be economically practicable and that I have selected the practicable method of treatment, storage, or disposal currently available to me which minimizes the present and future threat to human health and the environment; OR, if I am a small quantity generator, I have made a good faith effort to minimize the present and turure threat to human health and the environment; OR, if I am a small quantity generator, I have made a good faith effort to minimize the generation and select the best waste management method that is available to me and that I can afford. Printed/Typed Name Signature Month Day 17. Transporter 1 Acknowledgement of Receipt of Materials Printed/Typed Name Signature Month Day 19. Discrepancy Indication Space	160				X	
16. GENERATOR'S CERTIFICATION: I hereby declare that the contents of this consignment are fully and accurately described above by proper shipping name and are classified, packed, marked, and labeled, and are in all respects in proper condition for transport by highway according to applicable international government regulations. If I am a large quantity generator, I certify that I have a program in place to reduce the volume and toxicity of waste generated to the degree I have determined to be economically practicable and that I have selected the practicable method of treatment, storage, or disposal currently available to me which minimizes the present and future threat to human health and the environment; OR, if I am a small quantity generator, I have made a good faith effort to minimize the present and turure threat to human health and the environment; OR, if I am a small quantity generator, I have made a good faith effort to minimize the generation and select the best waste management method that is available to me and that I can afford. Printed/Typed Name Signature Month Day 17. Transporter 1 Acknowledgement of Receipt of Materials Printed/Typed Name Signature Month Day 19. Discrepancy Indication Space	1 14 A ST	I SOUTH THUS EHA	11/115			
GENERATOR'S CERTIFICATION: I hereby declare that the contents of this consignment are fully and accurately described above by proper shipping name and are classified, packed, marked, and labeled, and are in all respects in proper condition for transport by highway according to applicable international and national government regulations. If I am a large quantity generator, I certify that I have a program in place to reduce the volume and toxicity of waste generated to the degree I have determined to be economically practicable and that I have selected the practicable method of treatment, storage, or disposal currently available to me which minimizes the present and future threat to human health and the environment; OR, if I am a small quantity generator, I have made a good faith effort to minimize my waste generation and select the best waste management method that is available to me and that I can afford. Printed/Typed Name Signature Month Day 17. Transporter 1 Acknowledgement of Receipt of Materials Printed/Typed Name Signature Month Day 18. Transporter 2 Acknowledgement of Receipt of Materials Printed/Typed Name Signature Month Day 19. Discrepancy Indication Space				<u> </u>		
GENERATOR'S CERTIFICATION: I hereby declare that the contents of this consignment are fully and accurately described above by proper shipping name and are classified, packed, marked, and labeled, and are in all respects in proper condition for transport by highway according to applicable international and national government regulations. If I am a large quantity generator, I certify that I have a program in place to reduce the volume and toxicity of waste generated to the degree I have determined to be economically practicable and that I have selected the practicable method of treatment, storage, or disposal currently available to me which minimizes the present and future threat to human health and the environment; OR, if I am a small quantity generator, I have made a good faith effort to minimize my waste generation and select the best waste management method that is available to me and that I can afford. Printed/Typed Name Signature Month Day 17. Transporter 1 Acknowledgement of Receipt of Materials Printed/Typed Name Signature Month Day 18. Transporter 2 Acknowledgement of Receipt of Materials Printed/Typed Name Signature Month Day 19. Discrepancy Indication Space						
GENERATOR'S CERTIFICATION: I hereby declare that the contents of this consignment are fully and accurately described above by proper shipping name and are classified, packed, marked, and labeled, and are in all respects in proper condition for transport by highway according to applicable international and national government regulations. If I am a large quantity generator, I certify that I have a program in place to reduce the volume and toxicity of waste generated to the degree I have determined to be economically practicable and that I have selected the practicable method of treatment, storage, or disposal currently available to me which minimizes the present and future threat to human health and the environment; OR, if I am a small quantity generator, I have made a good faith effort to minimize my waste generation and select the best waste management method that is available to me and that I can afford. Printed/Typed Name Signature Month Day 17. Transporter 1 Acknowledgement of Receipt of Materials Printed/Typed Name Signature Month Day 18. Transporter 2 Acknowledgement of Receipt of Materials Printed/Typed Name Signature Month Day 19. Discrepancy Indication Space					-	
and are classified, packed, marked, and labeled, and are in all respects in proper condition for transport by highway according to applicable international and national government regulations. If I am a large quantity generator, I certify that I have a program in place to reduce the volume and toxicity of waste generated to the degree I have determined to be economically practicable and that I have selected the practicable method of treatment, storage, or disposal currently available to me which minimizes the present and future threat to human health and the environment; OR, if I am a small quantity generator, I have made a good faith effort to minimize my waste generation and select the best waste management method that is available to me and that I can afford. Printed/Typed Name Signature Month Day Month Day 18. Transporter 2 Acknowledgement of Receipt of Materials Printed/Typed Name Signature Month Day 19. Discrepancy Indication Space		rehy declare that the contents of this consignment a	re fully and accurate	ly describe	d above by	oroner shinning same
to be economically practicable and that I have selected the practicable method of treatment, storage, or disposal currently available to me which minimizes the present and future threat to human health and the environment; OR, if I am a small quantity generator, I have made a good faith effort to minimize my waste generation and select the best waste management method that is available to me and that I can afford. Printed/Typed Name Signature Month Day 17. Transporter 1 Acknowledgement of Receipt of Materials Printed/Typed Name Signature Month Day 18. Transporter 2 Acknowledgement of Receipt of Materials Printed/Typed Name Signature Month Day 19. Discrepancy Indication Space	and are classified, packed, marked, and	I labeled, and are in all respects in proper condition	for transport by high	away accord	ling to appli	cable international and
Printed/Typed Name) 17. Transporter 1 Acknowledgement of Receipt of Materials Printed/Typed Name Signature Month Day 18. Transporter 2 Acknowledgement of Receipt of Materials Printed/Typed Name Signature Month Day 19. Discrepancy Indication Space 20. Facility Owner or Operator Certification of receipt of hazardous materials covered by this manifest except as noted in Item 19.	to be economically practicable and that present and future threat to human hea	I have selected the practicable method of treatment th and the environment; OR, if I am a small quantity	t, storage, or dispos generator, I have m	al currently	available to	me which minimizes the
17. Transporter 1 Acknowledgement of Receipt of Materials Printed/Typed Name Signature Month Day 18. Transporter 2 Acknowledgement of Receipt of Materials Printed/Typed Name Signature Month Day 19. Discrepancy Indication Space 20. Facility Owner or Operator Certification of receipt of hazardous materials covered by this manifest except as noted in Item 19.	Printed/Typed Name	Signature				Month Day
Printed/Typed Name 18. Transporter 2 Acknowledgement of Receipt of Materials Printed/Typed Name Signature Month Day 19. Discrepancy Indication Space 20. Facility Owner or Operator Certification of receipt of hazardous materials covered by this manifest except as noted in Item 19.			5.37	٢,		///Y_5_L
18. Transporter 2 Acknowledgement of Receipt of Materials Printed/Typed Name Signature Month Day 19. Discrepancy Indication Space 20. Facility Owner or Operator Certification of receipt of hazardous materials covered by this manifest except as noted in Item 19.	L	<u> </u>			 -	Month Day
18. Transporter 2 Acknowledgement of Receipt of Materials Printed/Typed Name Signature Month Day 19. Discrepancy Indication Space 20. Facility Owner or Operator Certification of receipt of hazardous materials covered by this manifest except as noted in Item 19.	;		44	~ í		VIVE ISE
19. Discrepancy Indication Space 20. Facility Owner or Operator Certification of receipt of hazardous materials covered by this manifest except as noted in Item 19.		eipt of Materials				P
20. Facility Owner or Operator Certification of receipt of hazardous materials covered by this manifest except as noted in Item 19.	Printed/Typed Name	Signature				Month Day
	19. Discrepancy Indication Space				·	
Printed/Typed Name Signature Month Day	20. Facility Owner or Operator Certification	of receipt of hazardous materials covered by this m	anifest except as ne	oted in Item	19.	
	Printed/Typed Name	Signature				Month Day

KERN BACKHUE SERVICE IN __ KERN DACDUM SERVICE

Well, Tank No	P.O. BOX 5337	 BAKERSFIELD, CALIFORNIA 9338
Field or Area		(805) 589-5220

Nº14028

NON-HAZARDOUS WASTE HAULER RECORD

TO BE USED FOR NON-HAZARDOUS WASTES ONLY

TO BE USED FOR NON-HAZ	AUDODO MAGICO ONCI
City, State, Zip — State De Hope; Signature of Authorized Agent — My York Total Date 11-14-9 Title Construction Syrenyisok	WASTE TO BE DISPOSED Type
Name Address PO 3x . 5337 City, State, Zip Address Signature of Authorized Agent or Driver Date Date	Pick Up Date
Name Address City, State, Zip / Disp. Ticket # Signature of Authorized Agent Date	Quantity Received Bbls. Date AM Time PM DISPOSAL METHOD: Surface Impoundment Injection Landfill Other Return Copy To: GENERATOR UNLESS OTHERWISE SPECIFIED NOTE: It is not necessary to send copy to Dept. of Health Services. NO HAZARDOUS FEES SHOULD BE LEVIED
GENERATOR COPY	10.00

APPENDIX C - LABORATORY ANALYSIS and CHAIN OF CUSTODY

Analytical Laboratory (E694)

November 7, 1991

ChromaLab File No.: 1191042

AQUA SCIENCE ENGINEERS, INC.

Attn: David Prull

RE: Six soil and one water sample for Gasoline and Diesel analyses

Project Name: OLIVER RUBBER CO.

1200 65th St., Emeryville, CA Project Location:

Project Number: Job 2410

Date Sampled: Nov. 5, 1991

Date Extracted: Nov. 7, 1991

Date Analyzed: Nov. 7, 1991

RESULTS:

Sample	Gasoline	Diesel
<u>I.D.</u>	(mg/kg)	(mg/kg)
S-1	250*	N.D.
S-2	1.8*	N.D.
S-3	27*	N.D.
S-4	N.D.	N.D.
S-5	18*	N.D.
S-6	N.D.	N.D.
DETECTION LIMIT	1.0	1.0
METHOD OF ANALYSIS	5030/8015	3550/8015
Sample	Gasoline	Diesel
I.D.	(µg/l)	(μg/l)
GW-1	1900*	2900
BLANK	N.D.	N.D.
SPIKED RECOVERY	96.3%	89.7%
DUPLICATE SPIKED RECOVERY	94.2%	92.5%
DETECTION LIMIT	50	50
METHOD OF ANALYSIS	5030/8015	3510/8015

^{*}Unknown hydrocarbon quantified as gasoline.

ChromaLab, Inc.

David Duong

Chief Chemist

Eric Tam

Laboratory Director

5 DAYS TURNAROUND

Analytical Laboratory (E694)

November 8, 1991

ChromaLab File No.: 1191042

AQUA SCIENCE ENGINEERS, INC.

Attn: David Prull

RE: Six soil samples for Lead analysis

Project Name: OLIVER RUBBER CO.

Project Location: 1200 65th St., Emeryville, CA

Project Number: Job 2410

Date Sampled: Nov. 5, 1991 Date Submitted: Nov. 5, 1991
Date Extracted: Nov. 8, 1991 Date Analyzed: Nov. 8, 1991

RESULTS:

Sample I.D.	Lead (mg/kg)
S-1	6.96
S-2	6.86
S-3	4.45
S-4	6.59
S-5	7.47
S-6	6.54
BLANK	N.D.
SPIKED RECOVERY	104%
DUPLICATE SPIKED RECOVERY	92%
DETECTION LIMIT	0.05
METHOD OF ANALYSIS	7420
	-

ChromaLab, Inc.

Refart A. Mankarious Inorganics Supervisor

Eric Tam

Laboratory Director

Analytical Laboratory (E694)

November 7, 1991

ChromaLab File # 1191042 A

Aqua Science Engineers, Inc.

Date Sampled: Nov. 05, 1991

David Prull Attn: Date Submitted: Nov. 05, 1991

Date Analyzed: Nov. 07, 1991

Project Name: Oliver Rubber Co.

Project Number: Job 2410 Sample 1.D.: S-1

Method of Analysis: 8240 Detection Limit: 10 µg/kg

COMPOUND NAME	ug/kg	Spike Recovery
CHLOROMETHANE	N.D.	opike Recovery
VINYL CHLORIDE	N.D.	
BROMOMETHANE	N.D.	-
CHLOROETHANE	N.D.	===
TRICHLOROFLUOROMETHANE	N.D.	
1,1-DICHLOROETHENE	N.D.	92.4% 95.6%
METHYLENE CHLORIDE	N.D.	
1,2-DICHLOROETHENE (TOTAL)	N.D.	
1,1-DICHLOROETHANE	N.D.	-
CHLOROFORM	N.D.	
1,1,1-TRICHLOROETHANE	N.D.	
CARBON TETRACHLORIDE	N.D.	
1,2-DICHLOROETHANE	N.D.	
BENZENE	N.D.	93.4% 96.1%
TRICHLOROETHENE	N.D.	
1,2-DICHLOROPROPANE	N.D.	
BROMODICHLOROMETHANE	N.D.	<u> </u>
2-CHLOROETHYLVINYLETHER	N.D.	
TRANS-1,3-DICHLOROPROPENE	N.D.	
TOLUENE	N.D.	94.0% 96.7%
CIS-1,3-DICHLOROPROPENE	N.D.	
1,1,2-TRICHLOROETHANE	N.D.	
TETRACHLOROETHENE	N.D.	
DIBROMOCHLOROMETHANE	N.D.	
CHLOROBENZENE	N.D.	92.4% 95.8%
ETHYLBENZENE	(15)	
BROMOFORM	M.D.	
1,1,2,2-TETRACHLOROETHANE	N.D.	
1,3-DICHLOROBENZENE	N.D.	
1,4-DICHLOROBENZENE	N.D.	
1,2-DICHLOROBENZENE	N.D.	
TOTAL XYLENES	(14)	
ACETONE	N.D.	-
METHYL ETHYL KETONE	N.D.	
METHYL ISOBUTYL KETONE (CONTINUED ON NEXT PAGE)	N.D.	

Analytical Laboratory (E694)

.

5 DAYS TURNAROUND

page 2

November 7, 1991

ChromaLab File # 1191042 A

Project Name: Oliver Rubber Co.

Project Number: Job 2410

Sample I.D.: S-1

Method of Analysis: 8240

Detection Limit:

10 µg/kg

ADDITIONAL

COMPOUND NAME	ug/kg
n-HEXANE	N.D.
n-HEPTANE	690
CYCLOHEXANE	3500
METHYL CYCLOHEXANE	10000
DIMETHYL CYCLOPENTANE	N.D.
TRIMETHYL CYCLOPENTANES	2800

ChromaLab, Inc.

David Duong

Chief Chemist

Eric Tam

Lab Director

Analytical Laboratory (E694)

November 7, 1991

ChromaLab File # 1191042 B

David Prull

Date Submitted: Nov. 05, 1991

Attn:

Aqua Science Engineers, Inc.

Date Sampled: Nov. 05, 1991

Date Analyzed: Nov. 07, 1991

Project Name: Oliver Rubber Co.

Project Number: Job 2410 Sample I.D.: S-2

Method of Analysis: 8240 Detection Limit: 10 µg/kg

COMPOUND NAME	цg/kg	Spike Recovery
CHLOROMETHANE	N.D.	
VINYL CHLORIDE	N.D.	
BROMOMETHANE	N.D.	
CHLOROETHANE	N.D.	-
TRICHLOROFLUOROMETHANE	N.D.	-
1,1-DICHLOROETHENE	N.D.	92.4% 95.6%
METHYLENE CHLORIDE	N.D.	-
1,2-DICHLOROETHENE (TOTAL)	N.D.	
1,1-DICHLOROETHANE	N.D.	
CHLOROFORM	N.D.	
1,1,1-TRICHLOROETHANE	N.D.	
CARBON TETRACHLORIDE	N.D.	,
1,2-DICHLOROETHANE	N.D.	
BENZENE	N.D.	93.4% 96.1%
TRICHLOROETHENE	N.D.	
1,2-DICHLOROPROPANE	N.D.	
BROMODICHLOROMETHANE	N.D.	
2-CHLOROETHYLVINYLETHER	N.D.	 -
TRANS-1,3-DICHLOROPROPENE	N.D.	 -
TOLUENE	N.D.	94.0% 96.7%
CIS-1,3-DICHLOROPROPENE	N.D.	
1,1,2-TRICHLOROETHANE	N.D.	
TETRACHLOROETHENE	N.D.	
DIBROMOCHLOROMETHANE	N.D.	
CHLOROBENZENE	N.D.	92.4% 95.8%
ETHYLBENZENE	N.D.	
BROMOFORM	N.D.	
1,1,2,2-TETRACHLOROETHANE	N.D.	
1,3-DICHLOROBENZENE	N.D.	
1,4-DICHLOROBENZENE	N.D.	
1,2-DICHLOROBENZENE	N.D.	
TOTAL XYLENES	N.D.	
ACETONE	N.D.	
METHYL ETHYL KETONE	N.D.	
METHYL ISOBUTYL KETONE (CONTINUED ON NEXT PAGE)	N.D.	

Analytical Laboratory (E694)

5 DAYS TURNAROUND

page 2

November 7, 1991

ChromaLab File # 1191042 B

Project Name: Oliver Rubber Co.

Project Number: Job 2410

S-2

Sample 1.D.: Method of Analysis: 8240

Detection Limit:

 $10 \mu g/kg$

ADDITIONAL

COMPOUND NAME	ug/kg	
n-HEXANE	N.D.	
n-HEPTANE	120	
CYCLOHEXANE	N.D.	
METHYL CYCLOHEXANE	340	
DIMETHYL CYCLOPENTANE	N.D.	
TRIMETHYL CYCLOPENTANES	320	

ChromaLab, Inc.

Chief Chemist

Eric Tam

Lab Director

Analytical Laboratory (E694)

November 7, 1991

ChromaLab File # 1191042 C

Aqua Science Engineers, Inc.

Date Sampled: Nov. 05, 1991

David Prull Attn: Date Submitted: Nov. 05, 1991

Date Analyzed: Nov. 07, 1991

Project Name: Oliver Rubber Co.

Project Number: Job 2410 Sample | .D.: S-3

Method of Analysis: 8240 Detection Limit: 10 µg/kg

COMPOUND NAME	μg/kg	Spike Recovery
CHLOROMETHANE	N.D.	
VINYL CHLORIDE	N.D.	~ ~ ~
BROMOMETHANE	N.D.	- -
CHLOROETHANE	N.D.	-
TRICHLOROFLUOROMETHANE	N.D.	~ - ~
1,1-DICHLOROETHENE	N.D.	92.4% 95.6%
METHYLENE CHLORIDE	N.D.	
1,2-DICHLOROETHENE (TOTAL)	N.D.	
1,1-DICHLOROETHANE	N.D.	
CHLOROFORM	N.D.	
1,1,1-TRICHLOROETHANE	N.D.	
CARBON TETRACHLORIDE	N.D.	
1,2-DICHLOROETHANE	N.D.	
BENZENE	N.D.	93.4% 96.1%
TRICHLOROETHENE	N.D.	<u></u>
1,2-DICHLOROPROPANE	N.D.	
BROMODICHLOROMETHANE	N.D.	
2-CHLOROETHYLVINYLETHER	N.D.	
TRANS-1,3-DICHLOROPROPENE	N.D.	- a
TOLUENE	N.D.	94.0% 96.7%
CIS-1,3-DICHLOROPROPENE	N.D.	
1,1,2-TRICHLOROETHANE	N.D.	
TETRACHLOROETHENE	N.D.	
DIBROMOCHLOROMETHANE	N.D.	~ ~ ~ ~
CHLOROBENZENE	N.D.	92.4% 95.8%
ETHYLBENZENE	N.D.	
BROMOFORM	N.D.	-
1,1,2,2-TETRACHLOROETHANE	N.D.	
1,3-DICHLOROBENZENE	N.D.	
1,4-DICHLOROBENZENE	N.D.	
1,2-DICHLOROBENZENE	N.D.	
TOTAL XYLENES	N.D.	
ACETONE	N.D.	-
METHYL ETHYL KETONE	N.D.	
METHYL ISOBUTYL KETONE	N.D.	
(CONTINUED ON NEXT PAGE)		

Analytical Laboratory (E694)

5 DAYS TURNAROUND

page 2

November 7, 1991

ChromaLab File # 1191042 C

Project Name: Oliver Rubber Co.

Project Number: Job 2410

S-3

Sample I.D.:

Method of Analysis: 8240

Detection Limit: 10 μg/kg

ADDITIONAL

COMPOUND NAME	ug/kg
n-HEXANE	N.D.
n-HEPTANE	2300
CYCLOHEXANE	N.D.
METHYL CYCLOHEXANE	4400
DIMETHYL CYCLOPENTANE	N.D.
TRIMETHYL CYCLOPENTANES	5200

ChromaLab, Inc.

David Duong

Chief Chemist

Eric Tam

Lab Director

Analytical Laboratory (E694)

November 7, 1991

ChromaLab File # 1191042 p

Aqua Science Engineers, Inc. Date Sampled: Nov. 05, 1991

nc. Attn: David Prull

Date Sampled:

Nov. 07, 1991

Date Submitted: Nov. 05, 1991

Project Name: Oliver Rubber Co.

Project Number: Job 2410 Sample I.D.: S-4

Method of Analysis: 8240

Detection Limit: 10 µg/kg

COMPOUND NAME	ug/kg	Crika Brazuanu
CHLOROMETHANE	N.D.	Spike Recovery
VINYL CHLORIDE	N.D.	
BROMOMETHANE	N.D.	
CHLOROETHANE	N.D.	
TRICHLOROFLUOROMETHANE	N.D.	
1,1-DICHLOROETHENE	N.D.	92.4% 95.6%
METHYLENE CHLORIDE	N.D.	52.4% 55.6%
1,2-DICHLOROETHENE (TOTAL)	N.D.	
1,1-DICHLOROETHANE	N.D.	·
CHLOROFORM	N.D.	
1,1,1-TRICHLOROETHANE	N.D.	
CARBON TETRACHLORIDE	N.D.	. ———
1,2-DICHLOROETHANE	N.D.	AL
BENZENE	N.D.	93.4% 96.1%
TRICHLOROETHENE	N.D.	
1,2-DICHLOROPROPANE	N.D.	
BROMODICHLOROMETHANE	N.D.	
2-CHLOROETHYLVINYLETHER	N.D.	
TRANS-1,3-DICHLOROPROPENE	N.D.	
TOLUENE	N.D.	94.0% 96.7%
CIS-1,3-DICHLOROPROPENE	N.D.	
1,1,2-TRICHLOROETHANE	N.D.	
TETRACHLOROETHENE	N.D.	
DIBROMOCHLOROMETHANE	N.D.	
CHLOROBENZENE	N.D.	92.4% 95.8%
ETHYLBENZENE	N.D.	
BROMOFORM	N.D.	-
1,1,2,2-TETRACHLOROETHANE	N.D.	-
1,3-DICHLOROBENZENE	N.D.	
1,4-DICHLOROBENZENE	N.D.	
1,2-DICHLOROBENZENE	N.D.	
TOTAL XYLENES	N.D.	
ACETONE	N.D.	
METHYL ETHYL KETONE	N.D.	
METHYL ISOBUTYL KETONE (CONTINUED ON NEXT PAGE)	N.D.	

Analytical Laboratory (E694)

5 DAYS TURNAROUND

page 2

November 7, 1991

ChromaLab File # 1191042 D

Project Name: Oliver Rubber Co.

Project Number: Job 2410 Sample 1.D.:

Method of Analysis:

8240

Detection Limit: 10 µg/kg

ADDITIONAL

COMPOUND NAME	ug/kg
n-HEXANE	N.D.
n-HEPTANE	21
CYCLOHEXANE	N.D.
METHYL CYCLOHEXANE	56
DIMETHYL CYCLOPENTANE	N.D.
TRIMETHYL CYCLOPENTANES	63

ChromaLab, Inc.

Chief Chemist

Lab Director

Analytical Laboratory (E694)

November 7, 1991

ChromaLab File # 1191042 E

Aqua Science Engineers, Inc.

Date Sampled: Nov. 05, 1991 Date Analyzed: Nov. 07, 1991 Attn: David Prull
Date Submitted: Nov. 05, 1991

Project Name: Oliver Rubber Co. Project Number: Job 2410 Sample I.D.: S-5

Method of Analysis: 8240

Detection Limit: 10 µg/kg

COMPOUND NAME	ug/kg	Spike Recovery
CHLOROMETHANE	N.D.	
VINYL CHLORIDE	N.D.	···
BROMOMETHANE	N.D.	
CHLOROETHANE	N.D.	
TRICHLOROFLUOROMETHANE	N.D.	₩-₩
1,1-DICHLOROETHENE	N.D.	92.4% 95.6%
METHYLENE CHLORIDE	N.D.	
1,2-DICHLOROETHENE (TOTAL)	N.D.	
1,1-DICHLOROETHANE	N.D.	
CHLOROFORM	N.D.	
1,1,1-TRICHLOROETHANE	N.D.	
CARBON TETRACHLORIDE	N.D.	
1,2-DICHLOROETHANE	N.D.	
BENZENE	79	93.4% 96.1%
TRICHLOROETHENE	N.D.	
1,2-DICHLOROPROPANE	N.D.	
BROMODICHLOROMETHANE	N.D.	·
2-CHLOROETHYLVINYLETHER	N.D.	·
TRANS-1,3-DICHLOROPROPENE	N.D.	
TOLUENE	N.D.	94.0% 96.7%
CIS-1,3-DICHLOROPROPENE	N.D.	
1,1,2-TRICHLOROETHANE	N.D.	
TETRACHLOROETHENE	N.D.	
DIBROMOCHLOROMETHANE	N.D.	-
CHLOROBENZENE	N.D.	92.4% 95.8%
ETHYLBENZENE	N.D.	
BROMOFORM	N.D.	
1,1,2,2-TETRACHLOROETHANE	N.D.	
1,3-DICHLOROBENZENE	N.D.	
1,4-DICHLOROBENZENE	N.D.	
1,2-DICHLOROBENZENE	N.D.	
TOTAL XYLENES	N.D.	
ACETONE	N.D.	
METHYL ETHYL KETONE	N.D.	
METHYL ISOBUTYL KETONE (CONTINUED ON NEXT PAGE)	N.D.	

Analytical Laboratory (E694)

page 2

5 DAYS TURNAROUND

November 7, 1991

ChromaLab File # 1191042 E

Project Name: Oliver Rubber Co.

Project Number: Job 2410

Sample 1.D.:

Detection Limit: $10 \mu g/kg$ Method of Analysis: 8240

ADDITIONAL ug/kg COMPOUND NAME N.D. n~HEXANE 1500 n-HEPTANE N.D. CYCLOHEXANE 3400 METHYL CYCLOHEXANE N.D. DIMETHYL CYCLOPENTANE 3700 TRIMETHYL CYCLOPENTANES

ChromaLab, Inc.

David Duong

Chief Chemist

Eric Tam Lab Director

Analytical Laboratory (E694)

November 7, 1991

ChromaLab File # 1191042 F

David Prull

Aqua Science Engineers, Inc.

Date Sampled: Nov. 05, 1991

Date Submitted: Nov. 05, 1991

Date Analyzed: Nov. 07, 1991

Project Name: Oliver Rubber Co.

Project Number: Job 2410 Sample I.D.: S-6

Detection Limit: 10 µg/kg Method of Analysis: 8240

Attn:

COMPOUND NAME	ug/kg	Spike Recovery
CHLOROMETHANE	N.D.	
VINYL CHLORIDE	N.D	
BROMOMETHANE	N.D.	
CHLOROETHANE	N.D.	
TRICHLOROFLUOROMETHANE	N.D.	
1,1-DICHLOROETHENE	N.D.	92.4% 95.6%
METHYLENE CHLORIDE	N.D.	
1,2-DICHLOROETHENE (TOTAL)	N.D.	
1,1-DICHLOROETHANE	N.D.	
CHLOROFORM	N.D.	
1,1,1-TRICHLOROETHANE	N.D.	
CARBON TETRACHLORIDE	N.D.	
1,2-DICHLOROETHANE	N.D.	
BENZENE	N.D.	93.4% 96.1%
TRICHLOROETHENE	N.D.	
1,2-DICHLOROPROPANE	N.D.	
BROMODICHLOROMETHANE	N.D.	==-
2-CHLOROETHYLVINYLETHER	N.D.	
TRANS-1,3-DICHLOROPROPENE	N.D.	
TOLUENE	N.D.	94.0% 96.7%
CIS-1,3-DICHLOROPROPENE	N.D.	
1,1,2-TRICHLOROETHANE	N.D.	
TETRACHLOROETHENE	N.D.	<u> </u>
DIBROMOCHLOROMETHANE	N.D.	
CHLOROBENZENE	N.D.	92.4% 95.8%
ETHYLBENZENE	N.D.	
BROMOFORM	N.D.	THE SHAPE SAME
1,1,2,2-TETRACHLOROETHANE	N.D.	
1,3-DICHLOROBENZENE	N.D.	
1,4-DICHLOROBENZENE	N.D.	~
1,2-DICHLOROBENZENE	N.D.	
TOTAL XYLENES	N.D.	
ACETONE	N.D.	
METHYL ETHYL KETONE	N.D.	 -
METHYL ISOBUTYL KETONE (CONTINUED ON NEXT PAGE)	N.D.	

5 DAYS TURNAROUND

Analytical Laboratory (E694)

page 2

November 7, 1991

ChromaLab File # 1191042 F

Project Name: Oliver Rubber Co.

Project Number: Job 2410

Sample I.D.: S-6

Method of Analysis: 8240 Detection Limit: 10 μg/kg

ADDITIONAL

COMPOUND NAME µg/kg

n-HEXANE N.D.

n-HEPTANE 12

CYCLOHEXANE N.D.

METHYL CYCLOHEXANE 53

DIMETHYL CYCLOPENTANE N.D. 7

TRIMETHYL CYCLOPENTANES 26

ChromaLab, Inc.

David Duong/

Chief Chemist

Eric Tam Lab Director

5 DAYS TURNAROUND

CHROMALAB, INC.

Analytical Laboratory (E694)

November 7, 1991

ChromaLab File # 1191042 G

Aqua Science Engineers, Inc.

Date Sampled: Nov. 05, 1991 Date Analyzed: Nov. 07, 1991

Attn: David Prull Date Submitted: Nov. 05, 1991

Project Name: Oliver Rubber Co.

Project Number: Job 2410 Sample I.D.:

GW-1 Method of Analysis: 624

Detection Limit: 2.0 µg/l

COMPOUND NAME	<u>µg/</u>]	Spike Recovery
CHLOROMETHANE	N.D.	
VINYL CHLORIDE	N.D.	
BROMOMETHANE	N.D.	
CHLOROETHANE	N.D.	
TRICHLOROFLUOROMETHANE	N.D.	
1,1-DICHLOROETHENE	N.D.	92.4% 95.6%
METHYLENE CHLORIDE	N.D.	₩ - -
1,2-DICHLOROETHENE (TOTAL)	N.D.	
1,1-DICHLOROETHANE	N.D.	
CHLOROFORM	N.D.	~ ~ ~
1,1,1-TRICHLOROETHANE	N.D.	
CARBON TETRACHLORIDE	N.D.	~
1,2-DICHLOROETHANE	N.D.	 -
BENZENE	2.1	93.4% 96.1%
TRICHLOROETHENE	N.D.	·-
1,2-D1CHLOROPROPANE	N.D.	
BROMODICHLOROMETHANE	N.D.	
2-CHLOROETHYLVINYLETHER	N.D.	
TRANS-1,3-DICHLOROPROPENE	N.D.	
TOLUENE	(2.)	94.0% 96.7%
CIS-1,3-DICHLOROPROPENE	N.D.	
1,1,2-TRICHLOROETHANE	N.D.	-
TETRACHLOROETHENE	N.D.	
DIBROMOCHLOROMETHANE	N.D.	
CHLOROBENZENE	N.Q.	92.4% 95.8%
ETHYLBENZENE	(2.0	
BROMOFORM	N.D.	
1,1,2,2-TETRACHLOROETHANE	N.D.	
1,3-DICHLOROBENZENE	N.D.	
1,4-DICHLOROBENZENE	N.D.	~~~
1,2-DICHLOROBENZENE	N.D.	
TOTAL XYLENES	(18)	
ACETONE	M.D.	
METHYL ETHYL KETONE	N.D.	
METHYL ISOBUTYL KETONE (CONTINUED ON NEXT PAGE)	N.D.	

5 DAYS TURNAROUND

Analytical Laboratory (E694)

page 2

November 7, 1991

1191042 G ChromaLab File #

Project Name: Oliver Rubber Co.

Project Number: Job 2410

Sample 1.D.:

GW-1

Method of Analysis:

Detection Limit: 2.0 µg/1

ADDITIONAL

COMPOUND NAME <u>ug/1</u> n-HEXANE N.D. n-HEPTANE 30 / 43 / 380 CYCLOHEXANE METHYL CYCLOHEXANE N.D. DIMETHYL CYCLOPENTANE

ChromaLab, Inc.

TRIMETHYL CYCLOPENTANES

David Duong

Chief Chemist

Eric Tam

1604

Lab Director

aqua science en la composition de la composition

Aqua Science Engineers Inc.,

PO Box 535, San Ramon, CA 94583 • 415-820-9391

Chain of Custody

DATE_NOV 5 PAGE_/ OF

ROJ. OLIV	ER K	UBBE	P (6										ANA	LYSIS	REQ	UEST	,		IDON	1 A I A	R FI	IF:	# 119	1042
COMPANY 0	LIVER	RU81	57.	<u>6.</u>	g	e (5030) 602, 8020)	(95	34471CS 32, 8020)	PURGEABLE HALOCARBONS (EPA 601, 8010)	WICS (0)	S, ACIDS	GREASE	ងខ្ល	X0)			602 1, m,		OF	RDER	垃		54	, ~
AMPLERS (SIGNATUR	Chru	_	0)685.		t - Casolii PA 5030)	TPM - Gasoline (W/BTEX (EPA 60)	TPN - Diesel (EPA 3510, 3550)	PURCEABLE AROMATICS BTEX (EPA 602, 8020)	PA 601, 80	WILE DRG	BASE/WEUTRALS, (EPA 624/627, 1	TOTAL OIL & CREASE (EPA 50301E)	STICIDES/F	PHENOLS (EPA 604, 8040)			ETALS:	CUT NETALS	PRIORITY POLILI NETALS (13)					NUMBEROF
SAMPLE ID.	DATE		MATRIX	LAB ID.	TPM -	£ 3	E E	X 10	<u> 5</u>	Q E	≦ ≝	2 3	<u> </u>	2 2			Š	0 2	Z E			-		
5-1	11/5/51	11:30	5		$\langle \rangle$		(X)			$\stackrel{\times}{\hookrightarrow}$							\Leftrightarrow	 		}_		- · ·		+
5-2	11/5/91	11:40	5	į	\times		\times			\times									ļ	├—				
5-3	11/5/51				X		X			\times							\times			<u> </u>				
	1 / /								,								X			1				1/
5-4	11/5/51				\bigcirc					\Diamond	 -													,
5-5	11/5/91	12:10	5		\bigcirc		$\langle \mathcal{L} \rangle$				ļ						\Leftrightarrow			-	 			1
5-6	11/5/31	12:20	.5		\geq		X			\angle				<u> </u>						├—			-	
GW-1	11/5/51	16:41)	W		\times		$ \times $			\times										ļ				1
	1//	10 10			/					LP	CY	7772 1201 4EX	NES YEX	me							ļ			
	<u> </u>										17-1		TAN.	11/1	2///	XA	بعرا							
						DEL MONIEUED BY O A KA					RELINQUISHED BY 2.						RELINOUISHED BY 3.							
PROJECT INFORM		TOTAL	SAMPL NO. OF C	E RECEIPT		10				~	Tru	U												
ROJECT. OLIVER	RUBBER		OF CUSTO								ne)	(Signature) (Time)					ıwe)	(Signature) (Time)						
ONO JOB 2	410		GOOD CO		OLD		iPerni	ed Nam	10)			(Da	(4)	(Printed Name) (Date)					atel	(Printed Name) (Date)				
HIPPING ID NO	4	CONFC	RMS TO R	ECORD	AQUA SCIENCE 11/5/91					9/	(Company)						(Company)							
TA DAUM		LABN	J. 		(Company)					1. [RECEIVED BY 2					2.	RECEIVED BY (LABORATORY) 3.							
SPECIAL INSTRUCTION	IS/COMMEN	ITS:	_		(272 MIL DAZ 18702)																			
48 14.7	URN.	FAX	RE50	1175 B	13 & (Signature) Cook (1/5/9)			ne) (1	(Signature) (Time)						(Time) (Time)									
THURS	11/7/9.	/.						eu Nac				IDa		(Printed Name) (Date)						(Printed Name)				
							_	panyl	::					Compa	ny)					(LAB)				

5 DAYS TURNAROUND

CHROMALAB, INC.

Analytical Laboratory (E694)

November 7, 1991

ChromaLab File No.: 1191022

AQUA SCIENCE ENGINEERS, INC.

Attn: David Prull

RE: four soil samples for Gasoline and Diesel analyses

Project Name: OLIVER RUBBER CO.

Project Location: 1200 65th St., Emeryville, CA

Project Number: Job 2410

Date Sampled: Nov. 4, 1991 Date Submitted: Nov. 4, 1991 Date Extracted: Nov. 6, 1991 Date Analyzed: Nov. 7, 1991

RESULTS:

Sample I.D.	Gasoline (mg/kg)	Diesel (mg/kg)
STKP1	1.7	N.D.
STKP2	1.8	N.D.
STKP3	1.7	N.D.
STKP4	N.D.	N.D.
BLANK	N.D.	N.D.
SPIKED RECOVERY	96.3%	89.7%
DUPLICATE SPIKED RECOVERY	94.2%	92.5%
DETECTION LIMIT	1.0	1.0
METHOD OF ANALYSIS	5030/8015	3550/8015

ChromaLab, Inc.

David Duong

Chief Chemis

Laboratory Director

5 DAYS TURNAROUND

Analytical Laboratory (E694)

November 7, 1991

ChromaLab File No.: 1191022

AQUA SCIENCE ENGINEERS, INC.

Attn: D. Prull

RE: Four composite samples for Lead analysis

Project Name: OLIVER RUBBER CO.

Project Location: 1200 65th St., Emeryville, CA

Project Number: 2410

Date Submitted: Nov. 4, 1991
Date Analyzed: Nov. 7 Date Sampled: Nov. 4, 1991 Date Extracted: Nov. 5, 1991 Date Analyzed: Nov. 5, 1991

RESULTS:

Sample 1.D.	
STKP1 (A-D)	5.31
STKP2 (A-D)	21.9
STKP3 (A-D)	15.6
STKP4 (A-D)	5.78
BLANK	N.D.
DETECTION LIMIT	2.5
METHOD OF ANALYSIS	6010

ChromaLab, Inc.

Refact H. Mayon Refaat A. Mankarious Inorganics Supervisor

c Tam

Laboratory Director

5 DAYS TURNAROUND

Analytical Laboratory (E694)

December 4, 1991

ChromaLab File No.: 1191022

AQUA SCIENCE ENGINEERS, INC.

Attn: David Prull

RE: Four rush composited soil samples for Oil & Grease analysis

Project Name: OLIVER RUBBER CO.

Project Location: 1200 65th St., Emeryville, CA

Project Number: 2410

Date Sampled: Nov. 4, 1991 Date Submitted: Nov. 4, 1991 Date Extracted: Dec. 4, 1991 Date Analyzed: Dec. 4, 1991

RESULTS:

Sample I.D. Oil & Grease (mg/kg)

STKP1(A-D) STKP2 (A-D)

STKP3 (A-D)

STKP4 (A-D)

BLANK

DETECTION LIMIT

METHOD OF ANALYSIS

N.D.

N.D.

210

14

63

10

5520 E&F

ChromaLab, Inc.


David Duong

Chief Chemist

Evirtam (by 00)

Eric Tam

Laboratory Director



RECEIVED

DEC 1 8 1991

AQUA SCIENCE ENG.

Analytical Laboratory (E694)

November 7, 1991

ChromaLab File # 1191022 A

David Prull

Aqua Science Engineers, Inc.

Date Sampled: Nov. 05, 1991 Date Analyzed: Nov. 06, 1991

Attn:

Date Submitted: Nov. 05, 1991

Project Name: Oliver Rubber Co.

Project Number: Job 2410 Sample 1.D.: STKP 1

Detection Limit: 10 µg/kg Method of Analysis: 8240

	71	
COMPOUND NAME	ug/kg	Spike Recovery
CHLOROMETHANE	N.D.	
VINYL CHLORIDE	N.D.	
BROMOMETHANE	N.D.	 -
CHLOROETHANE	N.D.	~
TRICHLOROFLUOROMETHANE	N.D.	
1,1-DICHLOROETHENE	N.D.	92.4% 95.6%
METHYLENE CHLORIDE	N.D.	
1,2-DICHLOROETHENE (TOTAL)	N.D.	
1,1-DICHLOROETHANE	N.D.	
CHLOROFORM	N.D.	
1,1,1-TRICHLOROETHANE	N.D.	
CARBON TETRACHLORIDE	N.D.	
1,2-DICHLOROETHANE	N.D.	
BENZENE	N.D.	93.4% 96.1%
TRICHLOROETHENE	N.D.	
1,2-DICHLOROPROPANE	N.D.	 -
BROMODICHLOROMETHANE	N.D.	
2-CHLOROETHYLVINYLETHER	N.D.	
TRANS-1,3-DICHLOROPROPENE	N.D.	-
TOLUENE	N.D.	94.0% 96.7%
CIS-1,3-DICHLOROPROPENE	N.D.	
1,1,2-TRICHLOROETHANE	N.D.	
TETRACHLOROETHENE	N.D.	
DIBROMOCHLOROMETHANE	N.D.	
CHLOROBENZENE	N.D.	92.4% 95.8%
ETHYLBENZENE	N.D.	32.4% 33.0%
BROMOFORM	N.D.	
1,1,2,2-TETRACHLOROETHANE	N.D.	
1,3-DICHLOROBENZENE	N.D.	
1,4-DICHLOROBENZENE	N.D.	
1,2-DICHLOROBENZENE		
TOTAL XYLENES	N.D.	 -
ACETONE	17	*
	N.D.	~= <u>-</u>
METHYL ETHYL KETONE	N.D.	 -
METHYL ISOBUTYL KETONE (CONTINUED ON NEXT PAGE)	N.D.	-

Analytical Laboratory (E694)

page 2

5 DAYS TURNAROUND

November 7, 1991

ChromaLab File # 1191022 A

Project Name: Oliver Rubber Co.

Project Number: Job 2410 Sample I.D.:

STKP 1

Method of Analysis: 8240

Detection Limit: 10 μg/kg

ADDITIONAL

COMPOUND NAME	ug/kg
n-HEXANE	N.D.
n-HEPTANE	200
CYCLOHEXANE	150
METHYL CYCLOHEXANE	1500
DIMETHYL CYCLOPENTANE	980
TRIMETHYL CYCLOPENTANES	780

ChromaLab, Inc.

David Duong

Chief Chemist

Eric Tam

Lab Director

Analytical Laboratory (E694)

November 7, 1991

ChromaLab File # 1191022 B

Aqua Science Engineers, Inc.

neers, Inc. Attn: David Prull
Nov. 05 1991 Date Submitted: Nov

Date Sampled: Nov. 05, 1991 Date Analyzed: Nov. 06, 1991 Date Submitted: Nov. 05, 1991

Project Name: Oliver Rubber Co.

Project Number: Job 2410
Sample I.D.: STKP 2

Method of Analysis: 8240 Detection Limit: 10 µg/kg

COMPOUND NAME	ug/kg	Spike Recovery
CHLOROMETHANE	N.D.	
VINYL CHLORIDE	N.D.	
BROMOMETHANE	N.D.	
CHLOROETHANE	N.D.	
TRICHLOROFLUOROMETHANE	N.D.	 -
1,1-DICHLOROETHENE	N.D.	92.4% 95.6%
METHYLENE CHLORIDE	N.D.	
1,2-DICHLOROETHENE (TOTAL)	N.D.	
1,1-DICHLOROETHANE	N.D.	
CHLOROFORM	N.D.	
1,1,1-TRICHLOROETHANE	N.D.	
CARBON TETRACHLORIDE	N.D.	
1,2-DICHLOROETHANE	N.D.	
BENZENE	N.D.	93.4% 96.1%
TRICHLOROETHENE	N.D.	-
1,2-DICHLOROPROPANE	N.D.	
BROMODICHLOROMETHANE	N.D.	am 544
2-CHLOROETHYLV I NYLETHER	N.D.	
TRANS-1,3-DICHLOROPROPENE	N.D.	
TOLUENE	N.D.	94.0% 96.7%
CIS-1,3-DICHLOROPROPENE	N.D.	
1,1,2-TRICHLOROETHANE	N.D.	
TETRACHLOROETHENE	N.D.	
DIBROMOCHLOROMETHANE	N.D.	
CHLOROBENZENE	N.D.	92.4% 95.8%
ETHYLBENZENE	21	
BROMOFORM	N.D.	
1,1,2,2-TETRACHLOROETHANE	N.D.	
1,3-DICHLOROBENZENE	N.D.	~ ~
1,4-DICHLOROBENZENE	N.D.	
1,2-DICHLOROBENZENE	N.D.	
TOTAL XYLENES	190	
ACETONE	N.D.	
METHYL ETHYL KETONE	N.D.	
METHYL ISOBUTYL KETONE	N.D.	
(CONTINUED ON NEXT PAGE)		

Analytical Laboratory (E694)

page 2

5 DAYS TURNAROUND

November 7, 1991

ChromaLab File # 1191022 B

Project Name: Oliver Rubber Co.

Project Number: Job 2410

STKP 2

Sample 1.D.: Method of Analysis: 8240

Detection Limit: 10 μg/kg

ADDITIONAL

COMPOUND NAME	<u> </u>
n-HEXANE	N.D.
n-HEPTANE	150
CYCLOHEXANE	N.D.
METHYL CYCLOHEXANE	470
DIMETHYL CYCLOPENTANE	240
TRIMETHYL CYCLOPENTANES	270

ChromaLab, inc.

Chief Chemist

Eric Tam

Lab Director

Analytical Laboratory (E694)

November 7, 1991

ChromaLab File # 1191022 C

Aqua Science Engineers, Inc.

David Prull Attn:

Date Sampled: Nov. 05, 1991 Date Submitted: Nov. 05, 1991

Date Analyzed: Nov. 06, 1991

Project Name: Oliver Rubber Co.

Project Number: Job 2410 STKP 3 Sample I.D.:

Method of Analysis: 8240 Detection Limit: 10 µg/kg

COMPOUND NAME	ug/kg	Spike Recovery
CHLOROMETHANE	N.D.	
VINYL CHLORIDE	N.D.	
BROMOMETHANE	N.D.	
CHLOROETHANE	N.D.	
TRICHLOROFLUOROMETHANE	N.D.	
1,1-DICHLOROETHENE	N.D.	92.4% 95.6%
METHYLENE CHLORIDE	N.D.	
1,2-DICHLOROETHENE (TOTAL)	N.D.	-
1,1-DICHLOROETHANE	N.D.	
CHLOROFORM	N.D.	
1,1,1-TRICHLOROETHANE	N.D.	
CARBON TETRACHLORIDE	N.D.	
1,2-DICHLOROETHANE	N.D.	
BENZENE	N.D.	93.4% 96.1%
TRICHLOROETHENE	N.D.	
1,2-DICHLOROPROPANE	N.D.	
BROMODICHLOROMETHANE	N.D.	
2-CHLOROETHYLVINYLETHER	N.D.	
TRANS-1,3-DICHLOROPROPENE	N.D.	
TOLUENE	N.D.	94.0% 96.7%
CIS-1,3-DICHLOROPROPENE	N.D.	
1,1,2-TRICHLOROETHANE	N.D.	
TETRACHLOROETHENE	N.D.	
DIBROMOCHLOROMETHANE	N.D.	-
CHLOROBENZENE	N.D.	92.4% 95.8%
ETHYLBENZENE	N.D.	
BROMOFORM	N.D.	
1,1,2,2-TETRACHLOROETHANE	N.D.	
1,3-DICHLOROBENZENE	N.D.	
1,4-DICHLOROBENZENE	N.D.	
1,2-DICHLOROBENZENE	N.D.	
TOTAL XYLENES	27	
ACETONE	N.D.	
METHYL ETHYL KETONE	N.D.	,
METHYL ISOBUTYL KETONE	N.D.	
(CONTINUED ON NEXT PAGE)		

5 DAYS TURNAROUND

Analytical Laboratory (E694)

page 2

November 7, 1991

ChromaLab File # 1191022 C

Project Name: Oliver Rubber Co.

Project Number: Job 2410 Sample 1.D.:

STKP 3

Method of Analysis: 8240

Detection Limit:

10 µg/kg

ADDITIONAL

COMPOUND NAME	µg/kg
n-HEXANE	N.D.
n-HEPTANE	99
CYCLOHEXANE	N.D.
METHYL CYCLOHEXANE	370
DIMETHYL CYCLOPENTANE	150
TRIMETHYL CYCLOPENTANES	250

ChromaLab, Inc.

David Duong

Chief Chemist

Eric Tam

Lab Director

5 DAYS TURNAROUND

CHROMALAB, INC.

Analytical Laboratory (E694)

November 7, 1991

ChromaLab File # 1191022 D

Aqua Science Engineers, Inc.

eers, Inc. Attn: David Prull

Date Sampled: Nov. 05, 1991 Date Analyzed: Nov. 06, 1991 Date Submitted: Nov. 05, 1991

Project Name: Oliver Rubber Co.

Project Number: Job 2410
Sample 1.D.: STKP 4

Method of Analysis: 8240 Detection Limit: 10 μg/kg

COMPOUND NAME	μg/kg	Spike Recovery
CHLOROMETHANE	N.D.	
VINYL CHLORIDE	N.D.	
BROMOMETHANE	N.D.	
CHLOROETHANE	N.D.	
TRICHLOROFLUOROMETHANE	N.D.	
1,1-DICHLOROETHENE	N.D.	92.4% 95.6%
METHYLENE CHLORIDE	N.D.	
1,2-DICHLOROETHENE (TOTAL)	N.D.	
1,1-DICHLOROETHANE	N.D.	
CHLOROFORM	N.D.	
1,1,1-TRICHLOROETHANE	N.D.	
CARBON TETRACHLORIDE	N.D.	
1,2-DICHLOROETHANE	N.D.	
BENZENE	N.D.	93.4% 96.1%
TRICHLOROETHENE	N.D.	
1,2-DICHLOROPROPANE	N.D.	
BROMODICHLOROMETHANE	N.D.	·
2-CHLOROETHYLVINYLETHER	N.D.	
TRANS-1,3-DICHLOROPROPENE	N.D.	
TOLUENE	N.D.	94.0% 96.7%
CIS-1,3-DICHLOROPROPENE	N.D.	
1,1,2-TRICHLOROETHANE	N.D.	
TETRACHLOROETHENE	N.D.	
DIBROMOCHLOROMETHANE	N.D.	
CHLOROBENZENE	N.D.	92.4% 95.8%
ETHYLBENZENE	N.D.	~~~
BROMOFORM	N.D.	
1,1,2,2-TETRACHLOROETHANE	N.D.	
1,3-DICHLOROBENZENE	N.D.	
1,4-DICHLOROBENZENE	N.D.	
1,2-DICHLOROBENZENE	N.D.	
TOTAL XYLENES	N.D.	
ACETONE	N.D.	
METHYL ETHYL KETONE	N.D.	
METHYL ISOBUTYL KETONE (CONTINUED ON NEXT PAGE)	N.D.	

5 DAYS TURNAROUND

Analytical Laboratory (E694)

page 2

November 7, 1991

1191022 D ChromaLab File #

Project Name: Oliver Rubber Co.

Project Number: Job 2410 Sample 1.D.:

STKP 4

Method of Analysis: 8240

Detection Limit: 10 µg/kg

ADDITIONAL

COMPOUND NAME	ug/kg
n-HEXANE	N.D.
n-HEPTANE	55
CYCLOHEXANE	N.D.
METHYL CYCLOHEXANE	220
DIMETHYL CYCLOPENTANE	N.D.
TRIMETHYL CYCLOPENTANES	190

ChromaLab, Inc.

David Duong

Chief Chemist

Eric Tam

Lab Director

aqua science Essengineers inc.

Aqua Science Engineers Inc.,

PO Box 535, San Ramon, CA 94583 • 415-820-9391

Chain of Custody DATE NOV 3 1991 PAGE 1 OF 1

PROJ. OLIVE	EP {	UBBE	R C	ý 0									ANA	LYSIS	REQ	JEST		,			ים ל	ı: c	# 110	11022
COMPANY OLI ADDRESS IZC	DAR	RUBI 55 Th	ST.		e e	re (5030) 602, 8020)	530)	DMTICS 02, 8020)	PURCEABLE HALOCARBONS (EPA 601, 8010)	ANICS 40)	RASE/NEUTRALS, ACTOS (EPA 624/627, 8270) •	GREASE	80% (080	8040)			1EAD 1. 10.		0	RDEF	AB F ₹ #		# 119 24	I
AMPLERS ISIGNATURE	Chu	W	(PHO 510)60	one no.1 85-6700	- Gesol i A 5030)	TPM - Casoline w/STEX (EPA 60)	TPM - Dieset (EPA 3510, 3550)	PURCEABLE ARONATICS BTEX (EPA 602, 802	GEABLE HA A 601, 80	VOLATILE ORGANICS (EPA 624, 8240)	E/KEUTRAL 14 624/627	TOTAL OIL & CREASE (EPA 5030&E)	PESTICIDES/PCB (EPA 608, 8080)	PHENOLS (EPA 604, 8			70794 ETALS: ■,	CAN NETALS (18) M/Cr VI	PRIORITY POLL NETALS (13)					NUMBER OF
SAMPLE ID.	DATE	TIME	MATRIX	LAB ID.	1 M	¥ 2	TP#	PURGE BTEX	2 3	2 6	SE E	و ع	<u> </u>	₹ ¹³			× ×	23	医 原	 	<u> </u>			+-,
STKP1 (A-D)	11/4/91	11:30	5		\geq		\geq		.	$\langle \times \rangle$				 			\Leftrightarrow	 	<u> </u>					4
STKPZ(A-D)		11:30	.5		\geq		\geq			$\langle \rangle$									ļ				-	14
STKP3(A-D)					\geq		\geq			\geq				ļ			$\stackrel{\times}{\hookrightarrow}$			<u> </u> 				14
5TKP4(A-D)	114/91	11:30	5		\times		\times			X				ļ							_			+7
			{ 							4	1511	-6												
	,							li e iii e		CLC	HE	MAN	<u> </u>											
								100	17- M1	HF	DI	W	COH	EXA	WE									
														<u>.</u>		50.5			2.	9511/	VOLUS	HED BY		
PROJECT INFORM	ATION			E REÇEIP			REL	INQUI	SHED	BY	? ?::	1		RELIN	OUISH	EUBT				******	145.0			
PROJECT. OLIVER	RUBBER			ONTAINE		16	(Signi	ture)	<u>- (_</u>		- Li	1717) 1675	ne)	Signatu	re)			(T	ime)	Signat	ure)			(Time)
00 VOB 6	2410	REC'D	GOOD CO	NDITION/			(Print	ed Nan	nel	nev	<u> </u>	(D)	19)	(Printed Name) (Date) / (Company)				ate)	(Print)	d Nam	e) /	, ,	(Date)	
SHIPPING ID NO	14		AMS TO F	RECORD		l	J.Com	900	4 50	:/En	/CE	-11/3	751	(Compa	ny)		1	·····		(Comp	19/1	77		
TIA D. PRO	141_	LABN	O.		(Company)					RECEIVED BY 2				2.	RECE	VED E	Y Y AS	RATOR	(A) T					
SPECIAL INSTRUCTION	S/COMME	NTS:	وسند	,		·>													ıme)	(Signa	turel	W TO THE		(Time)
HE HR. THURS. 11/1 SET OF E	TURN	FA	X KI	=SULT.	5	BY	lSign	ature)						(Signate						<i>I</i>	d Nam		17.	(Time) /O (DATE)
THUPS. 11/7	7/91.	Com	post	TE	ACI	4	(Prin	ted Nar	nel			(Da		(Compa		· 		, L					B	11.4.9/
SET OF P	OUR	AS I	9 51N	KLE	SAM	PLE	1Com	(Auedu		~~.				1COmp.				,			rice	, -		مُنسماسين

5 DAYS TURNAROUND

Analytical Laboratory (E694)

November 21, 1991

ChromaLab File No.: 1191135

AQUA SCIENCE ENGINEERS, INC.

Attn: David Prull

RE: Three soil samples for Gasoline and Diesel analyses

Project Name: OLIVER RUBBER

Project Location: 1200 65th St., Emeryville

Project Number: 2410

Date Sampled: Nov. 14, 1991 Date Submitted: Nov. 14, 1991 Date Extracted: Nov. 19-20,1991

RESULTS:

Sample I.D.	Gasoline (mg/kg)	Diesel (mg/kg)
S-7	1.3	N.D.
S-8	N.D.	N.D.
STKP5*	N.D.	N.D.
BLANK	N.D.	N.D.
SPIKED RECOVERY	98.0%	92.6%
DUPLICATE SPIKED RECOVERY	93.8%	88.0%
DETECTION LIMIT	1.0	1.0
METHOD OF ANALYSIS	5030/8015	3550/8015

^{*}Composited soil sample.

ChromaLab, Inc.

David Duong

Chief Chemist

Erstam (by 20)

Eric Tam

Laboratory Director

and the second of the second of the second

Analytical Laboratory (E694)

November 22, 1991

ChromaLab File # 1191135 A

Client: Aqua Science Engineers

Attn: Dave Prull

Date Sampled: Nov. 14, 1991

Date Submitted: Nov. 14, 1991

Date Analyzed: Nov. 21, 1991

Project Name: Oliver Rubber, 1200 65th St., Emeryville

Project Number: 2410 Sample 1.D.: S-7

Method of Analysis: 8240

Detection Limit: $5.0 \mu g/kg$

ug/kg	Spike Recovery
N.D.	
N.D.	
N.D.	
N.D.	
N.D.	
N.D.	92.3% 96.4%
N.D.	
N.D.	
N.D.	
N.D.	
N.D.	
N.D.	
N.D.	'
N.D.	95.7% 90.4%
N.D.	
N.D.	93.4% 95.8%
N.D.	
N.D.	
N.D.	
N.D.	
N.D.	91.0% 93.6%
N.D.	
N.D.	<u></u>
N.D.	
N.D.	
N.D.	
N.D.	 -
N.D.	
N.D.	
N.D.	
N.D.	
	N.D. D. N.D. N.D. N.D. N.D. N.D. N.D. N

ChromaLab, Inc.

David Duong Senior Chemist Eric Tam Lab Director Analytical Laboratory (E694)

November 22, 1991

ChromaLab File # 1191135 B

Client: Aqua Science Engineers

Attn: Dave Prull

Date Submitted: Nov. 14, 1991

Date Sampled: Nov. 14, 1991 Date Analyzed: Nov. 21, 1991

Project Name: Oliver Rubber, 1200 65th St., Emeryville

Project Number: 2410 Sample I.D.:

S-8

Method of Analysis: 8240

Detection Limit: 5.0 µg/kg

COMPOUND NAME	µg/kg	Spike Recovery
CHLOROMETHANE	N.D.	
VINYL CHLORIDE	N.D.	
BROMOMETHANE	N.D.	
CHLOROETHANE	N.D.	
TRICHLOROFLUOROMETHANE	N.D.	
1,1-DICHLOROETHENE	N.D.	92.3% 96.4%
METHYLENE CHLORIDE	N.D.	
1,2-DICHLOROETHENE (TOTAL)	N.D.	
1,1-DICHLOROETHANE	N.D.	
CHLOROFORM	N.D.	
1,1,1-TRICHLOROETHANE	N.D.	
CARBON TETRACHLORIDE	N.D.	
1,2-DICHLOROETHANE	N.D.	
BÉNZENE	N.D.	95.7% 90.4%
TRICHLOROETHENE	N.D.	
1,2-DICHLOROPROPANE	N.D.	
BROMODICHLOROMETHANE	N.D.	
2-CHLOROETHYLVINYLETHER	N.D.	
TRANS-1,3-DICHLOROPROPENE	N.D.	
TOLUENE	N.D.	93.4% 95.8%
CIS-1,3-DICHLOROPROPENE	N.D.	
1,1,2-TRICHLOROETHANE	N.D.	
TETRACHLOROETHENE	N.D.	
DIBROMOCHLOROMETHANE	N.D.	
CHLOROBENZENE	N.D.	91.0% 93.6%
ETHYLBENZENE	N.D.	
BROMOFORM	N.D.	
1,1,2,2-TETRACHLOROETHANE	N.D.	
1,3-DICHLOROBENZENE	N.D.	 -
1,4-DICHLOROBENZENE	N.D.	
1,2-DICHLOROBENZENE	N.D.	~~~
TOTAL XYLENES	N.D.	
ACETONE	N.D.	-
METHYL ETHYL KETONE	N.D.	
METHYL ISOBUTYL KETONE	N.D.	

ChromaLab, Inc.

David Duong Senior Chemist Eric Tam Lab Director

5 DAYS TURNAROUND

Analytical Laboratory (E694) November 22, 1991

ChromaLab File # 11911.35 C

Client: Aqua Science Engineers

Attn: Dave Prull

Date Sampled: Nov. 14, 1991

Date Analyzed: Nov. 21, 1991

Date Submitted: Nov. 14, 1991

Project Name: Oliver Rubber, 1200 65th St., Emeryville

Project Number: 2410 Sample 1.D.:

STKP5 (4 in 1 soil composite)

Method of Analysis:

8240

Detection Limit: 5.0 µg/kg

COMPOUND NAME	µg/kg	Spike Recovery
CHLOROMETHANE	N.D.	
VINYL CHLORIDE	N.D.	
BROMOMETHANE	N.D.	
CHLOROETHANE	N.D.	
TRICHLOROFLUOROMETHANE	N.D.	
1,1-DICHLOROETHENE	N.D.	92.3% 96.4%
MÉTHYLENE CHLORIDE	26	
1,2-DICHLOROETHENE (TOTAL)	N.D.	~
1,1-DICHLOROETHANE	N.D.	
CHLOROFORM	N.D.	
1,1,1-TRICHLOROETHANE	N.D.	
CARBON TETRACHLORIDE	N.D.	
1,2-DICHLOROETHANE	N.D.	
BENZENE	N.D.	95.7% 90.4%
TRICHLOROETHENE	N.D.	
1,2-DICHLOROPROPANE	N.D.	
BROMODICHLOROMETHANE	N.D.	
2-CHLOROETHYLVINYLETHER	N.D.	
TRANS-1,3-DICHLOROPROPENE	N.D.	
TOLUENE	N.D.	93.4% 95.8%
CIS-1,3-DICHLOROPROPENE	N.D.	
1,1,2-TRICHLOROETHANE	N.D.	 -
TETRACHLOROETHENE	N.D.	
DIBROMOCHLOROMETHANE	N.D.	
CHLOROBENZENE	N.D.	91.0% 93.6%
ETHYLBENZENE	N.D.	
BROMOFORM	N.D.	
1,1,2,2-TETRACHLOROETHANE	N.D.	
1,3-DICHLOROBENZENE	N.D.	
1,4-DICHLOROBENZENE	N.D.	- - - -
1,2-DICHLOROBENZENE	N.D.	
TOTAL XYLENES	N.D.	
ACETONE	N.D.	
METHYL ETHYL KETONE	N.D.	
METHYL ISOBUTYL KETONE (CONTINUED ON NEXT PAGE)	N.D.	

5 DAYS TURNAROUND

Analytical Laboratory (E694)

page 2

November 22, 1991

ChromaLab File # 1191135 C

Project Name: Oliver Rubber, 1200 65th St., Emeryville

Project Number: 2410

Sample I.D.: STKP5 (4 in 1 soil composite)

Method of Analysis: 8240 Detection Limit: 10 µg/kg

ADDITIONAL

COMPOUND NAME	µg/kg	
n-HEXANE	N.D.	
n-HEPTANE	N.D.	
METHYLCYCLOPENTANE	80	
CYCLOHEXANE	. 150	
METHYL CYCLOHEXANE	1400	
DIMETHYL CYCLOPENTANE	270	
TRIMETHYL CYCLOPENTANES	510	

ChromaLab, Inc.

David Duong

Chief Chemist

Eric Tam

Lab Director

) ase	בוותר:	ccion	- 0
=		duud	SLICIII	
	-			
A	_ 	OMMI	nøørt	' neer
	<i>"A" - </i>			e e e e e e

Company- 195E

Aqua Science Engineers, Inc. PO Box 535, San Ramon CA 94583

Chain of Custody

• (415) 820-9391 SAMPLERS (SIGNAFURE) (PHONE NO.) PROJECT NAME OUVER (50)685-6700 ADDRESS 1200 PURCABLE HALOCARBONS (EPA 601/8010) PURGABLE AROMATICS (EPA 602/8020) CHROMALAB FILE # 1191135 **ANALYSIS REQUEST** (EPA 3510/8015) ORDER # 4174 NO. OF SAMPLE ID. DATE TIME MATRIX SAMPLES 11/14/31 15:15 STANDARD 2. RELINQUISHED BY: 2. RECEIVED BY LABORATORY: 1. RECEIVED BY: RELINOUISHED BY: (signature) (signature) (signature) GERALD SASSE Y14/91 GeRALD SASSE 1/14/91 (printed name) Company- ASF Company- CHRO MALAB, INC. Company- ASE

5 DAYS TURNAROUND

Analytical Laboratory (E694)

December 6, 1991

ChromaLab File No.: 1191154

AQUA SCIENCE ENGINEERS, INC.

Attn: David Prull

RE: Three water samples for STLC Lead analysis

Project Name: OLIVER RUBBER

Project Location: 1200 65th St., Emeryville

Project Number: 2410

Date Sampled: Nov. 15, 1991

Date Submitted: Nov. 15, 1991

Date Extracted: Dec. 3, 1991

Date Analyzed: Dec. 5, 1991

RESULTS:

Sample I.D.	STLC Lead (mg/L)					
STKP 2	0.32					
STKP 3	10.4					
STKP 5	0.74					
BLANK	N.D.					
SPIKED RECOVERY	97%					
DUPLICATE SPIKED RECOVERY	81%					
DETECTION LIMIT	0.05					

ChromaLab, Inc.

Retail p. Marien

METHOD OF ANALYSIS

Refaat A. Mankarious Inorganics Supervisor Eric Tam

Laboratory Director

7420

RECEIVED

DEC 1 4 1991

AQUA SCIENCE ENG.

5 DAYS TURNAROUND

Analytical Laboratory (E694)

November 22, 1991

ChromaLab File No.: 1191154

AQUA SCIENCE ENGINEERS, INC.

Attn: David Prull

RE: One water sample for Gasoline analysis and Diesel analysis

Project Name: OLIVER RUBBER

Project Number: 2410

Date Sampled: Nov. 15, 1991
Date Extracted: Nov. 20, 1991
Date Analyzed: Nov. 20, 1991

RESULTS:

Gasoline (µg/l) Diesel (µg/l)

GW-2

1600*

N.D.

N.D.

50

92.6%

3510/8015

BLANK N.D. SPIKE RECOVERY 98.0% DETECTION LIMIT 50 METHOD OF ANALYSIS 5030/8015

* Hydrocarbons found in Gasoline range and quantified as Gasoline.

ChromaLab, Inc.

David Duong

Chief Chemist

Erstam (by 20)

Eric Tam

Laboratory Director

5 DAYS TURNAROUND

Analytical Laboratory (E694) November 25, 1991

ChromaLab File # 1191154 D

Client: Aqua Science Engineers Date Sampled: Nov. 15, 1991 Attn: Dave Prull

Date Submitted: Nov. 15, 1991

Date Analyzed: Nov. 22, 1991

Project Name: Oliver Rubber, 1200 65th St., Emeryville

Project Number: 2410 Sample I.D.: GW-2

Method of Analysis: (624

Detection Limit: 2.0 µg/1

COMPOUND NAME	ug/l	Spike Recovery
CHLOROMETHANE	N.D.	7-2
VINYL CHLORIDE	N.D.	
BROMOMETHANE	N.D.	
CHLOROETHANE	N.D.	
TRICHLOROFLUOROMETHANE	N.D.	
1,1-DICHLOROETHENE	N.D.	90.5% 93.7%
METHYLENE CHLORIDE	N.D.	
1,2-DICHLOROETHENE (TOTAL)	N.D.	
1,1-DICHLOROETHANE	N.D.	
CHLOROFORM	N.D.	
1,1,1-TRICHLOROETHANE	N.D.	
CARBON TETRACHLORIDE	N.D.	
1,2-DICHLOROETHANE	N.D.	
BENZENE	N.D.	90.1% 88.6%
TRICHLOROETHENE	N.D.	~
1,2-DICHLOROPROPANE	N.D.	
BROMOD I CHLOROMETHANE	N.D.	
2-CHLOROETHYLVINYLETHER	N.D.	
TRANS-1,3-DICHLOROPROPENE	N.D.	er en eu
TOLUENE	N.D.	91.2% 93.3%
CIS-1,3-DICHLOROPROPENE	N.D.	
1,1,2-TRICHLOROETHANE	N.D.	
TETRACHLOROETHENE	N.D.	
DIBROMOCHLOROMETHANE	N.D.	
CHLOROBENZENE	N.D.	90.8% 91.5%
ETHYLBENZENE	N.D.	-
BROMOFORM	N.D.	
1,1,2,2-TETRACHLOROETHANE	N.D.	* - -
1,3-DICHLOROBENZENE	N.D.	~
1,4-DICHLOROBENZENE	N.D.	
1,2-DICHLOROBENZENE	N.D.	
TOTAL XYLENES	N.D.	~~~
ACETONE	N.D.	
METHYL ETHYL KETONE	N.D.	
METHYL ISOBUTYL KETONE	N.D.	
(CONTINUED ON NEXT PAGE)		

Analytical Laboratory (E694)

5 DAYS TURNAROUND

page 2

ChromaLab File # 1191154 D

Project Name: Oliver Rubber, 1200 65th St., Emeryville

2410 Project Number: Sample I.D.: GW-2

Method of Analysis: 624 Detection Limit: 2.0 µg/1

TENTATIVELY

IDENTIFIED COMPOUNDS CONCENTRATION (µg/1)

190 1-METHYL-2-PROPYL-CYCLOPENTANE 100+ 1.2-DIMETHYL-CYCLOPENTANE 50.

METHYL-CYCLOPENTANE

ChromaLab, Inc.

David Duong

Senior Chemist

Eric Tam Lab Director

aqua science PO Box 535, San Po Engineers inc. (415) 820-9391

Aqua Science Engineers, Inc. PO Box 535, San Ramon CA 94583

Chain of Custody

DATE 11/15/51 PAGE ____OF__/ RUBBER NO. 2410 PROJECT NAME OLIVER (PHONE NO.) Doel (50) 685-6700 SAMPLERS (SIGNATURE) ADDRESS ZEOO PURGABLE HALOCARBONS (EPA 601/8010) PURGABLE AROMATICS (EPA 602/8020) VOLATILE ORGANICS PCB (EPA 608/8080) ANALYSIS REQUEST (EPA 3510/8015) OIL & GREASE (EPA 5520 E&F BASE/NUETRALS, (EPA 625/8270) TCLP NO. OF SAMPLE ID. DATE TIME MATRIX SAMPLES 5 12:00 5 12:00 5 11/15/51 10:00 W GW-Z CHROMALAS FILE # 1191154 ORDER # 4/96 2. RECEIVED BY LABORATORY: 2. RELINQUISHED BY: 1. RECEIVED BY: 1. RELINQUISHED BY 16.05 (time) (signature) (time) (signature) (time) (signature) DAUID PEUL 1/15/91 (date) (printed name) (date) (printed name) (printed name) Company-CHROMALAB, INC. Company. 195E Company-Company-

5 DAYS TURNAROUND

Analytical Laboratory (E694)

December 23, 1991

ChromaLab File No.: 1291148

AQUA SCIENCE ENGINEERS

Two soil samples for total and WET Lead analysis RE:

Project Name: OLIVER RUBBER

Project Number: 2410

Date Sampled: Dec. 18, 1991 Date Submitted: Dec. 18, 1991 Date Analyzed: Dec. 23, 1991 Date Extracted: Dec. 18, 1991

RESULTS:

Sample I.D.	Lead (mg/Kg	g) WET Lead (mg/L)
STKP 3	30	1.5
STKP 5	45	1.2

BLANK	N.D.	N.D.
SPIKE RECOVERY	65%	100%
DUPLICATE SPIKE RECOVERY	67%	95%
DETECTION LIMIT	2.5	0.05
METHOD OF ANALYSIS	7420	7420

ChromaLab, Inc.

Refaat A. Mankarious Inorganics Supervisor

Eric Tam

Laboratory Director

RECEIVED

JAN - 2 1992

AQUA SCIENCE ENG

	 <u> </u>	acua	scien	ice
Ī.	i e	ngi	neer:	s inc.

Aqua Science Engineers, Inc. PO Box 535, San Ramon CA 94583

Chain of Custody

DATE 12/18/51 PAGE / OF / 820-9391 (415)RUBBER NO. 2410 (PHONE NO.) PROJECT NAME OLIVER SAMPLERS (SIGNATURE) AC/M/(50)685-6700 ADDRESS 1200 65 71 (EPA 1311/1310) **ANALYSIS REQUEST** EPA 3510/8015) BASE/NUETRALS, (EPA 625/8270) (EPA 624/8240) NO. OF SAMPLE ID. DATE TIME MATRIX SAMPLES 12:00 CHROMALAB FILE # 1291148 ORDER # 4547 2. RECEIVED BY LABORATORY: 1. RECEIVED BY: 2. RELINQUISHED BY: 1. RELINQUISHED BY: Main Cappelle (signature) 16:50 (signature) (time) (signature) (time) (signature) PAULO PRULL (date) (printed name) (printed name) (printed name) (date) (printed name) Company-Company-ASE Company- ASE

Company- ASE DUE MM 12/23

5 DAYS TURNAROUND

Analytical Laboratory (E694)

December 27, 1991

ChromaLab File No.: 1291219

AQUA SCIENCE ENGINEERS, INC.

RE: One soil sample for Title 22 CAM Metals (17) analysis

Project Name: OLIVER RUBBER

Project Number: 2410

Date Sampled: Dec. 26, 1991 Date Submitted: Dec. 26, 1991

Date Analyzed: Dec. 27, 1991

RESULTS: Sample I.D.: STK1

Metals	Concentration (mg/Kg)	Detection Limit (mg/Kg)	Regulatory Levels (mg/Kg)
		•	
Antimony (Sb)	N.D.	1.00	500
Arsenic (As)	2.1	0.25	500
Barium (Ba)	111	0.25	10000
Beryllium (Be)	N.D.	0.05	75
Cadmium (Cd)	1.7	0.05	100
Cobalt (Co)	9.6	0.50	8000
Chromium (Cr)	14	0.50	2500
Copper (Cu)	12	0.05	2500
Mercury (Hg)	0.1	0.05	20
Lead (Pb)	80	0.50	1000
Molybdenum (Mo)	N.D.	0.25	3500
Nickel (Ni)	30	0.50	2000
Selenium (Se)	N.D.	0.50	100
Silver (Ag)	N.D.	0.25	500
Thallium (T1)	N.D.	2.00	700
Vanadium (V)	19	0.50	2400
Zinc (Zn)	24	0.25	5000

Method of Analysis: 3050/6010/7000

ChromaLab, Inc.

Retard A. Montrom

Refaat A. Mankarious Inorganics Supervisor Eric Tam

Laboratory Director

5 DAYS TURNAROUND

Analytical Laboratory (E694)

December 27, 1991

ChromaLab File No.: 1291219

AQUA SCIENCE ENGINEERS, INC.

RE: One soil sample for Title 22 CAM Metals (17) analysis

Project Name: OLIVER RUBBER

Project Number: 2410

Date Sampled: Dec. 26, 1991 Date Submitted: Dec. 26, 1991

Date Analyzed: Dec. 27, 1991

RESULTS: Sample I.D.: STK2

Metals	Concentration (mg/Kg)	Detection Limit (mg/Kg)	Regulatory Levels (mg/Kg)
Antimony (Sb)	N.D.	1.00	500
Arsenic (As)	N.D.	0.25	500
Barium (Ba)	106	0.25	10000
Beryllium (Be)	N.D.	0.05	75
Cadmium (Cd)	2.1	0.05	100
Cobalt (Co)	8.0	0.50	8000
Chromium (Cr)	18.0	0.50	2500
Copper (Cu)	14.0	0.25	2500
Lead (Pb)	6.0	0.50	1000
Mercury (Hg)	1.0	0.05	20
Molybdenum (Mo)	N.D.	0.25	3500
Nickel (Ni)	25.0	0.50	2000
Selenium (Se)	10.0	0.50	100
Silver (Ag)	N.D.	0.25	500
Thallium (T1)	22.0	2.00	700
Vanadium (V)	21.0	0.50	2400
Zinc. (Z_n)	38.0	0.25	5000

Method of Analysis: 3050/6010/7000

ChromaLab, Inc.

Relat P. Mayon

Refaat A. Mankarious Inorganics Supervisor Eric Tam

Laboratory Director

RECEIVED

JAN - 6 1992

AQUA SCIENCE ENG.

•		
	scienc	_
cuyu	icci >	1114.

Aqua Science Engineers, Inc. PO Box 535, San Ramon CA 94583 (415) 820-9391

Chain of Custody

DATE DEC 26 91 PAGE 1 OF 1

														÷							
SAMPLERS (S			/	(Pi	IONE	NO.)	PROJ	ECT N	IAME	0	HUER	ر اكدر	BBET	_	NO. 2410						
Traig	. 9	Les	<i></i>	510 68	<u>೯</u> -೯	,0	ADD	RESS	12	60	651	µ গ্ৰ	60	wan	D .						
AŇA	LYS	IS R	EQU	EST		30)		ĽΔ	380		ACIDS	BCF)				(13) 7000)					
SPECIAL INST					_	17KX	_	E	AR.	83	Ŋ.	정	ĺ		~ ~	T. +	17)	_			
24 46	אעך ג	ud an	Dec vio		(国)	B /B	015	20)	10,01	(40)	3 (o	E 33	6	40)	000	E G	000.	310	18T	, <u>}</u> +	
24 HR TURN AROUND PLEASE				SOLLT 030/8	SOLIY 030/8	ESEL. 510/8	LE AE 02/80	LE HE 01/80	1.B OF 24/82	USTRA 25/82	GREAS 520 E	08/80	04/80	ETALS 010+7	TY PC 010	22 (c 010+7	311/1	311/1	VITY IVITY BILIT		
SAMPLE ID.	DATE	TIMB	MATRIX	NO. OF SAMPLES	TPH-CASOLINE (EPA 5030/8015)	TPH-GASCULINE/BIEX (EPA 5030/8015-8020)	TPH- DIESEL (EPA 3510/8015)	PURGABLE AROMATICS (EPA 602/8020)	PURGHBLE HALOCARBONS (EPA 601/8010)	VOLATILE ORGANICS (EPA 624/8240)	BASE/NUSTRALS, (EPA 625/8270)	OIL & CREASE (EPA 5520 E&F	PCB (EPA 608/8080)	PHENOLS (EPA 604/8040)	luft metals (5) (epa 6010+7000)	PRIORITY POLLUT. (EPA 6010 ICP +	ППВ 22 (САМ 17) (EPA 6010+7000)	TCLP (EPA 1311/1310)	STIC- CAM MET (EPA 1311/1310)	REACTI VI TY CORROSI VI TY I ŒU TABI LI TY	
STK 1		1: 30	5	7			-		()			•					×			707	
STK 2	1726	1.30	5	/													×				
																					
															CHRC	MAL	AB F	ILE	# 12	29121	9 7
															C	ואטצו	₹#	46	28	•	
			 				,							{							٦
																					
·····																					
1201 1																					
·····														, 							
1. RELINQUIS		Y;	1	. RECEIVE	D BY:			2	RELI	QUISI	IED B	Y:	_	2. R	ECEIV	ED BY	LAB	ORATO	ORY:		
Craix)	Heil	7	2:30				/								2	2				18:31	
(signature)	D	7	(time)	(signature)/		(tir	ne)	(signa	ine)			(time)		ignatur				(time)		
Craja	4	之 17	1/26			\times								Yil	n Ke	un	, la	m	12	-26-9	1
(printed)nan			(date)	(printed p	ame)		(da	te)	(printe	d name	3)		(date)		rinted				(date)		
Company-	ASI	E		Company	y -				Comp	any-				C	ompai	ny- C	UHR	o Me	rLAS	3	

5 DAYS TURNAROUND

Analytical Laboratory (E694)

December 5, 1991

ChromaLab File No.: 1191022

AQUA SCIENCE ENGINEERS, INC.

Attn: David Prull

RE: Four composited soil samples for Reactivity, Corrosivity, and Ignitability

Project Name: OLIVER RUBBER

Project Number: 2410

Date Sampled: Nov. 4, 1991

Date Analyzed: Dec. 5, 1991

Date Submitted: Nov. 4, 1991

RESULTS:

Sample I.D.	 Reactivity	Corrosivity	Ignitability
STKP 1 (A-D)	No	pH 7.5	No
STKP 2 (A-D)	No	pH 7.4	No
STKP 3 (A-D)	No	pH 7.7	No
STKP 4 (A-D)	No	pH 8.1	No

BLANK METHOD OF ANALYSIS

No SEC.66705 pH 7.0 SEC.66708 No SEC.66702

ChromaLab, Inc.

David Duong Chief Chemist Erretam (by DD)

Eric Tam
Laboratory Director

5 DAYS TURNAROUND

Analytical Laboratory (E694)

December 12, 1991

ChromaLab File # 1191135 C

Client: Aqua Science Engineers

Attn:

Dave Prull

One soil composite sample for Reactivity, Corrosivity and

Ignitability analyses

Project Name: Oliver Rubber, 1200 65th St., Emeryville

Project Number: 2410

STKP5 (4 in 1 soil composite) Sample i.D.:

Date Submitted: Nov. 14,

Date Sampled: Nov. 14, 1991 Date Analyzed: Dec. 10, 1991

Results:

STKP 5 pH 7.6 No BLANK. No pH 7.0 METHOD OF ANALYSIS Sec.66075 Sec.66708 Sec.66702

ChromaLab, Inc.

David Duong

Chief Chemist

Laboratory Director

RECEIVED

DEC 3 0 1991

AQUA SCIENCE ENG.

APPENDIX B

Tank Removal Report July 16, 1992



July 16, 1992

PROJECT REPORT UNDERGROUND STORAGE TANK CLOSURE

at
Oliver Rubber Company
1200 65th Street, Emeryville, CA.

Prepared for:

The Oliver Rubber Co. 1200 65th Street, Oakland, CA.

Submitted by:

AQUA SCIENCE ENGINEERS, INC. 1041 Shary Circle CONCORD, CA

TABLE OF CONTENTS

1.0	INTRODUCTION				
2.0	PERMITS				
3.0	MOBILIZATION, EXCAVATION AND REMOVAL				
4.0	SAMPLING AND ANALYSIS				
5.0	BACKFILLING AND RESURFACING				
6.0	DISCUSSION AND CONCLUSIONS				
FIGURE 1 - SITE MAP					
APPENDIX A - PERMITS					
APPEN	IDIX B - HAZARDOUS WASTE MANIFEST and CERTIFICATE OF DISPOSAL				
APPEN	DIX C - LABORATORY ANALYSIS and CHAIN OF CUSTODY				
APPEN	DIX D - UNDERGROUND STORAGE TANK				

UNAUTHORIZED RELEASE FORM

1.0 INTRODUCTION

This report documents the removal and related activities of the underground storage tank closure performed for the Oliver Rubber Company located at 1200 65th Street in Emeryville, Calif. (FIGURE 1). A 1,000 gallon underground storage tank last containing "Bunker Oil" low grade fuel oil. The scope of services provided by Aqua Science Engineers, Inc. (ASE) is in accordance with ASE proposal No. 92-017 and included the following tasks:

- o Obtain permits from the Alameda County Health Care Services Agency, City of Emeryville Fire Department and City of Emeryville Building Department.
- o Notify Cal-OSHA and the Bay Area Air Quality Management District.
- o Remove and dispose of residual liquids from the tank.
- o Remove and dispose of the underground storage tank.
- o Sample native soil adjacent the tank.
- o Prepare a report of methods and findings.

2.0 PERMITS

The application for permits to remove the underground storage tank were obtained from the Alameda County Health Care Services Agency, Emeryville Fire Department and Emeryville Building Department. Notice of construction was given to the Bay Area Air Quality Management District and CAL-OSHA. Copies of the permits and notification documents are contained in Appendix A.

3.0 MOBILIZATION

ASE mobilized for on-site work on June 24, 1992, commencing with removal of concrete surface materials. Project personnel included: Craig Hertz- Project Engineer, Steve DeHope- Construction Manager, and Gerald Sasse-Technical Labor.

3.1 EXCAVATION

The services of the Underground Service Alert network were utilized to identify primary utilities in the work area.

Excavation of the storage tank was initiated on July 24, 1992. Soil was removed along the outside perimeter of the vault to a depth of approximately 9 feet below grade. All piping was removed from the immediate vicinity around the tank. No overspill protection devices were in place at the fill locations.

Cleaning of the tanks and removal of residual liquid waste from the tanks was commenced on July 24. Approximately 550 gallons of residual liquid and tank rinsate was removed by Waste Oil Recovery Systems and disposed of at the Demenno Kerdoon facility in Compton, CA. A copy of the Hazardous Waste Manifest is appended to this report.

Native material surrounding the tank consisted of a light brown clayey silt with some medium/fine sand and little medium/fine gravel to a depth of approximately 4 feet below grade. Light grey clayey silts with increasing content of fine sand was encountered in the elevations between 4 feet and 11 feet below grade. Groundwater was not encountered during the excavation. Although groundwater was previously determined, from a former tank removal project on this site, to be at approximately 9.5 feet below grade. Tank backfill material around the tank was classified as an imported 3/8" crushed gravel with fines.

Air quality sampling was conducted at the edge of the excavation using an organic vapor analyzer model 580A by TEI. Volatile organic vapors were not detected in the air near the edge of the excavation. Mild petroleum odors were noted periodically during soil removal operations.

All tank piping was observed intact with no obvious holes or weakness. No overspill protection devices were in place. All excavated materials were placed on 10 ml. plastic sheeting and covered.

3.2 REMOVAL

Prior to tank removal on the morning of July 24, 1992, ASE inerted the tanks by adding dry ice at the rate of at least 1.5 pounds per 100 gallons of tank volume. After verifying a safe LEL of the tank atmosphere, the tanks were removed from the excavation. The tank removal operations were witnessed by the City of Emeryville Fire Department and the Alameda Health Care Services Agency Inspector-Susan Hugo. The tank was transported by Dexanna, Inc. to the Erickson Tank Disposal Facility in Richmond, CA, on the date of removal. Copies of

the Hazardous Waste Manifests and Tank Disposal Certificates are contained in Appendix B.

The tank was constructed of a single ply 5/16" riveted plate steel. No protective coatings were evident on the tank exterior. The exterior of the tank was examined and corrosion, pitting, and holes were observed.

4.0 SAMPLING AND ANALYSIS

Soil samples were collected from the excavation 2 feet below each end of the tank (BE & BW: Figure 1). Soil samples were taken between 2:30 and 3:30 PM by Project Engineer, Craig Hertz of ASE trained in sampling protocol by a registered civil engineer. Soil sampling was performed at the direction of the Alameda County Health Services Department Inspector- Susan Hugo.

Overexcavation and resampling was performed on the following day (June 25, 1992). Soil samples were collected along the side walls within the tank excavation (SW-N, SW-S, SW-E, SW-W) at approximately 6-7 feet below grade. The sampling locations are shown on the site map in Figure 1 and the results are shown below in Table One.

Soil samples were collected by driving a 6-inch by 2-inch brass tube into the soil using a wooden mallet when necessary. The sample of stock piled soil (STKP 1-A) was taken as a composite of four subsamples. The four samples were composited as one sample at the labratory. All soil samples were secured using aluminum foil, teflon caps and sealed with duct tape. All samples were put on ice and transported to an analyzing labratory under Chain of Custody procedures. A copy of the Chain of Custody is appended to this report.

All samples were submitted for analysis to the state certified laboratory, Priority Environmental Labs in Milpitas, California (408) 946-9636. The samples taken within the excavation were analyzed for Total Petroleum Hydrocarbons as Diesel, BTEX and Oil & Grease. The results of the soil sampling within the excavation are tabulated as TABLE 1: Analytical Results of Soil Sampling. Copies of signed laboratory data sheets are found in Appendix C.

TABLE 1: SOIL SAMPLE ANALYTICAL RESULTS

Sample No.	TPH Diesel (ppm)	Oil & Grease (ppm)	Benzene (ppb)	Toluene (ppb)	Ethyl Benzene (ppb)	Total Xylenes (ppb)
		~				
BE	ND	ND	ND	ND	ND	ND
\mathbf{BW}	390	670	ND	ND	ND	ND
SW-W	130	450	19	6.7	ND	33
SW-E	ND	ND	ND	ND	ND	ND
SW-N	490	1500	42	48	5.9	100
SW-S	470	1300	8.6	19	27	130

* - Composited sample

ND - Non Detectable at analytical method limits

ppm - parts per million

ppb - parts per billion

On June 24 and June 25 approximately 36 cubic yards of soil were removed from the tank area. Excavation of soils was conducted to a depth of approximately 7.0 feet below grade.

The stockpiled soil was sampled and analyzed for Total Recoverable Hydrocarbons (EPA 418.1), BTEX (EPA 1311/602), Reactivity (Title 22), Corosivity (Title 22), Ignitability (Title 22), Semi Volatile Organics (EPA 8270). The results indicated 1200 ppm of Total Petroleum Hydrocarbons, a pH of 7.6 for Corrosivity, and Method 8270 revealed 380 ppb of 2-Methylnaphthalene.

5.0 BACKFILLING AND RESURFACING

The excavation was not backfilled and was covered with 1" trenchplate.


All soil removed from the tank excavation were disposed of at a Class III Landfill. The acceptance certificate from BFI Waste Systems is located in Appendix B. Aggregate Systems Transport, a licensed hazardous waste hauler, transported the soil to the landfill under a non-hazardous waste manifest.

6.0 DISCUSSION AND CONCLUSIONS

One underground storage tank and related plumbing were removed from the site of the Oliver Rubber Co. in Emeryville, CA. The size of the tanks was noted at 1,000 gallons, constructed of a single layer steel plate and last contained diesel oil. Subsequent to tank removal, inspection of the tank revealed signs of corrosion, holes and pitting.

Analytical testing of soil samples in the tank excavation revealed detectable concentrations of diesel, Oil & Grease, Benzene, Toulene, Ethyl-Benzene and Xylenes. All soil removed from the excavation and subsequent over-excavated (approx. 36 cubic yards) were profiled for disposal and disposed of at a Class III Landfill. An underground storage tank unauthorized release form was prepared by Aqua Science Engineers and filed with the Alameda County Health Care Services Department. A copy of this form is in Appendix D.

The tank excavation was not backfilled, but covered with a 1" trenchplate.



APPENDIX A PERMITS

APPLICATION FOR PERMIT TO OPERATE, MAINT	AIN OR STORE	
Make check payable to: CITY OF EMERYVIL	TE	F.P.B. Permit No. 1/57
Mail to: Emeryville Fire De		Due Date:/
596-3750 Fire Prevention But 6303 Hollis Street		
PHONE: 🎖މާމާރާރާރާރާރާރާރާރާރާރާރާރާރާރާރާރާރާރ	1608	Renewal
XXXXXXX	Specify use if	
To: Manage Remove UG tank	Public Assembly	Date: 04/21/92
	1988 edition	Fee: \$35.00(initial)
Application made by: ARUA SCIENCE Enginee	£1.	Cash Ck. No. <u>/4723</u>
Location: 1200 65th st.		Receipt No.
- Oakland La 94662		Received by:
Signed brang Heat Phone # 685-	1700	
DO NOT WRITE BELOW THIS LINE	`	
		•
	CivicBank of Commerce	04.470
aqua science	1814 Franklin Street Oakland, CA 94612	01472
La Ela engineers inc.	90-4095	NO.
, 1041 SHARY CIRCLE CONCORD, CA 94518	1211	14723
		14/23
****FIFTY DOLLARS AND 00/100****		
	DATE	AMOUNT
	4-20-92	\$50.00
AY CITY OF EMERYVILLE	VOID #F N	OT CASHED WITHIN 3 MONTHS
PRDER		
· ·	Q	<u> </u>
	Level	La Sarre
	- John d	
#O14?23# #121140959#	1050310000	
	1050519769#	
is realisproofing required is it sensitionly		
DATE OF INSPECTION:		
REMARKS: \$35.00 filing fee; on-site inspec	tion fee of \$50.00	n/hour (1st hour
no charge): applicant to secure permits	•	
Dept., Public Works (right-of-way encroach	Arvom Alameda County	CITY BUILDING
=CVH 1117) 3/851 00		/
Signed 4	ELTGL LEVEN FIRE INSPECTOR	No
	17	

Permit Application and Job Notification Form

Construction Bomolition Tranches Exceptions Buildings Structures Falsowerk Scattolding

Bistrict (Name) Date No
supply and that the Division review, information necessary to evaluate the safety of the worksite subject to permit requirements. A permit will not be issued until evidence has been demonstrated that the place of employment will be safe and healthful
Preject Safety Contact: STEVE DEHOPE Employer's Representative. 17 17 Title & Phone No: Construction Supervisor Employer's State Contractor's License No.: 487000
General Contractor Option Initial this blank if applicant elects to assume responsibility for obtaining a single permit to cover one multi-employer project, e.g., a high-rise construction project. The duties of employers at the site to obey safety and health laws are not changed by this election. A list of employers on site will be attached by the Division to this application and the list will be updated as necessary
Multiple Project. (If projects to be covered are similar in all important spects work is performed by the same employer, and informtion concerning ach project covered is provided.)
4) The applicant understands that, under the permit program DOSH schedules routine inspections by authorized personnel for the purpose of verifying that holders of permits are meeting their obligation to provide a safe work place for their employees. The Division reserves the right to revoke a permit if it is unable to promptly verify compliance with the terms and conditions of the permit and its issuance. 5) The applicant understands that failure to comply with any of the above listed conditions for obtaining a permit could result in denial, suspension or revocation of the permit. Employers may appeal these actions to the Director of the Department of industrial Relations (California Labor Code, Section 6500 et. seq., and 8 California Administrative Code, Section 341). Is the applicant conducting any activities to be covered by this permit application in partnership or joint venture with any other persons or corporations conducting activities requiring permits? Yes

Permit Application and Job Notification Form (Continued)

				
Specific jobsite location1259 65	5th Street	Field phone 51	10-409-3536	
Emeryville, CA 94608		Office phone 51	10-685-6700	
Nearest major cross street Hollis S	Street	No of employees	3	
City Emeryville		Starting date6-	-24-92	
County Atamena		Anticipated compl		2
Name and title of jobsite supervisor	Steve DeHope	•	es in Proximity N	VoYes
INSTRUCTIONS: THE APPROPRIATE ITEM(s) must be in or check off blanks where appro	TYPE Of the completed and signed by a person opriate		e project, for each jobsite to be c	overed by a permit Please fill
Construction of: Building Tilt-up Wood frame Description	Liftslab F	Precast S		
Job description Wood over 60 ft. (re	equire design by California Reg	•	plans at site) [CSU 1643, 16	[44(c)(7)]
Falsework/Vertical Shoring M Job description	Maximum Height	•		iterial
Tower Crane Erection/Dismantlin Maximum Radius Capac Foundation and/or support(s) for crane on th Will crane be stepped or jumped as construc Name of crane certifier	city Make and his site designed/constructed in the cition proceeds (see CSO Section	by (see Section 1584(a) n 1584 1)Yo	i), CSO)	
	سنورز والمساواة			·····
Demolition of: Building State Steel frame Wood fram Loader/tractors Other CSO Article 31 - Demolition	me Concrete	Demolitio	on Ball Clam	No of Stories Explosives
Excavations/Trenches Depth Ground Protection Method: ShoringProject description:	Sloping	Tren val	nin./max.) 81	Total Length 10* Alternate
Division time Only	I hereby certify that, to the beat L/the applicant have knowledg		eve information and assartions a th the foregoing.	ire true and correct and that
fee				
Paid	Signatura:			
Approved	Thie Project Engi			· · · · · · · · · · · · · · · · · · ·
Conference	Date: 6-16-92			
I Other 3				

Bay Area Air Quality Management District acknowledges receipt of your Tank Removal/Contaminated Soil Excavation Notification Form received on 6/17/92 Pg.	NOTIFICATION FORM
) ,	ZIP 9460B
OWNER NAME Oliver Rubber Company	
SPECIFIC LOCATION OF PROJECT Side WALK!	ATA
TANK REMOVAL	CONTAMINATED SOIL EXCAVATION
SCHEDULED STARTUP DATE 6-24-92	SCHEDULED STARTUP DATE
VAPORS REMOVED BY:	STOCKPILES WILL BE COVERED? YES NO
[] WATER WASH	ALTERNATIVE METHOD OF AERATION (DESCRIBE BELOW):
(co ²)	
[] VENTILATION	(MAY REQUIRE PERMIT)
NAME AQUA SCIENCE Eng. ADDRESS 1041 Shary Circle CITY, STATE, ZIP CONCORD CA- 194518	CONTACT Steve De HopePHONE (510) 685-6700
	TANT INFORMATION (IF APPLICABLE)
NAME	CONTACT
ADDRESS	
CITY, STATE, ZIP	
FOR OFFICE USE ONLY	
DATE RECEIVED FAX 6/17/92	sy play
DATE POSTMARKED	(init.)
CC: INSPECTOR NO. 524	DATE 6/17/92 BY BG
UPDATE: CONTACT NAME	DATE
BAAQMD N #	DATA ENTRY 6/17/92 (init.)

ALAMEDA COUNTY HEALTH CARE SERVICES AGENCY HAZARDOUS MATERIALS DIVISION

DEPARTMENT OF ENVIRONMENTAL HEALTH 470 - 27th Straet, Third Floor Telephone: (415) 874-7237 Oakland, CA 94612 ACCEPTED

THERE IS A FINANCIAL PENALTY FOR NOT

OBTAINING THESE INSPECTIONS.

Underground tank closure plan Complete according to attached instructions

1.	Business Name OLIVER RUBBER CO.
	Business Owner STANDARD PRODUCTS CO.
2.	site Address 1259 65th STREET
	city EMERYVILLE zip 94608 Phone 654-7711
3.	Mailing Address P.O. Box 8447
	city <u>OAKLAND</u> , <u>CA</u> zip <u>94608</u> Phone 654-7711
4.	Land Owner OLIVER RUBBER Co.
	Address 1200 65 th ST city, State EMERYVILE, (A zip 54608
5.	Generator name under which tank will be manifested
	OLIVER RUBBER CO.
	EPA I.D. No. under which tank will be manifested <u>CAC000679616</u>

Ĝ.	contractor AQUA SCIENCE ENGINEERS
	Address 1041 SHARY CIRCLE
	city <u>CONCORD</u> , <u>CA</u> Phone (510) 685-6700
	License Type <u>ENG. A</u> ID# <u>487000</u>
7.	Consultant AQUA SCIENCE ENGINEERS
	Address 1041 SHARY CIRCLE
	city <u>Concord</u> , (A Phone <u>(510) 685 - 6700</u>
8.	Contact Person for Investigation
	Name DAVID PRULL TITLE PROJECT MANAGER
	Phone (510) 685-6700
9.	Number of tanks being closed under this plan
	Length of piping being removed under this plan Oft.
	Total number of tanks at facility
10.	State Registered Hazardous Waste Transporters/Facilities (see instructions).
	** Underground tanks are hazardous waste and must be handled ** as hazardous waste
	a) Product/Residual Sludge/Rinsate Transporter
	Name WASTE OIL RECO. EPA I.D. No. CADOO626515
	Name WASTE OIL RECO. EPA I.D. No. CADOO626515 Totts - 843 Hauler License No. CAL-TOC-106359 License Exp. Date 4/57
	Address 6401 LEONA STREET
	City OAKLAND State CA Zip 94605
	b) Product/Residual Sludge/Rinsate Disposal Site
	Name DEMENNO KERDOON EPA I.D. No. CATOBOO13350
	Address Z COO N. ALAMEDA
	city Compton State CA zip GOZZI
	^

c) Tank and Piping Transporter	
Name ERICKSON, INC. EPA I.D. No. CADOO946639	2
Hauler License No. 00/9 License Exp. Date 5-97	
Address Z55 PARR BOULEVARD	
AddressZ55 PARR BOULEVARD City RICHMOND State CA zip 94801	
d) Tank and Piping Disposal Site	
Name <u>ERICKSON</u> , INC. EPA I.D. No. <u>CAD 0094663</u>	3
Address Z55 PARR BOULE VARD	
city <u>figurest</u> State <u>A</u> Zip <u>94801</u>	
11. Experienced Sample Collector	
Name DAVID C. PRULL	
Company AQUA SCIENCE ENGINEERS	
Address 1041 SHARY CIRCLE	
City (ONCORD State 9 zip 94518 Phone (510) 685-6	70
12. Laboratory	
Name CHROMALAB, INC.	
Address 2239 OMEGA RD. #1	
city SAN RAMON State CA zip 94583	
State Certification No	
13. Have tanks or pipes leaked in the past? Yes [] No []	
If yes, describe	
· 	

14. Describe methods to be used for rendering tank inert

DRY	ICE	AT A	PATE	OF 1.5	POUNDS
•			-		VocumE
45	A C	minim vi	77		

Before tanks are pumped out and inerted, all associated piping must be flushed out into the tanks. All accessible associated piping must then be removed. Inaccessible piping must be plugged.

The Bay Area Air Quality Management District (771-6000), along with local Fire and Building Departments, must also be contacted for tank removal permits. Fire departments typically require the use of explosion proof combustible gas meters to verify tank inertness. It is the contractor's responsibility to bring a working combustible gas meter on site to verify tank inertness.

15. Tank History and Sampling Information

Ta	nk	Material to	
Capacity	Use History (see instructions)	be sampled (tank contents, soil, ground-water, etc.)	Location and Depth of Samples
500 gm.	INSTALLATION DATE UNKNOWN LAST USE DATE UNKNOWN TANK CURRENTLY CONTAINS LOW GRADE "BUNKER OIL"	SOIL G GROUNDWATER INTERFACE OR Z' BELOW TANK INVERT GROUNDWATER IF ENCOUNTERED	SOIL () SAMPLE MIDDLE OF TANK APPROX. G.O ST. BELOW GRADE O WATER SAMPLE IF FROUNDWITTER ENCLUNTERED

One soil sample must be collected for every 20 feet of piping that is removed. A ground water sample must be collected should any ground water be present in the excavation.

	Excavated/Stockpiled Soil
Stockpiled-Soil Volume (Estimated)	Sampling Plan / SAMPLE, COLLATED FROM 4 5UB- SAMPLES SELECTED PANDOMLY,
10 gd.	ANALYZE FOR TANK CONTENT Stockfilled Sail musi be Charactere & depending of disposal method.


Stockpiled soil must be placed on bermed plastic and must be completely covered by plastic sheeting.

16. Chemical methods and associated detection limits to be used for analyzing samples

The Tri-Regional Board recommended minimum verification analyses and practical quantitation reporting limits should be followed. See attached Table 2.

Contaminant Sought	EPA, DHS, or Other Sample Preparation Method Number	EPA, DHS, or Other Analysis Method Number	Method Detection Limit
BUNKER OIL FUEL OIL)	EPA 6C-FID (3550)	3550	1. ppm
	5170 - 5570 METHED 5570 E & F - 3570	577NDARD 5520 METHOD EST G(FID ————————————————————————————————————	50 ppm (- 1.0 pgm (- ,065 pgm)

17. Submit Site Health and Safety Plan (See Instructions)



HEALTH & SAFETY PLAN

for the

OLIVER RUBBER JOBSITE 1259 65th STREET EMERYVILLE, CA

prepared by

Aqua Science Engineers, Inc. 1041 Shary Circle Concord, CA 94518 1 (800) 678-9391

AQUA SCIENCE ENGINEERS, INC. HEALTH & SAFETY PLAN for the OLIVER RUBBER JOBSITE

A. GENERAL DESCRIPTION

Site: 1259 65TH STREET, EMERYVILLE CALIFORNIA

Work Scope: 1. PRO

- 1. PROVIDE EXCAVATION SERVICES FOR TANK REMOVAL.
- 2. PROVIDE EXTRICATION OF ONE 500 GALLON UNDERGROUND STORAGE TANKS.
- 3. SAMPLE SOIL AND WATER UPON SUCCESSFUL COMPLETION OF TANK REMOVAL. EXECUTE BACKFILLING OPERATIONS.
- 4. RESURFACE EXCAVATION AREA AND RESTORE TO PREVIOUS USABLE CONDITION.

NOTE: UST CURRENTLY CONTAINS "BUNKER OIL," LOW GRADE FUEL OIL.

SAFETY POLICY:

This Health and Safety Plan is written specifically for the Oliver Rubber jobsite, located at 1259 65th Street, Emeryville California. This plan does <u>not</u> include specific procedures for tank removal and/or soil offhaul, but addresses hazards associated with these and related activities. All persons on site will follow OSHA safe operating practices as outlined in 29 CFR 1910 and 1926, as well as established guidelines from their respective companies or organizations.

Plan Prepared by: David Prull Date: 3/23/92

Plan Approved by: David Prull Date: 3/23/92

Proposed Start Date: April 7, 1992

Overall Hazard Level: Serious: Low:

Moderate: XX Unknown:

Project Organization:

Site Manager for A.S.E.: Steve DeHope

A.S.E. Safety Officer: David Prull Other A.S.E Personnel: Craig Hertz

B. SITE/WASTE CHARACTERISTICS

Waste Type(s): Solid: XX

Solid: XX Sludge: Liquid: XX Gas:

Characteristics: PETROLEUM FUEL RESIDUALS, FLAMMABLE, TOXIC

Site Parameter: THE EXCAVATION PIT AS WELL AS ANY STOCKPILED

MATERIAL ARE IDENTIFIED AS EXCLUSION ZONES. A MINIMUM BOUNDARY OF THREE FEET SURROUNDING.

BOTH IS TO BE MAINTAINED IN AS MUCH AS IS

POSSIBLE. AT NO TIME SHALL ANY PERSONNEL ENTER THE EXCAVATION WITHOUT A SAFETY WATCH PERSON

STANDING BY OBSERVING THE ENTRY PERSON'S

ACTIVITY.

C. HAZARD EVALUATION

CHEMICAL HAZARDS

Potential chemical hazards include skin and eye contact or inhalation exposure to potentially toxic concentrations of hydrocarbon vapors. The potential toxic compounds that may exist at the site are listed below, with descriptions of specific health effects of each. The list includes the primary potential toxic constituents that may be found in gasoline, and the ingredients that are found in the petroleum solvent residue of the second tank. (excerpted from NIOSH Pocket Guide to Chemical Hazards, June 1990).

GASOLINE TANK

1. BENZENE

- a. Colorless, clear, highly flammable liquid (class 1B) with characteristic odor.
- b. High exposure levels may cause acute restlessness, convulsions, depression, respiratory failure. BENZENE IS A SUSPECTED CARCINOGEN.
- c. Permissible exposure level (PEL) for a time weighted average (TWA) over an eight hour period is 1.0 ppm.

2. TOLUENE

- a. Colorless, flammable liquid (class 1B) with a sweet benzene-like odor.
- b. High exposure levels may cause fatigue, euphoria, confusion, dizziness. TOLUENE IS LESS TOXIC THEN BENZENE.
- c. PEL for a ten hour TWA is 100 ppm.

- 3. XYLENE
- a. Colorless, flammable liquid (class 1B or IC depending on isomers) with aromatic odors.
- b. high exposure levels may case dizziness, drowsiness, narcosis.
- c. PEL for a ten hour TWA is 100 ppm.

4. ETHYLBENZENE

- a. Clear, colorless, highly flammable liquid (class 1B) with characteristic odor.
- b. High exposure levels may cause irritation to skin, nose and throat, constriction in chest, loss of consciousness, respiratory failure.
- c. PEL for an eight hour TWA is 100 ppm.

ALL SUBSTANCES AS THEY EXIST ON SITE ARE EXPECTED TO BE STABLE.

Site Status: ACTIVE: XX INACTIVE:

Site History: THE SITE IS CURRENTLY PARKING AREA ASSOCIATED WITH A RUBBER PRODUCT MANUFACTURING PLANT. A FACILITIES BUILDING HISTORICALLY LOCATED AT THE SITE.

PHYSICAL HAZARDS

No person will climb on any excavated material piles without a safety person observing that activity. Personnel shall otherwise maintain the maximum distance possible from the pit while performing their activities. On-site hazards include physical injuries due to the proximity of workers to engine-driven heavy equipment and tools. Equipment used during excavation may include a backhoe or other excavator, a crane for lifting the tanks and a mechanical tamper or other equipment as part of the subsequent backfilling operations. Only trained personnel will operate machines, tools and equipment; all equipment will be kept clean and in good repair. MANDATORY SAFETY CLOTHING REQUIRED AROUND HEAVY EQUIPMENT WILL INCLUDE A HARDHAT AND STEEL-TOED BOOTS AT A MINIMUM.

ALL WORK WILL BE PERFORMED IN ACCORDANCE WITH OSHA GUIDELINES.

Daily inspections of the excavation, the adjacent areas, and protective systems are to be made by a qualified person while personnel are on site. Attention will be made to note if any evidence of potential cave-in exists.

HAVE AT LEAST ONE DRY CHEMICAL MODEL PA-200 A-B-C FIRE EXTINGUISHER PRESENT.

LEVEL OF PROTECTION

A contamination Reduction Zone (CRZ) will be maintained and adjusted as work proceeds and moves around the site. The workers on site will wear level 'D' protective clothing. (This protection level may be upgraded after on-site conclusions of data are completed). THE LEVEL OF PROTECTION FOR PERSONNEL WORKING IN THE AREA WILL BE UPGRADED IF; the organic vapor levels in the equipment operator's breathing zone exceeds 5 ppm above background levels continuously for more then five minutes. In this event, personnel protective equipment will include full face respirators with double-cartridge filters for organic vapors and particulates, in addition to hardhat, steel-toed boots and coveralls. Excavation will cease, equipment shutdown, and personnel will withdraw from the area if either 1.) the organic concentration in the operator's breathing zone exceeds 200 ppm for 5 minutes or 2.) the organic vapor concentration two feet above the excavation exceeds 2,000 ppm or 25% of the lower explosive limit. If work proceeds in an environment where organic vapor concentrations exceed 200 ppm, a self contained breathing apparatus or airline respirator will be utilized by the personnel.

Levels of Protective Clothing are defined on the following pages as described in the "EPA Standard Operating Safety Guidelines":

LEVEL A PROTECTION

Components:

- 1.) Pressure-demand, supplied air respirator that is MSHA and NIOSH approved. Respirators may be pressure demand, self contained breathing apparatus (SCBA), or pressure demand, airline respirator with an escape bottle for atmospheres with an extreme IDLH.
- 2.) Fully encapsulating chemical resistant suit.
- 3.) Inner, chemical resistant gloves.
- 4.) Disposable gloves and boot covers, worn over the fully encapsulating suit.
- 5.) 2-way radio communications is highly recommended.

LEVEL B PROTECTION Components:

- 1.) Pressure-demand, supplied air respirator that is MSHA and NIOSH approved. Respirators may be pressure demand, self contained breathing apparatus (SCBA), or pressure demand, airline respirator with an escape bottle for atmospheres with an extreme IDLH.
- 2.) Chemical resistant clothing which includes overalls and long sleeved jacket or, hooded one or two piece chemical splash suit or disposable chemical resistant one piece suit..
- 3.) Outer chemical resistant gloves.
- 4.) Inner chemical resistant gloves.
- 5.) Chemical resistant, steel toed and shank boots.
- 6.) Disposable chemical resistant boot covers.
- 7.) Hardhat.
- 8.) 2-way radio communications is highly recommended.

LEVEL C PROTECTION

Components:

- 1.) Air purifying respirator, full face, with twin cartridge or cannister equipped filters, that are MSHA and NIOSH approved.
- 2.) Chemical resistant clothing which includes coveralls or, hooded one-piece or two-piece chemical splash suit or chemical resistant hood and apron; disposable chemical resistant coveralls.
- 3.) Outer chemical resistant gloves.
- 4.) Inner chemical resistant gloves.
- 5.) Chemical resistant, steel toed and shank boots.
- 6.) Disposable chemical resistant boot covers.
- 7.) Hardhat.
- 8.) 2-way radio communications is recommended.

LEVEL D PROTECTION

Components:

- 1.) Coveralls.
- 2.) Gloves.
- 3.) Leather boots, shoes or chemical resistant, with steel toe and shank.
- 4.) Safety glasses or chemical splash goggles.
- 5.) Hardhat or face shield.

COMBUSTIBLE GAS AND ORGANIC VAPOR MONITORING

Site personnel will monitor ambient levels of combustible gas vapors using a Thermo Environmental Instruments model 580A or a Gastech model GX-88 OVM. Volatile organic vapor levels greater then 5 ppm above background levels in the hot zone are not anticipated. If the OVM measurements do not decrease below 5 ppm, level 'C' protection will be required. The site Project Manager will be notified if organic vapor levels in the air samples exceed ambient concentrations.

A wetting agent or some form of dust control is recommended to reduce the airborne dust level and subsequent particulate hazard. HEPA respirator cartridges are also recommended as needed.

SITE ENTRY PROCEDURES

Any personnel entering the site will observe all conditions set forth by the owner of the property, including vehicle travel speeds, restricted areas and conduct.

Eating, drinking, smoking and other practices which increase the probability of hand-to-mouth transfer of contamination is prohibited in the work zone. All field personnel will be instructed to thoroughly wash their hands and face upon leaving the work area for breaks or cessation of day's activities. A first aid kit and at least one 20 pound A-B-C fire extinguisher will be available at the site.

DECONTAMINATION PROCEDURES

If required, equipment and personnel decontamination areas will be designated by the Project Manager at the start of the project. To prevent the transfer of contamination from the work site into clean areas, all tools will be cleaned adequately prior to final removal from the work zone. Protective clothing such as Tyvek coveralls, latex gloves, boot covers, etc. will be changed on a daily basis or at the discretion of the Project Manager on site. All disposable protective clothing will be put into plastic bags and disposed of in a proper manner. All respirator cartridges will be discarded and replaced with fresh units on a daily basis, disposal will be in the same manner as the protective clothing. Excavated soils will be stockpiled in an area designated by the Project Manager, until chemical analysis has been performed on representative samples.

In the event of a medical emergency, the injured party will be taken through decontamination procedures, if possible. However, the procedures may be omitted when it may aggravate or cause further harm to the injured party. Member of the work team will accompany the injured party to the medical facility to advise on matters concerning chemical exposure.

Personnel Protection Level will be Level 'D'. Protective clothing levels may be upgraded in the event that on site conclusions determine a greater then anticipated danger to personnel.

SPECIAL CONDITIONS

Site Entry: NORMAL, NO SPECIAL CONDITIONS

Decontamination-

Personnel and Equipment: IF REQUIRED, PERSONNEL AND EQUIPMENT

WILL BE DECONTAMINATED A PER USEPA

STANDARD OPERATING SAFETY
GUIDELINES. A SMALLER MODIFIED

DECONTAMINATION LINE MAY BE USED DUE

TO SPACE RESTRICTIONS.

Work Limitations (time, weather):

NONE ARE ANTICIPATED, HOWEVER, PERSONNEL WORKING ON SITE MAY EXPERIENCE ELEVATED TEMPERATURES DURING THE WORK DAY. IN THE EVENT THAT AMBIENT TEMPERATURES REACH OR EXCEED 80 DEGREES FAHRENHEIT, THE FOLLOWING GUIDELINES ARE RECOMMENDED.

- 1. Periods of work should be reduced to no less then one hour time frames and separated by breaks intended to reduce personnel stress due to reduced natural ventilation from wearing protective clothing.
- 2. All personnel wearing level C protective clothing or greater, will be subject to medical monitoring of body temperature after work periods, by the following guidelines;
- a. Heart Rate (HR) should be measured by counting the radial pulse rate for 30 seconds and doubling count for the correct pulse rate. This should be done as early as possible in the resting period. The HR at the beginning of the rest period should not exceed 110 beats per minute. If the HR is higher, the next work period should be shortened by 10 minutes, while the length of the rest period remains the same. If the HR is 100 beats per minute at the beginning of the next rest period, the following work period should be shortened by an additional 10 minutes.
- b. Body temperatures should be measured orally with a clinical thermometer as soon as possible in each resting period. Oral Temperatures (OT) should not exceed 99 degrees Fahrenheit. If it does, the next work period should be reduced by 10 minutes while the length of the resting period remains the same. If the OT exceeds 99 degrees Fahrenheit at the beginning of the next work period, the following work period should be reduced by an additional 10 minutes. OT should be measured at the end of each rest period to ensure that the body's temperature has dropped below 99 degrees Fahrenheit.

Body Water Loss (BWL) from sweating, could result in dehydration and further complications and stress on personnel working in protective clothing under adverse weather conditions. It is strongly recommended that plenty of stress relief beverages be available on site to replace body fluids. Commercial drink mixes that provide electrolyte balancing solutions or water are adequate for replacing body fluids.

Alternate methods of heat stress reduction can be made available such as,

Portable showers or hose-down facilities, Shelter cover to protect against direct sunlight, Rotating teams of personnel wearing protective clothing, Performing extremely arduous tasks early in the workday.

EMERGENCY INFORMATION

In the event of an injury or suspected chemical exposure, the first responsibility of the Project Manager will be to prevent any further injury. This objective will normally require an immediate stop to work until the situation is remedied. The Project Manager may order the evacuation of the work party. Other primary responsibilities in the event of an accident will be the first aid and decontamination of the injured team member(s). The injured party will be moved to a designated safe area and initial first aid will be rendered.

Employees are asked to make every effort and take personnel responsibility to prevent accidents involving machinery or any other aspect of the job, either by individual action or by notifying the Project Manager immediately of any unsafe condition that may exist.

In the event of an unexpected hazardous material discovery on site, the following actions will be taken by any employee involved;

- 1. The person having uncovered the unexpected material will notify the Project Manager and other workers of the danger. The site will be cleared of personnel if deemed necessary by the Project Manager. If site evacuation is required, appropriate local agencies such as the Fire Department or Health Department will be notified as well.
- 2. Immediate action will be taken to contain the hazardous material, provided the workers involved are properly attired with adequate protective clothing to avoid exposure.
- 3. Proper containment procedures will be determined for the hazardous material encountered prior to cleanup commencing. All personnel involved in the containment effort will be properly protected to prevent exposure. Backup personnel will be similarly protected while monitoring the work being done for any additional dangers.
- 4. The container(s) will be staged on site, away from the major activity areas and in such a way that if loss of containment occurs, the material will be withheld from further spread by a secondary containment berm or vessel.
- 5. The owner or agent controller of the property will be notified promptly of the incident and will be apprised as to the options available for proper disposal.

ACUTE EXPOSURE SYMPTOMS AND FIRST AID

EXPOSURE ROUTE	SYMPTOMS.	FIRST AID	
Skin	Dermatitis, itching redness, swelling	Wash immediately with soap and water contact ambulance if evacuation is needed.	
Eyes	Irritation, watering	Flush with water, transport directly to emergency room, if necessary.	
Inhalation	Vertigo, tremors stupor, dizziness	Move person to fresh air, cover source of exposure.	
Ingestion	Nausea, vomiting	Call Poison Control Center, DO NOT INDUCE VOMITING, transport to medical facility.	
Local Resources:			

HEALTH AND SAFETY CONTACT FOR ASE:

Michael D. Dirk

Office: (415) 820-9391

Ambulance *Police* : 911 Fire

(415) 476-6600 POISON CONTROL: SF

Emergency Route to nearest Medical Facility:

Exit site, Travel WEST on 65th Street LEFT on San Pablo Avenue RIGHT on Ashby Avenue (Hwy. 13) RIGHT on Colby Plaza

HOSPITAL IS NEAR THE CORNER OF ASHBY AY COLBY PLAZA

Hospital: -ALTA BATES HOSPITAL

3001 COLBY PLAZA, BERKELEY 540-0337 ext 6

AQUA SCIENCE ENGINEERS signature page for

Oliver Rubber Jobsite

The below signed personnel have read this plan, understand it's content, and agree to follow the guidelines set forth.

Name (print) Signature Project Assignment Date

STEVE Deligo And Start Project Manager 6/24/92

Gezald WSASSE Serold-lary Operator 6/24/92

APPENDIX B HAZARDOUS WASTE MANIFEST

UNIFORM HAZARDOUS 1. General	WATER THE	Monifest Documen	H IND.	2. Page 1	Information in the shaded area
	10101016171916111	18:3:4	0 15	or 1	is not required by Federal law.
Oliver	Rubber Co.				
P.O. Box 8447 - Oakland, Generalors Phone (\$10) 654-7711	California 946	608	80 G 8	enerators D	
Transporter 1 Company Name	6. US EPA ID Number	<u></u>		roreponers ID	20700
exenna, Ltd.	C (A)D(9 (8)2)	4131815616	D. Irone	orters Phone	15.55
. Transporter 2 Company Name	8. US EPA ID Number			creporters (D orters Phone	
Designated Facility Name and Site Address	10. US EPA ID Number	<u> </u>	G State	cacility's #D	
Erickson, Inc. 255 Parr			H FOCIE		nalodžionya atkologi. Bose o rodine azavel
Richmond, California 9480	01 C A D 10 10 19 #	12. Conto		13. Total	(510) 235-1393
. US DOT Description (including Proper Shipping Name, Haze	ord Class, and ID Number)	No.	Туре	Quantity	Wt/Vol 1. Waste Number
" Waste Empty Storage Ta					Sictle .
NON-RCRA Hazardous Was	ste Solid.	0:0:1	T 10	C161767	P P NONE
b.		0.0.1		1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1	State
					EPA/Other
c.			┝╌╌┤	1 1 1 1	State
		1 1		<u> 1 † </u>	EPA/Offier .
d.	· 			 	State
		1	, ,		
					EPA/Olher
ty. <u> </u>				g Codes for Was	
Additional Descriptions for Additional Limited Above Ly. L. Empty Storage Ter Description of Additional Information (eep away from sources of around U.S.T.'s. Site loc	Ice per 1000 ; f ignition. Alvertion: 1259 -	ways wear 65th Stre	hard	hats wh	en working
Expty Storage Tar marted with 15 lbs. Bry specify. Special Hondling Instructions and Additional Information Geep away from sources of ground U.S.T.'s. Site local 4 Hr. Contact Name: Ron	ignition. Alvestion: 1259 - Kessler - Phor	ways wear 65th Stre	hard et E	hats wh meryvil) 654-7	en working le, California
Expty Storage Tar nerted with 15 lbs. Bry specify Special Hondling Instructions and Additional Information Geep away from sources of ground U.S.T.'s. Site loc Hr. Contact Name: Ron GENERATORS CERTIFICATION: I hereby decides that the packed, marked, and labeled, and are in all respects in packed.	ignition. Alvestion: 1259 - Kessler - Phorecontents of this consignment are proper condition for irransport by his	Vays wear 65th Stre 1e Number fully and accurately or phiway according to a	hard et E (510 described oppicable)	hats wh meryvil) 654-7 bove by proper memorional and	en working le, California 711 shipping nome and are classified national government regulations.
Expty Storage Tar nerted with 15 lbs. Bry Special Handling Instructions and Additional Information Geop away from sources of around U.S.T.'s. Site loc 4 Hr. Contact Name: Ron GENERATOR'S CERTIFICATION: I hereby decider that the	Ice per 1000 fignition. Alvestion: 1259 - Kessler - Phore contents of the consignment are corper condition for ironsport by his a program in place to reduce the practicable method of treatment, a smoll quantity generator, I have	Veys wear 65th Stre 18 Number fully and accurately or phiway according to a phical condition of the conditio	hard et E (510 described of posicione is of worste surrently grown	hats whomer yull a second of the second of t	en working 1e, California 711 shipping nome and are classified notional government regulations. the principle of the present and father than the present and the p
Special Handling Instructions and Additional Information Leep away from sources of around U.S.T.'s. Site loc Leep away from sources of around U.S.T.'s. Site loc Leep away from sources of around U.S.T.'s Site loc Leep away from sources of around U.S.T.'s care in a leep away from sources of around U.S.T.'s care in a leep away from some in all respects in packed, marked, and labeled, and are in all respects in packed, marked, and labeled, and are in all respects in packed, marked, and labeled, and that I have selected the packed in a large quantity generator, I certify that I have a economically practicable and that I have selected the pathward to human health and the environment; OR, II amamanagement method that is available to me and that I care	Ice per 1000 fignition. Alvestion: 1259 - Kessler - Phore contents of the consignment are corper condition for ironsport by his a program in place to reduce the practicable method of treatment, a smoll quantity generator, I have	Veys wear 65th Stre 18 Number fully and accurately or phiway according to a phical condition of the conditio	hard et E (510 described of posicione is of worste surrently grown	hats whomer yull a second of the second of t	en working le, California 711 shipping nome and are classified national government regulations, a degree I have determined to be the minimizes the present and future meration and select the best wasternament.
named with 15 lbs. Bry special Handling Instructions and Additional Information eep sway from sources of ground U.S.T.'s. Site loc 4 lbr. Contacr Name: Ron GENERATOR'S CERTIFICATION: I hereby declare that the packed, marked, and labeled, and are in all respects in p if I am a large quantify generator, I certify that I have a economically practicable and that I have selected the p threat to human health and the environment; OR, if I am management method that is available to me and that I a	Ice per 1000 fignition. Alv Cation: 1259 - Kessler - Phor contents of this consignment are proper condition for iransport by his a program in place to reduce the practicable method of treatment, a a small quantity generator, I have can afford.	Veys wear 65th Stre 18 Number fully and accurately or phiway according to a phical condition of the conditio	hard et E (510 described of posicione is of worste surrently grown	hats whomer yull a second of the second of t	en working 1e, California 711 shipping name and are classifier national government regulations. degree I have determined to be an invitable the present and future meration and select the best waste. Month Day Ye
nerted with 15 lbs. Bry special Handling Instructions and Additional Information Leep away from sources of tround U.S.T.'s. Site loc 4 Hr. Contact Name: Ron GENERATOR'S CERTIFICATION: I hereby declare that the packed, marked, and labeled, and one in all respects in pe t I am a large quantity generator, I certify that I have economically practicable and that I have selected the p theat to human health and the environment; OR, II am management method that is available to me and that I a	Fignition. Alvertion: 1259 - Kessler - Phorecondents of this consignment are proper condition for ironsport by his a program in place to reduce the practicable method of treatment, a small quantity generator, I have condition. Signature	65th Street Number fully and accurately a private and toxicity stronge, or disposal aumade a good faith eff	hard et E (510 described of posicione is of worste surrently grown	hats whomer yull a second of the second of t	en working 1e, California 711 shipping name and are classifier national government regulations of degree I have determined to be an invitate the present and future meration and select the best was a Month Day Ye
nerted with 15 lbs. Bry special Handling Instructions and Additional Information Leep sway from sources of tround U.S.T.'s. Site loc Leep sway from sources of tround U.S.T.'s. Site loc Leep sway from sources of tround U.S.T.'s. Site loc Leep sway from sources of tround U.S.T.'s. Site loc Leep sway from sources of tround U.S.T.'s. Site loc Leep sway from sources in or the local local local local local local Leep sway from sources of Leep sway from sources o	Fignition. Alvertion: 1259 - Kessler - Phorecondents of this consignment are proper condition for ironsport by his a program in place to reduce the practicable method of treatment, a small quantity generator, I have condition. Signature	65th Street Number fully and accurately a private and toxicity stronge, or disposal aumade a good faith eff	hard et E (510 described of posicione is of worste surrently grown	hats whomer yull a second of the second of t	les listed Above D. California 711 Shipping nome and are classifier national government regulations of degree I have determined to be the minimizes the present and future the minimizer that the minimizes the minimize
Special Handling Instructions and Additional Information Leep away from sources of Leep away fro	Ice per 1000 fignition. Alvertion: 1259 - Kessler - Phore contents of the consignment are proper condition for irrasport by his practicable method of treatment, a small quantity generator, I have can afford. Signature	65th Street Number fully and accurately a private and toxicity stronge, or disposal aumade a good faith eff	hard et E (510 described of posicione is of worste surrently grown	hats whomer yull a second of the second of t	les listed Above D. C. C. C. C. C. C. C. C. C.
Special Handling Instructions and Additional Information Gep away from sources of around U.S.T.'s. Site loc 4 Hr. Contacr Name: Ron GENERATOR'S CERTIFICATION: I hereby declare that the packed, marked, and labeled, and are in all respects in particular to human health and the environment; OR, if I am a large quantity generator, I certify that I have a economically practicable and that I have selected the particular to human health and the environment; OR, if I am management method that is available to me and that I conted/Typed Name Transporter 1 Acknowledgement of Receipt of Materials med/Typed Name Lawrence F. DeKalh Transporter 2 Acknowledgement of Receipt of Materials	Ice per 1000 fignition. Alvertion: 1259 - Kessler - Phore contents of the consignment are proper condition for irrasport by his practicable method of treatment, a small quantity generator, I have can afford. Signature	65th Street Number fully and accurately a private and toxicity stronge, or disposal aumade a good faith eff	hard et E (510 described of posicione is of worste surrently grown	hats whomer yull a second of the second of t	tes listed Above D. d. d. len working 1e, Cali fornia 711 shipping nome and are classifier national government regulations. degree I have determined to be an inharizes the present and future meration and select the best wasterness of the select the
Special Handling Instructions and Additional Information Gep away from sources of around U.S.T.'s. Site loc 4 Hr. Contacr Name: Ron GENERATOR'S CERTIFICATION: I hereby declare that the packed, marked, and labeled, and are in all respects in particular to human health and the environment; OR, if I am a large quantity generator, I certify that I have a economically practicable and that I have selected the particular to human health and the environment; OR, if I am management method that is available to me and that I conted/Typed Name Transporter 1 Acknowledgement of Receipt of Materials med/Typed Name Lawrence F. DeKalh Transporter 2 Acknowledgement of Receipt of Materials	Ice per 1000 fignition. Alvertion: 1259 - Kessler - Phore contents of this consignment are proper condition for transport by his a program in place to reduce the practicable method of treatment, a small quantity generator, I have can afford. Signature	65th Street Number fully and accurately a private and toxicity stronge, or disposal aumade a good faith eff	hard et E (510 described of posicione is of worste surrently grown	hats whomer yull a second of the second of t	tes listed Above D. d. d. len working 1e, Cali fornia 711 shipping nome and are classifier national government regulations. degree I have determined to be an invinizes the present and future meration and select the best was invention and select the best was invention and select the Day Month Day Month Day Vo. 0 16 12 4 19
Transporter 1 Acknowledgement of Receipt of Materials Transporter 2 Acknowledgement of Receipt of Materials Transporter 3 Acknowledgement of Receipt of Materials	Ice per 1000 fignition. Alvertion: 1259 - Kessler - Phore contents of this consignment are proper condition for transport by his a program in place to reduce the practicable method of treatment, a small quantity generator, I have can afford. Signature	65th Street Number fully and accurately a private and toxicity stronge, or disposal aumade a good faith eff	hard et E (510 described of posicione is of worste surrently grown	hats whomer yull a second of the second of t	tes listed Above D. d. d. len working 1e, Cali fornia 711 shipping nome and are classifier national government regulations. I degree I have determined to be an interizes the present and future meration and select the best was interested and select the select
Special Handling Instructions and Additional Information Leep sway from sources of around U.S.T.'s. Site loc Leep sway from sources of around U.S.T.'s. Site loc Leep sway from sources of around U.S.T.'s. Site loc Leep sway from sources of around U.S.T.'s. Site loc Leep sway from sources of around U.S.T.'s. Site loc Leep sway from sources of around U.S.T.'s. Site loc Leep sway from sources of a control of the selected the power of the selected in the power of the	ignition. Alvestion: 1259 - Kessler - Phore contents of the consignment are corper condition for ironsport by his a program in place to reduce the practicable method of treatment, a small quantity generator, I have can afford. Signature Signature	Veys wear 65th Stre 16 Number fully and accurately a privacy according to a privacy and disposal au made a good faith eff	hard et E (510 described of oppicable in or waste our or to minister the control of the control	hats whomeryvil) 654-7 bove by proper memorated to the liable to me which nize my waste ge	les listed Above D. d. len working 1e, Cali fornis 711 shipping name and are classifier national government regulations of degree I have determined to be an invitrizes the present and future meration and select the best was Month Day You go worth Day You go
Special Handling Instructions and Additional Information Leep away from sources of around U.S.T. s. Site loc Leep away from sources of around U.S.T. s. Site loc Hr. Contact Name: Ron GENERATOR'S CERTIFICATION: I hereby decide that the packed, marked, and abeind, and one in all respects in personality practicable and that I have selected the personality practicable and that I have selected the personal to human health and the environment; OR, I I am management method that is available to me and that I amanagement method that is available to me and that I amanagement Marked F. DeKalh Transporter 1 Acknowledgement of Receipt of Materials inted/Typed Name Lawrence F. DeKalh Transporter 2 Acknowledgement of Receipt of Materials inted/Typed Name Discrepancy Indication Space	ignition. Alvestion: 1259 - Kessler - Phore contents of this consignment are proper condition for ironsport by his a program in place to reduce the practicable method of treatment, a small quantity generator, I have can afford. Signature Signature	Veys wear 65th Stre 16 Number fully and accurately a privacy according to a privacy and disposal au made a good faith eff	hard et E (510 described of oppicable in or waste our or to minister the control of the control	hats whomeryvil) 654-7 bove by proper memorated to the liable to me which nize my waste ge	Resulted Above Do C C Cen working 1e, Cali fornic 711 Shipping nome and are classified national government regulations. I degree I have determined to be a minimizes the present and future ineration and select the best wastern and formation and fo
Special Handling Instructions and Additional Information Leep sway from sources of around U.S.T.'s. Site loc Leep sway from sources of around U.S.T.'s. Site loc Leep sway from sources of around U.S.T.'s. Site loc Leep sway from sources of around U.S.T.'s. Site loc Leep sway from sources of around U.S.T.'s. Site loc Leep sway from sources of around U.S.T.'s. Site loc Leep sway from sources of a control of the selected the power of the selected in the power of the	ignition. Alvestion: 1259 - Kessler - Phore contents of the consignment are corper condition for ironsport by his a program in place to reduce the practicable method of treatment, a small quantity generator, I have can afford. Signature Signature	Veys wear 65th Stre 16 Number fully and accurately a privacy according to a privacy and disposal au made a good faith eff	hard et E (510 described of oppicable in or waste our or to minister the control of the control	hats whomeryvil) 654-7 bove by proper memorated to the liable to me which nize my waste ge	tes listed Above D. d. d. len working 1e, California 711 shipping nome and are classified rational government regulations. Declared I have determined to be an inharizes the present and future
Special Handling Instructions and Additional Information Special Handling Instructions and Additional Information Seep sway from sources of Around U.S.T. s. Site loc 4 Hr. Contact Name: Ron GENERATOR'S CERTIFICATION: I hereby declare that the packed, marked, and abeind, and one in all respects in per 8 I am a large quantity generator, I certify that I have selected the per 1 threat to human health and the environment; OR, II am a management method that is available to me and that I am Incomporter I Acknowledgement of Receipt of Materials Intersporter 2 Acknowledgement of Receipt of Materials Transporter 2 Acknowledgement of Receipt of Materials	ignition. Alvestion: 1259 - Kessler - Phore contents of this consignment are proper condition for ironsport by his a program in place to reduce the practicable method of treatment, a small quantity generator, I have can afford. Signature Signature	Veys wear 65th Stre 16 Number fully and accurately a privacy according to a privacy and disposal au made a good faith eff	hard et E (510 described of oppicable in or waste our or to minister the control of the control	hats whomeryvil) 654-7 bove by proper memorated to the liable to me which nize my waste ge	les listed Above D. Call fornia This call for

CALL THE NATIONAL RESPONSE CENTER 1-800-424-8802:

р

	THE PARTY OF THE P		
		在ET 1986年1986年,1916年,1916年,1916年,1916年,1916年,1916年,1916年,1916年,1916年,1916年,1916年,1916年,1916年,1916年,1916年,1916年	
	Designation of Proceedings Address LEAGUAGE LEAGUAGE LEAGUAGE	US EPA D NELLO	
All Carried	Transferred. By Art FAA	TUCKCAMIBOTE	
	33. UB:DOT Description (including Proper Shipping Name, Hazard Cla	23 -360 3 43 pe	Gen Wilko
E Q	CHARLENGE LIGHTLA		
NER A			
T OA	c.		
		411111	
	d.		. Sparting
	ENGLATE DICE IN THE	7 SE Standing Codes for	
		10 de 15 de	100
N O O O	15. Special Hendling Instructions and Additional Information		
*	WAR 1980 TEXT The ST.	Trival,	
Š			
	GENERATOR'S CERTIFICATION:I hereby declare that the con- ead are classified, packed, marked, and labeled, and are in all re- national government regulations.		
5	If I ats a large quantity generator, I certify that I have a program is to be accommically practicable and that I have selected the prac- present and future threat to human health and the environment; generation and select the best wester management method that is	DR, if I am a small quantity generator, I have made a good faith e	He degree I nave determine He to me which minimizes the Hort to minimize my waste
MEHIGENCY	Printed/Typed Name	Signature	Month Day
RANG	17. Transporter 1 Acknowledgement of Receipt of Materials Printed/Typed Name	Signature	Month Ony
9 P	18. Transporter 2 Acknowledgement of Receipt of Materials	I A TOTAL	0624
# P	Printed/Typed Name	Signature	Month Day
RT			
R	19. Discrepancy Indication Space		
RTER F	19. Discrepancy Indication Space 20. Facility Owner or Operator Certification of receipt of hazardous n		

Do Not Write Below This Line



NON-HAZARDOUS SPECIAL WASTE MANIFEST

GENE	RATOR
Senerator Name Oliver Rubber Co.	
Address 1200 65 th St Gmar will	Address 1200 65 th St Energyille
(A 94662	CA 94662
Phone No. 510 6547711	Phone No. 510 6547711
BFI Waste Code C A 4 0 5 0 7 1 0 9 2 Description of Waste	Quantity Units No. Type D-Drum C - Carton
Sol contamnated with oil & Griase	B-Bag
! !	T - Truck P - Pounds Y - Yards
	O - Other
	free liquid as defined by 40 CFR Part 260.10 or any applicable t 261 or any applicable state law, has been properly described, ation according to applicable regulations.
Steve De Hope Generator Authorized Agent Name Signature Signature	071552 Snipment Date
TRANS	PORTER
Truck No.	Phone No. (510) 732-6873
Fransporter Name A. S.T.	Driver Name (Print) T.U. GOWMAN
Address P.O. Cox 2005	Vehicle License No./State 1031207
	Vehicle Certification
hereby certify that the above named material was picked up at the generator site listed above.	I hereby certify that the above named material was delivered without incident to the destination listed below.
Driver Signature Shipment Date	Driver Signature Dolivery Date
DESTI	NATION
Site Name VASCO RIAD CANDFILL	
Address 4001 N VAVS 22 LISET 1	nuce 94:00
hereby certify that the above named material has been accepted a	and to the best of my knowledge the foregoing is true and accurate.
	011592
Name of Authorized Agent Signature	. Receipt Date
	Lar

PASS CODE _

ं ग्रहाम

ANONUHAZARDOUS SPECIALEWASTE NANIERST

GENE	RATOR
enerator Marpas Colover Rubber Co.	Generating Location Oliver Co.
agress status 65th St. Emeryville	Address 1200 65 St. Emeryulle
(A 9466)	CA 94662
None No. 5 1 0 - 65 4 7 7 1 1	Phone No. 510-6547711
BEI Waste Code CA 405 07109 2 Description of Waste	Containers Type Quantity Units No. Type C - Carton
Soll contaminated with oil + 50 ase	B - Bag T - Truck
	P - Pounds Y - Yards
	O - Other
at .	refree liquid as defined by 40 CFR Part 260.10 or any applicable rt 261 or any applicable state law, has been properly described, tation according to applicable regulations. Shipment Date
TRANS	PORTER
Tuck No. # 304	Phone No. (510) 732-6873
ansporter Name A.S.T	Driver Name (Print)
10. to 1 2605	Vehicle License No./State 4F09086
YSIJAU OUTZA	Vehicle Certification NOV -14AZ
hereby certify that the above named material was picked up the generator site listed above.	hereby certify that the above named material was delivered without incident to the destination listed below.
Wer Signature Shipment Date	Driver Signature Delivery Date
	NATION
Site Name VASCO ROAD LANGF. 11	Phone No. 510-44700451
ddress 4001 N. WAXES Rd liver	
hereby certify that the above named material has been accepted a	
	071592
Name of Authorized Agent Signature	Receipt Date

PASS CODE

APPENDIX C . LABORATORY ANALYSIS and CHAIN OF CUSTODY

APPENDIX D

UNDERGROUND STORAGE TANK UNAUTHORIZED RELEASE FORM

	UNDERGROUND STORAGE TANK UNAUTHORIZED RELEASE (LEAK) / CONTAMINATION SITE REPORT				
EME	RGENCY HAS STATE OFFICE OF EMERGENCY SERVICE		FOR LOCAL AGENCY USE ONLY		
	YES TO NO REPORT BEEN FILED? YES TO NO	HEREBY CERTIFY THAT I HA	VE DISTRIBUTED THIS INFORM	MATION ACCORDING TO THE	
REPO	ORT DATE CASE #	1		E INSTRUCTION SHEET ON TH	E BACK PAGE OF THIS FORM
'			ego ky fried i ge		
0 #	7 M 0 d 1d 9 d 2 d	PHONE	SIGNED	SNATURE	DATE
				SNATURE	
產	<u> </u>		685–6700		
нероктер ву	REPRESENTING X OWNER/OPERATOR REGIONAL BOX	ARD '	COMPANY OR AGENCY NAME	_	
🗟	LOCAL AGENCY OTHER		Aqua Science	Engineers, Inc	·
=	ADDRESS				
	1041 Shary Circle STREET Concord		CITY C	A <u>s</u>	94518 zip
RESPONSIBLE PARTY	NAME	(CONTACT PERSON		PHONE
SS È	Oliver Rubber Co. UNKKK	OWN	Ron Kessler		(510) 654-7711
PS A	ADDRESS				
뿐	1200 _{STREET} 65 Street		CITY Em	eryville s	CA ZIP
\Box	FACILITY NAME (IF APPLICABLE)	1	OPERATOR		PHONE
z	Oliver Rubber Co.		Ron Kessler		(510) 654-7711
SITE LOCATION	ADDRESS			· · · · · · · · · · · · · · · · · · ·	4,
ğ	1200 street 65th Street		crry Em	eryville ,	Alameda
E E	CROSS STREET		CITY		COUNTY ZIP
"	San Pablo				
-			CONTACT PERSON	· · · · · · · · · · · · · · · · · · ·	PHONE
E S	All a la Carata Harlet Com Compine	1			(510) 2714320
E S	Alameda County Health Care Services		Susan Hugo		PHONE
IMPLEMENTING AGENCIES	RWQCB San Francisco Bay Region	.	Eddy So		(510) 6580588
18 B	(1) NAM	vi E		J	QUANTITY LOST (GALLONS)
N S	Diesel Oil				X UNKNOWN
SUBSTANCES	(2)				
ļ					UNKNOWN
Ä	DATE DISCOVERED HOW DISCOVERED	:	<u></u>	SUBSURFACE MONITORING	NUISANCE CONDITIONS
NBATEMENT	$0 + 6 + 2 + 4 + 9 + 2 + \Box$ TANK TEST \overline{X}	, <u> </u>		THER	
	DATE DISCHARGE BEGAN		METHOD USED TO STOP DIS	SCHARGE (CHECK ALL THAT	APPLY)
DISCOVERY"	M M D D Y Y X UNKNOWN		REMOVE CONTENTS [X CLOSE TANK & REMOVE	REPAIR PIPING
8	HAS DISCHARGE BEEN STOPPED ?		REPAIR TANK	CLOSE TANK & FILL IN P	LACE CHANGE PROCEDURE
Sia	X YES NO IFYES, DATE 0 6 2 6 4 9	2	REPLACE TANK	OTHER	
ā	SOURCE OF DISCHARGE	JSE(S)	~ · · · · · · · · · · · · · · · · · · ·		· · · · · · · · · · · · · · · · · · ·
SOURCE	TANK LEAK X UNKNOWN	OVE	RFILL F	RUPTURE/FAILURE	SPILL
180	PIPING LEAK OTHER	COR	ROSION V	JNKNOWN	OTHER
<u> </u>	CHECK ONE ONLY		- 11		
8 ≥	CHECK ONE ONLY SOIL ONLY GROUNDWATER DRINKING WATER - (CHECK ONLY IF WATER WELLS HAVE ACTUALLY BEEN AFFECTED)				
-	CHECK ONE ONLY CHECK ONE ONLY CHECK ONLY IF WATER WELLS HAVE ACTUALLY BEEN AFFECTED)				
ž s					
CURRENT	LEAK BEING CONFIRMED PRELIMINARY SITE ASSESSMENT UNDERWAY POST CLEANUP MONITORING IN PROGRESS				
100	REMEDIATION PLAN CASE CLOSED (CLEANUP	COMPLE	TED OR UNNECESSARY)	CLEANUP UNDER	
 	CHECK APPROPRIATE ACTION(S)				
₹ z				PRODUCT (FP)	ENHANCED BIO DEGRADATION (IF,
REMEDIAL ACTION	CAP SITE (CD) EXCAVATE & TREAT			GROUNDWATER (GT)	REPLACE SUPPLY (RS)
图》	CONTAINMENT BARRIER (CB) NO ACTION REQUIR	IED (NA)	TREATMENT AT	THOOKUP (HU)	VENT SOIL (VS)
<u> </u> _	VACUUM EXTRACT (VE) OTHER (OT)				
2					
COMMENTS					
ğ					
1	i				

APPENDIX C

Environmental Site Assessment October 28, 1992



October 28, 1992

PROJECT REPORT
for
PHASE II SOIL AND GROUNDWATER
ASSESSMENT, NO. 2571
at
The Oliver Rubber Company
1200 65th Street
Emeryville, California

Prepared for:
Mr. Ron Kessler
The Oliver Rubber Company
1200 65th Street
Emeryville, California

Prepared by:
AQUA SCIENCE ENGINEERS, INC.
2411 Old Crow Canyon Road, #4
San Ramon, CA 94583
(510) 820-9391

EXECUTIVE SUMMARY

A limited groundwater and subsurface site investigation was conducted at The Oliver Rubber Company, 1200 65th Street, Emeryville, California as follow up to underground storage tank removals conducted in 1991 and 1992. The site assessment activities were initiated by the property owner in accordance with the Alameda County Health Care Services Agency (ACHCSA) requirements (see Appendix A for a copy of the "Direction Letter"). The purpose of this site assessment was to: (1) further define the limits of elevated concentrations of petroleum hydrocarbon and solvent contamination which was found in the soil upon excavation of the former underground storage tanks, and (2) to assess the potential for groundwater contamination caused by the leaking tanks or associated product lines. Prior to commencement of field activities, the work plan was approved by the ACHCSA, and well permits will be obtained from the Alameda County Flood Control and Water Conservation District, Zone 7 (see Appendix F for copies of the permit).

The project included the installation of three (3) groundwater monitoring wells and two (2) soil borings. Soil samples were to be collected at five foot intervals until saturated material was encountered. Groundwater samples were to be collected once well installation and well development activities were concluded. Both the soil and groundwater samples were tested at a State of California Certified Laboratory for all or a combination of the following constituents:

Total Petroleum Hydrocarbons as Diesel (TPH-d) (EPA 3550/8015)

BTEX (EPA 8020)

Volatile Organics (EPA 8240)

Oil & Grease (EPA 5520)

Purgeable Halocarbons (EPA 8010)

Acid/Base Extractables (EPA 8270)

The above-referenced analytical tests resulted in Non Detectable (N.D.) levels of constituents in the groundwater samples submitted. Soil samples submitted for analytical testing for the above-referenced constituents resulted primarily in N.D. levels of contamination. It is the opinion of ASE that the tank-removal, and overexcavation activities performed in early 1991 and mid 1992 sufficiently removed the contamination that could have possibly posed a significant threat to the groundwater on site. Groundwater sampling activities performed on October 1, 1992 resulted in N.D. levels of all constituents of which were tested.

TABLE OF CONTENTS

SECTI	ON		PAGE
1.0	INTRODU	CTION	1
2.0	SITE BACI	KGROUND	1
3.0	SCOPE OF	WORK	2
4.0	DRILLING CONSTRU	G AND GROUNDWATER WELL CTION	3
5.0		IPLE COLLECTION AND AL ANALYSIS	4
6.0		WATER SAMPLE COLLECTION MICAL ANALYSIS	6
7.0	GEOLOGY	AND GROUNDWATER GRADIENT	8
8.0	CONCLUS	IONS	9
9.0	RECOMM	ENDATIONS	. 9
10.0.	REPORT	LIMITATIONS	10
LIST O	F_TABLES	<u>5</u>	
TABLE	-	UMMARY OF CHEMICAL ANALYSIS OF SOIL SAMPLES	5
TABLE		UMMARY OF CHEMICAL ANALYSIS OF GROUNDWATER SAMPLES	7
TABLE		UMMARY OF GROUNDWATER VELL SURVEY DATA	8

LIST OF FIGURES

FIGURE 1 SITE LOCATION MAP

FIGURE 2 SITE PLAN

FIGURE 3 GROUNDWATER GRADIENT MAP

LIST OF APPENDICES

APPENDIX A ALAMEDA COUNTY HEALTH CARE SERVICES

AGENCY "DIRECTION LETTER"

APPENDIX B CAL EPA CERTIFIED LABORATORY

REPORT OF SOIL SAMPLES

APPENDIX C CAL EPA CERTIFIED LABORATORY

REPORT OF GROUNDWATER SAMPLES

APPENDIX D SOIL BORING LOGS AND WELL LOGS

APPENDIX E WELL SAMPLING FIELD LOGS

APPENDIX F PERMITS

1.0 INTRODUCTION

The following is a report on the further soil investigation and initial groundwater assessment conducted at The Oliver Rubber Company, 1200 65th Street, Emeryville, CA on October 1, 1992. investigation/assessment was conducted on behalf of representatives of Oliver Rubber, the current property owner, per the written request of the Alameda County Health Care Services Agency (see the "Direction Letter" attached in Appendix A). This report is intended as a supplement to the "Tank Pull" reports by Aqua Science Engineers, Inc. (ASE) dated December 5, 1991 and July 16, 1992. The December 5, 1991 report details the removal of 2 - 8,000 gallon, underground, steel, non-halogenated organic solvent tanks; the July 16, 1992 report details the removal of 1 - 1,000 gallon, underground, steel "Bunker Oil" tank. The purpose of the investigation detailed in this report was to define the direction and gradient of groundwater flow, and to investigate the possible existence and extent of soil and/or groundwater contamination resulting from the leakage of the underground storage tanks.

2.0 SITE BACKGROUND

2.1 Physical Location

The site is located at the corner of 65th Street at Hollis Street. The site is approximately 1/16 mile west of Interstate 80, and 1/16 mile south of Highway 13, within the City limits of Emeryville, California. The site is currently used as a manufacturing setting for rubber products. The topography of the immediate area is generally even and located at approximately 20 feet above mean sea level. (see Figure 1: Site Location Map).

2.2 Background and Site History

Between December 5, 1991 and July 16, 1992, (3) underground storage tanks were removed from the property by ASE; two of the tanks had 8,000 gallon capacities and contained non-halogenated solvents; one of the tanks had a 1,000 gallon capacity, and contained bunker oil. Underground tank removal activities were documented by ASE in a reports referenced in the previous sections.

2.3 General Geology/Hydrogeology

The site rests on unconsolidated sediments primarily composed of clay. The eastern shoreline of the San Francisco Bay is located approximately 1/16 mile west of the site. Shallow groundwater in the area is located approximately 8-10 feet below grade at the site, and is assumed to flow in a westerly direction towards the San Francisco Bay.

2.4 Review of Preliminary Soil Assessment, Baseline, March 1990

Details of the "Tank Pull" reports which include tank removals, disposals, and soil and water sampling and analysis, can be found in ASE reports dated December 5, 1991 and July16, 1992. Detectable levels of Total Petroleum Hydrocarbons (TPH) as Diesel, Oil and Grease, and several constituents of Volatile Organics were found in the sidewalls of both excavations upon backfilling activities. It was determined that groundwater monitoring wells would be necessary to investigate the possibility of groundwater contamination due to leaking tanks.

3.0 SCOPE OF WORK

What follows is the report covering the methods and findings regarding the initial groundwater assessment and additional soil investigation as outlined in the September 10, 1992 workplan.

The scope of work performed for the initial groundwater investigation and further limited soil assessment, included the following tasks:

- Installation of three 25 foot depth groundwater monitoring wells and two soil borings.
- Collection of soil samples at five foot intervals during drilling of the wells and within the capillary fringe.
- Surveying of the monitoring wells.
- Collection of groundwater depth measurements from the wells to determine the direction of groundwater flow and gradient at the site.
- Collection of groundwater samples from the wells.

• Chemical analysis of soil and groundwater samples included testing for all or combinations of the following EPA methods tests: TPH as Diesel and the fractions BTEX (3510/8015, 8020), Volatile Organics (8240), Oil and Grease (5520) Purgeable Halocarbons (8010), and Acid/Base Extractables (8270).

4.0 DRILLING AND GROUNDWATER WELL CONSTRUCTION

A total of three wells were installed at the site on October 1, 1992. The locations of the ground water monitoring wells (MW-1, MW-2, and MW-3) are indicated in Figure 2, Site Plan. The soil borings for well installation were drilled to 25 feet below ground surface using a CME-75 drill rig equipped with 8 inch O.D. continuous flight, hollow stem augers. All drilling equipment was steam cleaned before use and between borings. Water saturated soil was first encountered at approximately 15-17 feet in each of the monitoring well borings.

Two-inch diameter schedule-40 PVC well casing with 0.020-inch slots was installed from 25 feet to 5 feet below the surface in each boring. Two-inch diameter schedule-40 PVC blank casing was installed above the slotted casing, to the surface. The well casings were capped, on the bottom with a two-inch threaded female plug and on top with a two inch locking security plug. The annular space of the wells was packed with No. 3 Monterey sand from the bottom of the borings to 4.5 feet below the surface. 2.0 feet of bentonite clay was placed above the sand packs. Class "H" Portland Cement was placed above the bentonite seals, to the surface. The well heads were secured with concrete vaulted, water-tight, locking, steel, street boxes. Monitoring Well Logs details are provided in Appendix D.

The ground water wells were developed on October 2, 1992, using a 2-inch PVC bailer. The wells were initially surged to correct any sand pack bridging which may have occurred, and to remove any "fines" from the sand pack. Approximately 50 gallons of water was bailed from each well and placed in 55-gallon 17H steel drums for temporary on-site storage.

5.0 SOIL SAMPLE COLLECTION AND CHEMICAL ANALYSIS

Soil samples were collected in groundwater monitoring well MW-1, at 5. 10, and 15 foot depths. MW-2 and MW-3 soil borings were collected at 5, 10, and 15 foot depths. Soil Borings SB-1 and SB-2 (see Figure 2, Site Plan) had soil samples collected at 10 feet only. The samples were collected using a two-inch I.D. California split-spoon sampler holding three pre-cleaned two-inch O.D. by six-inch length sample tubes. tube nearest the shoe from each sample interval was secured with double thickness aluminum foil, plastic end caps, and tape then immediately placed in an ice chest containing "blue" ice for cold storage. The next sample tube nearest the shoe was emptied into a zip-loc plastic storage bag and placed in sunlight, to enhance the volatilization of organic carbon from the soil matrix. After approximately 1/2 hour, the sample was screened in the field with a "Gastechtor Super Surveyor", model No. 1314. The Gastechtor is equipped with a combustible gas sensor calibrated with hexane.

The soil samples were submitted to Priority Environmental Labs located in Milpitas, California for definitive chemical analysis. Soil samples from MW-1, SB-1, and SB-2 were analyzed for TPH as diesel, BTEX, Oil & Grease, Purgeable Halocarbons, and Acid/Base Extractables, by EPA methods 3550/8015, 8020; 5520 D&F; 8010; and 8270 respectively, (the 15 foot MW-1 sample was the only soil sampled submitted for analysis by 8270). MW-2 and MW-3 soil samples were analyzed for Volatile Organics, Purgeable Halocarbons, and BTEX by EPA methods 8240, 8010, and 8020 respectively. Priority Environmental Laboratory is CSDHS certified for the chemical analyses preformed for this investigation. The chemical analyses provided by Priority Environmental Laboratory regarding soil samples are provided below as tables 1 & 2. Copies of the Soil laboratory analytical reports and sample chain-of-custody documents are provided in Appendix B.

TABLE 1
Summary of Chemical Analysis of SOIL Samples
TPH Diesel, BTEX, and Oil & Grease
EPA Methods 3550/8015, 8020, and 5520 D&F

Sample I.D.	TPH Diesel (ppm)	Benzene (ppb)	Toluene (ppb)	Ethyl Benzene (ppb)	Total Xylenes (ppb)	Oil & Grease (ppm)
MW-1-10'	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
MW-2-10'		N.D.	N.D.	N.D.	N.D.	
MW-2-15'		N.D.	N.D.	N.D.	N.D.	
MW-3-5'		N.D.	N.D.	N.D.	N.D.	
MW-3-15'		N.D.	N.D.	N.D.	N.D.	
SB-1-10'	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
SB-2-10'	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
EPA METHOD	3550/ 8015	8020	8020	8020	8020	5520 D&F
ND ppm ppb	Non Detection parts per parts per	table at an million billion	alytical m	ethod limit	s	

TABLE 2
Summary of Chemical Analysis of SOIL Samples
Purgeable Halocarbons, and Volatile Organics
EPA Methods 8010, and 8240

	MW-2-5' (ppb)	MW-2-15' (ppb)
CONSTITUENT		
TRICHLOROFLOROMETHANE	13	
1,1-DICHLOROETHENE		2.9
CHLOROFORM		11
EPA METHOD	8240	8010
ppb parts per billion not analyzed		

not analyzed

*All other constituents tested for as part of these methods were found to be N.D. See Appendix B for copies of sample results.

6.0 GROUND WATER SAMPLE COLLECTION AND CHEMICAL ANALYSIS

Ground water measurements and identification of any "free-product" were collected before any water was purged from the wells. No free product was identified and no odor could be recognized from any of the wells. One ground water sample was collected from each of the three groundwater monitoring wells on October 5, 1992, after removal of approximately five well volumes of water and 90% well recharge. well was purged using a 2-inch PVC bailer. The well purge water was placed in 55-gallon steel 17H drums and stored on site pending analytical results. The samples were collected using disposable, sterile, polyethylene, single check valve bailers. The samples were placed in pre-cleaned, sterile, 40 ml. glass VOA vials, then immediately placed in an ice chest for cold storage. They were later transported to Priority Environmental Laboratory in Milpitas, California using proper Chain-of-The Groundwater analytical Custody procedures, for chemical analysis. results and chain-of-custody records are included in Appendix C. Well Sampling Field Logs are attached in Appendix E.

The groundwater samples collected for this project were analyzed for TPH as diesel, BTEX, Oil & Grease, Volatile Organics, and Acid/Base Extractables, by EPA methods 3550/8015, 8020; 5520 D&F; 8240; and 8270 respectively, (the MW-1 sample was the only water sample submitted for analysis by 8270). The results are tabulated below in tables 3, 4 & 5; Groundwater laboratory analytical results and chain-of-custody records are attached in Appendix C.

TABLE 3
Summary of Chemical Analysis of WATER Samples
TPH as Diesel, BTEX, and Oil & Grease
EPA Methods 3510/8015, 602, and 5520 C&F

Sample I.D.	TPH Diesel (ppb)	Benzene (ppb)	Toluene (ppb)	Ethyl Benzene (ppb)	Total Xylenes (ppb)	Oil & Grease (ppm)
	~~~~~					
MW-1	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
MW-2						***
MW-3						
EPA	3510/	602	602	602	602	5520
METHOD	8015		3 3			C&F
N.D.	Non Detec	table at an	alytical m	ethod limit	S	
ppm	parts per	million				
ppb	parts per	billion				
	not analy	zed				

#### TABLE 4

Summary of Chemical Analysis of Water Samples Volatile Organics and Acid/Base Extractables EPA Methods 8240 and 8270

I.D.	All Volatile Organics	All Acid/Base Extractables
3 6337 1		N D
MW-1		N.D.
MW-2	N.D.	
MW-3	N.D.	
N.D.	Non Detectable at analytical method	limits
	not analyzed	

# TABLE 5 Summary of Chemical Analysis of Water Samples pH and Conductivity EPA Methods 9045 and 120.1

Sample I.D.	pН	Conductivity
MW-1	6.8	930
MW-2	7.0	1100
MW-3	6.7	670
EPA Method	9045	120.1

#### 7.0 GEOLOGY AND GROUNDWATER GRADIENT

The native soil types encountered while drilling were primarily composed of blue-green organic clay (CL) from approximately 1 ft. to 10 feet, from 10 to the bottom of hole depth (25 feet), brown/blue-green, silty clay was observed. Water saturated soil was first encountered during drilling at approximately 15-17 feet in the monitoring well borings. A graphical description of the soil types are provided on the well construction logs (see Appendix D).

The elevations of the tops of the well casings were surveyed relative to mean sea level (MSL) on October 1, 1992. The depths to groundwater were measured in each well on the day of the survey using a water level sounder (Solinst). Two measurements were taken in each well to confirm groundwater depth. The depth to water and the top of casing survey data were used to calculate a groundwater flow direction and gradient. A summary of the elevation data is provided below.

TABLE 6
Summary of Groundwater Well Survey Data

Well Number	Depth to Water	Top of Casing Elevation	Groundwater Elevation
MW-1	8.08 ft.	20.0 ft. AMSL	11.92 ft. AMSL
MW-2	7.45 ft.	19.21 ft. AMSL	11.76 ft. AMSL
MW-3	7.44 ft.	19.80 ft. AMSL	12.36 ft. AMSL

A three-point problem was solved for well combinations MW-1, MW-2 and MW-3. A graphic representation of the three-point problem indicating groundwater flow direction and gradient is presented in the Groundwater Gradient Map, Figure 3. The current direction of groundwater flow is west across the site at a gradient of 0.02 ft/ft.

#### 8.0 CONCLUSIONS

Based on the results of the chemical analyses, and supplemental investigative work, it is the opinion of Aqua Science Engineers, Inc. that the tank excavations and the over-excavations of contaminated soils previously conducted at the subject site during late 1991 and mid 1992 by ASE adequately removed contamination which may have posed a potential threat to groundwater at the site. Furthermore, any impact that the soil contamination may have had on groundwater appears to be insignificant at this time (groundwater samples, MW-1, MW-2, and MW-3 resulted in N.D. levels of TPH as Diesel and the fractions BTEX, Oil & Grease, Volatile Organics, and Acid/Base Extractables).

The chemical analysis of soil samples from the three monitoring wells and from the two soil borings resulted primarily in non-detectable (N.D.) levels of contamination. Only in MW-2 soil samples was any contamination detected; furthermore, the concentrations of the constituents that did appear (Trichlorofloromethane, 1,1-Dichloroethene, and Chloroform) only resulted in trace levels of contamination, 0.013 ppm being the largest.

#### 9.0 RECOMMENDATIONS

Aqua Science Engineers recommends the depth to groundwater in the wells be measured and groundwater samples be collected on a quarterly basis for a period of 1 year to confirm the findings of this investigation. The groundwater samples should be analyzed for TPH as Diesel, and the fractions BTEX using EPA Method 5030/8015, 602 in MW-1; for Volatile Organics using EPA Method 8240/624 in MW-2 and MW-3. The laboratory chosen to perform the analyses must be CSDHS certified for both of these methods. A report of quarterly findings should be produced for review by the Regional Water Quality Control Board, San Francisco Bay Region, and The Alameda County Health Care Services Agency.

#### 10.0 REPORT LIMITATIONS

The results of this investigation represent conditions at the time and specific location at which soil and groundwater samples were collected, and for the specific parameters analyzed for by the laboratory. It does not fully characterize the site for contamination resulting from sources other than the underground storage tanks at the site, or for parameters not analyzed for by the laboratory. All of the laboratory work cited in this report was prepared under the direction of independent CSDHS certified laboratory. The independent laboratory is solely responsible for the contents and conc'usions of the chemical analysis data.


Respectfully submitted,


AQUA SCIENCE ENGINEERS, INC.

David Allen

Project Manager







### APPENDIX A

Alameda County Health Care Services Agency "Direction Letter"

# ALAMEDA COUNTY HEALTH CARE SERVICES AGENCY

DAVID J. KEARS, Agency Director

RAFAT A. SHAHID, ASST. AGENCY DIRECTOR

DEPARTMENT OF ENVIRONMENTAL HEALTH
State Water Resources Control Board
Division of Clean Water Programs
UST Local Oversight Program
80 Swan Way, Rm 200
Oakland, CA 94621
(510) 271-4530

RECEIVED

SEP 2 1992 AQUA SCIENCE ENG.

September 24, 1992 STID# 1330

Mr. Ron Kessler Oliver Rubber Company 1200 :65th Street Emeryville, California 94608

Oliver Rubber Company

Dear Mr. Kessler:

RE:

The Alameda County Department of Environmental Health, Hazardous Materials Division has recently reviewed the files concerning the removal of three underground storage tanks at the referenced site. This office is also in receipt and has completed its review of the "Workplan for Groundwater Contamination Assessment" dated September 10, 1992 submitted by Aqua Science Engineers Inc.

1200 65th Street, Emeryville, California 94608

Based on this review, this department concurs with the basic elements of the workplan. However, the following issues must be addressed before the workplan can be implemented:

- * Soil sample (SW-W) collected after limited overexcavation in June 25, 1992 on the west wall of the former bunker oil underground storage tank excavation still showed considerable levels of contamination. Total petroleum hydrocarbon as diesel (130 ppm), oil & grease (450 ppm), benzene (19 ppb), toluene (6.7 ppb), xylene (33 ppb) were detected. The lateral extent of soil contamination in the area west of the former bunker oil tank excavation must be determined.
- * Stockpiled soil from the former bunker oil tank contained significant levels of semi-volatile organics, specifically 2-Methylnaphthalene (0.38 ppm). Analysis of the soil and groundwater samples collected in the area of the former bunker oil tank must include Method 8270 for Semi-Volatile Organics in addition to Total Petroleum Hydrocarbon as diesel (TPH-d), oil & grease (0 & G), and benzene, toluene, ethyl benzene, xylene (BTEX).
- * Please explain how the protocol for one soil sample per hole will be selected for laboratory testing. Soil samples must be collected every five feet as per RWQCB's guidelines. Field instruments are acceptable as a screening tools only. Any evidence of soil contamination such as odor, visual staining or field instrument readings must be verified by analysis from a state certified laboratory.



Mr. Ron Kessler RE: 1200 65th Street, Emeryville 94608 September 24, 1992 Page 2 of 3

- * Groundwater elevation readings must be performed every month for twelve consecutive months and reduced to every quarter after the first year. Groundwater monitoring wells must be sampled on a quarterly basis and analyzed for target compounds. MW-1 must be analyzed for TPH-d, BTXE, semivolatile organics (8270), oil & grease. MW-2 and MW-3 must be sampled for TPH-g, BTXE and volatile organic compounds (8240). After four quarters of non detectable levels have been achieved, the frequency of sampling events will be evaluated and/or a recommendation for signoff/case closure by RWQCB will be determined.
- * Please submit a time schedule for all phases of the investigation and remediation activities and the anticipated time when cleanup will be completed at the site.

A report must be submitted within 30 days after completion of this investigation. Until cleanup is complete, you will need to submit reports to this office and to RWQCB every three months (or at a more frequent interval, if specified at any time by either agency). In addition, the following items must be incorporated in your future reports or workplans:

- a cover letter from the responsible party or tank owner stating the accuracy of the report and whether he/she concurs with the conclusions and recommendations in the report or workplan
- site map delineating contamination contours for soil and groundwater based on recent data should be included and the status of the investigation and cleanup must be identified
- proposed continuing or next phase of investigation / cleanup activities must be included to inform this department or the RWQCB of the responsible party or tank owner's intention
- any changes in the groundwater flow direction and gradient based on the measured data since the last sampling event must be explained
- historical records of groundwater level in each well must be tabulated to indicate the fluctuation in water levels
- tabulate analytical results from all previous sampling events; provide laboratory reports (including quality control/quality assurance) and chain of custody documentation

Mr. Ron Kessler RE: 1200 65th Street, Emeryville 94608 September 24, 1992 Page 3 of 3

All reports and proposals must be submitted under seal of a California Registered Geologist or Registered Civil Engineer with a statement of qualifications for each lead professionals involved with the project. Copies of reports must also be submitted to:

Rich Hiett
RWQCB, San Francisco Bay Region
2101 Webster Street, Fourth Floor
Oakland, California 94612

Because we are overseeing this site under the designated authority of the Regional Water Quality Control Board, this letter constitutes a formal requests for technical reports pursuant to California Water Code Section 13267 (b). Any extensions of stated deadlines or changes in the workplan must be confirmed in writing and approved by this agency or RWQCB.

Please contact me at (510) 271-4530 if you have any questions concerning this letter.

Sincerely,

Susan L. Hugo

Susair II. nugo v

Senior Hazardous Materials Specialist

CC: Rafat A. Shahid, Asst. Agency Director, Environmental Health Rich Hiett, San Francisco Bay RWQCB
Mark Thomson, Alameda County District Attorney's Office
Edgar B. Howell, Chief, Hazardous Materials Division - files
David Allen - Aqua Science Engineers, Inc.
2411 Old Crow Canyon Road, # 4
San Ramon, California 94583

### APPENDIX B

California EPA Certified Laboratory
Report of Soil Samples
and
Chain of Custody Record



October 08, 1992

PEL # 9210011

AQUA SCIENCE ENGINEERS, INC.

David Allen

Re: Seven soil samples for BTEX, Diesel, and Oil & Grease analyses.

Project name: Oliver Rubber

Project location: 1200 65th St. -Emeryville, CA.

Project number: 2571

Date sampled: Oct 01, 1992

Date extracted: Oct 06-08, 1992

Date submitted: Oct 06, 1992

Date analyzed: Oct 06-08, 1992

#### RESULTS:

Ì	SAMPLE I.D.	Dieselk	Benzene		Ethyl Benzene	Total Xylenes	Oil & Grease	
,		(mg/Kg)	(ug/Kg)		(ug/Kg)	(ug/Kg)	(mg/Kg)	
	SB 1-10'	N.D.	N.D.	N. D.	17 D	N D	W D	
=	•			N.D.	N.D.	N.D.	N.D.	
	SB 2-10'	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	
	MW 1-10'	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	
	MW 2-10'		N.D.	N.D.	N.D.	N.D.		
	MW 2-15'		N.D.	N.D.	N.D.	N.D.		
l	MW 3-5'		N.D.	N.D.	N.D.	N.D.		
	MW 3-15'		N.D.	N.D.	N.D.	N.D.		
ì	Blank	N.D.	N.D.	N.D.	N.D.	N.D.	-	•
	Spiked						,	
ł	Recovery	93.4%	97.6%	102.4%	98.2%	103.5%		
	Duplicate Spiked							
	Recovery	88.2%	86.0%	80.3%	89.0%	93.5%		
i	Detection				•			
	limit	1.0	5.0	5.0	5.0	5.0	10	
ļ	Method of Analysis	3550 / 8015	8020	8020	8020	8020	5520 D & F	

vid Duong Laboratory Director

1764 Houret Court Milpitas, CA. 95035

Tel: 408-946-9636

Fax: 408-946-9663

#### CERTIFICATE OF ANALYSIS

A CONTROL OF STATE OF STATE OF CONTRACTOR OF STATE OF STA

STATE LICENSE NO. 1150

Received: 10/07/92 Reported: 10/13/92

Job #: 73991

Attn: David Duong

Priority Environmental Labs

1764 Houret Court Milpitas, CA 95035

Project: #9210011

Matrix: Soil

ACID & BASE/NEUTRAL EXTRACTABLES EPA Method 8270 (Low Level) mg/Kg

Lab I.D.: 73991-2 Client I.D.: MW1-15'

		LIMIT
ACID COMPOUNDS	CONCENTRATION	OF DETECTION
Nh 7		*
Phenol	ND<0.08	0.08
2-chlorophenol	ND<0.06	0.06
2-methyl phenol	ND<0.09	0.09
4-methyl phenol	ND<0.10	0.10
2-nitrophenol	ND<0.06	0.06
2,4-dimethylphenol	ND<0.10	0.10
2,4-dichlorophenol	ND<0.10	0.10
4-chloro-3-methylphenol	ND<0.10	0.10
2,4,5-trichlorophenol	ND<0.07	0.07
2,4,6-trichlorophenol	ND<0.08	0.08
2,4-dinitrophenol	ND<0.40	0.40
4-nitrophenol	ND<0.10	0.10
2-methyl-4,6-dinitrophenol	ND<0.10	0.10
Pentachlorophenol	ND<0.30	0.30
	•	

#### BASE/NEUTRAL COMPOUNDS

N-nitrosodimethylamine	ND<0.10	0.10
Bis(2-chloroethyl)ether	ND<0.04	0.04
1,3-dichlorobenzene	ND<0.50	0.50
1,4-dichlorobenzene	ND<0.50	0.50
1,2-dichlorobenzene	ND<0.40	0.40
Bis-(2-chloroisopropyl)ether	ND<0.20	0.20

ND = Not Detected

Jurinder Sahlfor Jaime Chow

Laboratory Director

<u> Page 1 of 3</u>

OUTSTANDING QUALITY AND SERVICE
CALIFORNIA STATE CERTIFIED LABORATORY

JC/td

41:00 ARESON RIVER KISHMUMD - A 94806 -PHONE 510) 221 311 FAX 51 J 202 (25)

#### CERTIFICATE OF ANALYSIS

STATE LICENSE NO. 1150

Received: 10/07/92 Reported: 10/13/92

Job #: 73991

Attn: David Duong

Priority Environmental Labs

Project: #9210311

Matrix: Soil

#### ACID & BASE/NEUTRAL EXTRACTABLES EPA Method 8270 - Low Level

mg/Kg

Lab I.D.: 73991-2 Client I.D.: MW1-15'

		LIMIT
BASE/NEUTRAL COMPOUNDS	CONCENTRATION	OF DETECTION
N-nitrosodi-n-propylamine	ND<0.10	0.10
Hexachloroethane	ND<0.50	0.50
Nitrobenzene	ND<0.06	0.06
Isophorone	ND<0.09	0.09
Bis-(2-chloroethoxy) methane	ND<0.10	0.10
1,2,4-trichlorobenzene	ND<0.30	0.30
Napthalene	ND<0.20	0.20
Hexachlorobutadiene	ND<0.50	0.50
2-chloronaphthalene	ND<0.05	0.05
2-methyl naphthalene	ND<0.20	0.20
4-chloroaniline	ND<0.10	0.10
2-nitroaniline	ND<0.10	0.10
3-nitroaniline	ND<0.10	0.10
4-nitroaniline	ND<0.10	0.10
Hexachlorocyclopentadiene	ND<0.20	0.20
Dimethyl phthalate	ND<0.04	0.04
Acenaphthylene	ND<0.04	0.04
Acenaphthene	ND<0.04	0.04
2,4-dinitrotoluene	ND<0.10	0.10
2,6-dinitrotoluene	ND<0.06	0.06
Diethyl phthalate	ND<0.10	0.10
4-chlorophenylphenylether	ND<0.05	0.05
Fluorene	ND<0.20	0.20
N-nitrosodiphenylamine	ND<0.09	0.09
4-bromophenylphenylether	ND<0.07	0.07

A COUNTED FOR DRIVE A COMMON THE CONTROL AND A CONTROL AND

#### CERTIFICATE OF ANALYSIS

STATE LICENSE NO. 1150

Received: 10/07/92 Reported: 10/13/92

Job #: 73991

Attn: David Duong

Priority Environmental Labs

Project: #9210011

Matrix: Soil

ACID & BASE/NEUTRAL EXTRACTABLES EPA Method 8270 - Low Level

mg/Kg

Lab I.D.: 73991-2 Client I.D.: MW1-15'

·		LIMIT
BASE/NEUTRAL COMPOUNDS	CONCENTRATION	OF DETECTION
Hexachlorobenzene	ND<0.20	0.20
Phenanthrene	ND<0.10	0.10
Anthracene	ND<0.20	0.20
Di-n-butylphthalate	ND<0.20	0.20
Fluoranthene	ND<0.50	0.50
Benzidine	ND<1	1
Pyrene	ND<0.60	0.60
Benzylbutylphthalate	ND<0.10	0.10
3,3'-dichlorobenzidine	ND<0.30	0.30
Benzo(a)anthracene	ND<0.30	0.30
Bis-(2-ethylhexyl)phthalate	ND<0.30	0.30
Chrysene	ND<0.30	0.30
Di-n-octylphthalate	ND<0.13	0.13
Benzo(b) fluoranthene	ND<0.20	0,20
Benzo(k) fluoranthene	ND<0.40	0.40
Benzo(a)pyrene	ND<0.09	0.09
Indeno(1,2,3-cd)pyrene	ND<0.20	0.20
Dibenzo(a,h)anthracene	ND<0.20	0.20
Benzo(ghi)perylene	ND<0.20	0.20

ND = Not detected



October 09, 1992

COMPOUND NAME

PEL # 9210011

AQUA SCIENCE ENGINEERS, INC. Project Name: Oliver Rubber

Attn: David Allen
Project Number: 2571

CONCENTRATION

rioject name. Oriver nubber

Project location: 1200 65th St.-Emeryville, CA.

Sample I.D.: MW 2-5'
Date Sampled: Oct 05, 1992
Date Analyzed: Oct 09, 1992

Date Submitted: Oct 06, 1992

Method of Analysis: EPA 8240

Detection limit: 5.0 ug/Kg

SPIKE RECOVERY

COMPOUND NAME	( ug/Kg )	. (%)
Chloromethane	N.D.	
Vínyl Chloride	N.D.	
Bromomethane	N.D.	
Chloroethane	N.D.	83.1
Trichlorofluoromethane	13	
1,1-Dichloroethene	N.D.	
Methylene Chloride	N.D.	· /
Trans-1,2-Dichloroethene	N.D.	
1,1-Dichloroethane	N.D.	
. Chloroform	N.D.	85.8
1,1,1-Trichloroethane	N.D.	
Carbon Tetrachloride	N.D.	80.6
1,2-Dichloroethane	N.D.	
Trichloroethene	N.D.	86.3
1,2-Dichloropropane	N.D.	
Bromodichloromethane	N.D.	92.4
2-Chloroethylvinylether	N.D.	
Trans-1,3-Dichloropropene	N.D.	<b></b> ,
Cis-1,3-Dichloropropene	N.D.	
1,1,2-Trichloroethane	N.D.	
Tetrachloroethene	N.D.	87.8
Benzene	N.D.	92.5
Dibromochloromethane	N.D.	
Toluene	N.D.	95.3
Chlorobenzene	N.D.	91.8
Ethylbenzene	N.D.	
Bromoform	N.D.	
1,1,2,2-Tetrachloroethane	N.D.	
Dichlorodifluoromethane	N.D.	
Freon 113	N.D.	102.9
M & P-Xylenes	N.D.	
0-Xylene	N.D.	
1,3-Dichlorobenzene	N.D.	
1,4-Dichlorobenzene	N.D.	
1,2-Dichlorobenzene	N.D.	

David Duong Laboratory Director

1764 Houret Court Milpitas, CA. 95035

Tel: 408-946-9636

Fax: 408-946-9663



Environmental of Artistation in July 18 1

October 08, 1992

PEL # 9210011

AQUA SCIENCE ENGINEERS, INC.

Attn: David Allen

Project name: Oliver Rubber

Project location: 1200 65th St.-Emeryville, CA

Project number: 2571

Sample I.D.: MW 2-15'

Date Submitted: Oct 06, 1992

Date Sampled: Oct 01, 1992 Date Analyzed: Oct 06-07, 1992

Detection limit: 1.0 ug/Kg

Method of Analysis: EPA 8010

COMPOUND NAME	CONCENTRATION ( ug/Kg )	SPIKĖ RECOVERY (%)
Chloromethane	N.D.	
Vinyl Chloride	N.D.	89.1
Bromomethane	N.D.	
Chloroethane	N.D.	
Trichlorofluoromethane	N.D.	` <del></del>
1,1-Dichloroethene	2.9	
Methylene Chloride	N.D.	82.6
1,2-Dichloroethene (TOTAL)	N.D.	
1,1-Dichloroethane	N.D.	
Chloroform	11	_ 90.4
1,1,1-Trichloroethane	N.D.	
Carbon Tetrachloride	N.D.	
1,2-Dichloroethane	N.D.	
Trichloroethene	N.D.	97 <b>.</b> 2
1,2-Dichloropropane	N.D.	
Bromodichloromethane	N.D.	
2-Chloroethylvinylether	N.D.	
Trans-1,3-Dichloropropene	N.D.	
Cis-1,3-Dichloropropene	N.D.	
1,1,2-Trichloroethane	N.D.	
Tetrachloroethene	N.D.	94.0
Dibromochloromethane	N.D.	
Chlorobenzen <b>e</b>	N.D.	
Bromoform	N.D.	
1,1,2,2-Tetrachloroethane	N.D.	
1,3-Dichlorobenzene	N.D.	
1,4-Dichlorobenzene	N.D.	
1,2-Dichlorobenzene	N.D.	

David Duong Laboratory Director

1764 Houret Court Milpitas. CA. 95035

Tel: 408-946-9226

Env. 400 046 0669



October 09, 1992

PEL # 9210011

AQUA SCIENCE ENGINEERS, INC.

Attn: David Allen Project Number: 2571

Project Name: Oliver Rubber

Project location:1200 65th St.-Emeryville, CA

Sample I.D.: MW 3-10' Date Sampled: Oct 05, 1992 Date Analyzed: Oct 09, 1992

Date Submitted: Oct 06, 1992

Method of Analysis: EPA 8240

Detection limit: 5.0 ug/Kg

COMPOUND NAME	CONCENTRATION ( ug/Kg )	SPIKE RECOVERY (%)
Chloromethane	N.D.	
Vinyl Chloride	N.D.	
Bromomethane	N.D.	
Chloroethane	N.D.	83.1
Trichlorofluoromethane	И-D-	
1,1-Dichloroethene	N.D.	
Methylene Chloride	N.D.	
Trans-1,2-Dichloroethene	N.D.	
1,1-Dichloroethane	N.D.	
Chloroform	N.D.	85.8
1,1,1-Trichloroethane	N.D.	
Carbon Tetrachloride	N.D.	80.6
1,2-Dichloroethane	N.D.	
Trichloroethene	N.D.	86.3
1,2-Dichloropropane	N.D.	
Bromodichloromethane	N.D.	92.4
2-Chloroethylvinylether	N.D.	
Trans-1,3-Dichloropropene	N.D.	
Cis-1,3-Dichloropropene	N.D.	
1,1,2-Trichloroethane	N.D.	
Tetrachloroethene	N.D.	87.8
Benzene	N.D.	92.5
Dibromochloromethane	N.D.	
Toluene	N.D.	95.3
Chlorobenzene	N.D.	91.8
Ethylbenzene	N.D.	
Bromoform	N.D.	
1,1,2,2-Tetrachloroethane	N.D.	*
Dichlorodifluoromethane	N.D.	
Freon 113	N.D.	102.9
M & P-Xylenes	N.D.	
O-Xylene	N.D.	~
1,3-Dichlorobenzene	N.D.	
1,4-Dichlorobenzene	N.D.	
1,2-Dichlorobenzene	N.D.	
	=	

David Duong

Laboratory Director 1764 Houret Court Milpitas,

CA. 95035

Tel: 403-946-9636

Fax: 408-946-9663



October 08, 1992

PEL # 9210011

AQUA SCIENCE ENGINEERS, INC.

Attn: David Allen

Project name: Oliver Rubber

Project location: 1200 65th St.-Emeryville, CA

Project number: 2571

Sample I.D.: MW 3-15'

Date Submitted: Oct 06, 1992

Date Sampled: Oct 01, 1992 Date Analyzed: Oct 06-07, 1992

Detection limit: 1.0 ug/Kg

Method of Analysis: EPA 8010

COMPOUND NAME	CONCENTRATION ( ug/Kg )	SPIKE RECOVERY (%)
Chloromethane	N.D.	
Vinyl Chloride	N.D.	89.1
Bromomethane	N.D.	
- Chloroethane	N.D.	mppi, diddy winify allejs allegs
Trichlorofluoromethane	N.D.	
,1,1-Dichloroethene	N.D.	
Methylene Chloride	N.D.	82.6
1,2-Dichloroethene (TOTAL)	N.D.	
1,1-Dichloroethane	N.D.	
Chloroform	N.D.	90.4
1,1,1-Trichloroethane	N.D.	
Carbon Tetrachloride	N.D.	
1,2-Dichloroethane	N.D.	
Trichloroethene	N.D.	97.2
1,2-Dichloropropane	N.D.	
Bromodichloromethane	N.D.	÷ ÷ = =
2-Chloroethylvinylether	N.D.	
Trans-1,3-Dichloropropene	N.D.	
Cis-1,3-Dichloropropene	N.D.	
1,1,2-Trichloroethane	N.D.	
Tetrachloroethene	N.D.	94.0
Dibromochloromethane	N.D.	
Chlorobenzene	N.D.	~~~~
Bromoform	N.D.	
1,1,2,2-Tetrachloroethane	N.D.	
1,3-Dichlorobenzene	N.D.	
1,4-Dichlorobenzene	N.D.	
1,2-Dichlorobenzene	N.D.	

1764 Houret Court Milpitas, CA. 95035

Tel: 408-946-9636

Fax: 408-946-9663

PEL # 9210011

Aqua Science Engineers, Inc. 2411 Old Crow Canyon Road, #4, San Ramon, CA 94583 (510) 820-9391 - FAX (510) 837-4853

# Chain of Cus' INV# 23110

DATE 10-2-92 PAGE 1 OF 1

						····							<del></del>									
						R RUBBER																
Varied alle 510. 820. 9391			91	ADD	RESS	12	دى	65		5T. E	MER	ZYVI	LLE	LA								
ANA	LYS	IS RI	EQUE	ST		6			SS		22	B&F)										
SPECIAL INST	RUCTI	ONS:				'BTEX 5-802		TICS	ARBO	ည္သ	ACTDS	S.		<u>  5</u>	1							[
REGULAR TURNAROUND		עריי	TPH CASOLINE (EPA 5030/8015)	TPH- GASOLINE/BTEX (EPA 5030/8015-8020)	TPH- DIESEL (EPA 3510/8015)	EL 0/8015) AROMA: /8020)	PURGABLE ARMATICS (EPA 602/8020) PURGABLE HALOCARBONS (EPA 601/8010) VOLATILE ORGANICS (EPA 624/8240)	BASE/NUETRALS, ( EPA 625/8270)	REASE	OIL & GREASE (EPA 5520 EMF OI LUFT METALS (5) (EPA 6010+7000)		TITLE 22 (CAM 17) (EPA 6010+7000) TCLP (EPA 1311/1310) STLC- CAM WET (EPA 1311/1310)		TY 1 TY 11 TY	14							
<del></del>	1 12	IES!	<del></del>	<del>,</del>	33.5C	503	351 351	E02	BLE 603	TI 1	NU.	552	£ 6	601	131	១ឌ	TVI SIV	7	•			ļ
SAMPLE ID.	DATE	TIME	MATRIX	NO. OF SAMPLES	тен ( ( ке а	трн- с ( ера	TPH-I	PURGA (EPA	PURGI (EPA	VOLATI (EPA	BASE/	OIL 6 (EPA	LUFT (EPA	TITLE (EPA	TCLP (EPA	STLC- (EPA	REACTI VI TY CORROSI VI TY I GNI TABI LI TY	42				
5B1-101	10/1/02	12 2000	SUIL	1			X	×				Χ										
5B2 - 10'	ι,	11	SUIL	1			×	X				X							<u> </u>			
MW1-101	-1	Ipm	SOIL	1			X	X		<u> </u>		X										
MW1-151	11	11	SUIL	1										<u> </u>				X				
MW2-51	11	10 A W	5016	1						X												
MW2-10'	ц	į l	3-16	1				X				,	<u> </u>	<u> </u>								
MW2-15'	η	11	SIL	1				X	X			, <del></del>										
MW3-51	ч	4am	SUIL	1				X					. 	<u>.</u>					<u></u> '			<u> </u>
MW3-10'	1	11	らいし							X												
MW3-15	- 11	į i	Soll	l			· · · · · · · · · · · · · · · · · · ·	Х	X												<u> </u>	<u> </u>
!																	·			<u></u>		
RELINQUISHE	DBY:		RECEI	VED BY:			REL	INQUI	SHED I	BY:		REC	EIVED	BY LA	BORA	TORY	СОМ	MENTS	<b>):</b>			
Daniel	W	L Fin										Da	roldu	KA .	> (	8 ce p	n					
(signature)		(time	e) (signati	ure)	· · · · · · · · · · · · · · · · · · ·	(time)	(sign	nature)			(time	(8181		<u></u>		(time						
DAVID AL	JEN	16/6 ل										D	Ανισ	DUC	ONG	10/06	92					
(printed name)		(date	) (printe	i namc)		(datc)	(prin	ted nar	ne)		(date)	(prin	ited nai	ne)		(date	)					
Company-	ASE		Comp	any-			Con	pany-	·			Con	ıpany-	P	٤.							

### APPENDIX C

California EPA Certified Laboratory
Report of Groundwater Samples
and
Chain of Custody Record



October 08, 1992

PEL # 9210010

AQUA SCIENCE ENGINEERS, INC.

Attn: David Allen

Re: Three water samples for BTEX, Diesel, Oil & Grease, pH and

Conductivity analyses.

Project name: Oliver Rubber

Project location: 1200 65th , Emeryville, CA.

Project number: 2571

Date sampled: Oct 05, 1992

Date extracted: Oct 06-07, 1992

Date submitted: Oct 06, 1992

Date analyzed: Oct 06-07, 1992

#### RESULTS:

	SAMPLE	pН	Conductivity	Diesel	Benzene	Toluene	Ethyl enzene	Total Xylenes	Oil & Grease
*,	I.D.		(uS)	(ug/L)	(ug/L)			(ug/L)	(mg/L)
	MW 1	6.8	930	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
	MW 2	7.0	1100						
	MW 3	6.7	670						
	Blank	7.0	0.0	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
	Spiked Recovery			93.4%	97.6%	102.4%	98.2%	103.5%	
	Detection limit	0.2	10	50	0.5	0.5	0.5	0.5	0.5
	Method of Analysis	9045	120.1	3510 8015	602	602	602	602	5520 C & F

David Duong Laboratory Director

Fax: 408-946-9663 1764 Houret Court Milpitas, CA. 95035 Tel: 408-946-9636

4136 LAKESIDE DRIVE RICHMOND, CA 94806

PHONE (510) 222 3002 FAX (510) 222-1251

#### CERTIFICATE OF ANALYSIS

STATE LICENSE NO. 1150

Received: 10/07/92 Reported: 10/13/ Job #: __73991 10/13/92

Attn: David Duong

Priority Environmental Labs

1764 Houret Court Milpitas, CA 95035

Project: #9210011 Matrix: Water

ACID & BASE/NEUTRAL EXTRACTABLES

EPA Method 625 - Water

μg/L

Lab I.D.: 73991-1 Client I.D.: MW1

ACID COMPOUNDS	CONCENTRATION	LIMIT OF DETECTION
Phenol	ND<5	5
2-chlorophenol	ND<1	1
2-nitrophenol	ND<1	ī
2,4-dimethylphenol	ND<1	1
2,4-dichlorophenol	ND<1	1
4-chloro-3-methylphenol	ND<1	1
2,4,6-trichlorophenol	ND<1	1 '
2,4-dinitrophenol	ND<2	2
4-nitrophenol	ND<2	2
2-methyl-4,6-dinitrophenol	ND<1	1
Pentachlorophenol	ND<2	2
BASE/NEUTRAL COMPOUNDS		
N-nitrosodimethylamine	ND<5	5
Bis(2-chloroethyl)ether	ND<1	1
1,3-dichlorobenzene	ND<1	1
1,4-dichlorobenzene	ND<1	ī
1,2-dichlorobenzene	ND<1	ī
Bis-(2-chloroisopropyl) ethe		ī

ND = Not detected

Jaime Chow

Laboratory Director

Page 1_of 3

JC/td

4136 LAKESIDE DRIVE RICHMOND CA 94806

PHONE (510) 222 3002 FAX (510) 222-1251

STATE LICENSE NO. 1150

TTMTT

Received: 10/07/92 Reported: 10/13/92

- Job #: 73991

Attn: David Duong

Priority Environmental Labs

Project: #9210011 Matrix: Water

#### ACID & BASE/NEUTRAL EXTRACTABLES

EPA Method 625 - Water

μg/L

Lab I.D.: 73991-1 Client I.D.: MW1

		LIMIT
BASE/NEUTRAL COMPOUNDS	<u>CONCENTRATION</u>	OF DETECTION
A		
N-nitrosodi-n-propylamine	ND<1	1
Hexachloroethane	ND<1	1 1
Nitrobenzene	ND<1	1
Isophorone	ND<1	1
Bis-(2-chloroethoxy) methane	ND<2	2
1,2,4-trichlorobenzene	ND<2	2
Napthalene	ND<3	3
Hexachlorobutadiene	ND<1	i
2-chloronaphthalene	ND<1	1 2 2 3 1 1
2-methyl naphthalene	ND<2	2
4-chloroaniline	ND<1	1
2-nitroaniline	ND<1	1
3-nitroaniline	ND<1	ī
4-nitroaniline	ND<1	1 1 1
Hexachlorocyclopentadiene	ND<1	ĩ
Dimethyl phthalate	ND<10	. 10
Acenaphthylene	ND<1	1
Acenaphthene	ND<1	1
2,4-dinitrotoluene	ND<1	1
2,6-dinitrotoluene	ND<1	1
Diethyl phthalate	ND<1	
4-chlorophenylphenylether	ND<1	<u> 1</u>
Fluorene	ND<1	ī
N-nitrosodiphenylamine	ND<1	1 1 1
4-bromophenylphenylether	ND<1	ī
Hexachlorobenzene	ND<1	ī
		-

ND = Not detected

Page 2 of 3

41 POLANTSIDE DRIVE FROM MONO CALLIAGO COMPREMA SPORT LES COMPREMANDANCES.

STATE LICENSE NO. 1150

Received: 10/07/92 Reported: 10/13/92

Job #: 73991

Attn: David Duong

Priority Environmental Labs

Project: #9210011 Matrix Water

## ACID & BASE/NEUTRAL EXTRACTABLES EPA Method 625 - Water µg/L

Lab I.D.: 73991-1 Client I.D.: MW1

BASE/NEUTRAL COMPOUNDS	CONCENTRATION	LIMIT OF DETECTION
<u>=::==/;::==1::==</u>	CONCENTION	OI DDINGIION
Phenanthrene	ND<1	1
Anthracene	ND<1	1.
Di-n-butylphthalate	ND<3	3
Fluoranthene	ND<2	2
Benzidine	ND<30	30
Pyrene	ND<3	3
Benzylbutylphthalate	ND<1	1
3,3'-dichlorobenzidine	ND<40	40
Benzo(a)anthracene	ND<1	1
Bis-(2-ethylhexyl)phthalate	ND<12	12
Chrysene	ND<2	2
Di-n-octylphthalate	ND<2	2
Benzo(b) fluoranthene	ND<3	3
Benzo(k)fluoranthene	ND<3	3
Benzo(a)pyrene	ND<1	1
Indeno(1,2,3-cd)pyrene	ND<5	5
Dibenzo(a,h)anthracene	ND<3	3 .
Benzo(ghi)perylene	ND<2	2

ND = Not detected

#### Page 3 of 3



October 09, 1992

PEL # 9210010

AQUA SCIENCE ENGINEERS, INC. Project Name: Oliver Rubber

Sample I.D.: MW 2

Date Sampled: Oct 05, 1992 Date Analyzed: Oct 09, 1992

Method of Analysis: EPA 624

Attn: David Allen

Project Number: 2571

Project location: 1200 65th St.-Emeryville, CA

labor story

Date Submitted: Oct 06, 1992

Detection limit: 0.5 ug/L

COMPOUND NAME	CONCENTRATION ( ug/L )	SPIKE RECOVERY (%)
Chloromethane	N.D.	
Vinyl Chloride	N.D.	
Bromomethane	N.D.	
Chloroethane	N.D.	83.1
Trichlorofluoromethane	N.D.	
1,1-Dichloroethene	N.D.	
Methylene Chloride	N.D.	
Trans-1,2-Dichloroethene	N.D.	-
1,1-Dichloroethane	N.D.	
Chloroform	N.D.	85.8
1,1,1-Trichloroethane	N.D.	
Carbon Tetrachloride	N.D.	80.6
1,2-Dichloroethane	N.D.	
Trichloroethene	N.D.	86.3
1,2-Dichloropropane	N.D.	
Bromodichloromethane	N.D.	92.4
2-Chloroethylvinylether	N.D.	
Trans-1,3-Dichloropropene	N.D.	
Cis-1,3-Dichloropropene	N.D.	40 40 = = =
1,1,2-Trichloroethane	N.D.	
Tetrachloroethene	N.D.	87.8
Benzene	N.D.	92.5
Dibromochloromethane	N.D.	
Toluene	N.D.	95.3
Chlorobenzene	N.D.	91.8
Ethylbenzene	N.D.	
Bromoform	N.D.	
1,1,2,2-Tetrachloroethane	N.D.	
Dichlorodifluoromethane	N.D.	
Freon 113	N.D.	102.9
M & P-Xylenes	N.D.	
O-Xylene	N.D.	
1,3-Dichlorobenzene	N.D.	
1,4-Dichlorobenzene	N.D.	
1,2-Dichlorobenzene	N.D.	

d Duong Laboratory Director

1764 Houret Court Milpitas. CA. 95035

Tel: 408-946-9636

Fax: 408-946-9663



Environ ental - Analymai - Jab man.

October 09, 1992

PEL # 9210010

AQUA SCIENCE ENGINEERS, INC. Attn: David Allen

Project Name: Oliver Rubber

Sample I.D.: MW 3

Date Sampled: Oct 05, 1992

Date Analyzed: Oct 09, 1992

Method of Analysis: EPA 624

Project Number: 2571

Project location: 1200 65th St.-Emeryville, CA

Date Submitted: Oct 06, 1992

Detection limit: 0.5 ug/L

COMPOUND NAME	CONCENTRATION ( ug/L )	SPIKE RECOVERY (%)
Chloromethane	N.D.	
Vinyl Chloride	N.D.	
Bromomethane	N.D.	
Chloroethane	N.D.	83.1
Trichlorofluoromethane	N.D.	
1,1-Dichloroethene	N.D.	
Methylene Chloride	N.D.	
Trans-1,2-Dichloroethene	N.D.	
1,1-Dichloroethane	N.D.	
Chloroform	N.D.	85.8
1,1,1-Trichloroethane	N.D.	
Carbon Tetrachloride	N.D.	80.6
1,2-Dichloroethane	N.D.	
Trichloroethene	N.D.	86.3
1,2-Dichloropropane	N.D.	
Bromodichloromethane	N.D.	92.4
2-Chloroethylvinylether	N.D.	
Trans-1,3-Dichloropropene	N.D.	
Cis-1,3-Dichloropropene	N.D.	
1,1,2-Trichloroethane	N.D.	
Tetrachloroethene	N.D.	87.8
Benzene	N.D.	92.5
Dibromochloromethane	N.D.	
Toluene	N.D.	95.3
Chlorobenzene	N.D.	91.8
Ethylbenzene	N.D.	
Bromoform	N.D.	
1,1,2,2-Tetrachloroethane	N.D.	
Dichlorodifluoromethane	N.D.	
Freon 113	N.D.	102.9
M & P-Xylenes	N.D.	
0-Xylene	N.D.	
1,3-Dichlorobenzene	N.D.	
1,4-Dichlorobenzene	N.D.	
1,2-Dichlorobenzene	N.D.	

Laboratory Director

1764 Houret Court Milpitas, CA. 95035

Tel: 408-946-9636

Fax: 408-946-9663

PEL # 9210010

Aqua Science Engineers, Inc. 2411 Old Crow Canyon Road, #4, San Ramon, CA 94583 (510) 820-9391 - FAX (510) 837-4853

# Chain of Cust INV# 23109

DATE 10/5/92 PAGE 1 OF 1

			سنباد وي در اربار بارد	· · · · · · · · · · · · · · · · · · ·				المناكوري ويسور														
SAMPLERS (S	٠		1	(PI	HONE I	NO.)	ADDRESS 1200 6513 ST EMERYVILLE CA								-							
(Vau	eel	W					ADD	RESS	12	ں ں	651	ST EMERYVILLE CA										
ANALYSIS REQUEST					(0)			SING.		<b>S</b> 2	B&F)								<b></b>			
SPECIAL INST	RUCTI	ONS:				IEX 8020)		ICS	REEC	8	ACTIDS	ىۋ		5			,			. 푸.		
ST	ANDA	RD			3	3/B)	15)	144 (S	8 6	A 0	30	ان با	9 (5	¥ (00	10)	10,	, '					
TURNA	POU	ND	TIME	ئة	TPH-CASOLINE (EPA 5030/8015)	1PH-GASOLINE/BTEX (EPA 5030/8015-80:	TPH- DIESEL (EPA 3510/8015)	PURGABLE AROMATICS (EPA 602/8020)	PURGABLE HALOCARBONS (EPA 601/8010)	VOLATILE ORGANICS (EPA 624/8240)	BASE/NUETRALS, (EPA 625/8270)	OIL & GREASE (EPA 5520 E&F	METALS 5010+70	TITE 22 (CAM 17) (EPA 6010+7000)	1311/13	CAM WE	REACTI VI TY CORROSI VI TY I GNI TABI LI TY	8276		Conductivity		
SAMPLE ID.	DATE	TIME	MATRIX	NO. OF SAMPLES	TPH G (EPA	TPH- G ( EPA !	TPH-DIESEL (EPA 3510/	PURGA	PURGA (EPA	VOLAT (EPA	BASE/1	OIL E	LUFT METALS (5) (EPA 6010+7000)	TITE (EPA 6	1CLP (EPA 1311/1310)	STLC- CAM WET (EPA 1311/1310)	REACTI VI TY CORROSI VI T I GNI TABI LI	82	Hd	(c)		
MWI	10/5	zen	H20	4			$\times$	X				X						X	χ	χ		
MW2	11	, (	H20	1						X		~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~			<u> </u>				X	×		
MW3	11	11	H20	1			····			X									X	X		
<del></del>	<u> </u>												<u> </u>			.,						
												<del></del>	ļ	ļ	<u> </u>						-	
											<b></b>									<del></del>		
							··-															
							·	-														
												• • • • • • • • • • • • • • • • • • • •									<del></del>	
	ļi										<del></del>	<del></del>									_	
	<u> </u>	<u></u>		l	<u> </u>		<del>T</del>	<u></u>		<u> </u>	<u> </u>	T	l	<u> </u>						<del></del>	<u></u>	
RELINQUISHE	DBY:			VED BY:			REL	INQUI	SHED	BY:		1 .		BY LA			1	MENTS	:			
Vacual all gam										-		MC.	3	(r Ar								
(signature) (time) (signature) (time)			(time)	rgia)	nature)			(time)		(signature) (time)			ĺ.					1				
DAVID ALLEN 1-16										-	DAVID RUMO 14/20/12			<u></u> ]								
(printed name) (date) (printed name) (date)				(printed name) (date)			(pris	(printed name) (date)			)											
Company- ASE Company-					Company-			Company-														

# APPENDIX D

Soil Boring Logs and Well Logs

-									·		
s	SOIL BORING LOG AND MONITORING WELL CONSTRUCTION DETAILS BORING NO. SB1										
Pro	ject Name: Oli	iver Rul	bber			Projec	t Loc	t Location: 1200 65th Street, Oakland Page 1 o			Page 1 of 1
Dri	Driller: WEST HAZMAT Type of Rig: S				imco	2400 SK-1	Type and Size of	Auger: 6.	00" O.D., H.S.		
Lo	gged By: WCL	· · · - · · · ·			Date	Drilled:	10/0	1/92	Checked By: Dav	rid M. Schu	iltz, P.E.
WΑ	TER AND WEL	LL DAT	Ä				Tota	Depth of W	ell Completed: N/A		
Dep	th of Water Fin	st Enco	unte	red:N/	'A		Well	Screen Type	and Diameter: N	/A	-
Stat	ic Depth of Wa	ter in V	Vell:	N/A.			Well	Screen Slot	Size:N/A		
Tota	al Depth of Bori	ng: 15'					Туре	and Size of	Soil Sampler: 2"	l.D., Calif.	Split-Spoon
Feet		u O	SOI	JROC	K SAMP	LE DATA			D'ESCRIPTION C		
Depth In F	WELLYBORING DETAIL	Description	Interval	Ç ≸	Field VOC (ppmv)	Graphic Log	Depth in Fo		classification, te stiffness, odor-stal With		•
6		ă	Ĕ	Blow	를 G	ପ୍ର	De	(40-50%)		(25-10%)	
-0 (							-0	Approxim	ately 4" of asph	alt	
<b> </b>								Dark Gra	ay Ciay (CL) from	2 to 5 fe	et
-	1						-				
-							7				
<b>-</b> 5					< 10		Blue-Green Clay (CL), some plant matter, cobbles, slight moisture, no odor			mattter,	
[											
}							}				
-							}		•		
10					< 10		10 1		clay (CL), some p noisture, no odor		er
							1	<b>g</b>			
-							1				
-							1				
-15						11611	15	E .	clay (CL), some ebbles, no odor	plant mat	ter, very moist
t					į		t	EOH =			
-							-				
-20						-					
E											
-25	25										
AS	ASE FORM 20A AQUA SCIENCE ENGINEERS, INC.										

SOIL BORING LOG AND MONITORING WELL CONSTRUCTION DETAILS BORING NO. SB2													
Project Name: Oliver Rubber Project							ct Location: 1200 65th Street, Oakland Page 1 of 1						
Driller: WEST HAZMAT Type of Rig: S					of Rig: S	Simco 2400 SK-1 Type and Size of Auger: 6.00" O.D., H.S.							
Logged By: WCL Date Drilled:					10/0	1/92	Checked By: Dav	/ld M. Schu	litz, P.E.				
WA	TER AND WEL	L DA	[A	<u>.</u>			Tota	Depth of W	ell Completed: N/A	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	<u></u>		
Dep	th of Water Fin	st Enco	ounte	red:N/	'A		Well	Screen Type	e and Diameter: N	/A			
Stat	ic Depth of Wa	ter in V	Veli:	N/A.			Well	Screen Slot	Size:N/A		•		
Tota	il Depth of Bori	ng: 15'	1		•		Туре	and Size of	Soil Sampler: 2"	.D., Calif.	Split-Spoon		
Feet		Ĕ	SOI	UROC	K SAMP	LE DATA	Feet	-	DESCRIPTION	FUTHOLO	ЭGY		
Depth in Fe	WELL\BORING DETAIL	Description	rval	ರ	Field VOC (ppmv)	Graphic Log	드	density,	classification, te stiffness, odor-sta	ining, USC	S designation.		
Dep	DETRIC	De	Interval	Blow	Fletc (pp	Gra L	Depth	And (40-50%)	With (40-25%)	Some (25-10%)	Trace (10-0%)		
-0						,,,,,	-0	<u>-</u>	ately 4" of asph	alt			
-							Dark Gray Clay (CL), no odor						
-											,		
-		•		-			1						
<del>-</del> 5					< 10		Blue-Green Clay (CL), some plant matter, slight moisture, no odor				mattter,		
-													
-							}						
•							}	_					
-10					< 10		10		silty clay (CL), soisture, abundant				
<b>-</b>													
-							7						
-							1						
-15						11611	1-15	1	, silty clay (CL), oist, abundant pe	-			
_								EOH =	•		<del></del> -		
_							F						
-							-						
-20 -													
_						-	E						
							-						
25	-25												
AS	SE Form 20A				AQ	UA SCI	ENC	E ENGINE	ERS, INC.	·			

·								
SOIL BORING LOG AND MONITORING WELL CONSTRUCTION DETAILS WELL NO. MW1								
Project Name: Oliver Rubber	Projec	t Location: 1200 65th Street, Oakland Page 1 of 1						
Driller: WEST HAZMAT	Type of Rig: S	imco 2400 SK-1	Type and Size of Auge	r: 6.00" O.D., H.S.				
Logged By: WCL	Date Drilled:	10/01/92	Checked By: David M.	Schultz, P.E.				
WATER AND WELL DATA		Total Depth of W	eil Completed: 25.0°					
Depth of Water First Encountered: -	15'	Well Screen Typ	e and Diameter: 2" Diam	eter Schedule 40 PVC				
Static Depth of Water in Well: 8.08' E	elow T.O.C.	Well Screen Slot	Size: 0.020*					
Total Depth of Boring: 25'		Type and Size o	f Soil Sampler: 2" I.D., C	Calif. Split-Spoon				
SOIL/ROC	K SAMPLE DATA	1 (0)	DESCRIPTION OF LIT					
	30C 30C	standard density.	classification, texture, stiffness, odor-staining,					
Description Descri	Field VOC (ppmv) Graphic Log	a And	With Som	e Trace				
Street Box	- W-	- (40 00 %	(40-25%) (25-1) (25-1) (25-1) (25-1)	0%) (10-0%)				
	Cap	-   ``						
		Dark Gr	ay Clay (CL) from 2 to	) 5 <del>(00</del> t				
1 1/2/2/2 (2/2/2/2/2/10 1 )		<b>3</b>						
Portland		- Blue Gr	oon Clay (CL) trace	cilt (= 1006)				
5 \=\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	< 10	Blue-Green Clay (CL), trace silt (* 10% slight moisture, no odor						
Blank St. "H"		1						
Class		Stati	c Water Level = 8.08'					
		}   ⁻						
10 = 88	< 10		clay (CL), with silt ( blue-green mottling, sl					
ey Sand Bentonite		no odor						
ey Si		1						
and	1///	1 .	·					
Gasing Casing			clay (CL), with silt (	¥ 40%), some				
	1////	pebble	s, very moist, no odor					
0. 3 Washed Montere)		1						
F    =    o o o	1///	7						
-20 = Ž .020 · 0	1///	20						
20 0 9	1 1///	4"						
	////	4						
2.5 E.O.H. 25 №		4-25	EDS INO					
ASE Form 20A	AQUA SC	IENCE ENGINE	eno, inc.					

				······································				WELLN	D. MWO
SOIL BORING LOG AND MONITORING WILL CONSTITUTION OF A CONTROL OF A CON									
Project Name: O				-					l
Driller: WEST HA	ZMAT			f Rig: Cl Drilled:		102	Checked By: Dav		
Logged By: WCL	· ·		Date	Drilleu.					
WATER AND WE			.c. ^		<b> </b>		ell Completed: 25.0		Schedule 40 PVC
Depth of Water Fir					-		and Diameter: 2"	Diameter .	301100010 40 1 10
Static Depth of Wa	ter in Well:	7.45' B	elow T.C	D.C.			Size: 0.020"		Cálit Casas
Total Depth of Bor					<b></b>	and Size of	Soil Sampler: 2"	<del></del>	
WELLIBORING DETAIL	\ \frac{1}{2}	BIOW Ct.	Field VOC (ppmv)	Graphic Log	Depth in Feet	standard density, And (40-50%)	DESCRIPTION C classification, te stiffness, odor-sta With (40-25%)	exture, rela	ative moisture, S designation. Trace
10 15 20 15 20 15 20 15 15 15 16 16 16 16 16 16 16 16 16 16 16 16 16	Sch. 40, 0.020" Slot PVC Casing Bentonite Seal Class "H" Portland Cement Sch. 40, 0.020" Slot PVC Casing Bentonite Seal Class "H" Portland Cement Sch. 40, 0.020" Slot PVC Casing Bentonite Seal Class "H" Portland Cement Sch. 40, 0.020" Slot PVC Casing Bentonite Seal Class "H" Portland Cement Sch. 40, 0.020" Slot PVC Casing Bentonite Seal Class "H" Portland Cement Sch. 40, 0.020" Slot PVC Casing Bentonite Seal Class "H" Portland Cement Sch. 40, 0.020" Slot PVC Casing Bentonite Seal Class "H" Portland Cement Sch. 40, 0.020" Slot PVC Casing Bentonite Seal Class "H" Portland Cement Sch. 40, 0.020" Slot PVC Casing Bentonite Seal Class "H" Portland Cement Sch. 40, 0.020" Slot PVC Casing Bentonite Seal Class "H" Portland Cement Sch. 40, 0.020" Slot PVC Casing Bentonite Seal Class "H" Portland Cement Sch. 40, 0.020" Slot PVC Casing Bentonite Seal Class "H" Portland Cement Sch. 40, 0.020" Slot PVC Casing Bentonite Seal Class "H" Portland Cement Sch. 40, 0.020" Slot PVC Casing Bentonite Seal Class "H" Portland Cement Sch. 40, 0.020" Slot PVC Casing Bentonite Seal Class "H" Portland Cement Sch. 40, 0.020" Slot PVC Casing Bentonite Seal Class "H" PVC Casing Bentonite Sch. 40, 0.020" Slot PVC Casing Bentonite Seal Class "H" PVC Casing Bentonite Sch. 40, 0.020" Slot PVC Casing Bentonite Seal Class "H" PVC Casing Bentonite Sch. 40, 0.020" Slot PVC Casing Bentonite Seal Class "H" PVC Casing Bentonite Sch. 40, 0.020" Slot PVC Casing Bentonite Seal Class "H" PVC Ca	1 1	< 10		Comment of the state of the sta	Fine, Sablue-greslight in Stati	c Water Level = Sandy, Silty, Cla with blue-green ceable odor  Silty Clay (CL), ents and pebbles,	(SP-ML-Congress) (SP-ML	-CL) some pebbles e plant
ASE FORM 20A  AQUA SCIENCE ENGINEERS, INC.									
ASE Form 20A			A	QUA S	CIENC	E ENGINE	ers, Inc.		

SOIL BORING LOG AND MON	TORING WELL	L CONSTRUCTI	ON DETAILS WELL NO	). MW3		
Project Name: Oliver Rubber	Projec	t Location: 1200	on: 1200 65th Street, Oakland Page 1 of 1			
Driller: WEST HAZMAT	Type of Rig: Cl	ME 75	ME 75 Type and Size of Auger: 8.0° O.D., H.S.			
Logged By: WCL	Date Drilled:	10/01/92	Checked By: David M. Schul	tz, P.E.		
WATER AND WELL DATA			ell Completed: 25.0'			
Depth of Water First Encountered: ~	17'		and Diameter: 2" Diameter S	chedule 40 PVC		
Static Depth of Water in Well: 7.44' B	elow T.O.C.	Well Screen Slot				
Total Depth of Boring: 25'			Soll Sampler: 2" I.D., Calif. S			
Description Descr	(ppmv) Graphic Co	standard	DESCRIPTION OF LITHOLO classification, texture, relat stiffness, odor-staining, USCS With Some (40-25%) (25-10%)	ive moisture,		
Street Box Locking Well	Сар		ately 4" of asphalt			
11114111 11114111 1D Blank Sch 40 PVC Class "H" Portland Cer 	< 10	5 moderate slight m	en Clay (CL) e, unrecognizable odor oisture c Water Level = 7.45			
Sand 2. Sand 10   1   1   1   1   1   1   1   1   1	< 10	brown tragmer	rith blue-green Clay (CL) with blue-green mottling, so its, moderately moist, eable odor	ome plant		
No. 3 Washed Monterely Slot PVC Casing Be		71 1	with slight blue-green mott t,with abundant pebbles, v	• •		
No. 3		<del></del>	Clay with silt (CL), mottlents, moderately moist, no e			
2.5 E.O.H. 25' &	2///	25 As Ab	Ove.			
ASE Form 20A	AQUA SC	ENCE ENGINE	ERS, INC.			

## APPENDIX E

Well Sampling Field Logs



# WELL SAMPLING FIELD LOG

Aqua Science Engineers, Inc. San Ramon, CA 94583

Project Name: Oliver Rubber	Co.						
Project Address: 1200 65th Str	eet, Emeryville						
Job #2571	Date of sampling:10-5-9	2					
Completed by:Dave Allen							
Well Number / Designation: _	MW-1						
Top of casing elevation:	20.0'	·					
Total depth of well casing:	25' Well diameter:	2"					
Depth to water (before sampli	ng): <u>8.08</u>						
Thickness of floating product	if any: <u>N/A</u>						
Depth of well casing in water:	16.92						
Req'd volume of groundwater	to be purged before sampling:	10 Gallons					
Approximate volume of ground	ndwater purged: 10 Callons						
Type of seal at grade: Port1	and Cement						
Type of cap on the casing:							
Is the seal water tight? Yes	Is the cap water tight? Yes						
Number of samples (container	s) collected (2) -1 Liters. (	2) 40 ml VOA					
Did 40 ml VOA vials have he	eadspace: No No						
	d after sampling & for delivery						
Are Chain of Custody docume	ents accompanying the samples:	Yes					
Sample temperature: 19°C							
Sample pH: 6.8	Test method: 9045						
	·						
Physical description of water	during initial bailing period:						
Turbid, grey							
Physical description of water	sample: Clear						
Type of analysis requested:	3510/8015						
	8020	<del></del>					
	8240	<del></del>					
-	8270	<del></del>					
Type of bailer/sampling equip	pment used: PVC & Disposable						
Parismont despotation	TCD f Hotom						
Equipment decontamination procedures: TSP & Water							
Disposition of bailed water w	oluma:						
Disposition of bailed water version of bailed water versions on site, drummed.	orume.						
Troubling on Site, didmined.							



# WELL SAMPLING FIELD LOG

Aqua Science Engineers, Inc. San Ramon, CA 94583

Project Name: Oliver Rubber Co.
Project Address: 1200 65th Street, Emeryville
Job # 2571 Date of sampling: 10-5-92
Completed by: Dave Allen
Well Number / Designation: MW-2
Top of casing elevation: 19.2'
Total depth of well casing: 25' Well diameter: 2"
Depth to water (before sampling): 7.45
Thickness of floating product if any: N/A
Depth of well casing in water:
Req'd volume of groundwater to be purged before sampling: 10 Gallons
Approximate volume of groundwater purged:10 Gallons
Type of seal at grade: Portland Cement
Type of cap on the casing: Expandable, Locking
Is the seal water tight? Yes Is the cap water tight? Yes
Number of samples (containers) collected (2) 40 ml VOA
Did 40 ml VOA vials have headspace: No
Were sample containers chilled after sampling & for delivery? Yes
Are Chain of Custody documents accompanying the samples: Yes
Sample temperature: 19°C
Sample pH: 7.0 Test method: 9045
e de la companya del la companya de
Physical description of water during initial bailing period:
Turbid, grey
Physical description of water sample: Clear
00/0
Type of analysis requested: 8240
The state of the s
Type of bailer/sampling equipment used: PVC & Disposable
TSP & Water
Equipment decontamination procedures: TSP & Water
Disposition of bailed water volume:
Remained on site, drummed



# WELL SAMPLING FIELD LOG

Aqua Science Engineers, Inc. San Ramon, CA 94583

Project Name: Oliver Rubber Co.								
Project Address: 1200 65th Street, Emeryville								
Job # Date of sampling:								
Completed by: Dave Allen								
Well Number / Designation: MW-3								
Top of casing elevation: 19.80'								
Total depth of well casing: 25' Well diameter: 2"								
Depth to water (before sampling): 7.44'								
Thickness of floating product if any: N/A								
Depth of well casing in water: 17.46'								
Req'd volume of groundwater to be purged before sampling: 10 Gallons								
Approximate volume of groundwater purged: 10 Gallons								
Type of seal at grade: Portland Cement								
Type of cap on the casing: Expandable Locking								
Is the seal water tight? Yes Is the cap water tight? Yes								
Number of samples (containers) collected (2) 40 ml VOA								
Did 40 ml VOA vials have headspace: No								
Were sample containers chilled after sampling & for delivery? Yes								
Are Chain of Custody documents accompanying the samples: Yes								
Sample temperature: 19° C								
Sample pH: 6.7 Test method: 9045								
•								
Physical description of water during initial bailing period:								
Turbid, grey								
Physical description of water sample: Clear								
Type of analysis requested: 8240								
Type of bailer/sampling equipment used: PVC & Disposable								
Equipment decontamination procedures: TSP & Water								
Disposition of bailed water volume:								
Remained on site, drummed.								

# APPENDIX F

Permits



graden to the state of the stat

15 September 1992

Aqua Science Engineers, Inc. 2411 Old Crow Canyon Road San Ramon, CA 94583

#### Gentlemen:

Enclosed is drilling permit 92444 for a monitoring well construction project at 1200 - 65th Street in Oakland for Ron Kessler.

Please note that permit condition A-2 requires that a well construction report be submitted after completion of the work. The report should include drilling and completion logs, location sketch, and permit number.

If you have any questions, please contact Wyman Hong or me at 484-2600.

Very truly yours,

Craig A. Mayfield

Water Resources Engineer III

CM:mm

Enc.

RECEIVED

្នាក់ ដូច្នេក់ ដូច្នេក

ACOM SCIENCE ENG

3199.



## DRILLING PERMIT APPLICATION

FOR APPLICANT TO COMPLETE	FOR OFFICE USE
OCATION OF PROJECT OLIVER RUBBER COMPANY 1200 65th Street Oakland, CA 94662	PERMIT NUMBER 92444 LOCATION NUMBER
CLIENT Name Mr. Ron Kessler Address 1200 65th Street Phone 510-654-7711 City Oakland, CA Zip 94662	PERMIT CONDITIONS  Circled Permit Requirements Apply
APPLICANT Name Aqua Science Engineers, Inc.  Address 2411 Old Crow Canyon Findre, #4, 820-9391 City San Ramon, CA Zip 94583  TYPE OF PROJECT Well Construction Geotechnical investigation Cathodic Protection General Water Supply Contamination Monitoring X Well Destruction  PROPOSED WATER SUPPLY WELL USE Domestic Industrial Other Municipal Irrigation  DRILLING METHOD: Mud Rotary Air Rotary Auger X Cable Other  DRILLER'S LICENSE NO. 487000  WELL PROJECTS Drill Hole Diameter 8.5 in. Maximum Casing Diameter 2.0 in. Depth 25 ft. Surface Seal Depth 5.0 ft. Number 1  GEOTECHNICAL PROJECTS Number of Borings 2 Maximum Hole Diameter 8.5 in. Depth 15 ft.  ESTIMATED STARTING DATE 9-14-92	A. BENERAL  1. A permit application should be submitted so as to arrive at the Zone 7 office five days prior to proposed starting date.  2. Submit to Zone 7 within 60 days after completion of permitted work the original Department of Water Resources Water Well Projects, or drilling logs and location sketch for geotechnical projects.  3. Permit is void if project not begun within 90 days of approval date.  B. WATER WELLS, INCLUDING PIEZOMETERS  1. Minimum surface seal thickness is two inches of cament group placed by tremie.  2. Minimum seal depth is 50 feet for municipal and inclustrial wells or 20 feet for domestic and irrigation wells unless a lesser depth is specially approved. Minimum seal depth for monitoring wells is the maximum depth practicable or 20 feet.  GEOTECHNICAL. Backfill bore hole with compacted cuttings or heavy bentonite and upper two feet with compacted material. In areas of known or suspected contamination, tremied cament grout shall be used in place of compacted cuttings.  D. CATHODIC, Fill hole above anode zone with concrete placed by tremie.  E. WELL DESTRUCTION. See attached.
ESTIMATED COMPLETION DATE 9-14-92  I hereby agree to comply with all requirements of this permit and Alarned County Ordinance No. 73-68.	Approved Wyman Hong Date 11 Sep

## APPENDIX D

Overexcavation Report December 22, 1992



December 22, 1992

# FINAL REPORT OF BUNKER-OIL OVEREXCAVATION ACTIVITIES

at
The Oliver Rubber Company
1200 65th Street
Emeryville, California

Prepared for:
Mr. Ron Kessler
The Oliver Rubber Company
1200 65th Street
Emeryville, California

Prepared by:
AQUA SCIENCE ENGINEERS, INC.
2411 Old Crow Canyon Road, #4
San Ramon, CA 94583



December 22, 1992

The Oliver Rubber Company Emeryville, CA 94662

ATTENTION: Mr. Ron Kessler

SUBJECT: Overexcavation of Former Bunker Oil Tank Excavation

Oliver Rubber Emeryville, CA

ASE JOB NO.: 2571

Mr. Kessler:

## INTRODUCTION

Aqua Science Engineers, Inc. (ASE) was contracted by our client, Oliver Rubber Company to perform overexcavation duties in the area of the former Bunker Oil tank (see Figure 1, Site Plan). The overexcavation was prompted by Ms. Susan Hugo of the Alameda County Health Care Services Agency (ACHCSA) in the form of a letter from her agency addressed to Oliver Rubber, dated December 1, 1992. In brief, the letter stated that in order to apply for and potentially receive site closure, the elevated levels of soil contamination in the direct proximity of the former bunker oil tank would need to be remediated to levels far below what was detected during original excavation activities. During initial excavation and sampling activities, three of the four excavation sidewalls of the former bunker oil excavation indicated elevated levels of diesel and oil and grease contamination as follows:

Location	Diesel (ppm)	Oil & Grease (ppm)
SW-N	490	1500
SW-S	470	1300
SW-W	130	450

Therefore, on December 18, 1992, ASE personnel mobilized on site to remediate (overexcavate and offhaul) the known areas of soil contamination.

Bunker Overex - December, 1992

## **OVEREXCAVATION**

ASE personnel, Steve DeHope, and selected subcontractors arrived on site the morning of December 18, 1992. All personnel was currently certified with 29CFR 1910.120 training. Previous soil borings and a monitoring well in the general proximity of the former excavation had delineated the extent of the contamination. It was ASE's intent to excavate from within the former excavation up to the known areas of non-contaminated soils. The removed soil would be stockpiled on site, analyzed, and appropriately disposed of at a local certified landfill.

The overexcavation activities began by removing the backfill material of the initial excavation. That material, known to be free of contamination, was stockpiled separately to be used again as backfill. A gas line was encountered during excavation; however it was determined to be "dead", and was subsequently removed. Once all the backfill material was excavated, contaminated sidewalls were excavated to the limits of the soil borings and monitoring well surrounding the excavation (see Figure 1). The dimensions of the overexcavated area grew to approximately 19 feet by 10 feet, and 8 feet deep before all of the contaminated soil appeared to have been excavated. Visual inspections along with use of a hand-held organic vapor meter (OVM 580A) were used to define the extent of the soil contamination.

## SIDEWALL SOIL SAMPLING

Ms. Susan Hugo arrived on site at approximately 2:00 p.m. to verify that the "new" excavation sidewalls were excavated to the proper limits. samples were collected by ASE personnel at locations chosen by Ms. Hugo. A soil sample was collected from each of the three excavation sidewalls (SW-N, SW-S, SW-W), and one composited soil sample was collected from The soil samples were collected in the excavated material (STKP-1A). brass tubes, covered on each end with aluminum foil, capped and sealed Each sample was then appropriately labeled and stored in a cooler with ice prior to transport to the analytical laboratory. samples were transported to Priority Environmental Labs in Milpitas, CA, a under proper chain-of-custody analytical laboratory, state certified The soil samples were analyzed for Total Petroleum Hydrocarbons as Diesel (EPA method 3550/8015), the fractions BTEX (EPA method 8020), and for Oil & Grease (EPA method 5520 D&F). The results of the soil analytical testing are tabulated below as Table One, and copies of the original laboratory report is attached in Appendix A.

TABLE ONE
Summary of Chemical Analysis of SOIL Samples
TPH Diesel, BTEX, and Oil & Grease

Sample I.D.	TPH Diesel (ppm)	Benzene (ppb)	Toluene (ppb)	Ethyl Benzene (ppb)	Total Xylenes (ppb)	Oil & Grease (ppm)
SW-N SW-S SW-W STKP-IA*	2.9 N.D. 30 36	8.4 N.D. N.D. N.D.	14 N.D. N.D. N.D.	7.3 N.D. 6.6 N.D.	24 N.D. 12 N.D.	48 N.D. N.D. 150
EPA METHOD	3550/ 8015	8020	8020	8020	8020	5520 D&F

ND	Non-Detectable a	t analytical	method	limits
ppm	parts per million			

ppb parts per billion
* Composite sample

## STOCKPILED SOIL

The excavated material (approximately 50 cubic yards) was stockpiled on site and will be loaded, trucked, and properly disposed of at a local landfill once further "soil profiling" has occurred. ASE anticipates disposal as Non-Hazardous material at a local Class III landfill. The stockpiled soil is covered with visqueen.

## BACKFILLING AND RESURFACING

The excavation was backfilled with a combination of the original backfill material and imported base rock. The excavation was backfilled to 4 inches below grade, and will be resurfaced to match existing conditions at a later date.

#### **CONCLUSIONS AND RECOMMENDATIONS**

ASE spoke with Ms. Hugo of the ACHCSA immediately after soil sample results were faxed from the laboratory to our office. The results appeared to be low enough that further action regarding the soil in the direct proximity of the former bunker oil excavation would not be necessary. Furthermore, site closure is now possible once quarterly groundwater monitoring has proven that groundwater has not been impacted by petroleum hydrocarbon contamination. ASE recommends continuing

quarterly groundwater monitoring for a period of at least one year. Site closure may be applied for pending favorable quarterly monitoring results.

## REPORT LIMITATIONS

The results of this investigation represent conditions at the time of the soil sampling and specific location at which the samples were collected, and for the specific parameters analyzed for by the laboratory.

It does not fully characterize the site for contamination resulting from sources other than the former bunker oil tank, or for parameters not analyzed for by the laboratory. All of the laboratory work cited in this report was prepared under the direction of independent CSDHS certified laboratory. The independent laboratory is solely responsible for the contents and conclusions of the chemical analysis data.

Should questions or concerns arise regarding this report, please feel free to give us a call at (510) 820-9391.

Respectfully submitted,


AOUA SCIENCE ENGINEERS, INC.

David Allen

Project Manager

cc: Ms. Susan Hugo, ACHCSA

Mr. Rich Hiett, RWQCB, San Francisco Bay Region



## APPENDIX A

CAL EPA Certified
Laboratory Analytical Results
and
Chain-of-Custody Document



latoraicry Arakita

December 21, 1992

AQUA SCIENCE ENGINEERS, INC.

Attn: Steve DeHope

Re: Four soil samples for BTEX, Diesel, and Oil & Grease analyses.

Project name: Oliver Rubber

Date sampled: Dec 18, 1992

Date extracted: Dec 19-20, 1992

Date submitted: Dec 19, 1992 Date analyzed: Dec 19-20, 1992

## RESULTS:

SAMPLE I.D.	Diesel		Toluene Ethyl Benzene	Total Xylenes	Oil & Grease	
٠	(mg/Kg)	(ug/Kg)	(ug/Kg) (ug/Kg)	(ug/Kg)	(mg/Kg)	
SW-N SW-S SW-W STKP-1A*	2.9 N.D. 30 36	8.4 N.D. N.D. N.D.	14 7.3 N.D. N.D. N.D. 6.6 N.D. N.D.	24 N.D. 12 N.D.	43 N.D. N.D. 150	
Blank	N.D.	H.D.	N.D. N.D.	N.D.	N.D.	
Spiked Recovery	104.3%	82.4%	87.6% 92.0%	90.9%		
Duplicate Spiked Recovery	90.2%	88.6}	93.5% 91.4%	102.3%	A	
Detection limit	1.0	5.0	5.0 5.0	5.0	50	
Method of Analysis	3550 / 8015	8020	8020 8020	8020	5520 D & F	

^{*} composited soil sample.

David Duong Laboratory Director

1764 Houret Court Milpitas, CA. 95035 Tel: 408-946-9636

Fax: 408-946-96:

## Priority Environmental Labs 1764 Houret Court

1764 Houret Court Milpitas, CA 95035 _ (408) 946-9636 PEL#

9212042

INV#

23278

Chain of Custody

1764 Houret Ct. Milpitas, CA. 95035 Tel: 408-946-9636 Fa.

DATE: 12 / 19 / 92 PAGE: 1 OF:

DURCT MON: 57	EVE	DeHope		es a list	n igen. In the tr	500				AT	X	SS		(EP	ORI		44		100	No.		五 万
IDRESE: 2-111	<u> </u>	W CANYON U	<i>w</i>		0,80:51	(5.28	50 18 18	ļ		1.214					i					,	- ' "	F CONTARETES
MATURE:	-ani	5 FAX		S27 23.5		10/35.23	Pr (CT POST)	100 H		75 15 15 15 15 15 15 15 15 15 15 15 15 15	<u> </u>									,	,	NUVEER OF
sample of		TIMETMATRIX	LABID	상-IIJ: (2)	3-1-1-1 3-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-	701.3K AQ),	त्र क्षात्र होत्। इतिहास	7#1 7#1		7 2.									; :			2
5W-5	12.18	5				X	$\times$	X		,			j	ر ر <del>ب س</del> نن خون				· <b>-</b>	<u> </u>			
;U-N	12-13	5	,			X		$\times$														(
W-W	12-18					$\geq$	X	$\times$			ļ					 	ļ	.,			 	1
STKP-LA	12-13					X	$\times$				-								<b>,</b> . 	   	1	7
									 	- 1		i				2						
						   		i 1		·   	<u>;</u>  ]						 		<u> </u>		<u> </u> 	
And the second s				*** An I			† ·										;     ;		<u></u>	1	:     	
and the state of t														<b></b>	<del> </del>	: : }	:  	•			L i	··
ه جنسه خه جنهن هی جنسه و داری است								i -														
	RMATION	E SEE AMPL	E RECEIPT	E SE	MEUNON STEN		etlapo		1	NECRIVED I	Ý	_	1	⊌E)H(	MeHED	EY:		2	AEC EI VED	BY:		2
HOLECT NAME:  10 (100- Run HOLECT NUMBER:	yoc.	TOTAL # OF CON	<del> </del>	? es	LIGHAT	ine		154		Darra			Dane:	SHORA	TURE:		Del		HONATU	sie:		Defe:
A COMPANY A COM	MBITA; CO		tkp		NAME: A.S.	A		Tim		DAVID COMPANY ASE			ime:	NAME					DOMPAN	(:		Time

## APPENDIX E

Quarterly Monitoring Report January 29, 1993



January 29, 1993

## QUARTERLY GROUNDWATER MONITORING REPORT SECOND QUARTER - JANUARY 18, 1993

for
The Oliver Rubber Company
1200 65th Street
Emeryville, California

Prepared for:

Mr. Ron Kessler

The Oliver Rubber Company

1200 65th Street

Prepared by:

Prepared by:

AQUA SCIENCE ENGINEERS, INC.

2411 Old Crow Canyon Road, #4

San Ramon, CA 94583

### 1.0 INTRODUCTION

Site Location (Site), See Figure 1, Site Location Map 1200 65th Street Emeryville, CA

Property Owner
The Oliver Rubber Company
1200 65th Street
Emeryville, CA
Contact: Mr. Ron Kessler
(510) 654-7711

Environmental Consulting Firm
Aqua Science Engineers, Inc.
2411 Old Crow Canyon Road, #4
San Ramon, CA 94583
Contact: David Allen, Project Manager
(510) 820-9391

Agency Review
Alameda County Health Care Services Agency (ACHCSA)
80 Swan Way, Room 350
Oakland, CA 94621
Contact: Ms. Susan Hugo

RWQCB, San Francisco Bay Region 2101 Webster Street, Fourth Floor Oakland, CA 94612 Contact: Mr. Rich Hiett

The following is a report detailing the second quarter of a four quarter groundwater monitoring program, as required by the RWQCB and the ACHCSA. Aqua Science Engineers, Inc. (ASE) has prepared this report on behalf of the property owner, The Oliver Rubber Company. This report is intended as a supplement to the following reports: "Project Report Phase II Soil and Groundwater Assessment", produced by ASE in October, 1992 where three monitoring wells were installed; "Tank Pull" reports by Aqua Science Engineers, Inc. (ASE) dated December 5, 1991 and July 16, 1992. The December 5, 1991 report details the removal of 2 8,000 gallon, underground, steel, non-halogenated organic solvent tanks; the July 16, 1992 report details the removal of 1 1,000 gallon, underground, steel "Bunker Oil" tank.

### 2.0 SITE BACKGROUND

## 2.1 Physical Location

The site is located at the corner of 65th Street at Hollis Street. The site is approximately 1/16 mile west of Interstate 80, and 1/16 mile south of Highway 13, within the City limits of Emeryville, California. The site is currently used as a manufacturing setting for rubber products. The topography of the immediate area is generally even and located at approximately 20 feet above mean sea level. (see Figure 1: Site Location Map).

## 2.2 Background and Site History

Between December 5, 1991 and July 16, 1992, (3) underground storage tanks were removed from the property by ASE; two of the tanks had 8,000 gallon capacities and contained non-halogenated solvents; one of the tanks had a 1,000 gallon capacity, and contained bunker oil. Underground tank removal activities were documented by ASE in a reports referenced in the previous sections. Detectable levels of Petroleum Hydrocarbons (TPH) as Diesel, Oil and Grease, and several constituents of Volatile Organics were found in the sidewalls of both excavations upon backfilling activities. It was determined that groundwater monitoring wells would be necessary to investigate the possibility of groundwater contamination due to leaking tanks.In October of 1992, three groundwater monitoring wells were installed, developed and sampled for chemical contamination. The results of this investigation can be found in the October 1992, ASE report.

## 2.3 General Geology/Hydrogeology

The site rests on unconsolidated sediments primarily composed of clay.

The eastern shoreline of the San Francisco Bay is located approximately

1/16 mile west of the site. Shallow groundwater in the area is located approximately 10-12 feet below grade at the site, and flows in a westerly direction towards the San Francisco Bay.

- 2 -

#### 3.0 DRILLING AND GROUNDWATER WELL CONSTRUCTION

A total of three wells were installed at the site on October 1, 1992. The locations of the ground water monitoring wells (MW-1, MW-2, and MW-3) are indicated in Figure 2, Site Plan. The soil borings for well installation were drilled to 25 feet below ground surface using a CME-75 drill rig equipped with 8 inch O.D. continuous flight, hollow stem augers. All drilling equipment was steam cleaned before use and between borings. Water saturated soil was first encountered at approximately 15-17 feet in each of the monitoring well borings.

Two-inch diameter schedule-40 PVC well casing with 0.020-inch slots was installed from 25 feet to 5 feet below the surface in each boring. Two-inch diameter schedule-40 PVC blank casing was installed above the slotted casing, to the surface. The well casings were capped, on the bottom with a two-inch threaded female plug and on top with a two inch locking security plug. The annular space of the wells was packed with No. 3 Monterey sand from the bottom of the borings to 4.5 feet below the surface. 2.0 feet of bentonite clay was placed above the sand packs. Class "H" Portland Cement was placed above the bentonite seals, to the surface. The well heads were secured with concrete vaulted, water-tight, locking, steel, street boxes.

What follows is the results of groundwater sampling and analysis during the second quarter period. Included in this section are the results of the previous quarter's results.

# 4.0 GROUND WATER SAMPLE COLLECTION AND CHEMICAL ANALYSIS

On January 18, 1993, ASE personnel arrived on site. Ground water measurements and identification of any "free product" were collected before any water was purged from the wells. No free product was identified and no odor could be recognized from any of the wells. One ground water sample was collected from each of the three groundwater monitoring wells after removal of approximately five well volumes of water and 90% well recharge. The well was purged using a 2-inch PVC bailer. The well purge water was placed in 55-gallon steel 17H drums and stored on site pending analytical results. The samples were collected using disposable, sterile, polyethylene, single check valve bailers. The samples were placed in pre-cleaned, sterile, 40 ml. glass VOA vials, then immediately placed in an ice chest for cold storage. They were later transported to Priority Environmental Laboratory in

Milpitas, California using proper Chain-of-Custody procedures, for chemical analysis. The Groundwater analytical results and chain-ofcustody records are included in Appendix A. Well Sampling Field Logs are attached in Appendix B.

The groundwater samples collected for this quarter were analyzed for all or a combination of the following: TPH as Gasoline, TPH as Diesel, BTEX, Oil & Grease, Volatile Organics, pH, and Conductivity. The results are tabulated below in tables One, Two and Three. These tables also contain results from the previous quarter.

TABLE ONE Summary of Chemical Analysis of WATER Samples TPH as Gas, Diesel, BTEX, and Oil & Grease EPA Methods 5030/8015, 3510/8015, 602, and 5520 C&F

Sample I.D.	TPH Gas (ppb)	TPH Diesei (ppb)	Benzene (ppb)	Toluene (ppb)	Ethyl Benzene (ppb)	Total Xylenes (ppb)	Oil & Grease (ppm)
10/5/92							
MW-1		N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
MW-2		IX.D.	н.р.	IA.D.	R.D.	II.D.	N.D.
	<b></b>		~~~				
MW-3							
1/18/93							
MW-1		N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
MW-2	N.D.		N.D.	N.D.	N.D.	N.D.	
MW-3	N.D.	., :,=== ·	N.D.	N.D.	N.D.	N.D.	
EPA METHOD	5030/ 8015	3510/ 8015	602	602	.602	602	5520 C&F

N.D. Non Detectable at analytical method limits

ppm, a parts per million pp b parts per billion not analyzed

Quarterly Groundwater Monitoring Report - January 18, 1993

## TABLE TWO

# Summary of Chemical Analysis of Water Samples Volatile Organics EPA Method 624

Sample I.D.	All Volatile Organics
10/5/92	
MW-1 ***	
MW-2	N.D.
MW-3	N.D.
1/18/93	
MW-1	~~*
MW-2	N.D.
MW-3	N.D.
EPA METHOD	624
N.D.	Non Detectable at analytical method limits not analyzed

## TABLE THREE

## Summary of Chemical Analysis of Water Samples pH and Conductivity EPA Methods 9045 and 120.1

Sample I.D.		pН	-	Conductivity
	÷			
10/5/92				
MW-1		6.8		930
MW-2		7.0	_	1100
MW-3		6.7	<b>:.</b>	670
1/18/93	-		•	
MW-1		6.6	-,	1000
MW-2	<del></del>	6.7		1030
MW-3	•	6.7	_ <del></del>	- 650
EPA METHOD	····	9045		120.1

- 5 -

#### 5.0 GROUNDWATER GRADIENT AND DIRECTION

The elevations of the tops of the well casings were surveyed relative to mean sea level (MSL) several days after their installation. The depths to groundwater were measured in each well on January 18,1993 using a water level sounder (Solinst). Two measurements were taken in each well to confirm groundwater depth. The depth to water and the top of casing survey data were used to calculate a groundwater flow direction and gradient. A summary of the elevation data is provided below for the January 18 sampling date.

TABLE FOUR
Summary of Groundwater Well Survey Data

Well Number	Water	Top of Casing Elevation	Elevation
MW-1	4.0 ft.	20.0 ft. AMSL	16.00 ft. AMSL
MW-2	3.8 ft.	19.21 ft. AMSL	15.41 ft. AMSL
MW-3	3.46 ft.	19.80 ft. AMSL	16.34 ft. AMSL

A three-point problem was solved for well combinations MW-1, MW-2 and MW-3. A graphic representation of the three-point problem indicating groundwater flow direction and gradient is presented in the Groundwater Gradient Map, Figure 3. The current direction of groundwater flow is west across the site at a gradient of 0.013 ft/ft. Previously, the groundwater gradient was calculated as flowing west at 0.02 ft/ft.

ASE has been conducting monthly groundwater level measurements at the site as well. The data in Table Five is as follows (IN FEET ABOVE MEAN SEA LEVEL):

# TABLE FIVE Monthly Groundwater Elevations

		MW-1	MW-2	MW-3
OCTOBER	_ 172	11.92'	11.76	12.36
NOVEMBER		<u> 12.32'</u>		12.44'
DECEMBER	=	12.54'	12.14'	12:64
JANUARY		16.00'	15.41+	16.34

#### 6.0 CONCLUSIONS

Based on the results of the chemical analyses, for the second successive quarter groundwater sampling and analysis has resulted in Non-Detectable (N.D.) levels of the constituents of which were tested.

#### 7.0 RECOMMENDATIONS

Aqua Science Engineers recommends continuing with the groundwater monitoring program. The next sampling period will occur in the month of April, 1993. Should groundwater sampling and analysis result in N.D. levels of the constituents of which are being test, ASE will recommend applying for site closure.

### 8.0 REPORT LIMITATIONS

The results of this investigation represent conditions at the time at which groundwater samples were collected, and for the specific parameters analyzed for by the laboratory. It does not fully characterize the site for contamination resulting from sources other than the underground storage tanks at the site, or for parameters not analyzed for by the laboratory. All of the laboratory work cited in this report was prepared under the direction of independent CSDHS certified laboratory. The independent laboratory is solely responsible for the contents and conclusions of the chemical analysis data.

Respectfully submitted,

AQUA SCIENCE ENGINEERS, INC.

and 1000e


David Allen


Project Manager


cc: Mr. Ron Kessler, The Oliver Rubber Company

Ms. Susan Hugo, ACHCSA

Mr. Rich Hiett, RWQCB, San Francisco Bay Region







## APPENDIX A

California EPA Certified Laboratory
Report of Groundwater Samples
and
Chain of Custody Record

January 21, 1993

 $\Gamma L \Upsilon$ 

PEL # 9301028

AQUA SCIENCE ENGINEERS, INC.

Re: Three water samples for pH, Gasoline/BTEX, Diesel, Oil & Grease, and Conductivity analyses.

Project name: Oliver Rubber

Project location: 1200 65th St. -Emeryville

Project number: 2571

Date sampled: Jan 18 1993

Date extracted: Jan 19-20, 1993

Date submitted: Jan 19, 1993 Date analyzed: Jan 19-20, 1993

RESULTS:

Method of

	SAMPLE	рH	Gasoline	Diesel	Benzene	Toluene	Ethyl Benzene	Total Xylenes	oil & Grease	Conductivity _
•	I.D.		(ug/L)	(ug/L)	(ug/L)		(ug/L)	(ug/L)	(mg/L)	นรี
	MW-1 MW-2 MW-3	6.6 6.7 6.7	N.D.	N.D.	N.D. N.D.	N.D. N.D. N.D.	N.D. N.D. N.D.	N.D. N.D. N.D.	N.D.	1000 1030 650
		7.0	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	0.0
	Spiked Recove		82.9%	94.6%	84.1%	85.5%	94.2%	91.8%	<b></b>	
•	Duplic Spike Recov	d erv	- : 93.5%	_92.7\$	96.48	98.9%	93.0\$	94.8%	·	<b></b>
<u>-</u>	Detect limi	t	05 <del>≥50</del>	<b>50</b> -	् ध <b>ा0∓5</b> _	- 0-5	-` <b>0=5</b> -	<del>- : 0:5</del> -	0- <del>5-</del>	10

David Duong

Laboratory Director

January 21, 1993

PEL # 9301028

AQUA SCIENCE ENGINEERS, INC.

Attn: Steve DeHope Project number: 2571

Project name: Oliver Rubber
Project location: 1200 65th St.,-Emeryville

A .....

Date Submitted: Jan 19, 1993

Sample I.D.: MW-2

Date Sampled: Jan 18, 1993 Date Analyzed: Jan 20-21, 1993

Detection limit: 0.5 ug/L

Method of Analysis: EPA 624 SPIKE RECOVERY CONCENTRATION (%) COMPOUND NAME ( ug/L ) N.D. Chloromethane N.D. Vinyl Chloride N.D. Bromomethane N.D. 84.6 Chloroethane N.D. Trichlorofluoromethane N.D. 1,1-Dichloroethene N.D. Methylene Chloride N.D. Trans-1,2-Dichloroethene N.D. 1,1-Dichloroethane N.D. Chloroform N.D. 1,1,1-Trichloroethane N.D. Carbon Tetrachloride N.D. 1,2-Dichloroethane N.D. Trichloroethene 1,2-Dichloropropane N.D. Bromodichloromethane N.D. 2-Chloroethylvinylether Trans-1,3-Dichloropropene Cis-1,3-Dichloropropene N.D. 1,1,2-Trichloroethane N.D. Tetrachloroethene - Dibromochloromethane chlorobenzene N.D. Ethylbenzene Bromoform 1,1,2,2-Tetrachloroethane Dichlorodifluoromethane Freon 113 N.D. M & P-Xylenes O-Xylene
N.D.

1,3-Dichlorobenzene
N.D.

1,4-Dichlorobenzene
N.D.

David Duong

January 21, 1993

PEL # 9301028

AQUA SCIENCE ENGINEERS, INC. Attn: Steve DeHope
Project name: Oliver Rubber Project number: 2571

Project location: 1200 65th St.,-Emeryville

Sample I.D.: MW-3

Date Sampled: Jan 18, 1993

Date Submitted: Jan 19, 1993

Date Analyzed: Jan 20-21, 1993

netection limit: 0.5 ug/L

Method of Analysis: EPA 624		Detection	Timic: 0.2 mg/r
COMPOUND NAME	CONCENTRATION ( ug/L )	1	SPIKE RECOVERY
Chloromethane	N.D.		
Vinyl Chloride	N.D.		81.7
Bromomethane	N.D.	• .,	
Chloroethane	N.D.		
Trichlorofluoromethane	N.D.	,	84.6
1,1-Dichloroethene	N.D.	٠	<del></del>
Methylene Chloride	N.D.	•	
Trans-1,2-Dichloroethene	N.D.	<b>:</b>	
1,1-Dichloroethane	N.D.		
Chloroform	N.D.		.83.5
1,1,1-Trichloroethane	N.D.	4	
Carbon Tetrachloride	N.D.		
1,2-Dichloroethane	N.D.		
Trichloroethene	N.D.	,	97.2
1,2-Dichloropropane	N.D.		
Bromodichloromethane	N.D.		
2-Chloroethylvinylether	N.D.		
Trans-1,3-Dichloropropene	N.D.		
Cis-1,3-Dichloropropene	N.D.		چه <del>دی</del> چه چه
1,1,2-Trichloroethane	N.D.		
Tetrachloroethene	N.D.	•	92.1
Benzene	N.D.		
Dibromochloromethane	N.D.	.,	· · · · · · · · · · · · · · · · · · ·
Toluene	N.D.	·=- '	- turniger
	N.D.		
- Ethylbenzene	N.D.		
	N.D.	÷:	98.9
1,1,2,2-Tetrachloroethane	N.D.	. "	
Dichloredifluoromethane	N.D.		
Freon 113	N.D.		94.6
M & P-Xylenes	n.d.		
0-Xylene	w.d.		
	: 15 D	<del>-</del> -	·

N.D.

David Duong
Laboratory Director

1,3-Dichlorobenzene

1,2-Dichlorobenzene

Aqua Science Engineers, Inc.
2414 Old Crow Canyon Road, #4,
San Ramon, CA 94583
(510) 820-9391 - FAX (510) 837-4853 PEL # 9301028 istody INV # 23325 DATE 1-19-93 PAGE 1 OF 1 PROJECT NAME Oliver Rubber NO. 2571 SAMPLERS (SIGNATURE) (PHONE NO.) 1510/ 820-9391 ADDRESS 1200 65 th St Emergyille ANALYSIS REQUEST PURGABLE HALOCARBOIRS PURGABLE AROMATICS (EPA 602/8020) SPECIAL INSTRUCTIONS: VOLATTLE ORGANICS (EPA 624/8240) TCLP (EPA 1311/1310) LUTT METALS (5) (EPA 6010+7000) (EPA 601/8010) PASE/INETRALS, ( EPA 625/8270) ( EFA 5520 E&F REACTIVITY CORROSTVITY TGHITMHIJIY OIL & GREASE NO. OF SAMPLE TO DATE TIME MATRIX SAMPLES COMMENTS: RECEIVED BY LABORATORY: RELINQUISHED BY: RECEIVED BY: RETINQUISHED/BY: 8 45. (fignature) (time) (signature) (time) (signature) (time) (signature) (time) 01/19/93 DAVID DUONG STEVE DOBY, 1-19-53 (printed name) (date) (printed hame) (printed name) (date) (dat :) (date) Company A.S.E. Company- PEL Company-

## APPENDIX B

Well Sampling Field Logs



Aqua Science Engineers, Inc. San Ramon, CA 94583

Project Name: Oliver Rubber Co.
Project Address: 1200 65th St., Emeryville, CA
Joh # 2571 Date of sampling: 1/18/93
Completed by: Steve DeHope
Well Number / Designation: MW-2
Ton of cosing elevation: 19.2°
Total depth of well casing: 24.6' Well diameter: 2"
Depth to water (before sampling): 3.8'
Thickness of floating product if any: N/A
Death of sual casing in water 20.8
Rea'd volume of groundwater to be purged before sampling: 15 Gallons
Approximate volume of groundwater purged: 16 Gallons
Type of seal at grade: Portland
Time of can on the casing: Expanding locking cap
Is the seal water tight? Yes Is the cap water tight? Yes
Number of samples (containers) collected
Did 40 ml VOA vials have headspace: No.
Were sample containers chilled after sampling & for delivery? Yes
Are Chain of Custody documents accompanying the samples:  Yes
Sample temperature: 19° C
Sample pH: 6.7 Test method: 9040 Conductivity: 1030 Test Method: 120.1
Physical description of water during initial bailing period: Slightly cloudy & silty
Physical description of water sample: Almost clear
Type of analysis requested: TPH Gas
BTEX
H BH
COnductivity
Type of bailer/sampling equipment used: PVC and disposable
- Equipment decontamination procedures: TSP wash, tap water ringe
Disposition of bailed water volume:



Aqua Science Engineers, Inc. San Ramon, CA 94583

Project Name: Oliver Rubber Co.
Project Address: 1200 65th St., Emeryville, CA
Job # Date of sampling:
Completed by: Steve DeHope
Well Number / Designation: MW-3
Top of casing elevation: 19.80'
Total depth of well casing: 24.66! Well diameter: 2"
Depth to water (before sampling): 3.46'
Thickness of floating product if any: N/A
Depth of well casing in water: 21.2'
Req'd volume of groundwater to be purged before sampling: 16 Gallons
Approximate volume of groundwater purged: 16 Gallons
Type of seal at grade: Portland
Type of cap on the casing: Expanding locking cap
Is the seal water tight? Yes Is the cap water tight? Yes
Number of samples (containers) collected
Did 40 ml VOA vials have headspace: No
Were sample containers chilled after sampling & for delivery? Yes
Are Chain of Custody documents accompanying the samples: Yes
Sample temperature: 19° C
Sample pH: 6.7 Test method: 9040
Conductivity: 650 Test Method" 120.1
Physical description of water during initial bailing period:  Cloudy & clearing
Physical description of water sample: Almost clear
Type of analysis requested:  TPH Gas
BTEX
₽£
Conductivity
Type of bailer/sampling equipment used: PVC and disposable
Equipment decontamination procedures: TSP wash, tap water tinse
Disposition of bailed water volume:
Drummed on site.

## APPENDIX F

Quarterly Monitoring Report May 3, 1993



May 3, 1993

## QUARTERLY GROUNDWATER MONITORING REPORT THIRD QUARTER - APRIL 16, 1993

for
The Oliver Rubber Company
1200 65th Street
Emeryville, California

Prepared for:
Mr. Ron Kessler
The Oliver Rubber Company
1200 65th Street
Emeryville, California

Prepared by:
AQUA SCIENCE ENGINEERS, INC.
2411 Old Crow Canyon Road, #4
San Ramon, CA 94583

#### 1.0 INTRODUCTION

Site Location (Site), See Figure 1, Site Location Map 1200 65th Street Emeryville, CA

Property Owner
The Oliver Rubber Company
1200 65th Street
Emeryville, CA
Contact: Mr. Ron Kessler
(510) 654-7711

Environmental Consulting Firm
Aqua Science Engineers, Inc.
2411 Old Crow Canyon Road, #4
San Ramon, CA 94583
Contact: David Allen, Project Manager
(510) 820-9391

Agency Review
Alameda County Health Care Services Agency (ACHCSA)
80 Swan Way, Room 350
Oakland, CA 94621
Contact: Ms. Susan Hugo

RWQCB, San Francisco Bay Region 2101 Webster Street, Fourth Floor Oakland, CA 94612 Contact: Mr. Rich Hiett

The following is a report detailing the third quarter of a four quarter groundwater monitoring program, as required by the RWQCB and the ACHCSA. Aqua Science Engineers, Inc. (ASE) has prepared this report on behalf of the property owner, The Oliver Rubber Company. This report is intended as a supplement to the following reports: "Project Report - Phase II Soil and Groundwater Assessment", produced by ASE in October, 1992 where three monitoring wells were installed; "Tank Pull" reports by Aqua Science Engineers, Inc. (ASE) dated December 5, 1991 and July 16, 1992. The December 5, 1991 report details the removal of 2 - 8,000 gallon, underground, steel, non-halogenated organic solvent tanks; the July 16, 1992 report details the removal of 1 - 1,000 gallon, underground, steel "Bunker Oil" tank.

Quarterly Groundwater Monitoring Report - April 16, 1993

#### 2.0 SITE BACKGROUND

### 2.1 Physical Location

The site is located at the corner of 65th Street at Hollis Street. The site is approximately 1/16 mile west of Interstate 80, and 1/16 mile south of Highway 13, within the City limits of Emeryville, California. The site is currently used as a manufacturing setting for rubber products. The topography of the immediate area is generally even and located at approximately 20 feet above mean sea level. (see Figure 1: Site Location Map).

## 2.2 Background and Site History

Between December 5, 1991 and July 16, 1992, (3) underground storage tanks were removed from the property by ASE; two of the tanks had 8,000 gallon capacities and contained non-halogenated solvents; one of the tanks had a 1,000 gallon capacity, and contained bunker oil. Underground tank removal activities were documented by ASE in a reports referenced in the previous sections. Detectable levels of Total Petroleum Hydrocarbons (TPH) as Diesel, Oil and Grease, and several constituents of Volatile Organics were found in the sidewalls of both excavations upon backfilling activities. It was determined that groundwater monitoring wells would be necessary to investigate the possibility of groundwater contamination due to leaking tanks. In October of 1992, three groundwater monitoring wells were installed, developed and sampled for chemical contamination. The results of this investigation can be found in the October 1992, ASE report.

## 2.3 General Geology/Hydrogeology

The site rests on unconsolidated sediments primarily composed of clay. The eastern shoreline of the San Francisco Bay is located approximately 1/16 mile west of the site. Shallow groundwater in the area is located approximately 10-12 feet below grade at the site, and flows in a westerly direction towards the San Francisco Bay.

#### 3.0 DRILLING AND GROUNDWATER WELL CONSTRUCTION

A total of three wells were installed at the site on October 1, 1992. The locations of the ground water monitoring wells (MW-1, MW-2, and MW-3) are indicated in Figure 2, Site Plan. The soil borings for well installation were drilled to 25 feet below ground surface using a CME-75 drill rig equipped with 8 inch O.D. continuous flight, hollow stem augers. All drilling equipment was steam cleaned before use and between borings. Water saturated soil was first encountered at approximately 15-17 feet in each of the monitoring well borings.

Two-inch diameter schedule-40 PVC well casing with 0.020-inch slots was installed from 25 feet to 5 feet below the surface in each boring. Two-inch diameter schedule-40 PVC blank casing was installed above the slotted casing, to the surface. The well casings were capped, on the bottom with a two-inch threaded female plug and on top with a two inch locking security plug. The annular space of the wells was packed with No. 3 Monterey sand from the bottom of the borings to 4.5 feet below the surface. 2.0 feet of bentonite clay was placed above the sand packs. Class "H" Portland Cement was placed above the bentonite seals, to the surface. The well heads were secured with concrete vaulted, water-tight, locking, steel, street boxes.

What follows is the results of groundwater sampling and analysis during the third quarter period. Included in this section are the results of the previous quarter's results.

# 4.0 GROUND WATER SAMPLE COLLECTION AND CHEMICAL ANALYSIS

On April 16, 1993, ASE personnel arrived on site. Groundwater measurements and identification of any "free-product" were collected before any water was purged from the wells. No free product was identified and no odor could be recognized from any of the wells. One ground water sample was collected from each of the three groundwater monitoring wells after removal of approximately five well volumes of water and 90% well recharge. The well was purged using a 2-inch PVC bailer. The well purge water was placed in 55-gallon steel 17H drums and stored on site pending analytical results. The samples were collected using disposable, sterile, polyethylene, single check valve bailers. The samples were placed in pre-cleaned, sterile, 40 ml. glass VOA vials, then immediately placed in an ice chest for cold storage. They were later transported to Priority Environmental Laboratory in Quarterly Groundwater Monitoring Report - April 16, 1993

Milpitas, California using proper Chain-of-Custody procedures, for chemical analysis. The Groundwater analytical results and chain-of-custody records are included in Appendix A. Well Sampling Field Logs are attached in Appendix B.

The groundwater samples collected for this quarter were analyzed for all or a combination of the following: TPH as Gasoline, TPH as Diesel, BTEX, Oil & Grease, Volatile Organics, pH, and Conductivity. The results are tabulated below in Tables One, Two and Three. These tables also contain results from the previous quarter.

TABLE ONE
Summary of Chemical Analysis of WATER Samples
TPH as Gas, Diesel, BTEX, and Oil & Grease
EPA Methods 5030/8015, 3510/8015, 602, and 5520 C&F

Sample I.D.	TPH Gas (ppb)	TPH Diesel (ppb)	Benzene (ppb)	Toluene (ppb)	Ethyl Benzene (ppb)	Total Xylenes (ppb)	Oil & Grease (ppm)
10/5/03							
10/5/92		NI D	MD	ND	N.D.	N.D.	N.D.
MW-1		N.D.	N.D.	N.D.	14.15.	14.15.	
MW-2	~						
MW-3							
1/18/93 MW-1 MW-2 MW-3	N.D. N.D.	N.D. 	N.D. N.D. N.D.	N.D. N.D. N.D.	N.D. N.D. N.D.	N.D. N.D. N.D.	N.D. 
4116193							
MW-1		N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
MW-2	N.D.						
MW-3	N.D.						
EPA METHOD	5030/ 8015	3510/ 8015	602	602	602	602	5520 C&F

N.D. Non Detectable at analytical method limits

ppm parts per million ppb parts per billion --- not analyzed

## TABLE TWO

## Summary of Chemical Analysis of Water Samples Volatile Organics EPA Method 624

Sample I.D.	All Volatile Organics
10/5/92	
MW-1	
MW-2	N.D.
MW-3	N.D.
1/18/93	
MW-1	an an an
MW-2	N.D.
MW-3	N.D.
4116193	
MW-1	
MW-2	N.D.
MW-3	N.D.
EPA METHOD	624

N.D. Non Detectable at analytical method limits not analyzed

## TABLE THREE

## Summary of Chemical Analysis of Water Samples pH and Conductivity EPA Methods 9045 and 120.1

Sample I.D.	рН	Conductivity
4116193		
MW-1	6.8	810
MW-2	7.2	720
MW-3	6.9	970
EPA METHOD	9045	120.1

## 5.0 GROUNDWATER GRADIENT AND DIRECTION

The elevations of the tops of the well casings were surveyed relative to mean sea level (MSL) several days after their installation. The depths to groundwater were measured in each well on April 16,1993 using a water level sounder (Solinst). Two measurements were taken in each well to confirm groundwater depth. The depth to water and the top of casing survey data were used to calculate a groundwater flow direction and gradient. A summary of the elevation data is provided below for the April 16, 1993 sampling date.

TABLE FOUR
Summary of Groundwater Well Survey Data

Well Number	Depth to Water	Top of Casing Elevation	Groundwater Elevation
MW-1	5.1 ft.	20.0 ft. AMSL	16.00 ft. AMSL
MW-2	4.62 ft.	19.21 ft. AMSL	15.41 ft. AMSL
MW-3	4.6 ft.	19.80 ft. AMSL	16.34 ft. AMSL

A three-point problem was solved for well combinations MW-1, MW-2 and MW-3. A graphic representation of the three-point problem indicating groundwater flow direction and gradient is presented in the Groundwater Gradient Map, Figure 3. The current direction of groundwater flow is west across the site at a gradient of 0.009 ft/ft. Previously, the groundwater gradient was calculated as flowing west at 0.013 ft/ft.

#### 6.0 CONCLUSIONS

Based on the results of the chemical analyses, groundwater sampling and analysis has resulted in Non-Detectable (N.D.) levels of the constituents of which were tested.

-6-

#### 7.0 RECOMMENDATIONS

Aqua Science Engineers recommends continuing with the groundwater monitoring program. The next sampling period will occur in the month of July, 1993. Should groundwater sampling and analysis result in N.D. levels of the constituents of which are being tested for four (4) subsequent quarters, ASE will recommend applying for site closure.

#### 8.0 REPORT LIMITATIONS

The results of this investigation represent conditions at the time at which groundwater samples were collected, and for the specific parameters analyzed for by the laboratory. It does not fully characterize the site for contamination resulting from sources other than the underground storage tanks at the site, or for parameters not analyzed for by the laboratory. All of the laboratory work cited in this report was prepared under the direction of independent CSDHS certified laboratory. The independent laboratory is solely responsible for the contents and conclusions of the chemical analysis data.

Respectfully submitted,

AQUA SCIENCE ENGINEERS, INC.


David Allen


Project Manager


cc: Mr. Ron Kessler, The Oliver Rubber Company

Ms. Susan Hugo, ACHCSA

Mr. Rich Hiett, RWQCB, San Francisco Bay Region







## APPENDIX A

California EPA Certified Laboratory
Report of Groundwater Samples
and
Chain of Custody Record



Pressure - Equipmenta - Analytical -

April 19, 1993

PEL # 9304041

AQUA SCIENCE ENGINEERS, INC.

Attn: Steve DeHope

Re: Three water samples for pH, Gasoline/BTEX, Diesel, Oil &

Grease, and Conductivity analyses.

Project name: Oliver Rubber Co.

Project location: 1200 65th St., - Emeryville

Project number: 2516

Date sampled: Apr 16, 1993

Date extracted: Apr 16-17, 1993

Date submitted: Apr 16, 1993

Date analyzed: Apr 16-17, 1993

#### RESULTS:

	SAMPLE	рH	Gasoline	Diesel	Benzene	Toluene	Foluene Ethyl Total Benzene Xylene			Oll & Conductivity Grease	
Ì	I.D.		(ug/L)	(ug/L)	(ug/L)			(ug/L)		( us )	
•											
ŀ	MW-1	6.8		N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	810	
•	: MW-2 MW-3	6.9	N.D. N.D.		·					97.0	
	Blank	7.0	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	o	
	Spiked Recovery		80.4%	93.1%	90.2%	94.3%	91.6%	104.2%			
	Detection limit	n 0.0	5 50	50	0.5	0.5	0.5	0.5	0.5	10	
] ]	Method o		045 5030/ 8015	•		602	602	2 602	5520 C & F	120.1	

David Duong Laboratory Director

1764 Houret Court Milpitas. CA. 95035 Tel: 408-946-9636 Fax: 408-946-9663



Environmental Analytical Laboratory Precision

May 03, 1993

PEL # 9304041

AQUA SCIENCE ENGINEERS, INC.

Attn: Steve DeHope

Re: One water sample for pH and Conductivity analysis.

Project name: Oliver Rubber Co.

Project location: 1200 65th St., - Emeryville

Project number: 2516

Date sampled: Apr 16, 1993

Date extracted: May 03, 1993

Date submitted: Apr 16, 1993 Date analyzed: May 03, 1993

RESULTS:

SAMPLE I.D.	pН	Conductivit (us)			
MW-2	7.2	720			
Blank	7.0	0			
Detection limit	0.05	10			
Method of Analysis	9045	120.1			

-David Duong Laboratory Director

April 19, 1993

Presision Environmental Analytical Laborates # 9304041

AQUA SCIENCE ENGINEERS, INC.

Attn: Steve DeHope

Project name:Oliver Rubber Co.

Project number: 2516

Project location: 1200 65th St., - Emeryville

Sample I.D.: MW-2

Date Sampled: Apr 16, 1993

Date Analyzed: Apr 16-19, 1993

Date Submitted: Apr 16, 1993

Detection limit: 0.5 ug/L Method of Analysis: EPA 624

SPIKE RECOVERY CONCENTRATION. COMPOUND NAME (%) ( ug/L ) N.D. Chloromethane 83.1 Vinyl Chloride N.D. Bromomethane N.D. N.D. Chloroethane N.D. Trichlorofluoromethane 1,1-Dichloroethene N.D. Methylene Chloride N.D. Trans-1,2-Dichloroethene N.D. 1,1-Dichloroethane N.D. Chloroform N.D. 1,1,1-Trichloroethane N.D. Carbon Tetrachloride N.D. 1,2-Dichloroethane N.D. Trichloroethene N.D. 1,2-Dichloropropane N.D. Bromodichloromethane N.D. 2-Chloroethylvinylether N.D. Trans-1,3-Dichloropropene N.D. Cis-1,3-Dichloropropene N.D. 1,1,2-Trichloroethane N.D. Tetrachloroethene N.D. N.D. Benzene N.D. Dibromochloromethane Toluene N.D. Chlorobenzene N.D. Ethylbenzene N.D. N.D. Bromoform 1,1,2,2-Tetrachloroethane N.D. 100.9 Dichlorodifluoromethane N.D. Freon 113 N.D. M & P-Xylenes N.D. N.D. 0-Xylene 1,3-Dichlorobenzene N.D. 1,4-Dichlorobenzene N.D. 1,2-Dichlorobenzene N.D.

David Duong Laboratory Director

CA GENZE 1764 Hourst Court Milnites

Tal- 400 040 0636

Eau. ARROAR-OFFE

April 19, 1993

Precision Environmentor

Analytical Laborappez # 9304041

AQUA SCIENCE ENGINEERS, INC.

Attn: Steve DeHope

Project name:Oliver Rubber Co.

Project number: 2516

Project location: 1200 65th St., - Emeryville

Sample I.D.: MW-3

Date Sampled: Apr 16, 1993

Method of Analysis: EPA 624

Date Submitted: Apr 16, 1993

Date Analyzed: Apr 16-19, 1993

Detection limit: 0.5 ug/L

CONCENTRATION SPIKE RECOVERY COMPOUND NAME (\$) (ug/L)N.D. Chloromethane . 83.1 N.D. Vinyl Chloride N.D. Bromomethane Chloroethane N.D. N.D. Trichlorofluoromethane 87.6 1,1-Dichloroethene N.D. N.D. Methylene Chloride N.D. Trans-1,2-Dichloroethene 90.2 N.D. 1,1-Dichloroethane N.D. Chloroform 88.1 N.D. 1,1,1-Trichloroethane N.D. Carbon Tetrachloride N.D. 1,2-Dichloroethane 82.0 N.D. Trichloroethene 1,2-Dichloropropane N.D. N.D. Bromodichloromethane N.D. 2-Chloroethylvinylether N.D. Trans-1,3-Dichloropropene N.D. Cis-1,3-Dichloropropene 1,1,2-Trichloroethane N.D. N.D. Tetrachloroethene N.D. Benzene N.D. Dibromochloromethane Toluene N.D. N.D. Chlorobenzene N.D. Ethylbenzene N.D. Bromoform 1,1,2,2-Tetrachloroethane N.D. Dichlorodifluoromethane N.D. N.D. Freon 113 N.D. M & P-Xylenes N.D. O-Xylene N.D. 1.3-Dichlorobenzene 1,4-Dichlorobenzene N.D.

N.D.

David Duong Laboratory Director

1.2-Dichlorobenzene

1764 Houret Court Milbitas CA. 95035

Tel: 408-946-9636

Fay: 408-946-9663

Aqua Science Engineers, Inc. 2411 Old Crow Canyon Road, #4, San Ramon, CA 94583

# Chain of Custo INV# 23534

(510) 820-9391 - FAX (510) 837-4853 Rubber Co. NO. 2516 (PHONE NO.) SAMPLERS (SIGNATURE) PROJECT NAME OLIVEC Emenville : ADDRESS 1200 65th 5+ - (510) 820-9391 ANALYSIS REQUEST PURGABLE HALOCARBONS (EPA 601/8010) SPECIAL INSTRUCTIONS: STIC- CAM NET (EPA 5030/8015) EPA 1311/1310) BASE/NUETRALB, (EPA 625/8270) NO. OF DATE TIME MATRIX SAMPLE ID. SAMPLES 4-16 3:00 MW-1 mw-2 4-16 3.15 MW-3 4-66 2:30 RELINQUISHED BY: **RELINQUISHED BY:** RECEIVED BY LABORATORY: COMMENTS: RECEIVED BY: (time) (signature) (signature) (time) (signature) (time) (time) 2:00 m DAVID DUONG (printed name) (printed name) (printed name) (date) (date) (printed name) 4/16/93 Company-Company-ASE, 416 93 Company-

## APPENDIX B

Well Sampling Field Logs



Aqua Science Engineers, Inc. San Ramon, CA 94583

Project Name: Oliver Rubber Co.
Project Address: 1200 65th St., Emeryville, CA
Job # Date of sampling: 4/16/93
Completed by: Steve DeHope
Well Number / Designation: MW-1
Top of casing elevation: 20.0'
Total depth of well casing: 25' Well diameter: 2"
Depth to water (before sampling): 5.1'
Thickness of floating product if any: None
Depth of well casing in water: 19.9'
Req'd volume of groundwater to be purged before sampling: 16 Gallons
Approximate volume of groundwater purged: 16 Gallons
Type of seal at grade: Portland
Type of cap on the casing: Expanding locking cap
Is the seal water tight? Yes Is the cap water tight? Yes
Number of samples (containers) collected
Did 40 ml VOA vials have headspace: No.
Were sample containers chilled after sampling & for delivery? Yes
Are Chain of Custody documents accompanying the samples.
Sample temperature: 19° C
Sample pH: 6.8 Test method: 9040 Conductivity: 810 Test Method: 120.1
Physical description of water during initial bailing period:  Slightly cloudy & clearing
Physical description of water sample: Clear
Type of analysis requested: TPH Diesel
BTEX
Oil & Grease
F.:
Conductivity
Type of bailer/sampling equipment used: PVC and disposable
Equipment decontamination procedures: TSP Wash, tap water rinse
Disposition of bailed water volume:
Drummed on site.



Aqua Science Engineers, Inc., San Ramon, CA 94583

Project Name: Oliver Rubber Co.
Project Address: 1200 65th St., Emeryville, CA
Job # Date of sampling: 4/16/93
Completed by: Steve DeHope
Well Number / Designation: MW-2
Top of casing elevation: 19.2'
Total depth of well casing: 24.6' Well diameter: 2"
Depth to water (before sampling): 4.62'
Thickness of floating product if any:N/A
Depth of well casing in water: 19.98'
Req'd volume of groundwater to be purged before sampling: 16 Gallons
Approximate volume of groundwater purged: 16 Gallons
Type of seal at grade: Portland
Type of cap on the casing: Expanding locking cap
Is the seal water tight? Yes Is the cap water tight? Yes
Number of samples (containers) collected
Did 40 ml VOA vials have headspace: No.  Were sample containers chilled after sampling & for delivery? Yes
Are Chain of Custody documents accompanying the samples: Yes
Sample temperature: 19° C
• •
Sample pH: 7.2 Test method: 9040 Conductivity: 720 Test Method: 120.1
Physical description of water during initial bailing period: Slightly cloudy & silty
Physical description of water sample: Almost clear
Type of analysis requested: TPH Gas
Volatile Organics
H
<u>COnductivity</u>
Type of bailer/sampling equipment used: PVC and disposable
Equipment decontamination procedures: TSP wash, tap water rinse
Disposition of bailed water volume:  Drummed on site.



Aqua Science Engineers, Inc. San Ramon, CA 94583

Project Name: Oliver Rubber Co.
Project Address: 1200 65th St., Emeryville, CA
Job # Date of sampling:
Completed by: Steve DeHope
Well Number / Designation: MW-3
Top of casing elevation: 19.80'
Total depth of well casing: 24.66' Well diameter: 2"
Depth to water (before sampling): 4.6'
Thickness of floating product if any: N/A
Depth of well casing in water: 20.66'
Req'd volume of groundwater to be purged before sampling: 16 Gallons
Approximate volume of groundwater purged: 16 Gallons
Type of seal at grade: Portland
Type of cap on the casing: Expanding locking cap
Is the seal water tight? Yes Is the cap water tight? Yes
Number of samples (containers) collected
Did 40 ml VOA vials have headspace: No
Were sample containers chilled after sampling & for delivery?yes
Are Chain of Custody documents accompanying the samples: Yes
Sample temperature: 19° C
Sample pH: 6.9 Test method: 9040
Conductivity: 970 - Test Method" 120.1
Physical description of water during initial bailing period:
Cloudy & clearing
Physical description of water sample: Almost clear
Type of analysis requested:  TPH Gas
Volatile Organics
pН
Conductivity
Type of bailer/sampling equipment used: PVC and disposable
Equipment decontamination procedures: TSP wash, tap water rinse
Disposition of bailed water volume:  Drummed on site.
DI GENERA ON SILE.

## APPENDIX G

Quarterly Monitoring Report July 27, 1993



July 27, 1993

# QUARTERLY GROUNDWATER MONITORING REPORT FOURTH QUARTER - July 14, 1993 for

The Oliver Rubber Company 1200 65th Street Emeryville, California

Prepared for:
Mr. Ron Kessler
The Oliver Rubber Company
1200 65th Street
Emeryville, California

Prepared by:
AQUA SCIENCE ENGINEERS INC.
2411 Old Crow Canyon Road, #4
San Ramon, CA 94583

### 1.0 INTRODUCTION

Site Location (Site), See Figure 1, Site Location Map 1200 65th Street Emeryville, CA

Property Owner
The Oliver Rubber Company
1200 65th Street
Emeryville, CA
Contact: Mr. Ron Kessler
(510) 654-7711

Environmental Consulting Firm
Aqua Science Engineers, Inc.
2411 Old Crow Canyon Road, #4
San Ramon, CA 94583
Contact: David Allen, Project Manager
(510) 820-9391

Agency Review
Alameda County Health Care Services Agency (ACHCSA)
80 Swan Way, Room 350
Oakland, CA 94621
Contact: Ms. Susan Hugo

RWQCB, San Francisco Bay Region 2101 Webster Street, Fourth Floor Oakland, CA 94612 Contact: Mr. Rich Hiett

This report details the fourth quarter of a quarterly groundwater monitoring program, as required by the RWQCB and the ACHCSA. Aqua Science Engineers, Inc. (ASE) has prepared this report on behalf of the property owner, The Oliver Rubber Company. This report is intended as a supplement to the following reports: "Project Report - Phase II Soil and Groundwater Assessment", produced by ASE in October, 1992 where three monitoring wells were installed; "Tank Pull" reports by Aqua Science Engineers, Inc. (ASE) dated December 5, 1991 and July 16, 1992. The December 5, 1991 report details the removal of two 8,000-gallon, underground, steel, non-halogenated organic solvent tanks; the July 16, 1992 report details the removal of one 1,000-gallon, underground, steel "Bunker Oil" tank.

Quarterly Groundwater Monitoring Report - July 14, 1993

#### 2.0 SITE BACKGROUND

## 2.1 Physical Location

The site is located at the corner of 65th Street at Hollis Street within the city limits of Emeryville, California. The site is approximately 1/16 mile west of Interstate 80, and 1/16 mile south of Highway 13. The site is currently used as a manufacturing plant for rubber products. The topography of the immediate area is generally even and located at approximately 20 feet above mean sea level. (see Figure 1: Site Location Map).

## 2.2 Background and Site History

Between December 5, 1991 and July 16, 1992, ASE removed two 8,000gallon underground, non-halogenated solvent storage tanks and one 1.000-gallon underground bunker oil storage tank. Underground tank removal activities were documented by ASE in the reports referenced in Detectable concentrations of total petroleum the previous sections. hydrocarbons as diesel (TPH-D), oil and grease, and several volatile organic compounds were found in the sidewalls of both excavations upon backfilling activities. It was determined that groundwater monitoring wells would be necessary to investigate the possibility of groundwater contamination from the leaking tanks. In October of 1992, three groundwater monitoring wells were installed, developed and The results of this investigation can be found in the October 1992 ASE report.

## 2.3 General Geology/Hydrogeology

The site rests on unconsolidated sediments primarily composed of clay. The eastern shoreline of the San Francisco Bay is located approximately 1/16 mile west of the site. Shallow groundwater in the area is located approximately 10-12 feet below grade at the site, and flows in a westerly direction towards the San Francisco Bay.

## 3.0 DRILLING AND GROUNDWATER WELL CONSTRUCTION

Monitoring wells MW-1, MW-2 and MW-3 were installed at the site on October 1, 1992 (Figure 2, Site Plan). The soil borings for well installation were drilled to 25 feet below ground surface using a CME-75 drill rig equipped with 8-inch diameter continuous flight, hollow-stem augers. All drilling equipment was steam-cleaned prior to use and between each boring. Groundwater was first encountered at approximately 15-17 feet below ground surface in each boring.

Two-inch diameter, 0.020-inch slotted, schedule 40 PVC well screen was installed from the bottom of each boring to 5 feet below the ground Two-inch diameter schedule-40 PVC blank casing was installed above the slotted casing to the gound surface. The well casings were capped on the bottom with 2-inch diameter threaded female plugs and on top with 2-inch diameter locking security plugs. The annular space of each well was packed with No. 3 Monterey sand from the bottom of the boring to 4.5 feet below the surface. A 2-feet thick hydrated bentonite layer was placed above the sand pack. Class "H" Portland Cement was placed above the bentonite seal to the gound surface. well heads were secured with concrete vaulted, water-tight, locking, steel, street boxes.

Presented below are the methods and findings of the fourth quarter of groundwater monitoring. Also included in this section are results of the previous quarter's sampling.

# 4.0 GROUND WATER SAMPLE COLLECTION AND CHEMICAL ANALYSIS

On July 14, 1993, ASE personnel arrived on-site. After measuring and recording the depths to groundwater in MW-1, MW-2, and MW-3, ASE purged five well casing volumes of groundwater from each well using an electric PVC pump. No free product or odor was noted from any well. After each well was purged, groundwater samples were collected from the well using polyethylene bailers. These bailers were washed with TSP soap and triple rinsed before use. A bailer blank was collected from each bailer just prior to use by pouring distilled water into each bailer and then decanting the water from the bailer into a 40-ml glass volatile organic analysis (VOA) vial. The bailer blanks were then transported to the laboratory with the groundwater samples and were held pending analytical results of the groundwater samples.

The groundwater samples were decanted from the bailer into VOA vials. All samples were labeled, placed in protective foam sleeves and placed on crushed ice for transport to Priority Environmental Labs in Milpitas, California (DHS No. 1707) under chain-of-custody. The analytical reports and chain-of-custody records are included in Appendix A. Well Sampling Field Logs are attached in Appendix B. Well purge water was placed in a 55-gallon steel DOT 17H drums and stored on-site pending analytical results.

The groundwater samples collected this quarter were analyzed for all or a combination of the following: TPH-G, TPH-D, benzene, toluene, ethylbenzene and xylenes (BTEX), oil & grease, volatile organic compounds (VOCs), pH, and electrical conductivity. The results are tabulated below in Tables One, Two and Three. These tables also contain results from previous quarters.

TABLE ONE
Summary of Chemical Analysis of WATER Samples
TPH as Gas, Diesel, BTEX, and Oil & Grease
EPA Methods 5030/8015, 3510/8015, 602, and 5520 C&F

Sample I.D.	TPH Gas (ppb)	TPH Diesel (ppb)	Benzene (ppb)	Toluene (ppb)		Total Xylenes (ppb)	Oil & Grease (ppm)
10/5/92				•			
MW-1		N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
MW-2							
MW-3		<u>-</u>					
1/18/93							
MW-1		N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
MW-2	N.D.	~	N.D.	N.D.	N.D.	N.D.	
MW-3	N.D.		N.D.	N.D.	N.D.	N.D.	~
4/16/93							
MW-1		N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
MW-2	N.D.						
MW-3	N.D.				# <b></b>	~	
7114193							
MW-1		N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
MW-2	N.D.						
MW-3	N.D.						
							~ <b>~</b> ~ ~ ~ ~
EPA METHOD	5030/ 8015	3510/ 8015	602	602	602	602	5520 C&F

N.D. Non Detectable at analytical method limits ppm parts per million ppb parts per billion not analyzed

#### TABLE TWO

#### Summary of Chemical Analysis of Water Samples Volatile Organics EPA Method 624

Sample I.D.	All Volatile Organics
10/5/92	
MW-1	
MW-2	N.D.
MW-3	N.D.
1/18/93	
MW-1	
MW-2	N.D.
MW-3	N.D.
4/16/93	
MW-1	**=
MW-2	N.D.
MW-3	N.D.
7114193	
MW-1	
MW-2	N.D.
MW-3	<b>N.D.</b>
EPA METHOD	624
N.D.	Non Detectable at analytical method limits not analyzed

#### TABLE THREE

#### Summary of Chemical Analysis of Water Samples pH and Conductivity EPA Methods 9045 and 120.1

Sample		
I.D.	pН	Conductivity
		++
4116193		
MW-1	6.8	810
MW-2	7.2	720
MW-3	6.9	970
EPA METHOD	9045	120.1

#### 5.0 GROUNDWATER GRADIENT AND DIRECTION

The top of casing elevation of each well was surveyed relative to a project datum at the time of the well installation. The depths to groundwater were measured in each well on July 14, 1993 using an electric Solinst water level sounder. The top of casing elevations and July 14, 1993 depth to groundwater measurements are presented below in table four.

TABLE FOUR
Summary of Groundwater Well Survey Data

Well Number	Depth to Water (ft)	Top of Casing Elevation (project datum)	Groundwater Elevation (project elevation)
MW-1	6.82	20.00	13.18
MW-2	6.20	19.21	13.01
MW-3	6.11	19.80	13.69

Groundwater elevation contours are plotted on Figure 3. Goundwater flows to the west-southwest beneath the site at a gradient of 0.009 ft/ft which is consistent with previous results.

#### 6.0 CONCLUSIONS

No hydrocarbons or volatile organic compounds were detected in any groundwater sample.

#### 7.0 RECOMMENDATIONS

Since no hydrocarbons or volatile organic compounds have ever been detected in groundwater samples from any site well, and since the wells have now been sampled for four subsequent quarters, please consider this report as a formal request for site closure.

#### 8.0 REPORT LIMITATIONS

The results of this investigation represent conditions at the time at which groundwater samples were collected, and for the specific parameters analyzed for by the laboratory. It does not fully characterize the site for contamination resulting from sources other than the former underground storage tanks at the site, or for parameters not analyzed for by the laboratory. All of the laboratory work cited in this report was prepared under the direction of independent CSDHS certified laboratory. The independent laboratory is solely responsible for the contents and conclusions of the chemical analysis data.

Respectfully submitted,


AQUA SCIENCE ENGINEERS, INC.


Robert E. Kitay


Project Geologist

cc: Ms. Susan Hugo, ACHCSA

Mr. Rich Hiett, RWQCB, San Francisco Bay Region







### APPENDIX A

California EPA Certified Laboratory
Report of Groundwater Samples
and
Chain of Custody Record



### PRIORITY ENVIRONMENTAL LABS

Precision Environmental Analytical Laboratory

July 17, 1993

PEL # 9307036

AQUA SCIENCE ENGINEERS, INC.

Attn: David Allen

Re: Three water samples for pH, Gasoline/BTEX, Diesel, Oil &

Grease, and Conductivity analyses.

Project name: Oliver Rubber Company

Project location: 1200 65th street _ Emeryville , CA .

Project number: 2516

Date sampled: Jul 14, 1993
Date extracted: Jul 16-17, 1993

Date submitted: Jul 16, 1993

Date analyzed: Jul 16-17, 1993

#### RESULTS:

SAMPLE	pH G	asoline	Diesel	Benzene	Toluene	Ethyl	Total ( Xylenes (	)11 & C Trease	onductivity
I.D.		(ug/L)	(ug/L)	(ug/L)	(ug/L) (			(mg/L)	(uS)
MW-1	7.8	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	
MW-2 MW-3		N.D. N.D.							880 620
Blank	7.0	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	0
Spiked Recover		- 88.2%	94.1%	85.2%	87.6%	82.4%	93.0%		
Duplicat Spiked Recover		- 95.1%	93.68	s 94.81	k 96.7%	90.4	% 102.5 ⁵	<b>%</b>	
Detection limit	on 0.0	5 50	50	0.5	0.5	0.5	0.5	0.5	10
Method o		15 5030 8015	•	•	602	602	602	5520 C & F	120.1

David Duong Laboratory Director

1764 Houret Court Milpitas, CA. 95035

Tel: 408-946-9636 Fax: 408-946-9663



# PRIORITY ENVIRONMENTAL LABS

Precision Environmental Analytical Laboratory

July 19, 1993

PEL # 9307036

AQUA SCIENCE ENGINEERS, INC. Attn: David Allen
Project name :Oliver Rubber Company Project number: 2516

Project name :Oliver Rubber Company Project num Project location: 1200 65th St., - Emeryville, CA.

Sample I.D.: MW-3

Date Sampled: Jul 14, 1993 Date Analyzed: Jul 19, 1993

Method of Analysis: EPA 624

Date Submitted: Jul 16, 1993

Detection limit: 0.5 ug/L

COMPOUND NAME	CONCENTRATION	SPIKE RECOVERY				
	( ug/L )	(%)				
Acetone	N.D.					
Chloromethane	N.D.					
Vinyl Chloride	N.D.	81.2				
Bromomethane	N.D.	~~~~				
Chloroethane	N.D.					
Trichlorofluoromethane	N.D.					
1,1-Dichloroethene	N.D.	90.7				
Methylene Chloride	N.D.					
Trans-1,2-Dichloroethene	N.D.	86.4				
1,1-Dichloroethane	N.D.	83.5				
Chloroform	N.D.					
1,1,1-Trichloroethane	N.D.					
Carbon Tetrachloride	N.D.					
1,2-Dichloroethane	N.D.	91.7				
Trichloroethene	N.D.	94.3				
1,2-Dichloropropane	N.D.					
Bromodichloromethane	N.D.					
2-Chloroethylvinylether	N.D.					
Trans-1,3-Dichloropropene	N.D.					
Cis-1,3-Dichloropropene	N.D.					
1,1,2-Trichloroethane	N.D.					
Tetrachloroethene	N.D.	85.5				
Benzene	N.D.	94.1				
Dibromochloromethane	N.D.					
Toluene	N.D.	87.8				
Chlorobenzene	N.D.	93.9				
Ethylbenzene	N.D.	altin min sing take saff				
Bromoform	N.D.					
1,1,2,2-Tetrachloroethane	N.D.					
Dichlorodifluoromethane	N.D.					
Freon 113	N.D.	104.6				
M & P-Xylenes	N.D.					
O-Xylene	N.D.	90.9				
1,3-Dichlorobenzene	N.D.					
1,4-Dichlorobenzene	N.D.					
1,2-Dichlorobenzene	N.D.					

David Duong Laboratory Director

1764 Houret Court Milpitas, CA. 95035

Tel: 408-946-9636 Fax: 408-946-9663



# PRIORITY ENVIRONMENTAL LABS

Precision Environmental Analytical Laboratory

July 19, 1993

PEL # 9307036

AQUA SCIENCE ENGINEERS, INC. Attn: David Allen Project name: Oliver Rubber Company Project number: 2516

Project location: 1200 65th St., - Emeryville, CA.

Sample I.D.: MW-2

Date Sampled: Jul 14, 1993

Date Analyzed: Jul 19, 1993 Method of Analysis: EPA 624 Date Submitted: Jul 16, 1993

CRIVE DECOVERY

Detection limit: 0.5 ug/L

COMPOUND NAME	CONCENTRATION ( ug/L )	SPIKE RECOVERY (%)
Acetone	N.D.	·································
Chloromethane	N.D.	
Vinyl Chloride	N.D.	81.2
Bromomethane	N.D.	<b>→ → → → </b>
Chloroethane	N.D.	
Trichlorofluoromethane	N.D.	
1,1-Dichloroethene	N.D.	90.7
Methylene Chloride	N.D.	
Trans-1,2-Dichloroethene	N.D.	86.4
1,1-Dichloroethane	N.D.	83.5
Chloroform	N.D.	<u> </u>
1,1,1-Trichloroethane	N.D.	
Carbon Tetrachloride	N.D.	
1,2-Dichloroethane	N.D.	91.7
Trichloroethene	N.D.	94.3
1,2-Dichloropropane	N.D.	
Bromodichloromethane	N.D.	
2-Chloroethylvinylether	N.D.	
Trans-1,3-Dichloropropene	N.D.	
Cis-1,3-Dichloropropene	N.D.	
1,1,2-Trichloroethane	N.D.	
Tetrachloroethene	N.D.	85.5
Benzene	N.D.	94.1
Dibromochloromethane	N.D.	
Toluene	N.D.	87.8
Chlorobenzene	N.D.	93.9
Ethylbenzene	N.D.	
Bromoform	N.D.	
1,1,2,2-Tetrachloroethane	N.D.	
Dichlorodifluoromethane	N.D.	
Freon 113	N.D.	104.6
M & P-Xylenes	N.D.	
O-Xylene	N.D.	90.9
1,3-Dichlorobenzene	N.D.	
1,4-Dichlorobenzene	N.D.	
1,2-Dichlorobenzene	N.D.	

David Duong Laboratory Director

1764 Houret Court Milpitas, CA. 95035 Tel: 408-946-9636 Fax: 408-946-9663

Aqua Science Engineers, Inc. 2411 Old Crow Canyon Road, #4, San Ramon, CA 94583 (510) 820-9391 - FAX (510) 837-4853

# Chair

PEL # 9307036

**INV** # 23793

dy

DAIE 7-14-93 PAGE / OF /

SAMPLERS (	SIGNAT	URE)		(F	HONE	NO.)	700				1	0						PAGI	Ľ/	_OF.	<u> </u>	
Rold C.	Kit	i. 270		(510) 8	20 - 9	39 /	PRO	DECL I	NAME 12.C	0	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Ku	bbar *	ورون	pan	<u> </u>	UA	NO	2.5	516		
ANA	LYS	IS R	ЕОШ	EST			1						-171/	Emu	cy; 11	<u> </u>	UA	· <del></del>	<del></del>	71		
ANALYSIS REQUEST  SPECIAL INSTRUCTIONS:				TPH- GASOLINE ( EPA 5030/8015)	TPH- GASOLINE/BIEX (EPA 5030/8015-8020)	TPH- DIESEL (EPA 3510/8015)	PURGABLE ARCAGITUS (EPA 602/8020)	PURGABLE HALOCARBONS (EPA 601/8010)	VOLATILE ORGANICS (EPA 624/8240)	RASE/NUETRALS, ACIDS (EPA 625/8270)	OIL & GREASE (BPA 5520 E&F or B&F)	LUFT METALS (5) (EPA 6010+7000)	TITLE 22 (CAM 17) (EPA 6010+7000)	TCLP (EPA 1311/1310)	ъм Wet 11/1310)	TY TTY LLTY		Canductivity	j			
SAMPLE ID.	DATE	TIME	MATRIX	NO OF SAMPLES	TPH-G	TPH-GI	TPH-DI (EPA 3	PURGAB	PURGAB EPA 6	VOLATI EPA 6	BPSE/IN	EPA 59	EPA 60	FTLE 2 EPA 60	2LP 3PA 13	FLC- C.	REACTIVITY CORROSIVITY IGHITABILITY	40	andu	HOLD		! !
MW 1	7/1	13.50	Letitor	3		×	×				22	<del>\$</del>	7	FE	¥ 🖰	5	품 S 다					
ML: 2-	7/.4	12 25	Water	4	X		,			×								×		<b></b>		
MW 3			With	4	X					X								× X	X	<b>-</b>		
1313-1			White													······································		-				
rr) 2.	<del></del>																		X	$\dashv$		
<u>66 3</u>	7/./	17 u	1. J H. 10 -	-/																$\bigcirc$	-+	
																				$\triangle$	-	ᅴ
																					+	ᅦ
																					_	ᅱ
																					十	$\dashv$
RELINOUISHED		8:029	RECEIV	ED BY:	<u> </u>		RELIT	NQUISE	TED BY	Y:		RECE	IVEDI	BY LAI	BORAT	ORY:	сомм	ENTS:				]
/singature)				(time)	(signature) (time				(time)	fixed due For An (signature) (tine) (7/16/93				(tin c)	i							
		(date)	(printed	name)	(	(date)	(printe	d name	)		(date)	(printe	d name	e) ("') (;	07/	/6/43 (date)	[	•				
Company. AS	E	· · · · · ·	Compar	ıy-			Comp	апу-			,	Comp	4	E (-		· ·		•		٠		

### APPENDIX B

Well Sampling Field Logs



## WELL SAMPLING FIELD LOG

Aqua Science Engineers, Inc, San Ramon, CA 94583

Project Name: DLIVER Rubber
Project Address: 1200 65th Street, Emergicille  Job # 2571 Date of sampling: 7.14.73
Job # 257/ Date of sampling: 7.14.73
Completed by: KEK
Well Number / Designation:
Top of casing elevation: 17.86'
Top of casing elevation: 17.86°  Total depth of well casing: 2444 Well diameter: 2°  Depth to water (before sampling): 6.82°
Depth to water (before sampling): 6.82'
Thickness of hoating product if any: _ Non-
Depth of well casing in water: 17-37
Req'd volume of groundwater to be purged before sampling: 15 galle-5
Approximate volume of groundwater nurged: 15 461/6-5
Type of seal at grade:
Type of cap on the casing:kckr-c
Is the seal water tight? 4-5 Is the cap water tight? 4-5
Number of samples (containers) collected 3
Did 40 mi VOA vials have headspace: $\lambda x$
Were sample containers chilled after sampling & for delivery ? 4/5
Are Chain of Custody documents accompanying the samples:
Sample temperature: 17 -
Sample pH: Test method: 9040
Conductivity: Test method:
Physical description of water during initial bailing period:
219(41y 3:14y
Physical description of water sample:
True of a 1 to the same of the
Type of analysis requested: TIH-(-
Vitatila Cryan cs
$\frac{\rho_H}{\rho_H}$
PH conduction ty
,
Type of bailer/sampling equipment used: payatyland
Equipment decontamination procedures: TSP wish was triple wash.
Beiler blick BB 3 contested but - use
Disposition of bailed water volume:
Dinner on-site



### WELL SAMPLING FIELD LOG

Aqua Science Engineers, Inc. San Ramon, CA 94583

Project Name: OLIVER Rubby
Project Address: 1200 65th Street, Emplished  Job # 257/ Date of sampling: 7.14.93
Job # <u>~57/</u> Date of sampling: <u>7.14.93</u>
Completed by: REn
Well Number / Designation: $-\mu\omega^{-2}$
Top of casing elevation: 19.7.
Total depth of well casing: 2448 Well diameter: $z^n$
Depth to water (before sampling):
Thickness of floating product if any: Non- Depth of well casing in water: 18 28
Depth of well casing in water: 18 28
Req'd volume of groundwater to be purged before sampling: 15 gaile-5
Approximate volume of groundwater purged: 16 gathe-5
Type of seal at grade:
Type of cap on the casing:
Is the seal water tight? Y-> Is the cap water tight? Y-5
Number of samples (containers) collected 4
Did 40 ml VOA vials have headspace:
Were sample containers chilled after sampling & for delivery? 125
Are Chain of Custody documents accompanying the samples: 725
Sample temperature: 196
Sample pH: Test method: 9040
Conductivity: Test method:/
Physical description of water during initial bailing period:
Slightly 3.1ty
Physical description of water sample:
• • • • • • • • • • • • • • • • • • • •
Type of analysis requested:   The transfer of analysis requested:
Volatile Cramins
fH Conduction sty
Conduction 174
Type of bailer/sampling equipment used: perysteylore
Equipment decontamination procedures: Til wash and triple top with
rinse Bucher Work 1313- 2 withtheir bische use
Disposition of bailed water volume:
Denominad ency te



# WELL SAMPLING FIELD LOG

Aqua Science Engineers, Inc. San Ramon, CA 94583

Project Name: OLIVER RUBBER
FIGURE Address: 1700 / F. J.
Job # 257/ Date of compliance
Job # 257/ Date of sampling: 7.14.93
Well Number / Designation: Mw-3  Top of casing elevation: 2007
Top of casing elevation: 200
Total uculi () Well cacing: (4, 7, 0)
Total depth of well casing: 24.02. Well diameter: 2"  Depth to water (before sampling): 6.11'  Thickness of floating product if
Thickness of floating product if
Thickness of floating product if any: Atom.  Depth of well casing in water: 17.91
Rea'd volume of groundwater to 1
Req'd volume of groundwater to be purged before sampling: 15 groundwater
Type of seal at grade:     Compart   Type of cap on the casing:   In received.
Is the seal water tight?
Type of cap on the casing:  orking   Is the seal water tight?   Y=3   Is the cap water tight?   Y=5    Number of samples (containers) collected
Did 40 ml VOA vials have headspace:
Were sample containers chilled after sampling & for delivery?
Are Chain of Custody documents accompanying the samples: \(\frac{7-5}{2}\)
Sample pH: Test method:
Physical description of water sample:
Type of analysis requested: Tirl-D
<u> PTEX</u>
O. 1 & Crease
p if
Type of hailer/sampling and
or ouncersampling equipment used: privally
Equipment decontamination procedure 3
Find Bo by bear 22 2
Equipment decontamination procedures: TSP DISK and triple tof when Disposition of bailed water volume:
Discoursed on 5.42

### APPENDIX H

Area Well Survey



.5 mile radius from 65th & Hollis 03/01/1994

METT #	CITY	ADDRESS	OWNER	PHONE USE	DR.DATE	DIAM	TOT.DEPTH	DTW S	ST.BLEV WA	.ELEV :	YIRLD :	Log	WQ W	L DATAORG	N MARGIN
18/4W 10L10	BBR	2850 7th Street	Edwards-Temescal	O TES	10/91	2	26	` 20	0	0	0	D	0	0	D
1S/4W 10L11	BBR	2850 7th Street	Edwards-Temescal	O TES	10/91	2	26	13	ō	ō	ō	D			D
18/4W 10L12	BBR	2850 7th Street	Edwards-Temescal	o Tes	10/91	2	26	14	0	0	0	D	0 `	0	D
18/4W 10L13	BER	2850 7th Street	Edwards-Temescal	o Tes	10/91	2	26	14	0	0	O	D	0	<b>a</b> :	D
18/4W 10L14	BBR	2850 7th Street	Edwards-Temescal	O TES	10/91	2	. 26	15	0	٥٠	0	D	0	0	Ď
18/4W 10L15	BER	2850 7th Street	Edwards-Temescal	0 TES	10/91	2	26	20	0	0	0	D	0	0	D
18/4W 10L16	BBR	2850 7th Street	Edwards-Temescal	o Tes	10/91	2	26	13	0	0	0	D	-		D
18/4W 10L17	BBR	2850 7th Street	Edwards-Temescal	0 TES	10/91	2	26	13	0	0	0	D			D
18/4W 10L18	BBR	2850 7th Street 2850 7th Street	Edwards-Temescal	O TES	10/91	2	26	14	0	0	0	D			D
.1S/4W 10L19 1S/4W 10N 2	BER	700 HEINZ STREET	Edwards-Temescal WAREHAM DEVELOPMENT	O TES O TES	10/91 11/88	2 2	26 20	13 8	0	0	0	D D	-	-	D
18/4W 10N 2	BER	800 HEINZ ST	WAREHAM DEVELOPMENT	O TES	11/88	2	20	Ö	. 0	0	0	D			L L
18/4W 10P 1	BBR	7th & Ashby	Rinehart Oil Inc. W-1	MON 0	5/89	2	27	12	0	0	ŏ	D		-	D
15/4W 100 1	BBR	900 MURRAY AVE	UNIV. OF CAL BERKELEY	0 MON	08/30	2	21	9	ō	ŏ	ō	D			L L
18/4W 10Q 2	BER	900 MURRAY AVE	UNIV. OF CAL BERKELEY	0 MON	08/88	2	20	9	ō	ŏ	ō	D	-		ī.
18/4W 10Q 3	BER	2995 SAN PABLO AVE	CHEVRON STATION #90194	0 MON	11/88	4	30	11	0	0	0	G.	0	0 :	L
18/4W 10Q 4	BBR	2995 SAN PABLO AVE	CHEVRON STATION #90194	0 MON	1/88	4	31	11	0	0	0	G.	0	0	L
18/4W 10Q 5	BBR	2995 SAN PABLO AVE	CHEVRON STATION #90194	0 MON	11/88	4	32	12	0	0	0	G	0	0	L
18/4W 10Q 6	BBR	2995 SAN PABLO AVE	CHEVRON STATION #90194	0 MON	11/88	4	36	10	0	0	0	G	0	0	L
18/4W 10Q 7	BBR	2995 SAN PABLO AVE	CHEVRON STATION #90194	0 MON	11/88	4	30	6	0	0	0	G	-		Ĺ
18/4W 10Q 8	BER	2995 SAN PABLO AVE	CHEVRON STATION #90194	0 MON	11/88	4	21	5	0	0	0	G	0		L
18/4W 15A 1	OAK	6549 San Pablo Ave.	Myers Container Corp.	0 MON	8/88	2	70	63	0	0	0	D	-	•	D
18/4W 15A 2	OAK	6549 San Pablo Ave.	Myers Container Corp.	0 TES	10/90	2	19	14	0	0	0	D			D
19/4W 15A 3	OAK	6549 San Pablo Ave.	Myers Container Corp.	O TES	10/90	2	14	11	0	0	0	D	-	-	D
18/4W 15A 4	OAK	6549 San Pablo Ave.	Myers Container Corp.	O TES	10/90	2	15	14	0	0	0	D		-	D
1S/4W 15A 5	OAK	6549 San Pablo Ave.	Myers Container Corp. Myers Container Corp	O TES	10/90	2	15	10	0	0	0	D			D
18/4W 15A 6 18/4W 15A 7	OAK	6549 San Pablo 6549 San Pablo		0 MON	1/92 10/91	2 2	15 15	26 10	36	10	0	G G			D
18/4W 15A 8	MAG	6549 San Pablo Ave	Myers Container Corp W-6 Myers Container Corp W-9	O MON	10/91	1	17	17	34 40	24 23	1091	G	-	-	D D
18/4W 15A 9	OAK	6549 San Pablo Ave	Myers Container Corp W11	O MON	10/91	1	16	15	41	25 26	ŏ	G.			D
18/4W 15A10	OAK	6549 San Pablo Ave	Myers Container Corp W10	O MON	1/92	2	15	10	36	26	ő	Ġ			D
18/4W 15B	OAK	1200 65th St.	Oliver Rubber Co.	0 BOR	10/92	ō	.15	ō	ő	-0	ŏ	Ğ	-	-	b
18/4W 15B 1	OAK	1171 Ocean Avenue	Linde Gases, BAYOX	MOM 0	12/89	2	29	9	Ō	ō	0	G.	1		D
18/4W 15B 2	OAK	6549 San Pablo	Myers Container Corp	0 MON	10/91	0	0	0	0	0	0	G			D
1S/4W 15B 3	OAK	6549 San Pablo	Myers Container Corp	0 MON	10/91	0	0	0	0	0	0		0	0	Ď
18/4W 15B 4	OAK	6549 San Pablo	Myers Container W-7	0 MON	10/91	2	14	11	35	24	0	G	0	0	D
18/4W 15B 5	OAK		Myers Container W-8	0 MON	10/91	2	14	10	35	25	0	G-		-	D
18/4W 15B 6	OAK	1200 65th St.	Oliver Rubber Co. MW1	0 MON	10/92	2	25	8	0 '	0	0	G	-	-	D
18/4W 15B 7		1200 65th St.	Oliver Rubber Co. MW2	NON 0	10/92	2	25	8	0	0	0	G			D
18/4W 15B 8		1200 65th St.	Oliver Rubber Co. MW3	0 MON	10/92	2	25	7	0	0	0	G.			P
18/4W 15C 1	BMB BMB	1301 65TH ST 6529 Hollis St	CHARLES GENSLER	0 MON	06/88 2/92	2	23	11	0	0	0	D			L .
18/4W 15C 2 18/4W 15C 3	EME	6529 Hollis St	GROVE VALVE & REGULATOR GROVE VALVE & REGULATOR	0 MON 0 MON	2/92	4	25 25	13 23	21 16	8 ~7	0	G G			D D
18/4W 15C 4	BMB	6529 Hollis St	GROVE VALVE & REGULATOR	0 MON	2/92	4	25 25	23	17	-7 -6	Ö	G	-		D
18/4W 15D 1	EME	6707 Bay Street	MRCP Realty Properties	O TES	1/90	4	22	13	ő	0	ŏ	D	-		D
18/4W 15D 2	BMB	6707 Bay Street	MRCP Realty Properties	0 TES	1/90	4	22	15	ŏ	ŏ	ō	Ď		-	D
18/4W 15B 1	BMB	1650 65th St.	BENEFIT CAPITAL CO (OAK)	0 DES	7/87	2	30	12	ō	ŏ	ō.	D		-	_ 
18/4W 15B 2	EMB	1600 64th Street	Emeryvilla Rdvlpmnt Agncy	0 MON	12/89	2	20	7	0	ō	ō	D			, b
18/4W 15B 3	EMB	1600 64th Street	Emeryville Rdvlpmnt Agncy	0 MON	12/89	2	16	6	0	Ö	0	D	Ó	0 1	D
18/4W 15B 4	BMB	1600 64th Street	Emeryville Rdvlpmnt Agncy	0 MON	12/89	2	17	6	0	0	0	D	0	0 1	D
18/4W 15B 5	EMB	1650 65th Street	P.O. Partners	0 MON	9/89	2	, 29	12	0	0	٥	D	0	0 , 1	ס
19/4W 15R 6	EME	1650 65th Street	P.O. Partners	0 MON	11/89	4	18	9	0	0	0	D	0		)
18/4W 15E 7		1650 65th Street	P.O. Partners	0 MON	11/89	4	16	9	0	0	0	D	-		•
13/4W 15B 8	RME	1650 65th Street	P.O. Partners	0 MON	11/89	4	18	8	0	0	0	D	0		0
18/4W 15B 9	BMB	64th Street/Christie Av.	The Martin Company	0 MON	03/87	2	14	6	0	0	0	D			•
18/4W 15B10	BMB	64th St/Christie Avenue	The Martin Company	0 MON	04/87	2	13	3	0 .	0	0	D			)
18/4W 15B11	BMB	1650 65th Street 6475 Christie Avenue	P.O. Partners	0 IRR	9/90	6.	470	0	0	0	25	<u>D</u> .			)
18/4W 15R12	BMB	6475 Christie Avenue	P.O. Partners	O MON	3/90	4	22	9	0	0	0	D			2
18/4W 15B13 18/4W 15B14	eme	6475 Christie Avenue 64th St. & Christie Ave.	P.O. Partners Christie Avenue Partners	NOM 0	3/90 4/90	4 2	19 10	8 2	0	0	0	D	-		) }
18/4W 15B14 18/4W 15B15	BMB	64th St. & Christie Ave.	Christie Avenue Partners	0 MON	4/90	2	15	2 5	0	ņ	0	D D			) )
18/4W 15B16	BMB	64th St & Christie Ave	Christie Avenue Partners	MOM 0	4/90	2	16	8	ŏ	n		D			Ś
,				5 51 524	-, - •	_		_	-	•	_		- '	•	

.5 mile radius from 65th & Hollis (Page 2)

W	BLL #	CITY	ADDRESS	owner	PHONE USE	DR.DATE	DIAM	TOT.DEPTH	DTW	ST.BLEV	MY'BTRA	AIBFD	rog	WQ	WL	DATAORGN MARGIN	
1	S/4W 15B17	BMB	64th St. & Christie Ave.	Christie Avenue Partners	0 MON	4/90	2	18	4	0	0	0	D	0	0	D	
1.6	8/4W 15B18	BMB	64th St & Christie Ave	Christie Avenue Partners	0 MON	6/90	2	14	5	0	0	0	D	0	o	D	
18	S/4W 15R19	BMB	64th St. & Christie Ave	Christie Avenue Partners	0 MON	8/90	2	34	28	181	153	Ó	G	0	ō	D	
1,8	S/4W 15P 1	EME	63rd ST & OVERLAND AVE	WAREHAM DEVELOPMENT	0 MON	11/87	2	25	4	0	0	0	D	0	Ó	L	
14	8/4W 15F 2	EMB	63rd ST & OVERLAND AVE.	WAREHAM DEVELOPMENT	0 MON	11/87	2	25	6	0	0-	0	D	Ó	Ó	L	
18	S/4W 15F 3	OAK	1351 Ocean Avenue	HFH Limited	0 DOM	6/B8	5	140	80	0	0	15	D	ò	o	D	
14	8/4W 15F 3	OAK	1351 OCEAN AV.	HPH LTD.	o mon	11/88	2	15	10	0	0		D	ō	ō	ī.	
18	S/4W 15F 4	EME	64th Street/Christie Av.	The Martin Company	0 MON	03/87	2	12	7	0	0	Ô	ם	ŏ	ŏ	Ď	
1/	8/4W 15F 5	BMB	64th St/Christie Avenue	The Martin Company	0 MON	04/87	2	13	6	0	0	0	ם	ň	ō	D.	
	S/4W 15F 6	BMB	· · · · · · · · · · · · · · · · ·	The Martin Company	0 MON	04/87	2	12	5	ō	ō	-	Ď	-	ŏ	Ď	
18	8/4W 15F 7	BMB	64th St/Christie Avenue	The Martin Company	0 MON	04/87	2	14	6	0	0	Ď	D	Ď	ō	n n	
	S/4W 15F 8	BMB	64th St/Christie Avenue	The Martin Company	0 MON	04/87	2	13	6	ō	ō	•	D	-	ō	מ	
	S/4W 15G 1	OAK		PG&B	0 CAT	8/76	ō	120	ŏ	ō	ō	-	D	-	ŏ	ī,	
	8/4W 15K 1	EME	HOLLIS ST. & 59TH	BONTA COLLINS	0	-,	Ô	0	Ď	0	ō	ŏ	_	-	•	2	
	3/4W 15L	BMB	Landergan St. & Powell St		0 BOR	12/92	ō	79	ō	9	9	0	G	a	0	Ď.	
	3/4W 15L 2	BMB		The Martin Company	0 MON	04/87	2	13	5	0	0	Ď	D	ŏ	-	ם -	
	9/4W 15L 3	EME	6121 Hollis St	U.S. Postal Service	0 TES	1/92	2	19	8	ō	0	Ď	D	ŏ	ñ	n n	
	3/3W 34M 1		HOLLIS ST. & 59TH	BONTA COLLINS	0	-,	0	-0	ō	ō	0	Ô	_	•	•	<u> </u>	

#### WELL INVENTORY FILE

Definitions and abbreviations for items listed in the well inventory file are as follows:

[WELLNO] Well number - Wells are numbered according to their location in the rectangular system of the Public Land Survey. The part of the number preceding the slash indicates the township; the part following the slash indicates the range and section number; the letter following the section number indicates the 40-acre subdivision; and the final digit is a serial number for wells in each 40-acre subdivision.

[DAT] Date - The month and year when drilling or boring was completed.

[ELEV] Surface elevation - The surface elevation of the well, if known, in feet above mean sea level. A zero designates an unknown elevation.

[TD] Total depth - The depth of the well. This usually designates the completed well depth. If the well has a well log available on file, then the total drilled depth of the well is given. The inventory does not show total depth data for geotechnical borings. This is because only one state well number is assigned to one boring at a site, and there are usually several borings of different depth.

[DTW] Depth to water - This category usually indicates the standing groundwater level in the well on the date of completion. The "depth to first water encountered" is recorded in the inventory when it is the only water level data reported on the well driller's report.

[USE] Use - The well use (or in the case of cathodic protection wells and geotechnical borings, the reason for the excavation) as indicated in the well driller's report or data sheets. A plus sign (+) after the well use indicates a well in the current ACFC & WCD monitoring network.

[ABN] Abandoned well - A well whose use has been permanently discontinued or which is in such a state of disrepair that no water can be produced. In the inventory, this may include wells which are covered or capped but not properly destroyed.

[DES] Destroyed well - A well that has been properly filled so that it cannot produce water nor act as a vertical conduit for the movement of groundwater.

[DOM] Domestic well - A water well which is used to supply water for the domestic needs of an individual residence or systems of four or less service connections or "hookups".

[INA] Inactive well - A well not routinely operating but capable of being made operable with a minimum of effort. Also called a "standby well".

[IND] Industrial well - A water well used to supply industry on an individual basis.

[IRR] Irrigation well - A water well used to supply water only for irrigation or other agricultural purposes. In the inventory, this category includes large capacity wells as well as small capacity wells for lawn irrigation.

[MON] Monitoring or observation well - Wells constructed for the purpose of observing or monitoring groundwater conditions. (see piezometer).

[MUN] Municipal well - A water well used to supply water for domestic purposes in systems subject to Chapter 7, Part 1,

Division 5 of the California Health and Safety Code. Included are wells supplying public water systems classified by the Department of Health Services. (Also referred to as community water supply wells).

[PIE] Piezometer - A piezometer is a well specifically designated to measure the hydraulic head within a zone small enough to be considered a point as contrasted with a well that reflects the average head of the aquifer for the screened interval.

[STO] Stock - A water well used primarily for livestock.

[TES] Test well and test hole - A test well is constructed for the purpose of obtaining the information needed to design a well prior to its construction. Such wells are not to be confused with "test holes" which are temporary in nature (i.e., uncased excavations whose purpose is the immediate determination of existing geologic and hydrologic conditions). Test wells are cased and can be converted to observation or monitoring wells, and under certain circumstances, to production wells. In the inventory, "TES" includes both test wells and test holes.

[?] Unidentified use - This indicates water wells whose use could not be ascertained from the available well data.

[CAT] Cathodic protection well - Any artificial excavation constructed by any method for the purpose of installing equipment or facilities for the protection from

corrosion by electrochemical methods of metallic equipment (usually piping) in contact with the ground; commonly referred to as cathodic protection.

[GEO] Geotechnical boring - A temporary boring made to determine certain engineering properties of soils. An asterisk (*) indicates that the state well number assigned to the boring represents more than one boring at a particular site.

[LOG] Log - This category indicates whether a geologic record, or log, for the well or boring is available in the Agency's files. Abbreviations are as follows:

D - well driller's log

G - geotechnical boring log

E - electric (resistivity) log or other subsurface geophysical logs.

[WQ] Water quality data available - This category indicates which wells have water quality data available in ACFC & WCD files. The numbers 1 through 9 signify the number of sets of water quality measurements available for that well. A plus sign (+) indicates that 10 or more sets of data are available. A "0" indicates that no data is available.

[WL] Water level data available - This category indicates which wells have water level data other than the data reported on the well driller's logs. The numbers 1 through 9 signify the number of water level measurements available. A plus sign (+) indicates that 10 or more measurements are available for that well.

A "0" indicates that no data is available.

[YLD] Yield - The maximum pumping rate in gallons per minute that can be supplied by a well without lowering the water level in the well below the pump intake. This data is taken from pump test data recorded in the driller's records. Some of the yield data reflects current production rates and does not reflect maximum yield values determined in a capacity test.

[DIA] Diameter - The diameter in inches of the main casing in a well. May also indicate the diameter of a hand-dug well. Diameter data is not recorded for geotechnical borings.

