RO 2444



76 Broadway Sacramento, CA 95818 phone 916.558.7676 fax 916.558.7639

January 28, 2005

FEB 0 9 2000 Environmental Heart

Mr. Don Hwang Alameda County Health Agency 1131 Harbor Bay Parkway, Suite 250 Alameda, CA 94502

Re: Document Transmittal

Fuel Leak Case 76 Station #7124 10151 International Blvd. Oakland, CA

Dear Mr. Hwang:

Please find attached Secor's *Quarterly Summary Report*, dated 1/28/05, and TRC's *Quarterly Monitoring Report*, dated 1/10/05 for the above referenced site. I declare, under penalty of perjury, that to the best of my knowledge the information and/or recommendations contained in the attached proposal or report is true and correct.

If you have any questions or need additional information, please call me at (916) 558-7666.

Sincerely,

Thomas H. Kosel

Site Manger, Risk Management and Remediation

ConocoPhillips

76 Broadway, Sacramento, CA 95818

Tomas to lovel

Attachment

cc: Gavan Heinrich, Secor



SECOR INTERNATIONAL INCORPORATED www.secor.com

3017 Kilgore Road, Suite 100 Rancho Cordova, CA 95670 916-861-0400 TEL 916-861-0430 FAX

January 28, 2005

Mr. Donald Hwang Alameda County Environmental Health Services 1131 Harbor Bay Parkway Suite 250 Alameda, CA 94502

RE: Quarterly Summary Report-Fourth Quarter 2004

SECOR Project No.: 77CP.60008.01.7124

Dear Mr. Hwang:

On behalf of ConocoPhillips, SECOR International Incorporated (SECOR) is forwarding the quarterly summary report for the following location:

Service Station

Location

76 Service Station No. 7124

10151 International Blvd Oakland, California

Sincerely,


SECOR International Incorporated

Michael L. Stephens, CEG, C.HG, REA II

Senior Geologist

Attachment 1 - Quarterly Monitoring Report October Through December 2004, (TRC 2004)

cc: Mr. Thomas Kosel, ConocoPhillips



QUARTERLY SUMMARY REPORT Fourth Quarter 2004

76 Service Station No. 7124 10151 East 14th Street Oakland, California

City/County ID #: Oakland

County: Alameda

PREVIOUS ASSESSMENT

The Site is currently an active 76 Service Station located on the northwestern corner of the intersection of 14th Street and 102nd Avenue in Oakland, California. Site facilities include three underground storage tanks (USTs), and associated piping and fuel dispensers.

On March 22, 2000, SECOR supervised the removal and replacement of product lines and dispensers by Balch Petroleum (Balch) of Milpitas, California. Soil samples collected from beneath the dispensers and product lines revealed the presence of total petroleum hydrocarbons as gasoline (TPHg) at a maximum concentration of 6,200 milligrams per kilogram (mg/kg), MtBE at a maximum concentration of 120 mg/kg, and benzene at a maximum concentration of 7.4 mg/kg. Excavation and sampling activities were observed and approved by Inspector Gomez of the City of Oakland Fire Services Agency (COFSA).

On March 27, 2000, SECOR observed the over-excavation of approximately 60 cubic yards of soil from the beneath those portions of the dispensers and product lines where soil samples with elevated concentrations of petroleum hydrocarbons were located. Areas measuring approximately 8-10 feet long by 8-10 feet wide were over-excavated to an approximate depth of 8 feet below ground surface (bgs) in each of these areas. Additional over-excavation in these areas was not possible due to their proximity to the footings of the service station canopy. TPHg was detected in 2 of the 3 samples at a maximum concentration of 108 mg/kg; benzene was detected in 1 of the 3 samples at a maximum concentration of 0.162 mg/kg; and MtBE was detected in all 3 samples at a maximum concentration of 43.8 mg/kg. Lead was not detected at or above laboratory reporting limits in any samples.

During February, 2002, SECOR supervised the installation of four on-Site groundwater monitor wells. Prior to well installation, all borings were advanced to 26.5 feet bgs, and subsurface soil samples were collected every five feet. Soil samples were analyzed for gasoline range organics (GRO), BTEX, and fuel oxygenates via Method 8260B. The maximum reported concentrations were 42 mg/kg GRO, 0.36 mg/kg ethylbenzene, 0.26 mg/kg xylenes, and 1.2 mg/kg MtBE.

SENSITIVE RECEPTORS

During third quarter, 2004 SECOR completed a ½-mile radius agency receptor survey and obtained an EDR radius map for the site from Environmental Data Resources, Incorporated. The agency survey identified 2 industrial supply well, 3 cathodic protection wells, and 2 wells of unknown type within the search radius. The survey also identified 12 wells of unknown type that could not be located precisely because the records on file with DWR did not include this information. These wells may or may not be located within the search radius. The EDR radius map did not identify any water supply wells within the search radius but did identify two water supply wells within one mile of the site.

MONITORING AND SAMPLING

The Site has been monitored and sampled since 3rd quarter, 2002. Currently, 4 wells are monitored quarterly (MW-1 through MW-4). Samples are analyzed for TPHg, BTEX, and fuel oxygenates.

The fourth quarter monitoring report (Attachment 1) indicates that MW-2 is covered with asphalt and could not be accessed. The well will be restored or repaired, as necessary during first quarter 2005.

REMEDIAL STATUS

No active remediation

CHARACTERIZATION STATUS

Contamination in soil is adequately delineated. The highest concentrations of residual TPHg and MtBE contamination are localized in the area of the northern dispenser island. The extent of dissolved contamination is undefined in the downgradient (northwest) direction. MW-2 and MW-3, and MW-4 all contained elevated concentrations of TPHg and MtBE.

RECENT SUBMITTALS/CORRESPONDENCE

Submitted – October 14, 2004 Work Plan for Additional Off-Site Monitoring Well Installation.

THIS QUARTER ACTIVITIES (Fourth Quarter 2004)

- TRC performed groundwater monitoring and sampling event.
- 2. Prepared and submitted Work Plan for additional Off-Site Monitoring Well Installation dated October 14, 2004.

NEXT QUARTER ACTIVITIES (First Quarter 2005)

1. TRC to perform groundwater monitoring and sampling event.

SECOR

- 2. Implement October 14, 2004 Work Plan pending agency approval.
- 3. Waiting on property access agreements for off-site monitoring wells
- 4. Inspect and restore or repair MW-2.

CONSULTANT: SECOR International Incorporated

ATTACHMENT QUARTERLY MONITORING REPORT OCTOBER THROUGH DECEMBER 2004 (TRC)

76 Service Station No. 7124
10151 East 14th Street
San Francisco, California

SECOR Project No.: 77CP.60008.01.7124 January 28, 2005



January 10, 2005

ConocoPhillips Company 76 Broadway Sacramento, CA 95818

ATTN:

MR. THOMAS KOSEL

SITE:

76 STATION 7124

10151 INTERNATIONAL BLVD.

OAKLAND, CALIFORNIA

RE:

QUARTERLY MONITORING REPORT OCTOBER THROUGH DECEMBER 2004

Dear Mr. Kosel:

Please find enclosed our Quarterly Monitoring Report for 76 Station 7124, located at 10151 International Blvd., Oakland, California. If you have any questions regarding this report, please call us at (949) 753-0101.

Sincerely,

TRC

Anju Farfan

QMS Operations Manager

CC: Gavan Heinrich, SECOR International Inc. (2 copies)

Enclosures

200400/7124R05.QMS.doc

JAR 1 1 ZEF



QUARTERLY MONITORING REPORT OCTOBER THROUGH DECEMBER 2004

76 STATION 7124 10151 International Blvd. Oakland, California

Prepared For:

Mr. Thomas H. Kosel CONOCOPHILLIPS COMPANY 76 Broadway Sacramento, California 95818

By:

Senior Project Geologist, Irvine Operations December 20, 2004

	LIST OF ATTACHMENTS					
Summary Sheet	Summary of Gauging and Sampling Activities					
Tables	Table Key					
	Table 1: Current Fluid Levels and Selected Analytical Results					
	Table 2: Historic Fluid Levels and Selected Analytical Results					
	Table 3: Additional Analytical Results					
Figures	Figure 1: Vicinity Map					
	Figure 2: Groundwater Elevation Contour Map					
	Figure 3: Dissolved-Phase TPPH Concentration Map					
	Figure 4: Dissolved-Phase Benzene Concentration Map					
	Figure 5: Dissolved-Phase MTBE Concentration Map					
Graphs	Groundwater Elevations vs. Time					
	MTBE 8260B Concentrations vs. Time					
Field Activities	General Field Procedures					
	Groundwater Sampling Field Notes					
Laboratory	Official Laboratory Reports					
Reports	Quality Control Reports					
	Chain of Custody Records					
Statements	Purge Water Disposal					
	Limitations					

Summary of Gauging and Sampling Activities October 2004 through December 2004

76 Station 7124 10151 International Blvd. Oakland, CA

Decidet Coardinators	Thomas U. Vesel	Motor Compling Contractors	TOC
Project Coordinator:	Thomas H. Kosel	Water Sampling Contractor:	IKL

Telephone: 916-558-7666 Compiled by: Valentina Tobon

Date(s) of Gauging/Sampling Event: 10/29/04

Sample Points

Groundwater wells: 4 onsite, 0 offsite Wells gauged: 3 Wells sampled: 3

Purging method: Diaphragm pump

Purge water disposal: Onyx/Rodeo Unit 100 Other Sample Points: 0 Type: n/a

Liquid Phase Hydrocarbons (LPH)

Wells with LPH: 0 Maximum thickness (feet): n/a

LPH removal frequency: **n/a** Method: **n/a**

Treatment or disposal of water/LPH: **n/a**

Hydrogeologic Parameters

Depth to groundwater (below TOC): Minimum: 16.14 feet Maximum: 18.13 feet

Average groundwater elevation (relative to available local datum): **20.63 feet**Average change in groundwater elevation since previous event: **0.28 feet**

Interpreted groundwater gradient and flow direction:

Current event: 0.009 ft/ft, west

Previous event: 0.003 ft/ft to 0.008 ft/ft, west (07/22/04)

Selected Laboratory Results

Wells with detected **Benzene: 0** Wells above MCL (1.0 μg/l): **n/a**

Maximum reported benzene concentration: n/a

Wells with TPPH 8260B 2 Maximum: 4,600 μg/l (MW-3) Wells with MTBE 2 Maximum: 640 μg/l (MW-3)

Notes:

MW-2=Well is paved over.,

TABLES

TABLE KEY

STANDARD ABREVIATIONS

-- not analyzed, measured, or collected

LPH = liquid-phase hydrocarbons

Trace = less than 0.01 foot of LPH in well

μg/l = micrograms per liter (approx. equivalent to parts per billion, ppb)
mg/l = milligrams per liter (approx. equivalent to parts per million, ppm)

ND < = not detected at or above laboratory detection limit
TOC = top of casing (surveyed reference elevation)

ANALYTES

BTEX = benzene, toluene, ethylbenzene, and (total) xylenes

DIPE = di-isopropyl ether

ETBE = ethyl tertiary butyl ether

MTBE = methyl tertiary butyl ether

PCB = polychlorinated biphenyls

PCE = tetrachloroethene
TBA = tertiary butyl alcohol
TCA = trichloroethane
TCE = trichloroethene

TPH-G = total petroleum hydrocarbons with gasoline distinction TPH-D = total petroleum hydrocarbons with diesel distinction

TPPH = total purgeable petroleum hydrocarbons
TRPH = total recoverable petroleum hydrocarbons

TAME = tertiary amyl methyl ether

1,1-DCA = 1,1-dichloroethane

1,2-DCA = 1,2-dichloroethane (same as EDC, ethylene dichloride)

1,1-DCE = 1,1-dichloroethene

1,2-DCE = 1,2-dichloroethene (cis- and trans-)

NOTES

- 1. Elevations are in feet above mean sea level. Depths are in feet below surveyed top-of-casing.
- 2. Groundwater elevations for wells with LPH are calculated as: Surface Elevation Measured Depth to Water + (Dp x LPH Thickness), where Dp is the density of the LPH, if known. A value of 0.75 is used for gasoline and when the density is not known. A value of 0.83 is used for diesel.
- 3. Wells with LPH are generally not sampled for laboratory analysis (see General Field Procedures).
- 4. Comments shown on tables are general. Additional explanations may be included in field notes and laboratory reports, both of which are included as part of this report.
- 5. A "J" flag indicates that a reported analytical result is an estimated concentration value between the method detection limit (MDL) and the practical quantification limit (PQL) specified by the laboratory.
- 6. Other laboratory flags (qualifiers) may have been reported. See the official laboratory report (attached) for a complete list of laboratory flags.
- 7. Concentration graphs based on tables (presented following Figures) show non-detect results prior to the Second Quarter 2000 plotted at fixed values for graphical display. Non-detect results reported since that time are plotted at reporting limits stated in the official laboratory report.
- 8. Groundwater vs. Time graphs may be corrected for apparent level changes due to resurvey.
- 9. Historical data has been validated for this report. Values presented in the following tables supercede those from previous reports.

REFERENCE

TRC began groundwater monitoring and sampling for 76 Station 7124 in October 2003. Historical data compiled prior to that time were provided by Gettler-Ryan Inc.

Table 1
CURRENT FLUID LEVELS AND SELECTED ANALYTICAL RESULTS
October 29, 2004
76 Station 7124

Date Sampled	TOC Elevation	Depth to Water	LPH Thickness		Change in Elevation	TPH-G	TPPH 8260B	Benzene	Toluene	Ethyl- benzene	Total Xylenes	MTBE 8021B	MTBE 8260B	Comments
	(feet)	(feet)	(feet)	(feet)	(feet)	(µg/l)	(μg/l)	(μg/l)	(μg/l)	(μg/l)	(μg/l)	(μg/l)	(μg/l)	
MW-1 10/29/0	4 37.37	16.14	0.00	21.23	0.29		ND<50	ND<0.50	ND<0.50	ND<0.50	ND<1.0		ND<0.50	
MW-2 10/29/0	4 37.87		0.00			••	**							Well is paved over.
MW-3 10/29/0	4 37.72	17.29	0.00	20.43	0.33		4600	ND<5.0	ND<5.0	13	ND<10.		640	
MW-4 10/29/0	4 38.36	18.13	0.00	20.23	0.21	 ,	2700	ND<2.5	ND<2.5	ND<2.5	ND<5.0		76	

Table 2
HISTORIC FLUID LEVELS AND SELECTED ANALYTICAL RESULTS
April 2002 Through October 2004
76 Station 7124

Date Sampled	TOC Elevation	Depth to Water	LPH Thickness	Ground- water Elevation	Change in Elevation	ТРН-G	TPPH 8260B	Benzene	Toluene	Ethyl- benzene	Total Xylenes	MTBE 8021B	MTBE 8260B	Comments
	(feet)	(feet)	(feet)	(feet)	(feet)	(μg/l)	(μg/l)	(μg/l)	(μg/l)	(μg/l)	(μg/l)	(μg/l)	(μg/l)	
MW-1														
04/08/0	02 37.37	14.27	0.00	23.10		ND<50		ND<0.50	ND<0.50	ND<0.50	ND<0.50	ND<2.5	ND<2.0	
07/28/0	02 37.37	15.88	0.00	21.49	-1.61		ND<50	ND<0.50	ND<0.50	ND<0.50	ND<1.0		ND<2.0	
11/03/6)2 37.37	16.75	0.00	20.62	-0.87		ND<50	ND<0.50	ND<0.50	ND<0.50	ND<1.0		ND<2.0	
01/24/0	37.37	13.94	0.00	23.43	2.81		ND<50	ND<0.50	ND<0.50	ND<0.50	ND<1.0	**	ND<2.0	
04/02/0	37.37	14.99	0.00	22.38	-1.05		460	ND<0.50	ND<0.50	ND<0.50	ND<1.0	••	ND<2.0	
07/01/0	37.37	15.48	0.00	21.89	-0.49		ND<50	ND<0.50	ND<0.50	ND<0.50	ND<1.0	•-	ND<2.0	
10/02/0	37.37	16.68	0.00	20.69	-1.20		ND<50	ND<0.50	ND<0.50	ND<0.50	ND<1.0		ND<2.0	
01/09/0)4 37.37	13.79	0.00	23.58	2.89		ND<50	ND<0.50	ND<0.50	ND<0.50	ND<1		ND<2	
04/26/	04 37.37	15.21	0.00	22.16	-1.42		ND<50	ND<0.50	ND<0.50	ND<0.50	ND<1.0		ND<0.50	
07/22/	04 37.37	16.43	0.00	20.94	-1.22		ND<50	ND<0.50	ND<0.50	ND<0.50	ND<1.0		ND<0.50	
10/29/	37.37	16.14	0.00	21.23	0.29		ND<50	ND<0.50	ND<0.50	ND<0.50	ND<1.0		ND<0.50	
MW-2														
04/08/	02 37.87	15.86	0.00	22.01		4,400		ND<2.5	ND<2.5	6.4	ND<2.5	380	490	
07/28/	02 37.87	17.28	0.00	20.59	-1.42		3,200	ND<2.5	ND<2.5	ND<2.5	ND<5.0		170	
11/03/	02 37.87	18.03	0.00	19.84	-0.75		3,800	ND<5.0	ND<5.0	ND<5.0	ND<10		72	
01/24/	03 37.87	15.59	0.00	22.28	2.44		410	ND<2.5	ND<2.5	ND<2.5	ND<5.0		490	
04/02/	03 37.87	16.50	0.00	21.37	-0.91		1,000	ND<5.0	ND<5.0	ND<5.0	ND<10	**	180	
07/01/	03 37.87	16.94	0.00	20.93	-0.44		1,900	ND<2.5	ND<2.5	ND<2.5	ND<5.0		120	
10/02/	03 37.87	17.93	0.00	19.94	-0.99		6900	ND<0.50	ND<0.50	ND<0.50	ND<1.0		32	
01/09/	04 37.87	15.42	0.00	22.45	2.51		1000	ND<2.5	ND<2.5	ND<2.5	ND<5.0		300	
04/26/	04 37.87	,	•-		**									Covered with asphalt
07/22/	04 37.87													Covered with asphalt
10/29/	04 37.87	7	0.00			. 								Well is paved over.

MW-3

Table 2
HISTORIC FLUID LEVELS AND SELECTED ANALYTICAL RESULTS
April 2002 Through October 2004
76 Station 7124

Date Sampled	TOC Elevation	Depth to Water	LPH Thickness		Change in Elevation	TPH-G	TPPH 8260B	Benzene	Toluene	Ethyl- benzene	Total Xylenes	MTBE 8021B	MTBE 8260B	Comments
	(feet)	(feet)	(feet)	(feet)	(feet)	(µg/l)	(μg/l)	(μg/l)	(μg/l)	(μg/l)	(μg/l)	(μg/l)	(μg/l)	
	continued													
04/08/0		15.86		21.86		8,700		65	ND<25	400	ND<25	6,500	8,300	
07/28/0		17.22	0.00	20.50	-1.36		4,500	ND<25	ND<25	ND<25	ND<50		1,100	
11/03/0		17.90		19.82	-0.68		25,000	ND<5.0	ND<5.0	25	ND<10		470	
01/24/0	3 37.72	15.57	0.00	22.15	2.33		6,000	ND<25	ND<25	94	ND<50	••	10,000	
04/02/0	3 37.72	16.45	0.00	21.27	-0.88		130,000	ND<100	ND<100	ND<100	ND<200		4,400	
07/01/0	3 37.72	16.88	0.00	20.84	-0.43		9,400	ND<10	ND<10	ND<10	ND<20		2,200	
10/02/0	3 37.72	17.85	0.00	19.87	-0.97		73000	ND<50	ND<50	ND<50	ND<100		460	
01/09/0	4 37.72	15.31	0.00	22.41	2.54	B-4	8700	ND<25	ND<25	98	ND<50		3800	
04/26/0	4 37.72	16.62	0.00	21.10	-1.31		6700	ND<25	ND<25	ND<25	ND<50		3900	
07/22/0	4 37.72	17.62	0.00	20.10	-1.00		13000	ND<25	ND<25	ND<25	ND<50		980	
10/29/0	4 37.72	17.29	0.00	20.43	0.33		4600	ND<5.0	ND<5.0	13	ND<10		640	
MW-4														
04/08/0	2 38.36	16.59	0.00	21.77		13,000		ND<5.0	ND<5.0	28	ND<5.0	790	980	
07/28/0	2 38.36	17.93	0.00	20.43	-1.34		18,000	ND<2.5	ND<2.5	ND<2.5	ND<5.0		170	
11/03/0	2 38.36	18.66	0.00	19.70	-0.73		220	ND<0.50	ND<0.50	ND<0.50	ND<1.0		5.7	
01/24/0	3 38.36	16.27	0.00	22.09	2.39		ND<1,000	ND<10	ND<10	ND<10	ND<20		1,000	
04/02/0	3 38.36	17.19	0.00	21.17	-0.92		130,000	ND<100	ND<100	ND<100	ND<200		ND<400	
07/01/0	3 38.36	17.61	0.00	20.75	-0.42		15,000	ND<2.5	ND<2.5	ND<2.5	ND<5.0		170	
10/02/0	3 38.36	18.58	0.00	19.78	-0.97		7100	ND<10	ND<10	ND<10	ND<20		70	
01/09/0		16.15	0.00	22.21	2.43		18000	ND<10	ND<10	ND<10	ND<20		530	
04/26/0				21.16	-1.05		6500	ND<10	ND<10	ND<10	ND<20		240	
07/22/0				20.02	-1.14		18000	ND<10	ND<10	ND<10	ND<20		48	
10/29/0				20.23	0.21		2700	ND<2.5	ND<2.5	ND<2.5	ND<5.0		76	
10,200	. 50.50	10,10	2.30	20,20	0.2.1		2,00	. 12 -2.2	. 10	1 1 mm - 2m 1 m	1.12 2.0		, •	


Table 3
ADDITIONAL ANALYTICAL RESULTS
76 Station 7124

Date Sampled	EDC	EDB	TAME 8260B	TBA 8260B	DIPE 8260B	ETBE 8260B	Ethanol 8015B	Ethanol 8260B	1,2 DCE	
	(μg/l)	(µg/l)	(μg/l)	(µg/l)	(μg/l)	$(\mu g/l)$	(mg/l)	(μg/l)	(μg/l)	·
MW-1										
07/28/02	ND<2.0	ND<2.0	ND<2.0	ND<100	ND<2.0	ND<2.0	ND<500			
11/03/02	ND<2.0	ND<2.0	ND<2.0	ND<100	ND<2.0	ND<2.0	ND<500			
01/24/03	ND<2.0	ND<2.0	ND<2.0	ND<100	ND<2.0	ND<2.0	ND<500			
04/02/03	ND<2.0	ND<2.0	ND<2.0	ND<100	ND<2.0	ND<2.0	ND<500			
07/01/03	ND<2.0	ND<2.0	ND<2.0	ND<100	ND<2.0	ND<2.0	ND<500			
10/02/03	ND<2.0	ND<2.0	ND<2.0	ND<100	ND<2.0	ND<2.0		ND<500		
01/09/04	ND<2.0	ND<2	ND<2	ND<100	ND<2	ND<2		ND<500	ND<2	
04/26/04	ND<0.50	ND<0.50	ND<0.50	ND<5.0	ND<1.0	ND<0.50		ND<50		
07/22/04	ND<0.50	ND<0.50	ND<0.50	ND<5.0	ND<1.0	ND<0.50		ND<50	ND<0.50	
10/29/04	ND<0.50	ND<0.50	ND<0.50	ND<5.0	ND<1.0	ND<0.50		ND<50	••	
MW-2										
04/08/02	ND<40	ND<40	ND<40	ND<2,000	ND<40	ND<40	ND<10,000			
07/28/02	ND<10	ND<10	ND<10	ND<500	ND<10	ND<10	ND<2,500		•-	
11/03/02	ND<20	ND<20	ND<20	ND<1,000	ND<20	ND<20	ND<5,000			
01/24/03	ND<10	ND<10	ND<10	ND<500	ND<10	ND<10	ND<2,500			
04/02/03	ND<20	ND<20	ND<20	ND<1,000	ND<20	ND<20	ND<5,000			
07/01/03	ND<10	ND<10	ND<10	ND<500	ND<10	ND<10	ND<2,500			
10/02/03	ND<2.0	ND<2.0	ND<2.0	ND<100	ND<2.0	ND<2.0	**	ND<500		
01/09/04	ND<10	ND<10	ND<10	ND<500	ND<10	ND<10		ND<2500	ND<10	
MW-3			•							
10/02/03	ND<200	ND<200	ND<200	ND<10000	ND<200	ND<200		ND<50000		
01/09/04	ND<100	ND<100	ND<100	ND<5000	ND<100	ND<100		ND<25000	ND<100	
04/26/04	ND<25	ND<25	ND<25	ND<250	ND<50	ND<25		ND<2500		
07/22/04	ND<25	ND<25	ND<25	ND<250	ND<50	ND<25		ND<2500	ND<25	
10/29/04	ND<5.0	ND<5.0	ND<5.0	ND<50	ND<10	ND<5.0		ND<500		

Page 1 of 2

Table 3
ADDITIONAL ANALYTICAL RESULTS
76 Station 7124

Date Sampled	EDC	EDB	TAME 8260B	TBA 8260B	DIPE 8260B	ETBE 8260B	Ethanol 8015B	Ethanol 8260B	1,2 DCE
	(µg/l)	(μg/l)	(μg/l)	(μg/l)	(μg/l)	(μg/l)	(mg/l)	(μg/l)	(μg/l)
MW-4									
04/08/02	ND<100	ND<100	ND<100	ND<5,000	ND<100	ND<100	ND<25,000		
07/28/02	ND<10	ND<10	ND<10	ND<500	ND<10	ND<10	ND<2,500		
11/03/02	ND<2.0	ND<2.0	ND<2.0	ND<100	ND<2.0	ND<2.0	ND<500		
01/24/03	ND<40	ND<40	ND<40	ND<2,000	ND<40	ND<40	ND<10,000		
04/02/03	ND<400	ND<400	ND<400	ND<20,000	ND<400	ND<400	ND<100,000		
07/01/03	ND<10	ND<10	ND<10	ND<500	ND<10	ND<10	ND<2,500		h-
10/02/03	ND<40	ND<40	ND<40	ND<2000	ND<40	ND<40		ND<10000	
01/09/04	ND<40	ND<40	ND<40	ND<2000	ND<40	ND<40		ND<10000	ND<40
04/26/04	ND<10	ND<10	ND<10	430	ND<20	ND<10		ND<1000	
07/22/04	ND<10	ND<10	ND<10	ND<100	ND<20	ND<10		ND<1000	ND<10
10/29/04	ND<2.5	ND<2.5	ND<2.5	63	ND<5.0	ND<2.5		ND<250	••





0 1/4 1/2 3/4 1 MILE

SCALE 1: 24,000

SOURCE


United States Geological Survey 7.5 Minute Topographic Mapt Oakland West Quadrangle





VICINITY MAP

76 Station 7124 10151 International Boulevard Oakland, California



NOTES:


Contour lines are interpretive and based on fluid levels measured in monitoring wells. Elevations are in feet above mean sea level. NA = not analyzed, measured, or collected.


LEGEND MW-4 Monitoring Well with Groundwater Elevation (feet) 21.00 — Groundwater Elevation Contour General Direction of Groundwater Flow

GROUNDWATER ELEVATION CONTOUR MAP October 29, 2004

76 Station 7124 10151 International Boulevard Oakland, California







NOTES:

Contour lines are interpretive and based on laboratory analysis results of groundwater samples TPPH = total purgeable petroleum hydrocarbons, µg/l = micrograms per liter. ND = not detected at limit indicated on official laboratory report.

() = representative of historical value.

Results obtained using EPA Method 8260B.

LEGEND


_1,000 Dissolved-Phase TPPH
Contour (µg/I)

DISSOLVED-PHASE TPPH CONCENTRATION MAP October 29, 2004

76 Station 7124 10151 International Boulevard Oakland, California







NOTES:

 $\mu g/l$ = micrograms per liter. ND = not detected at limit indicated on official laboratory report. () = representative of historical value.

LEGEND


Concentration (µg/I)

DISSOLVED-PHASE BENZENE **CONCENTRATION MAP** October 29, 2004

76 Station 7124 10151 International Boulevard Oakland, California

TRC





NOTES:

Contour lines are interpretive and based on laboratory analysis results of groundwater samples. MTBE = methyl tertiary butyl ether. $\mu g/I = micrograms$ per liter. ND = not detected at limit indicated on official laboratory report. () = representative of historical value. Results abtained using EPA Method 8260B.

LEGEND

MW-4

→ Monitoring Well with


Dissolved-Phase MTBE Concentration (µg/I)

100 Dissolved-Phase MTBE Contour (µg/l)

DISSOLVED-PHASE MTBE **CONCENTRATION MAP** October 29, 2004


76 Station 7124 10151 International Boulevard Oakland, California

TRC




GRAPHS


Groundwater Elevations vs. Time 76 Station 7124





MTBE 8260B Concentrations vs Time

76 Station 7124









GENERAL FIELD PROCEDURES

Groundwater Monitoring and Sampling Assignments

For each site, TRC technicians are provided with a Technical Service Request (TSR) that specifies activities required to complete the groundwater monitoring and sampling assignment for the site. TSRs are based on client directives, instructions from the primary environmental consultant for the site, regulatory requirements, and TRC's pre vious experience with the site.

Fluid Level Measurements

Initial site activities include determination of well locations based on a site map provided with the TSR. Well boxes are opened and caps are removed. Indications of well or well box damage, or of pressure buildup in the well are noted.

Fluid levels in each well are measured using a coated cloth tape equipped with an electronic interface probe, which distinguishes between liquid phase hydrocarbon (LPH) and water. The depth to LPH (if it is present), to water, and to the bottom of the well are measured from the top of the well casing (surveyors mark or notch if present) to the nearest 0.01 foot. Unless otherwise instructed, a well with less than 0.67 foot between the measured top of water and the measured bottom of the well casing is considered dry, and is not sampled. If the well contains 0.67 foot or more of water, an attempt is made to bail and/or sample as specified on the TSR.

Wells that are found to contain LPH are not purged or sampled. Instead, one casing volume of fluid is bailed from the well and the well is re-sealed. Bailed fluids are placed in a container separate from normal purge water, and properly disposed.

Purging and Groundwater Parameter Measurement

TSR instructions may specify that a well not be purged (no-purge sampling), be purged using low-flow methods, or be purged using conventional pump and/or bail methods. Conventional purging generally consists of pumping or bailing until a minimum of three casing volumes of water have been removed or until the well has been pumped dry. Pumping is generally accomplished using submersible electric or pneumatic diaphragm pumps.

During conventional purging, three groundwater parameters (temperature, pH, and conductivity) are measured after removal of each casing volume. Stabilization of these parameters, to within 10 percent, confirm that sufficient purging has been completed. In some cases, the TSR indicates that other parameters are also to be measured during purging. TRC commonly measures dissolved oxygen (DO), oxidation-reduction potential (ORP), and/or turbidity. Instruments used for groundwater parameter measurement are calibrated daily according to manufacturer's instructions.

Low-flow purging utilizes a bladder or peristaltic pump to remove water from the well at a low rate. Groundwater parameters specified by the TSR are measured continuously until they become stable in general accordance with EPA guidelines.

Purge water is generally collected in labeled drums for disposal. Drums may be left on site for disposal by others, or transported to a collection location for eventual transfer to a licensed treatment or recycling facility. In some cases, purge water may be collected directly from the site by a licensed vacuum truck company, or may be treated on site by an active remediation system, if so directed.

Groundwater Sample Collection

5

After wells are purged, or not purged, according to TSR instructions, samples are collected for laboratory analysis. For wells that have been purged using conventional pump or bail methods, sampling is conducted after the well has recovered to 80 percent of its original volume or after two hours if the well does not recover to at least 80 percent. If there is insufficient recharge of water in the well after two hours, the well is not sampled.

Samples are collected by lowering a new, disposable, ½-inchto 4-inch polyethylene bottom-fill bailer to just below the water level in the well. The bailer is retrieved and the water sample is carefully transferred to containers specified for the laboratory analytical methods indicated by the TSR. Particular care is given to containers for volatile organic analysis (VOAs) which require filling to zero headspace and fitting with Teflon-sealed caps.

After filling, all containers are labeled with project number (or site number), well designation, sample date, and the samplers initials, and placed in an insulated chest with ice. Samples remain chilled prior to and during transport to a state-certified laboratory for analysis. Sample container descriptions and requested analyses are entered onto a chain-of-custody form in order to provide instructions to the laboratory. The chain-of-custody form accompanies the samples during transportation to provide a continuous record of possession from the field to the laboratory. If a freight or overnight carrier transports the samples, the carrier is noted on the form.

For wells that have been purged using low-flow methods, sample containers are filled from the effluent stream of the bladder or peristaltic pump. In some cases, if so specified by the TSR, samples are taken from the sample ports of actively pumping remediation wells.

Sequence of Gauging, Purging, and Sampling

The sequence in which monitoring activities are conducted are specified on the TSR. In general, wells are gauged beginning with the least-affected well and ending with the well that has highest concentration based on previous analytic results. After all gauging for the site is completed, wells are purged and/or sampled from the least-affected well to the most-affected well.

Decontamination

In order to reduce the possibility of cross-contamination between wells, strict isolation and decontamination procedures are observed. Portable pumps are not used in wells with LPH. Technicians wear nitrile gloves during all gauging, purging and sampling activities. Gloves are changed between wells and more often if warranted. Any equipment that could come in contact with fluids are either dedicated to a particular well, decontaminated prior to each use, or discarded after a single use. Decontamination consists of washing in a solution of Liqui-nox and water and rinsing twice. The final rinse is in deionized water.

Exceptions

Additional tasks or non-standard procedures, if any, that may be requested or required for a particular site, and noted on the site TSR, are documented in field notes on the following pages.

1/5/04 version

FIELD MONITORING DATA SHEET

 Technician: David Tenney
 Job #/Task #: 4/05000/F420
 Date: 10-29-04

 Site # 7/24
 Project Manager Advience Collins
 Page 1 of 1

Well#	TOC	Time Gauged	Total Depth	Depth to Water	Depth to Product	Product Thickness (feet)	Time Sampled	Misc. Well Notes
MW-4	X	0428	24.84	18.13	0	0	0500	4"
MW-3	×	0432	25.01	17-29	0	0	0518	4"
MW-1		0436	24.76		or	0	0534	<i>Υ</i> "
MW-2							NS.	Paved over
· · · · · · · · · · · · · · · · · · ·			· -	 				
							-	
					· · · · · · · · · · · · · · · · · · ·			· · · · · · · · · · · · · · · · · · ·
							<u></u>	
							<u></u>	
			: !			<u> </u>		
		 					-	
							<u>.</u>	
<u> </u>					<u> </u>			
		:						· .
FIELD DATA	COMPL	ETE	o≱⁄oc		ÇØC	<u>W</u>	ELL BOX⁄C	DNDITION SHEETS
WTT CERTI	ICATE	······································	MANIFES	ST	DRUMMN	/ENTORY	TRAF	FIC CONTROL

GROUNDWATER SAMPLING FIELD NOTES

Technician: David Tenney Date: 10-29-04 Project No.: 410500-01/FA20 site: 7124diaphragm 0969 Well No .: _ MW-1 Purge Method: Depth to Product (feet): Depth to Water (feet): 16.14 LPH & Water Recovered (gallons): 0 Total Depth (feet): 24.76 Casing Diameter (Inches): 4 Water Column (feet): 8.6.2 80% Recharge Depth (feet): 17,96 1 Well Volume (gallons):_ Conduc-Temperature Depth Volumé Time D.O. Turbidity tivity Purged : Stop To Water (E.G (úS/cm) (gallons) (feet) 16.2 159.9N 0523 6.90 145.4 18.1 12 6,60 138.5 18.7 18 0530 Time Sampled Total Gallons Purged Static at Time Sampled 0934 18 17.55 Comments: Purge Method:____ Well No.: Depth to Product (feet): Depth to Water (feet): LPH & Water Recovered (gallons):____ Total Depth (feet): Casing Diameter (Inches):_____ Water Column (feet):______ 1 Well Volume (gallons):____ 80% Recharge Depth (feet):_____ Temperature Depth Volume Conduc-Time Lime Turbidity tivity pH : To Water Purged Stop Start (F,C) (uS/cm) (gallons) (feet) Static at Time Sampled Total Gallons Purged Time Sampled Comments:

GROUNDWATER SAMPLING FIELD NOTES

Site: 71	2 L		Technician:	Varid 1		_	10	- 1011
216	27		Project No.:	410500-	01/FAZO		Date: 10	-29-04
,	Mw-4			Purge Method			a .	
Vell No.:	10 1	2		Depth to Prod		Q		
epth to Wate	er (feet): 19.1	<u>7</u>		LPH & Water	Recovered (a	allons): -0		
otal Depth (f	feet): 24.94	1	-	Casing Diame				
Vater Colum	n (feet): 6.7	10 117		•	e (gaflons):		 _	
0% Recharg	je Depth (feet):	1 1-7-		TATER TORUN	(90,10,10,10,10,10,10,10,10,10,10,10,10,10	<u></u>		tangan ing panggan pan
. Time	Time	Depth	Volume	Conduc-	Temperature	pΗ	Turbidity	D.O. *
Start	Stop	To Water (feet)	Purged (gallons)	tivity (dS/cm)	(F.6)		Toroiday	
<u>0450</u>		21.8(#EU)	4	149.6N	16-8	6.54	<i>*</i>	
0-190	\$84.		a	146.1	18,1	6-61	able	
			17	140.2		6.48	4.1	
	0458		17	170-2	187	10.40	<u> </u>	
						<u> </u>		
				<u> </u>				<u> </u>
	tic at Time San	ipled	To	otal Gallons Pu	rged	1		pled
	8-44			12	<u>. </u>		0500	:
							•	100
			<u></u>			<u> </u>		
Vell No.:	Mw-3		1	Purge Method	diaphi	ragm o	969	
enth to Wat	MW-3 ter (feet):	7.29	\(\frac{1}{2}\)		•		969	
enth to Wat	ter (feet)	7.29 .01	\(\frac{1}{2}\)	Depth to Prod	i: di aphi luct (feet): Recovered (g	9	-	
Depth to Wat Fotal Depth (ter (feet):[(feet):	. 0 \ 2	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	Depth to Prod	luct (feet):	allons): #	-	
Depth to Wat Fotal Depth (Water Colum	ter (feet)	2	· · · · · · · · · · · · · · · · · · ·	Depth to Prod	luct (feet): Recovered (g eter (Inches):	allons): #	-	·.
Depth to Wat Fotal Depth (Water Colum 80% Rechan	ter (feet):	, 0 \ 2 		Depth to Prod LPH & Water Casing Diame 1 Well Volume	luct (feet): Recovered (g eter (Inches): e (gallons):	allons): 6 4 5	-	
Depth to Wat Fotal Depth (Water Colum 80% Rechan	ter (feet):	, 0 \ 2 		Depth to Prod LPH & Water Casing Diame	luct (feet): Recovered (g eter (Inches): e (gallons): Temperature	allons): 6 4 5	-	D.O. *
Depth to Wat Fotal Depth (Water Colum 80% Rechard	ter (feet):	, 0 \ 2 	Purged (gallons)	Depth to Prod LPH & Water Casing Diame 1 Well Volume Conductivity (uS/cm)	luct (feet): Recovered (g eter (Inches):_ e (gallons): Temperature (F, 6)	allons): 6 4 5		D.O.*
Depth to Wat Fotal Depth (Water Colum 80% Rechard Time Start	ter (feet):	.0\ 2 B.63 Depth To Water	Purged	Depth to Prod LPH & Water Casing Diame 1 Well Volume Conductivity (uS/cm)	luct (feet): Recovered (g eter (Inches):_ e (gallons): Temperature (F, 6)	pH 6.98		D.O.
Depth to Wat Fotal Depth (Water Colum 80% Rechan	ter (feet):	.0\ 2 B.63 Depth To Water	Purged (gallons)	Depth to Prod LPH & Water Casing Diame 1 Well Volume Conduc- fivity	luct (feet): Recovered (g eter (Inches):_ e (gallons): Temperature (F, 6)	pH 6.98		D.O.
Depth to Wat Fotal Depth (Water Colum 80% Rechard Time Start	ter (feet):	.0\ 2 B.63 Depth To Water	Purged (gallons) F 10	Depth to Prod LPH & Water Casing Diame 1 Well Volume Conductivity (uS/cm) 1440x 148.3	recovered (geter (Inches):e (gallons): Temperature (F, 6) 15.3	6.98	Turbidity	D.O.
Depth to Wat Fotal Depth (Water Colum 80% Rechard Hine Start	ter (feet):	.0\ 2 B.63 Depth To Water	Purged (gallons)	Depth to Prod LPH & Water Casing Diame 1 Well Volume Conductivity (uS/cm)	luct (feet):	pH 6.98	Turbidity	D.O.
Depth to Wat Total Depth (Water Colum 10% Rechard Time Start	ter (feet):	.0\ 2 B.63 Depth To Water	Purged (gallons) F 10	Depth to Prod LPH & Water Casing Diame 1 Well Volume Conductivity (uS/cm) 1440x 148.3	recovered (geter (Inches):e (gallons): Temperature (F, 6) 15.3	6.98	Turbidity	D.O.
Depth to Water Column Start Off 0 Off 0	ter (feet):	Depth To Water (feet)	Purged (gallons) Fi 10 15	Depth to Prod LPH & Water Casing Diame 1 Well Volume Conductivity (uS/cm) 1440x 148.3	recovered (geter (Inches):_e (gallons): Temperature (F 6) 15.3 17.8	6.98	Turbidity	

4

>£

Comments:

STATEMENT OF NON-COMPLETION OF JOB

DATE OF EVENT:	10-29-04	STATION NUM	BER: -7124
NAME OF TECH:	David Tenney	CALLED	GORDON:
CALLED PM:	NAME OF	PM CALLED:	
WELL NUMBER:	MW-Z STAT	TEMENT FROM PM_	OR TECH
10611 151	LAVE & OVEL		· · · · · · · · · · · · · · · · · · ·
	•	,	
'	STATE		OR TECH
•			`
		•	
			OR TECH
WELL NUMBER:			OR TECH
 ,.			BAGE loft



TRC Alton Geoscience-Irvine

November 15, 2004

21 Technology Drive Irvine, CA 92718

Attn.:

Anju Farfan

Project#: 41050001FA20

Project:

Conoco Phillips # 7124

Site:

10151 International Blvd., Oakland

Attached is our report for your samples received on 11/01/2004 12:25 This report has been reviewed and approved for release. Reproduction of this report is permitted only in its entirety.

Please note that any unused portion of the samples will be discarded after 12/16/2004 unless you have requested otherwise.

We appreciate the opportunity to be of service to you. If you have any questions, please call me at (925) 484-1919.

You can also contact me via email. My email address is: dsharma@stl-inc.com Sincerely,

Dimple Sharma

Project Manager

haema



Gas/BTEX Fuel Oxygenates by 8260B

TRC Alton Geoscience- Irvine

Attn.: Anju Farfan

21 Technology Drive Irvine, CA 92718

Phone: (949) 341-7440 Fax: (949) 753-0111

Project: 41050001FA20

Conoco Phillips # 7124

Received: 11/01/2004 12:25

Site: 10151 International Blvd., Oakland

Samples Reported

Sample Name	Date Sampled	Matrix	Lab#
MW-4	10/29/2004 05:00	Water	1
MW-3	10/29/2004 05:18	Water	2
MW-1	10/29/2004 05:34	Water	3



Gas/BTEX Fuel Oxygenates by 8260B

TRC Alton Geoscience-Irvine

Attn.: Anju Farfan

21 Technology Drive Irvine, CA 92718

Phone: (949) 341-7440 Fax: (949) 753-0111

Project: 41050001FA20

Conoco Phillips # 7124

Received: 11/01/2004 12:25

Site: 10151 International Blvd., Oakland

Prep(s):

5030B

Test(s):

8260FAB

Sample ID: MW-4

Lab ID:

2004-11-0060 - 1

Sampled: 10/29/2004 05:00 Extracted:

11/9/2004 10:44

Matrix:

Water

QC Batch#: 2004/11/09-1B.66

Analysis Flag: L2 (See Legend and Note Section)

Compound	Conc.	RL	Unit	Dilution	Analyzed	Flag
Gasoline	2700	250	ug/L	5.00	11/09/2004 10:44	
Benzene	ND	2.5	ug/L	5.00	11/09/2004 10:44	
Toluene	ND	2.5	ug/L	5.00	11/09/2004 10:44	
Ethylbenzene	ND	2.5	ug/L	5.00	11/09/2004 10:44	
Total xylenes	ND	5.0	ug/L	5.00	11/09/2004 10:44	
tert-Butyl alcohol (TBA)	63	25	ug/L	5.00	11/09/2004 10:44	
Methyl tert-butyl ether (MTBE)	76	2.5	ug/L	5.00	11/09/2004 10:44	
Di-isopropyl Ether (DIPE)	ND	5.0	ug/L	5.00	11/09/2004 10:44	
Ethyl tert-butyl ether (ETBE)	ND	2.5	ug/L	5.00	11/09/2004 10:44	
tert-Amyl methyl ether (TAME)	ND	2.5	ug/L	5.00	11/09/2004 10:44	
1,2-DCA	ND	2.5	ug/L	5.00	11/09/2004 10:44	
EDB	ND	2.5	ug/L	5.00	11/09/2004 10:44	
Ethanol	ND	250	ug/L	5.00	11/09/2004 10:44	
Surrogate(s)			-			
1,2-Dichloroethane-d4	94.3	73-130	%	5.00	11/09/2004 10:44	
Toluene-d8	95.2	81-114	%	5.00	11/09/2004 10:44	



Gas/BTEX Fuel Oxygenates by 8260B

TRC Alton Geoscience-Irvine

Attn.: Anju Farfan

21 Technology Drive Irvine, CA 92718

Phone: (949) 341-7440 Fax: (949) 753-0111

Project: 41050001FA20

Conoco Phillips # 7124

Received: 11/01/2004 12:25

Site: 10151 International Blvd., Oakland

Prep(s): 5030B

Sample ID: MW-3

Sampled:

Matrix:

10/29/2004 05:18

Water

Analysis Flag: L2 (See Legend and Note Section)

Test(s): 8260FAB

2004-11-0060 - 2 Lab ID:

Extracted: 11/9/2004 11:07

QC Batch#: 2004/11/09-1B.66

Compound	Conc.	RL	Unit	Dilution	Analyzed	Flag
Gasoline	4600	500	ug/L	10.00	11/09/2004 11:07	
Вепzепе	ND	5.0	ug/L	10.00	11/09/2004 11:07	
Toluene	ND	5.0	ug/L	10.00	11/09/2004 11:07	
Ethylbenzene	13	5.0	ug/L	10.00	11/09/2004 11:07	
Total xylenes	ND	10	ug/L	10.00	11/09/2004 11:07	
tert-Butyl alcohol (TBA)	ND	50	ug/L	10.00	11/09/2004 11:07	
Methyl tert-butyl ether (MTBE)	640	5.0	ug/L	10.00	11/09/2004 11:07	
Di-isopropyl Ether (DIPE)	ND	10	ug/L	10.00	11/09/2004 11:07	
Ethyl tert-butyl ether (ETBE)	ND	5.0	ug/L	10.00	11/09/2004 11:07	
tert-Amyl methyl ether (TAME)	ND	5.0	ug/L	10.00	11/09/2004 11:07	
1,2-DCA	ND	5.0	ug/L	10.00	11/09/2004 11:07	
EDB	ND	5.0	ug/L	10.00	11/09/2004 11:07	
Ethanol	ND	500	ug/L	10.00	11/09/2004 11:07	
Surrogate(s)						
1,2-Dichloroethane-d4	90.1	73-130	%	10.00	11/09/2004 11:07	
Toluene-d8	92.7	81-114	%	10.00	11/09/2004 11:07	



Gas/BTEX Fuel Oxygenates by 8260B

TRC Alton Geoscience-Irvine

Attn.: Anju Farfan

21 Technology Drive Irvine, CA 92718

Phone: (949) 341-7440 Fax: (949) 753-0111

Project: 41050001FA20

Conoco Phillips # 7124

Received: 11/01/2004 12:25

Site: 10151 International Blvd., Oakland

Prep(s): 5030B

Test(s):

8260FAB

Sample ID: MW-1

10/29/2004 05:34

Lab ID:

2004-11-0060 - 3

Sampled: Matrix:

Water

Extracted: 11/8/2004 15:22

QC Batch#: 2004/11/08-2B.66

Compound	Conc.	RL	Unit	Dilution	Analyzed	Flag
Gasoline	ND	50	ug/L	1.00	11/08/2004 15:22	
Benzene	ND	0.50	ug/L	1.00	11/08/2004 15:22	
Toluene	ND	0.50	ug/L	1.00	11/08/2004 15:22	
Ethylbenzene	ND	0.50	ug/L	1.00	11/08/2004 15:22	
Total xylenes	ND	1.0	ug/L	1.00	11/08/2004 15:22	
tert-Butyl alcohol (TBA)	ND	5.0	ug/L	1.00	11/08/2004 15:22	
Methyl tert-butyl ether (MTBE)	ND	0.50	ug/L	1.00	11/08/2004 15:22	
Di-isopropyl Ether (DIPE)	ND	1.0	ug/L	1.00	11/08/2004 15:22	
Ethyl tert-butyl ether (ETBE)	ND	0.50	ug/L	1.00	11/08/2004 15:22	
tert-Amyl methyl ether (TAME)	ND	0.50	ug/L	1.00	11/08/2004 15:22	
1,2-DCA	ND	0.50	ug/L	1.00	11/08/2004 15:22	
EDB	ND	0.50	ug/L	1.00	11/08/2004 15:22	
Ethanol	ND	50	ug/L	1.00	11/08/2004 15:22	
Surrogate(s)				İ		
1,2-Dichloroethane-d4	96.8	73-130	%	1.00	11/08/2004 15:22	
Toluene-d8	93.7	81-114	%	1.00	11/08/2004 15:22	



Gas/BTEX Fuel Oxygenates by 8260B

TRC Alton Geoscience-Irvine

Attn.: Anju Farfan

21 Technology Drive Irvine, CA 92718

Phone: (949) 341-7440 Fax: (949) 753-0111

Project: 41050001FA20

Conoco Phillips # 7124

Received: 11/01/2004 12:25

Site: 10151 International Blvd., Oakland

Batch QC Report

Prep(s): 5030B Method Blank

MB: 2004/11/08-2B.66-013

Water

Test(s): 8260FAB QC Batch # 2004/11/08-2B.66

Date Extracted: 11/08/2004 09:13

Compound	Conc.	RL	Unit	Analyzed	Flag
Gasoline	ND	50	ug/L	11/08/2004 09:13	
tert-Butyl alcohol (TBA)	ND	5.0	ug/L	11/08/2004 09:13	
Methyl tert-butyl ether (MTBE)	ND	0.5	ug/L	11/08/2004 09:13	
Di-isopropyl Ether (DIPE)	ND	1.0	ug/L	11/08/2004 09:13	
Ethyl tert-butyl ether (ETBE)	ND	0.5	ug/L	11/08/2004 09:13	
tert-Amyl methyl ether (TAME)	ND	0.5	ug/L	11/08/2004 09:13	
1,2-DCA	ND	0.5	ug/L	11/08/2004 09:13	
EDB	ND	0.5	ug/L	11/08/2004 09:13	
Benzene	ND	0.5	ug/L	11/08/2004 09:13	
Toluene	ND	0.5	ug/L	11/08/2004 09:13	
Ethylbenzene	ND	0.5	ug/L	11/08/2004 09:13	
Total xylenes	ND	1.0	ug/L	11/08/2004 09:13	
Ethanol	ND	50	ug/L	11/08/2004 09:13	
Surrogates(s)					
1,2-Dichloroethane-d4	88.8	73-130	%	11/08/2004 09:13	
Toluene-d8	94.0	81-114	%	11/08/2004 09:13	



Gas/BTEX Fuel Oxygenates by 8260B

TRC Alton Geoscience- Irvine

Attn.: Anju Farfan

21 Technology Drive Irvine, CA 92718

Phone: (949) 341-7440 Fax: (949) 753-0111

Project: 41050001FA20

Conoco Phillips # 7124

Received: 11/01/2004 12:25

Site: 10151 International Blvd., Oakland

Batch QC Report

Prep(s): 5030B Method Blank

Water

Test(s): 8260FAB QC Batch # 2004/11/09-1B.66

MB: 2004/11/09-1B.66-012

Date Extracted: 11/09/2004 10:12

Compound	Conc.	RL	Unit	Analyzed	Flag
Gasoline	ND	50	ug/L	11/09/2004 10:12	
tert-Butyl alcohol (TBA)	ND	5.0	ug/L	11/09/2004 10:12	
Methyl tert-butyl ether (MTBE)	ND	0.5	ug/L	11/09/2004 10:12	
Di-isopropyl Ether (DIPE)	ND	1.0	ug/L	11/09/2004 10:12	
Ethyl tert-butyl ether (ETBE)	ND	0.5	ug/L	11/09/2004 10:12	
tert-Amyl methyl ether (TAME)	ND	0.5	ug/L	11/09/2004 10:12	
1,2-DCA	ND	0.5	ug/L	11/09/2004 10:12	
EDB	ND	0.5	ug/L	11/09/2004 10:12	
Benzene	ND	0.5	ug/L	11/09/2004 10:12	
Toluene	ND	0.5	ug/L	11/09/2004 10:12	
Ethylbenzene	ND	0.5	ug/L	11/09/2004 10:12	
Total xylenes	ND	1.0	ug/L	11/09/2004 10:12	
Ethanol	ND	50	ug/L	11/09/2004 10:12	
Surrogates(s)					
1,2-Dichloroethane-d4	88.4	73-130	%	11/09/2004 10:12	
Toluene-d8	94.4	81-114	%	11/09/2004 10:12	



Gas/BTEX Fuel Oxygenates by 8260B

TRC Alton Geoscience-Irvine

Attn.: Anju Farfan

21 Technology Drive Irvine, CA 92718

Phone: (949) 341-7440 Fax: (949) 753-0111

Project: 41050001FA20

Conoco Phillips # 7124

Received: 11/01/2004 12:25

Site: 10151 International Blvd., Oakland

Batch QC Report

Prep(s): 5030B

Test(s): 8260FAB

Laboratory Control Spike

Water

QC Batch # 2004/11/08-2B.66

LCS

2004/11/08-2B.66-050

Extracted: 11/08/2004

Analyzed: 11/08/2004 08:50

LCSD

Compound	Conc.	ug/L	Exp.Conc.	Reco	vегу %	RPD	Ctrl.Lin	nits %	Flags		
Compound	LCS	LCSD		LCS	LCSD	%	Rec.	RPD	LCS	LCSD	
Methyl tert-butyl ether (MTBE) Benzene Toluene	23.8 27.6 27.2		25 25 25	95.2 110.4 108.8			65-165 69-129 70-130	20 20 20			
Surrogates(s) 1,2-Dichloroethane-d4 Toluene-d8	414 462		500 500	82.8 92.4			73-130 81-114	1 1			



Gas/BTEX Fuel Oxygenates by 8260B

TRC Alton Geoscience-Irvine

Attn.: Anju Farfan

21 Technology Drive Irvine, CA 92718

Phone: (949) 341-7440 Fax: (949) 753-0111

Project: 41050001FA20

Conoco Phillips # 7124

Received: 11/01/2004 12:25

Site: 10151 International Blvd., Oakland

Batch QC Report

Prep(s): 5030B

Test(s): 8260FAB

Laboratory Control Spike

Water

QC Batch # 2004/11/09-1B.66

LCS

2004/11/09-1B.66-050

Extracted: 11/09/2004

Analyzed: 11/09/2004 09:50

LCSD

Compound	Сопс.	ug/L	Exp.Conc.	Recov	⁄егу %	RPD	Ctrl.Lin	nits %	Fla	igs
<u> </u>	LCS	LCSD		LCS	LCSD	%	Rec.	RPD	LCS	LCSD
Methyl tert-butyl ether (MTBE)	26.5		25	106.0			65-165	20		
Benzene	27.7		25	110.8			69-129	20		
Toluene	27.1		25	108.4			70-130	20		
Surrogates(s)										
1,2-Dichloroethane-d4	420		500	84.0			73-130			
Toluene-d8	470	<u></u>	500	94.0			81-114			



Gas/BTEX Fuel Oxygenates by 8260B

TRC Alton Geoscience-Irvine

Attn.: Anju Farfan

21 Technology Drive Irvine, CA 92718

Phone: (949) 341-7440 Fax: (949) 753-0111

Project: 41050001FA20

Conoco Phillips # 7124

Received: 11/01/2004 12:25

Site: 10151 International Blvd., Oakland

Batch QC Report

Prep(s): 5030B

Test(s): 8260FAB

Matrix Spike (MS/MSD)

Water

QC Batch # 2004/11/08-2B.66

MS/MSD

Lab ID: 2004-11-0054 - 002

Extracted: 11/08/2004 Analyzed: 11/08/2004 10:29

Dilution:

1.00

MSD:

MS:

2004/11/08-2B.66-052

2004/11/08-2B.66-029

Extracted: 11/08/2004

Analyzed:

11/08/2004 10:52

Dilution:

1.00

Compound	Conc.	ug/L		Spk.Level	R	ecovery	%	Limits	s %	Flags		
Composite	мѕ	MSD	Sample	ug/L	MS	MSD	RPD	Rec.	RPD	мѕ	MSD	
Methyl tert-butyl ether	27.7	24.5	ND	25	110.8	98.0	12.3	65-165	20			
Benzene	28.6	27.0	ND	25	114.4	108.0	5.8	69-129	20			
Toluene	28.7	27.8	ND	25	114.8	111.2	3.2	70-130	20			
Surrogate(s)												
1,2-Dichloroethane-d4	428	425		500	85.6	85.0		73-130				
Toluene-d8	478	495		500	95.7	99.0		81-114				



Gas/BTEX Fuel Oxygenates by 8260B

TRC Alton Geoscience- Irvine

Attn.: Anju Farfan

21 Technology Drive Irvine, CA 92718

Phone: (949) 341-7440 Fax: (949) 753-0111

Project: 41050001FA20

Conoco Phillips # 7124

Received: 11/01/2004 12:25

Site: 10151 International Blvd., Oakland

Batch QC Report

Prep(s): 5030B

Test(s): 8260FAB

Matrix Spike (MS/MSD)

2004/11/09-1B.66-037

Water

QC Batch # 2004/11/09-1B.66

MS/MSD

·u.o.

Lab ID: 2004-11-0101 - 004

IVISANISE

MS:

_

Extracted: 11/09/2004

Analyzed:

11/09/2004 12:37

Dilution:

1.00

MSD: 2004/11/09-1B.66-059

Extracted: 11/09/2004

Analyzed:

11/09/2004 12:59

Dilution:

1.00

Compound	Conc.	u	g/L	Spk.Level	R	ecovery	%	Limits	· %	Flags		
	MS	MSD	MSD Sample		мѕ	MSD	RPD	Rec.	RPD	MS	MSD	
Methyl tert-butyl ether Benzene Toluene	104 29.6 26.6	108 27.7 26.5	74.2 ND ND	25 25 25	119.2 118.4 106.4	135.2 110.8 106.0	12.6 6.6 0.4	65-165 69-129 70-130	20 20 20			
Surrogate(s) 1,2-Dichloroethane-d4 Toluene-d8	508 478	497 483		500 500	101.6 95.6	99.4 96.6		73-130 81-114				



Gas/BTEX Fuel Oxygenates by 8260B

TRC Alton Geoscience-Irvine

Attn.: Anju Farfan

21 Technology Drive Irvine, CA 92718

Phone: (949) 341-7440 Fax: (949) 753-0111

Project: 41050001FA20

Conoco Phillips # 7124

Received: 11/01/2004 12:25

Site: 10151 International Blvd., Oakland

Legend and Notes

Analysis Flag

L2

Reporting limits were raised due to high level of analyte present in the sample.



Submission #:2004 0060	eceipt Checklist
Checklist completed by: (initials) MV Date: 11 0	
Courier name: STL San Francisco 🗆 Client	
Custody seals intact on shipping container/samples	Not YesNo Present_\
Chain of custody present?	Yes_VNo
Chain of custody signed when relinquished and received?	Yes
Chain of custody agrees with sample labels?	YesNo
Samples in proper container/bottle?	YesNo
Sample containers intact?	YesNo
Sufficient sample volume for indicated test?	YesNo
All samples received within holding time?	YesNo
Container/Lemb Blank temperature in compliance $(4^0\mathrm{G}\pm2)$? Polentialize as on for $>6\mathrm{G}\pm1$ (remelted Π), Ice in bags $\langle\Pi\rangle$. Not sampled <4 h. ago 2Π . Sampled <4 h. ago 2Π . The not required (e.g. air or bulk sampled).	
Water - VOA vials have zero headspace?	No VOA vials submittedYesNo
(if bubble is present, refer to approximate bubble size and itemiz	e in comments as S (small \sim O), M (medium \sim O) or L (large \sim O)
Water - pH acceptable upon receipt? ☐ Yes ☐ No	
□ pH adjusted – Preservative used: □ HNO ₃ □ HCl □ H ₂ Sc	O₄ □ NaOH □ ZnOAc –Lot #(s)
For any item check-listed "No", provided detail of discrepa	ncy in comment section below:
Comments:	
Project Management [Routing for instruction	of indicated discrepancy(ies)]
Project Manager: (initials) Date:/	_/04 Client contacted: ☐ Yes ☐ No
Summary of discussion:	
Corrective Action (per PM/Client):	

STL-San Francisco

ConocoPhillips Chain Of Custody Record

95257

1220 Quarry Lane

Pleasanton, CA 94566

(925) 484-1919 (925) 484-1096 fax

ConocoPhillips Site Manager: INVOICE REMITTANCE ADDRESS:

2004-11-0060 CONOCOPHILLIPS
Attn: Dee Hutchinson
3611 South Harbor, Suite 200
Santa Ana, CA. 92704

ConocoPhillips Work Order Number
1634 TRC 500
ConocoPhillips CostObject

DATE: 10 - 29-09

PAGE: 1 of 1 *

SAMPLING COMPANY:		Valid Vali	Je ID:			lcom	OCÓPH	III LIP É	SITENI	MRED						L_		······································	GLOBA	ID NO					
TRC		7 457 0 7 467	IV.				م م ا	1121	4	marker marker	1.1.	4-						1000							
ADDRESS:		L	<u>-</u>			SITE	ADDRE	SS (St	reet and	写。[』 Cityl:	¥ ***	1							ONOC		-	MANAG	ER;		
21 Technology Drive, Irvir				 		10	15	1 7	nter	noi Ho	nal	Ŗ	lvd	. 0	nkl	and		Thomas H. Kosel							
PROJECT CONTACT (Hardcopy or Anju Farfan	PDF Report to):					EOF	EDF DELIVERABLE TO (RP or Dasignee): PHONE NO.:						E-MAIL: LAB USE ONLY												
TELEPHONE:	FAX:	E-MAIL				I_{Pet}	er Th	oms	on, T	RC .				١,	340.3	41-74	n.	- (5 USE:	• • • • • • • • • • • • • • • • • • •	
949-341-7440	949-753-0111	4		olutions		E .				itions.	com				3-3-0		-							n de la	BOT GPG-B COLUMN TO BE
sampler name(s) (print): David Tenn	*	CONSUL		OO1/FA20		REQUESTE								D AN	ALYS	ES	-								
TURNAROUND TIME (CALEND	AR DAYS):	_				1	Π	tes	S S	_		Ī.,										1	ПП	······································	·· - · ·
D 14 DAYS □ 7 DAYS □ 7	Hours 🔲 48 Hours	□ 24 HO	URS 🔲 LE	SS THAN 2	4 HOURS	$\left\{ \right.$		8260B - TPHg / BTEX / 8 Oxygenates	8260B - TPHg / BTEX / 8 oyxgenates + methanol (8015M)	8260B - Full Scan VOCs (does not include oxygenates)		8015M / 8021B - TPHg/BTEX/MtBE	Š	20	2608	æ								1	FIELD NOTES:
SPECIAL INSTRUCTIONS OF	R NOTES:	HECKBO	X IF EDD	SNEEDEC	2	۽ ا	Щ.	ő	Š	9		Ĭ	UTotal OSTLC OTCLP		· ke	760									
						Extractable	- TPHg/BTEX/MtBE	8/)	5	္လိ	s es	9/8	ပ္	8260										Co	ntainer/Preservative or PID Readings
						Į.	Ž	Ē	E 8	tes)	8270C - Semi-Volatiles	I I	IST	20	l `	20								¢	r Laboratory Notes
				•		μÛ	lé	9 / E	1 B	Scal	۱	8	=	TEPH by	-	٨									
						.TPHd	ΙŽ	Ĭ	품증	il x	E	621	Tot	土	BI EX/MT	sax oa	ŀ								20-
* Field Point name only re	equired if different from	n Sampl	e ID				1-	3.1	F a	a. F	13	=		6		<u></u>	1								
Sample identific	ation/Field Point	SAN	PLING	MATRIX	NO. OF	8015m	8260B	909	760E	1990 Cluc	100	15	Lead	+-	<u> </u>	20			ł	l		}		TÉMPÉR	ATURE ON RECEIPT C°
owy Na	me*	DATE			CONT.	≋	88	8	8 +	2. 8	123	18	تــــــــــــــــــــــــــــــــــــــ				Ц_								
Mw-	4	6-20	0500	6W	3									Ϋ́	Ϋ́	X									
Mw-	3		0518												\prod	П									
Mw-	1	V	0534	V	1							\top		V	V	V						1	\Box		
						1	T	·	 			 			_				1	_	\top	+	T		
					<u> </u>	-		<u> </u>	 	 	-	+	†		+	\dashv			\neg	_		+	-		
		1	 	,	†	╁	┼		\vdash	 -	-	+	 		+	+	+-					+-	+1		
			 	<u> </u>	 	╁╌		-	-	_	-	+	-	\vdash	-	-		\vdash		-	_	+-	┼╌┤		
		-	 	<u> </u>	 	┼┈	 	├	-		┼	-	+-	\vdash	\dashv	-				+		-	-		
		ļ		-		╀	┼-			<u> </u>	<u> </u>	-	ļ	-	\dashv	_			_			+	<u> </u>		
		<u> </u>	ļ		<u> </u>	 	<u> </u>	<u> </u>		ļ	╄.	_	<u> </u>				_				\bot				
		į							<u> </u>				<u> </u>								<u>.</u>				
Relinquished by: (Signature)	TUL			1	REFO		a to	<u></u>										Dale:	10	-20	4-04	/	Time:		129
Relinquished by (Signature)	700-			Received	Stapella	1	1			١								Date:				 -	Time		
Relinguished by Stopping				Mecalived I	y Janes Alle	$\frac{1}{2}$		/)			_	2.		-				Dale	"	ه ۲	/		Time:	1/3	8
11/1/69	HE					1		1			1				-			Jane.	///	0	1		Inne:	113 121	<u>.</u>
/ / /								7/	_							•		<u></u>						0/40/0	

STATEMENTS

Purge Water Disposal

Non-hazardous groundwater produced during purging and sampling of monitoring was accumulated at TRC's groundwater monitoring facility at Concord, California, for transportation by Onyx Transportation, Inc., to the ConocoPhillips Refinery at Rodeo, California. Disposal at the Rodeo facility was authorized by ConocoPhillips in accordance with "ESD Standard Operating Procedures – Water Quality and Compliance", as revised on February 7, 2003. Documentation of compliance with ConocoPhillips requirements is provided by an ESD Form R-149, which is on file at TRC's Concord Office. Purge water suspected of containing potentially hazardous material, such as liquid-phase hydrocarbons, was accumulated separately in a drum for transportation and disposal by Filter Recycling, Inc.

Limitations

The fluid level monitoring and groundwater sampling activities summarized in this report have been performed under the responsible charge of a California Registered Geologist or Registered Civil Engineer and have been conducted in accordance with current practice and the standard of care exercised by geologists and engineers performing similar tasks in this area. No warranty, express or implied, is made regarding the conclusions and professional opinions presented in this report. The conclusions are based solely upon an analysis of the observed conditions. If actual conditions differ from those described in this report, our office should be notified.