FAXCOVER

3 LIC 6690

EXERPTION & ASSOCIATES, INC.

545 PARROTT STREET, SAN JOSE, CA 95112

(408) 271-2200, (408) 271-2201 FAX

OFFICES SERVING THE WESTERN UNITED STATES

SUCEI
Attention: Ms. Susan Hugo
Fax #: 510-337-9335
Telephone #:
Company Name: Alameda County
Date: <u>7/28/00</u>
From: Alex Gallego
COMMENTS: Susan: Attached is the information regarding the installation of the piezometers and the groundwater sampling for lead. Based on the uniform lithology at the site site (i.e.: 5 feet of fill and then Merritt Sands), we did not prepare boring logs. I have also included the revised figure for the Conceputal Site Model/Risk Assessment, the revised contingency plan flow chart, and a revised site plan showing the elevator shafts. All will be included in the final documents. Please call at your earliest convienence regarding my voice mail. Thank You.
Please advise us immediately if you do not receive complete transmittal or if you have received this transmittal in error.
No. of pages, including transmittal sheet <u>15</u> Original will not follow
Onginal will hot follow _x_Original will follow
_x Regular Mail
Courier
Federal Express
Other
GEOTECHNICAL ENVIRONMENTAL CONSTRUCTION TESTING







GEOTECHNICAL ENGINEERING • ENVIRONMENTAL ENGINEERING CONSTRUCTION TESTING & INSPECTION

July 26, 2000

Project No. 044-00006

Ms. Susan Hugo, Hazardous Materials Specialist Alameda County Health Care Services Agency Environmental Health Services 1131 Harbor Bay Parkway, Suite 230 Alameda, CA 94502

RE:

Proposed Commercial Development 720 Second Street and 229 Castro Street Oakland, California

Dear Ms. Hugo:

On behalf of M.A Mortenson Company (Mortenson), Krazan & Associates Inc. (Krazan) has prepared this letter to transmit documents related to the installation of piezometers and the collection of groundwater samples at the above referenced Site (Figure 1). The three piezometers were installed to assess shallow groundwater levels for the purposes of the proposed future construction at the Site. The locations of the monitoring wells are shown on Figure 2. The borings for the monitoring wells were drilled on May 25, 2000, using a truck-mounted, hollow-stem auger rig equipped with 8-inch augers. Drilling services were provided by Krazan. Because the lithologies at the subject site had been established, and the borings for the monitoring wells were within a few feet of previously-installed borings, sampling for lithologic purposes was limited to 5, 10, and 15 feet below the ground surface (BGS). The subsurface conditions were logged by a State-registered geologist from Krazan.

Based on the lithologies encountered at the subject site, piezometers were constructed to a depth of 20-feet BGS in all three piezometers. The screen interval was 9.5 to 19.5 feet BGS. The piezometers were constructed of flush-jointed, threaded, 2-inch I.D., Schedule 40 PVC casing with 0.020-inch machined slots. The filter pack consisted of #3 Lonestar Sand. The slot size and filter pack was selected with the intent to minimize the amount of native lithologic and filter pack material entering the monitoring well. During placement of the filter pack, the well casing was suspended in the augers. The augers were lifted 2 to 4 feet and the sand filter pack was poured into the annulus. The augers were then slowly lifted with sand filter pack placed "continuously" until the sand backfill was approximately 2 foot above the top of the screen. An approximately 2-foot thick layer of bentonite was placed above the sand filter pack. The

Project No. 044-00006 Page No. 2

annulus above the bentonite was backfilled with a cement grout slurry. The cement grout was extended to a depth of approximately 1-foot below the ground surface. Well construction details for the three piezometers are presented in Figure 3. Vaults equipped with traffic-rated covers were placed above the well casings and set in concrete. The vaults were set approximately 2-inches above the ground surface to allow for surface drainage away from the wells. A locking device was installed to minimize the likelihood of unauthorized access to the piezometers.


→?. Shapiloodis identified here

The sampling equipment was cleaned prior to sampling and between borings to minimize the likelihood of cross-contamination. The work was performed at the direction of a California-registered professional geologist from Krazan. Chain-of-custody (COC) procedures were used to document the handling and transport of samples from the time the samples were collected to the time they were delivered to the laboratory for analysis.

Following your request to add lead as a target analyte in groundwater as presented in your letter to Mortenson and the Port of Oakland dated June 23, 2000, Krazan collected groundwater samples from the three piezometers. Prior to the collection of groundwater samples, the piezometers were developed by surging and bailing. Development was conducted to remove fine-grained sediment that accumulated in the piezometer and filter pack, and to increase the hydraulic communication with the aquifer material. Following development, groundwater samples were collected from the wells with dedicated disposable bailers. The sampled groundwater was transferred to laboratory-supplied containers specific for the anticipated analyses. The samples were labeled with the sample number, collection date, and project number and retained on ice in an insulated chest. The samples were immediately delivered to Entech Analytical Labs, Inc. (Entech) of Sunnyvale, California, a State of California certified analytical laboratory (CA ELAP# 2346). The samples were filtered and preserved by Entech prior to analyses for lead in accordance, with Environmental Protection Agency (EPA) Method 200.7. Lead was not detected in the three groundwater samples. A copy of the laboratory analytical report and chain-of-custody form are attached to this letter.

Page No. 3

We hope that this letter, and the reports provided have fully addressed the concerns raised in your June 23 letter. If you have any further questions, please do not hesitate to contact me at (408) 271-2200.



Very truly yours, Krazan & Associates, Inc.

Director of Environmental Services

CC: Mr. Stuart Block, Cox, Castle & Nicholson, LLP


4082712201

Mr. Marvin Doster, Thomas Management West

Mr. James Fey

Mr. Douglas Herman, Port of Oakland

Ms. Yane Nordhav, Baseline Environmental, Inc.






MAP SOURCE:

USGS QUADRANGLE, 7.5-MINUTE (TOPOGRAPHIC) OAKLAND WEST (DATED 1993)

0 2,000 4,000 SCALE IN FEET (±)

VICINITY MAP	Scale: AS SHOWN	2/00
City Block Bound By: Second, Third, Castro, &	Drawn by: AJG	Approved by: AJG
Brush Streets Oakland, California	Project No. 044-00006	Figure No.





LOCATION MAP	Scale: Date AS SHOWN (02/00	
City Block Bound By: Second, Third, Castro, &	Drawn by: Appr	AJG ENGINEERS, GEOLOGISTS AND	razan
Brush Streets Oakland, California	Project No. Figur 044-0006	re No.	Vestern United States

4082712201

Krazan & Associates, Inc. Environmental Department

545 Parrott Street San Jose, California 95112 (408) 271-2200

SCREEN

19.5

20'

20'

FIGURE 3

WELL INSTALLATION DIAGRAM FOR MW-1, MW-2, AND MW-3 PROJECT: M.A. MORTENSON COMPANY PROJECT NO: <u>044-00006</u> DATE: <u>7/24/00</u> LOCATION-720 SECOND STREET, OAKLAND, CALIFORNIA DRILLED BY: KRAZAN & ASSOCIATES Total CAP Depth 20' Type: Locking Cap Assembly <u>╙╬╜╬╻╩╻╩╻╩╻╩п╩п╩п╩п╩╻╩╻╩╻╩╻╩╻╩╻╩</u> **WELL VAULT** Dia: 8" Type: BOART LONGYEAR WITH STEEL LID & GASKET **VAULT SETTING** ANNULAR SEAL Type: 6-SACK CEMENT GROUT 3/8" AGGREGATE **CONCRETE BLANK CASING** Dia: SCH 40 PVC Type: Top of bentonite scal BENTONITE SEAL 3/8" dia. hydrated Type: bentonite pellets Top of filter pack **FILTER PACK** Type: #3 LONESTAR SAND 9.5' Top of screen

Dia:

Hole Dia:

Type: Flush Thread 0.020

slotted SCH 40 PVC

Bottom of screen

Bottom of cap

Bottom of hole

Entech Analytical Labs, Inc.

525 Del Rey Avenue, Suite E • Sunnyvale, CA 94086 • (408) 735-1550 • Fax (408) 735-1554

June 30, 2000

Alex Gallego Krazan & Associates, Inc. 550 Parrott Street, Suite One San Jose, CA 95112

Order:

21165

Date Collected:

6/27/00

Project Name:

6/27/00

Project Number:

04400006

Date Received:

Project Notes:

P.O. Number:

On June 27, 2000, samples were received under documentented chain of custody. Results for the following

analyses are attached:

Matrix Liquid

Test

Method

Chemical analysis of these samples has been completed. Summaries of the data are contained on the following pages. USEPA protocols for sample storage and preservation were followed.

Entech Analytical Labs, Inc. is certified by the State of California (#2346). If you have any questions regarding procedures or results, please call me at 408-735-1550.

Sincerely,

Michelle L. Anderson

Lab Director

Entech Analytical Labs, Inc.

QC Batch #: WM000619

525 Dei Roy Avenue, Suite E **Зивручаю, СА 94086**

QUALITY CONTROL RESULTS SUMMARY

METHOD: ICP

Laboratory Control Spikes

Date Analyzed: 06/27/00 Date Digested: 06/26/00

Quality Control Sample: Blank Spike Matrix: Liquid

Units	mg/L										
PARAMETER	Method #	MB mg/L	SA mg/L	SR mg/L	SP mg/L	SF %R	SPD mg/L	SPD % R	RPD	%R	C LIMITS RPD
Antimony	200.7	<0.005	0.50	ND	0.54	108	0.55	111	2.2	75- 125	25.0
Arsenic	200.7	<0.005	0.50	ND	0.53	107	0.57	114	6.4	75- 125	25.0
Barium	200.7	<0.005	0.50	ND	0.54	107	0.54	108	0.9	75- 125	25.0
Beryllium	200.7	<0.005	0.50	ND	0.54	108	0.54	109	0.5	75- 125	25.0
Cadmium	200.7	<0.005	0.50	ND	0.53	105	0.52	105	0.5	75- 125	25.0
Chromium	200.7	<0.005	0.50	ND	0.53	107	0.54	109	1.9	75- 125	25.0
Cobalt	200.7	<0.005	0.50	ND	0.54	108	0.55	110	1.8	<i>75-</i> 125	25.0
Copper	200.7	<0.005	0.50	ND	0.54	107	0.53	107	0.1	75- 125	25.0
Lead	200.7	<0.005	0.50	ND	0.55	110	0.56	112	2.1	. 75- 125	į 25.0
Molybdenum	200.7	<0.005	0.50	ND	0.55	110	0.54	109	1.2	75- 125	25.0
Nickel	200.7	<0.005	0.50	ND	0.54	108	0.55	110	1.9	75- 125	25.0
Selenium	200.7	<0.005	0.50	ND	0.61	122	0.61	121	0.1	75- 125	25.0
Silver	200.7	<0.005	0.50	ND	0.53	106	0.53	105	0.4	75 - 125	25.0
Thallium	200.7	<0.005	0.50	סא	0.48	96	0.48	96	0.2	75- 125	25.0
Vanadium	200.7	< 0.005	0.50	ND	0.52	105	0.53	107	1.6	75- 12 <i>5</i>	25.0
Zinc	200.7	<0.005	0.50	ND	0.55	110	0.55	111	0.7	75- 1 25	25.0

Definition of Terms:

MB: Method Blank

nc. Not Calculated due to high levels of analyte found in sample

na: Not analyzed in QC batch

SA: Spike Added SR: Sample Result SP: Spike Result

SP (%R) Spike % Recovery

SPD Spike Duplicate Result

SPD (%R) Spike % Recovery

Entech Analytical Labs, Inc.

4082712201

CA ELAP# 2346

525 Del Rey Avenue, Suite E • Sunnyvale, CA 94086 • (408) 735-1550 • Fax (408) 735-1554

Krazan & Associates, Inc. 550 Parrott Street, Suite One San Jose, CA 95112

Attn: Alex Gallego

Date: 6/30/00
Date Received: 6/27/00
Project Name:
Project Number: 04400006

P.O. Number: Sampled By: Client

Certified Analytical Report

Order ID;	21165	Lab S	ample ID:	21165-(201	Client	Sample ID: M	W-1					
Sample Time:	11:30 AM	San	uple Date:	6/27/00			Matrix: Li	Liquid					
Parameter Lead	Result ND	DF 1	FQL 0.015	DLR 0.015	Units mg/L	PrepDate 6/27/00	Analysis Date 6/29/00	QC Batch ID WM000619	Method EPA 200.7				
Order ID:	21165	Lab S	ample ID:	21165-0	002	Client	W-2						
Sample Time:	11;45 AM	Sau	ple Date:	6/27/00			quid	•					
Parameter	Result	DF	PQL	DLR	Units	PrepDate	Analysis Date	QC Batck ID	Method				
Lead	ND	1	0.015	0.015	mg/L	6/27/00	6/29/08	WM000619	EPA 200.7				
Order ID:	21165	Lab S	ample ID:	21165-0	003	Client Sample ID: MW-3							
Sample Time:	12:00 PM	San	iple Date:	6/27/00			Matrix: Li	quid					
Parameter	Result	DF	PQL	DLR	Unita	PrepDate	Analysis Date	QC Batch ID	Method				
Lesd	מא	1	0.015	0.015	mg/L	6/27/00	6/29/00	WM000619	EPA 200.7				

DF - Dilution Factor

ND = Not Detected

DLR - Detection Limit Reported

PQL = Practical Quantitation Limit

Analysis performed by Entech Analytical Labs, Inc. (CA ELAP #2346)


Michelle L. Anderson, Laboratory Director

Page 1 of 1



Chain of Cha

	Cra	Z	ın							Cł	1a	in	1 (of		_							cord of 1		 8862/28/288
KRAZAN &	ASSOCIAT	ES, INC	Jose office)			T		Τ]		P	MARIA	Ī	RS											1
CLOVIS, C/ (209) 348-2	193612 200 FAX	: (209) 3		G	METALS						QRGANICS	R	PESTICIDES	NO.								CONTAINERS	oper m	INTERNACI	18:07
Project No. OU Sampler Signature	cm	on.	/	CAC METALS (TILE)	PR. POLLUTANY ME	YOTAL LEAD	TPH-DIESEL	TPH-GAS	BTXE.TPHGAS	OIL & GREASE	HALOGENATED OR	VOLATILE ORGANICS (EPA BOZO/BOZ)	DRGANDCHLORINE B PCB'S (EPA BORG)	PENTACHLOROPHENOL	CREOSOTE	OION (SAFE) INS	AS 81 (PLM)	oral Lead	Sec. 1.0.1.	Thloride &		NUMBER OF C	OBSERV COMIN	AIRONS/ IENTS	4882712281
SAMPLE NO	6-27-00	1130		ر ا	14	2	_	0.	1/									X	7	-		2	Filter and	Presime	} _
mw-2 mw-3		1145	mw 2			7		90 20	+ 1									X	X	×		2	Filter and Souther as	neded	
																									1
																					<u> </u>			80 JUN-27-13:	25 _~
																									KRAZAN
													_											· · · · · · · · · · · · · · · · · · ·	SAN
											-														3SOC N
RELINQUISHED BY			RECEIVED BY	7	I AC	LINO	II S IE	DAV						RECE	IVEDI	3V] · '"
MitAL 7	News	DATE 6/ 27/	Signature	(dade								DATE		Signal						- 0	WITE.	MET	TOTAL NUMBER OF SUBMITTED TO THE THOO OF SHIPMENT	HE LAB	
Printed Name Krazan	MAULY	/00 TIME 1320	Printed Marse Entech	TIME 1327	Pri	nted f	kume					THAE	1	Printe	i Nam	e .			-	T	ME		CIAL SHIPMENTAHAI STORAGE REQUIRE	ADLING MENTS	
Company RELINCUISHED BY	,	DATE	Company RECEIVED BY	OATE		LINO		D 8 Y				DATE	. 1	Comp	ery NEDI	BV (he	hora	iony)		1	ATE /	7:	Zhr T/A or	, Tutal lend Salasted	PAGE
Signature			Signature		L	gnatue							;	Signer	ure d	ZU (Ja.	1	4	1	57	3	- AH OV	·	12
Printed Name Company		TIME	Printed Name Company	TIME		inted i					_	TIME		Printe Comp	d Nam					T	ME		SULTS DUE:	WRITTEN	
		لسيسيط	<u>-</u>				7						<u> </u>		,_									·	_i



NO

Reuse on-site

"Hot Spot" Management Procedures Telecommunications Building, Oakland

materials already identified in previous investigation?
- visual staining not previously identified - odor not characteristic of contaminants previously identified
- air monitoring readings substantially

Is excavated soil different from fill

higher than those from the rest of the site
cebris in fill not previously identified
(including tanks or pipelines)

Notify Port, who will notify County

Stockpile soil on top of visqueen and cover with visqueen

Collect samples of soil for laboratory analysis
- 1 sample for every 100 cubic yards or a
minimum of 4 samples for entire volume,
whichever is greater

Analyze soil samples for suspected constituents

Calculate at percent UCL for constituents quantified above laboratory reporting limits

Confered results of

Compare Remediation Goals for industrial landuse

Coults Is 30 percent UCL greater than PRG?

YES

Dispose of soil at appropriately permitted landfill

NOTES:

1. FROM BASELINE ENVIRONMENTAL CONSULTING AND THE PORT OF OAKLAND.

CONTINGENCY PLAN FLOW	CHART	Scale	Date		
		AS SHOWN	07/00		
City Block Bound By:		Drawn by:	Approved b		
Second, Third, Castro,	&c	AJG	AJG		
Brush Streets		Project No.	Figure No.		
Oakland, California		044-00006	5		



NO

