

**SAMPLE SPREADSHEET FOR CALCULATION OF BENZENE RBSLs BASED ON ASTM RBCA GUIDANCE**  
**Leaking Underground Storage Tank Oversight Program**  
**Santa Clara Valley Water District**

INPUT PARAMETERS		SITE SPECIFIC		DEFAULT	
		Residential	Commercial	Residential	Commercial
Exposure	Target excess individual cancer risk [unitless]	TR	1.00E-06	1.00E-06	1.00E-06
	Adult body weight [kg]	BW	70	70	70
	Averaging time for carcinogens [years]	AT_c	70	70	70
	Daily indoor inhalation rate [m <sup>3</sup> /day]	IR_air_ind	15	20	15
	Daily outdoor inhalation rate [m <sup>3</sup> /day]	IR_air_out	20	20	20
	Soil ingestion rate, mg/day	IR_soil	100	50	100
	Exposure frequency [days/year]	EF	350	250	350
	Exposure duration [years]	ED	30	25	30
	Oral relative absorption factor	RAF_o	1	1	1
	Skin surface area [cm <sup>2</sup> /day]	SA	3160	3160	3160
	Soil to skin adherence factor [mg/cm <sup>2</sup> ]	M	0.5	0.5	0.5
	Dermal relative absorption factor, volatiles/PAHs	RAF_d	0.5	0.5	0.5
Building	Averaging time for vapor flux [s]	tau	9.46E+08	7.88E+08	9.46E+08
	Enclosed space air exchange rate [L/s]	ER	0.00014	0.00023	0.00014
	Enclosed space volume/infiltration area ratio [cm]	L_b	200	300	200
	Enclosed space foundation or wall thickness [cm]	L_crack	15	15	15
	Aerial fraction of cracks in foundations/walls [cm <sup>2</sup> cracks/cm <sup>2</sup> total area]	nju	0.01	0.01	0.01
	Volumetric air content in foundation/wall cracks [cm <sup>3</sup> air/cm <sup>3</sup> total volume]	Phi_acrack	0.26	0.26	0.26
Surface	Volumetric water content in foundation/wall cracks [cm <sup>3</sup> water/cm <sup>3</sup> total volume]	Phi_wcrack	0.12	0.12	0.12
	Wind speed in ambient mixing zone [cm/s]	U_air	225	225	225
	Ambient air mixing zone height [cm]	delta_air	200	200	200
	Width of source area parallel to wind or groundwater flow direction [cm]	W	2400	2400	1500
	Particulate emission rate [g/cm <sup>2</sup> -s]	P_o	6.9E-14	6.9E-14	6.90E-14
INPUT PARAMETERS		SITE SPECIFIC		DEFAULT	
		Residential	Commercial	Residential	Commercial
Subsurface	Groundwater Darcy velocity [cm/year]	U_gw	1500	1500	2500
	Infiltration rate of water through soil [cm/year]	I	15	15	30
	Groundwater mixing zone thickness [cm]	delta_gw	260	260	200
	Thickness of capillary fringe [cm]	h_cap	4.6	4.6	5
	Thickness of vadose zone [cm]	h_v	235.4	235.4	295
	Depth to subsurface soil sources [cm]	L_s	91	91	100
	Depth to groundwater [cm]	L_gw	240	240	300
	Lower depth of surficial soil zone [cm]	d	279	279	100
Soil	Total soil porosity [cm <sup>3</sup> /cm <sup>3</sup> soil]	Phi_t	0.38	0.38	0.38
	Volumetric air content in vadose zone [cm <sup>3</sup> air/cm <sup>3</sup> soil]	Phi_as	0.26	0.26	0.26
	Volumetric water content in vadose zone [cm <sup>3</sup> H <sub>2</sub> O/cm <sup>3</sup> soil]	Phi_ws	0.12	0.12	0.12
	Volumetric air content in capillary fringe [cm <sup>3</sup> air/cm <sup>3</sup> soil]	Phi_acap	0.038	0.038	0.038
	Volumetric water content in capillary fringe [cm <sup>3</sup> H <sub>2</sub> O/cm <sup>3</sup> soil]	Phi_wcap	0.342	0.342	0.342
	Soil bulk density [g/cm <sup>3</sup> ]	Ro_s	1.7	1.7	1.7
	Fraction of organic carbon in soil [unitless]	f_oc	0.01	0.01	0.01
Chemical	Inhalation slope factor [(mg/kg-day)-1]	SF_i	0.029	0.029	0.029
	Oral slope factor [(mg/kg-day)-1]	SF_o	0.029	0.029	0.029
	Henry's constant [cm <sup>3</sup> H <sub>2</sub> O/cm <sup>3</sup> air]	H	0.22	0.22	0.22
	Pure component solubility in water [mg/L]	S	1780	1780	1780
	Carbon-water sorption coefficient [cm <sup>3</sup> H <sub>2</sub> O/g C]	k_oc	38.02	38.02	38.02
	Soil-water sorption coefficient [cm <sup>3</sup> H <sub>2</sub> O/g soil]	k_s	0.380	0.380	0.380
	Diffusion coeff. In air [cm <sup>2</sup> /s]	D_air	0.093	0.093	0.093
	Diffusion coeff. In water [cm <sup>2</sup> /s]	D_wat	0.000011	0.000011	0.000011

Using Geplexus' site specific values w/ 10<sup>-6</sup> risk

**SAMPLE SPREADSHEET FOR CALCULATION OF BENZENE RBSLs BASED ON ASTM RBCA GUIDANCE**  
**Leaking Underground Storage Tank Oversight Program**  
**Santa Clara Valley Water District**

CALCULATED TRANSPORT COEFFICIENTS		SITE SPECIFIC		DEFAULT	
		Residential	Commercial	Residential	Commercial
Effective diffusion coeff in soil based on vapor conc [cm <sup>2</sup> /s]	Deff_s	0.00722511	0.007225113	0.00722511	0.007225113
Effective diffusion coeff. Through capillary fringe [cm <sup>2</sup> /s]	Deff_cap	2.1732E-05	2.17324E-05	2.1732E-05	2.17324E-05
Effective diffusion coeff. From groundwater to surface [cm <sup>2</sup> /s]	Deff_ws	0.00098262	0.000982615	0.00110742	0.001107416
Effective diffusion coeff. Through foundation cracks [cm <sup>2</sup> /s]	Deff_crack	0.00725763	0.007257629	0.00725763	0.007257629
Volatilization factor from subsurface soil to enclosed space [mg/m <sup>3</sup> air/mg/kg soil]	VF_s_esp	0.0739572	0.03001452	0.07353951	0.02984499
Volatilization factor from subsurface soil to ambient air [mg/m <sup>3</sup> air/mg/kg soil]	VF_s_amb	0.00192308	0.00192308	0.00109375	0.00109375
Volatilization factor from surficial soil to ambient air (vapor) [mg/m <sup>3</sup> air/mg/kg soil]	VF_ss	0.00014613	0.00016012	9.1334E-05	0.00010007
Volatilization factor from surficial soil to ambient air (particulates) [mg/m <sup>3</sup> air/mg/kg soil]	VF_ss1 VF_p	2.674E-05 3.68E-12	3.2102E-05 3.68E-12	5.9901E-06 2.3E-12	7.1912E-06 2.3E-12
Volatilization factor from groundwater to enclosed space [mg/m <sup>3</sup> air/mg/L H <sub>2</sub> O]	VF_w_esp	0.01742311	0.00707058	0.01645076	0.00667597
Volatilization factor from groundwater to ambient air [mg/m <sup>3</sup> air/mg/L H <sub>2</sub> O]	VF_w_amb	4.8039E-05	4.8039E-05	2.707E-05	2.707E-05
Leaching factor from subsurface soils to groundwater [mg/L H <sub>2</sub> O/mg/kg soil]	LF_s_w	0.17444826	0.17444826	0.17044715	0.17044715

  

CALCULATED TARGET LEVELS		SITE SPECIFIC		DEFAULT		
		Residential	Commercial	Residential	Commercial	
AIR	RBSL for enclosed space air [ug/m <sup>3</sup> ]	RBSL_air_esp	3.92E-01	4.93E-01	3.92E-01	4.93E-01
	RBSL for ambient air [ug/m <sup>3</sup> ]	RBSL_air_amb	2.94E-01	4.93E-01	2.94E-01	4.93E-01
SOIL	Surficial soil - ingestion, inhalation of vapors and dust, dermal contact [mg/kg]	RBSL_s_surf	4.12E+00	6.66E+00	5.82E+00	1.00E+01
	Subsurface soil RBSL - Enclosed space vapor inhalation from subsurface soil [mg/kg]	RBSL_s_esp	1.64E-02	5.32E-03	1.65E-02	
	Subsurface soil RBSL - Ambient air vapor inhalation from subsurface soil [mg/kg]	RBSL_s_amb	1.53E-01	2.57E-01	2.69E-01	4.51E-01
	Soil RBSL to protect groundwater MCL	RBSL_s_w_MCL	2.87E-02	2.87E-02	2.93E-02	2.93E-02
	Soil RBSL to protect groundwater RBSL enclosed space vapor inh. [mg/kg]	RBSL_s_w_esp	1.29E-01	4.00E-01	1.40E-01	4.34E-01
	Soil RBSL to protect groundwater RBSL ambient air vapor inh. [mg/kg]	RBSL_s_w_amb	3.50E+01	5.89E+01	6.36E+01	1.07E+02
	Concentration in soil at which pore-water and vapor become saturated [mg/kg]	C_s_sat	8.62E+02		8.62E+02	
GROUND-WATER	Groundwater RBSL - Enclosed space vapor inhalation from groundwater [mg/L]	RBSL_w_esp	6.98E-02	2.38E-02	7.39E-02	
WATER	Groundwater RBSL - Ambient air vapor inhalation from groundwater [mg/L]	RBSL_w_amb	6.11E+00	1.03E+01	1.08E+01	1.82E+01
	MCL	MCL	5.00E-03	5.00E-03	5.00E-03	5.00E-03

1630 Park

SAMPLE SPREADSHEET FOR CALCULATION OF BENZENE RBSLs BASED ON ASTM RBCA GUIDANCE  
 Leaking Underground Storage Tank Oversight Program  
 Santa Clara Valley Water District

	INPUT PARAMETERS	SITE SPECIFIC		DEFAULT	
		Residential	Commercial	Residential	Commercial
Exposure	Target excess individual cancer risk [unitless]	TR	<u>1.00E-04</u>	1.00E-06	1.00E-06
	Adult body weight [kg]	BW	70	70	70
	Averaging time for carcinogens [years]	AT_c	70	70	70
	Daily indoor inhalation rate [m <sup>3</sup> /day]	IR_air_ind	15	20	15
	Daily outdoor inhalation rate [m <sup>3</sup> /day]	IR_air_out	20	20	20
	Soil ingestion rate, mg/day	IR_soil	100	50	100
	Exposure frequency [days/year]	EF	350	250	350
	Exposure duration [years]	ED	30	25	30
	Oral relative absorption factor	RAF_o	1	1	1
	Skin surface area [cm <sup>2</sup> /day]	SA	3160	3160	3160
Building	Soil to skin adherence factor [mg/cm <sup>2</sup> ]	M	0.5	0.5	0.5
	Dermal relative absorption factor, volatiles/PAHs	RAF_d	0.5	0.5	0.5
	Averaging time for vapor flux [s]	tau	<u>9.46E+08</u>	<u>7.88E+08</u>	<u>9.46E+08</u>
					<u>7.88E+08</u>
Surface	Enclosed space air exchange rate [L/s]	ER	0.00014	0.00023	0.00014
	Enclosed space volume/infiltration area ratio [cm]	L_b	200	300	200
	Enclosed space foundation or wall thickness [cm]	L_crack	15	15	15
	Aerial fraction of cracks in foundations/walls [cm <sup>2</sup> cracks/cm <sup>2</sup> total area]	nju	0.01	0.01	0.01
	Volumetric air content in foundation/wall cracks [cm <sup>3</sup> air/cm <sup>3</sup> total volume]	Phi_acrack	0.26	0.26	0.26
	Volumetric water content in foundation/wall cracks [cm <sup>3</sup> water/cm <sup>3</sup> total volume]	Phi_wcrack	0.12	0.12	0.12
Subsurface	Wind speed in ambient mixing zone [cm/s]	U_air	225	225	225
	Ambient air mixing zone height [cm]	delta_air	200	200	200
	Width of source area parallel to wind or groundwater flow direction [cm]	W	<u>2400</u>	2400	1500
	Particulate emission rate [g/cm <sup>2</sup> -s]	P_o	<u>6.9E-14</u>	6.9E-14	<u>6.90E-14</u>

	INPUT PARAMETERS	SITE SPECIFIC		DEFAULT	
		Residential	Commercial	Residential	Commercial
Subsurface	Groundwater Darcy velocity [cm/year]	U_gw	<u>1500</u>	1500	2500
	Infiltration rate of water through soil [cm/year]	I	<u>15</u>	15	30
	Groundwater mixing zone thickness [cm]	delta_gw	<u>260</u>	260	200
	Thickness of capillary fringe [cm]	h_cap	<u>4.6</u>	4.6	5
	Thickness of vadose zone [cm]	h_v	<u>235.4</u>	235.4	295
	Depth to subsurface soil sources [cm]	L_s	<u>91</u>	91	100
	Depth to groundwater [cm]	L_gw	<u>240</u>	240	300
	Lower depth of surficial soil zone [cm]	d	<u>279</u>	279	100
					0
Soil	Total soil porosity [cm <sup>3</sup> /cm <sup>3</sup> soil]	Phi_t	0.38	0.38	0.38
	Volumetric air content in vadose zone [cm <sup>3</sup> air/cm <sup>3</sup> soil]	Phi_as	0.26	0.26	0.26
	Volumetric water content in vadose zone [cm <sup>3</sup> H <sub>2</sub> O/cm <sup>3</sup> soil]	Phi_ws	0.12	0.12	0.12
	Volumetric air content in capillary fringe [cm <sup>3</sup> air/cm <sup>3</sup> soil]	Phi_acap	0.038	0.038	0.038
	Volumetric water content in capillary fringe [cm <sup>3</sup> H <sub>2</sub> O/cm <sup>3</sup> soil]	Phi_wcap	0.342	0.342	0.342
	Soil bulk density [g/cm <sup>3</sup> ]	Ro_s	1.7	1.7	1.7
	Fraction of organic carbon in soil [unitless]	f_oc	0.01	0.01	0.01
Chemical	Inhalation slope factor [(mg/kg-day)-1]	SF_i	<u>0.029</u>	0.029	0.029
	Oral slope factor [(mg/kg-day)-1]	SF_o	<u>0.029</u>	0.029	0.029
	Henry's constant [cm <sup>3</sup> H <sub>2</sub> O/cm <sup>3</sup> air]	H	<u>0.22</u>	0.22	0.22
	Pure component solubility in water [mg/L]	S	1780	1780	1780
	Carbon-water sorption coefficient [cm <sup>3</sup> H <sub>2</sub> O/g C]	k_oc	38.02	38.02	38.02
	Soil-water sorption coefficient [cm <sup>3</sup> H <sub>2</sub> O/g soil]	k_s	0.380	0.380	0.380
	Diffusion coeff. In air [cm <sup>2</sup> /s]	D_air	0.093	0.093	0.093
	Diffusion coeff. In water [cm <sup>2</sup> /s]	D_wat	0.000011	0.000011	0.000011

Using GeoPlexus' site specific values w/ 10<sup>-4</sup> risk

**SAMPLE SPREADSHEET FOR CALCULATION OF BENZENE RBSLs BASED ON ASTM RBCA GUIDANCE**

**Leaking Underground Storage Tank Oversight Program**

**Santa Clara Valley Water District**

CALCULATED TRANSPORT COEFFICIENTS		SITE SPECIFIC		DEFAULT	
		Residential	Commercial	Residential	Commercial
Effective diffusion coeff in soil based on vapor conc [cm <sup>2</sup> /s]	Def_s	0.00722511	0.007225113	0.00722511	0.007225113
Effective diffusion coeff. Through capillary fringe [cm <sup>2</sup> /s]	Def_cap	2.1732E-05	2.17324E-05	2.1732E-05	2.17324E-05
Effective diffusion coeff. From groundwater to surface [cm <sup>2</sup> /s]	Def_ws	0.00098262	0.000982615	0.00110742	0.001107416
Effective diffusion coeff. Through foundation cracks [cm <sup>2</sup> /s]	Def_crack	0.00725763	0.007257629	0.00725763	0.007257629
Volatilization factor from subsurface soil to enclosed space [mg/m <sup>3</sup> air/mg/kg soil]	VF_s_esp	0.0739572	0.03001452	0.07353951	0.02984499
Volatilization factor from subsurface soil to ambient air [mg/m <sup>3</sup> air/mg/kg soil]	VF_s_amb	0.00192308	0.00192308	0.00109375	0.00109375
Volatilization factor from surficial soil to ambient air (vapor) [mg/m <sup>3</sup> air/mg/kg soil]	VF_ss	0.00014613	0.00016012	9.1334E-05	0.00010007
Volatilization factor from surficial soil to ambient air (particulates) [mg/m <sup>3</sup> air/mg/kg soil]	VF_ss1 VF_p	2.674E-05 3.68E-12	3.2102E-05 3.68E-12	5.9901E-06 2.3E-12	7.1912E-06 2.3E-12
Volatilization factor from groundwater to enclosed space [mg/m <sup>3</sup> air/mg/L H <sub>2</sub> O]	VF_w_esp	0.01742311	0.00707058	0.01645076	0.00667597
Volatilization factor from groundwater to ambient air [mg/m <sup>3</sup> air/mg/L H <sub>2</sub> O]	VF_w_amb	4.8039E-05	4.8039E-05	2.707E-05	2.707E-05
Leaching factor from subsurface soils to groundwater [mg/L H <sub>2</sub> O/mg/kg soil]	LF_s_w	0.17444826	0.17444826	0.17044715	0.17044715

  

CALCULATED TARGET LEVELS		SITE SPECIFIC		DEFAULT		
		Residential	Commercial	Residential	Commercial	
AIR	RBSL for enclosed space air [ug/m <sup>3</sup> ] RBSL for ambient air [ug/m <sup>3</sup> ]	RBSL_air_esp RBSL_air_amb	3.92E+01 2.94E+01	4.93E-01 4.93E-01	3.92E-01 2.94E-01	4.93E-01 4.93E-01
SOIL	Surficial soil - ingestion, inhalation of vapors and dust, dermal contact [mg/kg]  Subsurface soil RBSL - Enclosed space vapor inhalation from subsurface soil [mg/kg] Subsurface soil RBSL - Ambient air vapor inhalation from subsurface soil [mg/kg]	RBSL_s_surf RBSL_s_esp RBSL_s_amb	4.12E+02 1.64E-01 1.53E+01	6.66E+00 1.64E-02 2.57E-01	5.82E+00 5.32E-03 2.69E-01	1.00E+01 1.65E-02 4.51E-01
	Soil RBSL to protect groundwater MCL Soil RBSL to protect groundwater RBSL enclosed space vapor inh. [mg/kg] Soil RBSL to protect groundwater RBSL ambient air vapor inh. [mg/kg]	RBSL_s_w_MCL RBSL_s_w_esp RBSL_s_w_amb	2.87E-02 1.29E+01 3.50E+03	2.87E-02 4.00E-01 5.89E+01	2.93E-02 1.40E-01 6.36E+01	2.93E-02 4.34E-01 1.07E+02
	Concentration in soil at which pore-water and vapor become saturated [mg/kg]	C_s_sat	8.62E+02		8.62E+02	
GROUND-WATER	Groundwater RBSL - Enclosed space vapor inhalation from groundwater [mg/L]	RBSL_w_esp	6.98E-02	2.38E-02	7.39E-02	
WATER	Groundwater RBSL - Ambient air vapor inhalation from groundwater [mg/L] MCL	RBSL_w_amb MCL	6.11E+02 5.00E-03	1.03E+01 5.00E-03	1.08E+01 5.00E-03	1.82E+01 5.00E-03

1630 Park

## SAMPLE SPREADSHEET FOR CALCULATION OF BENZENE RBSLs BASED ON ASTM RBCA GUIDANCE

## Leaking Underground Storage Tank Oversight Program

## Santa Clara Valley Water District

	INPUT PARAMETERS	SITE SPECIFIC		DEFAULT	
		Residential	Commercial	Residential	Commercial
Exposure	Target excess individual cancer risk [unitless]	TR	1.00E-06	1.00E-06	1.00E-06
	Adult body weight [kg]	BW	70	70	70
	Averaging time for carcinogens [years]	AT_c	70	70	70
	Daily indoor inhalation rate [m <sup>3</sup> /day]	IR_air_ind	15	20	15
	Daily outdoor inhalation rate [m <sup>3</sup> /day]	IR_air_out	20	20	20
	Soil ingestion rate, mg/day	IR_soil	100	50	100
	Exposure frequency [days/year]	EF	350	250	350
	Exposure duration [years]	ED	30	25	30
	Oral relative absorption factor	RAF_o	1	1	1
	Skin surface area [cm <sup>2</sup> /day]	SA	3160	3160	3160
Building	Soil to skin adherence factor [mg/cm <sup>2</sup> ]	M	0.5	0.5	0.5
	Dermal relative absorption factor, volatiles/PAHs	RAF_d	0.5	0.5	0.5
	Averaging time for vapor flux [s]	tau	9.46E+08	7.88E+08	9.46E+08
					7.88E+08
Surface	Enclosed space air exchange rate [L/s]	ER	0.00014	0.00023	0.00014
	Enclosed space volume/infiltration area ratio [cm]	L_b	200	300	200
	Enclosed space foundation or wall thickness [cm]	L_crack	15	15	15
	Aerial fraction of cracks in foundations/walls [cm <sup>2</sup> cracks/cm <sup>2</sup> total area]	nju	0.01	0.01	0.01
	Volumetric air content in foundation/wall cracks [cm <sup>3</sup> air/cm <sup>3</sup> total volume]	Phi_acrack	0.26	0.26	0.26
	Volumetric water content in foundation/wall cracks [cm <sup>3</sup> water/cm <sup>3</sup> total volume]	Phi_wcrack	0.12	0.12	0.12
Subsurface	Wind speed in ambient mixing zone [cm/s]	U_air	225	225	225
	Ambient air mixing zone height [cm]	delta_air	200	200	200
	Width of source area parallel to wind or groundwater flow direction [cm]	W	1500	1500	1500
	Particulate emission rate [g/cm <sup>2</sup> -s]	P_o	6.9E-14	6.9E-14	6.90E-14

	INPUT PARAMETERS	SITE SPECIFIC		DEFAULT	
		Residential	Commercial	Residential	Commercial
Subsurface	Groundwater Darcy velocity [cm/year]	U_gw	2500	2500	2500
	Infiltration rate of water through soil [cm/year]	I	30	30	30
	Groundwater mixing zone thickness [cm]	delta_gw	200	200	200
	Thickness of capillary fringe [cm]	h_cap	5	5	5
	Thickness of vadose zone [cm]	h_v	245	245	295
	Depth to subsurface soil sources [cm]	L_s	260	260	100
	Depth to groundwater [cm]	L_gw	250	250	300
	Lower depth of surficial soil zone [cm]	d	100	100	100
					0
Soil	Total soil porosity [cm <sup>3</sup> /cm <sup>3</sup> soil]	Phi_t	0.38	0.38	0.38
	Volumetric air content in vadose zone [cm <sup>3</sup> air/cm <sup>3</sup> soil]	Phi_as	0.26	0.26	0.26
	Volumetric water content in vadose zone [cm <sup>3</sup> H <sub>2</sub> O/cm <sup>3</sup> soil]	Phi_ws	0.12	0.12	0.12
	Volumetric air content in capillary fringe [cm <sup>3</sup> air/cm <sup>3</sup> soil]	Phi_acap	0.038	0.038	0.038
	Volumetric water content in capillary fringe [cm <sup>3</sup> H <sub>2</sub> O/cm <sup>3</sup> soil]	Phi_wcap	0.342	0.342	0.342
	Soil bulk density [g/cm <sup>3</sup> ]	Ro_s	1.7	1.7	1.7
	Fraction of organic carbon in soil [unitless]	f_oc	0.01	0.01	0.01
Chemical	Inhalation slope factor [(mg/kg-day)-1]	SF_i	0.029	0.029	0.029
	Oral slope factor [(mg/kg-day)-1]	SF_o	0.029	0.029	0.029
	Henry's constant [cm <sup>3</sup> H <sub>2</sub> O/cm <sup>3</sup> air]	H	0.22	0.22	0.22
	Pure component solubility in water [mg/L]	S	1780	1780	1780
	Carbon-water sorption coefficient [cm <sup>3</sup> H <sub>2</sub> O/g C]	K_oc	38.02	38.02	38.02
	Soil-water sorption coefficient [cm <sup>3</sup> H <sub>2</sub> O/g soil]	K_s	0.380	0.380	0.380
	Diffusion coeff. In air [cm <sup>2</sup> /s]	D_air	0.093	0.093	0.093
	Diffusion coeff. In water [cm <sup>2</sup> /s]	D_wat	0.000011	0.000011	0.000011

GW at 8.25 feet bgs

ASTM default numbers

Soil contam at 8.5 feet bgs

**SAMPLE SPREADSHEET FOR CALCULATION OF BENZENE RBSLs BASED ON ASTM RBCA GUIDANCE**

**Leaking Underground Storage Tank Oversight Program**

**Santa Clara Valley Water District**

CALCULATED TRANSPORT COEFFICIENTS		SITE SPECIFIC		DEFAULT	
		Residential	Commercial	Residential	Commercial
Effective diffusion coeff in soil based on vapor conc [cm <sup>2</sup> /s]	Def <sub>s</sub>	0.00722511	0.007225113	0.00722511	0.007225113
Effective diffusion coeff. Through capillary fringe [cm <sup>2</sup> /s]	Def <sub>cap</sub>	2.1732E-05	2.17324E-06	2.1732E-05	2.17324E-05
Effective diffusion coeff. From groundwater to surface [cm <sup>2</sup> /s]	Def <sub>ws</sub>	0.00094704	0.000947039	0.00110742	0.001107416
Effective diffusion coeff. Through foundation cracks [cm <sup>2</sup> /s]	Def <sub>crack</sub>	0.00725763	0.007257629	0.00725763	0.007257629
Volatilization factor from subsurface soil to enclosed space [mg/m <sup>3</sup> air/mg/kg soil]	VF <sub>s</sub> _esp	0.06682946	0.02712157	0.07353951	0.02984499
Volatilization factor from subsurface soil to ambient air [mg/m <sup>3</sup> air/mg/kg soil]	VF <sub>s</sub> _amb	0.00042067	0.00042067	0.00109375	0.00109375
Volatilization factor from surficial soil to ambient air (vapor) [mg/m <sup>3</sup> air/mg/kg soil]	VF <sub>ss</sub>	9.1334E-05	0.00010007	9.1334E-05	0.00010007
Volatilization factor from surficial soil to ambient air (particulates) [mg/m <sup>3</sup> air/mg/kg soil]	VF <sub>ss1</sub> VF <sub>p</sub>	5.9901E-06 2.3E-12	7.1912E-06 2.3E-12	5.9901E-06 2.3E-12	7.1912E-06 2.3E-12
Volatilization factor from groundwater to enclosed space [mg/m <sup>3</sup> air/mg/L H <sub>2</sub> O]	VF <sub>w</sub> _esp	0.01669263	0.00677413	0.01645076	0.00667597
Volatilization factor from groundwater to ambient air [mg/m <sup>3</sup> air/mg/L H <sub>2</sub> O]	VF <sub>w</sub> _amb	2.778E-05	2.778E-05	2.707E-05	2.707E-05
Leaching factor from subsurface soils to groundwater [mg/L H <sub>2</sub> O/mg/kg soil]	LF <sub>s</sub> _w	0.17044715	0.17044715	0.17044715	0.17044715

  

CALCULATED TARGET LEVELS		SITE SPECIFIC		DEFAULT		
		Residential	Commercial	Residential	Commercial	
AIR	RBSL for enclosed space air [ug/m <sup>3</sup> ]	RBSL_air_esp	3.92E-01	4.93E-01	3.92E-01	4.93E-01
	RBSL for ambient air [ug/m <sup>3</sup> ]	RBSL_air_amb	2.94E-01	4.93E-01	2.94E-01	4.93E-01
SOIL	Surficial soil - ingestion, inhalation of vapors and dust, dermal contact [mg/kg]	RBSL_s_surf	5.82E+00	1.00E+01	5.82E+00	1.00E+01
	Subsurface soil RBSL - Enclosed space vapor inhalation from subsurface soil [mg/kg]	RBSL_s_esp	[REDACTED]	1.82E-02	5.32E-03	1.65E-02
	Subsurface soil RBSL - Ambient air vapor inhalation from subsurface soil [mg/kg]	RBSL_s_amb	6.98E-01	1.17E+00	2.69E-01	4.51E-01
	Soil RBSL to protect groundwater MCL	RBSL_s_w_MCL	2.93E-02	2.93E-02	2.93E-02	2.93E-02
	Soil RBSL to protect groundwater RBSL enclosed space vapor inh. [mg/kg]	RBSL_s_w_esp	1.38E-01	4.27E-01	1.40E-01	4.34E-01
	Soil RBSL to protect groundwater RBSL ambient air vapor inh. [mg/kg]	RBSL_s_w_amb	6.20E+01	1.04E+02	6.36E+01	1.07E+02
	Concentration in soil at which pore-water and vapor become saturated [mg/kg]	C <sub>s</sub> _sat	8.62E+02		8.62E+02	
GROUND-	Groundwater RBSL - Enclosed space vapor inhalation from groundwater [mg/L]	RBSL_w_esp	[REDACTED]	7.28E-02	2.38E-02	7.39E-02
WATER	Groundwater RBSL - Ambient air vapor inhalation from groundwater [mg/L]	RBSL_w_amb	1.06E+01	1.78E+01	1.08E+01	1.82E+01
	MCL	MCL	5.00E-03	5.00E-03	5.00E-03	5.00E-03