


KAPREALIAN ENGINEERING, INC.

Consulting Engineers 535 Main Street Martinez, Ca. 94553 (415) 372-5444



35 TH AVE.



LOCATION PLAN

MW (MONITORING WELL)






Consulting Engineers 535 Main Street Martinez, Ca. 94553 (415) 372-5444

1


35 AVE.



LOCATION PLAN


MW (MONITORING WELL)

11/22/94



KAPREALIAN ENGINEERING, INC. Consulting Engineers

PO BOX 996 . BENICIA, CA 94510 (707) 746-6915 • (707) 746-6916 • FAX (707) 746-5581




SITE PLAN

LEGEND

Sample Point Location

60 30 Approx. scale feet BP Service Station 3201 35th Avenue Oakland, CA Figure C-4

Source: KEI, October 11, 1990a



MOBIL OIL CORPORATION OAKLAND, CALIFORNIA

MW-3

Well completed to 35.0 feet in depth with 2-inch Class 160 PVC casing, flush-threaded joints. Screen (.020-inch slot) set from 10.0 to 35.0 feet. No. 3 Monterey sand placed from 5.5 to 35.0 feet, bentonite pellets placed from 5.0 to 5.5 feet, and concrete seal placed from 0 to 5.0 feet.

L		OF	E)		SCIENCE, Inc.		PROJECT NO30-081 DATE DRILLED_1/29/90 CLIENTBP_OIL_COMPANY LOCATION3201_35TH_AVENUE, OAKLAND, CA LOGGED BYM. TAYLORAPPROVED BY MW-4
	,				BORING LOCATION EVATION 170.34		DRILLING METHOD HOLLOW-STEM AUGER HOLE DIAM: 8° SAMPLER TYPE MODIFIED SPLIT SPOON CASING DATA SEE MONITORING WELL CONSTRUCTION DETAIL DRILLER WEST HAZMAT
BLOWS PER	Pop (n)	CGI (PPM)	SAMPLE	DEPTH	WELL CONSTRUCTION ORBORING CLOSURE UBCS	PROFILE	WATER LEVEL 26.87 DATE July 9, 1990 TIME DESCRIPTION
			Ŧ	0	Christy Box		4000007
3,4	,6	0		2 4 6 8	Portland Cement CL. Bentonite A Pellets		ASPHALT SILTY CLAY; greenish brown, damp, high plasticity stiff
10, 35	,28,	0	I	- - 10 - - 12 -	2* sch CL 40 PVC Casing		SILTY CLAY; gravelly, greenish brown with rust stain residue, dry to damp, low to medium plasticity, hard
10, 28	,17,	0		- 14 - 16 - 18	2* sch. 40		SILTY CLAY; gravelly, brown, dry to damp, low to medium plasticity hard
14 35	,28,	0	1	20	.020 CL		SILTY CLAY; gravelly, brown rust residue, dry to damp, low plasticity, hard
7, 26	15, 3	0		- 24 - 26 - 28	Lonestar		SILTY CLAY; gravelly, brown, moist medium plasticity, hard
11, 25	, 17,	o		-32 -32	c	L	SILTY CLAY; very gravelly, brown wet, medium plasticity


	G C	FE		SCIENCE, Inc. LORATORY		PROJECT NO30-081 DATE DRILLED 1/29/90 CLIENTBP OIL COMPANY LOCATION _3201 35TH AVENUE, OAKLAND, CA LOGGED BY _M. TAYLOR APPROVED BY	BORING N WELL NO. MW-4
				BORING LOCATION	·	DRILLING METHOD HOLLOW-STEM AUGER HOLE DIA SAMPLER TYPE MODIFIED SPLIT SPOON CASING DATA SEE MONITORING WELL CONSTRUCTION DRILLER WEST HAZMAT	
BLOWS PER FOOT(N)	CGI (PPM)	SAMPLE	DEPTH	WELL CONSTRUCTION ORBORING CLOSURE USCS	PROFILE	WATER LEVEL DATE TIME DESCRIPTION	
8,18, 34 15, 28, 38	0		- 36 - 38 - 40 - 42 - 44	sch. 40 PVC .020 Slot End Cap		SILTY CLAY; gravelly, brown, dry to damp SILTY CLAY; gravelly, brown, moist, medium plasticity	
			- 46 - 48 - 50				
			-				

					<u> </u>			
	LOG	O	FE		SCIENCE, Inc.		PROJECT NO. 30-081 DATE DRILLED 2/1/90 CLIENT BP OIL COMPANY	BORING NO. WELL NO.
	BOF	(IN	G			1	LOCATION 3201 35TH AVENUE, OAKLAND, CA	WELLING.
							LOGGED BY M. TAYLOR APPROVED BY	MW-5
F	IELD S	SKE	TCH	OF	BORING LOCATION			
						ľ	DRILLING METHOD HOLLOW-STEM AUGER HOLE DI	AM8"
							AMPLED TYPE MODIFIED SPLIT SPOON	
						1	CASING DATA SEE MONITORING WELL CONSTRUCTION	ON DETAIL
. т		E C	A C I R	JG F	LEVATION 165.14	1	DRILLER WEST HAZMAT	
	OF C		7011	10 L			DNIELEN	
_					N Q	W/	TER LEVEL 24.75	
BLOWS PER	_	Σ	ш	Ŧ	1 1		TE July 9, 1990	
₹	FOOT(N)	립	1PL	DEPTH	LL 4STRUCT BORRING SCURE SCS	TIN		
3	ř	CGI (PPM)	SAMPLE	_	SOEU SOEU SOEU SOEU SOEU SOEU SOEU SOEU		DESCRIPTION	
				 	Christy Box	+		
				- 0			ASPHALT	
				- 2	Portland			
				-	Cement	a		-
				- 4	a		ANDY CLAY; gravelly, brown, damp, low plasticity	
13	3,23,	0		- 6		h	ard ·	
35	5		尸	- -	Bentonite Pellets	8		
				- 8				
ļ				1	W_Ma		SILTY CLAY; gravelly, greenish brown, damp, low	
1	1,25,	0	П	1- 10	2* sch.	g r	lasticity, gas odor present hard	
3	9		十	1- 12	40 PVC	8		
ŀ				-	Casing			
				- 14	a		SILTY CLAY; gravelly, greenish brown, moist medium plasticity, gas odor hard	
8	8,11,	0	П	T- 16	2"		nedium plasticity, gas occi hard	
1	21		Г	1.	sch. 40			
			1	- 18			an man an and an and an anigh	
			L	- 20			SILTY CLAY; sandy and gravel, greenish brown, moist medium plasticity, gas odor	
	8,23,	0	П	-			hard	
	33		۲	7-2	2			
				ŀ			<u> </u>	
			L		4 Sand #3 Lonestar	771	∑	
1	4,7,13	0	П	1-2	6 CL		SILTY CLAY; gravelly, reddish brown, moist to	
			۲	┧╴			saturated medium plasticity very stiff	
				- 2	8			
	4,5,8	١	, F	巾。				
1	4,3,0]		د ا	" a		SILTY CLAY; with fine sand, tan, damp to medium high	plasticity, stiff
				- 3	12			
			L				n total transmission algorithm	ity hard
1	14,17	· 0		1 -3	End Cap CL		SILTY CLAY; gravelly, reddish brown moist high plastic	ty, naru

.

*

• * * •



						<u> </u>
LOG BOF	RIN	F E	XP	SCIENCE, Inc. LORATORY BORING LOCATION		PROJECT NO
TOP O	F C	ASI	NG E	LEVATION 167.61	-	DRILLING METHOD HOLLOW-STEM AUGER HOLE DIAM. 8" SAMPLER TYPE MODIFIED SPLIT CASING DATA SEE MONITORING WELL CONSTRUCTION DETAIL DRILLER WEST HAZMAT
FOOT(N)	CGI (PPM)	SAMPLE	DEPTH	WELL CONSTRUCTION ORBORING CLOSURE USCS	PROFILE	DATE JULY 9, 1990 DESCRIPTION
			- 0	Christy Box		ASPHALT
14,14, 15	0		- 2 - 4 - 6	Portland Cement CH Bentonite		SILTY CLAY; brown, damp, high plasticity, very stiff
i 1,27, 39	0		- 8 - - 10 - - 12	2" sch		SILTY CLAY; gravelly, reddish brown damp medium plasticity, hard
15,21, 29	0	I	- - 14 - - 16 - - 18	2" sch. 40		SILTY CLAY; gravelly, reddish brown, damp, hard
36,15, 50/5"	0	I	- 18 - 20 - 22	.020 Slot CL		SILTY CLAY; gravelly, brown, moist medium plasticity, hard
8,15,21	0		- 24 - 26 - 28			SILTY CLAY; gravelly, brown, moist medium plasticity, hard
5,8,12	0		- 30	α		SILTY CLAY; gravelly, brown, saturated medium plasticity, very stiff
4,7,10	0		-34			SILTY CLAY; tannish brown, moist high plasticity, very stiff

ALTON GEOSCIENCE, Inc. LOG OF EXPLORATORY BORING FIELD SKETCH OF BORING LOCATION TOP OF CASING ELEVATION 168.01 TOP OF CASING ELEVATION 168.01 FIELD SKETCH OF BORING LOCATION TOP OF CASING ELEVATION 168.01 FIELD SKETCH OF BORING LOCATION TOP OF CASING ELEVATION 168.01 FIELD SKETCH OF BORING LOCATION TOP OF CASING ELEVATION 168.01 SWILL	PROJECT NO
TOP OF CASING ELEVATION 168.01	DRILLING METHOD HOLLOW-STEM AUGER HOLE DIAM. 12° SAMPLER TYPE CASING DATA SEE MONITORING WELL CONSTRUCTION DETAIL DRILLER WEST HAZMAT WATER LEVEL 27.93 DATE July 9, 1990 TIME DESCRIPTION ASPHALT SILTY CLAY; gravels, brown, damp, backfill SILTY CLAY; gravelly, greenish brown, dry to damp, low plasticity, odor present SILTY CLAY; gravelly, greenish brown, dry to damp, medium plasticity,
9,19, 0 33	SAMPLER TYPE CASING DATA SEE MONITORING WELL CONSTRUCTION DETAIL DRILLER WEST HAZMAT WATER LEVEL 27.93 DATE July 9, 1990 TIME DESCRIPTION ASPHALT SILTY CLAY; gravels, brown, damp, backfill SILTY CLAY; gravelly, greenish brown, dry to damp, low plasticity, odor present SILTY CLAY; gravelly, greenish brown, dry to damp, medium plasticity,
9,19, 0 33 16,33, 0 40 15,36, 0 15,36, 0 18, 00 18, 00 10, 00 1	TIME DESCRIPTION ASPHALT SILTY CLAY; gravels, brown, damp, backfill SILTY CLAY; gravelly, greenish brown, dry to damp, low plasticity, odor present SILTY CLAY; gravelly, greenish brown, dry to damp, medium plasticity,
9,19, 0	DESCRIPTION ASPHALT SILTY CLAY; gravels, brown, damp, backfill SILTY CLAY; gravelly, greenish brown, dry to damp, low plasticity, odor present SILTY CLAY; gravelly, greenish brown, dry to damp, medium plasticity,
9,19, 0	ASPHALT SILTY CLAY; gravels, brown, damp, backfill SILTY CLAY; gravelly, greenish brown, dry to damp, low plasticity, odor present SILTY CLAY; gravelly, greenish brown, dry to damp, medium plasticity,
9,19, 0	SILTY CLAY; gravels, brown, damp, backfill SILTY CLAY; gravelly, greenish brown, dry to damp, low plasticity, odor present SILTY CLAY; gravelly, greenish brown, dry to damp, medium plasticity,
9,19, 33 16,33, 40 15,36, 40 15,36, 43 CL Bentonite Pellets CL CL 6* sch. 40 PVC Casing CL CL 6* sch. 40 PVC Casing CL CL CL CL A0 PVC Casing CL CL CL CL CL CL Pellets CL CL CL CL CL CL CL CL CL C	SILTY CLAY; gravels, brown, damp, backfill SILTY CLAY; gravelly, greenish brown, dry to damp, low plasticity, odor present SILTY CLAY; gravelly, greenish brown, dry to damp, medium plasticity,
9,19, 33	SILTY CLAY; gravelly, greenish brown, dry to damp, low plasticity, odor present SILTY CLAY; gravelly, greenish brown, dry to damp, medium plasticity,
16,33, 40	
15,36, 0	odor present
18 PVC	SILTY CLAY; gravelly, brown, damp, medium odor present
11,16, 0	SILTY CLAY; gravelly, brown, damp, medium plasticity, odor present
6,7, 16 0 1 - 24 Sand #3 Lonestar CL	SILTY CLAY; sandy gravelly, greenish brown, medium plasticity
6,13, 0 30 30 CL	SILTY CLAY; gravelly, sandy (fine) brown, saturated very stiff

.

LOC BOI	G O RIN	F E G	XPL	SCIENCE, Inc. LORATORY		PROJECT NO. 30-081 DATE DRILLED 1/29/90 CLIENT BP OIL COMPANY LOCATION 3201 35TH AVENUE, OAKLAND, CA LOGGED BY M. TAYLOR APPROVED BY RW-1
				BORING LOCATION	-	DRILLING METHOD HOLLOW-STEM AUGER HOLE DIAM. 10" SAMPLER TYPE MODIFIED SPLIT SPOON CASING DATA SEE MONITORING WELL CONSTRUCTION DETAIL DRILLER WEST HAZMAT
BLOWS PEH FOOT(N)	CGI(PPM)	SAMPLE	SEPTH	WELL CONSTRUCTION OR BORING CLOSURE CLOSURE	PROFILE	WATER LEVEL DATE TIME DESCRIPTION
6, 16, 29 - 6, 15,	0		- 36 - - 38 - - 40	2" sch. 40 PVC .020 Slot	-	SILTY CLAY; gravelly, sandy (fine) brown, saturated, medium high plasticity, hard SAME
28			-	End Cap		
				× .		
			- - - -	·		
			-			
			-			

	LOC BOI	G O RIN	F E G	XPI	SCIENCE, In LORATORY BORING LOCATI			PROJECT NO. 30-081-01 DATE DRILLED 2-25-91 CLIENT BP Oil Company LOCATION 3201 35th Ave, Oakland LOGGED BY M. Taylor APPROVED BY M. Hopwood	BORING NO. SB-8 WELL NO. MW-8 Page 1 of 2
Ι΄	ILLD	JIL	.101	101	DOI WING ECONT			Day was AST IOD Hollow storn outgot 11015 DIA	
								DRILLING METHOD Hollow stem auger HOLE DIA SAMPLER TYPE Modified split spoon	м
								CASING DATA See well construction details	
١,	OP C	F C	ASIN	IG E	LEVATION 165	.74'		DRILLER Soils Exploration Services, Inc.	
							•	DHILLEN CONSTRUCTION CONTROL , MIC.	
æ					N Q			WATER LEVEL	
BLOWS PER	Ξ	CGI(PPM)	Щ	Ŧ	WELL CONSTRUCT ORBORING CLOSURE	l	岸	DATE	
₹	FOOT(N)	9)	SAMPLE	DE PT	WIELL CONSTRUC OR BORING CLOSURE	536n	PROFILE	TIME	·
Ē	Ϋ́	ខ	જે			Š		DESCRIPTION	
Γ				-0	Christy Box			10" Concrete	
				-		TO SOUTH		10 Concrete	· · · · · · · · · · · · · · · · · · ·
5,	13,25			2 4 6 8	2" sch. 40 PVC	GM		GRAVELLY SILT: green, damp, hard, low plasticity	
7,	14,11			- 10 - 12 - 14	Casi ng	ML		SANDY SILT: greenish brown, damp, very stiff, low plasticity, gra	velly
5,	14,16			- 16 - 18	9	4.00		SILTY CLAY: brownish green, damp, very stiff, low to medium pla fine sand	sticity, with
2	2,6,10			20 - 22		CL		Same, becomes moist, stiff, medium plasticity, with medium sand	
5	,9,12			24 26 28	sch. 40 PVC 0.020			Same, becomes brown, moist to wet, very stiff, medium plasticity 27'	
3	3,9,14			30 - 32 - 34		3008303636363636363636363636363636363636		Same, becomes brownish green, wet, with medium sand and grav	rel

	G O	FE		SCIENCE, In LORATORY	с. Д			PROJECT NO. 30-081-01 DATE DRILLED 2/25/91 CLIENT BP Oil Company LOCATION 3201 35th Ave., Oakland LOGGED BY M. Taylor APPROVED BY M. Hopwood	BORING NO. SB-8 WELL NO. MW-8
FIELD	SKE	TCF	OF	BORING LOCATI	ON			LOCALE DI , W. T.	Page 2 of 2
								DRILLING METHOD Hollow stem auger HOLE DI	AM. 8"
-								SAMPLER TYPE Modified split spoon	
			۰۵ = ۱	FUATION 10E	741			CASING DATA See well construction detail	
TOPC)F C	ASIN	IG E	_EVATION165.	.74	-		DRILLER Soils Exiplorations Services, Inc.	
Œ				N.			W	ATER LEVEL	
BLOWS PER FOOT(N)	CGI (PPM)	빌	두	WELL CONSTRUCT ORBORING CLOSURE		PROFILE	D	ATE	
BLOWS R FOOT(N)	<u> </u>	SAMPLE	8	HE WEST	33g	ĝ.	T	ME DESCRIPTION	
	_	S			-				
7,11,14			- 36 -				S	ILTY CLAY: brown, wet, very stiff, medium to high plasticity, with and gravel	h medium sand
			- 38		CL			and graves	
11,20,			- - 40	End Cap]		S	ame, becomes moist to wet, hard, medium plasticity	
20		П	- 42			******	В	ORING TERMINATED AT 41.5 FEET BELOW GRADE	•
			- 44						
			- 40						
			- 46 -	,					
			- 48			٠			
			50						
			- 52						
1			-						
			- 54 -						
			- 56						
			- - 58						
			60						
			۳						
								Portland Cement Sample	
								Sand #3 Lonestar Driven interval	
							3	Bentonite Pellets	ring drilling

LOC BOF FIELD	OG OF EXPLORATORY ORING LD SKETCH OF BORING LOCATION P OF CASING ELEVATION 166.20						PROJECT NO
BLOWS PER POOT(N)	CGI(PPM)	SAMPLE	SEPT.	WELL CONSTRUCTION OF BORING CLOSURE	soen	PROFILE	WATER LEVEL DATE TIME DESCRIPTION
·			-0	Christy Box			6" Asphalt (street)
6,11,14 4,5,13 5,12,14			- 4 - 6 - 10 - 12 - 14 - 16	2" sch. 40 PVC Casing	ML		SANDY SILT: reddish brown, damp, very stiff, low plasticity, with gravel Same, becomes brown, no gravel SILTY CLAY: brown with green streaks, moist, very stiff, medium plasticity
2,6,9		Ŧ	20		CL		Same, becomes moist to wet, stiff
5,8,10			24	sch. 40 PVC 0.020*			Same, becomes brown, wet to saturated, very stiff 26'
3,5,10			- 28 - 30 - 32 - 34	Fod Con			Same, becomes saturated, stiff, with fine to medium sand

•

E	-OC	G O RIN	F E	EXP	SCIENCE, In LORATORY BORING LOCATION			1	PROJECT NO. 30-081-01 DATE DRILLED 2/26/9 CLIENT BP Oil Company LOCATION 3201 35th Ave., Oakland LOGGED BY M. Taylor APPROVED BY M. Hopw	SB-9 WELL NO.
то	PO	F C	ASII	NG E	LEVATION 166.	20'			DRILLING METHOD Hollow stem auger HOLE SAMPLER TYPE Modified split spoon CASING DATA See well construction detail DRILLER Soils Explorations Services, Inc.	E DIAM8"
BLOWS PER	(u) 1.00	CGI (PPM)	SAMPLE	EF130	WELL CONSTRUCTION OR BORING CLOSURE	soen	PROFILE	D/	ATER LEVEL TE ME DESCRIPTION	
6,12	,17		H	- 36	¥ 8	CL		SI	TY CLAY: reddish brown, saturated to wet, very stiff, med	um plasticity
				- - 38				BO	PRING TERMINATED AT 36.5 FEET BELOW GRADE	
ŀ		·		- - 40						
				- 42						
	ı			-						
	ı			- 44 -						
	ı			- 46 -						
				- 48						
				- 50						
				- 52						
				- - 54	n de la companya de Na companya de la co		<			
				- - 56						
				- - 58						
			-	- - 60						·
				- 60					••	·
								_	ortland Cement Sample	
									and #3 Lonestar	
								3 5	entonite Pellets	auring arilling

FIELD SKETCH OF BORING LOCATION Page 1 of 2 DRILLING METHOD Hollow stem auger HOLE DIAM 8* SAMPLER TYPE Modified split spoon CASING BLEVATION 167.01* WATER LEVEL DATE DATE TIME DESCRIPTION Casing Christy Box 10* Concrete SILTY CLAY: tan, damp, very stiff, low plasticity, with gravel Same, becomes tan to brown Same, becomes brown with green streaks, moist, medium plasticity, with gravel Same, becomes moist to wet, with fine sand and gravel Same, becomes moist to wet, with fine sand and gravel Same, becomes brown, wet, hard, medium plasticity, with slight gravel Same, becomes brown, wet, hard, medium plasticity, with slight gravel Same, becomes brown, wet, hard, medium plasticity, with slight gravel		O	FE		SCIENCE, In LORATORY	ic.			CLIENT BP	30-081-01 Dil Company 201 35th Ave, Oa M. Taylor API	kland		BORING NO. SB-10 WELL NO. MW-10
DATE TIME DESCRIPTION Christy Box 10° Concrete SILTY CLAY: tan, damp, very stiff, low plasticity, with gravel Same, becomes brown with green streaks, moist, medium plasticity, with gravel Same, becomes moist to wet, with fine sand and gravel Same, becomes moist to wet, with fine sand and gravel Same, becomes moist to wet, with fine sand and gravel Same, becomes brown, wet, with slight gravel Same, becomes brown, wet, hard, medium plasticity, with slight gravel Same, becomes brown, wet, hard, medium plasticity, with slight gravel Same, becomes brown, wet, hard, medium plasticity, with slight gravel							· · · · · · · · · · · · · · · · · · ·		DRILLING METI SAMPLER TYPI CASING DATA	HOD Hollow stee Modified spli See well const	em auger t spoon ruction details		
SILTY CLAY: tan, damp, very stiff, low plasticity, with gravel Same, becomes tan to brown Same, becomes brown with green streaks, moist, medium plasticity, with gravel Same, becomes moist to wet, with fine sand and gravel Same, becomes moist to wet, with fine sand and gravel Same, becomes moist to wet, with fine sand and gravel Same, becomes moist to wet, with fine sand and gravel Same, becomes brown, with slight gravel Same, becomes brown, wet, hard, medium plasticity, with slight gravel	FOOT(N)	CGI (PPM)	SAMPLE	EP.14	WELL CONSTRUCTION OR BORING CLOGURE	soen	PROFILE	D/	\TE	DES	SCRIPTION		
SILTY CLAY: tan, damp, very stiff, low plasticity, with gravel Same, becomes tan to brown Same, becomes brown with green streaks, moist, medium plasticity, with gravel Same, becomes moist to wet, with fine sand and gravel Same, becomes moist to wet, with fine sand and gravel Same, becomes moist to wet, with fine sand and gravel Same, becomes moist to wet, with fine sand and gravel Same, becomes brown, wet, with slight gravel Same, becomes brown, wet, hard, medium plasticity, with slight gravel				- 0		E		4	O" Concrete				
Same, becomes brown with green streaks, moist, medium plasticity, with gravel Same, becomes moist to wet, with fine sand and gravel Same, becomes moist to wet, with fine sand and gravel Same, becomes moist to wet, with fine sand and gravel SANDY CLAY: brownish white, wet to saturated, very stiff, low to medium plasticity, with slight gravel Same, becomes brown, wet, hard, medium plasticity, with slight gravel				- 4 - 6 - 8 - 10	sch. 40 PVC	CL					v plasticity, with q	gravel	
3,8,18 26 27 30 31,19, 25 Same, becomes brown, wet, hard, medium plasticity, with slight gravel Same, becomes brown, wet, hard, medium plasticity, with slight gravel	-			- - 18 - - 20									ity, with grave
SANDY CLAY: brownish white, wet to saturated, very stiff, low to medium plasticity, with slight gravel CL Same, becomes brown, wet, hard, medium plasticity, with slight gravel				22					Value occurred inc		. Lane and grave		
Same, becomes brown, wet, hard, medium plasticity, with slight gravel	3,8,18			- - 26 -	sch. 40 PVC 0.020*				SANDY CLAY: brow			tiff, low to	medium
34 - - - - - - - - -	11,19, 25			-	End Cap	CL		· · · · · · · · · · · · · · · · · · ·	Same, becomes bro	own, wet, hard, mo	edium plasticity, v	vith slight (gravel

,

Sand #3 Lonestar Bentonite Pellets Driven interval

Water level encountered during drilling

又

10/13/03 >> BCA

October 6, 2003

Mr. Paul Supple BP Oil PO Box 6549 Moraga, CA 94570

Dear Mr. Supple:

Subject: Fuel Leak Case No. RO0000014, BP Station #11132, 3201 35th Ave., Oakland, CA

Alameda County Environmental Health (ACEH) staff has reviewed "Soil and Groundwater Investigation Workplan Amendment" dated May 28, 2003 by URS Corporation (URS). We generally concur with the work proposed. We request that you address the following technical comments and send us the technical reports requested below.

TECHNICAL COMMENTS

- 1. Corrective Action Plan The California Regional Water Quality Control Board, San Francisco Bay Region (SFRWQCB)'s "Screening For Environmental Concerns at Sites With Contaminated Soil and Groundwater (Interim Final July 2003)" is acceptable for risk evaluation. The Oakland Risk-Based Corrective Action (RBCA) approach to evaluate risk may also be used for Benzene, Toluene, Ethyl Benzene, Xylene (BTEX).
- 2. Contaminant Source Characterization Proposed borings UB-7 and UB-8 are located downgradient of the underground tanks. We would like them moved as close to the tanks as possible but in native soil. There may have been releases since the tanks were replaced in 1986. Please locate borings UB-7 and UB-8 closer to the tanks.
- 3. Preferential Pathway Survey In addition to the map(s) to be submitted, please use cross-sections showing the location and depth of all utility lines and trenches (including sewers, storm drains, pipelines, trench backfill, etc.) within and near the site and plume area(s). Evaluate the probability of the contaminant plumes encountering preferential pathways and conduits that could spread the contamination, particularly in the vertical direction to deeper water aquifers. Please submit.
- 4. Well Survey Locate at wells within a quarter mile radius of the site. Show the location of the wells on a map and list well construction details for each well. Indicate which of the wells may be potential receptors.
- 5. Missing reports
 - a. 1986 removal of underground tanks
 - b. September 4, 1990 installation of MW4, MW5, MW6, MW7, RW1
 - c. October 11, 1990 sampling of D1, D2, D3, PT-1, 2, 3, 4

Messrs. Hooton and DeWitt
March 20, 2003
Page 2 of 2

- d. December 16, 1994 sampling of THP1-S-4-4.5
- e. March 1991 SB 8, 9, 10

Please submit.

TECHINCAL REPORT REQUEST

Please submit technical reports to the Alameda County Environmental Health (Attention: Don Hwang), according to the following schedule:

December 6, 2003 – Site plan showing borings UB-7 and UB-8 closer to the tanks.

December 6, 2003 – Preferential Pathway Survey

December 6, 2003 – Well Survey

December 6, 2003 - Missing reports

These reports are being requested pursuant to the Regional Water Quality Control Board's (Regional Board) authority under Section 13267 of the California Water Code. If you have any questions, please call me at (510) 567-6746.

Sincerely,

Don Hwang Hazardous Materials Specialist Local Oversight Program

C: Leonard Niles, URS Corporation, 500-12th St., Suite 200, Oakland, CA 94607-4014 Donna Drogos File

Table 1-1. Comparison of RWQCB and Oakland Risk-Based Approaches

		RWQCB	¹ Oakland		
ach	Tiers	One tier of look-up tables. Includes separate screening levels for indoor air concerns based on soil type.	Two tiers of look-up tables: Tier 1 table applicable at any Oakland site; Tier 2 tables (3) account for site-specific soil types (Merritt Sands, sandy silts, and clayey silts) and alternate target risk. Tier 3 spreadsheets provided.		
Approach	Target Cancer Risk Level	10-6	10 ⁻⁶ for Tier 1; 10 ⁻⁵ for Tier 2.		
ral A	Target Noncancer Hazard Quotient	0.2 (with option for site specific adjustment)	1.0 (with requirement to address cumulative risk as necessary)		
General	Ceiling/Nuisance Levels	"Ceiling levels" to address gross contamination concerns, nuisances, free-product mobility, and general resource quality	No "ceiling levels"; recommends removal of mobile or potentially-mobile free product.		
	Total Petroleum Hydrocarbons	Screening levels for TPH included	No TPH screening levels.		
	Definition of "Shallow" Soils	0-3 meters below ground surface.	0-1 meter below ground surface.		
ways	Direct Exposure, Inhalation of Volatiles	USEPA PRG model (USEPA 2002). Assumes "infinite" source thickness for volatile organic compounds.	ASTM (1995) model. Assumes infinite source unless mass balance conditions violated based on 1.0 m thick source.		
Soil Pathways	Ecological Concerns	Screening levels for terrestrial biota included (shallow soils only).	Recommends site-specific analysis when significant ecological habitats are threatened.		
Š	Deep Soils	Direct-exposure soil screening levels for Construction/ Trench Worker exposure scenario.	No screening levels for this scenario; recommends a site-specific analysis as warranted.		
	Leaching Model	Employs the SESOIL model.	Employs the ASTM (1995) model.		
ater		No soil screening levels; recommends laboratory tests.	Soil screening levels for inorganic compounds, based on a neutral pH.		
Groundwater	Surface Water Protection	Groundwater screening levels for the ecological and aesthetic protection of surface water.	Screening levels for recreational use of groundwater and surface water. Recommends site-specific analysis of ecological and aesthetic concerns as warranted.		
	Thickness of Soil Source	Assumes five meters. Recommends site-specific analysis as warranted.	Assumes "infinite" source thickness.		
or Air	Convective Flow	Incorporates convective flow in indoor-air impact model.	Does not incorporate convective flow (i.e., assumes no pressure differential) in indoorair impact model.		
Indoor	Surface Soil Screening Levels	Includes screening levels for protection of indoor air for both surface and subsurface soils.	Recommends site-specific analysis and controls for shallow soils (<1m) and use of screening levels for deeper soils.		
	Soil Gas	Includes screening levels for soil gas.	Not included.		

^{1.} Oakland Risk-Based Corrective Action: Technical Background Document: City of Oakland, Environmental Services Division, January 2000 (and updates), www.oaklanddpw.com/urlprogram.

As discussed in the USEPA Region IX document, the PRGs are intended to address human direct-exposure with impacted soil and "...do not consider impact to groundwater or address ecological concerns." (USEPA 2002). Expansion of the USEPA PRGs in the lookup tables presented in this document includes:

- Modification of soil PRGs to reflect CalEPA-specific toxicity factors;
- Adjustment of PRGs for noncarcinogens to reflect a target hazard quotient of 0.2 to address potential cumulative health concerns;
- Addition of direct-exposure screening levels for construction and trench workers' exposure to subsurface soils;
- Addition of soil and groundwater screening levels for indoor-air impact concerns;
- Addition of groundwater screening levels for the protection of aquatic habitats/surface water quality;
- Use of a more rigorous leaching model to develop soil screening levels for protection of groundwater quality;
- Addition of soil screening levels for urban area, ecological concerns;
- Addition of soil and groundwater "ceiling levels" to address gross contamination and general resource degradation concerns; and
- Addition of soil and groundwater screening levels for Total Petroleum Hydrocarbons (TPH).

Use of the USEPA Region IX PRGs in the RWQCB lookup tables is discussed further in Section 3.2 of Appendix 1. A copy of the PRG background document is provided in Appendix 2.

1.3.2 City of Oakland Screening Levels

A brief comparison of the RWQCB and the City of Oakland approaches to the development of environmental screening levels is provided in Table 1-1. Since 1999, the City of Oakland has presented environmental screening levels for soil and groundwater through its Urban Land Redevelopment (ULR) Program. The ULR Program is a collaborative effort by the City of Oakland and the principal agencies charged with enforcing environmental regulations in Oakland to facilitate the cleanup and redevelopment of contaminated properties (Oakland 2000). It includes innovative institutional mechanisms for tracking residual contamination and ensuring long-term compliance with risk management plans. The ULR Program is coordinated by the City and is specific to Oakland sites.

The City of Oakland approach is based on the guidelines prescribed in Standard Guide for Risk-Based Corrective Action Applied at Petroleum Release Sites (ASTM 1995). The Guidance Document, Technical Background Document and other information on the Oakland ULR program is available on the internet at www.oaklandpw.com/ulrprogram. Modifications have been made to better address child exposure and recreational water use scenarios. In addition, many input values reflect Oakland-specific geologic, hydrogeologic and climatic conditions (Oakland Technical Background 2000 and

updates). These values may not be appropriate for other areas within the RWQCB's jurisdiction.

The RWQCB has agreed that the Oakland look-up tables are appropriate for use at Oakland sites under the conditions and limitations discussed in the ULR Program Guidance (memo dated August 3, 2001; RWQCBSF 2001b). In particular, sites where surface or groundwater conditions present ecological, aesthetic, taste or odor concerns may require additional analysis. Active remediation to address these concerns may not be necessary at most sites in Oakland that are not near sensitive water bodies, however, due to its highly-developed, urban setting

1.3.3 Hazardous Waste Regulations

California Total Threshold Limit Concentrations (TTLC) criteria for solids and Soluble Threshold Limit Concentration (STLC) criteria for liquids should not in most cases be used as soil and groundwater screening or cleanup levels. The TTLC and STLC criteria are intended to determine the type of landfill a waste material must be sent to (Title 22, Section 66699 - Persistent and Bioaccumulative Toxic Waste). Where TTLC or STLC criteria are exceeded, the waste must in general be sent to a Class I, hazardous waste landfill. The criteria, developed in the 1980s, are only loosely based on human health and environmental considerations. STLC values in general reflect drinking water or surface water goals of the time, although some are clearly out-of-date (e.g. trichloroethylene STLC value of 204 mg/L). TTLC values were derived by simply multiplying the STLC value by ten (organic substances) or one hundred (metals).

In most cases, TTLC values exceed the most conservative environmental screening levels presented in this document. In the case of Endrin and DDT/DDE/DDD, however, the TTLC is somewhat lower than the screening levels for human health concerns. For example, the TTLC for combined DDT/DDE/DDD is 1.0 mg/kg while the residential, direct-exposure soil screening is 1.7 mg/kg. This presents the enigma that while soil impacted below 1.7 mg/kg is not considered to pose a significant risk to human health, it could be classified as a "hazardous waste" if it were excavated and transported offsite for disposal. Again, this is not a difference of opinion about the potential toxic effects of these chemicals, it is merely a reflection of the less rigorous development of the TTLC values.

Unfortunately, it is not anticipated that the TTLC and STLC values will be revised in the near future. To avoid potential future problems with soil disposal and even public perception, it may be prudent to use TTLCs as final cleanup values for sites where the TTLC is less than cleanup values based on actual risk to human health and the environment.

RO0000014 – Site History

BP Oil No. 11132 3201 35th Avenue Oakland, CA 94619

The site is currently an operating BP Oil service station with three USTs (2-10K and 1-12K?) that were installed in 1987 after the first generation USTs were removed. The dispensers and product lines were not removed and upgraded until August 1990.

When the first generation tanks were removed, soil samples collected from beneath the tanks contained up to 420ppm TPHg. Prior, in July 1986, three groundwater monitoring wells (MW-1 through MW-3) were installed at the site. Dissolved petroleum hydrocarbons were detected in the water samples. To date, ten wells (MW-1 through MW-10) and one recovery well (RW-1) have been installed on- and off-site to delineate the vertical and lateral extent of the contaminant plume. Free product has been detected in wells MW-1, MW-2 and in the recovery well. Recently, free product is still measured in wells MW-1, MW-8, and MW-10.

In August 1992, an interim remediation system was installed. Groundwater and separate phase hydrocarbons was extracted from RW-1 and treated by 2-2,000 pound activated carbon vessels. The treated water was discharged to the sanitary sewer system. Groundwater extraction terminated on November 25, 1992.

Hydrocarbon-impacted soil is present in the vicinity of the UST complex at a depth interval from 13 to 27 feet bgs.

An aquifer pump test was performed in April 1991. The average transmissivity of the aquifer beneath the site was calculated to be 0.392 ft²/min. Soil typed encountered generally consisted of silty clay.

9/02 - Whywasid week Mo-5 sampled, need to delineate plume, control plume my attribute sections of isoporth + reseducy mother of gratient, continual same without future CAP
1/02 - Requested reports of subsidere invostigation
- would like to see another used so of Mw-8 - along 35th - another 60-60-feet away.

BP, 3201-35 the are

2131/03

5/2/03

5/2/03

5-SE

11/12/02

5W

6/20/02

5W

2/20/02

5W

5W, S, SE

9190/03 - Lestond don't nd zont rone al 5 Mw 9,6 2 2 rowing geoprobe and Leona UB 8/7 react UST/2 forward 10/4/03 Fronduit - incl x see mis removal '86 mis 10/11/90- P1,2,3, PT-1,2,34 mis 2/4/90 MW4, RW-1, MW5, MW6, MW7 mis 12/16/94 - THP1-5-4-4,5 rollected 1, Mr 194 mis 58 B, 9, 10 3/91

BP, 3201-35th Ove 7/31/03 5/28/03 WP 2 1 contents SAP RUDCB RBSL disapre - RWO CB RBSL for TPH, +5 mg/l MTBE, JA RBCA 1 horing Posations 20-30'below-1st exemptered W 8/2,63 5/28/03 WP proposed vongs for appear of




TABLE 1 - SUMMARY OF RESULTS OF GROUNDWATER MONITERING

WELL ID	DATE OF SAMPLING/ MONITORING	CASING ELEVATION (a) (Feet)	DEPTH TO WATER (Feet)	PRODUCT THICKNESS (Feet)	GROUNDWATER ELEVATION (b) (Feet)	TPH-G (ug/L)	B (ug/L)	T (ug/L)	E (ug/L)	X (ug/L)	MTBE (ug/L)	DO (ppm)	LAB
MW-1	07/09/90	169.75	***	0.22					•••				
MW-1	12/21/90	169.75		0.58			***		*****		*		
MW-1	03/07/91	169.75	20.59				***		***		***		•
MW-1	06/27/91	169.75		0.18	* ***					***	Motored		***
MW-1	09/27/91	169.75		0.27	***		-		***		-	****	
MW-1	12/18/91	169.75		0.28		-	***		****	*****		***	
MW-1	04/01/91	169.75	16.51	0.15	153.35		***						
MW-1	07/03/92	169.75	22.30	0.27	147.65	***					***	www	
MW-1	10/05/92	169.75	23.98	0.24	145.95				***				
MW-1	01/13/93	169.75	17.03	0.24	152.90			***			6-10-da	***	-
MW-1	04/23/93	169.75	18.10	0.42	151.97	-					***	-	
MW-1	07/12/93	169.75	22.02	0.49	148.10			-			S	****	
MW-1	10/21/93	169.75	25.12	1.09	145.45					***	***		
MW-1	01/21/94	169.75	23.02	0.76	147.30		-		***		***		
MW-1	04/20/94	169.75	24.54	1.80	146.56			-	***				***
MW-1	08/01/94	169.75	24.11	0.35	145.90			air.	***	***			
MW-1	12/23/94	169.75	18.19	0.29	151.78				***				
MW-1	01/26/95	169.75	16.25	1.10	154.33					***			
MW-1	06/08/95	169.75	22.92	1.20	147.73				***				
MW-1	08/22/95	169.75	24.45	0.85	145.94			***	***				
MW-1	10/27/95	169.75	25.41	0.69	144.86								
MW-1	01/25/96	169.75	18.20	1.40	152.60	***			***				***
MW-1	04/19/96	169.75	19.06	1.22	151,61	***	****					***	
MW-1	07/23/96	169.75	22.98	0.89	147.44	-							nten.
MW-1	11/11/96	169.75	23.99	0.98	146.50		***	*	ii-ai-	***			
MW-1	01/21/97	169.75	16.80	0.90	153.63	***	nei e				***		
MW-1	04/29/97	169.75	21.90	0.85	148.49	***		***	****		***		
MW-1	04/30/97	169.75				100000	3600	8000	4000	21300	7700	5.2	SPL
QC-1 (92000	3500	8100	4400	23800	6900		SPL
MW-1	08/21/97	169.75	23.40	0.87	147.00	140000	3000	8500	3900	22100	5700	5.3	SPL
QC-1 (***				120000	3200	8100	3800	19600	5200		SPL
MW-1	11/05/97	169.75	23.70	0.54	146.46	68000	6200	4400	3300	14300	8000	4.7	SPL
QC-1 (140,40	88000	7300	4800	3600	16900	8200	7.7	SPL
MW-1	02/03/98	169.75	13.63	0.32	156.36					10900			3FL
MW-1	02/04/98				100.00	190000	2200	10000	5600	32000	ND<10000	5.3	SPL
QC-1 (-				160000	2300	8400	5000	29400	ND<10000	J.J	SPL

8∀1	(bbw) DO	38TM (J\gu)	(ק/pn) X	(n3\ך) E	T (1/6n)	(ח/bn) 8	Ð-H q T (⊐\gu)	GROUNDWATER ELEVATION (b) (Feet)	PRODUCT (Feet)	OE HTGED ABTAW (fee9)	CASING ELEVATION (a) (Feet)	DATE OF SAMPLING/ DNIROTINOM	ID WELL
748	8.6	5900	00061	3600	3900	086	00078	151.85	71.0	18.03	37.691	86/87/90	I-WW
74\$		3600	16000	2900	3200	230	00002	15.031	80.0	19.50	37.691	12/30/98	r-wn
74\$		3200	21000	3200	3100	480	00062	150.84	60.0	18.93	37.691	05/05/88	r-WN
74\$	-	3000	24000	3200	1900	۱60	110000	121.49	60.0	18.28	37.691	66/01/90	I-WN
74\$		ND<20	19000	1900	1300	920	110000	79.64r	90.0	20.13	97.691	08\Z\4\66	r-WN
PACE		0068	0096	3300	1100	9300	00099	22.74r	96.0	72.22	37.691	11/03/66	I-WN
	-			***		***	***	155.14	62.0	67.4r	37.691	03/01/00	(4) I-MN
PACE	****	1300	12000	2100	780	330	61000	16.131	66.0	01.81	37.691	04/21/00	r-ww
PACE	***	2,700	120000	24000	2100	340	1500000	148.57	65.0	21.60	37.691	00/12/70	1-WN
PACE	***	3900	93000	19000	2300	1800	17000071	148.36	75.0	21.69	27.631	11/20/00	I-WW
-						***	***	31.531	£1.0	16.70	37.691	10/81/20	I-WM
PACE		1890	12000	4510	997	829	100000	122.49	31.0	14.38	37.691	02/26/01	I-WN
PACE		2720	12200	9820	0 † †	407	00004	76.841	00.0	87.02	37.631	10/20/90	I-WN
		***						79.941	95.0	23,36	37.691	10/90/60	(i) r-wn
				AF-100-00	***			149.23	14.0	20.85	27.631		NM-1 (K)
PACE		2400	4200	2150	762	3200	39000	151.25	72.0	27.81	37.691	12/06/01	I-WN

TABLE 1 - SUMMARY OF RESULTS OF GROUNDWATER MONITERING

WELL	DATE OF SAMPLING/ MONITORING	CASING ELEVATION (a) (Feet)	DEPTH TO WATER (Feet)	PRODUCT THICKNESS (Feet)	GROUNDWATER ELEVATION (b) (Feet)	TPH-G (ug/L)	B (ug/L)	T (ug/L)	E (ug/L)	X (ug/L)	MTBE (ug/L)	D (Pr		LAB
MW-2	07/09/90	168.14		0.10					***			-	-	
MW-2	12/21/90	168.14		0.48								-	-	
MW-2	03/07/91	168.14	19.18									-		
MW-2	06/27/91	168.14	***	0.19	***	****		***	***	***		-		
MW-2	09/27/91	168.14	***	0.15	***	***	***		***	-		-		
MW-2	12/18/91	168.14	***	0.36								-		
MW-2	04/01/91	168.14	15.21	0.10	153.01	***			•••			-		
MW-2	07/03/92	168.14	20.93	0.03	147.23		****		***	-				
MW-2	10/05/92	168.14	22.74	0.21	145.56							-		
MW-2	01/13/93	168.14	15.55	0.02	152.61					-		-		
MW-2	04/23/93	168.14	16.54	0.21	151.76		****			***		-	-	****
MW-2	07/12/93	168.14	20.46	0.06	147.73		***	***			***	-		
MW-2	10/21/93	168.14	24.91	0.31	143.46	***								
MW-2	01/21/94	168.14	21.20		146.94	***						-		
MW-2	04/20/94	168.14	22.44		145.70	1800	140	370	54	290	24	(i) 1	.7	PACE
MW-2	08/01/94	168.14	22.24	0.04	145.93		***					-		
MW-2	12/23/94	168.14	16.25	0.03	151.91		****					-		
MW-2	01/26/95	168.14	14.55	0.39	153.88		***					-		
MW-2	06/08/95	168.14	21.18	0.43	147.28								-	***
MW-2	08/22/95	168.14	22.76	0.36	145.65		***							
MW-2	10/27/95	168.14	23.61	0.30	144.76						***			
MW-2	01/25/96	168.14	15.95	0.15	152.30		-					-		
MW-2	04/19/96	168.14	17.33	0.07	150.86						1		-	
MW-2	07/23/96	168.14	21.25	0.05	146.93	at spin			***	-		-	-	
MW-2	11/11/96	168.14	22.27	0.01	145.88							•	-	
MW-2	01/21/97	168.14	15.19	0.01	152.96			***					-	
MW-2	04/29/97	168.14	20.22	0.01	147.93			***			****	••		
MW-2	04/30/97	168.14			***	130000	4600	15000	6000	37000	ND<5000	5.		SPL
MW-2	08/21/97	168.14	21.74	0.01	146.41	110000	6000	16000	4700	28000	ND<500	4.		SPL
MW-2	11/05/97	168.14	21.61	0.01	146.54	120000	7800	18000	4900	28100	ND<2500	4.		SPL
MW-2	02/03/98	168.14	11.51	***	156.63	75000	590	1500	1800	12800	ND<2500	4.		SPL
MW-2	05/28/98	168.14	16.51	-	151.63	79000	3900	3100	3100	18000	900	4.	.3	SPL
MW-2	12/30/98	168.14	17.70		150.44	95000	4700	3500	3700	21000	ND<250	_	-	SPL
MW-2	02/02/99	168.14	15.46	-	152.68	170000	3500	1500	5200	34000	ND<500		-	SPL
MW-2	05/10/99	168.14	16.52		151.62	84000	3200	3200	3700	20000	75		-	SPL
MW-2	08/24/99	168.14	20.73	*	147.41	130000	9100	9200	4700	27000	ND<250	•••	-	SPL

TABLE 1 - SUMMARY OF RESULTS OF GROUNDWATER MONITERING

WELL ID	DATE OF SAMPLING/ MONITORING	CASING ELEVATION (a) (Feet)	DEPTH TO WATER (Feet)	PRODUCT THICKNESS (Feet)	GROUNDWATER ELEVATION (b) (Feet)	TPH-G (ug/L)	B (ug/L)	T (ug/L)	E (ug/L)	X (ug/L)	MTBE (ug/L)	DO (ppm)	LAB
MW-2	11/03/99	168.14	20.93		147.21	120000	10000	21000	4700	30200	2200		PACE
MW-2	03/01/00	168.14	13.37		154.77	39000	1400	1500	1700	8100	44		PACE
MW-2	04/21/00	168.14	16.59	***	151.55	68000	3300	2500	3100	20000	260		PACE
MW-2	07/31/00	168.14	16.37		151.77	99000	5600	1400	4300	22000	490		PACE
MW-2	11/20/00	168.14	19.71		148.43	37000	5100	1500	1300	4800	2800		PACE
MW-2	02/18/01	168.14	15.29		152.85	54000	5020	3880	2850	15400	1010		PACE
MW-2	06/07/01	168.14	19.43		148.71	110000	7240	4380	4160	22100	567		PACE
MW-2	09/05/01	168.14	22.44		145.70	69000	5750	5790	2770	14200	1510		PACE
MW-2	11/30/01	168.14	19.58	***	148.56	120000	7270	6540	4590	23000	794	***	PACE

TABLE 1 - SUMMARY OF RESULTS OF GROUNDWATER MONITERING

WELL. ID	DATE OF SAMPLING/ MONITORING	CASING ELEVATION (a) (Feet)	DEPTH TO WATER (Feet)	PRODUCT THICKNESS (Feet)	GROUNDWATER ELEVATION (b) (Feet)	TPH-G (ug/L)	B (ug/L)	T (ug/L)	E (ug/L)	X (ug/L)	MTBE (ug/L)		DO (ppm)	LAB
MW-3	07/09/90	167.17			***	140	5.3	4.6	2.0	3.8				
MW-3	12/21/90	167.17		***		0.19	100	6.0	0.9	27			****	
MW-3	03/07/91	167.17	17.40		149.77	0.4	69	22	6.1	57			***	
MW-3	06/27/91	167.17				380	28	26	13	46	•••			
MW-3	09/27/91	167.17				0.07	7.9	ND	0.4	1.1	***			
MW-3	12/18/91	167.17				0.26	34	24	0.8	28				
MW-3	04/01/91	167.17	13.69		153.48	ND ·	ND	ND	ND	ND				
MW-3	07/03/92	167.17	19.59	-	147.58	71	9.4	0.9	5.0	13				ANA
MW-3	10/05/92	167.17	21.22		145.95	67	5.1	1.1	6.1	8.1	***			ANA
QC-1 (c) 10/05/92					ND<50	2.2	ND<0.5	1.5	2.8				ANA
MW-3	01/13/93	167.17	13.63		153.54	830	50	34	42	89		(i)		PACE
MW-3	04/23/93	167.17	15.02	***	152.15	ND<50	ND<0.5	ND<0.5	ND<0.5	ND<0.5		(i)		PACE
QC-1 (c) 04/23/93		***		***	ND<50	ND<0.5	ND<0.5	ND<0.5	ND<0.5		(i)		PACE
MW-3	07/12/93	167.17	19.16		148.01	250	12	4.2	12	16	ND<5.0	(i)	***	PACE
MW-3	10/21/93	167.17	21.81		145.36	52	4.4	1.4	4.7	3.3	ND<5.0	(i)		PACE
QC-1 (c) 10/21/93					65	7.4	1.0	6.9	4.2				PACE
MW-3	01/21/94	167.17	19.94		147.23	57	3.0	3.4	3.6	9.0	ND<5.0	(i)		PACE
MW-3	04/20/94	167.17	20.24		146.93	600	26	23	33	88	28.7	(i)	1.8	PACE
MW-3	08/01/94	167.17	20.74		146.43	99	6.2	1.1	4.5	5.2	ND<5.0	(i)	1.4	PACE
QC-1 (c) 08/01/94					120	7.7	1.6	5.9	6.7	5.43	(i)		PACE
MW-3	12/23/94	167.17	14.70		152.47	ND<50	ND<0.5	0.78	ND<0.5	ND<0.5	9.8	(i)	1.7	PACE
QC-1 (c) 12/23/94					ND<50	ND<0.5	ND<0.5	ND<0.5	ND<0.5				PACE
MW-3	01/26/95	167.17	12.89		154.28	190	16	0.5	35	24			6.6	ATI
MW-3	06/08/95	167.17	19.95		147.22	330	21	4.0	34	32			7.0	ATI
MW-3	08/22/95	167.17	21.41		145.76	150	14	ND<0.50	ND<0.50	1.6	ND<5.0	(d)	6.6	ATI
MW-3	10/27/95	167.17	22.43		144.74			***						
MW-3	10/30/95	167.17				51	2.4	ND<0.50	ND<0.50	ND<1.0	ND<5.0		6.9	ATI
MW-3	01/25/96	167.17	14.03		153.14	ND<50	ND<0.50	ND<0.50	ND<0.50	ND<1.0	5.1			CEI
MW-3	04/19/96	167.17	15.26		151.91	460	55	4	33	63	ND<10		9.4	SPL
MW-3	07/23/96	167.17	19.19		147.98	ND<50	ND<0.5	ND<0.5	ND<0.5	ND<0.5	ND<10		9.2	SPL
MW-3	11/11/96	167.17	20.24		146.93	ND<250	ND<2.5	ND<5.0	ND<5.0	ND<5.0	ND<50		8.4	SPL
MW-3	01/21/97	167.17	13.09	***	154.08	ND<50	ND<0.5	ND<1.0	ND<1.0	ND<1.0	ND<10		5.4	SPL
MW-3	04/29/97	167.17	18.14	***	149.03	ND<50	ND<0.5	ND<1.0	ND<1.0	ND<1.0	ND<10		4.3	SPL
MW-3	08/21/97	167.17	19.64		147.53	ND<50	ND<0.5	ND<1.0	ND<1.0	ND<1.0	ND<10		4.9	SPL
MW-3	11/05/97	167.17	19.95		147.22	ND<250	ND<2.5	ND<5.0	ND<5.0	ND<5.0	ND<50		4.5	SPL

TABLE 1 - SUMMARY OF RESULTS OF GROUNDWATER MONITERING

WELL	DATE OF SAMPLING/ MONITORING	CASING ELEVATION (a) (Feet)	DEPTH TO WATER (Feet)	PRODUCT THICKNESS (Feet)	GROUNDWATER ELEVATION (b) (Feet)	TPH-G (ug/L)	B (ug/L)	T (ug/L)	E (ug/L)	X (ug/L)	MTBE (ug/L)	DO (ppm)	LAB
MW-3	02/03/98	167.17	10.57	-	156.60	ND<50	ND<0.50	ND<1.0	ND<1.0	ND<1.0	ND<10	4.7	CDI.
MW-3	05/28/98	167.17	14.65		152.52	330	ND<2.5	ND<5.0	ND<5.0	ND<5.0	ND<50	4.7 4.2	SPL SPL
MW-3	12/30/98	167.17	16.63		150.54		***					4.2	1 (1)
MW-3	02/02/99	167.17	13.12		154.05	<250	<5.0	<5.0	<5.0	<5.0	<5.0		SDI
MW-3	05/10/99	167.17	14.21		152.96		***			-0.0	~5.0	-	SPL
MW-3	08/24/99	167.17	14.36		152.81		***						-11
MW-3	11/03/99	167.17	19.21		147.96		***						
MW-3	03/01/00	167.17	15.17		152.00	ND<50	ND<0.5	0.57	ND<0.5	0.62	ND<0.5		
MW-3	04/21/00	167.17	14.88		152.29			0.01			ND<0.5		PACE
MW-3	07/31/00	167.17	15.29		151.88					es principal de la companya della companya della companya de la companya della co			***
MW-3	11/20/00	167.17	17.31		149.86		***				***		
MW-3	02/18/01	167.17	12.85		154.32	160	1.95	1.31	10.2	9.09	4.0		
MW-3	06/07/01	167.17	18.00		149.17			1.51			1.0		PACE
MW-3	09/05/01	167.17	20.32		146.85					***			
MW-3	11/30/01	167.17	16.94	··· /	150.23		***				· ·		

TABLE 1 - SUMMARY OF RESULTS OF GROUNDWATER MONITERING

WELL ID	DATE OF SAMPLING/ MONITORING	CASING ELEVATION (a) (Feet)	DEPTH TO WATER (Feet)	PRODUCT THICKNESS (Feet)	GROUNDWATER ELEVATION (b) (Feet)	TPH-G (ug/L)	B (ug/L)	T (ug/L)	E (ug/L)	X (ug/L)	MTBE (ug/L)		DO (ppm)	LAB
MW-4	07/09/90	170.36				ND	ND	ND `	ND	ND				
MW-4	12/21/90	170.36		***		ND	ND	ND	ND	8.0			***	-
MW-4	03/07/91	170.36	20.72		149.64	ND	2.2	3.8	1.5	2.8			***	
MW-4	06/27/91	170.36		***		ND	6.3	1.8	0.4	1.0				***
MW-4	09/27/91	170.36		***		ND	ND	ND	ND	ND				***
MW-4	12/18/91	170.36			•••	ND	ND	ND	ND	ND	• •••			
MW-4	04/01/91	170.36	17.49		152.87	ND	ND	ND	ND	ND				
MW-4	07/03/92	170.36	22.16	***	148.20	ND<50	ND<0.5	ND<0.5	ND<0.5	ND<0.5			***	ANA
MW-4	10/05/92	170.36	23.38		146.98	ND<50	ND<0.5	ND<0.5	ND<0.5	ND<0.5				ANA
MW-4	01/13/93	170.36	17.58	***	152.78	ND<50	ND<0.5	ND<0.5	ND<0.5	ND<0.5		(i)		PACE
MW-4	04/23/93	170.36	15.72		154.64	ND<50	ND<0.5	ND<0.5	ND<0.5	ND<0.5		(i)		PACE
MW-4	07/12/93	170.36	21.74		148.62	ND<50	ND<0.5	ND<0.5	ND<0.5	ND<0.5	ND<5.0	(i)	****	PACE
MW-4	10/21/93	170.36	23.84		146.52	ND<50	ND<0.5	ND<0.5	ND<0.5	ND<0.5	ND<5.0	(i)		PACE
MW-4	01/21/94	170.36	22.42		147.94	ND<50	ND<0.5	ND<0.5	ND<0.5	ND<0.5	ND<5.0	(i)		PACE
MW-4	04/20/94	170.36	22.66	***	147.70	ND<50	ND<0.5	ND<0.5	ND<0.5	ND<0.5	ND<5.0	(i)	2.2	PACE
MW-4	08/01/94	170.36	23.01	***	147.35	ND<50	ND<0.5	ND<0.5	ND<0.5	ND<0.5	ND<5.0	(i)	1.9	PACE
MW-4	12/23/94	170.36	17.03		153.33									
MW-4	01/26/95	170.36	17.42		152.94	ND<50	ND<0.5	ND<0.5	ND<0.5	ND<1			7.5	ATI
MW-4	06/08/95	170.36	21.55		148.81			****	****					***
MW-4	08/22/95	170.36	23.47	***	146.89	ND<50	ND<0.50	ND<0.50	ND<0.50	ND<1.0	ND<5.0	(d)	6.4	ATI
MW-4	10/27/95	170.36	24.50	***	145.86	***								
MW-4	01/25/96	170.36	18.74		151.62	ND<50	ND<0.50	ND<0.50	ND<0.50	ND<1.0	58			CEI
MW-4	04/19/96	170.36	18.63		151.73					***	-			
MW-4	07/23/96	170.36	22.56		147.80		***			***				
MW-4	11/11/96	170.36	23.63		146.73	ND<50	ND<1.0	ND<1.0	ND<1.0	ND<1.0	34		8.2	SPL
MW-4	01/21/97	170.36	16.59		153.77			****						
MW-4	04/29/97	170.36	21.43		148.93	ND<50	ND<0.5	ND<1.0	ND<1.0	ND<1.0	ND<10		4.7	SPL
MW-4	08/21/97	170.36	22.91	****	147.45		***							
MW-4	11/05/97	170.36	22.34		148.02	60	ND<0.5	ND<1.0	ND<1.0	ND<1.0	76		4.9	SPL
MW-4	02/03/98	170.36	12.26	***	158.10			'		-				SPL
MW-4	05/28/98	170.36	18.50		151.86	70	ND<0.5	ND<1.0	ND<1.0	ND<1.0	160		4.2	SPL
MW-4	12/30/98	170.36	19.69		150.67				***					***
MW-4	02/02/99	170.36	18.26	***	152.10	70	ND<1.0	ND<1.0	ND<1.0	ND<1.0	130			SPL
MW-4	05/10/99	170.36	17.86		152.50		***	des						-
MW-4	08/24/99	170.36	17.93		152.43				***				***	-
MW-4	11/03/99	170.36	22.78		147.58									

TABLE 1 - SUMMARY OF RESULTS OF GROUNDWATER MONITERING

WELL	DATE OF SAMPLING/ MONITORING	CASING ELEVATION (a) (Feet)	DEPTH TO WATER (Feet)	PRODUCT THICKNESS (Feet)	GROUNDWATER ELEVATION (b) (Feet)	TPH-G (ug/L)	B (ug/L)	T (ug/L)	E (ug/L)	X (ug/L)	MTBE (ug/L)	DO (ppm)	LAB
MW-4	03/01/00	170.36	18.04		152.32	ND<50	ND<0.5	0.67	ND<0.5	0.7	110	***	PACE
MW-4	04/21/00	170.36	17.36		153.00								
MW-4	07/31/00	170.36	17.83		152.53	***							₩-
MW-4	11/20/00	170.36	18.91	***	151.45								#-
MW-4	02/18/01	170.36	17.72		152.64	88	ND<0.5	ND<0.5	ND<0.5	ND<0.5	97.3		PACE
MW-4	06/07/01	170.36	20.23		150.13								-
MW-4	09/05/01	170.36	22.76		147.60				-	***		***	#
MW-4	11/30/01	170.36	21.30		149.06	***	***						H -

TABLE 1 - SUMMARY OF RESULTS OF GROUNDWATER MONITERING

WELL ID	DATE OF SAMPLING/ MONITORING	CASING ELEVATION (a) (Feet)	DEPTH TO WATER (Feet)	PRODUCT THICKNESS (Feet)	GROUNDWATER ELEVATION (b) (Feet)	TPH-G (ug/L)	B (ug/L)	T (ug/L)	E (ug/L)	X (ug/L)	MTBE (ug/L)		DO (ppm)	LAB
MW-5	07/09/90	165.14			Scotts.	280	200	210	46	290				***
MW-5	12/21/90	165.14				0.69	300	34	8.4	39				***
MW-5	03/07/91	165.14	16.60		148.54	ND	17	0.9	0.7	1.6				
MW-5	06/27/91	165.14	***	***	***	330	120	10	12	8				
MW-5	09/27/91	165.14				0.73	230	16	20	22				
MW-5	12/18/91	165.14			***	ND	ND	ND	ND	ND				***
MW-5	04/01/91	165.14	11.99		153.15	800	250	54	11	60				
MW-5	07/03/92	165.14	18.65		146.49	150	36	ND<0.5	ND<0.5	1.1				ANA
'MW-5	10/05/92	165.14	20.32		144.82	270	79	4	1.7	2.9	***		***	ANA
MW-5	01/13/93	165.14	13.03		152.11	180	59	6.0	- 1.8	7.6		(i)	***	PACE
MW-5	04/23/93	165.14	13.51		151.63	8700	440	96	35	136		(i)		PACE
MW-5	07/12/93	165.14	18.06		147.08	250	57	2.9	2.1	6.0	ND<5.0	(i)		PACE
MW-5	10/21/93	165.14	20.41		144.73	210	82	1.5	ND<0.5	1.4		(i)		PACE
MW-5	01/21/94	165.14	18.86		146.28	110	36	1.2	ND<0.5	0.7	ND<5.0	(i)	***	PACE
MW-5	04/20/94	165.14	17.30		147.84	690	230	4.5	1.6	11	21.2	(i)	1.3	PACE
MW-5	08/01/94	165.14	17.53	•••	147.61	170	44	1.6	0.9	2.7	ND<5.0	(i)	0.9	PACE
MW-5	12/23/94	165.14	11.63		153.51	630	180	1.9	0.66	1.9	7.81	(i)	1.4	PACE
MW-5	01/26/95	165.14	11.25	•••	153.89	160	68	ND<0.5	ND<0.5	22			5.9	ATI
MW-5	06/08/95	165.14	16.80		148.34	2000	630	58	61	180			6.5	ATI
QC-1 (c) 06/08/95	-			***	1700	560	51	55	170				ATI
MW-5	08/22/95	165.14	19.02	****	146.12	3700	1100	18	27	59	ND<130	(d)	7.3	ATI
MW-5	10/27/95	165.14	20.94		144.20			***						
MW-5	10/30/95	165.14				6500	2200	55	180	270	ND<250		7.5	ATI
MW-5	01/25/96	165.14	13.30		151.84	590	37	0.70	ND<0.50	ND<1.0	ND<5.0			CEI
QC-1 (c) 01/25/96	***			***	540	37	0.66	ND<0.50	ND<1.0	ND<5.0			CEI
MW-5	04/19/96	165.14	13.63		151.51	1500	470	38	49	210	ND<50		8.1	SPL
MW-5	07/23/96	165.14	17,61		147.53	140	4.6	ND<0.5	ND<0.5	ND<0.5	ND<10		8.0	SPL
MW-5	11/11/96	165.14	18.70		146.44	140	40	ND<1.0	ND<1.0	ND<1.0	ND<10		7.9	SPL
MW-5	01/21/97	165.14	11.63	0.00	153.51	730	300	ND<5.0	7.8	26	ND<50		5.0	SPL
MW-5	04/29/97	165.14	16.74		148.40	340	530	ND<5.0	ND<5.0	ND<5.0	ND<50		4.8	SPL
MW-5	08/21/97	165.14	18.26		146.88	ND<50	ND<0.5	ND<1.0	ND<1.0	ND<1.0	ND<10		4.9	SPL
MW-5	11/05/97	165.14	18.84		146.30	120	13	ND<1.0	ND<1.0	ND<1.0	ND<10		4.4	SPL
MW-5	02/03/98	165.14	9.49		155.65	ND<50	ND<0.50	ND<1.0	ND<1.0	ND<1.0	ND<10		4.3	SPL
MW-5	05/28/98	165.14	13.57	•	151.57	4900	1500	34	180	311	ND<10		4.1	SPL
MW-5	12/30/98	165.14	14.65		150.49		***	***		***	***			***

TABLE 1 - SUMMARY OF RESULTS OF GROUNDWATER MONITERING

WELL	DATE OF SAMPLING/ MONITORING	CASING ELEVATION (a) (Feet)	DEPTH TO WATER (Feet)	PRODUCT THICKNESS (Feet)	GROUNDWATER ELEVATION (b) (Feet)	TPH-G (ug/L)	B (ug/L)	T (ug/L)	E (ug/L)	X (ug/L)	MTBE (ug/L)	DO (ppm)	LAB
MW-5	02/02/99	165.14	12.56		152.58	100	ND<1.0	ND<1.0	ND<1.0	ND<1.0	9.1		SPL
MW-5	05/10/99	165.14	13.36		151.78	***				145 41.0			OFL
MW-5	08/24/99	165.14	13.50	-	151.64			***					
MW-5	11/03/99	165.14	18.48		146.66	***			***				
MW-5	03/01/00	165.14	9.59		155.55	ND<50	ND<0.5	0.58	ND<0.5	0.54	2.9	***	DACE
MW-5	04/21/00	165.14	13.52	-	151.62		***			0.04	2.5		PACE
MW-5	07/31/00	165.14	14.04	***	151.10							***	
MW-5	11/20/00	165.14	15.89		149.25		***					***	
MW-5	02/18/01	165.14	11.88		153.26	560	161	2.38	6.11	13	5.67	***	
MW-5	06/07/01	165.14	15.30		149.84			2.00	0.11	13			PACE
MW-5	09/05/01	165.14	19.32		145.82							desam	
MW-5	11/30/01	165.14	17.44		147.70	***	•		; 				-

TABLE 1 - SUMMARY OF RESULTS OF GROUNDWATER MONITERING

WELL ID	DATE OF SAMPLING/ MONITORING	CASING ELEVATION (a) (Feet)	DEPTH TO WATER (Feet)	PRODUCT THICKNESS (Feet)	GROUNDWATER ELEVATION (b) (Feet)	TPH-G (ug/L)	B (ug/L)	T (ug/L)	E (ug/L)	X (ug/L)	MTBE (ug/L)		DO (ppm)	LAB
MW-6	07/09/90	165.40	•••			ND	ND	ND	ND	ND	***		***	
MW-6	12/21/90	165.40				0.17	2.6	7.0	4.9	26			***	
MW-6	e) 03/07/91	165.40												
MW-6	e) 06/27/91	165.40				***								
MW-6	e) 09/27/91	165.40		***	***				***					
MW-6	12/18/91	165.40	direction.			ND	1.3	22	ND	2.7	***		***	
MW-6	04/01/91	165.40	11.79		153.61	ND	ND	ND	ND	ND				
MW-6	07/03/92	165.40	17.77	•••	147.63	ND<50	ND<0.5	ND<0.5	ND<0.5	ND<0.5	***			ANA
MW-6	10/05/92	165.40	19.46		145.94	ND<50	ND<0.5	ND<0.5	ND<0.5	ND<0.5				ANA
MW-6	01/13/93	165.40	11.34	•••	154.06	ND<50	ND<0.5	ND<0.5	ND<0.5	ND<0.5		(i)		PACE
MW-6	04/23/93	165.40	12.92		152.48	ND<50	ND<0.5	ND<0.5	ND<0.5	ND<0.5		(i)		PACE
MW-6	07/12/93	165.40	17.36		148.04	ND<50	ND<0.5	ND<0.5	ND<0.5	0.7	ND<5.0	(i)		PACE
MW-6	10/21/93	165.40	19.98		145.42	ND<50	ND<0.5	ND<0.5	ND<0.5	ND<0.5		(i)		PACE
MW-6	01/21/94	165.40	18.10	***	147.30	ND<50	ND<0.5	ND<0.5	ND<0.5	ND<0.5	ND<5.0	(i)		PACE
MW-6	04/20/94	165.40	18.68		146.72	ND<50	ND<0.5	ND<0.5	ND<0.5	ND<0.5	17.4	(i)	2.0	PACE
MW-6	08/01/94	165.40	18.90	***	146.50	ND<50	ND<0.5	ND<0.5	ND<0.5	ND<0.5	8.66	(i)	1.5	PACE
MW-6	12/23/94	165.40	12.94		152.46									
MW-6	01/26/95	165.40	10.46	•	154.94	ND<50	ND<0.5	ND<0.5	ND<0.5	ND<1			7.3	ATI
MW-6	06/08/95	165.40	16.84	***	148.56							(-1)		A 771
MW-6	08/22/95	165.40	19.48		145.92	ND<50	ND<0.50	ND<0.50	ND<0.50	ND<1.0	ND<5.0	(d)	6.7	ATI
MW-6	10/27/95	165.40	20.39		145.01						9.9			CEI
MW-6	01/25/96	165.40	12.24		153.16	ND<50	ND<0.50	ND<0.50	ND<0.50	ND<1.0				
MW-6	04/19/96	165.40	13.90		151.50		***	***			***			
MW-6	07/23/96	165.40	17.83	***	147.57				ND 44.0	 ND4 O	 ND <10		7.7	SPL
MW-6	11/11/96	165.40	18.90		146.50	ND<50	ND<0.5	ND<1.0	ND<1.0	ND<1.0	ND<10			SPL
MW-6	01/21/97	165.40	11.97		153.43	***					ND 440		4.5	SPL
MW-6	04/29/97	165.40	17.04		148.36	ND<50	ND<0.5	ND<1.0	ND<1.0	ND<1.0	ND<10			
MW-6	08/21/97	165.40	18.58		146.82								4.3	SPL
MW-6	11/05/97	165.40	19.17		146.23	70	ND<0.5	ND<1.0	ND<1.0	ND<1.0	85			
MW-6	02/03/98	165.40	9.87		155.53				ND 44.0	ND-44 C	ND-40		3.7	SPL
MW-6	05/28/98	165.40	13.38		152.02	ND<50	ND<0.5	ND<1.0	ND<1.0	ND<1.0	ND<10			
MW-6	12/30/98	165.40	14.45		150.95		***							
MW-6	02/02/99	165.40	18.29		147.11	. ***	***							
MW-6	05/10/99	165.40	17.49		147.91			***			***			***
MW-6	08/24/99	165.40	17.61		147.79			***			***			***
MW-6	11/03/99	165.40	16.26		149.14				***					

TABLE 1 - SUMMARY OF RESULTS OF GROUNDWATER MONITERING

WELL ID	DATE OF SAMPLING/ MONITORING	CASING ELEVATION (a) (Feet)	DEPTH TO WATER (Feet)	PRODUCT THICKNESS (Feet)	GROUNDWATER ELEVATION (b) (Feet)	TPH-G (ug/L)	B (ug/L)	T (ug/L)	E (ug/L)	X (ug/L)	MTBE (ug/L)	DO (ppm)	LAB
MW-6	03/01/00	165.40	17.43		147.97								
MW-6	04/21/00	165.40	13.32		152.08			***					I
MW-6	07/31/00	165.40	13.46		151.94				***				
MW-6	11/20/00	165.40	14.78	***	150.62				***		***		
MW-6	02/18/01	165.40	11.33	****	154.07								
MW-6	06/07/01	165.40	16.36	***	149.04			***			-	****	
MW-6	09/05/01	165.40	18.61		146.79								1
MW-6	11/30/01	165.40	15.20	***	150.20	***				***		***	

TABLE 1 - SUMMARY OF RESULTS OF GROUNDWATER MONITERING

WELL ID	DATE OF SAMPLING/ MONITORING	CASING ELEVATION (a) (Feet)	DEPTH TO WATER (Feet)	PRODUCT THICKNESS (Feet)	GROUNDWATER ELEVATION (b) (Feet)	TPH-G (ug/L)	B (ug/L)	T (ug/L)	E (ug/L)	X (ug/L)	MTBE (ug/L)		DO (ppm)	LAB
MW-7	07/09/90	167.61	924		***	ND	ND	ND	ND					
MW-7	12/21/90	167.61		***	***	ND	ND	ND	ND	ND				
MW-7	03/07/91	167.61	19.04		148.57	ND	ND	0.4	ND	ND	Mydwyd			***
MW-7	06/27/91	167.61	****	***		70	17	4	0.3	2.4				
MW-7	09/27/91	167.61	***	***	***	ND	0.4	ND T	0.8	2.2			***	
MW-7	12/18/91	167.61			***	ND	0.7	2.9	ND	0.4	***			***
MW-7	04/01/91	167.61	15.18		152.43	ND	ND	ND	0.8	3.3				
MW-7	07/03/92	167.61	20.28		147.33	ND<50	ND<0.5	ND<0.5	ND ND 50.5	ND	***			
MW-7	10/05/92	167.61	21.56	***	146.05	ND<50	ND<0.5 ND<0.5		ND<0.5	ND<0.5				ANA
MW-7	01/13/93	167.61	15.41		152.20	ND<50		ND<0.5	ND<0.5	1.5				ANA
MW-7	04/23/93	167.61	15.84	***	151.77	ND<50	ND<0.5	ND<0.5	ND<0.5	ND<0.5		(i)		PACE
MW-7	07/12/93	167.61	19.84	***	147.77	ND<50	ND<0.5	ND<0.5	ND<0.5	ND<0.5		(i)		PACE
MW-7	10/21/93	167.61	21.61		146.00	ND<50	ND<0.5	ND<0.5	ND<0.5	ND<0.5	ND<5.0	· (i)		PACE
MW-7	01/21/94	167.61	20.49	***	147.12	ND<50	ND<0.5	ND<0.5	ND<0.5	ND<0.5	***	(i)		PACE
QC-1	(c) 01/21/94	***			147.12 —		ND<0.5	ND<0.5	ND<0.5	ND<0.5	ND<5.0	(i)		PACE
MW-7	04/20/94	167.61	20.54	***	147.07	ND<50	ND<0.5	ND<0.5	ND<0.5	ND<0.5	***		****	PACE
MW-7	08/01/94	167.61	20.99		146.62	ND<50	ND<0.5	ND<0.5	ND<0.5	ND<0.5	ND<5.0	(i)	1.5	PACE
MW-7	12/23/94	167.61	15.00			ND<50	0.7	ND<0.5	ND<0.5	ND<0.5	ND<5.0	(i)	1.9	PACE
MW-7	01/26/95	167.61	14.69		152.61	***								***
MW-7	06/08/95	167.61	19.87		152.92	ND<50	ND<0.5	ND<0.5	ND<0.5	ND<1			7.0	ATI
MW-7	08/22/95	167.61	21.49		147.74			***	****					
MW-7	10/27/95	167.61	22.53	***	146.12	ND<50	ND<0.50	ND<0.50	ND<0.50	ND<1.0	ND<5.0	(d)	6.4	ATI
MW-7	01/25/96	167.61	17.21		145.08					***		` ,		
MW-7	04/19/96	167.61	17.21		150.40	ND<50	ND<0.50	ND<0.50	ND<0.50	ND<1.0	ND<5.0			CEI
MW-7	07/23/96	167.61	21.02	the street,	150.52			***	***		***			
MW-7	11/11/96	167.61			146.59		***	***		***				-
MW-7	01/21/97	167.61	22.03 15.06	***	145.58	ND<50	ND<0.5	ND<1.0	ND<1.0	ND<1.0	ND<10		7.8	SPL
MW-7	04/29/97	167.61			152.55		***							
MW-7	08/21/97		20.11	***	147.50	ND<50	ND<0.5	ND<1.0	ND<1.0	ND<1.0	ND<10		4.4	SPL
MW-7	11/05/97	167.61	21.59	***	146.02			-		***				
		167.61	20.05		147.56	ND<50	ND<0.5	ND<1.0	ND<1.0	ND<1.0	ND<10		4.4	SPL
MW-7	02/03/98	167.61	9.97	***	157.64		***							SPL
MW-7	05/28/98	167.61	13.52		154.09	ND<50	ND<0.5	ND<1.0	ND<1.0	ND<1.0	ND<10		4.3	SPL
MW-7	12/30/98	167.61	18.33	***	149.28	-								3FL
MW-7	02/02/99	167.61	12.33		149.28			***		-	•			
MW-7	05/10/99	167.61	13.52		154.09	***								
MW-7	08/24/99	167.61	14.01		153.60			-						

TABLE 1 - SUMMARY OF RESULTS OF GROUNDWATER MONITERING

WELL	DATE OF SAMPLING/ MONITORING	CASING ELEVATION (a) (Feet)	DEPTH TO WATER (Feet)	PRODUCT THICKNESS (Feet)	GROUNDWATER ELEVATION (b) (Feet)	TPH-G (ug/L)	B (ug/L)	T (ug/L)	E (ug/L)	X (ug/L)	MTBE (ug/L)	DO (ppm)	LAB
-					147.70				*****		***		
MW-7	11/03/99	167.61	19.91										4-
MW-7	03/01/00	167.61	19.89		147.72	4400							4-
MW-7	04/21/00	167.61	17.94		149.67								
MW-7	07/31/00	167.61	17.33		150.28								III
		167.61	18.41		149.20							***	i i i i i i i i i i i i i i i i i i i
MW-7	11/20/00		15.13		152.48				***	***		***	
MW-7	02/18/01	167.61			148.86		***					***	
MW-7	06/07/01	167.61	18.75		147.13				-				-
MW-7	09/05/01	167.61	20.48								-		4-
MW-7	11/30/01	167.61	20.11		147.50	***							

TABLE 1 - SUMMARY OF RESULTS OF GROUNDWATER MONITERING

WELL ID	DATE OF SAMPLING/ MONITORING	CASING ELEVATION (a) (Feet)	DEPTH TO WATER (Feet)	PRODUCT THICKNESS (Feet)	GROUNDWATER ELEVATION (b) (Feet)	TPH-G (ug/L)	B (ug/L)	T (ug/L)	E (ug/L)	X (ug/L)	MTBE (ug/L)		DO (ppm)	LAB
MW-8	03/07/91	165.74	16.72	e	149.02	2.7	780	450	64	310				
MW-8	06/27/91	165.74	-		***	12000	3400	1100	240	750				
8-WM	09/27/91	165.74	-		•••	41	5700	5200	1100	4300	***			
MW-8	12/18/91	165.74	***			3.2	990	150	120	250			***	
MW-8	04/01/91	165.74	12.54		153.20	15000	3600	2600	410	1900	-			
8-WM	07/03/92	165.74	18.78	***	146.96	72000	19000	32000	3000	15000				ANA
MW-8	10/05/92	165.74	20.48	0.01	145.27		***							
MW-8	01/13/93	165.74	12.87	0.01	152.88									
MW-8	04/23/93	165.74	13.90	SHEEN	151.84	***			***	***				
8-WM	07/12/93	165.74	18.30	SHEEN	147.44			***	***	***			-	
MW-8	10/21/93	165.74	21.91	0.95	144.54									
MW-8	01/21/94	165.74	19.12	0.03	146.64	***	***	***						
MW-8	04/20/94	165.74	19.28	0.03	146.48	26000	1700	4100	960	4000	632	(i)	1.1	PACE
MW-8	08/01/94	165.74								4000		(1)		FACE
MW-8	12/23/94	165.74	13.81	0.03	151.95				•••					
MW-8	01/26/95	165.74				***	***	***						
MW-8	06/08/95	165.74	17.82	0.29	148.14	***		****						
MW-8	08/22/95	165.74	19.41	0.20	146.48	***							***	
MW-8	10/27/95	165.74	20.47	0.14	145.38			***	***		•••			
MW-8	01/25/96	165.74	13.35	0.22	152.56			***	***					***
MW-8	04/19/96	165.74	14.40	0.20	151.49			-		***				-
MW-8	07/23/96	165.74	18.35	0.14	147.50	•••		***		****				
MW-8	11/11/96	165.74	19.41	0.02	146.35		***		***	10.450	***		***	
MW-8	01/21/97	165.74	12.29	0.01	153.46		-	-			***			
MW-8 (e) 04/29/97	165.74	200								-		-	
MW-8	08/21/97	165.74	19.61		146.13	240000	1100	9300	4100	31100	ND<1000		5.2	SPL
MW-8	11/05/97	165.74	19.45	0.10	146.37	57000	790	2700	2300	15200	ND<1000		5.0	SPL
MW-8	02/03/98	165.74	9.33	0.03	156.43		***							
MW-8	02/04/98					94000	570	1500	2100	15200	ND<2500		5.5	SPL
MW-8 (e		165.74		***		****			2100				J.J	
MW-8	12/30/98	165.74	15.48	0.05	150.30	120000	460	2300	2200	15000	150			SPL
MW-8	02/02/99	165.74	18.29		147.45	82000	450	2200	3700	26000	ND<500			SPL
MW-8	05/10/99	165.74	15.62	***	150.12	28000	740	1800	1100	5800	ND<25			SPL
MW-8	08/24/99	165.74	18.41	***	147.33	75000	530	1400	3300	21000	150			SPL
MW-8	11/03/99	165.74	18.71		147.03	70000	600	1300	3600	20500	750			PACE

TABLE 1 - SUMMARY OF RESULTS OF GROUNDWATER MONITERING

WELL I	DATE OF SAMPLING/ MONITORING	CASING ELEVATION (a) (Feet)	DEPTH TO WATER (Feet)	PRODUCT THICKNESS (Feet)	GROUNDWATER ELEVATION (b) (Feet)	TPH-G (ug/L)	B (ug/L)	T (ug/L)	E (ug/L)	X (ug/L)	MTBE (ug/L)	DO (ppm)	LAB
MW-8	03/01/00	165.74	19.37		146.37	27000	1600	1200	2600	6600	120		PACE
MW-8 (e) 04/21/00	165.74		***	•••		***						4
MW-8 (e) 07/31/00	165.74						man.					4
MW-8	11/20/00	165.74	17.42		148.32	1300000	1400	1700	20000	16000	5700		PACE
MW-8 (6	e) 02/18/01	165.74										***	4
MW-8 (e) 06/07/01	165.74											144
MW-8 (j) 09/05/01	165.74	21.45	0.04	144.32								44
MW-8 (165.74	18.31	***	147.43					***			44
MW-8 (e) 12/06/01	165.74		***						***			44

TABLE 1 - SUMMARY OF RESULTS OF GROUNDWATER MONITERING

WELL ID	DATE OF SAMPLING/ MONITORING	CASING ELEVATION (a) (Feet)	DEPTH TO WATER (Feet)	PRODUCT THICKNESS (Feet)	GROUNDWATER ELEVATION (b) (Feet)	TPH-G (ug/L)	B (ug/L)	T (ug/L)	E (ug/L)	X (ug/L)	MTBE (ug/L)		DO (ppm)	LAB
MW-9	03/07/91	166.20	16.79		149.41	7.1	220	4	2.4	2400	***			
MW-9	06/27/91	166.20				3600	520	400	85	310				
MW-9	09/27/91	166.20				3.2	720	150	50	180				
MW-9	12/18/91	166.20			***	ND	2.5	1.1	0.3	5.8	***		***	***
MW-9	04/01/91	166.20	12.89		153.31 ·	12000	2000	2600	360	1600				
MW-9	07/03/92	166.20	18.89	***	147.31	5700	17000	840	230	800				ANA
MW-9	10/05/92	166.20	20.52	***	145.68	1400	440	17	14	100				ANA
MW-9	01/13/93	166.20	12.92		153.28	11000	1200	1700	340	1400		(i)	***	PACE
QC-1 ((c) 01/13/93		-			11000	1200	1600	330	1300		(i)		PACE
MW-9	04/23/93	166.20	14.08		152.12	24000	2800	4500	730	3400		(i)		PACE
MW-9	07/12/93	166.20	18.44		147.76	13000	1400	1100	360	1400	20.8	(i)		PACE
	(c) 07/12/93	***	***			10000	1200	900	310	1200				PACE
MW-9	10/21/93	166.20	21.81	0.89	145.06		***		***					
MW-9	01/21/94	166.20	19.28		146.92				4000	7000	760	/i\	1.7	PACE
MW-9	04/20/94	166.20	19.72		146.48	43000	2800	6800	1300	7900	768 - 740	(i)		PACE
QC-1						45000	2700	6800	1200	8200		(d)		PACE
MW-9	08/01/94	166.20	20.18	0.05	146.06		****							
MW-9	12/23/94	166.20	14.22	0.02	152.00									
MW-9	01/26/95	166.20	11.85	0.13	154.45	***	***	***	***					
MW-9	06/08/95	166.20	18.33	0.80	148.47									
MW-9	08/22/95	166.20	19.95	0.01	146.26	****		***						
MW-9	10/27/95	166.20	20.88	0.01	145.33		***							-
MW-9	01/25/96	166.20	13.84	0.07	152.41		***							
MW-9		166.20	40.04	0.00	 147.38									
MW-9	07/23/96	166.20	18.84	0.03										
MW-9	11/11/96	166.20	19.91	0.01	146.30	***								
MW-9	01/21/97	166.20	12.93	0.01	153.28								***	
MW-9	04/29/97	166.20	18.03	SHEEN	148.17	78000	1900	3600	3100	20600	ND<5000		5.5	SPL
MW-9	04/30/97	166.20	40.50	0.01	146.65	110000	2100	3400	2300	18800	ND<500		5.1	SPL
MW-9	08/21/97	166.20	19.56		145.62	59000	1400	1700	2200	17000	ND<500		4.5	SPL
MW-9	11/05/97	166.20	20.59	0.01	155.64	55000 55000	490	1200	1400	10200	ND<1000		4.9	SPL
MW-9	02/03/98	166.20	10.56	0.01	152.00	41000	250	1200	1500	11400	ND<250		3.8	SPL
MW-9	05/28/98	166.20	14.21	0.01	152.00	53000	290	830	1400	10500	ND<500			SPL
QC-1		466.00	15.61		150.59	83000	860	1300	2400	21000	180			SPL
MW-9	12/30/98	166.20	10.01		100.05	00000	000	,000						

TABLE 1 - SUMMARY OF RESULTS OF GROUNDWATER MONITERING

WELL ID	DATE OF SAMPLING/ MONITORING	CASING ELEVATION (a) (Feet)	DEPTH TO WATER (Feet)	PRODUCT THICKNESS (Feet)	GROUNDWATER ELEVATION (b) (Feet)	TPH-G (ug/L)	B (ug/L)	T (ug/L)	E (ug/L)	X (ug/L)	MTBE (ug/L)	DO (ppm)	LAB
MW-9	02/02/99	166.20	12.33		153.87	75000	530	960	1900	17000	ND<50		3PL
MW-9	05/10/99	166.20	15.67	-	150.53	22000	600	1500	1100	4400	72		SPL
MW-9	08/24/99	166.20	19.10		147.10	85000	850	1300	1700	20000	ND<250		SPL
MW-9	11/03/99	166.20	19.58		146.62	72000	700	780	1900	19000	ND<5.0		PACE
MW-9	03/01/00	166.20	13.19	***	153.01	34000	.78	490	1100	8200	63		PACE
MW-9	04/21/00	166.20	14.29		151.91	55000	260	920	1500	16000	ND<5.0		PACE
MW-9	07/31/00	166.20	15.01		151.19	1200000	1500	6300	15000	120000	1600		PACE
MW-9	11/20/00	166.20	18.23		147.97	320000	3500	19000	5000	40000	3900		PACE
MW-9	02/18/01	166.20	13.14		153.06	32000	290	417	1180	10400	121		PACE
MW-9	06/07/01	166.20	17.41		148.79	96000	421	704	2330	17300	223		PACE
MW-9	09/05/01	166.20	20.56		145.64	39000	445	323	1240	8940	310	***	PACE
MW-9	11/30/01	166.20	17.42		148.78	60000	310	586	1890	14200	285		PACE

TABLE 1 - SUMMARY OF RESULTS OF GROUNDWATER MONITERING

WELL	DATE OF SAMPLING/ MONITORING	CASING ELEVATION (a) (Feet)	DEPTH TO WATER (Feet)	PRODUCT THICKNESS (Feet)	GROUNDWATER ELEVATION (b) (Feet)	TPH-G (ug/L)	B (ug/L)	T (ug/L)	E (ug/L)	X (ug/L)	MTBE (ug/L)	DO (ppm)	LAB
MW-10	03/07/91	167.01	18.09		148.92	1.6	120	190	32	230	***	***	غده خدم
MW-10	06/27/91	167.01		***	***	12000	7300	500	150	300			
MW-10	09/27/91	167.01				57	12000	7200	1400	4600			***
MW-10	12/18/91	167.01				5.3	2500	120	36	79			
MW-10	04/01/91	167.01	13.92	***	153.09	ND	ND	ND	ND	ND ·			
MW-10	07/03/92	167.01	19.92	***	147.09	8600	5100	1300	180	690			ANA
MW-10	10/05/92	167.01	21.92	0.19	145.23			***					
MW-10	01/13/93	167.01	14.43	0.03	152.60		***	***	***				
MW-10	04/23/93	167.01	15.26	0.06	151.80	***							-
MW-10	07/12/93	167.01	19.78	0.45	147.57								
MW-10	10/21/93	167.01	22.90	0.69	144.63	***				***		***	***
MW-10	01/21/94	167.01	20.25	0.06	146.81				***				
MW-10	04/20/94	167.01	20.74		146.27	100000	12000	24000	2400	14000	1577	(d)(i) 1.0	PACE
MW-10	08/01/94	167.01	22.00	0.28	145.22		***				***	***	
MW-10	12/23/94	. 167.01	16.08	0.25	151.12								
MW-10	01/26/95	167.01	13.68	0.80	153.93			***			dy-bands		***
MW-10	06/08/95	167.01	19.08	0.75	148.49						***		***
MW-10	08/22/95	167.01	20.73	0.70	146.81		***						
MW-10	10/27/95	167.01	21.69	0.63	145.79			***			****		***
MW-10	01/25/96	167.01	15.05	0.81	152.57				***	***	***		
MW-10	04/19/96	167.01	16.26	0.58	151.19					***			
MW-10	07/23/96	167.01	20.18	0.62	147.30	***	***						****
MW-10	11/11/96	167.01	21.20	0.20	145.96			***					
MW-10	01/21/97	167.01	13.66	0.14	153.46								
MW-10	04/29/97	167.01	18.71	0.21	148.46							-	wan
MW-10	04/30/97	167.01			***	170000	9700	38000	4700	30500	ND<5000	5.6	SPL
MW-10	08/21/97	167.01	20.19	0.14	146.93	170000	9500	35000	4300	27100	ND<5000	5.3	SPL
MW-10	11/05/97	167.01	20.52	0.02	146.51	80000	3800	12000	2700	15700	ND<500	4.4	SPL
MW-10	02/03/98	167. 01	10.62	0.01	156.40	***						***	***
MW-10	02/04/98	***		***		72000	500	1300	1700	12000	ND<1000	5.1	SPL
MW-10	05/28/98	167.01	15.46		151.55	220000	3200	24000	5200	43000	ND<1000	4.8	SPL
MW-10	12/30/98	167.01	16.65	***	150.36	110000	3500	14000	5800	50000	ND<50		SPL
MW-10	02/02/99	167.01	14.58		152.43	74000	1000	2800	1000	26000	860		SPL
MW-10	05/10/99	167.01	15.72		151.29	81000	2800	2800	3000	17000	220		SPL
MW-10	08/24/99	167.01	19.85		147.16	54000	3500	3800	1500	9100	ND<250	***	SPL
MW-10	11/03/99	167.01	20.00	***	147.01	30000	3000	3500	1200	5000	31		PACE

TABLE 1 - SUMMARY OF RESULTS OF GROUNDWATER MONITERING

WELL ID	DATE OF SAMPLING/ MONITORING	CASING ELEVATION (a) (Feet)	DEPTH TO WATER (Feet)	PRODUCT THICKNESS (Feet)	GROUNDWATER ELEVATION (b) (Feet)	TPH-G (ug/L)	B (ug/L)	T (ug/L)	E (ug/L)	X (ug/L)	MTBE (ug/L)	DO (ppm)	LAB
100/40	03/01/00	167.01	14.62		152.39	62000	320	1200	1100	26000	4400		PACE
MW-10 MW-10	03/01/00	167.01	15.46		151.55	88000	2700	7400	3700	35000	2400		PACE
MW-10 (e		167.01	-		***	***							#
MW-10	11/20/00	167.01	18.74	***	148.27	78000	3800	5500	2800	13000	450		PACE
MW-10	02/18/01	167.01	14.10		152.91	39000	1050	1160	1550	14700	4180		PACE
MW-10	06/07/01	167.01	18.78		148.23	76000	2460	2840	3330	20700	635		PACE
MW-10	09/05/01	167.01	21.40	0.01	145.62	25000	2510	2070	1090	4540	189	***	PACE
MW-10	11/30/01	167.01	18.50		148.51	100000	2480	5720	3890	22800	325		PACE

TABLE 1 - SUMMARY OF RESULTS OF GROUNDWATER MONITERING

WELL ID	DATE OF SAMPLING/ MONITORING	CASING ELEVATION (a) (Feet)	DEPTH TO WATER (Feet)	PRODUCT THICKNESS (Feet)	GROUNDWATER ELEVATION (b) (Feet)	TPH-G (ug/L)	B (ug/L)	T (ug/L)	E (ug/L)	X (ug/L)	MTBE (ug/L)		DO (ppm)	LAB
RW-1	07/09/90	168.01		1.21	***									
RW-1	12/21/90	168.01		0.01	*****		***				***			
RW-1	03/07/91	168.01	17.62	SHEEN	150.39									
RW-1	06/27/91	168.01		0.04	***	***	***	no-	***					
RW-1	09/27/91	168.01		0.02										
RW-1	12/18/91	168.01		0.02	***		,		***	-			***	
RW-1	04/01/91	168.01	14.40	0.11	153.69	***		-		-	-			
RW-1	07/03/92	168.01	20.66	SHEEN	147.35		***		-	-	***			
RW-1	10/05/92	168.01	23.34	0.08	144.73		***							
RW-1	01/13/93	168.01	16.59	0.05	151.46	***							-	
RW-1	04/23/93	168.01	16.17	0.18	151.98									
RW-1	07/12/93	168.01	20.18	0.06	147.88			***		***	***			
RW-1	10/21/93	168.01	25.70	0.56	142.73			***						
RW-1	01/21/94	168.01	21.24	0.40	147.07						***		-	
RW-1	04/20/94	168.01	32.20		135.81		***	****						
RW-1	08/01/94	168.01	21.70	***	146.31	29000	580	950	300	7800	1200	(d)	1.1	PACE
RW-1	12/23/94	168.01	16.02		151.99	1300	25	8.6	1.4	69	616	(i)	1.8	PACE
RW-1	01/26/95	168.01	13.78	****	154.23	ND<50	ND<0.5	ND<0.5	ND<0.5	ND<1				ATI
QC-1 (***				ND<50	ND<0.5	ND<0.5	ND<0.5	ND<1	***			ATI
RW-1	06/08/95	168.01	20.05		147.96	1300	130	ND<1.0	ND<1.0	36				ATI
RW-1	08/22/95	168.01	21.74		146.27	3300	230	13	4.9	280	ND<25	(d)	6.6	ATI
	c) 08/22/95					2800	210	9.3	4.3	250	ND<25	(d)		ATI
RW-1	10/27/95	168.01	32.00	min day-life	136.01	***							***	
RW-1	10/30/95	168.01				230	1.4	ND<1.0	ND<1.0	ND<2.0	650		6.9	ATI
QC-1 (do nó ma	****	240	1.6	ND<1.0	ND<1.0	ND<2.0	630			ATI
RW-1	01/25/96	168.01	15.41		152.60	15000	3400	930	330	2500	5300			CEI
RW-1	04/19/96	168.01	16.83		151.18	35000	5500	3300	1700	9400	14000		7.6	SPL
QC-1 (***	***	33000	5600	3200	1700	8800	15000			SPL
RW-1	07/23/96	168.01	20.76	-	147.25	46000	3600	2300	900	5100	36000		7.4	SPL
QC-1 (400.04			***	47000	3700	2500	930	5300	35000			SPL
RW-1	11/11/96	168.01	21.73		146.28	34000	3000	1200	880	4600	22000		8.3	SPL
QC-1 (****		31000	2900	1000	860	4600	22000			SPL
RW-1	01/21/97	168.01	14.20		153.81	260	40	16	2.7	34	. 1500		6.1	SPL
QC-1 (400.04				270	42	17	2.7	36	1500			SPL
RW-1	04/29/97	168.01	19.15		148.86	32000	3100	590	1300	6000	46000		5.3	SPL
RW-1	08/21/97	168.01	20.67		147.34	7600	730	58	370	1780	9500		4.7	SPL

TABLE 1 - SUMMARY OF RESULTS OF GROUNDWATER MONITERING

WELL ID	DATE OF SAMPLING/ MONITORING	CASING ELEVATION (a) (Feet)	DEPTH TO WATER (Feet)	PRODUCT THICKNESS (Feet)	GROUNDWATER ELEVATION (b) (Feet)	TPH-G (ug/L)	B (ug/L)	T (ug/L)	E (ug/L)	X (ug/L)	MTBE (ug/L)	DO (ppm)	LA B
	44/05/07	168.01	21.01		147.00	39000	2300	86	1300	3840	56000	4.5	SPL
RW-1	11/05/97		10.68		157.33	3400	31	11	29	161	3200	5.1	\$PL
RW-1	02/03/98	168.01	15.55		152.46	2000	90	15	60	305	2700	4.3	\$PL
RW-1	05/28/98	168.01	17.35		150.66							-	1+-
RW-1	12/30/98	168.01	17.55	9,00	153.43	82000	2300	120	2000	3200	51000/78000 (g)		\$PL
RW-1	02/02/99	168.01	16.00		152.01	15000	620	88	340	660	61000	***	\$PL
RW-1	05/10/99	168.01			148.01	52000	1400	170	2200	2900	37000		\$PL
RW-1	08/24/99	168.01	20.00		147.62	17000	2500	86	1500	970	54000		PACE
RW-1	11/03/99	168.01	20.39		155.04	17000	580	78	790	1100	13000		PACE
RW-1	03/01/00	168.01	12.97		151.99	31000	2100	100	1400	1100	39000		PACE
RW-1	04/21/00	168.01	16.02		146.12	47000	1300	170	2700	2300	30000		PACE
RW-1	07/31/00	168.01	21.89		148.86								1+-
RW-1	(h) 11/20/00	168.01	19.15		152.66	14000	589	89	600	712	13000		PACE
RW-1	02/18/01	168.01	15.35		148.92	28000	1140	68.2	504	530	19100		PACE
RW-1	06/07/01	168.01	19.09	0.00	145.97	20000							PACE
RW-1 RW-1	(j) 09/05/01 11/30/01	168.01 168.01	22.06 19.53	0.02	148.48	20000	405	39.4	545	740	8260		PACE

ABBREVIATIONS:

TPH-G Total petroleum hydrocarbons as gasoline

B Benzene T Toluene

E Ethylbenzene

X Total xylenes

MTBE Methyl tert butyl ether
DO Dissolved oxygen
ug/L Micrograms per liter

ppm Parts per million

Not analyzed/available/applicable/measurable
 ND Not detected above reported detection limit

PACE Pace, Inc.
ANA Anametrix, Inc.

ATI Analytical Technologies, Inc.

CEI Ceimic Corporation

SPL Southern Petroleum Laboratories

NOTES:

- (a) Casing elevations surveyed to the nearest 0.01 foot relative to mean sea level.
- (b) Groundwater elevations adjusted assuming a specific gravity of 0.75 for free product.
- (c) Blind duplicate.
- (d) A copy of the documentation for this data is included in Appendix C of Alisto report 10-024-10-001.
- (e) Well inaccessible.
- (f) Travel blank.
- (g) EPA Methods 8020/8260 used.
- (h) Unable to sample.
- (i) A copy of the documentation for this data can be found in Blaine Tech Services report 010607-M-3.
 MTBE data for the January 13, 1993 and April 23, 1993 sampling events has been destroyed.
 No chromatograms could be located for MTBE data from wells MW-5, MW-6, and MW-7, sampled on October 21, 1993.
- (j) Well not sampled due to presence of SPH.
- (k) Could not purge and sample; Waste drum full.

	ALTON GEOSCIENCE, Inc. LOG OF EXPLORATORY BORING FIELD SKETCH OF BORING LOCATION								PROJECT NO. 30-081-01 DATE DRILLED 2-25-91 CLIENT BP Oil Company LOCATION 3201 35th Ave, Oakland LOGGED BY M. Taylor APPROVED BY M. Hopwood
F	FIELD	SKE	TC	OF	BORING LOCATI	ON			Page 1 of 2
	гор с	OF C	ASIN	NG E	LEVATION <u>165.</u>	74'	-		DRILLING METHOD Hollow stem auger HOLE DIAM. 8" SAMPLER TYPE Modified split spoon CASING DATA See well construction details DRILLER Soils Exploration Services, Inc.
E E	,	Σ			CTION IS		uj.		ATER LEVEL
BLOWS PER	FOOT(N)	CGI (PPM)	SAMPLE	DEPT.	WELL CONSTRUCTI OPBORING CLOSURE	536n	PROFILE		ME DESCRIPTION
十				- 0	Christy Box				
7,	13,25 14,11 14,16			- 4 - 6 - 8 - 10 - 12 - 14	2" sch. 40 PVC Casi ng	GM ML		G S	GRAVELLY SILT: green, damp, hard, low plasticity SANDY SILT: greenish brown, damp, very stiff, low plasticity, gravelly SILTY CLAY: brownish green, damp, very stiff, low to medium plasticity, with fine sand
2	2,6,10			- 18 - 20 - 22 - 24		CL		S	Same, becomes moist, stiff, medium plasticity, with medium sand
	5,9,12 3,9,14		H	26 - 28 - 30	sch. 40 PVC 0.020" Slot			포	Same, becomes brown, moist to wet, very stiff, medium plasticity 27'
	o, a, 14			32 - 34				S	Same, becomes brownish green, wet, with medium sand and gravel

			G C)F E		SCIENCE, In LORATORY	ic.		<u>\</u>	PROJECT NO. 30-081-01 DATE DRILLED 2/25/91 CLIENT BP Oil Company LOCATION 3201 35th Ave., Oakland WE	RING NO. SB-8 LL NO. MW-8
	F	IELD	SKI	ETC	H OF	BORING LOCATI	ION			· · · · · · · · · · · · · · · · · · ·	ge 2 of 2
	7	TOP OF CASING ELEVATION 165.74'								DRILLING METHOD Hollow stem auger HOLE DIAM. SAMPLER TYPE Modified split spoon CASING DATA See well construction detail DRILLER Soils Exiplorations Services, Inc.	8"
	Œ				·	WELL CONSTRUCTION OR BORING CLOGURE			W	ATER LEVEL	
	BLOWS PER	Ē	CGI (PPM)	Ä	DEPTH	25 E H		PROFILE	D.	ATE .	
	3	POOT(N)	ᇙ	SAMPLE	8	USA 1986 1986	8	ĝ		ME	
			<u> </u>	S		35 % ₽ ₽ 100=10	┞		<u> </u>	DESCRIPTION	·
	7,1	1,14			- 36 -				s	ILTY CLAY: brown, wet, very stiff, medium to high plasticity, with med and gravel	ium sand
					- 38 -						
	1.	,20,			- 40 -	End Cap]		s	ame, becomes moist to wet, hard, medium plasticity	
					- 42				В	ORING TERMINATED AT 41.5 FEET BELOW GRADE	
					- 44						
					- - 46						
					-						
•					- 48 -						
					- 50 -						
					- 52						
					- - 54						
					- - 56						
					- 1						*
					- 58 -						
					- 60						
						. "					
								,000	-	Comple	
			-					137		Portland Cement Sample Sand #3 Lonestar Driven interval	
										Sand #3 Lonestar	lling
				1							· · · · · ·
											1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1

	LOC BOI	O E	F E	XPI	SCIENCE, In LORATORY				CLIENT BP (30-081-01 Oil Company 1201 35th Ave, Oa M. Taylor AP	akland		BORING NO. SB-9 WELL NO. MW-9 Page 1 of 2
	FIELD	SKE	ICF	IOF	BORING LOCATI	ON .							
										HOD Hollow st		_HOLE DI	M
										E Modified spl			
									CASING DATA	See well cons	truction details	3	
	TOP O	FC	ASIN	IG EI	LEVATION 166.	20	-	l	DRILLER Soi	Is Exploration S	ervices , Inc.		
-							П		A 70000 A 700 A 700			T	
g g	_	₹			S S S S S		╽┈├		ATER LEVEL				
BI OWS PER	FOOT (N)	CGI (PPM)	SAMPLE	Ę	WELL CONSTRUCT ORBORING CLOSURE		PROFILE		NTE				
٥	ò	ોા	ξ	E E	WELL CONST OR BO CLOSIL	836n	Ě.	TI	ME	5.5	l constant		
L		၁	S]			· · · · · · · · · · · · · · · · · · ·	DE	SCRIPTION		
1				-0	Christy Box			6	* Asphalt (street)			· · · · · · · · · · · · · · · · · · ·	
				- 2	•				, topitali jolioog				
	,11,14 1,5,13			- 4 - 6 - 8 - 10 - 12	Sch. 40 PVC Casing	ML			SANDY SILT: redd Same, becomes b		very stiff, low p	lasticity, wit	h gravel
			\vdash	- "				_		•••	t	alee oo oo alissa	- planticity
5	,12,14			- 16				S	SILTY CLAY: brown	n with green strea	ks, moist, very s	sun, meaiun	i piasiicity
				- - 18 - - 20									
	2,6,9			<u> </u>				5	Same, becomes mo	oist to wet, stiff			
				- 22		CL							
				24									
			L	- 24 -	2" sch. 40			5	Same, becomes bro	own, wet to satura	ated, very stiff		
	5,8,10			- 26	PVC				26'		• • • • • • • • • • • • • • • • • • •		
					0.020"			_					
				- 28	Slot	4							
	3,5,10		I	30							fine to medice	oond	
	J,J, 1U		F	32					Same, becomes sa	turated, stiff, with	ine to medium :	oai IU	
				34	End Con								

	LO BO IELD	G C RIN SKE	OF I	=XP H OF	SCIENCE, Ir LORATORY BORING LOCAT	ION		\	PROJECT NO CLIENT _ BP OI LOCATION _ 32 LOGGED BY _ M DRILLING METHO SAMPLER TYPE CASING DATA _ S DRILLER _ Soils 6	BORING NO. SB-9 WELL NO. MW-9 Page 2 of 2			
BLOWS PER	FOOT(N)	CGI (PPM)	SAMPLE	DEPTH	WELL CONSTRUCTION OR BORING CLOGURE	SOSA	PROFILE	D/	ATER LEVEL ATE ME		DESCRIPTION		
6,1	2,17			- 36	88	CL		SI	LTY CLAY: reddish b	rown, satura	ated to wet, very st	iff, medium į	olasticity
				- - 38				В	ORING TERMINATED	AT 36.5 FE	ET BELOW GRADI	=	
				- 40									
				-									
				- 42 -									
				- 44 -									
	-			- 46 -									
				- 48									
				- 50								•	
				- 52									
				- - 54									
				- - 56									
				- - 58									
				- 60							•		
												•	
								_					
							More	-	ortland Cement		Sample		
								•	and #3 Lonestar entonite Pellets	至	Driven interval	المدامة ما المدامة	a drilling
					·			4		-	Water level encor	muerea anuu	y ariung

	LOC BOF	RIN	F E G	EXP	SCIENCE, Ir LORATORY			PROJECT NO. 30-081-01 DATE DRILLED 2-27-91 CLIENT BP Oil Company LOCATION 3201 35th Ave, Oakland LOGGED BY M. Taylor APPROVED BY M. Hopwood MW-16
FI	ELD :	SKE	TCł	HOF	BORING LOCAT	ION		Page 1 c
T	OP OF CASING ELEVATION 167.01'							DRILLING METHOD Hollow stem auger HOLE DIAM. 8" SAMPLER TYPE Modified split spoon CASING DATA See well construction details DRILLER Soils Exploration Services, Inc.
e:)			MOT			WATER LEVEL
BLOWS PER	ξļ	CGI (PPM)	Щ	Æ	WELL CONSTRUCT OR BORING CLOGURE		PROFILE	DATE
3	ROOT(N)	5) (5)	SAMPLE		WIELL CONSTRI OR BORIF	8	Ě	TIME
8	a.	ŏ	Š		<u> </u>	Ľ		DESCRIPTION
				-0	Christy Box	▙		10" Concrete
				-2				
6,1	2,17		- I	- 6 - 8 - 10	2" sch. 40 PVC			SILTY CLAY: tan, damp, very stiff, low plasticity, with gravel
6,1	4,17			- 12 - 14	Casing	CI		Same, becomes tan to brown
7,1	0,14	-		16 18	388 34	- La		Same, becomes brown with green streaks, moist, medium plasticity, with gr
4,	8,13		Ŧ	- 20 - 22				Same, becomes moist to wet, with fine sand and gravel
3,	8,18		Ŧ	- 24 - 26	sch. 40			SANDY CLAY: brownish white, wet to saturated, very stiff, low to medium
1 2	1,19, 5			- 28 - 30 - 32 - 34	Slot	C	L	plasticity, with slight gravel Same, becomes brown, wet, hard, medium plasticity, with slight gravel
!		·•						

	LO BO	G C RIN)F G	EXP	SCIENCE, In LORATORY BORING LOCATI			1	PROJECT NO. 30-081-01 DATE DRILLED 2/27/91 CLIENT BP Oil Company LOCATION 3201 35th Ave., Oakland LOGGED BY M. Taylor APPROVED BY M. Hopwood Page 2 of 2
	FIELD	SKL		1101	BONING LOCATI	ON			
									DRILLING METHOD Hollow stem auger HOLE DIAM. 8" SAMPLER TYPE Modified split spoon
1.									CASING DATA See well construction detail
	TOP C	OF C	ASI	NG E	LEVATION 167	.01'			DRILLER Soils Exiplorations Services, Inc.
	Œ				\$			w	VATER LEVEL
: :	BLOWS PER Foot(N)	PM	ш		WELL CONSTRUCTI ORBORING CLOGURE		H.E		ATE
	BLOWS P FOOT(N)	CGI (PPM)	SAMPLE	뿔	WELL CONSTRU OR BORIN CLOSURE	SOSI	PROFILE	П	IME
		<u> </u>	S				,,,,,		DESCRIPTION
\$1 ¹ 9	7,8,11		Ė	- 36		CL		S	ILTY CLAY: brown, wet, very stiff, medium plasticity, with some fine sand
s tu Line to				- 38				В	ORING TERMINATED AT 36.5 FEET BELOW GRADE
				40					
				- 42	* . *				
				-	,				
:				- 44					
·				- 46					
				- 48					
	·			- 50	·				
				- - 52					
				- - 54					
				-					
- \$4. - 1.				- 56 -					
				- 58				1	
H1 .				- 60					
: 									
									Postland Compet
							7,77		Portland Cement Sample Sand #3 Lonestar Driven interval
									Bentonite Pellets Water level encountered during drilling

: '...

Alameda County Environmental Health

want wal ~ 100' w/sw of

UNDERGROUND FUEL STORAGE TANK LOCAL OVERSIGHT PROGRAM

Ned to find M mother see admind at site

INFORMATION

Ned ust remoral not (181)

Date: ---/---/---

I. AGENCY INFORMATION

ŧ	10.200	CIRC	100	(
,	Need	057	new	wal	tops	(1987))

Agency Name: Alameda County Environmental Health	Address: 1131 Harbor Bay Parkway
City/State/Zip: Alameda, CA 94502	Phone: (510) 567-6700
Responsible Staff Person: Eva Chu	Title: Hazardous Materials Specialist

II. CASE INFORMATION

Site Facility Name: BP 01)	Facily 11132	
Site Facility Address: 320 \	35th Aue Oak CA 9461	9
RB LUSTIS Case No.:	Local Case No.:	LOP Case No.: RO ·OI
URF Filing Date:	SWEEPS No.:	APN:
Responsible Parties	Addresses	Phone Number
Scott Hooten BP Oil	295 SW413F St Bldg 13 Renton WA 98055 - 4931	sten (425) 251-0667
•		

Tank I.D. No	Size in Gallons	Contents	Closed In Place/Removed?	Date
(61 187
2				• \
3				e 4
,				
	Piping			

III. RELEASE AND SITE CHARACTERIZATION INFORMATION

Cause and Type of Release:	 		
Tank 1			
Tank 2			
Tank 3			

Site characterization complete? Yes Date Approved By Oversight Agency:

	Soil (ppm)		Water (ppb)
Contaminant	Before ¹	After ²	Before ³	After ⁴
TPH (Gas)				
TPH (Diesel)				
Oil & Grease				
Benzene				
Toluene				
Ethyl Benzene				
Xylenes				
MtBE				
Metals				
Other)				

Site History and Description of Corrective Actions:

The site is consortly an operating 3P 6:1 Service Jetem w/ 3-tok USTS in the withes?

(moballed in 1987; with ringh MM-3) were notated as the site. Dissolved pHC west the start permised the left generation USTS (Size) were removed in Jine 1987; soil singles in possible to Use the generation USTS (Size) were removed in Jine 1987; soil singles in possible to Use the territory and (MM-1 through MM-10) and are recovery well (RM-1) house even installed on and off-site to delineate the vertical 4 lateral extent of the continuant plane. FP has been detrived in MM-1 as MM-2 in Pay 1992 an interior was explanation explanation by the short of the continuant plane. FP has been detrived in MM-2 and MM-2.

Sympte Asse hydrocarbone was explanation explanation was installed. 6W 4

Sympte Asse hydrocarbone was explanated from RM-1 and treated by 2-2,000:160 activated carbon vessels. The treated water was door him which in sametry sever 8 yetem. GW extraction terminated in NM 25,992

He are present in soils in the sixually of the UST complex at a depth introd from 13 to 27 feet bys. (In the vicinity of bull m. 8, adsorbed Hessure present only or depth interval from 13 to 17 feet bys.)

An aquifir pump test was proposed on spil 1991. The average transmissionly of the aquifor herocultithe site was calculate to be 6.392 ft 2/min. The average hydraulic conductivity was determed to be 6.016 ft/min. Soil types exempted generally consisted of pulty day.

Flip still newsored on Mo-1, Mw-8, Mw-10

Monitoring wells installe	d? Yes No		Number:		
Proper Screened interval	? Yes				
Well No.	Screen Interval (depth in feet)	Highest C	-	Lowest GW Depth	Comment
			(Mo/Yr t	o Mo/Yr	
MW-1		<u> </u>			2"
MW-2					2"
MW-3					2''
nu-4 aunog					41'
m-5- m-0					2"
					TE.
RW-1					6"
Flow Direction south at ~ . 003 A/A but plane and suggest 6w flows more SW					
Most Sensitive Current U		1			
Are drinking water wells	affected?	Aquifer l	Name:		
Is Surface water affected		Nearest a	ffected SW n	ame water, ~500 f	eet without the inte
Off-site beneficial use in	pacts (addresses/location	ıs):			
Summary of production	wells in vicinity Then	eare n	trom r	noncepular prove	te water WEED
	W	Im a 1/2	mile rad	lus of the ster.	

Reports on file?	Where are reports?	
Alameda County Environmental He	alth	
1131 Harbor Bay Parkway		
Alameda, CA 94502		

TREATMENT AND DISPOSAL OF AFFECTED MATERIAL					
Material	Amount (Include Units)	Action (Treatment or Disposal w/Destination)	Date		
Tank					
Piping					
Free Product					
Soil					
Groundwater					

IV. CLOSURE

Does completed corrective action protect existing beneficial uses per the Regional Board Basin Plan? Yes No						
Does completed corrective action protect potential beneficial uses per the Regional Board Basin Plan? Yes No						
Does corrective action protect public health for current land use? Alameda County Environmental Health staff does not make specific determinations concerning public health risk. However, it does not appear that the release would present a risk to human health.						
Site Management Requirements:	Site Management Requirements:					
Should corrective action be reviewed if land use chang	Should corrective action be reviewed if land use changes? Yes No					
Monitoring Wells Decommissioned: Yes No Number Decommissioned: Number Retained:						
List Enforcement Actions Taken:						
List Enforcement Actions Rescinded:						

V. ADDITIONAL COMMENTS, DATA, ETC.

Considerations and/or Variances:	
Conclusion:	

VI. LOCAL AGENCY REPRESENTATIVE DATA

Prepared by: Eva Chu	Title: Hazardous Materials Specialist
Signature:	Date:
Reviewed by:	Title: Hazardous Materials Specialist
Signature:	Date:
Approved by: Donna L. Drogos, P.E.	Title: Supervising Hazardous Materials Specialist
Signature:	Date:

This closure approval is based upon the available information and with the provision that the information provided to this agency was accurate and representative of site conditions.

10/6/03 cont 10/6/03 cont 10/10/03 2, wellswey

BP, 3201 - 357h Ove 3/20/03 1903 MW-1 his FR/hi his hi tphy 1 B & his lo/ND his lo/MD N-5 Anig A Ro Cast Q 7,300 mg/l Tophy 1,400 mg/l B his mostly lo MW-6 not sampled since 98 no FP pe+98 MD MW. Z not sampled since 58, NPP pre - 1 98 MD MW-8 his hi Mw-9 his hi/FP

				en en de la company.
				en tradición de la companya de la c La companya de la co
M	EQ/ p'			
MW-10 Ri	, the		· · · · · · · · · · · · · · · · · · ·	
2	+ 0 (0 '		
RW-1	no FT/	n e	<u>_</u>	
and the second s				
			According to the second	
			, et	
	· .		·	
				,
			1875 1887 - 1887 - 1887	ng ngangang sa
				/ -
		y et en en en en en en en		

BP, 3201-35th ave 1/30/03 9/9/83,9/5/93 PPRS no descipto (0/25/24 that says diagnost specific 2/5/03 10/28/02 WP MW 11,12 proposed Tog got a tolocate wells 2/14/03 2000 9/9/02 los 3 100pach 2/28/03 7 mby MW 67 notsampled

1/30/03 flow din 9/11/02 5W. 6/20/22 SW 2/20/02 11/30/01 S, SE 9/5/01 SW 6/7/01 Sw 2/18/01 2F 11/20/00 541 7/31/00 Sw 4/21/00 SE 3/1/60 11/3/99 SE 8/24/99 54 712/99 MW 2/2/99 SE 12/30/98 SE 5/2898 213/98 W 11/5/97 5W 8/21/97 SE 4/29-70197 SE 1/21/97 SE 11/11/96 7/23/96 ら足 4/19/96 1/25/96

BP, 3201 35th At

1/30/03 Ront

10/27/95 AW

8/22/95 N

6/8/95 SW

1/28/95 SE

8/1/94 S

4/20/94 S

3P 3201-38 and and 1/29/03 7 trans 352 ft/m 9/Wor Pamples free prod MW-1, RW-1

also his

RW I is dryad fr MW-1, T'r hishi-MWZ his lo-MW-3,4 MW-5 Anccently to 4200 Tophs uda grad of REVI, Ta MW-6, This ND zuoz grad + away fr Tis MW81 + hi dagad of RW1 MW9 1, his his day and of The

1/29/03 cont MW10 his hi RWI his his du pad Tat disp 5/25/90 TW/s Twing Waising but descripty now by logo howing I have MWI-3 7/5/03 8/27/91 Mw 8,9,10 7 pumping text 7 sens recepsionery

Ms. Eva Chu October 28, 2002 Page 2

(ppb) as measured in MW-1 in January 2000. TPH-g concentration reported during the latest sampling event of this well in February 2002 noted the levels to decrease to 52,000 ppb. Benzene, toluene, ethylbenzene and xylenes (BTEX compounds) and MTBE have also been reported in the groundwater. Benzene was reported at a maximum concentration of 19,000 ppb in a groundwater sample collected from MW-1 in February 1998 but was noted to attenuate to 465 ppb during the February 2002 sampling event. MTBE was reported at a maximum concentration of 61,000 ppb from the sample collected from RW-1 during the February 1999 monitoring event. The concentration of MTBE was noted to decrease to 7,240 ppb in a sample collected from RW-1 during the February 2002 monitoring event. These decreases indicate that natural attenuation is occurring in the shallow groundwater of the subject property and surrounding area.

The down gradient extent of dissolved phase hydrocarbons have been monitored through the sampling of the down gradient wells MW-5 and MW-8. During the September 2002 sampling event, TPH-g, benzene and MTBE were reported in a groundwater collected from MW-8 located approximately 80 feet down gradient of the subject property at 190,000 ppb, 1,500 ppb and 1,200 ppb, respectively. Considerable lower concentrations were reported in the groundwater sample collected from MW-5 located approximately 100 feet further down (and slightly cross gradient) with respect to MW-8. During the February 2002 sampling event, a groundwater sample collected from MW-5 was reported to contain TPH-g, benzene and MTBE at 4,200 ppb, 940 and 55.6 ppb, respectively. This decrease in concentrations indicates that the amount of dissolved phase hydrocarbons is naturally attenuating through advection and dispersion and also likely by chemical and biological degradation as it migrates in the down gradient direction.

A sensitive receptor survey was completed in 1991 by Alton Geosciences. The survey revealed that the nearest residence is 50 feet from the subject property, the nearest hospital was 11,000 feet, and the nearest school was 11,000 feet from the subject property.

A groundwater remediation system was activated on the property in 1992 and operated intermittently through the 1990s. The treated groundwater was discharged into the sanitary sewer system under permit from the East Bay Municipal Utility District (EBMUD).

PROPOSED SCOPE OF WORK

The proposed scope of work responds to the ACHCS request for a work plan to further characterize the nature, extent and associated risks with hydrocarbon contamination. The scope of work includes:

- Completion of a Conduit Study;
- Contaminant Plume Definition;
- Contaminant Source Characterization;
- Groundwater Contaminant Plume Monitoring; and
- Corrective Action Plan.

Ms. Eva Chu October 28, 2002 Page 3

Conduit Study

URS proposes to complete a conduit study to identify potential migration pathways and conduits to assess the probability of the plume encountering preferential pathways and conduits that may promote the migration of petroleum hydrocarbons. A map showing location and depth of utility lines, trenches, sewers, storm drains, wells, creeks and underground water channels will be prepared at the conclusion of this study.

The data from the conduit study and data from previous investigations at the site and surrounding area will be used to develop the initial conceptual site model (CSM) for the site which will be used to assess future sampling points for the soil and groundwater sampling portions of this workplan.

Contaminant Plume Definition

The purpose of the assessing the contaminant plume is to develop a three-dimensional model of the nature and extent of the remaining petroleum hydrocarbons in the soil and groundwater. The initial task will be the installation of two new groundwater monitoring wells near the down gradient extent of the known hydrocarbon plume. As shown on Figure 1, MW-11 is proposed to be located approximately 100 feet west and down gradient of MW-8.

As presented in Attachment B, standard well drilling, installation, develop and sampling procedures will be followed. However, as requested by he ACHCS, the well selection of the well screened interval will be carefully determined to allow specific groundwater zones to be monitored. In order to assess the proper screened interval, the borings for the wells will be continuous cored. At the conclusion of well installation activities, the new wells will be surveyed in by a State Licensed Surveying following State Tank Geotracker lateral and vertical reporting requirements.

A State Certified Laboratory will analyze the groundwater samples for TPH-g, BTEX and MTBE using EPA Method 8021. In addition, ether oxygenates, ethanol, EDB and 1,2-DCA using EPA Method 8260 will be included in the initial two rounds of groundwater sampling.

The groundwater sampling program and CSM model will be refined based on on-site measurements and observations, and the results of recent monitoring events. The proposed scope of work will remain flexible so that the field manager can adjust the location, quantity, depth and type of samples based on the developing conceptual model to expedite data collection.

Contaminant Source Characterization

The purpose of the contaminant source characterization is to assess the nature and extent of separate and dissolved phase hydrocarbons in the soil and groundwater in the vicinity of the former and current USTs. The initial step in the task is to incorporate all existing soil data into the CSM to assess locations and depths of soil and groundwater sampling points. Once the data is plotted and evaluated, soil and groundwater samples will be collected by continuous coring direct-push drilling methods. The US EPA protocol "Expedited Site Assessment Tools for Underground Storage Tanks Sites: A Guide for Regulator" (EPA 510-B-97-001) dated March 1997 will be evaluated to provide a cost-effective approach to assess the nature and extent of the remaining petroleum hydrocarbons in the soil and groundwater.

Ms. Eva Chu October 28, 2002 Page 4

Groundwater Contaminant Plume Monitoring

The purpose of the groundwater monitoring is to assess the nature and extent over time of the remaining petroleum hydrocarbons in groundwater of the subject property and surrounding area. In order to achieve this objective, groundwater monitoring for all wells will continue on the current schedule except for change in the sampling schedule for MW-5 from annual to quarterly as requested by Ms. Chu on October 28, 2002. In addition, as previously noted, two proposed wells, MW-11 and MW-12 will be added to the monitoring program and be sampled on a quarterly basis.

As quarterly groundwater data is evaluated, the CSM will be updated on regular basis and will include cross-sections, structural contours and concentration isopachs maps.



The purpose for the Corrective Action Plan (CAP) is to evaluate data obtained during investigative activities to propose a cost-effective final cleanup objective for the remaining petroleum hydrocarbons in the soil and groundwater. The CAP will also select a final remedial alternative for soil and groundwater that will adequately address human health and safety, the environment, eliminate nuisance conditions, and protect water resources. The CAP will evaluate at least two technically and economically feasible methods to restore and protect the beneficial uses of water and to meet the cleanup objectives for each contaminant established in the CAP. The CAP will also propose verification monitoring to confirm completion of the correction actions and evaluate the CAP implementation effectiveness.

To identify and manage potential health and environmental risks, address impacts to water resources, and manage nuisance conditions, URS proposes to utilize the Oakland Risk-Based Correction Action (RBCA) approach in the decision-making process following the "Oakland Urban Land Redevelopment Program: Guidance Document, January 1, 2002".

SCHEDULE AND PROJECT MANAGEMENT

The schedule for the above noted work is as follows:

- Soil and Water Investigation Report 110 days after the approval of this workplan;
- <u>Soil and Water Investigation Completion Report</u> 180 days after the completion of the Soil and Water Investigation Report; and
- <u>Corrective Action Plan</u> 90 days after the completion of the Soil and Water Investigation Completion Report.

In addition, quarterly groundwater monitoring reports will be completed within 30 days of the end of each quarter.

The Project Manager for this proposed work will be Mr. Robert M. Horwath, A State Registered Geologist. Mr. Horwath will oversee all technical aspects of this work and act as liaison between ACHCS

Condut Strang) develop CSM · conduct Expedded Site Assessment (arthurst Place Rebutin) Mw sudallation Sho 4039

av/mpres@aol.com

ALAMEDA COUNTY **HEALTH CARE SERVICES**

RO000014

AGENCY

DAVID J. KEARS, Agency Director



ENVIRONMENTAL HEALTH SERVICES

ENVIRONMENTAL PROTECTION 1131 Harbor Bay Parkway, Suite 250 Alameda, CA 94502-6577 (510) 567-6700

FAX (510) 337-9335

September 9, 2002

Mr. Scott Hooton BP Oil 295 SW 41st Street, Bldg 13, Suite N Renton, CA 98055-4931

Mr. Dave DeWitt Tosco Marketing Co 2000 Crow Canyon Pl, Ste 400 San Ramon, CA 95118-3686

SWI and CAP for BP Station #11132 at 3201 35th Ave, Oakland, CA RE:

Dear Messrs. Hooton and DeWitt:

I have completed review of the fuel leak case file for the above referenced site. Up to 1,700,000 ppb TPHg, 19,000 ppb benzene and 56,000 ppb MTBE has been detected in groundwater. Separate phase hydrocarbon has been noted in wells RW-1 and MW-1 since July 1990. This letter presents a request for full three-dimensional definition, investigation, and a proposal for cleanup of soil and groundwater contamination from the unauthorized release at the site. You are hereby required to complete a Soil and Water investigation and prepare a Corrective Action Plan (CAP) for the subject site in accordance with California Code of Regulations, Title 23, Division 3, Chapter 16, Article11, "Corrective Action Requirements; State Water Resources Control Board Resolution 92-49, "Policies and Procedure for Investigation, Cleanup and Abatement of Discharges Under Water Code Section 13304"; and with the Regional Water Quality Control Board Water Quality Control Plan for the basin.

The following technical comments address investigation and cleanup performance objectives that shall be considered as part of the required Soil and Water Investigation and CAP. A workplan for the Soil and Water Investigation is due by October 28, 2002 that addresses each of the following technical comments.

TECHNICAL COMMENTS 1. Conduit Study Longwill Report

The purpose of the conduit study is to locate potential migration pathways and potential conduits and determine the probability of the plume encountering preferential pathways and conduits that could spread the contamination. Please provide a map showing the location and depth of all utility lines and trenches (including sewers and storm drains), wells (water supply, irrigation, monitoring, abandoned and improperly-destroyed), and creeks (former and present) or underground water channels.

Using the results of the conduit study and data from previous investigations at the site, you are to develop the initial three-dimensional conceptual model of site conditions. You are to use this initial conceptual model to determine the appropriate configuration for samplings points in the SWI phase of work at this site. Discuss your analysis and interpretation of the results of the conduit study and explain your rationale for the configuration of sampling points in the SWI work plan requested below.

2. Contaminant Plume Definition 9ω

The purpose of contaminant plume definition is to determine the three-dimensional extent of contamination in soil and groundwater. The plume extent at the site is undefined. In July 2002, up to 86,000 ppb TPHg, 7,310 ppb benzene and 2,520 ppb MTBE was detected in groundwater. Free phase product is currently present at the site.

MTBE is more mobile in soil and groundwater than the typical petroleum hydrocarbon compounds, is highly soluble in groundwater, and is not readily biodegradable. MTBE plumes can be long, narrow, and erratic. Because of these characteristics, conventional investigation techniques and monitoring well networks currently used at fuel leak sites are generally insufficient to adequately characterize MTBE contamination. Therefore, it is recommended that you propose an investigation that will include depth discrete soil and groundwater sampling. Soil and groundwater samples should be collected at 5 feet intervals, areas of obvious contamination, the soil/groundwater interface, and at each unit of lithology change. It is recommended that your investigation incorporate expedited site assessment techniques and borings installed along transects to define and quantify the full three-dimensional extent of MTBE. The borings should be continuously cored. Detailed cross sections, fence diagrams, structural contours, isopachs, and rose diagrams for groundwater should be subsequently incorporated in the SWI completion report. Discuss your proposal for performing this work in the SWI work plan requested below.

Expedited site assessment tools and methods are a scientifically valid and cost-effective approach to fully define the three-dimensional extent of the plume. Technical protocol for expedited site assessments are provide in the US EPA "Expedited Site Assessment Tools for Underground Storage Tank Sites: A guide for Regulators" (EPA 510-B-97-001), dated March 1997.

3. Contaminant Source Characterization

Sw 1

The purpose of contaminant source characterization is to determine the nature and extent of free product (liquid phase), petroleum saturate soils (residual phase), hydrocarbons dissolved in groundwater (aqueous phase), and high concentrations of soil vapor (vapor phase) that will continue to increase the concentration and mass of the dissolved phase contaminant plume.

It is requested that source area characterization be initiated at the start of the Soil and Water Investigation phase of work. Source area characterization and contaminant mass estimations are needed to determine the necessity and aggressiveness of interim source cleanup and/or dissolved phase mass removal. Report the results of your work in the Soil and Water Investigation Report requested below.

4. Groundwater Contaminant Plume Monitoring

Sw I camplotion Report

The purpose of groundwater monitoring is to determine the three-dimensional movement of the plume, the rate of plume growth, and the effectiveness of cleanup activities.

Once the extent of the plume is defined, we request that you install permanent monitoring wells to monitor the three-dimensional movement of the plume. Multi-depth discrete wells may be required. We request that you use the detailed cross section, structural contours, isopachs, and rose diagrams for groundwater gradient developed during Task 2 above, to determine the appropriate locations and designs for monitoring

wells that are necessary to appropriately monitor the movement of the plume. Please submit your proposal for the installation of monitoring wells in the Soil and Water Investigation Report and report on the installation of the wells in the Soil and Water Investigation Completion Report.

Quarterly groundwater monitoring should continue at the site. Analysis for ether oxygenates, ethanol, EDB and 1,2-DCA (using EPA Method 8260) should be included for the next two quarters, at a minimum.

5. Corrective Action Plan

The purpose of the CAP is to use the information obtained during investigation activities to propose cost-effective **final cleanup objective for the entire contaminant plume and remedial alternative for soil and groundwater** that will adequately protect human health and safety, the environment, eliminate nuisance conditions, and protect water resources.

A CAP for the final cleanup of contamination in soil and groundwater caused by an unauthorized release at the site will be requested upon completion of the Soil and Water Investigation in accordance with the schedule specified below. The CAP shall address at least two technically and economically feasible methods to restore and protect beneficial uses of water and to meet the cleanup objectives for each contaminant established in the CAP. The CAP must propose verification monitoring to confirm completion of corrective actions and evaluate CAP implementation effectiveness.

TECHINCAL REPORT REQUEST

Please submit technical reports according to the following schedule:

October 28, 2002 – Work plan for Soil and Water Investigation

110 Days from Work Plan Approval – Soil and Water Investigation (Results of Expedited Site Assessment) Report

180 Days from Submittal of Soil and Water Investigation Report — Soil and Water Investigation Completion Report

90 Days after Submittal of Soil and Water Investigation Completion Report - Corrective Action Plan

October 30, 2002 – Quarterly Report for the Third Quarter 2002

January 30, 2003 – Quarterly Report for the Fourth Quarter 2002

April 30, 2003 – Quarterly Report for the First Quarter 2003

These reports are being requested pursuant to the Regional Board's authority under Section 13267 of the California Water Code. Each report shall include conclusions and recommendations for the next phases of work required at the site. It is requested that all required work be performed in a prompt and timely manner. I have proposed a schedule for the submittal of the Soil and Water Investigation Report and the CAP. Revisions to the proposed schedule shall be requested in writing with appropriate justification for anticipated delays.

If you have any questions, I can be reached at (510) 567-6762.

Sincerely,

eva chu Hazardous Materials Specialist




Table 1. Summary of Ground-Water Monitoring Data: Relative Water Elevations and Laboratory Analyses

		тос	Depth to	Product	Water Level			Concentra	tions in (p	g/L)					
75171		Elevation	Water	Thickness	Elevation	GRO/			Ethyl-	Total		(mg/L)			
Well and Sample Date	P/NP	(feet msl)	(feet bgs)	(feet)	(feet msl)	TPHg	Benzene	Toluenc	Benzene	Xylenes	MTBE	DO	Lab	PH	Comments
•				100											
MW-1		1 SOUK	CE 1.	KED	uwaranna di iliang	JERUSANIANI (MIL	anuasana								
7/9/1990		169.75		022											
12/21/1990		169.75	**	0.58		 Deningauss									
3/7/1991		169,75	20.59	0	149.16						_				Terring the state of the state
4/1/1991		169.75	16.51	0.15	153.24										
6/27/1991		169.75		0:18											Figure Control of the section of the
9/27/1991		169.75	 	0.27		1									
[2/18/1991		169.75		028	147.45						-				
7/3/1992		169.75	22.30	0.27	45.77										
10/5/1992.		169.75	23.98		152.72				-	_	-		-		
1/13/1993		169.75	17.03	0.24	151.65										
4/23/1993		169.75	1810 22.02	0.49	147.73						and again a man, a pair 1 July 1 ye bank a co	-	-	_	
7/12/1993		169.75 169.75	25.12	0.77	144.63										
0/21/1993		169.75	23.02	0.76	146.73			-							- anglestaurreummentummentumentum
1/21/1994		169:75	24.54		16521										
4/20/1994 8/1/1994		169.75	24.11	0,35	145.64	 emminiciane	ar facultinimeter		-		_			n manndif	
12/23/1994		169.75	18 10		151.56										
1/26/1995		169.75	16.25	1.1	153.50	_		-	-		**			— S168444	
67871995			22,92		146.83										
8/22/1995		169.75	24.45	0.85	145.30	-			_			-	_	erenas	
[Q/27/1995		169.75	25/4		14434										
1/25/1996		169.75	18.20	-	151.55	-			 re ::::::::::::::::::::::::::::::::::::			 Ting (T2110617)			
4/19/1996		169.75	19.06	122	150.69										
7/23/1996	al igninana	169.75	22.98	0.89	146.77			 		. <u>-</u>		-			
[1]/[1]/1996		169,75	23.99	0.89	145,76										
1/21/1997	-	169.75	16,80	0.9	152.95			 mu ====================================	-			- 1			
4/29/1997		169:75	2190	0.85	147.85					22 000					c c
4/30/1997	-	169.75		_		92,000	and montenance	8,100	4,400 4,000	23,800 21,300		52	/ TO 100 100 100 100 100 100 100 100 100 10		
4/30/1997		169.75				100,00	gardar selleradan	8,000	4,000 3,800	19,600	Vir autolia intermediani				c
8/21/1997	###	169.75				120,00	and properties	8,100		22,100		53			
8/21/1997		169.75	23,40		14635	140,00	0 3,000	8.500					politika (h.		COCK TO STATE OR CONTRACT STATES OF THE STAT
the combiners of the president of the second	,														Page 1 nF 27

Table 1. Summary of Ground-Water Monitoring Data: Relative Water Elevations and Laboratory Analyses
Station #11132, 3201 35th Ave, Oakland, CA

<u> </u>		тос	Depth to	Product	Water Level			Concentra	tions in (µ	g/L)					
****		Elevation	Water	Thickness	Elevation	GRO/			Ethyl-	Total		(mg/L)			
Well and Sample Date	P/NP	(feet msl)	(feet bgs)	(feet)	(feet msl)	TPHg	Benzene	Toluene	Benzene	Xylenes	MTBE	DO	Lab	pH	Comments
MW-1 Cont.															100000000000000000000000000000000000000
		169.75				88,000	7,300	4,800	3,600	16,900	8,200				
175/1997		169.75	23.70		146,05	68,000	6,200	4,400	3,300	14,300	8,000	4.7			100 mm
11/5/1997		169.75	13.63	0.32	156.12										
2/3/1998		169.75				160,000	2,300	8,400	5,000	29,400	<10000				C
2/4/1998 2/4/1998		169.75				190,000	2200	10,000	5,600	32,000	<10000	53			
5/28/1998		169.75	18.03	0.17	151.72	87,000	980	3,900	3,600	19,000	2,900	3.8	_	**	
12/30/1998		169,75	19.50	0.08	150:25	70,000	590	3,200	2,900	16,000	3,600				
2/2/1999		169.75	18.93	0.03	150.82	79,000	480	3,100	3,500	21,000	3,500		 L (2) 177 177 177 177 177 177 177 177 177 17		
5/10/1999		169,75	1828	.0.03	151.47	110,000	160	1,900	3,700	24,000	3,000				
8/24/1999		169.75	20.13	0.06	149.62	110,000	850	1,300	1,900	19,000	<50	-	 e namentation		
11/3/1999		169 75	27.27	036	147.4B	65,000	6300	1,100	3/300	9,500	8,900				
3/1/2000		169.75	14,79	0.23	154.96		_			-		 		 11:51:18:00	b b
4/21/2000		169.75	18:10	. EE0	151.65	61,000	A Caluta Daniel	780	2700	17,000	15300				
7/3 1/2000		169.75	21.60	0.53	148.15	1,500,00	#12 ST CREEZ PROPERTY \$23	2,100	24,000	120,000	2,700 3,900	-			
11/20/2000		169:75	2 69	0.37	148.06	1,700,00	1.800	2300	19,000	99,000					
2/18/2001		169.75	16.70	0.13	153.05		-		4210	15.000	1,890				
2/26/2001		169.75	14.38	0.15	15537	100.000	iii bibirtire inii	466	3.870	12,200	2,720				
6/7/2001		169.75	20.78	0	148.97	70,000	705	440	3,870						
9/5/2001		169.75	23.16	0.35	46.39									A 47 P. P. P.	k
11/30/2001	-	169.75	20.85	0.41	148.90	e soughest	3,500		2,150	4300	5,400				
12/6/2001		169.75	18.72	027	151700	39,000 52,000		271	1,600	11,400	106		 	## #### OF	CHARLES FOR CHARLES AND A CONTRACTOR OF CONT
2/20/2002		169.75	17.43	0.15	152.32 148.57	*** ****** ************	405			1					
6/20/2002		169.75	21.18	0.54	146.89					######################################	######################################	-			j
9/11/2002		169.75	22.86	0.4	140.07										
11/12/2002		169 75	22,65 18,15	0.3	151.60					-	-				j,n
1/29/2003	 orbanomen	169.75	18.49	0.3	15126										
5/22/2003		169,75	21.44	0.35	148.31			######################################			-	-		_	0
6/24/2003		169.75		0.35	[47.03										
7/28/2003		169.75 169.75	22.64	0.23	147.11							_		-	O STATE OF THE PROPERTY OF THE
8/12/2003		169.75	22.04	0.24	149.05										0
9/12/2003					Sid accidentable nerrites:		en protestation	egrau g (g an t ermagnetablik	***************************************	ACA : 4:343544 :					n n 137

Table 1. Summary of Ground-Water Monitoring Data: Relative Water Elevations and Laboratory Analyses
Station #11132, 3201 35th Ave, Oakland, CA

		тос	Depth to	Product											
Well and		Elevation	Water	Thickness	Elevation	GRO/			Ethyl-	Total		(mg/L)			
Sample Date	P/NP	(feet msl)	(feet bgs)	(feet)	(feet msl)	TPHg	Benzene	Toluene	Benzene	Xylenes	MTBE	DO	Lab	рH	Comments
MW-1 Cont.															
	n			STOCKER STATES				annadaili Tarangalii							
11/18/2003	NP.	169,75	21.70		148.05										
02/23/2004	NP	169.75	16.34	 	153.41										
05/04/2004	NP	[69:75	21,28		14847										
08/04/2004		169.75	22.54		147.21	***************************************			 :::::::::::::::::::::::::::::::::::						
09/22/2004	NP	169.75	22.76		146.99										
11/10/2004		169.75	20.19		149.56										
01/13/2005		169.75	1458	0.03	155.17										
02/15/2005		169.75	16.13	0.04	153.62			 					 		
03/07/2005		169.75	1331	0.01	156.44										
05/16/2005		169.75	15.74	-	154.01			-			-				j sependeromanskommonististis
08/17/2005		169,75	21,15		148.60										
11/18/2005		169.75	20.15	_	149.60								-	 0.53703080	j
02/07/2006		169.75	15.19		154.56									6.9	ting titter til så er forder startet for er for til
5/19/2006	P	169.75	17.42		152.33	44,000	73	510	3,300	5,300	86 ************************************	- 10023	SEQM		u, t
8/23/2006		169,75	22.01	0.14	47.85									(- 1109991 (F-15)	b, j
11/15/2006	200000000000000000000000000000000000000	169.75	21.98	0.18	147.91	<u> </u>			-		_	 -	<u> </u>	 	6,1
MW-2		SW EI	DGE	OF 5	ITE "	DG	OF	150	JRCG	3	and the state of t				
7/9/1990		168.14													
12/21/1990		168.14				-	-	-			and the same of th		-		
3/7/1991		168 14	19.18		148,96										
######################################		168.14	15,21		152.93	-		-					 h (2) (1) (1) (1) (1)	-	
6/27/1991		168:147													
9/27/1991		168.14			— — — — — — — — — — — — — — — — — — —	N HALL CONTINUES		-						TO CHOCOL	e valorostanomentoriales
12/18/1991		168.14													
7/3/1992		168.14	20.93	angananggananan 	147.21	**************************************	571 3431431441 1 Marie 14 14 14							-	
(0/5/1992		1	22.74		145.40										
1/13/1993		168.14	15.55		152.59			-	_				-	121 01201200	and and an angle of the second and t
4/23/1993		168 14	16.54		151.60										
7/12/1993		168.14	20.46		147.68	(1) (1) (1) (1) (1) (1) (1) (1) (1) (1)			-		ne	***	 		
10/21/1993		168.14	24.91		143 23										

Table 1. Summary of Ground-Water Monitoring Data: Relative Water Elevations and Laboratory Analyses
Station #11132, 3201 35th Ave, Oakland, CA

		тос	Depth to	Product	Water Level			Concentra	tions in (µ	g/L)					
Well and		Elevation	Water	Thickness	Elevation	GRO/			Ethyl-	Total		(mg/L)			
Sample Date	P/NP	(feet msl)	(feet bgs)	(feet)	(feet msl)	TPHg	Benzene	Toluene	Benzene	Xylenes	MTBE	DO	Lab	рH	Comments
MW-2 Cont.								·							
1/21/1994		168.14	21 20		14694										
4/20/1994		168.14	22.44		145.70	1,800	140	370	54	290	24	1.7		-	i
8/1/1994		168 14	72.24		14590										
12/23/1994		168.14	16.25	**	151.89		-					-	••	-	n an regers tables and respect to the control of th
1/26/1995		168.14	1455		153,59										
6/8/1995	-	168.14	21.18		146.96				**	en					
8/22/1995		168.14	22,76		145.38										
10/27/1995	-	168.14	23.61	-	144.53						••				COMMONOS OF STREET
1/25/1996		168,14	1505		157 19										
4/19/1996		168.14	17.33		150.81			-	 3016391851622	 Harry institut	 Borrenoumestuscus				
7/23/1996		168.14	21,75		L46.89										
11/11/1996		168.14	22.27		145.87		— ::::::::::::::::::::::::::::::::::::		- 	-	 				
1/21/1997		168.14	15.19		152.95				in and the second						
4/29/1997	-	168.14	20.22		147.92	-		15,000	 6,000	37,000	- 				
4/30/1997		168.14			146.40	130,000	4,600 6,000	16,000	4,700	28,000	<500	4.6			
8/21/1997	 	168.14 168.14	21.74 21.61		146.40	110,000	7.800	18,000	4,900	28,100	<2500	48			
11/5/1997		168.14	11.51		156.63	75,000	590	1,500	1,800	12,800	<2500	4.5			
2/3/1998 5/28/1998		168.14	1651		151.63	79,000	3,900	3:100	3,100	18,000	900	Lab			
12/30/1998		168.14	17.70		150.44	95,000	4,700	3,500	3,700	21,000	<250		-		
2/2/1999		168.14	15.46		152.68	170,000	3,500	1,500	5,200	34,000	<500				
5/10/1999		168.14	16.52	<u> </u>	151.62	84,000	3,200	3,200	3,700	20,000	75	-			
8/24/1999		168.14	20.73		147,41	130,000	9.100	9,200	4,700	27,000	\$250				
11/3/1999		168.14	20.93		147.21	120,000	10,000	21,000	4,700	30,200	2,200	••		_	
3/1/2000	lauua	168.14	1337		154,77	39,000	1,400	500	1700	8,100	44				
4/21/2000		168.14	16.59		151.55	68,000	3,300	2,500	3,100	20,000	260	-	4-	-	
7/31/2000		168.14	1637		51.77	99,000	5,600	1,400	4,300	22,000	490				
11/20/2000		168.14	19.71		148.43	37,000	5,100	1,500	1,300	4,800	2,800	_	**	-	
2/18/2001		168.14	1529		152.85	54,000	\$,020	3,880	2,850	15,400	1,010				
6/7/2001	P B ACCORDER	168.14	19.43	er ombreder er e	148.71	110,000	7,240	4,380	4,160	22,100	567				
9/5/2001		168.14	22:44		145,70	69,000	5,750	5.790	2,770	14,200	1,510				

Table 1. Summary of Ground-Water Monitoring Data: Relative Water Elevations and Laboratory Analyses

Station #11132, 3201 35th Ave, Oakland, CA

		тос	Depth to	Product	Water Level			Concentra	tions in (µ	g/L)	,		İ		
Well and		Elevation	Water	Thickness	Elevation	GRO/			Ethyl-	Total		(mg/L)			
Sample Date	P/NP	(feet msl)	(fect bgs)	(feet)	(feet msl)	TPHg	Benzene	Toluene	Benzenc	Xylenes	MTBE	DO	Lab	pН	Comments
MW-2 Cont.															
11/30/2001		168:14	19.58		148.56	120,000	7,270	6,540	4,590	23,000	794				
2/20/2002		168.14	16.39		151.75	56,000	2,410	2,270	2,910	14,300	160	-			A CONTRACTOR OF THE CONTRACTOR
6/20/2002		168.14	19.77		14837	86,000	7,310	6,490	3,080	14,600	659				
9/11/2002		168.14	21.60		146.54	130,000	7,600	13,000	5,400	30,000	<5000	-		-	
11/12/2002		168/14	2134		T46.80	46,000	4,100	4,300	1,900	10,000	1,900				
1/29/2003		168.14	16.80		151.34	77,000	4,700	2,600	2,800	13,000	820		-	-	n,t
5/22/2003		168 14	17,15		150.99	52,000	6,400	2,600	1,800	7,400	1,000				
7/28/2003		168.14	21,47	men .	146.67	31,000	6,900	5,500	2,200	12,000	1,700				Р
1718/2003	i i più	168-14	2050		147.64	23,000	32300	800	500	2,000	500		SEQM	6.6	
02/23/2004	P	168.14	14.77	4-	153.37	84,000	14,000	6,200	3,100	14,000	790	-	SEQM	6.6	t
05/04/2004	l P	168.14	20,09		148.05	120,000	15,000	17,000	4900	24,000	780		SEQM	6.6	
08/04/2004	P	168.14	21.39		146.75	38,000	9,100	3,300	1,900	5,800	430	-	SEQM	6.69	1
11/10/2004	l P	168.14	18.98		149.16	22,000	4400	2,000	940	3,600	3163		SEQM	7.5	
02/15/2005	P	168.14	15.62	Elitticas in Scholastonen 2006 22 200	152.52	67,000	11,000	4,200	3,000	11,000	690		SEQM	7.1	t
05/16/2005	P	168:14	1471		153,43	94,000	11,000	7,600	4,100	17,000	560		SEOM	6.5	
08/17/2005	P	168.14	20.00		148.14	110,000	13,000	8,000	4,300	18,000	480		SEQM	6.6	
11/18/2005	li Pili	168,14	20,89		147.25	37,000	11,000	2,400	1,500	4.600	340		SEOM	6.6	
02/07/2006	P	168.14	13.31		154.83	74,000	8,900	5,800	3,600	14,000	440		SEQM	6.7	
5/19/2006	le p	168.14	1630		351.84	78,000	11,000	3,700	4,500	14,000	430		SEQM	6,6	
8/23/2006	P	168.14	20.83	••	147.31	100,000	12,000	9,100	5,800	25,000	480	-	TAMC	6.6	armene de la compania
11/15/2006		168.14	20.80		147.34	46,000	8,800	3,600	2,300	8,500	400	0.70	TAMC	6,73	
MW-3			VIRS	DW.											
7/9/1990	_	167.17	J . C.			140	5.3	4.6	2	3.8					
12/21/1990		167.17				0.19	100	6	0.9	27					
3/7/1991		167.17	17.40		149.77	0.4	69	22	6.1	57				**	Constitution of the Control of the Control of Strategian Con-
4/1/1991	A NEW YORK	167.17	13.69		153.48										
6/27/1991		167.17				380	28	26	13	46					An annotae como semente establica de l'establica de
9/27/1991		167.17				0.07	7.9		0.4	leux.					
12/18/1991		167.17				0.26	34	24	0.8	28					feminish (balismentan marking m
7/3/1991	s luguenosc	167.17	19.59		147.58		9.4	0.9	112525						

Table 1. Summary of Ground-Water Monitoring Data: Relative Water Elevations and Laboratory Analyses
Station #11132, 3201 35th Ave, Oakland, CA

-		moc.	Dunth to	Product	Water Level			Concentra	tions in (µ	g/L)					
_		TOC Elevation	Depth to Water	Thickness	Elevation	GRO/			Ethyl-	Total		(mg/L)			
Well and Sample Date	P/NP	(feet msl)	(feet bgs)	(feet)	(feet msl)	TPHg	Benzene	Toluene	Benzene	Xylenes	MTBE	DO	Lab	pH	Comments
								,							
MW-3 Cont.			en kantarripus (vojeta septembrilis)	assastat etalessistema	agenikaru (Passalie		2.2	₹0.5±	i iš	2.8					
10/5/1992		167.17				45 0	5.1		6.1	8,1			1121994911111111 		TERRITORIA CONTRACTORIS PORTA CONTRACTORIS C
10/5/1992		167.17	21.22	 Manusurinkanasansik	145.95	67 830	5.1 50	34	42	89					
[/[3/1998		167.17	13.63		153.54	<50	<0.5	<0.5	<0.5	<0.5			-	-	c,i
4/23/1993		167.17	- 15:02		152.15	<50	<0.5	<0.5	1405	₹0.5					
4/23/1993		167 17			148.01	250	12	4.2	12	16	<5.0	**	-	**	i
7/12/1993		167.17	19.16		146.01	65	7.4		6.9	1 32 2					9
10/21/1993		67 17			145.36	52	4.4	1.4	4.7	3.3	<5.0	-			j
10/21/1993		167.17	21.81		147.23	57		34	9.6		45 0				
1/21/1994		167.17	20.24		146.93	600	26	23	33	88	28.7	1.8			i
4/20/1994		167.17	20.24 			120	77	1.6	50	67	5,43				
8/1/1994		167.17 167.17	20.74		146.43	99	6.2	1.1	4.5	5.2	<5.0	1.4			[
8/1/1994 12/23/1994		167.17				45 6	3 05	\$05	₹0 5	20 5					
12/23/1994		167.17	14.70	-	152.47	<50	<0.5	0.78	<0.5	<0.5	9.8	1.7			i ····································
12/25/1995		167.17	2.80		154.28	190	16	Ö.S	35	24		6.6			
6/8/1995		167.17	19.95	-	147.22	330	21	4	34	32		7		- 12 241115	
8/22/1995		67 17	2 41		145-76	USO	14	<0.50	≥0.50	1.6	\$5.0	6.6			
10/27/1995		167.17	22.43		144.74	-				_	-	- 69			
10/30/1995		67.17				51		<0.50	<050	10	50				
1/25/1996	######################################	167.17	14.03		153.14	<50	<0.50	< 0.50	<0.50	<1.0	5.1 5.1	 5 4			
4/19/1996		167:17	15,26		151.91	460	55			-63	<10	9.2			
7/23/1996	_	167.17	19.19	4-	147.98	<50	<0.5	<0.5 <5.0	<0.5 <5.0	<0.5 <5.0	-10 	8.4			
11711/1996		167:17	20/24		14693	230	325		e pronomant	<1.0	<10	5.4			THE CONTROLLER OF THE PROPERTY
1/21/1997		167.17	13.09		154.08	<50	<0.5	<1,0 %10	<1.0 	1.0 21.0		43			
4/29/1997		167.17	18.14		149.03	250	<0.5	<1.0	<1.0	<1.0	<10	4.9			22 (3)(6)(10.02)(2)(5)(2)(5)(1)(4)(4)(4)(4)(4)(4)(5)(4)(5)(4)(5)(6)(4)(6)(6)(6)(6)(6)(6)(6)(6)(6)(6)(6)(6)(6)
8/21/1997	_	167.17	19.64		147.53	<50	<0.3 <2.5	<50	\$5.0	45.0	<50	45			
1175/1997		167.17	19.95		147,22	₹250		<1.0	<1.0	<1.0	<10	4.7		-	######################################
2/3/1998		167.17	10.57	ia samonemisenzani	156.60	<50	<0.50 <2.5	21.0 25.0	50	\$5.0	30	42			
5/28/1998		167-17	14.65		152.52	330							- CONTRACTOR		NE PRESIDENTIALISME ASSESSMENT OF CHARACTERS AND ASSESSMENT OF CHARACTERS
12/30/1998		167.17	16.63		150.54	 -250	- 	- 25.0	25.0		<5.0				
2/2/1999		167.17	19,12		154,05	5230	53.0						uri Elitapaanilli	marantai.	Zanika (1944) i 1947 (1944) 1945 (1945) (1945) (1945) 1945 (1945) (1945) 1946 (1945) 1946 (1945) 1946 (1945) 1

Table 1. Summary of Ground-Water Monitoring Data: Relative Water Elevations and Laboratory Analyses
Station #11132, 3201 35th Ave, Oakland, CA

					TOC Depth to Product Water Level Concentrations in (µg/L)										
			(mg/L)		Total	Ethyl-			GRO/	Elevation	Thickness	Water	Elevation		Well and
Comments	рĦ	Lab	DO	МТВЕ	Xylenes	Benzene	Toluene	Benzene	TPHg	(feet msl)	(feet)	(feet bgs)	(feet msl)	P/NP	Sample Date
															MW-3 Cont.
										152.96		14.21	167.17		5/10/1999
			-	••	**	**				152.81	-	14.36	167,17	695 <u>1444</u>	8/24/1999
										147,96		1921	167.17		11/3/1999
sedesderreitherheitherheit		 Massementer		<0.5	0,62	<0.5	0.57	<0.5	<50	152.0D		15.17	167.17		3/1/2000
										152.20		14:88	167.17		4/21/2000
	 SEMBORA	 ***********************************								151.88		15.29	167.17		7/31/2000
										149.86		17-1	167.17		11/20/2000
					9.09	10.2	1.31	1.95	160	154.32		12.85	167.17		2/18/2001
			(Miller and St							140 17		18.00	167,17		6/7/2001
			-			 		-		146.85		20.32	167.17	***	9/5/2001
				<0.5						150/23		1694	16707		ji/30/2001
				<0.3	5.75	6.58	0.845	<0.5	86	152.33		14.84	167.17		2/20/2002
										148.77		1840	167.17		6/20/2002
							 1355221 52 400			147.11	···	20.06	167.17		9/11/2002
n				0.76	45	24				147.33		19.84	167:17		11/12/2002
							9.7 当	20	850	152.34		14.83	167.17		1/27/2003
P	-									151.57		15.60	167.17		5/22/2003
									1	147.05 148.02		20.12	167.17		7/28/2003
A THE PROPERTY OF THE PARTY OF	6.7	SEQM		<0.50	12	9.6		<0.50	160	153.64		9 15	167 17		11/18/2003
										148.36		13.53 18.61	167.17	 :::::::::::::::::::::::::::::::::::	02/23/2004
	-		<u> </u>		-					147.96		19.21	167.17		05/04/2004
										L49 69		17.48	167.17		08/04/2004
7,77,77,000	7.5	SEQM		1.7	9.6	9.2	1.8	7.8	500	152.86	-	14.31	167.17	P	17/10/2004
										154.06			167.17		02/15/2005
711111111111111111111111111111111111111		-		_	-	_		-		148.64		18.53	167.17		05/16/2005 08/17/2005
										147.83		1934	67.17		08/1//2005 11/18/2005
· · · · · · · · · · · · · · · · · · ·	7.1	SEQM		<0.50	2.3	1.4	<0.50	<0.50	65	155.53		11.64	167.17	P	02/07/2006
										152.29		14.88	167, 7		5/19/2006
		— abisanaa::	-			_	-			147.74		19.43	167.17	-	8/23/2006
										147.95		19.22	167:17		11/15/2006

Table 1. Summary of Ground-Water Monitoring Data: Relative Water Elevations and Laboratory Analyses
Station #11132, 3201 35th Ave, Oakland, CA

-		TOG	Depth to	Product	Water Level			Concentra	itions in (u	g/L)					
		TOC Elevation	Depth to Water	Thickness	Elevation	GRO/	T		Ethyl-	Total		(mg/L)			
Well and Sample Date	P/NP	(feet msl)	(feet bgs)	(feet)	(feet msl)	TPHg	Benzene	Toluene	Benzene	Xylenes	МТВЕ	DO	Lab	pН	Comments
•	17111	(1001 (1111))	(****-8-/							-					
MW-3															
MW-4			UPG	RADIE	M										
7/9/1990		170.36	'				-				**	-	na n		dromeshirking midaliganing
12/21/1990		170:36								0.8					
3/7/1991		170.36	20.72	**	149.64		2.2	3.8	1.5	2.8					ne an headh an hair an headh
4/1/1991		170.36	17.49		152.87										
6/27/1991		170.36		**			6.3	1.8	0.4	1			 heroonsmitth		
9/27/1991		170,36													
12/18/1991	-	170.36	••	-	-	-						 :::::::::::::::::::::::::::::::::::		-	
7/3/1992		170.36	22.16		148.20	₹50	\$0.5	<05	50 5	305					
10/5/1992	-	170.36	23.38		146.98	<50	<0.5	<0.5	<0.5	<0.5	_ 	-			
1/13/1993		17036	17.58		i S2.78	₹50	50.5	\$0,5	₹05	205					
4/23/1993		170.36	15.72	***	154.64	<50	<0.5	<0.5	<0.5	<0.5	- 				
7/12/1993		2170:36	21.74		148.62	\$30	F0.5	<0.5	505	1 05	<5.0				
10/21/1993	-	170.36	23.84		146.52	<50	<0.5	<0.5	<0.5	<0.5	<5.0 45.0				
1/21/1994		170.36	22.42		147.94	\$50	203	\$0.5		(0.5)	<5.0	11111111111111111111111111111111111111			
4/20/1994		170.36	22.66		147.70	<50	< 0.5	<0.5	<0.5	<0.5	75.0 35.0	110			
8/1/1994		17036	2301		14735	420	5.405	<0.5	<0.5						
12/23/1994		170.36	17.03	-	153.33	-		-	 						
1/26/1995		170.36	1747		15294	250	<0.5	<0.5							
6/8/1995	_	170.36	21.55	-	148.81	- - - - - - - -	 	 	<0.50		25.0	6.4			a a
8/22/1995		170.36	23.47			e promininte									
10/27/1995	-	170.36	24.50		145.86	 <50	- - - - - - - - - - - - - - - - - - -	 <0.50	 <0.50		58			lш	
1/25/1996		17026	18 74		151.62		i: pridheuman					KAROLONIOSI 			
4/19/1996		170.36	18.63		151.73										
7/23/1996		170.36	22.56		147.80		<1.0	<1.0	<1.0	<1.0	34	B.2			
11/11/1996		170.36	23.63		146.73	<50	1								
1/21/1997			16.59		153.77				<1.0	<1.0	<10	4.7			SETSTRUCTURE DESCRIPTION
4/29/1997	##	170.36	21.43		148.93	<50	<0.5	<1.0	~1.0 						
8/21/1997		170:36	20.01		147,45				<1.0	<1.0	76	4.9		# Process	risasarupingusususuti
11/5/1997	-	170.36	22.34	-	148.02	60	<0.5	<1.0	1.0	1 -1.0	1 "	1 "	I	ı	1

Table 1. Summary of Ground-Water Monitoring Data: Relative Water Elevations and Laboratory Analyses
Station #11132, 3201 35th Ave, Oakland, CA

		тос	Danth to	Product	Water Level			Concentra	tions in (u	g/L)					
Well and		Elevation	Depth to Water	Thickness	Elevation	GRO/			Ethyl-	Total		(mg/L)			
Sample Date	P/NP	(feet msl)	(feet bgs)	(feet)	(feet msl)	TPHg	Benzene	Toluene	Benzene	Xylenes	MTBE	DO	Lab	pН	Comments
MW-4 Cont.		, , , , , , , , , , , , , , , , , , , ,					<u> </u>	ĺ							
M W-4 Cont.					. = 0 . 0										
2/3/1998	.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	170.36	12.26	 :::::::::::::::::::::::::::::::::::	158.10	 11:11:12:22:23:23:23:23:23:23:23:23:23:23:23:23	 <0.5	 <1.0	- - 51,0	- ZI 0 T	160	412			
5/28/1998		17036	18,50		151.86	70							251800/51/56 	Alliandik 	
12/30/1998		170.36	19.69		150.67	70	- - - -		- - 10	<1.0	130				
2/2/1999		17036	1826		152.10			in decading							
5/10/1999		170.36	17.86		152.50 152.43										
8/24/1999		170.36	17.93		1321 9 3 147.58										Fill the state of
11/3/1999	 managananan	170.36	22.78		147.36 152:32	- - - - - - - -		0.67	- 305	07	110				
3/1/2000			-18,04; 17.36		153.00									***	
4/21/2000		170.36	17.36		152.53										
7/31/2000		17036	18,91		151.45									••	iinii ≔iii kentatututineammaanorte
11/20/2000 Transportation (1970)	 (echiene)	170.36	16.71 17.72		152.64	88	k0.5	 	1205		973				
2/18/2001		170.36	20.23		150.13			-	-		-				
6/7/2001 9/5/2001		170.36	22.76		147.60										
11/30/2001		170.36	21.30	-	149.06		-		-			••	-		
2/20/2002		17036	19,32		151.04	76	*0.5	30.5	1 405		81				
6/20/2002		170.36	20.71		149.65				-	_		-			
9/11/2002		###17038 # #	55 55		14814										
11/12/2002	••	170.36	22.22		148.14			-							samonas arangan nangatan saka saka saka saka saka saka saka sak
1/29/2003		17036	19.80		150.56	TOO	<0.5	4.5	, <0.5	<0.5	66				
5/22/2003	HELEKTISTRIKING 	170.36	19.35		151.01			-							
7/28/2003		17036	22,18		148 18										P
11/18/2003		170.36	21.65	Miller eierberteurburb derse ere.	148.71		-		-	**		-	···	 	
02/23/2004	P	17036	17.53		152.83	75	<0.50	<0.50	<0.50	. <0.50	65		SEOM	6.8	
05/04/2004	***	170.36	20.62		149.74				-						
08/04/2004		170.36	21,30		149,06										
11/10/2004	***	170.36	20.65		149.71					-			-	7.6	
02/15/2005	P	17036	18.91		151,45	<50	<0.50	<0.50	\$0.5 D	<0.50	62		SEQM		
05/16/2005	-	170.36	17.34		153.02	 Karanganang		-	-	-		 Distribution			
08/17/2005		170.36	21.31		149.05										
11/18/2005	-	170.36	21.67		148.69			-	-	-		-	-	1 -	1

Table 1. Summary of Ground-Water Monitoring Data: Relative Water Elevations and Laboratory Analyses

Station #11132, 3201 35th Ave, Oakland, CA

		тос	Depth to	Product	Water Level			Concentra	itions in (µ	g/L)					
Well and		Elevation	Water	Thickness	Elevation	GRO/	<u> </u>		Ethyl-	Total		(mg/L)			
Sample Date	P/NP	(feet msl)	(feet bgs)	(feet)	(feet msl)	TPHg	Benzene	Toluene	Benzene	Xylenes	MTBE	DO	Lab	pН	Comments
MW-4 Cont.															
02/07/2006	Р	170.36	16.74		153.62	100	<0.50	<0.50	1.0	3.0	29		SEQM	6,8	
5/19/2006		170.36	18.22		152 14										
8/23/2006		170.36	20.95	**************************************	149.41				**			-		_	
11/15/2006		17036	2221		148115										
MW-5			X 150'	DG 0	r son	RCC	ARE	A							
7/9/1990		165.14	_	-		280	200	210	46	290					
12/21/1990		165 14				0.69	300	343	8.4	30					
3/7/1991		165.14	16.60		148.54		17	0.9	0.7	1.6					
4/1/1991		165.14	11.99		153.15	-800	250	34		60					
6/27/1991	_	165.14	**			330	120	10	12	8	••			 Managana	merchanitaningah menggangkan ka
9/27/1991		165 14				0.73	230	16	20	22					
12/18/1991	_	165.14		-			-					 Juneanis			
7/3/1992		165,14	18.65		146-49	150	36	<0.5	< 05						
10/5/1992		165.14	20.32		144.82	270	79	4	1.7	2.9		- kanaanmaa		 D7865446	
1/13/1993		165.14	13.03		152:11	180	59			76					
4/23/1993		165.14	13.51	enildaninistajana	151.63	8,700	440	96 5 2 9	35 35	136	- 				
7/12/1993		165.14	18.06		147.08	250 210	57 82	1.5	<0.5	1.4					
10/21/1993	 :::::::::::::::::::::::::::::::::::	165.14	20.41 18.86		144.73 146.28	110	96 236	1 1.2	10.5 10.5	07					
7/21/1994 4/20/1994		165.14 165.14	17,30		147.84	690	230	4.5	1.6	11	21.2	1.3			
4/20/1994 8/1/1994		165.14	17.50		14761	170	4	116	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	111271	50 F	0.9			
12/23/1994		165.14	11.63		153.51	630	180	1.9	0.66	1.9	7.81	1.4	Tikinyan wan	***	i
1/26/1995		T65.14	1125		153.89	160	68	*05	11 805	11-22		59			
6/8/1995		165.14	16.80		148.34	2,000	630	58	61	081		6.5	_		
6/8/1995		165:14				1700	560	511	11155	170					C Filippin
8/22/1995	######################################	165.14	19.02	-	146.12	3,700	1,100	18	27	59	<130	7.3	_	-	ď
10/27/1995		165.14	20.94		14420										
10/30/1995		165.14	 hedesimming		· · · · · · · · · · · · · · · · · · ·	6,500	2,200	55	180	270	<250	7.5		-	agyar pangi sanyi paggangganggan dalakinininin sangitari Ponsi.
1/25/1996		165.14				5 40	37	0.66	< 0.50	£1.0	<5.0				
1/25/1996		165.14	13.30	mm. Patalate genyindeniare terden mengim	151.84	590	37	0.7	<0.50	<1.0	<5.0		-	-	

Table 1. Summary of Ground-Water Monitoring Data: Relative Water Elevations and Laboratory Analyses
Station #11132, 3201 35th Ave, Oakland, CA

		тос	Nanth to	Product	Water Level			Concentra	tions in (n	9/1.)					
Well and		Elevation	Depth to Water	Thickness	Elevation	GRO/	1	Concentra	Ethyl-	Total		(mg/L)			
Sample Date	P/NP	(feet msl)	(feet bgs)	(feet)	(feet msl)	TPHg	Benzenc	Toluene	Benzene	Xylenes	МТВЕ	DO	Lab	ρН	Comments
MW-5 Cont.															
4/19/1996		165.14	13.63	_	151.51	1,500	470	38	49	210	<50	8.1			
7/23/1996		165.14	17.61		147.55	140	4.6	\$63 L	<0.5	1 20 5		. 8			
1 1/1 1/1 996		165.14	18.70		146,44	140	40	<1.0	<1.0	<1.0	<10	7.9		-	
1/21/1997		165.14	11.63		153.51	730	300-	25.0	7.8	26	<50::::				
4/29/1997	••	165.14	16.74	**************************************	148.40	340	530	<5.0	<5.0	<5.0	<50	4.8	-		Comment Contract of the Contract of Contra
8/21/1997		16514	18.26		146.88	<50	40.5	<10	\$10	<1.0	<10	49			
11/5/1997	-	165.14	18.84	**	146.30	120	13	<1.0	<1.0	<1.0	<10	4.4		_	
2/3/1998		16514	9,49		155.65	450	<0.30	<1.0	310		<10	43			
5/28/1998		165.14	13.57		151.57	4,900	1,500	34	180	311	<10	4.1		unineroni	765000000000000000000000000000000000000
12/30/1998		165,14	74.6S		150.49										
2/2/1999		165.14	12.56	arikimiisiokii kisi ti	152.58	100	<1.0	<1.0	<1.0	<1.0	9.1				
5/10/1999		j 65 14	1536		15178										
8/24/1999	nunterarius 	165.14 165.14	13.50		151.64 146.66	- 11675121.615									
11/3/1999		165.14	1848 9.59		155.55	<50	<0.5	0.58	<0.5	0.54	2.9				
3/1/2000 4/21/2000		165.14	13.52		151,62						1				
7/31/2000		165.14	14.04		151.10						- Epiter 2	-			
1 1/20/2000		16514	15/89		149 25										
2/18/2001		165.14	11.88		153.26	560	161	2.38	6.11	13	5.67) via via contraction of the con
6/7/2001		165:14	1530		149.84										
9/5/2001		165.14	19.32	••	145.82	— —	-	-	-	-	-	-	-	-	
1 1/30/2001		165.14	11734		T#7.70										
2/20/2002	in Millian disclaration	165.14	13.88		151.26	4,200	940	18.7	98.2	176	55.6		-		
6/20/2002		165.14	16 20		148.94										
9/11/2002	-	165.14	19.15	-	145.99						—			-	
11/12/2002		165.14	19.01		146 13	390		0.89	34	35	210				
1/29/2003		165.14	16.33	in in the second	148.81	7,900	1,400	34	220	350	82	-			n managanan managan mengan m
5/22/2003		165.14	14:35		150.79	9900	2,700	91	400	690	≪50				
7/28/2003		165.14	18.90		146.24	3,200	690	14	81	100	120				p Well maecessible e. q
1/18/2003		165.14							100	350	100		SEQM	6.7	
02/23/2004	P	165.14	12.21	_	152.93	7,500	1,500	100	190	1 330	100	†	ardw.	1 0.7	1

Table 1. Summary of Ground-Water Monitoring Data: Relative Water Elevations and Laboratory Analyses

			Dth. to	Product	Water Level			Concentra	tions in (µ	g/L)					
		TOC	Depth to Water	Thickness	Elevation	GRO/			Ethyl-	Total		(mg/L)			
Well and	DOID .	Elevation (feet msl)	(feet bgs)	(feet)	(feet msl)	TPHg	Benzene	Toluene	Benzene	Xylenes	MTBE	DO	Lab	pН	Comments
Sample Date	P/NP	(leer mar)	(leet ogs)	(1621)	(· · · · · · · · · · · · · · · · · · ·				
MW-5 Cont.													arou		
05/04/2004	Р	165.14	17.12	-	148.02	5,900	1,500	57	200	280	42	-	SEQM	6.6	
08/04/2004	P	165.14	19:05		146.09	<2,500	₹25	25	-25	25	390		SEQM	6,69	
11/10/2004	P	165.14	16.95		148.19	870	80	<5.0	<5.0	<5.0	530		SEQM	7.5	
02/15/2005	P	165 14	12.75		152:39	1,600	330	8.0	97	67	260		SEOM	7.2	
05/16/2005	Harekaumu P	165.14	15.46		149.68	<500	<5.0	<5.0	<5.0	<5.0	370	-	SEQM	6.7 6.6	
08/17/2005		165.14	17.00		148 14:	7,000	1,000		110	130	51		SEOM	7.3	
11/18/2005	p	165.14	18.33		146.81	1,900	91	<5.0	33	29	340 200	 s cupatuli (116	SEQM	6.7	
02/07/2006	P	165-14	1027		54.87	2,100	590	9.6	86	110			SEQM	6.8	
5/19/2006	P	165.14	13.08		152.06	3,200	720	9.7	150	170	44		SEQM TAMC	7.11	
8/23/2006	P	165 14	17.02		148.12	1,400	69	\$5.0	20	24	230		TAMC	6.82	
11/15/2006	2023111621277 P	165.14	18.30	-	146.84	1,100	24	<2.5	10	8.6	490	0.85	IAMC	9.02	
MW-6				1200	ADIEN	14	1								
webshies programme never being light desperation of the	enanganis														
7/9/1990		16540				0.17	2.6	7	4.9	26	**		-		The state of the s
12/21/1990		165.40 165.40													e e
3/7/1991		165.40 165.40			153.61	-	-			-			-		
4/1/1991	-	165.40													
6/27/1991		165.40					ii Harberinii			_			-	-	e
9/2 7/1991		165.40					13	22		27					
12/18/1991		165.40	17.77		147.63	<50	<0.5	<0.5	<0.5	<0.5			-		
7/3/1992		165.40	19.46		45.94	<50	- - 70 5	20.5	70.5	<0.5					
10/5/1992		165.40	11.34		154,06	<50	<0,5	<0.5	<0.5	<0.5	••	-			i aalaamaanaanuummummummiisinsii vadiliiiilii
1/13/1993			12 92		15248	 	505	₹0:5	*0 5	k0.5					
<i>A72</i> 3/1993		165,40	17.36		148.04	<50	<0.5	<0.5	<0.5	0.7	<5.0		_	-	
7/12/1993 10/21/1993			19.98		145 42	250	¥0.5	¥0.5	3 80 5	405					
	r canadaes	165.40	18.10		147.30	<50	<0.5	<0.5	<0.5	<0.5	<5.0	_	-	uni traccióni	es engles announcement announcement
1/21/1994		165.40	18.68		146.72	¥ 350	203	505	205	<0.5	17.4				
a/20/1994		165.40	18.90		146.50	<50	<0.5	<0.5	<0.5	<0,5	8.66	1.5	 		
8/1/1994 12/23/1994		165:40	12.94		152.46										
STEENING HERECOURTERING		165.40	10.46		154.94	<50	<0.5	<0.5	<0.5	<1	-	7.3	-	-	
1/26/1995	1	105.70	1	l	· ·	ı	1	,		-					

Table 1. Summary of Ground-Water Monitoring Data: Relative Water Elevations and Laboratory Analyses
Station #11132, 3201 35th Ave, Oakland, CA

				Dlost	Water Level			Concentra	tions in (µ	g/L)					
		TOC	Depth to Water	Product Thickness	Elevation	GRO/		-	Ethyl-	Total		(mg/L)			
Well and	P/NP	Elevation (feet msl)	(feet bgs)	(feet)	(fect msl)	TPHg	Benzene	Toluene	Benzene	Xylenes	мтве	DO	Lab	pН	Comments
Sample Date	Lifet	(teet man)	(rect oga)	(***-)											
MW-6 Cont.															
6/8/1995		165.40	16.84		148.56		••	_		uning state (1951)	 			 #######	
8/22/1995		165.40	1948		145.92	-50	≮0.50	<0.50	<0.50	\$10	\$5.0	6.7			
10/27/1995	dillinorisar	165.40	20.39	_	145.01					 		 1000688888		- 191604	
1/25/1996		165.40	1224		153.16	<50	<0.50	<0.50	2050	\$1.0	9.9				
4/19/1996		165.40	13.90		151.50			ea and assume armited	_ Lagaermeness	-					
7/23/1996		165.40	1783		147.37									State of the	
11/11/1996	-	165.40	18.90	***	146.50	<50	<0.5	<1.0	<1.0	<1.0	<10	7.7	 Enternament	-	
1/21/1997		165.40	1:97		153,43									MHERNIHI	
4/29/1997	-	165.40	17.04		148.36	<50	<0.5	<1.0	<1.0	<1.0	<10	4.5			
8/21/1997		16540	18.58		146.82										
11/5/1997		165.40	19.17		146.23	70	<0.5	<1.0	<1.0	<1.0	85	4.3			
2/3/1998		165 40	987		155.53							3.7			
5/28/1998		165.40	13.38		152.02	<50	<0.5	<1.0	<1.0	<1.0	<10				
12/30/1998		165.40	1445		150.95										
2/2/1999		165.40	18.29	**	147.11		-								
5/10/1999		165.40	7749		147,91					. I the standard states					
8/24/1999	_	165.40	17.61	**	147.79	-			-			·····			
11/3/1999		165.40	16.26		14914										
3/1/2000		165.40	17.43		147.97										
4/21/2000		165.40	13 52		152.08										
7/31/2000		165.40	13.46	-	151.94		 								
1 1/20/2000		165.40	14.78		150.62										
2/18/2001		165.40	11.33		154.07	er er entremen	-	 #							
6/7/2001		165.40	1636		149.04		di meranikan	"""				ЩЩ			
9/5/2001		165.40	18.61	**	146.79			 ***********************************	-						
1 1/30/2001		165.40	1520		50:20					***************************************					
2/20/2002		165.40	12.74	-	152.66			 	 PO ESPARADIZONO						
6/20/2002		165:40	16 68		148.72										
9/11/2002	100 10000	165.40	18.38		147.02		 ***********************************								
11/12/2002		165.40	18.78		146.62									# [MARIES.	n
1/29/2003		165.40	14.45	-	150.95	-	-	-	-	1 -		1 -	l	I	1

Table 1. Summary of Ground-Water Monitoring Data: Relative Water Elevations and Laboratory Analyses
Station #11132, 3201 35th Ave, Oakland, CA

		тос	Depth to	Product	Water Level			Concentra	ıtions in (µ	g/L)					
Well and		Elevation	Water	Thickness	Elevation	GRO/			Ethyl-	Total		(mg/L)			
Sample Date	P/NP	(feet msl)	(fect bgs)	(feet)	(feet msl)	TPHg	Benzene	Toluene	Benzene	Xylenes	MTBE	DO	Lab	pН	Comments
MW-6 Cont.					-							de sur l'annuaire de la constant de			
5/22/2003	-	165.40	14.36		151.04					**	***	**		••	
7/28/2003		165.40	18.41		146.97										P. C.
11/18/2003		165.40	17.48		147.92	-		nene Epopopopor i renesambaj	****************	 merecenses		-		- 6000	
02/23/2004		165:40	11,54		153186										
05/04/2004		165.40	16.58		148.82		-		 Laurmonacaar		######################################			LEGISTER'S	nia:somenimu:dinonuedinoranimu:
08/04/2004		65.40	18.12		147.28										
11/10/2004		165.40	15.75		149.65	_			 hannamanasas	_ -		 :::::::::::::::::::::::::::::::::::			
02/15/2005		165,40	1250		152.90								GEOV.		
05/16/2005	P	165.40	11.51		153.89	<50	<0.50	<0.50	<0.50	<0.50	<0.50	-	SEQM	7.0	
08/17/2005		165.40	16.85		148.55										e e
11/18/2005		165.40	 			- 30	- 	- <0.50	 <0:50	- 20.50	_ 		ł		
02/07/2006	P	165.40	993		155.47	161111111111111111111111111111111111111	michantian				-		SEOM		c
5/19/2006		165.40	 1635		- 149.05						ers created effection (Chillettin)				
8/23/2006		165,40 165,40	17.42		147.98										
11/15/2006		105.40	17.42	250			<u> </u>					 		<u> </u>	
MW-7				CKO.	is Gi	KND1	アン	1	alendeitlänkiikit	en en sonannore.					
7/9/1990		167.61													
12/21/1990		167.61					-		•• 2018763127611	**					
3/7/1991		167.61	19:04		148.57			0.4	03.	24					
4/1/1991	-	167.61	15.18		152.43					 DENGE ATTES					
6/27/1991		167.61				70			0.8	22					
9/27/1991		167.61	••	mentelimetraliteiteiteiteiteiteiteiteiteiteiteiteitei			0.4	 295	- 08	0.4 3.5	 1913:2 <u>Ш</u> УИИ			10007681011	
12/18/1991		767.61			Tanga namba sa mada		<0.5	<0.5	<0.5	<0.5					
7/3/1992	-	167.61	20.28		147.33	<50 # ₹50	<0.5 1 20.5	<0.5	<0.5 <0.5	-0.5			1		
10/5/1992		167.61	21.96		146.05 152.20	≤30 <50	<0.5	<0.5	<0.5						
1/13/1993 ###################################		167.61	15.41		monde and and and and	<50	<0.5 80.5	- 7.3 - 205	-0.5 	- K03					
4/23/1995		167.61	15.84		151.77 147.77	<50	<0.5	<0.5	<0.5	<0.5	<5.0			78500EL	
7/12/1993		167.61 167.61	19.84 21.61		46.00	550 T	\$0.5	\$0.5		<0.5					
10/21/1993	-				147.12	<50	<0.5	<0.5	<0.5	<0.5	<5.0			-	i i
1/21/1994		167.61	20.49	-	147.12	7,00	1 -0.5	70.5	1 -5.5	1	I	!	1	ı	ŀ

Table 1. Summary of Ground-Water Monitoring Data: Relative Water Elevations and Laboratory Analyses
Station #11132, 3201 35th Ave, Oakland, CA

					Water Level			Concentra	tions in (u	g/L)					
		TOC	Depth to	Product Thickness	Elevation	GRO/		Cuntenti	Ethyl-	Total		(mg/L)			
Well and	D/N/D	Elevation (feet msl)	Wuter (feet bgs)	(feet)	(feet msl)	TPHg	Benzene	Toluene	Benzene	Xylenes	MTBE	DO	Lab	pН	Comments
Sample Date	P/NP	(lect list)	(leer nga)	(,					<u></u>						
MW-7 Cont.															· e
1/21/1994		167.61				<50	<0.5	<0.5	<0.5	<0.5	- 50	40.0258		movens	
4/20/1994		167.61	2054		47.07	₹50	<0.5	< 0.5	<0.5	\$05	<5.0 <5.0	1.5			
8/1/1994		167.61	20.99		146.62	<50	0.7	<0.5	<0.5	<0.5					
12/23/1994		167.61	15.00		52.61							7			
1/26/1995		167.61	14.69		152.92	<50	<0.5	<0.5	<0.5	<1 					
6/8/1995		167.61	19:87		147.74					i laterinamiani	<5.0	6.4			d
8/22/1995		167.61	21.49		146.12	<50	<0.50	<0.50	<0.50	<1.0		0.7			
(0/27/1995		167.61	22.53		145.08					<1.0	<5.0				
1/25/1996	-	167.61	17.21		150.40	<50	<0.50	<0.50	<0.50	1					
4/19/1996		167.61	17 09		15052										
7/23/1996		167.61	21.02		146.59	-	- 205	- Rio		- E1.0	 	178			
11/11/1996		167.61	22 03		145 58	<50	u firitam us ingur								A STANDONE OF THE PARTY OF THE
1/21/1997	-	167.61	15.06	-	152.55		- - - - - -	 		#10 E	l sio	1.44			
4/29/1 99 7		167.61	2001		147.50	\$50									er error transmitten er
8/21/1997		167.61	21.59		146.02	 \$50	- - 303	eio.	410	 	les sio	44			
175/1997		167.61	20 05		147.56 157.64								_	-	10)
2/3/1998		167.61	9.97 18.52		154.09	350	Z0.5	1 210	451.0	1 1 1 1 1 1	i kio				
5/28/1998		167,61	18.33		149.28			# 15000000000000000000000000000000000000		 	**	##-	-	-	(A)
12/30/1998	-	167.61	253		135.28										
2/2/1999		167.61	13.52		154.09				-		***	-			
5/10/1999	-	167.61 167.61	1401		153.60										
8/24/1999 11/3/1999		167.61	19.91		147.70	######################################		er		_				- -	
3/1/2000		167.61	19.89		147.72										
		167.61	17.94		149.67				-				-		
4/21/2000 7/31/2000		l.	17.33		150:28										
(Alternative) and the second s		167.61	18.41		149.20	RI SPIJSKI AMERICA ***		-		-				 060 2781.7691	
11/20/2000 2/18/2001		167.61	5.13		152 48										
6/7/2001		167.61	18.75		148.86	01 KHIII (CA1114)	 188 Sincressing			_			-	 150 DANGAR	
9/5/2001		167.61	20.48		147,13										
11/30/2001		167.61	20.11		147.50		-		-	-	-		-	1 -	

Table 1. Summary of Ground-Water Monitoring Data: Relative Water Elevations and Laboratory Analyses
Station #11132, 3201 35th Ave, Oakland, CA

		тос	Depth to	Product	Water Level			Concentra	itions in (μ	g/L)					
Well and		Elevation	Water	Thickness	Elevation	GRO/			Ethyl-	Total		(mg/L)			
Sample Date	P/NP	(feet msl)	(feet bgs)	(feet)	(feet msl)	TPHg	Benzene	Toluene	Benzene	Xylenes	мтве	DO	Lab	рH	Comments
MW-7 Cont.															
2/20/2002		167.61	18,40	••	149.21										
6/20/2002		167.61	18.62		148.99										
9/1 1/2002		167.61	20.05		147.56	— 			 		**				Lagger lagger on the standard first from a self-self-specification and self-self-specification and self-self-specification and self-specification and self-speci
11/12/2002		167.61	1 21.13		146.48										n - i
1/29/2003	######################################	167.61	19.10		[48,5]					**	****	-	-		
5/22/2003		167-61	18.83		148.78										
7/28/2003		167.61	19.88	***	147.73		-		_	_					p
11/18/2003		168 08	20,50		147.68										
11/18/2003		167.61	20.50	**************************************	147.11	4-		-	-	_	**			-	S
02/23/2004		168.08	1592		152.16										
05/04/2004		168.08	18.86	w.m.	149.22				_		***		-	-	
08/04/2004		168.08	19710	Plantin	14898										
11/10/2004		168.08	20.25	•	147.83		-	 	 Imanulianilia	-			 liciticaliileisii	-	
02/15/2005		168.08	1637		15171										
05/16/2005		168.08						 				- 			e Ssiagopisas parakorobolikskir
08/17/2005		168.08	1974		14834										
11/18/2005		168.08	20,82		147.26	_	_ දුරු		- -55.0	 121025:012	270		SEQM	73	
02/07/2006		168.08	1426		153.82	₹500		25.0							
5/19/2006	 	168.08	16.51	_	151.57										
8/23/2006		68.08	2030		147.78 147.23									-	
11/15/2006		168.08	20.85	76-0	F Sou	DCC	MC	0	 	 		 		<u> </u>	
MW-8			2 75	700		RCE	TRE	i	1					ricasecora	
377/1991		165.74	1672		149,02	27	780	450	64	310					
4/1/1991	#2:16:46:4400-1-1-1	165.74	12.54		153.20	15,000	3,600	2,600	410	1,900	···				
6/27/1991		6574				12,000	3,400	1,100	240	750					
9/27/1991		165.74	-		-	41	5,700	5,200	1,100	4,300	 Haranantinani a entrantilli (l	 elecement	 1 TOTAL TABLET	- -	
12/18/1991		165.74					990	150	120	250					
7/3/1992	-	165,74	18.78		146.96	72,000	19,000	32,000	3,000 Lanamama	15,000	 managamananan	-		 (D)5:803	
L0/5/1992		165.74	20.48		145.26										
1/13/1993		165.74	12.87		152.87	-	-		-	-	1 -	-	-		1

Table 1. Summary of Ground-Water Monitoring Data: Relative Water Elevations and Laboratory Analyses
Station #11132, 3201 35th Ave, Onkland, CA

		тос	Depth to	Product	Water Level			Concentra	tions in (µ	g/L)					
Well and		Elevation	Water	Thickness	Elevation	GRO/			Ethyl-	Total		(mg/L)			•
Sample Date	P/NP	(feet msl)	(fect bgs)	(feet)	(feet msl)	ТРНд	Benzene	Toluene	Benzene	Xylenes	MTBE	DO	Lab	рH	Comments
MW-8 Cont.															
4/23/1993		165.74	13.90		151.84						••			e	l
7/12/1993		165,74	1830		147.44										
10/21/1993	**	165.74	21.91		143.83	-	••								
1/21/1994		165.74	19.12		146.62										
4/20/1994		165.74	19.28		146.46	26,000	1,700	4,100	960	4,000	632	1.1		***	
8/1/1994		165.74													
12/23/1994		165.74	13.81		151.93		-					uu Kanatounaa		unemater	**************************************
1/26/1995		165.74													
6/8/1995	••	165.74	17.82		147.92						 		_	_ 	
8/22/1995		165.74	1941		1146.33										
10/27/1995		165.74	20.47		145.27					interdebellutum					
1725/1996		165.74	19:35		152.39							1			
4/19/1996	-ummanand):	165.74	14.40	arasingementing	151.34	- tarininisivina		i Durcenseuriens	 		_ 				
7/23/1996		165.74	18,55		147.30										
11/11/1996		165.74	19.41 12.20		146.33 153.45										
1/21/1997		165.74	Heimandudun den der												c
4/29/1997		165.74 165.74	 1961		- 146 is 1	240,000		9,300		31,100	₹1000	5.2			
8/21/1997 11/5/1997		165.74	19.45		146.29	57.000	790	2,700	2,300	15,200	<1000	1 5		_	
2/3/1998		105.74 165.74	931		15641										
2/4/1998		165.74				94,000	570	1,500	2,100	15,200	<2500	5.5	-		ingeringspringensiet fraudsbereiten
5/28/1998		16574													
12/30/1998		165.74	15.48		150.26	120,000	460	2,300	2,200	15,000	150	**	~~	**	tarrator mir emineritatori elementamente.
2/2/1999		165.74	18.19		147.45	82,000	450	2,200	3,700	26,000	3500				
5/10/1999		165.74	15.62	undsmukšendičilis) 	150,12	28,000	740	1,800	1,100	5,800	<25				. A 1 Say (Carrier of Foreign College
8/24/1999		165-74			147:53	75,000	530	1,400-	3200	21,000	150				
11/3/1999		165.74	18.71		147.03	70,000	600	1,300	3,600	20,500	750			-	promote and the entry is a construction of the dependent of the entry of \$10 4 dead
3772000		165.74	19,37		146.37	7,000	1,600	1,200	2,600	6,600	120				
4/21/2000		165.74	-				-		-		**			-	e
7/31/2000		165:74													
11/20/2000		165.74	17.42		148.32	1,300,000	1,400	1,700	20,000	16,000	5,700		-	-	

Table 1. Summary of Ground-Water Monitoring Data: Relative Water Elevations and Laboratory Analyses

Station #11132, 3201 35th Ave, Oakland, CA

		1						Concentra	tiane in fir	o/1.)					
		TOC	Depth to	Product	Water Level Elevation	GRO/		Concentra	Ethyl-	Total		(mg/L)			
Well and		Elevation	Water	Thickness (feet)	(feet msl)	TPHg	Benzene	Toluene	Benzene	Xylenes	мтве	DO	Lab	pН	Comments
Sample Date	P/NP	(feet msl)	(feet bgs)	(rect)	(teet mar)										
MW-8 Cont.															_
2/18/2001		165.74	-			-			—— Системення положения	 				- 19740378##	c e
6/7/2001		165,74													
9/5/2001	***************************************	165.74	21.45	0.04	144.29					-			- 		
11/30/2001		165.74	- IB31		147,43										e e
12/6/2001	e-d	165.74			454443443454445444						80.4				
2/20/2002		165 74	1402		151.72	20,000	163		403	3,810	2,520				
6/20/2002		165.74	17.56		148.18	28,000	466	141	962	5,850	2,520 11,200				
9/11/2002		165.74	1945		146 29	190,000	1,500	670	4500	23,000	31				
11/12/2002		165.74	19.15		146.59	420	6.4	2.9	16	110					
1/29/2003		165.74	15 02		150.72	200,000	810	\$500	2,000	11,000					
5/22/2003		165.74	15.07		150.67		860	- 300	2100	9.600	46				
6/24/2003		165.74	795		147.79	43,000	690	230	1,800	15,000	2,100				: Hymero Champannandan-1975
7/28/2003		165.74	19.45	-	146.29 146.34	62,000	1	1							0.
8/12/2003		165.74	19.40	<0.01	146.40										0
9/12/2003		165.74	19.34	 	146.40	8.800	500		530	930	1,700		SEQM		0p
11/18/2003		165.74	i8.80	<0.01 <0.01	152.92	32,000	840	360	1,000	7,100	110		SEQM	6.6	1
02/23/2004	P	165.74	12.82 18.87	<0.01	146.87	42,000	570	230	1700	8,400	2.000		SEÇM	7.0	
05/04/2004	P	165.74	19.37		146.37			-	_					-	
08/04/2004		165.74	19.57		146 TA										
09/22/2004	NP P	165.74	16.58		149.16	11,000	790	61	1,000	830	74	-	SEQM	7.3	t t
11/10/2004	- ne namena	165.74	10.50		152.89	38,000	1,300	390	2,300	7,900	₹50		SEOM	7.2	
02/15/2005	P	165.74	12.22		153.52	31,000	1,000	360	2,500	7,500	<50		SEQM	6.5	
05/16/2005 08/17/2005	P	165.74	17.80		147.94	60,000	\$40	240	2,500	8,600	<50%		SEOM	6.7	
11/18/2005	P	165.74	21.02		144.72	33,000	340	120	1,400	4,900	140		SEQM	6.9	
02/07/2006	lisip.	165.74	10.73		155 01	5,700	94	27	260	820	7.5		SEOM	6.6	
5/19/2006	i i i i i i i i i i i i i i i i i i i	165.74	13.89		151,85	40,000	1,100	320	2,900	6,000	<25		SEQM	6.6	
8/23/2006	In Fig.	65-74	18.85		146.89	21,000	520	150	1,800	6,300	82		ТАМС	in the series	
11/15/2006	P	165.74	18.75		146.99	3,300	81	<25	130	430	110	0.81	TAMC	6.91	
	 		 							1					
MW-9				1		1	I	I	1	ı	1	1	1	'	•

Table 1. Summary of Ground-Water Monitoring Data: Relative Water Elevations and Laboratory Analyses

Station #11132, 3201 35th Ave, Oakland, CA

			D -15-45	Product	Water Level			Concentra	tions in (µ	g/L)					
_		TOC	Depth to Water	Thickness	Elevation	GRO/			Ethyl-	Total		(mg/L)			
Well and		Elevation	(feet bgs)	(feet)	(feet msl)	TPHg	Benzene	Toluene	Benzene	Xylenes	MTBE	DO	Lab	pН	Comments
Sample Date	P/NP	(feet msl)			` '										
MW-9 Cont.		(Ross	HOOR	GRADI	LEM!							1			
3/7/1991		166.20	16.79		149.41	7.1	220	4	2.4	2,400		 Emercentin	 Persengualiti	 Telian(195)	
4/1/1991		166.20	12.89		i53 31	12,000	2,000	2,600	360	1,600					
6/27/1991		166.20		STATE OF THE PROPERTY OF THE PARTY OF THE PA		3,600	520	400	85	310				}	
9/27/1991		166.20				3.2	720	150	50	180					
12/18/1991		166.20		-		••	2.5	1.1	0.3	5.8	ersennebelinen				
7/3/1992		166.20	18.89		147.31	5.700	17,000	840	230	800					
10/5/1992		166.20	20.52	••	145.68	1,400	440	17	14	100					
17/13/11993		166,20				11,000	1,200	1,600	330	1,300					
1/13/1993		166.20	12.92		153.28	11,000	1,200	1,700	340	1,400					
4723/1993		166.20	14 08		152:12	24,000	2,800	4,500	730	3,400					c
7/12/1993		166.20				10,000	1,200	900	310	1,200		ulaman			
7/12/1993		166.20	j 8 44		147.76	13,000	1,400	1,100	360	1,400					
10/21/1993		166.20	21.81		144.39		-								
1/21/1994		166.20	19.28		146.92				1.200	8,200	740				c,d
4/20/1994	-	166.20	-			45,000	2,700	6,800	1,200	7,900	768				
4/20/1994		166,20	1972		46.48	43,000	2,800	6,800						-	Emagatinisms)
8/1/1994		166.20	20.18		146.02										
12/23/1994		166.20	14722		151.98							H Hiberens		— —	in different-manifeliari (45 meta-manifes (47 meta-
1/26/1995	T -	166.20	11.85		154.35 147.87										
6/8/1995		166.20	18.83									-			En RICHARD TERMINATION OF THE PROPERTY OF THE
8/22/1995		166.20	19.95	ungasyonalasyan	146.25										
10/27/1995		123 4 : : 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -	20,88		in lenimaniman masar						2 1511: ESHIVATANUT 	- AD 19202-00-0		_	440 F778 7497 F Outman 1447 F V
1/25/1996		166.20	13.84		152.36										
4/19/1996		166,20	hill albant it menter erretten er eine er errer		142.26					######################################			10 110 31 10 111 110	**	AMM 0 2472 131 C 0 74 74 74 74 74 74 74 74 74 74 74 74 74
7/23/1996		166.20	18.84		147.36 146.29										
11/11/1996		16620	19:91						######################################	-			***		
1/21/1997	-	166.20	12.93		153.27										
4/29/1997		166.20	JB 03	01	148117	78.000		3,600	3,100	20,600	<5000	5.5		_	The state of the s
4/30/1997	ane sengaras	166.20	ta managanayanah		146.64	110,00		5,400	2,300	1 18,800	₹500	5.1			
8/21/1997			19.56	0.01	145.61	59,000	****	1,700	2,200	nig ilim tilmua	ini didinananana	4.5	-	-	
11/5/1997	-	166.20	20.59	0.01	143.01	39,000	1	1 7	1	1	t	,	•	•	

Table 1. Summary of Ground-Water Monitoring Data: Relative Water Elevations and Laboratory Analyses

					Water Lauri			Concentra	tions in (µ	g/L)					
		TOC	Depth to	Product Thickness	Water Level Elevation	GRO/	<u> </u>	Concent	Ethyl-	Total		(mg/L)			
Well and		Elevation	Water (fort her)	(feet)	(feet msl)	TPHg	Benzene	Toluene	Benzene	Xylenes	MTBE	DO	Lab	pН	Comments
Sample Date	P/NP	(feet msl)	(feet bgs)	(1001)	((()))		1								
MW-9 Cont.			1												
2/3/1998		166.20	10.56		155.64	55,000	490	1,200	1,400	10,200	<1000	4,9	 	usiama	
5/28/1998		166.20				53,000	290	830	1,400	10,500	₹500				
5/28/1998	######################################	166.20	14.21		151.99	41,000	250	1,200	1,500	11,400	<250	3.8			
12/30/1998		166:20	is.61		150.59	83,000	860	1,300	2,400	21,000	180				
2/2/1999		166.20	12.33	**	153.87	75,000	530	960	1,900	17,000	<50				
5/10/1999		166.20	15.67		150.53	22,000	600	1,500	1,100	4,400	72			HEUGH	
8/24/1999		166.20	19.10		147.10	85,000	850	1,300	1,700	20,000	<250				
1173/1999		166.20	19:58		146 62	72,000	700	780	14900	19,000	S 50				
3/1/2000		166.20	13.19		153.01	34,000	78	490	1,100	8,200	63 550				
4/21/2000		166.20	14/29		15 91	55,000	260	920	1,500	16,000	ing property and the second				
7/31/2000		166.20	15.01		151.19	1,200,000	- CONTRACTOR CONTRACTOR	6,300	15,000	120,000	1,600				
11/20/2000		166:20	18.23		147,97	320,000	3,500	3,000	5,00D	40,000	3.900 121				
2/18/2001		166.20	13.14		153.06	32,000	290	417	1,180	10,400 17,300	121 223				
6/7/2001		-166.20	770		148 79	96,000	421	704	2330	8, 9 40	310				
9/5/2001	**	166.20	20.56		145.64	39,000	445	323	1,240	14,200	285				
11/30/200		166.20	17.42			60,000	1910	586 122	1,890 897	2,650	293				
2/20/2002		166.20	13.87	-	152.33	14,000	64	122	1.100	5.670	208				
6/20/2002		=166.20	18,72		147 98	29,000	(04 H11)712417H20	680	3,600	23,000	<2500				A MARINE CONTRACTOR OF THE CON
9/11/2002		166.20	20.27	 	145.93	230,000	1,400 5,8		7,000	160	21				
11/12/2002		166.20	19,40		146,80	840									j ,n
1/29/2003		166.20	14.30	0.1	151.90	23,000		250	1000	2 900	250				
5/29/2003		The Part of the State of Service	1576		151.04	23,000						######################################			e
6/24/2003	_	166.20			146.65	1,500,00		2500	9,800	79.000	2500				
7/28/2003		THE PERSON NAMED IN COLUMN TWO IS NOT THE OWNER.	19.55	<0.01	146.60					::::::::::::::::::::::::::::::::::::::	Piking the street of the stree		eli (Staniolation)		o,t
8/12/2003		166.20	19.60	<0.01	146.60										o.t r
9/12/2003		166.20	19,60	<0.01	147.22	19.000		18	690	2,400	45		SEQM	6.8	о,р
11/18/2003	P	166.20	18.98	<0.01 <0.01	147.22 150.29	91,000		440	2200	13,000	250		SEOM	68	
02/23/2004	P		18,91		148.09	39,000		44	1,100	4,200	<25		SEQM	6.9	1
05/04/2004	P	166.20	18.11	<0.01	***************************************				1						
08/04/2004		166:20	18,90		146.51					-				-	
09/22/2004	NP	166.20	19.69	-	140.51	1	ì	l	į	ı	t	1.	•	•	•

Table 1. Summary of Ground-Water Monitoring Data: Relative Water Elevations and Laboratory Analyses

	-			·		·········		Concentra	tions in (n	g/1.)					
		тос	Depth to	Product	Water Level Elevation	GRO/		Concentra	Ethyl-	Total		(mg/L)			
Well and		Elevation	Water	Thickness (feet)	(feet msl)	TPHg	Benzenc	Toluene	Benzene	Xylenes	MTBE	DO	Lab	рĦ	Comments
Sample Date	P/NP	(feet msl)	(feet bgs)	(icci)	(1000 1000)										
MW-9 Cont.													arou.	7.3	
11/10/2004	NP	166.20	16.95		149.25	31,000	300	<50	1,100	3,800	<50	 10:00:00:00:00:00:00:00:00:00:00:00:00:0	SEQM		
02/15/2005	P	166.20	12,95		153 25	19,000	200	≤50	720	2,000	₹50		SEQM	7.3 6.7	
05/16/2005	P	166.20	12.53	-4	153.67	17,000	99	15	770	2,500	<10	-	SEQM SEQM	6.8	
08/17/2005	P	166.20	18.03		148.17	28,000	160	26	7,000	2,700	19		SEQM	7.1	
11/18/2005	P	166.20	19.04		147.16	12,000	98	<5.0	410	510	19 12/250		SEQM	6.9	
02/07/2006	P	166.20	10.95		155.25	18,000	110	8.7	770	1500					e
5/19/2006		166.20	-					-	-	6,200	 		TAMC	7.5	
8/23/2006	HEP.	166,20	1891		147:29	28,000	84		1,6004	370	26	0.92	TAMC	6.88	
11/15/2006	P	166.20	18.60		147.60	8,200	44	<25	190	370	20	1 0.72	111110		
MW-10														and the second	and a statement of the
		167.01	8 09		148 92	16	120	001	32	230					
3/7/1991 4/1/1991		167.01	13.92		153.09				_	_		-			THE REPORT OF THE PROPERTY OF
4/1/1991 6/27/1991		167.01				12,000	7,300	500	150	300					
9/27/1991		167.01				57	12,000	7,200	1,400	4,600				 ###################################	
12/18/1991		167.01				5.3	2,500	120	36	79					
7/3/1992		167.01	19.92	***************************************	147.09	8,600	5,100	1,300	180	690	 	 =============			
10/5/1992		167.01	21 92		145.09										
1/13/1993		167.01	14,43	-	152.58	-				 					
4/23/1993		167.01	15.26		151.75										
7/12/1993		167.01	19.78	-	147.23	_		-		— m ::::::::::::::::::::::::::::::::::::				m 1515	
0/2[/]993		167.01	22,90		14.1										
1/21/1994		167.01	20.25	***	146.76	-		 15 ************************************		- 14.000	- 1577 -				
4/20/1994		167.01	2074		146.27	100,000	12,000	ug lummandie	2,400	19.000					HE REPRESENTATION OF THE PROPERTY OF THE PARTY OF THE PAR
8/1/1994		167-01	22.00		145.01	-			 TO UNION SINGE						
12/23/1994		167.01	16.08		150.93										
1/26/1995	-	167.01	13.68	TO SECURITION OF THE PARTY.	153.33										
6/8/1995		167. 0 E	19,08		147,93										
8/22/1995		167.01	20.73		146.28										
10/27/1995		167.01	21,69		145.32								-		tern freite finite in 10 is bie er een beregkent in feet vereit en feet tot dat bei en een
1/25/1996	-	167.01	15.05	-	151.96			1 -	1 -	l .	1	ı	\$	1	1

Table 1. Summary of Ground-Water Monitoring Data: Relative Water Elevations and Laboratory Analyses
Station #11132, 3201 35th Ave, Oakland, CA

		тос	Depth to	Product	Water Level			Concentra	tions in (µ;	g/L)					
Well and		Elevation	Water	Thickness	Elevation	GRO/			Ethyl-	Total		(mg/L)			
Sample Date	P/NP	(feet msl)	(feet bgs)	(feet)	(feet msl)	TPHg	Benzene	Toluene	Benzene	Xylenes	MTBE	DO	Lab	рH	Comments
MW-10 Cont.															
		167.01	16.26		150.75										
4/19/1 996	 	167.01			146.83										
7/23/1996		167,01	20.18		145.81								ADICHTHURA 		
11/11/1996		167.01	(*************************************	- 	153,35							HIMIL			
1/21/1997		167.01	13.66 18.71		148.30							-			HTM HOTEL HOUSE HE STATE OF THE
4/29/1 997	-	167.01		14194988888888	148.50	170.000	9,700	38.000	4.700	30500	\$5000	3.6			
4/30/1997		167.01	20.19		146.82	170,000	9,500	35,000	4,300	27.100	<5000	5.3		 ruthanko:	tentur international international productions
8/21/1997	 musikatiii	167.01	20.19 50 52		146.49	80,000	3,800	12,000	2700	115.700	×500	244			
11/5/1997 2/3/1998		167.01	10.62		156.39									-	a i i i i i i i i i i i i i i i i i i i
2/4/1998	_ 0/200723116	167.01				72,000	500	1300	1 700	12,000	<1000	5.1			
5/28/1998		167.01	15.46		151.55	220,000	3,200	24,000	5,200	43,000	<1000	4.8			additioning to employed by any \$113 to Coban child has be group recommended.
12/30/1998		167.01	16.65		150.96	110,000	3,500	14,000	5,800	50,000	### # 5016.1				
2/2/1999		167.01	14.58		152.43	74,000	1,000	2,800	1,000	26,000	860	 			AND SHALL BUT COMPANY OF THE PARK OF THE P
5/10/1999		167.01	15.72		151 29	81,000	2,800	2,800	3,000	17,000	220				
8/24/1999		167.01	19.85	EEEEEEE	147.16	54,000	3,500	3,800	1,500	9,100	<250	-		_	
11/3/1999		167.01	20,00		147.01	30,000	3,000	3,500	1,200	5,000					
3/1/2000		167.01	14,62	######################################	152.39	62,000	320	1,200	1,100	26,000	4,400		- -	-	
A/21/2000		167.01	1546		15155	88,000	2700	7,400	3,700	35,000	2,400				
7/31/2000		167.01					***		-				-		e
11720/2000		167.01	1874		148727	78,000	3 800	5,500	2.800	13,000	450				
2/18/2001		167.01	14.10	Listerial Distriction (1914)	152.91	39,000	1,050	1,160	1,550	14,700	4,180				- podere priming property of the property of t
6/7/2001		167.01	18.78		148/23	76,000	2,460	2,840	3,330	20,700	635				
9/5/2001		167.01	21.40	0.01	145.61	25,000	2,510	2,070	1,090	4,540	189				4
11/30/2001		167.01	18.50		14851	100,000	2,480	5720	3,890	22,800	328				
2/20/2002		167.01	14.39	This is the contracting and property and pro	152.62	49,000	2,170	3,070	1,960	12,300	1,090	 6. 0.49470.2127			gunggenungningnintrinutaningstatibilist
6/20/2002		167.01	18.80		14821	44,000	2,040	3,050	1,690	8,430	224				
9/11/2002		167.01	20.52		146.49	28,000	1,200	2,700	1,400	6,800	<250		-	-	narra kontrala (jalja 1465 meta) a dida Marika ili dida.
11/12/2002		187.01	20.37	0.07	146.64										
1/29/2003		167.01	16.33	0.03	150.68	-				-				 c/ematig	j,n
5/22/2003		167:01	1652		150.69.	13,000	2,100	850	630	1,600	300				(Notice the companies of the companies o
6/24/2003		167.01	18.73	0.04	148.28	-	-	-	-	-			-	-	0

Table 1. Summary of Ground-Water Monitoring Data: Relative Water Elevations and Laboratory Analyses
Station #11132, 3201 35th Ave, Oakland, CA

	,	тос	Depth to	Product	Water Level			Concentra	tIons in (µ	g/L)					
Well and		Elevation	Water	Thickness	Elevation	GRO/			Ethyl-	Total		(mg/L)			
Sample Date	P/NP	(feet msl)	(feet bgs)	(feet)	(feet msl)	ТРНд	Benzene	Toluene	Benzene	Xylenes	MTBE	DO	Lab	pH	Comments
MW-10 Cont.															
7/28/2003		167.01	20.39	0.04	146.62							-			j
8/12/2003		167.01	20.43	30.01	146.58										
9/12/2003		167.01	20.41		146.60	,990m)+H152376 —		— — — — — — — — — — — — — — — — — — —	######################################		-			_	0
11/18/2003	P	167.01	19.55	₹0,01	147,46	9,900	2,200	530	320	860	# \$ 50		SEQM	6.8	9,0
02/23/2004	KORDENSKERSK P	167.01	15.45	< 0.01	151.56	46,000	1,900	2,000	1,800	9,000	180	_	SEQM	6.7	1
05/04/2004	e P	167.01	18.81	₹0.01	148:20	35,000	3,100	3,600	1,400	5,600	25		SEOM	7.1	
08/04/2004		167.01	18.90		148.11	-	-								
09/22/2004	NP	167,01	20:60		14641										
11/10/2004	b International	167.01	17.95		149.06	9,800	470	91	450	1,700	230	_ 	SEQM	7.3	t Investmentententententententen
01/13/2005		167.01	1221		154.80										
02/15/2005	P	167.01	14.19		152.82	30,000	510	330	1,800	7,200	77 		SEQM SEQM	7.2	
05/16/2005	P	67:0L	19.85		153 16	37,000	540	730	2,100	9,200	<50		SEQM	6.7 6.7	
08/17/2005	P	167.01	19.01	e-	148.00	15,000 12,000	1,100	420 240	1,200 550	4,100 1,300	-30 	.i	SEQM	6.8	
11/18/2005		167.01	19,95		147.06	i sente commu	1,200 340	580	1,300	4,500	73		SEQM	6.8	
02/07/2006	P mmonents	167.01	12.28		154.73 151.89	22,000 40,000	540 690	430	2,600	4,500	225		SEQM	6.9	
5/19/2006	P	167.01	15.12 20.00		19.097	13,000	1,500	540	1,200	3,000	<10		TAMC	6.97	
8/23/2006 11/15/2006	P P	167.01 167.01	19.84		147917	3,800	700	22	67	180	34.54	0.65	TAMO	6.78	
Significant Administration of		19/19/19			Nicolatine in manuscrip		: Etti (Hillinestera		1	· · · · · · · · · · · · · · · · · · ·	50000000000000000000000000000000000000				
QC-2			***************************************							10.5		1			f
10/5/1992		168.01				<50	<0.5	<0.5	<0.5	<0.5					
1/13/1993		168.01				50	305	<0.5 <0.5	<0.5 <0.5	<0.5					(#####################################
4/23/1993		168.01		 Europatantantantantan		<50 <50	<0.5 ≪0.5	20.5 20.5	-0.5 	<0.5					
7/12/1993		168.01				<50	<0.5	<0.5	<0.5	<0.5					i santangan kanangan di santangan di santangan di santangan di santangan di santangan di santangan di santanga I
10/21/1993		168.01				<50 450	<0.5 <0.5		20.5	10.51					
1/21/1994		168.01				<50	<0.5	<0.5	<0.5	<0.5	 				L THE STREET STREET STREET STREET
4/20/1994		168.01 168.01				₹50		205	*05	65					
12/23/1994 1/26/1995		168.01				<50	<0.5	<0.5	<0.5		-	-			f
6/8/1995		168.01				 	<0.50	<0.50	<0.50	1 210					
200001772		168.01				<50	< 0.50	<0.50	<0.50	<1.0	<5.0	-	**************************************	-	d,f

Table I. Summary of Ground-Water Monitoring Data: Relative Water Elevations and Laboratory Analyses
Station #11132, 3201 35th Ave, Oakland, CA

		70 6	Duralita	Product	Water Level			Concentra	tions in (μ	.g/L)					
		TOC	Depth to Water	Thickness	Elevation	GRO/	<u> </u>		Ethyl-	Total		(mg/L)	:		
Well and	D/MD	Elevation (feet msl)	(feet bgs)	(feet)	(feet msl)	TPHg	Benzene	Toluene	Benzene	Xylenes	MTBE	DO	Lab	pН	Comments
Sample Date	P/NP	(leet mai)	(icer nga)	(100.7)											
QC-2 Cont.															r
10/30/1995		168.01			**	<50	<0.50	<0.50	<0.50	<1.0	<5.0		 :::::::::::::::::::::::::::::::::::		
1/25/1996		168.0				<50	<0,50	<0.50	\$0,50	Miliamit Cressed	\$5.0				
4/19/1996		168.01	**************************************			<50	<0.5	<1	<1	<1	<10			-	
RW-1															
	rgaramenti (i														
7/9/1990		168.01									 AKB-19110751719-9114	-		_	
12/21/1990		168.01			- 150.39										
3/7/1991		168.01	17.62		153.61					<u> </u>		-		-	Star de la casa de la
4/1/1991	-	168,01	14.40												
6/27/1991		168.01									-			-	7 Carl Parlament / 257 / 1 4 Toronto
9/27/1991	—	168.01													
12/18/1991		168.01			147.35				 			—	***	-	t
7/3/1992		168.01	20.66		144.67										
10/5/1992	i i kalibutan		23:34 16.59		151.42								-	-	7.2.2.2.2.2.2.2.2.2.2.2.2.2.2.2.2.2.2.2
1/13/1993	-	168.01 168.01	10.59		151.84										
4/23/1993			20.18		147.83							_		-	
7/12/1993	 :::::::::::::::::::::::::::::::::::	168.01 168.01	20.16		14231										
10/21/1993			21.24		146.77		_	-		-				-	THE PARTY OF THE P
1/21/1994		168.01 168.01	32.20		1358										
4/20/1994	i printin	168.01	21.70		146.31	29,000	580	950	300	7,800	1,200	1.1	-	••	d
8/1/1994		ur larger en	21.70 		151,99	1,300	25	8.8	14	69	616	1.8			
12/23/1994		168.01	13.78		154.23	<50	<0.5	<0.5	<0.5	<1	-		-		
1/26/1995						 ₹50	₹0.5	1 2015	20.5	SI.					0
1/26/1995		168.01	20.05		147.96	1,300	130	<1.0	<1.0	36	-	-			
6/8/1995		168.01				2.800	210	9.3	43	250	25				
8/22/1995		168.01	21.74		146.27	3,300	230	13	4.9	280	<25	6.6			d
8/22/1995		168.01			13601										
10/27/1995			32,00			230	1.4	<1.0	0.1>	<2.0	650	6.9	-		
10/30/1995		168.01 168.01				240	1.6	i di	S TO	20	630				
10/30/1995			15.41		152.60	15,000		930	330	2,500	5,300		-		
1/25/1996	••	168.01	17.71		1	1	ŧ	1	•	•	•	•			

Table 1. Summary of Ground-Water Monitoring Data: Relative Water Elevations and Laboratory Analyses
Station #11132, 3201 35th Ave, Oakland, CA

				D-n-d-n-t	Water Level	Concentrations in (µg/L)									
	İ	TOC	Depth to Water	Product Thickness	Elevation	GRO/			Ethyl-	Total		(mg/L)			
Well and	P/NP	Elevation (feet msi)	(feet bgs)	(feet)	(feet msi)	ТРНд	Benzene	Toluenc	Benzene	Xylenes	MTBE	DO	Lab	pН	Comments
Sample Date	1/111	(ICCI III3I)	(tout aga)												
RW-1 Cont.								·			15.000				c
4/19/1996		168.01		••		33,000	5,600	3,200	1,700	8,800	15,000				
4/19/1996		168.01	16.83		151/18	35,000	5,500	3,300	1,700	9,400	14,000	7,6			
7/23/1996		168.01	20.76		147.25	46,000	3,600	2,300	900	5,100	36,000	7.4			
7/23/1996		168,01				47,000	9,700	2,500	930	5500	35,000				c
11/11/1996		168.01	••	•••		31,000	2,900	1,000	860	4,600	22,000 22,000	- 83			
11/11/1996		168.01	21.73		14628	34,000	3,000	1200	880	4,600					c
1/21/1997		168.01	••			270	42	17	2.7	36 34	1,500 1,500	61			
1/21/1997		168.01	1420		153.81	260	40	16				5.3			
4/29/1997		168.01	19.15		148.86	32,000	3,100	590	1,300	6,000	46,000 9,500	 45		-	
8/21/1997		168.01	20.67		147.34	7,600	730	58	370	1,780	56,000	4.5			
11/5/1997		168.01	21.01	a play transport and a late of the transport of the late of the la	147.00	39,000	2,300	86	1,300	3,840 161	3,200				
2/3/1998		168.01	10:68		157.53	3,400	111		29	305	2,700	4.3			
5/28/1998		168.01	15.55	## 200000000000000000000000000000000000	152.46	2,000	90	15 	60 		2,700				
12/30/1998		168.01	1735		150.66				2,000	3,200	51000/78000		_		g g
2/2/1999	-	168.01	14.58		153.43	82,000	2,300	120 88	2,000	660	61,000				
5/10/1999		168.01	16,00		52-01	15,000	620	170	2,200	2,900	37,000				
8/24/1999		168.01	20.00		148.01	52,000 17,000	1,400 2,500	86	1,500	970	54,000				
11/3/1999		168.01	20.39			17,000	580	78	790	1,100	13,000	Mahibiri ••		a: Lametier	To the state of th
3/1/2000		168.01	12.97		155.04	31,000	2,100		1400	1.100	39,000				
4/21/2000		168.01	1602		151.99 146.12	47,000	1,300	170	2,700	2,300	30,000	-	######################################	9 1507000	I Mitted by the control of the contr
7/31/2000		168.01	21,89		148.86	47,000									K K
11/20/2000		168.01	19.15		152.66	14,000	589	89	600	712	13,000				The Company of the Control of the Co
2/18/2001		168.01	15.35		148.92	28.000	1,140	682	504	2530	19,100				
6/7/2001		168.01	19.09		145.95					11. Suningud 32.11 —					j
9/5/2001		168.01	22.06	0.02	148.48	20,000	405	39.4	545	740	8260				
11/30/2001		With Assertance and Assertance and a	1953			13.000	469	11 12 17 17 18 19 19 19 19 19 19 19 19 19 19 19 19 19	434	655	7,240	544)(c)(c)(d)			el e avazzan hung poderderderder de charle (1,137 menters a servició en 1,137 menters en 1,
2/20/2002	-	168.01	15.99		152.02 148.70		407							h#	
6/20/2002		168.01	19,31	HI MENINGER VENEZONIONE	146.94									- C	j
9/11/2002	-	168.01	21.07	0.03	140.94			er correct or traces							
11/12/2002		168.01	20.92		151.70					970 Minister (1935) 77 	**		-		j,n
1/29/2003		168.01	16.31	0.04	131.70	1	1		i	1	1	I	1	1	•

Table 1. Summary of Ground-Water Monitoring Data: Relative Water Elevations and Laboratory Analyses
Station #11132, 3201 35th Ave, Oakland, CA

			<u> </u>			Concentrations in (µg/L)									
		тос	Depth to	Product	Water Level	0001		Concentro	Ethyl-	g/L) Total	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	(mg/L)			
Well and		Elevation	Water	Thickness	Elevation	GRO/	Benzene	Toluenc	Benzene	Xylenes	MTBE	DO	Lab	рĦ	Comments
Sample Date	P/NP	(feet msl)	(feet bgs)	(fect)	(feet msl)	TPHg	Denzene	Turnenc	Benzene	11,10,000					
RW-1 Cont.															_
5/22/2003		168.01	16.68	**	151.33		_						 	 PETABOLS	j,t angnamaganggggggggggggggg
6/24/2003		168.01	19.76	0.07	148,25										•
7/28/2003	***	168.01	21.04	0.04	146.97	-	-					-			j mananaganaganaganagan
8/12/2003		168.01	51 41	30.01	46.60										
9/12/2003		168.01	21.10	0.07	146.91			-	-	-		**			Ö
t I//18/2003	P	768.01	20.10	₹0.01	(470)	12,000	770	\$50	320	250	6,100		SEQM	6.6	ŏ.p
02/23/2004		168.01	14.35		153.66		-		-	-					
		168.01	1958		148.43										
05/04/2004		168.01	22.05		145.96			••	-	***************************************				-	22 NO. NO.
08/04/2004			21/28	0.06	146.73										
09/22/2004	NP	168.01	18.56		149.45							-	-	-	
11/10/2004		168.01	(A) 18 18 18 18 18 18 18 18 18 18 18 18 18	i – Hoom	155:50										
01/13/2005		168.01	12.51		152.77					-					3 Straight annual of the straight strai
02/15/2005		168.01	15.24	0.03	152.77 15611										
03/07/2003		168.01	11.90	0.02										in in the state of	j
05/16/2005		168.01	14,39	 	153.62		a commente							i i	
08/17/2005		168.01	الاوا		148.10									-	b, j
11/18/2005		168.01	20.36	-	147.65			1	1						
02/07/2006		168.01	12.87		155,14				1						b
5/19/2006	-	168.01	15.87	0.04	152.17		 n messame	- 							
8/23/2006		168.01	2050	0.07	14750								1		b, j
11/15/2006	-	168.01	20.52	0.07	147.54									J	"""

SYMBOLS AND ABBREVIATIONS:

- -- = Not analyzed/applicable/measured/available
- < = Not detected at or above specified laboratory reporting limit

DO = Dissolved oxygen

DTW = Depth to water in ft bgs

ft bgs = Feet below ground surface

ft MSL = Feet above mean sea level

GRO = Gasoline range organics

GWE = Groundwater elevation measured in ft MSL

mg/L = Milligrams per liter

MTBE = Methyl tert-butyl ether

NP = Well not purged prior to sampling

P = Well purged prior to sampling

TOC = Top of casing measured in fi MSL

TPH-g = Total petroleum hydrocarbons as gasoline

µg/L = Micrograms per liter

SEO/SEOM= Sequoia Analytical/Sequoia Analytical Morgan Hill (Laboratories)

SPH = Separate phase hydrocarbons

FOOTNOTES:

- a = Casing elevations surveyed to the nearest 0.01 ft MSL.
- b = GWE adjusted assuming a specific gravity of 0.75 for free product (FP).
- e = Blind duplicate.
- d = A copy of the documentation for this data is included in Appendix C of Alisto report 10-024-10-001.
- e = Well inaccessible.
- f = Travel blank.
- g = EPA Methods 8020/8260 used.
- h = Unable to sample.
- i = A copy of the documentation for this data can be found in Blaine Tech Services report 010607-M-3. MTBE data for the January 13, 1993 and April 23, 1993 sampling events has been destroyed. No chromatograms could be located for MTBE data from wells MW-5, MW-6, and MW-7, sampled on October 21, 1993.
- j = Well not sampled due to presence of SPH and nature of the product.
- k = Could not purge and sample; waste drum full.
- I = Value represents the depth to product. Unable to determine depth to water, product disabled the interface probe.
- m = Discrete p[ak @ C6-7.
- n = TPH-g, BTEX, and MTBE analyzed by EPA method 8260 B beginning on 1st quarter 2003 aampling event (1/29/03).
- o = Groundwater samples are not collected during FP bailing event.
- p = Well not included in the monthly FP bailing program.
- g = Well not sampled in November 2003 due to the presence of a pile of gravel dumped over the well box.
- r = This sample was analyzed beyond the EPA recommended holding time. The results may still be useful for their intended purpose.
- s = MW-7 TOC elevation raised +0.47 ft during well repair on January 20, 2004.
- t = Sheen in well.


NOTES:


Beginning in the fourth quarter 2003, the laboratory modified the reported analyte list. TPH-g was changed to GRO. The resulting data may be impacted by the potential of non-TPH-g analytes within the requested fuel range resulting in a higher concentration being reported.


Beginning in the second quarter 2004, the carbon range for GRO was changed from C6-C10 to C4-C12.


Values for DO and pH were obtained through field measurements.


Note: The data within this table collected prior to April 2006 was provided to Broadbent & Associates, Inc. by Atlantic Richfield Company and their previous consultants. Broadbent & Associates, Inc. has not verified the accuracy of this information.


















LEGEND:



MONITORING WELLS

(140.52')

GROUND WATER ELEVATION

138.00'

GROUND WATER ELEVATION CONTOUR

-

DIRECTION OF GROUND WATER FLOW

FIGURE 2 GROUND WATER ELEVATION CONTOUR MAP

B P SERVICE STATION NO. 11132 3201 35TH AVENUE OAKLAND, CALIFORNIA

35TH AVENUE