3884 RTIN LUTHER KING JR. WAY OAKLAND, CA



TION SITE
NNER AT
THE END
)F THE
RIALS AND
S WITHIN
RT AND
OR
ED BY
THE


DMPLETELY
DMPLETELY
DB SITE,
ERSONS
THE
ID ACCESS
RMED.

DMPLIANCE SUT NOT ATIONAL CODES, ND ND DINANCES (ERNING

AND PAY TO WHICH ND IS

OF THE
BUT
E
BUT
S
AND
SIES
TO
ENSIONS
THE

XE OF VITO D AS PLETION **y**,



3884 Martin Luther King Jr. Way

APN# 012-0968-031 OAKLAND, CA PROJECT NO. 05-21

DATE	SET ISSUE
04-16-0	7 ISSUED FOR ENVIRONMENTAL REVIEW

CONTACT:

SERINA CALHOUN

(415) 777-0561 P (415) 777-5117 F

SCALE: AS NOTED

COVER SHEET

A0.0

ISTRUCTION.
FINISH IS
ADJACENT
TEXTURE.

NTRACT IS ER THAN

SHALL ES ON

SHALL OR

"TYPICAL" ND ARE

NAL SHALL

TIME FOR S WORK USE IN STS.

IS, OR ARCHITECT

R OR SED BY THE


UARANTEE FECTS OF NOD OF CE BY THE UCTION OR DF THE È IN HITECT'S CIENCIES RKMANSHIP OF ONE REPLACED OF THE NO L BE CTIVE

D AS

AWINGS

ER KING JR. WAY OAKLAND, CA

RENDERING



DRAWING INDEX

	ARCHITECTURAL
0.0A	COVER SHEET
A2.0	BASEMENT PLAN
A2.1	GROUND FLOOR PLAN
A2.2	FLOOR PLAN: 2
A2.3	FLOOR PLAN: 3
A2.4	FLOOR PLAN: 4
A2.5	FLOOR PLAN: 5
A2.6	FLOOR PLAN: 6
127	POOF PLAN

AREA MAP 44th 81 43rd St Rich St W Macarthur Blvd -33rd 8t trackhurst de 32nd St NORTH -SITE

CONTACT LIST

OWNER:

COTTER & COYLE, L.L.C. 2193 TRAFALGAR STREET OAKLAND, CA 94611 510/381-9706 510/259-9323 FAX

CONTACT: NEIL COTTER

ARCHITECT:

LEVY DESIGN PARTNERS

90 SOUTH PARK

SAN FRANCISCO, CA 94107

415/777-0561 415/777-5117 FAX

CONTACT: TOBY LEVY

SERINA CALHOUN

SURVEY:

HUMANN COMPANY, INC. 1021 BROWN AVENUE LAFAYETTE, CA 94549 925/283-5000 925/283-3578 FAX

CONTACT: ERIC HUMANN

3884 MARTIN LUTH 40 RESIDENTIAL UNITS,

-ABBREVIATIONS LEGEND AIR CONDITIONING -DETAIL REFERENCE NUMBER AC AIR CONDITIONING ADJUSTABLE A.F.F. ABOVE FINISH FLOOR ALUM. ALUMINUM ALT. ALTERNATE APPROX. APPROXIMATELY ARCH. ARCHITECT(URAL) A.C.T. ACOUSTIC CEILING TILE SHEET WHERE DETAIL IS LOCATED DIRECTION OF SECTION VIEW INTERIOR SECTION IDENTIFICATION/ TELEPHONE BACK BOARD BUILDING BLOCKING BOTTOM B.BD. SHEET WHERE SECTION IS LOCATED CENTER LINE CABINET CORNER GUARD SHEET WHERE ELEVATION IS LOCATED CHANGE CEILING CLOSET CLEAR CLG. CLOS. CLR. C.M.U. ELEVATION REFERENCE NUMBER CONCRETE MASONRY UNIT (101)DOOR SYMBOL CONCRETE MAS COLUMN CONCRETE CONNECTION CONSTRUCTION CORRIDOR CERAMIC TILE WINDOW SYMBOL CONST. WALL / FLOOR TYPE SYMBOL CTR. CENTER **ELEVATION DATUM** DETAIL DIAMETER DIMENSION DOWN DRAWING DOWN SPOUT CEILING HEIGHT X'-X" REVISION SYMBOL **EXISTING** EXISTING EACH ELEVATION ELECTRICAL ELEVATOR EQUAL EQUIPMENT EXPANSION EXPOSED EXTERIOR ROOF DRAIN **●** RD FLOOR DRAIN ● FD **©** GAS HOOK-UP ### HOSE BIB WALL-MOUNTED INCANDESCENT Ò FLOOR DRAIN FINISH FLOOR FLASHING FLUORESCENT FACE OF FINISH FACE OF STUD FIREPROOF FURRING F.D. Fin: SCONCE LIGHT FIXTURE WALL-MOUNTED COMPACT FLUORESCENT ф FLUOR. F.O.F. F.O.S. SCONCE LIGHT FIXTURE RECESSED INCANDESCENT LIGHT FIXTURE AT CEILING RECESSED COMPACT FLUORESCENT Ф GALVANIZED GENERAL CONTRACTOR GLASS LIGHT FIXTURE AT CEILING GRADE BD.GYPSUM BOARD SURFACE-MOUNTED COMPACT Ŷ FLUORESCENT LIGHT FIXTURE AT CEILING H.B. HOSE BIB COMBINATION EXHAUST FAN AND COMPACT **\bar{Q}** HC H.C **HANDICAPPED** FLUORESCENT LIGHT FIXTURE, RECESSED HOLLOW CORE HARDWARE HDWR. AT CEILING HOLLOW METAL HIGH POINT HOUR HGT. H.M. HP HR. SURFACE-MOUNTED FLUORESCENT STRIP LIGHT FIXTURE, CEILING-MOUNTED H.W. INSUL. INT. HOT WATER INSULATION/INSULATED INTERIOR (WITH LENGTH AS INDICATED) SURFACE-MOUNTED TRACK LIGHT FIXTURE. JAN. **JANITOR CEILING-MOUNTED** JT. JOINT (WITH LENGTH AS INDICATED) L.P. LOW POINT MAXIMUM MEDICINE CABINET MOTION DETECTOR MAX 2'X4' SURFACE-MOUNTED FLUORESCENT M.C. M.D. LIGHT FIXTURE WITH WRAP AROUND LENS MECHANICAL MINIMUM 1'X4' SURFACE-MOUNTED FLUORESCENT MTD. MTL. MOUNTED METAL LIGHT FIXTURE WITH WRAP AROUND LENS EMERGENCY LIGHT FIXTURE WITH BATTERY \otimes (N) N.I.C. NO.S. O.FF. OPP.S NEW NOT IN CONTRACT NUMBER NOT TO SCALE ON CENTER OFFICE PACK, CEILING OR WALL-MOUNTED EXIT LIGHT FIXTURE WITH BATTERY BACK-UP, CEILING OR WALL-MOUNTED (WITH DIRECTIONAL ARROWS AS REQUIRED) OPENING OPPOSITE DATE 0.T.B. OPEN TO BELOW (SD) CEILING-MOUNTED SMOKE DETECTOR M 203 PR. P-LAM. PTD. PLYWD. PAIR PLASTIC LAMINATE (G) GARBAGE DISPOSAL PAINTED PLYWOOD PRIVATE OFFICE

\$

ONE-WAY SWITCH,

MOUNTED AT +48" A.F.F., U.O.N.

GENERAL NOTES

GENERAL CONDITIONS: AIA DOCUMENT A201, GENERAL CONDITIONS FOR THE PERFORMANCE OF THE CONTRACT IS HEREBY INCORPORATED INTO THESE DRAWINGS AND SHALL BE CONSIDERED AS PART OF THE REQUIREMENTS FOR THE COMPLETION OF THE WORK.

EXISTING CONDITIONS: CONDITIONS SHOWN OF THE DRAWINGS ARE AS SHOWN ON THE ORIGINAL DRAWINGS AND AS OBSERVED ON THE SITE, BUT THEIR ACCURACY IS NOT GUARANTEED. THE CONTRACTOR SHALL VERIFY ALL DIMENSIONS AND CONDITIONS AT THE SITE. ANY DISCREPANCIES SHALL BE REPORTED TO ARCHITECT PRIOR TO PROCEEDING WITH THE WORK. NOTE: DIMENSIONS SHALL TAKE PRECEDENCE OVER SCALE OF THE DRAWINGS. 1986 1985.

PERMITS: THE CONTRACTOR SHALL OBTAIN AND PA ALL CITY AND/OR COUNTY FEES RELATING TO PROJECT, EXCEPTING THE GENERAL PERMIT, WHICH IS THE RESPONSIBILITY OF THE OWNERS' AND IS REIMBURSABLE TO THE G.C.

CODES: ALL WORK SHALL BE DONE IN COMPLIANCE WITH ALL APPLICABLE CODES, INCLUDING BUT NOT LIMITED TO: UNIFORM BUILDING CODES, NATIONAL ELECTRICAL, MECHANICAL, AND PLUMBING CODES, HEALTH DEPARTMENT REGULATIONS, FIRE AND SAFETY CODES, CITY AND/OR COUNTY ORDINANCES AND REGULATIONS AND OTHER CODES GOVERNING CONSTRUCTION.

SITE RESPONSIBILITY: IN ACCORDANCE WITH GENERALLY ACCEPTED CONSTRUCTION PRACTICES, THE CONTRACTOR WILL BE SOLELY AND COMPLETEL RESPONSIBLE FOR CONDITIONS ON THE JOB SITE, INCLUDING HEALTH AND SAFETY OF ALL PERSONS AND PROPERTY DURING PERFORMANCE OF THE WORK. CONTRACTOR TO LIMIT TRAFFIC AND ACCES TO THOSE AREAS WHERE WORK IS PERFORMED.

CLEAN UP AND REPAIRS: THE CONSTRUCTION SITE SHALL: BE MAINTAINED IN AN ORDERLY MANNER AT ALL TIMES WITH ALL DEBRIS REMOVED AT THE END OF THE EACH DAY. AT THE COMPLETION OF THE CONSTRUCTION REMOVE ALL EXCESS MATERIALS AND REFUSE FROM SITE. LEAVE ALL SURFACES WITHIN CONSTRUCTION: SITE FREE FROM DUST, DIRT AND STAINS. THE CONTRACTOR SHALL REPAIR OR REPLACE ANY SURFACES OR ITEMS DAMAGED BY CONSTRUCTION TO THE SATISFACTION OF THE ARCHITECT AND OWNER.

PATCHING: PROPERLY PREPARE SURFACES FOR RECEIVING THE SPECIFIED FINISHES INCLUDING PATCHING OF SURFACES ALTERED BY CONSTRUCTION ON PATCHED AREAS OR AREAS WHERE A FINISH IS NOT SPECIFIED, THE FINISH SHALL MATCH ADJACENT MATERIAL IN CONSTRUCTION, COLOR AND TEXTURE.


ALL WORK NOTED "N.I.C." OR NOT IN CONTRACT IS TO BE PROVIDED BY A CONTRACTOR OTHER THAN THE GENERAL CONTRACTOR.

"AL'GN" AS USED IN THESE DOCUMENTS SHALL MEAN TO ACCURATELY LOCATE FINISH FACES ON THE SAME PLANE.

"TYPICAL" AS USED IN THESE DOCUMENTS SHALL MEAN THAT THE CONDITION IS THE SAME OR REPRESENTATIVE FOR SIMILAR CONDITIONS THROUGHOUT, U.O.N.

DETAILS ARE USUALLY KEYED AND NOTED "TYPICAL" ONLY ONCE, WHEN THEY FIRST OCCUR, AND ARE REPRESENTATIVE FOR SIMILAR CONDITIONS ASTHROUGHOUT, U.O.N:A

SCHEDULE: UPON SUBMITTAL OF THE FINAL CONSTRUCTION COSTS, THE CONTRACTOR SHALL ALSO SUBMIT A CONSTRUCTION SCHEDULE INDICATING THE RECHIRED CONCEDITION TIME ECO



NECESSED INCANDESCENT LIGHT FIXTURE AT CEILING RECESSED COMPACT FLUORESCENT LIGHT FIXTURE AT CEILING SURFACE-MOUNTED COMPACT FLUORESCENT LIGHT FIXTURE AT CEILING COMBINATION EXHAUST FAN AND COMPACT FLUORESCENT LIGHT FIXTURE, RECESSED AT CEILING SURFACE-MOUNTED FLUORESCENT STRIP LIGHT FIXTURE, CEILING-MOUNTED (WITH LENGTH AS INDICATED) SURFACE-MOUNTED TRACK LIGHT FIXTURE, CEILING-MOUNTED (WITH LENGTH AS INDICATED) 2'X4' SURFACE-MOUNTED FLUORESCENT LIGHT FIXTURE WITH WRAP AROUND LENS 1'X4' SURFACE-MOUNTED FLUORESCENT LIGHT FIXTURE WITH WRAP AROUND LENS EMERGENCY LIGHT FIXTURE WITH BATTERY PACK, CEILING OR WALL-MOUNTED EXIT LIGHT FIXTURE WITH BATTERY BACK-UP, CEILING OR WALL-MOUNTED (WITH DIRECTIONAL ARROWS AS REQUIRED) $\Lambda^{\prime\prime} T^{\prime\prime}$ CEILING-MOUNTED SMOKE DETECTOR 14-161-GARBAGE DISPOSAL ONE-WAY SWITCH, MOUNTED AT +48" A.F.F., U.O.N. TWO-WAY SWITCH, MOUNTED AT +48" A.F.F., U.O.N. THREE-WAY SWITCH, MOUNTED AT +48" A.F.F., U.O.N. DUPLEX OUTLET. MOUNTED AT +15" A.F.F, U.O.N. DUPLEX OUTLET (WATERPROOF) MOUNTED AT +15" A.F.F, U.O.N.

MOUNTED AT +15" A.F.F., U.O.N.

MOUNTED AT +48" A.F.F., U.O.N.

MOUNTED AT +15" A.F.F., U.O.N.

TELEVISION CABLE JACK,

DOORBELL:

0

 \bigcirc

CLEAN UP AND REPAIRS: THE CONSTRUCTION SITE SHALL BE MAINTAINED IN AN ORDERLY MANNER AT ALL TIMES WITH ALL DEBRIS REMOVED AT THE END OF THE EACH DAY. AT THE COMPLETION OF THE CONSTRUCTION REMOVE ALL EXCESS MATERIALS AND REFUSE FROM SITE. LEAVE ALL SURFACES WITHIN CONSTRUCTION SITE FREE FROM DUST, DIRT AND STAINS. THE CONTRACTOR SHALL REPAIR OR REPLACE ANY SURFACES OR ITEMS DAMAGED BY CONSTRUCTION TO THE SATISFACTION OF THE ARCHITECT AND OWNER.

Marie Con PATCHING: PROPERLY PREPARE SURFACES FOR RECEIVING THE SPECIFIED FINISHES INCLUDING PATCHING OF SURFACES ALTERED BY CONSTRUCTION. ON PATCHED AREAS OR AREAS WHERE A FINISH IS NOT SPECIFIED, THE FINISH SHALL MATCH ADJACENT MATERIAL IN CONSTRUCTION, COLOR AND TEXTURE.

ALL WORK NOTED "N.I.C." OR NOT IN CONTRACT IS TO BE PROVIDED BY A CONTRACTOR OTHER THAN THE GENERAL CONTRACTOR.

"ALIGN" AS USED IN THESE DOCUMENTS SHALL MEAN TO ACCURATELY LOCATE FINISH FACES ON THE SAME PLANE.

"TYPICAL" AS USED IN THESE DOCUMENTS SHALL MEAN THAT THE CONDITION IS THE SAME OR REPRESENTATIVE FOR SIMILAR CONDITIONS THROUGHOUT, U.O.N.

DETAILS ARE USUALLY KEYED AND NOTED "TYPICAL" ONLY ONCE, WHEN THEY FIRST OCCUR, AND ARE REPRESENTATIVE FOR SIMILAR CONDITIONS STHROUGHOUT, U.O.N.


SCHEDULE: UPON SUBMITTAL OF THE FINAL CONSTRUCTION COSTS, THE CONTRACTOR SHALL ALSO SUBMIT A CONSTRUCTION SCHEDULE INDICATING THE REQUIRED CONSTRUCTION TIME FOR ALL SUBCONTRACTOR'S AND CONTRACTOR'S WORK AND A COST-BY-TRADE BREAKDOWN FOR USE IN SCHEDULING AND EVALUATING PAY REQUESTS.


SUBSTITUTIONS, REVISIONS, OR CHANGES MUST HAVE APPROVAL BY THE ARCHITECT PRIOR TO PROCEEDING WITH THE WORK.

DAMAGE: THE CONTRACTOR SHALL REPAIR OR REPLACE ANY SURFACES OR ITEMS DAMAGED BY CONSTRUCTION TO THE SATISFACTION OF THE ARCHITECT OR OWNER.

GUARANTEES: THE CONTRACTOR SHALL GUARANTEE
THAT THE PROJECT WILL BE FREE OF DEFECTS OF
WORKMANSHIP AND MATERIALS FOR A PERIOD OF ONE YEAR FROM THE DATE OF ACCEPTANCE BY THE OWNER. NO WORK DEFECTIVE IN CONSTRUCTION OR QUALITY DEFICIENT IN ANY REQUIREMENT OF THE DRAWINGS OR NOTES WILL BE ACCEPTABLE IN CONSEQUENCE OF THE OWNER'S OR ARCHITECT'S FAILURE TO POINT OUT DEFECTS OR DEFICIENCIES DURING CONSTRUCTION. DEFECTS OF WORKMANSHIP OR MATERIALS REVEALED WITHIN A PERIOD OF ONE YEAR FROM THE ACCEPTANCE SHALL BE REPLACED BY WORK CONFORMING WITH THE INTENT OF THE CONTRACT AT NO COST TO THE OWNER. NO PAYMENT, EITHER PARTIAL OR FINAL, SHALL BE CONSTRUED AS AN ACCEPTANCE OF DEFECTIVE MOBK.


COLUMN CENTERLINES (ALSO REFERRED TO AS GRIDLINES) ARE SHOWN FOR DIMENSIONAL PURPOSES. (REFER TO BASE BUILDING DRAWINGS FOR EXACT LOCATIONS.







3884 TIN LUTHER KING JR. WAY OAKLAND, CA

LEVY DESTIGN PAINT SON BAINT SON Francisco CA 94107








3884 Martin Luther King Jr. Way


> APN# 012-0968-031 OAKLAND, CA PROJECT NO. 05-21

DATE SET ISSUE
02-09-2007 FOUNDATION PERMIT SUBMITTAL
CONTACT:
SERINA CALHOUN
(415) 777-0561 P
(415) 777-5117 F
SCALE: 1/8" = 1'-0"


FLOOR PLAN BASEMENT


A2.0







RTIN LUTHER KING JR. WAY OAKLAND, CA









3884 Martin Luther King Jr. Way

APN# 012-0968-031 OAKLAND, CA PROJECT NO. 05-21

DATE	SET ISSUE
02-09-2007	FOUNDATION PERMIT SUBMITTAL
	
CONTAC	Т:
SERINA	A CALHOUN
(415) 777	-0561 P
(415) 777	
SCALE:	1/8" = 1'-0"

FLOOR PLAN GROUND FLOOR

A2 1