



ENVIRONMENTAL HEALTH SERVICES
ENVIRONMENTAL PROTECTION
1131 Harbor Bay Parkway, Suite 250
Alameda, CA 94502-6577
(510) 567-6700
FAX (510) 337-9335

September 15, 2014

Mr. Walter Merkle
MCG Investments LLC
123 Estudillo Avenue
San Leandro, CA 94577

Shirley J Davini & Dorothy D McGuire
123 Estudillo Avenue
San Leandro, CA 94577

Mr. Jon Braden
McGrath Steel Company
Address Unknown

Mr. David Davini
Loretta A McGrath Family Trust
Address Unknown

Subject: Request for Feasibility Study / Corrective Action Plan; Fuel Leak Case No. RO0000063;
(Global ID # T0600102099); McGrath Steel Company, 6655 Hollis Street, Emeryville, CA
94608

Dear Messrs. Merkle and Braden, and Meses. Davini and McGuire:

Alameda County Environmental Health (ACEH) staff has reviewed the case file for the above referenced site including the *Indoor Air Quality Monitoring Report*, dated July 18, 2014, and the *Second Quarter 2014 Groundwater Monitoring*, dated July 21, 2014. Both reports were prepared and submitted on your behalf by AllWest Environmental, Inc. (AllWest). Thank you for submitting the reports.

The *Indoor Air Quality Monitoring Report* found that concentrations of benzene, naphthalene, and carbon tetrachloride exceeded commercial indoor air Environmental Screening Levels (ESLs), which are generally considered safe, that were promulgated by the San Francisco Bay Regional Water Quality Control Board (RWQCB). The report also noted that the indoor air sample collected in closest proximity to the former UST location did not yield concentrations of benzene and naphthalene above indoor air ESLs, and concluded that other site vicinity sources may have contributed to the results. Additionally, carbon tetrachloride is not a contaminant of concern at the site (is not known to have been sourced from the site).

Based on the review of the case file and the referenced report ACEH requests that you address the following technical comments and send us the documents requested below.

TECHNICAL COMMENTS

- 1. Focused Site Conceptual Model and Data Gap Investigation Work Plan and Meeting Dates –**
Please prepare a Data Gap Investigation Work Plan to address the technical comments discussed in our November 8, 2013 directive letter (attached). Please support the scope of work in the Data Gap Investigation Work Plan with a focused SCM and Data Quality Objectives (DQOs) that relate the data collection to each LTCP criteria. For example please clarify which scenario within each Media-Specific Criteria a sampling strategy is intended to apply to.

Prior to submitting the work plan and SCM, ACEH would like to invite you to meeting in order to discuss the site and to resolve any questions that may arise. This is expected to expedite review of the final work plan and SCM submittal. ACEH requests notification of suitable dates and times for the meeting by the date identified below.
- 2. Semi-Annual Groundwater Monitoring –** Please convert groundwater monitoring of all site vicinity wells to a semi-annual basis, and continue analytical analysis for all chemicals of concern at the site. Please sample groundwater in the months of August and February of each year until otherwise arranged. Please include a table reporting the total volume of free-phase and groundwater removed during each

servicing of the free-phase passive skimmer (past and future) in these groundwater monitoring reports. Please submit semi-annual reports by the dates identified below.

TECHNICAL REPORT REQUEST

Please upload technical reports to the ACEH ftp site (Attention: Mark Detterman), and to the State Water Resources Control Board's Geotracker website, in accordance with Attachment 1 and the specified file naming convention below, according to the following schedule:

- **October 3, 2014** – Notification of Meeting Dates
File to be named: RO63_CORRES_L_yyyy-mm-dd
- **December 5, 2014** – Data Gap Investigation Plan and Focused Site Conceptual Model
File to be named: RO63_WP_SCM_R_yyyy-mm-dd
- **April 24, 2015** – Semi-Annual Groundwater Monitoring Report
File to be named: RO63_GWM_R_yyyy-mm-dd
- **60 Days After Work Plan Approval** – Soil and Groundwater Investigation Report
File to be named: RO63_SWI_R_yyyy-mm-dd
- **October 23, 2015** – Semi-Annual Groundwater Monitoring Report
File to be named: RO63_GWM_R_yyyy-mm-dd

These reports are being requested pursuant to California Health and Safety Code Section 25296.10. 23 CCR Sections 2652 through 2654, and 2721 through 2728 outline the responsibilities of a responsible party in response to an unauthorized release from a petroleum UST system, and require your compliance with this request.

Online case files are available for review at the following website: <http://www.acgov.org/aceh/index.htm>. If your email address does not appear on the cover page of this notification, ACEH is requesting you provide your email address so that we can correspond with you quickly and efficiently regarding your case.

If you have any questions, please call me at (510) 567-6876 or send me an electronic mail message at mark.detterman@acgov.org.

Sincerely,

Mark E. Detterman, PG, CEG
Senior Hazardous Materials Specialist

Enclosures: Attachment 1 – Responsible Party (ies) Legal Requirements / Obligations and Electronic Report Upload (ftp) Instructions

cc: Leonard Niles, AllWest Environmental, Inc, 530 Howard Street, Suite 300, San Francisco, CA 94105; (sent via electronic mail to: leonard@allwest1.com)

Dilan Roe, ACEH, (sent via electronic mail to: dilan.roe@acgov.org)
Mark Detterman (sent via electronic mail to mark.detterman@acgov.org)
Electronic File, GeoTracker

Attachment 1

Responsible Party(ies) Legal Requirements / Obligations

REPORT REQUESTS

These reports are being requested pursuant to California Health and Safety Code Section 25296.10. 23 CCR Sections 2652 through 2654, and 2721 through 2728 outline the responsibilities of a responsible party in response to an unauthorized release from a petroleum UST system, and require your compliance with this request.

ELECTRONIC SUBMITTAL OF REPORTS

ACEH's Environmental Cleanup Oversight Programs (LOP and SLIC) require submission of reports in electronic form. The electronic copy replaces paper copies and is expected to be used for all public information requests, regulatory review, and compliance/enforcement activities. Instructions for submission of electronic documents to the Alameda County Environmental Cleanup Oversight Program FTP site are provided on the attached "Electronic Report Upload Instructions." Submission of reports to the Alameda County FTP site is an addition to existing requirements for electronic submittal of information to the State Water Resources Control Board (SWRCB) GeoTracker website. In September 2004, the SWRCB adopted regulations that require electronic submittal of information for all groundwater cleanup programs. For several years, responsible parties for cleanup of leaks from underground storage tanks (USTs) have been required to submit groundwater analytical data, surveyed locations of monitoring wells, and other data to the GeoTracker database over the Internet. Beginning July 1, 2005, these same reporting requirements were added to Spills, Leaks, Investigations, and Cleanup (SLIC) sites. Beginning July 1, 2005, electronic submittal of a complete copy of all reports for all sites is required in GeoTracker (in PDF format). Please visit the SWRCB website for more information on these requirements (http://www.waterboards.ca.gov/water_issues/programs/ust/electronic_submittal/).

PERJURY STATEMENT

All work plans, technical reports, or technical documents submitted to ACEH must be accompanied by a cover letter from the responsible party that states, at a minimum, the following: "I declare, under penalty of perjury, that the information and/or recommendations contained in the attached document or report is true and correct to the best of my knowledge." This letter must be signed by an officer or legally authorized representative of your company. Please include a cover letter satisfying these requirements with all future reports and technical documents submitted for this fuel leak case.

PROFESSIONAL CERTIFICATION & CONCLUSIONS/RECOMMENDATIONS

The California Business and Professions Code (Sections 6735, 6835, and 7835.1) requires that work plans and technical or implementation reports containing geologic or engineering evaluations and/or judgments be performed under the direction of an appropriately registered or certified professional. For your submittal to be considered a valid technical report, you are to present site specific data, data interpretations, and recommendations prepared by an appropriately licensed professional and include the professional registration stamp, signature, and statement of professional certification. Please ensure all that all technical reports submitted for this fuel leak case meet this requirement.

UNDERGROUND STORAGE TANK CLEANUP FUND

Please note that delays in investigation, later reports, or enforcement actions may result in your becoming ineligible to receive grant money from the state's Underground Storage Tank Cleanup Fund (Senate Bill 2004) to reimburse you for the cost of cleanup.

AGENCY OVERSIGHT

If it appears as though significant delays are occurring or reports are not submitted as requested, we will consider referring your case to the Regional Board or other appropriate agency, including the County District Attorney, for possible enforcement actions. California Health and Safety Code, Section 25299.76 authorizes enforcement including administrative action or monetary penalties of up to \$10,000 per day for each day of violation.

Alameda County Environmental Cleanup Oversight Programs (LOP and SLIC)	REVISION DATE: May 15, 2014
	ISSUE DATE: July 5, 2005
	PREVIOUS REVISIONS: October 31, 2005; December 16, 2005; March 27, 2009; July 8, 2010, July 25, 2010
SECTION: Miscellaneous Administrative Topics & Procedures	SUBJECT: Electronic Report Upload (ftp) Instructions

The Alameda County Environmental Cleanup Oversight Programs (LOP and SLIC) require submission of all reports in electronic form to the county's ftp site. Paper copies of reports will no longer be accepted. The electronic copy replaces the paper copy and will be used for all public information requests, regulatory review, and compliance/enforcement activities.

REQUIREMENTS

- **Please do not submit reports as attachments to electronic mail.**
- Entire report including cover letter must be submitted to the ftp site as **a single portable document format (PDF) with no password protection.**
- It is **preferable** that reports be converted to PDF format from their original format, (e.g., Microsoft Word) rather than scanned.
- **Signature pages and perjury statements must be included and have either original or electronic signature.**
- **Do not password protect the document.** Once indexed and inserted into the correct electronic case file, the document will be secured in compliance with the County's current security standards and a password. **Documents with password protection will not be accepted.**
- Each page in the PDF document should be rotated in the direction that will make it easiest to read on a computer monitor.
- Reports must be named and saved using the following naming convention:

RO#_Report Name_Year-Month-Date (e.g., RO#5555_WorkPlan_2005-06-14)

Submission Instructions

- 1) Obtain User Name and Password
 - a) Contact the Alameda County Environmental Health Department to obtain a User Name and Password to upload files to the ftp site.
 - i) Send an e-mail to deh.loptoxic@acgov.org
 - b) In the subject line of your request, be sure to include "**ftp PASSWORD REQUEST**" and in the body of your request, include the **Contact Information, Site Addresses**, and the **Case Numbers (RO# available in Geotracker) you will be posting for.**
- 2) Upload Files to the ftp Site
 - a) Using Internet Explorer (IE4+), go to <ftp://alcoftp1.acgov.org>
 - (i) Note: Netscape, Safari, and Firefox browsers will not open the FTP site as they are NOT being supported at this time.
 - b) Click on Page located on the Command bar on upper right side of window, and then scroll down to Open FTP Site in Windows Explorer.
 - c) Enter your User Name and Password. (Note: Both are Case Sensitive.)
 - d) Open "My Computer" on your computer and navigate to the file(s) you wish to upload to the ftp site.
 - e) With both "My Computer" and the ftp site open in separate windows, drag and drop the file(s) from "My Computer" to the ftp window.
- 3) Send E-mail Notifications to the Environmental Cleanup Oversight Programs
 - a) Send email to deh.loptoxic@acgov.org notify us that you have placed a report on our ftp site.
 - b) Copy your Caseworker on the e-mail. Your Caseworker's e-mail address is the entire first name then a period and entire last name @acgov.org. (e.g., firstname.lastname@acgov.org)
 - c) The subject line of the e-mail must start with the RO# followed by **Report Upload**. (e.g., Subject: RO1234 Report Upload) If site is a new case without an RO#, use the street address instead.
 - d) If your document meets the above requirements and you follow the submission instructions, you will receive a notification by email indicating that your document was successfully uploaded to the ftp site.



ENVIRONMENTAL HEALTH SERVICES
ENVIRONMENTAL PROTECTION
1131 Harbor Bay Parkway, Suite 250
Alameda, CA 94502-6577
(510) 567-6700
FAX (510) 337-9335

November 8, 2013

Mr. Walter Merkle
MCG Investments LLC
123 Estudillo Avenue
San Leandro, CA 94577

Shirley J Davini & Dorothy D McGuire
123 Estudillo Avenue
San Leandro, CA 94577

Mr. Jon Braden
McGrath Steel Company
Address Unknown

Mr. David Davini
Loretta A McGrath Family Trust
Address Unknown

Subject: Request for Feasibility Study / Corrective Action Plan; Fuel Leak Case No. RO0000063;
(Global ID # T0600102099); McGrath Steel Company, 6655 Hollis Street, Emeryville, CA
94608

Dear Messrs. Merkle and Braden, and Mses. Davini and McGuire:

Alameda County Environmental Health (ACEH) staff has reviewed the case file for the above referenced site including the *Additional Site Characterization and Monitoring Well Installation Report*, dated August 30, 2013 (received October 21, 2013), and the *Second Quarter 2013 Groundwater Monitoring*, dated July 11, 2013. Both reports were prepared and submitted on your behalf by AllWest Environmental, Inc. (AllWest). Thank you for submitting the reports. The site characterization report recommended the installation of a passive skimming device in well MW-3 to recover Light Non-Aqueous Phased Liquid Product (LNALP) that is currently present at thickness of 0.41 feet, and indicated that an indoor vapor intrusion risk might be present for the buildings immediately adjacent to the former underground storage tank (UST) location.

ACEH has evaluated the data and recommendations presented in the above-mentioned reports, in conjunction with the case files, and the State Water Resources Control Board's (SWRCBs) Low Threat Underground Storage Tank Case Closure Policy (LTCP). Based on ACEH staff review, we have determined that the site fails to meet the LTCP General Criteria d (LNAPL Removal), e (Site Conceptual Model), f (Secondary Source Removal) and the Media-Specific Criteria for Groundwater, the Media-Specific Criteria for Vapor Intrusion to Indoor Air, and the Media-Specific Criteria for Direct Contact (see Geotracker for a copy of the LTCP checklist).

Therefore, at this juncture ACEH requests that you prepare a Data Gap Investigation Work Plan that is supported by a focused Site Conceptual Model (SCM) to address the Technical Comments provided below.

ACEH would like to invite you to meeting in order to discuss the site and to resolve any questions that may arise due to these changes. ACEH requests notification of suitable dates and times for the meeting.

TECHNICAL COMMENTS

- 1. LTCP General Criteria d; Removal of LNAPL to the Maximum Extent Practicable** – The LTCP requires LNAPL to be removed to the extent practicable at release sites where investigations indicate the presence of free product by removing in a manner that minimizes the spread of the unauthorized release into previously uncontaminated zones by using recovery and disposal techniques appropriate to the hydrogeologic conditions at the site, and that properly treats, discharges, or disposes of recovery byproducts in compliance with applicable laws. Additionally, the LTCP requires that abatement of free product migration be used as a minimum objective for the design of any free product removal system.

ACEH's review of the case files indicates that recoverable LNAPL remains at the site in well MW-3, and based on groundwater analytical concentrations may extend to at least soil bore B-20. Grab groundwater concentrations collected in January 2013 indicate that concentrations up to 160,000 micrograms per liter ($\mu\text{g/l}$) Total Petroleum Hydrocarbons [TPH] as gasoline, 95,000 $\mu\text{g/l}$ TPH as diesel, 21,000 $\mu\text{g/l}$ benzene, and 140,000 $\mu\text{g/l}$ MTBE were detected at soil bores B20 and B21. These concentrations are significantly over concentrations that the *Technical Justification for Vapor Intrusion Media-Specific Criteria* generated in support of the LTCP, suggests is "indirect" evidence of LNAPL.

The proposed installation of a passive skimmer at well MW-3 appears appropriate; however, may not be a sufficient effort based on the data cited. Based on the location of potential preferential pathways in previous reports, in particular the sewer, this utility line may affect the distribution of the LNAPL at times. A storm drain line has not been depicted on these figures; however, if present may also be a preferential pathway. Please present your analysis of LNAPL migration and plume extent in a focused SCM and Data Gap Investigation Work Plan described in Technical Comment 7.

If based on your analysis further abatement of LNAPL is necessary, please present a proposed strategy in an Interim Remedial Action Plan (IRAP) as described in Technical Comment 8.

2. **LTCP General Criteria e (Site Conceptual Model)** – According to the LTCP, the SCM is a fundamental element of a comprehensive site investigation. The SCM establishes the source and attributes of the unauthorized release, describes all affected media (including soil, groundwater, and soil vapor as appropriate), describes local geology, hydrogeology and other physical site characteristics that affect contaminant environmental transport and fate, and identifies all confirmed and potential contaminant receptors (including water supply wells, surface water bodies, structures and their inhabitants). The SCM is relied upon by practitioners as a guide for investigative design and data collection. All relevant site characteristics identified by the SCM shall be assessed and supported by data so that the nature, extent and mobility of the release have been established to determine conformance with applicable criteria in this policy.

Our review of the case files indicates that insufficient data collection and analysis has been undertaken to assess the nature, extent, and mobility of the release and to support compliance with General Criteria d as discussed in Item 1 above, General Criteria f, and Media Specific Criteria for Vapor Intrusion to Indoor Air, Groundwater, and Direct Contact and Outdoor Air Exposure as described in Technical Comments 3, 4, 5, and 6 below, respectively.

3. **General Criteria f – Secondary Source Has Been Removed to the Extent Practicable** – The bore log for soil bore B-22 appears to have documented the removal of the secondary soil source beneath the former USTs to the extent practicable. As documented by the bore log for soil bore B-24, it is not clear that the secondary source beneath the former dispenser has been removed to the extent practicable. Additionally, the presence of LNAPL can be considered a significant residual source; however, under the LTCP it is not considered a secondary source. Please present a response to the adequacy of secondary source removal in a focused SCM as described in Technical Comment 7 and a proposed scope of work to address the identified data gap under the LTCP.
4. **LTCP Media Specific Criteria for Groundwater** – To satisfy the media-specific criteria for groundwater, the contaminant plume that exceeds water quality objectives must be stable or decreasing in areal extent, and meet all of the additional characteristics of one of the five classes of sites listed in the policy.

Our review of the case files indicates that the site data collection and analysis do not support the requisite characteristics of one of the five scenarios under the criteria. Our review of the case files indicates that insufficient data and analysis has been presented to support the requisite characteristics of plume stability or plume classification as follows:

- a. **Length of LNAPL Plume** – As noted above the extent of the LNAPL plume may extend further west than well MW-3. Based on grab groundwater analytical concentrations at soil bore B-21, and a southwesterly gradient direction depicted in the recent soil and groundwater investigation report, the LNAPL plume may extend beneath the adjacent site building. At present the extent of the LNAPL plume does not appear to be defined.

- b. **Length of Groundwater Dissolved-Phase Plume** – The length of the dissolved-phased plume may be adequately defined to the west; however, the recently installed wells suggest that the direction of groundwater flow is to the southwest beneath buildings immediately adjacent to the former UST excavation. Thus the dissolved-phase plume does not appear to be defined to the southwest, and the length of the dissolved-phase plume to the southwest has not been defined.
- c. **Water Well Survey** – A survey has not been conducted to determine the location of any water supply wells in the vicinity of the subject site. As a consequence, ACEH requests that a ¼-mile radius well survey be conducted using both Department of Water Resources (DWR) and Alameda County Public Works Agency (ACPWA) water well resources. All water supply wells should be located on a vicinity map. Please note that construction well details are considered to be confidential and therefore should not be uploaded to public websites.
- d. **Benzene Concentrations** – Benzene concentrations up to 21,000 µg/l have been detected in grab groundwater samples (B-20), and up to 9,800 µg/l in groundwater collected from well MW-3, beneath the LNAPL. Thus benzene concentrations exceed all LTCP groundwater media-specific criteria.
- e. **Current Groundwater Classification** – Again as previously addressed, please be aware that all groundwater in the East Bay Plain Groundwater Basin that underlies Emeryville is classified as 'MUN' (potentially suitable for municipal or domestic water supply). According to the RWQCB *Water Quality Control Plan (Basin Plan)*, dated January 18, 2007, for the San Francisco Bay Basin, "the term 'groundwater' includes all subsurface waters, whether or not these waters meet the classic definition of an aquifer or occur within identified groundwater basins.' The Basin Plan also states that 'all groundwaters are considered suitable, or potentially suitable, for municipal or domestic water supply (MUN)." Therefore, the groundwater beneath the subject site is considered beneficial for these uses unless shown to be non-beneficial using criteria presented in the Basin Plan (Please note that the proposed "Zone B Berkeley / Albany Groundwater Management Zone" contained in the June 1999 *East Bay Plain Groundwater Basin Beneficial Use Evaluation Report*, that was referenced in your work plan addendum, was not adopted in the 2007 Basin Plan). Please adjust future evaluations to reflect these classifications; however, please also be aware that case closure does not require cleanup to MUN cleanup goals, rather that those goals can be met within an identified reasonable timeframe. This is also stated to be consistent and reflected in the LTCP.

Alternatively, should alternative interpretations be possible from this data, please provide justification of why the site satisfies the Groundwater Media-Specific Criteria in a SCM that assures that the identified deficiencies have been addressed.

- 5. **LTCP Media Specific Criteria for Vapor Intrusion to Indoor Air** – The LTCP describes conditions, including bioattenuation zones, which if met will assure that exposure to petroleum vapors in indoor air will not pose unacceptable health risks to human occupants of existing or future site buildings, and adjacent parcels. Appendices 1 through 4 of the LTCP criteria illustrate four potential exposure scenarios and describe characteristics and criteria associated with each scenario.

Our review of the case files indicates that the site data and analysis fail to support the requisite characteristics of one of the four scenarios. Specifically, it appears that petroleum contamination is present at concentrations greater than 100 mg/kg TPH at multiple locations in the 0 to 5 and the 5 to 10 foot depth intervals beneath the site and site vicinity and groundwater benzene concentrations are greater than 1,000 ug/l benzene. Additionally, because no soil vapor samples have been collected, no soil vapor oxygen data is available.

Therefore, please present a strategy in the Data Gap Investigation Work Plan as described in Technical Comment 7 below to collect additional data to satisfy the bioattenuation zone characteristics of Scenarios 1, 2 or 3, or to collect soil gas data to satisfy Scenario 4, to ensure that exposure to petroleum vapors in indoor air does not pose unacceptable health risks to human occupants of existing or future site buildings, and adjacent parcels. Should vapor wells be proposed for installation ACEH requests that soil be collected and analyzed in the 0 to 5 foot interval, at lithologic changes, and at areas of obvious

impact. ACEH additionally requests that soil samples collected from these borings be submitted for all requisite analysis, including naphthalene analysis.

Alternatively, please provide justification of why the site satisfies the Media-Specific Criteria for Vapor Intrusion to Indoor Air in the SCM described in Technical Comment 7 that assures that exposure to petroleum vapors in indoor air will not pose unacceptable health risks to occupants of adjacent buildings.

Please note, that if direct measurement of soil gas is proposed, ensure that your strategy is consistent with the field sampling protocols described in the Department of Toxic Substances Control's Final Vapor Intrusion Guidance (October 2011). Consistent with the guidance, ACEH requires installation of permanent vapor wells to assess temporal and seasonal variations in soil gas concentrations.

- 6. LTCP Media Specific Criteria for Direct Contact and Outdoor Air Criteria** – The LTCP describes conditions where direct contact with contaminated soil or inhalation of contaminants volatilized to outdoor air poses a low threat to human health. According to the policy, release sites where human exposure may occur satisfy the media-specific criteria for direct contact and outdoor air exposure and shall be considered low-threat if the maximum concentrations of petroleum constituents in soil are less than or equal to those listed in Table 1 for the specified depth bgs. Alternatively, the policy allows for a site specific risk assessment that demonstrates that maximum concentrations of petroleum constituents in soil will have no significant risk of adversely affecting human health, or controlling exposure through the use of mitigation measures, or institutional or engineering controls.

Our review of the case files indicates that benzene concentrations up to 12 mg/kg is present at a depth of 10 feet in soil bore B21, and that this concentration exceeds allowable concentrations listed in Table 1 of the LTCP. Because of the potential southwesterly groundwater flow direction, additional elevated soil contamination may be present beneath the immediately adjacent building(s).

Therefore, please present a strategy in the Data Gap Investigation Work Plan as described in Technical Comment 7 below to collect additional data to laterally define the extent of soil contamination that does not satisfy the direct contact and outdoor air exposure criteria in areas immediately downgradient of the former UST location and soil bore B21. ACEH requests that soil be collected and analyzed in the 0 to 5 and the 5 to 10 foot intervals, at the groundwater interface, lithologic changes, and at areas of obvious impact. ACEH additionally requests that groundwater samples be collected from these borings and requisite analysis, including naphthalene and polycyclic aromatic hydrocarbons (PAH) analysis, be conducted.

Alternatively, please provide justification of why the site satisfies the Media-Specific Criteria for Direct Contact and Outdoor Air Exposure in an focused SCM and Data Gap Investigation Work Plan described in Item 7 below that assures that exposure to petroleum constituents in soil will have no significant risk of adversely affecting human health.

- 7. Focused Site Conceptual Model and Data Gap Investigation Work Plan** – Please prepare a Data Gap Investigation Work Plan to address the technical comments listed above. Please support the scope of work in the Data Gap Investigation Work Plan with a focused SCM and Data Quality Objectives (DQOs) that relate the data collection to each LTCP criteria. For example please clarify which scenario within each Media-Specific Criteria a sampling strategy is intended to apply to.

In order to expedite review, ACEH requests the focused SCM be presented in a tabular format that highlights the major SCM elements and associated data gaps, which need to be addressed to progress the site to case closure under the LTCP. Please see Attachment A "Site Conceptual Model Requisite Elements". Please sequence activities in the proposed revised data gap investigation scope of work to enable efficient data collection in the fewest mobilizations possible.

- 8. Interim Remedial Action Plan** - ACEH requests that interim remedial actions, in addition to the installation of a passive skimmer into well MW-3, be identified and implemented to abate LNAPL migration. Please present the proposed strategy in an IRAP by the date identified below.

9. **Quarterly Groundwater Monitoring** – Please institute quarterly groundwater monitoring of all site vicinity wells for a minimum period of one year for all chemicals of concern at the site. This will allow groundwater contaminant trends to be established quickly at the site.

TECHNICAL REPORT REQUEST

Please upload technical reports to the ACEH ftp site (Attention: Mark Detterman), and to the State Water Resources Control Board's Geotracker website, in accordance with Attachment 1 and the specified file naming convention below, according to the following schedule:

- **January 10, 2014** – Data Gap Investigation Plan and Focused Site Conceptual Model
File to be named: RO63_WP_SCM_R_yyyy-mm-dd
- **January 17, 2014** – Interim Remedial Action Plan
File to be named: RO63_IRAP_R_yyyy-mm-dd
- **January 24, 2014** – Quarterly Groundwater Monitoring Report
File to be named: RO63_GWM_R_yyyy-mm-dd
- **60 Days After Work Plan Approval** – Soil and Groundwater Investigation Report
File to be named: RO63_SWI_R_yyyy-mm-dd
- **April 25, 2014** – Quarterly Groundwater Monitoring Report
File to be named: RO63_GWM_R_yyyy-mm-dd

These reports are being requested pursuant to California Health and Safety Code Section 25296.10. 23 CCR Sections 2652 through 2654, and 2721 through 2728 outline the responsibilities of a responsible party in response to an unauthorized release from a petroleum UST system, and require your compliance with this request.

Online case files are available for review at the following website: <http://www.acgov.org/aceh/index.htm>. If your email address does not appear on the cover page of this notification, ACEH is requesting you provide your email address so that we can correspond with you quickly and efficiently regarding your case.

If you have any questions, please call me at (510) 567-6876 or send me an electronic mail message at mark.detterman@acgov.org.

Sincerely,



Digitally signed by Mark Detterman
DN: cn=Mark Detterman, o, ou,
email=mark.detterman@acgov.org, c=US
Date: 2013.11.08 09:49:40 -08'00'

Mark E. Detterman, PG, CEG
Senior Hazardous Materials Specialist

Enclosures: Attachment 1 – Responsible Party (ies) Legal Requirements / Obligations and
Electronic Report Upload (ftp) Instructions

Attachment A - Site Conceptual Model Requisite Elements

cc: Leonard Niles, AllWest Environmental, Inc, 530 Howard Street, Suite 300, San Francisco, CA
94105; (sent via electronic mail to: leonard@allwest1.com)

Dilan Roe, ACEH, (sent via electronic mail to: dilan.roe@acgov.org)
Mark Detterman (sent via electronic mail to mark.detterman@acgov.org)
Electronic File, GeoTracker

Attachment 1

Responsible Party(ies) Legal Requirements/Obligations

REPORT/DATA REQUESTS

These reports/data are being requested pursuant to Division 7 of the California Water Code (Water Quality), Chapter 6.7 of Division 20 of the California Health and Safety Code (Underground Storage of Hazardous Substances), and Chapter 16 of Division 3 of Title 23 of the California Code of Regulations (Underground Storage Tank Regulations).

ELECTRONIC SUBMITTAL OF REPORTS

ACEH's Environmental Cleanup Oversight Programs (Local Oversight Program [LOP] for unauthorized releases from petroleum Underground Storage Tanks [USTs], and Site Cleanup Program [SCP] for unauthorized releases of non-petroleum hazardous substances) require submission of reports in electronic format pursuant to Chapter 3 of Division 7, Sections 13195 and 13197.5 of the California Water Code, and Chapter 30, Articles 1 and 2, Sections 3890 to 3895 of Division 3 of Title 23 of the California Code of Regulations (23 CCR). Instructions for submission of electronic documents to the ACEH FTP site are provided on the attached "Electronic Report Upload Instructions."

Submission of reports to the ACEH FTP site is in addition to requirements for electronic submittal of information (ESI) to the State Water Resources Control Board's (SWRCB) Geotracker website. In April 2001, the SWRCB adopted 23 CCR, Division 3, Chapter 16, Article 12, Sections 2729 and 2729.1 (Electronic Submission of Laboratory Data for UST Reports). Article 12 required electronic submittal of analytical laboratory data submitted in a report to a regulatory agency (effective September 1, 2001), and surveyed locations (latitude, longitude and elevation) of groundwater monitoring wells (effective January 1, 2002) in Electronic Deliverable Format (EDF) to Geotracker. Article 12 was subsequently repealed in 2004 and replaced with Article 30 (Electronic Submittal of Information) which expanded the ESI requirements to include electronic submittal of any report or data required by a regulatory agency from a cleanup site. The expanded ESI submittal requirements for petroleum UST sites subject to the requirements of 23 CCR, Division, 3, Chapter 16, Article 11, became effective December 16, 2004. All other electronic submittals required pursuant to Chapter 30 became effective January 1, 2005. Please visit the SWRCB website for more information on these requirements: (http://www.waterboards.ca.gov/water_issues/programs/ust/electronic_submittal/).

PERJURY STATEMENT

All work plans, technical reports, or technical documents submitted to ACEH must be accompanied by a cover letter from the responsible party that states, at a minimum, the following: "I declare, under penalty of perjury, that the information and/or recommendations contained in the attached document or report is true and correct to the best of my knowledge." This letter must be signed by an officer or legally authorized representative of your company. Please include a cover letter satisfying these requirements with all future reports and technical documents submitted for this fuel leak case.

PROFESSIONAL CERTIFICATION & CONCLUSIONS/RECOMMENDATIONS

The California Business and Professions Code (Sections 6735, 7835, and 7835.1) requires that work plans and technical or implementation reports containing geologic or engineering evaluations and/or judgments be performed under the direction of an appropriately registered or certified professional. For your submittal to be considered a valid technical report, you are to present site specific data, data interpretations, and recommendations prepared by an appropriately licensed professional and include the professional registration stamp, signature, and statement of professional certification. Please ensure all that all technical reports submitted for this fuel leak case meet this requirement.

UNDERGROUND STORAGE TANK CLEANUP FUND

Please note that delays in investigation, late reports, or enforcement actions may result in your becoming ineligible to receive grant money from the state's Underground Storage Tank Cleanup Fund (Senate Bill 2004) to reimburse you for the cost of cleanup.

AGENCY OVERSIGHT

If it appears as though significant delays are occurring or reports are not submitted as requested, we will consider referring your case to the Regional Board or other appropriate agency, including the County District Attorney, for possible enforcement actions. California Health and Safety Code, Section 25299.76 authorizes enforcement including administrative action or monetary penalties of up to \$10,000 per day for each day of violation.

Alameda County Environmental Cleanup Oversight Programs (LOP and SCP)	REVISION DATE: July 25, 2012
	ISSUE DATE: July 5, 2005
	PREVIOUS REVISIONS: October 31, 2005; December 16, 2005; March 27, 2009; July 8, 2010
SECTION: Miscellaneous Administrative Topics & Procedures	SUBJECT: Electronic Report Upload (ftp) Instructions

The Alameda County Environmental Cleanup Oversight Programs (petroleum UST and SCP) require submission of all reports in electronic form to the county's FTP site. Paper copies of reports will no longer be accepted. The electronic copy replaces the paper copy and will be used for all public information requests, regulatory review, and compliance/enforcement activities.

REQUIREMENTS

- **Please do not submit reports as attachments to electronic mail.**
- Entire report including cover letter must be submitted to the ftp site as a **single Portable Document Format (PDF) with no password protection.**
- It is **preferable** that reports be converted to PDF format from their original format, (e.g., Microsoft Word) rather than scanned.
- **Signature pages and perjury statements must be included and have either original or electronic signature.**
- **Do not password protect the document.** Once indexed and inserted into the correct electronic case file, the document will be secured in compliance with the County's current security standards and a password. **Documents with password protection will not be accepted.**
- Each page in the PDF document should be rotated in the direction that will make it easiest to read on a computer monitor.
- Reports must be named and saved using the following naming convention:

RO#_Report Name_Year-Month-Date (e.g., RO#5555_WorkPlan_2005-06-14)

Submission Instructions

- 1) Obtain User Name and Password
 - a) Contact the Alameda County Environmental Health Department to obtain a User Name and Password to upload files to the ftp site.
 - i) Send an e-mail to deh.loptoxic@acgov.org
 - b) In the subject line of your request, be sure to include "**ftp PASSWORD REQUEST**" and in the body of your request, include the **Contact Information, Site Addresses, and the Case Numbers (RO# available in Geotracker) you will be posting for.**
- 2) Upload Files to the ftp Site
 - a) Using Internet Explorer (IE4+), go to <ftp://alcoftp1.acgov.org>
 - (i) Note: Netscape, Safari, and Firefox browsers will not open the FTP site as they are NOT being supported at this time.
 - b) Click on Page located on the Command bar on upper right side of window, and then scroll down to Open FTP Site in Windows Explorer.
 - c) Enter your User Name and Password. (Note: Both are Case Sensitive.)
 - d) Open "My Computer" on your computer and navigate to the file(s) you wish to upload to the ftp site.
 - e) With both "My Computer" and the ftp site open in separate windows, drag and drop the file(s) from "My Computer" to the ftp window.
- 3) Send E-mail Notifications to the Environmental Cleanup Oversight Programs
 - a) Send email to deh.loptoxic@acgov.org notify us that you have placed a report on our ftp site.
 - b) Copy your Caseworker on the e-mail. Your Caseworker's e-mail address is the entire first name then a period and entire last name @acgov.org. (e.g., firstname.lastname@acgov.org)
 - c) The subject line of the e-mail must start with the RO# followed by **Report Upload**. (e.g., Subject: RO1234 Report Upload) If site is a new case without an RO#, use the street address instead.
 - d) If your document meets the above requirements and you follow the submission instructions, you will receive a notification by email indicating that your document was successfully uploaded to the ftp site.

ATTACHMENT A

Site Conceptual Model Requisite Elements

ATTACHMENT A

Site Conceptual Model

The site conceptual model (SCM) is an essential decision-making and communication tool for all interested parties during the site characterization, remediation planning and implementation, and closure process. A SCM is a set of working hypotheses pertaining to all aspects of the contaminant release, including site geology, hydrogeology, release history, residual and dissolved contamination, attenuation mechanisms, pathways to nearby receptors, and likely magnitude of potential impacts to receptors.

The SCM is initially used to characterize the site and identify data gaps. As the investigation proceeds and the data gaps are filled, the working hypotheses are modified, and the overall SCM is refined and strengthened until it is said to be "validated". At this point, the focus of the SCM shifts from site characterization towards remedial technology evaluation and selection, and later remedy optimization, and forms the foundation for developing the most cost-effective corrective action plan to protect existing and potential receptors.

For ease of review, Alameda County Environmental Health (ACEH) requests utilization of tabular formats to (1) highlight the major SCM elements and their associated data gaps which need to be addressed to progress the site to case closure (see Table 1 of attached example), and (2) highlight the identified data gaps and proposed investigation activities (see Table 2 of the attached example). ACEH requests that the tables presenting the SCM elements, data gaps, and proposed investigation activities be updated as appropriate at each stage of the project and submitted with work plans, feasibility studies, corrective action plans, and requests for closures to support proposed work, conclusions, and/or recommendations.

The SCM should incorporate, but is not limited to, the topics listed below. Please support the SCM with the use of large-scaled maps and graphics, tables, and conceptual diagrams to illustrate key points. Please include an extended site map(s) utilizing an aerial photographic base map with sufficient resolution to show the facility, delineation of streets and property boundaries within the adjacent neighborhood, downgradient irrigation wells, and proposed locations of transects, monitoring wells, and soil vapor probes.

- a. Regional and local (on-site and off-site) geology and hydrogeology. Include a discussion of the surface geology (e.g., soil types, soil parameters, outcrops, faulting), subsurface geology (e.g., stratigraphy, continuity, and connectivity), and hydrogeology (e.g., water-bearing zones, hydrologic parameters, impermeable strata). Please include a structural contour map (top of unit) and isopach map for the aquitard that is presumed to separate your release from the deeper aquifer(s), cross sections, soil boring and monitoring well logs and locations, and copies of regional geologic maps.
- b. Analysis of the hydraulic flow system in the vicinity of the site. Include rose diagrams for depicting groundwater gradients. The rose diagram shall be plotted on groundwater elevation contour maps and updated in all future reports submitted for your site. Please address changes due to seasonal precipitation and groundwater pumping, and evaluate the potential interconnection between shallow and deep aquifers. Please include an analysis of vertical hydraulic gradients, and effects of pumping rates on hydraulic head from nearby water supply wells, if appropriate. Include hydraulic head in the different water bearing zones and hydrographs of all monitoring wells.
- c. Release history, including potential source(s) of releases, potential contaminants of concern (COC) associated with each potential release, confirmed source locations, confirmed release locations, and existing delineation of release areas. Address primary leak source(s) (e.g., a tank, sump, pipeline, etc.) and secondary sources (e.g., high-

ATTACHMENT A

Site Conceptual Model (continued)

concentration contaminants in low-permeability lithologic soil units that sustain groundwater or vapor plumes). Include local and regional plan view maps that illustrate the location of sources (former facilities, piping, tanks, etc.).

- d. Plume (soil gas and groundwater) development and dynamics including aging of source(s), phase distribution (NAPL, dissolved, vapor, residual), diving plumes, attenuation mechanisms, migration routes, preferential pathways (geologic and anthropogenic), magnitude of chemicals of concern and spatial and temporal changes in concentrations, and contaminant fate and transport. Please include three-dimensional plume maps for groundwater and two-dimensional soil vapor plume plan view maps to provide an accurate depiction of the contaminant distribution of each COC.
- e. Summary tables of chemical concentrations in different media (i.e., soil, groundwater, and soil vapor). Please include applicable environmental screening levels on all tables. Include graphs of contaminant concentrations versus time.
- f. Current and historic facility structures (e.g., buildings, drain systems, sewer systems, underground utilities, etc.) and physical features including topographical features (e.g., hills, gradients, surface vegetation, or pavement) and surface water features (e.g. routes of drainage ditches, links to water bodies). Please include current and historic site maps.
- g. Current and historic site operations/processes (e.g., parts cleaning, chemical storage areas, manufacturing, etc.).
- h. Other contaminant release sites in the vicinity of the site. Hydrogeologic and contaminant data from those sites may prove helpful in testing certain hypotheses for the SCM. Include a summary of work and technical findings from nearby release sites, including the two adjacent closed LUFT sites, (i.e., Montgomery Ward site and the Quest Laboratory site).
- i. Land uses and exposure scenarios on the facility and adjacent properties. Include beneficial resources (e.g., groundwater classification, wetlands, natural resources, etc.), resource use locations (e.g., water supply wells, surface water intakes), subpopulation types and locations (e.g., schools, hospitals, day care centers, etc.), exposure scenarios (e.g. residential, industrial, recreational, farming), and exposure pathways, and potential threat to sensitive receptors. Include an analysis of the contaminant volatilization from the subsurface to indoor/outdoor air exposure route (i.e., vapor pathway). Please include copies of Sanborn maps and aerial photographs, as appropriate.
- j. Identification and listing of specific data gaps that require further investigation during subsequent phases of work. Proposed activities to investigate and fill data gaps identified.

TABLE 1
INITIAL SITE CONCEPTUAL MODEL

CSM Element	CSM Sub-Element	Description	Data Gap	How to Address
Geology and Hydrogeology	Regional	<p>The site is in the northwest portion of the Livermore Valley, which consists of a structural trough within the Diablo Range and contains the Livermore Valley Groundwater Basin (referred to as "the Basin") (DWR, 2006). Several faults traverse the Basin, which act as barriers to groundwater flow, as evidenced by large differences in water levels between the upgradient and downgradient sides of these faults (DWR, 2006). The Basin is divided into 12 groundwater basins, which are defined by faults and non-water-bearing geologic units (DWR, 1974).</p> <p>The hydrogeology of the Basin consists of a thick sequence of fresh-water-bearing continental deposits from alluvial fans, outwash plains, and lacustrine environments to up to approximately 5,000 feet bgs (DWR, 2006). Three defined fresh-water bearing geologic units exist within the Basin: Holocene Valley Fill (up to approximately 400 feet bgs in the central portion of the Basin), the Plio-Pleistocene Livermore Formation (generally between approximately 400 and 4,000 feet bgs in the central portion of the Basin), and the Pliocene Tassajara Formation (generally between approximately 250 and 5,000 or more feet bgs) (DWR, 1974). The Valley Fill units in the western portion of the Basin are capped by up to 40 feet of clay (DWR, 2006).</p>	None	NA
	Site	<p>Geology: Borings advanced at the site indicate that subsurface materials consist primarily of finer-grained deposits (clay, sandy clay, silt and sandy silt) with interbedded sand lenses to 20 feet below ground surface (bgs), the approximate depth to which these borings were advanced. The documented lithology for one on-site boring that was logged to approximately 45 feet bgs indicates that beyond approximately 20 feet bgs, fine-grained soils are present to approximately 45 feet bgs. A cone penetrometer technology test indicated the presence of sandier lenses from approximately 45 to 58 feet bgs and even coarser materials (interbedded with finer-grained materials) from approximately 58 feet to 75 feet bgs, the total depth drilled. The lithology documented at the site is similar to that reported at other nearby sites, specifically the Montgomery Ward site (7575 Dublin Boulevard), the Quest laboratory site (6511 Golden Gate Drive), the Shell-branded Service Station site (11989 Dublin Boulevard), and the Chevron site (7007 San Ramon Road).</p> <p>Hydrogeology: Shallow groundwater has been encountered at depths of approximately 9 to 15 feet bgs. The hydraulic gradient and groundwater flow direction have not been specifically evaluated at the site.</p>	<p>As noted, most borings at the site have been advanced to approximately 20 feet bgs, and one boring has been advanced and logged to 45 feet bgs; CPT data was collected to 75 feet bgs at one location. Lithologic data will be obtained from additional borings that will be advanced on site to further the understanding of the subsurface, especially with respect to deeper lithology.</p> <p>The on-site shallow groundwater horizontal gradient has not been confirmed. Additionally, it is not known if there may be a vertical component to the hydraulic gradient.</p>	<p>Two direct push borings and four multi-port wells will be advanced to depth (up to approximately 75 feet bgs) and soil lithology will be logged. See items 4 and 5 on Table 2.</p> <p>Shallow and deeper groundwater monitoring wells will be installed to provide information on lateral and vertical gradients. See Items 2 and 5 on Table 2.</p>
Surface Water Bodies		The closest surface water bodies are culverted creeks. Martin Canyon Creek flows from a gully west of the site, enters a culvert north of the site, and then bends to the south, passing approximately 1,000 feet east of the site before flowing into the Alamo Canal. Dublin Creek flows from a gully west of the site, enters a culvert approximately 750 feet south of the site, and then joins Martin Canyon Creek approximately 750 feet southeast of the site.	None	NA
Nearby Wells		The State Water Resources Control Board's GeoTracker GAMA website includes information regarding the approximate locations of water supply wells in California. In the vicinity of the site, the closest water supply wells presented on this website are depicted approximately 2 miles southeast of the site; the locations shown are approximate (within 1 mile of actual location for California Department of Public Health supply wells and 0.5 mile for other supply wells). No water-producing wells were identified within 1/4 mile of the site in the well survey conducted for the Quest Laboratory site (6511 Golden Gate Drive; documented in 2009); information documented in a 2005 report for the Chevron site at 7007 San Ramon Road indicates that a water-producing well may exist within 1/2 mile of the site.	A formal well survey is needed to identify water-producing, monitoring, cathodic protection, and dewatering wells.	Obtain data regarding nearby, permitted wells from the California Department of Water Resources and Zone 7 Water Agency (Item 11 on Table 2).

**TABLE 2
DATA GAPS AND PROPOSED INVESTIGATION**

Item	Data Gap	Proposed Investigation	Rationale	Analysis
5	Evaluate the possible presence of impacts to deeper groundwater. Evaluate deeper groundwater concentration trends over time. Obtain data regarding the vertical groundwater gradient. Obtain more lithological data below 20 feet bgs.	Install four continuous multichannel tubing (CMT) groundwater monitoring wells (aka multi-port wells) to approximately 65 feet bgs in the northern parking lot with ports at three depths (monitoring well locations may be adjusted pending results of shallow grab groundwater samples; we will discuss any potential changes with ACEH before proceeding). Groundwater monitoring frequency to be determined. Soil samples will be collected only if there are field indications of impacts. Soil lithology will be logged. However, information regarding the moisture content of soil may not be reliable using sonic drilling technology (two borings will be logged using direct push technology; see Item 4, above).	One well is proposed at the western (upgradient) property boundary to confirm that there are no deeper groundwater impacts from upgradient. Two wells are proposed near the center of the northern parking lot to evaluate potential impacts in an area where deeper impacts, if any, would most likely be found. One well is proposed at the eastern (downgradient) property boundary to confirm that there are no impacts extending off-site. Port depths will be chosen based on the locations of saturated soils (as logged in direct push borings; see Item 4, above), but are expected at approximately 15, 45, and 60 feet bgs.	<i>Groundwater:</i> VOCs by EPA Method 8260, dissolved oxygen, oxidation/reduction potential, temperature, pH, and specific conductance.
6	Evaluate possible off-site migration of impacted soil vapor in the downgradient direction (east). Evaluate concentration trends over time.	Install 4 temporary nested soil vapor probes at approximately 4 and 8 feet bgs along the eastern property boundary. Based on the results of the sampling, two sets of nested probes will be converted to vapor monitoring wells to allow for evaluation of VOC concentration trends over time.	Available data indicate that PCE and TCE are present in soil vapor in the eastern portion of the northern parking lot. Samples are proposed on approximately 50-foot intervals along the eastern property boundary to provide a transect of concentrations through the vapor plume. The depths of 4 and 8 feet bgs are chosen to provide data closest to the source (i.e., groundwater) while avoiding saturated soil, and also provide shallower data to help evaluate potential attenuation within the soil column. Two sets of nested vapor probes will be converted into vapor monitoring wells (by installing well boxes at ground surface); the locations of the permanent wells will be chosen based on the results of samples from the temporary probes.	<i>Soil vapor:</i> VOCs by EPA Method TO-15.
7	Evaluate potential for off-site migration of impacted groundwater in the downgradient direction (east).	Advance two borings to approximately 20 feet bgs in the parking lot of the property east of the Crown site for collection of grab groundwater samples.	Two borings are proposed off-site, on the property east of the Crown site, just east of the building in the expected area of highest potential VOC concentrations.	<i>Groundwater:</i> VOCs by EPA Method 8260, dissolved oxygen, oxidation/reduction potential, temperature, pH, and specific conductance.
8	Evaluate VOC concentrations just north of the highest concentration area.	Advance two borings to approximately 20 feet bgs north of Building A for collection of soil and grab groundwater samples. Soil samples will be collected at two depths in the vadose zone. Soil samples will be collected based on field indications of impacts (PID readings, odor, staining) or, in the absence of field indications of impacts, at 5 and 10 feet bgs.	The highest concentrations of PCE in groundwater were detected at boring NM-B-32, just north of Building A. The nearest available data to the north are approximately 75 feet away. One of the borings will be advanced approximately 20 feet north of NM-B-32 to provide data close to the highest concentration area. A second boring will be advanced approximately halfway between the first boring and former boring NM-B-33 to provide additional spatial data for contouring purposes. These borings will be part of a transect in the highest concentration area.	<i>Groundwater:</i> VOCs by EPA Method 8260, dissolved oxygen, oxidation/reduction potential, temperature, pH, and specific conductance. <i>Soil:</i> VOCs by EPA Method 8260 (soil samples to be collected using field preservation in accordance with EPA Method 5035).
9	Evaluate VOC concentrations in soil vapor in the south parcel of the site.	Install four temporary soil vapor probes at approximately 5 feet bgs around boring SV-25, where PCE was detected in soil vapor at a low concentration.	PCE was detected in soil vapor sample SV-25 in the southern parcel, although was not detected in groundwater in that area. Three probes will be installed approximately 30 feet from of boring SV-25 to attempt to delineate the extent of impacts. A fourth probe is proposed west of the original sample, close to the property boundary and the location of mapped utility lines, which may be a potential conduit, to evaluate potential impacts from the west.	<i>Soil vapor:</i> VOCs by EPA Method TO-15.
10	Obtain additional information regarding subsurface structures and utilities to further evaluate migration pathways and sources.	Ground penetrating radar (GPR) and other utility locating methodologies will be used, as appropriate, to further evaluate the presence of unknown utilities and structures at the site.	Utilities have been identified at the site that include an on-site sewer lateral and drain line, and shallow water, electric, and gas lines. Given the current understanding of the distribution of PCE in groundwater at the site, it is possible that other subsurface utilities, and specifically sewer laterals, exist that may act as a source or migration pathway for distribution of VOCs in the subsurface.	NA