

1921 Ringwood Avenue • San Jose, California 95131-1721 • (408) 453-7300 • Fax (408) 437-9526

Date <u>June 18, 1996</u> Project <u>20805-129.003</u>

To:

Ms. Susan Hugo Alameda County Health Care Services Agency Department of Environmental Health 1131 Harborbay Parkway, Suite 250 Alameda, California 94502-6577

We are enclosing:

Copies	•	Description								
1		First quarter 1996 groundwater monitoring results and								
		remediation system performance evaluation report,								
		ARCO Servic	e Station 2169,	Oakland, Ca	alifornia					
For your:	— х	Use	Sent by:	х	Regular Mail					
- C- y		Approval Review Information	·		Standard Air Courier Other:					

Comments:

The enclosed groundwater monitoring and performance evaluation report is being sent to you per the request of ARCO Products Company. Please call if you have questions or comments.

John C. Young Project Manager

cc: Kevin Graves, RWQCB - SFBR
Michael Whelan - ARCO Products Company
File



Date:

June 18, 1996

Re: ARCO Station #

2169 • 889 West Grand Avenue • Oakland, CA First Quarter 1996 Groundwater Monitoring Results and Remediation System Performance Evaluation Report

"I declare, that to the best of my knowledge at the present time, that the information and/or recommendations contained in the attached proposal or report are true and correct."

Submitted by:

Michael R. Whelan Environmental Engineer

Michael R. Whelon





June 10, 1996 Project 20805-129.003

Mr. Michael Whelan **ARCO Products Company** P.O. Box 612530 San Jose, California 95161

First quarter 1996 groundwater monitoring program results and remediation system performance evaluation report, ARCO service station 2169, Oakland, California

Dear Mr. Whelan:

This letter presents the results of the first quarter 1996 groundwater monitoring program at ARCO Products Company (ARCO) service station 2169, 889 West Grand Avenue, Oakland, California (Figure 1). Operation and performance data for the interim soil-vapor extraction (SVE) and air-sparge (AS) remediation systems at the site are also presented. The quarterly monitoring program complies with Alameda County Health Care Services Agency (ACHCSA) requirements regarding underground tank investigations. Pertinent site features, including the locations of existing on-site monitoring and vapor extraction wells are shown in Figure 2.

LIMITATIONS

No monitoring event is thorough enough to describe all geologic and hydrogeologic conditions of interest at a given site. If conditions have not been identified during the monitoring event, such a finding should not therefore be construed as a guarantee of the absence of such conditions at the site, but rather as the result of the scope, limitations, and cost of work performed during the monitoring event.

Please call if you have questions.

Sincerely.

EMCON

Sailaja Yelamanchili Staff Engineer

allya - Y.

ohn C. Young) Project Manager

ARCO QUARTERLY REPORT

Station No.:	2169	Address:	889 West Grand Avenue, Oakland, California
EMCON Project	et No.		20805-129.003
ARCO Environ	mental Engineer	r/Phone No.:	Michael Whelan / (408) 453-1640
EMCON Project	t Manager/Pho	ne No.;	John C. Young /(408) 453-7300
_	//Regulatory ID		ACHCSA /Susan Hugo

WORK PERFORMED THIS QUARTER (First- 1996):

- 1. Conducted quarterly groundwater monitoring and sampling.
- 2. Prepared and submitted quarterly report for fourth quarter 1995.
- 3. SVE system has been shut down since October 12, 1995. SVE system was restarted on January 18, 1996 but a blower failure caused system to shut down.
- 4. Historical groundwater analytical data suggests the groundwater monitoring samples for wells A-5 and A-6 appear to have been switched in either the laboratory or the field. The first quarter 1996 analytical results for wells A-5 and A-6 are consistent with quarters prior to fourth quarter 1995.

WORK PROPOSED FOR NEXT QUARTER (Second- 1996):

- 1. Perform quarterly groundwater monitoring and sampling.
- 2. Prepare and submit quarterly report for first quarter 1996.
- 3. Replace the blower motor and restart the SVE and air-sparge systems.

QUARTERLY MONITORING:

Current Phase of Project:	Quarterly Groundwater Monitoring and Operation and Maintenan of Remediation Systems							
Frequency of Sampling:	Quarterly (groundwater), Monthly (SVE and Air-Sparge)							
Frequency of Monitoring:	Quarterly (groundwater), Monthly (SVE and Air-Sparge)							
Is Floating Product (FP) Present On-sig	te: Yes No							
Cumulative FP Recovered to Date:	4.8 gallons, Wells ADR-1 and ADR-2							
FP Recovered This Quarter:	None							
Bulk Soil Removed to Date:	2,196 cubic yards of TPH-impacted soil							
Bulk Soil Removed This Quarter:	None							
Water Wells or Surface Waters								
within 2000 ft., impacted by site:	None							
Current Remediation Techniques:	SVE and Air-Sparge Systems							
Approximate Depth to Groundwater:	8.70 feet							
Groundwater Gradient (Average):	0.003 ft/ft toward northwest (consistent with past events)							
SVE QUARTERLY OPERAT	ION AND PERFORMANCE:							
Equipment Inventory:	Therm Tech Model VAC-25, 250 cfm, Thermal/Catalytic Oxidizer							
Operating Mode:	Catalytic Oxidation							
BAAQMD Permit #:	12119							
TPH Conc. End of Period (lab):	NA (Not Available)							
Benzene Conc. End of Period (lab):	NA							
Flowrate End of Period:	NA							

NA HC Destroyed This Period: 7,287.9 pounds HC Destroyed to Date: Utility Usage Electric (KWH): **31 KWH** 4 Therms Gas/Propane (Therms): Operating Hours This Period: None Percent Operational: 0% 4243.5 hours Operating Hours to Date: NA Unit Maintenance: System manually shut down on 10-12-95. Number of Auto Shut Downs: **Destruction Efficiency Permit** 90% Requirement: Percent TPH Conversion: NA NA Stack Temperature: NA Source Flow: Process Flow: NA NΑ Source Vacuum:

ATTACHED:

- Table 1 Groundwater Monitoring Data, First Quarter 1996
- Table 2 Historical Groundwater Elevation Data
- Table 3 Historical Groundwater Analytical Data
- Table 4 Approximate Cumulative Floating Product Recovery Data
- Table 5 Soil Vapor Extraction System Operation and Performance Data
- Table 6 Soil-Vapor Extraction Well Data
- Table 7 Air-Sparge System Operation and Performance Data
- Figure 1 Site Location
- Figure 2 Site Plan
- Figure 3 Groundwater Data, First Quarter 1996
- Figure 4 Historical SVE System Influent TVHG and Benzene Concentrations
- Figure 5 Historical SVE System Hydrocarbon Removal Rates
- Appendix A Field Data Sheets, First Quarter 1996 Groundwater Monitoring Event
- Appendix B Analytical Results and Chain of Custody Documentation, First Quarter 1996
 Groundwater Monitoring Event
- Appendix C SVE System Monitoring Data Log Sheets
- Appendix D Operation and Maintenance Field Data Sheets, SVE and Air-Sparge Systems, First Quarter 1996

cc: Susan Hugo, ACHCSA Kevin Graves, RWQCB-SFBR

Table 1 Groundwater Monitoring Data First Quarter 1996

ARCO Service Station 2169 889 West Grand Avenue, Oakland, CA

Date: 05-07-96

Well Designation	Water Level Field Date	Top of Casing Elevation	Depth to Water	Groundwater Elevation	Floating Product Thickness	Groundwater Flow Direction	Hydraulic Gradient	Water Sample Field Date	TPHG LUFT Method	Benzene EPA 8020	Toluene EPA 8020	Ethylbenzene EPA 8020	Total Xylenes EPA 8020	MTBE EPA 8020	MTBE EPA 8240	TPHD LUFT Method
		ft-MSL	feet	ft-MSL	feet	MWN	ft/ft		μg/L	μg/L	µg/L	μg/L	μg/L	μg/L	μg/L	μg/L
A-1	03-01-96	14.16	8 78	5.38	ND	NW	0.003	03-13-96	1300	300	74	29	73	100		
A-2	03-01-96	14.55	9.34	5.21	ND	NW	0.003	03-13-96	<50	<0.5	0.6	< 0.5	1.3	<9		
A-3	03-01-96	15.75	9.90	5.85	ND	NW	0.003	03-13-96	<50	<0.5	<0.5	<0.5	<0.5	<3		
A-4	03-01-96	15.25	8.55	6.70	ND	NW	0.003	03-13-96	<50	<0.5	<0.5	<0.5	<0.5	<3		
A-5	03-01-96	13.51	8.11	5 40	ND	NW	0.003	03-13-96	11000	860	960	380	1600	<100		
A-6	03-01-96	13.51	8.21	5 30	ND	NW	0.003	03-13-96	1400	<3	<15	<7	<10	<20		
AR-1	03-01-96	15 61	8.19	7.42	ND	NW	0.003	03-13-96	· 150	3.8	0.5	14	1.3	<3		
AR-2	03-01-96	15 28	9.83	5.45	ND	NW	0.003	03-13-96	190	26	2.6	3 3	13	200		
ADR-1	03-01-96	13.95	8.76	5.19	ND	NW	0 003	03-13-96	89000	370	1000	840	8100	<500		
ADR-2	03-01-96	14.64	8.74	5.90	ND	NW	0 003	03-13-96	29000	1100	1200	710	3800	<500		••

ft-MSL: elevation in feet, relative to mean sea level

MWN: ground-water flow direction and gradient apply to the entire monitoring well network

ft/ft: foot per foot

TPHG: total petroleum hydrocarbons as gasoline, California DHS LUFT Method

μg/L: micrograms per liter

EPA: United Statest Environmental Protection Agency

MTBE: methyl-tert-butyl ether

TPHD. total petroleum hydrocarbons as diesel, California DHS LUFT Method

ND: none detected NW: northwest --: not analyzed

Table 2
Historical Groundwater Elevation Data
1994 - Present***

Date: 05-07-96

Hydrauli Gradiei	Groundwater Flow Direction	Floating Product Thickness	Groundwater Elevation	Depth to Water	Top of Casing Elevation	Water Level Field Date	Well Designation
foot/foo	MWN	feet	ft-MSL	feet	ft-MSL		
N	NR	ND	4.07	10.09	14.16	02-09-94	A-1
0.00	NW	ND	3.48	10 68	14.16	05-04-94	A-1
0.00	WNW	ND	3.88	10.28	14.16	08-10-94	۸-۱
0.00	NW	ND	4,41	9.75	14.16	11-16-94	A-1
0.00	NW	ND	6.06	8.10	14.16	03-24-95	A-I
0.00	NW	ND	3.03	11 13	14.16	06-05-95	A-1
0.00	W	ND	2.45	11.71	14.16	08-17-95	A-1
0 00	NNW	ND	1.88	12.28	14.16	12-04-95	A-1
0.00	NW	ND	5.38	8.78	14.16	03-01-96	I-A
N	NR	ND	3.88	10.67	14.55	02-09-94	A-2
0.00	NW	ND ND	3 30	11.25	14.55		
0.00	WNW	ND ND	2.99	11.56	14.55	05-04-94 08-10-94	A-2
0.00	NW	ND	4.24	10.31	14.55		A-2
0.00	NW	ND	5.91	8.64	14.55	11-16-94	A-2 A-2
0.00	NW	ND	2.83	11.72	14.55	03-24-95 06-05-95	A-2
0.00	w	ND	2.20	12.35	14.55		
0.00	NNW	ND	1.81	12.33	14.55	08-17-95 12-04-95	A-2 A-2
0.00	NW	ND	5.21	9.34	14.55	03-01-96	A-2
N	NR	ND	4.43	11.32	15.75	02-09-94	A-3
0.00	NW	ND	3.76	11.99	15.75	05-04-94	A-3
0.00	WNW	ND	4.63	11.12	15.75	08-10-94	A-3
0.00	NW	ND	4 73	11.02	15.75	11-16-94	A-3
0.00	NW	ND	6.92	8.83	15 75	03-24-95	Λ-3
0.00	NW	ND	3.31	12.44	15.75	06-05-95	۸-3
0 00	W	ND	2.71	13.04	15.75	08-17-95	A-3
0.00	NNW	ND	2 18	13.57	15.75	12-04-95	A-3
0.00	NW	ND	5.85	9.90	15.75	03-01-96	A-3
N	NR	ND	5.24	10.01	15.25	02-09-94	۸-4
0.00	NW	ND	4.17	11.08	15.25	05-04-94	Λ-4
0.00	WNW	ND	3.50	11 75	15.25	08-10-94	A-4
0.00	NW	ND	5.47	9.78	15.25	11-16-94	A-4
0 00	NW	ND	8.05	7.20	15.25	03-24-95	A-4
0.00	NW	ND	3 55	1170	15.25	06-05-95	A-4
0.00	w	ND	2.97	12.28	15.25	08-17-95	A-4
0.00	NNW	ND	2.62	12 63	15.25	12-04-95	A-4
0.00	NW	ND	6.70	8.55	15.25	03-01-96	A-4

Table 2
Historical Groundwater Elevation Data
1994 - Present***

Date 05-07-96

							=====
		Top of			Floating	Groundwater	
Well	Water Level	Casing	Depth	Groundwater	Product	Flow	Hydraulic
Designation	Field Date	Elevation	to Water	Elevation	Thickness	Direction	Gradient
		ft-MSL	feet	ft-MSL	feet	MWN	foot/foot
A-5	02-09-94	i3 5 1	9,44	4.07	ND	NR	NR
Λ-5	05-04-94	13 51	10.00	3.51	ND	NW	0.004
A-5	08-10-94	13.51	10.76	2.75	ND	WNW	0.007
A-5	11-16-94	13.51	9.09	4 42	ND	NW	0.005
A-5	03-24-95	13.51	7.40	6.11	ND	NW	0.009
A-5	06-05-95	13.51	10 43	3.08	ND	NW	0.002
۸-5	08-17-95	13 51	11.15	2.36	ND	w	0.001
A-5	12-04-95	13.51	11 42	2.09	ND	NNW	0.002
Λ-5	03-01-96	13.51	8.11	5.40	ND	NW	0.003
			2.42	4.02	ND	NR	NR
A-6	02-09-94	13.51	9.48	4.03	ND		
۸-6	05-04-94	13 51	10.07	3.44	ND	NW	0.004
Λ-6	08-10-94	13.51	10.77	2 74	ND	WNW	0 007
۸-6	11-16-94	13.51	9.14	4 37	ND	NW	0 00:
A-6	03-24-95	13.51	7.89	5.62	ND	NW	0.00
A-6	06-05-95	13.51	10 06	3.45	ND	NW 	0.002
A-6	08-17-95	13.51	11.10	2.41	ND	W	0.001
A-6	12-04-95	13 51	11.52	1.99	ND	NNW	0.002
Λ-6	03-01-96	13 51	8.21	5.30	ND	NW	0.003
					200	115	ND
AR-1	02-09-94	15.61	11 08	4.53	ND	NR	NR
AR-1	05-04-94	15.61	11.83	3.78	ND	NW	0.004
AR-1	08-10-94	15.61	11.09	4,52	ND	WNW	0.007
AR-I	11-16-94	15.61	10.19	5.42	ND	NW	0.005
AR-1	03-24-95	15,61	7 25	8.36	ND	NW	0.009
AR-1	06-05-95	15.61	11 37	4.24	ND	NW	0.002
AR-1	08-17-95	15 61	12.40	3.21	ND	W	0.001
AR-1	12-04-95	15.61	12.90	2.71	ND	NNW	0.002
AR-I	03-01-96	1 5.61	8.19	7 42	ND	NW	0.00
AR-2	02-09-94	15.28	11.33	3.95	ND	NR	NF
	02-09-94	15.28	11.88	3.40	ND	NW	0 004
AR-2	08-10-94	15.28	12.48	2.80	ND ND	WNW	0.00
AR-2		15.28	10.48	4.33	ND	NW	0.00
AR-2	11-16-94 03-24-95	15.28 15.28	9.13	6.15	ND	NW	0.00
AR-2	06-05-95	15 28	12.09	3.19	ND ND	NW	0.00
AR-2 AR-2	08-17-95	15.28	12.09	2.50	ND	w	0.001
AR-2 AR-2		15.28	11.44	3.84	ND	NNW	0.007
	12-04-95				ND ND	NW	0.002
AR-2	03-01-96	15.28	9.83	5.45	MD	1A AA	0.003

Table 2
Historical Groundwater Elevation Data
1994 - Present***

Date: 05-07-96

Well Designation	Water Level Field Date	Top of Casing Elevation	Depth to Water	Groundwater Elevation	Floating Product Thickness	Groundwater Flow Direction	Hydraulic Gradient
		ft-MSL	feet	ft-MSL	feet	MWN	foot/foot
ADR-1	02-09-94	13.95	9.90	4.05	ND	NR	NR
ADR-1	05-04-94	13 95	10.50	3.45	ND	NW	0.004
ADR-1	08-10-94	13 95	10.36	3.59	ND	WNW	0.007
ADR-I	11-16-94	13.95	9.64	4.31	Sheen	NW	0 005
ADR-1	03-24-95	13.95	8 04	** 5.92	0.01	NW	0.009
ADR-1	06-05-95	13.95	11.02	2.93	ND	NW	0 002
ADR-1	08-17-95	13.95	11.86	2.09	ND	W	0 001
ADR-1	12-04-95	13.95	10.05	3.90	ND	NNW	0.002
ADR-1	03-01-96	13.95	8.76	5.19	ND	NW	0 003
ADR-2 ADR-2	02-09-94 05-04-94	14 64 14.64	10.73 11.31	3.91 3.33	ND ND	NR NW	NI 0.00-
	08-10-94	14.64	9.81	** 4.90	0.10	WNW	0.00
ADR-2	11-16-94	14.64	9.84	** 4.87	0.09	NW	0.00
ADR-2	03-24-95	14.64	8.41	NR*	>3.00*	NR*	NR.
ADR-2		14.64	11.45	NR*	>3.00*	NR*	NR'
ADR-2	06-05-95	14.04	11.43	IAIC.	>3 00	1417	0.00

12.10

10.93

8.74

** 2.56

** 3.73

5.90

0.03

0.03

ND

w

NNW

NW

0.001

0.002

0.003

08-17-95

12-04-95

03-01-96

MWN: groundwater flow direction and gradient apply to the entire monitoring well network

14.64

14 64

14 64

ADR-2

ADR-2

ADR-2

NR: not reported; data not available or not measurable

NW: northwest WNW: west-northwest

W: west

NNW: north-northwest

ft-MSL: elevation in feet, relative to mean sea level

ND: none detected

^{*:} well contained more than 3 feet of floating product; exact product thickness and groundwater elevation could not be measured

^{**: [}corrected elevation (Z')] = Z + (h * 0.73) where: Z = measured elevation, h = floating product thickness, 0.73 = density ratio of oil to water

^{***:} For previous historical groundwater elevation data please refer to Fourth Quarter 1995 Groundwater Monitoring Program Results and Remediation System Performance Evaluation Report, ARCO Service Station 2169, 889 West Grand Avenue, Oakland, California, (EMCON, March 4, 1996).

Table 3 Historical Groundwater Analytical Data 1994 - Present*

Date: 05-07-96

•										
	Well Designation	Water Sample Field Date	TPHG LUFT Method	Benzene EPA 8020	Toluene EPA 8020	Ethylbenzene EPA 8020	Total Xylenes EPA 8020	MTBE EPA 8020	MTBE EPA 8240	TPHD LUFT Method
			μg/L	μg/L	µg/L	μg/L	μg/L	μg/L	μg/L	μg/L
=	A-1	02-09-94	3000	560	150	66	190			^650
	A-1	05-04-94	1300	250	61	27	110			^2100
	A-I	08-10-94	27000	3700	1100	540	3000			^3000
	A-1	11-16-94	2100	460	6.4	62	120	••		^^^640
	A-I	03-24-95	1200	230	39	34	66			^^^160
	A-I	06-05-95	1500	310	27	36	76		••	^710
	A-I	08-18-95	1600	470	35	48	110	120	••	^240
	A-1	12-04-95	1200	240	17	25	56		120	••
	A-I	03-13-96	1300	300	74	29	73	100		• •
	A-2	02-09-94	^^260	<0.6	<0.5	<0.5	<0.5			
	A-2	05-04-94	<50	<0.5	<0.5	< 0.5	<0.5		- •	
	A-2	08-10-94	690	47	25	3.9	86			
	A-2	11-16-94	<50	< 0.5	<0.5	<0.5	<0.5			
	A-2	03-24-95	<50	< 0.5	<0.5	<0.5	<0.5			
	A-2	06-05-95	<50	<0.5	<0.5	<0.5	<0.5			••
	A-2	08-17-95	<50	<0.5	<0.5	<0.5	<0.5	12		• •
	A-2	12-04-95	<50	<0.5	<0.5	<0.5	<0.5			~ -
	A-2	03-13-96	<50	<0.5	06	<0.5	1 3	<9		*-
	A-3	02-09-94	<50	<0.5	<0.5	<0.5	<0.5		••	
	A-3	05-04-94	<50	< 0.5	<0.5	<0.5	<0.5	••		••
	A-3	08-10-94	<50	< 0.5	<0.5	<0.5	<0.5			
	A-3	11-16-94	<50	<0.5	<0.5	<0.5	<0.5	••		
	A-3	03-24-95	<50	< 0.5	<0.5	<0.5	< 0.5	••		••
	A-3	06-05-95	Not sampled: not s	cheduled for c	hemical analysi	is				
	A-3	08-17-95	Not sampled not s	cheduled for c	hemical analysi	is				
	A-3	12-04-95	Not sampled: not s	scheduled for c	hemical analysi					
	A-3	03-13-96	<50	<0.5	<0.5	<0.5	<0.5	<3	**	••
	A-4	02-09-94	<50	<0.5	<0.5	<0.5	<0.5			
	۸-4	05-04-94	<50	<0.5	<0.5	<0.5	<0.5		••	
	۸-4	08-10-94	<50	<0.5	<0.5	<0.5	<0.5			
	۸-4	11-16-94	<50	<0.5	<0.5	<0.5	<0.5			••
	۸-4	03-24-95	<50	<0.5	<0.5	<0.5	<0.5		••	
	۸-4	06-05-95	Not sampled not s		-					
	A-4	08-17-95	Not sampled: not s		-					
	۸-4	12-04-95	Not sampled: not s		-			_		
	Λ-4	03-13-96	<50	<0.5	<0.5	<0.5	<0.5	<3	••	

Table 3
Historical Groundwater Analytical Data
1994 - Present*

Date: 05-07-96

•									
Well Designation	Water Sample Field Date	TPHG LUFT Method	Benzene EPA 8020	Toluene EPA 8020	Ethylbenzene EPA 8020	Total Xylenes EPA 8020	MTBE FPA 8020	MTBE EPA 8240	TPHD LUFF Method
		μg/L	μg/L	μg/L	μg/L	μg/L	μg/L	μg/L	µg/L
A-5	02-09-94	2200	190	130	130	310			···
۸-5	05-09-94	13000	1000	1500	490	2000			
A-5	08-10-94	11000	730	930	310	1300			
A-5	11-16-94	2600	160	220	130	400		••	• •
A-5	03-24-95	3300	200	310	130	460		••	••
A-5	06-05-95	57000	2700	4600	1500	6800		••	• •
A-5	08-18-95	34000	1600	2700	1100	5100	<28		
A-5	12-04-95	61	<0.5	<0.5	<0.5	<0.5		• •	• •
A-5	03-13-96	11000	860	960	380	1600	<100	••	• •
A-6	02-09-94	640	<2.9	<3.7	<2.4	<8.2			
Λ-6	05-04-94	260	<0.5	<1.5	<1.5	<0.5		• •	• •
A-6	08-10-94	300	<06	<2.5	<0.8	<1 -1.5			• •
A-6	11-16-94	250	<0.5	<1.5	<0.6	<1.5	••	••	• •
A-6	03-24-95	120	<0.5	<1	<0.5	<1.5 <0.5	••	••	
A-6	06-05-95	160	<0.5	<0.6	<0.5 <2 4	<0.5 <4.2	6		
۸-6	08-18-95	530	<0.5	<0.5	<2 4 880	3600			
A-6	12-04-95	28000	1600	1800 <15	<7	<10	<20		
A-6	03-13-96	1400	<3	<13	ζ,	<10	\2 0		
AR-I	02-09-94	26000	2900	450	920	3000			^4200
AR-I	05-04-94	36000	3400	360	1400	3700			^7200
AR-I	08-10-94	6100	120	66	65	530			^2900
AR-1	11-16-94	1200	66	20	34	210		••	^^^560
AR-I	03-24-95	270	14	0.6	2.5	2.1			^^^130
AR-I	06-05-95	190	10	< 0.5	8.0	0.5			^580
AR-1	08-17-95	960	110	12	4.5	150	14	• •	<50
AR-I	12-04-95	<50	1.5	<0.5	< 0.5	0.8			
AR-1	03-13-96	150	3.8	05	1.4	1.3	<3		
AR-2	02-09-94	^^82	<0.5	<0.5	< 0.5	<0.5			<50
AR-2	05-04-94	<50	<0.5	<0.5	<0.5	<0.5			<50
AR-2	08-10-94	200	5	1.7	2.7	38			^55
AR-2	11-16-94	<50	0.8	<0.5	<0.5	<0.5		••	<50
AR-2	03-24-95	. <50	6.2	<0.5	<0.5	0.6		••	<50
AR-2	06-05-95	<50	<0.5	<0.5	<0.5	<0.5	• -	••	<50
AR-2	08-18-95	<50	<0.5	<0.5	<0.5	<0.5	4	••	<50
AR-2	12-13-95	<50	<0.5	<0.5	<0.5	<0.5	200	••	• -
AR-2	03-13-96	190	26	2.6	3.3	13	200	••	

Table 3
Historical Groundwater Analytical Data
1994 - Present*

Date:	05-07-96
-------	----------

Well Designation	Water Sample Field Date	五 TPHG 答 LUFT Method	त Benzene 7/ EPA 8020	Toluene	Ethylbenzene	는 Total Xylenes 한 EPA 8020	H MTBE	ர் MTBE 7> EPA 8240	n TPHD
ADR-1	02-09-94	3000	380	140	59	240			^110
ADR-I	05-04-94	2100	490	93	68	140			^60
ADR-I	08-10-94	150000	5400	15000	3600	24000	÷-	••	^^^4800
ADR-1	11-16-94	Not sampled well	contained floa	ting product					
ADR-1	03-24-95	Not sampled: well	contained floa	ting product					
ADR-1	06-05-95	23000	310	420	300	1900			^13000
ADR-1	08-18-95	4400	150	120	95	620	120	••	^4500
ADR-1	12-13-95	. 8800	100	130	120	990	• •		
ADR-1	03-13-96	89000	370	1000	840	8100	<500		
ADR-2	02-09-94	83000	6300	6100	2000	11000	••		12000
ADR-2	05-04-94	36000	4600	2600	930	4500	••		^4200
ADR-2	08-10-94	Not sampled: well							
ADR-2	11-16-94	Not sampled well		- 1					
ADR-2	03-24-95	Not sampled, well		- *					
ADR-2	06-05-95	Not sampled, well							
ADR-2	08-17-95	Not sampled, well							
ADR-2	12-13-95	Not sampled, well							
ADR-2	03-13-96	29000	1100	1200	710	3800	<500		• •

µg/L: micrograms per liter

EPA: United Statest Environmental Protection Agency

MTBE: Methyl-tert-butyl ether

TPHG: total petroleum hydrocarbons as gasoline, California DHS LUFT Method

TPHD: total petroleum hydrocarbons as diesel, California DHS LUFT Method

^{--:} not analyzed

^{^:} sample contains a lower boiling point hydrocarbon quantitated as diesel; chromatogram does not match the typical diesel fingerprint

AA: sample contains a single non-fuel component eluting in the gasoline range, and quantified as gasoline

^{^^:} sample contains a mixture of diesel and a lower boiling point hydrocarbon quantitated as diesel; chromatogram does not match the typical diesel fingerprint

^{^^^;} sample contains components cluting in the diesel range, quantified as diesel; chromatogram does not match the typical diesel fingerprint

^{*:} For previous historical analytical data please refer to Fourth Quarter 1995 Groundwater Monitoring Program Results and Remediation System Performance Evaluation Report, ARCO Service Station 2169, 899 West Grand Avenue, Oukland, California, (EMCON, March 4, 1996).

Table 4
Approximate Cumulative Floating Product Recovered

Date:	05	$\Lambda \tau$	06
Date.	0.5-	v.	ーフい

Well Desig- nation	Date	Floating Product Recovered gallons
ADR-1 ADR-2	1994	0.0 0.0
ADR-1 ADR-2	1995	0.0 4.8
ADR-1 ADR-2	1996	0.0 0.0
	1994 to 1996 Total:	4.8

Table 5 Soil-Vapor Extraction System Operation and Performance Data

Facility Number: 2169

Location: 889 West Grand Avenue

Oakland, California

Vapor Treatment Unit: ThermTech Model

VAC-25, 250cfm Thermal/

Catalytic Oxidizer

Consultant: EMCON

1921 Ringwood Avenue San Jose, California

Start-Up Date: 06-02-94 Reporting Period From: 06-02-94

To: 04-01-96

San Jose, California			10: 04	4-01-96	
Beginning Date:	06-02-94	06-02-94	06-07-94	06-16-94	06-22-94
Ending Date:	06-02-94	06-07-94	06-16-94	06-22-94	06-30-94
Down-time (days):	0.00	0.00	0.93	0.00	3.57
Total Operation (days):	0.07	5.05	8.07	6 05	4.43
Total Operation (hours):	1.7	121.3	193.7	145.2	106.3
Operation Hours to Date:	1.7	123.0	316.7	462.0	568.2
TPH Concentrations					
Average Influent (ppmv):	18,000	16,000	830	1,100	230
Average Effluent (ppmv):	ND	45	ND	4.9	75.0
Benzene Concentrations					
Average Influent (ppmv):	250	420	17	24	3 8
Average Effluent (ppmv):	ND	0.30	ND	0.08	0.78
Flow Rates					
Average Influent (scfm):	61.1	131.5	145.3	194.1	176.7
Average Dilution (scfm):	184.2	97.8	69.9	0.0	0.0
Average Effluent (scfm):	268.6	252 3	289.7	264.4	288 9
TPH-G Recovery Data					
Recovery Rate (lbs/hr):	11.12	21.26	1.22	2.16	0.41
Recovery Rate (lbs/day):	266.80	510.34	29.25	51 77	9.86
Destruction Efficiency (%):	100.00	99.46	100.00	99.39	46 70
Product Recovered (lbs):	18.68	2579.35	236.08	313.27	43.64
Product Recovered to Date (lbs):	18.68	2598.02	2834.10	3147.37	3191.01
Product Recovered to Date (gal):	3.11	433.00	472.35	524.56	531.83
Benzene Recovery Data					
Recovery Rate (lbs/hr):	0.185	0.670	0.030	0.056	0.008
Recovery Rate (lbs/day):	4.447	16.076	0.719	1.355	0.195
Destruction Efficiency (%):	100.00	99.86	100.00	99.56	66.45
Product Recovered (lbs):	0.311	81.249	5.802	8.202	0.865
Product Recovered to Date (lbs):	0.311	81.561	87.363	95.565	96.430
Product Recovered to Date (gal):	0.043	11.250	12.050	13.181	13.301

Page 1 Footnotes

ppmv: parts per million by volume

sofm standard cubic feet per minute

lbs/hr: pounds per operational hour

lbs/day: pounds per day

lbs. pounds

gal, gallons

ND: None Detected; Recovery data calculated using laboratory detection limits

Notes:

- 1. Molecular weights used in recovery calculations are 65 for TPH and 78 for benzene.
- 2. Densities used in recovery calculations are 6.0 lbs/gal for TPH and 7.25 lbs/gal for benzene
- 3 All data and calculations on this page were prepared by GeoStrategies, Inc. (GSI), as presented in Letter Report, Vapor Extraction Start Up and Quarterly Groundwater Monitoring, Second Quarter 1994, (GSI, September 1994)

Table 5 Soil-Vapor Extraction System Operation and Performance Data

Number: 2169 Facility

Location: 889 West Grand Avenue

Oakland, California

Vapor Treatment Unit: ThermTech Model

VAC-25, 250cfm Thermal/

Catalytic Oxidizer

Consultant: EMCON

1921 Ringwood Avenue

Start-Up Date: 06-02-94 Reporting Period From: 06-02-94

	San Jose, California		Reporting Per	riod From: 06 To: 04	5-02-94 1-01-96	
Date Begin:		07-01-94	08-01-94	09-01-94	12-01-94	01-01-95
Date End:		08-01-94	09-01-94	12-01-94	01-01-95	02-01-95
Mode of Oxidation:		Therm-Ox	Cat-Ox	Cat-Ox	Cat-Ox	Cat-Ox
Days of Operation:		10.66	17.26	34.73	16.08	25 62
Days of Downtime:		20.34	13 74	56.27	14 92	5.38
Average Vapor Conc						
Well Field Influer	nt: ppmv (2) as gasoline	1983	680	450	1500	<15
	mg/m3 (3) as gasoline	5333	1800	1200	5600	<60
	ppmv as benzene	29	7.6	2.9	7	<0 1
	mg/m3 as benzene	95	25	9 4	22	<0.5
System Influer	nt: ppmv as gasoline	1983	680	450	400	<15
	mg/m3 as gasoline	5333	1800	1200	1600	<60
	ppmv as benzene	29	76	2.9	1.9	<0.1
	mg/m3 as benzene	95	25	9.4	6	<0.5
System Effluer	nt: ppmv as gasoline	17	44	4.1	<15	<15
	mg/m3 as gasoline	46	118	11.1	<60	<60
	ppmv as benzene	0.15	0.7	0.04	<0.1	<0.1
	mg/m3 as benzene	0.49	2.3	0 143	<0.5	< 0.5
Average Well Field Fle	ow Rate (4), scfm (5):	198.3	212.6	214.3	177	16.7
Average System Influe	ent Flow Rate (4), scfm:	198.3	212.6	214.3	120.1	164.3
Average Destruction I	Efficiency (6), percent (7):	99.1	93.4	99.1	96.3	NA
Average Emission Ra	tes (8), pounds per day (9)					
Gasoline.		0.82	2.25	0.21	0 65	0.89
Benzene:		10.0	0.04	0.00	0 01	0 01
Operating Hours This I	Period:	<u>255,95</u>	414,28	833.57	385,86	614.80
Operating Hours To D	ate:	256.0	670 2	1503.8	1889 7	2504 5
Pounds/ Hour Remova	1 Rate, as gasoline (10)	3 96	1.43	0.96	0.37	0.00
Pounds Removed This	Period, as gasoline (11):	1013.1	<u>593,4</u>	802.3	143.1	2.3
Pounds Removed To E	Date, as gasoline:	4204.1	4797.4	5599.7	5742.9	5745.2
Gallons Removed This	Period, as gasoline (12):	163,4	95.7	<u>129.4</u>	23.1	0.4
Gallons Removed To I	Date, as gasoline:	678.1	773.8	903.2	926.3	926.7

Table 5 Soil-Vapor Extraction System Operation and Performance Data

Number: 2169 Vapor Treatment Unit: ThermTech Model Facility

Location: 889 West Grand Avenue VAC-25, 250cfm Thermal/ Oakland, California

Catalytic Oxidizer

Start-Up Date: 06-02-94 Consultant, EMCON

1921 Ringwood Avenue San Jose, California			riod From: 00 To: 04		
Date Begin:	02-01-95	07-01-95	08-01-95	09-01-95	10-01-95
Date End:	07-01-95	08-01-95	09-01-95	10-01-95	11-01-95
Mode of Oxidation:	Cat-Ox	Cat-Ox	Cat-Ox	Cat-Ox	Cat-Ox
Days of Operation:	0.00	14.42	19.27	27.18	11.59
Days of Downtime.	150 00	16.58	11.73	2.82	19.41
Average Vapor Concentrations (1)					
Well Field Influent ppmv (2) as gasoline	NA (13)	1567	1975	1400	250
mg/m3 (3) as gasoline	NA	5767	7175	5200	900
ppmv as benzene	NA	12	10	3.1	0.6
mg/m3 as benzene	NA	40	33	10	1.7
System Influent: ppmv as gasoline	NA	200	270	230	66
mg/m3 as gasoline	NA	740	970	920	240
ppmv as benzene	NA	1.6	1	0.6	0.1
mg/m3 as benzene	NA	5.2	3.3	18	< 0.5
System Effluent: ppmv as gasoline	NA	23	<15	<15	<15
mg/m3 as gasoline	NA	83	<60	<60	<60
ppmv as benzene	· NA	<01	<0.1	<0.1	< 0.1
mg/m3 as benzene	NA	<0.5	<0.5	<0.5	<0.5
Average Well Field Flow Rate (4), scfm (5):	0.0	27.9	43 0	58.1	67.0
Average System Influent Flow Rate (4), scfm:	0.0	197.6	166.8	167.9	174.1
Average Destruction Efficiency (6), percent (7):	NA	88.8	93 8	93.5	75.0
Average Emission Rates (8), pounds per day (9)					
Gasoline:	0.00	1.47	0.90	0.90	0.94
Benzene:	0.00	0 01	0 01	0.01	0 01
Operating Hours This Period:	0.00	346,17	462,40	652.27	278.16
Operating Hours To Date	2504.5	2850.6	3313.0	3965.3	4243 5
Pounds/ Hour Removal Rate, as gasoline (10):	0 00	0.60	1.15	1 13	0.23
Pounds Removed This Period, as gasoline (11):	<u>0 0</u>	208.5	533.9	<u>737 6</u>	62.8
Pounds Removed To Date, as gasoline:	5745.2	5953.6	6487.6	7225 1	7287.9
Gallons Removed This Period, as gasoline (12):	0.0	33.6	<u>86.1</u>	<u>119.0</u>	<u>10.1</u>
Gallons Removed To Date, as gasoline:	926 7	960.3	1046.4	1165.4	1175.5

Table 5 Soil-Vapor Extraction System Operation and Performance Data

Facility Number: 2169

Location: 889 West Grand Avenue

Oakland, California

Vapor Treatment Unit: ThermTech Model

VAC-25, 250cfm Thermal/

Catalytic Oxidizer

Consultant	: EMCON 1921 Ringwood Avenue San Jose, California			Up Date: 06-02-94 d From: 06-02-94 To: 04-01-96	
Date Begin:		11-01-95	01-01-96		
Date End:		01-01-96	04-01-96		
Mode of Oxidation:		Cat-Ox	Cat-Ox		
Days of Operation:		0.00	0.00		
Days of Downtime:		61.00	91.00		
Average Vapor Concer	atrations (1)				
Well Field Influent	: ppmv (2) as gasoline	NA	NA		
	mg/m3 (3) as gasoline	NA	NA		
	ppmv as benzene	NA	NA		
	mg/m3 as benzene	NA	NA		
System Influent	: ppmv as gasoline	NA	NA		
•	mg/m3 as gasoline	NA	NA		
	ppmv as benzene	NA	NA		
	mg/m3 as benzene	NA	NA		
System Effluent	: ppmv as gasoline	NA	NA		
•	mg/m3 as gasoline	NA	NA		
	ppmv as benzene	NA	NA		
	mg/m3 as benzene	NA	NA		
Average Well Field Flow	w Rate (4), sofm (5)	0.0	0.0		
Average System Influen		0.0	0.0		
0 ,	ficiency (6), percent (7):	0.0	0.0		
Average Emission Rate	es (8), pounds per day (9)				
Gasoline:		0.00	0.00		
Benzene:		0.00	0.00		
Operating Hours This Po	eriod:	0.00	0.00		
Operating Hours To Dat		4243.5	4243.5		
Pounds/ Hour Removal	Rate, as gasoline (10):	0.00	0 00		
Pounds Removed This F	Period, as gasoline (11):	0.0	0.0		
Pounds Removed To Da	_	7287.9	7287 9		
Gallons Removed This I	Period, as gasoline (12):	0.0	0.0		
Gallons Removed To D		1175.5	1175.5		

Table 5 Soil-Vapor Extraction System Operation and Performance Data

Facility Number: 2169

Vapor Treatment Unit: ThermTech Model

Location: 889 West Grand Avenue

VAC-25, 250cfm Thermal/

Oakland, California

Catalytic Oxidizer

Consultant: EMCON

Start-Up Date: 06-02-94

1921 Ringwood Avenue

Reporting Period From: 06-02-94

San Jose, California

To 04-01-96

04-01-96 CURRENT REPORTING PERIOD. 01-01-96 to 2184.0 DAYS / HOURS IN PERIOD: 91.0 DAYS / HOURS OF OPERATION: 0.0 0.0 DAYS / HOURS OF DOWN TIME: 91.0 2184.0 0.0 % PERCENT OPERATIONAL: PERIOD POUNDS REMOVED: 0.0 0.0 PERIOD GALLONS REMOVED: AVERAGE WELL FIELD FLOW RATE (scfm): 0.0 0.0 AVERAGE SYSTEM INFLUENT FLOW RATE (scfm):

concentration (as gasoline in mg/m3) = [concentration (as gasoline in ppmv) x 65 lb/lb-mole / 24.05 (lb/m3/lb-mole of air)/mg] (rounded as appropriate) concentration (as benzene in mg/m3) = [concentration (as benzene in ppmv) x 78 lb/lb-mole / 24.05 (lb/m3/lb-mole of air)/mg] (rounded as appropriate) For the period from December 1, 1994, to July 1, 1995, ppmv results were converted to mg/m3 using the following formula:

concentration (as gasoline in mg/m3) = [concentration (as gasoline in ppmv) x 87 lb/lb-mole / 24 05 (lb/m3/lb-mole of air)/mg] (rounded as appropriate) concentration (as benzene in mg/m3) = [concentration (as benzene in ppmv) x 78 lb/lb-mole / 24.05 (lb/m3/lb-mole of air)/mg] (rounded as appropriate) After July 1, 1995, all vapor results were reported by the laboratory in ppmv and mg/m3.

- 4. Average flow rates (time weighted average) are based on instantaneous flow rates recorded during the month; refer to Appendix C for instantaneous flow data.
- 5. scfm. flow in standard cubic feet per minute at one atmosphere and 70 degrees Fahrenheit
- 6. Average destruction efficiencies are calculated using monthly average concentrations; refer to Appendix C for instantaneous destruction efficiency data
- 7 destruction efficiency, percent = ([system influent concentration (as gasoline in mg/m3)] system effluent concentration (as gasoline in mg/m3)] / system influent concentration (as gasoline in mg/m3)) x 100 percent
- 8. Average emission rates are calculated using monthly average concentrations and flow rates; refer to Appendix C for instantaneous emission rate data.
- emission rates (pounds per day) = system effluent concentration (as gasoline or benzene in mg/m3) x system influent flow rate (scfm) x 0 02832 m3/ft3
 x 1440 minutes/day x 1 pound/454,000 mg
- 10 pounds/hour removal rate (as gasoline) = well field influent concentration (as gasoline in mg/m3) x well field influent flow rate (scfm) x 0.02832 m3/ft3 x 60 minutes/hour x 1 pound/454,000 mg
- 11. pounds removed this period (as gasoline) = pounds/ hour removal rate x hours of operation
- 12. gallons removed this period (as gasoline) = pounds removed this period (as gasoline) x 0.1613 gallons/pound of gasoline
- 13. NA not applicable, not analyzed, or not available

¹ Average concentrations are based on discrete sample results reported during the month; refer to Appendix C for discrete sample results

² ppmv: parts per million by volume

^{3.} mg/m3; milligrams per cubic meter

For the period from July 1 to December 1, 1994, ppmv results were converted to mg/m3 using the following formula:

Table 6
Soil-Vapor Extraction Well Data

Date: 05-17-96

						Well Idea	ntification					
		A-1		1	A-2			A-3			A-4	
	Valve		Vacuum	Valve		Vacuum	Valve		Vacuum	Valve		Vacuum
Date	Position	TVHG	Response	Position	TVHG	Response	Position	TVHG	Response	Position	TVHG	Response
		ppmv	in-H2O		ppmv	ın-H2O		ppmv	ın-H2O		ppmv	ın-H2O
or SVE well m	T nonitoring data prior	to January 1, 199	5, please refer to	T the third quarter 199	95 groundwater n	nonitoring report fo	r this site.					
01-13-95	passive	NA	0	passive	NA	0	passive	NA	0	passive	NA	0
01-26-95	passive	NA	0	passive	NA	0	passive	NA	0	passive	NA	0
07-17-95	System was shut	down on January	26, 1995.	System was restar	ted on July 17, 19	995.						
07-17-95	closed	NA	NA	closed	NA	NA	closed	NA	NA	closed	NA	NA
07-25-95	closed	NA	NA	closed	NA	NA	closed	NA	NA	closed	NA	NA
08-22-95	closed	NA	NA	closed	NA	NA	closed	NA	NA	closed	NA	NA
09-21-95	closed	NA	0	closed	NA	0	closed	NA	Ð	closed	NA	0
09-21-95	open	NA	46	closed	NA	0	closed	NA	0	closed	NA	0
09-21-95	open	600 LAB	NA	closed	NA	NA	closed	NA	NA	closed	ŃΑ	NA
10-12-95	open	NA	36	closed	NA	-1	closed	NA	0	closed	NA	0
10-12-95	System was mant	ally shut down.							i			
	1								Į			
	İ											
				1								

TVHG: concentration of total volatile hydrocarbons as gasoline

ppmv: parts per million by volume

in-H2O, inches of water

open: open to the system

passive open to the atmosphere

closed closed to the system and atmosphere

NA, not analyzed or not measured

FID: TVHG concentration was measured with a portable flame ionization detector

LAB TVHG concentration was analyzed in the laboratory

PID TVHG concentration was measured with a portable photoionization detector

Table 6
Soil-Vapor Extraction Well Data

Date: 05-17-96

						Well Iden	ttrication					
		AV-I			AV-2	·		AV-3	_		AV-4	
Date	Valve Position	TVHG	Vacuum Response	Valve Position	TVHG	Vacuum Response	Valve Position	TVHG	Vacuum Response	Valve Position	TVHG	Vacuum Response
		ppmv	in-H2O		ppmv	in-H2O		ppmv	in-H2O		ppmv	in-H2O
or SVE well m	onitoring data prior	to January 1, 199	5, please refer to	T the third quarter 19	95 groundwater m	onitoring report fo	r this site.					
01-13-95	passive	NA	15	passive	NA	0	passive	NA	0	open	463 PID	16
01-26-95	passive	NA	27	passive	NA	0	passive	NA	0	open	1.8 FID	30
07-17-95	System was shut	down on January 2	26, 1995.	System was resta	rted on July 17, 19	95			1			
07-17-95	open	NA	NA	open	NA	NA	open	NA	NA	closed	NA	NA
07-25-95	open	1026 PID	42	open	1364 PID	42	open	869 PID	42	closed	NA	NA
07-25-95	open	1200 LAB	NA	open	1600 LAB	NA	open	980 LAB	NA	closed	NA	NA
08-22-95	open	NA	42	open	NA	44	ореп	NA	44	closed	NA	NA
09-21-95	ореп	NA	43	open	NA	47	open	NA	47	closed	NA	0
09-21-95	open	NA	46	open	NA	46	open	NA	46	closed	NA	1
10-12-95	open	NA	44	open	NA	43	ореп	NA	43	closed	NA	1
10-12-95	System was man	aally shut down.										

TVHG: concentration of total volatile hydrocarbons as gasoline

ppmv parts per million by volume

in-H2O: inches of water

open, open to the system

passive: open to the atmosphere

closed: closed to the system and atmosphere

NA: not analyzed or not measured

FID TVHG concentration was measured with a portable flame ionization detector

LAB TVHG concentration was analyzed in the laboratory

PID. TVHG concentration was measured with a portable photoionization detector

Table 6
Soil-Vapor Extraction Well Data

Date: 05-17-96

	-				Weli Iden	tification					
	AV-5		T	AV-6			AV-7			AR-2	****
Valve		Vacuum	Valve		Vacuum	Valve		Vacuum	Valve		Vacuum
Position	TVHG	Response	Position	TVHG	Response	Position	TVHG	Response	Position	TVHG	Response
	ppmv	in-H2O		ppmv	in-H2O		ppmv	ın-H2O		ppmv	in-H2O
T initoring data prior	to January 1, 199	5, please refer to	I the third quarter 19	95 groundwater m	onitoring report fo	r this site.					
passive	NA	1	open	46 PID	16	passive .	NA	0	passive	NA	0
open	2.2 FID	30	open	2.3 FID	30	passive	NA	0	passive	NA	0
System was shut of	lown on January	26, 1995.	System was resta	nted on July 17, 19	95						
closed	NA	NA	closed	NA	NA	closed	NA	NA	closed	NA	NA
closed	NA	NA	closed	NA	NA	closed	NA	NA	closed	NA	NA
closed	NA	NA	closed	NA	NA	closed	NA	NA	open	NA	44
closed	NA	0	closed	NA	0	closed	NA	0	open	NA	48
closed	NA	0	open	NA	46	closed	NA	0	open	NA	46
closed	NA	NA	open	2300 LAB	NA	closed	NA	NA	open	NA	NA
closed	NA	0	open	NA	42	closed	NA	0	open	NA	43
System was manu	ally shut down										
	Position nitoring data prior passive open System was shut d closed closed closed closed closed closed closed closed	Valve Position TVHG ppmv nitoring data prior to January 1, 199 passive NA open 2.2 FID System was shut down on January closed NA	Valve Position TVHG Response ppmv in-H2O nitoring data prior to January 1, 1995, please refer to passive NA open 2.2 FID 30 System was shut down on January 26, 1995. closed NA NA NA NA	Valve Position TVHG Response Position ppmv in-H2O nitoring data pnor to January 1, 1995, please refer to the third quarter 15 passive NA 1 open open 2.2 FID 30 open System was shut down on January 26, 1995. closed NA NA closed closed NA NA o closed closed NA NA O open open closed NA NA O open open open open	Valve Position TVHG Response Position TVHG Position TVHG Response Position TVHG Position TVHG Position TVHG Popmv in-H2O ppmv nitoring data prior to January 1, 1995, please refer to the third quarter 1995 groundwater m passive NA 1 open 46 PID open 2.2 FID 30 System was shut down on January 26, 1995. closed NA NA closed NA NA closed NA closed NA NA closed NA open 2300 LAB closed NA Open NA	Valve Vacuum Position TVHG Response Position	Valve Position TVHG Response Position TVHG Response Position ppmv in-H2O ppmv in-H2O nitoring data prior to January 1, 1995, please refer to the third quarter 1995 groundwater monitoring report for this site, open 46 PID 16 passive open 2.2 FID 30 open 2.3 FID 30 passive System was shut down on January 26, 1995. closed NA NA Closed NA NA Closed Closed NA NA Closed closed NA NA Closed Closed NA NA O closed NA NA O closed NA NA O closed NA NA O closed NA O closed NA NA O closed Closed NA NA O closed NA O open NA 46 closed Closed NA NA O open 2300 LAB NA Closed Closed NA O open NA 42 closed Closed NA O open NA 42 closed	Valve Position TVHG Response Position TVHG Position Position TVHG Position Position TVHG Posi	Name	Valve Vacuum Valve Position TVHG Response Pos	AV-5 Valve Vacuum Valve Vacuum Valve Vacuum Valve Position TVHG Response Position TVHG Ppmv In-H2O Ppmv

TVHG: concentration of total volatile hydrocarbons as gasoline

ppmv parts per million by volume

in-H2O inches of water

open open to the system

passive open to the atmosphere

closed: closed to the system and atmosphere

NA not analyzed or not measured

FID: TVHG concentration was measured with a portable flame ionization detector

LAB: TVHG concentration was analyzed in the laboratory

PID: TVHG concentration was measured with a portable photoionization detector

Table 6
Soil-Vapor Extraction Well Data

Date: 05-17-96

						Well lde	tification	-			-	
		ADR-1		T	ADR-2							
	Valve	*	Vacuum	Valve		Vacuum	Valve		Vacuum	Valve		Vacuum
Date	Position	TVHG	Response	Position	TVHG	Response	Position	TVHG	Response	Position	TVHG	Response
		ppmv	ın-H2O		ppmv	in-H2O		ppmv	in-H2O		ppmv	ın-H2O
For SVE well m	onitoring data prior	r to January I, 199	5, please refer to	I the third quarter 19	95 groundwater m	onitoring report fo	r this site.				· · · · · · · · · · · · · · · · · · ·	
01-13-95	open	58 PID	16	open	160 PID	16						
01-26-95	open	2.2 FID	30	open	4.4 FID	30						
07-17-95	System was shut	down on January	26, 1995.	System was resta	rted on July 17, 19	95						
07-17-95	open	NA	NA	open	NA	NA						
07-25-95	open	1184 PID	42	open	1057 PID	42						
07-25-95	open	1400 LAB	NA	open	1300 LAB	NA						
08-22-95	open	NA	44	open	NA	44						
09-21-95	open	NA	48	open	NA	47	İ					
09-21-95	open	NA	45	open	NA	46						
10-12-95	open	NA	43	open	NA	44						
10-12-95	System was man	ually shut down.										
1				1			1		'			
ļ												
							ļ					
1]					
							İ					
							1					
ţ				1						[
				1 .								

TVHG: concentration of total volatile hydrocarbons as gasoline

ppmv parts per million by volume

m-H2O, inches of water

open open to the system

passive open to the atmosphere

closed, closed to the system and atmosphere

NA, not analyzed or not measured

FID: TVHG concentration was measured with a portable flame ionization detector

LAB TVHG concentration was analyzed in the laboratory

PID: TVHG concentration was measured with a portable photoionization detector

Table 7 Air-Sparge System Operation and Performance Data

Air-Sparge Unit:* Facility Number: 2169

Location: 889 West Grand Avenue

Oakland, California

3-horsepower Conde blower 5-horsepower air compressor

Consultant: EMCON

1921 Ringwood Avenue San Jose, California

Start-Up Date: 07-15-94 Reporting Period From: 07-15-94

To: 04-01-96

			System was	shut down	on 10-12-9	6
Date Begin:	07-15-94	08-01-94	08-01-94	08-01-94	08-15-94	09-13-94
Date End:	08-01-94	08-01-94	08-01-94	08-15-94	09-13-94	11-28-94
Days of Operation:	5.5	0.0	0.1	19.3	27.2	0.0
Days of Downtime:	10.5	0.0	0.0	11.7	2.8	76.0
Air-Sparge Well Status:						
AS-1	open	open	open	open	open	closed
AS-2	open	open	open	open	open	closed
AS-3	open	open	open	open	open	closed
AS-4	open	open	open	open	open	closed
AS-5	open	open	open	open	open	closed
Air-Sparge Well Pressure (psig) (1):						
AS-1	2.8	2.8	3.0	2.0	2.4	0.0
AS-2	3.0	3.0	2.8	2.2	2.4	0.0
AS-3	3.6	3.6	3.8	3.1	2.2	0.0
AS-4	3.1	3.1	3.4	3.0	2.8	0.0
AS-5	2.8	2.8	3.2	2.8	3.2	0.0
Total Air-Sparge Flow Rate (scfm) (2):	25.0	29.0	29.0	27.0	29.0	0.0
Total Air-Sparge Pressure (psig):	5.0	2.8	2.8	2.6	3.0	0.0
Dissolved Oxygen (mg/L) (3): Air-Sparge Wells:						
AS-1	NA (4)	NA	NA	NA	NA	1.4
AS-2	NA	NA	NA	NA	NA	1.2
AS-3	NA	NA	NA	NA	NA	1.2
AS-4	NA	NA	NA	NA	NA	0.8
AS-5	NA	NA	NA	NA	NA	1.4
Depth to Water (ft-BGS) (5):						
Air-Sparge Wells:						
AS-1	NA	NA	NA	NA	NA	10.55
AS-2	NA	NA	NA	NA	NA	11.29
AS-3	NA	NA	NA	NA	NA	10.78
AS-4	NA	NA	NA	NA	NA	10.27
AS-5	NA	NA	NA	NA	NA	10.65

Table 7 Air-Sparge System Operation and Performance Data

Facility Number: 2169

Location: 889 West Grand Avenue

Air-Sparge Unit:* 3-horsepower Conde blower

Oakland, California

5-horsepower air compressor

Consultant: EMCON

Start-Up Date: 07-15-94 Reporting Period From: 07-15-94

1921 Ringwood Avenue

San Jose, California

To: 04-01-96 System was shut down on 10-12-96

Date Begin:				System was	shut down	on 10-12-9	6
Date End: 01-03-95 Days of Operation: 00-03-95 Days of Operation: 01-03-95 Days of Operation: 03-31-95 Days of Operation: 08-10-95 Days of Operation: 08-10-95 Days of Operation: 0.0 Days of Downtime: 0.0 Downtime: <th>Date Begin:</th> <th>11-28-94</th> <th>01-03-95</th> <th>02-03-95</th> <th>03-31-95</th> <th>07-25-95</th> <th>08-10-95</th>	Date Begin:	11-28-94	01-03-95	02-03-95	03-31-95	07-25-95	08-10-95
Days of Downtime: 36.0 31.0 56.0 89.0 14.0 12.0		01-03-95	02-03-95	03-31-95	06-28-95	08-10-95	08-22-95
Air-Sparge Well Status: AS-1	Days of Operation:	0.0	0.0				
AS-1 closed closed closed closed closed closed closed closed closed AS-2 closed closed closed closed closed closed closed AS-3 closed closed closed closed closed AS-4 closed closed closed closed closed AS-4 closed closed closed closed closed closed AS-4 closed closed closed closed closed closed closed closed AS-5 closed cl	Days of Downtime:	36.0	31.0	56.0	89.0	14.0	12.0
AS-2 closed closed closed closed closed closed closed AS-3 closed closed closed closed closed closed closed closed AS-4 closed c	Air-Sparge Well Status:						
AS-3	AS-I	•				•	•
AS-4	AS-2	closed	closed				
AS-5 closed closed closed closed closed closed closed closed closed Air-Sparge Well Pressure (psig) (1): AS-1 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.	AS-3	closed	closed	closed	closed	closed	closed
Air-Sparge Well Pressure (psig) (1): AS-1 AS-2 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0	AS-4	closed	closed	closed	closed	open	open
AS-1 AS-2 AS-5 Dissolved Oxygen (mg/L) (3): AS-3 AS-2 AS-3 AS-3 AS-3 AS-3 AS-3 AS-3 AS-3 AS-3	AS-5	closed	closed	closed	closed	closed	closed
AS-1 AS-2 AS-5 Dissolved Oxygen (mg/L) (3): AS-3 AS-2 AS-3 AS-3 AS-3 AS-3 AS-3 AS-3 AS-3 AS-3	Air-Sparge Well Pressure (psig) (1):						
AS-2 AS-3 O.0 O.0 O.0 O.0 O.0 O.0 O.0 O.0 O.0 O.0		0.0	0.0	0.0	0.0	8.9	5.5
AS-3 AS-4 AS-5 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0		0.0	0.0	0.0	0.0	0.0	0.0
AS-4 AS-5 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0		0.0	0.0	0.0	0.0	0.0	0.0
AS-5 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0		0.0	0.0	0.0	0.0	2.0	2.3
Total Air-Sparge Pressure (psig): Dissolved Oxygen (mg/L) (3): Air-Sparge Wells: AS-1 NA NA NA NA NA NA NA NA NA N		0.0	0.0	0.0	0.0	0.0	0.0
Dissolved Oxygen (mg/L) (3): Air-Sparge Wells: AS-1	Total Air-Sparge Flow Rate (scfm) (2):	0.0	0.0	0.0	0.0	2.0	2.0
Air-Sparge Wells: AS-1 AS-2 NA NA NA NA NA NA NA NA NA N	Total Air-Sparge Pressure (psig):	0.0	0.0	0.0	0.0	50	45
AS-1	Dissolved Oxygen (mg/L) (3):						
AS-2 AS-3 NA NA NA NA NA NA NA NA NA N	Air-Sparge Wells:						
AS-3 AS-4 AS-4 NA NA NA NA NA NA NA NA NA N	AS-1	NA	NA	NA	NA	1.1	
AS-4 AS-5 NA NA NA NA NA NA NA NA NA NA NA NA NA	AS-2	NA	NA	NA	NA	NA	NA
AS-5 NA NA NA NA 1.0 NA Depth to Water (ft-BGS) (5): Air-Sparge Wells: AS-1 NA NA 8.79 NA 11.75 NA AS-2 NA NA NA 9.37 NA NA NA AS-3 NA NA NA 8.93 NA NA NA AS-4 NA NA NA 8.43 NA 11.31 NA	AS-3	NA	NA	NA	NA	NA	NA
Depth to Water (ft-BGS) (5): Air-Sparge Wells: AS-1	AS-4	NA	NA	NA	NA	1.4	
Air-Sparge Wells: NA NA 8.79 NA 11.75 NA AS-1 NA NA NA 9.37 NA NA NA AS-2 NA NA NA 9.37 NA NA NA AS-3 NA NA NA NA NA NA NA AS-4 NA NA 8.43 NA 11.31 NA	AS-5	NA	NA	NA	NA	1.0	NA
Air-Sparge Wells: NA NA 8.79 NA 11.75 NA AS-1 NA NA NA 9.37 NA NA NA AS-2 NA NA NA 9.37 NA NA NA AS-3 NA NA NA NA NA NA NA AS-4 NA NA 8.43 NA 11.31 NA	Depth to Water (ft-BGS) (5):						
AS-1 NA NA 8.79 NA 11.75 NA AS-2 NA NA NA 9.37 NA NA NA AS-3 NA NA NA NA NA NA NA NA NA NA NA NA NA							
AS-2 NA NA 9.37 NA NA NA AS-3 NA NA NA NA NA NA NA NA NA NA NA NA NA	· -	NA	NA	8.79	NA		NA
AS-3 NA NA 8.93 NA NA NA AS-4 NA NA NA 8.43 NA 11.31 NA		NA	NA	9.37	NA	NA	NA
AS-4 NA NA 8.43 NA 11.31 NA		NA	NA	8.93	NA	NA	NA
		NA	NA	8.43	NA	11.31	NA
	AS-5	NA	NA	8.80	NA	11.62	NA

Table 7 Air-Sparge System Operation and Performance Data

Facility Number: 2169		Air-Sparge		er Conde blo	NIVA#
Location: 889 West Grand Ave Oakland, California	enue			er Conde bic er air compr	
Consultant: EMCON 1921 Ringwood Ave San Jose, California	nue	Re		t-Up Date: 0 od From: 0 To: 0	
Jun voso, Camorina		_	System was	shut down o	
Date Begin:	08-22-95	09-21-95	10-12-95	01-01-96	
Date End:	09-21-95	10-12-95	01-01-96	04-01-96	
Days of Operation:	10.9	NA	NA	NA	
Days of Downtime:	18.6	NA	NA	NA	
Air-Sparge Well Status:					
AS-1	open	closed	closed	closed	
AS-2	closed	closed	closed	closed	
AS-3	closed	closed	closed	closed	
AS-4	open	closed	closed	closed	
AS-5	open	closed	closed	closed	
Air-Sparge Well Pressure (psig) (1):					
AS-1	7.0	0.0	0.0	0.0	
AS-2	0.0	0.0	0.0	0.0	
AS-3	0.0	0.0	0.0	0.0	
AS-4	1.5	0.0	0.0	0.0	
AS-5	1.0	0.0	0.0	0.0	
Total Air-Sparge Flow Rate (scfm) (2):	6.0	0.0	0.0	0.0	
Total Air-Sparge Pressure (psig):	45	0	0	0	
Dissolved Oxygen (mg/L) (3):					
Air-Sparge Wells:					
AS-1	NA	7.4	NA	NA	
AS-2	NA	NA	NA	NA	
AS-3	NA	NA	NA	NA	
AS-4	NA	1.5	NA	NA	
AS-5	NA	1.6	NA	NA	
Depth to Water (ft-BGS) (5):					
Air-Sparge Wells:					
AS-1	NA	12.12	NA	NA	
AS-2	NA	NA	NA	NA	
AS-3	NA	NA	NA	NA	
AS-4	NA	11.78	NA	NA	
AS-5	NA	12.05	NA	NA	

Table 7 Air-Sparge System Operation and Performance Data

Facility Number: 2169

Air-Sparge Unit:*

Location: 889 West Grand Avenue

Oakland, California

3-horsepower Conde blower

5-horsepower air compressor

Consultant: EMCON

Start-Up Date: 07-15-94 Reporting Period From: 07-15-94

1921 Ringwood Avenue

To: 04-01-96

San Jose, California

System was shut down on 10-12-96

CURRENT REPORTING PERIOD:

DAYS / HOURS IN PERIOD:

DAYS / HOURS OF OPERATION: DAYS / HOURS OF DOWN TIME: PERCENT OPERATIONAL:

01-01-96 04-01-96 to

> 91.0 2184 NA NA

NA NA NA

^{1.} psig: pounds per square inch gauge


^{2.} scfm: standard cubic feet per minute at 14.7 psi and 70° F

^{3.} mg/L: milligrams per liter

^{4.} NA: not available or not analyzed

^{5.} ft-BGS: feet below grade surface

During the period from July 15, 1994 to July 25, 1995 the air-sparge system used a 3-horsepower Conde blower. On July 25, 1995, it was replaced with a 5-horsepower air compressor.






ARCO PRODUCTS COMPANY SERVICE STATION 2169, 889 WEST GRAND AVE. QUARTERLY GROUNDWATER MONITORING OAKLAND, CALIFORNIA

SITE LOCATION

FIGURE

1
PROJECT NO. 805-129.03



GROUNDWATER DATA


FIRST QUARTER 1996

805-129.003

G:\805-129\G00 REV 0 06/10/96 12:58:58 DD DJ

ARCO Service Station 2169
Soil-Vapor Extraction and Treatment System
Historical System Influent TVHG and Benzene Concentrations

Figure 4




TVHG total volatile hydrocarbons as gasoline ppmv; parts per million by volume

esj/h:\2169\2169tdb.xls\SVE Model:imi 20805-129.003

Figure 5

ARCO Service Station 2169

Soil-Vapor Extraction and Treatment System
Historical Hydrocarbon Removal Rates



esj/h:\2169\2169tss.xls\SVE Model:imi 20805-129.003

APPENDIX A

FIELD DATA SHEETS, FIRST QUARTER 1996 GROUNDWATER MONITORING EVENT

MW-3 Semmany

FIELD REPORT
DEPTH TO WATER/FLOATING PRODUCT SURVEY

1 Ww.1

PROJECT #: 21775-235.002 STATION ADDRESS: 899 West Grand Avenue, Oakland

DATE: 3-1-96

4

ARCO STATION #: 2169

FIELD TECHNICIAN: M. ROSS

DAY: FRIDAY

		Well	Well			Locking	FIRST	ČEOONID.	DESTILE	51.0.1=0.1=		,
DTW	WELL	Box	Lid		,			SECOND	DEPTH TO	FLOATING	WELL	
Order	ID				7	Well	DEPTH TO	DEPTH TO	FLOATING	PRODUCT 1	TOTAL	
Order	טו	Seal	Secure	Gasket	Lock	Cap	WATER	WATER	PRODUCT	THICKNESS	DEPTH	COMMENTS
				-	<u> </u>		(feet)	(feet)	(feet)	(feet)	(feet)	Y
1	A-2	OK	>\cdot S	Y05	No	NO	9,34	9.34	NA	MA	25.3	white IN Box
2	A-3	OK	1/15	125	Νo	NO	9,90	9,90	MA	NA		Water in 130x TO C.
3	A-4	9K	Vis	Vin	$\wedge \mathcal{O}$	NO	8.55	8.55	NA	NA	28.5	Wester IN BUX T.O.C
4	AR-2	OK	1/5	125	NP	20	9.83	9.83	NA	NA	29.2	
5	A-6	ا کارن	45	NO	109	105	8.21	8.21	NA		27,8	
6	AR-1	OK	6.	Young	13/7	NO	819	8.19	75	MA	28.0	WARDER (N BOX T.O. C.
7	A-1	0K	805	Yes	NO	NO	3.78	D. 22	NA	NO	24.5	Worth IN BOX TO.C
8	A-5	OK	105	NO	Var	205	7.11	8.11	NA	MA	29.4	With IN BOX
9	ADR-1	OK	Y	Y95	NO	No	8.76	8-76	NO	MA	21,3	
10	ADR-2	00	19	Μ	100	20	8.74	3.74	No	Nn	26,5	•
					SI	JRVE	POINTS A	ARE TOP C	F WELL C	ASINGS		
												

* NO BUTS IN LIE

Rev.	3,	2/94
------	----	------

WATER SAMPLE FIELD DATA SHEET
EMCON PROJECT NO: 2/775-235.002 SAMPLE ID: A -1 (24')
PURGED BY: M. Galle Gas / Twilliams CLIENT NAME: ARCOH 2/49
SAMPLED BY: LOCATION: CAKLAND, CA
TYPE: Ground Water X Surface Water Treatment Effluent Other
CASING DIAMETER (inches): 2 3 4 4.5 6 Other
CASING ELEVATION (feet/MSL): $\frac{1}{24}$ VOLUME IN CASING (gal.): $\frac{5194}{17,89}$ DEPTH TO WATER (feet): $\frac{8123}{17,89}$ CALCULATED PURGE (gal.): $\frac{17,89}{17,89}$
DEPTH OF WELL (feet): 24.5 ACTUAL PURGE VOL. (gal.): 18.0
DATE PURGED: 3-13-96 Start (2400 Hr) 1250 End (2400 Hr) 1254
DATE SAMPLED: Start (2400 Hr) End (2400 Hr)
TIME VOLUME PH E.C. TEMPERATURE COLOR TURBIDITY
(2400 Hr) (gal.) (units) (μmhos/cm@ 25° C) (°F) (visual) (visual)
1252 6.0 7.10 1318 70.6 Mosty Light
1253 120 6.98 1294 70.5
1254 180 6.93 1296 70.7 1/
D. O. (ppm): NR ODOR: Strong NR NR
(COBALT 0 - 500) (NTI 10 - 200
Field QC samples collected at this well: Parameters field filtered at this well: Or 0 - 1000) AR Or 0 - 1000)
PURGING EQUIPMENT SAMPLING EQUIPMENT
2" Bladder Pump Bailer (Teflon®) 2" Bladder Pump Bailer (Teflon®)
Centrifugal Pump — Bailer (PVC) — DDL Sampler — Bailer (Stainless Stee
—— Submersible Pump —— Bailer (Stainless Steel) —— Dipper —— Submersible Pump
— Well Wizard™ — Dedicated — Well Wizard™ — Dedicated
Other: Other:
WELL INTEGRITY: LOCK #: none
REMARKS: - CILL Samples take

Meter Calibration: Date: 3/13/96 Time: _____ Meter Serial #: 9204 Temperature °F: _____ (EC 1000 ____/ ___) (DI ____) (pH 7 ____/ ___) (pH 10 ____/ ___) (pH 4 ____/ ___) Location of previous calibration: Reviewed By: -Signature:

Rev.	3	2/04
nev.	J.	2/94

•

WATED CARADIE

WATER SAMPLE FIELD DATA SHEET
EMCON PROJECT NO: 2/775-235,002 SAMPLE ID: A-Z (ZS')
ASSOCIATES PURGED BY: M. Galle Gas / Timilliams CLIENT NAME: ARCOH 2/69
SAMPLED BY: LOCATION: CAKLAMO, CA
TYPE: Ground Water X Surface Water Treatment Effluent Other
CASING DIAMETER (inches): 2 3X
CASING ELEVATION (feet/MSL): A/R VOLUME IN CASING (gal.): $(.05)$ DEPTH TO WATER (feet): 25.3 CALCULATED PURGE (gal.): 18.17 DEPTH OF WELL (feet): 25.3 ACTUAL PURGE VOL. (gal.): 18.5
DATE PURGED: 3-13-96 Start (2400 Hr) 1032 End (2400 Hr) 1000 DATE SAMPLED: V Start (2400 Hr) 1042 End (2400 Hr) End (2400 Hr)
TIME VOLUME PH E.C. TEMPERATURE COLOR TURBIDITY
(2400 Hr) (gal.) (units) (μ mhos/cm@25°C) (°F) (visual) (visual) 10×1 (0×1 (0×1
1035 120 4.74 1007 (1911 (10014 MOD)
1034 18.5 (1-83 1013 693 char Light
D. O. (ppm): NR ODOR: Moill. NR NR
Field QC samples collected at this well: Parameters field filtered at this well: NR (COBALT 0 - 500) (NTU 0 - 200 or 0 - 1000)
PURGING EQUIPMENT SAMPLING EQUIPMENT
2* Bladder Pump Bailer (Teflon®) 2* Bladder Pump Bailer (Teflon®)
Centrifugal Pump — Bailer (PVC) — DDL Sampler — Bailer (Stainless Steel) Submersible Pump — Bailer (Stainless Steel) — Dipper — Submersible Pump
— Well Wizard™ — Dedicated — Well Wizard™ — Dedicated
Other:
WELL INTEGRITY: (100) LOCK #: ARCO-K-V
REMARKS: CII Samples taken
Meter Calibration: Date: 3/13/96 Time: 1933 Meter Serial #: 9204 Temperature °F: 553
Meter Calibration: Date: $3/13/96$ Time: 1030 Meter Serial #: 9204 Temperature °F: 583 (EC 1000 $1036/11000$) (DI) (pH $7689/700$) (pH $10209/11000$) (pH $4402/700$)
Location of previous calibration:
Signature: 71 Oldollen Reviewed By: 77 Page 2 of 10



WATER SAMPLE FIELD DATA SHEET
EMCON PROJECT NO: 2/775-235, 002 SAMPLE ID: A-3 (29')
PURGED BY: M. GATEGOS / TIW HIGHER CLIENT NAME: ARCOH 2/69
SAMPLED BY: LOCATION: CAKLAMS, CA
TYPE: Ground Water Surface Water Treatment Effluent Other
CASING DIAMETER (inches): 2 3 4 4.5 6 Other
CASING ELEVATION (feet/MSL): \sqrt{R} VOLUME IN CASING (gal.): $\sqrt{3.32}$
DEPTH TO WATER (feet): 9,22 CALCULATED PURGE (gal.): 21,97
DEPTH OF WELL (feet): 29.2 ACTUAL PURGE VOL. (gal.): 22.0
DATE PURGED: 3-13-94 Start (2400 Hr) 1049 End (2400 Hr) 1653
DATE SAMPLED: Start (2400 Hr) End (2400 Hr)
TIME VOLUME pH E.C. TEMPERATURE COLOR TURBIDITY
(2400 Hr) (gal.) (units) (μmhos/cm@25°C) (°F) (visual) (visual)
1057 7.5 1.51 91.9 1.65 BRN HMY
1053 22.0 7.57 1002 67.1
D. O. (ppm): NR ODOR: Noise NR NR
(COBALT 0 - 500) (NTU 0 - 200
Field QC samples collected at this well: Parameters field filtered at this well: or 0 - 1000)
PURGING EQUIPMENT SAMPLING EQUIPMENT
2° Bladder Pump — Bailer (Teflon®) — 2° Bladder Pump — Bailer (Teflon®)
Centrifugal Pump — Bailer (PVC) — DDL Sampler — Bailer (Stainless Steel)
—— Submersible Pump —— Bailer (Stainless Steel) —— Dipper —— Submersible Pump
— Well Wizard™ — Dedicated — Well Wizard™ — Dedicated
Other: Other:
WELL INTEGRITY: LOCK #: PRIO- Key.
REMARKS: all Samples faleen
newating.
Meter Calibration: Date: 3/13/9C Time: Meter Serial #: 9204 Temperature °F:
(EC 1000 /) (DI) (pH 7 /) (pH 10 /) (pH 4 /)
Location of previous calibration: 4-2
Signature: 71 / July Reviewed By: 77 Page 5 of 10

WATER SAIVIPLE FIELD DATA SHEET EMCON PROJECT NO: 2/775-235.002 SAMPLEID: A-4 (28')
PURGED BY: M. Galle Gas / T. William CLIENT NAME: ARCOH 2/6
SAMPLED BY: LOCATION: CAKLAM) CA
TYPE: Ground Water X Surface Water Treatment Effluent Other
CASING DIAMETER (inches): 2 3_X 4 4.5 6 Other
CASING ELEVATION (feet/MSL): \sqrt{R} VOLUME IN CASING (gal.): $7.(e/$ DEPTH TO WATER (feet): 7.77 CALCULATED PURGE (gal.): 2.80 DEPTH OF WELL (feet): 2.85 ACTUAL PURGE VOL. (gal.): 2.00
DATE PURGED: 3-/3-96 Start (2400 Hr) 1110 End (2400 Hr) 1//3 DATE SAMPLED: V Start (2400 Hr) 1//7 End (2400 Hr) ————————————————————————————————————
TIME VOLUME PH E.C. TEMPERATURE COLOR TURBIDITY (2400 Hr) (gal.) (units) (µmhos/cm@25°C) (°F) (visual) (visual)
1112 15.0 7.20 878 65.8 (b.d. mon) 1113 720 7.14 884 66.0 11 11
D. O. (ppm): NR ODOR: Noise NR NR
Field QC samples collected at this well: Parameters field filtered at this well: Or 0 - 1000) NR NR (COBALT 0 - 500) (NTU 0 - 200 or 0 - 1000)
PURGING EQUIPMENT SAMPLING EQUIPMENT
2° Bladder Pump — Bailer (Teflon 8) — 2° Bladder Pump — Bailer (Teflon 8) Centrifugal Pump — Bailer (PVC) — DDL Sampler — Bailer (Stainless Steel)
— Submersible Pump — Bailer (Stainless Steel) — Dipper — Submersible Pump — Well Wizard TM — Dedicated — Well Wizard TM — Dedicated Other: Other:
WELL INTEGRITY: COM LOCK #: Afrokay REMARKS. Coll Campbes tokan
HEWANKS.
Meter Calibration: Date: 3/13/CC Time: Meter Serial #: 9204 Temperature °F: (EC 1000/) (DI) (pH 7/) (pH 10/) (pH 4/)
Signature Page 4 of 10

CHOON

WATER SAMPLE FIEL			
EMCON PROJECT NO: 2/775-235, 002			
ASSOCIATES PURGED BY: M. Gallegas / Twilliam	CLIENT NAME: ARCOH 2/49		
SAMPLED BY:	LOCATION: CAKLAMD, CA		
TYPE: Ground Water X Surface Water Treatm	nent Effluent Other		
CASING DIAMETER (inches): 2 3 4	4.5 6 Other		
CASING ELEVATION (feet/MSL):	DLUME IN CASING (gal.): 3,53 ALCULATED PURGE (gal.): 10,61		
DEPTH OF WELL (feet): 29.4 AC	TUAL PURGE VOL. (gal.):/_/. O		
DATE PURGED: 3-/3-94 Start (2400 Hr)			
TIME VOLUME pH E.C. (2400 Hr) (gal.) (units) (μmhos/cm@ 25° C)	TEMPERATURE COLOR TURBIDITY (°F) (visual) (visual) 71.1 BRA1 HAVY		
1310 7.0 7.04 1002	68.1 cloudy mon		
1311 11.0 7.06 10ag	67.9 11 11		
D. O. (ppm): NR ODOR: Strong	<u>NR</u> NR		
Field QC samples collected at this well: Parameters field filt NR NR			
PURGING EQUIPMENT	SAMPLING EQUIPMENT		
2' Bladder Pump Bailer (Teflon®)	— 2° Bladder Pump — X Bailer (Teflon®)		
Centrifugal Pump — Bailer (PVC) —	— DDL Sampler — Bailer (Stainless Steel)		
Submersible Pump —— Bailer (Stainless Steel) —	— Dipper — Submersible Pump		
— Well Wizard™ — Dedicated — Other. — Other	Well Wizard™ Dedicated		
WELL INTEGRITY: Cook LOCK # ALCO-Kox' REMARKS: G// Scriple (fakes			
HEMAHKS:			
Meter Calibration: Date: 3/13/96 Time: Meter Series	al #: <u>9204</u> Temperature °F:		
(EC 1000/) (DI) (pH 7/)	(pH 10) (pH 4/)		
Location of previous calibration: A-2			
Signature: Meviewer	d By Page of		



WATER SAMPLE FIELD DATA SHEET
EMCON PROJECT NO: 2/775-235.002 SAMPLE ID: A - 6 (27)
PURGED BY: WILLIAMS CLIENT NAME: ARCOH 2/69
TYPE: Ground Water X Surface Water Treatment Effluent On
Treathert Endent Other
CASING DIAMETER (inches): 2 X 3 4 4.5 6 Other
CASING ELEVATION (feet/MSL):
DATE PURGED: 3-13-96 Start (2400 Hr) 1151 End (2400 Hr) 1/54 DATE SAMPLED: 1200 Start (2400 Hr) 1200 End (2400 Hr) 1
TIME VOLUME pH E.C. TEMPERATURE COLOR TURBIDITY (2400 Hr) (gal) (units) (umhos/cm@25°C) (°F) (visual) (visual) 115: 3.5 7.01 105G (.9.4 Ben 1400x
115-1 7.0 7.02 1110 696 J J1 100-011 dree at 7.0 gallons 120 Yichary 6.93 -1115 70.6
D. O. (ppm): NR ODOR: The AR OD
PURGING EQUIPMENT SAMPLING EQUIPMENT
— 2° Bladder Pump — Bailer (Teflon 8) — 2° Bladder Pump — Bailer (Teflon №) X Centrifugal Pump — Bailer (PVC) — DDL Sampler — Bailer (Stainless Steel)
Centrifugai Pump — Bailer (PVC) — DDL Sampler — Bailer (Stainless Steel) — Dipper — Submersible Pump
— Well Wizard™ — Dedicated — Well Wizard™ — Dedicated
Other Other
REMARKS All Samply faces
46 21.98
Meter Calibration: Date: 3/13/96 Time: Meter Serial # 9204 Temperature °F
(EC 1000/)(DI)(pH 7/)(pH 10/)(pH 4/)
Location of previous calibration:
Signature Reviewed By Page G of O



WATER SAMPLE FIELD DATA SHEET

EMCON PROJECT NO: 2/775-235, CO2 SAMPLE ID: AR-1(281) PURGED BY: M.Galle Gas / T.W. Iliam) CLIENT NAME: ARCOH 2/49
TYPE: Ground Water X Surface Water Treatment Effluent Other
CASING DIAMETER (inches): 2 3 4 4.5 6 X Other
CASING ELEVATION (feet/MSL): $\frac{\sqrt{R}}{\sqrt{R}}$ VOLUME IN CASING (gal.): $\frac{29.03}{}$
DEPTH TO WATER (feet): 8.25 CALCULATED BURGE (FEL)
DEPTH OF WELL (feet): 28.0 ACTUAL PURGE VOL. (gal.): 87.5
DATE PURGED: 3-/3-94 Start (2400 Hr) 12/9 End (2400 Hr) 1230 DATE SAMPLED: V Start (2400 Hr) 1234 End (2400 Hr)
TIME VOLUME pH E.C. TEMPERATURE COLOR TURBIDITY (2400 Hr) (gal.) (units) (umpos/cm@ 25°C)
1221 29.0 7.4) 942 (G = RD) (visual)
1225 58.0 711 Total Miles
1230 8715 7.74 GOV 704
D.O. (ppm): NR ODOR: Slight. NR NR
(CORNITO CON
Field QC samples collected at this well: Parameters field filtered at this well: Or 0 - 1000) (COBALT 0 - 500) (NTU 0 - 200 or 0 - 1000)
PURGING EQUIPMENT SAMPLING EQUIPMENT
2' Bladder Pump — Bailer (Teflon 8) — 2' Bladder Pump — Bailer (Teflon 8)
Centifugal Pump Bailer (PVC) — DDL Sampler — Bailer (Stainless Steel
Submersible Pump —— Bailer (Stainless Steel) —— Dipper —— Submersible Pump
Other Well Wizard™ — Dedicated — Well Wizard™ — Dedicated
Other.
WELL INTEGRITY: Cook LOCK #: Management
DEMARKS: G! Simulate to keep.
TENANS.
Mater Calibration Date 3/13/61 To
Meter Calibration: Date: 3/13/6/ Time: Meter Serial #: 9204 Temperature °F:
(EC 1000/) (DI) (pH 7) (pH 10/) (pH 4/) Location of previous calibration:
Signature: Page 7 of 10

Rev	3,	2/94
-----	----	------

WATER SAMPLE FIELD DATA PROJECT NO: 2/775-235,002 SAMPLE ID: PURGED BY: M.Galle Gas / Twilliam Client Name: A SAMPLED BY: LOCATION: C TYPE: Ground Water X Surface Water Treatment Effluent CASING DIAMETER (inches): 2 3 4 X 4.5	AR-2 (AR(0H 2/ CAKLAM) Other_	291) 49
CASING ELEVATION (feet/MSL): $\frac{\sqrt{R}}{\sqrt{R}}$ VOLUME IN CASING DEPTH TO WATER (feet): $\frac{9.23}{29.2}$ CALCULATED PURGE VOLUME IN CASING CASING CALCULATED PURGE VOLUME IN CASING C	E (gal.) :	39.14
DATE SAMPLED: VOLUME pH E.C. TEMPERATURE (2400 Hr) (1/42 E) TIME (2400 Hr) (gal.) (units) (μmhos/cm@ 25° C) (°F) 1121 132 262 7.23 1054 65.8 1134 39.5 7.16 1055 66.2	ind (2400 Hr) nd (2400 Hr) COLOR (visual) Ploudy	TURBIDITY (visual)
Field QC samples collected at this well: Parameters field filtered at this well: NR NR NR	MR COBALT 0 - 500	or 0 - 1000)
2° Bladder Pump —— Bailer (Teffon 8) —— 2° Bladder Pump —— Centrifugal Pump —— Bailer (PVC) —— DDL Sampler —— Submersible Pump —— Bailer (Stainless Steel) —— Dipper —— Well Wizard TM —— Dedicated —— Well Wizard TM Other: —— Other:	_X ;	Bailer (Teflon®) Bailer (Stainless Steel) Bubmersible Pump Dedicated
WELL INTEGRITY: Coup REMARKS: GII Schools tecking	LOCK#: 2	ARCO-Kay

Meter Calibration: Date: 3/13/90 Time. _____ Meter Serial #: 9204 ___ Temperature °F: _____ (EC:000 ____/___)(DI ____)(pH7 ____/___)(pH10 ____/___)(pH4 ___/___) Location of previous calibration:

Signature 2

Reviewed By: _



WATER SAMPLE FIELD DATA SHEET
EMCON PROJECT NO: 2/775-235.002 SAMPLEID: ADR-1 (21)
PURGED BY: M.Galle Gas / T.W. Miams, CLIENT NAME: ARCOH 2/49
SAMPLED BY: LOCATION: CAKLAM, CA TYPE: Ground Water X Surface Water Treatment Effluent Others
CASING DIAMETER (inches)
CASING ELEVATION (feet/MSL): X/R VOLUME IN CASING (gal.): 8,54
DEPTH TO WATER (feet): \$.08 CALCULATED PURGE (gal.): 26.89 DEPTH OF WELL (feet): 21.8 ACTUAL PURGE VOL. (gal.): 27.0
DEPTH OF WELL (feet):
DATE PURGED: 3-13-94 Start (2400 Hr) 1335 End (2400 Hr) 1339
DATE SAMPLED: Start (2400 Hr) End (2400 Hr)
TIME VOLUME pH E.C. TEMPERATURE COLOR TURBIDITY (2400 Hr) (gal.) (units) (umbos/cm@ 25°C) (°F) (vietal) (vietal)
(2400 Hr) (gal.) (units) ($\mu m hos/cm \oplus 25^{\circ} C$) (°F) (visual) (visual) $13 = 7$ 9 0 $13 = 7$ $13 = 7$ $13 = 7$ $13 = 7$ $13 = 7$ $13 = 7$
1338 18.0 6.82 1377 72.2 " cher
1339 27.0 (0.82 1371 71.7 11 11
D. O. (ppm): NR ODOR: Strong NR NR
(COBALT 0 - 500) (NTLI 0 - 200
Field QC samples collected at this well: Parameters field filtered at this well: Or 0 - 1000) AR AR
PURGING EQUIPMENT SAMPLING EQUIPMENT
Centrifugal Pump — Bailer (PVC) — DDL Sampler — Bailer (Stainless Steel) — Dipper — Submersible Pump
—— Submersible Pump —— Bailer (Stainless Steel) —— Dipper —— Submersible Pump —— Well Wizard TM —— Dedicated —— Well Wizard TM —— Dedicated
Other: Other:
WELL INTEGRITY: 600 LOCK #: Mone
REMARKS: C.11 Sample: for kin
3/2/01
Meter Calibration: Date: 3/13/96 Time: Meter Serial #: 9204 Temperature °F:
(EC 1000/) (DI) (pH 7/) (pH 10/) (pH 4/) Location of previous calibration:
$a \cap A = A \cap A$
Signature Page of C

Rev.	3.	2/94
110 V	v,	234



WATER SAMPLE SIELD DATA SHEET

WAITH SHIMFLE FIELD DATA SHEET
EMCON PROJECT NO: 2/775-235,002 SAMPLE ID: ADR-2(261)
ASSOCIATES PURGED BY: M. Galle Gas Twilliams CLIENT NAME: ARCOH 2/69
SAMPLED BY: LOCATION: OAKLAND, CA
TYPE: Ground Water X Surface Water Treatment Effluent Other
CASING DIAMETER (inches): 2 3 4
CASING ELEVATION (feet/MSL): \sqrt{R} VOLUME IN CASING (gal.): 9.74
DEPTH TO WATER (feet): 8.78 CALCULATED PURGE (gal.): 29.24
DEPTH OF WELL (feet): 237 ACTUAL PURGE VOL. (gal.): 21-0
DATE PURGED: 3-/3-94 Start (2400 Hr) 14/10 End (2400 Hr) 14/15
DATE SAMPLED: Start (2400 Hr) End (2400 Hr)
TIME VOLUME pH E.C. TEMPERATURE COLOR TURBIDITY
(2400 Hr) (gal.) (units) (μmhos/cm@25°C) (°F) (visual) (visual)
1/15
1424 richarge 7.00 1466 68.8 4
D. O. (ppm): NR ODOB: Strong NR NR
D. O. (ppm): NK ODOR: Strong NR NR (COBALT 0 - 500) (NTU 0 - 200
Field QC samples collected at this well: Parameters field filtered at this well: or 0 - 1000)
PURGING EQUIPMENT SAMPLING EQUIPMENT
——————————————————————————————————————
— Well Wizard™ — Dedicated — Well Wizard™ — Dedicated
Other:Other:
WELL INTEGRITY: COOK #: More.
REMARKS: CII Samples take
Meter Calibration: Date: 3/13/96 Time: Meter Serial #: 9204 Temperature °F:
(EC 1000 /) (DI) (pH 7 /) (pH 10 /) (pH 4 /)
Location of previous calibration: #2
Signature: 200 of 10 Reviewed By: St. Page 10 of 10

APPENDIX B

ANALYTICAL RESULTS AND CHAIN OF CUSTODY DOCUMENTATION, FIRST QUARTER 1996 GROUNDWATER MONITORING EVENT



March 28, 1996

Mr. John Young EMCON 1921 Ringwood Avenue

San Jose, CA 95131

Re: 2169 Oakland/Project No. 20805-129.003/TO#19350.00

Dear Mr. Young:

The following pages contain analytical results for sample(s) received by the laboratory on March 14, 1996. Results of sample analyses are followed by Appendix A which contains sample custody documentation and quality assurance deliverables requested for this project. The work requested has been assigned the Service Request No. Listed above -- to help expedite our service please refer to this number when contacting the laboratory.

Analytical results were produced by procedures consistent with Columbia Analytical Services' (CAS) Quality Assurance Manual (with any deviations noted). Signature of this CAS Analytical Report below confirms that pages 2 through 11, following, have been thoroughly reviewed and approved for release in accord with CAS Standard Operating Procedure ADM-DatRev3.

Please feel welcome to contact me should you have questions or further needs.

Sincerely,

Oustine V. Recepture for Steve Green

Project Chemist

Greg Anderson

Regional QA Coordinator

Service Request No: S9600418

CVR/smh

Acronyms

A2LA American Association for Laboratory Accreditation

ASTM American Society for Testing and Materials

BOD Biochemical Oxygen Demand

BTEX Benzene, Toluene, Ethylbenzene, Xylenes

CAM California Assessment Metals
CARB California Air Resources Board

CAS Number Chemical Abstract Service registry Number

CFC Chlorofluorocarbon
CFU Colony-Forming Unit
COD Chemical Oxygen Demand

DEC Department of Environmental Conservation
DEQ Department of Environmental Quality
DHS Department of Health Services
DLCS Duplicate Laboratory Control Sample

DMS Duplicate Matrix Spike
DOE Department of Ecology
DOH Department of Health

EPA U. S. Environmental Protection Agency

ELAP Environmental Laboratory Accreditation Program

GC Gas Chromatography

GC/MS Gas Chromatography/Mass Spectrometry

IC Ion Chromatography.

ICB Initial Calibration Blank sample

ICP Inductively Coupled Plasma atomic emission spectrometry

ICV Initial Calibration Verification sample

J Estimated concentration. The value is less than the MRL, but greater than or equal to

the MDL. If the value is equal to the MRL, the result is actually <MRL before rounding.

LCS Laboratory Control Sample
LUFT Leaking Underground Fuel Tank

M Modified

MBAS Methylene Blue Active Substances

MCL Maximum Contaminant Level. The highest permissible concentration of a

substance allowed in drinking water as established by the U.S. EPA

MDL Method Detection Limit
MPN Most Probable Number
MRL Method Reporting Limit

MS Matrix Spike

MTBE Methyl tert-Butyl Ether
NA Not Applicable

NA Not Applicable
NAN Not Analyzed
NC Not Calculated

NCASI
National Council of the paper industry for Air and Stream Improvement
ND
Not Detected at or above the method reporting/detection limit (MRL/MDL)

NIOSH National Institute for Occupational Safety and Health

NTU Nephelometric Turbidity Units

ppb Parts Per Billion ppm Parts Per Million

PQL Practical Quantitation Limit
QA/QC Quality Assurance/Quality Control

RCRA Resource Conservation and Recovery Act

RPD Relative Percent Difference SIM Selected Ion Monitoring

SM Standard Methods for the Examination of Water and Wastewater, 18th Ed., 1992

STLC Solubility Threshold Limit Concentration

SW Test Methods for Evaluating Solid Waste, Physical/Chemical Methods, SW-846,

3rd Ed., 1986 and as amended by Updates I, II, IIA, and IIB

TCLP Toxicity Characteristic Leaching Procedure

TDS Total Dissolved Solids
TPH Total Petroleum Hydrocarbons

tr Trace level. The concentration of an analyte that is less than the PQL but greater than or equal

to the MDL. If the value is equal to the PQL, the result is actually <PQL before rounding.

TRPH Total Recoverable Petroleum Hydrocarbons

TSS Total Suspended Solids

TTLC Total Threshold Limit Concentration

VOA Volatile Organic Analyte(s) ACRONLST.DOC 7/14/95

Analytical Report

Client: E

EMCON

Service Request: S9600418

Project:

2169 Oakland/#20805-129.003/TO#19350.00

Date Collected: 3/13/96

Sample Matrix: Water

Date Received: 3/14/96

Date Extracted: 3/21-22/96

	Sample Name: Lab Code: Date Analyzed:	A-2(25) \$9600418-001 3/21/96	A-3(29) S9600418-002 3/21/96	A-4(28) \$96004[8-003 3/21/96
Analyte	MRL			
TPH as Gasoline	50	ND	ND	ND
Benzene	0.5	ND	ND	ND
Toluene	0.5	0.6	ND	ND
Ethylbenzene	0.5	ND	ND	ND
Total Xylenes	0.5	1.3	ND	ND
Methyl-tert-butyl ether	3	<9*	ND	ND

The MRL is elevated because of matrix interferences and because the sample required diluting.

Analytical Report

Client: EMCON

2169 Oakland/#20805-129.003/TO#19350.00

Sample Matrix: Water

Project:

Service Request: \$9600418 Date Collected: 3/13/96 Date Received: 3/14/96 Date Extracted: 3/21-22/96

	Sample Name: Lab Code: Date Analyzed:	AR-2(29) S9600418-004 3/21/96	A-6(27) S9600418-005 3/21/96	AR-1(28) \$9600418-006 3/25/96
Analyte	MRL			
TPH as Gasoline	50	190	1400	150
Benzene	0.5	26	<3*	3 8
Toluene	0.5	2,6	<15**	0.5
Ethylbenzene	0.5	3.3	<7**	1 4
Total Xylenes	0.5	13	<10**	1.3
Methyl-tert-butyl ether	3	200	<20*	ND

^{*} The MRL is elevated due to high analyte concentration requiring sample dilution

^{**} The MRL is elevated because of matrix interferences and because the sample required diluting.

Analytical Report

Client: EMCON

2169 Oakland/#20805-129.003/TO#19350.00

Sample Matrix: Water

Project:

Service Request: S9600418

Date Collected: 3/13/96

Date Received: 3/14/96

Date Extracted: 3/21-22/96

	Sample Name: Lab Code: Date Analyzed:	A1(24) S9600418-007 3/25/96	A-5(29) S9600418-008 3/25/96	ADR-1(21) S9600418-009 3/25/96
Analyte	MRL			
TPH as Gasoline	50	1300	11000	89000
Benzene	0.5	300	860	370
Toluene	0.5	74	960	1000
Ethylbenzene	0,5	29	380	840
Total Xylenes	0.5	73	1600	8100
Methyl-tert-butyl ether	3	100	<100*	<500*

^{*} The MRL is elevated due to high analyte concentration requiring sample dilution.

Analytical Report

 Client:
 EMCON
 Service Request:
 \$9600418

 Project:
 2169 Oakland/#20805-129.003/TO#19350.00
 Date Collected:
 3/13/96

 Sample Matrix:
 Water
 Date Received:
 3/14/96

Date Extracted: 3/21-22/96

	Sample Name: Lab Code: Date Analyzed:	ADR-2(26) S9600418-010 3/25/96	Method Blank S960321-WB 3/21/96	Method Blank S960325-WB 3/25/96
Analyte	MRL			
TPH as Gasoline	50	29000	ND	ND
Benzene	0.5	1100	ND	ND
Toluene	0.5	1200	ND	ND
Ethylbenzene	0.5	710	ND	ND
Total Xylenes	0.5	3800	ND	ND.
Methyl-tert-butyl ether	3	<5()()*	ND	ND

^{*} The MRL is elevated due to high analyte concentration requiring sample dilution.

Analytical Report

Client:EMCONService Request:\$9600418Project:2169 Oakland/#20805-129.003/TO#19350.00Date Collected:3/13/96Sample Matrix:WaterDate Received:3/14/96

Date Received: 3/14/96

Date Extracted: 3/21-22/96

BTEX, MTBE and TPH as Gasoline EPA Methods 5030/8020/California DHS LUFT Method Units: ug/L (ppb)

Sample Name: Method Blank
Lab Code: S960326-WB
Date Analyzed: 3/26/96

Analyte	MRL	
TPH as Gasoline	50	ND
Benzene	0.5	ND
Toluene	0.5	ND
Ethylbenzene	0.5	ND
Total Xylenes	0.5	ND
Methyl-tert-butyl ether	3	ND

The MRL is elevated due to high analyte concentration requiring sample dilution.

APPENDIX A

QA/QC Report

 Client:
 EMCON
 Service Request:
 \$9600418

 Project:
 2169 Oakland/#20805-129.003/TO#19350.00
 Date Collected:
 3/13/96

Sample Matrix: Water

Date Received: 3/14/96
Date Extracted: NA

Date Analyzed: 3/21-26/96

Surrogate Recovery Summary
BTEX, MTBE and TPH as Gasoline
EPA Methods 5030/8020/California DHS LUFT Method

Sample Name	Lab Code	PID Detector Percent Recovery 4-Bromofluorobenzene	FID Detector Percent Recovery α, α, α -Trifluorotoluene
A-2(25)	S9600418-001	91	101
A-3(29)	S9600418-002	94	93
A-4(28)	S9600418-003	92	102
AR-2(29)	S9600418-004	93	107
A-6(27)	S9600418-005	86	105
AR-1(28)	S9600418-006	77	87
A1(24)	S9600418-007	88	110
A-5(29)	S9600418-008	90	109
ADR-1(21)	S9600418-009	93	108
ADR-2(26)	\$9600418-010	89	101
Method Blank	S960321-WB	92	97
Method Blank	S960325-WB	89	104
Method Blank	S960326-WB	89	109

CAS Acceptance Limits: 69-116 69-116

QA/QC Report

Client: EMCON
Project: 2169 Oakland/#208

2169 Oakland/#20805-129.003/TO#19350 00

Sample Matrix: Water

Service Request: S9600418

Date Collected: 3/13/96

Date Received: 3/14/96 **Date Extracted:** NA

Date Analyzed: 3/21/96

Matrix Spike/Duplicate Matrix Spike Summary

TPH as Gasoline

EPA Methods 5030/California DHS LUFT Method

Units: ug/L (ppb)

Sample Name:

A-2(25)

Lab Code:

\$9600418-001

	,						Perc	ent R	ecovery	
		Snike	: Level	Sample	Snike	Result			CAS Acceptance	Relative Percent
Analyte		MS	DMS	Result	MS	DMS	MS	DMS	Limits	Difference
Gasoline		250	250	ND	267	263	107	105	67-121	1

QA/QC Report

 Client:
 EMCON

 Project:
 2169 Oakland/#20805-129.003/TO#19350.00

Service Request: \$9600418

Date Analyzed: 3/21/96

Initial Calibration Verification (ICV) Summary BTEX, MTBE and TPH as Gasoline EPA Methods 5030/8020/California DHS LUFT Method Units: ppb

				CAS	
				Percent	
				Recovery	
	True		Percent	Acceptance	
Analyte	Value	Result	Recovery	Limits	
Benzene	25	24,3	97	85-115	
Toluene	25	24,2	97	85-115	
Ethylbenzene	25	23.8	95	85-115	
Xylenes, Total	75	72.7	97	85-115	
Gasoline	250	255	102	90-110	
Methyl-tert-butyl Ether	50	43	86	85-115	

Division of AtlanticRichfieldCompany Task Order No. 9350,00 ARCO Facility no. 2169 City (Facility) Onloan (Consultant) ARCO engineer Mile Whelan Telephone no. (Consultant) ARCO engineer Mile Whelan Telephone no. (Consultant) Address (nent 27 27
ARCO engineer Mile Whelen Telephone no. (ARCO) Consultant name EMCON Matrix Preservation Out and an an an an an an an an an an an an an	nent 27 27
Consultant name EMCON Consultant 97 R NOV Samble 10 Consultant name EMCON Consultant 97 R Reservation Countral 10 R Reservation Countral 10 R R R R R R R R R	nent 27 27
Matrix Preservation Somple 1.D. Somple 1.D	2r
A-2(25) 1 2 × × HQ 3/13/94 104/2 × Special detection of the supering special detection of the supering special detection of the supering special detection of the supering special detection of the supering super	2r
$A-2(25)$ 1 2 \times \times $+0$ $3/1394$ 1042 \times \times \times \times \times \times \times \times \times \times	
4-3(21) 2 2 × HCL 1100 × Lowes	7
A-46.81) = 2 x x HCL 1117 x Possis	ole
AR-2Gq,) 4 4 × × I+CL 1142 × ×	
A-6(27) = Z × HCL 1200 × AS NOI	mal
AR-1(28)6 4 × HCL 1234 × ×	11011
A-1(24) 7 4 × × HCL /360 × ×	
A C (dc) - 3	11/21
ADR-16119 4 X X HCL 1337 X X VOA ADR-26119 4 X X HCL 1344 X X (AII) W	IICL
ADR-26(1)04 X X HCI V 1422 X X	ells)
7-111-6 Glas	STNP S
A-1, AR-1,	AR-Z, ADR-1.
#2090	-179,003
Lab number	
S9600 Turnaround tim	
Priority Rush	
Condition of sample: Temperature received:	, –
Relinquished by sampler Date Time Received by Rush 2 Business Date Rush 2 Business Date	rs 🗆
Relinquished by Date Time Received by Expedited 5 Business Date	rs 🗆
Relinquished by Date Time Received by laboratory Date Time Standard 10 Business Date Standard 10 Business Date Distribution: White copy — Laboratory; Canary copy — ARCO Environmental Engineering; Pink copy — Consumant	3/01

28/32

APPENDIX C SVE SYSTEM MONITORING DATA LOG SHEETS

APPENDIX D

FIELD DATA SHEETS, OPERATION AND MAINTENANCE VISITS, FIRST QUARTER 1996