



Date June 27, 1997
Project 20805-129,004

To:

Ms. Susan Hugo Alameda County Health Care Services Agency Department of Environmental Health 1131 Harborbay Parkway, Suite 250 Alameda, California 94502-6577

We are enclosing:

Copies		Description			
1		First quarter 1	997 groundwat	er monitori	ng results and
		remediation sy	stem performa	nce evaluat	ion report,
		ARCO Service	Station 2169,	Oakland, C	alifornia
For your:	x	Use	Sent by:	x	Regular Mail
		Approval Review			Standard Air Courier
		Information			Other:

#### Comments:

The enclosed groundwater monitoring and performance evaluation report is being sent to you per the request of ARCO Products Company. Please call if you have questions or comments.

Valli Voruganti Project Manager

cc: Kevin Graves, RWQCB - SFBR
Paul Supple - ARCO Products Company
File



Date:

June 25, 1997

Re: ARCO Station #

2169 • 889 West Grand Avenue • Oakland, CA First Quarter 1997 Groundwater Monitoring Results and Remediation System Performance Evaluation Report

"I declare, that to the best of my knowledge at the present time, that the information and/or recommendations contained in the attached proposal or report are true and correct."

Submitted by:

Paul Supple

**Environmental Engineer** 



June 27, 1997 Project 20805-129.004

Mr. Paul Supple ARCO Products Company P.O. Box 6549 Moraga, California 94570

Re: First quarter 1997 groundwater monitoring program results and remediation system performance evaluation report, ARCO service station 2169, Oakland, California

Dear Mr. Supple:

This letter presents the results of the first quarter 1997 groundwater monitoring program at ARCO Products Company (ARCO) service station 2169, 889 West Grand Avenue, Oakland, California (Figure 1). Operation and performance data for the interim soil-vapor extraction (SVE) and air-sparge (AS) remediation systems at the site are also presented. The quarterly monitoring program complies with Alameda County Health Care Services Agency (ACHCSA) requirements regarding underground tank investigations. Pertinent site features, including the locations of existing on-site monitoring and vapor extraction wells are shown in Figure 2.

#### **LIMITATIONS**

No monitoring event is thorough enough to describe all geologic and hydrogeologic conditions of interest at a given site. If conditions have not been identified during the monitoring event, such a finding should not therefore be construed as a guarantee of the absence of such conditions at the site, but rather as the result of the scope, limitations, and cost of work performed during the monitoring event.

Please call if you have questions.

Sincerely,

**EMCON** 

Gowri Kowtha Staff Engineer Ann Gallagher, R.G. 6090

**Project Geologist** 

RG6090



## ARCO QUARTERLY REPORT

Station No.:	2169	Address:	889 West Grand Avenue, Oakland, California
EMCON Project	et No.		20805-129.004
ARCO Environ	mental Engine	er/Phone No.:	Paul Supple /(510) 299-8891
<b>EMCON</b> Project	t Manager/Pho	one No.:	Valli Voruganti /(408) 453-7300
Primary Agency	//Regulatory II	D No.:	ACHCSA /Susan Hugo
Reporting Perio	od:		January 1, 1997 to April 1, 1997

# **WORK PERFORMED THIS QUARTER (First-1997):**

- 1. Conducted quarterly groundwater monitoring and sampling for first quarter 1997.
- 2. Prepared and submitted quarterly report for fourth quarter 1996.
- 3. Stimulated natural biodegradation in groundwater monitoring well A-5 with oxygen releasing compounds (ORCs).
- 4. Operated air-sparge system.

### **WORK PROPOSED FOR NEXT QUARTER (Second- 1997):**

- 1. Perform quarterly groundwater monitoring and sampling for second quarter 1997.
- 2. Continue operating air-sparge system and restart soil-vapor extraction (SVE) system if influent hydrocarbon concentrations and groundwater levels warrant.
- 3. Continue to monitor dissolved oxygen in groundwater monitoring well A-5.
- 4. Prepare and submit quarterly report for first quarter 1997.

### **QUARTERLY MONITORING:**

Current Phase of Project:	Quarterly Groundwater Monitoring and Operation and Maintenance of Remediation Systems
	The SVE system was shut down on January 15, 1997, because of blower failure.
Frequency of Sampling:	Quarterly (groundwater), Monthly (SVE)
Frequency of Monitoring:	Quarterly (groundwater), Monthly (SVE and Air-Sparge)
Is Floating Product (FP) Present On-site	Yes No
Cumulative FP Recovered to Date:	4.8 gallons, Wells ADR-1 and ADR-2
FP Recovered This Quarter:	None
Bulk Soil Removed to Date:	2,196 cubic yards of TPH-impacted soil
Bulk Soil Removed This Quarter:	None
Water Wells or Surface Waters	
within 2000 ft., impacted by site:	None
Current Remediation Techniques:	SVE and Air-Sparge Systems
Average Depth to Groundwater:	10.55 feet
Groundwater Gradient (Average):	0.002 ft/ft towardnorthwest (consistent with past events)
SVE QUARTERLY OPERATION	ON AND PERFORMANCE:
Equipment Inventory:	Therm Tech Model VAC-25, 250 cfm, Thermal/Catalytic Oxidizer
Operating Mode:	Catalytic Oxidation
BAAQMD Permit #:	12119

**EMCON** 

TPH Conc. End of Period (lab):	NA (Not Available)
Benzene Conc. End of Period (lab):	NA
Flowrate End of Period:	NA
HC Destroyed This Period:	0.0 pounds
HC Destroyed to Date:	7830.3 pounds
Utility Usage	
Electric (KWH):	2669 KWH
Gas (Therms):	206 Thems
Operating Hours This Period:	215.7 hours
Percent Operational:	10.0% System was down for quarterly monitoring and other maintenance
	issues. See discussion.
Operating Hours to Date:	5850.6 hours
Unit Maintenance:	Routine monthly maintenance and replaced broken blower belt.
Number of Auto Shut Downs:	_1
Destruction Efficiency Permit	
Requirement:	90%
Percent TPH Conversion:	NA
Stack Temperature:	590°F (1-6-97)
Source Flow:	148.8 scfm (1-6-97)
Process Flow:	148.8 scfm (1-6-97)
Source Vacuum:	61.4 inches of water (1-6-97)

#### DISCUSSION:

The soil-vapor extraction (SVE) system was not operational during most of first quarter 1997, because of storm-related power interruptions and maintenance issues. During January 1997, power interruptions caused the system to automatically shut down and the blower belt was damaged. In February a new blower belt was installed, however the SVE and air-sparge systems remained shut down because of low influent concentrations and rising water levels which resulted in the submergence of the hydrocarbon-impacted zone of soil and screen in the SVE wells. The SVE and air-sparge systems may be restarted during the second or third quarter, if hydrocarbon concentrations and groundwater levels warrant.

#### ATTACHED:

- Table 1 Groundwater Monitoring Data, First Quarter 1997
- Table 2 Historical Groundwater Elevation and Analytical Data, Petroleum Hydrocarbons and Their Constituents
- Table 3 Approximate Cumulative Floating Product Recovery Data
- Table 4 Soil Vapor Extraction System Operation and Performance Data
- Table 5 Soil-Vapor Extraction Well Data
- Table 6 Air-Sparge System Operation and Performance Data
- Figure 1 Site Location
- Figure 2 Site Plan
- Figure 3 Groundwater Data, First Quarter 1997
- Figure 4 Historical SVE System Influent TVHG and Benzene Concentrations
- Figure 5 Historical SVE System Hydrocarbon Removal Rates
- Appendix A Analytical Results and Chain of Custody Documentation, First Quarter 1997
   Groundwater Monitoring Event
- Appendix B SVE System Monitoring Data Log Sheets

**EMCON** 

cc: Susan Hugo, ACHCSA Kevin Graves, RWQCB-SFBR

Table 1 Groundwater Monitoring Data First Quarter 1997

Date: 06-06-97

Well Designation	Water Level Field Date	Top of Casing Elevation	Depth to Water	Groundwater Elevation	Floating Product Thickness	Groundwater Flow Direction	Hydraultc Gradient	Water Sample Field Date	<b>TPHG</b> LUFT Method	Benzene EPA 8020	<b>Toluene</b> EPA 8020	Ethylbenzene EPA 8020	Total Xylenes EPA 8020	<b>MTBE</b> EPA 8020	MTBE EPA 8240	TPHD LUFT Method
		ft-MSL	feet	ft-MSL	feet	MWN	ft/ft		μg/L	μg/L	μg/L	μg/L	μg/L	μg/L	μg/L	μg/L
A-1	03-26-97	14 16	10 55	3 61	ND	NW	0.002	03-26-97	<50	0.8	<0.5	<0.5	<0.5	64		
A-2	03-26-97	14 55	11 12	3 43	ND	NW	0.002	03-26-97	<50	< 0.5	< 0.5	< 0.5	< 0.5	<20^	· -	
A-3	03-26-97	15 75	1181	3.94	ND	NW	0 002	03-26-97	<50	< 0.5	< 0.5	<0.5	< 0.5	<3		
A-4	03-26-97	15 25	10 97	4.28	ND	NW	0 002	03-26-97	<50	<0.5	<0.5	<0.5	< 0.5	<3		
A-5	03-26-97	13.51	9 87	3.64	ND	NW	0 002	03-26-97	3100	190	140	130	340	<30^		
A-6	03-26-97	13 51	9 93	3 58	ND	NW	0.002	03-26-97	110	< 0.5	8.0	1.0	14	15		
AR-1	03-26-97	1561	11 33	4 28	ND	NW	0.002	03-26-97	<50	< 0.5	< 0.5	< 0.5	<0.5	<3		
AR-2	03-26-97	15 28	1160	3.68	ND	NW	0 002	03-26-97	<50	<0.5	< 0.5	<0.5	< 0.5	9		
ADR-1	03-26-97	13 95	10 37	3.58	ND	NW	0 002	03-26-97	1300	260	6	39	27	95		
ADR-2	03-26-97	14.64	11 13	3 51	ND	NW	0 002	03-26-97	6100	320	23	180	400	32		

MWN: ground-water flow direction and gradient apply to the entire monitoring well network

TPHG- total petroleum hydrocarbons as gasoline, California DHS LUFT Method

EPA United Statest Environmental Protection Agency

MTBE: Methyl test-butyl ether

TPHD total petroleum hydrocarbons as diesel. California DHS LUFT Method

ND: none detected

NW northwest

ft-MSL elevation in feet, relative to mean sea level

ft/ft foot per foot

µg/L mucrograms per liter

<sup>^</sup> method reporting limit was taised due to (1) high analyte concentration requiring sample dilution, or (2) matrix interference

<sup>- - &#</sup>x27; not analyzed

Table 2
Historical Groundwater Elevation and Analytical Data
Petroleum Hydrocarbons and Their Constituents
1994 - Present\*\*\*

Date 06-06-97

Well Designation	Water Level Field Date	Top of Canng TS Elevation	Gepub to Water	Groundwater SE Elevation	Floating Product	Groundwater Flow Direction	Hydraulic	Water Sample Field Date	TPHG PLUFT Method	Benzene	Toluene	म् Ethylbenzene लु EPA 8020	Fotal Xylenes EPA 8020	т МТВЕ Т ЕРА 8020	MTBE	五 TPHD 上UFT Method
		IIIISE	1001	TI-MOL	1001				μ5/12	ны с	μg/E	P5/C	µ8/L	µg/L	μg/L	μg/ C
A-1	03-24-95	[416	8 10	6 06	ND	NW	0.009	03-24-95	1200	230	39	34	66			160^^^
A-1	06-05-95	14 16	11 13	3 03	ND	NW	0,002	06-05-95	1500	310	27	36	76			710^
A-I	08-17-95	14 16	1171	2 45	ND	w	0.001	08-18-95	1600	470	35	48	110	120		240^
A-l	12-04-95	14.16	12 28	1.88	ND	NNW	0 002	12-04-95	1200	240	17	25	56		120	
A-l	03-01-96	14.16	8.78	5 38	ND	NW	0 003	03-13-96	1300	300	74	29	73	100		
A-1	05-29-96	14 16	9 85	4 31	ND	NW	0.002	05-29-96	Not sampled	i: well samp	oled semi-a	nnually, du	ring the firs	st and third	quarters	
A-1	08-29-96	14 16	11 08	3 08	ND	w	0 002	08-29-96	1200	320	5 9	25	27	110		
A-1	11-21-96	14 16	10 54	3 62	NĎ	WNW	0.002	11-21-96	Not sampled	l well samp	oled semi-a	annally, du	ring the firs	st and third	quarters	
A-1	03-26-97	14 16	10 55	3 61	ND	NW	0 002	03-26-97	<50	0.8	<0.5	<0.5	<0.5	64		
A-2	03-24-95	14 55	8 64	5 91	ND	NW	0 009	03-24-95	<50	<0.5	<0.5	<0.5	<05			
A-2	06-05-95	14 55	11 72	2 83	ND	NW	0 002	06-05-95	<50	<0.5	<0.5	<0.5	< 0.5			
A-2	08-17-95	14 55	12 35	2 20	ND	W	0.001	08-17-95	<50	<0.5	< 0.5	<0.5	<0.5	12		
A-2	12-04-95	14 55	12.74	181	ND	NNW	0 002	12-04-95	<50	< 0.5	< 0.5	<0.5	< 0.5			
A-2	03-01-96	14 55	9.34	5 21	ND	NW	0 003	03-13-96	<50	< 0.5	0.6	<0.5	13	<9		
A-2	05-29-96	14 55	10 40	4 15	ND	NW	0 002	05-29-96	<50	< 0.5	<0.5	<0.5	< 0.5	<20		
A-2	08-29-96	14 55	11 50	3 05	ND	W	0.002	08-29-96	<50	<0.5	< 0.5	<0.5	< 0.5	<39^		
A-2	11-21-96	14.55	11 06	3.49	ND	WNW	0.002	11-21-96	<50	<0.5	<0.5	<0.5	< 0.5	<30^		
A-2	03-26-97	14 55	11 12	3 43	ND	NW	0 002	03-26-97	<50	< 0.5	<0.5	<0.5	<0.5	<20^		

Table 2
Historical Groundwater Elevation and Analytical Data
Petroleum Hydrocarbons and Their Constituents
1994 - Present\*\*\*

Date 06-06-97

Well Designation	evel	วีลงกดู	. Water	water	Floating Product Thickness	water rection	3 <sub>1</sub>	ample ate	Aethod	20	50	nzene 20	ytenes 20	20	40	Jethod
Well De	Water Level Field Date	Top of Casing Elevation	Depth to Water	Groundwater Elevation	Floating P Thickness	Groundwater Flow Direction	Hydraulie Gradieni	Water Sample Field Date	<b>TPHG</b> LUFT Method	Benzene EPA 8020	Toluene EPA 8020	Ethylbenzene EPA 8020	Total Xylenes EPA 8020	MTBE EPA 8020	<b>MTBE</b> EPA 8240	TPHD LUFT Method
		ft-MSL	feet	ft-MSL	feet	MWN	ft/ft		μg/L	μg/L	μg/L	μg/L	μg/L	μg/L	μg/L	μg/L
A-3	03-24-95	15 75	8 83	6 92	ND	NW	0.009	03-24-95	<50	<0.5	<0.5	<0.5	<0.5			
A-3	06-05-95	15 75	12 44	3 31	ND	NW	0.002	06-05-95	Not sampled	· well samp	led annuall	ly, during t	he first qua	rter		
A-3	08-17-95	15 75	13 04	271	ND	W	0 001	08-17-95	Not sampled	: well samp	oled annual	ly, during (	he first qua	rter		
A-3	12-04-95	15 75	13 57	2 18	ND	NNW	0 002	12-04-95	Not sampled	: well samp	led annual	ly, during t	he first qua	rter		
A-3	03-01-96	15.75	9 90	5 85	ND	NW	0 003	03-13-96	< 50	<0.5	< 0.5	<0.5	<0.5	<3		
A-3	05-29-96	15.75	11 08	4 67	ND	NW	0 002	05-29-96	Not sampled	well samp	led annual	ly, during 1	he first qua	rter		
A-3	08-29-96	15.75	12.38	3 37	ND	W	0 002	08-29-96	Not sampled	well samp	led annual	ly, during t	he first qua	rter		
A-3	11-21-96	15 75	11.86	3 89	ND	WNW	0 002	11-21-96	Not sampled	well samp	led annual	ly, during t	he first qua	rter		
A-3	03-26-97	15 75	11.81	3 94	ND	NW	0 002	03-26-97	<50	<0.5	<0.5	<0.5	<0.5	<3		
A-4	03-24-95	15.25	7 20	8.05	ND	NW	0.009	03-24-95	<50	<0.5	<0.5	<0.5	<0.5			
A-4	06-05-95	15 25	11.70	3 55	ND	NW	0 002	06-05-95	Not sampled	well samp	led annual	ly, during 1	he first qua	rter		
A-4	08-17-95	15 25	12.28	2 97	ND	W	100 0	08-17-95	Not sampled	well samp	oled annual	ly, during t	he first qua	rter		
A-4	12-04-95	15 25	12 63	2 62	ND	NNW	0 002	12-04-95	Not sampled	well samp	oled annual	ly, during t	he first qua	rter		
A-4	03-01-96	15 25	8 55	6.70	ND	NW	0 003	03-13-96	<50	< 0.5	< 0.5	<0.5	<0.5	<3		
A-4	05-29-96	15 25	10 32	4 93	ND	NW	0 002	05-29-96	Not sampled	l. well samp	ied annuai	ly, during	he first qua	rter		
A-4	08-29-96	15 25	11 55	3 70	NĐ	w	0.002	08-29-96	Not sampled	i: well samp	oled annual	ly, during	he first qua	rter		
A-4	11-21-96	15 25	10 83	4 42	ND	WNW	0 002	11-21-96	Not sampled	well samp	oled annual	ly, during	he first qua	rter		
A-4	03-26-97	15.25	10.97	4 28	ND	NW	0 002	03-26-97	<50	<0.5	<0.5	<0.5	<0.5	<3		

Table 2
Historical Groundwater Elevation and Analytical Data
Petroleum Hydrocarbons and Their Constituents
1994 - Present\*\*\*

Date: 06-06-97

Well Designation	Water Level Field Date	Top of Casing Elevation	Depth to Water	Groundwater Elevation	Floating Product Thickness	Groundwater Flow Direction	Hydraulic Gradient	Water Sample Field Date	TPHG LUFT Method	Benzene EPA 8020	Toluene EPA 8020	Ethylbenzene EPA 8020	Total Xylenes EPA 8020	MTBE GPA 8020	MTBE EPA 8240	TPHD LUFT Method
		ft-MSL	feet	ft-MSL	feet	MWN	ft/ft		μg/L	μg/L	μg/L	µg/L	μg/L	µg/L	μg/L	μg/L
A-5 A-5 A-3 A-5 A-5 A-5 A-5 A-5	03-24-95 06-05-95 08-17-95 12-04-95 03-01-96 05-29-96 08-29-96 11-21-96 03-26-97	13 51 13 51 13 51 13 51 13 51 13 51 13 51 13 51 13 51	7.40 10 43 11.15 11.42 8.11 9.30 10.60 10 05 9 87	6.11 3.08 2.36 2.09 5.40 4.21 2.91 3.46 3.64	ND ND ND ND ND ND ND ND	NW NW W NNW NW NW W NW	0 009 0 002 0 001 0 002 0 003 0 002 0 002 0 002 0 002	03-24-95 06-05-95 08-18-95 12-04-95 03-13-96 05-29-96 08-29-96 11-21-96 03-26-97	3300 57000 34000 61 11000 19000 7700 8000 3100	200 2700 1600 <0.5 860 1600 490 450 190	310 4600 2700 <0.5 960 1900 450 550 140	130 1500 1100 <0.5 380 880 260 340 130	460 6800 5100 <0.5 1600 3300 990 1100 340	<28  <100 <100 <30^ <30^ <30^		
A-6 A-6 A-6 A-6 A-6 A-6 A-6 A-6	03-24-95 06-05-95 08-17-95 12-04-95 03-01-96 05-29-96 08-29-96 11-21-96 03-26-97	13.51 13.51 13.51 13.51 13.51 13.51 13.51 13.51	7 89 10 06 11 10 11 52 8 21 9 25 10.52 10 54 9 93	5 62 3 45 2 41 1 99 5.30 4.26 2.99 2 97 3 58	ND ND ND ND ND ND ND ND	NW NW W NNW NW W W W W NW	0 009 0 002 0.001 0.002 0.003 0 002 0 002 0 002	03-24-95 06-05-95 08-18-95 12-04-95 03-13-96 05-29-96 08-29-96 11-21-96 03-26-97	120 160 530 28000 1400 410 80 62	<0.5 <0.5 <0.5 1600 <3 <2 <0.5 <0.5	<1 <06 <05 1800 <15 <2 <05 <05	<0.5 <0.5 <2.4 880 <7 <2 <0.5 <0.5	<1.5 <0.5 <4.2 3600 <10 <2 <0.5 <0.5	<20 3 6 12	     	   

Table 2
Historical Groundwater Elevation and Analytical Data
Petroleum Hydrocarbons and Their Constituents
1994 - Present\*\*\*

Date: 06-06-97

Wall De ignorion	Water Level Field Date	Top of Caving Sevation	pa Depth to Water	Groundwater S Elevation	Floating Product Thickness	Groundwater Flow Direction	Hydraulic	Water Sample Field Date	TPHG LUFT Method	Benzene 가 EPA 8020	Toluene EPA 8020	Ethylbenzene EPA 8020	Total Xylenes	ਜ MTBE ਨੂੰ EPA 8020	MTBE EPA 8240	TPHD LUFT Method
	· · · · · · · · · · · · · · · · · · ·									P5.2		P6, 2	P 5/ E		μ5/-2	75.0
A I	R-1 03-24-95	15.61	7.25	8 36	ND	NW	0 009	03-24-95	270	14	0.6	2,5	2 i			130^^^
AI		15.61	11 37	4.24	ND	NW	0 002	06-05-95	190	10	<0.5	0.8	0.5			580^
AI		15 61	12 40	3 21	ND	w	0 001	08-17-95	960	110	12	4.5	150	14		<50
	R-1 12-04-95	15 61	12 90	2.71	ND	NNW	0.002	12-04-95	<50	1.5	<0.5	<0.5	0.8			
A!	R-1 03-01-96	15.61	8.19	7.42	ND	NW	0.003	03-13-96	150	3.8	0.5	1.4	1.3	<3		
AI	R-1 05-29-96	15.61	10.41	5 20	ND	NW	0 002	05-29-96	Not sampled	i: well sam	oled semi-a	nnually, du	ring the fire	st and third	quarters	
ΑI	R-I 08-29-96	15 61	12 12	3 49	ND	W	0 002	08-29-96	<50	<0.5	< 0.5	< 0.5	0.8	<3		
AI	R-1 11-21-96	15 61	11 52	4 09	NĐ	WNW	0 002	11-21-96	Not sampled	l well samp	oled semi-a	nnually, du	ring the firs	st and third	quarters	
ΑI	R-1 03-26-97	15 61	11 33	4.28	ND	NW	0.002	03-26-97	<50	<0.5	<0.5	< 0.5	<0.5	<3		
Al	₹-2 03-24-95	15 28	9.13	6 15	ND	NW	0 009	03-24-95	<50	62	<0.5	< 0.5	06			<50
AI	R-2 06-05-95	15 28	12 09	3 19	ND	NW	0 002	06-05-95	<50	<0.5	<0.5	<0.5	< 0.5			<50
AI	R-2 08-17-95	15 28	12 78	2 50	ND	W	0 001	08-18-95	<50	<0.5	<0.5	<0.5	<0.5	4		<50
ΑI	R-2 12-04-95	15.28	11 44	3.84	ND	NNW	0.002	12-13-95	<50	<0.5	<0.5	<0.5	< 0.5			
	R-2 03-01-96	15 28	9 83	5 45	ND	NW	0.003	03-13-96	190	26	2.6	3 3	13	200		
	R-2 05-29-96	15 28	10 97	431	ND	NW	0 002	05-29-96	Not sampled					st and third	quarters	
	R-2 08-29-96	15 28	12 20	3 08	ND	W	0 002	08-29-96	<50	< 0.5	<0.5	<0.5	< 0.5	95		
	R-2 11-21-96	15.28	11 57	3.71	ND	WNW	0.002	11-21-96	Not sampled	-		nnually, du	ring the firs	st and third	quarters	
A	R-2 03-26-97	15.28	11.60	3 68	ND	NW	0.002	03-26-97	<50	<0.5	< 0.5	< 0.5	<0.5	9		

Table 2
Historical Groundwater Elevation and Analytical Data
Petroleum Hydrocarbons and Their Constituents
1994 - Present\*\*\*

Date: 06-06-97

Well Designation	Water Level Field Date	Top of Casing	Beath to Water	Groundwater Groundwater Elevation	Floating Product	Groundwater Flow Direction	Hydraulic Gradient	Water Sample Field Date	न TPHG ट्रिजिट LUFT Method	표 Benzene 역 EPA 8020	Toluene	Ethylbenzene	Total Xylenes	жт МТВЕ 7 ЕРА 8020	MTBE EPA 8240	TPHD LUFT Method
		TO INDE	1000	TO TO DE					μ <sub>0</sub> .	P6/2	P & P =	P612	μ <sub>6</sub> , ο	P8/C	p <sub>6</sub> , 2	Parc
ADR-1	03-24-95	13 95	8 04	** 5.92	0.01	NW	0.009	03-24-95	Not sampled	l: well conta	ained floati	ng product				
ADR-1	06-05-95	13 95	11 02	2 93	ND	NW	0.002	06-05-95	23000	310	420	300	1900			13000^
ADR-1	08-17-95	13 95	11.86	2 09	ND	w	0 001	08-18-95	4400	150	120	95	620	120		4500^
ADR-1	12-04-95	13 95	10.05	3.90	ND	NNW	0 002	12-13-95	8800	100	130	120	990			
ADR-1	03-01-96	13 95	8 76	5 19	ND	NW	0 003	03-13-96	89000	370	1000	840	8100	<500		
ADR-1	05-29-96	13.95	9 74	4.21	ND	NW	0.002	05-30-96	27000	230	380	370	2700	<100		
ADR-1	08-29-96	13.95	10 77	3 18	ND	W	0.002	08-29-96	5300	190	58	76	470	85		
ADR-1	11-21-96	13 95	10 49	3 46	ND	WNW	0.002	11-21-96	1900	82	21	32	270	110		
ADR-1	03-26-97	13 95	10.37	3 58	ND	NW	0 002	03-26-97	1300	260	6	39	27	95		
ADR-2	03-24-95	14.64	8 41	NR*	>3 00*	NR*	NR*	03-24-95	Not sampled	i. well conta	uned floati	ng product				
ADR-2	06-05-95	14 64	11.45	NR*	>3 00*	NR*	NR*	06-05-95	Not sampled			<b>~</b> .				
ADR-2	08-17-95	14 64	12.10	** 2 56	0 03	W	0.001	08-17-95	Not sampled	l; well conta	ained floati	ng product				
ADR-2	12-04-95	14 64	10.93	** 3.73	0 03	NNW	0 002	12-13-95	Not sampled	well conta	ained floati	ng product				
ADR-2	03-01-96	14 64	8 74	5.90	ND	NW	0 003	03-13-96	29000	1100	1200	710	3800	<500		
ADR-2	05-29-96	14.64	10 43	4 21	ND	NW	0 002	05-29-96	33000	510	500	470	2300	120		
ADR-2	08-29-96	14 64	11.64	3 00	ND	W	0 002	08-29-96	8000	230	180	150	730	53		
ADR-2	11-21-96	14 64	11 23	3 41	ND	WNW	0.002	11-21-96	15000	630	440	390	2100	75		
ADR-2	03-26-97	14 64	11 13	3.51	ND	NW	0 002	03-26-97	6100	320	23	180	400	32		

Table 2
Historical Groundwater Elevation and Analytical Data
Petroleum Hydrocarbons and Their Constituents
1994 - Present\*\*\*

Date:		

Well Designation	Water Level Field Date	Top of Caving Elevation	Depth to Water	Groundwater Elevation	Floating Product Thickness	Groundwater Flow Direction	Hydrawlic Gradient	Water Sample Field Date	TPHG LUFT Method	Benzene EPA 8020	Toluene BPA 8020	Ethylbenzene EPA 8020	Total Xylenes EPA 8020	MTBE EPA 8020	<b>MTBE</b> EPA 8240	TPHD LUFT Method
		ft-MSL	feet	ft-MSL	feet	MWN	ft/ft		μg/L	μg/L	μg/L	µg/L	μg/L	μg/L	μg/L	μg/L

ft-MSL, elevation in feet, relative to mean sea level

MWN groundwater flow direction and gradient apply to the entire monitoring well network

ft/ft foot per foot

TPHG total petroleum hydrocarbons as gasoline, California DHS LUFT Method

µg/L micrograms per liter

EPA United States Environmental Protection Agency

MTBE: Methyl tert-butyl ether

TPHD: total petroleum hydrocarbons as diesel, California DHS LUFT Method

ND none detected

NR, not reported; data not available or not measurable

NW. northwest

WNW: west-northwest

W west

NNW north-northwest

<sup>^</sup> method reporting limit was raised due to (1) high analyte concentration requiring sample dilution, or (2) matrix interference

<sup>^^</sup> sample contains a single non-fuel component eluting in the gasoline range, and quantified as gasoline

<sup>^^:</sup> sample contains a mixture of diesel and a lower boiling point hydrocarbon quantitated as diesel, chromatogram does not match the typical diesel fingerprint

<sup>^^^</sup> sample contains components eluting in the diesel range, quantified as diesel, chromatogram does not match the typical diesel fingerprint

<sup>- -</sup> not analyzed or not applicable

<sup>\*</sup> well contained more than 3 feet of floating product; exact product thickness and groundwater elevation could not be measured

<sup>\*\*. [</sup>corrected elevation (Z')] = Z + (h \* 0.73) where Z = measured elevation, h = floating product thickness, 0.73 = density ratio of oil to water

<sup>\*\*\*</sup> For previous historical groundwater elevation data please refer to Fourth Quarter 1995 Groundwater Monitoring Program Results and Remediation System Performance Evaluation Report, ARCO Service Station 2169, 889 West Grand Avenue, Oakland, California, (EMCON, March 4, 1996)

Table 3
Approximate Cumulative Floating Product Recovered

Date: 06-06-97

ARCO Service Station 2169 889 West Grand Avenue, Oakland, CA

Well Desig- nation	Date	Floating Product Recovered gallons
	1004	
ADR-1	1994	0 0
ADR-2		0.0
ADR-1	1995	0 0
ADR-2		4.8
ADR-1	1996	0.0
ADR-2		0.0
ADR-1	1997	0.0
ADR-2	****	0.0
	1994 to 1997 Total:	4 8

Table 4 Soil-Vapor Extraction System Operation and Performance Data

Location: 889 West Grand Avenue

Oakland, California

Consultant: EMCON

Vapor Treatment Unit: ThermTech Model

VAC-25, 250cfm Thermal/

Catalytic Oxidizer

Start-Up Date: 06-02-94

1921 Ringwood Avenue Operation and Performance Data From 06-02-94 San Jose, California

To: 04-01-97

System was shut down on 1-15-97

		S	ystem was shu	t down on 1-15	5-97. 
Beginning Date:	06-02-94	06-02-94	06-07-94	06-16-94	06-22-94
Ending Date:	06-02-94	06-07-94	06-16-94	06-22-94	06-30-94
Down-time (days):	0	0	1	0	4
Total Operation (days):	0	5	8	6	4
Total Operation (hours):	1.7	121.3	193.7	145.2	106.3
Operation Hours to Date.	1.7	123.0	316.7	462 0	568.2
TPH Concentrations					
Average Influent (ppmv):	18,000	16,000	830	1,100	230
Average Effluent (ppmv):	ND	45	ND	4.9	75 0
Benzene Concentrations					
Average Influent (ppmv):	270	420	17	24	3.8
Average Effluent (ppmv):	ND	0.30	ND	0.08	0.78
Flow Rates					
Average Influent (scfm):	61.1	131.5	145.3	194.1	176.7
Average Dilution (scfm):	184.2	97.8	69.9	0.0	0 0
Average Effluent (scfm):	268.6	272.3	289.7	264.4	288.9
TPH-G Recovery Data					
Recovery Rate (lbs/hr):	11.12	21.26	1.22	2 16	0.41
Recovery Rate (lbs/day):	266 80	510.34	29.27	51 77	9.86
Destruction Efficiency (%):	100.00	99.46	100.00	99.39	46.70
Product Recovered (lbs):	18.68	2779.35	236.08	313.27	43.64
Product Recovered to Date (lbs):	18.68	2798.02	2834.10	3147.37	3191 01
Product Recovered to Date (gal):	3.11	433.00	472.35	524.56	531.83
Benzene Recovery Data					
Recovery Rate (lbs/hr):	0.185	0.670	0 030	0.056	0 008
Recovery Rate (lbs/day):	4.447	16.076	0.719	1.355	0 195
Destruction Efficiency (%):	100.00	99.86	100.00	99.56	66.45
Product Recovered (lbs):	0.311	81.249	5 802	8.202	0 865
Product Recovered to Date (lbs):	0.311	81.561	87 363	95.565	96.430
Product Recovered to Date (gal):	0.043	11.270	12.050	13.181	13.301

#### Page 1 Footnotes

ppmy parts per million by volume

setm, standard cubic feet per minute

lbs/hr: pounds per operational hour

lbs/day pounds per day

lbs: pounds

gal, gallons

ND: None Detected, Recovery data calculated using laboratory detection limits

- 1 Molecular weights used in recovery calculations are 65 for TPH and 78 for benzene
- 2 Densities used in recovery calculations are 6.0 lbs/gal for TPH and 7.27 lbs/gal for benzene
- All data and calculations on this page were prepared by GeoStrategies. Inc. (GSI), as presented in Letter Report, Vapor Extraction Start Up and Quarterly Groundwater Monitoring, Second Quarter 1994, (GSI, September 1994)

Table 4 Soil-Vapor Extraction System Operation and Performance Data

Facility Number: 2169

Location: 889 West Grand Avenue

Oakland, California

Vapor Treatment Unit ThermTech Model

VAC-25, 250cfm Thermal/

Catalytic Oxidizer

Consultant: EMCON

1921 Ringwood Avenue

Start-Up Date: 06-02-94 Operation and Performance Data From: 06-02-94

	San Jose, California		•	ystem was shut	To: 04	I-01-97
Date Begin:		07-01-94	08-01-94	09-01-94	12-01-94	01-01-95
Date End:		08-01-94	09-01-94	12-01-94	01-01-95	02-01-95
Mode of Oxidation		Therm-Ox	Cat-Ox	Cat-Ox	Cat-Ox	Cat-Ox
Days of Operation:		11	17	35	16	26
Days of Downtime:		20	14	56	15	5
Average Vapor Concer	trations (1)					
	ppmv (2) as gasoline	1983	680	450	1500	<15
	mg/m3 (3) as gasoline	5333	1800	1200	5600	<60
	ppmv as benzene	29	7.6	2.9	7	<0 1
	mg/m3 as benzene	95	25	9 4	22	< 0.5
System Influent.	ppmv as gasoline	1983	680	450	400	<15
•	mg/m3 as gasoline	5333	1800	1200	1600	<60
	ppmv as benzene	29	7.6	29	19	<0.1
	mg/m3 as benzene	95	25	9.4	6	<0.5
System Effluent	ppmv as gasoline	17	44	4 1	<15	<15
•	mg/m3 as gasoline	46	118	11.1	<60	<60
	ppniv as benzene	0.15	0.7	0 04	< 0.1	<0.1
	mg/m3 as benzene	0.49	2.3	0.143	<0.5	< 0.5
Average Well Field Flov	v Rate (4), scfm (5)	198.3	212.6	214 3	17.7	167
Average System Influen	t Flow Rate (4), scfm:	198 3	212.6	214.3	120 1	164.3
Average Destruction Ef	ficiency (6), percent (7)	99 1	93.4	99.1	96 3	NA
Average Emission Rate	s (8), pounds per day (9)					
Gasoline;		0 82	2.25	0.21	0 65	0.89
Benzene:		0 01	0 04	0.00	0 01	0.01
Operating Hours This Pe	eriod:	255.95	414.28	833.57	385.86	614.80
Operating Hours To Dat	e·	256.0	670 2	1503 8	1889.7	2504.5
Pounds/ Hour Removal	Rate, as gasoline (10).	3.96	1 43	0 96	0.37	0 00
Pounds Removed This P	eriod, as gasolme (11):	<u>1013 1</u>	<u>593 4</u>	802.3	<u>143 l</u>	<u>23</u>
Pounds Removed To Da	te, as gasoline:	4204 1	4797,4	5599.7	5742 9	5745.2
Gallons Removed This I	Period, as gasoline (12).	<u> 163 4</u>	<u>95.7</u>	<u>129 4</u>	<u>23 1</u>	<u>0,4</u>
Gallons Removed To Da	nte, as gasoline	678.1	773 8	903 2	926 3	926.7

Table 4 Soil-Vapor Extraction System Operation and Performance Data

Location: 889 West Grand Avenue

Oakland, California

Vapor Treatment Unit: ThermTech Model VAC-25, 250cfm Thermal/ Catalytic Oxidizer

Consultant:	EMCON 1921 Ringwood Avenue San Jose, California		·	Performance 1	rt-Up Date: 06 Data From: 06 To: 04 down on 1-15	5-02-94 1-01-97
Date Begin:		02-01-95	07-01-95	08-01-95	09-01-95	10-01-95
Date End.		07-01-95	08-01-95	09-01-95	10-01-95	11-01-95
Mode of Oxidation:		Cat-Ox	Cat-Ox	Cat-Ox	Cat-Ox	Cat-Ox
Days of Operation:		0	14	19	27	12
Days of Downtime		150	17	12	3	19
Average Vapor Concen	trations (1)					
	ppmv (2) as gasoline	NA (13)	1567	1975	1400	250
	mg/m3 (3) as gasoline	NA	5767	7175	5200	900
	ppmv as benzene	NA	12	10	3 1	0.6
	mg/m3 as benzene	NA	40	33	10	1.7
System Influent:	ppmv as gasoline	NA	200	270	230	66
2,	mg/m3 as gasoline	NA	740	970	920	240
	ppmv as benzene	NA	1.6	1	0.6	0.1
	mg/m3 as benzene	NA	5 2	3 3	8 1	< 0.5
System Effluent.	ppmv as gasoline	NA	23	<15	<15	<15
ŕ	mg/m3 as gasoline	NA	83	<60	<60	<60
	ppmv as benzene	NA	< 0.1	1.0>	< 0.1	1.0>
	mg/m3 as benzene	NA	< 0.5	< 0.5	< 0.5	< 0.5
Average Well Field Flow	Rate (4), scfm (5).	0 0	27.9	43.0	58.1	67.0
Average System Influent		0 0	197.6	166.8	167.9	174,1
Average Destruction Eff	iciency (6), percent (7).	NA	88.8	93.8	93.5	75.0
Average Emission Rates	s (8), pounds per day (9)					
Gasoline.		0.00	1.47	0.90	0.90	0.94
Benzene:		0 00	0.01	0.01	0.01	0.01
Operating Hours This Pe.	riod:	0.00	346.17	462,40	652.27	278.16
Operating Hours To Date		2504 5	2850 6	3313 0	3965 3	4243 5
Pounds/ Hour Removal F	Rate, as gasoline (10).	0 00	0 60	1 15	1 13	0 23
Pounds Removed This Pe	eriod, as gasoline (11)	<u>0.0</u>	<u>208.5</u>	<u>533 9</u>	<u>737 6</u>	<u>62 8</u>
Pounds Removed To Dat	e, as gasoline:	5745.2	5953.6	6487 6	7225 1	7287 9
Gallons Removed This P	eriod, as gasoline (12)	<u>0 0</u>	<u>33 6</u>	<u>86 1</u>	<u>119 0</u>	<u> 10 1</u>
Gallons Removed To Da	te, as gasoline:	926 7	960 3	1046 4	1165 4	1175 5

Table 4 Soil-Vapor Extraction System Operation and Performance Data

Location: 889 West Grand Avenue

Oakland, California

Vapor Treatment Unit: ThermTech Model

VAC-25, 250cfm Thermal/

Catalytic Oxidizer

Consultant: EMCON

1921 Ringwood Avenue

Start-Up Date: 06-02-94 Operation and Performance Data From: 06-02-94

San Jose, California		Sy	stem was shut	To: 04 down on 1-15	1-01-97 -97.
Date Begin:	11-01-95	01-01-96	04-01-96	07-01-96	08-01-96
Date End:	01-01-96	04-01-96	07-01-96	08-01-96	09-01-96
Mode of Oxidation:	Cat-Ox	Cat-Ox	Cat-Ox	Cat-Ox	Cat-Ox
Days of Operation:	0	0	0	0	18
Days of Downtime.	61	91	91	31	13
Average Vapor Concentrations (1)					
Well Field Influent. ppmv (2) as gasoline	NA	NA	NA	NA	140
mg/m3 (3) as gasoline	NA	NA	NA	NA	570
ppmv as benzene	NA	NA	NA	NA	16
mg/m3 as benzene	NA	NA	NA	NA	5
System Influent: ppmv as gasoline	NA	NA	NA	NA	73
mg/m3 as gasoline	NA	NA	NA	NA	300
ppmv as benzene	NA	NA	NA	NA	0.8
mg/m3 as benzene	NA	NA	NA	NA	2 6
System Effluent: ppmv as gasoline	NA	NA	NA	NA	<5
mg/m3 as gasoline	NA	NA	NA	NA	<20
ppmv as benzene	NA	NA	NA	NA	< 0.2
mg/m3 as benzene	NA	NA	NA	NA	< 0.5
Average Well Field Flow Rate (4), scfm (5)	0 0	0.0	0.0	0.0	119.3
Average System Influent Flow Rate (4), scfm:	0.0	0.0	0 0	0 0	153 0
Average Destruction Efficiency (6), percent (7).	NA	NA	NA	NA	93 3
Average Emission Rates (8), pounds per day (9)					
Gasoline:	0 00	0.00	0.00	0 00	0.27
Benzene <sup>1</sup>	0.00	0.00	0 00	0 00	0.01
Operating Hours This Period.	0.00	0.00	0 00	<u>182</u>	<u>435 13</u>
Operating Hours To Date:	4243.5	4243.5	4243 5	4245 3	4680.4
Pounds/ Hour Removal Rate, as gasoline (10)	0 00	0 00	0.00	0.00	0.25
Pounds Removed This Period, as gasoline (11).	0.0	<u>0 0</u>	<u>0 0</u>	0.0	110.7
Pounds Removed To Date, as gasoline.	7287 9	7287.9	7287.9	7287 9	7398 7
Gallons Removed This Period, as gasoline (12)	00	0.0	0.0	<u>0 0</u>	<u>17 9</u>
Gallons Removed To Date, as gasoline	1175 5	1175.5	1175 5	1175 5	1193 4

Table 4 Soil-Vapor Extraction System Operation and Performance Data

Location: 889 West Grand Avenue

Oakland, California

Vapor Treatment Unit: ThermTech Model

VAC-25, 250cfm Thermal/

Catalytic Oxidizer

Consultant: EMCON

1921 Ringwood Avenue San Jose, California

Start-Up Date. 06-02-94 Operation and Performance Data From 06-02-94

To: 04-01-97

San Jose, California		Sy	stem was shut	10: 04-01-97 down on 1-15-97
Date Begin	09-01-96	10-01-96	11-01-96	12-01-96
Date End	10-01-96	11-01-96	12-01-96	01-01-97
Mode of Oxidation:	Cat-Ox	Cat-Ox	Cat-Ox	Cat-Ox
Days of Operation	8	30	0	2
Days of Downtime:	22	1	30	29
verage Vapor Concentrations (1)				
Well Field Influent. ppmv (2) as gasoline	770	110	NA	300
mg/m3 (3) as gasoline	3200	460	NA	1200
ppmv as benzene	2 4	1.5	NA	< 0.5
mg/m3 as benzene	7.8	4.9	NA	<2
System Influent: ppmv as gasoline	300	39	NA	300
mg/m3 as gasoline	1200	160	NA	1200
ppmv as benzene	0.8	0.5	NA	<0.5
mg/m3 as benzene	2.6	1.7	NA	<2
System Effluent: ppmv as gasoline	<5	<5	NA	11
mg/m3 as gasoline	<20	<20	NA	46
ppmv as benzene	< 0.1	< 0.2	NA	<0.1
mg/m3 as benzene	< 0.4	<0.5	NA	< 0.4
verage Well Field Flow Rate (4), sofm (5).	128.6	99 3	0.0	148.8
verage System Influent Flow Rate (4), scfm.	204.3	157 7	0 0	148.8
verage Destruction Efficiency (6), percent (7):	98.3	87.5	NA	96 2
verage Emission Rates (8), pounds per day (9)				
Gasoline:	0 37	0 28	NA	0 61
Benzene:	0.01	0.01	NA	0.01
perating Hours This Period	180.20	730.20	0.19	43.83
Operating Hours To Date	4860.6	5590.8	5591 0	5634.8
ounds/ Hour Removal Rate, as gasoline (10):	1 54	0.17	0.00	0 67
ounds Removed This Period, as gasoline (11):	<u>277.5</u>	<u>124.8</u>	<u>0.0</u>	<u>29.3</u>
Pounds Removed To Date, as gasoline:	7676.2	7801.0	7801.0	7830 3
Gallons Removed This Period, as gasoline (12):	44.8	<u>20.1</u>	<u>0.0</u>	<u>4 7</u>
Gallons Removed To Date, as gasolme:	1238.2	1258.3	1258.3	1263 0

Table 4
Soil-Vapor Extraction System
Operation and Performance Data

Facility Number: 2169

Location: 889 West Grand Avenue

Oakland, California

Vapor Treatment Unit: ThermTech Model

VAC-25, 250cfm Thermal/

Catalytic Oxidizer

Consultant: EMCON

Start-Up Date: 06-02-94 Operation and Performance Data From: 06-02-94

1921 Ringwood Avenuc San Jose, California		-	Performance Data	To: 04-01-97
Date Begin:	01-01-97	02-01-97	03-01-97	
Date End:	02-01-97	03-01-97	04-01-97	
Mode of Oxidation:	Cat-Ox	Cat-Ox	Cat-Ox	
Days of Operation.	9	0	0	
Days of Downtime	22	28	31	
Average Vapor Concentrations (1)				
Well Field Influent: ppmv (2) as gasoline	NA	NA	NA	
mg/m3 (3) as gasoline	NA	NA	NA	
ppmv as benzene	NA	NA	NA	
mg/m3 as benzene	NA	NA	NA	
System Influent: ppmv as gasoline	NA	NA	NA	
mg/m3 as gasoline	NA	NA	NA	
ppmy as benzene	NA	NA	NA	
mg/m3 as benzene	NA	NA	NA	
System Effluent: ppmv as gasoline	NA	NA	NA	
mg/m3 as gasoline	NA	NA	NA	
ppmy as benzene	NA	NA	NA	
mg/m3 as benzene	NA	NA	NA	
Average Well Field Flow Rate (4), scfm (5).	148.8	0.0	0.0	
Average System Influent Flow Rate (4), scfm.	148.8	0.0	0 0	
Average Destruction Efficiency (6), percent (7):	NA	NA	NA	
Ayerage Emission Rates (8), pounds per day (9)				
Gasoline:	NA	NA	NA	
Benzene.	NA	NA	NA	
Operating Hours This Period:	215.74	0.00	0.00	
Operating Hours To Date:	5850.6	5850 6	5850 6	
Pounds/ Hour Removal Rate, as gasoline (10).	0.00	0.00	0.00	
Pounds Removed This Period, as gasoline (11).	0.0	0.0	<u>0 0</u>	
Pounds Removed To Date, as gasoline:	7830 3	7830 3	7830 3	
Gallons Removed This Period, as gasoline (12):	<u>0 0</u>	<u>0 0</u>	<u>0 0</u>	
Gallons Removed To Date, as gasoline	1263 0	1263 0	1263.0	

# Table 4 Soil-Vapor Extraction System Operation and Performance Data

Facility Number: 2169

Location: 889 West Grand Avenue

Oakland, California

Vapor Treatment Unit: ThermTech Model

VAC-25, 250cfm Thermal/

Catalytic Oxidizer

Consultant: EMCON

1921 Ringwood Avenue San Jose, California Start-Up Date: 06-02-94 Operation and Performance Data From: 06-02-94

To: 04-01-97

System was shut down on 1-15-97.

CURRENT REPORTING PERIOD:	01-01-97	to	04-01-97
DAYS / HOURS IN PERIOD.	90	2160	0.0
DAYS / HOURS OF OPERATION:	9	215	5 7
DAYS / HOURS OF DOWN TIME:	81	1944	13
PERCENT OPERATIONAL		10	0.0 %
PERIOD POUNDS REMOVED:	0.0		
PERIOD GALLONS REMOVED:	0 0		
AVERAGE WELL FIELD FLOW RATE (scfm)		148	3.8
AVERAGE SYSTEM INFLUENT FLOW RATE (scfm)		148	3.8

For the period from July 1 to December 1, 1994, ppmy results were converted to mg/m3 using the following formula:

concentration (as gasoline in mg/m3) = [concentration (as gasoline in ppmv) x 65 lb/lb-mole / 24 05 (lb/m3/lb-mole of atr)/mg] (rounded as appropriate) concentration (as benzene in mg/m3) = [concentration (as benzene in ppmv) x 78 lb/lb-mole / 24 05 (lb/m3/lb-mole of atr)/mg] (rounded as appropriate) For the period from December 1, 1994, to July 1, 1995, ppmv results were converted to mg/m3 using the following formula:

concentration (as gasoline in mg/m3) = [concentration (as gasoline in ppmv) x 87 lb/lb-mole / 24 05 (lb/m3/lb-mole of air)/mg] (rounded as appropriate) concentration (as benzene in mg/m3) = [concentration (as benzene in ppmv) x 78 lb/lb-mole / 24 05 (lb/m3/lb-mole of air)/mg] (rounded as appropriate) After July 1, 1995, all vapor results were reported by the laboratory in ppmv and mg/m3.

- 4. Average flow rates (time weighted average) are based on instantaneous flow rates recorded during the month; refer to Appendix B for instantaneous flow data
- 5. setm. flow in standard cubic feet per minute at one atmosphere and 70 degrees Fahrenheit
- 6 Average destruction efficiencies are calculated using monthly average concentrations refer to Appendix B for instantaneous destruction efficiency data
- destruction efficiency, percent = ([system influent concentration (as gasoline in mg/m3)] system influent concentration (as gasoline in mg/m3)] / system influent concentration (as gasoline in mg/m3)) x 100 percent
- 8 Average emission rates are calculated using monthly average concentrations and flow rates, refer to Appendix B for instantaneous emission rate data.
- 9 emission rates (pounds per day) = system effluent concentration (as gasoline or benzene in mg/m3) x system influent flow rate (scfm) x 0 02832 m3/ft3 x 1440 minutes/day x 1 pound/454,000 mg
- 10 pounds/ hour removal rate (as gasoline) = well field influent concentration (as gasoline in mg/m3) x well field influent flow rate (scfm) \$\times 0.02832 \text{ m3/ft3} x 60 \text{ minutes/hour x 1 pound/454.000 mg}\$
- 11 pounds removed this period (as gasoline) = pounds/ hour removal rate x hours of operation
- 12. gallons removed this period (as gasoline) = pounds removed this period (as gasoline) x 0.1613 gallons/pound of gasoline
- 13 NA not applicable, not analyzed, or not available

<sup>1</sup> Average concentrations are based on discrete sample results reported during the month, refer to Appendix B for discrete sample results

<sup>2</sup> ppmy parts per million by volume

<sup>3.</sup> mg/m3 milligrams per cubic meter

Table 5
Soil-Vapor Extraction Well Data

Date: 05-30-97

						Well Iden	ufication					
		A-I		<u> </u>	A-2			A-3		<del></del>	A-4	<u> </u>
	Valve		Vacuum	Valve		Vacuum	Valve		Vacuum	Valve		Vacuum
Date	Position	TVHG	Response	Position	TVHG	Response	Position	TVHG	Response	Position	TVHG	Respons
		ppmv	ın-H2O		ppmv	in-H2O		ppmv	ın-H2O		ppmv	ın-H2C
or SVE well mo	I onitoring data prior	to January 1, 199	5. please refer to	the third quarter 19	95 groundwater n	nonitoring report fo	r this site					
01-13-95	passive	NA	0	passive	NA	0	passive	NA	0	passive	NA	0
01-26-95	passive	NA	0	passive	NA	0	passive	NA	0	passive	NA	0
07-17-95	System was shut of	down on January	26. 1995	System was restar	ted on July 17, 19	995						
07-17-95	closed	NA	NA	closed	NA	NA	closed	NA	NA	closed	NA	NA
07-25-95	closed	NA	NA	closed	NA	NA	closed	NA	NA	closed	NA	NA
08-22-95	closed	NA	NA	closed	NA	NA	closed	NA	NA	closed	NA	NA
09-21-95	closed	NA	0	closed	NA	0	closed	NA	0	closed	NA	0
09-21-95	open	NA	46	closed	NA	0	closed	NA	0	closed	NA	0
09-21-95	open	600 LAB	NA	closed	NA	NA	closed	NA	NA	closed	NA	NA
10-12-95	open	NA	36	closed	NA	0	closed	NA	0	closed	NA	0
10-12-95	System was manu	ally shut down										
08-02-96	closed	NA	0	closed	NA	0	open	NA	46	closed	NA	0
08-05-96	closed	NA	NA	closed	NA	NA	open	NA	22	closed	NA	NA
09-23-96	closed	NA	NA	closed	NA	NA	closed	NA	NA	closed	NA	NA
10-24-96	closed	NA	NA	closed	NA	NA	closed	NA	NA	closed	NA	NA
12-04-96	closed	NA	NA	closed	NA	NA	closed	NA	NA	closed	NA	NA
01-15-97	System was manu	ally shut down										

TVHG, concentration of total volatile hydrocarbons as gasoline

ppmv parts per million by volume

in-H2O inches of water

open, open to the system

passive open to the atmosphere

closed closed to the system and atmosphere

NA not analyzed or not measured

FID: TVHG concentration was measured with a portable flame ionization detector

LAB TVHG concentration was analyzed in the laboratory

PID TVHG concentration was measured with a portable photoionization detector

Table 5
Soil-Vapor Extraction Well Data

ARCO Service Station 2169

889 West Grand Avenue, Oakland, CA
Date 05-30-97

						Well Ider	tufication					
		AV-I		<u> </u>	AV-2			AV-3	<del></del>		AV-4	
Date	Valve Position	TVHG	Vacuum Response	Valve Position	TVHG	Vacuum Response	Valve Position	ТVНG	Vacuum Response	Valve Position	TVHG	Vacuum Respons
		ppmv	ın-H2O	_	ppmv	in-H2O		ppmv	in-H2O		ppmv	ın-H2O
or SVE well m	onitoring data prior	to January 1, 199	5. please refer to	T the third quarter 19	95 groundwater m	onitoring report fo	r this site					
01-13-95	passive	NA	15	passive	NA	0	passive	NA	0	ореп	463 PID	16
01-26-95	passive	NA	27	passive	NA	0	passive	NA	0	open	1 8 FID	30
07-17-95	System was shut of	down on January 2	26, 1995	System was resta	rted on July 17, 19	95						
07-17-95	open	NA	NA	open	NA	NA	open	NA	NA	closed	NA	NA
07-25-95	ореп	1026 PID	42	орел	1364 PID	42	open	869 PID	42	closed	NA	NA
07-25-95	open	1200 LAB	NA	open	1600 LAB	NA	open	980 LAB	NA	closed	NA	NA
08-22-95	open	NA	42	ореп	NA	44	open	NA	44	closed	NA	NA
09-21-95	open	NA	43	open	NA	47	open	NA	47	closed	NA	0
09-21-95	open	NA	46	open	NA	46	open	NA	46	closed	NA	1
10-12-95	open	NA	44	open	NA	43	open	NA	43	closed	NA	1
10-12-95	System was manu	ally shut down		f								
08-02-96	closed	48 5 PID	6	open	863 PID	46	open	322 PID	44	closed	NA	0
08-05-96	closed	NA	NA	open	NA	32	open	NA	36	open	NA	32
09-23-96	open	NA	42	open	NA	50	open	NA	53	open	NA	50
10-24-96	open	NA	NA	ореп	NA	NA	open	NA	NA	open	NA	NA
12-04-96	open	NA	NA	open	NA	NA	open	NA	NA	ореп	NA	NA
01-15-97	System was manu	ally shut down								•		
						:						

TVHG, concentration of total volatile hydrocarbons as gasoline

ppmv parts per million by volume

in-H2O inches of water

open open to the system

passive open to the atmosphere

closed: closed to the system and atmosphere

NA not analyzed or not measured

FID TVHG concentration was measured with a portable flame ionization detector

LAB. TVHG concentration was analyzed in the laboratory

PID TVHG concentration was measured with a portable photoionization detector

Table 5
Soil-Vapor Extraction Well Data

Date: 05-30-97

						Well Ider	itification					
		AV-5	<del></del>		AV-6			AV-7		<u> </u>	AR-2	-
	Valve		Vacuum	Valve		Vacuum	Valve		Vacuum	Valve		Vacuun
Date	Position	TVHG	Response	Position	TVHG	Response	Position	TVHG	Response	Position	TVHG	Respons
_		ppmv	ın-H2O		ppmv	ın-H2O		ppmv	in-H2O		ppmv	ın-H2C
or SVE well me	l onitoring data prior	to January 1, 199	5. please refer to	T the third quarter 19	95 groundwater me	onitoring report fo	r this site.					
01-13-95	passive	NA	1	open	46 PID	16	passive	NA	Đ	passive	NA	0
01-26-95	open	2 2 FID	30	open	2 3 FID	30	passive	NA	0	passive	NA	0
07-17-95	System was shut	down on January	26, 1995	System was resta	rted on July 17, 19	95						
07-17-95	closed	NA	NA	closed	NA	NA	closed	NA	NA	closed	NA	NA
07-25-95	closed	NA	NA	closed	NA	NA.	closed	NA	NA	closed	NA	NA
08-22-95	closed	NA	NA	closed	NA	NA	closed	NA	NA	open	NA	44
09-21-95	closed	NA	0	closed	NA	0	closed	NA	0	open	NA	48
09-21-95	closed	NA	0	open	NA	46	closed	NA	0	open	NA	46
09-21-95	closed	NA	NA	open	2300 LAB	NA	closed	NA	NA	open	NA	NA
10-12-95	closed	NA	0	open	NA	42	closed	NA	0	open	NA	43
10-12-95	System was manu	ally shut down		1								
08-02-96	open	NA	44	open	185 PID	42	ореп	NA	44	closed	NA.	40
08-05-96	open	NA	30-36	open	NA	32	open	NA	34	open	NA	28
09-23-96	open	455 PID	50	open	282 PID	49	closed	NA	NA	open	13 2 PID	45
10-24-96	open	NA	NA	open	NA	NA	closed	NA	NA	open	NA	NA
12-04-96	open	NA	NA	open	NA	NA	closed	NA	NA	open	NA	NA
		ally shut down		l .								

TVHG concentration of total volatile hydrocarbons as gasoline

ppmv parts per million by volume

in-H2O inches of water

open open to the system

passive open to the atmosphere

closed; closed to the system and atmosphere

NA not analyzed or not measured

FID: TVHG concentration was measured with a portable flame ionization detector

LAB. TVHG concentration was analyzed in the laboratory

PID TVHG concentration was measured with a portable photoionization detector

Table 5
Soil-Vapor Extraction Well Data

Date 05-30-97

						Well Ide
		ADR-1			ADR-2	
<b>\</b>	Valve		Vacuum	Valve		Vacuum
Date	Position	T∨HG	Response	Position	TVHG	Response
		ppmv	tn-H2O		ppmv	in-H2O
Ear SVE well me	I and the property of the prop	ro January 1 190	S. nlease refer to 1	the third quarter 19	95 groundwater me	onitaring report fo
01-13-95	open	58 PID	16	open	160 PID	16
01-26-95	open	2 2 FID	30	open	4 4 FID	30
14		down on January 2		1 '	rted on July 17, 19	
07-17-95	open	NA	NA	open	NA	NA NA
07-25-95	open	1184 PID	42	open	1057 PID	42
07-25-95	open	1400 LAB	NA	open	1300 LAB	NA.
08-22-95	open	NA	44	open	NA	44
08-22-93	1 -	NA NA	48	· ·	NA NA	47
	open		+o 45	open	NA NA	46
09-21-95	open	NA		open	NA NA	44
10-12-95	open	NA	43	open	NA	44
10-12-95	System was man	•			050 515	40
08-02-96	closed	NA	0	open	950 PID	42
08-05-96	closed	NA	NA	open	NA	32
09-23-96	open	1221 PID	NA	open	950 PID	50
10-24-96	open	NA	NA	open	NA	NA
12-04-96	open	NA	NA	open	NA	NA
01-15-97	System was man	ually shut down.				

TVHG concentration of total volatile hydrocarbons as gasoline

ppmv. parts per million by volume

in-H2O inches of water

open: open to the system

passive open to the atmosphere

closed closed to the system and atmosphere

NA not analyzed or not measured

FID TVHG concentration was measured with a portable flame ionization detector

LAB TVHG concentration was analyzed in the laboratory

PID: TVHG concentration was measured with a portable photoionization detector

Table 6
Air-Sparge System
Operation and Performance Data

Facility Number: 2169 Air-Sparge Unit:\*

Location: 889 West Grand Avenue 3-horsepower Conde blower
Oakland, California 5-horsepower air compressor

Consultant. EMCON Start-Up Date: 07-15-94

1921 Ringwood Avenue Operation and Performance Data From: 07-15-94

San Jose, California		To: 04-01-97 System was shut down on 1-15-97.					
		<del> </del>				-	
Date Begin:	07-15-94	08-01-94	08-01-94	08-01-94	08-15-94	09-13-94	
Date End:	08-01-94	08-01-94	08-01-94	08-15-94	09-13-94	11-28-94	
Days of Operation:	6	0	0	19	27	0	
Days of Downtime:	11	0	0	12	3	76	
Air-Sparge Well Status:							
AS-I	open	open	open	open	open	closed	
AS-2	open	open	open	open	open	closed	
AS-3	open	open	open	open	open	closed	
AS-4	open	open	open	open	open	closed	
AS-5	open	open	open	open	open	closed	
Air-Sparge Well Pressure (psig) (1):							
AS-1	2.8	2.8	3.0	2.0	2.4	0.0	
AS-2	3.0	3.0	2.8	2 2	2.4	0.0	
AS-3	3.6	3.6	3.8	3.1	2.2	0.0	
AS-4	3 1	3.1	3 4	3.0	2.8	0.0	
AS-5	2.8	2.8	3.2	2.8	3.2	0.0	
Total Air-Sparge Flow Rate (scfm) (2):	25.0	29.0	29.0	27.0	29.0	0.0	
Total Air-Sparge Pressure (psig):	5.0	2 8	2.8	2 6	3.0	0 0	
Dissolved Oxygen (mg/L) (3):							
Air-Sparge Wells:	NT 4 (4)	21.4	27.4		<b>N.</b> 1. A	1.4	
AS-1	NA (4)	NA	NA	NA	NA	1,4 1 2	
AS-2	NA	NA	NA	NA	NA NA	1 2	
AS-3	NA NA	NA NA	NA	NA	NA NA	0.8	
AS-4	NA NA	NA NA	NA NA	NA NA	NA NA	1.4	
AS-5	INA	NA	INA	IVA	NA	1.4	
Depth to Water (ft-BGS) (5):							
Air-Sparge Wells:							
AS-1	NA	NA	NA	NA	NA	10.55	
AS-2	NA	NA	NA	NA	NA	11.29	
AS-3	NA	NA	NA	NA	NA	10.78	
AS-4	NA	NA	NA	NA	NA	10.27	
AS-5	NA	NA	NA	NA	NA	10.65	

Table 6
Air-Sparge System
Operation and Performance Data

Facility Number: 2169 Air-Sparge Unit \* Location: 889 West Grand Avenue 3-horsepower Conde blower Oakland, California 5-horsepower air compressor Consultant: EMCON Start-Up Date: 07-15-94 Operation and Performance Data From: 07-15-94 1921 Ringwood Avenue To: 04-01-97 San Jose, California System was shut down on 1-15-97. 03-31-95 07-25-95 08-10-95 11-28-94 01-03-95 02-03-95 Date Begin: 03-31-95 06-28-95 Date End: 01-03-95 02-03-95 08-10-95 08-22-95 Days of Operation: 0 0 0 0 2 0 36 31 56 89 14 12 Days of Downtime: Air-Sparge Well Status: closed closed closed open open AS-1 closed closed closed closed closed closed closed AS-2 closed closed closed closed closed closed AS-3 closed closed closed open AS-4 closed open closed closed AS-5 closed closed closed closed Air-Sparge Well Pressure (psig) (1): 0.0 0.0 0.0 0.0 8.9 5 5 AS-1 0.0 0.0 0.0 0.0 0.0 AS-2 0.0 0.0 0.0 0.0 0.0 AS-3 00 0.0 0.0 0.0 0.0 2.0 2.3 0.0 AS-4 0.0 0.0 0.0 0.0 0.0 0.0 AS-5 0.0 0.0 0.0 2.0 2.0 Total Air-Sparge Flow Rate (scfm) (2). 0.0 Total Air-Sparge Pressure (psig): 0.0 0.0 0.0 0.0 50 45 Dissolved Oxygen (mg/L) (3): Air-Sparge Wells: NA NA NA NA 1.1 NA AS-1 NA NA NA NA NA NA AS-2 NA NA NA NA NA AS-3 NA NA 14 AS-4 NA NA NA NA 10 NA AS-5 NA NA NA NA Depth to Water (ft-BGS) (5): Air-Sparge Wells: NA 8.79 NA 11.75 NA AS-I NA AS-2 NA NA 9.37 NA NA NA NA 8.93 NA NA NA AS-3 NA NA NA 8.43 11.31 NA AS-4 NA

NA

8.80

NA

NA

11 62

NA

AS-5

Table 6 Air-Sparge System
Operation and Performance Data

Facility Number 2169 Air-Sparge Unit:\*

Location: 889 West Grand Avenue 3-horsepower Conde blower Oakland, California 5-horsepower air compressor

Consultant: EMCON

Start-Up Date: 07-15-94 Operation and Performance Data From: 07-15-94 1921 Ringwood Avenue

San Jose, California		To 04-01-97					
our rose, curronna		System was shut down on 1-15-97					
Date Begin:	08-22-95	09-21-95	10-12-95	01-01-96	04-01-96	07-01-96	
Date End:	09-21-95	10-12-95	01-01-96	04-01-96	07-01-96	08-01-96	
Days of Operation	11	NA	NA	NA	NA	0	
Days of Downtime:	19	NA	NA	NA	NA	31	
Air-Sparge Well Status:							
AS-1	open	closed	closed	closed	closed	closed	
AS-2	closed	closed	closed	closed	closed	closed	
AS-3	closed	closed	closed	closed	closed	closed	
AS-4	open	closed	closed	closed	closed	closed	
AS-5	open	closed	closed	closed	closed	closed	
Air-Sparge Well Pressure (psig) (1)							
AS-1	7.0	0.0	0.0	0.0	0.0	0.0	
AS-2	0.0	0.0	0.0	0.0	0.0	0.0	
AS-3	0.0	0.0	0.0	0.0	0.0	0.0	
AS-4	1.5	0.0	0.0	0.0	0.0	0.0	
AS-5	1.0	0.0	0.0	0.0	0 0	0.0	
Total Air-Sparge Flow Rate (scfm) (2):	6.0	0.0	0.0	0.0	0.0	0.0	
Total Air-Sparge Pressure (psig):	45	0	0	0	0	0.0	
Dissolved Oxygen (mg/L) (3): Air-Sparge Wells:							
AS-1	NA	7 4	NA	NA	NA	NA	
AS-2	NA	NA	NA	NA	NA	NA	
AS-3	NA	NA	NA	NA	NA	NA	
AS-4	NA	1.5	NA	NA	NA	NA	
AS-5	NA	1.6	NA	NA	NA	NA	
Depth to Water (ft-BGS) (5): Air-Sparge Wells:							
AS-1	NA	12.12	NA	NA	NA	NA	
AS-2	NA NA	NA	NA NA	NA.	NA	NA NA	
AS-3	NA.	NA	NA NA	NA	NA NA	NA NA	
AS-4	NA.	11.78	NA NA	NA NA	NA NA	NA NA	
AS-5	NA.	12.05	NA	NA NA	NA.	NA	
Un_n	14/1	12.03	1474	1474	11/7	11/1	

Table 6
Air-Sparge System
Operation and Performance Data

Facility Number: 2169 Air-Sparge Unit:\*

Location: 889 West Grand Avenue 3-horsepower Conde blower

Oakland, California 5-horsepower air compressor

Consultant: EMCON Start-Up Date. 07-15-94

1921 Ringwood Avenue Operation and Performance Data From: 07-15-94

San Jose, California		To: 04-01-97 System was shut down on 1-15-97.				
			System was	situt dowii	OII 1-13-97.	
Date Begin:	08-01-96	09-01-96	10-01-96	11-01-96	12-01-96	
Date End:	09-01-96	10-01-96	11-01-96	12-01-96	01-01-97	
Days of Operation:	18	0	30	0	2	
Days of Downtime:	13	22	1	30	29	
Air-Sparge Well Status.						
AS-1	open	open	open	closed	open	
AS-2	closed	open	open	closed	open	
AS-3	open	open	open	closed	open	
AS-4	open	open	open	closed	open	
AS-5	open	open	open	closed	open	
Air-Sparge Well Pressure (psig) (1):						
AS-1	2.0	1.5	2.0	0.0	2.0	
AS-2	NA	1.5	2.0	0.0	2.0	
AS-3	2.0	15	2.0	0.0	2.0	
AS-4	2 0	1.5	2.0	0.0	2.0	
AS-5	1.5	1.5	20	0.0	20	
Total Air-Sparge Flow Rate (scfm) (2):	6.0	12.0	9.0	0.0	9.0	
Total Air-Sparge Pressure (psig):	40	45	50	0	50	
Dissolved Oxygen (mg/L) (3): Air-Sparge Wells:						
AS-1	NA	NA	NA	NA	NA	
AS-2	NA	NA	NA	NA	NA	
AS-3	NA	NA	NA	NA	NA	
AS-4	NA	NA	NA	NA	NA	
AS-5	NA	NA	NA	NA	NA	
Depth to Water (ft-BGS) (5): Air-Sparge Wells:						
AS-1	NA	NA	NA	NA	NA	
AS-2	NA	NA	NA	NA	NA	
AS-3	NA	NA	NA	NA	NA	
AS-4	NA	NA	NA	NA	NA	
AS-5	NA NA	NA	NA	NA	NA	
<i>1</i> 10-2	1 171	, 17 (	11/1	1471	1121	

# Table 6 Air-Sparge System Operation and Performance Data

Facility Number: 2169 Air-Sparge Unit:\* Location: 889 West Grand Avenue 3-horsepower Conde blower Oakland, California 5-horsepower air compressor Consultant: EMCON Start-Up Date: 07-15-94 1921 Ringwood Avenue Operation and Performance Data From: 07-15-94 San Jose, California To: 04-01-97 System was shut down on 1-15-97. 01-01-97 02-01-97 03-01-97 Date Begin: Date End: 02-01-97 03-01-97 04-01-97 Days of Operation: 9 0 0 Days of Downtime: 22 28 31 Air-Sparge Well Status: AS-I closed closed open AS-2 closed closed open AS-3 closed closed open closed closed AS-4 open closed closed AS-5 open Air-Sparge Well Pressure (psig) (1): 0.0 0.0 AS-1 NA AS-2 NA 0.0 0.0 AS-3 NA 0.0 0.0 AS-4 NA 0.0 0.0 AS-5 NA 0.0 0.0 10.0 0.0 0.0 Total Air-Sparge Flow Rate (scfm) (2): 0 Total Air-Sparge Pressure (psig): 60 0 Dissolved Oxygen (mg/L) (3): Air-Sparge Wells: AS-I NA NA NA AS-2 NA NA NA AS-3 NA NA NA NA NA AS-4 NA NA NA AS-5 NA Depth to Water (ft-BGS) (5): Air-Sparge Wells: AS-I NA NA NA AS-2 NA NA NA AS-3 NA NA NA AS-4 NA NA NA AS-5 NA NA NA

# Table 6 Air-Sparge System Operation and Performance Data

Facility Number 2169

Air-Sparge Unit:\*

Location: 889 West Grand Avenue

3-horsepower Conde blower 5-horsepower air compressor

Consultant: EMCON

Start-Up Date: 07-15-94

1921 Ringwood Avenue

Oakland, California

Operation and Performance Data From: 07-15-94

San Jose, California

To: 04-01-97

System was shut down on 1-15-97

04-01-97

CURRENT REPORTING PERIOD:

01-01-97 to

DAYS / HOURS IN PERIOD: DAYS / HOURS OF OPERATION: DAYS / HOURS OF DOWN TIME: 90 2160.0 9 215.8

81 1944.2

PERCENT OPERATIONAL:

10.0%

<sup>1.</sup> psig, pounds per square inch gauge

<sup>2.</sup> scfm. standard cubic feet per minute at 14.7 psi and 70° F

<sup>3</sup> mg/L milligrams per liter

<sup>4</sup> NA; not available or not analyzed

<sup>5.</sup> ft-BGS, feet below grade surface

During the period from July 15, 1994 to July 25, 1995 the air-sparge system used a 3-horsepower Conde blower.
 On July 25, 1995, it was replaced with a 5-horsepower air compressor



Base map from USGS 7.5' Quad. Map: Oakland West, California. Photorevised 1980.

0 2000 4000 SCALE IN FEET





DATE APR. 1997	١
DWN KAJ	ŧ
APP	ı
REV	ı
PROJECT NO.	I
805-129.004	ł

### FIGURE 1

ARCO PRODUCTS COMPANY SERVICE STATION 2169, 889 W. GRAND AVE. SAN JOSE, CALIFORNIA


QUARTERLY GROUNDWATER MONITORING SITE LOCATION





ARCO Service Station 2169
Soil-Vapor Extraction and Treatment System
Historical System Influent TVHG and Benzene Concentrations

Figure 4




TVHG: total volatile hydrocarbons as gasoline ppmv: parts per million by volume

Figure 5

ARCO Service Station 2169

Soil-Vapor Extraction and Treatment System
Historical Hydrocarbon Removal Rates



esj/h:\2169\2169\ss.xls\SVE Model:imi 20805-129.004

### **APPENDIX A**

# ANALYTICAL RESULTS AND CHAIN OF CUSTODY DOCUMENTATION, FIRST QUARTER 1997 GROUNDWATER MONITORING EVENT



April 8, 1997 Service Request No.: <u>S9700556</u>

Mr. John Young **EMCON** 1921 Ringwood Avenue San Jose, CA 95131

RE: 2169 OAKLAND/20805-129.004/TO#19350.00

Dear Mr. Young:

The following pages contain analytical results for sample(s) received by the laboratory on March 26, 1997. Results of sample analyses are followed by Appendix A which contains sample custody documentation and quality assurance deliverables requested for this project. The work requested has been assigned the Service Request No. listed above. To help expedite our service, please refer to this number when contacting the laboratory.

Analytical results were produced by procedures consistent with Columbia Analytical Services' (CAS) Quality Assurance Manual (with any deviations noted). Signature of this CAS Analytica Report below confirms that pages 2 through 10, following, have been thoroughly reviewed and approved for release in accord with CAS Standard Operating Procedure ADM-DatRev3.

Please feel welcome to contact me should you have questions or further needs.

Sincerely.

Steven L. Green **Project Chemist** 

Acronyms

A2LA American Association for Laboratory Accreditation

ASTM American Society for Testing and Materials

**BOD** Biochemical Oxygen Demand

BTEX Benzene, Toluene, Ethylbenzene, Xylenes

CAM California Assessment Metals
CARB California Air Resources Board

CAS Number Chemical Abstract Service registry Number

CFC Chlorofluorocarbon
CFU Colony-Forming Unit
COD Chemical Oxygen Demand

DEC Department of Environmental Conservation
DEQ Department of Environmental Quality
DHS Department of Health Services
DLCS Duplicate Laboratory Control Sample

DMS Duplicate Matrix Spike
DOE Department of Ecology
DOH Department of Health

EPA U. S. Environmental Protection Agency

ELAP Environmental Laboratory Accreditation Program

GC Gas Chromatography

GC/MS Gas Chromatography/Mass Spectrometry

IC Ion Chromatography

ICB Initial Calibration Blank sample

ICP Inductively Coupled Plasma atomic emission spectrometry

ICV Initial Calibration Verification sample

J Estimated concentration. The value is less than the MRL, but greater than or equal to

the MDL. If the value is equal to the MRL, the result is actually <MRL before rounding.

LCS Laboratory Control Sample LUFT Leaking Underground Fuel Tank

M Modified

MBAS Methylene Blue Active Substances

MCL Maximum Contaminant Level. The highest permissible concentration of a

substance allowed in drinking water as established by the U. S. EPA.

MDL Method Detection Limit
MPN Most Probable Number
MRL Method Reporting Limit

MS Matrix Spike

MTBE Methyl tert-Butyl Ether

NA Not Applicable
NAN Not Analyzed
NC Not Calculated

NCASI National Council of the paper industry for Air and Stream Improvement
ND Not Detected at or above the method reporting/detection limit (MRL/MDL)

NIOSH National Institute for Occupational Safety and Health

NTU Nephelometric Turbidity Units

ppb Parts Per Billion ppm Parts Per Million

PQL Practical Quantitation Limit
QA/QC Quality Assurance/Quality Control
RCRA Resource Conservation and Recovery Act

RPD Relative Percent Difference SIM Selected Ion Monitoring

SM Standard Methods for the Examination of Water and Wastewater, 18th Ed., 1992

STLC Solubility Threshold Limit Concentration

SW Test Methods for Evaluating Solid Waste, Physical/Chemical Methods, SW-846,

3rd Ed., 1986 and as amended by Updates I, II, IIA, and IIB.

TCLP Toxicity Characteristic Leaching Procedure

TDS Total Dissolved Solids
TPH Total Petroleum Hydrocarbons

tr Trace level. The concentration of an analyte that is less than the PQL but greater than or equal

to the MDL. If the value is equal to the PQL, the result is actually <PQL before rounding.

TRPH Total Recoverable Petroleum Hydrocarbons

TSS Total Suspended Solids

TTLC Total Threshold Limit Concentration

VOA Volatile Organic Analyte(s) ACRONLST.DOC 7/14/95

#### **Analytical Report**

Client: ARCO Products Company

**Project:** 2169 OAKLAND/20805-129.004/TO#19350.00

Sample Matrix: Water

Service Request: S9700556

Date Collected: 3/26/97

Date Received: 3/26/97

Date Extracted: NA

BTEX, MTBE and TPH as Gasoline EPA Methods 5030/8020/California DHS LUFT Method Units: ug/L (ppb)

	Sample Name: Lab Code: Date Analyzed:	A-1 (11) S9700556-001 4/7/97	<b>A-2 (12)</b> S9700556-002 4/5/97	<b>A-3 (12)</b> \$9700556-003 4/5/97
Analyte	MRL			
TPH as Gasoline	50	ND	ND	ND
Benzene	0.5	0.8	ND	ND
Toluene	0,5	ND	ND	ND
Ethylbenzene	0.5	ND	ND	ND
Total Xylenes	0.5	ND	ND	ND
Methyl tert -Butyl Ether	3	64	<20 M1	ND

The MRL was elevated because of matrix interferences.

MI

#### **Analytical Report**

Client: **ARCO Products Company** 

Project: 2169 OAKLAND/20805-129.004/TO#19350.00

Sample Matrix: Water

Service Request: S9700556 Date Collected: 3/26/97 Date Received: 3/26/97

Date Extracted: NA

#### BTEX, MTBE and TPH as Gasoline EPA Methods 5030/8020/California DHS LUFT Method Units: ug/L (ppb)

	Sample Name: Lab Code: Date Analyzed:	A-4 (12) S9700556-004 4/5/97	<b>A-5 (10)</b> S9700556-005 4/5/97	<b>A-6 (10)</b> S9700556-006 4/5/97
Analyte	MRL			
TPH as Gasoline	50	ND	3100	110
Benzene	0.5	ND	190	ND
Toluene	0.5	ND	140	0.8
Ethylbenzene	0.5	ND	130	1.0
Total Xylenes	0.5	ND	340	1.4
Methyl tert -Butyl Ether	3	ND	<30 C1	15

The MRL was elevated due to high analyte concentration requiring sample dilution.

C1

#### **Analytical Report**

Client: ARCO Products Company

**Project:** 2169 OAKLAND/20805-129.004/TO#19350.00

Sample Matrix: Water

Service Request: S9700556

Date Collected: 3/26/97

Date Received: 3/26/97

Date Extracted: NA

#### BTEX, MTBE and TPH as Gasoline EPA Methods 5030/8020/California DHS LUFT Method Units: ug/L (ppb)

	Sample Name: Lab Code: Date Analyzed:	ADR-1 (11) S9700556-007 4/5/97	<b>ADR-2 (12)</b> S9700556-008 4/7/97	AR-1 (12) S9700556-009 4/5/97
Analyte	MRL			
TPH as Gasoline	50	1300	6100	ND
Benzene	0.5	260	320	ND
Toluene	0.5	6	23	ND
Ethylbenzene	0.5	39	180	ND
Total Xylenes	0.5	27	400	ND
Methyl tert -Butyl Ether	3	95	32	ND

#### Analytical Report

Client: ARCO Products Company

Project: 2169 OAKLAND/20805-129.004/TO#19350.00

Sample Matrix: Water

Service Request: S9700556

Date Collected: 3/26/97

Date Received: 3/26/97

Date Extracted: NA

BTEX, MTBE and TPH as Gasoline EPA Methods 5030/8020/California DHS LUFT Method Units: ug/L (ppb)

	Sample Name: Lab Code: Date Analyzed:	<b>AR-2 (12)</b> S9700556-010 4/5/97	Method Blank S970405-WB2 4/5/97	Method Blank S970407-WB2 4/7/97
Analyte	MRL			
TPH as Gasoline	50	ND	ND	ND
Benzene	0.5	ND	ND	ND
Toluene	0,5	ND	ND	ND
Ethylbenzene	0.5	ND	ND	ND
Total Xylenes	0.5	ND	ND	ND
Methyl tert-Butyl Ether	3	9	ND	ND

### APPENDIX A

.

#### QA/QC Report

Client: ARCO Products Company

**Project:** 2169 OAKLAND/20805-129.004/TO#19350.00

Sample Matrix: Water

Service Request: S9700556

Date Collected: 3/26/97

Date Received: 3/26/97

Date Extracted: NA

Date Analyzed: NA

## Surrogate Recovery Summary BTEX, MTBE and TPH as Gasoline EPA Methods 5030/8020/California DHS LUFT Method

Sample Name	Lab Code	PID Detector Percent Recovery 4-Bromofluorobenzene	FID Detector Percent Recovery $\alpha,\alpha,\alpha$ —Trifluorotoluene
A-1 (11)	S9700556-001	92	99
A-2 (12)	S9700556-002	94	95
A-3 (12)	S9700556-003	96	95
A-4 (12)	S9700556-004	95	98
A-5 (10)	S9700556-005	98	102
A-6 (10)	\$9700556-006	101	101
ADR-1 (11)	S9700556-007	92	101
ADR-2 (12)	S9700556-008	102	106
AR-1 (12)	S9700556-009	93	98
AR-2 (12)	S9700556-010	97	92
ADR-1 (11) (MS)	S9700556-007MS	94	115
ADR-1 (11) (DMS)	S9700556-007DMS	97	111
Method Blank	S970405-WB2	90	101
Method Blank	S970407-WB2	92	96

CAS Acceptance Limits: 69-116 69-116

QA/QC Report

Client: ARCO Products Company

Project: 2169 OAKLAND/20805-129.004/TO#19350.00

Sample Matrix: Water

Service Request: S9700556

Date Collected: 3/26/97

Date Received: 3/26/97

Date Extracted: NA

Date Analyzed: 4/5/97

Matrix Spike/Duplicate Matrix Spike Summary

TPH as Gasoline

EPA Methods 5030/California DHS LUFT Method

Units: ug/L (ppb)

Sample Name: ADR-1 (11)

Lab Code: \$970556-007MS, DMS

-						Perc	CAS Relative Acceptance Percent S DMS Limits Difference		
	Spike	Level	Sample	Spike	Result			Acceptance	Percent
Analyte	MS	DMS	Result	MS	DMS	MS	DMS	Limits	Difference
Gasoline	2500	2500	1300	4100	4000	112	108	67-121	2

QA/QC Report

Client: ARCO Products Company

Project: 2169 OAKLAND/20805-129.004/TO#19350.00

Service Request: \$9700556 Date Analyzed: 4/5/97

Initial Calibration Verification (ICV) Summary
BTEX, MTBE and TPH as Gasoline
EPA Methods 5030/8020/California DHS LUFT Method
Units: ppb

				CAS
				Percent
				Recovery
	True		Percent	Acceptance
Analyte	Value	Result	Recovery	Limits
Benzene	25	25	100	85-115
Toluene	25	25	100	85-115
Ethylbenzene	25	24	96	85-115
Xylenes, Total	75	73	97	85-115
Gasoline	250	270	108	90-110
Methyl tert -Butyl Ether	25	23	92	85-115

ARCO I	Produ Division	ICTS	Comp	Company	<b>\$</b>			Task O	rder No.	10	93	50	), c	O								Chain of Custody
ARCO Facilit	y no.	16	9	Cit	y ocility)	Oak	Leve			Project (Consu	manag Itant)	oer J	Oh	<b>√</b>	γ	10 V	4G					Laboratory name
ARCO engin	er Pa	l	5	000	10		Telephoi (ABCO)	ne no.		Telepha (Consu	one no	408)	45	3-7	300	Fax (Co	( no.	nt)	_			
ARCO engin	ame E	m	con	1			TATIOO	Address (Consulta	16	721		R.	1016	WOS	200	70	-vE	· 				Contract number -
				Matrix		Prese	rvation				20 SE	<b>₽</b>		띯	<b>'</b>			Semi VOA⊟	0010/7000			Method of shipment
Sample I.D.	Lab no.	Container no.	Soil	Water	Other	Ice	Acid	Sampling date	Sampling time	BTEX 602/EPA 8020	BTEXTPH "** EPA M602/8020/8015	TPH Modified 8015 Gas Diesel	Dil and Grease 113.1 ☐ 413.2	TPH EPA 418.1/SM503E	EPA 601/8010	EPA 624/8240	EPA 625/8270	TCLP Semi Metals □ VOA □ VOA	AM Metals EPA 6	Lead Org./DHS ☐ Lead EPA 7420/7421 ☐		Sampler Will Deliver
A-1(")		2		X		X	X	3-26-91	<del> </del>		7	1										Special detection Limit/reporting
A-2(12)	2	1				1			0838		1											LOWEST
A342)	3								0852													Limit
A462	4								0840	<u> </u>			ļ									Special QA/QC
A-5(10)	5					_			0935	<u> </u>			<u> </u>			 					_	AS Normal
A-6(10)	6			$\prod$				<del>                                     </del>	0922	_	<u> </u>	ļ <u>-</u>						-				
MOR-1(11				<u> </u>				<u> </u>	1000		<u> </u>	1										Remarks
ADR 2/12	8 (								0950	ļ												
AR-1(12 AR-2(12	9	17					11.		0910	<u> </u>	1								! 	-		20-40n(Nil)
AR-2(12	10	$\sqrt{V}$		W		Ψ_	1	V	090	-	7											
 						_				-		<u> </u>			-		\ 				_	Lab# 39100550
							-			╁											+	<del>3</del> 59100550
							<u> </u>			-												Lab number of # 20805-129,009
								<del>                                     </del>		<del>                                     </del>	<u></u>	<u> </u>										Turnaround time
				-		_	<del> </del>												_			Priority Rush  1 Business Day
Condition of	sample:		1	ok			<u> </u>			Temp	erature	receive	ed:	Co	of		_		<b>L</b>			1 Business Day
Relipquitne	by sam	oler					Date 3-26	-97	Time /500	Recei	ys by	٠	0	3	// ~			2				2 Business Days
Relinquished	by		· · ·				Date		Time	Recei	ved by	7										Expedited 5 Business Days
Relinquished	by						Date		Time	Recei	ved by	laborat	Bry K			ع ا	3/2	6/9	2	Time	50	Standard 10 Business Days
Distribution: \ APPC-3292 (2		y — Lai	boratory;	Canary	copy — A	RCO Envi	ronmental	Engineering;	Pink copy —	Consu	tænt											R8

# APPENDIX B SVE SYSTEM MONITORING DATA LOG SHEETS

#### ARCO 2169 SVE SYSTEM MONITORING DATA

eporting Period 01/01/97 00 00 02/01/97 00 00					n Period: n Period	744.00 31.00		Operation + Dow Operation + Dov	n Hours 744 00 vn Days 31 00													
[		F	eki Mont	toring Da	ita.	· · · · · · · · · · · · · · · · · · ·	]				Laboratory Monito						]					
ſ	Flow F	lates	FID	r PID R	sults			Well Fiel	d Influent	System	Influent	System	Effluent				]					
Reading Date & Time	Well Field Flow Rate	System Influent Flow Rate	Well Fletd	System Influent	System Effluent	Destruction Efficiency	Laboratory Sample Time	Gasoline	Benz <i>e</i> ne	Gasoline	Benzene	Gasoline	Benzene	Destruction Efficiency	Gasoline Emission Rate	Banzene Emission Rate	Period Hours	Meter Hours	Hours of Operation	Days of Operation	Down Hours	Down Days
	scfm	scim	ppm	ppm	ppm	%		ppmv mg/m3	ppmv mg/m3	ppmv mg/m3	ppmv mg/m3	ppmv mg/m3	ppmv mg/m3	%	lb/day	lb/day						
01/01/97 00 00 01/06/97 11 05 01/15/97 10 35 02/01/97 00 00	148 8 148 8 0 0	148 B 148 B 0 O															131 08 215 50 397 42	6089,28 6089 28 6305 02 6305 02	0 00 215 74 0 00	0 00 8 99 0 00	131.08 -0 24 397 42	5 -0 16
Period Totals												· <del>-</del>					744 00		215 74	8 99	528 26	22

02/01/97 00 00 03/01/97 00 00					n Period n Period	_		Operation + Dow	n Hours 672 00 vn Days 28 00													
				toring Da			]				Laboratory Monito				·		)					
	Flow F	lates	FID :	or PID R	sults			Well Fiel	d Influent	System	Influent	System	- Effluent				]					
Reading Date & Time	Well Field Flow Rate	System Influent Flow Rate	Well Field	System Influent	System Effluent	Destruction Efficiency	Laboratory Sample Time	Gasoline	Benzene	Gasoline	Benzene	Gasoline	Benzene	Destruction Efficiency	Gasoline Emission Rate	Benzene Emission Rate	Period Hours	Meter Hours	Hours of Operation	Days of Operation	Down Hours	,
	scfm	scfm	ppm	ppm	ppm	%		ppmv mg/m3	ppmv mg/m3	ppmv mg/m3	ppmv mg/m3	ppmv mg/m3	ppmv mg/m3	%	lb/day	lb/day						_
02/01/97 00 00 02/04/97 11 30 03/01/97 00 00	00	00															83 50 588 50	6305 02 6305 02 6305 02	0.00	0 00	83 50 588 50	
Penod Totals																	672 00		0 00	0 00	672 00	