

1921 Ringwood Avenue • San Jose, California 95 31-1721 • (408) 453-7300 • Fax (408) 437-9526

PROTECTION

97 500 00 81 0: 19

Date <u>September 30, 1997</u>
Project <u>20805-129.004</u>

To:

Ms. Susan Hugo Alameda County Health Care Services Agency Department of Environmental Health 1131 Harborbay Parkway, Suite 250 Alameda, California 94502-6577

We are enclosing:

Copies		Description			
11		Second quarte	r 1997 groundv	vater monito	ring results and
		remediation sy	stem performa	nce evaluati	on report,
		ARCO Service	e Station 2169,	Oakland, Ca	alifornia
For your:	<u>X</u>	Use	Sent by:	X	Regular Mail
		A 1			0. 1 1 4.
_		Approval			Standard Air
•		Approval Review			Standard Air Courier

Comments:

The enclosed groundwater monitoring and performance evaluation report is being sent to you per the request of ARCO Products Company. Please call if you have questions or comments.

Gary/P/ Messerotes Project Manager

cc: Kevin Graves, RWQCB - SFBR
Paul Supple - ARCO Products Company
File



Date: September 30, 1997

Re: ARCO Station #

2169 • 889 West Grand Avenue • Oakland, CA Second Quarter 1997 Groundwater Monitoring Results and Remediation System Performance Evaluation Report

"I declare, that to the best of my knowledge at the present time, that the information and/or recommendations contained in the attached proposal or report are true and correct."

Submitted by:

Paul Supple

Environmental Engineer



August 29, 1997 Project 20805-129.004

Mr. Paul Supple ARCO Products Company P.O. Box 6549 Moraga, California 94570

Re: Second quarter 1997 groundwater monitoring program results and remediation system performance evaluation report, ARCO service station 2169, Oakland,

California

Dear Mr. Supple:

This letter presents the results of the second quarter 1997 groundwater monitoring program at ARCO Products Company (ARCO) service station 2169, 889 West Grand Avenue, Oakland, California (Figure 1). Operation and performance data for the interim soil-vapor extraction (SVE) and air-sparge (AS) remediation systems at the site are also presented. The quarterly monitoring program complies with Alameda County Health Care Services Agency (ACHCSA) requirements regarding underground tank investigations. Pertinent site features, including the locations of existing on-site monitoring and vapor extraction wells are shown in Figure 2.

LIMITATIONS

No monitoring event is thorough enough to describe all geologic and hydrogeologic conditions of interest at a given site. If conditions have not been identified during the monitoring event, results should not be construed as a guarantee of the absence of such conditions at the site, but rather as the product of the scope, and limitations, of work performed during the monitoring event.

Please call if you have questions.

Sincerely,

EMCON

Gowri Kowtha

Staff Engineer

Project Manager

EMCON

5650

ARCO QUARTERLY REPORT

Station No.:	2169	Address:	889 West Grand Avenue, Oakland, California	
EMCON Proje	ct No.		20805-129.004	
ARCO Environ	mental Engineer	/Phone No.:	Paul Supple /(510) 299-8891	_
EMCON Project	ct Manager/Phor	ne No.:	Gary P. Messerotes /(408) 453-7300	
Primary Agenc	y/Regulatory ID	No.:	ACHCSA /Susan Hugo	_
Reporting Perio	od:		April 1, 1997 to July 1, 1997	

WORK PERFORMED THIS QUARTER (Second- 1997):

- 1. Prepared and submitted quarterly report for first quarter 1997.
- 2. Conducted quarterly groundwater monitoring and sampling for second quarter 1997.
- 3. Stimulated natural biodegradation in groundwater monitoring well A-5 with oxygen releasing compounds (ORCs).
- 4. Operated air-sparge system.

WORK PROPOSED FOR NEXT QUARTER (Third-1997):

- 1. Prepare and submit quarterly report for second quarter 1997.
- 2. Perform quarterly groundwater monitoring and sampling for third quarter 1997.
- 3. Continue operating air-sparge system and restart soil-vapor extraction (SVE) system if influent hydrocarbon concentrations and groundwater levels warrant.
- 4. Continue to monitor dissolved oxygen in groundwater monitoring well A-5.

QUARTERLY MONITORING:

Current Phase of Project:	Quarterly Groundwater Monitoring and Operation and Maintenance of Remediation Systems
	The SVE system was shut down on January 15, 1997, because of blower failure.
Frequency of Sampling:	Quarterly (groundwater), Monthly (SVE)
Frequency of Monitoring:	Quarterly (groundwater), Monthly (SVE and Air-Sparge)
Is Floating Product (FP) Present On-site	Yes No
Cumulative FP Recovered to Date:	4.8 gallons, Wells ADR-1 and ADR-2
FP Recovered This Quarter:	None
Bulk Soil Removed to Date :	2,196 cubic yards of TPH-impacted soil
Bulk Soil Removed This Quarter:	None
Water Wells or Surface Waters	
within 2000 ft., impacted by site:	None
Current Remediation Techniques:	SVE and Air-Sparge Systems
Average Depth to Groundwater:	11.51feet
Groundwater Gradient (Average):	0.002 ft/ft toward north-northwest (consistent with past)
SVE QUARTERLY OPERATION	ON AND PERFORMANCE:
Equipment Inventory:	Therm Tech Model VAC-25, 250 cfm, Thermal/Catalytic Oxidizer
Operating Mode:	Catalytic Oxidation
BAAQMD Permit #:	12119
	EMCON

TPH Conc. End of Period (lab):	NA (Not Available)
Benzene Conc. End of Period (lab):	NA
Flowrate End of Period:	NA
HC Destroyed This Period:	0.0 pounds
HC Destroyed to Date:	7830.3 pounds
Utility Usage	
Electric (KWH):	2197 KWH
Gas (Therms):	2 Thems
Operating Hours This Period:	0.0 hours
Percent Operational:	0.0% System was down for quarterly monitoring and other maintenance
	issues. See discussion.
Operating Hours to Date:	5850.6 hours
Unit Maintenance:	Routine monthly maintenance.
Number of Auto Shut Downs:	0
Destruction Efficiency Permit	
Requirement:	90%
Percent TPH Conversion:	NA
Stack Temperature:	NA
Source Flow:	NA
Process Flow:	NA
Source Vacuum:	NA

DISCUSSION:

The system was shut down 1-15-97. The soil-vapor extraction (SVE) system was not operational during second quarter 1997. The SVE system remained shut down because of low influent concentrations and rising water levels which resulted in the submergence of the hydrocarbon-impacted zone of soil and screen in the SVE wells. The SVE system may be restarted during the third or fourth quarter, if hydrocarbon concentrations and groundwater levels warrant.

ATTACHED:

- Table 1 Groundwater Monitoring Data, Second Quarter 1997
- Table 2 Historical Groundwater Elevation and Analytical Data, Petroleum Hydrocarbons and Their Constituents
- Table 3 Approximate Cumulative Floating Product Recovery Data
- Table 4 Soil Vapor Extraction System Operation and Performance Data
- Table 5 Soil-Vapor Extraction Well Data
- Table 6 Air-Sparge System Operation and Performance Data
- Figure 1 Site Location
- Figure 2 Site Plan
- Figure 3 Groundwater Data, Second Quarter 1997
- Figure 4 Historical SVE System Influent TVHG and Benzene Concentrations
- Figure 5 Historical SVE System Hydrocarbon Removal Rates
- Appendix A Analytical Results and Chain of Custody Documentation, Second Quarter 1997
 Groundwater Monitoring Event
- Appendix B SVE System Monitoring Data Log Sheets

cc: Susan Hugo, ACHCSA Kevin Graves, RWQCB-SFBR

EMCON

Table 1 Groundwater Monitoring Data Second Quarter 1997

Date: 08-27-97

Well Designation	Water Level Field Date	Top of Casing Solution To Elevation	as Depth to Water	TS Groundwater	Floating Product	S Groundwater S Flow Direction	Hydraulic B Gradient	Water Sample Field Date	TPHG	Benzene Benzene BPA 8020	Toluene Toluene Toluene Toluene	Ethylbenzene	Total Xylenes	MTBE P EPA 8020	MTBE	TPHD
1-A	05-21-97	14,16	11.10	3 06	ND	NNW	0.002	05-21-97	Not sampled	l: well samp	oled semi-a	nnually, du	ring the firs	st and third	quarters	
A-2	05-21-97	14 55	11.58	2.97	ND	NNW	0 002		Not sampled				_		-	
A-3	05-21-97	15,75	12 35	3.40	ND	NNW	0 002	05-21-97	Not sampled	l· well samp	pled annual	ly, during tl	he first qua	rter	•	
A-4	05-21-97	15.25	1151	3 74	ND	NNW	0.002	05-21-97	Not sampled	l: well samp	oled annual	ly, during th	he first qua	rter		
A-5	05-21-97	13 51	10.25	3 26	ND	NNW	0 002	05-21-97	16000	1500	900	700	2700	<120^		
A-6	05-21-97	13 51	10.54	2.97	ND	NNW	0.002	05-21-97	600	06	0.6	<2^	27	<3		
AR-I	05-21-97	15 61	12 02	3.59	ND	NNW	0.002	05-21-97	Not sampled	l well samp	pled semi-a	nnually, du	ring the fire	st and third	quarters	
AR-2	05-21-97	15 28	12 12	3 16	ND	NNW	0.002	05-21-97	Not sampled	l: well samp	pled semi-a	nnually, du	ring the fir	st and third	quarters	
ADR-1	05-21-97	13.95	10 90	3 05	ND	NNW	0 002	05-21-97	2100	300	18	37	200	79		
ADR-2	05-21-97	14 64	11.64	3.00	ND	NNW	0 002	05-21-97	6100	380	22	210	320	<30^		

MWN ground-water flow direction and gradient apply to the entire monitoring well network

ft/ft' foot per foot

TPHG: total petroleum hydrocarbons as gasoline, California DHS LUFT Method

μg/L: micrograms per liter

EPA United Statest Environmental Protection Agency

MTBE. Methyl tert-butyl ether

TPHD: total petroleum hydrocarbons as diesel, California DHS LUFT Method

NR, not reported, data not available or not measurable

ND none detected

NNW northwest

ft-MSL: elevation in feet, relative to mean sea level

[^] method reporting limit was raised due to (1) high analyte concentration requiring sample dilution, or (2) matrix interference

^{-- &#}x27; not analyzed

Table 2
Historical Groundwater Elevation and Analytical Data
Petroleum Hydrocarbons and Their Constituents
1995 - Present***

Date, 08-27-97

Well Designation	Water Level Field Date	Top of Casing S Elevation	ಣ್ಣ Depth to Water	Groundwater	Floating Product	M Groundwater M Flow Direction	Hydraulic ty Gradient	Water Sample Field Date	TPHG	Benzene	Toluene	Ethylbenzene E EPA 8020	Total Xylencs	MTBE	MTBE EPA 8240	TPHD
A-1	03-24-95	14 16	8.10	6 06	ND	NW	0.009	03-24-95	1200	230	39	34	66			160^^^
A-1	06-05-95	14 16	11 13	3 03	ND	NW	0.002	06-05-95	1500	310	27	36	76			710^
A-1	08-17-95	14.16	11 71	2.45	ND	w	0 001	08-18-95	1600	470	35	48	110	120		240^
A-1	12-04-95	14.16	12.28	1.88	ND	NNW	0 002	12-04-95	1200	240	17	25	56		120	
A-1	03-01-96	14.16	8 78	5 38	ND	NW	0.003	03-13-96	1300	300	74	29	73	100		
A-1	05-29-96	14 16	9.85	4 31	ND	NW	0.002	05-29-96	Not sampled	. well samp	oled semi-a	nnually, du	ring the firs	st and third	quarters	
A-1	08-29-96	14 16	80.13	3.08	ND	w	0 002	08-29-96	1200	320	59	25	27	110		
A-1	11-21-96	14.16	10.54	3.62	ND	WNW	0 002	11-21-96	Not sampled	well samp	oled semi-a	nnually, du	ring the firs	st and third	quarters	
A-1	03-26-97	14 16	10.55	3 61	ND	NW	0.002	03-26-97	<50	0.8	<0.5	<0.5	<0.5	64		
A-1	05-21-97	14.16	11 10	3 06	ND	NNW	0.002	05-21-97	Not sampled	. well samį	oled semi-a	nnually, du	ring the firs	st and third	quarters	
A-2	03-24-95	14 55	8.64	5 91	ND	NW	0 009	03-24-95	<50	<0.5	<0.5	<0.5	<0.5			
A-2	06-05-95	14 55	1172	2 83	ND	NW	0.002	06-05-95	<50	<0.5	<0.5	<0.5	<0.5			
A-2	08-17-95	14 55	12 35	2 20	ND	W	0.001	08-17-95	<50	<0.5	<0.5	<0.5	<0.5	12		^ -
A-2	12-04-95	14.55	12 74	1.81	ND	NNW	0 002	12-04-95	<50	<0.5	<0.5	<0.5	<0.5			
A-2	03-01-96	14 55	9.34	5 21	ND	NW	0 003	03-13-96	<50	<0.5	06	<0.5	1.3	<9		
A-2	05-29-96	14 55	10 40	4.15	ND	NW	0.002	05-29-96	<50	<0.5	<0.5	<0.5	<0.5	<20		
A-2	08-29-96	14.55	11.50	3.05	ND	W	0.002	08-29-96	<50	<0.5	<0.5	<0.5	<0.5	<39^		
A-2	11-21-96	14 55	11.06	3 49	ND	WNW	0 002	11-21-96	<50	<0.5	<0.5	<0.5	<0.5	<30^		
A-2	03-26-97	14 55	11 12	3 43	ND	NW	0.002	03-26-97	<50	<0.5	<0.5	<0.5	<0.5	<20^		
A-2	05-21-97	14.55	11 58	2.97	ND	NNW	0.002	05-21-97	Not sampled	· well samp	iled semi-a	nnually, du	ring the firs	st and third	quarters	

Table 2
Historical Groundwater Elevation and Analytical Data
Petroleum Hydrocarbons and Their Constituents
1995 - Present***

Date: 08-27-97

	Well Designation	Water Level Field Date	Top of Casing Elevation	as Depth to Water	ut.y TSW-tsution	Floating Product	Groundwater Flow Direction	Hydraulic By Gradient	Water Sample Field Date	TPHG	Benzene Ge EPA 8020	Toluene	Ethylbenzene	Total Xylenes	MTBE	TE MTBE	T TPHD
_	A-3	03-24-95	15.75	8.83	6 92	ND	NW	0.009	03-24-95	<50	<0.5	<0.5	<0.5	<0.5			
	A-3	06-05-95	15.75	12 44	3 31	ND	NW	0.002	06-05-95	Not sampled	well samp	led annuall	y, during t	he first qua	rter		
	A-3	08-17-95	15 75	13.04	2.71	ND	W	0.001	08-17-95	Not sampled	well samp	led annuali	ly, during t	he first qua	rter		
	A-3	12-04-95	15.75	13.57	2.18	ND	NNW	0 002	12-04-95	Not sampled:	well samp	led annuall	ly, during t	he first qua	rter		
	A-3	03-01-96	15.75	9.90	5 85	ND	NW	0.003	03-13-96	<50	<0.5	< 0.5	<0.5	< 0.5	<3		
	A-3	05-29-96	15.75	11 08	4 67	ND	NW	0 002	05-29-96	Not sampled.							
	A-3	08-29-96	15 75	12 38	3.37	ND	W	0 002	08-29-96	Not sampled:	well samp	led annuall	ly, during t	he first qua	rter		
	A-3	11-21-96	15.75	11.86	3 89	ND	WNW	0.002	11-21-96	Not sampled:		led annuall	ly, during t	he first qua	rter		
	A-3	03-26-97	15.75	1181	3 94	ND	NW	0.002	03-26-97	<50	< 0.5	<0.5	< 0.5	<0.5	<3		
	A-3	05-21-97	15 75	12.35	3.40	ND	NNW	0 002	05-21-97	Not sampled	well samp	led annuali	ly, during t	he first qua	rter		
	A-4	03-24-95	15 25	7 20	8.05	ND	NW	0.009	03-24-95	<50	< 0.5	<0.5	<0.5	< 0.5			
	A-4	06-05-95	15.25	11.70	3 55	ND	NW	0 002	06-05-95	Not sampled.	well samp	led annuall	ly, during t	he first qua	rter		
	A-4	08-17-95	15.25	12 28	2.97	ND	W	0.001	08-17-95	Not sampled,							
	A-4	12-04-95	15 25	12 63	2.62	ND	NNW	0.002	12-04-95	Not sampled	well samp	led annuall	ly, during t	he first qua	rter		
	A-4	03-01-96	15.25	8.55	6 70	ND	NW	0 003	03-13-96	<50	<0.5	< 0.5	< 0.5	<0.5	<3	~ =	
	A-4	05-29-96	15 25	10.32	4 93	ND	NW	0.002	05-29-96	Not sampled	well samp	led annuall	ly, during t	he first qua	rter		
	A-4	08-29-96	15 25	11 55	3.70	ND	W	0.002	08-29-96	Not sampled.	well samp	led annuali	ly, during t	he first qua	rter		
	A-4	11-21-96	15.25	10.83	4 42	ND	WNW	0 002	11-21-96	Not sampled	well samp	led annuall	y, during t	he first qua	rter		
	A-4	03-26-97	15.25	10 97	4.28	ND	NW	0.002	03-26-97	<50	<0.5	<0.5	< 0.5	<0.5	<3		
	A-4	05-21-97	15.25	11.51	3 74	ND	NNW	0 002	05-21-97	Not sampled:	well samp	led annuali	ly, during t	he first qua	rter		

Table 2
Historical Groundwater Elevation and Analytical Data
Petroleum Hydrocarbons and Their Constituents
1995 - Present***

Date. 08-27-97

Well Designation	Water Level Field Date	Top of Casing	as Depth to Water	TSW-13 Groundwater	Floating Product	S Groundwater Flow Direction	Hydraulic School Gradient	Water Sample Field Date	TPHG	EPA 8020	Toluene	Ethylbenzene	Total Kylenes	MTBE EPA 8020	MTBE F EPA 8240	TPHD S LUFT Method
A-5	03-24-95	13 51	7.40	6,11	ND	NW	0 009	03-24-95	3300	200	310	130	460			
A-5	06-05-95	13.51	10 43	3.08	ND	NW	0.002	06-05-95	57000	2700	4600	1500	6800			
A-5	08-17-95	13.51	11 15	2 36	ND	w	0.001	08-18-95	34000	1600	2700	1100	5100	<28		
A-5	12-04-95	13.51	11.42	2 09	ND	NNW	0.002	12-04-95	61	<0.5	<0.5	<0.5	<0.5			
A-5	03-01-96	13 51	8 1 1	5 40	ND	NW	0.003	03-13-96	11000	860	960	380	1600	<100		
A-5	05-29-96	13.51	9 30	4.21	ND	NW	0.002	05-29-96	19000	1600	1900	880	3300	<100		
A-5	08-29-96	13.51	10 60	2 91	ND	W	0 002	08-29-96	7700	490	450	260	990	<30^		
A-5	11-21-96	13 51	10.05	3 46	ND	WNW	0 002	11-21-96	8000	450	550	340	1100	<30^		
A-5	03-26-97	13 51	9,87	3 64	ND	NW	0.002	03-26-97	3100	190	140	130	340	<30^		
A-5	05-21-97	13.51	10 25	3 26	ND	NNW	0 002	05-21-97	16000	1500	900	700	2700	<120^	= +	
A-6	03-24-95	13.51	7 89	5 62	ND	NW	0.009	03-24-95	120	<0.5	< i	<0.5	<1.5			
A-6	06-05-95	13 51	10.06	3,45	ND	NW	0 002	06-05-95	160	<0.5	<0.6	<0.5	<0.5		- *	
A-6	08-17-95	13.51	11 10	2.41	ND	W	0 001	08-18-95	530	<0.5	<0.5	<2 4	<42	6		
A-6	12-04-95	13 51	11.52	1 99	ND	NNW	0 002	12-04-95	28000	1600	1800	880	3600			
A-6	03-01-96	13 51	8 21	5 30	ND	NW	0.003	03-13-96	1400	<3	<15	<7	<10	<20		
A-6	05-29-96	13.51	9 25	4.26	ND	NW	0 002	05-29-96	410	<2	<2	<2	<2	3		
A-6	08-29-96	13 51	10 52	2 99	ND	W	0 002	08-29-96	80	<0.5	<0.5	<0.5	<0.5	6		
A-6	11-21-96	13 51	10.54	2 97	ND	WNW	0.002	11-21-96	62	<0.5	<0.5	<0.5	<0.5	12		
A-6	03-26-97	13 51	9 93	3.58	ND	NW	0 002	03-26-97	110	<0.5	0.8	1	1.4	15	~ -	
A-6	05-21-97	13 51	10.54	2 97	ND	NNW	0 002	05-21-97	600	06	0.6	<2^	27	<3		

Table 2
Historical Groundwater Elevation and Analytical Data
Petroleum Hydrocarbons and Their Constituents
1995 - Present***

Date 08-27-97

Well Designation	Water Level Field Date	Top of Caving Selevation	na Depth to Water	Groundwater	Floating Product	Groundwater Flow Direction	Hydraulic	Water Sample Field Date	के TPHG 7 LUFT Method	Benzene P EPA 8020	Toluene	Ethylbenzene BPA 8020	Total Xylenes EPA 8020	म MTB E हैं EPA 8020	MTBE EPA 8240	TPHD LUFT Method
										μ ₆ , Ε	P6, 25	P6/12	рд/С	μg/L	рво	р <u>г</u> ус
AR-I	03-24-95	15.61	7.25	8.36	ND	NW	0.009	03-24-95	270	14	06	2.5	2 1			130^^^
AR-1	06-05-95	15.61	11.37	4 24	ND	NW	0.002	06-05-95	190	10	< 0.5	0.8	0.5			580^
AR-1	08-17-95	15 61	12 40	3 21	ND	W	0 001	08-17-95	960	110	12	4 5	150	14		<50
AR-1	12-04-95	15 61	12 90	2.71	ND	NNW	0.002	12-04-95	<50	1.5	< 0.5	< 0.5	0.8			
AR-1	03-01-96	15 61	8 19	7.42	ND	NW	0.003	03-13-96	150	3.8	0 5	1.4	13	<3		
AR-I	05-29-96	15.61	10.41	5.20	ND	NW	0.002	05-29-96	Not sampled	i well samp	oled semi-a	nnually, du	ring the firs	st and third	quarters	
AR-1	08-29-96	15.61	12 12	3.49	ND	W	0.002	08-29-96	<50	<0.5	< 0.5	<0.5	0.8	<3		
AR-1	11-21-96	15.61	11 52	4.09	ND	WNW	0 002	11-21-96	Not sampled	l well sam	oled semi-a	nnually, du	ring the firs	st and third	quarters	
AR-I	03-26-97	15 61	11.33	4 28	ND	NW	0 002	03-26-97	<50	< 0.5	<0.5	< 0.5	<0.5	<3		
AR-1	05-21-97	15.61	12.02	3 59	ND	MNW	0.002	05-21-97	Not sampled	l· well sam	oled semi-a	nnually, du	ring the firs	st and third	quarters	
AR-2	03-24-95	15 28	9 13	6.15	ND	NW	0 009	03-24-95	<50	6 2	< 0.5	<0.5	0.6			<50
AR-2	06-05-95	15 28	12.09	3 19	ND	NW	0 002	06-05-95	<50	< 0.5	< 0.5	<0.5	<0.5			<50
AR-2	08-17-95	15.28	12 78	2 50	ND	W	0.001	08-18-95	<50	<0.5	<0.5	< 0.5	<0.5	4		<50
AR-2	12-04-95	15 28	11 44	3.84	ND	NNW	0.002	12-13-95	<50	< 0.5	< 0.5	<0.5	< 0.5			
AR-2	03-01-96	15 28	9 83	5.45	ND	NW	0 003	03-13-96	190	26	26	3 3	13	200		
AR-2	05-29-96	15 28	10.97	4 31	ND	NW	0 002	05-29-96	Not sampled	i· weil samj	oled semi-a	nnually, du	ring the fire	st and third	quarters	
AR-2	08-29-96	15.28	12 20	3 08	ND	W	0.002	08-29-96	<50	<0.5	<0.5	<0.5	<0.5	95		
AR-2	11-21-96	15 28	11.57	3.71	ND	WNW	0 002	11-21-96	Not sampled	l: well sam	oled semi-a	nnually, du	ring the fire	st and third	quarters	
AR-2	03-26-97	15.28	11.60	3 68	ND	NW	0 002	03-26-97	<50	< 0.5	<0.5	< 0.5	<0.5	9		
AR-2	05-21-97	15.28	12 12	3.16	ND	NNW	0.002	05-21-97	Not sampled	l well sam	oled semi-a	nnually, du	ring the fir-	st and third	quarters	

Table 2
Historical Groundwater Elevation and Analytical Data
Petroleum Hydrocarbons and Their Constituents
1995 - Present***

Date. 08-27-97

Well Designation	Water Level Field Date	Top of Casing Sevation	39 Depth to Water	TS Groundwater	Floating Product	S Groundwater Flow Direction	Hydraulic S Gradient	Water Sample Field Date	TPHG C LUFT Method	Benzene F BPA 8020	Toluene	Ethylbenzene	ਨ Total Xylenes ਨੂੰ EPA 8020	MTBE FPA 8020	MTBE TEPA 8240	म TPHD वि LUFT Method
ADR-1	03-24-95	13.95	8 04	** 5.92	0.01	NW	0.009	03-24-95	Not sampled	l: wall sone	unad flansi					
ADR-I	05-24-95	13.95	11.02	2 93	ND	NW	0.009	06-05-95	23000	310	420	ng product	1900			*****
ADR-1	08-17-95	13.95	11.86	2 93	ND	W	0.001	08-18-95	4400	150	120	95	620	120		13000^ 4500^
ADR-1	12-04-95	13.95	10.05	3 90	ND	NNW	0.001	12-13-95	8800	100	130	120	990	-	*-	
ADR-1	03-01-96	13.95	8 76	5 19	ND	NW	0.002	03-13-96	89000	370	1000	840	8100	<500		
ADR-I	05-01-96	13.95	9.74	4.21	ND	NW	0 003	05-30-96	27000	230	380	370	2700	<100		••
ADR-1	08-29-96	13.95	10 77	3.18	ND	w	0.002	08-29-96	5300	190	58	76	470	85		
ADR-1	11-21-96	13.95	10 49	3.46	ND	WNW	0.002	11-21-96	1900	82	21	32	270	110		
ADR-1	03-26-97	13.95	10 37	3.58	ND	NW	0.002	03-26-97	1300	260	6	39	270	95	• • •	
ADR-1	05-20-97	13.95	10.90	3.05	ND	NNW	0.002	05-21-97	2100	300	18	37	200	79	• • • • • • • • • • • • • • • • • • • •	
ADR-2	03-24-95	14 64	8 41	NR*	>3.00*	NR*	NR*	03-24-95	Not sample	i: well conta	uned floati	ng product				
ADR-2	06-05-95	14.64	11 45	NR*	>3.00*	NR*	NR*	06-05-95	Not sampled	i well conti	ained floati	ng product				
ADR-2	08-17-95	14.64	12 10	** 2.56	0 03	W	0 001	08-17-95	Not sampled	i well conta	nined float	ng product				
ADR-2	12-04-95	14.64	10.93	** 3 73	0.03	NNW	0 002	12-13-95	Not sampled	i well conta	arned floati	ng product				
ADR-2	03-01-96	14 64	8.74	5 90	ND	NW	0.003	03-13-96	29000	1100	1200	710	3800	<500		
ADR-2	05-29-96	14 64	10 43	4 21	ND	NW	0.002	05-29-96	33000	510	500	470	2300	120		
ADR-2	08-29-96	14 64	11 64	3.00	ND	W	0 002	08-29-96	8000	230	180	150	730	53		
ADR-2	11-21-96	14.64	11 23	3.41	ND	WNW	0 002	11-21-96	15000	630	440	390	2100	75		
ADR-2	03-26-97	14.64	11.13	3.51	ND	NW	0 002	03-26-97	6100	320	23	180	400	32		
ADR-2	05-21-97	14 64	11 64	3 00	ND	NNW	0.002	05-21-97	6100	380	22	210	320	<30^		- -

Table 2
Historical Groundwater Elevation and Analytical Data
Petroleum Hydrocarbons and Their Constituents
1995 - Present***

Dat	٠.	08-	27.	97

Well Designation	Water Level Field Date	Top of Caming Elevation	Depth to Water	Groundwater Elevation	Floating Product Thickness	Groundwater Flow Direction	Hydraulic Gradient	Water Sample Field Date	TPHG LUFF Method	Benzene EPA 8020	Toluene EPA 8020	Ethylbenzenc EPA 8020	Total Xylenes EPA 8020	MTBE EPA 8020	MTBE EPA 8240	TPHD LUFT Method
		ft-MSL	feet	ft-MSL	feet	MWN	ft/ft		μg/L	μg/L	μg/L	µg/L	μg/L	μg/L	μg/L	μg/L

ft-MSL elevation in feet, relative to mean sea level

MWN: groundwater flow direction and gradient apply to the entire monitoring well network

ft/ft foot per foot

TPHG total petroleum hydrocarbons as gasoline, California DHS LUFT Method

µg/L: micrograms per liter

EPA United States Environmental Protection Agency

MTBE. Methyl tert-butyl ether

TPHD total petroleum hydrocarbons as diesel, California DHS LUFT Method

ND, none detected

NR: not reported, data not available or not measurable

NW northwest

WNW, west-northwest

W. west

NNW north-northwest

- ^. method reporting limit was raised due to (1) high analyte concentration requiring sample dilution, or (2) matrix interference
- ^^ sample contains a single non-fuel component eluting in the gasoline range, and quantified as gasoline
- ^^^ sample contains a muxture of diesel and a lower boiling point hydrocarbon quantitated as diesel; chromatogram does not match the typical diesel fingerprint
- ^^^. sample contains components eluting in the diesel range, quantified as diesel, chromatogram does not match the typical diesel fingerprint
- -: not analyzed or not applicable
- *. well contained more than 3 feet of floating product; exact product thickness and groundwater elevation could not be measured
- *** [corrected elevation (Z')] = Z + (h * 0.73) where Z = measured elevation, h = floating product thickness, 0.73 = density ratio of oil to water
- *** For previous historical groundwater elevation data please refer to Fourth Quarter 1995 Groundwater Monitoring Program Results and Remediation System Performance Evaluation Report, ARCO Service Station 2169, 889 West Grand Avenue, Oakland, California, (EMCON, March 4, 1996)

Table 3
Approximate Cumulative Floating Product Recovered

Date:	08-22-97
Date:	U0-22-97

Well Desig- nation	Date	Floating Product Recovered gallons
ADR-1 ADR-2	1994	0 0 0.0
ADR-1 ADR-2	1995	0.0 4 8
ADR-1 ADR-2	1996	0.0 0.0
ADR-1 ADR-2	1997	0.0 0.0
	1994 to 1997 Total:	4.8

Table 4 Soil-Vapor Extraction System Operation and Performance Data

Location: 889 West Grand Avenue

Oakland, California

Vapor Treatment Unit: ThermTech Model

VAC-25, 250cfm Thermal/

Catalytic Oxidizer

Consultant: EMCON

1921 Ringwood Avenue San Jose, California

Start-Up Date: 06-02-94 Operation and Performance Data From: 06-02-94

To: 07-01-97

		System was shut down on 1-15-97.					
Beginning Date:	06-02-94	06-02-94	06-07-94	06-16-94	06-22-94		
Ending Date:	06-02-94	06-07-94	06-16-94	06-22-94	06-30-94		
Down-time (days):	0	0	l	0	4		
Total Operation (days):	0	5	8	6	4		
Total Operation (hours):	1.7	121.3	193 7	145.2	106.3		
Operation Hours to Date:	1.7	123.0	316.7	462 0	568.2		
TPH Concentrations							
Average Influent (ppmv):	18,000	16,000	830	1,100	230		
Average Effluent (ppmv):	ND	45	ND	4.9	75.0		
Benzene Concentrations							
Average Influent (ppmv):	270	420	17	24	3.8		
Average Effluent (ppmv):	ND	0.30	ND	80.0	0.78		
Flow Rates							
Average Influent (scfm):	61.1	131 5	145.3	194 1	176.7		
Average Dilution (scfm):	184.2	97 8	69.9	0.0	0.0		
Average Effluent (scfm):	268.6	272.3	289.7	264.4	288.9		
TPH-G Recovery Data							
Recovery Rate (lbs/hr):	11 12	21.26	1.22	2,16	0.41		
Recovery Rate (lbs/day):	266.80	510.34	29.27	51,77	9.86		
Destruction Efficiency (%):	100.00	99.46	100.00	99.39	46.70		
Product Recovered (lbs):	18.68	2779 35	236.08	313.27	43.64		
Product Recovered to Date (lbs):	18.68	2798.02	2834.10	3147.37	3191.01		
Product Recovered to Date (gal):	3.11	433.00	472.35	524.56	531.83		
Benzene Recovery Data							
Recovery Rate (lbs/hr):	0.185	0.670	0.030	0.056	0.008		
Recovery Rate (lbs/day):	4.447	16.076	0.719	1 355	0.195		
Destruction Efficiency (%):	100.00	99.86	100.00	99.56	66.45		
Product Recovered (lbs):	0.311	81.249	5 802	8.202	0.865		
Product Recovered to Date (lbs):	0.311	81.561	87.363	95.565	96.430		
Product Recovered to Date (gal):	0.043	11.270	12.050	13.181	13.301		

Page 1 Footnotes

ppmy: parts per million by volume scfm, standard cubic feet per minute lbs/hr: pounds per operational hour lbs/day: pounds per day

lbs. pounds

gal gallons

ND None Detected, Recovery data calculated using laboratory detection limits

- 1. Molecular weights used in recovery calculations are 65 for TPH and 78 for benzene.
- 2 Densities used in recovery calculations are 6.0 lbs/gal for TPH and 7.27 lbs/gal for benzene.
- 3. All data and calculations on this page were prepared by GeoStrategies. Inc. (GSI), as presented in Letter Report, Vapor Extraction Start Up and Quarterly Groundwater Monitoring, Second Quarter 1994, (GSI, September 1994).

Table 4 Soil-Vapor Extraction System Operation and Performance Data

Location: 889 West Grand Avenue

Oakland, California

Vapor Treatment Unit: ThermTech Model

VAC-25, 250cfm Thermal/

Catalytic Oxidizer

Consultant: EMCON

1921 Ringwood Avenue San Jose California

Start-Up Date: 06-02-94 Operation and Performance Data From: 06-02-94

San Jose, California	To: 07-01- System was shut down on 1-15-97.							
Date Begin:	07-01-94	08-01-94	09-01-94	12-01-94	01-01-95			
Date End:	08-01-94	09-01-94	12-01-94	01-01-95	02-01-95			
Mode of Oxidation:	Therm-Ox	Cat-Ox	Cat-Ox	Cat-Ox	Cat-Ox			
Days of Operation:	11	17	35	16	26			
Days of Downtime.	20	14	56	15	5			
Average Vapor Concentrations (1)								
Well Field Influent: ppmv (2) as gasoline	1983	680	450	1500	<15			
mg/m3 (3) as gasoline	5333	1800	1200	5600	<60			
ppmv as benzene	29	7.6	2.9	7	< 0.1			
mg/m3 as benzene	95	25	9.4	22	<0.5			
System Influent: ppmv as gasoline	1983	680	450	400	<15			
mg/m3 as gasoline	5333	1800	1200	1600	<60			
ppmv as benzene	29	76	29	19	< 0 1			
mg/m3 as benzene	95	25	94	6	<0.5			
System Effluent: ppmv as gasoline	17	44	4 1	<15	<15			
mg/m3 as gasoline	46	118	11.1	<60	<60			
ppmv as benzene	0.15	07	0.04	< 0.1	< 0.1			
mg/m3 as benzene	0.49	2.3	0.143	<0.5	< 0.5			
Average Well Field Flow Rate (4), scfm (5).	198,3	212.6	214 3	17.7	16.7			
Average System Influent Flow Rate (4), scfm:	198.3	212.6	214.3	120.1	164.3			
Average Destruction Efficiency (6), percent (7):	99.1	93.4	99 1	96.3	NA			
Average Emission Rates (8), pounds per day (9)								
Gasoline:	0.82	2.25	0.21	0 65	0.89			
Benzene:	0.01	0.04	0 00	0.01	0.01			
Operating Hours This Period:	255.95	414,28	833.57	385.86	614.80			
Operating Hours To Date:	256.0	670.2	1503.8	1889.7	2504 5			
Pounds/ Hour Removal Rate, as gasoline (10):	3.96	1 43	0.96	0 37	0 00			
Pounds Removed This Period, as gasoline (11):	<u>1013.1</u>	<u>593.4</u>	802,3	<u>143.1</u>	2.3			
Pounds Removed To Date, as gasoline:	4204 1	4797.4	5599.7	5742.9	5745.2			
Gallons Removed This Period, as gasoline (12):	<u>163.4</u>	<u>95.7</u>	129.4	23.1	04			
Gallons Removed To Date, as gasoline:	678.1	773.8	903.2	926 3	926 7			

Table 4 Soil-Vapor Extraction System Operation and Performance Data

Location: 889 West Grand Avenue

Oakland, California

Vapor Treatment Unit. ThermTech Model

VAC-25, 250cfm Thermal/

Catalytic Oxidizer

Consultant: EMCON

1921 Ringwood Avenue

Start-Up Date: 06-02-94

Operation and Performance Data From: 06-02-94

	San Jose, California	To: 07-01-97 System was shut down on 1-15-97.							
Date Begin:		02-01-95	07-01-95	08-01-95	09-01-95	10-01-95			
Date End:		07-01-95	08-01-95	09-01-95	10-01-95	11-01-95			
Mode of Oxidation:		Cat-Ox	Cat-Ox	Cat-Ox	Cat-Ox	Cat-Ox			
Days of Operation.		0	14	19	27	12			
Days of Downtime-		150	17	12	3	19			
Average Vapor Concer	ıtrations (1)								
	. ppmv (2) as gasoline	NA (13)	1567	1975	1400	250			
	mg/m3 (3) as gasoline	NA	5767	7175	5200	900			
	ppmv as benzene	NA	12	10	3.1	0.6			
	mg/m3 as benzene	NA	40	33	10	1.7			
System Influent	: ppmv as gasoline	NA	200	270	230	66			
	mg/m3 as gasoline	NA	740	970	920	240			
	ppmv as benzene	NA	1.6	1	0.6	0.1			
	mg/m3 as benzene	NA	5.2	3.3	18	< 0.5			
System Effluent	. ppmv as gasotine	NA	23	<15	<15	<15			
,,	mg/m3 as gasoline	NA	83	<60	<60	<60			
	ppmv as benzene	NA	<0.1	<0.1	<0.1	<0.1			
	mg/m3 as benzene	NA	< 0.5	<0.5	< 0.5	<0.5			
Average Well Field Flow	v Rate (4), scfm (5):	0.0	27.9	43.0	58.1	67.0			
Average System Influent	t Flow Rate (4), scfm:	0.0	197.6	166.8	167.9	174.1			
Average Destruction Ef	ficiency (6), percent (7):	NA	88.8	93.8	93.5	75.0			
Average Emission Rate	s (8), pounds per day (9)								
Gasoline [,]		0.00	1 47	0.90	0.90	0.94			
Benzene:		0 00	0.01	10.0	0.01	0.01			
Operating Hours This Po	eriod:	0.00	346.17	462 40	652.27	278.16			
Operating Hours To Dat		2504.5	2850.6	3313.0	3965.3	4243 5			
Pounds/ Hour Removal	Rate, as gasoline (10).	0.00	0.60	1.15	1.13	0.23			
Pounds Removed This P	Period, as gasoline (11):	0.0	<u> 208 5</u>	533.9	737.6	<u>62.8</u>			
Pounds Removed To Da	ite, as gasoline:	5745 2	5953 6	6487 6	7225 1	7287.9			
Gallons Removed This I		0.0	<u>33.6</u>	<u>86 1</u>	119.0	<u> 10.1</u>			
Gallons Removed To Da		926.7	960 3	1046 4	1165 4	1175 5			

Table 4 Soil-Vapor Extraction System Operation and Performance Data

Location: 889 West Grand Avenue

Oakland, California

Vapor Treatment Unit: ThermTech Model

VAC-25, 250cfm Thermal/

Catalytic Oxidizer

Consultant: EMCON

Start-Up Date: 06-02-94

	1921 Ringwood Avenue San Jose, California	Operation and Performance Data From: 06-02-94 To. 07-01-97 System was shut down on 1-15-97.							
Date Begin:		11-01-95	01-01-96	04-01-96	07-01-96	08-01-96			
Date End:		01-01-96	04-01-96	07-01-96	08-01-96	09-01-96			
Mode of Oxidation:		Cat-Ox	Cat-Ox	Cat-Ox	Cat-Ox	Cat-Ox			
Days of Operation,		0	0	0	0	18			
Days of Downtime		61	91	91	31	13			
Average Vapor Concer	ntrations (1)								
	: ppmv (2) as gasoline	NA	NA	NA	NA	140			
	mg/m3 (3) as gasoline	NA	NA	NA	NA	570			
	ppmv as benzene	NA	NA	NA	NA	16			
	mg/m3 as benzene	NA	NA	NA	NA	5			
System Influent:	ppmv as gasoline	NA	NA	NA	NA	73			
•	mg/m3 as gasoline	NA	NA	NA	NA	300			
	ppmv as benzene	NA	NA	NA	NA	0.8			
	mg/m3 as benzene	NA	NA	NA	NA	2.6			
System Effluent:	ppmv as gasoline	NA	NA	NA	NA	<5			
•	mg/m3 as gasoline	NA	NA	NA	NA	<20			
	ppmv as benzene	NA	NA	NA	NA	<0.2			
	mg/m3 as benzene	NA	NA	NA	NA	< 0.5			
Average Well Field Flov	v Rate (4), scfm (5):	0.0	0.0	0.0	0.0	119.3			
Average System Influent		0.0	0.0	0 0	0.0	153.0			
Average Destruction Ef	ficiency (6), percent (7).	NA	NA	NA	NA	93.3			
Average Emission Rate	s (8), pounds per day (9)								
Gasoline [.]		0 00	0.00	0.00	0.00	0.27			
Benzene:		0.00	0.00	0.00	0.00	0.01			
Operating Hours This Pe	eried:	0.00	0.00	0.00	1.82	435.13			
Operating Hours To Dat		4243 5	4243.5	4243.5	4245.3	4680.4			
Pounds/ Hour Removal	Rate, as gasoline (10):	0.00	0.00	0.00	0.00	0.25			
Pounds Removed This P Pounds Removed To Da		<u>0 0</u> 7287.9	<u>0.0</u> 7287.9	<u>0.0</u> 7287.9	<u>0.0</u> 7287.9	<u>110.7</u> 7398 7			
	•								
Gallons Removed This F	2 .	<u>0.0</u>	<u>0.0</u>	<u>0.0</u>	<u>0.0</u>	<u>17.9</u>			
Gallons Removed To Da	ate, as gasoline:	1175.5	1175.5	1175.5	1175 5	1193.4			
	2 .	<u>0.0</u> 1175.5		<u>0,0</u> 1175.5	<u>0.0</u> 1175 5				

Table 4 Soil-Vapor Extraction System Operation and Performance Data

Location: 889 West Grand Avenue

Oakland, California

Vapor Treatment Unit: ThermTech Model

VAC-25, 250cfm Thermal/

Catalytic Oxidizer

Consultant: EMCON

1921 Ringwood Avenue

Start-Up Date: 06-02-94 Operation and Performance Data From: 06-02-94

	San Jose, California	Operation and Performance Data From: 06-02-94 To: 07-01-97 System was shut down on 1-15-97.							
Date Begin		09-01-96	10-01-96	11-01-96	12-01-96	01-01-97			
Date End:		10-01-96	11-01-96	12-01-96	01-01-97	02-01-97			
Mode of Oxidation:		Cat-Ox	Cat-Ox	Cat-Ox	Cat-Ox	Cat-Ox			
Days of Operation:		8	30	0	2	9			
Days of Downtime:		22	1	30	29	22			
Average Vapor Concer	ntrations (1)								
	. ppmv (2) as gasoline	770	110	NA	300	NA			
	mg/m3 (3) as gasoline	3200	460	NA	1200	NA			
	ppmv as benzene	2.4	1.5	NA	< 0.5	NA			
	mg/m3 as benzene	7.8	4 9	NA	<2	NA			
System Influent	· ppmv as gasoline	300	39	NA	300	NA			
•	mg/m3 as gasoline	1200	160	NA	1200	NA			
	ppmv as benzene	8 0	0.5	NA	< 0.5	NA			
	mg/m3 as benzene	2 6	1.7	NA	<2	NA			
System Effluent	ppmv as gasoline	<5	<5	NA	11	NA			
·	mg/m3 as gasoline	<20	<20	NA	46	NA			
	ppmv as benzene	< 0.1	< 0.2	NA	< 0 1	NA			
	mg/m3 as benzene	<0.4	<0.5	NA	<04	NA			
Average Well Field Flov	w Rate (4), scfm (5):	128.6	99 3	0 0	148.8	148.8			
Average System Influen	t Flow Rate (4), scfm:	204.3	157 7	0.0	148.8	148.8			
Average Destruction Ef	ficiency (6), percent (7).	98.3	87.5	NA	96.2	NA			
Average Emission Rate	s (8), pounds per day (9)								
Gasoline:		0.37	0.28	NA	0.61	NA			
Benzene.		0.01	0.01	NA	0.01	NA			
Operating Hours This Pe	eriod:	180.20	730.20	0.19	43.83	215.74			
Operating Hours To Dat	e;	4860.6	5590 8	5591 0	5634.8	5850.6			
Pounds/ Hour Removal	Rate, as gasoline (10).	1.54	0 17	0 00	0 67	0 00			
Pounds Removed This P	Period, as gasoline (11):	<u>277.5</u>	<u>124 8</u>	0.0	<u>29.3</u>	0.0			
Pounds Removed To Da	ite, as gasoline:	7676.2	7801 0	7801 0	7830.3	7830.3			
Gallons Removed This I	Period, as gasoline (12)	448	20 1	0.0	4.7	0.0			
Gallons Removed To Da	ate, as gasoline	1238 2	1258.3	1258.3	1263.0	1263.0			

Table 4 Soil-Vapor Extraction System Operation and Performance Data

Location: 889 West Grand Avenue

Oakland, California

Vapor Treatment Unit: ThermTech Model

VAC-25, 250cfm Thermal/ Catalytic Oxidizer

Consultant: EMCON

1921 Ringwood Avenue San Jose California

Start-Up Date. 06-02-94

Operation and Performance Data From: 06-02-94

	San Jose, California	To: 07-01-9 System was shut down on 1-15-97.						
Date Begin:		02-01-97	03-01-97	04-01-97				
Date End:			04-01-97	07-01-97				
Mode of Oxidation:			Cat-Ox	Cat-Ox				
Days of Operation:		· · · · · · · · · · · · · · · · · · ·	0	0				
Days of Downtime:		28	31	91				
Average Vapor Concer	trations (1)							
Well Field Influent	ppmv (2) as gasoline	NA	NA	NA				
	mg/m3 (3) as gasoline	NA	NA	NA				
	ppmv as benzene		NA	NA				
	mg/m3 as benzene	NA	NA	NA				
System Influent	ppmv as gasoline	NA	NA	NA				
•	mg/m3 as gasoline	NA	NA	NA				
	ppmv as benzene	NA	NA	NA				
	mg/m3 as benzene	03-01-97 Cat-Ox 0 28 NA NA NA NA NA	NA	NA				
System Effluent:	ppmv as gasoline	NA	NA	NA				
	mg/m3 as gasoline	NA	NA	NA				
	ppmv as benzene	NA	NA	NA				
	mg/m3 as benzene	NA	NA	NA				
Average Well Field Flov	v Rate (4), scfm (5):	0.0	0.0	0 0				
Average System Influent		0.0	0.0	0.0				
Average Destruction Ef	ficiency (6), percent (7):	NA	NA	NA				
Average Emission Rate	s (8), pounds per day (9)							
Gasoline:		NA	NA	NA				
Benzene:		NA	NA	NA				
Operating Hours This Po	eriod	0.00	0.00	0 00				
Operating Hours To Dat			5850.6	5850.6				
Pounds/ Hour Removal	Rate, as gasoline (10)	0.00	0 00	0 00				
Pounds Removed This P	eriod, as gasoline (11).	0.0	0.0	0.0				
Pounds Removed To Da			7830.3	7830.3				
Gallons Removed This I	Period, as gasoline (12):	0.0	0.0	<u>0_0</u>				
Gallons Removed To Da			1263.0	1263.0				

Table 4 Soil-Vapor Extraction System Operation and Performance Data

Facility Number: 2169

Vapor Treatment Unit: ThermTech Model

Location: 889 West Grand Avenue

VAC-25, 250cfm Thermal/

Oakland, California

Catalytic Oxidizer

Consultant: EMCON

Start-Up Date: 06-02-94

1921 Ringwood Avenue San Jose, California Operation and Performance Data From: 06-02-94

To: 07-01-97

System was shut down on 1-15-97.

CURRENT REPORTING PERIOD:	04-01-97	to 07-01-97	
DAYS / HOURS IN PERIOD:	91	2184.0	
DAYS / HOURS OF OPERATION:	0	0.0	
DAYS / HOURS OF DOWN TIME:	91	2184.0	
PERCENT OPERATIONAL:		00%	
PERIOD POUNDS REMOVED:	0.0		
PERIOD GALLONS REMOVED:	0.0		
AVERAGE WELL FIELD FLOW RATE (scfm):		0.0	
AVERAGE SYSTEM INFLUENT FLOW RATE (scfm)		0.0	,

For the period from July 1 to December 1, 1994, ppmv results were converted to mg/m3 using the following formula:

concentration (as gasoline in mg/m3) = [concentration (as gasoline in ppmv) x 65 lb/lb-mole / 24.05 (lb/m3/lb-mole of air)/mg] (rounded as appropriate) concentration (as benzene in mg/m3) = [concentration (as benzene in ppmv) x 78 lb/lb-mole / 24 05 (lb/m3/lb-mole of air)/mg] (rounded as appropriate) For the period from December 1, 1994, to July 1, 1995, ppmv results were converted to mg/m3 using the following formula:

concentration (as gasoline in mg/m3) = [concentration (as gasoline in ppmv) x 87 lb/lb-mole / 24.05 (lb/m3/lb-mole of air)/mg] (rounded as appropriate) concentration (as benzene in mg/m3) = [concentration (as benzene in ppmv) x 78 lb/lb-mole / 24 05 (lb/m3/lb-mole of air)/mg] (rounded as appropriate) After July 1, 1995, all vapor results were reported by the laboratory in ppmv and mg/m3.

- 4 Average flow rates (time weighted average) are based on instantaneous flow rates recorded during the month, refer to Appendix B for instantaneous flow data
- 5 scfm. flow in standard cubic feet per minute at one atmosphere and 70 degrees Fahrenheit
- 6. Average destruction efficiencies are calculated using monthly average concentrations, refer to Appendix B for instantaneous destruction efficiency data.
- 7 destruction efficiency, percent = ([system influent concentration (as gasoline in mg/m3)] system effluent concentration (as gasoline in mg/m3)] / system influent concentration (as gasoline in mg/m3)] x 100 percent
- 8 Average emission rates are calculated using monthly average concentrations and flow rates, refer to Appendix B for instantaneous emission rate data
- 9 emission rates (pounds per day) = system effluent concentration (as gasoline or benzene in mg/m3) x system influent flow rate (scfm) x 0.02832 m3/fi3 x 1.440 minutes/day x 1 pound/454,000 mg
- 10 pounds/hour removal rate (as gasoline) = well field influent concentration (as gasoline in mg/m3) x well field influent flow rate (scfm) x 0 02832 m3/ft3 x 60 imnutes/hour x 1 pound/454,000 mg
- 11 pounds removed this period (as gasoline) = pounds/ hour removal rate x hours of operation
- 12 gallons removed this period (as gasoline) = pounds removed this period (as gasoline) x 0 1613 gallons/pound of gasoline
- 13 NA not applicable, not analyzed, or not available

Average concentrations are based on discrete sample results reported during the month, refer to Appendix B for discrete sample results.

^{2.} ppmy parts per million by volume

^{3.} mg/m3 milligrams per cubic meter

Table 5
Soil-Vapor Extraction Well Data

Date: 08-22-97

		A-1			A-2			A-3		A-4		
Date	Valve Position	TVHG	Vacuum Response	Valve Position	TVHG	Vacuum Response	Valve Position	TVHG	Vacuum Response	Valve Position	TVHG	Vacuum Response
		ppmv	ın-H2O		ppmv	ın-H2O		ppmv	ın-H2O	II.	ppmv	in-H2O
r SVE well ma	T onitoring data prior	to January 1, 199	5, please refer to	l the third quarter 19	95 groundwater n	nonitoring report fo	r this site					
01-13-95	passive	NA	0	passive	NA	0	passive	NA	0	passive	NA	0
01-26-95	passive	NA	0	passive	NA	0	passive	NA	0	passive	NA	0
07-17-95	System was shut	down on January	26, 1995.									
07-17-95	closed	NA	NA	closed	NA	NA	closed	NA	NA	closed	NA	NA
07-25-95	closed	NA	NA	closed	NA.	NA	closed	NA	NA	closed	NA	NA
08-22-95	closed	NA	NA	closed	NA	NA	closed	NA	NA	closed	NA	NA
09-21-95	closed	NA	0	closed	NA	0	closed	NA	0	closed	NA	0
09-21-95	ореп	NA	46	closed	NA	0	ciosed	NA	0	closed	NA	0
09-21-95	open	600 LAB	NA	ciosed	NA	NA	closed	NA	NA	closed	NA	NA
10-12-95	open	NA	36	closed	NA	0	closed	NA	0	closed	NA	0
10-12-95	System was manu	ally shut down.										
08-02-96	closed	NA	0	closed	NA	0	open	NA	46	closed	NA	0
08-05-96	closed	NA	NA	closed	NA	NA	open	NA	22	closed	NA	NA
09-23-96	closed	NA	NA	closed	NA	NA	closed	NA	NA	closed	NA	NA
10-24-96	closed	NA	NA	closed	NA	NA	closed	NA	NA	ciosed	NA	NA
12-04-96	closed	NA	NA	closed	NA	NA	closed	NA	NA	closed	NA	NA
01-15-97	System was manu	ally shut down.				i						

TVHG concentration of total volatile hydrocarbons as gasoline

ppmv parts per million by volume

in-H2O inches of water

open open to the system

passive: open to the atmosphere

closed closed to the system and atmosphere

NA not analyzed or not measured

FID TVHG concentration was measured with a portable flame ionization detector

LAB TVHG concentration was analyzed in the laboratory

PID TVHG concentration was measured with a portable photoionization detector

esj/j:\qtr_rpts\2169\2169tdb.xls\Table 5:imi 20805-129 004

Page 1

Table 5
Soil-Vapor Extraction Well Data

Date: 08-22-97

	Well Identification											
	AV-I			AV-2			AV-3				AV-4	
	Valve		Vacuum	Valve		Vacuum	Valve		Vacuum	Valve		Vacuum
Date	Position	TVHG	Response	Position	TVHG	Response	Position	TVHG	Response in-H2O	Position	TVHG	Response
		ppmv	1л-Н2О		ppmv	in-H2O		ppmv			ppmv	in-H2O
or SVE well m	onitoring data prior	to January 1, 199	5, please refer to	the third quarter 19	95 groundwater m	onitoring report fo	r this site.					
01-13-95	passive	NA	15	passive	NA	0	passive	NA	0	open	463 PID	16
01-26-95	passive	NA	27	passive	NA	0	passive	NA	0	open	I 8 FID	30
07-17-95	System was shut											
07-17-95	open	NA	NA	open	NA	NA	open	NA	NA	closed	NA	NA
07-25-95	орел	1026 PID	42	open	1364 PID	42	open	869 PID	42	closed	NA	NA
07-25-95	open	1200 LAB	NA	open	1600 LAB	NA	open	980 LAB	NA	closed	NA	NA
08-22-95	open	NA	42	open	NA	44	open	NA	44	closed	NA	NA
09-21-95	open	NA	43	open	NA	47	open	NA	47	closed	NA	0
09-21-95	open	NA	46	open	NA	46	open	NA	46	closed	NA	1
10-12-95	open	NA	44	open	NA	43	open	NA	43	closed	NA	1
10-12-95	System was man	aally shut down		1								
08-02-96	closed	48 5 PID	6	ореп	863 PID	46	open	322 PID	44	closed	NA	0
08-05-96	closed	NA	NA	open	NA	32	open	NA	36	open	NA	32
09-23-96	open	NA	42	open	NA	50	open	NA	53	open	NA	50
10-24-96	open	NA	NA	open	NA	NA	open	NA	NA	open	NA	NA
12-04-96	open	NA	NA	open	NA	NA	open	NA	NA	open	NA	NA
01-15-97	System was man	System was manually shut down										
01-13-77	System was man	auny guar down										

TVHG, concentration of total volatile hydrocarbons as gasoline

ppmv parts per million by volume

in-H2O: inches of water

open: open to the system

passive: open to the atmosphere

closed closed to the system and atmosphere

NA: not analyzed or not measured

FID: TVHG concentration was measured with a portable flame ionization detector

LAB: TVHG concentration was analyzed in the laboratory

PID. TVHG concentration was measured with a portable photoionization detector

Table 5 Soil-Vapor Extraction Well Data

Date. 08-22-97

	Well Identification												
	<u> </u>	AV-5		AV-6		AV-7				AR-2			
	Valve		Vacuum	Valve		Vacuum	Valve		Vacuum	Valve		Vacuum	
Date	Position	TVHG	Respons <i>e</i>	Position	TVHG	Response	Position	TVHG	Response	Position	TVHG	Response	
		ppmv	tn-H2O		ppmv	ın-H2O		ppmv	ın-H2O		ppmv	ın-H2O	
or SVE well me	nitoring data prior	to January 1, 199	5, please refer to	T the third quarter 19	95 groundwater m	onitoring report fo	r this site.			!			
01-13-95	passive	NA	1	орел	46 PID	16	passive	NA	0	passive	NA	0	
01-26-95	open	2.2 FID	30	open	2 3 FID	30	passive	NA	0	passive	NA	0	
07-17-95	System was shut down on January 26, 1995. System was restarted on July 17, 1995												
07-17-95	closed	NA	NA	closed	NA	NA	closed	NA	NA	closed	NA	NA	
07-25-95	closed	NA	NA	closed	NA	NA	closed	NA	NA	closed	NA	NA	
08-22-95	closed	NA	NA	closed	NA	NA	closed	NA	NA	open	NA	44	
09-21-95	closed	NA	0	closed	NA	0	closed	NA	0	open	NA	48	
09-21-95	closed	NA	0	open	NA	46	closed	NA	0	open	NA	46	
09-21-95	closed	NA	NA	open	2300 LAB	NA	closed	NA	NA	open	NA	NA	
10-12-95	closed	NA	0	open	NA	42	closed	NA	0	open	NA.	43	
10-12-95	System was manu	ally shut down		ĺ									
08-02-96	open	NA	44	open	185 PID	42	ореп	NA	44	closed	NA	40	
08-05-96	open	NA	30-36	орел	NA	32	open	NA	34	open	NA	28	
09-23-96	open	455 PID	50	open	282 PID	49	closed	NA	NA	open	13 2 PID	45	
10-24-96	open	NA	NA	open	NA	NA	closed	NA	NA	open	NA.	NA	
12-04-96	open	NA	NA	open	NA	NA	closed	NA	NA	open	NA	NA	
01-15-97	System was manu	ally shut down		}									
01-15-97	System was manu	ally shut down											

TVHG, concentration of total volatile hydrocarbons as gasoline

ppmv parts per million by volume

in-H2O: inches of water

open: open to the system

passive, open to the atmosphere

closed: closed to the system and atmosphere

NA not analyzed or not measured

FID TVHG concentration was measured with a portable flame ionization detector

LAB: TVHG concentration was analyzed in the laboratory

PID TVHG concentration was measured with a portable photoionization detector

Table 5
Soil-Vapor Extraction Well Data

Date: 08-22-97

	Well Ide								
j	ADR-1			ADR-2					
	Valve		Vacuum	Valve	,,,,	Vacuum			
Date	Position	TVHG	Response	Position	TVHG	Response			
		ppmv	ın-H2O		ppmv	in-H2O			
				<u> </u>					
For SVF well m	onitoring data prior	to January 1, 199	5. nlease refer to t	I he third quarter 19	95 groundwater me	onitoring report fo			
01-13-95	open	58 PID	16	open	160 PID	16			
01-26-95	open	2.2 FID	30	open	4.4 FID	30			
07-17-95		down on January	26, 1995.		rted on July 17, 19	95.			
07-17-95	open	NA	NA	open	NA	NA			
07-25-95	open	1184 PID	42	open	1057 PID	42			
07-25-95	open	1400 LAB	NA	open	1300 LAB	NA			
08-22-95	open	NA	44	open	NA	44			
09-21-95	open	NA	48	open	NA	47			
09-21-95	open	NA	45	open	NA	46			
10-12-95	open	NA	43	open	NA	44			
10-12-95	System was manu	ually shut down.							
08-02-96	closed	NA	0	open	950 PID	42			
08-05-96	closed	NA	NA	open	NA	32			
09-23-96	open	1221 PID	NA	open	950 PID	50			
10-24-96	open	NA	NA	ореп	NA	NA			
12-04-96	ореп	NA	NA	open	NA	NA			
01-15-97	System was manu	ually shut down.		Į.					
 				}					
ii	İ								
ii									

TVHG concentration of total volatile hydrocarbons as gasoline

ppmv: parts per million by volume

in-H2O, inches of water

open: open to the system

passive, open to the atmosphere

closed: closed to the system and atmosphere

NA: not analyzed or not measured

FID: TVHG concentration was measured with a portable flame ionization detector

LAB: TVHG concentration was analyzed in the laboratory

PID TVHG concentration was measured with a portable photoionization detector

Table 6
Air-Bubbling and Air-Sparge Systems
Operation and Performance Data

Facility Number: 2169 Air-Bubbling and Air-Sparge* Unit:* Location: 889 West Grand Avenue 3-horsepower Conde blower Oakland, California 5-horsepower air compressor Consultant: EMCON Start-Up Date: 07-15-94 Operation and Performance Data From: 07-15-94 1921 Ringwood Avenue San Jose, California To: 07-01-97 System was shut down on 1-15-97. 08-01-94 08-01-94 Date Begin: 07~15-94 08-01-94 08-15-94 09-13-94 08-01-94 Date End: 08-01-94 08-01-94 08-15-94 09-13-94 11-28-94 Days of Operation: 0 0 19 6 27 0 11 0 0 Days of Downtime: 12 76 3 Air-Bubbling Well Status: See Table 5 for the status of the air-bubbling wells Air is bubbled at an average flow rate of 1 scfm per well. Air-Sparge Well Status: open AS-I open open open closed open open AS-2 open closed open open open AS-3 closed open open open open open AS-4 closed open open open open open AS-5 open open open open open closed Air-Sparge Well Pressure (psig) (1): AS-I 2.8 2.8 30 2.0 2.4 0.0 AS-2 3.0 3.0 0.0 2.8 2.2 2.4 AS-3 3.6 3.6 3.8 3.1 2.2 0.0 3.1 3.1 3.4 2.8 0.0 AS-4 3.0 2.8 3.2 AS-5 2.8 3.2 0.0 2.8 25.0 29.0 29.0 27.0 290 Total Air-Sparge Flow Rate (scfm) (2): 0.0 Total Air-Bubbling and Air-Sparge Pressure (psig): 5.0 2.8 2.8 2.6 3.0 0.0 Dissolved Oxygen (mg/L) (3): Air-Sparge Wells: AS-1 NA (4) NA NA NA NA 1.4 NA 1.2 AS-2 NA NA NA NA NA NA NA NA 12 AS-3 NA AS-4 NA NA NA NA 8.0 NA AS-5 NA NA NA NA NA 1.4 Depth to Water (ft-BGS) (5): Air-Sparge Wells: AS-1 NA NA NA NA NA 10.55 AS-2 NA NA NA NA NA 11.29 AS-3 NA NA NA NA NA 10 78 NA NA NA 10 27 AS-4 NA NA

NA

NA

NA

NA

NA

10.65

AS-5

Table 6
Air-Bubbling and Air-Sparge Systems
Operation and Performance Data

Air-Bubbling and Air-Sparge* Unit:* Facility Number, 2169 Location: 889 West Grand Avenue 3-horsepower Conde blower Oakland, California 5-horsepower air compressor Consultant: EMCON Start-Up Date: 07-15-94 1921 Ringwood Avenue Operation and Performance Data From: 07-15-94 San Jose, California To. 07-01-97 System was shut down on 1-15-97 Date Begin: 11-28-94 01-03-95 02-03-95 03-31-95 07-25-95 08-10-95 Date End: 01-03-95 02-03-95 03-31-95 06-28-95 08-10-95 08-22-95 Days of Operation: 0 0 0 0 2 0 Days of Downtime: 36 31 56 89 14 12 Air-Bubbling Well Status: See Table 5 for the status of the air-bubbling wells. Air is bubbled at an average flow rate of 1 scfm per well. Air-Sparge Well Status: AS-I closed closed closed closed open open closed closed closed closed closed AS-2 closed AS-3 closed closed closed closed closed closed AS-4 closed closed closed closed open open closed closed AS-5 closed closed closed closed Air-Sparge Well Pressure (psig) (1): 0.0 0.00.0 0.0 8.9 5.5 AS-1 AS-2 0.0 0.0 0.0 0.0 0.0 0.0 AS-3 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 2.0 2.3 AS-4 AS-5 0.0 0.0 0.0 0.0 0.0 0.0 Total Air-Sparge Flow Rate (scfm) (2): 0.0 0.0 0.0 0.0 2.0 2.0 Total Air-Bubbling and Air-Sparge Pressure (psig): 0.0 0.0 0.0 0.0 50 45 Dissolved Oxygen (mg/L) (3): Air-Sparge Wells: AS-1 NA NA NA NA 1.1 NA AS-2 NA AS-3 NA NA AS-4 NA NA NA NA 1.4 AS-5 NA NA NA NA 1.0 NA Depth to Water (ft-BGS) (5). Air-Sparge Wells: 8.79 AS-1 NA NA NA 11.75 NA NA 9.37 AS-2 NA NA NA NA 8.93 AS-3 NA NA NA NA NA AS-4 NA NA 8.43 NA 11.31 NA 8.80 AS-5 NA NA NA 11.62 NA

Table 6
Air-Bubbling and Air-Sparge Systems
Operation and Performance Data

Facility Number: 2169 Location: 889 West Grand Av Oakland, California	Air-Bubbling and Air-Sparge* Unit:* 3-horsepower Conde blower 5-horsepower air compressor Start-Up Date: 07-15-94 Operation and Performance Data From: 07-15-94 To: 07-01-97 System was shut down on 1-15-97.						
Consultant. EMCON 1921 Ringwood Av San Jose, California							
Date Begin:	08-22-95	09-21-95	10-12-95	01-01-96	04-01-96	07-01-96	
Date End:	09-21-95	10-12-95	01-01-96	04-01-96	07-01-96	08-01-96	
Days of Operation:	11	NA	NA	NA	NA	0	
Days of Downtime:	19	NA	NA	NA	NA	31	
Air-Bubbling Well Status:	See Table 5 Air is bubble						
Air-Sparge Well Status:							
AS-1	open	closed	closed	closed	closed	closed	
AS-2	closed	closed	closed	closed	closed	closed	
AS-3	closed	closed	closed	closed	closed	closed	
AS-4	open	closed	closed	closed	closed	closed	
AS-5	open	closed	closed	closed	closed	closed	
Air-Sparge Well Pressure (psig) (1):							
AS-1	7.0	0.0	0.0	0.0	0.0	0.0	
AS-2	0.0	0.0	0.0	0.0	0.0	0 0	
AS-3	0.0	0.0	0.0	0.0	0.0	0.0	
AS-4	1.5	0.0	0.0	0.0	0.0	0.0	
AS-5	1.0	0.0	0.0	0.0	0 0	0.0	
Total Air-Sparge Flow Rate (scfm) (2):	6.0	0.0	0.0	0 0	0.0	0.0	
Total Air-Bubbling and Air-Sparge Pressure (psig).	45	0	0	0	0	0.0	
Dissolved Oxygen (mg/L) (3):							
Air-Sparge Wells:	A.T.	. .	***	27.6	27.	* * *	
AS-1	NA	7.4	NA	NA	NA	ΝA	
AS-2	NA	NA	NA	NA	NA	NA NA	
AS-3 AS-4	NA NA	NA 1.5	NA NA	NA NA	NA NA	NA NA	
AS-5	NA NA	1.6	NA NA	NA NA	NA NA	NA NA	
		1.0				1.7.1	
Depth to Water (ft-BGS) (5):							
Air-Sparge Wells: AS-1	NA	12.12	NA	NA	NA	NA	
AS-1 AS-2	NA NA	12.12 NA	NA NA	NA NA	NA NA	NA NA	
AS-3	NA.	NA	NA	NA	NA	NA NA	
AS-4	NA	11.78	NA	NA	NA	NA	
AS-5	NA	12.05	NA	NA	NA	NA	
1 NJ-3	11/1	12,00	1 127	1111	1462	(***	

Table 6
Air-Bubbling and Air-Sparge Systems
Operation and Performance Data

Facility Number, 2169 Air-Bubbling and Air-Sparge* Unit * Location: 889 West Grand Avenue 3-horsepower Conde blower Oakland, California 5-horsepower air compressor Consultant: EMCON Start-Up Date: 07-15-94 Operation and Performance Data From: 07-15-94 1921 Ringwood Avenue San Jose, California To. 07-01-97 System was shut down on 1-15-97. 09-01-96 10-01-96 11-01-96 12-01-96 Date Begin: 08-01-96 Date End: 09-01-96 10-01-96 11-01-96 12-01-96 01-01-97 Days of Operation. 0 30 0 2 18 30 Days of Downtime: 13 22 1 29 Air-Bubbling Well Status See Table 5 for the status of the air-bubbling wells. Air is bubbled at an average flow rate of 1 scfm per well. Air-Sparge Well Status: open AS-1 open closed open open AS-2 closed open closed open open AS-3 closed open open open open AS-4 open open closed open open AS-5 open open open closed open Air-Sparge Well Pressure (psig) (1). AS-1 2.0 1.5 2.0 0.0 2.0 AS-2 1.5 2.0 0.0 2.0 NA AS-3 2.0 1.5 2.0 0.0 2.0 1.5 0.0 AS-4 2.0 2.0 2.0 AS-5 1.5 0.0 1.5 2.0 2.0 Total Air-Sparge Flow Rate (scfm) (2): 12.0 9.0 0.0 9.0 6.0 Total Air-Bubbling and Air-Sparge Pressure (psig): 40 45 50 0 50 Dissolved Oxygen (mg/L) (3): Air-Sparge Wells: AS-1 NA NA NA NΑ NΑ AS-2 NA NA NA NA NA AS-3 NA NA NA NA NA AS-4 NA NA NA NA NA AS-5 NA NA NA NA NA Depth to Water (ft-BGS) (5): Air-Sparge Wells: AS-1 NA NA NA NA NA AS-2 NA NA NA NA NA AS-3 NA NA NA NA NA AS-4 NA NA NA NA NA AS-5 NA NA NA NA NA

Table 6 Air-Bubbling and Air-Sparge Systems Operation and Performance Data

Facility Number: 2169 Location: 889 West Grand Av Oakland, California	ı								
Consultant: EMCON 1921 Ringwood Av San Jose, California		Start-Up Date: 07-15-94 Operation and Performance Data From: 07-15-94 To: 07-01-97							
	System was shut down on 1-15-97.								
Date Begin:	01-01-97	02-01-97	03-01-97	04-01-97	05-01-97	06-01-97			
Date End:	02-01-97	03-01-97	04-01-97	05-01-97	06-01-97	07-01-97			
Days of Operation (Air-Bubbler):									
Days of Downtime (Air-Bubbler):									
Days of Operation (Air-Sparge):	9	0	0	0	0	0			
Days of Downtime (Air-Sparge):	22	28	31	30	31	30			
Air-Bubbling Well Status:	See Table 5 for the status of the air-bubbling wells. Air is bubbled at an average flow rate of 1 scfm per well								
			-		•				
Air-Sparge Well Status:									
AS-1	open	closed	closed						
AS-2	open	closed	closed						
AS-3	open	closed	closed						
AS-4 AS-5	open open	closed closed	closed closed						
	Орси	Closed	Cloaca						
Air-Sparge Well Pressure (psig) (1):	•••	2.0							
AS-1	NA	0.0	0.0						
AS-2	NA	0.0	0.0						
AS-3	NA	0.0	0.0						
AS-4 AS-5	NA NA	0.0	0.0						
Total Air-Sparge Flow Rate (scfm) (2):	10.0	0.0	0.0						
Total Air-Bubbling and									
Air-Sparge Pressure (psig):	60	0	0						
Dissolved Oxygen (mg/L) (3): Air-Sparge Wells									
AS-1	NA	NA	NA						
AS-2	NA	NA	NA						
AS-3	NA	NA	NA						
AS-4	NA	NA	NA						
AS-5	NA	NA	NA						
Depth to Water (ft-BGS) (5):									
Air-Sparge Wells:	NIA	N.I.A	N.I.A						
AS-1	NA NA	NA NA	NA NA						
AS-2 AS-3	NA NA	NA NA	NA NA						
	NA NA	NA NA	NA NA						
AS-4		NA NA	NA NA						
AS-5	NA	NA	NA						

Table 6 Air-Bubbling and Air-Sparge Systems Operation and Performance Data

Facility Number: 2169

Air-Bubbling and Air-Sparge* Unit:*

Location: 889 West Grand Avenue

3-horsepower Conde blower

Oakland, California

5-horsepower air compressor

Consultant: EMCON

Start-Up Date: 07-15-94

1921 Ringwood Avenue

Operation and Performance Data From: 07-15-94

To: 07-01-97

San Jose, California

System was shut down on 1-15-97.

CURRENT REPORTING PERIOD:

04-01-97

to 07-01-97

DAYS / HOURS IN PERIOD: DAYS / HOURS OF OPERATION: 91 2184.0 0 0.0

DAYS / HOURS OF DOWN TIME.

91 2184.0

PERCENT OPERATIONAL

0.0%

^{1.} psig: pounds per square inch gauge


^{2.} scfm. standard cubic feet per minute at 14.7 psi and 70° F

^{3.} mg/L: milligrams per liter

NA: not available or not analyzed

ft-BGS: feet below grade surface

During the period from July 15, 1994 to July 25, 1995 the air-sparge system used a 3-horsepower Conde blower. On July 25, 1995, it was replaced with a 5-horsepower air compressor.





Base map from USGS 7.5' Quad. Map: Oakland West, California. Photorevised 1980.

0 2000 4000

SCALE IN FEET




DATE APR. 1997 DWN KAJ APP REV PROJECT NO

805-129 004

FIGURE 1


ARCO PRODUCTS COMPANY SERVICE STATION 2169, 889 W. GRAND AVE. SAN JOSE, CALIFORNIA

QUARTERLY GROUNDWATER MONITORING SITE LOCATION



ARCO Service Station 2169
Soil-Vapor Extraction and Treatment System
Historical System Influent TVHG and Benzene Concentrations

Figure 4




TVHG: total volatile hydrocarbons as gasoline ppmv: parts per million by volume

Figure 5


ARCO Service Station 2169

Soil-Vapor Extraction and Treatment System
Historical Hydrocarbon Removal Rates



esj/j.\qtr_rpts\2169\2169tss.xls\SVE Model:imi 20805-129.004

ARCO Service Station 2169 Soil-Vapor Extraction and Treatment System WF Influent TVHG Concentration and Cost per Pound This Period



APPENDIX A

ANALYTICAL RESULTS AND CHAIN OF CUSTODY DOCUMENTATION, SECOND QUARTER 1997 GROUNDWATER MONITORING EVENT



July 1, 1997

Service Request No.: <u>\$9700938</u>

Ms. Ivy Inouye **EMCON** 1921 Ringwood Avenue San Jose, CA 95131

RE: 20805-129-004/TO#21133.00/2169 OAKLAND

Dear Ms. Inouve:

The following pages contain analytical results for sample(s) received by the laboratory on May 21, 1997. Results of sample analyses are followed by Appendix A which contains sample custody documentation and quality assurance deliverables requested for this project. The work requested has been assigned the Service Request No. listed above. To help expedite our service, please refer to this number when contacting the laboratory.

Analytical results were produced by procedures consistent with Columbia Analytical Services' (CAS) Quality Assurance Manual (with any deviations noted). Signature of this CAS Analytical Report below confirms that pages 2 through 13, following, have been thoroughly reviewed and approved for release in accord with CAS Standard Operating Procedure ADM-DatRev3.

Please feel welcome to contact me should you have questions or further needs.

Sincerely,

Steven L. Green

Project Chemist

Acronyms

American Association for Laboratory Accreditation A2LA

ASTM American Society for Testing and Materials

BOD Biochemical Oxygen Demand

Benzene, Toluene, Ethylbenzene, Xylenes **BTEX**

California Assessment Metals CAM **CARB** California Air Resources Board

CAS Number Chemical Abstract Service registry Number

CFC Chlorofluorocarbon Colony-Forming Unit **CFU** Chemical Oxygen Demand COD

Department of Environmental Conservation DEC Department of Environmental Quality DEQ Department of Health Services DHS DLCS **Duplicate Laboratory Control Sample**

DMS **Duplicate Matrix Spike** Department of Ecology DOE DOH Department of Health

U. S. Environmental Protection Agency **EPA**

Environmental Laboratory Accreditation Program ELAP

Gas Chromatography GC

Gas Chromatography/Mass Spectrometry GC/MS

IC Ion Chromatography

ICB initial Calibration Blank sample

Inductively Coupled Plasma atomic emission spectrometry ICP

ICV Initial Calibration Verification sample

Estimated concentration. The value is less than the MRL, but greater than or equal to J

the MDL, if the value is equal to the MRL, the result is actually <MRL before rounding.

Laboratory Control Sample LCS LUFT Leaking Underground Fuel Tank

Modified М

Methylene Blue Active Substances **MBAS**

Maximum Contaminant Level. The highest permissible concentration of a MCL

substance allowed in drinking water as established by the U. S. EPA.

Method Detection Limit MDL Most Probable Number MPN MRL Method Reporting Limit

MS Matrix Spike

Methyl tert-Butyl Ether MTBE

Not Applicable NA Not Analyzed NAN Not Calculated NC

National Council of the paper industry for Air and Stream Improvement NCASI Not Detected at or above the method reporting/detection limit (MRL/MDL) ND

NIOSH National Institute for Occupational Safety and Health

NTU Nephelometric Turbidity Units

Parts Per Billion ppb Parts Per Million ppm

Practical Quantitation Limit POL Quality Assurance/Quality Control QA/QC Resource Conservation and Recovery Act

RCRA

Relative Percent Difference RPD Selected Ion Monitoring SIM

Standard Methods for the Examination of Water and Wastewater, 18th Ed., 1992 SM

Solubility Threshold Limit Concentration STLC

Test Methods for Evaluating Solid Waste, Physical/Chemical Methods, SW-846, SW

3rd Ed., 1986 and as amended by Updates I, II, IIA, and IIB.

Toxicity Characteristic Leaching Procedure TCLP

Total Dissolved Solids TDS

Total Petroleum Hydrocarbons **TPH**

Trace level. The concentration of an analyte that is less than the PQL but greater than or equal tr

to the MDL. If the value is equal to the PQL, the result is actually <PQL before rounding.

Total Recoverable Petroleum Hydrocarbons TRPH

Total Suspended Solids TSS

Total Threshold Limit Concentration TTLC

ACRONLST.DOC 7/14/95 Volatile Organic Analyte(s) VOA

Analytical Report

Client:

ARCO Products Company

Project:

20805-129-004/TO#21133.00/2169 OAKLAND

Sample Matrix: Water Service Request: \$9700938 Date Collected: 5/21/97

Date Received: 5/21/97

BTEX, MTBE and TPH as Gasoline

Sample Name:

A-5 (11)

Units: ug/L (ppb)

Basis: NA

Lab Code:

S9700938-001

Test Notes:

Analyte	Prep Method	Analysis Method	MRL	Dilution Factor	Date Extracted	Date Analyzed	Result	Result Notes
TPH as Gasoline	EPA 5030	CA/LUFT	50	40	NA	6/2/97	16,000	
Benzene	EPA 5030	8020	0.5	40	NA	6/2/97	1500	
Toluene	EPA 5030	8020	0.5	40	NA	6/2/97	900	
Ethylbenzene	EPA 5030	8020	0.5	40	NA	6/2/97	700	
Xylenes, Total	EPA 5030	8020	0.5	40	NA	6/2/97	2700	
Methyl tert -Butyl Ether	EPA 5030	8020	3	40	NA	6/2/97	<120	C1

The MRL was elevated due to high analyte concentration requiring sample dilution.

IS22/020597p

CI

Analytical Report

Client:

ARCO Products Company

Project:

20805-129-004/TO#21133.00/2169 OAKLAND

Service Request: S9700938 Date Collected: 5/21/97

Sample Matrix:

Water

Date Received: 5/21/97

BTEX, MTBE and TPH as Gasoline

Sample Name:

A-6(11)

Units: ug/L (ppb)

Lab Code:

\$9700938-002

Basis: NA

Test Notes:

Analyte	Prep Method	Analysis Method	MRL	Dilution Factor	Date Extracted	Date Analyzed	Result	Result Notes
TPH as Gasoline	EPA 5030	CA/LUFT	50	1	NA	6/4/97	600	
Benzene	EPA 5030	8020	0.5	1	NA	6/4/97	0.6	
Toluene	EPA 5030	8020	0.5	1	NA	6/4/97	0.6	
Ethylbenzene	EPA 5030	8020	0.5	1	NA	6/4/97	<2	MI
Xylenes, Total	EPA 5030	8020	0.5	1	NA	6/4/97	2.7	
Methyl tert -Butyl Ether	EPA 5030	8020	3	1	NA	6/4/97	ND	

Μl

The MRL was elevated because of matrix interferences.

1S22/020597p

Analytical Report

Client:

ARCO Products Company

Project:

20805-129-004/TO#21133.00/2169 OAKLAND

Date Collected: 5/21/97

Sample Matrix:

Water

Date Received: 5/21/97

Service Request: S9700938

BTEX, MTBE and TPH as Gasoline

Sample Name:

ADR-2 (12)

Units: ug/L (ppb)
Basis: NA

Lab Code:

S9700938-003

Test Notes:

Analyte	Prep Method	Analysis Method	MRL	Dilution Factor	Date Extracted	Date Analyzed	Result	Result Notes
TPH as Gasoline	EPA 5030	CA/LUFT	50	10	NA	6/2/97	6100	
Benzene	EPA 5030	8020	0.5	10	NA	6/2/97	380	
Toluene	EPA 5030	8020	0.5	10	NA	6/2/97	22	
Ethylbenzene	EPA 5030	8020	0.5	10	NA	6/2/97	210	
Xylenes, Total	EPA 5030	8020	0.5	10	NA	6/2/97	320	
Methyl tert-Butyl Ether	EPA 5030	8020	3	10	NA	6/2/97	<30	C1

The MRL was elevated due to high analyte concentration requiring sample dilution.

1S22/020597p

Cl

Analytical Report

Client:

ARCO Products Company

Project:

Sample Matrix:

20805-129-004/TO#21133.00/2169 OAKLAND

Water

Service Request: \$9700938

Date Collected: 5/21/97

Date Received: 5/21/97

BTEX, MTBE and TPH as Gasoline

Sample Name:

ADR-1 (11)

Units: ug/L (ppb)
Basis: NA

Lab Code:

S9700938-004

Test Notes:

Analyte	Prep Method	Analysis Method	MRL	Dilution Factor	Date Extracted	Date Analyzed	Result	Result Notes
TPH as Gasoline	EPA 5030	CA/LUFT	50	10	NA	5/31/97	2100	
Benzene	EPA 5030	8020	0.5	10	NA	5/31/97	300	
Toluene	EPA 5030	8020	0.5	10	NA	5/31/97	18	
Ethylbenzene	EPA 5030	8020	0.5	10	NA	5/31/97	37	
Xylenes, Total	EPA 5030	8020	0.5	10	NA	5/31/97	200	
Methyl tert -Butyl Ether	EPA 5030	8020	3	10	NA	5/31/97	79	

IS22/020597p

Analytical Report

Client:

ARCO Products Company

Project:

20805-129-004/TO#21133.00/2169 OAKLAND

Sample Matrix:

Water

Date Collected: NA Date Received: NA

Service Request: S9700938

BTEX, MTBE and TPH as Gasoline

Sample Name:

Method Blank

Units: ug/L (ppb)

Lab Code:

S970530-WB2

Basis: NA

Test Notes:

	Prep	Analysis		Dilution	Date	Date		Result
Analyte	Method	Method	MRL	Factor	Extracted	Analyzed	Result	Notes
TPH as Gasoline	EPA 5030	CA/LUFT	50	ı	NA	5/30/97	ND	
Benzene	EPA 5030	8020	0.5	1	NA	5/30/97	ND	
Toluenc	EPA 5030	8020	0.5	1	NA	5/30/97	ND	
Ethylbenzene	EPA 5030	8020	0.5	1	NA	5/30/97	ND	
Xylenes, Total	EPA 5030	8020	0.5	1	NA.	5/30/97	ND	
Methyl tert -Butyl Ether	EPA 5030	8020	3	1	NA	5/30/97	ND	

IS22/020597p

Analytical Report

Client:

ARCO Products Company

Project:

20805-129-004/TO#21133.00/2169 OAKLAND

Date Collected: NA

Service Request: S9700938

Sample Matrix:

Water

Date Received: NA

BTEX, MTBE and TPH as Gasoline

Sample Name:

Method Blank

Units: ug/L (ppb)

Lab Code:

\$970602-WB1

Basis: NA

Test Notes:

Analyte	Prep Method	Analysis Method	MRL	Dilution Factor	Date Extracted	Date Analyzed	Result	Result Notes
TPH as Gasoline	EPA 5030	CA/LUFT	50	1	NA	6/2/97	ND	
Benzene	EPA 5030	8020	0.5	1	NA	6/2/97	ND	
Toluene	EPA 5030	8020	0.5	1	NA	6/2/97	ND	
Ethylbenzene	EPA 5030	8020	0.5	1	NA	6/2/97	ND	
Xylenes, Total	EPA 5030	8020	0.5	1	NA	6/2/97	ND	
Methyl tert -Butyl Ether	EPA 5030	8020	3	1	NA	6/2/97	ND	

IS22/020597p

Analytical Report

Client:

ARCO Products Company

Project:

20805-129-004/TO#21133.00/2169 OAKLAND

Date Collected: NA
Date Received: NA

Service Request: S9700938

Sample Matrix:

Water

BTEX, MTBE and TPH as Gasoline

Sample Name:

Method Blank

Units: ug/L (ppb)

Lab Code:

S970604-WB1

Basis: NA

Test Notes:

Analyte	Prep Method	Analysis Method	MRL	Dilution Factor	Date Extracted	Date Analyzed	Result	Result Notes
TPH as Gasoline	EPA 5030	CA/LUFT	50	1	NA	6/4/97	ND	
Benzene	EPA 5030	8020	0.5	1	NA	6/4/97	ND	
Toluene	EPA 5030	8020	0.5	1	NA	6/4/97	ND	
Ethylbenzene	EPA 5030	8020	0.5	1	NA	6/4/97	ND	
Xylenes, Total	EPA 5030	8020	0.5	1	NA	6/4/97	ND	
Methyl tert -Butyl Ether	EPA 5030	8020	3	1	NA	6/4/97	ND	

1\$22/020597p

APPENDIX A

QA/QC Report

Client: **ARCO Products Company**

20805-129-004/TO#21133.00/2169 OAKLAND Project:

Date Collected: NA

Sample Matrix: Water

Date Received: NA Date Extracted: NA Date Analyzed: NA

Service Request: S9700938

Surrogate Recovery Summary BTEX, MTBE and TPH as Gasoline

Prep Method:

EPA 5030

Units: PERCENT

Analysis Method: 8020

CA/LUFT

Basis: NA

		Test	Percent	Recovery
Sample Name	Lab Code	Notes	4-Bromofluorobenzene	a,a,a-Trifluorotoluene
A-5 (11)	S9700938-001		99	96
A-6 (11)	S9700938-002		93	104
ADR-2 (12)	S9700938-003		96	96
ADR-1 (11)	S9700938-004		98	92
BATCH QC	S9700959-002MS		96	106
BATCH QC	S9700959-002DMS		99	105
Method Blank	S970530-WB2		91	87
Method Blank	S970602-WBI		101	96
Method Blank	S970604-WB1		101	96

CAS Acceptance Limits:

69-116

69-116

QA/QC Report

Client:

APCO Products Company

Project:

20805-129-004/TO#21133.00/2169 OAKLAND

Sample Matrix Water

Service Request: S9700938

Date Collected: NA Date Received: NA

Date Extracted: NA

Date Analyzed: 6/2/97

Matrix Spike/Duplicate Matrix Spike Summary

TPH as Gasoline

Sample Name: BATCH QC

Units. ug/L (ppb)

Lab Code:

S9700959-002MS,

S9700959-002DMS

Basis: NA

Test Notes:

Percent Recovery

	Prep	Analysis		Spike	Level	Sample	Spike	Result			CAS Acceptance	Relative Percent	Result
Analyte	Method	Method	MRL	MS	DMS	Resuit	MS	DMS	MS	DMS	Limits	Difference	Notes
Gasoline	EPA 5030	CA/LUFT	50	250	250	ND	240	270	96	108	75-135	12	

QA/QC Report

Client: Project: ARCO Products Company

20805-129-004/TO#21133.00/2169 OAKLAND

Service Request: S9700938

Date Analyzed: 5/30/97

Initial Calibration Verification (ICV) Summary BTEX, MTBE and TPH as Gasoline

Sample Name:

ίCV

Units: ug/L (ppb)

Lab Code:

ICVI

Basis: NA

Test Notes:

ICV Source:

Analyte	Prep Method	Analysis Method	True Value	Result	Percent Recovery	Result Notes
TPH as Gasoline	EPA 5030	CA/LUFT	250	250	100	
Benzene	EPA 5030	8020	25	25	100	
Toluene	EPA 5030	8020	25	24	96	
Ethylbenzenc	EPA 5030	8020	25	24	96	
Xylenes, Total	EPA 5030	8020	75	71	95	
Methyl tert -Butyl Ether	EPA 5030	8020	25	27	108	

ICV/032196

		41							. J	۱ ٦ ٦		\supset								chain of Custody
Devision of Atlantic Pacility no / C 9 Dengine Ray / S	omp	any 📢	59	700	938	Task Ord	ier No.	Project	manade	<u> </u>	<u>>, 0</u>	<u> </u>	1							Laboratory name (A) Contract number
Facility R92 //		City	()	AK	LANI	1		(Consult	ant)	1	Jhr		<u> </u>	Fax	no.	1.0.	٠ دے	- \ _	015	Contract number
769		(Fac	ility)		Telephone	no.		Telepho (Consult	ne no. ant)(/ į	X 1 4	45[3	5.7	<u>کن2</u>) (Con	sultant	108-		3 3	<u></u>	Contract number
1000		<u> </u>		1	(Ailoo)	Address	152	/	R	1	00	ن حز	AL	4.	Sin	2 <u>S</u> C	236	<u>~1</u>	<u>رد / 5 5 ج</u>	Method of shipment
litant name EM	0.7					(CONSUME			W ₁ C		_ }	1		}		.ĕ₩.	07.00	_		Sample
		Matrix	1	Presen	ation	.	Đ.		135	\$□ \$□	32	A503E		9	9	~~ <u>~</u>	EPA 6	18 L		Jel. ver
. \					ļ	Address (Consultar egg	Sampling time	BTEX 602/EPA 8020	BTEXTPH //77772 EPA M602/8020/8015	TPH Modified 8015 Gas ☐ Diesel ☐	Greas	TPH EPA 418.1/SM503E	11/801	24/824	25/82	ايّ	Melals	A25	ļ	Le 1. De
	Soil	Water	Other	Ice	Acid	mplin	illqmı	ÄË Ep a	A NS	# S □	13.1 13.1	#¥	EPA 64	EPA 6	EPA 6	7CP Metal	AST DIF	Lead 7420		Special detection
Lab no.		1				øs.	- SS	<u> 28</u>	<u> </u>	i-o	04									Littimiteborang
	 	1			\ X	5/21/9	1300		<u> </u>	ļ					-			 		possible.
(1) 2	-	$+ \checkmark$		- 1	X		1520		<u> </u>					 		-		ļ		1 2005, 56.
(ir) 2	-	 ^	 	ļ	1	 	1340	_	X								<u> </u>	-		
2-2(121) 2		$\perp \chi$	<u> </u>	<u> </u>	X	+	 		X	†	$\uparrow $			\						Special QA/QC
21(11) 2		1 1		X	1	1-4-	1400	_	+-^	+-	 	 	 	_						Hormal
	+-	1		_		<u> </u>	<u> </u>		-	↓ —	-	 -	-	+	+-	-	+	 		Normal
	 		+	 								 	 	 	┼─	+-	+-	+	+	┤ ′ ˙
						 	1			ļ	ļ		ļ	<u> </u>			1			Remarks
				 			 		1	1				_			_	<u> </u>		21000
	_	Ì	Ì	<u> </u>		<u> </u>		-+-	-	-	+	1	\top		1			_		2-40 ML. H
	\top				ļ	<u> </u>			_		-	+-	+		╁	_	+-			20805-129.004
	+-		_	1]						-}		-}	_	+	-}-	+ +	MBE-BX 80
	\dashv	_{-	+-						- }	\	\ _			_						- 20 y 25 129.00°
				 			- 	_			\top							_\		12505-120-00
									-							_				Lab number
			_		<u> </u>								-	-	\rightarrow	- -	1			Lab number 69700938
		-+-					\					_		_+-	+	-	-0	_ -	_ 	Turnaround time
		+		+-											1	1	_			Priority Rush
							_													1 Business Day
		_\						- +	empera	ture red	eived:		<u> </u>	0	0 (
Condition of sample:		[N] 7	AC	T				Time F											-	2 Business Days
Relinquished by sampler					Date /	1/97/	144	0												Expedited 5 Business Days
March Sue	Zull	-			Date	-1 11		Time F	eceive	d by		_								
Relinquished by								Time I	Receive	d by lak	Aratory	11	Z		Dat	e/2/	I	Tir		Standard 10 Business Days
Relinquished by					Date			,	17	$\mathcal{L}_{i}\ell$, ,,	z le	20		15	[2/	9 47		740/	6-5-9

APPENDIX B SVE SYSTEM MONITORING DATA LOG SHEETS

ARCO 2169 SVE SYSTEM MONITORING DATA

				Penod Penod	720 00 30 00				n Hours: vn Days																
Flow R	ates	FID o	r PID Re	sults				Well Fiel	d Influent			System	Influent	System	i Effluent	·				!					
Well Field Flow Rate	System Influent Flow Rate	Well Field	System Influent	System Effluent	Destruction Efficiency	Laboratory Sample Time	Gas	oline	Benz	zéne	Gasol	line	Benzene	Gasoline	Bei	nzene	Destruction Efficiency	Gasoline Emission Rate	Benzene Emission Rate	Period Hours	Meter Hours	dours of Operation	Days of Operation	Jown Hours	Down Days
scfm	scfm	ppm	ppm	ppm	%		ppmv	mg/m3	ута	mg/m3	ppmv	mg/m3	ppmv mg/m3	ppmv mg/m3	ppmv	mg/m3		lb/day	Ib/day						
0.0	0 0 0.0																			34 33 685 67	6305.02 6305.02 6305.02	0.00	0 00 0.00	34 33 685 67	1 4 28 5
-					-				<u> </u>											720 00		0 00	0 00	720 00	30 0
1	O Well Freid Flow Rate	Flow Rates Mel Held Flow Hate Make Make Make Make Make Make Make Make	Flow Rates FID of Male Held Flow Rate Mel Held Flow Rate Mel Held Mel Mel Held Mel Do 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	Flow Rates FID or PID Reference Laborators Held Flow Rate Reference Laborators Flow Rate Rate Reference Laborators Flow Rate Rate Rate Rate Rate Rate Rate Rate	Well Field Flow Rate System Influent Flow Rate Well Field Well Field System Influent	Flow Rates FID or PID Results Pipe Results Fig. 4 Avel Field Mell Field Mel	Flow Rates FID or PID Results Particle Flow Hale System Influent Flow Rate System Influent Flow Rate System Influent Flow Rate System Influent Makel Floor System Effluent Makel Floor System Influent Makel Floor Makel Flo	Flow Rates FID or PID Results Page 1	Flow Rates FID or PID Results Well Field How Hale Gasoline Gasoline The post of the property of the propert	Flow Rates FID or PID Results Well Field Influent Fig. 20	Flow Rates FID or PID Results Well Field Influent Posture Pin Pin	Flow Rates FID or PID Results Well Field Influent Gasoline Benzene Gaso Gasoline Benzene Gaso Gasoline Scim Piper Height Heid	Flow Rates FID or PID Results Well Field Influent System Well Field Influent System Well Field Influent System Gasoline Benzene Gasoline Gasoline Benzene Gasoline Flow Rates Gasol	Flow Rates FID or PID Results Well Field Influent System Influent Well Field Influent System Influent Gasoline Benzene Gasoline Benzene Gasoline Benzene Distriction Scim ppm ppm ppm 9% ppmv mg/m3 ppmv mg/m3 ppmv mg/m3 ppmv mg/m3 ppmv mg/m3	Well Field Influent System Influent Sy	Well Field Influent System Influent Sy	Well Field Influent System Influent System Influent System Effluent System Influent System Influent System Influent System Influent System Influent System Influent System Effluent System Effluent System Effluent System Effluent System Influent Sy	Well Field Influent System Influent System Influent System Effluent System Influent System Influent System Effluent System Effluent System Effluent System Effluent System Effluent System Influent System Effluent System Effluent System Effluent System Effluent System Influent Sy	Well Field Influent System Influent System Influent System Effluent Well Field Influent System Influent System Influent System Effluent System Influent System Effluent Well Field Influent Well Field Influent System Influent System Influent System Effluent System Effluent Gasoline Benzene Gasoline Benzene Gasoline Benzene Gasoline Benzene Gasoline Benzene Gasoline Benzene Benz	Well Field Influent System Influent System Effluent Gasoline Benzene Gasoline Benze	Well Field Influent System Influent System Influent System Effluent Sy	Well Field Influent System Influent System Eiffluent System Ei	Weil Field Influent System Influent System Influent System Effluent System	Well Field Influent System Influent System Influent System Influent System Effluent System	

ARCO 2169 SVE SYSTEM MONITORING DATA

Reporting Period 06/01/97 00 00 07/01/97 00:00	Hours in Penod. 720 00 Days in Period: 30 00 Field Monitoring Data							Operation + Dow Operation + Dov	n Hours 720 00 wn Days: 30.00											"\		
								Laboratory Monitoring Data														
[Flow Rates FID or F			or PID Re	PID Results		<u> </u>	Well Field Influent		System Influent		System Effluent]]					
Reading Date & Time	Well Field Flow Rate	System Influent Flow Rate	Well Field	System Influent	System Effluent	Destruction Efficiency	Laboratory Sample Time	Gasoline	Benzene	Gasoline	Benzene	Gasoline	Benzene	Destruction Efficiency	àasoline Émission Rate	Benzene Emission Rate	Period Hours	Meter Hours	tours of Operation	Days of Operation	Down Hours	Down Days
	scfm	scfm	ppm	ррт	ppm	%		ppmv mg/m3	ppmv mg/m3	ppmv mg/m3	ppmv mg/m3	ppmv mg/m3	ppmv mg/m3	%	lb/day	lb/day						<u> </u>
06/01/97 00 00 07/01/97 00:00	00	0.0										!			_		720 00	6305.02 6305.02	0 00	0.00	720 00	30 0
Penod Totals														-			720 00		0.00	0.00	720 00	30 0
Penod Averages	00	0.0																				