

December 17, 1999

#### REPORT

o f

ADDITIONAL SOIL AND GROUNDWATER ASSESSMENT

\_\_\_\_\_AND

QUARTERLY GROUNDWATER SAMPLING ASE JOB NO. 3540

a t

Oakland Truck Stop 8255 San Leandro Street Oakland, California

Submitted by:
AQUA SCIENCE ENGINEERS, INC.
208 West El Pintado
Danville, CA 94526
(925) 820-9391

### TABLE OF CONTENTS

SEC	CTION	<b>PAGE</b>
1.0	INTRODUCTION	1
2.0	SCOPE OF WORK	1
3.0	DRILLING SOIL BORINGS AND COLLECTING SAMPLES	2
	<ul><li>3.1 Drilling and Collection of Soil Samples</li><li>3.2 Site Specific Geology</li></ul>	2 3
4.0	ANALYTICAL RESULTS FOR SOIL	3
5.0	MONITORING WELL CONSTRUCTION, DEVELOPMENT AND SAMPLING	3
	<ul> <li>5.1 Monitoring Well Construction</li> <li>5.2 Monitoring Well Development</li> <li>5.3 Monitoring Well Sampling</li> </ul>	3 4 4
6.0	GROUNDWATER ELEVATIONS	5
7.0	ANALYTICAL RESULTS FOR GROUNDWATER	5
8.0	CONCLUSIONS AND RECOMMENDATIONS	6
9.0	REPORT LIMITATIONS	7
LIST	T OF TABLES	
TAB	LE 1 ANALYTICAL RESULTS FOR SOIL	
TAB	LE 2 GROUNDWATER ELEVATIONS	
TAB	LE 3 ANALYTICAL RESULTS FOR GROUNDWATER - HYDROC	'ARBONS
TAB	LE 4 ANALYTICAL RESULTS FOR GROUNDWATER – HVOCs, PCBs, & METALS	SVOCs,

#### LIST OF FIGURES

FIGURE 1 SITE LOCATION MAP

FIGURE 2 GROUNDWATER ELEVATION CONTOUR MAP

#### LIST OF APPENDICES

APPENDIX A ACHCSA LETTER

APPENDIX B PERMIT

APPENDIX C BORING LOGS AND WELL CONSTRUCTION DETAILS

APPENDIX D ANALYTICAL REPORT AND CHAIN OF CUSTODY FORM FOR

SOIL SAMPLES

APPENDIX E WELL SAMPLING FIELD LOGS

APPENDIX F ANALYTICAL REPORT AND CHAIN OF CUSTODY FORM FOR

**GROUNDWATER SAMPLES** 

#### 1.0 INTRODUCTION

This report presents the methods and findings of Aqua Science Engineers, Inc. (ASE)'s soil and groundwater assessment at the Oakland Truck Stop located at 8255 San Leandro Street in Oakland, California (Figure 1). The proposed site assessment activities were initiated by Mr. Nissan Saidian, owner of the property, to meet the requirements of the Alameda County Health Care Services Agency (ACHCSA) outlined in their letter dated October 4, 1999 (Appendix A).

#### 2.0 SCOPE OF WORK (SOW)

Based on the requirements of the ACHCSA outlined in their letter dated October 4, 1999, ASE's SOW was as follows:

- 1) Prepare a workplan and health and safety plan for the site.
- 2) Obtain a drilling permit from the Alameda County Public Works Agency (ACPWA).
- 3) Drill two (2) soil borings at the site.
- Analyze one soil sample collected from each soil boring at a CAL-EPA certified environmental laboratory for total petroleum hydrocarbons as gasoline (TPH-G) by modified EPA Method 5030/8015M, total petroleum hydrocarbons as diesel (TPH-D) and motor oil (TPH-MO) by modified EPA Method 3510/8015M, benzene, toluene, ethylbenzene and total xylenes (collectively known as BTEX) by EPA Method 8020 and methyl tertiary butyl ether (MTBE) by EPA Method 8020.
- 5) Install 2-inch diameter groundwater monitoring wells in each boring described in task 3.
- 6) Develop each new monitoring well using surge block agitation and pump and/or bailer evacuation.
- 7) Collect groundwater samples from each of the six site monitoring wells for analyses.
- 8) Analyze the groundwater samples at a CAL-EPA certified analytical laboratory for TPH-G, TPH-D, TPH-MO, BTEX and MTBE. In addition, the groundwater sample collected from monitoring well MW-4 will

also be analyzed for dissolved lead by EPA Method 6010, and MTBE will be confirmed in the groundwater sample collected from monitoring well MW-3 by EPA Method 8260.

- 9) Survey the top of casing elevation of each well relative to the existing site wells, and determine the groundwater flow direction and gradient beneath the site.
- 10) Prepare a report detailing the methods and findings of this assessment.

Details of this assessment follow.

#### 3.0 DRILLING SOIL BORINGS AND COLLECTING SAMPLES

#### 3.1 Drilling and Collection of Soil Samples

Prior to drilling, ASE obtained an Alameda County Public Works Agency (ACPWA) drilling permit (Appendix B). ASE also notified Underground Service Alert (USA) to have underground public utilities in the vicinity of the site marked prior to drilling.

On December 1, 1999, Gregg Drilling of Martinez, California drilled soil borings MW-5 and MW-6 at the site using a Mobile B-61 drill rig equipped with 8-inch diameter hollow-stem augers (Figure 2). Groundwater monitoring wells MW-5 and MW-6 were subsequently constructed in these borings. The drilling was directed by ASE senior geologist Robert E. Kitay, R.G.

Undisturbed soil samples were collected at 5-foot intervals as drilling progressed for lithologic and hydrogeologic description and for possible chemical analyses. The samples were collected by driving a split-barrel drive sampler lined with 2-inch diameter brass tubes ahead of the auger tip with successive blows from a 140-lb. hammer dropped 30-inches. One tube from each sampling interval was immediately trimmed, sealed with Teflon tape, plastic end caps and duct tape, labeled, sealed in a plastic bag and stored on ice for transport to Chromalab, Inc. of Pleasanton, California (ELAP #1094) under chain of custody. Soil from the remaining tubes was described by an ASE geologist using the Unified Soil Classification System and was screened for volatile compounds with an Organic Vapor Meter (OVM). The soil was screened by emptying soil from one of the sample tubes into a plastic bag. The bag was then sealed and placed in the sun for approximately 10 minutes. After the

hydrocarbons were allowed to volatilize, the OVM measured the vapor in the bag through a small hole punched in the bag. OVM readings are used as a screening tool only, since the procedures are not as rigorous as those used in the laboratory.

Drilling equipment was steam-cleaned prior to use, and sampling equipment was washed with a TSP solution between sampling intervals to prevent cross-contamination. Steam cleaning rinsate and drill cuttings were contained in sealed and labeled 55-gallon steel drums and left on-site for temporary storage until off-site disposal can be arranged.

#### 3.2 Site Specific Geology

Sediments encountered during drilling generally consisted of silty clay from beneath the asphalt/concrete surface to 12-feet below ground surface (bgs) and sandy silt from 12-feet bgs to the total depth explored of 15-feet bgs. Groundwater was encountered at approximately 6-feet bgs. The boring logs and well construction details are included as Appendix C.

#### 4.0 ANALYTICAL RESULTS FOR SOIL

The soil samples collected from 6.0-feet bgs (the capillary zone) in each boring were analyzed by Chromalab, Inc. for TPH-G by modified EPA Method 5030/8015, TPH-D and TPH-MO by modified EPA Method 3510/8015 and BTEX and MTBE by EPA Method 8020. The analytical results are tabulated in Table One, and a copy of the certified analytical report and chain of custody form are included in Appendix D.

The soil sample collected from 6.0-feet bgs in boring MW-5 contained 17 parts per million (ppm) TPH-D. No TPH-G, TPH-MO, BTEX or MTBE were detected in this soil sample. The soil sample collected from 6.0-feet bgs in boring MW-6 contained 2.0 ppm TPH-G, 0.013 ppm total xylenes and 0.025 ppm MTBE. No TPH-D, TPH-MO, benzene, toluene or ethyl benzene were detected in this soil sample.

## 5.0 MONITORING WELL CONSTRUCTION, DEVELOPMENT AND SAMPLING

#### 5.1 Monitoring Well Construction

Groundwater monitoring wells MW-5 and MW-6 were constructed in borings MW-5 and MW-6, respectively. The wells were constructed with

2-inch diameter, 0.020-inch slotted, flush-threaded, schedule 40 PVC well screen and blank casing. The wells are screened between 4-feet bgs and 14-feet bgs to monitor the first water bearing zone encountered. Lonestar #2/12 Monterey sand occupies the annular space between the borehole and the casing from the bottom of the boring to approximately 1-foot above the well screen. A 0.5-foot thick hydrated bentonite layer separates the sand from the overlying cement surface seal. The wellhead is secured with a locking wellplug beneath an at-grade, traffic-rated vault.

#### 5.2 Monitoring Well Development

On December 3, 1999, ASE associated geologist Ian Reed developed monitoring wells MW-5 and MW-6 using multiple episodes of surge-block agitation and bailer and pump evacuation. Over ten well casing volumes of water were removed from each well during development, continued until the water was relatively evacuation development purge water was contained in sealed and labeled 55-gallon steel drums and left on-site for temporary storage until off-site disposal can be arranged. No free-floating hydrocarbons or sheen were present on of groundwater during well development. hydrocarbon odors were present in the purge water from both of these wells.

#### 5.3 Monitoring Well Sampling

On December 6, 1999, ASE associated geologist Ian Reed collected groundwater samples from monitoring wells MW-2, MW-3, MW-4, MW-5 and MW-6 for analysis. Monitoring well MW-1 contained 0.12-feet of free-floating hydrocarbons, and therefore, was not sampled. No free-floating hydrocarbons or sheen were present on the surface of groundwater in any other monitoring well. However, hydrocarbon odors were present in water purged from monitoring wells MW-3 and MW-6.

Prior to sampling, each well was purged of four well casing volumes of groundwater. The pH, temperature and conductivity of the purge water were monitored during evacuation, and samples were not collected until these parameters stabilized. Samples were collected from each well using dedicated polyethylene bailers. The groundwater samples to be analyzed for volatile compounds (TPH-G, BTEX and MTBE) were decanted from the bailers into 40-ml volatile organic analysis (VOA) vials, preserved with hydrochloric acid, and capped without headspace. The samples to be analyzed for TPH-D, TPH-MO and lead were contained in 1-liter amber glass containers. All of the samples were labeled and chilled with ice for

transport to Chromalab, Inc. of Pleasanton, California under chain of custody. The laboratory was instructed to filter and preserve the sample to be analyzed for dissolved lead immediately upon receipt. Well sampling purge water was contained in sealed and labeled 55-gallon steel drums and left on-site for temporary storage until off-site disposal can be arranged. See Appendix E for a copy of the Field Logs.

#### 6.0 GROUNDWATER ELEVATIONS

On December 6, 1999, ASE surveyed the top of casing elevation of monitoring wells MW-5 and MW-6 relative to the existing site monitoring wells. Depths to groundwater were measured in each site well prior to sampling on December 6, 1999 with an electric water level sounder. Top of casing elevations, depth to groundwater measurements and groundwater elevations are presented in Table Two, and groundwater elevation (potentiometric surface) contours are plotted on Figure 2.

On December 6, 1999, groundwater appeared to flow to the southwest beneath the site at a gradient of between approximately 0.017 and 0.067-feet/foot. This groundwater flow direction differs slightly from previous groundwater sampling events which showed a groundwater flow to the west. The current groundwater flow is more consistent with the distribution of hydrocarbons in the groundwater beneath the site.

#### 7.0 ANALYTICAL RESULTS FOR GROUNDWATER

The groundwater samples were analyzed by Chromalab for TPH-G by modified EPA Method 5030/8015, TPH-D and TPH-MO by modified EPA Method 3510/8015, and BTEX and MTBE by EPA Method 8020. The analytical results are tabulated in Tables Three and Four, and copies of the certified analytical report and chain of custody form are included in Appendix F.

High hydrocarbon concentrations, including 40,000 parts per billion (ppb) TPH-G, 16,000 ppb benzene, 1,800 ppb ethyl benzene and 4,000 ppb MTBE, were detected in groundwater samples from monitoring well MW-3. These benzene, ethyl benzene and concentrations exceeded the California Department of Health Services maximum contaminant levels (MCLs) for drinking Groundwater samples collected from monitoring well MW-6 contained 13,000 ppb TPH-G, although the BTEX and MTBE concentrations relatively moderate for TPH-G concentrations this high. Only the benzene concentration in groundwater samples collected from this well exceeded DHS MCLs for drinking water. Much lower hydrocarbon concentrations were detected in groundwater samples collected from the remaining wells, with only benzene concentrations in monitoring well MW-2 and MTBE concentrations in monitoring wells MW-4 and MW-5 exceeding DHS MCLs for drinking water.

#### 8.0 CONCLUSIONS AND RECOMMENDATIONS

The soil sample collected from 6.0-feet bgs in boring MW-5 contained 17 ppm TPH-D. No TPH-G, TPH-MO, BTEX or MTBE were detected in this soil sample. The soil sample collected from 6.0-feet bgs in boring MW-6 contained 2.0 ppm TPH-G, 0.013 ppm total xylenes and 0.025 ppm MTBE. No TPH-D, TPH-MO, benzene, toluene or ethyl benzene were detected in this soil sample. None of the concentrations detected in either of these borings exceeded United States Environmental Protection Agency (USEPA) preliminary remediation goals (PRGs) for residential soil.

Free-floating hydrocarbons are still present on the groundwater surface of monitoring well MW-1, although the thickness has decreased from last High hydrocarbon concentrations, including benzene, ethyl benzene and MTBE concentrations exceeding California Department Health Services (DHS) maximum contaminant levels (MCLs) for drinking water, were detected in groundwater samples collected from monitoring well MW-2. Benzene concentrations in groundwater samples collected from monitoring wells MW-2 and MW-6 exceeded DHS MCLs for drinking The MTBE concentration in groundwater samples collected from monitoring wells MW-3, MW-4 and MW-5 also exceeded DHS MCLs for drinking water. MTBE was confirmed in monitoring well MW-3 by EPA Method 8260. Most of these concentrations are similar to previous with no significant increases or decreases in hydrocarbon No dissolved lead was detected in groundwater samples collected from monitoring well MW-4 this quarter.

On December 6, 1999, groundwater appeared to flow to the southwest beneath the site at a gradient of between approximately 0.017 and 0.067-feet/foot. This groundwater flow direction differs slightly from previous groundwater sampling events which showed a groundwater flow to the west. The current groundwater flow is more consistent with the distribution of hydrocarbons in the groundwater beneath the site.

The downgradient extent of hydrocarbons south of monitoring well MW-3 has still not been defined. Another groundwater monitoring well will likely be required to further define the downgradient extent of

contamination. A limited access drill rig will be required for any further drilling south of monitoring well MW-3 due to overhead electrical lines.

ASE recommends continued quarterly groundwater monitoring at the site with no change in analyses for the next sampling period.

#### 9.0 REPORT LIMITATIONS

The results of this assessment represent conditions at the time of the soil and groundwater sampling, at the specific locations where the samples were collected, and for the specific parameters analyzed by the laboratory.

It does not fully characterize the site for contamination resulting from unknown sources, or for parameters not analyzed by the laboratory. All of the laboratory work cited in this report was prepared the direction of an independent CAL-EPA certified laboratory. The independent laboratory is solely responsible for the contents and conclusions of the chemical analysis data.

Aqua Science Engineers appreciates the opportunity to provide environmental consulting services for this project. Should you have any questions or comments, please feel free to call us at (925) 820-9391.

Respectfully submitted,

AQUA SCIENCE ENGINEERS, INC.

Robert E. Kitaly, R.G., R.E.A.

Senior Geologist


Ruhd, U. Kitay

Attachments: Figures 1 through 2


Appendices A through E

Oakland Truck Stop Report - December 1999

- / -







## LOCATION MAP

OAKLAND TRUCK STOP 8255 SAN LEANDRO STREET OAKLAND, CALIFORNIA

AQUA SCIENCE ENGINEERS, INC.

Figure 1

PROPERTY BOUNDARIES CAFE MW-5 (90.36') SAN LEANDRO STREET MW-4 DISPENSERS (90.62") **CID** FORMER WASTE-OIL UST TRUCK STATION! WASH AREA MARKET TRUCK 'ASTE-OIL SCALE (88.36)(90.29'\*)ESTIMATED GROUNDWATER FLOW DIRECTION UNDERGROUND FORMER STORAGE FUEL TANK USTo MW-3 FARM **.** (90.73') MW-6 (90.99)· B7 B9 LEGEND MW-4 MONITORING WELL WITH (90.62)POTENTIOMETRIC GROUNDWATER ELEVATION IN FEET, ABOVE MEAN SEA LEVEL SURFACE CONTOUR MAP DECEMBER 6, 1999 GROUNDWATER ELEVATION (90.29'\*)ADJUSTED FOR FREE-FLOATING OAKLAND TRUCK STOP HYDROCARBON THICKNESS 8255 SAN LEANDRO STREET NORTH OAKLAND, CALIFORNIA SCALE 1" = 50' POTENTIOMETRIC SURFACE **,**90. CONTOUR

AQUA SCIENCE ENGINEERS, INC.

Figure 2

## **TABLES**

**TABLE ONE** 

# Summary of Analysis of **SOIL** Samples Petroleum Hydrocarbons All results are in **parts** per million

Boring  MW-5 6.0'	TPH Gasoline < 1.0	TPH Diesel  17*	TPH Motor Oil < 50	Benzene < 0.0050	Toluene < 0.0050	Ethyl Benzene < 0.0050	Total Xylenes < 0.0050	MTBE< 0.0050
MW-6 6.0'	2.0**	< 1.0	< 50	< 0.0050	< 0.0050	< 0.0050	0.013	0.025
PRG	NE	NE	NE	0.62	520	230	210	NE

#### Notes:

Non-detectable concentrations are noted by the less than symbol (<) followed by the detection limit.

Detectable concentrations are in bold.

PRG is the United States Environmental Protection Agency preliminary remediation goal for residential soil.

NE = No PRG is established.

- \* = Non-typical diesel pattern.
- \*\* = Non-typical gasoline pattern.

TABLE TWO
Groundwater Elevation Data

Well I.D.	Top of Casing Elevation (msl)	Depth to Water Measurement (feet)	Free-Floating Hydrocarbon Thickness (feet)	Groundwater Elevation (msl)
MW-1				
8-16-99	97.12	Unknown	> 1.00	II a to a con-
8-27-99	91.12	6.90	0.36	Unknown 90.51*
9-10-99		6.85	0.18	90.31**
9-24-99		6.65	0.08	90.41**
10-08-99		6.87	0.28	90.47*
10-22-99		6.81	0.23	90.49*
11-02-99		6.94	0.31	90.43*
11-19-99		6.91	0.12	90.31*
12-06 <b>-</b> 99		6.93	0.12	90.29*
<u>MW-2</u>				
8-16-99	96.82	6.30		90.52
12-6-99		8.46		88.36
MW-3				
8-16-99	96.43	5.85	<b>.</b> _	90.58
12-6-99		5.70		90.73
MW-4				
8-16-99	96.60	6.12		90.48
12-6-99	, ,,,,	5.98	= +-	90.62
				70.02
<u>MW-5</u> 12-6-99	96.30	5.94		90.36
.2 0 ))	70.50	3.77		90.30
<u>MW-6</u>				
12-6-99	96.79	5.80		90.99

#### Notes:

<sup>\* =</sup> Groundwater elevation adjusted for the presence of free-floating hydrocarbons by the equation: Adjusted groundwater elevation = Top of casing elevation - depth to groundwater + (0.8 x free-floating hydrocarbon thickness)

TABLE THREE

## Summary of Chemical Analysis of GROUNDWATER Samples Petroleum Hydrocarbons

#### All results are in parts per billion

	TPH	TPH	TPH	_		Ethyl	Total	
Boring	Gasoline	Diesel	Motor Oil	Benzene	Toluene	Benzene	Xylenes	MTBE
MW-1 8-16-99 12-6-99					oating Hydi			
<u>MW-2</u> 8-16-99 12-6-99	2,200 1,900	970* 400*	< 500 < 500	3.8 16	< 2.0 < 0.5	3.0 1.5	< 4.0 < 0.5	< 20 5.2
<u>MW-3</u> 8-16-99 12-6-99	56,000 40,000	10,000** 9,100*	< 500 < 500	17,000 16,000	2,600 140	2,600 1,800	1,200	6,100 2,200/ 4,000#
<u>MW-4</u> 8-16-99 12-6-99	61*** 130***	1,100* 220*	< 500 < 500	< 0.5 < 1.0	< 0.5 < 1.0	< 0.5 < 1.0	< 1.0 < 1.0	8 6 1 3 0
<u>MW-5</u> 12-6-99	450***	2,000*	< 500	< 1.0	< 1.0	< 1.0	< 1.0	2 1
<u>MW-6</u> 12-6-99	13,000	< 50	< 500	180	2 1	1 1	2 4	< 100
DHS MCL	NE	NE	NE	1.0	150	700	1,750	13

#### Notes:

Non-detectable concentrations are noted by the less than symbol (<) followed by the detection limit.

Detectable concentrations are in bold.

DHS MCL is the California Department of Health Services maximum contaminant level for drinking water.

NE = DHS MCLs are not established.

- \* = Non-typical diesel pattern, hydrocarbons in early diesel range.
- \*\* = Estimated concentration due to overlapping fuel patterns in the sample.
- \*\*\* = Non-typical gasoline pattern.
- # = MTBE concentration by EPA Method 8260

TABLE FOUR
Summary of Chemical Analysis of GROUNDWATER Samples
HVOCs, SVOCs, PCBs and LUFT 5 Metals
All results are in parts per billion

Boring	Isoproyl- benzene	Other VOCs	SVOCs	PCBs	Cđ	Cr	Рb	Ni	Zn
14377.0									
<u>MW-2</u> 8-16-99	1 1	ND	ND	ND	< 2.0 .	9.0	< 5.0	19	< 10
<u>MW-4</u>									
8-16-99	< 0.5	ND	ND	ND	2.7	4 5	260	5 5	3 2 0
12-6-99							< 5		
MCL	NE	Various	Various	0.5	5	50	15	100	5,000

#### Notes:

Non-detectable concentrations are noted by the less than symbol (<) followed by the detection limit or are indicated by ND if various detection limits are used for multiple compounds. Please see the original reports for detection limits for these compounds..

Detectable concentrations are in bold.

MCL is the California Department of Health Services maximum contaminant level for drinking water.

NE = Not established

## APPENDIX A

ACHCSA Letter

#### HEALTH CARE SERVICES





DAVID J. KEARS, Agency Director

October 4, 1999 StID # 559

Mr. Nissan Saidian 5733 Medallion Court Castro Valley, CA 94522 **ENVIRONMENTAL HEALTH SERVICES** 1131 Harbor Bay Parkway, Suite 250 Alameda, CA 94502-6577 (510) 567-6700 (510) 337-9335 (FAX)

Re: Oakland Truck Stop, 8255 San Leandro St., Oakland CA 94621

Dear Mr. Saidian

Our office has received and reviewed the September 22, 1999 Quarterly Groundwater Monitoring Report for the above site as prepared by Aqua Science Engineers Inc. (ASE). As you are aware, groundwater sampling and analysis was performed on wells MW-2, MW-3 and MW-4. Free product, encountered in MW-1, was bailed on several occasions in an attempt to remove the product. Based upon the sampling results and those of the prior soil and groundwater investigation, ASE has made a number of recommendations. Our office has the following comments to the ASE recommendations:

- ASE recommends the removal of free product from MW-1 every two weeks until no further free product is observed for a one-month period. This is acceptable. You should be aware that the initial free product removals were approved by our office prior to being done.
- Additional subsurface investigation is recommended in the area south of boring B-8. Our office agrees with this in addition to requesting additional investigation north of MW-1 and the dispensers. It appears that two additional monitoring wells would be required.
- ASE recommends and our office approves running only lead in the water sample from MW-
- ASE recommends running BTEX and MTBE by EPA Method 8020 as a cost savings measure. Prior to doing this, you must confirm the presence of MTBE in that well exhibiting the highest concentration via EPA Method 8020 ie MW-3.
- ASE recommends and our office concurs continuing quarterly monitoring at this site.

Please provide a work plan for this additional investigation along with your next groundwater monitoring report.

You may contact me at (510) 567-6765 if you have any questions

Sincerely,

Dervey Cli Wic Barney M. Chan

Hazardous Materials Specialist

C: B. Chan, files

Mr. R. Kitay, ASE, 208 W. El Pintado, Danville, CA 94526

Mon8255SLSt

## APPENDIX B

Drilling Permit



## ALAMEDA COUNTY PUBLIC WORKS AGENCY

WATER RESOURCES SECTION PHONE (510) 670-5248 ALVIN KAN FAX (510) 610-5262

DRILLING PERMI	T APPLICATION
OCATION OF PROJECT ON HAND Truste Stop 8255 San Lander Struct	FOR OFFICE USE  PERMIT NUMBER 99 WR68  WELL NUMBER
on Klane, EA	PERMIT CONDITIONS
Californis Captalinates Source N COB n. Accountly # (1)	Circled Permit Requirements Apply
CLIENT Name Nissan Saision Address 5733 Natallica Ct Phone Address 5733 Natallica Ct Phone Civ Lastra Valley Cd Zip 24572  APPLICANT Name Assar Valley Cd Zip 24572  Address 268 Elect Ed Ciotado Phone (25) 830-387  Civ Daovilley Cd Zip 94524  Type Of Project Well Construction Gagtschnical lovassigation Cathodis Protection G Contemination G Water Supply G C Contemination G Water Supply G	A. GENERAL  1. A permit application should be submitted so as to arrive at the ACPWA office five days prior to proposed starting date.  2. Audmit to ACPWA within 60 days after compission of permitted work the original Department of Water Resources Water Well Drillers Report or equivalent for well projects, or drilling logs and location sketch for content is void if project not begun within 90 days of approval date.  3. WATER SUPPLY WELLS  1. Minimum surface seal thickness is two inches of coment grout placed by womic.  2. Minimum scal depth is 30 feet for municipal and industrial wells or 20 feet for municipal and industrial wells or 20 feet for municipal and wells unless a losser depth is specially approved.  C. GROUNDWATER MONITORING WELLS  1. Minimum surface seal thickness is two inches of cement grout placed by tremic.  2. Minimum seal depth for monitoring wells is the maximum dopth practicable or 20 feet.  D. GEOTECHNICAL  Backfill bors hole with compacted cuttings or heavy beneate and spear two feet with compacted material. In access of known or suspected contamination, tramed coment grout shall be used in place of compacted entitings.  E. CATHODIC  Fill hole above anode tong with concrete placed by tremis.
Orill Hole Diameter O in. Maximum Casing Diameter 2 in. Dooth 25 (4. Surface Scal Depth 4 ft. Number 2	f. Well destruction Sec Misched.
CEOTECHNICAL PROJECTS  Number of Borings Maximum  Koto Diameter In. Depth 1.  ESTIMATED STARTING DATE 11-30-99  ESTIMATED COMPLETION DATE 11-30-99  I hereby agree to comply with all requirements of this permit and Alamedo County Ordinance No. 73-68.	G. SPECIAL CONDITIONS  APPROVED HOMBER Cold DATE 1-29

NOU 29 1999 11:51

APPLICANT'S SIONATURE

C. Kary DATE 11-29-99

9258374853

PAGE.01

## APPENDIX C

Boring Logs and Well Construction Details

Project Name: Oakland Truck Stop  Project Location: 8225 San Leandro Street, Oakland, CA  Page 1 of 1  Driller: Gregg Drilling  Logged By: Robert E. Kitay, R.G.  Date Drilled: December 1, 1999  Checked By: Robert E. Kitay, R.G.  WATER AND WELL DATA  Depth of Water First Encountered: 5.8'  Static Depth of Water in Boring: 5.94'  Total Depth of Boring: 15'  Type and Size of Drill: 8.0" Diameter  Well Screen Type and Diameter: 2" Diameter PVC Casing  Well Screen Siot Size: 0.020"  Type and Size of Soil Sampler: 2.0" I.D. Split-Barrel Sampler  DESCRIPTION OF LITHOLOGY  Standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation.  O Concrete  Gravelly SAND (SW); clive brown; medium dense; damy; 50% fine to course sand; 30% subangular to subrounded gravel to 2" diameter; 20% silt; non-plastic; medium estimated K; moderate plasticity; no odor slight hydrocarbon odor  Silty CLAY (CH); black; medium stiff; wet; 70% clay; 30% silt; high plasticity; very low estimated K; slight hydrocarbon odor  Silty SAND/Sandy SILT (SP/ML); brown; medium dense; damsol, silt; non-plastic; low estimated K; no odor slight hydrocarbon odor  Silty SAND/Sandy SILT (SP/ML); brown; medium dense/sight hydrocarbon odor  Silty SAND/Sandy SILT (SP/ML); brown; medium dense/sight hydrocarbon odor  Silty SAND/Sandy SILT (SP/ML); brown; medium dense/sight hydrocarbon odor  Silty SAND/Sandy SILT (SP/ML); brown; medium dense/sight hydrocarbon odor  Silty SAND/Sandy SILT (SP/ML); brown; medium dense/sight hydrocarbon odor  Silty SAND/Sandy SILT (SP/ML); brown; medium dense/sight hydrocarbon odor  Silty SAND/Sandy SILT (SP/ML); brown; medium dense/sight hydrocarbon odor  Bottom of boring at 15'									
Driller: Gregg Drilling  Type of Rig: Hollow-Stem Auger  Logged By: Robert E. Kitay, R.G.  Date Drilled: December 1, 1999  Checked By: Robert E. Kitay, R.G.  WATER AND WELL DATA  Depth of Water First Encountered: 5.8'  Static Depth of Water in Boring: 5.94'  Total Depth of Boring: 15'  Type and Size of Soil Sampler: 2.0" I.D. Split-Barrel Sampler  BORING DETAIL  BORING DETAIL  BORING DETAIL  Soil Province Sample Data  BORING DETAIL  Soil Province Sample Data  BORING DETAIL  Soil Province Sample Data  Soil Province Sample Data  Soil Province Sample Data  BORING DETAIL  Soil Province Sample Data  Soil Province Sample Data  BORING DETAIL  Soil Province Sample Data  Soil Province Sample Data  DESCRIPTION OF LITHOLOGY  standard classification, texture, relative moisture, density, sliffness, odor-staining, USCS designation.  Concrete  Gravelly SAND (SW); olive brown; medium dense; damp; 50% fine to course sand; 30% subangular to subrounded gravel to 2" diameter; 20% silt; non-plastic; medium estimated K; moderate plasticity; no odor  slight hydrocarbon odor at 5'  wet at 5.8'  Silty CLAY (CH); black; medium stiff; wet; 70% clay; 30% silt; high plasticity; very low estimated K; soldense/sliff; wet; 40-60% fine sand; 40-60% silt; non-plastic; low estimated K; no odor  Bottom of boring at 15'	SOIL BORING LOG AND MONITORING WELL COMPLETION DETAILS   Well MW-5								
Logged By: Robert E. Kitay, R.G.  WATER AND WELL DATA  Depth of Water First Encountered: 5.8'  Static Depth of Water in Boring: 5.94'  Total Depth of Boring: 15'  Type and Size of Soil Sampler: 2.0" I.D. Split-Barrel Sampler  BORING DETAIL  BORING DETAIL  SOIL/ROCK SAMPLE DATA  DESCRIPTION OF LITHOLOGY  standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation.  O Concrete  Gravelly SAND (SW); olive brown; medium dense; damp; 50% fine to course sand; 30% subangular to subrounded gravel to 2" diameter; 20% silt; non-plastic; medium estimated K; moderate plasticity; non-plastic; medium estimated K; slight hydrocarbon odor  Silty SAND/Sandy SILT (SP/ML); brown; medium dense; dense/stiff; wet; 40-80% fine sand; 40-60% silt; non-plastic; low estimated K; no odor  Bottom of boring at 15'	Project Name: Oakland Truck Stop	Project Loc							
WATER AND WELL DATA  Depth of Water First Encountered: 5.8'  Well Screen Type and Diameter: 2" Diameter PVC Casing  Static Depth of Water in Boring: 5.94'  Well Screen Slot Size: 0.020"  Total Depth of Boring: 15'  Type and Size of Soll Sampler: 2.0" I.D. Split-Barrel Sampler  DESCRIPTION OF LITHOLOGY  standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation.  O Concrete  Gravelly SAND (SW); olive brown; medium dense; damp; 50% fine to course sand; 30% subangular to subrounded gravel to 2" diameter; 20% silt; non-plastic; medium estimated K; moderate plasticity; no odor  Silty SAND/Sandy SILT (SP/ML); brown; medium dense/stliff; wet; 40-60% fine sand; 40-60% silt; non-plastic; low estimated K; no odor  Silty SAND/Sandy SILT (SP/ML); brown; medium dense/stliff; wet; 40-60% fine sand; 40-60% silt; non-plastic; low estimated K; no odor  Silty SAND/Sandy SILT (SP/ML); brown; medium dense/stliff; wet; 40-60% fine sand; 40-60% silt; non-plastic; low estimated K; no odor  Silty SAND/Sandy SILT (SP/ML); brown; medium dense/stliff; wet; 40-60% fine sand; 40-60% silt; non-plastic; low estimated K; no odor	Driller: Gregg Drilling	Type of Rig: I							
Depth of Water First Encountered: 5.8'  Static Depth of Water in Boring: 5.94'  Total Depth of Boring: 15'  Type and Size of Soil Sampler: 2.0" I.D. Split-Barrel Sampler  Type and Size of Soil Sampler: 2.0" I.D. Split-Barrel Sampler  DESCRIPTION OF LITHOLOGY  standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation.  O Concrete  Gravelly SAND (SW); olive brown; medium dense; damp; 50% fine to course sand; 30% subangular to subrounded gravel to 2" diameter; 20% silt; non-plastic; medium estimated K; moderate plasticity; no odor slight hydrocarbon odor at 5" wet at 5.8"  Silty CLAY (CH); black; medium stiff; wet; 70% clay; 30% silt; high plasticity; very low estimated K; slight hydrocarbon odor  Silty SAND/Sandy SILT (SP/ML); brown; medium dense; dense/stiff; wet; 40-60% fine sand; 40-60% silt; non-plastic; low estimated K; no odor  Bottom of boring at 15'	Logged By: Robert E. Kitay, R.G.	Date Drilled:	December 1, 1999 Checked By: Robert E. Kitay, R.G.						
Static Depth of Water in Boring: 5.94'  Total Depth of Boring: 15'  SOIL/ROCK SAMPLE DATA  BORING DETAIL  BORING DETAIL  SOIL/ROCK SAMPLE DATA  DESCRIPTION OF LITHOLOGY  standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation.  Concrete  Gravelly SAND (SW); olive brown; medium dense; damp; 50% fine to course sand; 30% subangular to subrounded gravel to 2" diameter; 20% silt; non-plastic; medium estimated K; moderate plasticity; no odor slight hydrocarbon odor  Silty CLAY (CH); black; medium stiff; wet; 70% clay; 30% silt; high plasticity; very low estimated K; slight hydrocarbon odor  Silty SAND/Sandy SILT (SP/ML); brown; medium dense; damp; 50% fine to course sand; 30% subangular to subrounded gravel to 2" diameter; 20% silt; non-plastic; medium estimated K; moderate plasticity; no odor slight hydrocarbon odor  Silty SAND/Sandy SILT (SP/ML); brown; medium dense/sliff; wet; 40-60% fine sand; 40-60% silt; non-plastic; low estimated K; no odor  Bottom of boring at 15'	WATER AND WELL DATA		Total Depth of Well Completed: 15'						
Total Depth of Boring: 15'  Type and Size of Soil Sampler: 2.0" I.D. Split-Barrel Sampler  DESCRIPTION OF LITHOLOGY  standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation.  O Concrete  Gravelly SAND (SW); olive brown; medium dense; damp; 50% fine to course sand; 30% subangular to subrounded gravel to 2" dlameter; 20% silt; non-plastic; medium estimated K; moderate plasticity; no odor slight hydrocarbon odor at 5" wet at 5.8"  Silty CLAY (CH); black; medium stiff; wet; 70% clay; 30% silt; high plasticity; very low estimated K; slight hydrocarbon odor  Silty SAND/Sandy SILT (SP/ML); brown; medium dense; damp; 50% fine sand; 40-60% silt; non-plastic; low estimated K; slight hydrocarbon odor  Silty SAND/Sandy SILT (SP/ML); brown; medium dense; damp; 50% fine sand; 40-60% silt; non-plastic; low estimated K; no odor  Bottom of boring at 15'	Depth of Water First Encountered: 5.6	3'	Well Screen Type and Diameter: 2" Diameter PVC Casing						
BORING DETAIL FIND ON	Static Depth of Water in Boring: 5.94		Well Screen Slot Size: 0.020"						
BORING DETAIL  Street Box Locking Well  Street									
Street Box Locking Well  The street Box Locking Boy			DESCRIPTION OF LITHOLOGY						
Gravelly SAND (SW); olive brown; medium dense; damp; 50% fine to course sand; 30% subangular to subrounded gravel to 2" diameter; 20% silt; non-plastic; medium estimated K; moderate plasticity; no odor slight hydrocarbon odor at 5' wet at 5.8'  Silty CLAY (CH); black; medium stiff; wet; 70% clay; 30% silt; high plasticity; very low estimated K; slight hydrocarbon odor  Silty SAND/Sandy SILT (SP/ML); brown; medium dense; damp; 50% fine to course sand; 30% subangular to subrounded gravel to 2" diameter; 20% silt; non-plastic; medium estimated K; moderate plasticity; no odor slight hydrocarbon odor at 5' wet at 5.8'  Silty CLAY (CH); black; medium stiff; wet; 70% clay; 30% silt; high plasticity; very low estimated K; slight hydrocarbon odor  Silty SAND/Sandy SILT (SP/ML); brown; medium dense; damp; 50% fine to course sand; 30% subangular to subrounded gravel to 2" diameter; 20% silt; non-plastic; wet at 5.8'  Silty CLAY (CH); black; medium stiff; wet; 70% clay; 30% silt; high plasticity; very low estimated K; slight hydrocarbon odor  Silty SAND/Sandy SILT (SP/ML); brown; medium dense; damp; 50% fine to course sand; 30% subangular to subrounded gravel to 2" diameter; 20% silt; non-plastic; medium estimated K; moderate plasticity; no odor slight hydrocarbon odor	Depth in Depth in Description	Water Leve Graphic Log	standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation.						
-30 0.020 -30 -30	D. 0.020" Slotted PVC Well Screen Bentonite Seal 2" ID Blank Sch 40 PVC In Sea Supply	5	Gravelly SAND (SW); olive brown; medium dense; damp; 50% fine to course sand; 30% subangular to subrounded gravel to 2" diameter; 20% silt; non-plastic; medium estimated K; moderate plasticity; no odor slight hydrocarbon odor at 5' wet at 5.8'  Silty CLAY (CH); black; medium stiff; wet; 70% clay; 30% silt; high plasticity; very low estimated K; slight hydrocarbon odor  Silty SAND/Sandy SILT (SP/ML); brown; medium dense/stiff; wet; 40-60% fine sand; 40-60% silt; non-plastic; low estimated K; no odor  Bottom of boring at 15'						

		COMPLETION DETAILS
SOIL BORING LOG AND MONIT	ORING WELL	COMPLETION DETAILS   Well MW-6
Project Name: Oakland Truck Stop	Project Loc	eation: 8225 San Leandro Street, Oakland, CA Page 1 of 1
Driller: Gregg Drilling	Type of Rig: I	Hollow-Stem Auger   Size of Drill: 8.0" Diameter
Logged By: Robert E. Kitay, R.G.	Date Drilled:	December 1, 1999 Checked By: Robert E. Kitay, R.G.
WATER AND WELL DATA		Total Depth of Well Completed: 15'
Depth of Water First Encountered: 12	2.3'	Well Screen Type and Diameter: 2" Diameter PVC Casing
Static Depth of Water in Boring: 5.80	·	Well Screen Slot Size: 0.020"
Total Depth of Boring: 15'		Type and Size of Soil Sampler: 2.0" I.D. Split-Barrel Sampler
\( \)   \( \	SAMPLE DATA	DESCRIPTION OF LITHOLOGY
Description Interval low Counts	Level hic	standard classification, texture, relative moisture,
Depth in Fe Description Descri	Water Level Graphic Log	standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation.
	2   ≥	
-0 ← Street Box - Locking Well Ca	р	Asphaltic Concrete Silty CLAY (CH); black; medium stiff; damp; 80% clay;
- XX XX 5 5		20% silt; high plasticity; very low estimated K; no odor
11111 Sch 40 PVC  8 9 9 9		
- 5 4 4 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5		slight hydrocarbon odor at 4'
Blank Sch  "H" Portlan	, <u>Z</u>	_
- 1000000 PANOS - 1 1 1		_
	68	moderate hydrocarbon odor at 9'
		<b>-</b> 10
Seal and	Ţ	Sandy SILT (ML); olive brown; medium stiff; wet; 60%
	48	silt; 40% fine sand; non-plastic; low estimated K;
Bentonite S, 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3		1 5 strong hydrocarbon odor
		Bottom of boring at 15'
l led		<b>-</b>
Well Screen Benton		-20
ell §		
NO. N		F
2 4		
<b>-</b> 25		<b>-</b> 25
[		
- 0.02(		- 1
2" I.D. 0.020" Slotted PVC Well Screen		30
[N]		
		aqua science engineers, inc.

## APPENDIX D

Analytical Report and Chain of Custody Form For Soil Samples Environmental Services (SDB)

Submission #: 1999-12-0037

Date: December 9, 1999

Aqua Science Engineers, Inc.

208 West El Pintado Road Danville, CA 94526

Attn.: Mr. Robert Kitay

Project: 3540

Oakland Truck Stop

Dear Mr. Kitay,

Attached is our report for your samples received on Thursday December 2, 1999 This report has been reviewed and approved for release. Reproduction of this report is permitted only in its entirety.

Please note that any unused portion of the samples will be discarded after January 1, 2000 unless you have requested otherwise. We appreciate the opportunity to be of service to you. If you have any questions, please call me at (925) 484-1919

Sincerely,

Asanch. Salin pon Vincent Vancil **Environmental Services (SDB)** 

#### Gas/BTEX and MTBE

Aqua Science Engineers, Inc.

⊠ 208 West El Pintado Road

Danville, CA 94526

Attn: Robert Kitay

Phone: (925) 820-9310 Fax: (925) 837-4853

Project #: 3540

Project: Oakland Truck Stop

#### Samples Reported

Sample ID	Matrix	Date Sampled	Lab#
MW-5 6.0`	Soil	12/01/1999 10:30	1
MW-6 6.0`	Soil	12/01/1999 13:10	2

Submission #: 1999-12-0037

**Environmental Services (SDB)** 

To: Aqua Science Engineers, Inc. Test Method:

8020

8015M

Attn.: Robert Kitay

Prep Method:

5030

Gas/BTEX and MTBE

Sample ID:

MW-5 6.0`

Lab Sample ID: 1999-12-0037-001

Project:

3540

Received:

12/02/1999 16:33

Oakland Truck Stop

Extracted:

12/06/1999 12:03

Sampled:

12/01/1999 10:30

QC-Batch:

1999/12/06-01.04

Matrix:

Soil

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Gasoline	ND	1.0	mg/Kg	1.00	12/06/1999 12:03	
Benzene	ND	0.0050	mg/Kg	1.00	12/06/1999 12:03	
Toluene	ND	0.0050	mg/Kg	1.00	12/06/1999 12:03	
Ethyl benzene	ND	0.0050	mg/Kg	1.00	12/06/1999 12:03	
Xylene(s)	ND	0.0050	mg/Kg	1.00	12/06/1999 12:03	
MTBE	ND	0.0050	mg/Kg	1.00	12/06/1999 12:03	
Surrogate(s)	ļ					
Trifluorotoluene	61.0	53-125	%	1.00	12/06/1999 12:03	
4-Bromofluorobenzene-FID	59.1	58-124	%	1.00	12/06/1999 12:03	

Submission #: 1999-12-0037

**Environmental Services (SDB)** 

To: Aqua Science Engineers, Inc.

Test Method:

8020

8015M

Attn.: Robert Kitay

Prep Method:

5030

Gas/BTEX and MTBE

Sample ID:

MW-6 6.0°

Lab Sample ID: 1999-12-0037-002

Project:

3540

Received:

12/02/1999 16:33

Oakland Truck Stop

Extracted:

12/04/1999 19:12

Sampled:

12/01/1999 13:10

QC-Batch:

1999/12/04-01.01

Matrix:

Soil

Sample/Analysis Flag: \*S\* ( See Legend & Note section )

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Gasoline	2.0	1.0	mg/Kg	1.00	12/04/1999 19:12	g
Benzene	ND	0.0050	mg/Kg	1.00	12/04/1999 19:12	-
Toluene	ND	0.0050	mg/Kg	1.00	12/04/1999 19:12	
Ethyl benzene	ND	0.0050	mg/Kg	1.00	12/04/1999 19:12	
Xylene(s)	0.013	0.0050	mg/Kg	1.00	12/04/1999 19:12	
MTBE	0.025	0.0050	mg/Kg	1.00	12/04/1999 19:12	
Surrogate(s)						
4-Bromofluorobenzene	67.1	58-124	%	1.00	12/04/1999 19:12	
Trifluorotoluene-FID	131.9	53-125	%	1.00	12/04/1999 19:12	sh

Submission #: 1999-12-0037

Environmental Services (SDB)

To: Aqua Science Engineers, Inc.

Test Method: 8

8020

8015M

Attn.: Robert Kitay

Prep Method: 50

5030

Batch QC Report
Gas/BTEX and MTBE

Method Blank

Soil

QC Batch # 1999/12/04-01.01

MB:

1999/12/04-01.01-001

Date Extracted: 12/04/1999 06:30

Compound	Result	Rep.Limit	Units	Analyzed	Flag
Gasoline	ND	1.0	mg/Kg	12/04/1999 06:30	
Benzene	ND	0.0050	mg/Kg	12/04/1999 06:30	
Toluene	ND	0.0050	mg/Kg	12/04/1999 06:30	
Ethyl benzene	ND	0.0050	mg/Kg	12/04/1999 06:30	
Xylene(s)	ND	0.0050	mg/Kg	12/04/1999 06:30	
MTBE	ND	0.0050	mg/Kg	12/04/1999 06:30	
Surrogate(s)					
Trifluorotoluene	107.0	53-125	%	12/04/1999 06:30	
4-Bromofluorobenzene-FID	73.8	58-124	%	12/04/1999 06:30	

Submission #: 1999-12-0037

**Environmental Services (SDB)** 

To: Aqua Science Engineers, Inc. Test Method:

8020

Attn.: Robert Kitay

Prep Method:

8015M 5030

**Batch QC Report** Gas/BTEX and MTBE

Method Blank

Soil

QC Batch # 1999/12/06-01.04

MB:

1999/12/06-01.04-001

Date Extracted: 12/06/1999 05:56

Compound	Result	Rep.Limit	Units	Analyzed	Flag
Gasoline	ND	1.0	mg/Kg	12/06/1999 05:56	
Benzene	ND	0.0050	mg/Kg	12/06/1999 05:56	
Toluene	ND	0.0050	mg/Kg	12/06/1999 05:56	
Ethyl benzene	ND	0.0050	mg/Kg	12/06/1999 05:56	
Xylene(s)	ND	0.0050	mg/Kg	12/06/1999 05:56	
MTBE	ND	0.0050	mg/Kg	12/06/1999 05:56	
Surrogate(s)					
Trifluorotoluene	68.2	53-125	%	12/06/1999 05:56	
4-Bromofluorobenzene-FID	79.0	58-124	%	12/06/1999 05:56	

Environmental Services (SDB)

To: Aqua Science Engineers, Inc.

Test Method:

8020

Submission #: 1999-12-0037

8015M

Attn: Robert Kitay

Prep Method:

5030

**Batch QC Report** 

Gas/BTEX and MTBE

Laboratory Control Spike (LCS/LCSD)

Soil

QC Batch # 1999/12/04-01.01

LCS:

1999/12/04-01.01-002

Extracted: 12/04/1999 06:58

Analyzed: 12/04/1999 06:58

LCSD:

1999/12/04-01.01-003

Extracted: 12/04/1999 07:26

Analyzed: 12/04/1999 07:26

Compound	Conc.	[ mg/Kg ]	Exp.Conc.	[ mg/Kg ]	Recov	егу [%]	RPD	Ctrl. Lim	its [%]	Flag	js
	LCS	LCSD	LCS	LCSD	LCS	LCSD	[%]	Recovery	RPD	LCS	LCSD
Gasoline	0.500	0.398	0.500	0.500	100.0	79.6	22.7	75-125	35		
Benzene	0.110	0.113	0.1000	0.1000	110.0	113.0	2.7	77-123	35		
Toluene	0.113	0.116	0.1000	0.1000	113.0	116.0	2.6	78-122	35		
Ethyl benzene	0.113	0.115	0.1000	0.1000	113.0	115.0	1.8	70-130	35		
Xylene(s)	0.338	0.349	0.300	0.300	112.7	116.3	3.1	75-125	35	1	(
Surrogate(s)	ĺ										
Trifluorotoluene	548	553	500	500	109.6	110.6		53-125	'		
4-Bromofluorobenzene-FI	383	308	500	500	76.6	61.6		58-124	1		

1220 Quarry Lane \* Pleasanton, CA 94566-4756 Telephone: (925) 484-1919 \* Facsimile: (925) 484-1096

Submission #: 1999-12-0037

**Environmental Services (SDB)** 

To: Aqua Science Engineers, Inc.

Test Method: 8020

8015M

Attn: Robert Kitay

Prep Method:

5030

**Batch QC Report** 

Gas/BTEX and MTBE

Laboratory Control Spike (LCS/LCSD)

Soil

QC Batch # 1999/12/06-01.04

LCS:

1999/12/06-01.04-002

Extracted: 12/06/1999 06:24

Analyzed: 12/06/1999 06:24

LCSD:

1999/12/06-01.04-003

Extracted: 12/06/1999 06:52

Analyzed: 12/06/1999 06:52

Compound	Conc.	[ mg/Kg ]	Exp.Conc.	[ mg/Kg ]	Recovery [%]		RPD	Ctrl. Limits [%]		Flags	
	LCS	LCSD	LCS	LCSD	LCS	LCSD	[%]	Recovery	RPD	LCS	LCSD
Gasoline	0.505	0.479	0.500	0.500	101.0	95.8	5.3	75-125	35		
Benzene	0.0900	0.0895	0.1000	0.1000	90.0	89.5	0.6	77-123	35		
Toluene	0.0912	0.0902	0.1000	0.1000	91.2	90.2	1.1	78-122	35		
Ethyl benzene	0.0918	0.0914	0.1000	0.1000	91.8	91.4	0.4	70-130	35		
Xylene(s)	0.267	0.268	0.300	0.300	89.0	89.3	0.3	75-125	35		
Surrogate(s)					ĺ				į		
Trifluorotoluene	347	347	500	500	69.4	69.4		53-125			
4-Bromofluorobenzene-Fi	424	403	500	500	84.8	80.6		58-124			

**Environmental Services (SDB)** 

To: Aqua Science Engineers, Inc. Test M

Test Method: 8015M

8020

Submission #: 1999-12-0037

Attn:Robert Kitay Prep Method: 5030

Legend & Notes

Gas/BTEX and MTBE

**Analyte Flags** 

g

Hydrocarbon reported in the gasoline range does not match our gasoline standard.

sh

Surrogate recoveries were higher than QC limits due to matrix interference.

1220 Quarry Lane \* Pleasanton, CA 94566-4756 Telephone: (925) 484-1919 \* Facsimile: (925) 484-1096

Submission #: 1999-12-0037

Environmental Services (SDB)

#### Total Extractable Petroleum Hydrocarbons (TEPH)

Aqua Science Engineers, Inc.

208 West El Pintado Road

Danville, CA 94526

Attn: Robert Kitay

Phone: (925) 820-9310 Fax: (925) 837-4853

Project: Oakland Truck Stop

Project #: 3540

#### Samples Reported

Sample ID	Matrix	Date Sampled	Lab#
MW-5 6.0`	Soil	12/01/1999 10:30	1
MW-6 6.0`	Soil	12/01/1999 13:10	2

Submission #: 1999-12-0037

**Environmental Services (SDB)** 

Aqua Science Engineers, Inc. To:

Test Method:

8015M

Attn.: Robert Kitay

Prep Method:

3550/8015M

Total Extractable Petroleum Hydrocarbons (TEPH)

Sample ID: MW-5 6.0 Lab Sample ID: 1999-12-0037-001

Project:

3540

Received:

12/02/1999 16:33

Oakland Truck Stop

Extracted:

12/07/1999 08:00

Sampled:

12/01/1999 10:30

Matrix:

Soil

QC-Batch:

1999/12/07-01.10

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Diesel Motor Oil	17 ND	1.0 50	mg/Kg mg/Kg	1.00 1.00	12/08/1999 19:26 12/08/1999 19:26	ndp
Surrogate(s) o-Terphenyl	91.3	60-130	%	1.00	12/08/1999 19:26	

Submission #: 1999-12-0037

**Environmental Services (SDB)** 

Aqua Science Engineers, Inc. To:

Test Method:

8015M

Attn.: Robert Kitay

Prep Method:

3550/8015M

Total Extractable Petroleum Hydrocarbons (TEPH)

Sample ID: MW-6 6.0`

Lab Sample ID: 1999-12-0037-002

Project:

3540

Received:

12/02/1999 16:33

Oakland Truck Stop

Sampled:

12/01/1999 13:10

12/07/1999 08:00

Matrix:

Soil

Extracted: QC-Batch:

1999/12/07-01.10

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Diesel Motor Oil	ND ND	1.0 50	mg/Kg mg/Kg	1.00 1.00	12/08/1999 18:49 12/08/1999 18:49	
Surrogate(s) o-Terphenyl	78.1	60-130	%	1.00	12/08/1999 18:49	

Environmental Services (SDB)

Aqua Science Engineers, Inc.

Attn.: Robert Kitay

Test Method:

8015M

Prep Method:

3550/8015M

#### **Batch QC Report**

Total Extractable Petroleum Hydrocarbons (TEPH)

Method Blank

To:

Soil

QC Batch # 1999/12/07-01.10

Submission #: 1999-12-0037

MB:

1999/12/07-01.10-001

Date Extracted: 12/07/1999 08:00

Compound	Result	Rep.Limit	Units	Analyzed	Flag
Diesel	ND	1	mg/Kg	12/08/1999 15:08	
Motor Oil	ND	50	mg/Kg	12/08/1999 15:08	
Surrogate(s)					
o-Terphenyl	93.5	60-130	%	12/08/1999 15:08	

1220 Quarry Lane \* Pleasanton, CA 94566-4756 Telephone: (925) 484-1919 \* Facsimile: (925) 484-1096

Printed on: 12/09/1999 14:55

Submission #: 1999-12-0037

**Environmental Services (SDB)** 

To: Aqua Science Engineers, Inc.

Test Method: 8015M

Prep Method: 355

3550/8015M

Attn: Robert Kitay

**Batch QC Report** 

Total Extractable Petroleum Hydrocarbons (TEPH)

Laboratory Control Spike (LCS/LCSD)

Soil

QC Batch # 1999/12/07-01.10

LCS:

1999/12/07-01.10-002

Extracted: 12/07/1999 08:00

Analyzed: 12/08/1999 06:24

LCSD:

1999/12/07-01.10-003

Extracted: 12/07/1999 08:00

Analyzed: 12/08/1999 07:01

Compound	Conc.	[ mg/Kg ]	Exp.Conc.	[ mg/Kg ]	Recovery [%]		Recovery [%]		Recovery [%]		Recovery [%]		RPD	Ctrl. Lim	its [%]	Flag	]s
	LCS	LCSD	LCS	LCSD	LCS	LCSD	[%]	Recovery	RPD	LCS	LCSD						
Diesel Surrogate(s)	34.0	36.0	41.7	41.7	81.5	86.3	5.7	60-130	25								
o-Terphenyl	18.6	18.6	20.0	20.0	93.0	93.0		60-130									

Printed on: 12/09/1999 14:55

Environmental Services (SDB)

Test Method: 8015M

Prep Method: 3550/8015M

Submission #: 1999-12-0037

To: Aqua Science Engineers, Inc.

Attn:Robert Kitay

#### Legend & Notes

Total Extractable Petroleum Hydrocarbons (TEPH)

**Analyte Flags** 

ndp

Hydrocarbon reported does not match the pattern of our Diesel standard

Printed on: 12/09/1999 14:55

Aqua Science Engineers, Inc. 208 W. El Pintado Road Danville, CA 94526 (925) 820-9391 FAX (925) 837-4853

## Chain of Custody

7717. (020)																		PAG	E	<u></u> c	F _/	<i></i>
SAMPLER (SIGN					ONE NO.		PRO.	JECT N	IAME	<u>O</u>	Klan	1	True	<i>L</i> =	11-0						· ·	_
Rolf C. ANAL	Kita	- -		(925)8.	20-9:	39/	ADD	RESS	8255	Sar	Lew	ndro	Stre	<u>~</u> 2∤,	Oak	land,	CA	DATE	 - :	2-/-	9 9	
ANAL'	Y819	3 RE	QUES	T	, , , <u>, , , , , , , , , , , , , , , , </u>	1		1			İ			<del></del>				- 			_/_	T
SPECIAL INSTRU	ICTIONS	,			TPH-GAS / MTBE & BTEX (EPA 5030/8015-8020)	TPH-GASOLINE (EPA 5030/8015)	TPH-DIESEL + 1/1/10 C. ( (EPA 3510/8015)	PURGEABLE HALOCARBONS (EPA 601/8010)	PURGEABLE AROMATICS (EPA 602/8020)	VOLATILE ORGANICS (EPA 624/8240)	SEMI-VOLATILE ORGANICS (EPA 625/8270)	36	LUFT METALS (5) (EPA 6010+7000)	CAM 17 METALS (EPA 6010+7000)	PCBs & PESTICIDES (EPA 608/8080)	ORGANOPHOSPHORUS PESTICIDES (EPA 8140) (EPA 608/8080)	ORGANOCHLORINE HERBICIDES (EPA 8150)	FUEL OXYGENATES (EPA 8260)				<u> </u>
				<del></del>	AS / 1	A50L	IESE1 5510/	ABLE 01/8	ABLE 0278	LE OF 24/8	OLA1	KEA6 520)	ETAL 010+	' MET	& PE	NOP! CIDE 308,	NOCH	)XYG				COMPOSITE
SAMPLE ID.	DATE	TIME	MATRIX	NO. OF SAMPLES	TPH-G (EPA 5	TPH-G (EPA 5	TPH-D (EPA 3	PURGE (EPA 6	PURGE (EPA 6	VOLATI (EPA 6	SEMI-1 (EPA 6	OIL & GREASE (EPA 5520)	LUFT N (EPA 6	CAM 17 (EPA 6	PCBs (EPA 6	ORGA PESTI (EPA	ORGA HERBI	FUEL (				Ø 00 00 00
MW-5 60'	12/1/2	10:30	50,1	l	×		X															
AW-6 6.0'		13.10			X		×															
MW-6 9.5	1	13-20	V	<b>√</b>	H	OLL	a.	i pe	- <i>R</i>	eber	+ K.	13/E:	[act							<u> </u>		
												1-1										
			——										- <u></u> -						ļ			
			<del></del> -																ļ			
																			ļ <del></del> !			
																	- 1	·				
			·														7	7			<u> </u>	
				7),																		
RELINQUISHED BY KAN E. K (signature)			RECEIVE (signatu	EDEM	// (time)	3.20	(sigila	QUISHE Wre)		(time)	14.00	(gigna	IVED B'			4:00		1MENTS		Ti	g.T	-
Robert E. K printed name)	ital (date	12-2-9 =)	printed,	Me 1/47)	(date)	2/2	(printe	Abw/ ed name	TR	(date)	Z/Z	CR (print				02						ļ
Company- ASE			Compan	y- CÜRÖN			Compa	any-	1	<u>-</u> 1	77.4	Comp		<u>-</u>		<u> </u>						

## APPENDIX E

Well Sampling Field Logs



Project Name and Address:	Vakland Mick Stop
Job #:	Date of sampling: 12-6-99
Well Name: Mw-1	Sampled by:TR
Total depth of well (feet):	Sampled by: VTR Well diameter (inches): 2 "
Depth to water before sampling (fe	eet): 6.93 7: 0.12
Thickness of floating product if any	/: <u>0.12</u>
Depth of well casing in water (feet)	) <b>:</b>
Number of gallon's per well casing	volume (gallons):
Number of well caking volumes to	be removed:
Req'd volume of groundwater to be	purged before sampling (gallons).
Equipment used to purge the well:	
Time Evacuation Began:	Time Evacuation Finished:
Approximate volume of groundwate	er purged:
Did the well go dry?:	After how many gallons:
Time samples were collected:	
Depth to water at time of sampling	·• ·•——————————————————————————————————
Percent recovery at time of sampli	ng:
Samples collected with:	Odor:
Sample color:	Odor:
Description of sediment in sample:	
CHEMICAL DATA	<u>~</u>
Volume Purged Temp	Conductivity
	7 8
<u></u>	
SAMPLES COLLECTED	<b>\</b>
Sample # of containers Volume & type containers	ontainer Pres \ Iced? Analysis



Project Name and Address:	U	allowed T	ruck	·-·
Job #: Well Name: $\mu \omega^{-2}$	Date of samp	ling:	17. (c · 49.	
Well Name: MW-2	Sampled by:	11 1:	1320	
Total depth of well (feet):	15.30 We	II diameter	(inches): _	
Depth to water before samplin	g (1eet):	). <del>40</del>		
Thickness of floating product i	1 any:			
Depth of well casing in water Number of gallons per well ca	(leet):	<u>+.07</u>	7	
Number of gallons per well ca	sing volume (galle	ons):	1.2	
Number of well casing volume	s to be removed:			
Req'd volume of groundwater t	o be purged below	e sampling	(gallons):	<u> 418</u>
Equipment used to purge the	well:	created	baler	
Time Evacuation Began: 153. Approximate volume of ground	Time E	vacuation b	finished:	<u> 1340</u> _
Approximate volume of groun-	dwater purged:	· J · J · J	<u> </u>	
Did the well go dry?: Ne Time samples were collected:	After he	ow many g	gallons:	
lime samples were collected:				
Depth to water at time of sam	pling: <u> </u>	7		
Percent recovery at time of sa	impling:	70		
Depth to water at time of sam Percent recovery at time of sa Samples collected with: Sample color: Coor crow Description of sediment in sam	01112+1	8 20.121	<u>_</u>	
Sample color: Coov Green	Odor:	marc.		
Description of sediment in san	nple:	<u>/ ,                                   </u>		
CHEMICAL DATA				
Volume Purged Temp	pH,, Co	onductivity		
1 27.1	3.4.7 	¥ 1 x 1		
7 7! V 3 210 14 74 5	<u></u>	2.3		
		ン・3 		
4 14.5				
SAMPLES COLLECTED				
Sample # of containers Volume &	type container Pres I	Iced? Analy	<u>sis</u>	
1.50 2	Fer Any,			
			,	
		<del></del>	······································	





Project Name and Address: _	Dalland Truck STOP
Job #: Well Name: <u>MW- リ</u>	Sampled by:TK
Total depth of well (feet):	Vell diameter (inches): Z'
Depth to water before sampli	ng (feet): 5.98
Thickness of floating product	if any:
Depth of well casing in water	if any: r (feet):9.02
Number of gallons per well	casing volume (gallons): 1.5
Number of well casing volun	nes to be removed: 4
Req'd volume of groundwater	to be purged before sampling (gallons):
Equipment used to purge the	well: decidated Saylor
Time Evacuation Began: 14	60 Time Evacuation Finished: 1410
Approximate volume of grou	ndwater purged: 6
Did the well go dry?: No	After how many gallons:
Time samples were collected	After how many gallons:
Depth to water at time of sa	mpling: <u>599</u>
Dargant racquary at time of	nomenting.
Samples collected with:	Odor:
Sample color:	Odor:
	ample;
CHEMICAL DATA	
Volume Purged Temp	pH Conductivity
	<u>7.61</u> 561
72.3 71.9 72.0 71.7	7108
3 77.0	9.22 15.08
719	7.91
SAMPLES COLLECTED	
Sample, # of containers Volume &	type container Pres Iced? Analysis
	MY VOR
Mp. 4 2	l'hte And.
Mp-4 2 250	m pasin

# 

Project Name and Address	SS:	Oakland Tr	111/2 STOP	
JOD #:	Date	of sampling	12.6-	0.9
Job #:  Well Name: MW-5  Total depth of well (feet):  Depth to water before sa	Sam	pled by:	<u>ITR</u>	
Death to water before	13.7	Well di	ameter (inches):	2.
Depth to water before sa Thickness of floating prod Depth of well casing in w Number of gallons per w Number of well casing vo	mpling (leel):	394		
Depth of well casing in	uct ii any:			
Number of gallons per w	vater (leet):		/	
Number of well casing w	ell casing volu	ıme (gallons):	1,2,	
Req'd volume of groundw Equipment used to purge Time Evacuation Began:	ine wen	7,		
TAPPLOYIBLE OF A OTHER OF A	n annamarater n	nrad.	C = =;	
go diy::	C	Aller how a	many collons.	
Time samples were collected. Depth to water at time of Percent recovery at time Samples collected with:	ted:	6	ganons	
Depth to water at time of	sampling:	5.72		
Percent recovery at time	of sampling:_	~ a · l.		
Samples collected with:	<u>der</u>	and war		
Sample color:		Odor:1	lare	
Description of sediment is	ı sample:	<u></u>		
CHEMICAL DATA				
Volume Purged Ten	<u>pH</u>	Conduct	ivity	
<u> </u>	<u> </u>		_	
	· · · · · · · · · · · · · · · · · · ·			
SAMPLES COLLECTED				
Sample # of containers Volum	e & type containe	r <u>Pres Iced?</u>	<u>Analysis</u>	
	on Vok	- <u>- 12</u> - 12 - 12 - 12		
	18 0 Arma	<u> </u>		<del></del>
,		_		<del></del>



Project Name and Addres	s:Oa/a T(
Job #:	Date of sampling:
Well Name: MW-6	Date of sampling: Sampled by: Well diameter (inches):
Total depth of well (feet):	Well diameter (inches):
Depth to water before sar	mpling (feet): 5.3.  uct if any: 5.3.  later (feet): 5.3.  lumes to be removed: 4.
Thickness of floating prod	uct if any:
Depth of well casing in w	ater (feet):
Number of gallons per we	Il casing volume (gallons).
Number of well casing vo	lumes to be removed:
Req'd volume of groundwa	nter to be purged before sampling (gallons): 5.6
Equipment used to purge	the well:
Time Evacuation Began: 1	Time Evacuation Finished: 1270
Approximate volume of g	roundwater purged: 4 4
Did the well go dry?:	After how many gallons:
Time samples were collect	ted: 17.7:
Depth to water at time of	sampling: < %2
Percent recovery at time	of sampling:
Samples collected with:	Site had
Sample color:	Odor:
Description of sediment in	roundwater purged:  After how many gallons:  ted: 17.75  sampling: 5.37  of sampling: 18.7  Odor: V. 5.67  sample: 0.37
CHEMICAL DATA	
Volume Purged Ten	pH Conductivity
7:	p pH Conductivity
7 4	
<u> </u>	
SAMPLES COLLECTED	
	e & type container Pres Iced? Analysis  - file Analysis
····	

#### **APPENDIX F**

Analytical Report and Chain of Custody Form For Groundwater Samples **Environmental Services (SDB)** 

Submission #: 1999-12-0102

Date: December 14, 1999

Aqua Science Engineers, Inc.

208 West El Pintado Road Danville, CA 94526

Attn.: Mr. Ian T. Reed

Project: Oakland Truck Stop (OTS)

Dear Mr. Reed,

Attached is our report for your samples received on Monday December 6, 1999 This report has been reviewed and approved for release. Reproduction of this report is permitted only in its entirety.

Please note that any unused portion of the samples will be discarded after January 5, 2000 unless you have requested otherwise. We appreciate the opportunity to be of service to you. If you have any questions, please call me at (925) 484-1919

Sincerely,

Vincent Vancil

Environmental Services (SDB)

#### MTBE - Volatile Organics by GC/MS

Aqua Science Engineers, Inc.

⊠ 208 West El Pintado Road

Danville, CA 94526

Attn: Ian T. Reed

Phone: (925) 820-9391 Fax: (925) 837-4853

Project #:

Project: Oakland Truck Stop (OTS)

#### Samples Reported

Sample ID	Matrix	Date Sampled	Lab#
MW-3	Water	12/06/1999 12:55	2

Submission #: 1999-12-0102

Environmental Services (SDB)

Aqua Science Engineers, Inc. To:

Test Method:

8260A

Attn.: Ian T. Reed

Prep Method:

5030

MTBE - Volatile Organics by GC/MS

Sample ID: MW-3

Lab Sample ID: 1999-12-0102-002

Project:

Oakland Truck Stop (OTS)

Received:

12/06/1999 15:05

Extracted:

12/10/1999 13:46

Sampled:

12/06/1999 12:55

QC-Batch:

1999/12/10-01 06

Matrix:

ao Bato	1000/12/10-01.00

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
MTBE	4000	500	ug/L	100.00	12/10/1999 13:46	
Surrogate(s) 1,2-Dichloroethane-d4	104.9	76-114	%	1.00	12/10/1999 13:46	

Submission #: 1999-12-0102

**Environmental Services (SDB)** 

To: Aqua Science Engineers, Inc.

Test Method:

8260A

Attn.: Ian T. Reed

Prep Method:

5030

#### **Batch QC Report**

MTBE - Volatile Organics by GC/MS

Method Blank Water QC Batch # 1999/12/10-01.06

MB: 1999/12/10-01.06-001

Date Extracted: 12/10/1999 12:21

Compound	Result	Rep.Limit	Units	Analyzed	Flag
Methyl tert-butyl ether (MTBE)	ND	5.0	ug/L	12/10/1999 12:21	<u> </u>
Surrogate(s)	į		ļ		
1,2-Dichloroethane-d4	105.6	76-114	%	12/10/1999 12:21	

**Environmental Services (SDB)** 

To: Aqua Science Engineers, Inc. Test Method:

8260A

Submission #: 1999-12-0102

Attn: Ian T. Reed

Prep Method:

5030

**Batch QC Report** 

MTBE - Volatile Organics by GC/MS

**Laboratory Control Spike (LCS/LCSD)** 

Water

QC Batch # 1999/12/10-01.06

LCS:

1999/12/10-01.06-002

Extracted: 12/10/1999 10:53

Analyzed:

12/10/1999 10:53

LCSD: 1999/12/10-01.06-003 Extracted: 12/10/1999 11:54

Analyzed: 12/10/1999 11:54

Compound	Conc.	[ ug/L ]	Exp.Conc.	[ ug/L ]	Recov	rery [%]	RPD	Ctrl. Lim	its [%]	Flag	gs
	LCS	LCSD	LCS	LCSD	LCS	LCSD	[%]	Recovery	RPD	LCS	LCSD
Methyl tert-butyl ether Surrogate(s)	56.1	55.3	50.0	50.0	112.2	110.6	1.4	65-165	20		
1,2-Dichloroethane-d4	512	509	500	500	102.4	101.8		76-114			

Submission #: 1999-12-0102

**Environmental Services (SDB)** 

#### Gas/BTEX and MTBE

Aqua Science Engineers, Inc.

208 West El Pintado Road

Danville, CA 94526

Attn: Ian T. Reed

Phone: (925) 820-9391 Fax: (925) 837-4853

Project #:

Project: Oakland Truck Stop (OTS)

#### Samples Reported

Sample ID	Matrix	Date Sampled	Lab#
MW-2	Water	12/06/1999 13:45	1
MW-3	Water	12/06/1999 12:55	2
MW-4	Water	12/06/1999 14:15	3
MW-5	Water	12/06/1999 11:40	4
MW-6	Water	12/06/1999 12:25	5

1220 Quarry Lane \* Pleasanton, CA 94566-4756 Telephone: (925) 484-1919 \* Facsimile: (925) 484-1096

Printed on: 12/14/1999 14:56

Submission #: 1999-12-0102

**Environmental Services (SDB)** 

Aqua Science Engineers, Inc. To:

Test Method:

8020

8015M

Attn.: lan T. Reed

Prep Method:

5030

Gas/BTEX and MTBE

Sample ID:

MW-2

Lab Sample ID: 1999-12-0102-001

Project:

Received: 12/06/1999 15:05

Oakland Truck Stop (OTS)

Extracted:

Sampled:

12/06/1999 13:45

12/13/1999 12:47

Matrix:

Water

QC-Batch:

1999/12/13-01.01

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Gasoline	1900	50	ug/L	1.00	12/13/1999 12:47	g
Benzene	16	0.50	ug/L	1.00	12/13/1999 12:47	_
Toluene	ND	0.50	ug/L	1.00	12/13/1999 12:47	
Ethyl benzene	1.5	0.50	ug/L	1.00	12/13/1999 12:47	
Xylene(s)	ND	0.50	ug/L	1.00	12/13/1999 12:47	
MTBE	5.2	5.0	ug/L	1.00	12/13/1999 12:47	
Surrogate(s)						
4-Bromofluorobenzene	121.3	50-150	%	1.00	12/13/1999 12:47	
4-Bromofluorobenzene-FID	52.8	50-150	%	1.00	12/13/1999 12:47	

Printed on: 12/14/1999 14:56

Submission #: 1999-12-0102

**Environmental Services (SDB)** 

To: Aqua Science Engineers, Inc. Test Method:

8020 8015M

Attn.: Ian T. Reed

Prep Method:

5030

Gas/BTEX and MTBE

Sample ID: MW-3 Lab Sample ID: 1999-12-0102-002

Received:

12/06/1999 15:05

Project:

Oakland Truck Stop (OTS)

Extracted:

12/13/1999 09:53

Sampled:

12/06/1999 12:55

QC-Batch:

Matrix:

Water

1999/12/13-01.01

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Gasoline	40000	2500	ug/L	50.00	12/13/1999 09:53	
Benzene	16000	25	ug/L	50.00	12/13/1999 09:53	
Toluene	140	25	ug/L	50.00	12/13/1999 09:53	l
Ethyl benzene	1800	25	ug/L	50.00	12/13/1999 09:53	Ì
Xylene(s)	100	25	ug/L	50.00	12/13/1999 09:53	
MTBE	2200	250	ug/L	50.00	12/13/1999 09:53	
Surrogate(s)						
Trifluorotoluene	100.7	58-124	%	1.00	12/13/1999 09:53	
4-Bromofluorobenzene-FID	81.3	50-150	%	1.00	12/13/1999 09:53	

**Environmental Services (SDB)** 

To: Aqua Science Engineers, Inc.

Test Method:

8020

8015M

Submission #: 1999-12-0102

Attn.: Ian T. Reed

Prep Method:

5030

Gas/BTEX and MTBE

Sample ID: MW-4

Lab Sample ID: 1999-12-0102-003

Project:

Received:

12/06/1999 15:05

Oakland Truck Stop (OTS)

Extracted:

12/14/1999 08:51

Sampled:

12/06/1999 14:15

QC-Batch:

1999/12/14-01.01

Matrix:

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Gasoline	130	100	ug/L	2.00	12/14/1999 08:51	g
Benzene	ND	1.0	ug/L	2.00	12/14/1999 08:51	v
Toluene	ND	1.0	ug/L	2.00	12/14/1999 08:51	
Ethyl benzene	ND	1.0	ug/L	2.00	12/14/1999 08:51	
Xylene(s)	ND	1.0	ug/L	2.00	12/14/1999 08:51	
MTBE	130	10	ug/L	2.00	12/14/1999 08:51	
Surrogate(s)			į į			
Trifluorotoluene	106.8	58-124	%	1.00	12/14/1999 08:51	
4-Bromofluorobenzene-FID	73.5	50-150	%	1.00	12/14/1999 08:51	

Submission #: 1999-12-0102

**Environmental Services (SDB)** 

To: Aqua Science Engineers, Inc.

Test Method:

8020 8015M

Attn.: Ian T. Reed

Prep Method:

5030

Gas/BTEX and MTBE

Sample ID: MW-5

Lat

Lab Sample ID: 1999-12-0102-004

Project:

Oakland Truck Stop (OTS)

Received:

12/06/1999 15:05

Extracted:

12/14/1999 09:19

Sampled:

12/06/1999 11:40

QC-Batch:

1999/12/14-01.01

Matrix:

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Gasoline	450	100	ug/L	2.00	12/14/1999 09:19	g
Benzene	ND	1.0	ug/L	2.00	12/14/1999 09:19	·
Toluene	ND	1.0	ug/L	2.00	12/14/1999 09:19	
Ethyl benzene	ND	1.0	ug/L	2.00	12/14/1999 09:19	
Xylene(s)	ND	1.0	ug/L	2.00	12/14/1999 09:19	
MTBE	21	10	ug/L	2.00	12/14/1999 09:19	
Surrogate(s)						
Trifluorotoluene	76.9	58-124	%	1.00	12/14/1999 09:19	
4-Bromofluorobenzene-FID	57.7	50-150	%	1.00	12/14/1999 09:19	

Submission #: 1999-12-0102

**Environmental Services (SDB)** 

To: Aqua Science Engineers, Inc.

Test Method:

8020 8015M

Attn.: lan T. Reed

Prep Method:

5030

Gas/BTEX and MTBE

Sample ID: MW-6

Lab Sample ID: 1999-12-0102-005

Project:

Received:

12/06/1999 15:05

Oakland Truck Stop (OTS)

Extracted:

12/13/1999 13:15

Sampled:

12/06/1999 12:25

QC-Batch:

1999/12/13-01.01

Matrix:

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Gasoline	13000	1000	ug/L	20.00	12/13/1999 13:15	
Benzene	180	10	ug/L	20.00	12/13/1999 13:15	
Toluene	21	10	ug/L	20.00	12/13/1999 13:15	
Ethyl benzene	11	10	ug/L	20.00	12/13/1999 13:15	
Xylene(s)	24	10	ug/L	20.00	12/13/1999 13:15	
MTBE	ND	100	ug/L	20.00	12/13/1999 13:15	
Surrogate(s)			ļ			
Trifluorotoluene	92.6	58-124	%	1.00	12/13/1999 13:15	
4-Bromofluorobenzene-FID	74.4	50-150	%	1.00	12/13/1999 13:15	

**Environmental Services (SDB)** 

To: Aqua Science Engineers, Inc.

Test Method: 8020

8015M

Attn.: Ian T. Reed

Prep Method:

5030

**Batch QC Report** Gas/BTEX and MTBE

Method Blank

Water

QC Batch # 1999/12/13-01.01

MB:

1999/12/13-01.01-001

Date Extracted: 12/13/1999 06:21

Compound	Result	Rep.Limit	Units	Analyzed	Flag
Gasoline	ND	50	ug/L	12/13/1999 06:21	
Benzene	ND	0.5	ug/L	12/13/1999 06:21	
Toluene	ND	0.5	ug/L	12/13/1999 06:21	
Ethyl benzene	ND	0.5	ug/L	12/13/1999 06:21	
Xylene(s)	ND	0.5	ug/L	12/13/1999 06:21	
MTBE	ND	5.0	ug/L	12/13/1999 06:21	
Surrogate(s)					
Trifluorotoluene	97.0	58-124	%	12/13/1999 06:21	
4-Bromofluorobenzene-FID	74.8	50-150	%	12/13/1999 06:21	

**Environmental Services (SDB)** 

Aqua Science Engineers, Inc.

Test Method:

8020

8015M

Attn.: Ian T. Reed

To:

Prep Method:

5030

#### **Batch QC Report** Gas/BTEX and MTBE

Method Blank

Water

QC Batch # 1999/12/14-01.01

Submission #: 1999-12-0102

MB:

1999/12/14-01.01-001

Date Extracted: 12/14/1999 05:25

Compound	Result	Rep.Limit	Units	Analyzed	Flag
Gasoline	ND	50	ug/L	12/14/1999 05:25	<u>-</u>
Benzene	ND	0.5	ug/L	12/14/1999 05:25	
Toluene	ND	0.5	ug/L	12/14/1999 05:25	
Ethyl benzene	ND	0.5	ug/L	12/14/1999 05:25	
Xylene(s)	ND	0.5	ug/L	12/14/1999 05:25	
MTBE	ND	5.0	ug/L	12/14/1999 05:25	
Surrogate(s)					
Trifluorotoluene	103.8	58-124	%	12/14/1999 05:25	
4-Bromofluorobenzene-FID	79.4	50-150	%	12/14/1999 05:25	

Submission #: 1999-12-0102

**Environmental Services (SDB)** 

To: Aqua Science Engineers, Inc. Test Method: 8020

8015M

Attn: Ian T. Reed

Prep Method:

5030

**Batch QC Report** 

Gas/BTEX and MTBE

Laboratory Control Spike (LCS/LCSD)

Water

QC Batch # 1999/12/13-01.01

LCS:

1999/12/13-01.01-002

Extracted: 12/13/1999 06:49

Analyzed: 12/13/1999 06:49

LCSD:

1999/12/13-01.01-003

Extracted: 12/13/1999 07:17

Analyzed: 12/13/1999 07:17

Compound	Conc.	[ ug/L ]	Exp.Conc.	[ ug/L ]	Recov	ery [%]	RPD	Ctrl. Lim	its [%]	Flag	gs
•	LCS	LCSD	LCS	LCSD	LCS	LCSD	[%]	Recovery	RPD	LCS	LCSD
Gasoline	494	462	500	500	98.8	92.4	6.7	75-125	20		
Benzene	103	109	100.0	100.0	103.0	109.0	5.7	77-123	20		
Toluene	104	109	100.0	100.0	104.0	109.0	4.7	78-122	20		
Ethyl benzene	104	110	100.0	100.0	104.0	110.0	5.6	70-130	20	: 	
Xylene(s)	316	331	300	300	105.3	110.3	4.6	75-125	20		
Surrogate(s)											
Trifluorotoluene	519	557	500	500	103.8	111.4		58-124			
4-Bromofluorobenzene-FI	425	392	500	50 <b>0</b>	85.0	78.4		50-150			

\*\*>>

Submission #: 1999-12-0102

**Environmental Services (SDB)** 

To: Aqua Science Engineers, Inc.

Test Method: 8020

8015M

Attn: Ian T. Reed

Prep Method:

5030

#### **Batch QC Report**

Gas/BTEX and MTBE

Laboratory Control Spike (LCS/LCSD)

Water

QC Batch # 1999/12/14-01.01

LCS:

1999/12/14-01.01-002

Extracted: 12/14/1999 05:53

Analyzed: 12/14/1999 05:53

LCSD:

1999/12/14-01.01-003

Extracted: 12/14/1999 06:21

Analyzed: 12/14/1999 06:21

Compound	Conc.	[ ug/L ]	Exp.Conc.	[ ug/L ]	Recov	ery [%]	RPD	Ctrl. Limi	its [%]	Flag	js.
	LCS	LCSD	LCS	LCSD	LCS	LCSD	[%]	Recovery	RPD	LCS	LCSD
Gasoline	505	476	500	500	101.0	95.2	5.9	75-125	20		\
Benzene	103	106	100.0	100.0	103.0	106.0	2.9	77-123	20		
Toluene	104	107	100.0	100.0	104.0	107.0	2.8	78-122	20		
Ethyl benzene	106	108	100.0	100.0	106.0	108.0	1.9	70-130	20		
Xylene(s)	318	326	300	300	106.0	108.7	2.5	75-125	20		
Surrogate(s)					,	:					
Trifluorotoluene	539	563	500	<b>50</b> 0	107.8	112.6		58-124			
4-Bromofluorobenzene-FI	450	405	500	500	90.0	81.0		50-150			

**Environmental Services (SDB)** 

To: Aqua Science Engineers, Inc.

Test Method: 8015M

8020

Submission #: 1999-12-0102

Attn:lan T. Reed Prep Method: 5030

Legend & Notes

Gas/BTEX and MTBE

**Analyte Flags** 

g

Hydrocarbon reported in the gasoline range does not match our gasoline standard.

1220 Quarry Lane \* Pleasanton, CA 94566-4756 Telephone: (925) 484-1919 \* Facsimile: (925) 484-1096

Printed on: 12/14/1999 14:56

Environmental Services (SDB)

Submission #: 1999-12-0102

Soluble Metais

Aqua Science Engineers, Inc.

208 West El Pintado Road

Danville, CA 94526

Attn: Ian T. Reed

Phone: (925) 820-9391 Fax: (925) 837-4853

Project #:

Project: Oakland Truck Stop (OTS)

#### Samples Reported

Sample ID	Matrix	Date Sampled	Lab#
MW-4	Water	12/06/1999 14:15	3

Submission #: 1999-12-0102

Environmental Services (SDB)

Aqua Science Engineers, Inc. To:

Attn.: Ian T. Reed

Test Method:

6010B

Prep Method:

3005A

Soluble Metals

Sample ID: MW-4

Lab Sample ID: 1999-12-0102-003

Project:

Received:

12/06/1999 15:05

Oakland Truck Stop (OTS)

Extracted:

12/07/1999 07:20

12/06/1999 14:15

Matrix:

8.+

Sampled:

Water

QC-Batch: 1999/12/07-01.15

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Lead	ND	0.0050	mg/L	1.00	12/07/1999 12:33	

**Environmental Services (SDB)** 

To: Aqua Science Engineers, Inc.

Test Method:

6010B

Prep Method:

3005A

**Batch QC Report** Soluble Metals

Method Blank

Water

QC Batch # 1999/12/07-01.15

Submission #: 1999-12-0102

MB:

Attn.: Ian T. Reed

1999/12/07-01.15-035

Date Extracted: 12/07/1999 07:20

Compound	Result	Rep.Limit	Units	Analyzed	Flag
Lead	ND	0.0050	mg/L	12/07/1999 11:59	

Printed on: 12/14/1999 14:56

Submission #: 1999-12-0102

**Environmental Services (SDB)** 

To: Aqua Science Engineers, Inc.

Test Method: 6010B

Attn: Ian T. Reed Prep Method:

3005A

**Batch QC Report** 

Soluble Metals

Laboratory Control Spike (LCS/LCSD) Water QC Batch # 1999/12/07-01.15 LCS: Extracted: 12/07/1999 07:20 1999/12/07-01.15-036 Analyzed: 12/07/1999 12:03 LCSD: 1999/12/07-01.15-037 Extracted: 12/07/1999 07:20 Analyzed: 12/07/1999 12:07

Compound	Conc.	[ mg/L ]	Exp.Conc.	[ mg/L ]	Recov	ery [%]	RPD	Ctrl. Limi	ts [%]	Flag	js
	LCS	LCSD	LCS	LCSD	LCS	LCSD	[%]	Recovery	RPD	LCS	LCSD
Lead	0.478	0.482	0.500	0.500	95.6	96.4	8.0	80-120	20		

**Environmental Services (SDB)** 

#### Total Extractable Petroleum Hydrocarbons (TEPH)

Aqua Science Engineers, Inc.

208 West El Pintado Road

Danville, CA 94526

Attn: Ian T. Reed

Phone: (925) 820-9391 Fax: (925) 837-4853

Project #:

Project: Oakland Truck Stop (OTS)

#### Samples Reported

Sample ID	Matrix	Date Sampled	Lab#	
MW-2	Water	12/06/1999 13:45	1	
MW-3	Water	12/06/1999 12:55	2	
MW-4	Water	12/06/1999 14:15	3	
MVV-5	Water	12/06/1999 11:40	4	
MW-6	Water	12/06/1999 12:25	5	

Submission #: 1999-12-0102

**Environmental Services (SDB)** 

To: Aqua Science Engineers, Inc.

Test Method:

8015m

Attn.: Ian T. Reed

Prep Method:

3510/8015M

Total Extractable Petroleum Hydrocarbons (TEPH)

Sample ID: MW-2

Lab Sample ID: 1999-12-0102-001

Project:

Oakland Truck Stop (OTS)

Received:

12/06/1999 15:05

Extracted:

12/09/1999 09:00

Sampled:

12/06/1999 13:45

QC-Batch:

Matrix:

Water

1999/12/09-01.10

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Diesel Motor Oil	440 ND	50 500	ug/L ug/L	1.00 1.00	12/10/1999 23:15 12/10/1999 23:15	ed
Surrogate(s) o-Terphenyl	96.0	60-130	%	1.00	12/10/1999 23:15	

Submission #: 1999-12-0102

**Environmental Services (SDB)** 

To: Aqua Science Engineers, Inc.

Test Method:

8015m

Attn.: Ian T. Reed

Prep Method:

3510/8015M

Total Extractable Petroleum Hydrocarbons (TEPH)

Sample ID: MW-3

Lab Sample ID: 1999-12-0102-002

Project:

Oakland Truck Stop (OTS)

Received:

12/06/1999 15:05

Extracted:

12/09/1999 09:00

Sampled:

12/06/1999 12:55

QC-Batch:

1999/12/09-01.10

Matrix:

Water

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Diesel Motor Oil	9100 ND	50 500	ug/L ug/L	1.00 1.00	12/10/1999 23:51 12/10/1999 23:51	, -
Surrogate(s) o-Terphenyl	112.6	60-130	%	1.00	12/10/1999 23:51	

Environmental Services (SDB)

To: Aqua Science Engineers, Inc.

Test Method:

8015m

Attn.: Ian T. Reed

Prep Method:

3510/8015M

Total Extractable Petroleum Hydrocarbons (TEPH)

Sample ID:

MW-4

Lab Sample ID: 1999-12-0102-003

Project:

Oakland Truck Stop (OTS)

Received:

12/06/1999 15:05

Extracted:

12/09/1999 09:00

Sampled:

12/06/1999 14:15

Matrix:

Water

QC-Batch: 1999/12/09-01.10

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Diesel	220	50	ug/L	1.00	12/10/1999 21:25	· •
Motor Oil	ND	500	ug/L	1.00	12/10/1999 21:25	
Surrogate(s) o-Terphenyl	94.1	60-130	%	1.00	12/10/1999 21:25	

Submission #: 1999-12-0102

**Environmental Services (SDB)** 

Aqua Science Engineers, Inc. To:

Test Method:

8015m

Attn.: lan T. Reed

Prep Method:

3510/8015M

Total Extractable Petroleum Hydrocarbons (TEPH)

Sample ID:

MW-5

Lab Sample ID: 1999-12-0102-004

Project:

Oakland Truck Stop (OTS)

Received:

12/06/1999 15:05

Extracted:

12/09/1999 09:00

Sampled:

12/06/1999 11:40

Matrix:

Water

QC-Batch:

1999/12/09-01.10

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Diesel Motor Oil	2000 ND	50 500	ug/L ug/L	1.00 1.00	12/10/1999 22:02 12/10/1999 22:02	ndp
Surrogate(s) o-Terphenyl	109.8	60-130	%	1.00	12/10/1999 22:02	

**Environmental Services (SDB)** 

To: Aqua Science Engineers, Inc.

Test Method:

8015m

Attn.: Ian T. Reed

Prep Method:

3510/8015M

Total Extractable Petroleum Hydrocarbons (TEPH)

Sample ID: MW-6

Lab Sample ID: 1999-12-0102-005

Project:

Oakland Truck Stop (OTS)

Received:

12/06/1999 15:05

Sampled:

Extracted:

12/09/1999 09:00

12/06/1999 12:25

QC-Batch:

Matrix:

Water

1999/12/09-01.10

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Diesel Motor Oil	ND ND	50 500	ug/L ug/L	1.00	12/10/1999 22:38 12/10/1999 22:38	
Surrogate(s) o-Terphenyl	93.9	60-130	%	1.00	12/10/1999 22:38	

**Environmental Services (SDB)** 

To: Aqua Science Engineers, Inc.

Attn.: Ian T. Reed

Test Method:

8015m

Prep Method:

3510/8015M

#### **Batch QC Report**

Total Extractable Petroleum Hydrocarbons (TEPH)

**Method Blank** 

Water

QC Batch # 1999/12/09-01.10

Submission #: 1999-12-0102

MB:

1999/12/09-01.10-001

Date Extracted: 12/09/1999 09:00

Compound	Result	Rep.Limit	Units	Analyzed	Flag	
Diesel Motor Oil	ND	50	ug/L	12/11/1999 14:33		
Surrogate(s)	ND	500	ug/L	12/11/1999 14:33		
o-Terphenyl	100.0	60-130	%	12/11/1999 14:33		

Printed on: 12/14/1999 14:56

**Environmental Services (SDB)** 

To: Aqua Science Engineers, Inc.

Test Method: 8015m

Attn: Ian T. Reed

Prep Method:

3510/8015M

Submission #: 1999-12-0102

Batch QC Report

Total Extractable Petroleum Hydrocarbons (TEPH)

Laboratory Control Spike (LCS/LCSD)

Water

QC Batch # 1999/12/09-01.10

LCS: LCSD: 1999/12/09-01.10-002 1999/12/09-01.10-003

Extracted: 12/09/1999 09:00

9 09:00 Analyzed:

12/10/1999 12:52

Extracted: 12/09/1999 09:00 Analyzed: 12/10/1999 13:28

Compound	Conc.	[ ug/L ]	Exp.Conc.	[ ug/L ]	Recovery [%]		RPD	Ctrl. Limits [%]		Flags	
	LCS	LCSD	LCS	LCSD	LCS	LCSD	[%]	Recovery	RPD	LCS	LCSD
Diesel Surrogate(s)	1090	1090	1250	1250	87 2	87.2	0.0	60-130	25		
o-Terphenyl	18.8	19.1	20.0	20.0	94.0	95.5		60-130			į

**Environmental Services (SDB)** 

To: Aqua Science Engineers, Inc.

Attn:lan T. Reed

Test Method: 8015m

Prep Method: 3510/8015M

Submission #: 1999-12-0102

#### Legend & Notes

Total Extractable Petroleum Hydrocarbons (TEPH)

**Analyte Flags** 

eđ

Hydrocarbon reported is in the early Diesel range, and does not match our Diesel standard

ndp

Hydrocarbon reported does not match the pattern of our Diesel standard

99-12-0102

Reference #:

49398

1220 Quarry Lane • Pleasanton, California 94566-4756

(925) 484-1919 • Fax (925) 484-1096

Chain of Custody

Environmental Services (SDB) (DOHS 1094) DATE 12-6-99 PAGE 1 OF 1 ANALYSIS HEPORT PROJ. MGR COMPANY Agua Science Engineers PURGEABLE AROMATICS BTEX (EPA 8020) TPH-Diesel (EPA.8015M) ADDRESS \_ 208 W. EL PINTado PESTICIDES(EPA 8080) PCB'S (EPA 8080) NUMBER OF CONTAINERS VOLATILE ORGANICS (VOCs) (EPA 8260) SEMIVOLATILES (EPA 8270) O Hexavalent Chronium O pH (24 hr hold time for Danville CAM'17 METALS IEPA 6010/7470/747 PNA's by C 8270 DW.E.T. (STLC) Cd, Cr, Pb, NI, SAMPLERS (SIGNATURE) (PHONE NO.) □ Spec. Cond. □ TSS □ TDS (FAX NO.) SAMPLE ID. DATE TIME MATRIX PRESERV. MW-Z 1345 water **ZVOAS** MW-3 2 Lt 1253 4 VOAS 2 L T マロ 1140 3 YOK ZLT 1225 340K PROJECT INFORMATION SAMPLE RECEIPT RELINQUISHED BY RELINQUISHED BY 2 RELINQUISHED BY TOTAL NO OF CONTAINERS Oakland Truck STUP (OTS 1505 PROJECT NUMBER HEAD SPACE (SIGNATURE) (SIGNATURE) (TIME) (SIGNATURE) (TIL(E) Ign TRoad 12-6-49 TEMPERATURE P.O. # (PRINTED NAME) (PRINTED NAME) (DATE) PRINTED NAME CONFORMS TO RECORD おも (DATE) STANDARD (COMPANY) 24 48 **ICOMPANY** 5-DAY 72 OTHER COMPANY SPECIAL INSTRUCTIONS/COMMENTS: RECEIVED BY RECEIVED BY RECEIVED BY (LABORATORY) Report: 🗆 Routine 🖰 Level 2 🗎 Level 3 🗎 Level 4 🗎 Electronic Report (SIGNATURE) TIME (SIGNATURE) IPPINTED NAME) (PRINTED NAME) PRINTED NAME COMPANY (COMPANY)