ALAMEDA COUNTY HEALTH CARE SERVICES AGENCY

CO

ALEX BRISCOE, Director

ENVIRONMENTAL HEALTH SERVICES ENVIRONMENTAL PROTECTION 1131 Harbor Bay Parkway, Suite 250 Alameda, CA 94502-6577 (510) 567-6700 FAX (510) 337-9335

November 29, 2011

Mr. Mike Olvera
AB&I Foundry
7825 San Leandro Street
Oakland, CA 94621-2598

(Sent via E-mail to: Mike. Olvera@abifoundry.com)

Mr. Kurt Winter McWane, Inc.
Nine Plus LLC c/o Mike Olvera
c/oAB&I Foundry AB&I Foundry

7825 San Leandro Street 7825 San Leandro Street Oakland, CA 94621-2598 Oakland, CA 94621-2598

(Sent via E-mail to: Kurt.Winter@abifoundry.com)

Subject: Case Closure for Fuel Leak Case No. RO0000092 and GeoTracker Global ID T0600100065. American Brass & Iron Foundry, 7825 San Leandro Street, Oakland, CA 94621

Dear Mr. Olvera and Mr. Winter:

This letter transmits the enclosed underground storage tank (UST) case closure letter in accordance with Chapter 6.75 (Article 4, Section 25299.37[h]). The State Water Resources Control Board adopted this letter on February 20, 1997. As of March 1, 1997, the Alameda County Environmental Health (ACEH) is required to use this case closure letter for all UST leak sites. We are also transmitting to you the enclosed case closure summary. These documents confirm the completion of the investigation and cleanup of the reported release at the subject site. The subject fuel leak case is closed. This case closure letter and the case closure summary can also be viewed on the State Water Resources Control Board's Geotracker website (http://geotracker.swrcb.ca.gov) and the Alameda County Environmental Health website (http://www.acgov.org/aceh/index.htm).

SITE INVESTIGATION AND CLEANUP SUMMARY

Please be advised that the following conditions exist at the site:

- Total Petroleum Hydrocarbons as diesel remain in soil at concentrations up to 5,800 ppm.
- Total Petroleum Hydrocarbons as gasoline remain in groundwater at concentrations up to 2,200 ppb.
- Vinyl chloride remains in groundwater at concentrations up to 0 97 ppb.
- Due to the residual contamination, a Covenant and Environmental Restriction was recorded for the site on September 22, 2011. The Covenant and Environmental Restriction limits future land use to the current industrial land use only. No excavation is to be conducted on the site unless expressly permitted in writing by ACEH.
- The restrictions on this site are to be entered into the City Of Oakland Permit Tracking System due to the residual contamination on the site.

If you have any questions, please call Jerry Wickham at (510) 567-6791 Thank you.

Sincerely.

Donna L. Drogos, P.E.

Division Chief

Enclosures:

- 1. Remedial Action Completion Certification
- 2. Case Closure Summary

CC:

Leroy Griffin (wlenc)
Oakland Fire Department
250 Frank H. Ogawa Plaza, Ste. 3341
Oakland, CA 94612-2032
(Sent via E-mail to: Igriffin@oaklandnet.com)

Dave Robinson AB&I Foundry 7825 San Leandro Street Oakland, CA 94621-2598 (Sent via E-mail

to: Dave Robinson@abifoundry.com)

Closure Unit (submitted to GeoTracker) State Water Resources Control Board UST Cleanup Fund P.O. Box 944212 Sacramento, CA 94244-2120

Kent Reynolds
The Source Group, Inc.
3451-C Vincent Road
Pleasant Hill, CA 94523
(Sent via E-mail
to: kreynolds@thesourcegroup.net)

Donna Drogos, ACEH (Sent via E-mail to: donna.drogos@acgov.org)

Jerry Wickham, ACEH (Sent via E-mail to: jerry.wickham@acgov.org)

GeoTracker (w/enc) eFile (w/orig enc)

ALAMEDA COUNTY HEALTH CARE SERVICES AGENCY



ALEX BRISCOE, Director

ENVIRONMENTAL HEALTH SERVICES ENVIRONMENTAL PROTECTION 1131 Harbor Bay Parkway, Suite 250 Alameda, CA 94502-6577 (510) 567-6700 FAX (510) 337-9335

REMEDIAL ACTION COMPLETION CERTIFICATION

November 29, 2011

Mr. Mike Olvera AB&I Foundry 7825 San Leandro Street Oakland, CA 94621-2598

(Sent via E-mail to: Mike Olvera@abifoundry.com)

Mr. Kurt Winter Nine Plus LLC c/oAB&I Foundry

c/o Mike Olvera AB&I Foundry 7825 San Leandro S(reet

7825 San Leandro Street Oakland, CA 94621-2598

Oakland, CA 94621-2598

(Sent via E-mail to: Kurt.Winter@abifoundry.com)

Subject: Case Closure for Fuel Leak Case No. RO0000092 and GeoTracker Global ID T0600100065, American Brass & Iron Foundry, 7825 San Leandro Street, Oakland, CA 94621

McWane, Inc.

Dear Mr. Olvera and Mr. Winter:

This letter confirms the completion of a site investigation and remedial action for the underground storage tanks formerly located at the above-described location. Thank you for your cooperation throughout this investigation. Your willingness and promptness in responding to our inquiries concerning the former underground storage tank(s) are greatly appreciated.

Based on information in the above-referenced file and with the provision that the information provided to this agency was accurate and representative of site conditions, this agency finds that the site investigation and corrective action carried out at your underground storage tank(s) site is in compliance with the requirements of subdivisions (a) and (b) of Section 25296.10 of the Health and Safety Code and with corrective action regulations adopted pursuant to Section 25299.3 of the Health and Safety Code and that no further action related to the petroleum release(s) at the site is required.

This notice is issued pursuant to subdivision (h) of Section 25296.10 of the Health and Safety Code. Please contact our office if you have any questions regarding this matter.

Sincerely,

Ariu Levi Director

Alameda County Environmental Health

CASE CLOSURE SUMMARY LEAKING UNDERGROUND FUEL STORAGE TANK - LOCAL OVERSIGHT PROGRAM

Date: July 20, 2011

I. AGENCY INFORMATION

Agency Name: Alameda County Environmental Health	Address: 1131 Harbor Bay Parkway
City/State/Zip: Alameda, CA 94502-6577	Phone: (510) 567-6791
Responsible Staff Person; Mr. Jerry Wickham	Title: Senior Hazardous Materials Specialist

II. CASE INFORMATION

Site Facility Name. American Brass & Iron Foundry				
Site Facility Address: 7825 San Leandro Street, Oakland, California 94621				
RB Case No.: 01-0071 STID No.: 523 LOP Case No.: RO0000092				
URF Filing Dates: 05/29/1992	GeoTracker ID: T0600100065 APN: 41-4209-1-1, 41-420 4209-8-1, 41-4209-1-2		41-4209-1-1, 41-4209-3-2, 41- 8-1, 41-4209-1-2	
Responsible Parties	Addresses		Phone Numbers	
AB&I Foundry, c/o Mike Olvera	7825 San Leandro Street, Oakland, CA 94621-2515		(800) 468-4766	
Nine Plus LLC, Kurt Winter c/o AB&I Foundry	7825 San Leandro Street, Oakland, CA 94621-2515		(800) 468-4766	
McWane, Inc., c/o Mike Olvera, AB&I Foundry	7825 San Leandro Street, Oakland, 94621-2515	CA	(800) 468-4766	

Tank I.D. No	Size in Gallons	Contents	Closed In Place/Removed?	Date
1 thru 3	10.000-gallons	Gasoline	Removed	Circa 1982/1983
4	8,000-gallons	Unleaded Gasoline	Removed	8/8/1991
5	550-gallons	Leaded Gasoline	Removed	8/26/1991
6	8,000-gallons	Mineral Spirits and 1,1,1- trichloroethane	Removed	10/4/1991
7	12.000-gallons	Diesel Fuel	Removed	6/3/1992
	Piping		Removed	_

III. RELEASE AND SITE CHARACTERIZATION INFORMATION

Cause and Type of Release: Unknown. During removal, the tanks appeared to be intact with no holes, cracks, or other signs of obvious failure.				
Site characterization complete? Yes Date Approved By Oversight Agency: —-				
Monitoring wells installed? Yes	Number: 10	Proper screened interval? Yes		
Highest GW Depth Below Ground Surface: 3.5 feet bgs Lowest Depth: 8.7 feet bgs Flow Direction: Northwest				
Most Sensitive Current Use: Potential drinking water source.				

Summary of Production Wells in Vicinity: The nearest water supply well is an on-site industrial water supply well located along the southwest perimeter of the Site (2S/3W/16R 01). The well is used by A8&I Foundry as a source for process (cooling) water for plant operations in conjunction with East Bay Municipal District (EBMUD) water. The well is 495 feet deep and is completed from 176 to 495 feet bgs. In 1993, approximately 362,752 gallons per day (gpd) of well water and 12,000 gpd of EBMUD water was used for plant operations. Current well water use is approximately 15,000 gpd. The on-site water supply well is sampled periodically for the Groundwater Ambient Monitoring and Assessment (GAMA) program implemented by the State Water Resource Control Board in coordination with the U.S. Geological Survey and Lawrence Livermore National Laboratory. Groundwaler samples collected from the on-site water supply well in June 2007 contained low concentrations (<2 ppb) of PCE, TCE, and cis-1,2-DCE. In 2008, grab groundwater samples were collected from depths of approximately 40 to 52 feet bgs to help evaluate whether shallow groundwater encountered in the water-bearing zone less than 40 feet bgs was affecting deeper groundwater below 40 feet bgs. The deeper grab groundwater samples contained TPHg, TPHd, 1,2-DCA, TCE, cis-1,2-DCE, and vinyl chloride at concentrations below Environmental Screening Levels for current or potential drinking water. Each of these chemicals with the exception of 1,2-DCA has been detected in shallow groundwater beneath the site. Therefore, it is possible that chemicals released to shallow groundwater from the USTs have migrated downward and affected deeper groundwater at the site. However, the grab groundwater sample collected at a depth of approximately 52 feet bgs from deeper groundwater closest to the water supply well contained 1,2-DCA at a concentration of 2.2 ppb but did not contain other VOCs at concentrations above reporting limits. 1,2-DCA has not been detected in shallow groundwater in the areas of the former USTs and may be related to a regional source rather than a site source. Groundwater monitoring data collected to date indicate that VOCs released from the USTs may have migrated to deeper groundwater at low concentrations below ESLs for drinking water. These VOCs potentially may reach the on-site water supply well at de minimis concentrations. Based on the current data and expected continued decreases in VOC concentrations in groundwater expected following remediation, the on-site water supply well is not expected to be significantly impacted by releases from USTs at the Site.

A shallow well (28 feet deep) of unknown use is located approximately 200 feet north of the site at 800 77th Avenue. Based on the distance and cross gradient location from the site, the unknown well at 800 77th Avenue is not expected to be a receptor for the site. Three wells of unknown use are located approximately 1,200 feet northwest of the site at Aero Quality Plating. Based on the distance of the three wells from the site, the Aero Quality Plating wells are not expected to be receptors for the site.

The Fitchburg well group, which historically consisted of about 20 municipal supply wells, was apparently located more than approximately 500 feet southwest of the site. The precise locations and the methods used for decommissioning the Fitchburg group are unknown. Several observation wells are located at the Coliseum, approximately 1,800 to 2,200 feet west to northwest of the site. Based on the distance from the site, the Coliseum observation wells are not expected to be receptors for the site

Are drinking water wells affected? No	Aquifer Name. East Bay Plain
Is surface water affected? No	Nearest SW Name: Elmhurst Creek is located along the southeast comer of the property and is approximately 350 feet southwest of the nearest UST.
Off-Sile Beneficial Use Impacts (Addresses/	Locations): None
Reports on file? Yes	Where are reports filed? Alameda County Environmental Health and Oakland Fire Department

Material	Amount (Include Units)	Action (Treatment or Disposal w/Destination)	Date
	Three 10,000-gallon gasoline USTs	The treatment or disposal of the USTs was not reported.	Circa 1982/1983
	8,000-gallon gasoline UST	Transported to H&H Ship Service Company in San Francisco, CA for disposal	8/8/1991
Tank	550-gallon gasoline UST	Transported to H&H Ship Service Company in San Francisco, CA for disposal	8/26/1991
	8,000-gallon solvent UST	Transported to Erickson, Inc. in Richmond, CA for disposal	10/4/1991
	12,000-gallon diesel UST	Transported to H&H Ship Service Company in San Francisco, CA for disposal	6/3/1992
Piping	Not reported	Transported to H&H Ship Service Company in San Francisco, CA for disposal	Various
Free Product			
Soil	15-25 cubic yards	Gasoline-affected soil removed from the 8,000-gallon gasoline tank (#4) excavation was spread on a concrete pad at the site for aeration. After sampling, the soil used for backfill for the 550-gallon gasoline tank pit in another area of the site.	9/1991
Soil	40-60 cubic yards	Gasoline-affected soil removed from the 550- gallon gasoline tank (#5) excavation was spread on a concrete pad at the site for aeration. After sampling, the soil used for backfill for the 8,000-gallon solvent tank pit in another area of the site.	9/1991
Soil	180 cubic yards	Solvent-affected soil removed from the tank excavation was spread on a concrete pad at the site for aeration. After sampling, the soil was reportedly used off-site for fill at an "R&A Trucking Project.".	10/1991
Soil	180 cubic yards	Excavated soil was stockpiled inside a covered building. The soil reportedly underwent a biological treatment by BioConverters, Inc. until the concentrations were less than 1,000 ppm. The soil was then sent to the BFI Vasco Road Landfill for disposal.	6/1992
Groundwater	_	_	_

MAXIMUM DOCUMENTED CONTAMINANT CONCENTRATIONS BEFORE AND AFTER CLEANUP (Please see Attachments 2 – 6 for additional information on contaminant locations and concentrations)

	Soil (ppm)		Groundwater (ppb)	
Contaminant	Before	After	Before	After
TPH (Gas)	2,000	1,400	19,000(1)	2,200(1)
TPH (Diesel)	5.800	5.800	37,000(2)	120(2)
Oil & Grease	3.500	3,500	2,000	2,000
Benzene	6.6	<1	250(3)	77(3)
Toluene	8	1.5	11(3)	1.8(3)
Ethylbenzene	15	27	51(3)	9.1(3)
Xylenes	81	62	14(3)	1.4(3)
Heavy Metals (Cd, Cr, Pb, Ni, Zn)	970(4)	970(4)	Not Analyzed	Not Analyzed
МТВЕ	<0.005(5)	<0.0005(5)	11(6)	11(6)
1,1,1-Trichloroethane	1.3	<0.25	2,700	<0.05
1,1-Dichloroethane	0.5	<0.25	2,600	0.29
1,1-Dichloroethene	<0.25	<0.25	3,200	0.8
Vinyl Chloride	<0.25	<0.25	50	0.97
Other (8270)	2,100(7)	2,100(7)	2.5(8)	2.5(8)

Footnotes:

- (1) The maximum concentration before cleanup is from a grab groundwater sample collected from boring SB-08 at 17 feet bgs on October 31, 2007; the maximum concentration after cleanup is the maximum concentration detected during the most recent sampling event on 12/22/2010.
- (2) The maximum concentration before cleanup is from a grab groundwater sample collected from boring SB-26 at 10 feet bgs on November 2, 2007; the maximum concentration after cleanup is the maximum concentration detected during the most recent sampling event on 12/22/2010.
- (3) The maximum concentration before cleanup is from a groundwater sample collected from well MW-9 on August 6, 2006; the maximum concentration after cleanup is the maximum concentration detected during the most recent sampling event on 12/22/2010.
- (4) Lead = 970 ppm; cadmlum = 3.4 ppm; chromium = 310 ppm; nickel = 87 ppm; and zinc = 550 ppm.
- (5) MTBE, EDB, and EDC <0.0005 ppm; TAME, ETBE, DIPE, and TBA not analyzed.
- (6) MTBE = 11 ppb; TBA = 15 ppb; TAME, ETBE, DIPE, EDB, and EDC not detected at various reporting limits.
- (7) Napthalene = 2,100 ppm; acenapthalene = 1,300 ppm; benzo(a)pyrene = 960 ppm in tar-like substance encountered in boring SB-26.
- (8) Napthalene = 2.5 ppb; no other PAHs detected above various reporting limits.

Site History and Description of Corrective Actions:

The site, which contains various warehouses, manufacturing, and office buildings, is an approximately 11.8 acres industrial facility in Oakland, CA. Site activities include the manufacture of pipe and fittings. AB&I has been operating at the facility since at least 1930. Surrounding land use is mixed commercial and industrial.

Three gasoline underground storage tanks (USTs) were removed from the site eirca 1982 to 1983. No reports are available to document the removal of the three USTs. Mr. Dave Robinson indicated that based on interviews with Mr. Frank Cole (former AB&I employee) the USTs were part of a service station operated by the Olympic Oil Company and included two fuel dispensers and three 10,000-gallon gasoline USTs. In 1972, AB&I purchased the property containing the service station. In 1977, the two fueling dispenser islands were removed and replaced by a single dispenser. All three USTs and the dispenser were reportedly removed by AB&I circa 1982/1983 (no longer depicted in a 1983 aerial photograph). The final disposition of the tanks is unknown. Mr. Frank Cole indicated that based on his recollection, the excavation was backfilled using soil generated from the removal of the USTs and imported soil. No confirmatory or UST closure samples were known to have been collected.

Between August 1991 and June 1992, four USTs (8,000-gallon gasoline, 550-gallon gasoline, 8,000-gallon solvent, and 10,000-gallon diesel) were removed from four separate areas of the site. Limited overexcavation was apparently conducted during the removals. Between August 5 and 8, 1991, an 8,000-gallon gasoline UST and associated plping were removed. Approximately 20 cubic yards of soil was removed from the tank pit. On August 26, 1991, a 550-gallon UST and associated piping were removed. Residual contamination along the west and south sides of the tank pit could not be removed by excavation due to the presence of underground utilities and foundations.

On October 4, 1991, an 8,000-gallon solvent UST was removed. The UST was used for storage of mineral spirits and later 1,1,1-trichloroethane (TCA). The excavation was extended 4-6 feet from the sides of the tank pit to remove approximately 180 cubic yards of contaminated soil. A tar-like substance was observed at a depth of 3.5 feet bgs along the northern side of the excavation. The tar-like substance was removed from portions of the northeast corner and northernmost area but due to difficulties in removing the concrete surface structures, excavation of the tar-like substance was terminated.

On June 3, 1992, a 10,000-gallon diesel UST was removed from the southern portion of the site. Approximately 180 cubic yards of soil was removed during the excavation. The excavation was stopped due to difficulty in removing a concrete surface slab.

Following the UST removals, four groundwater monitoring wells (MW-1 through MW-4) were installed on February 17 and 18, 1993, adjacent to each of the four former USTs (within 10 feet of the tank excavations). One shallow soil boring was to have been angled beneath the office building adjacent to the former 550-gallon gasoline UST to assess potential contamination beneath the building foundation; however, the boring could not be advanced due to overheard power lines. Elevated concentrations of petroleum hydrocarbons were reported in soil and groundwater samples from wells MW-1, MW-2, and MW-4.

Quarterly sampling of the four monitoring wells was conducted from 1993 to 1997. No investigations other than groundwater sampling appear to have taken place between 1993 and 2006.

In July 2006, a soil and groundwater assessment was conducted as part of a property transfer. Monitoring well MW-2 was found to be damaged and was replaced by well MW-2R. Five additional groundwater monitoring wells (MW-5 through MW-9) were installed between August 12 and 18, 2006.

On November 2, 2007, soil gas samples were collected from 10 locations to assess potential vapor infrusion to indoor air.

A total of 37 soil borings were advanced in November 2007 to address data gaps and define the source and extent of TPH and VOC-affected soil and groundwater. Six additional borings were advanced in the parking lot area along the eastern boundary of the site to assess the lateral extent of VOC-affected groundwater. TPHg. TPHd, BTEX, MTBE, TBA, and chlorinated VOCs were detected in groundwater beneath the site. Groundwater monitoring was continued in 2008.

On July 7, 2008, ten soil gas samples were collected at five locations to assess the potential for vapor intrusion to the office building adjacent to the 550-galon gasoline UST area. Tetrachloroethene (PCE) and vinyl chloride were detected in soil gas at maximum concentrations of 3.7 and 2.1 microgram per liter, respectively. The concentrations of PCE and vinyl chloride in soil gas exceeded the environmental screening level (ESL) under a commercial fand use scenario. The detections of PCE and vinyl chloride did not appear to correlate to areas of PCE and vinyl chloride in groundwater and were interpreted to be related to surface spills.

Site History and Description of Corrective Actions (continued);

Between July 8 and 12, 2008, 14 soil borings (SB-38 through SB-42 and SB-44 through SGI-52) were advanced. The soil borings were originally planned to be advanced to a depth of approximately 50 feet bgs; however, refusal and heaving sands were encountered in eleven of the borings (SB-38 through SB-48). To address the refusal and heaving sands issues, four borings (SB-49 through SB-52) were advanced using a direct push electrical conductivity probe. A total of six soil samples were collected from the borings. Nine grab groundwater samples were collected at seven locations to assess the vertical extent of TPH and VOC-impacted shallow and deep groundwater and to evaluate the potential for contaminated groundwater to impact the water supply well located on-site. TPHg, TPHd, 1,2-DCA, TCE, cis-1,2-DCE, and vinyl chloride were detected in deep groundwater underlying the site. Of these compounds, TPHg, TPHd, TCE, cis-1,2-DCE, and vinyl chloride were also detected in shallow groundwater. Based on the detection of contaminants in both shallow and deep groundwater, shallow contamination may be affecting deep groundwater. However, the presence of 1,2-DCA in deep groundwater but absence of 1,2-DCA in shallow groundwater was interpreted as a possible off-site source. None of the concentrations of TPH and VOCs exceeded drinking water ESLs.

On March 13, 2009, three soil gas samples (SG-17 through SG-19) were collected in the area of the employee training classroom, locker room, and lunchroom. PCE and benzene were the only compounds detected. PCE was detected at a concentration of 3.1 µg/L in sample SG-19 collected in the area of the lunchroom, which exceeds the ESL for indoor air vapor intrusion under the commercial land use scenario of 1.4 µg/L. A site-specific risk assessment for PCE in SG-19 estimated an excess cancer risk of 9 x 10-06, which is within range of 10-04 to 10-06, where the need for active remediation or risk management is evaluated on a site-specific basis. Based on the isolated detection beneath the lunchroom, the conservatism of the exposure assumptions used in the risk assessment in comparison to occupancy of the lunchroom, and the presence of a 12-inch thick concrete slab beneath the lunchroom, soil vapor beneath the lunchroom, active remediation does not appear to be warranted.

In June 2009, an enhanced aerobic biodegradation pilot study was conducted in the area of three former 10,000-gallon USTs to promote the breakdown of petroleum hydrocarbons through the addition of Oxygen Releasing Compound® (ORC) and Regenox®. A total of 1,200 pounds of ORC was injected in nine locations in the three former 10,000-gallon USTs. Groundwater monitoring data collected from June 2009 through December 2010 indicate that injection activities were initially effective in raising dissolved oxygen levels and reducing benzene and toluene concentrations but some rebound has occurred. However, TPHg and TPHd concentrations remained relatively stable.

An enhanced anaerobic biodegradation pilot study was conducted in the parking lot area to promote the breakdown of chlorinated VOCs via reductive dechlorination through addition of EOS®, which is a food-grade vegetable oil that serves as a slow-release carbon source. A total of 5,745 gallons of EOS® was injected into 15 locations in June 2009. Groundwater monitoring since June 2009 Indicate generally stable to declining concentrations. Significant decreases in chemical concentrations have taken place in the areas of wells MW-3 and MW-8.

IV. CLOSURE

Does completed corrective action protect existing beneficial uses per the Regional Board Basin Plan? Yes

Does completed corrective action protect potential beneficial uses per the Regional Board Basin Plan? Yes

Does corrective action protect public health for current land use? Alameda County Environmental Health staff does not make specific determinations concerning public health risk. However, based upon the information available in our files to date, it does not appear that the release would present a risk to human health based upon current land use and conditions.

Site Management Requirements: Case closure for the fuel leak site is granted for the current industrial land use only. This closure applies only to the former UST systems described in Sections II and III. Restrictions on future land use are described in the "Covenant and Environmental Restriction on Property" that is included as an attachment to this Case Closure Summary. This site is to be entered into the City of Oakland Permit Tracking System due to the residual contamination on site.

Should corrective action be reviewed if land use changes? Yes

Was a deed restriction or deed notification filed? Yes Date Recorded:

Monitoring Wells Decommissioned: No Number Decommissioned: 1 Number Retained: 9

List Enforcement Actions Taken: None

List Enforcement Actions Rescinded: ---

Considerations and/or Variances:

This case closure only addresses unauthorized releases from the seven former USTs identified in Sections I and IV. Other environmental conditions that may exist at the site but are not related to the releases from the former USTs have not been evaluated as part of this case closure. These conditions include the detection of elevated concentrations of metals in soil samples collected from 3 of the 5 monitoring well borings advanced in August 2006. With the exception of well MW-9, these wells are not located in close proximity to the former USTs. The elevated concentrations of metals do not appear to be related to releases from the former USTs.

During removal of the 8,000-gallon 1,1,1-TCA UST, a 2 to 3-inch thick layer of a lar-like substance was encountered at a depth of approximately 3.5 feet in the northern end of the excavation. Although much of the tar-like substance was removed from the tank pit, excavation was aborted prior to full removal of the layer due to difficulty in removing a concrete surface structure. The tar-like substance appears to be unrelated to releases from the solvent tank.

The highest concentrations of 1,1,1-TCA and vinyl chloride in groundwater at the site have been idetected in well MW-8, which is located approximately 150 feet west of the former mineral spirits/1,1,1-TCA tank. 1,1,1-TCA concentrations in groundwater samples collected in the area of the former solvent tank have typically been lower than concentrations measured in groundwater from well MW-8. Although, the source of 1,1,1-TCA in well MW-8 appears to be the former mineral spirits/1,1,1-TCA tank, it is possible that an unidentified secondary source of solvents could exist in the area of MW-8.

A soil vapor sample (SG-19) collected from a depth of 1.5 feet bgs beneath the lunchroom contained 3.0 µg/L of PCE. A site-specific risk assessment for PCE in SG-19 estimated an excess cancer risk of 9 x 10-06, which is within range of 10-04 to 10-06, where the need for active remediation or risk management is evaluated on a site-specific basis. Based on the isolated detection beneath the lunchroom, the conservatism of the exposure assumptions used in the risk assessment in comparison to occupancy of the lunchroom, and the presence of a 12-inch thick concrete slab beneath the lunchroom, soil vapor beneath the lunchroom, active remediation does not appear to be warranted.

Vinyl chloride was detected in soil vapor from two locations in the office building (SG-12 and SG-16B) at concentrations exceeding the ESL for vapor intrusion to indoor air. A sub-slab soil vapor sample collected from a depth of 0.5 feet bgs did not contain vinyl chloride at a concentration greater than the reporting limit of 0.05 µg/L. The south-facing side of the ground floor to the office building where SG-12 and SG-16B are located is open to the outside environment. The detections of PCE and vinyl chloride in soil vapor samples from SG-12 and SG-16B were presumed to be related to isolated surface spills and not releases from the UST systems.

Conclusion:

Alameda County Environmental Health staff believe that the levels of residual contamination do not pose a significant threat to water resources, public health and safety, and the environment under the current commercial land use based upon the information available in our files to date. No further investigation or cleanup for the fuel leak case is necessary unless a change in land use to any residential or other conservative land use scenario occurs at the site. ACEH staff recommend closure for this site.

VI. LOCAL AGENCY REPRESENTATIVE DATA

Prepared by: Jerry Wickham	Title: Senior Hazardous Materials Specialist
Signature: Ley Wichian	Date:07/20/11
Approved by: Donna L. Drogos, P.E.	Title: Chief
Signature: Lorun Horos	Date: 07/20/11

This closure approval is based upon the available information and with the provision that the information provided to this agency was accurate and representative of site conditions.

VIL REGIONAL BOARD NOTIFICATION

Regional Board Staff	Name: Cherie McCaulou	Title: Engineering Geologist	
Notification Date:	08/09/11		


VIII. MONITORING WELL DECOMMISSIONING

Date Requested by ACEH: 09/22/11	Date of Well Decommissioning Report: \\\\ \ \ \ \ \ \ \ \ \ \ \ \		
All Monitoring Wells Decommissioned:	Number Decommissioned: Q	Number Retained:	
Reason Wells Retained: NA	•		
Additional requirements for submittal of groundwater data from retained wells: \mathcal{N} o κ e			
ACEH Concurrence - Signature:	molelin	Date: 12/05/11	
A Th			


Attachments:

- Vicinity Map and Site Plans (4 pp)
- 2. Potentiometric Surface Maps, Cross Sections, and Concentration Graphs (10 pp)
- 3. Soil, Soil Gas, and Groundwater Samples Results Maps (15 pp)
- 4. Soil and Soil Vapor Analytical Data (15 pp)
- 5. Groundwater Analytical Data (21 pp)
- 6. Boring Logs and Electrical Conductivity Plots (90 pp)
- 7. Covenant and Environmental Restriction on Property (15 pp)
- 8. Revised Site Management Plan dated July 19, 2011 (47 pp)

This document and the related CASE CLOSURE LETTER & REMEDIAL ACTION COMPLETION CERTIFICATE shall be retained by the lead agency as part of the official site file.










A 8 & I Foundry 7825 San Leandro Street Oakland, California


BSK Job No. E0605504S SITE PLAN FIGURE 2


BSK





















EAnB Effectiveness Results: MW-3 Figure 6

1,1-DCA, Chloroethane, and Methane Trends







Figure 7
EAnB Effectiveness Results: MW-8

1,1,1-TCA, 1,1-DCA, Chloroethane, and Methane Trends



1,1-DCE, Vinyl Chloride, and Ethene Trends









Figure 8
Benzene and TPHg Concentration Trend: MW-9














EXPLANATION

- Soll sample location (depth in feet is last number)
- X Excavation water sample location

0 5 10 FEET

Figure 2 : PLAN SHOWING FORMER TANK AND SOIL SAMPLE LOCATIONS





Figure 2: SITE PLAN SHOWING FORMER 1,1,1-TCA TANK AND SOIL SAMPLE LOCATIONS



X




Figure 2: SITE PLAN SHOWING FORMER TANK LOCATION, EXCAVATION AND SOIL SAMPLE LOCATIONS

Project No. 2408

LEVINE-FRICKE BIOHEERS, HTOPOZEOLOGETTS & APPUIZO BOTOMISTS






Figure 2: PLAN SHOWING SOIL SAMPLE LOCATIONS


Project No. 2408


LEVINE-FRICKE


EMGNEURS, INDROGECLOGISTS & APPLIED SCIENTISMS














Table 3 Summary of Soil Sample Results - Organics AB&I Foundry 7825 San Leandro Street Oakland, California

Sample ID	Depth	Date	TPHg	рнчт	MTBE	Chloroethane	Benzene	Ethylbenzene	Toluene	Xylenes, Total
Units	(feet)		(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)
DIMOCR COL	Resid	ential	100	100	8.4	10	0.12	33	29	31
RWQCB ESLs -	Comm	nercial	450	150	8.4	11	0.26	33	29	100
Former Three 10,00	00-Gallon USTs	;			_					
SB-01-05	5	10/30/2007	<0.02	65	NA	NA	<0.00028	<0.00028	<0.00019	< 0.00057
SB-01-10	10	10/30/2007	91	2.4	NA	NA.	<0.42	< 0.34	<0.42	<0.76
SB-01-20	20	10/30/2007	450	8.9	NA NA	NA	<0.41	4.9	<0.41	< 0.75
SB-01-28	28	10/30/2007	0.39	<0.18	NA	NΑ	<0.00029	<0.00029	<0.00019	< 0.00057
SB-02-03	3	10/30/2007	68	110	NA	NA.	<0.42	<0.34	<0.42	< 0.75
SB-02-15	15	10/30/2007	410	47	NA NA	NA	<0.41	7,4	1.5	30
SB-02-20	20	10/30/2007	1400	120	NA	N/A	<1	27	<1	62
SB-02-25	25	10/30/2007	0.28	< 0.18	NA	NA	<0.00029	<0.00029	<0.00019	<0.00058
88-03-05	5	10/30/2007	<0.02	<0.18	NA	NA	<0.00028	<0.00028	0.008	< 0.00057
SB-03-10	10	10/30/2007	1,3	1.4	NA	NA	0.0049	<0.00028	<0.00019	< 0.00056
88-03-15	15 -	10/30/2007	1400	660	NΑ	NA	<0.98	12	<0.98	<1.8
8-03-25	25	10/30/2007	<0.021	<0.18	NA	NA .	<0.0003	< 0.0003	<0.0002	< 0.0006
B-04-10	10	10/30/2007	<0.02	<0.18	NA	NA.	<0.00029	<0.00029	< 0.00019	< 0.00057
B-04-15	15	10/30/2007	790	44	NA	NA	<0.11	2.4	< 0.074	< 0.22
B-04-20	20	10/30/2007	470	4.3	NΑ	NA .	<0.38	4	<0.38	< 0.68
SB-04-24	24	10/30/2007	<0.021	<0.18	NA	NA	<0.0003	<0.0003	<0.0002	<0.0006
3B-05-05	. 5	10/31/2007	1,9	2700	NA	NA	< 0.0003	< 0.0003	<0.0002	<0,0006
SB-05-10	10	10/31/2007	4.1	<0.18	NA	NA	0.012	< 0.0003	<0.0002	< 0.00059
SB-05-20	20	10/31/2007	78	22	NA	NA	< 0.42	< 0.34	<0.42	< 0.76
SB-05-25	25	10/31/2007	<0.02	<0.18	NA	NA	<0.00028	<0.00028	<0.00019	<0.00056
SB-08-15	15	10/31/2007	2.2	13	NA	NA	< 0.00029	< 0.00029	<0.00019	< 0.00057
SB-08-20	20	10/31/2007	1.9	<0.18	NA	NA	< 0.00027	< 0.00027	<0.00018	< 0.00054
SB-09-10	10	10/31/2007	4.6	240	NA.	NA	<0.0003	< 0.0003	<0.0002	< 0.0006
SB-09-15	15	10/31/2007	160	450	NA	NA	<0.4	< 0.33	<0.4	< 0.73
ormer 550-Gallon	Gasoline UST				•					
SB-10-05	5	10/31/2007	320	50	NA.	NA	<0.4	< 0.33	<0.4	< 0.73
SB-10-10	10	10/31/2007	450	38	NA	NA	<0.4	1.4	<0.4	<0.72
SB-10-15	15	10/31/2007	330	82	NA	N/A	<0.4	<0.32	<0.4	<0.72
B-10-20	20	10/31/2007	5.4	5.1	NA	NA NA	<0.00029	< 0.00029	<0.00019	<0.00057
SB-10-25	25	10/31/2007	<0.02	<0.18	NA	NA	<0.00029	< 0.00029	<0.00019	< 0.00058
SB-11-05	5	11/1/2007	8.6	NA	NA	NA	<0.0006	<0.0006	<0.0004	< 0.0012
SB-11-10	10	11/1/2007	71	NA	NA	NA	<0.38	<0.31	<0.38	< 0.69
SB-11-20	- 20	11/1/2007	<0.021	NA	NA	NA	<0.0003	<0.0003	<0.0002	< 0.00059
SB-12-05	5	11/1/2007	<0.02	NA	NA	NA	<0.00028	<0.00028	< 0.00019	< 0.00057

Table 3 Summary of Soil Sample Results - Organics

AB&I Foundry 7825 San Leandro Street Oakland, California

Sample ID	Depth	Date	TPHg	TPHd	MTBE	Chloroethane	Benzene	Ethylbenzene	Toluene	Xylenes, Total
Units	(feet)		(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)
RWQCB ESLs	Resid	lential	100	100	8.4	10	0.12	33	29	31
RWQCB ESES	Comm	nercial	450	150	8.4	· 11	0.26	33	29	100
SB-12-10	10	11/1/2007	<0.02	NA	NA	NA	<0.00028	<0.00028	<0.00019	< 0.00057
SB-12-15	15	11/1/2007	250	NA	NA	NA	<0.39	< 0.32	<0.39	<0.71
SB-12-25	25	11/1/2007	<0.02	NA	NA	NA NA	<0.00029	< 0.00029	<0.00019	<0.00058
SB-13-05	5	11/1/2007	<0.019	NA	NA	NA	<0.00027	< 0.00027	<0.00018	<0.00055
SB-13-10	10	11/1/2007	0.91	NA	NA	NA	< 0.0003	< 0.0003	<0.0002	< 0.0006
SB-13-15	15	11/1/2007	78	NA	NA	NA	<0.38	<0.31	<0.38	< 0.68
SB-13-25	25	11/1/2007	420	NA	NA	NA	< 0.42	< 0.34	<0.42	< 0.75
SB-14-03	3	11/1/2007	<0.02	NA	NA	NA	<0.00028	<0.00028	< 0.00019	< 0.00056
SB-14-10	10	11/1/2007	<0.02	NA	NA	NA	<0.00029	<0.00029	<0.00019	<0.00058
SB-14-15	15	11/1/2007	30	NA	NA	NA NA	<0.00093	<0.00093	<0.00062	< 0.0019
SB-15-05	5	11/1/2007	<0.019	NA	NA	NA	<0.00027	<0.00027	<0.00018	< 0.00055
SB-15-10	10	11/1/2007	<0.02	NA NA	NA	NA	<0.00028	<0.00028	<0.00019	< 0.00056
SB-15-15	15	11/1/2007	1100	NA	NA	NA	<0.39	<0.31	< 0.39	<0.7
SB-15-19	19	11/1/2007	7.9	NA	NA	NA	< 0.0004	0.019	<0.00026	< 0.00079
Former 8,000-Gall	on Mineral Spir	its/ 1,1,1-TCA US	ST			and the same	20583			
SB-22-03	3	11/2/2007	0.29	90	<0.00046	< 0.00055	<0.00021	< 0.00042	<0.00039	< 0.0015
SB-22-05	5	11/2/2007	<0.02	16	<0.00046	< 0.00055	<0.00021	< 0.00042	<0.00039	< 0.0015
SB-22-10	10	11/2/2007	0.99	150	<0.00045	< 0.00053	<0.00021	<0.00041	<0.00038	< 0.0015
SB-22-15	15	11/2/2007	<0.02	<0.18	< 0.00047	< 0.00055	<0.00021	<0.00042	< 0.0004	< 0.0016
SB-23-03	3	11/2/2007	2.1	110	< 0.00045	0.055	<0.0002	<0.00041	<0.00038	< 0.0015
SB-23-05	5	11/2/2007	0.45	190	<0.00044	< 0.00053	<0.0002	<0.0004	<0.00038	< 0.0015
SB-23-10	10	11/2/2007	0.25	69	< 0.00044	< 0.00053	<0.0002	<0.0004	<0.00037	< 0.0015
SB-23-15	15	11/2/2007	<0.02	<0.18	< 0.00045	< 0.00053	<0.00021	< 0.00041	<0.00038	<0.0015
SB-24-03	3	11/2/2007	1.2	170	<0.091	<0.11	<0.042	<0.083	<0.077	<0.31
SB-24-05	5	11/2/2007	1.1	61	<0.00044	0.022	<0.0002	< 0.0004	<0.00037	< 0.0015
SB-24-10	10	11/2/2007	0.69	<0.18	<0.00046	< 0.00054	<0.00021	< 0.00042	<0.00039	<0.0015
SB-24-20	20	11/2/2007	<0.02	<0.18	<0.00045	< 0.00054	<0.00021	< 0.00041	<0.00038	<0.0015
SB-26-04	4	11/2/2007	380	5800	<8.9	<11	<4.1	<8.1	<7.6	<30
SB-26-10	10	11/2/2007	72	19	<0.093	<0.11	<0.043	<0.084	<0.079	<0.31
SB-26-15	15	11/2/2007	<0.02	<0.18	<0.00046	<0.00055	<0.00021	<0.00042	<0.00039	<0.0016

Table 3

Summary of Soil Sample Results - Organics

AB&I Foundry

7825 San Leandro Street Oakland, California

Sample ID	Depth	Date	TPHg	TPHd	MTBE	Chloroethane	Benzene	Ethylbenzene	Toluene	Xylenes, Total
Units	(feet)		(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)
RWQCB ESLs	Reside	ntial	100	100	8.4	10	0.12	33	29	31
RWQCB ESLS	Comme	ercial	450	150	8.4	11	0.26	33	29	100
Former 10,000-Ga	allon Diesel UST						_			
SB-27-3	3	11/5/2007	NA	100	NA	NA	NA	NA	NA	NA
SB-27-5	5	11/5/2007	NA	6	NA	NA	NA	NA	NA	NA
SB-27-10	10	11/5/2007	NA	<0.18	NA	NA	NA	NA	NA	NA
SB-27-15	15	11/5/2007	NA	<0.18	NA	NA	NA	NA	NA	NA
SB-28-06	6	11/2/2007	<0.02	64	<0.00056	NA	<0.00028	<0.00028	<0.00019	<0.00056
SB-28-10	10	11/2/2007	<0.019	120	<0.00055	NA NA	<0.00027	<0.00027	<0.00018	<0.00055
SB-28-15	15	11/2/2007	<0.021	<0.18	NA	NA	<0.0003	< 0.0003	<0.0002	<0.00059
SB-29-6	6	11/5/2007	NA	13	NA	NA	NA	NA	NA	NA
SB-29-10	10	11/5/2007	NA	<0.18	NA	NA	NA	NA	NA	NA
SB-29-15	15	11/5//2007	NA	<0.18	NA	NA	NA	NA	NA	NA
SB-28-20	20	11/2/2007	<0.02	<0.18	NA	NA	<0.00029	<0.00029	<0.00019	<0.00058

Notes:

MTBE - Methyl tert butyl ether < 0.005

- Not reported at or above laboratory's reporting limit of 0.005 mg/kg

(mg/kg) TPHg

- milligrams per kilogram - Total Petroleum Hydrocarbons as Gasoline UST

- underground storage tank 1,1,1-TCA - 1,1,1-Trichloroethane

TPHd

- Total Petroleum Hydrocarbons as Diesel

-TPHg, BTEX, VOCs and fuel oxygenates analyzed using EPA Method 8260B by Test America Laboratories (TAL), Pleasanton, California

-TPHd analyzed using EPA Method 8015M with silica gel cleanup by TAL, Pleasanton, California

RWQCB ESLs - Environmental Screening Levels taken from the California Regional Water Quality Control Board, San Francisco Bay Region document entitled "Screening for Environmental Concerns at Sites with Contaminated Soil and Groundwater," Interim Final November 2007, groundwater is not a current or potential source of dnnking water.

-Concentrations in bold exceed commercial ESLs for shallow soil (less than 3 meters).

Table 4 Summary of Soil Sample Results - PAHs AB&I Foundry 7825 San Leandro Street Oakland, California

Sumple ID	Dopin	Date	Naph-thalane	Acenaphiene	Fluorena	Phonanthrene	Anthracene	Fluorantheng	Pyrene	Benzo[a]anthracene	Chrysene	Benzo[b]flupranthono	Benzolk/Ruoranthana	Benzolajpyrone	Indeno[1,2,3-ed]pyrere	Benzolg,h.Upreytene	2-Methylnaphtalane	Ofbenz(1,h)anthraccne
Units	(feæt)		(mg/Kg)	(mg/Kg)	(mg/Kg)	(mg/Kg)	(mg/Kg)	(mg/Kg)	(mg/Kg)	(mg/Kg)	(mg/Kg)	(mg/Kg)	(mg/Kg)	(mg/Kg)	(mg/Kg)	(mg/Kg)	(mg/Kg)	(mg/Kg)
RWQCB	Resid	lential	1.3	160	410	40	40	40	600	0,38	40	0,38	0,38	0.038	0.62	35	12	D.062
ESLs	Comm	nercial	2.8	160	1000	40	40	40	1000	1.3	40	1,3	1.3	0.13	2.1	35	12	0.21
Former 8,000-	Gallon Mine	ral Spirits/ 1	,1,1-TCA	UST			3			-	40 40							
38-26-4	4	11/2/2007	2100	1300	1300	4500	1300	3100	2400	1100	1300	1000	450	960	460	380	630	140
55-26-10	10	11/2/2007	0.76	0.65	0,57	2.0	0.42	1,2	0.92	0.30	0.26	0.29	0.090	0.23	0,10	0.084	0.32	<0.067
\$8-26-15	15	11/2/2007	< 0.067	<0.067	<0.067	0,15	< 0.067	0.12	0,085	< 0.33	<0.067	<0,067	<0.067	<0.067	< 0.067	<0,067	<0.067	< 0.067

Nides

(ուցմեց) <0.067

-miligrams per kilogram

- Not reported at its above laboratory's reporting limit of 0.067 mg/kg

-Polycyclic Architect Hydrocurrens (PArts) analyzed using EPA Method 1270BC by Territorics Laboratories (TAL), Pjeasanton, California

RWQCB ESLs to the state of the

-Concentrations in bold exceed commercial ESLs for shallow sed (less than 3 meters)

Table 3 Summary of Soil Sample Results - Organics

AB&I Foundry 7825 San Leandro Street Oakland, California

Sample ID	Depth	Date	TPHg	TPHd	Benzene	Isopropylbenzene	n-butylbenzene	sec-butylbenzene
Units	(feet)	Short	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)
DWOCD ECL	Res	idential	180	180	2	NE	NE	NE
RWQCB ESLs	Con	nmercial	180	180	2	NE	NE	NE
Former Three 10,	000-Gallon	USTs				•		73
SB-44-15	15	7/11/2008	150	580	0.11	0.45	0.47	0.27
SB-44-25	25	7/11/2008	0.22	1,1	<1.0	<0.80	<0.78	<0.68
SB-45-5	5	7/10/2008	<1.0	<1.0	<5.0	<5.0	<5.0	<5.0
SB-45-15	15	7/10/2008	66	<1.0	<250	<250	<250	<250
SB-45-20	20	7/10/2008	360	<1.0	<250	<250	0.25	<250
Former 550-Gallo	n Gasoline	UST						-
SB-42-40	40	7/9/2008	<1.0	<1.0	<5.0	<5.0	<5.0	<5.0

Notes:

(mg/kg)

- all concentrations expressed in milligrams per kilogram (mg/Kg)

TPHg TPHd - Total Petroleum Hydrocarbons as Gasoline - Total Petroleum Hydrocarbons as Diesel

-VOCs analyzed using EPA Method 8260B by Advanced Technology Laboratories (ATL), Signal

-TPHg and TPHd analyzed using EPA Method 8015M with silica get cleanup by Advanced Technology Laboratories (ATL), Signall Hill, California

RWQC8 ESLs - Environmental Screening Levels taken from the California Regional Water Quality Control Board, San Francisco Bay Region document entitled "Screening for Environmental Concerns at Sites with Contaminated Soil and Groundwater," Interim Final November 2007, updated May 2008, Residential and Commercial/Industrial land use.

-Concentrations in bold exceed commercial ESLs for deep soil (greater than 3 meters).

Table 1 Summary of Analytical Results Monitoring Well Soil Samples (mg/kg)

February 1993

	Depth	Total Oil & Grease	Hydrocarbon Oil & Grease	Total Organic Lead	TPE-Diesel	TPH-Gasoline	Beazeae	Toluene	Ethyl-benzene	Xylenes
Well ID	(feet)	בֿיַ	र्ह्म अ	. ∺ 7	=	_ F	ğ	Ĕ	ធ	×
MW-1	11				34	ND	ND	ND	ND	ND
MW-2	10,5	3,500	3,500	_	140	63	ND	0.039	ND	800.0
MW-3	10	-	-			ND	МD	DM	ND	QN
MW-4	14.5	-	-	0.6	-	2,100	מא	DN	MD	ИD
MW-4	25.5	-	-	ND	-	ND	ND	DM	ND	MD

Notes:

ND: Not detected above laboratory reportable detection limit.

B: Not analyzed.

TABLE 2

SOIL- AND WATER-QUALITY RESULTS AMERICAN BRASS AND IRON FOUNDRY 8,000 GALLON 1,1,1,-TCA TANK REMOVAL 7825 SAN LEANDRO STREET DAKLAND, CALIFORNIA

			1		Petroleur	n Hydrocar	bons			EPA 8010 Ana	lytes	
Sample Number	Date Collected	Depth (feet)	TPH as* Gesoline	TPH as** Diesel	Benzen e	Toluene	Ethyl- benzene		1,1,1,-Tri- chloroethane		1,1 Di- chloroethen	Chloro e ethane
Soil Sample	es (results i	n millig	rans per k	ilogram [r	ng/kg])		pro	then Junio	3 3010	3900	.082	2200
13-H-10 13-N2-8 13-S-10 13-SP-1 13-SP-2 13-E-7.5	04-0ct-91 04-0ct-91 04-0ct-91 04-0ct-91 04-0ct-91 04-0ct-91	10 8 10 1 2 7.5	500 0.6 13 18 <0.1	34 <1 7 8 <1	<0.005 <0.02 <0.02 <0.02 <0.005	<0.02	3 0.015 0.12 0.16 <0.005	6 0.6 0.39 0.34 <0.005	<0.1 0.14 1.30 0.19 0.02	<0.1 0.05 0.50 0.23 0.03	<0.1 <0.01 0.06 0.02 <0.01	<0.1 <0.01 0.67 1.10 0.33
Jater Sampl	es (results	in milli	grams per	liter [mg/	(l])			• • - • - • • • •	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,			
3-GRAB	04-0ct-91		11.000	****	0.130	0.310	0.260	2.200	22.000	4.900	<.100	7.000

NOTES:

All samples were analyzed by BC Anayltical Laboratory, Emeryville, California (BCA).

TPH = Total Petroleum Hydrocarbons

- * TPH as gesoline is reported by BC Analytical Laboratory as C6 to C12 Hydrocarbons
- ** TPH as diesel is reported by BC Analytical Laboratory as Co to Ca Hydrocarbons
- ---- Samples were not analyzed for the above analytes.
- < Concentrations below laboratory detection limits.

No other EPA 8010 analytes were detected in these samples.

Samples 73-SP-1 and 73-SP-2 were collected from a stockpile of soils around the tank.

TABLE 1

Soil and Water Quality Results
American Brass & Tron Foundry
12,000 Gallon Diesel Tank Removal
7825 San Leandro Street
Oakland, CA

			Extractable Eydrocarbons as			oil Matrix) EPA 8020	
Sample Mumber	Date Collected	<u>Depth (feet)</u>	Diesel (mg/kg)	Benzene	Toluene	Behylbenzene	Kilcaes, Total
Soil Samples (resu	ilts in milligrams p	er kilogram (mg/k	s])				
DEW 1-8-9	6-5-92	9	ND	N D	ND	מא	ан
DEW 2-N-9	6-5-92	9	MD	מא	. ND	σκ	סא
DEV 3-N-8.5	6-5-92	8.5	MD	~	•	-	
DEV 6-4-8	5-5-92	В	MO	ДK	ND	ND	αр
DEW 5-5-8.5	6-5-92	8.5	NO	•	~	-	-
DEW 6-5-9	6~5-92	9	2	ND	ø Ø	ND	MD
Water Samples (cos	cults in milligrams	per liter [mg/l])					
D-Groundwater	6-5-92	10	6.6	מא	WD	КD	ИО

RSTOK:

All samples were analyzed by Quanteo Laboratories.

TABLE 1

SOIL QUALITY RESULTS 550-GALLON UNDERGROUND GASOLINE TANK REMOVAL AMERICAN BRASS AND IRON FOUNDRY 7825 SAN LEANORD STREET CAXLAND, CALIFORNIA

(all results in milligrams per kilogram (mg/kg))

THE REMOVE DE	14 mm 24 mm 27 mm	وي من حيد ه	COMPANY AREA OF THE	÷•••	F-1-51-5-LV			- 2 - C) - C - C - C - C - C - C - C - C -
Sample	Date	Depth	TPH 48*			Ethyl-		Organic
Humber	Collected	(1001)	Gasoline	8402204	Toluene	benzone	Xylenes	Load
			**	• • • • • • • • • • • • • • • • • • • •				
12-N-8.5₩	26-Aug-91	8.5	2000	<2	8	15	81	` ∢1
72-S-6**	26-Aug-91	6	410	<	3	14	15	<1
T2-NT1-6.5	04-Sep-91	6.5	40.1	<0.005	<0.005	0.010	0.006	
12-N11-9.5	04-Sep-91	9.5	0.52	<0.005	0.011	0.029	0.060	
72-57-6.5	04-Sep-91	6.5	<0.1	<0.005	<0.005	<0.005	<0.005	
12-ET-9.5	04-Sep-91	9.5	40.1	<0.005	₹0.005	0.009	0.014	
12-SE-8.5	12-Sep-91	8.5	0.1	<0.005	<0.005	0.027	0.019	***
12-NE-9	12-8ep-91	9	<0.1	<0.005	<0.005	0.013	0.012	••••
T2-BASE-13	12-8 ep-91	13	78	40.05	0.21	0.2	3.3	****
12-NW-9	12-Sep-91	9	100	<0.05	0.52	3.1	3.1	
SP2-K	27-Sep-91	1	0.3	<0.005	<0.005	0.010	0.012	
\$P2-\$	27-Sep-91	t	<0.1	<0.005	40,005	<0.005	<0.005	
	•							

nen karangan karangan

HOTES:

All samples were enalyzed by BC Anayltical Laboratory, Emergyille, California.

Samples SP2-W and SP2-S were post-seration stockpile samples from soil excavated around the tank. The depth refers to the depth from the top of the stockpile.

Static ground water was not encountered.

- TPH Total Petroleum Hydrocarbona
- 1PX as gasoline is reported by 8C Analytical Laboratory as C6 to C12 hydrocarbons.
- These samples do not represent existing native soits due to re-excevation
- ---- Not enalyzed

TABLE 1A - SOIL RESULTS

BENZENE, TOLUENE, ETHYLBENZENE AND XYLENES

Results in Parts Per Million (ppm)

		CONSTI	TUENTS	
Sample Location	Benzene	Toluene	Ethylbenzene	Xylenes
MW-1 at 11'	ND	ND	ND	ND
MW-2 at 10.5'	ND	0.039	ND	0.008
MW-3 at 10'	ND	ND	ND	ND
MW-4 at 14.5'	6.6	4.1	7.0	17
MW-4 at 25.5'	ND	ND	ND	ND

ND - None Detected

TABLE 1B - SOIL RESULTS

TOTAL PETROLEUM HYDROCARBONS (TPH) AS GASOLINE AND DIESEL, TOTAL AND HYDROCARBON OIL AND GREASE, TOTAL ORGANIC LEAD, AND VOLATILE HALOCARBONS

Results in Parts Per Million (ppm)

			CONS	TITUENT	MESON	S
Sample Location	TPH Gasoline	TPH Diesel	Total Oil & Grease	Hydrocarbon Oil & Grease	Total Organic Lead	Volatile Halocarbons
MW-1, 11'	ND	34		w		
MW-2, 10.5'	63	140	3500	3500		}
MW-3, 10'	ND					
MW-4, 14.5'	2100				0.6	
MW-4, 25.5'	ND	_		_	ND	

ND - None Detected - Not Tested



TABLE 1

SOIL- AND WATER-QUALITY RESULTS 8,000-GALLON UNDERGROUND GASOLINE TANK REMOVAL AMERICAN BRASS & IRON FOUNDRY 7825 SAN LEANDRO STREET OAKLAND, CALIFORNIA

Sample	Date	Depth	JPH as	Benzene	tolueno	Ethyl-	Xyt enes
	Collected					benzene	
							• • • • • • • • • • • • • • • • • • • •
Soil Samples	-		,				
71-N-10.5 *	19-guA-80	10.5	820	<13	<13	40	120
11-2-11	08-Aug-91	11	0.5	<0.005	<0.005	0.018	0.0
T1-W-11	08-Aug-91	11	<0.1	<0.005	<0.005	<0.005	<0.00
T1-NE-17 *	08-Aug-91	11	1.8	0.11	0.01	0.19	0.1
T1-E-11	19-Aug-91	11	<0.1	<0.005	<0.005	<0.005	<0.00
T1-N2-10	19-Aug-91	10	<0.1	<0.005	<0,005	<0.005	<0.00
T1-NE2-10	19-Aug-91	10	<0.1	<0.00\$	<0.005	<0.005	<0.00
11-N-7	26-Aug-91	7	<0.1	<0.005	<0.005	<0.005	<0.00
11-พม-10	26-Aug-91	10	<0.1	<0.005	<0.005	<0.005	<0.00
12-SP-W	12-Sep-91	~~~	<0.1	<0.005	<0.005	<0.005	<0.00
12-SP-W	12-Sep-91	•••	0.70	<0.02	<0.02	<0.02	<0.02
Water Sample				-			
T1-WATER *						7 700	14.00
	•						
olt Water	20-AUG-91	-	0.150	0.0032	0.0026	0.0062	0.02

NOTES:

All samples were analyzed by BC Analytical Laboratory, Emeryville, California.

Excavation depth to water was 10.5 feet on August 8, 1991, and 9.5 feet on August 20, 1991.

Samples T2-SP-W and T2-SP-E were post-aeration stockpile samples from soil excavated around the tank.

TPH = Total Petroleum Hydrocarbons

- * These samples do not represent existing native soils and ground water due to re-excavation and ground-water pumping.
- ** TPH as gasoline is reported by BC Analytical Laboratory as C6 to C12 hydrocarbons.

Table 5 Summary of Soli Sample Results - Metals AB&I Foundry 7825 San Leandro Street Oakland, California

Sample ID	Depth	Data	Antimony	Arsenic	Sarium	Beryllium	Cadmium	Chromlum	Coball	Copper	Lead	Mercury	Molybdenum	Nickel	Selenium	Silver	Thallium	Vanadium	Zinc
Units	(feet)		(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(ang/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)
RWQCB ESLs	Resid	dential	6.1	0.36	760	4	1.7	750	40	230	200	1	40	150	10	20	1.2	15	600
MANGES ESTS	Comr	nercial	40	15	1500	8	7,4	750	80	230	750	1	40	150	10	40	15	190	690
Background			<10	42	410	1.1	5.6	120	25	63	57	0,5	<5	270	5.1	3	10	90	140
Former Three 10,	000-Gallon (J\$Ts																	
\$8-01-05	5	10/30/2007	<0.05	4.2	180	0.67	<0.0033	37	8.8	22	19	0.065	3.1	32	<0.11	<0.013	<0.072	31	44
SB-01-10	10	10/30/2007	<0.051	6.8	130	0.66	<0.0033	36	7.8	20	3.8	0.09	<0.042	34	<0.11	< 0.013	<0.073	37	30
Former 650-Gallo	n Gasoline i	JST																	
SB-13-05	5	11/1/2007	<0.05	5.5	190	1.7	<0.0033	310	5.1	77	36	<0.00099	7.1	32	7,8	2.7	16	480	320
\$8-13-10	10	11/1/2007	<0.05	4	140	0.5	<0.0032	37	11	21	4.6	0.056	<0,041	27	40.1	<0.013	<0.071	40	32
Former 8,000-Gal	ion Minerai :	Spirits/ 1,1,1-1	CA UST							-									
SB-22-05	5	11/2/2007	<0.053	4.3	150	<0.0036	<0.0035	40	12	22	5	0.058	<0.044	30	<0.11	<0.014	<0.076	44	36
SB-22-10	10	11/2/2007	<0.05	14	180	0,59	<0.0032	48	18	42	130	0.11	2.6	42	<0.1	<0.013	<0 071	48	110
SB-24-20	20	11/2/2007	<0.047	2.6	300	<0.0032	<0.0031	35	13	23	5	<0.00096	<0.039	41	<0.099	< 0.012	<0.068	30	37
SB-26-10	10	11/2/2007	<0.051	5.8	100	0.59	<0.0033	53	17	34	4.9	0.06	< 0.042	67	<0.11	<0,013	<0.073	72	100
SB-26-15	15_	11/2/2007	<0.05	2.2	120	0.54	< 0.0032	3.5	7.9	18	4	D 053	<0.041	44	<0.1	<0.013	<0.071	31	35
\$8-26-04	4	11/2/2007	3,1	13	19	<0,0034	<0.0033	130	10	240	28	<0.001	19	87	<0.71	<0.013	<0.073	35	57
Former 10,000-Ga	illon Diesel	UST																	
SB-28-06	8	11/2/2007	2.4	3.9	330	0,68	3.4	31	3	60	970	0.11	3.6	15	<0.1	<0.013	<0.071	12	550
88-28-10	10	11/2/2007	<0.053	10	130	< 0.0035	<0.0034	11	5.4	21	110	0.51	<0.044	11	<0.11	<0.014	<0.075	22	120

Notes,

(mq/kg)-infligrants per Allogram.

- Not reported at at above luberatory's reporting limit of 0 0033 mg/kg <0.0033

UST - undergrowed storage tank

I 1 S-FCA - 13 1-Trichtorogham

-CAM 17 Minute arraying using EPA Minute 6010B/7471A by Test Assertion Laboratories (TAL). Pleasanton Cultionia

RWCCB ESt. * Environmental Consentral Laboratory for Environmental Consentral States with Consentral States and Groundware.*

Interior Final November 2007, growedwater is not a current or policinal source of dressing water.

-Concentrations in pold exceed commercial ESUs for Shallow tail (less than 3 molers)

-Back and data and from Law to the Boy N and Law by E formental Restoration Program, Soil Man 1990.

Table 2 Summary of Soil Gas Sample Results AB&I Foundry 7825 San Leandro Street Oakland, California

Sample ID	Depth	Sample Matrix	PCE	Chloroethane	Benzene	Toluene	Ethylbenzene	m,p-xylene
Units	(feet)		(µg/l)	(µg/l)	(µg/l)	(µg/l)	(µg/l)	(µg/l)
RWQCB	Res	sidential	0.41	21	0.084	63	210	21
ESLs	Cor	nmercial	1,4	58	0.28	180	580	58
Former 8,000-0	Gallon Miner	al Splrits/ 1,1,1-TC	A UST	<u> </u>	_			
\$G-1	5	Soil	<0.10	0.2	0.31	<0.20	<0.10	<0.20
SG-2	5	Soil	<0.10	<0.10	<0.080	<0.20	<0.10	<0.20
SG-3	5	Şoil	<0.10	<0.10	<0.080	<0.20	<0.10	<0.20
Former 550-Ga	ıllon Gasolin	e UST						
SG-4	5	Soil	0.12	<0.10	0,11	0.22	2	0.63
SG-5	5	Soil	<0.84	<0.84	0.96	<0.84	13	3.4
SG-6	5	Soil	<0,10	<0.10	<0.080	<0.20	0.27	<0.20
Former Three	10,000-Galio	ก USTs						
SG-7	5	Soil	<0.10	<0.10	<0.080	<0.20	<0,10	<0.20
\$G-8	5	Soil	<0.41	<0.41	<0.33	<0.41	1.7	0.48
SG-9	5	Soil	<0.10	<0.10	<0.080	<0.20	0,56	<0.20
Parking Lot Ar	ea							
\$G-10	5	Soil	<0.10	<0.10	0.21	0.26	0.28	<0.20

Notes:

(µg/l) - micrograms per liter

PCE - letrachioroethylene

<0.20 - Not reported at or above faboratory's reporting limit of 0.20 µg/L

1,1,1-TCA - 1,1,1-Trichloroethane

- Samples analyzed using EPA Method 82608 by Arroxics Laboratories, Folsom, California

RWQCB ESLs - Environmental Screening Levels taken from the California Regional Water Quality Control Board, San Francisco Bay Region document entitled "Screening for Environmental Concerns at Sites with Contaminated Soil and Groundwater," Interim Final

November 2007, commercial use ESLs.

UST - underground slorage tank

Table 2 Summary of Soll Gas Sample Results **AB&I Foundry**

7825 San Leandro Street Oakland, California

Sample ID	Purge Volume	Depth (feet bgs)	Date	PCE	TCE	1,1-DCE	1,1,-DCA	Benzene	Toluene	Vinyl Chloride	m,p-xylene
RWQCB ESLs		Residential Commercial		0.41	1.2	42 120	1.5 5.1	0.084 0.28	63 180	0.031	21 58
SG-11	1	5.0	7/7/08	<0,1	<0.1	0.15	0.19	<0.08	0.23	<0.05	<0.2
SG-11		5.0	7/7/08	<0,1	<0.1	0.16	0.19	<0.08	<0.1	<0.05	<0.2
SG-11	7	5.0	7/7/08	<0.1	<0.1	0.16	0.19	<0.08	<0.1	<0.05	<0.2
SG-12	1	5.0	7/7/08	<0.1	<0.1	<0.1	<0.1	<0.08	0.27	2.1	<0.2
SG-12 (D)	1	5.0	7/7/08	<0.1	<0.1	<0.1	<0.1	<0.08	0.32	2.9	<0,2
SG-13A	1	Sub Slab	7/7/08	<0.1	<0.1	<0.1	<0.1	<0.08	<0.1	<0.05	<0.2
SG-13B	1	5.0	7/7/08	<0.1	<0.1	<0.1	<0.1	<0.08	<0.1	<0.05	<0.2
SG-14	1	5.0	7/7/08	<0.1	<0.1	<0.1	<0.1	<0.08	<0.1	<0.05	<0.2
SG-16A	1	Sub Slab	7/7/08	3.2	0.14	<0.1	<0.1	<0.08	<0.1	<0.05	0.22
SG-16B	1	5.0	7/7/08	0.58	<0.1	<0.1	<0.1	0.17	<0.1	3.7	<0.2

Notes:

- all concentrations expressed in micrograms per liter (µg/l)

- Duplicate sample (D)

feet bgs - feet below ground surface

PCE

Tetrachloroethene

TCE

- Trichloroethene

1,1 - DCE

- 1,1 - Dichloroethene

1.1 - DCA

1,1,1-TCA

- 1,1 - Dichloroethane - 1,1,1-Trichloroethane

< 0.10

- Not reported at or above laboratory's reporting limit of 0.10 µg/L

- RWQCB ESLs Environmental Screening Levels taken from the California Regional Water Quality Control Board, San Francisco Bay Region document entitled "Screening for Environmental Concerns at Sites with Contaminated Soil and Groundwater," Interim Final November 2007, updated May 2008, Residential and Commercial/Industrial Land Use.
 - Samples analyzed using EPA Method 8260B by Transglobal Environmental Geochemistry, Rancho Cordova, California
 - Concentrations In bold exceed ESLs for Indoor air vapor intrusion concerns Commercial/Industrial Use

Table 1 Summary of Soil Gas Sample Results AB&I Foundry

7825 San Leandro Street Oakland, California

Sample 1D	Purge Volume	Depth (feet bgs)	Date	PCE	Benzene
RWQCB ESLs		Commercial		1.4	0.28
SG-17	1	1.5	3/13/09	<0.1	<0.08
SG-18	1	1.5	3/13/09	<0.1	0.15
SG-18 (D)	1	1.5	3/13/09	<0.1	0.15
SG-19	1	1.5	3/13/09	3.1	<0.08
SG-19 (D)	1	1,5	3/13/09	3	<0.08

Notes:

µg/L

- all concentrations expressed in micrograms per liter (µg/l)

(D)

- Ouplicate sample

leel bgs

- feet below ground surface - Tetrachloroethene

PCE <0.10

- Not reported at or above laboratory's reporting limit of 0.10 µg/L

RWOCB ESLs - Environmental Screening Levels taken from the California Regional Water Quality Control Board, San Francisco Bay Region document entitled "Screening for Environmental Concerns at Sites with Contaminated Soil and Groundwater," Interim Final November 2007, updated May 2008, Residential and Commercial/Industrial Land Use.

- Samples analyzed using EPA Method 8260B by Transglobal Environmental Geochemistry. Rancho Cordova, California
- Concentrations in bold exceed ESLs for indoor sir vapor intrusion concerns -Commercial/Industrial Use

Table 5 Summary of Groundwater Sample Results - Organics AB&I Foundry 7825 San Leandro Street Oakland, California

Sample ID	Depun	Date	rPHg	грна	MTBE	rBA	1,1 - DCA	1,1 - DCE	cls 1,2-DCE	Benzene	Chloro- athane	Dishlora- Denzene	Ethyl- benzene	Naph- thalone	Toluene	1,1,1.TCA	ICE	Ylnyl	Xyfenes, Total
Units	(feet)		(ug/L)	(ug/L)	(495)	(ug/L)	(Jope)	(Ug/L)	(ug/L)	(ug/L)	(ug/L)	(UD/L)	(ug/L)	(ug/L)	(1/g/L)	(Jigu)	(ug/L)	(ug/L)	(LPg/L)
RWQCB ESLA			5,000	2,500	1,800	50,000	1,000	6,300	6,200	540	160	100	300	210	400	\$0,000	530	3.8	5,300
RWQC8 E5Ls1			100	100	6	NE	6	6	6	1	12	10	30	17	40	200	- 6	0.5	20
Former Three 10,0	00_Gallor	BSTe		-										- 75	152	- 500	100	600	-
MW-9	5-20	10/25/2007	1300	120	<0.50	15	<0.50	<0.50	<0.5	89 -	<10	<0.60	6	<1	2	<5	<0.50	<5	(1
SB-01-GW24 5	24.5	10/30/2097	.180	51	<0.13	<2.3	<0.059	<0.054	<0.11	0.75	<0.21	<0.05	32	1.5	0.67	<0.046	<0.063	<0.04	1.5
SB-06-GW23	23	10/31/2007	<28	110	<0.13	<23	<0.059	<0.054	<0.11	< 0.035	<0.21	<0.05	<0.039	<0.096	0.52	<0.046	c 0.063	40.04	40.49
SB-07-GW17	17	10/31/2007	2900	610	<0.13	<7.3	<0.059	<0.054	<0.11	37	40.21	<0.05	19	17	<0.049	<0.046	<0.083	<0.04	1.4
\$8-7-GW17 (D)	17	10/31/2007	4600 -	450	NA	NA	<0.059	<0.054	<0.11	45	<0.21	<0.05	17	16	<0.049	<0.046	<0.063	< 0.04	1.7
SB-08-CW1T	17	10/31/2007	19000	6100	<6.3	<2.3	< 0.59	< 0.054	<1.1	< 0.35	<2.1	<0.5	22	15	<0.49	<0.46	<0.63	<0.4	<4.9
SB-09-GW11	17	10/31/2007	11000	27000	₹63	<23	<0.059	<0.054	<0.11	25	<0.21	1.5	4.3	2.7	9.8	<0.046	2.1	<0.04	25
SB-37-GW16-5	16.5	11/27/2007	<50	<50	9.1 -	<50	< 0.50	<0.50	<0.50	<0.50	<1.0	<0.50	<0.50	<1.0	0.89	<0.50	<0.50	<0.50	<10
\$8-37-GW16.5 (D)	16.5	11/27/2007	NA	NA.	11	NA	<0.50	<0.50	<0.50	<0.60	11.0	<0.50	₹0.50	<1.0	0.91	<0.50	<0.50	€0.50	<0.50
Former 550-Gallon	Gasoline	The second second										-	12000						
W.4	5-20	10/24/2004	<50	450	<9.50	<5.0	<0.50	<0.50	<0.5	<5	<10	<0.50	<5	<1	<6	<5	<0.50	-45	<1
58-17-GW26	20	11/2/2007	2390	660	0.57	<2.3	<0.059	<0.054	<0.11	3.3	<0.21	<0.05	18	1.6	1,8	<0.046	<0.063	<0.04	44
58-14-GW13	13	11/1/2007	1600	80	<0.25	<23	<0.059	<0.054	<0.11	1.1	<0.21	<c.d5< td=""><td>2.8</td><td><0.096</td><td>1,6</td><td><0.046</td><td>< 0.063</td><td><0.04</td><td>7,3</td></c.d5<>	2.8	<0.096	1,6	<0.046	< 0.063	<0.04	7,3
Former 8,000-Gallo					-		4.554	11000	7111	-	-151	7.44	2.0	*****		4.0.0		4.64	- 10
MW-2R	5-20	10/25/2007	150	<50	<0.50	<5.0	₹0.50	<0.50	<0.50	<5	<10	<0.52	<5	<1	<5	- 45	<0.50	<5	<1
S8-22-GW10	10	11/2/2007	1300	87	40.13	<2.3	<0.059	<0.054	<0.11	<0.035	<0.21	<0.05	<0.039	<0.096	<0.049	+0.046	<0.063	<0.04	<0.49
SB-25-GW10	10	11/2/2007	1500	1200	<0.13	<2,3	403	<0.27	<0.53	5.4	<1.1	<0.25	50	<0.48	200	<0.73	<0.32	<02	410
S8-26-GW10	10	11/2/2007	2100	37000	<0.13	<2.3	<12	<1.1	<21	<0.7	<4.2	<1	17	630	<0.98	<0.92	<1.3	<0.8	49.8
Parking Lot Area	- 577	The same of	-			-						_ 4	200			-			
MW-3	5-20	10/24/2007	540	<50	<0.50	<5.0	180	680	5	<5	<10	<0.50	<5	41	<5	13	<0.50	7.5	<1
MW-5	5-20	10/25/2007	450	<50	<0.50	<5.0	2	15	1.5	<5	<10	<0.50	15	41	<\$	-45	<0.50	<5	<1
MW-6	5-20	10/24/2007	<50	110	<0.50	<5.0	40.50	<0.50	<0.50	<\$	<10	<0.50	<5	<1	<5	<5	<0.50	<5	<1
MW-B	5-20	10/25/2007	1200	<50	<0.50	<5.0	1600	1600	<0.50	<5	290	<0.50	<5	e1	<5	1700	€0,50	<5	<1
SB-16-GW15	15	11/1/2007	<28	<30	<0.13	<23	29	31	40.11	<0.035	< 0.21	<0.05	<0.039	<0.096	<0.049	16	0.58	<0.04	<0.49
\$8-16-GW15 (D)	15	11/1/2007	220	<30	<0.13	<23	26	35	<0.11	<0.035	<0.21	<0.05	<0.039	<0.096	<0.049	15	0.63	<0.04	<0.49
SB-17-GW15	15	11/1/2007	540	100	NA	NA	170	740	<21	<0,7	44.2	<1	<0.78	<19	<0.98	<0.92	<1.3	14	49.8
\$8-18-GN05	5	11/5/2007	330	160	<0.13	<2.3	250	660	<21	<0.7	28	<1	<0.78	<1.9	40.98	310	<13	<0.8	<9.8
\$8-19-GW15	15	11/5/2007	340	<30	< 0.13	<23	200	880	5	< 0.35	<21	<0.5	<0.39	<0.96	<0.49	<0.46	<0.63	10	c4 9
SB-20-GW15	15	11/5/2007	330	<30	<9.13	<2.3	200	950	<2.1	<0.7	<4.2	<1	<0.78	<1.9	<0.98	<0.92	<1.3	11	<9.8
SB-32-GW15	15	11/27/2007	NA	NA	<5.0	NA	<0.50	<0.50	<0.50	<0.50	<1.0	<0.50	0,62	<1.0	1.9	<0.50	<0.50	<0.50	3.3
8-33-GW15	15	11/27/2007	NA	NA	<5.0	NA	<0.50	<0.50	<0.50	<0.50	<1.0	<0.50	0.61	<1.Q	3.0	<0.50	<0.50	<0.50	3.4
6-34-GW15	15	11/27/2007	NA	NA.	<10	NA	<1,0	<1.0	€1.0	<1.0	<2.0	<1.0	<1.0	<2.0	2.2	<1,0	<1.0	<10	2.4
8-35-GW11.5	11.5	11/27/2007	NA	NA	<5.0	NA	<0.50	< 0.50	<0.50	<0.50	<1.0	<0.50	<0.50	<1.0	<0.50	<0.50	<0.50	<0.50	<1.0
36-GW11 5	11.5	11/26/2007	NA	NA	<5.0	NA	0.53	<0.50	<0.50	<0.50	1.6	<0.50	<0.50	<1.0	<0.50	<0.50	<0.50	<0.50	<1.0
Former 10,000-Gal	ion Diese	1UST	10.45									T 24					400		
I-yvM	5-20	10/25/2007	<50	450	<0.50	<5.0	<0.60	<0.50	45	<5	<10	<0.50	4	<1	<5	+5	<0.50	<5	<
MW-7 -	5-20	10/25/2007	<50	370	<0.50	<5.0	<0.50	<0.50	<5	<5	<10	<0,50	45	<1	<5	<5	40.50	<5	<1
SB-28-GW15	15	11/2/2007	<20	260	< 0.13	×2.3	<0.059	<0.054	<0.11	< 0.035	< 0.21	<0,05	<0.039	<0.096	0.52	<0.046	¢0.063	<0.04	<0.49
SB-29-GW15	15	11/5/2007	<28	.150	<0.13	12.3	<0.059	<0 D54	<0.11	<0.035	<0.21	<0.05	<0.039	<0.098	<0.049	< 0.046	<0.063	<0.04	<0.49

The Source Group

ATTACHMENT 5

Table 5 Summary of Groundwater Sample Results - Organics AB&I Foundry 7825 San Leandro Street

Oakland, California

Sample 10	Depth	Dale	TPNg	ТРЖе	MTBE	7BA	1,1 - DCA	1,1 - DCE	cts 1,2-DCE	Benzeno	Chloro. ethane	1,2. Dichioro- benzene	Ethyl- benzene	Naph- thalene	Toluene	1,1,1-TCA	тсе	Vlnys chloside	Xylenes, Total
Units	(feet)		(ug/L)	(ug/L)	(ug/L)	(աք/Լ)	(ug/L)	(ug/L)	(ug/L)	(ug/L)	(vg/L)	(ug/L)	(ug/L)	(ug/L)	(ug/L)	(ug/L)	(ug/L)	(ug/L)	(ug/L)
RWQCB ESLS"			5,000	2,500	1,800	50,000	1,000	6,390	8,200	540	160	100	300	210	400	50,000	530	3.6	5,300
RWQCB ESL*			100	100	5	NE	6	6	6	1	12	10	30	17	40	200	5	0.6	20
58-30-GW10	10	11/2/2007	<28	74	<0.13	<2.3	<0.059	<0.054	<0.11	<0.035	40.21	<0.05	<0.039	<0.096	0.64	<0.046	< 0.063	<0.04	1.5

RWOC8 ESEs* 1. Even that Some is Levels taken from the California Regional Water County Care Board, San Francisco Bay Region oddered infled "Screening for Environmental Concerns at Siles with Core and Groundwater," interim Final November

document entitled "Screening for Environmental Concerns at S4ss with Contaminated Sod and Groundwater," Interior Final November 2007, groundwater is a current or potential source of drinking water.

RWOC8 ESLS* *- Environmental Screening Levels taken from the California Regional Water Quality Control Board, San Francisco Bay Region

2007, a sundwater a not a current or potential source of drinking water.

Notes.

- tracegores per Liter (HULL)

· dupácate sample 1.1.1-TCA - 1.1.1-Trichloroethane

- Underground Storage Tank TEHO

- Title Pelinfeur - Thomas as Gasoline

TPHO - Total Personant Hydrocamens as Diesel MITTE - Methyl sen butyl other

- Yest thuly! alcoholciskl Z-DCE - Cis-1.2-dichlaroethylene

- Not reperfed at or above fahoratory's reperfing their or 0.50 µg/L <0.50

- Analyte not surgiced for

-TPHg BTEX VICE - Laboratoric TAL) Pleasanton, California

-TPH6 analyzed using EPA Method 8015M with silver and observe by TAL, Pleasanton, California

-Concentrations in held exceed ESLs for gloundwater as a numerit or potential source of drinking within

Table 5 Summary of Grab Groundwater Sample Results AB&I Foundry 7825 San Leandro Street

Oakland, California

Sample (C)	Sampiling Method	Dopth	Date	TPHg	TPHd	BCE.	1,1 - DCA	1,1 - DGE	1,2-0CA	trans 12-DCE	cis 1,2-0CE	Benzene	Chloroethane	Ethylbonzene	Toluena	1,1,1-TCA	YCE	Viny) chloride	Naphthalene	Xylenes, Tolat
Units	PVC/HP	(feet)	-8	(hg/L)	(pg/L)	(µg/L)	(µg/L)	(jig/L)	(ng/L)	(Jogu)	(Eg/L)	(pg/U)	(PQ/L)	(169/L)	(14 0/L)	{µ 9/L }	(iig/L)	(sg/L)	(jig/L)	(100/L)
RWQCB ESLs'				NE	NE	420	3,400	18,000	690	19,000	17,000	1,800	2,700	170,000	530,000	380,000	11,000	13.0	11,000	160,000
RWQCB ESLs1				NE	N€	120	5,000	6,300	200	6,700	6,200	540	820	170,000	360,000	130,000	530	3,8	3,200	180,000
Former Three 10,0	00-Gallon US	Ts																		-
SB-51-GW44	PVC	44	7/12/2008	170	<50	0.52	<0,38	<0,43	3,6	<0.41	6.2	Q,44J	<0.50	0,97	2.3	<0.48	3 8	0.51	2,5	7
SB-45-GW20	HP	20	7/10/2008	640	<50	40.50	<0,50	<0.50	<0.50	<0.50	<0.50	<0.50	< 0.50	< 0.50	< 0.50	<0.50	< 0.50	<0.50	<0.50	<0.50
SB-45-GW45	PVC	45	7/10/2008	900	50	40,50	<0.50	<0,50	<0.50	<0.50	<0.50	0,57	<0.50	<0.50	<0.50	<0.50	<0,50	<0.50	<0.50	<0,50
SB-46-GW48	HP	48	7/10/2008	<50	<:50	<0.50	<0,50	<0,50	<0,50	<0.50	< 0.50	<0,50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	< 0.50	<0.50
Former 8,000-Galle	on Mineral S	pirital/1,1,	1-TCA UST									-			1.36			- Day 1		
S8-50-CW\$8	HP	58	7/12/2008	<\$0	<50	<0.50	<0,38	<0.50	<0,50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	6.3	<0.38	1.5	<0.45
Parking Lot Area			•									-			554307		-40			
SB-49-GW42	HP	42	7/12/2008	<50	<50	<0.50	0.393	< 0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	< 0.50	< 0.45
S8-949-GW42(D)	HP	42	7/12/2008	<50	<56	<0.50	0 38J	<0.50	¢0.50	<0.50	<0,50	<0.50	<0.50	<0.50	<0.50	40.50	0.43 J	<0.38	<0.50	<0.45
Water Supply Well	Area														2010/50		COLUMN TO STATE		3000	1000
\$8-52-GW51	HP	51	7/12/2008	<50	<50	<0.50	<0.50	<0.50	2.2	<0.50	<0.50	< 0.50	<0.50	<0,50	<0.50	<0.50	< 0.50	<0.50	<0.50	<0.45
\$8-47-GW24	PVC	24	7/11/2008	450	<50	<0,50	<0,50	<0,50	40.50	<0.50	<0.50	<0.50	<0,50	<0.50	< 9.50	<0.50	0.62	<0,50	<0.50	40.45
SB-38-GW25	PVC	25	7/8/2008	130	<50	0.50	49	70	<0,50	<0.50	4.1	<0,50	<0.50	<0.50	<0.50	<0.50	0.55	10	40.50	+0.50
Notes:																				_

NE -value aux established

- doplicate sample (D) - Underground Storage Tank

UST

TPing - Your Petroleum Hydrocarbona as Gasolne - Total Petroleum Hydroca born as Dresel

TPHO 1,2 - DCA - 1,2-dichloroethans

- Trans-12-Inflormations trans-1,Z-DCE US-1,2-00E - Cis-1,2-dichloreethene

1.1.1-TCA -1,f_1-Trichloroethane

TCE -Trichtenettere

. at the second and a second in micrograms per Pier (µg/l)
- had reported at an above toporatory's reporting limit of 0.50 µg/L.

<0.50

-Title, Title, and VOCs analyzed using EPA Mathods 8915B(M) and 8260B by Advanced Technology Laboratonos (ATL), Signal Hill, California -Concentrate is bold deposed ESLs for vapor intrusion concerns - Residential Lend Use

PYC - Palyvinyl charico pie

- Hydropunch

RWOCS ESLS* *- Environmental Streeting Levels taken from the Calcumia Regional Water Quality Comfot Board, San Francisco Buy Region document whited "Screening for Facilities and Concerns in Orles with Contaminated Soil and Groundwise " Interim First November 2007, update May 2006, commercial land use.

RWOCD ESLs* - Environments ing Lave Water Quality Control Board, Sail Francisco Bay
Region documents - "Scienting for Londonn at Siles with Contaminated Soil and Gregoriewater,"
Interior First November 2007, updated May

Table C-2 Summary of Analytical Results Petroleum Hydrocerbon Releted Constituents (ug/L) AB&I Foundry

7825 San Leandro Street Oakland, California

Well Number	Date	Total OII & Grease	Hydrocarbon Oil & Grease	TPH-Diesel	Naphthalena	TPH- Gasoline	Benzene	Toluene	E(hyłbenzene	Xylenes	мтве	E188	TAME	DIPE	TBA	1,2-DCA
RWOCB ESLs"			NA	NA	11,000	NA	1,800	530,000	170,000	160,000	80,000	NA	NA	NΑ	NA,	690
ACLs ⁷			NA	NA	17*	NA	1.0	150	700	1,750	13	NA	NA	NA	NA	0.5
MW-1	03/10/93		-	830	_	_	0.6	ND	ND	МĎ			-	**] -
	08/20/93			2,100	-		2.2	3.7	4.5	17		-		~		
	12/03/93			3,200		-	ND	ND	ND	ND	**	-		-	-	-
	03/04/94			710			1.3	ND	ND	ND		••		••		
	06/10/94	_	-	490			ND	NO	ND	ND	**				**	-
	09/09/94	_	_	ND	-		NO	ND	DM	เล			-	-		
	12/16/94	_		180			0.6	NO	NO	ND						-
	03/17/95	_	-						_		••			-		
	06/23/95	_				-			ļ <i></i>	-					-	
	09/06/95			-	_					-		-		••		
	01/18/96	*-			~			_	_	~	~			••	-	
	04/26/98		_		-		-			~		-			**	
	02/03/97	_		_						-		•-	.,			
	07/14/06			180		<50	<0.3	<0.3	<0.3	<0.3	<1.0	<1,0	<1.0	<1.0	<50	<1.0
	10/25/07	-		450	<1.0	<50	<5.0	<5.0	<5.0	<1,0	< 0.50	<0.50	<0.50	<1.0	<5.0	<0.50
	02/22/08			560	<1.0	<50	<0.5	<0.5	<0.5	<1.0	<\$.0					€0.5
	02/22/08	-		560	<1.0	<50	<0.5	<0.5	<0.5	<1.0	<5.0	-				<0.5
	06/13/08	~	٠.	160	<0.50	<50	< 0.50	<0.50	<0.50	<1.0	-	**	"		~	< 0.50
	10/03/08	_		140	<0.50	<50	<0.50	<0.50	<0.50	0.1ء	••	-		~	-	<0.50
	12/12/08	-		100	<0.50	<\$0	<5.0	<5.0	<5.0	<10					-	<5.0
	05/22/09		-		<0.50		<0.50	<0.50	<0.50	<1.0					-	<0.50
	12/10/09	_		<50	<0.50	ය50	<50	<50	చ 0	د10			4-	••		<0,50
	07/09/10	-	-	81	<0.50	<50	0.42 J	<0.50	< 0.50	<1.0		++	-		44	< 0.50

Table C-2 Summary of Analytical Results

Petroleum Hydrocarbon Related Constituents (ug/L)

AB&I Foundry 7825 San Leandro Street Oakland, California

Well Number	Date	Total Oil & Grease	Hydrocarbon Oil & Grease	TPH-Diesel	Nephthalene	TPH- Gasoline	Benzene	Toluene	Ethylbenzene	Xylenes	MTBE	ETBE	TAME	DIPE	TBA	1,2-0CA
WQCB ESLs'			NA	NA	11,000	NA	1,800	530,000	170,000	160,000	80,000	NA	NА	NA	NA	690
Cಓಕ ²			NA	NA	17*	NA	1.0	150	700	1,750	13	NA	NA	NA	NA	0.5
MW-S	03/10/93	1,0	ND			920	ND	0.8	ND	ND	~	_			ļ - · - .]
	08/20/93	ND	ND		-	720	2.9	42	6.3	25		-				
	12/03/93	ОN	ND			900	NO	250	19	5.1	**					
	03/04/94	ND	ND	_		420	ND	QN	ND	3.6	-	~	-			
	06/10/94	2,000	2.000	_		920	ND	ND	NO	סא	-			-		
	09/09/94	2.0	2.0		-	830	ND	ND	ND	ND			-			
	12/16/94	ND	ND		-	130	ND	0.2	ВN	ND	-	••	-	-		
	03/17/95	-	1.0		-	320	4.9	ND	ND	ND	**	7	_	~		
	06/23/95	ND	ND	-	-	190	ND	ND	ND	ND		~				
	09/06/95	NO	ΝD			110	ND	ND	ND	ND		-				
	01/18/96	ИD	ND		-	120	ND	ND	ND	N.D		-		+-		
	04/26/96	ND	00			500	ND	ND	МD	ND		-				
	02/03/97	ND	NO		-	250	ND	ND	ND	1,7	••	-	-			-
	07/14/06	NS	N\$	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS
	06/13/08	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS .	NS	NS	NS	NS	NS
MW-2R	08/18/06	-		260		510	0.62	2.6	0.53	0.85	<0.5	<0.5	<0.5	<0.5	<20	<2.5
	10/25/07		_	< 50	<1.0	*150	<5.0	<5.0	<5.0	<1.0	<0.50	40.50	<0.50	<1.0	<5.0	<0.50
	02/22/08			200	<1.0	1120	<0,5	<0.5	<0.5	<1.0	<5.0				-	€0.5
	02/22/08			200	<1.0	1120	<0.5	<0.5	<0.5	<1.0	c5.0					<0.5
	06/13/06			<50	<0.50	198	<0.50	<0.50	<0.50	<1.0						<0.50
	10/03/08	_	_	<50	<0.50	171	<0,50	<0.50	<0.50	<1.0	_			٠.		<0.50
	12/12/08		_	52	< 0.50	⁻ 81	<0.50	<0.50	<0.50	<1.0	٠.	٠.				<0.50
	05/22/09	.,	_	<0.050	<0.50	110	<0.50	<0.50	<0.50	<10		-		-		<0.50
	12/10/09			<50	< 0.50	99	<0.50	<0.50	<0.50	<1.0						<0.50
	07/09/10			<50	<0.50	210	<0.50	<0.50	<0.50	€1.0	***					≤0.50

Table C-2 Summary of Analytical Results Petroleum Hydrocarbon Related Constituents (ug/L) A881 Foundry 7825 San Leandro Street Oakland, California

Well Number	Date	Total OII & Grease	Hydrocarbon Oli & Grease	TPM-Diesel	Naphthalene	TPH- Gasoline	Benzana	Taluene	Ethylbenzane	Xylenes	MTBE	ETBE	TAME	DIPE	TBA	1,2-0C
RWOCB ESLs1			NA	NA	11,000	ÑA	1.800	530,000	170,000	160,000	80,000	NA	NA	NA	NA	69D
NCL3 ²			NA	NA	17*	NA	1.0	150	700	1,750	13	NA	NA	NA	NA	0.5
MW-3	03/10/93			_		ND	ND	ND	ND	ND			_		_	-
	08/20/93	_				190	7.2	9.3	8.5	31		-+	-			
	12/03/93	_	^-	~		ND	ND	ND	ND	ND		**			,-	_
	03/04/94	_		۰.	-	ND	ND	ND	ND	ND		**			-	
	06/10/94	**			-	ВÐ	ND	ND	ND	ND					-	_
	09/09/94	_		_		NO	ND	ND	NO	ИD						
	12/16/94	_		_		ND	ND	ND	ND	ND		_				-
	03/17/95	_		_		ND	ND	ND	ND	ND	~		-			
	06/23/95		<u>_</u>	-	_	ND	ND	ND	ND	ND			-			,.
	09/06/95	_	_		_	ND	ND	ND	ND	סא	-	-		3-07		
	01/18/96		-	-	_	ND	ND	ND	ND	В			Δ'		~	-
	04/26/96			-	_	ИĎ	ND	ND	ND	ND		~	- 41	**	-	-
	02/03/97	•	_			-	ND	ND	ND	ND	-		*	-		-
	07/14/06	~		<50	<5.0	93	1.2	<0.3	<0,3	<0.3	<1.0	0.15	<1.0	41.0	<50	<10
	10/24/07			<50	<1.0	1540	<5.0	<5.0	<5.0	1.0ء	<5.0	<0.50	<0.50	<1 O	<5.0	<5.0
	02/21/08			110	<20	'660	<5.0	<\$.0	<5.0	<1.0	<50	•-		_		<10
	02/21/08			110	<20	'660	<6.0	<5.0	ය.0	<1.0	<50			٠.		<10
	06/13/08			<50	<0.50	*510	0.65	<0.50	<0.50	<1.0				_		<0.50
	10/02/08			<50	<0.50	*500	<2.5	<2.5	<2,5	<5	••			_		<2.5
	12/11/08		-	<50	<2.5	*410	<2.5	42.5	<2.5	9.5		_		_		<2.5
	05/21/09	-	120	<0.050	<2.5	0.55	<2.5	1.8	<2.5	<5.0	100				12	<2.5
		4 - 3					E	AnB Injects	ons				1			
	07/01/09	-			<2.5		<2.5	8.4	<2.5	e(6.0)	-	-		**		2.5
	08/07/09	-	1-		<0.50		0.67	7.1	<0.50	<1.0	-		-	**		<0.50
	09/10/09			-	<0.50	- 75	0.72	9.8	<0.50	<1.0		-		••	- 22	<0.50
	12/09/09	-	••	<0.50	<0.50	51	0.51	2.6	<0.50	<1.0				**		< 0.50
	04/09/10		1220 1	91	<0.50	-	0.41 J	1.4	<0.50	<1.0	-					<0.50
	07/08/10	100	1044.0	<50	<0.50	<50	0.36 J	<0.50	<0.50	<1.0			**	••	299	c0.50
	12/22/10		_	<50	<0.50	<50	Q.40 J	<0.50	<0.50	<1.0	-					<0.50

Table C-2 Summery of Analytical Results Petroleum Hydrocarbon Related Constituents (ug/L) AB&) Foundry 7825 San Leandro Street Oakland, California

Well Number	Date	Total Oll & Grease	Hydrocarbon Oil & Grease	TPH-Dlesel	Naphthalene	TPH- Gasoline	Benzene	Yoluene	Ethylbenzene	Xylenes	MTBE	EU8E	TAME	DIPE	; 184	1,2-DCA
RWQCB ESLa			NΑ	NA	11,000	NΑ	1,800	530,000	170,000	160,000	80,000	NA	NA	AN	NA	690
MCLs ²			NA	NA	17*	NA	1,0	150	700	1,750	13	NA	NA	NA	NA	0.5
MW⊸	03/10/93			_		1,800	1.0	2.0	7.6	19	-			_	-	
	08/20/93					350	5.6	4.9	7.5	22	-	_	_		_	
	12/03/93			_		1,100	ND	ND	1.4	2.8						
	03/04/94			_		50	ND	0.9	ND	1.1		-	_			-
	06/10/94	4+	~	-	_	460	4.3	ND	1.8	4.3						
	09/09/94			[-	_	150	0.4	ND	0.7	1.3	,-	_				
	12/16/94					100	0.4	0.4	ND	1.2	,.	_				
	03/17/95	_		-		82	NĐ	NĐ	ND	ND		-		_		
	06/23/95	-		-	-	180	ND	ВN	0.9	3.7	_				_	**
	09/06/95		-	-		420	9,4	1,4	6.3	6.2						
	01/18/96	-	-	_	-	90	0.8	ND	1.2	0.9		-			**	-
	04/26/96	-	-		-	NO	ND	ND	ND	ND				٠,	**	
	02/03/97	-		-		110	ND	ND	0.53	ND	**	-			-	
	07/14/06			82	9.9	1,200	11	2.8	18	9,3	¢1.0	<1.0	<1.0	<10	<50	<1.0
	10/24/07	-	••	<50	<1.0	<50	<5.0	<5.0	<5.0	<1.0	<0.50	<0.50	<0.50	<1.0	<5,0	<0.50
	02/21/08	_		95	<1.0	<50	<0.5	<0.5	<0.5	<1.0	<5.0			-		<0.5
	02/21/08	-		95	<1.0	<50	<0.5	<0.5	<0.5	<1.0	<5.0	-		-		<0.5
	06/13/08	-		≥50	<0.50	<50	<0.50	<0.50	<0.50	c1,0						<0.50
	10/02/08	**		<50	<0.50	<50	<0.50	<0.50	<0.50	c1,0		<i></i>				<0.50
	12/11/08	*1	-	c50	<0.50	<50	<0.50	<0.50	<0.50	<1.0				-	**	<0.50
	05/21/09		~	₹0.050	<0.50	<0.050	<0.SQ	<0.50	<0.50	<1.0		-				<0.50
	12/09/09	0.550 0	150	<0.50	<0.50	70	<0.50	<0.50	<0.50	<1.0		~	0 To 1		0.0	<0.50
	07/08/10		-	<50	< 0.50	110	<0.50	<0.50	<0.50	e1.0	- 4		•	red.	-	<0.50
MW-5	08/17/06	-	-	08	<1.0	<50	0.56	0.7	<0.3	<0.3	<0.5	<0.5	<0.5	<0.5	<20	<2.5
10000	10/25/07	-	-	<50	<1,0	<50	<5,0	c 5.0	<5.0	<1.0	<0.50	<0.50	<0.50	<1.0	<5.0	<0.50
	02/22/08			130	<1.0	50ء	<0.5	<0.5	<0.5	<1.0	<5.0	-	-		••	<0.5
	02/22/08		-	130	<1,0	<50	<0.5	<0.5	<0.5	<1.0	<5.0		_	-	,.	<0.5
	06/13/08	121		<50	<0.50	<50	0.65	<0.50	<0.50	<1.0	_			_		<0.50
	10/02/08	200	200	<50	<0.50	*54	<0.5	<0.50	<0.50	<1.0						<0.50
	12/11/08	44		51	<0.50	< 50	<0.50	<0.50	<0.50	<1.0	-					<0.50
	05/21/09	~	· .	<0.050	<0,50	<0.050	<0.50	<0.50	<0.50	<1.0	••				••	<0.50
	12/10/09	-		<50	<0.50	53	<0.50	<0.50	<0.50	<1.0		46	1 85 3	1.00	.00	<0.50
	07/09/10	+	4.0	<50	<0.50	120	< 0.50	<0.50	< 0.50	<1.0		44	14	-	24	<0.50

Table C-2 Summary of Analytical Results Petroleum Hydrocarbon Related Constituents (ug/L) AB&I Foundry 7825 San Leandro Street Oakland, California

Well Number	Dale	Total OII & Grease	Hydrocarbon Oil & Grease	TPH-Diesel	Naphthalens	TPH- Gasoline	8enzene	Talvêns	Ethylbenzana	Xylenes	мтає	ETBE	TAME	DIPE	T9A	1,2-DCA
RWQCB ESL5			NA	NA	11,000	NΑ	1,800	530,000	170,000	150,008	80,000	NA	NA	NA	ŇĄ	690
ACLs'			NA	NA	17	NA	1.0	150	700	1,750	13	NA	NA	NA	NA	0.5
MW-6	08/17/06	.,	_	110	<1.0	රුර	<0.3	<0.3	<0.3	<0.3	<0.5	<0.5	<0.5	<0.5	<50	<2.5
	10/24/07			110	<1.0	c50	<5.0	<5.0	<5.0	<1.0	<0.50	<0.50	<0.50	<1.0	<5.0	< 0.50
	02/21/08		_	150	<10	<50	<0.5	<0.5	€0.5	1.5	<5.0			_	h	<0.5
	02/21/08			150	<1.0	<50	<0.5	<0.5	<0.5	15	<5.0		_			<0.5
	06/13/08	_		54	<0.50	<50	<0.50	<0,50	<0.50	<1.0			-	••		<0.50
	10/02/08		-	56	<0.50	<50	<0.50	<0,50	<0.50	<1.0					_	<0.50
	12/11/08	-		<50	<5.0	<50	c5.0	ದ. 0	<5.0	c10	-			-	••	<5.0
	05/21/09	-	-	<0.050	<0.50	<0.050	<0.50	<0.50	<0.50	c10		**	-		_	<0.50
	12/09/09	**	(•)	<50	<0.50	<50	<0.50	<0.50	<0.50	<1.0	**	1~				< 0.50
	07/08/10	-	-	67	<0.50	<50	<0.50	<0.50	<0.50	<1.0	-		-	1000	- 44	<0.50
MW-7	08/17/06			520	<1.0	<50	<0.3	0.35	< 0.3	<0.3	<0.5	<0.5	<0.5	<0.5	<20	<2.5
	10/25/07	-		370	<1.0	<50	<5.0	<5.0	<5.0	<1.0	<0.50	<0.50	<0.50	<10	<5.0	<0.50
	02/21/08			180	<1.0	<50	<0.5	<0.5	< 0.5	<1.0	<5.0		-	11/27	71	<0.5
	02/21/08	_		180	<1.0	<50	<0.5	<0.5	<0.5	<1.0	<\$.0	~	-			<0.5
	08/13/06	~	_	59	<0.50	<50	<0.50	<0.50	< 0.50	<1.0		-	-	**		<0.50
	10/02/08	~	_	120	<0.50	<50	<0.50	<0.50	<0.50	<1.0		-	'	- -		<0.50
	12/12/08	~		78	<5.0	ර50	<5.0	<5.0	<5.0	<10			-		-	<5.0
	05/22/09	-	_	<0.050	< 0.50	<0.050	<0.50	<0.50	<0.50	<1.0	-			••		<0.50
	12/10/09			<50	<0,50	<50	<0.50	<Ò.50	<0.50	<1.0	-	_	- 5	1,	-	<0.50
	07/09/10			<50	<0.50	c50	< 0.50	<0.50	< 0.50	<1.0	2	44	14	1.4		<0.50

Table C-2 Summary of Analytical Results Petroleum Hydrocarbon Related Constituents (ug/L) A0&I Foundry 7825 San Leandro Street Oakland, California

Well Number	Date	Total Oil & Grease	Hydrocarbon Oil & Grease	TPH-Dlesel	Naphihalana	TPH- Gasoline	Benzane	Toluene	Ethylbenzene	Xylenes	MTBE	ETBE	TAME	DIPE	TBA	1,2-DCA
WQÇ8 ESLs'			NA	NA	11,000	NΑ	1,800	530,000	170,000	160,000	80,000	NA	NA	ŅΑ	NA	690
IÇLa ⁷			NA	NΑ	17'	NA	1.0	150	700	1,750	13	NA	NA	NA	NA	0.5
MW-8	08/17/06	-		78	<5.0	640	1.9	<0.3	<0.3	<0.3	<2.5	<2.5	<2.5	<2.5	c100	<2.5
	10/25/07			<50	<)0	1200	<5.0	<5.0	<5.0	< 1.0	<0.50	< 0.50	<0.50	<1.0	<5.0	<25
	02/21/08	_		140	⊲50	*2500	<25	<25	<2\$	<50	د250	_			_	<25
	02/21/08			140	<50	12500	<25	<25	<25	<25	<250	_		٠.	-	<25
	06/13/08	_		<50	c10	12100	<10	<10	<10	<20	••	-			_	<10
	10/02/08			<50	<5.0	2100	2.8	<5.0	<50	<10	-	-			_	⇔5.0
	12/11/08	-		<50	5.0ء	1900	3.0	5.0	<5.0	<10		-	-		_	<5.0
	05/21/09	_	-	<0.050	<5.0	2.1	2.9	<5.0	<5.0	<10	-	-	_		-	<5.0
Dup	05/21/09	- -	₩ = 3;	<0.050	<5.0	2.1	2.8	<5.0	<5.0	e10	-	-	-	7.5	HP.	<5.0
				-			. 8	And Injectio	COT.	To the last	-					
	07/01/09		-		<2.5		2.6	c2.5	<2.5	<5.0	-	-	-			×2.5
	08/07/09		٠.		<5.0		3.2	<5.0	<5.0	<10	-				-	<5.0
	09/10/09				<2.5		3,4	<2.5	<2.5	<5.0	~	~	-		-	<2.5
	12/09/09		~	<50	<2.5	180	3.0	<2.5	<2.5	<5.0						1,8
Dup	12/09/09		-	<50	<5.0	190	2.8	<5.0	<5.0	<10		•••	-			<5,0
	04/09/10	_			<2.5	**	2.4 J	<2.5	<2.5	c5.0		•				1.0 J
	07/08/10			110	<2.5	140	2.4 J	<2.5	<2.5	<5.0	H 7	-	•	4.		≺2.5
Dup	07/08/10			74	<2.5	140	2.2 J	د2.5	<2.5	c5.0	12		- 65	••	-	₹2.5
_	12/22/10		-	120	<0.50	<50	0.43 J	<0.50	c0.50	<1.0			-		-	<0.50
MW-9	08/17/06		-	440	<40	7,400	250	11	51	14	<50	<50	<50	<50	<500	<40
	10/25/07			120	<1	1,300	89	2.0	6.0	ç1	< 0.50	<0.50	<0.50	<1.0	15.0	<1,0
	02/21/08		-	190	<40	2,600	170	2.8	9.1	<4.0	<20	-				<2.0
	06/13/08		**	180	2.1	2,900	180	3.0	7.6	2.1	-	-				<0.50
	10/03/08		_	200	1.8	3,100	170	2.8	5.9	1.9				_		< 0.50
	12/11/08			86	1.3	2.300	120	2.1	2.7	1.4			-			c0.50
	05/22/09	44	+	250	2.2	3,500	180	2.9	3.9	1.7	.00	-		0.000	-	<0.50
							É	AB Injectio	ns							
	07/01/09			470	3.3	3,400	53	2.0	9.5	0.28	-	**	100	-	-	<0.50
	08/07/09	-		340	0.82	2.400	9.1	0.5	S-2	1.5	-			-	**.	< 0.50
	09/10/09			460	0.87	3,100	5.7	0,36	1.4	1.7				-	*	<0.50
	12/09/09			150	1,3	2,700	36	0.87	2.7	1.1				-		<0.50
	04/09/10) -	320	1,2	3,300	66	1.3	4.0	1.1	**		_			<0.50
	07/09/10	-	~	250	0.77	2,700	100	2.30	9.2	1.6	'		-			<0.50
	12/22/10			120	0.75	2.200	77	1.80	9.1	1.4		J.	-		-	<0.50

Table C-2

Summary of Analytical Results

Petroleum Hydrocarbon Related Constituents (ug/L)

AB&I Foundry

7825 San Leandro Street Oakland, California

We)I Number	Date	Total Oil & Grease	Hydrocarbon Oil & Grease	TPH-Diesel	Nophihalene	TPH- Gasoline	Banzene	Toluene	Elhylbenzene	Xylanes	MTSE	ETBE	TAME	DIPE	TBA	1,2-DCA
RWQC8 ESLs ^t			NA	NA	11,000	NA	1,800	530,000	170,000	160,000	80,000	NΑ	NA	NA	NA	690
MCLs ³			NA	NA	17'	NA	1.0	150	700	1,750	13	NA	NΑ	NA	NA	0.5

Notes:

Value in hold exceed the MCL

Strated values received the ESL for supply introduction

* California Department of Health Druking Water Program, Druking Water Notification Level, December 14, 2007

-Hawrigal data for sample growth conducted prior to October 2007 obtained from Table 2, Preliminary Groundater Investigation Report, A&& Foundry, BSK Associates, Inc., dated June 31, 2007.

California EPA Department of Health Service Maximum concentration levels for drinking water MCL

RWOCB ESLs (VI) Regional Water Quality Control Board Environmental Screening Levels based on vapor intrusion concerns for commercial land use scenario.

All concentrations reported in micrograms per liter (ug/L). Jg/L

TPH Total Petroleum Hydrocarbons

MTGE methyl tert but other

ETBE ethyl tert butyl ether

TAME tert-amyl methyl ether

DIPE disopropyl ether

TBA (ributy) alcohol

DCA dichlorgethage

Not detected at or above laboratory reporting limit. ND

<\$0 Not detected at or above laboratory reporting limit of 50 vo/L.

NS Not sampled.

Not analyzed.
Reported due to the presence of discrete peaks analyte detected below quantilation limits .500

Table C-3 Summary of Analytical Results Volatile Organic Compounds and PAHs (ug/L) AB&I Foundry

7825 San Leandro Street Oakland, California

Well Number	Dase	Bromoform	Chlorodibromomethane	Chlaroethana	1,7-Olchloroethane	1,1-Dichioroethene	cfs-1,2-Dlchloroethene	(rans-1,2-Dichloroethene	1,1,3 Trichlaroethane	Vinyl Chloride	Isopropyldenzena	n-Propylbenzene	Polycyclic Anomalic Hydrocarbons EPA 8270C
RWOCB ESLs1		NA	NA	2,700	3,400	1,800	17,000	19,000	360,000	13	NE	NE	
MCLs ²		NA	NA	NE	5.0	6.0	6.0	10	200	0.5	770*	280	
MW-1	03/10/93	-			-	14			-	-	-		~
	08/20/93	_	_	-	-						_		
	12/03/93	~	_		_			-	-	_		**	
	03/04/94	_		_	-			-	_				_
	06/10/94	_		-		-					~		_
	09/09/94	_		-	_		-	_	-	-	-		-
	12/16/94	~			_				-				_
	03/17/95	_		**	<u>.</u>				-	-	_		-
	08/23/95	_			_			~	-		^	,.	
	09/06/95	_	-		_	_	-		-	**	_		
	01/18/96			_		-	_) -	-			_	
	04/26/96					-	-		_				_
	02/03/97		,.		-				~				
	07/14/06	<5.0	<5.0	<\$.Q	<5.0	<5.0	<5.0	<5.0	<50	<5.0	<5.0	<50	_
	08/17/06	~	,.		-			**	_	<i>-</i> -			NO
	10/25/07	<1.0	<0.50	<1.0	<0.5	<0.5	<0.5	<0.5	0.5ء	<0.5	<0.5	<1.0	•-
	02/22/08	<1.0	<0.50	<1.0	0.58	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	₹1.0	-
	06/13/08	<0.50	<0.50	<0.50	0.4	<0.50	<0.50	<0.50	<0.50	<0,50	<0.50	<0.50	-
	10/03/08	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0,50	-
	12/12/08	<5.0	c5.0	۶5.Q	<5.0	<5.0	<5.0	<5.0	<5.0	<5.0	<5.0	د5.0	
	05/22/09	<0.50		<0.50	0.41	<0.50	<0.50	<0.50	<0,50	<0.50	<0.50	<0.50	-
	12/10/09	c0.50	_	<0.50	0.41	<0.59	<0.50	<0,50	<0.50	<0.50	<0.50	<0.50	-
	97/09/10	<0.50	C SHOW	<0.50	0.43 J	<0.50	<0.50	<0.50	<0.50	-,0.50	<0.50	<0.50	

Table C-3 Summary of Analytical Results Volatile Organic Compounds and PAHs (ug/L) AB&I Foundry 7825 San Leandro Street

Oakland, California

Well Number	Date	Bromotorm	Chlorodibromomethane	Chloroethane	1,1-Dichloroethane	t.1-Dichloroethene	cls-1,2-Dichloroethene	trans-1,2.Dichloroathene	1,1,1 Trichioroethane	Vinyi Chloride	lsoprapylbenzene	п-Ргору Бепzеле	Polycyclic Aromatic Hydrocarbons EPA 8270C
RWOCB ESLs'		NA	NA	2,700	3,400	1,800	17,000	19,000	360,000	13	NE	NE	
MCLs ²		NA	NA	NE	5.0	6.0	6.0	10	200	0.5	770′	260-	
WW-5	03/10/93	0.6	ND	5.0	1,7	ND	ND	ND	6.7	6.7	6.7	6.7	
	08/20/93	NO	ND	4.7	ND	ND	ND	ND	NO	ND	ND	ИD	-
	12/03/93	ND	ND	3.8	ND	ND	ND	ND.	ND	ND	ND	ND	
	03/04/94	В	ВN	3.7	ND	ND	ND	ди	ND	ND	ND	3.6	_
	06/10/94	ND	ND	4.2	0.6	ND	ND	NB	0.8	8.0	0.6	0.8	-
	09/09/94	ND	NO	1.4	0.8	GN	ND	GM	ND	ИD	ND	ND	_
	12/16/94	ND	NO	DN	ND	ND	ND	ND	ND	ВИ	ND	ND	_
	03/17/95	ND	ON	2.4	ND	ND	ND	ND	ND	ND	ND	ND	-
	06/23/95	NO	ND	0.9	ОИ	מא	ND	ND	ND	ND	ND	110	
	09/06/95	ВИ	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	
	01/18/96	ND	ND	ND	NO	ND	ND	ОN	ND	ND	ND	ИD	-
	04/26/96	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	_
	02/03/97	ND	ND	ND	D	ND	ND	ND	ND	ND	ND	ND	~
	07/14/06	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	
£	Well Abando	oned											
MW-2R	08/18/06	<2.5	<2.5	390	<2.5	<2.5	<2.5	<2.5	2.5	<2.5	<2.5	<2.5	ND
E. T. C. STAN C.	10/25/07	<1.0	<0.5	<1	<0.5	<0.5	<0.5	<0.5	<0.5	€0.5	<0.5	<1	
	02/22/08	<1	<0.5	<1	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<1	
	06/13/08	<0.50	<0.50	<0.50	<0.50	0.68	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	_
	10/03/0B	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.60	<0,50	_
	12/12/08	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	
	05/22/09	<0.50		⊲0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	_
	12/10/09	<0.50		<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	c0.50	<0.50	<0.50	_
/	07/09/10	<0.50		<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	e0.50	<0.50	<0.50	-

Table C-3 Summary of Analytical Results Volattle Organic Compounds and PAHs (ug/L) AB&I Foundry 7825 San Leandro Street Oakland, California

Well Number	Date	Вготогогт	Chlorodibromomethane	Chloroethane	1,1-Dichloroethane	1,1-Ofchloroeithene	cis-1,2-Dichloroethene	(rans-1,2-Dichloroethene	1,1,1 Trichtoroenhane	Vinyl Chloride	eneznedłycorgosi	n-Propylbenzene	Polycycke Aromatic Hydrocarbons EPA 8270C
RWQCB ESLs'		NA	NA	2,700	3,400	1,800	17,000	19,000	360,000	13	NE	NE	
ACLs'		NA	NA	NE	5.0	6.0	6.0	10	200	0.5	770	260'	_
MW-3	03/10/93	**			_		-	-		-	••		-
	08/20/93		**	-	_		-						-
	12/03/93			-	-	_	-				-		_
	03/04/94		-	-	_	•			_		-		_
	06/10/94	_	-		-			-	h	_			-
	09/09/94	~			-	-	-		~		٠-	-	_
	12/16/94	-	-	-	-	_		-	-		-		-
	03/17/95	-	-	-	_		-		~	-		-	-
	06/23/95	_	~			·-	-	_	~	-	**	-	_
	09/06/95			-	_	-	-		-	-		-	**
	01/18/96				_			-	~	-	-	-	_
	04/26/96	-		**	_	-			-				_
	02/03/97	-			-		-		-	-		-	
	07/14/06	<20	<20	<20	200	960	<20	<20	<20	<20	<20	<20	ND
	10/24/07	<10	<5.0	<10	180	680	5.0	<5	13.0	7,5	<5.0	<10	r-
	02/21/08	<10	<5	<10	220	920	9.3	<5	<5	10.0	<5	<10	~
	06/12/08	<0.50	<0.50	<0.50	170	910	7.9	0.5	<0.50	13.0	<0.50	<0.50	-
	10/02/08	<2.5	<2.5	<2.5	190	1,000	7,6	1.5 J	<2,5	9.6	<2.5	<2.5	
	12/11/08	<2.5	<2.5	<2.5	200	2,000	9,4	₹2.5	2.2	9.5	د2.5	<2.5	-
	05/21/09	<2.5	0,40	<2.5	220	1,000	10	1.2	<2.5	8.4	<2.5	<2.5	-
						EAri	B Injections					-	
	07/01/09	<2.5	1.0	<2.5	160	620	7.5	<2.5	<2.5	6.7	<2.5	<2.5	-
	08/07/09	<0.50		51	110	94	1,2	<0.50	<0.50	29	<0.50	<0.50	-
	09/10/09	<0.50	-	150	5.6	11	0.20	0.47	<0.50	3.6	<0.50	<0.50	-
	12/09/09	<0.50	٠-	78	16	5.4	0.25	0.37	<0.50	17	<0.50	<0.50	
	04/09/10	<0.50		47	0.78	0.74	<0.50	0.29 J	<0.50	1.4	<0.50	<0.50	**
	07/08/10	<0.50		39	0.58	1.0	<0.50	0.27 J	<0.50	1.1	<0.50	<0.50	[T
	12/22/10	-	-	3.6	0.29 J	0.8	<0.50	<0.50	<0.50	0.97	<0.50	<0.50	-

Table C-3 Summary of Analytical Results

Volatile Organic Compounds and PAHs (ug/L) A98 | Foundry 7825 San Leandro Street Oakland, Cattlornia

Well	Date	Bromaform	Съголобитотопення	Chloroethane	1,1-Dichloroelhane	1,1-Dichloroethene	cls-1,2-Dtchloroethane	trans-1,2-Dichtoroethene	1,1,1 Trichioroethane	Vinyi Chioride	lsopropylbenzene	n-Propylbenzene	Polycyclic Aromatic Hydrocarbons EPA 8270C
RWOCB ESLs'		NA	NA	2,700	3,400	1,800	17,000	19,000	360,000	13	NE	NE	
MCLs ³		NA	NA	NE	5.0	6.0	6.0	10	200	0.5	770*	260	
MW-4	03/10/93	-	_		_	_			-	••		_	
	08/20/93	-	-		-	-			_	-		-	
	12/03/93	-	~	-	-	-		-	-	**	-		
	03/04/94	_	~		_				-	-			
	06/10/94	~	-		_				~	-			~
	09/09/94	-		-	-							-	
	12/16/94	-			-			-				**	
	03/17/95	-			-		-		-	•-			
	06/23/95				-		-	-	-	~			
	09/06/95	-	-		-	-	-		-	-			
	01/16/96	_	-	-	_		~	,-	-	-	-		-
	04/25/96			~	-		-		••	-		-	
	02/03/97	~	-		-		_				**		_
	07/14/08	<5.0	<5.0	<5.0	<5.0	<5.0	<5.0	<5.0	5.0ء	<5.0	<0.5	<5.0) -
	10/24/07	< 1.0	<1.0	<1.0	<0.5	<0.5	<0.5	c0.5	c0.5	<0.5	<0.5	<1,0	
	02/21/08	<1.0	<0.5	c1,D	<0.5	<0.5	<0.5	<0,5	<0.5	<0.5	<0,5	<1.0	
	06/12/08	<0.50	<0.50	c0,50	<0.50	0.73	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	
	10/02/08	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0,50	<0.50	<0.50	<0.50	<0.50	*-
	12/11/08	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	~
	05/21/09	<0.50		<0.50	<0,50	<0.50	<0.50	<0₂50	<0.50	<0.50	<0.50	<0.50	
	12/09/09	<0.50	0.91	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	
	07/08/10	< 0.50	Sec. 277	<0.50	< 0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	

Table C-3 Summary of Analytical Results Volatile Organic Compounds and PAHs (ug/L) A8&I Foundry 7825 San Leandro Street Oakland, California

Well Number	Date	Bromoform	Chlorodibromomethane	Chloroethane	1,1-Dichloroethane	1,1-Dkchkoroethene	cls-1,2-Dichloroethene	trans-1,2-Dishloroethene	1,1,1 Trichloroeshane	Vinyl Chloride	lsopropylbenzene	n-Propylbenzene	Polycyclic Aramalic Hydrocarbons EPA 8270C
RWOC8 ESLa*		NA	NA.	2,700	3,400	1,800	17,000	19,000	360,000	13	NE	NE	
MCLs'		NA	NA	NE	5.0	6.0	6.0	10	200	0.5	770	260	
MW-5	08/17/06	2.2	1.0	4.8	4.8	1.2	3.1	1.0	<5.0	<5.0	₹5.0	<5.0	ВИ
	10/25/07	<1.0	<0.5	<1.0	2	15	1.5	<0.5	<0.5	<0.5	<0.5	<1.0	**
	02/22/08	<1.0	<0.5	<1.0	1.4	1	3.3	1.3	<0.5	<0.5	<0.5	<1.0	
	06/12/08	<0.50	<0.50	<0.50	1.3	1.5	5.1	2	<0.50	<0.50	<0.50	<0.50	-
	10/02/08	<0.50	<0.50	<0.50	1.2	0.81	3.9	1.7	<0.50	<0.50	<0.50	<0.50	
	12/11/08	<0 50	<0.50	<0.58	1,6	0.76	3.4	1.2	< 0.50	<0.50	<0.50	<0.50	-
	05/21/09	<0.50	-	<0.58	9.7	0.71	3,3	1.1	<0.50	<0,50	<0.\$0	<0.50	
	12/10/09	< 0.50		<0.50	0.58	0.63	2.2	0.67	<0.50	<0.50	<0.50	<0.50	
	07/09/10	< 0.50	-	<0.50	0.40	0.38	3.4	1,0	<0.50	<0.50	<0,50	<0.50	**
MW-6	08/17/06	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	NO
	10/24/07	<1.0	<0.5	<1.0	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	
	02/21/08	<1.0	<0.5	<1	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<1.0	_
	06/12/08	< 0.50	<0,50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	
	10/02/08	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0,50	<0.50	_
	12/11/08	<5.0	<5.0	<5.0	<5.0	<5.0	<5.0	<5.0	<5.0	<5.0	<5.0	<5.0	
	05/21/09	< 0.50	-)	<0.50	<0.50	< 0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	
	12/09/09	< 0.50	-	<0.50	∢ 0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	
2	07/08/10	<0.50		<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	
MVV-7	08/17/06	<0.5	₹0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	ND
	10/25/07	<10	<0.5	<10	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	_
	02/21/08	<1.0	<0.5	<1,0	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<1.0	-
	06/13/08	c0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	-
	10/02/08	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	
	12/12/08	<5.0	<5.0	<5.0	<\$.0	<5.0	<5.0	<5.0	< 5.0	<5.0	<8.0	-5.0	-
	05/22/09	<0.50		<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	(2 Jen 1
I,	12/10/09	<0.50	2	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	11
	07/09/10	<0.50	-	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	< 0.50	<0.50	-

Table C-3 Summary of Analytical Results Volatile Organic Compounds and PAHs (ug/L) AB&I Foundry 7825 San Leandro Sitee)

Oakland, California

Well Number	Date	Bramotom	Chlorodibromomelhane	Chloroethane	1,2-O'chloroethane	1,5-Dichloroelhene	cis-1.2-Dichloroethane	(ran s. 1,2. Dłohloroethene	1,1,1 Trkchloroethane	VInyì Chloride	Isapropylbenzone	n-Propylbenzene	Polycyclic Aromatic Hydrocarbons EPA 8270C
RWQCB ESLs		NA	AM	2,700	3,400	1,800	17,000	19,000	360,000	13	NE	₩E	
MCLs'		АИ	NA	NE	5.0	5.0	6.0	10	200	0.5	770*	260'	
MW-8	08/17/06	€.5	<2.5	100	560	900	<2.5	<2.5	1,000	7.A	1.000	7.4	ND
	10/25/07	<50	<25	290	1,600	1,600	<0.5	<25	1,700	<25	<25	<50	
	02/21/08	<50	<25	290	1,800	2,300	<25	<25	2,500	<25	<25	<50	
	06/12/08	<10	<10	300	1,400	3,200	<10	<10	2,700	19	<10	<10	
	10/02/08	<5.0	<5.0	320	1,100	1,900	4 5	<5	1,700	18	5.2	<5.0	-
	12/11/08	<5.0	<\$.0	320	1,300	2,000	<5.0	≥5.0	2,000	15	6.2	<5.0	() - 2
	05/21/09	c5.0		320	1,500	1,900	<5.0	<5.0	1,900	16	5.3	c5.0	-
						EAn	B Injections				4 1 1		
	07/01/09	<2.5		350	1,200	1,100	<2.5	₹2.5	960	31	<2.5	<2.5	**
	08/07/09	<5.0		370	1,600	1,300	<5.0	<5.0	1,700	9.6	<5.0	<5.0	**
	09/10/09	€.5		340	2,600	1,100	<2.5	<2.5	45	50	0.0	<2.5	-
	12/09/09	<2.5	_	2,400	94	58	<2,5	<2.5	14	85	4,1	<2.5	
	12/09/09	<5.0		2.400	92	60	<5.0	<5.0	14	82	<5.0	<5.0	-
	04/09/10	<2.5		1,400	32	2.3 J	<2.5	<2.5	<2.5	2.2 J	2.4 J	<2.5	-
	07/06/10	<2.5		1,300	15	2,5	<2,5	<2.5	42.5	2.2 J	2.8	<2.5	-
Dup	07/08/10	<2.5	~	1,200	18	4.5	<2.5	<2.5	<2.5	2.9	2.7	<2.5	
	12/22/10	+		91	<0.50	0.76	<0.50	<0.50	<0.50	< 0.50	<0.50	<0.50	1 1090 1

Table C-3 Summary of Analytical Results Volatile Organic Compounds and PAHs (ug/L) A88i Foundry 7825 San Leandro Street

Oakland, Catilornia

Weil Number	Date	Вготогот	Chlorodibromomelhane	Chloroethane	1,1-Dichloroethane	1.1.Dichloroethene	cis-1,2-Dichiaroethene	Irans-1,2-Dkhloroethene	1,1,1 Trickloroelhane	Viayl Chloride	Isopropylbenzene	п-Ргорујвапzепе	Polycyclic Aromatic Hydrocarbons EPA 8270C
RWQCB ESLs'		NA	NA.	2,700	3,400	1,800	17,000	19,000	360,000	13	NE	NE	
MCF;		NA	NA	NE	5.0	6.0	6.0	10	200	0.5	770*	260*	
MW-9	08/23/06	<40	<40	<40	<40	<40	<40	<40	<40	<40	53	62	NO
	10/25/07	<2.0	<1.0	<2.0	<1.0	<1,0	<0.5	<1.0	<1.0	<1.0	<1.0	<2.0	_
	02/21/08	<4.0	Ø.0	<4.6	<2.0	<2,0	<2.0	<2.0	<2.0	<2,0	23	24	
	06/12/08	<0.50	<0.50	<0.50	<0.50	14	<0.50	<0.50	<0.50	<0.50	22	26	
	10/03/08	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<3.50	<0.50	<0.50	<0.50	29	
	12/11/08	<0.50	<0.50	<0.50	<0.50	1.4	<0.50	<0.50	<0.50	<0.50	19	23	
	05/22/09	<0.50		<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	21	26	
						E/	B Injections						
	97/01/09	<0.50		<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	34	44	-
	08/07/09	<0.50	-	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	8.8	9.9	-
	09/10/09	<0.50	.,	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	60,50	4.0	3.8	
	12/09/09	<0.50	-	<0.50	<0.50	<0.50	<0.50	<0.50		<0.50	5.5	1.3	-
	04/09/10	<0.50		<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	5.9	5.5	_
	07/09/10	<0.50		< 0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	10.0	9.5	
	12/22/10			<0.50	<0.50	<0.50	<0.50	<d 50<="" td=""><td><0.50</td><td><0.50</td><td>120</td><td>12</td><td></td></d>	<0.50	<0.50	120	12	

Nems:

Value in bold exceed the MCL

Coltonia Department of Health Drinking Water Program, Drinking Water Notification Level, December 14, 2007.
 Shaded values exceed the SSL for vapor innuison.

-Historical data for samping events conducted prior to October 2007 obtained from Table 3, Preliminary Groundater Investigation Report, A88) Foundry, 8SK Associates, fnc., dated June 11.

MCL = Collisions EPA Department of Health Service Maximum concentration levels for during water
Ls (VV = Regional Water Quality Control Board Environmental Screening Levels based on vapor Intrusion concerns for commercial land use scenario

RWCCB ESLs (V) = fregional Water Quality Centrel Board Environment Screward

All concentrations reported in microgram per limit (LgfL)

NO = Not detected at or above laboratory reporting imit.

<5.0 > Not detected at or above laboratory reporting limit of 5.0 ug/L.

NS = Not sampled.

-- Not analyzed.

J analyte detected below quantitation limits

Table 2 Summary of Semi-Annual Groundwater Monitoring Results - December 2010 ABSI Foundry 7825 San Learnito Street Galland, Cablerry

i) admes	ž	1249	TPHG	Ebanc	Ethylane	Methane	roc	1,1 · DCA	1.1 - DCE	13-DCA	from 1,2-DCE	ch 1,2-0CE	a-Bufylbernene	n-Propy Prenting	sec Butylbanzons	Gyntzena	Chloroethane	Ethylberuche	12,3. Inchioropingane	Ten-Buty/Brnssna	Lsopropy/bentlene	ananjoykdoudene	falvene	1,(,1-30A	Yhyl enlañde	Page Kylene	Naphittalene
Vente		(244)	1000	WORL	fron!	(M2/L)	(PQ4)	(NPA)	(not)	TV OV	(Val)	ואפען	11021	(Vg/U	(4 gA)	(H9/L)	THAT	(J'gu)	(109/11)	TUVU	[Pey]	(40\Q).	(DOC)	(ndyh	lugal	(nwi)	(ugic)
MCLs		NE	NE I	WE	NE	NE	NE	5.0	6.0	0,5	10	6.0	360	160.	566-	1.0	NE	700	0.005	580,	770-	NE	160	200	0.5	1750	17
RWOCE ESLA (VE)	-415	NE	N€	NE	WE	WE	NE	3,400	18,000	690	19,000	17,090	NE	NE	NE	1,800	2,700	179,000	NE	NE	NE	N€	\$30,000	160,000	13	160,000	11,600
CAVIM	12/22/2010	<50	450	<10	<£\$	4,500	40,000	0.29.5	0,82	<0.50	<0.50	<0.50	<0.50	<0.50	40.50	0.40 J	3.5	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	Ø 50	0.97	<1.0	40.50
HYV-B	12/22/2010	<50	120	<10	<15),500	600,62	<0.50	0.76	<0.50	<0.50	<2.50	40,50	₹0.50	<6.55	0.43.1	91	<0.50	€0.50	<0.50	<0,50	<0,50	<0,50	<0.50	<0.50	4.0	<0.50
W/VF-3	12/22/2010	2,200	120	6.8	<3.0	2,200	74,000	<0.50	₹0,58	<0.50	<0,50	<0.50	1,2	12.0	1.8	77	10 50	9,1	<0.50	0,41 J	12	2.3	1.8	<0.50	<0,50	1.4	0.75

Notes!

Vidues in hold exceed MCLS

HE - rule out pit mad

Git, under amplyzed

The + Dymitch's sample:

Tirtig - Topa Ferminum Hydrocurbons as Gameira

I Fried a Toma Particulary Hydrox arbitras de Clares

1.1-DCE-11-Diebesehaw

1.11-DCA -1.1-Distribustrant

11 t-Year til-frentspenses

12-DDF - LDCONNember

runi 1 2008 - Tanur 3 doministran na 13 005 - 8a 13 doministran

40 ft/ - not sepontati el er abriva laboratory's recontrols sinte et 0 ft/2 cg/L

17 with the belonged below to arribation being

MCs. If Africa I has been seen at the in Service of a consequence of a bottom for a section when

1 Easterna Expansions of Health Driving Weller Program Driving Weier techtication Level December 14, 2007

RYANCE ESLA IT - Reg. of the state of the st

TABLE 2A - WATER RESULTS

BENZENE, TOLUENE, ETHYLBENZENE, AND XYLENES Results in Parts Per Billion (ppb)

		CONSTITUENTS								
Sample Location (Action Level)	Benzene (1) ₁	Toluene (100),	Ethylbenzene (680) ₍	Xylenes (1750),						
MW-1	0.6	ND	ND	ND						
MW-2	ND	0.8	ND	ND						
MW-3	ND	ND	ND	ND						
MW-4	1.0	2.0	7.6	19						

ND - None Detected

- California Department Of Health Services Drinking Water Standard, Revised 10/23/91

- California DOHS Action Level, 7/1/92

TABLE 2B - WATER RESULTS

TOTAL PETROLEUM HYDROCARBONS (TPH) AS GASOLINE AND DIESEL, TOTAL AND HYDROCARBON OIL AND GREASE, TOTAL LEAD, AND VOLATILE HALOCARBONS Results in Parts Per Billion (ppb)

(Action	TPH Sasoline	трн	Total Oil	Hydrocarbon	Total	Volatile
Level)	(NA)	Diesel (NA)	& Grease (NA)	Oil & Grease (NA)	Lead (50)	Halocarbons (Determined by Compound)
MW-I		830	_			
MW-2 (920		1.0	. ND		0.6 - Bromoform(100), 5 - Chloroethane(NA), 1.7 - 1,1-Dichloroethane(0.5), 6.7 - 1,1,1-Trichloroethane(200),
MW-3	ND					-
MW-4	1800		•-	/	0.058 SB 58	

- Not Tested

- California Department of Health Services Drinking Water Standards, Revised 10/23/91.

- BPA Drinking Water Standard, Revised 7/1/92



Table 7 Summary of Natural Attenuation Parameters AB&I Foundry

7825 San Leandro Street Oakland, California

Well ID	Screened interval	Date	Methane	Chloride	Sulfate	Alkalinity	Bicarbonate	Ferrous Fe	Mn
Units	(feet)		(mg/L)	(mg/L)	(mg/L)	(mg/L)	(mg/L)	(mg/L)	(mg/L)
MW-1	5-20	10/25/2007	<10	69,000	340,000	330,000	330,000	1,600	2,300
MW-2R	5-20	10/25/2007	1,600	110,000	55,000	590,000	590,000	3,900	2,600
MW-3	5-20	10/24/2007	2,300	250,000	190,000	850,000	850,000	220	1,300
MW-4	5-20	10/24/2004	3,500	21,000	51,000	350,000	350,000	1,200	1,700
MW-5	5-20	10/25/2007	23	130,000	33,000	650,000	650,000	380	1,800
MW-6	5-20	10/24/2007	12	210,000	140,000	960,000	960,000	420	1,000
MW-7	5-20	10/25/2007	11,000	110,000	1,700	710,000	710,000	2,900	340
MW-8	5-20	10/25/2007	3,100	200,000	61,000	750,000	750,000	310	690
MW-9	5-20	10/25/2007	9,000	130,000	9,700	720,000	720,000	2,900	3,900

Notes:

(mg/L) - milligrams per liter

Mn -manganese

Fe -iron

-methane analyzed using RSK Method by Test America Laboratories (TAL), Pleasanton, California

-chloride and sulfate analyzed using EPA Method 300.0 by TAL

-alkalinity and bicarbonate analyzed using SM 2320B by TAL

-ferrous iron analyzed using SM 3500 FE D by TAL

-manganese analyzed using EPA Method 6010B by TAL

Table 1 Well Construction Details and Groundwater Elevation - December 2010 AB&I Foundry

7825 San Leandro Street Oakland, California

Well Number	Total Depth ¹ (feet, bgs ¹)	Solid Casing ² (feel, bgs ¹)	Screened Interval ³ (feet, bgs ¹)	Top of Casing (feet, msl ⁴)	Depth to Water (feet, bloc ⁵)	Groundwater Elevation (feet, msl ⁶)
MW-1	23	0-10	10-20	9.60	4.92	4.68
MW-2	17	0-8	8-17	NM	NM	Destroyed
MW-2R	20.5	0-5	5-20	7.49	NM	NM
MW-3	19.5	0-9	9-19	9.90	5.60	4.30
MW-4	26.5	0-10	10-25	10.49	6.42	4.07
MW-5	20.5	0-5	5-20	10.92	6.70	4.22
MW-6	20.5	0-5	5-20	10.19	6.86	3.33
MW-7	20.5	0-5	5-20	10.61	5.64	4.97
MW-8	20.5	0-5	5-20	11.19	7.09	4.10
MW-9	20.5	0-5	5-20	7.95	3.52	4.43

Notes:

- 1) feet, bgs = feet below ground surface
- 2) All monitoring wells constructed with 2" I.D. schedule 40 PVC; monitoring well MW-2 constructed with 4" I.D. schedule 40 PVC
- 3) All well casing includes .02" slotted screen
- 4) Top of casing elevation in feet above mean sea level (msl)
- 5) Depth to water below top of casing (btoc) measured on December 22, 2010
- 6) Groundwater elevation in feet above mean sea level (msl)

			WELL NO MW-1	
			PROJECT NO. P922	70.3
	FURSH MOUNT	TRAFFIC BOX-	Date Installed _3	/10/93
	1003111001	TRAIL IC BOX		
0 FT.	·	<u> </u>	SURVEYED ELEY_	19.94 ft.
	LOCKING CAP	→ [REFERENCE ELEV	9.52 TOC
			WELL CASING	20
	GROUT MIX:	3333	TYPEPY SCHEDULE	
	Neat Cement	R333	SIZE 2"	ID
	_		OCMENT INDOLES	
			- CEMENT/GROUT	
7 FT.			BLANK WELL CASING	
8 FT.		←	– BENTONITE PELLETS	
10 FT. r				
		 ※ ■ ※ ■ ※ ■ ※ ■ ※ ■ ※ ■ ※ ■ ※ ■ ※ ■ ※ ■ ※ ■ ※ ■ ※ ■ ※ ■ ※ ■ ※ ■ ※ ■ ※ ■ ※ ■ ※ ■ ※ ■ ※ ■ ※ ■ ※ ■ ※ ■ ※ ■ ※ ■ ※ ■ ※ ■ ※ ■ ※ ■ ※ ■ ※ ■ ※ ■		
		 		
1				
			WELL CONCEN	
		X	— WELL SCREEN SLOT SIZE0.	.020"
			LENGTH	10'
			FILTER PACK	
			TYPE 2/12	hoas
- FY			LENGTH 15 f	eet
20 FT.				
23 FT.		- BASSASSASSASSASSASSASSASSASSASSASSASSASS	TOTAL DRILLED E	EPTH
		`		
REMAR	RKS :			
000 1507 110	pg2270 2	14011170	NINO WELL	D OLC
PROJECT NO	, x944/U.3		ING WELL	<u>BSK</u>
FIGURE: 3		INSTALLATIO	ON DIAGRAM	& ASSOCIATES

			WELL NO MW-2	
			PROJECT NO. P92	270.3
			DATE INSTALLED	3/10/93
	FLUSH M	DUNT TRAFFIC BOX—		
i		i		
0 FT.		\downarrow	SURYEYED ELEV	/ +7.8 ft.
	LOCKING CAP		REFERENCE ELI	Y. <u>+7.60 ft</u>
Į.				
		333333	WELL CASING	
1	GROUT MIX:	M. 155555	TYPE	PVC
ì	GROOT THA.	(2228)	SCHEDUL	F 40
ļ	Neat Cement	_ 886		- inch ID
		- RXX		
		¥\$\$\$\$ * \$\$\$\$ *	CEMENT/GROUT	
6 FT.		₹ ₹₹	BLANK WELL CASIN	G
ь '''		<u> </u>		
		· ·	- BENTONITE PELLET	'¢
7 FT.			PENTONICE PEEFE	•
A 1-4		\$\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\		
8 FT.				
l l				
1		⋙=== ₩		
1		₩		
I				
		 	WELL SCREEN	
}			SLOT SIZE	0.020-1nch
l			LENGTH	9.11.5
		※ ■■		
}			FILTED DACK	
		X	-FILTER PACK	
			TYPE	gand
17 FT.			LENGTH10'	
17 FT.				
17 11.			TOTAL DRILLED	DEPTH
		·		
DENALS	nve .			
KETIN	; <i></i>			
				
M IEST US		1401	(NA (APPLI	
KUJECI NU	· P92270.3	l l	ING WELL	BSK
IGURE: 4		INSTALLATIO)N DIAGRAM	& ASSOCIATES
IUUKL. 4				1


WELL NO MW-3 PROJECT NO. P92270.3 DATE INSTALLED 3/10/93 FLUSH MOUNT TRAFFIC BOX-O FT. SURVEYED ELEV +10.14 feet REFERENCE ELEY . +9.83 feet TOC LOCKING CAP -WELL CASING TYPE PVC **GROUT MIX:** SCHEDULE 40 SIZE 2-inch ID Nest Cement - CEMENT/GROUT -BLANK WELL CASING 6 FT. --- BENTONITE PELLETS 7 FT. g FT. r WELL SCREEN SLOT SIZE _ 0.020-inch 10 feet LENGTH ___ FILTER PACK TYPE 2/12 sand LENGTH 12 feet 19 FT. 19.5 FT. TOTAL DRILLED DEPTH REMARKS: _____ PROJECT NO. P92270.3 MONITORING WELL BSK INSTALLATION DIAGRAM


FIGURE: 5

& ASSOCIATES

WELL NO MW-4 PROJECT NO. P92270.3 DATE INSTALLED 3/10/93 FLUSH MOUNT TRAFFIC BOX-O FT. SURVEYED ELEY +10.67 feet LOCKING CAP -REFERENCE ELEY. 4 10 40 FORT TOC WELL CASING TYPE _PVC **GROUT MIX:** SCHEDULE 40 SIZE 2-inch ID Neat Cement CEMENT/GROUT —BLANK WELL CASING 7 FT. --- BENTONITE PELLETS 8 FT. 10 FT. - WELL SCREEN SLOT SIZE _0.020 inch LENGTH 15 feet -FILTER PACK TYPE _2/12 sand LENGTH 18.5 feet 25 FT. 26.5 FT. TOTAL DRILLED DEPTH REMARKS: _____

PROJECT NO. P92270.3	MONITORING WELL	BSK
FIGURE: 6	INSTALLATION DIAGRAM	& ASSOCIATES





 \triangle

Denotes stabilized water table

~

Denotes water table at the time of drilling

NOTES:

- 1. Boring completed at a depth of 17 feet on 2/17/93.
- Sampling resistance is measured in blows per foot required to drive the sampler 12 inches with a 140 lb. hammer falling 30 inches after sampler has been seated 6 inches.
- Boring log indicates interpreted subsurface conditions only at the location and the time the boring was drilled.
- . 4. For an explanation of terms used see the Soil Classification Chart, Figure 3.
- Well constructed of 4" PVC, 0.020" screen from 17' to 8', case to surface, sand from 17' to 7', bentinite to 8', cement to surface.

SHALLOW SOIL AND GROUNDWATER
CHARACTERIZATION
AMERICAN BRASS & IRON
OAKLAND, CALIFORNIA


Job No. P92270.3 April 1993 FIGURE: 9

BSK & ASSOCIATES

		FI	ELD DA	ATA			BORING LOG: MW-2R	•
ДЕРТН (Feot bgs)	SAMPLER TYPE SAMPLE NO.	SAMPLE INTERVAL	TIME OF COLLECTION	BLOWS/FOOT	P7D (ppm)		DATE(S): 8/13/06 LOGGED BY: E. Studley WATER LEVEL: 9 feet at time of drilling EQUIPMENT: BK-81, 8" HSA	WELL
8	33	SAM		5) <u>Q</u> ud	กรcล	DESCRIPTION	₹8 8
-	Drillied With me <u>st</u> down no sampling					CL/CH	4" Concrete Silty Sandy Clay: Olive brown/gray, moist, medium grained sand, very soft Cament 0-3' Bentonite 3-4'	
5 ~			-			SC	Clayey Sand: Dark gray, loose 2/12 Sand 20-4' medlum grained sand	no accurac
•						CL	Sandy Clay: Dark offive gray, wet, Stotled PVC 20-5 very soft	
0								
5 —					-1	CL/CH	Clayey Sand: Olive brown, wet, loose, medium grained sand	THE PERSON NAMED IN
						CL	Sandy Clay: Olive brown, wet, fine grained sand Total Depth Well 20	
0 -							Total Copul West 20	SE SELEN
						-		
0 -						_		
5								

PROJECT NAME: A B & I, Oakland, California


PROJECT NUMBER: E0605504S



SHALLOW SOIL AND GROUNDWATER
CHARACTIZATION
AMERICAN BRASS & IRON
OAKLAND, CALIFORNIA

Job No. P92270.3 April 1993 FIGURE: 10

BSKASSOCIATES



		F	ELD DA	ATA			BORING LOG: MW-5_	
DEPTH (Feet bgs)	SAMPLER TYPE/ SAMPLE NO.	SAMPLE INTERVAL	TIME OF COLLECTION	BLOWS/FOOT	PID (ppm)		DATE(S): 8/12/06 LOGGED BY: E. Studley WATER LEVEL: 13 feet at time of drilling EQUIPMENT: CME-75, 8" HSA	WELL
430	SAN	SAM	118ME	BLC	PD (USCS	DESCRIPTION	M 8
-						Fill	3" Asphalt Concrete Silty Sandy Gravel: Yellow brown, damp, (Fill) 2" PVC 0-5"	
-	CS-1		11:05	32		CL/CH		200 Sec.
5	CS-2		11:08	11		СН	Silty Clay: Dark gray, moist, soft, 2/12 Sand 20-4' trace organics	Duri Carretto San
-	CS-3		11:12	12			Slotted PVC 20-5'	
10 -	CS-41		11:15	11			Silty Clay: Brown mottled oilve gray, moist, soft	÷ A
15	CS-6)		11:18	4		CL/CH	Silty Sandy Clay: Olive brown, wet, soft medium grained sand	
20 -	~~~		11:54	24			grades mottled olive brown/gray Total Depth Well 20'	
-	C\$-61		11:24	21		SC	Clayey Silty Sand: Gray brown, medium grained sand	3 9 1
25 -								
30 -			_					
35								

		F	ELD DA	ATA			BORING LOG: MW-6	
DEPTH (Faet bgs)	SAMPLER TYPE/ SAMPLE NO.	SAMPLE INTERVAL	TIME OF COLLECTION	BLOWS/FOOT	PID (ppm)		DATE(S): 8/12/06 LOGGED BY: M. Cline WATER LEVEL: 13 feet at time of drilling EQUIPMENT: CME-75, 8" HSA	WELL
DEP	SAN	SAN	TIME	вго	PED	USCS	DESCRIPTION	WEL
-						Fill	3" Asphalt Concrete Silty Sandy Gravel: Brown, damp, (Fill) 2" PVC 0-5"	
_	CS-1		9:10	10		CL/CH Fill	Sandy Silty Clay: Dark gray brown, moist, trace gravel, wood, brick (Fill) Sentonite 3-4'	
5 —	CS-2		9:15	12		СН	Silty Clay: Dark gray, moist, soft, 2/12 Sand 20-4' trace organics	
40	CS-3		9:18	14			grades dark gray to olive gray, very moist Slotted PVC 20-5	
10 -	CS-4		9:21	15			Silty Clay: Brown mottled oilve gray, very moist to wet in pores, some carbonates	
15 -	CS-6 ,		9:25	10		CL/SC	Silty Clay/Clayey Sand: Brown to light olive brown, wet Total Depth Well 20*	
20 –	ČS-6		9:38	6		CL/CH	Silty Clay: Brown to light office brown, wet	
25 -								
30 -								

		FI	ELD DA	ATA .	_		BORING LOG: MW-7_	
DEPTH (Feet bgs)	SAMPLER TYPE/ SAMPLE NO.	SAMPLE INTERVAL	TIME OF COLLECTION	BLOWS/FOOT	PID (ppm)		DATE(S): 8/12/06 LOGGED BY: E. Studley WATER LEVEL: 13 feet at time of drilling EQUIPMENT: CME-75, 8" HSA	WELL
DEP	SAN	SAM	ME 100	ВГО	Old	uscs	DESCRIPTION	₹8 8
,		J				Fill	4" Concrete Silty Sandy Gravel: Yellow brown, damp, (Fill) 2" PVC 0-5"	
	CS-1		15:26	29		CL/CH Fill	1 1 1 1	
5 –	NR		15:30	18			2/12 Sand 20-4'	
- ! -	CS-21		15:34	11		СН	Silty Clay: Dark gray, wet, strong hydrocarbon odor Slotted PVC 20-5	dinaminati dina
10 -	CS-3	_	15;45	4			grades to dark gay mottled light gray wet, slight odor, roots/wood fragments Sandy Silty Clay: Olive brown/gray, wet,	Samuel of the same
15 -	CS-41		15:50	7		CLACH	soft, medium grained sand, faint odor	
20 -	22.5		10.01			 	grades to olive gray Total Depth Well 20"	
 - -	CS-5		16:01	9	-			
25 -						•		
30 -						 - 		
35 _								<u> </u>

		FI	ELD DA	ATA			BORING LOG: MW-8 _	
DEPTH (Feet bgs)	SAMPLER TYPE/ SAMPLE NO,	SAMPLE INTERVAL	TIME OF COLLECTION	BLOWS/FOOT	РІD (ррт)		DATE(S): 8/12/06 LOGGED BY: E. Studley WATER LEVEL: 13 feet at time of drilling EQUIPMENT: CME-75, 8" HSA	WELL CONSTRUCTION
750	SAN	SAN	TOS	вго	PID (บระร	DESCRIPTION	NO CON
						Fill	3" Asphalt Concrete Silty Sandy Gravel: Yellow brown, moist, (FIII) 2" PVC 0-5"	
-	CS-1		13:00	20		CL/CH Fill	Silty Clay: Dark olive brown, damp, gravels, Cement 0-3' wire, debris (Fill) Bentonite 3-4'	er ve
5 ~-	CS-2		13:02	В		CL/CH	Silty Clay: Dark olive brown, moist to wet 2/12 Sand 20-4' medium grained sand lenses	7. The state of th
-	CS-3		13:08	12			Stotted PVC 20-5'	
10 -	NR			13		СН	grades to olive brown mottled gray	
-			-					
15	CS-4	-	13:29	5		CL/CH	Slity Sandy Clay: Olive brown, wet, soft, medium grained sand	
-							trace carbonates Total Denth Well 201	
20 -	CS-5		13:36	15			trace caroonates	<u> </u>
]								
25 -								
30 -								
35						ŀ		

		FI	ELD DA	ATA			BORING LOG: MW-9	
DEPTH (Feet bgs)	SAMPLER TYPE/ SAMPLE NO.	SAMPLE INTERVAL	TIME OF COLLECTION	BLOWS/FOOT	PID (ppm)		DATE(S): _8/18/06 LOGGED BY: _J. Yeazell WATER LEVEL: 8 feet at time of drilling EQUIPMENT: Marl Limited Access, 8" HSA	WELL
DEP	SAM	SAM	E COL	BLO	PID (uscs	DESCRIPTION	SOR
						Fill	6" Concrete Sitty Clay: Dark gray, some concrete debris 2" PVC 0-5"	
	DP-1		10:57			СН	Silty Clay: Dark gray, hydrocarbon odor Cement 0-3' Bentonite 3-4'	(46) N - 18/30
5 -	DP-2		11:03				2/12 Sand 20-4	
-	DP-3		11:10			СН	Silty Clay: Olive brown/brown, no odor Slotted PVC 20-5'	Trade of the last
10	DP-4		11:29				grades wet, slight odor	
15	DP-5)		11:36				some fine sand, odor	Trafficial International Contraction
20 -	27.0						Total Depth Well 20	
-	DP-6		11:40					
25						_		
30 -							,	
35								

S	C		HE						BORINGWELL	ID:	
envire		11 (RC	E G	R	DUP, INC.			SB-1	
PROJE	CT NA	ME AND	ADDA C	ESS;		AB&	I Foundry		Project No.	01-ABI-001	
BORING	S LOC	ATION (AT SITE	Ε :		3 10	,000 Gallon USTs		Logged By:	Nathan Colfor	,
CONTR	ACTO	RANDI	EQUIPM	IENT:		Viror	nex Geoprobe				
SAMPL	ING M	ETHOD	:			Cont	linuous	MONITORING DEVICE:	MiniRae 2000		
START	DATE	(TIME)	:			10/3	0/2007 9:10	FINISH DATE/ TIME	10/30/2007 11:1	٥	
FIRST V	VATER	(BGS)	;			21.5	1	STABILIZED WATER LEVEL:			
SURFA	CE ELI	EVATIO	N:					CASING TOP ELEVATION:			
TOTAL	BORIN	IG DEP	TH(S):			30'		BORING DIAMETER/DEPTH:	3 1/4" / 30"		
Date/Time	Sample Interval	PID (ppm)	Recovery	Stradigraphy	Dөр\h (feet)	Water-level	(dassification ALL PERCENTAGE	LITHOLOGIC DESCRIPTION, color, moisture, density, grain as ARE APPROXIMATE UNLES	size/plasticity, of	her) : STATED	Well construction details
					0	ļ					.
					1		No recovery.				
	\times				2						
					3						
P	\times				4						
					5						
					8	_	Silty gravelly clay, medium	brown, moist (fill).			
		300			7						
					8						
	\times				9		_				
	-				10		Clay (CL), black (5Y, 2,6/1), moist, stiff, medium plaslicity,	no odor.		
					11						
					12						
		130B			14						
	\sim				15						
					16	-					
					17						
					18		Same as above, but more	moist, softer, pelroleum ador.			
					19	<u> </u>					
		-		<i>V///</i> 2	20						

C	C	$\overline{\Pi}$	THE						BORINGWELL	10	
anviro	XNIM61	lal		JR	BE (B	OUP, INC.		,	SB-1	
PROJEC	CT NA	ME A	ND ADD	RESS	S:	A8&	l Foundry		Project No.	01-AB(-001	
BORING	LOC	OITA	N (AT SI	TE):		3 10	,000 Gallon USTs		Logged By:	Nathan Colton	
CONTR	ACTO	R AN	D EQUIP	MEN	T:	Viror	nex Geoprabe			-	
SAMPL	NG M	ETHO	D:			Cont	inuous	MONITORING DEVICE:	MiniRae 2000		
START	DATE	(TIM	E):			10/30	0/2007 9-10	FINISH DATE/ TIME	10/30/2007 11:1	٥	
FIRST V	VATER	t {8G	S):			21 5		STABILIZED WATER LEVEL:			
SURFA	CE EL	EVAT	ION:					CASING TOP ELEVATION:			
TOTAL	BORIN	G D	EPTH(S):	:		30.		BORING DIAMETER/DEPTH:	3 1/4" / 30'		
Dale/fime	Sample Interval	PID (ppm)	Recovery	Stratigraphy	Depth (feet)	Wafer-level		LITHOLOGIC DESCRIPTI n, color, moisture, density, grain ES ARE APPROXIMATE UNLE	size/plasticity, of		Well construction details
				SISSINAL SECTION SECTI							
					20						
					21	_					
					22						
		0.9			23		Sandy gravel (SP) coarse	grained, wet, poorly sorted, loos	e no odor, arave	Loieces.	
	_		-		24		, , , , , , , , , , , , , , , , , , ,	g,,,	_,, g	,	
	\boxtimes				25						
					26						
				m	27						
		_			28		Silty clay (CL), light yellowis	sh brown (10YR, 6/4), wet, medi	um plasticity, no	odor	
	\boxtimes				29	_					
			_			_		5-44 of Paris- 20°			
		_		_				Bottom of Soring 30'			
				_	31						
					32						
					33						
		_			34						
					35						
					36						
					37						
					38						
				L	39						
					40						

SB I ds Page 2 of 2

		1	HE						BORINGWELL	ID:	
anviro	Onmen nemn			JR	CE (A	OUP, INC.		5	SB-2	
PROJE	CT NA	ME AN	D ADD	RES	S:	AB&	Foundry		Project No.	D1-ABI-001	
BORING	LOC	MOITA	(AT SI	TE):		3 10	,000 Gallon USTs	•	Logged By:	Nathan Colton	
CONTR	ACTO	ONA P	EQUIF	MEN	IT:	VIIOI	nex Geoprobe				
SAMPL	NG MI	ETHOE) :			Cont	เกชอนร	MONITORING DEVICE:	MiniRae 2000		
START	DATE/	(TIME	} :			10/3	0/2007 11:15	FINISH DATE/ TIME	10/30/2007 124	5	
FIRST V	VATER	(BGS	} :			16'		STABILIZED WATER LEVEL:			
SURFA	CEEL	EVATK	ON:					CASING TOP ELEVATION:			
TOTAL	BORIN	IG DEF	(S)HT	:		25'		BORING DIAMETER/DEPTH:	3 1/4" / 25"		
Date/Time	Sample Interval	PID (ppm)	Recovery	Shatigraphy	Depth (feet)	Water-feve		LITHOLOGIC DESCRIPTION, color, moisture, density, grain ES ARE APPROXIMATE UNLES	size/plasticity, oth		Well construction details
					1		Cement debris.				
	$\overline{}$				ž	-					
					3		Silly Gravelly Clay(fill), oliv	e brown, moisi, stiff, medium pla	isticity, strong pet	roleum odor.	
	\times				4						
					5						
					8						
		300			7						
					8					1	
	\times				10						
					11						
					12						
					13	-	Clay (CL), black, moisi, ve	ry stiff, medium plasticity, petrole	eum odor.		
					14						
					15						
				New Period	16	•	Sandy gravel (SP), dark gr	ay, coarse grained subangular g	gravel 1/4" to 1/2",	wel, petroleum	
					17						
					18		01. (01.)		4		
					19		Clay (CL), olive brown, mo	ist, stiff, medium plasticity, petro	leum oddr.		
	\searrow				20						

3		•	THE						BORINGWELL	. ID ⁻	
anviro	nmen	tal	Sou	JR	CE (R	BUP, INC.			SB-2	
PROJEC	ET NA	ME AN	ממא ם	RESS		AB&	Foundry		Project No.	01-ABI-001	
BORING	LOCA	MOITA	(AT SI	TE):		3 10	,000 Gallon USTs		Logged By:	Nathan Collon	
CONTRA	ACTO	R AND	EQUIP	MEN	T :	Viron	<u>вх Geo</u> probe				
SAMPLI	NG M	THOE);			Cont	inuous	MONITORING DEVICE:	MiniRae 2000		
START	DATE/	(TIME):			10/30	0/2007 11:15	FINISH DATE/ TIME	10/30/2007 12:4	45	
FIRST W	VATER	(BGS) :			18"		STABILIZED WATER LEVEL:			
SURFAC	CE ELI	EVATION	ON:					CASING TOP ELEVATION:			
TOTAL	BORIN	IG DEF	PTH(\$):	:		25'		BORING DIAMETER/DEPTH:	3 1/4" / 25"		
Date/Time	Sample Interval	PID (ppm)	Recovery	Strafigraphy	Depth (feet)	Water-tevel	(dassification	LITHOLOGIC DESCRIPTI n, color, moisture, density, grain ES ARE APPROXIMATE UNLE	size/plasticity, o	ther) E STATED	Well construction details
		1400			20						
			-		21		Sandy gravel (SP), coarse	grained, sub-angular 1/4" to 1/2	", poorly sorted, v	wet, na odar.	
			Į.		23						_
	$\overline{\mathbf{x}}$	2			24		Clay (CL), medium brown,	wel, tight, medium plasticity, no	odor.		
				<i>AULUU</i>	25			Bottom of Boring 25'			
					26						
					27						
		_			28						
					29						
					30						
			— —		31						
					32						
					33						
					34						
					36						
					37						
				_	38						
					39						
					40	1					

		1	THE						BORINGWELL	ID:	
envire	nmen	tal	Sol	JR	GE (ìR	oup, Inc.			SB-3	
PROJEC	T N'AI	ME AN	10A <u>0</u>	RES	S:	AB&	Foundry		Project No.	01-ABI-001	
BORING	LOC	ATION	(AT SI	TE):		3 10	,000 Gallon USTs		Lagged By:	Nathan Colton	
CONTR	ACTO	RAND	EQUIP	PMEN	IT:	Viror	nex Geoprobe				
SAMPLI	NG MI	ETHO):			Cont	เบทอกส	MONITORING DEVICE:	MiniRae 2000		
START	DATE	(TIME):			10/30	0/2007 1340	FINISH DATE/ TIME	10/30/2007 142	0	
FIRST V	VATER	(BGS) :			21'		STABILIZED WATER LEVEL:			
SURFAC	E ELI	EVATION	ON:					CASING TOP ELEVATION:			
TOTAL	BORIN	G DE	PTH(S)	;		25'		BORING DIAMETER/DEPTH:	3 1/4" / 25'		
Date∕Ti⊓e	Sample Interval	PID (ppm)	Recovery	Stratigraphy	Depth (feet)	Water-level		LITHOLOGIC DESCRIPTION, color, moisture, density, grain ES ARE APPROXIMATE UNLES	size/plasticity, oth	er) STATED	Well construction details
					1	-	Cement debris.				
					2					_	
	×				3		Gravely sand (SP) with chu	inks of asphall, reddish brown, r	noist, sub-angula	r, (fill).	
	$\overline{\mathbf{x}}$				4		Gravely sand (SP) with chu	inks of asphalt, reddish brown, r	noist, sub-angula	r, (fill).	
					5						
					6		No recovery.				
					7						
		140			8						
	\leq			***************************************	9						
					10						
	1				12		Clay (CL), gray, wet, soft, n	nedium plasticity, petroleum odo	ır.		
					13						l
	\times	120			14						
					15						
					16						
					t7	_					
					18						
					19						
	\times	112			50		Clay (CL), gray, wet, stiff, n	nedium plasticity, petroleum odo	1_		

SB-3 xls Page 1 of 2

			THE						BORINGWELL	ID:	
enviro	оптеп	tal (Sou	JRO	GE (iR	oup, Inc.			SB-3	
PROJEC				_		_	Foundry		Project No.	01-ABI-001	
BORING	3 LOC	ATION	AT SI	TE):		$\overline{}$,000 Gallon USTs		Logged By:	Nathan Collon	1
CONTR	ACTO	R AND	EQUIF	MEN	T :	Viror	nex Geoprobe				
SAMPL	ING M	OHTE) :			$\overline{}$	กบอบร	MONITORING DEVICE:	MiniRae 2000		
START	DATE	(TIME	<u>:</u>):			10/3	0/2007 13:40:00 AM	FINISH DATE/ TIME	1.0/30/2007 14:	20:00 AM	
FIRST V	NATER	(BGS	i):			21'		STABILIZED WATER LEVEL:	1		
SURFAC								CASING TOP ELEVATION:			
TOTAL	BORIN	IG DEI	PTH(S)	:		25'		BORING DIAMETER/DEPTH:	3 1/4" / 25"		
Date/Time	- u. v,				Dapth (feet)	Water-fevel	(dassificati ALL PERCENTAC	LITHOLOGIC DESCRIPT on, color, moisture, density, grain GES ARE APPROXIMATE UNLE	size/plasticity, o	ther) ESTATED	Well construction details
					20	Y					
				Sand (SP), medium grained, wet, loose, no odor. 22 Sandy gravel, coarse grained, sub-angular 1/2" to 3/4", poorly sorted, no							
					23		Sandy gravel, coarse grain	ned, sub-angular 1/2" to 3/4", por	олу sorted, па ад	òr.	
					24		Silty clay (CL), (Ight to med	dium brown, wet, stiff, medium pl	lasticity, no odor.		
	\times	٥		Willi.	25			Battom of Boring 25'			+
		_			26	_		-			
				-	27	├-					
					28	 					
					29						
					30						
					31	-					
				-	32						
					33						
					34						
					35						
					36						
					37	_					
					38						
					40				_		

		1	THE						BORINGWELL	ID:	
anvire	onmen			JR	CE (R	oup, Inc.		5	8B-4	
PROJE	CT NA	ME AN	D ADO	REŚ	S:	AB&I	Foundry		Project No.	01-ABJ-001	
BORING	G LOC	ATION	(AT S	ITE):		3 10	,000 Gallon USTs		Logged By:	Nathan Colton	,
CONTR	ACTO	R AND	EQUI	PMEN	ŧΤ:	Viron	ex Geoprobe	·			
SAMPL	ING MI	THO) ;			Cont	inuous	MONITORING DEVICE:	MiniRae 2000		
START	DATE	(TIME	:				0/2007 14:30	FINISH DATE/ TIME	10/30/2007 15:2	٥	
FIRST	NATER	(BGS);			21 5		STABILIZEO WATER LEVEL:			
SURFA	CE ELI	EVATION	ЭN:					CASING TOP ELEVATION:			
TOTAL	BORIN	IG DEF	PTH(S)):		54.		BORING DIAMETER/DEPTH;	3 1/4" / 24"		
Date/Time	Sample Interval	PID (ppm)	Recovery	Stratigraphy	O Depth (feet)	Water-leve)	(classification ALL PERCENTAGE	LITHOLOGIC DESCRIPTION, color, moisture, density, grain	size/plasticity, oth	er) STATED	Well construction details
					1	 -	Cement debris.				1
	\times				3			unks of asphall, reddish brown, r	ποίsι, sub-angulai	r, (तिll).	
					4	_	Clay (CL), black, moist, stil	f, medium plasticity, no odor.			-
					5		No recovery.				1
					•	Ì	,				
					6						
					7						
		-			8		Clay (CL), black, moist, stil	f, medium plasticity, no odor			
					9						
					10						
					11						
			ļ		12						
					13						
	\bowtie	700			15						
		700									
					16						
					17						
					18						
					19						
		200			20						

			THE						BORINGWELL	ID:	
envire		tal	Sol	JRO	CE E	iR	OUP, INC.			SB-4	
PROJE	CT NA	ME AN	D ADD	RESS		AB&I	Foundry		Project No.	01-ABI-001	$\overline{}$
BORING	LOC	MOITA	(AT SI	TE):			,000 Gallon USTs		Logged By:	Nathan Cotton	
CONTR	ACTO	R AND	EQUIP	MEN	Т:	Viron	ex Geoprobe				
SAMPL	ING MI	ETHO) :			Cont	กขอบร	MONITORING DEVICE:	MiniRae 2000		
START	DATE	(TIME):			10/30	0/2007 14:30	FINISH DATE/ TIME	10/30/2007 15:2	0	
FIRST						21.5		STABILIZED WATER LEVEL:			
SURFA	CE EL	EVATION	ON:					CASING YOP ELEVATION:			
TOTAL	BORIN	IG DEI	7TH(S):	:		24'		BORING DIAMETER/DEPTH:	3 1/4" / 24'		
Date/Time	Sample Interval	PIO (ppm)	Яесочелу	ЅѴҽ҈ѹӈү	Depth (feet)	WaterJevel	(classificatio ALL PERCENTAG	LITHOLOGIC DESCRIPTI n. ∞lor, moisture, density, grain ES ARE APPROXIMATE UNLE	size/plasticity, ol	her) E STATED	Well construction details
					20		Gravely sand (SP) with				
					21	T	Sandy gravel, coarse grain	ed, sub-angular 1/4" (o 3/4", we	L, no odor.		
					22		Claurical Stranger and add	war and the complete and a second			
	\simeq				23		Refusal @ 24' Battom of Boring 24'	f, medium plasticity, no odor			
					25		Battom of Bonng 24				
					26						
					27						
					28						
					29						
				-	30						
	-				31						
					32						
					33						
					34						
					35						
					36						
				_	38						
				_	39						
					40						
			l	1	70	1					J l

C	C	1	THE						BORING/WELL	. ID	
envir	onmen	l lal	Soi	JR	CE	GR	OUP, INC.			SB-5	
ROJE	CT NA	ME AN	ID ADI	DRES	S :	A8&	l Foundry		Project No.	01-ABI-001	
ORIN	G LOC	ATION	AT S	ITE):			0,000 Gallon USTs		Logged By:	Nathan Colto	n
ONTR	ACTO	R AND	EQUI	PMEN	(7):	Viror	nex Geoprobe			-	
AMPL	ING MI	ETHO) :			Cont	ยมดบกเ	MONITORING DEVICE:	MiniRae 2000		
TART	DATE	TIME):			10/3	1/2007 8:00	FINISH DATE TIME	10/31/2007 8:52	5	
IRST \	WATER	(BGS	i):			21 5		STABILIZED WATER LEVEL:			
URFA	CE ELI	TAVE	ON:					CASING TOP ELEVATION:			
OTAL	BORIN	IG DEI	PTH(S)) ;		25'		BORING DIAMETER/DEPTH;	3 1/4" / 25'		
Date/Time	Semple Interval	PID (ppm)	Recovery	Stratigraphy	Oepth (feet)	Water-tevel		LITHOLOGIC DESCRIPTION, color, moisture, density, grain ES ARE APPROXIMATE UNLE:	size/plasticity, ot		Well construction
					1	-	Con		_		1
			<u> </u>			ļ	Cement debris.	A CONTRACTOR OF THE CONTRACTOR	I At 4	14.4	4
					5		odor.	s at gravel 3/4" subangular, ligh	L megium piasuo	aty, petroleum	
	\boxtimes	•			3						
					4	-					
	\boxtimes					$oxed{oxed}$					1
					S						
					в		No re∞very.				
					7						1
					8		Clay (CL), black, moist, stil	ff, medium plasticity, petroleum o	odor.		
					9						
	\times				10						
					11	\vdash	Clay (CL) Allya hown stiff	f, moist, medium plasticity, petro	laum adaz		
					12		- Silly (SE), Blive Orbini, Still	, most, median prasacty, pend	Juliu Gabi		
					13	-					
			-		14	\vdash	Same as above bul more o	of a light gray to olive brown colo	or.		
_	$\geq \leq$	200			15	<u> </u>	Clay with trace out ICE Lin	ght to medium gray, wet, soft, pet	troteum odor		
					16	\vdash	Area more wet and more s				
					17	\vdash		nity Jul Saliic as BOUYE.			
					18	-	-				
	-				19		Clay (CL), light to medium	gray, well, soft, low plasticity, pe	rroteum adar.		
					20		-				
	\boxtimes	700				1					

			THE	_					BORINGWELL	. ID:		
enviso	onmar	tel (ate	Sol	IR	CE (GR	oup, Inc.			SB-5		
PROJE	CTNA	ME AN	ם מא מי	RES	S:	AB&	Foundry		Project No.	01-ABI-001		
BORING	LOC.	ATION	(AT S)	TE):		3 10	0,000 Gallon USTs	Logged By:	Nathan Colton			
CONTR	ACTO	RAND	EQUIP	MEN	ፕ:	Viror	nex Geoprobe					
SAMPL	NG M	ETHO):			Cont	กักบอบร	MONITORING DEVICE:	MiniRae 2000			
START	DATE	(TIME):			10/3	1/2007 800	FINISH DATE/ TIME	10/31/07 852			
FIRST	VATER	≀ (BGS):			21.5		STABILIZED WATER LEVEL:				
SURFA	CE EL	EVATION	ON:	_				CASING TOP ELEVATION:				
TOTAL	BORIN	IG DE	(e)HT	:		25'		BORING DIAMETER/DEPTH:	3 1/4" / 25'			
Date/Time	Sample Intervel	PID (ppm)	Recovery	Stretignaphy	Depth (feel)	Water-fevei	ther) E STATED	Well construction details				
					20	T	Silty clay (CL), light to med					
					22		Sandy gravel (SP), coarse no odor.	Sandy gravel (SP), coarse grained, 1/4" to 3/4" subangular gravel plece				
					23		Clay (CL), light brown, moi	st, stiff, medium plasticity, no od	lor.			
					24							
					25			Bottom of Boring 25'				
					26							
					27							
					28							
					29							
					30							
					31							
					32							
					34							
				_	35							
					36	_						
					37							
					38							
					39							
					40	 						

SB-3, us Page 2 of 2

C		1	THE						BORINGWELL	ID.				
envir	onmer	ital	Soi	JR	CE (3 R	OUP, INC.		:	SB-6				
PROJE	CT NA			_		_	Foundry		Project No.	01-ABI-001				
	G LOC					1	00 gal VSY		Logged By:	Nathan Colto	n			
	MCTO	_			IT:		nex Geoprobe		33					
	JING M						inuous	MONITORING DEVICE:	MiniRae 2000					
START	DATE	(TIME				11/5	/2007 900	F)NISH DATE/ TIME						
FIRST	WATER	R (BGS) :			6.5		STABILIZED WATER LEVEL:						
SURFA	CEEL	EVATION	ON:					CASING TOP ELEVATION:						
TOTAL	80RI	G DEF	TH(S)	:		24'		BORING DIAMETER/DEPTH:	3 1/4" 24'					
Date/Time Sample Interval PID (ppm) Recovery Stratigraphy Depth (feet)						Wafer-level		LITHOLOGIC DESCRIPTION (classification, color, moisture, density, grain size/plasticity, other) ALL PERCENTAGES ARE APPROXIMATE UNLESS OTHERWISE STATED						
					1	-	Cement debrīs.	ement debris. lay (CL), black, moist, stiff, medium plasticity, organic odor, chunks of gravel.						
			L		2	 								
		5			3									
					4		-							
	\times				5									
					6									
					7									
					8]							
	\times	20			9		Clay (CL), dark gray (2.5Y	4/1), stiff, medium plasticity, fair	t petroleum odor	•				
					10									
					11	<u> </u>	Clay (Ct) dark pressich o	ray (GLEY 2 4/1), moisl, tight, m	adlum Nasticitu	an ador				
					13				esioni producty,					
					14	-	_							
_	X	5			15	┼	Sifty day (CL), moist, soft,	low plasticity, no odor.						
					16	\vdash	_							
					17		Same as above but righter							
					18	-	-							
					19	—	Clay (CL), light gray, moisi	, tight, medium plasticity, no odd	r.					
					20		20' 24' - No recovery -	· GW sample @ 23'						

		1	THE						BORINGWELL	ID:		
envire	nemno	tal	Soi	JR(CE (R	oup, Inc.		;	SB-7		
PROJE	ÇT NA	ME AN	D ADD	RESS	3:	AB&	I Foundry		Project No.	01-ABI-001		
BORING	LOC	NOITA	(AT SI	TE):			ehouse		Logged By:			
CONTR	ACTO	R AND	EQUIP	MEN	T:	Viror	nex Geoprobe					
SAMPL	ING MI	ETHOD):			Мас	<i>-</i>	MONITORING DEVICE:	MiniRae 2000			
START	DATE	(TIME):			10/3	1/07 1045	FINISH DATE/ TIME	10/31/07 1200			
FIRST V		•	-			17'		STABILIZED WATER LEVEL:	1			
SURFA								CASING TOP ELEVATION:	<u> </u>			
	_			:		20		BORING DIAMETER/DEPTH:	20,			
	TOTAL BORING DEPTH(S):							.,		5		
Date/Time Sample Interval PID (ppm) Recovery Stratigraphy						Water-levef	(classification	LITHOLOGIC DESCRIPTION, cofor, moisture, density, grain ES ARE APPROXIMATE UNLES	size/plasticity, oli	her) STATED	Well construction details	
				\vdash	1	 	Concrete debris stiff.		·		-	
					•		Condete debris siin.					
				\Box	2		1					
		7.6		Ш								
				mm	3		Slay (CL), black, moist, medium plasticity, slight hydrocarbon odor?					
	\vdash				4	<u> </u>	Clay (CL), black, moist, me	dium plasticity, slight hydrocarb	on odor?			
					4							
	\boxtimes				5							
					6							
					7		Clay (GL), very dark gray (10YR 3/1), moist, stiff, medium p	Siasucity, no odoi	`.		
					8							
					9							
					10		Same as above but dark yo	ellowish brown (10YR 4/4)				
					11	 						
		140			12	-	Clay (CL) dady prophish a	ray (GLEY1 5/1), molst, stiff, me	dlum bloellaiht b	elroleum ndar	I I	
	-	140			13		(faint).	or come is only moist, studies	a.a.s. piesooiy, p			
		500			14							
	\bowtie	300			15		Silly risy (C)) dort aroos:	sin gray, wet, soft, low plasticity.	on odor			
					16		John Day (GE), Daik greens	an gray, wer, son, row prosticity.	0001.			
					17							
					16		Clay (CL), dark greenish g	ray, moist, stiff, medium plasticit	y, no odor.			
			3		19							
					20		Silty gravel (SP), greenish	gray, 1/4" subangular, moist, po	ally sorted, no oc	יסנ_		

C		1	THE						BORINGWELL	ID:	
enviro	nemo	181	Soi	UR	CE (GR	OUP, INC.		:	\$B-8	
PROJE	CT NA	ME AN	ID AD	ORES	 8 S :	AB8	l Foundry		Project No.	01-ABI-001	
BORING	LOC	ATION	(AT S	ITE):			ehouse		Logged By:	Nathan Colton	1
CONTR	ACTO	R AND	EQUI	PME	NT:	Viro	nex Geoprobe			•	
SAMPL	ING MI	ETHO) ;			Mac	rocore	MONITORING DEVICE:	MiniRae 2000		
START	DATE	/ (TIME	:			10/3	1/07 1240	FINISH DATE/ TIME	10/31/07 1340		
FIRST	VATER	R (BGS	s):			17'		STABILIZED WATER LEVEL:			
SURFA	CE ELI	EVATI	ON:					CASING TOP ELEVATION:			
TOTAL	BORIN	IG DEI	гртніг	<u>):</u>		20'		BORING DIAMETER/DEPTH:	20		
Dept (Well construction details	
					1		Cement debris,				-
					2		Sandy gravel (asphall), bla	ck, dry, poorly sorted, no odor.		_	1
					3						
				11111	1		Clay (CL), dark brown/blac	k, moist, stiff, medium plasticity,	no odar		1
					5), (==),	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,			
					6	-					
		_			7		Clay (CL), dark olive brown	n, moist, stiff, medium plasticity,	no odor.		
					8						
					9		Same as above but olive b	rown, more silt component.			
					10						
		16			11		Clay (CL), dark bluish gray	(GLEY2 4/1), moist, stiff, mediu	m plasticity, faint	petrolaum odor.	
					12						
	\overline{S}				13		Same as above but strong	er petroleum adar			
		544			15		Same as above out shorts.	er perioleum dadi.			
					16	_					
					17						
					18		Silly day (CL) with some 9.	ravel, wet, soft, low plasticity, no	odor		
					19		Clay (CL), medium gray, m	olst, stiff, medium plasticity, no	odor]
					20			Total Depth 20'			
<u></u>]					1	_			لــــــــــــــــــــــــــــــــــــــ

\$8-8×0 Page 1 of 1

	G		HE	_			_		BORINGWELL	. IO:	
envir				JR	CE (GR	OUP, INC.			SB-9	
PROJE	GT NA	ME AN	D ADC	RES	<u>s:</u>	88A	l Foundry		Project No.	01-ABI-001	
BORING	S LOC	ATION	(AT SI	TE):		Wan	ehouse		Logged By:	Nathan Colic	חי
CONTR	ACTO	RAND	EQUI	PMEN	∤ Τ:	Viror	ех Geoprobe				
SAMPL	ING M	ETHOL):			Cont	inuous	MONITORING DEVICE:	MiniRae 2000		
START	DATE	TIME):			10/3	1/07 1335	FINISH DATE/ TIME	10/31/07 1420		
FIRST	WATER	(BGS):			17'		STABILIZED WATER LEVEL:			
SURFA	CE EL	EVATIO	ON:			<u> </u>		CASING TOP ELEVATION:			
TOTAL	BORIN	IG DEF	PTH(S))t T		20'	T	BORING DIAMETER/DEPTH;	20'		
Sam Sam PID (Reco Strati								LITHOLOGIC DESCRIPTION, COID, MOISTURE, DESCRIPTION, MOISTURE, DENSITY, GRAIN ES ARE APPROXIMATE UNLE:	size/plasticity, of		Well construction detalls
					1		Cement debris.				1
			-		2		Sandy gravel (asphali), bla	ck, dry, poorly soried.			┨
		_			3						
					4						
			-		5		Clay (CL), dark gray, moist	stiff, medium plasficity, no odo	ī		_
					6						
					7						
					8		Clay (CL), dark bluish gray	, moist, medium plasticity, faint p	saudiaum odor.		
					9		Stronger petroleum odor.				
					10						
		25			11						
		•			12		Petroleum odor.				
					13						
		30			14						
					15						
					16	Y					
					17		No re∞very				
					18		•				
					19			majo sema ti ma			
					20			Bottom of Boring 20'			

58-9201

C		1	THE						BORING/WELL	. ID:			
envin	onmen			UR	CE	G R	OUP, INC.		8	B-10			
PROJE	CT NA	ME AN	D ADI	DRES	38:	AB&	Foundry		Project No.	01-ABI-001			
BORIN	G LOC	ATION	(AT S	ſ₹E):			Gal VST	Logged By:	Nathan Colton	n			
CONTR	RACTO	R AND	EQUI	PME	NT:	Vira	nex Geoprobe						
SAMPL	ING M	ETHO) :			Con	inuous OW	MONITORING DEVICE:	MiniRae 2000				
START	DATE	(TIME):			10/3	1/07 1430	FINISH DATE/ TIME					
FIRST	WATER	(BGS):			Nov	rater	STABILIZED WATER LEVEL:					
SURFA	URFACE ELEVATION:							CASING TOP ELEVATION:					
TOTAL	BORIN	IG DEF	PTH(S]:		30'	PATTUS MARKET	BORING DIAMETER/DEPTH:	3 1/4" / 30"				
Sarr Straff							(classification	LITHOLOGIC DESCRIPTION, color, moisture, density, grain ES ARE APPROXIMATE UNLES	size/plasticity, of	her) : STATED	Well construction details		
					1		Concrete debris.				1		
					3		Sandy gravel (asphall), dry	, 1/2" subangular, poorly sorted.	no odor.				
	\times				4		Same as above but petrole	Same as above but petroleum odor.					
		700			5		Clay (CL), dark bluish gray	(GLEY 2 4/1), moist (wet?), soft	low plasticity, p	etroleum odor.	┨		
					6		, , (o - <u>,,</u> com o		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,				
	_	300			7								
					8								
	\boxtimes	500			9								
					10								
					12	-	Pelrolaum odor.						
					13]						
		400			14								
					16								
		20	 		17								
					18		Less of an odor						
					19								
	\geq	20			20	L							

		1	THE						BORINGWELL	ID:	
anviro	оптеп			UR	CE	GR	oup, Ing.	S	B-10		
PROJE	CT NA	ME AN	D AD	DRES	is:	AB8	Foundry		Project No.	01-ABI-001	
BORING	LOC	NOITA	(AT S	iTE):		550	Gal VST	Logged By:	Nathan Colton	נ	
CONTR	ACTO	R AND	EQUI	PME	NT:	Vicor	nex Geoprobe				
SAMPL	ING M	ETHO) :			Cont	innoria DM	MiniRae 2000			
START	DATE	TIME	<u>)</u> :			10/3	1/07 1430	FINISH DATE/ TIME			
FIRST	VATER	R (BGS) :			Now	rater	STABILIZED WATER LEVEL:			
SURFA	CE ELI	EVATION	ON:					CASING TOP ELEVATION:			
TOTAL	BORIN	IG DEF	PTH(S) :		30,		BORING DIAMETER/DEPTH:	3 1/4" / 30'		
Date/Time	Sample Interval	PID (ppm)	Recovery	Straftgraphy	Oepih (feel)	Water-level	LITHOLOGIC DESCRIPTION (classification, color, moisture, density, grain size/plasticity, other) ALL PERCENTAGES ARE APPROXIMATE UNLESS OTHERWISE STATED				Well construction details
8					1		Concrete debris.				
					2		Sandy gravel (asphall), dry	, 1/2" subangular, poorly sorted,	no odor.		
	\times				3						
	\times				4	ı'.	Same as above but petrole	um odar			
		700		www.	5		Clay/Cl\ dade bluich gray	(GLEY 2 4/1), moist (wet?), soft	low placticity no	italeum adar	┤
		700			6		Clay (CL), dark bruish gray	(OLE 12 411), MOIST (WELT), SOM	, iow plasticity, pe	adjedin oddi.	
		300			7						
			_		8						
	\times	500			9						
					10						
					11						
					12		Petroleum odor.				
					14						
	\boxtimes	400			15						
					16	_					
		20			17						
					18		Less of an odor.				
					19						
	$\overline{\mathbb{X}}$	20			20						

C	G		HE						BORINGWELL ID;		
οπνίτο	nmen	tal	Sol	JR	CE (3 R	oup, Inc.	S	B-11		
PROJE	CT NA	WE AN	D ADE	RES	S:	AB&I	Foundry		Project No.	01-ABI-001	
BORING	LOCA	NOITE	(AT S	TE):		550 (Gallon USTs	Logged By:	Nathan Colton	,	
CONTR	ACTO	R AND	EQU	MEN	π: _	Vison	ex Geoprobe		•		
SAMPL	NG ME	THOE):			Cont	inuous	MONITORING DEVICE:	MiniRae 2000		
START	DATE/	(TIME):			11/1/	2007 7:45	FINISH DATE/ TIME	11/1/2007 9:40		
FIRST	VATER	(BGS);			20.5		STABILIZED WATER LEVEL:			
SURFA	CE ELI	EVATION	DN:					CASING TOP ELEVATION:			
TOTAL	BORIN	G DEF	TH(S)) :		25'		BORING DIAMETER/DEPTH:	3 1/4" / 25"	-	$\neg \neg$
	<u>_</u>										5
Date/Time	Sample Interval	PID (ppm)	Recovery	Stratigraphy	Depth (feet)	Water-level		LITHOLOGIC DESCRIPTION, COIOT, MOISTURE, DESCRIPTION CONTRACTOR OF THE CONTRACT CONTRACTOR CONTRACT	size/plasticity, oth		Well construction details
					1		Clay (CL), light and medium	n brown, wel, stiff, medium plasi	licity, no odor		1
					2						1
	\times			A DESCRIPTION OF THE PERSON OF	3		Sandy gravel (asphali), dry	, poorly sorted, no odor.			
	$\overline{\mathbb{X}}$	14			4		Clay (CL), black, stiff, medi	um, plasticity, faint petroleum or	or,		
					5						{
					6		Clay (CL), greenish gray (G	SLEY/ 5/1), moist stiff, medium (olasticity, petroleu	m odor.	
					7						
					8						
	\propto				10						
					11						
0					12						
			_		13						
					14						
	\simeq				15						
					16		Clay (CL), greenish gray w/	medium brown, moist, stiff, less	s of a pelroleum o	dor naticed.	
					17		Clau (Cl.) game se showe	bul with a higher grit content, m	nuckem toward	h m(w)	
					18		OLA SOME AS BOOME,	oot mut e nignet gni concest, tr	ore median	J. J	
					19						
	$\overline{\times}$				20	T	Silly clay (CL) (higher silt a ador.	onteni than above), medium bro	wn, wel, stiff, low	plasticity, no	

			THE						BORINGWELL	ID:	
S	UT NOTE OF	tal	So	UR	GE	GR	GUP, INC.		9	B-11	
PROJE						1	I Foundry		Project No.	01-ABI-001	
BORING							Gallon USTs		Logged By:	Nathan Colton	
CONTR							nex Geoprobe		203500 2)2	i i o o i o o i o o i o o i o o i	
SAMPL	_					-	inuous	MONITORING DEVICE:	MiniRae 2000		
START						1	/2007 7:45	FINISH DATE/ TIME	11/1/2007 9:40		
FIRST						20.5		STABILIZED WATER LEVEL:			
SURFA							_	CASING TOP ELEVATION:		-	
TOTAL	BORIN	IG DI	EPTH(S	3):		25`		BORING DIAMETER/DEPTH:	3 1/4" / 25'		
Date/Time	Sample Interval PID (apm) Recovery Strailgraphy			Depth (feet)	Water-laval	(classificatio	LITHOLOGIC DESCRIPTI n, color, moisture, density, grafn ES ARE APPROXIMATE UNLE	size/plasticity, of	her) E STATED	Well construction details	
					20		Cłay (CL), light and mediur	m brown, wel, stiff, medium plast	licity, no odor.	_	
					21						
					22	}					
					23						
	<u></u>				24						
			_		25	+		•			\vdash
				_	26						
					27						
					28						
					29						
					30						
					31						
		-			32		-				
	_	 			33	_					
					34	-	_				
	-	_			35						
					36]				
				-	37						
		<u> </u>		-	38	32					
					39						
	<u> </u>				40						
I			1	1	I	1	1				

C	G	1	THE						BORINGMELL	. ID;	
envin	onmen onmen	tal	So	UR	CE (Gr	OUP, INC.		5	SB-12	
PROJE	CT NA	ME AN	IO ADI	ORES	 33:	AB&	Foundry		Project No.	01-ABI-001	
BORIN	G LOC	ATION	(AT S	ITE :		$\overline{}$	Gailon USTs		Logged By:	Nathan Colto	ח
CONTR							nex Geoprobe		34		
SAMPL							inuous dw	MONITORING DEVICE:	MiniRae 2000		
START	DATE	(TIME) ;			_	/2007 9.30	FINISH DATE! TIME	11/1/2007		
	WATER	•				22'		STABILIZED WATER LEVEL:			
SURFA	CE EL	EVATION	ON:				_	CASING TOP ELEVATION:			
IOTAL	BORIN	IG DE	PTH(S	J:		25'		BORING DIAMETER/DEPTH:	3 1/4" / 25		
Date/Time	Sample Interval	РІО (ррт)	Recovery	Stratigraphy	Depth (feet)	Water-level		LITHOLOGIC DESCRIPTION, color, moisture, density, grain ES ARE APPROXIMATE UNLE	size/plasticity, of		Well construction
-					1		Cement debris.	<u>,</u>			-
					2	┼~~					-
							Candy any (al (santa)) blo	ali da asado esded			
	\boxtimes				3		Sandy gravel (asphall), bla	ack, ary, poony soneu.			
				uiin		┼—					4
					4		Clay (CL), black, moist, stir	ff, medium plasficity, no odor			
					5		1				
					6						
					7	├					
	1				′						
					8	1					
		_			9		Clay (CL), greenish gray, n	noist, stiff, medium plasticity, no	odor		
		0			10	+	-				
					, ,						
					\{1	1	1				
						<u> </u>					
		20			12		Same as above but faint p	etroleum odor noted.			
	\vdash	20			13	+	·				
		800			14		1				
	\sim				15		_				
					, ,						
					16		1				
							Clay (CL), dark greenish g	ray (GLEY 1 4/1), moist, stiff, me	edium pasticity, p	etroleum odor.	
					17						
	-				18		-				
					19						
	-		<u> </u>		20	+	1				
	\searrow	0					Same as above but lighter	petroleum odar noted			

6			THE				······································	·	BORING/WELL	_ IO:	
enviro	nmen	tal	So	UR	CE	Gr	oup, Inc.			SB-12	
						Т			Project No.	01-ABI-001	
						Virar	nex Geoprobe			•	
SAMPL	ING M	ETH	DD;					MONITORING DEVICE:	MiniRae 2000		
START	SOURCE GROUP, INC. SB-12 ROUGHT AND ADDRESS: ABASI Foundry Project No. O1-ABI-001 O1										
FIRST V	VATER	R (BG	S):			22'		STABILIZED WATER LEVEL:			
SURFA	CE EL	EVA ⁻	ΓΙΟN:					CASING TOP ELEVATION:			
TOTAL	BORIN	NG D	EPTH(S):		25'		BORING DIAMETER/DEPTH:	3 1/4" / 25		
Date/Time	Sample Interval	PID (ppm)	Recovery	Stratigraphy	Depth (feet)	Water-level	(classification	n, color, moisture, density, grain	size/plasticity, o	other) E STATED	Well construction details
							Clay (CL), medium brown.	rnoist, stiff, medium plasticity, no	o odor.		
	<u> </u>				22	1	_				
							Clay (CL) medium hrown	wet softer medium plasticity n	o odor.		
					23	-	John (Se), median brown,	wet, solor, mediani prosiety, n	0 0001.		
	~	0			24						
					25			Bottom of Baring 25'			
					26						
					27						
					28						
					29						
					30						
					31						
					32						
	<u></u>				33						
					34		1				
					35						
					36						
					37		1				
					38						
					39						
					40						

S	C	7 1	THE						BORINGWELL	, ID:	
envín	onmer	ital	Sot	JRO	CE (3 R	oup, Inc.		5	SB-13	
PROJE							l Foundry		Project No.	01-ABI-001	
BORIN					·-		Gallon USTs		Logged By:	Nathan Coll	on on
CONTR		_	•		T:		nex Geoprobe		Loggod Oy.	1.1007071 0011	
SAMPL							linuous DW	MONITORING DEVICE:	MiniRae 2000		
START	_					1	/2007 11:20	FINISH DATE/ TIME	11/1/2007 (2.00	2	
FIRST						22.5		STABILIZED WATER LEVEL		_	
SURFA								CASING TOP ELEVATION:			
TOTAL				:		25'		BORING DIAMETER/DEPTH:	3 1/4" / 25'		
	\Box										<u>ج</u>
Date/Time	Sample Interval	PID (ppm)	Recovery	Stratigraphy	Depth (feat)	Water-fevel		LITHOLOGIC DESCRIPTI n, color, moisture, density, grain ES ARE APPROXIMATE UNLE	size/plasticity, of		Well construction details
				14	1		Cement debris				+
			-		2	-					
1					_						
	\supset				3	\vdash	Sandy gravel (asphalt), dry	y, podrty sarted, no odor			
ĺ											_
					4		Clay (CL), black, moist, sti	ff, medium pasticity, no odor			
					5	ŀ					-
							NR				
					6						
									-		
					7						
	\vdash				8	-	Clay (C() black moves est	ff, medium pasticity, no odor			
					ů		Ciby (CE), Discx, Moist, 30	ii, iiigaloiii pasticity, no ocoi			
					9	 	1				
	$\geq \leq$	δ									
					10						
	<u> </u>	20			31	+	1				
					('	1					
					12		Clay (Ct.) occasich army	suff, medium pastloty, petroleum	odor.		
						<u> </u>	Ciay (Cc), greensingray, s	sin, mediam pasacity, pendiaun	1 000)		
					13						
	<u> </u>				14	-	1				
	\bowtie	500			, ,						
					15		1				
						<u> </u>					
					16		Same as above but softer,	more moist			
					17		-				
					''						
					18		1				
]	ت بدي يوني	4 .		
					19		Clay (CL), greenish gray, s	stiff, medium pasticity, petroleun	odor		
					20	1	-				
		155									

	ABI-001 than Colton
BORING LOCATION (AT SITE): 550 Gallon USTS Logged By: NE CONTRACTOR AND EQUIPMENT: Vironex Geoprobe SAMPLING METHOD: Continuous DW MONITORING DEVICE: MiniRae 2000 START DATE/ [TIME): 11/1/2007 11:20 FINISH DATE/ TIME 11/1/2007 12:00 FIRST WATER (BGS): 22.5' STABILIZED WATER LEVEL: SURFACE ELEVATION: CASING TOP ELEVATION: TOTAL BORING DEPTH(S): 25' BORING DIAMETER/DEPTH: 3 1/4" / 25'	
BORING LOCATION (AT SITE): 550 Gallon USTS Logged By: NE CONTRACTOR AND EQUIPMENT: Vironex Geoprobe SAMPLING METHOD: Continuous DW MONITORING DEVICE: MiniRae 2000 START DATE/ [TIME): 11/1/2007 11:20 FINISH DATE/ TIME 11/1/2007 12:00 FIRST WATER (BGS): 22.5' STABILIZED WATER LEVEL: SURFACE ELEVATION: CASING TOP ELEVATION: TOTAL BORING DEPTH(S): 25' BORING DIAMETER/DEPTH: 3 1/4" / 25'	than Colton
CONTRACTOR AND EQUIPMENT: Vironex Geoprobe SAMPLING METHOD: Continuous DW MONITORING DEVICE: MiniRae 2000 START DATE/ [TIME): 11/1/2007 11:20 FINISH DATE/ TIME 11/1/2007 12:00 FIRST WATER (BGS): 22.5' STABILIZED WATER LEVEL: SURFACE ELEVATION: CASING TOP ELEVATION: TOTAL BORING DEPTH(S): 25' BORING DIAMETER/DEPTH: 3 1/4" / 25'	
START DATE/ [TIME): 11/1/2007 11:20 FINISH DATE/ TIME 11/1/2007 12:00 FIRST WATER (BGS): 22.5' STABILIZED WATER LEVEL: SURFACE ELEVATION: CASING TOP ELEVATION: TOTAL BORING DEPTH(S): 25' BORING DIAMETER/DEPTH: 3 1/4" / 25'	
FIRST WATER (BGS): SURFACE ELEVATION: TOTAL BORING DEPTH(S): 22.5' STABILIZED WATER LEVEL: CASING TOP ELEVATION: BORING DIAMETER/DEPTH: 3 1/4" / 25'	
SURFACE ELEVATION: TOTAL BORING DEPTH(S): 25' BORING DIAMETER/DEPTH: 3 1/4" / 25'	
TOTAL BORING DEPTH(S): 25' BORING DIAMETER/DEPTH: 3 1/4" / 25'	
TITUOLOGIC DESCRIPTION	
LITHOLOGIC DESCRIPTION Part Part	
San Dep Dep Wath	Well construction
20	
21	
Silty clay (CL), dark greenish gray, wet, soft low plasticity, faint petroleum odor	
Clay (CL), medium brown, moist, stiff, no odor 25 Bottom of Boring 25'	
Note: PID reading 60 ppm at 25' but soil looks clean. Water from upper levels had into the lower soil sample. Possible cross contamination.	is drained
27	
29	
30	
31	
32	
33	
34	
36	
37	
38	
39	
40	

										_	
S	G		THE		_	_	_		BORINGWELL	.ID:	
enviro	птел	tal	<u> 50</u> 1	UR	CE	GR	OUP, INC.		5	SB-14	
PROJE	CT NA	ME AN	D AD	DRES	ss:	AB&	Foundry		Project No.	01-ABI-001	
BORING	LOC	ATION	(AT S	ITE]:		550-	galion USTs		Logged By:	Nathan Colto	n
CONTR	ACTO	R AND	EQUI	PME	NT:	Viror	nex Geoprobe		1000		
SAMPL	ING M	ETHO	<u>):</u>			Cont	inuous dw	MONITORING DEVICE:	MiniRae 2000		
START	DATE	(TIME):			11/1/	72007 12:50	FINISH DATE/ TIME	11/1/2007 13:40)	
FIRST V	VATE	REGS):			10.5		STABILIZED WATER LEVEL:			
SURFA	CE EL	EVATI	ON:					CASING TOP ELEVATION:			
TOTAL	BORII	IG DEI	РТН(З):		15'		BORING DIAMETER/DEPTH:	3 1/4" /15'		
Date/Time	Sample Interval	PID (ppm)	Recovery	Stratigraphy	Depth (feet)	Water-level	(dassification	LITHOLOGIC DESCRIPTION, COLOR, MOISTURE, DESCRIPTION, COLOR, MOISTURE, DESCRIPTION DESCRIPTION DE L'ACCEPTION D	size/plasticity, ot	her) : STATED	Well construction details
			-		1		Concrete debris.				1
	$\overline{\mathbf{x}}$		_		2		Sandy clay (fill), coarse gra	sined, black, moist, poorly sorted	l, no odor.		1
					3						
					4						
					5		No recovery				
					6		,				
					8						
				8983	9		(24// 24// 24// 24/			_
	X		_		10		Gravelly day (CL), dark bro	own, wet, soft, 3/4" subangular, r			-
					11						
					12		No recovery				
	_				13	-					
	$\overline{\mathbf{x}}$				14		Sandy gravel (SP), very da	irk gray 1/4" lo 3/4", subangular.	wet, loose, no o	dor	
					15			Battom of Boring 18'			
					18						
					17						
					18	_					
					20	-					
l		l			l	1				•	

		1	THE						BORING/WELL	ID:	
envir	onmen			UR	CE (GR	OUP, INC.		5	SB-15	
PROJE						1	I Foundry		Project No.	01-ABI-001	
BORIN						_	Gallon USTs		Logged By:	Nathan Colto	
CONTR					NT:	1	nex Geoprobe		Loggeo by:	madia, Solice	·
SAMPL		_					inuaus dw	MONITORING DEVICE:	MiniRae 2000		
START						-	/2007 13:42	FINISH DATE/ TIME	11/1/2007 14-30		
FIRST	_					5.5'	<u></u>	STABILIZED WATER LEVEL:			
SURFA								CASING TOP ELEVATION:			
TOTAL):		19'		BORING DIAMETER/DEPTH:	3 1/4" / 19'		
									,	-	٦
Date/Time	Sample Interval	PID (ppm)	Recovery	Strattgraphy	Depth (feet)	Water-level		LITHOLOGIC DESCRIPTION, color, moisture, density, grain ENTAGES ARE APPROXIMAT	size/plasticity, ot		Well construction details
				-	1		Concrete debris.				-
	\bowtie				2		Silty sand (SM), fine graine subangular, no odor.	ed, Very dark brown, moist, well s	sorted, some gra	vel particles 1/2"	
					3		Substigular, 110 0001.				
		û			4						
					5						1
	\vdash				8		Gravelly sand (SP), fine gr	ained, black, 1/2" subangular, w	et, poorly sorted,	no odor.	
					7	<u> </u>	Clay (CL), dark gray, moist	medium plasticity, no odor.			1
					8						
					9						
		٥			10						
					11	 	Clay (CL), greenish gray, r	noist, stiff, medium plasticity, fai	nt petroleum odo	r.	
		,			12		Silty clay (CL) with some g	ravel, greenish gray, moist, soft	er, petroleum oda	or.	
					13						
	$\overline{\mathbb{Z}}$	1200	3	11000	14		Sandy clay (SC), fine sand	, moist, well sorier, petroleum o	dor stranger.		
					15		Clay (CL), greenish gray, s	tiff, moist, medium plasticity, pe	iroleum odor.		
					16						
					17						
	\boxtimes	40			18	70.00	Same as above but no ode				
					19		Refusal at 19' bgs, Bottom	of Boring at 19'			
					20						

		1	THE						BORINGWELL	IĎ,	-
envir	onmen	(a)	Sol	J R	CE (ìR	oup, Inc.		s	B-16	
PROJE	CT NA	ME AN	D AD(DRES	S:	A88	l Foundry		Project No.	01-ABI-001	
BORING	G LOC	ATION	(AT S	ITE):		Park	ing Lot		Logged By:	Nathan Collor	1
CONTR	ACTO	R AND	EQUI	PME	NT:	Viror	nex Geoprobe				
SAMPL	ING M	ETHO) :			Mars	ocere	MONITORING DEVICE:	MiniRae 2000		
START	DATE	(TIME):			11/1/	/2007 14 45	FINISH DATE/ TIME	11/1/2007 15 30		
FIRST	NATER	₹(BGS) :				·	STABILIZED WATER LEVEL:	10'		
SURFA	CE EL	EVATION	ON:			ļ		CASING TOP ELEVATION:			
TOTAL	BORIL	IG DEI	ZJHT):		50,		BORING DIAMETER/DEPTH:	20'		
Date/Time	Sample Interval	PJD (ppm)	Recovery	Stratigraphy	Depth (feat)	Water-feve)	(classification ALL PERCENTAGI	LITHOLOGIC DESCRIPTION, color, moisture, density, grain ES ARE APPROXIMATE UNLES	size/plasticity, oth	er) STATED	Well construction details
					1	-	Asphall				
					2		Gravelly sand (SM), black,	1/2" subangular, dıy.			
					3		Clay (CL), some gravel, bia	ack, moist, soft, medium plasticit	y, no odor		
					4	 					
					5		Clay, black, moist, wood of	nips, tight, medium plasticity, no	odor		
					6	-					
					7						
					8						
	_				9						
					10						
					11	 -					
					12						
					13						
					14		Ctay (CL), light brownish gr	ray (10YR 6/2), moist, soft, high	plasticily, no odor	r	
					15				-		
					16						
					17						
					18		Clay (CL), grayish brown (1	(YR 5/2) moist, soft, high plasti	city, no odor.		
					19						
					20	-		Battom of Boring 20'		_	1

PROJECT NAME AND ADDRESS: A8&) Foundry Project No. 01-ABI-001 BORING LOCATION AT SITE): Parking Lat Logged By: Nathan Colton CONTRACTOR AND EQUIPMENT: Vironex Geoprobe SAMPLING METHOD: Marcocere MONITORING DEVICE: MiniRae 2000 START DATE/ (TIME): 11/1/2007 1515 FINISH DATE/ TIME 11/1/2007 1600 FIRST WATER (BGS): 15.5' STABILIZED WATER LEVEL: 9' SURFACE ELEVATION: CASING TOP ELEVATION: TOTAL BORING DEPTH(S): 20' BORING DIAMETER/DEPTH: 20'				THE						BORINGWELL	. ID	
BORNIG LOCATION AT SITE): Perking Let CONTRACTOR AND REQUIPMENT: Vironex Geoprobe Mancocre Monitroning DEVICE: Minina 2000 START DATE (TIME): 11/1/2007 1515 FINISH DATE (TIME): 15.5' STABILIZED WATER LEVEL. 9' CASING TOP ELEVATION: COASING TOP ELEVATION: TOTAL BORING DEPTH(S): 20' BORING DIAMETER/DEPTH: 20' LITHOLOGIC DESCRIPTION (Idassification, color, missiure, density, grain size/plasticity, other) ALL PERCENTAGES ARE APPROXIMATE UNLESS OTHERWISE STATED 1 Concrete debris. 2 Clay (CL), with some gravel, black, moist, stiff, no odor. 10 11 Clay (CL), light grayish brown, moist, tight, no odor. 12 13 Clay (CL), light grayish brown, moist, tight, no odor. 12 Cravel (GM), very dark gray, wet, subengular, 1/4", no odoc. 15 Gravel (GM), very dark gray, wet, subengular, 1/4", no odoc.	envire	onmer	ital	Sou	JR	CE (R	OUP, INC.		S	SB-17	
CONTRACTOR AND EQUIPMENT: SAMPLING METHOD: Marcocere MONITORING DEVICE: MINITAGE 2000 START DATE (TIME): 11/1/2007 1515 FINISH DATE TIME 11/1/2007 1600 FIRST WATER (BGS): SURFACE ELEVATION: COASING TOP ELEVATION: TOTAL BORING DEPTH(S): 20' BORING DIAMETER/DEPTH: Clay (GL), with some gravel. black. moist. stiff, no odor. 11 Concrete debria. Clay (CL), with some gravel. 5 Clay (CL), with some gravel. 11 Clay (CL), light graysh brown, moist. light, no odor. 12 13 Clay (CL), light graysh brown, moist. light, no odor. 14 Clay (CL), same as above but softer. Cravel (GM), very dark gray, wet, subengular, 1/4", no odor.	PROJE	CT NA	ME AN	O ADD	RES	S:	A8&	Foundry		Project No.	01-ABI-001	
SAMPLING METHOD: Marcocore MONITORING DEVICE: MiniRas 2000	BORING	G LOC	ATION	AT SI	TE):		Park	ing. Lat		Logged By:	Nathan Colto	n
START DATE/ (TIME):	CONTR	ACTO	R AND	EQUIP	MEN	ΙΤ;	√ігог	nek Geoprobe				
FIRST WATER (BOS): SURFACE ELEVATION: CASING TOP ELEVATION: TOTAL BORING DEPTH(S): 20' BORING DEPTH(S): Casing Top Elevation: Casing Top Elevation: Inthologic Description (classification, color, maisture, density, grain size/plasticity, other) ALL PERCENTAGES ARE APPROXIMATE UNLESS OTHERWISE STATED Concrete debris. Clay (CL), with some gravet, black, moist, stiff, no odor Same as above with no gravet. Clay (CL), light grayish brown, moist, tight, no odor. 11 Clay (CL), light grayish brown, moist, tight, no odor. 12 13 Clay (CL), same as above bull softer. Clay (CL), same as above bull softer. Cravel (GM), very dark gray, wet, subangular, 1/4", no odor.	SAMPL	ING M	ETHO	<u>):</u>			Marc	оселе	MONITORING DEVICE:	MiniRae 2000		
SURFACE ELEVATION: TOTAL BORING DEPTH(S): 20' BORING DIAMETER/DEPTH: 20' LITHOLOGIC DESCRIPTION (classification, color, maisture, density, gram size/plasticity, other) ALL PERCENTAGES ARE APPROXIMATE UNLESS OTHERWISE STATED Clay (CL), with some gravel, black, moist, stiff, no odor Clay (CL), with no gravel. Same as above with no gravel. Clay (CL), light grayish brown, moist, light, no odor. Clay (CL), same as above but softer. Clay (CM), very dark gray, wet, subangular, 1/4", no odor.	START	DATE	(TIME	i):			1 1/1/	2007 1515	FINISH DATEJ TIME	11/1/2007 1600	0	
TOTAL BORING DEPTH(S): 20' BORING DIAMETER/DEPTH: 20' LITHOLOGIC DESCRIPTION (classification, color, maisture, density, grain szer/plasticity, other) ALL PERCENTAGES ARE APPROXIMATE UNLESS OTHERWISE STATED 1 Concrete debris. 2 Clay (CL), with some gravel, black, moist, stiff, no odor 3 Same as above with no gravel. 5 6 7 7 8 8 9 9 10 Clay (CL), light grayish brown, moist, tight, no odor. 12 Clay (CL), same as above but softer. Clay (CL), same as above but softer. 15 V Gravel (GM), very dark gray, wet, subangular, 1/4", no odor.	FIRST	VATE	₹ (BGS):			15.5		STABILIZED WATER LEVEL:	ð.		
UITHOLOGIC DESCRIPTION (classification, color, maisture, density, grain size/plasticity, other) ALL PERCENTAGES ARE APPROXIMATE UNLESS OTHERWISE STATED 1	SURFA	CE EL	EVÀTI	ON:					CASING TOP ELEVATION:			
Clay (CL), with some gravel, black, moist, stiff, no odor Clay (CL), with some gravel, black, moist, stiff, no odor Same as above with no gravel. Same as above with no gravel. Clay (CL), light grayish brown, moist, tight, no odor. Clay (CL), same as above but softer. Clay (CL), same as above but softer. Gravel (GM), very dark gray, wet, subangular, 1/4", no odor.	TOTAL	BORI	IG DE	PTH(S)	:		20'		BORING DIAMETER/DEPTH:	20'		
Clay (CL), with some gravel, black, moist, stiff, no odos Clay (CL), with some gravel, black, moist, stiff, no odos Clay (CL), with some gravel, black, moist, stiff, no odos Clay (CL), light gravel, moist, stiff, no odos. Clay (CL), light gravish brown, moist, stiff, no odos. Clay (CL), light gravish brown, moist, stiff, no odos. Clay (CL), same as above but softer.	Date/Time	Sample Interval	PID (ppm)	Recovery	Stratigraphy		Water-fevel	(classification ALL PERCENTAGE	n, color, moisture, density, gram	size/plasticity, ot	iher) ESTATED	Well construction details
Same as above with no gravel. Same as above with no gravel.							<u> </u>	Concrete debris.				1
Same as above with no gravel. 5 6 7 8 9 10 11 Clay (CL), light grayish brown, moist, tight, no odor. 12 13 14 Clay (CL), same as above but softer. Gravel (GM), very dark gray, wet, subangular, 1/4", no odor.								Clay (CL), with some grave	el, black, moist, stiff, no odor			_
5 6 7 8 9 10 Clay (CL), light grayish brown, moist, tight, no odor. 12 13 14 Clay (CL), same as above but softer. 15 V Gravel (GM), very dark gray, wet, subengular, 1/4°, no odor.								Same as above with no gra	avel.			
7 8 10 Clay (CL), light grayish brown, moist, tight, no odor. 12 13 14 Clay (CL), same as above but softer. Clay (CL), same as above but softer. Gravel (GM), very dark gray, wet, subangular, 1/4", no odor.	-					5						
8 9 10 Clay (CL), light grayish brown, moist, tight, no edoc. 12 13 Clay (CL), same as above but softer. Gravel (GM), very dark gray, wet, subangular, 1/4", no edoc.						6						
11 Clay (CL), light grayish brown, moist, tight, no odor. 12 13 14 Clay (CL), same as above but softer. 15 V Gravet (GM), very dark gray, wet, subangular, 1/4", no odor.						7						
10 11 Clay (CL), light grayish brown, moist, tight, no odor. 12 13 Clay (CL), same as above but softer. Clay (CL), same as above but softer. Gravel (GM), very dark gray, wet, subangular, 1/4", no odor.						8						
Clay (CL), light grayish brown, moist, tight, no odor. 12 Clay (CL), same as above buit softer. Clay (CL), same as above buit softer. Gravel (GM), very dark gray, wet, subangular, 1/4", no odor.												
Clay (CL), same as above buit softer. 15 Gravel (GM), very dark gray, wet, subangular, 1/4", no odor. 17								Clay (CL), light grayish bro	wn, maist, tighl, no odar.			
Clay (CL), same as above but softer. 15 Gravel (GM), very dark gray, wet, subangular, 1/4", no odor. 17						12						
Gravel (GM), very dark gray, wet, subangular, 1/4", no odor.												
Gravel (GM), very dark gray, wet, subangular, 1/4", no odor.								Clay (CL), same as above	but softer.			
								Gravel (GM), very dark gra	iy, wet, subangular, 1/4", no odo.	t.		
18 Clay (CL), light to medium gray, moist, stiff, medium plasticity, no odor.						17	<u> </u>					
						18		Clay (CL), light to medium	gray, moisl, stiff, medium plastic	city, no odor.		†
19												
20 Bottom of Boring 20'						20			Battom of Boring 20			

		1 1	HE						BORINGWELL	. ID·	
enviro	nmen	tal	Sol	UR	CE (GR	OUP, INC.		8	SB-18	
PROJEC	T NA						l Foundry		Project No.	01-ABI-001	
BORING	LOCA	ATION	(AT S	łΤE):		Parki	ing Lot		Logged By:	Nathan Colto	n
CONTRA	ACTO	RAND	EQUI	PME	NT:		nex Geoprobe		,		
SAMPLI	NG M	THO):			Macr	о	MONITORING DEVICE:	MiniRae 2000		
START	DATE/	(TIME):			11/5/	/2007 12:45	FINISH DATE! TIME	11/5/2007 13:45	5	
FIRST W	VATER	(BGS):					STABILIZED WATER LEVEL	:		
SURFAC	CE ELI	EVATION	:NC					CASING TOP ELEVATION:			
TOTAL	BORIN	IG DES	TH(S	5):		20 [.]		BORING DIAMETER/DEPTH	: 2" 20'		
Date/Time	Sample Interval	PID (ppm)	Recovery	Stratigraphy	Depth (feet)	Water-level	(classification	LITHOLOGIC DESCRIPTION, color, moisture, density, grain	size/plasticity, ot	her) E STATED	Well construction details
					1		Asphalt debris.				
					2		Gravelly clay (SM) with sor	ne sand, grayish brown, soft/cn	umbly, no odor.		
					3						
					4		Clay (CL), dark brown, moi	st, stiff, medium plasticity, no o	dor.		
					5						
					6						
					7						
					8						
					9						
					10						
					11		Clay (CL), olive brown, mo	ist, soft, medium plasticity, no c	odor		
					12						
					13						
					14	▼	clay with some sand				
					15 16		Same as above with grave brown.	l 1/4" subangular and sand, me	edium grained, we	et, no odor, olive	
					17		SIOTH.				
					18	_					
					19	_					
					20	_					-

Page 1 of 1

C		1	HE						BORINGWELL	. ID:	
anviro	ormen		So	UR	CE	Gr	OUP, INC.		8	SB-19	
PROJE							Foundry		Project No.	01-ABI-001	
BORING							ing Lot		Logged By:	Nathan Colto	n
CONTR	ACTO	R AND	EQU	IPME	NT:		эех Geoprobe			•	
SAMPL	ING M	ETHO) :			Macı	0	MONITORING DEVICE:	MiniRae 2000		
START	DATE	/ (TIME	i):			11/5/	/2007 10:30	FINISH DATE/ TIME	11/5/2007 11:11	5	
FIRST	WATER	R (BGS) :			17.5		STABILIZED WATER LEVEL:			
SURFA	CE EL	EVATION	ON:					CASING TOP ELEVATION:			
TOTAL	BORIN	IG DE	PTH(S	<u>}</u> ;	_	20'	_	BORING DIAMETER/DEPTH:	2" 20		
Date/Time	Sample Interval	PID (ppm)	Recovery	Stratigraphy	Depth (feel)	Water-leve)		LITHOLOGIC DESCRIPTION. COLOR, MOISTURE, DESCRIPTION. COLOR, MOISTURE, DESCRIPTION DE L'ALLES	size/plasticity, ot		Well construction details
			_		1	<u> </u>	Cement debris.				1
					2	 	Gravelly clay (asphalt), dry	, lose, no odor.			-
					3	_					
			_		4						
					5	-					
					6	-	Clay (CL), very dark gray, s	naist, stiff, no odor.			-
					7						
			-		8	-					
					9						
	ļ		-		10						1
		0.5			11						
		0.0			12						
					13		Gravelly clay (GC), dark gr odor.	ay, almost black, with light gray	streaks, moist, p	oarly sorted, no	
					14		Clay (CL), medium gray, m	oist, stiff, medium plasticity, no	odor.		
					15		No recovery.				<u> </u>
					16		Silty day (CL), dark grav. v	vel, some gravel, soft, no odor			
					17	▼	, , , , , , , , , , , ,				
					18						
					19		Clay (CL), medium brown.	moist, stiff, medium plasticity, or	o ador.		
					20	\Box		Battom of Baring 20°	_		1
				_							

C		1	THE						BORINGWELL	. ID.	
nivne	namno	ital	So	UR	CE (GR	OUP, INC.		5	B-20	
PROJE						_	l Foundry		Project No.	01-ABL001	
_	G LOC					$\overline{}$	ing Lat		Logged By:	Nathan Collor	<u> </u>
	ACTO						nex Geoprobe				
	ING M					Mac		MONITORING DEVICE:	MinIRae 2000		
	DATE					_	/2007 12:00	FINISH DATE/ TIME	11/5/2007 13:0	<u> </u>	
	WATER							STABILIZED WATER LEVEL:			
	CE EL							CASING TOP ELEVATION:			
	BORIN			3);		20.		BORING DIAMETER/DEPTH:	2" 20'		
									,		۲
Da(e/Time	Sample Interval	PiD (ppm)	Recovery	Stratigraphy	Depth (feet)	Water-fevel	(classification	LITHOLOGIC DESCRIPTION, color, moisture, density, grain ES ARE APPROXIMATE UNLE	size/plasticity, of	her) E STATED	Well construction
	-				1	_	Asphalt debrts,				-
				888	ž	\vdash		ie sand, dark brown, moist, stiff,	medium plasticit	y, no odor.	-
					3	├-					
			ļ		4	_	_				
					ì	1					
					5		Clay (CL), dark gray (bnck	pieces red), majst, stiff, medium	plasticity, no od	or.	1
					6		1				
					7		-				
					8		-				
					9	-	- Same as above, no brick p	sieces.			
					10		-				
					11		_				
					12		1				
					13		Cłay (CL), olive brown, mo	oist, soft, medium plasticity, no o	dor.		
		_	 		14		1				
	+		-		15	+	-				
					16		More moist, almost wet.				
					17		1				
			+-		18	1	1				
			\vdash		19	-	Gravelly day (GC), olive t	prown, moist, stiff, medium plast	icity, no odor.		
	┼─	_	+	2000	20	+		Bottom of Boring 20'			4
	1		1		1						

S	G		LHE						BORING/WELL				
envir	onmer	tal (Soi	UR	CE (GR	oup, Inc.		S	B-21			
PROJE	CT NA	ME AN	ID ADI	DRES	S:	AB&	l Foundry		Project No.	01-ABI-001			
BORIN						-	ing Lot		Logged By:	Nathan Colto	on		
	ACTO				 ≀Υ:	$\overline{}$	nex Geoprobe						
SAMPL						Macr		MONITORING DEVICE:	MiniRae 2000				
TART	DATE	/ (TIME	 E):				/2007 11:30	FINISH DATE/ TIME	11/5/2007 0:00				
	WATER							STABILIZED WATER LEVEL					
URFA	CE EL	EVATI	ON:					CASING TOP ELEVATION:					
OTAL	BORIN	NG DE	PTH(\$):		20'		BORING DIAMETER/DEPTH:	2" / 20'				
Date/Ті⊓е	Sample interval PID (ppm) Recovery Stratigraphy					Water-level		LITHOLOGIC DESCRIPTI n, color, moisture, density, grain SES ARE APPROXIMATE UNLE	size/plasticity, ot		Well construction		
					1		Asphalt debris.	chalt debris.					
			 		2		Silty clay (CL), olive brown	n, dry.					
					3								
					4		Gravelly clay (GC), dark g	ray, 1/4", subangular, loose, moi	st, no odor				
				3888	5		Red rock (brick pieces), d	y		_	$\frac{1}{2}$		
					7						+		
			<u> </u>		8								
			<u> </u>		9	<u> </u>	Clay (CL), olive brown, mo	oist, stiff, medium plasticity, no o	dor.				
					10								
					11								
					12		-						
					13	+	1						
					14								
					15								
					16								
		_			17								
			ļ		19	-							
					20			Bottom of Boring 20'			4		

		<u> </u>	THE		_			_	BORING/WELL	. ID			
eovir	G			JRI	CE (3R	OUP, INC.		5	SB-22			
PROJE						_	Foundry		Project No.	01~ABI-001			
BORING						1	Digal TRA VST		Logged By:	Nathan Colle	מע		
CONTR					PT;	1	nex Geoprobe						
SAMPL							กับเดาร	MONITORING DEVICE:	MiniRae 2000				
START	DATE	(TIME	:):			11/2	07 745	FINISH DATE/TIME	11/2/07 645				
FIRST	VATER	R (BGS]:			ð.	-	STABILIZED WATER LEVEL:					
SURFA	CE EL	EVATION	ON:					CASING TOP ELEVATION:					
TOTAL	BORIN	IG DEF	PTH(S));		15'		BORING DIAMETER/DEPTH:	3 1/4" 15"	_			
Date/Time	Sample Interval PID (ppm) Recovery Stratigraphy					Water-level	(classification	LITHOLOGIC DESCRIPTION, color, moisture, density, grain ES ARE APPROXIMATE UNLES	size/plasticity, of	ስድ) E STATED	Well construction details		
		1 Cement debris.									+		
	\times				2		Clay (CL), very dark gray, r	y (CL), very dark gray, molst, medium plasticity, no odor					
					4		Sándy silt (ML), fine graine	ndy silt (ML), fine grained black, moist, loose, well sorted.					
	\simeq				5						+		
					6		NR						
					7		Gravelly day (GC), dark go	ay, moist, 1/2" to 3/4" subangula		no odor.			
					8			-	·				
	X	130			10		Gravelly clay (GC) with sor	ne medium grained sand, dark b	oluish gray, wel.	pooily sorted,			
	_	48			11	<u> </u>	slight oily sheen, no odor.	•		,			
		1.9			12		Gravelly sand, dark gray, w	vet, poorly sorted, no odor.					
	H Y				13		Clay (CL), light brownish as	ray, moist very soft, medium pla	sticity, no odor.				
	\boxtimes	0.7			14		, , , , , , , , , , , , , , , , , , ,	Bottom of Boring 16'			_		
					16			ឧបយោ ថា ឧបាពេទ្ធ វិទ					
					17								
					18								
					19								
					20								

		T 1	THE						BORINGWELL	ID;			
onivae	nman				CE (GR	OUP, INC,		S	B-23			
PROJE						1	l Foundry		Project No.	01-ABI-001			
BORING						_	D gal TRA VST		Logged By:	Nathan Colto	п		
CONTR						_	nex Geoprobe						
SAMPL							ทบอนร DW	MONITORING DEVICE:	MiniRae 2000				
START	DATE	/ (TIME	<u>():</u>			1	/2007 905	FINISH DATE/ TIME	11/2/2007 0:00				
FIRST	VATER	R (BGS	i):			8.5		STABILIZED WATER LEVEL:					
SURFA	_							CASING TOP ELEVATION:					
TOTAL	BORIN	4G DEI	PTH(S	5]:		15'		BORING DIAMETER/DEPTH:	3 1/4" 15'	_			
Date/Time	Sample Interval PID (ppm) Recovery Stratigraphy					Water-level		LITHOLOGIC DESCRIPTION, color, moisture, density, grain ES ARE APPROXIMATE UNLE	size/plasticity, of		Well construction details		
)				1		Cement debris.				-		
	-	0.1	-		2			moist, medium plasticity, no odo	r.		+		
	\times				3								
		۵,1			4		Sandy silt (ML), fine grains	silt (ML), fine grained, black, moist, loose, no odor.					
				<u>Ш</u> ШШ 	5		-				1		
				-	6	_	NR						
					7								
		0.4			8		Gravelly clay (GC), very da	ark gray, moist, poorly sorted, no	odor.				
	\times	0.3			9		Gravelly sand (SP), very d	ark gray, medium grained, poorl	y sorted, no odor	, wel.			
					10								
					11		Gravelly clay (GC), dark gr						
					12		Clay (Ct.), blive brownish o	gray, moist, stiff, medium plastic	ty, no odor.				
					13								
	\boxtimes	04			14			0.000					
					15			Bottom of Boring 15					
		_			16								
					18								
				_	19								
				_	20								
					20								

	7	1	THE				_		BORINGWELL	ID.	
envire	onmen	(8)	Soi	UR	CE (GR	OUP, INC.		8	SB-24	
PROJE	CTNA	ME AN	ID ADI	DRES	SS:	ABA	l Foundry		Project No.	01-ABI-001	
BORING	G LOC	ATION	AT S	ITE):		$\overline{}$	gal TRA VST		Logged By:	Nathan Collor	n
CONTR	ACTO	R AND	EQUI	PME	NT:	$\overline{}$	nex Geoprobe			•	
SAMPL	ING M	ETHO):			Cont	inuous	MONITORING DEVICE:	MiniRae 2000		
START	DATE	(TIME	:);			11/2	2007 1000	FINISH DATE/ TIME	11/2/2007 1100	3	
FIRST	NATER	R (BGS	s):			7.5		STABILIZED WATER LEVEL:			
SURFA	CE EL	EVATI	ON:					CASING TOP ELEVATION:			
TOTAL	BORIN	G DE	PTH(S) ;		20		BORING DIAMETER/DEPTH:	3 1/4" / 20'		
Date/Time	Sample Interval	PID (ppm)	Recovery	Stretigraphy	O Depth (feet)	Water-fevel	(classification ALL PERCENTAGI	LITHOLOGIC DESCRIPTION D. COTOR, MOISTURE, DENSITY, GRAIN ES ARE APPROXIMATE UNLES	size/plasticity, of	her) E STATED	Well construction details
					1		Cement debris				
					2		Clay (CL), very dark gray, r	noist, sorted, medium plasticity,	no adar.]
	\boxtimes				3		Sendy silt (ML), fine graine	d, dark gray, crumbly, most, no	odor.		
	\propto				4						<u> </u>
					5		NR				
					7		Sandy silt (ML), some grav	el, dark gray, moist, no odor.			
				***	8		Gravel (GC), brown to dark	gray, wet, to 3/4" to 1" subangu	lar, poody sorter	d, no odor.	
					9	_	Silty day (CL) bluish gray	moist, medium stiffness, mediu	m olasticity, no o	ndor.	│
	\geq				10	_	only day (bey bloom gray,		,		
		200			11		Clay (C) I bluich arry mai	st, stiff, medium plasticity, no od	lor		
		0.6			12		Cost, ordan gray, mor	or, our, moreum producty, no ou			
					13						
	\times	0.3			14						
					15		Gravel (GC), dark gray, we	ર 3/4" to 1" subangular, poorly s	sorted, no odor.		
					15	_					
					17						
					19	_	Clay (CL), dark olive brown	n, moist, still, medium plasticity,	no odor.		
		0.3			20			Bottom of Boring 20'			
	\boxtimes	0.3									

		1	THE						BORINGAVELL	ID.			
anviro	namen	la)	Soi	URC	CE (GR	OUP, INC.		9	B-25			
PROJEC							l Foundry	_	Project No.	D1-A8I-001			
BORING						1	uction Area		Logged By:	Nathan Colto	71		
CONTR					iT:	_	nex Geoprobe		Coggoo Ly.	110			
SAMPLI					-	Macr		MONITORING DEVICE:	MiniRae 2000				
START						1 -	/2007 1040	FINISH DATE/ TIME	11/2/2007 1110	<u> </u>			
FIRST V						8.5	1010	STABILIZED WATER LEVEL!					
SURFAC						10.0		CASING TOP ELEVATION:					
TOTAL				٠		10'		BORING DIAMETER/DEPTH:	2" 10"				
			111,0,	ΪΠ		-		DOMINO BRANCIE (BREAT THE	12 .0		Τç		
Date/Time	Sample Interval	PID (ppm)	Recovery	Stratigraphy	Oepth (feel)	Water-levet		LITHOLOGIC DESCRIPTION, color, maisture, density, grain ES ARE APPROXIMATE UNLES	size/plasticity, of		Well construction details		
					0								
					2		Cement debris.	nd (SM), coarse, light brown, moist, no odor.					
							,	hay (CL), black, moist, stiff, no odor.					
ı					3		NR	R					
				מנונוני									
					5		Clay (CL), some gravel, da	irk gray, moist, stiff, no odor.					
					8								
					7	_							
					8			and, grained, 1/4" to 1/2" suban	gular, dark gray,	wet poorly	+		
					9		sorted, ratten egg odor.						
					10			Bottom of Boring 10'					
					11								
					12								
				П	13		1						
					14		1						
				Н	15						1		
				Н	16		1						
				Н	17		1						
				\vdash	18	\vdash	1						
					19		1						
						1							

C		1	THE		_			_	BORINGWELL	. ID:		
envin	onmen			UR	CE (GR	OUP, INC.		5	B-26		
PROJE	CT NAI	VE AN	D ADD	RES	S:	A88	l Foundry		Project No.	01-ABI-001		
BORING	3 LOC	ATION	(AT S	ITE):			tuction Area		Logged By:	Nathan Colto	n	
CONTR	ACTO	R AND	EQUI	PMEN	IT:	Viro	nex Geoprobe			•		
SAMPL	ING MI	THOE);			Mac	70	MONITORING DEVICE:	MiniRae 2000			
START	DATE/	(TIME):	_		11/2	/2007 11315	FINISH DATE/ TIME	11/2/2007 1200)		
FIRST V	MATER	(BGS) :			13'		STABILIZED WATER LEVEL:				
SURFA								CASING TOP ELEVATION:				
TOTAL	BORIN	G DEF	TH(S):		15'		BORING DIAMETER/DEPTH:	2" 15'		_	
Date/Time	Sample Interval	P{D (ppm)	Recovery	Stretigraphy	Depth (feet)	Water-level		LITHOLOGIC DESCRIPTION, color, moisture, density, grain ES ARE APPROXIMATE UNLES	size/plasticity, ot		Well construction details	
					1		Cement debris			-		
					2		Sill (ML), dark brown, mois		+			
			0	W. C.	3		Gravelly sand (SP) with a very sticky black substance (tar?), moist, faint hydrocarbon odor.					
	\times	16			4		Gravelly sand (SP) with a very sticky black substance (tar?), moist, faint hydrocarbon odor. Clay (CL), dark brown, moist, stiff, medium plasticity, no odor.					
					5		,, (),,	out out, modern process, in ou				
			_		6							
		400	-		7		Cłay (CL), bluish gray, moi	st, stlff, medium plasticity, solve	nt odor?			
					8							
	\times				9							
		1000			10							
					12							
					13	-	Candu provot /CD\ bluich	gray, wet, loose, solvent odor.			-	
	$\mid - \mid$				14	-			r 13.5' to 14'			
	$\vdash \vdash$	\times	+		15		Sandy clay (SP), bluish gray, fine grained, wet, solvent odor 13.5' to 14'. Clay (CL), bluish gray, moist, stiff, medium plasticity, solvent odor 14' to 15".					
	$\vdash \vdash$				16		Bottom of Baring 15'					
					17	\vdash						
					18							
					19							
					20							

C	Ē	1	THE					_	BORINGIVELL	.iD:				
envir	олтеп			JR	CE (GR	OUP, INC.		5	B-27				
PROJE					_		Foundry		Project No.	01-ABI-001				
BORIN							00 gal VST		Logged By:	Nathan Colto	υ Λ			
CONTR			•		NT:		ex Geoprobe							
SAMPL							inuos DW	MONITORING DEVICE:	MiniRae 2000					
START	DATE/	(TIME):				2007 0710	FINISH DATE/ TIME	11/5/2007 830					
FIRST		•	•			==,07		STABILIZED WATER LEVEL:						
SURFA	CE ELI	EVATI	DN:					CASING TOP ELEVATION:						
TOTAL	BORIN	IG DE	THIS):		15'		BORING DIAMETER/DEPTH:	3 1/4" 15'					
Dale/Tim e	Sample Interval PID (ppm) Recovery Stratigraphy					Weler-fevel	(classification ALL PERCENTAG	LITHOLOGIC DESCRIPTION, color, moisture, density, grain. ES ARE APPROXIMATE UNLE	size/plasticity, of	her) ESTATEO	Well construction details			
					1	<u> </u>	Cement debris.	neM debris.						
					2									
	\times	13			3		Clay (CL), dark gray, molsi	(CL), dark gray, molst, stiff, medium plasticity, faint petroleum odor.						
			_		4		White chalking substance,	chalking substance, crumbly.						
		•		*********	5		NR							
		0.2			6 7		Silty day (CL), dark gray, n	noist, soft, medium plasticity, far	nt petraleum odo	т.				
					8					•				
					9		Clay (CL) dath army maje	t, stiff, medium plasticity, no odo	r					
					10		Olay (OE), balk glay, mois	, sun, mediani piasticity, no odo	•					
					11									
					12		Same as above bul mediu	m browniah grav.						
					13			, , , , , , , , , , , , , , , , , , ,						
	\times	0			14			Bottom of Boring 15'						
					16	_		20(23.11 2) 20/11ig (2						
					17									
					18									
					19									
					20									

C		1	THE					_	BORINGWELL	ID:	
anvir	onmen	lal	Sol	UR	CE (GR	oup, Inc.		s	B-28	
PROJE						т —	l Foundry		Project No.	01-ABI-001	
	G LOC					1	DO gal VST		Logged By:	Nathan Colto	n
	ACTO				NT:	_	nex Geoprobe				
SAMPL						1	inuos	MONITORING DEVICE:	MiniRae 2000		
	DATE					-	2007 1500	FINISH DATE/ TIME	11/2/2007 1610)	
	WATER		•			7,5		STABILIZED WATER LEVEL:	+		
	CEEL	_						CASING TOP ELEVATION:			
	BORIN			<u>\</u> :		50,		BORING DIAMETER/DEPTH:	3 1/4" 20'		
			,								5
Date/Time	Sample Interval	PID (ppm)	Recovery	Stratigraphy	Depth (faet)	Water-level		LITHOLOGIC DESCRIPTION, color, moisture, density, grain ES ARE APPROXIMATE UNLE	size/plasticity, of		Well construction
					1		NR .				+
					2						
					3						
					4						
					5	\vdash					
	\times				6		Clay (CL), dark brown, mo	ist, stiff, medium plasticity, no oc	sor.		
		02			7		Gravelly clay (GC) with fin	e sands, very dark brown, wel, p	oorly sorted, soft,	no odar.	$\frac{1}{2}$
					8		Clay (CL), very dark gray,	moist, stiff, no odor.			4
	\times	0.2			9		Gravelly clay (GC) with fin	e sands, very dark brown, wel, p	oorly sorted, soft	no odor	
					10						_
						1		ery fine particles, crumbles.			4
		0.1		iiiia	11			wel, poorly sorted, faint petroleur vist, stiff, medium plasticity, faint			-
		U, I			12			stiff, medium plasticity, no odor.			
					13						
	$\overline{\mathbb{X}}$				14						
					15		Sand (SP), medium grains	ed trace gravěl, light gray, wet, w	ell sarled, loase,	na odor.	-
					16						
					17		Clay (CL), medium browni	sh gray, moist, stiff, medlum plas	sticity, no odor		
			ā		18						
					19				_		
					20			Bottom of Boring 20'			<u> </u>

0		1	HE						BORINGWELL	ID:	
enviro	nmen			UR	CE (GR	OUP, INC.		s	B-29	
PROJEC	T NA	ME AN	D ADI	DRES	s:	AB&	Foundry		Project No.	01-ABI-001	
BORING	LOCA	ATION	(AT S	ITE):		10,00	DD gai VST		Logged By:	Nathan Colton	
CONTR	ACTO	RAND	EQUI	PME	NT:	Viron	nex Geoprobe		-		
SAMPLI	NG MI	ETHOE) :			Cont	inues	MONITORING DEVICE:	MiniRae 2000		
START	DATE	(TIME):			11/5/	2007 900	FINISH DATE/ TIME			
FIRSTV	VATER	(BGS):			6.5		STABILIZED WATER LEVEL:			
SURFAC	ČE ELI	EVATION	ON:			3000		CASING TOP ELEVATION:			
TOTAL	BORIN	IG DE	PTH(S) ;		15		BORING DIAMETER/DEPTH:	3 1/4" 15'		
Date/Time	Sample Interval	PID (ppm)	Recovery	Stratigraphy	Depth (feet)	Water-level		LITHOLOGIC DESCRIPTIC I, color, moisture, density, grain : ES ARE APPROXIMATE UNLES	size/plasticity, oth	ner) STATED	well construction details
					1		Cement debris.				
					•			s (sluffing from top of the sample	sleeve?) dry, sli	ght petroleum od	Ì
					2		,		,		
					3						
							No recovery.				
					4						
					5		Clay (CL), dark brown, moi:	st, stiff, medium plasticity, no od	or.		
	\times				6	V					
					7		Silty day (CL), dark gray, w	et, loose, no odor.			
		0.2			8						
					9		0(110)	-4'88 48			
	\sim				10		Clay (CE), dark gray, moist	, stiff, medium plasticity, no odor	, some ibols.		
					11						
					12						
					13		Clay (CL), light brown to gro odor.	ey, moist, stiff, medium plasticity	, trace rocks (1/4	"round), no	
		0.1			14						
					15			Bottom of Boring 15'			
					15						
					17						
				_	18		No water recovery at 15' C	i, screened 15' - :	50, pða		
					19						
					ŽÕ						

\$8-79.xis Page 1 of 1

0		1	THE		_				BORINGWELL	ID:		
enviro	nmen	tal	Sou	JR	CE (R	OUP, INC.		S	B-30		
PROJEC	T NA	ME AN	D ADD	RES	S:	A8&I	Foundry		Project No.	01-ABI-001		
BORING	LOCA	ATION	(AT S	TE):		10,00	00 gal VST		Logged By:	Nathan Colton		
CONTR	ACTO	RAND	EQUIP	MEN	IT:	Viror	nex Geoprobe					
SAMPLI	NG MI	ETHOR);			Cont	inuous	MONITORING DEVICE:	MiniRae 2000			
START	DATE/	(TIME):				2007 1345	FINISH DATE/ TIME	11/2/07 1445			
FIRST						10'		STABILIZED WATER LEVEL:				
SURFAC								CASING TOP ELEVATION:				
TOTAL	the second second	E-1		:		15'		BORING DIAMETER/DEPTH:	3 1/4" 15'			
Date/Time	Sample Interval	PID (ppm)	Recovery	Stratigraphy	Depth (feet)	Water-level		LITHOLOGIC DESCRIPTION, color, moisture, density, grain ES ARE APPROXIMATE UNLES	size/plasticity, oth	her)	Well construction details	
Dal	Sa Pic			De	§ ₩					We deta		
					0							
					1		Cement debris.					
							Gravelly sand (asphalt), da	rk gray, loose, dry, no odor.				
	\times											
	$\overline{}$				4		Clay (CL), dark gray, moist, stiff, medium plasticity, no odor.					
					5							
					6	_	NR					
					7		Gravelly sand (SP) dark b	rown, moist, loose, poorly sorted	no oder.			
					8		,,	,,, ,	,			
				VIIII)	9		Clay (CL), medium gray,			-		
					10		John (GE), medicin gray,					
					11					1		
					12							
					13	 	-					
	\nearrow				14		Clay (CL), dark brown, moi	ist and wet, soft, low plasticity, n	o odor.			
					15	T		Bottom of Boring 16'				
					17							
					18		-					
					19		-					
					20		_					

S	C		THE					BORINGWELL ID.					
envire		tei	Sol	JR	CE	R	oup, Inc.		S	B-31			
PROJE	CT NA	ME AN	00A D	RES	S:	88A	l Foundry		Project No.	01-ABI-001			
BORING	S LOC	ATION	(AT S	TE);		Park	ing Lot		Logged By:	Nathan Collon			
CONTR	ACTO	R AND	EQUIF	MEN	IT:	Viror	ех Geoprobe	_					
SAMPL	ING M	ETHO):			Macr	0	MONITORING DEVICE:	MiniRae 2000				
START	DATE	TIME);			11/5/	/07 1430	FINISH DATE! TIME					
FIRST	WATER	(BGS):					STABILIZED WATER LEVEL:					
SURFA	CE EL	EVATION	ON:					CASING TOP ELEVATION:					
TOTAL	BORIN	IG DE	TH(S)	:		25'		BORING DIAMETER/DEPTH:	2" 25'				
Date/Time	Sample Interval	PID (ppm)	Recovery	Straugraphy	O Dapth (feel)	Water-fevel	(classification ALL PERCENTAGE	LITHOLOGIC DESCRIPTION, COLOR, MAISTURE, DESCRIPTION, COLOR, MAISTURE, COLOR, C	size/plasticity, oth	er) STATED STATED STATED			
		<u> </u>		_	1								
	\boxtimes				2								
					3	-	Gase Jammed. Sample not	removed.					
					4								
	\times				5				_				
					6		ND						
							NR .						
		0.1			7		Clay (CL), black, moist, stif	f, medium plasticity, no odor					
					8					ı			
					9								
		0.1			10								
					11								
					12								
					13								
					14								
_					15		Clay (CL), olive brown, moi	st, stiff, medium plasticity, no oc	lor.				
					16		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	, , , , , , , , , , , , , , , , , , ,					
					17								
					18								
					19								
					20								

	<u></u>	<u> </u>	THE					-	BORINGWELL	, IO;		
enviro	nmer	tal	Sou	JR	GE (ìR	DUP, INC.			SB-31		
PROJEC	CT NA	ME A	ND ADD	RES	3:	AB&) Foundry		Project No.	01-ABI-001		
BORING	LOC	OITA	N (AT SI	TE):		Park	ing Lot		Logged By:	Nathan Colton		
CONTR	ACTO	R AN	D EQUIP	MEN	T:	νίτοι	nex Geoprobe					
SAMPL	NG M	ETHO	D:			Macr	o	MONITORING DEVICE:	MiniRae 2000			
START	DATE	(TIM	E):			11/5/	07 1430	FINISH DATE! TIME	11/5/07 1545			
FIRST V	VATER	(BG	S):					STABILIZED WATER LEVEL:				
SURFA	CE EL	EVA1	ION:					CASING TOP ELEVATION:				
TOTAL	BORIN	IG DI	EPTH(S):			25'		BORING DIAMETER/DEPTH:	2" 25'		_	
Date/Time	Sample Interval PID (ppm) Recovery Stratigraphy						(classificatio	LITHOLOGIC DESCRIPTI n, color, maisture, density, grain ES ARE APPROXIMATE UNLE	size/plasticity, o	ther) E STATED (STATED	details	
					20							
					22		Same as above but softer.					
					23	_						
					24	_	Clay (CL), gravelly clay, dark brown, moist, very stiff, medium plasticity, no odor.					
					25			Bottom of Baring 25				
					26							
					27	<u> </u>						
				-	28							
					29							
					30							
				-	31							
					32							
					33							
					34							
					35							
					36							
				_	38							
				<u> </u>	39							
					40							
				<u>l. </u>								

\$8-31 (1) Page 2 of 2

5	G	ΠB	THE		_		oup, Inc.		BORINGWELL					
envir	onmer	lai	501	JR	CE (iR	DUP, INC.		S	B-32				
ROJE	CT NA	ME AN	ID ADD	RES	S :	AB&	l Foundry		Project No.	01-A8I-001				
ORIN	G LOC	ATION	(AT SI	TE):		Park	ing lot		Logged By:	Nathan Colto	on_			
ONTR	ACTO	R AND	EQUII	PMEN	IT:	Vimr	nex Geoprobe							
AMPL	ING M	ETHO):			Macı	0	MONITORING DEVICE:	MiniRae 2000					
TART	DATE	(TIME	:):			11/2	8/2007 753	FINISH DATE/ TIME	11/26/2007					
IRST \	WATE	R (BGS	i):			10'		STABILIZED WATER LEVEL:						
BURFA	CE EL	EVATI	ON:					CASING TOP ELEVATION:						
OTAL	BORIN	IG DE	PTH(S)):		20'	<u> </u>	BORING DIAMETER/DEPTH:	2" 20'					
Date/Time	Sample Interval	PID (ppm)	Recovery	Straligraphy	Depth (leet)	Water-fevel	(classificatio ALL PERCENTAG	LITHOLOGIC DESCRIPTION, color, moislure, density, grain ES ARE APPROXIMATE UNLES	size/plasticity, of	her) ESTATED	Well construction			
				-	1	-		<u>.</u>		\dashv				
						<u> </u>	Asphall debns.	Sphall debns. Stavelly sill (ML), medium brown, dry, crumbly, poorly sorted, no odor, fill						
					2		Gravelly silt (ML), medium	brown, dry, crumbly, poorly sorte	ed, no odor, fill					
					3			v (CL) dark aray maist stiff medium plasticity on odor						
					4		Clay (CL), dark gray, mois	y (CL), dark gray, moist, stiff, medium plasticity, no odor.						
					5		-							
					_									
					6		1							
					7									
					8		Light gray.							
					9									
					10									
					11									
					12									
					13									
					14		More maist							
					15	<u> </u>	1							
					16									
					17		Canadaaniii aantanii ii							
					18		Greater sill content, more	moist. own. moist, stiff, medium plastici	iv no odor					
					19			,	,,, ,,,					
-					20	\vdash		Bottom of Boring 20'			\dashv			

	7	1	THE						BORINGWELL	, ID.						
envir	onmen	Lal (Sot	JR	CE (ir	OUP, INC.		S	B-33						
PROJE							I Foundry		Project No.	01-ABI-001						
BORIN			-				ing fol		Logged By:	Nathan Colto	n					
CONTR					T:	_	nex Geoprobe 6600		537	17.0						
SAMPL						Macr		MONITORING DEVICE:	MiniRae 2000							
START							6/2007 1030	FINISH DATE/TIME	11/26/2007							
FIRST						17.5		STABILIZED WATER LEVEL:								
SURFA	CE ELI	EVATION	ON:				_	CASING TOP ELEVATION:								
TOTAL	BORIN	IG DE	PTH(S)	:		20,		BORING DIAMETER/DEPTH:	2" 20′							
Date/Time	Sample Interval	PID (ppm)	Recovery	Stratigraphy	Depth (feel)	Water-levei	(classification	LITHOLOGIC DESCRIPTION, color, moisture, density, grain ES ARE APPROXIMATE UNLES	size/plasticity, of	her) ESTATED	Well construction details					
					1		Gravelly clay (fill).				-					
					2		NR									
					3											
					4		•									
					5											
					6	 										
	L				7											
					8											
					9											
		0.3			10		Clay (CL), light grayish bro fragments.	wn, molst, stiff, medium plasticit	y, no odor, Irace	red (brick?)						
					11		Olive brown with no brick f	ragments.								
					12		1									
					13											
					14											
					15		Olive to light brown (lan), r	noisl, sliff, medium plasticity, no	odor							
1	╂				16											
						1	4									
					17	•	Light grayish brown, well, s	off, medium plasticity, no odor.								
					17	T	Light grayish brown, well, s	oft, medium plasticity, no odar.								
						•		oft, medium plasticity, no odar. , medium plasticity, no odor.								

S9-33 yn Page 1 of 1

S	G		THE	I D a 4	n. 1		oup, Inc.		BORINGWELL		_			
envir	оптел	tal	2 U I	JKI	it l	ЯK	OUP, ING.		3	B-34				
ROJE	CT NA	ME AN	DADE	RES	S:	AB8	l Foundry		Project No.	01-ABI-001				
BORING	G LOC	ATTON	(AT SI	TE):		Park	ing lat		Logged By:	Nathan Colto	n.			
ONTR	ACTO	RAND	EQUIP	MEN	۲;	Viror	nex Geoproba 6600							
BAMPL	ING M	ETHO):			Mac	ro	MONITORING DEVICE:	MiniRae 2000					
TART	DATE	TIME):			11/2	B/2007 1030	FINISH DATE/ TIME	11/26/2007					
IRST (NATER	₹ (BGS) :			17.5	•	STABILIZED WATER LEVEL:						
SURFA	CE EL	EVATION	ON:				,	CASING TOP ELEVATION:						
OTAL	BORIN	IG DE	PTH(S)	:		20'		BORING DIAMETER/DEPTH:	2" 20"					
Date/Time	Sample interval PID (ppm) Recovery Stratigraphy					Water-level		LITHOLOGIC DESCRIPTION TILE COLOR, moisture, density, grain ES ARE APPROXIMATE UNLE	size/plasticity, of		Well construction			
	1						Gravelly clay (fill).			<u>.</u>				
		 _	2 NR											
					3		-							
					4	-	-							
					5									
		2			6									
					7									
					8									
					9									
			-		10		Clay (CL), plive brown, mo	ist, medium tighlness, medium p	olasticity, no cdoi					
					11									
		1.1			12		Clay (CL), trace gravel, me	edium grayish brown, maist						
					13									
					14	_		moist, stiff, medium plasticity, ne						
					15 16		Gravelly day (CL), mediun	n brown, moist, poorly soried, no	0001.					
					17		Clay (CL), ofive brown, mo	ist, stiff, medium plasticity, no od	dor					
					18									
		0.4			19	19								
					28			Bottom of Boring 20'			7			

SB-34 rts Page 1 of 1

C		1	HE						BORINGWELL !	D :			
enviro	n men	tal	Sol	JR	CE I	GR	oup, Inc.		SE	3-35			
PROJEC	T NA	ME AN	D ADI	RES	S :	AB&	Foundry		Project No.	01-ABI-001			
BORING	LOCA	NOITA	(AT S	TE):		Park	ing lat		Logged By:	Nathan Colton			
CONTR	ACTO	DIA P	EQUI	PMEI	VT:	Viron	ex Geoprobe						
SAMPLI	NG M	THOC);			Cont	inues	MONITORING DEVICE:	MiniRae 2000				
START	DATE	TIME	} :			11/28	5/2007 1140	FINISH DATE/ TIME	11/26/2007 1230				
FIRST V	VATER	(BG\$):			11.5		STABILIZED WATER LEVEL:					
SURFAC	CE ELE	EVATIO	:אכ					CASING TOP ELEVATION:					
TOTAL	BORIN	IG DEF	PTH(S	<u>}</u> ;		15'		BORING DIAMETER/DEPTH:	2" 15'				
Date/Time	Sample Interval	PID (ppm)	Recovery	Stratigraphy	Oepth (feel)	Water-fevel		LITHOLOGIC DESCRIPTION COLOR C	size/plasticity, othe	er) STATED	Well construction details		
		_	ш.	0)	0	_	_	-			- 0		
1 Hand auger to 5' bgs.													
					2								
					3								
					4	_							
					5		NR						
					8		NR .						
					7								
					8								
					9								
		0.6			10		Gravelly day (C) 1 black m	taist_soft, medium plasticity, no	Ddat				
					11		Graveny cray (CE), black, ii	reasized in mediani presserily, no	00012				
					12		Not much recovery, very wood black, very wel, loose, no o	et, water moving soil sample gre dor.	vel. Appears to be	gravelly clay,			
					13								
				111111	4.4	-		ay, wet, loose, poorly sorted, no					
					14		Ctay (CL), dank gray, moist	, stiff, medium plasticity, no odor	,				
					15			Bottom of Boring 15'					
		_			16								
					17								
18													
					19								
20													

Page 1 of 1

	7	1	HE						BORINGWELL	10.			
BOVITO	onmen			UR	CE (GR	OUP, INC.		S	B-36			
PROJE	CT NA	ME AN	D ADI	DRES	SS:	AB&	l Foundry		Project No.	01-ABI-001			
BORING	LOC	ATION	(AT S	ITE):		Park	ing lot		Logged By:	Nathan Colton			
CONTR	ACTO	R AND	EQUI	PME.	NT:	Viror	nex Geoprobe			•			
SAMPL	NG M	ETHOD):			Cont	inues	MONITORING DEVICE:	MiniRae 2000				
START	DATE	(LIME) :			 	5/2007 1300	FINISH DATE/ TIME	11/26/2007 140	00			
FIRSTY						11.5		STABILIZED WATER LEVEL:					
SURFA						_		CASING TOP ELEVATION:					
TOTAL	MIROB	IG DEF	PTH(S):		15'	•	BORING DIAMETER/DEPTH:	2" 15'				
Date/Time	Sample Interval PID (ppm) Recovery Stratigraphy							LITHOLOGIC DESCRIPTION, COLOR, MOISTURE, DESCRIPTION, MOISTURE, DESCRIPTION, GRAIN BES ARE APPROXIMATE UNLES	size/plasticity, ot				
					0								
					ſ		Sill (ML), light gray/white, d	iry, crumbly, no odor, fill.					
					2								
					3								
					4	-							
					5		NR						
					6								
					7								
					8					1			
					9	-							
					10								
					11	V	Very wel, water in empty sl	eeve.					
					12								
					13								
					14		Gravel (GP), dark gray, wel	t, loose, poorly sorted, 1/4" - 1/2"	° subangular, no	odor.			
					15	L.		Bottom of Boring 15'					
					16								
					17								
					18								
					19								
					20								

C	C		HE			_			BORINGWELL	. ID·				
envir	onmen	tal	102	JRO	CE (3 R	DUP, INC.		5	SB-37				
ROJE	CT NA	ME AN	D ADD	RESS	 3:	AB&	l Foundry		Project No.	01-ABI-001				
ORIN	G LOC.	ATION	(AT S)	TE):			ing lot		Logged By:	Nathan Colto	מס			
ONTR	ACTO	R AND	EQUIF	MEN	T:		nex Geoprobe 6600	<u> </u>	,	•				
AMPL	ING M	ETHO) ;			Macr	0	MONITORING DEVICE:	MiniRae 2000					
TART	DATE	TIME) :			11/26	3/2007 1110	FINISH DATE/ TIME	11/26/2007					
IRST	WATER	R (BGS) :			17.5		STABILIZED WATER LEVEL:						
URFA	CEEL	EVATK	אכ:					CASING TOP ELEVATION:						
OTAL	BORIN	IG DEF	7H(S)	:		20,		BORING DIAMETER/DEPTH:	2" 20'	_				
Date/Time	Sample Interval PID (ppm) Recovery Stratigraphy					Waterlevel		LITHOLOGIC DESCRIPTION, color, moisture, density, grain ES ARE APPROXIMATE UNLE	size/plasticity, of		Well construction			
					1		Cement debris, fill.							
_					2		Clay (CL), dark brown, mo	s), stiff, medium plasticity, no od	lor					
					3									
					4									
					5									
					6									
		_			7									
					8		Some gravel, subangular t	1/4" diameler						
		0.4			9				_					
					10		Clay (CL), grayish brown, r 	noist, stiff, medium plasticity, no	odor,					
					11		Olíve brown, moist, mediui	m stiffness, medium plasticity, n	o odor					
	-				13	<u> </u>								
					14									
					15									
					16	▼	Silty sand (SM), line grains	ad, olive brown, wet, loose, well.	sorted, no odor.					
					17		Clay (CL), grayish brown, 1	moist, stiff, medium plasticity, no	odor.					
1														
					19									
]]	20			Bottom of Boring 20'						

Sa 17 zki Paga 1 of 7

0		1	THE						BORINGWELL	, ID:		
enviro				JR	CE (ìR	OUP, INC.		S	SB-38		
PROJE	CT NA	ME AN	ID ADD	RES	S:	AB&	Foundry	•	Project No.	01-ABI-001		
BORING	LOC	MOITA	(AT SI	TE):					Logged By:	Nathan Colton	١	
CONTR	ACTO	R AND	EQUIF	MEN	IT:	WDO	Geoprobe 7730D T					
SAMPL	NG MI	ETHOI) ;			325	continuous	MONITORING DEVICE:	MiniRae 2000			
START	DATE	(TIME	:):			7/8/0	900	FINISH DATE/ TIME	7/8/08 1300			
FIRST V	VATER	(BGS	<u>)</u> :			19.5		STABILIZED WATER LEVEL:				
SURFA	CE ELI	EVATION	ON:					CASING TOP ELEVATION:				
TOTAL	BORIN	IG DEI	PTH(S)	:		44'		BORING DIAMETER/DEPTH:	4" 44'			
Date/Time	Sample Interval PID (ppm) Recovery Stratigraphy							LITHOLOGIC DESCRIPTION, color, moisture, density, grain as ARE APPROXIMATE UNLES	size/plasticity, ot		Well construction details	
					1	_	Cement debris, fill.					
							Silty Clay, trace gravet (con	crete?), dark gray, soft, modera	te plasticity, faint	odor		
					2		(petroleum?)					
					3							
					4							
		0.3			5		Clay, dark gray, moist, soft,	moderate plasticity, no odor				
					6	<u> </u>						
					7							
					B		Clay, alive brown, maist, so	ft, moderate plasticity, no odor				
					9							
		1.4			10							
					11							
					12		same as above, moist to w	le				
		_			13							
					14							
		0.3			15			ome gravel, 1/4" subangular, we	l graded, med-g	rained, no odor		
		3.6	_		16		Clay, olive brown, moist, stiff, low plasticity, no odor					
					17							
					18							
					19	Y						
					20							

6		$\overline{\Box}$	THE						BORINGWELL	ID:			
envire	onmer	ntal	Soi	URC	CE (RE	OUP, ING.		5	SB-38			
PROJE	CT NA	ME A	ND ADD	RESS	3:	AB&	l Foundry		Project No.	01-ABI-001			
BORING	3 LOC	ATIO	N (AT SI	TE):					Logged By:	Nathan Colton			
CONTR	ACTO	RAN	<u>D</u> EQUIP	MEN.	Τ:	WDO	C Geoprobe 7730DT						
SAMPL							continuous	MONITORING DEVICE:	MinìRae 2000				
START			•			7/8/0	08 900	FINISH DATE/ TIME	7/8/08 1300				
FIRST						├—	<u> </u>	STABILIZED WATER LEVEL:	_				
SURFA						╀		CASING TOP ELEVATION:					
TOTAL		NG DI	EPTH(S)	<i>:</i> 		44'	<u> </u>	BORING DIAMETER/DEPTH:	4" 44"		T _C		
Date/Time	Sample Interval	PID (ppm)	Квсочегу	Stratigraphy	Depth (feet)	Water-level	(classificatio ALL PERO	LITHOLOGIC DESCRIPTI n, color, moisture, denslty, grain CENTAGES ARE APPROXIMAT	size/plasticity, of	lher) IE	Well construction details		
		1.9			20				_				
					22		Silay Clay olive hours mo						
					23		Silty Clay, olive brown, moist, soft, low plasticity, no odor Silty Sand olive brown, medium preined, some gravel, 1/2" subangular well graded an od						
				<i></i>	24		Silty Sand, olive brown, medium-grained, some gravel, 1/2" subangular, well graded, no odor						
					25		-						
					26								
					27								
			-		28		Clay, olive brown, some gr	evel, 1/4" subangular, moist, stif	f, low plasticity, n	o odor			
					29	 	Gravelly Sand, medium gra	eined, 1/2" subangular, moist, w	ell graded, no odd	or			
					30		Clay, medium brown, wet,	stiff, moderate plasticity, no odo	,				
					31								
					32		Silt, medium brown, well, se	oft, no odar			1		
					33		Clay, light gray, moist, stiff,	moderate plasticity, no odor					
					34								
					35								
					38	same as above, soft, moist to wet							
					37								
39													
					40								

C	G		THE						BORINGWELL	D:	
arryire	onmer)tai	Sou	IRO	CE (R	DUP, INC.		s	B-38	
PROJEC	CT NA	ME A	ND ADD	RESS	ì:	AB&I	Foundry		Project No.	01-ABI-001	
BORING	LOC	ATIO	N (AT SI	TE):					Logged By:	Nathan Cofton	
CONTR	ACTO	RAN	D EQUIP	MEN.	T:	WDC	Geoprobe 7730DT				
SAMPL		_		_		325	continuous	MONITORING DEVICE:	MiniRae 2000		
START						7/8/0	8 900	FINISH DATE/ TIME	7/8/08 1300		
FIRST Y								STABILIZED WATER LEVEL:			
SURFA						-	<u> </u>	CASING TOP ELEVATION:			
TOTAL	BORIA	IG DE	EPTH(S):			44'		BORING DIAMETER/DEPTH:	4" 44'	·	
Date/Time	Sample Interval	PID (ppm)	Recovery	Stratigraphy	Depth (feet)	Water-level	(classificatio ALL PERC	LITHOLOGIC DESCRIPTI n, color, moisture, density, grain ENTAGES ARE APPROXIMATI	size/plasticity, oth	ner) R	Well construction details
		1.9	3		40						
					41		-				
					42						
					43						
					44		Refusal at 44'				
					46	_					
					47						
					48						
					49	-					
					50						
					51						
					52	\vdash					
		_			53						
					54						
					5\$						
					56						
1					57			-			
	l				58						
					59 60						
					👸						

SB-38 ets Page 3 of 3

0		T Y	THE					_	BORINGWELL	.ID:	
enviro	nmen			JRO	CE E	ìR	DUP, INC.	_	S	B-39	
PROJEC	T NA	VIE AN	D ADD	RES	S:	AB&I	Foundry		Project No.	01-ABI-001	Ì
BORING	LOCA	ATION	(AT SI	TE):					Logged By:	Nathan Collor	1
CONTR	ACTO	GNA F	EQUIP	MEN	T:	WDC	Geoprobe 7730DT				
SAMPLI	NG ME	THOD):			325 c	continuous	MONITORING DEVICE:	MiniRae 2000		
START	DATE/	(TIME):			7/8/0	8 1355	FINISH DATE/ TIME	7/8/08 1645		
FIRST V	VATER	(BGS	}:					STABILIZED WATER LEVEL:			
SURFAC	CE ELE	EVATIO	ON;				1	CASING TOP ELEVATION:	_		
TOTAL	BORIN	G DEF	TH(\$):	:		43'	_	BORING DIAMETER/DEPTH:	4" 43'		
Date/Time	Sample Interval PID (ppm) Recovery Stratigraphy					Water-level	(classification ALL PERCENTAGE	LITHOLOGIC DESCRIPTION, color, moisture, density, grain see ARE APPROXIMATE UNLES	size/plasticity, ot	her) : STATED	Well construction details
						Ш					1 1
					3						
											.
					5						
					6						
					7						
					В						
					9						
					10						
					11						
					12						
					13						
					14						
					13						
					16						
	 										
					19	Y					
					20						

SB-39 vir Page 1 of 3

C	C	17	THE						BORINGWELL	.10:				
envin	onmar	lair	Sou	JR(CE (ìR	OUP, INC.			SB-39				
PROJE	CT NA	ME A	ND ADD	RESS	S:	AB8	l Foundry		Project No.	01-ABI-001				
BORING	S LOC	ATIO	N (AT SI	ſE :					Logged By:	Nathan Colton				
CONTR	ACTO	RAN	D EQUIP	MEN.	T:	WD	C Geoprobe 7730DT							
SAMPL	ING M	ETHC	D:			325	continuous	MONITORING DEVICE:	MiniRae 2000					
START	DATE	/ (TIM	E):			7/8/0	08 1355	FINISH DATE/ TIME	7/8/08 1645					
FIRST Y	NATER	R (BG	S):					STABILIZED WATER LEVEL:						
SURFA	CE EL	EVAT	10N:					CASING TOP ELEVATION:						
TOTAL	BORIN	VG DE	EPTH[\$]:	:		43'		BORING DIAMETER/DEPTH:	4" 43'					
Date/Time	7				Depth (feet)	Water⊰evel	(classificatio ALL PER(LITHOLOGIC DESCRIPTI in, color, moisture, density, grain CENTAGES ARE APPROXIMA	stze/plasticity, o	ther) HE	Well construction			
								no odor						
		21												
					22									
					23	_								
		2			25		Clay, black, moist, soft, moderate plasticity, no odor							
		2	_		26		same as above, bluish g							
					27		-							
					28		-							
					29									
					30									
		4.4			31	_		own, fine-grained, wet, no od						
					32		Clay, medium brown, mois	t, stiff, moderate plasticity, no od	ior					
		$\vdash \vdash$			34	_								
	_	2	1		35									
					36									
					37		-							
							Silty Clay, olive brown, moist, stiff, moderate platicity, no odor							
					39									
					40									

SB-39.145 Page 2 of 3

0		$\overline{\Pi}$	THE						BORINGWELL	ID:	
envira	nmer	tal	Sou	JR	BE (R	DUP, INC.		S	B-39	
PROJEC	T NA	ME A	ND ADD	RESS);	AB&I	Foundry		Project No.	01-ABI-001	
BORING	LOC	ATIO	N (AT SIT	FE):					Logged By:	Nathan Colton	
CONTR	ACTO	R AN	D EQUIP	MEN.	T:		Geoprobe 7730DT				
SAMPLI						_	±ontinuous	MONITORING DEVICE:	MiniRee 2000		
START	DATE	(TIM	E):			7/8/0	8 1355	FINISH DATE/ TIME	7/8/08 1645		
FIRST V								STABILIZED WATER LEVEL			
SURFAC	_							CASING TOP ELEVATION:			
TOTAL	BORIN	IG DE	EPTH(S):			43'		BORING DIAMETER/DEPTH:	4* 43'		
Date/Time	Sample Interval	PID (ppm)	Recovery	Stratigraphy	Depth (faet)	Water-level	(classification ALL PERCI	LITHOLOGIC DESCRIPTI	size/plasticity, of	her) ER	Well construction details
		Ď.5			40		Clay, dark brown, very stiff	(lough drilling), moist, moderate	plasticity, no odo	of	
					41						
					42						
					43		Refusal at 43'				
					44						
					45 						
					47						
					48						
					49						
					50						
			_		51	_					
	•			-	52						
					53						
					54			,			
					55						
					56						
					58						
					59	-					
					60	-					

C	G		HE						BORINGWELL	ID:			
enviro	Miller			JR	CE (ìR	OUP, INC.		s	B-40			
PROJEC	ST NA	ME AN	D ADD	RES	S:	AB&I	Foundry		Project No.	01-ABI-001			
BORING	LOCA	ATTON	(AT SI	TE):					Logged By:	Nathan Colton	1		
CONTR	ACTO	RAND	EQUIP	MEN	IT:	WDC	Geoprobe 7730DT						
SAMPL	NG MI	ETHOU) ;			325	∞ntinuous	MONITORING DEVICE:	MiniRae 2000				
START	DATE/	TIME):			7/9/0	8 640	FINISH DATE/ TIME	7/9/08 900				
FIRST V	VATER	(BGS):					STABILIZED WATER LEVEL:					
SURFAC	CE ELI	EVATIO	ON:					CASING TOP ELEVATION:					
TOTAL	BORIN	G DE	PTH(S)	:		35'		BORING DIAMETER/DEPTH:	4" 35'				
Date/Time	Sample Interval PID (ppm) Recovery Stratigraphy					Water-tevel	ALL PERCENTAGE	LITHOLOGIC DESCRIPTION, color, moisture, density, graines ARE APPROXIMATE UNLES	size/plasticity, oth		Well construction details		
					0		asphalt	2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	- 14	. ma adaa Mili			
		_	80		1		Clay, orangish brown, somi	e gravel, 1/2" - 3/4" subangular,	sur, low plasticity	, no odor, FILL			
					2								
					3								
					4		Sandy Clay, bluish gray,	fine-grained sands, loose, no	o odor.				
					5		Clay, dark gray, moist, stiff, moderate plasticity, no odor						
					6		Clay, dark gray, moist, stiff, moderate plasticity, no odor						
_					7								
					8								
	\				9								
		0.5	100		10					1			
					11								
·	-				12								
					13		Silty Clay, olive brown, mo	ist to wet, soft , moderate plastic	tity, na odor				
	-				14								
		1.2			15								
			_		16								
					17		Gravelly Clay, olive brown.	1/4" subangular, moist to wet, m	noderate plasticity	, no odar.			
					18								
					19	Y							
					20								
			I	l							I		

SB-10,xls Page 1 of 2

			THE						BORINGWELL	. ID:				
enviro	nmen	ta)	Sol	JRO	GE (R	OUP, INC.			SB-40				
PROJEC	AN TO	ME A	D ADD	RESS	S :	AB&	I Foundry		Project No.	01-ABI-001				
BORING	LOC	ATIO	N (AT SI	TE):					Logged By:	Nathan Colton				
CONTR	ACTO	RAN	D EQUIP	MEN	T:	WDG	C Geoprobe 7730DT							
SAMPLI	NG M	ETHO	D:	_		325	continuous	MONITORING DEVICE:	MiniRae 2000					
START	DATE	MIT)	E):			7/9/0	08 640	FINISH DATE/ TIME	7/9/08 900					
FIRST V	VATER	t (BG	S):	_				STABILIZED WATER LEVEL:						
SURFA						<u> </u>		CASING TOP ELEVATION:						
TOTAL	BORIN	ig bi	PTH(S)	<u>. </u>		35'		BORING DIAMETER/DEPTH:	4" 35'					
Date/Time	Sample Interval PID (ppm) Recovery Stratigraphy							LITHOLOGIC DESCRIPTI in, color, moislure, density, grain CENTAGES ARE APPROXIMAT	size/plasticity, o		Well construction details			
			100		20									
					21									
					22									
					23		same as above, trace grav							
	_	4			24	L		, stiff, moderate plasticity, no						
					25		Clay, olive brown, moist, sliff, moderate plasticity, no odor							
					26									
					27	_								
		2.3			29									
					30									
					31									
					32									
					33		Sand, medlum brown, n	nedium-grained, wet, loose, p	oorly graded, r	o odor	-			
		2.3			34									
					35		Heaving sands encour	ntered at 35' bgs						
					36		•							
				=	36									
			_	ļ	39									
					40									

SB-40 xtt Page 2 of 2

		1	THE						BORINGWELL	ID:		
envire		tal	Sol	JR	GE E	ìR	OUP, INC.		S	B-41		
PROJE	CT NA	ME AN	D ADD	RES	S:	AB&I	l Faundry		Project No.	01-ABI-001		
BORING	LOC	MOTTA	(AT SI	T ξ):					Logged By:	Nathan Colto	n	
CONTR	ACTO	RAND	EQUIP	MEN	IT;	WDC	Geoprobe 7730DT					
SAMPL	ING M	ETHO):			326 (continuous	MONITORING DEVICE:	MiniRae 2000			
START	DATE	(TIME);			7/9/0	8 900	FINISH DATE/ TIME	7/9/08 1100			
FIRST	VATER	BGS):					STABILIZED WATER LEVEL:				
SURFA					_	L		CASING TOP ELEVATION:				
TOTAL	BORIN	IG DEF	TH(S)	:		35'		BORING DIAMETER/DEPTH:	4" 35'		,	
Date/Time	Sample Interval	PID (ppm)	Recovery	Stratigraphy	Depth (feet)	Water-tevel	ALL PERCENTAGE	LITHOLOGIC DESCRIPTION, color, moisture, density, grain ES ARE APPROXIMATE UNLES	size/plasticity, ot		Well construction details	
		1			0	-	asphalt Gravelly Clay (fill)				-l	
		•			2		Chaveny Cley (mi)					
					3		Clay, dark gray, some gi	ravel (fill)				
					4							
					5		No Recovery					
		_	ļ .	11.000	7	<u> </u>	Cand light may pearen a	sined, wat, poorly graded, no od	Ar.		_	
					8		Clay, black, moist, stiff, mo					
					9		olay, black, molec, abii, mo	defate placedly, no see				
	_				10	_	Clay, bluish gray, moist, so	ft, moderate plasticity, no odor				
					11							
					12							
					13							
					14							
					15							
					16							
					17							
					18							
					19							
1	1			1		1						

C	C	$\overline{1}$	THE						BORING/WELL	. ID:	
enviro	nmer	tal	Sou	JRO	CE (R	DUP, INC.			SB-41	
PROJE	CT NA	ME A	ND ADD	RESS	š:	A8&	Foundry		Project No.	01-ABI-001	
BORING	LOC	ATKO	N (AT SF	TE):					Logged By:	Nathan Colton	
CONTR	ACTO	RAN	D EQUIP	MEN	Τ:	WDC	Geoprobe 7730DT				
SAMPL	NG M	ETHC	D:			325	continuous	MONITORING DEVICE:	MiniRae 2000		
START	DATE	(TIM	E):			7/9/0	8 900	FINISH DATE/ TIME	7/9/08 1100		
FIRST V	VATE	(BG	S):					STABILIZED WATER LEVEL:	:		
SURFA	CE EL	EVAT	ON:					CASING TOP ELEVATION:			
TOTAL	BORIN	}G DE	EPTH(S)	:		35'	<u> </u>	BORING DIAMETER/DEPTH:	4" 35'		_
Dale/Time	Sample Interval PID (ppm) Recovery Strattgrapfry					Waterlevel		LITHOLOGIC DESCRIPTI n, color, moisture, density, grain CENTAGES ARE APPROXIMA	size/plasticity, o		Well construction
			100		20						
					22		Silty Clay, olive brown, moi	st, stiff, moderate plasticity, no o	odor, some 1/4° n	ed gravel	
					23			•			
		0.2			24						
					25		Clay, olive brown, moist	, stiff, moderate plasticity, no	odor		
					26						
					27						
					29						
		2.3			30						
					31						
					32						
					33		Sand, olive brown, medi	um-grained, wet, loose, poor	rly graded, no o	dor	
					34		Heaving sands encour	stored at 15' has			
					36	_	i Lagaring squas sucont	iteren at 35 ugs			
					37	-					
					38						
					39						
					40						

		1	THE						80RING/WELL	. ID:	
enviro	nmer		Sol	JR	CE (ìR	OUP, INC.		S	B-42	
PROJE	CT NA	ME AN	D ADD	RES	S :	AB&	I Foundry		Project No.	01-ABI-001	
BORING	LOC	ATION	(AT 51	TE):					Logged By:	Nathan Colf	on
CONTR	ACTO	R AND	EQUIF	MEN	T:	WDC	C Geoprobe 7730DT				
SAMPL	NG M	ETHO	<u>):</u>			325 (continuous	MONITORING DEVICE:	MiniRae 2000		
START	DATE	(TIME	<u>):</u>			7/9/0	8 1442	FINISH DATE! TIME	7/9/08 1645		
FIRST V	VATER	R (BGS):					STABILIZED WATER LEVEL:			
SURFA	CE EL	EVATION	ON:					CASING TOP ELEVATION:			
TOTAL	BORIN	IG DE	PTH(S)	:		45'		BORING DIAMETER/DEPTH:	4" 45'		
Date/Time	Sample Interval	PID (ppm)	Recovery	Stratigraphy	Oepth (feet)	Water-level	(dassification ALL PERCENTAGE	LITHOLOGIC DESCRIPTION, color, moisture, density, grain as ARE APPROXIMATE UNLES	size/plasticity, of	her) E STATED	Well construction details
					1		0' bgs to 20' bgs see boring	1 SB-13			
					2			, 55 . 5			
					3						
					4						
					6						
					7						
					8						
					9						
					10						
					12						
					13						
					14	 					
_					15	-					
					16						
					17						
					18						
					19						
					20						

C		$\overline{\Pi}$	THE						BORINGWELL	ID:	
envir	onmer	/tel	Soi	JR	GE (GR	OUP, INC.		5	SB-42	
PROJE	CT NA	ME A	ND ADO	RES	5:	AB&	l Foundry		Project No.	01-ABI-001	
			N (AT SI			<u> </u>			Logged By:	Nathan Colton	
			D EQUIF	MEN	T:		C Geoprobe 7730DT	T			
SAMPL						_	continuous	MONITORING DEVICE:	MiniRae 2000		
START		_				7/9/0	08 1442	FINISH DATE/ TIME	7/9/08 1645		
FIRST V		_	•					STABILIZED WATER LEVEL: CASING TOP ELEVATION:			
TOTAL				•		45'		BORING DIAMETER/DEPTH:	A" A5'		
Date/Time	100				Depth (feet)	Water-level	(dassificatio ALL PERG	LITHOLOGIC DESCRIPTI n, color, moisture, density, grain CENTAGES ARE APPROXIMAT	ON słze/plasticity, ot	iher) IE	Well construction details
	-		1	1 0,		 _				70.00	<i>-</i> 2 6
	100			20		Clay, bluish gray, moist, sti	ff, moderate plasticity, no odor			1	
				21							
					22		-				
					23		-				
		1.8	-		24]				
		1.0	- No		25	-	1				
			100		26						
					27						
					28						
		1.8			29						
			100		30					•	
					31		Clay, medium brown, m	oist, stiff, moderate plasticity,	no odor		
	_				32						
			====		33		1				
		0			34						
	_				35		-				
			-307		36		_				
		<u> </u>			37	-	-				
					38	1					
1618	-				39	+	-				
	\geq					-					-
				1	40						

C		Ī	THE				_		BORINGWELL	ID;	
enviro	плег	tal	Sou	JRO	CE (ìR	DUP, INC.		5	B-42	
PROJEC	TNA	ME A	ND ADD	RESS	3:	AB&	1 Foundry		Project No.	01-A81-001	
BORING	LOC	OITA	N (AT SI	TE):			•	1	Logged By:	Nathan Colton	
			D EQUIP		T:	WDC	Geoprobe 7730DT		1	-	-
SAMPLI	NG M	ETHO	D:			Г		MONITORING DEVICE:	MiniRae 2000	-	
START	DATE	(TIM	 E :		-	_		FINISH DATE/ TIME	7/9/0B 1645		
FIRST V	VATER	₹ (BG	S):					STABILIZED WATER LEVEL			
SURFAC	E ELI	EVAT	ION:					CASING TOP ELEVATION:		-	
TOTAL	BORIN	iG Di	EPTH(S):			45'		BORING DIAMETER/DEPTH:	4" 45'		
Date/Time	Sample Interval	PID (ppm)	Recovery	Stratigraphy	Depth (feet)	Water-level	(dassification	LITHOLOGIC DESCRIPT I, color, moisture, density, grain ENTAGES ARE APPROXIMAT	ION n size/plasticity, ot	her) ER	Well construction details
					40				_		
					41						
					42						
					43						
					44						
					45		Refusal at 45'				
					46						
					47						
		~			48						
					49						
					50						
					51						
					52						
					\$3						
					54						
					55 56						
					57						
					58	-					
					59	_					
					60	_					

SB-42 xh Page 3 of 3

		1	THE						BORINGWELL	_ ID:					
envir	олтел	tal	Soi	JR	CE (GR	oup, Inc.			SB-44					
PROJE	CT NA	ME AN	D ADD	RES	S:	A88	I Foundry		Project No.	01-ABI-001					
BORING	LOC	ATION	(AT SI	TE):			•		Logged By:	Nathan Colt	ton .				
CONTR	ACTO	R AND	EQUIF	MEN	IT:	WDO	C Geoprobe 7730D 7								
SAMPL	ING M	ETHOL) :			325	∞ntinuous	MONITORING DEVICE:	MiniRae 2000						
START	DATE	(TIME]:			7/10	/08 630	FINISH DATE/ TIME	7/10/2008						
FIRST	VATER	(BGS):					STABILIZED WATER LEVEL:							
SURFA	CE EL	EVATI	ON:				<u></u>	CASING TOP ELEVATION:							
TOTAL	BORIN	IG DEI	PTH(S)	:		35'		BORING DIAMETER/DEPTH:	4" 35'						
Date/Time	Sample Interval PID (ppm) Recovery Strattgraphy					Water-level	(dassification ALL PERCENTAGI	LITHOLOGIC DESCRIPTION, color, moisture, density, grain ES ARE APPROXIMATE UNLE	size/plasticity, of	iher) E STATED	Well construction details				
				_	0		Concrete No Recovery								
					1		No Recovery								
					2										
					3		ilt, black, dry, loose, trace gravel, (concrete?) FILL								
		3.5			4		You block was stiff medarate planticity strang netrology edge (III)								
1305	\times			-	5	+	Clay, black, wet, stiff, moderate plasticity, strong petroleum odor FILL No Recovery								
					3		No Recovery .								
					6		Clay, black, moist, stiff, mo	Clay, black, moist, stiff, moderate plasticity, petroleum odor							
					7										
					8		-								
		_			9										
1315	\times	9			10	\vdash	same as above, bluish gra	y							
	_				11	_									
					12	+-									
<u></u>					13		-								
1320	X	25			14										
					15			-							
				_	16										
					18		Clay, light bluish brown, ma	olslt, very stiff, moderate plastici	ty, faint petroleui	m odar					
					19										
1330	\sim	2.4		-	20	┼-	same as above, brown, no	odor							
					~	1									

Page 1 of 2

58-44 **1**14

C		Ī	THE						BORINGAVELL	. IO:			
enviro	nemar	nal .	Sou	JR	CE (ir	OUP, INC.			SB-44			
PROJE	CT NA	ME A	DOA ON	RES	S :	AB&	l Foundry		Project No.	01-ABI-001			
BORING	LOC.	OITA	N (AT ST	TE):					Lägged By:	Nathan Colton			
CONTR	ACTO	R AN	D EQUIP	MEN	T:	WDO	C Geopirobe 7730DT						
SAMPL	ING M	ETH	:םכ			325	continuous	MONITORING DEVICE:	MiniRae 2000				
START	DATE	/ (TIN	IE):			7/10	/08 630	FINISH DATE/ TIME	7/10/2008				
FIRST V	VATER	₹ (BG	is):					STABILIZED WATER LEVEL:					
SURFA	CE EL	EVA	rion:				,	CASING TOP ELEVATION:					
TOTAL	BORIN	NG D	EPTH(S):			35		BORING DIAMETER/DEPTH:	4" 35`				
Date/Time	Date/Time Sample Interval PID (ppm) Recovery Stratigraphy					Water-level		LITHOLOGIC DESCRIPTI n, color, maisture, density, grain CENTAGES ARE APPROXIMAT	size/plasticity, o		Well construction details		
					20		Gravelly Clay, medium brown, 1/4" aubangular, moist, no odor Gravelly Sand, dark brown, wet, loose, medium-grained, 1/2" subangular, well graded, no odo						
					21		Gravelly Sand, dark brown, wet, loose, medium-grained, 1/2" subangular, well graded, no odor Gravelly Clay, dark brown, moist, stiff, low plasticity, no odor						
					22								
					23		Clay, medium brown, moist, stiff, moderate plasticity, no odor						
1340	\boxtimes		_		24								
					25								
					26								
					27						,		
					28			•					
					29			vn, wel, medium-grained, loose,	poorly graded, r	o odor, trace	1		
					30		gravel, 1/2" subangular Heaving sands encounter	red at 30' (10 feet of dual wall	core filled with	sand)	-		
					31								
					32								
					33								
		٥			34								
					35								
					36	_							
					38								
1618					39	_							
	\boxtimes	<u> </u>				_					1		
					40								

		1	HE			_	_		BORINGWELL	, ID:		
enviro	nemno	lal	Sol	JR(CE (ìR	OUP, INC.		S	B-45		
PROJE	CT NA	ME AN	D ADI	RESS	3:	AB&	l Foundry		Project No.	01-ABI-001		
BORING									Logged By:	Nathan Colto	n	
CONTR					T:	WDO	C Geoprobe 7730DT		44 - 7	AP 10 MIA TO		
SAMPLI							continuous	MON)TORING DEVICE:	MiniRae 2000			
START				_		_	/08 630	FINISH DATE/ TIME	7/10/2008			
FIRST V								STABILIZED WATER LEVEL:				
SURFAC					_	1		CASING TOP ELEVATION:		-		
OTAL						35'		BORING DIAMETER/DEPTH:	A" 35'			
				Ĭ T		-		BONNO DIAMETRIOSE III.	[- 30		=	
Date/Time	Sample Interval PID (ppm) Recovery Stratigraphy					Water-level		LITHOLOGIC DESCRIPTION, color, moisture, density, grain ES ARE APPROXIMATE UNLES	size/plasticity, of		Well construction	
					0		Concrete	-	_			
					1		Gravelly Clay, very dark gr	ay, maist, soft, low plasticity, no	odor (fill)			
					2		Silt, dark gray, moist, loose, petroleum odor Clay, dark grayish black, moist, stiff, low plasticity, petroleum odor, trace concrete pieces					
					3			, moist, sun, low plasucity, pe	aroleum odor, i	race concrete		
1305	\times	3.5			4							
					5							
					6							
					7		Clay, dark bluish gray, moi	st, stiff, moderate plasticity, no o	dor			
		-			8		name es aboue some elle	(Silk, Place)				
1315	\boxtimes	9_			10		same as above, some silt ((Silty Clayr)				
					11		Silty Clay, bluish gray, trac	a gravel, moist, stiff, low plastich	y, petroleum oda	of.		
					12			medium-grained, 1/2" subangula				
					13							
1320		25			14		Clay, medium brown, mois	t, stiff, moderate plasticity, no oc	lor			
					15							
					16							
_					18							
					19		Sandy Clay, bluish gray, fir	ne-grained, loose, poorly graded	, petroleum odor			
		2.4				I	1	-			1	

6		<u>. T</u>	THE						BORING/WELL II	D;	
enviro	D Man	tal		IR	CE (ìR	DUP, INC.		s	B-45	
PROJEC	T NA	ME A	ND ADD	RESS	: :	AB&	l Foundry		Project No.	01-ABI-001	
BORING	LOC	ATIO	N (AT SI	TE):					Logged By:	Nathan Colton	
CONTR	ACTO	RAN	D EQUIP	MEN	T:	WDO	Geoprobe 7730DT			_	
SAMPLI	NG MI	ETHO	DD;			325 (continuous	MONITORING DEVICE:	MiniRae 2000		
START	DATE	(TIM	E):			7/10/	08 630	FINISH DATE/ TIME	7/10/2008		
FIRST		_						STABILIZED WATER LEVEL:			
SURFAC								CASING TOP ELEVATION:			
TOTAL	BORIN	IG DI	EPTH(S):			35'		BORING DIAMETER/DEPTH:	4" 35'		
Date/Time	Sample Interval	PID (ppm)	Recovery	Stratigraphy	Depth (feat)	Water-level	(classification ALL PERC	LITHOLOGIC DESCRIPTI	size/plasticity, oth	er)	Well construction details
				19861	20						
					20						
					21		Gravelly Sand, medium bro	wn, medium-grained, wel, well (graded, no odor, 3/	/4" 6Ubangular	
					22						
				23							
	40 2			24							
1340	340			25							
	25		26								
					27						
					28						
					29			·			
					30		Heaving sands encounter	ed at 30' (10 feet of dual wall	core filled with sa	ind)	
					31						
					33						
		0			34						
			-		35						
					36						
					37						
					38						
1618					39						
					40						

		1	THE						BORINGWELL	. ID:				
envire		(8)	Sol	IR	CE (ìR	OUP, INC.		S	B-46				
PROJE	CT NA	ME AN	D ADD	RES	S:	AB&	l Foundry		Project No.	01-ABI-001				
BORING	3 LOC	ATION	(AT SI	TE):					Logged By:	Nathan Collo	n			
CONTR	ACTO	RAND	EQUIP	MEN	IT:	WDC	Geoprobe 7730DT	ź <u>-</u>		-				
SAMPL	ING MI	OHTE	D:			325	continuous	MONITORING DEVICE:	MiniRae 2000					
START	DATE/	(TIME): 			7/10/	/08 1200	FINISH DATE/ TIME	7/10/08 1430					
FIRST	VATER	BGS) :					STABILIZED WATER LEVEL:						
SURFA	CE ELI	EVAT	ON:				-	CASING TOP ELEVATION:						
TOTAL	BORIN	IG DEF	PTH[S]	:		45'		BORING DIAMETER/DEPTH:	4" 45'					
Date/Time	Sample Interval	PiD (ppm)	Recovery	Stratigraphy	O Depth (feet)	Water-level	ALL PERCENTAGE	LITHOLOGIC DESCRIPTION, COLOR, MOISTURE, DESCRIPTION OF LINES ARE APPROXIMATE UNLES	síze/plasticity, oti SS OTHERWISE	STATED	Well construction details			
					2		Clay, very dark brown, mois (concrete?) FILL	st, medium stiffness, moderate p	olasticity, no odor	r, trace gravel	1			
					3									
					5 6		do Recovery							
					7		Silty Sand, olive brown, fine	e-grained, wet, loose, well grade	d, no odor					
					9	l	Clay, very dark grayish blad	k, stiff, moderate plasticity, spe	cks of brown silt,	no odor	1			
					10									
					12		same as above, grayish bro	own, soft, sticky clay						
					13									
					15		Na Recovery							
					16		Gravelly Clay, medium gray	yish brown, wet soft 1/4" suban	gular, no odor		1			
					17		same as above, stiff, moist	, low plasticity, no odor, some se	and, fine-grained					
					19									
					20									

		$\overline{\Pi}$	THE						BORINGWELL	L ID:	
enviro	onmer.	otal	Soi	JR	CE (R	ove, Inc.		:	SB-46	
PROJE	CT NA	ME A	ND ADD	RESS	S:	AB&	l Foundry		Project No.	01-ABI-001	\neg
BORING	S LOC	OITA	N (AT SI	TE):				Logged By:	Nathan Colton		
CONTR	ACTO	R AN	D EQUIP	MEN	T:	WDO	C Geoprobe 7730DT		•		
SAMPL							continuous	MiniRae 2000			
START	DATE	(TIM	IE):				/08 1200	FINISH DATE/ TIME	7/10/08 1430		
FIRST								STABILIZED WATER LEVEL:			
SURFA								CASING TOP ELEVATION:			
TOTAL	BORIN	NG DE	EPTH(S)	:		45'	_	BORING DIAMETER/DEPTH:	4" 45'		
Date/Time	(terval					Water-level	(classificatio ALL PER(LITHOLOGIC DESCRIPTI n. color, molsture, density, grain CENTAGES ARE APPROXIMAT	size/plasticity, o	Mell construction	details
		7			20		Clay, medium brown, stiff,	moist, moderate plasficity, no od	or		
					21						
					22						
					23		sama as above, organīc m	alter (rools)			
					25						
		2			26	_					
					27	_					
					28						
					29	-					
					30						
		4.4			31						
			_		32						
					33						
					34 35		anna ao ahan sarah sarah	6 made at a state to the			
		2			36		Gravelly Clay, 1/4"-1/2"	ft, moderate plasticity, no odd	- -		
					37	-		55521 (go:lo:			
					38		Sand, fine-grained, wet,no	odor, trace gravel, 1/4"-1/2" sub	angular,	_	
					39		Clay, dark gray, moist, s	tiff, moderate plasticity, no oc	dor		
					40	_					

C	<u></u>	1	THE						BORINGWELL	ID:	
enviro	nmer	nta)	So	JRO	CE (A	oup, Inc.	5	SB-46		
PROJEC	T NA	ME A	DDA DM	RESS	3;	AB&	l Foundry		Project No.	01-ABI-001	
BORING									Logged By:	Nathan Cotton	
CONTR				MEN	<u> </u>		Geoprobe 7730DT				
SAMPLI			_			325	continuous I	MONITORING DEVICE:	MiniRae 2000		
START						7/10/	08 1200	FINISH DATE/ TIME	7/10/08 1430		
FIRST V								STABILIZED WATER LEVEL:			
SURFACE ELEVATION:								CASING TOP ELEVATION:			_
TOTAL	BORIN	ig Di	PTH(S)	:		45		BORING DIAMETER/DEPTH:	4" 45'		-
Date/Time	Sample Interval	PID (ppm)	Recovery	Stratigraphy	Ospth (feet)	Water-level		LITHOLOGIC DESCRIPTI , color, moisture, density, grain :NTAGES ARE APPROXIMAT	size/plasticity, of		Well construction details
		Ö.5			40		Clay, dark brown, very stiff (lough drilling), moist, moderale	plasticity, no odd	or	_
					41						
					43						
					44						
					45		Refusal at 45'				-
					46	<u> </u>					
					47						
					48						
					49						
					50						
					51						
				_	52			,			
				_	54						
					55						
					56						
					57	-					
					58	-					
					59	1					
					60	1					

Page 3 of 3

\$8-48.75

C			THE						BORING/WELL	ID:	
өпийг	onmen			JR	CE (GR	OUP, INC.		S	B-47	
PROJE	CT NA	WE AN	D ADD	RES	S :	AB&	I Foundry		Project No.	o. 01-A8I-001	
BORIN	G LOCA	ATION	(AT SI	TE):				Logged By:	Nathan Colto	n	
CONTR	ACTO	R AND	EQUI	PMEN	IT;	WDO	C Geoprobe 7730DT				
SAMPL	ING ME	ETHO) .:			325	continuous	MiniRae. 2000			
START	START DATE/ (TIME):						/08 635	FINISH DATE/TIME	7/11/08 930		
FIRST	NATER	(BGS):				`	STABILIZED WATER LEVEL:			
SURFA	CE EL	EVATION	ON:					CASING TOP ELEVATION:			
TOTAL	BORIN	G DE	PTH(S)	<u>;</u>		44.		BORING DIAMETER/DEPTH:	4" 44'		
Date/Time	Sample Interval	PJD (ppm)	Recovery	Stratigraphy	Depth (feet)	Waterlevel		LITHOLOGIC DESCRIPTION COLOR, MOISTURE, DESCRIPTION COLOR, MOISTURE, DESCRIPTION COLOR (NECESTRE LA PEROXIMATE UNLES	size/plasticity, of		Well construction
			40		1		Gravelly Clay, dark gray, di	ry, stiff, low plasticity, no odor, so	ome sitt		
		2.6	100		2 3 4 5 6 7 8 9 10		same as above, medium b	y, stiff, moist, low plasticity, no o stiff, moderate plasticity			
713	×	36	100		13 14 15		same as above, no gravel				
715	×	0,9			17 18 19			n, fine-grained, wet, loose, no oc moderate plasticity, no odor	dor, trace gravel,	1'4" round	


58-47 xts Page 1 of 3


C		Ī	THE						BORINGWELL	ID:				
enviro	vimen vimen	lal		IR	GE (BR	DIIP, INC.		S	B-47				
PROJEC	T NA	ME A	ND ADD	ress	S :	AB8	Foundry		Project No.	01-ABI-001				
BORING	LOC	ΑΠΟ	N (AT SI	TE):				Logged By:	Nathan Colton					
CONTR	ACTO	RAN	D EQUIP	MEN	T;	WDO	C Geopratie 7730BT							
SAMPLI	NG MI	ETHO	D:			325	2001กับอยล	MiniRae 2000						
STARY	DATE	(TIM	E):			7/11/	68 635	FINISH DATE/ TIME	7/11/08 930					
FIRST V	VATER	(BG	S):					STABILIZED WATER LEVEL:						
SURFACE ELEVATION:								CASING TOP ELEVATION:						
TOTAL	BORIN	IG DE	PTH(S)	:		44'		BORING DIAMETER/DEPTH:	4" 44'					
Date/Time	Sample Interval	P(D (ppm)	Recovery	Stratigraphy	Depth (test)	Water-level	LITHOLOGIC DESCRIPTION (dassification, color, moisture, density, grain size/plasticity, other) ALL PERCENTAGES ARE APPROXIMATE UNLESS OTHE							
			100		20		Sandy Gravel, medium bro odor	wn, weł, medlum-grained, 1/4" -	1/2" subangular,	well graded, no				
					21									
					22]							
					23		Clayey Gravel, medium brown, moist to wet, stiff, 1/2" - 3/4" subangular, no odor							
		0.4			24	-								
			100		25	├─	1							
			100		26	 								
			•	and a	27									
					28		Clay, medium brown, moist	, stiff, moderate plasticity, no od	or					
					29	\vdash	1							
		0.3			30									
			100		31									
					32									
					33									
					34									
	,		100		35 36	ļ								
					37	_								
					38									
					39	\vdash								
				ATITUTE	40	T					1			


C		$\overline{\Pi}$	THE						BORINGWELL	ID:	
enviro	nmer	stal	Sol	JRI	CE (RE	oup, Inc.	S	B-47		
PROJEC	CT NA	ME A	ND ADD	RESS	3:	AB&	Foundry		Project No.	01-ABI-001	
			N (AT SI					Logged By:	Nathan Colton		
			D EQUIP	MEN	T:	WDC	Geoprobe 7730DT				
5AMPLI						+		MONITORING DEVICE:	MiniRae 2000		
START			_			7/11/	08 635	7/11/08 930			
FIRST V								STABILIZED WATER LEVEL:			
SURFAC						<u> </u>	_	CASING TOP ELEVATION:			
TOTAL	AL BORING DEPTH(S):					44'	I	BORING DIAMETER/DEPTH:	4" 44'		
Dale/Time	Sample Interval	PiD (ppm)	Recovery	Stratigraphy	Depth (feet)	Water-fevel	(classificatio ALL PERC	LITHOLOGIC DESCRIPTI n, color, moislure, density, grain ENTAGES ARE APPROXIMAT	size/plasticity, otl	ner) :R	Well construction getails
			80		40		same as above				
					41						
					42						
		1.4			43						
			-		44		Refusal at 44'				
					45						
					46						
					47						
					48						
					49						
					50						
					51						
				_	52						l
					53						
					54						
	<u> </u>				55						
					56					ı	
					57					Į	
					58	 				,	
					59					'	
					60						


0			THE						BORINGWELL	ID;	
envire	nmen	(A)	Spi	JR	CE (R	DUP, INC.	s	B-48		
PROJEC	CT NAME AND ADDRESS:					AB8I	Foundry		Project No.	01-ABI-001	
BORING	RING LOCATION (AT SITE):							Logged By:	Nathan Colton		
CONTR	ACTO	R AND	EQUIP	MEN	IT:	WDC	Geoprobe 7730DT				
SAMPL	NG M	ETHO):			325	antinuous	MONITORING DEVICE:	MiniRae 2000		
START	DATE	(TIME	:):			7/11/	08 945	FINISH DATE/ TIME	7/11/08 1200		
FIRST V	VATER	BGS) :		_			STABILIZED WATER LEVEL:			
SURFA	CE ELI	EVATION	ON:					CASING TOP ELEVATION:			
TOTAL	BORIN	IG DEF	PTH(S)	į		29.5		BORING DIAMETER/DEPTH:	4" 29.5'		
Date/Time	Sample Inferval	PID (ppm)	Кесочегу	Stratigraphy	Depth (feet)	Water-level	(classification ALL PERCENTAGE	LITHOLOGIC DESCRIPTION, color, moisture, density, grain ES ARE APPROXIMATE UNLES	size/plasticity, att	ner) STATED	Well construction details
					٥						
					1		no soil samples collected 0	-20 ft bgs. See boring SB-22 fo	r lithology.		
					2						
					3						
					5						
					6	<u> </u>					
					7						
					8						
					9						
					10						
					11	-					
				_	12						
					13						
					14						
					15						
					16						
					17						
					18						
					19						
					20						

SOURCE GROUP, INC. PROJECT NAME AND ADDRESS: ASBI Foundry BORING LOCATION (AT SITE): CONTRACTOR AND EQUIPMENT: SAMPLING METHOD: START CATE (TIME): 7/11/08 945 PROJECT GROUP AND THE CONTRACTOR AND EQUIPMENT: SAMPLING METHOD: START CATE (TIME): 7/11/08 945 PROJECT GROUP AND THE CONTRACTOR AND EQUIPMENT: SURFACE ELEVATION: TOTAL BORING DEPTH(S): 29 5 BORING DEMETER(DEPTH): 100 100 100 100 100 100 100 1			T	THE		_	_			BORINGWELL	ID:			
PROJECT NAME AND ADDRESS: ABBI Foundry Project No. 01-ABI-001 BORING LOCATION (AT SITE): Legged By: Nathan Collon CONTRACTOR AND EQUIPMENT: 325 continuous Monitroring Device: Minister 2000 SAMPLING METHOD: 325 continuous MONITORING DEVICE: Minister 2000 START DATE (TIME): 7/11/08 945 FINISH DATE/TIME 7/11/08 1200 PRST WATER (BOS): STABILIZED WATER LEVEL: SURFACE ELEVATION: CASING TOP ELEVATION: CASING TOP ELEVATION: TOTAL BORING DEPTH(S): 29.5' BORING DAME FERVICE STABILIZED WATER LEVEL: 100 20 Clay, diversity of the control	S		194	Sni	IR	CF (R	OUP INC		5	B-48			
BORING LOCATION (AT SITE): CONTRACTOR AND EQUIPMENT: START DATE (TIME): PRIST WATER (BGS): SURFACE ELEVATION: TOTAL BORING DEPTH(S): 29 5' Clay, clive brown, moist, soft, moderate plasticity, no odor 21 Sandy Clay, dark gray, moist, soft, moderate plasticity, no odor 23 Clay, race sand, medium brown, wet, 1/4" subangular, no odor 24 Clay, race sand, medium brown, soff, fine-grained, no odor 26 Gravelly Clay, grayish brown, wet, 1/4" subangular, well graded, no odor 27 Clay, race sand, medium brown, soff, fine-grained, no odor 28 Gravelly Clay, grayish brown, wet, 1/4" subangular, well graded, no odor 29 Sand, clive brown, coanse-grained. 1/2" subangular, well graded, no odor 29 Sand, clive brown, coanse-grained. 1/2" subangular, well graded, no odor 29 Sand, clive brown, coanse-grained. 1/2" subangular, well graded, no odor 29 Sand, clive brown, coanse-grained. 1/2" subangular, well graded, no odor 29 Sand, clive brown, coanse-grained. 1/2" subangular, well graded, no odor 29 Sand, clive brown, coanse-grained. 1/2" subangular, well graded, no odor 29 Sand, clive brown, coanse-grained. 1/2" subangular, well graded, no odor 20 Sand, clive brown, coanse-grained. 1/2" subangular, well graded, no odor 20 Sand, clive brown, coanse-grained. 1/2" subangular, well graded, no odor 30 30 30 30 30 30 30 30 30 30 30 30 30 3							_							
CONTRACTOR AND EQUIPMENT: SAMPLING METHOD: 335 continuous MONITORING DEVICE: MiniRae 2000 7/11/08 945 FIRST WATER (BGS): STABLIZED WATER (EBG): STABLOATE (TIME): OCASING TOP ELEVATION: TOTAL BORING DEPTH(S): 22.5' BORING DAMETERDEPTH:) ;	A8&	i Foundry			-			
SAMPLING METHOD: 325 continuous MONTORING DEVICE: MiniRage 2000						T:	wat	C Geographe 7730DT	Logged Ly.	I VEDIANI CONON				
									MONITORING DEVICE:	MiniRae 2000				
FIRST WATER (BGS): SURFACE ELEVATION: TOTAL BORING DEPTH(S): 29 5' BORING DIAMETER/DEPTH: 4" 29.5' ROSING TOP ELEVATION: 100 29 5' BORING DIAMETER/DEPTH: 4" 29.5' ROSING TOP ELEVATION: 100 20 Clay, dive brown, moist, soft, moderate plasticity, other) ALL PERCENTAGES ARE APPROXIMATE UNLESS OTHE 21 100 21 Clay, dark gray, moist, soft, moderate plasticity, medium-grained, no odor, trace gravel, 14" subangular 22 1 Clay, medium brown, moist, siff, moderate plasticity, no odor 23 23 25 Clay, medium brown, moist, siff, moderate plasticity, no odor 24 Clay, grayish brown, wet, 1/4" subangular, no odor 25 Clay, gravelly Clay, grayish brown, wet, 1/4" subangular, no odor 26 Clay, gravelly Clay, grayish brown, wet, 1/4" subangular, no odor 27 Clayer Gravell, dark gray, wet, some sand, coarse-grained 28 Clay, trace sand, medium brown, stiff, fine-grained, no odor 29 Sand, dive prown, coarse-grained, 1/2" subangular, well grades, no odor Refusal at 29.5" Refusal at 29.5"	START	DATE	/ (TIM	lE):			_							
TOTAL BORING DEPTH(S): 29.5' BORING DIAMETER/DEPTH: 4" 29.5' LITHOLOGIC DESCRIPTION (classification, color, moisture, density, grain size/plasticity, other) ALL PERCENTAGES ARE APPROXIMATE UNLESS OTHE 100 20 Clay, dirk gray, moist, soft, moderate plasticity, no odor 21 Sandy Clay, dark gray, moist, soft, moderate plasticity, no odor 22 Clay, medium brown, moist, siff, moderate plasticity, no odor 23 Clay, medium brown, moist, siff, moderate plasticity, no odor 24 Clay, medium brown, moist, siff, moderate plasticity, no odor 25 Clay, grayish brown, wet, 1/4" subangular, no odor 26 Clay, trace sand, medium brown, stiff, fine-grained, no odor 27 Clayer Gravel, dark gray, wet, some sand, coarse-grained 28 Clay, trace sand, medium brown, stiff, fine-grained, no odor 29 Sand, clive brown, coarse-grained. 1/2" subangular, well graded, no odor Refusal at 29.5' 30 33 33 34 35 37 37 38 38 39 39 39 39 39 39 39 39 39 39 39 39 39									STABILIZED WATER LEVEL:					
Section Page	SURFAC	CE EL	EVAT	TION:					CASING TOP ELEVATION:					
100 20 Clay, olive brown, moist, soft, moderate plasticity, no odor 21 Sandy Clay, dark gray, moist, soft, moderate plasticity, medium-grained, no odor, trace gravel, 1/4" subangular Clay, medium brown, moist, aliff, moderate plasticity, no odor 23 24 25 26 Gravelly Clay, grayish brown, wet, 1/4" subangular, no odor 27 Clayey Gravel, dark gray, wet, some sand, coarse-grained Clay, trace sand, medium brown, stiff, fine-grained, no odor 29 Sand, olive brown, coarse-grained, 1/2" subangular, well graded, no odor Refusal at 29.5" 31 32 33 34 35 36 37 36 37 38 39 39 39 39	TOTAL	BORIN	IG DI	EPTH(S):	<u>:</u>		29.5	-	BORING DIAMETER/DEPTH:	4" 29.5'				
Clay, clay, dark gray, moist, soft, moderate plasticity, medium-grained, no odor, trace gravel, 1/4" subangular Clay, medium brown, moist, sliff, moderate plasticity, no odor Clay, medium brown, moist, sliff, moderate plasticity, no odor 23 24 Clay, medium brown, moist, sliff, moderate plasticity, no odor 25 Clay, grayish brown, wet, 1/4" subangular, no odor Clayer Gravell, dark gray, wet, some sand, coarse-grained Clay, trace sand, medium brown, stiff, fine-grained, no odor Page Sand, olive brown, coarse-grained, 1/2" subangular, well graded, no odor Refusal at 29.5" 31 32 33 34 35 36 37 38 39 39 39 39 39	Date/Time	Sample Interval	PID (ppm)	Recovery	Stratigraphy	Depth (feet)	Water-level	LITHOLOGIC DESCRIPTION (classification, color, moisture, density, grain size/plasticity, other) ALL PERCENTAGES ARE APPROXIMATE UNLESS OTHE						
1/4" subangular Clay, medium brown, moist, atiff, moderate plasticity, no odor 23 24 25 26 Gravelly Clay, grayish brown, wet, 1/4" subangular, no odor Clayer Gravel, dark gray, wet, some sand, coarse-grained Clay, trace sand, medium brown, stiff, fine-grained, no odor 29 Sand, olive brown, coarse-grained, 1/2" subangular, well graded, no odor Refusal at 29.5" 31 32 33 34 35 36 37 38 39				100		. 20		Clay, olive brown, moist, so	oft, moderate pleaticity, no odor					
C(ay, medium brown, moist, sliff, moderate plasticity, no odor 24 25 26 Gravelly Clay, grayish brown, wet, 1/4" subangular, no odor 27 Clayey Gravel, dark gray, wet, some sand, coarse-grained Clay, trace sand, medium brown, sliff, fine-grained, no odor 29 Sand, olive brown, coarse-grained, 1/2" subangular, well graded, no odor Refusal at 29.5' 30 31 32 33 34 35 36 37 38 39														
1.3						22		Clay modition house maint atiff moderate plantists an edge						
1.3 25 26 Gravelly Clay, grayish brown, wet, 1/4" subangular, no odor 27 Clayey Gravel, dark gray, wet, some sand, coarse-grained 28 Clay, trace sand, medium brown, stiff, fine-grained, no odor 29 Sand, olive brown, coarse-grained, 1/2" subangular, well graded, no odor Refusal at 29.5' 30 31 32 33 34 35 36 37 38 39 39						23		Cray, medium prown, moist, stiff, moderate plasticity, no odor						
Gravelly Clay, grayish brown, wel, 1/4" subangular, no odor Clayey Gravel, dark gray, wet, some sand, coarse-grained Clay, trace sand, medium brown, stiff, fine-grained, no odor Sand, olive brown, coarse-grained, 1/2" subangular, well graded, no odor Refusal at 29.5' 30 31 32 33 34 35 36 37 38 39			1.3			24								
Clayey Gravel, dark gray, wet, some sand, coarse-grained 28 Clay, trace sand, medium brown, stiff, fine-grained, no odor 29 Sand, olive brown, coarse-grained, 1/2" subangular, well graded, no odor Refusal at 29.5' 30 31 32 33 34 35 36 37 38						25								
Clayey Gravel, dark gray, wet, some sand, coarse-grained Clay, trace sand, medium brown, stiff, fine-grained, no odor Sand, clive brown, coarse-grained, 1/2" subangular, well graded, no odor Refusal at 29.5' 31 32 33 34 35 36 37 38								Gravelly Clay, grayish br	own, wet, 1/4" subangular, r	o odor				
28 Clay, trace sand, medium brown, stiff, fine-grained, no odor 29 Sand, olive brown, coerse-grained, 1/2" subangular, well graded, no odor Refusal at 29.5" 31 32 33 34 34 35 36 36 39 39						27		Clause Control dode need to				-		
Refusal at 29.5' 30 31 32 33 34 35 36 37 38 39						28				o odor		1		
30 31 32 33 34 35 36 37 38 39			_		1	29	 	Sand, clive brown, coarse-	grained, 1/2" subangular, well g	raded, no odor				
32 33 34 35 36 37 38						30		Refusal at 29.5'						
34 35 36 37 38 39						31								
34 35 36 37 38 39					-	32								
35 36 37 38 39						33		•						
36 37 38 39														
38 39														
38														
						39								
	40											-		









Recording Requested By:

McWane, Inc. c/o Mike Olvera, AB&I Foundry 7825 San Luandro Street Oakland, California 94621-2598

15

15 PGS

When Recorded, Mail To:

Ariu Levi, Director Alameda County Environmental Health Services 1131 Harbor Bay Parkway Alameda, California 94502

COVENANT AND ENVIRONMENTAL RESTRICTION ON PROPERTY

AB&1 Foundry 7825 San Leandro Street Oakland, California

This Covenant and Environmental Restriction	on Property (this "Covenant") is made as of
the 21st day of September, 2011 by McWane	. Inc. ("Covenantor") who is the Owner of
record of that certain property situated at 7825 Sar	n Leandro Street, in the City of _ Oakland
, County of Alameda	State of California, which is more
particularly described in Exhibit A attached hereto	and incorporated herein by this reference
(such portion hereinafter referred to as the "Burder	ned Property"), for the benefit of the Alameda
County Environmental Health Services (the "Cour	nty"), with reference to the following facts:

- A. The Burdened Property and groundwater underlying the property contains hazardous materials.
- B. Contamination of the Burdened Property. Soil at the Burdened Property was contaminated by previous industrial operations, including but not limited to the manufacture of cast pipe and fittings and warehousing operations and by releases from six underground fuel storage tanks formerly present at the Burdened Property. These operations resulted in contamination of soil and groundwater with organic chemicals including petroleum hydrocarbons, primarily benzene, toluene, ethylbenzene, and xylene; and chlorinated solvents, primarily 1,1,1-TCA, 1,1-dichloroethane (1,1-DCA), 1,1-dichloroethene (1,1-DCE), chloroethane, cis-and trans-1,2-dichloroethene (1,2-DCE), and vinyl chloride. These constituents constitute hazardous materials as that term is defined in Health & Safety Code Section 25260. To treat and control migration of contaminated soil and groundwater, several remedial actions were conducted at the Burdened Property including excavation and off-site disposal of contaminated

soil in the immediate vicinity of the UST areas and implementation of an enhanced biodegradation injection program.

- C. Exposure Pathways. The contaminants addressed in this Covenant are present in soil and groundwater on the Burdened Property. Without the mitigation measures which have been performed on the Burdened Property, exposure to these contaminants could take place via exposure during future soil excavation resulting in dermal contact, inhalation, or ingestion by humans. The risk of public exposure to the contaminants has been substantially lessened by the remediation and controls described herein.
- D. Adjacent Land Uses and Population Potentially Affected. The Burdened Property is used for the manufacture of cast pipe and fittings and warehousing operations and is adjacent to industrial and commercial land uses and is adjacent to industrial and commercial land uses land uses.
- E. Full and voluntary disclosure to the County of the presence of hazardous materials on the Burdened Property has been made and extensive sampling of the Burdened Property has been conducted.
- F. Covenantor desires and intends that in order to benefit the County, and to protect the present and future public health and safety, the Burdened Property shall be used in such a manner as to avoid potential harm to persons or property that may result from hazardous materials that may have been deposited on portions of the Burdened Property.

ARTICLE I GENERAL PROVISIONS

- 1.1 Provisions to Run with the Land. This Covenant sets forth protective provisions, covenants, conditions and restrictions (collectively referred to as "Restrictions") upon and subject to which the Burdened Property and every portion thereof shall be improved, held, used, occupied, leased, sold, hypothecated, encumbered, and/or conveyed. The restrictions set forth in Article III are reasonably necessary to protect present and future human health and safety or the environment as a result of the presence on the land of hazardous materials. Each and all of the Restrictions shall run with the land, and pass with each and every portion of the Burdened Property, and shall apply to, inure to the benefit of, and bind the respective successors in interest thereof, for the benefit of the County and all Owners and Occupants. Each and all of the Restrictions are imposed upon the entire Burdened Property unless expressly stated as applicable to a specific portion of the Burdened Property. Each and all of the Restrictions run with the land pursuant to section 1471 of the Civil Code. Each and all of the Restrictions are enforceable by the County.
- 1.2 Concurrence of Owners and Lessees Presumed. All purchasers, lessees, or possessors of any portion of the Burdened Property shall be deemed by their purchase, leasing, or possession of such Burdened Property, to be in accord with the foregoing and to agree for and among themselves, their heirs, successors, and assignees, and the agents, employees, and lessees of such owners, heirs, successors, and assignees, that the Restrictions as herein established must be adhered to for the benefit of the County and the Owners and Occupants of the Burdened Property

and that the interest of the Owners and Occupants of the Burdened Property shall be subject to the Restrictions contained herein.

- 1.3 <u>Incorporation into Deeds and Leases</u>. Covenantor desires and covenants that the Restrictions set out herein shall be incorporated in and attached to each and all deeds and leases of any portion of the Burdened Property. Recordation of this Covenant shall be deemed binding on all successors, assigns, and lessees, regardless of whether a copy of this Covenant and Agreement has been attached to or incorporated into any given deed or lease.
- 1.4 <u>Purpose</u>. It is the purpose of this instrument to convey to the County real property rights, which will run with the land, to facilitate the remediation of past environmental contamination and to protect human health and the environment by reducing the risk of exposure to residual hazardous materials.

ARTICLE II DEFINITIONS

- 2.1 County. "County" shall mean the Alameda County Environmental Health Services and shall include its successor agencies, if any.
- 2.2 <u>Improvements</u>. "Improvements" shall mean all buildings, roads, driveways, regradings, and paved parking areas, constructed or placed upon any portion of the Burdened Property.
- 2.3 Occupants. "Occupants" shall mean Owners and those persons entitled by ownership, leasehold, or other legal relationship to the exclusive right to use and/or occupy all or any portion of the Burdened Property.
- 2.4 Owner or Owners. "Owner" or "Owners" shall mean the Covenantor and/or its successors in interest, who hold title to all or any portion of the Burdened Property.

ARTICLE III DEVELOPMENT, USE AND CONVEYANCE OF THE BURDENED PROPERTY

- 3.1 <u>Restrictions on Development and Use</u>. Covenantor promises to restrict the use of the Burdened Property as follows:
 - a. Development of the Burdened Property shall be restricted to industrial;
 - b. No residence for human habitation shall be permitted on the Burdened Property;
 - c. No hospitals shall be permitted on the Burdened Property:

- d. No schools for persons under 21 years of age shall be permitted on the Burdened Property;
- e. No day care centers for children or day care centers for Senior Citizens shall be permitted on the Burdened Property;
- f. No Owners or Occupants of the Property or any portion thereof shall conduct any excavation work on the Property, unless expressly permitted in writing by the County. Any contaminated soils brought to the surface by grading, excavation, trenching, or backfilling shall be managed by Covenantor or his agent in accordance with all applicable provisions of local, state and federal law. Notwithstanding the foregoing, Covenantor may perform routine landscaping and maintenance of surface improvements thereon;
- g. All uses and development of the Burdened Property shall be consistent with any applicable County Cleanup Order or Risk Management Plan, each of which is hereby incorporated by reference including future amendments thereto. All uses and development shall preserve the integrity of any cap, any remedial measures taken or remedial equipment installed, and any groundwater monitoring system installed on the Burdened Property pursuant to the requirements of the County, unless otherwise expressly permitted in writing by the County.
- h. With the exception of the use of the one existing onsite water supply well for industrial water supply, no Owners or Occupants of the Property or any portion thereof shall drill, bore, otherwise construct, or use a well for the purpose of extracting water for any use, including but not limited to, domestic, potable, or industrial uses, unless expressly permitted in writing by the County.
- i. The Owner shall notify the County of each of the following: (1) The type, cause, location and date of any disturbance to any cap, any remedial measures taken or remedial equipment installed, and of the groundwater monitoring system installed on the Burdened Property pursuant to the requirements of the County, which could affect the ability of such cap or remedial measures, remedial equipment, or monitoring system to perform their respective functions and (2) the type and date of repair of such disturbance. Notification to the County shall be made by registered mail within ten (10) working days of both the discovery of such disturbance and the completion of repairs;
- j. The Covenantor agrees that the County, and/or any persons acting pursuant to County cleanup orders, shall have reasonable access to the Burdened Property for the purposes of inspection, surveillance, maintenance, or monitoring, as provided for in Division 7 of the Water Code.
- k. No Owner or Occupant of the Burdened Property shall act in any manner that will aggravate or contribute to the existing environmental conditions of the Burdened Property. All use and development of the Burdened Property shall preserve the integrity of any capped areas.
- 1. No Owner or Occupant of the Burdened Property shall use the Burdened Property to grow fruits or vegetables for consumption.

- 3.2 <u>Enforcement</u>. Failure of an Owner or Occupant to comply with any of the restrictions, as set forth in paragraph 3.1, shall be grounds for the County, by reason of this Covenant, to have the authority to require that the Owner modify or remove any Improvements constructed in violation of that paragraph. Violation of the Covenant shall be grounds for the County to file civil actions against the Owner as provided by law.
- 3.3 Notice in Agreements. After the date of recordation hereof, all Owners and Occupants shall execute a written instrument which shall accompany all purchase agreements or leases relating to the property. Any such instrument shall contain the following statement:

The land described he	erein contains hazardous material	ls in soils and in the
ground water under the p	property, and is subject to a deed	restriction dated as
of, 7	2011, and recorded on	, 2011, in
the Official Records of	County, California	, as Document No.
, which Cov	venant and Restriction imposes	certain covenants,
conditions, and restrictio	ons on usage of the property design	cribed herein. This
statement is not a declara	ition that a hazard exists.	

ARTICLE IV VARIANCE AND TERMINATION

- 4.1 <u>Variance</u>. Any Owner or, with the Owner's consent, any Occupant of the Burdened Property or any portion thereof may apply to the County for a written variance from the provisions of this Covenant.
- 4.2 <u>Termination</u>. Any Owner or, with the Owner's consent, any Occupant of the Burdened Property or a portion thereof may apply to the County for a termination of the Restrictions as they apply to all or any portion of the Burdened Property.
- 4.3 <u>Term</u>. Unless terminated in accordance with paragraph 4.2 above, by law or otherwise, this Covenant shall continue in effect in perpetuity.

ARTICLE V MISCELLANEOUS

- 5.1 No Dedication Intended. Nothing set forth herein shall be construed to be a gift or dedication, or offer of a gift or dedication, of the Burdened Property or any portion thereof to the general public.
- 5.2 <u>Notices</u>. Whenever any person gives or serves any notice, demand, or other communication with respect to this Covenant, each such notice, demand, or other communication shall be in writing and shall be deemed effective (1) when delivered, if

personally delivered to the person being served or official of a government agency being served, or (2) three (3) business days after deposit in the mail if mailed by United States mail, postage paid certified, return receipt requested:

If To: "Covenantor"
McWane, Inc.
c/o Mike Olvera
AB&I Foundry
7825 San Leandro Street
Oakland, California 94621-2598

If To: "County"

Alameda County Environmental Health Services

Attention: Director

1131 Harbor Bay Parkway

Alameda, California 94502

- 5.3 <u>Partial Invalidity</u>. If any portion of the Restrictions or terms set forth herein is determined to be invalid for any reason, the remaining portion shall remain in full force and effect as if such portion had not been included herein.
- 5.4 <u>Article Headings</u>. Headings at the beginning of each numbered article of this Covenant are solely for the convenience of the parties and are not a part of the Covenant.
- 5.5 Recordation. This instrument shall be executed by the Covenantor and by the Director of Environmental Health Services. This instrument shall be recorded by the Covenantor in the County of within ten (10) days of the date of execution.
 - 5.6 References. All references to Code sections include successor provisions.
- 5.7 Construction. Any general rule of construction to the contrary notwithstanding, this instrument shall be liberally construed in favor of the Covenant to effect the purpose of this instrument and the policy and purpose of the Water Code. If any provision of this instrument is found to be ambiguous, an interpretation consistent with the purpose of this instrument that would render the provision valid shall be favored over any interpretation that would render it invalid.

M WIT	INESS WHEREOF, the parties execute this Covenant as of the date set forth above.
Covena	INESS WHEREOF, the parties execute this Covenant as of the date set forth above. antor: WCWAND Incorporated
Ву:	But Wint
Title:	Up am weware Corporation
Date: _	9-21-11
	KYRT WINTER 6

DOCSSVI-35004 1/ro0092 ab&s draft deed restriction 2011-07-20.doc 11-29-00

Agency:

Alameda County Environmental Health Services

By:____

Title: Director

Date: 1/17 21, 2 1/1

ARIV LEVI

STATE OF CALIFORNIA COUNTY OF ALAMEDA

On 09-21-, 2011 before me, the undersigned a Notary Public in and for said state, personally appeared [Covenantor], personally known to me or proved to me on the basis of satisfactory evidence to be the person who executed the within instrument.

WITNESS my hand and official seal. Notary Public in and for said County and State SUNIL JASWAL Commission # 1883191 Notary Public - Galifornia Alameda County

My Gomm, Expires Apr 2, 2014

Stale of California, County of On 09-21-2011 before me,_ Molary Public, personally appeared to be the person(s) who proved to me on the basis of satisfactory evidence to be the person(s) whose name(s) is/one subscribed to the within instrument and acknowledged to me that he/sheithey executed the same in his/her/their authorized capacityles), and that by his/her/their signature(s) on the instrument the person(s), or the entity upon behalf of which the person(s) acted, executed the instrument I certify under PENALTY OF PERJURY under the laws of the State of California that the foregoing paragraph is true and correct. WITNESS my hand and official seal.

STATE OF CALIFORNIA

COUNTY OF ALAMEDA

On <u>09-21</u> - 2011 before me, the undersigned a Notary Public in and for said state, personally appeared [DIRECTOR], personally known to me or proved to me on the basis of satisfactory evidence to be the person who executed the within instrument.

WITNESS my hand and official seal.

Notary Public in and for said

County and State

SUNIL JASWAL Commission # 1883191 Notary Public - California Alameda County

My Comm. Expires Apr 2, 2014

State of California. County of On 09-21-211 before me,

Notary Public, personally appeared who proved to me on the basis of solistoctory evidence to be the person(s) whose name(s) islare subscribed to the within Instrument and acknowledged to me that he/she/they executed the same in his/he/fiheir authorized copacity(les). and that by his/her/their signature(s) on the instrument the person(s), or the entity upon behalf of which the person(s) acted, executed the instrument.

I certify under PENALTY OF PERJURY under the laws of the State of California that the foregoing paragraph is live and correct.

WITNESS my hand and official seal.

I Jamel, way Rhi

STATE LAS WAS Commission 1883) 21
Commission 1883) 21
Votary Public California
Algoria Capity
MyCommission 1862

SUNC JASWAL Commission in 1883191 Nectary Popine Calcarnia

**Alamenta Caupity

**My committee April - -

EXHIBIT A

LEGAL DESCRIPTION OF PROPERTY

Parcel 2:

COMMENCING AT THE INTERSECTION OF THE SOUTHEASTERN LINE OF 77TH AVENUE WITH THE SOUTHWESTERN LINE OF SAN LEANDRO STREET, AS SAID SOUTHWESTERN LINE IS DESCRIBED IN THE DEED FROM H. SORENSEN TO SAN FRANCISCO BAY AREA TRANSIT DISTRICT, RECORDED DECEMBER 9, 1966, REEL 1885, IMAGE 513 OF OPPICIAL RECORDS OF ALAMEDA COUNTY, INSTROMENT NO. AY/137604; THENCE ALONG SAID SOUTHWESTERN LINE OF SAN LEANDRO STREET, SOUTH 44° 24' 56" EAST, 199.26 PEBT; THENCE ALONG THE ARC OF A TANGENT CURVE TO THE RIGHT HAVING A RADIUS OF 5953.01 FRET, THROUGH A CENTRAL ANGLE OF 0° 27' 26", AN ARC DISTANCE OF 47.52 PRET TO THE ACTUAL POINT OF BEGINNING OF THIS DESCRIPTION; THENCE FROM SAID POINT, SOUTH 52° 17' 11' WEST, S10.14 PRET TO THE NORTHEASTERN LINE OF THE LANDS OF CENTRAL PACIFIC RAILWAY COMPANY; THENCE ALONG SAID NORTHEASTERN LINE, SOUTH 41° 16' 08" EAST, 103.97 FEBT TO THE NORTHWESTERN LINE OF THE PARCEL OF LAND DESCRIBED IN THE DEED TO AMERICAN BRASS AND IRON FOUNDRY; THENCE ALONG SAID NORTHWESTERN LIME, NORTH 52° 03' 12" EAST, 513.94 FEBT TO A POINT ON THE SOUTHWESTERN LINE OF SAN LEANDRO STREET, FROM SAID POINT THE CENTER OF A TANGENT CURVE TO THE LEFT, HAVING A RADIUS OF 595J.01 FEET BEARS SOUTH 47° 01' 31" WEST; THENCE ALONG SAID CURVE, THROUGH A CENTRAL ANGLE OF 0° 59' 01", AN ARC DISTANCE OF 102.20 PRET BACK TO THE POINT OF BEGINNING.

EXCEPTING THEREFROM, ALL TANGIBLE IMPROVEMENTS BXISTING ON JUNE 15, 2006, INCLUDING, WITHOUT RESERVATION, ALL BUILDINGS, POUNDATIONS, FOOTINGS, STRUCTURAL ATTACHMENTS, PAVING AND FLOORING, AND OTHER PHYSICAL ACCESSIONS OF EVERY KIND AND NATURE, THAT ARE LOCATED ON, UNDER OR ABOVE THE GROUND SURFACE OF THE REAL PROPERTY DESCRIBED AS PARCELS 1, 2, 3 AND 4 OF THE DEEDS RECORDED JUNE 29, 2006, INSTRUMENT NO. 2006249865 AND OCTOBER 30, 2006, INSTRUMENT NO. 2006404171, OFFICIAL RECORDS, AS RESERVED BY DEED FROM ABLI, A CALIFORNIA CORPORATION, RECORDED JUNE 29, 2006, AS INSTRUMENT NO. 2006249865, OFFICIAL RECORDS, AND CORRECTED BY "CORRECTION GRANT DEED" RECORDED OCTOBER 30, 2006, AS INSTRUMENT NO. 2006404171, OFFICIAL RECORDS.

ASSESSOR'S PARCEL NO. 041-4209-001-01

Parcel 3:

BEGINNING AT A POINT ON THE SOUTHWESTERN LINE OF SAN LEANDRO STREET, AS SAID STREET EXISTED PRIOR TO THE WIDENING THEREOF TO 80 FEBT, DISTANT THEREON SOUTH 44° 12' EAST, 392.13 FEET FROM THE SOUTHEASTERN LINE OF 77TH AVENUE, AS SAID AVENUE EXISTED PRIOR TO JULY 25, 1945; THENCE ALONG SAID LINE OF SAN LEANDRO STREET, SOUTH 44° 12' RAST, 156.85 FEET; THENCE SOUTH 50° 15' WEST, 388.65 FEET TO THE NORTHEASTERN LINE OF THE PARCEL OF LAND DESCRIBED IN THE DEED FROM E. G. NEILSON AND LUCY L. NEILSON TO ARNOLD A. BOSCACCI, ET AL, DATED APRIL 24, 1942, RECORDED MAY 18, 1942, BOOK 4220 OR, PAGE 222, ALAMEDA COUNTY RECORDS; THENCE ALONG THE LAST NAMED LINE, SOUTH 43° 06' BAST, 80 FEET TO THE SOUTHEASTERN LINE OF SAID LAND DESCRIBED IN SAID DEED; THENCE ALONG THE LAST NAMED LINE, SOUTH 50° 15' WEST, 170 FEET TO THE NORTHEASTERN LINE OF THE PARCEL OF LAND FIRSTLY DESCRIBED IN THE DEED BY W. K. WASHBURN AND M. B. WASHBURN TO CENTRAL PACIFIC RAILWAY COMPANY AND WESTERN PACIFIC RAILROAD COMPANY, DATED APRIL 8, 1929. RECORDED IN BOOK 2092 OR, PAGE 383, ALAMEDA COUNTY RECORDS; THENCE ALONG THE LAST NAMED LINE, NORTH 43° 06' WEST, 236.65 FEET TO A LINE DRAWN SOUTH 50° 15' WEST FROM THE POINT OF BEGINNING; THENCE NORTH 50° 15' EAST, 555.58 FEET TO THE POINT OF BEGINNING.

EXCEPTING THEREFROM, THE NORTHEASTERN 30 FEET THEREOF, TAKEN FOR THE WIDENING OF SAN LEANDRO STREET, AS SAID STREET NOW EXISTS 80 FEET WIDE, SINCE JUNE 26, 1947.

ALSO EXCEPTING THEREFROM, THE FOLLOWING DESCRIBED REAL PROPERTY:

COMMENCING AT THE INTERSECTION OF THE SOUTHEASTERN LINE OF 77TH AVENUE WITH THE SOUTHWESTERN LINE OF SAN LEANDRO STREET, AS SAID AVENUE AND SAID STREET NOW EXIST; THENCE ALONG THE SOUTHWESTERN LINE OF SAN LEANDRO STREET, SOUTH 42° 23' 40" EAST, 347.97 FEET TO THE TRUE POINT OF BEGINNING, SAID POINT LYING ON THE SOUTHEASTERN LINE OF A PARCEL OF LAND DESCRIBED IN THE DEED BY BANK OF AMERICA NATIONAL TRUST AND SAVINGS ASSOCIATION TO H. A. SORENSEN, DATED FEBRUARY 20, 1939, RECORDED FEBRUARY 25, 1939, BOOK 3740 OR, PAGE 240, ALAMEDA COUNTY RECORDS; THENCE CONTINUING ALONG THE SOUTHWESTERN LINE OF SAN LEANDRO STREET, SOUTH 42° 23' 40" EAST, 156.84 PEET; THENCE LEAVING SAID SOUTHWESTERN LINE OF SAN LEANDRO STREET, SOUTH 52° 03' 20" WEST, 11.12 FEET; THENCE NORTH 42° 22' 28" WEST, 94.48 FEET; THENCE ALONG A TANGENT CURVE TO THE LEFT HAVING A RADIUS OF 5,953.01 FEET, THROUGH A CENTRAL ANGLE OF 0° 36' 01", AN ARC DISTANCE OF 62.37 PEET TO THE AFOREMENTIONED SOUTHEASTERN LINE (3740 OR 40); THENCE ALONG SAID SOUTHEASTERN LINE, NORTH 52° 03' 20" BAST, 11.39 FEET TO THE TRUE POINT OF BEGINNING.

ALSO EXCEPTING THEREFROM, ALL TANGIBLE IMPROVEMENTS EXISTING ON JUNE 15, 2006, INCLUDING, WITHOUT RESERVATION, ALL BUILDINGS, FOUNDATIONS, FOOTINGS, STRUCTURAL ATTACHMENTS, PAVING AND FLOORING, AND OTHER PHYSICAL ACCESSIONS OF EVERY KIND AND NATURE, THAT ARE LOCATED ON, UNDER OR ABOVE THE GROUND SURFACE OF THE REAL PROPERTY DESCRIBED AS PARCELS 1, 2, 3 AND 4 OF THE DEEDS RECORDED JUNE 29, 2006, INSTRUMENT NO. 2006249865 AND OCTOBER 30, 2006 AS INSTRUMENT NO. 2006404171, OFFICIAL RECORDS, AS RESERVED BY DEED FROM AB&I, A CALIFORNIA CORPORATION, RECORDED JUNE 29, 2006, AS INSTRUMENT NO. 2006249865, OFFICIAL RECORDS, AND CORRECTED BY "CORRECTION GRANT DEED" RECORDED OCTOBER 30, 2006, AS INSTRUMENT NO, 2006404171, OFFICIAL RECORDS.

ASSESSOR'S PARCEL NO. 041-4209-003-02

Parcel 4:

BEGINNING AT A POINT ON THE SOUTHWESTERN LINE OF SAN LEANDRO STREET, DISTANT THEREON SOUTH 44° 12' EAST, 548.98 FEET FROM THE SOUTHEASTERN LINE OF 77TH AVENUE; THENCE ALONG SAID LINE OF SAN LEANDRO STREET, SOUTH 44° 12' 3AST, 153.13 FEET TO THE NORTHWESTERN LINE OF 81ST AVENUE, AS SAID AVENUE IS DESCRIBED IN THE DEED FROM R. D. AYER AND OLIVO TO THE CITY OF OAKLAND, DATED JANUARY 16, 1914 AND RECORDED FEBRUARY 3, 1914, IN BOOK 2231 OF DEEDS, PAGE 60, IN THE OFFICE OF THE COUNTY RECORDER OF ALAMEDA COUNTY, STATE OF CALIFORNIA; THENCE ALONG THE LAST NAMED LINE, SOUTH 50° 15' WEST, 561.59 FEET TO THE NORTHEASTERN LINE OF LANT CONVEYED BY W. K. WASHBURN AND M. E. WASHBURN TO CENTRAL PACIFIC RAILWAY COMPANY AND THE WESTERN PACIFIC RAILROAD COMPANY, BY DEED DATED APRIL 8, 1929 AND RECORDED APRIL 20, 1929, IN BOOK 2092 OF OFFICIAL RECORDS OF ALAMEDA COUNTY, AT PAGE 383; THENCE ALONG THE LAST NAMED LINE, NORTH 43° 06' WEST, 152.93 FEET TO A LINE DRAWN SOUTH 50° 15' WEST FROM THE POINT OF BEGINNING; THENCE NORTH 50° 15' EAST, 558.65 FEET TO THE POINT OF BEGINNING.

BXCEPTING THEREFROM, THE POLLOWING:

BEGINNING AT THE INTERSECTION OF THE SOUTHWESTERN LINE OF SAN LEANDRO STREET WITH THE NORTHWESTERN LINE OF 81ST AVENUE, AS SAID STREET AND AVENUE NOW EXIST; THENCE ALONG SAID SOUTHWESTERN LINE OF SAN LEANDRO STREET, NORTH 42° 23′ 40° WEST, 152.77 FEET TO THE SOUTHEASTERN LINE OF A PARCEL OF LAND DESCRIBED IN THE DEED BY BANK OF AMERICA NATIONAL TRUST AND SAVINGS ASSOCIATION TO ARNOLD A. BOSCACCI AND RITA M. BOSCACCI, DATED NOVEMBER 25, 1940, RCORDED IN BOOK 4011 OF OFFICIAL RECORDS OF ALAMEDA COUNTY, PAGE 112; THENCE LEAVING THE SOUTHWEST LINE OF SAN LEANDRO STREET AND RUNNING ALONG THE SOUTHEASTERN LINE OF SAID PARCEL (4011 OR 112), SOUTH 52° 03′ 20° WEST, 11.12 FEET; THENCE LEAVING SAID SOUTHEASTERN LINE, SOUTH 42° 22′ 28° EAST, 152.77 FEET TO THE NORTHWESTERN LINE OF 81ST STREET; THENCE ALONG SAID NORTHWESTERN LINE, NORTH 52° 03′ 20° EAST, 11.17 FEET TO THE POINT OF BEGINNING.

EXCEPTING THEREFROM, ALL THAT REAL PROPERTY DESCRIBED IN THE DEED FROM E. G. NEILSON, ET UX, TO ARNOLD A. BOSCACCI, ET UX, RECORDED MAY 18, 1942, IN BOOK 4220, PAGE 222, OFFICIAL RECORDS OF ALAMEDA COUNTY, CALIFORNIA.

ALSO EXCEPTING THEREFROM, ALL TANGIBLE IMPROVEMENTS EXISTING ON JUNE 15, 2006, INCLUDING, WITHOUT RESERVATION, ALL BUILDINGS, FOUNDATIONS, FOOTINGS, STRUCTURAL ATTACHMENTS, PAVING AND FLOORING, AND OTHER PHYSICAL ACCESSIONS OF EVERY KIND AND NATURE, THAT ARE LOCATED ON, UNDER OR ABOVE THE GROUND SURFACE OF THE REAL PROPERTY DESCRIBED AS PARCELS 1, 2, 3 AND 4 OF THE DEEDS RECORDED JUNE 29, 2006, INSTRUMENT NO. 2006249865 AND OCTOBER 30, 2006, AS INSTRUMENT NO, 2006404171, OFFICIAL RECORDS, AS RESERVED BY DEED FROM AB&I, A CALIFORNIA CORPORATION, RECORDED JUNE 29, 2006, AS INSTRUMENT NO. 2006249865, OFFICIAL RECORDS, AND CORRECTED BY "CORRECTION GRANT DEED" RECORDED OCTOBER 30, 2006, AS INSTRUMENT NO, 2006404171, OFFICIAL RECORDS.

ASSESSOR'S PARCEL NO. 041-4209-008-01 (PORTION)

Parcel 5:

A PORTION OF THAT CERTAIN PIECE OR PARCEL OF LAND HERETOFORE CONVEYED BY EMMA F. MATHEWS TO R. B. AYER, BY DEED DATWED MAY 23, 1912 AND RECORDED IN BOOK 2073 OF DEEDS, AT PAGE 155, RECORDS OF ALAMEDA COUNTY, CALIFORNIA, AND BEING A STRIP OF LAND, 60 FEET IN WIDTH, FURTHER DESCRIBED AS FOLLOWS:

BEGINNING AT THE POINT OF INTERSECTION OF THE SOUTHWESTERN LINE OF THE 80-FOOT RIGHT OF WAY OF THE WESTERN PACIFIC RILWAY (NOW SOUTHERN PACIFIC RAILWAY) WITH A LINE DRAWN PARALLEL TO AND DISTANT 700.00 FEET SOUTHEASTERLY (MEASURED AT RIGHT ANGLES) FROM THE SOUTHEASTERN LINE OF FITCHBURG, AS SAID FITCHBURG IS DELINEATED AND SO DESIGNATED ON THAT CERTAIN MAP ENTITLED, "MAP OF FITCHBURG", ETC., AND FILED IN THE OFFICE OF THE RECORDER OF ALAMEDA COUNTY, CALIFORNIA, JANUARY 25, 1870; AND RUNNING THENCE ALONG SAID LINE DRAWN PARALLEL TO SAID SOUTHEASTERN LINE OF FITCHBURG, SOUTH 50° 15' WEST, 631.09 FEET TO THE POINT OF INTERSECTION THEREOF WITH THE NORTHEASTERN LINE OF THE 100-FOOT RIGHT OF WAY OF THE CENTRAL PACIFIC RAILWAY; THENCE LEAVING SAID LINE SO DRAWN, PARALLEL TO THE SOUTHEASTERN LINE OF FITCHBURG AND ALONG SAID NORTHEASTERN RIGHT OF WAY LINE OF THE CENTRAL PACIFIC RAILWAY, SOUTH 43° 07' EAST, 60.11 FEET TO THE POINT OF INTERSECTION THEREOF WITH A LINE DRAWN PARALLEL TO AND DISTANT 760.00 FEET SOUTHEASTERLY (MEASURED AT RIGHT ANGLES) FROM SAID SOUTHBASTERN LINE OF FITCHBURG; THENCE LEAVING SAID RIGHT OF WAY LINE OF THE CENTRAL PACIFIC RAILWAY AND ALONG LAST SAID LINE DRAWN PARALLEL TO THE SOUTHEASTERN LINE OF FITCHBURG, NORTH 50° 15' EAST, 632.25 FEET TO THE POINT OF INTERSECTION THEREOF WITH THE SAID SOUTHWESTERN LINE OF THE 80 FOOT RIGHT OF WAY OF THE WESTERN PACIFIC RAILWAY; THENCE LEAVING SAID LAST PARALLEL LINE AND ALONG SAID SOUTHEASTERN RIGHT OF WAY LINE OF THE WESTERN PACIFIC RAILWAY, NORTH 44° 13' WEST, 60.13 FEET TO THE POINT OF BEGINNING.

EXCEPTING THEREFROM: THIS PORTION OF THE HEREIN DESCRIBED PARCEL LYING NORTHEASTERLY OF THE SOUTHWESTERN LINE OF SAN LEANDRO STREET, AS SAN LEANDRO STREET (FORMERLY RUSSETT STREET) IS DESCRIBED AND DEDICATED IN CERTAIN FINAL JUDGMENT IN CONDEMNATION, BEING ALSO ACTION NUMBER 82662 IN THE SUPERIOR COURT OF THE STATE OF CALIFORNIA, IN AND FOR THE COUNTY OF ALAMEDA, FILED UNDER RECORDER'S SERIES NUMBER Y 76189, OFFICIAL RECORDS, ALAMEDA COUNTY, CALIFORNIA.

ALSO EXCEPTING THEREFROM, ALL TANGIBLE IMPROVEMENTS EXISTING ON JUNE 15, 2006, INCLUDING, WITHOUT RESERVATION, ALL BUILDINGS, FOUNDATIONS, FOOTINGS, STRUCTURAL ATTACHMENTS, PAVING AND PLOORING, AND OTHER PHYSICAL ACCESSIONS OF EVERY KIND AND NATURE, THAT ARE LOCATED ON, UNDER OR ABOVE THE GROUND SURFACE OF THE REAL PROPERTY DESCRIBED AS PARCELS 1, 2, 3 AND 4 OF THE DEEDS RECORDED JUNE 29, 2006, INSTRUMENT NO. 2006249865 AND OCTOBER 30, 2006, AS INSTRUMENT NO. 2006404171, OFFICIAL RECORDS, AS RESERVED BY DEED FROM AB&I, A CALIFORNIA CORPORATION, RECORDED JUNE 29, 2006, AS INSTRUMENT NO. 2006249865, OFFICIAL RECORDS, AND CORRECTED BY "CORRECTION GRANT DEED" RECORDED OCTOBER 30, 2006, AS INSTRUMENT NO, 2006404171, OFFICIAL RECORDS.

ASSESSOR'S PARCEL NO. 041-4209-008-01 (PORTION)

Parcel 6:

BEGINNING AT THE INTERSECTION OF THE SOUTHEASTERN LINE OF 77TH AVENUE WITH THE SOUTHWESTERN LINE OF SAN LEANDRO STREET, AS SAID AVENUE AND STREET NOW EXIST; THENCE ALONG SAID LINE OF SAN LEANDRO STREET, SOUTH 44° 12' EAST, 347.99 FEET TO THE SOUTHEASTERN LINE OF THE PARCEL OF LAND DESCRIBED IN THE DEED BY BANK OF AMERICA NATIONAL TRUST AND SAVINGS ASSOCIATION TO H. A. SORENSEN, DATED FEBRUARY 20, 1939, RECORDED FEBRUARY 25, 1939, IN BOOK 3740 OF OFFICIAL RECORDS OF ALAMEDA COUNTY, PAGE 240; THENCE ALONG THE LAST NAMED LINE, SOUTH 50° 15' WEST, 525.49 FEET TO THE NORTHEASTERN LINE OF THE PARCEL OF LAND FIRSTLY DESCRIBED IN THE DEED BY W. K. WASHBURN, ET UX, TO CENTRAL PACIFIC RAILWAY COMPANY, ET AL, DATED APRIL 8, 1929, RECORDED APRIL 20, 1929, BOOK 2092 OF OFFICIAL RECORDS OF ALAMEDA COUNTY, PAGE 383; THENCE ALONG THE LAST NAMED LINE, NORTHWESTERLY 347.40 FEET TO SAID SOUTHEASTERN LINE OF 77TH AVENUE; THENCE ALONG THE LAST NAMED LINE, NORTHWESTERLY ON A CURVE TO THE RIGHT WITH A RADIUS OF 353 FEET, A DISTANCE OF 10.18 FEET, AND TANGENT WITH THE LAST NAMED COURSE, NORTH 50° 15' EAST, 508.67 FEET TO THE POINT OF BEGINNING.

EXCEPTING THEREFROM, THAT PORTION CONVEYED TO SAN FRANCISCO BAY AREA RAPID TRANSIT DISTRICT, DATED OCTOBER 4, 1966, RECORDED DECEMBER 9, 1966, REEL 1885, IMAGE 513, OFFICIAL RECORDS, INSTRUMENT NO. AY/137604.

EXCEPTING THEREFROM, ALL THAT REAL PROPERTY IN THE CITY OF OAKLAND, ALAMEDA COUNTY, STATE OF CALIFORNIA, DESCRIBED AS FOLLOWS:

COMMENCING AT THE INTERSECTION OF THE SOUTHEASTERN LINE OF 77TH AVENUE WITH THE SOUTHWESTERN LINE OF SAN LEANDRO STREET, AS SAID SOUTHWESTERN LINE IS DESCRIBED IN THE DEED FROM H. SORENSEN TO SAN FRANCISCO BAY AREA RAPID TRANSIT DISTRICT, RECORDED DECEMBER 9, 1966, REEL 1885, IMAGE 513, OF OFFICIAL RECORDS OF ALAMEDA COUNTY, INSTRUMENT NO. AY/137604; THENCE ALONG SAID SOUTHWESTERN LINE OF SAN LEANDRO STREET, SOUTH 44° 24' 56" EAST, 199.26 FEET; THENCE ALONG THE ARC OF A TANGENT CURVE TO THE RIGHT, HAVING A RADIUS OF 5953.01 FEET, THROUGH A CENTRAL ANGLE OF 0° 27' 26", AN ARC DISTANCE OF 47.52 FEET TO THE ACTUAL POINT OF BEGINNING OF THIS DESCRIPTION; THENCE PROM SAID POINT, SOUTH 52° 17' 11" WEST, 510.14 FEET TO THE NORTHEASTERN LINE OF THE LAND OF CENTRAL PACIFIC RAILWAY COMPANY; THENCE ALONG SAID NORTHEASTERN LINE, SOUTH 41° 16' 08" BAST, 103.97 FEET TO THE NORTHWESTERN LINE OF THE PARCEL OF LAND DESCRIBED IN THE DEED TO AMERICAN BRASS AND IRON FOUNDRY; THENCE ALONG SAID NORTHWESTERN LINE, NORTH 52° 03' 12" EAST, 513.94 FEET TO A POINT ON THE SOUTHWESTERN LINE OF SAN LEANDRO STREET, FROM SAID POINT THE CENTER OF A TANGENT CURVE TO THE LEFT, HAVING A RADIUS OF 5953.01 FEET, BEARS SOUTH 47° 01' 31" WEST; THENCE ALONG SAID CURVE, THROUGH A CENTRAL ANGLE OF 0° 59' 01", AN ARC DISTANCE OF 102.20 FEET BACK TO THE POINT OF BEGINNING.

ALSO EXCEPTING THEREFROM, ALL TANGIBLE IMPROVEMENTS EXISTING ON JUNE 15, 2006, INCLUDING, WITHOUT RESERVATION, ALL BUILDINGS, FOUNDATIONS, FOOTINGS, STRUCTURAL ATTACHMENTS, PAVING AND FLOORING, AND OTHER PHYSICAL ACCESSIONS OF EVERY KIND AND NATURE, THAT ARE LOCATED ON, UNDER OR ABOVE THE GROUND SURPACE OF THE REAL PROPERTY, AS RESERVED IN THE DEED FROM AB&I, A CALIFORNIA CORPORATION, RECORDED JUNE 29, 2006, AS INSTRUMENT NO. 2006249864, OFFICIAL RECORDS.

(parcel 6 continued on next page)

ALSO EXCEPTING THEREFROM. ALL TANGIBLE IMPROVEMENTS EXISTING ON OCTOBER 26. 2006, INCLUDING, WITHOUT RESERVATION, ALL BUILDINGS, FOUNDATIONS, FOOTINGS, STRUCTURAL ATTACHMENTS, PAVING AND FLOORING, AND OTHER PHYSICAL ACCESSIONS OF EVERY KIND AND NATURE, THAT ARE LOCATED ON, UNDER OR ABOVE THE GROUND SURPACE OF THE REAL PROPERTY, AS GRANTED IN THE DEED FROM BOSCACCI GROUP, LLC, A CALIFORNIA LIMITED LIABILITY COMPANY TO ABSI, A CALIFORNIA CORPORATION, RECORDED OCTOBER 30, 2006, AS INSTRUMENT NO. 2006404174, OFFICIAL RECORDS.

ASSESSOR'S PARCEL NO. 041-4209-001-02



Foundry/Corporate Office

Los Angeles Service Center

7825 San Leandro Street Oakland, CA 94621-2598 510/632-3467 510/632-8035 Fax 15006 Nelson Avenue City of Industry, CA 91744-4331 625/333-4882 626/333-8681 Fax

July 19, 2011

10:36 am, Jul 21, 2011 Alameda County

Environmental Health

RECEIVED

Mr. Jerry Wickham Hazardous Materials Specialist Alameda County Environmental Health 1131 Harbor Bay Parkway, Suite 250 Alameda, CA 94502-6577

Subject: Fuel Leak Case No. RO0000092 and Geotracker Global ID T0600100065 Revised

Site Management Plan, AB&I Foundry, 7825 San Leandro Street, Oakland

California 94621

Dear Mr. Wickham:

AB&I respectfully submits the attached Revised Site Management Plan for the AB&I Foundry Site located at 7825 San Leandro Street, Oakland, California.

I declare, under penalty of perjury, that the information and/or recommendations contained in the attached document are true and correct to the best of my knowledge.

Sincerely,

Dave Robinson Engineering Manager

Attachment: Revised Site Management Plan, AB&I Foundry, 7825 San Leandro Street, Oakland,

California

REVISED SITE MANAGEMENT PLAN

AB&I Foundry 7825 San Leandro Street Oakland, California 01-ABI.001

Prepared For.



Prepared By:



3451-C Vincent Road Pleasant Hill, California 94523

July 19, 2011

Prepared By:

Kent R. Reynolds

Principal Geologist

Reviewed By:

Andrew Zdon, P.G., C.HG.

Principal Hydrogeologist

TABLE OF CONTENTS

LIST	OF FIG	URE\$	PAGE ii
LIST	OF TAE	BLES	ii
CERT	IFICAT	ION	iii
1.0	INTR	ODUCTION	1-1
	1.1	Site Location and Description	
	1.2	Purpose and Objectives	.,1-2
2.0	BACK	(GROUND	2-1
	2.1	Site Operational History	
	2.2	Hydrogeologic Setting	
	2.3	Summary of Remedial Actions and Current Environmental Conditions	2-2
3.0	Sumr	nary of Human Health Risks	3-1
		3.1.1 Potential Sources	
		3.1.2 Contaminant Migration Pathways	
		3.1.3 Potential Receptors and Exposure Pathways	
4.0	site M	MANAGEMENT ACTIVITIES	4-1
	4.1	General	
	4.2	Soil Management	
	4.3	Site Specific Health and Safety Plans	
	4.4	Soil Management Protocols	
		4.4.1 Soil Testing and Analytical Protocol	4-2
		4.4.2 Handling Procedures for Contaminated Soil	4-3
	4.5	Handling Procedures for Contaminated Groundwater	4-3
	4.6	Minimizing Soil and Groundwater Contact by Construction Workers	
	4.7	Site Control	
	4.8	Dust/Vapor Control Measures	
	4.9	Decontamination	
	4.10	Monitoring Wells	
	4.11 4.12	Storm Water ControlReporting	
	.		
5.0		ngency Plan	
	5.1 5.2	Implementation of Site Management PlanLimitations	
6.0	REFE	RENCES	6-1

LIST OF FIGURES

Figure 1	Site Location Map
Figure 2	Site Plan and Sampling Locations
Figure 3	Soil Sample Results - Former 10,000-Gallon Diesel UST Area - 2007
Figure 4	Soil Sample Results – Former 8,000-Gallon Mineral Spirits/1,1,1-TCA UST Area - 2007
Figure 5	Soil Sample Results - Former 550-Gallon Gasoline UST Area - 2007
Figure 6	Soil Sample Results - Three 10,000-Gallon USTs Area - 2007
Figure 7	Soil Gas Sample Results - 2007
Figure 8	Soil Gas Sample Results - 2008
Figure 9	Soil Gas Sample Results - 2009
Figure 10	Groundwater Analytical Results – TPHg, TPHd, & BTEX - 2007
Figure 11	Groundwater Analytical Results - Chlorinated VOCs - 2007
Figure 12	Groundwater Analytical Results – TPHg, TPHd, & BTEX – July 2010
Figure 13	Groundwater Analytical Results - Chlorinated VOCs - July 2010
Figure 14	Groundwater Analytical Results - TPHg, TPHd, & BTEX - December 2010
Figure 15	Groundwater Analytical Results - Chlorinated VOCs - December 2010

	LIST OF TABLES
Table 1	Summary of Soil Sample Results - Organics
Table 2	Summary of Soil Sample Results - Metals
Table 3	Groundwater Analytical Results Petroleum Hydrocarbon Related Constituents – Year 2009/2010
Table 4	Groundwater Analytical Results VOCs - Year 2009/2010

CERTIFICATION

All hydrogeologic and geologic information in this document regarding the AB&I Foundry Site have been prepared under the grand reviewed by the certified professional whose signature appears below.

12DON No. 348

Andrew Zdon, P.G., C.HG. Principal Hydrogeologist

The Settree Group, Inc.

1.0 INTRODUCTION

On behalf of AB&I Foundry (AB&I), The Source Group, Inc. (SGI) has prepared this Revised Site Management Plan (SMP) for the AB&I Site located at 7825 San Leandro Street in Oakland, California (Figure 1; Site).

This SMP has been prepared in response to a letter submitted to AB&I by Alameda County Environmental Health (ACEH) dated April 28, 2011 (ACEH, 2011a). The ACEH April 28, 2011 letter requests that "In order to prevent potential future exposure to residual contamination and move the site towards case closure, we request that you now submit a draft Covenant and Environmental Restriction on Property (Deed Restriction) along with a Site Management Plan (SMP)."

An administrative control in the form of a deed restriction will be implemented as part of the case closure. The deed restriction has been prepared under separate cover and specifies that the Site will be limited in development for industrial use. Article III, section 3.1, part f of the deed restriction states:

No Owners or Occupants of the Property or any portion thereof shall conduct any excavation work on the Property, unless expressly permitted in writing by the County. Any contaminated soils brought to the surface by grading, excavation, trenching, or backfilling shall be managed by Covenantor or his agent in accordance with all applicable provisions of local, state and federal law. Notwithstanding the foregoing, Covenantor may perform routine landscaping and maintenance of surface improvements thereon.

Consistent with the deed restriction, this SMP provides a framework to manage residual chemicals in soil at the Site in a manner that is: (1) satisfactory to ACEH and other regulatory agencies, (2) protective of human health and the environment, and (3) consistent with current land uses.

This Revised SMP replaces the Revised SMP dated June 15, 2011. The Revised SMP incorporates comments provided by ACEH in their letter dated June 8, 2011 (ACEH, 2011b) and subsequent verbal comments provided on July 12, 2011.

1.1 Site Location and Description

The Site is located at 7825 San Leandro Street, east of the intersection with 77th Avenue, in a light industrial area of Oakland (Figures 1 and 2). The Site is bounded by commercial/industrial properties to the north, south, east, and west. Union Pacific Railroad is located immediately adjacent to and west of the Site. Oakland Truck Stop is located immediately adjacent to and east of the Site. Elmhurst Creek is located along the southeast corner of the property (Figure 2). San

Leandro Bay is located approximately one mile west of the Site. The entire Site is covered with concrete and asphalt/concrete pavement.

1.2 Purpose and Objectives

The purpose of this SMP is to provide a plan to prevent or minimize human exposure to soil and groundwater contamination at the Site. This SMP was prepared to govern all future redevelopment and/or intrusive work at the Site such as soil excavation, trenching and backfilling activities.

2.0 BACKGROUND

This section provides information about subsurface conditions and remediation activities at the Site.

2.1 Site Operational History

AB&I have been operating at the Site location since at least 1930 (BSK Associates [BSK], 1993). Business activities include the manufacture of cast pipe and fittings. The facility accepts scrap iron and steel, which it stockpiles on-site, and uses during manufacturing activities. The Site encompasses an area of approximately 11.8 acres and contains various warehouses, manufacturing and office buildings. The entire Site is covered with buildings and asphalt/concrete pavement. Seven underground storage tanks (USTs) were previously located on the Site, including one 8,000-gallon UST used for storing unleaded gasoline, one 8,000-gallon UST used for the storage of mineral spirits and later 1,1,1-trichloroethane (1,1,1-TCA), one 550-gallon UST used for storing regular leaded gasoline, one 10,000-gallon UST used for storing diesel, and three 10,000-gallon USTs used for storing gasoline. All UST have been removed from the Site. UST removal activities were initiated in 1982 and completed in the early 1990s.

2.2 Hydrogeologic Setting

The Site is located near the San Francisco Bay within an area identified as the East Bay Plain. The East Bay Plain is situated on the east side of the San Francisco Bay depression. The alluvial sediments of the East Bay Plain consist of a mixture of gravel, sand and clay deposited by coalescing alluvial fans. In the vicinity of the Site, fluvial and near shore deposits have been mapped (Helley et. al., 1979). The fluvial deposits are described as unconsolidated, moderately sorted, fine sand and silt, with clayey silt and occasional thin beds of coarse sand (Muir, 1993). The near-shore deposits are described as a well-sorted, fine to medium grained sand and silt, with lenses of sandy clay and clay. Regional groundwater flow in the vicinity of the Site is interpreted to be towards the west - southwest toward San Leandro Bay.

The Site is underlain by a mixture of sandy/silty clay to a depth of at least 20-feet below ground surface (bgs). Groundwater has been encountered in borings and excavations at depths ranging from 3 to 8-feet bgs at the Site. Groundwater monitoring data from on-site monitoring wells generally flows to the northwest at a gradient of approximately 0.006 feet per foot (ft/ft); (SGI, 2009a).

2-1

2.3 Summary of Remedial Actions and Current Environmental Conditions

Initial site assessment activities began in 1991 as part of the facility's UST removal program. The USTs removed consisted of:

- three 10,000-gallon tanks used for storing gasoline (removed 1982/1983);
- one 550-gallon UST used for storing regular, leaded gasoline (removed 1991);
- one 8,000-gallon tank used for storing unleaded gasoline (removed 1991);
- one 8,000-gallon tank initially used for storing mineral spirits and later for storing 1,1,1-trichloroethane (removed 1991); and
- one 10,000-gallon tank used for storing diesel fuel (removed 1992).

Removal of the tanks, with the exception of the three 10,000-gallon gasoline USTs were provided in UST closure reports. The locations of the former USTs are identified on Figure 2.

In July/August 2006, a soil and groundwater assessment was conducted as part of a property transfer. The assessment consisted of sampling three existing monitoring wells (MW-1, MW-3, and MW-4); abandoning damaged well MW-2; and installing and sampling six new groundwater monitoring wells (MW-2R, and MW-5 through MW-9). Soil samples were collected at various depth intervals during the installation of monitoring wells MW-5, MW-6, MW-7, and MW-8. Results of the assessment were presented in the Preliminary Groundwater Investigation Report (BSK, 2007).

In response to a request from ACEH, additional soil, groundwater and soil vapor investigations were conducted in 2007, 2008, and 2009. These investigations included the investigation of shallow groundwater (less than 30 feet bgs) and deep groundwater (greater than 30 feet bgs), and the collection of soil vapor samples. The results of these investigations indicated that shallow groundwater in the vicinity of the Parking Lot Area (located in the vicinity and northwest of well MW-8; Figure 2) was impacted with chlorinated volatile organic compounds (VOCs), including 1,1,1-TCA, 1,1-dichloroethane (1,1-DCA), 1,1-dichloroethene (1,1-DCE), chloroethane, cis-and trans-1,2-dichloroethene (1,2-DCE), and vinyl chloride. Shallow groundwater in the vicinity of the former three 10,000 gallon USTs area (located in the vicinity of well MW-9) was impacted with petroleum fuels including benzene, toluene, ethylbenzene and xylenes (BTEX), total petroleum hydrocarbons as gasoline (TPHg), and total petroleum hydrocarbons as diesel (TPHg). Results of the soil vapor analysis indicated that isolated soil gas samples had indoor air vapor intrusion environmental screening level (ESL) exceedences for benzene, ethylbenzene, vinyl chloride and tetrachloroethene (PCE) under the commercial land use scenario. A site specific risk assessment was conducted and results concluded that the risks posed by soil vapors were acceptable with respect to indoor air exposure under the industrial land use scenario and did not require further action. Further details can be found in SGI's reports titled, "Site Investigation Report," "Additional Site Investigation Report," and "Supplemental Soil Vapor Investigation Report" (SGI 2008a; SGI,

2008b, and SGI, 2009b). ACEH concurred with the report conclusions in a letter dated May 20, 2009.

In order to address residual petroleum hydrocarbons and VOCs in groundwater, enhanced anaerobic biodegradation (EAnB) injections occurred in June 2009 at the Site beneath the parking lot area (near MW-3 and MW-8) and aerobic biodegradation (EAB) injections occurred near the former three 10,000 gallon USTs (near MW-9). Since that time, groundwater monitoring has occurred to track the progress of bioremediation in the subsurface.

Soil sample results associated with the 2007 investigations are summarized in Tables 1 and 2 and Figures 3 through 6. Soil gas sample results for the investigations conducted in 2007, 2008, and 2009 are presented in Figures 7 though 9. Groundwater sample results associated with the 2007 investigations are presented in Figures 10 and 11. Groundwater monitoring well sample results conducted during 2009 and 2010 are summarized in Tables 3 and 4 and groundwater monitoring well sample results conducted during July and December 2010 are presented in Figures 12 through 15.

3.0 SUMMARY OF HUMAN HEALTH RISKS

This section presents a summary of a screening level risk evaluation (SLRE) that was conducted by SGI for the Site. The SLRE included the development of a conceptual site model that was used to evaluate the potential sources, contaminant migration pathways, and potential receptors for the petroleum hydrocarbons and VOCs within the area of and downgradient of the former mineral spirits/1,1,1-TCA UST and former three 10,000-Gallon USTs dispenser island area. The results of the SLRE are summarized below.

3.1.1 Potential Sources

The potential source(s) of contaminants released into the environment are interpreted to be leaks associated with the operation of the former mineral spirits/1,1,1-TCA UST and the former three 10,000-Gallon gasoline USTs dispenser island area.

Previous investigations related to the former mineral spirits/1,1,1-TCA UST removal and subsequent groundwater sampling have identified the presence of 1,1,1-TCA, chloroethane, 1,1-DCA, 1,1-DCE, and vinyl chloride in soil and, or groundwater in the immediate vicinity and downgradient (northwest) of the former mineral spirits/1,1,1-TCA UST (Figure 11). In addition, releases of TPH from the former three 10,000-Gallon gasoline USTs dispenser island area also appear to be commingling with and have impacted groundwater in the area of the former mineral spirits/1,1,1-TCA UST (Figure 10).

Groundwater underlying and south-southwest of the former three 10,000-Gallon gasoline USTs dispenser island area is impacted with TPHg, BTEX, and TPHd. The highest concentrations of TPHg, BTEX, and TPHd were reported in samples collected from beneath the storage goods warehouse, which is located south-southwest of the tank area (Figure 10). Higher concentrations of TPHg, BTEX, and TPHd in groundwater samples collected downgradient of the UST area suggest that excavation of the source area during the removal of the USTs was effective in reducing the source of contaminants to groundwater in the immediate vicinity of the USTs. The presence of elevated concentrations of TPHg, BTEX, and TPHd in groundwater underlying the storage goods warehouse is interpreted to be related to residual petroleum hydrocarbons that have migrated via groundwater flow from the former UST area.

The migration of TPH and chlorinated VOCs at the Site is interpreted to occur as a result of shallow groundwater flow. However, natural processes such as adsorption, dispersion, and natural degradation are expected to limit the horizontal and vertical extent of TPH and chlorinated VOCs. The primary source of the contaminants, leaks associated with discharges of TPH and chlorinated VOCs from the UST systems, have been terminated. Therefore, the only remaining sources are interpreted to be the affected soil beneath and downgradient of the USTs. As previously described

in Section 1.1, the entire Site is covered with concrete or asphalt/concrete (A/C) pavement. Therefore, there is currently no direct access to the affected soil.

3.1.2 Contaminant Migration Pathways

TPH tends to sorb to soil particles and can be transported from surface soils at the Site via dust generation or in surface water runoff. VOCs detected at the Site (e.g., chlorinated solvents or gasoline-range petroleum hydrocarbons) would not be expected to be present in surface soils, but can migrate downward from shallow soils to deeper soils under the force of gravity. VOCs could also migrate upward in soil vapor to indoor or outside air. In addition, these types of chemicals can migrate to underlying groundwater through leaching. Dissolved chlorinated solvents and petroleum hydrocarbons can also migrate with groundwater flow.

3.1.3 Potential Receptors and Exposure Pathways

The Site and surrounding areas are currently zoned for commercial/industrial use and they are expected to remain as such in the future. Therefore, the following receptors include:

- Hypothetical On-Site Outdoor Commercial/Industrial Worker Receptor (current and future exposure scenario);
- Hypothetical On-Site Indoor Commercial/Industrial Worker Receptor (current and future exposure scenario), and;
- Hypothetical On-Site and Off-Site Outdoor Construction Worker Receptor (current and future exposure scenario).

The exposure pathways assumed to be complete and significant for the hypothetical On-Site outdoor commercial/industrial and On-Site and Off-Site construction worker receptors include:

- Ingestion of soil;
- Dermal contact with soil; and
- Inhalation of dusts/vapors in outdoor air generated from soil and groundwater.

4.0 SITE MANAGEMENT ACTIVITIES

4.1 General

No excavation work shall be conducted at the Site, unless expressly permitted in writing by the ACEH. Any contaminated soils brought to the surface by grading, excavation, trenching, or backfilling shall be managed by the Site or his agent in accordance with all applicable provisions of local, state and federal law. Notwithstanding the foregoing, the Site may perform routine landscaping and maintenance of improvements thereon.

All uses and development shall preserve the integrity of any cap, any remedial measures taken or remedial equipment installed, and any groundwater monitoring system installed on the Site pursuant to the requirements of the ACEH, unless otherwise expressly permitted in writing by the ACEH. No additional buildings or other subsurface structures are to be constructed without the approval of ACEH.

With the exception of the existing onsite water supply well, no Owners or Occupants of the Site or any portion thereof shall drill, bore, otherwise construct, or use a well for the purpose of extracting water for any use, including but not limited to, domestic, potable, or industrial uses, unless expressly permitted in writing by the ACEH.

The Site shall notify the ACEH of each of the following: (1) The type, cause, location and date of any disturbance to any cap, any remedial measures taken or remedial equipment installed, and of the groundwater monitoring system installed on the Site pursuant to the requirements of the ACEH, which could affect the ability of such cap or remedial measures, remedial equipment, or monitoring system to perform their respective functions and (2) the type and date of repair of such disturbance. Notification to the ACEH shall be made by registered mail within ten (10) working days of both the discovery of such disturbance and the completion of repairs.

4.2 Soil Management

Soil management during construction addresses precautions that will be taken to mitigate risks to human health and the environment from identified chemicals during future redevelopment and/or intrusive activities at the Site such as soil excavation, trenching, new construction, site development, grading and utility repair. These precautions will include the following:

 Implementation of construction impact mitigation measures, including control of dust generation at the Site, decontamination of equipment, and prevention of storm water runoff; and Establishment of procedures to: (1) manage soil and groundwater on the Site during construction and (2) characterize soil if it is found to contain concentrations of TPH, VOCs, or metals in excess of State of California hazardous waste criteria or ESLs for commercial land use.

4.3 Site Specific Health and Safety Plans

During all activities involving disturbance of the surface cap or subsurface excavation, those workers that may directly contact soil or groundwater containing constituents of concern (VOCs, petroleum hydrocarbons, and metals) will perform these activities in accordance with a site-specific health and safety plan. The plan will be consistent with State and Federal Occupational Safety and Health Administration ("OSHA") standards for hazardous waste operations (CCR, Title 8, Section 5192 and 29 Code of Federal Regulations 1910.120, respectively). Among other things, the health and safety plan will include a description of health and safety training requirements for onsite construction workers, a description of the level of personal protective equipment to be used, if any, air quality monitoring plans, and any other applicable precautions to be undertaken. The health and safety Plan shall include procedures for handling soil and/or groundwater contaminated with VOCs, petroleum hydrocarbons, and/or metals.

4.4 Soil Management Protocols

Soil management protocols described in this section provide guidance for excavating and handling soil at the Site. The specific protocols to be followed when managing soil on the Site are summarized below:

- If soil is to be disposed offsite then sampling frequencies and test methods employed to characterize the soil will be determined by the disposal facility accepting the soil.
- If soil is to remain at the Site it must be tested to determine if TPH, VOCS, and metals are less than the appropriate screening levels for reuse.
- Testing of soil for reuse can be performed: (1) in advance of excavation by collecting soil samples from soil borings installed to the depth of the intended excavation or (2) during excavation by sampling excavated soil as stockpiles are being formed.

4.4.1 Soil Testing and Analytical Protocol

Soil intended for reuse will be sampled at an appropriate frequency in accordance with the Department of Toxic Substances Control (DTSCs) Information Advisory Clean Imported Fill Material (Advisory), dated October 2001 (DTSC 2001). A sampling grid will be established for each stockpile based on the volume of soil and minimum number of samples to be collected in accordance with DTSC's Advisory as follows:

- Stockpiles up to 1,000 cubic yards: 1 sample per 250 cubic yards.
- Stockpiles from 1,000 to 5,000 cubic yards: 4 samples for first 1000 cubic yards plus 1 sample per each additional 500 cubic yards.
- Stockpiles greater than 5,000 cubic yards: 12 samples for first 5,000 cubic yards plus 1 sample per each additional 1,000 cubic yards.

Stockpile samples will be collected by removing the surface soil (approximately 6-inches) followed by inserting a brass or stainless steel tube into the soil. Each sample container will be labeled, sealed, and placed on ice in a cooler. Samples will be transmitted under chain-of-custody procedures to a State of California certified laboratory. Soil samples will be analyzed for TPH, VOCs, and metals using EPA Methods 8015M, 8260B, and 6010. Soil samples that exceed ten times their respective soluble threshold limit concentration (STLC; metals) will also be analyzed using the waste extraction test (WET) to further assess the re-use of soil onsite. Soil that exceeds the STLC or commercial ESL will be disposed of offsite at an appropriate disposal facility.

Additional soil samples may also be collected from the stockpiled soil to aid in disposal. Soil samples in stockpiles will be collected at a frequency that is required by the disposal facility (landfill). Samples will be analyzed for additional analytes as required for disposal.

4.4.2 Handling Procedures for Contaminated Soil

The following handling procedures shall be followed during excavation activities.

- Any stockpiled soil shall be covered with plastic sheeting or tarps and will not be stockpiled in or near storm drains.
- Access to excavated areas shall be controlled to prevent unauthorized persons accessing exposed soil.
- Soil determined to be hazardous waste shall be disposed of offsite. Soil shall be transported under applicable U.S. and California Department of Transportation regulations. Current federal and state requirements should be reviewed prior to disposal of soil.

4.5 Handling Procedures for Contaminated Groundwater

VOCs and TPH at levels above ESLs have been detected in groundwater samples from the Site. Therefore, if any excavation activities require dewatering, water shall be stored in holding tanks and sampled in accordance with applicable laws and regulations for disposal.

Any project-related water associated with dewatering activities shall either discharge into the sanitary sewer, under permit with East Bay Municipal Utility District (EBMUD), or comply with the National Pollutant Discharge System (NPDES) permit regulations and an associated Storm Water

Pollution Prevention Plan (SWPPP) regarding discharge into storm drains. Such permit requirements typically include on-site treatment to remove pollutants prior to discharge. Alternatively, the water shall be temporarily stored onsite in holding tanks, pending off-site disposal at an approved disposal facility.

4.6 Minimizing Soil and Groundwater Contact by Construction Workers

There are potential health and safety risks associated with the petroleum hydrocarbons, VOCs, and metals detected in Site soils, as well as petroleum hydrocarbons and VOCs detected in groundwater. There is the potential for contact by construction workers with residual chemicals in soil at the Site. The routes of potential exposure to the petroleum hydrocarbons, VOCs, and metals in soil are: dermal (skin) contact with the soil; (2) inhalation of dusts; and (3) ingestion of the soil.

Groundwater occurs on-Site at a depth of 3 to 8 feet bgs. There is the potential for contact by construction workers with residual chemicals in groundwater at the Site. The routes of potential exposure to the petroleum hydrocarbons and VOCs in groundwater are: (1) dermal (skin) contact with groundwater; and (2) inhalation of emissions from exposed water. The greatest potential for human exposure to the petroleum hydrocarbons and VOCs in water will be during soil excavation operations and dewatering activities.

The abovementioned health risks to on-Site construction workers will be minimized by developing and implementing a site-specific health and safety plan. The Site Environmental Manager or representative overseeing removal actions will be responsible for establishing and maintaining proper health and safety procedures to minimize construction worker exposure to Site contaminants. At minimum, the site-specific health and safety plan will include: (1) health and safety training requirements for on-Site personnel; (2) personal hygiene and monitoring equipment to be used during construction to protect and verify the health and safety of the construction workers; (3) additional precautions to be undertaken to minimize direct contact with hazardous substances, including implementation of dust control measures; and (4) a description of the procedures to mitigate any potential health risk to bystanders during subsurface activities.

A Site health and safety officer (HSO) or designee will be on-Site during excavation activities to ensure that all health and safety measures are maintained. The HSO will have the authority to direct and, if necessary, stop all construction activities in order to ensure compliance with the site-specific health and safety plan.

4.7 Site Control

Access to the work zones where soil will be disturbed shall be controlled using caution tape, cones, fencing, steel plates, or other measures to clearly designate the active work area and to prevent access by the public. To minimize the migration of contaminated soils from the Site to

uncontaminated areas, excavated soil shall be covered and secured by temporary fences or other means to prevent unauthorized access.

4.8 Dust/Vapor Control Measures

Dust control measures will be implemented during construction activities at the Site to minimize the generation of dust. Dust generation that will be mitigated includes that associated with excavation activities, truck traffic, ambient wind traversing soil stockpiles, and loading of transportation vehicles.

Dust generation will be minimized using appropriate measures. These measures include but are not limited to the following:

- Mist or spray water while performing excavation activities and loading transportation vehicles:
- Limit vehicle speeds on the property to 5 miles per hour;
- Control excavation activities to minimize the generation of dust;
- Minimize drop heights while loading transportation vehicles; and
- Cover soil stockpiles, if present, with visqueen or tarps.

If the construction area is greater than 4 acres, use enhanced control measures as specified in Table 2 of the BAAQMD California Environmental Quality Act Guidelines (BAAQMD, 1999).

4.9 Decontamination

Decontamination procedures shall be developed by contractors to minimize the equipment contamination during excavation activities. The procedures should include removing loose soil from the vehicle exterior using dry methods, such as brushing, scraping or vacuuming. Soil not removed by dry methods, should be cleaned by pressure washing or steam cleaning. Water collected from the cleaning process should be sampled prior to disposal.

4.10 Monitoring Wells

All groundwater monitoring wells located onsite shall be protected during excavation and construction activities. A map showing the locations of wells currently on the property are shown on Figure 2. Any damage to these wells should be reported immediately. All the wells should be accessible to others during excavation and construction activities. Prior to removal or relocation of any wells, the ACEH shall be notified and well destruction or installation permits shall be obtained from Alameda County Department of Public Works.

4.11 Storm Water Control

Storm water pollution controls shall be implemented by construction contractors to minimize sediment runoff in storm water, which could include soil containing contaminants of concern. Prior to the initiation of the work, the contractors must follow the requirements of the CRWQCB general permit and other permits by the CRWQCB. Storm water pollution controls implemented at the Site will be based on best management practices, such as those described in the "Information on Erosion and Sediment Controls for Construction Projects: A Guidebook," Erosion and Sediment Control Field Manual (CRWQCB, 2002), and the Storm Water Best Management Practices Handbook (CSQA, 2003).

Procedures to prevent erosion and sediment runoff from the Site shall include grading the Site, installing storm water control devices such as temporary earth berms or erecting sllt fences around the perimeter of exposed soil at the Site. Straw bale barriers or sediment traps are required to protect the existing catch basins.

4.12 Reporting

After earthwork activities are complete, a report will be prepared to document the relocation and final disposition of soil reused or disposed of offsite. At a minimum, the report will include the dimensions of the excavation and confirmation sample locations. The analytical data will be provided in tables and a Site plan showing sampling locations and limits of excavation and grading will be presented. If applicable, copies of receipts pertaining to the disposition of the soil will be appended to the report.

5.0 CONTINGENCY PLAN

The following contingency plan shall be implemented to address unknown contamination during grading, trenching, and dewatering activities:

- All grading, trench excavation and filling operations, and dewatering operations shall be observed for the presence of free-phase petroleum products, chemicals, or contaminated soil/groundwater. Discolored soil or suspected contaminated soil shall be segregated from clean soil. In the event unexpected, contaminated soil or groundwater is encountered during construction, the contractor shall notify Site Environmental Manager. The Site Environmental Manager shall confirm the presence of the suspect material and direct the contractor to remove, stockpile or contain, and characterize the suspect material(s) identified within the boundaries of the construction area. Continued work at a contaminated site shall require the approval of the Site Environmental Manager.
- A photoionization detector (or other organic vapor detecting device) shall be present during grading and excavation through suspected chemically impacted soil.
- Excavation of VOC-impacted soil will require obtaining and complying with a Bay Area Air Quality Management District Rule 40 permit.
- The extent of removal actions shall be determined on a site-specific basis. At a minimum, the chemically impacted area(s) within the boundary of the construction area and/or trench shall be remediated to the satisfaction of the lead regulatory agency (ACEH) for the site. The Site Environmental Manager or representative overseeing removal actions shall inform the contractor when the removal action is complete.
- In the event that contaminated soil is encountered, all on-site personnel handling or working in the vicinity of the contaminated material shall be trained in accordance with OSHA regulations for hazardous waste operations. These regulations are based on CFR 1910.120 (e) and 8 CCR 5192, which states that "general site workers" shall receive a minimum of 40 hours of classroom training and a minimum of three days of field training. This training provides precautions and protective measures to reduce or eliminate hazardous materials/waste hazards at the work place.
- All excavations shall be filled with structurally suitable fill material which contains non-hazardous contaminant concentrations (if any) that do not exceed ESLs. The cover (cap) shall be repaired and returned to its pre-excavation condition.
- Any project-related dewatering activities shall either discharge into the sanitary sewer, under permit with the EBMUD, or comply with the NPDES permit regulations and an associated SWPPP regarding discharge into storm drains. Such permit requirements typically include on-site treatment to remove pollutants prior to discharge. Alternatively, the

water shall be temporarily stored onsite in holding tanks, pending off-site disposal at an approved disposal facility.

- The Site Environmental Manager shall confirm the presence of the suspect contaminated soil and direct the contractor to remove, stockpile, or contain the suspect material identified within the boundaries of the construction area. Contaminated soil shall either be treated onsite or trucked off-site for disposal at a California licensed facility approved for disposal of such waste.
- After earthwork activities are complete, a report will be prepared to document the relocation and final disposition of soil reused or disposed of offsite. At a minimum, the report will include the dimensions of the excavation and confirmation sample locations. The analytical data will be provided in tables and a Site plan showing sampling locations and limits of excavation and grading will be presented. If applicable, copies of receipts pertaining to the disposition of the soil will be appended to the report.

5.1 Implementation of Site Management Plan

AB&I shall oversee implementation of this SMP at the Site. A copy of this SMP shall be included in all confracts signed with confractors and third party contractors working in the subsurface at the Site. It is the responsibility of the confractor to adhere to this SMP, project specifications, and site safety. The confractor is also responsible for providing a copy of this SMP to its subconfractors.

This SMP was developed based on the current conditions at the Site and applicable regulations. It may be necessary to modify this SMP from time to time for any of several reasons, including the following.

- Change in property use (e.g., addition of buildings to the site);
- Any change in legal requirements;
- Change in environmental conditions;
- Intrusive activity that is not addressed by this SMP; and
- New chemical toxicity information for chemicals present at the Site.

5.2 Limitations

This SMP was prepared to address VOCs, TPH and metals present in the soil and groundwater at the Site and current known site conditions, regulations and laws. This SMP does not address issues related to other chemicals or future site conditions that may be encountered during construction projects, including but not limited to, demolition and construction debris, asphalt, concrete, and asbestos-containing materials. If such materials are encountered during a

construction project, contractors and workers are responsible for complying with all applicable laws pertaining to the handling and disposal of these materials.


The Site-related activities may be subject to federal, state, and local laws and regulations, including those published by U.S. Environmental protection Agency (USEPA), the BAAQMD, California Environmental Protection Agency (Cal-EPA), Alameda County, and the City of Oakland. These regulations address issues such as health and safety, hazardous waste, dust generation, storm water, and community right-to-know. It is the responsibility of the parties involved to ensure that all construction and maintenance activities abide by current applicable laws and regulations.

SGI disclaims any responsibility for any unauthorized use of this SMP. It is understood that while this SMP is intended to provide guidance and establish a framework for the management of residual product in the subsurface in soil to protect human health and the environment, this SMP shall not create any warranties or obligations to AB&I as to implementation, adequacy, or success of protective measures under this SMP.

6.0 REFERENCES


- Alameda County Department of Environmental Health (ACEH 2008). Letter regarding, "Fuel Leak Case No. RO0000092, American Brass & Iron Foundry, 7825 San Leandro Street, Oakland, California". November 4.
- Alameda County Department of Environmental Health (ACEH 2009). Letter regarding, "Fuel Leak Case No. RO0000092, American Brass & Iron Foundry, 7825 San Leandro Street, Oakland, California". March 26.
- Alameda County Department of Environmental Health (ACEH 2011a). Letter regarding, "Fuel Leak Case No. RO0000092, American Brass & Iron Foundry, 7825 San Leandro Street, Oakland, California" request for a draft Covenant and Environmental Restriction on Property (Deed Restriction) along with a Site Management Plan (SMP). April 28.
- Alameda County Department of Environmental Health (ACEH 2011b). Letter regarding, "Fuel Leak Case No. RO0000092, American Brass & Iron Foundry, 7825 San Leandro Street, Oakland, California" request for a revised Site Management Plan (SMP). June 8.
- BAAQMD (Bay Area Air Quality Management District), 1999. BAAQMD CEQA Guidelines, Assessing the Air Quality Impacts of Projects and Plans, San Francisco, California. December.
- BSK Associates, Inc. (BSK). 1993. "Report Shallow Soil and Groundwater Investigation American Brass & Iron Foundry". April 30.
- BSK Associates, Inc. (BSK). 2007. "Preliminary Groundwater Investigation Report AB&I Foundry". June 11.
- California Department of Toxic Substances Control, 2001, Information Advisory Clean Imported Fill Material. October 2001.
- California Department of Water Resources, 1991. California Well Standards. Bulletin 74-90. June.
- California Regional Water Quality Control Board (CRWQCB). 2007. Screening for Environmental Concerns at Sites with Contaminated Soil and Groundwater. Interim Final. November
- CRWQCB, 2002. Information on Erosion and Sediment Controls for Construction Projects: A Guidebook, Erosion and Sediment Control Field Manual. August.
- CSQA (California Stormwater Quality Association), 2003. Storm Water Best Management Practices Handbook. January.
- Helley, E.J., K.R. Lajoie, W.E. Spangle, and M.L. Blair. 1979. Flatland Deposits of the San Francisco Bay Region. California, Their Geology and Engineering Properties, and Their Importance to Comprehensive Planning. U.S. Geological Survey Professional Paper 943. Washington D.C.


- Muir, K.S., 1993. Geologic Framework of the East Bay Plain Groundwater Basin, Alameda County, California.
- Regional Water Quality Control Board (RWQCB, 1995). Water Quality Control Plan for the San Francisco Bay Basin (Basin Plan)
- Regional Water Quality Control Board (RWQCB, 1999).
- Regional Water Quality Control Board (RWQCB, 2006). Water Quality Control Plan for the San Francisco Bay Basin (Basin Plan)
- The Source Group, Inc. (SGI 2007). "Revised Site Investigation Work Plan", AB&I Foundry, 7825 San Leandro Street, Oakland, California. September 17.
- The Source Group, Inc. (SGI 2008a). "Site Investigation Report", AB&I Foundry, 7825 San Leandro Street, Oakland, California. February 14.
- The Source Group, Inc. (SGI 2008b). "Report for Additional Site Investigation", AB&I Foundry, 7825 San Leandro Street, Oakland, California. September 25.
- The Source Group, Inc. (SGI 2009a). "Work Plan for Enhanced Anaerobic Biodegradation Pilot Study Parking Lot Area & Former 8,000-Gallon Mineral Spirits/1,1,1-TCA UST", AB&I Foundry, 7825 San Leandro Street, Oakland, California. March 12.
- The Source Group, Inc. (SGI 2009b). "Supplemental Soil Vapor Investigation Report", AB&I Foundry, 7825 San Leandro Street, Oakland, California. April 22.
- The Source Group, Inc. (SGI 2009c). "May 2009 Semi-Annual Monitoring and Enhanced Anaerobic Biodegradation Pilot Study", AB&I Foundry, 7825 San Leandro Street, Oakland, California. October 7.
- The Source Group, Inc. (SGI 2009d). "Enhanced Aerobic Biodegradation Pilot Study Report Former Three 10,000-Gallon USTs Area", AB&I Foundry, 7825 San Leandro Street, Oakland, California. October 7.
- The Source Group, Inc. (SGI 2010). "Quarter 1/Quarter 2 2010 Semi-Annual Monitoring Report and Request for Site Closure, AB&I Foundry, 7825 San Leandro Street, Oakland, California. September 7.
- The Source Group, Inc. (SGI 2011). "Quarter 4 2010 Semi-Annual Monitoring Report, AB&I Foundry, 7825 San Leandro Street, Oakland, California. January 26.
- USEPA, 1989. Risk Assessment Guidance for Superfund, Human Health Evaluation Manual, Part A. Interim Final. Solid Waste and Emergency Response. December.




SOURCE: U.S.G.S. 7.5' QUAD SHEET OAKLAND EAST, CALIFORNIA PHOTOREVISED 1997

CLIENT:	AB&I FOUNDRY	DATE: 6/27/07
LOCATION:	7825 San Leandro Street Oakland, California	FIGURE:














SOIL SAMPLE RESULTS - FORMER
10,000-GALLON DIESEL UST AREA - 2007
7625 SAN LEARNING STREET
CANO INC. DOI: 1006
3
AS SQUIESCHOP
































Table 1 Summary of Soil Sample Results - Organics AB&I Foundry 7825 San Leandro Street Oakland, California

Sample ID	Depth	Date	TPHg	TPHd	MTBE	Chloroethane	Benzene	Ethylbenzene	Toluene	Xylenes, Total
Units	(feet)		(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)
RWQCB ESLs	Reside	ntial	100	100	8.4	10	0.12	33	29	31
RWQCB ESLS -	Comme	ercial	450	150	8.4	11	0.26	33	29	100
Former Three 10,00	00-Gallon USTs									
SB-01-05	5	10/30/2007	<0.02	65	NA.	NA	<0.00028	<0.00028	<0.00019	<0.00057
SB-01-10	10	10/30/2007	91	2.4	NA	NA	<0.42	<0.34	<0.42	<0.76
SB-01-20	20	10/30/2007	450	8.9	ΝA	NA	< 0.41	4.9	<0.41	<0.75
SB-01-28	28	10/30/2007	0.39	<0.18	NA	NA	<0.00029	<0.00029	<0.00019	< 0.00057
SB-02-03	3	10/30/2007	68	110	NΑ	NA.	<0.42	<0.34	<0.42	<0.75
SB-02-15	15	10/30/2007	410	47	ΝA	NA	< 8.41	7,4	1.5	30
\$8-02-20	20	10/30/2007	1400	120	NA	NA.	<1	27	<1	62
SB-02-25	25	10/30/2007	0.28	<0,18	NA.	NA NA	<0.00029	< 0.00029	< 0.00019	<0.00058
SB-03-05	5	10/30/2007	<0.02	<0.18	NA.	NA.	<0.00028	<0.00028	0.008	<0.00057
SB-03-10	10	10/30/2007	1.3	1.4	NA NA	NA	0.0049	<0.00028	<0.00019	< 0.00056
SB-03-15	15	10/30/2007	1400	660	NA	NA	<0.98	12	<0.98	<1.8
SB-03-25	25	10/30/2007	<0.021	<0.18	NA	NA	< 0.0003	< 0.0003	<0.0002	<0.0006
\$B-04-10	10	10/30/2007	<0.02	<0.18	NA.	NA	<0.00029	<0.00029	<0.00019	<0.00057
SB-04-15	15	10/30/2007	790	44	NA.	NA	<0.11	2,4	<0.074	<0.22
SB-04-20	20	10/30/2007	470	4.3	NA.	NA	<0.38	4	<0.38	<0.68
SB-04-24	24	10/30/2007	<0.021	<0.18	NA	NA	<0.0003	<0.0003	<0.0002	<0.0006
SB-05-05	5	10/31/2007	1.9	2700	NA	NA	<0.0003	<0.0003	<0.0002	<0.0006
SB-05-10	10	10/31/2007	4.1	<0.18	NA	NA	0.012	<0.0003	<0.0002	<0.00059
SB-05-20	20	10/31/2007	78	22	NA	NA.	<0.42	<0.34	<0.42	<0.76
SB-05-25	25	10/31/2007	<0.02	<0.18	NA.	NA	<0.00028	<0.00028	<0.00019	< 0.00056
\$B-08-15	15	10/31/2007	2.2	13	NA	NΑ	<0.00029	<0.00029	<0.00019	<0.00057
SB-08-20	20	10/31/2007	1.9	<0.18	NA.	NA.	<0.00027	<0.00027	<0.00018	<0.00054
SB-09-10	10	10/31/2007	4.6	240	NA	NA	< 0.0003	<0.0003	<0.0002	<0.0008
\$8-09-15	15	10/31/2007	160	450	NA	NA	<0.4	< 0.33	<0.4	<0.73
Former 550-Gallon	Gasoline UST	•					•		•	
\$B-10-05	5	10/31/2007	320	50	NA	NA	<0.4	<0.33	<0.4	<0.73
SB-10-10	10	10/31/2007	450	38	NA	NA	<0,4	1.4	<0.4	<0.72
SB-10-15	15	10/31/2007	330	82	NA	NA	<0.4	< 0.32	<0.4	<0.72
SB-10-20	20	10/31/2007	5.4	5.1	NA.	NA.	<0.00029	<0.00029	<0.00019	<0.00057
SB-10-25	25	10/31/2007	<0.02	<0.18	NA	NA.	<0.00029	<0.00029	<0.00019	<0.00058
SB-11-05	5	11/1/2007	8.6	NA	NA	NA	<0.0006	<0.0006	<0.0004	<0.0012
SB-11-10	10	11/1/2007	71	NA.	NA	NA NA	<0.38	<0.31	<0.38	<0.69
SB-11-20	20	11/1/2007	<0.021	NA.	NA	NA NA	<0.0003	<0.0003	<0.0002	<0.00059

Table 1 Summary of Soll Sample Results - Organics AB&I Foundry

7825 San Leandro Street Oakland, California

Sample ID	Depth	Date	TPHg	TPHd	MTBE	Chloroethane	Benzene	Ethylbenzene	Toluene	Xylenes, Total
Units	(feet)		(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)
DIMOCO 551 -	Resid	ential	100	100	8.4	10	ນ.12	33	29	31
RWQC8 ESLs -	Comm	ercial	450	150	8.4	11	0.26	33	29	100
SB-12-05	5	11/1/2007	<0.02	NA	NA	NA	<0.00028	<0.00028	<0.00019	<0.00057
\$B-12-10	10	11/1/2007	<0.02	NA	N/A	NA	<0.00028	<0.00028	<0.00019	<0.00057
SB-12-15	15	11/1/2007	250	NA	NA	NA	< 0.39	< 0.32	<0.39	<0.71
SB-12-25	25	11/1/2007	<0.02	NA	NA	NA	<0.00029	<0.00029	<0.00019	<0.00058
SB-13-05	5	11/1/2007	<0.019	NA	NA	NA	<0.00027	<0.00027	<0.00018	<0.00055
SB-13-10	10	11/1/2007	0.91	NA	NA	NA	<0.0003	<0.0003	<0.0002	<0.0006
SB-13-15	15	11/1/2007	78	NA	25	NA.	<0.38	<0.31	<0.38	<0.68
SB-13-25	25	11/1/2007	420	NΑ	NA	NA	<0.42	<0.34	<0.42	<0.75
SB-14-03	3	11/1/2007	<0.02	NA	NA	NA	<0.00028	<0.00028	<0.00019	< 0.00056
SB-14-10	10	11/1/2007	<0.02	NA	NΑ	NA	<0.00029	<0.00029	<0.00019	<0.00058
SB-14-15	15	11/1/2007	30	NΑ	NA _	NA	<0.00093	<0.00093	<0.00062	<0.0019
SB-15-05	5	11/1/2007	<0.019	NΑ	NA _	NA	<0.00027	<0.00027	<0.00018	<0.00055
SB-15-10	10	11/1/2007	<0.02	NA	NA	NA	<0.00028	<0.00028	<0.00019	<0.00056
SB-15-15	15	11/1/2007	1100	NA	NA	NA	<0.39	<0.31	<0.39	<0.7
SB-15-19	19	11/1/2007	7.9	NA	NA	NA	<0.0004	0.019	<0.00026	< 0.00079
Former 8,000-Gallo	on Mineral Spiri	ts/ 1,1,1-TCA US	SŤ		•					
SB-22-03	3	11/2/2007	0.29	90	<0.00046	< 0.00055	<0.00021	<0.00042	<0.00039	<0.0015
SB-22-05	5	11/2/2007	<0.02	16	<0.00046	< 0.00055	<0.00021	<0.00042	<0.00039	<0.0015
SB-22-10	10	11/2/2007	0.99	150	<0.00045	< 0.00053	<0.00021	<0,00041	<0,00038	<0.0015
SB-22-15	15	11/2/2007	<0.02	<0.18	<0.00047	< 0.00055	<0.00021	<0.00042	<0.0004	<0.0016
SB-23-03	3	11/2/2007	2.1	110	<0.00045	0.055	<0,0002	<0.00041	<0.00038	<0.0015
SB-23-05	5	31/2/2007	0,45	190	<0.00044	<0.00053	<0.0002	<0.0004	<0,00038	<0.0015
SB-23-10	10	11/2/2007	0.25	69	<0.00044	<0.00053	<0.0002	<0,0004	<0.00037	<0.0015
SB-23-15	15	11/2/2007	<0.02	<0.18	<0.00045	<0.00053	<0.00021	< 0.00041	<0.00038	<0.0015
SB-24-03	3	11/2/2007	1.2	170	<0.091	<0.11	< 0.042	<0.083	<0.077	<0.31
SB-24-05	5	11/2/2007	1.1	61	<0.00044	0.022	<0.0002	<0.0004	<0.00037	<0.0015
SB-24-10	10	11/2/2007	0.69	<0.18	<0.00046	< 0.00054	<0.00021	< 0.00042	<0.00039	<0.0015
SB-24-20	20	11/2/2007	<0.02	<0.18	<0.00045	<0.00054	<0.00021	<0.00041	<0.00038	<0.0015
SB-26-04	4	11/2/2007	380	5800	<8.9	<11	<4.1	<8.1	<7.6	<30
\$8-26-10	10	11/2/2007	72	19	<0.093	<0.11	<0.043	<0.084	<0,079	<0.31
SB-26-15	15	11/2/2007	<0.02	<0.18	<0.00046	<0.00055	<0.00021	<0.00042	<0.00039	<0.0016

Table 1 Summary of Soil Sample Results - Organics

AB&I Foundry 7825 San Leandro Street Oakland, California

Sample ID	Depth	Date	трнд	TPHd	MTBE	Chloroethane	Benzene	Ethylbenzene	Toluene	Xylenes, Total
Units	(feet)		(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)
514/5/5/5 554	Reside	ntial	100	100	8.4	10	0.12	33	29	31
RWQCB ESLs	Comma	ercial	450	150	8.4	11	0.26	33	29	100
Former 10,000-Ga	llon Olesel UST									
SB-27-3	3	11/5/2007	NA	100	NA	NA	NA	NΑ	NA	NΑ
SB-27-5	5	11/5/2007	NA.	6	N/A	NA	NA	NA	NA	NA
SB-27-10	10	11/5/2007	NA.	<0.18	NA	NA	NA	NA	NA	NA.
\$B-27-15	15	11/5/2007	NA	<0.18	NA	NA	NA	NA	NA	NA
SB-28-06	6	11/2/2007	<0.02	64	<0.00056	NA _	<0.00028	<0.00028	<0.00019	<0,00056
SB-28-10	10	11/2/2007	<0.019	120	<0.00055	NA	<0.00027	<0.00027	<0.00018	<0,00055
SB-28-15	15	11/2/2007	<0.023	<0,18	NA	NA	< 0.0003	<0.0003	<0.0002	< 0.00059
SB-29-6	6	11/5/2007	NA NA	13	NA	NΑ	NA	NA	NA.	NA
SB-29-10	10	11/5/2007	NA	<0.18	NA.	NA	NA	NA.	NA	NA NA
SB-29-15	15	11/5//2007	NA	<0.18	NA	NA	NA.	NA	NA	NA
SB-28-20	20	11/2/2007	<0.02	<0.18	NA	NA	<0.00029	<0.00029	<0.00019	<0.00058

Notes:

MTBE - Methyl len butyl ether < 0.005 - Not reported at or above laboratory's reporting limit of 0,005 mg/kg

 (mg/kg)
 - milligrams per kilogram
 UST
 - underground storage tank

 TPHq
 - Total Petroleum Hydrocarbons as Gasoline
 1,1,1-TCA
 - 1,1,1-Trichloroethane

TPHd - Total Petroleum Hydrocarbons as Diesel

-TPHg, BTEX, VOCs and fuel oxygenates analyzed using EPA Method 82608 by Test America Laboratories (TAL), Pleasanton, California

-TPHd analyzed using EPA Method 8015M with silica gel cleanup by TAL, Pleasanton, California

RWOC8 ESLs - Environmental Screening Levels taken from the California Regional Water Quality Control Board, San Francisco Bay Region document entitled "Screening for Environmental Concerns at Sites with Contaminated Soil and Groundwater," Interim Final November 2007, groundwater is not a current or potential source of drinking water.

-Concentrations in bold exceed commercial ESLs for shallow soil (less than 3 meters).

Table 2 Summary of Solf Sample Results - Metals AB&I Foundry 7825 San Leandro Street Ookland, California

Sample)D	Depth	Date	Antimony	Arsenic	Barlum	Beryllium	Cadmium	Chromium	Cobalt	Copper	Load	Мессилу	Molybdanum	Nickel	Şelenium	Silver	Thatlium	Vanadlum	Zinc
Units	(feet)		(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/(g))	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)
RWQCB ESLs	Resid	ential	6.1	91.0	760	4	1.7	75.0	40	230	200	1	40	160	10	20	1.2	15	600
KWQCB ESCS	Comn	tertlal	40	15	1600	e	7.4	750	90	230	750	1	40	160	10	40	15	190	800
Background			<ኅ0	42	410	1.1	5.6	120	2Ġ	63	57	8.0	<\$	270	5.1	2	10	90	140
Former Three 10,	,900-Galion U	ST:																	
\$B-01-05	ş	10/30/2007	<0.05	4.2	160	0 67	40.0033	37	8.6	22	19	0.065	1,1	32	<0.11	<0.013	<0.072	31	44
\$B-01-10	10	10/30/2007	<0.051	8.8	130	88,0	<0,0033	36	7.8	20	3.6	9.06	<0.042	34	<0.11	<0.013	<0.073	37	3D
Former 550-Gbild	on Gasoline (3ST																	
SB-13-05	5	11/1/2007	40 05	5.5	190	1.7	<0.0033	310	6.1	77	38	<0.00099	7.1	32	7 B	2,7	16	480	320
\$8-13-10	10	11/1/2007	<0.05	4	140	0.5	<0.0032	37	11	21	4.8	0.056	<0.041	27	<0.1	<0.013	<0.071	40	32
Former 8,000-Ga	dion Mineral S	Spirits/ 1,1,1-1	CA UST				7.44												
SB-22-05	5	11/2/2007	<0 053	4.3	150	<0.0036	<0.0035	40	12	22	5	D.058	<0.044	30	<0.11	<0.014	<0.076	44	36
SB-22-10	10	11/2/2007	<0.05	14	180	0.59	<0,0032	48	18	42	130	0.11	2.8	42	ج0.1	<0.013	<0.071	48	110
\$6-24-20	20	11/2/2007	<0.047	2.6	300	<0.0032	<0.0031	35	13	23	5	<0.00098	<0.039	41	<0.099	<0.012	<0.068	30	37
S8-26-10	ιō	11/2/2007	<0.051	5.8	100	0.59	<0.0033	53	17	34	4.9	80.0	<0.042	67	<0.11	<0.013	<0.073	72	100
SB-26-15	15	11/2/2007	<0.05	2.2	120	0.54	<0.0032	35	7.9	18	4	0 053	<0.041	44	<0.1	<0.013	<0.071	31	35
SB-26-04	4	11/2/2007	3.1	13	าย	<0.0034	<0.0033	130	10	24B	28	<0,001	19	87	<0.11	<0.013	<0.073	35	57
Former 10,000-G	alion Diesel i	JST			· ·							· ·							
SB-28-06	- 6	11/2/2007	2.4	3.9	330	0.69	3.4	31	3	60	970	0.11	3.6	15	<0,1	Z (0,0>	<0,071	12	550
SB-28-10	10	11/2/2007	<0.053	10	₹30	<0.0035	<0.0034	# 1	5.4	23	110	0.51	<0.044	11	<0.11	<0.014	<0.075	22	120

Notes:

(mg/kg) -crifflyrams per kilograms

ga con transport of first gent and a second avoid to a second of the contract of the contract

UST - undergranio storage lank

1,1,5-TCA -1,1,1-Trichlorgerhains

-CAM 17 Metals analyzed using EPA Methos 60109/7471A by Yest American Laboratories (TAL), Pleasanton, California

RWQCB ESLs - Environmental Economics Levels taken from the Casterna Proposal Winer Quality Caster Board, San Francisco Bay Region document entitled "Screening for Environmental Economics at Sinus with Constituted Soil and Oroundwebs "

blacker Plant November 2002, groundwater is not a current or potential sounce of directing water.

-Concentrations to bold except commercial ESts for snakew soil fless than 3 meters).

Background data paramed from Lawrence Boxeloy Navonal Laboratory Environmental Restoration Program, Soil Management Plan, 2006

Table 3 Summary of Analytical Results Petroleum Hydrocarbon Related Constituents (µg/L) AB&) Foundry 7825 San Leandro Street Oakland, California

Well Number	Date	TPH-Diesel	Naphitralene	TPH- Gasoline	Senzena	Toluene	Ethylbenzona	Xylenos	WTBE	ETBE	TAME	DIPE	TBA	1,2-064
WQCB E\$L≤ [†]		NA	11,000	NA	1,800	530,000	170,000	160,000	80,000	NA	NA	NA.	NA	690
1CLs?		NA.	17"	NA	1.0	160	700	1,760	13	NA	NΑ	NA	NA	0.5
MW-1	05/22/09		<0.50		< 0.50	<0.50	<0.50	<1.0	_	-	~	-	_	<0.50
	12/10/09	<50	<0.50	<50	<50	<50	<50	<10	-	-	-	-	-	<0,50
	07/09/10	81	<0.50	<50	0,42 J	<0,50	<0.50	<1.0	H	-	~	-	-	<0.50
MW-2R	05/22/09	<50	< 0.50	110	<0,50	<0.50	<0.50	<1.0	~	-	-	-	-	<0.50
	12/10/09	<50	< 0.50	99	<0.50	< 0.50	<0.50	<1,0	-	-	¥.	-	_	<0.50
	07/09/10	<50	<0.50	210	<0.50	<0.50	<0.50	<10	4.	12		_	14.	<0.50
MW-3	05/21/09	<0.050	<2.5	0.55	×2.5	1.8	<2.6	₹5.0	-	-	-	-		<2.5
	111111111						EArth Inject	ions.	300			-	-	
	07/01/09	The state of	<2.5		<2.5	8.4	<2.5	<5.0	-	- 44	-	-	-	-2.5
	08/07/09	1 1	<0.50		0 67	7.1	<0.50	<1.0	_	~	-	-		<0,50
	09/10/09	-	<0.50	-	0.72	9,8	<0,50	<1.0	-	-	-	-	-	< 0.50
	12/09/09	<50	<0.50	51	0.51	2.6	<0.50	<1.0	-	-	-	_	-	<0.50
	04/09/10	-	<0.50	-	0,41 J	1,4	<0.50	<1.0	_	-	~	~	~	<0.50
	07/08/10	<50	<0,50	<50	0,36 J	<0,50	<0.50	<1,0	~	-	-	-	_	<0.50
- Constitution	12/22/10	<50	<0.50	<50	0.40 J	<0.50	<0.60	<1.0	-	-	- 1	-	-	<0.50
MW-4	05/21/09	450	×0.50	<50	<0.50	<0.50	<0.60	<1.0	-	-		-	-	<0.50
	12/09/09	<50	<0.50	70	<0.50	<0.50	<0.50	<1.0	44	-	9.0	1-0	1 -	<0.50
	07/08/10	<50	<0.50	110	<0.50	<0.50	<0.50	<1.0		-	1 2	-		<0.50
MVV-5	05/21/09	<50	<0.50	<50	<0.50	<0.50	<0.50	<10	-	(-):	-	-	-	<0.50
	12/10/09	<50	< 0.50	53	<0.50	< 0.50	<0.50	<1.0	4	- 1	1 2	-		<0.50
	07/09/10	<50	<0.50	120	<0.50	<0.50	<0.50	<1.0	10	1-17	<u>-</u>	-	_ =	<0.50
MW-6	05/21/09	<50	<0.50	<50	<0.50	<0.50	<0.50	<10	-	185	-	-	-	<0.50
	12/09/09	<50	<0.50	<50	<0.50	<0.50	<0.50	<10	-	-	- 1	-	-	<0.50
	07/08/10	67	<0.50	<50	<0.50	<0.50	<0.50	<1.0	-	-	- 1	-	-	<0.50
MW-7	05/22/09	<50	<0.50	<50	<0.50	<0.50	<0.50	<1.0	-	-	-	-	-	<0.50
	12/10/09	<50	<0.50	<50	<0,50	<0.50	<0.50	<1.0	40	-	- Y N	-	-	<0.50
	07/09/10	<50	<0.50	<50	<0.50	<0.50	< 0.60	₹1.0	-			- 24		<0.80

Table 3 Summary of Analytical Results Petroleum Hydrocarbon Related Constituents (µg/L) AB&I Foundry 7825 San Leandro Street Oakland, California

Well Number	Date	TPH-Olasel	Naphthalene	TPH- Gasoline	Senzene	Toluene	Ethylbenzene	Xylenes	мтве	E78E	TAME	DIPE	TBA	1,2-DCA
RWQCB ESL¢		NA.	11,000	NA.	1,800	\$30,000	170,000	169,000	80,000	NA	NA	NΆ	NA	690
MCL s		NA.	17*	NΑ	1.0	160	700	1,750	13	NΑ	NA	NΑ	NA	0.5
MW-8	05/21/09	<50	<5.0	2.1	2.9	<5.0	<5.0	<10	-	_		-	-	<50
Dup	05/21/09	<50	<5.0	21	2.8	<5.0	≪5.0	<10	_	-	(E) 4((C)	1 - 1	(H)	₹5.0
							EArth Inject	ións .						
	07/01/09		<2.5		2.6	≺2.5	42.5	45.0		_		-	-	<2.5
	08/07/09		<5,0		3.2	<5.0	<5.0	<10	V =1	_	2 1	102		<5.0
	09/10/09	-	<25	-	3.4	<2.5	<2.5	<5,0	-	_	1 - 1	-	_	<25
	12/09/09	<s< b="">0</s<>	<2.5	180	3.0	<25	<2.5	<5.0		_	-	-	-	1.8
Dup	12/09/09	<50	<50	190	28	<5.0	<5.0	<10	_	-	-	-	-	<5.0
	04/09/10	-	<2,5		24 J	<2,5	<2.5	<5.0	-	~	-	-	-	1,0 J
	07/08/10	110	₹2.5	140	24 J	<25	<2.5	<5,0	-	-	_	-		<2.5
Dup	07/08/10	74	425	140	2,2 J	<2.5	<2.5	<5.0	14	~	· •	-		<25
	12/22/10	120	<0.50	<50	0.43 J	<0.50	<0.50	<1.0		-	-	-	-	<0.50
MW-9	05/22/08	250	2.2	3.500	180	2:9	3.9	1.7	-	-	- 1	-	-	<0.50
	The state of						EAB transp	5/10	-					
	07/01/09	470	3.3	3,400	53	2.0	9.5	0.28	-	-	-	+	-	<0.50.
	08/07/09	340	0.82	2,400	9,1	0.5	2.2	1.5	^	_	- 4		_	<0.50
	09/10/09	480	0 87	3,100	5.7	0.36	1.4	1.7	-	_	-	-	-	<0.50
	12/09/09	150	1.3	2,700	36	0.87	2.7	1.1		-	-	_	-	<0.50
	04/09/10	320	1.2	3,300	88	1,3	4,6	3.1	-	_	_	-	-	<0.50
	07/09/10	250	0.77	2,700	100	2.30	9.2	1.6	-	_	-	_		<0.50
	12/22/10	120	0.75	2,200	77	1.80	9,1	1,4	-	-	-	-	-	<0.50

Notes:

Value in bold exceed the MCL.

* Carama Experiment of the British District Water Program, Drinking Water Notification Level. December 14, 2007

California EPA Department of Health Service Maximum concentration levels for drinking water MCL

RWOCE ESLs (VI) Regional Water Quality Control Board Environmental Screening Levels based on vapor introdon concerns for commercial land use scenario.

ug/L All concentrations reported in micrograms per liter (ug/t.).

Total Petroleum Hydrocarbons

MTBE methyl test butyl ether

C TOU othyl Ion bulyl other

TAME tert-arreyl mothyl ether

DIPE disopropyl ether

TBA tributyl alcohol

dichloroethano

DÇA ND Not detected at or above laboratory reporting firmit.

<50 Not detected at or above laboratory reporting limit of 50 ug/L.

NG Not sampled.

Not analyzed. Reported due to the presence of discrete peaks analyte detected below quantitation limits 1500

Table 4 Summary of Analytical Results Volatile Organic Compounds (ug/L) A981 Foundry
7825 San Leandro Street
Oaltand, California

		=	othana	٥٤	herie	he/all	ethene.	outhene	thane	*	rene	
Well Number	Oute	გოობ ტ ო ო	Chloradibromomothana	Chloroethano	1,1-Olchloroethene	1,3-Dichloroethon	sie-1,2.Olohforaethene	Pans-1.2-Outhlorouthene	1,1,1 Thehiorpothane	Vinyi Chibáde	Isopropyleenzene	n-Propybana
tMdC8 E2f*,		NA.	NA.	2,700	3,400	1,800	17,000	19,000	360,000	10	ΝĒ	NE
(CLs'		NA .	NA	NE.	5,0	\$.0	6.0	10	200	0.5	770-	2601
MW-1	05/22/09	<0.50		<0.50	0.41	∠0, 50	<0.50	40.50	<0.50	<0.50	<0.50	∞.58
	12/10/09	<0,50	-	<0.50	0.41	<0.50	<0.50	<0.50	<0.50	<0.50	<0,50	< 0.50
	07/09/10	<0.50	-	¢0 50	0.43 J	<0.50	<0.50	<0.50	<0.50	<0.50	+8.50	<0.50
MW-2R	05/22/09	<0.50	-	40.50	-0.50	c0.50	<0.50	<0.50	<0 50	<0.50	+0.50	₹0.50
	12/10/09	<0.50	-	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50
	07/09/10	*0.50	-	*0.50	<0.50	*0.50	e0.50	<0.50	c0 50	10.50	40.50	ro 50
MW-3	05/21/09	×2.5	-	<2,5	220	1,000	10	1.2	42.5	8.4	c2.5	<2.5
				1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		EANS SYNCEN	PR -	40-0	and the second	500	a permit	17000-00
	07/01/09	<2.5	-	<2.5	150	120	7.6	4.5	42.5	6.7	€2.5	<2.5
	08/07/09	<0.10	-	61	110	144	1.2	<0.50	<0.50	28	<0,50	40.50
	09/10/09	<0.50	-	150	9,5	11	Ø 20	0.47	<0.50	3,6	<0.50	<0.50
	12/09/09	<0.50	-	78	16	6.4	0.25	0.37	<0.50	17	<0,50	<0.50
	04/09/10	<0.50	-	47	0.78	0.74	<0.50	0.29 J	<0.50	1.4	<0,50	< 0,50
	07/08/10	e0 S0	3.	3-5	0.58	1.0	<0.50	0 27 J	<0.50	3.1	<0,50	<0.50
	12/22/10	-	-	3.8	0.29.J	0.9	<0.60	<0,50	e0.50	0,97	<0,50	<0.50
NWA	05/21/09	<0.50	(-)	<0.50	<0.50	<0.50	<0,50	<0.50	<0.50	40.50	<0.50	<0.50
	12/09/09	<0.50	-	<0.50	<0,50	<0,50	<0.50	<0.50	<0.50	<0.50	<0.50	< 0.60
	07/06/10	<0.50	2	+0.50	<0.60	<0.50	<0.50	40.50	<0.50	<0.50	<0.50	10.50
MW-S	05/21/09	r0,50	+	<0.50	0.7	0.71	33	1.1	<0.50	+0.60	40,50	+0,50
	12/10/09	₹0.50		<0.50	0.58	0.63	2.2	0.67	<0.50	<0.50	<0.50	<0.50
	07/09/10	<0.50	-	<0.50	0.40	0.20	3.4	1,0	40.50	<0.50	<0.50	+0.50
MW-6	05/21/09	<0.50	-	<0.50	<0,56	40,50	10,50	≠0,50	+0.50	<0.50	40,5G	<0.50
	12/08/09	<0 50	- H	<0.50	<0,50	<0.50	<0,50	<0.50	<0.50	<0.50	<0.50	40.50
	07/06/10	+0.50	-	<0.50	<0.50	40,50	<0.50	<0.50	<0.50	<0.90	≠0.50	< 0.50

Table 4 Summary of Analytical Results Volatile Organic Compounds (ug/L) ABAI Foundry 7825 San Leandro Street Oakland, California

	$\overline{}$		г				1					
Wall Number	Cate	Влепобот	Chlorodibromomethene	Chloroethane	1,1-Dichionosthane	1,1-Dichlenedhene	als-1,2-Dichloroethane	Irane-1,2-Dichloroethene	1.1,1 Trichloroethane	Vinyi Chlodde	teopropylaencene	n-Propylbenkane
RWOOD ESL4"		NA	NA.	2,700	3,400	1,800	17,000	19,000	360,000	13	NE	NE
₩¢L±'		NA	NA.	NE	5.0	6.0	6.0	10	200	0.5	770-	560,
MV4-7	05/22/09	<0.50	-	<0.50	<0.50	د0.50	<0.50	<0,50	<0,50	<0.50	<0.50	<0,20
	12/10/09	<9.50	-	<0.50	<0.60	<0.50	<0.50	<0.50	<0,50	<0.50	<0,50	<0,50
	67/09/10	<0.50	19	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50
MAN	05/21/09	<5.0	-	329	1.500	1,990	+5.0	45.0	1,500	16	5.3	45.0
						EARS Wends	MIS:					
	07/01/09	<25	-	350	1,200	1,100	<25	₹2.5	980	31.	42.5	<2.5
	08/07/09	<50	-	370	1,600	1,300	<60	<50	1,700	9.6	<5.0	¢5:0
	09/10/09	<25	-	340	2,600	1,100	<2 S	-25	46	10	4.0	<2.5
	12/09/09	<2.5	-	2,400	94	58	<2 S	<25	14	86	4.1	<2.5
	12/09/09	<5.0	l-	2,400	92	60	<6 D	<6 0	14	82	<5.0	<5.0
	94/09/10	<2.5	-	1,400	32	2.3 J	<25	<2.5	<2.5	2.2 J	241	<2.5
	07/08/10	×2 S	-	1,300	15	2.5	<2.5	52.5	<2.5	22J	2.8	<2.5
Dup	07/08/10	<2.5	1 2	1,200	18	4.5	<2.5	<2.6	<2.5	29	2.7	<2.5
	12/22/10	-	-	91	<0.56	0.78	<0.50	≪0,50	<0.50	<0.50	<0.50	<0.50
MW-9	05/22/09	<0.50	- ·	<0,50	40.50	40,50	<0.50	<0.50	<0.50	<0.50	21	25
				a marine		EAST Injection	rit.	Market .				
	07/01/09	49.50	-	<0.50	+9.50	*9.50	<0.50	<0.50	49.50	40.00	34	44
	08/07/09	<0.50	-	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	8.8	9.9
	09/10/09	<0,50	_	<0,50	<0.50	<0,50	<0.50	<0.50	<0.50	<0.60	40	3.8
	12/08/09	<0.50	-	<0,50	<0.50	<0.50	<0.50	<0.50		<0.50	5·S	13
	04/09/10	~0.50	-	<0.50	<0.60	<0.50	<0,50	< 0.50	<0.50	<0.50	5,9	5.5
	07/09/10	<0.50	-	<0.50	<0.50	<0.50	<0,50	<0.50	<0.50	<0.50	10.0	9.5
	12/22/10	-	-	<0.60	<0,≲0	<0.50	<0.50	<0,50	<0.50	<0.50	12.0	12

Notes:

Value in bold exceed the MCL

Compared to t

NS

Not sampled Not analyzed

analyte detected below quantitation limits