

42501 Albrae Street, Suite 100 Fremont, California 94538 Phone: (510) 440-3300 FAX: (510) 651-2233

LETTER REPORT QUARTERLY GROUNDWATER MONITORING AND REMEDIATION SYSTEM OPERATION First Quarter 1994

ARCO Station 2035 1001 San Pablo Avenue Albany, California

69036.17

69036-17/1-94QM



42501 Albrae Street, Suite 100 Fremont, California 94538 Phone: (510) 440-3300 FAX: (510) 651-2233

June 8, 1994

Mr. Michael Whelan ARCO Products Company P.O. Box 5811 San Mateo, California 94402

Subject:

Quarterly Groundwater Monitoring and Remediation System Operation

First Quarter 1994 ARCO Station 2035

1001 San Pablo Avenue, Albany, California

Mr. Whelan:

As requested by ARCO Products Company (ARCO), RESNA Industries Inc. (RESNA) presents this letter report summarizing the results of First Quarter 1994 Groundwater Monitoring and Remediation System Operation at the above-referenced site. The location of the site is shown on Plate 1, and site features such as groundwater monitoring wells, vapor extraction wells, and the remediation compound are shown on Plate 2.

Field work associated with groundwater monitoring was performed by Integrated Wastestream Management Inc. (IWM) of Milpitas, California. RESNA's scope of work for groundwater monitoring was to interpret field and laboratory analytical data, which included evaluating trends in hydrocarbon concentrations in the local groundwater, the groundwater gradient, and direction of groundwater flow beneath the site. Evaluation and warrant of IWM's groundwater monitoring field procedures and protocols is beyond RESNA's scope of work.

Field work associated with remediation system operation was performed by RESNA and consists of collecting field data, sampling the treatment unit influent and effluent vapor stream and adjusting the system to optimize performance. Evaluation of remediation system operation was performed by RESNA using laboratory analytical results and collected field data. Previous environmental work performed at the site is summarized in RESNA's reports cited in the References section.



GROUNDWATER MONITORING

Field Work

IWM field personnel were onsite February 1, 1994, to measure depth-to-water (DTW) levels, perform subjective analysis for the presence of product, and perform quarterly sampling in groundwater in wells MW-1 through MW-6, and RW-1.

Laboratory Analyses

Water samples were analyzed by Columbia Analytical Services, Inc., located in San Jose, California (Hazardous Waste Testing Laboratory Certification #1426) for benzene, toluene, ethylbenzene, and total xylenes (BTEX), and total petroleum hydrocarbons as gasoline (TPHg) using Environmental Protection Agency (EPA) Methods 5030/8020/DHS LUFT Method. In addition, the water sample from groundwater monitoring well MW-3 (located next to the former waste-oil tank pit) was analyzed for total oil and grease (TOG) using Standard Method 5520 C and F. The chain of custody records and laboratory analysis reports are included in Appendix A.

Results of Groundwater Monitoring

Groundwater elevations rose an average of approximately 1.41 feet in wells MW-1 through MW-5, dropped 1.69 feet in well MW-6, and rose 9.46 feet in well RW-1, since last quarter. No floating product or product sheen was noted in any wells during this quarter. Based on February 1, 1994 DTW data, groundwater was interpreted to flow toward the west with a gradient of approximately 0.02 ft/ft (Plate 3). Recovery well RW-1 was not used in the gradient evaluation because it possessed an anomalously high groundwater elevation. Groundwater monitoring data from this and previous quarters is presented in Table 1. The results of IWM's field work on the site are presented in Appendix A.

The following trends in hydrocarbon concentrations have been identified since the last quarter: concentrations of TPHg and benzene decreased in well MW-1; increased or remained not detected in well MW-3; and remained not detected in wells MW-2 and MW-4 through MW-6 (Plate 4). Extraction well RW-1 is no longer being sampled in association with quarterly groundwater monitoring because it is connected to the interim remediation system.



Product Removal

No floating product or sheen was observed this quarter during groundwater monitoring. A floating product skimmer was removed from well RW-1 prior to system startup in December 1993. Quantities of floating product recovered to date are presented in Table 4.

REMEDIATION SYSTEM OPERATION

The system consists of both a Groundwater Extraction System (GES) and a Vapor Extraction System (VES). The GES has not been started and therefore will not be discussed in this report. The VES uses 9 vapor extraction wells (VW-1 through VW-9), one groundwater extraction well (RW-1), and two air sparge wells (AS-1, and AS-2), to vapor extract from a total of 12 wells. The major components of the VES include a 5 horsepower positive displacement blower, and a 100 standard cubic feet per minute (scfm) Therm-Tech VAC 10 combination thermal and catalytic oxidizer (oxidizer) for the combustion treatment of extracted gasoline vapors. The oxidizer can be operated in either the thermal or catalytic mode to minimize supplemental fuel costs as hydrocarbon concentrations in extracted soil gas decline. Oxidizer operation is authorized under the Bay Area Air Quality Management District (BAAQMD) Permit to Operate Application #10931.

VES Startup and Operation

The oxidizer operated in the thermal mode with extraction occurring from nine of the available 12 extraction wells during the first quarter 1994. Cumulative VES operational data is summarized in Table 5 and includes extraction well on/off status, flowrates, and TPHg vapor concentrations. The VES was shutdown on January 24, 1994 due to rising groundwater levels causing submersion of the well screen in the vapor extraction wells. In addition, groundwater being drawn into the condensate drum caused frequent system shutdowns. Restarting of the VES will occur upon initial startup of the GES which is expected to occur during the second quarter 1994.

The system operated on wells VW-1 through VW-9 during the first quarter 1994. The combined well flow rates for the extraction wells ranged from 37 to 41 standard cubic feet per minute (scfm) at vacuums ranging from 40 to 42 inches of water column (WC). Dilution air flowrates measured during the quarter were 23 scfm during the quarter. The addition of dilution air is currently necessary to reduce the blower vacuum and prevent the oxidizer from shutting down due to a high vacuum condition. The oxidizer is designed to shutdown at a high vacuum of approximately 60 inches of WC. The VES operated for a total of 408 hours of the available 2,160 hours during the first quarter 1994.

3

69036-17/1-94QM



Air Sampling and Analysis

Air samples were collected in Tedlar® sample bags using polyvinyl chloride (PVC) tubing and an electric air vacuum sampling pump. Air samples were analyzed for TPHg and for the gasoline constituents BTEX using modified EPA Methods 5030/8015/8020 by Sequoia Analytical Laboratories in Redwood City, California. The results of laboratory analyses of air samples collected from individual wells and from the oxidizer influent and effluent are summarized in Table 6. Copies of laboratory analytical results with chain-of-custody records for air samples are included in Appendix A.

From the sampling on January 12, 1994, TPHg vapor concentrations from the oxidizer influent (with dilution air) were 2,500 micrograms per cubic meter (mg/m³). Assuming a molecular weight of 95 grams/mole for TPHg, the oxidizer influent concentrations were 644 parts per million (ppm) by volume. TPHg vapor concentrations in the oxidizer effluent were 52 mg/m³ while effluent benzene concentrations were 0.93 mg/m³.

Mass Extraction and Emission Rates

Using the analytical results and system influent flowrates (measured after dilution air), the TPHg extraction rates from the wells and TPHg and benzene emissions rates to the atmosphere were calculated. TPHg extraction rates are summarized in Table 7 and TPHg and benzene emission rates are shown in Table 8. TPHg mass extraction rates for the quarter ranged from 11.6 to 14.4 pounds per day (ppd). Total TPHg mass extracted by the VES during first quarter 1994 is estimated at 230 pounds, bringing the total since startup to 324 pounds.

The TPHg emission rates were 0.30 ppd while the benzene emissions were 0.005 ppd. Based on the influent and effluent concentrations, the thermal destruction efficiency (DE) of the oxidizer was 97.9%. Pursuant to BAAQMD permit requirements, this reported DE is in compliance with the minimum required 90% DE for TPHg influent concentrations less than 1,000 parts per million (ppm). In addition, the mass emission rate for benzene was below the 0.05 ppd (benzene) emission limit applicable to this site.

69036-17/1-94QM



PREVIOUS AND FUTURE WORK

First Ouarter 1994

- Performed First Quarter 1994 groundwater monitoring.
- Performed operation and maintenance of interim remediation system.
- Submitted Fourth Quarter 1993 Quarterly Groundwater Monitoring Report to ARCO and regulatory agencies.

Second Quarter 1994

- Perform Second Quarter 1994 groundwater monitoring.
- Initiate startup of the GES in conjunction with restarting the VES.
- Perform operation and maintenance of interim remediation system after startup.
- Submit a report of findings for the air sparge pilot test to ARCO and regulatory agencies.
- Submit First Quarter 1994 Quarterly Groundwater Monitoring Report to ARCO and regulatory agencies.

REPORTING REQUIREMENTS

Copies of this report should be forwarded to:

Mr. Barney Chan Alameda County Health Care Services Agency Department of Environmental Health 80 Swan Way, Room 200 Oakland, California 94621

Mr. Richard Hiett Regional Water Quality Control Board San Francisco Bay Region 2101 Webster Street, Suite 500 Oakland, California 94612



If you have any questions or comments, please call us at (510) 440-3300.

Sincerely,

RESNA Industries Inc.

Erin D. Krueger
Staff Geologist

David Peterson Staff Engineer

Richard H. Walls, P.E. 43139 Senior Project Engineer

Rahard H. Walls



Attachments:

References

| Plate 1: | Site Vicinity Map |
|----------|---|
| Plate 2: | Generalized Site Plan |
| Plate 3: | Groundwater Gradient Map, February 1, 1994 |
| Plate 4: | TPHg/Benzene Concentrations in Groundwater, February 1, 1994 |
| Table 1: | Cumulative Groundwater Monitoring Data |
| Table 2: | Cumulative Results of Laboratory Analyses of Water Samples - TPHg and |
| | BTEX |
| Table 3: | Cumulative Results of Laboratory Analyses of Water Samples - TPHd, TOG, |
| | VOCs, BNAs, PCBs and Metals |
| Table 4: | Approximate Cumulative Product Recovered |
| Table 5: | Vapor Extraction System Operation Data |
| Table 6: | Cumulative Results of Laboratory Analysis of Air Samples |
| Table 7: | Vapor Extraction System Estimated Gasoline Removal |
| Table 8: | Vapor Extraction System Destruction Efficiencies |
| | and Emission Rates |

Appendix A: IWM's Summary of Ground Water Sample Analyses, Field Report, Ground Water Sample Field Data Sheets, and Certified Analytical Reports with Chain-of-Custody Record


Appendix B: Laboratory Analytical Results of Air Samples with Chain-of-Custody Records




REFERENCES

RESNA November 30, 1992. Additional Subsurface Environmental Investigation and Vapor Extraction Test at ARCO Station 2035, 1001 San Pablo Avenue, Albany, California. 69036.05

RESNA March 31, 1994. Letter Report, Quarterly Groundwater and Remediation System Monitoring Fourth Quarter 1993 at ARCO Station 2035, 1001 San Pablo Avenue, Albany, California. 69036.08



Source: U.S. Geological Survey 7.5-Minute Quadrangles Richmond/Oakland West, California Photorevised 1980





Working to Restore Nature

PROJECT 69036.17

SITE VICINITY MAP ARCO Station 2035 1001 San Pablo Avenue Albany, California PLATE

1










TABLE 1 CUMULATIVE GROUNDWATER MONITORING DATA ARCO Station 2035 Albany, California (Page 1 of 4)

| Well Date | Elevation of Wellhead | Depth to Water | Elevation of Groundwater | Evidence of Product |
|--------------|--------------------------|-------------------|--------------------------|------------------------|
| \$60.4 | | | | |
| MW-1 | | | | |
| 10/29/91 | 41.41 | 11.86 | 29.55 | None |
| 11/07/91 | | 10.94 | 30.47 | None |
| 11/14/91 | | 10.97 | 30.44 | None |
| 01/19/92 | | 10.06 | 31.35 | None |
| 02/19/92 | | 8.65 | 32.76 | None |
| 03/19/92 | | 8.33 | 33.08 | None |
| 04/21/92 | | 9.32 | 32.09 | None |
| 05/12/92 | | 9.82 | 31.59 | None |
| 06/12/92 | | 10.50 | 30.91 | None |
| 07/15/92 | | 10.69 | 30.72 | None |
| 08/07/92 | | 10.53 | 30.88 | None |
| 09/08/92 | | 11.04 | 30.37 | None |
| 10/26/92 | | 11.24 | 30.17 | None |
| 11/23/92 | | 10.90 | 30.51 | None |
| 12/16/92 | | 9.40 | 32.01 | None |
| 01/13/93 | | 7.73 | 33.68 | |
| 02/22/93 | | 7.56 | 33.85 | None |
| 03/25/93 | | 8,48 | 32.93 | None |
| 04/13/93 | | 8.91 | 32.50 | None |
| 05/22/93 | | 9.68 | 31.73 | None |
| 06/17/93 | | 9.68 | 31.73 | None |
| 07/27/93 | | 10.09 | | None |
| 08/24/93 | | 10.51 | 31.32 | None |
| 12/08/93 | | | 30.90 | None |
| 02/01/94 | | 10.39 | 31.02 | None |
| 02/01/24 | | 9.29 | 32.12 | None |
| MW-2 | | | | |
| 10/29/91 | 40.38 | 11.10 | 29.28 | None |
| 11/07/91 | | 11.20 | 29.18 | None |
| 11/14/91 | | 11.21 | 29.17 | None |
| 01/19/92 | | 10.44 | 29.94 | None |
| 02/19/92 | | 8.70 | 31.68 | None |
| 03/19/92 | | 8.84 | 31.54 | None |
| 04/21/92 | | 9.80 | 30.58 | None |
| 05/12/92 | | 10.29 | 30.09 | None |
| 06/12/92 | | 10.95 | 29.43 | None |
| 07/15/92 | | 11.15 | 29.23 | None |
| 08/07/92 | | 11.01 | 29.37 | None |
| 09/08/92 | | 11.41 | 28.97 | None |
| 10/26/92 | | 11.60 | 28.78 | None |
| 11/23/92 | | 7.31 | 33.07 | None |

See notes on page 4 of 4.



TABLE 1 CUMULATIVE GROUNDWATER MONITORING DATA ARCO Station 2035 Albany, California (Page 2 of 4)

| Well Date | Elevation of Wellhead | Depth to Water | Elevation of Groundwater | Evidence of Product |
|--------------|--------------------------|-------------------|--------------------------|------------------------|
| | | | | |
| MW-2 (cont.) | | | | |
| 12/16/92 | | 9.82 | 30.56 | None |
| 01/13/93 | | 8.25 | 32.13 | None |
| 02/22/93 | | 8.25 | 32.13 | None |
| 03/25/93 | | 8.82 | 31.56 | None |
| 04/13/93 | | 9.30 | 31.08 | None |
| 05/22/93 | | 10.57 | 2 9.81 | None |
| 06/17/93 | | 10.25 | 30.13 | None |
| 07/27/93 | | 10.48 | 29.90 | None |
| 08/24/93 | | 10.82 | 29.56 | None |
| 12/08/93 | | 10.68 | 29,70 | None |
| 02/01/94 | | 9.66 | 30.72 | None |
| 1 | | | | |
| <u>MW-3</u> | | | | |
| 10/29/91 | 41.44 | 11.62 | 29.82 | None |
| 11/07/91 | | 11.52 | 29.92 | None |
| 11/14/91 | | 11.50 | 29.94 | None |
| 01/19/92 | | 10.56 | 30.88 | None |
| 02/19/92 | | 9.52 | 31.92 | None |
| 03/19/92 | | 9.01 | 32.43 | None |
| 04/21/92 | | 9.70 | 31.74 | None |
| 05/12/92 | | 10.29 | 31.15 | None |
| 06/12/92 | | 11.26 | 30.18 | None |
| 07/15/92 | | 11.28 | 30.16 | None |
| 08/07/92 | | 11.15 | 30.29 | None |
| 09/08/92 | | 11.70 | 29.74 | None |
| 10/26/92 | | 12.15 | 29.29 | None |
| 11/23/92 | | 12.55 | 28.89 | None |
| 12/16/92 | | 10.15 | 31,29 | None |
| 01/13/93 | | 9.12 | 32.32 | None |
| 02/22/93 | | 8.18 | 33.26 | None |
| 03/25/93 | | 8.57 | 32.87 | None |
| 04/13/93 | | 9.55 | 31.89 | None |
| 05/22/93 | | 10.56 | 30,88 | None |
| 06/17/93 | | 10.41 | 30.70 | None |
| 07/27/93 | | 10.53 | 30.91 | None |
| 08/24/93 | | 10.86 | 30.58 | None |
| 12/08/93 | | 10.91 | 30.53 | None |
| 02/01/94 | | 9.71 | 31.73 | None |

See notes on page 4 of 4.



TABLE 1 CUMULATIVE GROUNDWATER MONITORING DATA ARCO Station 2035 Albany, California (Page 3 of 4)

| Well Date | Elevation of Wellhead | Depth to Water | Elevation of Groundwater | Evidence of Product |
|--------------|--------------------------|-------------------|--------------------------|---------------------------------------|
| | | <u></u> | | |
| <u>MW-4</u> | | | | |
| 01/13/93 | 40.33 | 8.05 | 32.28 | None |
| 02/22/93 | | 7.58 | 32.75 | None |
| 03/25/93 | | 8.27 | 32.06 | None |
| 04/13/93 | | 8.54 | 31.79 | None |
| 05/22/93 | | 9.52 | 30.81 | None |
| 06/17/93 | | 9.53 | 30.80 | None |
| 07/27/93 | | 10.14 | 30.19 | None |
| 08/24/93 | | 10.42 | 29.91 | None |
| 12/08/93 | | 10.31 | 30.02 | None |
| 02/01/94 | | 9.10 | 31.23 | None |
| | | | | · · · · · · · · · · · · · · · · · · · |
| <u>MW-5</u> | | | | * |
| 01/13/93 | 41.84 | 8.22 | 33.62 | None |
| 02/22/93 | | 7.92 | 33.92 | None |
| 03/25/93 | • | 8.67 | 33.17 | None |
| 04/13/93 | | 9.18 | 32.66 | None |
| 05/22/93 | | 10.12 | 31.72 | None |
| 06/17/93 | | 10.03 | 31.81 | None |
| 07/27/93 | | 10.74 | 31.10 | None |
| 08/24/93 | | 11.02 | 30.82 | None |
| 12/08/93 | | 10.92 | 30.92 | None |
| 02/01/94 | | 9.74 | 32.10 | None |
| MW-6 | | | | |
| 01/13/93 | 40.13 | 9.84 | 30,29 | None |
| 02/22/93 | | 9.94 | 30.19 | None |
| 03/25/93 | | 10.68 | 29.45 | None |
| 04/13/93 | | 11.12 | 2 9.01 | None |
| 05/22/93 | | 11.74 | 28.39 | None |
| 06/17/93 | | 11.75 | 28.38 | None |
| 07/27/93 | | 12.20 | 27.93 | None |
| 08/24/93 | | 12.41 | 27.72 | None |
| 12/08/93 | | 10.11 | 30.02 | None |
| 02/01/94 | | 11.80 | 28.33 | None |
| RW-1 | | | | |
| 10/29/91 | 40.33 | 10.85 | 29.48 | Sheen |
| 11/07/91 | | 11.97 | 28.36 | 0.01 |
| 11/14/91 | | 11.03 | 29.30 | 0.01 |
| 01/19/92 | | 10.22* | 30.11* | 3.26 |
| 02/19/92 | | 8.49* | 31.84* | 2.14 |

See notes on page 4 of 4.



TABLE 1 CUMULATIVE GROUNDWATER MONITORING DATA ARCO Station 2035

Albany, California (Page 4 of 4)

| Well Date | Elevation of Wellhead | Depth to Water | Elevation of Groundwater | Evidence of Product |
|---------------------|-----------------------|-------------------|--------------------------|------------------------|
| <u>RW-1 (cont.)</u> | | | | |
| 03/19/92 | | 8.50* | 31.83* | 0.50 |
| 04/21/92 | | 9.68* | 30.65 | 0.03 |
| 05/12/92 | 40.33 | 10.47 | 29.86 | Product not measured |
| 06/12/92 | | 11.41 | 28.92 | |
| 07/15/92 | | 11.35 | 28.98 | Product not measured |
| 08/07/92 | | 10.80* | 29.53* | None |
| 09/08/92 | | 10.80* | 29.53* | 0.02 |
| 10/26/92 | | 11.42* | 28.91* | 0.62 0.04 |
| 11/23/92 | | 10.94 | 29.39 | |
| 12/16/92 | | 9.78* | 30.55* | Sheen 0.51 |
| 01/13/93 | | 8.35 | 31.98 | |
| 02/22/93 | | 7.94* | 32.39* | Product in skimmer |
| 03/25/93 | | 8.81 | 31.52 | 0.01 |
| 04/13/93 | | 9.67** | NC** | None |
| 05/22/93 | | 10.04 | 30.29 | Product not measured |
| 06/17/93 | | 10.26* | 30.07* | Sheen |
| 07/27/93 | | 10.58 | 29.75 | 0.01 in bailer |
| 08/24/93 | | 10.80* | 29.73 29.53* | Sheen |
| 12/08/93 | | 10.46* | 29.87* | 0.05 |
| 02/01/94 | | 1.00 | 39.33 | 0.30 |
| , , | | 1.00 | 39.33 | None |
| AS-1*** | | | | |
| 08/24/93 | 41.03 | 10.97 | 30.06 | N |
| , , | 12.00 | 10.77 | 30,06 | None |
| AS-2*** | | | | |
| 08/24/93 | 40.31 | 10.45 | 29.86 | None |

Notes:

Depth-to-water measurements in feet below the top of the well casing.

* = Adjusted water level due to product. The recorded thickness of the floating product was multiplied by 0.80 to obtain an approximate value for the displacement of water by the floating product. This approximate displacement value was then subtracted from the measured depth to water to obtain a calculated depth to water. These calculated groundwater depths were subtracted from surveyed wellhead elevations to obtain the adjusted groundwater elevations.

** = Well contained product of unknown thickness. Groundwater elevation could not be corrected, therefore it was not used in gradient evaluation.

Wells AS-1 and AS-2 were monitored during Third Quarter 1993 as a one-time event in conjunction with an air-sparge pilot test performed at the site.



TABLE 2 CUMULATIVE RESULTS OF LABORATORY ANALYSES OF WATER SAMPLES - TPHg and BTEX ARCO Station 2035 Albany, California (Page 1 of 2)

| Well | | | (1 age 1 | <u> </u> | | | |
|--------------|-------|-------|----------|----------------|-------|-------------|--|
| Date | ТРНд | В | T | E | х | | |
| MW-1 | | | | | | | |
| 10/29/91 | 620 | 76 | 46 | | | | |
| 03/19/92 | 6,500 | | 69 | 15 | 60 | | |
| 06/12/92 | 2,900 | 2,600 | 89 | 42 | 290 | | |
| 09/08/92 | 820 | 1,100 | 2.5 | 21 | 15 | | |
| 10/26/92 | 190 | 350 | <5* | <5* | <5* | | |
| 01/13/93 | 430 | 68 | < 0.5 | 0.6 | < 0.5 | | |
| 04/13/93 | 5,300 | 130 | 5.3 | 5.0 | 9.0 | | |
| 08/24/93 | 630 | 2,100 | <20* | 63 | 36 | | |
| 12/08/93 | 81 | 230 | <2.5* | 3.1 | 3.3 | | |
| 02/01/94 | | 20 | <0.5 | 0.9 | < 0.5 | | |
| 02/01/74 | <50 | 13 | < 0.5 | 0.5 | 0.6 | | |
| <u>M</u> W-2 | | | | | | | |
| 10/29/91 | | | | | | | |
| | <60 | 2.4 | 4.6 | 0.48 | 2.3 | | |
| 03/19/92 | <50 | 6.8 | 0.9 | < 0.5 | 1.1 | | |
| 06/12/92 | <50 | < 0.5 | < 0.5 | <0.5 | <0.5 | | |
| 09/08/92 | <50 | < 0.5 | <0.5 | < 0.5 | < 0.5 | | |
| 10/26/92 | <50 | < 0.5 | < 0.5 | < 0.5 | < 0.5 | | |
| 01/13/93 | <50 | < 0.5 | < 0.5 | < 0.5 | < 0.5 | | |
| 04/13/93 | < 50 | < 0.5 | < 0.5 | < 0.5 | < 0.5 | | |
| 08/24/93 | <50 | < 0.5 | < 0.5 | < 0.5 | < 0.5 | | |
| 12/08/93 | <50 | < 0.5 | < 0.5 | < 0.5 | < 0.5 | | |
| 02/01/94 | <50 | < 0.5 | <0.5 | < 0.5 | < 0.5 | | |
| MW-3 | | | | | | | |
| 10/29/91 | 32 | 2.1 | 2.8 | 0.35 | 1.0 | | |
| 03/19/92 | 2,100 | 780 | 8.8 | 16 | 1.8 | | |
| 06/12/92 | 720 | 210 | <2.5* | 23 | 58 | | |
| 9/08/92 | < 50 | 5.3 | <0.5 | <0.5 | 4.0 | | |
| 0/26/92 | <50 | 0.6 | < 0.5 | < 0.5 < 0.5 | < 0.5 | | |
| 01/13/93 | <50 | 1.1 | < 0.5 | < 0.5 < 0.5 | <0.5 | | |
| 4/13/93 | 68 | 13 | <0.5 | | <0.5 | | |
| 08/24/93 | <50 | < 0.5 | <0.5 | 1.6 | 1.1 | | |
| 2/08/93 | <50 | <0.5 | <0.5 | <0.5 | <0.5 | | |
| 2/01/94 | <50 | 1.9 | <0.5 | < 0.5 | <0.5 | | |
| • | | 1.7 | | 2.1 | < 0.5 | | |
| <u>MW-4</u> | | | | | | | |
| 01/13/93 | < 50 | < 0.5 | 1.3 | 40 ° | | | |
| 4/13/93 | <50 | <0.5 | < 0.5 | <0.5 | 1.6 | | |
| 8/24/93 | <50 | <0.5 | | < 0.5 | <0.5 | | |
| 2/08/93 | <50 | < 0.5 | < 0.5 | <0.5 | < 0.5 | | |
| 2/01/94 | <50 | < 0.5 | <0.5 | < 0.5 | <0.5 | | |
| | 7.50 | <050 | < 0.5 | < 0.5 | < 0.5 | | |

See notes on page 2 of 2.



TABLE 2 CUMULATIVE RESULTS OF LABORATORY ANALYSES OF WATER SAMPLES - TPHg and BTEX ARCO Station 2035 Albany, California (Page 2 of 2)

| | | | (B | <i>-</i> , | | |
|--------------|--------------|--------------|------------------|----------------|-------|-------------|
| Well Date | ТРН | В | Т | Е | х | |
| | | | | | | |
| MW-5 | | | | | | |
| 01/13/93 | < 50 | < 0.5 | < 0.5 | -0.5 | | |
| 04/13/93 | <50 | < 0.5 | < 0.5 | < 0.5 | < 0.5 | |
| 08/24/93 | <50 | < 0.5 | < 0.5 | < 0.5 | <0.5 | |
| 12/08/93 | <50 | < 0.5 | <0.5 | < 0.5 | <0.5 | |
| 02/01/94 | <50 | < 0.5 | | <0.5 | < 0.5 | |
| -,, | 450 | <0.5 | <0.5 | < 0.5 | < 0.5 | |
| MW-6 | | | | | | |
| 01/13/93 | <50 | <0.5 | <0.5 | | | |
| 04/13/93 | <50 | < 0.5 | | < 0.5 | <0.5 | |
| 08/24/93 | < 5 0 | < 0.5 | <0.5 <0.5 | < 0.5 | <0.5 | |
| 12/08/93 | <50 | < 0.5 | | < 0.5 | < 0.5 | |
| 02/01/94 | <50 | <0.5 | <0.5 | < 0.5 | <0.5 | |
| , , , | 130 | <0.5 | < 0.5 | < 0.5 | < 0.5 | |
| <u>RW-1</u> | | | | | | |
| 10/29/91 | | | Ta.4 | | | |
| 03/19/92 | | N-+ | lot sampled-shee | n _ | | |
| 06/12/92 | | NOT Sa | mpled-floating p | roduct | | |
| 09/08/92 | | Not sa | mpled-floating p | roduct | | |
| 10/23/92 | | Not sa | mpled-floating p | roduct | | |
| 01/13/93 | | Not sa | mpled-floating p | roduct | | |
| 04/13/93 | | Not sampled | floating product | in skimmer | | |
| 08/24/93 | | Not sa | mpled-floating p | roduct | | |
| 12/08/93 | | Not sa | mpled-floating p | roduct | 1 | |
| 02/01/94 | | Not sa | mpled-floating p | roduct | | |
| ~~, VII)~ | | Not sampledc | onnected to reme | diation system | | |
| AS-1** | | | | | | |
| 08/24/93 | 2,400 | 70 | .= | _ | | |
| , , , , , | 4,400 | 78 | 87 | 52 | 370 | |
| AS-2** | | | | | | |
| 08/24/93 | 30,000 | 1 200 | 0.000 | | | |
| | 50,000 | 1,300 | 2,800 | 980 | 5,900 | |
| MCL: | | | | | | |
| | | 1 | | 680 | 1,750 | |
| DWAL: | | | 100 | | | |

Notes:

Results in parts per billion (ppb).

TPHg Total petroleum hydrocarbons as gasoline using EPA Method 5030/8015/8020.

BIEX B: benzene, T: toluene, E: ethylbenzene, X: total xylenes isomers, analyzed using EPA Method 5030/8015/8020. <

Results reported below the laboratory detection limit.

Laboratory Raised Methods Reporting Limit (MRL) due to high analyte concentration requiring sample dilution.

Wells AS-1 and AS-2 were monitored during Third Quarter 1993 as a one-time event in conjunction with an air-sparge pilot

test performed at the site.

MCL State Maximum Contaminant Level (October 1990).

DWAL State Drinking Water Action Level (October 1990).



TABLE 3 CUMULATIVE RESULTS OF LABORATORY ANALYSES OF WATER SAMPLES - TPHd, TOG, VOC, BNAs, PCB and Metals ARCO Station 2035 Albany, California

| Well Date | ТРНа | TOG | voc | BNAs | РСВ | Cd | Cr | Pb | Ni | Zn |
|-------------------------|----------|--------------|----------|--------|----------|-----------|-----|----|----------|----------|
| | | | | | | | | | <u> </u> | |
| <u>MW-3</u> 10/29/91 | NA | <5,000 | KIFM | B.T.A | | 4.0 | | | | |
| 03/19/92 | NA NA | NA | ND' | NA | NA | <10 | <10 | <5 | <50 | 45 |
| 06/12/92 | NA | | NA | NA | NA | NA | NA | NA | NA | NA |
| 09/08/92 | NA NA | NA | NA | NA | NA | NA | NA | NA | NA | NA |
| | | NA | NA. | NA | NA | NA | NA | NA | NA | NA |
| 10/26/92 | <50 | (600)[600] | ND_{p} | NA | NA | NA | NA | NA | NA | NA |
| 12/01/92 | NA | NA. | NA | ND^c | ND^{4} | NA | NA | NA | NA | NA |
| 01/13/93 | NA | (780)[1,100] | NA | NA | NA | NA | NA | NA | NA | NA |
| 04/13/93 | NA | (<0.5)[<0.5] | l NA | NA | NA | NA | NA | NA | NA | NA NA |
| 08/24/93 | NA | (<0.5)[<0.5] | | NA | NA | NA | NA | NA | NA | |
| 12/08/93 | NA | (900)[500] | | NA | NA | NA | NA. | | | NA |
| 02/01/94 | NA | (<500)[<500 | | NA | NA | | | NA | NA | NA |
| _ | | (1500)[1500 | 71.40 | na . | | NA ——— | NA | NA | NA | NA |
| MCL: | | | - | | 10 | 50 | 50 | _ | | |

Notes:

Results in parts per billion (ppb).

TPHd Total petroleum hydrocarbons as diesel analyzed using EPA Method 3510/California DHS LUFT Method. TOG Total oil and grease analyzed using Standard Method 5520B&F or 5520C (780) and 5520F [1.100]. **VOCs** Volatile organic compounds analyzed using EPA Method 624. **BNAs** Semivolatile organic compounds analyzed using EPA Method 3510/8270. **PCBs**

Polychlorinated biphenyls analyzed using EPA Method 3510/8080. Cđ

Cadmium analyzed using EPA Method 200.7. Cr Chromium analyzed using EPA Method 200.7. Ni Nickel analyzed using EPA Method 200.7. Zn Zinc analyzed using EPA Method 200.7. Pb = Lead analyzed using EPA Method 3010. NA

Not analyzed. Results reported below the laboratory detection limit.

ND Not detected; detection limit varied according to analyte.

All 37 compounds were nondetectable except for toluene (3.0 ppb).

All 41 compounds analyzed were nondetectable. All 34 compounds analyzed were nondetectable. All 7 compounds analyzed were nondetectable.

MCL State Maximum Contaminant Level (October 1990).



TABLE 4 APPROXIMATE CUMULATIVE PRODUCT RECOVERED ARCO Station 2035 Albany, California

| Well | YEAR | Product Recovered (gallons) | |
|------|----------------|-----------------------------|--|
| RW-1 | | | |
| | 1992 TOTAL: | 22.30 | |
| | 1993 TOTAL: | 1.0 | |
| | 1994 TO DATE: | 0.0 | |
| | TOTAL TO DATE: | 23.30 | |

| R | 45 | VA |
|---------|--------------|-------|
| Working | to Restore N | ature |

| | | | | | | | VAPOR H | XTRAC RCO Su | TAI TION S Ition 203 | TABLE 5 IN SYSTEM of 2035, Alban (Page 1 of 2) | TABLE 5 EXTRACTION SYSTEM OPERATION ARCO Station 2035, Albany, California (Page 1 of 2) | TABLE 5 VAPOR EXTRACTION SYSTEM OPERATION DATA ARCO Station 2035, Albany, California (Page 1 of 2) | | | | | |
|----------|--------------------------|----------|------------------|--------------|--------|-----------|----------------------|-----------------|----------------------------|--|---|--|---|---|-----------------|-----------------|-----------------|
| | | | VAPOR EXTRACTION | EXTRA | | VELLS (| WELLS ON LINE STATUS | STATU | | | COMB | DIL | INF | INF | TPHg | TPHE | TPHg |
| | . VM. □ | 7.W | 3 & | V W 4 | Ϋ́W | λ.γ. 9 | W L | ≱ ∞ | 3. | RW 1 | FLOW (scfm) | FLOW (scfm) | (scfm) | (JAC) | CONC (mg/m³) | CONC (mg/m²) | CONC (mg/m³) |
| 12/07/93 | ` | | | ` | \ | ` | ` | ` | ` | ` | 10 | 8 | 100 | ΣZ | 10.000 | 1.400 | 72 |
| 12/08/93 | | | | | SY | STEM S | HUTDO | WN AN | NOT S | AMPLE | D DUE T | O A FAILI | SYSTEM SHUTDOWN AND NOT SAMPLED DUE TO A FAILED SAMPLING PUMP | NG PUMP | 200/54 | Port's | |
| 12/09/93 | ` | ` | ` | ` | ` | ` | <u> </u> | ` | ` | ` | 10 | 8 | 100 | 9 | SZ | 1400 | 130 |
| 12/10/93 | ` | | ` | ` | ` | ` | `` | \ | ` | ` | 5 | 82 | 87 | 88 | SZ | 1.500 | 7 |
| 12/15/93 | ` | ` | ` | ` | • | / | ` | ` | ` | | 45 | 55 | 100 | 3 | Ş | 1 800 | i y |
| 12/16/93 | | | | | SYSTEN | ¶ SHUTI | DOWN 1 | 2/16/93 | TO 12/2 | 1/93 DU | E TO FAI | LURE OF | THE PRO | SYSTEM SHUTDOWN 12/16/93 TO 12/21/93 DUE TO FAILURE OF THE PROCESS BLOWER | | | |
| 12/21/93 | ` | ` | ` | ` | , | , | • | ` | ` | - | 50 | 08 | 901 | 48 | SN | NS | SN |
| 12/25/93 | | | | S | YSTEM | SHUTD | OWN 12 | /25/93 T | 0 12/29, | /93 DUE | TO A CC | NTROL F | AULT OF | SYSTEM SHUTDOWN 12/25/93 TO 12/29/93 DUE TO A CONTROL FAULT OF THE OXIDIZER | ZER | | |
| 12/29/93 | ` | <u>\</u> | ` | ` | \ | ` | ` | ` | ` | | \$2 | 24 | 82 | 09 | SN | SZ | SN |
| 12/31/93 | | | | | SYSTEN | SHUT | DOWN 1 | 2/31/93 | DUE TO | HIGH | LIQUID I | EVEL IN | THE KNO | SYSTEM SHUTDOWN 12/31/93 DUE TO HIGH LIQUID LEVEL IN THE KNOCKOUT DRUM | M D M | | |
| 01/07/94 | ` | ` | ` | ` | ` | ` | `` | ` | 1 | | 37 | 23 | 99 | 6 | NS | SN | SNS |
| 01/12/94 | ` | ` | • | ` | ` | ` | ^ | , | 1 | | 41 | 23 | 2 | 42 | NS | 2.500 | 52 |
| 01/24/94 | | | | | | SYSTE | M SHU | DOWN | 1/24/94 | DUE TO | O NO AV | AILABLE | SYSTEM SHUTDOWN 1/24/94 DUE TO NO AVAILABLE WELL SCREEN. | EEN. | | | |
| Œ | SEE NOTES ON PAGE 2 OF 2 | (GE 2 0) | F 2. | | | | | | | | | | | | , | | ing |
| | | | | | | | | | | | | | | | | | t |



VAPOR EXTRACTION SYSTEM OPERATION DATA ARCO Section 2035, Albany, California (Page 2 of 2)

COMB WELL FLOW = Combined Well Flow Rates

DIL AIR FLOW = Dilution Air Flow Rate

INF FLOW = Influent Flow Rate to therm-ox (well plus dilution flows)

scfm = standard cubic feet per minute

INF VAC = Influent Vacuum

"WC = inches of water column vacuum

TPHg = Total petroleum hydrocarbons as gasoline
WELL TPHg CONC = Concentration of TPHg vapor in combined well flow
TPHg INF CONC = Concentration of TPHg vapor in therm-ox influent flow
TPHg EFF CONC = Concentration of TPHg vapor in therm-ox effluent flow

mg/m³ = milligrams per cubic meter ✓ = Vapor Extraction Well Online

NS = Not Sampled

NM = Not Measured



TABLE 6 CUMULATIVE RESULTS OF LABORATORY ANALYSES OF AIR SAMPLES ARCO Station 2035, Albany, California (Page 1 of 2)

| Sample Location & Date | Sample ID | ТРНд | Benzene | Toluene | Ethylbenzene | Total Xylenes | |
|------------------------------|-----------------------|--------|---------|---------|--------------|------------------|---|
| <u>VW-1</u> 12/09/93 | AS-HV-1 | 9,700 | 990 | 430 | <0.05 | 38 | |
| <u>VW-2</u> 12/09/93 | AS-HV-2 | 21,000 | 1,200 | 630 | 79 | 240 | · |
| <u>VW-3</u> 12/09/93 | AS-HV-3 | 8,000 | 270 | 400 | 57 | 200 | |
| <u>VW-4</u> 12/09/93 | AS-HV-4 | 9,000 | 250 | 320 | 44 | 140 | |
| <u>VW-5</u> 12/09/93 | AS-HV-5 | 2,100 | 11 | 280 | 32 | 110 | |
| <u>VW-6</u> 12/09/93 | AS-HV-6 | 9,600 | 450 | 330 | 46 | 140 | |
| <u>VW-7</u> 12/09/93 | AS-HV-7 | 12,000 | 1,300 | 480 | 32 | 91 | |
| <u>VW-8</u> 12/09/93 | AS-HV-8 | 4,900 | 89 | 38 | < 0.05 | 18 | |
| <u>VW-9</u> 12/09/93 | AS-HV-9 | 6,600 | 130 | 74 | 58 | 120 | |
| <u>RW-1</u> 12/09/93 | AS-HV-10 | 6,800 | 130 | 82 | 36 | 77 | |
| ALL WELL 12/07/93 | S AS-COMBINE WELLS | 10,000 | 540 | 300 | 31 | 100 | |

See notes on page 2 of 2.



TABLE 6 CUMULATIVE RESULTS OF LABORATORY ANALYSES OF AIR SAMPLES

ARCO Station 2035, Albany, California (Page 2 of 2)

| Sample Location & Date | Sample ID | TPHg | Benzene | Toluene | Ethylbenzene | Total Xylenes |
|------------------------------|-------------|-------|---------|---------|--------------|------------------|
| INFLUENT | | | | | | |
| 12/07/93 | AS-INFLUENT | 1,400 | 38 | 22 | 3.5 | 11 |
| 12/09/93 | AS-INFLUENT | 1,400 | 60 | 67 | 3.5 17 | 11 |
| 12/10/93 | AS-INFLUENT | 1,500 | 100 | 39 | 6.1 | 55 |
| 12/15/93 | AS-INFLUENT | 1,800 | 79 | 73 | 13 | 19 |
| 01/12/94 | AS-INFLUENT | 2,500 | 37 | 140 | 13 27 | 42 110 |
| EFFLUENΓ | | | | | | |
| 12/07/93 | AS-EFFLUENT | 76 | 2.3 | 4.8 | 2.1 | 7.2 |
| 12/09/93 | AS-EFFLUENT | 130 | 3.1 | 21 | 4.6 | 15 |
| 12/10/93 | AS-EFFLUENT | 21 | < 0.05 | 1.7 | 1.4 | |
| 01/12/94 | AS-EFFLUENT | 52 | 0.93 | 2.4 | 1.1 | 5.0 7.4 |

Notes:

Results in milligrams per cubic meter (mg/m³), equivalent to micrograms per liter (μ g/l).

TPHg = Total petroleum hydrocarbons as gasoline

BTEX and TPHg analyzed using EPA method 5030/8015/8020.

ALL WELLS = Sample taken before fresh air dilution.

INFLUENT = Samples taken after fresh air dilution before entering Therm-Ox.

EFFLUENT = Samples taken from exhaust stack of Therm-Ox.



52

324

| | | VAPOR EXT | | TABLE 7 /STEM ESTIMATED ARCO Station 2035 Albany, California | GASOLINE REMO | OVAL | |
|----------------------------------|-------------------|---------------------------------|----------------------|--|---------------------------------------|----------------------------|-----------------------------|
| The first transfer of the course | ATING IOD I | OPERATING HRS THIS PERIOD | TOTAL HOURS IN | PERCENT OF TIME OPERATIONAL | ESTIMATED EXTRACTION RATE (ppd) | TOTAL POUNDS REMOVED | TOTAL GALLONS REMOVED |
| FROM | то | | PERIOD | | (Ma) | KEMOVED | REMOVED |
| 1/01/94 | 1/07/94 | 0 | 158 | 0 % | SYSTEM SHUTDOWN | | |
| 1/07/94 | 1/12/94 | 123 | 123 | 100 % | 11.6 | 59 | 9.5 |
| 1/12/94 | 1/24/94 | 285 | 288 | 99 % | 14.4 | 171 | 27 |
| 1/24/94 | 3/31/94 | 0 | 1,591 | 0 % | SYSTEM SHUTDOWN | | N |
| TOTAL THIS QUARTER | | 408 | 2,160 | 19 % | 4 | 230 | 37 |

27 %

NOTES:

STARTUP

TOTAL SINCE

ppd = Pounds per day Example Calculations:

Extraction Rate (ppd) = Inf. Conc. $(\mu g/\ell)$ x Total Flow(scfm) x 1,440 min/day x 1 lb/454,000,000 μ g x 28.32 ℓ/ft^3

Pounds Removed = Operating hours(hrs) ÷ 24(hrs/day) x Extraction rate(lb/day)

2,745

Gallons Removed = Pounds removed(lbs) ÷ 6.22 (lbs/gal)

| SAMPLING DATE | AND CONTROL OF CONTROL PROTECTION AND AND CONTROL OF CO | ENE EMISSION ATE (ppd) |
|---------------|--|---------------------------|
| | | |

TPHg = Total purgeable hydrocarbons as gasoline

ppd = Pounds per day

Example Calculations:

Destruction efficiency (%) = [TPHg Inf. Conc. - TPHg Eff. Conc.]/TPHg Inf. Conc. x 100 Emission Rate (lb/day) = Eff. Conc.(μ g/ ℓ) x Total Flow(scfm) x 1,440 min/day x 1 lb/454,000,000 μ g x 28.32 ℓ /ft³



APPENDIX A

IWM'S SUMMARY OF GROUND WATER SAMPLE ANALYSES, FIELD REPORT, GROUND WATER SAMPLE FIELD DATA SHEETS, AND CERTIFIED ANALYTICAL REPORTS WITH CHAIN-OF-CUSTODY RECORD

I NTEGRATEDW ASTESTREAMM ANAGEMENT, INC.



February 22, 1994

Mr. John Young RESNA Industries 3315 Almaden Expressway Suite 34 San Jose, CA. 95118

Dear Mr. John Young:

Attached are the field data sheets and analytical results for quarterly ground water sampling at ARCO Facility No. A-2035 in Albany, California. Integrated Wastestream Management measured the depth to water and collected samples from wells at this site on February 1, 1994.

Sampling was carried out in accordance with the protocols described in the "Request for Bid for Quarterly Sampling at ARCO Facilities in Northern California".

Please call us if you have any questions.

Sincerely,

Integrated Wastestream Management

Tom DeLon

Project Manager

Walter H. Howe

Registered Geologist

I NTEGRATED

W ASTESTREAM

M ANAGEMENT

Summary of Ground Water Sample Analyses ARCO Facility No. A-2035, Albany, California

| | RW-1 | 2/1/94 | 1.00 | NONE | NA | * | | ** | * | * | * | | NA | | NA |
|--------------------------|-------------|--------------|----------------|-------|-------------------|------|------|---------|---------|--------------|---------|-----------|--------------|-----------|--------------|
| Carrier 2 | MW-6 | 2/1/94 | 11.80 | NONE | NA | N.D. | | N.D. | N.D. | N.D. | N.D. | | NA | | NA |
| Same target and the same | MW-5 | 2/1/94 | 9.74 | NONE | NA | N.D. | | N.D. | N.D. | N.D. | N.D. | | NA | | NA |
| mr.v. a.d | MW-4 | 2/1/94 | 9.10 | NONE | NA | N.D. | | N.D. | N.D. | N.D. | N.D. | | NA | | NA |
| . | MW-3 | 2/1/94 | 9.71 | NONE | NA | N.D. | | 1.9 | N.D. | 2.1 | N.D. | | N.D. | | N.D. |
| | MW-2 | 2/1/94 | 99.6 | NONE | NA | N.D. | | N.D. | N.D. | N.D. | N.D. | | NA | | NA |
| | MW-1 | 2/1/94 | 9.29 | NONE | NA | N.D. | | 13 | N.D. | 0.5 | 9.0 | | NA | | NA |
| | WELL NUMBER | DATE SAMPLED | DEPTH TO WATER | SHEEN | PRODUCT THICKNESS | TPHg | BTEX | BENZENE | TOLUENE | ETHLYBENZENE | XYLENES | SM 5520 C | OIL & GREASE | SM 5520 F | HYDROCARBONS |

FOOTNOTES:

Concentrations reported in ug/L (ppb).

TPHg = Total Purgeable Petroleum Hydrocarbons (USEPA Method 8015 Modified)

BTEX Distinction (USEPA Method 8020)

PCE = Tetrachloroethene (USEPA Method 8010)

DCE = cis-1, 2-Dichloroethene (USEPA Method 8010)

TCE = Trichloroethene (USEAP Method 8010)

N.D. = Not Detected. NA = Not applicable

** = Well obstruction, unable to sample

FIELD REPORT

DEPTH TO WATER / FLOATING PRODUCT SURVEY

SITE ARRIVAL TIME: 13FX

SITE DEPARTURE TIME: 730

WEATHER CONDITIONS: SWANDLY / TOU

| DATE: 9-41-94/ | 1/10/00/00/00 | LETAINCACOUNTY OF WEEK: //COM | |
|----------------|---------------|-------------------------------|---|
| ROJECT NO.: | 200 2 - / | y | s |
| | | | |

| | | | | | | | | | | | 1-1 | ; | , <u>,</u> | | | | | |
|-------|--|------------------|--------|------|------------------------|----------|----------|-------------------|--------------------|---------------------------|-----------------------------|---------------------------|-------------------|--------------|---|---|---|--|
| | | MAIERIALS | | | | | | | | sed to | ON RK | obtained | Line for | 2 | | | | |
| | O LIVER NAME OF THE PARTY OF TH | 7 | 7.4 | p 7 | 41, | | id | 12 12 SAMOO SAMOO | Constitution for a | A bailer was not used for | subjective evaluation on RW | The results were obtained | by visual observa | Surface 2.0 | | | | |
| } | SHEEN (Y=YES, N=NO |) \ 2 | \sim | | | <u> </u> | <u> </u> | 45 | _ | | | | | | | | | |
| | FLOATING PRODUCT THICKNESS | 1/17 | 1 1 | | // | | - | 5 5 | | | | | | | | | - | |
| | DEPTH TO FLOATING PRODUCT (Feet) | N/4 | | | // | | | 93 | | | | | | | | | | |
| | SECOND DEPTH TO WATER (Feet) | 9.29 | 166 | 9.71 | 01.6 | 416 | 11. 80- | 00 1 | | | | | | | | | | |
| | FIRST DEPTH TO WATER (Feet) | 4.29 | 100 | | 216 | 116.6 | -08.7 | 00. | | | | | | | | | | |
| | TOTAL DEPTH (Feet) | Ho | 38.7 | 326 | 55.0 | 242 | 24.2 | 250 | | | | | | | | | | |
| | EXPANDING CAP | š | 3 | * | Ä | ¥ | 37 | | | | | | | | | | | |
| - | LOCK | | 3 | 7 | , Y | Ž | Y | .7 | | | | | | | | | - | |
| | GASKET | | | | 3 | * | Š | 75 | \perp | | \perp | \perp | | | | | | |
| - | LID SECURE | 3/4/ | | | \(\sum_{\frac{3}{2}}\) | (1/1) | 37/2 | 7.5 | _ | | _ | _ | _ _ | \downarrow | _ | | | |
| - | SURFACE SEAL | | 2 | š | × | | 3 | | | + | - | \perp | \perp | _ | _ | _ | | |
| | WELL ID | 1.00 | P.W.2 | M. 3 | 19:00-4 | Mus 5 | NW 6 | 19w./ | | | 3 | | | | | | | |
| L | DTW ORDER | 3 | ٠- | 7 | ^ | `\ | ٠,٠ | ·~ | | | | | | 1 | 1 | | | |

| PROJECT NO: | WELL ID: Μω'-5 |
|--|--|
| CLIENT/STATION #: ARCO 2 | C35 ADDRESS: 1621 GAN PABLO AVE |
| CASING DIAMETER (inches): 2 | 346812 Other |
| GALLON/LINEAR FOOT:0. | 17 0.38 0.66 1.5 2.6 5.8 Other |
| TD242 - DTW9:14 X GALLON 0:60 LINEAR FT. | X CASING 3 = CALCULATED 2363 ACTUAL 23.0 VOLUME PURGE PURGE 23.0 |
| DATE PURGED: 2-1-94 STA DATE SAMPLED: 2-1-94 STA | RT (2400 HR) <u>1455</u> END (2400 HR) <u>1501</u> RT (2400 HR) <u>1570</u> END (2400 HR) <u>1570</u> |
| TIME VOLUME pH (2400 HR) (GAL.) (UNITS) | E.C. TEMP. COLOR TURBIDITY (UMHOS/ (F) (VISUAL) (VISUAL) CM@25 C) |
| <u>1456 3 748</u> <u>1458 12 729</u> | 055 649 cloudy |
| <u>1459</u> <u>18</u> <u>7.22</u> <u>1501</u> <u>23</u> <u>7.19</u> | 052 64.1 clear |
| | |
| FIELD QC SAMPLES COLLECTED AT THIS | WELL (I.E., FB-1, XDUP-1): |
| PURGING EQUIPMENT | SAMPLING EQUIPMENT |
| 2" Bladder Pump Bailer (TEFLON) | 2° Bladder Pump Bailer (TEFLON) |
| ✓ Centrifugal Pump Bailer (PVC) | DDL Sampler Bailer (Stainless Steel) |
| Submersible Pump Bailer (Stainless Steel) |) Dipper Submersible Pump |
| Dedicated | Bailer Disposable Dedicated |
| Other: | Other: |
| REMARKS: Well pumped | dry at 23 gallors |
| | |
| | PRINT NAME: Vace Valor |
| page 2 of <u>8</u> | SIGNATURE: Laid Tald' |

| PROJECT NO: | WELL ID: | MW-4 | | | | |
|---|--|---------------------------------------|--|--|--|--|
| CLIENT/STATION #: ARCO: | | | | | | |
| CASING DIAMETER (inches):2 | 3 4 6 8 12 | Other | | | | |
| GALLON/LINEAR FOOT: <u>0.</u> | 17 0.38 0.66 1.5 2.6 | Other | | | | |
| TD <u>25 C</u> - DTW ^{G, 10} X <u>GALLON</u> <u>C.w.</u> LINEAR FT. | VOLUME PU | TLATED 31.48 ACTUAL 28 C | | | | |
| DATE PURGED: $\frac{2-1-74}{2-1-94}$ STADATE SAMPLED: $\frac{2-1-94}{2-1-94}$ STA | RT (2400 HR) $\frac{7575}{200}$ END RT (2400 HR) $\frac{7500}{200}$ END |) (2400 HR) 1500- 0 (2400 HR) 1504 | | | | |
| TIME VOLUME pH (2400 HR) (GAL.) (UNITS) | E.C. TEMP. (UMHOS/ (F) CM@25 C) | COLOR TURBIDITY (VISUAL) (VISUAL) | | | | |
| 1516 4 657 | 047 660 | Cloudy | | | | |
| 1518 11 6.46 | | clian _ | | | | |
| 1519 16 6.42 | 0.42 659 | <u> Chan</u> | | | | |
| <u>1520</u> <u>35</u> 6.35 | | <u>lean</u> | | | | |
| 1522 <u>645</u> | <u> 656</u> | clear | | | | |
| FIELD QC SAMPLES COLLECTED AT THIS | WELL (I.E., FB-1, XDUP-1): | | | | | |
| PURGING EQUIPMENT | SAMPLING I | SAMPLING EQUIPMENT | | | | |
| 2" Bladder Pump Bailer (TEFLON) | 2" Bladder Pump | Bailer (TEFLON) | | | | |
| Centrifugal Pump Bailer (PVC) | DDL Sampler | Bailer (Stainless Steel) | | | | |
| Submersible Pump Bailer (Stainless Steel | <u> </u> | Submersible Pump | | | | |
| Dedicated Other: | Bailer Disposable | Dedicated | | | | |
| Outer. | Other: | | | | | |
| REMARKS: Well pumps | ed dry at 22 | ? sallen | | | | |
| | , | | | | | |
| | | | | | | |
| | | | | | | |
| | PRINT | NAME: Vince Valogs | | | | |
| PAGE 2 OF 2 | SIGN | NATURE: Juneant Julius | | | | |

| PROJE | CT NO: | | WELL ID: _ | MW-2 | • |
|----------------------|---|------------------------------------|-----------------------|--|-----------------------|
| CLIENT/S | STATION#: <u>ARCO 2</u> | 035 | ADDRESS: _ | 1001 SAN P | ABLO AVE |
| | DIAMETER (inches): 2 /LINEAR FOOT: 0.1 | <u>3 4 6</u> 7 <u>0.38 0.66</u> | | , | er |
| тр <u>28-7</u> - ртw | 1966X GALLON O.66 LINEAR FT. | x <u>casing</u> 3 volume | = <u>CALCU</u> PUI | LATED 3760 | 9 ACTUAL 40.0 |
| DATE PU DATE SAI | RGED: 2-1-94 STAR MPLED: 2-1-94 STAR | RT (2400 HR) / RT (2400 HR) / | 538_end 552_end | (2400 HR) <u>/5</u> (2400 HR) <u>/5</u> | 76 52 |
| | OLUME pH GAL.) (UNITS) | E.C. (UMHOS/ CM@25 C) | TEMP. (F) | COLOR (VISUAL) | TURBIDITY (VISUAL) |
| 1540 <u>·</u> | 4 63c 10 652 | 0.67 C 68 | 663 | clocky clock | |
| 1542 1 1544 2 | <u>8</u> <u>6.55</u> <u>20</u> <u>2.61</u> | <u>0.70</u> <u>0.70</u> | 662 665 | clear clear | |
| 1596 £ | 40 6.42 | <u>(2.7)</u> | <u>(20.1</u> | clian | |
| | ES COLLECTED AT THIS V JRGING EQUIPMENT | VELL (I.E., FB-1, | XDUP-1): | | |
| 2" Bladder Pump | • | | | | |
| Centrifugal Pump | Bailer (TEFLON) | | | Bailer (TEFL | |
| Submersible Pump | Bailer (PVC) Bailer (Stainless Steet) | | L Sampler | Bailer (Stain) | |
| Dedicated | Danci (Statiuess Steet) | Dip | ler Disposable | Submersible | Pump |
| | | _ | • | Dedicated | |
| REMARKS: | | | | | |
| | | | | | |
| - | | | | · | |
| | | | PRINT | NAME: Vin | CE VBLOGES |
| PAGE 4 O | F _ { | | SIGN | ATURE: | La Jalais |

| PROJECT NO | | | WELL ID: | MW3 | |
|----------------------------------|-----------------------------------|--------------------------------|--|---------------------|--------------------------|
| CLIENT/STATIO | N#: <u>ARCO 20</u> | 735 | ADDRESS: | ICOI SAN | PABLO AVE |
| CASING DIAMET | TER (inches): 2 R FOOT: 0.17 | | 6 <u>8 12</u> 5 1.5 2.6 | | ner |
| TD 32 8 - DTW 9-7/ | X <u>GALLON かんし</u> LINEAR FT. | X <u>CASING</u> VOLUME | 3 = <u>CALCU</u> PU | JLATED 45. 7 RGE | Z/ ACTUAL Z PURGE_Z C |
| DATE PURGED: DATE SAMPLED: | 2-1-94 STAR 2-1-94 STAR | T (2400 HR) Z T (2400 HR) _ | / <u>// C/c</u> ENI // <u>// 2/</u> ENI |) (2400 HR) _/ | 615 |
| TIME VOLUME (2400 HR) (GAL.) | pH (UNITS) | E.C. (UMHOS/ CM@25 C) | ТЕМР. (F) | COLOR (VISUAL) | TURBIDITY (VISUAL) |
| 1607 <u>4</u> 1609 12 | <u>6.73</u> 6.65 | <u>063</u> <u>0.63</u> | (500 (4.) | clean Cloan | |
| 1611 <u>25</u> 1613 <u>36</u> | 6.01 | C.7C C.62 | <u>64.6</u> 250 | clear cloudy | |
| 1k15 44 | <u>(c.7)</u> | <u>0,62</u> | <u>648</u> | cloudy | |
| FIELD QC SAMPLES COL PURGING | LECTED AT THIS W EQUIPMENT | ELL (I.E., FB- | I, XDUP-1): SAMPLING I | | |
| 2" Bladder Pump | Bailer (TEFLON) | 2 | | Bailer (TEF | LON) |
| | Bailer (PVC) | | DDL Sampler | Bailer (Stair | ŕ |
| Submersible Pump | Bailer (Stainless Steel) | I | Dipper | Submersible | |
| Dedicated | | | Bailer Disposable | Dedicated | • |
| Other: | | Other: | | | |
| REMARKS: | | | | | |
| | | | | | |
| | | · | | | |
| | | | DDING | NAME: U.A. | 10 1/2/1/10 |
| PAGE 5 OF % | | | | IATURE: | in Teldi. |

| PROJECT NO: | WELL ID: MW-6 |
|---|---|
| CLIENT/STATION #: PRCO 2035 | ADDRESS: 1001 SAN PARLO QUE |
| CASING DIAMETER (inches): 2 3 GALLON/LINEAR FOOT: 0.17 0.38 TD 24.2 - DTW // 30 X GALLON (177 X VO DATE PURGED: 2-/-0/4 START (2 DATE SAMPLED: 2-/-0/4 START (2 TIME VOLUME pH (2400 Hr) (gal.) (units) (µm) | 4 6 8 12 Other 0.66 1.5 2.6 5.8 Other SING 3 = CALCUATED D. 32 PURGE PURGE 2400 Hr) 1632 END (2400 Hr) 1635 E.C. TEMPERATURE COLOR TURBIDITY 1005/cm @ 25° C) (°F) (visual) (visual) |
| $\frac{1637}{1635} = \frac{7}{1} = \frac{660}{1670} = 0$ | 73 667 Closely |
| | - Coaj |
| FIELD QC SAMPLES COLLECTED AT THIS WELL PURGING EQUIPMENT 2" Bladder Pump Bailer (Teflon®) Centrifugal Pump Bailer (PVC) Submersible Pump Bailer (Stainless Steel | SAMPLING EQUIPMENT 2" Bladder Pump Bailer (Teflon®) DDL Sampler Bailer (Stainless Steel) Dipper Submersible Pump |
| Other: | Bailer Disposable Dedicated Other: |
| REMARKS: | |
| | PRINT NAME. |
| AGE OF | SIGNATURE: SIGNATURE: |

| ٠٠٠ | OND WAILING | WINILIE LIE | LU DAT | A SHEET | Γ |
|---|---|------------------------|--|------------------|-----------------------|
| PROJECT NO: | | | | ・ ル・/ | • |
| CLIENT/STATION #: | ARCU 2035 | | | SAM PABL | 0 |
| CASING DIAMETER (incl GALLON/LINEAR FOOT: TD 2666 - DTW 9.2 | | _ | 8 1 2.6 5 | ACTUA | L /// m |
| DATE PURGED: DATE SAMPLED: | 2-1-94 START (| (2400 Hr) 1650 | END | (2400 Hr) / | 410 251 702 |
| TIME VOLUM (2400 Hr) (gal.) /65/ 6 /652 12 /653 23 /655 23 /657 41 | (units) (µn 1. 94 0 2.71 C. 4.67 C 4.65 0 | 75 (| MPERATURE (°F) 64 6 64.7 64.5 64.3 64.3 | | TURBIDITY (visual) |
| PURGING 2" Bladder Pump Centrifugal Pump Submersible Pump Dedicated Other: | COLLECTED AT THIS WELL GEQUIPMENT Bailer (Teflon®) Bailer (PVC) Bailer (Stainless Ste | 2" Blace | SAMPLING ladder Pump Sampler er r Disposable | Bailer (Subme | i |
| AGE OF | 8 | . PRINT NAME: | VIACE | Valdis | |
| AGE OF | <u>Z</u> | PRINT NAME: SIGNATURE: | Thrum | Valdes t Cald | <u> </u> |



February 16, 1994

Service Request No. SJ94-0166

Gina Austin Tom DeLon IWM 950 Ames Avenue Milpitas, CA 95035

Re: ARCO Facility No. A2035

Dear Ms. Austin/Mr. DeLon:

Attached are the results of the water samples submitted to our lab on February 7, 1994. For your reference, these analyses have been assigned our service request number SJ94-0166.

All analyses were performed consistent with our laboratory's quality assurance program. All results are intended to be considered in their entirety, and CAS is not responsible for use of less than the complete report. Results apply only to the samples analyzed.

Please call if you have any questions.

Respectfully submitted:

COLUMBIA ANALYTICAL SERVICES, INC.

Keoni A. Murphy

Laboratory Manager

KAM/kmh

Regional QA Coordinator



Analytical Report

Client:

IWM

Project:

ARCO Facility No.

A2035

Sample Matrix: Water

Dates Collected:

02/01/94

Date Received:

02/07/94

Date Extracted: Date Analyzed: N/A

Service Request:

N/A SJ94-0166

Oil and Grease, IR SM 5520 C Petroleum Hydrocarbons, IR SM 5520 F

Units: mg/L (ppm)

| Sample Name | Oil and Grease, IR | Hydrocarbons, IR |
|--------------|--------------------|------------------|
| MW-3 | ND | ND |
| Method Blank | ND | ND |
| MRL | 0.5 | 0.5 |

SMStandard Methods for the Examination of Water and Wastewater, 17th Ed., 1989.

Date: Horvary 16,19

[940166.XLW]Oil & Grease/2/16/94



Acronyms

ASTM American Society for Testing and Materials

CARB California Air Resources Board

CAS Number Chemical Abstract Service registry Number

CFC Chlorofluorocarbon

DEC Department of Environmental Conservation

DEQ Department of Environmental Quality

DHS Department of Health Services

DOE Department of Ecology

DOH Department of Health

EPA U. S. Environmental Protection Agency

GC Gas Chromatography

GC/MS Gas Chromatography/Mass Spectrometry

LUFT Leaking Underground Fuel Tank

MCL Maximum Contaminant Level is the highest permissible concentration of a

substance allowed in drinking water as established by the USEPA.

MDL Method Detection Limit

MRL Method Reporting Limit

NA Not Applicable

NAN Not Analyzed

NC Not Calculated

NCASI National Council of the Paper Industry for Air and Stream Improvement

ND Not Detected at or above the MRL

NR Not Requested

NIOSH National Institute for Occupational Safety and Health

PQL Practical Quantitation Limit

RCRA Resource Conservation and Recovery Act

SIM Selected Ion Monitoring

TPH Total Petroleum Hydrocarbons

VPH Volatile Petroleum Hydrocarbons



Analytical Report

Client:

IWM

Project:

Sample Matrix: Water

ARCO Facility No.

A2035

Dates Collected: Date Received:

02/01/94 02/07/94

Date Extracted: Date Analyzed:

N/A 02/08/94

Service Request:

SJ94-0166

BTEX and TPH as Gasoline EPA Methods 5030/8020/DHS LUFT Method

| | Analyte: Units: Method Reporting Limit: | Benzene μg/L (ppb) 0.5 | Toluene μg/L (ppb) 0.5 | Ethyl- benzene µg/L (ppb) 0.5 | Total Xylenes µg/L (ppb) 0.5 | TPH as Gasoline μg/L (ppb) |
|--------------|---|------------------------------|------------------------------|--|---------------------------------------|----------------------------------|
| Sample Name | | | | | | |
| MW-1 | | 13. | ND | 0.5 | 0.6 | ND |
| MW-2 | | ND | ND | ND | ND | ND |
| MW-3 | | 1.9 | ND | 2.1 | ND | ND |
| MW-4 | | ND | ND | ND | ND | ND |
| MW-5 | | ND | ND | ND | ND | ND |
| MW-6 | | ND | ND | ND | ND | ND |
| Method Blank | | ND | ND | ND | ND | ND |

Approved By:

[940166.XI,W]8020w1/2/16/94



APPENDIX A LABORATORY QC RESULTS



QA/QC Report

Client: Project:

Sample Matrix: Water

IWM

ARCO Facility No.

A2035

Dates Collected:

02/01/94

Date Received:

02/07/94

Date Extracted: Date Analyzed: N/A N/A

Service Request:

SJ94-0166

Initial Calibration Verification Petroleum Hydrocarbons, IR SM 5520 F Units: mg/L (ppm)

| <u>Analyte</u> | True <u>Value</u> | Result | Percent <u>Recovery</u> | CAS Acceptance <u>Criteria</u> |
|-----------------|----------------------|--------|----------------------------|--------------------------------------|
| Hydrocarbon Mix | 40. | 39. | 90. | 90-110 |

SMStandard Methods for the Examination of Water and Wastewater, 17th Ed., 1989.

Approved By:

[940166.XLW]O&Gccsw4/2/16/94

Page No..



QA/QC Report

Client:

IWM

Project:

ARCO Facility No.

A2035

Sample Matrix: Water

Dates Collected: 02/01/94 Date Received: 02/07/94 Date Extracted: N/A

Date Analyzed: N/A

Service Request: SJ94-0166

Laboratory Control Spike Summary Petroleum Hydrocarbons, IR SM 5520 F Units: mg/L (ppm)

| | | | | Perc | ent Re | covery |
|-----------------|-------------|------------|--------|------------|-------------|-------------------|
| A.v. Var | 5 4 7 1 | - | Result | Y 600 | r con | CAS Acceptance |
| Analyte | Spike Level | <u>LCS</u> | LCSD | <u>LCS</u> | <u>LCSD</u> | <u>Criteria</u> |
| Hydrocarbon Mix | 4. | 3.5 | 3.8 | 88. | 96. | 60-121 |

SM Standard Methods for the Examination of Water and Wastewater, 17th Ed., 1989.

Approved By:

Date: February 16,19

[940166.XLW]O&Glcsw5/2/16/94



QA/QC Report

Client:

IWM

Project:

ARCO Facility No.

A2035

Sample Matrix: Water

Date Received: Date Extracted:

Dates Collected:

02/01/94 02/07/94

Date Analyzed:

N/A 02/08/94

Service Request:

SJ94-0166

Surrogate Recovery Summary BTEX and Total Petroleum Hydrocarbons (TPH) as Gasoline EPA Methods 5030/8020/California DHS LUFT Method

| Sample Name | Percent Recovery |
|--------------|------------------------|
| | a,a,a-Trifluorotoluene |
| MW-1 | 77. |
| MW-2 | 88. |
| MW-3 | 78 . |
| MW-4 | 88. |
| MW-5 | 81. |
| MW-6 | 79. |
| MS | 79. |
| DMS | 83. |
| Method Blank | 88. |

CAS Acceptance Limits:

62-112

Lowd Munhy



Client:

IWM

Project:

ARCO Facility No.

Sample Matrix: Water

A2035

Dates Collected: Date Received: 02/01/94 02/07/94

Date Extracted:

N/A

Date Analyzed: Service Request:

02/08/94 SJ94-0166

Initial Calibration Verification BTEX and TPH as Gasoline

EPA Methods 5030/8020/DHS LUFT Method Units: µg/L (ppb)

| <u>Analyte</u> | True <u>Value</u> | Result | Percent <u>Recovery</u> | CAS Acceptance <u>Criteria</u> |
|-----------------|----------------------|--------|----------------------------|--------------------------------------|
| Benzene | 25. | 27.8 | 111. | 85-115 |
| Toluene | 25. | 27.4 | 110. | 85-115 |
| Ethylbenzene | 25. | 27,4 | 110. | 85-115 |
| Total Xylenes | 75. | 83.4 | 111. | 85-115 |
| TPH as Gasoline | 25 0. | 253. | 101. | 90-110 |

Approved By:

[940166.XLW]8020ccs/2/16/94

Page No..



QA/QC Report

Client:

IWM

Project:

ARCO Facility No.

Sample Matrix: Water

A2035

Dates Collected:

02/01/94

Date Received:

02/07/94

Date Extracted: Date Analyzed:

N/A 02/08/94

Service Request:

SJ94-0166

Matrix Spike/Duplicate Matrix Spike Summary BTE

> EPA Methods 5030/8020 Units: µg/L (ppb)

> > Percent Recovery

| <u>Analyte</u> | Spike Level | Sample <u>Result</u> | Spike <u>MS</u> | Result <u>DMS</u> | <u>MS</u> | <u>DMS</u> | CAS Acceptance <u>Criteria</u> |
|----------------|-------------|-------------------------|--------------------|-------------------|-----------|------------|--------------------------------|
| Benzene | 25. | ND | 28,4 | 26.6 | 114. | 106. | 75-135 |
| Toluene | 25. | ND | 28.0 | 26.4 | 112. | 106. | 73-136 |
| Ethylbenzene | 25. | ND | 28.1 | 26.4 | 112. | 106. | 69-142 |

Den Muyly

Page No..



APPENDIX B CHAIN OF CUSTODY


| ARCO Products Company Division of AtlanticRichfieldCompany | roducts Company Division of AtlanticRichfieldCompany | | | | | Task O | rder No. | | | 7 | | 75 | V) | | | Chain of Custody | } |
|--|---|-------------|--------------------|-----------|---------------------------------|-----------------------|---------------|---|-------------------------------------|---------------------|-----------------|--------------|-------------------------|--|---------------|-----------------------------------|-------|
| ARCO Facility no. A | 2025 | | City (Facility) | A14 | y Ned | | | Project manager (Consultant) |) Jee | てい | Q' | るル | 13 | ń | | _ | <* |
| 4 3 | 200 | 7 | 3 | <u> </u> | Telephorne no. | no. | | Telephone no. 403 , | 307 | 1942 | 2 8955 | | Fax no. (Consultant) | 188 | 1942 1499 | | |
| Consultant name | 3 | | | | | Address (Consultar | ant) C. | C Am | 7. A. | CO | , , | | , C | 3 9 | 5 | 07077 | |
| | | Matrix | | Preset | Preservation | | : | 910 | | | 7 <i>39</i> | • | ,, | | | Method of shipment | _ |
| Sample 1.D. | Container no. | Water Water | Other | 92 | Acid #CC | etsb gailqms2 | Sampling time | BIEX/TPH 602/EPA 8020 BTEX/TPH EPA M602/8020/8 | 108 bəihboM H9T ∐ləsəiG □ ss:Ð | S.E14 ☐ 1.E14 | EPA 418.1/SM500 | EPA 624/8240 | EPA 625/8270 | TCLP Metals \(\text{VOA} \) CAM Metals \(\text{CPA 6} \) TLLC \(\text{CPA 5TLC} \) | TTC STC | (BUILE) | 4 |
| 78.FB 1-2 | 7 | > | | 7 | \ | 1-1-84 | 7.355 | > | > | | | | | | | Special defection Limit/reporting | |
| Mw 1 3-4 5 | 7 | > | | > | > | ,- | 1/27 | > | Ż | | | | | | | | |
| MW2 5-6 2 | 7 | 7 | | / | \ | | /557 | > | Ż | | | | | | | | |
| HW-3 7-9 | 7 | 7 | | 7 | / | | 1621 | ? | 7 | > | | | | | | Special QA/QC | |
| HW-4 10-11 3 | ქ | > | | 7 | 7 | | 1526 | 7 | 7 | | | | | | | | |
| MW-5/2-17 | ~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~ | > | | 7 | > |) | 15,10 | 7 | 7 | | | | | | | | |
| 12 S. 140 J. | ~ | / | | 7 | > | 9 | SHON | <i>'</i> | > | | | | | | | | |
| | | | | | | | | | | | | | | | | Hemarks / () / | |
| | | | | | | | | | | | | | | | | 5 5 | |
| | | | | | | - | | | | | | | | | | 18.FR | |
| | | | | | | | | | | | | | | | | The | 1 4 |
| | | | | | | | | | | | | | | | | 2/8/44 CLC 2/8/44 | 723 |
| | | | | | | | | | | | | | | | | 101 | |
| | | | | | | | | | | | | | | | | SJ94-016 | ٥ |
| | | | | | | | | | | | | | | | | Turnaround time | |
| | | | | | | | | | | | | | | | | Priority Rush 1 Business Day | |
| Condition of sample: | | ر (| | Ole | | | | Temperature received: | e received | # | e) | 1000 | | | | es a | |
| Relinquished by sampler | 1 | lde, | | | STY C | the | 9.03m | Received by | | X | 12/1 | | | | | 2 Business Days | |
| Relinguished by | 1 Star | | | | Date // | H | Time | Received by | | MA | 10 | 3 | · 5# | 2-7 | of: 11 115-10 | Expedited 5 Business Days | |
| Relinquished by | | | | | Date | | Time | Received by laboratory | y laborato | \ \ _≥ | | | Date | | Tine | Standard 10 Business Days | Ø |
| Distribution: White cook | - Laboratony: Canapy | | 1 | ACO Envir | ABCO Environmental Engineering: | naineerina: | Pink copy — | Consultant | | | | 1 | | | | | |

Distribution: White copy — Laboratory; Canary copy — ARCO Environmental Engineering; Pink copy — Consultant APPC-3292 (2-91)



APPENDIX B

LABORATORY ANALYTICAL RESULTS OF AIR SAMPLES WITH CHAIN-OF-CUSTODY RECORDS



680 Chesapeake Drive 1900 Bates Avenue, Suite L 819 Striker Avenue, Suite 8

Redwood City, CA 94063 Concord, CA 94520 Sacramento, CA 95834

(415) 364-9600 (510) 686-9600 (916) 921-9600 FAX (415) 364-9233 FAX (510) 686-9689 FAX (916) 921-0100

RESNA

3315 Almaden Expwy., Suite 34

San Jose, CA 95118 Attention: John Young Client Project ID:

Sample Matrix:

ARCO, 2035 Albany Air

EPA 5030/8015/8020 Analysis Method: First Sample #: 4A67801

Jan 12, 1994 Jan 14, 1994

Received: Reported: Amended:

Sampled:

Jan 26, 1994 May 18, 1994

TOTAL PURGEABLE PETROLEUM HYDROCARBONS with BTEX DISTINCTION

| Analyte | Reporting Limit μg/L | Sample I.D. 4A67801 AS-Influent | Sample I.D. 4A67802 AS-Effluent | |
|---------------------------|----------------------------|--|--|--|
| Purgeable Hydrocarbons | 50 | 2,500 | 52 | |
| Benzene | 0.50 | 37 | 0.93 | |
| Toluene | 0.50 | 140 | 2.4 | |
| Ethyl Benzene | 0.50 | 27 | 1.1 | |
| Total Xylenes | 0.50 | 110 | 7.4 | |
| Chromatogram Pa | ttern: | Gas + Non-Gas Mix < C8 | Gas | |

Quality Control Data

| Report Limit Multiplication Factor: | 25 | 1.0 |
|---|-----------|---------|
| Date Analyzed: | . 1/14/94 | 1/14/94 |
| Instrument Identification: | GCHP-17 | GCHP-2 |
| Surrogate Recovery, %: (QC Limits = 70-130%) * Coelution confirmed. | 166* | 101 |

Purgeable Hydrocarbons are quantitated against a fresh gasoline standard. Analytes reported as N.D. were not detected above the stated reporting limit.

SEQUOIA ANALYTICAL

Vickie Tague Clark Project Manager

4A67801.RES <1>



680 Chesapeake Drive 1900 Bates Avenue, Suite L 819 Striker Avenue, Suite 8

Redwood City, CA 94063 Concord, CA 94520 Sacramento, CA 95834

(415) 364-9600 (510) 686-9600 (916) 921-9600 FAX (415) 364-9233 FAX (510) 686-9689 FAX (916) 921-0100

RESNA

3315 Almaden Expwy., Suite 34

San Jose, CA 95118 Attention: John Young Client Project ID: /

ARCO, 2035 Albany

Matrix: Liquid

QC Sample Group: 4A67801

Reported:

Jan 26, 1994

QUALITY CONTROL DATA REPORT

| | | QUALITICO | NINOL DA | IA IILI OII | • |
|--------------------------|---------------------------------------|-----------|------------------|-------------|---|
| ANALYTE | Benzene | Toluene | Ethyf Benzene | Xylenes | |
| Method: | EPA 8020 | EPA 8020 | EPA 8020 | EPA 8020 | |
| Analyst: | М. Пірр | M. Nipp | M. Nipp | M. Nipp | |
| MS/MSD | | | | | |
| Batch#: | 4A38709 | 4A38709 | 4A38709 | 4A38709 | • |
| Date Prepared: | - | - | - | - | |
| Date Analyzed: | 1/14/94 | 1/14/94 | 1/14/94 | 1/14/94 | |
| Instrument I.D.#: | GCHP-17 | GCHP-17 | GCHP-17 | GCHP-17 | |
| Conc. Spiked: | 10 μg/L | 10 μg/L | 10 μg/L | 30 μg/L | |
| Matrix Spike | | | | | |
| % Recovery: | 110 | 110 | 110 | 110 | |
| Matrix Spike | | | | | |
| Duplicate % Recovery: | 110 | 110 | 110 | 107 | |
| Relative % | | | | | |
| Difference: | 0.0 | 0.0 | 0.0 | 2.8 | |
| | | | | | |
| LCS Batch#: | | - | - | • | |
| Date Prepared: | | - | - | - | |
| Date Analyzed: | - | - | - | - | |
| Instrument I.D.#: | - | - | • | - | |
| LCS % | | | | | |
| Recovery: | - | - | - | - | |
| % Recovery | · · · · · · · · · · · · · · · · · · · | | | | |
| Control Limits: | 71-133 | 72-128 | 72-130 | 71-120 | |

Quality Assurance Statement: All standard operating procedures and quality control requirements have been met.


Please Note:

The LCS is a control sample of known, interferent free matrix that is analyzed using the same reagents, preparation, and analytical methods employed for the samples. The matrix spike is an aliquot of sample fortified with known quantities of specific compounds and subjected to the entire analytical procedure. If the recovery of analytes from the matrix spike does not fall within specified control limits due to matrix interference, the LCS recovery is to be used to validate the batch.

Vickie Tague Clark Project Manager

SEQUOIA ANALYTICAL

4A67801.RES <2>



680 Chesapeake Drive 1900 Bates Avenue, Suite L 819 Striker Avenue, Suite 8

Redwood City, CA 94063 Concord, CA 94520 Sacramento, CA 95834 (415) 364-9600 (510) 686-9600 (916) 921-9600 FAX (415) 364-9233 FAX (510) 686-9689 FAX (916) 921-0100

RESNA

3315 Almaden Expwy., Suite 34

San Jose, CA 95118

Attention: John Young

Client Project ID: ARCO, 2035 Albany

Matrix: Liquid

QC Sample Group: 4A67802

Reported:

Jan 26, 1994

QUALITY CONTROL DATA REPORT

| ANALYTE | Benzene | Toluene | Ethyl Benzene | Xylenes | |
|--|-------------------|-------------------|-------------------|----------|---------------------------------------|
| Method: | EPA 8020 | EPA 8020 | EPA 8020 | EPA 8020 | |
| Analyst: | M. Nipp | M. Nipp | M. Nipp | M. Nipp | |
| MS/MSD | | | | | |
| Batch#: | 4A38709 | 4A38709 | 4A38709 | 4A38709 | · · · · · · · · · · · · · · · · · · · |
| Data Dramavadi | | | | | |
| Date Prepared: Date Analyzed: | 1 (14 (04 | - | 4 (4 4 /0 4 | - | |
| Instrument I.D.#: | 1/14/94 GCHP-2 | 1/14/94 GCHP-2 | 1/14/94 GCHP-2 | 1/14/94 | |
| Conc. Spiked: | 10 μg/L | | | GCHP-2 | |
| Coric. opikeu. | 10 µg/L | 10 μg/L | 10 μg/L | 30 μg/L | |
| Matrix Spike % Recovery: | 96 | 97 | 96 | 93 | |
| Matrix Spike Duplicate % Recovery: | 94 | 95 | 94 | 93 | |
| Relative % Difference: | 2.1 | 2.1 | 2.1 | 0.0 | |
| | | | | | |
| LCS Batch#: | - | • | | - | |
| Date Prepared: | - | - | - | - | |
| Date Analyzed: | - | _ | - | | |
| Instrument I.D.#: | - | - | - | • | - |
| LCS % | | | | | |
| Recovery: | - | • | - | - | |
| % Recovery Control Limits: | 71-133 | 72-128 | 72-130 | 71-120 | |

Quality Assurance Statement: All standard operating procedures and quality control requirements have been met.

Please Note:

The LCS is a control sample of known, interferent free matrix that is analyzed using the same reagents, preparation, and analytical methods employed for the samples. The matrix spike is an aliquot of sample fortified with known quantities of specific compounds and subjected to the entire analytical procedure. If the recovery of analytes from the matrix spike does not fall within specified control limits due to matrix interference, the LCS recovery is to be used to validate the batch.

Vickie Tague Clark Project Manager

SEQUOIA ANALYTICAL

4A67801.RES <3>



| ARCO Facility no. | ol Atla | tlanticRichfiel | IdCompany | City | > | | 1 day Other 140 | - 1- | Project manager (Consultant) | 1 manager Itani) | | _ } | = | | | | | | _ | | Laboratory name |
|------------------------|---------------|-----------------|-----------|-----------|----------|-------------------|-------------------------|---------------|---------------------------------|------------------------------|----------------------------|-------------------------------|--------------------------------|--------------|-------------------------|----------------------|----------------|--|----|---------|------------------------------|
| ARCO enginaled | | | 7 | 13 | W111(w. | Telepho (ARCO) | B no. | | Telephone no. (Consultant) | , e | | - | | = 11 | Fax no. (Consultant) | 크 .~ | - | , | - | | Contract number |
| Consultant name | 10 | 2 | () | | | | Address (Consultant) | | | 11 11 | | 1 1 | | - | - | - | |] - | - | | 07012 |
| | | | Matrix | | Pres | Preservation | j | | | | | | 3E | | | Semi ⊒ VOA □ | 6010/7000 | <u> </u> | | | Melhod of shipment |
| Sample I.D. | Container no. | Soil | Water | Olher | <u>c</u> | Acid | Sampling date | Sampling time | 8TEX 602/EPA 8020 | BTEX/TPH THE EPA M602/8020/8 | TPH Modified 80 Gas Diesel | Oil and Grease 413.1 413.2 | EPA 418.1/SM50 EPA 601/8010 | EPA 624/8240 | EPA 625/8270 | TCLP Metals - VOA | CAM Metals EPA | Lead Org./DHS i Lead EPA 7420/7421 | | <u></u> | 140167.3 |
| المند | , , | 7 | | `, | | | 11.71-1 | 11.71 | | | | | | | | | | 9 | | | Limitreporting |
| - | - | <i>i</i> | | ţ | | | 11 | 14: 14 | | | | | | <u></u> | | | | - 07 | | | |
| | | | | | | | | | | | | | | | | | | | | | |
| į | | | | | | | | | | | | | | | | | | | | | Special QA/QC |
| | | | | | | | | | | | | | - | | | | | | | | |
| | | | | | | | | | | | - | | | + | | | | | | | |
| | | | ! | | | | | | | | | | <u> </u> | | | | | | | | Remarks |
| | | | | | - | | | | | - | - | 1 | | | | | | | | | |
| | | | | | | | | | | | | | | - | | - | † | | | | |
| | | | | | | | | | | | _ | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | - | | | - | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | CHOILS |
| | | | | | | | | | | <u> </u> | <u> </u> | | | <u> </u> | <u> </u> | | | | | | Turnaround lime |
| | | | | | | | | | | | | | | | | | | | | | Priority Rush 1 Business Day |
| Condition of sample: | e. | | | | | | | | Тетре | Temperature received: | ceived | _ | 7 | | | | | | | | Rush |
| Relinquished by sample | ampler | 1 | | <u>}_</u> | | Date | | Time | Received by | مرکز کم کرد | , | L | 13. | 20-2 | 1 | | | | | | 2 Business Days |
| Relipquished by | 12/20 | Kd | r | | | Db10 | | السو مست | Heceived by | ed by | - | , | | | | | | | | | 5 Business Days |
| Relinquished by | 1 | | | | | Date | | Time | Receiv | Received by laboratory | borator | * | | | Date O t | ale O1 -14 -}4 | 73 | Time 325 | لغ | | Slandard 10 Business Days |