

Date

March 31, 1998

Project

20805-123,004

#3858

To:

Mr. Barney Chan Alameda County Health Care Services Agency Department of Environmental Health 1131 Harborbay Parkway, Suite 250 Alameda, California 94502-6577

We are enclosing:

Copies		Description			
1		Fourth quarter	1997 groundwa	ater monito	ring results and
		remediation sy	stem performan	ice evaluati	on report,
		ARCO service	station 2035, A	lbany, Cali	fornia
For your:	X	Use	Sent by:	X	Regular Mail
		Approval			Standard Air
		Review			Courier
		Information			Other:

Comments:

The enclosed groundwater monitoring report is being sent to you per the request of ARCO Products Company. Plaese call if you have questions or comments.

Gary P. Messerotes Project Manager

cc: Paul Supple, ARCO Products Company File



Date: March 31, 1998

Re: ARCO Station #


2035 • 1001 San Pablo Avenue • Albany, CA Fourth Quarter 1997 Groundwater Monitoring Results and Remediation System Performance Evaluation Report

"I declare, that to the best of my knowledge at the present time, that the information and/or recommendations contained in the attached proposal or report are true and correct."

Submitted by:

Paul Supple

Environmental Engineer





March 13, 1998 Project 20805-123.004

Mr. Paul Supple **ARCO Products Company** P.O. Box 6549 Moraga, California 94570

Fourth quarter 1997 groundwater monitoring results and remediation system performance evaluation report, ARCO service station 2035, Albany, California

Dear Mr. Supple:

This letter presents the results of the fourth quarter 1997 groundwater monitoring program at ARCO Products Company (ARCO) service station 2035, 1001 San Pablo Avenue, Albany, California (Figure 1). Operation and performance data for the site's soilvapor extraction (SVE) and groundwater extraction remediation systems are also presented. The quarterly monitoring program complies with Alameda County Health Care Services Agency (ACHCSA) requirements regarding underground tank investigations.

LIMITATIONS

No monitoring event is thorough enough to describe all geologic and hydrogeologic conditions of interest at a given site. If conditions have not been identified during the monitoring event, results should not be construed as a guarantee of the absence of such conditions at the site, but rather as the product of the scope and limitations of work performed during the monitoring event.

Please call if you have questions.

Sincerely,

EMCON

Valli Voruganti, P.E.

Project Engineer

. Messerotes, R.G. 5650

Project Manager

EMCON

5650

ARCO QUARTERLY REPORT

Station No.: _	2035	Address:	1001 San Pablo Avenue, San Pablo, California
EMCON Proje	ect No.:		20805-123.004
ARCO Enviro	nmental Enginee	r/Phone No.:	Paul Supple /(510) 299-8891
EMCON Proje	ect Manager/Pho	ne No.:	Gary P. Messerotes /(408) 453-7300
Primary Agend	cy/Regulatory ID	No.:	ACHCSA /Barney Chan
Reporting Peri	iod:		October 1, 1997 to January 1, 1998

WORK PERFORMED THIS QUARTER (Fourth- 1997):

- 1. Prepared and submitted quarterly report for third quarter 1997.
- 2. Conducted quarterly groundwater monitoring and sampling for fourth quarter 1997.
- 3. SVE system was pulsed on in November 1997 for approximately 2 weeks. System was shut down due to low hydrocarbon in extracted vapor.
- 4. Continued air bubbling at RW-1.

WORK PROPOSED FOR NEXT QUARTER (First-1998):

- 1. Prepare and submit quarterly report for fourth quarter 1997.
- 2. Perform quarterly groundwater monitoring and sampling for first quarter 1998.
- 3. Continue air bubbling at RW-1.

QUARTERLY MONITORING:

Current Phase of Project:	Quarterly Groundwater Monitoring and Operation and Maintenance of Remediation Systems
	The SVE system was shut down on August 12, 1996, because of low
	TVHg and benzene concentrations in extracted soil vapor. System pulsed on occasionally to see if hydrocarbon concentrations in extracted vapor warrant continued operation.
	The groundwater treatment system was shut down on August 8, 1996, because of low TPHG concentrations in extracted groundwater.
Frequency of Sampling:	Quarterly (groundwater), Monthly (SVE)
Frequency of Monitoring:	Quarterly (groundwater), Monthly (SVE)
Is Floating Product (FP) Present On-site:	☐ Yes ☒ No
Cumulative FP Recovered to Date :	27.9 gallons, Wells AS-1, AS-2, RW-1, VW-1, VW-2, and VW-7
FP Recovered This Quarter:	None (FP was last recovered in 1996)
Bulk Soil Removed to Date :	605 cubic yards of TPH impacted soil
Bulk Soil Removed This Quarter :	None
Water Wells or Surface Waters,	
within 2000 ft., impacted by site:	None
Current Remediation Techniques:	Air-Bubbling in RW-1
Average Depth to Groundwater:	11.23 feet
Groundwater Gradient (Average):	0.038 ft/ft toward southwest
SVE QUARTERLY OPERATION	AND PERFORMANCE.

Equipment Inventory: Therm Tech Model VAC-10 Thermal/Catalytic Oxidizer **EMCON** The SVE system was shut down on August 12, 1996, because of low TVHg and benzene concentrations in extracted soil vapor.

The groundwater treatment system was shut down on August 8, 1996, because of low TPHG concentrations in extracted groundwater.

Operating Mode:

BAAQMD Permit #:

10931

TPH Conc. End of Period (lab):

NA (Not Available)

Benzene Conc. End of Period (lab):

SVE Flowrate End of Period:

Total HC Recovered This Period:

Total HC Recovered to Date:

Utility Usage

NA

9.0 pounds

3016.5 pounds

Utility Usage

Gas (Therms):

Operating Hours This Period (SVE):

Operating Hours to Date (SVE):

Percent Operational (SVE):

15.3%

Operating Hours This Period (SVE):

15.3%

1775.1 KWH

 Operating Hours This Period (GWE):
 0.0 hours

 Percent Operational (GWE):
 0.0%

 Unit Maintenance:
 Routine monthly maintenance

Number of Auto Shut Downs: 0

Destruction Efficiency Permit

Requirement: 90% if POC concentrations are less than 200 ppmv

Percent TPH Conversion: 94.7%

Average Stack Temperature: 732°F

Average SVE Source Flow: 118.7 scfm

Average SVE Process Flow: 221.4 scfm

Average Source Vacuum: 21.5 inches of water

DISCUSSION:

Electric (KWH):

The SVE system has been shut down since August 12, 1996, because of relatively low gasoline concentrations in the influent vapor stream. The SVE system was restarted for two weeks during the fourth quarter, and was shut down again because of low hydrocarbons concentrations in extracted vapor. Currently bubbling air at low flow rates of less than 2 cfm in well RW-1 to introduce dissolved oxygen into groundwater to promote biodegradation of hydrocarbons in the vicinity of RW-1.

ATTACHED:

- Table 1 Groundwater Monitoring Data, Fourth Quarter 1997
- Table 2 Historical Groundwater Elevation and Analytical Data, Petroleum Hydrocarbons and Their Constituents
- Table 3 Historical Groundwater Elevation Data, Shell Station
- Table 4 Approximate Cumulative Floating Product Recovered, Wells AS-1, AS-2, RW-1, VW-1, VW-2, and VW-7
- Table 5 Soil-Vapor Extraction System Operation and Performance Data
- Table 6 Soil-Vapor Extraction Well Data
- Table 7 Influent and Effluent Groundwater Analyses Summary Report
- Table 8 Estimated Total Dissolved TPHG and Benzene Removed, Summary Report
- Figure 1 Site Location

EMCON

- Figure 2 Site Plan
- Figure 3 Groundwater Data, Fourth Quarter 1997
- Figure 4 Soil-Vapor Extraction and Treatment System, Historical System Influent TVHG and Benzene Concentrations
- Figure 5 Soil-Vapor Extraction and Treatment System, Historical Hydrocarbon Removal Rates
- Figure 6 Groundwater Treatment System, Historical System Influent TPHG and Benzene Concentrations
- Figure 7 Groundwater Treatment System, Historical Hydrocarbon Removal Rates
- Appendix A Analytical Results and Chain of Custody Documentation, Fourth Quarter 1997
 Groundwater Monitoring Event
- Appendix B SVE System Monitoring Data Log Sheets
- Appendix C Analytical Results and Chain-of-Custody Documentation for Soil Vapor Extraction System, Fourth Quarter 1997

cc: Barney Chan, ACHCSA

Table 1 Groundwater Monitoring Data Fourth Quarter 1997

ARCO Service Station 2035 1001 San Pablo Avenue, Albany, California

Date: 03-10-98

Well Designation	Water Level Field Date	-13 Top of Casing CS Elevation	and Depth to Water	Groundwater S Elevation	Floating Product	Groundwater Flow Direction	Hydraulic S Gradient	Water Sample Field Date	TPHG LUFT Method	는 Benzene 라 EPA 8020	Toluene	Ethylbenzene	Total Xylenes	표 MTBE 연 EPA 8020	ਜ MTBE ਲੋ EPA 8240	Oil and Grease SM 5520B&F	Oil and Grease SM 5520C	Oil and Grease SM 5520F	म TRPH ्रिक EPA 418.1	TPHD
MW-1	11-03-97	41.41	10.68	30.73	ND	sw	0.038	11-03-97	83	8	< 0.5	<0.5	< 0.5	13						
MW-2	11-03-97	40.38	11,25	29.13	ND	SW	0.038	11-03-97	<50	< 0.5	< 0.5	<0.5	< 0.5	18						
MW-3	11-03-97	41.44	11.44	30.00	ND	SW	0.038	11-03-97	<200^	<2^	<2^	<2^	<2^	130						
MW-4	11-03-97	40.33	10.79	29.54	ND	sw	0.038	11-03-97	<50	< 0.5	<0.5	< 0.5	< 0.5	<3		• -				
MW-5	11-03-97	41.84	11.23	30.61	ND	SW	0.038	11-03-97	Not sampled	l: well samı	led annual	ly, during ti	he first qua	rier						
MW-6	11-03-97	40.13	13.42	26.71	ND	SW	0.038	11-03-97	<50	< 0.5	< 0.5	< 0.5	< 0.5	19						
RW-1	11-03-97	40.33	9,10	31.23	ND	SW	0.038	11-03-97	<200^	14	19	3	19	140						

ft-MSL: elevation in feet, relative to mean sea level

MWN: ground-water flow direction and gradient apply to the entire monitoring well network

ft/ft: foot per foot

TPHG: total petroleum hydrocarbons as gasoline, California DHS LUFT Method

μg/L: micrograms per liter

EPA: United States Environmental Protection Agency

MTBE: Methyl tert-butyl ether

SM; standard method

TRPH: total recoverable petroleum hydrocarbons

TPHD: total petroleum hydrocarbons as diesel, California DHS LUFT Method

ND: none detected

W: west

^: method reporting limit was raised due to: (1) high analyte concentration requiring sample dilution, or (2) matrix interference

- -: not analyzed or not applicable

Table 2
Historical Groundwater Elevation and Analytical Data
Petroleum Hydrocarbons and Their Constituents
1995 - Present*

Well Designation	Water Level Field Date	Top of Casing SE Elevation	eg Depth to Water	Groundwater S Groundwater S Elevation	Floating Product	Groundwater Groundwater Z Flow Direction	Hydraulic 과 Gradient	Water Sample Field Date	TPHG	Benzene EPA 8020	Toluene	Ethylbenzene	Total Xylenes	56 MTBE 건 EPA 8020	mTBE √ EPA 8240	는 Oil and Grease 한 SM 5520B&F	Oil and Grease SM 5520C	Oil and Grease SM 5520F	म TRPH EPA 418.1	দ TPHD ন LUFT Method
MW-I	03-24-95	41.41	6.21	35.20	ND	NW	0.037	03-24-95	8800	3600	<50	62	99							
MW-1	05-24-95	41.41	9.37	32.04	ND	WNW	0.013	05-24-95	4800	2000	<20	52	<20							
MW-1	08-22-95	41.41	10.30	31.11	ND	SW	0.012	08-22-95	780	310	<2.5	12	<2.5	14						
MW-1	11-09-95	41.41	12.25	29.16	ND	WSW	0.01	11-09-95	58	14	<0.5	< 0.5	<0.5							
MW-I	02-27-96	41.41	9.08	32.33	ND	SW	0.009	02-27-96	2700	930	12	18	32	51		- -				
MW-1	04-22-96	41.41	9.11	32.30	ND	WSW	0.014	04-22-96	2700	1000	<10	22	<10	<60						
MW-1	08-15-96	41.41	10.37	31.04	ND	SW	0.011	08-15-96	300	52	<0.5	0.9	< 0.5	22						
MW-1	12-10-96	41.41	8.79	32.62	ND	WSW	0.023	12-10-96	270	63	0.7	< 0.5	l	25						
MW-1	03-27-97	41.41	9.80	31.61	ND	WSW	0.026	03-27-97	1500	610	<5^	15	7	56						
MW-1	05-22-97	41,41	9.65	31.76	ND	WSW	0.024	05-22-97	110	5.5	<0.5	< 0.5	0.7	10				~ -		
MW-1	09-04-97	41.41	10.22	31.19	ND	W	0.019	09-04-97	180	40	< 0.5	1.2	0.5	26						
MW-1	11-03-97	41.41	10.68	30.73	ND	SW	0.038	11-03-97	83	8	<0.5	<0.5	<0.5	13					= =	
MW-2	03-24-95	40.38	6.96	33.42	ND	NW	0.037	03-24-95	<50	<0.5	<0.5	<0.5	<0.5			•-				••
MW-2	05-24-95	40.38	10.02	30.36	ND	WNW	0.013	05-24-95	Not sampled	: well samp	led semi-a	nnually, du	ring the firs	t and third	quarters					
MW-2	08-22-95	40.38	10.87	29.51	ND	SW	0.012	08-22-95	<50	< 0.5	< 0.5	< 0.5	<0.5	<3						
MW-2	11-09-95	40.38	13.12	27.26	ND	wsw	0.01	11-09-95	Not sampled	: well samp	oled semi-a	nnually, du	ring the firs	st and third	quarters					
MW-2	02-27-96	40.38	10.25	30.13	ND	SW	0.009	02-27-96	<50	< 0.5	<0.5	< 0.5	< 0.5	<3						
MW-2	04-22-96	40.38	9.98	30.40	ND	WSW	0.014	04-22-96	Not sampled	: well samp	oled semi-a	onually, du	ring the firs	t and third	quarters					
MW-2	08-15-96	40.38	11.10	29.28	ND	SW	0.011	08-15-96	<50	< 0.5	<0.5	< 0.5	< 0.5	4						
MW-2	12-10-96	40.38	10.00	30.38	ND	wsw	0.023	12-10-96	Not sampled	: well samp	oled semi-a	nnualty, du	ring the firs	st and third	quarters					
MW-2	03-27-97	40.38	10.38	30.00	ND	WSW	0.026	03-27-97	<50	< 0.5	< 0.5	< 0.5	<0.5	12						
MW-2	05-22-97	40.38	10.65	29.73	ND	WSW	0.024	05-22-97	Not sampled	: well samp	oled semi-a	nnually, du	ring the firs	st and third	quarters					
MW-2	09-04-97	40.38	10.87	29.51	ND	W	0.019	09-04-97	<50	< 0.5	<0.5	< 0.5	<0.5	19						
MW-2	11-03-97	40.38	11.25	29.13	ND	SW	0.038	11-03-97	<50	< 0.5	<0.5	<0.5	<0.5	18						

Table 2
Historical Groundwater Elevation and Analytical Data
Petroleum Hydrocarbons and Their Constituents
1995 - Present*

Well Designation	Water Level Field Date	Top of Casing Elevation	ed Depth to Water	Groundwater Groundwater Elevation	Floating Product	Groundwater A Flow Direction	Hydraulic If Gradient	Water Sample Field Date	TPHG LUFT Method	ъ Benzene 75 EPA 8020	Toluene Toluene Toluene Toluene	Ethylbenzene	Total Xylenes EPA 8020	MTBE	한 MTBE 한 EPA 8240	Oil and Grease SM 5520B&F	Oil and Grease SM 5520C	Oil and Grease SM 5520F	ਜੂ TRPH ਨੂੰ EPA 418.1	TPHD Sp LUFT Method
MW-3	03-24-95	41,44	7,29	34.15	ND	NW	0.037	03-24-95	51	0.8	<0.5	2.4	<0.5						<500	
MW-3	05-24-95	41.44	9.53	31.91	ND	WNW	0.013	05-24-95	<50	<0.5	<0.5	< 0.5	<0.5						<500	
MW-3	08-22-95	41.44	11.19	30.25	ND	SW	0.012	08-22-95	<50	< 0.5	< 0.5	< 0.5	<0.5	79					<500	
MW-3	11-09-95	41.44	12.77	28.67	ND	wsw	0.01	11-09-95	<50	<0.5	<0.5	< 0.5	< 0.5						600	
MW-3	02-27-96	41.44	9.41	32,03	ND	SW	0.009	02-27-96	120	3.6	<0.5	2.2	3.7	90		÷ ÷			< 0.5	
MW-3	04-22-96	41.44	9.63	31.81	ND	WSW	0.014	04-22-96	<50	< 0.5	<0.5	< 0.5	<0.5	90						
MW-3	08-15-96	41.44	11.12	30.32	ND	SW	0.011	08-15-96	<50	< 0.5	< 0.5	< 0.5	<0.5	54						
MW-3	12-10-96	41.44	10.34	31.10	ND	WSW	0.023	12-10-96	71	< 0.5	< 0.5	< 0.5	< 0.5	130						
MW-3	03-27-97	41.44	10.28	31.16	ND	WSW	0.026	03-27-97	<100^	<1^	<i^< td=""><td><1^</td><td><1^</td><td>170</td><td></td><td></td><td></td><td></td><td></td><td></td></i^<>	<1^	<1^	170						
MW-3	05-22-97	41.44	10.40	31.04	ND	WSW	0.024	05-22-97	<100^	<1^	<1^	<1^	<1^	95						
MW-3	09-04-97	41.44	10.75	30.69	ND	W	0.019	09-04-97	<50	< 0.5	< 0.5	< 0.5	<0.5	37						
MW-3	11-03-97	41.44	11.44	30.00	ND	SW	0.038	11-03-97	<200^	<2^	<2^	<2^	<2^	130				= <u>=</u>		
MW-4	03-24-95	40.33	5.92	34.41	ND	NW	0.037	03-24-95	<50	<0.5	<0.5	<0.5	<0.5							
MW-4	05-24-95	40.33	9.23	31.10	ND	WNW	0.013	05-24-95	<50	< 0.5	<0.5	<0.5	< 0.5							
MW-4	08-22-95	40.33	10.61	29.72	ND	SW	0.012	08-22-95	<50	< 0.5	< 0.5	<0.5	< 0.5	99						
MW-4	11-09-95	40,33	11.97	28.36	ND	wsw	0.01	11-09-95	<50	< 0.5	< 0.5	<0.5	< 0.5		89					
MW-4	02-27-96	40.33	8.84	31.49	ND	SW	0.009	02-27-96	<50	0.8	< 0.5	<0.5	<0.5	<3						
MW-4	04-22-96	40.33	9.15	31.18	ND	WSW	0.014	04-22-96	Not sampled	: well samp	iled annuall	ly, during th	he first quar	rter						
MW-4	08-15-96	40.33	10.35	29.98	ND	SW	0.011	08-15-96	Not sampled	: well samp	iled annuall	ly, during th	he first quar	rter						
MW-4	12-10-96	40.33	8.70	31.63	ND	WSW	0.023	12-10-96	Not sampled	: well samp	oled annuall	y, during tl	he first quai	rter						
MW-4	03-27-97	40.33	9.75	30.58	ND	WSW	0.026	03-27-97	<5000^	<50^	<50^	<50^	<50^	4200						
MW-4	05-22-97	40.33	9.91	30.42	ND	WSW	0.024	05-22-97	Not sampled											
MW-4	09-04-97	40.33	10.25	30.08	ND	W	0.019	09-04-97	Not sampled	: well samp	led annuall	y, during tl	ne first quai	rter						
MW-4	11-03-97	40.33	10.79	29.54	ND	SW	0.038	11-03-97	< 50	< 0.5	<0.5	<0.5	<0.5	<3						

Table 2
Historical Groundwater Elevation and Analytical Data
Petroleum Hydrocarbons and Their Constituents
1995 - Present*

Well Designation	Water Level Field Date	Top of Casing Selevation	a Depth to Water	TSM Groundwater	Floating Product	Groundwater Flow Direction	Hydraulic tl/d Gradient	Water Sample Field Date	r TPHG الم	Benzene	Toluene	Ethylbenzene	Total Xylenes	شخ MTBE ازام EPA 8020	MTBE 7/8 EPA 8240	Oil and Grease	Oil and Grease	Oil and Grease SM 5520F	t TRPH ≥ EPA418.1	TPHD
 MW-5	03-24-95	41.84	6.23	35.61	ND	NW	0.037	03-24-95	<50	<0.5	<0.5	<0.5	<0.5						,	
MW-5	05-24-95	41.84	9.61	32.23	ND	WNW	0.037	05-24-95	Not sampled											
MW-5	08-22-95	41.84	11.12	30.72	ND	SW	0.013	08-22-95	Not sampled				-							
MW-5	11-09-95	41.84	12.52	29.32	ND	wsw	0.012	11-09-95	Not sampled	-		-								
MW-5	02-27-96	41.84	9.52	32.32	ND	sw	0.009	02-27-96	<50	<0.5	< 0.5	<0.5	<0.5	<3						
MW-5	04-22-96	41.84	9.44	32.40	ND	WSW	0.014	04-22-96	Not sampled											
MW-5	08-15-96	41.84	10.83	31.01	ND	SW	0.011	08-15-96	Not sampled	-		-	-							
MW-5	12-10-96	41.84	9.20	32.64	ND	wsw	0.023	12-10-96	Not sampled											
MW-5	03-27-97	41.84	10.10	31.74	ND	wsw	0.026	03-27-97	<50	<0.5	< 0.5	<0.5	<0.5	<3						
MW-5	05-22-97	41.84	10.28	31.56	ND	wsw	0.024	05-22-97	Not sampled	: well samp	led annuall	ly, during th	he first quai	rter						
MW-5	09-04-97	41.84	10.73	31.11	ND	w	0.019	09-04-97	Not sampled	•		-								
MW-5	11-03-97	41.84	11.23	30.61	ND	SW	0.038	11-03-97	Not sampled	: well samp	oled annuall	ly, during th	he first qua	rter						
MW-6	03-24-95	40.13	9.03	31.10	ND	NW	0.037	03-24-95	<50	<0.5	<0.5	<0.5	<0.5							
MW-6	05-24-95	40.13	12.45	27.68	ND	WNW	0.013	05-24-95	Not sampled					rter						
MW-6	08-22-95	40.13	13.32	26.81	ND	SW	0.012	08-22-95	Not sampled			-								
MW-6	11-09-95	40.13	14.13	26.00	ND	WSW	0.01	11-09-95	Not sampled											
MW-6	02-27-96	40.13	11.86	28.27	ND	SW	0.009	02-27-96	<50	<0.5	<0.5	<0.5	<0.5	<3						
MW-6	04-22-96	40.13	12.35	27.78	ND	WSW	0.014	04-22-96	Not sampled	: well samp	ied annuali	iv. during t								
MW-6	08-15-96	40.13	13.18	26.95	ND	SW	0.011	08-15-96	Not sampled			_								
MW-6	12-10-96	40.13	11.94	28.19	ND	WSW	0.023	12-10-96	Not sampled				,							
MW-6	03-27-97	40.13	13.10	27.03	ND	wsw	0.026	03-27-97	<50	<0.5	<0.5	<0.5	<0.5	<3						
MW-6	05-22-97	40.13	13.00	27.13	ND	wsw	0.024	05-22-97	Not sampled	: well samp	led annuall	ly, during t	he first quar							
MW-6	09-04-97	40.13	13.30	26.83	ND	W	0.019	09-04-97	Not sampled			_								
MW-6	11-03-97	40.13	13.42	26.71	ND	sw	0.038	11-03-97	<50	< 0.5	<0.5	<0.5	<0.5	19						

Table 2
Historical Groundwater Elevation and Analytical Data
Petroleum Hydrocarbons and Their Constituents
1995 - Present*

Well Designation	Water Level Field Date	Top of Casing	pad Depth to Water	tp. Groundwater S Elevation	Floating Product	Groundwater R Flow Direction	Hydraulic F Gradient	Water Sample Field Date	표 TPHG 전 LUFT Method	Benzene	Toluene	Ethylbenzene	Total Xylenes EPA 8020	MTBE	т МТВЕ Р EPA 8240	Oil and Grease SM 5520B&F	n Oil and Grease N 5520C	n Oil and Grease	TRPH E EPA 418.1	TPHD LUFT Method
									F 67	r-e-	re-		P6, 2	Р Б/13	дыс	ив, с	pg/L	μg/L	μg/L	μg/L
RW-I	03-24-95	40.33	9.32	31.02**	0.01	NW	0.037	03-24-95	11000	560	660	150	1700							
RW-1	05-24-95	40.33	9.75	30.60**	0.03	WNW	0.013	05-24-95	Not sampled	: well conta	ained floati	ng product								
RW-1	08-22-95	40.33	10.86	29.48**	0.02	SW	0.012	08-22-95	Not sampled											
RW-I	11-09-95	40.33	20.61	19.72	ND	wsw	0.01	11-09-95	1600	79	46	13	240							
RW-I	02-27-96	40.33	16.56	23.77	ND	SW	0.009	02-27-96	210	44	7.5	2.5	24	29						
RW-I	04-22-96	40.33	9.65	30.68	ND	wsw	0.014	04-22-96	36000	7400	3700	580	3400	<300						
RW-1	08-15- 9 6	40.33	10.60	29.73	ND	SW	0.011	08-15-96	1800	31	38	15	150	<30^						
RW-1	12-10-96	40.33	8.72	31.61	ND	wsw	0.023	12-10-96	25000	1900	1000	330	3200	<100^						
RW-1	03-27-97	40.33	10.33	30.00	ND	wsw	0.026	03-27-97	7200	1900	59	95	240	480						
RW-1	05-22-97	40.33	10.10	30.23	ND	wsw	0.024	05-22-97	3000	630	84	45	340	<60^						
RW-1	09-04-97	40.33	10.42	29.91	ND	w	0.019	09-04-97	7100	120	55	14	160	<60^						
RW-1	11-03-97	40.33	9.10	31.23	ND	sw	0.038	11-03-97	<200^	14	19	3	19	140						

Table 2 Historical Groundwater Elevation and Analytical Data Petroleum Hydrocarbons and Their Constituents 1995 - Present*

ARCO Service Station 2035 1001 San Pablo Avenue, Albany, California

Date: 03-09-98

Well Designation	Water Level Field Date	Top of Casing Elevation	Depth to Water	Groundwater Elevation	Floating Product Thickness	Groundwater Flow Direction	Hydraulic Gradient	Water Sample Field Date	TPHG LUFT Method	Benzene EPA 8020	Toluene EPA 8020	Ethylbenzene EPA 8020	Total Xylenes EPA 8020	MTBE EPA 8020	MTBE EPA 8240	Oil and Grease SM 5520B&F	Oil and Grease SM 5520C	Oil and Grease SM 5520F	TRPH EPA 418.1	TPHD LUFT Method
		ft-MSL	feet	ft-MSL	feet	MWN	ft/ft		μg/L	μg/L	μg/L	μg/L	μg/L	μg/L	μg/L	μg/L	μg/L	μg/L	μg/L	μg/L

ft-MSL: elevation in feet, relative to mean sea level

MWN: ground-water flow direction and gradient apply to the entire monitoring well network

ft/ft: foot per foot

TPHG: total petroleum hydrocarbons as gasoline, California DHS LUFT Method

µg/L: micrograms per liter

EPA: United States Environmental Protection Agency

MTBE: Methyl tert-butyl ether

SM: standard method

TRPH: total recoverable petroleum hydrocarbons

TPHD: total petroleum hydrocarbons as diesel, California DHS LUFT Method

ND: none detected

NW: northwest

WNW: west-northwest

SW: southwest

WSW: west-southwest

- ^: method reporting limit was raised due to: (1) high analyte concentration requiring sample dilution, or (2) matrix interference
- -: not analyzed or not applicable
- *: For previous historical groundwater elevation and analytical data please refer to Fourth Quarter 1995 Groundwater Monitoring Program Results and Remediation System Performance Evaluation Report, ARCO Service Station 2035, Albany, California, (EMCON, March 25, 1996).
- **: [corrected elevation (Z')] = Z + (h * 0.73); where Z = measured elevation, h = floating product thickness, 0.73 = density ratio of oil to water

Table 3 Historical Groundwater Elevation Data

Shell Station, 999 San Pablo Avenue

Well Designation	Water Level Field Date	TOC Elevation	Depth to Water	Groundwater Elevation	Floating Product Thickness	
		ft-MSL	feet	ft-MSL	feet	
nell Station						
S-1	12-10-96	42.73	7.56	35.17	ND	
S-1	02-20-97	42.73	7.95	34.78	ND	
S-1	05-22-97	42.73	8.11	34.62	ND	
S-2	12-10-96	40.73	8.57	32.16	ND	
S-2	02-20-97	40.73	8.15	32.58	ND	
S-2	05-22-97	40.73	8.79	31.94	ND	
S-3	12-10-96	41.46	7.96	33.50	ND	
S-3	02-20-97	41.46	7.44	34.02	ND	
S-3	05-22-97	41.46	7.13	34.33	ND	
S-4	12-10-96	41.10	7.04	34.06	ND	
S-4	02-20-97	41.10	7.07	34.03	ND	
S-4	05-22-97	41.10	6.63	34,47	ND	
S-5	12-10-96	39.99	9.10	30.89	ND .	
S-5	02-20-97	39.99	8.93	31.06	ND	
S-5	05-22-97	39.99	10.07	29.93**	0.02	
S-6	12-10-96	40.12	6.68	33.44	ND	
S-6	02-20-97	40.12	5.70	34.42	ND	
S-6	05-22-97	40.12	5.49	34.63	ND	
S-7	12-10-96	40.10	9.04	31.06	ND	
S-7	02-20-97	40.10	9.60	30.50	ND	
S -7	05-22-97	40.10	10.63	29.47	ND	

TOC: top of casing

ft-MSL: elevation in feet, relative to mean sea level

ND: none detected

^{**: [}corrected elevation (Z')] = Z + (h * 0.73); where Z = measured elevation, h = floating product thickness, 0.73 = density ratio of oil to water

Table 4
Approximate Cumulative Floating Product Recovered

Date: 01-19-98

Well Designations	Date	Floating Product Recovered gallons	
RW-1	1992	22.3	
RW-I	1993	1.0	
RW-I	1994	0.0	
AS-1, AS-2, RW-1, VW-1, VW-2, and VW-7	1995	4.6	
VW-7	1996	0.003	
VW-7	1997	0.0	
		1992 to 1997 Total: 27.9	

Table 5 Soil-Vapor Extraction System Operation and Performance Data

Location: 1001 San Pablo Avenue

Albany, California

Vapor Treatment Unit: Therm Tech Model

VAC-10 thermal/catalytic

oxidizer

Consultant: EMCON

1921 Ringwood Avenue San Jose, California

Start-Up Date: 12-07-93 Operation and Performance Data From: 12-07-93
To: 01-01-98

San Jose, California		S	ystem shut do	To: 0 wn on 8-12-96.	1-01-98
Date Begin:	12-07-93	12-08-93	12-09-93	12-10-93	12-15-93
Date End:	12-08-93	12-09-93	12-10-93	12-15-93	12-16-93
Mode of Oxidation:	Therm-Ox (17)	Therm-Ox	Therm-Ox	Therm-Ox	Therm-Ox
Days of Operation:	l	0	1	5	1
Days of Downtime:	0	J	0	0	0
Average Vapor Concentrations (1)					
Well Field Influent: ppmv (2) as gasoline (3)	2800	NA (18)	NA	NA	NA
mg/m3 (4) as gasoline	10000	NA	NA	NA	NA
ppmv as benzene (5)	170	NA	NA	NA	NA
mg/m3 as benzene	540	NA	NA	NA	NA
System Influent: ppmv as gasoline	390	NA	390	410	500
mg/m3 as gasoline	1400	NA.	1400	1500	0081
ppmv as benzene	12	NA	19	31	24
mg/m3 as benzene	38	NA	60	100	79
System Effluent: ppmv as gasoline	21	NA	36	6	NA
mg/m3 as gasoline	76	NA	130	21	NA
ppmv as benzene	0.7	NA	1	< 0.01	NA
mg/m3 as benzene	2.3	NA	3.1	< 0.05	NA
Average Well Field Flow Rate (6), scfm (7):	10.0	0.0	10.0	5.0	45.0
Average System Influent Flow Rate (6), scfm:	100.0	0.0	100.0	87.0	100.0
Average Destruction Efficiency (8), percent (9):	94.6	NA	90.7	98.6	NA
Average Emission Rates (10), pounds per day (11)					
Gasoline:	0.68	0.00	1.17	0.16	NA
Benzene:	0.02	0.00	0.03	< 0.00	NA
Operating Hours This Period:	21.00	0.00	23.00	121.00	18.00
Operating Hours To Date:	21.0	21.0	44.0	165.0	183.0
SVE Pounds/ Hour Removal Rate, as gasoline (12):	0.52	0.00	0.52	0.49	0.67
SVE Pounds Removed This Period, as gasoline (13):	11.00	0.00	12.05	59.10	12.13
GWE Pounds Removed This Period, as gasoline (14):	0.00	0.00	<u>0.00</u>	<u>0.00</u>	0.00
Total Pounds Removed This Period, as gasoline (15):	11.00	0.00	12.05	59.10	12,13
Total Pounds Removed To Date, as gasoline:	11.0	11.0	23.1	82.2	94.3
Total Gallons Removed This Period, as gasoline (16):	<u>1.77</u>	0.00	1.94	9.53	<u>1.96</u>
Total Gallons Removed To Date, as gasoline:	1.8	1.8	3.7	13.3	15.2

Table 5 Soil-Vapor Extraction System Operation and Performance Data

Location: 1001 San Pablo Avenue

Albany, California

Vapor Treatment Unit: Therm Tech Model

VAC-10 thermal/catalytic

oxidizer

Consultant: EMCON

1921 Ringwood Avenue

Start-Up Date: 12-07-93 Operation and Performance Data From: 12-07-93

	San Jose, California		S	ystem shut dov	To: 0	1-01-98
Date Begin:		12-16-93	12-21-93	12-25-93	12-29-93	12-31-93
Date End:		12-21-93	12-25-93	12-29-93	12-31-93	01-07-94
Mode of Oxidation:		Therm-Ox	Therm-Ox	Therm-Ox	Therm-Ox	Therm-Ox
Days of Operation:		0	4	0	2	0
Days of Downtime:		5	0	4	0	7
Average Vapor Concen	trations (1)					
Well Field Influent	: ppmv (2) as gasoline (3)	NA	NA	NA	NA	NA
	mg/m3 (4) as gasoline	NA	NA	NA	NA	NA
	ppmv as benzene (5)	NA	NA	NA	NA	NA
	mg/m3 as benzene	NA	NA	NA	NA	NA
System Influent	ppmv as gasoline	NA	NA	NA	NA	NA
	mg/m3 as gasoline	NA	NA	NA	NA	NA
	ppmv as benzene	NA	NA	NA	NA	NA
	mg/m3 as benzene	NA	NA	NA	NA	NA
System Effluent:	ppmv as gasoline	NA	NA	NA	NA	NA
	mg/m3 as gasoline	NA	NA	NA	NA	NA
	ppmv as benzene	NA	NA	NA	NA	NA
	mg/m3 as benzene	NA	NA	NA	NA	NA
Average Well Field Flow	Rate (6), scfm (7):	0.0	20.0	0.0	54.0	0.0
Average System Influent	Flow Rate (6), scfm:	0.0	100.0	0.0	78.0	0.0
Average Destruction Eff	iciency (8), percent (9):	NA	NA	NA	NA	NA
Average Emission Rates	(10), pounds per day (11)					
Gasoline:		0.00	0.00	0.00	0.00	0.00
Benzene:		0.00	0.00	0.00	0.00	0.00
Operating Hours This Per	riod:	0.00	104.00	0.00	43,00	0.00
Operating Hours To Date	:	183.0	287.0	287.0	330.0	330.0
SVE Pounds/ Hour Remo	oval Rate, as gasoline (12):	0.00	0.00	0.00	0.00	0.00
SVE Pounds Removed T	his Period, as gasoline (13):	0.00	0.00	0.00	0.00	0.00
	This Period, as gasoline (14):	0.00	00.0	0.00	0.00	0.00
Total Pounds Removed T	his Period, as gasoline (15):	0.00	0.00	0.00	0.00	0.00
Total Pounds Removed T	o Date, as gasoline:	94.3	94.3	94.3	94.3	94.3
Total Gallons Removed 1	This Period, as gasoline (16):	0.00	0.00	0.00	0.00	0.00
Total Gallons Removed 1	Γο Date, as gasoline:	15.2	15.2	15.2	15.2	15.2

Table 5 Soil-Vapor Extraction System Operation and Performance Data

Location: 1001 San Pablo Avenue

Albany, California

Vapor Treatment Unit: Therm Tech Model

VAC-10 thermal/catalytic

oxidizer

Consultant: EMCON

1921 Ringwood Avenue San Jose, California

Start-Up Date: 12-07-93

Operation and Performance Data From: 12-07-93

To: 01-01-98

San Jose, California		S	ystem shut dov	1-01-98	
Date Begin:	01-07-94	01-12-94	01-24-94	03-31-94	12-31-94
Date End:	01-12-94	01-24-94	03-31-94	12-31-94	02-06-95
Mode of Oxidation:	Therm-Ox	Therm-Ox	Therm-Ox	Therm-Ox	Therm-Ox
Days of Operation:	5	12	0	0	0
Days of Downtime:	0	0	66	275	37
Average Vapor Concentrations (1)					
Well Field Influent: ppmv (2) as gasoline (3)	NA	NA	NA	NA	NA
mg/m3 (4) as gasoline	NA	NA	NA	NA	NA
ppmv as benzene (5)	NA	NA	NA	NA	NA
mg/m3 as benzene	NA	NA	NA	NA	NA
System Influent: ppmv as gasoline	NA	690	NA	NA	NA
mg/m3 as gasoline	NA	2500	NA	NA	NA
ppmv as benzene	NA	11	NA	NA	NA
mg/m3 as benzene	NA	37	NA	NA	NA
System Effluent: ppmv as gasoline	NA	14	NA	NA	NA
mg/m3 as gasoline	NA	52	NA	NA	NA
ppmv as benzene	NA	0.29	NA	NA	NA
mg/m3 as benzene	NA	0.93	NA	NA	NA
Average Well Field Flow Rate (6), scfm (7):	37.0	41.0	0.0	0.0	0.0
Average System Influent Flow Rate (6), scfm:	60.0	64.0	0.0	0.0	0.0
Average Destruction Efficiency (8), percent (9):	97.9	97.9	NA	NA	NA
Average Emission Rates (10), pounds per day (11)					
Gasoline:	0.30	0.30	0.00	0.00	0.00
Benzene:	0.01	0.01	0.00	0.00	0.00
Operating Hours This Period:	123.00	285.00	0.00	0.00	8.90
Operating Hours To Date:	453.0	738.0	738.0	738.0	746.9
SVE Pounds/ Hour Removal Rate, as gasoline (12):	0.48	0.60	0.00	0.00	0.00
SVE Pounds Removed This Period, as gasoline (13):	59.40	170.67	0.00	0.00	0.00
GWE Pounds Removed This Period, as gasoline (14):	0.00	0.00	<u>0.00</u>	0.00	0.00
Total Pounds Removed This Period, as gasoline (15):	59.40	170.67	0.00	0.00	0.00
Total Pounds Removed To Date, as gasoline:	153.7	324.3	324.3	324.3	324.3
Total Gallons Removed This Period, as gasoline (16):	9.58	27.53	0.00	0.00	0.00
Total Gallons Removed To Date, as gasoline:	24.8	52.3	52.3	52.3	52.3

Table 5 Soil-Vapor Extraction System Operation and Performance Data

Location: 1001 San Pablo Avenue

Albany, California

Vapor Treatment Unit: Therm Tech Model

VAC-10 thermal/catalytic

Start-Up Date: 12-07-93

oxidizer

Consultant: EMCON

1921 Ringwood Avenue

Operation and Performance Data From: 12-07-93

San Jose, California

To: 01-01-98

	 		,		
Date Begin:	02-06-95	03-01-95	04-01-95	06-01-95	07-01-95
Date End:	03-01-95	04-01-95	06-01-95	07-01-95	08-01-95
Mode of Oxidation:	Therm-Ox	Therm-Ox	Therm-Ox	Cat-Ox (19)	Cat-Ox
Days of Operation:	21	7	0	5	26
Days of Downtime:	2	24	61	25	5
Average Vapor Concentrations (1)					
Well Field Influent: ppmv (2) as gasoline (3)	1800	2500	NA	3300	130
mg/m3 (4) as gasoline	6650	8900	NA	12000	480
ppmv as benzene (5)	17	31	NA	50	4
mg/m3 as benzene	62	99	NA	170	14
System Influent: ppmv as gasoline	240	<15	NA	600	130
mg/m3 as gasoline	880	<60	NA	2200	480
ppmv as benzene	6	<0.1	NA	10	4
mg/m3 as benzene	21	<0.5	NA	34	14
System Effluent: ppmv as gasoline	<15	<15	NA	<15	<15
mg/m3 as gasoline	<60	<60	NA	<60	<60
ppmv as benzene	< 0.1	< 0.1	NA	0.5	< 0.1
mg/m3 as benzene	<0.5	<0.5	NA	1.5	< 0.5
Average Well Field Flow Rate (6), scfm (7):	4.7	4.1	1.2	20.9	25.2
Average System Influent Flow Rate (6), scfm:	35.6	32.7	25.3	33.8	33.6
Average Destruction Efficiency (8), percent (9):	93.2	NA	NA	97.3	87.5
Average Emission Rates (10), pounds per day (11)					
Gasoline:	0.19	0.18	NA	0.18	0.18
Benzene:	0.00	0.00	NA	0.00	0.00
Operating Hours This Period:	501,95	162.83	3.02	112.33	614.38
Operating Hours To Date:	1248.9	1411.7	1414.7	1527.0	2141.4
SVE Pounds/ Hour Removal Rate, as gasoline (12):	0.12	0.14	0.00	0.94	0.05
SVE Pounds Removed This Period, as gasoline (13):	58.72	22.24	0.00	105.44	27.81
GWE Pounds Removed This Period, as gasoline (14):	4.28	0.31	0.00	1.42	0.00
Total Pounds Removed This Period, as gasoline (15):	63.00	22.55	0.00	106.86	27.81
Total Pounds Removed To Date, as gasoline:	387.3	409.9	409.9	516.8	544.6
Total Gallons Removed This Period, as gasoline (16):	10.16	3.64	0.00	17.24	4.49
Total Gallons Removed To Date, as gasoline:	62.5	66.1	66.1	83.4	87.8

Table 5 Soil-Vapor Extraction System Operation and Performance Data

Location: 1001 San Pablo Avenue

Albany, California

Vapor Treatment Unit: Therm Tech Model VAC-10 thermal/catalytic

oxidizer

Consultant: EMCON

1921 Ringwood Avenue San Jose, California

Start-Up Date: 12-07-93 Operation and Performance Data From: 12-07-93

To: 01-01-98

		S	System shut down on 8-12-96.				
Date Begin:	08-01-95	09-01-95	10-01-95	11-01-95	12-01-95		
Date End:	09-01-95	10-01-95	11-01-95	12-01-95	01-01-96		
Mode of Oxidation:	Cat-Ox	Cat-Ox	Cat-Ox	Cat-Ox	Cat-Ox		
Days of Operation:	23	30	26	30	21		
Days of Downtime:	8	0	5	1	10		
Average Vapor Concentrations (1)							
Well Field Influent: ppmv (2) as gasoline (3)	1850	617	425	850	940		
mg/m3 (4) as gasoline	7800	2233	1535	3100	3385		
ppmv as benzene (5)	17.5	5.9	4.7	11	7.4		
mg/m3 as benzene	56	19	15	36	23		
System Influent: ppmv as gasoline	1950	457	320	570	310		
mg/m3 as gasoline	8300	1667	1165	2100	1300		
ppmv as benzene	20	4.6	3.9	7	4.1		
mg/m3 as benzene	63	15	12	23	13		
System Effluent: ppmv as gasoline	54	<15	<15	<15	17		
mg/m3 as gasoline	155	<60	<60	<60	63		
ppmv as benzene	l	0.2	0.2	0.4	0.3		
mg/m3 as benzene	3.2	0.6	0.5	1,2	0.9		
Average Well Field Flow Rate (6), scfm (7):	27.7	139.7	91.2	68.0	39.5		
Average System Influent Flow Rate (6), scfm:	76.5	114.7	88.4	73.4	57.8		
Average Destruction Efficiency (8), percent (9):	98.1	96.4	94.8	97.1	95.2		
Average Emission Rates (10), pounds per day (11)							
Gasoline:	1.07	0.62	0.48	0.40	0.33		
Benzene:	0.02	0.01	0.00	0.01	0.00		
Operating Hours This Period:	<u>562.61</u>	717,42	624.47	708.09	493.54		
Operating Hours To Date:	2704.0	3421.4	4045.9	4754.0	5247.5		
SVE Pounds/ Hour Removal Rate, as gasoline (12):	0.81	1.17	0.52	0.79	0.50		
SVE Pounds Removed This Period, as gasoline (13):	454.96	837.62	327.19	558.66	246.98		
GWE Pounds Removed This Period, as gasoline (14):	0.49	0.24	0.07	11.02	<u>5.51</u>		
Total Pounds Removed This Period, as gasoline (15):	455.45	837.86	327.26	569.68	252.49		
Total Pounds Removed To Date, as gasoline:	1000.0	1837.9	2165.1	2734.8	2987.3		
Total Gallons Removed This Period, as gasoline (16):	<u>73.46</u>	<u>135.15</u>	<u>52.79</u>	<u>91.89</u>	40.73		
Total Gallons Removed To Date, as gasoline:	161.3	296.5	349.2	441.1	481.9		

Table 5 Soil-Vapor Extraction System Operation and Performance Data

Location: 1001 San Pablo Avenue

Albany, California

Vapor Treatment Unit: Therm Tech Model

VAC-10 thermal/catalytic

oxidizer

Consultant: EMCON

1921 Ringwood Avenue San Jose, California

Start-Up Date: 12-07-93

Operation and Performance Data From: 12-07-93

To: 01-01-98

			y otom snae do .		
Date Begin:	01-01-96	02-01-96 (20)	03-01-96	04-01-96	05-01-96
Date End:	02-01-96	03-01-96	04-01-96	05-01-96	06-01-96
Mode of Oxidation:	Cat-Ox	Cat-Ox	Cat-Ox	Cat-Ox	Cat-Ox
Days of Operation:	31	29	24	0	5
Days of Downtime:	0	0	7	30	26
Average Vapor Concentrations (1)					
Well Field Influent: ppmv (2) as gasoline (3)	<15	<15	NA	NA	NA
mg/m3 (4) as gasoline	<60	<60	NA	NA	NA
ppmv as benzene (5)	<0.1	<0.1	NA	NA	NA
mg/m3 as benzene	<0.5	<0.5	NA	NA	NA
System Influent: ppmv as gasoline	<15	<15	NA	NA	NA
mg/m3 as gasoline	<60	<60	NA	NA	NA
ppmv as benzene	0.3	0.3	NA	NA	NA
mg/m3 as benzene	0.9	0.9	NA	NA	NA
System Effluent: ppmv as gasoline	<15	<15	NA	NA	NA
mg/m3 as gasoline	<60	<60	NA	NA	NA
ppmv as benzene	<0.1	< 0.1	NA	NA	NA
mg/m3 as benzene	<0.5	<0.5	NA	NA	NA
Average Well Field Flow Rate (6), scfm (7):	24.8	28.6	0.0	0.0	32.5
Average System Influent Flow Rate (6), scfm:	51.2	53.1	0.0	0.0	41.3
Average Destruction Efficiency (8), percent (9):	NA	NA	NA	NA	NA
Average Emission Rates (10), pounds per day (11)					
Gasoline:	0.28	0.29	NA	NA	NA
Benzene:	0.00	0.00	NA	NA	NA
Operating Hours This Period:	744.00	158.00	0.00	2.38	120.25
Operating Hours To Date:	5991.5	6149.5	6149.5	6151.9	6272.2
SVE Pounds/ Hour Removal Rate, as gasoline (12):	0.01	0.01	0.00	0,00	0.01
SVE Pounds Removed This Period, as gasoline (13):	4.14	1.01	0.00	0.00	0.88
GWE Pounds Removed This Period, as gasoline (14):	<u>3.99</u>	0.00	0.01	00.0	0.00
Total Pounds Removed This Period, as gasoline (15):	8.13	1.01	0.01	0.00	0.88
Total Pounds Removed To Date, as gasoline:	2995.5	2996.5	2996.5	2996.5	2997.4
Total Gallons Removed This Period, as gasoline (16):	<u>1.31</u>	0.16	0.00	0.00	0.14
Total Gallons Removed To Date, as gasoline:	483.2	483.3	483.3	483.3	483.5

Table 5 Soil-Vapor Extraction System Operation and Performance Data

Location: 1001 San Pablo Avenue

Albany, California

Vapor Treatment Unit: Therm Tech Model

VAC-10 thermal/catalytic

oxidizer

Consultant: EMCON

1921 Ringwood Avenue

Start-Up Date: 12-07-93 Operation and Performance Data From: 12-07-93

Ta: 01 01 09

San Jose, California				To: 01	-01-98
		S	ystem shut dow		
Date Begin:	06-01-96	07-01-96	08-01-96	09-01-96	10-01-96
Date End:	07-01-96	08-01-96	09-01-96	10-01-96	01-01-97
Mode of Oxidation:	Cat-Ox	Cat-Ox	Cat-Ox	Cat-Ox	Cat-Ox
Days of Operation:	0	16	10	0	0
Days of Downtime:	30	15	21	30	92
Average Vapor Concentrations (1)					
Well Field Influent: ppmv (2) as gasoline (3)	NA	160	16	NA	NA
mg/m3 (4) as gasoline	NA	660	67	NA	NA
ppmv as benzene (5)	NA	0.8	< 0.2	NA	NA
mg/m3 as benzene	NA	2.5	<0.5	NA	NA
System Influent: ppmv as gasoline	NA	160	16	NA	NA
mg/m3 as gasoline	NA	660	67	NA	NA
ppmv as benzene	NA	0.8	< 0.2	NA	NA
mg/m3 as benzene	NA	2.5	<0.5	NA	NA
System Effluent: ppmv as gasoline	NA	<5	<5	NA	NA
mg/m3 as gasoline	NA	<20	<20	NA	NA
ppmv as benzene	NA	< 0.2	< 0.2	NA	NA
mg/m3 as benzene	NA	<0.5	<0.5	NA	NA
Average Well Field Flow Rate (6), scfm (7):	0.0	52.4	52.6	0.0	0.0
Average System Influent Flow Rate (6), scfm:	0.0	95.1	95.4	0.0	0.0
Average Destruction Efficiency (8), percent (9):	NA	97.0	70.1 (22)	NA	NA
Average Emission Rates (10), pounds per day (11)					
Gasoline:	NA	0.17	0.17	NA	NA
Benzene:	NA	0.00	0.00	NA	NA
Operating Hours This Period:	0.00	372.17	228.86	0.00	0.00
Operating Hours To Date:	6272.2	6644.3	6873.2	6873.2	6873.2
SVE Pounds/ Hour Removal Rate, as gasoline (12):	0.00	0.01	0.01	0.00	0.00
SVE Pounds Removed This Period, as gasoline (13):	0.00	4.38	2.70	0.00	0.00
GWE Pounds Removed This Period, as gasoline (14):	0.00	3.07	0.00	<u>0,QQ</u>	0.00
Total Pounds Removed This Period, as gasoline (15):	0.00	7.45	2.70	0.00	0.00
Total Pounds Removed To Date, as gasoline:	2997.4	3004.8	3007.5	3007.5	3007.5
Total Gallons Removed This Period, as gasoline (16):	0.00	<u>1,20</u>	<u>0.44</u>	0.00	0.00
Total Gallons Removed To Date, as gasoline:	483.5	484.7	485.1	485.1	485.1

Table 5
Soil-Vapor Extraction System
Operation and Performance Data

Location: 1001 San Pablo Avenue

Albany, California

Vapor Treatment Unit: Therm Tech Model

VAC-10 thermal/catalytic

oxidizer

Consultant: EMCON

1921 Ringwood Avenue San Jose, California Start-Up Date: 12-07-93 Operation and Performance Data From: 12-07-93

To: 01-01-98

			ystem shat dov	711 011 6-12-90.	
Date Begin:	01-01-97	04-01-97	07-01-97	10-01-97	11-01-97
Date End:	04-01-97	07-01-97	10-01-97	11-01-97	12-01-97
Mode of Oxidation:	Cat-Ox	Cat-Ox	Cat-Ox	Cat-Ox	Cat-Ox
Days of Operation:	0	0	0	0	14
Days of Downtime:	90	91	92	31	16
Average Vapor Concentrations (1)					
Well Field Influent: ppmv (2) as gasoline (3)	NA	NA	NA	NA	160
mg/m3 (4) as gasoline	NA	NA	NA	NA	640
ppmv as benzene (5)	NA	NA	NA	NA	0.6
mg/m3 as benzene	NA	NA	NA	NA	2
System Influent: ppmv as gasoline	NA	NA	NA	NA	160
mg/m3 as gasoline	NA	NA	NA	NA	640
ppmv as benzene	NA	NA	NA	NA	0.6
mg/m3 as benzene	NA	NA	NA	NA	2
System Effluent: ppmv as gasoline	NA	NA	NA	NA	8
mg/m3 as gasoline	NA	NA	NA	NA	34
ppmv as benzene	NA	NA	NA	NA	<0.1
mg/m3 as benzene	NA	NA	NA	NA	<0.4
Average Well Field Flow Rate (6), scfm (7);	0.0	0.0	0.0	0.0	118.7
Average System Influent Flow Rate (6), scfm:	0.0	0.0	0.0	0.0	221.4
Average Destruction Efficiency (8), percent (9):	NA	NA	NA	NA	94.7
Average Emission Rates (10), pounds per day (11)					
Gasoline:	NA	NA	NA	NA	0.68
Benzene:	NA	NA	NA	NA	NR
Operating Hours This Period:	0.00	0.00	0.00	0.00	337.86
Operating Hours To Date:	6873.2	6873.2	6873.2	6873.2	7211.1
SVE Pounds/ Hour Removal Rate, as gasoline (12):	0.00	0.00	0.00	0.00	0.03
SVE Pounds Removed This Period, as gasoline (13):	0.00	0.00	0.00	0.00	10.9
GWE Pounds Removed This Period, as gasoline (14):	0.00	0.00	0.00	0.00	0.00
Total Pounds Removed This Period, as gasoline (15):	0.00	0.00	0.00	0.00	9.01
Total Pounds Removed To Date, as gasoline:	3007.5	3007.5	3007.5	3007.5	3016.5
Total Gallons Removed This Period, as gasoline (16):	0.00	0.00	0.00	0.00	1.45
Total Gallons Removed To Date, as gasoline:	485.1	485.1	485.1	485. I	486.6

Table 5 Soil-Vapor Extraction System Operation and Performance Data

Number: 2035 Facility

Location: 1001 San Pablo Avenue

Albany, California

Vapor Treatment Unit: Therm Tech Model VAC-10 thermal/catalytic

oxidizer

Consultant: EMCON

Start-Up Date: 12-07-93 ice Data From: 12-07-93

	21 Ringwood Avenue		Operation and Performance Data From: 12-07-93
	n Jose, California		To: 01-01-98 System shut down on 8-12-96.
Date Begin:		[2-0]-97	
Date End:		01-01-98	
Mode of Oxidation:		Cat-Ox	
Days of Operation:		0	
Days of Downtime:		31	
Average Vapor Concentrati			
Well Field Influent: ppr	nv (2) as gașoline (3)	NA	
mg	/m3 (4) as gasoline	NA	
	nv as benzene (5)	NA	
mg	/m3 as benzene	NA	
System Influent: ppr	nv as gasoline	NA	
mg	/m3 as gasoline	NA	
	nv as benzene	NA	
mg	/m3 as benzene	NA	
System Effluent: ppr	nv as gasoline	NA	
mg	/m3 as gasoline	NA	
ррг	nv as benzene	NA	
mg	/m3 as benzene	NA	
Average Well Field Flow Rate	e (6), scfm (7):	0.0	
Average System Influent Flov	/ Rate (6), scfm:	0.0	
Average Destruction Efficien	cy (8), percent (9);	NA	
Average Emission Rates (10	, pounds per day (11)		
Gasoline:		NA	
Benzene:		NA	
Operating Hours This Period:		0.07	
Operating Hours To Date:		7211.1	
SVE Pounds/ Hour Removal I	Rate, as gasoline (12):	0.00	
SVE Pounds Removed This P	eriod, as gasoline (13):	0.00	
GWE Pounds Removed This I	Period, as gasoline (14):	0.00	
Total Pounds Removed This F	Period, as gasoline (15):	0.00	
Total Pounds Removed To Da	ite, as gasoline:	3016.5	
Total Gallons Removed This	Period, as gasoline (16):	0.00	
Total Gallons Removed To Da	ate, as gasoline:	486.6	

Table 5 Soil-Vapor Extraction System Operation and Performance Data

Facility Number: 2035

Location: 1001 San Pablo Avenue

Albany, California

Vapor Treatment Unit: Therm Tech Model

VAC-10 thermal/catalytic

oxidizer

Consultant: EMCON

1921 Ringwood Avenue San Jose, California Start-Up Date: 12-07-93 Operation and Performance Data From: 12-07-93

To: 01-01-98

System shut down on 8-12-96.

			
CURRENT REPORTING PERIOD:	10-01-97	to 01-01-98	-
DAYS / HOURS IN PERIOD:	92	2208.0	
DAYS / HOURS OF OPERATION:	14	337.9	
DAYS / HOURS OF DOWN TIME:	78	1870.1	
PERCENT OPERATIONAL:		15.3 %	
PERIOD POUNDS REMOVED:	9.0		
PERIOD GALLONS REMOVED:	1.5		
AVERAGE WELL FIELD FLOW RATE (scfm):		118.7	
AVERAGE SYSTEM INFLUENT FLOW RATE (scfm):		221.4	

2. ppmv: parts per million by volume

Concentration (as gasoline in ppmv) = [concentration (as gasoline in mg/m3) x 24.05 (lb/m3/lb-mole of air)/mg] / 87 lb/lb-mole

mg/m3: milligrams per cubic meter

Concentration (as benzene in ppmv) = [concentration (as benzene in mg/m3) x 24.05 (lb/m3/lb-mole of air)/mg] / 78 lb/lb-mole

7. scfm; flow in standard cubic feet per minute at one atmosphere and 70 degrees Fahrenheit

- 13. Soil-vapor extraction (SVE) pounds removed this period (as gasoline) = pounds/ hour removal rate (SVE) x hours of operation (SVE)
- 14. Groundwater extraction (GWE); refer to Table 8 for GWE system performance data
- 15. Represents the total mass recovered by the SVE and GWE systems, and the total mass abated by the thermal/catalytic oxidizer
- 16. gallons removed this period (as gasoline) = pounds removed this period (as gasoline) x 0.1613 gallons/pound of gasoline
- 17. Therm-Ox: thermal oxidation
- 18. NA: not analyzed, not applicable, or not available
- 19. Cat-Ox: catalytic oxidation; the SVE system's abatement unit was converted to the Cat-Ox mode of operation on June 20, 1995
- 20. On February 7, 1996 the SVE wells were taken off-line; however, the therm tech unit remained on for the groundwater extraction system.
- 21. The utility costs for February and March were \$694.00 and \$649.00, respectively. The SVE system was shut down on February 7, 1996, therefore cost per pound was not calculated for these periods. The utility costs incurred during February and March are associated with the off gas abatement for the aeration tank.
- 22. Although the destruction efficiency appeared to be less than 90 percent, laboratory analytical results collected during this period indicate the effluent TVHG and benzene concentrations in off-gas discharged to the atmosphere were below laboratory detection limits, indicating compliance with BAAQMD discharge requirements.

Average vapor monitoring concentrations were calculated for all periods after February 6, 1995. Average concentrations are based on discrete sample results reported during the month; refer to Appendix B for discrete sample results.

Between December 7, 1993, and February 6, 1995;

^{5.} Between December 7, 1993, and February 6, 1995;

^{6.} Average flow rates (time weighted average) are based on instantaneous flow rates recorded during the month; refer to Appendix B for instantaneous flow data.

^{8.} Average destruction efficiencies are calculated using monthly average concentrations; refer to Appendix B for instantaneous destruction efficiency data.

^{9.} destruction efficiency, percent = (fsystem influent concentration (as gasoline in mg/m3) - system effluent concentration (as gasoline in mg/m3)] / system influent concentration (as gasoline in mg/m3)) x 100 percent

^{10.} Average emission rates are calculated using monthly average concentrations and flow rates; refer to Appendix B for instantaneous emission rate data.

^{11.} emission rates (pounds per day) = system effluent concentration (as gasoline or benzene in mg/m3) x system influent flow rate (scfm) x 0.02832 m3/ft3 x 1440 minutes/day x 1 pound/454,000 mg

^{12.} pounds/ hour removal rate (as gasoline) = well field influent concentration (as gasoline in mg/m3) x well field influent flow rate (scfm) x 0.02832 m3/ft3 x 60 minutes/hour x 1 pound/454,000 mg

Table 6
Soil-Vapor Extraction Well Data

Date: 01-20-98

						Well Ide	ntification								
		VW-1	1 VW-2 VW-3				VW-2 VW-3 VW-4				VW-2 VW-3			VW-4	
	Valve		Vacuum	Valve		Vacuum	Valve		Vacuum	Valve		Vacuur			
Date	Position	TVHG	Response	Position	TVHG	Response	Position	TVHG	Response	Position	TVHG	Respon			
		ppmv	in-H2O		ppmv	in-H2O		ppmv	in-H2O		ppmv	in-H20			
or SVE well m	onitoring data prior	to October 1, 19!	95, please refer to t	l he fourth quarter 1	1995 groundwater	monitoring report	for this site.			"					
10-26-95	open	NA	25.5	орел	NA	25.5	closed	NA	0.0	open	NA	25.3			
12-05-95	open	NA	54.0	орел	NA	54.0	closed	NA	NA	closed	NA	NA			
02-07-96	open	698 PID	NA	орел	390 PID	NA	open	501 PID	NA	ореп	610 PID	NA			
03-25-96	System was manu	ally shut down.								-					
05-17-96	open	1945 PID	30.0	closed	101 PID	18.0	closed	50.1 PID	18.0	орел	197 PID	25.0			
05-22-96	System was manu	ally shut down.													
07-16-96	open	7600 PID	NA	open	3100 PID	NA	open	1450 PID	NA	open	3310 PID	NA			
08-08-96	open	NA	NA	open	NA	NA	open	NA	NA	open	NA	NΑ			
02-04-97	closed	NA	NA	closed	NA	NA	closed	NA	NA	closed	NA	NA			
02-18-97	closed	NA	NA	closed	NA	ÑΑ	closed	NA	NA	closed	NA	NA			
03-07-97	closed	NA	NA	closed	NA	NA	closed	NA	NA	closed	NA	NA			
05-23-97	closed	NA	NA	closed	NA	NA	closed	NA.	NA	closed	NA	NA			
07-23-97	closed	NA	NA	closed	NA	NA	closed	NA	NA	closed	NA	NA			
08-04-97	closed	NA	NA	closed	NA	NA	closed	NA	NA	closed	NA	NA			
09-11-97	closed	NA	NA	closed	NA	NA	closed	NA	NA	closed	NA	NA			
10-22-97	closed	NA	NA	closed	NA	NA	closed	NA	NA	closed	NA	NA			
11-05-97	open	NA	NA	open	NA	NA	open	NA	NA	open	NΛ	NA			
11-19-97	closed	NA	NA	closed	NA	NA	closed	NA	NA	closed	NA	NA			
12-15-97	closed	NA	NA	closed	NA	NA	closed	NA	NA	closed	NA	NA			

TVHG: concentration of total volatile hydrocarbons as gasoline

ppmv: parts per million by volume

in-H2O: inches of water open: open to the system

open(b): open to the system and bubbling air

passive: open to the atmosphere

closed: closed to the system and atmosphere

closed (b): closed to the system and atmosphere, but bubbling air

NA: not analyzed or not measured

PID: TVHG concentration was measured with a portable photo-ionization detector

LAB: TVHG concentration was analyzed in the laboratory

Table 6
Soil-Vapor Extraction Well Data

Date: 01-20-98

	Well Identification												
		VW-5			VW-6			VW-7			VW-8		
	Valve		Vacuum	Valve		Vacuum	Valve	, <u>.</u>	Vacuum	Valve	·-···	Vacuun	
Date	Position	TVHG	Response	Position	TVHG	Response	Position	TVHG	Response	Position	TVHG	Respon	
		ppmv	in-H2O		ppmv	in-H2O		ppmv	in-H2O		ppmv	in-H20	
or SVE well n	l nonitoring data prior	ta October 1, 199	95, please refer to t	l he fourth quarter I	995 groundwater	monitoring report	for this site,			· · · · · · · · · · · · · · · · · · ·	· · · · · · · · · · · · · · · · · · ·		
10-26-95	open	NA	25.3	closed	NA	0.0	open	NA	19.0	орел	NA	21.9	
12-05-95	closed	NA	NA	closed	NA	NA	open	NA	54.0	closed	NA	NA	
02-07-96	open	47.2 PID	NA	open	840 PID	NA	open	102 PID	NA	open	780 PID	NA	
03-25-96	System was manu	ally shut down.										7.7.	
05-17-96	closed	80.6 PID	20.0	open	195 PID	22.0	орел	419 PID	28.0	closed	116 PID	18.0	
05-22-96	System was manu	ally shut down.		!								10.0	
07-16-96	open	300 PID	NA	open	NA	NA	open	590 PID	NA	open	1400 PID	NA	
08-08-96	open	NA	NA	open	NA	NA	open	NA	NA	open	NA	NA	
02-04-97	closed	NA	NA	closed	NA	NA	closed	NA	NA	closed	NA	NA	
02-18-97	closed	NA	NA	closed	NA	NA	closed	NA	NA	closed	NA	NA	
03-07-97	closed	NA	NA	closed	NA	NA	closed	NA	NA	closed	NA	NA	
05-23-97	closed	NA	NA	closed	NA	NA	closed	NA	NA	closed	NA	NA	
07-23-97	closed	NA	NA	closed	NA	NA N	closed	NA	NA	closed	NA	NA	
08-04-97	closed	NA	NA	closed	NA	NA	closed	NA	NA	closed	NA	NA	
09-11-97	closed	NA	NA	closed	NA	NA	closed	NA	NA	closed	NA	NA	
10-22-97	closed	NA	NA	closed	NA	NA	closed	NA	NA	closed	NA	NA	
11-05-97	open	NA	NA	ореп	NA	NA	open	NA	NA	open	NA	NA	
11-19-97	closed	NA	NA	cłosed	NA	NA NA	closed	NA	NA NA	closed	NA	NΑ	
12-15-97	closed	NA	NA	closed	NA	NA.	closed	NA	NA	closed	NA.	NA	

TVHG: concentration of total volatile hydrocarbons as gasoline

ppmv: parts per million by volume

in-H2O: inches of water

open: open to the system

open(b): open to the system and bubbling air

passive: open to the atmosphere

closed: closed to the system and atmosphere

closed (b): closed to the system and atmosphere, but bubbling air

NA: not analyzed or not measured

PID: TVHG concentration was measured with a portable photo-ionization detector

LAB: TVHG concentration was analyzed in the laboratory

Table 6
Soil-Vapor Extraction Well Data

Date: 01-20-98

						Well Ide	ntification					
		VW-9			RW-1			AS-1V			AS-2V	
	Valve		Vacuum	Valve		Vacuum	Valve		Vacuum	Valve		Vacuum
Date	Position	TVHG	Response	Position	TVHG	Response	Position	TVHG	Response	Position	TVHG	Response
		ppmv	in-H2O		ppmv	in-H2O		ppmv	in-H2O		ppmv	in-H2O
For SVE well m	l nonitoring data priot	to October 1, 199	5, please refer to t	l he fourth quarter 1	995 groundwater i	monitoring report	for this site.		:			
10-26-95	open	NA	22.4	open	NA	23.9	open	NA	25.7	open	NA	25.7
12-05-95	closed	NA	NA	closed	NA	NA	open	NA	54.0	closed	NA	NA
02-07-96	орел	1110 PID	NA	open	57 PID	NA	open	465 PID	NA	open	465 PID	NA
03-25-96	System was manu	ally shut down.										
05-17-96	open	384 PID	28.0	closed	118 PID	25.0	open	146 PID	30.0	open	208 PID	30.0
05-22-96	System was man	ially shut down.										
07-16-96	open	425 PID	NA	орея	1140 PID	NA	ореп	4600 PID	NA	open	4600 PID	NA
08-08-96	open	NA	NA	open	NA	NA	орел	NA	NA	open	NA	NA
02-04-97	closed	NA	NA	closed	NA	NA	closed	NA	NA	closed	NA	NA
02-18-97	closed	NA	NA ·	closed (b)	NA	NA	closed	NA	NA	closed	NA	NA
03-07-97	closed	NA	NA	closed	NA	NA	closed	NA	NA	closed	NA	NA
05-23-97	closed	NA	NA	closed (b)	NA	NA	closed	NA	NA	closed	NA	NA
07-23-97	closed	NA	NA	closed (b)	NA	NA	closed	NA	NA	closed	NA	NA
08-04-97	closed	NA	NA	elosed	NA	NA	closed	NA	NA	closed	NA	NA
09-11-97	closed	NA	NA	closed (b)	NA	NA	closed	NA	NA	closed	NA	NA
10-22-97	closed	NA	NA	closed(b)	NA	NA	closed	NA	NA	closed	NA	NA
11-05-97	open	NA	NA	open(b)	NA	NA	ореп	NA	NA '	open	NA	NA
11-19-97	closed	NA	NA	closed(b)	NA	NA	closed	NA	NA	closed	NA	NA
12-15-97	closed	NA	NA	closed(b)	NA	NA	closed	NA	NA	closed	NA	NA

TVHG: concentration of total volatile hydrocarbons as gasoline

ppmv: parts per million by volume

in-H2O: inches of water open: open to the system

open(b): open to the system and bubbling air

passive: open to the atmosphere

closed: closed to the system and atmosphere

closed (b): closed to the system and atmosphere, but bubbling air

NA: not analyzed or not measured

PID: TVHG concentration was measured with a portable photo-ionization detector

LAB: TVHG concentration was analyzed in the laboratory

Table 7 Influent and Effluent Groundwater Analyses

Facility Nur Location:	nber: 2035 1001 San Pablo Albany, Californ		Groundwater Treatment Unit: Aeration Tank wit onue Two 200 Pound Liquid-Phase Carbon Polish Un								
Well Desig- nation	Water Sample Field Date	TPHG	Groundwater treatment system was shut down on Ethyl- Total Benzene Toluene benzene Xylenes								
		μg/L	µg/L	μg/L	μg/L	μg/L					
I-1	02-08-95	NA	NA	NA	NA	NA					
I-1	02-08-95	49000	4300	4900	1000	5200					
[-]	02-14-95	33000	4300	5800	970	5600					
Ĭ-1	02-21-95	21000	940	1500	360	4000					
I-]	02-28-95	15000	430	290	54	2000					
[-]	06-20-95	20000	1500	1200	220	2300					
I-1	08-08-95	11000	970	1100	210	1800					
I-1	09-12-95	2700	200	150	29	290					
I-1	10-11-95	1000	97	38	7	69					
I-1	11-08-95	2500	38	27	8	240					
I-1	11-30-95	29000	190	530	300	3100					
I-1	01-30-96	70	4.5	1.8	<0.5	8.3					
I-1	07-16-96	4300	530	210	110	550					
I-2	02-08-95	NA	NA	NA	NA	NA					
I-2	02-08-95	1500	59	70	14	86					
I-2	02-14-95	1500	59	70	14	86					
I-2	02-21-95	340	7.2	8.8	1.9	37					
I-2	02-28-95	390	3.9	2.5	0.9	16					
I-2	06-20-95	2200	- 30	27	11	77					
1-2	08-08-95	330	17	18	3.5	36					
1-2	09-12-95	78	4.1	3	< 0.5	8.9					
1-2	10-11-95	<50	0.9	< 0.5	< 0.5	1					
I-2	11-08-95	1800	2.5	2.7	3.8	35					
I-2	11-30-95	220	5	7.4	1.7	22					
I-2	01-30-96	< 50	< 0.5	< 0.5	< 0.5	<0.5					
1.0	07.16.06	220	22	7.0	4.5	21					

I-2

07-16-96

230

23

7.6

4.5

21

Table 7
Influent and Effluent Groundwater Analyses

Facility Num Location:	nber: 2035 1001 San Pablo Albany, Califort		Groundwater Treatment Unit: Aeration Tank with Two 200 Pound Liquid-Phase Carbon Polish Units								
Well Desig- nation	Water Sample Field Date	TPHG μg/L	Gr Benzene µg/L	was shut down o Total Xylenes µg/L	n 8-8-96.						
I-3	02-08-95 02-14-95 02-21-95 02-28-95 06-20-95 08-08-95 09-12-95 10-11-95 11-08-95 11-30-95 01-30-96 07-16-96	<50 <50 <50 <50 <50 <50 <50 <50 <50 <50	<0.5 <0.5 <0.5 <0.5 <0.5 <0.5 <0.5 <0.5	<0.5 <0.5 <0.5 <0.5 <0.5 <0.5 <0.5 <0.5	<0.5 <0.5 <0.5 <0.5 <0.5 <0.5 <0.5 <0.5	<0.5 <0.5 <0.5 <0.5 <0.5 <0.5 <0.5 <0.5					
E-1 E-1 E-1 E-1 E-1 E-1 E-1 E-1 E-1 E-1	02-08-95 02-14-95 02-21-95 02-28-95 06-20-95 08-08-95 09-12-95 10-11-95 11-08-95 11-30-95 01-30-96 07-16-96	<50 <50 <50 <50 <50 <50 <50 <50 <50 <50	0.7 <0.5 <0.5 <0.5 <0.5 <0.5 <0.5 <0.5 <0.5	<0.5 <0.5 <0.5 <0.5 <0.5 <0.5 <0.5 <0.5	<0.5 <0.5 <0.5 <0.5 <0.5 <0.5 <0.5 <0.5	<0.5 <0.5 <0.5 <0.5 <0.5 <0.5 <0.5 <0.5					

TPHG: total petroleum hydrocarbons as gasoline

μg/L: micrograms per liter

NA: not analyzed

Table 8
Estimated Total Dissolved TPHG Removed

Groundwater Treatment Unit: Aeration Tank with Two 200 Pound Liquid-Phase Carbon Polish Units

		Groun	dwater Extr	action		Removal D	ata		Benzene Removal Data					
Sample Desig- nation	Sample Date	Total Volume Extracted	Period Volume Extracted	Period Flow Rate	Period Influent Concentration	Period Removal Rate	Period Pounds Removed '	Total Pounds Removed	Total Gallons Removed ²	Period Influent Concentration	Period Removal Rate	Period Pounds Removed '	Total Pounds Removed	Total Gallons Removed
		gallons	gallons	gpd	μg/L	lbs/day	pounds	pounds	gallons	μg/L	lbs/day	pounds	pounds	gallons
I-1 I-1 I-1 I-1 I-1 I-1 I-1 I-1 I-1 (6) I-1 (6) I-1 (6) I-1 I-1 (6)	12-22-95 01-01-96 01-30-96 04-01-96 07-16-96 08-08-96	331,575 382,464	0 252 449 14,170 13,289 2,570 337 9,238 5,483 11,018 9,100 40,120 44,912 22,945 16,552 60,124 45,639 34,749 50,889 was shut d	0 2,520 76 2,051 1,894 316 3 924 141 315 314 1,433 2,041 1,043 1,655 2,073 736 328 2,213 own on 8-	NA 49,000 33,000 21,000 15,000 15,000 20,000 20,000 11,000 2,700 1,000 29,000 29,000 29,000 70 70 4,300 4,300 8-96.	0.000 1.031 0.021 0.360 0.237 0.040 0.001 0.154 0.013 0.007 0.003 0.494 0.252 0.401 0.001 0.000 0.012 0.079	0.000 0.103 0.124 2.484 1.664 0.322 0.056 1.542 0.503 0.248 0.076 0.837 10.871 5.554 4.007 0.035 0.027 1.247 1.826	0.000 0.103 0.227 2.710 4.374 4.696 4.752 6.294 6.798 7.046 7.122 7.959 18.831 24.385 28.391 28.426 28.453 29.700 31.527	0.000 0.017 0.037 0.437 0.706 0.757 0.767 1.015 1.097 1.137 1.149 1.284 3.037 3.933 4.580 4.585 4.589 4.791 5.085	NA 4,300 4,300 940 430 430 1,500 1,500 970 200 97 38 190 190 190 4.5 4.5 530 530	0.0000 0.0904 0.0027 0.0161 0.0068 0.0011 0.0000 0.0116 0.0003 0.0005 0.0032 0.0017 0.0026 0.0001 0.0000 0.0015 0.0098	0.0000 0.0090 0.0161 0.1112 0.0477 0.0092 0.0042 0.1157 0.0444 0.0127 0.0712 0.0364 0.0262 0.0023 0.0017 0.1537 0.2251	0.0000 0.0090 0.0251 0.1363 0.1840 0.1932 0.1975 0.3131 0.3575 0.3759 0.3833 0.3960 0.4672 0.5036 0.5299 0.5321 0.5339 0.6876 0.9127	0.0000 0.0012 0.0035 0.0188 0.0254 0.0266 0.0272 0.0432 0.0493 0.0518 0.0529 0.0546 0.0644 0.0695 0.0731 0.0734 0.0736 0.0948 0.1259

Table 8
Estimated Total Dissolved TPHG Removed

Groundwater Treatment Unit: Aeration Tank with Two 200 Pound Liquid-Phase Carbon Polish Units

Total Gallons Removed * gallons 0.0000 0.0000 0.0000 0.0002 0.0002 0.0002 0.0002
0.0000 0.0000 0.0000 0.0002 0.0002 0.0002
0.0000 0.0000 0.0002 0.0002
0.0006 0.0007 0.0007 0.0009 0.0011 0.0012 0.0013 0.0014 0.0014 0.0014

Table 8 Estimated Total Dissolved TPHG Removed

ARCO Service Station 2035 1001 San Pablo Avenue, Albany, California

Groundwater Treatment Unit: Aeration Tank with Two 200 Pound Liquid-Phase Carbon Polish Units

		Ground	dwater Extr	action		TPHO	G Removal D	ata			Benze	ene Removal	<u>Data</u>	
Sample Desig- S nation	Sample Date	Total Volume Extracted gallons	Period Volume Extracted gallons	Period Flow Rate gpd	Period Influent Concentration µg/L	Period Removal Rate Ibs/day	Period Pounds Removed 1 pounds	Total Pounds Removed pounds	Total Gallons Removed ² gallons	Period Influent Concentration µg/L	Period Removal Rate Ibs/day	Period Pounds Removed' pounds	Total Pounds Removed pounds	Total Gallons Removed gallons
		RTING PE		07-01-97		10-01-97	•							
		N PERIOD	=	92	2,208.0									
		OF OPERA		0	0.0									
		OF DOWN		92	2,208.0									
PERCENT	I OPEKA	ATIONAL:			0%									
PERIOD C	GROUNE	WATER E	EXTRACTE	ED (gallons	s):	0								
			EMOVAL		·	0	pounds	0.000	gallons		0.0000	pounds	0.0000	gallons
HYDROC	ARBONS	S REMOVI	ED BY AEF	RATION T	`ANK:	0	pounds	0.000	gallons		0.0000	-	0.0000	gallons
HYDROC	ARBONS	S REMOVI	ED BY CAI	RBON:		0	pounds	0.000	gallons		0.0000	pounds	0.0000	gallons
PERCENT	T PRIMA	RY CARB	ON LOAD	ING: 5		0%								
PERIOD A	AVERA (GE FLOW	RATE (gpd	l):		0.0	(includes do	wn time)						
PERIOD A	AVERAC	GE FLOW	RATE (gpd):		0.0	(excludes do	wn time)						
PERIOD A	AVERAC	GE FLOW	RATE (gpm	n):		0.0	(excludes do	wn time)						

TPHG: total petroleum hydrocarbons as gasoline

gpd: gallons per day

µg/L: micrograms per liter

lbs/day: pounds per day

NA: not analyzed


gpm: gallons per minute

- *: The totalizer reading of the groundwater system was estimated from two consecutive monitoring events.
- **: The TPHG and benzene concentrations were assumed to be equal to the previous sampling event.
- 1. Period TPHG removed (pounds) = period influent TPHG concentration (µg/L) x period volume of groundwater extracted (gallons) x 3.7854 (liters/gallon) x 0.000000002205 (pounds/µg)
- 2. Total TPHG removed (gallons) = total TPHG removed (pounds) x 0.1613 (gallons/pound)
- 3. Period benzene removed (pounds) = period influent benzene concentration (µg/L) x period volume of groundwater extracted (gallons) x 3.7854 (liters/gallon) x 0.000000002205 (pounds/µg)
- 4. Total benzene removed (gallons) = total benzene removed (pounds) x 0.1379 (gallons/pound)
- 5. Percent carbon loading = (total TPHG removed by carbon / 10 pounds of TPH-G) x 100

The percent carbon loading calculation assumes a 5% by weight carbon adsorption efficiency. The treatment system uses two 200 pound carbon canisters.

Carbon Loading (10 lbs TPHG) = 1 canister x 200 lbs carbon/canister x 1 lb TPHG/20 lb carbon

6. Assumption that the BTEX and TPHG concentrations in the groundwater treatment system samples are the same as the previous sampling event on 11-30-95. System sampling schedule was reduced from monthly to quarterly by EBMUD during the third quarter 1995, therefore samples were not collected in December 1995.





Base map from USGS 7.5' Quad. Maps: Oakland West and Richmond, California. Photorevised 1980.

0 2000 4000

SCALE IN FEET





DATE NOV. 1997 DWN KAJ APP REV PROJECT NO. 805-123.004

FIGURE 1

ARCO PRODUCTS COMPANY SERVICE STATION 2035, 1001 SAN PABLO AVE. ALBANY, CALIFORNIA

QUARTERLY GROUNDWATER MONITORING SITE LOCATION






JOSE-CAD/DRAWINGS: R:\805-123\SJGWELEV.dwg Xrefs: <NONE> 1 = 30.00 DimScole: 1 = 30.00 Date: 3/10/98 Time: 1:25 PM Operator:

ARCO Service Station 2035

Soil-Vapor Extraction and Treatment System Historical Well Field Influent TVHG and Benzene Concentrations

Figure 4




TVHG: total volatile hydrocarbons as gasoline ppmv: parts per million by volume

Figure 5

ARCO Service Station 2035


Soil-Vapor Extraction and Treatment System
Historical Hydrocarbon Removal Rates



esj/j:\qtr_rpts\2035\2035tdb.xls\SVE Model:imi 20805-123.004

Figure 6

ARCO Service Station 2035
Historical Groundwater Treatment System




TPHG: total petroleum hydrocarbons as gasoline

µg/L; micrograms per liter

Figure 7

ARCO Service Station 2035

Iistorical Groundwater Treatment System Hydrocarbon Recovery Rates



APPENDIX A

ANALYTICAL RESULTS AND CHAIN OF CUSTODY DOCUMENTATION, FOURTH QUARTER 1997 GROUNDWATER MONITORING EVENT



November 17, 1997

Service Request No.: S9702252

Gary Messerotes EMCON 1921 Ringwood Avenue San Jose, CA 95131

RE: 20805-123.004/TO#21133.00/2035 ALBANY

Dear Mr. Messerotes:

The following pages contain analytical results for sample(s) received by the laboratory on November 4, 1997. Results of sample analyses are followed by Appendix A which contains sample custody documentation and quality assurance deliverables requested for this project. The work requested has been assigned the Service Request No. listed above. To help expedite our service, please refer to this number when contacting the laboratory.

Analytical results were produced by procedures consistent with Columbia Analytical Services' (CAS) Quality Assurance Manual (with any deviations noted). Signature of this CAS Analytical Report below confirms that pages 2 through 13, following, have been thoroughly reviewed and approved for release in accord with CAS Standard Operating Procedure ADM-DatRev3.

Please feel welcome to contact me should you have questions or further needs.

Sincerely,

Steven L. Green

Project Chemist

Greg Anderson

Regional QA Coordinator

Acronyms

A2LA American Association for Laboratory Accreditation

ASTM American Society for Testing and Materials

BOD Biochemical Oxygen Demand

BETEX Benzene, Toluene, Ethylbenzene, Xylenes

CAM California Assessment Metais
CARB California Air Resources Board

CAS Number Chemical Abstract Service registry Number

CFC Chlorofluorocarbon
CFU Colony-Forming Unit
COD Chemical Oxygen Demand

DEC Department of Environmental Conservation

DEQ Department of Environmental Quality
DHS Department of Health Services
DLCS Duplicate Laboratory Control Sample

DMS Duplicate Matrix Spike
DOE Department of Ecology
DOH Department of Health

EPA U. S. Environmental Protection Agency

ELAP Environmental Laboratory Accreditation Program

GC Gas Chromatography

GC/MS Gas Chromatography/Mass Spectrometry

IC Ion Chromatography

ICB Initial Calibration Blank sample

ICP Inductively Coupled Plasma atomic emission spectrometry

ICV Initial Calibration Verification sample

J Estimated concentration. The value is less than the MRL, but greater than or equal to

the MDL. If the value is equal to the MRL, the result is actually <MRL before rounding.

LUFT Laboratory Control Sample
Leaking Underground Fuel Tank

M Modified

MBAS Methylene Blue Active Substances

MCL Maximum Contaminant Level. The highest permissible concentration of a

substance allowed in drinking water as established by the U. S. EPA.

MDLMethod Detection LimitMPNMost Probable NumberMRLMethod Reporting Limit

MS Matrix Spike

MTBE Methyl tert-Butyl Ether

NA Not Applicable
NAN Not Analyzed
NC Not Calculated

NCASI

National Council of the paper industry for Air and Stream Improvement

ND

Not Detected at or above the method reporting/detection limit (MRL/MDL)

NIOSH National Institute for Occupational Safety and Health

NTU Nephelometric Turbidity Units

ppb Parts Per Billion**ppm** Parts Per Million

SM

PQL Practical Quantitation Limit
QA/QC Quality Assurance/Quality Control
RCRA Resource Conservation and Recovery Act

RPD Relative Percent Difference

SIM Selected Ion Monitoring

Glandard Methods for the Examination of Water and Wastewater, 18th Ed., 1992

STLC Solubility Threshold Limit Concentration

SW Test Methods for Evaluating Solid Waste, Physical/Chemical Methods, SW-846,

3rd Ed., 1986 and as amended by Updates I, II, IIA, and IIB.

TCLP Toxicity Characteristic Leaching Procedure

TDS Total Dissolved Solids

TPH Total Petroleum Hydrocarbons

tr Trace level. The concentration of an analyte that is less than the PQL but greater than or equal

to the MDL. If the value is equal to the PQL, the result is actually <PQL before rounding.

TRPH Total Recoverable Petroleum Hydrocarbons

TSS Total Suspended Solids

TTLC Total Threshold Limit Concentration

VOA Volatile Organic Analyte(s) ACRONLST.DOC 7/14/95

Analytical Report

Client:

ARCO Products Company

Project:

20805-123,004 TO#21133,00 2035 ALBANY

Date Collected: 11/3/97

Sample Matrix:

vater

Date Received: 11/4/97

Service Request: \$9702252

BTEX, MTBE and TPH as Gasoline

Sample Name:

MW-6(15)

Units: ug/L (ppb) Basis: NA

Lab Code:

S9702252-001

Test Notes:

Analyte	Prep Method	Analysis Method	MRL	Dilution Factor	Date Extracted	Date Analyzed	Result	Result Notes
TPH as Gasoline	EPA 5030	CA/LUFT	50	ĺ	NA	11/14/97	ND	
Benzene	EPA 5030	8020	0.5	1	NA	11/14/97	ND	
Toluene	EPA 5030	8020	0.5	1	NA	11/14/97	ND	
Ethylbenzene	EPA 5030	8020	0.5	1	NA	11/14/97	ND	
Xylenes, Total	EPA 5030	8020	0.5	1	NA	11/14/97	ND	
Methyl tert -Butyl Ether	EPA 5030	8020	3	1	NA	11/14/97	19	

Analytical Report

Client:

ARCO Products Company

Project:

20805-123.004/TO#21133.00/2035 ALBANY

Sample Matrix:

Water

Service Request: \$9702252

Date Collected: 11/3/97

Date Received: 11/4/97

BTEX, MTBE and TPH as Gasoline

Sample Name:

MW-2(28)

Lab Code:

89702252-002

Test Notes:

Units: ug/L (ppb) Basis: NA

Analyte	Prep Method	Analysis Method	MRL	Dilution Factor	Date Extracted	Date Analyzed	Result	Result Notes
TPH as Gasoline	EPA 5030	CA LUFT	50	1	NA	11/14/97	ND	
Benzene	EPA 5030	8020	0.5	I	NA	11/14/97	ND	
Toluene	EPA 5030	8020	0.5	1	NA	11/14/97	ND	
Ethylbenzene	EPA 5030	8020	0.5	1	NA	11/14/97	ND	
Xylenes, Total	EPA 5030	8020	0.5	1.	NA	11/14/97	ND	
Methyl tert -Butyl Ether	EPA 5030	8020	3	T	NA	11/14/97	18	

Analytical Report

Client:

ARCO Products Company

Project:

20805-123 004°TO+21133.00/2035 ALBANY

Sample Matrix:

Water

Service Request: 89702252

Date Collected: 11/3/97

Date Received: 11/4/97

BTEX, MTBE and TPH as Gasoline

Sample Name:

RW-1(11)

Units: ug/L (ppb)
Basis: NA

Lab Code:

S9702252-003

Test Notes:

Analyte	Prep Method	Analysis Method	MRL	Dilution Factor	Date Extracted	Date Analyzed	Result	Result Notes
TPH as Gasoline	EPA 5030	CA/LUFT	50	4	NA	11/14/97	<200	Cl
Benzene	EPA 5030	8020	0.5	4	NA	11/14/97	14	
Toluene	EPA 5030	8020	0.5	4	NA	11/14/97	19	
Ethylbenzene	EPA 5030	8020	0.5	4	NA	11/14/97	3	
Xylenes, Total	EPA 5030	8020	0.5	4	NA	11/14/97	19	
Methyl tert-Butyl Ether	EPA 5030	8020	3	4	NA	11/14/97	140	

C1

The MRL was elevated due to high analyte concentration requiring sample dilution.

1822/020597р

Analytical Report

Client:

ARCO Products Company

Project:

20805-123.004/TO#21133.00/2035 ALBANY

Sample Matrix:

Water

Service Request: S9702252

Date Collected: 11/3/97

Date Received: 11/4/97

BTEX, MTBE and TPH as Gasoline

Sample Name:

MW-1(28)

Lab Code:

S9702252-004

Test Notes:

Units: ug/L (ppb)

Basis: NA

Analyte	Prep Method	Analysis Method	MRL	Dilution Factor	Date Extracted	Date Analyzed	Result	Result Notes
TPH as Gasoline	EPA 5030	CA/LUFT	50	1	NA	11/14/97	83	
Benzene	EPA 5030	8020	0.5	1	NA	11/14/97	8.0	
Toluene	EPA 5030	8020	0.5	1	NA	11/14/97	ND	
Ethylbenzene	EPA 5030	8020	0.5	1	NA	11/14/97	ND	
Xylenes, Total	EPA 5030	8020	0.5	1	NA	11/14/97	ND	
Methyl tert-Butyl Ether	EPA 5030	8020	3	1	NA	11/14/97	13	

Analytical Report

Client:

ARCO Products Company

Project:

. 6805-123,004 TO+21133,00/2035 ALBANY

Date Collected: 11/3/97

Sample Matrix:

Mater

Date Received: 11/4/97

Service Request: S9702252

BTEX, MTBE and TPH as Gasoline

Sample Name:

MW-3(32)

Units: ug/L (ppb) Basis: NA

Lab Code:

S9702252-005

Test Notes:

Analyte	Prep Method	Analysis Method	MRL	Dilution Factor	Date Extracted	Date Analyzed	Result	Result Notes
TPH as Gasoline	EPA 5030	CA/LUFT	50	4	NA	11/14/97	<200	C1
Benzene	EPA 5030	8020	0.5	4	NA	11/14/97	<2	C1
Toluene	EPA 5030	8020	0.5	4	NA	11/14/97	<2	Cl
Ethylbenzene	EPA 5030	8020	0.5	4	NA	11/14/97	<2	C1
Xylenes, Total	EPA 5030	8020	0.5	4	NA	11/14/97	<2	Cl
Methyl tert -Butyl Ether	EPA 5030	8020	3	4	NA	11/14/97	130	

C1

The MRL was elevated due to high analyte concentration requiring sample dilution.

Analytical Report

Client:

ARCO Products Company

Project:

20805-123.004/TO#21133.00/2035 ALBANY

Service Request: S9702252 Date Collected: 11/3/97

Sample Matrix:

Water

Date Received: 11/4/97

BTEX, MTBE and TPH as Gasoline

Sample Name:

MW-4(12)

Units: ug/L (ppb)

Basis: NA

Lab Code:

S9702252-006

Test Notes:

Analyte	Prep Method	Analysis Method	MRL	Dilution Factor	Date Extracted	Date Analyzed	Result	Result Notes
TPH as Gasoline	EPA 5030	CALUFT	50	1	NA	11/14/97	ND	
Benzene	EPA 5030	8020	0.5	1	NA	11/14/97	ND	
Toluene	EPA 5030	8020	0.5	1	NA	11/14/97	ND	
Ethylbenzene	EPA 5030	8020	0.5	1	NA	11/14/97	ND	
Xylenes, Total	EPA 5030	8020	0.5	1	NA	11/14/97	ND	
Methyl tert-Butyl Ether	EPA 5030	8020	3	1	NA	11/14/97	ND	

Analytical Report

Client:

ARCO Products Company

Project:

2/1805-123.004 TO#21133.00.2035 ALBANY

Service Request: \$9702252 Date Collected: NA

Sample Matrix:

Water

Date Received: NA

BTEX, MTBE and TPH as Gasoline

Sample Name:

Method Blank

Units: ug/L (ppb)
Basis: NA

Lab Code:

S97H13-WB1

Test Notes:

Analyte	Prep Method	Analysis Method	MRL	Dilution Factor	Date Extracted	Date Analyzed	Result	Result Notes
TPH as Gasoline	EPA 5030	CA/LUFT	50	Į.	NA	11/13/97	ND	
Benzene	EPA 5030	8020	0.5	1	NA	11/13/97	ND	
Toluene	EPA 5030	8020	0.5	1	NA	11/13/97	ND	
Ethylbenzene	EPA 5030	8020	0.5	1	NA	11/13/97	ND	
Xylenes, Total	EPA 5030	8020	0.5	1	NA	11/13/97	ND	
Methyl tert -Butyl Ether	EPA 5030	8020	3	1	NA	11/13/97	ND	

APPENDIX A

QA/QC Report

Client:

ARCO Products Company

Service Request: S9702252

Project:

20805-123.004/TC#21133.00/2035 ALBANY

Date Collected: NA

Sample Matrix:

Water

Date Received: NA

Date Extracted: NA Date Analyzed: NA

Surrogate Recovery Summary BTEX, MTBE and TPH as Gasoline

Prep Method:

Analysis Method: 8020

EPA 5030

CA/LUFT

Units: PERCENT

Basis: NA

Sample Name	Lab Code	Test Notes	Percent 4-Bromofluorobenzene	Recovery a,a,a-Trifluorotoluene
MW-6(15)	S9702252-001		98	105
MW-2(28)	S9702252-002		100	99
RW-1(11)	S9702252-003		100	81
MW-1(28)	S9702252-004		97	101
MW-3(32)	89702252-005		105	80
MW-4(12)	S9702252-006		100	93
MW-6 (15)	S9702252-001MS		99	97
MW-6 (15)	S9702252-001DMS		99	98
Method Blank	8971113-WBI		100	99

CAS Acceptance Limits:

69-1**16**

69-116

QA/QC Report

Client:

ARCO Products Company

Project:

20805-123.004/TO#21133.00/2035 ALBANY

Sample Matrix:

Water

Service Request: S9702252

Date Collected: NA

Date Received: NA
Date Extracted: NA

Date Analyzed: 11/14/97

Matrix Spike/Duplicate Matrix Spike Summary

BTE

Sample Name:

MW-6 (15)

Units: ug/L (ppb)

Lab Code:

S9702252-001MS,

S9702252-001DMS

Basis: NA

Test Notes:

Percent Recovery

Analyte	Prep Method	Analysis Method	MRL	•	e Level DMS	Sample Result	Spike MS	Result DMS	MS	DMS	CAS Acceptance Limits	Relative Percent Difference
Benzene	UPA 5030	8020	0.5	25	25	ND	23	24	92	96	75-135	4
Toluene	EPA 5030	8020	0.5	25	25	ND	23	22	92	88	73-136	4
Ethylbenzene	EPA 5030	8020	0.5	25	25	ND	23	22	92	88	69-142	4

QA/QC Report

Client:

-RCO Products Company

Project: 20805-123.004 TO#21133.00/2035 ALBANY Service Request: S9702252

Date Analyzed: 11/13/97

Initial Calibration Verification (ICV) Summary BTEX, MTBE and TPH as Gasoline

Sample Name;

 ICV

Units: ug/L (ppb)

Lab Code:

 $\{CV\}$

Basis: NA

Test Notes:

ICV Source:					CAS Percent Recovery		
Analyte	Prep Method	Analysis Method	True Value	Result	Acceptance Limits	Percent Recovery	Result Notes
TPH as Gasoline	EPA 5030	CALUTT	250	260	90-110	104	
Benzene	EPA 5030	8020	25	26	85-115	104	
Toluene	EPA 5030	8020	25	26	85-115	104	
Ethylhenzene	EPA 5030	8020	25	26	85-115	104	
Xylenes, Total	EPA 5030	8020	75	79	85-115	105	
Methyl tert-Butyl Ether	EPA 5030	8020	25	26	85-115	104	

ICV/032196

ARCO Products Company Division of Atlantic/Richfield Company	Task Order	No. 21/33.00 Ch	ain of Custody
ARCO Facility no. 2035 City (Facility)	Pany	(Consultant) Paul Supple Can Musserofes	Laboratory Name
ARCO engineer Paul Sunnie	Telephone no. (ARCO)	Telephone no (40%) 453 - 7300 Fax no. (Consultant) (40%) 453 - 04	45Z Contract Number
Consultant name EMCN	Address (Consultant)	121 Ringwood Ave Son has CA 95131	
Matrix Pre	servation	D12	Method of shipment
Soil Water Other Ice	Acid #	20 10 20 13.2 D 13.2 D 13.2 D 10 10 10 10 10 10 10 10 10 10	Sampler Will deliver
Soil Water Other Ice	Acid date date Sampling date	BTEX 602/EPA 8020 BTEX/TPH in cdc, MTE EPA M602/ED200615 Gas D Desel C Oil and Grease 413.1 D 413.2 C TPH EPA 418.1/SM 503/E EPA 624/8240 EPA 624/8240 CAM Metals EPA 6010/7000 CAM Metals EPA 6010/7000 TLCD Semi MetalsC YOACI VOACI CAM Metals EPA 6010/7000 TLCC Lead GPA 7420/7421C Lead EPA 7420/7421C	
MW-6(4) 1 Z X X	HO 1/3/97 11:20	\sim	Special Detection Limit/reporting
MW-7(28)27 × ×	HCL 11155		Lowest Possible
$2W-1(VI)^3$ $2\times$	I+CL 13:05	×	- Possible
4W-1G8)4 2 × ×	IXCL 13:52	\times	Special QA/QC
1W3(4)5 2 × ×	140 17:40	\times	As Normal
M1-4(12)6 2 X X	14CL \$ 15:00	\times	Normal
			Remarks
			Z-40m1Ha
			Z-40m1Ha VOAs
			#20405 - 173 . C
			59702252
			Turnaround Time;
			Priority Rush 1 Business Day ☐
			Rush 2 Business Days ☐
Condition of sample:		Temperature received:	Expedited
Relinguished by sampler	Date Time	Received by	5 Business Days
Relinguished by		Received by	Standard 10 Business Days
Relinguished by	Date Time	Acceived by lattoratory and OS Date 4/97 Time 1555	

APPENDIX B SVE SYSTEM MONITORING DATA LOG SHEETS

	F	eld Moni	toring Da	ala]	Laboratory Monitoring Data									1					
Flow	Rates	FID	or PID R	esults		1	Well Field Influent		System	Influent	System Effluent					1					
Well Field Flow Rate	System influent Flow Rate	Well Field	System influent	System Effluent	Destruction Efficiency	Laboratory Sample Time	Gasoline	Benzene	Gasoline	Benzene	Gasoline	Benzene	Destruction Efficiency	Sasoline Emission Rate	senzene Emission Rate	eriod Hours	Aeter Hours	lours of Operation	lays of Operation	own Hours	Down Days
scfm	scfm	ppm	ppm	ppm	%		ppmv mg/m3	ppmv mg/m3	ppmv mg/m3	opmv mg/m3	ppmv mg/m3	ppmv mg/m3	%	ib/day							
	I															516.08 227.92	11146.50 11146.50 11146.50	0.00			2.
																744.00		0.00	0.00	744.00	3
	Well Field Flow Rate	Flow Rates Well Field Flow Hate System influent Flow Bate Sctm Sctm O.0	Flow Rates FID of Plant	Field Monitoring D. Flow Rates FID or PID R The Half Field How Hate The Hate The Half Field How Hate The Half Field How Hate The Half Field How Hate The Ha	Days in Period: Field Monitoring Data Flow Rates FID or PID Results Flow Rates FID or PID Results Flow Hates Figure Hullow Hate Field How Hate Field How Hate Figure Hate Figure Hate Figure Figur	Days in Period: 31.00 Field Monitoring Data Flow Rates FID or PID Results Flow Hates Fide How Hate Light How	Field Monitoring Data Flow Rates Field Library Rate Field Library Rate Field Library Rate Field Flow Hate Field Flow Rate Fl	Days in Period: 31.00 Field Monitoring Data Flow Rates FID or PID Results Well Field Light Monitoring Data Flow Rates FID or PID Results Well Field Light Monitoring Data Gasoline Gasoline October Monitoring Data Well Field Light Monitoring Data Well Field Light Monitoring Data Gasoline Gasoline October Monitoring Data Well Field Monitoring Data Well Field Light Monitoring Data Well Field Light Monitoring Data Figure Monitoring Data October Monitoring Data Well Field Light Monitoring Data Figure Monitoring Data October Monitoring Data October Monitoring Data October Monitoring Data Well Field Monitoring Data October Monitoring Data Octob	Days in Period: 31.00 Field Monitoring Data Flow Rates FID or PID Results Well Field Influent Well Field Influent Flow Rates FID or PID Results Well Field Influent Gasoline Benzene Benzene Gasoline Scfm scfm ppm ppm ppm ppm % ppmv mg/m3 ppmv mg/m3 ppmv mg/m3 ppmv mg/m3	Days in Period: 31.00 Operation + Down Days: 31.00 Field Monitoring Data Flow Rates FID or PID Results Well Field Influent System Well Field Influent System Well Field Influent Gasoline Gasoline Benzene Gasoline Gasoline Scfm scfm ppm ppm ppm ppm ppm 9 ppm ppm ppm ppm	Plays in Period: 31.00 Field Monitoring Data	Plays in Period: 31.00 Operation + Down Days:	Field Monitoring Data Flow Rates FID or PID Results Well Field Influent System Influent System Effluent Benzene Gasoline Ben	Field Monitoring Data Flow Rates FID or PID Results Well Field Influent System Influent System Effluent Benzene Gasoline Ben	Plays in Period: 31.00 Operation + Down Days: 31.00 Field Monitoring Data	Plays in Period: 31.00 Operation + Down Days: 31.00 Field Monitoring Data	Page Page	Page Period: 31.00 Operation + Down Days: 31.00 Operation + Down Days: 31.00	Pays in Period: 31.00 Operation + Down Days: 31.00	Days in Period: 31.00 Operation + Down Days: 31.00 Opera	Days in Period: 31.00 Operation + Down Days: 31.00

eporting Period: 11/01/97 00:00 12/01/97 00:00	Hours in Period: 720.00 Operation + Down Hours: 720.00 Days in Period: 30.00 Operation + Down Days: 30.00																											
[F]			•				Laboratory M	onitorin	g Data							1					
ļ	Flow	Rales	FID	or PID Re	sults	ļ	-	ļ	Well Fiel	d Influen	t		System	Influent			System	Effluent										
Reading Date & Time	Well Field Flow Rate	System Influent Flow Rate	Well Field	System Influent	System Effluent	Destruction Efficiency	Laboratory Sample Time	Gas	oline	Ben	zene	Gas	oline	Benzena		Gaso	oline	Ben:	zenė	Destruction Efficiency	Gasoline Emission Rate	Benzene Emission Rate	Period Hours	Meter Hours	Hours of Operation	Days of Operation	Down Hours	Down Days
	scim	scfm	ppm	ppm	ppm	%		ppmv	mg/m3	ppmv	mg/m3	ppmv	mg/m3	ррти тд	/m3 p	рти	mg/m3	ppmv	mg/m3	%	lb/day	lb/day						
11/01/97 00:00	(40.7			204			40.00		646		_	400												11146.50	-			
11/05/97 10:32 11/19/97 12:30	118.7 118.4	221.4 221.4		294 12.2			12:00	160	640	0.6	2	160	640	0.6	2	8	34	<0.1	<0.4	94.7	0.68	NA		11146.50	0.00	0.00	106.53	
12/01/97 00:00	0.0	0.0		12.2													ļ						337.97 275.50	11484.08 11484.36	337.58 0.28	14,07 0.01	0.39 275.22	0. 11.
Period Totals:							1					I			- 1			1					720.00		337.86	14.08	382.14	15

od: 00 Hours in Period: 744.00 Operation + Down Hours: 744.00 00 Days in Period: 31.00 Operation + Down Days: 31.00																					
	F	ield Moni	itoring Da	ata	_	}				Laboratory Monito	ring Data					1					
Flow	Rates	FID o	or PID Re	esults			Well Fiel	ld Influent	System	Influent	System	Effluent]					
Well Field Flow Rate	System Influent Flow Rate	Well Field	System Influent	System Effluent	Destruction Efficiency	Laboratory Sample Time	Gasoline	Benzene	Gasoline	Benzene	Gasoline	Benzene	Destruction Efficiency	Gasoline Emission Rate	Benzene Emission Rate	Period Hours	Weter Hours	Hours of Operation	Days of Operation	Jown Hours	Down Days
scim	scim	ppm	ppm	ppm	%		ppmv mg/m3	ppmv mg/m3	ppmv mg/m3	ppmv mg/m3	ppmv mg/m3	ppmv mg/m3	%	lb/day	lb/day				_		_ <u>=</u>
0.0	0.0 0.0															348.50 395.50	11484.36 11484.43 11484.43	0.07	0.00 0.00	348.43 395.50	14. 16.
																744.00		0.07	0.00	743.93	31.
	Well Field Flow Rate	Flow Rate Rate Co. System Influent Flow Rate Co. System Influent Flow Rate Co.	Flow Rates FID Melt Liefd Flow Rate System Influent Flow Rate System Field Melt Field Flow Rate Co. O.O.	Field Monitoring Dispersion of the Liel of Monitoring Dispersion of the Lie of Monitoring D	Days in Period: Field Monitoring Data Flow Rates FID or PID Results Flow Rates FID or PID Results A Stem Field Monitoring Data Flow Rates FID or PID Results A Stem Field Monitoring Data Flow Rates FID or PID Results A Stem Field Monitoring Data Flow Rates FID or PID Results A Stem Field Monitoring Data Flow Rates FID or PID Results Flow Rates FID or PID Results A Stem Field Monitoring Data Flow Rates FID or PID Results Flow Rates FID or PID Resul	Days in Period: 31.00 Field Monitoring Data Flow Rates FID or PID Results Plow Bate Field Hold Flow Bate Flow Rates FID or PID Results A State Field Hold Flow Bate Flow Rates FID or PID Results A State Field Monitoring Data Flow Rates FID or PID Results A State Field Monitoring Data Flow Rates FID or PID Results A State Field Monitoring Data Flow Rates FID or PID Results A State Field Monitoring Data Flow Rates FID or PID Results A State Field Monitoring Data Flow Rates FID or PID Results A State Field Monitoring Data Flow Rates FID or PID Results A State Field Monitoring Data Flow Rates FID or PID Results A State Field Monitoring Data Flow Rates FID or PID Results A State Field Monitoring Data Flow Rates FID or PID Results A State Field Monitoring Data Flow Rates FID or PID Results A State Field Monitoring Data Flow Rates FID or PID Results A State Field Monitoring Data Flow Rates FID or PID Results A State Field Monitoring Data Flow Rates FID or PID Results A State Field Monitoring Data Flow Rates Fill Or PID Results A State Field Monitoring Data Flow Rates Fill Or PID Results A State Fill O	Days in Period: 31.00 Field Monitoring Data Flow Rates FID or PID Results Flow Rate Field Light Ligh	Field Monitoring Data Flow Rates FID or PID Results Well Field Light L	Field Monitoring Data Flow Rates FID or PID Results Well Field Influent Flow Rates FID or PID Results Well Field Influent Flow Rates FID or PID Results Benzene Gasoline Benzene Gasoline Benzene Scfm scfm ppm ppm ppm % ppmv mg/m3 ppmv mg/m3 ppmv mg/m3 ppmv mg/m3	Pied Monitoring Data Field Monitoring Data Flow Rates FID or PID Results Well Field Influent System Well Field Influent Gasoline Gasoline Gasoline Gasoline Gasoline Gasoline Gasoline Flow Rates FID or PID Results Well Field Influent Gasoline Gasoline Gasoline Gasoline Flow Rates FID or PID Results Flow Rates FID or PID Results Gasoline Gasoline Gasoline Flow Rates FID or PID Results Flow Rates FID or PID Results Flow Rates FID or PID Results Gasoline Gasoline Flow Rates FID or PID Results Gasoline Gasoline Flow Rates FID or PID Results Flow Rates FID or	Field Monitoring Data Filed Monitoring Data Flow Rates Floor PID Results Well Field Influent System Influent Gasoline Benzene Gasoline Benzene	Field Monitoring Data Filed Monitoring Data Flow Rates Flow Rates Flow Part Part Part Part Part Part Part Part	Field Monitoring Data Flow Rates FID or PID Results Well Field Influent System Influent System Influent System Effluent Well Field Influent Gasoline Benzene Gasoline Benzene Gasoline Benzene Benzene Gasoline Benzene Gasoline Benzene Gasoline Benzene Gasoline Benzene Gasoline Benzene Sctm scfm ppm ppm ppm ppm % ppmv mg/m3 p	Field Monitoring Data Flow Rates Flow Rates Flow PiD Results Well Field Influent Well Field Influent System Influent System Influent Gasoline Benzene Gasoline Benzene	Field Monitoring Data Flow Rates Flow Rates Flow PiD Results Flow Rates Flow Rates Flow Rates Flow Rates Flow Rates Flow PiD Results Flow Rates Flow Ra	Field Monitoring Data Flow Rates Flow Ra	Page Page	Days in Period: 31.00 Operation + Down Days: 31.00	Days in Period: 31.00 Operation + Down Days: 31.00	Days in Period: 31.00 Operation + Down Days: 31.00 Operation + Operation	Days in Period: 31.00 Operation + Down Days: 31.00

APPENDIX C

ANALYTICAL RESULTS AND CHAIN-OF-CUSTODY DOCUMENTATION FOR SVE SYSTEM, FOURTH QUARTER 1997



November 18, 1997

Service Request No.: S9702267

Valli Voruganti **EMCON** 1921 Ringwood Avenue San Jose, CA 95131

RE: 20805-123.004/TO#20815.00/2035 ALBANY

Dear Ms. Voruganti:

The following pages contain analytical results for sample(s) received by the laboratory on November 5, 1997. Results of sample analyses are followed by Appendix A which contains sample custody documentation and quality assurance deliverables requested for this project. The work requested has been assigned the Service Request No. listed above. To help expedite our service, please refer to this number when contacting the laboratory.

Analytical results were produced by procedures consistent with Columbia Analytical Services' (CAS) Quality Assurance Manual (with any deviations noted). Signature of this CAS Analytical Report below confirms that pages 2 through 12, following, have been thoroughly reviewed and approved for release in accord with CAS Standard Operating Procedure ADM-DatRev3.

Please feel welcome to contact me should you have questions or further needs.

Sincerely,

Project Chemist

Greg Anderson

Regional QA Coordinator

Cuietina V. Raybur for

Acronyms

A2LA American Association for Laboratory Accreditation

ASTM American Society for Testing and Materials

BOD Biochemical Oxygen Demand

BTEX Benzene, Toluene, Ethylbenzene, Xylenes

CAM California Assessment Metals
CARB California Air Resources Board

CAS Number Chemical Abstract Service registry Number

CFC Chlorofluorocarbon
CFU Colony-Forming Unit
COD Chemical Oxygen Demand

DEC Department of Environmental Conservation
DEQ Department of Environmental Quality
DHS Department of Health Services
DLCS Duplicate Laboratory Control Sample

DMS Duplicate Matrix Spike
DOE Department of Ecology
DOH Department of Health

EPA U. S. Environmental Protection Agency

ELAP Environmental Laboratory Accreditation Program

GC Gas Chromatography

GC/MS Gas Chromatography/Mass Spectrometry

IC Ion Chromatography

ICB Initial Calibration Blank sample

Inductively Coupled Plasma atomic emission spectrometry

ICV Initial Calibration Verification sample

J Estimated concentration. The value is less than the MRL, but greater than or equal to

the MDL. If the value is equal to the MRL, the result is actually <MRL before rounding.

LUFT Leaking Underground Fuel Tank

M Modified

MBAS Methylene Blue Active Substances

MCL Maximum Contaminant Level. The highest permissible concentration of a

substance allowed in drinking water as established by the U. S. EPA.

MDL Method Detection Limit
MPN Most Probable Number
MRL Method Reporting Limit

MS Matrix Spike

MTBE Methyl tert-Butyl Ether

NA Not Applicable
NAN Not Analyzed
NC Not Calculated

NCASI National Council of the paper industry for Air and Stream Improvement
ND Not Detected at or above the method reporting/detection limit (MRL/MDL)

NIOSH National Institute for Occupational Safety and Health

NTU Nephelometric Turbidity Units

ppb Parts Per Billion ppm Parts Per Million

PQL Practical Quantitation Limit
QA/QC Quality Assurance/Quality Control

RCRA Resource Conservation and Recovery Act

RPD Relative Percent Difference SIM Selected Ion Monitoring

SM Standard Methods for the Examination of Water and Wastewater, 18th Ed., 1992

STLC Solubility Threshold Limit Concentration

SW Test Methods for Evaluating Solid Waste, Physical/Chemical Methods, SW-846,

3rd Ed., 1986 and as amended by Updates I, II, IIA, and IIB.

TCLP Toxicity Characteristic Leaching Procedure

TDS Total Dissolved Solids

TPH Total Petroleum Hydrocarbons

tr Trace level. The concentration of an analyte that is less than the PQL but greater than or equal

to the MDL. If the value is equal to the PQL, the result is actually <PQL before rounding.

TRPH Total Recoverable Petroleum Hydrocarbons

TSS Total Suspended Solids

TTLC Total Threshold Limit Concentration

VOA Volatile Organic Analyte(s) ACRONLST.DOC 7/14/95

Analytical Report

Client:

ARCO Products Company

Project:

20805-123.004/TO#20815.00/2035 ALBANY

Sample Matrix:

Air

Service Request: \$9702267

Date Collected: 11/5/97

Date Received: 11/5/97

BTEX and Total Volatile Hydrocarbons

Sample Name:

I-1

Units: mg/m3 Basis: NA

Lab Code:

S9702267-001

Test Notes:

Analyte	Prep Method	Analysis Method	MRL	Dilution Factor	Date Extracted	Date Analyzed	Result	Result Notes
Benzene	5030	8020	0.4	1	NA	11/7/97	2.0	
Toluene	5030	8020	0.4	1	NA	11/7/97	ND	
Ethylbenzene	5030	8020	0.5	ı	NA	11/7/97	7.0	
Xylenes, Total	5030	8020	0.9	1	NA	11/7/97	11	
Total Volatile Hydrocarbons:								
C1 - C5	5030	8015M	12	1	NA	11/7/97	230	
C6 - C12	5030	8015M	20	1	NA	11/7/97	640	
TPH as Gasoline*	5030	8015M	20	1	NA	11/7/97	640	

TPH as gasoline is defined as C6 (benzene) through C12 (dodecane) and uses a molecular weight of 100 to calculate the ppmv.

Analytical Report

Client:

ARCO Products Company

Project:

20805-123.004/TO#20815.00/2035 ALBANY

Sample Matrix:

Аіг

Service Request: \$9702267

Date Collected: 11/5/97

Date Received: 11/5/97

BTEX and Total Volatile Hydrocarbons

Sample Name:

I-1

Units: ppmV

Lab Code:

S9702267-001

Basis: NA

Test Notes:

Analyte	Prep Method	Analysis Method	MRL	Dilution Factor	Date Extracted	Date Analyzed	Result	Result Notes
Benzene	5030	8020	0.1	1	NA	11/7/97	0.6	
Toluene	5030	8020	0.1	1	NA	11/7/97	ND	
Ethylbenzene	5030	8020	0.1	1	NA	11/7/97	1.6	
Xylenes, Total	5030	8020	0.2	1	NA	11/7/97	2.5	
Total Volatile Hydrocarbons:								
C1 - C5	5030	8015M	5	1	NA	11/7/97	97	
C6 - C12	5030	8015M	5	1	NA	11/7/97	160	
TPH as Gasoline*	5030	8015M	5	1	NA	11/7/97	160	

TPH as gasoline is defined as C6 (benzene) through C12 (dodecane) and uses a molecular weight of 100 to calculate the ppmv.

Analytical Report

Client:

ARCO Products Company

Project:

20805-123.004/TO#20815.00/2035 ALBANY

Sample Matrix:

Air

Service Request: \$9702267 Date Collected: 11/5/97

Date Received: 11/5/97

BTEX and Total Volatile Hydrocarbons

Sample Name:

E-1

Lab Code: Test Notes:

S9702267-002

Units: mg/m3

Basis: NA

Analyte	Prep Method	Analysis Method	MRL	Dilution Factor	Date Extracted	Date Analyzed	Result	Result Notes
Benzene	5030	8020	0.4	1	NA	11/7/97	ND	
Toluene	5030	8020	0.4	1	NA	11/7/97	0.5	
Ethylbenzene	5030	8020	0.5	1	NA	11/7/97	ND	
Xylenes, Total	5030	8020	0.9	1	NA	11/7/97	1.5	
Total Volatile Hydrocarbons:								
C1 - C5	5030	8015M	12	1	NA	11/7/97	ND	
C6 - C12	5030	8015M	20	1	NA	11/7/97	34	
TPH as Gasoline*	5030	8015M	20	1	NA	11/7/97	34	

TPH as gasoline is defined as C6 (benzene) through C12 (dodecane) and uses a molecular weight of 100 to calculate the ppmv.

Analytical Report

Client:

ARCO Products Company

Project:

20805-123.004/TO#20815.00/2035 ALBANY

Sample Matrix:

Air

Service Request: S9702267 Date Collected: 11/5/97

11/7/97

11/7/97

0.3

8

Date Received: 11/5/97

BTEX and Total Volatile Hydrocarbons

Sample Name:

E-1

Lab Code: Test Notes:

Xylenes, Total

TPH as Gasoline*

5030

5030

S9702267-002

Units: ppmV Basis: NA

Dilution Result Prep Analysis Date Date Notes Analyte Method Method MRL Factor Extracted Analyzed Result ND 5030 8020 1 NA 11/7/97 Benzene 0.1 8020 0.1 1 NA 11/7/97 0.1 Toluene 5030 5030 8020 0.1 1 NA 11/7/97 ND Ethylbenzene

0.2

5

1

1

NA

NA

Total Volatile Hydrocarbons: ND 11/7/97 C1 - C5 5030 8015M 5 1 NA C6-C12 5030 8015M 5 1 NA 11/7/97 8

8020

8015M

TPH as gasoline is defined as C6 (benzene) through C12 (dodecane) and uses a molecular weight of 100 to calculate the ppmv.

1822/020597p

Analytical Report

Client:

ARCO Products Company

Project:

20805-123.004/TO#20815.00/2035 ALBANY

Sample Matrix:

Air

Service Request: S9702267

Date Collected: NA

Date Received: NA

BTEX and Total Volatile Hydrocarbons

Sample Name:

Method Blank

Lab Code:

S971106-VB1

Units: mg/m3 Basis: NA

Test Notes:

Analyte	Prep Method	Analysis Method	MRL	Dilution Factor	Date Extracted	Date Analyzed	Result	Result Notes
Benzene	5030	8020	0.4	1	NA	11/6/97	ND	
Toluene	5030	8020	0.4	1	NA	11/6/97	ND	
Ethylbenzene	5030	8020	0.5	1	NA	11/6/97	ND	
Xylenes, Total	5030	8020	0.9	1	NA	11/6/97	ND	
Total Volatile Hydrocarbons:								
C1 - C5	5030	8015M	12	1	NA	11/6/97	ND	
C6 - C12	5030	8015M	20	1	NA	11/6/97	ND	
TPH as Gasoline*	5030	8015M	20	1	NA	11/6/97	ND	

TPH as gasoline is defined as C6 (benzene) through C12 (dodecane) and uses a molecular weight of 100 to calculate the ppmv.

Analytical Report

Client:

ARCO Products Company

Project:

20805-123.004/TO#20815.00/2035 ALBANY

Sample Matrix:

Air

Service Request: \$9702267

Date Collected: NA
Date Received: NA

BTEX and Total Volatile Hydrocarbons

Sample Name:

Method Blank

Lab Code:

S971106-VB1

Test Notes:

Units: ppmV Basis: NA

Analyte	Prep Method	Analysis Method	MRL	Dilution Factor	Date Extracted	Date Analyzed	Result	Result Notes
Benzene	5030	8020	0.1	1	NA	11/6/97	ND	
Toluene	5030	8020	0.1	1	NA	11/6/97	ND	
Ethylbenzene	5030	8020	0.1	1	NA	11/6/97	ND	
Xylenes, Total	5030	8020	0.2	1	NA	11/6/97	ND	
Total Volatile Hydrocarbons:								
C1 - C5	5030	8015M	5	1	NA	11/6/97	ND	
C6 - C12	5030	8015M	5	1	NA	11/6/97	ND	
TPH as Gasoline*	5030	8015M	5	1	NA	11/6/97	ND	

TPH as gasoline is defined as C6 (benzene) through C12 (dodecane) and uses a molecular weight of 100 to calculate the ppmv.

APPENDIX A

QA/QC Report

Client:

ARCO Products Company

Project:

20805-123.004/TO#20815.00/2035 ALBANY

Sample Matrix: Air

Service Request: S9702267

Date Collected: NA
Date Received: NA

Date Extracted: NA
Date Analyzed: 11/7/97

Duplicate Summary BTEX and Total Volatile Hydrocarbons

Sample Name:

I-1

Lab Code:

S9702267-001DUP

Test Notes:

Units: mg/m3 Basis: NA

Analyte	Prep Method	Analysis Method	MRL	Sample Result	Duplicate Sample Result	Average	Relative Percent Difference	Result Notes
Benzene	5030	8020	0.4	2.0	1.7	1.7	16	
Toluene	5030	8020	0.4	ND	ND	ND	<1	
Ethylbenzene	5030	8020	0.5	7.0	7.0	7.0	<1	
Xylenes, Total	5030	8020	0.9	11	11	11	<1	
Total Volatile Hydrocarbons								
C1 - C5	5030	8015M	12	230	230	230	<1	
C6 - C12	5030	8015M	20	640	660	650	3	
TPH as Gasoline*	5030	8015M	20	640	660	650	3	

QA/QC Report

Client:

ARCO Products Company

Project:

20805-123.004/TO#20815.00/2035 ALBANY

Sample Matrix: Air

Service Request: S9702267

Date Collected: NA

Date Received: NA
Date Extracted: NA
Date Analyzed: 11/7/97

Duplicate Summary BTEX and Total Volatile Hydrocarbons

Sample Name:

I-1

Lab Code:

S9702267-001DUP

Test Notes:

Units: ppmV Basis: NA

Analyte	Prep Method	Analysis Method	MRL	Sample Result	Duplicate Sample Result	Average	Relative Percent Difference	Result Notes
Benzene	5030	8020	0.1	0.6	0.5	0.6	17	
Toluene	5030	8020	0.1	ND	ND	ND	ND	
Ethylbenzene	5030	8020	0.1	1.6	1.6	1.6	<1	
Xylenes, Total	5030	8020	0.2	2.5	2.5	2.5	<1	
Total Volatile Hydrocarbons								
C1 - C5	5030	8015M	5	97	97	97	<1	
C6 - C12	5030	8015M	5	160	160	160	<1	
TPH as Gasoline*	5030	8015M	5	160	160	160	<1	

QA/QC Report

Client:

ARCO Products Company

Project: 20

20805-123.004/TO#20815.00/2035 ALBANY

Service Request: S9702267

Date Analyzed: 11/6/97

Initial Calibration Verification (ICV) Summary BTEX and Total Volatile Hydrocarbons

Sample Name:

ICV ICV1 Units: mg/m3

Lab Code: Test Notes:

Basis: NA

ICV Source:

Analyte	Prep Method	Analysis Method	True Value	Result	Percent Recovery	CAS Acceptance Limits
Benzene	5030	8020	25	28	112	80-120
Toluene	5030	8020	25	28	112	80-120
Ethylbenzene	5030	8020	25	28	112	80-120
Xylenes, Total	5030	8020	75	86	115	80-120
Gasoline	5030	8015M	250	260	104	80-120

ICV/032196

TPHNOA F

							Task Order i	er No. 20815.00 Project manager (Consultant) V V V C v c n + . Telephone no. (Consultant) (Consultant)											Ch	ain	of Custody			
ARCO Fa	cility no	20	031	5	City (Facility) A1	Bren	V		Proj (Co	ject ma nsultar	anager nt)	1.	/ · L	101	~ V C	101	$n \downarrow$	^					Laboratory Name
ARCO en	gineer	7	avl		$S \cup P_{\ell}$	PIC	Tele (AR	phone no. (CO)		Tele (Co	phone nsultar	no. nt)					Fax (Con	no. Isultan	t)					Contract Number
Consultan	t name		Em	1001	1	,		1 7100	dress ensultant)								' 		<u></u>			;		
				Matrix		Prese	rvation				5							8	10/7000	4210				Method of shipment
Sample I.D.	Lab no.	Container no	Soil	Water	Other	łce	Acid	Sampling date	Sampling time	BTEX 602/EPA 8020	BTEX/TPH EPA M602/8020/80	TPH Modified 8015 Gas □ Diesel □	Oil and Grease 413.1 ☐ 413.2 ☐	TPH EPA 418.1/SM 5036	EPA 601/8010	EPA 624/8240	EPA 625/8270	TCLP Semi Metals⊡ VOA⊡ V	CAM Metals EPA 60	Lead Org/DHS□ Lead EPA 7420/7421□				Tech Special Detection
T-1	1				AIR			11/5	1210		$ \mathcal{N} $													Limit/reporting
巨-1	2				AIR	-		"15	1200		X	,												Report in PPMV mg/m3
																	-			_	Special QA/QC			
																								Remarks
																								Lab Number 59702267
																								Turnaround Time:
	-																							Priority Rush 1 Business Day ☐
·					•																		- 31.11	Rush 2 Business Days 🔲
						Temperature received:										Expedited 5 Business Days								
Relinguished by sampler Date Date Time 115/97/144C Relinguished by Date Time					Time Received by Time Received by							Standard 10 Business Days												