

April 30, 1993

Ms. Jennifer Eberle Hazardous Materials Specialist Alameda County Health Care Services Agency 80 Swan Way, Room 200 Oakland, CA 94621

1287

Subject:

First Quarter 1993

Groundwater Monitoring Report & Subsurface Investigation

Dreyer's Grand Ice Cream

5929 College Avenue, Oakland, California

(Project No. 919313)

Dear Ms. Eberle:

Aqua Terra Technologies, Inc. (ATT) is pleased to present the results for groundwater monitoring activities conducted by ATT during the first quarter, 1993 (January 1 through March 31, 1993) for the subject site. Monitoring activities during the first quarter included monthly recording of groundwater level measurements, groundwater sample collection, and laboratory sample analysis.

This report also summarizes activities associated with the subsurface investigation performed by ATT at the subject site during the first quarter 1993. The investigation was performed to comply with the requirements of the Alameda County Health Care Services Agency (ACHCSA) in their letter dated March 27, 1992. The work was performed in accordance with the June 18, 1992 ATT Workplan approved by the ACHCSA, and subsequent telephone conversations and written correspondence. The investigation included soil borings using Powercore equipment, collection of soil and grab groundwater samples, and laboratory sample analysis. The results of the routine quarterly monitoring and the subsurface investigation are presented below.

INTRODUCTION

The subject site is located in the city of Oakland, California, approximately 0.25 miles north of California Highway 24 and approximately 0.25 miles south of the Berkeley City limits (Plate 1, Attachment A). The property is bounded by Claremont Avenue to the northwest, College Avenue to the east, and Chabot Road to the south.

Aqua Terra Technologics Consulting Engineers & Scientists

2950 Buskirk Avenue Suite 120 Walnut Creek, CA 94596-2079 FAX 934-0418 510 934-4884 PCL-13.5 NO M $U(\tilde{V})$ V 9 2-19.51 AND STATE OF THE 3-14 MO 100 1015 N 0 6.4 ω 0110 4-12 ND 1000 100 ND NO 7-9.5 $\sim N \odot$ 8-9.5 1.1 CM 93 01 7.6 9-9,5 ON

= discolored soil and/or odors bet 14-18 bgs

.

ALAMEDA COUNTY HEALTH CARE SERVICES AGENCY



DAVID J. KEARS, Agency Director

RAFAT A. SHAHID, ASST. AGENCY DIRECTOR

DEPARTMENT OF ENVIRONMENTAL HEALTH
State Water Resources Control Board
Division of Clean Water Programs
UST Local Oversight Program
80 Swan Way, Rm 200
Oakland, CA 94621
(510) 271-4530

April 29, 1993 STID 1585

Alice, Edward, and May Lim c/o Russell Lim 601 Brush St. Oakland CA 94607

RE: Former Exxon Station

250-8th St.

Oakland CA 94607

Dear Lim Family,

As you know, overexcavation of affected soils and confirmatory soil sampling was conducted in my presence on 2/3/93. Preliminary laboratory results were faxed to me on 2/11/93 and 2/15/93 by your consultant, All Environmental, Inc. On 2/16/93, permission was given by Tom Peacock of this office to backfill the excavation.


A report summarizing the overexcavation and resampling work needs to be submitted to this office. This report should contain documentation for the offhaul of soil, as well as original laboratory reports, chains-of-custody, a map with sampling locations, and a narrative description of field activities. Please submit this report within 45 days or by June 13, 1993.

In addition, we request a workplan for a groundwater investigation, which would include at least 3 groundwater monitoring wells. Please submit this workplan within 45 days or by June 13, 1993.

All work should adhere to a) the Tri-Regional Board Staff
Recommendations for Preliminary Evaluation and Investigation of
Underground Tank Sites, dated 8/10/90; b) the State WAter
Resources Control Board LUFT Field Manual; and c) Article 11 of
Title 23, California Code of Regulations. Reports and proposals
must be submitted under seal of a California-Registered
Geologist, -Certified Engineering Geologist, or -Registered Civil
Engineer. All reports and documents pertaining to this
investigation should also be sent to:

Rich Hiett San Francisco Bay Region Regional Water Quality Control Board 2101 Webster St., Ste 500 Oakland CA 94612

grab water
gas die BTEX
NO ---PCI no water 3 ND---no water no water 8 ND --



One 1,000-gallon and one 8,000-gallon gasoline tank, two 4,000-gallon diesel tanks and one 2,000-gallon diesel tank were removed from the southeast corner of the property during December, 1989 (before construction of the current office building at the site). Two 1,000-gallon waste oil tanks were also removed from the southwest portions of the property in December, 1989.

The approximate locations of the former underground tank excavations are shown on Plate 2.

QUARTERLY GROUNDWATER MONITORING

Groundwater Elevations and Flow Direction

Groundwater level measurements were recorded on January 18, February 10, and March 10, 1993. Groundwater elevation contours and flow directions for the monitoring events above are shown on Plates 2, 3, and 4, Attachment A. Historic groundwater elevations are summarized in Table 1 (Attachment B).

During the first quarter 1993, groundwater table elevations ranged from approximately 174.49 feet above mean sea level (msl) to 181.29 feet above msl. Groundwater gradients ranged from 0.015 feet per foot (ft/ft) to 0.022 ft/ft. Groundwater flow direction was predominantly towards the southeast. Groundwater flow directions ranged from southwest and west, to northwest during the two preceding quarters (3rd and 4th quarter, 1992).

Groundwater Sample Collection & Analytical Methods

On March 10, 1993 ATT field personnel collected a set of groundwater samples from monitoring wells MW1, MW2, and MW3. The samples were transported with ATT chain-of-custody documentation to a California Department of Health Services (DHS) certified laboratory for analysis of total petroleum hydrocarbons as diesel (TPH/d) and gasoline (TPH/g) using U.S. Environmental Protection Agency (EPA) Test Method 3510/8015 and EPA Test Method 5030/8015, respectively. The samples were also analyzed for benzene, toluene, ethylbenzene, and total xylenes (BTEX) using EPA Test Method 602.



Groundwater Sample Analytical Results

The recent and historic analytical results for groundwater samples collected from monitoring wells MW1, MW2, and MW3, are summarized in Table 2, Attachment B. Copies of the signed laboratory reports, chain-of-custody documentation and sample collection records are presented in Attachment C. With one exception, the recent analytical results were within historic ranges. Historic ranges included non-detect (ND) to 1900 ug/L TPH/d (MW2), ND to 91,000 ug/L TPH/g (MW2), and ND to 8,300 ug/L benzene (MW2). A concentration of 85 ug/L (equal to parts per billion or ppb) TPH/d was detected in sample MW1; TPH/d had not previously been detected in MW1.

Planned Activities

Monthly groundwater level measurements will be recorded during the second quarter 1993. Groundwater samples will be collected quarterly from the existing monitoring wells and submitted for laboratory analysis. Quarterly groundwater monitoring reports will be compiled and submitted to the appropriate regulatory agencies.

SUBSURFACE INVESTIGATION

Soil and Groundwater Sampling Procedures

ATT was retained to investigate the lateral extent of petroleum hydrocarbons in soils and groundwater in the vicinity of the Dryer's Grand Ice Cream Corporate Headquarters building. Soil and water samples were collected from nine locations identified as PC1 through PC9. The sampling locations are shown on Plate 5, Attachment A.

Prior to sampling, the sampling locations were cleared for subsurface utilities by Underground Service Alert (USA). POWERCORE Soil Sampling Inc. of Antioch, California, was contracted to provide sampling services. POWERCORE is a California licensed C-57 contractor. Sample collection activities began on February 24 and were completed on March 8, 1993.

POWERCORE hydraulically-operated portable equipment was utilized for all soil and groundwater sample collection activities. POWERCORE equipment consists of an hydraulically actuated hammer/driver which is hoisted into place over an assembled string of 1.75 inch outside diameter (O.D.) steel AWML drill rod attached to 2.0 inch O.D., 24-inch-long standard penetration test, split-spoon samplers. The 70 pound hammer delivers strikes at a rate of approximately 1,000-12,000 per minute to drive the assembly into the subsurface. At each two-foot depth interval, the drive hammer is hoisted off the drill string and placed to the side. A hydraulically operated ram is used to pull the drill string out of the sample hole.

This continuous coring procedure is repeated in two-foot intervals down to the desired depth. A soil sample can be collected at any desired depth by lining the continuously driven core barrels/split spoon samplers with brass tubes. This process results in a two-inch O.D. sample hole and creates no drill cuttings. Sample holes PC1 through PC9 were driven to total depths of 18, 25, 20, 17, 25, 25, 17.5, 18, and 15 feet below surface grade (bsg), respectively. All subsurface equipment was steam-cleaned prior to coring at each sample hole.

Soil Sample Collection

Soil samples were collected using a standard penetration test split-spoon sampler. For each sample drive, the sampler was lined with four clean brass tubes. The sampler and tubes were cleaned before each sample drive by scrubbing in a solution of Alconox and potable water, followed by two purified water rinses. One soil sample was generally collected from each sample hole just above the first encountered groundwater, or near the bottom of the boring when groundwater was not encountered. Two soil samples were generally collected from borings within which groundwater was not initially encountered during coring. A total of 14 soil samples were collected.

Groundwater Sample Collection

Groundwater "grab" sample collection procedures consisted of the following: an assembly of Schedule 80, 1.0-inch inside diameter (I.D.) PVC casing and screen was placed in each open boring. The bottom five feet of the assembly consisted of screen with 0.02-inch slots. A 24-inch long by 0.75-inch O.D.



Teflon bailer was used to collect the groundwater samples. Three bailers of groundwater were purged from each sample hole before collecting the groundwater samples. Groundwater samples were collected from borings PC1, PC3, PC4, PC5, PC6, and PC9 (a total of six groundwater samples were collected). The Teflon bailer and PVC casing and screen was steam-cleaned prior to sampling and between each boring.

Site Geology/Hydrogeology

The following description of the shallow geology in the vicinity of borings PC1 through PC9 is based on ATT's soil boring logs (see Attachment D). Asphalt and gravel base fill was generally encountered from the surface to approximately 1.0 feet below surface grade (bsg). The asphalt and base was generally underlain by silty clay or sandy clay with a minor component of fine sand to the total depths of the borings. Most of the borings contained occasional sand and/or gravel lenses below 10 feet. Borings PC1, PC3, PC5, PC6, and PC9 contained thick layers of clayey sand with a major component of fine sand. Borings PC1, PC4, PC7, PC8, and PC9 contained clean sand or soil and gravel backfill materials ranging from approximate depths of 4.0 to 6.0 feet bsg. Discolored soils and/or odors (suggestive of aged petroleum hydrocarbons) were encountered in the saturated zone depths ranging from approximately 14 to 18 feet bsg in borings PC1, PC5, PC6, and PC8.

Groundwater was first encountered in borings PC1, PC3, PC4, and PC9, at approximately 15, 14.5, 12, and 11 feet bsg, respectively. No water was encountered during coring in borings PC2, PC5, PC6, PC7, and PC8. Within approximately four hours of reaching the bottom of borings PC5 and PC6, the equilibrated depth to groundwater was approximately 21 and 23 feet bsg, respectively. Borings PC2, PC7, and PC8 remained dry during the field assessment.

LABORATORY SAMPLE ANALYSIS

Copies of the signed laboratory analytical reports and chain-of-custody records are presented in Attachment C.

Soil Sample Analytical Methods

A total of 12 soil samples were analyzed for total petroleum hydrocarbons as diesel (TPH/d) and gasoline (TPH/g) using U.S. Environmental Protection Agency (EPA) Test Method 3550/8015 and EPA Test Method 5030/8015, respectively. The soil samples were also analyzed for benzene, toluene, ethylbenzene, and total xylenes (BTEX) using EPA Test Method 8020.

Soil Sample Analytical Results to table?

Soil sample PC4-12 contained 6.4 mg/Kg (equal to parts per million or ppm) TPH/d. Soil sample PC8-9.5 contained 1.1 ppm TPH/g, 0.0057 ppm ethylbenzene, and 0.0099 ppm total xylenes. Soil sample PC8-15 contained 12 ppm TPH/g, 0.0076 ppm benzene, 0.023 ppm toluene, 0.029 ppm ethylbenzene, and 0.070 ppm total xylenes. All other soil samples contained no analytes at or above the test method detection limits.

Groundwater Sample Analytical Methods

A total of six groundwater grab samples (from borings PC1, PC3, PC4, PC5, PC6 and PC9) were analyzed for TPH/d, TPHg, and BTEX using EPA Test Method 3510/8015, 5030/8015, and 602, respectively.

Groundwater Sample Analytical Results

No analytes were detected in the groundwater samples at or above the test method detection limits. Due to refusal, however, groundwater quality could not be evaluated a several locations.

CONCLUSIONS & RECOMMENDATIONS

Petroleum hydrocarbons, including gasoline and diesel-range constituents, have been detected at relatively high concentrations in groundwater samples from MWB and MW2. The results of the powercore soil and groundwater assessment indicate that soil contamination is present near the west site boundary (PC8) and offsite beneath Chabot Road near the southwest corner of the site (PC4). Here relatively low concentrations of petroleum hydrocarbons were detected in soils between approximate depths of nine and

fifteen feet bsg, immediately above the groundwater surface. No petroleum hydrocarbons were detected in groundwater grab samples collected as part of the powercore assessment program. Water samples could not be collected, due to core barrel refusal and/or absence of saturated soil conditions, from borings (PC7, PC8, and PC2). Hence, water quality west of MW2 and east of MW3 and PC9 has not been characterized. The presence of petroleum hydrocarbons in MW1 is perplexing, and may potentially be due to offsite, upgradient sources. Several service stations sites are present northeast of the site near the intersection of Claremont and College Avenues.

Based on the results of the soil and groundwater assessments to date, ATT recommends that 2 to 3 additional monitoring wells be installed to define the extent of petroleum hydrocarbon contamination. At least one of the wells should be installed east of existing monitoring well MW2, near the 5929 College Avenue building. In addition, we recommend that two to three geologic cross sections be prepared to determine potential migration pathways and the extent of the first water bearing zone. The potential for upgradient sources needs to be evaluated. ATT recommends that regulatory agency files be reviewed to assess potential ongoing monitoring and/or remediation activities at the nearby service station sites. At the request of Dreyers Grand Ice Cream, Inc., ATT will prepare a proposal and cost estimate for the additional characterization work.

Limitations and uncertainties to this report are in Attachment E.

Please call if you have any questions regarding this letter.

Sincerely,

AQUA TERRA TECHNOLOGIES, INC.

Benjamin Berman Staff Scientist

Mark R. Lafferty, R.G. Senior Hydrogeologist

California Registered Geologist #4701

(Expires 6/30/94)

Terrance E. Carter

Senior Environmental Engineer

Project Manager


BB/MRL/TEC/:pd


Attachments


cc: William C. Collett, Dreyer's Grand Ice Cream


ATTACHMENT A


Plates











ATTACHMENT B

Tables

Table 1
Groundwater Elevation Summary
Dreyer's Grand Ice Cream
5929 College Avenue
Oakland, California

Well	TOC Elevation ^a	 .	Groundwater Depth ^b	Groundwater Elevation ^c
No.	(feet)	Date	(feet)	(feet)
MW1	189.14	08/12/91	14.86	174.28
		12/04/91	16.16	172.98
		04/24/92	11,93	177,21
		05/04/92	12.15	176.99
		06/17/92	13.17	175.97
		07/15/92	13.66	175.48
		08/31/92	14.91	174.23
		09/14/92	15.18	173.96
		10/22/92	15.34	173.80
		11/20/92	15.27	173.87
	" . <u>^</u>	12/03/92	14.44	174.70
	182.224	01/18/93	7.85	181.29
		02/10/93	9.29	179.85
		03/10/93	9.88	179.26
MW2	185.23	08/12/92	12.26	172.97
		12/04/91	12.30	172.93
		04/24/92	10.00	175.23
		05/04/92	10.29	174.94
		06/17/92	10.86	174.37
		07/15/92	11.48	173.75
		08/31/92	12.02	173.21
		09/14/92	12.34	172.89
		10/22/92	12.37	172.86
		11/20/92	11.64	173.59
		12/03/92	11.95	173.28

Table 1
Groundwater Elevation Summary
Dreyer's Grand Ice Cream
5929 College Avenue
Oakland, California

Well	TOC Elevation ^a	D-4-	Groundwater Depth ^b	Groundwater Elevation ^c
No.	(feet)	Date	(feet)	(feet)
	185.84 ⁶	01/18/93	5.86	179.37
	189.76	02/10/93	8.20	177.03
		03/10/93	8.57	176.66 1 + 179
MW3	184.68	08/12/91	11.73	172.95
		12/04/91	11.65	173.03
		04/24/92	11.00	173.68
	•	05/04/92	11.09	173.59
		06/17/92	11.51	173.17
		07/15/92	11.84	172.84
		08/31/92	11.70	172.98
		09/14/92	11.74	172.94
		10/22/92	11.33	173.35
		11/20/92	10.58	174.10
	185.21 185.290	12/03/92	10.12	174.56 —
	185.29	01/18/93	8.42	176.26
		02/10/93	9.94	174.74
		03/10/93	10.19	174.49 = 175.0

a. TOC: top of well casing elevation measured relative to an arbitrary bench mark which was measured to mean sea level (MSL) by interpolation from the Oakland West, California, 7.5' Quadrangle Topographic Map (T.1S, R.3W).

b. Depth to groundwater measured from the TOC.

c. Groundwater elevation is equal to the difference between the TOC elevation and groundwater depth.

d. Top of casing resurveyed on May 1, 1993

Table 2
Summary of Laboratory Analytical Results
Groundwater Samples
5929 College Avenue, Oakland, California

				Concent	ration (µg/L)		·····
Well No./ Sample I.D.	Sample Collection Date	TPH/dª	TPH/g ^b	Bc	T ^c	Ec	X ^c
MW1	08/05/91	NA ^d	NDe	1.1	ND	ND	ND
	12/04/91	ND	ND	ND	ND	ND	ND
	03/10/93	85	ND	ND	ND	ND	ND
MW2	08/05/91	1,900	38,000	8,300	8,200	2,300	13,000
	12/04/91	ND	91,000	6,900	6,800	3,200	25,000
3.4'	08/05/91 12/04/91 03/10/93	89	59,000	5,800	5,300	3,100	15,000
		800 ^f	3,300	3,900	160	95	150
TOSC. 4	12/04/91	ND	10,000	3,300	88	80	130
MW3 gw 1000.41 gw fell	03/10/93	ND	8,100	2,000	31	240	30

a. TPH/d = total petroleum hydrocarbons as diesel

b. TPH/g = total petroleum hydrocarbons as gasoline

c. BTEX: B = benzene, T = toluene, E = ethylbenzene, X = total xylenes

d. NA = not analyzed

e. ND = not detected at or above the test method detection limits

f. Petroleum hydrocarbons quantified as diesel are due to hydrocarbons that are lighter than diesel

ATTACHMENT C

Laboratory Analytical Reports Chain-of-Custody Records Sample Collection Records

ATTACHMENT C

Laboratory Analytical Reports Chain-of-Custody Records Sample Collection Records

CHROMALAB, INC.

Environmental Laboratory (1094)

5 DAYS TURNAROUND

March 18, 1993

ChromaLab File No.: 0393135

AQUA TERRA TECHNOLOGIES, INC.

Attn: Kimberly Lagomarsino

RE: Three water samples for Gasoline and BTEX analysis

Project Number: 919313

Date Sampled: Mar. 10, 1993

Date Submitted: Mar. 11, 1993

Date Analyzed: Mar. 16, 1993

RESULTS:

Sample I.D.	Gasoline (µg/L)	Benzene (µg/L)	Toluene (µg/L)	Ethyl Benzene (µg/L)	Total Xylenes (µg/L)
MW1	N.D.	N.D.	N.D.	N.D.	N.D.
MW2	59000	5800	5300	3100	15000
MW3	8100	2000	31	240	30
BLANK	N.D.	N.D.	N.D.	N.D.	N.D.
SPIKE RECOVERY	94%	95%	105%	104%	103%
DUP SPIKE RECOVERY		100%	112%	107%	107%
DETECTION LIMIT	50	0.5	0.5	0.5	0.5
METHOD OF ANALYSIS	5030/8015	602	602	602	602

ChromaLab, Inc.

Billy Thach

Analytical Chemist

Eric Tam

Laboratory Director

CÇ

CHROMALAB, INC.

Environmental Laboratory (1094)

5 DAYS TURNAROUND

March 19, 1993

ChromaLab File No.: 0393135

AQUA TERRA TECHNOLOGIES, INC.

Attn: Kimberly Lagomarsino

RE: Three water samples for Diesel analysis

Project Number: 919313

Date Sampled: Mar. 10, 1993 Date Submitted: Mar. 11, 1993 Date Extracted: March 16, 1993 Date Analyzed: March 16, 1993

RESULTS:

Sample I.D.	Diesel (μg/L)
MW1	85
MW2	89
MW3	N.D.
DT 3.177	W D
BLANK	N.D.
SPIKE RECOVERY	87%
DUP SPIKE RECOVERY	89%
DETECTION LIMIT	50
METHOD OF ANALYSIS	3510/8015

ChromaLab, Inc.

Yiu Tam

Analytical Chemist

Eric Tam

Laboratory Director

do

Aqua Terra Technologies, inc. 2950 Buskirk Avenue, Ste. 120 Walnut Creek, CA 94598 CHA Tel. (415) 934-4884 Fex. (415) 934-0418

CHAIN OF SAMPLE CUSTODY RECORD

A	M	M
A		1

(original document, please return)

• •		`	Ū					. ,				•			Pa	age			of _	
Sampled By: 그	DAUD	BEA	000	-C 1:	=}/	,					Da	ate	San	nple	ed:		3	11	10	93
Signature:	MARIA	ud	la f	/	, (·												
/	//			ď	مدا	r. Ank	140.	614	10						<u> </u>	LV&	2111	<u>4</u>	AB	
Results To Be Se Results Needed I	Bv:	TAND	ne C	Ť-	70	204	100	UNL.	2 <u>0</u>		F	COI ha	ntac ne :	ΣΙ; 4 •	<u> </u>	31		75	38	
Fax Results ASA	P 🖂												ob 7							
Sample	Collection	on			San eser				Sar	nple			Ar	alys	sis/	EP/	\ Mo	əthc	od N	0.
Sample I.D.	Time (24 hr)	Matrix (e.g. Water, Soil)	Number of Containers	lce	HCL	Dry Ice		JW 8h	1 LITEL AMBER			/£			X	/	\int	7	Rem	arks
MINI	13:29	WATER	4	٦	ŗ			2	2			7	٠ ـــ	٦						
MINZ	14:20	11	4	٧				2	2			V		٦						
MW3	15:15	11	4	L				2	2			J	- \	۔ ـ						
								-								-		\vdash		- υ
				-	-	_		-				-								Ş
				_			_	\vdash								_				
					_									-	_	_		_		7
			ļ	_				<u> </u>										_	_	/ C
					_														_	7
							ļ								_					7
	<u></u>		<u> </u>			L.									L_					\sim
Notes:																				
			_																	
																			_	
																			_	
Dell'e e del del																			_	
Relinquished by/ Company Affiliation		Dat	е		Ti	ne		ICa	ceiv ompa			atio	n "	,		Date	3		Tìm	16
Mull	u T	3-11.	-23	T	16:	24	LPC	-	G			700			3	die	193	-	16 2	<u>e</u>
/// /)/				1		'-	ن بری	1					La	b-	1	1 /		+		
		 -	 -	†-				1		<u>-</u>	·				+			十		··



PRIORITY ENVIRONMENTAL LABS

Environmental Analytical Laboratory Precision

February 28, 1993

PEL # 9302063

AQUA TERRA TECHNOLOGIES, INC.

Benjamin Berman Attn:

Re: Three water and three soil samples for Gasoline/BTEX and Diesel analyses.

Project number: 919313

Date sampled: Feb 24, 1993

Date extracted: Feb 26-27, 1993

Date submitted: Feb 26, 1993 Date analyzed: Feb 26-27, 1993

RESULTS:

SAMPLE I.D.	Gasoline	Diesel	Benzene			Total Xylenes	
	(ug/L)	(ug/L)	(ug/L)	(ug/L)		(ug/L)	
PC 1	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	M
PC 3	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	V
PC 4	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	
Detection limit	50	50	0.5	0.5	0.5	0.5	
Method of Analysis	5030 / 8015	3510 / 8015	, 602	602	602	602	
SAMPLE I.D.	Gasoline					Total Xylenes	
1.0.	(mg/Kg)	(mg/Kg)	(ug/Kg)				
PC 1-13.5	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	l.
PC 3-14	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	
PC 4-12	N.D.	6.4	N.D.	N.D.	N.D.	N.D.	٠
Blank	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	
Spiked Recovery	101.4%	82.1%	94.6%	97.3%	92.0%	105.7%	
Duplicate Spiked Recovery	86.8%	94.2%	85.0%	88.6%	90.2%	94.3%	
Detection limit	1.0	1.0	5.0	5.0	5.0	5.0	
Method of Analysis	5030 / 8015	3550 8015	•	8020	8020	8020	

Duong Laboratory Director

1764 Houret Court Milpitas, CA. 95035

Tel: 408-946-9636

Fax: 408-946-9663

Aqua Terra Technologies, Inc. 2950 Buskirk Avenue, Ste. 120 Walnut Creek, CA 94596 CHA Tel. (510) 934-4884 Fax. (510) 934-0418

CHAIN

PEL#

23408

9302063

(Ofiginal document, please return)

A	T	T
		_

, and (6.10) 504 04 10			(5					-1 [-				•••			P	age	<u>,</u>		_ of _	\perp
Sampled By: Z	<u>Senja</u>	nin "	Be	<u> </u>	<u>مم</u>	<u> </u>				_	D	ate	Saı	mpi	ed:	2		24	-93)
Signature:															_		13			
	_		_								La	d d	lam	e: '	P.	<u>.or</u>	idy	E	nu. l	عطهم
Results To Be Se Results Needed	ent To:	<u>senje</u>	<u>m</u>	<u>.~</u>	<u> </u>	<u> </u>	m	<u>ah</u>		_		Co	nta	ct:	1	<u>) æ</u>	نبط	\mathcal{Q}_{-}	-26	9
Fax Results ASA	By: <u>3 020</u> P (naer	<u>q 3</u>		2 ^ }	<u>_</u>	uri	nai	pun	<u>a</u>			ne : ob :		<u>(∓.c</u>	<u>ාප</u>) 94	16	<u>-26</u>	36
	-				San	nole		ſ	Saı	mple		J 3.					A 14		od No	
Sample	e Collection			Pro	eser	vatio	חמ			taine	ers '	L.,		-	313/		, , , , ,	5U IC	שון גונ).
Sample I.D.	Time (24 hr)	Matrix (e.g. Water, Soil)	Number of Containers	lce	HCL	Dry Ice		press	4 liter	40 ml. Von Viàl		A.Har		STE	•			/	Rema	arks
PC1-13.5	9:35	Soil	1	Х				X				X	X	X						
PC2-19.5	12:15	L(1	X				X										4	old	
Pe2-24.5	13:20	11	1	X				X										t	Hold)
PC3-14	14:40	H	1	と				X				X	X	X						
PC4-12	16:50	U	1	λ				X				X	X	×						
004		. 1 1	()																	
PCI PC3	10:45			X			_		2	<u>ဥ</u>			\leq	\times				_	note	٢.
PC3	16:00	- 1	4	Χ	i -				2	ည			\times	X				_		
PCH	17:00	I(4	X	: 		_		2	α		\leq	\succeq	\times	:					
							_												-	
Mara																				
Notes:	in San	nplox	<u>as</u>	-29	.r	my		cle	eph	4	_	on	ver	<u> </u>	10		witt	L		
Victor	at	Prior	体火	٤	nu.	La	<u>مط</u>		<u>.</u> 3-	- 9-	- 93	3, 6	2/	7: ₁	5	am	, <u>, </u>			
			·											= 7	15.	1	Sa			
							·		·-···											
Relinquished by/		7						100	- Pivi	ed b										
Company Affiliation		Date		<u> </u>	Tin			Co	mpa	iny /	Affilia	atior	1			Date	=		Time	
B.Da		2.26	,43	19	<u>3</u>	7A/	И_	4	and	du	<u>*</u>	<u> </u>			2	/VE,	/13	1	:37	M
							<u> </u>											\perp		



PRIORITY ENVIRONMENTAL LABS

Precision Environmental Analytical Laboratory

March 12, 1993

PEL # 9302063

AQUA TERRA TECHNOLOGIES, INC.

Attn: Benjamin Berman

Re: One water sample for Gasoline/BTEX and Diesel analyses.

Project number: 919313

Date sampled: Feb 24, 1993
Date extracted: Mar 10-11, 1993

Date submitted: Feb 26, 1993 Date analyzed: Mar 10-11, 1993

RESULTS:

SAMPLE I.D.	Gasoline (ug/L)	Diesel (ug/L)				Total Xylenes (ug/L)
PC 1	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
Blank	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
Spiked Recovery	105.4%	97.6%	101.3%	100.9%	98.2%	105.0%
Detection limit	50	50	0.5	0.5	0.5	0.5
Method of Analysis	5030 / 8015	3510 / 8015	/ 602	602	602	602

David Duong Laboratory Director

1764 Houret Court Milpitas, CA. 95035

Tel: 408-946-9636

Fax: 408-946-9663

Aqua Terra Technologies, Inc. 2950 Buskirk Avenue, Ste. 120 Walnut Creek, CA 94596 CHA Tel. (510) 934-4884 Fax. (510) 934-0418

CHAIN INV # 23408 (Ofiginal document, please return)

A	Ί'	1

1 EX. (310) 337-04 16			(5					., P		, ,		'''			Р	age	,		_ of _	
Sampled By: Z	benja	rin "	Be	N.V	<u>~a</u>	<u> </u>	<u> </u>				D	ate	Sai	mpl	ed:	<u> </u>	-6	24	-93	,
Signature:											A	Π.	Job	#:,	<u> </u>	110	13	13	<u>, </u>	
			*																nv. l	
Results To Be Se Results Needed	ent To:	senje	<u> </u>	<u>~</u>	7	<u>,e</u> /	m	an na		7	_	Co	nta	ct:	لمنم	<u>)a</u>	نط	4	-26	9
Fax Results ASA	P (XXI	Caper	4 0		7		<u>~/ /</u>	,,,,,,,	-	<u>~</u>			ne ob :		<u>(16</u>	<u> </u>	<u>/ 7°</u>	76	<u>-86</u>	<u>36</u>
Sample	e Collecti	on	i	Sample Preservation					Sample Containers					Analysis/EPA Method No.).
Sample I.D.	Time (24 hr)	Matrix (e.g. Water, Soil)	Number of Containers	eoj	HCL	Dry Ice		pres	なんだら	40 ml. VOM Vial		N. Hatt		STATE OF THE PROPERTY OF THE P	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\				Rem	arks
PC1-13.5	9:35	8:11	1	X				X				X	X	X						
PC2-19.5	12:15	l (-	x				X										4	lold	
Pe2-24.5	13:20	11	l	X				X										f	Hold	,
PC3-14	14:40	L1	1	X				X				X	X	X						
PC4-12	16:50	11	1	λ				X				X	X	×						
PC1	10:45	Waster	4	X					2	ລ		\times	_ ×	X					·	
PC3 PCH	16:00	li	4	X					a	a		Z	X	X					·	
PCH	17:00	ιίς	4	×					2	Ω		\leq	\times	\times					-	
						_	_		_	_		_							**	
		-		\dashv	_	-	\dashv		_			_						<u> </u>		
Notes:	ļ								J		1									
		·															·		-	
·····																				
Relinquished by/ Company Affiliation		Date	3		Tin				eive npa		y: \ffilia	tion)			Date)		Time	
B.D.		226	43	9.	:3	7A/	И		and			2			2/	/ኒፍ/	113	1	:37	m
		ļ					ر.								_				····	
		j		1																



PRIORITY ENVIRONMENTAL LABS

Precision Environmental Analytical Laboratory

March 11, 1993

PEL # 9303012

AQUA TERRA TECHNOLOGIES, INC.

Attn: Benjamin Berman

Re: Three water and nine soil samples for Gasoline/BTEX and Diesel analyses.

Project number: 919313

Date sampled: Mar 08, 1993

Date extracted: Mar 09-10, 1993

Date submitted: Mar 09, 1993 Date analyzed: Mar 09-10, 1993

RESULTS:

SAMPLE		Gasoline	Diesel	Benzene			Total
I.D.							Xylenes
		(ug/L)	(ug/L)	(ug/L)	(ug/L)	(nd/r)	(ug/L)
	1/2	^	37 75	N. D.	N D	N. D.	N.D.
PC 5	Na	N.D.	N.D.	N.D.	N.D.	N.D.	
PC 6	O	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
PC 9		N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
Detection	Limit	50	50	0.5	0.5	0.5	0.5
Method of	Analysis	5030/8015 3	510/8015	602	602	602	602
SAMPLE		Gasoline	Diesel	Benzene	Toluene	Ethvl	Total
I.D.		ouborine	DICUCI	D0D0		Benzene	
		(mg/Kg)	(mg/Kg)	(ug/Kg)	(ug/Kg)		
PC 5-9	00	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
PC 5-15	(YUV	N.D.	N.D.	N.D.	N.D.		N.D.
PC 6-9.5	(N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
PC 6-16.5		N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
PC 7-9.5		N.D.	N.D.	N.D.	N.D.		N.D.
PC 7-16		N.D.	N.D.	N.D.	N.D.		N.D.
PC 8-9.5		1.1	N.D.	N.D.	N.D.	5.7	9.9
PC 8-15		12	N.D.	7.6	23	29	70
PC 9-9.5		N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
Blank		N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
Spiked Rec	COVORY	105.4%	97.6%			እ.ይ. % 98.2 [%]	
				86.0%		8 97.1 ⁹	-
Detection	Spiked Reco	1.0	1.0				
					8020		8020
mechoa oi	Analysis	ananlenta .	つつつの/ ロハエ	5 6020	0020	0020	0020

Laboratory Director

1764 Houret Court Milpitas, CA. 95035

Tel: 408-946-9636

Fax: 408-946-9663

PEL # 9303012

Aqua Terra Technologies, Inc. 2950 Buskirk Avenue, Ste. 120 Walnut Creek, CA 94598 CHAI Tel. (510) 934-4884 Fax. (510) 934-0418

CHAIN OF SAME

INV # 23424

A	M
A	

(original document, please return)

	Fax. (310) 334-0418	_		(59					·, P	···	,	·	''			Pa	age	1		of _	
	Sampled By:	<u>Benja</u>	min_	Be	m	an.	e					Da	ite :	San	nple	ed:	3	<u>-2</u>	<u>3-</u>	-93	<i>></i>
	Signature:	3.4	Sam									AT	TJ	ob	#:_	9	19	31	3	······	
			_									Lab	N	am	e: 1	<u> </u>	<u>irub</u>	YE	NV.	. La	<u>رجا</u>
. 1 .	Results To Be Sent To: Benjamin Berman Results Needed By: 3-11-93 (48 hr Jurnar and)																				vid 36
*	Results Needed Fax Results ASA		<u> </u>	(48	21	· de	urn	arr	کر یم	()						40	<u>8</u>)	94	16	<u>-96</u>	<u>.36</u>
					_	<u> </u>				0-		Lab	JC				==				
	Sample	e Collecti			Preservation C				Containers			Αп	alys	lysis/EPA Method No.).		
	Sample I.D.	Time (24 hr)	Matrix (e.g. Water, Soil)	Number of Containers	Ice	HCL	Dry Ice		gang	40ml. VOM	1 literal		14 H	Z T	STR	<i>\$</i> /	/	\int_{I}	\int_{\cdot}	Rema	arks
	PC5-9	8:45	Soil	1	X				X				X	X	X						
	PC5-15.	8:55	=		X				X				X	X	X						
	PC6-9.5	10:45	W	1	X				X				X	X	X						
	PC6-16.5	10:55	1(X				X			;	\times [,	\times	\times						
	PC7-9.5	13:20	ιſ	1	X				\times					\times	\times						
	PC7-16	13:35	((1	X				X				$\times $	\times	X						
	PC8-9.5	14:45	11		X				X				\times	\times	X						
	PC8-15	14:55	{ {	1	X				X				$\angle \psi$	\times	\times						
	PC9-9.5	17:00	11	1	X				X			`	\times	X	X				,		
	PC5	14:30	Water	3	X					2			X,	X	X				A.	Liter	dilled
	PC6	15:45	11	3	X					a	1		A)	\times	X				1 Li	ifer a	mky Allud
	PC9	18:00	ш	3	X					೩	1		$\langle \uparrow \rangle$	X	X						
	Notes: Impo	rdant	: 8	Ret	w	n		al	1	u	nu	<i>ise</i>	d	_	sa	m	<u>~</u> (S	90	
	our od	fice	(inc	لسك	iù	<u> </u>	a	12			us		,		br	7	,		 9	£	
	samples), sa	mel	e_		d	/	,	1	ৈ	<i>41</i> 0	ons	-		us			<u>Z.</u>			-
Ì	mainstaine			_		Ju					ZM										
	* no extra	charge	ع عدر	ver j	/ica	on	14	leç					Sad	ازد		3.	-9.	- 93	و	11:16	s an
	Relinquished by/ Company Affiliation		Dat	e		Tin	ne				ed by any A		tion			1	Date)		Time	'
	B. Be		3-9	-23		1:4	01	OM	\prod	7	rdd		~			3,	1919	73	17	1:40	PA
1					1				Idi							T			7		

Date: 3 - 1	0-93	Sample I.	D.: MK)	Job No.	: 919313							
Site Locat:	ion: Dery	bes Ger	an Tot Ce	eam \	DAKCAND							
No. of Cont	tainers :	·/	(check one)	:Wel	l Samples;							
Duplicat)							
Field B	•											
W.L. (1/100): <u>9.88</u>	Time	: 13:01 E	3.0.W. (1/	2'): <u>28.5</u>							
Method: VElectric Well Sounder;Other/												
Meters calibrated: Y / N Well Loc. Map: Y / N												
Calculated Purge Volume (4 casing volumes): 12 gallons												
Purging Met	hod:	Disposab	le Bailer;	Tefl	on Bailer;							
Other/	···		·									
Time Start Sheen: Y // Turbidity:	Purging	(24 hr); r: Y / N	13:08 , Vapor:_	Produ	ct: Y /N / LEL							
Time Stop P Sheen: Y / (Turbidity:_	urging (N). Odo	24 hr): r: Y / N	13:25,	Produ	ct: Y / M							
_	Temp.		Cond.									
13:14	_18 _e	7.13	CHOC)	_4_	109							
13:20	<u> </u>	4.82	0390	8	87							
12.75				. 7								
17:67	<u> 18°</u>	(0.7.1	0350	_(<u></u>							
:	_ <u>18°</u>	(0.71	<u>0350</u>	(C								
:	_ <u>l8°_</u>	<u>(6.9'1</u>	<u>0350</u>									
· · · · · ·	· · · · · · · · · · · · · · · · · · ·											
Sample Colle	ection T											
Sample Colle	ection T											
: Sample Colle	ection T		r): <u>/3:Z</u>	9								
Sample Colle	ection T		r): <u>/3:Z</u>	9								

Date: 3 -1												
Site Locat	ion: Dey	per Gean	JEE GEFAN	<u>O</u> A	KLAND							
No. of Con												
Duplica	tes from	well		Trav	el Blanks;							
Field B	•											
					•							
W.L.(1/100	'): <u>867</u>	Time	: <u>13:41</u> B	.o.w. (1/	21):26.5							
Kethod:Other/Other/												
Meters calibrated: Y N . Well Loc. Map: Y N												
Calculated	Purge Vo	olume (4	casing volu	mes):4	gallons							
Purging Met	hod:	Disposab	le Bailer;	Tefl	on Bailer;							
Other/			· · · · · · · · · · · · · · · · · · ·									
Time Start Sheen: Y / Turbidity:	Purging N , Odo	(24 hr): er: (Y)/ N 33	13:45 Vapor:	Produc	et: Y /N ALEL							
Time Stop F Sheen: (Y)/ Turbidity:_	N , Odo	r: Y)/ N	, Vapor:_	ppm /	*LEL							
Time												
(24 hr)	_(C)		(us)	(Gal)	(UTU)							
13.55	_18°	6.48	0630	15	_/3							
14:06	<u> 18°</u>	6.56	0770	30	_9							
14:18	<u>18°</u>	6.55	0770	45								
	-		·		-							
												
Sample Coll	ection T	ime (24 h	r): 14:20	<u>o</u> .								
iotes: <u>4.00</u>	JG PETO	coleum of	DEP PURMA	PORGE	-SHEN							
Developed A	FOR	20 GAL.	RURGED T	WE BAILE	er usop							
4" were			200	10:	·· · · · · · · · · · · · · · · · · · ·							
Collected B	y (signa	ture) :	May	U/								

ATT

Date: 3-1	<u>0-93</u> s	Sample I.	D.: MW3	Job No.	: 919313								
Site Locat:	ion: <u>Dev</u> e	5 GRAND	TC= CREAM	<u> </u>	AKLAND								
No. of Cont	tainers :	4	(check one)	:Wel	l Samples;								
Duplicat	es from	well	;	Trav	el Blanks;								
Field Bl	lanks; _	Other	(explain)/_										
					•								
W.L. (1/100'): 10.19 Time: 14:33 B.O.W. (1/2'): 26.5													
Method:Other/													
Meters calibrated: Y N . Well Loc. Map: Y N													
Calculated	Purge Vo	lume (4 d	casing volu	mes): <u>42</u>	_ gallons								
Purging Met	hod:	Ďisposab:	le Bailer;	Tefl	on Bailer;								
Other/		 	· · · · · · · · · · · · · · · · · · ·										
Time Start Sheen: (Y)/ Turbidity:_ Time Step P Sheen: (Y)/ Turbidity:_													
Time (24 hr)	Temp.												
14:50		4.88	0670										
													
<u> </u>	_18°	<i>کانیک</i>	040	28	72								
			0730		<u>72</u> 111								
	18°	<u>686</u> —	0730	42_									
15:13 : Sample Colle	18°	<u>686</u> ———————————————————————————————————	0730 	42_									
15:13 Sample Colle	18° ection Ti	(24 h	0730 	42_ 									
15:13 Sample Colle	18° ection Ti	(24 h	_0730 	42 SHEEN 4P 4"									
15:13 	ection Ti	1me (24 h	0730 	42 SHEEN 4P 4"									

ATTACHMENT D Soil Boring Logs

Project: <u>Dreyer's</u>	n: 5929 College Ave., Oakland, Ca. Date: 2/24/93 No.: PC1 Driller: Powercore Page 1 of	Job No.: <u>919313</u>
Location: <u>5929 Col</u>	lege Ave., Oakland, Ca.	Date: <u>2/24/93</u>
Boring No.: <u>PC</u> :	1 Driller: Powercore	Page1 of2
Logged By: BB	Proj. Mgr. TEC	Reviewed By:

Penetra- tion (Blows/ (feet (f	Asphalt Base	Field Description	Remarks
(Blows/ (feet 6") 0	Asphalt Base	Field Description	Remarks
6")	Asphalt Base	Field Description	Remarks
1	Base		
1	Base		
- 2 - 3 - 4 - 5 - 6 - 7 - 8 - 9 - 10 - 11 - 12 - 13		A1 44 B	
- 3 - 4 - 5 - 6 - 7 - 8 - 9 - 10 - 11 - 12 - 13		0'-1' Asphalt and gravel base 1'-5' Sand; backfill, fine, clean	
- 3 - 4 - 5 - 6 - 7 - 8 - 9 - 10 - 11 - 12 - 13	1 1	sand	
- 4 - 5 - 6 - 7 - 8 - 9 - 10 - 11 - 12 - 13	Sand		
- 5 - 6 - 7 - 8 - 9 - 10 - 11 - 12 - 13	Backfill		
- 6 - 7 - 8 - 9 - 10 - 11 - 12 - 13			
- 7 - 8 - 9 - 10 - 11 - 12 - 13		5'-18' Clayey Sand; very dark gray-	
- 7 - 8 - 9 - 10 - 11 - 12 - 13		ish brown (2.5Y 3/2); 40% to 80%	
- 8 - 9 - 10 - 11 - 12 - 13		very fine sand; minor component	
- 9 - 10 - 11 - 12 - 13		of medium to coarse sand; slightly damp	ļ
- 9 - 10 - 11 - 12 - 13			
- 10 - 11 - 12 - 13		•	
- 11 - 12 - 13			
- 11 - 12 - 13		- -	
- 12 - 13			
	sc		
		Soil moist to very moist below 12'	
		with minor iron staining	
			13.5'
1 44			Sample
-			l
		Aged hydrocarbon discoloring and odor in soil below 16'	15' First Water
	1 1	AMOL IN BOIL DELOM FO.	Hacer
- -			1

Field Drilling and Sampling Log

ATT

Job No: 919313

Page _2 of _2

Penetra- tion (Blows/ 6")	Depth	U.S.C.S. Soil Class.	PC1 Field Description	Remarks
	17			
	— 18		B.O.H. @ 18.	
	_ 19			
<u> </u>	20			
	21 			
	22 _			
	— 23 –			
	24 - 25			
	_ 27			
	_ 28			
	29			
[<u> </u>			
	— 31 –			
	— 32 —			
	- 33 - 34			
	- - 35			
	- 36			
	37			
	38 		· .	
		<u> </u>		

Project: <u>Dreyer's Grand Ic</u>	e Cream	Job No.: 919313
Location: <u>5929 College Ave.</u>	, Oakland, Ca.	Date: 2/24/93
Boring No.: PC2	Driller: Powercore	_ Page1 of2
Logged By: BB	Proj. Mgr. TEC	_ Reviewed By:

Penetra- tion (Blows/ 6")	Depth (feet)	U.S.C.S. Soil Class.	Field Description	Remarks
	- 1 - 2 - 3 - 4	Asphalt -& Gravel- Base CL	0'-1' Asphalt and gravel base 1'-5' Silty Clay; very dark grayish brown (2.5Y 3/2); minor component of fine, medium, and coarse sand and fine gravel (poorly graded); medium plasticity; slightly damp	
	- - - - - - - - 7 - - 8		5'-25' Silty Clay; dark yellowish brown (10YR 4/4); very stiff to hard; medium plasticity; slightly damp to dry; very minor component of very fine sand	
	- 9 - 10 - 11 - 12	CL	Increase in fine sand and moisture content below 9'(damp to moist)	
	- 13 - 14 - 15 - 16 - 16		Minor component of fine to medium gravel below 16' (angular, vary- ing composition) and intermittent thin lenses of very fine sand	

Field Drilling and Sampling Log

Job No: 919313

Page 2 of 2

Penetra-U.S.C.S. tion Soil PC2 Depth Field Description (Blows/ Remarks Class. 6") 17-18 - 19 19.5 20 CL Sample 21 22 23 24.51 24 Sample B.O.H. @ 25' (Dry Hole) 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39

Project:1	Dreyer's Grand	Ce Cream	Job No.: 919313
Location: _!	5929 College Ave	o., Oakland, Ca.	Date: <u>2/24/93</u>
Boring No.:	PC3	Driller: Powercore	Page1 of2
Logged By: _	BB	Proj. Mgr. TEC	Reviewed By: MRC

Penetra- tion (Blows/ 6")	Depth (feet)	U.S.C.S. Soil Class.	Field Description	Remarks
	_ 1 _	Asphalt Base	0'-1' Asphalt and gravel base 1'-10' Silty Clay; very dark gray- ish brown (2.5Y 4/2); medium	
	2 3 3		<pre>plasticity; stiff; moist</pre>	
	- 4 - 5 -	CL		
	- 6 - 7 - 7		·	
	- 8 - 9 -		· -	·
	— 10 - — 11 -		10'-20' Clayey Sand; olive brown (2.5Y 4/4); 40% to 80% fine sand; moist to very moist	
	— 12 - — 13 -	sc	Varies to sandy clay with minor component of five to medium	
	— 14 - — 15 -		<pre>gravel below 12' (angular, vary- ing composition) Color change below 15'; very dark</pre>	14' Sample 14.5' First Water
	- 16 - 17		grayish brown (2.5Y 3/2)	

Field Drilling and Sampling Log

Job No: 919313

Page 2 of 2

Penetra- tion (Blows/ 6")	Depth	U.S.C.S. Soil Class.	PC3 Field Description	Remarks
	- 18 - 19 - 20	SC	В.О.Н. @ 20'	
	- - 21 - 22 -			
	— 23 — 24 — 25 —		·	
	26 27 28 28			
	- 29 - 30 - 31 - 31			
	— 32 — 33 — 34 —			
	- 35 - 36 - 37 - 37			
	- 38 - - 39			

Project: <u>Dreyer's Grand Ic</u>	e Cream	Job No.: <u>919313</u>
Location: <u>5929 College Ave.</u>	, Oakland, Ca.	Date: 2/24/93
Boring No.: PC4	Driller: Powercore	Page <u>1</u> of <u>1</u>
Logged By:BB	Proj. Mgr. TEC	Reviewed By: MKC

Penetra-		U.S.C.S.		
tion	Depth	Soil		
(Blows/ 6")	(feet)	Class.	Field Description	Remarks
	 от	 		
	-	Asphalt	Asphalt and gravel base	
	1	Base	0'-6' Sand; backfill, clean, fine	
	-		sand	
				
	-	Sand		
	— з	Backfill		[
	- 4			
	-			1
	5			
	-			
	6		6'-9' Silty Clay; dark grayish	
			brown (2.5Y 4/2); stiff to hard;]
	7	CL	medium to high plasticity; damp;	
	-		minor component of fine sand	
	8		to fine gravel, poorly graded;	
	_		sand content increases with depth	
	- 9		9'-17' Sandy Clay; dark yellowish	
	_		brown (10YR 4/4); minor component	
	10		of fine sand to fine gravel (as	
	_		above); damp	
	— 11			
			San A Jan - Smar - 101 La - 101	
	<u> </u>		Sand lens from 12' to 13'	12' Sample 12' First
	13	ac l		Water
	13	80		Marat
	_ 14			
	15			1
			15.5'-16.5' Gravel lens	
	— 16		72:3TA:3. ATGAGT TRUD	
	_ **		B.O.H. @ 17'	
	17			

Project:	Dreyer's Grand 1	ce Cream	Job No.: _	919313
Location: _	5929 College Ave	., Oakland, CA	Date: 3/08/	93
Boring No.:	PC5	Driller: Powercore	_ Page 1 o	f
Logged By: _	ВВ	Proj. Mgr. TC	_ Reviewed By: _	MRC

Penetra- tion (Blows/ 6")	Depth (feet)	U.S.C.S. Soil Class.	Field Description	Remarks
	- 1	Fill	0'-2' Landscaping soil, fill	
	- - - - 3 - - 4		2'-25' Clayey Sand; dark olive gray (5Y 3/2); 20% to 80% very fine sand; medium dense (crumbles under slight hand pressure); damp Beginning at ~ 4', color change;	
	5 6		dark yellowish brown (10YR4/4); minor component of coarse sand and fine gravel	
	- 8 - 9 -	BC/CL	Beginning at "9', color change; dark olive gray (5Y 3/2); very	9' Sample
	— 10 - — 11		moist	
-	12 12			
	— 13 –			
	— 14 - — 15		Beginning at "14', color change; bluish/greenish gray; possible aged hydrocarbon discoloring;	15' Sample
	_ 16 		changes to dark yellowish brown (as above) below 17 '	(slight odor)
	└─ _17 ┴	<u> </u>		

Field Drilling and Sampling Log

Job No: 919313

Page 2 of 2

Penetra- tion (Blows/ 6")	Depth (feet)	U.S.C.S. Soil Class.	PC5 Field Description	Remarks
	- 18 - 19 - 20 - 21 - 22	8C/CL		Hole init- ially dry, small quan- tity of water after 2 hours
	23 24 25 26 27 27		B.O.H. @ 25'	
	28 29 30 31 32		·	
	- - - 34 - - - 35 - - 36			·
	37 - - 38 - - 39			

Project:	Dreyer's Grand	Ice Cream	Job No.:9	19313
Location: _	5929 College Av	e., Oakland, CA	Date:3/08/93	<u> </u>
Boring No.:	PC6_	Driller: _Powercore	Page1 of	
Logged By:	BB	Proj. Mgr. TC	Reviewed By:	MKE

Penetra-		U.S.C.S.		
tion	Depth	Soil		
(Blows/	(feet)	Class.	Field Description	Remarks
611)			_	
	<u></u> о⊤	-Asphalt-		
	-		0'-0.5' asphalt and Gravel base	
	1	İ	0.5'-8.5' Silty Clay; black (5Y	
	–		2.5/1); medium plasticity; stiff;	
	— 2]	slightly damp	
	-		2' Color change; very dark grayish	
	— з		brown (10YR 3/2); minor component	
			of coarse sand to fine gravel	
	<u> </u>	1	(angular to semi-angular, varying	
	_		composition; sightly damp	
	5	CL	Beginning at 4', increase in moist	ire
	_		content; minor component of very	
	<u> </u>		fine sand	
	_ 1			
	7			
	_			
	s			
	_		8.5'-17.5' Silty Clay; olive brown	
	le		(2.5Y 4/4); medium to high plast-	9.5 Sample
	_		icity; damp to moist	
·	— 10	}	1010], 1110	
	11	ŀ		
	<u> </u>	CL	12.5' minor component of fine to	
			medium gravel (to \ inch diameter)	
	— 13		angular to semi-angular, varying	
	_ **		composition.	
	14		Increase in fine sand content,	
	_ **		moisture content, below 13'	16'-17'
	— 15		management and real re-	odor
			16'-17' Clayey Gravel (as above);	16.5 Sample
	16		bluish greenish gray, possible age	
	_ 1		hydrocarbon discoloring	
			nlatostron arecording	

Field Drilling and Sampling Log

Job No: 919313

Page <u>2</u> of <u>2</u>

Penetra- tion (Blows/ 6")	Depth (feet)	U.S.C.S. Soil Class.	PC6 Field Description	Remarks
6")	17 - 18 - 19 - 20 - 21 - 22 - 23 - 24 - 25 - 26 - 27 - 28 - 29 - 30 - 31 - 32 - 33	8C	17.5-25' Clayey Sand; dark yellowish brown (10YR 4/4); 15% to 40% very fine to fine sand; minor component of medium to coarse sand; poorly graded; medium plasticity; stiff; damp to moist 18' aged hydrocarbon discoloring B.O.H. @ 25'	18' Slight
	— 34 — 35 — 36			
	- - - 37 - - 38 -			. ,

Project:	Dreyer's Grand	Ice Cream	Job No.: <u>919313</u>
Location: _	5929 College 7	ve., Oakland, CA	Date:3/08/93
Boring No.:	PC7	Driller: Powercore	Page1 _ of1
Logged By: _	ВВ	Proj. Mgr. TC	Reviewed By:MKU_

Penetra- tion (Blows/ 6")	Depth (feet)	U.S.C.S. Soil Class.	Field Description	Remarks
	— о—	+Asphalt $-$		
	_	Base	0'-0.5' Asphalt and gravel base rock	
	<u> </u>	CL	0.5-2' Silty Clay; black (5Y 2.5/1);	
		(Fill?)	dry (crumbles under moderate hand	ī
	2		pressure) (Possible Fill Material)	
	-		2'-5' Sand; yellowish brown (10YR	
	— з	8W	5/4); fine sand, clean, compressed	
		(Fill?)	(crumbles under applied hand pres-	
	4		sure); dry. (Possible Fill	
	5		Material)	
			5'-9' Silty Clay; very dark grayish brown (10YR 3/2); medium plasticity	
	_ 6		damp	(*
		CL	9'-11.5 Silty Clay; brown (10YR	
		CL	4/3); medium to high plasticity;	
			slightly damp	
	8		11.5'-14' Clayey Sand; dark brown	
	-	1	(7.5YR 4/4); 20% to 60% very fine	
	9		to fine sand; minor iron staining;	
	_		damp to moist (increase in fine	9.5' Sample
·····	10		sand, moisture content below 13')	_
	_	CL	14'-15' Clayey Gravel; fine to	
	<u> </u>		medium gravel (to 1" diameter);	
	-		angular to semi-angular, varying	
	— 12		composition; damp	
	-		15'-16.5' Silty Clay; dark yellowish	
	13	SC	brown (10YR 4/4); medium plasticity	73
			damp	
	14	GC	16.5'-17.5' Clayey Sand/Gravel; fine to coarse sand and fine to medium	
	15	GC	gravel; compressed sand (crumbles	
	_ 15	CL	under applied hand pressure)	
	- 16		mider apprise mend bressars)	16' Sample
			B.O.H. @ 17.5 (Refusal, dry hole)	70. Dambie
	17	[⊥] sc/gc—	minimit & min (mores) and more)	

Project:	Dreyer's Grand 1	ce Cream	Job No.: <u>919313</u>
Location: _	5929 College Ave	., Oakland, CA	_ Date:3/08/93
Boring No.:	PC8	Driller: <u>Powercore</u>	_ Page1 of1
Logged By: _	ВВ	Proj. Mgr. TC	Reviewed By: MKV

Penetra- tion (Blows/ 6")	Depth (feet)	U.S.C.S. Soil Class.	Field Description	Remarks
	- 1 - 1		0'-4' Fill material (potting soil, gravel)	
	2 3 1	Fill		,
	4 5 6		4'-8' Silty Clay; very dark grayish brown (10YR 3/2); medium plast- icity; stiff; slightly damp	
	- 8 - 7 - 8	CL	8'-18' Silty Clay; dark brown (10YR	
	- - - - 10		4/2); medium to high plasticity; very stiff; slightly damp	9.5' Sample
	_ 11 _ 12	CL	Beginning ~ 12.5'; minor iron stain- ing, minor component of fine to medium gravel (to 3/4 inch diamete:	
	- - 13 - - 14		angular to semi-angular, varying composition 14' blue-green hydrocarbon dis- coloring, increase in iron	14' Odor
	- - 15 - 16		staining Very stiff to hard below 16.5' 18' minor aged hydrocarbon dis- coloring	15' Sample 15.5' Odor 18' Slight
	₁₇ _		B.O.H. @ 18' (Refusal, dry hole)	Odor

Project: <u>Drey</u>	er's Grand I	ce Cream	Job No.: <u>919313</u>
Location: 5929	College Ave	., Oakland, CA	Date: 3/08/93
Boring No.:	PC9	Driller: Powercore	Page <u>1</u> of <u>1</u>
Logged By:	вв	Proj. Mgr. TC	Reviewed By: MKL

Penetra- tion (Blows/ 6")	Depth (feet)	U.S.C.S. Soil Class.	Field Description	Remarks
	- 1 - 2 - 3	Fill	0'-4' Fill material (potting mix, gravel, etc.)	
	- 4 - 5 - 6		4'-11' Silty Clay; black (5Y 2.5/2); medium plasticity; vary minor component of medium to coarse sand; damp	
	7 8 8	CL		
	— 9 — 10 —		9' Color change; dark grayish brown 2.5Y 4/2); medium to high plasticity; very stiff to hard	9.5' Sample
	- 11 - 12 - 13	8C	11'-15' Sandy Clay; dark grayish brown (2.5Y 4/2); 15% to 40% very fine sand; medium plasticity; minor rust staining; damp	11° First Water
	- - 14 - - 15		B.O.H. @ 15'	
	- - 16 -			

ATTACHMENT E Limitations & Uncertainty

LIMITATIONS AND UNCERTAINTY

This report was prepared in general accordance with the accepted standard of practice which exists in northern California at the time the investigation was conducted and within the scope of services outlined in our proposal. It should be recognized that the definition and evaluation of surface and subsurface environmental conditions is a difficult and inexact science. Judgements leading to conclusions is a difficult and inexact science. Judgements leading to conclusions and recommendations generally are made with an incomplete knowledge of the conditions present. It is possible that variations in the soil and/or groundwater conditions could exist beyond the points explored for this investigation. Also changes in groundwater conditions could occur sometime in the future due to variations in tides, rainfall, temperature, local or regional water use or other factors. If the client wishes to reduce the uncertainty beyond the level associated with this study, ATT should be notified for additional consultation.

The discussion and recommendations presented in this report are based on: 1) information and data provided by third party consultants, 2) the exploratory test borings drilled at the site, 3) the observations of field personnel, 4) the results of laboratory analysis by a California Department of Health Services (DHS) accredited laboratory, and 5) interpretations of federal, state, and local regulations and/or ordinances.

Chemical analytical data included in this report have been obtained from state certified laboratories. The analytical methods employed by the laboratories were in accordance with procedures suggested by the U.S. Environmental Protection Agency and the State of California. ATT is not responsible for laboratory errors in procedures or reporting.

ATT has conducted this investigation in a manner consistent with the level of care and skill ordinarily exercised by members of the environmental consulting profession currently practicing under similar conditions in northern California. ATT has prepared this report for the client's (and assigned parties) exclusive use for this particular project. No other warranties, expressed or implied, as to the professional advice provided are made.