

Phone: (925) 944-2899

Fax: (925) 944-2895

July 27, 2005

Mr. Barney Chan Alameda County Health Care Services Agency 1131 Harbor Bay Parkway, Suite 250 Alameda, CA 94502-6577

Subject:

**Quarterly Groundwater Monitoring Report** 

2<sup>nd</sup> Quarter 2005 1075 40<sup>th</sup> Street Oakland, California AEI Project No. 3119 eport FO

Dear Mr. Chan:

Enclosed is a copy of the quarterly groundwater report for the 2<sup>nd</sup> Quarter 2005 groundwater monitoring event.


The client is holding back on remediation until we get some sort of approval for our previous request. We also need to clean up the free product as suggested in this report.

Please call me or Robert Flory at (925) 944-2899 x122, if you have any questions.

Sincerely,

**AEI Consultants** 

Jeremy Quick Staff Geologist July 27, 2005



## GROUNDWATER MONITORING REPORT 2<sup>nd</sup> Quarter 2005

1075 40th Street Oakland, California 94608

AEI Project No. 8326 ACHCSA Fuel Leak Case No. RO0000186

Prepared For

Mr. Monte Upshaw Fidelity Roof Company 1075 40th Street Oakland, CA 94608

Prepared By

AEI Consultants 2500 Camino Diablo Blvd., Suite 200 Walnut Creek, CA 94597 (925) 944-2899



Phone: 19251 944-2899

Fax: (925) 944-2895

July 27, 2005

Mr. Monte Upshaw Fidelity Roof Company 1075 40th Street Oakland, CA 94608

Subject:

**Quarterly Groundwater Monitoring Report** 

2<sup>nd</sup> Quarter 2005 1075 40th Street Oakland, California 94608 AEI Project No. 8326

ACHCSA Fuel Leak Case No. RO0000186

Dear Mr. Upshaw:

AEI Consultants (AEI) has prepared this report on behalf of Fidelity Roof Company to document the ongoing groundwater investigation at the above referenced site (Figure 1: Site Location Map). The purpose of this activity was to monitor groundwater quality near the previously removed underground storage tanks (USTs). The work was performed in compliance with requirements of the Alameda County Health Care Services Agency (ACHCSA). This report presents the findings of the 2<sup>nd</sup> Quarter 2005 groundwater monitoring and sampling event conducted on June 15, 2005.

### Site Description and Background

The site currently supports the operation of Fidelity Roof Company and is located in a mixed residential and commercial area of Oakland at 1075 40th Street.

On December 19, 1995, Tank Protect Engineering, Inc. removed one (1) 1,000-gallon diesel underground storage tank (UST) and one (1) 500-gallon gasoline UST from the southeast corner of the property. The removal of the tanks produced a single excavation. Analysis of the soil samples indicated that soil beneath the 1,000-gallon UST had been impacted by minor concentrations of total petroleum hydrocarbons as gasoline (TPH-g), TPH as diesel (TPH-d), benzene, toluene, ethylbenzene, and total xylenes (BTEX), and methyl tertiary-butyl ether (MTBE).

On September 12, 1996, AEI advanced four (4) soil borings near the former UST excavation. Analytical results from the subsurface investigation revealed significant levels of gasoline and diesel petroleum hydrocarbons present in soil and groundwater to the south and to the west of the open excavation. Due to the high concentrations of petroleum hydrocarbons within the

groundwater, the ACHCSA required further investigation of the extent and magnitude of the groundwater contaminant plume.

On October 25, 1996, AEI extended the excavation laterally 7 feet to the south and 12 feet to the west. Soil was removed to a depth of 9 feet below ground surface (bgs). The dispenser island and associated piping were also removed. Analyses of the soil samples collected from the excavation sidewalls indicated that up to 150 milligrams per kilogram (mg/kg) of TPH-g, 16 mg/kg of benzene, and 300 mg/kg of TPH-d remained within the western sidewall of the excavation.

On March 6, 1997, AEI installed three (3) groundwater monitoring wells, MW-1 through MW-3. TPH-g and TPH-d were detected in well MW-3 at concentrations of 26,000 micrograms per liter ( $\mu$ g/L) and 5,000  $\mu$ g/L, respectively. No TPH-g or TPH-d was detected in wells MW-1 and MW-2, at the time of the initial sampling. MTBE was detected in wells MW-1, MW-2 and MW-3 at concentrations of 23  $\mu$ g/L, 65  $\mu$ g/L and 230  $\mu$ g/L, respectively. Well construction details for the groundwater monitoring wells are summarized in Table 1.

At the request of the ACHCSA, six (6) additional soil borings were drilled south and west of the well locations on November 4, 1998. TPH-d was detected at a concentration of 2,400  $\mu$ g/L in groundwater to the south of the former excavation. No significant concentrations of petroleum hydrocarbons were detected from the other borings.

Monitoring well MW-4 was installed on July 15, 1999, located south of the former tank locations along Yerba Buena Avenue. No hydrocarbons were detected in MW-4 at the time of it's installation, however MTBE was reported at a concentration of 37  $\mu$ g/L. The results of on going groundwater monitoring of these four wells is summarized on Tables 2, 2a, 3.

On May 6, 2004, AEI installed one (1) vapor extraction well (VES-1) and two (2) air sparge wells (AS-1 and AS-1). Six (6) shallow vapor monitoring mini-wells (DP-I through DP-6) were installed on May 13, 2004. On May 19 through 20, 2004, AEI carried out a soil vapor extraction and air sparge pilot test. The results of this pilot test and recommendations for remediation are summarized in the AEI August 6, 2005, Soil Vapor Extraction and air sparge extraction Test Report. Installation of the remediation system is planned upon approval of the report recommendations by the ACHCSA, which is still pending.

### LNAPL Removal

Light non-aqueous phase liquid (LNAPL) was reported by the laboratory in samples from monitoring well MW-3 collected on November 18, 1999, but was not present in a measurable thickness until 2004.

On September 9, 2004, 0.66 feet of LNAPL was measured in MW-3. On September 23, 2004, 200 gallons of liquid (water and gasoline) were removed from well MW-3 by Excel

Environmental Services. The liquid was removed by placing a 1-inch PVC stinger into the well and dewatering the well to 17 feet bgs for approximately 90 minutes using a vacuum truck. On September 29, 2004, 0.52 feet of LNAPL was measured in MW-3.

On October 22, 2004, 30 gallons of liquids were removed from MW-3 by extending the 1-inch PVC stinger into the top of the water approximately 6-inches and vacuuming for approximately 1 hour. On October 27, 2004, 0.32 feet of LNAPL was measured in well MW-3.

On November 4 and 23, 2004, 15 gallons of liquid was removed on each visit by vacuuming the surface of the groundwater. LNAPL measurements were on November 6 and 19, 2004 were 0.01 feet and 0.14 feet respectively. At the time of this monitoring event, the LNAPL thickness in MW-3 was 0.05 feet in thickness.

The total amount of LNAPL removed is unknown, LNAPL removal was discontinued when the LNAPL thickness stabilized at a thickness of 0.05 feet.

### **Summary of Monitoring Activities**

AEI measured the depth to groundwater in the four wells (MW-1 to MW-4) on March 11, 2005. The locations of groundwater monitoring wells are shown on Figure 2. Prior to sampling, each well was checked for free product using a bailer. The depth to water from the top of the casing in wells MW-1, 2 and 4 was measured with an electric water level indicator and in Well MW-3 using an electronic air/hydrocarbon/water interface meter. Each well sampled was then purged of at least three well volumes with a submersible pump. Temperature, pH, specific conductivity and oxidation-reduction potential (ORP) were measured during the purging of the wells and turbidity was visually noted. Once water levels had recovered to at least 90% of their original level, a water sample was collected.

The groundwater samples were collected from each well using clean disposable bailers. The water samples were collected into 1-liter amber glass bottles and 40 ml glass volatile organic analysis (VOA) vials. The VOAs were capped so neither headspace nor air bubbles were present within the sample containers. Samples were delivered on ice under proper chain of custody protocol to McCampell Analytical, Inc. of Pacheco, California (Department of Health Services Certification #1644).

Three groundwater samples were submitted for chemical analysis for TPH-g, MTBE, and BTEX by method SW 8021B/8015Cm, and TPH-d by method SW 8015C.

### **Field Results**

LNAPL with a thickness approximately 0.12 feet was present in well MW-3. Groundwater elevations for the current monitoring episode ranged from 34.18 to 37.20 feet above mean sea level (amsl). These groundwater elevations were an average of 1.55 feet lower than the average

level observed during the previous episode. Based on these water level measurements, the direction of the groundwater flow at the time of measurement was towards the northwest with a hydraulic gradient of approximately 0.015 ft/ft. This flow direction and gradient are consistent with previous episodes.

Groundwater elevation data and groundwater sample analytical data are summarized in Tables 2, 2a, and 3. The groundwater elevation contours and the groundwater flow direction are shown on Figure 4. Refer to Appendix A for Groundwater Monitoring Well Field Sampling Forms, which include field measurements and observations made during the monitoring activities.

### **Groundwater Quality**

TPH-g, TPH-d, benzene, and ethylbenzene were detected in MW-1 at 440  $\mu$ g/L, 220  $\mu$ g/L, 26  $\mu$ g/L, and 0.60  $\mu$ g/L, respectively. MTBE, toluene, and xylenes were not detected in MW-1 above laboratory detection limits.

TPH-g, MTBE, and benzene were detected in MW-2 at 1,200  $\mu$ g/L, 12,000  $\mu$ g/L, and 85  $\mu$ g/L, respectively. TPH-d, toluene, ethylbenzene, and xylenes were not detected in MW-2 above laboratory detection limits.

Well MW-3 was not sampled due to the presence of 0.12 feet of LNAPL.

TPH-g, TPH-d and BTEX continued to be at non-detectable concentration is MW-4. MTBE was detected at a concentration of 15 µg/L in MW-4.

Groundwater sample analytical data is presented in Table 3. Historical hydrocarbon concentrations in wells MW-1 and MW-3 are shown in Figures 5 and 6, respectively. Laboratory results and chain of custody documents are included in Appendix B.

### **Summary**

LNAPL continues to be present in the immediate vicinity of MW-3. Significant concentrations of MTBE continue to be present in well MW-2. The MTBE concentration reported in MW-2 during this event represents the highest concentration of MTBE ever reported in MW-2.

Installation of the remediation system is planned as soon as approval is received from the ACHCSA.

#### Recommendations

Based on the current and historical data, AEI recommends the following:

- Continued quarterly monitoring, with the next monitoring event tentatively scheduled for September 2005. To aid in further delineation of the extent of the contamination plume in the vicinity of wells MW-2 and MW-3, AEI recommends that wells DP-1, DP-2, and DP-3 also be sampled, assuming a sufficient volume of water is present to sample. Should in insufficient volume of water be present, these wells may not be purged prior to obtaining samples.
- Removal of free product from MW-3.
- Following removal of LNAPL in well MW-3 and approval from the ACHCSA, installation of the previously recommended air sparge and vapor extraction system.

### Report Limitations and Signatures

This report presents a summary of work completed by AEI Consultants including observations and descriptions of site conditions. Where appropriate, it includes analytical results for samples taken during the course of the work. The number and location of samples are chosen to provide required information, but it cannot be assumed that they are entirely representative of all areas not sampled. All conclusions and recommendations are based on these analyses, observations, and the governing regulations. Conclusions beyond those stated and reported herein should not be inferred from this document.

These services were performed in accordance with generally accepted practices in the environmental engineering and construction field that existed at the time and location of the work.

No. 5825

Sincerely,

**AEI Consultants** 

Yeremy Quick Staff Geologist

MARK

Robert F. Flory, PG Senior Project Geologist

### **Figures**

Figure 1 Site Location Map

Figure 2 Site Plan

Figure 3 Sample Analytical Data Figure 4 Water Table Contours

Figure 5 MW-1 Figure 6 MW-3

### **Tables**


Table 1Well Construction DetailsTable 2Groundwater Elevation DataTable 2aGroundwater Flow DataTable 3Groundwater Analytical Data

### **Appendices**

Appendix A Groundwater Monitoring Well Field Sampling Forms
Appendix B Laboratory Analyses with Chain of Custody Documentation

cc:


Barney Chan ACHCSA 1131 Harbor Bay Parkway, Suite 250 Alameda, CA 94502-6577




# AEI CONSULTANTS SITE LOCATION MAP

1075 40<sup>th</sup> STREET OAKLAND, CALIFORNIA

FIGURE 1 PROJECT NO. 8326








Monitoring Well
Groundwater results are reported in µg/L
TPH-g = Total Petroleum Hydrocarbons as gasoline
TPH-d = Total Petroleum Hydrocarbons as diesel
MTBE = Methyl tertiary-Butyl Ether

BTEX = Benzene, Toluene, Ethylbenzene, and Xylenes

Sampling Event: 6/15/05






### **AEI CONSULTANTS**

2500 CAMINO DIABLO, SUITE 200, WALNUT CREEK, CA

### SAMPLE ANALYTICAL DATA

1075 40TH AVENUE OAKLAND, CALIFORNIA

Figure 3 AEI Project: 8326





Monitoring Well (Water table elevation in feet above mean sea level)

MW-3 (33.88)

\* Free product present, elevation not used to contour groundwater Water table contours drawn by Surfer mapping software

Scale: 1" = 20'





### **AEI CONSULTANTS**

2500 CAMINO DIABLO, SUITE 200, WALNUT CREEK, CA

### WATER TABLE CONTOURS

**1075 40TH AVENUE** OAKLAND, CALIFORNIA

Figure 4 AEI Project: 8326

FIGURE 5 - Fidelity Roof - MW-1




FIGURE 6 - Fidelity Roof - MW-3




Table 1: Well Construction Details
Fidelity Roof Company, 1075 40th Street, Oakland, California

Well ID	Date Drilled	Elevation	Water Depth 12/13/04	Boring Depth	Slotted Casing	Slot Size	Blank Casing	Sand Interval	Sand Size	Bentonite Interval	Grout Interval
		(ft amsl)	(ft)	(ft)	(ft)	(in)	(ft)	(ft)		(ft)	(ft)
MW-1	03/06/97	45.41	6.94	21.0	6-21	0.020	0.5-6	5-21	#3	4-5	0.5-4
MW-2	03/19/97	44.94	9.26	21.0	6-21	0.020	0.5-6	5-21	#3	4-5	0.5-4
MW-3	03/19/97	44.32	8.91	21.0	6-21	0.020	0.5-6	5-21	#3	4-5	0.5-4
MW-4	08/05/99	43.48	5.51	20.0	5-21	0.020	0.55	4-20	#3	3-4	0.5-3
AS-1	05/06/04	45.2 est		30.0	25-30	0.010	0.75-25	22-30	2/12	19-22	1.0-19
AS-2	05/06/04	45.2 est.		30.0	25-30	0.010	0.75-25	22-30	2/12	19-22	1.0-19
VE-1	05/06/04	45.0 est.		10.0	5-10	0.010	0.75-10	4-10	2/12	3-4	1.0-3
DP-1	05/13/04	44.0 est.		16.0	5.5-15.5	# 40 mesh	5.5-0.5	4.5-15.5	#30	3.5-4.5	0.75-3.5
DP-2	05/13/04	44.6 est.		16.0	5.5-15.5	# 40 mesh	5.5-0.5	4.5-15.5	#30	3.5-4.5	0.75-3.5
DP-3	05/13/04	44.7 est.		16.0	5.5-15.5	# 40 mesh	5.5-0.5	4.5-15.5	#30	3.5-4.5	0.75-3.5
DP-4	05/13/04	44.8 est.		16.0	5.5-15.5	# 40 mesh	5.5-0.5	4.5-15.5	#30	3.5-4.5	0.75-3.5
DP-5	05/13/04	45.0 est.		16.0	5.5-15.5	# 40 mesh	5.5-0.5	4.5-15.5	#30	3.5-4.5	0.75-3.5
DP-6	05/13/04	44.3 est.		16.0	5.5-15.5	# 40 mesh	5.5-0.5	4.5-15.5	#30	3.5-4.5	0.75-3.5

Notes:

All well elevations are measured from the top of the casing and

ft amsl = feet above mean sea level

Table 2: Groundwater Elevation Data
Fidelity Roofing, 1075 40th Street, Oakland, California

Well ID	Date	Elevation (ft amsl)	Depth to Water (ft)	Groundwater Elevatio (ft amsl)
MW-1	03/19/97	45.41	8.25	37.16
	06/20/97	45.41	9.10	36.31
	10/08/97	45.41	9.95	35.46
	01/16/98	45.41	7.57	37.84
	08/05/99	45.49	10.16	35.33
	11/18/99	45.49	8.52	36.97
	02/24/00	45.49	7.65	37.84
	05/24/00	45.49	8.47	37.02
	08/29/00	45.49	10.28	35.21
	01/12/01	45.49	8.50	36.99
	04/18/01	45.49	8.77	36.72
	07/27/01	45.49	10.50	34.99
	11/06/01	45.49	10.28	35.21
	02/13/02	45.49	8.47	37.02
	05/14/02	45.49	9.50	35.99
			10.39	35.10
	08/15/02	45.49	9.08	36.41
	11/14/02	45.49		
	02/12/03	45.49	8.36	37.13
	05/16/03	45.49	8.49	37.00
	08/29/03	45.49	9.91	35.58
	12/02/03	45.49	8.88	36.61
	03/08/04	45.49	7.66	37.83
	06/08/04	45.49	9.39	36.10
	09/10/04	45.49	9.95	35.54
	12/13/04	45.49	6.94	38.55
	03/11/05	45.49	7.35	38.14
	06/15/05	45.49	8.29	37.20
MW-2	03/19/97	44.94	8.40	36.54
	06/20/97	44.94	8.85	36.09
	10/08/9 <b>7</b>	44.94	9.80	35.14
	01/16/98	44.94	5.28	39.66
	08/05/99	44.98	9.32	35.66
	11/18/99	44.98	10.20	34.78
	02/24/00	44.98	7.03	37.95
	05/24/00	44.98	8.01	36.97
	08/29/00	44.98	11.07	33.91
	01/12/01	44.98	8,60	36.38
	04/18/01	44.98	8.80	36.18
	07/27/01	44.98	11.10	33.88
	11/06/01	44.98	12.21	32.77
	02/13/02	44.98	7.98	37.00
	05/14/02	44.98	10.48	34.50
	08/15/02	44.98	10.64	34.34
	11/14/02	44.98	11.69	33.29
	02/12/03	44.98 44.98	9.07	35.29
		44.98 44.98	11.25	33.73
	05/16/03		12.19	32.79
	08/29/03	44.98		34.06
	12/02/03	44.98	10.92	
	03/08/04	44.98	8.41	36.57 34.70
	06/08/04	44.98	10.19	34.79
	09/10/04	44.98	10.84	34.14
	12/13/04	44.98	9.26	35.72 37.17
	03/11/05 <b>06/15/05</b>	44.98 <b>44.98</b>	7.81 <b>10.80</b>	37.17 34.18

Table 2: Groundwater Elevation Data Fidelity Roofing, 1075 40th Street, Oakland, California

MW-3         03/19/97         44.32         7.59           10/08/97         44.32         9.98           06/20/97         44.32         8.36           01/16/98         44.32         9.18           08/05/99         44.37         10.56           11/18/99         44.37         10.92           02/24/00         44.37         8.49           05/24/00         44.37         8.42	(ft amsl)  36.73 34.34 35.96 35.14 33.81 33.45 35.88 35.95
10/08/97       44.32       9.98         06/20/97       44.32       8.36         01/16/98       44.32       9.18         08/05/99       44.37       10.56         11/18/99       44.37       10.92         02/24/00       44.37       8.49	34.34 35.96 35.14 33.81 33.45 35.88 35.95
06/20/97       44.32       8.36         01/16/98       44.32       9.18         08/05/99       44.37       10.56         11/18/99       44.37       10.92         02/24/00       44.37       8.49	35.96 35.14 33.81 33.45 35.88 35.95
01/16/98       44.32       9.18         08/05/99       44.37       10.56         11/18/99       44.37       10.92         02/24/00       44.37       8.49	35.14 33.81 33.45 35.88 35.95
08/05/99       44.37       10.56         11/18/99       44.37       10.92         02/24/00       44.37       8.49	33.81 33.45 35.88 35.95
11/18/99 44.37 10.92 02/24/00 44.37 8.49	33.45 35.88 35.95
02/24/00 44.37 8.49	35.88 35.95
	35.95
03/24/00 44.37 6.42	
08/29/00 44.37 12.00	32.37 33.87
01/12/01 44.37 10.50	
04/18/01 44.37 9.50	35.22
07/27/01 44.37 11.61	32.76
11/06/01 44.37 11.73	32.64
02/13/02 44.37 9.36	35.01
05/14/02 44.37 9.00	35.37
08/15/02 44.37 11.72	32.65
11/14/02 44.37 11.28	33.09
02/12/03 44.37 10.17	34.20
05/16/03 44.37 11.47	32.90
08/29/03 44.37 11.92	32.45
12/02/04 44.37 10.96	33.41
03/08/04 44.37 10.49	33.88
06/08/04 44.37 9.89	34.48
09/10/04 44.37 11.54	32.83
12/13/04 44.37 8.96	35.41
03/11/05 44.37 6.99	37.38
06/15/05 44.37 7.72	36.65
MW-4 08/05/99 43.48 8.79	34.69
11/18/99 43.48 8.11	35.37
02/24/00 43.48 5.19	38.29
05/24/00 43.48 7.23	36.25
08/29/00 43.48 9.04	34.44
01/12/01 43.48 6.40	37.08
04/18/01 43.48 7.30	36.18
07/27/01 43.48 9.16	34.32
11/06/01 43.48 9.03	34.45
02/13/02 43.48 6.60	36.88
05/14/02 43.48 7.19	36.29
08/15/02 43.48 8.97	34.51
11/14/02 43.48 7.52	35.96
02/12/03 43.48 6.37	37.11
05/16/03 43.48 6.81	36.67
08/29/03 43.48 8.56	34.92
12/02/03 43.48 6.02	37.46
	37.73
	37.73 35.29
09/10/04 43.48 8.84	34.64
12/13/04 43.48 5.51	37.97
03/11/05 43.48 5.26	38.22
06/15/05 43.48 6.79	36.69

#### Notes Notes

All well elevations are measured from the top of the casing and not from the ground surface ft amsl = feet above mean sea level

Table 2a: Groundwater Flow Data Fidelity Roofing, 1075 40th Street, Oakland, California

Episode	Date	Average Water Table Elevation (ft amsl)	Water Table Elevation Change (ft)	Hydraulic Gradient Flow Direction (ft/ft)
1	03/19/97	36.81		
2	06/20/97	35.58	-1.23	
3	10/08/97	35.52	-0.06	
4	01/16/98	37.55	2.03	
5	08/05/99	34.87	-2.67	
6	11/18/99	35.14	0.27	
7	02/24/00	37.49	2.35	
8	05/24/00	36.55	-0.94	<del></del>
9	08/29/00	33.98	-2.57	NW (0.09)
10	01/12/01	36.08	2.10	W (0.06)
11	04/18/01	36.08	0.00	W (0.02)
12	07/27/01	33.99	-2.09	W (0.02)
13	11/06/01	33.77	-0.22	NW (0.05)
14	02/13/02	36.48	2.71	NW (0.05)
15	05/14/02	35.54	-0.94	N (0.04)
16	08/15/02	34.15	-1.39	W (0.05)
17	11/14/02	4 34.69	0.54	N (0.08)
18	02/12/03	36.09	1.40	NW (0.03)
19	05/16/03	35.08	-1.01	NW (0.06)
20	08/29/03	33.94	-1.14	NW (0.04)
21	12/02/03	35.39	1 <b>.45</b>	NW (0.05)
22	03/08/04	36.50	1. <b>12</b>	NW (0.04)
23	06/08/04	35.17	-1.34	NW (0.02)
24	09/10/04	34.29	-0.88	NW (0.007)
25	12/13/04	36.91	2.63	NW (0.05)
26	03/11/05	37.73	0.81	NW (0.016)
27	06/15/05	36.18	-1.55	## (#.###)

Notes:

ft amsi = feet above mean sea level

Table 3: Groundwater Analytical Data Fidelity Roofing, 1075 40th Street, Oakland, California

Well ID	Date	Depth to Water	ТРНд	TPHd	мтве	Benzene	Toluene	Ethyl- benzene	Xylenes
		,,	EPA Method	SW8015Cm/C		EPA	4 Method SW8	021B	
		(ft)	(us	g/L)			_(ug/L)		
MW - 1	03/19/97	8.25	<50	<50	23	< 0.5	<0.5	<0.5	<0.5
WI W - 1	05/19/97	9.10	1,300	420	14	150	2.1	12	19
	10/08/97	9.95	56	66	5.8	2.8	<0.5	< 0.5	<0.5
	01/16/98	7.57	1,500	910	<33	95	0.72	69	8.4
	08/05/99	10.16	160	63	<15	1.6	<0.5	0.56	1.1
	11/18/99	8.52	79	< <b>5</b> 0	<5.0	<0.5	< 0.5	<0.5	< 0.5
	02/24/00	7.65	300	160	<5.0	14	0.82	3.5	1.6
	05/24/00	8.47	1,300	480	<10	93	<0.5	17	1.6
	08/29/00	10.28	120	<0.5	<5.0	0.93	<0.5	< 0.5	< 0.5
	01/12/01	8.50	360	170	<5.0	16	< 0.5	9.3	0.69
	04/18/01	8.77	1,100	410	2,800	63	<0.5	34	0.73
	07/27/01	10.50	1,100	66	<5.0	1.6	<0.5	< 0.5	< 0.5
	11/06/01	10.28	<50	<50	<5.0	< 0.5	<0.5	<0.5	<0.5
	02/13/02	8.47	430	270	<5.0	17	0.51	11	0.64
	05/14/02	9.50	340	170	<5.0	21	< 0.5	5.3	0.67
	03/14/02	10.39	96	53	<5.0	0.66	<0.5	<0.5	<0.5
		9.08	<50	<50	<5.0 <5.0	< 0.5	<0.5 <0.5	<0.5	· <0.5
	11/14/02		710	120	<5.0	28	4.3	32	130
	02/12/03	8.36		340	<15	20 54	4.1	40	100
	05/16/03	8.49	1,100		<5.0	46	5.1	55	230
	08/29/03	9.91	1,200	280	<5.0 <5.0	<0.5	<0.5	<0.5	< 0.5
	12/02/03	8.88 7.66	<50 120	<50 240 <sup>1,2</sup>	<5.0 <5.0	2.9	<0.5	<0.5	0.71
	03/08/04	9.39	<50	78 <sup>2</sup>	<5.0	<0.5	<0.5	<0.5	<0.5
	06/08/04	9.39 9.95	<50 <50	<50	<5.0	<0.5	<0.5	<0.5	<0.5
	09/10/04 12/13/04	9.93 6.94	240	150	<5.0	11	<0.5	5.6	<0.5
	03/11/05	7.35	1,100	420	<40	43	0.60	12	0.80
	06/15/05	8.29	440	220	<15	26	<0.5	0.60	<0.5
MW - 2	03/19/97	8.40	<50	<50	65	<0.5	<0.5	<0.5	<0.5
	06/23/97	8.85	<50	<50	70	3.4	< 0.5	< 0.5	< 0.5
	10/08/97	9.80	<50	<50	90	<0.5	< 0.5	< 0.5	< 0.5
9	01/16/98	5.28	<50	<50	65	< 0.5	< 0.5	<0.5	< 0.5
	08/05/99	9.32	<50	<50	600	<0.5	<0.5	<0.5	< 0.5
	11/18/99	10.20	<50	<50	370	<0.5	<0.5	< 0.5	< 0.5
	02/24/00	7.03	<50	<50	880	<0.5	<0.5	< 0.5	< 0.5
	05/24/00	8.01	<250	62	2,200	< 0.5	< 0.5	< 0.5	< 0.5
	08/29/00	11.07	<200	<50	1,900	<0.5	<0.5	< 0.5	< 0.5
	01/12/01	8.60	470	70	2,000	8.7	3.1	16	73
	04/18/01	8.80	<50	<50	2,800	<0.5	<0.5	< 0.5	< 0.5
	07/27/01	11.10	<100	<50	3,300	<0.5	< 0.5	< 0.5	< 0.5
	11/06/01	12.21	<100	<50	3,000	< 0.5	< 0.5	< 0.5	< 0.5
÷	02/13/02	7.98	54	<50	3,200	< 0.5	< 0.5	< 0.5	< 0.5
	05/14/02	10.48	<150	<50	3,800	4.8	<1.0	<1.0	<1.0
	08/15/02	10.64	<50	<50	2,900	< 0.5	< 0.5	< 0.5	< 0.5
	11/14/02	11.69	<120	<50	3,800	<1.0	<1.0	<1.0	<1.0
	02/12/03	9.07	1,100	120	3,200	57	7	55	210
	05/16/03	11.25	530	85	6,000	35	3.6	22	79
	08/29/03	12.19	2,400	1200	4,800	39	5.8	77	320
	12/02/03	10.96	<100	<50	3,300	<1.0	<1.0	<1.0	<1.0
	03/08/04	8.41	<250	<50	4,600	<2.5	<2.5	<2.5	<2.5
	06/08/04	10.19	<120	<50	3,400	<1.2	<1.2	<1.2	<1.2
	09/10/04	10.84	<250	<250	4,100	<2.5	<2.5	<2.5	<2.5
	12/13/04	8.41	77	<50	4,200	< 0.5	0.83	< 0.5	1.9
	03/11/05	7.81	120	<50	4,900	14	< 0.5	0.56	< 0.5
	06/15/05	10.80	1,200	<50	12,000	85	<5.0	<5.0	<5.0

Table 3: Groundwater Analytical Data Fidelity Roofing, 1075 40th Street, Oakland, California

Well ID	Date	Depth to	ТРНд	TPHd	MTBÉ	Benzene	Toluene	Ethyl-	Xylenes
		Water	EPA Method	SW8015Cm/C		EPA	Method SW8	benzene 0218	
		(ft)	l	z/L)		231 77	(ug/L)	0212	
		(12)	(2)	1			(//		
MW-3	03/19/97	7.59	26,000	5,000	230	3,000	530	340	2,300
	06/23/97	9.98	25,000	7,000	270	4,400	120	540	1,500
	10/08/97	8.36	17,000	5,100	<280	4,400	47	280	410
	01/16/98	9.18	29,000	7,300	<360	5,600	740	950	3,500
	08/05/99	10.56	31,000	5,100	<200	5,400	150	1100	2,300
	11/18/99	10.92	74,000	49,000	<1,000	8,100	5,000	2,100	8,100
	02/24/00	8.49	110,000	6,300	<200	12,000	1,400	2,900	14,000
	05/24/00	8.42	87,000	26,000	<200	13,000	1,900	2,900	14,000
	08/29/00	12.00	49,000	9,400	<200	7,400	800	1,800	7,400
	01/12/01	10.50	69,000	21,000	<300	8,600	980	2,600	11,000
	04/18/01	9.50	75,000	13,000	<500	9,200	1,200	2,500	12,000
	07/27/01	11.61	75,000	85,000	<650	8,700	1,100	2,600	12,000
	11/06/01	11.73	89,000	86,000	<200	7,900	910	2,800	12,000
	02/13/02	9.36	85,000	13,000	<2,000	8,500	830	2,600	11,000
	05/14/02	9.00	94,000	35,000	<1,000	9,700	1,100	3,400	15,000
	08/15/02	11.72	37,000	9,700	<1,200	5,200	430	1,800	5,900
	11/14/02	11.28	66,000	23,000	<1,200	8,300	860	3,000	11,000 9,800
	02/12/03	10.17	61,000	8,400	<500	6,800	500 320	2,400 2,000	6,500
	05/16/03	11.47	59,000	17,000	<500	6,200	440	2,900	11,000
	08/29/03	11.92	78,000	100,000 46,000	<1,200	6,800 7,600	450	2,900	10,000
	12/02/03	11.32	68,000	160,000	<1,000 <250	7,700	570	300	13,000
	03/08/04	10.49 9.89	79,000 90,000		<1,200	6,700	580	2,500	13,000
	06/08/04 06/08/04	11.54		26,000 ee Product	<1,200	7,600*	540*	3,500*	14,000*
	12/13/04	8.91		oduct = $0.05 \text{ ft}$	~100°	7,000	340	3,300	1-7,000
	03/11/05	6.94		oduct = $0.05 \text{ ft}$	-	-	-	_	_
	06/15/05	7.72		oduct = 0.12 ft	_	_		-	_
	00/15/05	1.72	i i i i i i i i i i i i i i i i i i i	odder o.12 it					
MW-4	08/05/99	8.79	<50	<50	37	<0.5	< 0.5	< 0.5	< 0.5
	11/18/99	8.11	<50	< 50	20	< 0.5	<0.5	<0.5	< 0.5
	02/24/00	5.19	<50	<50	20	< 0.5	< 0.5	<0.5	< 0.5
	05/24/00	7.23	120	140	31	1.3	<0.5	<0.5	< 0.5
	08/29/00	9.04	<50	<50	22	< 0.5	< 0.5	<0.5	<0.5
	01/12/01	6.40	<50	81	25	<0.5	< 0.5	<0.5	< 0.5
	04/18/01	7.30	30	170	35	2.4	1.1	0.66	4.2
	07/27/01	9.16	87	110	26	1.8	< 0.5	2	10
	11/06/01	9.03	200	59	21	4.5	1	5.2	24
	02/13/02	6.60	<50	91	15	< 0.5	< 0.5	<0.5	< 0.5
	05/14/02	7.19	260	140	26	12	2.7	11	49
	08/15/02	8.97	<50	<50	12	< 0.5	<0.5	< 0.5	< 0.5
	11/14/02	7.52	<50	<50	11	< 0.5	< 0.5	<0.5	< 0.5
	02/12/03	6.37	170	130	16	3.1	0.66	6.4	27
	05/16/03	6.81	<50	60	23	< 0.5	<0.5	<0.5	< 0.5
	08/29/03	8.56	610	120	10	16	2.7	30	130
	12/02/03	6.02	<50	<50	7.7	<0.5	< 0.5	<0.5	<0.5
	03/08/04	5.75	<50	<50	10	<0.5	<0.5	<0.5	<0.5
	06/08/04	8.19	<50	<50	11	< 0.5	<0.5	<0.5	<0.5
	09/10/04	8.84	<50	<50	10	< 0.5	< 0.5	<0.5	< 0.5
	12/13/04	5.75	<50	<50	16	< 0.5	< 0.5	<0.5	<0.5
	03/11/05	5.26	<50	<50	16	< 0.5	<0.5	<0.5	<0.5
	06/15/05	6.79	<50	<50	15	<0.5	<0.5	<0.5	<0.5

Notes:

ug/L= micrograms per liter

MTBE= Methyl Tertiary Butyl Ether

TPHg= Total Petroleum Hydrocarbons as gasoline TPHd= Total Petroleum Hydrocarbons as diesel

\* + Analysis by 8260

- 1 gasoline range compounds are significant
- 2 diesel range compounds are significant; no recognizable pattern
- 3 unmodified or weakly modified diesel is significant
- 4 lighter than water immiscible sheen/product is present
- 5- oil range compounds are significant

Project Name:	Fidelity Roof Company	Date of Sampling: 6/15/2005
Job Number:	3119	Name of Sampler: Adrian Nieto
Project Address:	1075 40th Avenue, Oakland	

**Monitoring Well Number:** 

**MW-1** 

MONTORI	NGWELLIDAYA WAREN AND AND AND AND AND AND AND AND AND AN			
Well Casing Diameter (2"/4"/6")	2			
Wellhead Condition	OK ▼			
Elevation of Top of Casing (feet above msl)	45.49			
Depth of Well	21.00			
Depth to Water (from top of casing)	8.29			
Water Elevation (feet above msl)	37.20			
Well Volumes Purged	3			
Calculated Gallons Purged: formula valid only for casing sizes of 2" (.16 gal/ft), 4" (.65 gal/ft), and 6" (1.44 gal/ft)	6.1			
Actual Volume Purged (gallons)	8.0			
Appearance of Purge Water	Clear			
Free Product Present	t? No Thickness (ft): -			

Number of Samples/Container Size					2 40mL VOA, 1 1L				
	Time	Vol Removed (gal)	Temperature (deg C)	pΗ	Conductivity (μ S/cm)	DO (mg/L)	ORP (meV)	Comments	
Meter	Malfunction								
				- <del></del>	!				
		·						-	

Purge water was clear with no noted hydrocarbon or	dor.		
		,	

**Monitoring Well Number:** 

MW-2

Project Name:	Fidelity Roof Company	Date of Sampling: 6/15/2005
Job Number: 3119		Name of Sampler: Adrian Nieto
Project Address:	1075 40th Avenue, Oakland	

MONITORIN	CEWELLDAIA STATEMENT				
Well Casing Diameter (2"/4"/6")	2				
Wellhead Condition	OK ▼				
Elevation of Top of Casing (feet above msl)	44.98				
Depth of Well	21.00				
Depth to Water (from top of casing)	10.80				
Water Elevation (feet above msl)	34.18				
Well Volumes Purged	3				
Calculated Gallons Purged: formula valid only for casing sizes of 2" (.16 gal/ft), 4" (.65 gal/ft), and 6" (1.44 gal/ft)	4.9				
Actual Volume Purged (gallons)	6.0				
Appearance of Purge Water	Initially light-brown, cleared after 1/2 gallon purged				
Free Product Present?	No Thickness (ft): -				

Number of Sam	ples/Container S	Size	Maring P	2 40mL VOA,	1 1L		
Time	Vol Removed (gal)	Temperature (deg C)	рН	Conductivity (μ S/cm)	DO (mg/L)	ORP (meV)	Comments
Meter Malfunction	on					-	
<del></del>							
					"		
<del>-</del>	-			:			<u></u>

Purge water was initially light-	brown, and cleared after 1/2 gallo	on was purged. No noted l	nydrocarbon odor.

Monitoring Well Number:

MW-3

Project Name:	Fidelity Roof Company	Date of Sampling: 6/15/2005
Job Number:	3119	Name of Sampler: Adrian Nieto
Project Address:	1075 40th Avenue, Oakland	

MONINORIA	GWELLONIA
Well Casing Diameter (2"/4"/6")	2
Wellhead Condition	ок
Elevation of Top of Casing (feet above msl)	44.37
Depth of Well	21.00
Depth to Product (from top of casing)	7.60
Depth to Water (from top of casing)	7.72
Water Elevation (feet above msl)	36.65
Well Volumes Purged	3
Calculated Gallons Purged: formula valid only for casing sizes of 2" (.16 gal/ft), 4" (.65 gal/ft), and 6" (1.44 gal/ft)	6.4
Actual Volume Purged (gallons)	6.0
Appearance of Purge Water	Brown with notable sheen
Free Product Present?	Yes Thickness (ft): 0.12

mber of Sample	es/Container S	Size	w."	2 40mL VOA,	1 1L		
Time	Vol Removed (gal)	Temperature (deg C)	pН	Conductivity (μ sec/cm)	DO (mg/L)	ORP (meV)	Comments
	3						
		<u> </u>				,	
				<u> </u>	<del> </del>		

	<u></u>	<u> </u>	 
Three gallons purged by bailer, heavy sheen noted.	-		 
	· · · · · · · · · · · · · · · · · · ·		 

Project Name:	Fidelity Roof Company	Date of Sampling: 6/15/2005
Job Number:	3119	Name of Sampler: Adrian Nieto
Project Address:	1075 40th Avenue, Oakland	

**Monitoring Well Number:** 

MW-4

MONITORIN	IGWELLEDATA TO THE TELEPROPERTY OF THE TELEPRO		
Well Casing Diameter (2"/4"/6")	2		
Wellhead Condition	OK <u>▼</u>		
Elevation of Top of Casing (feet above msl)	43.48		
Depth of Well	20.00		
Depth to Water (from top of casing)	6.79		
Water Elevation (feet above msl)	36.69		
Well Volumes Purged	20		
Calculated Gallons Purged: formula valid only for casing sizes of 2" (.16 gal/ft), 4" (.65 gal/ft), and 6" (1.44 gal/ft)	6.3		
Actual Volume Purged (gallons)	8.0		
Appearance of Purge Water	Cleared quickly		
Free Product Present	P No Thickness (ft): -		

		SR.	(OUNDW)	Alekkane e	5		
Number of Sam	ples/Container S	Size		2 40mL VOA,	1 1L		
Time	Vol Removed (gal)	Temperature (deg C)	pН	Conductivity (μ S/cm)	DO (mg/L)	ORP (meV)	Comments
leter Malfuncti	on					_	
<del></del>							
	<u>:</u>						
<u></u>							<u> </u>

Purge water was initially light-brown, and cleared quickly.	 	 <del></del>	



110 2nd Avenue South, #D7, Pacheco, CA 94553-5560 Telephone: 925-798-1620 Fax: 925-798-1622 Website: www.mccampbell.com E-mail: main@mccampbell.com

AEI Consultants	Client Project ID: #3119; Fidelity Roof	Date Sampled: 06/15/05
2500 Camino Diablo, Ste. #200		Date Received: 06/15/05
Walnut Creek, CA 94597	Client Contact: Peter McIntyre	Date Reported: 06/20/05
Wallitt Cleek, CA 94397	Client P.O.:	Date Completed: 06/21/05

WorkOrder: 0506273

June 21, 2005

Dear Peter:

### Enclosed are:

- 1). the results of 3 analyzed samples from your #3119; Fidelity Roof project,
- 2). a QC report for the above samples
- 3). a copy of the chain of custody, and
- 4). a bill for analytical services.

All analyses were completed satisfactorily and all QC samples were found to be within our control limits. If you have any questions please contact me. McCampbell Analytical Laboratories strives for excellence in quality, service and cost. Thank you for your business and I look forward to working with you again.

Angela Rydelius, Lab Manager



110 2nd Avenue South, #D7, Pacheco, CA 94553-5560 Telephone: 925-798-1620 Fax: 925-798-1622 Website: www.mccampbell.com E-mail: main@mccampbell.com

AEI Consultants	Client Project ID: #3119; Fidelity Roof	Date Sampled: 06/15/05
2500 Camino Diablo, Ste. #200		Date Received: 06/15/05
W. 1 C 1. CA 04507	Client Contact: Peter McIntyre	Date Extracted: 06/17/05-06/18/05
Walnut Creek, CA 94597	Client P.O.:	Date Analyzed: 06/17/05-06/18/05

xtraction n	nethod: SW5030B			Analytical i	nethods: SW80211				Order: 05	
ab ID	Client ID	Matrix	TPH(g)	MTBE	Benzene	Toluene	Ethylbenzene	Xylenes	DF	% SS
001A	MW-I	w	440,a	ND<15	26	ND	0.60	ND	1	90
002A	MW-2	w	1200,a	12,000	85	ND<5.0	ND<5.0	ND<5.0	10	101
003A	MW-4	w	ND	15	ND	ND	ND	ND	1	106
									-	
										+
	· · · · · · · · · · · · · · · · · · ·								-	
									-	<del> </del> <del> </del>
			:							
	·			<u> </u>		T				
	g Limit for DF =1; s not detected at or	W	50	5.0	0.5	0.5	0.5	0.5	1	μд
	he reporting limit	S	NA	NA	NA NA	NA	NA	NA	1	m

<sup>\*</sup> water and vapor samples and all TCLP & SPLP extracts are reported in ug/L, soil/sludge/solid samples in mg/kg, wipe samples in µg/wipe, product/oil/non-aqueous liquid samples in mg/L.

<sup>#</sup> cluttered chromatogram; sample peak coelutes with surrogate peak.

<sup>+</sup>The following descriptions of the TPH chromatogram are cursory in nature and McCampbell Analytical is not responsible for their interpretation: a) unmodified or weakly modified gasoline is significant; b) heavier gasoline range compounds are significant(aged gasoline?); c) lighter gasoline range compounds (the most mobile fraction) are significant; d) gasoline range compounds having broad chromatographic peaks are significant; biologically altered gasoline?; e) TPH pattern that does not appear to be derived from gasoline (stoddard solvent / mineral spirit?); f) one to a few isolated non-target peaks present; g) strongly aged gasoline or diesel range compounds are significant; h) lighter than water immiscible sheen/product is present; i) liquid sample that contains greater than ~1 vol. % sediment; j) reporting limit raised due to high MTBE content; k) TPH pattern that does not appear to be derived from gasoline (aviation gas). m) no recognizable pattern; n) TPH(g) range non-target isolated peaks subtracted out of the TPH(g) concentration at the client's request.



110 2nd Avenue South, #D7, Pacheco, CA 94553-5560 Telephone: 925-798-1620 Fax: 925-798-1622 Website: www.mccampbell.com E-mail: main@mccampbell.com

AEI Consultants	Client Project ID: #3119; Fidelity Roof	Date Sampled: 06/15/05
2500 Camino Diablo, Ste. #200		Date Received: 06/15/05
Walnut Create CA 04507	Client Contact: Peter McIntyre	Date Extracted: 06/15/05
Walnut Creek, CA 94597	Client P.O.:	Date Analyzed: 06/15/05-06/17/05
···		

Diesel Range (C10-C23) Extractable Hydrocarbons as Diesel*  Extraction method: SW3510C Analytical methods: SW8015C Work (										
Lab ID	Client ID	Matrix	TPH(d)	DF	% SS					
0506273-001B	MW-1	w	220,d	1	112					
0506273-002B	MW-2	w	ND	1	111					
0506273-003B	MW-4	w	ND	1	119					
					:					
			· · · · · · · · · · · · · · · · · · ·							
Reporting I	imit for DF =1;	w	50	ц	g/L					
	ot detected at or reporting limit	S	NA	1	٧A					

* water samples are reported in µg/L, wipe samples in µg/wipe, soil/solid/sludge samples	in mg/kg, product/oil/non-aqueous liquid samples in mg/L, an	ıd
all DISTLC / STLC / SPLP / TCLP extracts are reported in µg/L.		

# cluttered chromatogram resulting in cocluted surrogate and sample peaks, or; surrogate peak is on elevated baseline, or; surrogate has been diminished by dilution of original extract.

+The following descriptions of the TPH chromatogram are cursory in nature and McCampbell Analytical is not responsible for their interpretation: a) unmodified or weakly modified diesel is significant; b) diesel range compounds are significant; no recognizable pattern; c) aged diesel? is significant); d) gasoline range compounds are significant; e) unknown medium boiling point pattern that does not appear to be derived from diesel; f) one to a few isolated peaks present; g) oil range compounds are significant; h) lighter than water immiscible sheen/product is present; i) liquid sample that contains greater than ~1 vol. % sediment; k) kerosene/kerosene range/jet fuel range; l) bunker oil; m) fuel oil; n) stoddard solvent/mineral spirit.

Angela Rydelius, Lab Manager



110 2nd Avenue South, #D7, Pacheco, CA 94553-5560 Telephone: 925-798-1620 Fax: 925-798-1622 Website: www.mccampbell.com E-mail: main@mccampbell.com

### QC SUMMARY REPORT FOR SW8021B/8015Cm

W.O. Sample Matrix: Water

QC Matrix: Water

WorkOrder: 0506273

EPA Method: SW8021B/	8015Cm E	xtraction:	SW5030B	ŀ	Batc	hID: 1665	6	Spiked Sample ID: 0506270-003A						
Analyte	Sample	Spiked	MS	MSD	MS-MSD	LCS	LCSD	LCS-LCSD	Acceptance	criteria (%)				
Analyte	μg/L	µg/L	% Rec.	% Rec.	% RPD	% Rec.	% Rec.	% RPD	MS / MSD	LCS / LCSD				
TPH(btex) <sup>£</sup>	ND	60	103	99.8	2.94	102	102	0	70 - 130	70 - 130				
MTBE	ND	10	112	113	0.831	113	116	2.59	70 - 130	70 - 130				
Benzene	ND	10	106	107	1.68	113	113	0	70 - 130	70 - 130				
Toluene	ND	10	107	109	1.62	114	115	0.584	70 - 130	70 - 130				
Ethylbenzene	ND	10	108	110	1.58	114	114	0	70 - 130	70 - 130				
Xylenes	ND	30	110	110	0	117	113	2.90	70 - 130	70 - 130				
%SS:	112	10	98	99	1.03	101	102	1.18	70 - 130	70 - 130				

All target compounds in the Method Blank of this extraction batch were ND less than the method RL with the following exceptions:

NONE

### BATCH 16656 SUMMARY

Sample ID	Date Sampled	Date Extracted	Date Analyzed	Sample ID	Date Sampled	Date Extracted	Date Analyzed
0506273-001A	6/15/05	6/17/05	6/17/05 12:44 AM	0506273-002A	6/15/05	6/17/05	6/17/05 1:14 AM
0506273-002A	6/15/05	6/18/05	6/18/05 2:55 AM	0506273-003A	6/15/05	6/17/05	6/17/05 2:14 AM

MS = Matrix Spike; MSD = Matrix Spike Duplicate; LCS = Laboratory Control Sample; LCSD = Laboratory Control Sample Duplicate; RPD = Relative Percent Deviation.

% Recovery = 100 \* (MS-Sample) / (Amount Spiked); RPD = 100 \* (MS - MSD) / ((MS + MSD) / 2).

MS / MSD spike recoveries and / or %RPD may fall outside of laboratory acceptance criteria due to one or more of the following reasons: a) the sample is inhomogenous AND contains significant concentrations of analyte relative to the amount spiked, or b) the spiked sample's matrix interferes with the spike recovery.

£ TPH(btex) = sum of BTEX areas from the FID.

# cluttered chromatogram; sample peak coelutes with surrogate peak.

N/A = not applicable or not enough sample to perform matrix spike and matrix spike duplicate.

NR = analyte concentration in sample exceeds spike amount for soil matrix or exceeds 2x spike amount for water matrix or sample diluted due to high matrix or analyte content.

MQA/QC Officer



110 2nd Avenue South, #D7, Pacheco, CA 94553-5560 Telephone: 925-798-1620 Fax: 925-798-1622 Website: www.mccampbell.com E-mail: main@mccampbell.com

### **QC SUMMARY REPORT FOR SW8015C**

W.O. Sample Matrix: Water

QC Matrix: Water

WorkOrder: 0506273

EPA Method: SW8015C	E	xtraction:	SW35100	;	Batc	hID: 1665	3	Spiked Sample ID: N/A					
Analyte	Sample	Sample Spiked		MSD	MS-MSD	LCS	LCSD	LCS-LCSD	Acceptance Criteria (				
Analyte	μg/L	µg/L	% Rec.	% Rec.	% RPD	% Rec.	% Rec.	% RPD	MS / MSD	LCS / LCSD			
TPH(d)	N/A	1000	N/A	N/A	N/A	102	102	0	N/A	70 - 130			
%SS:	N/A	2500	N/A	N/A	N/A	108	109	0.740	N/A	70 - 130			

All target compounds in the Method Blank of this extraction batch were ND less than the method RL with the following exceptions:

NONE

### BATCH 16653 SUMMARY

Sample ID	Date Sampled	Date Extracted	Date Analyzed	Sample ID	Date Sampled	Date Extracted	Date Analyzed
0506273-001B	6/15/05	6/15/05	6/17/05 2:46 AM	0506273-002B	6/15/05	6/15/05	6/15/05 11:16 PM
0506273-003B	6/15/05	6/15/05	6/16/05 4:30 PM			,,	

MS = Matrix Spike; MSD = Matrix Spike Duplicate; LCS = Laboratory Control Sample; LCSD = Laboratory Control Sample Duplicate; RPD = Relative Percent Deviation.

% Recovery = 100 \* (MS-Sample) / (Amount Spiked); RPD = 100 \* (MS - MSD) / ((MS + MSD) / 2).

MS / MSD spike recoveries and / or %RPD may fall outside of laboratory acceptance criteria due to one or more of the following reasons: a) the sample is inhomogenous AND contains significant concentrations of analyte relative to the amount spiked, or b) the spiked sample's matrix interferes with the spike recovery.

N/A = not enough sample to perform matrix spike and matrix spike duplicate.

NR = analyte concentration in sample exceeds spike amount for soll matrix or exceeds 2x spike amount for water matrix or sample diluted due to high matrix or analyte content.

M QA/QC Officer

act-0500275

	McCAMPBELL ANALYTICAL INC.																				O	D)	DY RECORD				(A)							
	1	10 2nd AV	ENUE SO O, CA 945	UTH,	#D7									ŢŢ	JR	N.	\R	JO	JNI	ľQ	IN	E								D B HR			□ HR	5 DAY
Telephor	ie: (925) 798		U, CA 743.	J. J 4,14,2 4	F	ax:	(925	798	<b>3-16</b>	22			1,	eti	r d	ont	ılre	49 -	r	٦.	Yes			Ä	ЉН До		24 I	īK.	44	) ILE	•	2.4	III	
			D:	n Ta	: sam		-						╼┼	LIV.	<u> </u>	cqı	ш		Ans				_		<del>7 · ·</del>					Othe	er		Comn	ients
Report To: Peter Company: AEI C				21 A V	· adin											<u></u>																		
	lamino Diat	olo. Suite	200										].	_	ļ	B&		ļ		}	İ		l											
	ut Creek, C.			E-M	ail: p	meir	ityre(	a)aei	cons	altar	ts.c	OID	[		1000	E&F		ľ		Ì			ŀ	8310								-		
Fele: (925) 944-2	899				925)							,		8015/W1BE		220 ]	18.1							/02:								١		
Project#: 31		£ 1 10 £			et Name: Fide lity Rod				٦.	+		Se (5	9	ĺ	(020		73			7.82			ခ					1		,				
Project Location:		401			Ogkland				- 3	Cas (602/8020		Grease (5520 E&F/B&F)	6		2 / 8		S			EPA 625 / 8270 / 8310			100/											
Sampler Signatur	e: K)	VGS_	Me	H.		Γ.				М	ETI	IOD	, ,	3		182	₹		A 60	ĺ	B's						39.2			1		1		
	ĺ	SAMP	LING	2	ners		MAI	(KL)	<b>K</b>	PR	SE	RVE	, a	3	<u>8</u>	Ö	HH	္ဓ	<u>E</u>	۵	30 PC	8	ا ۾	's by	श्च	sq	421/2					1		
SAMPLE ID Field Point Name)	LOCATION	Date	Time	#Containers	Type Containers	Water		Sludge	Other		FŠ	HINO,	Officer	BIEX & TPH as	TPH as Diesel (8015)	Total Petroleum Oil &	Total Petroleum Hydrocarbons (418.1)	EPA: 601 / 8010	BTEX ONLY (EPA 602 / 8020)	EPA 608 / 8080	EPA 608 / 8080 PCB's ONLY	EPA 624 / 8260	EPA 625 / 8270	PAH's / PNA's by	CAM-17 Metals	LUFT 5 Metals	Lead (7240/7421/239.2/6010)	RCI						
				# C	13	W	Soil	Sluc	ŏ	aor	HC		Ö		Ē	直	٦	邑	E	B	Ei	B	B	PA	ਹੋ	וו	2	×			_	4		
MW-1		Glisto		4	7/					X	1		1	47				_				_									$\dashv$	-		
n1w-1.		~ ( <del>6 )1 0</del>			1						λ		۷		x	_	1										ļ		$\sqcup$		4	-		
nw-1				(						$\times^{\!\!\!\!/}$	X		X																	_		-	<del> </del>	
VVIV		t									7				`												ļ	ļ <u>.</u>		$\dashv$	$\dashv$	_		
			-										1															<u> </u>			_	_		
					1	1		-																		,		<u> </u>		$\dashv$				
					<b> </b>								$\neg \Gamma$														_	<u> </u>			$\perp$	_		
			-						<b>†</b>			_	_												<u> </u>			ļ. <u>.</u>			$\bot$			
		<del></del>			1	┞		$\top$	+																									
					<del> </del>	1-		+	<del>                                     </del>				$\neg$	7	_†				-															· .
					1-				+			$\dashv$	1	1	$\neg$															•	1			
<del></del> -					<del> </del>	┢	$\dashv$				$\neg$		_	$\top$																				
					<b> </b>	一			+			+	1	+								-												
					<b></b>		$\dashv$	$\dashv$	+-			+	+	$\dashv$	-		$\dashv$																	
Relinguished By:	Næn	Date:	Time:	19:21	elved B			a/a	//	7		8	1		CE/	 t• `	J	<u></u>		L	·						ATIC	ON_	OAS	oa	₽G	М	ETALS	OTHER
Relinquished By:		Date:	·					. G	OO EA	D C	ON PAC	CE 2	rio Abs Tei	EN				APE COI	PRO NTA	PR INI	IAT. ERS	E,	LAE	<b>3</b>		· ;								
Relinguished By:		I MARCE	A Miles	ACCU	witen E	.1.				DECHLORINATED IN LABPERSERVED IN LAB																								

ナナナ

### **CHAIN-OF-CUSTODY RECORD**

of I

110 Second Avenue South, #D7 Pacheco, CA 94553-5560 (925) 798-1620

WorkOrder: 0506273

ClientID: AEL

Report to:

Peter McIntyre

**AEI Consultants** 2500 Camino Diablo, Ste. #200 TEL:

(925) 283-6000

(925) 283-6121

Walnut Creek, CA 94597

FAX:

ProjectNo: #3119; Fidelity Roof

Bill to:

Requested TAT:

5 days

Diane

All Environmental, Inc.

2500 Camino Diablo, Ste. #200

Walnut Creek, CA 94597

Date Received:

06/15/2005

Date Printed:

06/15/2005

	•																					
				ſ	Requested Tests (See legend below)																	
Sample ID	ClientSampID	Matrix	Collection Date	Hold	1	2	3	4		5	6	7	7	8	9	1	0	11	12	13	14	15
0506273-001	MW-1	Water	06/15/2005		Α	В			7								• •					
0506273-002	MW-2	Water	06/15/2005		Α	В																
0506273-003	MW-3	Water	06/15/2005		Α	В			1													

#### Test Legend:

1 G-MBTEX_W	2 TPH(D)_W	3	4	5
6	7	8	9	10
11	12	13	14	15

Prepared by: Rosa Venegas

#### Comments:

NOTE: Samples are discarded 60 days after results are reported unless other arrangements are made. Hazardous samples will be returned to client or disposed of at client expense.