RECEIVED

9:47 am, Mar 27, 2012

Alameda County

Environmental Health

March 30, 2011

Mr. Mark Detterman Alameda County Environmental Health 1131 Harbor Bay Parkway Alameda, CA 94502

Re: Kerry & Associates - Palace Garage

14336 Washington Avenue San Leandro, California ACEH Case No. RO0000208

Dear Mr. Detterman,

I declare, under penalty of perjury, that the information and/or recommendations contained in the **Fourth Quarter 2011 Groundwater Monitoring Report** are true and correct to the best of my knowledge.

Since cly,

Mr. Jeffrey Kerry



January 27, 2012

Mr. Mark Detterman Alameda County Environmental Health 1000 San Leandro Boulevard, Suite 300 San Leandro, CA 94577

Subject: Fourth Quarter 2011 Groundwater Monitoring Report

Palace Garage

14336 Washington Avenue San Leandro, California ACEH Case No. RO0000208

SFRWQCB LUFT Case No. 01-1133

Dear Mr. Detterman:

On behalf of Kerry & Associates, Closure Solutions, Incorporated (Closure Solutions) has prepared this *Fourth Quarter 2011 Groundwater Monitoring Report* (Report) for the Palace Garage facility (the Site), located at 14336 Washington Avenue, in San Leandro, California (Figure 1).

1.0 SITE BACKGROUND SUMMARY

A 550-gallon gasoline underground storage tank (UST) was removed from the Site in 1991. Subsequent investigations included the installation of three monitoring wells (MW-1 through MW-3) and the drilling of 15 borings (B-1 through B-15). Based on data obtained from the wells and borings, impacted unsaturated-zone soil is confined to the area of the former dispenser pad and UST. The primary groundwater flow direction is toward the southwest.

In December 2002, Professional Service Industries, Inc. (PSI) conducted a soil and groundwater investigation to evaluate the lateral extent of petroleum hydrocarbons in the soil and groundwater at the Site. Borings B-16 and B-17 were advanced to between 20 and 24 feet below ground surface (bgs). Boring B-16 was converted into monitoring well MW-4. Concentrations of total petroleum hydrocarbons as gasoline (TPHg) and gasoline related contaminants were detected only in soil from boring B-17 and groundwater from wells MW-1 and MW-2. The locations of the monitoring wells and soil borings are presented on Figure 2.

Closure Solutions conducted a Sensitive Receptor Survey to identify all water supply wells and sensitive receptors within a 2,000-foot radius of the Site. The closest water supply wells are two industrial wells approximately 450 feet northwest (cross-gradient) of the Site. The closest domestic well is approximately 1,500 feet southeast (cross-gradient) of the Site. The closest

down-gradient well is an irrigation well approximately 1,400 feet southwest of the Site. No surface water bodies were identified within a 2,000 foot radius of the Site. Results of the Sensitive Receptor Survey are presented in the *Sensitive Receptor Survey* report dated August 27, 2008.

Closure Solutions prepared and submitted a *Site Conceptual Model* (SCM) dated September 30, 2008 for the Site. The preparation of the SCM was requested by Alameda County Environmental Health (ACEH) in their letter dated September 2, 2008.

In an email dated June 12, 2009, Mr. Steve Plunkett with the ACEH approved the reduction of groundwater monitoring to a Semi-annual basis conducted in second and fourth quarters. Mr. Plunkett also approved the recommendation to eliminate the fuel oxygenates from the suite of laboratory analytes.

On October 15, 2009, Closure Solutions discussed the Site status with ACEH. Data gaps presented in the SCM and other information that ACEH would require for site closure werre identified. Closure Solutions submitted the *Soil Vapor Probe and Additional Assessment Work Plan* on November 13, 2009 to address the work necessary to move the Site toward closure.

On May 14, 2010, Closure Solutions submitted a letter to the ACEH stating that Closure Solutions intended to proceed with the proposed scope of work pursuant to CCR Title 23, Division 3, Chapter 16, Section 2722 (e) which states "Implementation of the proposed workplan may begin sixty (60) calendar days after submittal, unless the responsible party is otherwise directed in writing by the regulatory agency". On May 21, 2010, the ACEH responded to Closure Solutions' letter of intent via email explaining that the ACEH has been largely precluded from generating letters on cases due to the work load imposed by SWRCB Resolution 2009-0042 and they will attempt to raise the review interval for the Site.

On July 26, 2010, a representative from Closure Solutions was on site to oversee the installation and sampling of three temporary soil vapor probes (SV-1 through SV-3) and advancement of one down-gradient soil boring (SB-18). A *Soil Vapor Testing and Additional Assessment Report* describing field activities and discussing analytical soil and soil vapor results was submitted to the ACEH on August 30, 2010.

In response to the additional assessment report, the ACEH issued a letter on May 18, 2011 requesting the preparation of a work plan for the collection of additional soil and groundwater data and completion of work necessary to undertake corrective actions at the Site.

On July 22, 2011, Closure Solutions submitted an Additional Investigation and Remediation Pilot Test Work Plan.

On October 5, 2011, the ACEH requested a work plan addendum to provide further information and additional clarification to the proposed work scope. A work plan addendum addressing requests from the ACEH was submitted on November 11, 2011 and was conditionally approved on December 15, 2011.

Closure Solutions continues to conduct groundwater monitoring and sampling on a semi-annual basis during second and fourth quarters.

2.0 WORK PERFORMED AND WORK PROPOSED

Following is a summary of work performed this quarter and work proposed for next quarter:

WORK PERFORMED THIS QUARTER:

- 1. Prepared and Submitted Additional Investigation and Remediation Pilot Test Work Plan Addendum on November 11, 2011.
- 2. Performed semi-annual groundwater monitoring event on December 15, 2011.

WORK PROPOSED FOR NEXT QUARTER:

- 1. Conduct well installation and development field activities in January 2012.
- 2. The next groundwater monitoring event will be performed in second quarter 2012.

3.0 DISCUSSION OF RECENT ACTIVITIES

Closure Solutions performed this quarter's groundwater monitoring and sampling event at the Site on December 15, 2011. Gauging, purging and sampling were conducted in accordance with Closure Solution's Standard Operating Procedures (included in Attachment A). The collected groundwater samples were submitted to SunStar Laboratories for laboratory analysis under Chain-of-Custody protocols. The samples were analyzed for gasoline range organics (GRO) and benzene, toluene, ethylbenzene and total xylenes (BTEX) by EPA Method 8260B. Due to a miscommunication, samples MW-1 and MW-3 in addition to MW-2 were analyzed for the following bio-attenuation parameters: ferrous iron by EPA Method 6010, total alkalinity by EPA Method 310.1, and sulfate and nitrate by EPA Method 300.0.

Following is a summary of the current status of the environmental program at the site:

Current Phase of Project:	Monitoring
Groundwater Monitoring & Sampling:	Semi-Annual: MW-1 through MW-4
Is Free Product (FP) Present On-Site:	No
Current Remediation Techniques:	Natural Attenuation

Following is a summary of this quarter's field and analytical data:

4.82
2.06 (MW-4) to 22.82 (MW-1)
outh-southwest
005 feet per foot
5 μg/L (MW-4) to 4,300 μg/L (MW-2)
5 μg/L (MW-3) to 160 μg/L (MW-2)
88 μg/L (MW-1) and 26 μg/L (MW-2)
0 μg/L (MW-3) to 480 μg/L (MW-3)
3 μg/L (MW-4) to 790 μg/L (MW-2)
2

Laboratory procedures, chain of custody records, and the certified analytical reports are included as Attachment B. Groundwater elevation and analytical data are summarized in Tables 1 and 2. Bio-attenuation parameters are summarized in Table 3.

Purge water generated during the monitoring and sampling event was stored onsite pending characterization and disposal.

4.0 CONCLUSIONS AND RECOMMENDATIONS

Closure Solutions submitted Additional Investigation and Remediation Pilot Test Work Plan (dated July 22, 2011) and a Work Plan addendum (dated November 11, 2011) addressing the request for additional soil and groundwater data collection and completion of work necessary to undertake corrective actions at the Site. The proposed work was conditionally approved by ACEH on December 15, 2011. As part of the Work Plan, Closure Solutions has scheduled installation of two additional groundwater monitoring wells for January 24, 2012. Upon completion, the wells will be incorporated into the existing monitoring program and activities for the proposed dual phase extraction pilot test will be initiated.

In accordance with directive received by the ACEH, Closure Solutions will continue the Site groundwater monitoring and sampling on a semi-annual basis during the second and fourth quarters.

We appreciate the opportunity to present this document and trust that it meets with your approval. If you have any questions or concerns, please contact the undersigned at (916) 760-7579 or at mfarris@closuresolutions.com.

Sincerely,

Closure Solutions, Inc.

Matthew Farris, P.G. Project Geologist



ATTACHMENTS:

Figure 1 Site Location Map

Figure 2 Fourth Quarter 2011 Groundwater Monitoring & Sampling Results –

Groundwater Contour Map – December 15, 2011

Table 1 Groundwater Elevation and Analytical Data

Table 2 Fuel Oxygenate & Lead Scavenger Analytical Data


Table 3 Bio-Attenuation Parameters

Attachment A Field Procedures and Field Data Sheets

Attachment B Laboratory Procedures, Certified Analytical Reports and Chain-of-Custody

Records

cc: Mr. Jeff Kerry, Kerry & Associates




REFERENCE: USGS 7.5 MIN QUAD MAP TITLED:SAN LEANDRO, CALIFORNIA DATED: 1959 REV: 1980

FIGURE 1 SITE LOCATION MAP

PALACE GARAGE 14336 WASHINGTON AVENUE SAN LEANDRO, CALIFORNIA



4600 Northgate Boulevard •Suite 230 Sacramento • California • 95834 Phone: (800) 988-7880



⊞ SOIL VAPOR PROBE

SOIL BORING LOCATION LOCATION

- PROPERTY LINE

WELL -ELEV -GRO BENZENE -

D:\Client Drawings\Closure\palace

WELL DESIGNATION
CROUNDWATER FLEVATION (FT.

GROUNDWATER ELEVATION (FT ABOVE MSL)

GRO and BENZENE CONCENTRATIONS (µg/L)

_22.5

GROUNDWATER ELEVATION CONTOURS (FEET ABOVE MEAN SEA LEVEL- NAVD 88)



GROUNDWATER FLOW DIRECTION AND GRADIENT (FT/FT)

NOTES:

1. BASEMAP SOURCE: MORROW SURVEYING, 2/05/03

FOURTH QUARTER 2011 GROUNDWATER MONITORING & SAMPLING RESULTS

GROUNDWATER CONTOUR MAP DECEMBER 15, 2011

PALACE GARAGE 14336 WASHINGTON AVENUE SAN LEANDRO, CALIFORNIA



CLOSURE SOLUTIONS, INC.

4600 Northgate Boulevard • Suite 230 Sacramento • California • 95834 Phone: (800) 988-7880

Table 1
Groundwater Elevation and Analytical Data

Well ID	Date Sampled	Casing Elevation (Feet MSL)	Depth To Water (Feet)	Groundwater Elevation (Feet)	TPHg/ GRO (μg/L)	B (µg/L)	T (μg/L)	E (µg/L)	X (µg/L)
MW-1	12/31/2002	37.59	13.62	23.97	48,000	1,030	2,380	1,690	9,220
	9/22/2006		13.33	24.26	44,000	870	2,200	720	9,700
	12/21/2006		13.94	23.65	17,000	240	980	180	5,000
	3/29/2007		13.71	23.88	2,000	30	85	23	550
	9/27/2007		15.53	22.06	540	14	3.9	44	87
	12/20/2007		15.69	21.90	280	4.3	1.3	15	37
	2/21/2008		13.72	23.87	19,000	300	150	1,100	4,900
	5/15/2008		14.60	22.99	7,200	140	50	370	2,040
	8/7/2008		15.62	21.97	820	13	3.1	44	100
	11/13/2008		16.14	21.45	670	10	2.1	31	110
	6/19/2009		15.15	22.44	1,490	85.8	13.4	164	310
	11/3/2009		15.98	21.61	75	6.0	0.70	12	40.5
	5/4/2010		13.40	24.19	18,000	300	61	880	4,070
	11/8/2010		15.83	21.76	170	4.9	ND<0.50	7.7	24
	4/22/2011		12.34	25.25	3,800	250	48	810	3,260
	12/15/2011		14.77	22.82	1,500	21	0.88	29	4.6

Table 1
Groundwater Elevation and Analytical Data

Well ID	Date Sampled	Casing Elevation (Feet MSL)	Depth To Water (Feet)	Groundwater Elevation (Feet)	$\frac{TPHg/\ GRO}{(\mu g/L)}$	B (µg/L)	T (µg/L)	E (µg/L)	X (µg/L)
MW-2	12/31/2002	37.12	13.38	23.74	1,670	1,030	11.00	23	16.4
	9/22/2006		13.25	23.87	1,800	53	1.40	14	7.5
	12/21/2006		13.89	23.23					
	3/29/2007		13.57	23.55	2,100	51	1.30		4.5
	9/27/2007		15-37	21.75	1,600	58	0.99	12	3.7
	12/20/2007		15.40	21.72	1,500	63	1.1	16	4.9
	2/21/2008		13.60	23.52	710	23	ND<0.50	6.2	1.1
	5/15/2008		14.47	22.65	1,600	84	1.4	28	9.8
	8/7/2008		15.48	21.64	2,100	86	1.6	22	9.0
	11/13/2008		15.99	21.13	2,300	46	1.1	15	4.5
	6/19/2009		15.03	22.09	931	60.1	ND<2.0	30	3.1
	11/3/2009		15.87	21.25	220	22	0.55	9.4	5.05
	5/4/2010		12.92	24.20	950	14	0.57	9.1	13.2
	11/8/2010		15.71	21.41	1,900	45	1.6	44	9.28
	4/22/2011		12.27	24.85	1,400	30	1.2	29	5.78
	12/15/2011		14.86	22.26	4,300	160	26	480	790

Table 1
Groundwater Elevation and Analytical Data

Well ID	Date Sampled	Casing Elevation (Feet MSL)	Depth To Water (Feet)	Groundwater Elevation (Feet)	TPHg/ GRO (µg/L)	B (µg/L)	T (µg/L)	E (µg/L)	X (µg/L)
MW-3	12/31/2002	37.01	13.29	23.72	< 50	< 0.5	< 0.5	< 0.5	<1.0
	9/22/2006		13.14	23.87	< 50	< 0.5	< 0.5	< 0.5	<1.5
	12/21/2006								
	3/29/2007		13.47	23.54	< 50	< 0.5	< 0.5	< 0.5	<1.5
	9/27/2007		15.29	21.72	ND<50	ND<0.50	ND<0.50	ND<0.50	ND<0.50
	12/20/2007		15.30	21.71	ND<50	ND<0.50	ND<0.50	ND<0.50	ND<0.50
	2/21/2008								
	5/15/2008		14.35	22.66	ND<50	ND<0.50	ND<0.50	ND<0.50	ND<1.0
	8/7/2008		15.39	21.62	ND<50	ND<0.50	ND<0.50	ND<0.50	ND<0.50
	11/13/2008		15.90	21.11	ND<50	ND<0.50	ND<0.50	ND<0.50	ND<0.50
	6/19/2009		14.94	22.07	ND<50	ND<1.0	ND<1.0	ND<1.0	ND<2.0
	11/3/2009		15.76	21.25	ND<50	ND<0.50	ND<0.50	ND<0.50	ND<1.0
	5/4/2010		13.20	23.81	ND<50	ND<0.50	ND<0.50	ND<0.50	ND<1.5
	11/8/2010		15.62	21.39	ND<50	ND<0.50	ND<0.50	ND<0.50	ND<1.5
	4/22/2011		12.17	24.84	ND<50	ND<0.50	ND<0.50	ND<0.50	ND<1.5
	12/15/2011		14.63	22.38	150	1.5	ND<0.50	3.0	12.2

Table 1
Groundwater Elevation and Analytical Data

Well ID	Date Sampled	Casing Elevation (Feet MSL)	Depth To Water (Feet)	Groundwater Elevation (Feet)	TPHg/ GRO (μg/L)	B (µg/L)	T (µg/L)	E (µg/L)	X (μg/L)
MW-4	12/31/2002	37.09	13.45	23.64	< 50	< 0.5	< 0.5	< 0.5	<1.0
	9/22/2006		13.40	23.69	< 50	< 0.5	< 0.5	< 0.5	<1.5
	12/21/2006		13.86	23.23	< 50	< 0.5	< 0.5	< 0.5	<1.5
	3/29/2007		13.69	23.40	< 50	< 0.5	< 0.5	< 0.5	<1.5
	9/27/2007		15.48	21.61	ND<50	1.5	ND<0.50	0.71	0.74
	12/20/2007		15.28	21.81	ND<50	ND<0.50	ND<0.50	ND<0.50	ND<0.50
	2/21/2008		13.56	23.53	ND<50	ND<0.50	ND<0.50	ND<0.50	ND<1.0
	5/15/2008		14.58	22.51	ND<50	ND<0.50	ND<0.50	ND<0.50	ND<1.0
	8/7/2008		15.57	21.52	ND<50	ND<0.50	ND<0.50	ND<0.50	ND<0.50
	11/13/2008		16.09	21.00	ND<50	ND<0.50	ND<0.50	ND<0.50	ND<0.50
	6/19/2009		15.15	21.94	ND<50	ND<1.0	ND<1.0	ND<1.0	ND<2.0
	11/3/2009		16.03	21.06	ND<50	ND<0.50	ND<0.50	ND<0.50	ND<1.0
	5/4/2010		13.11	23.98	ND<50	ND<0.50	ND<0.50	ND<0.50	ND<1.5
	11/8/2010		15.89	21.20	ND<50	ND<0.50	ND<0.50	ND<0.50	ND<1.5
	4/22/2011		12.40	24.69	ND<50	ND<0.50	ND<0.50	ND<0.50	ND<1.5
	12/15/2011		15.03	22.06	86	ND<0.50	ND<0.50	ND<0.50	1.3

Table 1 Groundwater Elevation and Analytical Data

Palace Garage 14336 Washington Avenue San Leandro, California

Well Date Casing Depth To Groundwater TPHg B T E X ID Sampled Elevation Water Elevation $(\mu g/L)$ $(\mu g/L$	Well ID
--	------------

ABBREVIATIONS:

TPHg/ GRO total petroleum hydrocarbons as gasoline. Gasoline range organics

- T Toluene
- E Ethylbenzene
- X Total xylenes
- μg/L Micrograms per liter (parts per billion [ppb])
- --- Not analyzed/measured/applicable
- ND< Not detected at or above specified laboratory reporting limit
- **Bold** Current sampling event
- MSL mean sea level

LIMITATIONS:

Background information, including but not limited to previous field measurements, analytical results, Site plans, and other data have been obtained from previous consultants, and/or third parties, in the preparation of this report. Closure Solutions has relied on this information as furnished. Closure Solutions is not responsible for, nor has it confirmed the accuracy of data collected or generated by others.

Table 2
Fuel Oxygenate & Lead Scavenger Analytical Data

Well ID	Date Sampled	MTBE (μg/L)	TBA (μg/L)	DIPE (µg/L)	ETBE (µg/L)	TAME (μg/L)	1,2-DCA (μg/L)	EDB (µg/L)
MW-1	12/31/2002	<0.5						
	9/22/2006	<1.0						
	12/21/2006	3.9						
	3/29/2007	<1.0						
	9/27/2007	1.6	ND<5.0	ND<0.50	ND<0.50	ND<0.50	ND<0.50	ND<0.50
	12/21/2007	1.5	ND<5.0	ND<0.50	ND<0.50	ND<0.50	ND<0.50	ND<0.50
	2/21/2008	ND<7.0	ND<40	ND<7.0	ND<7.0	ND<7.0	ND<7.0	ND<7.0
	5/15/2008	ND<2.5	ND<15	ND<2.5	ND<2.5	ND<2.5	ND<2.5	ND<2.5
	8/7/2008	1.0	ND<5.0	ND<0.50	ND<0.50	ND<0.50		
	11/13/2008	1.1	ND<5.0	ND<0.50	ND<0.50	ND<0.50		
MW-2	12/31/2002	<0.5						
	9/22/2006	<1.0						
	12/21/2006							
	3/29/2007	1.10						
	9/27/2007	0.89	ND<5.0	ND<0.50	ND<0.50	ND<0.50	ND<0.50	ND<0.50
	12/20/2007	0.95	ND<5.0	ND<0.50	ND<0.50	ND<0.50	ND<0.50	ND<0.50
	2/21/2008	ND<0.50	ND<5.0	ND<0.50	ND<0.50	ND<0.50	ND<0.50	ND<0.50
	5/15/2008	ND<0.90	ND<5.0	ND<0.90	ND<0.90	ND<0.90	ND<0.90	ND<0.90
	8/7/2008	0.59	ND<5.0	ND<0.90	ND<0.90	ND<0.90		
	11/13/2008	0.53	ND<5.0	ND<0.50	ND<0.50	ND<0.50		

Table 2
Fuel Oxygenate & Lead Scavenger Analytical Data

Well ID	Date Sampled	MTBE (μg/L)	TBA (μg/L)	DIPE (µg/L)	ETBE (µg/L)	TAME (μg/L)	1,2-DCA (μg/L)	EDB (µg/L)
MW-3	12/31/2002	<0.5						
	9/22/2006	<1.0						
	12/21/2006							
	3/29/2007	<1.0						
	9/27/2007	ND<0.50	ND<5.0	ND<0.50	ND<0.50	ND<0.50	ND<0.50	ND<0.50
	12/20/2007	ND<0.50	ND<5.0	ND<0.50	ND<0.50	ND<0.50	ND<0.50	ND<0.50
	2/21/2008							
	5/15/2008	ND<0.50	ND<5.0	ND<0.50	ND<0.50	ND<0.50	ND<0.50	ND<0.50
	8/7/2008	ND<0.50	ND<5.0	ND<0.50	ND<0.50	ND<0.50		
	11/13/2008	ND<0.50	ND<5.0	ND<0.50	ND<0.50	ND<0.50		
MW-4	12/31/2002	<0.5						
	9/22/2006	<1.0						
	12/21/2006	<1.0						
	3/29/2007	<1.0						
	9/27/2007	ND<0.50	ND<5.0	ND<0.50	ND<0.50	ND<0.50	ND<0.50	ND<0.50
	12/20/2007	ND<0.50	ND<5.0	ND<0.50	ND<0.50	ND<0.50	ND<0.50	ND<0.50
	2/21/2008	ND<0.50	ND<5.0	ND<0.50	ND<0.50	ND<0.50	ND<0.50	ND<0.50
	5/15/2008	ND<0.50	ND<5.0	ND<0.50	ND<0.50	ND<0.50	ND<0.50	ND<0.50
	8/7/2008	ND<0.50	ND<5.0	ND<0.50	ND<0.50	ND<0.50		
	11/13/2008	ND<0.50	ND<5.0	ND<0.50	ND<0.50	ND<0.50		

Table 2 Fuel Oxygenate & Lead Scavenger Analytical Data

Palace Garage 14336 Washington Avenue San Leandro, California

Well	Date	MTBE	TBA	DIPE	ETBE	TAME	1,2-DCA	EDB
ID	Sampled	$(\mu g/L)$						

ABBREVIATIONS:

Methyl Tertiary Butyl Ether
Tertiary Butyl Alcohol
Diisopropyl Ether
Ethyl Tertiary Butyl ether
Tertiary Amyl Methyl Ether
1,2-Dichloroethane
1,2-Dibromoethane
Micrograms per liter (parts per billion [ppb])
Not analyzed/measured/applicable
Not detected at or above specified laboratory reporting limit

LIMITATIONS

Background information, including but not limited to previous field measurements, analytical results, Site plans, and other data have been obtained from previous consultants, and/or third parties, in the preparation of this report. Closure Solutions has relied on this information as furnished. Closure Solutions is not responsible for, nor has it confirmed the accuracy of data collected or generated by others.

Table 3 Bio-Attenuation Parameters

Palace Garage 14336 Washington Avenue San Leandro, California

Well ID	Date Sampled	Dissolved Oxygen (mg/L)	Alkalinity (pH) (mg/L)	Sulfate (mg/L)	Nitrate (mg/L)	Ferrous Iron (mg/L)
MW-1	12/15/2011	1.23	420	23.4	18.9	0.352
MW-2	12/15/2011	1.86	370	53.8	44.0	ND<0.100
MW-3	12/15/2011	1.23	200	37.2	42.3	ND<0.100
MW-4	12/15/2011	3.93				

ABBREVIATIONS:

mg/L Milligrams per liter

--- Not analyzed/measured/applicable

ND< Not detected at or above specified laboratory reporting limit

Attachment A

Field Procedures and Field Data Sheets



Standard Operating Procedures: Basic Gauge, Purge, and Sample.

Routine Water Level Measurements

- 1. Confirm that water or debris will not enter the well box upon removal of the well box lid.
- **2.** Remove the cover using the appropriate tools.
- **3.** Inspect the wellhead for deficiencies and document accordingly.
- **4.** Confirm that water or debris will not enter the well upon removal of the well cap.
- **5.** Unlock and remove the well cap lock (if applicable). If lock is not functional cut it off.
- **6.** Loosen and remove the well cap. CAUTION: DO NOT PLACE YOUR FACE OR HEAD DIRECTLY OVER WELLHEAD WHEN REMOVING THE WELL CAP. WELL CAP MAY BE UNDER PRESSURE AND/OR MAY RELEASE ACCUMULATED AND POTENTIALLY HARMFULL VAPORS.
- 7. Verify and identify survey point as written on S.O.W.

TOC: If survey point is listed as Top of Casing (TOC), look for the exact survey point in the form of a notch or mark on the top of the casing. If no mark is present, use the north side of the casing as the measuring point.

TOB: If survey point is listed as Top of Box (TOB), the measuring point will be established manually. Place the inverted well box lid halfway across the well box opening and directly over the casing. The lower edge of the inverted cover directly over the casing will be the measuring point.

- **8.** Put new Nitrile gloves on your hands.
- **9.** Slowly lower the decontaminated water level meter probe into the well until it signals contact with water with a tone and/or flashing a light.
- 10. Gently raise the probe tip slightly above the water and hold it there. Wait momentarily to see if the meter emits a tone, signaling rising water in the casing. Gently lower the probe tip slightly below the water. Wait momentarily to see if the meter stops emitting a tone, signaling dropping water in the casing. Continue process until water level stabilizes indicating that the well has equilibrated.
- 11. While holding the probe at first contact with water and the tape against the measuring point, note depth. Repeat twice to verify accuracy. Write down measurement on well gauging sheet under depth to water column.
- **12.** Recover probe, replace and tighten well cap, replace lock (if applicable), replace well box cover and tighten hardware (if applicable).

Purging With a Bailer (Teflon or Disposable)

- **1.** Attach bailer cord or string to bailer. Leave other end attached to spool.
- **2.** Gently lower empty bailer into well until well bottom is reached.
- **3.** Cut cord from spool. Tie a loop at end cord.
- **4.** Gently raise full bailer out of well and clear of wellhead. Do not let the bailer or cord touch the ground.
- **5.** Pour contents into graduated 5-gallon bucket or other graduated receptacle.
- **6.** Repeat purging process.
- 7. Upon removal of first casing volume, fill clean parameter cup with purge water, empty the remainder of the purge water into the bucket, lower the bailer back into the well and secure the cord on the Sampling Vehicle.
- **8.** Use the water in the cup to collect and record parameter measurements.
- **9.** Continue purging until second casing volume is removed.

- **10.** Collect parameter measurements.
- 11. Continue purging until third casing volume is removed.

Purging With a Fixed Speed Electric Submersible Pump

- **1.** Position thoroughly decontaminated pump over the top of the well.
- **2.** Gently unreel and lower the pump to the well bottom.
- **3.** Raise the pump to client specified location within screened interval. If no direction is given the pump inlet will be placed 5 feet above the bottom of the well.
- **4.** Secure the hose reel.
- 5. Begin purging.
- **6.** Verify pump rate with flow meter or graduated 5-gallon bucket.
- 7. Upon removal of first casing volume, fill clean parameter cup with water.
- **8.** Use the water in the cup to collect and record parameter measurements.
- **9.** Continue purging until second casing volume is removed.
- 10. Collect parameter measurements.
- 11. Continue purging until third casing volume is removed.
- **12.** Upon completion of purging, gently recover the pump and secure the reel.

Sampling with a Bailer (Teflon or Disposable)

- **1.** Put new Latex or Nitrile gloves on your hands.
- 2. Determine required bottle set.
- **3.** Fill out sample labels completely and attach to bottles.
- **4.** Arrange bottles in filling order and loosen caps (see Determine Collection Order below).
- **5.** Attach bailer cord or string to bailer. Leave other end attached to spool.
- **6.** Gently lower empty bailer into well until water is reached.
- **7.** As bailer fills, cut cord from spool and tie end of cord to hand.
- **8.** Gently raise full bailer out of well and clear of wellhead. Do not let the bailer or cord touch the ground. If a set of parameter measurements is required, go to step 9. If no additional measurements are required, go to step 11.
- **9.** Fill a clean parameter cup, empty the remainder contained in the bailer into the sink, lower the bailer back into the well and secure the cord on the sampling vehicle. Use the water in the cup to collect and record parameter measurements.
- **10.** Fill bailer again and carefully remove it from the well.
- **11.** Slowly fill and cap sample bottles. Fill and cap volatile compounds first, then semivolatile, then inorganic (see following steps). Return to the well as needed for additional sample material.
- **12.** Fill 40-milliliter vials for volatile compounds as follows: Slowly pour water down the inside on the vial. Carefully pour the last drops creating a convex or positive meniscus on the surface. Gently screw the cap on eliminating any air space in the vial. Turn the vial over, tap several times and check for trapped bubbles. If bubbles are present, repeat the process.
- **13.** Fill 1 liter amber bottles for semi-volatile compounds as follows: Slowly pour water into the bottle. Leave approximately 1 inch of headspace in the bottle. Cap bottle.
- **14.** Field filtering of inorganic samples using a disposable bailer is performed as follows: Attach 0.45 micron filter to connector plug. Attach connector plug to bottom of full disposable bailer. Gravity feed water through the filter and into the sample bottle. If high turbidity level of water clogs filter, repeat process with new filter until bottle is filled. Leave headspace in the bottle. Cap bottle.
- 15. Bag samples and place in ice chest.
- **16.** Note sample collection details on well data sheet and Chain of Custody.

FIELD DATA SHEET-DEPTH TO WATER DATA

			NTE INFORMA	TION		
			SITE INFORMA	ATION		
Site Information		12/16/11				
Palace Garage Project Name		Date	Project Number	.		
14336 Washington	Ave	San Leandro	CA	. Pro ₹		
Address		City	State			
Water Level Equipme	nt		Kevin Dolan_			;
x Electronic Indicator		•	100111 201211			
Oil Water Interface			Event:	4Q 2011 QM	c	
175	Probe	-	CAGUE	-1 Q 2011 QM	<u> </u>	
Other (specify)		- Dr	DTU TO WATE	D DATA		
		DE	PTH TO WATE	RUAIA		
					7	
11		i	DTW	Total Depth	Depth to SPH /	
DTW Order	Well ID	Time (24:00)	(toc)	(toc)	Thickness	Notes:
3	WW-1	1412	14,77	23,25		
4	MW-2	1420	14.86	23-64		
2	MW-3	1406	14,63	23.06		
			15.03	21.85		
1	MW-Y	1353	10103	21103	 	2/19 (0 = 16/2)
<u> </u>					<u> </u>	34" weu = (0.0419F)
II						
				1		
		 				
[
 					 	
<u> </u>					<u> </u>	
	ļ					
į į	ł					
		·				- water Stored
	† 				 	in drive may so
 		Section 1			 	PAU In
		0.55				- Water Stored in drum onsite? Back Lot Whom:HAZ label-
<u> </u>	, ,	y to			 	non-HAZ
<u> </u>	į		No.			label -
!	Í		1			
					†	
II	 	 		 	 	
]	 	 			 	
 			*.		 	
		(3)				<u> </u>

Project Nar	ne:	Palace	Garage				Date:	15 December-5, 2011	1
Sample No.		MW-1							_
Samplers N	lame:	Kevin Dolan					•		
Purge Equi	pment: Bailer: Dis _l 12 v. Pump Bladder Pu	posable or Acryli - mp	ic				Sample Equ	_ Disposable Bailer _ Whaler # _ Bladder Pump	
	SS Monsoc		mmhe\e				Numb	Submersible Pump	
		circle all that a ate, sulfate, fer			41	ionis	W/ Her	per and Types of Bo	ittle Usea:
	nity in 2" w		1045 11011,			Spp w		tic	
Well Number Depth to W	•	14,77	TOC			We	ell Diameter:	<u>2 </u>	
Well Depth	;	23.25	BGS or TOC					4" = (0.65 G	allon/Feet)
Height W-C	Column:		feet (well dep	th - depth	to water)			5" = (1.02 G	allon/Feet)
Volume in \	•	1,35	gallons (casir	•	•			6" = (1.47 G	
Gallons to	purge:	4.07	gallons (volu	_	· ·			8" = (2.61 G	•
Lab:	SunStar		, ,	,		Transpo	rtation:		
	Volume								
Time (24 hr.)	Purged (Gallons)	Temperature (°C)	Conductivity (ms/cm)—	D.O. (ppm)	pН	TDS (ppm)	-Turbidit	y: Color - Fines	Micropurge Paramaters Stebilized
1533	Shae	T						2787	
	15	18.1	,798	210	7.45		12.	1000	
1535			-		7.40			lear, min	╅──┤
1537	3,-	17.6	,791	1.78	7,36		100	1	-
1534	4.5	17:3	1786	123	732		93	VV	
Shr.	pure co	molele		} 					
]			
			,			,			
				· · · · · · · · · · · · · · · · · · ·		y- '			
		1/52		63:			-		
<u> </u>		Wa	it for 80% we	il volume	recovery	orior to s	ampling		<u>.</u> 34. 34.
			depth to water						
			Calc	ulate 80% of	orginal well vo	lume:	V.C		A CONTRACTOR OF THE CONTRACTOR
	Origin	al Height of Water C			-		n 23.25	Denth to Water 16	lb ·
			102		<u> </u>			mental and the second	10
Time:Time:	1st measured	depth to water, depth to water, depth to water,	feet be	low TOC. low TOC. low TOC.		is well with	nin 80% of origina	al well casing volume: Yes al well casing volume: Yes al well casing volume: Yes	: No_:
, , , , , , , , , , , , , , , , , , ,	. 100 1100000100	dopin to water,				15 WOII WILL	in con or origina	ii well casing volume. Tes	
				Sam	ple Well				
Time:	1549	-	Sample ID:		mw-	1	_ Depti	14.83	
Comments	:	Shaht	Hz od	en	-WO	Sneed	1		ď
Well Condi	tion: Q	los/							
TYCH COHOL	U.S.I.			· · · · · · · · · · · · · · · · · · ·	· · · · · · · · · · · · · · · · · · ·				
					· · · · · ·		Closure So	olutions INC QMS	FDS

Project Na	me:	Palace	Garage				Date:	Decembe	1 2011	
Sample No):	N	W-2							
Samplers I	Name:	Kevin Dolan					_			
Purge Equ	ipment: Bailer: Dis 12 v. Pump Bladder Pu SS Monsoc	posable or Acryl - mp on #					X	_ Disposable _ Whaler # Bladder Pi _ Submersit	ump ole Pump	tlo l load:
					u v	male	Wumi	berand typ	es or bot	tie Usea:
					3	500 V	mi Plas	tic		
14(-11 No)		nic) o				344			0 - 1 14	
Depth to W Well Depth Height W-0	Vater: 1: Column:	14.86 23.64 8.78	,	•	=	VV	eli Diameter:	2" = 4" = 5" =	: (0.16 Ga : (0.65 Ga : (1.02 Ga	illon/Feet) illon/Feet) illon/Feet)
	'			_	v Height)				•	•
Lab:	,	9100	ganons (volu	ile V 3)		Transpe	włatian:	0 -	- (2.6) Ga	.llon/reet/
Lau.						nanspe	Tauon.			
Time (24 hr.)	Purged (Gallons)	Temperature (°C)	(ms/cm)	D.O. (ppm)	ρН	TDS (ppm)	Turbidi	ty: Color - F	ines	Micropurge Paramaters Stabilized
1609	StA	W								
1611	1.5	20.6	789	2.14	7.39		98; clear, mn			
1613	3	2013	781	2.01	1,35		90	4 ′	j	 -
1615	4.5	2011	773	1.86	7,28		83'.	V	V	
Stol	Puse	Conpl	ex		1	ľ				
								-		
					-	 	<u> </u>			
	/				·		<u> </u>			
	1/6			<u> </u>	<u> </u>	 	<u> </u>			
	L K	<u> </u>	11.5	<u> </u>	` <u> </u>	<u> </u>	<u> </u>			
								y:		
			Calo	culate 80% of	orginal well vo	iume:				
	Origin	al Height of Water C	olumn = 8.7	8 x 0.8 =	7.02	- (Well Dept	in 23/64=	Depth to water	16.6) (
Time: 1626 Time:	_ 1st measured	depth to water,	feet be	low TOC. low TOC.	ple Well	is well with	hin 80% of origina	al well casing vo	olume: Yes _	No No No
Time:	plers Name: Kevin Dolan Baller: Disposable or Acrylic Baller: Disposable Bailer Baller: Disposable or Acrylic Liv. Pump Bladder Pump SS Monscon # Bladder Pump SS Monscon # Bladder Pump Submersible Pump Number and Types of Bottle Used: Hof JETX (nitrate, sulfate, ferrous Iron, blad. Ad alkalinity in 2" wells) Number: Just Bos or TOC Well Diameter: 2" with Casing Volume of: th to Water: Just Bos or TOC A" = (0.16 Gallon/Feet) Just Bos or TOC A" = (0.65 Gallon/Feet) Just Bos or TOC J									
Comment	. 11	12000 101	الم ما							
Comments	·. 1/L	Marile,	TL OO	<u> </u>		·				
Well Cond	ition: 🖓	ood:								
	<u> </u>						Clasura C	alutiona INC	CMC	EDe
							Closure St	JULI 2001 BL	WIVIO	ruo .

Project Nar	me:	Palace	Garage	400			Date: De	cember 5 , 2011	
Sample No	.:	MW-2	>						
Samplers N	lame:	Kevin Dolan					,		
Purge Equi	ipment:								
		•	С			,			
						,			
			nalv):			•			tle Used:
Well Numb	———— ег:	MWCZ	7		We	II Diameter: 2"	with Casing Vo	olume of:	
Depth to W	/ater:	14,63							
-	•	73.00						•	-
-				th - death	to water)			*'	•
_			•	-	•			•	•
	•		. –	_	X (loight)				_
		7105	galions (volui	ne x 3)		T	-4-4!	0 - (2.01 Ga	monreed
Lab:						Transpo	rtation:		
Time		Temperature	Conductivity	D.O.	, nù	TDS	Turbidity: C	vlor - Fines	Micropurge
(24 hr.)	(Gallons)	(°C)	(ms/cm)	(ppm)	ρ, τ ————————————————————————————————————	(ppm)	Tarblaity. Of		Stabilized
1504	STAR								
1506	15	18.4	,733	7147	630		-10: clea	R, min	
150%	3			ľ			1	1 1	
							1		
20.00	Pures	Complete							
									
	 								
	/								1
 	1/15	7 -				ļ. — - —		-	
	<u> </u>	18/0	it for 909/ wa	ii volume					ــــــــــــــــــــــــــــــــــــــ
			Calc	ulate 80% of	orginal well vo	olume:			
	Origin	al Height of Water C			_		h) <i>23,06</i> <u>De</u> pti	to water 16.3	2 .
- 1500)	de attribute and a	415						X
							_	-	
Time:			feet bei	ow TOC.					No
	Ample No.: MW 3 Sample No.: MW 3 Sample No.: MW 3 Sample No.: MW 4 Sample No.: MW 4 Sample No.: MW 5 Sample Sequipment: Baller: Disposable or Acrylic X 12 v. Pump - Bladder Pump SS Monsoon # Solonseaded (circle all that apply): North-GJ BTEX (nitrate, sulfate, ferrous iron, and alkalinity in 2" wolts) Mell Number: MW 5 Sept to Water: MW 6 Sept to Water: MW 6 Sellon/Feet) Mell Depth: 4" = (0.65 Gallon/Feet) Mell Depth: 4" = (0.65 Gallon/Feet) Mell Depth: 6" = (1.07 Gallon/Feet) Mell Depth: 6" =								
1	1521		Comple ID:	i	1/41-2		Danth	1425	
# ime:	1301		Sample ID:		- W 3		Deptn:	1-1000	
Comments	: <u> </u>	so ador - N	OSNEEU	· · · · · · · · · · · · · · · · · · ·	 				
· · · · · · · · · · · · · · · · · · ·									
Well Condi	tion: 💋	<u>sad</u>							
									

Project Nat							Date: Dec	/5 ember奪2011		
Sample No	.:	MW	-4							
Samplers N	iame:	Kevin Dolan								
Purge Equi	ipment:						Sample Equipmen	nt:		
		posable or Acryli	ic					osable Bailer		
	12 v. Pump		$ve \omega ^3/8tnt$	e				aler#		
	Bladder Pu SS Monsoc		• -		11.	•		lder Pump mersible Pump		
		circle all that a	pply):		•			d Types of Bot	tle Used:	
					Ų,	vortis	w/ Her			
and alkali	inity in 2" v	rells)								
Well Numb		#\W-U				We	II Diameter: 3/1	with Casing Vo	olume of	
			TOC		<i>Y</i> .		,	00 (0.40.0		
•			•		•	2	/4"=(0.041)	•	•	
-				th danth	to water					
•					-				•	
- * - *								•	-	
							4-6	6" = (2.61 Ga	llion/Feet)	
Lab:	ab: SunStar					ranspo	rtation:			
Time		Temperature	Conductivity	D.O.	I I	TDS	Turkidika Cal	las Finas	Micropurge	
(24 hr.)		(°C)	(ms/cm)	(ppm)	þπ	(ppm)	Turbidity: Coi	or - rines	Stabilized	
1432		ac							-	
1434							- NO read			
1436	0,60	22.1	,723	412	7.53			n, may		
1438	0.90	21.8.	1693		1		1	,		
Stor.	Proce	complet	R					7-		

-	K									
	<u> </u>	Calculate	depth to water	er (from T	OC), for 80°	% well vo	ume recovery:			
					_	_			_	
	Origin	al Height of Water C	olumn = 608	$\frac{2}{2}$ 0.8 =	5,48	- (Well Depti	h) 21,85 Depth	to water 16,3	3 9	
Time: 1449	/ 1st measured	depth to water,!	5.83 feet be	low TOC.		ls well with	nin 80% of original well c	asing volume: Yes	<u> </u>	
Time:	_ 1st measured	depth to water,								
111116	_ ist incasuled	deptit to water,	reet be			19 AACH AAID	an oom or original well c	asing volunie. res_	NO	
	Number:									
Time:	1450	-	Sample ID:		<u>lw-4</u>		Depth:	15,83		
Comments	: 20	0002-	NO Sue	en		<u> </u>				
							·	 		
Well Condi	ition:	and -								
THOSE CORRE		Greek								
	-						· · · · · · · · · · · · · · · · · · ·			

Attachment B

Laboratory Procedures, Certified Analytical Reports and Chain-of-Custody Records





23 December 2011

Kate Waldo Closure Solutions 2300 Clayton Rd. Suite 1435 Concord, CA 94520

RE: Palace Garage

Enclosed are the results of analyses for samples received by the laboratory on 12/16/11 10:15. If you have any questions concerning this report, please feel free to contact me.

Sincerely,

Wendy Hsiao

Project Manager

Wordy Plsia



Closure Solutions
Project: Palace Garage

2300 Clayton Rd. Suite 1435
Project Number: [none]
Reported:

Concord CA, 94520
Project Manager: Kate Waldo
12/23/11 15:35

ANALYTICAL REPORT FOR SAMPLES

Sample ID	Laboratory ID	Matrix	Date Sampled	Date Received
MW-1	T111914-01	Water	12/15/11 15:49	12/16/11 10:15
MW-2	T111914-02	Water	12/15/11 16:26	12/16/11 10:15
MW-3	T111914-03	Water	12/15/11 15:21	12/16/11 10:15
MW-4	T111914-04	Water	12/15/11 14:50	12/16/11 10:15

SunStar Laboratories, Inc.

The results in this report apply to the samples analyzed in accordance with the chain of custody document. This analytical report must be reproduced in its entirety.

Wordy Plsia



Closure Solutions
Project: Palace Garage

2300 Clayton Rd. Suite 1435
Project Number: [none]
Reported:
Concord CA, 94520
Project Manager: Kate Waldo
12/23/11 15:35

MW-1 T111914-01 (Water)

Austra	D14	Reporting	I India	Dibetion	Datah	Duamanad	A a la a d	Matha d	Natas
Analyte	Result	Limit	Units	Dilution	Batch	Prepared	Analyzed	Method	Notes
		SunStar La	aborator	ries, Inc.					
Metals by SM 3500 Series Methods	l								
Ferrous Iron	0.352	0.100	mg/l	1	1121625	12/16/11	12/23/11	EPA6010/S M3500	
Volatile Organic Compounds by El	PA Method 8260	В							
Benzene	21	0.50	ug/l	1	1121601	12/16/11	12/21/11	EPA 8260B	
Toluene	0.88	0.50	"	"	"	"	"	"	
Ethylbenzene	29	0.50	"	"	"	"	"	"	
m,p-Xylene	4.6	1.0	"	"	"	"	"	"	
o-Xylene	ND	0.50	"	"	"	"	"	"	
Methyl tert-butyl ether	ND	1.0	"	"	"	"	"	"	
C6-C12 (GRO)	1500	50	"	"	"	"	"	"	
Surrogate: 4-Bromofluorobenzene		107 %	83.5	-119	"	"	"	"	_
Surrogate: Dibromofluoromethane		110 %	81-	136	"	"	"	"	
Surrogate: Toluene-d8		98.5 %	88.8	-117	"	"	"	"	
Conventional Chemistry Parameter	rs by APHA/EPA	A/ASTM M	ethods						
Total Alkalinity	420	20	mg/l	1	1121323	12/15/11	12/16/11	EPA 310.1	
Anions by EPA Method 300.0									
Sulfate as SO4	23.4	0.500	mg/l	1	1121620	12/16/11	12/17/11	EPA 300.0	
Nitrate as NO3	18.9	0.500	"	"	"	"	"	"	

SunStar Laboratories, Inc.

The results in this report apply to the samples analyzed in accordance with the chain of custody document. This analytical report must be reproduced in its entirety.

Wendy Hsiao, Project Manager



Closure Solutions Project: Palace Garage
2300 Clayton Rd. Suite 1435 Project Number: [none] Reported:
Concord CA, 94520 Project Manager: Kate Waldo 12/23/11 15:35

MW-2 T111914-02 (Water)

Analyte	Result	Reporting Limit	Units	Dilution	Batch	Prepared	Analyzed	Method	Notes
		SunStar La	aborator	ies, Inc.					
Metals by SM 3500 Series Methods									
Ferrous Iron	ND	0.100	mg/l	1	1121625	12/16/11	12/23/11	EPA6010/S M3500	
Volatile Organic Compounds by EP	A Method 8260	B							
Benzene	160	2.5	ug/l	5	1121601	12/16/11	12/21/11	EPA 8260B	
Toluene	26	0.50	"	1	"	"	"	"	
Ethylbenzene	480	2.5	"	5	"	"	"	"	
m,p-Xylene	650	25	"	25	"	"	"	"	
o-Xylene	140	2.5	"	5	"	"	"	"	
Methyl tert-butyl ether	ND	1.0	"	1	"	"	"	"	
C6-C12 (GRO)	4300	50	"	"	"	"	"	"	
Surrogate: 4-Bromofluorobenzene		102 %	83.5	-119	"	"	"	"	
Surrogate: Dibromofluoromethane		108 %	81	136	"	"	"	"	
Surrogate: Toluene-d8		98.5 %	88.8	-117	"	"	"	"	
Conventional Chemistry Parameter	s by APHA/EP	A/ASTM M	ethods						
Total Alkalinity	370	20	mg/l	1	1121323	12/15/11	12/16/11	EPA 310.1	
Anions by EPA Method 300.0									
Sulfate as SO4	53.8	0.500	mg/l	1	1121620	12/16/11	12/17/11	EPA 300.0	
Nitrate as NO3	44.0	0.500	"	"	"	"	"	"	

SunStar Laboratories, Inc.

The results in this report apply to the samples analyzed in accordance with the chain of custody document. This analytical report must be reproduced in its entirety.

Wendy Hsiao, Project Manager

evandy flsia



Closure Solutions
Project: Palace Garage

2300 Clayton Rd. Suite 1435
Project Number: [none]

Concord CA, 94520
Project Manager: Kate Waldo

Reported:

12/23/11 15:35

MW-3 T111914-03 (Water)

Analyte	Result	Reporting Limit	Units	Dilution	Batch	Prepared	Analyzed	Method	Notes
		SunStar La	borator	ies, Inc.					
Metals by SM 3500 Series Methods									
Ferrous Iron	ND	0.100	mg/l	1	1121625	12/16/11	12/23/11	EPA6010/S M3500	
Volatile Organic Compounds by EP	A Method 8260	В							
Benzene	1.5	0.50	ug/l	1	1121601	12/16/11	12/21/11	EPA 8260B	
Toluene	ND	0.50	"	"	"	"	"	"	
Ethylbenzene	3.0	0.50	"	"	"	"	"	"	
m,p-Xylene	11	1.0	"	"	"	"	"	"	
o-Xylene	1.2	0.50	"	"	"	"	"	"	
Methyl tert-butyl ether	ND	1.0	"	"	"	"	"	"	
C6-C12 (GRO)	150	50	"	"	"	"	"	"	
Surrogate: 4-Bromofluorobenzene		104 %	83.5	-119	"	"	"	"	
Surrogate: Dibromofluoromethane		108 %	81	136	"	"	"	"	
Surrogate: Toluene-d8		96.5 %	88.8	-117	"	"	"	"	
Conventional Chemistry Parameter	s by APHA/EPA	A/ASTM M	ethods						
Total Alkalinity	200	20	mg/l	1	1121323	12/15/11	12/16/11	EPA 310.1	
Anions by EPA Method 300.0									
Sulfate as SO4	37.2	0.500	mg/l	1	1121620	12/16/11	12/17/11	EPA 300.0	•
Nitrate as NO3	42.3	0.500	"	"	"	"	"	"	

SunStar Laboratories, Inc.

The results in this report apply to the samples analyzed in accordance with the chain of custody document. This analytical report must be reproduced in its entirety.

Wendy Hsiao, Project Manager



Volatile Organic Compounds by EPA Method 8260B

25712 Commercentre Drive Lake Forest, California 92630 949.297.5020 Phone 949.297.5027 Fax

Closure Solutions Project: Palace Garage 2300 Clayton Rd. Suite 1435 Project Number: [none]

Concord CA, 94520 Project Manager: Kate Waldo

Reported: 12/23/11 15:35

MW-4 T111914-04 (Water)

		Reporting							
Analyte	Result	Limit	Units	Dilution	Batch	Prepared	Analyzed	Method	Notes

SunStar Laboratories, Inc.

Benzene	ND	0.50	ug/l	1	1121601	12/16/11	12/21/11	EPA 8260B	
Toluene	ND	0.50	"	"	"	"	"	"	
Ethylbenzene	ND	0.50	"	"	"	"	"	"	
m,p-Xylene	1.3	1.0	"	"	"	"	"	"	
o-Xylene	ND	0.50	"	"	"	"	"	"	

 m,p-Xylene
 1.3
 1.0
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "
 "

SunStar Laboratories, Inc.

The results in this report apply to the samples analyzed in accordance with the chain of custody document. This analytical report must be reproduced in its entirety.

evenly flsia



Closure Solutions Project: Palace Garage

2300 Clayton Rd. Suite 1435Project Number: [none]Reported:Concord CA, 94520Project Manager: Kate Waldo12/23/11 15:35

Metals by SM 3500 Series Methods - Quality Control SunStar Laboratories, Inc.

		Reporting		Spike	Source		%REC		RPD	
Analyte	Result	Limit	Units	Level	Result	%REC	Limits	RPD	Limit	Notes
Batch 1121625 - EPA 3010A										
Blank (1121625-BLK1)				Prepared:	12/16/11	Analyzed	1: 12/23/11			
Ferrous Iron	ND	0.100	mg/l							
LCS (1121625-BS1)				Prepared:	12/16/11	Analyzed	1: 12/23/11			
Ferrous Iron	0.508	0.100	mg/l	0.526		96.6	80-120			_
Matrix Spike (1121625-MS1)	Sou	rce: T11191	4-01	Prepared:	12/16/11	Analyzed	1: 12/23/11			
Ferrous Iron	0.0926	0.100	mg/l	0.526	0.352	NR	75-125			QM-07
Matrix Spike Dup (1121625-MSD1)	Sou	rce: T11191	4-01	Prepared:	12/16/11	Analyzed	1: 12/23/11			
Ferrous Iron	0.135	0.100	mg/l	0.526	0.352	NR	75-125	37.0	20	QM-07

SunStar Laboratories, Inc.

The results in this report apply to the samples analyzed in accordance with the chain of custody document. This analytical report must be reproduced in its entirety.

Wordy Plsia



Closure Solutions Project: Palace Garage

2300 Clayton Rd. Suite 1435Project Number: [none]Reported:Concord CA, 94520Project Manager: Kate Waldo12/23/11 15:35

Volatile Organic Compounds by EPA Method 8260B - Quality Control SunStar Laboratories, Inc.

Analyte	Result	Reporting Limit	Units	Spike Level	Source Result	%REC	%REC Limits	RPD	RPD Limit	Notes
Batch 1121601 - EPA 5030 GCMS										
Blank (1121601-BLK1)				Prepared:	12/16/11	Analyze	d: 12/20/11			
Benzene	ND	0.50	ug/l	•						
Toluene	ND	0.50	"							
Ethylbenzene	ND	0.50	"							
m,p-Xylene	ND	1.0	"							
o-Xylene	ND	0.50	"							
Methyl tert-butyl ether	ND	1.0	"							
C6-C12 (GRO)	ND	50	"							
Surrogate: 4-Bromofluorobenzene	7.88		"	8.00		98.5	83.5-119			
Surrogate: Dibromofluoromethane	8.94		"	8.00		112	81-136			
Surrogate: Toluene-d8	7.46		"	8.00		93.2	88.8-117			
LCS (1121601-BS1)				Prepared:	12/16/11	Analyze	d: 12/21/11			
Benzene	18.9	0.50	ug/l	20.0		94.6	75-125			
Toluene	19.0	0.50	"	20.0		95.2	75-125			
Surrogate: 4-Bromofluorobenzene	8.40		"	8.00		105	83.5-119			
Surrogate: Dibromofluoromethane	8.96		"	8.00		112	81-136			
Surrogate: Toluene-d8	7.86		"	8.00		98.2	88.8-117			
Matrix Spike (1121601-MS1)	Source: T111900-02		Prepared: 12/16/11 Analyzed: 12/21/11							
Benzene	18.6	0.50	ug/l	20.0	ND	92.8	75-125			
Toluene	18.4	0.50	"	20.0	ND	92.2	75-125			
Surrogate: 4-Bromofluorobenzene	8.05		"	8.00		101	83.5-119			
Surrogate: Dibromofluoromethane	9.02		"	8.00		113	81-136			
Surrogate: Toluene-d8	7.68		"	8.00		96.0	88.8-117			
Matrix Spike Dup (1121601-MSD1)	Source: T111900-02		Prepared: 12/16/11 Analyzed: 12/21/11							
Benzene	18.3	0.50	ug/l	20.0	ND	91.4	75-125	1.52	20	
Toluene	18.2	0.50	"	20.0	ND	91.0	75-125	1.37	20	
Surrogate: 4-Bromofluorobenzene	8.23		"	8.00		103	83.5-119			
Surrogate: Dibromofluoromethane	8.88		"	8.00		111	81-136			
Surrogate: Toluene-d8	8.09		"	8.00		101	88.8-117			

SunStar Laboratories, Inc.

The results in this report apply to the samples analyzed in accordance with the chain of custody document. This analytical report must be reproduced in its entirety.

Wardy Flsia



Closure Solutions Project: Palace Garage

2300 Clayton Rd. Suite 1435Project Number: [none]Reported:Concord CA, 94520Project Manager: Kate Waldo12/23/11 15:35

Conventional Chemistry Parameters by APHA/EPA/ASTM Methods - Quality Control SunStar Laboratories, Inc.

		Reporting		Spike	Source		%REC		RPD	
Analyte	Result	Limit	Units	Level	Result	%REC	Limits	RPD	Limit	Notes
Batch 1121323 - General Preparation										
Blank (1121323-BLK1)				Prepared:	12/14/11	Analyzed	: 12/16/11			
Total Alkalinity	ND	20	mg/l							
Duplicate (1121323-DUP1)	Sou	ırce: T11188	1-01	Prepared:	12/14/11	Analyzed	1: 12/16/11			
Total Alkalinity	140	20	mg/l		150			6.90	20	

SunStar Laboratories, Inc.

The results in this report apply to the samples analyzed in accordance with the chain of custody document. This analytical report must be reproduced in its entirety.

Wendy Hsiao, Project Manager

evandy flsias



Closure Solutions Project: Palace Garage

2300 Clayton Rd. Suite 1435Project Number: [none]Reported:Concord CA, 94520Project Manager: Kate Waldo12/23/11 15:35

Anions by EPA Method 300.0 - Quality Control SunStar Laboratories, Inc.

		Reporting		Spike	Source		%REC		RPD	
Analyte	Result	Limit	Units	Level	Result	%REC	Limits	RPD	Limit	Notes
Batch 1121620 - General Preparation										
Blank (1121620-BLK1)				Prepared:	12/16/11	Analyzed	: 12/19/11			
Sulfate as SO4	ND	0.500	mg/l							
Nitrate as NO3	ND	0.500	"							
LCS (1121620-BS1)				Prepared:	12/16/11	Analyzed	: 12/19/11			
Sulfate as SO4	9.15	0.500	mg/l	10.0		91.5	80-120			
Nitrate as NO3	10.3	0.500	"	11.1		92.4	80-120			
Matrix Spike (1121620-MS1)	Sou	rce: T11191	4-01	Prepared:	12/16/11	Analyzed	: 12/19/11			
Sulfate as SO4	33.3	0.500	mg/l	10.0	23.4	99.4	80-120			
Nitrate as NO3	30.7	0.500	"	11.1	18.9	106	80-120			
Matrix Spike Dup (1121620-MSD1)	Sou	rce: T11191	4-01	Prepared:	12/16/11	Analyzed	: 12/19/11			
Sulfate as SO4	33.3	0.500	mg/l	10.0	23.4	98.9	80-120	0.147	20	
Nitrate as NO3	30.6	0.500	"	11.1	18.9	105	80-120	0.114	20	

SunStar Laboratories, Inc.

The results in this report apply to the samples analyzed in accordance with the chain of custody document. This analytical report must be reproduced in its entirety.

Wordy Plsia



Closure Solutions Project: Palace Garage

2300 Clayton Rd. Suite 1435 Project Number: [none] Reported:
Concord CA, 94520 Project Manager: Kate Waldo 12/23/11 15:35

Notes and Definitions

QM-07 The spike recovery and or RPD was outside acceptance limits for the MS and/or MSD. The batch was accepted based on acceptable

LCS recovery.

DET Analyte DETECTED

ND Analyte NOT DETECTED at or above the reporting limit

NR Not Reported

dry Sample results reported on a dry weight basis

RPD Relative Percent Difference

SunStar Laboratories, Inc.

The results in this report apply to the samples analyzed in accordance with the chain of custody document. This analytical report must be reproduced in its entirety.

Wordy Flsia

SunStar Laboratories, Inc. 25712 Commercentre Dr Lake Forest, CA 92630

Chain of Custody Record

949-297-5020

T111914 Client: Date: **Project Name:** Phone: Collector: Client Project #: EDF#: 10600101043 Project Manager: Batch #: Chain 6010/7000 Title 22 Metals 8260 BTEX, OXY only Total # of containers 8015M Ext./Carbon 8015M (gasoline) 8015M (diesel) aboratory ID 8021 BTEX 70978 8270 Sample Container Sample ID Date Sampled Time Type Type Comments/Preservative 4504151 12/15/11 MW-01 1626 MW-2 30049 02 MW-3 152 03 45045 mu- u 04 Relinguished by: (sibriature). Date / Time Received by; (signature) Total # of containers 25 Chain of Custody seals Y/N/NA NA Relinquished by: (signature) Date / Time Date / Time Seals intact? Y/N/NA Received good condition/cold 1.2 Received by: (signature) Relinguished by: (signature) Date / Time Date / Time 10:15 FED EX 12.16.11 Turn around time: Pickup Sample disposal Instructions: Disposal @ \$2.00 each Return to client



SAMPLE RECEIVING REVIEW SHEET

BATCH #			
Client Name: Cosure Solutions Proj	iect: PALNEC GA	KAG-E	
Received by: Brian Date	e/Time Received:/	2.16.11	10:15
Delivered by: Client SunStar Courier GSO	∫ FedEx ☐ Other		
Total number of coolers received Temp criter	ria = 6°C > 0°C (no	frozen (ontainers)
Temperature: cooler #1 $\phantom{aaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaa$			
cooler #2°C +/- the CF (- 0.2°C) =	_°C corrected temperate	ıre	
cooler #3°C +/- the CF (- 0.2°C) =	_°C corrected temperate	ıre	
Samples outside temp. but received on ice, w/in 6 hours of final sa	mpling. 🏿 Yes	□No	*
Custody Seals Intact on Cooler/Sample	□Yes	□No	*
Sample Containers Intact	Yes	□No	*
Sample labels match COC ID's	Yes	□No	*
Total number of containers received match COC	Yes	□No	*
Proper containers received for analyses requested on COC	∑ Yes	□No	*
Proper preservative indicated on COC/containers for analyses requ	uested Yes	□No	*
Complete shipment received in good condition with correct tempe preservatives and within method specified holding times. Yes		ibels, vo	lumes
* Complete Non-Conformance Receiving Sheet if checked Cooler	/Sample Review - Initia	ls and da	ate <u>BC 12-16-11</u>
Comments:			
			•