MONITORING WELL INSTALLATION & FOURTH QUARTER 2002 MONITORING REPORT

PALACE GARAGE 14336 WASHINGTON AVENUE SAN LEANDRO, CALIFORNIA

Feb 2003

prepared for

Kerry & Associates 151 Callan Avenue Suite 300 San Leandro, California 94577

prepared by

Professional Service Industries, Inc. 4703 Tidewater Avenue, Suite B Oakland, California 94601 (510) 434-9200

February 10, 2003 575-2G033



February 12, 2003

Mr. Scott Seery Alameda County Health Care Services Agency 1131 Harbor Bay Parkway Alameda, CA 94502-6577

RE: Monitoring Well Installation & Fourth Quarter 2002 Monitoring Report

Palace Garage

14336 Washington Avenue San Leandro, California PSI Project No.: 575-2G033

Dear Mr. Seery:

On behalf of Kerry & Associates, Professional Service Industries, Inc. is pleased to present this Monitoring Well Installation & Fourth Quarter 2002 Monitoring Report in San Leandro, California. PSI refers you to the report for details.

If you have any questions regarding this report or any aspect of the project, please do not hesitate to call.

Respectfully submitted,

PROFESSIONAL SERVICE INDUSTRIES, INC.

Frank R. Poss

Senior Technical Professional

cc: Mr. Jeff Kerry, Kerry & Associates

Mr. Chuck Headlee, RWQCB

TABLE OF CONTENTS

STA	TEMEN	T OF LIMITATIONS AND PROFESSIONAL CERTIFICATION	İ
1.0	1.1 P	PROJECT OBJECTIVE	1
2.0	PRE-FI	ELD ACTIVITIES	2
3.0	3.1 S 3.2 M 3.3 G	RFACE INVESTIGATION SOIL BORINGS MONITORING WELL INSTALLATION SROUNDWATER SAMPLING IYDROGEOLOGY 3.4.1 Subsurface Exploration 3.4.2 Groundwater Elevation and Hydraulic Gradient	3 4 5 5
4.0		ATORY ANALYSIS PROGRAM	
5.0	5.1 L	ATORY RESULTSABORATORY ANALYTICAL RESULTS - SOILABORATORY ANALYTICAL RESULTS - GROUNDWATER	6
6.0	CONCL	USIONS & RECOMMENDATIONS	7
FIGI	URES		
	•	LOCATION MAP SITE PLAN AND GROUNDWATER CONTOUR MAP	
TAE	BLES		
		ANALYTICAL RESULTS: SOIL ANALYTICAL RESULTS: GROUNDWATER	

TABLE OF CONTENTS

APPENDICES

APPENDIX A: PERMITS

APPENDIX B: FIELD PROCEDURES

APPENDIX C: BORING LOGS & WELL CONSTRUCTION LOG

APPENDIX D: SURVEY DATA APPENDIX E: PURGE LOGS

APPENDIX F: LABORATORY RESULTS AND CHAIN-OF-CUSTODY RECORDS

STATEMENT OF LIMITATIONS AND PROFESSIONAL CERTIFICATION

Information provided in Professional Services Industries, Inc., (PSI) report number 575-2G033 is intended exclusively for the Kerry & Associates for the evaluation of soil and groundwater contamination as it pertains to the subject site. PSI is responsible for the facts and accuracy of the data presented herein. The professional services provided have been performed in accordance with practices generally accepted by other geologists, hydrologists, hydrogeologists, engineers, and environmental scientists practicing in this field. No other warranty, either expressed or implied, is made. As with all subsurface investigations, there is no guarantee that the work conducted will identify any and all sources or locations of contamination.

This report is issued with the understanding that Kerry & Associates is responsible for ensuring that the information contained in this report is brought to the attention of the appropriate regulatory agency. This report has been reviewed by a geologist who is registered in the State of California and whose signature and license number appear below.

Frank R. Poss, R.E.A. Senior Hydrogeologist Brand Burfield, RG 6986

Senior Geologist

1.0 INTRODUCTION

Professional Service Industries, Inc. (PSI) has been retained by Kerry & Associates to conduct a hazardous-waste site assessment to assess current soil and groundwater conditions at the Palace Garage at 14336 Washington Avenue of San Leandro, California (subject site; Figure 1).

The scope of work for this investigation included:

- Advance two (2) soil borings using direct push drill rig,
- Install one groundwater monitoring well,
- Survey the elevations of the tops of each well casing,
- Perform chemical analysis of soil and groundwater samples,
- Prepare a technical report describing the investigation and interpretation of the data generated.

The scope of work was developed based on the Allcal Environmental Proposed Work Plan for Phase IV Further Assessment, dated September 25, 2001. The Work Plan was approved by Mr. Scott Seery of the Alameda County Health Care Services Agency (AHCSA) in a letter dated October 22, 2001.

1.1 PROJECT OBJECTIVE

The objective of the project is to help define the lateral extent of petroleum hydrocarbons in the soil and groundwater.

1.2 SITE BACKGROUND

PSI has reviewed information provided by Kerry & Associates and understands that a 550-gallon gasoline underground storage tank (UST) was removed from the site in 1991. Subsequent investigations included the installation of 3 monitoring wells and the drilling of 15 borings. Based on data obtained from the wells and borings, impacted unsaturated-zone soil is confined to the area of the former dispenser pad and UST. Groundwater appears to be moving to the southwest along the driveway between the subject site and the northern adjacent property. Historically, TPH-G concentrations at the site have been detected as high as 52 milligrams per liter (mg/l) with benzene concentrations as high as 1.9 mg/l.

2.0 PRE-FIELD ACTIVITIES

Prior to initiation of field activities, PSI marked the drilling locations with white paint and contacted Underground Service Alert a minimum of 48-hours prior to beginning work to locate any potential buried utilities.

Prior to drilling PSI obtained a permit from the AHCSA. A copy of the permit is included in Appendix A.

3.0 SUBSURFACE INVESTIGATION

3.1 SOIL BORINGS

On December 6, 2002, borings SB-16 and SB-17 were drilled at the site. The boring locations are presented in Figure 2. The borings were drilled by V&W Drilling of Rio Vista, California using a Geoprobe drill rig. The borings were advanced to between 20 and 24 feet below ground surface (bgs). Soil samples were collected for lithologic logging purposes. However, the samples collected from the soil/groundwater interface of each boring were submitted to a laboratory for chemical analysis. Fieldwork for drilling and soil sampling activities was conducted in accordance with the field procedures described in Appendix B.

The soil samples collected for chemical analysis were transported under Chain-Of-Custody Protocol to Basic Laboratories, Inc. of Redding, California, a California Department of Health Services certified hazardous materials testing laboratory. The samples were maintained in a cooler with ice, or a refrigerator until delivered to the analytical laboratory. The tests performed and the analytical results are described in Section 4.

3.2 MONITORING WELL INSTALLATION

Based on the ALLCAL Workplan stipulations, PSI converted only one of the borings (SB-16) into a monitoring well (MW-4). Visual and olfactory evidence of petroleum hydrocarbon-impacted groundwater was observed in boring SB-17, so according to the stipulations set forth in the workplan, a monitoring well was not installed.

The well casing consisted of 1-inch inside-diameter Schedule 40 PVC casing with 0.020-inch machine-slotted screen. The sand pack (Monterey-type number 2/12 sand) extended approximately 0.5 foot above the screened interval. Approximately 1 foot of hydrated bentonite chips was placed above the sand pack, and neat cement mixed at a ratio of 5 gallons of water per 94-pound sack of cement was used for the annular seal from the top of the bentonite to approximately 1 foot below grade. A flush-mounted traffic-rated wellhead was mounted in concrete at the top of the well. The well construction log is presented in Appendix C.

The locations and top-of-casing elevations of all four wells were surveyed by Morrow Surveying, a California Licensed Surveyor, on February 5, 2003. A copy of the well survey report can be found in Appendix D.

3.3 GROUNDWATER SAMPLING

On December 31, 2002, groundwater samples were collected from monitoring wells MW-1 through MW-4. Prior to the collection of groundwater samples, the monitoring wells were purged of a minimum of three well volumes of water until pH, conductivity, and temperature stabilized.

The following procedures for well monitoring, well purging, and water sampling were implemented while sampling the wells:

- 1. All non-dedicated equipment was washed prior to entering the well with an Alconox solution, followed by one tap water rinse and a deionized water rinse.
- 2. Prior to purging the well and borings, depth to water was measured using a groundwater interface probe to an accuracy of 0.003 meters (0.01 foot). The measurements were made from the top of the well casing on the north side.
- 3. The monitoring wells were purged of a minimum of three well volumes of water until pH, conductivity, and temperature stabilized. Each well was purged with a new, dedicated, disposable bailer.
- 4. After purging a water sample was collected from each well. The water collected was immediately decanted into laboratory-supplied, preserved vials and bottles. The containers were overfilled, capped, labeled, and placed in a chilled cooler prior to delivery to the laboratory for analysis.
- 5. Chain-of-custody procedures, including chain-of-custody forms, were used to document water sample handling and transport from collection to delivery to the laboratory for analysis.
- 6. Groundwater samples were delivered to the State-certified hazardous waste laboratory within approximately 72-hours of collection.
- 7. Purged water was contained in a DOT approved 55-gallon drum and left on site pending analysis for proper disposal. The drum was labeled with the contents, date, well number, client name, and project number.

Purge logs are presented in Appendix E.

3.4 HYDROGEOLOGY

3.4.1 Subsurface Exploration

Soils were logged according to the Unified Soil Classification System. The ground surface was covered with a pavement section consisting of approximately 1 inch of asphaltic concrete over 2 inches of aggregate baserock. The subsurface materials encountered consisted of approximately two feet of sandy/clay/clayey sand fill underlain by 10 to 12 two feet of silty clay. Underlying the silty clay was from 6 to 7 feet of clayey or gravelly sand. A more detailed description of subsurface soil encountered is presented in the soil boring logs (Appendix C).

3.4.2 Groundwater Elevation and Hydraulic Gradient

On December 31, 2002, depth to groundwater measurements were obtained from the monitoring wells (MW-1 through MW-4) using a groundwater probe. Floating product was not encountered in any of the wells. The groundwater measurements were converted to groundwater elevation data, which are presented in Table 2 and Figure 2. The calculated groundwater flow direction is to the southwest at a gradient of 0.002.

4.0 LABORATORY ANALYSIS PROGRAM

The soil and groundwater samples collected during this investigation were submitted to Basic Laboratories, Inc., a State of California Department of Health Services certified hazardous waste laboratory.

4.1 SOIL AND GROUNDWATER

The soil and groundwater samples collected for analyses were analyzed for the following constituents:

- EPA Method 8015 modified TPH-G; and
- EPA Method 8260 Volatile Organic Compounds (VOCs); including methyl tert butyl ether (MTBE), ethyl dibromide, 1,2 dichloroethane (1,2 DCA), and other oxygenates.

5.0 LABORATORY RESULTS

A summary of the analytical results is presented in Tables 1 and 2. A copy of the laboratory reports and chain-of-custody records are included in Appendix F.

5.1 LABORATORY ANALYTICAL RESULTS - SOIL

The soil analytical results are presented in Table 1. None of the constituents tested were detected in sample SB-16-15. Neither of the soil samples contained detectable concentrations of benzene, toluene, ethylbenzene, and total xylenes (BTEX), or MTBE. TPH-G was detected in soil sample SB-17-19.0 at 0.292 mg/kg. Common constituents of gasoline (n-butylbenzene, isopropylbenzene, etc.) were detected in soil sample SB-17-19.0. None of the compounds had a concentration greater than their respective EPA Region IX Preliminary Remediation Goals (PRGs).

5.2 LABORATORY ANALYTICAL RESULTS - GROUNDWATER

Groundwater samples from the wells were submitted to the laboratory for analysis. The groundwater analytical results are presented in Table 2.

None of the groundwater samples contained detectable concentrations of MTBE. TPH-G was detected in groundwater samples MW-1 and MW-2 at 4.8 and 1.67 milligrams per liter (mg/l). Numerous constituents of gasoline (BTEX, n-butylbenzene, isopropylbenzene, etc) were detected in groundwater samples from MW-1 and MW-2. the following constituents had concentrations greater than the State of California Primary Maximum Contaminant Levels (MCL):


- Benzene (MW1 at 1,030 ug/l, MW2 at 1,030 ug/l) (MCL of 1 ug/l)
- Toluene (MW1 at 2,380 ug/l) (MCL of 150 ug/l)
- Ethylbenzene (MW1 at 1,690 ug/l) (MCL of 700 ug/l)
- Total Xylenes (MW1 at 9,220 ug/l) MCL of 1,750 ug/l)

6.0 CONCLUSIONS & RECOMMENDATIONS

Based on the information presented in this report, the following conclusions have been reached:

- The calculated groundwater flow direction is to the southwest with a hydraulic gradient of approximately 0.002.
- None of the groundwater samples contained detectable concentrations of TPH-G with the exception of MW-1 and MW-2 at 4.8 and 1.67 mg/l, respectively.
- All four BTEX compounds were above the MCL in the groundwater sample collected from MW-1, while only benzene was detected above the MCL in groundwater sample MW-2. BTEX compounds were not detected in the groundwater samples collected from MW-3 and MW-4.
- Based on the concentrations detected in MW-3 and MW-4, the lack of BTEX in the soil sample collected from SB-17, and the calculated flow direction, the downgradient extent of BTEX impacted groundwater has been defined.

Based on the results of this investigation, PSI recommends groundwater monitoring continue at the site. Additionally, PSI recommends a meeting be coordinated with the Alameda County Health Care Agency (ACHCA) to discuss further work at the site.






TABLE 1

ANALYTICAL RESULTS: SOIL PALACE GARAGE 14336 WASHINGTON AVENUE SAN LEANDRO, CALIFORNIA

Sample I.D.	TPH-G mg/kg	MTBE mg/kg	Benzene mg/kg	Toluene mg/kg	to a regret to the contract of	St. Committee
SB16-15	<0.06	<0.005	<0.005	<0.005	<0.005	<0.005
SB17-19	0.292	<0.005	<0.005	<0.005	<0.005	<0.005

NOTES:

TPH-G = Total Petroleum Hydrocarbons as Gasoline by EPA Method 8015M.

MTBE = Methyl Tertiary Butyl Ether

mg/kg = milligrams per kilogram

<0.06 = Concentration below indicated detection limit

TABLE 2

ANALYTICAL RESULTS: GROUNDWATER PALACE GARAGE 14336 WASHINGTON AVENUE SAN LEANDRO, CALIFORNIA

Sample I.D.	Date	TOC Elevation (feet msl)*	Depth To Groundwater	Groundwater Elevation (feet msl)*	TPH-G	MTBE	Benzene	Toluene	Ethyl-benzene	Total Xylenes
MW-1	12/31/02	37.59	13.62	23.97	4,800	<0.5	1,030	2,380	1,690	9,220
MW-2	12/31/02	37.12	13.38	23.74	1,670	<0.5	1,030	11	23.1	16.4
MW-3	12/31/02	37.01	13.29	23.72	<0.05	<0.5	<0.5	<0.5	<0.5	<1.0
MW-4	12/31/02	37.09	13.45	23.64	<0.05	<0.5	<0.5	<0.5	<0.5	<1.0

NOTES:

TPH-G = Total Petroleum Hydrocarbons as Gasoline by EPA Method 8015M.

MTBE = Methyl Tertiary Butyl Ether

All contaminants are re reported in ug/l = micrograms per liter

<0.06 = Concentration below indicated detection limit

APPENDIX A

DRILLING PERMIT



ALAMEDA COUNTY PUBLIC WORKS AGENCY

and the second s	
DRILLING PERMIT	APPLICATION
FOR APPLICANT TO COMPLETE LOCATION OF PROJECT PRIACE GARAGE 19336 GARAINSTON ALOUA	FOR OFFICE USE PERMIT NUMBER
क्रिक्सिक स्थापक स्यापक स्थापक स्यापक स्थापक	PERMIT CONDITIONS Circled Permit Requirements Apply
Name KERRY & ASSOCIATES Name KERRY & ASSOCIATES Address 151 (HUAD AC 90 Dephone (510) 463-421 City SAD LEADED Zip 94577 APPLICANT Name PROCESSIONAL SCRUTCE TURNSRIES Fax 510-434-7676 Address 4703 TURNSER AE 565 Phone 510-434-9200 City PAKLAND Zip 74601	A GENERAL 1. A permit application should be submitted so as to arrive at the ACPWA office five days prior to proposed starting date. 2. Submit to ACPWA within 60 days after completion of permitted original Department of Water Resources-Well Completion Report. 3. Permit is void if project not begun within 90 days of approval date B. WATER SUPPLY WELLS
TYPE OF PROJECT Well Construction: Geotechnical Investigation Cathodic Protection: General General Water Supply Genumination General Monitoring Well Destruction PROPOSED WATER SUPPLY WELL USE	1. Minimum surface seal thickness is two inches of cement grout placed by tremic. 2. Minimum seal depth is 30 fast for municipal and Industrial wells of 20 feet for domestic and irrigation wells unless a lesser depth is specially approved. C. GROUNDWATER MONITORING WELLS INCLUDING PIEZOMETERS 1. Minimum surface seal thickness is two inches of cement grout placed by tremic.
New Domestic Replacement Domestic Municipal Imigation Imigation Industrial Other Other Other Other Cable Other Mud Rolary Other Must - Maller Other Maller's NAME V+ W DRILLER'S LICENSE NO. C57 720904	2. Minimum seal depth for manitoring wells is the maximum depth practicable or 20 feet. D. GEOTECHNICAL Backfill bore hole by wemls with coment grout or cement groutesand mixture. Upper two-three feet replaced in kind or with compacted cuttings. E. CATHODIC Fill hole anode zone with concrete placed by tremle. F. WELL DESTRUCTION Send a map of work site. A separate permit is required for wells deeper than 45 feet. G. SPECIAL CONDITIONS
WELL PROJECTS Drill Hole Diameter 2 in Maximum Casing Diameter 3/4 in. Depth 25 ft. Surface Soul Depth 5 ft. Owner's Well Number MW-4	NOTE: One application must be submitted for each well or well destruction. Multiple harings on one application are acceptable for gentechnical and cuntamination investigations.
APPLICANT'S SIGNATURE	APPROVED DATE 12-2-02 Ordinance No. 73-68. 12/2/02.
PLEASE PRINTNAME BRAND W. BURFIELD R	av.5=13-00

PUBLIC WORKS

ALAMEDA COUNTY PUBLIC WORKS AGENCY

WATER RESOURCES SECTION

399 ELMHURST ST. HAYWARD CA. 94544-1395

PHONE (510) 530-5554 6-70-66-73 - 347-75 700

FAX (510)782-1939

DRILLING PERMIT	APPEICATION
LOCATION OF PROJECT PALACE GARAGE	FOR OFFICE USE PERMIT NUMBER WOZ-161 WELL NUMBER
14 6 7 6 LATAINE TOW MUDOUS	APN
THE CEADING CALIFORNIA 94978.	M17
The state of the s	PERMIT CONDITIONS
	Circled Permit Requirements Apply
Name KERRY & ASSOCIATES (510)	A. GENERAL
Address 15 CALLAN AVE THE 300 Phone 483-1211	1. A permit application should be submitted so at to arrive at the ACPWA office five days prior to
City SAN (FANTICO Zip 94977	State of the William date
City 2000	proposed starting date. 2. Submit to ACPWA within 60 days after completion of
APPLICANT A TO THE RESERVE	permined original Department of Water Resources-
Wirm PROTESTIONAL PROJECT WOUGHES	Well Completion Reports
NN 701-77-7800	3. Permit is void if project not begun within 90 days of
Address 4703 TOCOLAFR ANE. 46 B Phone 710 434-9700	approval date
City DAKLAND Zip 94601	6 WITER CHEPLY WELLS
•). Minimum surface seal thickness is two inches of
ALL IND APRILATECT	coment grout placed by tromic.
TYPE OF PROJECT Well Construction Geotechnical Invastigation	2. Minimum real depth is 50 feat for municipal and
Cuthodic Protestian [] General []	Industrial wells of 20 feet for domestic and Irrigation wells unless a lesser depth is specially approved.
Water Supply [] Confamination []	C GROUNDWATER MONITORING WELLS
Monitoring Well Destraction	INCLUDING PIEZOMETERS
	I. Minimum surface seal thickness is two inches of
PROPOSED WATER SUPPLY WELL USE	coment grout placed by tramia.
New Domestic II Replacement Domestic II	2. Minimum seal depth for mealtering wells is the
Watterbat it its fancti	maximum depth practicable or 20 feet.
Industrial 0 Other	n GEOTECHNICAL
PRINCIPAL MARKETIAN	Backfill bore hole by tremie with coment grout or cement
PRILLING METHOD: Mud Retary 0 Air Rotary 0 Auger 0	grouveand mixture. Upper two-three fest replaced in kind
Cable Other & (Pugu DELL)	or with compacted cuttings.
Chulle	E. CATHODIC Fill hole anode zone with concrete pieced by tremis.
DRILLER'S NAME V+ W DRILLING	F. WELL DESTRUCTION
000001	Send a map of work site. A separate permit is required
DRILLER'S LICENSE NO. C57 720904	for wells deeper than 45 feet.
	G. SPECIAL CONDITIONS
A A THE ARMS	
WELL PROJECTS Drill Hole Diamoter in. Maximum	NOTE: One application must be submitted for each well or well
Drill Hote manifestory	despuction. Multiple borings on one application are acceptable
Caring Diameter 3/11 in. Depth Surface Seal Depth B it. Owner's Well Number MW-5	for geotechnical and contamination invarigations.
·	•
GEOTECHNICAL PROJECTS	
Number of Bonings Meximum	K12 .
Hole Diameterin. Depthft.	DMI pose
ESTEMATED STARTING DATE DEC 6, 2002	APPROVED DATE 12-2-CR
ESTIMATED COMPLETION DATE DEC 6, 2002	APPROVED DATE!
	N 27 49 / X \ Y
I heroby agrae to comply with all requirements of this positit and Alameda County O	Ordinance No. 13:08.
A 111 VVII (1	72/02 []]
APPLICANT'S SIGNATURE	
NEAST BEINT NAME PRAND D. BULFTELD RO	-v,5-13-00
PLEASE PRINT NAME_BRADO 13. GUESTILL RO	

FIELD PROCEDURES

I. ADVANCING OF SOIL BORINGS AND COLLECTION OF SOIL SAMPLES

The following procedures were used for advancing soil borings and collecting soil samples at the site:

- Prior to the commencement of soil boring activities at the site, boring locations were marked with white paint. Underground Service Alert (USA) was contacted to identify underground utilities in the vicinity of the soil borings.
- 2. A licensed State of California drilling company conducted soil boring and sampling activities. The soil borings were advanced using the Geoprobe direct push method. Flush-threaded rods with a stainless steel sampler were advanced into the ground using a hydraulic press and percussion hammer. The opening of the sampler was sealed with a drive tip held in place by a threaded pin.
- Soil samples were collected using a 1.2 meter (4-foot) long, 0.05 meter (2-inch) inside diameter macro-core stainless steel sampler. Soil samplers were washed between borings with Alconox soap followed by two deionized water rinses. The sampler was lined with clean brass, stainless steel, or acetate sleeves.
- 4. After the sampler was retrieved, the sleeves were extracted from the sampler without disturbing the sample. The sample for analyses was collected from the lowest tube in the sampler. The ends of the sample were covered with Teflon™ sheets and capped with polyethylene end caps. The sample was labeled and placed in a ziplock bag in a chilled cooler prior to delivery to the laboratory.
- 5. Soil samples were assigned identification numbers such as B1-5, where B1 indicates the boring designation and -5 indicates that the sample was collected from 5 meters bgs. The samples were labeled with the project number, date and time of sample collection, sampling depth, and client name.
- 6. Chain-of-custody procedures using chain-of-custody records were implemented during handling and transportation of the samples to the laboratory for analyses.
- 7. Boring logs were prepared for the soil borings under the supervision of a California-Registered Geologist. Soil from each sample was described in accordance with Unified Soil Classification System by a PSI geologist and recorded on a field-boring log. The data recorded on the logs were based on examination of soil samples retrieved in the tubes, and drilling conditions observed in the field. Boring logs include information regarding the location of each boring, geologic descriptions of

materials encountered, occurrence of groundwater (if applicable) and organic vapor analyzer (OVA) measurements of the soil samples collected.

II. BACKFILL OF SOIL BORINGS

The following procedures were used to backfill the soil borings at the site:

1. Soil borings were backfilled to grade with Portland grout slurry. The slurry consisted of neat cement and 5% bentonite powder.

III. FIELD DOCUMENTATION OF SAMPLING PROCEDURES

The following outline describes the procedures followed by PSI for proper sampling documentation.

- 1. Sampling procedures were documented in field notes that contain:
 - 1. Sample collection procedures
 - 2. Date and time of collection
 - 3. Date of shipping
 - 4. Sample collection location
 - 5. Sample identification number(s)
 - 6. Intended analysis
 - Quality control samples
 - 8. Sample preservation
 - 9. Name of sampler
 - 10. Any pertinent observations
- 2. Samples were labeled with the following information:
 - 1. Sample designation number
 - 2. Date and time sample was collected
 - 3. Sampler's name
 - 4. Sample preservatives (if required)
 - 5. Project Name

3. The following was the sample designation system for the site:

For Borings, the samples were labeled B-(Boring Number)-(Depth) (i.e. sample collected from boring 4 at 5 meters would be B4-5).

For Groundwater Samples, the samples were labeled WB-(Boring Number (i.e. sample collected from boring 7 would be WB-7).

- 4. Handling of the samples were recorded on a chain of custody form, which shall include:
 - 1. Project name
 - 2. Site location
 - 3. Signature of collector
 - 4. Date and time of collection
 - 5. Sample identification number
 - 6. Number of containers in sample set
 - 7. Description of sample and container
 - 8. Name and signature of persons, and the companies or agencies they represent, who are involved in the chain of possession
 - 9. Inclusive dates and times of possession
 - 10. Analyses to be completed

APPENDIX C

BORING LOGS & WELL CONSTRUCTION LOGS

PROJECT INJME: PALACE GARACE PROJECT INJME: PALACE GARACE DOCUMENT OF STACODS DATE: 129802 DATE:	SOI	LE	30	RI	NG LOG			BORING NO: SB-1	6
PROJECT NAME: PALACE GARAGE PROJECT NAME: PALACE GARAGE PROJECT NAME: PALACE GARAGE PROJECT NAME: PALACE GARAGE PROJECT NAME: SOURCEST STATES DRILLING COMPANY: VAW DRILLING DRILLING COMPANY: VAW DRILLING DRILLING COMPANY: VAW DRILLING GROUNDATER LEVELS GROUNDATER LEVELS DATE COMMENTS DEPTH BOS 126/02 INTIALLY ENCOUNTERED 15.5 FEET PID USCS REMARKS PID USCS REMARKS (PPM) IT Apphalitic Concrete over 2' Aggregate Basenock. Sandy Cay (CL), Light brown, moist, stiff, medium to coarse care (FILL). Silty Clay (CL), Dark brown, moist, stiff, (NATIVE). As above; medium brown. As above; medium brown. IT As above; medium brown, very moist to wet, medium and. As above; medium brown, very moist to wet, medium and. Claysy Sand (SC), Medium brown, very moist to wet, medium and. Claysy Sand (SC), Medium brown, very moist to wet, medium SC Sandy Stift (ML), Medium brown, wet, stiff, fine sand. ML Boring terminated at 24.0 feet.									
PROJECT NUMBER ST-S20033 DATE: 12/80/02 DRILLING OCMPANY: VAW DRILLING DRILLING OCMPANY: VAM DRILLING DRILLING OCCUPANY: VAM DRILLING OCCUPANY: VAM DRILLING DRILLING OCCUPANY: VAM DRILLING DRILLING OCCUPANY: VAM DRILL	1				PROJECT NAME: PALACE GARA	GF		JOHNEL 1 OF	<u> </u>
DRILLING COMPANY: VAW DRILLING DRILLING THEORY. SEPTEMBUL. DRILLING STRIPLO. SECRETS BUSH-DRILL SORING DIAMETER: 2 INCHES DEPTH 24.0 FEET GROUNDWATER LEVELS DATE COMMENTS DEPTH 80S 12/8/02 INTIALLY ENCOUNTERED 15.5 FEET PID USCS REMARKS (PPM) Santy City (L), Light brown, moist, stiff, (NATIVE). CL Santy City (L), Dark brown, moist, stiff, (NATIVE). As above; medium brown. As above; medium brown. As above; medium brown, very moist to wet, medium Clayer Santy (SC), Medium brown, very moist to wet, medium As above; met to medium sand, some stit. Santy Stiff (ML), Medium brown, wet, stiff, fine sand. ML Boring terminated at 24.0 feet.	1				· · · · · · · · · · · · · · · · · · ·	<u> </u>		DATE: 12/6/02	
DRILING METHOD. GEOPHOSE PUSH-DRILL BORNING DIAMETER: 2 NORTH 1808 DATE GROUNDWATER LEVELS DATE COMMENTS DEPTH BOS. 12/602 INITIALLY ENCOUNTERED 15.5 FEET PID USCS REMARKS PID USCS REMARKS Sandy Clay (CL), Light brown, moist, stiff, (NATIVE). As above; medium brown. As above; medium brown. As above; medium brown, very moist to wet, medium Clayey Sand (SC), Medium brown, very moist to wet, medium Sandy Sit (ML), Medium brown, wet, stiff, fine sand. As above; fine to medium sand, some sitt. DEPTH: 24.0 FEET GROUNDWATER LEVELS DATE COMMENTS DEPTH: 24.0 FEET GROUNDWATER LEVELS DATE COMMENTS DEPTH BOS. DATE COMMENTS PID USCS REMARKS REMARKS CL Brick encountered in boring. CL Brick encountered in boring. CL Brick encountered in boring. No odor. No odor. Sea bove; many fine sand. 179 No odor. Softer at 18 feet. Sandy Sit (ML), Medium brown, wet, stiff, fine sand. ML Sandy Sit (ML), Medium brown, wet, stiff, fine sand. ML Boning terminated at 24.0 feet.						ING		DATE: 12/00UZ	
BORING DIAMETER: 2 NOHES GROUNDWATER LEVELS DATE COMMENTS DEPTH BOS 12/6/02 INTIALLY ENCOUNTERED 15.5 FEET OF THE PROPERTY OF	1				· · · · · · · · · · · · · · · · · · ·				·
DATE COMMENTS DEPTH BOS 12/8/02 INITIALLY ENCOUNTERED 15.5 FEET Lag of the property of the pr	1					DEPTH: 24.0 FFFT			
DATE COMMENS DEPTH BOS 12/6/2 INTIALLY ENCOUNTERED 15.5 FEET PID (PPM) USCS REMARKS 1** Asphalic Concrete over 2* Aggregate Baserock. Sandy Clay (CL), Light brown, moist, stiff, (NATIVE). CL Brick encountered in boring. Slity Clay (CL), Dark brown, moist, stiff, (NATIVE). As above; medium brown. 1221 No odor. As above; many fine send. Clayey Sand (SC), Medium brown, very moist to wet, medium search. As above; metium brown, very moist to wet, medium search. Clayey Sand (SC), Medium brown, very moist to wet, medium search. No odor. Softer at 18 feet.						GROUNOWA	TER LEV		
12/6/02 INTIALLY ENCOUNTERED 15.5 FEET (A) A B A B A B A B A B A B A B A B A B A	[-,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,			EPTH BGS
Comparison of the control of the c	1				· · · · · · · · · · · · · · · · · · ·	AITIM			
1 Asphallic Concrete over 2" Aggregate Baserock. Sandy Clay (CL), Light brown, moist, stiff, medium to coarse sand (FILL). Silty Clay (CL), Dark brown, moist, stiff, (NATIVE). CL 403 As above; medium brown. As above; medium brown. 1221 No odor. As above; many fine sand. Clayey Sand (SC), Medium brown, very moist to wet, medium sand. Clayey Sand (SC), Medium brown, very moist to wet, medium sand. As above; wet. As above; fine to medium sand, some slit. Sandy Silt (ML), Medium brown, wet, stiff, fine sand. ML Boring terminated at 24.0 feet.			1_	1.	12002	11301123		I I	10.01 LL1
Sandy Clay (CL), Light brown, moist, stiff, medium to coarse sand (Fill.L). Sity Clay (CL), Dark brown, moist, stiff, (NATIVE). Sity Clay (CL), Dark brown, moist, stiff, (NATIVE). As above; medium brown. As above; medium brown. As above; many fine sand. As above; many fine sand. CL No odor. No odor. SSC Clayey Sand (SC), Medium brown, very moist to wet, medium sand. As above; wet. As above; wet. As above; fine to medium sand, some silt. Sandy Silt (ML), Medium brown, wet, stiff, fine sand. ML Boring terminated at 24.0 feet.	рертн (FEET)	SAMPLE NO.	RECOVERY (IN)	SAMPLE INTERVAL			uscs	REMARI	KS .
sand (FILL). Sitty Clay (CL), Dark brown, molst, stiff, (NATIVE). As above; medium brown. As above; medium brown. As above; many fine sand. Ciayey Sand (SC), Medium brown, very moist to wet, medium sand. Ciayey Sand (SC), Medium brown, very moist to wet, medium sand. Ciayey Sand (SC), Medium brown, very moist to wet, medium sand. As above; wet. As above; fine to medium sand, some silt. Softer at 18 feet. Sandy Silt (ML), Medium brown, wet, stiff, fine sand. ML Boning terminated at 24.0 feet.									
Sity Clay (CL), Dark brown, moist, stiff, (NATIVE). As above; medium brown. As above; medium brown. As above; many fine sand. Clayey Sand (SC), Medium brown, very moist to wet, medium sand. Clayey Sand (SC), Medium brown, very moist to wet, medium sand. As above; wet. Softer at 18 feet. Sandy Sift (ML), Medium brown, wet, stiff, fine sand. ML Boring terminated at 24.0 feet.	1						CL		
As above; medium brown. As above; medium brown. As above; many fine sand. Clayey Sand (SC), Medium brown, very moist to wet, medium sand. Clayey Sand (SC), Medium brown, very moist to wet, medium sand. As above; wet. Clayey Sand (SC), Medium brown, very moist to wet, medium sand. As above; wet. Sc Water at approx. 15.5 feet. No odor. Softer at 18 feet. Sandy Sitt (ML), Medium brown, wet, stiff, fine sand. ML	2_				sand (FILL).			Brick encountered in	boring.
As above; medium brown. As above; medium brown. As above; many fine sand. Clayey Sand (SC), Medium brown, very moist to wet, medium sand. Clayey Sand (SC), Medium brown, very moist to wet, medium sand. As above; wet. Clayey Sand (SC), Medium brown, very moist to wet, medium sand. As above; wet. Sc Water at approx. 15.5 feet. No odor. Softer at 18 feet. Sandy Sitt (ML), Medium brown, wet, stiff, fine sand. ML					Silty Clay (CL.), Dark brown, moist, stiff, (NATIVE).		CL	************************************	
As above; medium brown. As above; medium brown. 1221 No odor. 588 No odor. 129 No odor. 179 No odor. Clayey Sand (SC), Medium brown, very moist to wet, medium sand. Clayey Sand (SC), Medium brown, very moist to wet, medium sand. As above; wet. 199 As above; fine to medium sand, some slit. Sandy Slit (ML), Medium brown, wet, stiff, fine sand. ML Boring terminated at 24.0 feet.	3						-		
As above; medium brown. As above; medium brown. 1221 No odor. 588 No odor. No odor. 179 No odor. Clayey Sand (SC), Medium brown, very moist to wet, medium sand. Clayey Sand (SC), Medium brown, very moist to wet, medium sand. As above; wet. As above; fine to medium sand, some slit. Softer at 18 feet. Sandy Slit (ML), Medium brown, wet, stiff, fine sand. ML Boring terminated at 24.0 feet.	4_		Ш	1		403			
As above; medium brown. As above; medium brown. 1221 No odor. No odor. As above; many fine sand. 179 No odor. Clayey Sand (SC), Medium brown, very moist to wet, medium sand. As above; wet. SC Water at approx. 15.5 feet. No odor. Softer at 18 feet. Sandy Sift (ML), Medium brown, wet, stiff, fine sand. ML Boring terminated at 24.0 feet.	_							No odor.	
As above; many fine sand. 1221	5			ĺ					
As above; many fine sand. 1221					As above; medium brown				
As above; many fine sand. As above; many fine sand. IT 9	6—				As above, medium brown.	1221			
As above; many fine sand. As above; many fine sand. Clayey Sand (SC), Medium brown, very moist to wet, medium sand. As above; wet. As above; wet. As above; fine to medium sand, some slit. Softer at 18 feet. Sandy Slit (ML), Medium brown, wet, stiff, fine sand. ML Boring terminated at 24.0 feet.	,-			İ		,		No odor.	
As above; many fine sand. 179	'_								
As above; many fine sand. As above; many fine sand. Clayey Sand (SC), Medium brown, very moist to wet, medium sand. Clayey Sand (SC), Medium brown, very moist to wet, medium sand. As above; wet. Sc Water at approx. 15.5 feet. No odor. Softer at 18 feet. Softer at 18 feet.	8		\Box		·	588			
As above; many fine sand. As above; many fine sand. Clayey Sand (SC), Medium brown, very moist to wet, medium sand. Clayey Sand (SC), Medium brown, very moist to wet, medium sand. As above; wet. As above; wet. As above; fine to medium sand, some silt. Softer at 18 feet. Sandy Silt (ML), Medium brown, wet, stiff, fine sand. ML Boring terminated at 24.0 feet.	_							No odor.	
As above; many fine sand. 179	9			•					
As above; many fine sand. 179	-								
13— 13— 14— 15— 15— 16— 17— 18— 19— 18— 20— 21— 21— 22— 23— Boring terminated at 24.0 feet. 179 No odor. 179 No odor. SC Water at approx. 15.5 feet. No odor. Softer at 18 feet. ML	10								
Clayey Sand (SC), Medium brown, very moist to wet, medium sand. Clayey Sand (SC), Medium brown, very moist to wet, medium sand. As above; wet. As above; fine to medium sand, some silt. Softer at 18 feet. Softer at 18 feet. Boring terminated at 24.0 feet.	44_				As above; many fine sand.			•	
No odor. Clayey Sand (SC), Medium brown, very moist to wet, medium sand. SC Water at approx. 15.5 feet. No odor.	l ''=l			i		_ i			
Clayey Sand (SC), Medium brown, very moist to wet, medium sand. As above; wet. As above; fine to medium sand, some silt. Softer at 18 feet. Softer at 18 feet. Sandy Silt (ML), Medium brown, wet, stiff, fine sand. Boring terminated at 24.0 feet.	12					179			
Clayey Sand (SC), Medium brown, very moist to wet, medium sand. As above; wet. As above; fine to medium sand, some silt. Softer at 18 feet. Sandy Silt (ML), Medium brown, wet, stiff, fine sand. Boring terminated at 24.0 feet.	-							No odor.	
Clayey Sand (SC), Medium brown, very moist to wet, medium sand. As above; wet. ISC Water at approx. 15.5 feet. No odor. Softer at 18 feet. Softer at 18 feet. Sandy Silt (ML), Medium brown, wet, stiff, fine sand. ML Boring terminated at 24.0 feet.	13 —						ļ		
Clayey Sand (SC), Medium brown, very moist to wet, medium sand. As above; wet. ISC Water at approx. 15.5 feet. No odor. Softer at 18 feet. Sandy Silt (ML), Medium brown, wet, stiff, fine sand. ML Boring terminated at 24.0 feet.									
Sand. As above; wet. As above; fine to medium sand, some silt. Softer at 18 feet. Softer at 18 feet. Sandy Silt (ML), Medium brown, wet, stiff, fine sand. Boring terminated at 24.0 feet.	14 —	-			Clayey Sand (SC), Medium brown, very moist to wet, medium		SC		
As above; wet. As above; wet. As above; fine to medium sand, some silt. Softer at 18 feet. Softer at 18 feet. Sandy Silt (ML), Medium brown, wet, stiff, fine sand. ML Boring terminated at 24.0 feet.	15 —	$\overline{}$							
No odor. No odor. No odor. Softer at 18 feet. As above; fine to medium sand, some silt. 20— 21— 22— Sandy Silt (ML), Medium brown, wet, stiff, fine sand. ML Boring terminated at 24.0 feet.		\preceq		\bowtie				Water at approx. 15.	5 feet.
As above; fine to medium sand, some silt. As above; fine to medium sand, some silt. Softer at 18 feet. Softer at 18 feet. Softer at 18 feet. Softer at 18 feet.	16		\perp		As above; wet.	199	.	No odo-	
Softer at 18 feet. As above; fine to medium sand, some silt. Softer at 18 feet.	_							INO OUOF.	
As above; fine to medium sand, some silt. As above; fine to medium sand, some silt. Sandy Silt (ML), Medium brown, wet, stiff, fine sand. Boring terminated at 24.0 feet.	17								
As above; fine to medium sand, some silt. As above; fine to medium sand, some silt. Sandy Silt (ML), Medium brown, wet, stiff, fine sand. Boring terminated at 24.0 feet.	1,							Softer at 18 feet.	
Sandy Silt (ML), Medium brown, wet, stiff, fine sand. Sandy Silt (ML), Medium brown, wet, stiff, fine sand. Boring terminated at 24.0 feet.	""-								
Sandy Silt (ML), Medium brown, wet, stiff, fine sand. ML Boring terminated at 24.0 feet.	19—				As above; fine to medium sand, some silt.				
Sandy Silt (ML), Medium brown, wet, stiff, fine sand. ML Boring terminated at 24.0 feet.	-								
Sandy Silt (ML), Medium brown, wet, stiff, fine sand. ML Boring terminated at 24.0 feet.	20 —	ļ	+						
Sandy Silt (ML), Medium brown, wet, stiff, fine sand. ML Boring terminated at 24.0 feet.									
Sandy Silt (ML), Medium brown, wet, stiff, fine sand. ML Boring terminated at 24.0 feet.	21								
Sandy Silt (ML), Medium brown, wet, stiff, fine sand. ML Boring terminated at 24.0 feet.	22	l							
24 Boring terminated at 24.0 feet.					Sandy Silt (ML), Medium brown, wet, stiff, fine sand.		ML		
_ Boring terminated at 24.0 feet.	23 —								
_ Boring terminated at 24.0 feet.		Ì							
Groundwater encountered at approximately 15 5 feet	24		\dashv		Boring terminated at 24.0 feet.				
25 Groundwater encountered at approximately 15.5 leet.	25				Groundwater encountered at approximately 15.5 feet.				
Borehole converted to MW-4 (22.5 feet total well depth).					Borehole converted to MW-4 (22.5 feet total well depth).				
Reviewed By: LOGGED BY: Brand Burfield	Reviewe	d By:			LOGGED BY: Bra	nd Burfield		•	

SOI	L E	30	RII	NG LOG				BORING NO:	SB-17			
			. ~!!					SHEE 1	OF 1			
				PROJECT NAME:	PALACE GARAGE							
1				PROJECT NUMBER				DATE: 12/6/02				
				DRILLING COMPAN	YY: V&W DRILLING							
1					: GEOPROBE PUS	H-DRILL						
1				BORING DIAMETER				DEPTH: 20.0 F	EET			
]						UNDWA						
					ATE .		СОММ		DEPTH BGS			
ļ		_	1	12/0	6/02	INITIA	LLY EN	COUNTERED	16.5 FEET			
рертн (геет)	SAMPLE NO.	RECOVERY (IN)	SAMPLE INTERVAL			PID (PPM)	USCS	RI	EMARKS			
ᆸ	Š	2	SAM									
		П	-	1" Asphaltic Concrete over 2" Aggregate Baserock.								
1				Clayey Sand (SC), Light brown, damp to moist, med fine to medium sand, many fine to medium gravel, (I		-	SC	No odor.	·			
				Silty Clay (CL), Dark brown, moist, stiff, some rootle	t voids,		CL					
3—				(NATIVÉ).								
4		\vdash				65		No odor.				
5 — 6 —				As above; medium brown.								
7						81		No odor.				
9				As above; damp to moist.		20			<i>.</i>			
12				Gravelly Sand (SW), Medium to dark brown, damp to coarse sand, fine to medium gravel.	o moist, medium	29	SW	No odor.				
14— 15—						-			•			
16				As above; ver <u>y</u> moist.		28		Water at appro	ox. 16.5 feet.			
17—		.						No odor.				
18 — — 19 —				Silty Clay (CL), Medium brown, wet, stiff.	1		CL	Moderate gase	oline odor and green			
-			\times			54		staining from 1	8.5 to 20.0 feet.			
20—				Boring terminated at 24.0 feet. Groundwater encountered at approximately 15.5 fee Borehole backfilled with cement to 3 feet below grade 6 inches below grade and topped with concrete.	de, soil to							
22 23				5 mones bolom grade and topped with controller.								
24 —												
25 —												
Reviewe	d By:	Li.		LC	GGED BY: Brand B	urfield						


.

MONITORING	WELL RECO	RD	WELL/BORING NO: 16B-16
DATE: 12/6/02	PROJECT NAME:	KE	PROJECT NO: 579-26033
LOCATION PLAN:		C: TWN:	RGE: LAT: LONG:
	DF	RILLERS:	
		V+W J	RELEW - RYN KUBIE
	PE	ACPWA	WOZ-1160
	_		SHALLOW SINGLE CASED MONITORING
			☐ INTERMEDIATE ☐ DOUBLE CASED ☐ RECOVERY
MELL COM	ITANATIO	☐ TEMPORARY	DEEP OTHER OTHER
WELL SCH	IEWANC	DECON.	STEAM CLEAN HIGH PRESSURE WASH
4	/		SOAP WASH OTHER
14 1	TOC ABOVE GROUND IF	CASING TYPE:	PVC STAINLESS STEFLON OTHER
	RISER BOX		THREADED WELDED COUPLED
	OR STICKUP	PIT CASING:	SCREWED OTHER
	FT.		
		WELL SCREEN: DIAMETER:	
			0.010 0.020 OTHERIN
ANNULAR	BOREHOLE DIAMETER	DRILLING	SOLID STEM HOLLOW STEM MUD ROTARY
BACKFILL			☐ AIR ROTARY ☐ DIRECT PUSH ☐ HAND AUGER
			OTHER
4.5 FT.		BIT SIZE: DRILLING MUD:	2"
	CASING		OTHER
CEMENT CEMENT	DIAMETER	CENTRALIZER:	YES XNO
WELL GROUT□	7/4 IN.		FLUSH MOUNT STICKUP RISER BOX
DEPTH SILICA SAND	SCH.	LOCK TYPE:	☐ DOLPHIN ☐ MASTER KEY NO
TOC OTHER	 40	PAD:	□ 2'X2' □ 4'X4' □ OTHER
22.5	,	CUTTINGS:	DRUMMED NUMBER OF DRUMS
FT.			SPREAD TOTHER
SEAL	BENTONITE MASONRY SAND	DEVELOPMENT	□ NONE □ BAILING □ PUMPING □ AIR LIFT
[FT.]	OTHER	METHOD:	SURGE & BLOCK OTHER
		TIME:	☐ 10 MIN ☐ 20 MIN ☐ OTHERMIN ☐ 5 GAL ☐ 10 GAL ☐ OTHER ☐ GAL
		WATER BEFORE:	SILTY TURBID OPAQUE CLEAR
FILTER PACK	↑ WELL	WATER AFTER: EVIDENT ODOR:	SILTY TURBID OPAQUE CLEAR YES NO TYPE
	SCREEN		
TYPE	LENGTH	DEVELOPMENT WATER:	DRUMMED NUMBER OF DRUMS SPREAD TREATED POTW OTHER
#2/12	19 17	WATER LEVEL:	INITIAL 15.5 FT BTOC BLS
Silvidi	T		1/2/03 13.45 FT BELOW TOC
Y	V*	DATE:	,
OVER DRILL	WELL SUMP	DATE:	FT BELOW TOC
1.5 FT.	YES X NO	NOTES: (DE	SCRIBE ALL NON-STANDARD METHODS & MATERIALS)
(CROSS OUT IF	IN.		
NOT DRILLED) ↓			
<u></u> ₩			
[psi]	PF	REPARED BY:	3. BURFIELD

APPENDIX D

SURVEY DATA

Monitoring Well Exhibit
Prepared for:
PSI



DESCRIPTION	NORTHING	EASTING	ELEV (PVC)	ELEV (BOX)
MW-1 MW-2 MW-3 MW-4	2083680, 4 2083607, 1 2083636, 1 2083539, 2	6086328. 7 6086260. 5 6086195. 0 6086261. 4	37. 59 37. 12 37. 01 37. 09	37. 84 37. 45 37. 27 37. 45
MW-1 MW-2 MW-3 MW-4	LATITUDE 37. 7059301 37. 7057253 37. 7058019 37. 7055389	LBNGITUDE +122. 1432028 -122. 1434341 -122. 1436622 -122. 1434268		

BASIS OF COORDINATES

COURDINATES ARE CALIFORNIA STATE PLANE ZONE 3 COURDINATES FROM GPS
OBSERVATIONS USING UNIVERSITY OF CALIFORNIA BAY AREA DEFORMATION CORS
STATION OBSERVATION FILES AND BASED ON THE CALIFORNIA SPATIAL REFERENCE
CENTER DATUM, REFERENCE EPOCH 2000. 35.
COURDINATE DATUM IS NAD 83(1986)
DATUM ELLIPSOID IS GRS80
REFERENCE GEDID IS NGS99

CORS STATIONS USED WERE TIBB AND POTB.

ELEVATIONS ARE BASED ON SAN LEANDRO BENCHMARK. ELEVATION=39.25'.

0 15 30 60 90 SCALE IN FEET Palace Garage 14336 Washington Avenue San Leandro Alameda County California



1450 Harbor Blvd. Ste. D West Sacramento California 95691 (916) 372-8124 tom@morrowsurveying.com Date: 02/05/03 Scale: 1"= 30" Sheet 1 of 1 Revised: Field Book: MW-12 Dwg. No. 6381-024DT

FLUID MEASUREMENT FIELD DATA

							SHEET:	OF \	7
DATE: 12 る;	102	PROJECT NAME:	PALACE (SARAGE		PROJECT NO:	26033		
WATER LEVEL M	EASUREMENT IN		OLINST			SERIAL NO:			
PRODUCT DETE	CTION INSTRUME	NT:				SERIAL NO:			
EQUIP. DECON:	☐ ALCONOX	WASH DIST	7/DEION 1 RINSE	☐ ISOPROPANOL	☐ ANALYTE	FREE FINAL RINSE	☐ TAP WATER F	INAL RINSE	
☐ TAP WA	TER WASH	LIQUINOX WASH	☐ DIST/DEIC	ON 2 RINSE	OTHER SOLVENT	☐ DIST/DEION	FINAL RINSE	☐ AIR DRY	
WELL NUMBER	GROUND SURFACE ELEVATION	TOP OF CASING ELEVATION	DEPTH TO PRODUCT BELOW TOC	DEPTH TO WATER BELOW TOC	WELL DEPTH BELOW TOC	PRODUCT THICKNESS	WATER TABLE ELEVATION	ACTUAL TIME	
mw-I				13.71	24.00				2"
MW-2				13,44	24.00				$\Box u$
mw-3					24.00				11 COVERED
MW-4				13,50	22.5] r"
Mw-1				13.62			<u> </u>	1237	-
MW-2				13,38				1242	
Mw-3			- · · ·	13,29	24.00			1234	_
Mw-4				13,45	0.1.0			1244	1
				·					
									_
	·								_]
									_
						\			_
		<u> </u>							_

PSI

Rev. 12/95

				_			WELL N	10: MW -	-}
DATE:		PROJEC	T NAME:				PROJE	CT NO:	:
WEATHE	R CONDIT	ions:							
WELL DI	AMETER (I	N.)	1	<u> </u>	<u> </u>	6	OTHER		
SAMPLE	TYPE:	GROUN	DWATER	WAS	TEWATER	SUF	RFACE WATE	R [] 0]	THER
WELL DE	PTH (TOC) 76		Fì	r. DEPTH	TO WATE	ER BEFORE	PURGING	(TOC) [3.7/FT.
LENGTH	OF WATE	٦ ٩.	29	F	CALCU	LATED O	NE WELL VO	DLUME1:	~ 1 , 7 GAL.
PURGING	G DEVICE:				⊘ DEDK	CATED (DISPOSA	BLE 🕏 DE	CONTAMINATED
SAMPLIN	NG DEVICE				Z DEDK	CATED (DISPOSA	BLE 🗑 DE	CONTAMINATED
EQUIP.	DECON.	TA	P WATER	WASH		ISOPROP			REE FINAL RINSE
	CONOXW		=	EION 1 RINS	_		_	· · · · · · · · · · · · · · · · · · ·	N FINAL RINSE
	QUINOX WA			ION 2 RINS			ER FINAL RII	NSE L	AIR DRY
	VER PRESI				D FIELD	PRESER	VED		·
WATERA	ANALYZER	MODEL 8	SERIAL N	10: M	YRON L	- 602	:	· · · · · · · · · · · · · · · · · · ·	
ACTUAL TIME (MIN)	CUMUL. VOLUME PURGED (GAL)	TEMP	SPECIFIC CONDUCT.	ρΗ	DISS. OXYGEN	TURBIDITY (NTUs)	WATER APPEAR CL=CLEAR CO=CLOUDY	Ī .	REMARKS ODOR, COLOR, PID)
	(GAL)						TU=TURB!D	ore	7
1310	INITIAL	17.2	457	7.57			C470/00	50	\$ 60
1311	2.0	177	940	7.56			co	48	6 46
1312	5.0	N.S	946	7.57			Co	49	650
13 14	6.5	(7,9	943	7.48			CURO	45	648
							<u> </u>		
		ļ		 					
	ļ								
							<u> </u>		
	<u> </u>			<u> </u>					
								<u> </u>	
DEPTH T	O WATER	AFTER P	URGING (T	OC)	FT.	SAMPLE	FILTERED		
NOTES:					SAMPLE :	TIME:	1315	ID#	MW-1
					DUPLICA"	TE 🗌	TIME:	1D#:	
					EQUIP. BI	LANK: 🗌	TIME:	ID#:	
					PREPARE	D BY:			

PSI 1 A 1 FOOT LENGTH OF WATER = 0.05 GAL IN 1" DIA. PIPE 0.17 GAL IN 2" DIA PIPE 0.65 GAL IN 4" DIA PIPE 1.5 GAL IN 6" DIA P Rev. 12/95

							WELL N	10: M	W-2	
DATE: (2 31 02	PROJEC	T NAME:	PALA	CE		PROJE	CT NO:	26033	
WEATHER CONDITIONS: SUNNY, BREEZY, COOL										
WELL DI	WELL DIAMETER (IN.)									
SAMPLE	TYPE:	GROUN	DWATER	WAS	TEWATER	SUR	FACE WATE	R []C)ŢHER	
WELL DE	РТН (ТОС) 2	4	FT	. DEPTH	TO WATE	R BEFORE	PURGINO	3 (TOC) 13, 44 FT.	
LENGTH	LENGTH OF WATER 9.56 FT. CALCULATED ONE WELL VOLUME!: ~1,7 GAL.									
PURGING	PURGING DEVICE: DEDICATED DISPOSABLE DECONTAMINATED									
SAMPLIN	G DEVICE	:		·	DEDIC	CATED [] DISPOSA	BLE 🛜 D	ECONTAMINATED	
EQUIP. D	ECON.	☐ TA	AP WATER V	VASH		ISOPROPA			FREE FINAL RINSE	
	CONOXW		_	ION 1 RINS	_		_	_	ON FINAL RINSE	
	ZUINOX WA	\SH	DIST/DE	ION 2 RINS	<u> </u>	TAP WATE	R FINAL RII	NSE L	AIR DRY	
			1: 🛭 LAB							
WATERA	NALYZER	MODEL 8	SERIAL N	io: M	YRUN	L 602	.155			
ACTUAL TIME (MIN)	CUMUL. VOLUME PURGED (GAL)	TEMP □ °F □ °C	SPECIFIC CONDUCT.	рΗ	DISS. OXYGEN	TURBIDITY (NTUs)	WATER APPEAR CL=CLEAR CO=CLOUDY TU=TURBID	(EVIDEN	REMARKS IT ODOR, COLOR, PID)	
1243	INITIAL	17,2	1144	7,65			OUTURO	80	796	
1245	7.0	14,0	1149	7.55			ÇO	90	796	
1246	4,0	18.2	<u> </u>	7.43			01/00	86	798	
1247	5.0	18.2	1150	7.32			0	64	797	
		<u>-</u>								
	-									
	·		,							
	 -									
DEPTH T	O WATER	AFTER P	URGING (T	OC)	FT.	SAMPLE	FILTERED	YES [NO SIZE	
NOTES:					SAMPLE 1	IME: 17	50	ID#	M W-2	
					DUPLICAT	TE []	TIME:	ID#:		
					EQUIP. BL	ANK: 🗌	TIME:	ID#:		
<u></u>					PREPARE	DBY:				

	WELL NO: MW-3
DATE: 14 02/03 PROJECT NAME: PALAC	PROJECT NO: 2G033
WEATHER CONDITIONS:	
WELL DIAMETER (IN.) 1 2	46OTHER
SAMPLE TYPE: GROUNDWATER WAS	STEWATER SURFACE WATER OTHER
WELL DEPTH (TOC) 224 F	T. DEPTH TO WATER BEFORE PURGING (TOC) (329 FT.
LENGTH OF WATER 10.71 F	T. CALCULATED ONE WELL VOLUME ¹ : ~1,7 GAL.
PURGING DEVICE:	☐ DEDICATED ② DISPOSABLE ☐ DECONTAMINATED
SAMPLING DEVICE:	DEDICATED SOURCE DECONTAMINATED
EQUIP. DECON. TAP WATER WASH	ISOPROPANOL ANALYTE FREE FINAL RINSE
ALCONOX WASH DIST/DEION 1 RIN	
LIQUINOX WASH DIST/DEION 2 RIN	
CONTAINER PRESERVATION: 2 LAB PRESERV	
WATER ANALYZER MODEL & SERIAL NO: My	ron L 602 154
ACTUAL CUMUL. TEMP SPECIFIC pH TIME VOLUME	DISS. TURBIDITY WATER REMARKS OXYGEN (NTUS) APPEAR (EVIDENT ODOR, COLOR, PID) CL=CLEAR CO=CLOUDY TU=TURBID ORP T D 5
1300 INITIAL 19,3 677 8,40	
1304 2.0 19.0 686 7.32	
13084.0 19.06477.04	(T) (1)
1312 6.0 19.0 646 6.94	
DEPTH TO WATER AFTER PURGING (TOC)	FT. SAMPLE FILTERED YES NO SIZE
NOTES:	SAMPLETIME: 1315 ID# MW-3
	DUPLICATE TIME: ID#:
	EQUIP. BLANK: TIME: ID#:
	PREPARED BY:

	WELL NO: MW-4				
DATE: 12/3, 62 PROJECT NAME: PALAC	PROJECT NO: 26033				
WEATHER CONDITIONS:					
WELL DIAMETER (IN.) 1 2 4 6 OTHER					
SAMPLE TYPE: MI GROUNDWATER WAS	TEWATER SURFACE WATER OTHER				
WELL DEPTH (TOC) 22,5 F	DEPTH TO WATER BEFORE PURGING (TOC) / \$.5 FT.				
LENGTH OF WATER //, O F	CALCULATED ONE WELL VOLUME¹: ~,5 GAL.				
PURGING DEVICE:	DEDICATED DISPOSABLE DECONTAMINATED				
SAMPLING DEVICE:	DEDICATED DISPOSABLE DECONTAMINATED				
EQUIP. DECON. TAP WATER WASH	☐ ISOPROPANOL ☐ ANALYTE FREE FINAL RINSE				
ALCONOXWASH DIST/DEION 1 RINS					
LIQUINOX WASH DIST/DEION 2 RINS					
CONTAINER PRESERVATION: LAB PRESERVA					
WATER ANALYZER MODEL & SERIAL NO: MYE	on 1602155				
ACTUAL CUMUL. TEMP SPECIFIC pH TIME VOLUME 0 °F CONDUCT. (MIN) PURGED 0 °C	DISS. TURBIDITY WATER REMARKS OXYGEN (NTUS) APPEAR (EVIDENT ODOR, COLOR, PID) CL=CLEAR				
(GAL) US	TU=TURBID ORP TPS				
1223 INITIAL 18.6 804 9.32	TU B9 547				
1224 , 5 18.8 816 8.30	TU 86 556				
1225 1,0 18.4 783 8.01	00 91 532				
1226 1.5 18.6 788 7.81	5LT CO 92 536				
No.					
<u> </u>					
DEPTH TO WATER AFTER PURGING (TOC) FT. SAMPLE FILTERED YES NO SIZE					
NOTES: SAMPLE TIME: 1230 ID# MW-4					
	DUPLICATE TIME: ID#:				
EQUIP. BLANK: TIME: ID#:					
	PREPARED BY:				

APPENDIX F

LABORATORY RESULTS AND CHAIN-OF-CUSTODY RECORDS

Basic Laboratory, Inc.

Report To:

Attention:

P.S.1.

4703 TIDEWATER AVE., STE.B

OAKLAND, CA 94601

FRANK POSS

Lab No:

0301059

Date:

01/15/03 (510) 434-9200

Phone: Date Sampled:

12/31/02

Date Received:

01/03/02

Project Name: PALACE GARAGE

Project No.:

2G033

Sample

WATER TESTING Description:

Page 1 of 9

TPH-Gas Range

4-Bromofluorobenzene

Reporting <u>Limit</u>

Date

Test: Method: Units:

Organics 8015 ug/l

Surrogate

%

43-155

ug/l

<u>Analyzed</u>

Sample ID

Control Limit:

MW-1	4800	66,6	50	01/13/03
MW-2	1670	100	50	01/13/03
MW-3	n	85,6	50	01/13/03
MW-4	n	102	50 .	01/13/03

Comments:

California D.O.H.S. Cert. #1677.

n - Not detected at the reporting limit.

Reported by:

Basic Laboratory, Inc.

EPA METHOD 8260

Report To:

P.S.I.

Lab Number:

0301059-1

4703 TIDEWATER AVE., STE.B

Phone:

510-434-9200

OAKLAND, CA 94601

Date Sampled:

12/31/02

Attention:

FRANK POSS

Date Received:

01/03/02

Project Name:

PALACE GARAGE

Date Analyzed:

01/13/03

Project Number:

2G033

Date Reported:

01/15/03

Sampling Location:

Sample ID:

MW-1 WATER

Sample Matrix: Sample Collected By:

CHRIS MERRITT

	PAGE 2 OF 9				
COMPOUND	RESULT	REPORTING	QUANTITATION LIMIT		
		UNITS			
Acetone	n	ug/l	5.0		
Acrylonitrile		ug/l	5.0		
Benzene	1030	ug/l	0.5		
Bromobenzene	n	ug/l	0.5		
Bromochloromethane	n	ug/l	0.5		
Bromodichloromethane	n	ug/l	0.5		
Bromoform	n	ug/l	0.5		
Bromomethane	n	ug/l	0.5		
2-Butanone (MEK)	n	ug/l	5.0		
n-Butylbenzene	24.3	ug/l	0.5		
sec-Butylbenzene	11.2	ug/l	0.5		
tert-Butylbenzene	n	ug/l	0.5		
Carbon Disulfide	n	ug/l	0.5		
Carbon tetrachioride	n	ug/l	0.5		
Chlorobenzene	n	ug/l	0.5		
Chloroethane	n	ug/l	0.5		
2-Chloroethylvinylether	n	ug/l	0.5		
Chloroform	n	ug/l	0.5		
Chloromethane	n	ug/l	0.5		
2-Chlorotoluene	n	ug/l	0.5		
4-Chlorotoluene	n	ug/l	0.5		
Dibromochloromethane	п	ug/l	0.5		
1,2-Dibromo-3-Chloropropane	18.4	ug/l	0.5		
1,2-Dibromoethane	n	ug/l	0.5		
Dibromomethane	n	ug/l	0.5		
1,2-Dichlorobenzene	n	ug/l	0.5		
1,3-Dichlorobenzene	n	ug/l	0.5		
1,4-Dichlorobenzene	n	ug/l	0.5		
Dichlorodifluoromethane	n	ug/l	0.5		
1,1-Dichloroethane	n	ug/i	0.5		
1,2-Dichloroethane	n	ug/l	0.5		
1,1-Dichloroethene	n	ug/l	0.5		
cis-1,2-Dichloroethene	В	ug/l	0.5		
trans-1,2-Dichloroethene	n	ug/l	0.5		
1,2-Dichloropropane	n	ug/l	0.5		

EPA METHOD 8260

Report To:

P.S.I.

Lab Number:

0301059-1

PAGE 3 OF 9

		PAGE 3 OF 9	u a a a a a a a a a a a a a a a a a a a
COMPOUND	RESULT	REPORTING	QUANTITATION
		UNITS	LIMIT
		0,111.0	
1,3-Dichloropropane	n	ug/l	0.5
2,2-Dichloropropane	n	ug/l	0.5
1,1-Dichloropropene		ug/l	0.5
cis-1,3-Dichloropropene	Л	ug/l	0.5
trans-1,3-Dichloropropene	П	ug/l	0.5
1.4-Dioxane	n	ug/l	25
Ethyl Benzene	1690	ug/l	0.5
Ethyl-Tert-Butyl Ether (ETBE)	n	ug/I	0.5
Hexachlorobutadiene	n	ug/l	0.5
2-Hexanone (MBK)	n	ug/l	5.0
Isopropylbenzene	П	ug/I	0.5
Di-Isopropyl Ether (DIPE)	n	ug/l	0.5
p-isopropytoluene	19.2	ug/l	0.5
4-Methyl-2-Pentanone (MIBK)	n	ug/l	5.0
Methylene Chloride	n	ug/l	1.0
Methyl Tert-Butyl Ether (MTBE)	n	ug/I	0.5
Napthalene	2480	ug/l	0.5
n-Propylbenzene	218	ug/l	0.5
Styrene	an an an an an an an an an an an an an a	ug/l	0.5
Tert-Amyl Methyl Ether (TAME)	n	ug/l	0.5
1,1,1,2-Tetrachloroethane	ก	ug/l	0.5
1.1,2,2-Tetrachloroethane	n	ug/l	0.5
Tetrachloroethene	ſ	ug/l	0.5
Tetrahydrofuran	Π	ug/l	5.0
tert - Butanol (TBA)	'n	ug/l	50
Toluene	2380	ug/l	0.5
1,2,3-Trichlorobenzene	л	ug/l	0.5
1,2,4-Trichlorobenzene	n	ug/l	0.5
1,1,1-Trichloroethane	n	ug/i	0.5
1,1,2-Trichloroethane	n	ug/l	0.5
Trichloroethene	n	ug/I	0.5
1,1,2-Trichlorotrifluoroethane	ก	ug/l	0.5
Trichlorofluoromethane	n	ug/l	0.5
1,2,3-Trichloropropane	n	ug/l	0.5
1,2,4-Trimethylbenzene	1690	ug/l	0.5
1,3,5-Trimethylbenzene	451	ug/l	0.5
Vinyl Acetate	ŋ	ug/l	0.5
Vinyl Chloride	n	ug/l	0.5
Total Xylenes	9220	ug/ł	1.0
SURROGATES	RECOVERY	%	CONTROL
	, o 7 bi\1		1
			LIMITS (%)
			00 445
1,2-Dichloroethane-d4	84.6	%	28-145
Toluene-d8	122	%	52-150
4-Bromofluorobenzene	66.6	%	43-155
1		<u> </u>	<u> </u>

Comments

Caifornia D.O.H.S Cert # 1677

n - Not detected at the quantitation limit.

Reported By

EPA METHOD 8260

Report To:

P.S.I.

Lab Number:

0301059-2

4703 TIDEWATER AVE., STE.B

Phone:

510-434-9200

OAKLAND, CA 94601

Date Sampled:

12/31/02

Attention:

FRANK POSS

Date Received:

01/03/02

Project Name:

PALACE GARAGE

Date Analyzed:

01/13/03

Project Number:

2G033

Date Reported:

01/15/03

Sampling Location:

Sample ID: Sample Matrix: MW-2

WATER

Sample Collected By:

CHRIS MERRITT

PAGE 4 OF 9

		PAGE 4 OF 9			
COMPOUND	RESULT	REPORTING	QUANTITATION		
		UNITS	ЦМП*		
			F0		
Acetone	n	ug/l	50		
Acrylonitrile	<u>n</u>	ug/i	50		
Benzene	1030	ug/l	5		
Bromobenzene	n	ug/l	5		
Bromochloromethane	n	ug/l	5		
Bromodichloromethane	· n	ug/l	5		
Bromoform	n	ug/l	5		
Bromomethane	n	ug/l	5		
2-Butanone (MEK)	n	ug/l	50		
n-Butylbenzene	30.8	ug/l	5		
sec-Butylbenzene	15.9	ug/l	5		
tert-Butylbenzene	n	ug/l	5		
Carbon Disulfide	n	ug/l	5		
Carbon tetrachloride	п	ug/l	5		
Chlorobenzene	n	ug/l	5		
Chloroethane	n	ug/l	5		
2-Chloroethylvinylether	ń	ug/l	5		
Chloroform	П	ug/l	5		
Chloromethane	n	ug/l	5		
2-Chlorotoluene	n	ug/l	5		
4-Chlorotoluene	n	ug/l	5		
Dibromochloromethane	n	ug/l	5		
1,2-Dibromo-3-Chloropropane	n	ug/I	5		
1,2-Dibromoethane	n	ug/l	5		
Dibromomethane	n	ug/l	5		
1,2-Dichlorobenzene	n	ug/l	5		
1,3-Dichlorobenzene	n	ug/l	5		
1.4-Dichlorobenzene	n	ug/l	5		
Dichlorodifluoromethane	1	ug/l	5		
1,1-Dichloroethane	n	ug/I	5		
1,2-Dichloroethane	n	ug/l	5		
1.1-Dichloroethene	n	ug/l	5		
cis-1,2-Dichloroethene	n	ug/l	5		
trans-1.2-Dichloroethene	n	ug/l	5		
1,2-Dichloropropane	n .	ug/l	5		

EPA METHOD 8260

Report To:

P.S.I.

Lab Number:

0301059-2

PAGE 5 OF 9

		PAGE 5 OF 9	,		
COMPOUND	RESULT	REPORTING	QUANTITATION		
		UNITS	LIMIT*		
1,3-Dichloropropane	n	ug/l	5		
2,2-Dichloropropane	វា	ug/l	5		
1,1-Dichloropropene	n	ug/l	5		
cls-1,3-Dichloropropeле	n	ug/l	5		
trans-1,3-Dichloropropene	n	ug/!	5		
1,4-Dioxane	n	ug/i	250		
Ethyl Benzene	23.1	ug/l	5		
Ethyl-Tert-Butyl Ether (ETBE)	n	ug/l	5		
Hexachlorobutadiene	n	ug/l	5		
2-Hexanone (MBK)	n	ug/l	50		
Isopropylbenzene	106	ug/l	5		
Di-Isopropyl Ether (DIPE)	n	ug/l	5		
p-Isopropyitoluene	n	ug/l	5		
4-Methyl-2-Pentanone (MIBK)	n	ug/l	50		
Methylene Chloride	n	ug/l	10		
Methyl Tert-Butyl Ether (MTBE)	n	ug/l	5		
Napthalene	914	ug/l	5		
n-Propylbenzene	207	ug/l	5		
Styrene	n	ug/l	5		
Tert-Amyl Methyl Ether (TAME)	n	ug/l	5		
1,1,1,2-Tetrachloroethane	n	ug/l	5		
1.1.2.2-Tetrachloroethane	n	ug/l	5		
Tetrachloroethene	n	ug/l	5		
Tetrahydrofuran	n	ug/l	50		
tert - Butanol (TBA)	n	ug/i	500		
Toluene	11.0	ug/l	5		
1.2.3-Trichlorobenzene	n	ug/l	5		
1,2,4-Trichlorobenzene	n	ug/l	5		
1,1,1-Trichloroethane	n n	ug/l	5		
1,1,2-Trichloroethane	n	ug/l	5		
Trichloroethene	n n	ug/l	5		
1,1,2-Trichlorotrifluoroethane	n n	ug/l	5		
Trichlorofluoromethane	n	ug/l	5		
1,2,3-Trichloropropane	n	ug/l	5		
1,2,4-Trimethylbenzene	n	ug/l	5		
1,3,5-Trimethylbenzene	10.0	ug/l	5		
Vinyl Acetate	n	ug/l	5		
Vinyl Chloride	n	ug/l	5		
Total Xylenes	16.4	ug/l	10		
			CONTROL		
SURROGATES	RECOVERY	%	CONTROL		
			LIMITS (%)		
1,2-Dichloroethane-d4	77.6	%	28-145		
Toluene-d8	113	%	52-150		
4-Bromofluorobenzene	100	%	43-155		
•					

Comments:

Calfornia D.O.H.S Cert # 1677

n - Not detected at the quantitation limit.

* - QL raised due to required dilution

Repetied By

EPA METHOD 8260

Report To:

P.S.I.

Lab Number:

0301059-3

4703 TIDEWATER AVE., STE.B

Phone:

510-434-9200

OAKLAND, CA 94601

Date Sampled:

12/31/02

Attention:

FRANK POSS

Date Received:

01/03/02

Project Name:

PALACE GARAGE

Date Analyzed:

01/14/03

Project Number:

2G033

Date Reported:

01/15/03

Sampling Location:

Sample ID:

MW-3

Sample Matrix:

WATER

Sample Collected By:

CHRIS MERRITT

PAGE 6 OF 9

	PAGE OUP 9										
COMPOUND	RESULT	REPORTING	QUANTITATION								
		UNITS	LIMIT*								
			,								
Acetone	n	ug/l	25								
Acrylonitrile	'n	ug/l	25								
Benzene	n	цд/І	2.5								
Bromobenzene	n	ug/l	2.5								
Bromochloromethane	n	ug/l	2.5								
Bromodichloromethane	n	ug/l	2.5								
Bromoform	n	ug/l	2.5								
Bromomethane	n	ug/l	2.5								
2-Butanone (MEK)	n	ug/l	25								
n-Butylbenzene	n	ug/l	2.5								
sec-Butylbenzene	n	ug/l	2.5								
tert-Butylbenzene	n	ug/l	2.5								
Carbon Disulfide	n	ug/l	2.5								
Carbon tetrachloride	n	ug/l	2.5								
Chlorobenzene	n	ug/l	2.5								
Chloroethane	n	ug/l	2.5								
2-Chloroethylvinylether	n	ug/l	2.5								
Chloroform	n	ug/l	2.5								
Chloromethane	n	ug/l	2.5								
2-Chlorotoluene	n	ug/l	2.5								
4-Chlorotoluene	n	ug/l	2.5								
Dibromochloromethane	n	ug/l	2.5								
1,2-Dibromo-3-Chloropropane	n	ug/l	2.5								
1,2-Dibromoethane	n n	ug/l	2.5								
Dibromomethane	n	ug/l	2.5								
1,2-Dichlorobenzene	n	ug/l	2.5								
1,3-Dichlorobenzene	n	ug/i	2.5								
1,4-Dichlorobenzene	n	ug/l	2.5								
Dichlorodifluoromethane	n	ug/l	2.5								
1,1-Dichloroethane	n	ug/l	2.5								
1,2-Dichloroethane	n	ug/l	2.5								
1,1-Dichloroethene	n	ug/l	2.5								
cis-1,2-Dichloroethene	n	ug/l	2.5								
trans-1,2-Dichloroethene	n	ug/l	2.5								
1,2-Dichloropropane	n	ug/l	2.5								

EPA METHOD 8260

Report To:

P.S.I.

Lab Number:

0301059-3

PAGE 7 OF 9

	PAGE 7 OF 9										
COMPOUND	RESULT	REPORTING	QUANTITATION								
·		UNITS	LIMIT*								
1,3-Dichloropropane	n	ug/l	2.5								
2,2-Dichloropropane	n	ug/l	2.5								
1,1-Dichloropropene	0	ug/l	2.5								
cis-1,3-Dichloropropene	n	ug/l	2.5								
trans-1,3-Dichloropropene	n	ug/l	2.5								
1,4-Dioxane	n	ug/l	125								
Ethyl Benzene	n	ug/l	2.5								
Ethyl-Tert-Butyl Ether (ETBE)	n	ug/l	2.5								
Hexachlorobutadiene	n	ug/l	2.5								
2-Hexanone (MBK)	n	ug/l	25								
Isopropylbenzene	n .	ug/l	2.5								
Di-Isopropyl Ether (DIPE)	ก	ug/l	2.5								
p-Isopropyltoluene	n	ug/l	2.5								
4-Methyl-2-Pentanone (MIBK)	n	ug/l	25								
Methylene Chloride	ก	ug/l	5								
Methyl Tert-Butyl Ether (MTBE)	n	ug/l	2.5								
Napthalene	П	ug/l	2.5								
n-Propylbenzene	n	ug/l	2.5								
Styrene	n	ug/l	2.5								
Tert-Amyl Methyl Ether (TAME)	n	ug/l	2.5								
1,1,1,2-Tetrachloroethane	n	ug/l	2.5								
1.1.2.2-Tetrachloroethane	n	ug/l	2.5								
Tetrachloroethene	n n	ug/l	2.5								
Tetrahydrofuran	n "	ug/l	25								
tert - Butanol (TBA)	n "	ug/l	250								
Toluene		ug/l	2.5								
1,2,3-Trichlorobenzene	. n	ug/l	2.5								
1,2,4-Trichlorobenzene	n "	ug/l	2.5								
1,1,1-Trichloroethane		ug/l	2.5								
1,1,2-Trichloroethane		ug/l	2.5								
Trichloroethene	n n	ug/i	2.5								
	n	ug/l	2.5								
1,1,2-Trichlorotrifluoroethane	<u>n</u>	ug/l	2.5								
Trichlorofluoromethane	n	ug/l	2.5								
1,2,3-Trichloropropane	n	ug/l	2.5								
1,2,4-Trimethylbenzene	<u>n</u>		2.5								
1,3,5-Trimethylbenzene	<u>n</u>	ug/l	2.5								
Vinyl Acetate	<u>n</u>	ug/l	2.5								
Vinyl Chloride	n	ug/l ug/l	5								
Total Xylenes	n	i i i i i i i i i i i i i i i i i i i	· · · · · · · · · · · · · · · · · · ·								
SURROGATES	RECOVERY	%	CONTROL								
			LIMITS (%)								
1,2-Dichloroethane-d4	115	%	28-145								
Toluene-d8	85.8	%	52-150								
4-Bromofluorobenzene	85.6	%	43-155								

Comments:

Caifornia D.O.H.S Cert # 1677

n - Not detected at the quantitation limit.

* - QL raised due to required dilution

Reported By

EPA METHOD 8260

Report To:

P.S.I.

Lab Number:

0301059-4

4703 TIDEWATER AVE., STE.B

Phone:

510-434-9200

OAKLAND, CA 94601

Date Sampled:

12/31/02

Attention:

FRANK POSS

Date Received:

01/03/02

Project Name:

PALACE GARAGE

Date Analyzed:

01/14/03

Project Number:

2G033

Date Reported:

01/15/03

Sampling Location:

Sample ID:

MW-4

Sample Matrix:

WATER

Sample Collected By:

CHRIS MERRITT

PAGE 8 OF 9

	PAGE 8 OF 9												
COMPOUND	RESULT	REPORTING	QUANTITATION										
		UNITS	LIMIT*										
Acetone	n	ug/l	100										
Acrylonitrile	n	ug/l	100										
Benzene	n	ug/l	· 10										
Bromobenzene	n	ug/l	10										
Bromochloromethane	n	ug/l	10										
Bromodichloromethane	n	ug/l	10										
Bromoform	n	ug/l	10										
Bromomethane	n	ug/l	10										
2-Butanone (MEK)	n	ug/l	100										
n-Butylbenzene	n	ug/l	10										
sec-Butylbenzene	П	ug/l	10										
tert-Butylbenzene	n	ug/l	10										
Carbon Disulfide	n	ug/l	10										
Carbon tetrachloride	n	ug/l	10										
Chlorobenzene	n	ug/l	10										
Chloroethane	n	ug/l	10										
2-Chloroethylvinylether	n	ug/l	10										
Chloroform	n	ug/l	10										
Chloromethane	n	ug/l	10.										
2-Chlorotoluene	n	ug/l	10										
4-Chlorotoluene	n	ug/l	10										
Dibromochloromethane	n	ug/l	10										
1,2-Dibromo-3-Chloropropane	n	ug/l	10										
1.2-Dibromoethane	n	ug/l	10										
Dibromomethane	ก	ug/l	10										
1,2-Dichlorobenzene	n	ug/l	10										
1,3-Dichlorobenzene	n	ug/l	10										
1.4-Dichlorobenzene	n	ug/l	10										
Dichlorodifluoromethane	n	ug/l	10										
1.1-Dichloroethane	n	ug/l	10										
1,2-Dichloroethane	n	ug/l	10										
1,1-Dichloroethene	n	ug/l	10										
cis-1,2-Dichloroethene	n	ug/l	10										
trans-1,2-Dichloroethene	n	ug/l	10										
1,2-Dichloropropane	n	ug/l	10										

EPA METHOD 8260

Report To:

P.S.I.

Lab Number:

0301059-4

PAGE 9 OF 9

COMPOUND	RESULT	REPORTING	QUANTITATION			
SOMPOOND	KLOOLI	UNITS	LIMIT*			
		UNITS	LIMIT "			
1,3-Dichloropropane	n	ug/l	10			
2,2-Dichloropropane	n	ug/l	10			
1,1-Dichloropropene	n	ug/l	10			
cis-1,3-Dichloropropene	n	ug/l	10			
trans-1,3-Dichloropropene	n	ug/l	10			
1,4-Dioxane	П	ug/l	500			
Ethyl Benzene	П	ug/l	10			
Ethyl-Tert-Butyl Ether (ETBE)	n	ug/l	10			
-lexachlorobutadiene	n	ug/l	10			
2-Hexanone (MBK)	n	ug/l	100			
sopropylbenzene	n	ug/l	10			
Di-Isopropyl Ether (DIPE)	n	ug/l	10			
p-Isopropyltoluene	n	ug/l	10			
4-Methyl-2-Pentanone (MIBK)	n	ug/l	100			
Methylene Chloride	n	ug/l	20			
Methyl Tert-Butyl Ether (MTBE)	n	ug/I	10			
Napthalene	n	ug/i	10			
n-Propylbenzene	n	ug/i	10			
Styrene	n	ug/l	10			
Tert-Amyl Methyl Ether (TAME)	n	ug/l	10			
1.1.1.2-Tetrachloroethane	n	ug/l	10			
1,1,2,2-Tetrachloroethane	n	ug/l	10			
Tetrachloroethene	n	ug/l	10			
	n	ug/l	100			
Tetrahydrofuran	n	ug/l	1000			
tert - Butanol (TBA)	n n	ug/l	10			
Toluene		ug/l	10			
1,2,3-Trichlorobenzene	n n	ug/l	10			
1,2,4-Trichlorobenzene	n	ug/l	10			
1,1,1-Trichloroethane	n	ug/l	10			
1,1,2-Trichloroethane	<u>n</u>	ug/l	10			
Trichloroethene	n	ug/l	10			
1,1,2-Trichlorotrifluoroethane	n	ug/l	10			
Trichlorofluoromethane	. <u>n</u> _	ug/l	10			
1,2,3-Trichloropropane	<u>n</u>		10			
1,2,4-Trimethylbenzene	<u>n</u>	ug/l	10			
1,3,5-Trimethylbenzene	n	ug/l	10			
Vinyl Acetate	n	ug/l	10			
Vinyl Chloride	n	ug/l	20			
Total Xylenes	n	ug/l				
SURROGATES	RECOVERY	%	CONTROL			
		ı	LIMITS (%)			
			Little (76)			
	07.4	%	28-145			
1,2-Dichloroethane-d4	97.4		52-150			
Toluene-d8	125	<u>%</u>	43-155			
4-Bromofluorobenzene	102	70	49-100			
	· - · · · · · · · · · · · · · · · · · ·		 			
		Reported By	<u> </u>			
Comments:		111-	11			
Caifornia D.O.H.S Cert # 1677		///40	4			
n - Not detected at the quantitation limit.		Reported Ry				
* - QL raised due to required dilution		Керомефър				

BASIC LABORATORY CHAIN OF CUSTODY RECORD 2218 Railroad Avenue, Redding, CA 96001 (530) 243-7234 FAX 243-7494

CLIENT N										TNA					PRO	JEC	T #:	L	AB :	#:		
	P5	I		_				PALACE CARAGE 26033							33	0301059						
ADDRES	S:					,		REQUESTED COMP. DATE:									#SAMP:					
	01	(-	I	し [']	F_			TURN AROUND TIME: STD / RUSH PAGE / OF														
BOJECT	T MANAGE	<u>.</u>									ANA	LYSE	S RE	QUE	STED)	·	\perp				
HOJEC	I WANAGE	-A1	16	- 8	055														L	REP:		
PHONE:	PHONE: FAX: E-MAIL: 510 434 - 7676							#											L	I.D.# SYST	EM #:	
INVOICE	TO: SAM F		1-			PO#:		P		2XV											r. SEAL	
PECIAL]	E-N	/AIL	FAX [B 0		0/10										ICE		
		W A T	СОМ	s				T T	67	Ó									Ľ	QC =	12	3 4
DATE	TIME	E R	M P		SAMPLE	DESCRIP	TION	S	THIA	826									AB D	F	REMARI	KS
12/3/02		X			mw-1			HOA	X	X									7			
2/31/02		X			MW-2			\prod	X	X								o	2			
1/02/03		X			_mw-3				X	X								= ==	3			
2/31/02	1230	X			mw-	<u> </u>		•	X	X								4	1			
					·														+			
																			\perp			
						<u> </u>	<u> </u>												\downarrow			
					NO TE	<u>3</u> S													_			
	<u> </u>			_			•						{						+	<u></u>		
		\vdash	-	\dashv															+			
_	<u> </u>		_				· · · · · · · · · · · · · · · · · · ·												+	-		
				-		····												_	+			
_																			+			
																			土			
				\bot															$oxed{\bot}$			
	···-··			_														\perp	\perp			
				\perp	<u></u>																	
																			\perp			
	BY:		O ₃			NaOH DATE/TII	ZnAce/NaC	REL	INOL	HCL JISHE	D BY				The Parket			DATE	/TIM 2 /	JE: 0.3	163	0
SAMPLED BY: DATE/TIME: 12/31/02 1/02/03 ECEIVED BY: DATE/TIME:						ISHE			سار	<u> </u>				DATE								
RECEIVED BY: DATE/TIME:				ME:							DATE	ATE/TIME:										
ECCIVED BY LAB: DATE/TIME: 55						5.55	SAN	1PLE	SHIP	PED	VIA:	UPS	PC	ST !	BUS	FED-I	EX C	IHTC	ER			
					TIONS ON BACK.																	

Report To:

P.S.I.

4703 TIDEWATER AVE., STE.B

OAKLAND, CA 94601

Lab No:

0212447A

Date:

01/08/03

Phone: Date Sampled: (510) 434-9200

Date Received:

12/06/02 12/13/02

Attention:

FRANK POSS

Project No.:

Project Name: PALACE GARAGE

575-2G033

Sample

Description:

SOIL TESTING

Page 1 of 3

TPH-Gas Range

Organics

4-Bromofluorobenzene

Reporting <u>Limit</u>

Date

Test: Method:

8015 mg/kgW Surrogate

mg/kgW

Analyzed

Units: Control Limit: %

39-128

Sample ID

SB-16-15.0'	n	64,3	0.06	12/16/02
	·			

Comments:

California D.O.H.S. Cert. #1677.

n - Not detected at the reporting limit.

Reported by:

EPA METHOD 8260

Report To:

P.S.I.

Lab Number:

0212447A

•

4703 TIDEWATER AVE., STE.B

Phone:

510-434-9200

OAKLAND, CA 94601

Date Sampled:

12/06/02

Attention:

FRANK POSS

Date Received:

12/13/02

Project Name:

PALACE GARAGE

Date Analyzed:

12/16/02

Project Number:

575-2G033

Date Reported:

01/08/03

Sampling Location:

Sample ID:

SB-16-15.0'

Sample Matrix:

SOIL

Sample Collected By:

BRAND BURFIELD

PAGE 2 OF 3

COMBOUND	DECLUT	PAGE 2 OF 3 REPORTING	AUANETTATION.		
COMPOUND	RESULT	l l	QUANTITATION		
		UNITS	LIMIT		
Acetone		ug/kg	50		
Acrylonitrile	n n	ug/kg	50		
Benzene	n	ug/kg	5		
Bromobenzene		ug/kg	5		
Bromochloromethane	n n	ug/kg	5		
Bromodichloromethane	n n	ug/kg	5		
Bromoform		ug/kg	5		
Bromomethane	<u>n</u>	ug/kg	5		
	<u>n</u>	ug/kg	50		
2-Butanone (MEK)	n	ug/kg	5		
n-Butylbenzene	<u>n</u>		5		
sec-Butylbenzene	<u>n</u>	ug/kg	5		
tert-Butylbenzene	. <u>n</u>	ug/kg	5		
Carbon Disulfide	n	ug/kg			
Carbon tetrachloride		ug/kg	5		
Chlorobenzene	n	ug/kg	5		
Chloroethane	n	ug/kg	5		
2-Chloroethylvinylether	n	ug/kg	5		
Chloroform	n	ug/kg	5		
Chloromethane	n	ug/kg	5		
2-Chiorotoluene	n	ug/kg	5		
4-Chlorotoluene	n	ug/kg	5		
Dibromochloromethane	n ·	ug/kg	5		
1,2-Dibromo-3-Chloropropane	п	ug/kg	5		
1,2-Dibromoethane	n	ug/kg	5		
Dibromomethane	n	ug/kg	5		
1,2-Dichlorobenzene	n	ug/kg	5		
1,3-Dichlorobenzene	n	ug/kg	5		
1,4-Dichlorobenzene	n	ug/kg	5		
Dichlorodifluoromethane	n	ug/kg	5		
1,1-Dichloroethane	n	ug/kg	5		
1,2-Dichloroethane	n	ug/kg	5		
1,1-Dichloroethene	п	ug/kg	5		
cis-1,2-Dichloroethene	n	ug/kg	5		
trans-1,2-Dichlorcethene	n	ug/kg	5		
1,2-Dichloropropane	П	ug/kg	5		

EPA METHOD 8260

Report To:

P.S.I.

Lab Number:

0212447A

PAGE 3 OF 3

		PAGE 3 OF 3	
COMPOUND	RESULT	REPORTING	QUANTITATION
		UNITS	LIMIT
1,3-Dichloropropane	n	ug/kg	5
2,2-Dichloropropane	n	ug/kg	5
1,1-Dichloropropene	n	ug/kg	. 5
cis-1,3-Dichloropropene	n	ug/kg	5
trans-1,3-Dichloropropene	n	ug/kg	5
1,4-Dioxane	n	ug/kg	250
Ethyl Benzene	n	ug/kg	5
Ethyl-Tert-Butyl Ether (ETBE)	n n	ug/kg	5
Hexachlorobutadiene	n	ug/kg	5
2-Hexanone (MBK)	n	ug/kg	50
Isopropylbenzene	n	ug/kg	5
Di-Isopropyl Ether (DIPE)	n	ug/kg	5
p-Isopropyltoluene	n	ug/kg	5
4-Methyl-2-Pentanone (MIBK)	n	ug/kg	50
Methylene Chloride	n	ug/kg	10
Methyl Tert-Butyl Ether (MTBE)	n	ug/kg	5
Napthalene	n	ug/kg	- 5
n-Propylbenzene	n	ug/kg	5
Styrene	n	ug/kg	5
Tert-Amyl Methyl Ether (TAME)	<u>n</u>	ug/kg	5
1,1,1,2-Tetrachioroethane	n	ug/kg	5
1.1.2.2-Tetrachloroethane	n	ug/kg	5
Tetrachloroethene	n	ug/kg	5
Tetrahydrofuran	n	ug/kg	50
tert - Butanol (TBA)	n	ug/kg	40
Toluene	n n	ug/kg	5
1.2.3-Trichlorobenzene	n	ug/kg	5
1,2,4-Trichlorobenzene	n n	ug/kg	5
1,1,1-Trichloroethane	n	ug/kg	5
1,1,2-Trichloroethane	n	ug/kg	5
Trichloroethene	ก	ug/kg	5
1,1,2-Trichlorotrifluoroethane		ug/kg	5
Trichlorofluoromethane	n	ug/kg	5
1,2,3-Trichloropropane		ug/kg	5
1,2,3-Tricnioropropane	n	ug/kg	5
	<u>n</u>	ug/kg	5
1,3,5-Trimethylbenzene Vinyl Acetate	<u> </u>	ug/kg	5
	<u> </u>	ug/kg	5
Vinyl Chloride	<u>n</u>		
Total Xylenes	n	ug/kg	10
SURROGATES	RECOVERY	%	CONTROL LIMITS (%)
1,2-Dichloroethane-d4	39.2	%	11-185
Toluene-d8	86.3	%	19-168
4-Bromofluorobenzene	64.3	%	39-128
4-PIOLIOHIOLOPCITACHE	04.0	//	00.120

Comments:

Caifornia D.O.H.S Cert # 1677

n - Not detected at the quantitation limit.

Befored By

	O C	340				TORY CHAIN C												LAB	_
CLIENT NA		210	Kan		d Ave., Reddii	ng, CA 96001 (53	_				30) 2	43-7	494	Topa:	VIEC	T 44.	02/2/447 A SAMPLE TYPE:		
Ps.	T						I N	PROJECT NAME: PROJE						ハモヘ	i #:				
ADDRESS:			·		· · ·		REC	REQUESTED COMP. DATE: STA						STA	STATE FORMS?			SOIL # OF SAMPLES:	
4	1703 T	id	عد	کان	iter Ave				-/3								•	,,,	/
ش	melan	1.	CH	1_	tter Ave		TUE				ΛE: S	TO T	∇		USH				
_		,,,		į	s. s.			T			ANALY		<u></u>					PA	GEOF
ROJECT M									T		T			Τ	<u> </u>	Π	-		REP:
Fran	k Pos	<u> </u>) 1457	_		-,	#					ĺ							
PHONE:	4-9200	5	FAX	(; ∖ ∡d	34 7676	E-MAIL:	o												ID#:
MVOICE TO) .	<u>-</u> '	<i></i>	<u>, T</u>	54 /6 /6	PO#:	— F							1					SYSTEM#:
PSI							В	İ						•					
PECIAL MA	AIL	E-M	AIL		FAX	EDT	O T		~										GLOBAL ID #:
		W	С	s			T	9		r									
		Т	О М	9			E	12	260										QC = 1 2 3 4
DATE	TIME	R	Р	_	SAMPI	LE DESCRIPTION		1/2	200					ļ			<u> </u>	LAB ID	REMARKS
1.6.0z	10:05			X	SB-16-	-15.0		X	×									7	
				\exists					<u> </u>									<u> </u>	
<u> </u>										ļ									
									<u> </u>										
										-		_	 	<u> </u>					
				1	· · · · · · · · · · · · · · · · · · ·			1	-										
									-										
n				1				-							-				
		\Box	\dashv	7	-														
_				1	a Addition	val testina													
					ner 110 start	Pau B Coll	,												
			丁	ď	13-30-02	perBrand													
1		H			, o <u> </u>			,											
		\Box	_	十								\dashv			-		-		
	-	\dashv		\dashv	<u> </u>														
			+	\dashv											\dashv				
<u></u>			\dashv	\dashv			-									-	\dashv	-	
		\dashv	\dashv	+			 												
			+	+	<u> </u>						$\vdash \vdash$		-		\dashv			\dashv	
		-	+	+		-							_					 	
RESERVED	WITH: HNO	<u> </u>	4		SO ₄ Na	OH ZnAce/Na	~~~	£J.	CL F		NaT	bio C	<u></u>	ОТН	ED.				
AMPLED BY	/: _	-3 ∟			Z-V4 [Na'	DATE/TIME:	RELI			BY:		шо [OIH			1	DATE/	TIME:
rand 8. 126.02																			
CEIVED BY: DATE/TIME:						RELI	NQUI	SHED	BY:							Ţ	DATE/	TIME:	
CEIVED BY: (SAMPLES UNVERIFIED) DATE/TIME: 15/7						, RELI	RELINQUISHED BY: D						DATE/	TIME:					
ECEIVED B	Y LAB: (VERI	FIED	17.	<u>' `</u> `	107, 13	DATE/TIME: AT		PLES	SHIP	PED	VIA:	UPS	FE	DEX	PC	DST	BUS	от	HER
JULULU	<u> </u>	ILL)	101	1_	12.30.0	2/			,										

TRUCTIONS, TERMS AND CONDITIONS ON BACK.

Report To:

Attention:

P.S.I,

4703 TIDEWATER AVE., STE.B

OAKLAND, CA 94601

Lab No:

0212447-2

Date:

12/30/02

Phone:

(510) 434-9200

Date Sampled:

12/06/02

Date Received:

12/13/02

Project No.:

575-2G033

Project Name: PALACE GARAGE

Description:

SOIL TESTING

FRANK POSS

Page 1 of 3

TPH-Gas Range

Reporting

Date

Test:

Organics

4-Bromofluorobenzene

<u>Limit</u>

<u>Analyzed</u>

Method: Units:

Control Limit:

8015 mg/kgW

Surrogate % 39-128

mg/kgW

Sample ID

SB-17-19.0°	292	83.4	0,060	12/16/02

Comments:

California D.O.H.S. Cert. #1677.

n - Not detected at the reporting limit.

Reported by:

EPA METHOD 8260

Report To:

P.S.I.

Lab Number:

0212447-2

4703 TIDEWATER AVE., STE.B

OAKLAND, CA 94601

Phone:

510-434-9200

FRANK POSS

Date Sampled:

12/06/02

Project Name:

PALACE GARAGE

Date Received:

12/13/02

Project Number:

575-2G033

Date Analyzed: Date Reported: 12/16/02 12/30/02

Sampling Location:

Sample ID:

Attention:

SB-17-19.0'

Sample Matrix:

SOIL

Sample Collected By:

BRAND BURFIELD

PAGE 2 OF 3

PAGE 2 OF 3				
COMPOUND	RESULT	REPORTING	QUANTITATION	
		UNITS	LIMIT	
Acetone	n	ug/kg	50	
Acrylonitrile	n	ug/kg	50	
Benzene	n	ug/kg	5	
Bromobenzene	n	ug/kg	5	
Bromochloromethane	n	ug/kg	5	
Bromodichloromethane	ń	ug/kg	5	
Bromoform	n	ug/kg	5	
Bromomethane	n .	ug/kg	5	
2-Butanone (MEK)	п	ug/kg	50	
n-Butylbenzene	259	ug/kg	5	
sec-Butylbenzene	302	ug/kg	5	
tert-Butylbenzene	n.	ug/kg	5	
Carbon Disulfide	, n	ug/kg	5	
Carbon tetrachloride	n	ug/kg	5	
Chlorobenzene	n	ug/kg	5	
Chloroethane	n	ug/kg	5	
2-Chloroethylvinylether	n	ug/kg	5	
Chloroform	n	ug/kg	5	
Chloromethane	n	ug/kg	5	
2-Chlorotoluene	n	ug/kg	5	
4-Chlorotoluene	n	ug/kg	5	
Dibromochloromethane	n	ug/kg	5	
1,2-Dibromo-3-Chloropropane	n	ug/kg	5	
1,2-Dibromoethane	n	ug/kg	5	
Dibromomethane	n	ug/kg	5	
1,2-Dichlorobenzene	n	ug/kg	5	
1,3-Dichlorobenzene	n	ug/kg	5	
1,4-Dichlorobenzene	n	u g /kg	5	
Dichlorodifluoromethane	n	ug/kg	5	
1,1-Dichloroethane	n	ug/kg	5	
1,2-Dichloroethane	n	ug/kg	5	
1,1-Dichloroethene	η	ug/kg	5	
cis-1,2-Dichloroethene	n	ug/kg	5	
trans-1,2-Dichloroethene	n	ug/kg	5	
1,2-Dichloropropane	n	ug/kg	5	

EPA METHOD 8260

Report To:

P.S.I.

Lab Number:

0212447-2

PAGE 3 OF 3

	PAGE 3 OF 3			
COMPOUND	RESULT	REPORTING	QUANTITATION	
		UNITS	LIMIT	
1,3-Dichloropropane		ug/kg	5	
2,2-Dichloropropane	<u>n</u>		5	
1,1-Dichloropropene	п	ug/kg	5	
cis-1,3-Dichloropropene	<u> </u>	ug/kg	5	
	<u>n</u>	ug/kg	5	
trans-1,3-Dichloropropene	n .	ug/kg		
1,4-Dioxane	<u>n</u>	ug/kg	250	
Ethyl Benzene	n	ug/kg	5	
Ethyl-Tert-Butyl Ether (ETBE)	n	ug/kg	5	
Hexachlorobutadiene	n n	ug/kg	5	
2-Нехаполе (МВК)	<u> </u>	ug/kg	50	
Isopropylbenzene	34	ug/kg	5	
Di-Isopropyl Ether (DIPE)	<u>n</u>	ug/kg	5	
p-Isopropyltoluene	20	ug/kg	5	
4-Methyl-2-Pentanone (MIBK)	n	ug/kg	50	
Methylene Chloride	n	ug/kg	10	
Methyl Tert-Butyl Ether (MTBE)	n	ug/kg	5	
Napthalene	n	ug/kg	5	
n-Propylbenzene	87	ug/kg	5	
Styrene	n	ug/kg	. 5	
Tert-Amyl Methyl Ether (TAME)	n	ug/kg	5	
1,1,1,2-Tetrachloroethane	n	ug/kg	5	
1,1,2,2-Tetrachloroethane	n	ug/kg	5	
Tetrachloroethene	n	ug/kg	5	
Tetrahydrofuran	n	ug/kg	50	
tert - Butanol (TBA)	n	ug/kg	40	
Toluene	n	ug/kg	5	
1.2.3-Trichlorobenzene	n	ug/kg	5	
1,2,4-Trichlorobenzene	n	ug/kg	5	
1,1,1-Trichloroethane	п	ug/kg	5	
1,1,2-Trichloroethane	n	ug/kg	5	
Trichloroethene	n	ug/kg	5	
1.1.2-Trichlorotrifluoroethane	n	ug/kg	5	
Trichlorofluoromethane	· n	ug/kg	5	
1,2,3-Trichloropropane	n	ug/kg	5	
1,2,4-Trimethylbenzene	n	ug/kg	5	
1,3,5-Trimethylbenzene	n .	ug/kg	5	
Vinvi Acetate	n	ug/kg	5	
Vinyl Chloride	n	ug/kg	5	
Total Xylenes		ug/kg	10	
	RECOVERY	%	CONTROL	
SURROGATES	RECOVERY	%	CONTROL LIMITS (%	
1,2-Dichloroethane-d4	67.8	%	11-185	
Toluene-d8	110	%	19-168	
4-Bromofluorobenzene	83.4	<u> </u>	39-128	

Comments:

Calfornia D.O.H.S Cert # 1677

n - Not detected at the quantitation limit.

Reported By

2218 Railroad Avenue, Redding, CA 96001 (530) 243-7234 FAX 243-7494

CLIENT NAME:	PROJECT NAME:	PROJECT #:	LAB#:				
	PALACE GARAGE	979-G033	0212447				
ROFESSIONAL SERVICE TURS RESIDENCES:	PARACE GARAGE REQUESTED COMP. DATE:		#SAMP:				
4703 TIDEWAYER AVE	12.30.0.2						
DAKLAND, CA 94601	TURN AROUND TIME: STD	RUSH	PAGE OF				
_	ANALYSES REQUE	STED					
PROJECT MANAGER:			AEP:				
FRANK POSS HONE: FAX: FAX: E-MAIL: 50 434 9200 50 434 7676			1.D.#				
50 434 9200 50 434 7676	_ "	!	SYSTEM#:				
NVOICE TO: PO#:	P S		CUST. SEAL				
SPECIAL MAIL E-MAIL FAX	OF B		ICE				
			OC = 1 2 3 4				
	[[[년 및]						
DATE TIME R P L SAMPLE DESCRIPTION	E 8 22 0		ID REMARKS				
16/02 10:05 X 58-16-15.0'			2 405				
1 12:10 X 58-17-19.0'	1 X X 1		2				
=							
- 							
		 					
			 				
	<u> </u>		 				
ESERVATIONS HNO3 H2SO4 NaOH Znace/N	AOH HCL Nathio	10/	AŢE/TIME:				
BRAND RIOTERD 12/6/02	Man		112/02 17:05				
CEIVED BY: DATE/TIME:			ATE/TIME:				
RECEIVED BY: DATE/TIME:	RELINQUISHED BY: DATE/TIME:		ATE/TIME:				
CEIVED BY LAB: LOW HOY 12.13.02	SAMPLE SHIPPED VIA: UPS P	OST BUS (ED-E)	OTHER				
NSTRUCTIONS, TERMS, CONDITIONS ON BACK.							