

55 Hawthorne Street, Suite 500 San Francisco, California 94105-3906

Telephone **415 543-4200** FAX 415 777-3157



December 30, 1989 88-44-369-01-346

Ms. Dyan Whyte Water Resource Control Engineer San Francisco Bay Regional Water Quality Control Board 1800 Harrison Street Oakland, California 94607

Subject: Shell Oil Company - Quarterly Report

630 High Street Oakland, California

Dear Ms. Whyte:

Enclosed please find one copy of the Shell Oil Company Quarterly Report of Activities for Quarter 4, 1989 prepared by Converse Environmental West (CEW) - San Francisco.

Please call if you have any questions.

Very truly yours,

Converse Environmental West

Marc I. Yalom

Project Hydrogeologist

Robin Grewer

MIY:fs Enclosure

cc: Ms. Diane Lundquist - Shell Oil Company (w/encl.)

Mr. Rafat Shahid - Alameda County Health Car Services (w/encl.)

Mr. Douglas W. Charlton - CEW (w/o encl.)

Ms. Robin M. Breuer - CEW (w/ encl.)



DOUGLAS ***. CHARLTON Principal Geologist

ACTIVE GASOLINE STATION

SHELL OIL COMPANY

630 High Street Oakland, California

December 30, 1989

CEW Project No. 88-44-369-01

This report has been prepared by the staff of Converse Environmental West (CEW) under the professional supervision of the Engineer and/or Geologist whose seal(s) and signature(s) appear hereon.

The findings, recommendations, specifications or professional opinions are presented, within the limits prescribed by the Client, after being prepared in accordance with generally accepted professional engineering and geologic practice. We make no other warranty, either expressed or implied.

Converse Environmental West

REPORT OF ACTIVITIES

SHELL OIL COMPANY FACILITY 630 High Street Oakland, California

For Quarter 4, 1989 Submitted: December 31, 1989

RWQCB Representative:

Ms. Dyan Whyte

Water Resource Control Engineer

San Francisco Bay RWQCB

1800 Harrison Street

Oakland, California 94607

LIA Representative:

Mr. Rafat Shahid

Alameda County Health Care Services Agency

80 Swan Way

Oakland, California 94621

Shell Engineer:

Ms. Diane Lundquist **Environmental Engineer** Shell Oil Company 1390 Willow Pass Road Concord, California

Converse Project Manager:

Ms. Robin Breuer, Project Manager 55 Hawthorne Street, Suite 500 San Francisco, California 94105

(415) 543-4200

Registered Geologist in Charge: Douglas W. Charlton, Principal Geologist

55 Hawthorne Street, Suite 500 San Francisco, California 94105

(415) 543-4200

Site Owner:

Shell Oil Company

1. SITE DESCRIPTION

1.1 <u>Maps</u>

Vicinity Map: See Drawing 1 Plot Plan: See Drawing 2

1.2 Neighborhood Topography

Slightly sloping to the northwest.

1.3 Primary Surface Waters Nearby

Alameda Estuary is approximately one-eighth of a mile to the west, _

1.4 Water Table Information

Q4/89: Depth to Water: 9-12 feet below grade.

Depth to Highest High Water determined by redox boundary: approximately 9 feet below

grade.

2. INVESTIGATION HISTORY

2.1 Soil Borings Drilled to Period Start

Boring	<u>Date</u>	<u>Status</u>
SB-1	4/89	Abandoned
SB-2	4/89	Abandoned
SB-3	8 ['] /89	Abandoned

2.2 Groundwater Wells Drilled to Period Start

Well	<u>Date</u>	Status
MW-1	4/89	Active
MW-2	4/89	Active
MW-3	4/89	Active
MW-4	4/89	Active
MW-5	8/89	Active
MW-6	8/89	Active
MW-7	8/89	Active
MW-8	8/89	Active

2.3 <u>Investigative History Summary</u>

CHRONOLOGICAL SUMMARY

The following is a chronological summary of site activities.

<u>Date</u>	Description of Activity
01/85	Re-modernization of gas station. Armer/Norman dismantled and removed all fuel dispensing facilities and excavated certain areas near former pump islands, product lines and areas which smelled of gasoline.
01/26/89	Blaine Tech Services collected and analyzed (10) excavation soil samples. The inspector from the Alameda County Health Department specified sampling locations. Soils were analyzed for TPH-g, BTEX and organic lead.
02/03/89	Blaine Tech Services collected and analyzed soil samples in areas of product dispensing pump islands after additional excavation in these areas and in areas of former waste oil and gasoline tank pits (sample No. 10 - 75 ppm and No. 12 - 600 ppm TPH-g).
02/03/89	Further excavation in former waste oil tank pit. Soil and groundwater samples were collected and analyzed in the area around sample no. 12 of February 3, 1989 sampling event. These soil samples contained less than 50 ppm TPH-d. Groundwater sample no. 3 from that area contained 1,800 ppb TPH-g and 200 ppb TPH-d.
02/24/89	Alameda County Environmental Health Department notified Shell that site conditions indicated a confirmed release, which required an investigation Work Plan within 25 days of the letter date.
03/89	Shell transferred project to CEW.
03/20/89	CEW submitted Revised Work Plan to agencies.
04/26/89	CEW installed wells MW-1 to MW-4 and soil borings SB-1 and SB-2.
05/19/89	CEW developed wells MW-1 through MW-4.
05/25/89	CEW surveyed site and well head elevations (MW-1 through MW-4) to arbitrary datum.
05/26/89	CEW sampled groundwater from wells MW-1 through MW-4.
08/15/89	CEW installed wells MW-5 through MW-8 and boring SB-3.
08/22/89	CEW surveyed wells MW-5 through MW-8 to arbitrary datum.
08/29/89	CEW sampled and developed wells MW-5 through MW-8.
10/17/89	Loma Prieta Earthquake struck.
11/15/89	CEW installed wells MW-9 and MW-10 and Boring SB-4.
11/22/89	CEW developed wells MW-9 and MW-10.
12/11/89	CEW sampled and surveyed wells MW-9 and MW-10.

3. WORK COMPLETED THIS PERIOD

3.1 Introduction

Work initiated and completed during the quarter followed the task descriptions and modifications of the site Work Plan dated March 20, 1989. The relative timing and schedule of these activities is shown in summary in the Critical Path for the project (Drawing 3).

Initially, the Work Plan called for drilling of ten soil borings. Six borings were to be abandoned. Four borings were to be completed as groundwater monitoring wells.

Once investigations began, a more thorough study became necessary. As a consequence, fourteen borings have been drilled. Ten borings have been completed as groundwater monitoring wells and the remainder have been abandoned.

3.2 Soil Boring Drilling/Sampling

During Q4/89, a total of three soil borings were drilled, sampled, and abandoned or completed as monitoring wells following the protocols described in Appendices A and B. Soil cuttings were handled by Crosby Overton, following task procedures described in Appendix G. Boring logs are enclosed as Attachment 1. A summary of soil boring activities is presented in Table 1.

3.3 Well Installations

In Q4/89, two groundwater monitoring wells were installed, developed and sampled following the protocols in Appendices A, C, D and E. These wells were installed as 4-inch diameter filter-packed PVC wells through hollow-stem auger drilling equipment. The boring logs and as-built well construction diagrams for these wells are included as Attachment 1. A summary of well installations is provided in Table 2.

3.4 Soil Analysis/Results

Soil samples from the borings were collected on five foot centers downhole. These samples were properly packaged and transferred to a California State-certified analytical laboratory under proper chain-of-custody and preservation (see Appendix F). The samples were analyzed for TPH as gasoline (EPA Methods 5030 and 8015), TPH as diesel (EPA Methods 3550 and 8015), TPH as motor oil (EPA Methods 3550 and 8015), BTEX (EPA Methods 5030 and 8020), and lead (EPA Methods 3050 and 7421). Analytical results are summarized in Table 3, and certified sheets from all analyses are enclosed as Attachment 2.

3.5 Groundwater Analysis and Results

Groundwater samples were properly packaged and transferred to a California State-certified analytical laboratory under proper chain-of-custody and preservation (see Appendix E). The samples were analyzed for TPH as gasoline (Methods 5030 and 8015), TPH as diesel (Methods 3510 and 8015), TPH as motor oil (EPA Methods 3510 and 8015) BTEX (EPA Methods 5030 and 602), and lead (EPA Methods 5030 and 7421). Because wells MW-1, MW-9, and MW-10 were located near the approximate location of the former onsite waste oil tank, groundwater samples from these wells were analyzed for chlorinated hydrocarbons (EPA Method 624). Samples from MW-1 were analyzed for Zn, Cr, Cd (by ICP) and oil and grease (EPA Methods 503A&E).

Selected certified past and Q4/89 preliminary groundwater analytical results are summarized in Table 4.

NOTE: Certified groundwater analytical results are pending at the issuance of this report. Upon receipt of the certified results, a supplemental report will be submitted to the RWQCB, containing appropriate isopleth maps for soil and groundwater, cross-sections, and hard copy of analytical results.

The supplemental report will be submitted on or before January 31, 1990, as an exception to the normal quarterly scheduled reporting for this site. Therefore, a full quarterly report will be presented to the RWQCB on or before its next due date, March 31, 1990.

3.6 Physical Monitoring Results

All ten wells were physically monitored for depth to water table, and inspection for floating product, once during the quarter. A summary of these results is presented in Table 5.

3.7 Neighborhood Environmental Assessment

An environmental assessment of neighborhood business, ownerships and unauthorized subsurface tank releases reported to regulatory agencies commenced during Q4/89. This research and neighborhood inspection showed that certain parties other than Shell could, in part, be responsible for site contamination.

A list of sites with reported underground fuel leaks which potentially impact the Shell property is included as Table 6. The sites listed in Table 6 are located on Plate 1.

Due to the October 17, 1989 earthquake impact on operations of the RWQCB, Alameda County Health Care Services Agency, and the Oakland Fire Department, detailed information on reported offsite fuel tanks was not available.

4. REVIEW OF DATA AND INTERPRETATIONS

4.1 Groundwater Elevation and Gradient (See Drawing 4)

- The groundwater gradient is approximately 0.005 ft/ft. to the southwest to west.
- Groundwater is at approximately 10 feet below ground surface across much of the section.

4.2 <u>Distribution of MVF Contamination in Soil</u> (See Drawings 5, 6, 7 and 8)

 The highest TPH-g soil contamination (≤ 12 ppm) is centered about the site of the former underground waste oil and fuel tanks.

TPH-g was detected in soil samples at MW-1. This well was sited adjacent to the former underground fuel tank bed and in the general vicinity of the former waste oil tank. These tanks are suggested as the sources of contamination at MW-1.

Petroleum hydrocarbons were also detected from soil samples at SB-1 and SB-2, samples collected from fill materials of the former fuel tank excavation.

Lead, toluene, benzene, xylenes, and grease were also detected in the same area.

- TPH-d is the principal contaminant in unsaturated soil.
- The highest TPH-d and TPH-mo soil contamination is centered at MW-10.

MW-10 is located near the property boundary with EBMUD. The EBMUD property is listed on the RWQCB's Alameda County list of sites with reported fuel leaks. The data suggest an offsite source of the diesel and motor oil contamination. Observed at the Shell property.

 An area of petroleum hydrocarbon soil contamination is located in the vicinity of well MW-4.

Analysis of soil samples indicated the presence of benzene, toluene, and lead in excess of 20 ppm at MW-4.

MW-4 is sited in an area of no known previous underground tanks or piping runs. Soil analytical results suggest a surface product release to the vadose zone. This is supported by the detection of heavier hydrocarbon fractions (diesel and motor oil), which would have been less likely to migrate from the former underground tank bed at SB-1 and SB-2.

· Offsite sources of contamination are not ruled out, and further investigation is required.

Petroleum hydrocarbon contamination (TPH-g, TPH-d, and BTEX) was detected in groundwater at well MW-5. This well is located cross-gradient from the former underground tank bed, and on the upgradient side of the property. Non-detection

of petroleum hydrocarbons in the soil at MW-5 implies migration of contaminants through groundwater.

 Neighborhood background concentrations of lead in the soil have not been established. Lead in site soils may not be the result fuel releases at the site.

Elevated Highway 880 is located adjacent to the site (directly east). Decades of leaded fuel exhaust emissions from vehicular traffic may have contributed to lead concentrations in the neighborhood and site.

4.3 <u>Distribution of MVF Dissolved in Groundwater</u>

 The certified groundwater analytical results for MW-1 through MW-10 are pending at the time of release of this report. These results will be presented with appropriate maps, tables, and conclusions in a supplemental report issued in January 1990.

4.4 Distribution of Floating Product on Groundwater

Floating product was not detected on groundwater in any well.

4.5 Site Geology (See Drawings 9 and 10)

- The uppermost part of the subsurface consists of fill averaging four feet in thickness.
 The fill soil materials include gravel, sand, and clay in heterogeneous mixtures.
 Concrete rubble, wood fragments, asphalt chunks, and rubbish are present in the fill.
- Beneath the fill is a layer of clay varying up to 8 feet in thickness (MW-7). At wells MW-2 and MW-3 this a thin (less than two feet thick) sand layer within the clay zone thick was intersected. The base of the clay layer is approximately 10 feet bgs.
- A layer of sands and gravels, ranging between 2 feet (MW-7) and 12 feet (MW-8) in thickness underlies the clayey stratum. These more permeable soils are generally clayey with some scattered clay free zones.
- The more sands and gravels are underlain by clay which extend from approximately
 15 feet bgs to 24 feet bgs, the depth of maximum exploration.

5. WORK PLANED BUT NOT COMPLETED

Groundwater sampling occurred in December, but year-end backlog of analytical laboratory work prevented completion of certified analysis early enough for inclusion of data into this report. Analytical results arrived today (12/29/89). These results will be compiled, interpreted and presented with certified isopleth maps and will be discussed in the text in a supplemental report to be presented in January 1990.

Slug tests planned for Q4/89 were not completed.

Preparation of a Soil Remediation Action Plan was commenced but not finalized.

Preparation of An Offsite Groundwater Investigation Plan was commenced but not finalized.

6. WORK PLANNED FOR NEXT QUARTER

- <u>Task 2: Complete the Soil Remediation Action Plan</u>. Options for cost effective soil remediation will be identified and relatively evaluated on the volume of contaminated soil, the hydrologic conditions of contamination, and the concentration of contaminants involved.
- <u>Task 6: Collect and Analyze Groundwater Samples</u>. Quarterly samples will be collected and all wells will be physically monitored once during Q1/90.
- <u>Task 7: Conduct Hydrology Tests and Research</u>. Perform slug tests on all wells and interpret collected data so that hydraulic properties may be assessed.
- <u>Task 11: Complete the Offsite Groundwater Investigation Plan</u>. Amend the March 20, 1989 Revised Work Plan to address the potential for offsite groundwater MVF contamination.

TABLE 1: Summary of Soil Borings Drilled

Boring <u>No.</u>	Date <u>Drilled</u>	Completion	Diameter (inches)	T.D. (ft. bgs)	Unsaturated Soil Samples (ft. bgs)	High <u>OVM</u>	Saturated Soil Samples (ft. bgs)
MW-1	4/25/89	4" weli	12	20	5	>1000 @ 12	' None
MW-2	4/25/89	4" well	12	25	5,10	NR	
MW-3	4/26/89	4" well	12	20	5,10 5,10	0	15 None
MW-4	4/26/89	4" weli	12	22	5,10	5 @ 5'	None
MW-5	8/17/89	4" well	12	20	5,10 5,10	450 @ 16'	None
MW-6	8/26/89	4" well	12	24	5,10 5,10	430 @ 10	None
MW-7	8/15/89	4" well	12	24	5,10 5,10	0	15
MW-8	8/15/89	4" well	12	24	5	0	15,20
MW-9	11/15/89	4" well	12	16	5	0	10 None
MW-10	11/16/89	4" well	12	17	5,9	5 @ 9'	None
SB-1	4/27/89	Abandoned	8	10	5	NR	None
SB-2	4/27/89	Abandoned	8	10	5,10	NR	None
SB-3	8/17/89	Abandoned	8	10	5,10	1300 @ 5'	None
SB-4	11/15/89	Abandoned	8	9	5,9	0	None

NR - Not recorded

TABLE 2: Summary of Groundwater Monitoring Well Installations

Well No.	<u>Date</u>	Diameter Well (in.)	Initial Water Table <u>(ft. bgs)</u>	Static Water Table (ft. bgs)	T.D. Well (ft. bgs)	Screen (ft. bgs)	Bentonite Seal (ft. bgs)	Grout Seal (ft. bgs)
MW-1	4/25/89	4	10	10.43	20	13-9	9-6	6-0
MW-2	4/25/89	4	14.5	11.67	25	20-10	10-8	8-0
MW-3	4/26/89	4	11.5	10.36	20	17-8	8-6	6-0
MW-4	4/26/89	4	10.0	10.91	22	17-7	7-6	6-0
MW-5	08/17/89	4	12.0	11.34	18.0	8-18	5-7	1-5
MW-6	08/16/89	4	15.0	10.58	20	10-20	7-9	1-7
MW-7	08/15/89	4	17.5	9.76	20	10-20	7-9	1-7
MW-8	08/15/89	4	9.0	9.01	21	9-21	6-8	1-6
MW-9	11/15/89	4	10.0	11.52	12	6-12	4-5	1-4
MW-10	11/16/89	4	11.0	9.55	13	7-13	5-6	1-5

TABLE 3: Soil Analytical Results (ppm)

Boring <u>No.</u>	Sample Depth (ft. bgs)	<u>TPH-g</u>	TPH-d	TPH-mo	<u>Benzene</u>	Toluene a	Total Oil and Grease	<u>Xylene</u>	Total <u>Lead</u>
SB-1	5	12*	27	85	< 0.025	0.10	NA	0.14	71
\$B-2	5	<10	<10	<10	0.042	0.054	NA	<0.075	16
\$B-2	5,10 ''	<10	<10	130	<0.025	0.04	NA	<0.075	10
SB-3	5	<10	<10	<10	<0.025	0.22	290	<0.075	66
SB-3	10	<10	<10	<10	<0.025	0.045	<50	<0.075	4.2
SB-4	5	<1	16	77	<0.0025	0.032	NA	<0.0025	220
SB-4	9	<1	< 1	11	<0.0025	0.056	NA	<0.0025	3.9
MW-1	5	11	<10	<10	<0.025	0.11	NA	<0.075	9.6
MW-1	5,10**	63	<10	<10	0.042	0.14	NA	0.16	7.6
MW-2	5	<10	<10	<10	<0.025	0.34	NA	<0.075	13
MW-2	5,10,15**	<10	<10	<10	<0.025	0.15	NA	<0.075	4.0
MW-3	10	<10	<10	<10	<0.025	<0.025	NA	<0.075	3.9
MW-3	5,10**	<10	<10	<10	<0.025	0.068	NA	<0.075	5.1
MW-4	5	<10	<10	<10	0.046	0.21	NA	<0.075	26
MW-4	5,10**	<10	<10	<10	<0.025	0.066	NA	<0.075	27
MW-5	5	<10	<10	<10	<0.025	<0.025	<50	<0.075	14.0
MW-5	10	<10	<10	<10	<0.025	<0.025	<50	<0.075	5.9
MW-6	5	<10	<10	<10	<0.025	0.057	220	<0.075	5.6
MW-6	10	<10	<10	<10	<0.025	<0.025	<50	<0.075	4.3
MW-7	5	<10	<10	<10	<0.025	0.040	<50	<0.075	9.8
MW-7	10	<10	<10	<10	<0.025	<0.025	<50	<0.075	3.7
MW-8	5	<10	<10	<10	<0.025	<0.025	<50	<0.075	5.1
MW-8	10	<10	<10	<10	<0.025	<0.025	<50	<0.075	2.6
MW-9	5	< 1	< 1	10	< 0.0025	0.013	NA	< 0.0025	170
MW-10	5	<1	< 1	240	<0.0025	0.049	NA	<0.0025	120
MW-10	9	<1	380	3.1	<0.0025	<0.0025	NA	<0.0025	3.1

Sample contains higher boiling hydrocarbons not characteristic with gasoline. Composite sample.

Not analyzed.

NA

TABLE 4: Groundwater Analytical Results (ppm)

Well <u>No.</u>	Date <u>Sampled</u>	TPH-g	TPH-d	TPH-mo	Benzene	<u>Toluene</u>	Ethyl- <u>benzene</u>	<u>Xylenes</u>	<u>Lead</u>
MW-1	5/25/89	11	7.1	1.6	0.0066	0.023	0.023	0.180	NA
MW-1	8/29/89	17	7.2	1.9	0.20	0.18	0.059	0.55	<0.002
MW-1	12/12/89	13	4.4	< 0.05	0.250	0.036	0.270	0.380	NA
MW-2	5/25/89	<0.05	<0.05	<0.05	<0.0005	<0.0005	<0.0015	<0.0015	NA
MW-2	8/29/89	<0.05	<0.05	<0.05	<0.0005	<0.0005	<0.0015	<0.0015	<0.002
MW-2	12/11/89	<0.05	0.081	0.22	< 0.0005	< 0.0005	< 0.0005	< 0.0005	NA
MW-3	5/25/89	1.2	0.40	0.088	<0.0005	<0.0005	<0.0015	<0.0015	NA
MW-3	8/29/89	2.5	0.81	<0.05	0.025	0.01	0.0065	0.0055	<0.002
MW-3	12/15/89	2.8	0.81	< 0.05	0.015	0.008	0.004	0.012	NA
MW-4	5/25/89	2.9	1.1	0.29	<0.005	0.0094	<0.0015	0.0034	NA
MW-4	8/29/89	2.9	1.5	0.79	0.029	<0.0005	0.012	0.0016	<0.002
MW-4	12/12/89	4.6	1.0	< 0.05	0.170	0.026	0.011	0.020	NA
MW-5	8/30/89	1.4	0.30	<0.05	0.0049	0.00079	0.0056	0.0068	<0.002
MW-5	12/5/89	1.4	0.33	< 0.05	0.0049	0.0038	0.0091	0.008	NA
MW-6	8/29/89	<0.05	0.32	0.45	<0.0005	<0.0005	<0.0015	<0.0015	<0.002
MW-6	12/5/89	< 0.05	0.60	< 0.05	< 0.0005	< 0.0005	< 0.0005	< 0.0005	NA
MW-7	8/29/89	<0.05	<0.05	<0.05	<0.0005	<0.0005	<0.0015	<0.0015	<0.002
MW-7	12/5/89	< 0.05	< 0.05	< 0.05	< 0.0005	<0.0005	< 0.0005	< 0.0005	NA
MW-8	8/29/89	<0.05	<0.05	<0.05	<0.0005	<0.0005	<0.0015	<0.0015	<0.002
MW-8	12/11/89	< 0.05	< 0.05	0.0011	< 0.0005	< 0.0005	< 0.0005	< 0.0005	NA
MW-9	12/13/89*	< 0.05	0.23	0.54	< 0.0044	< 0.006	< 0.0072	< 0.005	NA
MW-10	12/13/89*	< 0.05	0.11	0.30	< 0.0044	<0.006	< 0.0072	< 0.005	NA

NA - Not Analyzed * BTEX analyses by GCMS (EPA Method 624)

TABLE 5: Physical Monitoring Results: Evidence of Contamination*

Well No.	<u>Date</u>	Depth to <u>Water (ft.)</u>	Petroleum Odor <u>in Water</u>	Thickness Floating Product (inches)	<u>Notes</u>
MW-1	5/25/89	10.43	Yes	0.0	Gray sheen
MW-1	8/29/89	10.94	Yes	0.0	Sheen
MW -1	1 2/5/89	10.32	Yes	0.0	No sheen
MW-2	5/25/89	11.63	No	0.0	No sheen
MW-2	8/29/89	12.62	No	0.0	No sheen
MW-2	1 2/5/89	11.83	No	0.0	No sheen
MW-3	5/25/89	10.43	No	0.0	No sheen
MW-3	8/29/89	10.90	No	- 0.0	No sheen
MW-3	12/5/89	10.46	Yes	0.0	No sheen
MW-4	5/25/89	10.72	Yes	0.0	Sheen
MW-4	8/29/89	11.28	Yes	0.0	No sheen
MW-4	12/5/89	10.53	Yes	0.0	No sheen
MW-5	8/30/89	11.38	Yes	0.0	No sheen
MW-5	12/5/89	11.27	Yes	0.0	No sheen
MW-6	8/29/89	10.59	Yes	0.0	No sheen
MW-6	12/5/89	8.23	No	0.0	No sheen
MW-7	8/29/89	9.75	No	0.0	No sheen
MW-7	12/5/89	9.29	No	0.0	No sheen
MW-8	8/29/89	9.02	No	0.0	No sheen
MW-8	12/5/89	9.87	No	0.0	No sheen
MW-9	12/5/89	11.52	No	0.0	No sheen
MW-10	12/5/89	9.55	No	0.0	No sheen

^{*} Sheen; odor; FID; color; PID (opened/odor trapped in casing)

TABLE 6: Neighborhood Potentially Responsible Parties

Site Name Location

American Can Company 3801 East 8th Street

EBMUD Oakport Street

Eko-Tek 4200 Alameda Avenue


Exxon 720 High Street

Owens-Illinois 3600 Alameda Avenue

U.S. Cold Storage 3925 Alameda Avenue

I.M. Rich Paint Company 615 High Street

Sandblasting Co. 4356 Coliseum Way



SITE LOCATION MAP

SHELL OIL COMPANY 630 High Street Oakland, California

Scale AS SHOWN Project No.

Prepared by


Approved by


88-44-369-01 Date

KGC 3/16/89 Checked by Drawing No. **RMB**

DWC







TASKS

Program 1: Onsite Soil investigation/Remediation

Task 1 Drill and Sample Soil Borings

Task 2 Drill Step-Out Borings

Task 3 Prepare Soil Remedial Action Plan (if needed)

Task 4 Remediate Soil (if needed)

Task 5 Establish Clean Standards - Soil

Task 6 Confirm Remediated Soil

Program 2: Onsite Groundwater Investigation

Task 7 Install/Develop Groundwater Monitoring Wells

Task 8 Sample/Analyze Groundwater

Task 9 Conduct Hydrology Tests and Research

Program 3: Offsite Groundwater Investigation (if needed)

Task 10 Perform Neighborhood Assessment

Task 11 Refer to Legal Counsel

Task 12 Inform RWQCB

Task 13 Prepare Offsite Groundwater Investigation Plan

Task 14 Install Offsite Wells, Sample/Analyze

Program 4: Groundwater Remediation (if needed)

Task 15 Prepare Groundwater Remedial Action Plan

Task 16 Implement Remedial Action Plan

Task 17 Establish Cleanup Standards - Groundwater

Task 18 Confirm Groundwater Remediation

QUESTIONS

Q1: Are there concentrations of TPH greater than 100 ppm in any soil?

Q2: Is soil characterized?

Q3: Is the leaching potential acceptably low for contaminants proposed to be left in place?

Q4: Is groundwater actionable?

Q5: Is groundwater characterized onsite?

Q6: Does groundwater pollution extend offsite?

Q7: Is groundwater characterized offsite?

Q8: Is the environmental risk acceptably low for contaminants proposed to be left in groundwater?

SUMMARY OF PROGRESS - QUARTER 3, 1989

SHELL OIL COMPANY 630 High Street Oakland, California Scale N/A


LQL Drawing No


ecked By


3


Converse Environmental Consultants California Approved By


DWC

































ATTACHMENT 1

	MAJOR DIVIS	sions	SYM	8013	TYPICAL NAMES
		Clean grovels with little or	GW	O.	Well graded gravels, gravel - sand mixtures
O sieve	GRAVELS More than	no fines	G۴		Poorly graded gravels, gravel-sand mixtures
SOILS No. 20	half coorse fraction is larger than	Gravels with	GM		Silty gravels, poorly graded gravel—sand—silt mixtures
COARSE GRAINED e than half is larger than	No. 4 sieve	over 12% fines	GC		Clayey gravels, poorly graded gravel – sand – clay mixtures
	SANDS	Clean sands	sw	000	Well groded sands, grovelly sands
	More than	no fines	SP		Poorly graded sands, gravelly sands
	half coarse fraction is smaller than	Sands with	SM		Silty sands, poorly graded sand – silt mixtures
2	No. 4 sieve	over 12% fines	sc		Clayey sands, poorly groded sand-clay mixtures
9 2		· · · · · · · · · · · · · · · · · · ·	ML		Inorganic silts and very fine sands, rock flour, silty or clayey fine sands, or clayey silts with slight plasticity
SOILS Io. 200 sieve		AND CLAYS	CL		Inorganic clays of low to medium plasticity, gravelly clays, sandy clays, silty clays, lean clays
JED SC on No.					Organic clays and organic silty clays of low plasticity
FINE GRAINED SO half is smaller than No.			мн		Inorganic silts, micoceous or diatomaceous fine, sandy or silty sails, elastic silts
FINE Fis smo		ND CLAYS greater than 50	СН		Inorganic clays of high plasticity, fat clays
Pe					Organic clays of medium to high plasticity, organic silts
ı	HIGHLY ORGA	NIC SOILS	Pt		Peat and other highly organic soils



DRIVE SAMPLE, 2.5" ID Sampler, driven with 140 lb. weight, 30" drop NO RECOVERY Water level at time of drilling Stabilized water level on date noted

Note:

Soil conditions indicated by boring logs apply only at the location of the particular boring and at the time of drilling. Subsurface conditions may differ at other locations and may change at the boring location with the passage of time. Data presented in the logs represent a simplification of the actual conditions encountered.

UNIFIED SOIL CLASSIFICATION AND BORING LOG SYMBOLS

		Scale	Project No.
		Prepared by	Date
		Checked by	Drawing No.
₩	Converse Environmental Consultants California	Approved by	- A 1

LOG OF BORING NO.SB-4

DATE	DAI	LLE	D; 11-1	15-89 EL	EVATION:	——————————————————————————————————————	L TAKEN: n/a EQUIPMENT: 3 3/	4"x 8"	Hollo	w-Stem	Auger
оертн (ft)	SAMPLE	NATER LEVEL	SYMBOL	MOISTURE	CONSISTENCY	COLOR	DESCRIPTION	BLOWS/FT.	0.V.K. (ppm)	DRY DENSITY 1b/ft ³	TESTS
			000000	slightly moist	medium dense	yellow brown	Sandy GRAVEL. GW (Fill)				
_				slightly moist	medium	brown	Gravelly SAND. SW (Fill) Fine Sandy SILT, ML organics. (Fill)				
5-	1			moist		black	Silty CLAY, CH trace Gravel, brown organics.	11	0		-
-							Ciltu CIAV				
_	2					black	Silty CLAY.	11	0	<u> </u>	
10-							Total Depth of Boring: 9 ft Below Ground Surface.				
-							PROFESSION (Company) Solve Douglas W. Charlton (Company) No. 4110				
15-							Douglas W. Charlion Signature of CALL CO.				
-											
20-									Protect		

SHELL OIL COMPANY 630 High Street Oakland, California Project No.

88-44-369-01



Converse Environmental West

Drawing No.

A-2

LOG OF BORING NO.MW-9

DATE	DRI	LLE	D: 11-1	15-89 EL	EVATION:	· · · · · · · · · · · · · · · · · · ·	BUHING NO.MW-S EQUIPMENT: 3 3/4"x 8" Hollow-Stem AL	ıger
ОЕРТН (Ft)	SAMPLE	KATER LEVEL	SYMBOL	MOISTURE	CONSISTENCY	COLOR	MELL CONSTRUCTION BLOMS/FT.	T.P.H. (ppm)
			000	slightly moist	medium dense	מאסיום	Sandy angular GRAVEL, GW trace Clay. (Fill)	
_				moist slightly moist	stiff	tan and gray	Increasing Sand. Silty CLAY, CL trace fine Sand.	
_	1			moist very moist	medium	gray green light gray	Silty CLAY, little Sand, CL trace Gravel. Black staining. No odor. 7 0	
5- -				110200		green gray	OROFESS/O	
_							Douglas W. Charlton & Shaper S	
10-	2	Ā		wet	medium dense	brown	trace Clay.	
				moist	stiff	tan mottled black	Silty CLAY, little Sand, CL : 8 trace Gravel. Rust staining. 15 0	
_							17 0	
15-				wet	dense	dark gray	SAND and GRAVEL. SP/GP 53 0	
							Total Depth of Boring: 16 ft Below Ground Surface.	
-						; ;		
20-		<u> </u>		<u></u>		<u> </u>	Project No.	

SHELL OIL COMPANY 630 High Street Oakland, California

Project No.

88-44-369-01



Drawing No. Converse Environmental West

LOG OF BORING NO.MW-10

DATE	DRI	LLE	D: 11-1	1 <i>5-89</i> El	_EVATION:	JG UF	WL TAKEN: n/a EQUIPMENT: 3 3/4"x 8" Hollow-Stem Auger
ОӨРТН (ГС)	SAMPLE	NATER LEVEL	SYMBOL	MOISTURE	CONSISTENCY	COLOR	MOITAINSSEAD WELL CONSTRUCTION BLOWS/FT. (ppm)
-				slightly moist moist	medium dense	gray brown yellow brown	Sandy angular GRAVEL. GW (Fill) Gravelly SAND, SW trace cobble. (Fill)
-				slightly moist	medium	brown	Fine Sandy SILT, ML trace Gravel. (Fill)
5-	1			moist		black	Silty CLAY. CH
	_			 very	 medium	gray blue	Silty CLAY, trace Sand. CL
10-	2	∇		moist	dense	green	Staining. Odor. grading to SAND and CLAY. Thin lenses white angular Gravel. Odor.
-		Ā		wet slightly moist	'stiff	gray tan	Gravelly SAND. SP
15-				10 00000000000000000000000000000000000	FESSION AL	tan	Silty Clay, mottled rust and black, trace fine Sand.
-				A REGIS	Cheritan d 4110	36157 *	Total Depth of Boring: 17 ft Below Ground Surface.
20-	<u> </u>						Protect No.

SHELL OIL COMPANY 630 High Street Oakland, California Project No.

88-44-369-01



Converse Environmental West

Drawing No.

ATTACHMENT 2



NET Pacific, Inc. 435 Tesconi Circle Santa Rosa, CA 95401 Tel: (707) 526-7200 Fax: (707) 526-9623

CTT - CONTESTA

Marc Yalom Converse Consultants 55 Hawthorne St., Ste 500 San Francisco, CA 94105

11-30-89

NET Pacific Log No: 8618 Series No: 103.1

Client Ref: Proj#88-44-369-01-11

Subject: Analytical Results for "Shell - 630 High Street, Oakland" Received

11-17-89.

Dear Mr. Yalom:

Sample analysis in support of the project referenced above has been completed and results are presented on following pages. Should you have questions regarding procedures or results, please feel welcome to contact Client Services.

Submitted by:

Approved by:

Judy Ridley Client Services Jules Skamarack

Laboratory Manager

/sm

Enc: Sample Custody Document

KEY TO ABBREVIATIONS and METHOD REFERENCES

Abbreviations

mean : Average; sum of measurements divided by number of measurements.

mg/Kg (ppm): Concentration in units of milligrams of analyte per kilogram of sample, wet-weight basis

(parts per million).

mg/L : Concentration in units of milligrams of analyte per liter of sample.

mL/L/hr : Milliliters per liter per hour.

MPN/100 mL : Most probable number of bacteria per one hundred milliliters of sample.

N/A : Not applicable.

NA : Not analyzed.

ND : Not detected; the analyte concentration is less than applicable listed

reporting limit.

NR : Not requested.

NTU : Nephelametric turbidity units.

RPD : Relative percent difference, 100 [Value 1 - Value 2]/mean value.

SNA : Standard not available.

ug/Kg (ppb): Concentration in units of micrograms of analyte per kilogram of sample, wet-weight basis

(parts per billion).

ug/L : Concentration in units of micrograms of analyte per liter of sample.

umhos/am : Micramhos per centimeter.

Method References

Methods 601 through 625: see "Guidelines Establishing Test Procedures for the Analysis of Pollutants" U.S. EPA, 40 CFR, Part 136, rev. 1988.

Methods 1000 through 9999: see "Test Methods for Evaluating Solid Waste", U.S. EPA SW-846, 3rd edition, 1986.

^{*} Reporting Limits are a function of the dilution factor for any given sample. To obtain the actual reporting limits for this sample, multiply the stated reporting limits by the dilution factor.

		Descriptor, Lab No. and Results		
	Reporting	MW-9 #1 5' 11-15-89	MW-10#1 5' 11-15-89	MW-10#2 9' 11-15-89
<u>Parameter</u>	Limit (ppm)	(-39837)	(-39838)	(-39839)
Lead (EPA 7421)	0.2	170	120	3.1
PETROLEUM HYDROCARBONS VOLATILE (SOIL) DILUTION FACTOR * DATE ANALYZED METHOD GC FID/5030 as Gasoline METHOD 8020 Benzene Ethylbenzene Toluene Xylenes, total PETROLEUM HYDROCARBONS EXTRACTABLE (SOIL) DILUTION FACTOR * DATE EXTRACTED DATE ANALYZED METHOD GC FID/3550 as Diesel as Motor Oil	1 0.0025 0.0025 0.0025 0.0025		1 11-27-89 ND ND ND 0.049 ND 10 11-18-89 11-20-89 ND 240	1 11-28-89 ND ND ND ND ND ND 11-18-89 11-20-89 380 ND

		Descripto and Resul	or, Lab No. ts
	Reporting	SB4 #1 5' 11-15-89	SB4 #2 9' 11-15-89
Parameter	Limit (ppm)	(-39840)	(-39841)
Lead (EPA 7421)	0.2	220	3.9
PETROLEUM HYDROCARBONS VOLATILE (SOIL) DILUTION FACTOR * DATE ANALYZED METHOD GC FID/5030 as Gasoline METHOD 8020 Benzene Ethylbenzene Toluene Xylenes, total PETROLEUM HYDROCARBONS EXTRACTABLE (SOIL) DILUTION FACTOR * DATE EXTRACTED DATE ANALYZED METHOD GC FID/3550 as Diesel	1 0.0025 0.0025 0.0025 0.0075	 1 11-27-89 ND ND ND 0.032 ND 1 11-18-89 11-27-89 16	
as Diesel as Motor Oil	10	16 77	ND 11



WICH

8618

PM:MIY

CHAIN OF CUSTODY RECORD

CHAIN OF CUSTODY RECORD	
Project No. Project Name 88-41-367-01-11 630 High 5'+ Samplers: (signature) Station Date Time & P. Station Location	
No. Date Time () ()	Remarks
11/15/89 Drive 1 @ 5 1 x x x x	S+D TAT
140 1 20 10 1 nold	saturated
JIO Drive 1 @ 5 1 X X X X	
MW10 20 7 1 X X X X	
584 ZQ 9 1 XXXX	
Relinquished by: (signature) Date/Time Received by: (signature) Relinquished by: (signature) Date V. Of 11/16/14:45 Jeff Delle Vignature) Date Vignature	e/Time Received by: (signature)
Relinquished by: (signature) Date/Time Received by: (signature) Relinquished by: (signature) Date	re/Time Received by: (signature)
Relinquished by Courier: Date/Time Received by Mobile Lab: Relinquished by Mobile Lab: (signature) Date/Signature)	te/Time Received by Courier: (signature)
Shipped by: (signature) Courier from Airport: Rece	eived for Laboratory: Date/Time liature) 11-178/070