

TRANSMITTAL

TO: Mr. Thomas Bauhs

Chevron Products Company

P.O. Box 6004

San Ramon, CA 94583

DATE: December 21, 2000

PROJECT #: 346473.04/DG94612C.4C

SUBJECT: Site Conceptual Model for

Former Chevron Service

Station #9-4612.

FROM:

Barbara Sieminski Project Geologist Gettler-Ryan Inc. 6747 Sierra Court, Suite G

Dublin, California 94568

WE ARE SENDING YOU:

COPIES	DATED	DESCRIPTION					
1	12/14/00	Site Conceptual Model for Former Chevron Service					
		Station #9-4612, 3616 San Leandro Street,					
		Oakland, California.					

THESE ARE TRANSMITTED as checked below:

- [] For review and comment [] Approved as submitted [] Resubmit _ copies for approval
- [X] As requested [] Approved as noted [] Submit _ copies for distribution
- [] For approval [] Return for corrections [] Return __ corrected prints
- [X] For your files
- cc: Mr. James Brownell, Delta Environmental Consultants, Inc.
 - Ms. Bette Owen, Chevron Products Company
 - Mr. Barney Chan, Alameda County Health Services Agency
 - Mr. Terry Mc Ilraith
 - Mr. Jack Ratto, Ratto Land Company
 - GR File

COMMENTS: Attached is a copy of the report for your use. Copies of this report have been submitted to the above listed parties. Please call if you have questions.



3164 Gold Camp Drive Suite 200 Rancho Cordova, CA 95670-6021 U.S.A. 916/638-2085 FAX: 916/638-8385

SITE CONCEPTUAL MODEL

for Former Chevron Service Station #9-4612 3616 San Leandro Street Oakland, California

Report No. 346473.04-1

Prepared for:

Mr. Thomas Bauhs **Chevron Products Company** P.O. Box 6004 San Ramon, California 94583

Prepared by:

Delta Environmental Consultants Inc.

Network Associate Gettler-Ryan Inc. 6747 Sierra Court, Suite G Dublin, California 94568

Barbara Sieminski

Project Goologist

R.G. 6676

(916) 631-1314 Sacranento

No. 6676

Stephen J. Carter Senior Geologist

R.G. 5577

December 14, 2000

TABLE OF CONTENTS

1.0 INTROD	UCTION 1
2.0 SITE DE	SCRIPTION 1
	eneral 1
2.2 Pr	evious Environmental Work
2.3 G	eology and Hydrogeology4
	NCEPTUAL MODEL4
	lease Scenario and Plume Characterization4
	tential Receptors5
	her Environmental Issues6
4.0 DISCUSS	SION AND RECOMMENDATION
	FIGURES
Figure 1.	Vicinity Map
Figure 2.	Site Plan
Figure 3.	Site Conceptual Model
Figure 4.	TPHg Concentration in Site Wells
Figure 5.	Benzene Concentrations in Site Wells
Figure 6.	MtBE Concentrations in Site Wells
	APPENDICES
Appendix A:	Soil Data
Appendix B:	Groundwater Data
	Potentiometric Maps
Appendix D:	List of Wells within ½-mile Radius
Appendix E:	Utility Map
Appendix F:	Soil Vapor Chemical Analytical Data
Appendix G:	Cross Sections and Boring Logs

SITE CONCEPTUAL MODEL

for
Former Chevron Service Station #9-4612
3616 San Leandro Street
Oakland, California

Report No. 346473.04-1

1.0 INTRODUCTION

At the request of Chevron Products Company (Chevron), Delta Environmental Consultants Inc./Gettler-Ryan Inc. (GR) is submitting this report presenting the site conceptual model (SCM) for the former Chevron Service Station #9-4612 located at 3616 San Leandro Street in Oakland, California. The purpose of this work was to evaluate whether the implementation of further environmental investigation and/or remediation related to soil and groundwater is warranted at the site. This report was prepared based on information supplied by Chevron, and describes site hydrogeological conditions and distribution of contaminants in space and time, identifies potential current and future receptors, and recommends the most appropriate action plan for the site.

2.0 SITE DESCRIPTION

2.1 General

The subject site is a former Chevron service station located on the northwestern corner of the intersection of San Leandro Street and 37th Avenue in Oakland, California, as shown on the Vicinity Map (Figure 1). The former station facilities included a station building, three fuel underground storage tanks (USTs), one waste oil UST, and two dispenser islands. All aboveground and underground former Chevron station structures islands have been removed in 1976. A warehouse building was constructed in the western portion of the site in 1988. Currently, the warehouse building is used by Appliance Part & Equipment Distributors. The eastern portion of the property is a fenced vacant land. The current and former site features are shown on the Site Plan (Figure 2).

The site vicinity is used for residential, commercial, and transportation purposes. The subject site is bounded by a residential property to the west, Bay Area Rapid Transit (BART) tracks to the north, 37th Avenue to the east, and San Leandro Street to the south. A residential building is situated approximately 4 feet the western border of the subject site. A commercial building (a warehouse for Remanufactured Auto Parts East Bay Generator Co.) is located east of the site, across 37th Avenue. Commercial buildings (Smog Station Auto Repair, Favro Construction), a church, and residential buildings are located south of the subject site, across San Leandro Avenue.

2.2 Previous Environmental Work

Station Demolition and Groundwater Monitoring Well Installation

All aboveground and underground former Chevron station structures including a station building, three fuel USTs, one waste oil UST, and two dispenser islands were removed in September 1976. Soil samples were not collected during UST removal activities. In 1988, a warehouse building was constructed in the western portion of the site, over the area of the former fuel USTs. Geotechnical borings (B-1 through B-3) drilled in the warehouse area prior to building construction (in March 1988) indicated strong gasoline odor in saturated soil at depths of approximately 20 feet below ground surface (bgs). In August 1988, groundwater monitoring well VH-1 was installed to monitor groundwater condition beneath the warehouse building. Unsaturated samples were not collected for analysis from boring VH-1. Saturated samples collected from this boring at approximate depths of 20.5 and 25.5 feet bgs did not contain total petroleum hydrocarbons as gasoline (TPHg), but contained up to 0.042 parts per million (ppm) of benzene. The groundwater sample collected from well VH-1 contained 11,000 ppb of TPHg, 3,300 parts per billion (ppb) of benzene, and 3 ppb of 1,2-dichloroethane (EDC). 1,2-dibromoethane (EDB) was not detected in this sample. Soil or groundwater remediation was not performed, but the warehouse building was constructed.

Two additional on-site wells (MW-2 and MW-3) were installed in February 1993, and one off-site well (MW-4) was installed in August 1995. One on-site soil boring (SB-1) was also drilled in August 1995. Soil samples collected from borings MW-2 and MW-3 at 5 feet bgs (unsaturated samples) and 10 feet bgs (saturated samples) did not contain TPHg or benzene, toluene, ethylbenzene and xylenes (BTEX). Unsaturated soil samples from borings MW-4 and SB-1 were not collected for analysis. The saturated soil samples collected from borings SB-1 and MW-4 at 21.5 feet bgs contained 16 ppm and 2 ppm of TPHg, respectively, but did not contain benzene. A grab groundwater sample from boring SB-1 contained 21,000 ppb TPHg and 240 ppb benzene. Well and boring locations are shown on Figure 2. Tables summarizing soil and groundwater data are included in Appendices A and B, respectively.

Groundwater Monitoring and Sampling

Groundwater beneath the subject site has been monitored and sampled since August 1988. During this period of time a shallow groundwater depth has fluctuated between 5 and 15 feet bgs, however, groundwater depths exceeding 13 feet bgs have been noted only few times (in well VH-1 in September and October 1989, and in well MW-3 in November 1993). Groundwater beneath the site flowed to the northeast prior to September 1993. Since December 1993, groundwater has flowed toward well MW-2 and then southwest. The gradient has ranged from 0.01 to 0.05. Potentiometric maps are included in Appendix C.

The groundwater sampling data indicate that groundwater beneath the subject site has been impacted by hydrocarbons at concentrations up to 21,000 ppb TPHg, 2,200 ppb benzene, 590 ppb methyl tertiary butyl ether (MtBE), and 1,400 ppb total petroleum hydrocarbons as diesel (TPHd). The highest hydrocarbon concentrations have been present in groundwater in the vicinity of boring SB-1 and wells VH-1 and MW-2.

346473.04-1

TPHg and benzene concentrations have decreased in well VH-1 since groundwater monitoring began, but MtBE concentrations in this well have not changed significantly. Hydrocarbon concentrations in wells MW-2 and MW-3 have not changed significantly (except for benzene concentration in MW-2, which has decreased). Hydrocarbon concentrations in on-site wells appear to have stabilized. During the latest monitoring event (July 2000), hydrocarbon concentrations in site wells were up to 3,000 ppb of TPHg, 76 ppb of benzene, 490 ppb of TPHd, and 130 ppb of MtBE. Off-site well MW-4 has contained hydrocarbons only on few occasions. The lateral extent of hydrocarbon impacted groundwater has not been delineated, except for benzene and MtBE to the southeast (nondetectable concentrations in MW-4). The oxygen release compound (ORC) was installed in wells VH-1, MW-2 and MW-3 in February 1999. However, the dissolved oxygen concentrations in these wells after the ORC installation were not significantly different from the concentration in downgradient background well MW-4.

Well and Underground Utility Surveys

The review of DWR's files conducted in February 1993 indicated that 36 active and 25 destroyed wells are located within the ½-mile radius of the subject site. Two of the identified active wells were water producing wells (one irrigation well and one industrial well). The nearest active well is a cathodic protection well belonging to PG&E and located approximately 500 feet northwest (upgradient) of the subject site. Both water producing wells are located approximately 1,000 feet upgradient of the subject site. The nearest active well located crossgradient or downgradient of the subject site is the monitoring well located at the BART Fruitvale station approximately 1,000 feet crossgradient of the subject site. The well locations are shown on Figure 1, and the list of the wells is included in Appendix D.

Underground utilities are present in the streets bordering the subject site. Underground utilities present in San Leandro Street include gas, sewer, and water lines and Shell fuel line. Deputs an action of the utilities.

The Shell fuel line may be a potential secondary source of hydrocarbons in the downgradient vicinity of the subject site. Underground utility location map is included in Appendix E.

Soil Vapor Survey

Vapor sampling was performed at the site in February 1999 to assess soil vapor concentrations beneath the existing warehouse building. Soil vapor samples were collected from two GeoProbe borings (VB-1 and VB-2) advanced to 3 feet bgs at the eastern ends of the former fuel USTs (just outside the warehouse building). The results of the soil vapor survey indicated the presence of: benzene (up to 2.7 parts per billion by volume [ppbv]), toluene (up to 5.8 ppbv), total xylenes (up to 3.32 ppbv), freon 12 (up to 4.8 ppbv), ethanol (up to 19 ppbv), acetone (up to 89 ppbv), 2-propanol (up to 370 ppbv), methylene chloride (0.68 ppbv), chloromethane (1.1 ppbv), trichloroethene (0.67 ppbv), styrene (1.2 ppbv), and 1,2,4-trimethylbenzene (0.79 ppbv). The detected levels of contaminants were below the permissible exposure limits (PELs) listed in the NIOSH Guide to Chemical Hazards, suggesting no apparent risk to short time volatile organic exposure for human health or the environment. Soil Vapor Chemical Analytical Data Table is included in Appendix F.

Conda.

Groundwater beneath the subject site has been monitored and sampled since August 1988 through the network of four groundwater monitoring wells. During this period of time shallow groundwater fluctuated between 5 to 15 feet bgs, and flowed to the southwest. The groundwater sampling data indicate that groundwater beneath the subject site has been impacted by gasoline hydrocarbons at concentrations up to 21,000 ppb TPHg, 2,200 ppb benzene, 590 ppb MtBE, and 1,400 ppb TPHd. Hydrocarbon concentrations in on-site wells appear to have stabilized (Figures 4 through 6). Currently, hydrocarbon concentrations in groundwater beneath the site are up to 3,000 ppb TPHg, 76 ppb benzene, 490 ppb TPHd, and 130 ppb MtBE. However, as MtBE was not added to gasoline when the station was closed in 1976, the presence of MtBE in groundwater beneath the site appears to be from a secondary source. The lateral extent of hydrocarbon impacted groundwater has not been delineated, except for benzene and MtBE to the southeast (nondetectable concentrations in MW-4). The second of the concentrations in MW-4.

3.2 Potential Environmental Receptors

The hydrocarbon plume extends beneath the warehouse building, the vacant land east of the warehouse building, and possibly beneath the residential building on the adjacent property (4 feet west of the warehouse building), and also possibly beneath the public street (San Leandro Street). The potential exposure receptors are current and future workers in the existing warehouse building (and potential future building in the eastern portion of the site) and in other commercial buildings in the site vicinity; current and future site visitors (Appliance Part and Equipment Distributors clients, motorist, pedestrians, etc.); future construction workers (development of the eastern portion of the site, utility maintenance); and residents of the houses in the vicinity of the site. The nearest water producing wells are located 1,000 feet upgradient of the subject site, therefore are not likely to be receptors for the Chevron plume. The nearest crossgradient well (Fruitvale station monitoring well) is located 1,000 feet of the subject site, and the nearest downgradient wells are located almost ½ mile of the subject site. Based on the distance to the subject site, these wells do not appear to be the likely receptors or vertical conduits for the Chevron plume.

The potential exposure mediums are ambient air, indoor air in commercial and residential buildings, and soil and groundwater in potential future excavation areas. The major exposure pathway is hydrocarbon volatilization from smear zone soils and groundwater to ambient and indoor air. A dermal contact with hydrocarbon impacted soil and groundwater is the potential exposure pathway for construction workers (potential future development of the eastern portion of the subject site), and utility maintenance workers (if utilities are present within the plume area).

3.3 Other Environmental Issues

The lateral extent of hydrocarbon impacted soil and groundwater has not been fully delineated, especially in the downgradient and crossgradient directions, where the residential properties are present. To adequately evaluate risks associated with the hydrocarbon plume, it is necessary to know whether the plume extends beneath the residential houses and what is the magnitude of the impact (if any).

The results of soil vapor survey indicated that hydrocarbon concentrations in soil vapors beneath the existing warehouse building do not exceed PELs. However, PELs pertain to short term exposures only. The long term exposure risk for warehouse workers was not evaluated.

346473.04-1 5

Due to shallow groundwater, the utility trenches may act as the preferential pathways and conduits that could enhance contaminant migration. The Shell fuel line (unknown condition) present beneath the southern side of San Leandro Street might be a secondary source for hydrocarbons in the vicinity of the subject site. This line also appears to be a likely source of MtBE detected in groundwater beneath the subject site.

need to Show

4.0 DISCUSSION AND RECOMMENDATION

Site conditions consist of petroleum impacted soil and groundwater. Hydrocarbon impacted soil appears to be present within the smear zone (5 to 15 feet bgs), however, information regarding unsaturated soil condition is limited. Concentrations of hydrocarbons in groundwater appeared to stabilize but not at low levels indicating that natural biodegradation rate is slow. The use of the ORC compound in on-site wells has had a limited success in increasing natural biodegradation rate.

The dissolved hydrocarbon plume is not fully delineated. The plume extends beneath the warehouse building, the vacant land east of the warehouse building, and may extend beneath the residential building on the adjacent property and beneath San Leandro Street. Underground utilities are present in the immediate downgradient vicinity of the subject site (in San Leandro Street), and due to shallow groundwater may act as preferential pathways and conduits that could enhance contaminant migration. However, no water producing wells (potential dissolved plume receptors) are present at the site or in its immediate vicinity.

Since the primary sources have been removed, and concentrations of dissolved hydrocarbons appear to have stabilized, natural attenuation may be the preferable approach to remediate the site. However, before this approach is considered, potential threats to human health and the environment must be evaluated. The existing site data are not sufficient to perform an appropriate risk evaluation for the identified receptors (human receptors in the current and future commercial buildings at the subject site and in the residential building at the adjacent property). Therefore, GR recommends additional environmental investigation to obtain site specific data to be used in risk evaluation:


- Hand-auger two borings to grandwater (approximately 12 feet bgs) between the existing warehouse and
 the house to the east (Figure 2) and collect soil and grand groundwater samples from the borings for laboratory
 analyses to evaluate whether hydrocarbon impacted soil and groundwater extend beneath the residential
 property west of the subject site.
- Advance three off-site GeoProbe borings in San Leandro Street (Figure 2) and obtain soil and grab
 groundwater samples from the borings to delineate the downgradient extent of the Chevron plume and to
 determine if the utility trenches act as preferential pathways for plume migration.
- Advance six on-site GeoProbe soil borings (Figure 2) and collect soil and grab groundwater samples from the borings to delineate the plume to the north and east, and obtain data to be used in risk evaluation for the existing warehouse building and for the future development in the eastern portion of the site.

6

346473.04-1

GR recommends conducting the Risk Based Corrective Action (RBCA) planning as described in ASTME-1739 based on the data collected from the borings to evaluate whether further evaluation and/or active remediation is required at the site. Quarterly monitoring and sampling of site wells shall be continued to confirm that the dissolved groundwater plume remains stable.

346473.04-1 7







6747 Sierro Ct., Suite J (925) 551-7555 Dublin, CA 94568 Former Chevron Service Station No. 9-4612 3516 San Leandro Street Oakland, California 1


JOB NUMBER 346473.04 REVIEWED BY

DATE

REVISED DATE









6747 Sierra Ct., Suite J Dublin, CA 94568


(925) 551-7555

TPHg CONCENTRATIONS IN SITE WELLS
Former Chevron Service Station No. 9-4612
3616 San Leandro Street
Oakland, California

4

JOB NUMBER 346473.04 REVIEWED BY

DATE 12/00 REVISED DATE





6747 Sierra Ct., Suite J Dublin, CA 94568

(925) 551-7555


BENZENE CONCENTRATIONS IN SITE WELLS Former Chevron Service Station No. 9-4612 3616 San Leandro Street Oakland, California

REVISED DATE

REVIEWED BY 346473.04

DATE 12/00

JOB NUMBER





6747 Sierra Ct., Suite J Dublin, CA 94568

(925) 551-7555

Former Chevron Service Station No. 9-4612 3616 San Leandro Street Oakland, California

JOB NUMBER 346473.04 REVIEWED BY

DATE 12/00 REVISED DATE

TABLE 1 Analytical Results of Soil Samples

(Results expressed as milligrams per kilogram)

Chevron Service Station No. 9-4612 3616 San Leandro Street Oakland, California

Date	Sample ID	Sample Depth (ft) ^a	Benzene	Toluene	Ethyl- benzene	Xylenes	TPH-g
8-15-95	MW 4-16.5	16.5	<0.005	<0.005	<0.005	< 0.005	<1
8-15-95	MW 4-21.5	21.5	< 0.005	0.014	0.007	0.01	2
8-15-95	SB 1-21.5	21.5	< 0.005	0.12	0.21	1.1	16

TPH-g = total petroleum hydrocarbons as gasoline

a = feet below surface grade

TABLE 1 ANALYTICAL RESULTS FOR SOIL SAMPLES (Concentrations in parts per million)

Date	Sample ID	Sample Depth (ft)	Benzen e	Toluene	Ethyl- benzene	Total Xylenes	TPH-as- Gasoline	Total Lead
08/10/88	VH-1	20.5 25.5	0.042 0.036	<0.005 <0.005	<0.005 <0.005	<0.005 <0.005	<0.5 <0.5	6 6&7
02/01/93	MW-13	5 10	<0.005 <0.005	<0.005 <0.005	<0.005 <0.005	<0.005 <0.005	<1 <1	NA NA
02/01/93	MW-2	5 10	<0.005 <0.005	<0.005 <0.005	<0.005 <0.005	<0.005 <0.005	<1 <1	NA NA

TPH = Total petroleum hydrocarbons

NA = Not applicable MW = Monitoring well

Data for VH-1 from Vonder Haar Hydrogeology Report, September 16, 1988.

- Table 1 Groundwater Monitoring Data and Analytical Results

Former Chevron Service Station #9-4612 3616 San Leandro Street Oakland, California

Vertical Measurements are in feet.

Analytical results are in parts per billion (ppb)

Vertical M	ertical Measurements are in feet.					Oakiaid,	Camoina		Analytical results are in parts per billion (ppb)				
	Well	Ground	Depth									,	
DATE	Head	Water	To	Notes	TPH-	TPH-	Benzene	Toluene	Ethyl-	Xylenes	MTBE	MTBE	TOG
	Elev.	Elev.	Water	· · · · · · · · · · · · · · · · · · ·	Diesel	Gasoline		· · · · · · · · · · · ·	Benzene			by 8260	-
VH-1													
08/10/88			13.00			11,000	3300	200	520	540			
06/01/89			10.32			15,000	2200	120	540	310			
09/15/89			15.69			5600	1900	90	350	160			
12/08/89			14.77	-		11,000	1900	69	270	99			
03/07/91			11.26			4500	820	39	120	77		,==	
09/24/91		-	12.98			3300	520	19	39	27			
01/08/92			13.77			5000	600	34	81	76			
04/20/92			8.18	-		7400	670	60	110	140	_		
03/26/93	27.85	21.14	6.71			4900	600	40	72	94		-	
05/27/93	27.85	19.27	8.58		**	13,000	1600	120	230	220	***		
08/18/93	27.85	17.39	10.46		••	2700	210	10	8.1	18			
11/03/93	27.85	15.28	12.57	_		4600	680	42	35	68			
02/10/94	27.85	18.77	9.08			1900	260	19	22	29			-
05/12/94	27.85	19.76	8.09			2000	390	28	3.9	29			
08/26/94	27.85	17.10	10.75			4900	500	<5.0	23	31			
11/14/94	27.85	18.40	9.45		300	760	69	<2.0	<2.0	2.2	 ·		
02/01/95	27.85	21.88	5.97			1300	120	5.9	<0.5	13			
05/12/95	27.85	20.14	7.71		_	4400	460	31	45	49			
08/22/95	27.85	18.59	9.26			2900	310	15	28	32			
12/19/95	27.85	19.05	8.80		•-	930	53	<2.5	<2.5	<2.5	39		**
01/31/96	27.85	22.35	5.50	, 		3700	320	<10	41	40	180	••	
04/30/96	27.85	19.81	8.04			3900	270	<20	<20	<20	120		
08/01/96	27.85	18.67	9.18			2700	140	11	18	28	200		
10/30/96	27.85	18.67	10.76	· ·		2700	140	<12	<12	<12	280		
02/07/97	27.85	19.75	8.10	·		220	13	0.6	<0.5	1.6	15		
05/07/97	27.85	18.33	9.52		••	5200	33	12	21	26	330	••	••
07/22/97	27.85	17.43	10.42			4200	80	<10	16	24	400	••	
11/03/97	27.85	16.85	11.00			2400	150	6.8	6.5	9.5	510		
01/28/98	27.85	20.75	7.10	_	_	850	69	4.8	5.0).5 11	38	 48	. –
05/08/98	27.85	20.14	7.71			4200	200	30	3.0 40	42	•		• ==
07/29/98	27.85	18.40	9.45		-	3800	200 54	30 10			310	200	
11/06/98	27.85	17.15	10.70			4800			27	30	35	290	
	_,,,,,		10.70			4000	100	20	12	23	360	210	

Former Chevron Service Station #9-4612 3616 San Leandro Street

Oakland, California Vertical Measurements are in feet. Analytical results are in parts per billion (ppb) Ground Well Depth DATE Head Water To TPH-Notes TPH-Benzene Toluene Ethyl-**Xylenes** MTBE **MTBE** TOG Water Elev. Elev. Diesel Gasoline Benzene by 8260 VH-1 (cont) 02/09/99 27.85 21.87 5.98 ORC socks installed 2950 79.5 <10 <10 <10 435 312 05/13/99 27.85 19.71 8.14 4180 147 12.8 16.5 20.3 433 245 09/07/99 17.94 <5.0 27.85 9.91 2750 57.6 6.53 <5.0 297 233 11/24/99 27.85 17.36 10.49 2550 38 3.18 2.54 5.21 216+ --02/25/00 27.85 21.20 6.65 120 2.7 < 0.5 < 0.5 < 0.5 20.5 11.9 1.400^3 05/10/00 27.85 19.76 8.09 63 3.3 3.1 4.9 230 110 360³ 07/31/00 27.85 18.30 9.55 22 **ORC** in well 2.7 1.6 3.1 100 88 MW-2 02/16/93 27.51 9200 720 110 250 170 03/26/93 27.51 19.89 7.62 --05/27/93 27.51 18.04 9.47 360 5.3 2.1 1.8 2.5 08/18/93 27.51 16.46 11.05 9400 76 1100 110 100 11/03/93 27.51 14.56 12.95 8600 390 20 2.7 120 02/10/94 27.51 17.72 9.79 2700 370 38 44 41 05/12/94 27.51 18.59 8.92 3800 650 76 15 62 08/26/94 27.51 16.14 11.37 16,000 1300 270 28 120 11/14/94 27.51 17.48 10.03 5100 390 10 43 27 02/01/95 27.51 20.47 7.04 6900 520 82 170 110 05/12/95 27.51 18.76 8.75 7700 510 83 110 100 •• 08/22/95 27.51 17.35 10.16 4500 220 16 61 47 --12/19/95 27.51 18.05 9.46 2900 240 <10 19 18 220 01/31/96 27.51 21.91 5.60 3900 320 18 72 39 <25 04/30/96 27.51 18.68 8.83 5600 200 36 55 47 170 08/01/96 27.51 17.25 10.26 6200 190 15 62 59 220

10/30/96

02/07/97

05/07/97

07/22/97

27.51

27.51

27.51

27.51

17.25

18.11

17.57

16.36

11.48

9.40

9.94

11.15

190

210

190

18

<25

34

12

25

67

70

38

62

36

59

37

41

260

330

530

630

5700

8300

6900

10,000

⁺ Lab could not get a good ion chromatogram match for MTBE. See laboratory report,

^{9-4612.}xls/#386473

Former Chevron Service Station #9-4612 3616 San Leandro Street Oakland, California

Vertical Measurements are in feet.			Oakland, California					Analytical results are in parts per billion (p				
Well	Ground	Depth			CONTRACTOR CONTRACTOR							
Head	Water	To	Notes	TPH-	ТРН-	Benzene	Toluene	Ethyl-	Xylenes	MTBE	MTBE	TOG
Elev.	Elev.	Water		Diesel	Gasoline	······		Benzene			by 8260	
t)								·				
27.51	15.93	11.58			6500	260	8.5	26	14	590		**
27.51	15.93	11.58	Confirmation run								96	
27.51	19.38	8.13			6700	65	13	67	54	280	94	
27.51	18.89	8.62			5500	91	38	43	61	220	62	
27.51	17.06	10.45			3600	41	8.9	3.6	14	16	94	
27.51	15.89	11.62	==		6900	77	<5.0	14	17	290		
27.51	20.61	6.90	ORC socks installed		8070	75.6	<10	<10	<10	397		-
27.51	18.21	9.30	••	_	5890	120	<5.0	12.5	26.6	401		
27.51	16.57	10.94			5820	41.2	<5.0					
27.51	15.98	11.53			5940	40.9	<10					
27.51	21.00	6.51			6370	101	9.37			321		***
27.51	18.49	9.02			6.100^3							
27.51	17.18	10.33	ORC in well	••	3,000 ³	75	14	28	28	200	130	-
					•							
28.50			 .		3500	<0.5	8.1	4.6	7.7			
28.50	21.32	7.18				-	-	 ,				-
28.50	19.17	9.33			4200	580	84	150	100			
28.50	16.50	12.00		1400	910	12	3.7	6.2	3.8	-	••	<5000
28.50	15.21	13.29			5300	29	1.9	0.6	27			**
28.50	18.87	9.63		<50	63	<0.5	0.7	<0.5	<0.5			
28.50	19.73	8.77		84	<50	<0.5	0.5	<0.5	<0.5			
28.50	17.08	11.42	 .		2100	12	<0.5	5.0	0.5		•	
28.50	18.43	10.07	••		140	0.78	<0.5					
28.50	22.21	6.29		<50	<50						. ••	
28.50	20.43	8.07		540*								
28.50	18.55	9.95								٠	_	
	Well Head Elev. 27.51	Well Ground Head Water Elev. Elev. Elev. 27.51 15.93 27.51 15.93 27.51 15.93 27.51 19.38 27.51 17.06 27.51 15.89 27.51 17.06 27.51 15.89 27.51 20.61 27.51 16.57 27.51 16.57 27.51 16.57 27.51 17.18 28.50 21.32 28.50 21.32 28.50 19.17 28.50 16.50 28.50 19.17 28.50 18.87 28.50 19.73 28.50 17.08 28.50 17.08 28.50 22.21 28.50 20.43	Well Ground Depth Head Water To Elev. Elev. Water 27.51 15.93 11.58 27.51 15.93 11.58 27.51 19.38 8.13 27.51 18.89 8.62 27.51 15.89 11.62 27.51 15.89 11.62 27.51 16.57 10.94 27.51 15.98 11.53 27.51 15.98 11.53 27.51 15.98 10.33 27.51 15.98 11.53 27.51 15.98 10.33 27.51 15.98 10.33 28.50 21.32 7.18 28.50 17.18 10.33 28.50 19.17 9.33 28.50 15.21 13.29 28.50 15.21 13.29 28.50 19.73 8.77 28.50 17.08 11.42 28.50 <td>Well Ground Depth Head Water To Notes Elev. Elev. Water 27.51 15.93 11.58</td> <td>Well Ground Head Water Elev. Depth Water To Notes TPH-Diesel 27.51 15.93 11.58 27.51 15.93 11.58 Confirmation run 27.51 19.38 8.13 27.51 18.89 8.62 27.51 15.89 11.62 27.51 15.89 11.62 27.51 15.89 11.62 27.51 15.89 11.62 27.51 16.57 10.94 27.51 15.98 11.53 27.51 15.98 11.53 27.51 15.98 10.94 27.51 15.98 11.53 27.51 17.18 10.33 ORC in well 28.50 19.17 9.33 </td> <td> Well Ground Depth Head Water To Notes TPH- TPH- </td> <td> Well Ground Depth Head Water To Notes TPH- TPH- Benzene </td> <td> Well Ground Depth Head Water To Notes TPH- Diesel Gasoline TPH- Benzene Toluene </td> <td> Well Ground Depth Head Water To Notes TPH- Diesel Gasoline Toluene Behyl- Benzene Toluene Behyl- Benzene Toluene Toluene </td> <td> Well Ground Depth Head Water To Notes TPH- Diesel Gasoline Toluene Ethyl- Ethy</td> <td> Well Ground Depth Head Water To Notes TPH- Diesel Gasoline Benzene Toluene Ethyl- Renzene Renzene Renzene Renzene Renzene Renzene Renzene Renzene Renzene Renzene Re</td> <td> </td>	Well Ground Depth Head Water To Notes Elev. Elev. Water 27.51 15.93 11.58	Well Ground Head Water Elev. Depth Water To Notes TPH-Diesel 27.51 15.93 11.58 27.51 15.93 11.58 Confirmation run 27.51 19.38 8.13 27.51 18.89 8.62 27.51 15.89 11.62 27.51 15.89 11.62 27.51 15.89 11.62 27.51 15.89 11.62 27.51 16.57 10.94 27.51 15.98 11.53 27.51 15.98 11.53 27.51 15.98 10.94 27.51 15.98 11.53 27.51 17.18 10.33 ORC in well 28.50 19.17 9.33	Well Ground Depth Head Water To Notes TPH- TPH-	Well Ground Depth Head Water To Notes TPH- TPH- Benzene	Well Ground Depth Head Water To Notes TPH- Diesel Gasoline TPH- Benzene Toluene	Well Ground Depth Head Water To Notes TPH- Diesel Gasoline Toluene Behyl- Benzene Toluene Behyl- Benzene Toluene Toluene	Well Ground Depth Head Water To Notes TPH- Diesel Gasoline Toluene Ethyl- Ethy	Well Ground Depth Head Water To Notes TPH- Diesel Gasoline Benzene Toluene Ethyl- Renzene Renzene Renzene Renzene Renzene Renzene Renzene Renzene Renzene Renzene Re	

⁺ Lab could not get a good ion chromatogram match for MTBE. See laboratory report.

^{*} Chromatogram pattern indicates an unidentified hydrocarbon.

Former Chevron Service Station #9-4612 3616 San Leandro Street Oakland, California

Vertical Measurements are in feet.				Oakland,	California			Analytical results are in parts per billion (ppb					
DATE	Well Head Elev.	Ground Water Elev.	Depth To Water	Notes	TPH- Diesel	TPH- Gasoline	Benzene	Toluene	Ethyl- Benzene	Xylenes	МТВЕ	MTBE by 8260	TOG
MW-3 (co	nt)												
12/19/95	28.50	19.10	9.40		<50	<50	<0.5	<0.5	<0.5	<0.5	<2.5		
01/31/96	28.50	23.45	5.05		<50	<50	<0.5	<0.5	<0.5	<0.5	<2.5		
04/30/96	28.50	20.10	8.40		240*	320	2.4	<0.5	0.75	<0.5	7.8		
08/01/96	28.50	18.70	9.80	-	470*	980	9.6	<0.5	0.98	2.2	54		
10/30/96	28.50	18.70	11.48		760*	2000	14	<10	<10	<10	140		
02/07/97	28.50	19.90	8.60	_	61*	200*	<0.5	<0.5	<0.5	<0.5	8.9		
05/07/97	28.50	19.49	9.01		550*	3500	14	3.9	3.6	8.0	160		
07/22/97	28.50	17.38	11.12		800*	3500	55	<10	<10	<10	150		
11/03/97	28.50	16.99	11.51		910*	4100	140	<5.0	<5.0	<5.0	380	 .	
01/28/98	28.50	21.16	7.34		_	1100	24	<1.2	<1.2	2.8	33	6.1	
)5/08/98	28.50	20.44	8.06		250*	990	3.6	7.7	0.7	2.2	37	7.5	
07/29/98	28.50	18.25	10.25	-	290*	1200	13	<0.5	<0.5	1.4	11	28	_
11/06/98	28.50	17.11	11.39		390*	2600	5.3	<2.5	<2.5	3.0	91	41	
02/09/99	28.50	22.40	6.10	ORC socks installed	184*	406	<1.0	4.03	<1.0	<1.0	17.7	1.97	
05/13/99	28.50	19.38	9.12			615	13.8	1.05	<0.5	<0.5	43.5	21.2	
09/07/99	28.50	17.77	10.73		528*	2710	<5.0	<5.0	<5.0	<5.0	96.3	57.9	
11/24/99	28.50	17.37	11.13		1070*	5530	<5.0	<5.0	5.59	<5.0		66+	
02/25/00	28.50	22.22	6.28	- ·		189	4.68	<0.5	<0.5	<0.5	11.9	<2.0	
03/01/00	28.50	21.80	6.70	-	380*								
05/10/00	28.50	19.90	8.60		830 ²	1,600 ¹	22	<10	<10	<10	100	51	
07/31/00	28.50	18.43	10.07	ORC in well	496 ²	2,200 ¹	76	10	<5.0	13	230	52	-
					•								
MW-4													
08/22/95	27.27	18.16	9.11			9600	100	<10	<10	<10	•••	-	
12/19/95	27.27	18.97	8.30		-	<50	<0.5	<0.5	<0.5	<0.5	<2.5		
01/31/96	27.27	21.67	5.60		-	<50	<0.5	<0.5	<0.5	<0.5	<2.5	· 	
04/30/96	27.27	20.27	7.00	-		<50	<0.5	<0.5	<0.5	<0.5	<2.5	'	
08/01/96	27.27	18.12	9.15			<50	<0.5	<0.5	<0.5	<0.5			***

⁺ Lab could not get a good ion chromatogram match for MTBE. See laboratory report.

^{*} Chromatogram pattern indicates an unidentified hydrocarbon.

^{9-4612.}xls/#386473

Former Chevron Service Station #9-4612 3616 San Leandro Street

Oakland, California

Vertical Me	ertical Measurements are in feet.					Oakianu, Camornia						Analytical results are in parts per billion (ppb)			
DATE	Weli Head	Ground Water	Depth To	Notes	ТРН-	ТРН-	Benzene	Toluene	Ethyl-	Xylenes	MTBE	МТВЕ	TOG		
	Elev.	Elev.	Water		Diesel	Gasoline	··· ———		Benzene	· · · · · · · · · · · · · · · · · · ·		by 8260			
MW-4 (co	nt)														
10/30/96	27.27	18.12	10.74			110	<0.5	<0.5	<0.5	<0.5	<2.5				
02/07/97	27.27	19.47	7.80			80	<0.5	<0.5	<0.5	<0.5	4.1				
05/07/97	27.27	21.42	5.85			<50	<0.5	<0.5	<0.5	<0.5	<2.5				
07/22/97	27.27	17.22	10.05	-		150	<0.5	<0.5	<0.5	<0.5	<2.5				
11/03/97	27.27	16.55	10.72		-	52	0.9	<0.5	<0.5	<0.5	*				
01/28/98	27.27	20.76	6.51			<50	<0.5	<0.5	<0.5	<0.5	<2.5	<2.0			
05/08/98	27.27	20.25	7.02			56	<0.5	<0.5	<0.5	<0.5	<2.5	<2.0			
07/29/98	27.27	18.32	8.95	·		<50	0.9	<0.5	<0.5	<0.5	<2.5	<2.0			
11/06/98	27.27	16.68	10.59			72	<0.5	<0.5	<0.5	<0.5	<2.5	<2.0			
02/09/99	27.27	21.41	5.86	_		<50	<0.5	<0.5	<0.5	<0.5	<2.0	1.1			
05/13/99	27.27	19.32	7.95	**	·	<50	<0.5	<0.5	<0.5	<0.5	<5.0	<2.0	-		
09/07/99	27.27	17.79	9.48		-	70.2	<0.5	<0.5	<0.5	<0.5	<2.0	<1.0			
11/24/99	27.27	17.22	10.05			227	<0.5	<0.5	<0.5	<0.5		<0.5			
02/25/00				Inaccessible											
03/01/00	27.27	21.10	6.17			<50	<0.5	<0.5	<0.5	<0.5	<2.5	<2.0			
05/10/00				Inaccessible											
07/31/00	27.27	17.90	9.37		••	<50	< 0.50	<0.50	<0.50	<0.50	<2.5	<2.0	••,		

^{*} No value for MTBE could be determined; see lab report for analyses.

Former Chevron Service Station #9-4612 3616 San Leandro Street

Oakland, California Analytical results are in parts per billion (ppb) Vertical Measurements are in feet. Ground Depth Well DATE Water To TPH-TPH-Benzene Toluene Ethyl-**Xylenes MTBE** MTBE TOG Head Notes Elev. Water Gasoline by 8260 Elev. Diesel Benzene TRIP BLANK < 0.5 <0.5 <0.5 <1.5 <50 05/27/93 <5000 <0.5 < 0.5 <0.5 <1.5 <50 08/18/93 1400 < 0.5 <0.5 <0.5 <50 < 0.5 11/03/93 --<0.5 <50 <50 <0.5 < 0.5 <0.5 02/10/94 <50 <0.5 < 0.5 <0.5 < 0.5 84 05/12/94 < 0.5 <50 < 0.5 < 0.5 <0.5 08/26/94 <0.5 < 0.5 <0.5 <50 < 0.5 11/14/94 < 0.5 < 0.5 <0.5 < 0.5 02/01/95 <50 < 0.5 <0.5 <0.5 <50 < 0.5 05/12/95 08/22/95 <50 <0.5 <0.5 <0.5 <0.5 < 0.5 < 0.5 <0.5 < 0.5 <2.5 <50 12/19/95 <0.5 <2.5 <50 <0.5 < 0.5 < 0.5 01/31/96 < 0.5 <0.5 < 0.5 <2.5 <50 < 0.5 04/30/96 <50 <0.5 <0.5 <0.5 <0.5 <2.5 08/01/96 <0.5 <2.5 < 0.5 < 0.5 <50 < 0.5 10/30/96 <50 <0.5 <0.5 < 0.5 <0.5 <2.5 02/07/97 <0.5 <0.5 <2.5 < 0.5 < 0.5 05/07/97 <50 <0.5 <2.5 <50 < 0.5 < 0.5 < 0.5 07/22/97 <0.5 < 0.5 <2.0 01/28/98 <50 < 0.5 < 0.5 <2.0 05/08/98 <50 <0.5 <0.5 <0.5 < 0.5 <2.0 07/29/98 < 0.5 <2.5 <0.5 < 0.5 <0.5 <50 11/06/98 <0.5 <2.0 <50 < 0.5 <0.5 < 0.5 02/09/99 < 0.5 <5.0 05/13/99 <50 < 0.5 <0.5 < 0.5 < 2.0<2.0 <50 <0.5 < 0.5 < 0.5 <0.5 09/07/99 <50 < 0.5 <0.5 < 0.5 <0.5 <2.5 11/24/99 02/25/00 <50 < 0.5 < 0.5 < 0.5 <0.5 <5.0 <2.5 03/01/00 <50 <0.5 <0.5 < 0.5 <0.5 05/10/00 <50 < 0.50 < 0.50 < 0.50 < 0.50 <2.5 07/31/00 <50 < 0.50 < 0.50 < 0.50 < 0.50 <2.5

Table 1

Groundwater Monitoring Data and Analytical Results

Former Chevron Service Station #9-4612 3616 San Leandro Boulevard Oakland, California

EXPLANATIONS:

Groundwater monitoring data and laboratory analytical results prior to May 10, 2000, were compiled from reports prepared by Blaine Tech Services, Inc.

TPH = Total Petroleum Hydrocarbons

MTBE = Methyl tertiary butyl ether

TOG = Total Oil & Grease

-- = Not Measured/Not Analyzed

- Laboratory report indicates gasoline C6-C12.
- 2 Laboratory report indicates unidentified hydrocarbons <C16.</p>
- 3 Laboratory report indicates gasoline C6-C12 + unidentified hydrocarbons <C6.</p>

Table 2

Dissolved Oxygen Concentrations

Former Chevron Service Station #9-4612 3616 San Leandro Street


Oakland, California

05/10/00 07/31/00	0.90 1.25	-
07/31/00	1.25	
		
05/10/00	0.57	
07/31/00	1.26	••
05/10/00	1.56	••
07/31/00	1.46	•••
05/10/00	Inaccessible	—
07/31/00	0.64	-
	05/10/00 07/31/00 05/10/00	07/31/00 1.26 05/10/00 1.56 07/31/00 1.46 05/10/00 Inaccessible

EXPLANATIONS:

mg/L = milligrams per liter

- = Not Measured



July 31, 2000

FILE NUME: P:\EMMRO\CHEVRON\9-4612\000-9-4612.DWG | Loyout Tab: P013

PREPARED BY




Chevron Station 9-4612 3616 San Leandro Street Oakland, California

GROUNDWATER ELEVATION CONTOUR MAP, SEPTEMBER 7, 1999

FIGURE:

PROJECT:






Chevron Station 9-4612 3616 Son Leondro Street Oakland, California

GROUNDWATER ELEVATION CONTOUR MAP, MAY 13, 1999

FIGURE: 1 PROJECT: DACO4



EXPLANATION

MONITORING WELL

21.41 GROUNDWATER ELEVATION (FT, MSL)

22.00 - GROUNDWATER ELEVATION CONTOUR (FT, MSL)

APPROXIMATE GROUNDWATER FLOW DIRECTION; APPROXIMATE GRADIENT = 0.02



Bosemap from Combria Environmental Technology, Inc.

PREPARED BY

RRM
engineering contracting firm


Chevron Station 9-4612 3616 Son Leandro Street Oakland, California

GROUNDWATER ELEVATION CONTOUR MAP, FEBRUARY 9, 1999

FIGURE:

1 PROJECT:

DAC04



SAN LEANDRO STREET

● MW-4 16.68

EXPLANATION

MONITORING WELL

16.69 GROUNDWATER ELEVATION (FT, MSL)

16.00 - GROUNDWATER ELEVATION CONTOUR (FT, MSL)

APPROXIMATE GROUNDWATER FLOW DIRECTION;
APPROXIMATE GRADIENT = 0.01



Bosemop from Cambria Environmental Technology, Inc.

PREPARED BY

RRM
engineering contracting firm


Chevron Station 9-4612 3616 Son Leandro Street Ookland, California

GROUNDWATER ELEVATION CONTOUR MAP, NOVEMBER 6, 1998

FIGURE:

1

PROJECT: DACO4



EXPLANATION

MONITORING WELL

17.06 GROUNDWATER ELEVATION (FT, MSL)

18.00 - GROUNDWATER ELEVATION CONTOUR (FT, MSL)

APPROXIMATE GROUNDWATER FLOW DIRECTION;
APPROXIMATE GRADIENT = 0.02

Basemap from Cambria Environmental Technology, Inc.

PREPARED BY


PRINT

Engineering contracting firm

Chevron Station 9-4612 3616 San Leandro Street Oakland, California

GROUNDWATER ELEVATION CONTOUR MAP, JULY 29, 1998 FIGURE:

PROJECT: DACO4







Former Chevron Station 9-4612 3616 San Leandro Street Oakland, California

GROUNDWATER ELEVATION CONTOUR MAP, MAY 8, 1998

FIGURE: 1 PROJECT

PROJECT:






EXPLANATION

MONITORING WELL

20.76 GROUNDWATER ELEVATION (FT, MSL)

20.00 - GROUNDWATER ELEVATION CONTOUR (FT. MSL)

APPROXIMATE GROUNDWATER FLOW DIRECTION;
APPROXIMATE GRADIENT = 0.02



Bosemap from Cambria Environmental Technology, Inc.

PREPARED BY

RRM engineering contracting firm

Chevron Station 9-4612 3616 San Leandro Street Oakland, California

GROUNDWATER ELEVATION CONTOUR MAP, JANUARY 28, 1998 FIGURE:

1 ROJE

PROJECT: DACO4

EXPLANATION

◉ MONITORING WELL

16.85 GROUNDWATER ELEVATION (FT, MSL)

GROUNDWATER ELEVATION CONTOUR (FT, MSL) 16.50

APPROXIMATE GROUNDWATER FLOW DIRECTION;

APPROXIMATE GRADIENT = 0.01



Basemap from Combria Environmental Technology, Inc.

PREPARED BY


engineering contracting firm

Chevron Station 9-4612 3616 San Leondro Street Oakland, California

GROUNDWATER ELEVATION CONTOUR MAP, NOVEMBER 3, 1997

FIGURE:

1 **PROJECT:** DAC04



•

MONITORING WELL

17.43

GROUNDWATER ELEVATION (FT, MSL)

17.00-

GROUNDWATER ELEVATION CONTOUR (FT, MSL)

V

APPROXIMATE GROUNDWATER FLOW DIRECTION;

APPROXIMATE GRADIENT = 0.02



Basemop from Combria Environmental Technology, Inc.


PREPARED BY

RRM
engineering contracting firm

Chevron Station 9-4612 3616 San Leandro Street Oakland, California

GROUNDWATER ELEVATION CONTOUR MAP, JULY 22, 1997 FIGURE:

1 PROJECT: DACO4



<u>EXPLANATION</u>

MONITORING WELL

17.57 GROUNDWATER ELEVATION (FT, MSL)

18.00 - GROUNDWATER ELEVATION CONTOUR (FT, MSL)

APPROXIMATE GROUNDWATER FLOW DIRECTION; APPROXIMATE GRADIENT = 0.05

Besemap from Cambrie Environmental Technology, inc.



PREPARED BY


RRM

engineering contracting firm

Chevron Station 9-4612 3616 San Leandro Street Oakland, California

GROUNDWATER ELEVATION CONTOUR MAP, MAY 7, 1997

FIGURE: 1 PROJECT: DACO4




engineering contracting firm

Oakland, California

GROUNDWATER ELEVATION CONTOUR MAP, FEBRUARY 7, 1997

PROJECT: DAC04



Chevron Station 9-4612

Solution 10-4612


Chevron Station 9-4612

Solution 10-4612

FIGURE:

3616 San Leandro Street
Oakland, California

PROJECT:
DAC04




Chevron Station 9-4612

3616 San Leandro Street
Oakland, Colifornio

INC.

GROUNDWATER ELEVATION
CONTOUR MAP, AUGUST 1,1996

FIGURE:
1
PROJECT:
DAC04



CAMBRIA Environmental Technology, Inc.

Chevron Station 9-4612 3616 San Leandro Street Oakland, California


VCHEVRON9-4612/4612-QMLDWG

Base map from Groundwater Technology, Inc.


Ground Water Elevation
April 30, 1996

FIGURE

1



YCHEVRON9-4612/4612-QM.DWG





Oakland, California

YCHEVRON9-4612/4612-QMLDWG

1

December 19, 1995








Chevron Station 9-4612 3616 San Leandro Street Oakland, California


VCHEVRON/9-4612/4612-ONLDWG

Ground Water Elevation
May 12, 1995

FIGURE

1





③

22.00

1. CONTOURS REPRESENT APPROXIMATE ELEVATIONS ABOVE MEAN SEA LEVEL.

POTENTIOMETRIC SURFACE ELEVATION (FT)

POTENTIOMETRIC SURFACE CONTOUR

GROUNDWATER FLOW DIRECTION AND GRADIENT

Base map from Groundwater Technology, Inc.

AMBRIA Environmental Technology, Inc.


MONITORING WELL

Chevron Station 9-4612 3616 San Leandro Street Oakland, California

VCHEVROM9-4612/4612-OM.DWG

Ground Water Elevation February 1, 1995

FIGURE



MONITORING WELL

XXXX

POTENTIOMETRIC SURFACE ELEVATION (FT)

POTENTIOMETRIC SURFACE CONTOUR

GROUNDWATER FLOW DIRECTION AND GRADIENT

ELEVATIONS ABOVE MEAN SEA LEVEL.

Base map from Groundwater Technology, Inc.

Environmental Technology, Inc.


Chevron Station 9-4612 3616 San Leandro Street Oakland, California


VCHEVROM9-4612/4612-OM(4Q94).DWG

Ground Water Elevation

November 14, 1994

FIGURE









----- PR + MC X.XX PO

PROPERTY LINE

MONITORING WELL

POTENTIOMETRIC SURFACE ELEVATION (FT)

POTENTIOMETRIC SURFACE CONTOUR


GROUNDWATER FLOW DIRECTION





1. CONTOURS REPRESENT APPROXIMATE
ELEVATIONS ABOVE MEAN SEA LEVEL


No. 4422


POTENTIOMETRIC SURFACE MAP GROUNDWATER (8/26/94)TECHNOLOGY CLIENT: PE/RG . FILE: PROJECT NO .: 4099PSM, (1:30) 02010-4099 CHEVRON U.S.A. PRODUCTS CO. SERVICE STATION No. 9-4612 RCY. LOCATION: 3616 SAN LEANDRO STREET FIGURE: DATE: DES. DET. OAKLAND, CALIFORNIA SS SS 8/30/94





















T= Trigation
N=Industrial C/= Catholic Pro-Caction Sheet ___ of ____ 0= Dakland

N=Industrial

N=Industrial Owner's Address Well Location Drilled Owner PG+E 4801 Oakport, Oakland 18# 5/0 34# St. There are no well Cogged for subsection R Section 7 Coca Cola: 3001 Chapman O. State Shingle 880 Fruituals, O. NG N G Subsection H Same (3wells) other 90. U.S. Army Corps 650 Capital Mail, of Engineers Sacramento Fruitvale \mathfrak{L} Pestroye 1725 Park St _M_ 78 Wickland DEL 1765 Challenge, Sacto (Buells) Section 8 Trust for Public Land 82 200 St. SF PG+E 4801 On Rport, O. ---1601 39 to st 72 39 to + Footfill 75 375 NO E/12 73 Vernon Mc T. Craith 1990 N. CA. Blvd. Bart-Frutzale XX Station Walnut Creek 80 Postrojal I, E, S, 799 High O. Same 3750 E,145 90 ALOR Dis PoBox 484 8 analaem 499 High 6. ZZ Same I.E.S. 3800 Willamosa, 4280 Fretiell Just 89 Matil Oil Bustank (6 wells) 90 ROBOX 5004, Pan Panon 4265 Fortheld 2000 Crow Cyn Pe. (?) 4251 E 14 5 m Mocal Cop. 1939 Hanson # 605,0. 1066 47 th (3 wells) 89 Jo -0-0-Potouson Prip.

3616 Dan Franden Inventory of Wells Located in Township 25 Range 3W Section 7, County 20an Drilled Well Location Owner's Address Owner



engineering contracting firm

Oakland, California

GROUNDWATER ELEVATION CONTOUR MAP, NOVEMBER 3, 1997

PROJECT: DAC04

TABLE 1: SOIL VAPOR CHEMICAL ANALYTICAL DATA

Former Chevron Service Station #9-4612 3516 San Leandro Street

Oakland, California

Sample ID	Date Collected	Freon 12 µg/l ppbv	Methylene Chloride µg/l ppbv	Benzene µg/l ppbv	Tri- Chloroethene µg/l ppbv	Toluene µg/l ppbv	Total Xylenes µg/l ppbv	Styrene µg/l ppbv	1,2,4-Tri- methylbenzene µg/l ppbv	Acctone μg/l ppbv	2-propanol μg/l ppbv	Ethanol µg/l ppbv	Chloro- methane µg/l ppbv
VB-I	2/16/99	0.022	0.002 0.68^2	0.009 2.7 ²	0.004 0.67 ²	0.2 5.2	0.015 3.32 ²	0.005 1.2 ²	0.004 0.79 ²	0.215 89	0.924 370 ³	0.033 17	<0.001 <0.67
VB-2 ^t	2/16/99	0.024 4.8	<0.003 <0.76	0.006 1.7 ²	<0.004 <0.76	0.022 5.8	0.008 1.8 ²	<0.003 <0.76	<0.004 <0.76	0.029	0.095 38	0.036 19	0.002 1.1 ²
<u> </u>		Freon 12	Methylene Chloride ppm	Benzene ppm	Tri- Chloroethene ppm	Toluene ppm	Total Xylenes ppm	Styrene ppm	1,2,4-Tri- methylbenzene ppm	Acetone ppm	2-propanol ppm	Ethanol ppm	Chloro- methane ppm
	PEL	1,000	500	0.1	25	100	100	50	NA	250	200	NA	50

Explanation:

µg/l = micrograms/liter

ppbv = parts per billion by volume

μg/l = ppbv*molecular weight/24055

PELs = Permissable Exposure Limit

ppm = parts per million

NA = not available

All other compounds listed in Laboratory report were less than their respective reporting limit.

Analytical Laboratory

Air Toxics LTD (ELAP #1149)

Analytical Methods

TO-14 = EPA Method TO-14

² Estimated value.

³ Exceeds instrument calibration range.

	SURFACE EI					OGGE			
DEPTH TO GROUNDWATER 14 feet ATOD	BORING DIA	METER O	inch	nes	4	DATE DE	HLLED	2/10/8	8
DESCRIPTION AND CLASSIFIC	ATION			DEPTH	P, Ca	RATION TANCE YS/FT	TER (NT 1°-1	AY Sity CF	COM-
DESCRIPTION AND REMARKS	COLOR	CONSIST.	SOIL TYPE	(FEET)	FAVPLE	PINCHATION SISTANCE (BLOWS/F)	WATER CONTENT	DENSIT PCF	. 0 5
ILAY, homogeneous, less than 2% of sample is comprised of charred fragments	Dusky yellowish brown			- 1	. . !	-			
LAY, silty, charred fragments common Plasticity Data: depth 5'-6" L.L.= 55 P.I.= 37	Light olive gray	STIFF	CH	5 - 6 - 7 - 6 - 7 - 8 -	X	15*	15 15	111	
CLAY, sandy, mottled, increasing number of clasts with depth, transition zone	Dark yellowish brown			10-					
CONGLOMERATE, 20-30% of matrix is very coarse grain, subangular to rounded fragments of quartzite, chert and greenstone. < 5% of sample is comprised of ½-1½" dia. angular quartzite.		VERY STIFF		- 12 -	X	19*	12 ATOD	108	
CLAY, silty, fine sand with occasional clast, homogeneous.	Moderate yellowis brown	FIR:		15 - 16 - 17 - 18 - 19 - 19 -	X	5*	27	104	
strong gasoline odor	<u> </u>	STIFF		- 20 -	\triangleright	8*	23	100	
		EXF	۰ اور	4TOR	Y B	ORIN	G L	og .	



ROGERS/PACIFIC

Lot 18 & 19 man Leandro Street Oakland, Calif.

PROJECT NO

BATE

BORING - 4

DAILL AIG Continuous Flight Auger	SURFACE	LEVATION				LOGGE	Dey 1	KS	LOGGED BY KS				
DEPTH TO GROUNDWATER 14 feet ATOD	BORING DI	AMETER 6	inch	es	I	DATE D	PILLED	2/10/8	38				
DESCRIPTION AND CLASSIF	ICATION			DEPTH	5	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1							
DESCRIPTION AND REMARKS	COLOR	CONSIST,	SOIL TYPE		SAME	PENTANTION RESISTANCE (BLOWS/FT)	CONTENT	DRY DEMSIT	₩ 00				
LAY, sandy, silty, occasionally	Moderate yellowish brown			- 21 -	X	8*	. 23	100					
Bottom of borring 21.5 feet				- 22 - - 23 - - 24 -									
				- 25 - - 26 - - 27 -	-								
•				28 -		-							
		-		- 31 - - 32 - - 33 -	-								
				36			-		-				
				- 37 - - 38 - - 39 -		·							
			Ì	- 40									



ROGERS/PACIFIC

EXPLORATORY BORING LOG.

Lots 18 & 19 San Leandro Street Cakland, Calif.

PROJECT NO

DATE

BORING R-1 1000+

EPTH TO GROUNDWATER 14 feet ATOD	BORING DIA								
		WEIEN O	1110	1169				2/10,	
DESCRIPTION AND CLASSIFIC	CATION		,	DEPTH	SAVPLER	AA310 JAMEL	TEN NI (*.	ORY NSITÝ PCF	. E
DESCRIPTION AND REMARKS	COLOR	CONSIST.	SOIL TYPE	(FEET)	3	FINETANTION RESISTANCE (BLOWS/FT)	WATER CONT(NT (%)	DENSIT PCF	-MOD
AND, angular gravels, increases clay content with depth, fill material sieve data: % passing #200: 21%	Dark yellowis brown		sc	1 2 3 7 8 7 9 7 7 8 7 9 7 7 9 7 7 9 7 7 9 7 7 9 7 9			9		
LAY, silty, occasional angular clasts, 20-30% of sample is comprised of subangular to rounded pebble size clasts composed of guartzite sandstone and weathered feldspars	Dark yellowis brown	STIFF ish		12 - 13 14 15 1	X	10*	11 21	109	
transition into conglomerate population of clasts, clast size, consistency, and roundness increases with depth	. e	VERY STIFF		- 17	×	20*	15	110	



EXPLORATORY BORING LOG

Lot 18 & 19 San Leandro Street Oakland, Calif.

PROJECT NO

DATE - F

BORING

DAILL RIGCOntinuous Flight Auger	SURFACE	LEVATION		•		FOCCEC BA KZ					
DEPTH TO GROUNDWATER 14 feet ATOD	BORING OI	AMETER 6	inch	es		DATE D	AILLED	2/10/8	38		
DESCRIPTION AND CLASSIFIC	ATION			DEPTH	5	Triber /rrs	- E 2	7	,		
DESCRIPTION AND REMARKS	COLOR	CONSIST.	11		HURVS	PENETRATION RESISTANCE IBLOWS/FED	WATER CONTENT	DENSIT PCF	¥ Ö		
CONGLOMERATE, approximately 85% of sample is comprised of greater than 1/8" rounded clasts, composed of chert, quartzite, and greenstone Bottom of borring 26.5 feet	Moderate yellowish brown	VERY		21 - 22 - 23 - 24 - 25 - 26 - 27 - 28 - 30 - 31 - 32 - 33 - 34 - 35 - 36 - 37 - 38 - 39 - 39 - 39 - 39 - 39 - 39 - 39	X	20*	13	114			



ROGERS/PACIFIC

EXPLORATORY BORING LOG

Lots 18 & 19 San Leandro Street Oakland, Calif.

PAOJECT NO

DATE

BOAING

CLAY, sandy, abundant course grain size, rounded clasts of quartzite and greenstone. \frac{1}{2}" dia. clasts of angular greenstone, comprise 20% of a given sample CLAY, silty, slightly mottled, occasional charred fragments, homogeneous STIFF CH 1 2 12* 23 101 8 STIFF CH 3	DRILL FIG Continuous Flight Auger			LEVATION 3			╼╅┈╴	LOGGEL			
CLAY, sandy, abundant course grain size, rounded clasts of quartzite shown size, rounded clasts of quartzite and greenstone. \(\frac{1}{2} \) " dia. \(\frac{1}{2} \) " clasts of argular greenstone, comprise 20% of a given sample \(\frac{1}{2} \) " Moderate shown size, rounded clasts of quartzite shown size, rounded clasts	DEPTH TO GROUNDWATER 9 feet	BOR	NG OI	METER 6	inch	les		DATE DE	ILLED	2/10/88	
CLAY, sandy, abundant course grain size, rounded clasts of quantzite policy and greenstone. 2-2" dia. clasts of angular greenstone, comprise 20% of a given sample CLAY, slity, slightly mottled, occasional charred fragments, homogeneous CLAY, slity, slightly mottled, occasional charred fragments, homogeneous Brown black STIFF CH 1 1 12* 23 101 8 VERY STIFF 6 - 4 10* 22 104 10* 22 104	DESCRIPTION AND CLASSIFIC	ATIO	N			DEPTH	มีโล	BATION TAMEC IS/FT)	TER NT (*.)	ay SiTY SF	: ¥ §
CLAY, sandy, abundant course grain size, rounded clasts of quartzite proving and greenstone. 1-2" dia. clasts of angular greenstone, comprise 20% of a given sample CLAY, silty, slightly mottled, occasional charred fragments, homogeneous STIFF STIFF CH 1 1 12* 23 101 8 VERY STIFF 5	DESCRIPTION AND REMARKS	СО	LOR	CONSIST.	SOIL. TYPE	(FEET)	N.	PENET RESIS TOLOM	CONTE	DEN:	COM-
CLAY, sandy, abundant course grain size, rounded clasts of quartzite yellowish and greenstone. \(\frac{1}{2} \) 2" dia. Clay, silty, slightly mottled, occasional charred fragments, homogeneous STIFF STIFF STIFF STIFF 10 12* 12* 109 12* 110 12* 111 12* 13 14 14 14 15 16 16 16 17 18 10* 10* 10* 10* 10* 10* 10*				STIFF	CH	- 1					
CLAY, sailty, sandy CLAY, sandy, abundant course grain size, rounded clasts of quartzite yellowist brown STIFF 11 12* 17 113 CLAY, sandy, abundant course grain size, rounded clasts of quartzite yellowist brown Clasts of angular greenstone, comprise 20% of a given sample CLAY, silty, slightly mottled, occasional charred fragments, homogeneous Moderate yellowist brown STIFF 10 22 104				STIFF	CH	-	X	12*	23	101	84
CLAY, sandy, abundant course grain size, rounded clasts of quartzite yellowist and greenstone. ½-2" dia. clasts of angular greenstone, comprise 20% of a given sample CLAY, silty, slightly mottled, occasional charred fragments, homogeneous Moderate yellowist brown STIFF 11	CLAY, silty, sandy	yell	letwo	STIFF		5	X	18*	12	109	
CLAY, silty, slightly mottled, occasional charred fragments, homogeneous Moderate yellowis brown STIFF 10* 22 104	size, rounded clasts of quartzit and greenstone. $\frac{1}{2}$ -2" dia. clasts of angular greenstone,	ely e l l	OWIE			- 11 -	×	12*	17	113	
	occasional charred fragments,	yel	lowis			- 15 16 18	×	10*		104	
			·			- 50 -					



Lot 18 & 19 San Leandro Street Oakland, Calif.

PROJECT NO

DATE

BORING D .3

DRILL RIG Continuous Flight Auger	SURFACE ELEVATION 30 feet LOGGED BY KS										
DEFTH TO GROUNDWATER 9 feet ATOD		AMETER 6			}		2/10/	88			
DESCRIPTION AND CLASSIF	1				-		1 27 107				
DESCRIPTION AND CLASSIF	ILATION			DEPTH	SAWTICE ACTRALIC ICSISTANC ICOMS/FI	NER INTE	DRY MSIT	_ 2			
DESCRIPTION AND REMARKS	COLOR	CONSIST,	SOIL TYPE	(FEET)	SAMPLER PEMETRATION RESISTANCE IBLOWS/FF	WATER COHJENT 1°23	DRY DENSIT	* Ö			
CLAY, silty, sandy, subangular gravels, strong gasoline odor	Koderata yellowis brown	VERY STIFF		- 21 -	24*	17	112				
BOTTOM OF BORRING 21.5 FEET				- 23 24 25 26 27 28 30 31 31 31 31							
				40							




ROGERS/PACIFIC PROFESSIONAL ENGINEERING CONSULTANTS

EXPLORATORY BORING LOG

Lots 18 & 19 San Leandro Street Cakland, Calif.

PROJECT NO	DATE	1
	V-15	BOAING
		1 GOUING



Boring Log and Well Construction Details - Well VH-1

3614 San Leandro St. Oakland, CA



Monitoring Well MW-2

Project <u>C</u>	hev/3616	San Lear	dro Stree	<u>t</u>	_ 0	wher <u>Chevron U.S.A. Products Co.</u>	See Site Map For Boring Location
Location .	Oakland, (California		Project	t No.	<u>02020 2892</u> Date drilled <u>02/01/93</u>	
Surface E	lev. <u>28.80</u>	<u>77t.</u> To	tal Hole O	epth 🕹	20.5	ft. Diameter 8.5 in.	COMMENTS:
Top of Ca	sing <u>28.5</u>	<u>77.</u> Wa	ter Level	Initial .	0.0 1	t. Static 03/26/93 7.62 ft.	The well was set at approximately
Screen: D	118 <u>4 " 1.</u> 12 2 in	Le	ngth <u>15 /t</u> noth <i>5 ft</i>	•		Type/Size <u>0.020 in.</u> Type <u>SCH 40 PVC</u>	20.5 feet below grade, the soil cuttings were placed on plastic
Casing: U	k Material	#3 sand	ngur vit		Ri	g/Core Type <u>Mobile B-53/Split Spoon</u>	and was left on site until it could be analyzed and disposed
Drilling Co	mpany <u>K</u> v	rilhaug Wa	tt <u>Drilling</u>	. Meth	od £	<i>follow Stem Auger</i> Permit # 92366	of properly.
Driller Ro	d Furlow				L	og By S.C. Hurley	}
Checked	By <u>David</u>	Kleesatt	el	Licer	nse N	10. RG# 5136 () 3 {) () Carre	
£a	Well	_ €	sample ID low Count/ Recovery	ž D	Class	Descripti	on
Depth (ft.)	P P P P	PIO (ppm)	d S	raphí Log	ایما	(Color, Texture, S	Structure)
	ပ်		X B S	Gr	SS.	Trace < 10%, Little 10% to 20%, Some	20% to 35%, And 35% to 50%
2-							
- 0 -				777		Surface material-grass and soil	
					1	Brown silty CLAY	
[1 4 14					Significantly dent	
2 -	1,4 1,4				1		
				<u> </u>	1		
- 4			!				
┝╶┤	∦ 	146	35 X		ML	. Light brown clayey SILT (10% silt, sli	ghtly moist)
- 6 -			50				
-						Static water level - 3/26/93	
8 -					1	Encountered groundwater at 12:30PM	02/01/93
} -							
 10 -	[: <u>≣</u> ::	9.1	20		1		
-	∦∶ ≣ ∶		23 🛭		CL	·	
- 12 -	∥: ≣ :				1		
[]	 				1	<u>'</u>	
[,,]	∦ :: ≣[::				7		
- 14 -	∦: ≣ ⊹	2800	22 [1		
<u> </u>	<u> </u>	2000	28	inini	rl	Greenish silty SAND (about 50% sand (saturated, strong hydrocarbon odo	g, adout 35% siit, adout 15% ciay r)
- 16 -	¶: ≣ :		45			tagen area, arrong hydrocarbon add	
} .	#: ≣ [::					:	
- 18 -	∦:l≣l:				SM	·	
[]	JE ≣ :						
• []]: ≣ :	1050	25			Light brown sandy SILT (10% clay, s	aturated, slight petroleum
- 20 -	. تعجوز	1	48		膨	hydrocarbon odor)	
·						End of boring at 20.5 feet. Installed	groundwater monitoring well.
- 22 -	1					·	
} ·	1						
- 24 -	1						
		03		**			Page: 1 of 1



Monitoring Well MW-3

	TEC	HNOLO	GY			!	
- · · Cha	./281B :	San Lean	dra SI		Ωw	mer Chevron U.S.A. Products Co.	See Site Map For Boring Location
Project <u>Chev</u>	kland, (California	5,05(. F	rolect	_ U*	02020 2892 Date drilled 02/01/93	For Boring Location
Curinos Elev	28.30) ft. Tot	al Hole De	enth 🚄	<u> 20.5 1</u>	t. Diameter <u>8.5 in.</u>	COMMENTS:
Top of Casin	g <u>27.5</u>	<u>lft.</u> Wat	er Level I	initial .	<u>8.5 f</u>	t. Static <u>03/26/93 7.18 ft.</u>	The well wa set at approximately
Screen: Dia	<u>2 in.</u> 2 in	Ler	igth <u>15 16.</u> Nath <i>5 ft.</i>			Type/Size <u>0.020 in.</u> Type <u>SCH 40 PVC</u>	20.5 feet below grade. The soil cuttionswere placed on plastic
Citize Dock b	istorial	#3 sand			_ Ric	a/Care Type Mobile 6-33/30iii 3000ii	and was left on site until it could be analyzed and disposed
Drilling Comp	any <u>Kv</u>	ilhaug Wei	I Drilling	Meth	od <u>H</u>	ollow Stem Auger Permit # 32303	of properly.
Oriller Rod F	<i>David</i>	Kieesatte		Licer	Lo ise N	og By <u>S.C. Hurley</u> o <u>RG# 5136</u> Did Kleath	7
					5.5		
£3 .	Well	PID (ppm)	Sample ID Iow Count/ Recovery	일	Ses	Descript	
Depth (ft.)	¥è ∥	<u> </u>	E * S	Graphic	SCS	. (Color, Texture, S Trace < 10%, Little 10% to 20%, Some	Structure) 5 20% to 35%, And 35% to 50%
	ပိ		พื≅ห		S	Trace Cluz, Little lox to 20%, Some	
-2-							
1 1	İ		i				
L 0 -	, ,			777		Surface material— grass and soil	
The M	 {1				1		
- 2 - 4	[7]						
\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \					CL	Brown silty CLAY (moist)	
7 7						Brown clayey SILT (10% fine sand, s	slightly maist)
		12.3	35 50			Brown clayey are those time server	
6 -	¦≣I∷		_		ML	Static level - 3/26/93	·
		- - -		000	3	Static level - 3/20/93	
- 8 -	≣ ∶			000		¥ Encountered groundwater at 9:30Al	1 02/01/93
	: ≣ :		∥	000	LEI		And about 20% course sand
<u> </u>	≣ ∶	8.6	38 50	1000	GP C	Brown sandy GRAVEL (about 75% g about 5% silt, water saturated, no h	ydrocarbon odor).
			30	500	곘		
<u> </u> 12	: ≣ :	. .		500	2		
1	: <u> ≣</u> :	· .			$: \Gamma$		
L 14 -	: ≣ :	•	1		:		•
	:l≣I:	186	25 F	1: •		Brown silty SAND (50% coarse sand	d, 30% fine sand, 20% silt.
L 16 -	: ≣ :	:∭	45			saturated)	
	: <u>≣</u> :	•			∴¦Sh	:	
18 -	: ≣ :	-		 ::: :	$: \parallel$		
	: ≣ :	•			∷∥		
T 1	: ≣ :	1	22	∃ ::		No recovery	
├ 20 -		4	25 45		:	End of boring at 20.5 feet. Installe	ed groundwater monitoring well.
							-
- 22 -							
1 2/ 1		III .	11	11		li .	•



Monitoring Well MW-4

Location 3616 San I Surface Elev. 27.68 Top of Casing 27.2 Screen: Dia 2 in. Casing: Dia 2 in. Fill Material Neat C Drill Co. SES, Inc. Driller Morris Peter: Checked By Ed Sir	tt. 7 ft. ement	o Street, Oa Total Hole D Water Level Length 13 ft Length 7 ft. Metho Log By Bria	epth 21.5 Initial 15 od Hollow on McAloon License	Rig/Cor Stem A	ouger/PID Date 08/15/95 Permit # 95503 6#4422	See Site Map For Boring Location COMMENTS:
Depth (ft.) Well Completion	PIO (mod)	Sample ID Blow Count/ x Recovery	Graphic Log	Tra	Descrip (Color, Texture, ce < 10%, Little 10% to 20%, Som	Structure)
- 2 - 0 - 2 - 4 - 6 - 10 - 12 - 12 - 12 - 12 - 12 - 12 - 12	0 0	MW-4 12 -6.5'	F	CL L/SC	8" concrete. Silty CLAY (15,85): brown, dry. Pebbly sandy CLAY (20,30,50): b Static water, 08/15/95, 1400 hr Pebbly sandy CLAY (10,40,50): t Pebbly silty clayey SAND (15,25)	s. orown, dry, no hydrocarbon odor.
- 14 - - 16 18 20 - -			7 4 7	sc ¥	hydrocarbon odor. Encountered water (driller's co	all), 08/15/95, 1255 hrs. It, slight hydrocarbon odor. 0,20,50): brown with orange and gra



Soil Boring SB-1

Project <u>Chevron - O</u> a	akland	Owner <u>Chevron USA Products Company</u> and, CA Proj. No. <u>02020 4530</u>	See Site Map For Boring Location
Surface Elev Top of Casing Screen: Dia Casing: Dia Fill Material Neal Cer Drill Co. SES, Inc.	Total Hole Dep Water Level Ini Length Length Method	1	
Checked By Ed Simo	onist	icense No. <u>RG#4422</u> EL	
Depth (ft.) PID (ppm)	Blow Count/ x Recovery Graphic Log USCS Class.	Descript (Color, Texture, Trace < 10%, Little 10% to 20%, Som	Structure)
2- - 0 - - 2 - - 4 - - 6 - - 8 - - 10 - - 12 - - 14 -	5. 5. 5.	Clayey silty pebbly SAND (10,10,20,60): be grading to clayey sandy pebbly (up to 3 dry to damp, no hydrocarbon odor.	down no hydrocarbon odor
- 16 - SE		Encountered water (driller's call), 08/15. Pebbly clayey SAND (10,30,60): brown wicasts, damp to moist, no hydrocarbon od Static water, 08/15/95, 0953 hrs. Sandy silty CLAY (10,30,60): light brown wet, slight hydrocarbon odor.	th 5% gray staining along rootlet or.
- 20 - 3.75 55 - 22 - - 24 -	21.5	End of boring. Backfilled with grout 08/	15/95.

