

Re 243

June 15, 2004

TRC Project No. 42016501

Don Hwang Alameda County Health Services 1131 Harbor Bay Parkway Alameda, CA 94502-6577

RE:

Quarterly Status Report - First Quarter 2004

76 Service Station #0018, 6201 Claremont Avenue, Oakland, California

Alameda County

Dear Mr. Hwang:

On behalf of ConocoPhillips Company (ConocoPhillips), TRC is submitting the First Quarter 2004 quarterly status report for the subject site, shown on the attached Figure 3.

PREVIOUS ASSESSMENTS

The subject site is an active service station located on the northern corner of the intersection of Claremont and College Avenues in Oakland, California. The nearest surface water is Claremont Creek, approximately 0.1 mile northeast of the site.

March 1997: Karpealian Engineering Inc. (KEI) collected soil and grab groundwater samples during underground storage tank (UST) and product line replacement activities. A groundwater sample collected from the former gasoline UST excavation contained 6,100 parts per billion (ppb) total petroleum hydrocarbons as gasoline and 54 ppb benzene.

March 1998: Tosco was issued a Notice of Responsibility by the Alameda County Health Care Services Agency.

December 2000: Gettler-Ryan Inc. installed three groundwater monitoring wells to depths of 30 to 30.5 feet below ground surface (bgs). Groundwater samples contained low maximum concentrations of total petroleum hydrocarbons calculated as gasoline, benzene, and methyl tertiary butyl ether (MTBE).

October 2003: Site environmental consulting responsibilities were transferred to TRC.

SENSITIVE RECEPTORS

Surface water Claremont Creek is located 0.1 miles northeast of the site. A sensitive receptor survey has not been performed for this site.

QSR – Fourth Quarter 2003 76 Service Station #0018, Oakland, California June 15, 2004 Page 2

MONITORING AND SAMPLING

Three wells are currently monitored quarterly. The groundwater gradient and flow direction were 0.012 foot/foot to the southwest. The groundwater gradient and flow direction were generally consistent with recent historical data.

CHARACTERIZATION STATUS

Total purgeable petroleum hydrocarbons (TPPH) were detected in monitoring well MW-1 at a concentration of 520 micrograms per liter ($\mu g/l$). TPPH was not detected above the reporting limit in the other wells sampled this quarter. These levels were consistent with recent historical data.

Benzene was detected in monitoring well MW-2 at a concentration of 0.5 μ g/l. These levels were generally consistent with recent historical data.

MTBE was detected in monitoring well MW-1 at a concentration of 44 μ g/l. MTBE was not detected above the reporting limit in the other wells sampled this quarter. These levels were generally consistent with recent historical data.

REMEDIATION STATUS

Remediation is not currently being conducted at the site.

RECENT CORRESPONDENCE

No correspondence this quarter.

CURRENT QUARTER ACTIVITIES

January 29, 2004: TRC performed groundwater monitoring and sampling. Wastewater generated from well purging and equipment cleaning was stored at TRC's groundwater monitoring facility in Concord, California, and transported by Onyx to the ConocoPhillips Refinery in Rodeo, California, for treatment and disposal.

NEXT QUARTER ACTIVITIES

Await agency directives for additional assessment work, if any.

Continue quarterly monitoring and sampling to assess plume stability and concentration trends at key wells.



QSR – Fourth Quarter 2003 76 Service Station #0018, Oakland, California June 15, 2004 Page 3

If you have any questions regarding this report, please call Roger Batra at (925) 688-2466.

Sincerely,

TRC

Roger Batra

Senior Project Manager


Barbara Moed, R.G. Senior Project Geologist

Attachments:

Figure 3 – Dissolved Phase Hydrocarbon Concentrations Map, January 29, 2004, from First Quarter 2004 Fluid Level Monitoring and Sampling Report, dated March 10, 2004 by TRC.

cc: Thomas Kosel, ConocoPhillips (hard copy and electronic upload)

No. 7529



NOTES:

TPPH = total purgeable petroleum hydrocarbons.

B = benzene. MTBE = methyl tertiary butyl ether.

µg/l = micrograms per liter. ND = not detected

at limit indicated on official laboratory report.

UST = underground storage tank. Results

abtained using EPA Method 8260B.



LEGEND

No.	み
µg/I	4
ا/وپر	
ug/l	
	hā\ hā\

Monitoring Well with
Dissolved—Phase
Hydrocarbon
Concentrations
(µg/l)

DISSOLVED-PHASE HYDROCARBON CONCENTRATIONS MAP January 29, 2004

76 Station 0018 6201 Claremont Avenue Oakland, California



June 4, 2004

ConocoPhillips Company 76 Broadway Sacramento, CA 95818

ATTN:

MR. THOMAS H. KOSEL

SITE:

76 STATION 0018

6201 CLAREMONT AVENUE OAKLAND, CALIFORNIA

RE:

QUARTERLY MONITORING REPORT

APRIL THROUGH JUNE 2004

Dear Mr. Kosel:

Please find enclosed our Quarterly Monitoring Report for 76 Station 0018, located at 6201 Claremont Avenue, Oakland, California. If you have any questions regarding this report, please call us at (949) 753-0101.

Sincerely,

TRC

Anju Farfan 🗤

QMS Operations Manager

CC: Mr. Don Huang, Alameda County Health Care Service Division

Barbara Moed, TRC

Enclosures 20-0400/0018R03.QMS



QUARTERLY MONITORING REPORT APRIL THROUGH JUNE 2004

76 Station 0018 6201 Claremont Avenue Oakland, California

Prepared For:

Mr. Thomas H. Kosel CONOCOPHILLIPS COMPANY 76 Broadway Sacramento, California 95818

By:

Senior Project Geologist, Irvine Operations June 4, 2004

QUARTERLY MONITORING REPORT

	LIST OF ATTACHMENTS
Summary Sheet	Summary of Gauging and Sampling Activities
Tables	Table Key Table 1: Summary of Groundwater Levels and Chemical Analysis Results Table 2: Historic Groundwater Levels and Chemical Analysis Results Table 3: Summary of Additional Chemical Analysis Results
Figures	Figure 1: Vicinity Map Figure 2: Groundwater Elevation Contour Map Figure 3: Dissolved-Phase TPPH Concentration Map Figure 4: Dissolved-Phase Benzene Concentration Map Figure 5: Dissolved-Phase MTBE Concentration Map
Graphs	Benzene Concentrations vs. Time Hydrographs
Field Activities	General Field Procedures Groundwater Sampling Field Notes
Laboratory Reports	Official Laboratory Reports Quality Control Reports Chain of Custody Records
Statements	Purge Water Transport and Disposal Limitations

Summary of Gauging and Sampling Activities April 2004 through June 2004 76 Station 0018 6201 Claremont Boulevard Oakland, CA

Site:	76 Station 6201 Claremont Boulevard Oakland, CA
Project Coordinator/Phone Number:	Thomas H. Kosel/916-558-7666
Groundwater wells onsite:	3
Groundwater wells offsite:	0
ctivity:	
Sampling consultant:	TRC
Date(s) sampled:	5/7/2004
Groundwater wells gauged:	3
Groundwater wells sampled:	3
Purging method:	submersible pump
Treatment/disposal method during sampling event:	Onyx/Rodeo Unit 100
Free product pumpouts other than sampling event:	No
Treatment/Disposal method during free product pumpouts:	N/A
drogeology:	
Minimum depth to groundwater (feet bgs):	16.74
Maximum depth to groundwater (feet bgs):	17.79
Average groundwater elevation (feet relative to mean sea level):	192.03
Average change in groundwater elevations since previous event (feet):	0.90
Groundwater gradient and flow direction:	0.01 ft/ft, Southwest
Previous gradient and/or flow direction (and date):	0.012 ft/ft, Southwest (1/29/2004)
water Condition (Benzene Maximum Contaminant Level [MCL] = 1.0 μ	g/i)
Wells with benzene concentrations below MCL:	3
Wells with benzene concentrations at or above MCL:	0
Minimum benzene concentration (µg/l):	ND
Maximum benzene concentration (µg/l):	ND
Minimum MTBE concentration (µg/l):	ND
Maximum MTBE concentration (µg/l):	25
·· - ·	
	ND
Minimum TPPH concentration (μg/t):	100 (BAIN) 11
Maximum TPPH concentration (µg/t): Maximum TPPH concentration (µg/t):	180 (MW-1)
	0
Maximum TPPH concentration (μg/l):	, ,

This report presents the results of groundwater monitoring and sampling activities performed by TRC. Please contact the primary consultant for other specific information on this site.

TABLE KEY

ABBREVIATIONS / SYMBOLS

LPH = liquid-phase hydrocarbons

☐g/l = micrograms per liter mg/l = milligrams per liter

ND = not detected at or above laboratory detection limit

DTSC = Department of Toxic Substances Control

N/A = not applicable

Trace = less than 0.01 foot of LPH in well

USTs = underground storage tanks

-- = not analyzed, measured, or collected

TPH-G = total petroleum hydrocarbons with gasoline distinction BTEX = benzene, toluene, ethylbenzene, and total xylenes

TPH-D = total petroleum hydrocarbons with diesel distinction

TRPH = total recoverable petroleum hydrocarbons

MTBE = methyl tertiary butyl ether TAME = tertiary amyl methyl ether ETBE = ethyl tertiary butyl ether

DIPE = di-isopropyl ether
TBA = tertiary butyl alcohol
1,1-DCA = 1,1-Dichloroethane
1,2-DCA = 1,2-Dichloroethane
1,1-DCE = 1,1-Dichloroethene

1,2-DCE = cis- and trans-1,2-Dichloroethene

PCE = tetrachloroethenc TCA = trichloroethane TCE = trichloroethene

PCB = polychlorinated biphenyls

TPPH = total purgeable petroleum hydrocarbons

NOTES

Elevations are in feet above mean sea level.

Groundwater elevation for wells with LPH is calculated as follows:

Surface elevation – depth to water + (0.75 x LPH thickness).

Concentration Graphs have been modified to plot non-detect results at the reporting limit stated in the official laboratory report. All non-detect results prior to the Second Quarter 2000 were plotted at 0.1 \Box g/l for graphical display.

J = estimated concentration, value is between the Method Detection Limit (MDL) and the Practical Quantitation Limit (PQL)

REFERENCE

TRC began groundwater monitoring and sampling activities in October 2003. Historical data for 76 Station 0018 was provided by Gettler-Ryan Inc., Dublin, California, in an excel table received in September 2003.

Table 1
SUMMARY OF GROUNDWATER LEVELS AND CHEMICAL ANALYSIS RESULTS
May 7, 2004
76 Station 0018

Date Sampled	TOC Elevation	Depth to Water	LPH Thickness		Change in Elevation	TPH-G	TPPH 8260B	Benzene	Toluenè	Ethyl- benzene	Total Xylenes	MTBE 8021B	MTBE 8260B	Comments
	(feet)	(feet)	(feet)	(feet)	(feet)	(μg/l)	(µg/l)	(µg/l)	(µg/1)	(μg/l)	(µg/l)	(µg/l)	(µg/l)	
MW-1 5/7/2004	4 208.15	,	nterval in fe	et: 10.0-3 0 191.41	0. 0) 0.77		180	ND<0.50	ND<0.50	ND<0.50	ND<1.0		25	
MW-2 5/7/2004	4 210.27	•	nterval in fe	et: 10.0-3 0 192.48	0. 0) 0.94	'	ND<50	ND<0.50	ND<0.50	ND<0.50	ND<1.0		ND<0.50	
MW-3 5/7/2004	4 208.98	`	nterval in fe	et: 10.0-30 192.19).0) 1.00		ND<50	ND<0.50	ND<0.50	ND<0.50	ND<1.0		0.55	

Table 2
HISTORIC GROUNDWATER LEVELS AND CHEMICAL ANALYSIS RESULTS
August 2000 Through May 2004

76 Station 0018

								, o Static	n coro					
Date Sampled	TOC Elevation	Depth to Water	LPH Thickness	Ground- water Elevation	Change in Elevation	TPH-G	TPPH 8260B	Benzene	Toluene	Ethyl- benzene	Total Xylenes	MTBE 8021B	MTBE 8260B	Comments
	(feet)	(feet)	(feet)	(feet)	(feet)	(μg/l)	(μ <u>g</u> /l)	(µg/l)	(μg/l)	(μg/l)	(μg/l)	(μg/l)	(μg/l)	
MW-1	(Screen Int	erval in feet	t: 10.0-30.0))									
2/9/200	208.1	5 20.16	0.00	187.99		330	••	1.3	ND	1.0	4.6	140	150	
5/11/20	01 208.13	5 17.68	0.00	190.47	2.48	1250		ND	ND	ND	ND	145	122	
8/10/20	01 208.13	5 20.38	0.00	187.77	-2.70	580		ND<0.50	ND<0.50	ND<0.50	ND<0.50	110	150	
11/7/20	01 208.1	22.68	0.00	185.47	-2.30	250		ND<0.50	1.5	ND<0.50	ND<0.50	120	100	
2/6/200	208.13	5 16.20	0.00	191.95	6.48	790		ND<2.5	12	8.8	ND<2.5	90	72	
5/8/200	208.15	5 17.54	0.00	190.61	-1.34	890		ND<2.5	ND<2.5	ND<2.5	ND<2.5	87	81	
8/9/200	208.15	5 20.21	0.00	187.94	-2 .67	450		ND<0.50	ND<0.50	ND<0.50	ND<1.0	100	100	
11/29/20	002 208.15	5 22.33	0.00	185.82	-2.12	110		ND<0.50	ND<0.50	ND<0.50	ND<1.0	72	72	
2/3/200	3 208.15	16.41	0.00	191.74	5.92	540		ND<0.50	ND<0.50	ND<0.50	ND<1.0	40	40	
5/5/200	3 208.15	5 16.09	0.00	192.06	0.32	670		ND<2.5	ND<2.5	ND<2.5	ND<5.0	57	57	
9/4/200	3 208.15	3 21.46	0.00	186.69	-5.37									No analysis; past holding time
11/13/20	003 208.13	5 21.52	0.00	186.63	-0.06		97	ND<0.50	5.0	0.82	3.5	**	29	
1/29/20	04 208.13	5 17.51	0.00	190.64	4.01		520	ND<0.50	ND<0.50	ND<0.50	ND<1.0		44	
5/7/200	04 208.15	5 16.74	0.00	191.41	0.77		180	ND<0.50	ND<0.50	ND<0.50	ND<1.0		25	
MW-2	(Screen Into	erval in feet	: 10.0-30.0)									
8/24/20	00 210.2	7 19.69	0.00	190.58		ND		ND	ND	ND	ND	ND	ND	
11/16/20	000 210.2	7 21.61	0.00	188.66	-1.92	ND		ND	ND	ND	ND	ND	ND	
2/9/200	210.2	7 21,52	0.00	188.75	0.09	ND		ND	ND	ND	ND	ND	ND	
5/11/20	01 210.2	7 18.76	0.00	191.51	2.76	ND		ND	ND	ND	ND	ND	ND	
8/10/20	01 210.2	7 21.65	0.00	188.62	-2.89	ND<50		ND<0.50	ND<0.50	ND<0.50	ND<0.50	ND<5.0	ND<2.0	
11/7/20	01 210.2	7 24.25	0.00	186.02	-2.60	ND<50			ND<0.50			ND<5.0	ND<1.0	
2/6/200	210.2	7 18.22	0.00	192.05	6.03	ND<50		ND<0.50	ND<0.50	ND<0.50	ND<0.50	ND<2.5		
5/8/200	210.2	7 18.63	0.00	191.64	-0.41	ND<50		ND<0.50	ND<0.50	ND<0.50	ND<0.50	ND<5.0		
8/9/200	210.2	7 21.53	0.00	188.74	-2.90	ND<50		ND<0.50	ND<0.50	ND<0.50	ND<1.0	ND<2.0	ND<2.0	
11/29/20	002 210.2	7 23.73	0.00	186.54	-2.20	ND<50		ND<0.50	ND<0.50	ND<0.50	ND<1.0	ND<2.0	ND<2.0	

Page 1 of 2


Date Sampled	TOC Elevation	Depth to Water	LPH Thickness	Ground- water Elevation	Change in Elevation	TPH-G	TPPH 8260B	Benzene	Toluene	Ethyl- benzene	Total Xylenes	MTBE 8021B	MTBE 8260B	Comments
	(feet)	(feet)	(feet)	(feet)	(feet)	(μg/l)	(μg/l)	(µg/l)	(μg/l)	(μg/l)	(μg/l)	(μg/l)	(μg/l)	
MW-2	continued													
2/3/200	3 210.27	17.43	0.00	192.84	6.30	ND<50		ND<0.50	ND<0.50	ND<0.50	ND<1.0	ND<2.0	ND<2.0	
5/5/200	3 210.27	17.15	0.00	193.12	0.28	ND<50		ND<0.50	ND<0.50	ND<0.50	ND<1.0	ND<2.0	ND<2.0	
9/4/200	3 210.27	22.75	0.00	187.52	-5.60							**		No analysis; past holding time
11/13/20	03 210.27	23.02	0.00	187.25	-0.27		ND<50	ND<0.50	ND<0.50	ND<0.50	ND<1.0		ND<2.0	
1/29/200	04 210.27	18.73	0.00	191.54	4.29		ND<50	0.50	ND<0.50	ND<0.50	ND<1.0		ND<2.0	
5/7/200	4 210.27	17.79	0.00	192.48	0.94		ND<50	ND<0.50	ND<0.50	ND<0.50	ND<1.0		ND<0.50	
MW-3	(9	Screen Inte	erval in feet	: 10.0-30.0)	•								
8/24/200	00 208.98	18.68	0.00	190.30		ND		ND	ND	ND	ND	4.7/2.32	2.3	
11/16/20	00 208.98	20.56	0.00	188.42	-1.88	ND		ND	ND	ND	ND	ND	ND	
2/9/200	1 208.98	20.45	0.00	188.53	0.11	ND		ND	ND	ND	ND	ND	ND	
5/11/200	208.98	17.75	0.00	191.23	2.70	ND		ND	ND	ND	ND	ND	ND	
8/10/200	1 208.98	20.70	0.00	188.28	-2.95	ND<50		ND<0.50	ND<0.50	ND<0.50	ND<0.50	ND<5.0	ND<2.0	
11/7/200	1 208.98	23.02	0.00	185.96	-2.32	ND<50		ND<0.50	ND<0.50	ND<0.50	ND<0.50	ND<5.0	1.5	
2/6/200	2 208.98	17.19	0.00	191.79	5.83	ND<50		ND<0.50	ND<0.50	ND<0.50	ND<0.50	ND<2.5		
5/8/200	2 208.98	17.59	0.00	191.39	-0.40	ND<50	-	ND<0.50	ND<0.50	ND<0.50	ND<0.50	ND<5.0		
8/9/200	2 208.98	20.48	0.00	188.50	-2.89	ND<50		ND<0.50	ND<0.50	ND<0.50	ND<1.0	ND<2.0	ND<2.0	
11/29/20	02 208.98	22.64	0.00	186.34	-2.16	ND<50		ND<0.50	ND<0.50	ND<0.50	ND<1.0	ND<2.0	ND<2.0	
2/3/200	3 208.98	16.46	0.00	192,52	6.18	ND<50	5 H	ND<0.50	ND<0.50	ND<0.50	ND<1.0	ND<2.0	ND<2.0	
5/5/200	3 208.98	16.16	0.00	192.82	0.30	ND<50		ND<0.50	ND<0.50	ND<0.50	ND<1.0	2.6	2.6	
9/4/200	3 208.98	21.71	0.00	187.27	-5.55						**			No analysis; past holding time
11/13/20	03 208.98	21.93	0.00	187.05	-0.22		ND<50	ND<0.50	ND<0.50	ND<0.50	ND<1.0		ND<2.0	
1/29/200	04 208.98	17.79	0.00	191.19	4.14	-	ND<50	ND<0.50	ND<0.50	ND<0.50	ND<1.0		ND<2.0	
5/7/200	4 208.98	16.79	0.00	192.19	1.00		ND<50	ND<0.50	ND<0.50	ND<0.50	ND<1.0		0.55	

Table 3
SUMMARY OF ADDITIONAL CHEMICAL ANALYSIS RESULTS
76 Station 0018

Date Sampled	EDC	EDB	TAME 8260B	TBA 8260B	DIPE 8260B	ETBE 82 60B	Ethanol 8015B	Ethanol 8260B
	(μg/l)	(μg/l)	(µg/l)	(μg/l)	(µg/l)	(μg/l)	(mg/l)	(µg/l)
MW-1								
2/9/2001	ND	ND	ND	ND	ND	ND		ND
5/11/2001	ND	ND	ND	ND	ND	ND	**	ND
8/10/2001	ND<2.0	ND<2.0	ND<2.0	ND<100	ND<2.0	ND<2.0		ND<1,000
11/7/2001	ND<1.0	ND<1.0	ND<1.0	ND<20	ND<1.0	ND<1.0		ND<500
2/6/2002	ND<2.0	ND<2.0	ND<2.0	ND<100	ND<2.0	ND<2.0		ND<500
5/8/2002	ND<2.0	ND<2.0	ND<2.0	ND<100	ND<2.0	ND<2.0		ND<500
8/9/2002	ND<2.0	ND<2.0	ND<2.0	ND<100	ND<2.0	ND<2.0		ND<500
11/29/2002	ND<2.0	ND<2.0	ND<2.0	ND<100	ND<2.0	ND<2.0		ND<500
2/3/2003	ND<2.0	ND<2.0	ND<2.0	ND<100	ND<2.0	ND<2.0		ND<500
5/5/2003	ND<10	ND<10	ND<10	ND<500	ND<10	ND<10		ND<2,500
11/13/2003	ND<2.0	ND<2.0	ND<2.0	ND<100	ND<2.0	ND<2.0		ND<500
1/29/2004	ND<2.0	ND<2.0	ND<2.0	ND<100	ND<2.0	ND<2.0		ND<500
5/7/2004	ND<0.50	ND<0.50	ND<0.50	ND<5.0	ND<1.0	ND<0.50		ND<50
MW-2								
8/24/2000			ND	ND	ND	ND		ND
11/16/2000			ND	ND	ND	ND		ND
2/9/2001	ND	ND	ND	ND	ND	ND		ND
5/11/2001	ND	ND	ND	ND	ND	ND		ND
8/10/2001	ND<2.0	ND<2.0	ND<2.0	ND<100	ND<2.0	ND<2.0		ND<1,000
11/7/2001	ND<1.0	ND<1.0	ND<1.0	ND<20	ND<1.0	ND<1.0		ND<500
8/9/2002				+-				
11/29/2002								
2/3/2003				•				
5/5/2003								
11/13/2003								ND<500
1/29/2004								ND<500

Page 1 of 2

Date Sampled	EDC	EDB	TAME 8260B	TBA 8260B	DIPE 8260B	ETBE 8260B	Ethanol 8015B	Ethanol 8260B
	(μg/l)	(µg/l)	(µg/l)	(μg/l)	(μg/l)	(μg/l)	(mg/l)	(μg/l)
MW-2 c 5/7/2004	ontinued 	**				4-		ND<50
MW-3 8/24/2000	~-		ND	ND	ND	ND	ND	
11/16/2000			ND	ND	ND	ND	ND	
2/9/2001			ND	ND	ND	ND	ND	
5/11/2001			ND	ND	ND	ND	ND	
8/10/2001			ND<2.0	ND<100	ND<2.0	ND<2.0	ND<1,000	
11/7/2001			ND<1.0	ND<20	ND<1.0	ND<1.0	ND<500	
8/9/2002	ND	ND	••					
11/29/2002	ND	ND						
2/3/2003	ND<2.0	ND<2.0						
5/5/2003	ND<1.0	ND<1.0	45					
11/13/2003				••				ND<500
1/29/2004			••					ND<500
5/7/2004								ND<50





SOURCE:

United States Geological Survey 7.5 Minute Topographic Map: Oakland East & Oakland West Quadrangles







SCALE 1: 24,000



VICINITY MAP

76 Station 0018 6201 Claremont Avenue Oakland, California





CLAREMONT AVENUE



NOTES:

Contour lines are interpretive and based on laboratory analysis results of groundwater samples. TPPH = total purgeable petroleum hydrocarbons. pg/l = micrograms per liter. ND = not detected at limit indicated on official laboratory report. UST = underground storage tank. Results obtained using EPA Method 8260B.



LEGEND


MW-3

→ Monitoring Well with
Dissolved-Phase
Hydrocarbon
Concentrations (µg/I)

Dissolved-Phase
TPPH Contour (µg/l)

DISSOLVED-PHASE TPPH CONCENTRATIONS MAP May 7, 2004

76 Station 0018 6201 Claremont Avenue Oakland, California



CLAREMONT AVENUE



NOTES:

B= benzene. $\mu g/l=$ micrograms per liter. ND = not detected at limit indicated on official laboratory report. UST = underground storage tank. Results obtained using EPA Method 8260B.




LEGEND

MW-3

Monitoring Well with
Dissolved-Phase
Benzene Concentrations
(μg/I)

DISSOLVED-PHASE BENZENE CONCENTRATIONS MAP May 7, 2004

76 Station 0018 6201 Claremont Avenue Oakland, California



CLAREMONT AVENUE



NOTES:

Contour lines are interpretive and based on laboratory analysis results of groundwater samples. MTBE = methyl tertiory butyl ether.

µg/l = micrograms per liter. ND = not detected at limit indicated on official laboratory report.

UST = underground storage tank. Results obtained using EPA Method 8260B.



LEGEND

MW-3

Monitoring Well with

Dissolved—Phase

MTBE Concentrations
(μg/l)


10

Dissolved-Phase MTBE Contour (µg/l) DISSOLVED-PHASE MTBE CONCENTRATIONS MAP May 7, 2004


76 Station 0018 6201 Claremont Avenue Oakland, California

GRAPHS

Graph 1
Benzene Concentrations vs. Time
76 Station 0018



Graph 2 Hydrograph 76 Station 0018



→ MW-1 **→** MW-2 **→** MW-3

GENERAL FIELD PROCEDURES

Groundwater Monitoring and Sampling Assignments

For each site, TRC technicians are provided with a Technical Service Request (TSR) that specifies activities required to complete the groundwater monitoring and sampling assignment for the site. TSRs are based on client directives, instructions from the primary environmental consultant for the site, regulatory requirements, and TRC's previous experience with the site.

Fluid Level Measurements

Initial site activities include determination of well locations based on a site map provided with the TSR. Well boxes are opened and caps are removed. Indications of well or well box damage, or of pressure buildup in the well are noted.

Fluid levels in each well are measured using a coated cloth tape equipped with an electronic interface probe, which distinguishes between liquid phase hydrocarbon (LPH) and water. The depth to LPH (if it is present), to water, and to the bottom of the well are measured from the top of the well casing (surveyors mark or notch if present) to the nearest 0.01 foot. Unless otherwise instructed, a well with less than 0.67 foot between the measured top of water and the measured bottom of the well casing is considered dry, and is not sampled. If the well contains 0.67 foot or more of water, an attempt is made to bail and/or sample as specified on the TSR.

Wells that are found to contain LPH are not purged or sampled. Instead, one casing volume of fluid is bailed from the well and the well is re-sealed. Bailed fluids are placed in a container separate from normal purge water, and properly disposed.

Purging and Groundwater Parameter Measurement

TSR instructions may specify that a well not be purged (no-purge sampling), be purged using low-flow methods, or be purged using conventional pump and/or bail methods. Conventional purging generally consists of pumping or bailing until a minimum of three casing volumes of water have been removed or until the well has been pumped dry. Pumping is generally accomplished using submersible electric or pneumatic diaphragm pumps.

During conventional purging, three groundwater parameters (temperature, pH, and conductivity) are measured after removal of each casing volume. Stabilization of these parameters, to within 10 percent, confirm that sufficient purging has been completed. In some cases, the TSR indicates that other parameters are also to be measured during purging. TRC commonly measures dissolved oxygen (DO), oxidation-reduction potential (ORP), and/or turbidity. Instruments used for groundwater parameter measurement are calibrated daily according to manufacturer's instructions.

Low-flow purging utilizes a bladder or peristaltic pump to remove water from the well at a low rate. Groundwater parameters specified by the TSR are measured continuously until they become stable in general accordance with EPA guidelines.

Purge water is generally collected in labeled drums for disposal. Drums may be left on site for disposal by others, or transported to a collection location for eventual transfer to a licensed treatment or recycling facility. In some cases, purge water may be collected directly from the site by a licensed vacuum truck company, or may be treated on site by an active remediation system, if so directed.

Groundwater Sample Collection

After wells are purged, or not purged, according to TSR instructions, samples are collected for laboratory analysis. For wells that have been purged using conventional pump or bail methods, sampling is conducted after the well has recovered to 80 percent of its original volume or after two hours if the well does not recover to at least 80 percent. If there is insufficient recharge of water in the well after two hours, the well is not sampled.

Samples are collected by lowering a new, disposable, ½-inch to 4-inch polyethylene bottom-fill bailer to just below the water level in the well. The bailer is retrieved and the water sample is carefully transferred to containers specified for the laboratory analytical methods indicated by the TSR. Particular care is given to containers for volatile organic analysis (VOAs) which require filling to zero headspace and fitting with Teflon-sealed caps.

After filling, all containers are labeled with project number (or site number), well designation, sample date, and the samplers initials, and placed in an insulated chest with ice. Samples remain chilled prior to and during transport to a state-certified laboratory for analysis. Sample container descriptions and requested analyses are entered onto a chain-of-custody form in order to provide instructions to the laboratory. The chain-of-custody form accompanies the samples during transportation to provide a continuous record of possession from the field to the laboratory. If a freight or overnight carrier transports the samples, the carrier is noted on the form.

For wells that have been purged using low-flow methods, sample containers are filled from the effluent stream of the bladder or peristaltic pump. In some cases, if so specified by the TSR, samples are taken from the sample ports of actively pumping remediation wells.

Sequence of Gauging, Purging, and Sampling

The sequence in which monitoring activities are conducted are specified on the TSR. In general, wells are gauged beginning with the least-affected well and ending with the well that has highest concentration based on previous analytic results. After all gauging for the site is completed, wells are purged and/or sampled from the least-affected well to the most-affected well.

Decontamination

In order to reduce the possibility of cross-contamination between wells, strict isolation and decontamination procedures are observed. Portable pumps are not used in wells with LPH. Technicians wear nitrile gloves during all gauging, purging and sampling activities. Gloves are changed between wells and more often if warranted. Any equipment that could come in contact with fluids are either dedicated to a particular well, decontaminated prior to each use, or discarded after a single use. Decontamination consists of washing in a solution of Liqui-nox and water and rinsing twice. The final rinse is in deionized water.

Exceptions

Additional tasks or non-standard procedures, if any, that may be requested or required for a particular site, and noted on the site TSR, are documented in field notes on the following pages.

FIELD MONITORING DATA SHEET

Technician: Dav of Tenney Job#Task#: 410900-01/FA26 Date: 5-7-04

Site # 0018 Project Manager Bas basa Moed Page 1 of 1

Well #	Grade	тос	Total Depth	Depth to Water	Depth to Product	Product Thickness (feet)	Time Sampled	Misc. Well Notes
MW-3		X	29.88	16.79	0	O	1001	2/1
MW-1		X	29.71	16.74	0	0	0938	2"
MW-2		X	29.58		0	9	1026	2/1
								•
			_					
	1							
						<u> </u>		
	 			-				
	-	 			•		1	
	<u> </u>	 					-	
			-	· ·				
_	-	-	-		 			
		 	<u> </u>		-		 	
		 			-			
	_	<u> </u>			1			
	1/_	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>		
IELD DAT	COMP	LETE	QAQ	ć	CQ1	<u> </u>	WELL BOX1	CONDITION SHEETS
MTT CER	ΠΕΙCATE	 	MANIFI	EST	DRUM I	NYENTORY	TR	AFFIC CONTROL

GROUNDWATER SAMPLING FIELD NOTES

		Т	'echnician: 👤	burid Teune	7			
Site: 00/8	3	F	Project No.:	410500-01/	FA20	ŧ	Date: 5-7-	04
Site: <u> </u>	1W-3			Purge Method	54b 09	169		
Depth to Wate	1/	.79			uct (feet):			
Total Depth (fe	et): 29.88	-		LPH & Water I	Recovered (gall	ons): -		
Water Column	(feet)13. (79						
80% Recharge	e Depth (feet):_	19.41		1 Well Volume	ter (Inches): e (gallons):	2		
Time Start	Time Stop	Depth To Water (feet)	Volume Purged (gallons)	Conduc- tivity (uS/cm)	Temperature	рΗ	Turbidity	D .O.
0951			2	620	18-1	6.40		
			4	664		5.70		
	0956		6	641	18,9	539		
-	0 100				10,1			·
-							<u></u>	<u></u>
Staf	ic at Time Sam	nled	1	l otal Gallons Pu	urged		Time Sampl	ed .
	1.37	pica		6	inged	ł. ·	1001	
Well No.:	1w - 1 '		· ···		d. 54b 09	69		
		7 <u>4</u>						
	ter (feet): 6.				duct (feet):			
Total Depth (feet): 29.7	97	-		r Recovered (ga			
Water Colum 80% Recharg	nn (feet): \[\frac{2}{2} \] ge Depth (feet)	19.33	-	-	neter (Inches): ne (gallons):	<u></u>		•
Time Start	Time Stop	Depth To Water (feet)	Volume Purged (gallons)	Conduc- tivity (uS/cm)	Temperature (F. \mathcal{G}	pH	Turbidity	D.O.
0929			2	751w	17.6	5.87		
			4	755	18.6	5.66		
	0931		6	739	19.4	5.45		
ļ			,,		<u> </u>			
	1	1		T. () O !!		<u> </u>	Line Com	
	atic at Time Sa	mplea	<u></u>	Total Gallons F	rurged		Time Sam	

GROUNDWATER SAMPLING FIELD NOTES

				land letthe			_	
Site: 0018		P	roject No.:	110500-01	/FA20	_	Date: 5-7-	04
Vell No.: M	w-2			Purae Method	Sub o	969		
Depth to Water	(feet): 17	1.79			uct (feet):			
Total Depth (fee	et): 29.5	58			Recovered (gal			
Water Column ((feet):	79						
80% Recharge	Depth (feet):	20.15		1 Well Volume	ter (Inches): e (gallons):	2	·	
Time Start	Time Stop	Depth To Water (feet)	Volume Purged (gallons)	Conduc- tivity (uS/cm)	Temperature	Hq		D.O.
1013	<u> </u>	. (icet)	2	499	108	17 23		<u> </u>
+01)				498	18.7	6.02		
<u> </u>	Don't Co		4	3 2	H- 1	0.02		The state of the s
	019		6	49 7	19.1	5.51		
	at Time San	pled	To	otal Gallons Pu	rged		Time Samples	j
17.9	0			6			1026	
Comments:								
Well No.:	j.			Purge Metho	d:			
Well No.:				Depth to Pro	duct (feet):			
Well No.:	er (feet):			Depth to Pro				
Well No.:	er (feet): eet):			Depth to Pro	duct (feet):	allons):		
Well No.: Depth to Wate Total Depth (fe Water Column	er (feet): eet): n (feet);			Depth to Proi LPH & Water Casing Diam	duct (feet): r Recovered (g	allons):	· · · · · · · · · · · · · · · · · · ·	
Well No.: Depth to Wate Total Depth (fe Water Column	er (feet): eet): n (feet);			Depth to Proi LPH & Water Casing Diam	duct (feet): r Recovered (g leter (Inches):_	allons):	· · · · · · · · · · · · · · · · · · ·	D.O.
Well No.:	er (feet): eet): i (feet): e Depth (feet) Time	Depth To Water	Volume Purged	Depth to Pro- LPH & Water Casing Diam 1 Well Volun Conduc- tivity	duct (feet):r Recovered (gleter (Inches):ne (gallons):	allons):	· · · · · · · · · · · · · · · · · · ·	D.O.
Well No.:	er (feet): eet): i (feet): e Depth (feet) Time	Depth To Water	Volume Purged	Depth to Pro- LPH & Water Casing Diam 1 Well Volun Conduc- tivity	duct (feet):r Recovered (gleter (Inches):ne (gallons):	allons):	· · · · · · · · · · · · · · · · · · ·	D.O.
Well No.:	er (feet): eet): i (feet): e Depth (feet) Time	Depth To Water	Volume Purged	Depth to Pro- LPH & Water Casing Diam 1 Well Volun Conduc- tivity	duct (feet):r Recovered (gleter (Inches):ne (gallons):	allons):	· · · · · · · · · · · · · · · · · · ·	D.O.
Well No.: Depth to Water Total Depth (for Water Column 80% Recharge Start	er (feet): eet): i (feet): e Depth (feet) Time	Depth To Water (feet)	Volume Purged (gallons)	Depth to Pro- LPH & Water Casing Diam 1 Well Volun Conduc- tivity	duct (feet): r Recovered (g leter (Inches): ne (gallons): Temperature	allons):	· · · · · · · · · · · · · · · · · · ·	



Submission#: 2004-05-0345

TRC Aiton Geoscience

May 24, 2004

21 Technology Drive Irvine, CA 92718

Attn.:

Anju Farfan

Project#: 41050001FA20

Project:

Conoco Phillips # 0018

Site:

6201 Claremont Boulevard

Attached is our report for your samples received on 05/10/2004 12:20 This report has been reviewed and approved for release. Reproduction of this report is permitted only in its entirety.

Please note that any unused portion of the samples will be discarded after 06/24/2004 unless you have requested otherwise.

We appreciate the opportunity to be of service to you. If you have any questions, please call me at (925) 484-1919.

You can also contact me via email. My email address is: dsharma@stl-inc.com

Sincerely,

Dimple Sharma Project Manager

aema_

Submission: 2004-05-0345 Project Verification

Received on: 05/10/2004 12:20 From: TRC Alton Geoscience

By: Dimple Sharma Anju Farfan STL San Francisco

Cooler Tmp: 3.0 21 Technology Drive 1220 Quarry Ln Pleasanton CA 94566

Irvine, CA 92718

Project#: 41050001FA20 Tel.: (925) 484-1919
Fax: (925) 484-1096
www.stl-inc.com

Project: Conoco Phillips # 0018 6201 Claremont Boulevard

CA DHS ELAP#:2496

Lab Sample #	Sample ID	Matrix		Sampled
EPA Method	Analysis		TAT	Due Date
2004-05-0345 - 1	MW-3	Water		05/07/2004 10:01
8260B	Gas/BTEX Fuel Oxygenates by 8260B (Selec	table)	9 Day	05/21/2004 17:00
	Benzene, Ethanol, Ethylbenzene, Gasoline, Methyl tert-butyl ether (MTBE), Toluene, Total	xylenes		
2004-05-0345 - 2	MW-1	Water		05/07/2004 09:38
8260B	Gas/BTEX Fuel Oxygenates by 8260B (Select	table)	9 Day	05/21/2004 17:00
	1,2-DCA, Benzene, Di-isopropyl Ether (DIPE), Ethanol, Ethyl tert-butyl ether (ETBE), Ethylbe Methyl tert-butyl ether (MTBE), tert-Amyl meth Toluene, Total xylenes	nzene, Gasol		yl alcohol (TBA),
2004-05-0345 - 3	MW-2	Water	illerie (1275) wys Kwel alkindenide Aks	05/07/2004 10:26
8260B	Gas/BTEX Fuel Oxygenates by 8260B (Selec	table)	9 Day	05/21/2004 17:00
	Benzene, Ethanol, Ethylbenzene, Gasoline, Methyl tert-butyl ether (MTBE), Toluene, Total	xylenes		





TRC Alton Geoscience

Attn.: Anju Farfan

21 Technology Drive Irvine, CA 92718

Phone: (949) 341-7440 Fax: (949) 753-0111

Project: 41050001FA20


Conoco Phillips # 0018

Received: 05/10/2004 12:20

Site: 6201 Claremont Boulevard

Samples Reported

Sample Name	Date Sampled	Matrix	Lab#
MW-3	05/07/2004 10:01	Water	1
MW-1	05/07/2004 09:38	Water	2
MW-2	05/07/2004 10:26	Water	3





TRC Alton Geoscience Attn.: Anju Farfan

21 Technology Drive Irvine, CA 92718

Phone: (949) 341-7440 Fax: (949) 753-0111

Project: 41050001FA20

Conoco Phillips # 0018

Received: 05/10/2004 12:20

Site: 6201 Claremont Boulevard

Prep(s): 5030B

Sample ID: MW-3

Sampled: 05/07/2004 10:01

Matrix: Water

Test(s): 8260FAB

Lab ID: 2004-05-0345 - 1

Extracted: 5/20/2004 22:59

QC Batch#: 2004/05/20-02.64

Compound	Conc.	RL	Unit	Dilution	Analyzed	Flag
Gasoline	ND	50	ug/L	1.00	05/20/2004 22:59	
Benzene	ND	0.50	ug/L	1.00	05/20/2004 22:59	
Toluene	ND	0.50	ug/L	1.00	05/20/2004 22:59	
Ethylbenzene	ND	0.50	ug/L	1.00	05/20/2004 22:59	
Total xylenes	ND	1.0	ug/L	1.00	05/20/2004 22:59	
Methyl tert-butyl ether (MTBE)	0.55	0.50	ug/L	1.00	05/20/2004 22:59	
Ethanol	ND	50	ug/L	1.00	05/20/2004 22:59	
Surrogate(s)			, i			
Toluene-d8	98.4	88-110	%	1.00	05/20/2004 22:59	
1,2-Dichloroethane-d4	105.9	76-114	%	1.00	05/20/2004 22:59	



TRC Alton Geoscience

Attn.: Anju Farfan

21 Technology Drive Irvine, CA 92718

Phone: (949) 341-7440 Fax: (949) 753-0111

Project: 41050001FA20

Conoco Phillips # 0018

Received: 05/10/2004 12:20

Site: 6201 Claremont Boulevard

Prep(s): 5030B

Test(s):

8260FAB

Sample ID: MW-1

05/07/2004 09:38

Lab ID:

2004-05-0345 - 2 5/20/2004 23:21


Sampled: Matrix:

Water

Extracted: QC Batch#:

2004/05/20-02.64

Compound	Conc.	RL	Unit	Dilution	Analyzed	Flag
Gasoline	180	50	ug/L	1.00	05/20/2004 23:21	g
Benzene	ND	0.50	ug/L	1.00	05/20/2004 23:21	
Toluene	ND	0.50	ug/L	1.00	05/20/2004 23:21	
Ethylbenzene	ND	0.50	ug/L	1.00	05/20/2004 23:21	
Total xylenes	ND	1.0	ug/L	1.00	05/20/2004 23:21	
tert-Butyl alcohol (TBA)	ND	5.0	ug/L	1.00	05/20/2004 23:21	
Methyl tert-butyl ether (MTBE)	25	0.50	ug/L	1.00	05/20/2004 23:21	
Di-isopropyl Ether (DIPE)	ND	1.0	ug/L	1.00	05/20/2004 23:21	
Ethyl tert-butyl ether (ETBE)	ND	0.50	ug/L	1.00	05/20/2004 23:21	
tert-Amyl methyl ether (TAME)	ND	0.50	ug/L	1.00	05/20/2004 23:21	
1,2-DCA	ND	0.50	ug/L	1.00	05/20/2004 23:21	
EDB	ND	0.50	ug/L	1.00	05/20/2004 23:21	
Ethanol	ND	50	ug/L	1.00	05/20/2004 23:21	
Surrogate(s)						·
Toluene-d8	97.6	88-110	%	1.00	05/20/2004 23:21	
1,2-Dichloroethane-d4	103.5	76-114	%	1.00	05/20/2004 23:21	





TRC Alton Geoscience Attn.: Anju Farfan

21 Technology Drive Irvine, CA 92718

Phone: (949) 341-7440 Fax: (949) 753-0111

Project: 41050001FA20

Conoco Phillips # 0018

Received: 05/10/2004 12:20

Site: 6201 Claremont Boulevard


Prep(s): 5030B Test(s): 8260FAB

Sample ID: MW-2 Lab ID: 2004-05-0345 - 3

Sampled: 05/07/2004 10:26 Extracted: 5/20/2004 23:43

Matrix: Water QC Batch#: 2004/05/20-02.64

Compound	Conc.	RL	Unit	Dilution	Analyzed	Flag
Gasoline	ND	50	ug/L	1.00	05/20/2004 23:43	
Benzene	ND	0.50	ug/L	1.00	05/20/2004 23:43	
Toluene	ND	0.50	ug/L	1.00	05/20/2004 23:43	
Ethylbenzene	ND	0.50	ug/L	1.00	05/20/2004 23:43	
Total xylenes	ND	1.0	ug/L	1.00	05/20/2004 23:43	
Methyl tert-butyl ether (MTBE)	ND	0.50	ug/L	1.00	05/20/2004 23:43	
Ethanol	ND	50	ug/L	1.00	05/20/2004 23:43	
Surrogate(s)		[,	
Toluene-d8	96.2	88-110	%	1.00	05/20/2004 23:43	
1,2-Dichloroethane-d4	105.9	76-114	%	1.00	05/20/2004 23:43	





TRC Alton Geoscience

Attn.: Anju Farfan

21 Technology Drive Irvine, CA 92718

Phone: (949) 341-7440 Fax: (949) 753-0111

Project: 41050001FA20

Conoco Phillips # 0018

Received: 05/10/2004 12:20

Site: 6201 Claremont Boulevard

		Batch QC Report		海撒
Prep(s): 5030B			Test(s): 8260F	AB
Method Blank		Water	QC Batch # 2004/05/20-02	
MB: 2004/05/20	-02.64-050		Date Extracted: 05/20/2004 18	r:50

Compound	Conc.	RL	Unit	Analyzed	Flag
Gasoline	ND	50	ug/L	05/20/2004 18:50	
Benzene	ND	0.5	ug/L	05/20/2004 18:50	
Toluene	ND	0.5	ug/L	05/20/2004 18:50	
Ethylbenzene	ND	0.5	ug/L	05/20/2004 18:50	
Total xylenes	ND	1.0	ug/L	05/20/2004 18:50	
tert-Butyl alcohol (TBA)	ND	5.0	ug/L	05/20/2004 18:50	
Methyl tert-butyl ether (MTBE)	ND	0.5	ug/L	05/20/2004 18:50	
Di-isopropyl Ether (DIPE)	ND	1.0	ug/L	05/20/2004 18:50	
Ethyl tert-butyl ether (ETBE)	ND	0.5	ug/L	05/20/2004 18:50	
tert-Amyl methyl ether (TAME)	ND	0.5	ug/L	05/20/2004 18:50	
1,2-DCA	ND	0.5	ug/L	05/20/2004 18:50	
EDB	ND	0.5	ug/L	05/20/2004 18:50	
Ethanol	ND	50	ug/L	05/20/2004 18:50	
Surrogates(s)					
1,2-Dichloroethane-d4	107.0	72-128	%	05/20/2004 18:50	
Toluene-d8	100.4	80-113	%	05/20/2004 18:50	

Tel 925 484 1919 Fax 925 484 1096 * www.stl-inc.com * CA DHS ELAP# 2496





TRC Alton Geoscience Attn.: Anju Farfan

21 Technology Drive Irvine, CA 92718

Phone: (949) 341-7440 Fax: (949) 753-0111

Project: 41050001FA20


Conoco Phillips # 0018

Received: 05/10/2004 12:20

Site: 6201 Claremont Boulevard

		Batch QC	Report		
Prep(s):				egi arting seles seles Agenderal artista Alexandria (d. 1911)	Test(s): 8260FAB
Laborato LCS	ory Control Spik 2004/05/20-02	Wa Extracted	ter I: 05/20/2004	9,18,16,6,1,19,18	# 2004/05/20-02.64 : 05/20/2004 18:06
LCSD	2004/05/20-02.		I: 05/20/2004	THE REPORT OF THE PARTY	1: 05/20/2004 18:28

Compound	Conc.	ug/L	Exp.Conc.	Reco	very %	RPD	Ctrl.Lin	nts %	Fla	ags
	LCS	LCSD		LCS	LCSD	%	Rec.	RPD	LCS	LCSD
Benzene	22.3	20.2	25.0	89.2	80.8	9.9	69-129	20		
Toluene	22.9	20.9	25.0	91.6	83.6	9.1	70-130	20		
Methyl tert-butyl ether (MTBE)	24.4	23.1	25.0	97.6	92.4	5.5	65-165	20		
Surrogates(s)										
1,2-Dichloroethane-d4	518	498	500	103.6	99.6		72-128			
Toluene-d8	519	505	500	103.8	101.0		80-113			





TRC Alton Geoscience

Attn.: Anju Farfan

21 Technology Drive Irvine, CA 92718

Phone: (949) 341-7440 Fax: (949) 753-0111

Project: 41050001FA20

Conoco Phillips # 0018

Received: 05/10/2004 12:20

Site: 6201 Claremont Boulevard

Legend and Notes

Result Flag

g

Hydrocarbon reported in the gasoline range does not match our gasoline standard.

STL

STL San Francisco

Sample Receipt Checklist

3dbinission #.2004-175 - 77.245	
Checklist completed by: (Initials) Date: (75 / // 104	
Courier name: [2] STL San Francisco [] Client	
Custody seals intact on shipping container/especies	YesNoPresent
Chain of custody present?	YesNo
Chain of custody signed when relinquished and received?	Yes_No_
Chain of custody present? Chain of custody signed when relinquished and received? Chain of custody agrees with sample labels? Samples in proper container/bottle? Sample containers intact? Sufficient sample volume for indicated test? All samples received within holding time?	Yes V No
Samples in proper container/bottle?	Ves_UNO
Sample containers intact?	Yes_ Vo
Sufficient sample volume for indicated test?	YesNo
All samples received within holding time?	YesNo
Container/Temp Blank temperature in compliance (4° C ± 2)?	Temp: C Yes No
	Ice Present Yes No No
Water - VOA vials have zero headspage?	No VOA vials submitted Yes No
(if bubble is present, refer to approximate bubble size and itemize in comments	as S (small \sim 0), M (medium \sim 0) or L (large \sim 0)
Water - pH acceptable upon receipt? ☐ Yes ☐ No	
□ pH adjusted— Preservative used: □ HNO₃ □ HCl □ H₃SO₄ □ NaOH □ I	ZnOAc ~Lot #(s)
For any item check-listed "No", provided detail of discrepancy in commer	nt section below:
Comments:	
	,
Project Management [Routing for instruction of indicate	ed discrepancy(ies)]
Project Manager: (initials) Date://04	
Client contacted: ☐ Yes ☐ No	
Summary of discussion:	
AND THE RESIDENCE OF THE PROPERTY OF THE PROPE	
Conscilve Action (per PM/Client):	
Section of Lands (Leaf 1 180 Colored)	

2004-05-0345

ConocoPhillips Chain Of Custody Record

85666

CoлоcoPhillips Site Manager: ConocoPhillips Work Order Number 1220 Quarry Lane INVOICE REMITTANCE ADDRESS: 1062 TR C SOO CONOCOPHILLIPS Pleasanton, CA 94566 Attn: Dee Hutchinson ConcoPhilips Cost Object 3611 South Harbor, Suite 200 (925) 484-1919 (925) 484-1096 fax Santa Ana, CA, 92704 SAMPLING COMPANY CONOCOPHILLIPS STIE PLANDER TO 60010 223 1 TRC AUDINES# 21 Technology Drive, Irvine CA 92618 Clairement Boylevard Thomas H. Korl PROJECT CONTACT (Mardenby or PDF Report for Anju Farfan LAB USE CALY TEL SPHONE Peter Thomson, TRC 949-341-7408 949-341-7440 849-753-0111 afarfan@ircselutions.com othomson@tresolutions.com SAMPLER NAME(S) (Prive): Computant Project Kumber REQUESTED ANALYSES David Tenner 41050001/FA20 TURNAROUND TIME (CALENDAR DAYS): 250B - TPHg / BTEX / 8 Oxygenates 180X1843 14 DAYS 7 DAYS 72 HOURS 1 48 HOURS 1 24 HOURS 1 LESS THAN 24 HOURS BOISM / 8021B - TPHSJETEXIMBE CTotal CSTLC CTCLP **FIELD NOTES:** 260 SPECIAL INSTRUCTIONS OR NOTES: CHECK BOX IF EDD IS NEEDED ... - TPHG Extractable Container/Preservative 8270C - Semi-Volatios or PID Readings or Laboratory Notes a C * Field Point name only required if different from Sample ID Sample Identification/Field Point HO. 09 TEMPERATURE ON RECEIPT OF SMI Y MATRIX Name* DATE TIME MW-3 1001 MW-1 048 MW-2 1026 5-7-04 1200

STATEMENTS

Purge Water Transport and Disposal

Non-hazardous groundwater produced during purging and sampling was accumulated at TRC's groundwater monitoring facility at Concord, California, for transportation by Onyx Transportation, Inc., to the ConocoPhillips Refinery at Rodeo, California. Disposal at the Rodeo facility was authorized by ConocoPhillips in accordance with "ESD Standard Operating Procedures – Water Quality and Compliance", as revised on February 7, 2003. Documentation of compliance with ConocoPhillips requirements is provided by an ESD Form R-149, which is on file at TRC's Concord Office. Purge water suspected of containing potentially hazardous material, such as liquid-phase hydrocarbons, was accumulated separately in a drum for transportation and disposal by Filter Recycling, Inc.

Limitations

The fluid level monitoring and groundwater sampling activities summarized in this report have been performed under the responsible charge of a California Registered Geologist or Registered Civil Engineer and have been conducted in accordance with current practice and the standard of care exercised by geologists and engineers performing similar tasks in this area. No warranty, express or implied, is made regarding the conclusions and professional opinions presented in this report. The conclusions are based solely upon an analysis of the observed conditions. If actual conditions differ from those described in this report, our office should be notified.