### STELLAR ENVIRONMENTAL SOLUTIONS

2198 SIXTH STREET, BERKELEY, CA 94710 Tel: 510.644.3123 ★ FAX: 510.644.3859

Alamede County 159 OCT 2 I 2002 Environmental Health

#### TRANSMITTAL MEMORANDUM

To: Alameda County Health Care Services Date: 10/16/02

AGENCY

DEPT. OF ENVIRONMENTAL HEALTH HAZARDOUS MATERIALS DIVISION 1131 HARBOR BAY PKWY, SUITE 250 ALAMEDA, CA 94502

ATTENTION: Mr. SCOTT SEERY FILE: SES-2001-53

SUBJECT: REDWOOD REGIONAL PARK FUEL

LEAK SITE

WE ARE SENDING: HEREWITH 

UNDER SEPARATE COVER

✓ VIA MAIL

□ VIA

THE FOLLOWING: THIRD QUARTER 2002 SITE MONITORING REPORT FOR

REDWOOD REGIONAL PARK SERVICE YARD SITE - OAKLAND,

CALIFORNIA (JULY 2002)

☐ AS REQUESTED ☐ FOR YOUR APPROVAL

☐ FOR REVIEW ☐ FOR YOUR USE

☐ FOR SIGNATURE ☐ FOR YOUR FILES

50 - 644 - 3123 By: Bruce Rucker SMR x 12

COPIES TO: K. BURGER (EBRPD)

M. Rugg (FISH & GAME)

R.BREWER (REGIONAL BOARD)

# **Stellar Environmental Solutions**

2198 Sixth Street, Suite 201. Berkeley, CA 94710 Tel: (510) 644-3123 • Fax: (510) 644-3859

Geoscience & Engineering Consulting

October 14, 2002

Alameda County

Mr. Scott O. Seery
Hazardous Materials Specialist
Alameda County Health Care Services Agency

OCT 2 1 2002

Alameda County Health Care Services Agency

Department of Environmental Health, Hazardous Materials Division

Environmental Health

1131 Harbor Bay Parkway, Suite 250

Alameda, California 94502

Subject:

Third Quarter 2002 Site Monitoring Report

Redwood Regional Park Service Yard Site - Oakland, California

Dear Mr. Seery:

Attached is the referenced Stellar Environmental Solutions report for the underground fuel storage tank site at the Redwood Regional Park Service Yard, located at 7867 Redwood Road, Oakland, California. This project is being conducted for the East Bay Regional Park District, and follows previous site investigation and remediation activities associated with former leaking underground fuel storage tanks, conducted since 1993. The key regulatory agencies for this investigation are the Alameda County Health Care Services Agency, the California Regional Water Quality Control Board, and the California Department of Fish and Game.

This report summarizes groundwater and surface monitoring and sampling activities conducted in September 2002 (Third Quarter 2002). If you have any questions regarding this report, please contact Mr. Ken Burger of the East Bay Regional Park District, or contact us directly at (510) 644-3123.

No. 6814

Sincerely,

· Brue M. Ruhl.

Bruce M. Rucker, R.G., R.E.A.

Project Manager

Richard S. Makaisi, R.G., R.E.A.

Principal

cc:

Michael Rugg, California Department of Fish and Game Roger Brewer, California Regional Water Quality Control Board Ken Burger, East Bay Regional Park District

FADocs-M&Worth2001-53-EBRPD-Redwood:Reports/REPORT-Q3-2002-Final-Oct02-.de

# THIRD QUARTER 2002 SITE MONITORING REPORT

# REDWOOD REGIONAL PARK SERVICE YARD OAKLAND, CALIFORNIA

### Prepared for:

EAST BAY REGIONAL PARK DISTRICT P.O. BOX 5381 OAKLAND, CALIFORNIA 94605

Prepared by:

STELLAR ENVIRONMENTAL SOLUTIONS 2198 SIXTH STREET BERKELEY, CALIFORNIA 94710

October 14, 2002

**Project No. 2001-53** 

# TABLE OF CONTENTS

Sectio	n Pag	zе
1.0	INTRODUCTION	. 1
	Project Background	. 1
2.0	PHYSICAL SETTING	.5
3.0	CURRENT GROUNDWATER AND SURFACE WATER MONITORING EVENT ACTIVITIES	.8
	Groundwater Level Monitoring and Sampling  Creek Surface Water Sampling	.8 .9
4.0	REGULATORY CONSIDERATIONS	11
	Groundwater Contamination	11 11
5.0	MONITORING EVENT ANALYTICAL RESULTS	13
	Current Event Groundwater Results  Current Event Natural Attenuation Parameters Results  Quality Control Sample Analytical Results	13
6.0	SUMMARY, CONCLUSIONS, AND PROPOSED ACTIONS	18
	Summary and Conclusions  Proposed Actions	18 19
7.0	REFERENCES AND BIBLIOGRAPHY	20
8.0	LIMITATIONS	23
Appe	ndices	
	ndix A Groundwater Monitoring Field Documentation  ndix B Analytical Laboratory Reports and Chain-of-Custody Records	

# TABLES AND FIGURES

Tables	Page
Table 1	Groundwater Monitoring Well Construction and Groundwater Elevation Data
Table 2	Groundwater and Surface Water Sample Analytical Results – September 24, 2002
Table 3	Groundwater Sample Analytical Results Natural Attenuation Indicators – September 24, 2002
Figures	Page
Figure 1	Site Location Map3
Figure 2	Site Plan and Historical Sampling Locations4
Figure 3	Groundwater Elevation Map – September 24, 20026
Figure 4	Groundwater and Surface Water Analytical Results – September 24, 2002 15

## 1.0 INTRODUCTION

### PROJECT BACKGROUND

The subject property is the East Bay Regional Park District (EBRPD) Redwood Regional Park Service Yard located at 7867 Redwood Road in Oakland, Alameda County, California. The site has undergone site investigations and remediation since 1993 to address subsurface contamination caused by leakage from one or both of two former underground fuel storage tanks (UFSTs) that contained gasoline and diesel fuel. The Alameda County Health Care Services Agency (ACHCSA) has provided regulatory oversight of the investigation since its inception. Other regulatory agencies with historical involvement in site review include the California Regional Water Quality Control Board (RWQCB) and the California Department of Fish and Game (CDFG).

### OBJECTIVES AND SCOPE OF WORK

This report discusses the following activities conducted/coordinated by Stellar Environmental Solutions (SES) in September 2002:

- Collecting water levels in site wells to determine shallow groundwater flow direction;
- Sampling site wells for contaminant analysis and natural attenuation indicators; and
- Collecting surface water samples for contaminant analysis.

Previous SES reports (see References section) have provided a full discussion of previous site remediation and investigations; site geology and hydrogeology; residual site contamination; conceptual model for contaminant fate and transport; and evaluation of hydrochemical trends and plume stability. An October 2000 Feasibility Study report for the site, submitted to ACHCSA, provided detailed analyses of the regulatory implications of the site contamination and an assessment of viable corrective actions (SES, 2000d). Additional monitoring well installations and corrective action by ORC<sup>TM</sup> injection proposed by SES were approved by the ACHCSA in its January 8, 2001 letter to the EBRPD. Two phases of ORC<sup>TM</sup> injection have been conducted: September 2001 and July 2002. A total of 23 groundwater monitoring events have been conducted on a quarterly basis since inception (November 1994), and a total of 11 groundwater monitoring wells are currently available for monitoring.


#### SITE DESCRIPTION


Figure 1 shows the location of the project site. The site slopes to the west, from an elevation of approximately 564 feet above mean sea level (amsl) at the eastern edge of the service yard to approximately 545 feet amsl at Redwood Creek which defines the approximate western edge of the project site with regard to this investigation. Figure 2 shows the site plan.

#### REGULATORY OVERSIGHT

The lead regulatory agency for the site investigation and remediation is ACHCSA, with oversight provided by the RWQCB. The CDFG is also involved with regard to water quality impacts to Redwood Creek. All workplans and reports are submitted to these agencies. The most recent ACHCSA directive regarding the site (letter dated January 8, 2001) approved the ORC™ injection corrective action and requested continued quarterly groundwater monitoring and sampling. Historical ACHCSA-approved revisions to the groundwater sampling program have included: 1) discontinuing hydrochemical sampling and analysis in wells MW-1, MW-3, MW-5, and MW-6; 2) discontinuing creek surface water sampling at upstream location SW-1; and 3) reducing the frequency of creek surface water sampling from quarterly to semi-annually (ACHCSA, 1996). The latter recommendation has not yet been implemented due to continued concern over potential impacts to Redwood Creek.

Electronic Data Format (EDF) groundwater analytical results from the groundwater monitoring events beginning in the third quarter of 2001 have been successfully uploaded to the State of California Water Resources Control Board's GeoTracker database, in accordance with that agency's requirements for EDF submittals.





### 2.0 PHYSICAL SETTING


Following is a brief summary of the site hydrogeologic conditions based on geologic logging and water level measurements collected at the site since September 1993. A full discussion is presented in the SES June 1999 report.

Shallow soil stratigraphy consists of a surficial 3- to 10-foot-thick clayey silt unit underlain by a 5- to 15-foot-thick silty clay unit. In the majority of boreholes, a 5- to 10-foot-thick clayey coarse-grained sand and clayey gravel unit that laterally grades to a clay or silty clay was encountered. This unit overlies a weathered siltstone at the base of the observed soil profile. Soils in the vicinity of MW-1 are inferred to be landslide debris.

Groundwater at the site occurs under unconfined and semi-confined conditions, generally within the clayey, silty sand-gravel zone. The top of this zone varies between approximately 12 and 19 feet below ground surface (bgs), and the bottom of the water-bearing zone (approximately 25 to 28 feet bgs) corresponds to the top of the siltstone bedrock unit. Seasonal fluctuations in groundwater depth create a capillary fringe of several feet which is saturated in the rainy period (late fall through early spring) and unsaturated during the remainder of the year. The thickness of the saturated zone plus the capillary fringe varies between approximately 10 and 15 feet in the area of contamination. Local perched water zones have been observed well above the top of the capillary fringe.

Figure 3 is a groundwater elevation map constructed from the current event monitoring well static water levels, and Table 1 (in Section 3.0) summarizes current event groundwater elevation data. The groundwater gradient is relatively steep—approximately 2 feet per foot—between well MW-1 and the former UFST source area, resulting from the topography and the highly disturbed nature of sediments in the landslide debris. Downgradient from (west of) the UFST source area (between MW-2 and Redwood Creek) the groundwater gradient is approximately 0.1 feet per foot. The direction of shallow groundwater flow during the current event was to the west-southwest (toward Redwood Creek), which is consistent with historical site groundwater flow direction.

We estimated site groundwater velocity at 7 to 10 feet per year using site-specific empirical data, from the date of UST installation in the late 1970s to the date when contamination was first observed in Redwood Creek (1993).



Redwood Creek, which borders the site to the west, is a seasonal creek known for the occurrence of rainbow trout. Creek flow in the vicinity of the site shows significant seasonal variation, with little to no flow during the summer and fall dry season, and vigorous flow with depths exceeding 1 foot during the winter and spring wet season. The creek is a gaining stream (i.e., it is recharged by groundwater) in the vicinity of the site, and discharges into Upper San Leandro Reservoir located approximately 1 mile southeast of the site.

# 3.0 CURRENT GROUNDWATER AND SURFACE WATER MONITORING EVENT ACTIVITIES

This section presents the creek surface water and groundwater sampling and analytical methods for the most recent event. Groundwater and surface water analytical results are summarized in Section 5.0. Monitoring and sampling protocols were in accordance with the ACHCSA-approved SES technical workplan (SES 1998a). Current event activities included:

- Measuring static water levels and field analyzing pre-purge groundwater samples for indicators of natural attenuation (dissolved oxygen, ferrous iron, and redox potential) in all 11 site wells;
- Collecting pre-purge groundwater samples for laboratory analysis of the natural attenuation indicators nitrate and sulfate from monitoring wells MW-3, MW-4, MW-7, and MW-8;
- Collecting post-purge groundwater samples for laboratory analysis of site contaminants from wells located within the groundwater plume (MW-2, MW-4, MW-7, MW-8, MW-9, MW-10, and MW-11); and
- Collecting Redwood Creek surface water samples for laboratory analysis from locations SW-2 and SW-3.

Creek sampling and monitoring/sampling was conducted on September 24, 2002. The locations of all site monitoring wells and creek water sampling locations are shown on Figure 2. Well construction information and water level data are summarized in Table 1. Appendix A contains the groundwater monitoring field records.

#### GROUNDWATER LEVEL MONITORING AND SAMPLING

Groundwater monitoring well water level measurements, purging, sampling, and field analyses were conducted by Blaine Tech Services under the direct supervision of SES personnel. Groundwater sampling was conducted in accordance with State of California guidelines for sampling dissolved analytes in groundwater associated with leaking UFSTs (RWQCB, 1989), and followed the methods and protocols approved by the ACHCSA in the SES 1998 workplan (SES, 1998a).

Table 1 Groundwater Monitoring Well Construction and Groundwater Elevation Data Redwood Regional Park Corporation Yard, Oakland, California

Well	Well Depth	Screened Interval	TØC Elevation	Groundwater Elevation (9/24/02)
MW-1	18	7 to 17	565.9	561.4
MW-2	36	20 to 35	566.5	542.2
MW-3	42	7 to 41	560.9	537.3
MW-4	26	10 to 25	548.1	533.5
MW-5	26	10 to 25	547.5	530.6
MW-6	26	10 to 25	545.6	531.8
MW-7	24	9 to24	547.7	533.5
MW-8	23	8 to 23	549.2	535.5
MW-9	26	11 to 26	549.4	535.3
MW-10	26	11 to 26	547.3	533.8
MW-11	26	11 to 26	547.9	531.7

Notes:

TOC = Top of casing.

Wells MW-1 through MW-6 are 4-inch diameter; all other wells are 2-inch diameter.

All elevations are feet above USGS mean sea level. Elevations of wells MW-1 through MW-6 were surveyed by EBRPD relative to USGS Benchmark No. JHF-49. Wells MW-7 through MW-11 were surveyed by a licensed land surveyor using existing site wells as datum.

As the first task of the monitoring event, static water levels were measured using an electric water level indicator. Pre-purge groundwater samples were then collected for field and laboratory analysis of natural attenuation indicators. The wells to be sampled for contaminant analyses were then purged (by bailing and/or pumping) of three wetted casing volumes. Aquifer stability parameters (temperature, pH, and electrical conductivity) were measured after each purged casing volume to ensure that representative formation water would be sampled.

The well development, purge water, and decontamination rinseate (approximately 80 gallons) from the current event was containerized in the onsite plastic tank. Purge water from future events will continue to be accumulated in the onsite tank until it is full, at which time it will be transported offsite for proper disposal.

### CREEK SURFACE WATER SAMPLING

Surface water sampling was conducted by SES on September 24, 2002. Surface water samples were collected from Redwood Creek location SW-2 (immediately downgradient of the former UFST source area and within the area of documented creek bank soil contamination). The creek was dry at,

and several hundred feet upstream/downstream of, location SW-3 (approximately 500 feet downstream from SW-2); therefore, no surface water sample was collected. In accordance with a previous ACHCSA-approved SES recommendation, upstream sample location SW-1 was not sampled.

At the time of sampling, the creek was not flowing and water was present only in the vicinity of SW-2, at depths of less than 1 foot. Locations SW-1 and SW-3 were dry, which is consistent with historical conditions in the dry season. At the SW-2 location, where contaminated groundwater discharge to the creek has historically been observed, a petroleum odor was noted, as was an orange algae growing on the saturated portion of the creek bank. It is likely that this algae is utilizing the petroleum as a carbon source, and is therefore a good indicator of the presence of petroleum contamination.

## 4.0 REGULATORY CONSIDERATIONS

The following is a summary of regulatory considerations regarding surface water and groundwater contamination.

#### GROUNDWATER CONTAMINATION

As specified in the RWQCB's San Francisco Bay Region Water Quality Control Plan, all groundwaters are considered potential sources of drinking water unless otherwise approved by the RWQCB, and are also assumed to ultimately discharge to a surface water body and potentially impact aquatic organisms. While it is likely that site groundwater would satisfy geology-related criteria for exclusion as a drinking water source (excessive total dissolved solids and/or insufficient sustained yield), RWQCB approval for this exclusion has not been obtained for the site. As summarized in Table 2 (Section 5.0), site groundwater contaminant levels are compared to two sets of criteria: 1) RWQCB Tier 1 Risk-Based Screening Levels (RBSLs) for sites where groundwater is a current or potential drinking water source; and 2) RBSLs for sites where groundwater is not a current or potential drinking water source.

As stipulated in the RBSL document (August 2000, Interim Final), the RBSLs are not cleanup criteria; rather, they are conservative screening-level criteria designed to be protective of both drinking water resources and aquatic environments in general. The groundwater RBSLs are composed of multiple components, including ceiling value, human toxicity, indoor air impacts, and aquatic life protection. Exceedance of RBSLs suggests that additional investigation and/or remediation is warranted. While drinking water standards [e.g., Maximum Contaminant Levels (MCLs)] are published for the site contaminants of concern, the ACHCSA has indicated that impacts to nearby Redwood Creek are of primary importance, and that site target cleanup standards should primarily be evaluated in the context of surface water quality criteria.

#### SURFACE WATER CONTAMINATION

As summarized in Table 2 (Section 5.0), site surface water contaminant levels are compared to the most stringent screening level criteria published by the State of California, U.S. Environmental Protection Agency, and U.S. Department of Energy. These screening criteria address chronic and acute exposures to aquatic life. As discussed in the RWQCB's RBSL document, benthic communities at the groundwater/surface water interface (e.g., at site groundwater discharge location

SW-2) are assumed to be exposed to the full concentration of groundwater contamination prior to dilution/mixing with the surface water). This was also a fundamental assumption in the instream benthic macroinvertebrate bioassessment events, which documented no measurable impacts.

Historical surface water sampling in the immediate vicinity of contaminated groundwater discharge (SW-2) has sporadically documented petroleum contamination, usually in periods of low stream flow, and generally at concentrations several orders of magnitude less than adjacent (within 20 feet) groundwater monitoring well concentrations. It is likely that mixing/dilution between groundwater and surface water precludes obtaining an "instantaneous discharge" surface water sample that is wholly representative of groundwater contamination at the discharge location. Therefore, the most conservative assumption is that surface water contamination at the groundwater/surface water interface is equivalent to the upgradient groundwater contamination (e.g., site downgradient wells MW-4, MW-7, and MW-9).

While site target cleanup standards for groundwater have not been determined, it is likely that no further action will be required by regulatory agencies when groundwater (and surface water) contaminant concentrations are all below their respective screening level criteria. Residual contaminant concentrations in excess of screening level criteria might be acceptable to regulatory agencies if a more detailed risk assessment (e.g., Tier 2 and/or Tier 3) demonstrates that no significant impacts are likely.

# 5.0 MONITORING EVENT ANALYTICAL RESULTS

This section presents the field and laboratory analytical results of the most recent monitoring event. Table 2 summarizes the contaminant analytical results of the current monitoring event, and Table 3 summarizes natural attenuation indicator results from the current event. Figure 4 shows the current event contaminant analytical results and the inferred limits of the TPH-gas groundwater plume. Appendix B contains the certified analytical laboratory report and chain-of-custody records for the current event.

#### CURRENT EVENT GROUNDWATER RESULTS

Current site groundwater contaminant concentrations exceed their respective groundwater RBSLs (for both cases in which the drinking water resource is and is not threatened)—with the exception of toluene, which does not exceed either set of criteria. Site groundwater contaminant concentrations also exceed all surface water screening levels, with the exception of toluene and MTBE.

Maximum groundwater contaminant concentrations for all site contaminants except benzene and MTBE were detected in downgradient well MW-11 (approximately 70 feet downgradient of the former USTs and approximately 50 feet upgradient of Redwood Creek). The maximum concentrations of benzene and MTBE were detected in wells MW-9 (further downgradient) and MW-10, respectively. Contaminants detected in former source area well MW-2 and in downgradient wells on the edges of the plume were less than method detection limits and/or less than surface water screening criteria.

Site-sourced contaminants detected in the surface water sample from location SW-2 included gasoline (590  $\mu$ g/L), benzene (10  $\mu$ g/L), ethylbenzene (13  $\mu$ g/L), and diesel (220  $\mu$ g/L).

# CURRENT EVENT NATURAL ATTENUATION PARAMETERS RESULTS

Pre-purge groundwater samples from selected wells were collected and analyzed for indicators of the natural biodegradation of the hydrocarbon contamination or "natural attenuation." Petroleum hydrocarbons require molecular oxygen to break down the ring structure of specific constituents. Accordingly, although biodegradation of hydrocarbons can occur under anaerobic conditions, hydrocarbon biodegradation is greatest under aerobic conditions. As a result of the demonstrated

Table 2
Groundwater and Surface Water Sample
Analytical Results – September 24, 2002
Redwood Regional Park Corporation Yard, Oakland, California

		Concentrations in μg/L								
Compound	TPHg	ТРН	Benzene	Toluene	Ethyl- benzene	Total Xylenes	МТВЕ			
GROUNDWATE	ER SAMPLES									
MW-2	98	<50	5.0	<0.5	<0.5	<0.5	13			
MW-4	<50	<50	<0.5	<0.5	<0.5	<0.5	<2.0			
MW-7	9,600	3,900	180	<0.5	380	160	<2.0			
MW-8	1,000	420	22	<0.5	64	50.3	<2.0			
MW-9	3,600	2,800	440	11	260	39.2	<4.0			
MW-10	160	120	10	<0.5	6.7	3.6	26			
MW-11	12,000	4,400	330	13	880	654	<10			
Groundwater RBSLs <sup>(a)</sup>	100/500	100/640	1.0/46	40/130	30/290	13/13	5/1,800			
REDWOOD CR	EEK SURFAC	CE WATER SA	AMPLES							
SW-2	590	220	10	<0.5	13	<0.5	<2.0			
SW-3	· · · · · · · · · · · · · · · · · · ·	Location	on not sampled	d (no surface w	ater available)					
Surface Water Screening Levels (a, b)	500	640	46	130	290	13	8,000			

#### Notes

MTBE = Methyl tertiary-butyl ether


TPHg = Total petroleum hydrocarbons - gasoline range (equivalent to total volatile hydrocarbons - gasoline range)

TPHd = Total petroleum hydrocarbons - diesel range (equivalent to total extractable hydrocarbons - diesel range)

 $\mu g/L = Micrograms per liter, equivalent to parts per billion (ppb)$ 

<sup>(</sup>a) RWQCB Risk-Based Screening Levels (drinking water resource threatened/not threatened) (RWQCB, 2000).

<sup>(</sup>b) Lowest of chronic and acute surface water criteria published by the State of California, U.S. Environmental Protection Agency, or U.S. Department of Energy.



25-53-20

Table 3
Groundwater Sample Analytical Results
Natural Attenuation Indicators – September 24, 2002
Redwood Regional Park Corporation Yard, Oakland, California

Sample I.D.	Nitrogen (as Nitrate) (mg/L)	Sulfate (mg/L)	Dissolved Oxygen (mg/L)	Ferrous Iron (mg/L)	Redox Potential (milliVolts)
MW-1	NA	NA	1.0	0.0	198
MW-2	NA	NA	2.0	0.0	198
MW-3	<0.05	37	0.5	0.0	130
MW-4	0.57	55	15.9	0.0	228
MW-5	NA	NA	1.1	0.0	216
MW-6	NA	NA	0.4	0.0	243
MW-7	<0.05	1.9	0.2	2.4	-117
MW-8	<0.05	86	0.3	0.8	138
MW-9	0.32	72	2.9	1.6	236
MW-10	0.21	64	14.5	0.0	213
MW-11	<0.05	3.7	2.4	4.4	-103

Notes:

mg/L = Milligrams per liter, equivalent to parts per million (ppm)

NA = Not analyzed

degradability of petroleum hydrocarbons, remediation by natural attenuation has been found to be a viable option for addressing many hydrocarbon plumes, replacing the need for active remediation. However, such natural attenuation only occurs if the concentration of hydrocarbons is low enough to facilitate the infiltration of natural oxygen through the interstitial space around the contamination, supporting the microorganisms for which the contamination is a food source (thus "attenuating" it). The concentration in soil or groundwater above which natural attenuation is unlikely to take place is still the subject of various research studies. In general, biodegradation of petroleum hydrocarbons in groundwater has a significant role in creating a stable plume and minimizing groundwater plume configuration and concentrations over time. Evidence of the historical occurrence and potential for future occurrence of biodegradation can be obtained from analysis of groundwater for specific biodegradation-indicator parameters, including dissolved oxygen, oxidation-reduction potential, and general mineral analyses.

#### **Dissolved Oxygen**

Dissolved oxygen (DO) is the most thermodynamically-favored electron acceptor used in aerobic biodegradation of hydrocarbons. Active aerobic biodegradation of petroleum hydrocarbon compounds requires at least 1 to 2 mg/L of DO in groundwater. During aerobic biodegradation, DO levels are reduced in the hydrocarbon plume as respiration occurs. Therefore, DO levels that vary inversely to hydrocarbon concentrations are consistent with the occurrence of aerobic biodegradation.

Current monitoring event DO concentrations ranged from 0.2 mg/L to 15.9 mg/L. The highest concentrations of total hydrocarbons in the current quarter were in wells MW-7, MW-8, MW-9, and MW-11. Dissolved oxygen in these wells ranged from 0.2 to 2.9 mg/L. In wells with little or no hydrocarbon contamination (e.g., MW-1, MW-2, MW-3, MW-5, and MW-6), similar DO concentrations were observed. Only wells MW-4 and MW-10 showed elevated DO concentrations of 15.9 and 14.5 mg/L, respectively, which may be a function of localized supersaturation at these wells resulting from the ORC<sup>TM</sup> injection.

#### **Oxidation-Reduction Potential**

The oxidation-reduction potential (ORP — a.k.a. redox potential) of groundwater is a measure of electron activity, and is an indicator of the relative tendency of a solute species to gain or lose electrons. The ORP of groundwater generally ranges from -400 millivolts (mV) to +800 mV. In oxidizing (aerobic) conditions, the ORP of groundwater is positive while in reducing (anaerobic) conditions, the ORP is typically negative (or less positive). Therefore, ORP values of groundwater inside a hydrocarbon plume are typically less than those measured outside the plume. Of the four wells with pronounced hydrocarbon contamination (MW-7, MW-8, MW-9, and MW-11), the ORP values ranged from -117 mV to +236 mV. Other wells with little or no contamination showed positive ORP values ranging from +130 mV to +243 mV. Thus, the ORP values in this field event showed a general inverse correlation with hydrocarbon concentrations, although similar ORP values for some contaminated vs. non-contaminated wells are inconsistent with the expected trend.

#### **General Mineral Analyses**

An inverse relationship between general minerals—including ferrous iron ( $Fe_2^+$ ), nitrate ( $NO_3^-$ ), and sulfate ( $SO_4^{2^+}$ )—and hydrocarbon concentrations is also indicative of the occurrence of biodegradation. Specifically, anaerobic degradation and oxidation of compounds is implied where general mineral concentrations are low and hydrocarbon concentrations are high. In the current site monitoring event, neither the  $Fe_2^+$  nor the  $SO_4^{2^-}$  results showed the expected inverse correlation with hydrocarbon concentrations. Nitrate concentrations showed a viable correlation.

### QUALITY CONTROL SAMPLE ANALYTICAL RESULTS

Laboratory QC samples (e.g., method blanks, matrix spikes, surrogate spikes, etc.) were analyzed by the laboratory in accordance with requirements of each analytical method. All laboratory QC sample results and sample holding times were within the acceptance limits of the methods (see Appendix B).

# 6.0 SUMMARY, CONCLUSIONS, AND PROPOSED ACTIONS

The following conclusions and proposed actions are focused on the findings of the current event activities, as well as salient historical findings.

#### **SUMMARY AND CONCLUSIONS**

- Groundwater sampling has been conducted approximately on a quarterly basis since November 1994 (23 events in the original wells).
- Current site groundwater contaminant concentrations exceed their respective groundwater RBSLs (both for cases in which the drinking water resource is and is not threatened)—with the exception of toluene, which does not exceed either set of criteria. Site groundwater contaminant concentrations also exceed all surface water screening levels, with the exception of toluene and MTBE.
- The groundwater contaminant plume has become disconnected from the former source, and has migrated well beyond the former source area (represented by well MW-2) toward Redwood Creek. The zone of greatest groundwater contamination (TPHg greater than 3,500 μg/L) is centered around wells MW-7, MW-9, and MW-11 in the downgradient portion of the site (immediately upgradient of the creek). The area of groundwater contamination in excess of screening level criteria appears to be no greater than 70 feet long by 50 feet wide, which is significantly reduced relative to pre-ORC<sup>TM</sup> injection conditions. Maximum groundwater concentrations for the majority of the contaminants have reached the most downgradient wells (just upgradient of the creek). Continued discharge of elevated concentrations could continue for at least several years if unabated.
- Hydrochemical (contaminant and dissolved oxygen) trends indicate that the first phase of the ORC<sup>TM</sup> injection (September 2001) was generally successful in increasing DO levels and reducing groundwater contaminant concentrations, although the active life of the ORC<sup>TM</sup> appears to have been exceeded between the second and third post-injection events in some of the wells. A second phase of the ORC<sup>TM</sup> injection, conducted in July 2002, appears to have been effective in controlling the lateral limits of the plume, although it has not been wholly effective in reducing the magnitude of contamination within the centerline of the plume.
- The only contaminant detected in site surface water (creek samples) above screening-level criteria was gasoline (at 590  $\mu$ g/L—the RBSL is 500  $\mu$ g/L). Other contaminants detected in

the creek surface water sample (below screening-level criteria) included diesel, benzene, and ethylbenzene.

■ The existing well layout fully constrains the lateral extent of groundwater contamination, and the vertical limit is very likely the top of the near-surface siltstone bedrock. The saturated interval extends approximately 12 to 15 feet from top of bedrock through the capillary fringe.

#### PROPOSED ACTIONS

The EBRPD proposes to implement the following actions to address regulatory concerns:

■ Continue the quarterly program of creek and groundwater sampling and reporting, including evaluating future groundwater and surface water analytical results in the context of the need for additional corrective action.

### 7.0 REFERENCES AND BIBLIOGRAPHY

- California State Water Resources Control Board, 1989. Leaking Underground Fuel Tank Field Manual: Guidelines for Site Assessment, Cleanup, and Underground Storage Tank Closure. State of California Leaking Underground Fuel Tank Task Force. October.
- Parsons Engineering Science (Parsons), 1998. Quarterly Progress Report 11, Redwood Regional Park Service Yard, Oakland, California. January 28.
- Parsons, 1997a. Quarterly Progress Report 7, Redwood Regional Park Service Yard, Oakland, California. January 31.
- Parsons, 1997b. Quarterly Progress Report 8 and Annual Summary Assessment, Redwood Regional Park Service Yard, Oakland, California. April 4.
- Parsons, 1997c. Quarterly Progress Report 9, Redwood Regional Park Service Yard, Oakland, California. June 30.
- Parsons, 1997d. Quarterly Progress Report 10, Redwood Regional Park Service Yard, Oakland, California. September 22.
- Parsons, 1996a. Quarterly Progress Report 5, Redwood Regional Park Service Yard, Oakland, California. June 6.
- Parsons, 1996b. Quarterly Progress Report 6, Redwood Regional Park Service Yard, Oakland, California. September 24.
- Parsons, 1995a. Quarterly Progress Report 2, Redwood Regional Park Service Yard, Oakland, California. March 8.
- Parsons, 1995b. Quarterly Progress Report 3, Redwood Regional Park Service Yard, Oakland, California. June 23.
- Parsons, 1995c. Quarterly Progress Report 4 and Annual Summary Assessment (November 1994

   August 1995), Redwood Regional Park Service Yard, Oakland, California. November

   13.

- Parsons, 1994a. Creek and Soil Sampling at Redwood Regional Park, Oakland, California. March 2.
- Parsons, 1994b. Creek Surface Water at Redwood Regional Park, Oakland, California. May 13.
- Parsons, 1994c. Workplan for Groundwater Characterization Program at East Bay Regional Park Service Yard, Oakland, California. August 17.
- Parsons, 1994d. Quarterly Progress Report 1, Redwood Regional Park Service Yard, Oakland, California. December 28.
- Parsons, 1993a. Closure of Underground Fuel Storage Tanks and Initial Site Characterization at Redwood Regional Park Service Yard, Oakland, California. December 16.
- Parsons, 1993b. Workplan for Site Characterization at East Bay Regional Park District, Redwood Regional Park Corporation Yard, Oakland, Alameda County, California. September 3.
- Regional Water Quality Control Board, San Francisco Bay Region, 2000. Application of Risk-Based Screening Levels and Decision Making to Sites With Impacted Soil and Groundwater, Interim Final. August.
- Stellar Environmental Solutions (SES), 2002a. Year 2001 Annual Summary Report, Redwood Regional Park Service Yard, Oakland, California. January 15.
- SES, 2002b. First Quarter 2002 Site Monitoring Report, Redwood Regional Park Service Yard, Oakland, California. April 16.
- SES, 2002c. Second Quarter 2002 Site Monitoring Report, Redwood Regional Park Service Yard, Oakland, California. July 23.
- SES, 2001a. Monitoring Well Installation and Site Monitoring Report, Redwood Regional Park Service Yard, Oakland, California. February 8.
- SES, 2001b. Site Monitoring Report, Redwood Regional Park Service Yard, Oakland, California. May 4.
- SES, 2001c. Well Installation, Site Monitoring, and Corrective Action Report, Redwood Regional Park Service Yard, Oakland, California. October 26.
- SES, 2000a. Site Monitoring Report, Redwood Regional Park Service Yard, Oakland, California. April 21.

- SES, 2000b. Workplan for Groundwater Monitoring Well Installations, Redwood Regional Park Service Yard, Oakland, California. October 19.
- SES, 2000c. Site Monitoring Report, Redwood Regional Park Service Yard, Oakland, California. October 19.
- SES, 2000d. Site Feasibility Study Report, Redwood Regional Park Service Yard, Oakland, California. October 20.
- SES, 1999a. Workplan for Subsurface Investigation, Redwood Regional Park Service Yard, Oakland, California. April 8.
- SES, 1999b. Residual Contamination Investigation and Remedial Action Assessment Report, Redwood Regional Park Service Yard, Oakland, California. June 9.
- SES, 1998a. Workplan for Continued Site Investigation and Closure Assessment, Redwood Regional Park Service Yard, Oakland, California. October 9.
- SES, 1998b. Site Investigation and Closure Assessment Report, Redwood Regional Park Service Yard, Oakland, California. December 4.

### 8.0 LIMITATIONS

This report has been prepared for the exclusive use of the East Bay Regional Park District, its authorized representatives, and the regulatory agencies. No reliance on this report shall be made by anyone other than those for whom it was prepared.

The findings and conclusions presented in this report are based on the review of previous investigators' findings at the site, as well as onsite activities conducted by SES since September 1998. This report provides neither a certification nor guarantee that the property is free of hazardous substance contamination. This report has been prepared in accordance with generally accepted methodologies and standards of practice. The SES personnel who performed this limited remedial investigation are qualified to perform such investigations and have accurately reported the information available, but cannot attest to the validity of that information. No warranty, expressed or implied, is made as to the findings, conclusions, and recommendations included in the report.

The findings of this report are valid as of the present. Site conditions may change with the passage of time, natural processes, or human intervention, which can invalidate the findings and conclusions presented in this report. As such, this report should be considered a reflection of the current site conditions as based on the investigation and remediation completed.

# WELL GAUGING DATA

Project #_	OSO TENADNES	Date _	9-24-12	_ Client	Stellar Environmenta	1
-						

# Site Redwood Projenal Park Service Yard Oakland

Well ID	Well Size (in.)	Sheen / Odor		Thickness of Immiscible Liquid (ft.)	Volume of Immiscibles Removed (ml)	Depth to water (ft.)	Depth to well bottom (ft.)	Survey Point: TOB or TOC	Daloep/Fr	(a) (a)
mw-1	4					4.47	18.85		1.0/198/0	
mw-2	4					24.34	38.82		20/235/6	54
mw·3	4		·			23.61	44.10		0.5/170/6	53
MW-Y	4					14.65	26.51		0.5/130/6	53
mws	У				·	16.94	26.92		1.1/216/0	53
mv-6	4					13.82	27.93		0.4/243/	6 S
mw7	2					14.24	25.33		0.4/243/0.2/138/	12.
mw-f	2	odor				13.75	22.21		0.3/138/	0.8
mw-9	2					14.15	26.00		2.9/25/1	6
MW-B	2					13.55	28.75	1 1	Just 3	<u>ا</u> ۲
mwii	2	oder				16.19	26.00	U	2.4/-103/	4.4
-										
7										

Blaine Tech Services, Inc. 1680 Rogers Ave., San Jose, CA 95112 (408) 573-0555

WELL	MONITORING DATA	SHEET

		<b>V</b> V	ELL MUNICIPAL	CORUNG DAI	a soleli	
Project #	1: 02092	4-0w-	1	Client: Stell	lar Environn	mentalo Redwood Rog
Sampler	: Dave	Walb.	er	Start Date:		10
Well I.D				Well Diameter	r: 2 3 <u>(</u> 4	68
Total W	ell Depth:	18.85	<u>=</u> :	Depth to Wate	r: 4.47	
Before:		After:		Before:		After:
Depth to	Free Produ	ct:		Thickness of F	ree Product (f	eet):
Referenc	ed to:	#VC)	Grade	D.O. Meter (if	req'd):	(AST) HACH
Purge Meth	Bailer  Disposable Ba  Middleburg  Electric Subme	ersible	Waterra Peristaltic Extraction Pump Other	Sampling Method:  Other:  Well Diametr  1" 2" 3"	Disposable Bailer Extraction Port Dedicated Tubing	Niameter Multiplier 0.65 1.47
Time	Temp. (°F or °C)	pН	Conductivity (mS or µS)	Turbidity (NTU)	Gals. Removed	Observations
Did well	devxater?	Yes	No	Fer Gallons actually	rous Icon=	0
Sampling	<del></del>	<u> </u>				
Sample I.				Sampling Date:	7-24-0.	<del>\</del>
<del></del>	for: (PH-O	ATEN (		Laboratory: C	. \	mpkins
	t Blank I.D	<del></del>		Other: Witrake Duplicate I.D.	1 24 1746	
	for: TPH-G		<del></del>	Other:		
).O. (if re	q'd):		Pre-purge:	). D mg/L	Post-purge:	mg/L
RP (if re	:q'd):		Pre-purge:	198 mV	Post-purge:	mV

Blaine Tech Services, Inc. 1680 Rogers Ave., San Jose, CA 95112 (408) 573-0555

		v	VELL MONT	TORING DAT	A SHEET	
Project	#: 02093	24-0w-	1	Client: 54e	Var Environ	mental @ Rodwood Rog
Sampler	: Dave	Walt	er	Start Date:		74
Well I.D	).: mw-2				· ·	0 6 8
Total W	ell Depth:	38.82		Depth to Wate	<del></del>	
Before:		After:		Before:		After:
Depth to	Free Produ	ict:		Thickness of I	Free Product (f	<del></del>
Referenc	ed to:	AVC)	Grade	D.O. Meter (if		(KST) HACH
Purge Meti	nod: Bailer Disposable Ba Middleburg Electric Submo		Waterra Peristaltic Extraction Pump Other	Sampling Method Other	Disposable Bailer Extraction Port Dedicated Tubing	
Gals.		3	= 28.7	1"	0.04 4" 0.16 6"	0.65 1.47 ner radius <sup>2 e</sup> 0.163
Time	Temp. (°F or °C)	рН	Conductivity (mS or us)	Turbidity (NTU)	Gals. Removed	Observations
12156	71.0	7,1	773	25	10	
17:58	65,1	7.1	820	7200	20	cloudy
13100	64.9	71	833	7200	30	
		•				
					Ferrow Dronz	Ö
oid well	lewater?	Yes (	No	Gallons actuall		30
ampling	Time: [3	:06		Sampling Date:	9-24-0	2
ample I.I	D.: MW	- }_		Laboratory: C	uctist To	naki-e
nalyzed	for: (PH-G	(TEX)	твв (грн-д)	Other:	Lande	(A)
quipmen	t Blank I.D.		@	Duplicate I.D.:	\\	
nalyzed	for: TPH-G	BTEX M	TBE TPH-D (	Other:		
.O. (if re	g'd):		Pre-purge:	O mg/L	Post-purge:	ing/L
RP (if re	q'd):		Pre-purge:	198 mV	Post-purge:	mV
						·· '

Biaine Tech Services, Inc. 1680 Rogers Ave., San Jose, CA 95112 (408) 573-0555

WELL	MON	TTOR	INC D	ATA	SHEET
******	/ 171 <b>(</b> ) 1				

		Ψ'	1 TO TAKE 1 1 TO 1 1 T		G DAI	a sileli			
Project #	1: 02092	4-0w-	1	Client	Stell	lar Environm	mental o Rodwood	R	
Sampler	: 02092 : Dave	Walt	er	Start Date: 9-24-02					
Well I.D.: mw-3 Total Well Depth: 44,10					Well Diameter: 2 3 4 6 8  Depth to Water: 23.61				
Depth to	Free Produc	ot:	## ###################################	Thickness of Free Product (feet):					
Referenc	ed to:	PVC	Grade	D.O. N	leter (if	req'd):	(KST) HACH		
	od: Bailer Disposable Bail Middleburg Electric Submer	rsible	Waterra Peristaltic Extraction Pump Other	Samplin	g Method:	Bailer Disposable Bailer Extraction Port Dedicated Tubing er Multiplier Wo 0.04 4° 0.16 6°	II Diameter Multiplier		
Gals.	T		Ta			0.37 OI	nei 170105 - 0.163		
Time	Temp. (°F or °C)	рН	Conductivity (mS or µS)			Gals. Removed	Observations	,	
10:23		7.5	980	85				_	
Did well o	iovator?	V	N			Ferrous Iru	50		
		Yes				y evacuated:			
	Time: 10:	<del></del>	<u> </u>	Samplir	g Date:	9-24-0. urlist To	<u></u>		
•	D.: MWI	1	0 h	Laborat	ory: C	urtist To	mpkins	,	
	for: The		and they	Other:	/itrate	1 sulfate			
quipmen	t Blank I.D.	<u> </u>	@ Time	Duplica	te I.D.:				
nalyzed	for: TPH-G	BTEX N	ATBE TPH-D (	Other:					
).O. (if re	q'd):		Pre-purge:	0.9	mg/ <sub>L</sub>	Post-purge:	mg	L.	
RP (if re	q'd):		Pre-purge:	130	mV	Post-purge:		ıV	
						F Ga.			

Blaine Tech Services, Inc. 1680 Rogers Ave., San Jose, CA 95112 (408) 573-0555

WELL MONITORING DATA SHEET	
Project #: 020924-0w-1 Client: Stellar Environmental @ Rolwood!	5~
Sampler: Dave Walter Start Date: 9-24-02	7~
Well I.D.: mw- 4 Well Diameter: 2 3 4 6 8	
Total Well Depth: 26.5) Depth to Water: 14.65	
Before: After: Before: After:	
Depth to Free Product: Thickness of Free Product (feet):	
Referenced to: Grade D.O. Meter (if req'd): (151) HACH	
Purge Method:  Bailer  Waterra  Disposable Bailer  Disposable Bailer  Peristaltic  Middleburg  Batraction Pump  Dedicated Tubing  Electric Submersible  Other  Well Diameter  Multiplier  Multiplier	<del></del> -1
$\frac{7}{1} \frac{7}{1} \text{ (Gals.) X} \frac{3}{3} = \frac{27}{1} \frac{1}{1} \frac{0.04}{2^{11}} \frac{4^{11}}{0.16} \frac{0.65}{6^{11}} \frac{1.47}{1.47}$ Gals.	
Time Temp. Conductivity (mS or (S) Turbidity (NTU) Gals. Removed Observations	
13:20 70.9 8.8 797 7200 8 Cloudy	
13:21 64.3 8.9 676 7000 16	
13-23 623 9.0 665 7200 24	7
	7
Ferrons Iron = 0	ヿ
Did well dewater? Yes (No) Gallons actually evacuated: 24	$\exists$
Sampling Time: 13: 28 Sampling Date: 9-24-02	$\exists$
Sample I.D.: phw. 4 Laboratory: Curtist Tompkins	7
Analyzed for: (PH-G) NTEX (TBB) (PH-D) Other: Nitrate   Salfate	$\dashv$
Equipment Blank I.D.; @ Duplicate I.D.;	7
Analyzed for: TPH-G BTEX MTBE TPH-D Other:	$\dashv$
O.O. (if req'd):  Pre-purge:   5,9 mg/L   Post-purge:   mg/L	7
ORP (if req'd): Pre-purge: 23% mV Post-purge: m'	7

Blaine Tech Services, Inc. 1680 Rogers Ave., San Jose, CA 95112 (408) 573-0555

BEVINE LECH SERVICES Fax:1+408+573+7771 Oct 4 2002 8:34 P.UB

#### WELL MONITORING DATA SHEET

	YY OWNIG DUIL				
24-0w-1	Client: Stell	lar Environmente	lo Redwood Re		
		Start Date: 9-24-02			
	Well Diameter: 2 3 4 6 8				
26.92	Depth to Water	Depth to Water: 16.94			
After:	Before:	Before: After:			
ıct:	Thickness of Free Product (feet):				
PVC) Grade	D.O. Meter (if				
Extraction Pum	Other:	Disposable Bailer Extraction Port Dedicated Tubing	de Multiplier		
3 =	1" 2* 3*	0.04 4* 0.16 6" 0.37 Other	0.65 1.47 radius <sup>2</sup> • 0.163		
1 i	' [	Gals. Removed	Observations		
		Ferrous Fra	on =0		
Yes No	Galions actually		on =0		
Yes No	Sampling Date:	y evacuated: 9-24-0-2			
Yes No	Sampling Date:	y evacuated: 9-24-0-2			
Yes No	Sampling Date:	y evacuated: 9-24-03 uctist Tompk			
	Sampling Date:	y evacuated: 9-24-03 uctist Tompk			
NIEW (IPH-D)	Sampling Date:  Laboratory: Control  Other: Vitrate	y evacuated: 9-24-03 uctist Tompk			
Time	Sampling Date: Laboratory: Conternation District Laboratory: Content District Laboratory: Content Laborato	y evacuated: 9-24-03 uctist Tompk			
	Walter  26.92  After:  OCC Grade  Waterra Peristaltic Extraction Pum Other  Conductivity	Well Diameter  26.92 Depth to Wate  After: Before:  Ict: Thickness of F  Orade D.O. Meter (if  Sampling Method:  Waterra  Peristaltic Extraction Pump Other  Conductivity  Conductivity	Well Diameter: 2 3 4  26.92 Depth to Water: 16.94  After: Before: After:  Thickness of Free Product (feet):  Office D.O. Meter (if req'd): After:  Sampling Method: Bailer  Disposable Bailer  Extraction Port  Dedicated Tubing  Other  Well Diameter Multiplier Well Diameter  Well Diameter Multiplier Well Diameter  Well Diameter Multiplier Well Diameter  Conductivity  Conductivity		

Biaine Tech Services, Inc. 1680 Rogers Ave., San Jose, CA 95112 (408) 573-0555

		W	ELL MONI	TORING DATA SHEET			
Project #: 020924-0w-1				Client: Stellar Environmental & Redwood	Region		
Sampler: Dave Walter Well I.D.: MW-6 Total Well Depth: 27.93				Start Date: 9-24-02			
				Well Diameter: 2 3 4 6 8  Depth to Water: 13,82			
							Before: After:
Depth to Free Product:				Thickness of Free Product (feet):			
Referenc	ed to:	PVC)	Grade	D.O. Meter (if req'd): (YSI) HACH			
Purge Meth	dd: Bailer Disposable Bai Middieburg Electric Subme		Water a Peristaltic Extraction Pump Other	Sampling Method: Bailer Disposable Bailer Extraction Port Dedicated Tubing Other: Well Diameter Multiplier			
Gals.	_(Gais.) X	3	=	3" 0.04 4" 0.65 2" 0.16 6" 1.47 3" 0.37 Other radius <sup>2</sup> * 0.163			
Time	Temp. (°F or °C)	рН	Conductivity (mS or µS)	Turbidity (NTU) Gals. Removed Observations			
Did well o	iewater?	Yes	No	Gallons actually evacuated:			
Sampling	Time:\		·-	Sampling Date: 9-21-027			
Sample I	<del></del>			Laboratory: Curtist Tompkins			
	for: (PH-)	STEX)	твр (грн-р)	Other: Nitrate   Sulfate			
- '	t Blank I.D.		0	Duplicate I.D.;			
Analyzed	for: TPH-G	BIEX M	$\overline{}$	Other:	$\dashv$		
D.O. (if re	:q'd):		Pre-purge:	O, 4 mg/L Post-purge: mg/	/1		
ORP (if re	:q'd):		Pre-purge:	2112	nV		

Blaine Tech Services, Inc. 1680 Rogers Ave., San Jose, CA 95112 (408) 573-0555

BEANNE TECH SERVICES Fax: 1+408+573+7771 0ct 4 2002 8:35 P.08

			VELL MONI	TORING DAT	TA SHEET	_			
Project #	#: 0209.	24-0W-	-1	Client: 54	Client: Stellar Environmental & Redwood Res				
Sampler	: Dave	Walt	ar	Į.	9-24-02	12			
Well I.D	" MW	7		Well Diamet		6 8			
Total We	ell Depth:	25,33	<u>-</u> -	* <del></del>	ter: 14.24				
Before:		After:		Before:		After:			
Depth to	Free Produ	act:		Thickness of	Free Product (f				
Referenc	ed to:	₹VC)	Grade	D.O. Meter (i		(KST) HACH			
Purge Meth	eod: Bailer Disposable Ba Middleburg Electric Subro		Waterra Peristaltic Extraction Pump Other	Sampling Method Othe	Disposable Bailer Extraction Port Dedicated Tubing	· 			
Cals.	_(Gals.) X	3	- <u>s.</u> y	Well Diam J' 2° 3"	0.04 4* 0.16 6* 0.37 Oth	Dismeter Multiplier   0.65   1.47   1.63			
Time	Temp.	рН	Conductivity (mS or as)	Turbidity (NTU)	Gals. Removed	Observations			
14:34	66.3	7.2	680	7200	2	odor Bion			
14:36	63.2	7.1	690	7200	Ч	grad			
14:38	61.5	7.0	692	7200	6	11.69			
					Ferrous	Tran= 2.4			
id well d	ewater?	Yes	(No)	Gallons actuall	y evacuated:	6			
ampling	Time: [4	: 44		Sampling Date	9-24-03				
ample I.L	D.: M4	V-7	]	Laboratory: C	urtist Ton	ak: e			
nalyzed f	for: (PH-G	TEX)	TBB (PH-D)	Other: Nitrate	1 sulfate	PRIN			
quipment	Blank I.D.	.:	@	Ouplicate I.D.:					
nalyzed f	or: TPH-G	BTEX M		Other:	-				
O. (if rec	η'd):		Pre-purge:	O, 2 mg/L	Post-purge:	mg/L			
RP (if req	 l'd):		Pre-purge:	-117 mV	Post-purge:	mV			

Blaine Tech Services, Inc. 1680 Rogers Ave., San Jose, CA 95112 (408) 573-0555

Project:	#: 0209.	24-Dw	1	Client: 54	1/ar Environ	mental o Redwood				
Sampler	: Dave	Walt	er	1	9-24-02					
Well I.L	).: Mw-	4			Well Diameter: (2') 3 4 6 8					
Total W	ell Depth:	22.21		Depth to War	ter: 13.75					
Before:		After:		Before:		After:				
Depth to	Free Produ	uct:		Thickness of	Free Product (f	eet):				
Reference	ed to:	AVC)	Grade	D.O. Meter (i		(KST) HACH				
Purge Meth	Bailer Disposable Ba Middleburg Electric Subm		Waterra Peristaltic Extraction Pump Other	Sampling Method	Disposable Bailer Extraction Port Dedicated Tubing	; 				
J. U.	_(Gals.) X	3	= 4.2	Well Diami	0.04 4* 0.16 6* 0.37 Oth	1 Djamoter <u>Multipljer</u> 0.65 1.47 ner radius <sup>2 a</sup> 0.163				
Time	Temp.	рН	Conductivity (mS or mS)	Turbidity (NTU)	Gals. Removed	Observations				
14110	65,6	7.4	744	7200	1.5	Brown				
1411	63.6	7.4	7.58	7200	3,0					
14113	62.1	7.3	765	7200	4.5					
id well d	00004002		0		Ferron	Fron= 0.8				
	<del></del>				y evacuated:					
	Fime: 141			Sampling Date:	9-24-02					
	): mur b		$\sim$	Laboratory: C	urtist Tom	pkins				
	or: (PH-G		TBB (IPH-D) (	Other: Nitrate	1 sulfafe					
	Blank I.D.	······································	Time	Duplicate I.D.:						
	or: TPH-G	BTEX M	TBE TPH-D (	Other:						
O. (if req			Pre-purge:	0,3 me/L	Post-purge:	mg/ <sub>L</sub>				
RP (if req	(d):		Pre-purge:	138 mV	Post-purge:					

Fax:1+408+573+7771

BLAINE TECH SERVICES

01.q

0cf 4 2002 8:36

من المنافي المنافي في من من من المنافية المنافية المنافية المنافية المنافية المنافقة المنافقة المنافقة المنافقة	WELL MONI	TORING DATA SHEET					
Project #: 020924-0	w-1	Client: 5/e/	lar Environm	ental o Redwood Re-			
Sampler: Dave Wa		Start Date:		7-			
Well I.D.: MW-9			: (2) 3 4	6 8			
Total Well Depth: 16.00	0	Depth to Wate	r: /4.15				
Before: After		Before:		After:			
Depth to Free Product:		Thickness of F	ree Product (fe	et):			
Referenced to:	Grade	D.O. Meter (if		KSI HACH			
Purge Method:  Bailer  Disposable Bailer  Middleburg  Electric Submersible	Waterra Peristaltic Extraction Pump Other	_ Other:	Disposable Bailer Extraction Port Dedicated Tubing				
Gals.) X	= 5,7	Well Diamete 1" 2" 3"	er <u>Multiplier</u> Well 0.04 4" 0.16 6" 0.37 Oth	Diameter Multiplier   0.65   1.47     radius <sup>2</sup> * 0.163			
Time Temp.  Time Por °C) pH	Conductivity (mS of $\mu$ S)	Turbidity (NTU)	Gals. Removed	Observations			
12:30 640 9.4	652	>200	2	Prioun/ador			
1234 620 8.3		7200 4		, , , , ,			
12131 61.3 7.3	835	>200	6				
12:39 60.6 7.2	2 846	7.200	8				
			Ferrous Iron	= 1.6			
Did well dewater? Yes	(No)	Gallons actually					
Sampling Time: ():40							
Sample I.D.: MW-9		Sampling Date: 9-24-02  Laboratory: Curtist Tompkins					
Analyzed for: (PH-G) FTEX	(TBB (TPH-D)	Other: Nitrate / Sulfate					
	@ Time	Duplicate I.D.:					
Equipment Blank I.D.:	Time	Duplicate I.D.: Other:					
Equipment Blank I.D.:  Analyzed for: TPH-G BTEX  D.O. (if req'd):	Time		Post-purge:	mg/L			

Blaine Tech Services, Inc. 1680 Rogers Ave., 5an Jose, CA 95112 (408) 573-0555

Project	#: 0209.	24-0W	1	Client: Stellar Environmental @ Redwood & Start Date: 9-24-02					
Sample	r: Dave	Walt	,er						
Well I.I	D.: MW1	O			er: <del>(2</del> ) 3 4	6 8			
Total W	ell Depth:	28,75			ter: 13.55				
Before:		After:		Before:		After:			
Depth to	Free Produ	ıct:		Thickness of	Free Product (fe				
Referen	ced to:	PVC	Grade	D.O. Meter (i		(KST) HACH			
Purge Met	Bailer Disposable Ba Middleburg Electric Subme		Waterra Peristaltic Extraction Pump Other	Sampling Method Other	Disposable Bailer Extraction Port Dedicated Tubing				
2. (		3	- 7.2	1,4	0.04 4" 0.16 6" 0.37 Oth	Dismeter         Multiplier           0.65         1.47           er         radius² * 0.163			
Time	Temp.	pН	Conductivity (mS or us)	Turbidity (NTU)	Gals. Removed	d Observations			
3:46	69.	8.8	771	7.200	25	Brown			
13:49	65,7	8.7	756	7200	50				
7:51	63.6	8.8	736	7200	7.5-				
	·								
					Ferrous Iron=	<u> </u>			
<u>-</u>		Yes -	No)	Gallons actually	y evacuated: 7				
mpling		57		Sampling Date:	9-24-02	_			
mple I.I			I	Laboratory: C	artist Tom	ak:			
nalyzed:	for: (PH-G	ETEX)	твв (грн-р) с	Other: Witrate	1 Sulfate	VK.B)			
uipmen	Blank I.D.	<del></del>	@ <del></del>	Ouplicate I.D.:					
alyzed i	or: трн-G	BTEX M		ther:					
O. (if red	q'd):		Pre-purge:	14.5 mg/L	Post-purge:	mg/ <sub>L</sub>			
P (if rec			Pre-purge:	213 mV	т กละ-ทิศเลิส:	- 1 <sub>L</sub>			

BEWINE LECH SEBAICES Lax:1+408+573+7771

P.12

16:8

7007 \$ 100

	V	VELL MONI	TORING DAT	A SHEET				
Project #: 020	924-Ow-	1	Client: Ste	Var Environn	vental @ Redwood Rog			
Sampler: Dav	c Walt	er	Start Date:		/^			
Well I.D.: Mu			Well Diamete		6 8			
Total Well Depth			Depth to Wate	er: 16.19				
Before:	After:		Before:	1041)	After:			
Depth to Free Pro	duct:		Thickness of I	Free Product (fe				
Referenced to:	P(C)	Grade	D.O. Meter (if		(KST) HACH			
Purge Method:  Bailer  Disposable  Middleburg  Electric Su	g	Waterra Peristaltic Extraction Pump Other	Other	Disposable Bailer Extraction Port Dedicated Tubing	_			
Gals.) X	3	- 4,8	Well Diamet	o.04 4" 0.16 6" 0.37 Oth	<u>Diameter Multiplier</u>   0.65   6.47   er   radius <sup>2</sup>   0.163			
Time For °C		Conductivity (mS or \(\mu \text{S}\)	Turbidity (NTU)	Gals. Removed	Observations			
14:56 67.0	6.9	931	5000	1.6	stor/gray			
14:58 63.2	7.6	964	7700	5.2	70			
15:00 G1.1	7,1	969	7200	4.8				
				·				
				Ferious Iron	-4.4			
Did well dewater?	Yes	Ño	Gallons actually	y evacuated:	4.8			
Sampling Time:	15105		Sampling Date:	9-24-02	_			
Sample I.D.: M	W-11		Laboratory: C	uctist To	ok:			
Analyzed for: (FPH	TEX) (	(TBB (PH-D)	Other: V; +rate	1 sulfate	See (a)			
Equipment Blank I	.D.;	<b>@</b>	Duplicate I.D.:					
analyzed for: трн	-G BTEX M	<u> </u>	Other:					
O.O. (if req'd):		Pre-purge:	2 4 mg/L	Post-purge:	mg/L			
ORP (if req'd):		Pre-purge:	-103 mV	Post-purge:	mV			
					'			

Blaine Tech Services, Inc. 1680 Rogers Ave., San Jose, CA 95112 (408) 573-0555 

# WELLHEAD INSPECTION CHECKLIST AND REPAIR ORDER

Client 5	fellar Engless Redwood	vironmental Solutions	Inspection Date Service Yard Inspected By	9-24-02 ave Wa	Her
1. Lid on bo. 2. Lid broke 3. Lid bolts of 4. Lid bolts of 9. Lid seal bolts	x? n? missing? stripped?	6. Casing secure? 7. Casing cut level? 8. Debris in wellbox? 9. Wellbox is loo far above grade? 10. Wellbox is too far below grade? 11. Wellbox is crushed/damaged?	12. Water standing in wellbox? 12a. Standing above the top of casing? 12b. Standing below the top of casing? 12c. Water even with the top of casing? 13. Well cap present? 14. Well cap found secure?	15. Well cap t	unctional? be pulled loose? seal out water? resent?
Well I.D.	Check box if	no deficiencles were found.	Note below deficiencies you were Corrective Action Taken	e able to co	rrect.
				<del>_</del>	
	]		·		
					<u> </u>
Note below	w all defiencies i	that could not be corrected and	still need to be corrected.		
Well i.D.	Persisting Defic	ciency	BTS Office assigns or defers Correction to:	Date assigned	Date corrected
			000000000000000000000000000000000000000	baaigiieu	Contected
	<u> </u>				
L				1	



# Curtis & Tompkins, Ltd., Analytical Laboratories, Since 1878

2323 Fifth Street, Berkeley, CA 94710, Phone (510) 486-0900, Fax (510) 486-0532

#### ANALYTICAL REPORT

Prepared for:

Stellar Environmental Solutions 2198 6th Street Suite 201 Berkeley, CA 94710

Date: 09-OCT-02 Lab Job Number: 160913

Project ID: 020924-DW-1

Location: Redwood Regional Park

This data package has been reviewed for technical correctness and completeness. Release of this data has been authorized by the Laboratory Manager or the Manager's designee, as verified by the following signatures. The results contained in this report meet all requirements of NELAC and pertain only to those samples which were submitted for analysis.

Reviewed by:

Project Manager

Reviewed by:

anions Manager

This package may be reproduced only in its entirety.

NELAP # 01107CA

Page 1 of \_\_\_\_\_\_\_



Laboratory Numbers: 160913

Client: Stellar Environmental Solutions

Location: Redwood Regional Park

Project#: 020924-DW-1

Sampled Date: 09/24/02
Received Date: 09/24/02

#### CASE NARRATIVE

This hardcopy data package contains samples and QC results for eight water samples, which were received from the site referenced above on September 24, 2002. The samples were received cold and intact.

**TVH/BTXE:** High Trifluorotoluene surrogate recoveries were observed for samples MW-7 (CT# 160913-004), MW-8 (CT# 160913-005) and MW-9 (CT# 160913-006) due to coelution of the hydrocarbons with the surrogate. No other analytical problems were encountered.

TEH by EPA 8015B(M): No analytical problems were encountered.

General Chemistry: No analytical problems were encountered.

Laboratory CCT Address							200	erd	ردار بر ا ا		76			/	j	i.	te Roo.	1
Berkeley CA  Client Stellar Env. Sol.  Address 2198 Sixth St.  Berkeley CA  Project Name Redwood Regum	J P	wk	Alr — Co	ibili Nooler Nooler Noolect Managerolect Managerolect Managerolect Managerolect Noolect No.		· lo a · c		Filled Services	184.4/BT	C. W. M. B.E.		7-7	Anetye	lis Req	ulred		Floring	neleo
1	Date	Three	Factor	mplere: (Signature)	- 144	ervation /	//											
		13.06				100 50 HOL		<b>-</b> 1 \					-	-	-	-		· · · · · · · · · · · · · · · · · · ·
MW-4		13:58		Poly, Voa's, Ambers		ioa se HCL	6		×									
mu-7 mu-8		14:14 14:19						_   X _   <u> </u>	×	X			PE	Rec	eive	e Ambri	Fon ice	
1mw-9		12:40	<del>                                     </del>					_   <u> </u>	<del></del>	スメ						-	7 magn	
mu-10	۱Ÿ.	15:05	1 1 7			V	1	7/7	X	X								
														YAR.	vetio -	MGD.	nect?	
Relinquished by: Navil ( Mark	De		calved by		9/2	Rollnquished Signature Printed Company	d by:					Date -	1	elved b				Dato
Printed David C. Walter  Company Blains Tech  Resson	Tin	<u> </u>	Printed	Cal	71m		'					Time		rinted				Time
Comments:		`	Compan	γ		Relinquisher Signature						Pale	1	elved b	=			Dale
						Printed						Time		rinted ompar				Timo



	Curtis & Tompkins Lab	oratories Anal	
Lab #: Client:	160913 Stellar Environmental Solutions 020924-DW-1	Location: Prep:	Redwood Regional Park EPA 5030B
Project#: Matrix: Units:	Water ug/L	Sampled: Received:	09/24/02 09/24/02

Field ID:

Gasoline C7-C12

MW-2 SAMPLE Diln Fac: Batch#: Analyzed:

1.000 75546 09/26/02

Type: Lāb ID:

> MTBE Benzene Toluene Ethylbenzene m,p-Xylenes o-Xylene

160913-001

		_		
Analute	Result	RL	Analysi	5
7-C12	98	50	8015B(M)	
, , ,	13	2.0	EPA 8021B	
		0.50	EPA 8021B	
	ND	0.50	EPA 8021B	
220	ND	0.50	EPA 8021B	
ene	ND	0.50	EPA 8021B	
es	ND	0.50	EPA 8021B	

		ANGLYSES
Trifluorotoluene (FID) 11	0 68-145	8015B(M)
Bromofluorobenzene (FID) 11	8 66-143	8015B(M)
Trifluorotoluene (PID) 90	53-143	EPA 8021B
Bromofluorobenzene (PID) 10	0 52-142	EPA 8021B

ND

Field ID: Type: Lab ID:

MW - 4 SAMPLE 160913-003 Diln Fac: Batch#: Analyzed: 1.000 75546 09/26/02

Analys18 Result Analyte 8015B(M) ND 50 Gasoline C7-C12 **EPA 8021B** 2.0 ND MTBE EPA 8021B EPA 8021B 0.50 NDBenzene 0.50 Toluene ND 0.50 **EPA 8021B** Ethylbenzene ND EPA 8021B 0.50 ND m.p-Xylenes 0.50 EPA 8021B o-Xylene ND

Surrogate	%REC	Limits	Analysis
Trifluorotoluene (FID)	93	68-145	8015B(M)
Bromofluorobenzene (FID)	112	66-143	8015B(M)
Trifluorotoluene (PID)	86	53-143	EPA 8021B
Bromofluorobenzene (PID)	98	52-142	EPA 8021B

<sup>\*=</sup> Value outside of QC limits; see narrative C= Presence confirmed, but confirmation concentration differed by more than a factor of two ND= Not Detected RL= Reporting Limit Page 1 of 5



Curtis & Tompkins Laboratories Analytical Report Redwood Regional Park EPA 5030B Location: Lab #: 160913 Prep: Stellar Environmental Solutions Client: Project#: 020924-DW-1 09/24/02 09/24/02 Water Sampled: Matrix: Received: <u> Units:</u> uq/L

ield ID: Type: Lab ID: MW-7 SAMPLE 160913-004 Diln Fac: Batch#: Analyzed: 1.000 75546 09/26/02

Analysis Result Analyte 8015B(M) 50 Gasoline C7-C12 9,600 EPA 8021B EPA 8021B 2.0 MTBE ND 0.50 180 Benzene 0.50 **EPA 8021B** ND Toluene EPA 8021B Ethylbenzene 380 0.50 m,p-Xylenes o-Xylene 0.50 EPA 8021B 160 EPA 8021B 0.50

Surrogate	*REC	Limits	Analysis
Trifluorotoluene (FID)	177 *	68-145	8015B(M)
Bromofluorobenzene (FID)	117	66-143	8015B(M)
Trifluorotoluene (PID)	85	53-143	EPA 8021B
Bromofluorobenzene (PID)	111	52-142	EPA 8021B

Field ID: Type: Lab ID: MW-8 SAMPLE 160913-005 Diln Fac: Batch#: Analyzed: 1.000 75546 09/26/02

Result	(4)	Analysis	
1,000	50	8015B(M)	
ND	2.0	EPA 8021B	
22	0.50	EPA 8021B	
	1,000	1,000 50 ND 2.0 22 0.50 ND 0.50 64 0.50 48 0.50	1,000 50 8015B(M)  ND 2.0 EPA 8021B  22 0.50 EPA 8021B  ND 0.50 EPA 8021B  64 0.50 EPA 8021B  48 0.50 EPA 8021B

Surrogate	%RE	C Limits	Agalvsis
Trifluorotoluene (FID)	118	68-145	8015B(M)
Bromofluorobenzene (FID)	111	66-143	8015B(M)
Trifluorotoluene (PID)	86	53-143	EPA 8021B
_ Bromofluorobenzene (PID)	97	52-142	EPA 8021B
· · · · · · · · · · · · · · · · · · ·			

<sup>\*=</sup> Value outside of QC limits; see narrative
C= Presence confirmed, but confirmation concentration differed by more than a factor of two
ND= Not Detected
RL= Reporting Limit
Page 2 of 5



Curtis & Tompkins Laboratories Analytical Report Redwood Regional Park Location: 160913 Lab #: Stellar Environmental Solutions 020924-DW-1 EPA 5030B Prep: Client: Project#: 09/24/02 Sampled: Received: Water Matrix: 09/24/02 uq/L Units:

Field ID:

MW-9

Lab ID:

160913-006

Type:

SAMPLE

Analyte	Result	RL	Diln Fac		Analyzed	Analyeis
Gasoline C7-C12	3,600	50	1.000	75546	09/26/02	8015B(M)
MTBE	ND ·	4.0	2.000	75599	09/27/02	EPA 8021B
Benzene	440	1.0	2.000	75599	09/27/02	EPA 8021B
Toluene	11 C	1.0	2.000	75599	09/27/02	EPA 8021B
Ethvlbenzene	260	1.0	2.000	75599	09/27/02	EPA 8021B
	32	1.0	2.000	75599	09/27/02	EPA 8021B
m,p-Xylenes	7.2 C	1.0	2.000	75599	09/27/02	EPA 8021B
o-Xylene	7.2 (	1.0	2.500		,	

Surrogate	%REC	Limits	Diln	Fac Batch#		Analysis
Trifluorotoluene (FID)	170 *	68-145	1.000	75546	,,	8015B(M)
Bromofluorobenzene (FID)	122	66-143	1.000		**,,	
Trifluorotoluene (PID)	103	53-143	2.000		,,	
Bromofluorobenzene (PID)	100	52-142	2.000	75599	09/27/02	EPA 8021B

Field ID:

MW-10

SAMPLE

Diln Fac: Batch#:

1.000 75546

Type: Lab ID: 160913-007

Analyzed:

09/26/02

Releyede	RI.	<u> Analysis</u>	
160	50	8015B(M)	
26	2.0	EPA 8021B	
10	0.50	EPA 8021B	
— <del>-</del> -	0.50		
6.7	0.50		
3.6	0.50		
ND	0.50	EPA 8021B	
	10 ND 6.7 3.6	26 2.0 10 0.50 ND 0.50 6.7 0.50 3.6 0.50	26 2.0 EPA 8021B 10 0.50 EPA 8021B ND 0.50 EPA 8021B 6.7 0.50 EPA 8021B 3.6 0.50 EPA 8021B

Surrogs	te	%REC	Limits	Anal	Lysts
Trifluorotoluene	(FID)	98	68-145	8015B(M)	
Bromofluorobenzer	e (FID)	108	66-143	8015B(M)	
		84	53-143	EPA 8021B	
Bromofluorobenzer	ie (PID)	95	52-142	EPA 8021B	

<sup>\*=</sup> Value outside of QC limits; see narrative C= Presence confirmed, but confirmation concentration differed by more than a factor of two

ND= Not Detected RL= Reporting Limit Page 3 of 5



Curtis & Tompkins Laboratories Analytical Report Redwood Regional Park Location: Lab #: 160913 EPA 5030B Stellar Environmental Solutions 020924-DW-1 Client: Project#: Matrix: Prep: 09/24/02 09/24/02 Sampled: Water Received: uq/L Units:

ield ID: Type:

MW-11 SAMPLE Lab ID:

160913-008

Diln Fac: 5.000

-2E						
Analyte	Result	Ril	Batch#	Analyzed	Analysis	
Gasoline C7-C12	12,000	250	75611	09/28/02	8015B(M)	i
TMTBE	ND	10	75599	09/27/02	EPA 8021B	
Benzene	330	2.5	75599	09/27/02	EPA 8021B	
Toluene	13	2.5	75599	09/27/02	EPA 8021B	l
Ethylbenzene	880	2.5	75599	09/27/02	EPA 8021B	
m, p-Xylenes	630	2.5	75599	09/27/02	EPA 8021B	
o-Xvlene	24	2.5	7 <u>5599</u>	09/27/02	EPA 8021B	

Surrogate	%REC	Trimilitis	Batch	WATER STATES	Analysis
Trifluorotoluene (FID)	181 *	68-145	75611	09/28/02	8015B (M)
Bromofluorobenzene (FID)	109		75611	09/28/02	8015B(M)
Trifluorotoluene (PID)	118	53-143			EPA 8021B
Bromofluorobenzene (PID)	99	52-142	<u>75599</u>	09/27/02	EPA 8021B

ab ID: iln Fac: BLANK QC190969 1.000

Batch#: Analyzed: 75546 09/25/02

1	Analyte	Result	134	Analysis
	Gasoline C7-C12	ND	50	8015B(M)
М	MTBE	ND	2.0	EPA 8021B
8	Benzene	ND	0.50	EPA 8021B
	Toluene	ND	0.50	EPA 8021B
	Ethylbenzene	ND	0.50	EPA 8021B
1	m,p-Xylenes	ND	0.50	EPA 8021B
T	o-Xylene	ND	0.50	EPA 8021B

Surrogate	%REC	Limits	Analysis
Trifluorotoluene (FID)	89	68-145	8015B (M)
Bromofluorobenzene (FID)	104	66-143	8015B (M)
Trifluorotoluene (PID)	83	53-143	EPA 8021B
Bromofluorobenzene (PID)	92	<u>52-142</u>	EPA 8021B

<sup>\*=</sup> Value outside of QC limits; see narrative C= Presence confirmed, but confirmation concentration differed by more than a factor of two ND= Not Detected RL= Reporting Limit Page 4 of 5



Curtis & Tompkins Laboratories Analytical Report Redwood Regional Park Location: 160913 Lab #: EPA 5030B Stellar Environmental Solutions 020924-DW-1 Prep: Client: Project#: 09/24/02 09/24/02 Sampled: Water Matrix: Received: Units: uq/L

Type: Lab ID: Diln Fac: BLANK QC191190  $\tilde{1}.000$ 

Batch#: Analyzed: Analysis: 75599 09/27/02 EPA 8021B

Result Analyte ND 2.0 MTBE 0.50 Benzene ND 0.50 ND Toluene 0.50 Ethylbenzene ND 0.50 ND m,p-Xylenes o-Xylene 0.50

%REC Limits Surrogate 53-143 52-142 Trifluorotoluene (PID) 100 Bromofluorobenzene (PID) 101

Type: Láb ID: Diln Fac: BLANK QC191226 1.000

Batch#: Analyzed: Analysis:

75611 09/27/02 8015B(M)

Result RL Analyte Gasoline C7-C12 ND

Surrogate	%REC	Limits	
Trifluorotoluene (FID)	103	68-145	
Bromofluorobenzene (FID)	108	66-143	

RL= Reporting Limit Page 5 of 5

11.0

<sup>\*=</sup> Value outside of QC limits; see narrative C= Presence confirmed, but confirmation concentration differed by more than a factor of two ND= Not Detected

mple Name : 160913-001,75546

: G:\GC07\DATA\268A020.raw leName

ethod : TVHBTXE Start Time : 0.00 min ale Factor: 1.0

End Time : 26.00 min

Plot Offset: 10 mV

Sample #: a1

Page 1 of 1


Date: 9/26/02 02:34 AM

Time of Injection: 9/26/02 02:08 AM

Low Point : 9.91 mV

Plot Scale: 115.2 mV

High Point : 125.10 mV



Sample Name : 160913-004,75546

; G:\GC07\DATA\268A022.raw

FileName Method ; TVHBTXE

Start Time : 0.00 min Scale Factor: 1.0

End Time : 26.00 min

Plot Offset: -25 mV

Page 1 of 1


Sample #: a1 Date: 9/26/02 03:42 AM

Time of Injection: 9/26/02 03:16 AM

Low Point : -25.00 mV High Point: 821.46 mV

Plot Scale: 846.5 mV





mple Name : 160913-005,75546

: G:\GC07\DATA\268A023.raw .eName

: TVHBTXE thod Start Time : 0.00 min Fale Factor: 1.0

End Time : 26.00 min Plot Offset: 9 mV

Sample #: al

Page 1 of 1

Date : 9/26/02 04:16 AM


Time of Injection: 9/26/02 03:50 AM

Low Point : 8.61 mV

High Point: 146.60 mV

Plot Scale: 138.0 mV

Response [mV]



Sample Name : 160913-006,75546

: G:\GC07\DATA\268A024.raw FileName

: TVHBTXE Method

Start Time : 0.00 min Scale Factor: 1.0

End Time : 26.00 min

Plot Offset: -17 mV

Sample #: al


Page 1 of 1

Date: 9/26/02 04:50 AM

Time of Injection: 9/26/02 04:24 AM Low Point: -16.73 mV High Po High Point: 653.32 mV

Plot Scale: 670.0 mV





mple Name : 160913-007,75546

: G:\GC07\DATA\268A025.raw leName

thod : TVHBTXE

tart Time : 0.00 min cale Factor: 1.0

End Time : 26.00 min

Plot Offset: 10 mV


Sample #: a1

Date: 9/26/02 05:25 AM Time of Injection: 9/26/02 04:59 AM

High Point: 118.72 mV

Page 1 of 1

Low Point : 9.92 mV Plot Scale: 108.8 mV



Page 1 of 1 Sample Name : 160913-008,75611 Sample #: B1 Date: 9/28/02 03:44 PM : G:\GC05\DATA\270G028.raw FileName Time of Injection: 9/28/02 02:10 AM : TVHBTXE Method High Point: 432.08 mV Start Time : 0.00 min End Time : 25.00 min Low Point : -0.93 mV Plot Offset: -1 mV Plot Scale: 433.0 mV Scale Factor: 1.0 Response [mV] 200 250-150 <del>1.32</del>1.38 232<sup>2</sup>.01 -1.671.83 C-6 -2.61 <u>=3.22</u>3.39 4.00 4.46 5.31 TRIFLUO -5.98 --6.42 ≻7.417 7.41 7.83 -8.18 -8.45 -8.84 <del>-9.25</del> 9.66 9.95 -10.33 10,92 11,17 -11.50 -11.71 **⊱12.23**. -12.83-13.23 -13.58 -14.51 BROMOF -15.06 C-10 -15.41 -16.21 <sup>∠</sup>17.15 17.61 17.90 -18.30 18.68 -19.30 19,69 --20.00 20.37 21.63 21.95 -22.21 -22.69 --23.28 £23.47 23 23.73 24.14 24.43

**≾**-24.90

mple Name : ccv/lcs,qc190970,75546,02ws1468,5/5000

: G:\GC07\DATA\268A001.raw

Method : TVHBTXE Start Time : 0.00 min

leName

End Time : 26.00 min Plot Offset: -22 mV

Sample #:

Page 1 of 1


Date: 9/25/02 03:33 PM

Time of Injection: 9/25/02 03:07 PM

Low Point : -21.58 mV

High Point : 746.20 mV

Plot Scale: 767.8 mV





Total Volatile Hydrocarbons Redwood Regional Park 160913 Location: Lab #: EPA 5030B Stellar Environmental Solutions Prep: Client: 8015B(M) Analysis: 020924-DW-1 Project#: Diln Fac: 1.000 Type: LCS QC190970 Batch#: 75546 Lab ID: 09/25/02 Analyzed: Water Matrix: Units: ug/L

Analyte	Spiked	Result	%REC	Limits
Gasoline C7-C12	2,000	2,211	111	79-120

Surrogate	%REC	Limits		
Trifluorotoluene (FID)	102	68-145		
Bromofluorobenzene (FID)	107	66-143		



Benzene, Toluene, Ethylbenzene, Xylenes Redwood Regional Park Location: Lab #: 160913 Client: Stellar Environmental Solutions Prep: EPA 5030B Analysis: EPA 8021B Project#: 020924-DW-1 75546 Water Batch#: Matrix: 09/25/02 Analyzed: Units: ug/L Diln Fac: 1.000

уре:

BS

Lab ID:

QC190971

Analyte	Spiked	Result	%REC	Limits
MTBE	20.00	19.72	99	<b>51</b> -125
Benzene	20.00	20.42	102	65-122
Toluene	20.00	20.82	104	67-121
	20.00	21.19	106	70-121
m.n-Xvlenes	40.00	40.02	100	72-125
Ethylbenzene m,p-Xylenes o-Xylene	20.00	20.79	104	73-122

Surrogate	%REC	Limits	
Trifluorotoluene (PID)	87	53-143	
Bromofluorobenzene (PID)	96	52-142	

vne:

BSD

Lab ID:

QC191004

<del></del>						
Analyte	Spiked	Result	%REC	Limits	RPD	Lim
MTBE	20.00	19.60	98	51-125	1	20
Benzene	20.00	19.91	100	65-122	3	20
Toluene	20.00	20.20	101	67-121	3	20
Ethylbenzene	20.00	20.69	103	70-121	2	20
-	40.00	38.95	97	72-125	3	20
To-Xylene		20.43	102	73-122	2	20
m,p-Xylenes   o-Xylene	20.00	20.43	102	73-122	2	20

Surrogate	%RE	C Limits	
Trifluorotoluene (PID)	86	53-143	İ
Bromofluorobenzene (PID)	96	52-142	



	Benzene, Toluene,	Ethylbenzene,	Xylenes
Lab #:	160913	Location:	Redwood Regional Park
Client:	Stellar Environmental Solutions	Prep:	EPA 5030B
	020924-DW-1	Analysis:	EPA 8021B
Type:	LCS	Diln Fac:	1.000
Lab ID:	QC191191	Batch#:	75599
Matrix:	Water	Analyzed:	09/27/02
Units:	ug/L		

Spiked	Result	%REC	: Limits	
20.00	20.05	100	<b>5</b> 1- <b>1</b> 25	
20.00	21.13	106	65-122	
20.00	20.33	102	67-121	
20.00	20.58	103	70-121	į
=	35.73	89	72-125	1
* *	20.30	101	73-122	
	20.00 20.00 20.00	20.00     20.05       20.00     21.13       20.00     20.33       20.00     20.58       40.00     35.73	20.00 20.05 100 20.00 21.13 106 20.00 20.33 102 20.00 20.58 103 40.00 35.73 89	20.00     20.05     100     51-125       20.00     21.13     106     65-122       20.00     20.33     102     67-121       20.00     20.58     103     70-121       40.00     35.73     89     72-125

Surrogate	%REC	Limits	
Trifluorotoluene (PID)	99	53-143	
Bromofluorobenzene (PID)	99	52-142	



Total Volatile Hydrocarbons

Lab #: 160913 Location: Redwood Regional Park

Client: Stellar Environmental Solutions Prep: EPA 5030B

Project#: 020924-DW-1 Analysis: 8015B(M)

 Type:
 LCS
 Diln Fac:
 1.000

 Lab ID:
 QC191227
 Batch#:
 75611

Matrix: Water Analyzed: 09/27/02 Units: ug/L

 Analyte
 Spiked
 Result
 %REC
 Limits

 Gasoline C7-C12
 2,000
 1,795
 90
 79-120

Surrogate	%REC	Limits
Trifluorotoluene (FID)	125	68-145
Bromofluorobenzene (FID)	110	66-143



	Total Volat	ile Hydrocarbo	ons
<del></del>	llar Environmental Solutions	Location: Prep: Analysis:	Redwood Regional Park EPA 5030B 8015B(M)
Project#: 020 Field ID: MSS Lab ID: Matrix:	ZZZZZZZZZ 160919-001 Water	Batch#: Sampled: Received:	75546 09/23/02 09/25/02 09/26/02
Units: Diln Fac:	ug/L 1.000	Analyzed:	09/26/02

Type:

MS

Lab ID:

QC191005

Analyte	MSS Result	Spiked	Result	%REC	Limits
Gasoline C7-C12	49.23	2,000	2,031	99	67-120
Gasoline C) C12					/
	0 BEA 1:47				

Surrogate	*REC	Limits
Trifluorotoluene (FID)	107	68-145
Bromofluorobenzene (FID)	116	66-143

Type:

MSD

Analyte

Lab ID:

QC191006

Result %REC Limits RPD Lim

Gasoline C7-C12		2,000	2,026	99	67-120	0	20
Surrogate	%REC	San Caranta Ca					69060000
Trifluorotoluene (FID)	107	68-145					
Bromofluorobenzene (FID)	118	66-143					

Spiked



	Benzene, Toluene,	Ethylbenzene,	Xylenes
Lab #: 16091	.3	Location:	Redwood Regional Park
Client: Stell	ar Environmental Solutions	Prep:	EPA 5030B
Project#: 02092	24-DW-1	Analysis:	EPA 8021B
Field ID:	ZZZZZZZZZZ	Batch#:	75599
MSS Lab ID:	160872-005	Sampled:	09/19/02
Matrix:	Water	Received:	09/20/02
Units:	ug/L	Analyzed:	09/27/02
Diln Fac:	1.000	-	

Type:

MS

Lab ID: QC191192

<u> </u>					
Analyte	MSS Result	Spiked	Result	%REC	Limits
MTBE	ND	20.00	21.71	109	33-131
Benzene	2.139	20.00	23.10	105	52-149
Toluene	<0.05100	20.00	20.32	102	69-130
Ethylbenzene	1.675	20.00	21.65	100	70-131
m,p-Xylenes	4.500	40.00	38.79	86	68-137
o-Xylene	1.529	20.00	22.29	104	73-133

Surrogate	%REC	Limits
Trifluorotoluene (PID)	100	53-143
Bromofluorobenzene (PID)	103	52-142

Type:

MSD

Lab ID: QC191193

Analyte	Spiked	Result	%RBC	Limits	RPD	Lim
MTBE	20.00	21.73	109	33-131	0	20
Benzene	20.00	23.02	104	52-149	0	30
Toluene	20.00	20.41	102	69-130	0	30
Ethylbenzene	20.00	21.71	100	70-131	0	30
m,p-Xylenes	40.00	38.91	86	68-137	0	30
m,p-Xylenes o-Xylene	20.00	22.06	103	73-133	1	30

Surrogate	%REC	Limits
Trifluorotoluene (PID)	100	53-143
Bromofluorobenzene (PID)	101	52-142

ND= Not Detected RPD= Relative Percent Difference

Page 1 of 1



	Total Volat	ile Hydroc <b>arb</b> o	ms
<del>-</del>	913 llar Environmental Solutions 924-DW-1	Location: Prep: Analysis:	Redwood Regional Park EPA 5030B 8015B(M)
Field ID: MSS Lab ID: Matrix: Units: Diln Fac:	ZZZZZZZZZZ 160863-010 Water ug/L 1.000	Batch#: Sampled: Received: Analyzed:	75611 09/19/02 09/20/02 09/27/02

Type:

MS

Lab ID: QC191228

Analyte	MSS Result	Spiked	Result	%RE(	Limits
Gasoline C7-C12	14.41	2,000	1,912	95	67-120

Surroga	te	%RB	C Limits	
Trifluorotoluene	(FID)	126	68-145	
Bromofluorobenzen	e (FID)	114	66-143	

Type:

MSD

Lab ID:

QC191229

Analyte	Spiked	Result	%REC	Limits	RPD Lin	
Gasoline C7-C12	2,000	1,853	92	67-120	3 20	
OUBOTING C. CIG					<u></u>	_

Surrogate	%REC	Limits		
Trifluorotoluene (FID)	125	68-145		
Bromofluorobenzene (FID)	112	66-143	 	

Total Extractable Hydrocarbons

Lab #: 160913 Location: Redwood Regional Park

Client: Stellar Environmental Solutions EPA 3520C Prep:

Project#: 020924-DW-1 Matrix: Wate EPA 8015B(M) 09/24/02 Analysis: Water Sampled: 09/24/02 Units: ug/L Received:

Batch#: 09/27/02 75619 Prepared:

Field ID:

MW-2 SAMPLE

Type: jab ID:

160913-001

Diln Fac:

1.000

09/29/02 Analyzed:

Analyte Result Diesel C10-C24 ND 50

Surrogate (4:0:(0) | K \$115 (4:1)

Hexacosane 39-137

ield ID: ype:

Lab ID:

MW-4

SAMPLE

160913-003

Diln Fac:

1.000

Analyzed:

09/29/02

Analyte Result RL Diesel C10-C24 50

Surrogate %REC Limits Hexacosane 87 39-137

Field ID:

ype: ab ID:

MW - 7 SAMPLE

160913-004

Diln Fac:

1.000

Analyzed:

09/29/02

Analyte Result

Diesel C10-C24 3,900 L Y 50

Surrogate %REC Limits Hexacosane 87 39-137

ield ID:

ab ID:

Type:

MM-8

SAMPLE

160913-005

Diln Fac:

1.000

Analyzed:

09/29/02

Analyte Result Diesel Cl0-C24 420 L Y 50

Surrogate %REC Limits

Hexacosane 89 39-137

L= Lighter hydrocarbons contributed to the quantitation Y= Sample exhibits fuel pattern which does not resemble standard

ND= Not Detected

RL= Reporting Limit Page 1 of 2

5.0



Total Extractable Hydrocarbons

Redwood Regional Park Location: Lab #: 160913

EPA 3520C EPA 8015B(M) 09/24/02 Stellar Environmental Solutions Prep: Client: 020924-DW-1 <u>Analysi</u> Project#:

Sampled: Water Matrix: 09/24/02 09/27/02 Received: ug/L Units: Prepared: Batch#; 756<u>19</u>

Field ID:

MW-9 SAMPLE

Type: Lab ID: 160913-006

1.000 Diln Fac: 09/29/02 Analyzed:

Analyte Result 50

2,800 L Y Diesel C10-C24

\*REC Limits Surrogate 39-137 Hexacosane 83

Field ID: Type:

Lab ID:

MW-10

SAMPLE 160913-007 Diln Fac:

1.000

09/29/02 Analyzed:

Analyte Result RL 50 120 **L** Y Diesel C10-C24

Surrogate %REC Limits

39-137 90 Hexacosane

Field ID:

MW-11

Type: Lab ID: SAMPLE 160913-008 Diln Fac:

2.000

Analyzed:

09/30/02

RL Result Analyte

100 4,400 L Y Diesel C10-C24

Limits Surrogate 39-137 88 Hexacosane

Type: Lab ID:

Hexacosane

BLANK QC191257 Diln Fac:

1.000

Analyzed:

09/29/02

Result Analyte Diesel C10-C24

%REC Limits Surrogate 39-137

L= Lighter hydrocarbons contributed to the quantitation Y= Sample exhibits fuel pattern which does not resemble standard

ND= Not Detected

RL= Reporting Limit Page 2 of 2

ple Name : 160913-004,75619

: G:\GC15\CHB\272B006.RAW

hod : BTEH230.MTH

Start Time : 0.00 min Scale Factor: 0.0

End Time : 31.90 min

Plot Offset: -20 mV

Sample #: 75619

Date: 09/30/2002 11:50 AM


Time of Injection: 09/29/2002 03:07 PM Low Point : -20.25 mV

High Point : 1024.00 mV

Page 1 of 1

Plot Scale: 1044.3 mV

Response [mV]



Sample Name : 160913-005,75619

FileName : G:\GC15\CHB\272B007.RAW

Method : BTEH230.MTH Start Time : 0.01 min

Start Time : 0.01 min Scale Factor: 0.0 End Time : 31.91 min

Plot Offset: 26 mV

Sample #: 75619


Page 1 of 1

Date: 09/30/2002 11:51 AM

Time of Injection: 09/29/2002 03:48 PM

Low Point: 25.64 mV High Point: 232.17 mV

Plot Scale: 206.5 mV



mple Name : 160913-006,75619

ame : G:\GC15\CHB\272B008.RAW

chod : BTEH230.MTH

Start Time : 0.01 min Scale Factor: 0.0

End Time : 31.91 min

Plot Offset: 26 mV

Sample #: 75619

Page 1 of 1


Date: 09/30/2002 11:51 AM

Time of Injection: 09/29/2002 04:29 PM

High Point : 691.11 mV

Low Point: 25.51 mV Plot Scale: 665.6 mV





Sample Name : 160913-007,75619

: G:\GC15\CHB\272B009.RAW

FileName : BTEH230.MTH Method

Start Time : 0.01 min

End Time : 31.91 min Plot Offset: 26 mV


Sample #: 75619

Page 1 of 1

Date: 09/30/2002 11:52 AM
Time of Injection: 09/29/2002 05:09 PM

High Point : 217.09 mV

Low Point : 25.77 mV Plot Scale: 191.3 mV



Sample Name : 160913-008sq, 75619

ileName Wethod : G:\GC15\CHB\272B032.RAW

: BTEH230.MTH Start Time : 0.01 min

Scale Factor: 0.0

C-50

End Time : 31.91 min Plot Offset: 26 mV

Sample #: 75619

Page 1 of 1


Date: 09/30/2002 05:09 PM

Time of Injection: 09/30/2002 02:13 PM

Low Point : 26.38 mV High Point : 874.95 mV

Plot Scale: 848.6 mV





ample Name : ccv,02ws1485,dsl

: G:\GC11\CHA\272A002.RAW ileName

: ATEH262.MTH ethod tast Time : 6.01 min

cale Factor: 0.0

End Time : 31.91 min

Plot Offset: 25 mV

Sample #: 500mg/L

Date: 9/29/02 11:49 AM

Time of Injection: 9/29/02 11:05 AM


Low Point : 24.97 mV

High Point: 339.51 mV

Page 1 of 1

Plot Scale: 314.5 mV







Total Extractable Hydrocarbons

Lab #: 160913 Location: Redwood Regional Park

Client: Stellar Environmental Solutions Prep: EPA 3520C Project#: 020924-DW-1 Analysis: EPA 8015B(M)

Matrix: Water Batch#: 75619
Units: ug/L Prepared: 09/27/02

Diln Fac: 1.000 Analyzed: 09/30/02

Type:

BS

Lab ID:

QC191258

 Analyte
 Spiked
 Result
 %REC Limits

 Diesel C10-C24
 2,500
 2,183
 87
 37-120

Surrogate %REC Limits
Hexacosane 103 39-137

Camer

BSD

Lab ID:

QC191259

Anal	yte Spiked	Result	%REC	Limits	RPD	Lim
Diesel C10-C24	2,500	1,943	78	37-120	12	26

Surrogate %REC himits
Hexacosane 96 39-137



	Nitra	te Nitrogen	
	160913 Stellar Environmental Solutions 020924-DW-1	Location: Analysis:	Redwood Regional Park EPA 300.0
Analyte: Matrix: Units: Diln Fac:	Nitrogen, Nitrate Water mg/L 1.000	Batch#: Sampled: Received: Analyzed:	75529 09/24/02 09/24/02 09/25/02

Field ID			sult	<b>RL</b> 0.05	
MW - 3	SAMPLE 160913-002	ND		•	
MW - 4	SAMPLE 160913-003		0.57	0.05	
MW-7	SAMPLE 160913-004	ND		0.05	
	SAMPLE 160913-005	ND		0.05	
MW - 8			0.32	0.05	
MW-9	SAMPLE 160913-006			0.05	
MW-10	SAMPLE 160913-007		0.21		
MW-11	SAMPLE 160913-008	ND		0.05	
MM - TT	BLANK QC190917	ND		0.05	



Sulfate Redwood Regional Park 160913 Location: Lab #: Analysis: EPA 300.0 client: Stellar Environmental Solutions Project#: 020924-DW-1 Sulfate Sampled: 09/24/02 Analyte: 09/24/02 Water Received: Matrix: 09/25/02 Analyzed: Units: mg/L Batch#: 75529

Field ID	Type Lab ID	Result	RL	Diln Fac
MW-3	SAMPLE 160913-002	37	0.50	1.000
MW - 4	SAMPLE 160913-003	55	1.0	2.000
MW - 7	SAMPLE 160913-004	1.9	0.50	1.000
 MW-8	SAMPLE 160913-005	~ 86	1.0	2.000
MW - 9	SAMPLE 160913-006	72	1.0	2.000
MW-10	SAMPLE 160913-007	64	1.0	2.000
MW-11	SAMPLE 160913-008	3.7	0.50	1.000
_	BLANK QC190917	ND	0.50	1.000



	Nitra	te Nitrogen	
Lab #: 1609 Client: Stel Project#: 0209	lar Environmental Solutions	Location: Analysis:	Redwood Regional Park EPA 300.0
Analyte: Field ID: MSS Lab ID: Matrix: Units:	Nitrogen, Nitrate MW-3 160913-002 Water mg/L	Batch#: Sampled: Received: Analyzed:	75529 09/24/02 09/24/02 09/25/02

Туре	Lab ID	MSS Result	Spiked	Result	%REC	Limits	RPD	Lim	Diln Fac	
BS	OC190918		1.000	1.052	105	90-110			1.000	
BSD	OC190919		1,000	1.025	102	90-110	3	20	1.000	
MS	OC190920	<0.07000	2.500	2.368	95	80-120			5.000	
MSD	OC190921		2.500	2.532	101	80-120	7	20	5.000	



Sulfate Redwood Regional Park Lab #: 160913 Location: EPA 300.0 Analysis: Client: Stellar Environmental Solutions Project#: 020924-DW-1 Batch#: 75529 Sulfate Analyte: 09/24/02 Field ID: Sampled: MW-3 09/24/02 MSS Lab ID: 160913-002 Received: Analyzed: 09/25/02 Matrix: Water Units: mg/L

Type	Lab ID	MSS Result	Spiked	Result	%REC	Limits	RPE	) Lim	Diln Fac
BS	OC190918		10.00	10.13	101	90-110			1.000
BSD	OC190919		10.00	10.06	101	90-110	1	20	1.000
MS	OC190920	34.63	25.00	59.42	99	72-125			5.000
MSD	QC190921		25.00	59.70	100	72-125	0	20	5.000



# Curtis & Tompkins, Ltd., Analytical Laboratories, Since 1878

2323 Fifth Street, Berkeley, CA 94710, Phone (510) 486-0900, Fax (510) 486-0532

### ANALYTICAL REPORT

Prepared for:

Stellar Environmental Solutions 2198 6th Street Suite 201 Berkeley, CA 94710

Date: 08-OCT-02 Lab Job Number: 160898 Project ID: 2001-53

Location: Redwood Park Service Yard

This data package has been reviewed for technical correctness and completeness. Release of this data has been authorized by the Laboratory Manager or the Manager's designee, as verified by the following signatures. The results contained in this report meet all requirements of NELAC and pertain only to those samples which were submitted for analysis.

Reviewed by:

Project Manager

Reviewed by:

perations Manager

This package may be reproduced only in its entirety.

NELAP # 01107CA

Page 1 of |2

Laboratory Curlis 4 To Address 33.33 Boiledo	LITTLE 24	l. net		Sh	elhod of Shipment	-	diray			/-		·- <del>-</del>	·		<u> </u>	ysis Re		·	Page	01	
Project Owner East By Site Address 7867	86-0900 Regional Pa Redwood Ravol CP	Road		Co Pro	bill No	- Vic R 4-3123	uler	- - -	Filler	No. 07.05	Sul alivera	+ Blex + H		<i>/</i>	Analy	//		7/		Remai	rkes
Project Number 2001-	1 Paik Se 53	AAME	Yaid	Fa Sa	x No. (510) 64 mplers: (Signature)	-B.M.	Rull	- - /		`₹/	/3 /3	10 / 10 / 10 / 10 / 10 / 10 / 10 / 10 /		/ /	//	//	//	//	′ /		
Field Sample Number	Location/ Depth	Date	Time	Sample Type	Type/Size of Container	Cooler	eservation Chemical /	/ /	/ <del>-                                    </del>	/ <del>-                                    </del>	/ <i>\</i> ^	<del>/</del>		$\leftarrow$	_	_	_	$\leftarrow$	_		
Sw-J		1/2400	810	₩0	40 ml Vols	<u> </u>	Hcl		3		χ										·
n n		4	,n		1-Lambre	V	none		1		-	X			-		<u> </u>			·- ·	<u> </u>
50x-2 (8R)					40 my your (BR	) X	NCI		V		X	/		_	<del> </del>						
M.		1		1	1-L/amber	A	none		A		$\angle$	X	;	-	-				-		
													-								
							Preser	vatio	n Ca	ггес	7				T/	Re	ceiv	ed Am	D∕O pient	n Ice	ct
				_			<b>≥</b> Yes						_								
Relinquished by: Signature B-M- Tull		Date /24/02	Receive Signs	\ \	2	Date 1/2	Relinquished to	Σγ:					Date -	9	Receive Signs	d by: dure			· -		Date
Printed Bluce Rucker  Company Stellar Env. Solv	<del></del> [	Time GoP	Printe		_ Cllwygz CaT	- Ilme	Printed			- Timi	6	Printed				Time					
	DAY		Corti				Refinquished i				**		Oat	е	Receive					:	Date
Comments:	•						Printed		<del>,</del>				_ Tim	le l	Print	ed	·····		<del></del>		Time
		and the second					Company .					don Transport	_	بالمحجود	Com	pany	****	Name and			

Chain of Buston Report



Curtis & Tompkins Laboratories Analytical Report

Redwood Park Service Yard Location: 160898

EPA 5030B Stellar Environmental Solutions Prep:

Project#: 2001-53

Lab #:

Client:

75546 Batch#: SW-2 Field ID:

09/24/02 Sampled: Water Matrix: 09/24/02

Received: ug/L Units: 1.000 Diln Fac:

. 09/26/02 Analyzed: SAMPLE

Type: 160898-001 Lab ID:

Analyte	Result	RL	Analysis	
Gasoline C7-C12	590	50	8015B(M)	
MTBE	ND	2.0	EPA 8021B	1
Benzene	10	0.50	EPA 8021B	ļ
Toluene	ND	0.50	EPA 8021B	ļ
Ethylbenzene	13	0.50	EPA 8021B	
	ND	0.50	EPA 8021B	
m,p-Xylenes	ND	0.50	EPA 8021B	

Surrogate	%REC	Limits	Analysis
Trifluorotoluene (FID)	141	68-145	8015B(M)
Bromofluorobenzene (FID)	112	66-143	8015B(M)
Trifluorotoluene (PID)	96	53-143	EPA 8021B
Bromofluorobenzene (PID)	99	52-142_	EPA 8021B

09/25/02 Analyzed: BLANK Type:

QC190969 Lab ID:

Analyte	Result	RL	Analysis	
Gasoline C7-C12	ND	50	8015B(M)	
MTBE	ND	2.0	EPA 8021B	
	ND	0.50	EPA 8021B	
Benzene	ND	0.50	EPA 8021B	
Toluene	ND	0.50	EPA 8021B	
Ethylbenzene		0.50	EPA 8021B	
m,p-Xylenes	ND	· ·	EPA 8021B	
o-Xylene	ND	0.50	EPA 6021B	

Surrogate	%REC	Limits	Analysis
Trifluorotoluene (FID)	89	68-145	8015B(M)
Bromofluorobenzene (FID)	104	66-143	8015B(M)
Trifluorotoluene (PID)	83	53-143	EPA 8021B
Bromofluorobenzene (PID)	92	52-142	EPA 8021B

ND= Not Detected RL= Reporting Limit Page 1 of 1

## GC07 TVH 'A' Data File RTX 502

ple Name : 160898-001,75546

; G:\GC07\DATA\268A019.raw

: TVHBTXE hod

Start Time : 0.00 min Scale Factor: 1.0

End Time : 26.00 min

Plot Offset: 10 mV

Sample #: al

Date: 9/26/02 08:39 AM


Time of Injection: 9/26/02 01:34 AM

Low Point : 10.49 mV High Point: 114.34 mV

Page 1 of 1

Plot Scale: 103.8 mV





#### 'A' Data File RTX 502 GC07 TVH

Sample Name : ccv/lcs,qc190970,75546,02ws1468,5/5000

: G:\GC07\DATA\268A001.raw FileName

: TVHBTXE

4ethod

Start Time : 0.00 min End Time : 26.00 min

Plot Offset: -22 mV

Page 1 of 1

Sample #: Date: 9/25/02 03:33 PM


Time of Injection: 9/25/02 03:07 PM

Low Point: -21.58 mV

High Point : 746.20 mV

Plot Scale: 767.8 mV







Total Volatile Hydrocarbons

160898 ab #:

Stellar Environmental Solutions

Project#: 2001-53

Type:

ab ID:

:lient:

QC190970

latrix: Units:

Water ug/L

LCS

Location:

Prep:

Redwood Park Service Yard EPA 5030B

Analysis:

8015B(M) 1.000

Diln Fac:

75546

Batch#: Analyzed:

09/25/02

Analyte	Spiked	Result	%REC	Limits	
Gasoline C7-C12	2,000	2,211	111	79-120	

Surrogate	%REC	Limits
Trifluorotoluene (FID)	102	68-145
Bromofluorobenzene (FID)	107	66-143



	Benzene, Toluene,	Ethylbenzene,	Xylenes
Lab #: Client: Project#:	160898 Stellar Environmental Solutions 2001-53	Location: Prep: Analysis:	Redwood Park Service Yard EPA 5030B EPA 8021B
Matrix: Units: Diln Fac:	Water ug/L 1.000	Batch#: Analyzed:	75546 09/25/02

Type:

BS

Lab ID:

QC190971

Analyte	Spiked	Result	%REC	Limits	
MTBE	20.00	19.72	99	51-125	
Benzene	20.00	20.42	102	65-122	
Toluene	20.00	20.82	104	67-121	
Ethylbenzene	20.00	21.19	106	70-121	
m,p-Xylenes	40.00	40.02	100	72-125	
o-Xylene	20.00	20.79	104	73-122	

Surrogate	%REC	Limits	<u> </u>
Trifluorotoluene (PID)	87	53-143	l l
Bromofluorobenzene (PID)	96	52-142	-4

Type:

BSD

Lab ID:

QC191004

Analyte	Spiked	Result	%REC	Limits	RPD	Lim
MTBE	20.00	19.60	98	51-125	1	20
Benzene	20.00	19.91	100	65-122	3	20
Toluene	20.00	20.20	101	67-121	3	20
Ethylbenzene	20.00	20.69	103	70-121	2	20
m,p-Xylenes	40.00	38.95	97	72-125	3	20
o-Xylene	20.00	20.43	102	73-122	2	20

Surrogate	%RE(	] Limits	
Trifluorotoluene (PID)	86	53-143	
Bromofluorobenzene (PID)	96	52-142	



	Total Volat:	lle Hydrocarbo	ns
.,	.60898 Stellar Environmental Solutions 2001-53	Location: Prep: Analysis:	Redwood Park Service Yard EPA 5030B 8015B(M)
Field ID: MSS Lab ID: Matrix: Units: Diln Fac:	ZZZZZZZZZ	Batch#: Sampled: Received: Analyzed:	75546 09/23/02 09/25/02 09/26/02

тре:

MS

Lab ID:

QC191005

Analyte	MSS Result	Spiked	Result	%RE	C Limits
Gasoline C7-C12	49.23	2,000	2,031	99	67-120
		····			

Surrogate	%REC	Limits	
Trifluorotoluene (FID)	107	68-145	
Bromofluorobenzene (FID)	116	66-143	

Type:

MSD

Lab ID:

QC191006

Analyte	Spiked	Result	%REC		RPD	Lim
Gasoline C7-C12	2,000	2,026	99	67-120	0	20

Surrogate	₩RBC	Limits	
Trifluorotoluene (FID)	107	68-145	
Bromofluorobenzene (FI	(D) 118	66-143	



Total Extractable Hydrocarbons Redwood Park Service Yard Location: Lab #: 160898 **EPA 3520C** Stellar Environmental Solutions Prep: Client: EPA 8015B(M) Project#: 2001-53 Analysis: SW-2 Batch#: 75621 Field ID: 09/24/02 Sampled: Matrix: Water 09/24/02 Received: Units: ug/L 09/27/02 Prepared: 1.000 Diln Fac:

Type: Lab ID: SAMPLE

160898-001

Analyzed:

09/30/02

Analyte Diesel C10-C24

Result

220 L Y

RL

Surrogate Limita 39-137 78 Hexacosane

Type: Lab ID: BLANK

QC191264

Analyzed:

09/29/02

Cleanup Method: EPA 3630C

RL Result Analyte 50 Diesel Cl0-C24 ND

Surrogate	*REC	Limite		
Hexacosane	87	39-137		

L= Lighter hydrocarbons contributed to the quantitation

Y= Sample exhibits fuel pattern which does not resemble standard

ND= Not Detected

RL= Reporting Limit

Page 1 of 1

# Chromatogram

Sample Name: 160898-001,75621

leName : G:\GC15\CHB\272B023.RAW

: BTEH230.MTH

art Time : 0.01 min Scale Factor: 0.0

End Time : 31.91 min

Plot Offset: 26 mV

Sample **#:** 75621


Date: 09/30/2002 12:02 PM Time of Injection: 09/30/2002 02:40 AM

High Point: 201.98 mV

Page 1 of 1

Low Point : 26.15 mV Plot Scale: 175.8 mV







Total Extractable Hydrocarbons Redwood Park Service Yard Location: 160898 Lab #: EPA 3520C Stellar Environmental Solutions Prep: Client: EPA 8015B(M) Analysis: Project#: 2001-53 75621 Batch#: Matrix: Water 09/27/02 ug/L Prepared: Units:

Type:

Cleanup Method: EPA 3630C

Analyzed:

09/30/02

Lab ID:

Diln Fac:

QC191265

1.000

RRC Limits Result Spiked

37-120 1,823 Diesel Cl0-C24 2,500

\*REC Limits Surrogate 39-137 86 Hexacosane

Type: Lab ID: BSD

QC191266

Cleanup Method: EPA 3630C

Analyte	Spiked	Result	%REC	Limits	RPI	) Lim
Diesel Cl0-C24	2,500	1,804	72	37-120	1	26

%REC Limits 39-137 Hexacosane

RPD= Relative Percent Difference Page 1 of 1

## Chromatogram

le Name : ccv,02ws1485,dsl

: G:\GC11\CHA\272A002.RAW

: ATEH262.MTH

Start Time : 0.01 min Scale Factor: 0.0

End Time : 31.91 min

Plot Offset: 25 mV

Sample #: 500mg/L

Date: 9/29/02 11:49 AM

Time of Injection: 9/29/02 11:05 AM

Low Point : 24.97 mV

High Point : 339.51 mV

Page 1 of 1

Plot Scale: 314.5 mV



