

September 30, 2000

ENVINCESCRIPTION

DO DET -4, PM. 3: 24

REPORT
for
SOIL AND GROUNDWATER ASSESSMENT
at the
Romak Iron Works
3250 Hollis Street
Oakland, California

Submitted by: AQUA SCIENCE ENGINEERS, INC. 208 West El Pintado Danville, CA 94526 (925) 820-9391

1.0 INTRODUCTION

Site Location (Site), See Figure 1
3250 Hollis Street
Oakland, CA

Responsible Party
Mr. Kevin Romak
3250 Hollis Street
Oakland, CA 94662-0588

Environmental Consulting Firm Aqua Science Engineers, Inc. (ASE) 208 West El Pintado Danville, CA 94526 Contact: Robert Kitay, Senior Geologist (925) 820-9391

Agency Review
Ms. Susan Hugo
Alameda County Health Care Services Agency (ACHCSA)
1131 Harbor Bay Parkway, Suite 250
Alameda, CA 94502

Mr. Chuck Headlee California Regional Water Quality Control Board (RWQCB) San Francisco Bay Region 1515 Clay Street, Suite 1400 Oakland, CA 94612

This submittal presents Aqua Science Engineers, Inc. (ASE)'s results for a soil and groundwater assessment at the Romak Iron Works located at 3250 Hollis Street in Oakland, California (Figure 1). The proposed site assessment activities were initiated by Mr. Kevin Romak, property owner to perform the tasks required to determine whether the case may be closed. The scope of work in the workplan was approved by Ms. Susan Hugo of the Alameda County Health Care Services Agency (ACHCSA) in a letter dated August 4, 2000.

2.0 BACKGROUND INFORMATION

On January 15, 1992, two underground gasoline storage tanks (USTs) were removed from the site. ASE collected one soil sample from beneath Total petroleum hydrocarbons as gasoline each former tank location. (TPH-G) was detected at 180 parts per million (ppm) in one of the two samples. On January 16, 1992, approximately 20 cubic yards of soil were overexcavated and additional soil samples were collected to confirm that all hydrocarbon-bearing soil was removed. One of the confirmation samples still contained 11 ppm TPH-G. Since hydrocarbons were still detected in the soil, the ACHCSA requested in a letter dated April 29, 1993 that a soil and groundwater investigation be preformed at the site. Although the April 29, 1993 letter from ACHCSA requests that three monitoring wells be installed at the site, Ms. Susan Hugo of ACHCSA, in a conversation with David Allen of ASE, stated that it would be acceptable to install only one groundwater monitoring well at the site if a reliable gradient could be established in the site vicinity.

ASE researched the groundwater flow direction in the site vicinity by reviewing the ACHCSA and San Francisco Bay Regional Water Quality Control Board files for the Guiton Charter Bus Company at the opposite corner of the 34th Street and Hollis Street intersection at 3421 Hollis Street in Oakland, California. ASE also contacted Epigene International and Hageman-Aguiar, Inc. (Guiton's former environmental consultants) for information in their files concerning the groundwater flow direction beneath their site. ASE also measured depths to groundwater in the Guiton wells on June 25, 1993. Groundwater appeared to flow to the southwest beneath the Guiton site.

In July 1993, ASE installed groundwater monitoring well MW-1 at the site. No hydrocarbons were detected in the soil sample collected from the boring. Since the well installation, groundwater samples have been collected from the site well on a quarterly basis up until September 1998 and on a semi-annual basis since September 1998. During this time there has been a steady decrease in hydrocarbon concentrations in groundwater samples collected from this well. TPH-G and benzene concentrations have dropped from as high as 24,000 parts per billion (ppb) and 6,200 ppb, respectively, in 1994 to as low as 2,300 ppb and 330 ppb, respectively during the past year. See Table One for tabulated groundwater monitoring results.

3.0 PROPOSED SCOPE OF WORK (SOW)

The scope of work in this workplan was approved by the ACHCSA in a letter dated August 4, 2000. For the case to be closed, the following three requirements must be met:

- I) The horizontal extent of contamination must be defined. This can be accomplished by collecting soil and groundwater samples from temporary borings. At least six borings will be required.
- II) The bottom of the utility lines in Hollis Street must be shown to be above the shallowest water table beneath the site. Otherwise, additional borings will be required along the utility trenches.
- III) A human health risk assessment will need to be performed showing no unacceptable threat to human health.

To complete the requirements outlined above, ASE proposes the following scope of work:

- 1) Prepare this workplan and health and safety plan for approval by the ACHCSA.
- 2) Contract with an underground utility locating service to locate as precisely as possible the underground utility line locations in the site vicinity. Underground Service Alert will also be contacted.
- 3) Visit the various utility company offices and review their utility line maps for the site vicinity.
- 4) Obtain an excavation permit from the City of Oakland to drill in the street.
- 5) Obtain a drilling permit from the Alameda County Public Works Agency (ACPWA).
- 6) Drill six soil borings at the site in an attempt to define the horizontal extent of contamination, and collect soil and groundwater samples from the borings for analysis.
- 7) Analyze one soil and one groundwater sample from each boring at a CAL-EPA certified analytical laboratory for total petroleum

hydrocarbons as gasoline (TPH-G) by modified EPA Method 5030/8015, total petroleum hydrocarbons as diesel (TPH-D) by modified EPA Method 3510/8015, and benzene, toluene, ethylbenzene and total xylenes (collectively known as BTEX) and methyl tertiary butyl ether (MTBE) by EPA Method 8020.

- 8) Backfill the borings with neat cement.
- 9) Prepare a report outlining the methods and findings of this assessment.
- 10) ASE will prepare a human health risk assessment for the site using the Risk-Based Corrective Action (RBCA) model.

Details of the assessment are presented below.

4.0 UNDERGROUND UTILITY LOCATING

On July 25, 2000, Subtronics Corporation of Concord, California accurately located the public utilities around the proposed drilling locations (Figure 2). An eight (8)-inch sewer line runs down the center of Hollis Street at a depth of 4 to 5-feet bgs. Groundwater at the site has ranged between 9 and 10-feet bgs. All utility lines located were found to be above the water table.

5.0 DRILL SOIL BORINGS AND COLLECT SAMPLES

Prior to drilling, ASE obtained a drilling permit from the Alameda County Public Works Agency (ACPWA) and an excavation permit from the City of Oakland. Copies of the permits are located in Appendix A.

On August 17, 2000, Vironex, Inc. of Hayward, California drilled soil borings BH-A through BH-F at the site using a Geoprobe hydraulic sampling rig (Figure 2). The drilling was directed by ASE associate geologist Ian Reed.

Undisturbed soil samples were collected continuously as drilling progressed for lithologic and hydrogeologic description and for possible analysis. The samples were collected by driving a sampler lined with acetate tubes using hydraulic direct push methods. Selective soil samples were immediately trimmed, sealed with Teflon tape, plastic end caps and tape, labeled, sealed in plastic bags and stored on ice for transport to Kiff Analytical, LLC of Davis, California under chain of custody. Soil from the

remaining tubes was described by the site geologist using the Unified Soil Classification System and was screened for volatile compounds using an Organic Vapor Meter (OVM). The soil was screened by emptying soil from one of the sample tubes into a plastic bag. The bag was then sealed and placed in the sun for approximately 10 minutes. After the volatile compounds were allowed to volatilize, the OVM measured the vapor in the bag through a small hole punched in the bag. OVM readings are used as a screening tool only, since the procedures are not as rigorous as those used in the laboratory. OVM readings can be found on the boring logs located in Appendix B.

Groundwater samples were removed from the borings with a bailer. The groundwater samples were contained in 40-ml volatile organic analysis (VOA) vials (pre-preserved with hydrochloric acid) and sealed without headspace. The samples to be analyzed for TPH-D and TPH-MO were contained in 1-liter amber glass bottles. All samples were then labeled and stored on ice for transport to Chromalab, Inc. under chain of custody.

Upon completion of the soil and groundwater sampling, the borings were backfilled with neat cement to the ground surface.

Drilling equipment was cleaned with a TSP solution between sampling intervals and between borings to prevent potential cross-contamination.

Sediments encountered during drilling generally consisted of silts and clays beneath the surface to the depth explored of 28-feet bgs. Groundwater was encountered between approximately 12-feet bgs and 17-feet bgs. Boring logs are presented as *Appendix B*.

6.0 ANALYTICAL RESULTS FOR SOIL

Soil samples collected from 15.5-feet bgs in boring BH-A, 7.5-feet bgs in boring BH-B, 18.0-feet bgs in borings BH-C and BH-D, 19.0-feet bgs in boring BH-E, and 11.0-feet bgs in boring BH-F were analyzed by Chromalab, Inc. for TPH-G by modified EPA Method 5030/8015, TPH-D and TPH-MO by modified EPA Method 3510/8015, and BTEX and MTBE by EPA Method 8020. These samples represent either the capillary zone or the unsaturated soil sample that appeared the most contaminated based on odor, staining, and/or OVM readings. The analytical results are tabulated in Table Two and the certified analytical report and chain of custody forms are included in Appendix C.

There were no hydrocarbons or oxygenates detected in soil samples analyzed from all six borings.

7.0 GROUNDWATER MONITORING WELL SAMPLING

On August 17, 2000, ASE measured the depth to water in the site groundwater monitoring well using an electric water level sounder. The well was also checked for the presence of free-floating hydrocarbons. A sheen was present on the groundwater surface this quarter. Prior to sampling, the well was purged of four well casing volumes of groundwater using a pre-cleaned polyethylene bailer. The groundwater samples were decanted from the bailer into three (3) 40-ml volatile organic analysis (VOA) vials, pre-preserved with hydrochloric acid, and two (2) 1-liter amber glass bottles. The samples were labeled, placed in protective foam sleeves, and placed into a cooler with wet ice for transport to Chromalab, Inc. of Pleasanton, California under appropriate chain of custody documentation.

Well sampling purge water was contained in steel 55-gallon drums and removed from the site for disposal. The well sampling log is included as Appendix E.

8.0 ANALYTICAL RESULTS FOR GROUNDWATER

The groundwater samples were analyzed by Chromalab, Inc. for TPH-G by modified EPA Method 5030/8015, TPH-D and TPH-MO by modified EPA Method 3510/8015, and BTEX and MTBE by EPA Method 8020. The analytical results are tabulated in Tables One and Three, and the certified analytical report and chain of custody forms are included in Appendix D.

The groundwater samples collected from boring BH-C contained 150 parts per billion (ppb) TPH-D and 0.8 ppb total xylenes. The groundwater samples collected from monitoring well MW-F contained 0.81 ppb total xylenes. There were no hydrocarbons detected in groundwater samples collected from the remaining borings.

The groundwater samples collected from the site monitoring well contained 840 ppb TPH-G, 1,100 ppb TPH-D, 700 ppb TPH-MO, 55 ppb benzene. 0.74 ppb toluene, 7.5 ppb ethyl benzene, and 23 ppb MTBE.

9.0 CONCLUSIONS AND RECOMMENDATION

Since elevated hydrocarbon concentrations have only been detected in the immediate area of the former USTs, ASE recommends that this case be reviewed for closure following the Risk-Based Corrective Action (RBCA) model which will be prepared by ASE within the next quarter. that a vapor intrusion from groundwater recommends industrial and residential buildings be the only scenario considered since there is a significant decreasing trend in hydrocarbon concentrations and all of the off-site downgradient borings did not contain detectable concentrations. In addition, ASE recommends hydrocarbon average of hydrocarbon concentrations detected in monitoring well MW-1 during the last year be used as the groundwater concentration beneath the site in the RBCA model.

10.0 REPORT LIMITATIONS

The results of this assessment represent conditions at the time of the soil and groundwater sampling, at the specific locations where the samples were collected, and for the specific parameters analyzed by the laboratory.

This report does not fully characterize the site for contamination resulting from unknown sources or for parameters not analyzed by the laboratory. All of the laboratory work cited in this report was prepared under the direction of an independent CAL-EPA certified laboratory. The independent laboratory is solely responsible for the contents and conclusions of the chemical analysis data.

Aqua Science Engineers appreciates the opportunity provide environmental consulting services for this project. Should you have any questions or comments, please feel free to call us at (925) 820-9391.

Respectfully submitted,

AQUA SCIENCE ENGINEERS, INC.

Ian T. Reed

Associate Geologist

Robert E. Kitay, R.G., R.E.A.

Senior Geologist

Attachments: Tables One through Three

Figures 1 and 2

Appendices A through E

cc: Mr. Kevin Romak, Romak Iron Works

Ms. Susan Hugo, Alameda County Health Care Services Agency

Mr. Chuck Headlee, California Regional Water Quality Control Board




TABLE ONE FIVE Certified Analytical Results of GROUNDWATER Samples Monitoring Well MW-1 TPH-G, TPH-D, BTEX and MTBE All results are in parts per billion

		Sampling Date	TPH Gasoline	TPH Diesel	Benzene	Toluene	Ethyl Benzene	Total Xylenes	MTBE
		08-04-93	12,000	همو عبي ميه ممر عبي عبر ضم شد	7.6	9.7	9.9	29	
1	9.65	11-18-93	10,270		3,169	<i>38.</i> 3	661.2	659.4	
die	11. of	02-09-94	17.000		6,200	64	770	420	
sheh	12. 42	05-25-94	24,000		6,200	27	1,100	210	
Eyeen !		→ 08-18-94	22,000	بين شو شو	5,000	10	740	150	
Sylin	12.54	11-14-94	20,000	4,200 4,600	4,200	25	860	450	
Sher	4.20	- 02-03-95 -	**20,000	4,600'	3,400	11	810	100	
Shehn	11.63	→ 05-02-95	21,000	3,400	3,100	21	910	130	
Sylle	265	~ 08-08-95	17,000	1,800	2,800	11	680	63	
Eyeen	6.3	1-13-95	17,000	<1,000	2,300	8	550	69	
Juan		02-16-96	8,900	7,600	3,100	21	760	474	< 40
huln	5.13 -	- 05-17-96	9,900	1,400	2,100	6	560	23	12 <i>0</i>
A		08-01-96	11,000	5,100 ²	1,600	14	580	66	< 50
Sheen	10.06	√ 11-12-96	13,000	6,000	910	27	440	440	85
Sheen	5.64	- 02-06-97	16,000	7,000	1,200	170	660	410	< 500
Sulv	664	05-21-97	8,600	2,900 ¹	72 <i>0</i>	< 10	460	41	17 <i>0</i>
sheen	. gshl.	- 09-24-97	6,400	2,600	520	12	310	13	210
sleen	7.4	-03-04-98	6,500	3,300 ²	<i>650</i>	2.3	290	35	98
Silvenia	7.65	- 09-18-98	5,400	2,000 ²	980	· 11	150	24	< 50
dien	121.	- 03-10-99	6,600	2,500 ²	470	<i>8</i> 5	130	20	< 50
Almo	428	- 09-09-99	2,300	2,400 ²	<i>330</i>	11	48	19	61
shew	, 7.0	03-02-00	6,700 ²	670 ²	440	< 2.5	65	< 2.5	77
		08-17-00*	840 ²	1,100 ²	55	0.74	7.5	< 0.5	23

Notes:

--- = Not analyzed

NE = Not established

DHS= California Department of Health Services

MCL = maximum contaminant level for drinking water

1 = motor oil detected

2 = Fuel pattern does not match hydrocarbon standard

* = Motor Oil detected at 700 parts per billion

TABLE TWO .

Summary of Chemical Analysis of SOIL Samples

Romak Iron Works - Collected on August 17, 2000

Petroleum Hydrocarbons

All results are in parts per million

Boring - Depth	TPH Gasoline	TPH Diesel	TPH Motor Oil	Benzene	Toluene	Ethyl Benzene	Total Xylenes	MTBE
<u> </u>				201,201,0	. 0.000.10	55,125,15	7.0.00	
BH-A-15.5'	< 1.0	< 1.0	< 50	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005
BH-B-7.5'	< 1.0	< 1.0	< 50	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005
BH-C-18.0'	< 1.0	< 1.0	< 50	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005
BH-D-18.0°	< 1.0	< 1.0	< 50	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005
BH-E-19.0'	< 1.0	< 1.0	< 50	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005
BH-F-11.5'	< 1.0	< 1.0	<50	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005

Notes:

MTBE = Methyl-t-butyl ether

PRG = United States Environmental Protection Agency Region IX Preliminary Remediation Goal for Residential Soil.

NE = PRG has not been established.

Non-detectable concentrations are noted by the less than symbol (<) followed by the detection limit.

Detectable concentrations are in bold.

TABLE THREE

Summary of Chemical Analysis of GROUNDWATER Samples

Romak Iron Works - Collected on August 17, 2000

Petroleum Hydrocarbons

All results are in parts per billion

Boring	TPH Gasoline	TPH Diesel	TPH Motor Oil	Benzene	Toluene	Ethyl Benzene	Total Xylenes	МТВЕ
ВН-А	< 50	< 71**	< 710**	< 0.5	< 0.5	< 0.5	< 0.5	< 5.0
ВН-В	< 50	< <i>8</i> 3	< 830**	< 0.5	< 0.5	< 0.5	< 0.5	< 5.0
ВН-С	< 50	150*	< 770**	< 0.5	< 0.5	< 0.5	0.8	< 5.0
BH-D	< 50	< 100**	< 1,000**	< 0.5	< 0.5	< 0.5	< 0.5	< 5.0
ВН-Е	< 50	< 61**	< 610**	< 0.5	< 0.5	< 0.5	< 0.5	< 5.0
BH-F	< 5 <i>0</i>	< 59**	< 590**	< 0.5	< 0.5	< 0.5	<i>0.</i> 81	< 5.0
DHS MCL.	NE	is NE s	NE		150	700	1,750	13

Notes:

MTBE = Methyl-t-butyl ether

DHS MCL is the California Department of Health Services maximum contaminant level for drinking water.


NE = DHS MCLs are not established.


Non-detectable concentrations are noted by the less than symbol (<) followed by the detection limit.

Detectable concentrations are in bold.

^{*} Hydrocarbon reported does not match the laboratory diesel standard.

^{**} Laboratory detection limits raised due to limited samples size.






Romak Iron Works 3250 Hollis Street Oakland, California

Aqua Science Engineers

Figure 1

BASE: USGS Oakland West 7.5 minute quadrangle topographic r dated 1980, scale 1:24,000.





• Geoprobe Location

MW-1

Monitoring Well



MONTORING WELL AND BORING LOCATION

Romak Iron Works 3250 Hollis Street Oakland, California

AQUA SCIENCE ENGINEERS, INC.

FIGURE 2

APPENDIX A

Permits

Sont by: AQUA SCIENCE

Aud-11-80 89120am

from \$258374853}5187821939



ALAMEDA COUNTY PUBLIC WORKS AGENCY

WATER RESOURCES SECTION

399 BLMHULGT ST. HAYWARD, CA 94544-1395

THOME (310) (710-1554) (MARION MAGALANIES) X (510) 782-1939

(510) (470-5783) (FLANK CODD)

A CONTROL	<u>'</u>
DRILLING PERMI	T APPLICATION
FOR APPLICANT TO COMPLETE OCATION OF PROJECT, 32 50 Hollis Street Ooklonel, ca	PERMIT NUMBER WO-498 WELL NUMBER
Celliomia Coordinates Source	PERMIT CONDITIONS Circled Permit Requirements Apply
CLIENT Name Kevin Romak Address 3250 Halle 51 Phone City Ocklend CA 210 Gyllez 10588. APPLICANT Name Aqua Science Engineers Inc. Address 288 W CL Promises Phane 9271840—1857 937 1 City Departe Zip Geotechnical Investigation Cathodic Protection O General O Water Supply O Contamination W Monitoring O Well Destruction O PROPOSED WATER SUPPLY WELL USE New Domestic O Replacement Domestic O Municipal O Invigation O BRILLING METHODI Mud Rotery O Air Rotary O Auger O Coble O Other A Graphobe DRILLER'S LICENSE NO. C-57 405927 WELL PROJECTS Drill Hole Diameter In Maximum Casing Diameter In Maximum Casing Diameter In Depth R. Surface Scal Depth In Number	A. GENERAL A permit application should be submitted so as to arrive at the ACPWA office five days prior to proposed storting date. Submit to ACPWA within 60 days after completion of permitted work the original Department of Water Resources Water Well Drillers Report or equivalent for well projects, or drilling logs and location akotch for well projects, or drilling logs and location akotch for well projects. 1. Fermit is void if project not begun within 80 days of approval date. 8. WATER SUPPLY WELLS 1. Minimum seriace seal thickness is two inches of cement grout placed by tremie. 2. Minimum seal depth is 50 fact for municipal and industrial wells or 20 feet for domantic and irrigation wells unless a lesser depth is appealably approved. C. GROUNDWATER MONITORING WELLS 1. Minimum surface seal thickness is two inches of cement grout placed by tremis. 2. Minimum seal depth for monitoring wells is the maximum depth practicable or 20 feet. D. GEOTECHNICAL Backfill bore hole with compacted outlings or heavy bentoning and upper two feet with compacted nucterial. In kreaze of known or suspecied contamination, tremiod coment grout shall be used in place of compacted cuttings. E. CATHODIC Fill hole above anode zone with contrets placed by tremic. 5. WELL DESTRUCTION See aliached. G. SPECIAL CONDITIONS
GEOTECHNICAL PROJECTS Number of Borings 4 Maximum Hole Diameter 2 in. Depth 12 ft.	· M

APPROVED

I hereby agree to camply with all requirements of this permit and Alameda County Ordinance No. 73-68.

BILLING

APPLICANT'S SIGNATURE

ESTIMATED STARTING DATE ______

DATE\$-15-00



EXCAVATION PERMIT

CIVIL ENGINEERING

PAGE 2 of 2

TO EXCAVATE IN STREETS OR OTHER SPECIFIED WORK

		•
PERMIT NUMBER	00000	SITE ADDRESS/LOCATION
X	0001309	3250 Holles St
APPROX. START DATE	APPROX. END DATE	24-HOUR EMERGENCY PHONE NUMBER
		(Permit not valid without 24-Hour number)
CONTRACTOR'S LICENSE # A	L L L L L L L L L L L L L L L L L L L	CITY BUSINESS TAX #
	487000	
ATTENTION:		
1) State law requires that inquiry identification n	the contractor/owner call Underground Ser umber issued by USA. The USA telephone	pice Alert (USA) two working days before excavating. This permit is not valid unless applicant has secured an number is 1 (800) 642-2444. UNDERGROUND SERVICE ALERT (USA) #:
2) 48 hours prior	to starting work, YOU MU	ST CALL (510) 238-3651 TO SCHEDULE AN INSPECTION.
OWNER/BUILDER		
provisions of the Contractor's Licer alleged exemption. Any violation Col. I, as an owner of the property, Professions Code: The Contractor' provided that such improvements at turden of proving that he did not bo. I, as owner of the property, am be performed prior to sale, (3) I has structures more than once during at I. as owner of the property, am does not apply to an owner of property.	nse law Chapter 9 (commencing with Sec. 7 of Section 7031.5 by any applicant for a per or my employees with wages as their sole ce is License Law does not apply to an owner or not intended or offered for sale. If howe wild or improve for the purpose of sale), exempt from the sale requirements of the always three-year period, (Sec. 7044 Business at exclusively contracting with licensed contracting with high property who builds or improves thereon, and we can be seen to the sale of t	te, also requires the applicant for such permit to file a signed statement that he is licensed pursuant to the 1000) of Division 3 of the Business and Professions Code, or that he is exempt therefrom and the basis for the mit subjects the applicant to a civil penalty of not more than \$500): compensation, will do the work, and the structure is not intended or offered for sale (Sec. 7044, Business of property who builds or improves thereon, and who does such work himself or through his own employees, wer, the building or improvement is sold within one year of completion, the owner-builder will have the soove due to: (1) I am improving my principal place of residence or appurtenances thereto, (2) the work will a prior to completion of the work, and (4) I have not claimed exemption on this subdivision on more than two and Professions Code). ctors to construct the project, (Sec. 7044, Business and Professions Code: The Contractor's License Law the contracts for such projects with a contractor(s) licensed pursuant to the Contractor's License law).
WORKER'S COMPENSATION		*
☐ I hereby affirm that I have a cer	tificate of consent to self-insure, or a certifi	cate of Worker's Compensation Insurance, or a certified copy thereof (Sec. 3700, Labor Code).
Policy #	Company Name	
I certify that in the performance of California (not required for work	of the work for which this permit is issued at one hundred dollars (\$100) or le	, I shall not employ any person in any manner so as to become subject to the Worker's Compensation Laws
comply with such provisions or this granted upon the express condition perform the obligations with respect and employees, from and against an sustained or arising in the constructi	permit shall be deemed revoked. This pen that the permittee shall be responsible for at to street maintenance. The permittee shall by and all suits, claims, or actions brought by and all suits, claims, or actions the permit on of the work performed under the permit	a should become subject to the Worker's Compensation provisions of the Labor Code, you must forthwith mit is issued pursuant to all provisions of Title 12 Chapter 12.12 of the Oakland Municipal Code. It is a claims and liabilities arising out of work performed under the permit or arising out of permittee's failure to and by acceptance of the permit agrees to defend, indemnify, save and hold harmless the City, its officers y any person for or on account of any bodily injuries, disease or illness or damage to persons and/or property or in consequence of permittee's failure to perform the obligations with respect to street maintenance. This by the Director of the Office of Planning and Building.
I hereby affirm that I am licensed ur this permit and agree to its requirem	nder provisions of Chapter 9 of Division 3 of that the above information is true	of the Business and Professions Code and my license is in full force and effect (if contractor), that I have read and correct under penalty of law.
Signature of Permittee	G Agent for Contractor Owner	Easing Inc & E/10/00
DATE STREET LAST	117	HOLIDAY RESTRICTION? LIMITED OPERATION AREA?
RESURFACED	REQUIRED? DYES DNO	(NOVI-JANI) DYES DNO (JAM-9AM & 4PM-6PM) DYES DNO
ISSUED BY	\wedge	DATE ISSUED
	-	8.16.00
		V 1 N

APPENDIX B

Boring Logs

Project Name: Romak fron Works Diller: Vironex Type of Rig: Geoprobe Size of Drill: 2.0' Diameter Logged By: Ian T. Reed Date Drilled: August 17, 2000 Checked By: Robert E. Kitay, R.G. WATER AND WELL DATA Depth of Water First Encountered: 16' Static Depth of Water in Well: NA Total Depth of Boring: 24.0' Type and Diameter: NA Well Screen Type and Diameter: NA Well Screen Slot Size: NA Total Depth of Boring: 24.0' Type and Size of Soil Sampler: 2.0' LD. Macro Sampler DESCRIPTION OF LITHOLOGY standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation. DESCRIPTION OF LITHOLOGY standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation. DESCRIPTION OF LITHOLOGY standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation. DESCRIPTION OF LITHOLOGY standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation. DESCRIPTION OF LITHOLOGY standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation. Sandy SILT (ML); dark brown; damp; stiff; 75% slit; 25% fine to coarse sand; low plasticity very low astimated K; no odor 10 Sandy SILT (ML); brown; very moist; stiff; 50% clay; 30% fine to medium sand; 20% slit; trace grave; medium plasticity; very low estimated K; no odor 20 End of Boring at 24.0' End of Boring at 24.0'	SOIL BORING LOG AND MONITORING WELL COMPLETION DETAILS Boring: BH-A						
Logged By: Ian T. Reed Date Drilled: August 17, 2000 Checked By: Robert E. Kitay, R.G. WATER AND WELL DATA Depth of Water First Encountered: 16' Static Depth of Water in Well: NA Well Screen Type and Diameter: NA Well Screen Stot Size: NA Total Depth of Boring: 24.0' Type and Size of Soil Sampler: 2.0" I.D. Macro Sampler DESCRIPTION OF LITHOLOGY standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation. O Asphalt Sandy SILT (ML); dark brown; damp; serif; 75% slit; 25% fine to coarse sand; trace clay; very low plasticity; low estimated K; no odor Silty CLAY (CL); light brown; damp; very sliff; 60% clay; 20% slit; 20% fine to coarse sand; low plasticity very low estimated K; no odor 10 10 10 10 110 125 Sandy CLAY (CL); brown; very moiat; stiff; 50% clay; 30% fine to medium sand; 20% slit; trace grave); medium plasticity; very low estimated K; no odor 20 End of Boring at 24.0'	Project Name: Romak Iron Works	Project Location	ion: 3250 Hollis St., Oakland, CA Page 1 of 1				
WATER AND WELL DATA Depth of Water First Encountered: 16' Well Screen Type and Diameter: NA Well Screen Slot Size: NA Total Depth of Water in Well: NA Well Screen Slot Size: NA Total Depth of Boring: 24.0' Type and Size of Soil Sampler: 2.0" (LD. Macro Sampler DESCRIPTION OF LITHOLOGY standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation. O Asphalt Sandy SILT (ML); dark brown; damp; serif; 75% silt; 25% fine to coarse sand; low plasticity; low estimated K; no odor Silty CLAY (CL); light brown; damp; very silf; 60% clay; 20% silt; 20% fine to coarse sand; low plasticity very low estimated K; no odor 10 Sandy CLAY (CL); brown; very moist; stiff; 50% clay; 30% fine to medium sand; 20% silt: trace grave); medium plasticity; very low estimated K; no odor 20 End of Boring at 24.0'	Driller: Vironex	Type of Rig: G	Geoprobe Size of Drill: 2.0" Diameter				
Depth of Water First Encountered: 16' Static Depth of Water in Well: NA Total Depth of Boring: 24.0' Type and Size of Soll Sampler: 2.0" (I.D. Macro Sampler) SOIL/ROCK SAMPLE DATA BORING DETAIL BORING DESCRIPTION OF LITHOLOGY standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation. Asphalt Sandy SILT (ML); dark brown; damp; stiff; 75% silt; 25% line to coarse sand; low plasticity very low estimated K; no odor 10 Solly CLAY (CL); light brown; damp; very sliff; 80% clay; 30% fine to medium sand; 20% silt; trace grave; medium plasticity; very low estimated K; no odor 20 End of Boring at 24.0' End of Boring at 24.0'	Logged By: Ian T. Reed	Date Drilled:	August 17, 2000 Checked By: Robert E. Kitay, R.G.				
Static Dapth of Water in Well: NA Total Depth of Boring: 24.0' Type and Size of Soil Sampler: 2.0" LID. Macro Sampler DESCRIPTION OF LITHOLOGY standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation. Asphalt Sandy SiLT (ML); dark brown; damp; stiff; 75% silt; 25% line to coarse sand; trace clay; very low plasticity; low estimated K; no odor 10 Sandy CLAY (CL); light brown; damp; very sliff; 60% clay; 20% silt; 20% s	WATER AND WELL DATA		Total Depth of Well Completed: NA				
Total Depth of Boring: 24.0' Type and Size of Soil Sampler: 2.0" I.D. Macro Sampler DESCRIPTION OF LITHOLOGY standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation. O Asphalt Sandy SILT (ML); dark brown; damp; stiff; 75% silt; 25% fine to coarse sand; trace clay; very low plasticity; low estimated K; no odor Silty CLAY (CL); light brown; damp; very stiff; 60% clay; 30% fine to medium sand; 20% silt; trace gravel; medium plasticity; very low estimated K; no odor End of Boring at 24.0' End of Boring at 24.0'	Depth of Water First Encountered: 16'		Well Screen Type and Diameter: NA				
SOIL/ROCK SAMPLE DATA L. S. BORING DETAIL BORING	Static Depth of Water in Well: NA		Well Screen Slot Size: NA				
BORING DETAIL Second BORING DETAIL Second Boring at 24.0' Boring at 24.0'	<u> </u>						
Sching DETAIL The purple of t		1	DESCRIPTION OF LITHOLOGY				
Sandy SILT (ML); dark brown; damp; stiff; 75% silt; 25% fine to coarse sand; trace clay; very low plasticity; low estimated K; no odor Silty CLAY (CL); light brown; damp; very stiff; 60% clay; 20% silt; 20% fine to coarse sand; low plasticity very low estimated K; no odor Sandy CLAY (CL); light brown; damp; very stiff; 60% clay; 20% silt; 20% fine to coarse sand; low plasticity very low estimated K; no odor Sandy CLAY (CL); brown; very moist; stiff; 50% clay; 30% fine to medium sand; 20% silt; trace gravel; medium plasticity; very low estimated K; no odor End of Boring at 24.0'	Descriptic Descriptic Descriptic OVM (ppm Descriptic Description Descriptic Description Descriptic Description Descr	Water Leve Graphic Log	standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation.				
	Portland Cement Portland Cement To 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	▼ [:	Sandy SILT (ML); dark brown; damp; stiff; 75% silt; 25% fine to coarse sand; trace clay; very low plasticity; low estimated K; no odor Silty CLAY (CL); light brown; damp; very stiff; 60% clay; 20% silt; 20% fine to coarse sand; low plasticity very low estimated K; no odor Sandy CLAY (CL); brown; very moist; stiff; 50% clay; 30% fine to medium sand; 20% silt; trace gravel; medium plasticity; very low estimated K; no odor End of Review of CLAY				

SOIL BORING LOG AND MONITORING WELL COMPLETION DETAILS Boring: BH-B							
<u></u>							
Project Name: Romak Iron Works		on: 3250 Hollis St., Oakland, CA Page 1 of 1					
Driller: Vironex	Type of Rig: G						
Logged By: Ian T. Reed	Date Drilled:	August 17, 2000 Checked By: Robert E. Kitay, R.G.					
WATER AND WELL DATA		Total Depth of Weil Completed: NA					
Depth of Water First Encountered: 20	.0'	Well Screen Type and Diameter: NA					
Static Depth of Water in Well: NA	·	Well Screen Slot Size: NA					
Total Depth of Boring: 28.0'		Type and Size of Soil Sampler: 2.0" I.D. Macro Sampler					
1 × 1 — ———————————————————————————————	SAMPLE DATA	DESCRIPTION OF LITHOLOGY					
Depth in Fe Description Interval Blow Counts	Water Level Graphic Log	DESCRIPTION OF LITHOLOGY standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation.					
-0 - 5 - 10 - 15 - 15 - 10 - 20 - 25 - 25 - 25 - 25 - 25 - 25 - 2		Concrete Clayey SILT (ML); dark brown; damp; very stiff; 60% silt; 40% clay; trace sand; low plasticity; very low estimated K; no odor Silty CLAY (CL); light brown with speckled gray; damp; very stiff; 60% clay; 30% silt; 10% fine sand; low plasticity; very low estimated K; no odor very slight hydrocrabon odor at 7.5' speckled green, slight hydrocarbon odor trace gravel to 0.5" diameter Silty SAND (SM): brown; wet; medium stiff; 60% fine to medium sand; 30% silt; 10% clay; low plasticity; medium estimated K; no odor Silty CLAY (CL); light brown with speckled gray; damp; very sliff; 60% clay; 30% silt; 10% fine sand; low plasticity; very low estimated K; no odor wet at 20' End of Boring at 28.0'					
		aqua science engineers, inc.					

Project Name: Romak Iron Works Project Location: 3250 Hollis St., Oakland, CA Page 1 of 1	SOIL BORING LOG AND MONITORING WELL COMPLETION DETAILS Boring: BH-C					
Logged By: Ian T. Read Date Drilled: August 17, 2000 Checked By: Robert E. Kitay, R.G. WATER AND WELL DATA Depth of Well Completed: NA Well Screen Type and Diameter: NA Well Screen Siot Size: NA Total Depth of Boring: 24.0' Type and Size of Soil Sampler: 2.0" I.D. Macro Sampler Type and Size of Soil Sampler: 2.0" I.D. Macro Sampler DESCRIPTION OF LITHOLOGY standard classification, texture, relative moisture, density, stiffness, edor-staining, USCS designation. Concrete Saldy SILT (ML); brown to light brown; damp; very stiff; 60% clay; 30% stit; 10% fine to coarse sand; trace gravel to 0.5" diameter; low plasticity; very low estimated K; no odor Stity CLAY (CL); brown with black speckles; damp; very stiff; 60% clay; 30% stit; 10% fine sand wet at 13' gray to light brown; 70% clay; 20% slit; 10% fine sand wet at 13' gray to light brown; 70% clay; 30% slit; damp to moist; no odor End of Boring at 24.0'	Project Name: Romak Iron Works	Project Location	on: 3250 Hollis St., Oakland, CA Page 1 of 1			
Water First Encountered: 13.0' Static Depth of Water First Encountered: 13.0' Well Screen Type and Diameter: NA Well Screen Siot Size: NA Total Depth of Boring: 24.0' Type and Size of Soil Sampler: 2.0" I.D. Macro Sampler DESCRIPTION OF LITHOLOGY Standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation. Concrete Siffy CLAY (CL); brown with black speckles; damp; very stiff; 60% clay; 30% stit; 10% fine to coarse sand; trace gravel to 0.5' diameter; low plasticity; very low estimated K; no odor Siffy CLAY (CL); brown; 70% clay; 20% stit; 10% fine sand wet at 13' gray to light brown; 70% clay; 20% stit; damp to moist; no odor End of Boring at 24.0'	Driller: Vironex	Type of Rig: G	seoprobe Size of Drill: 2.0" Diameter			
Depth of Water First Encountered: 13.0' Static Depth of Water in Well: NA Total Depth of Boring: 24.0' Type and Size of Soil Sampler: 2.0' I.D. Macro Sampler Type and Size of Soil Sampler: 2.0' I.D. Macro Sampler DESCRIPTION OF LITHOLOGY standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation. Concrete Sandy SILT (ML); brown to light brown; damp; very stiff; 60% clay; 30% silt; 10% fine to coarse sand; trace gravel to 0.5' diameter; low plasticity; very low estimated K; no odor Sitty CLAY (CL): brown with black speckles; damp; very stiff; 60% clay; 30% silt; 10% fine to coarse sand; trace gravel to 0.5' diameter; low plasticity; very low estimated K; no odor Sitty CLAY (CL): brown; 70% clay; 20% silt; 10% fine sand wet at 13' gray to light brown; 70% clay; 30% silt; damp to moist; no odor End of Boring at 24.0' End of Boring at 24.0'	Logged By: Ian T. Reed	Date Drilled:	August 17, 2000 Checked By: Robert E. Kitay, R.G.			
Static Depth of Water in Well: NA Total Depth of Boring: 24.0' Type and Size of Soil Sampler: 2.0" I.D. Macro Sampler DESCRIPTION OF LITHOLOGY standard classification, texture, relative moisture, density, stiffness, odor-staining. USCS designation. Concrete Sandy SiLT (ML); brown to light brown; damp; very stiff; 60% clay; 30% silt; 10% fine to coarse sand; trace gravel to 0.5' diameter; low plasticity; very low estimated K; no odor Sity CLAY (CL); brown with black speckles; damp; very stiff; 60% clay; 30% silt; 10% fine to coarse sand; trace gravel to 0.5' diameter; low plasticity; very low estimated K; no odor Sity CLAY (CL); brown with black speckles; damp; very stiff; 60% clay; 30% silt; 10% fine sand wet at 13' gray to light brown; 70% clay; 20% silt; 10% fine sand wet at 13' gray to light brown; 70% clay; 30% silt; damp to moist; no odor 25 End of Boring at 24.0'	WATER AND WELL DATA		Total Depth of Well Completed: NA			
Total Depth of Boring: 24.0' Type and Size of Soil Sampler: 2.0" I.D. Macro Sampler DESCRIPTION OF LITHOLOGY standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation. O Concrete Sandy SILT (ML); brown to light brown; damp; very stiff; 60% slit; 20% fine to coarse sand; 20% clay; low plasticity; very low estimated K; no odor Sitty CLAY (CL); brown with black speckles; damp; very stiff; 60% clay; 30% slit; 10% fine to coarse sand; trace gravel to 0.5" diameter; low plasticity; very low estimated K; no odor DESCRIPTION OF LITHOLOGY standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation. Concrete Sandy SILT (ML); brown to light brown; damp; very sliff; 60% clay; 30% slit; 10% fine to coarse sand; trace gravel to 0.5" diameter; low plasticity; very low estimated K; no odor DESCRIPTION OF LITHOLOGY standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation. Concrete Sandy SILT (ML); brown to light brown; damp; very sliff; 60% clay; 30% slit; 10% fine to coarse sand; trace gravel to 0.5" diameter; low plasticity; very low estimated K; no odor DESCRIPTION OF LITHOLOGY standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation. Concrete Sandy SILT (ML); brown to light brown; damp; very sliff; 60% clay; 30% slit; 10% fine to coarse sand; trace gravel to 0.5" diameter; low plasticity; very low estimated K; no odor DESCRIPTION OF LITHOLOGY standard classification, texture, relative moisture, density emoisture, density, stiffness, odor-staining, USCS designation.	Depth of Water First Encountered: 13	.0'	Well Screen Type and Diameter: NA			
BORING DETAIL Solitrock sample Data 1 2 2 2 2 2 2 2 2 2	Static Depth of Water in Well: NA		Well Screen Slot Size: NA			
BORING DETAIL Standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation. Concrete Sandy Silt. (ML); brown to light brown; damp; very stiff; 60% silt; 20% fine to coarse sand; trace gravel to 0.5" diameter; low plasticity; very low estimated K; no odor Silty CLAY (CL); brown with black speckles; damp; very stiff; 60% clay; 30% silt; 10% fine to coarse sand; trace gravel to 0.5" diameter; low plasticity; very low estimated K; no odor Silty CLAY (CL); brown with black speckles; damp; very stiff; 60% clay; 30% silt; 10% fine to coarse sand; trace gravel to 0.5" diameter; low plasticity; very low estimated K; no odor Silty CLAY (CL); brown with black speckles; damp; very stiff; 60% clay; 30% silt; 10% fine sand wet at 13' gray to light brown; 70% clay; 20% silt; 10% fine sand wet at 13' gray to light brown; 70% clay; 30% silt; damp to moist; no odor Silty CLAY (CL); brown with black speckles; damp; very stiff; 60% clay; 30% silt; 10% fine sand wet at 13' gray to light brown; 70% clay; 30% silt; damp to moist; no odor Silty CLAY (CL); brown with black speckles; damp; very stiff; 60% clay; 30% silt; 10% fine to coarse sand; trace gravel to 0.5" diameter; low plasticity; very low estimated K; no odor Silty CLAY (CL); brown with black speckles; damp; very stiff; 60% clay; 30% silt; 10% fine to coarse sand; trace gravel to 0.5" diameter; low plasticity; very low estimated K; no odor Silty CLAY (CL); brown with black speckles; damp; very stiff; 60% clay; 30% silt; 10% fine to coarse sand; trace gravel to 0.5" diameter; low plasticity; very low estimated K; no odor Silty CLAY (CL); brown with black speckles; damp; very stiff; 60% silt; 20% clay; 30% silt; 10% fine to coarse sand; trace gravel to 0.5" diameter; low plasticity; very low estimated K; no odor	Total Depth of Boring: 24.0'		Type and Size of Soil Sampler: 2.0" I.D. Macro Sampler			
25 End of Boring at 24.0'	Portland Cement Portland Cement Blow Counts Description Blow Counts	Water Level Graphic Log	Standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation. Concrete Sandy SILT (ML); brown to light brown; damp; very stiff; 60% silt; 20% fine to coarse sand; 20% clay; low plasticity; very low estimated K; no odor Silty CLAY (CL); brown with black speckles; damp; very stiff; 60% clay; 30% silt; 10% fine to coarse sand; trace gravel to 0.5" diameter; low plasticity; very low estimated K; no odor brown to light brown; 70% clay; 20% silt; 10% fine sand wet at 13' gray to light brown; 70% clay; 30% silt; damp to moist; no odor			
AQUA SCIENCE ENGINEERS, INC.			-30			

Project Name: Romak Iron Works Driller: Vironex Type of Rig: Geoprobe Logged By: Ian T. Reed Date Drilled: August 17, 2000 Checked By: Robert E. Kitay, R.G. WATER AND WELL DATA Depth of Water First Encountered: 17.0° Static Depth of Water in Well: NA Total Depth of Boring: 28.0° BORING DETAIL DETAIL Depth of Boring: 28.0° DETAIL OPERAL OPER	SOIL BORING LOG AND MONIT	ORING WELL	L COMPLETION DETAILS Boring: BH-D
Logged By: fan T. Reed Date Drilled: August 17, 2000 Checked By: Robert E. Kitay, R.G. WATER AND WELL DATA Depth of Water First Encountered: 17.0' Static Depth of Water in Well: NA Total Depth of Water in Well: NA Total Depth of Boring: 28.0' Type and Size of Soil Sampler: 2.0" I.D. Macro Sampler Type and Size of Soil Sampler: 2.0" I.D. Macro Sampler DESCRIPTION OF LITHOLOGY standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation. Concrete Sandy SILT (ML); dark brown; damp; very stiff; 70% slit; 25% fine to coarse sand; 5% clay; low plasticity; very low estimated K; no odor Concrete Sandy CLAY (CL); light brown with black speckles; damp; stiff; 80% clay; 25% slit; 15% fine to coarse sand; low plasticity; very low estimated K; no odor Sandy CLAY (CL); light brown with black speckles; damp; stiff; 80% clay; 25% slit; 15% fine to coarse sand; low plasticity; very low estimated K; no odor Sandy CLAY (CL); light brown with black speckles; damp; stiff; 80% clay; 25% slit; 15% fine to coarse sand; low plasticity; very low estimated K; no odor Silty CLAY (CL); light brown with black speckles; damp; stiff; 80% clay; 25% slit; 15% fine to coarse sand; low plasticity; very low estimated K; no odor Silty CLAY (CL); light brown with black speckles; damp; stiff; 80% clay; 25% slit; 15% fine to coarse sand; low plasticity; very low estimated K; no odor Silty CLAY (CL); light brown with black speckles; damp; stiff; 80% clay; 25% slit; 15% fine to coarse sand; low plasticity; very low estimated K; no odor Fine sand layer at 22' - 23' End of Boring at 28.0'	Project Name: Romak Iron Works	Project Locati	tion: 3250 Hollis St., Oakland, CA Page 1 of 1
WATER AND WELL DATA Depth of Welter First Encountered: 17.0' Well Screen Type and Diameter: NA Well Screen Stot Size: NA Total Depth of Boring: 28.0' Type and Size of Soil Sampler: 2.0" i.D. Macro Sampler Soil/FIGCK SAMPLE DATA BERNING DETAIL BORING DET	Driller: Vironex	Type of Rig: G	Geoprobe Size of Drill: 2.0" Diameter
Depth of Water First Encountered: 17.0" Well Screen Type and Diameter: NA Well Screen Type and Diameter: NA Well Screen Type and Diameter: NA Total Depth of Water in Well: NA Total Depth of Boring: 28.0" SOIL/ROCK SAMPLE DATA BORING DETAIL BORING DETAIL BORING DETAIL SOIL/ROCK SAMPLE DATA Concrete Sandy SILT (ML); dark brown; damp; very stiff; 70% slit; 25% fine to coarse sand; 5% clay; low plasticity; very low estimated K; no odor Sity CLAY (CL); light brown with black speckles; damp; stiff; 60% clay; 25% slit; 15% fine to coarse sand; low plasticity; very low estimated K; no odor Sandy CLAY (CL); light brown to gray; damp; very sliff; 80% clay; 30% fine to coarse sand; low plasticity; very low estimated K; no odor Sandy CLAY (CL); light brown with black speckles; damp; sliff; 60% clay; 25% slift; 15% fine to coarse sand; low plasticity; very low estimated K; no odor Sandy CLAY (CL); light brown with black speckles; damp; sliff; 60% clay; 25% slift; 15% fine to coarse sand; low plasticity; very low estimated K; no odor Sandy CLAY (CL); light brown with black speckles; damp; sliff; 60% clay; 25% slift; 15% fine to coarse sand; low plasticity; very low estimated K; no odor Sandy CLAY (CL); light brown with black speckles; damp; sliff; 60% clay; 25% slift; 15% fine to coarse sand; low plasticity; very low estimated K; no odor Sandy CLAY (CL); light brown with black speckles; damp; sliff; 60% clay; 25% slift; 15% fine to coarse sand; low plasticity; very low estimated K; no odor End of Boring at 28.0'	Logged By: Ian T. Reed	Date Drilled:	August 17, 2000 Checked By: Robert E. Kitay, R.G.
Static Depth of Water in Well: NA Total Depth of Boring: 28.0' BORING DETAIL BORING DETAIL BORING DETAIL Type and Size of Soil Sampler: 2.0" I.D. Macro Sampler DESCRIPTION OF LITHOLOGY standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation. Concrete Sandy SILT (MLL); dark brown; damp; very stiff; 70% slit; 25% fine to coarse sand; 5% clay; low plasticity; very low estimated K; no odor Sity CLAY (CL); light brown with black speckles; damp; stiff; 60% clay; 25% slit; 15% fine to coarse sand; low plasticity; very low estimated K; no odor Sandy CLAY (CL); light brown with black speckles; damp; stiff; 60% clay; 25% slit; 15% fine to coarse sand; low plasticity; very low estimated K; no odor Sandy CLAY (CL); light brown with black speckles; damp; stiff; 60% clay; 25% slit; 15% fine to coarse sand; low plasticity; very low estimated K; no odor Sity CLAY (CL); light brown with black speckles; damp; stiff; 60% clay; 25% slit; 15% fine to coarse sand; low plasticity; very low estimated K; no odor Sity CLAY (CL); light brown with black speckles; damp; slity; very low estimated K; no odor Sity CLAY (CL); light brown with black speckles; damp; slity; every low estimated K; no odor Sandy CLAY (CL); light brown with black speckles; damp; slity; every low estimated K; no odor Sandy CLAY (CL); light brown with black speckles; damp; slity; every low estimated K; no odor End of Boring at 28.0'	WATER AND WELL DATA		Total Depth of Well Completed: NA
Total Depth of Boring: 28.0' Type and Size of Soil Sampler: 2.0* I.D. Macro Sampler DESCRIPTION OF LITHOLOGY standard classification, texture, relative moisture, density, stiffness, odor-stalning, USCS designation. Concrete Sandy SILT (ML); dark brown; damp; very stiff; 70% slit; 25% fine to coarse sand; 5% clay; low plasticity; very low estimated K; no odor 10 10 10 10 10 10 10 10 10 1	Depth of Water First Encountered: 17.	.0'	Well Screen Type and Diameter: NA
SOLLROCK SAMPLE DATA BORING DETAIL BORICH STIMP, Very low estimated K; no odor BORING DETAIL	Static Depth of Water in Well: NA	······································	Well Screen Slot Size: NA
BORING DETAIL Solution Detail Description of Lithology Standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation.	Total Depth of Boring: 28.0'		Type and Size of Soil Sampler: 2.0" I.D. Macro Sampler
SOFING DETAIL The purple of t	[\(\text{\text{\$\}}}}}}}}}}}}}}}}}}}}}}}}}}}}}}}}}}}}	\	DESCRIPTION OF LITHOLOGY
Sandy SILT (ML); dark brown; damp; very stiff; 70% slit; 25% fine to coarse sand; 5% clay; low plasticity; very low estimated K; no odor Silty CLAY (CL); light brown with black speckles; damp; stiff; 60% clay; 25% slit; 15% fine to coarse sand; low plasticity; very low estimated K; no odor Sandy CLAY (CL); brown to gray; damp; very stiff; 60% clay; 30% fine to coarse sand; 10% slit; very low plasticity; very low estimated K; no odor Sandy CLAY (CL); brown to gray; damp; very stiff; 60% clay; 30% fine to coarse sand; 10% slit; very low plasticity; very low estimated K; no odor Silty CLAY (CL); light brown with black speckles; damp; stiff; 60% clay; 25% slit; 15% fine to coarse sand; low plasticity; very low estimated K; no odor fine sand layer at 22' - 23' End of Boring at 28.0'	Descriptio Descriptio Descriptio OVM (ppm)	Water Leve Graphic Log	standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation.
	Sortiand Cement Portland Cement	<u> </u>	Sandy SILT (ML); dark brown; damp; very stiff; 70% silt; 25% fine to coarse sand; 5% clay; low plasticity; very low estimated K; no odor Silty CLAY (CL); light brown with black speckles; damp stiff; 60% clay; 25% silt; 15% fine to coarse sand; low plasticity; very low estimated K; no odor Sandy CLAY (CL); brown to gray; damp; very stiff; 60 clay; 30% fine to coarse sand; 10% silt; very low plasticity; very low estimated K; no odor Silty CLAY (CL); light brown with black speckles; damp stiff; 60% clay; 25% silt; 15% fine to coarse sand; low plasticity; very low estimated K; no odor fine sand layer at 22' - 23' End of Boring at 28.0'

Project Name: Romak Iron Works Driller: Vironex Type of Rig: Geoprobe Logged By: Ian T. Roed Date Drilled: August 17, 2000 Checked By: Robert E. Kitay, R.G. WATER AND WELL DATA Depth of Water First Encountered: 12.5' Static Depth of Boring: 24.0' Total Depth of Boring: 24.0' SOIL/ROCK SAMPLE DATA DETAIL SOIL/ROCK SAMPLE DATA DETAIL OBTAIL SOIL/ROCK SAMPLE DATA SOIL/ROCK SAMPLE DATA OBTAIL SOIL/ROCK SAMPLE DATA SOIL/ROCK SAMPLE DATA SOIL/ROCK SAMPLE DATA OBTAIL SOIL/ROCK SAMPLE DATA SOIL/ROCK SAMPLE DATA OBTAIL SOIL/ROCK SAMPLE DATA OBTAIL SOIL/ROCK SAMPLE DATA OBTAIL SOIL/ROCK SAMPLE DATA O	SOIL BORING LOG AND MONITORING WELL COMPLETION DETAILS Boring: BH-E					
Legged By: Ian T. Reed Date Drilled: August 17, 2000 Checked By: Robert E. Kitay, R.G. WATER AND WELL DATA Depth of Water First Encountered: 12.5' Static Depth of Water First Encountered: 12.5' Well Screen Type and Diameter: NA Total Depth of Boring: 24.0' Type and Size of Soil Sampler: 2.0* I.D. Macro Sampler DESCRIPTION OF LITHOLOGY Sandy SILT (ML); dark brown; damp; very stiff; 60% silt; 30% fine to coarse sand; 10% clay; very low plasticity; very low estimated K; no odor Concrete Sandy SILT (ML); dark brown; damp; very stiff; 60% clay; 30% silt; 10% fine to coarse sand; very low plasticity; very low estimated K; no odor Silty CLAY (CL); light brown; damp; very stiff; 60% clay; 30% silt; 10% fine to coarse sand; very low plasticity; very low estimated K; no odor 10 Silty CLAY (CL); light brown; damp; very stiff; 60% clay; 30% silt; 10% fine to coarse sand; very low plasticity; very low estimated K; no odor 15 Silty CLAY (CL); light brown; damp; very stiff; 60% clay; 30% silt; 10% fine to coarse sand; very low plasticity; very low estimated K; no odor 10 End of Boring at 28.0' End of Boring at 28.0'	Project Name: Romak Iron Works	Project Location	on: 3250 Hollis St., Oakland, CA Page 1 of 1			
MATER AND WELL DATA Dopth of Water First Encountered: 12.5' Static Depth of Water in Well: NA Total Depth of Water In Well: NA Total Depth of Boring: 24.0' Type and Size of Soil Sampler: 2.0* LD. Macro Sampler DESCRIPTION OF LITHCLOGY standard classification, texture, relative moisture, density, stiffness, odor-staining, USCs designation. DETAIL Depth of Well Completed: NA Well Screen Type and Diameter: NA Well Screen Stot Size: NA Type and Size of Soil Sampler: 2.0* LD. Macro Sampler DESCRIPTION OF LITHCLOGY standard classification, texture, relative moisture, density, stiffness, odor-staining, USCs designation. Concrete Sandy SILT (ML); dark brown; damp; very stiff; 60% clay; 30% silt; 30% fine to coarse sand; 10% clay; very low plasticity; very low estimated K; no odor Silty CLAY (CL); light brown; damp; very stiff; 60% clay; 30% silt; 10% fine to coarse sand; very low plasticity; very low estimated K; no odor 10 Silty CLAY (CL); light brown; damp; very stiff; 60% clay; 30% silt; 10% fine to coarse sand; very low plasticity; very low estimated K; no odor 10 20 20 End of Boring at 28.0' End of Boring at 28.0'	Driller: Vironex	Type of Rig: G	eoprobe Size of Drill: 2.0" Diameter			
Depth of Water First Encountered: 12.5° Static Depth of Water in Well: NA Total Depth of Boring: 24.0° Total Depth of Boring: 24.0° BORING DETAIL BORING DETAIL Total Depth of Boring: 24.0° SOIL/ROCK SAMPLE DATA BORING DETAIL Total Depth of Boring: 24.0° SOIL/ROCK SAMPLE DATA DESCRIPTION OF LITHOLOGY standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation. Concrete Sandy SILT (ML); dark brown; damp; very stiff; 60% sit; 30% file to coarse sand; 10% clay; very low plasticity; very low estimated K; no odor Stiffy CLAY (CL); light brown; damp; very stiff; 60% clay; 30% silt; 10% fine to coarse sand; very low plasticity; very low estimated K; no odor 10 Lamber Depth of Water in Well: NA Well Screen Type and Diameter: NA Well Screen Slot Size: NA Type and Size of Soil Sampler: 2.0° I.D. Macro Sampler DESCRIPTION OF LITHOLOGY Standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation. Concrete Soily CLAY (CL); light brown; damp; very stiff; 60% clay; 30% silt; 10% fine to coarse sand; very low plasticity; very low estimated K; no odor 10 Lamber Depth of Boring at 28.0° End of Boring at 28.0°	Logged By: Ian T. Reed	Date Drilled:	August 17, 2000 Checked By: Robert E. Kitay, R.G.			
Static Depth of Water in Well: NA Total Depth of Boring: 24.0' Type and Size of Soil Sampler: 2.0" I.D. Macro Sampler DESCRIPTION OF LITHOLOGY standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation. Concrete Sandy SiL7 (ML); dark brown; damp; very stiff; 60% slit; 30% fine to coarse sand; 10% clay; very low plasticity; very low estimated K; no odor Sity CLAY (CL); light brown; damp; very stiff; 60% clay; 30% silt; 10% fine to coarse sand; very low plasticity; very low estimated K; no odor 10 Lack Sity CLAY (CL); light brown; damp; very stiff; 60% clay; 30% silt; 10% fine to coarse sand; very low plasticity; very low estimated K; no odor Lack Sity CLAY (CL); light brown; damp; very stiff; 60% clay; 30% silt; 10% fine to coarse sand; very low plasticity; very low estimated K; no odor Lack Sity CLAY (CL); light brown; damp; very stiff; 60% clay; 30% silt; 10% fine to coarse sand; very low plasticity; very low estimated K; no odor Lack Sity CLAY (CL); light brown; damp; very stiff; 60% clay; 30% silt; 10% fine to coarse sand; very low plasticity; very low estimated K; no odor Lack Sity CLAY (CL); light brown; damp; very stiff; 60% clay; 30% silt; 10% fine to coarse sand; 10% clay; very low estimated K; no odor Lack Sity CLAY (CL); light brown; damp; very stiff; 60% clay; 30% silt; 10% fine to coarse sand; 10% clay; very low estimated K; no odor Lack Sity CLAY (CL); light brown; damp; very stiff; 60% clay; 30% silt; 10% fine to coarse sand; 10% clay; very low estimated K; no odor Lack Sity CLAY (CL); light brown; damp; very stiff; 60% clay; 30% silt; 10% fine to coarse sand; 10% clay; very low estimated K; no odor Lack Sity CLAY (CL); light brown; damp; very stiff; 60% clay; very low estimated K; no odor Lack Sity CLAY (CL); light brown; damp; very stiff; 60% clay; very low estimated K; no odor	WATER AND WELL DATA	;	Total Depth of Well Completed: NA			
Total Depth of Boring: 24.0' Type and Size of Soil Sampler: 2.0* I.D. Macro Sampler DESCRIPTION OF LITHOLOGY standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation. O Concrete Sandy SiLT (ML); dark brown; damp; very stiff; 60% clay; very low plasticity; very low estimated K; no odor Silty CLAY (CL); light brown; damp; very stiff; 60% clay; 30% silt; 10% fine to coarse sand; very low plasticity; very low estimated K; no odor Wet af 12.5' End of Boring at 28.0'	Depth of Water First Encountered: 12.5	5'	Well Screen Type and Diameter: NA			
SOIL/ROCK SAMPLE DATA BORING DETAIL Solid Sample Did Concrete Sandy SiLT (ML): dark brown; damp; very stiff; 60% silt; 30% fine to coarse sand; 10% clay; very low plasticity; very low estimated K; no odor Concrete Sandy SiLT (ML): dark brown; damp; very stiff; 60% silt; 30% fine to coarse sand; 10% clay; very low plasticity; very low estimated K; no odor Silty CLAY (CL): light brown; damp; very stiff; 60% clay; 30% silt; 10% fine to coarse sand; very low plasticity; very low estimated K; no odor Location Details of the coarse sand; 10% clay; very low plasticity; very low estimated K; no odor Silty CLAY (CL): light brown; damp; very stiff; 60% clay; 30% silt; 10% fine to coarse sand; very low plasticity; very low estimated K; no odor Location Details of the coarse sand; 10% clay; very low estimated K; no odor End of Boring at 28.0'	Static Depth of Water in Well: NA		Well Screen Slot Size: NA			
BORING DETAIL Second Part Part	المستحد					
SERING DETAIL Section	<u> </u>	T	DESCRIPTION OF LITHOLOGY			
Sandy SiLT (ML); dark brown; damp; very stiff; 60% silt; 30% fine to coarse sand; 10% clay; very low plasticity; very low estimated K; no odor Silty CLAY (CL); light brown; damp; very stiff; 60% clay; 30% silt; 10% fine to coarse sand; very low plasticity; very low estimated K; no odor wet af 12.5' End of Boring at 28.0'	Depth in Boulage Description Interval Blow County OVM (ppm)	Water Leve Graphic Log	standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation.			
aqua science engineers, inc.	Portland Cement Portland Cement	▼];	Sandy SiLT (ML); dark brown; damp; very stiff; 60% silt; 30% fine to coarse sand; 10% clay; very low plasticity; very low estimated K; no odor Silty CLAY (CL); light brown; damp; very stiff; 60% clay; 30% silt; 10% fine to coarse sand; very low plasticity; very low estimated K; no odor wet af 12.5' End of Boring at 28.0' End of Boring at 28.0'			

Driller: Vironex Type of Rig: Geoprobe Size of Drill: 2.0" Diameter Logged By: Ian T. Reed Date Drilled: August 17, 2000 Checked By: Robert E. Kitay, R.G. WATER AND WELL DATA Depth of Water First Encountered: 12.0' Well Screen Type and Diameter: NA Static Depth of Water in Well: NA Well Screen Slot Size: NA Total Depth of Boring: 16.0' Type and Size of Soil Sampler: 2.0" I.D. Macro Sampler SOIL/ROCK SAMPLE DATA BORING BORING Type and Classification, texture, relative moisture	SOIL BORING LOG AND MONITORING WELL COMPLETION DETAILS Boring: BH-F					
Logged By: lan T. Reed Date Drilled: August 17, 2000 Checked By: Robert E. Kitay, R.G. WATER AND WELL DATA Depth of Water First Encountered: 12.0' Static Depth of Water in Well: NA Total Depth of Boring: 16.0' BORING DETAIL BORING DETAIL Depth of Boring: 16.0' Concrete Concrete Sity CLAY (CL); light brown; damp; very sliff; 60% of plasticity; very low estimated K; no odor Concrete Sity Concrete Sity CLAY (CL); light brown; damp; very sliff; 60% of plasticity; very low estimated K; no odor End of Boring at 16.0' End of Boring at 16.0' End of Boring at 16.0'	Project Name: Romak Iron Works	Project Location	on: 3250 Hollis St., Oakland, CA Page 1 of 1			
WATER AND WELL DATA Depth of Water First Encountered: 12.0° Static Depth of Water in Well: NA Total Depth of Boring: 16.0° Type and Size of Soil Sampler: 2.0° I.D. Macro Sampler DESCRIPTION OF LITHOLOGY standard classification, texture, relative moisture density, stiffness, odor-staining, USCS designation Concrete Silty CLAY (CL); light brown; damp; very stiff; 60% clay; 30% silt; 10% fine to coarse sand; very low plasticity; very low estimated K; no odor End of Boring at 16.0° End of Boring at 16.0° End of Boring at 16.0°	Driller: Vironex	Type of Rig: G	eoprobe Size of Drill: 2.0" Diameter			
Depth of Water First Encountered: 12.0' Static Depth of Water in Well: NA Total Depth of Boring: 16.0' SOILROCK SAMPLE DATA Type and Size of Soil Sampler: 2.0" I.D. Macro Sampler DESCRIPTION OF LITHOLOGY standard classification, texture, relative moisture density, stiffness, odor-staining, USCS designation O Concrete Sity CLAY (CL): light brown; damp: very stiff; 60% clay; 30% silt; 10% fine to coarse sand; very low plasticity; very low estimated K; no odor End of Boring at 16.0' End of Boring at 16.0' End of Boring at 16.0'	Logged By: Ian T. Reed	Date Drilled:	August 17, 2000 Checked By: Robert E. Kitay, R.G.			
Static Depth of Water in Well: NA Total Depth of Boring: 16.0' Type and Size of Soil Sampler: 2.0' I.D. Macro Sampler Type and Size of Soil Sampler: 2.0' I.D. Macro Sampler DESCRIPTION OF LITHOLOGY standard classification, texture, relative moisture density, stiffness, odor-staining, USCS designation O Concrete Silty CLJ: light brown; damp; very stiff; 60% clay; 30% silt; 10% fine to coarse sand; very low plasticity; very low estimated K; no odor Total Depth of Boring at 16.0' DESCRIPTION OF LITHOLOGY standard classification, texture, relative moisture density, stiffness, odor-staining, USCS designation O Concrete Silty CLJ: light brown; damp; very stiff; 60% clay; 30% silt; 10% fine to coarse sand; very low plasticity; very low estimated K; no odor End of Boring at 16.0'	WATER AND WELL DATA		Total Depth of Well Completed: NA			
Total Depth of Boring: 16.0' Type and Size of Soil Sampler: 2.0" I.D. Macro Sampler DESCRIPTION OF LITHOLOGY standard classification, texture, relative moisture density, stiffness, odor-staining, USCS designation Concrete Silty CLAY (CL); light brown; damp; very stiff; 60% clay; 30% silt; 10% fine to coarse sand; very low plasticity; very low estimated K; no odor End of Boring at 16.0' End of Boring at 16.0'	Depth of Water First Encountered: 12.	.0'	Well Screen Type and Diameter: NA			
SOIL/ROCK SAMPLE DATA The properties of the pro	Static Depth of Water in Well: NA		Well Screen Slot Size: NA			
BORING DETAIL Superproduction of the production						
The purple of the property of			DESCRIPTION OF LITHOLOGY			
Concrete Sithy CLAY (CL); light brown; damp; very stiff; 60% clay; 30% silt; 10% fine to coarse sand; very low plasticity; very low estimated K; no odor wet at 12' End of Boring at 16.0'	Description Descri	Water Leve Graphic Log	standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation.			
	- 1 0	▼ :	Silty CLAY (CL); light brown; damp; very stiff; 60% clay; 30% silt; 10% fine to coarse sand; very low plasticity; very low estimated K; no odor wet at 12' End of Boring at 16.0' End of Boring at 16.0'			

APPENDIX C

Certified Analytical Report and Chain of Custody Documentation Soil Samples Environmental Services (SDB)

Submission #: 2000-08-0399

Date: August 25, 2000

Aqua Science Engineers, Inc. 208 West El Pintado Road Danville, CA 94526

Attn.: Mr. Ian T. Reed

Project: Romak Iron Works

Dear Mr. Reed,

Attached is our report for your samples received on Friday August 18, 2000 This report has been reviewed and approved for release. Reproduction of this report is permitted only in its entirety.

Please note that any unused portion of the samples will be discarded after October 2, 2000 unless you have requested otherwise. We appreciate the opportunity to be of service to you. If you have any questions, please call me at (925) 484-1919. You can also contact me via email. My email address is: vvancil@chromalab.com

Sincerely,

Vincent Vancil

Environmental Services (SDB)

Gas/BTEX and MTBE

Aqua Science Engineers, Inc.

⊠ 208 West El Pintado Road

Danville, CA 94526

Attn: Ian T. Reed

Phone: (925) 820-9391 Fax: (925) 837-4853

Project #: Project: Romak Iron Works

Samples Reported

Sample ID	Matrix	Date Sampled	Lab#
BH-A-15.5`	Soil	08/17/2000 08:45	1
BH-B-7.5°	Soil	08/17/2000 09:40	2
BH-C-18'	Soil	08/17/2000 11:45	3
BH-D-18`	Soil	08/17/2000 15:30	4
BH-E-19`	Soil	08/17/2000 15:00	5
BH-F-11.5`	Soil	08/17/2000 16:00	6

Submission #: 2000-08-0399

Environmental Services (SDB)

To: Aqua Science Engineers, Inc.

8020 Test Method:

8015M

Attn.: Ian T. Reed

Prep Method:

5030

Gas/BTEX and MTBE

Sample ID:

BH-A-15.5°

Lab Sample ID: 2000-08-0399-001

Project:

Received:

08/18/2000 15:25

Romak Iron Works

Extracted:

08/24/2000 17:33

Sampled:

08/17/2000 08:45

QC-Batch:

2000/08/24-01.01

Matrix:

Soil

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Gasoline	ND	1.0	mg/Kg	1.00	08/24/2000 17:33	
Benzene	ND	0.0050	mg/Kg	1.00	08/24/2000 17:33	
Toluene	ND	0.0050	mg/Kg	1.00	08/24/2000 17:33	
Ethyl benzene	ND	0.0050	mg/Kg	1.00	08/24/2000 17:33	
Xylene(s)	ND	0.0050	mg/Kg	1.00	08/24/2000 17:33	
мтве	ND	0.0050	mg/Kg	1.00	08/24/2000 17:33	
Surrogate(s)						
Trifluorotoluene	73.5	53-125	%	1.00	08/24/2000 17:33	
4-Bromofluorobenzene-FID	64.9	58-124	%	1.00	08/24/2000 17:33	

Aqua Science Engineers, Inc.

Environmental Services (SDB)

Test Method:

8020 ,8015M

Submission #: 2000-08-0399

Attn.: Ian T. Reed

To:

Prep Method:

5030

Gas/BTEX and MTBE

Sample ID:

BH-B-7.5

Lab Sample ID: 2000-08-0399-002

Project:

Received:

08/18/2000 15:25

Romak Iron Works

Extracted:

08/24/2000 18:09

Sampled:

08/17/2000 09:40

QC-Batch:

2000/08/24-01.01

Matrix:

Soil

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Gasoline	ND	1.0	mg/Kg	1.00	08/24/2000 18:09	•
Benzene	ND	0.0050	mg/Kg	1.00	08/24/2000 18:09	
Toluene	ND	0.0050	mg/Kg	1.00	08/24/2000 18:09	
Ethyl benzene	ND	0.0050	mg/Kg	1.00	08/24/2000 18:09	
Xylene(s)	ND	0.0050	mg/Kg	1.00	08/24/2000 18:09	
MTBE	ND	0.0050	mg/Kg	1.00	08/24/2000 18:09	
Surrogate(s)			,			
Trifluorotoluene	76.6	53-125	%	1.00	08/24/2000 18:09	
Trifluorotoluene-FID	72.9	53-125	%	1.00	08/24/2000 18:09	

Printed on: 08/25/2000 17:43

Submission #: 2000-08-0399

CHROMALAB, INC.

Environmental Services (SDB)

To: Aqua Science Engineers, Inc. Test Method:

8020 8015M

Attn.: Ian T. Reed

Prep Method:

5030

Gas/BTEX and MTBE 1

Sample ID:

BH-C-18'

Lab Sample ID: 2000-08-0399-003

Project:

Received:

08/18/2000 15:25

Romak Iron Works

Extracted:

08/24/2000 18:44

Sampled:

08/17/2000 11:45

QC-Batch:

2000/08/24-01.01

Matrix:

Soil

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Gasoline	ND	1.0	mg/Kg	1.00	08/24/2000 18:44	
Benzene	ND	0.0050	mg/Kg	1.00	08/24/2000 18:44	
Toluene	ND	0.0050	mg/Kg	1.00	08/24/2000 18:44	
Ethyl benzene	ND	0.0050	mg/Kg	1.00	08/24/2000 18:44	
Xylene(s)	ND	0.0050	mg/Kg	1.00	08/24/2000 18:44	
MTBE	ND	0.0050	mg/Kg	1.00	08/24/2000 18:44	
Surrogate(s)		1				
Trifluorotoluene	80.8	53-125	%	1.00	08/24/2000 18:44	
4-Bromofluorobenzene-FID	66.7	58-124	%	1.00	08/24/2000 18:44	

Submission #: 2000-08-0399

Environmental Services (SDB)

Aqua Science Engineers, Inc. To:

Test Method:

8020 8015M

Prep Method:

5030

Gas/BTEX and MTBE

Sample ID:

Attn.: Ian T. Reed

BH-D-18'

Lab Sample ID: 2000-08-0399-004

Project:

Received:

08/18/2000 15:25

Romak Iron Works

Extracted:

08/24/2000 19:19

Sampled:

08/17/2000 15:30

QC-Batch:

2000/08/24-01.01

Matrix:

Soil

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Gasoline	ND	1.0	mg/Kg	1.00	08/24/2000 19:19	
Benzene	ND	0.0050	mg/Kg	1.00	08/24/2000 19:19	
Toluene	ND	0.0050	mg/Kg	1.00	08/24/2000 19:19	
Ethyl benzene	ND	0.0050	mg/Kg	1.00	08/24/2000 19:19	
Xylene(s)	ND	0.0050	mg/Kg	1.00	08/24/2000 19:19	
MTBE	ND	0.0050	mg/Kg	1.00	08/24/2000 19:19	
Surrogate(s)						
Trifluorotoluene	80.8	53-125	%	1.00	08/24/2000 19:19	
4-Bromofluorobenzene-FID	64.9	58-124	%	1.00	08/24/2000 19:19	

Submission #: 2000-08-0399

Environmental Services (SDB)

Aqua Science Engineers, Inc. To:

8020 Test Method:

8015M

Attn.: Ian T. Reed

Prep Method:

5030

Gas/BTEX and MTBE

Sample ID:

BH-E-19"

Lab Sample ID: 2000-08-0399-005

Project:

08/18/2000 15:25

Romak Iron Works

Extracted:

Received:

08/24/2000 19:54

Sampled:

08/17/2000 15:00

QC-Batch:

2000/08/24-01.01

Matrix:

Soil

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Gasoline	ND	1.0	mg/Kg	1.00	08/24/2000 19:54	
Benzene	ND	0.0050	mg/Kg	1.00	08/24/2000 19:54	
Toluene	ND	0.0050	mg/Kg	1.00	08/24/2000 19:54	
Ethyl benzene	ND	0.0050	mg/Kg	1.00	08/24/2000 19:54	
Xylene(s)	ND	0.0050	mg/Kg	1.00	08/24/2000 19:54	
MTBE	ND	0.0050	mg/Kg	1.00	08/24/2000 19:54	
Surrogate(s)						
Trifluorotoluene	79.6	53-125	%	1.00	08/24/2000 19:54	
4-Bromofluorobenzene-FID	68.0	58-124	%	1.00	08/24/2000 19:54	

Page 6 of 11 Printed on: 08/25/2000 17:43

Submission #: 2000-08-0399

Environmental Services (SDB)

To: Aqua Science Engineers, Inc. Test Method:

8020 8015M

Attn.: Ian T. Reed

Prep Method:

5030

Gas/BTEX and MTBE

Sample ID:

BH-F-11.5

Lab Sample ID: 2000-08-0399-006

Project:

Received:

08/18/2000 15:25

Romak Iron Works

Extracted:

08/25/2000 16:41

Sampled:

08/17/2000 16:00

QC-Batch:

2000/08/25-01.01

Matrix:

Soil

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Gasoline	ND	1.0	mg/Kg	1.00	08/25/2000 16:41	
Benzene	ND	0.0050	mg/Kg	1.00	08/25/2000 16:41	
Toluene	ND	0.0050	mg/Kg	1.00	08/25/2000 16:41	
Ethyl benzene	ND	0.0050	mg/Kg	1.00	08/25/2000 16:41	
Xylene(s)	ND	0.0050	mg/Kg	1.00	08/25/2000 16:41	
MTBE	ND	0.0050	mg/Kg	1.00	08/25/2000 16:41	
Surrogate(s)			1			
Trifluorotoluene	67.7	53-125	%	1.00	08/25/2000 16:41	
Trifluorotoluene-FID	65.6	53-125	%	1.00	08/25/2000 16:41	

Submission #: 2000-08-0399

Environmental Services (SDB)

To: Aqua Science Engineers, Inc.

Test Method:

8015M

Prep Method:

8020 5030

Batch QC Report
Gas/BTEX and MTBE

Method Blank

Attn.: Jan T. Reed

Soil

QC Batch # 2000/08/24-01.01

MB:

2000/08/24-01.01-001

Date Extracted: 08/24/2000 07:32

Compound	Result	Rep.Limit	Units	Analyzed	Flag
Gasoline	ND	1.0	mg/Kg	08/24/2000 07:32	
Benzene	ND	0.0050	mg/Kg	08/24/2000 07:32	
Toluene	ND	0.0050	mg/Kg	08/24/2000 07:32	
Ethyl benzene	ND	0.0050	mg/Kg	08/24/2000 07:32	
Xylene(s)	ND	0.0050	mg/Kg	08/24/2000 07:32	
MTBE	ND	0.0050	mg/Kg	08/24/2000 07:32	
Surrogate(s)					
Trifluorotoluene	92.8	53-125	%	08/24/2000 07:32	
4-Bromofluorobenzene-FID	80.8	58-124	%	08/24/2000 07:32	

Submission #: 2000-08-0399

Environmental Services (SDB)

To: Aqua Science Engineers, Inc.

Test Method: 80

8015M 8020

Attn.: Ian T. Reed

Prep Method:

5030

Batch QC Report Gas/BTEX and MTBE

Method Blank Soil QC Batch # 2000/08/25-01.01

MB: 2000/08/25-01.01-001 Date Extracted: 08/25/2000 06:21

Compound	Result	Rep.Limit	Units	Analyzed	Flag
Gasoline	ND	1.0	mg/Kg	08/25/2000 06:21	
Benzene	ND	0.0050	mg/Kg	08/25/2000 06:21	
Toluene	ND	0.0050	mg/Kg	08/25/2000 06:21	
Ethyl benzene	ND	0.0050	mg/Kg	. 08/25/2000 06:21	
Xylene(s)	ND	0.0050	mg/Kg	08/25/2000 06:21	
MTBE	ND	0.0050	mg/Kg	08/25/2000 06:21	
Surrogate(s)			, †		
Trifluorotoluene	96.4	53-125	%	08/25/2000 06:21	
4-Bromofluorobenzene-FID	85.6	58-124	%	, 08/25/2000 06:21	

Submission #: 2000-08-0399

CHROMALAB, INC.

Environmental Services (SDB)

To: Aqua Science Engineers, Inc.

Test Method: 8020

8015M

Attn: Ian T. Reed

Prep Method:

5030

Batch QC Report

Gas/BTEX and MTBE

Laboratory Control Spike (LCS/LCSD)

Soil

QC Batch # 2000/08/24-01.01

LCS:

2000/08/24-01.01-002

Extracted: 08/24/2000 08:06

Analyzed

08/24/2000 08:06

LCSD:

2000/08/24-01.01-003

Extracted: 08/24/2000 08:41

Analyzed 08/

08/24/2000 08:41

Compound	Conc.	[mg/Kg]	Exp.Conc.	[mg/Kg]	Recov	ery [%]	RPD	Ctrl. Limi	ts [%]	Flag	gs
-	LCS	LCSD	LCS	LCSD	LCS	LCSD	[%]	Recovery	RPD	LCS	LCSD
Gasoline	0 544	0.536	0.500	0.500	108.8	107.2	1.5	75-125	35		
Benzene	0.0969	0.0922	0.1000	0.1000	96.9	92.2	5.0	77-123	35	!	
Toluene	0.0941	0.0896	0.1000	0.1000	94.1	89.6	4.9	78-122	35		}
Ethyl benzene	0.0944	0.0908	0.1000	0.1000	94.4	90.8	3.9	70-130	35	!]	
Xylene(s)	0.277	0.267	0.300	0.300	92.3	69.0	3,6	75-125	35		1
Surrogate(s)	ļ		i					}			
Trifluorotoluene	477	460	500	500	95.4	92.0		53-125		! ;	į I
4-Bromofluorobenzene-Fl	423	405	500	500	84.6	81.0		58-124		1 	j

Submission #: 2000-08-0399

CHROMALAB, INC.

Environmental Services (SDB)

To: Aqua Science Engineers, Inc.

Test Method: 8020

8015M

Attn: Ian T. Reed

Prep Method:

5030

Batch QC Report

Gas/BTEX and MTBE

Laboratory Control Spike (LCS/LCSD)

Soil

QC Batch # 2000/08/25-01.01

LCS:

2000/08/25-01.01-002

Extracted: 08/25/2000 07:45

Analyzed

08/25/2000 07:45

LCSD: 2000/08/25-01.01-003

Extracted: 08/25/2000 08:20

Analyzed 0

08/25/2000 08:20

Compound	Conc.	[mg/Kg]	Exp.Conc.	[mg/Kg]	Recov	ery [%]	RPD	Ctrl. Lim	its [%]	Flag	js
	LCS	LCSD	LCS	LCSD	LCS	LCSD	[%]	Recovery	RPD	LCS	LCSD
Gasoline	0.523	0.501	0.500	0.500	104.6	100.2	4.3	75-125	35		
Benzene	0.0936	0.0939	0.1000	0.1000	93.6	93.9	0.3	77-123	35		
Toluene	0.0908	0.0920	0.1000	0.1000	90.8	92,0	1.3	78-122	35		
Elhyl benzene	0.0911	0.0925	0.1000	0.1000	91.1	92.5	1.5	70-130	35		
Xylene(s)	0.269	0.273	0.300	0.300	89.7	91.0	1.4	75-125	35		
Surrogate(s)	ļ	1					i				
Trifluorotoluene	462	473	500	500	92.4	94.6		53-125			
4-Bromofluorobenzene-FI	398	380	500	500	79.6	76.0		58-124]		

Environmental Services (SDB)

Total Extractable Petroleum Hydrocarbons (TEPH)

Aqua Science Engineers, Inc.

208 West El Pintado Road

Danville, CA 94526

Attn: lan T. Reed

Phone: (925) 820-9391 Fax: (925) 837-4853

Submission #: 2000-08-0399

Project #:

Project: Romak Iron Works

Samples Reported

Sample ID	Matrix	Date Sampled	Lab#
BH-A-15.5`	Şoil	08/17/2000 08:45	1
BH-B-7.5`	Soil	08/17/2000 09:40	2
BH-C-18'	Soil	08/17/2000 11:45	3
BH-D-18'	Soil	08/17/2000 15:30	4
BH-F-19	Soil	08/17/2000 15:00	5
BH-F-11.5`	Soil	08/17/2000 16:00	6

Submission #: 2000-08-0399

Environmental Services (SDB)

Aqua Science Engineers, Inc. To:

Test Method:

8015M

Attn.: Ian T. Reed

Prep Method:

3550/8015M

Total Extractable Petroleum Hydrocarbons (TEPH)

Sample ID:

BH-A-15.5

Lab Sample ID: 2000-08-0399-001

Project:

Received:

08/18/2000 15:25

Romak Iron Works

Extracted:

08/21/2000 10:00

Sampled:

08/17/2000 08:45

QC-Batch:

2000/08/21-01.10

Matrix:

Soil

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Diesel Motor Oil	ND ND	1.0 50	mg/Kg mg/Kg	1.00 1.00	08/21/2000 21:14 08/21/2000 21:14	· · · · · · · · · · ·
Surrogate(s) o-Terphenyl	72.4	60-130	%	1.00	08/21/2000 21:14	

1220 Quarry Lane * Pleasanton, CA 94566-4756 Telephone: (925) 484-1919 * Facsimile: (925) 484-1096

Aqua Science Engineers, Inc.

Environmental Services (SDB)

Test Method:

8015M

Submission #: 2000-08-0399

Attn.: Ian T. Reed

To:

Prep Method:

3550/8015M

Total Extractable Petroleum Hydrocarbons (TEPH)

Sample ID:

BH-B-7.5

Lab Sample ID: 2000-08-0399-002

Project:

Romak Iron Works

Received:

08/18/2000 15:25

Extracted:

08/21/2000 10:00

Sampled:

08/17/2000 09:40

QC-Batch:

2000/08/21-01.10

Matrix:

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Diesel Motor Oil	ND ND	1.0 50	mg/Kg mg/Kg	1.00 1.00	08/21/2000 21:52 08/21/2000 21:52	
Surrogate(s) o-Terphenyl	71.6	60-130	%	1.00	08/21/2000 21:52	

Submission #: 2000-08-0399

CHROMALAB, INC.

Environmental Services (SDB)

To: Aqua Science Engineers, Inc. Test Method:

8015M

Attn.: Ian T. Reed

Prep Method:

3550/8015M

Total Extractable Petroleum Hydrocarbons (TEPH)

Sample ID:

BH-C-18'

Lab Sample ID: 2000-08-0399-003

Project:

Received:

08/18/2000 15:25

Romak Iron Works

Extracted:

08/21/2000 10:00

Sampled:

08/17/2000 11:45

QC-Batch:

2000/08/21-01.10

Matrix:

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Diesel Motor Oil	ND ND	1.0 50	mg/Kg mg/Kg	1.00 1.00	08/21/2000 22:31 08/21/2000 22:31	
Surrogate(s) o-Terphenyl	72.7	60-130	%	1.00	08/21/2000 22:31	

Submission #: 2000-08-0399

Environmental Services (SDB)

Aqua Science Engineers, Inc.

Test Method:

8015M

Attn.: Ian T. Reed

To:

Prep Method:

3550/8015M

Total Extractable Petroleum Hydrocarbons (TEPH)

Sample ID: BH-D-18'

Lab Sample ID: 2000-08-0399-004

Project:

Received:

08/18/2000 15:25

Romak Iron Works

Extracted:

08/21/2000 10:00

Sampled:

08/17/2000 15:30

QC-Batch:

2000/08/21-01.10

Matrix:

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Diesel Motor Oil	ND ND	1.0 50	mg/Kg mg/Kg	1.00 1.00	08/21/2000 23:10 08/21/2000 23:10	
Surrogate(s) o-Terphenyl	72.8	60-130	%	1.00	08/21/2000 23:10	· <u>·</u> ····-

Submission #: 2000-08-0399

CHROMALAB, INC.

Environmental Services (SDB)

To: Aqua Science Engineers, Inc. Test Method:

8015M

Attn.: Ian T. Reed

Prep Method:

3550/8015M

Total Extractable Petroleum Hydrocarbons (TEPH)

Sample ID:

BH-E-19'

Lab Sample ID: 2000-08-0399-005

Project:

Received:

08/18/2000 15:25

Romak Iron Works

Extracted:

08/21/2000 10:00

Sampled:

08/17/2000 15:00

QC-Batch:

2000/08/21-01.10

Matrix:

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Diesel Motor Oil	ND ND	1.0 50	mg/Kg mg/Kg	1.00 1.00	08/21/2000 23:48 08/21/2000 23:48	
Surrogate(s) o-Terphenyl	70.2	60-130	%	1.00	08/21/2000 23:48	

Submission #: 2000-08-0399

Environmental Services (SDB)

To: Aqua Science Engineers, Inc. Test Method:

8015M

Attn.: Ian T. Reed

Prep Method:

3550/8015M

Total Extractable Petroleum Hydrocarbons (TEPH)

Sample ID:

BH-F-11.5

Lab Sample ID: 2000-08-0399-006

Project:

Received:

08/18/2000 15:25

Romak Iron Works

Extracted:

08/21/2000 10:00

Sampled:

08/17/2000 16:00

QC-Batch:

2000/08/21-01.10

Matrix:

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Diesel Motor Oil	ND ND	1.0 50	mg/Kg mg/Kg	1.00 1.00	08/22/2000 00:27 08/22/2000 00:27	
Surrogate(s) o-Terphenyl	72.0	60-130	%	1.00	08/22/2000 00:27	

Submission #: 2000-08-0399

Environmental Services (SDB)

To: Aqua Science Engineers, Inc.

Test Method:

8015M

Attn.: Ian T. Reed

Prep Method: 35

3550/8015M

Batch QC Report

Total Extractable Petroleum Hydrocarbons (TEPH)

Method Blank Soil

QC Batch # 2000/08/21-01.10

MB: 2000/08/21-01.10-001

Date Extracted: 08/21/2000 10:00

Compound	Result	Rep.Limit	Units	Analyzed	Flag
Diesel Motor Oil	ND ND	1 50	mg/Kg mg/Kg	08/22/2000 01:44 08/22/2000 01:44	
Surrogate(s) o-Terphenyl	79.5	60-130	%	08/22/2000 01:44	

1220 Quarry Lane * Pleasanton, CA 94566-4756 Telephone: (925) 484-1919 * Facsimile: (925) 484-1096

Submission #: 2000-08-0399

Environmental Services (SDB)

To: Aqua Science Engineers, Inc.

Test Method:

8015M

Attn: Ian T. Reed

Prep Method:

3550/8015M

Batch QC Report

Total Extractable Petroleum Hydrocarbons (TEPH)

Laboratory Control Spike (LCS/LCSD)

Soil

QC Batch # 2000/08/21-01.10

LCS: LCSD: 2000/08/21-01.10-002 2000/08/21-01.10-003 Extracted: 08/21/2000 10:00 Extracted: 08/21/2000 10:00

Analyzed Analyzed 08/22/2000 02:23 08/22/2000 03:01

Compound	Conc.	[mg/Kg]	Exp.Conc.	[mg/Kg]	Recov	ery [%]	RPD	Ctrl. Lim	ts [%]	Flag	ıs
	LCS	LCSD	LCS	LCSD	LCS	LCSD	[%]	Recovery	RPD	LCS	LCSD
Diesel	30 3	30.0	41.7	41.7	72.7	71.9	1.1	60-130	25		i !
Surrogate(s)	23.1	23.2	20.0	20.0	115.5	116.0		60-130			

2000-08-0399

54025

Aqua Science Engineers, Inc. 208 W. El Pintado Road Danville, CA 94526 (925) 820-9391 EAX (925) 837-4853

Chain of Custody

1711(020)00					_													PAC	3E	1	OF	}
SAMPLER (SIGN	ATURE)	}		(Pt	IONE NO.)	PRO.	JECT N	AME	R	amak	Iron	0 1 30	oc Ks					NO.			
lat	D ~	ſ	t o	~ 10==	Ctc.	[ADDI					s st.			CA			- 500	,,,,,			
ANIAI	Y G 16	PE	QUES	25)820- T	1341			T T		T		, 	, <u> </u>	1	T							
SPECIAL INSTRU			XULU	· · · · · · · · · · · · · · · · · · ·	ا _{×6}			SNS		ις.					00		ED)		-			
or Lorne mothe	CHONS	•			BTE 502(OR O	ARB(2860) XX				8	SKU 814	S	SOLV	ر. ۲.5	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\			}
					BE &	15,	MOT(20)	ANIC:	0 KC		600	000	200	2 Z Z S	ATE	933	200	70)	-	1	
	5-	day	TAT	_	TPH-GAS / MTBE & BTEX (EPA 5030/8015-8020)	TPH-DIESE. (EPA 3510, 6015)	TPH-DIESEL & MOTOR OIL (EPA 3510,:3015)	PURGEABLE HALOCARBONS (EPA 601/8010)	VOLATILE ORGANICS (EPA 624/8240/8260)	SEMI-VOLATILE ORGANICS (EPA 625/8270)	OIL & GREASE (EPA 5520) —	LUFT METALS (5) (EPA 6010+7000)	CAM 17 METALS (EPA 6010+7000)	PCBs & PESTICIDES (EPA 608/8080)	ORGANOPHOSPHORUS PESTICIDES (EPA 8140 EPA 608/8080)	FUEL OXYGENATES (EPA 8260)	Pb (TOTAL or DISSOLVED) (EPA 6010)	TPH-G/BTEX/5 0XY'S (EPA 8260)	TPH-G/BTEX/70XY'S HVOCS (EPA 8260)			SIE E
SAMPLE ID.	D			NO. OF	GAS 503	DIES 1351	DIES 356	EAB 601	TILE 624	-VOL 625	GRE 552	MET. 601	17 MI 601	\$ P P	NA PS PS PS PS PS PS PS PS PS PS PS PS PS	0X)	0.0 V 100	G/B 826	9/B	1		COMPOSITE
SAMPLE ID.	DATE	TIME	MATRIX	SAMPLES	1PH- (EPA	TPH (EPA	TPH- (EPA	PURC (EPA	VOLA (EPA	SEMI (EPA	OR & (EPA	LUFT (EPA	CAM (EPA	PCB _E	PES:	EPA FPA	2b (1 EPA	FPH	FH- ₹00			000
BH-A -15.5'	8/17	0845	Soil	ŧ	X		X							<u> </u>					-	 	 	
BHB-7.6'	8/17	0940	1		X		X									L				 	 	
BH-C-18'	8/17	1145			X		\searrow												-		 	
GH-D -18'	8/17	७५७			X																 	
BH-E - 191	8/17	1500		1-1	X			•											 		 '	-
BH-F-11.5'		1600	4-		X		\bigcirc			,										<u> </u>	 	
- 011		,,,,,	VV																		 	
			 	 																		
			<u> </u>	 						·												 -
<u> </u>																						
SEL BLOUBOURD BY	· · · · · · · · · · · · · · · · · · ·				<u> </u>							7					1601	MENTS				
RELINQUISHED B	1:		KECEIV	EDBY.	7/-	re til	RELIN	IQUISHE	DBY:			KECE	₩ED BY	JABO	RATOR	(:	CON	AMENTS	<i>ɔ</i> :			
(signature) led	(tim	ie <u>)</u>	(signat	ur <i>e</i>)((time)/	031	(signa	iture)		(time)	15/5	Keigha	US E	me	(Char)	152	\$					
1. ~ D	 		R	Horr	7/1~				Mo				ر و الا د	5	11	1	7					
lon T. Reed (printed name)	(da	te)		d name)		2/18/	1				<u> 8) ji ja</u>	Incint.	t (S)	Kou	(date)	ક્ષીક્ષી	90	TUI	RN ARC	T DNUC	IME	
Company-			Compar			1. 40	Comp		<u>, </u>	(da be)	<u> </u>	1		<i>)</i>	(date)	<u> </u>	SI/	ANDARI) 24!	Hr 4.	9Hr 7	2Hr
ASI	=			^/	11			Z,	//		/	Compa			{ _	6	OTH	IER:				
	 -		<i>حول</i>	uma	4		14	0	valu				RVO	ma	<u>. La</u>							

APPENDIX D

Certified Analytical Report and Chain of Custody Documentation Groundwater Samples

Submission #: 2000-08-0402

Date: August 25, 2000

Aqua Science Engineers, Inc. 208 West El Pintado Road Danville, CA 94526

Attn.: Mr. Ian T. Reed

Project: Romak Iron Works

Dear Mr. Reed,

Attached is our report for your samples received on Friday August 18, 2000 This report has been reviewed and approved for release. Reproduction of this report is permitted only in its entirety.

Please note that any unused portion of the samples will be discarded after October 2, 2000 unless you have requested otherwise. We appreciate the opportunity to be of service to you. If you have any questions, please call me at (925) 484-1919. You can also contact me via email. My email address is: vvancil@chromalab.com

Sincerely,

Vincent Vancil

CHROMALAB, INC. Environmental Services (SDB)

Gas/BTEX and MTBE

Aqua Science Engineers, Inc.

208 West El Pintado Road

Danville, CA 94526

Attn: Ian T. Reed

Phone: (925) 820-9391 Fax: (925) 837-4853

Project #:

Project: Romak Iron Works

Samples Reported

Sample ID	Matrix	Date Sampled	Lab#
BH-A	Water	08/17/2000 11:00	1
BH-B	Water	08/17/2000 10:20	2
BH-C	Water	08/17/2000 12:00	3
BH-D	Water	08/17/2000 14:15	4
BH-E	Water	08/17/2000 15:20	5
BH-F	Water	08/17/2000 16:15	6
MW-1	Water	08/17/2000 15:00	7

Submission #: 2000-08-0402

CHROMALAB, INC.

Environmental Services (SDB)

Aqua Science Engineers, Inc. To:

Test Method:

8020

8015M

Attn.: Ian T. Reed

Prep Method:

5030

Gas/BTEX and MTBE

Sample ID:

BH-A

Lab Sample ID: 2000-08-0402-001

Project:

Received:

08/18/2000 15:25

Romak Iron Works

Extracted:

08/24/2000 18:22

Sampled:

08/17/2000 11:00

QC-Batch:

2000/08/24-01.02

Matrix:

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Gasoline	ND	50	ug/L	1.00	08/24/2000 18:22	
Benzene	ND	0.50	ug/L	1.00	08/24/2000 18:22	
Toluene	ND	0.50	ug/L	1.00	08/24/2000 18:22	
Ethyl benzene	ND	0.50	ug/L	1.00	08/24/2000 18:22	
Xylene(s)	ND	0.50	ug/L	1.00	08/24/2000 18:22	
MTBE	ND	5.0	ug/L	1.00	08/24/2000 18:22	
Surrogate(s)		1			1	
Trifluorotoluene	88.3	58-124	: %	1.00	08/24/2000 18:22	
4-Bromofluorobenzene-FID	88.3	50-150	%	1.00	08/24/2000 18:22	

Submission #: 2000-08-0402

CHROMALAB, INC.

Environmental Services (SDB)

Aqua Science Engineers, Inc. To:

Test Method:

8020 8015M

Prep Method:

5030

Gas/BTEX and MTBE

Sample ID:

Attn.: Ian T. Reed

BH-B

Lab Sample ID: 2000-08-0402-002

Project:

Received:

08/18/2000 15:25

Romak Iron Works

Extracted:

08/24/2000 18:53

Sampled:

08/17/2000 10:20

QC-Batch:

2000/08/24-01.02

Matrix:

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Gasoline	ND	50	ug/L	1.00	08/24/2000 18:53	
Benzene	ND	0.50	ug/L	1.00	08/24/2000 18:53	
Toluene	ND	0.50	ug/L	1.00	08/24/2000 18:53	
Ethyl benzene	ND	0.50	ug/L	1.00	08/24/2000 18:53	
Xylene(s)	ND	0.50	ug/L	1.00	08/24/2000 18:53	
MTBE	ND	5.0	ug/L	1.00	08/24/2000 18:53	
Surrogate(s)		50.404	0/	1.00	08/24/2000 18:53	
Trifluorotoluene	94.0	58-124	%	}	08/24/2000 18:53	
4-Bromofluorobenzene-FID	88.2	50-150	%	1.00	08/24/2000 18:53	

Submission #: 2000-08-0402

Environmental Services (SDB)

To: Aqua Science Engineers, Inc.

Test Method:

8020 8015M

Attn.: lan T. Reed

Prep Method:

5030

Gas/BTEX and MTBE

Sample ID:

вн-с

Lab Sample ID: 2000-08-0402-003

Project:

Received:

08/18/2000 15:25

Romak Iron Works

Extracted:

08/24/2000 19:25

Sampled:

08/17/2000 12:00

QC-Batch:

2000/08/24-01.02

Matrix:

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Gasoline	ND	50	ug/L	1.00	08/24/2000 19:25	
Benzene	ND	0.50	ug/L	1.00	08/24/2000 19:25	
Toluene	ND	0.50	ug/L	1.00	08/24/2000 19:25	
Ethyl benzene	ND	0.50	ug/L	1.00	08/24/2000 19:25	
Xylene(s)	0.80	0.50	ug/L	1.00	08/24/2000 19:25	
MTBE	ND	5.0	ug/L	1.00	08/24/2000 19:25	
Surrogate(s)			1			
Trifluorotoluene	98.3	58-124	%	1.00	08/24/2000 19:25	
4-Bromofluorobenzene-FID	89.1	50-150	%	1.00	08/24/2000 19:25	

Environmental Services (SDB)

Aqua Science Engineers, Inc.

Test Method:

8020

8015M

Submission #: 2000-08-0402

Attn.: Ian T. Reed

To:

Prep Method:

5030

Gas/BTEX and MTBE

Sample ID:

BH-D

Lab Sample ID: 2000-08-0402-004

Project:

Received:

08/18/2000 15:25

Romak Iron Works

Extracted:

08/24/2000 20:59

Sampled:

08/17/2000 14:15

QC-Batch:

2000/08/24-01.02

Matrix:

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Gasoline	ND	50	ug/L	1.00	08/24/2000 20:59	
Benzene	ND	0.50	ug/L	1.00	08/24/2000 20:59	
Toluene	ND	0.50	ug/L	1.00	08/24/2000 20:59	
Ethyl benzene	ND	0.50	ug/L	1.00	08/24/2000 20:59	
Xylene(s)	ND	0.50	ug/L	1.00	08/24/2000 20:59	
MTBE	ND	5.0	ug/L	1.00	08/24/2000 20:59	
Surrogate(s)						
Trifluorotoluene	95.4	58-124	%	1.00	08/24/2000 20:59	
4-Bromofluorobenzene-FID	90.8	50-150	%	1.00	08/24/2000 20:59	

Environmental Services (SDB)

To: Aqua Science Engineers, Inc.

Test Method:

8020

Submission #: 2000-08-0402

8015M

5030

Attn.: Ian T. Reed

Prep Method:

Gas/BTEX and MTBE

Sample ID:

BH-E

Lab Sample ID: 2000-08-0402-005

Project:

Romak Iron Works

Received:

08/18/2000 15:25

Sampled:

Extracted:

08/24/2000 21:30

08/17/2000 15:20

QC-Batch:

2000/08/24-01.02

Matrix:

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Gasoline Benzene	ND ND	50 0.50	ug/L	1.00	08/24/2000 21:30	<u> </u>
Toluene	ND	0.50	ug/L ug/L	1.00 1.00	08/24/2000 21:30 08/24/2000 21:30	
Ethyl benzene Xylene(s)	ND ND	0.50 0.50	ug/L ug/L	1.00 1.00	08/24/2000 21:30 08/24/2000 21:30	
MTBE	ND	5.0	ug/L	1.00	08/24/2000 21:30	
Surrogate(s) Trifluorotoluene	78.9	58-124	%	1.00	08/24/2000 21:30	
4-Bromofluorobenzene-FID	81.5	50-150	%	1.00	08/24/2000 21:30	

Submission #: 2000-08-0402

Environmental Services (SDB)

To: Aqua Science Engineers, Inc.

Test Method:

8020 8015M

Attn.: Ian T. Reed

Prep Method:

5030

Gas/BTEX and MTBE

Sample ID:

BH-F

Lab Sample ID: 2000-08-0402-006

Project:

Received:

08/18/2000 15:25

Romak Iron Works

Sampled:

08/17/2000 16:15

Extracted:

08/24/2000 22:02

Matrix:

Water

QC-Batch:

2000/08/24-01.02

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Gasoline	ND	50	ug/L	1.00	08/24/2000 22:02	
Benzene	ND	0.50	1 - 1	1.00	, ,	
Toluene	ND	0.50	ug/L		08/24/2000 22:02	
Ethyl benzene	ND	,	ug/L	1.00	08/24/2000 22:02	
Xylene(s)	1 · · =	0.50	ug/L	1.00	08/24/2000 22:02	
MTBE	0.81	0.50	ug/L	1.00	08/24/2000 22:02	
MITE	ND	5.0	ug/L	1.00	08/24/2000 22:02	
Surrogate(s)	ĺ		!			
Trifluorotoluene	94.8	58-124	%	1.00	08/24/2000 22:02	
4-Bromofluorobenzene-FID	90.0	50-150	%	1.00	08/24/2000 22:02	

CHROMALAB, INC. Environmental Services (SDB)

Submission #: 2000-08-0402

To: Aqua Science Engineers, Inc.

Test Method:

8020 8015M

Attn.: Ian T. Reed

Prep Method:

5030

Gas/BTEX and MTBE

Sample ID:

MW-1

Lab Sample ID: 2000-08-0402-007

Project:

Received:

08/18/2000 15:25

Romak Iron Works

Sampled:

08/17/2000 15:00

Extracted:

08/24/2000 22:33

Matrix:

Water

QC-Batch:

2000/08/24-01.02

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Gasoline	840	50	ug/L	1.00	08/24/2000 22:33	
Benzene	55	0.50	ug/L	1.00	08/24/2000 22:33	g
Toluene	0.74	0.50	ug/L	1.00	08/24/2000 22:33	
Ethyl benzene	7.5	0.50	ug/L	1.00	08/24/2000 22:33	
Xylene(s)	ND	0.50	ug/L	1.00	08/24/2000 22:33	
MTBE	23	5.0	ug/L	1.00	08/24/2000 22:33	
Surrogate(s)					00,2 112000 22.00	
Trifluorotoluene	80.0	58-124	%	1.00	08/24/2000 22:33	
4-Bromofluorobenzene-FID	85.6	50-150	%	1.00	08/24/2000 22:33	

CHROMALAB, INC. Environmental Services (SDB)

Submission #: 2000-08-0402

To: Aqua Science Engineers, Inc.

Test Method:

8020

Attn.: Ian T. Reed

Prep Method:

8015M 5030

Batch QC Report Gas/BTEX and MTBE

Method Blank

Water

QC Batch # 2000/08/24-01.02

MB:

2000/08/24-01.02-001

Date Extracted: 08/24/2000 06:31

Compound	Result	Rep.Limit	Units	Analyzed	Flag
Gasoline	ND	50	ug/L	08/24/2000 06:31	<u> </u>
Benzene	ND	0.5	ug/L	08/24/2000 06:31	
Toluene	ND	0.5	ug/L	08/24/2000 06:31	
Ethyl benzene	ND	0.5	ug/L	08/24/2000 06:31	
Xylene(s)	ND	0.5	ug/L	08/24/2000 06:31	
MTBE	ND	5.0	ug/L	08/24/2000 06:31	
Surrogate(s)			1		
Trifluorotoluene	88.8	58-124	%	09/24/2000 00:04/	
4-Bromofluorobenzene-FID	86.4	50-150	%	08/24/2000 06:31 08/24/2000 06:31	

Submission #: 2000-08-0402

Environmental Services (SDB)

To: Aqua Science Engineers, Inc.

Test Method:

8020

8015M

5030

Attn: lan T. Reed

Prep Method:

Batch QC Report

Gas/BTEX and MTBE

Laboratory Control Spike (LCS/LCSD)

Water

QC Batch # 2000/08/24-01.02

LCS:

2000/08/24-01.02-002

Extracted: 08/24/2000 07:29

Analyzed

08/24/2000 07:29

LCSD:

2000/08/24-01.02-003

Extracted: 08/24/2000 10:06

Analyzed

08/24/2000 10:06

Compound	Conc.	[ug/L]	Exp.Conc.	[ug/L]	Recov	ery [%]	RPD	Ctrl. Lim	its [%]	Flac	
	LCS	LCSD	LCS	LCSD	LCS	LCSD	[%]	Recovery		LCS	LCSE
Gasoline	566	568	500	500	113.2	113.6	0.4	75-125	20		-
Benzene	109	109	100.0	100.0	109.0	109.0	0.0	77-123	20		
Toluene	108	107	100.0	100.0	108.0	107.0	0.9	78-122	20		
Ethyl benzene	100	100	100.0	100 0	100.0	100.0	0.0	70-130	20		! !
Xylene(s)	289	289	300	300	96.3	96.3		75-125	20		
Surrogate(s)		<u>;</u>						10 120	20		
Trifluorotoluene	528	527	500	500	105.6	105.4		58-124			
4-Bromofluorobenzene-FI	493	484	500	500	98.6	96.8		50-150	-		

CHROMALAB, INC. Environmental Services (SDB)

Submission #: 2000-08-0402

To: Aqua Science Engineers, Inc.

Test Method:

8015M

Attn:lan T. Reed

8020

Prep Method: 5030

Legend & Notes

Gas/BTEX and MTBE

Analyte Flags

g

Hydrocarbon reported in the gasoline range does not match our gasoline standard.

1220 Quarry Lane * Pleasanton, CA 94566-4756 Telephone (925) 484-1919 'Facsimile' (925) 484-1096

CHROMALAB, INC. Environmental Services (SDB)

Submission #: 2000-08-0402

To: Aqua Science Engineers, Inc.

Test Method:

8015M 8020

Attn:lan T. Reed

Prep Method: 5030

Legend & Notes

Gas/BTEX and MTBE

Analyte Flags

g

Hydrocarbon reported in the gasoline range does not match our gasoline standard.

1220 Quarry Lane * Pleasanton, CA 94566-4756 Telephone (925) 484-1919 · Facsimile (925) 484-1096 Environmental Services (SDB)

Total Extractable Petroleum Hydrocarbons (TEPH)

Aqua Science Engineers, Inc.

208 West El Pintado Road

Danville, CA 94526

Attn: lan T. Reed

Phone: (925) 820-9391 Fax: (925) 837-4853

Project #:

Project: Romak Iron Works

Samples Reported

Sample ID	Matrix	Date Sampled	Lab#
BH-A	Water	08/17/2000 11:00	1
вн-в	Water	08/17/2000 10:20	2
BH-C	Water	08/17/2000 12:00	3
BH-D	Water	08/17/2000 14:15	4
BH-E	Water	08/17/2000 15:20	5
BH-F	Water	08/17/2000 16:15	6
MW-1	Water	08/17/2000 15:00	7

Environmental Services (SDB)

To: Aqua Science Engineers, Inc.

Test Method:

8015m

Submission #: 2000-08-0402

Attn.: Ian T. Reed

Prep Method:

3510/8015M

Total Extractable Petroleum Hydrocarbons (TEPH)

Sample ID:

BH-A

Lab Sample ID: 2000-08-0402-001

Project:

Romak Iron Works

Received:

08/18/2000 15:25

Extracted:

08/21/2000 10:12

Sampled:

08/17/2000 11:00

QC-Batch:

Matrix:

Water

2000/08/21-02.10

Sample/Analysis Flag rl (See Legend & Note section)

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Diesel Motor Oil	ND ND	71 710	ug/L ug/L	1.43 1.43	08/22/2000 05:52 08/22/2000 05:52	
Surrogate(s) o-Terphenyl	87.6	60-130	%	1.43	08/22/2000 05:52	

Submission #: 2000-08-0402

Environmental Services (SDB)

To: Aqua Science Engineers, Inc.

Attn.: Ian T. Reed

Test Method:

8015m

Prep Method:

3510/8015M

Total Extractable Petroleum Hydrocarbons (TEPH)

Sample ID:

вн-в

Lab Sample ID: 2000-08-0402-002

Project:

Romak Iron Works

Received:

08/18/2000 15:25

Extracted:

08/21/2000 10:12

Sampled:

08/17/2000 10:20

QC-Batch:

2000/08/21-02.10

Matrix:

Water

Sample/Analysis Flag rl (See Legend & Note section)

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Diesel Motor Oil	ND ND	83 830	ug/L ug/L	1.67 1.67	08/22/2000 06:30 08/22/2000 06:30	ndp
Surrogate(s) o-Terphenyl	89.9	60-130	%	1.67	08/22/2000 06:30	

Submission #: 2000-08-0402

Environmental Services (SDB)

To: Aqua Science Engineers, Inc.

Attn.: Ian T. Reed

Test Method:

8015m

Prep Method:

3510/8015M

Total Extractable Petroleum Hydrocarbons (TEPH)

Sample ID:

BH-C

Lab Sample ID: 2000-08-0402-003

Project:

Romak Iron Works

Received:

08/18/2000 15:25

Sampled:

08/17/2000 12:00

Extracted:

08/21/2000 10:12

Matrix:

Water

QC-Batch: 2000/08/21-02.10

Sample/Analysis Flag rl (See Legend & Note section)

Compound	Result	Rep.Limit Units		Dilution	Analyzed	Flag
Diesel Motor Oil	150 ND	¹ 77 770	ug/L ug/L	1.54 1.54	08/22/2000 07:08 08/22/2000 07:08	ldr
Surrogate(s) o-Terphenyl	47.4	60-130	%	, 1,54	08/22/2000 07:08	si,si

Submission #: 2000-08-0402

Environmental Services (SDB)

Aqua Science Engineers, Inc. To:

Attn.: Ian T. Reed

Test Method:

8015m

Prep Method:

3510/8015M

Total Extractable Petroleum Hydrocarbons (TEPH)

Sample ID:

BH-D

Lab Sample ID: 2000-08-0402-004

Project:

Romak Iron Works

Received:

08/18/2000 15:25

Extracted:

08/21/2000 10:12

Sampled:

08/17/2000 14:15

QC-Batch:

2000/08/21-02.10

Matrix:

Water

Sample/Analysis Flag rl (See Legend & Note section)

Compound	Result	Rep.Limit Units		Dilution	Analyzed	Flag
Diesel Motor Oil	ND ND	100 1000	ug/L ug/L	2.00 2.00	08/22/2000 07:47 08/22/2000 07:47	ndp
Surrogate(s) o-Terphenyl	89.6	60-130	%	2.00	08/22/2000 07:47	

Submission #: 2000-08-0402

Environmental Services (SDB)

Aqua Science Engineers, Inc. To:

Test Method:

8015m

Attn.: Ian T. Reed

Prep Method:

3510/8015M

Total Extractable Petroleum Hydrocarbons (TEPH)

Sample ID:

BH-E

Lab Sample ID: 2000-08-0402-005

Project:

Romak Iron Works

Received:

08/18/2000 15:25

Sampled:

Extracted:

08/21/2000 10:12

08/17/2000 15:20

QC-Batch:

2000/08/21-02.10

Matrix:

Water

Sample/Analysis Flag rl (See Legend & Note section)

Compound	Result	Rep.Limit Unit		Dilution	Analyzed	Flag
Diesel ND Motor Oil ND		61 610	ug/L ug/L	1.22 1.22	08/23/2000 17:47 08/23/2000 17:47	
Surrogate(s) o-Terphenyl			%	1.22	08/23/2000 17:47	

Submission #: 2000-08-0402

Environmental Services (SDB)

To: Aqua Science Engineers, Inc.

Test Method:

8015m

Attn.: Ian T. Reed Prep Method:

3510/8015M

Total Extractable Petroleum Hydrocarbons (TEPH)

Sample ID:

BH-F

Lab Sample ID: 2000-08-0402-006

Project:

Romak Iron Works

Received:

08/18/2000 15:25

Sampled:

08/17/2000 16:15

Extracted:

08/21/2000 10:12

QC-Batch:

2000/08/21-02.10

Matrix:

Water

Sample/Analysis Flag rl (See Legend & Note section)

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Diesel Motor Oil	ND ND	59 590	ug/L ug/L	1.18 1.18	08/22/2000 08:25 08/22/2000 08:25	
Surrogate(s) o-Terphenyl	80.1	60-130	%	1.18	08/22/2000 08:25	

Submission #: 2000-08-0402

Environmental Services (SDB)

To: Aqua Science Engineers, Inc.

Test Method:

8015m

Attn.: Ian T. Reed

Prep Method:

3510/8015M

Total Extractable Petroleum Hydrocarbons (TEPH)

Sample ID:

MW-1

Lab Sample ID: 2000-08-0402-007

Project:

Romak Iron Works

Received:

08/18/2000 15:25

Sampled:

08/17/2000 15:00 .

Extracted:

08/21/2000 10:12

Matrix:

Water

QC-Batch:

2000/08/21-02.10

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Diesel Motor Oil	1100 700	50 50 0	ug/L ug/L		08/22/2000 09:03 08/22/2000 09:03	ndp
Surrogate(s) o-Terphenyl	92.6	60-130	%		08/22/2000 09:03	!

Submission #: 2000-08-0402

Environmental Services (SDB)

To: Aqua Science Engineers, Inc.

Attn.: Ian T. Reed

Test Method:

8015m

Prep Method:

3510/8015M

Batch QC Report

Total Extractable Petroleum Hydrocarbons (TEPH)

Method Blank

Water

QC Batch # 2000/08/21-02.10

MB:

2000/08/21-02.10-001

Date Extracted: 08/21/2000 10:12

Compound	Result	Rep.Limit	Units	Analyzed	Flag
Diesel Motor Oil	ND ND	50 500	ug/L ug/L	08/22/2000 02:00 08/22/2000 02:00	
Surrogate(s) o-Terphenyl	89.0	60-130	%	08/22/2000 02:00	

Submission #: 2000-08-0402

Environmental Services (SDB)

To: Aqua Science Engineers, inc.

Test Method:

8015m

Attn: Ian T. Reed

Prep Method:

3510/8015M

Batch QC Report

Total Extractable Petroleum Hydrocarbons (TEPH)

Laboratory Control Spike (LCS/LCSD)

Water

QC Batch # 2000/08/21-02.10

LCS:

2000/08/21-02.10-002

Extracted: 08/21/2000 10:12

Analyzed 08/22/2000 01:22

LCSD:

2000/08/21-02.10-003

Extracted: 08/21/2000 10:12

Analyzed 08/22/2000 00:43

Compound	Conc.	[ug/L]	Exp.Conc.	[ug/L]	Recov	/ery [%]	RPD	Ctrl. Lim	its [%]	Flag	 18
	LCS	LCSD	LCS	LCSD	LCS	LCSD	[%]	Recovery	RPD	LCS	LCSD
Oiesel Surrogate(s)	804	785	1250	1250	64.3	62.8	2.4	60-130	25		
o-Terphenyl	17.2	17.0	20.0	20.0	86.0	85.0		60-130			

Environmental Services (SDB)

To: Aqua Science Engineers, Inc.

Attn:lan T. Reed

Test Method:

8015m

Prep Method: 3510/8015M

Legend & Notes

Total Extractable Petroleum Hydrocarbons (TEPH)

Analysis Flags

Γĺ

Reporting limits raised due to reduced sample size.

Analyte Flags

ldr

Hydrocarbon reported is in the late Diesel range, and does not match our Diesel standard

ndp

Hydrocarbon reported does not match the pattern of our Diesel standard

si

Surrogate recoveries were lower than QC limit due to matrix interference, confirmed by

reanalysis.

54026.

2000-08-0402

Aqua Science Enginee**rs, Inc.** 208 W. El P. ntado Road Danville, CA 94526 (925) 820-9391 FAX (925) 837-48**53**

Chain of Custody

SAMPLER (510	NATURE)		_		(PH	IONE NO).)	PRC) IFCT I	VALJE	τ	,	. 7						PA	GE 3 NO.		. OF	
West	\mathcal{P}_{0}	ed		(029	:)02	رو - 0	1 <i>G</i> /		ADD	RESS	3:	<u></u>	<u>omo</u>	κ ፲, st, (con	Wor	Ks			_ JOE	3 NO.	_		
ANAL	YSI	S RE	QL	JES	T	0 12	Ť	 		T .		<u> </u>	701113	<u> </u>	<u> </u>	1d (<u>A</u>			-				
SPECIAL INSTI	RUCTIONS			-			TPH-GAS / MTBE & BTEX (EPA 5030/8015-8020)	TPH-DIESEL (EPA 3510/8015)	TPH-DIESEL & MOTOR OIL (EPA 3510/8015)	PURGEABLE HALOCARBONS (EPA 601/8010)	VOLATILE ORGANICS (EPA 624/8240/8260)	SEMI-VOLATILE ORGANICS (EPA 625/8270)	EASE	LUFT METALS (5) (EPA 6010+7000)	CAM 17 METALS (EPA 6010+7000)	PCBs & PESTICIDES (EPA 608/8080)	ORGANOPHOSPHORUS PESTICIDES (EPA 8140 EPA 608/8080)	FUEL OXYGENATES (EPA 8260)	Pb (TOTAL or DISSOLYED) (EPA 6010)	TPH-G/BTEX/5 0XY'S (EPA 8260)	TPH-G/BTEX/ 7 0XY'S / HVOCS (EPA 8260)			1E
SAMPLE ID	DATE		МА	TRIX		D. OF IPLES	TPH-GA (EPA 5C	TPH-DIE (EPA 35	TPH-DIE (EPA 35	PURGEA (EPA 60	VOLATILE (EPA 62	SEMI-VOI (EPA 62!	OIL & GREASE (EPA 5520)	LUFT MET EPA 601	CAM 17 M EPA 601	CBs & F EPA 60	ORGANC FETICID PA 608	UEL OXY EPA 820	F (TOTA	7H-G/B1	74-6/81 70CS (EF			COMPOSITE
BH-A	0/17	1100	ارا	ter	5	5	\geq		\times						-	***	- W- HI	F (f	三二二	口巴	产壬		 	+-
BH-B	8/17	1020		<u> </u>		<u> </u>	\geq	·	\geq														-	
13H-C	8/17	1200					\geq		\approx															
13H-E	6/17	1415 1520	\dashv		\dashv		\bowtie		\iff													···		
BH-F	8/17	1915	\dashv		+		\Diamond	-	$\langle \rangle$															 -
Mw-1	8/17	1500	7		4		\Rightarrow		>															
														_										
																		\dashv	\rightarrow					
													 											
251 1404164 150 0			_											`						+				
RELINQUISHED 8: (signature)		*)	ı	CEIVE gratur	(e) (A)	(time)	}/	RELING (signat		(time)	1575 1575	RECENT Signat	ED BY	DABOR	ATORY:	52		MENTS):		<u>l</u> .	1
(printed name)	(date	»)		nted r	iame)	110v	(date)		(printe	d name)	1100	•		(printed	\geq_{∞}	LEY	(date)	18/0	<u> </u>	TUR	N AROU	ND TIN	/E	_
Company- A5 [<u> </u>	···	Cor	npany.	En	alf	"_	 .	Compa 4	ny-	m	- 		Compar			(SIGNO)	(STAI	VDARD	24Hr			Hr

APPENDIX E

Well Sampling Field Logs

WELL SAMPLING FIELD LOG

Project Name and Address:	Momal Iron works
Job #: 2659	Date of sampling: 8/17/00 2(4) Sampled by: 1TC 21.78 Well diameter (inches): 2"
Well Name: MW-1 2	2(6) Sampled by:ITR
Total depth of well (feet):	21.78 Well diameter (inches). 2"
Depth to water before sampling	g (feet): 8 • 3 f any:
Thickness of floating product is	fany:
Depth of well casing in water	(fcet): 13.75
Number of gallons per well ca	sing volume (gallons) 2.3
Number of well casing volume	s to be removed
-Keqa volume of groundwater t	o be purged belote sampling (gallons). 9,4
Equipment used to purge the	well: dea boiler
Time Evacuation Began: 1410	Time Evacuation Finished: 1930
Approximate volume of ground	dwater purged 95
Did the well go dry?. NO.	After how many gallons
Time samples were collected:_	1500
Depth to water at time of sam	1500 pling: 8 07 impling: 94'/
Percent recovery at time of sa	umpling:
Samples collected with:	d. Jale
Sample color: Clear Groy	Odor: sugnt Hoder
Description of sediment in san	nple: Sitt
CHEMICAL DATA	· .
Yolume Purged <u>Temp</u>	pil Conductivity
	(11) 700
71.3	(.40 (.41 720
71.9	1.41
11.3	+1-13 - 3-19
Yolurne Purged Temp 1 7 2 71.3 3 71.4 4 71.5	
SAMPLES COLLECTED	
Samuel Market and Market	
Sample # of containers Volume & MW-1 5 YUr	type container Pres Iced? Analysis
	11 VOA- V V