

Fax: 510-547-5043 Phone: **510-450-6000**

December 16, 1994

Brian Oliva Alameda County Department of Environmental Health 1131 Harbor Bay Parkway Suite 250 Alameda, CA 94502 STID84

Re: Shell Service Station WIC #204-2495-0101 1800 Powell Street Emeryville, California WA Job #81-0794-104

Dear Mr. Oliva:

This letter describes recently completed and anticipated activities at the Shell service station referenced above (Figure 1). This status report satisfies the quarterly reporting requirements prescribed by California Administrative Code Title 23 Waters, Chapter 3, Subchapter 16, Article 5, Section 2652.d. Included below are descriptions and results of activities performed in the fourth quarter 1994 and proposed work for the first quarter 1995.

Fourth Quarter 1994 Activities:

- Blaine Tech Services, Inc. (BTS) of San Jose, California measured ground water depths and collected ground water samples from the site wells. BTS' report describing these activities and the analytic report for the ground water samples are included as Attachment A.
- BTS sampled well S-8 for total dissolved solids (TDS). The sample contained 4,500 parts per million (ppm) TDS, above the Regional Water Quality Control Board's threshold of 3,000 ppm for domestic water supply.
- Weiss Associates (WA) calculated ground water elevations, compiled the analytic data (Table 1) and prepared a ground water elevation contour map (Figure 2).

Brian Oliva December 16, 1994



Anticipated First Quarter 1995 Activities:

WA will submit a report presenting the results of the first quarter 1995 ground water sampling and ground water depth measurements. The report will include tabulated chemical analytic results, ground water elevations and a ground water elevation contour map.

Please call if you have any questions.

Sincerely,

Weiss Associates

J. Michael Asport Staff Scientist I

James W. Carmody, C.E.G. Senior Project Hydrogeologist

JMA/JWC:jma

cc:

Attachments: A - Blaine Tech's Ground Water Monitoring Report

> Dan Kirk, Shell Oil Company, P.O. Box 4023, Concord, California 94524 Kevin Graves, Regional Water Quality Control Board - San Francisco Bay Region,

2101 Webster Street, Suite 500, Oakland, California 94612






Figure 1. Site Location Map - Shell Service Station WIC# 204-2495-01, 1800 Powell Street, Emeryville, California






Figure 2. Monitoring Well Locations and Ground Water Elevation Contours - November 9, 1994 - Shell Service Station - WIC# 204-2495-0107, 1800 Powell Street, Emeryville, California

Table 1. Ground Water Elevations and Analytic Results - Shell Service Station WIC# 204-2495-0101, 1800 Powell Street, Emeryville, California

Well ID	Sampling Date	Top-of- Casing (ft msl)	Depth to Water (ft)	Separate- Phase Hydrocarbon Thickness (ft)	Ground Water Elevation (ft msl)	TDS	ТРН-G	TPH-D	B -parts per billion	Τ n (μg/L)———	E	X →
S-5	10/26/84	11.72					3,000		660	20	20	70
0 3	02/09/85			****			2,800		740	20	20	140
	04/27/85					special sp	4,300		750	10	20	<30
	07/06/85			Moranda			1,500		300	8.0	7.0	9.0
	10/24/85						2,100		760	10	40	50
	01/03/86		W 700 FF				1,300		520	9.0	8.0	10
	07/05/86		8.36		3.36	***	1,400		500	10	4.0	<10
	10/18/86						4,200		1,100	9.0	14	7.0
	01/13/87				===		4,500	6,100	1,100	15	30	25
	07/07/87		9.15		2.57		3,200	0,100	1,000	15 16	9.0	12
	10/10/87		9.67		2.05		1,700		1,000	5.7	5.2	8.9
	02/11/88		9.00		2.72		1,300		300	5.0	< 5	<5
	05/10/88		8.61		3.11		1,900		490	< 0.5	<5	<5 .
	08/31/88		9.61		2.11		6,700		760	26	<25	<25
	12/03/88		9.47		2.25		2,900	***	890	5.3	7.3	13
	02/16/89		8.29		3.43		1,300		280	3.0	3.4	9.4
	08/10/89		9.30		2.42	Birm	1,700		530	5.5	<5	5.8
	11/11/89		9.42		2.30		1,700			J.J		J.0
	02/21/94		7.95		3.77		1,000		250	<5	<5	<5
	02/21/94 ^{dup}		7.95		3.77		1,300		220	<5	<5	11
	05/16/94		8.00		3.72		1,200		230	<5	<5	< 5
	08/09/94°						1,200		250			
	11/9/94	ray debesin	8.32		3.40		1,600		220	3.1	1.8	5.0
	11/9/94 ^{dup}		8.32		3,49 75		1,600		250 250	3.3	1.9	5.9
S-6 ^b	04/27/85		*				6,500		2,400	30	50	210
	07/06/85					***	3,700		1,700	34	55	200
	10/24/85						< 50		23	< 0.5	< 5	10
	11/09/85 ^b			~~~		-						
S-7 ^b	10/26/84						50		1.1	<1	<1	4
	02/09/85					*			0.90	< 1	< 1	<3
	04/27/85						< 50		<1	<1	<1	<3
	07/06/85						70		2.2	< 1	<1	<3
	10/24/85	,					6,200		2,200	130	190	660
	11/09/85 ⁶						***	***				

⁻Table 1 continues on next page-



Table 1. Ground Water Elevations and Analytic Results - Shell Service Station WIC# 204-2495-0101, 1800 Powell Street, Emeryville, California (continued)

Well ID	Sampling Date	Top-of- Casing (ft nisl)	Depth to Water (ft)	Separate- Phase Hydrocarbon Thickness (fl)	Ground Water Elevation (ft msl)	TDS	TPH-G	TPH-D	B -parts per billic	T	E	X
		` /	· · ·	3-7			·		parts par state	, (FB, 22)		<u>′</u>
S-8	10/26/84	12.76					1,000	k	610	9.0	1.0	42
•	02/09/85	12.70			***		500		160	5.0	<2	17
	04/27/85						2,700		1500	20	10	40
	07/06/85						440		180	5.0	2.0	12
	10/24/85					No. do com	2,000		1,100	17	5.0	70
	01/03/86						1,900		1,300	20	<10	70
	07/05/86		9.50		3.26		1,600		920	30	<10	60
	10/18/86				3.20		1,400		640	< 10	< 10	30
	01/13/87						670	760	190	5.8	< 0.5	30 19
	04/22/87						2,400	700	740	5.8 54	5.7	59
	07/07/87		10.45		2.31		1,100		450	15	<2.5	42
	10/10/87		10.43		1.93		340		4.0	0.60	<0.5	17
	02/11/88		10.44		2.32		<1,000		260	<10	< 10	11
	05/10/88		10.17		2.59		1,800		700	14	<5	46
	08/31/88 ^{SPH}		10.81	***	1.95		1,400		700			
	12/03/88		10.81		1.95		960		250	4.3	<2.5	14
	02/16/89		9.65		3.11		2,700		800	35	10	83
	05/28/89		10.46		2.3		960		710	25	84	80
•	08/10/89		10.59	,	2.17		1,300		630	17	<5	46
	11/11/89		10.29		2.47		910		180	8	<2.5	15
	02/21/94		9.52		3.24	2.910.000	3,200		480	52	< 5	130
	05/16/94		9.49	***	3.27	2,510,000	1,000		220	7.3	<5	28
	05/16/94 ^{dup}		9.49		3.27		1,000		280	10	<5	28 29
	08/09/94		10.37		2.39	4,500,000	400		27	6.6	< 0.5	18
	11/09/94	edg edga	9.58		3.18	4,600,000	650		170	5.3	<0.5	10 17
S-9	10/26/84 ^{SPH}	12.75										
3-9	02/09/85 ^{SPH}	12.73		1.70								A-4-4
	04/27/85 ^{SPH}			1.30								
	04/2//85 07/06/85 ^{SPH}	-		1.25								
	10/24/85 ^{SPH}			1.20								
	01/03/86 ^{SPH}		th code									
	04/11/86 SPH											
	04/11/86 07/05/86 ^{SPH}		0.67		2.00	***				41 to -12		***
	10/18/86 SPH		9.67		3.08							
	10/10/00											

⁻Table 1 continues on next page-



Table 1. Ground Water Elevations and Analytic Results - Shell Service Station WIC# 204-2495-0101, 1800 Powell Street, Emeryville, California (continued)

04/ 07/ 10/ 02/ 05/ 08/ 11/ S-10 10/ 02/ 04/ 07/ 10/ 01/ 04/ 07/ 10/ 01/ 04/ 07/ 10/ 01/ 04/ 07/ 10/ 04/ 07/ 04/ 07/	1/13/87 ^{SPH} 4/22/87 ^{SPH} 4/22/87 ^{SPH} 7/07/87 ^{SPH} 0/10/87 ^{SPH} 2/24/94 ^{SPH} 5/16/94 ^{SPH} 1/09/94 ^{SPH} 1/09/94 ^{SPH} 0/26/84 2/09/85 4/27/85 7/06/85 0/24/85 1/03/86 4/11/86 ^{SPH}	12.58	22.30	1.5 2.0	 -9.55 0.95		700,000 6,500 13,000 4,200 1,700		37,000 480 1,300 1,300 580 360	100,000 700 500 310 34	20,000 100 600 270 4 7.8	110000 1800 3700 2400 440 170
04/ 07/ 10/ 02/ 05/ 08/ 11/ S-10 10/ 02/ 04/ 07/ 10/ 01/ 04/ 07/ 10/ 01/ 04/ 07/ 10/ 01/ 04/ 07/ 10/ 04/ 07/ 04/ 07/	4/22/87 ^{SPH} 7/07/87 ^{SPH} 7/07/87 ^{SPH} 0/10/87 ^{SPH} 0/10/87 ^{SPH} 2/24/94 ^{SPH} 5/16/94 ^{SPH} 8/09/94 ^{SPH} 1/09/94 ^{SPH} 0/26/84 2/09/85 4/27/85 7/06/85 1/03/86 4/11/86 ^{SPH}	12.58	22.30 11.80 	 1.5 2.0	-9.55 -9.55 0.95		700,000 6,500 13,000 14,000 4,200 1,700	 	37,000 480 1,300 1,300 580	100,000 700 500 310 34	20,000 100 600 270 4 7.8	110000 1800 3700 2400 440 170
07/ 10/ 02/ 05/ 08/ 11/ S-10 10/ 02/ 04/ 07/ 10/ 01/ 04/ 07/ 10/ 04/ 07/ 10/ 04/ 07/ 10/ 04/ 07/	7/07/87 ^{SPH} 0/10/87 ^{SPH} 0/10/87 ^{SPH} 2/24/94 ^{SPH} 5/16/94 ^{SPH} 8/09/94 ^{SPH} 1/09/94 ^{SPH} 0/26/84 2/09/85 4/27/85 7/06/85 1/03/86 4/11/86 ^{SPH}	12.58	22.30 11.80 	 1.5 2.0	-9.55 0.95		700,000 6,500 13,000 14,000 4,200 1,700		37,000 480 1,300 1,300 580	100,000 700 500 310 34 10	20,000 100 600 270 4 7.8	110000 1800 3700 2400 440 170
10/ 02/ 05/ 08/ 11/ S-10 10/ 02/ 04/ 07/ 10/ 01/ 04/ 07/ 10/ 01/ 04/ 07/ 10/ 04/ 07/ 10/ 04/ 07/ 01/ 04/ 07/ 01/ 04/ 07/ 01/ 04/ 07/ 04/ 07/ 04/ 07/ 04/ 07/ 04/ 07/ 04/ 07/ 04/ 07/ 04/ 04/ 04/ 04/ 04/ 04/ 04/ 04/ 04/ 04	0/10/87 ^{SPH} 2/24/94 ^{SPH} 5/16/94 ^{SPH} 8/09/94 ^{SPH} 1/09/94 ^{SPH} 0/26/84 2/09/85 4/27/85 7/06/85 0/24/85	12.58	22.30 11.80 	 1.5 2.0	-9.55 0.95	 	700,000 6,500 13,000 14,000 4,200 1,700		37,000 480 1,300 1,300 580	100,000 700 500 310 34 10	20,000 100 600 270 4 7.8	110000 1800 3700 2400 440 170
02/ 05/ 08/ 11/ S-10 10/ 02/ 04/ 07/ 10/ 01/ 04/ 07/ 10/ 01/ 04/ 07/ 10/ 04/ 07/	2/24/94 ^{SPH} 5/16/94 ^{SPH} 8/09/94 ^{SPH} 1/09/94 ^{SPH} 0/26/84 2/09/85 4/27/85 7/06/85 1/03/86 4/11/86 ^{SPH}	12.58	 11.80	 1.5 2.0 0.01	 0.95	 	700,000 6,500 13,000 14,000 4,200 1,700	 	37,000 480 1,300 1,300 580	100,000 700 500 310 34 10	20,000 100 600 270 4 7.8	110000 1800 3700 2400 440 170
05/ 08/ 11/ S-10 10/ 02/ 04/ 07/ 10/ 01/ 04/ 07/ 10/ 04/ 07/ 10/ 02/ 05/ 08/	5/16/94 ^{SPH} 8/09/94 ^{SPH} 1/09/94 ^{SPH} 0/26/84 2/09/85 4/27/85 7/06/85 0/24/85 1/03/86 4/11/86 ^{SPH}	12.58	 11.80	1.5 2.0	 0.95	 	700,000 6,500 13,000 14,000 4,200 1,700	 	37,000 480 1,300 1,300 580	100,000 700 500 310 34 10	20,000 100 600 270 4 7.8	110000 1800 3700 2400 440 170
08/ 11/ S-10 10/ 02/ 04/ 07/ 10/ 01/ 04/ 07/ 10/ 02/ 05/ 08/	8/09/94 ^{SPH} 1/09/94 ^{SPH} 0/26/84 2/09/85 4/27/85 7/06/85 0/24/85 1/03/86 4/11/86 ^{SPH}	12.58	 	2.0 0.01	0.95		700,000 6,500 13,000 14,000 4,200 1,700	 	37,000 480 1,300 1,300 580	100,000 700 500 310 34 10	20,000 100 600 270 4 7.8	110000 1800 3700 2400 440 170
S-10 10/ 02/ 04/ 07/ 10/ 01/ 04/ 07/ 10/ 04/ 07/ 10/ 02/ 05/ 08/	1/09/94 SPH 0/26/84 2/09/85 4/27/85 7/06/85 0/24/85 1/03/86 4/11/86 SPH	12.58	 	 0.01	 		6,500 13,000 14,000 4,200 1,700	 	37,000 480 1,300 1,300 580	100,000 700 500 310 34 10	100 600 270 4 7.8	1800 3700 2400 440 170
02/ 04/ 07/ 10/ 01/ 04/ 07/ 10/ 07/ 10/ 02/ 05/ 08/	2/09/85 4/27/85 7/06/85 0/24/85 1/03/86 4/11/86 ^{SPH}	12.58		 0.01	 		6,500 13,000 14,000 4,200 1,700		480 1,300 1,300 580	700 500 310 34 10	100 600 270 4 7.8	1800 3700 2400 440 170
02/ 04/ 07/ 10/ 01/ 04/ 07/ 10/ 07/ 10/ 02/ 05/ 08/	2/09/85 4/27/85 7/06/85 0/24/85 1/03/86 4/11/86 ^{SPH}			 0.01	 		6,500 13,000 14,000 4,200 1,700		480 1,300 1,300 580	700 500 310 34 10	100 600 270 4 7.8	1800 3700 2400 440 170
04/ 07/ 10/ 01/ 04/ 07/ 10/ 04/ 07/ 10/ 02/ 05/ 08/	4/27/85 7/06/85 0/24/85 1/03/86 4/11/86 ^{SPH}	,		 0.01	 		13,000 14,000 4,200 1,700		1,300 1,300 580	500 310 34 10	600 270 4 7.8	3700 2400 440 170
07/ 10/ 01/ 04/ 07/ 10/ 01/ 07/ 10/ 02/ 08/	7/06/85 0/24/85 1/03/86 4/11/86 ^{SPH}	,		 0.01	 		14,000 4,200 1,700		1,300 580	310 34 10	270 4 7.8	2400 440 170
10/ 01/ 04/ 07/ 10/ 01/ 04/ 07/ 10/ 02/ 05/ 08/	0/24/85 1/03/86 4/11/86 ^{SPH}			0.01	 		4,200 1,700		580	34 10	4 7.8	440 170
01/ 04/ 07/ 10/ 01/ 04/ 07/ 10/ 02/ 05/ 08/	1/03/86 4/11/86 ^{SPH}		***	0.01			1,700			10	7.8	170
04/ 07/ 10/ 01/ 04/ 07/ 10/ 02/ 05/ 08/	4/11/86 ^{SPH}						•					
07/ 10/ 01/ 04/ 07/ 10/ 02/ 05/ 08/	CDIT		9 16								***	
01/ 04/ 07/ 10/ 02/ 05/ 08/	7/05/86 ^{SPH}			0.01	3.42							***
04/ 07/ 10/ 02/ 05/ 08/	0/18/86 ^{SPH}			0.03								
04/ 07/ 10/ 02/ 05/ 08/	1/13/87 ^{SPH}			0.03								
07/ 10/ 02/ 05/ 08/	4/22/87 ^{SPH}			0.01	***						**	
02/ 05/ 08/	7/07/87 ^{SPH}		9.41	0.03	3.17			***			_	,
05/ 08/	0/10/87 ^{SPH}		7.77	***	4.81							
08/	2/11/88		6.41		6.17		1,200	****	470	16	<5	14
08/	5/10/88		9.04	-	3.54		1,100		100	6	4	19
	8/31/88 ^{SPH}		9.38	0.01	3.20							
	2/03/88 ^{SPH}		6.89		5.69							
	2/16/89		7.34		5.24		530	***	89	8.5	1.6	4.5
	5/28/89		6.60		5.98	+	240		65	3.8	2.2	8.6
	8/10/89		9.09		3.49		250		23	4.1	<1	6.4
	1/11/89°		6.58		6		320		1.6	1.3	1.4	6.2
	2/21/94		8.32		4.26		1,400	**	190	9.9	< 2.5	19
	5/16/94		8.35		4.23		300		45	8.6	6.2	19
	8/08/94 1/ <mark>09/94</mark>	· · · · · · · · · · · · · · · · · · ·	8.66 6.68		3.92 5.90		700 640		57 130	14 2.0	<0.5 1.6	9.3 4.1
\$-12 07/		es Personalis	8.22	er i tur eka beste		aga mara ay ar an ilin m	<250	2,200	0.71	<0.5	<0.5	<3.6

⁻Table 1 continues on next page-



Table 1. Ground Water Elevations and Analytic Results - Shell Service Station WIC# 204-2495-0101, 1800 Powell Street, Emeryville, California (continued)

Well ID	Sampling Date	Top-of- Casing (ft msl)	Depth to Water (ft)	Separate- Phase Hydrocarbon Thickness (ft)	Ground Water Elevation (ft mst)	TDS	TPH-G	ТРН-D	B	T	E	. x
	Date	(It msi)	(11)	(11)	(n msi)		<u> </u>		parts per billio	n (µg/L)		}
	11/16/85						<250	1,400	18	< 2	<2	<5
	01/03/86						<250		24	2	< 2	<5
	07/05/86		8.27		4.57		80		15	0.7	< 0.5	2
	10/18/86						150		12	9	< 0.5	3.6
	01/13/87						120	1,000	3.6	0.8	< 0.5	2.9
	04/22/87						100	820	3.7	3.8	0.8	11
	07/07/87		9.5		3.34		70	***	2.5	0.8	< 0.5	2.4
	10/10/87		9.9		2.94		220	2,500	2.1	0.7	< 0.5	1.2
	02/11/88		9.43		3.41		110	2,500	0.8	< 0.5	< 0.5	1.3
	05/10/88		8.65		4.19		140	3,800 ^d	0.8	0.8	< 0.5	2.5
	08/31/88		9.86		2.98		190	2,600 ^d	3	15	0.5	4.5
	12/03/88		9.93		2.91		180	3,900 ^d	1.2	1	1	7.7
	02/16/89		8.08		4.76		350°	2,100 ^d	0.6	< 0.5	0.5	5.5
	05/28/89		9.08		3.76	***	290	2,200	2	1.6	4.4	6
	08/10/89		9.35		3.49		240	720	0.7	< 0.5	< 0.5	1.1
	11/11/89		9.28		3.56		210°	4,100	0.7	0.5	< 0.5	3.4
	02/21/94		8.22		4.62		240 ^f	2,200g	0.7	< 0.5	< 0.5	3.6
	05/16/94		8.92		3.92	***	96	2,200	1.5	< 0.5	< 0.5	2.0
	08/08/94						110 ^h	3,500 ⁱ	< 0.5	< 0.5	< 0.5	< 0.5
	11/09/94		7.56		5.28		80	5,400°	80	< 0.5	< 0.5	0.6
S-13	07/06/85	12.59	9.26				700	3,600	200	<5	<5	45
	11/16/85						1,900	2,000	700	160	70	340
	01/03/86						2,800	,	1.400	130	10	500
	07/05/86		9.47		3.12		3,100		1,800	60	40	270
	10/23/86						3,400		1,500	28	28	250
	01/13/87						1,900	900	830	15	< 10	99
	04/22/87						2,900°	770 ⁱ	1,100	20	30	140
	07/07/87		10.38		2.21		1.500		880	10	6	160
	10/10/87		10.78		1.81		480	2,400	830	15	< 0.5	120
	02/11/88		10.48		2.11		1,300	1,300	510	< 10	< 10	86
	05/10/88		9.48		3.11		1,000	1,300 ^d	470	< 0.5	<5	50
	08/31/88 ^{SPH}		10.74		1.85		-,				2	
	12/03/88		10.3		2.29		900	2,400 ^d	290	4.6	< 2.5	20
	02/16/89		7.6		4.99		840 ^e	1,200 ^d	310	3.5	< 2.5	27
	05/28/89°		10.6		1.99		2,100	4,600	1.100	19	50	350

⁻Table 1 continues on next page-



Table 1. Ground Water Elevations and Analytic Results - Shell Service Station WIC# 204-2495-0101, 1800 Powell Street, Emeryville, California (continued)

Well ID	Sampling Date	Top-of- Casing (ft msl)	Depth to Water (ft)	Separate- Phase Hydrocarbon Thickness (ft)	Ground Water Elevation (fl msl)	TDS	TPH-G	TPH-D	B -parts per billic	T on (μg/L)	E	x
	08/10/89°		10.58		2.01		900	2,300	230	16	6.9	65
	11/11/89		9.84	~==	2.75		2,800	2,800	200	15	8.6	58
	02/21/94		9.26		3.33		700	1.800 ^f	200	< 5	<5	45
	05/16/94		9.62		2.97		650	1,700	180	2.5	< 2.5	21
	08/08/94		10.32		2.27		470	2,600 ⁱ	12	1.5	0.5	14
	11/09/94°		San Artist	e e e e e e e e e e		. júlia - 1.				10 (10 177 11 1 11 1	44	
S-14	11/16/85	12.69					<250	400	3	<2	<2	< 5
	01/03/86						<250		3	2	<2	< 5
	04/22/87						1,200	18,000	7.4	2.7	15	110
	07/07/87		10.32		2.37		190		6.5	0.6	1.9	26
	10/10/87		10.77		1.92		4,900	21,000	7	1.2	< 0.5	25
	02/11/88		10.4		2.29		370	12,000°	4.6	< 2.5	<2.5	26
	05/10/88		9.66		3.03		660	$2,200^{d}$	2.9	< 2.5	< 2.5	24
	08/31/88		10.74		1.95		700	7,900	3.2	< 2.5	< 2.5	15
	12/03/88		10.69		2.00		210	$11,000^{d}$	< 0.5	< 0.5	0.8	6.8
	02/16/89		9.69		3.00		130°	5,700 ^d	< 0.5	< 0.5	< 0.5	4.4
	05/28/89		10.42		2,27		770	5,200	< 0.5	< 0.5	< 0.5	4.5
	08/10/89		10.54		2.15		920	8,800	<1	<1	1.6	17
	11/11/89		9.91		2.78		710	28,000	20	57	25	69
	02/21/94		9.3		3.09		2,800	3,600	< 5	<5	<5	14
	02/21/94		9.30		3.39		2,300 ^f	$3,600^{8}$	< 5.0	<5	<5	14
	05/16/94		9.54		3.15		310	6,700	< 2.5	< 2.5	< 2.5	3.1
	08/08/94		10.29		2.4		480 ^k	$2,900^{1}$	< 0.5	0.6	< 0.5	0.8
	08/08/94 ^{dup}		10.29		2.4		590 ^k	2,900 ¹	< 0.5	0.6	< 0.5	1.5
	11/09/94		9.52		3.07		170 ^k	6,400 ^t	0.7	<0.5		2.7
Trip	02/21/94						< 50		< 0.5	< 0.5	<0.5	< 0.5
Blank	02/24/94				= town		< 50		< 0.5	<0.5	< 0.5	< 0.5
	05/16/94						< 50		< 0.5	< 0.5	<0.5	< 0.5






Table 1. Ground Water Elevations and Analytic Results - Shell Service Station WIC# 204-2495-0101, 1800 Powell Street, Emeryville, California (continued)

Well ID	Sampling Date	Top-of- Casing (ft msl)	Depth to Water (ft)	Separate- Phase Hydrocarbon Thickness (ft)	Ground Water Elevation (ft msl)	TDS	ТРН-G	ТРН-D	B arts per billion (Τ [μg/L}	E :	x
	08/08/94 11/09/94					. 9726 - 2 9	<50 <50		<0.5 <0.5	<0.5 < 0.5	<0.5 < 0.5	<0.5 < 0.5
DTSC MCLs						*	NE	NE	1	100°	680	1,750

Abbreviations:

ft msl = Feet above mean sea level

TPH·G = Total petroleum hydrocarbons as gasoline by Modified EPA Method 8015

TPH-D = Total petroleum hydrocarbons as diesel by Modified EPA Method 8015

B = Benzene by EPA Method 8020

T = Toluene by EPA Method 8020

E = Ethylbenzene by EPA Method 8020

X = Xylenes by EPA Method 8020

NE = Not established

DTSC MCLs = California Department of Toxic Substances Control maximum contaminant levels for drinking water

< n = Not detected at detection limits of n ppb

dup = Duplicate sample

SPH = Separate-phase hydrocarbons present, often unable to measure thickness accurately


-- = Not analyzed/not measured

Notes:

- a = Well inaccessible
- b = Well abandoned on 11/09/85
- c = DTSC recommended action level; MCL not established
- d = Compounds detected within the chromatographic range appear to be weathered diesel
- e = Compounds detected within the chromatographic range of gasoline but not characteristic of the standard gasoline pattern.
- f = The concentrations reported as gasoline for samples S-12 and S-14 are primarily due to the presence of a discrete peak
- g = The concentrations reported as diesel for samples S-12, S-13 and S-14 are due to the presence of a combination of diesel and a heavier petroleum product of hydrocarbon range C18 - C36, possibly motor oil
- h = The result for gasoline is an unknown hydrocarbon which consists of several peaks
- i = The positive result appears to be a heavier hydrocarbon than diesel
- = Compounds detected within the chromatographic range of diesel appears to include gasoline compounds.
- k = The positive result appears to be a heavier hydrocarbon than gasoline
- l = Maximum concentration suitable for domestic water supply as defined by Regional Water Quality Control Board Resolution #89-39

ATTACHMENT A

GROUND WATER MONITORING REPORT AND ANALYTIC REPORT



BLAINE TECH SERVICES INC.

985 TIMOTHY DRIVE SAN JOSE, CA 95133 (408) 995-5535 FAX (408) 293-8773

November 30, 1994

Shell Oil Company P.O. Box 4023 Concord, CA 94524

Attn: Daniel T. Kirk

SITE: Shell WIC #204-2495-0101 1800 Powell Street Emeryville, California

QUARTER: 4th quarter of 1994

QUARTERLY GROUNDWATER SAMPLING REPORT 941109-M-2

This report contains data collected during routine inspection, gauging and sampling of groundwater monitoring wells performed by Blaine Tech Services, Inc. in response to the request of the consultant who is overseeing work at this site on behalf of our mutual client, Shell Oil Company. Data collected in the course of our field work is presented in a TABLE OF WELL GAUGING DATA. The field information was collected during our preliminary gauging and inspection of the wells, the subsequent evacuation of each well prior to sampling, and at the time of sampling.

Measurements taken include the total depth of the well and the depth to water. The surface of water was further inspected for the presence of immiscibles which may be present as a thin film (a sheen on the surface of the water) or as a measurable free product zone (FPZ). At intervals during the evacuation phase, the purge water was monitored with instruments that measure electrical conductivity (EC), potential hydrogen (pH), temperature (degrees Fahrenheit), and turbidity (NTU). In the interest of simplicity, fundamental information is tabulated here, while the bulk of the information is turned over directly to the consultant who is making professional interpretations and evaluations of the conditions at the site.

STANDARD PROCEDURES

Evacuation

Groundwater wells are thoroughly purged before sampling to insure that the sample is collected from water that has been newly drawn into the well from the surrounding geologic formation. The selection of equipment to evacuate each well is based on the physical characteristics of the well and what is known about the performance of the formation in which the well has been installed. There are several suitable devices which can be used for evacuation. The most commonly employed devices are air or gas actuated pumps, electric submersible pumps, and hand or mechanically actuated bailers. Our personnel frequently employ USGS/Middleburg positive displacement pumps or similar air actuated pumps which do not agitate the water standing in the well.

Normal evacuation removes three case volumes of water from the well. More than three case volumes of water are removed in cases where more evacuation is needed to achieve stabilization of water parameters and when requested by the local implementing agency. Less water may be obtained in cases where the well dewaters and does not recharge to 80% of its original volume within two hours and any additional time our personnel have reason to remain at the site. In such cases, our personnel return to the site within twenty four hours and collect sample material from the water which has recharged into the well case.

Decontamination

All apparatus is brought to the site in clean and serviceable condition. The equipment is decontaminated after each use and before leaving the site. Effluent water from purging and on-site equipment cleaning is collected and transported to Shell's Martinez Manufacturing Complex in Martinez, California

Free Product Skimmer

The column headed, VOLUME OF IMMISCIBLES REMOVED (ml) is included in the TABLE OF WELL GAUGING DATA to cover situations where a free product skimming device must be removed from the well prior to gauging. Skimmers are installed in wells with a free product zone on the surface of the water. The skimmer is a free product recovery device which often prevents normal well gauging and free product zone measurements. The 2.0" and 3.0" PetroTraps fall into the category of devices that obstruct normal gauging. In cases where the consultant elects to have our personnel pull the skimmers out of the well and gauge the well, our personnel perform the additional task of draining the accumulated free product out of the PetroTrap before putting it back in the well. This

recovered free product is measured and logged in the VOLUME OF IMMISCIBLES REMOVED column. Gauging at such sites is performed in accordance with specific directions from the professional consulting firm overseeing work at the site on Shell's behalf.

Sample Containers

Sample material is collected in specially prepared containers which are provided by the laboratory that performs the analyses.

Sampling

Sample material is collected in stainless steel bailer type devices normally fitted with both a top and a bottom check valve. Water is promptly decanted into new sample containers in a manner which reduces the loss of volatile constituents and follows the applicable EPA standard for handling volatile organic and semi-volatile compounds.

Following collection, samples are promptly placed in an ice chest containing prefrozen blocks of an inert ice substitute such as Blue Ice or Super Ice. The samples are maintained in either an ice chest or a refrigerator until delivered into the custody of the laboratory.

Sample Designations

All sample containers are identified with a site designation and a discrete sample identification number specific to that particular groundwater well. Additional standard notations (e.g. time, date, sampler) are also made on the label.

Chain of Custody

Samples are continuously maintained in an appropriate cooled container while in our custody and until delivered to the laboratory under a standard Shell Oil Company chain of custody. If the samples are taken charge of by a different party (such as another person from our office, a courier, etc.) prior to being delivered to the laboratory, appropriate release and acceptance records are made on the chain of custody (time, date, and signature of the person releasing the samples followed by the time, date and signature of the person accepting custody of the samples).

Hazardous Materials Testing Laboratory

The samples obtained at this site were delivered to National Environmental Testing, Inc. in Santa Rosa, California. NET is a California Department of Health Services certified Hazardous Materials Testing Laboratory and is listed as DOHS HMTL #178.

Objective Information Collection

Blaine Tech Services, Inc. performs specialized environmental sampling and documentation as an independent third party. In order to avoid compromising the objectivity necessary for the proper and disinterested performance of this work, Blaine Tech Services, Inc. performs no consulting and does not become involved in the marketing or installation of remedial systems of any kind. Blaine Tech Services, Inc. is concerned only with the generation of objective information, not with the use of that information to support evaluations and recommendations concerning the environmental condition of the site. Even the straightforward interpretation of objective analytical data is better performed by interested regulatory agencies, and those engineers and geologists who are engaged in the work of providing professional opinions about the site and proposals to perform additional investigation or design remedial systems.

Reportage

Submission of this report and the attached laboratory report to interested regulatory agencies is handled by the consultant in charge of the project. Any professional evaluations or recommendations will be made by the consultant under separate cover.

Please call if we can be of any further assistance.

Richard C. Blaine

RCB/lp

attachments: table of well gauging data

chain of custody

certified analytical report

cc: Weiss Associates

5500 Shellmound Street Emeryville, CA 94608-2411 ATTN: Michael Asport

TABLE OF WELL GAUGING DATA

WELL 1.D.	DATA COLLECTION DATE	MEASUREMENT REFERENCED TO	QUALITATIVE OBSERVATIONS	DEPTH TO FIRST IMMISCIBLES LIQUID (FPZ)	THICKNESS OF IMMISCIBLES LIQUID ZONE	VOLUME OF IMMISCIBLES REMOVED	DEPTH TO WATER	DEPTH TO WELL BOTTOM
			(sheen)	(feet)	(feet)	(ml)	(feet)	(feet)
S-5 *	11/9/94	TOB	ODOR	NONE			8.32	12.38
S-8	11/9/94	TOB	ODOR	NONE	_		9.58	18.66
S-9	11/9/94	TOB	FREE PRODUCT					
S-10	11/9/94	TOB		NONE			6.68	19.62
S-12	11/9/94	TOB	ODOR	NONE			7.56	24.24
S-13	11/9/94	INACCESSIBLE						
S-14	11/9/94	TOB		NONE		-	9.52	23.74

^{*} Sample DUP was a duplicate sample taken from well \$-5.

SHELL OIL COMPANY CHAIN OF CUSTODY RECORD Sorial No: 941107-112 Dalo: RETAIL ENVIRONMENTAL ENGINEERING - WEST Paga / of Silo Addross: 1800 Powell Street, Emeryville Analysis Regulred LAB: NET WICK: 204-2495-0101 CHECK OHE (I) FOX OHLY CIVE TURN AROUND BULL Sholl Engineer: Chateth Moveous X 111 Phono No.: (510) 675-6168 Fax #: 675-6160 24 hours 📋 Dan Kirk Acido Marchardia LH. 44 hours 📋 Consultant Namo & Addross: Blaine Tech Services, Inc. & 57EX 8020 □ 6442 Sall Cloudy/Disposal 16 days XXX(Heimal) 985 Timothy Drive San Jose, CA 95133 6240) Consultant Contact: Phono No.: (408) Closelly/Disposal PH EPA 8015 Mod, Diesel). 10 ATO 795-5535 Fox #: 293-8773 SOX/Ak Roms or Sys. Jim Keller Ü 5442 Combination 17H 8015 HOTE: Nolly Lob ou soon as Passible of 24/44 hm. TAL Commonis: Works tem, of lys, □ HU TPH (EPA 8015 Mod. Preparation Used Test for Disposa Υ.\N Sampled by: Container Siza Composite Printed Name: MILL WYENS Asbestos SAMPLE -MATERIAL CONDITION DESCRIPTION No. of Sample ID Sludge COMMENTS Date \$oll Woler ΑĬŧ conis. 5-5 119 3 X 119 X 4-9 3 X 5 K 11-9 5 X 11-9 3 X 3 11-9 Religguisked by (Hanalure): 1/10/6 Rodalyon (signaluro) Religional By (signature): ime: Qipa Printed blame: Date: /// 0 Dole: \\\\ 11/21): north Relinguished By (Lignature): Printed Name: Dale: Printed Hame: 0,40c Dale: Hare; THE LABORATORY MUSE PROVIDE A COPY OF THIS CHAIN-OF-CUSTODY WITH INVOICE AND RESULTS



Santa Rosa Division 435 Tesconi Circle Santa Rosa, CA 95401

Tel: (707) 526-7200 Fax: (707) 526-9623

Jim Keller Blaine Tech Services 985 Timothy Dr. San Jose, CA 95133 Date: 11/21/1994

NET Client Acct. No: 1821 NET Pacific Job No: 94.05446

Received: 11/11/1994

Client Reference Information

Shell 1800 Powell St. Emeryville/941109-M2

Sample analysis in support of the project referenced above has been completed and results are presented on following pages. Results apply only to the samples analyzed. Reproduction of this report is permitted only in its entirety. Please refer to the enclosed "Key to Abbreviations" for definition of terms. Should you have questions regarding procedures or results, please feel welcome to contact Client Services.

Approved by:

yndy Rydley Project Coordinatør

natør / Opera/lions Manager

Enclosure(s)





Client Acct: 1821 NET Job No: 94.05446 Date: 11/21/1994

ELAP Cert: 1386 Page: 2 of 13

Ref: Shell 1800 Powell St. Emeryville/941109-M2

SAMPLE DESCRIPTION: S-5

Date Taken: 11/09/1994

Time Taken:

NET Sample No: 222354		•						Run
			Reporting			Date	Date	Batch
Parameter	Results	Flags	Limit	Units	Method	Extracted	Analyzed	No.
TPH (Gas/BTXE, Liquid)								
METHOD 5030/M8015							11/17/1994	2315
DILUTION FACTOR*	1						11/16/1994	2306
as Gasoline	1,600		50	ug/L	5030		11/16/1994	2306
Carbon Range:	C5-C14						11/16/1994	2306
METHOD 8020 (GC, Liquid)							11/16/1994	2306
Benzene	220	FF	0.5	ug/L	8020		11/17/1994	2315
Toluene	3.2		0.5	ug/L	8020		11/16/1994	2306
Ethylbenzene	1.8		0.5	ug/L	8020		11/16/1994	2306
Xylenes (Total)	5.0		0.5	ug/L	8020		11/16/1994	2306
SURROGATE RESULTS			•				11/16/1994	2306
Bromofluorobenzene (SURR)	120			% Rec.	5030		11/16/1994	2306

FF : Compound quantitated at a 100% dilution factor.



Client Acct: 1821 NET Job No: 94.05446

Date: 11/21/1994 ELAP Cert: 1386

Page: 3 of 13

Ref: Shell 1800 Powell St. Emeryville/941109-M2

SAMPLE DESCRIPTION: S-8

Date Taken: 11/09/1994

Time Taken:

NET Sample No: 222355								Run
			Reportin	g		Date	Date	Batch
Parameter	Results	Flags	Limit	Units	Method	Extracted	Analyzed	No.
Tot. Dissolved Solids (TFR)	4,600,00	00	10,000	ug/L	160.1		11/15/1994	499
TPH (Gas/BTXE, Liquid)								
METHOD 5030/M8015							11/17/1994	2315
DILUTION FACTOR*	1			•			11/16/1994	2306
as Gasoline	650		50	ug/L	5030		11/16/1994	2306
Carbon Range:	C5-C14						11/16/1994	2306
METHOD 8020 (GC, Liquid)							11/16/1994	2306
Benzene	170	FC	0.5	ug/L	8020		11/17/1994	2315
Toluene	5.3		0.5	ug/L	8020		11/16/1994	2306
Ethylbenzene	ND		0.5	ug/L	8020		11/16/1994	2306
Xylenes (Total)	17		0.5	ug/L	8020		11/16/1994	2306
SURROGATE RESULTS							11/16/1994	2306
Bromofluorobenzene (SURR)	110			% Rec.	5030		11/16/1994	2306

FC : Compound quantitated at a 10% dilution factor.



NET Job No: 94.05446

Date: 11/21/1994

ELAP Cert: 1386 Page: 4 of 13

Ref: Shell 1800 Powell St. Emeryville/941109-M2

SAMPLE DESCRIPTION: S-10

Date Taken: 11/09/1994

Time Taken:

NET Sample No: 222356								Run
			Reportin	ıg		Date	Date	Batch
Parameter	Results	Flags	Limit	Units	Method	Extracted	Analyzed	No.
TPH (Gas/BTXE, Liquid)								
METHOD 5030/M8015							11/17/1994	2315
DILUTION FACTOR*	1						11/16/1994	2306
as Gasoline	640		50	ug/L	5030		11/16/1994	2306
Carbon Range:	C5-C14						11/16/1994	2306
METHOD 8020 (GC, Liquid)							11/16/1994	2306
Benzene	130	FC	0.5	ug/L	8020		11/17/1994	2315
Toluene	2.0		0.5	ug/L	8020		11/16/1994	2306
Ethylbenzene	1.6		0.5	ug/L	8020		11/16/1994	2306
Xylenes (Total)	4.1		0.5	ug/L	B020		11/16/1994	2306
SURROGATE RESULTS							11/16/1994	2306
Bromofluorobenzene (SURR)	107			% Rec.	5030		11/16/1994	2306

FC : Compound quantitated at a 10% dilution factor.



Client Acct: 1821 NET Job No: 94.05446 Date: 11/21/1994 ELAP Cert: 1386

Page: 5 of 13

Ref: Shell 1800 Powell St. Emeryville/941109-M2

SAMPLE DESCRIPTION: S-12

Date Taken: 11/09/1994

Time Taken:

NET Sample No: 222357								Run
			Reporting			Date	Date	Batch
Parameter	Results	Flags	Limit	Units	Method	Extracted	Analyzed	No.
TPH (Gas/BTXE,Liquid)								
METHOD 5030/M8015							11/16/1994	2306
DILUTION FACTOR*	1						11/16/1994	2306
as Gasoline	80		50	ug/L	5030		11/16/1994	2306
Carbon Range:	C5-C14			•			11/16/1994	2306
METHOD B020 (GC, Liquid)							11/16/1994	2306
Benzene	0.9		0.5	ug/L	8020		11/16/1994	2306
Toluene	ND		0.5	ug/L	8020		11/16/1994	2306
Ethylbenzene	ND		0.5	ug/L	8020		11/16/1994	2306
Xylenes (Total)	0.6		0.5	ug/L	8020		11/16/1994	2306
SURROGATE RESULTS							11/16/1994	2306
Bromofluorobenzene (SURR)	104			% Rec.	5030		11/16/1994	2396
METHOD M8015 (EXT., Liquid)						11/15/1994		
DILUTION FACTOR*	10						11/16/1994	647
as Diesel	5,400	D-	500	ug/L	351C		11/16/1994	847
Carbon Range:	C10-C28+					•	11/16/1994	847

 $[\]ensuremath{\text{D-}}\xspace$: The positive result has an atypical pattern for Diesel analysis.



Client Acct: 1821 NET Job No: 94.05446 Date: 11/21/1994

ELAP Cert: 1386 Page: 6 of 13

Ref: Shell 1800 Powell St. Emeryville/941109-M2

SAMPLE DESCRIPTION: S-14

Date Taken: 11/09/1994

Time Taken:

NET Sample No: 222358

NET Sample No: 222358								Run
			Reporting			Date	Date	Batch
Parameter	Results	Flags	Limit	Units	Method	Extracted	Analyzed	No.
TPH (Gas/BTXE,Liquid)		•						
METHOD 5030/M8015							11/17/1994	2315
DILUTION FACTOR*	1						11/17/1994	2315
as Gasoline	170	GH	50	ug/L	5030		11/17/1994	2315
Carbon Range:	C5-C14						11/17/1994	2315
METHOD 8020 (GC, Liquid)							11/17/1994	2315
Benzene	0.7		0.5	ug/L	8020		11/17/1994	2315
Toluene	ND		0.5	ug/L	8020		11/17/1994	2315
Ethylbenzene	ND		0.5	ug/L	8020		11/17/1994	2315
Xylenes (Total)	2.7		0.5	ug/L	8020		11/17/1994	2315
SURROGATE RESULTS							11/17/1994	2315
Bromofluorobenzene (SURR)	83			% Rec.	5030		11/17/1994	2315
METHOD M8015 (EXT., Liquid)						11/15/1994		
DILUTION FACTOR*	10						11/16/1994	847
as Diesel	6,400	D-	500	ug/L	3510		11/16/1994	847
Carbon Range:	C10-C28+						11/16/1994	847

 $[\]ensuremath{\text{D-}}\xspace$: The positive result has an atypical pattern for Diesel analysis.

 $^{{\}tt GH}$: The positive result appears to be a heavier hydrocarbon than Gasoline.



Client Acct: 1821 NET Job No: 94.05446 Date: 11/21/1994

ELAP Cert: 1386 Page: 7 of 13

Ref: Shell 1800 Powell St. Emeryville/941109-M2

SAMPLE DESCRIPTION: EB

Date Taken: 11/09/1994

Time Taken:

NET Sample No: 222359							Run
		Reporting			Date	Date	Batch
Parameter	Results Flags	Limit	Units	Method	Extracted	Analyzed	No.
TPH (Gas/BTXE,Liquid)							
METHOD 5030/M8015						11/16/1994	2306
DILUTION FACTOR*	1					11/16/1994	2306
as Gasoline	ND	50	ug/L	5030		11/16/1994	2306
Carbon Range:						11/16/1994	2306
METHOD 8020 (GC, Liquid)						11/16/1994	2306
Banzene	ND	0.5	ug/L	8020		11/16/1994	2306
Toluene	ND	.0.5	ug/L	8020		11/16/1994	2306
Ethylbenzene	ND	0.5	ug/L	8020 -		11/16/1994	2306
Xylenes (Total)	ND	0.5	ug/L	8020		11/16/1994	2306
SURROGATE RESULTS						11/16/1994	2305
Bromofluorobenzene (SURR)	106		% Rec.	5030		11/16/1994	2306



NET Job No: 94.05446

Date: 11/21/1994 ELAP Cert: 1386

Page: 8 of 13

Ref: Shell 1800 Powell St. Emeryville/941109-M2

SAMPLE DESCRIPTION: DUP

Date Taken: 11/09/1994

Time Taken:

NET Sample No: 222360								Run
			Reportin	g		Date	Date	Batch
Parameter	Results	Flags	Limit	Units	Method	Extracted	Analyzed	No.
TPH (Gas/BTXE, Liquid)								
METHOD 5030/M8015							11/17/1994	2315
DILUTION FACTOR*	1						11/16/1994	2306
as Gasoline	1,600		50	ug/L	5030		11/16/1994	2306
Carbon Range:	C5-C14						11/16/1994	2306
METHOD 8020 (GC, Liquid)							11/16/1994	2306
Benzene	250	FC	0.5	ug/L	8020		11/17/1994	2315
Toluene	3.3		0.5	ug/L	8020		11/16/1994	2306
Ethylbenzene	1.9		0.5	ug/L	8020		11/16/1994	2306
Xylenes (Total)	5.9		0.5	ug/L	8020		11/16/1994	2306
SURROGATE RESULTS							11/16/1994	2306
Bromofluorobenzene (SURR)	108			% Rec.	5030		11/16/1994	2306

PC : Compound quantitated at a 10% dilution factor.



Client Acct: 1821

NET Job No: 94.05446

Date: 11/21/1994

ELAP Cert: 1386 Page: 9 of 13

Ref: Shell 1800 Powell St. Emeryville/941109-M2

SAMPLE DESCRIPTION: TB

Date Taken: 11/09/1994

Time Taken:

NET Sample No: 222361							Run
		Reporting	•		Date	Date	Batch
Parameter	Results Flags	Limit	Units	Method	Extracted	Analyzed	No.
TPH (Gas/BTXE, Liquid)							
METHOD 5030/M8015						11/16/1994	2306
DILUTION FACTOR*	1					11/16/1994	2306
as Gasoline	ND	50	ug/L	5030		11/16/1994	2306
Carbon Range:						11/16/1994	2306
METHOD 8020 (GC, Liquid)						11/16/1994	2306
Benzene	ЙD	0.5	ug/L	8020		11/16/1994	2306
Toluene	ND	0.5	ug/L	8020		11/16/1994	2306
Ethylbenzene	ND	0.5	ug/L	8020		11/16/1994	2306
Xylenes (Total)	ND	0.5	ug/L	8020		11/16/1994	2306
SURROGATE RESULTS						11/16/1994	2306
Bromofluorobenzene (SURR)	105		% Rec.	5030		11/16/1994	2306



Client Acct: 1821 NET Job No: 94.05446 Date: 11/21/1994

ELAP Cert: 1386 Page: 10 of 13

Ref: Shell 1800 Powell St. Emeryville/941109-M2

CONTINUING CALIBRATION VERIFICATION STANDARD REPORT

		CCV	CCV			
	CCV	Standard	Standard			
	Standard	Amount	Amount		Date	Analyst
Parameter	% Recovery	Pound	Expected	Units	Analyzed	<u>Initials</u>
TPH (Gas/BTXE, Liquid)						
as Gasoline	102.0	1.02	1.00	mg/L	11/16/1994	lss
Benzene	91.6	4.58	5.00	ug/L	11/16/1994	lss
Toluene	90.2	4.51	5.00	ug/L	11/16/1994	lss
Ethylbenzene	94.0	4.70	5.00	ug/L	11/16/1994	lss
Xylenes (Total)	96.7	14.5	15.0	ug/L	11/16/1994	lss
Bromofluorobenzene (SURR)	100.0	100	100	% Rec.	11/16/1994	lss
TPH (Gas/BTXE,Liquid)						
as Gasoline	104.0	1.04	1.00	mg/L	11/17/1994	aal
Benzene	107.8	5.39	5.00	ug/L	11/17/1994	aal
Toluene	89.2	4.46	5.00	ug/L	11/17/1994	aal
Ethylbenzene	100.6	5.03	5.00	ug/L	11/17/1994	aal
Xylenes (Total)	99.3	14.9	15.0	ug/L	11/17/1994	aal
Bromofluorobenzene (SURR)	93.0	93	100	% Rec.	11/17/1994	aal
METHOD M8015 (EXT., Liquid)						
as Diesel	112.0	1120	1000	mg/L	11/16/1994	tts



Client Name:

Blaine Tech Service

lient Acct: 1821

94 05446

ine Tech Services

ELAP Cert: 1386

Page: 11 of 13

Date: 11/21/1994

Ref: Shell 1800 Powell St. Emeryville/941109-M2

METHOD BLANK REPORT

Method

	Blank					
	Amount	Reporting		Date	Analyst	
Parameter	Found	Limit	Units	Analyzed	Initials	
Tot. Dissolved Solids (TFR)	ND	10	mg/L	11/15/1994	shr	
TPH (Gas/BTXE, Liquid)						
as Gasoline	ND	0.05	mg/L	11/16/1994	lss	
Benzene	ND	0.5	ug/L	11/16/1994	lss	
Toluene	ND	0.5	ug/L	11/16/1994	lss	
Ethylbenzene	ND	0.5	ug/L	11/16/1994	lss	
Xylenes (Total)	ND	0,5	ug/L	11/16/1994	lss	
Bromofluorobenzene (SURR)	99		% Rec.	11/16/1994	lss	
TPH (Gas/BTXE, Liquid)						
as Gasoline	ND	0.05	mg/L	11/17/1994	aal	
Benzene	ND	0.5	ug/L	11/17/1994	aal	
Toluene	ND	0.5	ug/L	11/17/1994	aal	
Ethylbenzene	ND	0.5	ug/L	11/17/1994	aal	
Xylenes (Total)	ND	0.5	ug/L	11/17/1994	aal	
Bromofluorobenzene (SURR)	90		% Rec.	11/17/1994	aal	
METHOD M8015 (EXT., Liquid)						
as Diesel	ND	0.05	mg/L	11/16/1994	tts	



Client Name: Blaine Tech

Client Acct: 1821

t: 1821

Date: 11/21/1994 ELAP Cert: 1386 Page: 12 of 13

Ref: Shell 1800 Powell St. Emeryville/941109-M2

MATRIX SPIKE / MATRIX SPIKE DUPLICATE

+		Matrix					Matrix			
	Matrix	Spike				Matrix	Spike			
	Spike	Dup		Spike	Sample	Spike	Dup.		Date	Analyst
Parameter	% Rec.	% Rec.	RPD	Amount	Conc	Солс.	Conc.	Units	Analyzed	Initials
TPH (Gas/BTXE,Liquid)										
as Gasoline	99.0	94.0	5.2	1.00	ND	0.99	0.94	mg/L	11/16/1994	lss
Benzene	96.7	88.5	8.9	20.9	ND	20.2	18.5	ug/L	11/16/1994	lss
Toluene	96.3	86.8	10.4	87.6	ND	84.4	76.0	ug/L	11/16/1994	lss
TPH (Gas/BTXE, Liquid)										
as Gasoline	107.0	96.0	10.7	1.00	ND	1.07	0.96	mg/L	11/17/1994	aal
Benzene	101.9	93.2	8.8	20.7	ND	21.1	19.3	ug/L	11/17/1994	aal
Toluene	106.5	97.4	8.8	84.5	ND	90.0	82.3	ug/L	11/17/1994	aal
METHOD M8015 (EXT., Liquid)										
as Diesel	100.0	96.5	3.5	2.00	ND	2.00	1.93	mg/L	11/15/1994	tts



Client Name: Blaine Tech

Client Acct: 1821

ET Job No: 94,05446

Date: 11/21/1994

ELAP Cert: 1386

Page: 13 of 13

Ref: Shell 1800 Powell St. Emeryville/941109-M2

LABORATORY CONTROL SAMPLE REPORT

		LCS	LCS			
	LCS	Amount	Amount		Date	Analyst
Parameter	% Recovery RPD	Found	Expected	Units	Analyzed	<u> Initials</u>
Tot. Dissolved Solids (TFR)	101.5	1,015	1000	mg/L	11/15/1994	shr
METHOD M8015 (EXT., Liquid)						
as Diesel	63.0	0.630	1.00	mg/L	11/16/1994	tts



KEY TO ABBREVIATIONS and METHOD REFERENCES

: Less than; When appearing in results column indicates analyte not detected at the value following. This datum supercedes the listed Reporting Limit.

Reporting Limits are a function of the dilution factor for any given sample. Actual reporting limits and results have been multiplied by the listed dilution factor. Do not multiply the reporting limits or reported values by the dilution factor.

dw : Result expressed as dry weight.

mean : Average; sum of measurements divided by number of measurements.

mg/Kg (ppm) : Concentration in units of milligrams of analyte per kilogram of

sample, wet-weight basis (parts per million).

mg/L : Concentration in units of milligrams of analyte per liter of sample.

mL/L/hr : Milliliters per liter per hour.

MPN/100 mL : Most probable number of bacteria per one hundred milliliters of sample.

N/A : Not applicable.

NA : Not analyzed.

ND : Not detected; the analyte concentration is less than the applicable

listed reporting limit.

NTU : Nephelometric turbidity units.

RPD : Relative percent difference, 100 [Value 1 - Value 2]/mean value.

SNA : Standard not available.

ug/Kg (ppb) : Concentration in units of micrograms of analyte per kilogram of sample,

wet-weight basis (parts per billion).

ug/L : Concentration in units of micrograms of analyte per liter of sample.

umhos/cm : Micromhos per centimeter.

Method References

Methods 100 through 493: see "Methods for Chemical Analysis of Water & Wastes", U.S. EPA, 600/4-79-020, Rev. 1983.

Methods 601 through 625: see "Guidelines Establishing Test Procedures for the Analysis of Pollutants" U.S. EPA, 40 CFR, Part 136, Rev. 1988.

Methods 1000 through 9999: see "Test Methods for Evaluating Solid
Waste", U.S. EPA SW-846, 3rd edition, 1986., Rev. 1, December 1987.

 \underline{SM} : see "Standard Methods for the Examination of Water & Wastewater, 17th Edition, APHA, 1989.

Revised September, 1993 abb.93

COOLER RECEIPT FORM

Project: 941101-M2	Log No:
Cooler received on: \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	checked on ///// why has
	(signature)
	(VIII)
Were custody papers present?	YES NO
Were custody papers properly fill	led out?YES NO
Were the custody papers signed?	YES NO
Was sufficient ice used?	YES) NO TELW!, O
Did all bottles arrive in good co	ondition (unbroken)?YES NO
Did bottle labels match COC?	YES NO
Were proper bottles used for ana	lysis indicated?(ES) NO
Correct preservatives used?	(YES) NO
VOA vials checked for headspace Note which voas (if any)	bubbles?YES NO had bubbles:*
Sample descriptor:	Number of vials:
	-
*All VOAs with headspace bubbles used for analysis	have been set aside so they will not beYES NO
List here all other jobs receive	d in the same cooler:
Client Job #	NET log #
·	•
	· · ·
	

(coolerrec)