00 MAY 26 PM 4: 55

May 24, 2000

REPORT
for
SOIL AND GROUNDWATER ASSESSMENT
at
Compare Prices Service Station
2844 Mountain Boulevard
Oakland, California

Submitted by: AQUA SCIENCE ENGINEERS, INC. 208 West El Pintado Danville, CA 94526 (925) 820-9391

1.0 INTRODUCTION

This report presents the methods and findings of Aqua Science Engineers, Inc. (ASE)'s soil and groundwater assessment at the Compare Prices Service Station located at 2844 Mountain Boulevard in Oakland, California (Figure 1). This site was formally Desert Petroleum Station #796. The proposed site assessment activities were initiated by Mr. Shahram Shahnazi, property owner, as required by the Alameda County Health Care Services Agency (ACHCSA) in their letters dated June 10, 1999, October 29, 1999 and February 9, 2000 (Appendix A).

2.0 SITE BACKGROUND

Soil contamination was initially identified at the site in March 1989, during the replacement of the product lines by Diablo Tank and Equipment. Up to 8,400 parts per million (ppm) total petroleum hydrocarbons as gasoline (TPH-G) were identified in soil samples collected from the southern edge of the underground storage tanks (USTs).

In July 1989, On-site Technologies excavated and disposed of contaminated soil from the southern end of the premium unleaded tank. Up to 3,300 ppm TPH-G were collected from the sidewalls of the excavation.

In May 1990, Remediation Service International (RSI) conducted a soil and groundwater assessment at the site which included the installation of four groundwater monitoring wells (RS-1 through RS-4). Hydrocarbons were detected in both soil and groundwater during this assessment.

In June 1991, soil remediation began at the site using soil vapor extraction (SVE). In October 1991, groundwater remediation began at the site using RSI's S.A.V.E. system. Remediation was suspended in 1992 apparently due to Desert Petroleum's financial problems.

The site has been monitored on a quarterly basis since May 1990. Beginning in 1995, hydrocarbon concentrations started to rise and free-floating hydrocarbons appeared in monitoring well MW-1. Between October and December 1996, 30.4 gallons of gasoline and 1,077 gallons of contaminated groundwater were removed from monitoring well RS-1 during interim free-product removal.

In March 1999, Western Geo-Engineers of Woodland, California prepared a quarterly groundwater monitoring report and subsurface conduit study

for the site. This subsurface conduit study identified a sewer line with its bottom below the typical depth to groundwater at the site. This sewer line could potentially act as a conduit for the migration of groundwater contamination.

3.0 SCOPE OF WORK (SOW)

ASE's scope of work was to further delineate the extent of soil and groundwater contamination off-site. To accomplish this task, ASE prepared the following scope of work:

- 1) Prepare a workplan and health and safety plan for approval by the ACHCSA.
- 2) Contract with an underground utility contractor to accurately mark the underground utility lines in Mountain Boulevard.
- 3) Obtain an excavation permit from the City of Oakland to drill in the street areas and prepare a traffic plan to allow for closing traffic lanes during drilling activities.
- 4) Obtain a drilling permit from the Alameda County Public Works Agency (ACPWA).
- 5) Drill thirteen (13) soil borings with a Geoprobe drill rig in the locations shown on Figure 2. Collect soil samples continuously and screen the soil samples for volatile compounds with an organic vapor meter (OVM). Groundwater samples will also be collected from each boring.
- 6) Analyze one soil sample from each boring, as well as the groundwater sample collected from each boring, at a CAL-EPA certified analytical laboratory for total petroleum hydrocarbons (TPH-G) by modified EPA Method 5030/8015 and benzene, toluene, ethyl benzene and total xylenes (BTEX) and methyl tertiary butyl ether (MTBE) by EPA Method 8020.
- 7) Backfill the borings with neat cement.
- 8) Prepare a report outlining the methods and findings of this assessment.

At the request of the ACHCSA, the borings on the west side of Mountain Boulevard were drilled as soon as they could be scheduled (January 2000). The other borings were drilled in the spring when groundwater was at its highest elevation. Two additional borings were added at the request of the ACHCSA to ASE's original scope of work which called for 11 borings. These two additional borings were added to further define the extent of contamination south of boring BH-A across Mountain Boulevard from the site.

4.0 UNDERGROUND UTILITY LOCATING

On January 7, 2000, Subtronics Corporation of Concord, California accurately located the public utilities around the proposed drilling locations (Figure 2). They also accurately located the lines that could potentially act as a conduit for groundwater contamination. Several lines were inaccurately located in the Western Geo-Engineers report. Underground Service Alert (USA) was also notified at least 48 hours prior to each drilling event. An updated map of the utility line locations is provided as Figure 2.

5.0 DRILL SOIL BORINGS AND COLLECT SAMPLES

5.1 Permits

Prior to drilling, ASE obtained a drilling permit from the Alameda County Public Works Agency (ACPWA). ASE also obtained excavation permits from the City of Oakland. Copies of these permits are presented in Appendix B.

5.2 Drilling and Soil Sampling

On January 7, 2000, Vironex, Inc. of Hayward, California drilled soil borings BH-A through BH-D at the site using a Geoprobe hydraulic sampling rig (Figure 2). Borings BH-E through BH-M were drilled by Vironex, Inc. on April 18 and 19, 2000. The drilling was directed by ASE associate geologist Ian Reed. Traffic safety for the lane closure was provided by Flash Safety of Oakland, California.

Undisturbed soil samples were collected continuously as drilling progressed for lithologic and hydrogeologic description and for possible analysis. The samples were collected by driving a sampler lined with acetate tubes using hydraulic direct push methods. Selective soil samples were immediately trimmed, sealed with Teflon tape, plastic end caps and

tape, labeled, sealed in plastic bags and stored on ice for transport to Chromalab, Inc. of Pleasanton, California (ELAP #1094) under chain of custody. Soil from the remaining tubes was described by the site geologist using the Unified Soil Classification System and was screened for volatile compounds using an Organic Vapor Meter (OVM). The soil was screened by emptying soil from one of the sample tubes into a plastic bag. The bag was then sealed and placed in the sun for approximately 10 minutes. After the volatile compounds were allowed to volatilize, the OVM measured the vapor in the bag through a small hole punched in the bag. OVM readings are used as a screening tool only, since the procedures are not as rigorous as those used in the laboratory. OVM readings can be found on the boring logs located in Appendix C.

5.3 Groundwater Sampling

Groundwater samples were removed from the borings with bailers. The groundwater samples were contained in 40-ml volatile organic analysis (VOA) vials (pre-preserved with hydrochloric acid) and sealed without headspace. The samples were then labeled and stored on ice for transport to Chromalab under chain of custody.

5.4 Backfilling and Decontamination

Upon completion of the soil and groundwater sampling, the borings were backfilled with neat cement to the ground surface.

Drilling equipment was cleaned with a TSP solution between sampling intervals and between borings to prevent potential cross-contamination.

5.5 Subsurface lithology

Sediments encountered during drilling generally consisted of sandy and clayey silts beneath the surface to the total depth explored of 40-feet below ground surface (bgs). Groundwater was encountered at approximately 20-feet bgs in the locations across Mountain Boulevard from the site and at approximately 12-feet bgs in the borings adjacent to the sewer lines along Mountain Boulevard and Werner Court. Sandy sediments were present in many of the borings near the sewer line, most likely indicating fill material. Boring logs are presented as Appendix C.

6.0 ANALYTICAL RESULTS FOR SOIL

Soil samples collected from 10-feet bgs in borings BH-J and BH-K, 11.5-feet bgs in borings BH-G, BH-H, BH-L and BH-M, 15.5-feet bgs in boring BH-I, 18.0-feet bgs in boring BH-E, 19.0-feet bgs in borings BH-A, BH-D and BH-F, 20-feet bgs in boring BH-C and 21-feet bgs in boring BH-B were analyzed by Chromalab for TPH-G by modified EPA Method 5030/8015, and BTEX and MTBE by EPA Method 8020. These samples represent either the capillary zone or the unsaturated soil sample that appeared the most contaminated based on odor, staining, and/or OVM readings. The analytical results are tabulated in Table One and the certified analytical report and chain of custody forms are included in Appendix D.

The soil samples collected from boring BH-A contained 620 ppm TPH-G, 3.4 ppm ethyl benzene and 14 ppm total xylenes. No MTBE was detected in this soil sample. The soil samples analyzed from borings BH-G, BH-J and BH-K, all located along the sewer line adjacent to the site, contained TPH-G concentrations ranging from 16 ppm to 730 ppm and MTBE ranging from 20 ppm to 35 ppm. The soil sample concentrations analyzed from boring BH-K also contained 14 ppm ethyl benzene and 79 ppm total xylenes. All of the other soil samples analyzed contained very low to non-detectable concentrations of hydrocarbons concentrations less than 10 ppm, and BTEX and MTBE concentrations None of the BTEX concentrations detected at the site below 0.5 ppm. exceeded United States Environmental Protection Agency (US EPA) Region IX preliminary remediation goals (PRGs) for residential soil.

7.0 ANALYTICAL RESULTS FOR GROUNDWATER

The groundwater samples were analyzed by Chromalab for TPH-G by modified EPA Method 5030/8015, and BTEX and MTBE by EPA Method 8020. When detected, the presence of MTBE was confirmed using EPA Method 8260, although MTBE concentrations were not quantified. The analytical results are tabulated in Table Two, and the certified analytical report and chain of custody forms are included in Appendix E. TPH-G, benzene and MTBE isoconcentration contour maps are included as Figures 3, 4 and 5, respectively.

TPH-G was detected in groundwater samples collected from borings BH-A and BH-E at 15,000 parts per billion (ppb). TPH-G was also detected in groundwater samples collected from borings BH-H, BH-I and BH-L at 960 ppb, 130 ppb and 120 ppb, respectively, although the laboratory noted that the TPH-G concentrations in groundwater samples collected from

borings BH-I and BH-L did not have typical gasoline chromatogram patterns. Benzene was detected in groundwater samples collected from borings BH-A, BH-E, BH-H and BH-K at 370 ppb, 260 ppb, 12 ppb and 6,400 ppb, respectively. Toluene was detected in groundwater samples collected from borings BH-A, BH-B, BH-E and BH-H at concentrations ranging from 2.3 ppb to 780 ppb, and total xylenes were detected in these same borings at concentrations ranging from 23 ppb to 4,600 ppb. Ethyl benzene was detected in groundwater samples collected from borings BH-A, BH-E and BH-H at concentrations ranging from 40 ppb to 890 ppb. Very high MTBE concentrations of 130,000 ppb, 170,000 ppb and 410,000 ppb were detected in groundwater samples collected from borings BH-G, BH-J and BH-K, respectively. MTBE concentrations in groundwater samples collected from borings BH-G, BH-J and BH-K, respectively. MTBE concentrations in groundwater samples collected from borings BH-A, BH-B, BH-C, BH-H, BH-I and BH-L ranged from 33 ppb to 660 ppb.

8.0 CONCLUSIONS

Very high MTBE concentrations (over 100,000 ppb) were detected in groundwater samples collected from borings BH-G, BH-J and BH-K, all of which are located close to the corner of Mountain Boulevard and Werner Groundwater samples collected from boring BH-I along the Mountain Boulevard sidewalk north of Werner Court, BH-H east of boring BH-G in Werner Court, BH-L south of boring BH-K along the Mountain and borings BH-C and BH-B across Mountain sidewalk. Boulevard, all contained MTBE concentrations ranging from 110 ppb to Groundwater samples collected from boring BH-A, across Mountain Boulevard from the site and south of boring BH-B contained 33 ppb MTBE. No MTBE was detected in groundwater samples collected from borings BH-E and BH-F south of boring BH-A across Mountain Boulevard, and boring BH-M, south of boring MW-L along the Mountain Boulevard These borings define the extent of MTBE south of the site along both sides of Mountain Boulevard. In addition, no MTBE was detected in groundwater samples collected from boring BH-D north of boring BH-C This boring defines the extent of MTBE across Mountain Boulevard. contamination across Mountain Boulevard to the north.

The highest benzene concentration (6,400 ppb) was in boring BH-K, in the sidewalk adjacent to the site. The only other two borings which contained benzene concentrations over 100 ppb were borings BH-A and BH-E across Mountain Boulevard from the site. These two borings contained 370 ppb and 260 ppb, respectively. Groundwater samples collected from boring BH-H, the eastern most boring in Werner Court, contained a benzene concentration of 12 ppb, which exceeds the California Department of

Health Services (DHS) maximum contaminant level (MCL) for drinking water. Ethyl benzene, xylenes and/or toluene concentrations exceeded DHS MCLs for drinking water in the groundwater samples collected from borings BH-A and BH-E, across Mountain Boulevard to the west.

In summary, elevated hydrocarbon concentrations, including benzene and MTBE, were detected in groundwater samples collected from borings located near the intersection of Warner Court and Mountain Boulevard. As shown on Figures 3, 4 and 5, these elevated concentrations extend west across Mountain Boulevard to a retaining wall which separates Mountain Boulevard and Highway 13 below. This retaining wall acts as a barrier for The extent of hydrocarbons has been groundwater movement to the west. defined to both the north and south of the site on the western side of Mountain Boulevard, and to the south on the eastern side of Mountain The extent of contamination has not been defined to nondetectable to the east on Werner Court and to the north on the eastern However, groundwater samples collected side of Mountain Boulevard. from the borings furthest from the site in these directions have shown a significant decrease in concentrations, and the plume likely does not extend much further from these borings.

It does not appear, based on the distribution of hydrocarbons in groundwater, the depth to groundwater in the borings, and the lithology in the borings, that the subsurface utility lines act as a significant conduit for the movement of contaminants in groundwater at the site, particularly along Mountain Boulevard. It is possible the storm water line that crosses Mountain Boulevard and continues to the south across Highway 13 may act as a conduit since it is deeper on the west side of Mountain Boulevard than the other utility lines in the site vicinity, but it will be difficult to assess the impact of this line since it crosses Highway 13 immediately and drilling will not be possible in the highway area. In addition, the utility lines adjacent to the site may provide a recharge source for groundwater at the site since groundwater was at a shallower depth in borings near the sewer line.

9.0 RECOMMENDATION

ASE recommends that five additional groundwater monitoring wells be installed at the site to monitor the seasonal variations hydrocarbon concentrations in the areas of the site that have the highest dissolved hydrocarbon concentrations, and in downgradient off-site areas to monitor the seasonal variations in hydrocarbon concentrations across Mountain Boulevard. ASE recommends the following placement of these

new wells: One on-site near the corner of Werner Court and Mountain Boulevard, one on-site near boring BH-K, and three across Mountain Boulevard (near borings BH-C, BH-A and BH-F) which will allow the continued monitoring of the downgradient center of the plume as well as its lateral extent to the north and south along Mountain Boulevard.

ASE anticipates that the ACHCSA will require further groundwater remediation at the site. Free-floating hydrocarbons should be removed from the existing site monitoring wells. This could be accomplished by biweekly bailing, and possibly a skimmer if the free-floating hydrocarbon thickness does not decrease using bailing alone.

In addition to the removal of free-floating hydrocarbons, ASE also anticipates that remediation will be required to reduce dissolved hydrocarbon concentrations in on-site areas. As the February 3, 1995 "Corrective Action Plan" prepared by Remediation Services International (RSI) eludes to, the low permeability nature of the sediments beneath the site will decrease the effectiveness of all of the available remediation technologies currently in widespread use. However, given the available options, ASE suggests that the injection of Oxygen Releasing Compound (ORC) into groundwater in closely spaced borings in the affected area might be a cost effective means of groundwater remediation at the site.

10.0 REPORT LIMITATIONS

The results of this assessment represent conditions at the time of the soil and groundwater sampling, at the specific locations where the samples were collected, and for the specific parameters analyzed by the laboratory.

This report does not fully characterize the site for contamination resulting from unknown sources or for parameters not analyzed by the laboratory. All of the laboratory work cited in this report was prepared under the direction of an independent CAL-EPA certified laboratory. The independent laboratory is solely responsible for the contents and conclusions of the chemical analysis data.

Aqua Science Engineers appreciates the opportunity provide environmental consulting services for this project. Should you have any questions or comments, please feel free to call us at (925) 820-9391.

Respectfully submitted,

AQUA SCIENCE ENGINEERS, INC.

Robert E. Kitay, R.G., R.E.A.

Senior Geologist

Attachments: Figures 1 through 5


Appendices A through E


cc: Mr. Shahram Shahnazi


Mr. Scott Seery, Alameda County Health Care Services Agency, 1131 Harbor Bay Parkway, Suite 250, Alameda, CA 94502


Na. 6586

Mr. Chuck Headlee, California Regional Water Quality Control Board, San Francisco Bay Region, 1515 Clay Street, Suite 1400, Oakland, CA 94612












TABLE ONE
Summary of Chemical Analysis of SOIL Samples
Petroleum Hydrocarbons
All results are in parts per million

Boring	Depth	TPH- Gasoline	Benzene	Toluene	Ethyl Benzene	Total Xylenes	MTBE
вн-а	19.0'	620*	< 0.62	< 0.62	3.4	1 4	< 0.62
вн-в	21.0'	< 1.0	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005
вн-с	20.0'	< 1.0	< 0.005	< 0.005	< 0.005	< 0.005	0.2
вн-р	19.0'	< 1.0	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005
вн-Е	18.0'	< 10	< 0.62	< 0.62	< 0.62	< 0.62	< 0.62
BH-F	19.0'	< 1.0	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005
вн-G	11.5	16*	< 0.62	< 0.62	< 0.62	< 0.62	2 0
вн-н	11.5'	8.5	0.13	< 0.005	0.14	0.15	0.065
BH-I	15.5'	< 1.0	< 0.005	< 0.005	< 0.005	< 0.005	0.019
вн-Ј	10.0	230*	< 1.2	< 1.2	< 1.2	< 1.2	3 5
вн-к	10.0'	730	< 3.1	< 3.1	1 4	79	2 0
BH-L	11.5'	2.1*	< 0.005	< 0.005	< 0.005	< 0.005	0.014
вн-м	11.5'	< 1.0	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005
PRG		NE	0.62	520	230	210	NE

Notes:

Detectable concentrations are in bold.

Non-detectable concentrations are noted by the less than sign (<) followed by the detection limit.

PRG = United States Environmental Protection Agency Region IX Preliminary Remediation Goal for Residential Soil.

NE = PRG has not been established.

^{* =} Hydrocarbons do not match the laboratory gasoline standard

TABLE TWO
Summary of Chemical Analysis of GROUNDWATER Samples
Petroleum Hydrocarbons
All results are in parts per billion

Boring	TPH- Gasoline	Benzene	Toluene	Ethyl Benzene	Total Xylenes	МТВЕ
BH-A	15,000	370	780	790	4,600	3 3
вн-в	< 1,000	< 10	1 1	< 10	23	660
вн-С	< 100	< 1.0	< 1.0	< 1.0	< 1.0	170
BH-D	< 50	< 0.5	< 0.5	< 0.5	< 0.5	< 5.0
вн-Е	15,000	260	2 7	890	4,000	< 250
BH-F	< 50	< 0.5	< 0.5	< 0.5	< 0.5	< 5.0
вн-G	< 50,000	< 500	< 500	< 500	< 500	130,000
вн-н	960	1 2	2.3	4 0	4 5	250
BH-I	130*	< 0.5	< 0.5	< 0.5	< 0.5	130
вн-Ј	< 25,000	< 1,300	< 1,300	< 1,300	< 1,300	170,000
BH-K	< 130,000	6,400	< 1,300	< 1,300	< 1,300	410,000
BH-L	120*	< 0.5	< 0.5	< 0.5	< 0.5	110
вн-м	< 50	< 0.5	< 0.5	< 0.5	< 0.5	< 5.0
MCL	NE	1.0	150	680	1,750	13

Notes:

Detectable concentrations are in bold.

Non-detectable concentrations are noted by the less than sign (<) followed by the detection limit.

MCL = California Department of Health Services maximum contaminant level for drinking water.

NE = DHS MCL has not been established.

NE = MCL has not been established.

^{* =} Hydrocarbons do not match the laboratory gasoline standard

APPENDIX A

ACHCSA Letters





DAVID J. KEARS, Agency Director

1131 Harbor Bay Parkway, Suite 250

Alameda, CA 94502-6577 (510) 567-6700

ENVIRONMENTAL HEALTH SERVICES

(510) 337-9335 (FAX)

June 10, 1999

STID 851

Mr. Shahram Shahnazi 140 Geldert Drive Tiburon, CA 94520

Mr. John Rutherford Desert Petroleum P.O. Box 1601 Oxnard, CA 93030

2844 Mountain Boulevard, Oakland - Request for Soil and Water Investigation RE:

Dear Messrs. Shahnazi and Rutherford:

I have completed review of the Western Geo-Engineers (WEGE) quarterly sampling and monitoring report dated March 8, 1999. This report also presents the results of a revised version of WEGE's earlier subsurface conduit study, which evaluates the potential for utility conduits and fault-related features to affect contaminant dispersal from the site. The conduit study reveals the potential for sanitary sewer trenches to contribute to contaminant migration away from the site. The fault element of the study was less conclusive.

Cumulative sampling and monitoring data clearly demonstrate that the releases from the underground storage tanks at this site have not been fully defined. The conduit study adds an additional layer of uncertainty to the plume definition issue. Consequently, plume definition must be achieved through completion of a soil and water investigation (SWI). Ultimately, an appropriate corrective action plan (CAP) will also be required, the scope of which will be substantially based on what is discovered following completion of the SWI.

You directed to submit a SWI work plan for the continued investigation of this gasoline release. The SWI work plan is due within 60 days of the date of this letter.

This phase of the SWI will involve intrusive investigations of the sanitary sewer trenches, as well as other on- and off-site locations. Consequently, you are encouraged to employ the use of so-called "rapid site assessment tools" (e.g., Geoprobe, etc.) for the initial stage of this investigation. Final, permanent well locations may then be determined based on these initial results.

Messrs. Shahnazi and Rutherford RE: 2844 Mountain Blvd., Oakland

June 10, 1999 Page 2 of 2

Please contact me at (510) 567-6783 should you have any questions or comments.

Sincerely,

Scott Q. Seery, CHMM

Hazardous Materials Specialist

cc: Chuck Headlee, RWQCB
Dave Deaner, SWRCB UST Fund
Leroy Griffin, Oakland Fire Department

Jill Duerig, Alameda County District Attorney's Office

ALAMEDA COUNTY HEALTH CARE SERVICES

AGENCY





October 29, 1999

ENVIRONMENTAL HEALTH SERVICES ENVIRONMENTAL PROTECTION 1131 Harbor Bay Parkway. Suite 250 Alameda, CA 94502-6577 (510) 567-6700

STID 851

Mr. Shahram Shahnazi 140 Geldert Drive Tiburon, CA 94520

RE: 2844 Mountain Boulevard, Oakland - Soil and Water Investigation

Dear Mr. Shahnazi:

I have completed review of the August 6, 1999 Aqua Science Engineers Inc. (ASE) soil and water investigation (SWI) work plan for the subject site. This phase of work is intended to: 1) quickly assess potential off-site groundwater impacts using push-tool technology (e.g., Geoprobe®, etc.), and 2) determine whether or not sewer line trenches serve as preferential pathways for plume migration away from the site. This SWI work plan was submitted in response to correspondence from this office dated June 10, 1999.

I have been in contact with ASE's Robert Kitay over the last couple of weeks to discuss boring placement strategies and timing for initiation of this two-pronged phase of the pending SWI. We concluded that three (3) additional borings were necessary for proper coverage (revised map is attached). We also concluded that implementation of the proposed scope of work should be in two stages. Those borings proposed for the opposite side of Mountain Boulevard should be completed as soon as the drillers can be scheduled; however, the sewer line assessment should only begin once groundwater levels have recovered in the early Spring of 2000, and utilities have been more precisely located.

The cited ASE work plan has been accepted as currently amended.

Please have your consultant implement the first stage of the SWI, as articulated above, within 45 days of the date of this letter.

ALAMEDA COUNTY

HEALTH CARE SERVICES







February 9, 2000

STID 851

ENVIRONMENTAL HEALTH SERVICES ENVIRONMENTAL PROTECTION (LOP) 1131 Harbor Bay Parkway, Suite 250 Alameda, CA 94502-6577 (510) 567-6700 FAX (510) 337-9335

Mr. Shahram Shahnazi 140 Geldert Drive Tiburon, CA 94520

RE:

2844 Mountain Boulevard, Oakland - Request for modification to approved Soil and Water Investigation scope of work

Dear Mr. Shahnazi:

I have completed review of the January 27, 2000 Aqua Science Engineers, Inc. (ASE) "interim" report that documents the completion of four (4) Geoprobe® borings (BH-A through BH-D) emplaced on the opposite side of Mt. Boulevard from the subject site. This work is a portion of that proposed in the ASE workplan dated August 6, 1999. The remaining borings, to be emplaced along the sanitary sewer trenches, are slated to be completed in Spring 2000.

ASE's January 27th interim report presents data that demonstrates some degree of fuel hydrocarbon impact to groundwater in off-site locations. Of particular note are the laboratory results from water sampled from boring BH-A, where 15,000 micrograms per liter (ug/l) total petroleum hydrocarbons as gasoline (TPH-G), 370 ug/l benzene, and 4600 ug/l total xylenes, among other compounds, have been identified.

At this time you are requested to augment the remaining scope of the August 6, 1999 ASE workplan with the addition of two (2) more borings in locations south of BH-A, emplaced along the same alignment and spacing as the current boring string of BH-A to BH-D. These two additional borings may be completed at the same time as those planned for completion this Spring.

Please contact me at (510) 567-6783 should you have any questions or comments.

Sincerely,

Scott O. Seery, CHMM

Hazardous Materials Specialist

cc: Chuck Headlee, RWQCB

Dave Deaner, SWRCB UST Fund

Leroy Griffin, Oakland Fire Department

Jill Duerig, Alameda County District Attorney's Office

John Rutherford, Desert Petroleum, P.O. Box 1601, Oxnard, CA 93032

Robert Kitay, Aqua Science Engineers, Inc., 208 W. Pintado Rd., Danville, CA 94526

Mr. Shahnazi

RE: 2844 Mountain Blvd., Oakland

October 29, 1999

Page 2 of 2

Please contact me at (510) 567-6783 should you have any questions or comments, and to inform me when field work will begin.

Sincerely,

Scott O. Seery, CHMM

Hazardous Materials Specialist

Attachment

cc: Chuck Headlee, RWQCB

Dave Deaner, SWRCB UST Fund (w/ attachment)

Leroy Griffin, Oakland Fire Department

Jill Duerig, Alameda County District Attorney's Office

John Rutherford, Desert Petroleum Inc., (w/ attachment)

P.O. Box 1601, Oxnard, CA 93032

Robert Kitay, Aqua Science Engineers Inc.

208 West El Pintado, Danville, CA 94526

ALAMEDA COUNTY

HEALTH CARE SERVICES



DAVID J. KEARS, Agency Director



February 9, 2000

STID 851

ENVIRONMENTAL HEALTH SERVICES ENVIRONMENTAL PROTECTION (LOP) 1131 Harbor Bay Parkway, Suite 250 Alameda, CA 94502-6577 (510) 567-6700 FAX (510) 337-9335

Mr. Shahram Shahnazi 140 Geldert Drive Tiburon, CA 94520

RE:

2844 Mountain Boulevard, Oakland - Request for modification to approved Soil and Water Investigation scope of work

Dear Mr. Shahnazi:

I have completed review of the January 27, 2000 Aqua Science Engineers, Inc. (ASE) "interim" report that documents the completion of four (4) Geoprobe® borings (BH-A through BH-D) emplaced on the opposite side of Mt. Boulevard from the subject site. This work is a portion of that proposed in the ASE workplan dated August 6, 1999. The remaining borings, to be emplaced along the sanitary sewer trenches, are slated to be completed in Spring 2000.

ASE's January 27th interim report presents data that demonstrates some degree of fuel hydrocarbon impact to groundwater in off-site locations. Of particular note are the laboratory results from water sampled from boring BH-A, where 15,000 micrograms per liter (ug/l) total petroleum hydrocarbons as gasoline (TPH-G), 370 ug/l benzene, and 4600 ug/l total xylenes, among other compounds, have been identified.

At this time you are requested to augment the remaining scope of the August 6, 1999 ASE workplan with the addition of two (2) more borings in locations <u>south</u> of BH-A, emplaced along the same alignment and spacing as the current boring string of BH-A to BH-D. These two additional borings may be completed at the same time as those planned for completion this Spring.

Please contact me at (510) 567-6783 should you have any questions or comments.

Sincerely,

Scott O. Seery, CHMM

Hazardous Materials Specialist

cc: Chuck Headlee, RWQCB

Dave Deaner, SWRCB UST Fund

Leroy Griffin, Oakland Fire Department

Jill Duerig, Alameda County District Attorney's Office

John Rutherford, Desert Petroleum, P.O. Box 1601, Oxnard, CA 93032

Robert Kitay, Aqua Science Engineers, Inc., 208 W. Pintado Rd., Danville, CA 94526

APPENDIX B

Permits



EXCAVATION PERMIT

CIVIL ENGINEERING

TO EXCAVATE IN STREETS OR OTHER SPECIFIED WORK

AGE 2 of 2								
PERMIT NUMBER		SITE ADDRESS/LOCATION 2898 MOUNTAIN BL.						
APPROX. START DATE	T DATE APPROX. END DATE 24-HOUR EMERGENCY PHONE NUMBER (Permit not valid without 24-Hour number)							
CONTRACTOR'S LICENSE # AND	CLASS	CITY BUSINESS TAX #						
487000								
	contractor/owner call Underground Service ber issued by USA. The USA telephone is	ce Aleri (USA) two working days before excavating. This permit is not valid unless applicant has secured an number is 1 (800) 642-2444. UNDERGROUND SERVICE ALERT (USA) #:						
48 hours prior to starting work, YOU MUST CALL (510) 238-3651 TO SCHEDULE AN INSPECTION.								
construct, alter, improve, demolish, o provisions of the Contractor's License alleged exemption. Any violation of S I, as an owner of the property, or Professions Code: The Contractor's provided that such improvements are burden of proving that he did not buil I, as owner of the property, am ex be performed prior to sale, (3) I have structures more than once during any I, as owner of the property, am ex does not apply to an owner of propert I am exempt under Sec. WORKER'S COMPENSATION I hereby affirm that I have a certification.	repair any structure, prior to the standard end have repair any structure, prior to the standard end have repaired by any applicant for a perm my employees with wages as their sole conclined to the standard end for the purpose of sale. If however, the sale requirements of the above resided in the residence for the 12 months. The sale repaired in the residence for the 12 months. The sale requirements of the above resided in the residence for the 12 months. The sale requirements of the sale requirements of the sale resided in the residence for the 12 months. The sale requirements of the sale resided in the residence for the 12 months. The sale requirements of the sale residence for the 12 months. The sale requirements are sale requirements of the sale requirements and the sale requirements are sale requirements. The sale requirements are sale requirements as a sale requirement of the sale requirements are sale requirements. The sale requirements are sale requirements as a sale requirement of the sale requirements are sale requirements. The sale requirements are sale requirements of the sale requirements are sale requirements as a sale requirement of the sale requirements are sale requirements. The sale requirements are sale requirements as a sale requirement as a sale requirement of the sale requirements are sale requirements. The sale requirements are sale requirements as a sale requirement as a sale requirement of the sale requirements are sale requirements. The sale requirements are sale requirements as a sale requirement of the sale requirements are sale requirements. The sale requirements are sale requirements as a sale requirement of the sale requirements are sale requirements. The sale requirements are sale requirements as a sale requirement of the sale requirements are sale requirements. The sale requirements are sale requirements as a sale requirement of the sale requirements are sale requirements. The sale requirements are sale requirements are sale requirements as a sale requirement of the sale require	the contracts for such projects with a contractor(s) licensed pursuant to the Co-tractor's License law). Sicate of Worker's Compensation Insurance, or a certified copy thereof (Sec. 3700, Labor Code). 11. I shall not employ any person in any manner so as to become subject to the Worker's Compensation Laws						
NOTICE TO APPLICANT: If, after comply with such provisions or this granted upon the express condition the perform the obligations with respect and employees, from and against any	r making this Certificate of Exemption, ye permit shall be deemed revoked. This per hat the permittee shall be responsible for a to street maintenance. The permittee shall y and all suits, claims, or actions brought	ou should become subject to the Worker's Compensation provisions of the Labor Code, you must forthwith rmit is issued pursuant to all provisions of Title 12 Chapter 12.12 of the Oakland Municipal Code. It is all claims and liabilities arising out of work performed under the permit or arising out of permittee's failure to all, and by acceptance of the permit agrees to defend, indemnify, save and hold harmless the City, its officers by any person for or on account of any bodily injuries, disease or illness or damage to persons and/or proper it or in consequence of permittee's failure to perform the obligations with respect to street maintenance. This is by the Director of the Office of Planning and Building.						
I hereby affirm that I am licensed ur this permit and agree to its requirem	nder provisions of Chapter 9 of Division 3 nents, and that the above information is tru	of the Business and Professions Code and my license is in full force and effect (if contractor), that I have re- ic and correct under penalty of law.						
VRIX C-K	ten	1-5-00						
Signature of Permittee DATE STREET LAST RESURFACED	SPECIAL PAVING DETAIL REQUIRED? DYES DO	HOLIDAY RESTRICTION? LIMITED OPERATION AREA? (NOV 1 - JAN 1) PYES NO (7AM-9AM & 4PM-6PM) TYPES NO (7AM-9AM & 4PM-6PM)						
ISSUED BY	1	DATE ISSUED /- -						



EXCAVATION PERMIT

CIVIL ENGINEERING

TO EXCAVATE IN STREETS OR OTHER SPECIFIED WORK

PAGE 2 of 2

								
PERMIT NUMBER X 00 00346		SITE ADDRESS/LOCATION 2848 MC	UNTAIN BC					
APPROX. START DATE APPROX.	END DATE	24-HOUR EMERGENCY PHONE NUMBER						
		(Permit not valid without 24-Hour number)						
CONTRACTOR'S LICENSE # AND CLASS		CITY BUSINESS TAX #						
ATTENTION: State law requires that the contractor/owner call Underground Service Alert (USA) two working days before excavating. This permit is not valid unless applicant has secured an inquiry identification number issued by USA. The USA telephone number is 1 (800) 642-2444. UNDERGROUND SERVICE ALERT (USA) #: 48 hours prior to starting work, YOU MUST CALL (510) 238-3651 TO SCHEDULE AN INSPECTION.								
OWNER/BUILDER I hereby affirm that I am exempt from the Contractor's License Law for the following reason (Sec. 7031.5 Business and Professions Code: Any city or county which requires a permit to construct, alter, improve, demolish, or repair any structure, prior to its issuance, also requires the applicant for such permit to file a signed statement that he is licensed pursuant to the provisions of the Contractor's License law Chapter 9 (commencing with Sec. 7000) of Division 3 of the Business and Professions Code, or that he is exempt therefrom and the basis for the alleged exemption. Any violation of Section 7031.5 by any applicant for a permit subjects the applicant to a civil penalty of non more than \$500): I, as an owner of the property, or my employees with wages as their sole compensation, will do the work, and the structure is not intended or offered for sale (Sec. 7044, Business provided that such improvements are not intended or offered for sale. If however, the building or improves thereon, and who does such work himself or through his own employees, provided that such improvements are not intended or offered for sale. If however, the building or improvement is sold within one year of completion, the owner-builder will have the burden of proving that he did not build or improve for the purpose of sale). I, as owner of the property, an exempt from the sale requirements of the above due to: (1) I am improving my principal place of residence or appurtenances thereto, (2) the work will be performed prior to sale, (3) I have resident in the residence for the 12 months prior to completion of the work, and (4) I have not claimed exemption on this subdivision on more than two structures more than once during any three-year period. (Sec. 7044 Business and Professions Code). I, as owner of the property, an exclusively contracting with licensed contractors to construct the project, (Sec. 7044, Business and Professions Code). B&PC for this reason B&PC for this reason								
WORKER'S COMPENSATION 1 hereby affirm that 1 have a certificate of conse	ent to self-insure, or a certifi	icate of Worker's Compensation Insurance, or a certi-	fied copy thereof (Sec. 3700, Labor Code).					
☐ I certify that in the performance of the work for	Policy # Company Name I certify that in the performance of the work for which this permit is issued, I shall not employ any person in any manner so as to become subject to the Worker's Compensation Laws of California (not required for work valued at one hundred dollars (\$100) or less).							
NOTICE TO APPLICANT: If, after making this	NOTICE TO APPLICANT: If, after making this Certificate of Exemption, you should become subject to the Worker's Compensation provisions of the Labor Code, you must forthwith comply with such provisions or this permit shall be deemed revoked. This permit is issued pursuant to all provisions of Title 12 Chapter 12.12 of the Oakland Municipal Code. It is granted upon the express condition that the permittee shall be responsible for all claims and liabilities arising out of work performed under the permit or arising out of permittee's failure to perform the obligations with respect to street maintenance. The permittee shall, and by acceptance of the permit agrees to defend, indemnify, save and hold harmless the City, its officers and employees, from and against any and all suits, claims, or actions brought by any person for or on account of any bodily injuries, disease or illness or damage to persons and/or property sustained or arising in the construction of the work performed under the permit or in consequence of permittee's failure to perform the obligations with respect to street maintenance. This permit is void 90 days from the date of issuance unless an extension is granted by the Director of the Office of Planning and Building.							
granted upon the express condition that the permits perform the obligations with respect to street maint and employees, from and against any and all suits, sustained or arising in the construction of the work	to shall be responsible for a enance. The permittee shall claims, or actions brought to performed under the permi-	Il claims and liabilities arising out of work performed I, and by acceptance of the permit agrees to defend, in by any person for or on account of any bodily injuries t or in consequence of permittee's failure to perform	number the permit or arising out of permittee's families in indemnify, save and hold harmless the City, its officers is, disease or illness or damage to persons and/or property the obligations with respect to street maintenance. This					
granted upon the express condition that the permitt perform the obligations with respect to street maint and employees, from and against any and all suits, sustained or arising in the construction of the work permit is void 90 days from the date of issuance un	the shall be responsible for a chance. The permittee shall claims, or actions brought to performed under the permittees an extension is granted of Chapter 9 of Division 3	Il claims and liabilities arising out of work performed, and by acceptance of the permit agrees to defend, it by any person for or on account of any bodily injuries t or in consequence of permittee's failure to perform by the Director of the Office of Planning and Building of the Business and Professions Code and my licenses and correct under penalty of law.	number the permit or arising out of permittee's families in indemnify, save and hold harmless the City, its officers is, disease or illness or damage to persons and/or property the obligations with respect to street maintenance. This					
granted upon the express condition that the permitt perform the obligations with respect to street maint and employees, from and against any and all suits, sustained or arising in the construction of the work permit is void 90 days from the date of issuance upon the beautiful that I am licensed under provisions this permit and agree to its requirements, and that the Signature of Permittee Agent for	pe shall be responsible for a chance. The permittee shall claims, or actions brought by performed under the permittees an extension is granted of Chapter 9 of Division 3 he above information is true	Il claims and liabilities arising out of work performed, and by acceptance of the permit agrees to defend, it by any person for or on account of any bodily injuries t or in consequence of permittee's failure to perform by the Director of the Office of Planning and Building of the Business and Professions Code and my licenses and correct under penalty of law.	under the permit or arising out of permittee's families and monify, save and hold harmless the City, its officers is, disease or illness or damage to persons and/or property the obligations with respect to street maintenance. This is					



EXCAVATION PERMIT

CIVIL ENGINEERING

TO EXCAVATE IN STREETS OR OTHER SPECIFIED WORK

AGE 2 of 2	ON	WERNE	R						
PERMIT NUMBER		SITE ADDRESS/LOCATION							
X00 00	339	2848	MOUNTAIN BL						
APPROX. START DATE	APPROX. END DATE	24-HOUR EMERGENCY PHONE NUM	(BER						
		(Permit not valid without 24-Hour number	r)						
CONTRACTOR'S LICENSE # AND									
ATTENTION:									
			ccavating. This permit is not valid unless applicant has secured an OUND SERVICE ALERT (USA) #:						
2) 48 hours prior to	48 hours prior to starting work, YOU MUST CALL (510) 238-3651 TO SCHEDULE AN INSPECTION.								
OWNER/BUILDER									
construct, alter, improve, demolish, or provisions of the Contractor's License alleged exemption. Any violation of S l, as an owner of the property, or s Professions Code: The Contractor's I provided that such improvements are r burden of proving that he did not build l. as owner of the property, am exist performed prior to sale, (3) I have structures more than once during any t. I, as owner of the property, am exist does not apply to an owner of property.	r repair any structure, prior to its issuance law Chapter 9 (commencing with Sec. 7 dection 7031.5 by any applicant for a pen my employees with wages as their sole of License Law does not apply to an owner not intended or offered for sale. If hower dor improve for the purpose of sale), empt from the sale requirements of the attestided in the residence for the 12 month three-year period. (Sec. 7044 Business are clusively contracting with licensed contra	te, also requires the applicant for such perm. (2000) of Division 3 of the Business and Prof. (2000) of Division 3 of the Business and Prof. (2001) of Division 3 of the Business and Prof. (2001) of Division 3 of the Business and Prof. (2001) of the work, and the structure of property who builds or improves thereon ver, the building or improvement is sold with bove due to: (1) I am improving my principles prior to completion of the work, and (4) I and Professions Code). (2001) (Sec. 7044, Black of Construct the project, (Sec. 7044, Black of Constructs for such projects with a contra-	refessions Code: Any city or county which requires a permit to it to file a signed statement that he is licensed pursuant to the fessions Code, or that he is exempt therefrom and the basis for the of not more than \$500): ture is not intended or offered for sale (Sec. 7044, Business, and who does such work himself or through his own employees, thin one year of completion, the owner-builder will have the sal place of residence or appurtenances thereto, (2) the work will have not claimed exemption on this subdivision on more than two dusiness and Professions Code: The Contractor's License Law ctor(s) licensed pursuant to the Contractor's License law).						
WORKER'S COMPENSATION									
C I hereby affirm that I have a certifi	cate of consent to self-insure, or a certifi	icate of Worker's Compensation Insurance,	or a certified copy thereof (Sec. 3700, Labor Code).						
Policy #	Company Name								
	the work for which this permit is issued alued at one hundred dollars (\$100) or lea		ner so as to become subject to the Worker's Compensation Laws						
comply with such provisions or this per granted upon the express condition that perform the obligations with respect to and employees, from and against any sustained or arising in the construction	ermit shall be deemed revoked. This pen it the permittee shall be responsible for all a street maintenance. The permittee shall and all suits, claims, or actions brought b a of the work performed under the permit	mit is issued pursuant to all provisions of T il claims and liabilities arising out of work p l, and by acceptance of the permit agrees to by any person for or on account of any bodil	compensation provisions of the Labor Code, you must forthwith itle 12 Chapter 12.12 of the Oakland Municipal Code. It is erformed under the permit or arising out of permittee's failure to defend, indemnify, save and hold harmless the City, its officers by injuries, disease or illness or damage to persons and/or property perform the obligations with respect to street maintenance. This ad Building.						
	er provisions of Chapter 9 of Division 3 of that the above information is true		by license is in full force and effect (if contractor), that I have read						
Signature of Permittee	Agent for Contractor Owner		Date						
DATE STREET LAST	SPECIAL PAVING DETAIL	HOLDAY RESTRICTION?	LIMITED OPERATION AREA?						
RESURFACED	REQUIRED? OYES ONO	(NOV I - JAN I) TYES	NO TAM-SAM & 4PM-6PM TYES PONO						
ISSUED BY	rtió	DATE ISSUED 4-12	-00						

from 5107821

5197821939 → ADUA SCIENCE 10 RM239 FAX NO. 5197821939 Page 2



ALAMEDA COUNTY PUBLIC WORKS AGENCY
WATER RESOURCES SECTION
399 ELMHURST ST. HAMMARD CH. 94544
510-670-5554
510-752-1039 FAX#

drilling permit application POR OFFICE USE FOR APPLICANT TO COMPLETE PERMIT NUMBER LOCATION OF PROJECT WELL NUMBER TERMIT CONDITIONS Circled Permit Requirements Apply CON APN GENERAL

Netwist application should be submitted so as so

across five days prior to CLIENT nram Shakinazi Woothigate Orace P Stiahram_ serive at the ACPWA office five days prior to Name Phone (415 proposed starting date. Earl UCA 99302 Zip Submit to ACPWA within 60 days affer completion of permitted work the original Department of Waler Resources - Well Completion ermit is void if proffeilmor begun within go days of anninva date. O WATER SUPPLY WELLS TYPE OF PROJECT 1. Minimum surface seal thickness is two inches of Geotechnical Investigation Well Construction coment grout placed by tremis. General Cathodic Protecțien 9.00 2. Minimum seat depth is 50 feet for municipal and Contamination : 1 ষ্ Water Supply industrial wells or 20 feet for contestic and irrigation Well Destruction Monitoring wells unless a lesser depth is specially approved. CROUNDWATER MONITORING WELLS PROPOSED WATER SUPPLY WELL USE ٥ Replacement Domestic New Domestic 0 . I Minimum surface seel thickness is two inches of mertegism Ö Municipai 0 coment grout placed by tremie. Other Industrial Ď 1. Minimum scat depth for monitoring wells is the maximum depth practicable or 20 teel-DRILLING METHOD: (B) GEOTECHNICAL BOXXIII Air Rolary Mud Rosary 0 th cement grant or Cable Other DRILLER'S LICENSE NO. CATRODIC WELL PROJECTS

Orill Hole Dismeter. Fill hole above anode zone with Honerete placed by hit mic. mumjas M WELL DESTRUCTION Depil _ Çasing Qiamqiçi Sec alinehed. Spriage Scal Depth . Number_ GEOTECHNICAL PROJECTS Maximum Deptile__ ESTIMATED STARTING DATE ESTIMATED COMPLETION DATE

APR 11 2020 15:44

APPLICANT'S

Alameda County Ordinance No. 73-68.

i hereby agree to comply with all requirements of this permit and

9259374853

PROE. 0

Pa98 1/ 1



ALAMEDA COUNTY PUBLIC WORKS AGENCY

WATER RESOURCES SECTION 951 TURNER COURT, SUITE 300, HAVWARD, CA 94545-2651
PHONE (510) 670-5575 ANDREAS GODFREY FAX (510) 670-5262
(510) 670-5248 ADVIN KAN

for applicant to complete	for office use
· ·	PERMIT NUMBER WCO-014
ATION OF PROJECT 2844 Mountain Blud) D.N. 11 1 V V V 2
· Oalland	WELL NUMBER
The state of the s	PERMIT CONDITIONS
formis Coordinates Source n. GCE A Recuracy #_ fi.	PERMIT CONDITIONS
n. cce	Circled Parmit Requirements Apply
ENT .	A. GENERAL
. Shahmam Shahmaæi	l. A permit application should be submitted so as to
155 140 beldert Driver Phone (415) 902-3558	arrive at the ACPIVA office five days prior to
Thuron, ch 210 97520	proposed elarting date.
11000000	A submit to ACPWA within 60 days after completion of
LICANT	permitted work the original Department of Weter
10 day Science Engineers Inc	Resources Water Well Dritters Report or equivalent for
40: Rebort Kiton Fai(9=5)837-4853	well projects, or drilling logs and location sketch for
100 108 Wast & Property Phone (725) 820-7451	contachnical projects.
Disoville, cd Zip 94526	Pormit is void if project not begun within 90 days of
	approval date.
PE OF PROJECT	B. WATER SUPPLY WELLS
eli Construction Geossophical Investigation	1. Minimum surface seal thickness is two inches of
Cathodic Protection 🗇 General 🗆	centent grout placed by fromie.
Water Supply Q Contentination &	2. Minimum seal depth is 30 (cer for municipal and
Monitoring C Well Destruction C	Industrial wells or 20 feet for domestic and irrigation
,	wells unless a losser depth is specially approved.
oposed water supply well use	C. Jroundwater monitoring wells
New Domestie O Replacement Domestic O	INCLUDING PIEZOMETERS
Municipal G Irrigation C	Attnimum surface scal thickness is two inches of
Industrial D Other	🤾 🖰 thient grout placed by tremis.
modes is a constant of the con	Lightnum seal depth for monitoring wells is the
illing method:	maximum depth practicable or 20 feet.
Mud Rotary O Air Rotary D Auger D	(D) GEOTECHNICAL CEMENT ATOUT
Cable S Other S	D GEOTECHNICAL CEMENT BOUT Backfill bore hole with computed outsides or heav)
VIII .	begionlie and upper two feet with compacted material.
ILLER'S LICENSE NO. 457 487000	omorphisms, acquied
	samest group abalilian and in place of agrapheral analogue
ell projects	E. CATHODIC
Drill Hole Diameterin. Maximum	Fill hole above anode zone with concrete placed by tremie
Casing Diameter in Depth [].	F. WELL DESTRUCTION
Surface Seal Depth R. Number	See attached.
•	G. SPECIAL CONDITIONS
eotechnical projects	
Number of Borings Maximum	4
Hole Dismeter 2 in Depth 30 ft	
	APPROVED THOMPS LOOK DATE 1-07-
TIMATED STARTING DATE 1.7-00	APPROVED ON UMPALOTAL DATE -UT
TIMATED COMPLETION DATE 17-00	

APPLICANT'S

APPENDIX C

Boring Logs

Project Name: Comparing Project Name: Comparing Priller: Vironex Logged By: Ian T. Recomparing Prince Prin	pare Prices eed DATA Encountered: 19	Project Locat Type of Rig: 0 Date Drilled:	tion: 2844 Mountain Blvd., Oakland, CA Page 1 of 2 Geoprobe Size of Drill: 2.0" Diameter April 18, 2000 Checked By: Robert E. Kitay, R.G.
Driller: Vironex Logged By: Ian T. Rec WATER AND WELL Depth of Water First E Static Depth of Water i Total Depth of Boring: BORING DETAIL O -0	eed DATA Encountered: 19	Type of Rig: (Geoprobe Size of Drill: 2.0" Diameter April 18, 2000 Checked By: Robert E. Kitay, R.G.
Logged By: Ian T. Ree WATER AND WELL Depth of Water First E Static Depth of Water i Total Depth of Boring: BORING DETAIL O O	DATA Encountered: 19	Date Drilled:	April 18, 2000 Checked By: Robert E. Kitay, R.G.
WATER AND WELL Depth of Water First E Static Depth of Water i Total Depth of Boring: BORING HE DETAIL O -0	DATA Encountered: 19		
Depth of Water First E Static Depth of Water i Total Depth of Boring: 100 100 100 100 100 100 100 100 100 1	Encountered: 19	,ı	Total Depth of Well Completed: NA
Static Depth of Water is Total Depth of Boring: 199 LL LI BORING DETAIL 0 -0		y.	
Total Depth of Boring: tell BORING DETAIL 0 -0	in Well: NA		Well Screen Type and Diameter: NA
BORING DETAIL O O O O O O O O O O O O O O O O O O			Well Screen Slot Size: NA
BORING DETAIL O O O O O O O O O O O O O	: 36'		Type and Size of Soil Sampler: 2.0" I.D. Macro Sampler
BORING DETAIL O O O O O O O O O O O O O		SAMPLE DATA	DESCRIPTION OF LITHOLOGY
- - - - - 5	Description Interval Blow Counts	Water Level Graphic Log	standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation.
→ 1		0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	Clayey SILT (ML); brown to black; moist; very stiff; 60% silt; 30% clay; 10% fine sand; trace gravel; medium plasticity; low estimated K; no odor Sandy SILT (ML); dark brown to light brown; damp; medium stiff; 70% silt; 30% fine to coarse sand; low estimated K; no odor moderate hydrocarbon odor at 15' moderate hydrocarbon odor at 18' Silty SAND (SM); light brown to orange brown; damp; very stiff; 60% fine to coarse sand; 40% silt; non-plastic; low estimated K; no odor Clayey SILT (ML); brown; damp; very stiff; 60% silt; 30% clay; 10% fine to coarse sand; low plasticity; very low estimated K; no odor slight hydrocarbon odor

Project Location: 2844 Mountain Blvd., Calkland, CA Page 2 of 2	SOIL BORING LOG AND MONITORING WELL COMPLETION DETAILS BORING: BH-E											
BORNO DETAIL The second of Detail De										2 of 2		
Sandy SILT (ML); gray; wet; very stiff; 60% stit; 30% fine to coarse sand; 5% clay; 5% gravel; trace organics tow plasticity; low estimated K; slight hydrocarbon odor strength of the same strength o	eet		SOII	-			LE DATA	eet	DESCRIP*	TION OF LITH	OLOGY	
Sandy SILT (ML); gray; wet; very stiff, 60% silt; 30% fine to coarse sand; 5% clay; 5% gravel; trace organics tow plasticity; low estimated K; slight hydrocarbon odor solution and state of the same	.⊆ I BOF	Descriptio	Interval	Blow Count	OVM (ppm	Water Level	Graphic Log	Depth in F				
-40 -40 -45 -45 -45 -50 -50 -55 -55 -66 -66 -66	- - - - - 35				20			_ _ _ _ _35	fine to coarse sand; to low plasticity; low est	5% clay; 5% timated K; slig	gravel; trace ght hydrocarb	organics;
									Er	nd of Boring a	at 36'	
	_											
aqua science Engineers, inc.		. <u> </u>				···			a /~ 11 a /~ 1	AIENAE E		08*

SOIL BORING LOG AND MONIT	ORING WELI	COMPLETION DET	TAILS BORING: BH-F	
Project Name: Compare Prices	Project Location	n: 2844 Mountain Blvd	., Oakland, CA	Page 1 of 2
Driller: Vironex	Type of Rig: G	eoprobe Siz	ze of Drill: 2.0" Diamete	
Logged By: Ian T. Reed	Date Drilled:	April 18, 2000	Checked By: Robert 6	E. Kitay, R.G.
WATER AND WELL DATA		Total Depth of Well Co	mpleted: NA	
Depth of Water First Encountered: 19		Well Screen Type and	Diameter: NA	
Static Depth of Water in Well: NA		Well Screen Slot Size:	NA	
Total Depth of Boring: 40'	"		Sampler: 2.0" I.D. Macro	Sampler
X	SAMPLE DATA	LL	ESCRIPTION OF LITHOLO	GY
Depth in Fe TIVIAN Description Interval Blow Counts	Water Level Graphic Log	F 1	assification, texture, rel fness, odor-staining, USG	
-0 5 1 5	▼	70% silt; 25% plasticity; low of	clay; 20% fine to coars	sand; low nedium stiff; on-plastic; low
- - -25 -		30% clay; 10% low estimated l		low plasticity;
- - -30		stiff; 60% silt;	IL); light brown speckled 30% fine to coarse san low estimated K; no odo	d; 10% clay;
		AQ	ua science engli	neers, inc.

son	SOIL BORING LOG AND MONITORING WELL COMPLETION DETAILS BORING: BH-F										
Proje	ct Name: Co	mpare	Price	s		Proje	ct Location	on: 284	4 Mountain Blvd., Oakland, C	A Page 2	of 2
eet			SOIL				LE DATA	eet	DESCRIPTION C	OF LITHOLOGY	
Depth in Feet	BORING DETAIL	Description	Interval	Blow Counts	OVM (ppmv)	Water Level	Graphic Log	Depth in Feet	standard classification, density, stiffness, odor-s		
Jed - 35 - 40 - 5 - 60 - 60		Des	M MAMMAMM M Inde		NAO o	Wate	Out of the state o	lad	Clayey SILT (ML); light bro 30% clay; 10% fine to med low estimated K; no odor Silty CLAY (CL); olive gray clay; 30% silt; 10% fine to plasticity; very low estimate	own; moist; stiff; 60% fium sand; low plastici y; moist; very stiff; 6 coarse sand; low ed K; no odor	silt; ity;
F											
F		,						-			
- 65								- 65 -			
F								<u> </u>			
								_			
	aqua science engineers, inc.										

SOIL BORING LOG AND MONIT	ORING WEL	L COMPLETION DETAILS BORING: BH-G					
Project Name: Compare Prices	Project Location	ion: 2844 Mountain Blvd., Oakland, CA Page 1 of 1					
Driller: Vironex	Type of Rig: G						
Logged By: lan T. Reed	Date Drilled:	April 18, 2000 Checked By: Robert E. Kitay, R.G.					
WATER AND WELL DATA		Total Depth of Well Completed: NA					
Depth of Water First Encountered: 14	.5'	Well Screen Type and Diameter: NA					
Static Depth of Water in Well: NA		Well Screen Slot Size: NA					
Total Depth of Boring: 28'		Type and Size of Soil Sampler: 2.0" I.D. Macro Sampler					
	SAMPLE DATA	DESCRIPTION OF LITHOLOGY					
Depth in Fe TIVETYAL Blow Counts	Water Level Graphic Log	DESCRIPTION OF LITHOLOGY standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation.					
-0 - 5 - 10 - 15 20 25 - 25 - 25 - 2	00 00 00 00	Silty CLAY (CL); black; moist; very stiff; 60% clay; 30% silt; 10% fine to coarse sand; low plastcity; low estimated K; no odor Sandy SILT (ML); light brown to olive gray; damp; very stiff; 70% silt; 30% fine to coarse sand; non-plastic; low estimated K; moderate hydrocarbon odor 60% silt; 25% fine to coarse sand; 10% silt; 5% gravel to 0.5" diameter; low plastcity; very low estimated K; strong hydrocarbon odor wet at 14.5' Clayey SILT (ML); light brown; moist; very stiff; 60% silt; 30% clay; 10% fine to coarse sand; low plasticity; low estimated K; slight hydrocarbon odor End of Boring at 28'					
-30							
		aqua science engineers, inc.					

Project Name: Compare Prices Project Location: 2844 Mountain Bivd., Oakland, CA Page 1 of 1 Driller: Vironex Type of Rig: Geoprobe Size of Drill: 2.0° Diameter Checked By: Robert E. Kitay, R.G. Potential State of Drilled: April 18, 2000 Checked By: Robert E. Kitay, R.G. Potential State of Drilled: NA WATER AND WELL DATA Depth of Water First Encountered: 12.5' Total Depth of Well Completed: NA Well Screen Type and Diameter: NA Well Screen Type and Diameter: NA Total Depth of Boring: 28' Type and Size of Soil Sampler: 2.0° I.D. Mecro Sampler DESCRIPTION OF LITHOLOGY standard classification, texture, rolative moisture, density, stiffness, odor-staining, USCS designation. Aphalt Gravelly SAND (SW); brown; damp; very stiff; 60% fine to coarse sand; 30% gravel to 0.5° diameter; 10% silit; non-plastic; low estimated K; sight hydrocarbon odor at 7.5' Sility SAND (SM); clive gray; wet; stiff; 60% fine to medium sand; 40% silt; non-plastic; medium estimated K; slight hydrocarbon odor 12 Sility SAND (SM); clive gray; wet; stiff; 60% fine to medium sand; 40% silt; non-plastic; medium estimated K; slight hydrocarbon odor 20 Salty SLT (ML); brown to olive gray; damp; stiff; 60% fine to medium sand; 40% silt; non-plastic; medium estimated K; slight hydrocarbon odor 15 Sility SAND (SM); clive gray; wet; stiff; 60% fine to medium sand; 35% silt; 5% clay; non-plastic; high estimated K; no odor End of Boring at 28' AQUA SCIENCE ENGINEERS NO.	SOIL BORING LOG AND MOI	IITORING WE	ELL COMPLETION DETAILS BORING: BH-H
Logged By: Ian T. Reed Date Drilled: April 18, 2000 Checked By: Robert E. Kilay, R.G. Total Depth of Water First Encountered: 12.5' Static Depth of Water in Well: NA Static Depth of Boring: 28' BORING DETAIL DETAIL DETAIL DETAIL DETAIL DETAIL DETAIL DESCRIPTION OF LITHOLOGY Sandy SLT (ML); brown; damp; very stiff; 60% fine to coarse sand; 30% gravel to 0.5' diameter; 10% slit; non-plastic; low estimated K; slight hydrocarbon odor at 7.5' Silly SAND (SM); olive gray; wet; sliff; 60% fine to medium sand; 40% slit; non-plastic; medium estimated K; slight hydrocarbon odor Saturated; 60% fine to medium sand; 35% slit; 5% clay; non-plastic; high estimated K; no odor End of Boring at 28'	Project Name: Compare Prices	Project Loca	cation: 2844 Mountain Blvd., Oakland, CA Page 1 of 1
Total Depth of Walter First Encountered: 12.5' Well Screen Type and Diameter: NA Well Screen Type and Diameter: NA Total Depth of Water First Encountered: 12.5' Type and Size of Soil Sampler: 2.0' I.D. Macro Sampler Size of Soil Sampler: 2.0' I.D. Macro Sampler DESCRIPTION OF LITHOLOGY standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation. DETAIL DESCRIPTION OF LITHOLOGY standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation. Applied Gravelly SAND (SW); brown; damp; very stiff; 60% fine to coarse sand; 30% gravel to 0.5' diameter; 10% stilt; non-plastic; low estimated K; no odor Sandy SILT (ML); brown to offive gray; well, stiff; 60% silt; non-plastic; medium and 40% silt; non-plastic; medium and 40% silt; non-plastic; medium estimated K; slight hydrocarbon odor End of Boring at 28' End of Boring at 28'	Driller: Vironex	Type of Rig:	: Geoprobe Size of Drill: 2.0" Diameter
Depth of Water First Encountered: 12.5' Well Screen Type and Diameter: NA Well Screen Slot Size: NA Total Depth of Boring: 28' Type and Size of Soil Sampler: 2.0" I.D. Macro Sampler BORING DETAIL	Logged By: Ian T. Reed	Date Drilled	d: April 18, 2000 Checked By: Robert E. Kitay, R.G.
Static Depth of Water in Well: NA Total Depth of Boring: 28' Solution Color Solution Size So	WATER AND WELL DATA		Total Depth of Well Completed: NA
Total Depth of Boring: 28' Type and Size of Soil Sampler: 2.0' I.D. Macro Sampler DESCRIPTION OF LITHOLOGY standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation. Asphalt Gravelly SAND (SW); brown; damp; very stiff; 60% film to coarse sand; 30% gravel to 0.5' dlameter; 10% stilt, non-plastic; low estimated K; slight hydrocarbon odor at 7.5' Sandy SILT (ML); brown to olive gray; damp; stiff; 60% silt, 40% fine to coarse sand; non-plastic; low estimated K; slight hydrocarbon odor at 12' Silty SAND (SM); olive gray; wet; stiff; 60% fine to medium sand; 40% silt; non-plastic; medium estimated K; slight hydrocarbon odor saturated; 60% fine to medium sand; 35% silt; 5% clay; non-plastic; high estimated K; no odor End of Boring at 28'	Depth of Water First Encountered:	12.5'	Well Screen Type and Diameter: NA
BORING DETAIL TO THE POPULATION OF LITHOLOGY Standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation. Asphalt Gravelly SAND (SW); brown; damp, very stiff; 60% fine to coarse sand; 30% gravel to 0.5* dlameter; 10% stiffne to coarse sand; 30% gravel to 0.5* dlameter; 10% stiffne to coarse sand; non-plastic; low estimated K; no odor Sandy SILT (ML); brown to olive gray; damp; stiff; 60% silt; 40% fine to coarse sand; non-plastic; low estimated K; no odor Sandy SILT (ML); brown to olive gray; damp; stiff; 60% silt; 40% fine to coarse sand; non-plastic; low estimated K; no odor Sandy SILT (ML); brown to olive gray; damp; stiff; 60% silt; 40% fine to medium sand; 40% silt; non-plastic; medium estimated K; slight hydrocarbon odor at 12' Silty SAND (SM); olive gray; wet; stiff; 60% fine to medium sand; 40% silt; non-plastic; medium estimated K; slight hydrocarbon odor saturated; 60% fine to medium sand; 35% silt; 5% clay; non-plastic; high estimated K; no odor End of Boring at 28'	Static Depth of Water in Well: NA		Well Screen Slot Size: NA
BORING DETAIL Standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation. Asphalt Gravelly SAND (SW); brown; damp; very stiff; 60% fine to coarse sand; non-plastic; low estimated K; night hydrocarbon odor at 12' Silty SAND (SM); brown to dive gray; damp; stiff; 60% fine to coarse sand; non-plastic; low estimated K; slight hydrocarbon odor at 12' Silty SAND (SM); olive gray; wet; stiff; 60% fine to medium sand; 40% slit; non-plastic; medium estimated K; slight hydrocarbon odor Silty SAND (SM); olive gray; wet; sliff; 60% fine to medium sand; 40% slit; non-plastic; medium estimated K; slight hydrocarbon odor BORING DETAIL			
Section Detail Detail	* 1		TA
Asphalt Gravelly SAND (SW); brown; damp; very stiff; 60% fine to coarse sand; 30% gravel to 0.5' diameter; 10% silt; non-plastic; low estimated K; no odor Sandy SILT (ML); brown to olive gray; damp; stiff; 60% silt; 40% fine to coarse sand; non-plastic; low estimated K; slight hydrocarbon odor at 7.5' slight hydrocarbon odor at 7.5' slight hydrocarbon odor at 12' Silty SAND (SM); olive gray; wet; stiff; 60% fine to medium sand; 40% silt; non-plastic; medium estimated K; slight hydrocarbon odor 20 saturated; 60% fine to medium sand; 35% silt; 5% clay; non-plastic; high estimated K; no odor End of Boring at 28'	Depth in Descriptic Blow Coun	OVM (ppm Water Leve Graphic	standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation.
AQUA SCIENCE FNGINEERS INC	-0 - 5 10 15	85 3,300 4,000 4,000 ¥ 300	Gravelly SAND (SW); brown; damp; very stiff; 60% fine to coarse sand; 30% gravel to 0.5" diameter; 10% silt; non-plastic; low estimated K; no odor Sandy SILT (ML); brown to olive gray; damp; stiff; 60% silt; 40% fine to coarse sand; non-plastic; low estimated K; slight hydrocarbon odor slight hydrocarbon odor at 7.5' slight hydrocarbon odor at 10' moderate hydrocarbon odor at 12' Silty SAND (SM); olive gray; wet; stiff; 60% fine to medium sand; 40% silt; non-plastic; medium estimated K; slight hydrocarbon odor saturated; 60% fine to medium sand; 35% silt; 5% clanon-plastic; high estimated K; no odor End of Boring at 28'
	-30		AQUA SCIENCE ENGINEERS, INC.

.

		IVIOI	1110	אווחי	G WELI		MPLETION DETAILS BORING: BH-I
Project Name: Compare Prices Project Location				Proje	ct Locatio	on: 28	44 Mountain Blvd., Oakland, CA Page 1 of 1
Driller: Vironex			1	Гуре	of Rig: G	eoprob	
Logged By: lan T. I	Reed		ו	Date	Drilled:	April	19, 2000 Checked By: Robert E. Kitay, R.G.
WATER AND WEL	L DATA					Total	Depth of Well Completed: NA
Depth of Water Firs	t Encounte	red:	17'			Well	Screen Type and Diameter: NA
Static Depth of Wate	er in Well:	NA				Well	Screen Slot Size: NA
Total Depth of Borin	g: 24'					Туре	and Size of Soil Sampler: 2.0" I.D. Macro Sampler
Feet					LE DATA	Feet	DESCRIPTION OF LITHOLOGY
BORING DETAIL	Description	Blow Counts	OVM (ppmv)	Water Level	Graphic Log	Depth in F	standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation.
			0 0 0	Ţ		- 0 - 5 - 10 - 15 - 20 - 25 - 30	Clayey SILT (ML); dark brown; moist; stiff; 60% silt; 40% clay; low plasticity; very low estimated K; no odor Sandy SILT (ML); brown; moist; stiff; 60% silt; 30% fine to coarse sand; 5% clay; 5% gravel to 0.5" diameter; non-plastic; low estimated K; no odor wet at 17' Silty CLAY (CL); olive gray; moist; stiff; 60% clay; 40% silt; low plasticity; very low estimated K; no odor Silty SAND (SM); brown; wet; stiff; 70% fine to coarse sand; 30% silt; non-plastic; medium estimated K; no odor Silty CLAY (CL); olive to brown. very moist; stiff; 60% clay; 30% silt; 10% fine to coarse sand; medium plasticity; very low estimated K; no odor Gravelly CLAY (CL); olive gray; very moist; stiff; 60% clay; 25% gravel to 1" diameter; 10% fine to coarse sand; 5% silt; low plasticity; very low estimated K;

Project Name: Compare Prices Project Location: 2844 Mountain Blvd., Oakland, CA Page 1 of 1 Priller: Vironex Type of Rig: Geoprobe Size of Drill: 2.0° Diameter Coged By: Ian T. Reed Date Drilled: April 18, 2000 Checked By: Robert E. Kitay, R.G. WATER AND WELL DATA Dopth of Water First Encountered: 12' Well Screen Type and Diameter: NA Static Depth of Water in Well: NA Total Depth of Boring: 16' BORNAS BO	SOIL BORING LOG AND MONITORING WE	LL COMPLETION DETAILS BORING: BH-J
Logged By: Ian T. Reed Date Drilled: April 18, 2000 Checked By: Robert E. Kitay, R.G. WATER AND WELL DATA Depth of Water First Encountered: 12' Static Depth of Water in Well: NA Total Depth of Boring: 16' Total Depth of Boring: 16' BORNG BORNG DETAIL BORNG DETAIL BORNG BORNG	Project Name: Compare Prices Project Loca	tion: 2844 Mountain Blvd., Oakland, CA Page 1 of 1
WATER AND WELL DATA Depth of Water First Encountered: 12' Static Depth of Water in Well: NA Well Screen Type and Diameter: NA Well Screen Slot Size: NA Total Depth of Boring: 16' Type and Size of Soil Sampler: 2.0" I.D. Macro Sampler DESCRIPTION OF LITHOLOGY standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation. DETAIL BORING B	Driller: Vironex Type of Rig:	Goopius
Depth of Water First Encountered: 12' Static Depth of Water in Well: NA Total Depth of Boring: 16' Type and Size of Soil Sampler: 2.0' I.D. Macro Sampler Type and Size of Soil Sampler: 2.0' I.D. Macro Sampler DESCRIPTION OF LITHOLOGY Standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation. Concrete Sandy Sil.T (ML); brown; damp; stiff; 70% silt; 30% fine to medium sand; non-plastic; low estimated K; no odor Not coarse sand; 40% silt; non-plastic; medium estimated K; strong hydrocarbon odor at 13' Sandy Sil.T (ML); brown; damp; stiff; 60% fine to coarse sand; 40% silt; non-plastic; medium estimated K; strong hydrocarbon odor at 13' Sandy Sil.T (ML); brown; damp; stiff; 60% fine to coarse sand; 40% silt; non-plastic; medium estimated K; strong hydrocarbon odor at 13' Sandy Sil.T (ML); olive to light brown; stiff; 70% silt; 30% fine to medium sand; non-plastic; low estimated K; hydrocarbon odor End of Boring at 16'	Logged By: Ian T. Reed Date Drilled	April 18, 2000 Checked By: Robert E. Kitay, R.G.
Static Depth of Water in Well: NA Total Depth of Boring: 16' Type and Size of Soil Sampler: 2.0' I.D. Macro Sampler DESCRIPTION OF LITHOLOGY standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation. Concrete Sandy SILT (ML); brown; damp; stiff; 70% silt; 30% fine to medium sand; non-plastic; low estimated K; no odor hydrocarbon odor at 6' Sitty SAND (SM); green; very moist; stiff; 60% fine to coarse sand; 40% silt; non-plastic; medium estimated K; strong hydrocarbon odor at 13' Sandy SILT (ML); brown; damp; stiff; 60% fine to coarse sand; 40% silt; non-plastic; medium estimated K; strong hydrocarbon odor at 13' Sandy SILT (ML); brown; damp; stiff; 60% fine to coarse sand; 40% silt; non-plastic; medium estimated K; strong hydrocarbon odor at 13' Sandy SILT (ML); olive to light brown; stiff; 70% silt; 30% fine to medium sand; non-plastic; low estimated K; hydrocarbon odor End of Boring at 16'	WATER AND WELL DATA	Total Depth of Well Completed: NA
Total Depth of Boring: 16' Type and Size of Soil Sampler: 2.0" I.D. Macro Sampler DESCRIPTION OF LITHOLOGY standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation. O Concrete Sandy SILT (ML): brown: damp; stiff; 70% silt; 30% fine to medium sand; non-plastic; low estimated K; no odor 10 Silty SAND (SM); green; very moist; stiff; 60% fine to coarse sand; 40% silt; non-plastic; medium estimated K; strong hydrocarbon odor at 13' Sandy SILT (ML): brown; damp; stiff; 70% silt; 30% fine to medium sand; non-plastic; medium estimated K; strong hydrocarbon odor wet at 12' very strong hydrocarbon odor at 13' Sandy SILT (ML): olive to light brown; stiff; 70% silt; 30% fine to medium sand; non-plastic; low estimated K; hydrocarbon odor End of Boring at 16'	Depth of Water First Encountered: 12'	Well Screen Type and Diameter: NA
SOLUTION OF LITHOLOGY BORING DETAIL THE DETAIL BORING DETAIL THE DETAIL BORING DETAIL BORI	Static Depth of Water in Well: NA	Well Screen Slot Size: NA
BORING DETAIL Secondary S	Total Depth of Boring: 16'	Type and Size of Soil Sampler: 2.0" I.D. Macro Sampler
Standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation. Standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation. Concrete		DESCRIPTION OF LITHOLOGY
Sandy SILT (ML); brown; damp; stiff; 70% silt; 30% fine to medium sand; non-plastic; low estimated K; no odor 10	Depth in F Description Description Interval Blow Count OVM (ppmv Water Level	
aqua science engineers, inc.		Sandy SILT (ML); brown; damp; stiff; 70% silt; 30% fine to medium sand; non-plastic; low estimated K; no odor Silty SAND (SM); green; very moist; stiff; 60% fine to coarse sand; 40% silt; non-plastic; medium estimated K; strong hydrocarbon odor wet at 12' very strong hydrocarbon odor at 13'

Project Name: Composition of Project Name: Composition of Priller: Vironex Logged By: Ian T. Re WATER AND WELL Depth of Water First to Static Depth of Water Total Depth of Boring:	ed DATA Encountered: 12	Type o	of Rig: G	ion: 2844 Mountain Blvd., Oakland, CA Page 1 of 1 Geoprobe Size of Drill: 2.0" Diameter April 19, 2000 Checked By: Robert E. Kitay, R.G.
Logged By: Ian T. Re WATER AND WELL Depth of Water First I Static Depth of Water Total Depth of Boring:	DATA Encountered: 12	Date		
WATER AND WELL Depth of Water First I Static Depth of Water Total Depth of Boring:	DATA Encountered: 12		Drilled:	April 19, 2000 Checked By: Robert E. Kitay, R.G.
Depth of Water First I Static Depth of Water Total Depth of Boring:	Encountered: 12	<u>.</u>		
Static Depth of Water Total Depth of Boring:		<u>2</u> '		Total Depth of Well Completed: NA
Total Depth of Boring:	in Well: NA			Well Screen Type and Diameter: NA
				Well Screen Slot Size: NA
se t	: 16'			Type and Size of Soil Sampler: 2.0" I.D. Macro Sampler
	SOIL/ROC		LE DATA	DESCRIPTION OF LITHOLOGY
BORING DETAIL	Description Interval Blow Counts	OVM (ppmv) Water Level	Graphic Log	standard classification, texture, relative moisture density, stiffness, odor-staining, USCS designation
0	4. 4.	50 600 500 300		Concrete Sandy SILT (ML); dark brown; damp; medium stiff; 70 silt; 30% fine to medium sand; non-plastic; low estimated K; no odor Strong hydrocarbon odor at 6' Clayey SILT (ML); black; moist; very stiff; 60% silt; 40% clay; very low plasticity; very low estimated K; stong hydrocarbon odor Sandy SILT (ML); olive gray; very moist; stiff; 60% silt; 40% fine to coarse sand; non-plastic; medium estimated K; strong hydrocarbon odor; (FILL) wet at 12' Silty SAND (SM); olive gray; saturated; stiff; 70% for to coarse sand; 20% silt; 10% gravel to 0.5" diameter non-plastic; high estimated K; strong hydrocarbon odor (FILL) Sandy SILT (ML); brown; damp; 70% silt; 30% fine to medium sand; non-plastic; low estimated K; slight hydrocarbon odor End of Boring at 16'

Project Name: Compare Prices Project Location: 2844 Mountain Blvd., Oakland, CA Page 1 of 1 Driller: Vironex Type of Rig: Geoprobe Size of Drill: 2.0° Diameter Checked By: Robert E. Kitay, R.G. FF WATER AND WELL DATA Depth of Water First Encountered: 17' Static Depth of Water in Well: NA Total Depth of Boring: 24' BORING DETAIL BORING DETAIL Depth of Water in Well: NA Total Depth of Boring: 24' Soll ROCK SAMPLE DATA Depth of Boring: 24' Type and Size of Soil Sampler: 2.0° I.D. Macro Sampler DESCRIPTION OF LITHOLOGY standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation. Concrete Clayey Sil.T (ML); black; damp; stiff; 70% silt; 25% clay; 5% fine to coarse sand; low estimated K; non-plastic; no odor Clayey Sil.T (ML); olive gray; molst; stiff; 60% silt; 40% clay; low plasticity; very low estimated K; slight hydrocarbon odor Sandy Sil.T (ML); dark brown; moist; stiff; 60% silt; 40% clay; low plasticity; low estimated K; slight hydrocarbon odor Sandy Sil.T (ML); dark brown; moist; stiff; 60% silt; 40% clay; low plasticity; low estimated K; slight hydrocarbon odor Sandy Sil.T (ML); dark brown; moist; stiff; 60% fine to coarse sand; non-plastic; low estimated K; slight hydrocarbon odor Sandy Sil.T (ML); dark brown; moist; stiff; 60% fine to coarse sand; non-plastic; low estimated K; slight hydrocarbon odor Sandy Sil.T (ML); dark brown; moist; stiff; 60% fine to coarse sand; non-plastic; low estimated K; slight hydrocarbon odor Sandy Sil.T (ML); dark brown; moist; stiff; 60% fine to coarse sand; non-plastic; low estimated K; slight hydrocarbon odor Silty SAND (SM); dark brown; moist; stiff; 60% fine to	SOIL BORING LOG AND MONITOR	RING WELI	L COM	APLETION DETAILS BORING: BH-L
Driller: Vironex Logged By: Ian T. Reed Date Drilled: April 19, 2000 Checked By: Robert E. Kitay, R.G. WATER AND WELL DATA Depth of Water First Encountered: 17' Static Depth of Water in Well: NA Total Depth of Boring: 24' Type and Size of Soil Sampler: 2.0" I.D. Macro Sampler DETAIL BORING DETAIL		····		
Logged By: lan T. Reed Date Drilled: April 19, 2000 WATER AND WELL DATA Depth of Water First Encountered: 17' Static Depth of Water in Well: NA Total Depth of Water in Well: NA Total Depth of Boring: 24' Type and Size of Soil Sampler: 2.0* LD. Macro Sampler DESCRIPTION OF LITH-OLOGY standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation. Concrete Clayey SILT (ML); black; damp; stiff, 70% stilt; 25% clay; 5% fine to medium sand; low plasticity; low estimated K; non-plastic; no odor Sandy SILT (ML); light brown; damp; stiff, 70% silt; 30% fine to coarse sand; low estimated K; silght hydrocarbon odor Sandy SILT (ML); olive gray; mild hydrocarbon odor from 10' to 11' Clayey SILT (ML); olive gray; moist; stiff, 60% silt; 40% clay; low plasticity; low estimated K; slight hydrocarbon odor Sandy SILT (ML); olive gray; moist; stiff, 60% silt; 40% clay; low plasticity; low estimated K; slight hydrocarbon odor Sandy SILT (ML); olive gray; moist; stiff, 60% silt; 40% clay; low plasticity; low estimated K; slight hydrocarbon odor Sandy SILT (ML); olive gray; moist; stiff, 60% silt; 40% clay; low plasticity; low estimated K; slight hydrocarbon odor Sandy SILT (ML); olive gray; moist; stiff, 60% silt; 40% clay; slow plasticity; low estimated K; slight hydrocarbon odor Sandy SILT (ML); olive gray; moist; stiff, 60% silt; 40% clay; slow plasticity; low estimated K; slight hydrocarbon odor Sandy SILT (ML); olive gray; moist; stiff, 60% silt; 40% clay; slow plasticity; low estimated K; slight hydrocarbon odor Silty SAND (SM); dark brown; moist; stiff, 60% fine to coarse sand; 40% silt; non-plastic; medium estimated K; no odor End of Boring at 24'				
WATER AND WELL DATA Depth of Water First Encountered: 17' Static Depth of Water In Well: NA Total Depth of Boring: 24' Type and Size of Soil Sampler: 2.0' I.D. Macro Sampler SOIL/ROCK SAMPLE DATA BERING DETAIL BORING DETAIL	_		•	
Depth of Water First Encountered: 17' Well Screen Type and Diameter: NA Static Depth of Water in Well: NA Total Depth of Boring: 24' Type and Size of Soil Sampler: 2.0' I.D. Macro Sampler DESCRIPTION OF LITHOLOGY standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation. Concrete Clayey SILT (ML); black; damp; stiff; 70% silt; 25% clay; 5% fine to coarse sand; low estimated K; non-plastic; no odor Samy SILT (ML); olive gray; moist; stiff; 60% silt; 40% clay; low plasticity; very low estimated K; slight hydrocarbon odor Clayey SILT (ML); olive gray; moist; stiff; 60% silt; 40% clay; low plasticity; very low estimated K; slight hydrocarbon odor Sandy SILT (ML); dark brown; moist; stiff; 60% silt; 40% clay; low plasticity; low estimated K; slight hydrocarbon odor Sandy SILT (ML); dark brown; moist; stiff; 60% silt; 40% fine to coarse sand; non-plastic; low estimated K; slight hydrocarbon odor Sandy SILT (ML); dark brown; moist; stiff; 60% silt; 40% fine to coarse sand; non-plastic; low estimated K; slight hydrocarbon odor Silty CLAY (CL); gray to light brown; moist; stiff; 60% fine to coarse sand; 40% silt; non-plastic; medium estimated K; no odor End of Boring at 24'			Total	
Static Depth of Water in Well: NA Total Depth of Boring: 24' Type and Size of Soil Sampler: 2.0' I.D. Macro Sampler DESCRIPTION OF LITHOLOGY standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation. Concrete Clayey SILT (ML); black; damp; stiff; 70% silt; 25% clay; 5% fine to medium sand; low plasticity; low estimated K; no odor Sandy SILT (ML); light brown; damp; stiff; 70% silt; 30% fine to coarse sand; low estimated K; slight hydrocarbon odor Clayey SILT (ML); olive gray; moist; stiff; 60% silt; 40% clay; low plasticity; very low estimated K; slight hydrocarbon odor Silty CLAY (CL); gray to light brown; moist, stiff; 60% fine to coarse sand; and some plasticity; low estimated K; no odor Silty CLAY (CL); gray to light brown; moist, stiff; 60% fine to coarse sand; how plasticity; low estimated K; no odor Silty CLAY (CL); gray to light brown; moist, stiff; 60% fine to coarse sand; 40% silt; non-plastic; mo odor Silty SAND (SM); dark brown; moist; stiff; 60% fine to coarse sand; 40% silt; non-plastic; medium estimated K; no odor End of Boring at 24'				•
Total Depth of Boring: 24' Type and Size of Soil Sampler: 2.0' I.D. Macro Sampler DESCRIPTION OF LITHOLOGY standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation. O Concrete Clayey SiLT (ML); black; damp; stiff; 70% silt; 25% clay; 5% fine to medium sand; low plasticity; low estimated K; no odor 18 13 13 15 Clayey SiLT (ML); light brown; damp; stiff; 70% silt; 25% clay; 5% fine to coarse sand; low estimated K; non-plastic; no odor Clayey SiLT (ML); light brown; damp; stiff; 70% silt; 30% fine to coarse sand; low estimated K; slight hydrocarbon odor Clayey SiLT (ML); olive gray; mild hydrocarbon odor from 10' to 11' Clayey SiLT (ML); olive gray; moist; stiff; 60% silt; 40% clay; low plasticity; very low estimated K; slight hydrocarbon odor Sandy SiLT (ML); olive gray; moist; stiff; 60% silt; 40% fine to coarse sand; non-plastic; low estimated K; slight hydrocarbon odor Sandy SiLT (ML); olive gray; moist; stiff; 60% silt; 40% fine to coarse sand; non-plastic; low estimated K; slight hydrocarbon odor Sandy SiLT (ML); olive gray; moist; stiff; 60% silt; 40% fine to coarse sand; non-plastic; low estimated K; slight hydrocarbon odor Sandy SiLT (ML); olive gray; moist; stiff; 60% silt; 40% fine to coarse sand; non-plastic; low estimated K; slight hydrocarbon odor Sandy SiLT (ML); olive gray; moist; stiff; 60% silt; 40% fine to coarse sand; non-plastic; low estimated K; slight hydrocarbon odor Sandy SiLT (ML); olive gray; moist; stiff; 60% silt; 40% fine to coarse sand; non-plastic; low estimated K; slight hydrocarbon odor End of Boring at 24'	Static Depth of Water in Well: NA			
DESCRIPTION OF LITHOLOGY standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation. Concrete Clayey SiLT (ML); black; damp; stiff; 70% silt; 25% clay; 5% fine to medium sand; low plasticity; low estimated K; non-plastic; no odor Sandy SiLT (ML); light brown; damp; stiff; 70% silt; 25% clay; 5% fine to coarse sand; low estimated K; non-plastic; no odor Clayey SiLT (ML); light brown; damp; stiff; 70% silt; 25% clay; 5% fine to coarse sand; low estimated K; non-plastic; no odor Clayey SiLT (ML); light brown; damp; stiff; 70% silt; 40% clay; low plasticity; very low estimated K; slight hydrocarbon odor Sandy SiLT (ML); light brown; moist; stiff; 60% silt; 40% clay; low plasticity; very low estimated K; slight hydrocarbon odor Sandy SiLT (ML); light brown; moist; stiff; 60% silt; 40% fine to coarse sand; non-plastic; low estimated K; slight hydrocarbon odor Sandy SiLT (ML); light brown; moist; stiff; 60% silt; 40% fine to coarse sand; non-plastic; low estimated K; slight hydrocarbon odor Sandy SiLT (ML); light brown; moist; stiff; 60% silt; 40% fine to coarse sand; non-plastic; low estimated K; slight hydrocarbon odor Sandy SiLT (ML); light brown; moist; stiff; 60% silt; 40% fine to coarse sand; non-plastic; low estimated K; slight hydrocarbon odor Sandy SiLT (ML); light brown; moist; stiff; 60% silt; 40% fine to coarse sand; non-plastic; medium estimated K; slight hydrocarbon odor End of Boring at 24'			Туре	and Size of Soil Sampler: 2.0" I.D. Macro Sampler
SORING DETAIL THE	lan manua.	MPLE DATA	te e	DESCRIPTION OF LITHOLOGY
Clayey SiLT (ML); black; damp; stiff; 70% silt; 25% clay; 5% fine to medium sand; low plasticity; low estimated K; no odor Sandy SiLT (ML); light brown; damp; stiff; 70% silt; 30% fine to coarse sand; low estimated K; non-plastic; no odor olive gray; mild hydrocarbon odor from 10' to 11' Clayey SiLT (ML); light brown; damp; stiff; 70% silt; 30% fine to coarse sand; low estimated K; non-plastic; no odor Clayey SiLT (ML); light brown; damp; stiff; 60% silt; 40% clay; low plasticity; very low estimated K; slight hydrocarbon odor Sandy SiLT (ML); olive gray; moist; stiff; 60% silt; 40% fine to coarse sand; non-plastic; low estimated K; slight hydrocarbon odor Silty CLAY (CL); gray to light brown; moist; stiff; 70% clay; 30% silt; low plasticity; low estimated K; no odor Silty SAND (SM); dark brown; moist; stiff; 60% fine to coarse sand; 40% silt; non-plastic; medium estimated K; no odor End of Boring at 24'	Depth in Fe TIVE SAINOR Description Interval Blow Counts OVM (ppmv)	Water Level Graphic Log	Depth in Fe	standard classification, texture, relative moisture,
	The state of the s	▼ i	- 5 - 5 - 10 - 15 - 20 - 25 - 25	Clayey SILT (ML); black; damp; stiff; 70% silt; 25% clay; 5% fine to medium sand; low plasticity; low estimated K; no odor Sandy SILT (ML); light brown; damp; stiff; 70% silt; 30% fine to coarse sand; low estimated K; non-plastic; no odor olive gray; mild hydrocarbon odor from 10' to 11' Clayey SILT (ML); olive gray; moist; stiff; 60% silt; 40% clay; low plasticity; very low estimated K; slight hydrocarbon odor Sandy SILT (ML); dark brown; moist; stiff; 60% silt; 40% fine to coarse sand; non-plastic; low estimated K; slight hydrocarbon odor Silty CLAY (CL); gray to light brown; moist; stiff; 70% clay; 30% silt; low plasticity; low estimated K; no odor Silty SAND (SM); dark brown; moist; stiff; 60% fine to coarse sand; 40% silt; non-plastic; medium estimated K; no odor

Total Depth of Water First Encountered: 17' Static Depth of Water First Encountered: 17' Static Depth of Boring: 24' Total Depth of Boring: 24' Soll/ROCK SAMPLE DATA BORING DETAIL Soll/ROCK SAMPLE DATA GO COncrete Sandy SILT (ML); light brown; moist; stiff; 60% fine coarse sand; 10% clay; low plasticity; loe estimated K; no odor Silty SAND (SM); light brown; moist; stiff; 60% silt; 30% fine to coarse sand; 10% clay; low plasticity; loe estimated K; no odor Sandy SILT (ML); light brown; moist; stiff; 60% silt; 30% fine to coarse sand; 10% clay; low plasticity; loe estimated K; no odor Sandy SILT (ML); light brown; moist; stiff; 60% silt; 30% fine to coarse sand; 10% clay; low plasticity; loe estimated K; no odor Sandy SILT (ML); light brown; moist; stiff; 60% silt; 30% fine to coarse sand; 10% clay; low plasticity; loe estimated K; no odor Sandy SILT (ML); light brown; moist; stiff; 60% silt; 30% fine to coarse sand; 10% clay; low plasticity; loe estimated K; no odor Sandy SILT (ML); light brown; moist; stiff; 60% silt; 30% fine to coarse sand; 10% clay; low plasticity; loe estimated K; no odor Sandy SILT (ML); light brown; moist; stiff; 60% silt; 30% fine to coarse sand; 10% clay; low plasticity; loe estimated K; no odor	SOIL BORING LOG AND MONI	TORING WELL	L COMPLETION DETAILS BORING: BH-M
Date Drilled: April 19, 2000 Checked By: Robert E. Kitay, R.G. WATER AND WELL DATA Depth of Water First Encountered: 17' Well Screen Type and Diameter: NA Static Depth of Water in Well: NA Total Depth of Boring: 24' BORING DETAIL DETAIL DETAIL DETAIL DESCRIPTION OF LITHOLOGY standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation Concrete Sandy SILT (ML); light brown to dark brown; damp; s 70% slit; 30% fine to coarse sand; non-plastic; low estimated K; no odor Silty SAND (SM); light brown; moist; stiff, 60% fine coarse sand; 10% clay; low plasticity; lo estimated K; no odor Wet at 17' saturated at 20'	Project Name: Compare Prices	Project Location	on: 2844 Mountain Blvd., Oakland, CA Page 1 of 1
Total Depth of Water First Encountered: 17' Static Depth of Water First Encountered: 17' Static Depth of Boring: 24' Total Depth of Boring: 24' Soll/ROCK SAMPLE DATA BORING DETAIL Soll/ROCK SAMPLE DATA GO COncrete Sandy SILT (ML); light brown; moist; stiff; 60% fine coarse sand; 10% clay; low plasticity; loe estimated K; no odor Silty SAND (SM); light brown; moist; stiff; 60% silt; 30% fine to coarse sand; 10% clay; low plasticity; loe estimated K; no odor Sandy SILT (ML); light brown; moist; stiff; 60% silt; 30% fine to coarse sand; 10% clay; low plasticity; loe estimated K; no odor Sandy SILT (ML); light brown; moist; stiff; 60% silt; 30% fine to coarse sand; 10% clay; low plasticity; loe estimated K; no odor Sandy SILT (ML); light brown; moist; stiff; 60% silt; 30% fine to coarse sand; 10% clay; low plasticity; loe estimated K; no odor Sandy SILT (ML); light brown; moist; stiff; 60% silt; 30% fine to coarse sand; 10% clay; low plasticity; loe estimated K; no odor Sandy SILT (ML); light brown; moist; stiff; 60% silt; 30% fine to coarse sand; 10% clay; low plasticity; loe estimated K; no odor Sandy SILT (ML); light brown; moist; stiff; 60% silt; 30% fine to coarse sand; 10% clay; low plasticity; loe estimated K; no odor	Driller: Vironex	Type of Rig: G	
Depth of Water First Encountered: 17' Static Depth of Water in Well: NA Total Depth of Boring: 24' SOIL/ROCK SAMPLE DATA SOIL/ROCK SAMPLE DATA Go Go Go Go Go Go Go G	Logged By: Ian T. Reed	Date Drilled:	April 19, 2000 Checked By: Robert E. Kitay, R.G.
Static Depth of Water in Well: NA Total Depth of Boring: 24' Total Depth of Boring: 24' BORING DETAIL DESCRIPTION OF LITHOLOGY standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation Concrete Sandy SiLT (ML); light brown; moist; stiff; 60% fine coarse sand; non-plastic; low estimated K; no odor Sandy SiLT (ML); light brown; moist; stiff; 60% silt; 30% fine to coarse sand; 10% clay; low plasticity; loestimated K; no odor Sandy SiLT (ML); light brown; moist; stiff; 60% silt; 30% fine to coarse sand; 10% clay; low plasticity; loestimated K; no odor Sandy SiLT (ML); light brown; moist; stiff; 60% silt; 30% fine to coarse sand; 10% clay; low plasticity; loestimated K; no odor Sandy SiLT (ML); light brown; moist; stiff; 60% silt; 30% fine to coarse sand; 10% clay; low plasticity; loestimated K; no odor saturated at 20'	WATER AND WELL DATA		Total Depth of Well Completed: NA
Total Depth of Boring: 24 Type and Size of Soil Sampler: 2.0" I.D. Macro Sampler DESCRIPTION OF LITHOLOGY standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation Concrete Sandy SiLT (ML); light brown; moist; stiff; 60% fine to coarse sand; non-plastic; low estimated K; no odor Trace gravel to 0.5" diameter Sity SAND (SM); light brown; moist; stiff; 60% fine coarse sand; non-plastic; medium estimated K; no odor Sandy SiLT (ML); light brown; moist; stiff; 60% silt; 30% fine to coarse sand; 10% clay; low plasticity; loestimated K; no odor Sandy SiLT (ML); light brown; moist; stiff; 60% silt; 30% fine to coarse sand; 10% clay; low plasticity; loestimated K; no odor saturated at 20'	Depth of Water First Encountered: 17	'I	Well Screen Type and Diameter: NA
SOIL/ROCK SAMPLE DATA Soil/ROCK SAMPLE DATA Soil/ROCK SAMPLE DATA The standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation Concrete Sandy SILT (ML); light brown to dark brown; damp; s 70% silt; 30% fine to coarse sand; non-plastic; low estimated K; no odor Soil/ROCK SAMPLE DATA The standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation Concrete Sandy SILT (ML); light brown to dark brown; damp; s 70% silt; 30% fine to coarse sand; non-plastic; low estimated K; no odor Soilty SAND (SM); light brown; moist; stiff; 60% silt; 30% fine to coarse sand; 10% clay; low plasticity; loestimated K; no odor Sandy SILT (ML); light brown; moist; stiff; 60% silt; 30% fine to coarse sand; 10% clay; low plasticity; loestimated K; no odor saturated at 20'	Static Depth of Water in Well: NA		Well Screen Slot Size: NA
BORING DETAIL Standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation Concrete Sandy SILT (ML); light brown to dark brown; damp; some stimated K; no odor Silty SAND (SM); light brown; moist; stiff; 60% fine coarse sand; 40% silt; non-plastic; medium estimated K; no odor Silty SAND (SM); light brown; moist; stiff; 60% fine coarse sand; 10% clay; low plasticity; low estimated K; no odor Sandy SILT (ML); light brown; moist; stiff; 60% silt; 30% fine to coarse sand; 10% clay; low plasticity; low estimated K; no odor Sandy SILT (ML); light brown; moist; stiff; 60% silt; 30% fine to coarse sand; 10% clay; low plasticity; low estimated K; no odor Sandy SILT (ML); light brown; moist; stiff; 60% silt; 30% fine to coarse sand; 10% clay; low plasticity; low estimated K; no odor Sandy SILT (ML); light brown; moist; stiff; 60% silt; 30% fine to coarse sand; 10% clay; low plasticity; low estimated K; no odor Sandy SILT (ML); light brown; moist; stiff; 60% silt; 30% fine to coarse sand; 10% clay; low plasticity; low estimated K; no odor Sandy SILT (ML); light brown; moist; stiff; 60% silt; 30% fine to coarse sand; 10% clay; low plasticity; low estimated K; no odor	Total Depth of Boring: 24'		Type and Size of Soil Sampler: 2.0" I.D. Macro Sampler
Standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation Concrete Sandy SILT (ML); light brown to dark brown; damp; s 70% silt; 30% fine to coarse sand; non-plastic; low estimated K; no odor Silty SAND (SM); light brown; moist; stiff; 60% fine coarse sand; 40% silt; non-plastic; medium estimated K; no odor Sandy SILT (ML); light brown; moist; stiff; 60% fine coarse sand; 40% silt; non-plastic; medium estimated K; no odor Sandy SILT (ML); light brown; moist; stiff; 60% silt; no odor sandy SILT (ML); light brown; moist; stiff; 60% silt; 30% fine to coarse sand; 10% clay; low plasticity; loe estimated K; no odor saturated at 20'			DESCRIPTION OF LITHOLOGY
Sandy SILT (ML); light brown to dark brown; damp; s 70% silt; 30% fine to coarse sand; non-plastic; low estimated K; no odor 10 10 15 15 15 15 16 17 18 19 10 20 20 20 20 20 20 20 20 20	Descriptio Interval Blow Count	Ovim (ppim) Water Leve Graphic Log	standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation.
-30 -30			Sandy SILT (ML); light brown to dark brown; damp; stiff; 70% silt; 30% fine to coarse sand; non-plastic; low estimated K; no odor 10 Silty SAND (SM); light brown; moist; stiff; 60% fine to coarse sand; 40% silt; non-plastic; medium estimated K; no odor Sandy SILT (ML); light brown; moist; stiff; 60% silt; 30% fine to coarse sand; 10% clay; low plasticity; low estimated K; no odor wet at 17' saturated at 20' End of Boring at 24'

APPENDIX D

Certified Analytical Report and Chain of Custody Documentation Soil Samples Environmental Services (SDB)

Submission #: 2000-04-0331

Date: April 25, 2000

Aqua Science Engineers, Inc. 208 West El Pintado Road Danville, CA 94526

Attn.: Mr. lan T. Reed

Project: 3538

Compare Prices-Shahnazi

Dear Mr. Reed,

Attached is our report for your samples received on Thursday April 20, 2000 This report has been reviewed and approved for release. Reproduction of this report is permitted only in its entirety.

Please note that any unused portion of the samples will be discarded after May 20, 2000 unless you have requested otherwise. We appreciate the opportunity to be of service to you. If you have any questions, please call me at (925) 484-1919. You can also contact me via email. My email address is: vvancil@chromalab.com

Sincerely,

Vincent Vancil

Environmental Services (SDB)

Gas/BTEX and MTBE

Aqua Science Engineers, Inc.

208 West El Pintado Road

Danville, CA 94526

Attn: Ian T. Reed

Phone: (925) 820-9391 Fax: (925) 837-4853

Project #: 3538

Project: Compare Prices-Shahnazi

Samples Reported

Sample ID	Matrix	Date Sampled	Lab#
8H-F-19`	Soil	04/18/2000	2
BH-H-11.5'	Soil	04/18/2000	4 -
BH-I-15.5	Soil	04/19/2000	5
BH-L-11.5`	Soil	04/19/2000	8
BH-M-11.5	Soil	04/19/2000	9

Submission #: 2000-04-0331

Environmental Services (SDB)

Aqua Science Engineers, Inc. To:

Test Method:

8020 8015M

Attn.: Ian T. Reed

Prep Method:

5030

Gas/BTEX and MTBE

Sample ID:

BH-F-19"

Lab Sample ID: 2000-04-0331-002

Project:

3538

Received:

04/20/2000 18:12

Compare Prices-Shahnazi

Extracted:

04/21/2000 12:37

Sampled:

04/18/2000

QC-Batch:

2000/04/21-01.02

Matrix:

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Gasoline	ND	1,0	mg/Kg	1.00	04/21/2000 12:37	
Benzene	ND	0.0050	mg/Kg	1.00	04/21/2000 12:37	
Toluene	ND	0.0050	mg/Kg	1.00	04/21/2000 12:37	
Ethyl benzene	ND	0.0050	mg/Kg	1.00	04/21/2000 12:37	
Xylene(s)	ND	0.0050	mg/Kg	1,00	04/21/2000 12:37	
MTBE	ND	0.0050	mg/Kg	1.00	04/21/2000 12:37	
Surrogate(s)						
Trifluorotoluene	104.8	53-125	%	1.00	04/21/2000 12:37	
4-Bromofluorobenzene-FID	88.6	58-124	%	1.00	04/21/2000 12:37	

Submission #: 2000-04-0331

Environmental Services (SDB)

Aqua Science Engineers, Inc. To:

Test Method:

8020 8015M

Attn.: Ian T. Reed

Prep Method:

5030

Gas/BTEX and MTBE

Sample ID:

BH-H-11.5°

Lab Sample ID: 2000-04-0331-004

Project:

3538

Received:

04/20/2000 18:12

Compare Prices-Shahnazi

Extracted:

04/21/2000 13:08

Sampled:

04/18/2000

QC-Batch:

2000/04/21-01.02

Matrix:

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Gasoline	8.5	1.0	mg/Kg	1.00	04/21/2000 13:08	
Benzene	0.13	0.0050	mg/Kg	1.00	04/21/2000 13:08	
Toluene	ND	0.0050	mg/Kg	1.00	04/21/2000 13:08	
Ethyl benzene	0.14	0.0050	mg/Kg	1.00	04/21/2000 13:08	
Xylene(s)	0.15	0.0050	mg/Kg	1.00	04/21/2000 13:08	
MTBE	0.065	0.0050	mg/Kg	1.00	04/21/2000 13:08	
Surrogate(s)	Ì					
4-Bromofluorobenzene	97.6	58-124	%	1.00	04/21/2000 13:08	
4-Bromofluorobenzene-FID	129.3	58-124	%	1.00	04/21/2000 13:08	sh

Submission #: 2000-04-0331

Environmental Services (SDB)

Aqua Science Engineers, Inc. To:

Test Method:

8020 8015M

Attn.: Ian T. Reed

Prep Method:

5030

Gas/BTEX and MTBE

Sample ID:

BH-I-15.5

Lab Sample ID: 2000-04-0331-005

Project:

3538

Received:

04/20/2000 18:12

Compare Prices-Shahnazi

Extracted:

04/21/2000 13:39

Sampled:

04/19/2000

QC-Batch:

2000/04/21-01.02

Matrix:

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Gasoline	ND	1.0	mg/Kg	1.00	04/21/2000 13:39	
Benzene	ND	0.0050	mg/Kg	1.00	04/21/2000 13:39	
Toluene	ND	0.0050	mg/Kg	1.00	04/21/2000 13:39	
Ethyl benzene	ND	0.0050	mg/Kg	1.00	04/21/2000 13:39	
Xylene(s)	ND	0.0050	mg/Kg	1.00	04/21/2000 13:39	
MTBE	0.019	0.0050	mg/Kg	1.00	04/21/2000 13:39	
Surrogate(s)						
Trifluorotoluene	70.3	53-125	%	1.00	04/21/2000 13:39	
Trifluorotoluene-FID	66.9	53-125	. %	1.00	04/21/2000 13:39	

Submission #: 2000-04-0331

Environmental Services (SDB)

Aqua Science Engineers, Inc. To:

Test Method:

8020 8015M

Attn.: Ian T. Reed

Prep Method:

5030

Gas/BTEX and MTBE

Sample ID:

BH-L-11.5`

Lab Sample ID: 2000-04-0331-008

Project:

3538

04/20/2000 18:12

Received:

Compare Prices-Shahnazi

Extracted:

04/24/2000 10:27

Sampled:

04/19/2000

QC-Batch:

2000/04/24-01.02

Matrix:

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Gasoline	2.1	1.0	mg/Kg	1.00	04/24/2000 10:27	g
Benzene	ND	0.0050	mg/Kg	1.00	04/24/2000 10:27	
Toluene	ND	0.0050	mg/Kg	1.00	04/24/2000 10:27	
Ethyl benzene	ND	0.0050	mg/Kg	1.00	04/24/2000 10:27	
Xylene(s)	ND	0.0050	mg/Kg	1.00	04/24/2000 10:27	
MTBE	0.014	0.0050	mg/Kg	1.00	04/24/2000 10:27	
Surrogate(s)						
Trifluorotoluene	90.3	53-125	%	1.00	04/24/2000 10:27	
Trifluorotoluene-FID	68.5	53-125	%	1.00	04/24/2000 10:27	

Submission #: 2000-04-0331

Environmental Services (SDB)

Aqua Science Engineers, Inc. To:

Test Method:

8020 8015M

Attn.: Ian T. Reed

Prep Method:

5030

Gas/BTEX and MTBE

Sample ID:

BH-M-11.5

Lab Sample ID: 2000-04-0331-009

Project:

3538

Received:

04/20/2000 18:12

Compare Prices-Shahnazi

Extracted:

04/21/2000 16:48

Sampled:

04/19/2000

QC-Batch:

2000/04/21-01.02

Matrix:

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Gasoline	ND	1.0	mg/Kg	1.00	04/21/2000 16:48	
Benzene	ND	0.0050	mg/Kg	1.00	04/21/2000 16:48	
Toluene	ND	0.0050	mg/Kg	1.00	04/21/2000 16:48	
Ethyl benzene	ND	0.0050	mg/Kg	1.00	04/21/2000 16:48	
Xylene(s)	ND	0.0050	mg/Kg	1,00	04/21/2000 16:48	
MTBE	ND	0.0050	mg/Kg	1.00	04/21/2000 16:48	
Surrogate(s)					.	
Trifluorotoluene	79.6	53-125	%	1.00	04/21/2000 16:48	
Trifluorotoluene-FID	60.1	53-125	%	1.00	04/21/2000 16:48	

Submission #: 2000-04-0331

Environmental Services (SDB)

2000/04/21-01.02-001

To: Aqua Science Engineers, Inc.

Test Method:

8020

Prep Method:

8015M 5030

Attn.: Ian T. Reed

MB:

Batch QC Report Gas/BTEX and MTBE

Soil

Method Blank

QC Batch # 2000/04/21-01.02

Date Extracted: 04/21/2000 06:41

Compound	Result	Rep.Limit	Units	Analyzed	Flag
Gasoline	ND	1.0	mg/Kg	04/21/2000 06:41	
Benzene	ND	0.0050	mg/Kg	04/21/2000 06:41	
Toluene	ND	0.0050	mg/Kg	04/21/2000 06:41	
Ethyl benzene	ND	0.0050	mg/Kg	04/21/2000 06:41	
Xylene(s)	ND	0.0050	mg/Kg	04/21/2000 06:41	
MTBE	ND	0.0050	mg/Kg	04/21/2000 06:41	
Surrogate(s) Trifluorotoluene 4-Bromofluorobenzene-FID	97.8 102.8	53-125 58-124	% %	04/21/2000 06:41 04/21/2000 06:41	

Submission #: 2000-04-0331

CHROMALAB, INC.

Environmental Services (SDB)

Aqua Science Engineers, Inc. To:

Test Method:

8020 8015M

Attn.: lan T. Reed

Prep Method:

5030

Batch QC Report Gas/BTEX and MTBE

Method Blank

Soil

QC Batch # 2000/04/24-01.02

MB:

2000/04/24-01.02-001

Date Extracted: 04/24/2000 06:35

Communication	Result	Rep.Limit	Units	Analyzed	Flag
Compound Gasoline Benzene Toluene Ethyl benzene Xylene(s) MTBE	ND ND ND ND ND ND	1.0 0.0050 0.0050 0.0050 0.0050 0.0050	mg/Kg mg/Kg mg/Kg mg/Kg mg/Kg mg/Kg	04/24/2000 06:35 04/24/2000 06:35 04/24/2000 06:35 04/24/2000 06:35 04/24/2000 06:35 04/24/2000 06:35	
Surrogate(s) Trifluorotoluene 4-Bromofluorobenzene-FID	108.0 100.2	53-125 58-124	%	04/24/2000 06:35 04/24/2000 06:35	

Submission #: 2000-04-0331

Environmental Services (SDB)

Aqua Science Engineers, Inc. To:

8020 Test Method:

8015M

Attn: lan T. Reed

Prep Method:

5030

Batch QC Report

Gas/BTEX and MTBE

Laboratory Control Spike (LCS/LCSD)

Soil

QC Batch # 2000/04/24-01.02

LCS:

2000/04/24-01.02-002

Extracted: 04/24/2000 07:06

Analyzed

04/24/2000 07:06

2000/04/24-01.02-003 LCSD:

Extracted: 04/24/2000 07:37

Analyzed

04/24/2000 07:37

Compound	Conc.	[mg/Kg]	Exp.Conc.	[mg/Kg]	Recov	ery [%]	RPD	Ctrl. Limi	ts [%]	Flag	gs
,	LCS	LCSD	LCS	LCSD	LCS	LCSD	[%]	Recovery	RPD	LCS	LCSD
Gasoline	0.466	0.463	0.500	0.500	93.2	92.6	0.6	75-125	35		
	0.0995	0.0929	0.1000	0.1000	99.5	92.9	6.9	77-123	35		
Toluene	0.0954	0.0925	0.1000	0.1000	95.4	92.5	3.1	78-122	35		-
Ethyl benzene	0.0928	0.0924	0.1000	0.1000	92.8	92.4	0.4	70-130	35	i I	
Xylene(s)	0,276	0.276	0.300	0.300	92.0	92.0	0.0	75-125	35		ļ
Surrogate(s)			! 	İ			Ì		<u> </u> !	1	1
	: : 481	446	500	500	96.2	89.2	ļ	53-125	:		
4-Bromofluorobenzene-Fl	. 520	503	500	500	104.0	100.6	ĺ	58-124		į	

Environmental Services (SDB)

Aqua Science Engineers, Inc.

Test Method: 8020

Submission #: 2000-04-0331

8015M

Prep Method: 5030

Attn.: Ian T. Reed

Batch QC Report

Gas/BTEX and MTBE

Soil

Matrix Spike (MS / MSD)

QC Batch # 2000/04/21-01.02

Lab Sample ID: 2000-04-0331-009

Sample ID: BH-M-11.5

2000/04/21-01.02-004 Extracted: 04/21/2000 17:19 Analyzed: 04/21/2000 17:19 Dilution: 1.0

MS: 2000/04/21-01.02-005Extracted: 04/21/2000 17:51 Analyzed: 04/21/2000 17:51 Dilution: 1.0 MSD:

Compound	iConc.	ſ'n	ig/Kg]	Exp.Conc.	[mg/Kg]	Recov	ery [%]	RPD	Ctd. Limi	ts [%]	FI	ags
Compound	MS	MSD	Sample	MS	MSD	MS	MSD		Recovery	RPD	MS	MSD
Gasoline	0.277	0.323	ND	0.437	0.478	63.4	67.6	6.4	65-135	35	mso	1
	0.0591	0.0660	ND	0.0874	0.0956	67.6	69.0	2.0	65-135	35		1
Benzene	0.0586	0.0669	ND	0.0874	0.0956	67.0	70.0	4.4	65-135	35		i
Toluene	0.0580	0.0686	ND	0.0874	0.0956	66.4	71.8	7.8	65-135	35		
Ethyl benzene Xylene(s)	0.170	0.202	ND	0.262	0.287	64.9	70.4	8.1	65-135	35	mso	1
Surrogate(s)					555	70.0	74.6	:	53-125			1
Trifluorotoluene	354	373	İ	500	500	70.8				İ	!	
Trifluorotoluene-FID	372	313		500	500	74.4	62.6		53-125		<u> </u>	<u> </u>

Printed on: 04/25/2000 13:10

Page 11 of 12

To: Aqua Science Engineers, Inc.

Environmental Services (SDB)

Test Method: 8015M

8020

Submission #: 2000-04-0331

Attn:lan T. Reed

Prep Method: 5030

Legend & Notes

Gas/BTEX and MTBE

QC Compound Flags

mso

MS/MSD spike recoveries were out of QC limits due to matrix interference. Precision and

Accuracy were verified by LCS/LCSD.

Analyte Flags

Hydrocarbon reported in the gasoline range does not match our gasoline standard.

sh

Surrogate recoveries were higher than QC limits due to matrix interference.

1220 Quarry Lane * Pleasanton, CA 94566-4756 Telephone: (925) 484-1919 * Facsimile: (925) 484-1096

Printed on: 04/25/2000 13:10

CHROMALAB, INC. Environmental Services (SDB)

Gas/BTEX (Methanol Extraction)

Aqua Science Engineers, Inc.

Danville, CA 94526

Attn: Ian T. Reed

Phone: (925) 820-9391 Fax: (925) 837-4853

Project #: 3538

Project: Compare Prices-Shahnazi

Samples Reported

Sample ID	Matrix	Date Sampled	Lab#
BH-E-18`	Soil	04/18/2000	1
BH-G-11.5	Soil	04/18/2000	3
BH-J-10	Soil	04/19/2000	6
BH-K-10`	Soil	04/19/2000	7

Submission #: 2000-04-0331

Environmental Services (SDB)

Aqua Science Engineers, Inc. To:

Test Method:

8020 8015M

Attn.: Ian T. Reed

Prep Method:

5030

Gas/BTEX (Methanol Extraction)

Sample ID:

BH-E-18`

Lab Sample ID: 2000-04-0331-001

Project:

3538

Received:

04/20/2000 18:12

Compare Prices-Shahnazi

Extracted:

04/21/2000 23:32

Sampled:

04/18/2000

QC-Batch:

2000/04/21-05.02

Matrix:

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Gasoline	13	10	mg/Kg	1.00	04/21/2000 23:32	
Benzene	ND	0.62	mg/Kg	1.00	04/21/2000 23:32	
Toluene	ND	0.62	mg/Kg	1.00	04/21/2000 23:32	
Ethyl benzene	ND	0.62	mg/Kg	1.00	04/21/2000 23:32	
Xylene(s)	1.0	0,62	mg/Kg	1.00	04/21/2000 23:32	
MTBE	ND	0.62	mg/Kg	1.00	04/21/2000 23:32	
Surrogate(s)	!		:			
Trifluorotoluene	100.2	53-125	%	1.00	04/21/2000 23:32	
4-Bromofluorobenzene-FID	105.7	58-124	%	1.00	04/21/2000 23:32	

Environmental Services (SDB)

Aqua Science Engineers, Inc.

Test Method:

8020

Submission #: 2000-04-0331

8015M

Prep Method:

5030

Attn.: Ian T. Reed

To:

Gas/BTEX (Methanol Extraction)

Sample ID:

BH-G-11.5`

Lab Sample ID: 2000-04-0331-003

Project:

3538

Received:

04/20/2000 18:12

Compare Prices-Shahnazi

Extracted:

04/21/2000 00:04

Sampled:

04/18/2000

QC-Batch:

2000/04/21-05.02

Matrix:

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Gasoline	16	10	mg/Kg	1.00	04/22/2000 00:04	g
Benzene	ND	0.62	mg/Kg	1.00	04/22/2000 00:04	
Toluene	ND	0.62	mg/Kg	1.00	04/22/2000 00:04	
Ethyl benzene	ND	0.62	mg/Kg	1.00	04/22/2000 00:04	
Xylene(s)	ND	0.62	mg/Kg	1.00	04/22/2000 00:04	
MTBE	20	0.62	mg/Kg	1.00	04/22/2000 00:04	
Surrogate(s) Trifluorotoluene	99.6	53-125	%	1.00	04/22/2000 00:04	
4-Bromofluorobenzene-FID	104.4	58-124	%	1.00	04/22/2000 00:04	

Submission #: 2000-04-0331

Environmental Services (SDB)

Aqua Science Engineers, Inc. To:

Test Method:

8020 8015M

Attn.: Ian T. Reed

Prep Method:

5030

Gas/BTEX (Methanol Extraction)

Sample ID:

BH-J-10'

Lab Sample ID: 2000-04-0331-006

Project:

04/20/2000 18:12

Received:

3538 Compare Prices-Shahnazi

Extracted:

04/21/2000 11:23

Sampled:

04/19/2000

QC-Batch:

2000/04/21-05.02

Matrix:

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Gasoline	230	20	mg/Kg	2.00	04/25/2000 11:23	g
Benzene	ND	1,2	mg/Kg	2.00	04/25/2000 11:23	
Toluene	ND	1.2	. mg/Kg	2.00	04/25/2000 11:23	
Ethyl benzene	ND	1.2	mg/Kg	2.00	04/25/2000 11:23	
Xylene(s)	ND	1.2	mg/Kg	2.00	04/25/2000 11:23	
MTBE	35	1.2	mg/Kg	2.00	04/25/2000 11:23	
Surrogate(s)	i i					
Trifluorotoluene	NA	53-125	%	1.00	04/25/2000 11:23	
4-Bromofluorobenzene-FID	NA	58-124	₁ mg/Kg	1.00	04/25/2000 11:23	sh

Submission #: 2000-04-0331

Environmental Services (SDB)

Aqua Science Engineers, Inc. To:

Test Method:

8020

8015M

Attn.: Ian T. Reed

Prep Method:

5030

Gas/BTEX (Methanol Extraction)

Rep.Limit

50

3.1

3.1

3.1

3.1

3.1

53-125

58-124

Sample ID:

BH-K-10°

Lab Sample ID: 2000-04-0331-007

Project:

3538

Compare Prices-Shahnazi

Result

730

ND

ND

14

79

20

NA

NA

Received:

04/20/2000 18:12

Sampled:

04/19/2000

Extracted: QC-Batch:

1.00

1.00

mg/Kg

mg/Kg

04/21/2000 11:54 2000/04/21-05.02

Matrix:

Compound

Gasoline

Benzene

Toluene

Xylene(s)

MTBE

Ethyl benzene

Surrogate(s)

Trifluorotoluene

4-Bromofluorobenzene-FID

Soil

Units	Dilution	Analyzed	Flag
mg/Kg	5.00	04/25/2000 11:54	
mg/Kg	5.00	04/25/2000 11:54	
mg/Kg	5.00	04/25/2000 11:54	
mg/Kg	5.00	04/25/2000 11:54	
mg/Kg	5.00	04/25/2000 11:54	
mg/Kg	5.00	04/25/2000 11:54	

04/25/2000 11:54

04/25/2000 11:54

sh

sh

Submission #: 2000-04-0331

Environmental Services (SDB)

To: Aqua Science Engineers, Inc.

Test Method:

8020

8015M

Attn.: Ian T. Reed

MB:

Prep Method:

t: 5030

Batch QC Report
Gas/BTEX (Methanol Extraction)

Soil

Method Blank

2000/04/21-05.02-001

QC Batch # 2000/04/21-05.02

Date Extracted: 04/21/2000 19:55

Compound	Result	Rep.Limit	Units	Analyzed	Flag
Gasoline	ND	10	mg/Kg	04/21/2000 19:55	
Benzene	ND	0.62	mg/Kg	04/21/2000 19:55	
Toluene	ND	0.62	mg/Kg	04/21/2000 19:55	
Ethyl benzene	ND	0.62	mg/Kg	04/21/2000 19:55	
Xylene(s)	ND	:0.62	mg/Kg	04/21/2000 19:55	
MTBE	ND	0.62	mg/Kg	04/21/2000 19:55	
Surrogate(s)		ļ			
Trifiuorotoluene	64.6	53-125	%	04/21/2000 19:55	
4-Bromofluorobenzene-FID	98.2	58-124	%	04/21/2000 19:55	

Submission #: 2000-04-0331

Environmental Services (SDB)

To: Aqua Science Engineers, Inc.

Test Method:

8020

8015M

Attn: Ian T. Reed

Prep Method:

5030

Batch QC Report

Gas/BTEX (Methanol Extraction)

Laboratory Control Spike (LCS/LCSD)

Soil

QC Batch # 2000/04/21-05.02

LCS:

2000/04/21-05.02-002

Extracted: 04/21/2000 20:26

Analyzed

04/21/2000 20:26

LCSD: 20

2000/04/21-05.02-003

Extracted: 04/21/2000 20:57

Analyzed

04/21/2000 20:57

Compound	Conc.	[mg/Kg]	Exp.Conc.	[mg/Kg]	Recov	ery [%]	RPD	Ctrl. Lim	its [%]	Flag	gs
,	LCS	LCSD	LCS	LCSD	LCS	LCSD	[%]	Recovery	RPD	LCS	LCSD
Gasoline	0.700	0.781	0.625	0.625	112.0	125.0	11.0	75-125	35		
Benzene	0.127	0.116	0.125	0.125	101.6	92.8	9.1	77-123	35		
Toluene	0.137	0.126	0.125	0.125	109.6	100.8	8.4	78-122	35		
Ethyl benzene	0.148	0.141	0.125	0.125	118.4	112.8	4.8	70-130	35		
Xylene(s)	0.432	0.458	0.375	0.375	115.2	122.1	5.8	75-125	35		
Surrogate(s)						: :					ì
Trifluorotoluene	580	515	500	500	116.0	103.0	į	53-125			
4-Bromofluorobenzene-Fl	578	519	500	500	115.6	103.8		58-124	!		İ

Submission #: 2000-04-0331

Environmental Services (SDB)

To: Aqua Science Engineers, Inc.

Test Method: 8015M

8020

Attn:lan T. Reed

Prep Method: 5030

Legend & Notes

Gas/BTEX (Methanol Extraction)

Analyte Flags

g

Hydrocarbon reported in the gasoline range does not match our gasoline standard.

sh

Surrogate recoveries were higher than QC limits due to matrix interference.

Aqua Science Engineers, Inc. 208 W. El Pintado Road & Danville, CA 94526 (925) 820-9391

Chain of Custody 2000-04-0331

FAX (925) 837-4853 SAMPLER (SIGNATURE) (PHONE NO.) PROJECT NAME Compare Prices - Shahnazi 4/20/00 DATE (925)820-9301 2844 Mainton Glod, Oakland CA ADDRESS PURGEABLE HALOCARBONS (EPA 601/8010) ORGANOCHLORINE HERBICIDES (EPA 8150) ORGANOPHOSPHORUS PESTICIDES (EPA 8140) (EPA 608/8080) SPECIAL INSTRUCTIONS: PCBs & PESTICIDES (EPA 608/8080) FUEL OXYGENATES (EPA 8260) VOLATILE ORGANICS (EPA 624/8240) TPH-GASOLINE (EPA 5030/8015) CAM 17 METALS (EPA 6010+7000) TPH-DIESEL (EPA 3510/8015) COMPOSITE 5-day TAT NO. OF SAMPLE ID. DATE TIME MATRIX SAMPLES BH-E-181 4/18 501 BH-F-19' 1/18 B1-6-11.5' 4/10 BH-4 -11.5 4/18 BH-I-15.5 4/19 BH - 10 14/19 13H-K-10 4/19 BH-L- 115 4/19 BH-M-11.5 4/19 RECEIVED BY LABORATORY: L Wenne Harrington. COMMENTS: RECEIVED BY: 10:02 (time) 1003 (signature) (date) 18 m (printed name) (date)

Company 4/20/00

Chromalah 1812 5-day TAT 4.5°C & Murrow (printed name) (printed name) (printed name) Company-Company-

APPENDIX E

Certified Analytical Report
and
Chain of Custody Documentation
Groundwater Samples

Environmental Services (SDB)

Submission #: 2000-04-0332

Date: April 26, 2000

Aqua Science Engineers, Inc.

208 West El Pintado Road Danville, CA 94526

Attn.: Mr. Ian T. Reed

Project: 3538

Compare Prices-Shahnnazi

Dear Mr. Reed,

Attached is our report for your samples received on Thursday April 20, 2000 This report has been reviewed and approved for release. Reproduction of this report is permitted only in its entirety.

Please note that any unused portion of the samples will be discarded after May 20, 2000 unless you have requested otherwise. We appreciate the opportunity to be of service to you. If you have any questions, please call me at (925) 484-1919. You can also contact me via email. My email address is: vvancil@chromalab.com

Sincerely,

Vincent Vancil

CHROMALAB, INC. Environmental Services (SDB)

Gas/BTEX and MTBE

Aqua Science Engineers, Inc.

208 West El Pintado Road

Danville, CA 94526

Phone: (925) 820-9391 Fax: (925) 837-4853

Attn: Ian T. Reed Project #: 3538

Project: Compare Prices-Shahnnazi

Samples Reported

Matrix	Date Sampled	Lab#
	04/18/2000 10:30	1
!		2
	04/18/2000 15:00	3
1	04/18/2000 17:00	4
	04/19/2000 10:30	5
	04/19/2000 10:20	6
	04/19/2000 11:30	7
1	04/19/2000 14:00	8
Water	04/19/2000 13:30	9
	Matrix Water Water Water Water Water Water Water Water Water Water Water	Water 04/18/2000 10:30 Water 04/18/2000 13:00 Water 04/18/2000 15:00 Water 04/18/2000 17:00 Water 04/19/2000 10:30 Water 04/19/2000 10:20 Water 04/19/2000 11:30 Water 04/19/2000 14:00

CHROMALAB, INC. Environmental Services (SDB)

Submission #: 2000-04-0332

Aqua Science Engineers, Inc. To:

Test Method:

8020 8015M

Attn.: Ian T. Reed

Prep Method:

5030

Gas/BTEX and MTBE

Sample ID:

BH-E

Lab Sample ID: 2000-04-0332-001

Project:

3538

Received:

04/20/2000 18:12

Compare Prices-Shahnnazi

04/18/2000 10:30

Extracted:

04/24/2000 11:24

Sampled:

QC-Batch:

2000/04/24-01.01

			•		
ъ.	^	٠,	м	v	-
М	~		1	л	

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Gasoline	15000	2500	ug/L	50.00	04/24/2000 11:24	
Benzene	260	25	ug/L	50.00	04/24/2000 11:24	
Toluene	27	25	ug/L	50.00	04/24/2000 11:24	
Ethyl benzene	890	25	ug/L	50,00	04/24/2000 11:24	
Xylene(s)	4000	25	ug/L	50.00	04/24/2000 11:24	
MTBE	ND	250	ug/L	50.00	04/24/2000 11:24	
Surrogate(s)						
Trifluorotoluene	65.8	58-124	%	1.00	04/24/2000 11:24	
4-Bromofluorobenzene-FID	73.5	50-150	%	1.00	04/24/2000 11:24	

Aqua Science Engineers, Inc.

Environmental Services (SDB)

Test Method:

8020

Submission #: 2000-04-0332

8015M

Attn.: Ian T. Reed

Prep Method:

5030

Gas/BTEX and MTBE

Sample ID:

BH-F

Lab Sample ID: 2000-04-0332-002

Project:

To:

3538

Received:

04/20/2000 18:12

Compare Prices-Shahnnazi

Extracted:

04/21/2000 21:21

Sampled:

04/18/2000 13:00

QC-Batch:

2000/04/21-01.03

Matrix:

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Gasoline	ND	50	ug/L	1.00	04/21/2000 21:21	
Benzene	ND	0.50	ug/L	1.00	04/21/2000 21:21	
Toluene	ND	0.50	ug/L	1.00	04/21/2000 21:21	
Ethyl benzene	ND	0.50	uo/L	1.00	04/21/2000 21:21	
Xylene(s)	ND	0.50	ug/L	1.00	04/21/2000 21:21	
MTBE	ND	5.0	ug/L	1.00	04/21/2000 21:21	
Surrogate(s)					5 4 10 4 10 0 0 0 0 1 - 0 1	
Trifluorotoluene	105.9	58-124	%	1.00	04/21/2000 21:21	
4-Bromofluorobenzene-FID	87.9	50-150	%	1.00	04/21/2000 21:21	

Environmental Services (SDB)

Aqua Science Engineers, Inc.

Test Method:

8020

Submission #: 2000-04-0332

8015M

Attn.: Ian T. Reed

To:

Prep Method:

5030

Gas/BTEX and MTBE

Sample ID:

BH-G

Lab Sample ID: 2000-04-0332-003

Project:

3538

Received:

04/20/2000 18:12

Compare Prices-Shahnnazi

04/25/2000 14:37

Sampled:

04/18/2000 15:00

Extracted: QC-Batch:

2000/04/25-01.01

Matrix:

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Gasoline	ND	50000	ug/L	1000.00	04/25/2000 14:37	
Benzene	ND	500	ug/L	1000.00	04/25/2000 14:37	
Toluene	ND	500	ug/L	1000.00	04/25/2000 14:37	
Ethyl benzene	ND	500	ug/L	1000.00	04/25/2000 14:37	
Xylene(s)	ND	500	ug/L	1000.00	04/25/2000 14:37	
MTBE	130000	5000	ug/L	1000.00	04/25/2000 14:37	
Surrogate(s)	1		i			
Trifluorotoluene	74.2	58-124	%	1.00	04/25/2000 14:37	
4-Bromofluorobenzene-FID	80.3	50-150	%	1.00	04/25/2000 14:37	

Submission #: 2000-04-0332

CHROMALAB, INC.

Environmental Services (SDB)

To: Aqua Science Engineers, Inc. Test Method:

8020 8015M

Attn.: Ian T. Reed

Prep Method:

5030

Gas/BTEX and MTBE

Sample ID:

вн-н

Lab Sample ID: 2000-04-0332-004

Project:

3538

Received:

04/20/2000 18:12

Compare Prices-Shahnnazi

Sampled:

04/18/2000 17:00

Extracted:

04/24/2000 18:37

Matrix:

Water

QC-Batch:

2000/04/24-01.01

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Gasoline	960	100	ug/L	2.00	04/24/2000 18:37	·
Benzene	12	1.0	ug/L	2.00	04/24/2000 18:37	
Toluene	2.3	1.0	ug/L	2.00	04/24/2000 18:37	
Ethyl benzene	40	1.0	ug/L	2.00	04/24/2000 18:37	
Xylene(s)	45	1.0	ug/L	2.00	04/24/2000 18:37	
MTBE	250	10	ug/L	2.00	04/24/2000 18:37	
Surrogate(s)			:		i	
Trifluorotoluene	98.6	58-124	%	1.00	04/24/2000 18:37	
4-Bromofluorobenzene-FID	89.0	50-150	%	1.00	04/24/2000 18:37	

Submission #: 2000-04-0332

Environmental Services (SDB)

Aqua Science Engineers, Inc. To:

Test Method:

8020 8015M

Attn.: Ian T. Reed

Prep Method:

5030

Gas/BTEX and MTBE

Sample ID:

BH-I

Lab Sample ID: 2000-04-0332-005

Project:

3538

Received:

04/20/2000 18:12

Compare Prices-Shahnnazi

04/21/2000 22:54

Sampled:

04/19/2000 10:30

Extracted: QC-Batch:

2000/04/21-01.03

Matrix:

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Compound Gasoline Benzene Toluene Ethyl benzene Xylene(s) MTBE	130 ND ND ND ND ND 130	50 0.50 0.50 0.50 0.50 0.50 5.0	ug/L ug/L ug/L ug/L ug/L ug/L	1.00 1.00 1.00 1.00 1.00 1.00	04/21/2000 22:54 04/21/2000 22:54 04/21/2000 22:54 04/21/2000 22:54 04/21/2000 22:54 04/21/2000 22:54	
Surrogate(s) Trifluorotoluene 4-Bromofluorobenzene-FID	110.1 101.4	58-124 50-150	% %	1.00 1.00	04/21/2000 22:54 04/21/2000 22:54	

Submission #: 2000-04-0332

Environmental Services (SDB)

Aqua Science Engineers, Inc. To:

Test Method:

8020 8015M

Prep Method:

5030

Attn.: Ian T. Reed

Sample ID:

Gas/BTEX and MTBE

Lab Sample ID: 2000-04-0332-006

Project:

BH-J

Received:

04/20/2000 18:12

3538

Compare Prices-Shahnnazi

Extracted:

04/24/2000 11:59

Sampled:

04/19/2000 10:20

QC-Batch:

2000/04/24-01.01

Matrix:

Water

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Gasoline Benzene Toluene Ethyl benzene Xylene(s) MTBE	ND ND ND ND ND ND	25000 1300 1300 1300 1300 1300	ug/L ug/L ug/L ug/L ug/L ug/L	500.00 2500.00 2500.00 2500.00 2500.00 2500.00	04/24/2000 11:59 04/25/2000 01:04 04/25/2000 01:04 04/25/2000 01:04 04/25/2000 01:04 04/25/2000 01:04	
Surrogate(s) Trifluorotoluene 4-Bromofluorobenzene-FID	72.3 85.6	58-124 50-150	%	1.00 1.00	04/25/2000 01:04 04/24/2000 11:59	

Submission #: 2000-04-0332

CHROMALAB, INC.

Environmental Services (SDB)

Aqua Science Engineers, Inc. To:

Test Method:

8020 8015M

Attn.: Ian T. Reed

Prep Method:

5030

Gas/BTEX and MTBE

Sample ID:

вн-к

Lab Sample ID: 2000-04-0332-007

Project:

3538

Received:

04/20/2000 18:12

Compare Prices-Shahnnazi

Extracted:

04/25/2000 15:12

Sampled:

04/19/2000 11:30

QC-Batch:

2000/04/25-01.01

Matrix:

Water

Compound	Result	Rep,Limit	Units	Dilution	Analyzed	Flag
Gasoline	ND	130000	ug/L	2500.00	04/25/2000 15:12	
Benzene	6400	1300	ug/L	2500.00	04/25/2000 15:12	
Toluene	ND	1300	ug/L	2500.00	04/25/2000 15:12	
Ethyl benzene	ND	1300	ug/L	2500.00	04/25/2000 15:12	
Xylene(s)	7900	1300	ug/L	2500.00	04/25/2000 15:12	
MTBE	410000	13000	ug/L	2500.00	04/25/2000 15:12	
Surrogate(s)					2 440 5 10 20 4 5 4 0	
Trifluorotoluene	76.4	58-124	%	1.00	04/25/2000 15:12	
4-Bromofluorobenzene-FID	88.0	50-150	%	1.00	04/25/2000 15:12	

Submission #: 2000-04-0332

Environmental Services (SDB)

Aqua Science Engineers, Inc. To:

Test Method:

8020 8015M

Attn.: Ian T. Reed

Prep Method:

5030

Gas/BTEX and MTBE

Sample ID:

BH-L

Lab Sample ID: 2000-04-0332-008

Project:

Received:

04/20/2000 18:12

3538

Compare Prices-Shahnnazi

Extracted:

04/21/2000 22:23

Sampled:

04/19/2000 14:00

QC-Batch:

2000/04/21-01.03

Matrix:

Water

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
	120	50	ug/L	1.00	04/21/2000 22:23	g
Gasoline		0.50	ug/L	1.00	04/21/2000 22:23	
Benzene	ND	0.50	ug/L	1.00	04/21/2000 22:23	
Toluene	ND	0.50	ug/L	1.00	04/21/2000 22:23	
Ethyl benzene	ND	1	ug/L	1.00	04/21/2000 22:23	
Xylene(s) MTBE	ND 110	0.50 5.0	ug/L	1.00	04/21/2000 22:23	
Surrogate(s)	101.6	58-124	%	1.00	04/21/2000 22:23	
Trifluorotoluene 4-Bromofluorobenzene-FID	95.2	50-150	%	1.00	04/21/2000 22:23	

Submission #: 2000-04-0332

Environmental Services (SDB)

Aqua Science Engineers, Inc. To:

Test Method:

8020 8015M

Attn.: lan T. Reed

Prep Method:

5030

Gas/BTEX and MTBE

Sample ID:

BH-M

Lab Sample ID: 2000-04-0332-009

Project:

3538

Received:

04/20/2000 18:12

Compare Prices-Shahnnazi

Extracted:

04/24/2000 15:43

Sampled:

04/19/2000 13:30

QC-Batch:

2000/04/24-01.01

Matrix:

Water

Compound	Result	Rep.Limit	Units	Dilution	Analyzed	Flag
Gasoline	ND	50	ug/L	1.00	04/24/2000 15:43	
Benzene	ND	0.50	ug/L	1.00	04/24/2000 15:43	
Toluene	ND	0.50	ug/L	1.00	04/24/2000 15:43	
* * * * * * * * * * * * * * * * * * * *	ND	0.50	ug/L	1.00	04/24/2000 15:43	
Ethyl benzene	ND	0.50	ug/L	1.00	04/24/2000 15:43	
Xylene(s) MTBE	ND	5.0	ug/L	1.00	04/24/2000 15:43	
Surrogate(s)	75.5	58-124	%	1.00	04/24/2000 15:43	
Trifluorotoluene 4-Bromofluorobenzene-FID	75.5 _{86.7}	50-150	%	1.00	04/24/2000 15:43	

Printed on: 04/26/2000 13:43

CHROMALAB, INC. Environmental Services (SDB)

Submission #: 2000-04-0332

Aqua Science Engineers, Inc. To:

Test Method:

8020

8015M

Attn.: Ian T. Reed

Prep Method:

5030

Batch QC Report Gas/BTEX and MTBE

Method Blank

Water

QC Batch # 2000/04/21-01.03

MB:

2000/04/21-01.03-001

Date Extracted: 04/21/2000 12:22

Company	Result	Rep.Limit	Units	Analyzed	Flag
Compound Gasoline Benzene Toluene Ethyl benzene Xylene(s) MTBE	ND ND ND ND ND	50 0.5 0.5 0.5 0.5 5.0	ug/L ug/L ug/L ug/L ug/L ug/L	04/21/2000 12:22 04/21/2000 12:22 04/21/2000 12:22 04/21/2000 12:22 04/21/2000 12:22 04/21/2000 12:22	
Surrogate(s) Trifluorotoluene 4-Bromofluorobenzene-FID	70.2 60.6	58-124 50-150	% %	04/21/2000 12:22 04/21/2000 12:22	

Printed on: 04/26/2000 13:43

Submission #: 2000-04-0332

Environmental Services (SDB)

Aqua Science Engineers, Inc. To:

Test Method:

8020

8015M

Attn.: Ian T. Reed

Prep Method:

5030

Batch QC Report Gas/BTEX and MTBE

Method Blank

Water

QC Batch # 2000/04/24-01.01

MB:

2000/04/24-01.01-001

Date Extracted: 04/24/2000 06:11

	Result	Rep.Limit	Units	Analyzed	Flag
Compound Gasoline Benzene Toluene Ethyl benzene Xylene(s) MTBE	ND ND ND ND ND ND	50 0.5 0.5 0.5 0.5 5.0	ug/L ug/L ug/L ug/L ug/L ug/L	04/24/2000 06:11 04/24/2000 06:11 04/24/2000 06:11 04/24/2000 06:11 04/24/2000 06:11 04/24/2000 06:11	
Surrogate(s) Trifluorotoluene 4-Bromofluorobenzene-FID	83.4 89.6	58-124 50-150	% %	04/24/2000 06:11 04/24/2000 06:11	,,

CHROMALAB, INC. Environmental Services (SDB)

Submission #: 2000-04-0332

Aqua Science Engineers, Inc. To:

8020 Test Method:

8015M

Attn.: Ian T. Reed

Prep Method:

5030

Batch QC Report Gas/BTEX and MTBE

Method Blank

Water

QC Batch # 2000/04/25-01.01

MB:

2000/04/25-01.01-001

Date Extracted: 04/25/2000 06:23

	Result	Rep.Limit	Units	Analyzed	Flag
Compound Gasoline Benzene Toluene Ethyl benzene Xylene(s) MTBE	ND ND ND ND ND ND	50 0.5 0.5 0.5 0.5 5.0	ug/L ug/L ug/L ug/L ug/L ug/L	04/25/2000 06:23 04/25/2000 06:23 04/25/2000 06:23 04/25/2000 06:23 04/25/2000 06:23 04/25/2000 06:23	
Surrogate(s) Trifluorotoluene 4-Bromofluorobenzene-FID	74.8 83.0	58-124 50-150	%	04/25/2000 06:23 04/25/2000 06:23	

Submission #: 2000-04-0332

Environmental Services (SDB)

To: Aqua Science Engineers, Inc.

Test Method: 8

Prep Method:

8020 8015M

Attn: lan T. Reed

5030

Batch QC Report

Gas/BTEX and MTBE

Laboratory Control Spike (LCS/LCSD)

Water

QC Batch # 2000/04/21-01.03

LCS:

2000/04/21-01.03-002

Extracted: 04/21/2000 12:53

Analyzed

04/21/2000 12:53

LCSD: 2000/04/21-01.03-003

Extracted: 04/21/2000 13:25

Analyzed 04/21/2000 13:25

Compound	Conc.	[ug/L]	Exp.Conc.	[ug/L]	Recovery [%]		RPD	Ctrl. Limi	ts [%]	Fla	gs
Compound	LCS	LCSD	LCS	LCSD	LCS	LCSD	[%]	Recovery	RPD	LCS	LCSD
Gasoline	544	530	500	500	108.8	106.0	2.6	75-125	20		
Benzene	46.6	45.3	50	50	93.2	90.6	2.8	77-123	20		
Toluene	47.2	46.1	50	50	94.4	92.2	2.4	78-122	20		
Ethyl benzene	47.8	46.6	50	50	95.6	93.2	2.5	70-130	20	 	
Xylene(s)	151	146	150	150	100.7	97.3	3.4	75-125	20		
Surrogate(s)		İ			1]			
Trifluorotoluene	236	256	250	250	94.4	102.4	!	58-124			
4-Bromofluorobenzene-FI	484	477	500	500	96.8	95.4	:	50-150	<u> </u>		1

Submission #: 2000-04-0332

Environmental Services (SDB)

To: Aqua Science Engineers, Inc.

Test Method: 8020

8015M

Attn: Ian T. Reed

Prep Method:

5030

Batch QC Report

Gas/BTEX and MTBE

Laboratory Control Spike (LCS/LCSD)

Water

QC Batch # 2000/04/24-01.01

LCS:

2000/04/24-01.01-002

Extracted: 04/24/2000 06:46

Analyzed

04/24/2000 06:46

LCSD:

2000/04/24-01.01-003

Extracted: 04/24/2000 07:21

Analyzed

04/24/2000 07:21

Compound	Conc.	[ug/L]	Exp.Conc.	[ug/L]	Recovery [%]		RPD	Ctrl. Limits [%]		Flags	
Compound	LCS	LCSD	LCS	LCSD	LCS	LCSD	[%]	Recovery	RPD	LCS	LCSD
Gasoline	494	480	500	500	98.8	96.0	2.9	75-125	20		
Benzene	86.1	85.5	100.0	100.0	86.1	85.5	0.7	77-123	20		
Toluene	82.2	81.6	100.0	100.0	82.2	81.6	0.7	78-122	20		
Ethyl benzene	83.6	83.8	100.0	100.0	83.6	83.8	0.2	70-130	20		
Xylene(s)	254	255	300	300	84.7	85.0	0.4	75-125	20		
Surrogate(s)	İ	! 							ĺ		
Trifluorotoluene	387	382	500	500	77.4	76.4		58-124			
4-Bromofluorabenzene-FI	432	428	500	500	86.4	85.6		50-150		ļ	<u> </u>

Submission #: 2000-04-0332

Environmental Services (SDB)

Aqua Science Engineers, Inc. To:

Test Method:

8020

8015M

Attn: Ian T. Reed

Prep Method:

5030

Batch QC Report

Gas/BTEX and MTBE

Laboratory Control Spike (LCS/LCSD)

Water

QC Batch # 2000/04/25-01.01

LCS:

2000/04/25-01.01-002

Extracted: 04/25/2000 06:58

Analyzed

04/25/2000 06:58

LCSD: 2000/04/25-01.01-003

Extracted: 04/25/2000 07:33

Analyzed

04/25/2000 07:33

Compound	Conc.	[ug/L]	Exp.Conc.	[ug/L]	Recov	ery [%]	RPD	Ctrl. Lim	its [%]	Flag	gs
•	LCS	LCSD	LCS	LCSD	LCS	LCSD	[%]	Recovery	RPD	LCS	LCSD
Gasoline	511	464	500	500	102.2	92.8	9.6	75-125	20		
Benzene	85.8	86.0	100.0	100.0	85.8	86.0	0.2	77-123	20		
Toluene	81.6	81.8	100.0	100.0	81.6	81.8	0.2	78-122	20		
Ethyl benzene	83.0	83.6	100.0	100.0	83.0	83.6	0.7	70-130	20		
Xylene(s)	255	255	300	300	85.0	85.0	0.0	75-125	20	į	
Surrogate(s)	1					[]			1		
Trifluorotoluene	374	376	500	500	74.8	75.2		58-124			
4-Bromofluorobenzene-Fl	443	408	500	500	88.6	81.6		50-150		1	

Environmental Services (SDB)

Aqua Science Engineers, Inc.

Test Method: 8020

8015M

Submission #: 2000-04-0332

Prep Method: 5030

Attn.: Ian T. Reed

Batch QC Report

Gas/BTEX and MTBE

Matrix Spike (MS / MSD)

Water

QC Batch # 2000/04/24-01.01

Sample ID: BH-M

Lab Sample ID: 2000-04-0332-009

MS:

2000/04/24-01.01-004 Extracted: 04/24/2000 16:18 Analyzed: 04/24/2000 16:18 Dilution: 1.0

MSD:

2000/04/24-01.01-005Extracted: 04/24/2000 16:53 Analyzed: 04/24/2000 16:53 Dilution: 1.0

Compound	Conc.]	ug/L]	Exp.Conc.	[ug/L]	Recov	ery [%]	RPD	Ctrl. Limit	ts [%]	FI	ags
•	MS	MSD	Sample	MS	MSD	MS	MSD	[%]	Recovery	RPD	MS	MSD
Gasoline	483	467	ND	500	500	96.6	93.4	3.4	65-135	20		
	85.2	85.9	מא	100.0	100.0	85.2	85.9	8.0	65-135	20		
201120110	79.3	79.7	ND	100.0	100.0	79.3	79.7	0.5	65-135	20		1
, 0.00	78.6	79.6	iND	100.0	100.0	78.6	79.6	1.3	65-135	20		
,	222	223	ND	300	300	74.0	74.3	0.4	65-135	20		
Surrogate(s)		į						İ				
Trifluorotoluene	362	374		500	500	72.4	74.8		58-124			
4-Bromofluorobenzene-F	439	434		500	500	87.8	86.8		50-150			

Printed on: 04/26/2000 13:43

Page 17 of 18

CHROMALAB, INC. Environmental Services (SDB)

To: Aqua Science Engineers, Inc.

Submission #: 2000-04-0332

Test Method: 8015M

8020

Attn:lan T. Reed

Prep Method: 5030

Legend & Notes

Gas/BTEX and MTBE

Analyte Flags

g

Hydrocarbon reported in the gasoline range does not match our gasoline standard.

Aqua Science Engineers, inc. 208 W. El Pintado Road Danville, CA 94526

Chain of Custody 2000.04-0332 (925) 820-9391 FAX (925) 837-4853 OF PAGE (PHONE NO.) 353 E SAMPLER (SIGNATURE) JOB NO. Compare Power Shahnazi PROJECT NAME 4/20/00 (925) 820- 9391 Dallland, CA DATE 2844 Mountain blud, ADDRESS ANALYSIS REQUEST PURGEABLE HALOCARBONS (EPA 601/8010) ORGANOPHOSPHORUS PESTICIDES (EPA 8140) (EPA 608/8080) ORGANOCHLORINE HERBICIDES (EPA 8150) SEMI-YOLATILE ORGANICS (EPA 625/8270) TPH-GAS / MTBE & BTEX (EPA 5030/8015-8020) SPECIAL INSTRUCTIONS: PURGEABLE AROMATICS (EPA 602/8020) PCBs & PESTICIDES (EPA 608/8080) VOLATILE ORGANICS (EPA 624/8240) CAM 17 METALS (EPA 6010+7000) LUFT METALS (5) (EPA 6010+7000) TPH-DIESEL (EPA 3510/8015) 5-dal TAT COMPOSITE OIL & GREASE (EPA 5520)___ NO. OF SAMPLE ID. TIME MATRIX **SAMPLES** DATE 4/18/60 1030 B1+ = E woter 14/10/10 1300 13H - F 4 MES 1500 BH·G 11/18/0 BH-H 1700 BH I 14/19/00/1630 4 14 6 ,0 20 BH . I 1/19/4/1130 2H-K JAN 1400 BH - L N 1, 9/10 1330 B17-14 REGEIVED BY LABORATORY:

Deuse Favrivator
(Signature) (time) COMMENTS: RECEIVED BY: RELINQUISHED BY: RELINQUISHED BY: 10 03 (time) (time) 1003 (signature) D. Harrington 5-dCV TAT.

Exprinted name) (date)

Company. 4/20/00

Chromalab 1812 4.5°C D Harrington
Yzim (printed name) (date) ant Reed 0/400 (date) 4/20/2 (printed name) (printed name) (printed name) Company-Company-, Company-