RECEIVED

1:27 pm, Jul 23, 2012

Alameda County
Environmental Health

Mr. Jerry Wickham
Alameda County
Environmental Health I epartment
1131 Harbor Bry Parky ay, Suite 250
Alameda, California 94 502-6577

7/19/12

Re: B&C Gas Mini M art, 2008 First Street, Livermore, California (ACEHD Case No. RO0000278)

Dear Mr. Wickliam:

Stratus Envirormental, nc. (Stratus) has recently prepared a document titled Quarterly Remediation Status Rep. rt, Second Quarter 2012 on my behalf. The report was prepared in regards to Alameda County Fuel Leak Case No. RO0000278, located at 2008 First Street, Livermore, California.

I have reviewed a copy of this report, sent to me by representatives of Stratus, and "I declare, under renalty o 'perjury, that the information and or/recommendations contained in the attached cocumen or report is true and correct to the best of my knowledge."

Sincerely,

Balaji Angle

B&C Gas Mini Mart



July 16, 2012 Project No. 2146-2008-01

Mr. Jerry Wickham Alameda County Environmental Health Department 1131 Harbor Bay Parkway, Suite 250 Alameda, California 94502-6577

Re: Quarterly Remediation Status Report, Second Quarter 2012, B&C Gas Mini Mart, 2008 First Street, Livermore, California (ACEHD Case No. RO0000278)

Dear Mr. Wickham:

Stratus Environmental, Inc. (Stratus) is submitting the attached report, on behalf of Mr. Balaji Angle, to document work performed during the second quarter 2012 at the B&C Gas Mini Mart, located at 2008 First Street, Livermore, California. This report has been prepared in compliance with Alameda County Environmental Health Department (ACEHD) requirements for underground storage tank (UST) investigations.

If you have any questions regarding this report, please contact Scott Bittinger at (530) 676-2062 or Gowri Kowtha at (530) 676-6001.

Sincerely,

STRATUS ENVIRON

T No

Scott G Pittinger

Scott G. Bittinger, P.G.

Project Manager

Deborah L. Barr, P.E.

Project Engineer

Attachment: Quarterly Remediation Status Report, Second Quarter 2012

cc: Mr. Balaji Angle, B&C Gas Mini Mart

Date July 16, 2012	
--------------------	--

B&C GAS MINI MART QUARTERLY REMEDIATION STATUS REPORT

Facility Address: 2008 First Street, Livermore, California

Consulting Co./Contact Person: Stratus Environmental, Inc. / Scott Bittinger, P.G.

Consultant Project No: 2146-2008-01

Primary Agency/Regulatory ID No: Alameda County Environmental Health Department (ACEHD) / Case

No. RO0000278

WORK PERFORMED THIS PERIOD (Second Quarter 2012):

- 1. Stratus performed seven site visits to perform operation and maintenance work on an ozone injection system that is operating at the site. Field data sheets prepared at the time of each site visit are attached to this report (see Appendix A).
- In accordance with SWRCB Resolution No. 2009-0042, this site is under a semi-annual groundwater monitoring and sampling program, with these activities performed during the first and third quarters of each calendar year; therefore, no groundwater sampling was conducted during the second quarter 2012.

WORK PROPOSED FOR NEXT PERIOD (Third Quarter 2012):

- 1. In a letter dated June 28, 2012, ACEHD personnel requested that a revised plan to perform remediation activities at the site be developed and submitted for agency review. These activities are to include an expansion of the area of groundwater treatment by ozone injection and a re-evaluation of possible use of soil vapor extraction (SVE) at the site, which was proposed for use at the site in a January 2009 Corrective Action Plan but not implemented, apparently due to recent 'above average' groundwater levels. A deadline of August 28, 2012 was established for submittal of a work plan.
- 2. Semi-annual groundwater monitoring and sampling will be performed in accordance with the approved well gauging and sampling schedule. Tentatively, we anticipate performing the next well gauging/sampling event in August 2012.
- 3. Stratus will continue operation of the existing ozone injection system until a revised remedial plan is developed and approved by ACEHD. It should be noted that during the second quarter 2012, ongoing maintenance problems with the existing ozone injection system resulted in non-continuous operation of this equipment. While we believe that ozone injection is a viable groundwater remedial alternative for near-source fuel contaminants, replacement of the existing ozone injection system will be considered as part of the late August 2012 work plan to allow for continuous remediation of the saturated zone.

Current Phase of Project: Groundwater Monitoring, Onsite Ozone Injection (CAP/REM – O&M)

Frequency of Groundwater Sampling: MW-2 though MW-7, MW-13, CMT-1 Z1, CMT-2 Z1, CMT-3 Z1, and CMT-4 Z2 = semi-appually (first 8 third calculate and a semi-a

CMT-4 Z2 = semi-annually (first & third calendar quarter); MW-8 through MW-12 and D-2 = annually (third calendar quarter)

Frequency of Groundwater Monitoring: All wells = semi-annual (1st & 3rd); additional groundwater level measurements are collected during operation and maintenance visits

for the ozone injection system.

IN-SITU GROUNDWATER REMEDIATION SYSTEM

Equipment Inventory: Calcon Environmental (Calcon) HiPro[™] 2500 Ozone Injection

System

Ozone Injection System Status: Operational

> Injection wells: SP-1A/B, SP-2A/B, SP-4A/B (ozone not being injected into well

Offsite wells SP-5 A/B/C and SP-6 A/B/C not

connected to remediation system).

REMEDIATION SYSTEM

Ozone Injection System Description and Second Quarter 2012 Operation and Maintenance

A Calcon HiProTM 2500 ozone injection system is currently being used to complete remedial work. The remediation system is situated within a locked, fenced remedial compound located immediately adjacent to a convenience store building located on the property (see Figure 2). The system is currently configured to cyclically inject an air/ozone mixture into wells SP-1A/B, SP-2A/B, and SP-4A/B. Subgrade piping with conveyance tubing extends from the remediation compound area to well SP-3A/B, however this tubing is not currently connected to the ozone injection system. Conveyance piping and tubing has not been installed to offsite wells SP-5A/B/C or SP-6A/B/C.


Stratus personnel visited the site on April 10, April 23, May 7, May 22, May 31, June 4, and June 20, 2012 in order to conduct operation and maintenance visits for the ozone injection system. Field data sheets documenting observations and work performed by Stratus personnel are included in Appendix A. Upon arrival at five of the seven visits, the remediation system was observed non-operational due to equipment malfunctions. Maintenance work was performed during each site visit and the equipment was re-started prior to departure.

ATTACHMENTS:

Figure 1 Site Location Map


• Figure 2 Site Plan

 Appendix A Field Data Sheets



GENERAL NOTES: BASE MAP FROM U.S.G.S. LIVERMORE, CA. 7.5 MINUTE TOPOGRAPHIC PHOTOREVISED 1999






STRATUS ENVIRONMENTAL, INC.

B & C GAS MINI MART 2008 FIRST STREET LIVERMOORE, CALIFORNIA

SITE LOCATION MAP

FIGURE

PROJECT NO. 2146-2008-01



APPENDIX A FIELD DATA SHEETS

OFFICE WAL

BTC GAS Min. Mart 2008 FIRST STREET, LIVERMORE

Date: Onsite Time Offsite Time Equipment	: 113	0				ician: er Conditi nt Temper		CHILL Run 50	- - -
Ozone Gen	erator Pan	el·							-
System Stat			_	J 0				41 Y	
System Stat Com Hour Meter I	us Upon Ar	rival:	レ 区 ここ	∫ Opera		Oxyge	n flow rate	Non-operational Non-operational	np
Injection Pre				Stat	m3			ate: 4.0	
		Fie	ld Meas	urments				10 mins AT	.
Well ID	Time	DTW	pH	DO	Cond.	ORP	Temp	, , ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	ialy me
mw-2		feet bgs		mg/L	msieme	+	deg F		
MW-6		BAD	7.39	17	797	327	17,8		
mw-1			u.c.		_		<u> </u>		
No. of the		Nom	A III	Daugh	in			7	
mw-3		37.69	1 46	100 2	1:==/	- 11			
MW-5				10.00	77(357	18.1	- once or twice a	a ugr ter
SP-5		midel	e Ru	mi	 			- Once or your	ı
B		3760	151	156	(-)				• ,
A		3799	016	1.59	092	298	18.6		
C		37.67	6.69	1.94	924	334	181		
		37.62	7.14	2.04	097	366	18.6		
Signature:	CHI	n				Date:	4-1	10-12	

BTC GAS Min. Mart 2008 FIRST STREET, LIVERMORE

ORIGINAL

Date: Onsite Time Offsite Time Equipment	09	3-12 30 er/Model#:			cian: er Conditi t Temper		CHILL Clouds 52	
Ozone Gen System Stat System Stat Hour Meter I Injection Pre	us Upon Ar us Upon Ar Reading:	rival: rival:	1, 2 Vivo	Operat Operat		n flow rate:	Non-operational Non-operational 13 SCYM rate: Z.5 ScYM	
Well ID MW-2 MW-6 MW-7 MW-3 MW-5 SP-5 A B C	Time	Fie DTW feet bgs 36.84 BAD No W 35.90 N M 36.15 36.15 36.72 35.7)	7.16 inel	DO mg/L Z.Z/c	168	Temp deg F 19./ 18.9 19.2 18.8 18.4	- once or twice a qu	ar te
Signature:		-	sta 4,			47	Filter 83/4×93 312 extra one	¥

BTC GAS Mini Mart 2008 First Street, Livermore OFFICE

				Ozon	e Injectio	n System		
Offsite Time	5-7 e: 083 e: 092 Manufacture	30				ician: er Conditi nt Temper	CHILL Clear 58	
Ozone Gen System Star System Star Hour Meter Injection Pre	tus Upon Ari tus Upon Ari Reading:	rival:	<u> </u>	Operat	tional	Oxyge Air + o.	n flow rate	Non-operational Non-operational IZSofH rate: \$2.6 CFM
Well ID MW-2 -NAW-6 MW-3 MW-5 SP-5 A B C	Time	DTW feet bgs 37.11 36.25 36.37 36.0	6.71	DO mg/L 3.27	Cond. msieme 696 701 716 1420 1887	-	Temp deg F 19.3 18.8 18.6 18.6	- once or twice a quarte

Date: 5-7-12

Solinal-ACIEV 45 MA 100% ED IP65

Durn Valve. DUPA Valve Medel 4M310-08 Page 75-110 751

BTC GAS Min. Mart 2008 First Street, Livermore ORIGINAL Ozone Injection System

				02011	c mjectioi	ıı System			
Offsite Time	Onsite Time: 045 (Offsite Time: 10/5 Equipment Manufacturer/Model#:				Techni Weath Ambier	CHILL Clus 50			
Ozone Gen	erator Pan	el:							
System Stat	us Upon Ar	rival:		Opera	tional		ί ν	#1	94
System State	us Upon Ar	rival:		Operat				Non-operational Te	mp
Hour Meter F	Reading:	<i>3</i> 72			 -	Oxvae	תے n flow rate	Non-operational :	
Injection Pre	_	012	6		_				-]
COMP 1	A.	74				Air + o	zone flow r	rate: 4 1 /	#4
		Fie	eld Measu	irments				1	
Well ID	Time	DTW	pН	DO	Cond.	ORP	Temp	1	
		feet bgs	units	mg/L	msieme	n mV	deg F		
mw-2		32.81	6.94	1.00	706	303	18.0		
MW-6		3 15	KIL	ell				1	
mw-1		Gom	4					ĺ	
2		2116	100 44 4	4 5 5					
MW-3		30.89	7.08	1, 29	702	305	18.1	, :	a wanter
MW-5 SP-5		37.27	6.94	1.24	910	259	18.1	- once or twi	ce a quarter
A A		717	111	100 001					
		36.75	6.61	0394	745	292	1810		
B		37.02	4 . 3	5 ./	151.5	278	18.8		
		3653	6265	1.65	182	264	18.4	11 1 15 15	SP3H+B
								HOOK 0/	
								TO 915+EM	•
								AZDAY. TO	ASP SPIATE
								020110 10	5727.5
									573)
									504
							`	Hook of S To system Ozone To	work work
Signature:	ONI	//	_					2 - (Z	
Signature:	0111					Date:	5-2	2-12	

BTC GAS Mini MALT 2008 FIRST STREET, LIVERMONE OFFICINAL

Date: Onsite Time Offsite Time Equipment I	091	9	_ _ _		Technici Weather Ambient	Conditio		CHILL 70 Clyn
Ozone Gen								
System Stat	us Upon Ar	rival:		Operati	onal		X	Non-operational
System Stat	us Upon Arı	rival:	区	Operati	onal			Non-operational
Hour Meter F	Reading:	380	1			Oxygen	flow rate	
Injection Pre 1 ろみあ	ssure: HTC5 C		2		_	Air + oz	one flow r	rate: 4,4 #6
		Fiel	d Measu	rments				7
Well ID	Time	DTW	рН	DO	Cond.	ORP	Temp	
mw-2		feet bgs	units	mg/L	msiemen	mV	deg F	
MW-6								
mw-1		 						
120-	_	2		11		1		
mw-3								
Mw-5								- once or twice a quar
SP-5								
A					+			
В								
C								
Signature:	CAN	1				Date:	5-3	11-12

OPI WAR

BTC GAS Min. MALT 2008 FIRST STREET, LIVERMORE

Offsite Tim	he: (75)	10				iician: ner Conditi nt Tempe		CHILL Clouds 40	- - -
1	nerator Pan			7 .					
	atus Upon Ai		Ľ Ž	」 Opera 【 Opera				Non-operational Non-operational	
Hour Meter	Reading:	386				Oxyge	n flow rate		
Injection Pro	essure:	137	51	#5		Air + o	zone flow r	rate: 4.4	
		Fie	eld Meas	urments				1 C 200 700 55 01	v mfx
Well ID	Time	DTW	рН	DO	Cond.	ORP	Temp	Like Tunne	a orbe
mw-2	 	feet bgs		mg/L	msieme		deg F	Like Tunner or Pestant	try
MW-6	 	ارهار	7.01	2.77	694	217	18.8	Rosfar Y	
mw-1) PEXIT	
	1/mm = ±=		70 A - 10	(6)				8	
mw-3		37.41	7.12	2.00	688	214	18.6		· ·
MW-5				- 0	900		10.0	- once or twice a	quarter
SP-5					 				
A		367	7.0Z	3.31	872	299	18.2		
В		37.58	7.44	3.06	692	334	181		
C		37.35	7.51	3.10	216	328	18.6		
Signature: <u>/</u>	24/1	4				Date:	6-4	-15	

BTC GAS MIN! MALT OR NAL 2008 FIRST STREET, LIVERMORE

Onsite Time Offsite Time Equipment N	0943	£	 			ian: r Conditio Tempera	CHILL Clu 50	
Ozone Gene	rator Pane	ıl:						
System Statu	ıs Upon Arr	ival:		Operati	ional		Ø	Non-operational
System Statu	ıs Upon Arr	ival:	X	Operati	onai			Non-operational
Hour Meter R	leading:	387	1.4			Oxygen	flow rate:	
Injection Pres	ssure:	12						rate: 4, Z
		Fiel	d Measu	rments				
Well ID	Time	DTW	рΗ	DO	Cond.	ORP	Temp	
mw-2		feet bgs	units	mg/L	msiemen	mV	deg F	
MW-6	1/	-		1				
mw -1		01	emo	11/5				
							A water	<u> </u>
mw-3								
MW-5								- once or twice a quarte
SP-5								- Once or
A							j	
В								
C								
							ň.	
								D+T = 2001
								Pul larpole
								Put Tarp over Compoul To shalk From son sex in Helps over Hell
								rom sun see in
								Helps over Hell