

GETTLER-RYAN INC.

Facility Number 9-012	21
General Corr.	Ō
Service Reqs./Proposals	
Permits/Bonds Drawings/Photos/Notes	
Spill & Leak Reports	
Legal/Easements/Lic.	\Box
Reports	LX.

TRANSMITTAL

DATE:

PROJ. #:

SUBJECT:

TO: Mr. Tom Bauhs

Chevron Product Company

P.O. Box 6004

San Ramon, California 94583

FROM:

David W. Herzog, R.G.

Senior Geologist

Gettler-Ryan Inc.

3140 Gold Camp Drive, Suite 170

Rancho Cordova, California 95670

RECEIVED

October 15, 2001

Chevron #9-0121

DGDG90121G.4C01

3026 Lakeshore Avenue Oakland, California

10:47 am, Mar 02, 2011

Alameda County
Environmental Health

WE ARE SENDING YOU:

COPIES DATED		DESCRIPTION
1 October 15, 2	2001 Si	ite Conceptual Model
THESE ARE TRANSMITTED as	checked below:	
[] For review and comment	[] Approved as submitted	[] Resubmit _ copies for approval
[] As requested	[] Approved as noted	[] Submit _ copies for distribution
[] For approval	[] Return for corrections	[] Return corrected prints
[X] For Your Files		
COMMENTS:		

Please call Gettler-Ryan at 916.631.1300 if you have questions.

cc: Ms. Eva Chu, ACHCS-DEH, 1131 Harbor Bay Parkway. Suite 250, Alameda, CA 94502 Mr. Jim Brownell, Delta Environmental Consultants, Inc.



3164 Gold Camp Drive Suite 200 Rancho Cordova, California 95670-6021 916/638-2085 FAX: 916/638-8385

No. 7211

SITE CONCEPTUAL MODEL

for Chevron Service Station #9-0121 3026 Lakeshore Avenue Oakland, California

Report No. DG90121C.4C01 Delta Project No. DG90-121

Prepared for:

Mr. Thomas Bauhs Chevron Products Company P.O. Box 6004 San Ramon, California 94583

Prepared by:

Delta Environmental Consultants, Inc.
Network Associate
Gettler-Ryan Inc.
3140 Gold Camp Drive, Suite 170
Rancho Cordova, California 95670

David W. Herzog ⁶ Senior Geologist R.G. 7211

Greg A. Gurss Senior Project Manager

October 15, 2001

TABLE OF CONTENTS

INTRODUCTION	ON		••••••	1
SITE DESCRI	PTION		***************************************	1
Hydrocarbon Leak Detection Discovery of LUST Abandor Well Destruct Product Line & Monitoring W	RVIRONMENTAL WORK Release and UST Replacement, and Ir Free Product in Soil and Instancent and Station Remodel ion and Installation of Moniand Dispenser Replacement Tell Installation and Replace Monitoring and Sampling Hydrogeology	ent	ystemell	
Well Survey Underground SITE CONCEL Release Scent Potential Env Other Environ	URVEY Utility Survey PTUAL MODEL ario and Plume Characteriza ironmental Receptors nmental Issues	ition		
		TABLES		
Table 1.	Well Search Data			
		FIGURES		
Figure 1. Figure 2. Figure 3. Figure 4. Figure 5. Figure 6. Figure 7. Figure 8. Figure 9.	Vicinity Map Site Plan/Utility Map Cross Section A-A' Cross Section B-B' Hydrocarbon Concentration TPHg Concentrations in G Benzene Concentrations in G TPHd Concentrations in G	roundwater on 3/1/01 Groundwater on 3/1/01 Froundwater on 3/1/01		

APPENDICES

Soil Chemical Analytical Data Appendix A.

Groundwater Monitoring Data and Analytical Results Appendix B.

Appendix C. Well Survey Data Appendix D. Appendix E. Potentiometric Maps

Boring logs and Well Construction Details



3164 Gold Camp Drive Suite 200 Rancho Cordova, California 95670-6021 916/638-2085 FAX: 916/638-8385

SITE CONCEPTUAL MODEL

for Chevron Service Station #9-0121 3026 Lakeshore Avenue Oakland, California

Report No. DG90121C.4C01 Delta Project No. DG90-121

INTRODUCTION

At the request of Chevron Products Company (Chevron), Delta Environmental Consultants, Inc. network associate Gettler-Ryan Inc. (GR) is submitting this report presenting the site conceptual model (SCM) for Chevron Service Station #9-0121 located at 3026 Lakeshore Avenue in Oakland, California. The purpose of this work is to evaluate whether the implementation of further environmental investigation and/or remediation related to soil and groundwater is warranted at the site. This report was prepared based on information supplied by Chevron, and describes site hydrogeological conditions and distribution of contaminants in space and time, identifies potential current and future receptors, and recommends an appropriate action plan for the site.

SITE DESCRIPTION

The subject site is an active service station located on the southern corner of the intersection of Lakeshore Avenue and MacArthur Boulevard. Aboveground facilities consist of an island marketer, six dispenser islands located in the central portion of the site, and a storage/restroom building located in the southern corner of the site. Three gasoline underground storage tanks (USTs) and one diesel UST share a common pit near the northern corner of the site. A 7-foot diameter storm drain is located along the southeastern property line.

The site is located at the western edge of Piedmont Hills, approximately 800 feet northeast of Lake Merritt. The topography of the site and its northern and western vicinity is relatively flat, however, the surface southeast and east of the site slopes steeply toward the site.

The site vicinity is used for transportation, commercial, residential, and recreational purposes. The site is bounded by Lakeshore Avenue to the northwest, MacArthur Boulevard to the northeast, Excelsior Court to the southeast, and commercial properties to the southwest. The nearest commercial building (3014 Lakeshore) is located along the southwestern border of the subject site. Residential apartment complexes are present south and southeast of the site across Excelsior Court. The nearest residential buildings are located approximately 10 feet south and 40 feet southeast of the subject site boundary. First floors of these buildings are used for garages. Lake Merritt Park is

located approximately 90 feet northwest of the subject site across Lakeshore Avenue. Interstate 580 is located north and northeast of the site parallel to MacArthur Boulevard.

PREVIOUS ENVIRONMENTAL WORK

Hydrocarbon Release and UST Replacement

Chevron began service station operations at the site in the 1950s. In 1967, a 2,000-gallon inventory loss was discovered. The adjacent property owner (presumably at 3014 Lakeshore) complained about gasoline odors in the basement. The steel USTs were replaced with new USTs double wrapped in asphalt. A 32" long gash was observed in one of the removed tanks.

Leak Detection, UST Replacement, and Installation of Recovery System

In 1980, a tenant in the adjacent building complained of a gasoline odor most likely from the air conditioning system that obtained air from the basement, which created negative pressure in the basement that drew vapor from the subject site. A tank tightness test showed that the USTs at the Chevron site might have had a slight leak. The USTs were replaced with new fiberglass USTs and lines. The removed tanks were found to be tight, but some old product was found in the excavation. An unknown quantity of hydrocarbon impacted soil (reportedly several dozen truckloads) was removed from the site.

A recovery system consisting of a plastic barrier 14 to 16 feet deep was installed along the southwestern property line, against the basement wall of the adjacent building. Six wells were installed to recover any remaining product beneath the site, however, product and water infiltration problems continued in the adjacent building's basement.

Discovery of Free Product in Soil and Installation of Extraction Well

In May 1981, a large pocket of free product was discovered while checking on the remediation system. In July 1981, four additional observation wells were installed. A 24-inch diameter extraction well was installed near the UST pit area, but it appears that the recovery system was not turned on for any significant length of time. A pumping test performed in February 1982, indicated that groundwater depression could not be achieved even at 200 gallons per minute (heavy rains contributed to inflow of groundwater).

UST Abandonment and Station Remodel

In 1984, aboveground station facilities were renovated, but the USTs were not replaced. Two old USTs were discovered beneath the sidewalk and abandoned in place by filling with grout. Approximately 741 cubic yards of soil were removed during station reconstruction activities. It is not clear whether that soil was removed because of hydrocarbon impact. Tenants in the building at 3014 Lakeshore Avenue again complained of a gasoline odor in their building. No odor or sheen was noted in the basement sump during site inspection. In a letter sent to the property owner from

DG90121C.4C01

SITE CONCEPTUAL MODEL

Chevron Service Station #9-0121 3026 Lakeshore Avenue Oakland, California Page 3

Chevron stated that during the two previous years that Chevron had been inspecting the basement of their building for odor or product in the sump, they did not find evidence of any hydrocarbons.

In March 1985, a water sample collected from the basement of the adjacent building (collected in response to an odor complaint) indicated a presence of aromatic compounds typical of gasoline products.

In December 1990, a gage stick hole was discovered in the unleaded gasoline UST. The hole was repaired and the UST went back into service.

In 1993, a drive off occurred and a small quantity of product was released into pea gravel beneath the dispenser.

Well Destruction and Installation of Monitoring Wells

In April 1991, the existing wells at the site were located and sampled, but it was observed that most of the wells were damaged beyond repair, most likely due to site reconstruction activities in 1984. All wells except the 24-inch extraction well were destroyed in July 1991. The extraction well was destroyed in September 1996.

Four 3/4-inch diameter on-site monitoring wells (MW-1 through MW-4) were installed in August 1991, and regular groundwater monitoring and sampling began. Four 2-inch diameter off-site monitoring wells (MW-5 through MW-8) were installed in July 1992.

Product Line and Dispenser Replacement

In September 1996, product lines and dispensers were replaced. Fifteen soil samples were collected from beneath the product lines and dispensers at depths ranging from 2.5 to 3 feet bgs). Soil sample chemical analytical data indicated that shallow soil beneath the site has been impacted by gasoline hydrocarbons.

Monitoring Well Installation and Replacement

In April 1999, groundwater monitoring well MW-9 was installed, and the 3/4-inch diameter wells MW-2 through MW-4 were abandoned and replaced with 2-inch diameter wells MW-2A through MW-4A, respectively.

All wells at the site except MW-5 are screened at various depths between 2 to 25 feet bgs. The screen interval in well MW-5 extends from 15 to 35 feet bgs. The top-of-casing of well MW-5 is at a higher elevation than the other wells at the site, and well MW-5 is in an area that appears to be semiconfined. Based on historical groundwater measurements (ranging from 9.74 to 13.75 feet bgs), the screened interval in the well is flooded, therefore, groundwater samples collected from well MW-5 may not detect gasoline hydrocarbons, which tend to concentrate near the groundwater surface.

Groundwater Monitoring and Sampling

Currently all on-site wells are sampled quarterly, and off-site wells are sampled biannually (MW-5 and MW-6) or annually (MW-7 and MW-8) for Total Petroleum Hydrocarbons as gasoline and diesel (TPHg and TPHd), benzene, toluene, ethylbenzene, and xylenes (BTEX), and methyl tert-butyl ether (MtBE). All wells are monitored quarterly. ORC was installed in well MW-1 in 1999 to enhance natural bioremediation. Historical groundwater monitoring and sampling data are in Appendix B, and historical potentiometric maps are in Appendix D.

During the most recent monitoring and sampling event on June 4, 2001, all wells were monitored, and only wells MW-1, MW-2A, MW-3A, MW-4A, and MW-9 were sampled. TPHg were detected in wells MW-1, MW-4A, and MW-9 at concentrations up to 3,200 ppb. Benzene and MtBE were detected in all wells ranging in concentrations from 2.0 to 310 ppb, and 37 to 7,800 ppb, respectively. TPHd were detected in all wells at concentrations up to 1,200 ppb. Figures 6 through 9 are isoconcentration maps for TPHg, benzene, MtBE, and TPHd, respectively, based on data collected during the March 1, 2001 event when all wells were sampled. Wells MW-5 through MW-8 are sampled semi-annually or annually, and were last sampled on March 1, 2001. At that time, these wells were non-detect for TPHg, TPHd, benzene, and MtBE, except for well MW-8 that had TPHd at a concentration of 51 ppb.

During the June 4, 2001 event, depth to water ranged from 1.52 to 11.31 feet below top of casing, with groundwater flow in the eastern corner of the site to the southeast, and flow to the southwest near the western corner of the site at gradients from 0.01 to 0.02.

Geology and Hydrogeology

The subject site is located approximately 1.75 miles northeast of the Oakland Inner Harbor, and approximately 3.75 miles northeast of San Francisco Bay. As mapped by E.J. Helley and others (1979, Flatland Deposits of the San Francisco Bay Region, California: U.S. Geological Survey Professional Paper 943), soil in the site vicinity consists of Holocene age estuarine deposits consisting of unconsolidated, water-saturated, dark, plastic clay and silty clay rich in organic material (Bay Mud) overlying Holocene age alluvial deposits of unconsolidated, moderately sorted, permeable sand and silt and Pleistocene alluvial deposits of weakly consolidated, poorly sorted, irregular interbedded clay, silt, sand, and gravel.

The boring logs indicate that the subject site is underlain by clays interbedded with silt, silty sand, and fine sand layers to the total depth explored of 35 feet bgs. Boring logs are included in Appendix E. Groundwater was encountered beneath the site at depths ranging from 4 to 10 feet bgs with the exception of well MW-5. Groundwater in well MW-5, which is located at the significantly higher elevation than the other wells, was encountered at a depth of 23 feet bgs and stabilized at a depth of 12.24 feet bgs. Groundwater in the area of well MW-5 appears to be in the semiconfined condition. Groundwater flow beneath the site is to the southwest in the northwestern part of the site and to the southeast under the eastern part of the site.

RECEPTOR SURVEY

Well Survey

Well data obtained by GR from the County of Alameda Public Works Agency (CAPWA) indicates that 33 monitoring wells and one cathode well are located within ½ mile of the Chevron site. Table 1 lists these wells and Figure 1 shows their locations. No water supply wells are located within ½ mile of the site according to the CAPWA.

Underground Utility Survey

GR obtained utility maps from the City of Oakland Public Works Department (sewer and storm drain), East Bay Municipal Utility District, or EBMUD (water), and Pacific Gas & Electric (gas and electric). Figure 2 shows the location of buried utility lines in the vicinity of the Chevron site.

Underground utility lines in Lakeshore Avenue include one 6'3"x10' storm drain, one 27-inch diameter sanitary sewer line, and water, gas, and electric lines. Underground utility lines in MacArthur Boulevard and Excelsior Court include sanitary sewer, gas, and water lines. Along the southeast property boundary of the Chevron site, adjacent to Excelsior Court, is a 7-foot diameter storm drain line located between approximately 6 to 13 feet below ground surface (bgs)

The specific depths of water, electric, or gas lines were not available, however these lines are usually buried shallower than 5 feet bgs. According to the EBMUD, water lines are usually buried between 3 and 5 feet bgs.

SITE CONCEPTUAL MODEL

The site conceptual model was prepared based on the site assessment and quarterly monitoring and sampling data collected at the site to date. A pictorial representation of the site conceptual model is presented on Figures 3 and 4.

Release Scenario and Plume Characterization

Shallow soil at the subject site has been impacted with fuel hydrocarbons at concentrations up to 4,100 parts per million (ppm) of TPHg, 100 ppm of TPHd, 40 ppm of benzene, and 31 ppm of MtBE. Impacted soil is present within a smear zone (2.5 to 11 feet bgs) over the area of the dissolved hydrocarbon plume. The highest hydrocarbon concentrations have been present in soil beneath the northern and middle dispenser islands. An unverified amount of soil has been removed from the site during UST replacement in 1980 and site reconstruction in 1984.

Groundwater beneath the site has been impacted by fuel hydrocarbons. Historically, floating product was present on groundwater beneath the site. A recovery system was installed which consisted of a 14 to 16 foot deep plastic barrier along the southwestern (downgradient) property boundary, and seven recovery wells.

DG90121C.4C01

Hydrocarbons have been detected in groundwater beneath the site at concentrations up 60,000 parts per billion (ppb) of TPHg, 7,100 ppb of benzene, and 160,000 ppb of TPHd. MtBE has been reported at concentrations up to 63,000 ppb by EPA Method 8020. The highest hydrocarbon concentrations have been present in wells MW-1 and MW-2. These two wells have also contained floating product or product sheen (up to 0.75 feet thick). Floating product was removed from well MW-2 between June 1995 and March 1999 by bailing (total of 0.364 gallons removed).

Currently, floating product is not present on groundwater beneath the site. Hydrocarbon concentrations have decreased significantly in on-site wells MW-1 and MW-2A through MW-4A, and have not changed significantly in on-site well MW-9, since well installation. TPHg, benzene, and MtBE concentrations in off-site wells MW-5 through MW-8 generally have remained non-detectable (low concentrations detected only on few occasions), and TPHd concentrations in these wells decreased. However, groundwater samples collected from well MW-5 may not be representative of shallow groundwater conditions because of a deeper screen interval. In December 1998, groundwater samples from wells MW-1 and MW-3 through MW-8 were analyzed for bioremediation indicator parameters (sulfate, nitrate, ferrous iron and total alkalinity) to evaluate the occurrence of intrinsic bioremediation. Results of the analysis were inconclusive.

The existence of the plastic barrier influences groundwater flow direction beneath the site, causing groundwater mounding in the western portion of the site. West of the barrier, the groundwater flow direction has been consistently toward the southwest. In the eastern portion of the site, the groundwater has been flowing generally toward the southeast. The groundwater flow direction in the eastern and southern portions of the site may be influenced by the presence of the 7-foot-diameter storm drain. The gradient has ranged from 0.01 to 0.03

TPHg, benzene, and MtBE have been delineated to the west, north and east in wells MW-6, MW-7, and MW-8. Unidentified hydrocarbons in the TPHd range are present in wells MW-6 and MW-8 at concentrations of 190 ppb and 51 ppb, respectively. The dissolved hydrocarbon plume appears to be shrinking. However, the groundwater condition beneath the commercial buildings immediately southwest of the subject site (downgradient side of the plastic barrier) is unknown. The plume has not been delineated downgradient (southeast) of well MW-3A, and plume delineation south of the site is not certain due to the deeper screen interval in well MW-5.

Potential Environmental Receptors

The hydrocarbon plume extends beneath the area, which currently is used for commercial purposes (gasoline sale) and transportation (Lakeshore Avenue and possibly MacArthur Boulevard and Excelsior Court). Most of this area is paved with asphalt or concrete. The Chevron island marketer building is present within the plume area. The edges of the plume may extend beneath the building located at 3014 Lakeshore Avenue, which is adjacent to the southwest property boundary of the Chevron site, however, the hydrocarbon concentrations in this area are expected to be low. The nearest residential buildings, located southeast of the site across Excelsior Court, are most likely

outside the plume area based on analytical data from wells MW-3A and MW-5. No water producing wells are located within ½ mile of the Chevron site.

Potential exposure receptors include current and future workers and customers of the Chevron station and building at 3014 Lakeshore Avenue, motorists, pedestrians, and utility maintenance workers. The potential exposure mediums are ambient air, indoor air in buildings, and soil and groundwater in potential future excavation areas. The major exposure pathway is hydrocarbon volatilization from smear zone soils and groundwater to ambient and indoor air. The potential exposure pathway for utility maintenance workers is dermal contact with hydrocarbon-impacted soil and groundwater.

Other Environmental Issues

The dissolved hydrocarbon plume has not been delineated southeast of MW-3A (downgradient, toward residential buildings). Delineation to the south by MW-5 is questionable due to a flooded screen interval in that well. Replacement of well MW-5 and installing an additional well or boring on the south side of Excelsior Court should be considered. Data from these wells/borings could be used for a Risk Based Correction Action (RBCA) evaluation (residential receptor).

Hydrocarbon concentrations in groundwater beneath the building at 3014 Lakeshore Avenue, adjacent to the southwestern Chevron site property line (downgradient of the plastic barrier) are unknown. Water samples should be collected from the pump sump in the basement of that building and analyzed. Data could be used for a RBCA evaluation (commercial receptor).

Several underground utility lines are present near the subject site, including a 7-foot diameter storm drain along the southeastern property line and a sewer line beneath the southern side of Lakeshore Avenue. Due to shallow groundwater conditions, utility trenches may be a factor in plume migration.

DISCUSSION AND RECOMMENDATION

Site conditions consist of petroleum-impacted soil and groundwater. Hydrocarbon impacted soil appears to be present within the smear zone between approximately 2 and 11 feet bgs. Concentrations of hydrocarbons in groundwater beneath the site have been decreasing. Natural attenuation processes appear to be facilitating concentration decreases and limiting hydrocarbon migration.

The dissolved hydrocarbon plume has been delineated to the west, north, and east, but not to the south. The northwestern edge of the plume may extend beneath Lakeshore Avenue, and the southeastern edge of the plume may extend beneath Excelsior Court, where underground utilities are present. Due to shallow groundwater conditions, the utility trenches may act as preferential pathways and conduits that could enhance contaminant migration.

Since the primary sources have been removed and the plume appears to be shrinking, natural attenuation may be the preferable approach to remediate the site. However, before this approach is considered, potential threats to human health and the environment must be evaluated. The existing

DG90121C.4C01

site data are not sufficient to perform an appropriate risk evaluation for the identified receptors. GR recommends the following additional environmental investigation to obtain site-specific data to be used in risk evaluation:

- Continue quarterly monitoring and sampling at the site on the current schedule.
- Repeat the analysis for bioremediation indicator parameters (sulfate, nitrate, ferrous iron, total alkalinity, dissolved oxygen) to evaluate the occurrence of intrinsic bioremediation.
- Investigate if underground utility trenches adjacent to the Chevron site are acting as preferential pathways for hydrocarbon migration by advancing borings next to utility lines (specifically sanitary sewer and storm drain lines) and collecting grab groundwater samples.
- Install additional wells, properly screened, on the south side of Excelsior Court to investigate hydrocarbon migration to the southeast toward neighboring residential buildings.
- Collect water samples from the pump sump in the basement of 3014 Lakeshore Avenue to investigate possible hydrocarbon migration around the plastic barrier at the southwest boundary of the Chevron site.

GR recommends conducting a Risk Based Corrective Action (RBCA) evaluation as described in ASTME-1739 based on the data collected from additional environmental investigation to determine whether further site assessment and/or active remediation is necessary at the site.

TABLES

TABLE 1 - WELL SEARCH DATA

Chevron Service Station No. 9-0121 3026 Lakeshore Avenue Oakland, California

Map	Well	Well	Alameda County	Well	Year
ID ^[1]	Owner	Location	Well ID	Use	Installed
1	Chevron USA	460 Grand Avenue	1S/4W 25P16	Monitoring	1995
2	EBMUD	Athol Avenue & Macarthur Boulevard	1S/3W 31D1	Cathode	1998
3	Lamorinda Development	3329 Lakeshore Avenue	1S/4W 25J1	Monitoring	1994
4	Quik Stop Markets	363 Grand Avenue (3 Wells)	1S/4W 25P1-3	Monitoring	1988
4	Quik Stop Markets	363 Grand Avenue (5 Wells)	1S/4W 25P4-8	Monitoring	1990
4	Quik Stop Markets	363 Grand Avenue	1S/4W 25P12	Monitoring	1990
5	Ranger Pipeline	637 Beacon	1S/4W 25R1	Monitoring	1989
6	Shell Oil Company	350 Grand Avenue	1S/4W 25P9	Piezometer	1990
6	Shell Oil Company	350 Grand Avenue (2 Wells)	1S/4W 25P10-11	Monitoring	1991
7	Texaco Inc.	500 Grand Avenue (4 Wells)	1S/4W 25Q1-4	Monitoring	1988
7	Texaco Inc.	500 Grand Avenue (2 Wells)	1S/4W 25Q1-2	Monitoring	1989
7	Texaco Inc.	500 Grand Avenue (3 Wells)	1S/4W 25Q3-4	Monitoring	1990
7	Texaco Inc.	500 Grand Avenue (2 Wells)	1S/4W 25Q10-11	Monitoring	1993
8	Unocal Corporation	3220 Lakeshore Avenue	1S/4W 25R2	Monitoring	1990
8	Unocal Corporation	3220 Lakeshore Avenue (2 Wells)	1S/4W 25R3-4	Test	1990
8	Unocal Corporation	3220 Lakeshore Avenue (3 Wells)	1S/4W 25R22-24	Monitoring	1994
8	Unocal Corporation	3220 Lakeshore Avenue	1S/4W 25R25	Observation	1997

Notes

Well data in this table obtained from the County of Alameda Public Works Agency.

^[1]Well location numbers correspond to Figure 1.

FIGURES



Source: Street Atlas USA, Delorme (1995).

FIGURE



Gettler - Ryan Inc.

6747 Sierra Ct., Suite J Dublin, CA 94568

(925) 551-7555

VICINITY MAP Chevron Service Station No. 9-0121 3026 Lakeshore Avenue Oakland, California


DATE


REVISED DATE


JOB NUMBER 346462


REVIEWED BY

05/99











DG90121C.4C01





March 1, 2001

DG90121C.4C01 FILE NAME: P:\ENVIRO\CHEVRON\9-0121\A01-9-0121.DWG | Layout Tab: Tphg1 9-01

PROJECT NUMBER







APPENDIX A

TABLE A

SAMPLING SUMMARY

Chevron Service Station No. 9-0121

3026 Lakeshore Avenue, Oakland, California

Results in mg/Kg - parts per million (ppm), unless otherwise noted

PIPING TRENCH AND DISPENSER SAMPLING RESULTS

PIPING TREN	DEPTH (ft.)	DATE	TPH- Gasoline	Benzene	Toluene	Ethyl- Benzene	Xylenes	МТВЕ	Lead
			- <u> </u>	ND	ND	ND	ND	ND	18
P1-3'	3	3-Sep-96	ND	ND	ND	ND	ND	ND	12
P2-2'	2	3-Sep-96	ND	ND	ND	ND	0.005	0.63	25
P3-2.5'	2.5	3-Sep-96	ND	0.0056		7.8	78	15	28
P4-2.5'	2.5	3-Sep-96	710	ND	19 NO	ND	0.46	ND	14
P5-3'	3	3-Sep-96	110	ND ND	ND 0.15	0.033	0.18	2.5	6.6
P6-3'	3	3-Sep-96	1.3	0.021	0.15	0.0063	0.024	0.49	8.0
P7-3'	3	3-Sep-96	ND -	ND	0.0071	51	30	31	20
P8-2.5'	2.5	3-Sep-96	4,100	33	19	5.4	5.0	9.7	13
P9-2'	2	3-Sep-96	1,400	ND	22	4.8	2.4	ND	52
P10-2.5'	2.5	3-Sep-96	410	8.3	ND ND	25	26	ND	15
P11-3'	3	3-Sep-96	1,600	25	ND	23	12	ND	20
P12-2.5'	2.5	3-Sep-96	2,200	28	ND		1.3	ND	36
	3	3-Sep-96	290	6.1	4.0	2.1	7.5 76	ND	19
P13-3'	2.5	3-Sep-96	2,500	40	20	27		ND	44
P14-2.5' P15-2.5'	2.5	3-Sep-96	1,000	23	ND	13	3.0	ND	

STOCKPILE SAMPLING RESULTS

PSP-1(A-D)	4-Sep-96	1,000	3.3	3.0	8.4	5	55 	1.3
STOCKPILE SAMPLE ID	DATE	TPH-Gasoline		Toluene	Ethyl- Benzene	Xylenes	Lead	STLC Lead


NOTES:

TPH-Gasoline = Total Petroleum Hydrocarbons calculated as gasoline.

MTBE = Methyl t-Butyl Ether

ND = Not detected at or above the laboratory detection limits.

ppm = Parts per Million, results reported in mg/Kg by the laboratory.





SITE PLAN AND SAMPLE LOCATION MAP

FIGURE

Chevron Service Station No. 9-0121 3026 Lakeshore Avenue Oakland, California

DATE:

DRAWN BY:

BASE MAP

Robert H. Lee Associates - Site Plan 8/96

Table 3 Soil Analytical Results	Chayron Service Station #9-0121	. 3026 Lakeshore Avenue,	Oakland, California.

Table 3.	Soil A	nalytical Re	sults - Che	vron Servi	ce Station #5	9-0121, 302	6 Lakeshore A	verrue, Can	iana, ca	Fraction		Bulk Den	-		Moisture
Sample ID	Depth	Date	TPHd	TPHg	Benzene	Toluene	Ethylbenzene	Xylenes	MtBE >	Organic Carbon %	Dry gm/cc	Natural gm/cc	Matrix gm/cc	Porosity %	Cantent %
	(ft)					ррт									
			1	222	1.7	2.8	13	29	< 5.0	. -	-	_	_	_	
MW2A-3	3	04/01/99	281	820		1.7	5.0	2.6	< 10	· —	_			-	
MW2A-6	6	04/01/99	100,	430	< 1	1.7	J.U.			_	1.47	1.92	2.66	44.9	_
MW2A-17	17	04/01/99	_	_	-		_								
									_	0.069	1.98	2.25	2.72	27.2	15
MW3A-5.5	5.5	04/01/99	_			-	-	0.20	<1		_	_		_	
MW3A-6	6	04/01/99	3.8^{2}	41	< 0.1	< 0.1	< 0.1	0.28	< 5	_			_		
MW3A-11	11	04/01/99	9.23	180⁴	0.57	0.52	< 0.50	1.8		0.078	1.60	2.00	2.69	40.5	_
MW3A-15	15	04/01/99				-		-	_	0.076	1.00	2.00	2.07		
M M SW-13	. 13	01/01/22										_			
	2	04/01/99	94³	540 ⁵	0.96	1.6	4.6	1.3	< 2.5	_	-			_	_
MW4A-3	3		723	1,1006	5.6	13	2.4	18	< 10	-	-	_			
MW4A-6	6	04/02/99	12	1,100	2.0										
	_	0.4104.400	1.27	225	0.036	0.048	0.028	0.091	0.089	-	_	_	_		
MW9-3	3	04/01/99		8.36	0.011	0.033	0.010	0.078	0.18	- .				_	_
MW9-6	6	04/02/99	< 1.0	0.3	0.011	Ų.055				•					
			0	45	0.15	0.21	0.45	0.79	_	_	-	-		_	
SP-(A-D)	_	04/02/99	<1.0	45	0.15	0.21	5.15								

EXPLANATION:

TPHd - Total Petroleum Hydrocarbons as diesel

TPHg - Total Petroleum Hydrocarbons as gasoline

MtBE - Methyl t-Butyl Ether

ft - Feet

ppm - Parts per million

gm/cc - gram per cubic centimeter

- Not analyzed/not applicable
- 1 = Laboratory report indicates unidentified hydrocarbons > C9
- ² Laboratory report indicates unidentified hydrocarbons < C14
- ³ = Laboratory report indicates unidentified hydrocarbons C9-C24
- 4 Laboratory report indicates gasoline and unidentified hydrocarbons < C8
- 5 Laboratory report indicates gasoline and unidentified hydrocarbons C6-C12
- 6 Laboratory report indicates gasoline and unidentified hydrocarbons < C7
- ⁷ = Laboratory report indicates unidentified hydrocarbons > C14

ANALYTICAL METHODS:

TPHg, benzene, toluene, ethylbenzene, xylenes, MtBE = EPA Methods 5030/8015Mod/8020

TPHd - EPA Method 3550/8015Mod

Porosity, densities - Method API RP-40

ANALYTICAL LABORATORY:

Seguoia Analytical (ELAP #1271)

TABLE 2 ANALYTICAL RESULTS FOR SOIL SAMPLES COLLECTED ON JUNE 12 AND 19, 1992 (Concentration in parts per million)

BORING	SAMPLE ID	DATE DEPTH		BENZENE	TOLUENE	ETHYL- BENZENE	XYLENES	TPH-AS- GASOLINE	TPH-AS- DIESEL
NAV 4	MW1A	6/19/92	20.5	0.006	0.019	< 0.005	0.015	<1	<1
MW-1 MW-5	MW5D	6/12/92	20.5	<0.005	< 0.005	< 0.005	<0.005	<1	<1
	MW6A	6/12/92	5.5	<0.005	< 0.005	< 0.005	<0.005	<1	<1
MW-6		6/12/92	5.5	<0.005	< 0.005	< 0.005	<0.005	<1	<1
MW-7 MW-8	MW7A MW8A MW8B	6/19/92	5.5 10.5	<0.005 <0.005	<0.005 0.006	<0.005 0.012	<0.005 0.078	<1 13	<1 2*

Total petroleum hydrocarbons

The analytical laboratory reported that the pattern observed in the chromatogram was not typical of diesel.

TABLE 2 SOIL SAMPLE ANALYTICAL RESULTS (Results in parts per million)

							4.000000000000000000000000000000000000	
SAMPLE	SAMPLE DATE	DEPTH (ft)	BENZENE	TOLUENE	ETHYL- BENZENE	XYLENES	TPH-AS- GASOLINE	TPH-AS- DIESEL
ID			1.5	1.2	2.3	4.6	660	4
MW-2A	08/07/91	2			11.0	4.3	540	17
MW-2B	08/07/91	7	2.8	1.3	11.0			0
MW-3A	08/13/91	2	0.021	<0.005	<0.005	<0.005	<1.0	2
		9	3.0	3.7	5.0	8.0	660	34
MW-3B	08/13/91		3.0		0.0	7.4	560	13
MW-4A	08/13/91	3	<0.6	4.5	3.6	1.4		_
MW-4B	08/13/91	8	0.170	0.290	0.110	0.220	31	2

TABLE 3 WATER SAMPLE ANALYTICAL RESULTS SAMPLES COLLECTED ON AUGUST 20, 1991 (Results in parts per billion)

well D	BENZENE	TOLUENE	ETHYL- BENZENE	XYLENES	TPH-AS- GASOLINE	TPH-AS- DIESEL *
WELT ID		21	220	34	5,100	260
MW-1	1,700	55	530	75	9,300	600
MW-2	3,700	13	15	12	3,100	200
MW-3	200	13	3	9	1,800	160
MW-4	870	4	<u> </u>	<u> </u>		

^{*} Gasoline pattern present in sample




Table 1
Groundwater Monitoring Data and Analytical Results

Chevron Service Station #9-0121 3026 Lakeshore Avenue Oakland, California

				SPH	SPH								
WELL ID/	тос	GWE	DTW	Thickness	Removed	TPH-D	TPH-G	В	T	E	X	MTBE	TDS
DATE	(ft.)	(msl)	(ft.)	(ft.)	(gallons)	(ppb)	(ppb)	(ppb)	(ppb)	(ppb)	(ppb)	(ppb)	(ppb)
DATE	UNI	100007	V .772			-							
MW-1								1 700	21	220	34		
08/20/91	6.82	1.62	5.20			260	5,100	1,700	21		3 4		
09/30/91	6.82	1.15	5.67	Sheen									
10/28/91	6.82	1.50	5.30	0.03					12	 95	31		
01/08/92	6.82	1.67	5.15	Sheen		4,400	5,400	770	13	95 			
01/13/92	6.82							1.500	40	230	100		
06/23/92	6.89	1.48	5.41			2,000	7,700	1,500	40	230			
08/24/92	6.89	1.12	5.77						 20	190	 78		
09/21/92	6.89	1.00	5.89			<50	3,500	1,700	28	-			
10/26/92	6.89	0.95	5.94			- -			240	2,000	1,300		
12/23/92	6.89	2.18	4.71	+-		5,500	60,000	7,100	240	•		 	
01/08/93	6.89									67	 79		
03/25/93	6.89	2.17	4.72			<10	530	1,100	41	67 120	79 69	9,600	840
06/11/93	6.89	5.37	5.07				7,000	1,900	33	43	74		
09/29/93	6.89	1.13	5.76			<10	6,600	1,600	28	43 82	65		
12/20/93	6.89	1.74	5.15			<10	6,300	1,900	36 55		. 38	12,000	
03/07/94	6.89	2.21	4.68			<10	7,700	1,100	55	66	38	12,000	
06/17/94	6.89	1.83	5.06			2,200	4,300	710	12	90		12,000	
09/12/94	6.89	1.24	5.65			2,500	6,400	1,500	<25	180	<25	3,900	
11/30/94	6.89	2.32	4.57			2,300 ¹	4,900	690	26	97	60	1,300	
03/24/95	6.89	3.91	2.98			$1,400^2$	1,800	160	7.3	11	14	5,100	
06/27/95	6.89	1.87	5.02			$2,300^2$	4,600	1,300	11	97	13	5,800	
09/28/95	6.89	1.59	5.30			3,900 ²	6,600	1,500	<20	<20	<20	6,300	
12/19/95	6.89	2.21	4.68			$2,600^2$	3,800	930	<10	100	<10		
02/28/96	6.89	3.27	3.62			$1,800^2$	3,600	280	<5.0	18	5.5	2,200	
06/25/96	6.89	1.87	5.02			3,000	4,700	1,600	36	150	31	3,000	
12/17/96	6.89	2.23	4.66			$2,700^3$	7,800	1,000	28	340	63	1,200	
03/31/97	6.89	2.01	4.88			$2,200^2$	5,300	590	55	210	53	950	
06/30/97	6.89	1.32	5.57			$2,200^{2}$	4,400	350	<10	<10	11	580	
09/12/97	6.89	1.56	5.33			$2,300^2$	3,400	220	9.5	15	11	460	

Table 1
Groundwater Monitoring Data and Analytical Results
Chevron Service Station #9-0121

Chevron Service Station #9-012 3026 Lakeshore Avenue Oakland, California

					C)akland, Ca	IIIOI IIIa						
WELL ID/	TOC	GWE	DTW	SPH Thickness	SPH Removed		TPH-G	B (ppb)	T (ppb)	E (ppb)	X (ppb)	MTBE (ppb)	TDS (ppb)
DATE	(ft.)	(msl)	(ft.)	(ft.)	(gallons)	(ppb)	(рри)	(рро)					
MW-1 (cont)						1,900 ²	4,700	870	21	120	18	750	
12/05/97	6.89	2.44	4.45			1,600 ²	4,400	120	12	11	7.7	270	
02/16/98	6.89	3.52	3.37			1,300 ²	7,800	<25	50	34	650	650	
06/17/98	6.89	2.24	4.65			$2,400^2$	3,700	620	17	120	31	380	
08/31/98	6.89	1.70	5.19			$1,500^2$	3,800	250	14	28	15	330	
12/28/98	6.89	1.94	4.95	. 				17.9	<0.5	4.17	1.05	70.4	
03/04/99	6.89	3.24	3.65			1,070 ²	1,560	820	240	320	640	<500	
06/14/99	6.89	1.89	5.00			$2,500^2$	<10,000	141	12.3	<10	<10	238	
09/17/99	6.89	0.30	6.59			$2,110^2$	3,300	2:18 '	16.3	20	<10	232	
12/20/99	6.89	1.92	4.97			$1,840^2$	2,990	210		1.87	1.87	29.1	
03/20/00	6.89	3.11	3.78			938 ²	1,340	20	3.07	<2.5	7.9	190	
06/24/00 ⁵	6.89	2.45	4.44	0.00		1,6809	1,500 ⁷	12	5.3	<2.5 14	<10	210	
09/07/00 ⁵	6.89	1.74	5.15	0.00		1,500 ⁹	3,100 ⁷	190	13		<5.00	<25.0	
12/05/00	6.89	2.16	4.73	0.00		970 ¹³	2,140 ¹⁴	248	<5.00	20.5		280	
	6.89	3.33	3.56	0.00		610 ⁹	1,000 ⁷	21	<10	<10	<10	200	
03/01/01	0.02	3.00											
MW-2						600	9,300	3,700	55	530	75		
08/20/91	6.27	1.92	4.35			600	3,500	2,600	47	440	68		
09/30/91	6.27	1.28	4.99	, 			4,600	1,800	29	290	53		
10/28/91	6.27	1.36	4.91			·	14,000	4,300	70	<25	130		
01/08/92	6.27	1.63	4.64	Sheen									
01/13/92	6.27					38,000							 ,
06/23/92	6.27	1.63	4.64	0.02									
08/24/92	6.27	1.34	4.94	0.02		·							
09/21/92	6.27	1.20	5.08	0.01									
10/26/92	6.27	0.34	5.93				, 			1 200	160		
12/23/92	6.27					160,000	21,000	5,400	59	1,300			
	6.27	2.57	3.70			·							
01/08/93		2.89	3.38	Sheen	· · ·	, ·	•						
03/25/93	6.27	2.09	4.18			, 	5,900	1,100	23	240	51		2,300
06/11/93	6.27	4.09	7.10							,			٨٥

Table 1 Groundwater Monitoring Data and Analytical Results

Chevron Service Station #9-0121 3026 Lakeshore Avenue Oakland, California

				SPH	SPH	mbu P	TPH-G	В	Т	E	X	MTBE	TDS	
WELL ID/	TOC	GWE	DTW	Thickness				D (ppb)	(ppb)	(dqq)	(ppb)	(ppb)	(ppb)	
DATE	(ft.)	(msl)	(ft.)	(ft.)	(gallons)	(ppb)	(ppb)	(рро)	(рро)	W V V V V V V V V V V V V V V V V V V V	· PF-3			
MW-2 (cont)			•											
09/29/93	6.27	0.07	6.20											
12/20/93	6.27	1.94	4.35	0.02										
03/07/94	6.27	2.60	3.67			<10	26,000	5,700	170	1,000	150			
06/17/94	6.27	2.25	4.02	Sheen										
09/12/94	6.27	1.45	4.83	0.01										
11/30/94	6.27	2.27	4.00			INACCES	SIBLE							
03/24/95	6.27	2.73	4.01	0.59										
06/27/95	6.27	1.71	4.96	0.50	0.013									
09/28/95	6.27	2.62	4.25	0.75	0.013									
12/19/95	6.27	1.99	4.76	0.60	0.010									
02/28/96	6.27	1.99	4.58	0.38	0.008					. 				
06/25/96	6.27	2.36	4.29	0.47	0.030									
12/17/96	6.27	2.22	4.16	0.14										
03/31/97	6.27	2.34	4.07	0.18	0.030									
06/30/97	6.27	2.06	4.32	0.14	0.030									
09/12/97	6.27	2.00	4.38	0.14									~-	
12/05/97	6.27	2.51	3.78	0.02		 :								
02/16/98	6.27	3.08	3.29	0.12	0.007									
06/17/98	6.27	2.35	4.00	0.10	0.010									
08/31/98	6.27	0.65	5.71	0.11	0.008									
12/28/98	6.27	1.75	4.60	0.10	0.005									
03/04/99	6.27	2.58	3.73	0.05	0.200									
DESTROYE														
DEGTRO 12.														
MW-2A				•										
04/19/99	6.53	1.67	4.86			820 ²	<2000	<20	<20	<20	<20	9200		
06/14/99	6.53	1.23	5.30			$2,000^2$	<5000	89	<50	66	<50	10,000		
09/17/99	6.53	0.69	5.84			$1,050^2$	903	42	1.63	22.8	7.74	11,400		
12/20/99	6.53	-0.07	6.60			$2,820^{2}$	2,280	115	<10	87.2	27.2	14,000		
12/20/99	0.55	-0.07	0.00			, –	•							

As of 03/01/01

Table 1
Groundwater Monitoring Data and Analytical Results
Chevron Service Station #9-0121

3026 Lakeshore Avenue Oakland, California

				SPH	SPH	TPH-D	TPH-G	В	Т	E	X	MTBE	TDS
WELL ID/	TOC	GWE	DTW				(ppb)	(ppb)	(ppb)	(ppb)	(ppb)	(ppb)	(ppb)
DATE	(ft.)	(msl)	(ft.)	(ft.)	(gallons)	(ppb)	(PPO)	W. K. Z. A. G. G. G. G.					
												10.0002	
MW-2A (cont)			. 2-			$1,220^2$	1,040	54.3	<5.0	33.8	12.1	10,900 ²	
03/20/00	6.53	1.74	4.79			1,3009	690 ⁷	50	2.5	18	9.5	15,0008	
06/24/00	6.53	1.28	5.25	0.00		7709	310 ⁷	6.7	1.4	1.6	3.8	16,000	
09/07/00	6.53	1.09	5.44	0.00		810 ¹³	41414	32.4	< 0.500	7.49	5.96	8,9108	
12/05/00	6.53	1.16	5.37	0.00		590°	370 ⁷	30	4.0	12	9.2	8,200	
03/01/01	6.53	2.03	4.50	0.00							•		
MW-3			0 15			200	3,100	200	13	15	12		
08/20/91	8.71	0.26	8.45				1,000	150	8.3	13	6.7		
09/30/91	8.71	-0.03	8.74				1,200	120	6.7	11	7.5		
10/28/91	8.71	-0.05	8.76 8.77	 ·			410	120	0.9	4.1	3.4	'	
01/08/92	8.71	-0.06	8.77			220					 ,		
01/13/92	8.71					<50	630	43	0.8	8.2	3.4		
06/23/92	8.71	0.03	8.68										
08/24/92	8.71	-0.14	8.85			<50	1,800	730	1.4	66	. 39		
09/21/92	8.71	-0.23	8.94								- -		
10/26/92	8.71	-0.36	9.07			850	840	270	3.4	15	4.2		
12/23/92	8.71				, 	830							
01/08/93	8.71	1.02	7.69			<10	760	270	4.0	10	5.0	 .	
03/25/93	8.71	0.97	7.74			<10 	200	32	1.0	5.0	2.0		5,600
06/11/93	8.71	0.19	8.52				9,300	2,800	60	270	62		
09/29/93	8.71	2.66	6.05			 <10	460	250	4.0	8.0	4.0		,
12/20/93	8.71	-0.12	8.83				2,400	260	13	35	18	·	
03/07/94	8.71	0.64	8.07			<10 <50	1,000	200	4.0	6.6	6.7		
06/17/94	8.71	0.19	8.52	•			360	130	3.4	4.8	3.3	130	
09/12/94	8.71	-0.21	8.92			<50 INACCE				·			
11/30/94	8.71	0.58	8.13					920	<10	23	<10	70	
03/24/95	8.71	1.93	6.78		·	1,200 ²		640	16	31	<10	<50	
06/27/95	8.71	0.49	8.22			$1,000^2$			3.4	4.4	2.4	38	•
09/28/95	8.71	-0.14	8.85			460 ²	490	78	3.4		'		
U7120175	J •												As of

As of 03/01/01

Table 1
Groundwater Monitoring Data and Analytical Results

Chevron Service Station #9-0121 3026 Lakeshore Avenue Oakland, California

							namen in anno anno 1880		ww.comau.coccoccoccocc				
				SPH	SPH			n	T	E	X	MTBE	TDS
WELL ID/	TOC	GWE	DTW	Thickness		TPH-D	TPH-G	В (ь)	(ppb)	(ppb)	(ppb)	(ppb)	(ppb)
DATE	(ft.)	(msl)	(ft.)	(ft.)	(gallons)	(ppb)	(ppb)	(ppb)	(рри)	(рро)	NPP47		
MW-3 (cont)						650 ²	2,600	580	<10	25	<10	<50	
12/19/95	8.71	0.69	8.02		- -	780 ²	1,500	510	<5.0	9.9	<5.0	<25	
02/28/96	8.71	1.16	7.55			$1,200^2$	1,300	390	7.8	14	6.5	31	
06/25/96	8.71	0.34	8.37			$1,200$ $1,100^2$	760	85	<1.2	5.9	5.1	<6.2	
12/17/96	8.71	0.41	8.30			1,100	2,000	380	12	24	12	<25	
03/31/97	8.71	0.52	8.19			620^2	1,900	340	9.9	23	6.1	<25	
06/30/97	8.71	0.00	8.71	••		400^2	1,900	200	4.6	14	4.8	3.9	
09/12/97	8.71	1.07	7.64				460	72	2.7	5.2	1.7	<5.0	
12/05/97	8.71	0.46	8.25			190 ²			20	34	12	<50	
02/16/98	8.71	1.71	7.00			1,000 ²	6,200	1,100	<10	<10	<10	120	
06/17/98	8.71	0.71	8.00			$1,100^2$	3,000	350		8.6	6.0	<12	
08/31/98	8.71	0.08	8.63			790 ²	430	100	2.6	12	<10	<50	
12/28/98	8.71	-0.02	8.73			180 ²	1,400	220	<10	12	<5.0	<20	
03/04/99	8.71	1.06	7.65		**	763 ²	2,880	355	9.15	19	₹3.0	~20	
DESTROYE)									•			
MW-3A									<0.5	<0.5	<0.5	3.1	
04/19/99	8.70	1.00	7.70			93 ²	<50	<0.5		0.53	1.1	3.7	
06/14/99	8.70	0.50	8.20			160 ²	148	4.55	0.82	0.515	0.786	4.68	
09/17/99	8.70	-0.02	8.72			101 ²	169	6.02	0.806		<0.5	11	
12/20/99	8.70	-0.22	8.92			153 ²	<50	1.82	<0.5	<0.5		10.1	
03/20/00	8.70	1.06	7.64			223 ²	140	5.08	0.695	<0.5	< 0.5		
06/24/00	8.70	0.32	8.38	0.00		128 ⁹	<50	0.74	<0.50	<0.50	<0.50	34	
09/07/00	8.70	-0.09	8.79	0.00		<50	<50	1.4	< 0.50	<0.50	<0.50	15	
12/05/00	8.70	0.02	8.68	0.00	, 	<50	<50.0	1.39	< 0.500	< 0.500	<0.500	12.9	
03/01/01	8.70	0.88	7.82	0.00		66 ¹¹	<50	1.0	< 0.50	< 0.50	<0.50	19	

Table 1
Groundwater Monitoring Data and Analytical Results
Chevron Service Station #9-0121

evron Service Station #9-01 3026 Lakeshore Avenue Oakland, California

					O	akianu, Cai	HOIMA						
WELL ID/	TOC (ft.)	GWE	DTW (ft.)	SPH Thickness (ft.)	SPH Removed (gallons)	TPH-D (ppb)	TPH-G (ppb)	B (ppb)	T (ppb)	E (<i>ppb</i>)	X (ppb)	MTBE (ppb)	TDS (ppb)
	(1.17)							870	4.0	3.0	9.0	· ·	
MW-4	7.27	1.32	5.05			160	1,800	830	5.5	2.7	12		
08/20/91	7.37	1.70	5.67				670	990	5.8	4.8	19	"	
09/30/91	7.37	1.56	5.81				2,800		10	7.0	18		
10/28/91	7.37	2.03	5.34				2,900	1,200	10				
01/08/92	7.37	2.03				1,000		 200	6.5	3.0	12		
01/13/92	7.37	2.00	5.37			<50	1,600	380					
06/23/92	7.37	1.62	5.75						5.6	3.7	11		
08/24/92	7.37	1.42	5.95			<50	1,200	480		J.,			
09/21/92	7.37	1.42	5.96			'	'	+- (3.6	3.2	11		
10/26/92	7.37					1,800	1,500	700					
12/23/92	7.37	2.73	4.64						3.0	1.0	4.0		.
01/08/93	7.37	2.73	4.42			<10	520	160		6.0	11		2,600
03/25/93	7.37		5.12	_ 	·		1,200	430	5.0	2.0	14		
06/11/93	7.37	2.25	5.80				1,300	210	8.0		8.0		
09/29/93	7.37	1.57	5.10			3,900	570	230	5.0	4.0	11	22,000	
12/20/93	7.37	2.27				2,600	2,200	290	18	2.5	9.5		
03/07/94	7.37	2.36	5.01			2,800	2,100	480	11	4.3	9.7	63,000	
06/17/94	7.37	1.55	5.82			3,000	1,700	340	6.1	2.7			
09/12/94	7.37	1.73	5.64			INACCES	SSIBLE					12,000	
11/30/94	7.37	1.79	5.58			$3,000^2$	1,500	280	<5.0	<5.0	6.9	32,000	
03/24/95	7.37	2.42	4.95			$3,100^2$	<10,000	310	<100	<100	<100	630	
06/27/95	7.37	-1.42	8.79			$6,300^2$	330	64	1.1	<0.5	<0.5	44,000	
09/28/95	7.37	1.52	5.85			$3,400^2$	3,000	520	<25	<25	<25	32,000	
12/19/95	7.37	1.87	5.50	 :	. <u></u>	4,700 ²	<10,000	230	<100	<100	<100	31,000	
02/28/96	7.37	2.27	5.10			3,100	<10,000	160	<100	<100	<100	22,000	
06/25/96	7.37	1.59	5.78			3,600 ³	<5000	110	<50	<50	<50		
12/17/96	7.37	1.42	5.95			$2,700^2$		130	<25	<25	<25	16,000	
03/31/97	7.37	1.75	5.62			$2,700^{2}$		130	<25	<25	<25	14,000	
06/30/97	7.37	1.34	6.03			2,100 ²		63	<50	<50	<50	15,000	
09/12/97	7.37	1.68	5.69	·	•	'2,600		120	<5.0	<5.0	8.5	15,000	
12/05/97	7.37	2.22	5.15			2,000	1,500			•			As of

Table 1
Groundwater Monitoring Data and Analytical Results
Chevron Service Station #9-0121

Chevron Service Station #9-012 3026 Lakeshore Avenue Oakland, California

				·									
				SPH	SPH			10	T	E	X	MTBE	TDS
WELL ID/	TOC	GWE	DTW	Thickness		TPH-D	TPH-G	В	ı (ppb)	(ppb)	(ppb)	(ppb)	(ppb)
DATE	(ft.)	(msl)	(ft.)	(ft.)	(gallons)	(ppb)	(ppb)	(ppb)	(μρυ)	үро	· · · · · · · · · · · · · · · · · · ·	200000000000000000000000000000000000000	
MW-4 (cont)						1,300 ²	1,200	57	4.5	<2.5	7.0	12,000	·
02/16/98	7.37	1.11	6.26			530 ²	5,300	390	290	28	150	17,000	
06/17/98	7.37	2.41	4.96			$2,400^2$	<50	89	<0.5	<0.5	<0.5	14,000/16,000 ⁴	
08/31/98	7.37	1.46	5.91			$2,400$ $2,900^2$	1,000	52	5.6	4.6	9.1	8,400	
12/28/98	7.37	1.96	5.41			$4,490^2$	<2500	85.5	40.9	<25	<25	11,400	
03/04/99	7.37	2.17	5.20			4,490	<2300	05.5	1012				
DESTROYED)												
MW-4A	7.60	2.78	4.91			370 ²	<500	<5.0	<5.0	<5.0	<5.0	1600	`
04/19/99	7.69	2.76	5.25			$2,500^{2}$	5,360	312	<20	44	<20	2880	
06/14/99	7.69		7.37			$1,430^{2}$	1,290	38.6	<5.0	7.01	<5.0	1780	
09/17/99	7.69	0.32	6.30			$7,480^{2}$	852	43.5	4.63	9.18	4.36	1070	
12/20/99	7.69	1.39	5.62			1,280 ²	1,370	129	8.6	18.3	7.3	2,110	
03/20/99	7.69	2.07 1.57	6.12	0.00		1,190 ⁹	190 ⁷	1.4	1.7	1.7	3.3	3,900 ⁷	
06/24/00	7.69		6.26	0.00		740 ⁹	490 ⁷	15	1.9	1.1	3.9	3,300	
09/07/00	7.69	1.43	5.99	0.00		560 ¹²	<500	<5.00	<5.00	<5.00	<5.00	3,380 ⁸	
12/05/00	7.69	1.70	5.68	0.00		600 ⁹	<1,000	10	<10	<10	<10	4,600	
03/01/01	7.69	2.01	5.00	0.00			,						
MW-5									0.5	<0.5	<0.5		
06/23/92	14.14	1.90	12.24			<50	<50	<0.5	<0.5			<u></u>	
08/24/92	14.14	1.85	12.29				. 			 -0 5	<0.5		
09/21/92	14.14	1.68	12.46			60	<50	<0.5	<0.5	<0.5			
10/26/92	14.14	1.62	12.52										عد
12/23/92	14.14	3.02	11.12				••						
01/08/93	14.14									-0.5	0.9		
03/25/93	14.14	4.40	9.74			<10	<50	<0.5	<0.5	<0.5			770
06/11/93	14.14	3.70	10.44		•••		<50	<0.5	<0.5	<0.5	<0.5		770
09/29/93	14.14	2.22	11.92			<10	<50	<0.5	0.6	<0.5	0.6		

Table 1
Groundwater Monitoring Data and Analytical Results

Chevron Service Station #9-0121 3026 Lakeshore Avenue Oakland, California

				U	akianu, Ca	IIIIOIIII						
			SPH	SPH			D	Т	E	X	MTBE	TDS
TOC	GWE	DTW	Thickness						(ppb)	(ppb)	(ppb)	(ppb)
		(ft.)	(ft.)	(gallons)	(ppb)	(ppo)	(PPC)	17.7		 _		
0.7	energia de la companya del companya de la companya del companya de la companya de											
14.14							<0.5	<0.5	<0.5			
	2.80	11.34					<0.5	<0.5	< 0.5			
	2.87	11.27					<0.5	<0.5	<0.5			
	1.28	12.86					<0.5	<0.5	<0.5			
	2.23	11.91					<0.5	< 0.5	<0.5			
	4.38	9.76						<0.5	<0.5			
	2.74	11.40						<0.5	<0.5			
	2.24	11.90						<0.5	<0.5			
	1.56	12.58						< 0.5	< 0.5			
	2.44	11.70						<0.5	<0.5			
	2.71	11.43						<0.5	<0.5	<0.5		
	2.74	11.40						<0.5	< 0.5	<0.5		
	2.04	12.10			130							
	1.36	12.78					<0.5	< 0.5	<0.5	<0.5	<2.5	
	0.46	13.68										
		13.03						<0.5	<0.5	< 0.5	<2.5	-
		9.97										-
		11.85							< 0.5	<0.5	<2.5	-
		12.82									·	-
		13.43							<0.5	<0.5	3.34	
		13.75			70.5						·	•
		14.10							<0.5	< 0.5	<2.5	
		14.18			<50							
		13.70								<0.5	<2.5	
		12.64				<50						
			0.00			'			<0.50	<0.50	5.0	
					<50							•
				 .					<0.50	< 0.50	<2.5	
				•-	<50	<50	<0.50	70.00				
	TOC (ft.) 14.14	(ft.) (mst) 14.14 14.14 2.80 14.14 1.28 14.14 1.28 14.14 2.23 14.14 2.74 14.14 2.24 14.14 2.56 14.14 2.71 14.14 2.74 14.14 2.74 14.14 2.04 14.14 1.36 14.14 1.36 14.14 1.41 14.14 1.11 14.14 1.32 14.14 1.32 14.14 0.04 14.14 0.04 14.14 0.04 14.14 0.04 14.14 1.50 14.14 1.10 14.14 0.97 14.14 2.86	(ft.) (msl) (ft.) 14.14	TOC (msl) (ft.) (ft.) (ft.) 14.14	TOC GWE (ft.) (mst) (ft.) (ft.) Thickness (gallons) 14.14	TOC GWE DTW Thickness Removed (ft.) (ft.) (ft.) (ft.) (ft.) (gallons) (pph) 14.14	TOC GWE (ft.) Thickness (gallons) (ppb) (ppb) (ppb) 14.14	TOC (ft.) GWE (mst) DTW (ft.) Thickness (gallons) Removed (ppb) TPH-D (ppb) TPH-G (ppb) B 14.14	SPH SPH Thickness Removed TPH-D TPH-G Pph (pph) (pph	TOC GWE DTW Thickness Removed TPH-D TPH-G PPD (ppb) (ppb	TOC GWE DTW Thickness Removed TPH-D TPH-G B T E X [14.14	TOC GWE DTW Thickness (q_1) Removed (q_2) TPLO (q_2) q_2) q_2 <

Table 1
Groundwater Monitoring Data and Analytical Results

Chevron Service Station #9-0121 3026 Lakeshore Avenue Oakland, California

				SPH	SPH	TPH-D	TPH-G	В	T	E	X	MTBE	TDS
WELL ID/	TOC	GWE	DTW	Thickness		(ppb)	(ppb)	(ppb)	(ppb)	(ppb)	(ppb)	(ppb)	(ppb)
DATE	(ft.)	(msl)	(ft.)	(fi.)	(gallons)	(рро)	(рри)	(PP0)	(PPU)	(FF-2	50000 A 5 1 - 5 - 5 - 5 - 5 - 5 - 5 - 5 - 5 - 5		
N 6777 6													
MW-6	4.46	-0.68	5.14			120	<50	4.3	< 0.5	0.8	0.9		
06/23/92	4.46 4.46	-0.49	4.95										
08/24/92 09/21/92	4.46 4.46	-0.44	4.90			<50	<250	<2.5	<2.5	<2.5	<2.5		
10/26/92	4.46 4.46	-1.06	5.52										
10/26/92	4.46	-0.94	5.40			81	<50	<0.5	< 0.5	<0.5	< 0.5		
-01/08/93	4.46												
03/25/93	4.46	-1.64	6.10			<10	<50	< 0.5	<0.5	<0.5	0.7		
06/11/93	4.46	-2.10	6.56				<50	<0.5	< 0.5	< 0.5	<0.5		15,000
	4.46 4.46	-0.71	5.17			<10	<50	< 0.5	< 0.5	<0.5	<0.5		
09/29/93	4.46	-1.47	5.93			<10	<50	< 0.5	< 0.5	<0.5	<0.5		
12/20/93	4.46 4.46	-0.81	5.27			<10	54	< 0.5	< 0.5	<0.5	0.6		
03/07/94	4.46 4.46	-0.61			<u></u> -				·			 ,	
06/17/94		-0.64	5.10			<50	<50	<0.5	< 0.5	< 0.5	< 0.5	<50	
09/12/94	4.46		5.58			800 ¹	<50	<0.5	< 0.5	< 0.5	<0.5		
11/30/94	4.46	-1.12	6.33			490 ²	<50	< 0.5	<0.5	<0.5	<0.5		
03/24/95	4.46	-1.87	8.20			300 ²	<50	< 0.5	< 0.5	<0.5	< 0.5		
06/27/95	4.46	-3.74	4.65			1,200 ²	120	1.1	<0.5	<0.5	< 0.5		
09/28/95	4.46	-0.19				820 ²	<50	<0.5	<0.5	<0.5	< 0.5	<2.5	
12/19/95	4.46	-1.58	6.04			270^{2}	<50	<0.5	<0.5	<0.5	< 0.5	<2.5	
02/28/96	4.46	-1.54	6.00			750 ²	97	<0.5	<0.5	<0.5	0.71	<2.5	
06/25/96	4.46	-1.71	6.17			540 ²	65	<0.5	<0.5	<0.5	<0.5	<2.5	
12/17/96	4.46	-1.67	6.13			780 ²	65	<0.5	<0.5	< 0.5	<0.5	<2.5	
03/31/97	4.46	-2.23	6.69				D SEMI-AN		40.5				
06/30/97	4.46	-2.62	7.08			270 ²	65 65	<0.5	<0.5	<0.5	<0.5	<2.5	
09/12/97	4.46	-0.95	5.41		·					. 40.5		 -	·
12/05/97	4.46	-1.96	6.42	•				 -0.5	<0.5	<0.5	<0.5	<2.5	
02/16/98	4.46	-0.30	4.76			330 ²	140	<0.5					
06/17/98	4.46	-1.54	6.00								<0.5	<2.5	
08/31/98	4.46	-0.64	5.10			270¹	<50	<0.5	<0.5	<0.5		<2.3 	
12/28/98	4.46	-2.04	6.50							 -0.5	-0.5		
03/04/99	4.46	-1.35	5.81			638 ¹	95.5	<0.5	<0.5	<0.5	<0.5	<2.0	

Table 1
Groundwater Monitoring Data and Analytical Results
Chevron Service Station #9-0121

Chevron Service Station #9-012 3026 Lakeshore Avenue Oakland, California

						Jakianu, Ca							
WELL ID/	TOC	GWE	DTW	SPH Thickness (ft.)	SPH Removed (gallons)	TPH-D	TPH-G	B (ppb)	T (ppb)	E (ppb)	X (ppb)	MTBE (ppb)	TDS (ppb)
DATE	(ft.)	(msl)	(ft.)	U to 2					٠				
												·	·
MW-6 (cont)		-0.97	5.43						<0.5	<0.5	<0.5	<2.5	•
06/14/99	4.46	-1.74	6.20			258¹	<50	<0.5				. 	·
09/17/99	4.46	-2.31	6.77	<u> </u>				 <0.5	<0.5	<0.5	<0.5	<2.5	,
12/20/99	4.46	-2.12	6.58			257 ²	<50		70.5			 .	 -
03/20/00	4.46	-2.52	6.98	0.00	 ;	SAMPLED	SEMI-AN	<0.50	<0.50	< 0.50	< 0.50	<2.5	
06/24/00	4.46	-0.46	4.92	0.00	**	9811	<50						
09/07/00	4.46	-0.64	5.10	0.00					<0.50	<0.50	< 0.50	<2.5	
12/05/00	4.46	-0.43	4.89	0.00		1909	<50	<0.50	<0.50	40.0		•	
03/01/01	4.46	-0.43					•	, .					
MW-7	5.06	-0.29	5.55						<0.5	<0.5	<0.5		
08/24/92	5.26	-0.39	5.65	·		<50	<50	<0.5	`				
09/21/92	5.26	-0.25	5.51						<0.5	<0.5	<0.5		
10/26/92	5.26	1.31	3.95			60	<50	2.9					
12/23/92	5.26					•			<0.5	<0.5	<0.5		
01/08/93	5.26	2.76	2.50			<10	<50	<0.5		<0.5	<0.5		2200
03/25/93	5.26	1.80	3.46			 .	<50	0.6	<0.5	1.0	7.0		
06/11/93	5.26	-0.26	5.52			<10	<50	2.0	1.0	<0.5	<0.5		
09/29/93	5.26		4.41			<10	<50	2.0	<0.5	<0.5	<0.5		
12/20/93	5.26	0.85	2.62			<10	<50	<0.5	<0.5	<0.5	<0.5		 .
03/07/94	5.26	2.64	3.27			<50	<50	<0.5	<0.5	<0.5	<0.5	<5.0	
06/17/94	5.26	1.99	4.11	, <u>.</u> .		<50	<50	<0.5	<0.5	<0.5	<0.5		. <u></u> , `
09/12/94	5.26	1.15	2.76			92 ¹	<50	<0.5	<0.5		<0.5		
11/30/94	5.26	2.50	2.70			<50	<50	<0.5	<0.5	<0.5	<0.5		
03/24/95	5.26	3.06	3.90	-		69 ²	<50	< 0.5	<0.5	<0.5	<0.5		
06/27/95	5.26	1.36				84 ²	<50	<0.5	<0.5	<0.5		<2.5	
09/28/95	5.26	0.41	4.85 3.02			84 ²	<50	<0.5	<0.5	<0.5	<0.5	<2.5	
12/19/95	5.26	2.24				99 ²	<50	<0.5	<0.5	<0.5	<0.5	<2.5	
02/28/96	5.26	3.83	1.43			110 ²	<50	<0.5	<0.5	<0.5	<0.5	<2.3	
06/25/96	5.26	0.97	4.29										As of

Table 1
Groundwater Monitoring Data and Analytical Results

Chevron Service Station #9-0121 3026 Lakeshore Avenue Oakland, California

SPIT SPIE THE COLUMN TOC GWE DTW Tickness Removed THE D THE COLUMN THE COL							Juni-, -							
WPLLID TOC GWE DIW Inicianes Removed TPH.D TPH.G B CPD GPD GP					SPH	SPH					T	v	MTRF	TDS
NW-7 (cont) NW-8 (cont)	WELL ID/	TOC	GWE	DTW	Thickness	Removed								
MW-7 (cont) 12/17/96				(ft.)	(ft.)	(gallons)	(ppb)	(ppb)	(ppb)	(ррь)	(<i>ppo)</i>	(рри)	(PPe)	paragraph of the Language
12/17/96	DATE	V·· ·	A											
12/17/96	MW 7 (cont)									-O. 6	√ 0.5	<0.5	<2.5	
03/31/97 5.26 2.32 2.94 100° 50° 50.5 50.5 50.5 50.5 50.5 50.5 50		5.26	3.08	2.18										
06/30/97 5.26 1.68 3.58 - SAMPLED ANNUALLY 09/12/97 5.26 1.85 3.41				2.94										
09/1297 5.26 1.85 3.41				3.58			SAMPLE	D ANNUAL						
12/05/97 5.26 3.37 1.89			1.85	3.41										
02/16/98 5.26 3.43 1.83 - 777			3.37	1.89									<2.5	
06/17/98 5.26 3.32 1.94				1.83			77*							
08/31/98 5.26 1.07 4.19			3.32	1.94										
12728/98 5.26 0.79 4.47 73.4 <50 <0.5 <0.5 <0.5 <0.5 <0.5 <0.0 12728/98 5.26 3.51 1.75 73.4 <50 <0.5 <0.5 <0.5 <0.5 <0.5 <0.5 <0.5			1.07	4.19										
03/04/99 5.26 3.51 1.75			0.79	4.47		, 							<2.0	
06/14/99 5.26 3.64 1.62			3.51	1.75			73.4							,
09/17/99 5.26 0.42 4.84			3.64	1.62										
12/20/99 5.26 0.45 4.81	,		0.42	4.84										·
03/20/00 5.26 3.41 1.85			0.45	4.81									<2.5	
06/24/00 5.26 3.05 2.21 0.00			3.41	1.85			<50							
09/07/00 5.26 1.61 3.65 0.00			3.05	2.21	0.00									
12/05/00 5.26 2.31 2.95 0.00 <50 <50 <0.50 <0.50 <0.50 <0.50 <2.5 0.30/01/01 5.26 4.61 0.65 0.00 <50 <50 <0.5 <0.5 <0.5 <0.5 <0.5 <			1.61	3.65	0.00									
MW-8 06/23/92 8.94 -15.20 24.14 <50 <50 <0.5 <0.5 <0.5 <0.5 <0.5 <				2.95	0.00									
MW-8 06/23/92 8.94 -15.20 24.14 <50 <50 <0.5 <0.5 <0.5 <0.5 <				0.65	0.00		<50	<50	<0.50	<0.50	<0.50	70.50	\2.	
06/23/92 8.94 -15.20 24.14	03/01/01	0.2 0												
06/23/92 8.94 -15.20 24.14														
06/23/92 8.94 -15.20 24.14	MW-8									.0.5	-0.5	-0.5		
08/24/92 8.94 0.34 8.60 <50		8.94	-15.20	24.14			<50	<50	<0.5					·
09/21/92 8.94 0.55 8.39 -50 94 20.3 20.3 20.5 20.5 20.5 10/26/92 8.94 -0.18 9.12 12/23/92 8.94 0.83 8.11 <td< td=""><td></td><td></td><td>0.34</td><td>8.60</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></td<>			0.34	8.60										
10/26/92 8.94 -0.18 9.12 79 <50 0.7 5.0 0.7 2.9 12/23/92 8.94 0.83 8.11 79 <50 0.7 5.0 0.7 2.9 12/23/92 8.94 0.83 8.11			0.55	8.39			<50	94	<0.5					
12/23/92 8.94 0.83 8.11 79 <50 0.7 3.0 0.7 2.5 01/08/93 8.94			-0.18	9.12		,	•							
01/08/93 8.94				8.11			79	<50						
03/25/93 8.94 <50 <0.5 <0.5 <0.5 <- 3500 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0.5 <- 0														
06/11/93 8.94 0.55 8.39 <50 <0.5 <0.5 <0.5 <0.5 < <														
10 <50 <0.5 <0.5 <0.3 <0.3			0.55	8.39										
	09/29/93	8.94	0.69	8.25			<10	<50	<0.5	<0.5	<0.5	<0.5		

Table 1
Groundwater Monitoring Data and Analytical Results
Chevron Service Station #9-0121

3026 Lakeshore Avenue Oakland, California

					. C	akland, Ca	lifornia						
WELL ID/ DATE	TOC (ft.)	GWE (msl)	DTW (ft.)	SPH Thickness (fi.)	SPH Removed (gallons)	TPH-D	TPH-G	B (ppb)	T (ppb)	E (ppb)	X (ppb)	MTBE (ppb)	TDS (ppb)
									0.6	<0.5	1.0		
MW-8 (cont)	0.04	0.48	8.46			<10	<50	<0.5 <0.5	<0.5	<0.5	<0.5		
12/20/93	8.94	0.48	8.66			<10	<50	<0.5	<0.5	<0.5	<0.5		
03/07/94	8.94 8.94	0.12	8.82			<50	<50	<0.5	<0.5	<0.5	0.8	<5.0	
06/17/94	8.94 8.94	0.11	8.83			<50	<50	<0.5	<0.5	<0.5	<0.5	- -	
09/12/94	8.94 8.94	0.31	8.63			1201	<50	<0.5	<0.5	<0.5	<0.5		
11/30/94	8.94 8.94	0.43	8.51			110 ²	< 5 0	<0.5	<0.5	<0.5	<0.5		
03/24/95	8.9 4 8.94	-0.03	8.97			67 ²	<50	<0.5	<0.5	<0.5	<0.5		
06/27/95	8.94 8.94	0.04	8.90			91 ²	<50	<0.5	<0.5	<0.5	<0.5	<2.5	
09/28/95		0.54	8.40			76²	< 50	<0.5	<0.5	<0.5	<0.5	<2.5	
12/19/95	8.94	0.50	8.44			<50	< 50	<0.5 <0.5	<0.5	<0.5	< 0.5	<2.5	
02/28/96	8.94 8.94	0.05	8.89	. 		80 ²	<50	<0.5 <0.5	<0.5	<0.5	<0.5	<2.5	
06/25/96		0.49	8.45			79 ²	<50		<0.5	<0.5	< 0.5	3.6	
12/17/96	8.94	0.49	8.76		·	72 ²	<50	<0.5	20.5	,			
03/31/97	8.94	-0.18	9.12			SAMPLE	ED ANNUA	LLY					
06/30/97	8.94	0.13	8.81		 '			, 					
09/12/97	8.94	0.13	8.35					0.5	<0.5	<0.5	<0.5	4.3	
12/05/97	8.94	1.00	7.94			68 ²	<50	<0.5					
02/16/98	8.94	0.51	8.43	·			· 			<u></u>			
06/17/98	8.94	0.31	8.88							, 			
08/31/98	8.94	0.64	8.30						 <0.5	<0.5	<0.5	3.83	
12/28/98	8.94		8.65			106	<50	<0.5	<0.5				
03/04/99	8.94	0.29	8.42			 .		7					
06/14/99	8.94	0.52	9.87									·	
09/17/99	8.94	-0.93	8.40	:			,				<0.5	3.46	'
12/20/99	8.94	0.54				82.2 ⁶	<50	<0.5	<0.5	<0.5			
03/20/00	8.94	0.82	8.12	0.00		SAMPI	LED ANNU	ALLY		, ,			
06/24/00	8.94	0.31	8.63	0.00				·					
09/07/00	8.94	0.26	8.68	0.00								<2.5	
12/05/00 03/01/01	8.94 8.94	0.81 1.04	8.13 7.90	_		5111	<50	<0.50	<0.50	<0.50	<0.50	٧	

Table 1
Groundwater Monitoring Data and Analytical Results
Chevron Service Station #9-0121

hevron Service Station #9-013 3026 Lakeshore Avenue Oakland, California

					C	akiano, C							
				SPH	SPH		mmr c	n	T	E	X	МТВЕ	TDS
WELL ID/	TOC	GWE	DTW	Thickness		TPH-D	TPH-G	В	(ppb)	(ppb)	(ppb)	(ppb)	(ppb)
DATE	(ft.)	(msl)	(ft.)	(ft.)	(gallons)	(ppb)	(ppb)	(ppb)	(рро)	уррол	(000 <u>0.) </u>	***************************************	
MW-9						2,600 ²	3,900 ⁶	14	6.9	14	24	140	
04/19/99	5.87	2.71	3.16			$2,800^2$	2,880	12.6	<10	<10	<10	138	
06/14/99	5.87	1.06	4.81	 .		$1,770^2$	3,370	33.1	14.4	<5.0	<5.0	202	
09/17/99	5.87	1.02	4.85			996 ²	3,970	42.2	13.5	<10	<10	311	
12/20/99	5.87	1.87	4.00			2,710 ²	5,920	22.1	<5.0	6.8	<5.0	106.0	
03/20/00	5.87	2.87	3.00			2,710 1,940 ⁹	$2,500^7$	12	<10	11	<10	120	
06/24/00	5.87	1.96	3.91	0.00		1,500 ⁹	3,700 ⁷	<25	<25	<25	<25	330	
09/07/00	5.87	1.59	4.28	0.00		1,300 ¹²	$3,700^2$	<5.00	7.64	<5.00	<5.00	177	
12/05/00	5.87	2.07	3.80	0.00	, 	960 ⁹	2,400 ⁷	11	18.0	<10	<10	250	
03/01/01	5.87	3.19	2.68	0.00		300	2,400	**	2011				
										•			
TRIP BLAN	I T /												
08/24/92	 ·												•
							<50	<0.5	<0.5	< 0.5	<0.5		
09/21/92													
10/26/92							<50	< 0.5	<0.5	<0.5	<0.5		
12/23/92								- -					
01/08/93						· ,	<50	< 0.5	<0.5	< 0.5	<0.5		
03/25/93							<50	<0.5	<0.5	<0.5	< 0.5		
06/11/93							<50	<0.5	<0.5	<0.5	< 0.5		
09/29/93							<50	< 0.5	<0.5	< 0.5	<0.5		
12/20/93							<50	<0.5	< 0.5	< 0.5	< 0.5		
03/07/94							<50	<0.5	<0.5	< 0.5	<0.5		
06/17/94	·						<50	<0.5	<0.5	<0.5	1.0		 .
09/12/94			<u> </u>				<50	<0.5	< 0.5	<0.5	< 0.5		
11/30/94							<50	<0.5	< 0.5	<0.5	<0.5		
03/24/95							<50	< 0.5	<0.5	<0.5	<0.5		
06/27/95							<50	< 0.5	< 0.5	<0.5	<0.5	'	
09/28/95							<50	<0.5	< 0.5	<0.5	< 0.5		
12/19/95						**	<50	<0.5	< 0.5	< 0.5	< 0.5		
02/28/96													

Table 1 Groundwater Monitoring Data and Analytical Results Chevron Service Station #9-0121

Chevron Service Station #9-012 3026 Lakeshore Avenue Oakland, California

						aiduiio, o							
WELL ID/	TOC (ft.)	GWE (msl)	DTW (ft.)	SPH Thickness (ft.)	SPH Removed (gallons)	TPH-D	TPH-G (ppb)	B (ppb)	T (ppb)	E <i>(ppb)</i>	X (ppb)	MTBE (ppb)	TDS (ppb)
TRIP BLANE 06/25/96 12/17/96 03/31/97 06/30/97 09/12/97 12/05/97 02/16/98 06/17/98 08/31/98 12/28/98 03/04/99 06/14/99 09/17/99 12/20/99 03/20/00 06/24/00 09/07/00							<50 <50 <50 <50 <50 <50 <50 <50 <50 <50	<0.5 <0.5 <0.5 <0.5 <0.5 <0.5 <0.5 <0.5	<0.5 <0.5 <0.5 <0.5 <0.5 <0.5 <0.5 <0.5	<0.5 <0.5 <0.5 <0.5 <0.5 <0.5 <0.5 <0.5	<0.5 <0.5 <0.5 <0.5 <0.5 <0.5 <0.5 <0.5	<pre> <2.5 <2.5 <2.5 <2.5 <2.5 <2.5 <2.5 <2.5</pre>	
12/05/00 03/01/01	 		· 		 		<50	<0.50	<0.50	<0.50	<0.50	<2.5	

Table 1

Groundwater Monitoring Data and Analytical Results

Chevron Service Station #9-0121 3026 Lakeshore Avenue Oakland, California

EXPLANATIONS:

Groundwater monitoring data and laboratory analytical results prior to June 24, 2000, were compiled from reports prepared by Blaine Tech Services, Inc.

TOC = Top of Casing

(ft.) = Feet

GWE = Groundwater Elevation

(msl) = Mean sea level

DTW = Depth to Water

SPH = Separate Phase Hydrocarbons

TPH-D = Total Petroleum Hydrocarbons as Diesel

TPH-G = Total Petroleum Hydrocarbons as Gasoline

B = Benzene

T = Toluene

E = Ethylbenzene

X = Xylenes

MTBE = Methyl tertiary butyl ether

(ppb) = Parts per billion

TDS = Total Dissolved Solids

-- = Not Measured/Not Analyzed

- Chromatogram pattern indicates a non-diesel mix.
- Chromatogram pattern indicates an unidentified hydrocarbon. 2
- Chromatogram pattern indicates an unidentified hydrocarbon and weathered diesel.
- Confirmation run.
- ORC in well.
- Laboratory report indicates gasoline and unidentified hydrocarbons >10.
- Laboratory report indicates gasoline C6-C12.
- Laboratory report indicates this sample was analyzed outside of the EPA recommended holding time.
- Laboratory report indicates unidentified hydrocarbons C9-C24.
- Laboratory report indicates unidentified hydrocarbons C10-C24. 10
- Laboratory report indicates unidentified hydrocarbons >C16. 11
- Laboratory report indicates unidentified hydrocarbons C9-C40. 12
- Laboratory report indicates diesel C9-C24+ unidentified hydrocarbons <C16. 13
- Laboratory report indicates weathered gasoline C6-C12. 14

Table 2 **Groundwater Analytical Results** Chevron Service Station #9-0121

3026 Lakeshore Avenue

WELL ID/ DATE	Total Alkalinity (ppb)	Oakland, California Ferrous Iron (ppb)	Sulfate (ppb)	Nitrate (ppb)
MW-1 12/28/98	390,000	4900	<1000	<1000
MW-3 12/28/98	980,000	4500	390,000	<1000
MW-4 12/28/98	670,000	3500	6800	<1000
MW-5 12/28/98	480,000	15	51,000	<1000
MW-6 12/28/98	2,400,000	810	110,000	<1000
MW-7 12/28/98	350,000	12,000	79,000	<1000
MW-8 12/28/98	1,100,000	45	87,000	<1000

EXPLANATIONS:

Groundwater laboratory analytical results were compiled from reports prepared by Blaine Tech Services, Inc.

(ppb) = Parts per billion

Table 3

Dissolved Oxygen Concentrations

Chevron Service Station #9-0121 3026 Lakeshore Avenue Oakland, California

WELL ID	DATE	Before Purging (mg/L)	After Purging (mg/L)
MW-1	06/24/00	5.3	
	09/07/00	4.02	
	12/05/00	3.86	
	03/01/01	3.04	

EXPLANATIONS:


(mg/L) = Milligrams per liter

-- = Not Measured

APPENDIX C

Virgil Chavez Land Surveying

312 Georgia Street, Suite 200 Vallejo, California 94590-5907 (707) 553-2476 • Fax (707) 553-8698



April 28, 1999 Project No. 1704-06

Barbara Sieminski Gettler-Ryan, Inc. 6747 Sierra Ct., Suite J Dublin, Ca. 94568

Subject: Monitoring Well Survey Chevron SS # 9-0121 3026 Lakeshore Ave. Oakland, Ca.

Dear Barbara:

This is to confirm that we have proceeded at your request to survey the monitoring wells at the above referenced location. Our findings for the are shown in the tables below. The survey was performed on April 12, 1999. Measurements were taken at notches on the top of casing. The benchmark for the survey was a City benchmark, being a cut square in the top of curb, at the northeasterly corner of Walker & Cheney Ave. The second table is for top of casing locations, using the back of sidewalk on Lakeshore as reference line, beginning near the westerly property corner and looking northeasterly. Benchmark Elev. = 9.055 feet, City Datum.


Well No. Ri	m Elevation	TOC Elevation
MW - 2A	6.83′	6.53 <i>'</i>
MW - 3A	9.01′	8.70′
MW - 4A	7.92′	7.69 <i>′</i>
MW - 9	6.21'	5.87′
Well No.	Station	<u>Offset</u>
MW - 2A	0+41.87	11.76(Rt.)
MW - 3A	1+30.15	77.06(Rt.)
MW - 4A	1+30.22	47.78(Rt.)
MW - 9	0+06.82	5.62(Rt.)
BSW W'ly Prop Cor.	0+00.00	0.00
BSW Beg. Curve Lakeshore	0+54.20	0.00

No. 6323
Exp. 12-31-02. AT


Sincerely,


Virgil D. Chavez, PLS 6323






FILE NAME: P:\Enviro\Chevron\9-0121\Q01-9-0121.DWG | Layout Tab: Pot2






FILE NAME: P:\ENVIRO\CHEVRON\9-0121\Q00-9-0121.DWG | Layout Tab: Pot4









REVIEWED BY

6747 Sierra Ct., Suite J Dublin, CA 94568

(925) 551-7555

3026 Lakeshore Avenue Oakland, California


DATE

June 24, 2000

REVISED DATE

JOB NUMBER 386462

FILE NAME: P:\ENVIRO\CHEVRON\8-0121\Q00-9-0121.DWG | Layout Tab: POT2






Chevron Station 9-0121 3026 Lakeshore Avenue Oakland, California

GROUNDWATER ELEVATION CONTOUR MAP, MARCH 20, 2000

FIGURE:



JOB NUMBER 346462

REVIEWED BY


6747 Sierra Ct., Suite J Dublin, CA 94568

(925) 551-7555

3026 Lakeshore Avenue

Oakland, California


DATE April 19, 1999 REVISED DATE



3026 Lakeshore Avenue Oakland, California


GROUNDWATER ELEVATION CONTOUR MAP, MARCH 4, 1999

1




3026 Lakeshore Avenue Oakland, California

GROUNDWATER ELEVATION CONTOUR MAP, FEBRUARY 16, 1998



3026 Lakeshore Avenue Oakland, California

GROUNDWATER ELEVATION CONTOUR MAP, JUNE 17, 1998




3026 Lakeshore Avenue Oakland, California

GROUNDWATER ELEVATION CONTOUR MAP, **DECEMBER 28, 1998**

1 PROJECT:

DAC04



RIRING engineering contracting firm


Chevron Station 9-0121 3026 Lakeshore Avenue Oakland, California


GROUNDWATER ELEVATION CONTOUR MAP, AUGUST 31, 1998

FIGURE:

1

PROJECT:
DAC04






RRIVER ENGINEERING CONTRACTING FIRM

Chevron Station 9-0121 3026 Lakeshore Avenue Oakland, California


GROUNDWATER ELEVATION CONTOUR MAP, JUNE 30, 1997 FIGURE:



3026 Lakeshore Avenue Oakland, California


GROUNDWATER ELEVATION CONTOUR MAP, SEPTEMBER 12, 1997


1




3026 Lakeshore Avenue Oakland, California

GROUNDWATER ELEVATION CONTOUR MAP, DECEMBER 5, 1997








TITLE : GROUND-WATER ELEVATION CONTOUR MAP - DECEMBER 17, 1996

LOCATION: CHEVRON SERVICE STATION 9-0121 3026 LAKESHORE AVENUE, OAKLAND, CALIFORNIA

GEOCONSULTANTS, INC SAN JOSE, CALIFORNIA Project No. G758-09

.....



CAMBRIA
Environmental Technology, Inc.


Chevron Station 9-0121 3026 Lakeshore Avenue Oakland, California


\CHEVRON\9-0121\0121-QM(1Q95).DWG

Ground Water Elevation

March 24, 1995

1







CAMBRIA
Environmental Technology, Inc.


Chevron Station 9-0121 3026 Lakeshore Avenue Oakland, California


\CHEVRON\9-0121\0121-QM.DWG


Ground Water Elevation


December 19, 1995

1











Environmental Technology, Inc.


3026 Lakeshore Avenue Oakland, California


November 30, 1994


\CHEVRON\9-0121\0121-QM(4Q94).DWG













•











FIGURE 3
GROUNDWATER ELEVATION MAP
(8/20/91)

CHEVRON U.S.A. INC. SERVICE STATION #9-0121 3026 LAKESHORE AVENUE OAKLAND, CALIFORNIA 0 FEET 30 SCALE

DRAWN BY: ML 9/13/91







APPENDIX E



Location <u>Oakland, California</u> Surface Elev To Top of Casing <u>6.89 ft.</u> Wa Screen: Dia <u>4 in.</u> Le Casing: Dia <u>4 in.</u> Le	Pr tal Hole Del ter Level Ir ngth 15 ft. ngth 4 ft. ustre 2/12	Method License	ft. Rig/C Hollo Log E No. F	Type SCH 40 PVC Type Mobile B-53/split spoon w stem auger Permit # 92281 By Greg Mischel	
-2- -0- -10- -12- -16- -18- -20- -24-	У В Ж Д	Still		Concrete CRUSHED ROCK about one-inch dia Static groundwater level at 5.41 fee Encountered groundwater at 6 fee Encountered groundwater at 6 fee End of boring at 21.5 feet. Sloug groundwater monitoring well	emeter (fill) et. t on 06/19/92 (1700 hours). n stiff, saturated) th up to 19 feet. Constructed

Gettler-Ryan, Inc	>.	Log of Boring MW-2A	
PROJECT: Chevron SS #9-0121		LOCATION: 3026 Lakeshore Avenue, Oakland, CA.	
GR PROJECT NO.: 346462.01		SURFACE ELEVATION: 6.53ft. MSL	
DATE STARTED: 04/01/99		WL (ft. bgs): 5.0 DATE: 04/01/99 TIME: 15:05	
DATE FINISHED: 04/01/99		WL (ft. bgs): 5.0 DATE: 04/02/99 TIME: 11:20	
DRILLING METHOD: 8 in. Hollow Stem	Auger	TOTAL DEPTH: 18.0 Feet	
DRILLING COMPANY: Bay Area Explo	ration Inc.	GEOLOGIST: Barbara Sieminski	
/FT. * //FT. * E NUMBER LE 1NT.	GI CLASS		Dentonite
			90
152 5 MW2A-3	medium plasticii coarse sand, ti	ark greenish gray (5GY 4/1), moist,	_
5— 149 6 MW2A-8	- Becomes satur	(0.02 inch)	- -
10- 13.6 2 MW2A-11	10 feet bgs.	95-100% clay, 0-5% organic matter at	-
15— 2 3 MW2A-17 MW2A-17.5	SILTY SAND saturated, ve silt.	(SM) - very dark gray (5Y 3/1), ry loose; 70% fine to coarse sand, 30%	
	Bottom of bo	oring at 18.0 feet.	
25-	Į.	ted to equivalent standard penetration	
35- JOB NUMBER: 346462.01		P	age 1

JOB NUMBER: 346462.01

Gettler-Ryan, Inc.	Log of Boring MW-3A
ROJECT: Chevron SS #9-0121	LOCATION: 3026 Lakeshore Avenue, Oakland, CA.
GR PROJECT NO.: 346462.01	SURFACE ELEVATION: 8.70ft. MSL
DATE STARTED: 04/01/99	WL (ft. bgs): 8.0 DATE: 04/01/99 TIME: 12:20
DATE FINISHED: 04/01/99	WL (ft. bgs): 8.0 DATE: 04/02/99 TIME: 11:00
DRILLING METHOD: 8 in. Hollow Stem Auger	TOTAL DEPTH: 18.0 Feet
DRILLING COMPANY: Bay Area Exploration Inc.	GEOLOGIST: Barbara Sieminski
EPTH Set LOWS/FT.* SAMPLE NUMBER SRAPHIC LOG SOIL CLASS	GEOLOGIC DESCRIPTION GEOLOGIC DESCRIPTION - Concrete over baserock WELL DIAGRAM WELL DIAGRAM OF THE STATE OF THE STAT
plasticity, m	- gray (10YR 5/1), moist, medium nedium stiff; 100% clay, trace fine sand.
10— 45 7 MW3A-11 CL-ML SILTY CLA (5Y 5/3), clay, 40%	nottling (5Y 5/3); 95% clay, 5% fine sand, gravel at 5 feet bgs. IY (CL-ML) - gray (5Y 5/1) mottled clive saturated, low plasticity, medium stiff; 55% silt, 5% fine to coarse sand. Description of the brown (2.5Y 5/6) mottled y 5/0), saturated, low plasticity, stiff; 70% clay.
9 (2.5 silt, 30% c) - light olive brown (2.5Y 5/8) mottled Y 5/0), saturated, low plasticity, stiff; 70% clay. L) - pale olive (5Y 8/3) mottled white (5Y t to damp, low to medium plasticity, very c clay, 30% silt.
Bottom o (* = con	of boring at 18.0 feet. Averted to equivalent standard penetration A NA = not applicable, sample collected and augering.)
30-	
35-	Page 1

	G	ett	ler-R	ya	n, Ir	nc.		Log of Boring MW-4A
PROJE	CT:	Chevi	ron SS #8	9-0	121			LOCATION: 3026 Lakeshore Avenue, Oakland, CA.
			: 34646					SURFACE ELEVATION: 7.69ft. MSL
			04/01/5					WL (ft. bgs): 4.5 DATE: 04/01/99 TIME: 13:55
			04/02/					WL (ft. bgs): 4.5 DATE: 04/02/99 TIME: 9:00
			D: 8 in.		low St	em Au	ger	TOTAL DEPTH: 18.5 Feet
ORIL	LING C	OMPA	NY: Ba)	/ Ar	еа Ехр	olorati	on Inc.	GEOLOGIST: Barbara Sieminski
DEPTH feet	(mdd) OId	BLOWS/FT. ¥	SAMPLE NUMBER	SAMPLE INT.	GRAPHIC LOG	SOIL CLASS	GE	OLOGIC DESCRIPTION OLOGIC DESCRIPTION Ocrete over pea gravel and Ocrete over pea gravel and
1 1 1	0	NA .	MW4A-3	-		CL	Daserock. CLAY (CL) - da gray (5GY 5/1), ₹ 70% clay, 20% s	rk gray (10YR 4/1) mottled greenish
5-	65	6	MW4A-6			ML		ted at 4.5 feet bgs.
10-	1.6	1	MW4A-11		*	CL-ML	saturated, low prine sand, 10% c	plasticity, very soft: 60% silt, 30% lay.
15-	3.0	4	MW4A-15	5		CL	silt.	plasticity, medium stiff; 80% clay, 40%
	3.0	6	MW4A-17	.5			brown (10YR 4 medium stiff; 80	ive (5Y 5/3) mottled dark yellowish /6), moist, low to medium plasticity, 0% clay, 20% silt.
20-							(* = converte	ng at 18.5 feet. d to equivalent standard penetration not applicable, sample collected gering.)
25-	+ + + + + + + + + + + + + + + + + + + +				1			
30								
35	;- 				_			Page 1 (

JOB NUMBER: 346462.01



Project <u>CH</u>	//3026 L	akeshore	Ave.		. Own	er CHEVRON U.S.A. Products Company	See Site Map For Boring Location
Landina Oi	akland Ca	alifornia		Project	No. C	02020 2781 Date drilled 00712732	COMMENTS
Surface Ele	v. <u>14.56</u>	ft. Tota	al Hole (Depth 그 I Initial	23 ft.	Diameter <u>8 inches ft.</u> Static <u>12.24 ft.</u>	COMMENTS:
Corpon: Dia	2 in.	1 en	ath 20	<i>II</i> .		Type/Size <u>0.020 iii.</u>	1
Carior Dia	2 in	1 en	oth 15 1	ft.		Type <u>SCH 40 FVC</u>	
Filter Back	Material	Lapis Lus	itre 2/12	?	_ Ria	/Core Type Mobile 8-53/split spoot	
Drilling Com	pany <u>Kvii</u> Crocker	haug Well	Drilling	Metho	od <u>au</u>	By Steve Kranyak	
Checked B	y <u>Dave k</u>	(leesatte		Licen	se No	RG# 5136 Oni Klantles	
	~ II	1	555	ıl i	355.	Descript	ion
Depth (ft.)	e e	PID (mdd)	Cou	Graphic Log	ū	(Color, Texture,	
- G	Well	ه ق	Sample Blow Co	Gre	SCS	Trace < 10%, Little 10% to 20%, Some	20% to 35%, And 35% to 50%
1	O	11	03 @ 34	1			
├ -2 -							
+ 1	Ì						
上 0 十	4-714	ļ	l I	0.00		ASPHALT Coarse base aggregate	
1				7//		-Coarse pase aggregate	
- 2 -	<	ļ			1	Brown silty CLAY with trace sand ar	nd gravel (stiff, moist)
+ -1	<u>{</u>						
- 4 -	[]				1 1		
1	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \		7		1		
- 6 -	רק קי -		A 7				
	\ \ \ \ \		ll .				
- 8 -	7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7						
	14 14						
	Py Py			///		Dark brown silty CLAY with trace s	and and gravel (stiff, moist)
- 10	Ed Fo	1	∥в	7			
·			1	° 0//	CL		
- 12 -						Y Static groundwater level at 12.24 f	eet.
- t			II.				
- 14 -	#	:∦	1				
·		: <u> </u>		10 12		Light brown silty CLAY (stiff, mois	t)
- 16 -	∦: <u> </u> ;	:∥	С	15			
- -	∦ <u> ≣</u> :						
- 18 -	∦. <u> </u>						
		.:					
- 20 -	. : <u> </u> : : :			7 [Light brown silty CLAY (stiff, very	/ moist)
			۵	9 12			
- 22 -				"4//	4	Brown fine SAND	
L 22.		:	1		∷∦ .	Encountered groundwater at 23 to	feet on 06/12/92.
Ţ	1				<u>∷: </u>		
- 24		- .			1/0		



<u></u>	.011102				autoria de la Campaga
Project <u>CHV/30</u> Location <u>Oaklan</u>	26 Lakesho d, California	re Ave.	Project	_ 0w No.	ner <u>CHEVRON U.S.A. Products Company</u> 02020 2781 Date drilled <u>06/12/92</u>
Depth (ft.) Well Completion	PIO (mdd)	Sample ID Blow Count/ X Recovery	Graphic Log	USCS Class.	Description (Color, Texture, Structure) Trace < 10%, Little 10% to 20%, Some 20% to 35%, And 35% to 50%
-24		E 12 12 12 12 12 12 12 12 12 12 12 12 12		CL	Brown and gray mottled SILT (stiff, moist) Blueish gray silty CLAY (stiff, moist) End of boring at 35 feet. Installed groundwater monitoring well.



ocation <u>Oakland, California</u> Surface Elev. <u>5.32 ft.</u> To Top of Casing <u>4.46 ft.</u> Wa Screen: Dia <u>2 in.</u> Le Casing: Dia <u>2 in.</u> Le Filter Pack Material <u>Lapis Le</u> Drilling Company <u>Kvilhaug Wa</u>	Project tal Hole Depth 2 ter Level Initial ngth 15 ft. ngth 4 ft. stre 2/12 ell Drilling Meth	No. <u>02</u> 0.0 ft. 7 ft. Rig/(Static
Driller <u>Mike Crocker</u> Checked By <u>Dave Kleesatt</u>	e/ Licer	Log ise No.:	RG# 5136 D-1 Klaratus
Depth (1t.) Well Completion PID (ppm)	Sample ID Blow Count/ x Recovery Graphic Log	USCS Class.	Description (Color, Texture, Structure) Frace < 10%, Little 10% to 20%, Some 20% to 35%, And 35% to 50%
2- - 0 - 12 - 14 - 16 - 18 - 20 - 24 - 24 - 24 - 24 - 24 - 24 - 24	A 3 4 C 2 3 C 4 7 9	-	Tan brown clayey SILT with some very fine sand



Location Oakland, California Surface Elev. 5.62 ft. Top of Casing 5.26 ft. Vice Screen: Dia 2 in. Lapis Casing: Dia 2 in. Lapis Drilling Company Kvilhaug In Checked By Dave Kleesa	tel Projected Acter Level Inition of the Project Tevel Inition of the Initio	ect No	Type/Size 0.020 in. Type SCH 40 PVC Ig/Core Type Mobile B-53/split spoon Hollow stem auger Permit # 92281 log By Steve Kranyak No. RG# 5136
Depth (ft.) Well Completion PID (ppm)	Sample ID Blow Count/ x Recovery Graphic	Log S Cie	Description (Color, Texture, Structure) Trace < 10%, Little 10% to 20%, Some 20% to 35%, And 35% to 50%
- 2 - 4 - 10 - 12 - 14 - 16 - 18 - 20 - 22 - 24 - 24 - 24 - 24 - 24 - 24	A B C D	ML CI	Dark gray silty CLAY with sand (soft, wet) Dark gray silty CLAY with sand (soft, wet)



Project <u>Cr</u>	HV/3026 L	akeshore	Ave.		_ Ow	ner CHEVRON U.S.A. Products Company	See Site Map For Boring Location
Location	Oakland, Ca	alifornia	F	rolect	No.	02020 2/81 Date drilled 00/19/92	COMMENTS
Surface E	lev. <u>9.23 f</u>	<u>r. </u>	al Hole D	epth <u>-</u> Initial	<u>0.0 1</u> 10 ft	ft. Diameter 8 inches ft. Static 24.14 ft.	COMMENTS:
Top of Ca	ising <u>0.94 </u>	ic. Wat	er Level.	iniciai . t.		State	
Caring Di	∍ 2 in.	Len	oth $5 ft$.			Type SCH 40 PVC	
Cillar Pac	v Material	Lapis Lus	stre 2/12		_ Ri	a/Core Type Mobile 8-33/3Dill Spoot	
Drilling Co	mpany <u>Kvil</u>	haug Wel	I Drillina	Meth	od 💆	follow stem auger Permit # 92201	
Driller <u>Mik</u>	e Crocker		,		_ L(og By Grea Mischel BG# 5136 Direct Klasatta	
Checked		ieesatte		Licer		10. RG# 5136 D-1 Fresauce	
جے ا	Well	- F	very	일	Class.	Descript	ion
Depth (ft.)	Well	PID (ppm)	de 200	Graphic Log		(Color, Texture,	Structure)
	E O)	Sample Blow Cou X Recove	Ğ	USCS	Trace < 10%, Little 10% to 20%, Some	20% to 35%, And 35% to 50%
	 						
-2-	1.						
†							
-0-	THE THE			V. > V	1	- CONCRETE .	
-	[4]			177	} 	Gray CLAY with little silt (soft, moist	()
- 2 -	[<]				1		
		l			1		
L4-							
					1		
		6	A 4				
-6-	1:1=1:1		6	9///	1		
-	1 ≡ ∶		1				
- 8 -	- = :						
}	∦: ≣ :						
- 10 -	JI I≣I	254	3			Encountered groundwater at 10 fee	et on 06/19/92 (1300 hours).
		234	B 4 5			Gray CLAY with little silt and trace	sand and gravel (soft, moist)
[₁₀			,	4//			
- 12	∄ ≣		N.			ri	
t	1 =						
- 14	네 []	.∦					
- }		. 0	5			Brown and gray CLAY with some si (medium stiff)	It and little sand and gravel
- 16	_ <u> </u>	:∦	C 7			(medialit stirr)	
		:∥		4//			
10		:	1				×
- 18							
t						3 3 3 AV (370	
- 20	113	: o		7 🗖		Brown silty CLAY (stiff)	
-	1 1	:	110	3 🛮			
- 22	413	·.					
ļ	#: =	.:∥					
24					4		

GROUNDWATER TECHNOLOGY

52

54

Monitoring Well MW-8

Owner CHEVRON U.S.A. Products Company Project CHV/3026 Lakeshore Ave. Project No. 02020 2781 Date drilled 06/19/92 Location Oakland, California Graphic Log Sample ID Blow Count/ X Recovery Description P10 (mdd) (Color, Texture, Structure) JSCS Trace < 10%, Little 10% to 20%, Some 20% to 35%, And 35% to 50% 24 Static groundwater at 24.14 feet. Gray silty CLAY (stiff, moist) Ε 26 - 28 30 End of boring at 30 feet. Backfilled with bentonite up to 25 feet. Installed groundwater monitoring well at 25 feet. 32 34 - 36 - 38 40. - 42 44 46 48 50

Gettler-Ryan, Inc.	Log of Boring MW-9		
PROJECT: Chevron SS #9-0121	LOCATION: 3026 Lakeshore Avenue, Oakland, CA.		
GR PROJECT NO.: 346462.01	SURFACE ELEVATION: 5.87ft. MSL		
DATE STARTED: 04/01/99	WL (ft. bgs): 4.0 DATE: 04/01/99 TIME: 13:20		
DATE FINISHED: 04/02/99	WL (ft. bgs): 4.0 DATE: 04/02/99 TIME: 10:15		
DRILLING METHOD: 8 in. Hollow Stem Auger	TOTAL DEPTH: 18.0 Feet		
DRILLING COMPANY: Bay Area Exploration Inc.	GEOLOGIST: Barbara Sieminski		
(ppm) MS/FT. * PLE NUMBER PLE INT. PHIC LOG	MELL DIAGRAM MELL DIAGRAM And the demont and the sear comment and the sear committee and the search		
PAVEMENT - C CL CLAY (CL) - volark greenish of plasticity, medi The second of the se	oncrete over pea gravel. ery dark brown (2.5Y 3/2) mottled gray (5GY 4/1), moist, medium um stiff; 100% clay, trace fine sand. ated and soft at 4.0 feet bgs.		
5— 109 2 MW9-8	gray (5GY 471), moist, medium um stiff; 100% clay, trace fine sand. ated and soft at 4.0 feet bgs.		
10— 4.0 2 MW9-11 95-100% clay,	0-5% oganic matter at 10.0 feet bgs.		
15 10 3 MW9-15 ML SANDY SILT low plasticity, clay.	(ML) - dark gray (5Y 4/1), saturated, soft; 50% silt, 40% fine sand, 10%		
2.0 4 MN9-17.5 4/1), saturate	with GRAVEL (SM) - dark gray (5Y d, loose; 50% fine to medium sand, 20% e gravel, 20% silt, 10% clay.		
20 \ medium plasti	greenish gray (5GY 5/1), saturated, city, soft; 100% clay.		
(* = convert	ring at 18.0 feet. ed to equivalent standard penetration = not applicable, sample collected augering).		
25—			
30-			
JOB NUMBER: 346462.01	Page 1 c		