

EXXON COMPANY, U.S.A.
A DIVISION OF EXXON CORPORATION

DATE ISSUED: 10/08/87
SUPERSEDES DATE: 09/18/87

MATERIAL SAFETY DATA SHEET

EXXON COMPANY, U.S.A. P.O. BOX 2180 HOUSTON, TX 77252-2180

A. IDENTIFICATION AND EMERGENCY INFORMATION

PRODUCT NAME
JOBBER UNLEADED GASOLINE 87

PRODUCT CODE
045140 - 00289

CHEMICAL NAME
Motor Gasoline

CAS NUMBER
Complex Mixture
CAS Number not applicable

PRODUCT APPEARANCE AND ODOR
Clear colored liquid (typically yellow)
Gasoline hydrocarbon odor

EMERGENCY TELEPHONE NUMBER
(713) 656-3424

B. COMPONENTS AND HAZARD INFORMATION

COMPONENTS

**CAS NO. OF APPROXIMATE
COMPONENTS CONCENTRATION**

Product is a variable complex mixture of components, principally hydrocarbons, blended to performance, rather than chemical, specifications.

See Section E for Health and Hazard Information.

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM (HMIS)

Health Flammability Reactivity BASIS
1 4 0 Recommended by Exxon

EXPOSURE LIMIT FOR TOTAL PRODUCT BASIS

100 ppm (300 mg/m³) for an 8-hour workday
Recommended by Exxon. The American Conference of Governmental Industrial Hygienists (ACGIH) lists Threshold Limit Value (TLV) of 300 ppm (900 mg/m³) for an 8-hour workday; 500 ppm STEL

C. PRIMARY ROUTES OF ENTRY AND EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT

If splashed into the eyes, flush with clear water for 15 minutes or until irritation subsides. If irritation persists, call a physician.

SKIN

In case of skin contact, remove any contaminated clothing and wash skin thoroughly with soap and water

INHALATION

If overcome by vapor, remove from exposure and call a physician immediately. If breathing is irregular or has stopped, start resuscitation, administer oxygen, if available.

INGESTION

If ingested, DO NOT induce vomiting; call a physician immediately

E. HEALTH AND HAZARD INFORMATION

VARIABILITY AMONG INDIVIDUALS

Health studies have shown that many petroleum hydrocarbons and synthetic lubricants pose potential human health risks which may vary from person to person. As a precaution, exposure to liquids, vapors, mists or fumes should be minimized.

EFFECTS OF OVEREXPOSURE (Signs and symptoms of exposure)

High vapor concentrations (greater than approximately 1000 ppm) are irritating to the eyes and the respiratory tract, may cause headaches and dizziness, are anesthetic, may cause unconsciousness, and may have other central nervous system effects including death.

Prolonged or repeated liquid contact with the skin will dry and defat the skin, leading to possible irritation and dermatitis.

NATURE OF HAZARD AND TOXICITY INFORMATION

Prolonged or repeated skin contact with this product tends to remove skin oils possibly leading to irritation and dermatitis; however, based on human experience and available toxicological data, this product is judged to be neither a "corrosive" nor an "irritant" by OSHA criteria.

Product contacting the eyes may cause eye irritation.

This product may contain up to a maximum of 4.9 weight percent benzene, CAS No. 71-43-2, as a natural constituent of various gasoline blend components. Benzene can cause anemia and other blood diseases, including leukemia (cancer of the blood-forming system), after prolonged or repeated exposures at high concentrations (e.g., 50-500 ppm). It has also caused fetal defects in tests on laboratory animals. Exxon's recommended OEL for benzene is 5 ppm for an 8-hour period, or 250 ppm-minutes over a 5- to 30-minutes period.

Contains light hydrocarbon components. Lifetime studies by the American Petroleum Institute have shown that kidney damage and kidney cancer can occur in male rats after prolonged inhalation exposures at elevated concentrations of total gasoline. Kidneys of mice and female rats were unaffected. The implication of these data for humans has not been determined, particularly since most human exposures are to light components, not to total gasoline. Certain components, such as normal hexane, may also affect the nervous system at high concentrations (e.g., 1000-1500 ppm). Typically, n-hexane represents 1 to 3% of gasoline. May contain a combined concentration of toluene, CAS No. 108-88-3, and xylene, CAS No. 1330-20-7, ranging from approximately 5 to 50%.

Product has a low order of acute oral and dermal toxicity, but minute amounts aspirated into the lungs during ingestion or vomiting may cause mild to severe pulmonary injury and possibly death.

This product is judged to have an acute oral LD50 (rat) greater than 5 g/kg of body weight, and an acute dermal LD50 (rabbit) greater than 3.16 g/kg of body weight.

PRE-EXISTING MEDICAL CONDITIONS WHICH MAY BE AGGRAVATED BY EXPOSURE

Benzene - Individuals with liver disease may be more susceptible to toxic effects.

Hexane - Individuals with neurological disease should avoid exposure.

Petroleum Solvents/Petroleum Hydrocarbons - Skin contact may aggravate an existing dermatitis.

F. PHYSICAL DATA

The following data are approximate or typical values and should not be used for precise design purposes

BOILING RANGE

Approximately 21°C (70°F) IBP
to 227°C (440°F) FBP

VAPOR PRESSURE

Varies seasonally from approximately
5 to 15 psi Reid Vapor Pressure

SPECIFIC GRAVITY (15.6 C/15.6 C)

Approximately 0.74

VAPOR DENSITY (AIR = 1)

Approximately 5

OTHER PROTECTIVE EQUIPMENT

Use chemical-resistant apron or other impervious clothing, if needed, to avoid contaminating regular clothing which could result in prolonged or repeated skin contact.

WORK PRACTICES / ENGINEERING CONTROLS

Keep containers and storage containers closed when not in use. Do not store near heat, sparks, flame or strong oxidants. Adequate ventilation required sufficient to prevent exceeding recommended exposure limit or buildup of explosive concentrations of vapor in air. Tanks that have been in leaded gasoline service may have lead-containing residue. Special precautions needed in cleaning. See American Petroleum Institute publications 2013, 2015 and 2015A. Use explosion-proof equipment. No smoking or open lights.

To minimize fire or explosion risk from static charge accumulation and discharge, effectively ground product transfer system in accordance with the National Fire Protection Association standard for petroleum products.

For use as a motor fuel only. Do not use as a cleaning solvent, or thinner, or for other non-motor fuel uses. Do not siphon by mouth. Minute amounts of liquid gasoline aspirated into the lungs may cause potentially fatal chemical pneumonitis.

PERSONAL HYGIENE

Minimize breathing vapor or mist. Avoid prolonged or repeated contact with skin. Remove contaminated clothing; launder or dry-clean before reuse. Remove contaminated shoes and thoroughly clean and dry before reuse. Cleanse skin thoroughly after contact, before breaks and meals, and at end of work period. Product is readily removed from skin by waterless hand cleaners followed by washing thoroughly with soap and water.

J. TRANSPORTATION INFORMATION

TRANSPORTATION INCIDENT INFORMATION

For further information relative to spills resulting from transportation incidents, refer to latest Department of Transportation Emergency Response Guidebook for Hazardous Materials Incidents, DOT P 5800.3.

DOT IDENTIFICATION NUMBER

UN 1203

The information and recommendations contained herein are, to the best of Exxon's knowledge and belief, accurate and reliable as of the date issued. Exxon does not warrant or guarantee their accuracy or reliability, and Exxon shall not be liable for any loss or damage arising out of the use thereof.

The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use.

The Environmental Information included under Section H hereof as well as the Hazardous Materials Identification System (HMIS) and National Fire Protection Association (NFPA) ratings have been included by Exxon Company, U.S.A. in order to provide additional health and hazard classification information. The ratings recommended are based upon the criteria supplied by the developers of these rating systems, together with Exxon's interpretation of the available data.

FOR ADDITIONAL INFORMATION ON HEALTH EFFECTS CONTACT:

DIRECTOR OF INDUSTRIAL HYGIENE
EXXON COMPANY, U.S.A.
P O BOX 2180 ROOM 3157
HOUSTON, TX 77252-2180
(713) 656-2443

FOR OTHER PRODUCT INFORMATION CONTACT:

MANAGER, MARKETING TECHNICAL SERVICES
EXXON COMPANY, U.S.A.
P O BOX 2180 ROOM 2355
HOUSTON, TX 77252-2180
(713) 656-5949

EXXON COMPANY, U.S.A.
 A DIVISION OF EXXON CORPORATION

DATE ISSUED 4/10/86

MATERIAL SAFETY DATA SHEET

EXXON COMPANY, U.S.A. P.O. BOX 2180 HOUSTON, TX 77252-2180

A. IDENTIFICATION AND EMERGENCY INFORMATION

PRODUCT NAME
DIESEL 2

PRODUCT CODE
072720 - 00787

CHEMICAL NAME
Petroleum Distillate Fuel

CAS NUMBER
68476-34-6

PRODUCT APPEARANCE AND ODOR
Clear liquid, yellow color
Faint petroleum hydrocarbon odor

EMERGENCY TELEPHONE NUMBER
(713) 656-3424

B. COMPONENTS AND HAZARD INFORMATION

COMPONENTS	CAS NO. OF COMPONENTS	APPROXIMATE CONCENTRATION
Diesel Fuel No. 2	68476-34-6	100%

See Section E for Health and Hazard Information

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM (HMIS)
 Health Flammability Reactivity BASIS
 1 2 0 Recommended by Exxon

EXPOSURE LIMIT FOR TOTAL PRODUCT BASIS
 100 ppm (900 mg/m³) for an 8-hour workday
 Recommended by Exxon

C. EMERGENCY AND FIRST AID PROCEDURES**EYE CONTACT**

If splashed into the eyes, flush with clear water for 15 minutes or until irritation subsides. If irritation persists, call a physician.

SKIN CONTACT

In case of skin contact, remove any contaminated clothing and wash skin thoroughly with soap and water.

INHALATION

Vapor pressure is very low. Vapor inhalation under ambient conditions is normally not a problem. If overcome by vapor from hot product, remove from exposure and call a physician immediately. If breathing is irregular or has stopped, start resuscitation, administer oxygen, if available.

INGESTION

If ingested, DO NOT induce vomiting, call a physician immediately.

D. FIRE AND EXPLOSION HAZARD INFORMATION

FLASH POINT (MINIMUM)

60°C (140°F)

ASTM D 93, Pensky Martens Closed Cup

AUTOIGNITION TEMPERATURE

Greater than 204°C (400°F)

NOTE: Non-marine product may be 52°C (125°F) minimum flash to meet No. 2 Diesel Fuel Oil (ASTM D 975). Seasonal blends may be as low as 38°C (100°F).

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) - HAZARD IDENTIFICATION

Health Flammability Reactivity

0

2

0

BASIS

Recommended by the National Fire Protection Association

HANDLING PRECAUTIONS

Keep product away from heat, sparks, pilot lights, static electricity, and open flame.

FLAMMABLE OR EXPLOSIVE LIMITS (APPROXIMATE PERCENT BY VOLUME IN AIR)

Estimated values: Lower Flammable Limit 0.9% Upper Flammable Limit 7%

EXTINGUISHING MEDIA AND FIRE FIGHTING PROCEDURES

Foam, water spray (fog), dry chemical, carbon dioxide and vaporizing liquid type extinguishing agents may all be suitable for extinguishing fires involving this type of product, depending on size or potential size of fire and circumstances related to the situation. Plan fire protection and response strategy through consultation with local fire protection authorities or appropriate specialists.

The following procedures for this type of product are based on the recommendations in the National Fire Protection Association's "Fire Protection Guide on Hazardous Materials", Eighth Edition (1984):

Use dry chemical, foam or carbon dioxide. Water may be ineffective, but water should be used to keep fire-exposed containers cool. If a leak or spill has ignited, use water spray to disperse the vapors and to protect men attempting to stop a leak. Water spray may be used to flush spills away from exposures. Minimize breathing gases, vapor, fumes or decomposition products. Use supplied-air breathing equipment for enclosed or confined spaces or as otherwise needed.

NOTE: The inclusion of the phrase "water may be ineffective" is to indicate that although water can be used to cool and protect exposed material, water may not extinguish the fire unless used under favorable conditions by experienced fire fighters trained in fighting all types of flammable liquid fires.

DECOMPOSITION PRODUCTS UNDER FIRE CONDITIONS

Fumes, smoke, carbon monoxide, aldehydes and other decomposition products, in the case of incomplete combustion.

"EMPTY" CONTAINER WARNING

"Empty" containers retain residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Do not attempt to clean since residue is difficult to remove. "Empty" drums should be completely drained, properly bunged and promptly returned to a drum reconditioner. All other containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations. For work on tanks refer to Occupational Safety and Health Administration regulations, ANSI Z49.1, and other governmental and industrial references pertaining to cleaning, repairing, welding, or other contemplated operations.

E. HEALTH AND HAZARD INFORMATION

VARIABILITY AMONG INDIVIDUALS

Health studies have shown that many petroleum hydrocarbons and synthetic lubricants pose potential human health risks which may vary from person to person. As a precaution, exposure

to liquids, vapors, mists or fumes should be minimized.

EFFECTS OF OVEREXPOSURE (Signs and symptoms of exposure)

Prolonged or repeated liquid contact with the skin will dry and defat the skin, leading to possible irritation and dermatitis.
High vapor concentrations (greater than approximately 1000 ppm, attainable at temperatures well above ambient) are irritating to the eyes and the respiratory tract, may cause headaches and dizziness, are anesthetic, may cause unconsciousness, and may have other central nervous system effects.

NATURE OF HAZARD AND TOXICITY INFORMATION

Prolonged or repeated skin contact with this product tends to remove skin oils possibly leading to irritation and dermatitis; however, based on human experience and available toxicological data, this product is judged to be neither a "corrosive" nor an "irritant" by OSHA criteria.

Product contacting the eyes may cause eye irritation

Lifetime skin painting studies conducted by the American Petroleum Institute, Exxon and others have shown that similar products boiling between 175-370°C (350-700°F) usually produce skin tumors and/or skin cancer in laboratory mice. The degree of carcinogenic response was weak to moderate with a relatively long latent period. The implications of these results for humans have not been determined.

Limited studies on oils that are very active carcinogens have shown that washing the animals' skin with soap and water between applications greatly reduces tumor formation. These studies demonstrate the effectiveness of cleansing the skin after contact.

Potential risks to humans can be minimized by observing good work practices and personal hygiene procedures generally recommended for petroleum products. See Section I for recommended protection and precautions.

Reports of animal studies using both sexes of several species have shown that kidney damage can occur in male rats after prolonged and repeated inhalation exposures to light hydrocarbon vapors of the general type present in this product. While the damage is of a low order of severity in animals, the implications of these results for humans have not yet been determined.

Product has a low order of acute oral and dermal toxicity, but minute amounts aspirated into the lungs during ingestion may cause mild to severe pulmonary injury and possibly death.

This product is judged to have an acute oral LD50 (rat) greater than 5 g/kg of body weight, and an acute dermal LD50 (rabbit) greater than 3.16 g/kg of body weight.

F. PHYSICAL DATA

The following data are approximate or typical values and should not be used for precise design purposes.

BOILING RANGE
160-350°C (320-650°F)

VAPOR PRESSURE
Less than 1 mm Hg @ 20°C

SPECIFIC GRAVITY (15.6 C/15.6 C)
0.86

VAPOR DENSITY (AIR = 1)
Greater than 5

MOLECULAR WEIGHT
Approximately 212 average

PERCENT VOLATILE BY VOLUME
100

pH
Essentially neutral

EVAPORATION RATE @ 1 ATM. AND 25 C (77 F)
(n-BUTYL ACETATE = 1)
0.02

POUR, CONGEALING OR MELTING POINT
-16 C (0 F)
Pour Point by ASTM D 97

SOLUBILITY IN WATER @ 1 ATM. AND 25 C (77 F)
Negligible; less than 0.1%

VISCOSITY
2.7 cSt @ 40 C

G. REACTIVITY

This product is stable and will not react violently with water. Hazardous polymerization will not occur. Avoid contact with strong oxidants such as liquid chlorine, concentrated oxygen, sodium hypochlorite or calcium hypochlorite.

H. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Shut off and eliminate all ignition sources. Keep people away. Recover free product. Add sand, earth or other suitable absorbent to spill area. Minimize breathing vapors. Minimize skin contact. Ventilate confined spaces. Open all windows and doors. Keep product out of sewers and watercourses by diking or impounding. Advise authorities if product has entered or may enter sewers, watercourses, or extensive land areas. Assure conformity with applicable governmental regulations. Continue to observe precautions for volatile, combustible vapors from absorbed material.

I. PROTECTION AND PRECAUTIONS

VENTILATION

Use only with ventilation sufficient to prevent exceeding recommended exposure limit or buildup of explosive concentrations of vapor in air.

RESPIRATORY PROTECTION

Use supplied-air respiratory protection in confined or enclosed spaces, if needed.

PROTECTIVE GLOVES

Use chemical-resistant gloves, if needed, to avoid prolonged or repeated skin contact.

EYE PROTECTION

Use splash goggles or face shield when eye contact may occur.

OTHER PROTECTIVE EQUIPMENT

Use chemical-resistant apron or other impervious clothing, if needed, to avoid contaminating regular clothing which could result in prolonged or repeated skin contact.

WORK PRACTICES / ENGINEERING CONTROLS

Keep containers and storage containers closed when not in use. Do not store near heat, sparks, flame or strong oxidants.

PERSONAL HYGIENE

Minimize breathing vapor, mist or fumes. Avoid prolonged or repeated contact with skin. Remove contaminated clothing; launder or dry-clean before reuse. Remove contaminated shoes and thoroughly clean before reuse; discard if oil-soaked. Cleanse skin thoroughly after contact, before breaks and meals, and at end of work period. Product is readily removed from skin by waterless hand cleaners followed by washing thoroughly with soap and water.

J. TRANSPORTATION INFORMATION

TRANSPORTATION INCIDENT INFORMATION

For further information relative to spills resulting from transportation incidents, refer to latest Department of Transportation Emergency Response Guidebook for Hazardous Materials Incidents, DOT P 5800 3

DOT IDENTIFICATION NUMBER

NA 1993

The information and recommendations contained herein are, to the best of Exxon's knowledge and belief, accurate and reliable as of the date issued. Exxon does not warrant or guarantee their accuracy or reliability, and Exxon shall not be liable for any loss or damage arising out of the use thereof.

The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use.

The Hazardous Materials Identification System (HMIS) and National Fire Protection Association (NFPA) ratings have been included by Exxon Company, U.S.A. in order to provide additional health and hazard classification information. The ratings recommended are based upon the criteria supplied by the developers of these rating systems, together with Exxon's interpretation of the available data.

FOR ADDITIONAL INFORMATION ON HEALTH
EFFECTS CONTACT:
DIRECTOR OF INDUSTRIAL HYGIENE
EXXON COMPANY, U.S.A.
P. O. BOX 2180 ROOM 2737
HOUSTON, TX 77252-2180
(713) 656-2443

FOR OTHER PRODUCT INFORMATION CONTACT:
MANAGER, MARKETING TECHNICAL SERVICES
EXXON COMPANY, U.S.A.
P. O. BOX 2180 ROOM 2455
HOUSTON, TX 77252-2180
(713) 656-5949