



July 24, 1995 Project 305-085.2C

Mr. Dan Kirk Shell Oil Products Company P.O. Box 4023 Concord, California 94524

Re: Quarterly Report - Second Quarter 1995
Shell Service Station
230 West MacArthur Boulevard at Piedmont Avenue
Oakland, California
WIC No 204-5508-0703

Dear Mr. Kirk:

The following presents the results of the second quarter 1995 monitoring program for the site referenced above. This letter has been prepared for Shell Oil Products Company by Pacific Environmental Group, Inc. (PACIFIC).

FINDINGS

Groundwater monitoring wells were gauged and sampled by Blaine Tech Services, Inc. (Blaine) at the direction of PACIFIC on June 26, 1995. Groundwater elevation contours for the sampling date are shown on Figure 1. Table 1 presents groundwater elevation data.

All wells were analyzed for total petroleum hydrocarbons calculated as gasoline (TPH-g). Groundwater analytical data are presented in Table 2; TPH-g and benzene concentrations for the June 1995 sampling event is shown on Figure 2. Blaine's groundwater sampling report, which includes field data and the certified analytical report, is presented as Attachment A.

If you have any questions regarding the contents of this letter, please call.

Sincerely,

Pacific Environmental Group, Inc.

Ross W.N. Tinline

Project Geologist

RG 5860

Attachments: Table 1 - Groundwater Elevation Data

Table 2 - Groundwater Analytical Data - Total Petroleum

TINLINE No. 5860

Hydrocarbons (TPH as Gasoline and BTEX Compounds)

Figure 1 - Groundwater Elevation Contour Map Figure 2 - TPH-g/Benzene Concentration Map Attachment A - Groundwater Sampling Report

cc: Ms. Lisa McCann, Regional Water Quality Control Board - S.F. Bay Region

Mr. Craig Mayfield, Alameda County Flood Control and Water

Conservation District

Mr. Gil Wistar, Alameda County Health Department

Table 1
Groundwater Elevation Data

| <u> </u> | | Well | Depth to | Groundwater |
|-----------|----------|---------------|-------------|-------------|
| Well | Date | Elevation | Water | Elevation |
| Number | Gauged | (feet, MSL) | (feet, TOC) | (feet, MSL) |
| Iddiliber | Gaugeu | (ICCL, INIOL) | (1661, 100) | (ICCL, MOL) |
| MW-1 | 07/14/88 | 73.89 | 13.30 | 60.59 |
| | 10/04/88 | | 13.65 | 60.24 |
| | 11/10/88 | | 13.55 | 60,34 |
| | 12/09/88 | | 13.22 | 60.67 |
| | 01/10/89 | | 12.86 | 61.03 |
| | 01/20/89 | | 12.91 | 60.98 |
| | 02/06/89 | | 12.94 | 60.95 |
| | 03/10/89 | | 12.59 | 61.30 |
| | 06/06/89 | | 14.05 | 59.84 |
| | 09/07/89 | | 14.92 | 58.97 |
| | 12/18/89 | | 14.88 | 59.01 |
| | 03/08/90 | | 14.08 | 59.81 |
| | 06/07/90 | | 13.89 | 60.00 |
| | 09/05/90 | | 14.83 | 59.06 |
| | 12/03/90 | | 15.05 | 58.84 |
| | 03/01/91 | | 14.34 | 59.55 |
| | 06/03/91 | | 14.16 | 59.73 |
| | 09/04/91 | | 14.60 | 59.29 |
| ŀ | 03/13/92 | | 13.40 | 60.49 |
| | 06/03/92 | | 13.76 | 60.13 |
| | 08/19/92 | | 14.57 | 59.32 |
| | 11/16/92 | | 14.78 | 59.11 |
| | 02/18/93 | | 12.14 | 61.75 |
| | 06/01/93 | | 13.30 | 60.59 |
| | 08/30/93 | | 14.32 | 59.57 |
| | 12/13/93 | | 14.06 | 59.83 |
| | 03/03/94 | | 13.12 | 60.77 |
| | 06/06/94 | | 14.20 | 59.69 |
| | 09/12/94 | | 15.72 | 58.17 |
| | 12/15/94 | | 12.98 | 60.91 |
| | 03/13/95 | | 11.74 | 62.15 |
| | 06/26/95 | | 13.00 | 60.89 |
| MW-2 | 07/14/88 | 75.24 | 15.18 | 60.06 |
| 14144-22 | 10/04/88 | 73.24 | 15.30 | 59.94 |
| | 11/10/88 | | 15.17 | 60.07 |
| | 12/09/88 | | 14.82 | 60.42 |
| 1 | 01/20/89 | | 14.54 | 60.70 |
| | 02/06/89 | | 14.59 | 60.65 |
| | 03/10/89 | | 14.88 | 60,36 |
| | 06/06/89 | | 15.30 | 59.94 |
| | 09/07/89 | | 16.76 | 58.48 |
| | 12/18/89 | | 16.65 | 58.59 |
| | 03/08/90 | j | 15.92 | 59.32 |
| ļ | 06/07/90 | | 16.10 | 59.14 |
| | 09/05/90 | . | 16.61 | 58.63 |
| | 00/00/80 | | 10.01 | 30.03 |

Table 1 (continued) Groundwater Elevation Data

| | - | Well | Depth To | Groundwater |
|---------|--------------|---------------|----------------|----------------|
| Well | Date | Elevation | Water | Elevation |
| Number | Gauged | (feet, MSL) | (feet, TOC) | (feet, MSL) |
| | | (1004, 14104) | | |
| MW-2 | 12/03/90 | | 17.06 | 58.18 |
| (cont.) | 03/01/91 | | 16.62 | 58.62 |
| | 06/03/91 | | 16.65 | 58.59 |
| | 09/04/91 | | 16.57 | 58.67 |
| | 03/13/92 | | 14.66 | 60.58 |
| | 06/03/92 | | 15.90 | 59.34 |
| | 08/19/92 | | 16.72 | 58.52 |
| | 11/16/92 | | 16.66 | 58.58 |
| | 02/18/93 | | 13.88 | 61.36 |
| | 06/01/93 | | 14.74 | 60.50 |
| | 08/30/93 | | 15.85 | 59.39 |
| | 12/13/93 | | 15.83 | 59.41 |
| | 03/03/94 | | 14.80 | 60.44 |
| | 06/06/94 | | 16.65 | 58.59 |
| | 09/12/94 | | 16.72 | 58.52 |
| | 12/15/94 | | 15.25 | 59,99 |
| | 03/13/95 | | 15.32 | 59.92 |
| | 06/26/95 | | 14.65 | 60.59 |
| MW-3 | 07/14/88 | 74.68 | 14.05 | 60.63 |
| IVIVV-3 | | 74.00 | | 60.08 |
| | 10/04/88 | | 14.60 | |
| | 11/10/88 | - | 14.35 | 60.33 |
| | 12/09/88 | | 14.04 13.70 | 60.64 |
| | 01/10/89 | | | 60,98 |
| | 01/20/89 | | 13.72 | 60.96 |
| | 02/06/89 | | 13.75 | 60.93 |
| | 03/10/89 | | 13.42 | 61.26 |
| | 06/06/89 | | 14.52 | 60.16 50.46 |
| | 09/07/89 | | 15.52 | 59.16 55.00 |
| | 12/18/89 | | 19.59 | 55.09 |
| | 03/08/90 | | 14.72 | 59.96 |
| | 06/07/90 | | 14.65 | 60.03 |
| | 09/05/90 | | 15.51 | 59.17 |
| | 12/03/90 | | 14.85 | 59.83 |
| | 03/01/91 | | 14.92 | 59.76 |
| | 06/03/91 | | 14.75 | 59.93 |
| | 09/04/91 | | 15.14 | 59.54 |
| | 03/13/92 | | 13.50 | 61.18 |
| | 06/03/92 | | 14.39 | 60.29 |
| į | 08/19/92 | į | 15.08 | 59.60 |
|] | 11/16/92 | : | 15.43 | 59.25 |
| 1 | 02/18/93 | | 12.96 | 61.72 |
| Ì | 06/01/93 | | 13.98 | 60.70 |
| 1 | 08/30/93 | | 14.82 | 59.86 |
| | 12/13/93 | | 14.70 | 59.98 |

Table 1 (continued) Groundwater Elevation Data

| | | Well | Depth To | Groundwater |
|---------|----------------|-------------|-------------|-------------|
| Well | Date | Elevation | Water | Elevation |
| Number | Gauged | (feet, MSL) | (feet, TOC) | (feet, MSL) |
| MW-3 | 03/03/94 | | 13.92 | 60.76 |
| (cont.) | 06/06/94 | | 14.73 | 59.95 |
| (00///) | 09/12/94 | | 15.42 | 59.26 |
| | 12/15/94 | | 13.80 | 60.88 |
| | 03/13/95 | | 12.41 | 62.27 |
| | 06/26/95 | | 13.79 | 60.89 |
| | 33.23.33 | | | •••• |
| MW-4 | 01/23/90 | 73.83 | 14.68 | 59.15 |
| | 03/08/90 | : | 14.38 | 59.45 |
| | .06/07/90 | | 14.27 | 59.56 |
| į | 09/05/90 | | 15.40 | 58.43 |
| | 12/03/90 | | 15.90 | 57.93 |
| | 06/03/91 | | 14.60 | 59.23 |
| | 09/04/91 | | 15.25 | 58.58 |
| | 03/13/92 | | 12.72 | 61.11 |
| | 06/03/92 | | 14.33 | 59.50 |
| | 08/19/92 | | 15.18 | 58.65 |
| | 11/16/92 | | 15.39 | 58.44 |
| | 02/18/93 | | 12.62 | 61.21 |
| | 06/01/93 | | 13.68 | 60.15 |
| | 08/30/93 | | 14.83 | 59.00 |
| 1 | 12/13/93 | | 14.50 | 59.33 |
| | 03/03/94 | | 13.48 | 60.35 |
| | 06/06/94 | | 14.26 | 59.57 |
| | 09/12/94 | | 15.42 | 58.41 |
| | 12/15/94 | | 13.43 | 60.40 |
| | 03/13/95 | ļ | 12.13 | 61.70 |
| | 06/25/95 | | 13.26 | 60.57 |
| MSL = N | lean sea level | | | |
| TOC = T | op of casing | | | |

Table 2
Groundwater Analytical Data
Total Petroleum Hydrocarbons
(TPH as Gasoline and BTEX Compounds)

| Well Number | Date Sampled | TPH as Gasoline (ppb) | Benzene (ppb) | Toluene (ppb) | Ethylbenzene (ppb) | Xylenes (ppb) |
|----------------|-----------------------|-----------------------------|------------------|------------------|-----------------------|------------------|
| MW-1 | 07/14/88 | ND | ND | ND | ND | ND |
| | 10/04/88 | ND | 8 | 4.3 | ND | 9 |
| | 11/10/88 | ND | ND | ND | ND | ND |
| | 12/09/88 | ND | ND | ND | ND | ND |
| | 01/10/89 | ND | ND | ND | ND | NA |
| | 01/20/89 | ND | ND | NA | NA | ND |
| | 02/06/89 | ND | ND | ND | ND | ND |
| | 03/10/89 | ND | ND | ND | ND | ND |
| | 06/06/89 | ND | ND | ND | ND | ND |
| | 09/07/89 | ND | ND | ND | ND | ND |
| | 12/18/89 | ND | ND | ND | ND | ND |
| | 03/08/90 | ND | ND | ND | ND | ND |
| | 06/07/90 | ND | ND | ND | ND | ND |
| | 09/05/90 | ND | ND | ND | ND | ND |
| | 12/03/90 | ND | ND | ND | ND | ND - |
| | 03/01/91 | ND | ND | ND | ND | ND |
| | 06/03/91 | ND | ND | ND | ND | ND |
| | 09/04/91 | ND | ND | ND | ND | ND |
| • | 03/13/92 | ND | ND | ND | ND | ND |
| | 06/03/92 | ND | ND | ND | ND | ND |
| | 08/19/92 | 87 | ND | ND | ND | ND |
| | 11/16/92 | ND | ND | ND | ND | ND |
| | 02/18/93 | 59ª | ND | ND | ND | ND |
| | 06/01/93 | ND | ND | ND | ND | ND |
| | 08/30/93 | ND | ND | ND | ND | ND |
| | 12/13/93 | ND | ND | ND | ND | ND |
| | 03/03/94 | 100 | ND | ND | ND | ND |
| | 06/06/94 | ND | ND | ND | ND | ND |
| | 09/12/94 | ND | ND | ND | ND | ND |
| | 12/15/94 | ND | ND | ND | ND | ND |
| | 03/13/95 ^d | 60 | 4.7 | 9.8 | ND | 2.9 |
| | 04/21/95 | ND | ND | ND. | ND | ND. |
| | 06/26/95 | ND | ND | ND | ND | ND |
| MW-2 | 07/14/88 | ND | 7.9 | 2.6 | 1.1 | 4 |
| | 10/04/88 | 90 | ND | 1.3 | 2.3 | 12 |
| | 11/10/88 | ND | ND | ND | ND | 2 |
| | 12/09/88 | ND | ND | 0.6 | ND | 3 |
| | 01/20/89 | ND | ND | ND | ND | ND |
| | 02/06/89 | NA | ND | ND | ND | ND |
| | 03/10/89 | ND | ND | ND | ND | ND |
| | 06/06/89 | ND | ND | 0.5 | ND | ND |
| | 09/07/89 | ND | ND | ND | ND | ND |

Table 2 (continued) Groundwater Analytical Data Total Petroleum Hydrocarbons (TPH as Gasoline and BTEX Compounds)

| | | TPH as | | | | |
|---------|-------------|------------------|-------------|---------|--------------|---------|
| Well | Date | Gasoline | Benzene | Toluene | Ethylbenzene | Xylenes |
| Number | Sampled | (ppb) | (ppb) | (ppb) | (ppb) | (ppb) |
| MW-2 | 12/18/89 | ND | ND | ND | ND | ND |
| (cont.) | 03/08/90 | ND | ND | ND | ND | ND |
| | 06/07/90 | ND | ND | ND | ND | ND |
| | 09/05/90 | ND | ND | ND | ND | ND |
| | 12/03/90 | ND | ND | ND | ND | ND |
| | 03/01/91 | ND | ND | ND | ND | ND |
| | 06/03/91 | ND | ND | ND | ND | ND |
| | 09/04/91 | ND | ND | ND | ND | ND |
| | 03/13/92 | ND | ND | ND | ND | ND |
| • | 06/03/92 | ND | ND | ND | ND | ND |
| | 08/19/92 | 67 | ND | ND | ND | ND |
| | 11/16/92 | 50 | ND | ND | ND | 1.2 |
| | 02/18/93 | 52 ^a | ND | ND | ND | ND |
| | 02/18/93(D) | 52 ^a | ND | ND | ND | ND |
| | 06/01/93 | ND | ND | ND | ND | ND |
| | 08/30/93 | 70 ^a | ND | ND | ND | ND |
| | 12/13/93 | 68 ^a | ND | ND | ND | ND |
| | 03/03/94 | 280 ^a | ND | ND | ND | ND |
| | 06/06/94 | ND | ND | ND | ND | ND |
| | 09/12/94 | ND | ND | ND | ND | ND |
| | 12/15/94 | 230 ^a | ND | ND | ND | ND |
| | 03/13/95 | ND | 2.9 | 6.3 | ND | 2.7 |
| | 04/21/95 | ND | ND | ND | ND | ND |
| | 06/26/95 | ND | ND | ND | ND | ND |
| MW-3 | 07/14/88 | ND | ND | ND | ND | ND |
| | 10/04/88 | ND | ND | ND | ND | 5 |
| | 11/10/88 | ND | ND | ND | ND | ND |
| | 12/09/88 | ND | ND | ND | ND | ND |
| | 01/10/89 | ND | ND | ND | ND | NA |
| | 01/20/89 | NA | NA | ND | ND | ND |
| | 02/06/89 | 70 | ND | ND | ND | ND |
| | 03/10/89 | 150 | ND | ND | ND | ND |
| | 06/06/89 | ND | ND | ND | ND | ND |
| | 09/07/89 | ND | 0.65 | ND | ND | ND |
| | 12/06/89 | 46 | 1.3 | ND | 0.44 | 0.66 |
| | 03/08/90 | ND | ND | ND | ND | ND |
| | 06/07/90 | ND | ND | ND | ND | ND |
| | 09/05/91 | ND | ND | ND | ND | ND |
| | 12/03/90 | ND | ND | ND | ND | ND |
| | 03/01/91 | 1.9 | 59 | ND | 22 | ND |
| | 06/03/91 | ND | ND | ND | ND | ND |
| | 09/04/91 | ND | ND | ND | ND | ND |
| | 03/13/92 | ND | ND | ND | ND | ND |

Table 2 (continued)

Groundwater Analytical Data

Total Petroleum Hydrocarbons

(TPH as Gasoline and BTEX Compounds)

| | | TPH as | | | | |
|---------|-------------|---|---------|---------------|--------------|---------|
| Well | Date | Gasoline | Benzene | Toluene | Ethylbenzene | Xylenes |
| Number | Sampled | (ppb) | (ppb) | (ppb) | (ppb) | (ppb) |
| MW-3 | 06/03/92 | ND | ND | ND | ND | ND |
| (cont.) | 08/19/92 | 92 | ND | ND | ND | ND |
| ` ' | 08/19/92(D) | 76 | ND | ND | ND | ND |
| | 11/16/92 | 200 ^a | ND | ND | ND | ND |
| | 11/16/92(D) | 140 ^a | ND | ND | ND | ND |
| | 02/18/93 | 680ª | ND | ND | ND | ND |
| | 06/01/93 | 160° | ND | ND | ND | ND |
| | 06/01/93(D) | 150 ^a | ND | ND | ND | ND |
| | 08/30/93 | 110 ^a | ND | ND | ND | ND |
| | 12/13/93 | 140 ^a | ND | ND | ND | ND |
| | 12/13/93(D) | 110 ^a | ND | ND | ND | ND |
| | 03/03/94 | 61 ^a | ND | ND | ND | ND |
| | 06/06/94 | ND | ND | ND | ND | ND |
| | 09/12/94 | ND | ND | ND | ND | ND |
| | 12/15/94 | ND | ND | 0.9 | ND | 0.6 |
| | 03/13/95 | 100 ^b | 7.9 | 17 | 0.7 | 6.1 |
| | 04/21/95 | 60 | 0.9 | 1.1 | ND | 1.0 |
| | 06/26/95 | ND | ND | ND | ND | ND |
| MW-4 | 01/23/90 | 1,600 | 100 | 10 | 30 | 20 |
| | 03/08/90 | 4,200 | 260 | 18 | 88 | 39 |
| | 06/07/90 | 2,000 | 150 | 6.9 | 14 | 17 |
| | 09/05/90 | 1,700 | 130 | 10 | 7.2 | 19 |
| | 12/03/90 | 2,600 | 108 | 41 | 17 | 59 |
| | 06/03/91 | 2,800 | 160 | 15 | 8.8 | 32 |
| | 09/04/91 | *************************************** | Separat | e-Phase Hydro | carbon Sheen | |
| | 03/13/92 | 2,700 | 180 | 70 | 5.9 | 29 |
| | 06/03/92 | 1,700 | 190 | ND | 30 | 23 |
| | 08/19/92 | 170 | 4.2 | ND | 0.6 | 1.0 |
| | 11/16/92 | 2,600 | 92 | 49 | 50 | 81 |
| | 02/18/93 | 7,400 | 120 | 38 | 51 | 87 |
| | 06/01/93 | 7,000 | 1,800 | 1,700 | 1,600 | 1,700 |
| | 08/30/93 | 2,100 | 80 | 11 | ND | 11 |
| | 08/30/93(D) | 2,100 | 77 | 5,6 | ND | 5.5 |
| | 12/13/93 | 2,000 ^a | 20 | ND | 21 | 52 |
| | 03/03/94 | 3,500 | 150 | 86 | 85 | 90 |
| | 03/03/94(D) | 3,200 | 130 | 73 | 74 | 76 |

Table 2 (continued) Groundwater Analytical Data

Total Petroleum Hydrocarbons (TPH as Gasoline and BTEX Compounds)

Shell Service Station 230 West MacArthur Boulevard at Piedmont Avenue Oakland, California

| Well Number | Date Sampled | TPH as Gasoline (ppb) | Benzene (ppb) | Toluene (ppb) | Ethylbenzene (ppb) | Xylenes (ppb) |
|----------------|--------------------------|-----------------------------|------------------|------------------|-----------------------|------------------|
| _ | 06/06/94 | 590 | 25 | ND | ND | ND |
| | 06/06/94(D) | 400 | 16 | ND | ND | ND |
| | 09/12/94 | 1,800 | 42 | ND | 3.7 | 4.7 |
| | 09/12/94(D) | 2,000 | 40 | ND | 5.7 | 8.0 |
| | 12/15/94 | 2,900 | 78 | 14 | 94 | 17 |
| | 12/15/94(D) | 2,900 | 90 | 7 | 96 | 18 |
| | 03/13/95 ^c | 2,700 | 240 | 24 | 99 | 34 |
| | 03/13/95(D) ^c | 2,500 | 300 | 24 | 140 | 28 |
| | 06/26/95 ` | 2,100 | 87 | 10 | 67 | 25 |
| | 06/26/95(D) | 2,300 | 92 | 12 | 74 | 26 |

ppb = Parts per billion


ND = Not detected


NA = Not analyzed

(D) = Duplicate sample


- a. The concentration reported as gasoline is primarily due to the presence of a discrete hydrocarbon peak not indicative of gasoline.
- b. The laboratory noted result to have an atypical gasoline pattern.
- c. The laboratory noted sample was analyzed within hold time but further dilution was required and done out of hold time. The laboratory suggests these to be minimum concentrations.
- d. The laboratory noted the sampled was analyzed after the method specified holding time.

See certified analytical reports for detection limits.





ATTACHMENT A GROUNDWATER SAMPLING REPORT



BLAINE TECH SERVICES INC.

985 TIMOTHY DRIVE SAN JOSE, CA 95133 (408) 995-5535 FAX (408) 293-8773

July 10, 1995

Shell Oil Company P.O. Box 4023 Concord, CA 94524

Attn: Daniel T. Kirk

SITE: Shell WIC #204-5508-0703 230 West MacArthur Blvd. Oakland, California

QUARTER: 2nd quarter of 1995

QUARTERLY GROUNDWATER SAMPLING REPORT 950626-A-1

This report contains data collected during routine inspection, gauging and sampling of groundwater monitoring wells performed by Blaine Tech Services, Inc. in response to the request of the consultant who is overseeing work at this site on behalf of our mutual client, Shell Oil Company. Data collected in the course of our field work is presented in a TABLE OF WELL GAUGING DATA. The field information was collected during our preliminary gauging and inspection of the wells, the subsequent evacuation of each well prior to sampling, and at the time of sampling.

Measurements taken include the total depth of the well and the depth to water. The surface of water was further inspected for the presence of immiscibles which may be present as a thin film (a sheen on the surface of the water) or as a measurable free product zone (FPZ). At intervals during the evacuation phase, the purge water was monitored with instruments that measure electrical conductivity (EC), potential hydrogen (pH), temperature (degrees Fahrenheit), and turbidity (NTU). In the interest of simplicity, fundamental information is tabulated here, while the bulk of the information is turned over directly to the consultant who is making professional interpretations and evaluations of the conditions at the site.

STANDARD PROCEDURES

Evacuation

Groundwater wells are thoroughly purged before sampling to insure that the sample is collected from water that has been newly drawn into the well from the surrounding geologic formation. The selection of equipment to evacuate each well is based on the physical characteristics of the well and what is known about the performance of the formation in which the well has been installed. There are several suitable devices which can be used for evacuation. The most commonly employed devices are air or gas actuated pumps, electric submersible pumps, and hand or mechanically actuated bailers. Our personnel frequently employ USGS/Middleburg positive displacement pumps or similar air actuated pumps which do not agitate the water standing in the well.

Normal evacuation removes three case volumes of water from the well. More than three case volumes of water are removed in cases where more evacuation is needed to achieve stabilization of water parameters and when requested by the local implementing agency. Less water may be removed in cases where the well dewaters and does not recharge to 80% of its original volume within two hours and any additional time our personnel have reason to remain at the site. In such cases, our personnel return to the site within twenty four hours and collect sample material from the water which has recharged into the well case.

Decontamination

All apparatus is brought to the site in clean and serviceable condition. The equipment is decontaminated after each use and before leaving the site. Effluent water from purging and on-site equipment cleaning is collected and transported to Shell's Martinez Manufacturing Complex in Martinez, California.

Free Product Skimmer

The column headed, VOLUME OF IMMISCIBLES REMOVED (ml) is included in the TABLE OF WELL GAUGING DATA to cover situations where a free product skimming device must be removed from the well prior to gauging. Skimmers are installed in wells with a free product zone on the surface of the water. The skimmer is a free product recovery device which often prevents normal well gauging and free product zone measurements. The 2.0" and 3.0" PetroTraps fall into the category of devices that obstruct normal gauging. In cases where the consultant elects to have our personnel pull the skimmers out of the well and gauge the well, our personnel perform the additional task of draining the accumulated free product out of the PetroTrap before putting it back in the well. This

recovered free product is measured and logged in the VOLUME OF IMMISCIBLES REMOVED column. Gauging at such sites is performed in accordance with specific directions from the professional consulting firm overseeing work at the site on Shell's behalf.

Sample Containers

Sample material is collected in specially prepared containers which are provided by the laboratory that performs the analyses.

Sampling

Sample material is collected in stainless steel bailer type devices normally fitted with both a top and a bottom check valve. Water is promptly decanted into new sample containers in a manner which reduces the loss of volatile constituents and follows the applicable EPA standard for handling volatile organic and semi-volatile compounds.

Following collection, samples are promptly placed in an ice chest containing prefrozen blocks of an inert ice substitute such as Blue Ice or Super Ice. The samples are maintained in either an ice chest or a refrigerator until delivered into the custody of the laboratory.

Sample Designations

All sample containers are identified with a site designation and a discrete sample identification number specific to that particular groundwater well. Additional standard notations (e.g. time, date, sampler) are also made on the label.

Chain of Custody

Samples are continuously maintained in an appropriate cooled container while in our custody and until delivered to the laboratory under a standard Shell Oil Company chain of custody. If the samples are taken charge of by a different party (such as another person from our office, a courier, etc.) prior to being delivered to the laboratory, appropriate release and acceptance records are made on the chain of custody (time, date, and signature of the person releasing the samples followed by the time, date and signature of the person accepting custody of the samples).

page 3

Hazardous Materials Testing Laboratory

The samples obtained at this site were delivered to National Environmental Testing, Inc. in Santa Rosa, California. NET is a California Department of Health Services certified Hazardous Materials Testing Laboratory and is listed as DOHS HMTL #178.

Objective Information Collection

Blaine Tech Services, Inc. performs specialized environmental sampling and documentation as an independent third party. In order to avoid compromising the objectivity necessary for the proper and disinterested performance of this work, Blaine Tech Services, Inc. performs no consulting and does not become involved in the marketing or installation of remedial systems of any kind. Blaine Tech Services, Inc. is concerned only with the generation of objective information, not with the use of that information to support evaluations and recommendations concerning the environmental condition of the site. Even the straightforward interpretation of objective analytical data is better performed by interested regulatory agencies, and those engineers and geologists who are engaged in the work of providing professional opinions about the site and proposals to perform additional investigation or design remedial systems.

Reportage

Submission of this report and the attached laboratory report to interested regulatory agencies is handled by the consultant in charge of the project. Any professional evaluations or recommendations will be made by the consultant under separate cover.

Please call if we can be of any further assistance.

Fire This he.
Richard C. Blaine

RCB/lp

attachments: table of well gauging data

chain of custody

certified analytical report

cc: Pacific Environmental Group, Inc. 2025 Gateway Place, Suite #440

San Jose, CA 95110 ATTN: Rhonda Barrick

TABLE OF WELL GAUGING DATA

| WELL I.D. | DATA COLLECTION DATE | MEASUREMENT REFERENCED TO | QUALITATIVE OBSERVATIONS (sheen) | DEPTH TO FIRST IMMISCIBLES LIQUID (FPZ) (feet) | THICKNESS OF IMMISCIBLES LIQUID ZONE (feet) | VOLUME OF IMMISCIBLES REMOVED (ml) | DEPTH TO WATER (feet) | DEPTH TO WELL BOTTOM (feet) |
|--------------|----------------------------|---------------------------------|----------------------------------|---|--|---|--------------------------------|--------------------------------------|
| MW-1 | 6/26/95 | TOC | | NONE | - | | 13.00 | 29.38 |
| MW-2 | 6/26/95 | TOC | _ | NONE | | _ | 14.65 | 27.85 |
| MW-3 | 6/26/95 | TOC | - | NONE | | _ | 13.79 | 28.10 |
| MW-4 * | 6/26/95 | TOC | - | NONE | | | 13.26 | 23.98 |

^{*} Sample DUP was a duplicate sample taken from well MW-4.

| SHEL | 1 01 | 1 00 | NAF | - Λ ΛΙ | v | | | | 7 | | | | | <u> </u> | | ···· | | <u></u> | | | \$7353 |
|------------------------------------|--------------|--------|--------|-----------------|--------------|------------------|-------------------|-----------|--------------|-------------------|-------------------|-------------------|--------|----------|-------------------|----------------|------------------|---------------|----------------------------|-------------|------------------------|
| RETAIL | ENVIR | ONME | NTAL | ENGI | NEER | NG - | WF | :51 | | | C | IAH se | N C | OF (| CUS 9 <u>5</u> | 10 2 | DY | RE | CORD | 1 | e: 6-26-95 |
| ISile Address: | | MacArt | | | | | T | | <u></u> | | | | | | | | 40 | | 7 | <u> </u> | e / ol /- : |
| | -5508- | | id. D | 1.00., | Uakı | Land | | | | Ar | aly | sis R | equ | lire | <u>d</u> | | -, | - | LAB: NE | <u></u> | |
| | | | | | | | | | | | | | | 1. | | İ | | | CHECK ONE (1) LOX ONLY | CI/DI | JMIT DHUORA HRUT |
| Shell Engineer: | | | | Phone | No.: | (510) | 1 | | | | | | | | | | | } | Quarterly Montoring | Q sun | 24 hours |
| Dan Kirk Consuliani Name & | Addes | | | Fax # | 675 <u>-</u> | -6160 | | | | | | | | | | } | | | \$1 investigation |] 1411 | 44 hours |
| Blaine Tech Ser 985 Timothy Dri | vices. | Inc. | | | | | | | | - | | 8020 | | | | : | | | Soll Closelly/Disposal |] £LL3 | |
| Consultant Contact | .ve : | an Jos | | Phone | No | (408) | 1 | | | 6 | | BIEX | | | | | | | Woles Closelty/Disposal | J 443 | 15 days (Normal |
| Jim Keller | | | | 995-5 Fax #: | 535 293- | -8773 | S _{GS}) | Diesel). | , | 8240) | | જ | | ļ | | ļ · | | | Lawrence . |] 6462 | Olyet 🗀 🗀 |
| Comments: | | | | - | 64, Z V. | 0110 | | | 8 | (EPA | | 8015 | | | | | | | Woler Rem, or Sys. |] His | NOTE: Notify Lab at |
| Sampled by: Lan | | 11-0 | | 2 | | | Mod | Mod. | 8020/602) | 50 | ਰ | TPH 8 | | | | <u> </u> | Ď | _ | Other | _ | 24/48 hm. 1AT. |
| | / | | 2 | | | • | 8015 | 8015 | 802 | Į g | 9 | l no | | | | ezi. | 200 | Y/N | | | |
| Printed Name: DA | WIDY | VAL | EN | 77.NF | = | | ≾ | (EPA 8 | (EPA | O O | ğ | <u> </u> | | | So | Jer S | 등 | SHe | MATERIAL | 1 | SAMPLE |
| Sample ID | Date | Sludge | Soll | Waler | Alr | No. of conts. | TPH (E | IPH Œ | BIEX | Volatile Organics | Test for Disposal | Combination | | | Asbestos | Confainer Size | Preparation Used | СотроѕН | DESCRIPTION | | CONDITION/ COMMENTS |
| mu 1 | 6/26 | | | X | | 3 | • | | | - | - | X | | | Ť | | | | | - | |
| MW 2 | 926 | | | X | , | 3 | | | | | | X | | | | | | | | | |
| MW 3 | 6/26 | , | | X | | 3 | | | | | | X | | | | | | | | | |
| NW 4 | 926 | | \$ | X | | 3 | | | | | | X | | | - | | | | | - | |
| TB | 1/26 | | | X | | 2 | | | | | | X | | | | | | / | 6/276- | | |
| EB | 976 | | | X | | 3 | | | | | • | X | | | | | | 1 | 9275 | | |
| DUP | 926 | • | | X | | 3 | | | | | | $\langle \rangle$ | | | | | | | Deal Sorta | at . | |
| 1 | | | | | | | | | _ | | | / \ | | | ┪ | | | | Alal Inta | - | |
| elinquished by Monopure | } | Printe | d Nam | <u> </u> e: | | <u> </u> | Dale | | [| Rog | 9 N 9 9 | TUGA | glure. | 10 | | | | riotos | i Matme: | | |
| olling plastical of (signal pro |); - | Pinje | d None | 9; | | | | : 61 | 30 | 174 | 70 | THE S | ~~ | | | | | 1-21 | | | Dote: 6/27 |
| elinquished By (signature | | Printe | d Name | ien. | 19 PC | | Time Date | 16 | 100 | Rec | € 7 00 q | (HOUG | Jule) | ene | | | P | | M GLEENE Name: | | Date: ()7 (01) |
| | | IHE | LABOR | A YROIA | AUST PE | OVIDE A | Time | : Y OF | THIS C | L CHAII | Ų N•OF• | CUSTO | י צמכ | VITIL | NVOV | TE AL | | | | · | Date: Time: |
| • | | | | | | | | | | | | | | ****** | XI) | دة./A() | | | NCS | | hate On plane |



Santa Rosa Division 3636 North Laughlin Road Suite 110 Santa Rosa, CA 95403-8226

Tel: (707) 526-7200 Fax: (707) 541-2333

Jim Keller Blaine Tech Services 985 Timothy Dr. San Jose, CA 95133 Date: 07/06/1995

NET Client Acct. No: 1821

NET Job No: 95.02514 Received: 06/28/1995

Client Reference Information

Shell 230 West MacArthur Blvd., Oakland, CA/950626-A1

Sample analysis in support of the project referenced above has been completed and results are presented on following pages. Results apply only to the samples analyzed. Reproduction of this report is permitted only in its entirety. Please refer to the enclosed "Key to Abbreviations" for definition of terms. Should you have questions regarding procedures or results, please feel welcome to contact Client Services.

Project Manager

Approved by:

Ken Larson

Division Manager

Enclosure(s)





Client Name: Blaine Tech Services

Client Acct: 1821 ® NET Job No: 95.02514

Date: 07/06/1995

BLAP Cert: 1386

Page: 2

Ref: Shell 230 West MacArthur Blvd., Oakland, CA/950626-A1

SAMPLE DESCRIPTION: MW1

Date Taken: 06/26/1995

Time Taken:

| NET 29 WDTG NO: 744828 | | | | | | | | Run |
|----------------------------|---------|-------|-----------|--------|------------|-----------|------------|-------|
| | | | Reporting | | | Date | Date | Batch |
| Parameter | Results | Flags | Limit | Units | Method | Extracted | Analyzed | No. |
| METHOD 5030/8015-M (Shell) | | | | | | | | |
| DILUTION FACTOR* | 1 | | | • | | | 06/30/1995 | 2976 |
| Purgeable TPH | ND | | 50 | ug/L | 5030/M8015 | | 06/30/1995 | 2976 |
| Carbon Range: C6 to C12 | | | | | | | 06/30/1995 | 2976 |
| METHOD 8020 (GC, Liquid) | | | | | | | 06/30/1995 | 2976 |
| Benzene | ND | | 0.5 | ug/L | 8020 | | 06/30/1995 | 2976 |
| Toluene | ND | | 0.5 | ug/L | 8020 | | 06/30/1995 | 2976 |
| Ethylbenzene | ND | | 0.5 | ug/L | 8020 | | 06/30/1995 | 2976 |
| Xylenes (Total) | ND | | 0.5 | ug/L | 8020 | | 06/30/1995 | 2976 |
| SURROGATE RESULTS | | | | | | | 06/30/1995 | 2976 |
| Bromofluorobenzene (SURR) | 94 | | | % Rec. | 8020 | | 06/30/1995 | 2976 |
| | | | | | | | | |



Client Name: Blaine Tech Services Date: 07/06
Client Acct: 1821 BLAP Cert: 1386 ® NET Job No: 95.02514

Date: 07/06/1995

Page: 3

Ref: Shell 230 West MacArthur Blvd., Oakland, CA/950626-Al

SAMPLE DESCRIPTION: MW2

Date Taken: 06/26/1995

Time Taken:

| NET Sample No: 244859 | | | | | | | Run |
|----------------------------|---------------|-----------|--------|--------------------|-----------|------------|-------|
| | | Reporting | | | Date | Date | Batch |
| Parameter | Results Flags | Limit | Units | Method | Extracted | Analyzed | No. |
| METHOD 5030/8015-M (Shell) | | | | | | | |
| DILUTION FACTOR* | 1 | | | | • | 06/30/1995 | 2976 |
| Purgeable TPH | ND | 50 | ug/L | 5030/M8 015 | | 06/30/1995 | 2976 |
| Carbon Range: C6 to C12 | | | | | | 06/30/1995 | 2976 |
| METHOD 8020 (GC, Liquid) | | | | | | 06/30/1995 | 2976 |
| Benzene | ND | 0.5 | ug/L | 8020 | | 06/30/1995 | 2976 |
| Toluene | ND | 0.5 | ug/L | 8020 | | 06/30/1995 | 2976 |
| Ethylbenzene | ND | 0.5 | ug/L | 8020 | | 06/30/1995 | 2976 |
| Xylenes (Total) | ND | 0.5 | ug/L | 8020 | | 06/30/1995 | 2976 |
| SURROGATE RESULTS | | | | | | 06/30/1995 | 2976 |
| Bromofluorobenzene (SURR) | 88 | | % Rec. | 8020 | | 06/30/1995 | 2976 |



Client Name: Blaine Tech Services Date: 07/06/1995
Client Acct: 1821 ELAP Cert: 1386

NET Job No: 95.02514 ® NET Job No: 95.02514

Page: 4

Ref: Shell 230 West MacArthur Blvd., Oakland, CA/950626-A1

SAMPLE DESCRIPTION: MW3

Date Taken: 06/26/1995

Time Taken:

| NET Sample No: 244860 | | | | | | | | Kun |
|----------------------------|---------|-------|-----------|--------|------------|-----------|------------|-------|
| | | | Reporting | | | Date | Date | Batch |
| Parameter | Results | Flags | Limit | Units | Method | Extracted | Analyzed | No. |
| METHOD 5030/8015-M (Shell) | | | | | | | | |
| DILUTION FACTOR* | 1 | | | | | | 06/30/1995 | 2976 |
| Purgeable TPH | ND | | 50 | ug/L | 5030/M8015 | | 06/30/1995 | 2976 |
| Carbon Range: C6 to C12 | | | | | | | 06/30/1995 | 2976 |
| METHOD 8020 (GC, Liquid) | | | | | | | 06/30/1995 | 2976 |
| Benzene | ND | | 0.5 | ug/L | 8020 | | 06/30/1995 | 2976 |
| Toluene | ND | | 0.5 | ug/L | 8020 | | 06/30/1995 | 2976 |
| Ethylbenzene | ND | | 0.5 | ug/L | 8020 | | 06/30/1995 | 2976 |
| Xylenes (Total) | ND | | 0.5 | ug/L | 8020 | | 06/30/1995 | 2976 |
| SURROGATE RESULTS | | | | | | | 06/30/1995 | 2976 |
| Bromofluorobenzene (SURR) | 94 | | | % Rec. | 8020 | | 06/30/1995 | 2976 |
| | | | | | | | | |



Client Name: Blaine Tech Services Date: 07/06
Client Acct: 1821 ELAP Cert: 1386 ® NET Job No: 95.02514

Page: 5

Date: 07/06/1995

Ref: Shell 230 West MacArthur Blvd., Oakland, CA/950626-A1

SAMPLE DESCRIPTION: MW4

Date Taken: 06/26/1995

Time Taken:

| NET Sample No: 244861 | | | | | | | | Run |
|----------------------------|---------|-------|-----------|--------|------------|-----------|------------|-------|
| | | | Reporting | | | Date | Date | Batch |
| Parameter | Results | Flags | Limit | Units | Method | Extracted | Analyzed | No. |
| METHOD 5030/8015-M (Shell) | | | | | | | | |
| DILUTION FACTOR* | 10 | | | | | | 07/03/1995 | 2977 |
| Purgeable TPH | 2,100 | | 500 | ug/L | 5030/M8015 | | 07/03/1995 | 2977 |
| Carbon Range: C6 to C12 | | | | | | · | 07/03/1995 | 2977 |
| METHOD 8020 (GC, Liquid) | | | | | | | 07/03/1995 | 2977 |
| Benzene | 87 | | 5 | ug/L | 8020 | | 07/03/1995 | 2977 |
| Toluene | 10 | | 5 | ug/L | 8020 | | 07/03/1995 | 2977 |
| Ethylbenzene | 67 | | 5 | ug/L | 8020 | | 07/03/1995 | 2977 |
| Xylenes (Total) | 25 | | 5 | ug/L | 8020 | | 07/03/1995 | 2977 |
| SURROGATE RESULTS | | | | | | | 07/03/1995 | 2977 |
| Bromofluorobenzene (SURR) | 117 | | | % Rec. | 8020 | | 07/03/1995 | 2977 |



 Client Name:
 Blaine Tech Services
 Date:
 07/06/1995

 Client Acct:
 1821
 ELAP Cert:
 1386

 ® NET Job No:
 95.02514
 Page:
 6

Ref: Shell 230 West MacArthur Blvd., Oakland, CA/950626-A1

SAMPLE DESCRIPTION: TB

Date Taken: 06/26/1995

Time Taken:

| NET Sample No: 244862 | | | | | | Run | | |
|----------------------------|---------|-------|-----------|--------|------------|-------------------|------------|-------|
| | | | Reporting | | | Date Extracted | Date | Batch |
| Parameter | Results | Flags | Limit | Units | Method | | Analyzed | No. |
| METHOD 5030/8015-M (Shell) | | | | | | | | |
| DILUTION FACTOR* | 1 | | | | ٠ | | 06/30/1995 | 2976 |
| Purgeable TPH | ND | | 50 | ug/L | 5030/M8015 | | 06/30/1995 | 2976 |
| Carbon Range: C6 to C12 | | | | | | | 06/30/1995 | 2976 |
| METHOD 8020 (GC, Liquid) | | | | | | | 06/30/1995 | 2976 |
| Benzene | ND | | 0.5 | ug/L | 8020 | | 06/30/1995 | 2976 |
| Toluene | ND | | 0.5 | ug/L | 8020 | | 06/30/1995 | 2976 |
| Ethylbenzene | ND | | 0.5 | ug/L | 8020 | | 06/30/1995 | 2976 |
| Xylenes (Total) | ND | | 0.5 | ug/L | 8020 | | 06/30/1995 | 2976 |
| SURROGATE RESULTS | | | | | | | 06/30/1995 | 2976 |
| Bromofluorobenzene (SURR) | 88 | | | % Rec. | 8020 | | 06/30/1995 | 2976 |
| | | | | | | | | |



Client Name: Blaine Tech Services

Client Acct: 1821 ® NET Job No: 95.02514

Date.
ELAP Cert: 1386 Date: 07/06/1995

Page: 7

Ref: Shell 230 West MacArthur Blvd., Oakland, CA/950626-Al

SAMPLE DESCRIPTION: DUP

Date Taken: 06/26/1995

Time Taken:

NET Sample No: 244863

| NEI Sample No: 244863 | | | | | | | | Run |
|----------------------------|---------------|-------|-----------|-----------|------------|----------|------------|-------|
| | | | Reporting | Reporting | | | Date | Batch |
| Parameter | Results Flags | Limit | Units | Method | Extracted | Analyzed | No. | |
| METHOD 5030/8015-M (Shell) | | | | | | | | |
| DILUTION FACTOR* | 10 | | | | | | 07/03/1995 | 2977 |
| Purgeable TPH | 2,300 | | 500 | ug/L | 5030/M8015 | | 07/03/1995 | 2977 |
| Carbon Range: C6 to C12 | | | - | | | | 07/03/1995 | 2977 |
| METHOD 8020 (GC, Liquid) | | | | | | | 07/03/1995 | 2977 |
| Benzene | 92 | | 5 | ug/L | 8020 | | 07/03/1995 | 2977 |
| Toluene | 12 | | 5 | ug/L | 8020 | | 07/03/1995 | 2977 |
| Ethylbenzene | 74 | | 5 | ug/L | 8020 | | 07/03/1995 | 2977 |
| Xylenes (Total) | 26 | | 5 | ug/L | 8020 | | 07/03/1995 | 2977 |
| SURROGATE RESULTS | | | | | | | 07/03/1995 | 2977 |
| Bromofluorobenzene (SURR) | 122 | MI | | % Rec. | 8020 | | 07/03/1995 | 2977 |
| | | | | | | | | |

MI : Matrix Interference Suspected.



Client Name: Blaine Tech Services Date: 07/06
Client Acct: 1821 ELAP Cert: 1386 ® NET Job No: 95.02514

Date: 07/06/1995

Page: 8

Ref: Shell 230 West MacArthur Blvd., Oakland, CA/950626-A1

SAMPLE DESCRIPTION: EB

Date Taken: 06/26/1995

Time Taken:

| NET Sample No: 244864 | | | | | | | | Run |
|----------------------------|-----------|------|-----------|-------------------|------------|-----------|------------|-------|
| | | | Reporting | ŗ | | Date | Date | Batch |
| Parameter | Results F | lags | Limit | Units | Method | Extracted | Analyzed | No. |
| METHOD 5030/8015-M (Shell) | | | | | | | | |
| DILUTION FACTOR* | í | | | | | | 07/01/1995 | 2976 |
| Purgeable TPH | ND | | 50 | ug/L | 5030/M8015 | | 07/01/1995 | 2976 |
| Carbon Range: C6 to C12 | | | | | | | 07/01/1995 | 2976 |
| METHOD 8020 (GC, Liquid) | | | | | | | 07/01/1995 | 2976 |
| Benzene | ND | | 0.5 | ug/L | 8020 | | 07/01/1995 | 2976 |
| Toluene | ND | | 0.5 | ug/L | 8020 | | 07/01/1995 | 2976 |
| Ethylbenzene | ND | | 0.5 | ug/L | 8020 | | 07/01/1995 | 2976 |
| Xylenes (Total) | ND | | 0.5 | ug/L | 8020 | | 07/01/1995 | 2976 |
| SURROGATE RESULTS | | | | | | | 07/01/1995 | 2976 |
| Bromofluorobenzene (SURR) | 87 | | | <pre>% Rec.</pre> | 8020 | | 07/01/1995 | 2976 |
| | | | | | | | | |



Client Name: Blaine Tech Services Date: 07/06/1995
Client Acct: 1821 ELAP Cert: 1386
® NET Job No: 95.02514 Page: 9

Ref: Shell 230 West MacArthur Blvd., Oakland, CA/950626-A1

CONTINUING CALIBRATION VERIFICATION STANDARD REPORT

| | | CCV | CCV | | | | |
|----------------------------|-----------------------|----------|----------|--------|------------|----------|--------|
| | CCV | Standard | Standard | | | | Run |
| | Standard | Amount | Amount | | Date | Analyst | Batch |
| Parameter | <pre>% Recovery</pre> | Found | Expected | Units | Analyzed | Initials | Number |
| METHOD 5030/8015-M (Shell) | | • | | | | | |
| Purgeable TPH | 104.0 | 0.52 | 0.50 | mg/L | 06/30/1995 | aal | 2976 |
| Benzene | 87.2 | 4.36 | 5.00 | ug/L | 06/30/1995 | aal | 2976 |
| Toluene | 85.8 | 4.29 | 5.00 | ug/L | 06/30/1995 | aal | 2976 |
| Ethylbenzene | 94.0 | 4.70 | 5.00 | ug/L | 06/30/1995 | aal | 2976 |
| Xylenes (Total) | 95.3 | 14.3 | 15.0 | ug/L | 06/30/1995 | aal | 2976 |
| Bromofluorobenzene (SURR) | 99.0 | 99 | 100 | % Rec. | 06/30/1995 | aal | 2976 |
| METHOD 5030/8015-M (Shell) | | | | | | | |
| Purgeable TPH | 104.0 | 0.52 | 0.50 | mg/L | 07/03/1995 | lss | 2977 |
| Benzene | 95.6 | 4.78 | 5.00 | ug/L | 07/03/1995 | lss | 2977 |
| Toluene | 94.8 | 4.74 | 5.00 | ug/L | 07/03/1995 | lss | 2977 |
| Ethylbenzene | 103.4 | 5.17 | 5.00 | ug/L | 07/03/1995 | lss | 2977 |
| Xylenes (Total) | 105.3 | 15.8 | 15.0 | ug/L | 07/03/1995 | lss | 2977 |
| Bromofluorobenzene (SURR) | 107.0 | 107 | 100 | % Rec. | 07/03/1995 | lss | 2977 |



Client Name: Blaine Tech Services Date: 07/06/1995 Client Acct: 1821 ELAP Cert: 1386 ® NET Job No: 95.02514

Page: 10

Ref: Shell 230 West MacArthur Blvd., Oakland, CA/950626-A1

METHOD BLANK REPORT

| | Method | | • | | | | |
|----------------------------|--------|-----------|--------|------------|----------|--------|--|
| | Blank | | | | • | Run | |
| | Amount | Reporting | | Date | Analyst | Batch | |
| Parameter | Found | Limit | Units | Analyzed | Initials | Number | |
| METHOD 5030/8015-M (Shell) | | | | | | | |
| Purgeable TPH | ND | 0.05 | mg/L | 06/30/1995 | aal | 2976 | |
| Benzene | ND | 0.5 | ug/L | 06/30/1995 | aal | 2976 | |
| Toluene | ND | 0.5 | ug/L | 06/30/1995 | aal | 2976 | |
| Ethylbenzene | ND | 0.5 | ug/L | 06/30/1995 | aal | 2976 | |
| Xylenes (Total) | ND | 0.5 | ug/L | 06/30/1995 | aal | 2976 | |
| Bromofluorobenzene (SURR) | 95 | | % Rec. | 06/30/1995 | aal | 2976 | |
| METHOD 5030/8015-M (Shell) | | | | | | | |
| Purgeable TPH | ND | 0.05 | mg/L | 07/03/1995 | lss | 2977 | |
| Benzene | ND | 0.5 | ug/L | 07/03/1995 | lss | 2977 | |
| Toluene | ND | 0.5 | ug/L | 07/03/1995 | lss | 2977 | |
| Ethylbenzene | ND | 0.5 | ug/L | 07/03/1995 | lss | 2977 | |
| Xylenes (Total) | ND | 0.5 | ug/L | 07/03/1995 | lss | 2977 | |
| Bromofluorobenzene (SURR) | 104 | | % Rec. | 07/03/1995 | lss | 2977 | |
| | | | | | | | |



Client Name: Blaine Tech Services Date: 07/06/1995 Client Acct: 1821 ELAP Cert: 1386

Page: 11

Ref: Shell 230 West MacArthur Blvd., Oakland, CA/950626-A1

MATRIX SPIKE / MATRIX SPIKE DUPLICATE

| | | Matrix | | | | Matrix | Matrix Spike | | | | |
|----------------------------|--------|--------|------|--------|--------|--------|-----------------|-------|------------|-------|--------|
| | Matrix | Spike | | | | | | | | | |
| | Spike | Dup | | Spike | Sample | Spike | Dup. | | Date | Run | Sample |
| Parameter | ₹ Rec. | % Rec. | RPD | Amount | Conc. | Conc. | Conc. | Units | Analyzed | Batch | Spiked |
| METHOD 5030/8015-M (Shell) | | | | | | | | | | | 244762 |
| Purgeable TPH | 106.0 | 104.0 | 1.9 | 0.5 | ND | 0.53 | 0.52 | mg/L | 06/30/1995 | 2976 | 244762 |
| Benzene | 90.7 | 87.9 | 3.1 | 10.7 | ND | 9.7 | 9.4 | ug/L | 06/30/1995 | 2976 | 244762 |
| Toluene | 99.1 | 105.9 | 6.5 | 32 | ND | 31.7 | 33.9 | ug/L | 06/30/1995 | 2976 | 244762 |
| METHOD 5030/8015-M (Shell) | | | | | | | | | | | 244907 |
| Purgeable TPH | 104.0 | 112.0 | 7.4 | 0.50 | ND | 0.52 | 0.56 | mg/L | 07/03/1995 | 2977 | 244907 |
| Benzene | 97.1 | 108.7 | 11.2 | 10.3 | ND | 10.0 | 11.2 | ug/L | 07/03/1995 | 2977 | 244907 |
| Toluene | 101.2 | 95.9 | 5.3 | 34.4 | ND | 34.8 | 33.0 | ug/L | 07/03/1995 | 2977 | 244907 |



KEY TO ABBREVIATIONS and METHOD REFERENCES

Less than; When appearing in results column indicates analyte
not detected at the value following. This datum supercedes
the listed Reporting Limit.

: Reporting Limits are a function of the dilution factor for any given sample. To obtain the actual reporting limits for this sample, multiply the stated Reporting Limits by the dilution factor (but do not multiply reported values).

ICVS : Initial Calibration Verification Standard (External Standard).

mean : Average; sum of measurements divided by number of measurements.

mg/Kg (ppm): Concentration in units of milligrams of analyte per kilogram of sample, wet-weight basis (parts per million).

mg/L : Concentration in units of milligrams of analyte per liter of sample.

mL/L/hr : Milliliters per liter per hour.

MPN/100 mL : Most probable number of bacteria per one hundred milliliters of sample.

N/A : Not applicable.

NA : Not analyzed.

ND : Not detected; the analyte concentration is less than applicable listed

reporting limit.

NTU : Nephelometric turbidity units.

RPD : Relative percent difference, 100 [Value 1 - Value 2]/mean value.

SNA : Standard not available.

ug/Kg (ppb) : Concentration in units of micrograms of analyte per kilogram of sample,

wet-weight basis (parts per billion).

ug/L : Concentration in units of micrograms of analyte per liter of sample.

umhos/cm : Micromhos per centimeter.

Method References

Methods 100 through 493: see "Methods for Chemical Analysis of Water & Wastes", U.S. EPA, 600/4-79-020, rev. 1983.

Methods 601 through 625: see "Guidelines Establishing Test Procedures for the Analysis of Pollutants" U.S. EPA, 40 CFR, Part 136, rev. 1988.

Methods 1000 through 9999: see "Test Methods for Evaluating Solid Waste", U.S. EPA SW-846, 3rd edition, 1986.

 \underline{SM} : see "Standard Methods for the Examination of Water & Wastewater, 17th Edition, APHA, 1989.

| Project #: 950626-A1 Wic #: 204-5508-0703 | | | | | | | | | | |
|---|---|-------------|-------------------------------------|--|--------------------|--|--|--|--|--|
| Sampler: | 2V | | Sta | rt Date: 6 | -26-95 | | | | | |
| Well I.D | · · nw-) | | Wel | l Diameter: (| circle one) | 2 3 🚯 6 | | | | |
| Total We | 11 Depth: | | Dep | th to Water: | | | | | | |
| Before 2 | 29.38 A | fter | Bef | ore 13.00 | After | | | | | |
| Depth to | Free Produ | ct: | Thi | ckness of Fre | e Product (| feet): | | | | |
| Measurem | ents refere | nced to: | (FVC) | Grade | Other: | | | | | |
| | Well Diamet 1" 2" 3" 4" 5" | er | VCF 0.04 0.16 0.65 1.02 | Well Diamet 6" 8" 10" 12" 16" | er | VCF 1.47 2.61 4.08 5.87 10.43 | | | | |
| 10. | 6 | x | 3 | | 31- | 8 | | | | |
| 1 Case | Volume | - | Specified Vo | olumes = | gallons | | | | | |
| Purging: Bailer Disposable Bailer Middleburg Electric Submersible Extraction Pump Other Sampling: Bailer Disposable Bailer Extraction Port Other | | | | | | | | | | |
| TIME 1145 | TEMP. | рн | COND. | TURBIDITY: | VOLUME REMOVED: | OBSERVATIONS: | | | | |
| 1146 | 66-2 | 6.7 | 570 | 146- | 10-0 | | | | | |
| 1147 | 66.6 | 6.5 | 490 | <i>15</i> 3. | 20.0 | | | | | |
| 1149 | 66.0 | 6.4 | 490 | 92. | 35.0 | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| Did Well | Dewater? 1 | If yes | , gals. | Gallons A | Actually Eva | acuated: 35.0 | | | | |
| Sampling | Time: 1155 | 5 | Samp | oling Date: | -26 -95 | | | | | |
| Sample I. | D.: MW | 1 | Labo | oratory: | ET | | | | | |
| Analyzed for: PH-C BTEX TPH-D OTHER: | | | | | | | | | | |
| Duplicate | I.D.; | | Clea | ning Blank I. | .D.: | | | | | |
| Analyzed (Circle) | for: TPH-0 | BTEX | TPH-D OTH | ER: | | | | | | |

| Project #: 950626-PM Wic #: 204 5508 0703 | | | | | | | | | | | |
|--|---|-------|---|---------------------------------------|--------------------|--|--|--|--|--|--|
| Sampler | : RU | | Sta | ert Date: 6 - | 26-95 | | | | | | |
| Well I.I | o.: Mw. | -7 | | l Diameter: (| | | | | | | |
| 1 | ell Depth: | | Dep | th to Water: | | | | | | | |
| Before 27.85 After Before 14.65 After | | | | | | | | | | | |
| Depth to Free Product: Thickness of Free Product (feet): | | | | | | | | | | | |
| Measurements referenced to: PVC Grade Other: | | | | | | | | | | | |
| | Well Diamet 2" 3" 4" 5" | er | VCF 0.04 0.16 0.37 0.65 1.02 | Well Diamet 8" 10" 12" 16" | er | VCF 1.47 2.61 4.08 5.87 10.43 | | | | | |
| 8. | 6 | x | 3 | · · · · · · · · · · · · · · · · · · · | 25 | · 8 | | | | | |
| $ \begin{array}{c ccccccccccccccccccccccccccccccccccc$ | | | | | | | | | | | |
| Purging: Bailer Sampling: Bailer Disposable Bailer Disposable Bailer Extraction Port Other Other | | | | | | | | | | | |
| TIME | TEMP. (F) | рн | COND. | TURBIDITY: | VOLUME REMOVED: | OBSERVATIONS: | | | | | |
| 1118 | 686 | 6.9 | 860 | 7200 | 10.0 | | | | | | |
| 1119 | 67.4 | 6.1 | 700 | 7200 | 20-0 | | | | | | |
| 1120 | 68.0 | 6.1 | 690 | 7200 | 30.0 | | | | | | |
| | - | | · | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | , | | | | | |
| Did Well | Dewater? | If ye | s, gals. | Gallons 1 | Actually Eva | acuated: 30 | | | | | |
| Sampling Time: 1130 Sampling Date: 6-26-95 | | | | | | | | | | | |
| Sample I.D.: MW-Z Laboratory: NET | | | | | | | | | | | |
| Analyzed for: TPH-G BTEX TPH-D OTHER: | | | | | | | | | | | |
| Duplicat | Duplicate I.D.: Cleaning Blank I.D.: FRO 113C | | | | | | | | | | |
| Analyzed for: TPH-C STEX TPH-D OTHER: (Circle) | | | | | | | | | | | |

| Project | #.0-010 | | Wic | # . 30.04 | | 0 | | | | | | |
|---|---|---------------|--------------------------------------|--|-----------------------------------|--|--|--|--|--|--|--|
| | #:950626 | o- A1 | | #: 204 55 | | 10 | | | | | | |
| Sampler: | EU . | | | rt Date: 6- | | | | | | | | |
| Well I.D | Well I.D.: NU-> Well Diameter: (circle one) 2 3 4 6 | | | | | | | | | | | |
| Total Well Depth: Depth to Water: | | | | | | | | | | | | |
| Before 28.10 After Before 13.79 After | | | | | | | | | | | | |
| Depth to Free Product: Thickness of Free Product (feet): | | | | | | | | | | | | |
| Measurements referenced to: PVC Grade Other: | | | | | | | | | | | | |
| | Well Diamet 1" 2" 3" 4" 5" | êr | VCF 0.04 0.137 0.65 1.02 | Well Diamet 6" 8" 10" 12" 16" | er | VCF 1.47 2.61 4.08 5.87 10.43 | | | | | | |
| | 7-3 | х | . 3 |) | 27 | 9 | | | | | | |
| · · | Volume | - •• . | Specified V | olumes = | gallons | | | | | | | |
| Purging: Bailer Disposable Bailer Middleburg Electric Submersible Extraction Pump Sampling: Bailer Disposable Bailer Extraction Port Other | | | | | | | | | | | | |
| 1 | Other | | | — · i ———— | | | | | | | | |
| 17.0% | TEMP. (F) | PH | COND. | TURBIDITY: | VOLUME REMOVED: | OBSERVATIONS: | | | | | | |
| 1206 | 67.2 | 6-4 | 530 | 190. | 10.0 | | | | | | | |
| 1207 | 67.6 | 6.2 | 520 | 181. | 20.0 | | | | | | | |
| 1208 | 68.0 | 6-2 | 520 | 189. | 30.0 | | | | | | | |
| | | | | | | | | | | | | |
| | | [| | | | | | | | | | |
| | | | | | · · · · · · · · · · · · · · · · · | | | | | | | |
| Did Well | Dewater? |) If ye | s, gals. | Gallons A | Actually Ev | acuated: 30.0 | | | | | | |
| Sampling | Time: 12/5 | | Samp | oling Date: 6 | | - | | | | | | |
| Sample I | D.: MW | 3 | | oratory: VE | <u>-0 ()</u> | | | | | | | |
| Analyzed for: TPH-C BTEX TPH-D OTHER: | | | | | | | | | | | | |
| Duplicate | ≥ I.D.: | | Clea | ening Blank I. | D.: | | | | | | | |
| Analyzed (Circle) | for: TPH- | G BTEX | TPH-D OTI | HER: | | | | | | | | |

| Project #: 950626-A1 Wic #: 204-5508-0703 | | | | | | | | | | |
|--|-------------------------------------|----------|-------------------------------------|---|--------------------|--|--|--|--|--|
| Sampler: | RV | | | rt Date: | | | | | | |
| Well I.D. | · mw- | -4 | Wel | l Diameter: (| circle one) | 2 3 4 6 | | | | |
| Total Wel | l Depth: | | Dep | th to Water: | | | | | | |
| Before 2 | 3.98 A | fter | Bef | ore 13.26 | After | • | | | | |
| Depth to Free Product: Thickness of Free Product (feet): | | | | | | | | | | |
| Measureme | nts refere | nced to: | PVC | Grade | Other: | | | | | |
| W | ell Diameto 2" 3" 4" 5" | er | VCF 0.14 0.15 0.35 1.02 | Well Diamete 8" 10" 12" 16" | er | VCF 1.47 2.61 4.08 5.87 10.43 | | | | |
| 6.9 | 1 | x | ~ | | 20. | 7 | | | | |
| 1 Case | · | - ^ - | Specified Vo | olumes = | gallons | | | | | |
| Purging: Bailer Disposable Bailer Middleburg Electric Submersible Extraction Fump Other | | | | | | | | | | |
| TIME (2.2.5 | TEMP. (F) | рн | COND. | TURBIDITY: | VOLUME REMOVED: | OBSERVATIONS: | | | | |
| 1726 | 66.8 | 6.4 | 610 | 7200 | 100 | | | | | |
| 1227 | 66.8 | 6.2 | 650 | 150. | 20.0 | | | | | |
| 1228 | 66.6 | 6-2 | 660 | 75. | 25,0 | | | | | |
| | | | | · · | | | | | | |
| Did Well I | Dewater? N | If yes | gals. | Gallons A | Actually Eva | acuated: 25.6 | | | | |
| Sampling S | | | Samp | oling Date: | 5-76-95 | _ | | | | |
| Sample I.I | o.: NW | 4 | Labo | ratory: NE | | | | | | |
| Analyzed for: TPH-G PTEX TPH-D OTHER: | | | | | | | | | | |
| Duplicate | I.D.: | 1235 | Clea | ning Blank I. | D.: | | | | | |
| Analyzed in (Circle) | For: TPH-G | BTEX | TPH-D OTH | ER: | | | | | | |