



# GETTLER-RYAN INC.

ENVIRONMENTAL  
PROTECTION

00 JAN 12 PM 3:53

## TRANSMITTAL

TO: Mr. Brett Hunter  
Chevron Products Company  
P.O. Box 6004  
San Ramon, CA 94583

DATE: January 10, 2000  
PROJECT #: 346461.05-1

SUBJECT: Work Plan for Monitoring Well  
Installation for Former  
Chevron Service Station #9-  
8139.

FROM:  
Barbara Sieminski  
Project Geologist  
Gettler-Ryan Inc.  
6747 Sierra Court, Suite G  
Dublin, California 94568

### WE ARE SENDING YOU:

COPIES	DATED	DESCRIPTION
1	01/10/00	Work Plan for Monitoring Well Installation at Former Chevron Service Station #9-8139, 16304 Foothill Boulevard, San Leandro, California.

THESE ARE TRANSMITTED as checked below:

- For review and comment     Approved as submitted     Resubmit \_\_ copies for approval
- As requested     Approved as noted     Submit \_\_ copies for distribution
- For approval     Return for corrections     Return \_\_ corrected prints
- For your files

cc: Mr. Chuck Headlee, RWQCB San Francisco Bay Region (certified mail)  
Mr. Scott Seery, Alameda County Health Care Services Agency (certified mail)  
Mr. Harv Dhaliwal, G&S Associates, Inc. (certified mail)  
Ms. Betty Owen, Chevron Products Company  
Mr. Greg Gurss, Gettler-Ryan Inc.  
GR File

COMMENTS: Attached is a copy of the final work plan for your use. Copies of this work plan have been submitted to the above listed parties. Please call if you have questions.



# GETTLER-RYAN INC.

## WORK PLAN FOR MONITORING WELL INSTALLATION

at

Former Chevron Service Station #9-8139  
16304 Foothill Boulevard  
San Leandro, California

Report No. 346461.05-1

**Prepared for:**

Mr. Brett Hunter  
Chevron Products Company  
P.O. Box 6004  
San Ramon, California 94583

**Prepared by:**

Gettler-Ryan Inc.  
6747 Sierra Court, Suite G  
Dublin, California 94568

*Barbara Sieminski*

Barbara Sieminski  
Project Geologist  
R.G. 6676



*Stephen J. Carter*

Stephen J. Carter  
Senior Geologist  
R.G. 5577

January 6, 2000

## TABLE OF CONTENTS

<b>INTRODUCTION</b> .....	1
<b>SITE DESCRIPTION</b> .....	1
General .....	1
Geology and Hydrogeology .....	2
Previous Work .....	2
<b>PROPOSED SCOPE OF WORK</b> .....	2
Task 1. Pre-Field Activities .....	3
Task 2. Well Installation .....	3
Task 3. Wellhead Survey .....	3
Task 4. Well Development and Sampling .....	4
Task 5. Laboratory Analyses .....	4
Task 6. Report Preparation .....	4
<b>PROJECT STAFF</b> .....	4
<b>SCHEDULE</b> .....	4

### FIGURES

Figure 1.	Vicinity Map
Figure 2.	Site Plan
Figure 3.	Well Construction Detail

### APPENDICES

Appendix A:	GR Field Methods and Procedures
-------------	---------------------------------



# GETTLER-RYAN INC.

---

## WORK PLAN FOR MONITORING WELL INSTALLATION

at

Former Chevron Service Station #9-8139  
16304 Foothill Boulevard  
San Leandro, California

Report No. 6461.05-1

### INTRODUCTION

At the request of Chevron Products Company (Chevron), Gettler-Ryan Inc. (GR), has prepared this Work Plan for the installation of one groundwater monitoring well to further evaluate soil and groundwater conditions at the subject site and to collect additional data for the risk-based corrective action (RBCA) evaluation. The proposed work includes: preparing the site safety plan; obtaining the required well installation permit; installing one on-site groundwater monitoring well; surveying the wellhead elevation; developing and sampling the newly installed well; collecting and submitting selected soil and groundwater samples for laboratory analysis; arranging for Chevron's contractor to dispose of the waste materials; and preparing a report presenting the observations associated with the well installation. This work was requested by the Alameda County Health Care Services Agency (ACHCSA) in their letters dated October 15, 1998, and June 28, 1999.

The scope of work proposed in this Work Plan is intended to comply with the State of California Water Resources Control Board's *Leaking Underground Fuel Tanks (LUFT) Manual* and *California Underground Storage Tank Regulations, 1994*, the Regional Water Quality Control Board's (RWQCB) *Tri-Regional Board Staff Recommendations for Preliminary Investigation and Evaluation of Underground Tank Sites*, and the ACHCSA guidelines.

### SITE DESCRIPTION

#### General

The subject site is located on the eastern side of Foothill Boulevard approximately 0.1 mile south of Strang Avenue in San Leandro, California (Figure 1). The site is a Chevron service station currently redeveloped into a mini-market/gas station facility. The previous Chevron station facilities consisted of a station building, three gasoline underground storage tanks (USTs) and two dispenser islands. All previous Chevron station aboveground and underground facilities have been removed prior to the site reconstruction. A current site configuration includes a mini-market building located in the eastern corner of the site, two new gasoline USTs that share a common pit southwest of the mini-market building and service islands located in the central portion of the site. Pertinent former and current site features are shown on Figure 2.

## **Geology and Hydrogeology**

The subject site is located at the western edge of San Leandro Hills approximately 4 miles east of San Francisco Bay and approximately 1 ¼ mile south of Lake Chabot. The site is a relatively flat lot at an elevation of approximately 125 feet above mean sea level. Based on the boring logs from previous environmental investigations, the subject site is underlain by sandy clay with clayey and gravelly sand interbeds to the total depth explored of 41.5 feet below ground surface (bgs). Groundwater was encountered in the borings at depths ranging from 17 to 26 feet bgs and stabilized at depths ranging from 12 to 19 feet bgs. Based on the historical groundwater monitoring data, groundwater in the vicinity of the subject site flows to the south. Between December 1989 and April 1990, the groundwater depth has fluctuated between 8.5 and 22.5 feet. The nearest surface water is San Lorenzo Creek located approximately 1 mile south of the subject site.

## **Previous Work**

Eleven groundwater monitoring wells (on-site wells MW-1 through MW-7 and off-site wells MW-8 through MW-11) were installed at the subject site between 1989 and 1992 to monitor groundwater condition beneath the site and in its downgradient (southern) vicinity. Groundwater extraction well EW-1 was installed at the site in 1990 for groundwater remediation. In 1991, groundwater monitoring wells MW-5 and MW-4 were destroyed and extraction wells EW-2 and EW-3 were installed in the locations of the destroyed wells, respectively, to add in groundwater remediation. In 1998, on-site wells MW-1, MW-2, MW-3, MW-6, MW-7, and EW-1 were destroyed, prior to the site redevelopment. Extraction wells EW-2 and EW-3 were retained for future use as monitoring wells.

Groundwater at the subject site has been monitored and sampled since December 1989. Historical sampling data indicate that on-site wells MW-3, MW-4/EW-3, MW-5/EW-2, and EW-1 have contained total petroleum hydrocarbons as gasoline (TPHg), benzene and methyl tertiary butyl ether (MtBE) at concentrations up to 51,000 parts per billion (ppb), 12,000 ppb and 13,000 ppb, respectively. Floating product (up to 1.3 feet) was present in well MW-5 between September 1990 and May 1991. Off-site wells MW-8 and MW-9 have contained TPHg, benzene, and MtBE at concentrations up to 17,000 ppb, 470 ppb, and 5,000 ppb, respectively. On-site wells MW-1, MW-2, MW-6, MW-7 and off-site wells MW-10 and MW-11 have never contained MtBE. Benzene was detected in these wells only on few occasions at low concentrations (up to 19 ppb). TPHg has never been detected in wells MW-6, MW-10 and MW-11, and has been detected sporadically at low concentrations (up to 100 ppb) in wells MW-1, MW-2 and MW-7.

## **PROPOSED SCOPE OF WORK**

GR proposes to install one on-site groundwater monitoring well (MW-12) to further assess soil and groundwater conditions at the subject site and to collect additional data for RBCA evaluation. GR Field Methods and Procedures are included in Appendix A. To implement this scope of work, GR proposes the following six specific tasks:

**Task 1. Pre-Field Activities**

Prepare the site-specific safety plan, and obtain the necessary well installation permit from the Alameda County Public Works Agency. Notify Underground Service Alert (USA) a minimum of 48 hours prior to drilling. Contract with a private utility locator to clean boring locations.

**Task 2. Well Installation**

Install groundwater monitoring well MW-12 in the location shown on Figure 2. Drilling and well construction activities will be performed by Bay Area Exploration Inc. (C57 #522125). A GR geologist will observe drilling, collect soil samples for chemical and physical analyses, describe the encountered soil, and prepare a log of the boring. The well boring will be advanced using 8-inch-diameter hollow-stem augers and truck-mounted drill rig.

Groundwater monitoring well MW-12 will be constructed of 2-inch-diameter Schedule 40 polyvinyl chloride (PVC) well casing and 0.01-inch machine slotted PVC well screen. The screened interval will extend from approximately 5 feet bgs to 25 feet bgs. Proposed Well Construction Details are shown on Figure 3.

Soil from each sampled interval will be screened in the field for the presence of volatile organic compounds using a photoionization detector (PID). These data will be collected for reconnaissance purposes only, and will not be used as verification of the presence or absence of petroleum hydrocarbons. Screening data will be recorded on the boring log.

Soil samples for description and possible chemical and physical analysis will be obtained from the borings at five-foot intervals, as a minimum. Although the actual number of samples submitted for analysis will depend on site conditions and field screening data, we anticipate a minimum of one unsaturated and one saturated soil sample from the boring will be submitted for analysis as described in Task 5.

Drill cuttings will be stockpiled at the site pending disposal. Stockpiled cuttings will be placed on and covered with plastic sheeting. Four soil samples from the drill cuttings will be collected for disposal characterization as described in Appendix A. These samples will be submitted to the laboratory for compositing into one sample, then analyzed as described in Task 5. Drill cuttings will be disposed of by Integrated Wastestream Management Inc. (IWM).

**Task 3. Wellhead Survey**

Following installation, the top of casing for well MW-12 will be surveyed to mean sea level by a California-licensed surveyor. Wellhead elevations for wells EW-2 and EW-3 will be also surveyed at that time. Horizontal coordinates of wells location will be obtained at the same time.

**Task 4. Well Development and Sampling**

Newly installed groundwater monitoring well MW-12 will be developed after being allowed to stand a minimum of 72 hours following installation. Well MW-12 will be sampled after development and subsequently monitored and sampled by Blaine Tech Services, Inc. Rinsate water and groundwater purged from the well during development and sampling will be transported by IWM to McKittrick Waste Management. The groundwater samples will be analyzed as described in Task 5.

**Task 5. Laboratory Analyses**

All samples will be submitted to a California-certified Hazardous Materials Testing Laboratory. Soil and groundwater samples will be analyzed for TPHg, BTEX, and MTBE by EPA Methods 5030/8015/8020. In addition, one saturated and one unsaturated soil sample will be analyzed for fraction organic carbon, porosity, and dry, natural, and matrix densities. The unsaturated soil sample will also be analyzed for moisture content. Disposal characterization samples from the soil stockpile will be analyzed for TPHg and BTEX.

**Task 6. Report Preparation**



Following receipt and analysis of all data, a report will be prepared which summarizes the procedures and the results associated with this well installation. This report will be submitted to Chevron for their use and distribution.

**PROJECT STAFF**

Ms. Barbara Sieminski, a Registered Geologist in the State of California (R.G. No. 6676), will provide technical oversight and review of the work. Mr. Greg Gurss, Project Manager, will supervise and direct field and office operations. GR employs a staff of geologist, engineers, and technicians who will assist with the project.

**SCHEDULE**

Implementation of the proposed scope of work will commence upon receipt of regulatory approval and a well installation permit.



Base Map: USGS Topographic Map



**Gottler - Ryan Inc.**

6747 Sierra Ct., Suite J (925) 551-7555  
Dublin, CA 94568

VICINITY MAP  
Chevron Service Station No. 9-8139  
16304 Foothill Boulevard  
San Leandro, California

FIGURE 1


JOB NUMBER  
346461

REVIEWED BY

DATE  
01/00

REVISED DATE





**Gettler - Ryan Inc.**

6747 Sierra Ct., Suite J (925) 551-7555  
Dublin, CA 94568

**SITE PLAN**

Chevron Service Station No. 9-8139  
16304 Foothill Boulevard  
San Leandro, California

FIGURE

**2**


JOB NUMBER  
346461.05

REVIEWED BY  
*[Signature]*

DATE  
11/99

REVISED DATE

# WELL CONSTRUCTION DETAIL



- A Total Depth Of Boring \_\_\_\_\_ 25 \_\_\_\_\_ ft.
- B Diameter Of Boring \_\_\_\_\_ 8 \_\_\_\_\_ in.  
Drilling Method Hollow-stem Auger
- C Top Of Box Elevation \_\_\_\_\_ ft.  
 Referenced To Mean Sea Level  
 Referenced To Project Datum
- D Casing Length \_\_\_\_\_ 25 \_\_\_\_\_ ft.  
Material Schedule 40 PVC
- E Casing Diameter \_\_\_\_\_ 2 \_\_\_\_\_ in.
- F Depth To Top Perforations \_\_\_\_\_ 5 \_\_\_\_\_ ft.
- G Perforated Length \_\_\_\_\_ 20 \_\_\_\_\_ ft.  
Perforated Interval From 5 to 25 ft.  
Perforation Type machine slot  
Perforation Size \_\_\_\_\_ 0.01 \_\_\_\_\_ in.
- H Surface Seal From \_\_\_\_\_ 0 \_\_\_\_\_ to \_\_\_\_\_ 1 \_\_\_\_\_ ft.  
Seal Material concrete
- I Backfill From \_\_\_\_\_ 1 \_\_\_\_\_ to \_\_\_\_\_ 3 \_\_\_\_\_ ft.  
Backfill Material neat cement
- J Seal From \_\_\_\_\_ 3 \_\_\_\_\_ to \_\_\_\_\_ 4 \_\_\_\_\_ ft.  
Seal Material bentonite
- K Gravel Pack From \_\_\_\_\_ 4 \_\_\_\_\_ to \_\_\_\_\_ 25 \_\_\_\_\_ ft.  
Pack Material Lonestar #2/12
- L Bottom Seal None \_\_\_\_\_ ft.  
Seal Material \_\_\_\_\_
- M Vault box with waterproof  
locking cap and lock

PROPOSED MONITORING WELL  
Former Chevron Service Station  
#9-8139  
16304 Foothill Boulevard  
San Leandro, California

Note: Depths Measured From Initial Ground Surface.



**Gettler - Ryan Inc.**

3164 Gold Camp Drive, Suite 240  
Rancho Cordova, CA 95670

JOB NUMBER  
346461.05

REVIEWED BY  
*[Signature]*

DATE  
11/99

REVISION DATE

Figure 3

**APPENDIX A**

**GR FIELD METHODS AND PROCEDURES**

## **GETTLER - RYAN FIELD METHODS AND PROCEDURES**

### **Site Safety Plan**

Field work performed by Gettler-Ryan, Inc. (GR) is conducted in accordance with GR's Health and Safety Plan and the Site Safety Plan. GR personnel and subcontractors who perform work at the site are briefed on the contents of these plans prior to initiating site work. The GR geologist or engineer at the site when the work is performed acts as the Site Safety Officer. GR utilizes a photoionization detector (PID) to monitor ambient conditions as part of the Health and Safety Plan.

### **Collection of Soil Samples**

Exploratory soil borings are drilled by a California-licensed well driller. A GR geologist is present to observe the drilling, collect soil samples for description, physical testing, and chemical analysis, and prepare a log of the exploratory soil boring. Soil samples are collected from the exploratory soil boring with a split-barrel sampler or other appropriate sampling device fitted with clean brass or stainless steel liners. The sampling device is driven approximately 18 inches with a 140-pound hammer falling 30 inches. The number of blows required to advance the sampler each successive 6 inches is recorded on the boring log. The encountered soil is described using the Unified Soil Classification System (ASTM 2488-84) and the Munsell Soil Color Chart.

After removal from the sampling device, soil samples for chemical analysis are covered on both ends with teflon sheeting or aluminum foil, capped, labeled, and placed in a cooler with blue ice for preservation. A chain-of-custody form is initiated in the field and accompanies the selected soil samples to the analytical laboratory. Samples are selected for chemical analysis based on:

- a. depth relative to underground storage tanks and existing ground surface
- b. depth relative to known or suspected groundwater
- c. presence or absence of contaminant migration pathways
- d. presence or absence of discoloration or staining
- e. presence or absence of obvious gasoline hydrocarbon odors
- f. presence or absence of organic vapors detected by headspace analysis

### **Field Screening of Soil Samples**

A PID is used to perform head-space analysis in the field for the presence of organic vapors from the soil sample. This test procedure involves removing some soil from one of the sample tubes not retained for chemical analysis and immediately covering the end of the tube with a plastic cap. The PID probe is inserted into the headspace inside the tube through a hole in the plastic cap. Head-space screening results are recorded on the boring log. Head-space screening procedures are performed and results recorded as reconnaissance data. GR does not consider field screening techniques to be verification of the presence or absence of hydrocarbons.

### **Stockpile Sampling**

Stockpile samples consist of four individual sample liners collected from each 100 cubic yards (yd<sup>3</sup>) of stockpiled soil material. Four arbitrary points on the stockpiled material are chosen, and discrete soil sample is collected at each of these points. Each discrete stockpile sample is collected by removing the upper 3 to 6 inches of soil, and then driving the stainless steel or brass tube into the stockpiled material with a wooden mallet or hand driven soil sampling device. The sample tubes are then covered on both ends with teflon sheeting or aluminum foil, capped, labeled, placed in the

cooler with blue ice for preservation. A chain-of-custody form is initiated in the field and accompanies the selected soil samples to the analytical laboratory. Stockpiled soils are covered with plastic sheeting after completion of sampling.

### **Construction of Monitoring Wells**

Monitoring wells are constructed in the exploratory borings with Schedule 40 polyvinyl Chloride (PVC) casing. All joints are thread-joined; no glues, cements, or solvents are used in well construction. The screened interval is constructed of machine-slotted PVC well screen which generally extends from the total well depth to a point above the groundwater. An appropriately-sized sorted sand is placed in the annular space adjacent to the entire screened interval. A bentonite transition seal is placed in the annular space above the sand, and the remaining annular space is sealed with neat cement or cement grout.

Wellheads are protected with water-resistant traffic rated vault boxes placed flush with the ground surface. The top of the well casing is sealed with a locking cap. A lock is placed on the well cap to prevent vandalism and unintentional introduction of materials into the well.

### **Storing and Sampling of Drill Cuttings**

Drill cuttings are stockpiled on plastic sheeting or stored in drums depending on site conditions and regulatory requirements. Stockpile samples are collected and analyzed on the basis of one composite sample per 50 cubic yards of soil. Stockpile samples are composed of four discrete soil samples, each collected from an arbitrary location on the stockpile. The four discrete samples are then composited in the laboratory prior to analysis.

Each discrete stockpile sample is collected by removing the upper 3 to 6 inches of soil, and then driving the stainless or brass sample tube into the stockpiled material with a hand, mallet, or drive sampler. The sample tubes are then covered on both ends with teflon sheeting or aluminum foil, capped, labeled, and placed in a cooler with blue ice for preservation. A chain-of-custody form is initiated in the field and accompanies the selected soil samples to the analytical laboratory. Stockpiled soils are covered with plastic sheeting after completion of sampling.

### **Wellhead Survey**

The top of the newly-installed well casing is surveyed by a California-licensed Land Surveyor to mean sea level (MSL).

### **Well Development**

The purpose of well development is to improve hydraulic communication between the well and surrounding aquifer. Prior to development, each well is monitored for the presence of separate-phase hydrocarbons and the depth-to-water is recorded. Wells are then developed by alternately surging the well with the bailer, then purging the well with a pump to remove accumulated sediments and draw groundwater into the well. Development continues until the groundwater parameters (temperature, pH, and conductivity) have stabilized.