

9838 Old Placerville Road Suite 100 Sacramento, CA 95827-3559 916/369-8971 FAX 916/369-8370

3-29-95

FOURTH QUARTER 1994 GROUND WATER MONITORING REPORT

Southern Pacific Transportation Company 5th Avenue and 7th Street Oakland, California

IC Project No. 05100269

Prepared For:

Southern Pacific Transportation Company One Market Plaza San Francisco, CA 94105

March 29, 1995





9838 Old Placerville Road Suite 100 Sacramento, CA 95827-3559 916/369-8971 FAX 916/369-8370

March 29, 1995

IC Project No. 05100269

Ms. Jennifer Eberle
Alameda County Health Care Services Agency
Department of Environmental Health
Division of Hazardous Materials
1131 Harbor Bay Parkway
Alameda, California 94502

VIA REGULAR MAIL

Re: Fourth Quarter 1994 Ground Water Monitoring Report

Southern Pacific Transportation Company

5th Avenue and 7th Street Property - Oakland, California

Dear Ms. Eberle:

Industrial Compliance (IC), on behalf of Southern Pacific Transportation Company (SPTCo), has prepared the attached Fourth Quarter 1994 Ground Water Monitoring Report for the SPTCo property located in the East Oakland Yard at 5th Avenue and 7th Street, Oakland, California.

If you should have any questions regarding this report, please contact either of the undersigned at your earliest convenience at (510) 238-9540 or (916) 369-8971.

Sincerely,

INDUSTRIAL COMPLIANCE

James B. Ackerman

Project Geologist

Richard L. Bateman, R.G. Principal Hydrogeologist

JBA/RLB/ekw

Attachment

cc: Mr. Mike Grant, Southern Pacific Transportation Company (with attachment)

Mr. Darrell J. Maxey, Oakland Program Office, Southern Pacific Transportation

Company (with attachment)

Ms. Gina Kathuria, California Regional Water Quality Control Board. San Francisco

Region (with attachment)

1880-251 LTR:03-29-95 G .KEYDATA I-880 LETTERS

FOURTH QUARTER 1994 GROUND WATER MONITORING REPORT

Southern Pacific Transportation Company
5th Avenue and 7th Street
Oakland, California

Prepared By:

James B. Ackerman Project Geologist

Reviewed By:

Richard L. Bateman Principal Hydrogeologist

TABLE OF CONTENTS

1.0	INTRODUCTION 1
2.0	BACKGROUND 4
3.0	FIELD INVESTIGATION
	3.1Monitoring Well Water Level Data73.2Monitoring Well Purging73.3Monitoring Well Sampling103.4Quality Assurance/Quality Control12
4.0	ANALYTICAL RESULTS
5.0	DISCUSSION
6.0	GLOSSARY OF ACRONYMS 20
	FIGURES
Figure Figure Figure	Site Layout Map
Figure Figure	5 Chemical Distribution Map for Constituents in Ground Water Samples,
Figure	November, 1994
	TABLES
Table : Table : Table : Table :	Ground Water Purge Characterization Data, November, 1994




TABLE OF CONTENTS (continued)

APPENDICES

Appendix A	Purge Characterization and Sample Log Field Data Sheets
Appendix B	Chain-of-Custody Document
Appendix C	Analytical Laboratory Reports, Ground Water Samples
Appendix D	Ground Water Elevation Contour Maps, Previous Monitoring Events

1.0 INTRODUCTION

Industrial Compliance (IC) on behalf of Southern Pacific Transportation Company (SPTCo), is conducting quarterly ground water monitoring at the SPTCo property located on a portion of the East Oakland Yard at 5th Avenue and 7th Street in Oakland, California (Figure 1). The site was formerly the location of four underground fuel storage tanks (Figure 2). Fourth quarter monitoring and sampling activities were performed on November 9 and 10, 1994. This report presents the results of that monitoring event.



Reference Map of Oakland, Berkeley, Alameda American Automobile Association



05100269

Patti Decker

Project No

Drawn By

Industrial Compliance

Checked James Ackerman

A Subsidiary of SP Environmental Systems Inc




12/01/94

SOUTHERN PACIFIC TRANSPORTATION COMPANY 5TH AVENUE AND 7TH STREET PROPERTY OAKLAND, CALIFORNIA

SITE LOCATION MAP

Ek∂nte
1
Page No
2
Scale
as shown




2.0 BACKGROUND

In February, 1989, Canonie Environmental Services Corporation (Canonie) prepared to remove four underground storage tanks (USTs) from the site: two 7,000-gallon diesel USTs (which Canonie referred to as Tanks A and B) and two 7,000-gallon Bunker "C" oil USTs (which Canonie referred to as Tanks C and D). Prior to removal of the USTs, Canonie collected four subsurface soil samples from borings adjacent to the perimeter of the USTs (Figure 3). This preliminary collection of samples was required by Alameda County Health Care Services Agency - Department of Environmental Health, Division of Hazardous Materials (Alameda County) to verify that Canonie's tank removal activities would not further impact the site. Laboratory analyses performed on these soil samples indicated a maximum concentration of total extractable petroleum hydrocarbons (TEPH) of 16,000 parts per million (ppm). The results of these sampling activities were summarized in a Canonie letter report dated February 15, 1989 (letter report entitled: Soil Sampling Report and Records of Correspondence with Regulatory Agencies, Southern Pacific Transportation Company Railyard, Fifth Avenue and Seventh Street, Oakland, California).

On February 20, 1989, Canonie began the excavation and removal of the four USTs. Soil was removed from the excavation to a depth of approximately 12 feet below ground surface (bgs). According to the Canonie report, no water entered the excavation in the three days that it remained open. According to the Canonie report, soil in the excavation did not appear impacted (by visual observation). Canonie reported approximately 500 cubic yards (cy) of soil was generated from the UST excavation and was stockpiled on plastic sheeting onsite.

Prior to backfilling the excavation, a total of 12 soil samples were collected from the excavation. Six soil samples were taken from the bottom of the excavation at a depth of 12 feet bgs and six soil samples were taken from 2 feet below the bottom of the excavation (or at 14 feet bgs). Laboratory analyses performed on the soil samples collected at 12 feet bgs





identified maximum concentrations of 12 ppm of TEPH and 43 ppm of total recoverable petroleum hydrocarbons (TRPH). The six samples at 12 feet bgs were composited into two samples and analyzed for polychlorinated biphenyls (PCBs). Laboratory analysis did not detect PCBs at or above the method practical quantitation limit. The excavation was backfilled with clean imported fill material. The procedures and results of this work were presented in a Canonie report dated April 3, 1989 (report entitled: Completion Report, Underground Storage Tank Removal, Southern Pacific Transportation Company Facility, Oakland, California).

At the request of Alameda County, IC conducted a preliminary site assessment at the site in April, 1994. A total of three soil borings were drilled at the site, which were then converted to monitoring wells (MW-1, MW-2, and MW-3) (Figure 3). Because of restricted access (due to utility lines and railroad tracks), the locations for two of the monitoring wells (MW-2 and MW-3) were moved in a westerly direction from their previously approved location. After a period of approximately nine days these wells were developed, and subsequently sampled six days thereafter. The procedures and results of this work were presented in an IC report dated September 2, 1994 (report entitled: *Soil and Ground Water Investigation Report, Southern Pacific Transportation Company, 5th Avenue and 7th Street, Oakland, California*).

In August of 1994, IC initiated quarterly ground water monitoring and sampling activities with the monitoring wells installed during the April 1994 field activities. The results of the fourth quarter, 1994 sampling event are presented in this report.

3.0 FIELD INVESTIGATION

This section discusses the procedures and protocol used for the collection of monitoring well water level data and ground water samples for laboratory analyses.

3.1 Monitoring Well Water Level Data

On November 9, 1994, prior to purging, the depth to ground water was measured in all wells (MW-1, MW-2, and MW-3). All measurements were taken from the top of casing (which had been surveyed by a licensed surveyor relative to mean sea level [MSL]) using a water level indicator with an accuracy to 0.01 feet. Ground water elevations this quarter ranged from 5.14 to 6.12 feet above MSL. Ground water elevation data are summarized in Table 1. Ground water elevation data were used to construct a ground water elevation contour map (Figure 4). Ground water flow is in a southerly direction. The calculated local hydraulic gradient is 0.013 feet per foot.

3.2 Monitoring Well Purging


After measurement of the ground water level in each well, the saturated well volume was calculated by subtracting the depth to ground water from the total depth of the well and multiplying the resultant length by the number of gallons per foot of casing. Prior to sample collection, each well was purged to ensure that the water sample obtained from the well was representative of the formation water. Each well was purged by hand-bailing a minimum of three times the saturated casing volume in the well, or until the well was bailed dry (which was the case for well MW-3). Purging equipment was cleaned with Alconox and rinsed with deionized (DI) water prior to each use. Ground water characterization data, consisting of electrical conductivity, temperature and pH, were measured from the initial water removed and at least three times during purging. The ground water in each well was assumed to be



TABLE 1 GROUND WATER ELEVATION DATA NOVEMBER, 1994

Monitoring Well ^a	Date Measured	Time Measured	Reference Elevation ^b (feet MSL)	Depth to Ground Water ^c (feet TOC)	Ground Water Elevation ^d (feet MSL)
MW -1	11/09/94	0755	8.20	2.08	6.12
MW-2	11/09/94	0815	6.36	1.22	5.14
MW-3	11/09/94	0810	6.84	1.10	5.74

- a See Figure 3 for approximate location of monitoring wells.
- b Reference casing elevation is a point marked on the top of the well casing, which has been measured by a licensed surveyor.
- c Depth to ground water measured from top of casing (TOC).
- d Ground water elevation calculated by subtracting the depth to ground water from the reference casing elevation.
- MSL Mean sea level
- TOC Top of casing



representative of the formation when a minimum of three well volumes had been removed and consecutive parameter readings were within 10 percent (unless dewatering occurred). After purging was complete, each well was allowed to recover to at least 90 percent of the original water level. Due to the slow recharge rate, well MW-3 was bailed dry and subsequently sampled before recovering to 90 percent of the pre-purge water level. Monitoring well ground water purge characterization parameters are summarized in Table 2. Monitoring well purge characterization and sample log field data sheets are included in Appendix A.

3.3 Monitoring Well Sampling

Ground water samples were collected using new, disposable polyethylene bailers. The water samples from the bailers were transferred to laboratory-supplied containers of appropriate volumes and with required preservatives for the intended analyses. Volatile organic analysis (VOA) sample containers were filled to capacity, sealed with Teflon-lined lids, and checked for air bubbles. If air bubbles were detected, the vial was re-opened, additional sample water added, and the vial resealed.

After sample collection was completed, each sample was labeled with a unique sample number, the site name, date of collection, time of collection, initials of collector, and any other pertinent information. The samples were then placed in a chilled ice chest for transport to Chromalab Inc. Environmental Services (Chromalab). A chain-of-custody document was completed concurrent with sample collection and accompanied the samples upon transport to the laboratory. Chain-of-custody documents are included in Appendix B.



TABLE 2 GROUND WATER PURGE CHARACTERIZATION DATA NOVEMBER, 1994

Monitoring Well ²	Date Measured	Purge Volume (galions)	Electrical Conductivity (µmhos)/cm	Temperature (°F)	Field pH (units)
		1	780	61.8	6.35
MW-1	11/00/04	9	720	59.1	6.25
M W-1	11/09/94	14	700	58.2	6.23
		23	730	61.1	6.32
	11/10/94	1	1090	57.3	7.28
MW-2		9	520	61.6	7.32
M W-2		18	540	60.1	7.24
		27	610	60.2	7.16
		1	700	60.7	7.27
	11/10/94	9	2070	61.6	6.68
MW-3		17	5250	63.3	6.76
		20	6830	62.7	7.03
		22	2760	63.5	7.06

a See Figure 3 for approximate location of monitoring wells.

μmhos/cm Micromhos per centimeters

°F Degrees Fahrenheit

Note: Purge characterization data sheets included in Appendix A.



All ground water samples were analyzed for the following constituents:

Constituent	Analytical Method			
Total petroleum hydrocarbons as diesel (TPH-D)	EPA Method 8015 Modified			
Total petroleum hydrocarbons as motor oil (TPH-MO)	EPA Method 8015 Modified			
Benzene, toluene, ethylbenzene, and xylenes (BTEX)	EPA Method 8020			
Sodium chloride	Calculation ¹			
Total dissolved solids (TDS)	EPA Method 160.1			

3.4 Quality Assurance/Quality Control

To evaluate the integrity of the ground water sampling/analysis process, a duplicate ground water sample was collected from MW-1 using the procedures previously described in Section 3.3. The duplicate ground water sample was analyzed for TPH-D, TPH-MO, BTEX, sodium chloride and TDS.

To assess the potential for cross-contamination of the ground water samples during transport to the laboratory, one trip blank was prepared on site prior to sample collection with DI water and accompanied the ground water samples during shipment to the laboratory. The trip blank was submitted to the laboratory for BTEX analysis only.

In addition, one equipment blank was collected by pouring DI water through the sampling equipment into the appropriate sample bottles. The equipment blank was analyzed for TPH-D, TPH-MO, and BTEX.

Sodium chiefide concentration obtained by calculation, after analyzing for sodium and onlorede separately

4.0 ANALYTICAL RESULTS

Fourth quarter 1994 ground water samples were analyzed by Chromalab for the suite of constituents listed in Section 3.3. Analytical results are summarized in Table 3. Figure 5 is a chemical distribution map. Analytical laboratory reports are included as Appendix C. The following is a summary of the fourth quarter, 1994 analytical results:

- * TPH-D, TPH-MO, and BTEX were not detected in any of the wells sampled at or above their respective reporting limits.
- * Sodium chloride concentrations ranged from 25 milligrams per liter (mg/L) in MW-1 to 140 mg/L in MW-3 (average concentration for all three wells = 67 mg/L).
- * TDS ranged from 370 mg/L in MW-2 to 620 mg/L in MW-3 (average concentration for all three wells = 487 mg/L).

The analytical results for the duplicate ground water sample collected from MW-1 were consistent with those of the original ground water sample.

None of the analyzed constituents were detected at or above their respective reporting limits in either the trip blank or the equipment blank.

All laboratory procedures (holding times, methods used, method blanks, documentation, etc.) and subsequent results were monitored throughout the analytical process according to standard quality assurance/quality control (QA/QC) procedures. In addition, all laboratory reports were evaluated as part of QA/QC procedures for ground water monitoring. The analytical data included in this fourth quarter, 1994 report are considered quantitatively valid.

TABLE 3 GROUND WATER ANALYTICAL RESULTS NOVEMBER, 1994

	Total Petroleum ^a Hydrocarbons (µg/L)		Volatile Organic Compounds ^b (μg/L)				Sodium	Total Dissolved	
Sample Location	Date Sampled	Diesel	Motor Oil	Benzene	Toluene	Ethylbenzene	Xylenes	Chloride ^c (mg/L)	Solids ^d (mg/L)
MW 1	11/09/94	<50	< 500	<0.5	<0.5	< 0.5	<0.5	25	470
MW/2	11/10/94	< 50	< 500	<0.5	<0.5	< 0.5	<0.5	35	370
MW 3	11/10/94	< 50	< 500	<0.5	<0.5	< 0.5	< 0.5	140	620
MW 1 Duplicate	11/09/94	< 50	< 500	<0.5	<0.5	< 0.5	<0.5	25	480
Equipment Blank	11/09/94	< 50	< 500	<0.5	<0.5	< 0.5	<0.5	NA	NA
1 np Blank	□/09/94	NA	NA	<0.5	<0.5	< 0.5	<0.5	NA	NA
Cal DHS MC	15'	NE	NE	1	100 ^f	680	1,750	NE	500

- a Analyzed by TPA Method 8015 Modified.
- b BTI X analyzed by FPA Method 8020.
- c Sodium chloride concentrations determined by calculation, after analyzing for sodium and chloride separately.
- d I ofal dissolved solids analyzed by EPA Method 160.1.
- e California Department of Health Services (DHS) Maximum Contaminant Levels (MCLs) for drinking water (California RWQCB, May, 1993, Compilation of Water Quality Goals)
- f California DHS action level for drinking water (California RWQCB, May, 1993, Compilation of Water Quality Goals).

NA Not analyzed.


NE No MCL established.

mg/L Milligrams per liter

μg/L Micrograms per liter

 Indicates the constituent was not detected at a concentration at or above the reporting limit as listed.





5.0 DISCUSSION

No petroleum hydrocarbons or related volatile organic compounds were detected in ground water samples collected during the fourth quarter, 1994 ground water monitoring event at the SPTCo Fifth Avenue and Seventh Street property. This result is generally consistent with analytical results from all previous monitoring events (Table 4). TPH-MO was detected in MW-2 at a concentration of 750 mg/L during the third quarter 1994 monitoring event. None of the constituents analyzed this or any preceding quarter has exceeded established California Department of Health Services (DHS) maximum contaminant levels (MCLs) or action levels (ALs) for drinking water.

Ground water elevation contour maps for all previous monitoring events are included in Appendix D. Table 5 lists all ground water elevation data collected to date. A comparison of ground water elevation data collected during the fourth quarter, 1994 sampling event with ground water elevations measured during third the quarter 1994, indicates a slight increase in ground water elevations in wells MW-2 and MW-3, and a substantial increase in ground water elevation in MW-1. Ground water elevations measured during the fourth quarter (November 9, 1994) show an average increase of 4.11 feet over third quarter water levels (August 16, 1994). The local hydraulic gradient for the fourth quarter, 1994 was calculated to be 0.013 feet per foot which is slightly lower than the gradient calculated for August, 1994 of 0.017 feet per foot. The ground water flow direction has changed from a northeasterly direction in August of 1994 to a southerly direction this quarter (November 1994). The observed increase in ground water elevation is most likely due to seasonal variation. The change in flow direction may be due to seasonal variation or tidal influence. Figure 6 shows hydrographs of ground water elevations for all monitoring wells.



TABLE 4 GROUND WATER ANALYTICAL RESULTS HISTORIC SUMMARY

Sample Location	Date Sampled	Total Petroleum Hydrocarbons (µg/L)		Volatile Organic Compounds ^b (µg/L)				Sodium	Total Dissolved
		Diesel ^a	Motor Oil ^b	Benzene	Toluene	Ethylbenzene	Xylenes	Chloride ^c (mg/L)	Solids ^d (mg/L)
MW 1	04/28/94	< 50	<200	< 0.5	<0.5	<0.5	< 0.5	61	530
	08/ 16/94	<120	< 750	< 0.3	<0.3	<0.5	<0.5	86	600
	11/09/94	<50	< 500	<0.5	<0.5	<0.5	<0.5	25	470
MW?	04/28/94	<50	<200	<0.5	<0.5	<0.5	< 0.5	77	460
	08/16/94	<120	750	< 0.3	< 0.3	<0.5	<0.5	170	690
	11/10/94	<50	<500	<0.5	<0.5	<0.5	<0.5	35	370
MW 3	04/28/94	<50	<200	<0.5	<0.5	<0.5	<0.5	300	680
	08 '16/94	<120	<750	<0.3	< 0.3	<0.5	< 0.5	1200	3700
	11/10/94	<50	<500	<0.5	<0.5	<0.5	<0.5	140	620
Cal DHS MCLS		NE	NE	1	100 ^f	680	1,750	NE	5008

f

a	Analyzed by EPA	Method 8015 Modified	(April 1994 sample	s analyzed by EPA
---	-----------------	----------------------	--------------------	-------------------

b Analyzed by LPA Method 8015 Modified (April 1994 samples analyzed by EPA Method 8270)

Sodium chloride concentrations determined by calculation, after analyzing for sadium and chloride separately.

d Fotal dissolved solids analyzed by EPA Method 160.1.

e California Department of Health Services (DHS) Maximum Contaminant Levels (MCIs) for drinking water (California RWQCB, May, 1993, Compilation of Water Quality Goals).

California DHS action level for drinking water (California RWQCB, May, 1993, Compilation of Water Quality Goals).

g California DHS Standard Secondary (Recommended) Drinking Water.

NA Not analyzed.

NE No MCL established.

mg/L Milligrams per liter

μg/L Micrograms per liter

Indicates the constituent was not detected at a concentration at or above the method practical quantitation limit or method detection limit as listed.




TABLE 5 GROUND WATER ELEVATION DATA HISTORIC SUMMARY

Monitoring Well ^a	Date Measured	Time Measured	Reference Elevation ^b (feet MSL)	Depth to Ground Water ^c (feet TOC)	Ground Water Elevation ^d (feet MSL)
	04/28/94	0900		4.68	3.52
MW-1	08/16/94	0815	8.20	10.50	-2.30
	11/09/94	0755		2.08	6.12
	04/28/94	0913		2.01	4.35
MW-2	08/16/94	0845	6.36	3.16	3.20
	11/09/94	0815		1.22	5.14
	04/28/94	0920		2.99	3.85
MW-3	08/16/94	0910	6.84	3.06	3.78
_	11/09/94	0810		1.10	5.74

- a See Figure 3 for approximate location of monitoring wells.
- b Reference casing elevation is a point marked on the top of the well casing, which has been measured by a licensed surveyor.
- c Depth to ground water measured from top of casing (TOC).
- d Ground water elevation calculated by subtracting the depth to ground water from the reference casing elevation.
- MSL Mean sea level
- TOC Top of casing





6.0 GLOSSARY OF ACRONYMS

ALs Action levels

bgs Below ground surface

BTEX Benzene, toluene, ethylbenzene, and xylenes

cy Cubic yards

DHS California Department of Health Services

DI Deionized
DI Deionized

IC Industrial Compliance

MCLs Maximum contaminant levels

mg/L Milligrams per liter

MSL Mean sea level

PCBs Polychlorinated biphenyls

ppm Parts per million

QA/QC Quality Assurance/Quality Control

SPTCo Southern Pacific Transportation Company

TDS Total dissolved solids

TEPH Total extractable petroleum hydrocarbons

TPH-D Total petroleum hydrocarbons as diesel

TPH-MO Total petroleum hydrocarbons as motor oil

TRPH Total recoverable petroleum hydrocarbons

UST Underground storage tank

VOA Volatile organic analysis



APPENDIX A PURGE CHARACTERIZATION FIELD DATA SHEETS



PURGE CHARACTERIZATION AND SAMPLE LOG

Project Number:	05100269	Project Name: Inst OAKLAND /ACD	Date:
Well Number:	MW-3	Sampler JAMES ALEXAND MIKE FADEWITT	Weather: Sunny PARTIALLY
			CLOUPY

Military Time	0915	0925	0940	1000	1030	1300	
Gallons Purged	/	9	17	20	22		Depth to bottom (DB): /3.60
Purge Rate						.5	Depth to water (DW): 1.29
pН	7,27	6.68	6.76	7.03	7.06	A	Height of water column (H) = DB - DW: 12.31
Conductivity	.70×1030	2.07×1000	5.25/°00	6.83×100	2. Koto	181	One casing volume (CV) = H x multiplier: 8,00
Temperature (C)	60.7	61.60	63.3	62.7	63.5	P	Three casing volumes (3CV): 24.0
Salinity (0/00)			ļ			L	Multipliers = 2" well = 0.16 gallons/loot
Turbidity	LUUDI					-E	4 well = 0.65 gallons/foot
Color	· · · · · · · · · · · · · · · · · · ·	 			May		6" well = 1.47 gallons/foot
Water Level Casing	ļ						· 8" well = 2.61 gallons/foot
Calibration	pH						S.C.:

Sample #	Quantity	Volume	Туре	Preserv.	Analysis	Lab	Sample Equip.	Purge Equip.	Field Comments
MW-3	2	Yoml	VOA	HCL	BIEX	CHROMA	Dis. BANK	TETION, RAWER	Tiold Compilering
	1	14	AMBER	NONE	TPH-D	LAB)		
	1	14	AMBOR	NONE	TAM-MO				
<u>\</u>	1	11+	POLY	NONE	TOS/NALL	V	\/		· · · · · · · · · · · · · · · · · · ·
			· /						
	ļ								
			ļ		<u> </u>				
						<u> </u>			
					<u> </u>				
									<u></u>
	•				<u> </u>				·
		<u> </u>	<u> </u>						
aning.									
ជាហាents.	WHILE	PURGING	MDE M	O TICES	ROTTEN F	GG"C	1527H) 200K	WELL SON TO	PETHADO-
							1	THE COLUMN TO	

Sampler's Signature:

James Softerman

GROUND WATER ELEVATION MEASUREMENT LOG

Sheet	_/	οf	

Project Name: AKLAND YARO KAST	Project No. 05/00 269	Task/Phase:
Date: //-09-94	Equipment:	Weather: CLODY

Well Number	Reference Elevation (feet-MSL)	Time (military)	Depth to Water (feet)	Depth to Product (feet)	Total Depth (feet)	PT (feet)	PT x 0.8 (feet)	Adjusted DTW ¹ (feet)	Ground Water Elevation ² (feet-MSL)
MW-1	8.20	0755	2,08		13.68			208	6,12
MN-2	6.36	0815	1.22		13.64			1,22	5.14
MW-3	6.84	0810	1.10		13.60			1.10	5.74

Com	ments:								1

1	l Adousted	denth	to	water =	DTW -	/PT x	0.	. 8	١

MSL Mean sea level

Depth to water (to 0.01 foot) DTW

PTProduct thickness (0.01 foot)

Ground water elevation = Reference elevation - Adjusted DTW 2



PURGE CHARACTERIZATION AND SAMPLE LOG

Well Number: _	MW-1	Sampler: JAMES ACKERMAN/ MILLE ENDICOT	Weather: <u>CLOCED</u> Y

Military Time	800	පිල	1815	835	845	
Gallons Purged		9	14	23		Depth to bottom (DB): /3.68
Purge Rate						Depth to water (DW): 202
pH	6-35	6-25		6.32	5	Height of water column (H) = DB - DW: (1.60
Conductivity	28	-22	~ 500	*:000 -23		One casing volume (CV) = H x multiplier: 2.54
Temperature (C)	66-8	32-1	58.3	61.1	<i>p</i>	Three casing volumes (3CV): 22-62
Salimity (0/00)					1	Multipliers = 2" well = 0.16 gallons/foot
Turbidity	CLEAR	CLERK	CLEAR	CLERR	E	4" well = 0.65 gallons/foot
Color	CLEAR	CLERC	CLEAR	CHEAR		6" well = 1.47 gallons/foot
Water Level Casing			<u> </u>			8" well = 2.61 gallons/foot
Calibration	pH					S.C.:

Sample #	Quantity	Volume	Туре	Preserv.	Analysis	Lab	Sample Equip.	Purge Equip.	Field Comments
M6-1	2	40me	COA	HCL	8020	CHROM	TEL BALLER	PISP BALLER	
MW-1	/	147	AMBER		11PH/2005	CHROY	TEL BALLER	DISP BAILER	
MW-1	1	147	Pay				TEL COILER	DEP BAILER	
1-10-1		LLT	AMBER		TPH/DESEL	CHRON	TEL BAILER	DISP BALLER	
MW-1D	2	40ML	COA	HCL	8020	1	TEL BALLER	DISP BAILER	
MW-10		147	AMBER		TPH/MOIGE	CHOO	TEL BALLER	DISP BOILER	
M60-10		LLT	POLY					DISP BOILER	
M6-10		16.7	AMBER		7PH/DOGE	CHROS	TEL BALLER	DAD BALLER	
	· 	<u> </u>			<u> </u>	 	 		
						 	 		
					 	 			
Cleaning:	QUASHE	12 Ce2/TH	ALCOHOK	/ PIXISE	DOET W	OPTH CE	I PATER		
Comments							······································	· · · · · · · · · · · · · · · · · · ·	
	1			·····				 	

Sampler's Signature: Deke Endros



PURGE CHARACTERIZATION AND SAMPLE LOG

Project Number:	5100269
-----------------	---------

Well Number: MW-Z

Project Name: EAST JAKLAND YARD

Sampler: JAMES ACKERYN / MIKE ENDECOTE

Weather: SUNNY / PARTALLY (LOURY

Military Time	0810	0815	0830	0845	0900	
Gallons Purged	/	9	18	27		Depth to bottom (DB): 13,64
Purge Raie	_				5	Depth to water (DW): , 08
pH	7.28	7.32	7.24	7.16	Α	Height of water column (H) = DB - DW: 13.56
Conductivity		,52×100	:54×1000	, GIX	M	One casing volume (CV) = H x multiplier: 8.8
Temperature (C)	57.3	61.6	60.1	60.2	P	Three casing volumes (3CV): 26.4
Salimity (0/00)					2	Multipliers = 2" well = 0.16 gallons/foot
Turbidity	CUCAR				E	4" well = 0.65 gallons/foot
Color	_					6" well = 1.47 gallons/foot
Water Level Casing	ļ					8" well = 2.61 gallons/foot
Calibration	pH:					S.C.:

Sample#	Quantity	Volume	Туре	Preserv.	Analysis	Lab	Sample Equip.	Purge Equip.	Field Comments
MW-2	2	VSA 4PM	VOA	HCI	BIEX	CHRWA	Dis. BANDE	TEFLIN BALLER	THE COMMITTEE
\		11	AUB 32	NINE	TPH-DIEZ		1	TET LESS ESTATES	
	Į.	ilt	AMBER	NUNE	TP4-Mb				
	1	11+	POLY	I	TOS NALL	V			
			7					<u> </u>	
								-	
	. <u>.</u>			<u> </u>					
		1							
-									
leaning.								*	
omments:									
	1						 	· · · · · · · · · · · · · · · · · · ·	

Sampler's Signature:

APPENDIX B CHAIN-OF-CUSTODY DOCUMENT

CHAIN-OF-CUSTODY RECORD

129/69480-69485

19284 20428

LAB COPY

INDUSTRIAL COMPLIANCE • 9838 OLD PLACERVILLE ROAD, SUITE 100 • SACRAMENTO, CA 95827-3559 • Phone 916-369-8971 • FAX 916-369-8370 PROJECT LOCATION PROJECT NAME SURM #: 9411129 **ANALYSIS DESIRED** CAKLAND, FAST CAKLAND YARD
PROJECT CONTACT (INDICATE CLIENT: INDCOMP NUMBER PROJECT TELEPHONE NO. SEPARATE 11/17/94 DUE: (50) 238-9540 CONTAINERS) 05,00269 REF #:19284 PROJECT MANAGER/SUPERVISOR CLIENT'S REPRESENTATIVE ARL TAYLOR TEM NO SAMPLE LOCATION (INCLUDE MATRIX AND POINT OF SAMPLE) COMP GRAB SAMPLE NUMBER DATE TIME REMARKS 11-9 0830 TRIP SAMPLE, MONTORING HELLMW C845 AMPLE MONTORING 0649 1300 MONTORING WELL MW-Z X 11-10 0900 WATER MONITURING WELL MW-3 XX XX /360 16 MW-3 WATER 9 10 REMARKS TRANSFER NUMBER **TRANSFERS** TRANSFERS ITEM DATE TIME **ACCEPTED BY** RELINQUISMED/BY DAY TURNAROUND NUMBER 11-11941623 1 2 3 SAMPLER'S SIGNATURE SAMPLER'S NAME AUGS ACKORMAN

APPENDIX C

ANALYTICAL LABORATORY REPORTS, GROUND WATER SAMPLES

CHROMALAB, INC.

Environmental Services (SDB)

November 17, 1994

Submission #: 9411129

INDUSTRIAL COMPLIANCE-OAKLAND

Atten: Carl Taylor

Project: EAST OAKLAND YARD Received: November 10, 1994 Project#: 05100269

6 samples for BTEX analysis.

Sampled: November 9, 1994

Matrix: WATER

Run#: 4568

Analyzed: November 15, 1994

Total

grijank in in

Rthv1

Method: EPA 8020

Sp1 #	CLIENT SMPL ID	Benzene (ug/L)		Benzene (ug/L)	Xylenes (ug/L)
	MW-1-DUP	N.D. N.D.	N.D. N.D.	N.D. N.D.	N.D. N.D.

Matrix: WATER

Run#: 4568

Analyzed: November 15, 1994

Sampled: November 10, 1994 Method: EPA 8020

	Benzene Toluene	Benzene	Xylenes
_Spl # CLIENT SMPL ID	(uq/L) (uq/L)	(ug/L)	<u>(ug/L)</u>
69484 MW-2	N.D. N.D.	N.D.	N.D.
COACE MI 2	NDWND	N .D.	N.D.

Matrix: WATER

Analyzed: November 17, 1994 Run#: 4580 Sampled: November 9, 1994 Method: EPA 8020

Spl # CLIENT SMPL ID	Benzene (ug/L)	Toluene (ug/L)	Ethyl Benzene (ug/L)	Xylenes (ug/L)
69480 TRIP	N.D.	N.D.	N.D.	N.D.
69481 MW-1	N.D	N.D.	N.D.	N.D.
Reporting Limits Blank Result Blank Spike Result (%)	0.5	0.5	0.5	0.5
	N.D.	N.D.	N.D.	N.D.
	103	101	101	110

Jack Kelív

Chemist

Alı Kharrazi Organic Manager

CHROMALAB, INC.

Environmental Services (SDB)

November 17, 1994

Submission #: 9411129

INDUSTRIAL COMPLIANCE-OAKLAND

Atten: Carl Taylor

Project: EAST OAKLAND YARD

Project#: 05100269

Received: November 10, 1994

re: Five samples for TEPH analysis

Matrix: WATER Extracted: November 14, 1994 Sampled: See Below Analyzed: November 15, 1994

Method: 3510/8015

Sample #	Client Sample ID	Kerosene (μg/L)	Diesel (µg/L)	Motor Oil (mg/L)	Date <u>Sampled</u>
69481 69482 69483 69484 69485	MW-1 MW-1 DUP EQUIP MW-2 MW-3	N.D. N.D. N.D. N.D.	N.D. N.D. N.D. N.D.	N.D. N.D. N.D. N.D.	11/9/94 11/9/94 11/9/94 11/10/94 11/10/94
Blank Spike Recovery Dup Spike Reco Reporting Limi	very	N.D. 50	N.D. 102% 114% 50	N.D.	0(p)0

ChromaLab, Inc.

Sirinat Challatorn

Sirirat Chullakorn Analytical Chemist Ali Kharrazi Organic Manager

CC



GeoAnalytical Laboratories, Inc.

1031 Kansas Avenue Modesto, CA 95351

Phone (209) 572-0900 FAX (209) 572-0916

CERTIFICATE OF ANALYSIS

Report# F315-06

ChromaLab 1220 Quarry Lane

Pleasanton CA 94566 - 4756

Date:

11/23/94

Date Received:

11/11/94 11/11/94

Date Started:

Date Completed: 11/18/94

Project Name: INDCOMP

Project# 9411129

Sample ID	Lab ID	Detection Limit	Method	Analyte	Results	Units mg/L
MW-1	F35581	1	300	Chloride	15	
MW-1-Dup	F35582	1	300	Chloride	15	
MW-2	F35583	1	300	Chloride	21	
MW-3	F35584	1	300	Chloride	85	
MW-1	F35581	1	6010	Sodium	42	
MW-1-Dup	F35582	1	6010	Sodium	42	

Ramiro Salgado Chemist

Donna Allsup Laboratory Director

Certification # F757



GeoAnalytical Laboratories, Inc.

1031 Kansas Avenue Modesto, CA 95351

Phone (209) 572-0900 FAX (209) 572-0916

CERTIFICATE OF ANALYSIS

F315-06 Report #

ChromaLab

1220 Quarry Lane Pleasanton CA 94566 - 4756 Date:

11/23/94

Date Received:

11/11/94

Date Started: Date Completed: 11/18/94

11/11/94

Project Name: INDCOMP

Project#

9411129

Sample ID	Lab ID	Detection Limit	Method	Analyte	Results	Units mg/L
MW-2	F35583	1	6010	Sodium	39	

			****	0 11	00
MW-3	F35584	1	6010	Sodium	98

MW-1	F35581	10	160.1	Total Dissolved Solids	47 0

MW-1-Dup	F35582	10	160.1	Total Dissolved Solids	480

MW-2	F35583	10	160.1	Total Dissolved Solids	370
14144 =					

MW-3	F35584	10	160.1	Total Dissolved Solids	620
V1 VV = 3	E.303079	117	1170.1	TOTAL INTESTRICT	

Ramiro Salgado Chemist

Certification # F757

Dona allow Donna Allsup Laboratory Director

APPENDIX D

GROUND WATER ELEVATION CONTOUR MAPS PREVIOUS MONITORING EVENTS

