93 SEP 17 AM 10: 07



3315 Almaden Expressway, Suite 34 San Jose, CA 95118 Phone: (408) 264-7723

FAX: (408) 264-2435

TRANSMITTAL

Ms. Susan Hugo Alameda County Health Care Services Ag Department of Environmental Health 80 Swan Way, Room 200	DATE: September 14, 1993 ency PROJECT NUMBER: 61026.02 SUBJECT: ARCO Station No. 6113
80 Swan Way, Room 200	
Oakland, CA 94621	

FROM: John C. Young

WE ARE SENDING YOU:

COPIES DATED		DESCRIPTION					
1	8/16/93	Site Status Update for ARCO Station No. 6113, 785 East Stanley Boulevard, Livermore, California.					
THESE	ARE TRANSMIT	TED as checked below:					
[] Fo	r review and com	ent [] Approved as submitted [] Resubmit copies for approval					
[X] A	s requested	[] Approved as noted [] Submit copies for distribution					
[] Fo	r approval	[] Return for corrections [] Return corrected prints					
[X] F	or your files						
REMA Copie		ject file no. 61026.02					
		John C. Young, Project Manager					

cc: Mr. Mark Thomson, ACDAO Mr. Eddy So, RWQCB



3315 Almaden Expressway, Suite 34 San Jose, CA 95118 Phone: (408) 264-7723

FAX: (408) 264-2435

August 16, 1993 0816SHUG.6113 61026.02

Ms. Susan Hugo Alameda County Health Care Services Agency Department of Environmental Health 80 Swan Way, Room 200 Oakland, California 94624

Subject:

Site Status Update for ARCO Station 6113, 785 East Stanley Blvd.,

Livermore, California.

Dear Ms. Hugo:

This letter provides an update on investigation and remedial activities conducted for the above-referenced site. This update covers site activities performed during June and July 1993, and site activities anticipated for the month of August 1993.

June and July 1993 Activities

- Performed monthly groundwater monitoring.
- Installed vapor wells VW-3 and VW-4.
- Drilled soil boring B-15/VW-5.
- Analyzed soil samples from borings B-13 through B-15.
- Submitted Remedial Action Plan (RAP) and Addendum Three to Work Plan for Installation of Air Sparge Wells and Performance of an Air Sparge Test.



Site Status Update ARCO Station 6113, Livermore, California August 16, 1993 61026.02

Work Anticipated for August 1993


- Perform groundwater sampling for Third Quarter 1993.
- As a result of this past winter's rains, water levels in all onsite monitoring wells have risen from 60 feet below grade to 20 feet below grade. ARCO is currently re-evaluating soil and groundwater remediation alternatives that may be applicable to this site as a result of higher water levels.
- As shown on Plate 7 of the Work Plan, approximately 18 weeks are necessary to complete the scope of work outlined in the preliminary time schedule. This work will be initiated following a decrease in groundwater elevations to allow installation of air sparge wells.
- Per your telephone conversation with Keith McVicker of RESNA, the results of vapor well installation performed in June 1993, will be incorporated into the Report of Findings for Air Sparge Well Installation and Testing. RESNA has enclosed for your review the Generalized Site Plan, Boring Logs, and Analytical Results of Soil Samples from vapor well installation.
- Based on a consistent groundwater flow direction over the past year of monthly monitoring at the subject site, ARCO will discontinue monthly monitoring as of September 1993, and continue quarterly sampling.

If you have any questions or comments regarding this letter, please call us at (408) 264-7723.

Sincerely, RESNA Industries Inc.

John C. Young Project Manager

cc: Mr. Michael Whelan, ARCO Products Company Mark Thomson, Alameda County District Attorney's Office Eddy So, Regional Water Quality Control Board



EXPLANATION

- = Brass manument markers for location of 1" sparge pipe stub-outs below grade
- MW-12 Boring/monitoring well (RESNA 09/89, 02/91, 06/92 and 03/93)
- VW-4 () = Boring/vapor extraction well (RESNA, 06/92 and 08/92)
 - w MW-10, 11, and 12 installed in March 1993
 - VW-3 and VW-4 installed in June 1993
 - = Service island in operation since April 1993
- = Existing underground gasoline storage tanks
 - Vault/junction box
- = Center line of subgrade remediation piping trench
 - Pipes stubbed below grade and capped
- Soil boring/vapor extraction well drilled but not installed in June 1993 since no hydrocarbon-impacted soil B-15/W-5 ⊕

was encountered to a depth of 30 feet below grade.

Approximate Scale

Source: Modified from plan supplied by Ron Archer, Civil Engineer Inc., Feb. 1991; and John Kach Land Surveyor, June 1992 and April 1993.

Working to Restore Fiature

GENERALIZED SITE PLAN ARCO Station 6113 785 East Stanley Boulevard Livermore, California

PLATE

UNIFIED SOIL CLASSIFICATION SYSTEM

MAJOR D	MAJOR DIVISION		R DESCRIPTION MAJOR DIVISION		IVISION	LTŘ	DESCRIPTION
		GW	Well-graded gravels or gravel-sand mixtures, little or no fines.		SILTS AND	ML	Inorganic silts and very fine sands, rock flour, silty or clayey fine sands or clayey silts with slight
	GRAVEL	GP	Poorly—graded gravels or gravel—sand mixtures,				plasticity
	AND GRAVELLY SOILS		little or no fines.		CLAYS	CL	Inorganic clays of low to medium plasticity, gravelly
COARSE-		GM	Silty gravels, gravel—sand— silt mixtures.		LL<50		clays, sandy clays, sifty clays, lean clays
		GC	Clayey gravel, gravel—sand—clay mixtures	FINE – GRAINED SOILS		OL	Organic silts and organic silt—clays of low plasticity
GRAINED SOILS	SAND	SW	Well—graded sand or gravelly sands, little or no fines.		SILTS	мн	Inorganic silts, micaceous or diatomaceous fine sandy or silty soils, elastic silts
	AND SANDY SOILS	SP	Poorly—graded sands or gravelly sands, little or no fines		AND CLAYS LL>50	СН	Inorganic clays of high plasticity, fat clays
	SUILS	SM	Silty sands, sand—silt mixtures.		22,00	ОН	Organic clays of medium to high plasticity, organic silts.
		SC	Clayey sands, sand-clay mixtures	HIGHLY ORG	ANIC SOILS	PT	Peat and other highly organic soils

T	Depth through which		Sand pack		
<u></u>	sampler is driven		Bentonit e		Stratigraphic contact
	Relatively undisturbed sample	∇ ¢	Neat cement		
図	No sample recovered		Caved native soil		Gradational contact
<u></u>	Static water level observed in well/boring		Biank PVC		
$\frac{\nabla}{\overline{z}}$	Initial water level observed in boring		Machine-slotted PVC		Inferred contact
S-10	Sample number	P.I.D.	Photoionization detector	1	

BLOWS REPRESENT THE NUMBER OF BLOWS OF A 140-POUND HAMMER FALLING 30 INCHES TO DRIVE THE SAMPLER THROUGH EACH 6 INCHES OF AN 18-INCH PENETRATION.

GRADATIONAL AND INFERRED CONTACT LINES SEPARATING UNITS ON THE LOG REPRESENT APPROXIMATE BOUNDARIES ONLY. ACTUAL BOUNDARIES MAY BE GRADUAL. LOGS REPRESENT SUBSURFACE CONDITIONS AT THE BORING LOCATION AT THE TIME OF DRILLING ONLY.

R			
Working	10	Restore	Nature

PROJECT 69028.07

UNIFIED SOIL CLASSIFICATION SYSTEM PLATE AND SYMBOL KEY

ARCO Station 6113 785 East Stanley Boulevard Livermore, California

Total depth of bori	ng: 24 feet	Casing diameter:	4 inches
Diameter of boring:	12 inches	Casing material:	Sch 40 PVC
Date drilled:	6-16-93	Slot size:	0.10~inch
Drilling Company:	Exploration Geoservices	Sand size:	3/8" pea gravel
Driller:	John	Screen Interval:	15-1/2 feet to 24 feet
Drilling method:	Hollow-Stem Auger	Field Geologist:	Zbigniew Ignatowicz
Sie	gnature of Registered Professional:		
	Registration No.: CEG 146	3 State: CA	

Depth	Sample No.	Blows	P.I.D.	USCS Code	Description	Well Const
2 -					Pea gravel backfill.	A
4						4
6 =	E	6 8 8				7 ♥ 7 ♥ 7
8 =						0 7
10 -	I	7				7 0 7
12 -	S-11	7 9 10 8 18 25 25 25 25 25 25 25 25 25 25 25 25 25	10.5	ML	Gravelly silt, dark olive—gray, damp, low plasticity, very stiff to hard; fine gravel ~10%.	7 0 7
14 :=		50/6 25	14.3 21.8		Fine gravel, color change to dark greenish-gray; rootlets.	V
16	S-16	28 50/6	26.2	GW	Sandy gravel, coarse-grained sand, fine gravel, greenish-gray,	0
18 -	Ħ	20 21 24	373		damp, very dense.	0
20 -	S-20.5	50/6 50/6	1096	<u>₹</u>		3
22 -	5-20.5	30/6	1096		Silty clay, ~10% fine-grained sand, olive-brown, moist, low to	-641
24 -	S-23.5	22 27	2800	CL	medium plasticity, hard.	O
26 -					Total Depth = 14 feet.	
28 -						
30 -						
32 -						
34 -						
36 -						
38 -						
40 -						



PROJECT:

69028.07

LOG OF BORING B-13/VW-3

ARCO Station 6113

785 East Stanley Boulevard

Livermore, California

.

PLATE

Sch 40 PVC 0.10-inch
0.10-inch
Pea gravel
17 feet to 30 feet
Zbigniew Ignatowicz
_

epth	Sample No.	Blows	P.I.D.	USCS Code	Description	Well Const.
					Pea gravel backfill.	, v
4 -		30 50		GW	Sandy gravel, coarse—grained sand, fine to coarse gravel, dark brown, damp, very dense.	A A
8 -	S-5.5	50				A A A A A A A A A A A A A A A A A A A
10 -	S-11	15 24 25	129	CL/CH	Sitty clay, very dark grayish—brown, damp, medium to high plasticity, hard.	∇ 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7
16 =	S-14.5	8 9 9	49.8		Moist, yellow—orange oxidation stains.	0
18 -	S-17	50/6	45.6	GW	Sandy gravel, dark gray, moist, very dense.	000
20 -	S-23	50/3			Wet.	0000000
26 - 28 -	S-28	23 25 18	2570	SC_	Clayey sand, fine-grained, dark olive-gray, wet, dense.	2000
30 32	S-30.5	12 18	230	CL	Silty clay, olive, moist, medium plasticity, stiff. Total Depth = 31 feet.	
34 - 36 -						
38 - 40 -						



PROJECT: 69028.07

LOG OF BORING B-14/VW-4

ARCO Station 6113

785 East Stanley Boulevard

Livermore, California

PLATE

Total depth of boring:	31-1/2 feet	Casing diameter:	NA
Diameter of boring:	12 inches	Casing material:	NA
Date drilled:	6-16-93	Slot size:	NA
Drilling Company:	Exploration Geoservices	Sand size:	NA.
Driller:	John	Screen Interval:	NA
Drilling method:	Hollow-Stem Auger	Field Geologist:	Zbigniew Ignatowicz
Signa	ture of Registered Professional:		

ire of Registered Professional: $_$

Registration No.: CEG 1463 State: CA

Depth	Sample No.	Blows	P.I.D.	USCS Code	Description	Well Const.
					Steel box.	7 7 7
2 -				GW	Sandy gravel, grayish-brown, stightly damp, dense.	7 7 7
4 -	633		-			7 7 7
6 -	S-6	15 21 29	6.1			7 0 0
8 -	1					7 7 7
				1 1		7 7 7
10 -	S-10.5	25 50/6	7.0			7 7 7
12 -						700
14 -				- _{ML}		700
16 -	S-15.5	27 50/3	17.8	ML	Sandy silt, with some gravel, dark grayish-brown, damp, low plasticity, hard.	7 0 0
				CL	Gravelly clay, olive, damp, medium plasticity, hard.	7 7 7
18 -						7
- 20 -	S-20.5	35 50/2	21.4			7 0 0
22 -						7
- 24 -				CL	Sandy clay, dark greenish—gray, very moist, medium plasticity,	\rangle \rangle \rangle \rangle \rangle
26	F	11 18 25			hard.	7 7 7
- 26 -	S-26	25	34.2			444
- 28 -				1		444
- 30 -	S-31	13				000
32 -	S-31	18	28.6		Total Depth = $31-1/2$ feet.	
- 34 -					Total Depth = 31-1/2 leet.	
J+ [
- 36 -						
38 -						
- 40 -						

		\sqrt{N}	
Working	to Res	tore N	ature

PROJECT:

69028.07

LOG OF BORING B-15 ARCO Station 6113 785 East Stanley Boulevard Livermore, California

PLATE



APPLICANT'S

Kut meVal Date 6/8/93

ALAMEDA COUNTY FLOOD CONTROL AND WATER CONSERVATION DISTRICT

5997 PARKSIDE DRIVE | PLEASANTON, CALIFORNIA 94566 | (415) 484-2600

GROUNDWATER PROTECTION ORDI	NANCE PERMIT APPLICATION
FOR APPLICANT TO COMPLETE	FOR OFFICE USE
ocation of project Arco # 6113 785 East Stanley Boulevard Livermore, California	PERMIT NUMBER 93320 LOCATION NUMBER
CLIENT Name Ar CO Address P.O. Box 5811 Phone (415) 571-2434 City San Mateo Zip 94402	PERMIT CONDITIONS Circled Permit Requirements Apply
APPLICANT Name RESNA Findustries - Keith McVicker Suite 34 Address 33/5 Almaden Expression Phone (408) 264-7723 City San Jose Zip 95/18 TYPE OF PROJECT Well Construction General Content investigation Water Supply Content in Well Destruction Vapor Well PROPOSED WATER SUPPLY WELL USE Domestic Industrial Other Vapor Monitoring Municipal Irrigation DRILLING METHOD: Mud Rotary Air Rotary Auger Houdon-stem Cable Other DRILLER'S LICENSE NO. 484288 (C-57) WELL PROJECTS Drill Hole Diameter 10 in. Maximum Casing Diameter 4 in. Depth 25ft. Surface Seal Depth 15 ft. Number 3 GEOTECHNICAL PROJECTS Number of Borings Maximum Hole Diameter In. Depth 1t. ESTIMATED STARTING DATE 6/16/93 ESTIMATED COMPLETION DATE 6/16/93 ESTIMATED COMPLETION DATE 6/16/93 ESTIMATED COMPLETION DATE 6/16/93 ESTIMATED COMPLETION DATE 6/16/93 CALLERY SUPPLY WELL USE Contential Investigation General Co	A. GENERAL 1. A permit application should be submitted so as to arrive at the Zone 7 office five days prior to proposed starting date. 2. Submit to Zone 7 within 60 days after completion of permitted work the original Department of Water Resources Water Well Drillers Report or equivalent for well projects, or drilling logs and location sketch for geotechnical projects. 3. Permit is void if project not begun within 90 days of approval date. 8. WATER WELLS, INCLUDING PIEZOMETERS 1. Minimum surface seal thickness is two inches or cement grout placed by tremie. 2. Minimum seal depth is 50 feet for municipal and industrial wells or 20 feet for domestic and irrigation wells unless a lesser depth if specially approved. Minimum seal depth for monitoring wells is the maximum depth practicable or 20 feet. C. GEOTECHNICAL. Backfill bore hole with compacted cuttings or heavy bentonite and upper two feet with compacted material. In areas of known or suspected contamination, tremied cement grout shall be used in place of compacted cuttings. D. CATHODIC. Fill hole above anode zone with concrete placed by tremie. E. WELL DESTRUCTION. See attached.
I hereby agree to comply with all requirements of this	Warman Hona 10 In a

Wyman Hong

ARCO Pro	ducts	Comp	ompany	\$			Task O	rder No.	113-	93	-2	.6	77	9 L	9.	11	-		_			Chain of Custo	dy
ARCO Facility no	611	3	Cit (Fa	y icility)	LIV		<u>MOR</u>	E	Project (Consul	manag tant)	jer	70	γKΛ	J	40	U N	\mathcal{L}					SEQUOLA	
ARCO engineer	Mic	hael	الما	ela	h	Telephon (ARCO)	e no.		Telepho (Consul	one glo(itant)	t08)	269	1-77	1X13	Fax (Co	. no. nsultan	1408)26	4-2	143	5	Contract number	
Consultant name	Mic RE	SNI	4	<u> </u>		141	Address (Consulta	72	15)EN		EX	PRE	:55	\mathcal{W}	45			07-073	
			Matrix			rvation				15		П	111				[] §§	0000 0000				Method of shipment	
Sample 1.D.	Container no.	Soil	Water	Other	lce	Acid	Sampling date	Sampling time	BTEX BOZEPA 8020	BTEXTPH EPA M602/8020/8015	TPK Modified 8015 Gas □ Diesel □	Oil and Grease 413.1 🗀 413.2 🗆	TPH EPA 418.1/SM503E	EPA 601/8010	EPA 624/8240	EPA 625/8270	TCLP Semi	W Metals EPA 60	Lead Org./OHS Lead EPA 7420/7421	中中		69028.11	1
B13-1-11	8 8					<u> </u>	6-16-93	ļ <u></u>	28	面础	# 35	22	# th	2/2 4	14/			E	322	\times		Special detection Limit/reporting	
R12-7-1/	1	 	 			<u> </u>	10/5		 				7.20	7		0	/					†	
R12-2-205	1	X			X	i										 ≽	2	P)	\mathbf{X}			
B13-2-16 B13-3-205 B13-4-23.5	1	X			X				1	X	ļ					04	24	P				Special QA/QC	
B14-1-55	1	X			X											0	30	>		X			
R14-7-11		X	,		X											S	AU.)		X]	
R16-3/45		X			X											X	50	P		X			
R14-17	1	X			X											X	7.7			X		Remarks	
B/Y-5-23	1				X					X						13	3]	
B14-3-14.5 B14-4-17 B14-5-23 B14-6-28 B14-7-30.5	1	X			X										,	5	Za			X			
BH-7-305	1	X			X		V			\boxtimes						0	4					}	
		63																					
									-													Lab number G300A45	•
			<u> </u>					<u> </u>	1		 											Turnaround time	
		-						+														Priority Rush 1 Business Day	
Condition of sam		1000	4								receive	ed:	Cc	0								Aush	
Relinguished by	sampler Wew	Jou	Hor	in		Date A	7-43	1100		ved by		de	-2-4		(12	1192	۱ <i>و حر</i>					2 Business Days	
Reliaquished by		y	•		-	Date	/47	Time 4.01	Recei	ved by							1					Expedited 5 Business Days	
Relinquished by	-WGV-	<u> </u>				Date	<i>t</i> : '	Time	Recei	ver.	laboral	ory			C	lete G-	21-	43	Time	16	01	Standard 10 Business Days	×

[ARCO I	Prod	ucts (Comp	Dany	\$			Task O	rder No.		67	02	8.	H	(_	0113	3-9	3-	2			Chain of Custo	_
	ARCO Facilit	y no. (011:	3	City (Fa	y icitity)	LIVE	RM Telephon (ARCO)	ME		Project (Consult Telepho	manag tant) ne hd.,	er (AQ)	76	DH/	92	70 Fax	U/ no.	16 (41)	877	G4_	0435 SE	SPQU0/14	
L	Consultant n		Mr.	cha:	el i	<u>Uhe</u> V)	lay	(ARĆO)	Address	32	(Consult	tant) t	1/	VHI	×Λ/		$\chi \mathcal{D}$	nsultan S	797		109	585	Contract number	•
ŀ			V	<u> </u>	Matrix	IC)		rvation	(Consulte		\bigcap	1					31		J.Vov.				Method of shipment	
	Sample I.D.	Lab no.	Container no.	Soli	Water	Other	lce	Acid	Sampling date	Sampling time	BTEX 602/EPA 8020	BTEX/TPH EPA M602/8020/8015	TPH Modified 8015 Gas ☐ Diesel ☐	Oil and Grease 413.1 🗀 413.2 🗀	TPH EPA 418.1/SM503E	EPA 601/8010	EPA 624/8240	EPA 625/8270	TCLP Semi	CAM Metals EPA (Lead Org./OHS Lead EPA 7420/7421	PIOH		
	R15-1-6		1	X		-	X		6-16-13										Z(A)			X_{-}	Special detection Limit/reporting	
V	315-2-12	,		X			X					\times				1		05	2	JON.				
W	315-3-155 B15-420:5 315-5-26		i	X			X			<u> </u>								->	2º			X_{-}	_	
V	B15-426.5			X			X					\times						00	9				Special QA/QC	
	315-5-26		\	X	<u> </u>		X	-	1/-							-	•	<u>-</u> X			<u> </u>			
୯/	BK-6-31			X	ļ		X	ļ <u>-</u>	LV_			X				1		0	1				-	
																							Remarks	
							 	-															9306A4	<u> </u>
		†	 																	ļ	ļ		Turnaround time	
	-															<u> </u>							Priority Rush 1 Business Day	
	Condition of	ed by se	mpler ,	7000 [Mail	fon	~~~		Date	17-42	Time	Recei	ved by		ed: Val	-				3:15				Rush 2 Business Days	
	Religeulati			7.00	V &		<u>. </u>	Date	1/97	Time		ved by								1-,			Expedited 5 Business Days	
	Relinquish	ed by	אבעני	w	<u> </u>			Date	1/77	Time	Recei	de la constant de la	labora	lory				Date /	21/	93	Time	PO1_	Standard 10 Business Days	0

[•]Distribution: White copy — Laboratory; Canary copy — ARCO Environmental Engineering; Pink copy — Consultant •APPC-3292 (2-91)



3315 Almaden Expwy., Suite 34

San Jose, CA 95118 Attention: John Young

Project: 69028.11, Arco 6113

Enclosed are the results from 7 soil samples received at Sequoia Analytical on June 21,1993. The requested analyses are listed below:

SAMPLE #	SAMPLE DESCRIPTION	DATE OF COLLECTION	TEST METHOD
3FA4501	Soil, B13-2-16	6/16/93	EPA 5030/8015/8020
3FA4502	Soil, B13-4-23.5	6/16/93	EPA 5030/8015/8020
3FA4503	Soil, B14-5-23	6/16/93	EPA 5030/8015/8020
3FA4504	Soil, B14-7-30.5	6/16/93	EPA 5030/8015/8020
3FA4505	Soil, B15-2-10.5	6/16/93	EPA 5030/8015/8020
3FA4506	Soil, B15-4-20.5	6/16/93	EPA 5030/8015/8020
3FA4507	Soil, B15-6-31	6/16/93	EPA 5030/8015/8020

Please contact me if you have any questions. In the meantime, thank you for the opportunity to work with you on this project.

Very truly yours,

SEQUOIA ANALYTICAL

Vickie Tague Project Manager



3315 Almaden Expwy., Suite 34

San Jose, CA 95118

Client Project ID:

69028.11, Arco 6113

Sampled:

Jun 16, 1993

Sample Matrix: Analysis Method:

Soil EPA 5030/8015/8020 Received:

Jun 21, 1993

Attention: John Young

First Sample #:

3FA4501

Reported:

Jul 2, 1993

TOTAL PURGEABLE PETROLEUM HYDROCARBONS with BTEX DISTINCTION

Analyte	Reporting Limit mg/kg	Sample I.D. 3FA4501 B13-2-16	Sample I.D. 3FA4502 B13-4-23.5	Sample I.D. 3FA4503 B14-5-23	Sample I.D. 3FA4504 B14-7-30.5	Sample I.D. 3FA4505 B15-2-10.5	Sample I.D. 3FA4506 B15-4-20.5
Purgeable Hydrocarbons	1.0	15	1,100	340	2.9	N.D.	N.D.
Benzene	0.0050	N.D.	14	3.0	0.69	N.D.	N.D.
Toluene	0.0050	N.D.	54	13	0.085	N.D.	N.D.
Ethyl Benzene	0.0050	0.011	18	5.1	0.021	N.D.	N.D.
Total Xylenes	0.0050	0.046	110	34	0.054	N.D.	N.D.
Chromatogram Pat	tern:	Non-Gas Mix > C6	Gas	Gas	Gas		••

Quality Control Data

deality condition						
Report Limit Multiplication Factor:	1.0	50	50	1.0	1.0	1.0
Date Analyzed:	6/27/93	6/28/93	6/28/93	6/27/93	6/27/93	6/27/93
Instrument Identification:	GCHP-18	GCHP-1	GCHP-18	GCHP-18	GCHP-17	GCHP-17
Surrogate Recovery, %: (QC Limits = 70-130%)	96	83	116	112	112	119

Purgeable Hydrocarbons are quantitated against a fresh gasoline standard. Analytes reported as N.D. were not detected above the stated reporting limit.

SEQUOIA ANALYTICAL

Vickie Tague **Project Manager**

3FA4501.RES <1>



3315 Almaden Expwy., Suite 34

San Jose, CA 95118

Attention: John Young

Client Project ID: Sample Matrix:

First Sample #:

69028.11, Arco 6113

Soil

EPA 5030/8015/8020

Analysis Method: 3FA4507 Sampled:

Jun 16, 1993

Received: Reported:

Jun 21, 1993 Jul 2, 1993

TOTAL PURGEABLE PETROLEUM HYDROCARBONS with BTEX DISTINCTION

Analyte	Reporting Limit mg/kg	Sample I.D. 3FA4507 B15-6-31	
Purgeable Hydrocarbons	1.0	N.D.	
Benzene	0.0050	N.D.	
Toluene	0.0050	N.D.	
Ethyl Benzene	0.0050	N.D.	
Total Xylenes	0.0050	N.D.	
Chromatogram Pat	ttern:		

Quality Control Data

Report Limit

Multiplication Factor:

1.0

Date Analyzed:

6/27/93

Instrument Identification:

GCHP-17

Surrogate Recovery, %: (QC Limits = 70-130%)

108

Purgeable Hydrocarbons are quantitated against a fresh gasoline standard.

Analytes reported as N.D. were not detected above the stated reporting limit.

SEQUOIA ANALYTICAL

Vickie Tague Project Manager



Client Project ID:

69028.11, Arco 6113

3315 Almaden Expwy., Suite 34

Matrix:

Soil

San Jose, CA 95118 Attention: John Young

QC Sample Group: 3FA4501-07

Reported: Jul 2, 1993

QUALITY CONTROL DATA REPORT

ANALYTE	·		Ethyl-		
	Benzene	Toluene	Benzene	Xylenes	
Method:	504 5055	501	554 444		
	EPA 8020	EPA 8020	EPA 8020	EPA 8020 A. Maralit	
Analyst:	A. Maralit	A. Maralit	A. Maralit		
Conc. Spiked: Units:	0.20	0.20	0.20	0.60	
Oilles.	mg/Kg	mg/Kg	mg/Kg	mg/ Kg	
LCS Batch#:	BLK062593	BLK062593	BLK062593	BLK062593	
Date Prepared:	6/25/93	6/25/93	6/25/93	6/25/93	
Date Analyzed:	6/27/93	6/27/93	6/27/93	6/27/93	
nstrument I.D.#:	GCHP-18	GCHP-18	GCHP-18	GCHP-18	
LCS %					
Recovery:	90	90	90	90	
Control Limits:	60-140	60-140	60-140	60-140	
MS/MSD					
Batch #:	3FA4008	3FA4008	3FA4008	3FA4008	
Date Prepared:	6/25/93	6/25/93	6/25/93	6/25/93	
Date Analyzed:	6/27/93	6/27/93	6/27/93	6/27/93	
nstrument l.D.#:	GCHP-18	GCHP-18	GCHP-18	GCHP-18	
Matrix Spike					
% Recovery:	75	80	80	82	
Matrix Spike					
Duplicate %					
Recovery:	80	85	85	85	
Deletine of					
Relative % Difference:	6.5	6.1	6.1	3.6	
Difference: Quality Assurance S	6.5				

SEQUOIA ANALYTICAL

Please Note:

The LCS is a control sample of known, interferent free matrix that is analyzed using the same reagents, preparation and analytical methods employed for the samples. The LCS % recovery data is used for validation of sample batch results. Due to matrix effects, the QC limits for MS/MSD's are advisory only and are not used to accept or reject batch results.

Vickie Tague Project Manager



Client Project ID:

69028.11, Arco 6113

3315 Almaden Expwy., Suite 34 San Jose, CA 95118

Matrix:

Soil

Attention: John Young

QC Sample Group: 3FA4501-07

Reported: Jul 2, 1993

QUALITY CONTROL DATA REPORT

ANALYTE			Ethyl-		-
	Benzene	Toluene	Benzene	Xylenes	
Method:	EPA 8020	EPA 8020	EPA 8020	EPA 8020	
Analyst:	R. Geckler	R. Geckler	R. Geckler	R. Geckler	
Conc. Spiked:	0.20	0.20	0.20	0.60	
Units:	mg/Kg	mg/Kg	mg/Kg	mg/Kg	
Oints.	mg/ng	ing/ng	mg/ng	mg/ng	
LCS Batch#:	BLK062593	BLK062593	BLK062593	BLK062593	
Date Prepared:	6/25/93	6/25/93	6/25/93	6/25/93	
Date Analyzed:	6/25/93	6/25/93	6/25/93	6/25/93	
nstrument I.D.#:	GCHP-17	GCHP-17	GCHP-17	GCHP-17	
LCS %					
Recovery:	110	100	100	100	
Control Limits:	60-140	60-140	60-140	60-140	
MS/MSD					
Batch #:	3FA4004	3FA4004	3FA4004	3FA4004	
Date Prepared:	6/25/93	e (ae (aa	6 /26 /02	6/25/93	
Date Analyzed:	6/25/93	6/25/93 6/25/93	6/25/93 6/25/93	6/25/93	
nstrument I.D.#:	6/25/93 GCHP-18	GCHP-18	GCHP-18	GCHP-18	
iiga Gillelit I.D.#.	GCDF-18	GCHP-16	GONT-18	GUNTER	
Matrix Spike					
% Recovery:	95	95	95	97	
Matrix Spike					
Duplicate %					
	100	100	100	98	
Mecovery:					
Recovery:					
Relative % Difference:		5.1	5.1	1.0	

SEQUOIA ANALYTICAL

Vickie Taguě Project Manager

The LCS is a control sample of known, interferent free matrix that is analyzed using the same reagents. preparation and analytical methods employed for the samples. The LCS % recovery data is used for validation of sample batch results. Due to matrix effects, the QC limits for MS/MSD's are advisory only and are not used to accept or reject batch results.



APPLICANTS

SIGNATURE Parbain Aleminski Date 1/19/93

ZONE 7 WATER AGENCY

5997 PARKSIDE DRIVE

PLEASANTON, CALIFORNIA 94588

VOICE (510) 484-2600 FAX (510) 462-3914

31992

DRILLING PERMIT APPLICATION

FOR APPLICANT TO COMPLETE	FOR OFFICE USE					
LOCATION OF PROJECT ARCO 6113 785 Earl Stunley Boulevand, Livermore, CA	PERMIT NUMBER 93044 LOCATION NUMBER					
CLIENT Name	PERMIT CONDITIONS Circled Permit Requirements Apply					
APPLICANT Name RESNA Judustines Tac for ARCO 23.5 Atmostic Exp Address 5 11 2 Phone 103 334-7133 City 5 2 Phone 103 334-7133 TYPE OF PROJECT Well Construction Geotechnical Investigation Cathodic Protection General Water Supply Contamination Monitoring Well Destruction Vapur Extraction PROPOSED WATER SUPPLY WELL USE Domestic Industrial Cther Municipal Irrigation DRILLING METHOD: Mud Rotary Air Rotary Auger Hollow Stem Cable Other DRILLER'S LICENSE NO. (-57 # 484288 WELL PROJECTS Drill Hole Diameter 10 in. Maximum Casing Diameter 6 (4) [2] In. 1, (5) [2] Depth 75, (55) It. 4, Surface Seal Depth 45, (25) It. 4, (3) Number	A. GENERAL 1. A permit application should be submitted so as to arrive at the Zone 7 office five days prior to proposed starting date. 2. Submit to Zone 7 within 60 days after completion of permitted work the original Department of Water Resources Water Well Drillers Report or equivalent for well Projects, or drilling logs and location sketch for geotechnical projects. 3. Permit is void if project not begun within 90 days of approval date. B. WATER WELLS, INCLUDING PIEZOMETERS 1. Minimum surface seal thickness is two inches of cement grout placed by tremie. 2. Minimum seal depth is 50 feet for municipal and industrial wells or 20 feet for domestic and irrigation wells unless a lesser depth is specially approved. Minimum seal depth for monitoring wells is the maximum depth practicable or 20 feet. C. GEOTECHNICAL. Backfill bore hole with compacted cuttings or heavy bentonite and upper two feet with compacted material. In areas of known or suspected contamination, tremied cement grout shall be used in place of compacted cuttings. D. CATHODIC. Fill hole above anode zone with concrete placed by tremie. E. WELL DESTRUCTION. See attached.					
GEOTECHNICAL PROJECTS Number of Borings Maximum Hole Diameter in. Depth ft.						
ESTIMATED STARTING DATE 02/01/93 ESTIMATED COMPLETION DATE 02/05/93	Approved Wyman Hong Date 27 Jan 9					
I hereby agree to comply with all requirements of this permit and Alameda County Ordinance No. 73-68.	Wyman Hong					

CITY OF LIVERMORE Public Works Department

STREET ENCROACHMENT PERMIT APPLICATION (18 1 192)

PERMIT TO DO WORK IN ACCORDANCE WITH CHAPTER 12.08 OF THE LIVERMORE MUNICIPAL CODE AND SPECIFICATIONS AS ADOPTED BY THE CITY OF LIVERMORE AND ANY SPECIAL REQUIREMENTS SHOWN OR LISTED HEREIN.

AS ADOPTED BY THE CITY	OF LIVERMORE AN	ID ANY SPECIAL R	EQUIREMENTS	SHOWN OH LIST	ED REMEIN.
* t	Y	Dor	mit No.		
Applicant/Permittee: Name: <u>RESNA J</u> nJ	lustries Inc.	for AR (O Re	ceipt No.:		
	1 A. A. C 5	. la 49 En	o. C.		
Address: 500 Tose	(A 95118	Bo	nd: \$	24	
Phone: (408) 264-	7713				
Phone: 1900 201		THE WORK	CITE TO ARRAN	IGE FOR INSPECT	TION, PHONE 373-5240 AT
PLEASE READ THIS PERMIT LEAST 24 HOURS BEFORE	CAREFULLY. KEEP YOU START WORK	THE WORK	= = = 11 /	1 1 2 L. I	Limain CA Plate
JOB LOCATION VICINIL	110f ARICO-S	tation 61134	RE ESAN S	Hanley Dione	Livering Co. Liver
DESCRIPTION OF WORK: Two 10-inch diagram divater mon After initial is a quarterly ba for sampling to The wells will and groundwater Jength of Excavation	ineter soil be inturing well installation is to det o determine	onings will be is (MW-11 of of the well emine char presence	and MW-4 is, they of any	ind two 2- i) installe will be n oundwater proundwater	nonitored on levels, and recontamination.
Length of Excavation	N/A Lt.	Widthlo*	I.f. Dept	12	_ n.
ATTENTION IS DIRECTED	TO THE CENERAL	PROVISIONS PAIN	IED OH HIVE HE	· · · · · ·	THIS PERMIT AND TO THE
1. Sue attached conc	ditions.			challate of th	e apolicant.
_	1 1	cies shall be	the respons	FRITTLY OF C.	erenledt.
	The Depoint NO	in ty cated	, T/24/93 on	Elic era e-	
. , ,			4	ì	10 No. 100
- 993 · (1-mg	1.2	·承诗:	H	*	
24				•	
	, Sec. 12.		demonlika dil	ioent and expedition	is manner, and must be completed
Liability and Damages: The po	ermittee shall be respone by permittee under this maintenance and encrose	nsible for all liability im s permit, or which may achment. The permitted at law for damage or i	posed by law for parise out of the failu	ersonal injury or propers	is manner, and must be completed perty damage which may arise out permittee to perform his obligation ivermore, its officers and employees rise out of or be occasioned in an
Signature of Permittee			City Engineer	^	
Orginater of Formatte	1 5 4 1	;2	By: M	Demnard	Ing
-BK	7/ -	ン		2/6/12	0
Date:	(-	<u> </u>	Date of Issue:		
Work Completed:					
Inspector:white	E — PUBLIC WORKS YELI	LOW - FINANCE PINK	_ APPLICANT GOLD	ENROD — ENGINEERING	DEPARTMENT

Total depth of boring:	31-1/2 feet	Casing diameter:	NA
Diameter of boring:	12 inches	Casing material:	NA .
Date drilled:	6-16-93	Slot size	NA.
Drilling Company:	Exploration Geoservices	Sand size:	NA NA
Driller:	John	Screen Interval:	NA .
Drilling method:	Hollow-Stern Auger	Field Geologist:	Zbigniew Ignatowicz
Signat	ture of Registered Professional:		

Signature of Registered Professional:

Registration No: CEG 1463 State: CA

Depth	Sample No.	Blows	P.I.D.	USCS Code	Description	Well Const
					Steel box.	7 7 7 7
- 2 -				GW	Sandy gravel, grayish—brown, slightly damp, dense	
4 =						7 7 7
- 6 -	S-6	15 21 29	6.1			7 7 7 7
8						7
- 10 -	S-10.5	25 50/6	7.0			7 0 0
12 -						2
14				ML	Sandy silt, with some gravel, dark grayish—brown, damp, low	7 7 7
- 16 -	S−15.5	27 50/3	17.8	CL	plasticity, hard. Gravelly clay, olive, damp, medium plasticity, hard.	
- 18 -					Gravelly clay, onve, damp, modium plasticity, hard.	7
20	S-20.5	35 50/2	21.4			7
- 22 -						\(\sigma\) \(\sigma\) \(\sigma\)
- 24 -				CL	Sandy clay, dark greenish—gray, very moist, medium plasticity, hard.	7 7 7
- 26 -	S-26	11 18 25	34.2			7 7 7
- 28 -						2 2 2 2 2 2 2 2 2
- 30 -	S-31 ±	13 31 18	28.6			0 0 0 0 0 0
- 32 -	3 31	18	20.0		Total Depth = 31-1/2 feet.	- Nilesti
- 34 -						
- 36 -						
- 38 -						
40 -						



PROJECT:

69028.07

LOG OF BORING B-15 ARCO Station 6113 785 East Stanley Boulevard Livermore, California

PLATE

Depth of boring: 54 1/2 feet Diameter	of baring: 10 inc	thes Date drilled: 03/24/93										
Well depth: 52 feet Material ty	pe: Sch 40 PVC	Casing diameter:4 inches										
Screen interval: 32 to 52 feet	Slot size:	0.020-inch										
Drilling Company: Exploration GeoServi	ces Driller:	John and Dennis										
Method Used: Hollow-Stem Auge	<u></u>	Field Geologist: Barbara Sieminsk										
Signature of Registered Professional:												
Registration No.: <u>CS</u>	<u> </u>	CA										

Sample No.	Blows	P.I.D.	USCS Code	Description						
				Aspnalt (4 inches)	70 6					
			GP	Sandy gravel, gray, damp, dense; baserock	A 2.					
			SP	Sandy, medium— to coarse—grained, brown, damp, dense	0 0					
			GP	Sandy gravel, brown, damp, very dense.	A 4					
S-5.5	34 50	3 /6"			7 0 7 7 0 7 7 0 7					
	[50,	/5"		With cobbles.	7 7 7 7 7 7					
					7					
			ML	Clayey silt with sand, light brown mottled orange, damp, low plasticity, hard	7 0 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7					
S-15.5	24 50	4" 5	GW-GC	Sandy gravel with clay, brown, damp, very dense.	A A A					
					200					
S-20	5 0	/5" ₅		Increasing clay.	A A A A A A A A A A A A A A A A A A A					
	S-5.5	S-5.5 ■ 34 50 50 S-15.5 ■ 24 50	S-5.5 34 6" 3 S-5.5 50 5" S-15.5 50 50 5" S-20 50 5" 5	GP SP GP SP GP ST	Aspnalt (4 inches) GP Sandy gravel, gray, damp, dense; baserock. SP Sandy, medium— to coarse—grained, brown, damp, dense GP Sandy gravel, brown, damp, very dense. S-5.5 34 50 6" 3 With cobbles. ML Clayey silt with sand, light brown mottled orange, damp, low plasticity, hard. S-15.5 50 4" 5 CW-GC Sandy gravel with clay, brown, damp, very dense.					

Working to Restore Nature

PROJECT:

69028.11

LOG OF BORING B-17/MW-10 ARCO Station 6113

ARCO Station 6113 785 East Stanley Boulevard Livermore, California PLATE

epth Sample No.	P.I.D. USCS Code Description 50/5" 5 GW-GC Increasing clay.					
	50,	/5" ₅	GW-GC	Increasing clay.	20 00	
-55 –			ML	Gravelly sit with cay, prown, damp, ow plasticity, very stiff	70 0 0	
-24					70 0	
-26-S-25.5	10	6	CL	Sandy clay, brown, moist, medium plasticity, very stif	7 07 7	
-28 -					2 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	
-30 - S-30.5	11 16 25	7	ML	Sandy silt with clay, trace gravel, grayish—prown mottled prange, moist, low plasticity, hard	7 7 V	
-32 -	123					
-34 - S-35	10		sc	Clayey sand with fine gravel, brown, moist, medium dense.	1 = 1	
- 36 -	10 15 23	6	ML	Sandy silt, brown, moist, low plasticity, hard.	7 🔡	
- 38 -			□ GC	Clayey gravel, brown, wet, very dense.		
-40 - S-40	26 30	4.5 /6"				
-42 -	□ 50	/6"				
-44 -			GP	Sandy gravel, brown, wet, very dense.		
-46-S-45.5	23 50	/5" ⁰				
- 48 -						
_50 _	K 50	/6"				

(Section continues downward)

Working to Restore Nature

69028.11 PROJECT

LOG OF BORING B-17/MW-10 ARCO Station 6113 785 East Stanley Boulevard Livermore, California

PLATE

)epth	Sample No.	BLOWS	P.I.D.	USCS Code	Description	Well Const.
			e e	GP	Sandy gravel, brown, wet, very dense.	
-52 -						
-54 -	S-54	50	75.9		T :: d:: 54 1/2 Frank	(4.11
-56 -					Total depth = $54 ext{ 1/2 feet.}$	1
-58 -						
-60 —						
-62 -						
-64 -						
-66-						
-68-						
– 70 –						
-72 -						
-74 -						
- 76 -						
- 78 -						
_ 80 -						

Worlding to Restore Nature

PROJECT 69028.11

LOG OF BORING B-17/MW-10

ARCO Station 6113
785 East Stanley Boulevard
Livermore, California

PLATE

Depth of boring: 47 1/2 feet Diameter of	boring: 8 inch	nes Date drilled: 03/23/93									
Well depth: 45 feet Material type:	Sch 40 PVC	_ Casing diameter: 2 inches									
Screen interval: 38 to 45 feet	Slot size:	0_020-inch									
Drilling Company: Exploration GeoServices	Driller:	John and Dennis									
Method Used: Hollow-Stem Auger		Field Geologist: Barbara Sieminski									
Signature of Registered Professional:											
Registration No.: CEG 1	463 State:	CA									

Sam	ple o.	Blows	P.I.D.	USCS Code	Description						
				GW-GC	Sandy gravel with clay, damp, brownish—gray, very dense	20 20 20 20 20 20 20 20 20 20 20 20 20 2					
				GC	Clayey gravel with sand, brown, damp, very dense	20 20					
S-5	5	21 25 25	0	gw-gc	Sandy gravel with clay and cobbles, dark brown, damp, very dense; gravel up to 3" diameter.	200					
					72	2000					
S-1		11 33 31	0		Decreasing clay; color change to grayish—brown.	2000					
						44444					
S-1	15	1 48 3.3 1 3.5	3 2			2000					
				ML	Clayey silt with sand, trace fine gravel, light brown mottled gray, damp, low plasticity, hard.	4 4 4 4					
- S-2	20	I 1 3	6			200					
	S-1 S-1	S-5 S-10	S-5 II 25 II 25 S-10 II 33 S-15 II 35	S-5 II 21 25 25 25 25 25 33 2 35 2	GW-GC GC GW-GC S-5 II 25 0 GW-GC S-10 II 33 0 0 1 31 0 0 1 1 1 1 1 1 1 1 1 1 1 1	GW-GC Sandy gravel with clay, damp, brownish-gray, very dense. GC Clayey gravel with sand, brown, damp, very dense. Sandy gravel with clay and cobbles, dark brown, damp, very dense; gravel up to 3" diameter. S-10 33 31 0 Decreasing clay; color change to grayish-brown. S-15 48 33 35 2 ML Clayey silt with sand, trace fine gravel, light brown mottled gray, damp, low plasticity, hard.					

Working to Restore Nature

PROJECT: 69028.11

LOG OF BORING B-18/MW-11

ARCO Station 6113 785 East Stanley Boulevard Livermore, California PLATE

epth 3	ample No.	BLOWS	P.I.D.	USCS Code	Description	Well Cons
22 -		36 150,	/5" ⁰	ML	Clayey silt with sand, trace fine gravel, light brown mottled gray, damp, low plasticity, hard.	00000
						200
24 -	5-25	T 13	0	sc	Clayey sand, fine—grained, brown, moist, med:um dense.	20 0
26-		1 26		ML	Sandy silt with clay, light brown, moist, low plasticity, hard.	20 0
30 - 3	20	П12		SC	Clayey sand, fine—grained, brown, moist, medium dense.	2000
32 -	3-30	12 17 122	0	ML	Clayey silt with sand, light brown, damp, low to medium plasticity, hard.	2000
						20
34 -	S-35	Ш7_			la consciencia de de la consciencia del consciencia de la consciencia del consciencia de la conscienci	φ ·
36 -		17 18	0		Increasing clay.	
38-				▽ -	Clayey sand, fine—grained, brown, moist, medium	- F
40 -	S-40	II 8	4 0	sc	dense.	
-42 -						
-44-	C 45	П1.	3	GL	Silty clay with sond, brown, damp, medium plasticity hard.	
- 46 -	S-45	1 2 2 1 2 4	8 0 8 0			t
- 48 -		H4	Ö		Total depth = 47 1/2 feet.	
- 50 -						

Working to Restore Nature

LOG OF BORING B-18/MW-11

ARCO Station 6113
785 East Stanley Boulevard
Livermore, California

PLATE

Depth of boring: 37 1/2 feet Diameter of boring: 8 inches Date drilled: 03/23/93

Well depth: 34 1/2 feet Material type: Sch 40 PVC Casing diameter: 2 inches

Screen interval: 18 to 34 1/2 feet Slot size: 0.020-inch

Drilling Company: Exploration GeoServices Driller: John and Dennis

Method Used: Hollow-Stem Auger Field Geologist: Barbara Sieminski

Signature of Registered Professional:

Registration No.: CEG 1463 State: CA

)epth ⁽	Sample No.	Blows	P.I.D.	USCS Code	Description	Well Const.
0 -				GW	Sandy gravel, brown, damp, very dense.	9 9 9
2 -						
4				GC	Clayey gravel, dark brown, damp, very dense.	20 2
- 6 -		23 25 30	o	GW-GC	Sandy gravel with clay, damp, very dense.	7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7
8 -						2 0 2 2 0 2 2 0 2
10 -	S-10	11 16 21	0	CL	Sandy clay, trace fine gravel, brown, damp, medium plasticity, hard.	200
12 -				ML	Gravelly silt with sand, grayish—brown, damp, low plasticity, hard.	2 G G
14 -	S-15	15	0			70 0
16 -		22				
- 18 -				GW-GC	Sandy gravel with clay, brown, moist, very dense.	
- 20 -		50	/3"0			
					(Section continues downwo	ord)

Working to Restore Nature

PROJECT: 69028.11

LOG OF BORING B-19/MW-12

ARCO Station 6113 785 East Stanley Boulevard Livermore, California PLATE

epth	Sample No.	BLOWS	Description	Well Const		
		Ī		GW-GC	Sandy gravel with clay, brown, moist, very dense.	
- 22 -				▽▼		
24 -	S-24.5		cen O	77	Becoming wet.	
- 26 -	1	1 50)	6.0			
-28 -						
	S-29.5	3 50.	/6" ⁰			
-30 -	l i					
-32 -				SM	Silty sand, fine—grained, brown, wet, dense.	1 1
-34 -	1 P	L22			Sandy silt with clay, brown, damp, low plasticity, hare	d.
- 36 -	S-35.5	24 26	0	ML CL	Silty clay with sand, brown, damp, medium plasticity, hard.	
- 38 -		<u>†</u> šŏ	/4" ⁰		Total depth = 37 1/2 feet.	
_ 40 -						
-42-						
-44						
- 46						
- 48						
-50	1					

R	,	5	A
Working	(lo	Restore	Nature

PROJECT 69028.11

LOG OF BORING B-19/MW-12

ARCO Station 6113
785 East Stanley Boulevard
Livermore, California

PLATE

ARCO	Produ	ICTS of Atlantic	Comp	Dany (\$			Task Or	der No.	61	13	-93	3 -	2								Chain of Custody
ARCO Facil	ly no.	611.	3	Cit (Fa	y icility) L	iver	more			Project Consul	manag tant)	jer	och	· (o	ffu	nan		- -y-				Laboratory name Segue: a Contract number
ARCO engir Consultant i	ARCO Escility no. 6113 City (Facility) Liver ARCO engineer Michael Whelaw Consultant name RESNA						(ARCO)	Address (Consultant)			Telephone no (Consultant) (408) 264-7723 Fax no (Co							(408 Jos)-26 e , (4-2 A9	435 5118	Contract number
				Matrix		Prese	ervation	, p			20015	% □	2	Œ				□ YOA	. 80107000 C			Method of shipment Sequel'e Coun'es
Sample I.D.	Lab no.	Container no	Soil	Water	Other	ice	Acid	Sampling date	Sampling time	BTEX. 602/EPA B020	BTEXTIPH 9-0-0 EPA MODZ/BC20/8015	TPH Modified 8015 Gas Diesel	Oil and Greese 413.1 C 413.	TPH EPA 418.1/SM503E	EPA 601/8010	EPA 624/8240	EPA 625/8270	TCLP Shmi	CAM Mecas EPA	Lead Org./DHS C		
5-15,5-		1	V	4		J	3/19/00	3/24/92			X		930	0.50	09		01					Special detection Limit/reporting
5-20-	1	1	V	≥ £		√		3/24/92			X						02			ļ <u>.</u>		
5-305-	BIT	1	V	¥		V		2/24/93	<i>y</i>		X					1	03			ļ <u>.</u> .		
5-35-	вП	١	V			V		3/24/92			X						०प					Special QA/QC
5-10-		1	V			V		3/23/92			X					1	or		ļ			_
5-20-	18	١	V			V		3/23/92		<u> </u>	X					ļ	06		ļ			
5-30-1			V	<u>]</u>		V		3/23/95		ļ	X				ļ	ļ	07	ļ		ļ		Remarks
5-35	1	}	V			V		3/23/92		<u> </u>	X	<u> </u>	ļ	ļ			0(<u> </u>		
5-45-		1	V			V		3/23/92			X		<u> </u>		ļ	<u> </u>	07		ļ	ļ		
5-10-	B 19	1	V			W	-	3/23/93		.	X	ļ	ļ			ļ	10	ļ		ļ <u>-</u>		
5-15-	\$17	1	V			J	_	3/23/93			X	ļ	<u> </u>		ļ			ļ	ļ	ļ		_
5-25.	618	1	1		_	V	_	3/23/93		<u> </u>	X		 	 	 		112	-	_	 		
		-	-		ļ	_	<u> </u>				<u> </u>		<u> </u> .	1								Lab number
 	 	-		-	1			<u> </u>			1											Turnaround time
ļ	 	 	-		 .	1	1	-														Priority Rush 1 Business Day
Condition	of sample):								<u> </u>	perature	, P-4	red:							_		Rush
	rba		Sie	mi'r	esle	•		193	Time	ļ	ived by) —	I	 L		<u>.</u>					2 Business Days Expedited
Relinquis		7	<u>t </u>	اِن	<u>k</u>		Date	5/43	1 Time Time		olved by		ntgry _	1) /	<u>r</u>	Date		<u> </u>	Time	7 U 2	5 Business Days Standard 10 Business Days
	10 1	- J	obat	ai Cosos	. copu	ADCO Ex	viconmental	Engineering;	Pink conv —	Consu	<u>∠7</u> Itant) (!)	<u> </u>	4	7 T	-	ا د	78	<u>) '=</u>	1	/ 4/2	To Duamess Days

APPC-3292 (2-91)



3315 Almaden Expwy., Suite 34

San Jose, CA 95118 Attention: Joel Coffman

Project: Arco 6113, Livermore

Enclosed are the results from 12 soil samples received at Sequoia Analytical on March 25,1993. The requested analyses are listed below:

3CD0901	Soil, S-15.5-B17	3/24/93	EPA 5030/8015/8020
3CD0902	Soil, S-20-B17	3/24/93	EPA 5030/8015/8020
3CD0903	Soil, S-30.5-B17	3/24/93	EPA 5030/8015/8020
3CD0904	Soil, S-35-B17	3/24/93	EPA 5030/8015/8020
3CD0905	Soil, S-10-B18	3/24/93	EPA 5030/8015/8020
3CD0906	Soil, S-20-B18	3/24/93	EPA 5030/8015/8020
3CD0907	Soil, S-30-B18	3/24/93	EPA 5030/8015/8020
3CD0908	Soil, S-35- B 18	3/24/93	EPA 5030/8015/8020
3CD0909	Soil, S-45-B18	3/24/93	EPA 5030/8015/8020
3CD0910	Soil, S-10-B19	3/24/93	EPA 5030/8015/8020
3CD0911	Soil, S-15-B19	3/24/93	EPA 5030/8015/8020
3CD0912	Soil, S-35.5-B19	3/24/93	EPA 5030/8015/8020

Please contact me if you have any questions. In the meantime, thank you for the opportunity to work with you on this project.

Very truly yours,

SEQUOIA ANALYTICAL

Project Marager

3315 Almaden Expwy., Suite 34

San Jose, CA 95118

Attention: Joel Coffman

Client Project ID: Arco 6113, Livermore

Sampled:

Mar 24, 1993

Sample Matrix:

Soil

Received:

Mar 25, 1993

Analysis Method: First Sample #:

EPA 5030/8015/8020 3CD0901

Reported:

Apr 7, 1993 .

TOTAL PURGEABLE PETROLEUM HYDROCARBONS with BTEX DISTINCTION

Analyte	Reporting Limit mg/kg	Sample I.D. 3CD0901 S-15.5-B17	Sample I.D. 3CD0902 S-20-B17	Sample I.D. 3CD0903 S-30.5-B17	Sample I.D. 3CD0904 S-35-B17	Sample I.D. 3CD0905 S-10-B18	Sample I.D. 3CD0906 S-20-B18
Purgeable Hydrocarbons	1.0	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
Benzene	0.0050	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
Toluene	0.0050	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
Ethyl Benzene	0.0050	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
Total Xylenes	0.0050	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
Chromatogram Pati	tern:		••	••			

Quality Control Data

Report Limit Multiplication Factor:	1.0	1.0	1.0	1.0	1.0	1.0
Date Analyzed:	3/31/93	3/31/93	3/31/93	3/31/93	3/30/93	3/30/93
Instrument Identification:	GCHP-7	GCHP-7	GCHP-7	GCHP-7	GCHP-7	GCHP-6
Surrogate Recovery, %: (QC Limits = 70-130%)	77	87	87	89	82	89

Purgeable Hydrocarbons are quantitated against a fresh gasoline standard. Analytes reported as N.D. were not detected above the stated reporting limit.

SEQUOIA ANALYTICAL

3CD0901.RES <1>

3315 Almaden Expwy., Suite 34

Client Project ID:

Arco 6113, Livermore

Sampled:

Mar 24, 1993

San Jose, CA 95118

Sample Matrix: Analysis Method:

Soil EPA 5030/8015/8020 Received:

Mar 25, 1993

Attention: Joel Coffman

First Sample #:

3CD0907

Reported:

Apr 7, 1993

TOTAL PURGEABLE PETROLEUM HYDROCARBONS with BTEX DISTINCTION

Analyte	Reporting Limit mg/kg	Sample I.D. 3CD0907 S-30-B18	Sample I.D. 3CD0908 S-35-B18	Sample I.D. 3CD0909 S-45-B18	Sample I.D. 3CD0910 S-10-B19	Sample I.D. 3CD0911 S-15-B19	Sample I.D. 3CD0912 S-35.5-B19
Purgeable Hydrocarbons	1.0	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
Benzene	0.0050	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
Toluene	0.0050	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
Ethyl Benzene	0.0050	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
Total Xylenes	0.0050	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
Chromatogram Pat	tern:		••				

Quality Control Data

Report Limit Multiplication Factor:	1.0	1.0	1.0	1.0	1.0	1.0
Date Analyzed:	3/30/93	3/31/93	3/31/93	3/31/93	3/31/93	3/31/93
Instrument Identification:	GCHP-7	GCHP-7	GCHP-7	GCHP-7	GCHP-7	GCHP-7
Surrogate Recovery, %: (QC Limits = 70-130%)	105	87	95	85	92	90

Purgeable Hydrocarbons are quantitated against a fresh gasoline standard. Analytes reported as N.D. were not detected above the stated reporting limit.

SEQUOIA ANALYTICAL

3CD0901.RES <2>



SEQUOIA ANALYTICAL

680 Chesapeake Drive . Redwood City, CA 94063 (415) 364-9600 • FAX (415) 364-9233

RESNA

Client Project ID: Arco 6113, Livermore

3315 Almaden Expwy., Suite 34 San Jose, CA 95118

Attention: Joel Coffman

Matrix: Soil

QC Sample Group: 3CD0901 - 012

Reported: Apr 7, 1993

QUALITY CONTROL DATA REPORT

LANDERSENDE COLLEGE - LANDE COUNTE CONTRACTOR CO

ANALYTE			Ethyl-	
	Benzene	Toluene	Benzene	Xylenes
0.0 - 1.1 1 -				
Method:	EPA 8020	EPA 8020	EPA 8020	EPA 8020
Analyst:	R.Geckler	R.Geckler	R.Geckler	R.Geckler
Conc. Spiked:	0.20	0.20	0.20	0.60
Units:	mg/kg	mg/kg	mg/kg	mg/kg
LCS Batch#:	GBLK033193	GBLK033193	GBLK033193	GBLK033193
Date Prepared:	3/31/93	3/31/93	3/31/93	3/31/93
Date Analyzed:	3/31/93	3/31/93	3/31/93	3/31/93
instrument i.D.#:	GCHP-7	GCHP-7	GCHP-7	GCHP-7
LCS %				
Recovery:	95	105	110	110
Control Limits:	60-140	60-140	60-140	60-140

MS/MSD				
Batch #:	3CD0903	3CD0903	3CD0903	3CD0903
Date Prepared:	3/31/93	3/31/93	3/31/93	3/31/93
Date Analyzed:	3/31/93	3/31/93	3/31/93	3/31/93
Instrument I.D.#:	GCHP-7	GCHP-7	GCHP-7	GCHP-7
Matrix Spike				
% Recovery:	85	95	100	103
Matrix Spike				
Duplicate %				
Recovery:	85	100	100	100

Relative %

Difference:

0.0

3.3

Quality Assurance Statement: All standard operating procedures and quality control requirements have been met.

SEQUOTA ANALYTICAL

Please Note:

The LCS is a control sample of known, interferent free matrix that is analyzed using the same reagents, preparation and analytical methods employed for the samples. The LCS % recovery data is used for validation of sample batch results. Due to matrix effects, the QC limits for MS/MSD's are advisory only and are not used to accept or reject batch results.

Project Manager

3CD0901.RES <3>



3315 Almaden Expwy., Suite 34

San Jose, CA 95118

Attention: Joel Coffman

Client Project ID: Arco 6113, Livermore

Matrix:

Soil

QC Sample Group: 3CD0901 - 12

Reported: Apr 7, 1993

QUALITY CONTROL DATA REPORT

ANALYTE					
	Benzene	Toluene	Benzene	Xylenes	
Method:	EPA 8020	EPA 8020	EPA 8020	EPA 8020	
Analyst:	R.Geckler	R.Geckler	R.Geckler	R.Geckier	
Conc. Spiked:	0.20	0.20	0.20	0.60	
Units:	mg/kg	mg/kg	mg/kg	mg/kg	
LCS Batch#:	GBLK033093	GBLK033093	GBLK033093	GBLK033093	
Date Prepared:	3/30/93	3/30/93	3/30/93	3/30/93	
Date Analyzed:	3/30/93	3/30/93	3/30/93	3/30/93	
Instrument i.D.#:	GCHP-7	GCHP-7	GCHP-7	GCHP-7	
LCS %					
Recovery:	105	110	125	120	
Control Limits:	60-140	60-140	60-140	60-140	
MS/MSD					
Batch #:	3CC4405	3CC4405	3CC4405	3CC4405	
Date Prepared:	3/30/93	3/30/93	3/30/93	3/30/93	
Date Analyzed:	3/30/93	3/30/93	3/30/93	3/30/93	
Instrument I.D.#:	GCHP-7	GCHP-7	GCHP-7	GCHP-7	
Matrix Spike					
% Recovery:	100	110	115	112	
Matrix Spike					
Duplicate %					
Recovery:	100	115	120	115	
Relative %					
Difference:	0.0	4.4	4.3	2.9	
Quality Assurance	Statement: All sta	andard operating	procedures ar	nd quality con	trol requirements have been met.

SEQUOIA ANALYTICAL

Please Note:

The LCS is a control sample of known, interferent free matrix that is analyzed using the same reagents, preparation and analytical methods employed for the samples. The LCS % recovery data is used for validation of sample batch results. Due to matrix effects, the QC limits for MS/MSD's are advisory only and are not used to accept or reject batch results.

3CD0901.RES <4>