HAZARDOUS WASTE PRELIMINARY SITE INVESTIGATION REPORT TASK ORDER NUMBER 04-911175-DH CONTRACT NUMBER 43A0012

SOUTH OAKLAND MAINTENANCE STATION 1112 29th AVENUE OAKLAND, CALIFORNIA

5-25-99

prepared for

CALIFORNIA DEPARTMENT OF TRANSPORTATION District 4

111 Grand Avenue Oakland, California 94623

prepared by

Professional Service Industries, Inc. 1320 West Winton Avenue Hayward, California 94545

(510) 785-1111

May 25, 1999 575-9G014

TABLE OF CONTENTS

STATEMENT OF LIMITATIONS AND PROFESSIONAL CERTIFICATION	i
1.0 INTRODUCTION	1
2.0 PRE-FIELD ACTIVITIES	2
3.0 SUBSURFACE INVESTIGATION 3.1 GEOPHYSICAL SURVEY 3.2 SOIL BORINGS 3.3 TEMPORARY MONITORING WELL INSTALLATION	3 3
AND DEVELOPMENT	4 4
4.0 LABORATORY ANALYSIS PROGRAM	
5.0 LABORATORY RESULTS	7 7
6.0 CONCLUSIONS AND RECOMMENDATIONS	9
REFERENCES	10

FIGURES

FIGURE 1: SITE LOCATION

FIGURE 2: SITE PLAN

FIGURE 3: GROUNDWATER ELEVATION MAP: 4/8/99

TABLE OF CONTENTS

TABLES

TABLE 1: GROUNDWATER ELEVATION DATA

TABLE 2: ANALYTICAL RESULTS FOR SOIL SAMPLES

TABLE 3: ANALYTICAL RESULTS FOR GROUNDWATER SAMPLES

APPENDICES

APPENDIX A: FIELD PROCEDURES

APPENDIX B: BORING LOGS

APPENDIX C: SURVEY INFORMATION

APPENDIX D: LABORATORY RESULTS AND CHAIN-OF-CUSTODY RECORDS

STATEMENT OF LIMITATIONS AND PROFESSIONAL CERTIFICATION

Information provided in this Site Investigation Report, prepared by Professional Service Industries, Inc. (PSI), is intended exclusively for the use of Caltrans for the evaluation of subsurface conditions as it pertains to the subject site. The professional services provided have been performed in accordance with practices generally accepted by other geologists, hydrologists, hydrogeologists, engineers, and environmental scientists practicing in this field. No other warranty, either expressed or implied, is made. As with all subsurface investigations, there is no guarantee that the work conducted identified any or all sources or locations of contamination.

This report is issued with the understanding that Caltrans is responsible for ensuring that the information contained herein is brought to the attention of the appropriate regulatory agency. This report has been reviewed by a geologist who is registered in the State of California and whose signature and license number appear below.

Frank R. Poss, R.E.A. Senior Hydrogeologist

Scott A. Bowers Staff Geologist Timothy R. O'Brien RG/CEG/CHG Senior Geologist



1.0 INTRODUCTION

Professional Service Industries, Inc. (PSI) has been retained by the California Department of Transportation (Caltrans), under Task Order Number 04-911175-DH and Contract Number 43A0012, to conduct a hazardous waste site assessment of current soil and groundwater conditions at the South Oakland Maintenance Station at 1112 29th Avenue, Oakland, California (subject site; Figure 1). The scope of work for this investigation included:

- A geophysical investigation to clear borings;
- Installation of six temporary groundwater monitoring wells;
- Collection of soil and groundwater samples to characterize soil and groundwater;
- Preparation of a report detailing the results of the investigation.

1.1 SITE DESCRIPTION

The site is currently used as a maintenance station by Caltrans. The maintenance station includes offices, a repair shop, a sign shop, and several material storage bins. The entire property covers approximately two acres. The site is paved with asphalt and is relatively flat. The Alameda/Oakland Estuary is approximately 0.5 miles southwest of the site.

One 4,000-gallon diesel underground storage tank (UST) and one 2,000-gallon gasoline UST were removed from the site on March 11, 1997. The tank pit was over-excavated and soil samples were collected. Sidewall and bottom samples collected from the excavation contained concentrations of Total Petroleum Hydrocarbons as Gasoline (TPH-G, [as high as 380 milligrams per kilogram (mg/kg)]), and Total Petroleum Hydrocarbons as Diesel (TPH-D, [as high as 21 mg/kg]). Concentrations of Benzene, Toluene, Ethylbenzene, and Total Xylenes (BTEX), ranged from 0.010 to 48 mg/kg. Methyl Tertiary Butyl Ether (MTBE) concentrations ranged from 0.041 to 9.15 mg/kg. Groundwater samples were not collected (Caltrans, 1999).

1.2 PROJECT OBJECTIVE

The objective of the project is to delineate the extent of hydrocarbon impacted soil and groundwater at the site. Analytical results from the soil and groundwater investigations were examined with respect to regulatory requirements and guidelines.

2.0 PRE-FIELD ACTIVITIES

Prior to initiation of field activities, PSI marked the drilling locations with white paint and contacted Underground Service Alert a minimum of 48-hours prior to beginning work to locate any potential buried utilities.

A site-specific Health and Safety Plan (HSP) was developed in compliance with 29 CFR 1910.120, under the supervision of a Certified Industrial Hygienist. The HSP was designed to address the potential hazardous materials that may be encountered during field activities at the site and to minimize the exposure to potentially hazardous materials and unsafe working conditions to on-site personnel (PSI, 1999).

3.0 SUBSURFACE INVESTIGATION

3.1 GEOPHYSICAL SURVEY

PSI utilized Norcal Geophysical Surveys of Petaluma, California to perform a geophysical survey to clear soil boring locations. Norcal Geophysical completed the geophysical survey using ground-penetrating radar, magnetometry, and electromagnetic line locating.

The geophysical survey found no evidence of subsurface debris or utilities that may have obstructed drilling operations. The geophysical investigation was performed under the supervision of a California Registered Geophysicist (Norcal, 1999).

3.2 SOIL BORINGS

On April 6 and 7, 1999, Borings B1 through B6 were drilled at the site. The boring locations are presented in Figure 2. All of the borings were converted to 1.3 centimeter (cm) (0.5-inch) inside diameter temporary groundwater monitoring wells. Borings were drilled using a Geoprobe 5300 drill rig. Fisch Environmental of Valley Springs, California provided drilling services.

The borings were advanced using a 0.038 meter (1.5-inch) diameter core sampler fitted with a retractable tip and lined with acetate sleeves. Soil samples were collected from each boring at depths of 1.52, 3, and 4.56 meters (5, 10, and 15 feet) below ground surface (bgs).

Soils were logged according to the "Soil and Rock Logging Classification Manual" of the State of California, Department of Transportation. Boring logs are presented in Appendix B. Soils observed during drilling activities consisted primarily of clay and sand mixtures. Groundwater was encountered approximately 1.5 meters (49 feet) below ground surface (bgs).

The soil samples were logged on chain-of-custody records and transported to Pace Analytical of Long Beach, California, a California Department of Health Services certified hazardous materials testing laboratory, following chain-of-custody protocol. The samples were maintained in a cooler with ice, or a refrigerator until transported to the analytical laboratory. The analytical results are described in Section 4.

3.3 TEMPORARY MONITORING WELL INSTALLATION AND DEVELOPMENT

Temporary groundwater monitoring wells were constructed in all six of the soil borings. The well casings consisted of 1.3 centimeter (cm) (0.5-inch) inside diameter, Schedule 40 Polyvinyl chloride (PVC) casing with 0.025 cm (0.010-inch) machine-slotted screen from 1.5 to 6 meters (5 to 20 feet) bgs. The temporary wells were installed with a prepackaged sand pack and a sanitary seal. Following groundwater sampling, the casing of the temporary wells was removed and the borings were grouted with neat cement to grade using a tremie pipe.

Following installation, the wells were developed by bailing. The development water was collected in 55-gallon drums for proper disposal. Following completion of the well installation, the newly installed well casings and boring locations were surveyed by a professional Land Surveyor. The surveyor's report is presented in Appendix C. Elevation and location were surveyed to accuracy of at least 0.003 m (0.01 foot) vertically and 0.003 m (0.01 foot) horizontally.

3.4 GROUNDWATER SAMPLING

3.4.1 Groundwater Elevation and Hydraulic Gradient

On April 8, 1999 depth to groundwater measurements were collected from six wells (B1 through B6) at the site. The groundwater depths were measured using a groundwater probe. Based on a lack of product sheen or measurable thickness of product in sampling bailers, floating product was not encountered in any of the wells. The groundwater measurements were converted to groundwater elevation data. The data is presented in Table 1 and Figure 3. The calculated groundwater flow direction is to the east with a hydraulic gradient of 0.053 meter per meter (foot per foot).

Groundwater flow direction was measured to be to the east. Interpretation of the United States Geological Survey's topographic map titled, Oakland West, indicates groundwater would be expected to flow to the southwest, towards the Alameda Channel. The deviation from the expected direction may be due to operation of groundwater extraction well(s) for industrial use, dewatering of underground structures, or localized hydrogeology. It is noted that the highest concentrations of contaminants were reported in the well located south of the former tank pit, consistent with the expected flow direction.

3.4.2 Groundwater Sampling

Groundwater samples were collected from the temporary monitoring wells. Prior to the collection of groundwater samples, the monitoring wells were purged of a minimum of three well volumes of water until pH, conductivity, and temperature stabilized. The wells were allowed to recover to at least 80 percent of their original static groundwater levels prior to sampling.

The following procedures for well monitoring, well purging, and water sampling were implemented while sampling the wells:

- 1. All equipment was washed prior to entering the well with an Alconox solution, followed by one tap water rinse and a deionized water rinse.
- 2. Prior to purging the wells, depth-to-water was measured using a groundwater interface probe to an accuracy of 0.003 meters (0.01 foot). The measurements were made to the top of the well casing on the north side.
- 3. Water samples were collected with a single-use Teflon bailer after the well had been purged and water in the well had equilibrated to approximately 80 percent of the static water level. The water collected was immediately decanted into laboratory supplied vials and bottles. The containers were overfilled, capped, labeled, and placed in a chilled cooler prior to delivery to the laboratory for analysis.
- 4. Chain-of-custody procedures, including chain-of-custody forms, were used to document water sample handling and transport from collection to delivery to the laboratory for analyses.
- 5. Groundwater samples were delivered to the State-certified hazardous waste laboratory within approximately 48-hours of collection.
- 6. Purged water was contained in a DOT approved 55-gallon drum. The drum was labeled with the contents, date, well number, client name, and project number.

4.0 LABORATORY ANALYSIS PROGRAM

The soil and groundwater samples collected during this investigation were submitted to Pace Analytical, a State of California Department of Health Services certified hazardous waste laboratory.

4.1 SOIL AND GROUNDWATER

The following analytical methods were used to analyze soil and groundwater samples:

- EPA Method 8015 modified Total Petroleum Hydrocarbons as Gasoline (TPH-G);
- EPA Method 8015 modified Total Petroleum Hydrocarbons as Diesel (TPH-D);
- EPA Method 8260 Volatile Organic Compounds (VOCs)

5.0 LABORATORY RESULTS

A summary of the analytical results are presented in Tables 2 and 3. A copy of the laboratory reports and chain-of-custody records are included in Appendix D.

5.1 LABORATORY ANALYTICAL RESULTS - SOIL

The soil analytical results are presented in Table 2. TPH-G was detected in one soil sample (B6-10 [13 mg/kg]). None of the soil samples contained detectable concentrations of TPH-D.

MTBE was the only VOC detected in the soil samples analyzed. MTBE was detected in the sample B5-1.5 meters (0.16 mg/kg). No other soil sample contained a detectable concentration of MTBE. The MTBE found in the soil sample collected from Boring B5 at 1.5 meters (5 feet) bgs could be related to the release from the former tank pit. The lack of other contaminants in Boring B5 and the lack of contaminants in any of the other soil samples collected from the borings located adjacent to the former tank pit indicates that soil contamination is limited to the former tank pit.

5.2 LABORATORY ANALYTICAL RESULTS - GROUNDWATER

Groundwater samples from temporary wells B1 through B6 were submitted to the laboratory for analysis. The groundwater analytical results are presented in Table 3

TPH-G was detected in groundwater samples from Wells B3 (520 μ g/l) and B4 (520 μ g/l). No other groundwater samples contained detectable concentrations of TPH-G. No TPH-D was detected in any of the groundwater samples.

Benzene was detected in the water sample from Well Wb3 (6.3 ug/l). MTBE was detected in the samples from Well WB5 (6,600 ug/l) and WB6 (24 ug/l). Concentrations of other gasoline related compounds were detected in samples from Wells WB1, WB3, WB4, and WB5.

Chloroform was detected in water samples from Wells WB4 (2.4 ug/l) and WB6 (2.7 ug/l). Tetrachloroethene (synonym Perchloroethene [PCE]) was detected in the water sample from Well WB6 (12 ug/l)

5.3 COMPARISON OF GROUNDWATER RESULTS WITH REGULATORY CRITERIA

The concentrations of contaminants reported by the analytical laboratory were compared to State of California Primary and Secondary Drinking Water Standards (PDWS and SDWS). The following samples were above their respective PDWS and/or SDWS.

- The benzene concentration detected in Well B3 (6.3 ug/l) exceeded the PDWS (1.0 ug/l).
- The MTBE concentration detected in Wells B5 (6,600 ug/l) and B6 (24 ug/l) exceeded the SDWS (5.0 ug/l).
- The PCE concentration detected in Well B6 (12 ug/l) exceeded the PDWS (5.0 ug/l).

6.0 CONCLUSIONS AND RECOMMENDATIONS

Based on the information presented in this report, the following conclusions have been reached:

- The groundwater flow direction measured at the site is east with a hydraulic gradient of 0.053 meter per meter (foot per foot). The measured groundwater flow direction is not consistent with the anticipated flow direction interpreted from a topographic map. This anomaly may be due to nearby groundwater extraction or local hydrogeology.
- TPH-G and VOC concentrations were detected in two soil samples at the site. Soil
 contamination appears to be limited to the tank pit.
- TPH-G concentrations were detected in two of six groundwater samples at low concentrations
- A low concentration of benzene was detected in one groundwater sample.
- A moderate concentration of MTBE was detected in one groundwater sample, and a low concentration was detected in a second sample.
- Gasoline related compounds were reported in for of the six groundwater samples.
- Chloroform and/or PCE were detected in two groundwater samples.

Based on the results presented in this report, PSI recommends additional investigation to better delineate the extent of impacted groundwater. PSI recommends drilling three additional hydropunch borings to the south and east of Boring B5 to determine the extent of the MTBE impacted groundwater.


REFERENCES


Caltrans, 1999, Task Order # 04-911175-DH, Hazardous Waste Preliminary Site Investigation, prepared for Caltrans, March 4.


PSI, 1999, Health and Safety Plan, prepared for Caltrans, March 26.

PSI, 1997, Hazardous Waste Preliminary Site Investigation Workplan, prepared for Caltrans, March 26.

Norcal, 1999, Geophysical Results for the South Oakland Maintenance Station, prepared for PSI, April 6.







0 35 70 SCALE IN FEET

LEGEND

SOIL BORING/TEMPORARY WELL LOCATION

28.40 GROUNDWATER ELEVATION IN FEET ABOVE MEAN SEA LEVEL

LINE OF EQUAL GROUNDWATER ELEVATION

0.053 FT/FT GROUNDWATER FLOW DIRECTION AND GRADIENT

AN ASTERISK (*) INDICATES DATA NOT USED IN CONTOURING DUE TO ANOMALOUS READING.



GROUNDWATER ELEVATION MAP: 4/8/99
CALTRANS MAINTENANCE STATION
1112 29TH AVENUE
OAKLAND, CALIFORNIA
PROJECT NUMBER: 575-9G014

DATE: 4/22/99

CKD BY:

FIGURE NO.: 3

FILE NO: 90014-2

DRAWN BY: S.BOWERS

TABLE 1

GROUNDWATER ELEVATION DATA SOUTH OAKLAND MAINTENANCE STATION 1112 29TH AVENUE OAKLAND, CALIFORNIA

TEMPORARY WELL	TOC ELEVATION (feet msl)	DEPTH TO GROUNDWATER	GROUNDWATER ELEVATION
B-1	32.41	NM	
B-2	32.97	4.57	28.40
B-3	33.52	8.27	25.25
B-4	32.99	8.81	24.18
B-5	33.11	16.56	16.55
B-6	32.59	8.60	23.99

Notes:

Depth to water measurements from 4/8/99.

TOC = Top of Casing.

msl = mean sea level.

All measurments are presented in feet.

NM = Not measured

TABLE 2

ANALYTICAL RESULTS FOR SOIL SAMPLES SOUTH OAKLAND MAINTENANCE STATION 1112 29TH AVENUE OAKLAND, CALIFORNIA

Sample I.D.	TPH-G mg/kg	TPH-D mg/kg	MTBE µg/kg	VOCs* µg/kg	
B1-5	<1.0	<10	<5	ND	
B1-10	<1.0	<10	<5	ND	
B2-5	<1.0	<10	<5	ND	
B2-10	<1.0	<10	<5	ND	
B3-5	<1.0	<10	<5	ND	
B3-10	<1.0	<10	<5	ND	
B4-5	<1.0	<10	<5	ND	
B4-10	<1.0	<10	<5	ND	
B5-5	<1.0	<10	160	160	
B5-10	<1.0	<10	<5	ND	
B6-5	<1.0	<10	<5	ND	
B6-10	13	<10	<5	ND	

NOTES:

TPH-D = Total Petroleum Hydrocarbons as Diesel by EPA Method 8015M.

TPH-G = Total Petroleum Hydrocarbons as Gasoline by EPA Method 8015M.

MTBE = Methyl Tertiary Butyl Ether

VOCs* reported as the sum of all analytes detected in EPA Method 8260

TABLE 3

ANALYTICAL RESULTS FOR GROUNDWATER SAMPLES SOUTH OAKLAND MAINTENANCE STATION 1112 29TH AVENUE OAKLAND, CALIFORNIA

Sample I.D.	TPH-G µg/l	TPH-D mg/l	MTBE μg/l	Benzene µg/l	Toluene µg/l	Ethyl- benzene µg/l	Total Xylenes µg/l	I-PB µg/l	N-propyl- benzene µg/l	Naph- thalene µg/l	1,2,4-TMB µg/l	1,3,5-TMB µg/l	Chloroform µg/l	PCE µg/l
WB1	<500	<10	<1.0	<0.5	<0.5	<0.5	2.0	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5
WB2	<500	<10	<1.0	<0.5	<0.5	<0.5	<1.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5
WB3	520	<10	<1.0	6.3	2.2	11	40	1.8	5.4	3.5	31.0	12.0	<0.5	<0.5
WB4	520	<10	<1.0	<0.5	<0.5	3.7	7.7	1.3	3.0	2.6	19.0	6.3	2.4	<0.5
WB5	<500	<10	6,600	<0.5	0.6	<0.5	<1.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5
WB6	<500	<10	24	<0.5	<0.5	<0.5	<1.5	<0.5	<0.5	<0.5	<0.5	<0.5	2.7	12

NOTES:

TPH-D = Total Petroleum Hydrocarbons as Diesel by EPA Method, 8015M.

TPH-G = Total Petroleum Hydrocarbons as Gasoline by EPA Method 8015M.

MTBE = Methyl Tertiary Butyl Ether

1,2,4 TMB = 1,2,4 Trimethylbenzene

1,3,5 TMB = 1,3,5 Trimethylbenzene

I-PB = iso-Propylbenzene

PCE = Tetrachloroethene (Synonym perchloroethen

APPENDIX A

PSI FIELD PROCEDURES

APPENDIX A FIELD PROCEDURES

I. FIELD DOCUMENTATION OF SAMPLING PROCEDURES

The following outline describes the procedures adhered by PSI for proper sampling documentation.

- 1. Sampling procedures will be documented in field notes that contain:
 - 1. Sample collection procedures
 - 2. Date and time of collection
 - 3. Date of shipping
 - 4. Sample collection location
 - 5. Sample identification number(s)
 - 6. Intended analysis
 - 7. Quality control samples
 - 8. Sample preservation
 - 9. Name of sampler
 - 10. Any pertinent observations
- 2. Samples will be labeled with the following information:
 - 1. Sample designation number
 - 2. Date and time sample was collected
 - 3. Sampler's name
 - 4. Sample preservatives (if required)
- 3. The following is the sample designation system for the site:

For Borings the samples will be labeled B-(Boring Number)-(Depth) (i.e. sample collected from boring 4 at 5 meters (feet) would be B4-5).

- 4. Handling of the samples will be recorded on a chain of custody form which shall include:
 - 1. Project name
 - 2. Site location
 - 3. Signature of Collector
 - Date and time of collection
 - 5. Sample identification number
 - 6. Number of containers in sample set
 - 7. Description of sample and container
 - 8. Name and signature of persons, and the companies or agencies they represent, who are involved in the chain of possession
 - 9. Inclusive dates and times of possession
 - 10. Analyses to be completed

II. ADVANCING OF SOIL BORINGS AND COLLECTION OF SOIL SAMPLES

The following procedures were used for advancing soil borings and collecting soil samples at the site:

- 1. Prior to the commencement of soil boring activities at the site, soil boring locations were marked with white paint. Underground Service Alert (USA) was contacted to identify underground utilities in the vicinity of the soil borings.
- 2. Soil boring and sampling activities were conducted by Fisch Environmental of Valley Springs, California. The soil borings were advanced using GeoProbe direct push method. Flush-threaded rods with a stainless steel sampler were advanced into the ground using a hydraulic press and percussion hammer. The opening of the sampler was sealed with a drive tip held in place by a threaded pin.
- 3. Soil samples were collected using a .45 meter (1.5-foot long), 0.02 meter (1-inch) inside diameter macro-core stainless steel sampler. Soil samplers were washed between sampling intervals with Alconox soap followed by two deionized water rinses. The sampler was lined with clean brass, stainless steel, or acetate sleeves. When the boring was advanced to the desired sampling depth the threaded pin was removed allowing the drive tip to retract as the sampler was advanced 45 meter (1.5-foot long) into native soil using a percussion hammer.

- 4. After the sampler was retrieved the sleeves were extracted from the sampler without disturbing the sample. The sample was collected for analyses from the lowest tube in the sampler. The ends of the sample were covered with Teflon™ sheets and capped with polyethylene end caps. The sample was labeled and placed in a ziplock bag in a chilled cooler prior to delivery to the laboratory for analyses.
- 5. Soil samples were assigned identification numbers such as B1-5, where B1 indicates the boring designation and -5 indicates that the sample was collected at 5 feet bgs. The samples were labeled with the project name, date and time of sample collection, sampling depth, and client name.
- 6. Chain-of-custody procedures using chain-of-custody records were implemented during handling and transportation of the samples to the laboratory for analyses.
- 7. Boring logs were prepared for the soil borings under the supervision of a California-Registered Geologist. Soil from each sample was described in accordance with Unified Soil Classification System by a PSI geologist and recorded on a field boring log. The data recorded on the logs were based on examination of soil samples retrieved in the tubes, and drilling conditions observed in the field. Boring logs include information regarding the location of each boring, geologic descriptions of materials encountered, occurrence of groundwater (if applicable) and organic vapor analyzer (OVA) measurements in the soil samples collected.
- 8. A HNU photoionizer (PID) was used to monitor volatile organic compounds (VOCs) in the ambient air during drilling at the site in accordance with the site health and safety plan. VOC concentrations in the soil were measured at the sampling depths by partially filling a zip-loc bag and closing the top. The components of the soil were allowed to volatilize and fill the head space in the bag for approximately 15 to 30 minutes prior to inserting the OVA probe through the top of the bag and recording the measurements.
- 9. No soil cuttings were generated during drilling, due to the use of a geoprobe drill rig.

III. BACKFILL OF SOIL BORINGS

The following procedures were used to backfill the soil borings at the site:

1. Soil borings were backfilled to grade with Portland grout slurry. The slurry consisted of neat cement and 5% bentonite powder.

APPENDIX B

BORING LOGS

SHEET 1 OF 2	SOI	L B	OI	RII	NG	LOG					BORING NO:	B1	
PROJECT NUMBER: 875-96014											SHEET 1	OF	2
NORTHINGS: EASTINGS:						PROJECT N	AME:	Caltrans	: South C	akland N	Maintenance Stat	tion	
DRILLING METHOD: Dived Push (opencies)						PROJECT N	UMBER:	575-9G0)14		DATE:	4/6/99	
DRILLING METHOD: Direct Plath (Geoporbe)													
BORING DIAMETER 2 Inch												al	
Capability Cap									Dire				
DATE COMMENTS DEPTH BGS 4/6/99 Sitabilized 3.2						BORING DIA	METER:					36 feet	
African Afri								G	ROUND				
A77/99 Stabilized 6.9													
Clay Description PiD USCS Remarks PiD Pi													
Sity Clay, low plasticity, brown, damp, no odor. CL. Asphalt Surface ML Clayery Sit, brown, low plasticity, damp, no odor. Clayery Sit, brown, low plasticity, damp, no odor. ML Clayery Sit, brown, low plasticity, damp, no odor. Clayery Sit, brown, low plasticity, damp, no odor. ML Clayery Sit, brown, low plasticity, damp, no odor. Clayery Sit, brown, low						_	411133	1		Stabili	260		0.9
1	рЕРТН (FEET)	SAMPLE NO.	RECOVERY (IN)	SAMPLE INTERVAL	BLOW COUNT	DESCRIPTION	l			uscs	R	EMARKS	
2						Silty Clay, low plasticity, brown, damp, no oc	lor.			CL	Asphalt Surface		
2	1_			ĺ									
3	_												
11	2				\vdash								
11													
5— 6— 7— 7— 8— 9— 14	3—											<u>.</u>	
6 — 7 — 8 — 9 — 14 — 14 — 18 — 18 — 18 — 18 — 19 — 20 — 20 — 20 — Log continues downward.	4—			<u> </u>	├ -								
6 — 7 — 8 — 9 — 14 — 14 — 18 — 18 — 18 — 18 — 19 — 20 — 20 — 20 — Log continues downward.	l —		16		-				· · · · · ·				
6 — 7 — 8 — 9 — Clayey Silt, brown, low plasticity, damp, no odor.	5—		'						0				
7 — 8 — 9 — Clayey Silt, brown, low plasticity, damp, no odor.													
8— 9— 10— 114 110— 114 110— 115— 118 116— 117— 118— 119— 20— 20 Log continues downward.				ł									
9 14 14 17 18 18 18 18 18 18 19 19	7—				-						 		
9 14 14 17 18 18 18 18 18 18 19 19													
10 — 14	*_												
10— 14	9									541			
10— 11— 12— 13— 14— 15— 16— 17— 18— 19— 20— 20 Log continues downward.	_		14		-	Clayey Silt, brown, low plasticity, damp, no	odor.	_		ML			
11— 12— 13— 14— 15— 16— 17— 18— 19— 20— 20 Log continues downward. 10— 11— 110— 120— 13— 140— 140— 150— 160— 170— 180— 180— 190— 200— 100— 100— 100— 100— 100— 100— 10	10		'	100	8				0				
12— 13— 14— 15— 16— 17— 18— 19— 20— Log continues downward. Log continues downward.	11_			and par]			
13— 14— 15— 16— 17— 18— 19— 20— Log continues downward.] ''_				-				ļ	1			
13— 14— 15— 16— 17— 18— 19— 20— Log continues downward.	12				-				 -				
14— 15— 16— 17— 18— 19— 20— Log continues downward.			}							1			
15— 18	13—]			
15— 18	14			<u>_</u>					ļ				
15— 16— 17— 18— 19— 20— Log continues downward. 0	-		1.0		 					-	moisture increase.		
16— 17— 18— 19— 20— Log continues downward. 0	15		'"						0		<u> </u>		
17— 18— 19— 20— Log continues downward. 0	1.0			4 10						j			
18— 19— 20— Log continues downward. 0	"-												
19— 20 Log continues downward. 0	17—									-			
19— 20 Log continues downward. 0					\vdash				1	1			
20 Log continues downward.	18—			1						1			
20 Log continues downward.	19—			L									
Log continues downward.	_									-		•••	<u> </u>
1999/1999	20		20			Log continues downward			0	-			
	REVIE	WED B	Y: T	im O	Brie		LOGG	GED BY: S		ers	I		

SOI	L B	OI	RII	NG	LOG					BORING NO:	B1	
]				SHEET 2	OF	2
						PROJECT NAME:	Caltrans	: South C	akland N	Maintenance Sta	tion	
						PROJECT NUMBER:	575-9G	014		DATE:	4/6/99	
						NORTHINGS:				EASTINGS:		
						DRILLING COMPANY	:			ch Environment	al	
						DRILLING METHOD:		Dire		Geoprobe)		
						BORING DIAMETER:	2 inch				36 feet	
								SROUND				
						DATE			COMM	ENTS	DEP	TH BGS
						I					<u> </u>	
оертн (FEET)	SAMPLE NO.	RECOVERY (IN)	SAMPLE INTERVAL	BLOW COUNT	DE	SCRIPTION		PID (PPM)	USCS	R	EMARKS	
					Clayey Silt as described abo	ove.			ML			
 21									'			
_				<u> </u>					-			
22 —				\vdash				<u> </u>	1			
		ĺ			<u>.</u> .				1			
23—]			
24—		ł			·							
					Silty Clay, low to medium pl	asticity, damp, no odor			CL			
25 —		17							1			
				<u> </u>				0				
26			H					 				
									1			
27 —]			
28—									_			******
				-		<u>.</u>			_			
29 —			H	┼					-	moisture increase.	<u> </u>	
]	12										
30 —								0]			
31 —			\prod						1			
									4	ļ		
32—				\vdash	<u> </u>			 	-	ļ		
				\vdash				 	1			
33									1			
34—	1		L]				<u> </u>			
			\prod		Silty Sandy Gravel, coarse	sand, fine gravel, tan, wet, r	o odor.	ļ	GW			
35		20						 	-			
-								0	4			
36 —			\vdash	+				1		Total Depth = 36 f	feet	<u></u>
37—]	Boring drilled to si		for investigation
" _									4	Groundwater stab		
38 —		1		-				_	-	Boring converted	to temporary	groundwater
-				-				 -	-	monitoring well. Well grouted by re	moving opein	n and tremie
39				\vdash				1	4	placement of neat		9 and deline
								1	1			
40						· · · · · · · · · · · · · · · · · · ·		0	1			
REVIE	WED B	Y: T	im O	'Brie	n	LOG	GED BY: 9	Scott A. B	owers			
						<u>1</u>						

PROJECT NAME: Caltrans: South Oakland Maintenance Station PROJECT NUMBER: 575-9G014 DATE: 4/6/99 NORTHINGS: EASTINGS: DRILLING COMPANY: Fisch Environmental DRILLING METHOD: Direct Push (Geoprobe) BORING DIAMETER: 2 inch DEPTH: 20 feet GROUNDWATER LEVELS DATE COMMENTS DEPTH: 4/6/99 initial 19 4/6/99 stabilized 5 Caltrans: South Oakland Maintenance Station PROJECT NUMBER: 575-9G014 DATE: 4/6/99	1
PROJECT NUMBER: 575-9G014 DATE: 4/6/99 NORTHINGS: EASTINGS: DRILLING COMPANY: Fisch Environmental DRILLING METHOD: Direct Push (Geoprobe) BORING DIAMETER: 2 inch DEPTH: 20 feet GROUNDWATER LEVELS DATE COMMENTS DEPTH: 4/6/99 stabilized 19 4/6/99 stabilized 5 (I) AVAILABLE TOWN ON THE STABLE TOWN	
PROJECT NUMBER: 575-9G014 DATE: 4/6/99	
NORTHINGS: EASTINGS: DRILLING COMPANY: Fisch Environmental DRILLING COMPANY: Fisch Environmental DRILLING COMPANY: Fisch Environmental DRILLING METHOD: Direct Push (Geoprobe) BORING DIAMETER: 2 inch DEPTH: 20 feet GROUNDWATER LEVELS DATE COMMENTS DEPTH: 4/6/99 stabilized 5 LIDD A4/6/99 stabilized 5 DESCRIPTION PID USCS REMARKS (PPM) Sity Clay with some fine grained gravet, low to medium plasticity, brown, damp, no odor.	
DRILLING COMPANY: Fisch Environmental DRILLING METHOD: Direct Push (Geoprobe) BORING DIAMETER: 2 inch DEPTH: 20 feet GROUNDWATER LEVELS DATE COMMENTS DEPTH: 4/6/99 initial 19 4/6/99 stabilized 5 (N) A WAR WAR WAR WAR WAR WAR WAR WAR WAR W	
DRILLING METHOD: Direct Push (Geoprobe) BORING DIAMETER: 2 inch DEPTH: 20 feet GROUNDWATER LEVELS DATE COMMENTS DEPTH: 4/6/99 initial 19 4/6/99 stabilized 5 CI STANDON ON A STANDON ON	•
BORING DIAMETER: 2 inch DEPTH: 20 feet GROUNDWATER LEVELS DATE COMMENTS DEPTH: 4/6/99 initial 19 4/6/99 stabilized 5 ON JUNEAN STABILIZED S	
DATE COMMENTS DEPTH 4/6/99 initial 19 4/6/99 stabilized 5 5	
DATE COMMENTS DEPTH 4/6/99 initial 19 4/6/99 stabilized 5 (I) VALUE OF THE PROPERTY OF THE PR	
4/6/99 initial 19 4/6/99 stabilized 5 (Lag Variable Plant Variable Plan	
4/6/99 stabilized 5 (Light of the content of the c	BGS
DESCRIPTION PID USCS REMARKS REMARKS PID USCS REMARKS REMARKS PID USCS REMARKS REMARKS PID USCS REMARKS REMARKS PID USCS REMARKS	
Silty Clay with some fine grained gravel, low to medium plasticity, brown, damp, no odor. The state of the	
1—	
2— 3— 4— 5— 6— 7—	
3— 4— 5— 6— 7—	
3— 4— 5— 6— 7—	
5— 17 0 0 — — — — — — — — — — — — — — — — —	
5— 17 0 0 — — — — — — — — — — — — — — — — —	
5— 17 0 0 — — — — — — — — — — — — — — — — —	
5— 17 0 0 — — — — — — — — — — — — — — — — —	
6— 7— — — — — — — — — — — — — — — — — —	
6— 7— — — — — — — — — — — — — — — — — —	
9-	
0— 0	
3_	
5 0	
6— Groundwater encountered at 19 fee	et bgs.
Total Depth = 20 feet	
8— Boring drilled to sufficient depth for	
Groundwater stabilized at 5 feet bg	
Boring converted to temporary grou	undwater
22 monitoring well.	
0 Well grouted by removing casing a	na tremie
placement of neat cement.	
REVIEWED BY: Tim O'Brien LOGGED BY: Scott Bowers	

SOIL BORING LOG			BORING NO:	B3
			SHEET 1	OF 1
	PROJECT NAME:	Caltrans: South Oak	and Maintenance Sta	tion
	PROJECT NUMBER:	575-9G014	DATE:	4/6/99
	NORTHINGS:		EASTINGS:	
	DRILLING COMPANY:		Fisch Environmenta	
	DRILLING METHOD:	Direct P	ush (Geoprobe)	
	BORING DIAMETER:	2 inch		20 feet
	are the trace well within I had to	GROUNDWA		:
	DATE		OMMENTS	DEPTH BGS
	4/6/99		initial	10
	4/6/99		stabilized	5
	410/33		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
DEPTH (FEET) SAMPLE NO. RECOVERY (IN) SAMPLE INTERVAL BLOW COUNT	DESCRIPTION	PID US	SCS R	EMARKS
Sitty Clay with	some gravel, fine grained gravel, low to		CL Concrete surface	
1 medium plastic	ty, brown, damp, no odor.			
2_				
2 — 3 — 4 — 2a				
3				
	·			
4-				
20				
5—		0		
6—				
\ <u> </u>				
7				
8				
				
9-1		-	••	
21				
10—		0	Groundwater enco	untered.
1 -				****
12—		`		
	-			····
13—				
<u> </u>				
1 14 —				
	·-			.
15—		0		
16				
16—				
17—			<u></u>	
	<u> </u>		Total Depth = 20 f	
18—			/	ufficient depth for investigation
- -				to temporary groundwater
19—		 ,	monitoring well.	o tamperary groundinates
		0		moving casing and tremie
20 —			placement of neat	
REVIEWED BY: Tim O'Brien	LOGGE	ED BY: Scott Bowe	ers	

SOI	L B	0	RII	NC	LOG					BORING NO:	В4
										SHEET 1	OF 1
						PROJECT NAME:	Caltrans	s: South C	akland	Maintenance Sta	tion
						PROJECT NUMBER:	575-9G	014		DATE:	4/6/99
						NORTHINGS:				EASTINGS:	
						DRILLING COMPANY:			Fis	ch Environment	al
						DRILLING METHOD:		Dire	ct Push	(Geoprobe)	
						BORING DIAMETER:	2 inch				20 feet
								SROUND			
						DATE			COMM		DEPTH BGS
						4/6/99 4/6/99			init stabil		9.5 9.5
	Γ-	l				4/0/33			Statili	260	9.5
рертн (FEET)	SAMPLE NO.	RECOVERY (IN)	SAMPLE INTERVAL	BLOW COUNT	DE	SCRIPTION		PID (PPM)	USCS	R	EMARKS
					Silty Clay with some gravel,	fine grained gravel, low to m	edium		CL	Asphalt surface	
1					plasticity, brown, damp, no	odor.					
-				-				·		<u> </u>	
2—											
3											
								<u> </u>			
4	l		┢	┼							
5—	'	10		\vdash							
- 1								0			
6			Щ	+							
-											
7—]		
8				<u> </u>				-			
8—				\vdash				<u> </u>	-		
9			П						1		
10—		20								Groundwater enco	ountered.
10—								0			
11—		İ	۲	+					1	-	
12							`		1		
■ ``									1		
13—				\vdash				 	1		
	•						<u></u>		1		
■ 14—			\prod					[]		
_ 15—		24						0	-		
— 16—	·							 	1		
16—				1]		
17—									1	T-4-1 D. H. CO.	
1/	-			\vdash				 	1 /	Total Depth = 20 to Boring drilled to se	reet ufficient depth for investigation
18—	-		T	+-					1 /	Groundwater stab	ilized at 5 feet bgs.
19	[]	1] /		to temporary groundwater
19	-	24						0		monitoring well.	emoving casing and tremie
20—	-							1 0	- [placement of near	
REVIE	WED E	3Y: T	im C)'Brie	en	Logo	ED BY:	Scott Bo	owers		

SOIL BORING LO	G	BORING NO: B5
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		SHEET 1 OF 1
	PROJECT NAME: Caltran	ns: South Oakland Maintenance Station
	PROJECT NUMBER: 575-9G	
	NORTHINGS:	EASTINGS:
	DRILLING COMPANY:	Fisch Environmental
	DRILLING METHOD:	Direct Push (Geoprobe)
	BORING DIAMETER: 2 inch	DEPTH: 20 feet
		GROUNDWATER LEVELS
	DATE	COMMENTS DEPTH BGS
	4/7/99	initial 5
	4/7/99	stabilized 5
DEPTH (FEET) SAMPLE NO. RECOVERY (IN) SAMPLE INTERVAL BLOW COUNT	DESCRIPTION	PID USCS REMARKS
Silty Ctay	with some gravel, fine grained gravel, low to	CL Asphalt surface
	asticity, brown, damp, no odor.	
'_		
2—	<u></u>	
.,		<u> </u>
3—		
1 - - 		-
<u> </u> 4		
		0 Groundwater encountered.
3— 4— 5— 6— 7—		
	·····	
7		
8		
		· · · · · · · · · · · · · · · · · · ·
9		
10 — 12		
		0
11		<u> </u>
12—		
13—		
14		
'l		
15		
		0
16—		
<u> </u>		
17—		Total Depth = 20 feet
18—		Boring drilled to sufficient depth for investiga
		Groundwater stabilized at 5 feet bgs.
19		Boring converted to temporary groundwater
22	,	monitoring well. Well grouted by removing casing and tremie
20 —		placement of neat cement.
REVIEWED BY: Tim O'Brien	LOGGED BY:	Scott Bowers

SOII	LB	O	RII	NC	S LOG					BORING NO:	B6	
					<u> </u>					SHEET 1	OF	_1
						PROJECT NAME:	Caltrans	: South C	Dakland I	Maintenance Stat	ion	
						PROJECT NUMBER:	575-9G	014		DATE:	4/7/99	
						NORTHINGS:				EASTINGS:		
						DRILLING COMPANY:				ch Environmenta	I	· · · · · · · · · · · · · · · · · · ·
						DRILLING METHOD:		Dire		(Geoprobe)		
						BORING DIAMETER:	2 inch				t0 feet	
								ROUND				
						DATE	Ì		COMM		DEP.	TH BGS
						4/7/99			initi			8
						4/7/99			stabil			8
Т			· ·			477700			Otabii	1		
חברות (רבבו)	SAMPLE NO.	RECOVERY (IN)	SAMPLE INTERVAL	BLOW COUNT	DE	SCRIPTION		PID (PPM)	USCS	RE	EMARKS	
					Silty Clay with some fine gra	ained gravel, low to			CL	Asphalt surface		
					medium plasticity, brown, d]			
_												
_				$ldsymbol{ldsymbol{ldsymbol{eta}}}$								
			1	\vdash								
_									-			
				\vdash				<u> </u>	ł	<u> </u>		<u> </u>
_			\vdash	\vdash					1			
-		17		\vdash				-	1			
-								0	1			
]			
_			广]			
_						<u> </u>]			
_				_				<u> </u>	1			
_			1	<u> </u>				ļ	4		-4 '	···
_				_				ļ	-	Groundwater encou	ntered.	
			-	 					1	<u> </u>		
-		12		\vdash				 	1			
-		"		2020				17.5	1		.	
-				\top				<u> </u>	1			
-			一	1					1	***		
-]		<u>. </u>	
_]			
_		1							1			
_	1				ļ			ļ	4			
_ !		-	_	<u> </u>					-	<u> </u>		
_	İ	L		<u> </u>	-			ļ	4			
_		21						 	1			
								0	1			
			-	+-					1	· ·		
			1	-				1	1			
_	Ì	1	-					<u> </u>	1 /	Total Depth = 20 fe	et	
_] / /	Boring drilled to suf		n for investigati
_			\prod] /	Groundwater stabil	ized at 8 fee	et bgs.
] /	Boring converted to	temporary	groundwater
_		22							↓/	monitoring well.		
_				800				0	¥	Well grouted by rer		ng and tremie
			Ш.		1	r		<u> </u>	<u> </u>	placement of neat	cement.	
VIEV	NED 8	Y: T	im C	'Brie	en	Logo	ED BY:	Scott Bo	wers			
									.			

APPENDIX C

SURVEY DATA

GENERAL NOTES:


- (1) ALL DISTANCES ARE IN DECIMAL FEET UNLESS OTHERWISE NOTED.
- IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO HAVE ALL THE UTILITIES MARKED BY THE RESPECTIVE UTILITY COMPANY PRIOR TO CONSTRUCTION.
- (3) PRIOR TO ANY DIGGING, CALL U.S.A. (1-800-642-2444) AT LEAST 48
- (4) GROUND CONDITIONS SHOWN HEREON REFLECT CONDITIONS ON THE DATE OF THE SURVEY.
- THIS MAP WAS PREPARED FOR THE EXCLUSIVE USE OF PSI ENVIRONMENTAL, INC., USE BY ANY OTHER PARTY FOR ANY PURPOSE WHATSOEVER IS PROHIBITED AND NOT WARRANTED.
- (6) ELEVATIONS SHOWN HEREON ARE TOP OF PVC PIPES AT THE NORTHERLY (PROJECT) EDGE.

Ø 32.50 9−6

(6) THIS IS NOT A BOUNDARY SURVEY.

BASIS OF ELEVATION

FOUND STANDARD CITY OF OAKLAND MONUMENT. IN THE EASTERLY SIDEWALK OF 29TH AVENUE, 5.9' SOUTHERLY OF THE SO. RAIL OF S.P.R.R., 7' EASTERLY OF THE EAST CURB OF 29TH AVENUE. EL = 26.873' NGVD'29 DATUM.



STORAGE

₹27.11

₫ 32.00

32.97 B-2

\$33.52 6-3

CALTRANS WAREHOUSE

STREET 29TH AVENUE E.12TH 07



\$ 32.41

LEGEND

TEMPORARY WELL

TEMPORARY WELL SURVEY

CALTRANS SO. OAKLAND MAINTENANCE STA. 1112 - 29TH AVENUE PSI PROJECT NO. 575-9G014 · CITY OF OAKLAND PREPARED AT THE REQUEST OF PSI ENVIRONMENTAL, INC.



MERIDIAN SURVEYING ENGINEERING, INC.

1812 UNION STREET SAN FRANCISCO 94123 (415) 440-4131

100 DRAKES LANDING #164 GREENBRAE, CA 94904 (415) 461-1241

men	DMD/PC	DATE 04/08/99
sine:	DMD	MM 194 99044
mmosso.	S70	MENTERN HOL ORIGINAL
eseme.	99044	_ 1 _ 1

APPENDIX D

LABORATORY RESULTS AND CHAIN-OF-CUSTODY RECORDS

Pace Analytical Services, Inc. 3970 Gilman St. Long Beach, CA 90815

> Tel: 562-498-9515 Fax: 562-597-0786

> > Page 1 of 6

Client Name:

PROFESSIONAL SERVICE INDUSTRIES, INC.

1320 W. WINTON AVE HAYWARD, CA 94545

Report To:

FRANK POSS

Project Name: Site Location:

CALTRANS: S. OAKLAND M.S.

PACE ANALYTICAL Project #: 6029329
PACE ANALYTICAL WO #: 14723A

Client ID #: 575-9G-014

Date:

4/26/99

Pace Analytical Services, Inc. is pleased to provide you with analytical data for your above referenced project. Samples were collected on 04/06/99 and received on 04/08/99. Please refer to the chain of custody included at the end of this report for conditions of the samples upon receipt. In accordance with the chain of custody, the samples were analyzed for the following analytical parameters:

ANALYTICAL TEST	<u>PAGE</u>
TPH-G (Soil)	2-3
TPH-D (Soil)	4-5
List of Abbreviations and Definitions	6

The analysis for 8260 was subcontracted to an outside laboratory with results attached.

Reviewed by,

Lily Bayati, Project Manager

This report pertains only to the samples investigated and does not necessarily apply to other apparently identical or similar materials. All samples are analyzed on an as received (wet weight) basis. Sampling, handling and analytical methods must be in accordance with EPA established protocols. Deviations from these protocols may compromise analytical results. All method numbers referenced are EPA method numbers except where otherwise noted. This report is submitted for the exclusive use of the client to whom it is addressed and is only valid in its entirety. ELAP certification #2310.

Pace Analytical Services, Inc. 3970 Gilman St. Long Beach, CA 90815

> Tel: 562-498-9515 Fax: 562-597-0786

Page 2 of 6 PACE ANALYTICAL Project#:6029329 PACE ANALYTICAL WO#:14723A Client ID#:575-9G-014

Analyst:

VN

Preparation Method:

5030 Soil Matrix:

ANALYSIS OF VOLATILE ORGANICS BY GAS CHROMATOGRAPHY/FID GASOLINE (TPH-G) BY DOHS METHOD

Units		TPH Gasoline µg/kg	Surrogate Recovery %	PRL µg/kg	DF
	Analysis				
Sample ID	Date				
Method Blank	04/08/99	<1000	88	1000	1
B1-5	04/08/99	<1000	81	1000	1
B1-10	04/08/99	<1000	88	1000	1
B2-5	04/08/99	<1000	88	1000	1
B2-10	04/08/99	<1000	81	1000	1
B3-5	04/08/99	<1000	87	1000	1
B3-10	04/08/99	<1 00 0	84	1000	1
B4-5	04/08/99	<1000	84	1000	1
B4-10	04/08/99	<1000	85	1000	1
B5-5	04/08/99	<1000	84	1000	1
B5-10	04/08/99	<1000	85	1000	1
B6-5	04/08/99	<1000	81	1000	1
B6-10	04/08/99	13,000	78	1000	1
B4-10 Duplicate	04/08/99	<1000	83	1000	1
B5-5 Duplicate	04/08/99	<1000	82	1000	1

Pace Analytical Services, Inc. 3970 Gilman St. Long Beach, CA 90815

> Tel: 562-498-9515 Fax: 562-597-0786

Page 3 of 6 PACE ANALYTICAL Project#:6029329 PACE ANALYTICAL WO#:14723A

QUALITY ASSURANCE/QUALITY CONTROL SUMMARY

Client ID#:575-9G-014

Analyst:

VN

Preparation Method: Matrix:

5030 Soil

ANALYSIS OF VOLATILE ORGANICS BY GAS CHROMATOGRAPHY/FID

GASOLINE (TPH-G) BY DOHS METHOD

•	Matrix Spike % REC	Matrix Spike Dup. % REC	Acceptable Range	RPD %	Acceptable Range	
Analysis Date:	04/19/99	04/19/99				
Gasoline	98	99	70-130	2.0	0-25	

REPORT OF LABORATORY ANALYSIS

Pace Analytical Services, Inc. 3970 Gilman St. Long Beach, CA 90815

> Tel: 562-498-9515 Fax: 562-597-0786

Page 4 of 6 PACE ANALYTICAL Project#:6029329 PACE ANALYTICAL WO#:14723A Client ID#:575-9G-014

Analyst: Preparation Analyst: WK WK

Matrix:

Soil

ANALYSIS OF TOTAL PETROLEUM HYDROCARBONS - DIESEL EPA 8015 Modified

·•			TPH Diesel	PRL	DF
Units			mg/Kg	mg/Kg	
	Preparation	Analysis			
Sample ID	Date	Date			
Method Blank	4/9/99	4/9/99	<10	10	1
31-5	4/9/99	4/9/99	<10	10	1
31-10	4/9/99	4/9/99	<10	10	1
32-5	4/9/99	4/9/99	<10	10	1
B2-10	4/9/99	4/9/99	<10	10	1
B3-5	4/9/99	4/9/99	<10	10	1
B3-10	4/9/99	4/9/99	<10	10	1
B4-5	4/9/99	4/9/99	<10	10	1
B4-10	4/9/99	4/9/99	<10	10	1
B5-5	4/9/99	4/9/99	<10	10	1
B5-10	4/9/99	4/9/99	<10	10	1
B6-5	4/9/99	4/9/99	<10	10	1
B6-10	4/9/99	4/9/99	<10	10	1
B1-10 Duplicate	4/9/99	4/9/99	<10	10	1
B6-5 Duplicate	4/9/99	4/9/99	<10	10	1

Pace Analytical Services, Inc. 3970 Gilman St. Long Beach, CA 90815

> Tel: 562-498-9515 Fax: 562-597-0786

Page 5 of 6 PACE ANALYTICAL Project#:6029329 PACE ANALYTICAL WO#:14723A Client ID#:575-9G-014

QUALITY ASSURANCE/QUALITY CONTROL SUMMARY

Analyst:

Matrix:

WK WK

Preparation Analyst:

Soil

ANALYSIS OF TOTAL PETROLEUM HYDROCARBONS - DIESEL EPA 8015 Modified

	Matrix Spike % REC	Matrix Spike Dup. % REC	Acceptable Range	RPD %	Acceptable Range	<u>.</u>
Analysis Date:	4/9/99	4/9/99	e.			
TPH-Diesel	118	115	61-127	2.6	0-25	

REPORT OF LABORATORY ANALYSIS

Pace Analytical Services, Inc. 3970 Gilman St. Long Beach, CA 90815

> Tel: 562-498-9515 Fax: 562-597-0786

Page 6 of 6 PACE ANALYTICAL Project#:6029329 PACE ANALYTICAL WO#:14723A Client ID#:575-9G-014

List of Abbreviations and Definitions

	SM	=	Standard Methods for the examination of water and waste water
•	EPA	=	EPA approved methodology, 40 CFR Part 136
	sw	=	EPA SW 846, Test Methods for Evaluating Solid Wastes
	TCLP	=	Toxicity Characteristic Leaching Procedure
	STLC	=	Soluble Threshold Limit Concentration
	mg/L	=	milligrams per liter, parts per million (ppm), unit of measurement for a liquid
	mg/Kg	=	milligrams per kilogram, parts per million (ppm), unit of measurement for a solid
	μg/L	=	micrograms per liter, parts per billion (ppb), unit of measurement for a liquid
	µg/Kg	=	micrograms per kilogram, parts per billion (ppb), unit of measurement for a solid
	MDL	=	Laboratory Method Detection Limit, minimum level of detection derived from actual laboratory data
	DF	=	Dilution Factor, the magnitude in which a sample must be diluted to eliminate matrix interference and/or to bring the sample concentration within the linear calibration range
	RPD	=	Relative Percent Difference, measure of precision
	% REC	=	Percent Recovery, measure of accuracy
	<	= .	less than, analyte of interest below stated numerical value
	NA	=	Not Applicable
	LCS	=	Laboratory Control Sample
	DOHS	=	Department of Health Services
	ELAP	=	Environmental Laboratory Accreditation Program
	PRL	=	Pace Reporting Limit

Centrum Analytical Laboratories, Inc.

CERTIFIED HAZARDOUS WASTE TESTING LABORATORY . CHEMICAL AND BIOLOGICAL ANALYSES

Client:

Pace Analytical

3960 E. Gilman Street

Long Beach, CA 90815

Date Sampled:

04/06/99

Date Received:

04/09/99

Job Number:

14729

Project: Caltrans: S. Oakland

CASE NARRATIVE

The following information applies to samples which were received on 04/09/99:

The samples were received at the laboratory chilled and sample containers were intact.

Unless otherwise noted below, the Quality Control acceptance criteria were met for all samples for every analysis requested.

Report approved

Robert R. Clark, Ph.D. Laboratory Director

ELAP #1184

DL: Detection Limit - The lowest level at which the compound can reliably be detected under normal laboratory conditions,

ND: Not Detected -- The compound was analyzed for but was not found to be present at or above the detection limit.

NA: Not Analyzed - Per client request, this analyte was not on the list of compounds to be analyzed for.



Client: Pace Analytical

Project: Caltrans: S. Oakland

Job No.: 14729 Matrix: Soil Analyst: JMR Date Sampled: 04/06/99
Date Received: 04/09/99

Date Analyzed: 04/12-13/99 Batch Number: 8260S1642

8260S1644

	Sample ID:	Blank	B1-5	B1-10	B2-5	B2-10	B3-5
Compounds	DL	mg/Kg	mg/Kg	mg/Kg	mg/Kg	mg/Kg	mg/Kg
Acetone	0.05	ND	ND	ND	ND	ND	ND
Benzene	- 0.001	ND	ND	ND	ND	ND	ND
Bromobenzene	0.005	ND	ND	ND	ND	ND	ND
Bromochloromethane	0.005	ND	ND	ND	ND	ND	ND
Bromodichloromethane	0.001	ND	ND	ND	ND	ND	ND
Bromoform	0.005	ND	ND	ND	ND	ND	ND
Bromomethane	0.005	ND	ND	ND	ND	ND	ND
2-Butanone (MEK)	0.01	ND	ND	ND	ND	ND	ND
n-Butylbenzene	0.002	ND	ND	ND	ND	ND	ND
sec-Butylbenzene	0.002	ND	ND	ND	ND	ND	ND
tert-Butylbenzene	0.002	ND	ND	ND	ND	ND	ND
Carbon disulfide	0.01	ND	ND	ND	ND:	ND	ND
Carbon tetrachloride	0.001	ND	ND	ND	ND	ND	ND
Chlorobenzene	0,001	ND	ND	ND	ND	ND	. ND
Chloroethane	0.005	ND	ND	ND	ND	ND	ND
Chloroform	0.002	ND	ND	ND	ND	NO	ND
Chloromethane	0.001	ND	ND	ND	ND	ND	ND
2-Chlorotoluene	0.002	ND	ND	ND	ND	ND	ND
4-Chlorotoluene	0.002	ND	ND	ND	ND	ND	ND
Dibromochloromethane	0.002	ND	ND	ND	ND	ND	ND
1,2-Dibromoethane	0.002	ND	ND	ND	ND	ND	ND
1,2-Dibromo-3-chloropropa	ine 0.01	ND	ND	ND	ND	ND	ND
Dibromomethane	0.001	ND	ND	ND	ND	ND	ND
1,2-Dichlorobenzene	0.001	ND	ND	ND	ND	ND	ND
1,3-Dichlorobenzene	0.002	ND	ND	, ND	ND	ND	ND
1,4-Dichlorobenzene	0.002	ND	ND	ND	ND	ND	ND
Dichlorodifluoromethane	0.005	ND	ND	ND	ND	ND	ND
1,1-Dichloroethane	0.001	ND	ND	ND	ND	ND	ND
1,2-Dichloroethane	0.001	ND	ND	ND	ND	ND	ND
1,1-Dichloroethene	0.005	ND	ND	ND	ND	ND	ND
cis-1,2-Dichloroethene	0.002	ND	ND	ND	ND	ND	ND
trans-1,2-Dichloroethene	0.002	ND	ND	ND	ND ND	ND	ND
1,2-Dichloropropane	0.001	ND	ND	ND	ND	ND	ND
1,3-Dichloropropane	0.001	ND	ND	ND	ND	ND	ND
2,2-Dichloropropane	0.001	ND	ND	ND	ND	ND	ND
1,1-Dichloropropene	0.001	ND	ND	ND	ND	ND	ND
cis-1,3-Dichloropropene	0.001	ND	ND	ND	ND	ND	ND
trans-1,3-Dichloropropene	0.001	ND ND	ND	ND	ON	ND	ND



Client:

Pace Analytical

Project:

Caltrans: S. Oakland

Job No.:

14729

Matrix:

Soil

Analyst: **JMR** Date Sampled:

Date Received:

04/06/99 04/09/99

Date Analyzed:

04/12-13/99

Batch Number:

8260S1642

8260S1644

	Sample ID:	Blank	B1-5	B1-10	B2-5	B2-10	B3-5
Compounds	DL	mg/Kg	mg/Kg	mg/Kg	mg/Kg	mg/Kg	mg/Kg
Ethylbenzene	0.001	ND	ND	ND	ND	ND	ND
Hexachlorobutadiene	0.001	ND	ND	ND	ND	ND	ND
2-Hexanone	0.01	ND	ND	ND	ND	ND	ND
Isopropylbenzene	0.001	ND	ND	ND	ND	ND:	ND
p-Isopropyltoluene	0.002	ND	ND	ND	ND	ND	ND
Methylene chloride	0.01	ND	ND	ND	ND	ND	ND
4-Methyl-2-pentanone	0.01	ND	ND	ND	ND	ND	ND
Methyl-tert-butyl ether (MtB	E) 0.005	ND	ND	ND	ND	ND	ND
Napthalene	0.002	ND	ND	ND	ND	ND	ND
n-Propylbenzene	0.001	ND	ND	ND	ND	ND	ND
Styrene	0.001	ND	ND	ND	ND	ND	ND
1,1,1,2-Tetrachloroethane	0.001	ND	ND	ND	ND	ND	ND
1,1,2,2-Tetrachloroethane	0.002	ND	ND	ND	ND	ND	ND
Tetrachloroethene	0.001	ND	ND	ND	ND	ND	ND
Toluene	0.001	ND	ND	ND	ND	ND	ND
1,2,3-Trichlorobenzene	0.002	ND	ND	ND	ND	ND	ND
1,2,4-Trichlorobenzene	0.002	ND	ND	ND	ND	ND	ND
1,1,1-Trichloroethane	0.001	ND	ND	ND	ND	ND .	ND
1,1,2-Trichloroethane	0.003	ND	ND	ND	ND	ND	ND
Trichloroethene	0.001	ND	ND	ND	ND	ND	ND
1,2,3-Trichloropropane	0.003	ND	ND	ND	ND	ND	ND
Trichlorofluoromethane	0.001	ND	ND	ND	ND	ND	ND
Trichlorotrifluoroethane	0.005	ND	ND	ND	ND	ND	ND
1,2,4-Trimethylbenzene	0.001	· · ND · · ·	ND	ND	ND	ND	ND
1,3,5-Trimethylbenzene	0.001	ND	ND	' ND	ND	ND	ND
Vinyl chloride	0.002	ND	ND	ND	ND	ND	ND
Xylenes (total)	0.003	ND	ND	ND	ND	ND	ND

Surrogates (% recovery) Limits: 80 - 130

	Sample ID:	Blank	B1-5	B1-10	B2-5	B2-10	B3-5
Dibromofluoromethan	e	108	107	111	107	107	104
Toluene-d8		98	98	102	99	99 -	96
Bromofluorobenzene		107	99	105	103	102	95



Client: Pace Analytical
Project: Caltrans: S. Oakland

Job No.: 14729 Matrix: Soil Analyst: JMR

 Date Sampled:
 04/06/99

 Date Received:
 04/09/99

 Date Analyzed:
 04/12-13/99

 Batch Number:
 8260S1642

8260	181	64	4

	Sample ID:	B3-10	B4-5	B4-10	B5-5	B5-10	B6-5
Compounds	DL	mg/Kg	mg/Kg	mg/Kg	mg/Kg	mg/Kg	mg/Kg
Acetone	0.05	ND	. ND	ND	ND ·	ND	ND
Benzene	0.001	ND	ND	ND	NĐ	ND	ND
Bromobenzene	0.005	ND	ND	ND .	ND	ND	ND
Bromochloromethane	0.005	ND	ND	· ND	ND	ND	ND.
Bromodichloromethane	0.001	ND	ND	ND	ND	ND	ND
Bromoform	0.005	ND	ND	ND	ND	ND	ND
Bromomethane	0.005	ND	ND	ND	ND	ND /	ND
2-Butanone (MEK)	0.01	ND	ND	ND	ND	ND	ND
n-Butyibenzene	0.002	ND	ND	ND	ND	ND	ND
sec-Butylbenzene	0.002	ND	ND	ND	ND	ND	ND
tert-Butylbenzene	0.002	ND	ND	ND	ND	ND	ND
Carbon disulfide	0.01	ND	· · · ND · · ·	ND	ND	ND .	ND
Carbon tetrachloride	0.001	ND	ND	ND	ND	ND	ND
Chlorobenzene	0.001	ND	ND	ND	ND	ND	ND
Chloroethane	0.005	ND	ND	ND	ND	ND	ND
Chloroform	0.002	ND	ND	ND	ND	ND	ND
Chloromethane	0.001	ND	ND	ND	ND	ND	ND
2-Chlorotoluene	0.002	ND	ND	ND	₩D	ND	ND
4-Chlorotoluene	0.002	ND	ND	ND	ND	ND	ND
Dibromochloromethane	0.002	ND	ND	ND	ND	ND	ND
1,2-Dibromoethane	0.002	ND	ND	ND	ND	ND	ND
1,2-Dibromo-3-chloropropa	ne 0.01	ND	ND	ND **	ND	ND	ND
Dibromomethane	0.001	ND	ND	ND	ND	ND	ND
1,2-Dichlorobenzene	0.001	ND	ND	ND	ND	ND	ND
1,3-Dichlorobenzene	0.002	ND	ND	, ND	ND	ND	ND
1,4-Dichlorobenzene	0.002	ND	ND	ND	ND	ND	ND
Dichlorodifluoromethane	0.005	ND	ND	ND	ND	ND	ND
1,1-Dichloroethane	0.001	DM	ND	ND	ND	ND	OM
1,2-Dichloroethane	0.001	ND	ND	ND	ND .	ND	ND
1,1-Dichloroethene	0.005	ND	ND	ND	ND	ND	ND
cis-1,2-Dichloroethene	0.002	ND	ND	ND	ND	ND .	ND
trans-1,2-Dichloroethene	0.002	ND	ND	ND	. ND ∞	ND	ND
1,2-Dichloropropane	0.001	ND	ND	ND	ND	ND	ND
1,3-Dichloropropane	0.001	ND	ND	ND	ND	ND	ND.
2,2-Dichloropropane	0.001	ND	ND	ND	ND	ND	ND
1,1-Dichloropropene	0.001	ND	ND	ND	ND	ND	ND
cis-1,3-Dichloropropene	0.001	ND	ND	ND	ND	ND	ND
trans-1,3-Dichloropropene	0.001	ND	ND	ND	ND	ND	ND



Client: Pace Analytical

Project: Caltrans: S. Oakland

Job No.: 14729 Matrix: Soil Analyst; JMR Date Sampled:

Batch Number:

04/06/99 04/09/99

Date Received: Date Analyzed:

04/12-13/99

8260S1642 8260S1644

	Sample ID:	B3-10	B4-5	B4-10	B5-5	B5-10	B6-5
Compounds	DL	mg/Kg	mg/Kg	mg/Kg	mg/Kg	mg/Kg	mg/Kg
Ethylbenzene	0.001	ND	ND	ND	ND	ND	ND
Hexachlorobutadiene	0.001	ND	ND .	ND	ND	ND	ND
2-Hexanone	0.01	ND	ND	ND	ND	ND	- ND
lsopropylbenzene	0.001	ND	ND	ND	ИD	ND	ND .
p-Isopropyltoluene	0.002	ND	ND	ND	ND	ND	ND
Methylene chloride	0.01	ND	ND	ND	ND	ND	ND
4-Methyl-2-pentanone	0.01	ND	ND	ND	ND	ND	ND
Methyl-tert-butyl ether (MtB	E) 0.005	ND.	ND	ND	0.16	ND	ND
Napthalene	0.002	ND	ND	ND	ND	ND	ND
n-Propylbenzene	0.001	ND	ND	ND	ND	ND	ND
Styrene	0.001	ND	ND	ND	ND	ND	ND
1,1,1,2-Tetrachloroethane	0.001	ND	ND	ND	ND	ND	. ND
1,1,2,2-Tetrachloroethane	0.002	ND	ND	ND	ND	ND	. ND
Tetrachloroethene	0.001	ND	ND	ND	МD	ND	ND
Toluene	0.001	ND	ND	ND	ND	ND	ND
1,2,3-Trichlorobenzene	0.002	ND	ND	ND	ND	ND	ND
1,2,4-Trichlorobenzene	0.002	ND	ND	ND	ND	ND	ND
1,1,1-Trichloroethane	0.001	ND	ND	ND	ND	ND	ND
1,1,2-Trichloroethane	0.003	ND	ND	ND	ND	ND	ND
Trichloroethene	0.001	ND	ND	: OM	ND	ND	ND
1,2,3-Trichloropropane	0.003	ND	ND	ND	ND	ND	ND
Trichlorofluoromethane	0.001	ND	ND	ND	. ON	ND	ND
Trichlorotrifluoroethane	0.005	ND	ND	ND	ND	ND	ND
1,2,4-Trimethylbenzene	0,001	ND	ND	ND	ИD	ND	ND
1,3,5-Trimethylbenzene	0.001	ND	ND	, ND	ND	ND	ND
Vinyl chloride	0.002	ND	ND	ND	ON	ND	ND
Xylenes (total)	0.003	ND	ND	ND	ND	ND	ND

Surrogates (% recovery) Limits: 80 - 130

Danogatos (Artedovery) Entit	113. 50 - 100					
Sample	ID: B3-10	B4-5	B4-10	B5-5	B5-10	B6-5
Dibromofluoromethane	111	100	109	104	108	106
Toluene-d8	100	98	99	101	99	98
Bromofluorobenzene	106	97	100	100	102	99



Client: Pace Analytical
Project: Caltrans: S. Oakland

Job No.: 14729 Matrix: Soil Analyst: JMR Date Sampled: 04/06/99
Date Received: 04/09/99
Date Analyzed: 04/12-13/99
Batch Number: 8260S1642
8260S1644

*	Sample ID:	B6-10	. •
Compounds	DL	mg/Kg	٠
Acetone	0.05	ND	
Benzene	0.001	ND	
Bromobenzene	0.005	ND	
Bromochloromethane	0.005	ND	
Bromodichloromethane	0.001	ND	
Bromoform	0.005	ND DIN	- 100 000 000 000
Bromomethane	0.005	ND	*
2-Butanone (MEK)	0.01	ND	- 000000000000000000000000000000000000
n-Butylbenzene	0.002	ND .	
sec-Butylbenzene	0.002	N/D	
tert-Butylbenzene	0.002	ND	
Carbon disulfide	0_01	ND	
Carbon tetrachloride	0.001	ND	
Chlorobenzene	0.001	ND	3 (2002) 38 (4
Chloroethane	0.005	ND	
Chloroform	0.002	ND	
Chloromethane	0.001	ND	
2-Chlorotoluene	0.002	ND	
4-Chiorotoluene	0.002	ND 1	.*
Dibromochloromethane	0.002	ND	. (5.5 4 69 4 9 6 6 6 . (5.5 4 69 4 9 6 6 6
1,2-Dibromoethane	0.002	ND .	
1,2-Dibromo-3-chloropropa	ane 0.01	ND	
Dibromomethane	0.001	ND	
1,2-Dichlorobenzene	0.001	ND	
1,3-Dichlorobenzene	0.002	ND `	
1,4-Dichlorobenzene	0.002	ND	
Dichlorodifluoromethane	0.005	ND	
1,1-Dichloroethane	0.001	ND	10000 COM 000 UCC
1,2-Dichloroethane	0.001	ND	
1,1-Dichloroethene	0.005	ND	essenerieden. Levenerieden
cis-1,2-Dichloroethene	0.002	ND	
trans-1,2-Dichloroethene	0.002	ND	
1,2-Dichloropropane	0.001	ND	
1,3-Dichloropropane	0.001	ND	
2,2-Dichloropropane	0.001	ND	an and decreed the
1,1-Dichloropropene	0.001	ND	
cis-1,3-Dichloropropene	0.001	ND	
trans-1,3-Dichloropropene	0.001	ND CONTRACTOR OF THE CONTRACTO	



Client: Pace Analytical
Project: Caltrans: S. Oakland

Job No.: 14729 Matrix: Soil Analyst: JMR

 Date Sampled:
 04/06/99

 Date Received:
 04/09/99

 Date Analyzed:
 04/12-13/99

 Batch Number:
 8260S1642

8260S1644

	Sample ID:	B6-10
Compounds	· DL	mg/Kg
Ethylbenzene	0.001	ND
Hexachlorobutadiene	0.001	ND
2-Hexanone	0.01	ND
Isopropyibenzene	0 001	ND
p-isopropyltoluene	0.002	ND
Methylene chloride	0.01	ND
4-Methyl-2-pentanone	0.01	ND
Methyl-tert-butyl ether (MtB	E) 0.005	ND .
Napthalene	0.002	ND
n-Propylbenzene	0.001	ND
Styrene	0.001	ND
1,1,1,2-Tetrachloroethane	0.001	ND
1,1,2,2-Tetrachloroethane	0.002	ND
Tetrachloroethene	0.001	0.003
Toluene	0.001	ND
1,2,3-Trichlorobenzene	0.002	ND
1,2,4-Trichlorobenzene	0.002	ND
1,1,1-Trichloroethane	0,001	ND
1,1,2-Trichloroethane	0.003	ND
Trichloroethene	0.001	NO
1,2,3-Trichloropropane	0.003	ND
Trichlorofluoromethane	0.001	ND
Trichlorotrifluoroethane	0.005	ND .
1,2,4-Trimethylbenzene	0.001	ND
1,3,5-Trimethylbenzene	0.001	ND * * * * * * * * * * * * * * * * * * *
Vinyl chloride	0.002	ND
Xylenes (total)	0.003	ND .

Surrogates (% recovery) Limits: 80 - 130

Sample ID:	B6-10		
Dibromofluoromethane	115		
Toluene-d8	92	et e	
IDIQITIO NUOTODGIZGIG	88		

QC Sample Report - EPA Method 8260

Matrix: Soil

Batch #: 8260S1642

Batch Accuracy Results

Sample ID: Laboratory Cont	troi Sampi	е		
Analyte	Spike Concentration mg/Kg	% Recovery LCS	Acceptance Limits % Recovery	Pass/Fail
1,1-Dichloroethene	0.020	92	59 - 172	Pass
Benzene	0.020	97	66 - 142	Pass
Trichloroethene	0.020	.97	71 - 137	Pass
Toluene	0.020	97 🎄	59 - 139	Pass
Chlorobenzene	0.020	99	60 - 133	Pass

Analytical Notes:

Batch Precision Results

MS/MSD Sample ID: B2-10)				
Analyte	Spike Sample Recovery mg/Kg	Spike Duplicate Recovery mg/Kg	Relative Percent Difference (RPD)	Upper Control Limit RPD	Pass/Fail
1,1-Dichloroethene	0.0182	0.0211	15%	22%	Pass
Benzene	0,0189	0.0217	14%	21%	Pass
Trichloroethene	0.0193	0.0210	8%	24%	Pass
Toluene	0.0184	0.0207	12%	21%	Pass
Chlorobenzene	0.0191	0.0221	15%	21%	Pass

MS: Matrix Spike Sample
MSD: Matrix Spike Duplicate

Analytical Notes:		
	•	
4 1	•	
4		
•		•
		· ·
	: '	e



QC Sample Report - EPA Method 8260

Matrix: Soil

Batch #: 8260S1644

Batch Accuracy Results

Sample ID: Laboratory (Jontrol Sample	}		
Analyte	Spike Concentration mg/Kg	% Recovery LCS	Acceptance Limits % Recovery	Pass/Fail
1,1-Dichloroethene	0.020	95	59 - 172	Pass
Benzene	0.020	99	66 - 142	Pass
Trichloroethene	0.020	96	71 - 137	Pass
Toluene	0.020	92	59 - 139	Pass
Chlorobenzene	0.020	97	60 - 133	Pass

Analytical	Notes:	<u> </u>
	.*	
٠.		
ļ		
,	**	
ľ	•	

Batch Precision Results

MS/MSD Sample ID: Laboratory Control Samples

Analyte	Spike Sample Recovery mg/Kg	Spike Duplicate Recovery mg/Kg	Relative Percent Difference (RPD)	Upper Control Limit RPD	Pass/Fail
1,1-Dichloroethene	0.0190	0.0202	6%	22%	Pass
Benzene	0.0199	0.0202	2%	21%	Pass
Trichloroethene	0.0191	0.0208	8%	24%	Pass
Toluene	0.0186	0.0194	4%	21%	Pass
Chlorobenzene	0.0195	0,0203	4%	21%	Pass

Analytical I	Notes:		
ľ			
-			
i			

MS: Matrix Spike Sample
MSD: Matrix Spike Duplicate

Centrum Analytical Laboratories, Inc.

290 TENNESSEE STREET

REDLANDS, CA 92373

(909) 798-9336 • (800) 798-9336 FAX (909) 793-1559 Chain C

Chain of Custody Record

Centrum Job #

14723A

6029329

Page 1 of 2

												Ana	lyses	s Rec	quest	:ed		29	99		
Project No.:				Project N		· C A 1.1	1 44 6	Τ.	<u>"</u>		*					T					Turn-around time
	75-9GO	<u> 14</u>		La	1 tran	<u>s: 5. Oaklan</u>	M.S.	1	Pest/PCB				i	RCR\$		8	Hex Chrome	Ì			24 Hr. RUSH*
Project Mar Fra	nager: nk Poss			Phone:	70E-	Fax: 1111 (510) 785	- 1107	1	4				χ	ı K		Conductivity	Ş				1 24 Hr. RUSH*
Client Name			{	Δddroee:			-	ιи.	i 👸		8		9	Ē				Į			Normal TAT
(Company)	PSI			1320	W.	Winton Aver, Hay	grand, CA	#	¥	12° 15°	i i		827	3	[i		Fluoride				* Requires prior approval, additional charges apply
Centrum ID (Lab use only)	Sample ID (As it should appear on report)		pled	Time sampled	Sample matrix	Site location	Containers: # and type	GCMS: 8260	8080: Pesticides PCBs	8015M: Diesel	8015M: Gasoline	418.1 (TRPH)	Semivolatiles: 8270 625	Metals: TTLC(CAM) PP	Lead Only	pH TDS TSS	Flashpoint F				Remarks/ Special Instructions
	B1-5	4/6,	99	900	5		Acctate Sleeve	X		X	X										6029329
	B1-10			915						Ш	Ц						,				602494163
	BZ-5			1215				\coprod		Ш	Ц										602494171
	BZ-10			1230				\coprod	_	Ш											602494189
	B3-5			1310			<u> </u>	\coprod	<u> </u>	Ш	\coprod						_			-	602494197
	B3-10			1320	'			\coprod			\coprod										602494205
	B4-5			1450				Ц	_		Щ							<u> </u>			602494213
	34-10	<u> </u>	<u>'</u>	1500	 		<u> </u>	\prod		Ш	\coprod										602494270
	B5-5	4/7	19	845		-		Ц			Ц	ļ									602494288
	B5-10		,	900	\V		14	V	L	V	V										602494296
Relinquished t	by; (Sampler's Signature)	_		Date: 4/7/49	1700	Relinguished by:		Date	l	Time		Tob	ж соп	nplete	d by la	aborat	tory p	ersonr —	nel:		Sample Disposal
Received by:	Sin Race		,	71849	Time	Received by:	·	Date	te Time Samples chilled?		İ	☐ Client will pick up									
The delivery of samples and the signature on this chain of custody form		stody form	Relinquished by:		Date		Time					ainers	-		Yes (J No		☐ Return to client			
	onstitutes authorization to perform the analyses specified above under		Received for Laboratory by: Date		1	Time C		Courier 5/1/PS/Fed Ex Hand carried						☐ Lab disposal fee \$5							
Laboratory f	aboratory Notes: * Include oxygenates in 8260 analysis							Sample Locator No.													
																					Ì

Centrum Job #

290 TENNESSEE STREET REDLANDS, CA 92373

(909) 798-9336 • (800) 798-9336 FAX (909) 793-1559

Chain of Custody Record

ob# 14723A
Page Z of 2

	·										Ana	ilyse:	s Re	quest	ed		2	99	q	
Project No.: 57 Project Man	5-96014		Project N Cal Phone:	ame: +rans	: S, Oakland Fax:	M, S.	2783-	Pest/PCB	1	N. S. S. S. S. S. S. S. S. S. S. S. S. S.					8	x Chrome				Turn-around time 24 Hr. RUSH*
Client Name (Company)	PSI		Address:					es PCBs	BEZ	ine seed		8270 62	(CAM) PP		Conductivity	Fluoride Hex				Normai TAT *Requires prior approval, additional charges apply
Centrum ID (Lab use only)	Sample ID (As it should appear on report)	Date sampled	Time sampled	Sample matrix	Site location	Containers: # and type	GCMS: 8260	8080: Pestiddes PCBs Pest/PCB	8015M: Diesel	8015M: Gasoline	418.1 (TRPH)	Semivolatiles: 8270 625	Metals: TTLC(CAM) PP RCRA	Lead Only	E TOS TSS	Plashpoint Fl		:		Remarks/ Special Instructions
	B6-5	4/7/99	1020	5		Acetate Sleeve	X		X	X										602494304
	B6-10	4/7/99	1030	2,		V	X		X	X										602494312
		<u> </u>	1000			/	7				<u> </u>						7			
									-							/			一	
	/		/		/	/					1-	H	-		7					
		/		 ,					7						<u> </u>				7	
								7	1				7					/		
		/					7	1		_			7							
				/		/	1		1				_							
			/																	_
Relinquished t	y: (Sampler's Signature)	<u> </u>	Date /	Time	Relinquished by:		Date		Time	<u>/-</u>	Tot	be cor	mplete	d by i	aborai	tory p	erson	nel:	<u></u>	Sample Disposal
Received by:	welim		Date 1/7/49 Date:	Time	Received by:		Date	,	Time		1	•		#7 @ Y						☐ Client will pick up
	of samples and the signature	ure on this	7/3	tody form	Relinquished by:		Date		Time		Alla	- sampl	e com	tainers	intac	t7 🗆	, Yes	□ No		☐ Return to client
constitutes a	uthorization to perform the ad Conditions set forth on t	analyses s	pecified abo	-	Received for Laboratory by:		Date	•	Time		00	Courle	r 🗆 (UPS/F	ed Ex	- - 1	land o	arried		(1 Lab disposal fee \$5
Laboratory f	Votes: XI	ncli	vlo_	οκγ	genates in	826	0	,	an	al	ysi	ìs.				••				Sample Locator No.

Pace Analytical Services, Inc. 3970 Gilman St. Long Beach, CA 90815

> Tel: 562-498-9515 Fax: 562-597-0786

> > Page 1 of 6

Client Name:

PROFESSIONAL SERVICE INDUSTRIES, INC.

1320 W. WINTON AVE HAYWARD, CA 94545

Report To:

FRANK POSS

Project Name: Site Location:

CALTRANS: S. OAKLAND M.S.

PACE ANALYTICAL Project #: 6029331

PACE ANALYTICAL WO #: 14738A

Client ID #: 575-9G-014

Date:

4/30/99

Pace Analytical Services, Inc. is pleased to provide you with analytical data for your above referenced project. Samples were collected on 04/08/99 and received on 04/09/99. Please refer to the chain of custody included at the end of this report for conditions of the samples upon receipt. In accordance with the chain of custody, the samples were analyzed for the following analytical parameters:

ANALYTICAL TEST	<u>PAGE</u>
TPH-G (Water)	2-3
TPH-D (Water)	4-5
List of Abbreviations and Definitions	6

The analysis for 8260 was subcontracted to an outside laboratory with results attached.

Lily Bayati, Project Manager

This report pertains only to the samples investigated and does not necessarily apply to other apparently identical or similar materials. All samples are analyzed on an as received (wet weight) basis. Sampling, handling and analytical methods must be in accordance with EPA established protocols. Deviations from these protocols may compromise analytical results. All method numbers referenced are EPA method numbers except where otherwise noted. This report is submitted for the exclusive use of the client to whom it is addressed and is only valid in its entirety. ELAP certification #2310.

Pace Analytical Services, Inc. 3970 Gilman St. Long Beach, CA 90815

> Tel: 562-498-9515 Fax: 562-597-0786

Page 2 of 6 PACE ANALYTICAL Project#:6029331 PACE ANALYTICAL WO#:14738A Client ID#:575-9G-014

Analyst:

VN

Preparation Method: Matrix:

5030

Water

ANALYSIS OF VOLATILE ORGANICS BY GAS CHROMATOGRAPHY/FID GASOLINE (TPH-G) BY DOHS METHOD

Units	V19445	TPH Gasoline µg/L	Surrogate Recovery %	PRL µg/L	DF
Sample ID	Analysis Date				
Method Blank	04/16/99	<500	106	500	1
WB1	04/16/99	<500	108	500	1
WB2	04/16/99	<500	105	500	1
WB3	04/16/99	520	130	500	1
WB4	04/16/99	520	136	500	1
WB5	04/16/99	<500	87	500	1
WB6	04/16/99	<500	98	500	1

Pace Analytical Services, Inc. 3970 Gilman St. Long Beach, CA 90815

> Tel: 562-498-9515 Fax: 562-597-0786

Page 3 of 6 PACE ANALYTICAL Project#:6029331 PACE ANALYTICAL WO#:14738A

QUALITY ASSURANCE/QUALITY CONTROL SUMMARY

Client 1D#:575-9G-014

Analyst:

VN

Preparation Method:

5030

Matrix:

Water

ANALYSIS OF VOLATILE ORGANICS BY GAS CHROMATOGRAPHY/FID GASOLINE (TPH-G) BY DOHS METHOD

	Matrix Spike % REC	Matrix Spike Dup. % REC	Acceptable Range	RPD %	Acceptable Range	
Analysis Date:	04/16/99	04/16/99				
Gasoline	95	95	70-130	0.0	0-25	

REPORT OF LABORATORY ANALYSIS

Pace Analytical Services, Inc. 3970 Gilman St. Long Beach, CA 90815

> Tel: 562-498-9515 Fax: 562-597-0786

Page 4 of 6 PACE ANALYTICAL Project#:6029331 PACE ANALYTICAL WO#:14738A Client ID#:575-9G-014

Analyst: Preparation Analyst: WK WK

Matrix:

Water

ANALYSIS OF TOTAL PETROLEUM HYDROCARBONS - DIESEL EPA 8015 Modified

-					
			Dieşel	PRL	DF
Units			mg/L	mg/L	
	Preparation	Analysis			
Sample ID	Date	Date			
Method Blank	4/16/99	4/16/99	<10	10	1
WB1	4/16/99	4/16/99	<10	10	1
WB2	4/16/99	4/16/99	<10	10	1
WB3	4/16/99	4/16/99	<10	10	1
WB4	4/16/99	4/16/99	<10	10	1
WB6	4/16/99	4/16/99	<10	10	1

This report shall not be reproduced, except in full, without the written consent of Pace Analytical Services, Inc.

Pace Analytical Services, Inc. 3970 Gilman St. Long Beach, CA 90815

> Tel: 562-498-9515 Fax: 562-597-0786

Page 5 of 6
PACE ANALYTICAL Project#:6029331
PACE ANALYTICAL WO#:14738A
Client ID#:575-9G-014

QUALITY ASSURANCE/QUALITY CONTROL SUMMARY

Analyst: Preparation Analyst: WK WK

Matrix:

Water

ANALYSIS OF TOTAL PETROLEUM HYDROCARBONS - DIESEL EPA 8015 Modified

	Matrix Spike % REC	Matrix Spike Dup. % REC	Acceptable Range	RPD %	Acceptable Range
Analysis Date:	4/16/99	4/16/99			
TPH-Diesel	106	104	61-127	1.9	0-25

Pace Analytical Services, Inc. 3970 Gilman St. Long Beach, CA 90815

> Tel: 562-498-9515 Fax: 562-597-0786

Page 6 of 6 PACE ANALYTICAL Project#:6029331 PACE ANALYTICAL WO#:14738A Client ID#:575-9G-014

List of Abbreviations and Definitions

	SM	=	Standard Methods for the examination of water and waste water
•	EPA	=	EPA approved methodology, 40 CFR Part 136
	sw	=	EPA SW 846, Test Methods for Evaluating Solid Wastes
	TCLP	=	Toxicity Characteristic Leaching Procedure
	STLC	=	Soluble Threshold Limit Concentration
	mg/L	=	milligrams per liter, parts per million (ppm), unit of measurement for a liquid
	mg/Kg	=	milligrams per kilogram, parts per million (ppm), unit of measurement for a solid
	μg/L	=	micrograms per liter, parts per billion (ppb), unit of measurement for a liquid
	μg/Kg	=	micrograms per kilogram, parts per billion (ppb), unit of measurement for a solid
	MDL	=	Laboratory Method Detection Limit, minimum level of detection derived from actual laboratory data
	DF	=	Dilution Factor, the magnitude in which a sample must be diluted to eliminate matrix interference and/or to bring the sample concentration within the linear calibration range
	RPD	=	Relative Percent Difference, measure of precision
	% REC	=	Percent Recovery, measure of accuracy
	<	=	less than, analyte of interest below stated numerical value
	NA	=	Not Applicable
	LCS	=	Laboratory Control Sample
	DOHS	=	Department of Health Services
	ELAP	=	Environmental Laboratory Accreditation Program
	PRL	=	Pace Reporting Limit

REPORT OF LABORATORY ANALYSIS

Centrum Analytical Laboratories, Inc.

CERTIFIED HAZARDOUS WASTE TESTING LABORATORY . CHEMICAL AND BIOLOGICAL ANALYSES

Client:

Pace Analytical

3960 E. Gilman Street

Long Beach, CA 90815

Date Received:

Date Sampled:

04/06/99

04/09/99

Job Number:

14730

Project: Caltrans: S. Oakland

CASE NARRATIVE

The following information applies to samples which were received on 04/09/99:

The samples were received at the laboratory chilled and sample containers were intact.

Unless otherwise noted below, the Quality Control acceptance criteria were met for all samples for every analysis requested.

Report approved

Rebert R. Clark, Ph.D. Laboratory Director

ELAP #1184

DL: Detection Limit - The lowest level at which the compound can reliably be detected under normal laboratory conditions.

ND: Not Detected - The compound was analyzed for but was not found to be present at or above the detection limit.

NA: Not Analyzed -- Per client request, this analyte was not on the list of compounds to be analyzed for.



Client:

Pace Analytical

Project:

Caltrans: S. Oakland

Job No.:

14730

Matrix:

Water JMR

Analyst:

Date Sampled:

04/06/99

Date Received:

04/09/99

Date Analyzed:

04/12-13/99

satcn	Number:	8260771641
	and the second second	

	Sample ID:	Blank	WB1	WB2	WB3	WB4	WB5
Compounds	DL	μ g/L	μg/L	μg/L	μg/L	μg/L	μg/L
Acetone	50	ND	ND	ND	ND	ND	ND
Benzene	0.5	ND	ND	ND	6,3	ND	ND
Bromobenzene	1.0	ND	ND	ND	ND	ND	ND
Bromochloromethane	1.0	ND	ND	ND	ND	ND	ND
Bromodichloromethane	0.5	ND	ND	ND	ND	ND	ND
Bromoform	0:5	ND	ND	ND	ND	ND	ND
Bromomethane	0.5	ND	ND	ND	ND	ND	ND
2-Butanone (MEK)	10	ND	ND	ND	ND	ND	ND
n-Butylbenzene	0.5	ND	ND	ND	ND	ND .	ND
sec-Butylbenzene	0,5	ND	ND	ND	ND	ND	ND
tert-Butylbenzene	0.5	ND	ND	ND	ND	ND	ND
Carbon disulfide	10	ND	ND	ND	ND	ND	ND
Carbon tetrachloride	0.5	ND	ND	ND	ND	ND -	ND
Chlorobenzene	0.5	ND	ND	ND	ND	ND	ND
Chloroethane	0.5	ND	ND	ND	ND	ND	ND
Chloroform	0.5	NĐ	ND	ND	ND	2.4	ND
Chloromethane	0.5	ND	ND	ND	ND	ND	ND
2-Chlorotoluene	0.5	ND	ND	ND	ND	ND.	ND
4-Chlorotoluene	0.5	ND	ND	ND	ND	ND	ND
Dibromochloromethane	0,5	NO	ND	ND	ND	ND	ND
1,2-Dibromoethane	0.5	ND	ND	ND	ND	ND	ND
1,2-Dibromo-3-chloropropa	ne 10	ND	ND	ND	ND	ND	ND
Dibromomethane	0.5	ND	ND	ND	ND	ND	ND
1,2-Dichlorobenzene	0.5	ND	ND	ND	ND	ND	ND
1,3-Dichlorobenzene	0.5	ND	ND	, ND	ND	ND	ND
1,4-Dichlorobenzene	0.5	ND	ND	ND	ND	ND	· ND
Dichlorodifluoromethane	0,5	ND	ND	ND	ND	ND	ND
1,1-Dichloroethane	0.5	ND	ND	ND	ND	ND	ND
1,2-Dichloroethane	0.5	ND	ND	ND	ND	ND	ND
1,1-Dichloroethene	0.5	ND	ND	ND	ND	ND .	ND
cis-1,2-Dichloroethene	0.5	ND	ND	ND	ND	ND	ND
trans-1,2-Dichloroethene	0.5	ND	ND	ND	ND	ND	ND
1,2-Dichloropropane	0.5	ND	ND	ND	ND	ND	ND
1,3-Dichloropropane	0.5	ND	ND	ND	ND	ND	ND
2,2-Dichloropropane	0.5	ND	ND	ND	ND	ND	ND
1,1-Dichloropropene	0.5	ND	ND	ND	ND	ND	ND
cis-1,3-Dichloropropene	0.5	ND	ND	ND	ND	ND	ND
trans-1 3-Dichloropropene	0.5	ND	ND	ND	ND	ND	ND



Client: Pace Analytical
Project: Caltrans: S. Oakland

Job No.: 14730 Matrix: Water Analyst: JMR Date Sampled:

04/06/99

Date Received:

04/09/99

Date Analyzed: Batch Number: 04/12-13/99 8260W1641

	Sample ID:	Blank	WB1	WB2	WB3	WB4	WB5
Compounds	DL	. µg/L_	μg/L	μg/L	μg/L	μg/ L	μg/L
Ethylbenzene	0.5	ND	ND	ND	11	3.7	ND
Hexachlorobutadiene	0.5	ND	ND	ND	ND	ND	ND
2-Hexanone	10	ND	ND	ND	ND	ND	ND
lsopropylbenzene	0.5	ND	ND	ND	1,8	1.3	ND
p-Isopropyltoluene	0.5	ND	ND	ND	ND	ND	ND
Methylene chloride	10	ND	ND	ND	ND	ND	ND
4-Methyl-2-pentanone	5.0	ND	ND	ND	ND	.ND	ND
Methyl-tert-butyl ether (MtB	3E) 1.0	ND	ND	ND	ND	ND	6,600
Napthalene	0.5	ND	ND	ND	3,5	2.6	ND
n-Propylbenzene	0.5	ND	ND	ND	5.4	3.0	ND:
Styrene	0.5	ND	ND	ND	ND	ND	ND
1,1,1,2-Tetrachloroethane	0.5	ND	ND	ND	ND	ND	ND
1,1,2,2-Tetrachloroethane	1.0	ND	ND	ND	ND	ND	ND
Tetrachioroethene	0.5	MD	ND	ND	ND	ND	ND
Toluene	0.5	ND	ND	ND	2.2	ND	0.6
1,2,3-Trichlorobenzene	0.5	ND	ND	ND	ND	ND	ND
1,2,4-Trichlorobenzene	0,5	ND	ND	ND	ND	ND	ND
1,1,1-Trichloroethane	0.5	ND	ND	ND	ND	ND	ND
1,1,2-Trichloroethane	0,5	ND	ND	ND	ND	ND	ND
Trichloroethene	0.5	ND	ND	ND	ND	ND	ND
1,2,3-Trichloropropane	0.5	ND	ND	ND	ND	ND	ND
Trichlorofluoromethane	0.5	ND	ND	ND	ND	ND	ND
Trichlorotrifluoroethane	5.0	ND	ND	ND	ND	ND	ND
1,2,4-Trimethylbenzene	0.5	ND	ND	ND	31	19	ND
1,3,5-Trimethylbenzene	0.5	ND	ND	、 ND	12	6.3	ND
Vinyl chloride	0.5	ND	ND	ND	ND	ND	ND
Xylenes (total)	1.5	ND	2.0	ND	40	7.7	ND

Surrogates (% recovery) Limits: 80 - 130

	Sample ID:	Blank	WB1	WB2	WB3	WB4	WB5
Dibromofluoromethane		108	100	105	108	107	105
Toluene-d8		98	95	101	99	98	100
Bromofluorobenzene		107	102	102	96	110	101



Client: Pace Analytical
Project: Caltrans: S. Oakland

Job No.: 14730 Matrix: Water Analyst: JMR

 Date Sampled:
 04/06/99

 Date Received:
 04/09/99

 Date Analyzed:
 04/12-13/99

 Batch Number:
 8260W1641

	Sample ID:	WB6	. ,		1,1				
Compounds	DL	μ g/ L				1.	4		100
Acetone	50	ND							
Benzene	0,5	ND						*	
Bromobenzene	1.0	ND	1						
Bromochloromethane	1.0	ND :	a Polita atomo	a kad Nesh agea. Sala Shibbasan				usanser utensati dis Sur desta abadeas	
Bromodichloromethane	0.5	ND		and the second s		and the second s	*		
Bromoform	0.5	ND			. 2 10 10 10 10 10 10 10 10 10 10 10 10 10			ig nach nord in de lig Gedaroù one in in	ópskalatoka Rukska akua
Bromomethane	0.5	ND			A confineration			-	
2-Butanone (MEK)	10	ND							
n-Butylbenzene	0.5	ND				· · · · · · · · · · · · · · · · · · ·			
sec-Butylbenzene	0,5	ND			3 /4/ 60 60 80 50 10 10 6 / 1 2 8 60 80 80 10 10 10 10 10 10 10 10 10 10 10 10 10	0.0000000000000000000000000000000000000			
tert-Butylbenzene	0.5	ND							
Carbon disulfide	10		V						
Carbon tetrachloride	0.5	ND							
Chlorobenzene	0.5	ND							
Chloroethane	0.5	ND							
Chloroform	0.5	2.7				. 406. 20. 20. 20. 20. 20.		ng i galakkar riby: Marajan	
Chloromethane	0.5	ND							,
2-Chlorotoluene	0.5	ND					6 x 13 0x 0 00 x 000 0x 00 00 00 00 00 00 00 00 00 00 00		
4-Chlorotoluene	0.5	ND				***************************************			
Dibromochloromethane	0,5	ND							
1,2-Dibromoethane	0.5	ND		-	,				
1,2-Dibromo-3-chloropropa	ine 10	ND							onine sieno e on Sistema e onine Sistema e onine
Dibromomethane	0.5	ND							
1,2-Dichlorobenzene	0.5	ND	A1150 050 30 000 C044 500 05000	803000000000000000000000000000000000000	. + 189 89000 9 80 . A. 00 8800 808 00	10000000 colo 33 45 45 10000 - No. 30 4 5 5 5 5	san y mnodkiča. Hana i koznača	Salaka kitabur Alakatan	egen propor Ordan Socia
1,3-Dichlorobenzene	0.5	ND							and an incident and the street
1,4-Dichlorobenzene	0.5	ND					add i dagarrain ag Johann Grander (19		
Dichlorodifluoromethane	0.5	ND			*				
1,1-Dichloroethane	0.5	ND:) 	vad (0. 600 v. 60
1,2-Dichloroethane	0.5	ND							
1,1-Dichloroethene	0.5	ND	y. Colodoperation			3300000	88 : 57 : 88 : 53 :	80.900 00 00 V	
cis-1,2-Dichloroethene	0.5	ND		action of the test of	and the second second second	The state of the s	· · · · · · · · · · · · · · · · · · ·	****	
trans-1,2-Dichloroethene	0,5	ND						egnes december Kanadansk blade	6000000 61 000 80 50 50 60 60
1,2-Dichloropropane	0.5	ND							
1,3-Dichloropropane	0.5	ND		an 72 mene age ye Punun Xearesian A			egendek i Terribada b Parteka Sabarasa		
2,2-Dichloropropane	0,5	ND	and the state of the state of			e i i i i i i i i i i i i i i i i i i i	gravitation of the property of		a a service of the service of
1,1-Dichloropropene	0.5	ND			48888		884 (C. 203.050).		
cis-1,3-Dichloropropene	0.5	ND		outur uterbiili	a a a ang magantantan iya i		summer un sum notal seut (1967)	nach nach an such at a 1990	on ones X
trans-1,3-Dichloropropene	0.5	ND						\$24598534854	



Client: Pace Analytical
Project: Caltrans: S. Oakland

Job No.. 14730 Matrix: Water Analyst: JMR Date Sampled: Date Received:

04/06/99 04/09/99 04/12-13/99

Date Analyzed: Batch Number:

8260W1641

<u> </u>	Sample ID:	WB6	
Compounds	DL	μg/L	
Ethylbenzene	0.5	ND	
Hexachlorobutadiene	0.5	ND	
2-Hexanone	10	ND	
lsopropylbenzene	0.5	ND	
p-isopropyitoluene	0.5	ND	
Methylene chloride	10	ND	
4-Methyl-2-pentanone	5.0	ND	
Methyl-tert-butyl ether (MtB	E) 1.0	24	
Napthalene	0.5	ND	
n-Propylbenzene	0.5	ND	
Styrene	0.5	ND	
1,1,1,2-Tetrachloroethane	0.5	ND	
1,1,2,2-Tetrachloroethane	1.0	ND	
Tetrachloroethene	0.5	12	
Toluene	0.5	0.6	
1,2,3-Trichlorobenzene	0.5	ND	
1,2,4-Trichlorobenzene	0.5	ND	
1,1,1-Trichloroethane	0.5	ND	
1,1,2-Trichloroethane	0.5	ND	
Trichloroethene	0.5	ND	
1,2,3-Trichloropropane	0.5	ND	
Trichlorofluoromethane	0.5	ND	
Trichlorotrifluoroethane	5.0	ND	
1,2,4-Trimethylbenzene	0.5	ND	
1,3,5-Trimethylbenzene	0.5	ND	· · · · · · · · · · · · · · · · · · ·
Vinyl chloride	0.5	ND	
Xylenes (total)	1.5	ND	

Surrogates (% recovery) Limits: 80 - 130

	Sample	ID:	WB6									
Dibromofluoromethane		4130	109	1. 13	- Paradistria extant			6046000		1		
Toluene-d8			98									
Bromofluorobenzene	<u>i. 19</u>	UTBB	103	1.1 + 85.1 1.1 -	- 1. 20 mm m m m m m m m m m m m m m m m m m	200 mg - 1 mg - 1	620,600 (1) 620,600 (1)	stagnasturi Laboritada - 1 Laboritada - 1	.12022011 1227551	241,0000010 31 (10,00000		

QC Sample Report - EPA Method 8260

Matrix: Water

Batch #: 8260W1641

Batch Accuracy Results

Sample ID:	Laboratory	Control	Sample
------------	------------	---------	--------

Analyte	Spike Concentration µg/L	% Recovery LCS	Acceptance Limits % Recovery	Pass/Fail
1,1-Dichloroethene	20.0	92	59 - 172	Pass
Benzene	20.0	97	66 - 142	Pass
Trichloroethene	20.0	97	71 - 137	Pass
Toluene	20.0	97	59 - 139	Pass
Chlorobenzene	20.0	99	60 - 133	Pass

Analytical Notes:

Batch	Precision	Results

MS/MSD Sample ID: Laboratory Control Sample

Analyte	Spike Sample Recovery µg/L	Spike Duplicate Recovery µg/L	Relative Percent Difference (RPD)	Upper Control Limit RPD	Pass/Fail
1,1-Dichloroethene	18.3	19.1	4%	22%	Pass
Benzene	19.5	21.4	9%	21%	Pass
Trichloroethene	19.4	20.8	7%	24%	Pass
Toluene	19.5	20.5	5%	21%	Pass
Chlorobenzene	19.8	21.6	9%	21%	Pass

MS: Matrix Spike Sample MSD: Matrix Spike Duplicate

Analytical N	otes:	

Centrum Analytical Laboratories, Inc.

Centrum Job #

602933/

290 TENNESSEE STREET REDLANDS, CA 92373

(909) 798-9336 • (800) 798-9336 FAX (909) 793-1559

Chain of Custody Record

Page____of___

											Anal	yses	Req	uest	ed				
	ack Poss		Project N Cal Phone: (510) Address: (320)	ame: trans 785. W. h	: S. Oakland M -1111 (510) 785 Into the Haywar	, S. -119Z (LA 149	0 <u>8540 0018 634</u> 2	8080: Pesticides PCBs Pest/PCB	8015M: Diesel Fuel Screen	soline 8020 CHENTER	£	ns: 8270 625	C(CAM) PP RCRA		pH TDS TSS Conductivity COD	Fluoride Hex Chrome			Turn-around time 24 Hr. RUSH* 48 Hr. RUSH* Normal TAT Requires prior approval additional charges apply
Centrum ID (Lab use only)	Sample ID (As it should appear on report)	Date sampled	Time sampled	Sample matrix	Site location	Containers: # and type	GCIMS: 8260	8080: Pesti	8015M: Die	8015M: Gasoline	118.1 (TRPH)	Serrivolatiles: 8270	Metals: TTLC(CAM)	Lead Only	n som Hq	Flashpoint			Remarks/ Special Instructions
	MB)	4/8/99	855	W		5- VOAS 1-1LAML	X		X	X									602 494 353
	WBZ		915	1					\times										602494361
	WB3		1015						X										602494379
	W B4		1030			- V n 50			X	1				7.					602494387
	W B5		1100			4-Vons													602494486
	WB6		1148	V		5-Voas 1-11 Ambir	. 🗸		X										602494494
											,								,
·																			
										٠.									
Relinguished by	y: (Sampler's Signature)		Date 4/8/99	Time 1700	Relinquished by Pace		Date 4	ila 1	∏me £	180	. To be completed by laboratory personnel:							Sample Disposal	
Received by:			Date	Time	Received 6.		Date Time		r ·							10	_	☐ Client will pick up	
The delivery of samples and the signature on this chain of custody form constitutes authorization to perform the analyses specified above under the Terms and Conditions set forth on the back hereof.		Relinquished by:		Date Time		•	Custody seals? X Yes No All sample containers intact? Xes No					☐ Return to client							
		ve under	Received for Laboratory by:		Date		Time		□ Co	ourler	×ψ	PS/Fe	ed Ex	□ H	and ca	ırried	Lab disposal fee \$5		
Laboratory Notes:				•											Sample Locator No.				