

November 28, 2012

Roya C. Kambin Project Manager Marketing Business Unit Chevron Environmental Management Company 6101 Bollinger Canyon Road San Ramon, CA 94583 Tel (925) 790-6270 RKambin@chevron.com

RECEIVED

8:20 am, Nov 29, 2012

Alameda County Environmental Health

Alameda County Health Care Services Agency Environmental Health Services Environmental Protection 1131 Harbor Bay Parkway, Suite 250 Alameda, California 94502-6577

Re: Chevron Facility No. 351645 (Former Unocal Service Station No. 1156)

4276 MacArthur Boulevard, Oakland, California

ACEH Fuel Leak Case No. RO0000409 RWQCB Case No. 01-2474 GeoTracker Global ID T0600102279

I have reviewed the attached *Work Plan for Limited Site Assessment*, dated November 28, 2012.

I agree with the information and recommendations presented in the referenced report. The information in this report is accurate to the best of my knowledge and all local Agency/Regional Board guidelines have been followed. This report was prepared by AECOM, upon whose assistance and advice I have relied.

This letter is submitted pursuant to the requirements of California Water Code Section 13257(b)(1) and the regulating implementation entitled Appendix A pertaining thereto.

I declare under penalty of perjury that the foregoing is true and correct to the best of my knowledge.

Sincerely,

Roya Kambin Project Manager

Rogella

Attachment: Work Plan for Limited Site Assessment



Work Plan for Limited Site Assessment

Environment



Former Unocal Station No. 1156 (Chevron Facility 351645) 4276 MacArthur Boulevard Oakland, California

ACEH Case No. RO409 RWQCB Case No. 01-2474

Prepared by: AECOM Camarillo, California November 28, 2012

Work Plan for Limited Site Assessment

Former Unocal Station No. 1156 (Chevron Facility 351645) 4276 MacArthur Boulevard Oakland, California

ACEH Case No. RO409 RWQCB Case No. 01-2474

Prepared by:

Bryan Elder Project Engineer

Reviewed by:

Brenda Evans Project Manager Carmen Caceres-Schnell, P.G.

Project Geologist

i

Contents

1.0	Introduction					
	1.1	1.1 Objectives				
	1.2	1- 1				
	1.3	Site Lo	ocation and Description	1-2		
	1.4 History					
	1.5	Geolo	gy/Hydrogeology	1-3		
2.0	Pro	posed (Scope of Work	2-1		
	2.1	2-1				
	2.2	Field A	Activities	2-1		
		2.2.1	Unknown Vault Investigation			
		2.2.2	Soil Borings and Soil Sampling	2-2		
		2.2.3	Groundwater Monitoring Well Installation	2-3		
		2.2.4	Groundwater Monitoring Well Development and Survey	2-3		
		2.2.5	Laboratory Analysis	2-3		
		2.2.6	Investigation-Derived Wastes	2-4		
3.0	Rep	orting.		3-1		
4.0	Refe	erences	s	4-1		

Appendices

Appendix A – Figures

- 1 Site Location Map
- 2 Site Plan
- 3 Sewer Cleanout/Vault Photographs
- 4 Proposed Monitoring Well Construction Diagram

Appendix B - Conceptual Site Model

Appendix C – Standard Operating Procedures

1.0 Introduction

On behalf of Chevron Environmental Management Company, for itself and as Attorney-in-Fact for Union Oil Company of California (hereinafter "EMC"), AECOM is pleased to submit this Work Plan for Limited Site Assessment. AECOM has prepared this work plan in association with Alameda County Environmental Health (ACEH) Case No. RO409, for Unocal Service Station No. 1156 (Chevron Site 351645), located at 4276 MacArthur Boulevard, Oakland, California (see **Appendix A – Figures 1 and 2**).

1.1 Objectives

AECOM has reviewed and evaluated available data for the site and prepared a Conceptual Site Model (CSM; attached as **Appendix B**). Based on this evaluation, the following data gaps were identified.

- The horizontal soil and groundwater impacts in vertically isolated water-bearing zones (if any) less than 20 feet below ground surface (bgs) have not been sufficiently evaluated to determine potential down-gradient migration of source zone residual impacts (e.g., the former underground storage tanks [USTs]).
- The nature of the previously "unidentified underground concrete vault" (that appears to be a sewer cleanout rather than a "vault") has not been sufficiently determined. Therefore, whether the structure is a source of elevated petroleum hydrocarbons detected in soil, soil vapor, and groundwater in the area of former monitoring well MW-1 has not been evaluated.
- Soil vapor impacts associated with the site, and the potential for soil vapor intrusion to the
 adjacent Oakland Veterinary Hospital, has not been sufficiently assessed. Additional
 assessment has been proposed (AECOM 2012) and approved by the ACEH (2012). This
 assessment will be completed following execution of an access agreement with the property
 owner.

The proposed scope of work will focus on soil boring and monitoring well installation and investigation of the "vault".

1.2 Rationale for Proposed Scope of Work

Current groundwater concentrations from on-site monitoring wells (MW-1B to MW-4B) represent a discrete interval (i.e., 20 to 25 feet bgs) of a permanent saturated zone. Groundwater in this zone is under significant hydrostatic pressure, with minimal hydrocarbon impacts. Groundwater concentrations collected from previously abandoned on-site monitoring wells (MW-1 to MW-4) screened over a much larger interval (5 to 25 feet bgs) were significantly higher than current concentrations. These former wells likely allowed groundwater confined to the permanent saturated zone (under pressure) to saturate the upper vadose layers, mobilizing soil impacts and, thus, contributing to higher dissolved-phase concentrations in the former wells. The current scope of work will focus on installing six shallow groundwater monitoring wells on site to determine what discrete groundwater zones may exist above the known permanent groundwater zone below 20 feet bgs.

In addition, site assessment activities will include further investigation of the previously identified "unknown vault" located near the northern boundary of the site. This "vault" was previously investigated by Delta in 2009 and 2010, during which it was described to appear to be a "sewer

cleanout". Delta reported that they were "unable to open and better identify the structure" based on "the age and deterioration of the cleanout cap". To further assess the structure, Delta employed ground penetrating radar (GPR) to identify utility lines running to and from this "cleanout". A line running from the restroom area of the building to the "cleanout" was identified, but no other lines were identified. No details regarding the materials, size, etc., for the cleanout, were provided in Delta's reports, except that the "vault" appeared to be filled with sand, and the bottom could not be determined beyond 2 feet bgs.

AECOM visited the site on November 16, 2012, and visually inspected the "unknown vault" by removing the surface lid. What appeared to be a typical sewer cleanout pipe and cap (approximately 4-inch-diameter) was observed within an approximately 8-inch-diameter casing (see photograph provided in **Appendix A – Figure 3**). There are bindings on the "plastic" (non-metal) piping holding the metal cap in place. No odors were noted and no hydrocarbons were detected with the photoionozation detector (PID). No other potential sewer cleanouts were found on site. The primary utility corridor for the site is located along MacArthur Boulevard. Typical sewer construction would indicate that this "unknown vault" is the station's sewer cleanout. The surface grade at the cleanout is at an approximately 4- to 5-foot higher elevation than MacArthur Boulevard. Therefore, based on the "plastic" nature of the piping, and that it is likely buried up to 10 feet bgs, it is not surprising that GPR did not detect a line running from the cleanout toward MacArthur Boulevard. AECOM plans to further investigate the vault and associated piping.

1.3 Site Location and Description

The site is located in an urbanized area of Oakland at the base of the San Leandro Hills. The station site is located at the north corner of the intersection between MacArthur Boulevard and High Street in Oakland (see **Figures 1 and 2**).

The site area consists of mixed commercial and residential development. The Oakland Veterinary Hospital borders the site to the northwest, beyond which is a pharmacy/drug store. Single-family dwellings border the station site to the northeast. An apartment building and commercial businesses (cleaners, tax service, pizza place, and sandwich shop) are present across High Street to the southeast. A vacant lot is located south of the station site at the south corner of the MacArthur Boulevard and High Street intersection. A vacant lot is also located across MacArthur Boulevard to the southwest of the station site.

Based on site survey data (Morrow Surveying 2010), surface elevations at the site range from 179.42 feet above mean sea level (amsl) at MW-4B to 173.99 feet amsl at MW-2B. Observations during the area reconnaissance on March 15, 2012, further revealed that the elevation at the northeast site boundary is noticeably higher than at MW-4B. Additionally, the elevation at MW-5 is 169.67 feet amsl. MW-5 is located in the street in front of the Oakland Veterinary Hospital (adjacent to the northwest of the station site). To summarize, the southwest portion of the station site is at least 8 feet lower in elevation than the northeast portion; and the west corner is approximately 4 feet lower in elevation than the south corner.

1.4 History

A review of historical aerial photographs, city directories, and Sanborn fire insurance maps indicate that the site has been in use as a gasoline service station since at least 1950. The 1950 Sanborn map indicates that MacArthur Boulevard was formerly known as Hopkins. Aerial photographs and Sanborn maps indicate that the station underwent a complete remodel in 1965/1966. Earlier Sanborn maps indicate that dwellings were formerly present on site. Copies of the Sanborn maps were previously

provided with the *Revised Work Plan for Vapor Intrusion Investigation and Risk Assessment*, dated August 27, 2012.

A site map with historical sampling locations is included as **Figure 2**. Historical information provided in previously prepared reports (Miller Brooks Environmental 2004; ATC 2005; Delta 2007b, 2008a, 2009, 2010) is summarized below.

Historical information provided in previously prepared reports indicates investigative activities have been conducted at the site from 1997 through 2010. The investigations have included the drilling of numerous soil borings, installation of 12 groundwater monitoring wells, four of which (MW-1 through MW-4) have been abandoned, and several soil vapor assessments.

The most recent investigative activities were conducted by Delta Consultants in 2010 and included soil vapor point sampling, soil vapor well installation and sampling, monitoring well abandonment and re-installation, soil and groundwater borings, and assessment of a previously unidentified underground vault/utility. The investigations were conducted to determine if a pathway existed between the former gasoline UST pit and MW-1, to adjust the effective screen interval of four onsite monitoring wells, and to assess the soil vapor intrusion risk to the Oakland Veterinary Hospital, located adjacent to the northwest of the station.

A total of eight sonic borings (SB-12 through SB-19) were sited along the northwest, northeast, and southeast portions of the station building; six soil vapor wells were installed along the northwest portion of the station; and the four on-site monitoring wells (MW-1 through MW-4) were abandoned and reinstalled with different screen intervals (MW-1B through MW-4B).

Groundwater samples were collected from SB-15, SB-16, SB-17, SB-18, and SB-19. SB-18, located between the unknown vault location and the former waste oil UST on the northwest side of the station building had the highest concentrations of petroleum hydrocarbons. SB-15, located near the current waste oil aboveground storage tank, on the northeast side of the station building, had the lowest concentrations.

Of the six vapor wells installed, extractable soil vapor samples were collected from only five – SVW-1, SVW-2, SVW-3, SVW-5, and SVW-6. A soil vapor sample was not collected from SVW-4 due to water in the well. The soil vapor wells that were sampled contained very high concentrations of petroleum hydrocarbons as gasoline (TPHg) up to 420,000,000 micrograms per cubic meter (μ g/m3) at SVW-6, benzene up to 1,100,000 μ g/m3 at SVW-3, toluene up to 19,000 μ g/m3 at SVW-2, ethylbenzene up to 610,000 μ g/m3 at SVW-3, and total xylenes up to 820,000 μ g/m3 at SVW-3. Methyl tertiary butyl ether (MTBE) was not detected in the soil vapor analyses, though reporting limits were higher than Environmental Screening Level values in many cases.

1.5 Geology/Hydrogeology

AECOM reviewed boring logs prepared by other consultants during previously completed subsurface investigations (Delta 2007a, 2007b, 2008a, 2009, 2010). The boring logs indicate that soil types encountered beneath the site consist of unconsolidated deposits of sand and silt in a clay matrix, with some intermixed fine-to-medium-grained gravel. Clay is predominant in the upper lithology with sandy/silty clay and clayey sand units, between approximately 1 to 15 feet bgs. The clay unit is underlain by clay interbedded with sandy clay, clayey sand, silty sands, and some gravelly sandy clay units, observed to the maximum depth explored (50.5 feet bgs).

Based on a review of boring logs and groundwater monitoring data tables prepared by previous consultants (Delta, 2007b, 2008a, 2009, 2010; CRA, 2011), discontinuous confined and/or unconfined water bearing zones may exist within the stratified clay matrices. Soil boring logs depict groundwater being encountered first between 4 (SB-1) and 42 (SB-11) feet bgs. During monitoring well installations in 1999, groundwater was typically encountered at a depth of approximately 23.5 feet bgs (MW-1, MW-2, MW-3, MW-4). During well installations in 2001, groundwater was encountered at 6 and 5.5 feet bgs in MW-5 and MW-6, respectively. Groundwater was encountered at 15 feet bgs in MW-7 during installation in 2001.

During the most recent groundwater monitoring event, conducted on July 24, 2012 (third quarter), the static groundwater elevation ranged from 164.86 feet (MW-7) to 172.87 feet (MW-4B) amsl. The depth to water measurements during the third quarter 2012 ranged from 7.25 feet bgs (MW-7) to 1.90 feet bgs (MW-5). To note, the southwest portion of the station site is at least 8 feet lower in elevation than the northeast portion; and the west corner is approximately 4 feet lower in elevation than the south corner. The groundwater flow direction and gradient was interpreted to be to the southwest at 0.06 foot per foot (ft/ft). The predominant historical groundwater flow at the station site has been to the west (with variations to the southwest) at an average gradient of approximately 0.05 ft/ft.

Varying groundwater-encounter depths during soil boring installations are indicative of multiple water-bearing zones due to semi-impermeable, discontinuous clay layers identified in the soil boring logs. In addition, shallow static groundwater levels indicate a confined groundwater aquifer below 20 feet bgs under hydrostatic pressure. Previous well installations (MW-1 through MW-4) were screened across multiple confining layers, thus providing a conduit for deeper groundwater to saturate upper layers with higher hydrocarbon impacts. While there may be some perched water in the area (as observed in some of the soil borings above), the deeper, confined aquifer is considered indicative of true groundwater elevation.

2.0 Proposed Scope of Work

The proposed investigation will consist of installing six collocated groundwater monitoring wells for the purpose of evaluating the groundwater contaminant pathways that may exist in the source areas to complete data gaps identified in the CSM (**Appendix B**). The locations of the proposed well installations are shown on **Figure 2**. These locations were selected based on their proximity to existing monitoring wells in the permanent saturated zone, and down-gradient of known source impacts.

In addition, AECOM proposes to further investigate the "unknown vault" located in the northwestern portion of the site. AECOM will attempt to confirm this structure is the sewer cleanout for the site. Additional information regarding the scopes of work is provided in the subsections below. AECOM will commence work upon receipt of regulatory acceptance of this work plan, and contingent upon successful completion of an access agreement with the property owner, the availability of subcontractors, and securing appropriate permits. A report will be prepared and submitted upon completion of the investigation.

2.1 Pre-Field Activities

Prior to drilling and installing monitoring wells on site, AECOM will mark and identify the proposed boring locations and request an underground utility line clearance at least 48 hours in advance of any subsurface activities. In addition, AECOM will contract with a private utility line locating service to establish that there are no obstructions near the proposed boring areas.

AECOM will obtain necessary well permits from the appropriate Alameda County and City of Oakland agencies. AECOM will comply with the terms specified in the permits and will provide a minimum 72-hour notification to the agencies prior to mobilization. AECOM will contract with and schedule a State of California C-57-licensed drilling contractor to advance the boreholes and install the monitoring wells.

2.2 Field Activities

Field activities will be performed under the supervision of a State of California Professional Engineer or Geologist. At the commencement of field activities, AECOM will perform the following tasks:

- Conduct a tailgate safety meeting at the site.
- Review the contents of the Health and Safety Plan with all AECOM and subcontracted workers, and review the requirements mandated by the Chevron Operational Excellence and Safety Program.
- Set up and demarcate an Exclusion Zone around the work area for each boring location to preclude access by anyone whose entry is unauthorized.
- Keep written documentation of field conditions during sampling and drilling. This will include, but not be limited to, weather conditions (e.g., temperature, wind direction, degree of cloud cover, etc.); and surface soil conditions (e.g., presence of standing water). AECOM will maintain detailed field records of all activities, conditions, and sampling processes, including names of field personnel, dates and times, etc.

2.2.1 Unknown Vault Investigation

Based on site reconnaissance conducted by AECOM on November 16, 2012, the vault appears to be a sewer cleanout for the station restroom. The location of the vault is between the station's restroom facility and sewer lateral in MacArthur Boulevard. Previous investigations determined (via GPR) that a subsurface line from the cleanout terminates near the station restroom, but a line from the cleanout to the main sewer line could not be confirmed. This is likely due to the difference in elevation from the cleanout location to MacArthur Boulevard.

AECOM proposes to remove the lid to access the cleanout. The cleanout cap will be removed and the piping will be video scoped and traced using a third-party sewer inspection company. Upon determination of the purpose of the cleanout, AECOM will re-cap the pipe and replace the steel lid. The sand surrounding the cleanout was previously probed and hydrocarbon odors were noted (Delta 2010). AECOM will examine the sand using a probe and PID monitoring device. If elevated hydrocarbon concentrations are detected with the PID, a sample of the sand may be collected for laboratory analysis, if possible.

2.2.2 Soil Borings and Soil Sampling

As stated in section 1.2, the focus of the soil boring scope of work is to determine the subsurface lithology at depths up to 20 feet bgs, as this zone has not been sufficiently assessed to determine what (if any) discrete permanent/temporary saturated zones may be present. Determining the presence of such zones will facilitate evaluation of source pathways (if any) to down-gradient receptors.

AECOM will supervise a truck-mounted roto-sonic drill rig to advance and sample six soil borings (MW-9A/B, MW-10A/B, and MW-11A/B) that will be converted into six groundwater monitoring wells (approximate locations on **Figure 2**). The borings will be continuously cored from the surface to approximately 20 feet bgs.

Soil cores will be collected in 5- to 10-foot lengths. Each cored interval will be visually inspected and logged in accordance with ASTM guidelines. At each of the paired locations, the deepest boring will be advanced first. During the boring advancement, should perched groundwater be identified, the proposed well construction may be modified to target the zone.

Soil samples will be labeled in accordance with EMC sample naming standards, which include the field point name (e.g., MW-9A), the matrix sampled (e.g., S for soil), whether the sample is a duplicate (e.g., Y or N), the depth in feet (e.g., 15), and the date (YYYYMMDD). For example, a non-duplicate soil sample collected from boring MW-9A at 15 feet bgs on November 19, 2012, would be labeled MW9A-S-N-15-20121119. If refusal is encountered in the boring and the boring is relocated to avoid the subsurface obstruction, the relocated boring will be identified with the original boring number using the letter suffix "R" (e.g., MW-9R).

Soil samples for laboratory analyses will be collected from the core at a minimum of 5-foot intervals, and will be biased towards the highest probable degree of contamination based on field screening results. A 6-inch-long pre-cleaned brass or stainless steel sampling sleeve will be pushed into the center of each core at the prescribed interval to collect the soil sample.

The soil samples will be sealed with Teflon sheets and capped with plastic end caps, labeled, and placed in a cooler with ice (Standard Operating Procedures [SOP] for soil sampling methods are provided in **Appendix C**). The remaining soil will be used for field headspace volatile analysis with a

PID and lithologic description. For volatile organic compounds and total petroleum hydrocarbon (TPH) volatile fraction analyses, an EnCore® sampler (or pre-weighed laboratory-prepared VOA vials and an Easy Draw® syringe) will be used for sample collection and field preservation, consistent with U.S. Environmental Protection Agency (EPA) Method 5035 requirements. The sample containers will be sealed, labeled, recorded on a chain-of-custody form and placed in a cooler with ice pending delivery to the analytical laboratory.

2.2.3 Groundwater Monitoring Well Installation

Following completion of the soil sampling, soil borings will be completed as groundwater monitoring wells. Each well location will consist of a 2-inch-diameter monitoring well. The wells will be constructed with 2-inch-diameter schedule 40 polyvinyl chloride (PVC) well casings with 5 feet of 0.020-inch slot PVC screen. Proposed well screen depths and screened intervals are based on lithology and groundwater elevation data compiled to date. Final screen intervals may be adjusted based on field observations during drilling activities. Shallow wells will be labeled "MW-XA, with screen intervals set from approximately 10 to 15 feet bgs. Intermediate wells will be labeled "MW-XB", with screen intervals set from approximately 15 to 20 feet bgs.

A 2-inch-diameter end cap will be added to the bottom of each well casing. A sand pack (Monterey #3) will be placed in the annular space from the bottom of the well screen to approximately 2 feet above the top slot of the well screen. The well will be surged during sand emplacement to settle the sand pack and prevent bridging. A 3-foot-long hydrated bentonite seal will be placed in the annular space above the sand pack using bentonite chips. The remaining annular space will be filled with bentonite cement grout. Well construction diagrams are included as **Figures 4a and 4b**. The SOP for monitoring well installation is included in **Appendix C**. Well construction details may change depending on the lithology and site conditions encountered during installation.

Each monitoring well will be completed with a traffic-rated well box with a locking well cap. The cap will be permanently labeled with the well identification number. The well box will be set in concrete colored to match surrounding conditions.

2.2.4 Groundwater Monitoring Well Development and Survey

The groundwater monitoring well will be developed at least 48 hours after installation to allow the annular seal to adequately set. The well will then be developed using a surge block. The well will be surged along the entire length of well screen for approximately 10 minutes. The well will then be purged using a stainless steel bailer or Grundfos pump until the water is visibly free of suspended sediments to the extent feasible. Additionally, water quality parameters, including temperature, pH, turbidity, dissolved oxygen, and electrical conductivity, will periodically be collected from the bailer or pump effluent. AECOM's SOP for monitoring well development is included in **Appendix C**.

A licensed land surveyor will survey each monitoring well during well development.

2.2.5 Laboratory Analysis

The soil samples will be analyzed by a State of California-certified laboratory for the following constituents:

• TPH carbon chain (TPH-CC) by EPA Method 8015B(M); and

 TPHg, benzene, toluene, ethylbenzene, xylenes, and fuel oxygenates, including MTBE, tertiary butyl alcohol, diisopropyl ether, ethyl tertiary butyl ether, tertiary amyl methyl ether, and ethanol by EPA Method 8260B

2.2.6 Investigation-Derived Wastes

Soil cuttings will be stored on site in Department of Transportation-approved 55-gallon drums. Decontamination water and purge water from well development will also be stored in 55-gallon drums. Following receipt of analytical results, the 55-gallon drums will be removed from the site and transported to an appropriately permitted facility.

3.0 Reporting

Upon completion of field activities, AECOM will prepare a report for submittal to ACEH documenting the findings of the site assessment. The report will include field observations, boring logs, laboratory results, conclusions, and recommendations. The report will be prepared under the supervision of and signed by a California Professional Geologist or Engineer. AECOM will submit all required electronic files necessary to comply with ACEH and State of California GeoTracker requirements.

4.0 References


- ACEH, 2012.Letter of Conditional Work Plan Approval for Fuel Leak Case No. RO0000409 and GeoTracker Global ID T0600102279, Unocal #1156, 4276 MacArthur Boulevard, Oakland, CA 94619. October 4.
- AECOM, 2012. Revised Work Plan for Vapor Intrusion Investigation and Risk Assessment. August 27.
- Aerial photographs dated 1939, 1946, 1958, 1965, 1974, 1982, 1993, and 1998. Provided by Environmental Data Resources, 440 Wheelers Farms Road, Milford, Connecticut 06461, 800-352-0050, www.edrnet.com.
- ATC Associates, Inc., 2005. Quarterly Summary Report Second Quarter 2005, 76 Service Station No. 1156/WNO1112, ATC Project No. 75.75118.1112, 4276 MacArthur Boulevard, Oakland, California. Prepared by ATC Associates, Inc., 6602 Owens Drive, Suite 100, Pleasanton, California 94588, 925-460-5300. Dated June21.
- CRA, 2011. Fourth Quarter 2011 Groundwater Monitoring and Sampling Report. Dated December 16.
 Prepared by Conestoga-Rovers & Associates, 5900 Hollis Street, Suite A, Emeryville,
 California 94608.
- Delta, 2007a. Work Plan Site Investigation, 76 Service Station No. 1156, 4276 MacArthur Boulevard, Oakland, California, dated March 1. Prepared for ConocoPhillips Company, 76 Broadway, Sacramento, California. Prepared by Delta Consultants, 3164 Gold Camp Drive, Suite 200, Rancho Cordova, California 95670.
- Delta, 2007b. Site Investigation Report, 76 Service Station No. 1156, 4276 MacArthur Boulevard, Oakland, California, dated December 28. Prepared for ConocoPhillips Company, 76 Broadway, Sacramento, California. Prepared by Delta Consultants, 3164 Gold Camp Drive, Suite 200, Rancho Cordova, California 95670.
- Delta, 2008a. Draft Corrective Action Plan, 76 Service Station No. 1156, 4276 MacArthur Boulevard, Oakland, California, dated April 24. Prepared for ConocoPhillips Company, 76 Broadway, Sacramento, California. Prepared by Delta Consultants, 11050 White Rock Road, Suite 110, Rancho Cordova, California 95670.
- Delta 2008b. Aquifer and Utility Survey, 76 Service Station No. 1156, 4276 MacArthur Boulevard, Oakland, California, dated May 8. Prepared for ConocoPhillips Company, 76 Broadway, Sacramento, California. Prepared by Delta Consultants, 11050 White Rock Road, Suite 110, Rancho Cordova, California 95670.
- Delta, 2009. Site Investigation Report, 76 Service Station No. 1156, 4276 MacArthur Boulevard, Oakland, California, dated September 8. Prepared for ConocoPhillips Company, 76 Broadway, Sacramento, California. Prepared by Delta Consultants, 11050 White Rock Road, Suite 110, Rancho Cordova, California 95670.
- Delta, 2010. Additional Assessment Report, 76 Service Station No. 1156, 4276 MacArthur Boulevard, Oakland, California, dated October 21. Prepared for ConocoPhillips Company, 76 Broadway,


- Sacramento, California. Prepared by Delta Consultants, 11050 White Rock Road, Suite 110, Rancho Cordova, California 95670.
- Miller Brooks Environmental, 2004. Summary of Potential Receptor Survey, 76 Service Station No. 1156, 4276 MacArthur Boulevard, Oakland, California, COP No. WNO.1112. Dated April 30.
- Morrow Surveying, 2010. Monitoring Well Exhibit prepared for Delta Environmental by Morrow Surveying, 1255 Starboard Drive, West Sacramento, California 95691, 916-372-8124. Drawing No. 1275-106 MAM. Dated 1-10-08, Revised 8-24-10.
- Sanborn fire insurance maps dated 1912, 1926, 1950, 1952, 1957, 1965, 1966, 1968, and 1969.

 Provided by Environmental Data Resources, 440 Wheelers Farms Road, Milford, Connecticut 06461, 800-352-0050, www.edrnet.com.
- USGS 7.5-minute Topographic Map. Oakland East dated 1980 (photorevised from 1959).

APPENDIX A

Figures







View of sewer cleanout/vault on northwest side of station building




View inside sewer cleanout/vault

Figure 3 – Sewer Cleanout/Vault Photographs



Chevron EMC		WELL ID: MW-9A, MW-10A, MW-11A	
60249149			
4276 MacArt	hur Boulevard, 0	Date Installed: TBD	
NA	Coords:	NA	Inspector: NA
Sonic			Contractor: TBD


FIGURE 4a -- PROPOSED MONITORING WELL CONSTRUCTION DIAGRAM





Chevron EMC		- WELL ID: MW-9B, MW-10B, MW-11B	
60249149			
4276 MacArt	hur Boulevard, C	Date Installed: TBD	
NA	Coords:	NA	Inspector: NA
Sonic			Contractor: TBD

FIGURE 4b -- PROPOSED MONITORING WELL CONSTRUCTION DIAGRAM




APPENDIX B

Conceptual Site Model

Conceptual Site Model

Former Unocal Station No. 1156 (Chevron Facility 351645) 4276 MacArthur Boulevard Oakland, California

ACEH Case No. RO409 RWQCB Case No. 01-2474



Conceptual Site Model

Former Unocal Station No. 1156 (Chevron Facility 351645) 4276 MacArthur Boulevard Oakland, California

ACEH Case No. RO409 RWQCB Case No. 01-2474

Prepared by:

Bryan Elder Project Engineer

Reviewed by:

Brenda Evans Project Manager Sally Bilodeau, PG 3580

OF CALIFOR

Senior Geologist

Contents

1.0	Site B	Background, Context, and History	4					
	1.1	1.1 Site Description and Vicinity4						
	1.2	Regional Setting						
		1.2.1 Geography, Topography, and Site Elevation						
		1.2.2 Hydrogeology						
		1.2.3 Surface Water Drainage / Distance to Closest Surface	-					
	1.3	Release History						
		1.3.1 First Release						
	1.4	Summary of Previous Site Investigations and Remedial Activitie						
	1.4	1.4.1 Previous Site Investigations						
		1.4.2 First Remediation						
		1.4.3 Any Subsequent Remediation(s)	10					
	1.5	Off-site Sources	10					
2.0	Sourc	ce	11					
	2.1 Ongoing							
	2.2 Contained / Stable							
	2.3	3 Remedial Measures						
	2.4	Release Mechanism	11					
3 0	Media	a of Concern	12					
5.0	Media	a or concern	12					
4.0	Conta	aminant(s) of Concern	12					
	4.1	12						
	4.2	Analytical Results	12					
		4.2.1 Soil						
		4.2.2 Current Groundwater						
		4.2.3 Historical Groundwater						
	4.3	Monitoring Results						
. 0	Diverse	a Dalimantian and Otability	40					
5. U		Plume Delineation and Stability						
	5.1	Vertical5.1.1 Soil						
		5.1.2 Groundwater						
		5.1.3 Vanor	15					

	5.2	Horizo	ontal	15
		5.2.1	Soil	15
		5.2.2	Groundwater	15
		5.2.3	Vapor	16
	5.3	Plume	Stability	16
		5.3.1	Soil	16
		5.3.2	Groundwater	16
		5.3.3	Vapor	16
6.0	Pathv	vays an	nd Receptors	16
	6.1	Potent	tial Receptors	16
	6.2	Potent	tial Exposure Pathways	17
7.0	Data	Gap An	alysis	17
R N	Pofor	oncos		17
0.0	Kelei	ences		17
Lis	st of	Table	s	
4-1	Maxir	mum His	torical Soil Concentrations for Constituents of Concern	12
4-2	Curre	ent Maxin	num Groundwater Concentrations	13
4-3	Histo	rical Max	kimum Groundwater Concentrations	13
4-4	Temp	orary Mo	onitoring Well Groundwater Concentrations (June 2010)	14
4-5	Maxir	num Soil	l Vapor Concentrations	14
Lis	t of A	Attach	ments	
A –	Figure	s		

- 1 Site Location Map
- 2 Site Plan
- 3 Third Quarter 2012 Groundwater Elevation Contour Map
- 4 Site Survey Map
- Conceptual Site Model Transport and Exposure Pathways

B – Boring Logs

C - Cross-sections

D - Historical Data Tables

- 1 Historical Soil Analytical Results 1998 through 2009
- 2 Soil Analytical Results August 2010
- 3 Historical Groundwater Monitoring Data and Analytical Results
- 4 Historical Groundwater Analytical Results Oxygenate Compounds
- 5 Historical Groundwater Analytical Results Additional Analytes
- 6 Grab Groundwater Analytical Results July 2009
- 7 Discrete Groundwater Analytical Results June 2010
- 8 Soil Gas Analytical Results August 2009 and September 2010

E - Hydrographs

1.0 Site Background, Context, and History

1.1 Site Description and Vicinity

The site is a branded 76 Service Station located at the north corner of the intersection between MacArthur Boulevard and High Street within the Oakland city limits (Attachment A – Figure 1). The station building is situated in the north portion of the site. An automotive service bay is located in the north portion of the building and a mini-mart/cashier area is located in the south portion. Two dispenser islands are located on site, both in the south portion of the site – one parallel to MacArthur Boulevard and one parallel to High Street. Previously prepared environmental documents (e.g., Delta 2010 and 2010b) indicate that two 10,000-gallon gasoline underground storage tanks (USTs) are located in the southwestern portion of the site (Figure 2).

What appears to be a sewer cleanout (formerly identified as an "unidentified concrete vault" [Delta 2010a]) was reported to be located on the northwest side of the station building, in the vicinity of former groundwater monitoring well MW-1. There are currently four groundwater monitoring wells (MW-1B through MW-4B) and one tank backfill well (TP-1) located on site, and two groundwater monitoring wells (MW-5 and MW-7) located off site on MacArthur Boulevard.

The site area consists of mixed commercial and residential development, with the following adjacent site uses (see Figure 2):

- Northwest The Oakland Veterinary Hospital (4258 MacArthur Boulevard) abuts the station site to the northwest, beyond which is a pharmacy/drug store.
- North and northeast Single-family dwellings (4257 Masterson Street and 3627 High Street) abut the station site to the north and northeast.
- East and southeast High Street borders the station site to the southeast, beyond which are
 a post office, apartment building (3618 to 3622 High Street), and commercial businesses
 (4300 to 4312 MacArthur Boulevard cleaners, tax service, pizza place, and sandwich shop).
 Based on a review of the State Water Resources Control Board GeoTracker database, a
 leaking underground storage tank (LUST) site was formerly located at this corner Chevron
 gasoline service station #93676 (4300 MacArthur Boulevard, Case No. 01-0371). The LUST
 case was closed in 1999.
- South A vacant lot is located south of the station site, beyond the intersection of MacArthur Boulevard and High Street. The GeoTracker database indicates that an open LUST case is located in this area – the former Robert's Tires facility, 4311-4333 MacArthur Boulevard (Case No. 01-3601).
- Southwest and west MacArthur Boulevard borders the station site to the southwest, beyond
 which are a vacant lot and commercial businesses. The GeoTracker database indicates that
 Shell gasoline service station #13-5701 (4255 MacArthur Boulevard) was formerly located at
 the vacant lot. There is an open LUST case (Case No. 01-1366) associated with the former
 Shell station.

Site and neighboring property uses are not expected to change significantly in the near future. The vacant lots are not expected to be redeveloped without resolution of the open LUST cases.

Drinking water for the city of Oakland is provided by East Bay Municipal Utility District (EBMUD). Information provided on the EBMUD website (EBMUD 2012) indicates that their water supply begins at the Mokelumne River watershed in the Sierra Nevada and extends 90 miles to the East Bay.

1.2 Regional Setting

1.2.1 Geography, Topography, and Site Elevation

Based on a review of boring logs prepared by previous consultants (Delta 2007b, 2008a, 2009a, 2009b, 2010a, 2010b), the site geology consists of unconsolidated deposits of sand and silt in a clay matrix, with some intermixed fine-to-medium-grained gravel. Clay is predominant in the upper lithology with sandy/silty clay and clayey sand units, between approximately 1 to 15 feet below grade surface (bgs). The clay unit is underlain by clay interbedded with sandy clay, clayey sand, silty sands, and some gravelly sandy clay units, observed to the maximum depth explored (50.5 feet bgs). Available boring logs are provided as Attachment B and cross-sections prepared by Delta are provided as Attachment C.

The site is located in a highly urbanized area of Oakland at the base of the San Leandro Hills. Based on site survey data (Morrow Surveying 2008 – Figure 4) surface elevations at the site range from 179.42 feet above mean sea level (amsl) at MW-4B to 173.99 feet amsl at MW-2B. Observations during the area reconnaissance on March 15, 2012, further revealed that the elevation at the northeast site boundary is noticeably higher than at MW-4B. Additionally, the elevation at MW-5 is 169.67 feet amsl. MW-5 is located in the street in front of the Oakland Veterinary Hospital (adjacent to the northwest portion of the station site). To summarize, the southwest portion of the station site is at least 8 feet lower in elevation than the northeast portion; and the west corner is approximately 4 feet lower in elevation than the south corner.

1.2.2 Hydrogeology

According to an aquifer study performed by Delta in 2008 (Delta 2008b), the site is located on the eastern edge of the East Bay Plain subbasin of the Santa Clara Valley Groundwater Basin. The East Bay Plain is bounded by San Pablo Bay to the north and by Franciscan Basement rock to the east, and extends beneath the San Francisco Bay to the west. The Niles Cone Groundwater Basin is located to the south.

Groundwater in the East Bay Plain subbasin is both unconfined and confined. The shallow aquifer system consists of the Newark aquifer (30 to 130 feet bgs) and Centerville aquifer (extends to 220 feet bgs) (WRIR 2003). The lower aquifer system consists of the Freemont aquifer (240 to 400 feet bgs) and Deep aquifer (500 to 650 feet bgs). Depth to groundwater in the upper aquifer system ranges from 5 to 40 feet bgs. Groundwater in both aquifers generally flows in a western direction from the mountain front to the San Francisco Bay (WRIR 02-4259); however, pumping in the northern portion of the subbasin has drawn groundwater in from the south.

Based on a review of boring logs and groundwater monitoring data tables (Attachment D) prepared by previous consultants (Delta 2007b, 2008a, 2009a, 2009b, 2010a, 2010b; CRA 2011), discontinuous confined and/or unconfined water bearing zones may exist within the stratified clay matrices. Soil boring logs reported groundwater being encountered first between 4 (SB-1) and 42 (SB-11) feet bgs. During monitoring well installations in 1999, groundwater was typically encountered at a depth of 23.5 feet bgs (MW-1, MW-2, MW-3, MW-4). During well installations in 2001, groundwater was encountered at 6 and 5.5 feet in MW-5 and MW-6, respectively. Additionally, groundwater was encountered at 15 feet bgs in MW-7 during installation in 2001. Finally, groundwater was encountered at 23.5 feet bgs in borings MW-1B, MW-2B, MW-3B, and MW-4B in 2010; however, significant moisture content was noted at 5 feet bgs and deeper. Cross-sections prepared by Delta are provided in Attachment C.

During the most recent groundwater monitoring event, conducted on July 24, 2012 (third quarter), the static groundwater elevation ranged from 164.86 feet (MW-7) to 172.87 feet amsl (MW-4B) (Figure 3). The depth to water measurements during the third quarter 2012 ranged from 1.90 feet bgs (MW-5) to 7.25 feet bgs (MW-7). As stated above, the southwest portion of the station site is at least 8 feet lower in surface elevation than the northeast portion; and the west corner is approximately 4 feet lower in surface elevation than the south corner. The groundwater flow direction and gradient was interpreted to be to the west-southwest at 0.06 foot per foot (ft/ft). This is consistent with the predominant historical groundwater flow at the station site, which has been to the west (with variations to the southwest) at an average gradient of approximately 0.06 ft/ft.

Varying groundwater-encounter depths are indicative of multiple water-bearing zones due to semi-impermeable, discontinuous clay layers identified in the soil boring logs. In addition, shallow static groundwater levels indicate a confined groundwater aquifer below 20 feet bgs under hydrostatic pressure. Previous well installations (MW-1 through MW-4) were likely screened across multiple confining layers, thus providing a conduit for deeper groundwater to contact and potentially mix with upper layers.

Additional assessment is required to determine the horizontal groundwater impacts in vertically isolated water-bearing zones (if any).

1.2.3 Surface Water Drainage / Distance to Closest Surface Water Body

Surface water drainage at the site is directed downslope toward MacArthur Boulevard. Based on a review of Google Earth images on the internet and the United States Geological Survey (USGS) 7.5-minute topographic map (Oakland East quadrangle) dated 1980, the nearest surface water bodies are the Thirtyninth Avenue Reservoir, located approximately 0.6 mile to the northwest (topographically upgradient), and Peralta Creek, located approximately 0.6 mile to the northwest (topographically cross-gradient).

1.3 Release History

1.3.1 First Release

Soil contamination was identified during the removal of the USTs and waste oil tank (WOT) in 1998. No releases or leaks were documented prior to tank removals.

1.3.2 Any Subsequent Release(s)

No subsequent releases on site have been documented.

1.4 Summary of Previous Site Investigations and Remedial Activities

1.4.1 Previous Site Investigations

A site map with historical sampling locations is included as Figure 2. Historical information provided in previously prepared reports (Miller Brooks Environmental [MBE] 2004; ATC 2005; Delta 2007b, 2008a, 2009a, 2009b, 2010a, 2010b) indicates the following.

As reported by Delta (Delta 2010b), in 1997, Pacific Environmental Group Inc. advanced five soil vapor probes (D-1, D-2, D-3, T-1, T-2) in the vicinity of the USTs and dispenser islands to depths ranging from 3 to 15 feet bgs. Soil vapor concentrations of total petroleum hydrocarbons as gasoline (TPHg), benzene, and methyl tert butyl ether (MTBE) were reported at up to 4,700 micrograms per liter (μ g/L), 70 μ g/L, and 140 μ g/L, respectively.

In 1998, Tosco Marketing Company (Tosco, now ConocoPhillips) removed one 280-gallon WOT, and removed and replaced two 10,000-gallon gasoline USTs, associated piping, and fuel dispensers. Laboratory analyses of soil samples collected at 6 feet bgs from the sidewall at each end of the gasoline UST excavations revealed concentrations of total purgeable petroleum hydrocarbons as gasoline (TPPHg) of up to 1,200 milligrams per kilogram (mg/kg). TPPHg was not detected at or above laboratory method detection limits in soil samples collected adjacent to dispensers D1 (S-D1 at 2 feet bgs) and D4 (S-D4 at 3 feet bgs), but was detected in soil samples collected adjacent to dispensers D2 (S-D2 at 3 feet bgs) and D3 (S-D3 at 3 feet bgs), and within the former product line trenching at concentrations up to 590 mg/kg. Laboratory analyses of soil samples from the bottom. and western and southern limits of the WOT excavation detected TPPHg (6.5 feet bgs) up to 130 mg/kg; total extractable petroleum hydrocarbons as diesel (TEPHd) up to 78,000 mg/kg; benzene up to 0.55 mg/kg; and total recoverable petroleum hydrocarbons (TRPH) up to 8,400 mg/kg. Following the over-excavation of approximately 4.6 tons of soil from the WOT excavation, samples collected from the excavation (6 feet bgs) revealed concentrations of TEPHd at 560 mg/kg, TPPHg at 81 mg/kg, benzene at 0.64 mg/kg, and TRPH at 360 mg/kg. Analytical data from a groundwater sample collected from the gasoline UST excavation (7.5 feet bgs) reported TPPHg at 41,000 µg/L, toluene at 400 μg/L, ethyl-benzene at 770 μg/L, and xylenes at 8,900 μg/L. Benzene was reported to be below the laboratory's indicated reporting limit in the groundwater sample collected for analysis. Available historical soil and groundwater analytical data are provided in Attachment D.

In 1999, Environmental Resolutions Inc. (ERI) conducted a soil and groundwater assessment which included the installation of four on-site groundwater monitoring wells (MW-1 through MW-4). Analytical data from the soil samples collected from the borings at a depth of 10.5 feet bgs reported TPPHg at 6,800 mg/kg, benzene at 2.6 mg/kg, and MTBE at 0.71 mg/kg. The soil sample collected from MW-1, near the former WOT, was also analyzed for total petroleum hydrocarbons as diesel (TPHd) and TPPH. Analytical data from this soil sample reported TEPHd at 140 mg/kg and TRPH at 73 mg/kg. A soil sampled collected from MW-4 at 20.5 feet bgs did not contain TPHg, benzene, or MTBE at or above the laboratory detection limit. The groundwater sample collected from MW-1, near the former WOT, was analyzed for TEPHd, TRPH, TPPHg, benzene, toluene, ethylbenzene and xylenes (BTEX), and MTBE. Analytical data from this water sample reported TEPHd at 16,000 µg/L, TPPHg at 120,000 µg/L, benzene at 11,000 µg/L, toluene 27,000 µg/L, ethylbenzene at 3,300 µg/L, and xylenes at 18,000 µg/L. MTBE was at or below laboratory detection limits in MW-1. However, MTBE was detected in the groundwater sample from MW-2 at a concentration that varied from 4,500 µg/L (U.S. Environmental Protection Agency [EPA] Method 8021B) to 11,000 µg/L (EPA Method 8260B). Analytical data from an additional soil sample collected at a depth of 20.5 feet bgs from the MW-4 boring reported TPPHq, benzene, and MTBE below the laboratory's indicated reporting limits. Available historical soil and groundwater analytical data are provided in Attachment D.

Quarterly groundwater monitoring and sampling activities commenced in July 1999 and are currently ongoing.

In July 2001, ERI installed a UST pit backfill well (TP-1) in the vicinity of the new USTs and initiated monthly purging of groundwater "from the UST excavation". Monthly and/or bi-weekly groundwater purging was conducted at the site using wells TP-1 and MW-1 from July 2001 through December 2004. Well construction details for TP-1 were not found in the historical documents available to AECOM.

In August 2001, ERI installed three off-site monitoring wells (MW-5 though MW-7; see Figure 2). Analytical data from soil samples collected from these well borings indicated TPHg and MTBE below the laboratory's indicated reporting limits. Analytical data reported benzene in one soil sample collected from MW-7 (10 feet bgs) at a concentration of 0.18 mg/kg (see historical data tables in Attachment D).

Beginning in June 2004, monitoring well MW-7 was added to the ongoing bi-weekly purging events. Approximately 1,600 gallons of groundwater were removed from monitoring well MW-7 from June through December 2004. A cumulative total of approximately 476,015 gallons of groundwater was removed from the site from July 2001 through December 2004. ATC Associates became the new lead consultant for the site in January 2005. Delta Consultants became the new consultant for the site in September 2005.

In October and November 2007, Delta advanced six on-site soil borings (SB-1 through SB-6) and installed an additional off-site monitoring well (MW-8) (Delta, 2007b). The subsurface materials reported to be encountered consisted of predominantly lean clay and sand with some silt. First water was reported at depths ranging from approximately 17.5 to 23 feet bgs in borings SB-2 through SB-6 and MW-8. First water was reported at 4 feet bgs in borings SB-1. Static groundwater was reported at depths ranging from approximately 4 to 6 feet bgs in borings SB-2 through SB-6. Static groundwater in MW-8 was measured prior to well development at 0.11 feet below the top of the casing. Groundwater was first observed at a depth of approximately 4 feet bgs in boring SB-1. The above information indicates that the groundwater at the site is under confined/partially-confined conditions. Boring SB-1 was advanced in the former UST excavation area, which was backfilled with fill material, gravel, sand, and clay. Based on the shallow depth to first water that was encountered, the former UST excavation was reported to be acting as a basin and that this shallow groundwater is perched in the fill material above the lean clay below.

Based on the analytical data collected during Delta's 2007 investigation, the soil and groundwater beneath the site were reported to not be significantly impacted by total oil and grease (TOG), volatile organic compounds (VOCs), and semi-volatile organic compounds (SVOCs), indicating that the former WOT had not significantly impacted soil and groundwater quality beneath the site. However, due to insufficient water volume, groundwater samples from soil borings SB-5 and SB-6 in the vicinity of and downgradient of the former WOT were not collected. Delta recommended that groundwater samples collected from monitoring wells MW-1, MW-5, MW-6, and MW-8 (downgradient of the former waste oil tank) be analyzed for VOCs by EPA Method 8260B, SVOCs by EPA Method 8270, and TOG by EPA Method 1664.

Based on the data obtained during the investigation, Delta reported that the soil appeared to be impacted to depths ranging from approximately 12 feet bgs in boring SB-2 to 17 feet bgs in boring SB-5. Additionally, the soil did not appear to be significantly impacted in the vicinity of borings SB-3, SB-4, and MW-8, indicating that the extent of the petroleum hydrocarbon impact to the soil was predominantly located on site in the vicinity of the former USTs, the current USTs, and downgradient of the station building.

Based on the data obtained during the investigation, Delta reported that groundwater appeared to be impacted across the site with the highest concentration of TPPH found in boring SB-1 at a depth of approximately 16 feet bgs, beneath the former UST location. However, based on the quarterly groundwater data obtained from MW-4, downgradient of the former USTs, with the exception of MTBE, the petroleum hydrocarbon impact to the groundwater was significantly lower than that found in the groundwater beneath the former USTs. Delta recommended that a revised Corrective Action Plan be prepared.

In July 2009, Delta performed site assessment activities to further assess the horizontal and vertical migration potential of petroleum hydrocarbons in soil, groundwater, and soil vapor, and to evaluate if a preferential pathway existed between the former UST pit and MW-1 (Delta 2009a). A total of five CPT/direct push borings (SB-7 through SB-11) were advanced outside the southeast, southwest and northwest perimeter of the station building. Seven temporary soil vapor sampling points (SV-1 through SV-7) were installed outside and around the station building.

Subsurface geology was reported to consist of clay from the surface to 25 feet bgs. Below this clay unit was another clay unit that contained discontinuous stringers or small deposits of sandy clay and clayey sand to the maximum depth explored of 44 feet bgs. The discontinuity of sandy clay/clayey sand stringers, or deposits, was demonstrated in the boring logs of SB-7, SB-9, and SB-11, which showed first water being encountered at depths of 23.5 feet bgs, 26 feet bgs, and 42 feet bgs, respectively.

Results of the UVOST analyses of borings SB-7, SB-9, and SB-11 indicated low levels of petroleum hydrocarbons from approximately 5 feet bgs to 17 feet bgs. Analyses of soil samples extracted from direct push borings and the soil vapor points indicated petroleum hydrocarbon impact from 4.5 feet bgs to approximately 18.5 feet bgs. Hydrocarbon concentrations decreased rapidly with depth within the clay soil column.

Groundwater samples were collected from SB-7, SB-9, and SB-11. SB-7 had the highest concentrations of petroleum hydrocarbons. SB-9 and SB-11 had much lower concentrations of petroleum hydrocarbons. This appeared to indicate that there was no preferred pathway between the former UST pit and MW-1. The soil vapor points that were sampled contained very high concentrations of petroleum hydrocarbons. Of the seven soil vapor points installed, only SV-2, SV-4, SV-6, and SV-7 had extractable soil vapors – TPHg up to 82,000,000 micrograms per cubic meter (μ g/m3) (SV-7); benzene up to 120,000 μ g/m3 (SV-7); toluene at 370 μ g/m3 (SV-2); ethylbenzene up to 32,000 μ g/m3 (SV-7); m,p-xylenes up to 6,200 μ g/m3 (SV-4); and o-xylenes at 140 μ g/m3 (SV-2). MTBE was not detected in the soil vapor samples.

Analysis of the data gathered indicates that the highest concentration of petroleum hydrocarbons in groundwater occurred in the vicinity of SB-7, SB-9, and SB-11. Though concentrations of petroleum hydrocarbons exist in the clay soil, Delta reported that little could be done to eliminate or reduce these concentrations due to the tight structure of the clay, with the exception of site excavation.

According to Delta (2010a), during a site visit on November 10, 2009, a "previously unidentified underground concrete vault was observed in the northwest corner of the site, in proximity to MW-1." The "vault" was reported to be of unknown depth and filled with sand. Delta probed the sand with a 2-foot-long field instrument and was "unable to locate the bottom of the vault." A "faint hydrocarbon odor" was reported to have been "noted" upon removal of the instrument.

In August and September 2010, Delta conducted additional assessment of the horizontal and vertical potential for petroleum hydrocarbon migration in the soil, groundwater and soil gas (Delta 2010b). The activities included soil vapor point sampling, soil vapor well installation and sampling, monitoring well abandonment and reinstallation, soil and groundwater borings, and assessment of a previously unidentified underground vault/utility. The investigations were conducted to determine if a pathway existed between the former gasoline UST pit and MW-1, to adjust the effective screen interval of the on-site monitoring wells, and to assess the soil vapor intrusion risk to the Oakland Veterinary Hospital, located adjacent to the northwest of the station.

Delta used ground-penetrating radar (GPR) to attempt to identify utility lines running to and from this "cleanout". A line running from the restroom area of the building to the "cleanout" was identified, but no line running from the "cleanout" to the sewer main approximately 6 feet to the north could be identified. Delta reported that the only way to positively identify the nature of this structure would be to open the "cleanout" lid, but that it was highly likely that the structure would be destroyed or badly damaged in the process due to age and deterioration.

A total of eight sonic borings (SB-12 through SB-19) were sited along the northwest, northeast, and southeast portions of the station building; six soil vapor wells were installed along the northwest portion of the station; and the four on-site monitoring wells (MW-1 through MW-4) were abandoned and reinstalled with different screen intervals (MW-1B through MW-4B).

Groundwater samples were collected from SB-15, SB-16, SB-17, SB-18, and SB-19. SB-18, located between the unknown vault location and the former waste oil UST on the northwest side of the station building had the highest concentrations of petroleum hydrocarbons. SB-15, located near the current waste oil AST, on the northeast side of the station building, had the lowest concentrations.

Of the six vapor wells installed, extractable soil vapor samples were collected from only five – SVW-1, SVW-2, SVW-3, SVW-5, and SVW-6. The soil vapor wells that were sampled contained very high concentrations of petroleum hydrocarbons – TPHg up to 420,000,000 μ g/m3 at SVW-6, benzene up to 1,100,000 μ g/m3 at SVW-3, toluene up to 19,000 μ g/m3 at SVW-2, ethylbenzene up to 610,000 μ g/m3 at SVW-3, and total xylenes up to 820,000 μ g/m3 at SVW-3. MTBE was not detected in the soil vapor analyses, though reporting limits were higher than Environmental Screening Level (ESL) values in many cases.

1.4.2 First Remediation

Approximately 1,350 tons of soil were excavated and removed during the UST removal in 1998 (Delta 2009a). In addition, approximately 4.6 tons of soil were over-excavated and removed during the WOT removal, also in 1998.

1.4.3 Any Subsequent Remediation(s)

A UST pit backfill well (TP-1) was installed in July 2001 and monthly purging of groundwater from the excavation was initiated (Delta 2009a). Bi-weekly groundwater purging was conducted from July 2001 to December 2004 at TP-1 and MW-1. In addition, biweekly purging of MW-7 was conducted in June 2004. Approximately 1,600 gallons of groundwater were removed from MW-7. In total, approximately 476,015 gallons of groundwater were removed through December 2004 from the site (Delta 2009b).

1.5 Off-site Sources

Two gasoline service stations were formerly located adjacent to the station site (Figure 2). The southwest former Shell Station No. 13-5701, located at 4255 MacArthur Boulevard, operated from at least 1965 (from aerial photographs) to 2003 when the final USTs were removed (Cambria 2005). The Shell station previously operated three USTs and three dispenser islands. The former Shell station has an active LUST case since 1985 with Alameda County Environmental Health (ACEH) and the San Francisco Regional Water Quality Control Board (RWQCB).

To the southeast, former Chevron Station No. 9-3676 operated from at least 1965 (from aerial photographs) to approximately 1988 when a leak was reported to RWQCB during the UST excavations (GeoTracker). The station was no longer visible in aerial photographs taken in 1993. Previous operations for the station (i.e., number of USTs and dispenser islands) are unknown. The former Chevron station has a closed LUST case with Alameda County and the RWQCB as of 1999.

2.0 Source

2.1 Ongoing

Migration of residual contamination in the unsaturated zone is the only likely source contributing to groundwater contamination aside from unknown upgradient sources. However, dense clay matrices layered beneath the site have prevented significant vertical transport as identified by relatively low contaminant concentrations in groundwater wells screened from 20 to 25 feet (MW-1B through 4B). Known off-site sources are downgradient from the station site.

2.2 Contained / Stable

Based on declining concentrations in off-site, downgradient wells MW-5 and MW-7, the plume is stable and shrinking (see Attachment E – Hydrographs). On-site well concentrations (MW-1B, MW-2B, MW-3B, and MW-4B), also exhibit stable to decreasing trends. In addition, benzene concentrations in soil below 20 feet bgs have not been detected above the EPA Residential Screening Level in any boring installed on or off site. Therefore, no saturated zone source of benzene is believed to exist.

2.3 Remedial Measures

As stated above in section 1.4.2, approximately 1,350 tons of soil were excavated and removed during the UST removal in 1998 (Delta 2009a). In addition, approximately 4.6 tons of soil were over-excavated and removed during the WOT removal, also in 1998.

Over-purging events were conducted on up to three wells from 2001 to 2004 (MW-1, TP-1, and MW-7). Approximately 476,000 gallons of water were removed during that period. No data regarding these overpurge events was found in the documentation available to AECOM.

2.4 Release Mechanism

The location and vertical extent of contaminated soil and groundwater indicate on-site releases occurred at the subsurface dispenser/product piping, WOT, and USTs.

Additionally, an "unidentified underground concrete vault" was previously investigated by Delta in 2009 and 2010, during which it was described to appear to be a "sewer cleanout". Delta reported that they were "unable to open and better identify the structure" based on "the age and deterioration of the cleanout cap". To further assess the structure, Delta employed GPR to identify utility lines running to and from this "cleanout". A line running from the restroom area of the building to the "cleanout" was identified, but no other lines were identified. No details regarding the materials, size, etc., for the cleanout, were provided in Delta's reports, except that the "vault" appeared to be filled with sand, and the bottom could not be determined beyond 2 feet bgs.

AECOM visited the site on November 16, 2012, and visually inspected the "unknown vault" by removing the surface lid. What appeared to be a typical sewer cleanout pipe and cap (approximately 4-inch diameter) was observed within an approximately 8-inch-diameter casing. There are bindings on the "plastic" (non-metal) piping holding the metal cap in place. No odors were noted and no VOCs were detected with the photoionization detector. No other potential sewer cleanouts were found on site. The primary utility corridor for the site is located along MacArthur Boulevard. Typical sewer construction would indicate that this "unknown vault" is the station's sewer cleanout. The surface grade at the cleanout is at an approximately 4- to 5-foot higher elevation than MacArthur Boulevard. Therefore, based on the "plastic" nature of the piping, and that it is likely buried up to 10 feet bgs, it is not surprising that GPR did not detect a line running from the cleanout toward MacArthur Boulevard.

Additional assessment is required to determine the nature of the structure (that appears to be a sewer cleanout rather than a "vault") and to evaluate whether the structure is a source of elevated petroleum hydrocarbons detected in soil, soil vapor, and groundwater in the area of former monitoring well MW-1.

3.0 Media of Concern

Media of concern include groundwater, soil, and soil vapor (potentially indoor air concentrations, off site).

4.0 Contaminant(s) of Concern

4.1 Contaminant Name(s)

Contaminants of concern are related to gasoline, diesel, and motor oil (e.g., TPHg, BTEX, MTBE) releases.

4.2 Analytical Results

4.2.1 Soil

Soil boring samples collected from 1997 to date indicate that soil contamination is largely confined to the upper 15 feet of the unsaturated zone. Maximum benzene concentrations of 7.8 mg/kg were observed in soil boring SB-2 at 8.5 feet bgs in 2007. Maximum MTBE concentrations of 1.2 mg/kg were collected from the same boring at 12 feet bgs. Table 4-1 (below) summarizes maximum observed soil concentrations for constituents of concern.

Constituent	Boring ID	Date	Depth [ft bgs]	Concentration [mg/kg]
Benzene	SB-2	2007	8.5	7.8
Toluene	SB-2	2007	8.5	51
Ethylbenzene	B1/MW-1	1999	10.5	110
Total Xylenes	B1/MW-1	1999	10.5	470
MTBE	SB-2	2007	12	1.2

Table 4-1 Maximum Historical Soil Concentrations for Constituents of Concern

4.2.2 Current Groundwater

Groundwater monitoring from 1999 to 2010 included monitoring of MW-1, MW-2, MW-3, and MW-4. These wells were screened from 5 to 25 feet bgs. In 2010, these wells were abandoned and replaced with monitoring wells screened from 20 to 25 feet bgs located near the former well locations. Differences in groundwater concentrations at the same well locations (but different screen intervals) indicate confined water-bearing zones. Current maximum groundwater concentrations are summarized in Table 4-2.

Table 4-2 Current Maximum Groundwater Concentrations

Constituent	Well ID	Date	Concentration [µg/L]
TPHg	MW-3B	7/24/2012	1,500
TPHd	MW-3B	7/24/2012	190
Benzene	MW-3B	7/24/2012	66
Toluene	MW-3B	7/24/2012	10
Ethylbenzene	MW-3B	7/24/2012	76
Total Xylenes	MW-3B	7/24/2012	39
MTBE	MW-7	7/24/2012	300

4.2.3 Historical Groundwater

In comparison to current concentrations, maximum groundwater concentrations prior to well abandonments in 2010 are provided in Table 4-3.

Table 4-3 Historical Maximum Groundwater Concentrations

Constituent	Well ID	Date	Concentration [µg/L]
TPHg	MW-1	8/2/2010	71,000
TPHd	MW-1	8/2/2010	3,900
Benzene	MW-1	8/2/2010	7,000
Toluene	MW-1	8/2/2010	11,000
Ethylbenzene	MW-1	8/2/2010	3,300
Total Xylenes	MW-1	8/2/2010	10,000
MTBE	MW-7	8/2/2010	770

Average depth to water measurements during the August 2010 sampling event for on-site wells (MW-1 to MW-4) was 5.90 feet bgs while average depth to water measurements during the July 2012 sampling event for on-site wells (MW-1B to MW-4B) was 6.23 feet bgs. The similarities in depth to water indicate that wells MW-1 to MW-4 were screened across multiple water-bearing zones, including that which is monitored by recent well installations (MW-1B to MW-4B). Furthermore, the long screen of the original monitoring wells may have allowed groundwater from the deeper confined aquifer under hydrostatic pressure to mix with impacted soils in the 5- to 20-foot unsaturated zone, contributing to higher groundwater impacts observed in these wells.

Furthermore, temporary monitoring wells were installed in soil borings SB-15 through SB-19 in June 2010. The wells were allowed to accumulate groundwater overnight before grab samples were collected. Table 4-4 provides a summary of the results obtained.

Table 4-4 Temporary Monitoring Well Groundwater Concentrations (June 2010)

Boring	Screen	Dissolved-Phase Concentration									
	Interval [ft bgs]	TPHg [µg/L]	TPHd [µg/L]	TPHmo [µg/L]	Benzene [µg/L]	MTBE [µg/L]					
SB-12	20-25	Dry									
SB-14	19-24	Dry									
SB-15	19-24	ND<50	54	ND<200	ND<0.50	29					
SB-16	20-25	ND<50	150	ND<200	140	460					
SB-17	14-19	260	260	ND<290	8.7	82					
SB-18	15-20	1,900	720	480	94	180					
SB-19	15-20	1,100	230	230	8.6	93					

Notes:

TPHmo = Total Petroleum Hydrocarbons as motor oil.

4.2.4 Soil Vapor

Soil vapor samples were collected along the northern property boundary for vapor intrusion risk assessment. Table 4-5 presents the maximum observed concentrations.

Table 4-5 Maximum Soil Vapor Concentrations

Constituent	Boring ID	Date	Depth [ft bgs]	Concentration [µg/m3]
Benzene	SVW-3	9/8/2010	4.5	1,100,000
Toluene	SVW-2	9/8/2010	4.5	19,000
Ethylbenzene	SVW-3	9/8/2010	4.5	610,000
Total Xylenes	SVW-3	9/8/2010	4.5	820,000
MTBE	SVW-6	9/8/2010	4.5	ND<37,000

4.3 Monitoring Results

A summary of results of contaminant of concern monitoring are presented in the above Tables 4-1 through 4-5. Additional historical monitoring results are presented in Attachment D.

5.0 Plume Delineation and Stability

The vertical/horizontal extent and stability of impacts for impacted media are discussed below.

5.1 Vertical

5.1.1 Soil

Soil impacts have been vertically delineated at the site to a maximum depth of 50 feet bgs. A review of historical soil data indicates that, in soil samples collected from >20 feet bgs, no compounds of concern have been detected that exceed the residential ESLs for deep soils for non-drinking water sources (San Francisco RWQCB 2008).

5.1.2 Groundwater

Vertical groundwater contamination has not been delineated. The vertical soil profile is such that multiple confined/semi-confined water-bearing zones may exist. A more extensive confined (i.e., under hydrostatic pressure) aquifer has been identified at a depth of approximately 20 feet bgs. Initial groundwater monitoring wells screened from 5 to 25 feet bgs exhibited much higher groundwater concentrations than more recent monitoring wells installed with screens from 20 to 25 feet bgs. Hydrostatic pressure from the underlying aquifer (below 20 feet bgs) is likely to have contacted impacted shallow soils due to the exposed screen and, therefore, resulting concentrations of COCs detected may not be representative of interlayer groundwater concentrations.

5.1.3 Vapor

Soil vapor samples have been collected to a maximum depth of 5 feet bgs near the northern property line. Contaminants of concern were measurable to the maximum depth of observation (see Table 4-5, above); however, in some samples, concentrations declined significantly at 3.5 feet bgs compared to 5 feet bgs.

The vertical extent of soil vapor at the station site has been delineated to the extent necessary given the site's use as an active service station.

5.2 Horizontal

5.2.1 Soil

Soil contamination is confined to the site property, in the vicinity of the former USTs, WOT, and product lines. In the northern portion of the site, soil contamination is distributed laterally downgradient to the west from the former WOT. This trend is evident from approximately surface to 20 feet bgs. Horizontal distribution of soil impacts downgradient of the WOT, USTs, and dispensers may be a result of perched groundwater conditions. Additional assessment is required to make this determination.

5.2.2 Groundwater

Groundwater contamination has been identified in the four on-site wells, in addition to off-site, downgradient wells MW-5 and MW-7. The plume extends west from the station site where it comingles with the horizontal plume of former Shell Station No. 13-5701. Currently, groundwater contamination is delineated in the water-bearing zone below 20 feet bgs. Additional assessment is required to determine the horizontal groundwater impacts in vertically isolated water-bearing zones (if any).

5.2.3 Vapor

Soil vapor concentrations have been measured along the northern property boundary to identify vapor intrusion risk to the adjacent commercial building. The concentrations are highest near the former WOT location (see Table 5, above). Additional assessment has been proposed (AECOM 2012) and approved by the ACEH (2012) to address off-site soil vapor intrusion.

5.3 Plume Stability

5.3.1 Soil

The vertical extent of soil contamination is confined to the unsaturated/partially saturated shallow one. Additional assessment is required to determine the stability and extent of horizontal soil impacts in the unsaturated zone(s).

5.3.2 Groundwater

Limited groundwater concentration data from monitoring wells MW-1B through MW-4B suggest a stable to shrinking plume in the confined saturated zone. Concentrations in fringe wells MW-5 and MW-7 have declined from historic highs for TPHg, benzene, and MTBE. Additional assessment is required to determine the vertical and horizontal extent of groundwater zones/impacts.

5.3.3 Vapor

Additional assessment has been proposed (AECOM 2012) and approved by the ACEH (2012) to further determine soil vapor impacts associated with the site.

6.0 Pathways and Receptors

6.1 Potential Receptors

In 2001 a GeoTracker database search was performed by Environmental Resolutions, Inc. (MBE 2004). Four public water supply wells owned by the East Bay Regional Park District (Park District) were identified within a ½-mile radius of the site. Representatives from the Park District reported having no knowledge or records of any wells under their ownership or oversight located in this area and indicated that the wells may have belonged to the EBMUD. EBMUD was contacted and reported no knowledge or records of any wells under their ownership or oversight located in the area.

Also in 2001 a Department of Water Resources (DWR) database search was performed by Environmental Resolutions, Inc. (MBE 2004). Four water supply wells belonging to Mills College were identified within a ½-mile radius search area. A representative from Mills College indicated that all wells associated with Mills College had been destroyed and Mills College was now connected to a municipal water supply. The DWR search also indicated a well was located at 3397 Arkansas Street, approximately 880 feet outside of the search area. No other wells, surface water bodies, or potentially sensitive environmental habitats were reported to have been identified during ERI's field receptor search.

In 2006, a well survey, which included a visit to the DWR office in Sacramento, was performed to examine well log records and identify domestic wells within the survey area (Delta 2007a). The DWR survey identified two potential receptors within 1 mile of the site – one irrigation well located 0.9 mile northwest of the site, and one domestic/irrigation well located 1.0 mile northeast of the site. Two additional potential receptors were reported to have been identified, although the specific addresses could not be verified.

The adjacent Oakland Veterinary Hospital has been identified as a potential "receptor" due to elevated soil vapor concentrations detected along the northwest property boundary of the station site. Additional assessment has been proposed (AECOM 2012) and approved by the ACEH (2012) to further determine soil vapor impacts associated with the site.

Based on the information above, no other potential receptors have been identified.

6.2 Potential Exposure Pathways

As shown on Figure 5, potential exposure pathways were evaluated. The exposure pathways determination was based on the information obtained to date.

Additional assessment has been proposed (AECOM 2012) and approved by the ACEH (2012) to further determine soil vapor impacts associated with the site, and the potential for soil vapor intrusion to the adjacent Oakland Veterinary Hospital.

7.0 Data Gap Analysis

Based on a review of the data collected to date, the following data gaps have been identified for additional assessment:

- The horizontal extent of impacts in vertically isolated water-bearing zones above 20 feet bgs (if any) need to be assessed downgradient of potential sources (e.g., the former WOT and USTs).
- The nature of the structure (that appears to be a sewer cleanout rather than a "vault") needs
 to be assessed to determine and to evaluate whether the structure is a source of elevated
 petroleum hydrocarbons detected in soil, soil vapor, and groundwater in the area of former
 monitoring well MW-1.
- Soil vapor impacts associated with the site, and the potential for soil vapor intrusion to the adjacent Oakland Veterinary Hospital, need to be assessed. Additional assessment has been proposed (AECOM 2012) and approved by the ACEH (2012).

8.0 References


- ACEH, 2012.Letter of Conditional Work Plan Approval for Fuel Leak Case No. RO0000409 and GeoTracker Global ID T0600102279, Unocal #1156, 4276 MacArthur Boulevard, Oakland, CA 94619. October 4.
- AECOM, 2012. REVISED Work Plan for Vapor Intrusion Investigation and Risk Assessment. August 27.
- ATC Associates, Inc., 2005. Quarterly Summary Report Second Quarter 2005, 76 Service Station No. 1156/WNO1112, ATC Project No. 75.75118.1112, 4276 MacArthur Boulevard, Oakland, California. Prepared by ATC Associates, Inc., 6602 Owens Drive, Suite 100, Pleasanton, California 94588, 925-460-5300. Dated June21.


- Cambria, 2005. Subsurface Investigation Report, Former Shell Service Station, 4255 MacArthur Boulevard, Oakland, California, SAP Code 135701, Incident No. 98995758, ACHCSA #3769. Prepared for Shell Oil Products US, Carson, California. Prepared by Cambria Environmental Technology, Inc., 5900 Hollis Street, Suite A, Emeryville, CA 94608.
- CRA, 2011. Fourth Quarter 2011 Groundwater Monitoring and Sampling Report. Dated December 16. Prepared by Conestoga-Rovers & Associates, 5900 Hollis Street, Suite A, Emeryville, California 94608.
- Delta, 2007a. Work Plan Site Investigation, 76 Service Station No. 1156, 4276 MacArthur Boulevard, Oakland, California, dated March 1. Prepared for ConocoPhillips Company, 76 Broadway, Sacramento, California. Prepared by Delta Consultants, 3164 Gold Camp Drive, Suite 200, Rancho Cordova, California 95670.
- Delta, 2007b. Site Investigation Report, 76 Service Station No. 1156, 4276 MacArthur Boulevard, Oakland, California, dated December 28. Prepared for ConocoPhillips Company, 76 Broadway, Sacramento, California. Prepared by Delta Consultants, 3164 Gold Camp Drive, Suite 200, Rancho Cordova, California 95670.
- Delta, 2008a. Draft Corrective Action Plan, 76 Service Station No. 1156, 4276 MacArthur Boulevard, Oakland, California, dated April 24. Prepared for ConocoPhillips Company, 76 Broadway, Sacramento, California. Prepared by Delta Consultants, 11050 White Rock Road, Suite 110, Rancho Cordova, California 95670.
- Delta 2008b. Aquifer and Utility Survey, 76 Service Station No. 1156, 4276 MacArthur Boulevard, Oakland, California, dated May 8. Prepared for ConocoPhillips Company, 76 Broadway, Sacramento, California. Prepared by Delta Consultants, 11050 White Rock Road, Suite 110, Rancho Cordova, California 95670.
- Delta, 2009a. Site Investigation Report, 76 Service Station No. 1156, 4276 MacArthur Boulevard, Oakland, California, dated September 8. Prepared for ConocoPhillips Company, 76 Broadway, Sacramento, California. Prepared by Delta Consultants, 11050 White Rock Road, Suite 110, Rancho Cordova, California 95670.
- Delta, 2009b. Initial Site Conceptual Model for 4276 MacArthur Boulevard, Oakland, California. January 26.
- Delta, 2010a. Work Plan for Additional Assessment, 76 Service Station No. 1156, 4276 MacArthur Boulevard, Oakland, California, dated March 1. Prepared for ConocoPhillips Company, 76 Broadway, Sacramento, California. Prepared by Delta Consultants, 11050 White Rock Road, Suite 110, Rancho Cordova, California 95670.
- Delta, 2010b. Additional Assessment Report, 76 Service Station No. 1156, 4276 MacArthur Boulevard, Oakland, California, dated October 21. Prepared for ConocoPhillips Company, 76 Broadway, Sacramento, California. Prepared by Delta Consultants, 11050 White Rock Road, Suite 110, Rancho Cordova, California 95670.
- EBMUD, 2012. 375 11th Street, Oakland, California 94607; P.O. Box 24055, Oakland, California 94623; 866-403-2683. Website accessed on April 11, 2012. http://www.ebmud.com/ourwater/water-supply.


- MBE, 2004. Summary of Potential Receptor Survey, 76 Service Station No. 1156, 4276 MacArthur Boulevard, Oakland, California, COP No. WNO.1112. Dated April 30.
- Morrow Surveying, 2008 and 2010. Monitoring well survey maps prepared by Morrow Surveying, 1255 Starboard Drive, West Sacramento, California 95691. Prepared for Delta Environmental. January 1, 2008 and August 24, 2010.
- San Francisco RWQCB, 2008. Screening for Environmental Concerns at Sites with Contaminated Soil and Groundwater. Prepared by California Regional Water Quality Control Board, San Francisco Bay Region, 1515 Clay Street, Suite 1400, Oakland, California 94612. INTERIM FINAL November 2007 (Revised May 2008)
- USGS 7.5-minute Topographic Map. Oakland East dated 1980 (photorevised from 1959).
- WRIR, 2003. Water Resources Investigation Report 02-4259, Hydrogeology and Geochemistry of Aquifers Underlying the San Lorenzo and San Leandro Areas of the East Bay Plain, Alameda County, California. By John A. Izbicki, James W. Borchers, David A. Leighton, Justin Kulongoski, Latoya Fields, Devin L. Galloway, and Robert L. Michel. U.S. Geological Survey, Sacramento, California. Prepared in cooperation with the East Bay Municipal Utility District and Alameda County Flood Control and Water Conservation District.

Attachment A

Figures











Figure 5 – Conceptual Site Model Transport and Exposure Pathways Construction Commercial Residential Ecological **Transport Exposure Exposure Pathways** Media Routes Ingestion Χ Χ Χ Surface Impacted Soil Oil Includes Surface Χ Χ **Dermal Contact** and Subsurface Dust Outdoor Inhalation Χ Χ Χ **Emissions** Air **Petroleum** Release Leaching to Groundwater Volatilization Indoor Inhalation Χ Χ Χ Air Ingestion Χ Χ Χ Impacted **Dermal Contact** Ground-Χ Groundwater water Inhalation of Χ Χ volatile emissions Confirmed completed pathway Ingestion Χ Χ Χ Potentially complete pathway Surface **Dermal Contact** Χ Χ Χ Water Exposure pathway may be complete for this receptor Inhalation of Χ Χ Χ Χ volatile emissions Exposure pathway is incomplete for this receptor Χ

Attachment B

Boring Logs



	Project No:	C101156		Clier		COP	Boring/Well No: MW-1B
	Logged By:	Alan Buel	nler		tion:	Oakland	Page 1 of 2
l 👝 🕠	Driller:	Gregg Dri			Drilled		
Delta	Drilling Method:			Hole	Diame		
I	Sampling Metho		Split Spoor	Hole	Depth	: 25'	
Consultants	Casing Type:	Sch 40			Dlame		
	Slot Size:	0.02			Depth		
	Gravel Pack:	2/12			Depth: er Depth:		
	Elevation:	······································	Northing:		C VVGCC	Easting:	
Well Completion ହି	6	Ę	G .	ample			
Backfill Casing Lough Lough Water Level	Moisture Content PID Reading (ppm)	Sample Identification	ŭ	Interval A	Soil Type	LITH	HOLOGY / DESCRIPTION
						Airknife to 5'	
Facilities Mark			1-			Brown and grayish	n-sgrren clay
			+	+			- Adda Assessment Control of the Con
			2-	+			
] 3				
			4-	\perp			
			+	+			
	299	MW-1B	5		CL.	Greenish-gray sar	ndy lean clay with gravel, 15%
		-5					l, strong odor, damp
			6-				
			7				
			8-				
**********	, , ,		10	vers autocenc			
-	173	MW-1B -10			CL		th sand, mottled with granular erial, 20% sand, strong odor,
		1 -10	11 ——	9888		moist	erial, 20% sand, strong odor,
			1,, +	30/4/53/00		1110/30	
			12				
			13				
_			1	-			
Mark Manushoto			14			MANUMANUMANUMANUMANUMANUMANUMANUMANUMANU	A
-			-	_		The state of the s	
	952	MW-1B	15		CL	Brown sandy clay,	, fine-course sand, 35% sand,
	ĺ	-15	16			strong odor, damı)
			17—	+-			
			1.0 +				
			18				
			19				
						common field and have been stated and a first of a state of the control of the co	
	19	MW-1B	20		ÇL	Black sandy lean	clay with gravel, 30% sand, 10%
	17	-20	1		ÇL	gravel, strong odd	
			21 —		CL.		sand, 25% sand, some odor,
			22			damp	

		Project	+ No:	C101156		Ċ	ient:	COP	Boring/Well No: MW-1B
		Logged		Alan Buehl	·lor			COP Oakland	Page 2 of 2
İ		Driller:		Gregg Drill			cation: ste Drillec		Page 2 Oi 2
	+->				ung			· ·	· [
Del	La	Drining	g Method:	HAS	··· c -		ole Diame		1
			ing Method		Split Spo		ole Depth		,
Environm				Sch 40			ell Diame		·
Consulta		Slot Siz		0.02			ell Depth		1 1
Inc.	,	Gravel I	Pack:	2/12				r Depth: 23.5'	1
ĺ						∑ Sta	atic Wate	er Depth:	
Well		Elevatio			Northing:	:		Easting:	
Completion	ब्	ا ہے ا	- Bu	no C	fg	Sample	e ا س		1
	Water Level	Moisture Content	PID Reading (ppm)	Penetration (blows/6")	Depth (feet)	i	ı ā	1.22	
Backfill Casing	قِ ا	l oist	8 g	ow	i i	<u>ğ</u> ?	- =	Litr	HOLOGY / DESCRIPTION
Backfill Casing	₩	Žυ	١ĕ,	Pen (bl	g l	Recovery	ž S		, , , , , , , , , , , , , , , , , , ,
	<u> </u>	4'	<u> </u>	_	1°	1 × -			
	1 '	1	1		23				0.707
.	↓_ ′	1	1	1		1	CL	Brown sandy grav	vely clay, 25% sand, 10% gravel,
l	▼	1	1	1	24			saturated, mild od	
l!] '	1	1	1			CL	Brown sandy clay	, 15% samp, mild odor, damp
<u> </u>	1	1 1	44	MW-1B	25		4		
	1 '	1 1	1	-25	25			Total Depth	= 25'
	1 '	1 7	1	1	1 ¬		7		
1 7	1 '	1	1	'	26		7		The second secon
	1 '	I = I	1 '	1	-	\sqcap	4		
***************************************	1	(J	1 '	1	27		\dashv	aman dagana dagan kasada mik 1 dagadan ke dagan salam da 1 a a a a a a a a 1 1 1 1 1 1 1 1 1	
<i>i</i> 1	1 /	(-1)	1 '	,	-	—	-	THE STRAWNSON	
	1 1	1 1	1 '	· •	28	-	-		
<i>i</i> j	()	í J	1 '	1	-		4		VALUE OF THE PARTY
i	1 1	()	1 '	1	29	\leftarrow	4		
1 -	1 1	1 1	1 '	1		\leftarrow	4		
	1 1	i = 1	1 '	1	30-		_	Manual and Manual Property and Control of the Contr	
	()	i J	('	,	1 1	-	_		
	()	i J	('	1	31	—	_		
-	, ,	()	t '	1	1" _				
4 —	. 1	, J	('	1	32-				
<i>i</i>	ı J	. 1	('	1	132	4			
4	i J	. 1	1 ,	1	33]		
4	,]		1	1	133.]		
4	, ,	, ,	i '	1	124		7		
4	. 1	, [(· · · · · · · ·	1	34	1	7		
1	.]	, ,	1	1	1		7		
<i>i</i> —	.)	, J	()	1	35	-	7		4000
<i>i</i>		, J	()	1	1 →		7		
	. 1	.]	_i 1	1 '	36		7		- William Control of the Control of
		.	, 1	1	1 +	<u></u>	\dashv		
		.	, 1	1	37		-		
-]	.	, 1	1	1 +	$\overline{}$	4		
	1	.	, 1	1	38—	\leftarrow	\dashv		The state of the s
	1	.	, 1	1	1 -		-		
	- 1	.	, ,	1	39		4		
	- 1	.	, ,	1	1 -		4	Villariamini i i i i i i i i i i i i i i i i i i	
	1		, ,	1 '	40-		4		
	[, ,	1	1 - 1		4	***************************************	
	1	1	, 1	1 1	41		_		
]		, 1	į	1 1		_]		
	1	1	, ,	1 1	42	<u> </u>			
	1		. 1	1 1	172]		
			1	1 1	43		7		
	1		1	1	143-		٦	West Attached to the state of t	
	1	1		()	1,,]		7	The State of the State of Education of the Contract of Contract Contract of Contract	Control of the Contro
1	ı		J	, ,	44		-1	and december of the second section of the	

	Project No.: 2235 Boring: BZ/MWZ Plate: APPENDIX
ERI FANDROMENTAL	Site: Tosco 76 Service Station 1156 Date: 7/16/99
ENVIRONMENTAL RESOLUTIONS, INC.	Drill Contractor: Woodward Drilling
Sample Method: Split	Spoon Geologist: MARK S. DOCKHM
-	Bore Hole Diameter: 8" Signature fault Si Tarte
	st of Southernmost Driveway Registration: R.G. 4412
	rthur Boulevard Logged by: Dylan Crouse
(N) / / / /	
	GEOLOGIC DESCRIPTION
	GEOLOGIC DESCRIPTION
12/40/40/4	
	Clay dark greenish gray, mottled redish grange.
	Clay, dark greenish gray, mottled redish orange, some coarse—grained sand, slightly damp, high plasticity, (35% sand, 65% clay)
	nigh plasticity, (35% saita, 55% clay)
-5-11 20	
[0] 11 CU	I I
	15% fine gravels up to 0.5" 20% sand
10-18 0	15% fine gravels up to 0.5", 20% sand, medium-grained, damp
	Silty clay, orange brown, mottled green gray, (35% silt, 65% clay), moist, medium plasticity
15 21 130	
CI.	
20 29 20	gravelly clay, light yellowish brown, (40% fine gravel, 60% clay), medium plasticity, very moist, black staining
	moist, black statung
	Sandy clay, trace of silt, yellowish brown, wet,
¥ //ML	Sandy clay, trace of silt, yellowish brown, wet, medium plasticity, (35% sand, 15% silt, 50%
25 45 18	
	Total depth at 26.5 feet.
	Total depth at 26.5 feet. Groundwater encountered at 23' 6".
	Groundwater encountered at 23 6.
 .	
 	
<u> </u>	هٔ ا
<u> </u>	
	·
	Diameter.
	i i i i i i i i i i i i i i i i i i i
N: 2235B002	

•

	Project No: C101156					Clie	nt:	COP Boring/Well No: MW-2B
		Logged		Alan Bueh	ler		ation:	Oakland Page 1 of 2
		Driller:		Gregg Dril			e Drille	
Delt	ta	1	Method:				Diame	
	LU	1		: Split Spc	non	Hole		
Consulta	nts	Casing		Sch 40			i Diame	
		Slot Siz		0.02			l Depth	
		Gravel		2/12		▼ Firs		
1				-•				er Depth;
		Elevation	on:		Northing			Easting:
Well	-		5	c	_			
Completion	Water Level	원본	PID Reading (ppm)	Sample Identification	Depth (feet)	Sample	8	
<u> </u>	;;	Str.	p E	Sample	5	क ह		LITHOLOGY / DESCRIPTION
Backfill Casing	äte	Moisture Content		Sal	Į įį	Recovery	Soil Type	
8 Ö	≥		II.	ğ	ă	Red Int	٠,	
 					 	+-	 	Airknife to 5'
					-	+ + -	CL	Brown and greenish lean clay with sand
				ļ	1	 	1	Diowii aliu greensii lean day widi sana
-]			-	 	1	
					2	++-	1	
I					 	 	-	
					3	 	1	- PUM National Advantage and the second seco
I -					-		-	· · · · · · · · · · · · · · · · · · ·
					4	┼-┼	-	
-					l –	 	1	
			4.04	, , , , , , , , , , , , , , , , , , ,	5—	100000000000000000000000000000000000000	L	
			181	MW-2B	_		CL	Light brown/green mottled lean clay with sand,
I		-5			6	Session		15% sand, strong odor, damp
					l	33350		
					7	L		
						 		
					8	 		
					_]	
l —-					9]	
					·	 	1	
		-	^	55	10		١	
		I	0	MW-2B	_		СН	Greenish fat clay, dense, damp, odor
		I		-10	11	33533		
					_	3858		
		-			12			Parameter Commence (Commence Commence C
		1	ĺ]	
		- 1			13]	
		J						
		1			14			
		- 1	Į					
	- 1				15 —			
			120	MW-2B			CL	Green lean clay with sand, 15% med-course sand,
	[-15	16			damp, odor
	1							
P2 474 T 444	1	·			17			V-ALIANDA ANTENNA DE LA CANTA DEL CANTA DE LA CANTA DEL CANTA DE LA CANTA DEL CANTA DEL CANTA DEL CANTA DEL CANTA DE LA CANTA DEL CANTA DE LA CANTA DE LA CANTA DE LA CANTA DE LA CANTA DEL
*						lacksquare		The state of the s
					18	<u> </u>		THE REPORT OF THE PROPERTY AND ADDRESS OF THE PROPERTY ADDRESS OF THE PROPERTY AND ADDRESS OF THE PROPERTY ADDRESS OF THE PROPERTY AND ADDRESS OF THE PROPERTY
		- 1			-	<u> </u>		
		l			19	 		
****			İ		_	 	ļ	
			ا ہ	MIM OF	20	ACCESSED DESCRICTOR		
		- 1	8	MW-2B			CL	Dark borwn lean clay with sand, 15% sand, fine-
1,00,00,000				-20	21	0.684		med sand, damp, odor
						3333		
			[22 —			The state of the s
	-	1	1				•	


,

		Louis	4. 81	2101456	***************************************	Ct.			In Zistali Nia. MANAZ. TD
				C101156 Alan Buehle		Clie		COP	Boring/Well No: MW-2B Page 2 of 2
		Drille					ation:	Oakland	Page 2 of 2
Delt	- ~	1		Gregg Drilli	ng		e Drilled		
一レヒル	_a			od: HAS			2 Diame		
				thod: Split S	poon		e Depth		
Environme				Sch 40			l Diame		
Consultar	its,	Slot S		0.02			Depth		
Inc.		Grave	! Pack:	2/12				Depth: 23.5' er Depth:	
		Elevat	tion:	······································	Northing	<u>. V.</u> 5ta	ic wate	Easting:	-
Well							1	Lasting	
Completion	Water Level	Moisture Content	PID Reading (ppm)	Penetration (blows/6")	Depth (feet)	Sample	<u> 원</u>		
₩ 2	۳. ب	istu	g g	tra ws/	"	Recovery Interval	Soil Type	LITH	OLOGY / DESCRIPTION
Backfill	/ate	8 %	٦	ene	l g	cov	Soil		·
a 0	5		<u></u>	a. ~	ă	Re			
					23				
					25]	Brown lean clay w	ith sand, 25% sand, some gravel,
					24—		CL	mild odor	
							CL	Black/brown mottl	ed clay, damp, mild odor
			190	MW-2B	25				
*				-25	23]	Total Depth	= 25'
					26-				
]	*** ***********************************	the second of th
					27-				
					- ' _		_		
*//me//					28]	MAIN MARKET MAIN CONTRACTOR OF THE STATE OF	The state of the s
					l →		4		
					29—		4		- Control of the Cont
					-		4		
					30-		4		
					-		4		
					31		-		
					│		1		
\$1000000000000000000000000000000000000					32-		1		
					-		1		
					33		┪		
_					-		┪		10 19 19 19 19 19 19 19 19 19 19 19 19 19
					34		1		
					l	-	1	· · · · · · · · · · · · · · · · · · ·	A STATE OF THE STA
4110,000					35		1		
]	l			ا م		1	414/4	The state of the s
		l			36		1	ATT 01-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-	
	l				37		1		
		l			3/]		AND THE PROPERTY OF THE PROPER
***********	j	-			38]		
					ا" ∟		1		
	1	- 1			39—		1		
							1	**************************************	
************					40		1	ARRIVANIA ARRAMANIA ARRAMA	
							1		
	ĺ				41-				
4	- 1						-		
14 10-41					42		-		
		1			-		1		
<u></u>					43		1		
							1	A 24 Per 12 Manual Australia	
	-		l		44		1		

.

.

.



	Drainet	No.	C101156		Clian	h.	600	Boring/Well No: MW-3B
	Project Logged		C101156 Alan Bueh	ler	Clien Locat		COP Oakland	Page 1 of 2
	Dellar		Gregg Drilling			Drilled		1 490 1 01 2
Delta	Drilling	Method:			Hole	Diame	• •	·
Delica	Sampli	ng Method	l: Split Spo	on	Hole	Depth	: 25'	
Consultants	Casing		Sch 40			Dlame		
	Slot Siz		0.02			Depth		
	Gravel	Раск:	2/12		▼ First ∇ Statio		Depth: rr Depth:	
	Elevation	on:		Northing		Vale	Easting:	-
Well		0	Ĕ		C(-			•
Sackfill OO Casing dumoing dum	Moisture Content	PID Reading (ppm)	Sample Identification	Depth (feet)	Sample > _	Soil Type		
Backfill Casing Water I	Sont	Control Region of the Control				Oii T	LIT	HOLOGY / DESCRIPTION
8	20	l m	I & P	Del	Recovery	Ŋ		
			<u> </u>		1		Airknife to 5'	
-					+++	CL		with sand, some gravel, no odor
				1				
				2				
				-	+			
section and find a				3	+			
				4_	111			
				4				
			M) 4/ 20	5—	NAMES 200 (2003) 200	οï		
		6	MW-3B -5	-		ÇĹ	Light brown/greel lodor	nish mottled clay, moist, slight
***************************************				6				
				_ ~	***************************************		**************************************	
,,,,,,				'				
·				8	1			
\dashv				-	1		A charles and the second secon	
				9 —	 			
				10				
		36	MW-3B			CH		n/black mottled lean clay with
			-10	11			sand, 15% fine sa	and, damp, mild odor
			1	-	53930			
			1	12—				
				13-				
pi-sen.							H.,H.,	
				14	+			
_					+			
		790	MW-3B	15—		CL	Light brown/gree	n mottled lean clay with sand,
,			-15	16-			20% fine-med sa	nd, damp, strong odor
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,				-				
				17	+			
-				10 -	 			
				18 —				
1-A-1-A-1-A-1-A-1-A-1-A-1-A-1-A-1-A-1-A				19	-			
				-	 			
		9	MW-3B	20		СН	Light brown fat cl	ay, damp, mild odor
		÷*	-20	21			27.55.75.8617.1818.1818.1818.1818.1818.1818.1818	
				~		CL	Dark brown lean	clay with sand, 15% fine sand,
		ļ		22 —			damp, mild odor	
							<u></u>	

.

		············	Projec	t No:	C101156			Clien	·+·	COP	Boring/Well No: MW-3B
					Alan Buehle	er.				Oakland	Page 2 of 2
1			Driller		Gregg Drilli				Drilled		1 4 9 5 2 01 2
	Delt	- 2		g Metho	HAS				Diame		
	Dell	.u	Sampl	ing Mei	thod:	Split Spo					
	Environme	ntal	1						Diame		
	Consultar		Slot S		0,02				Depth:		·
1	Inc.			Pack:						Depth: 23.5'	
ı	2.101				•					r Depth:	
			Elevation:			Northing	:			Easting:	
	Well Completion	<u>e</u>	41	C Reading (ppm)	nc (,	-	Sar	nple	a)		
		Water Level	Moisture Content	adi (m	Penetration (blows/6")	Depth (feet)	4	i	Soil Type		
- 1	Backfill	ĘĘ	oist	Re	netr ow:	£	ě	2	iž T	LITI	HOLOGY / DESCRIPTION
	Backfill	Wa	Συ	PID (Per (bl) j	Recovery	Interval	Š		
ŀ							<u>~</u>			- 11-11-11-11-11-11-11-11-11-11-11-11-11	
ĺ						23					
1						-	-	2000		nderekora - in a resperies i secono este este en este este en este este est	
						24	 			Light brown lean (clay with sand, 30% fine-med
	*****			15	MW-3B	_		200250	CL	sand, moist, very	elight odor
					-25	25	3,93,939	(340)5460		Total Depth	= 25'
	_									Total & open	
- 1						26					
l	7									***************************************	da da da da da da da da da da da da da d
						27					
ł						28 —					
- 1	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,					28					
ľ	**********					29 —					
			İ	I		-					
-						30					
ı						l				AND CONTRACTOR OF THE CONTRACT	
						31		\vdash			
						32					
	· · ·										beautiful and the first and the second secon
1	·					33					
		ı									
						34				100-100-100 100 100 100 100 100 100 100	7- 1
Į			ľ								
						35				ar fallif a fir a beneficiologica delle se des se se des se con con describit de conducto del con contrar de co	
1		İ				26	-				
			1			36					
			Ì	- 1		37					
						38 ——				Marie Book (All 1864) A B B B B B B B B B B B B B B B B B B	
l											and the second s
						39		 		Activities but the fire and a surface and a	
	-										
						40					
l						_		\vdash		Tree-rest values con restant Almont Street 1	
						41		$\vdash\vdash\vdash$			
	_					-		$\vdash \vdash \vdash$			
					,	42		$\vdash \vdash \vdash$			A
											
				-		43					
			- 1								
	1	1				44				1	

	pject No.: 2235 Boring: B4/MW4 Plate: APPENDIX	
/ / S FROSTONIES TAL	e: Tosco 76 Service Station 1156 Date: 7/16/99	_
Sample Method: Split Spoo	ll Contractor: Woodward Drilling Geologist: WARK STOCKUM	
	Bore Hole Diameter: 8" Signature / Janh > Auch	-
<u> </u>	Southernmost Dispenser Registration: R.G./4412	_
<u> Island Parallel Hig</u>	h Street Logged by: Dylan Crouse	<u>.</u>
	GEOLOGIC DESCRIPTION	
	4 1/2" asphalt	a
	Clay, greenish gray, mottled, orange slightly damp, high plasticity	
	slightly damp, high plasticity	3 1
5-17 309		17
		g
		Portland
		B
10- 22 253 1		
10 CH	trace of medium-grained sand, slightly moist	ut:
 		Grout
15-19 4		12
	moist	2
H-1 F-2		Size:
20 28 4		1 1
20 28 4	brownish yellow, black staining, 20% gravel, 20% medium-grained sand, moist	Sand
		"
¥ ===	111 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	d
	brown, mottled, olive yellow, moist, black staining	a
25 36 0	:::::::::::::::::::::::::::::::::::::	6
	Tabal danth at 905 feat	Size
	Total depth at 26.5 feet. Groundwater encountered at 23.6 feet.	Slot
	·	<u> 22</u>
		,
		į,
		ij
		Diameter
		len
		Casing
		2
FN: 223578004		

Del	ta		i By: Method:	C101156 Alan Bueh Gregg Dril HAS : Split Spo	ling	Lo Da Ho	ent: cation: te Drilled le Diame	eter: 8"	Boring/Well No: MW-4B Page 1 of 2
Consulta	ants	Casing Slot Siz Gravel	Type: ze:	Sch 40 0.02 2/12		We	ell Diame ell Depth st Water	25'	
		Elevati	on:		Northing	∑ Sta		er Depth: Easting:	
Backfill Casing uoiseld Mell	Water Level	Moisture Content	PID Reading (ppm)	Sample Identification	Depth (feet)	Recovery Solutions	ă		HOLOGY / DESCRIPTION
		 			_		1	Airknife to 5'	1 1.1 d
					1		GC	Brown clayey grav	/el with sand,
					2—		-		
					3-				
***************************************					4				
,					5—		GW	T	el with sand, cobbles up to 4"
***************************************			2.1	MW-4B -5	5 —		SW-		graded sand with silt and , 20% gravel, no odor
					6			gravery so to sacra	
					7		_		
141.0014000					8	 	_		
					9—		1		
			4404	MW 47	10	3332333 3333			d 111 - 111 CON 51 - 1
			1401	MW-4B -10	11		SW-	strong odor	sand with silt, 60% fine sand,
					-				
					12 —		4		
		:			13				
					14		_		ANALYSIA ANALYSIA ANALYSIA ANALYSIA ANALYSIA ANALYSIA ANALYSIA ANALYSIA ANALYSIA ANALYSIA ANALYSIA ANALYSIA ANA
			19.5	MW-4B	15—		CL	Brown/green mot	tled lean clay with sand, 15% fine
				-15	16			sand, some odor	
					17				
					18				
					-				
g144 - 11 - 11 - 11 - 11 - 11 - 11 - 11			ı		19			***************************************	
				MW-4B	20		CL		led sandy lean clay, 30% fine-
sauce tradicione				-20	21 —			med sand, some	odor
					22		7	1.470	

		,								·	
,		1		C101156			Clien		СОР	Boring/Well No: MW-	4B
Ì				Alan Buehle					Oakland	Page 2 of 2	
	- ~	Driller		Gregg Drilli	ng			Drilled			
Delt	.a		g Metho ling Me		C-11+ C-			Diame			
Environme				Sch 40	Split Sp	oon		Depth Diame			
Consultar		Slot S		0.02				Depth:			
Inc.	1637	1	l Pack:			\blacksquare			Depth: 23.5'		
2116.				•					r Depth:		
Well		Elevat	·	I	Northin	g:			Easting:		
Casing Casing	Water Level	Moisture Content	PID Reading (ppm)	Penetration (blows/6")	Depth (feet)	Recovery g	Interval aldu	Soil Type	LITI	HOLOGY / DESCR	IPTION
			<u> </u>		23 —	<u> </u>					
					23 -						
					24	1					
			10	MANAL 4 P	-	22,545.5		CI	Droup loss store 4	00/ fine med as = 1	I como ada-
0.6-3 (F.A.7 M.)00M			19	MW-4B -25	25 —	10000		CL	Brown lean clay, 1 Total Depth	.0% nne-med sand	, some odor
				2.0		+	$\vdash \vdash$		Total Depth		
					26 —	 	$\vdash \vdash$			100 100 100 100 100 100 100 100 100 100	
					27 —						Action of the second se
					28	-					· · · · · · · · · · · · · · · · · · ·
***************************************					29 —						
			·		30 —						
					-	-					
*****					31						
					32 —						
***************************************		:			33—	\vdash				//A	
					34 —						
					35						
					36 —						
_						-					
4,000,00					37						
IAMAN-					38						The state of the s
ob y a final hander o					39						
					40 —						
· · · · · · · · · · · · · · · · · · ·					41						
					42 						
					_						Value in the state of the state
					43 						
					44 —						

•

	Project No.: 2235 Boring: MW5 Plate: At		_
ENVIRONMENTAL RESOLUTIONS, INC.	Site: Tosco 76 Service Station 1156 Date: Drill Contractor: Woodward Drilling Company, Inc.	8/29/01	
	Spoon Geologist: JOHN BA BO		
Drill Rig: BK-81	Bore Hole Diameter: 8" Signature: 16/10		-
	le of MacArthur Boulevard Registration: R.G.	4313	_
approximat	ely 40 feet north of site Logged by: 'Rob Saur		-
		4. 4	ļ
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		AN SERVER	
	6" Concrete	77 777	
			1
			1
-5-	CLAY WITH SAND AND TRACE OF CDAYEL . specials		Cemen
23 8.3 💆	CLAY WITH SAND AND TRACE OF GRAVEL: greenish gray, moist, high plasticity, fine—grained sand, fine—grained poorly—sorted subangular gravel.		3
CI CI	ine-grained poorly-sorted subangular gravel.		덤
			1 4
10			Portland
27 7.7	SANDY CLAY: orange brown, moist, low plasticity, fine-grained sand.		4 '
 	inte-granied sand.		Grout:
			שׁ
			آ_ ا
57 11.2	SANDY SILT: orange brown, moist, low plasticity,		SF
	fine-grained sand.		
			Size:
			1
20 30			Sand
			S
			ام
38 7.7	light brown, wet.		0.020
25 00 111			1 1
	Boring Terminated at 25 feet. Boring converted to groundwater monitoring well.		Size:
	Groundwater encountered at 6 feet.	·.	
		· .	Slot
-			
			72
			ter
			Diameter
			Dia
			п 99
			Casing
			J

Drill Rig: BK-81 Location: Western side approx. 30	feet north of Shell station Logged by: Rob Saur	8/29/01 DBBITT 4313
		Rit Sea
	6" Concrete	77 777
-5- 24 10.6 [♥]	CLAYEY SILT: greenish gray, very moist, medium plasticity.	
19 10.0 MI	light brown, trace of fine—grained sub—angular sand (approx. 5%).	
24 6.0	CLAYEY SILT WITH SAND: light brown, fine-grained sub-angular sand (approx. 15%).	
20-48 7.7 SM	SAND WITH SILT: orange brown, wet, medium- grained well—sorted well—rounded sand.	
25 8 **	Boring terminated at 25 feet. Boring converted to groundwater monitoring well. Groundwater encountered at 5.5 feet.	
		-
TN: 28308098		<u> </u>

	Project No.: 2235 Boring: MW7 Plate: A		
Maria Orania III.		8/29/01	_
Sample Method: Split Sp	Orill Contractor: Woodward Drilling Company, Inc.	ADD Tmm	_
	Bore Hole Diameter: 8" Signature: 10HN B. Be	OBBITT -	
Location: Western side	of MacArthur Boulevard Registration: R.G.	4313	_
approx. 40 fe	et north of High Street Logged by: Rob Saur		
		ACT STATES	
	6" Concrete	77 777	7
			4 .
			1
-5-50 25	SANDY SILT: brown with bluish groon mottling		Cemen
5" 25	SANDY SILT: brown with bluish green mottling, moist, low plasticity, 40% fine—grained sand.		
		H	넘
			Portland
10			E G
36 236			.1
			Grout:
MI			9
15 ♥			
35 8.9	light brown, wet.		F
	•		Size:
20			
25 57			Sand
			ַ מֿ
			g
50 19.3	reddish brown, 30% medium-grained sand.		0.020
25 5	Boring terminated at 25 feet.	<u> </u>	٦
	Boring converted to groundwater monitoring well.		Size:
	Groundwater encountered at 15 feet.	ļ	
		-	Slot
			2"
	·		13
	·		H
			Diameter:
			am
			Casing
			Cas
		1	

	Project	No: C10	1156151	 [Client:	Conoco	Phillins		Well No: MW-8		
	1		bitha Cr				MacArthur Bouleva	rd	Date Drilled: 10/30/07		
— 11]	-	Orilling &	-		Oakland, CA Page 1 of 2					
Delta	Drilling	Method:	HSA		Hole D	Diameter:					
			d: Split S			Depth: 25	= First Water				
Consultants			chedule 4	10 PVC		iameter:		_			
	!	e: 0.01 (epth: 25		▼	= Static Groundwater		
		Pack: #2 Elevatio		Nor	thing	Vater Dep	Easting	*	= Selected for lab		
	Lievation			1.0.			Labering		analysis		
Well Completion		б	5	Đ Si	ample						
Static	Moisture Content	S Reading (ppm)	Sample Identification	اق	' 1	Soil Type			/ 		
Backfill Casing Hotel	loist	Re (pp	Sam	뒱	Interval	[]	LITHO	LOGY	/ DESCRIPTION		
Bac	50	PID (I	Idei	Depth (f		Ň					
Well Box					<u> </u>		Concrete = 6	15			
						CL			brown; medium soft;		
—				1					city; low toughness;		
			ம	1 、十					; moist; (0,0,100)		
			Air-Knife	2					<u> </u>		
			1	3——							
Neat Cement			⋖								
				4	1						
						.					
	moist	0.1	@ 5	 5——	A		l lean clay: bl	ack: me	edium stiff; medium		
	1110150	0.1	9:46						ess; some fine sand;		
				6					sub round gravel;		
				7			moist; no odo				
				17—							
				8——							
				9							
				+							
	moist	0.2	@ 10*	10			Tan: some ora	nge m	ottling; trace roots;		
	1110130	0.2	9:51						slight odor; (5,15,80)		
				11-	1						
				1,2			* ****** ** ** ** ** ** ** ** ** ** **		AR 111 311 12 12 31 311 4 P. P. P. P. P. P. P. P. P. P. P. P. P.		
				12					U 10 4 0 1 4 1 1 4 1 1 1 1 1 1 1 1 1 1 1		
				13							
				14							
			1	+							
	maist	0.2	@ 15*	15			Cando das		ongo mottling. Lagar		
	moist	0.2	9:56		- 	CI			ange mottling; trace lining; medium stiff;		
			9.50	16-					d toughness; sand fine		
			Ì		Y		grain; moist;				
				17			g,o.oc,	3001	LATITICAL		
			1	18							
				<u> </u>							
	moist	0.2	@ 20*		1 1				plasticity; low		
		}	10:P37	/			toughness; (0	,30,70))		
			}	20 —	*				18 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		
				+					THE I STATE OF THE		
- Section 1971 - Section 1971				21 —		S S					
				_ +							
				22					er an er er get a trette i til er eller selve er annannen er annan skalt at skalt i til er er		
	·										

Well No: MW-8 Client: ConocoPhillips Project No: C101156151 Date Drilled: 10/30/07 Location: 4276 MacArthur Boulevard Logged By: Tabbitha Croy Page 2 of 2 Driller: Gregg Drilling & Testing Oakland, CA Delta Drilling Method: HSA Hole Diameter: 8" Sampling Method: Split Spoon Hole Depth: 25' Well Diameter: 2" **Consultants** Casing Type: Schdule 40 PVC Slot Size: 0.010" Well Depth: 25' ▼ = Static Groundwater First Water Depth: 23' Gravel Pack: #2/12 * = Selected for lab Elevation Northing Easting analysis Well PID Reading (ppm) Sample Identification Depth (feet) Completion Sample Moisture Content Soil Type Static Recovery Interval LITHOLOGY / DESCRIPTION Water Level ∇ 23 Clayey sand; tan; orange mottling; medium SC 24 grain; poorly graded; loose; wet; no odor (0,65,35)25 26 Total Depth = 25 feet bgs 27 28 29 30 31 32 33 34 35 37 38 39

		Project	No: C10	1156151		Clie	nt: Con	ocoPh	illing		Boring No: SB-1		
		1 .		bitha Cro					acArthur Blvd		Date Drilled: 11/6/07		
	•	1	Gregg [-		0:	Page 1 of 2						
Del	ta	i	Method:	-	_		e Diame		•	<u> </u>	1: -9		
DCI	Ca			d: Contin	uous		e Depth				= First Water		
Consulta	ants	Casing				Well Diameter: NA							
		Slot Siz					Depth						
			Pack: NA			Water			, <u>, , , , , , , , , , , , , , , , , , </u>	, static Groundwater			
					otion N				Easting	. *.	= Selected for lab		
									3		analysis		
Well			6	L.	(:	Comple				***************************************			
Completion	Static	Moisture Content	PID Reading (ppm)	Sample Identification	Depth (feet)	Sample	8						
E G	Water	ist. nte	Sea opn	m ific) P	Recovery	Soil Type		LITH	OLOGY /	DESCRIPTION		
Backfill Casing	Level	၂ 😤 ပို	الق ق	Sa	ept	te co	Soil			•			
a 0				PI	۵	å E							
								<u> </u>	Asphalt - 6"				
						 			Fill; tan, with m		el: surrounded:		
e e					1-	 					s; soft; moist; (45,5,50)		
E I				ا س		1			no plasticity, mg	in toughnes	13, 3011, 1110131, (43,3,30)		
Veat Cement				Air-Knife	2	 			Fill; some clay:	brown: ora	vel medium to coarse;		
at			,	`				l	sub rounded; so				
Ne e				<u>A</u> i	3	1-1-							
	∇							l		**************			
	_				4	1			@ 4' large rocks	: subround:	; wet; trace fine sand		
									and clay; (90,5,		, wee, trace fine sailu		
		wet	6.2		5	A			una cia / (30/5)	<u> </u>			
					_					•			
					6			CL	Lean clay: olive	green: sor	me fine to medium sand;		
						₩ ↓		. – –			lium stiff; medium		
		wet	326	@ 7*	7	A			plasticity and to				
				8:39					(0,30,70)		20, 00.00.9 000.		
					8—	₩ ₩							
		wet	165	@ 8.5		A			Some black spec	 CS			
				8.42	9—						**************************************		
					10								
		wet	221	@ 10	10				Some black and	red stainin	g		
				8:45	11								
					11								
Ø					12—	₩ +			Sand fine to me	dium grain	(0,40,60)		
		wet	140	@ 12*		__		L_			**************************************		
				8:48	13—	2001		sc	Poorly graded	sand with	clay; brown; some		
						₩ +			• • • • • • • • • • • • • • • • • • • •		ay staining; sand fine to		
		wet	118	@ 13.5	14 —						wet; strong odor		
· ·				8:50				I	(0,70,30)		The state of the s		
M					15	₩ ₹		l			The second secon		
		wet	133	@ 15		1							
				8:52	16								
-					_				Red brown with	orange and	l olive green mottling;		
					17			L	medium stiff; (0	,50,50)			
		wet	419	@ 17		A		CL	Lean clay; som	e fine to m	edium sand; red brown		
				8:56	18				.,,		lack specs; medium		
						₩ +					nedium stiff; wet; strong		
		wet	1056	@ 18.5*	19	A			odor; (0,35,65)		en en en en en en en en en en en en en e		
				8:58									
					20 —	₩					The second secon		
		wet	148	@ 20		A			Stiff; trace med	ium gravel;	sand medium grain;		
器				9:02	21			1	(5,35,60)				
								1					
		wet	152	@ 22	22 —	₩ +			Some black stai	ning	*** * * * * * * * * * * * * * * * * *		
				9:04							The second secon		

Delta consultants	Logged Driller: Drilling Sampli Casing Slot Siz Gravel	By: Tab Gregg I Method: ng Metho Type: NA ze: NA Pack: NA Elevatio	d: Contir	Testing nuous	Loca Hole Hole Well Well	Diame Depth: Diame Diame Depth: Water	276 Makland ter: 4" : 35' ter: NA	acArthur Blvd , CA	Boring No: SB-1 Date Drilled: 11/6/07 Page 2 of 2
Stati Wate Leve	ist.	PID Reading (ppm)	Sample Identification	Depth (feet)	Recovery Interval	Soil Type		LITHO	LOGY / DESCRIPTION
Neat Cement	wet wet wet wet	61.1 78.1 41.2 53.9 76.8 38.3	@ 25 9:13 @ 27 9:15	23 — 24 — 25 — 26 — 27 — 28 — 30 — 31 — 32 — 33 — 34 — 34 — 34 — 34 — 34 — 34			sc -	coarse; low plastic (5,40,55) Tan; some black s coarse sand; trace stiff; (5,35,60) Red brown with or sand fine to mediu No orange mottline (0,40,60) Stiff; red brown; s specs; sand fine g Medium stiff; red plasticity and toug Poorly graded sa sand medium to co	and with clay; trace fine gravel; parse; red brown and orange;
				35 — 36 — 37 — 38 — 40 — 41 — 42 — 44 — 44 — 44 — 44 — 44 — 44				black specs; grave (5,65,30)	hard but crumbles easily; some el sub angular; wet; odor; = 35 feet bgs

		Project	No: C10	1156151		Clie	nt: Con	ocoPh	illips		Boring No: SB-2	
	ŀ	Logged	By: Tab	bitḥa Cro	у	Loc	ation: 4	276 M	acArthur Blvd		Date Drilled: 11/5/07	
	, h	Driller:	Gregg D	Testing	g	O	akland	Page 1 of 2				
Delt	7	Drilling	Method:		Hole	e Diame						
DCI	LU		g Metho	นดบร		e Depth			▽ =	First Water		
Consulta		-	Type: NA				l Diame			_ _	- That Water	
Consulta		Slot Size				Depth:		•	₩_	Static Groundwater		
			e. NA Pack: NA				t Water		221	<u> </u>	- Static Groundwater	
	F	Graveri					t water	Depth			Colored E. 11	
		Elevation				Northing			Easting	7 =	Selected for lab	
Well							т —				analysis	
Completion			ρ̈́	c o	£	Sample	1					
	Static	Moisture Content	PID Reading (ppm)	Sample Identification	Depth (feet)		Soil Type					
Backfill	Water	ž ž	Reppr	tific	뜐	Recovery	=		LITHO	LOGY /	DESCRIPTION	
acl	Level	ق۲	<u>ور</u> (e Si	e D	ite io	S	ł				
m 0	İ		۵	2	۵	l & r		Ì				
						1 1		i	Asphalt - 2"			
🚆	ŀ	İ			-	 		CL	Lean clay with g	ravel: tan	: low to medium	
t	Ī	- 4			1 —	++-		CL		errore error	The second of the second	
me		İ		σ,	-		-				tiff; moist; gravel fine	
je				ife	2				to medium; (30,0	,70)		
Neat Cement	ļ	İ		Air-Knife	. -				*****			
ja 📕	ļ			[<u>î</u> [,							
ž	-			Ϋ́	3			l				
	Í				-							
	ļ				4	 		 				
	ļ				-	+		 				
			000.0		5—	200000000]				
	Ì	moist	932.0	_					Tan with olive gre	en mottlin	g; medium plasticity	
	ľ	- }		8:43	6				and toughness; so	ome silt; tr	race fine sand; moist;	
	ļ				J			1	strong odor; (0,10	0,90)		
	į									Armoral		
2	l.	moist	1599	@ 7	7-	A			Red brown specs	some roof	ts; medium stiff; trace	
10				8:45	-						o, nedulii selli, trace	
	ĺ	- 1		0.45	8			J	fine gravel; (5,25	,/0)		
	I		1207	O 0 F*	-	JOHNSON A	-188					
	ľ	moist	1307	@ 8.5*	9—			L	(5,40,55)			
	ľ	Ī		8:47				SC	Clayey sand; tan	and olive	green; some red	
	Ī				40	1			brown mottling; r	ed specs;	sand fine to medium	
		moist	1528	@ 10	10 —	A A					ly; no plasticity; gravel	
	ŀ			8:49					fine grain; moist;			
	į			0	11							
	1					33333	s Carroll (special)		Loose; some black		 	
	l				12-	<u> </u>	100	CL			e olive green mottling;	
	Į	moist	1335	@ 12*	l .	1		8			some black specs; low	
	ļ			8:51	12				plasticity; high to	ughness; r	moist; strong odor;	
	ŀ				13-	₩ ₩			(0,35,65)		eminer men en en Er (, , , , , , , , , , , , , , , , , ,	
		moist	1227	@ 13.5	١ '	A				um: trace	fine gravel; red brown	
	ľ			8:53	14				and tan; some oli			
	1	ļ		0.55		1]	and tan, some on	ve green;	(3,23,70)	
		m =!-+	767	@ 1 =	15 —	A A		[
	1	moist	762	@ 15	[.			J			icity and toughness; red	
	1			8:55	16			1	brown; some olive	e green; s	ome black specs;	
	ļ				10				(0,35,65)			
	1				۱ ـ ـ ا	₩ +						
		moist	308	@ 17	17	A		XI	Red brown; some	nink stain	ing: olive green	
	ľ			8:57				1	mottling; crumble			
<u> </u>	ļ			0.57	18		-			s easily; s	some line gravel;	
	ļ		100	G 10 -			-	XI	(10,35,55)		reconstruction and the second	
		moist	182	@ 18.5	19—	1		X			The second contract with the contract of the c	
	1	I	! 	8:59					Red brown; doesn	n't crumble	e easily; some fine sand;	
	}	1			ا مرا				odor; (0,40,60)			
	<u> </u>	moist	124	@ 20*	20 —	A A					The second secon	
	l l			9:04	[Medium coft: mor	dium cand	; trace fine gravel; some	
	j	l		J.07	21 —							
-		,,,,,,	220	6 22	.		-		black specs; low p	plasticity;	nign toughness;	
M	又	wet	228	@ 22	22	▼		L .	(10,40,50)			
				9:06				SC	Clayey sand; red	d brown wi	ith orange mottling;	

Driller: Gregg Drilling & Testing Drilling Method: HSA Sampling Method: Continuous Consultants Casing Type: NA Slot Size: NA Gravel Pack: NA Elevation Well Completion Well Completion Well Completion Well Completion Well Completion Well Completion Wetl	ater froundwater ed for lab sis
Delta Consultants Drilling Method: HSA Sampling Method: Continuous Consultants Casing Type: NA Slot Size: NA Gravel Pack: NA Elevation Well Completion Water Level Water Level Static Water Level Water Level Static Water Level Water Level Drilling Method: HSA Sampling Method: Continuous Hole Diameter: 4" Hole Depth: 35' Well Diameter: NA Well Depth: NA First Water Depth: 22' * Sample * Sample * Sample * Sample * Sample * Sample * Sample * Sample * Sample * Diameter: 4" * Sample * Sample * Sample * Sample * Sample * Sample * Sample * Diameter: 4" * Sample * Sam	ater froundwater ed for lab sis
Casing Type: NA Slot Size: NA Gravel Pack: NA Elevation Well Completion Water Level Static Water Level	ed for lab sis
Consultants Casing Type: NA Slot Size: NA Gravel Pack: NA Elevation Well Completion Water Level Static Water Lithology / Descre	ed for lab sis
Slot Size: NA Gravel Pack: NA Elevation Well Completion Water Level Water Level Static Water Level Static Water Level Static Water Level Static Water Level Static Water Level Water Lev	ed for lab sis
Gravel Pack: NA Elevation Well Completion Static Water Level Water Level Water Level Elevation Static Water Level W	ed for lab sis
Well Completion Static Water Level Volume Level Volume Soul 23 Sample Solecter Sanity Soul 24 Sample Solecter S	RIPTION
Well Completion Static Water Level Level Soil Type Soil	RIPTION
Well Completion Static Water Level Level Soil Type Soil	RIPTION
black specs; silty; sand fine to medium	
black specs; silty; sand fine to medium	
black specs; silty; sand fine to medium	
black specs; silty; sand fine to medium	m; fine gravel
	m; fine gravel
wet 55.1 Value of the state o	
□ wet 55.1 24 1	(15,50,35)
Cemented; very stiff; sand medium gr	
wet 51.2 @ 25* 25 brown; some orange mottling; (5,55,4	40)
9:30	
CL Lean clay; red brown and tan with or	range
mottling; some black space; modium	and the first than the second second
wet 14.6 27 A plasticity and toughness; sand fine gra	to the comment of the
28 odor; (0,40,60)	
Wet 21.1 29 A Red brown with tan mottling	
wet 13.7 30 The Black specs; stiff; trace fine gravel; lo	ou plantite.
high truighness: (5.35.60)	ow plasticity;
31 - Ingritouginiess, (3,33,00)	
Some pink staining	
wet 2.3 32 Medium soft; (5,40,55)	
33	
Red brown with black specs; very stiff	f; some fine
wet 11.1 34 sand; slight odor; (0,30,70)	
- Madium at 156 (0.20.80)	
35 Medium stiff; (0,20,80)	
36	
37	• • • • • • • •
37 TD = 35 feet bgs	,
38	
39———	* ** ** ** ** ** ** ** ** ** ** ** ** *
40	
41	
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	The state of the second
42	******
43	
44	

Project No: C101156151						Clie	nt: Con	ocoPhi	illips	Boring No: SB-3		
		,		bitha Cro	У				acArthur Blvd	Date Drilled: 11/2/07		
		Drillor	-	rilling &	-			akland		Page 1 of 2		
Del	lta	Drilling	Method:	_		Hole	e Diame			1.030 - 0		
レロ	lla	Samplin		d: Contin	uouc		e Depth			∇ = First Water		
		Sampini	-		uous				ļ	✓ = First water		
Consul	itants)	Type: NA	1			Diame		· }			
		Slot Size					l Depth:			Static Groundwater		
		Gravel F			t Water	Depth:						
		Elevation				Northing			Easting	* = Selected for lab		
Well		ļ						·	L	analysis		
Completion	Statio Water Level	str	PID Reading (ppm)	Sample Identification	Depth (feet)	Recovery Interval	Soil Type		LITHO	LOGY / DESCRIPTION		
									Concrete - 6"			
								CL	Silty clay; tannish	brown; medium plasticity;		
Neat Cement					1					o medium toughness; moist;		
E M				ဖျ			18.3		(0,0,100)			
ت الله ت	1			Ë	2		1		211 1 =			
ਕੂ ਕ				Air-Knife		 	151			······································		
2 🔳 —				Ā	3				@ 3' lean clave stif	f; medium plasticity; high		
	-				_	 		l .	toughness; moist;	control of the contro		
M ····					4	+ + -			tougimess, moist,	(0,0,100)		
					-	1	1			et market in the second of the control of the contr		
		moist	1.1	@ 5	5	1000			Campa black stuncts	at the same and business.		
		ITIOISC	1.1	_			4			s; tan; some red brown specs;		
				8:54	6				some medium san	d; no odor; (0,15,85)		
		1			. —			.				
II					7	*						
		moist	0.7	@ 7*	_	1 1			Some gray streaks	; (0,20,80)		
]			8:57	8							
数					0	*			·			
		moist	0.4	@ 8.5	_	***			Some black specs;	some white caliche; trace fine		
	7			9:00	9					um to coarse; (5,25,70)		
	1				_	Ţ	1			······································		
	-1	moist	0.6	@ 10	10	A	100		Tan with red brown	n mottling		
				9:02			1					
M	• •			""	11		1		• • • •			
							+					
4.0		miast	0.0	@ 12	12		1		B. 4 b			
		miost	0.8	@ 12	-	T	-			n; black specs; trace fine gravel;		
	-			9:04	13	N. San	-		(10,25,65)			
			0.0		l _	V A	-	.				
		moist	0.6	@ 13.5	14	T	-		A lot of black spec	s; crumbles easily		
				9:07	-		-		**			
					15	¥						
		moist	0.6	@ 15*	l	1			Very stiff; low plas	sticity		
		[]		9:09	16							
	1	1 1			ـ آا							
					17—	▼			More sand; some	silt; (5,35,60)		
M]	moist	0.8	@ 17	1 /	A				ed brown with tan mottling; soft;		
				9:11	٦				some black specs;	(0,35,65)		
					18—	■						
		moist	2.6	@ 18.5		A		1	Trace fine gravel:	meidum soft; medium palsticity;		
3				9:15	19 —				crumbles easily; s	the same consequences are supplied to the same of the		
				5.15	-			4	crombics easily, S	, (5,10,555)		
		wet	36.1	@ 20*	20	X						
	- ("	50.1		-			L				
	∇			9:21	21		- 20 16 19 1 - 20 16 19 1	SC		orly graded with fine gravel; sand		
					l –		-835			ed brown with tan mottling; soft;		
II	Į	wet	8.8		22—	*			loose; trace black	specs; wet; slight odor; (5,55,40)		
		1			~~					***************************************		

Consu	Project No: C101156151 Logged By: Tabbitha Croy Driller: Gregg Drilling & Testin Drilling Method: HSA Sampling Method: Continuous Casing Type: NA Slot Size: NA Gravel Pack: NA Elevation Well Completion Well Completion Rel 1								Diame Depth Diame Depth: Water	276 Makland ter: 4" . 35' ter: NA	acArthur Blvd , CA	▼ =	Boring No: SB-3 Date Drilled: 11/2/07 Page 2 of 2		
Backfill Casing	Sta Wa Le	tic ter vel	Moisture Content	PID Reading (ppm)	Sample Identification	Depth (feet)	Recovery g	Interval ald	Soil Type		LITH	OLOGY /	DESCRIPTION		
Neat Cement			wet wet	3.7 1.8	@ 25* 9:48	23 — 24 — 25 — 26 —		\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \		<u>c</u> ī.	brown Lean clay with and tan with ora	dium grain; sand; fine t	trace fine sand; red o medium; red brown g; some red specs; stiff; s; wet; no odor;		
			wet wet	0.7		27 28 29		A			Some black spe medium stiff; tr	ace fine grav	n and some tan; rel; (5,40,55) th red brown mottling;		
			wet wet	1.1		30 —		*	100		Tan; some red I sand; very stiff;	wet; (0,30,	ng; trace medium 70) to fine grain; wet;		
-		\	wet	1.8		33 — 34 — 35 —		+			A lot of black sp		wn with tan mottling; um grain; (0,25,75)		
						35 — 36 — 37 — 38 — 39 — 40 — 41 — 42 — 43 — 44 —					TE	= 35 fee	et bgs		

	Project N	lo: C10 :	1156151		Client: C	nocoPhillips	Boring No: SB-4	
	_		oitha Cro			4276 MacArthur Blvd	Date Drilled: 10/30/07	
	Driller: G	Gregg D	rilling &	Testing		Oakland, CA	Page 1 of 2	
Delta	Drilling M	1ethod:	HSA		Hole Dia	neter: 4"		
DCICA	Sampling	Method	i: Contin	uous	Hole De	th: 35'	∇ = First Water	
Consultants	Casing T	ype: NA			Well Dia	neter: NA		
	Slot Size	: NA			Well Dep	h: NA	▼ = Static Groundwater	
	Gravel Pa	ack: NA			First Wa	er Depth: 17.5'		
	ı	Elevatio	n	No	rthing	Easting	* = Selected for lab	
Well						<u> </u>	analysis	
Completion		PID Reading (ppm)	io	S G	ample a			
Static	Moisture Content	adi E	Sample Identification	Depth (feet)	terval d		N. 0.0V / D. 0.0D D. 1.	
Backfill Casing Hevel	lois	P R	sarr etifi	友		FILHO	DLOGY / DESCRIPTION	
Bac Cas	ΣΟ	吕	Ger	Dер	Interval	:		
AGR .					¥	Asphalt - 6"		
		l			e anne			
int				1		2020	o olive green; medium plasticity;	
m me		I	o)			_	ss; stiff; moist; some black	
Neat Cement		l	4ir-Knife	2		staining; (0,0,10	<u> </u>	
at			À					
N N		į	Air	3-				
				4				
		į						
	moist	7.5	@ 5	5	A	Very stiff; high to	oughness; some red specs; trace	
		1	3:30	6-		medium sand; o	dor; (0,5,95)	
		l						
				7	▼			
	moist	27.5	@ 8*					
			3:32	88				
	moist	25.3	@ 9	_	¥ .			
	HOISC	25.5	3:35	9		Orange mottling	THE STATE OF THE S	
		l	5.55	_	+			
	moist	11.5	@ 11	10		Tan some gray s	taining: stiff	
			3:37	-		van some gray s	turning, stir	
				11				
		i			₩		The second secon	
	miost	6.5	@ 13.5*	12	1	Tan and red brov	wn; some medium sand; slight	
		l	3:39	13		odor; (0,25,75)		
				10	₩			
	moist	5.5	@ 14	14		Trace fine grave	; (5,30,65)	
			3:40	_		X		
			0.15*	15	Y W			
	moist	0.8	@ 16*	-			ed brown and tan; slightly	
M			3:43	16			umbles easily; soft; no plasticity;	
				-			sand medium grain; moist; slight	
∇	wet	0.7		17	T A BE	odor; (5,60,30)		
		٠.,				l ow plasticity: e	and fine to medium; wet; (0,60,40)	
				18		LOW plasticity, S	and the to mediatif, wet, (0,00,40)	
	wet	1			4			
		-		19		Trace gray stain	ing	
				20		227 33911		
	wet	1.1		20	A		en en en en en en en en en en en en en e	
				₂₁				
				21 —		No plasticity; (0	,65,35)	
	wet	0.3		22	V			
		1		144	Q24.0	48		

Boring No: SB-4 Project No: C101156151 Client: ConocoPhillips Logged By: Tabbitha Croy Date Drilled: 10/30/07 Location: 4276 MacArthur Blvd Page 2 of 2 Driller: Gregg Drilling & Testing Oakland, CA Delta Drilling Method: HSA Hole Diameter: 4" Sampling Method: Continuous Hole Depth: 35' **Consultants** Well Diameter: NA Casing Type: NA Slot Size: NA Well Depth: NA ▼ = Static Groundwater First Water Depth: 17.5' Gravel Pack: NA * = Selected for lab Elevation Northing Easting analysis Well Sample Identification PID Reading (ppm) Depth (feet) Sample Completion Moisture Content Soil Type Static Recovery LITHOLOGY / DESCRIPTION Interval Casing Water Level CL Lean clay; tan to red brown; medium soft; 23 medium plasticity and toughness; some fine sand; Veat Cement wet 0.6 moist; no odor; (0,15,85) wet 0.6 With fine to medium sand; some black specs; 26 moist 0.4 @ 27* Olive green and tan; stiff; (0,0,100) 4:15 moist 0.4 29 30 No Recovery 31 32 0.5 moist Very stiff; trace fine gravel; some medium sand; low plasticity; high toughness; tan to red brown; 33 moist 0.4 (10,30,60)36 37 TD = 35 feet bgs 38 39 40

	Des	viect No. C	101156151		Clier	nt: Con	ocoPhi	llins		Boring No: SB-5
		-	abbitha Cro					inps icArthur Blvd		Date Drilled: 11/1/07
	D.,		g Drilling &		2000		akland,			Page 1 of 2
Delt	Dri	illing Metho	-	_	Hole	Diame	•			<u></u>
DCIU	.u _{Sai}		hod: Contin	uous	Hole	Depth:	: 35'		▽ =	First Water
Consulta	nts Cas	sing Type:	NA		Well	Diame	ter: NA			
		ot Size: NA			Well	Depth:	: NA		▼ =	Static Groundwater
	Gra	avel Pack:	NA		First	Water	Depth:	18'	[
		Eleva	ition	N	orthing			Easting	* =	Selected for lab
Well						· ·			L	analysis
Completion		Content PID Reading	Sample	[]	Sample	a				
	Static	Content D Readin	ple	Depth (feet)	<u> </u>	ſyp		i TTUO	LOCY /	DECCRIPTION
	Water 150 Level 5	S a s	i gar	뒱	Recovery Interval	Soil Type		LITHOLOGY / DESCRIPTION		
Bac Cas	20101 2		i de	Deg	Recovery Interval	S				
30								Asphalt - 5"		
- 数				-		en a company	CL -	<u></u>	areen: me	dium stiff; medium
				1	-		\ <u></u>	the second contract of the second contract of		me medium sand and
Neat Cement			au	+				trace fine gravel;	Table 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
<u>ම</u>		Ì	Air-Knife	2-				strong odor; (10,		22111137 1110134
t M st			À	_ +	\dashv			22.2.2.2.2.1 (101.		The same of the sa
N W			Air	3						
- 1				1, 7		1		* 10 YE 00 1		The second secon
				4						
	İ	1		5						
	m	oist 46	1 -		A					iff; low plasticity; high
			11:11	6—]				coarse sand; trace fine
		Ì						gravel; (10,30,60))	
				7—	* *					The second secon
	m	oist 68	-	-						red brown mottling;
			11:19	8-				some medium sa	na; (u,zu,	80)
		oist 63	8 @ 8.5	-		1		Low to medium p	lacticitu	
	""	10131 03	11:20					Low to inculant p	ioselercy .	
			12.20	-						
	m	oist 57	3 @ 10	10-						
			11:22		100 T	1				
										27 A 100 A American and an age of the contract
				12	33 ↓			(0.25,75)		
	m	iost 62		` _					; low plast	icity; meidum soft;
		ŀ	11:25	13			<u> </u>	(5,25,70)		
				1 _	¥	4				
	lm	oist 57				-		Crumbles easily;	(5,35,60)	
		1	11:27	-		-			a contrato a	
		noist 53	2 @ 15	15	¥ A	1	Š	Red brown with	olive areen	mottling; stiff; (0,35,65)
7		וטופנן אמ	11:30	.		100		Ven DIOMH MIELL	Juve green	(moccing, sciii, (0,33,03)
			11.50	16						
	1			-						A 124 M. A AMERICA TO THE TOTAL CO. 110 MINES OF
	lm	noist 15	7 @ 17*	17—	■	7				
	∇		11:32	, -						
				18	₩ +					
	l v	wet 10	0	19—			sc	and the second of the second o		nd olive; trace gravel;
		ļ		1,9	2814					e; soft; crumbles easily;
	Ì			20-	*			medium sand; fi	ne gravel;	wet; odor; (10,50,40)
	V	wet 53	-	'l _	↑					
		·	11:41	21 —						grain; trace fine gravel;
		. _	, ,						dium plast	icity and toughness; wet;
	\	wet 5		1//	*		8 -	odor; (5,50,45)		
			11:44	<u> </u>			7			·

	Project	No: C10	1156151		Clie	nt: Con	ocoPh	illips	Boring No: SB-5		
			bitha Cro					acArthur Blvd	Date Drilled: 11/1/07		
Dalta	1		rilling &	Testing			akland		Page 2 of 2		
Delta	1	Method:				Diame Depth			<u> </u>		
1		_	d: Contin	uous							
Consultants	Slot Size	Type: NA	`			l Diame l Depth:		\	▼ = Static Groundwater		
1	į.	Pack: NA				t Water		<u> </u>			
		Elevatio			Northing			Easting	* = Selected for lab		
			,				ļ		analysis		
Well Completion		<u>D</u>	Sample Identification	<u>it</u>	Sample	, n					
Static	Moisture Content	PID Reading (ppm)	ple	Depth (feet)	1	Soil Type		LITUO	LOCY / DESCRIPTION		
Backfill Casing Hater	Jois Tour	Re (pp	Sam	돭	tecovery Interval	i≅		LITHO	LOGY / DESCRIPTION		
Cas Cas	≥ 0	PIC	s Ide	De	Recovery	S					
٠٠٠٠ 🚺 مو				23 —	1		CL.	Lean clay; tan wi	ith red brown mottling; black		
ien	wet	51.8	•	24 —	A				medium soft; medium plasticity		
e de de de de de de de de de de de de de								and toughness; w	et; odor; (0,30,70)		
Neat Cement				25 —	<u> </u>						
lea	moist	7.3	}	-		-		Some fine to med	lium sand; moist; slight odor		
-				26		4					
						1		Stiff; (0,15,85)			
	moist	8.6		27 —	A	1			n with some olive green mottling		
				28							
				_	*						
	moist	11.4		29 —	1						
				-		-		Medium stiff; (0,3	35,65)		
	wet	16.8	@ 30*	30			sc.	Clavey sand: red	brown; some black specs; trace		
	Wet	10.0	12:07			-	-		medium grain; soft; loose; no		
	'			31					ight odor; (10,50,40)		
				32	*						
	wet	14.1		-	1	_		Some olive green	mottling; medium stiff		
			ļ	33 —		-			······································		
	moist	125		-	X	(124 ¹ 20	CL	Lean clay: light i	tan to olive green; stiff; some		
	IIIOISC	13.3		34 —		-			te black specs; low to medium		
		İ			+				oughness; moist; odor; (0,15,85)		
				35 —	7.00.00	Jan 2 Laboration	<u> </u>	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,			
				36—							
						4					
				37 —	 	-			- 25 foot hes		
]		-		-		10	= 35 feet bgs		
				38	+	-					
				-	1	┪	.				
				39 —]	1				
				40			1				
				-		_					
	}			41 —		4					
				-	1	-					
				42	+	-					
				-	++-	-					
				43 —	1-1-	7					
	1			44 —							
				144							

Project No: C101156151 Client: ConocoPhillips Boring No: SB-6 Logged By: Tabbitha Croy Location: 4276 MacArthur Blvd Date Drilled: 10/31/07 Driller: Gregg Drilling & Testing Oakland, CA Page 1 of 2 Delta Drilling Method: HSA Hole Diameter: 4" Sampling Method: Continuous Hole Depth: 35' ∇ = First Water **Consultants** Casing Type: NA Well Diameter: NA Slot Size: NA Well Depth: NA Static Groundwater Gravel Pack: NA First Water Depth: 17' Elevation Northing Easting = Selected for lab analysis Well Sample Identification O Reading (ppm) Depth (feet) Sample Completion Moisture Content Soil Type Static Recovery Interval Casing Water LITHOLOGY / DESCRIPTION Level ď Asphalt - 3" Lean clay; olive green; medium stiff; medium Veat Cement plasticity and toughness; some tan coloring; some Air-Knife medium sand; medium to coarse gravel; moist; slight odor; (15,25,60) @ 5* moist 253 Strong odor 1:02 moist 47.4 @ 7 Stiff; sand fine to medium grain; (0,20,80) 1:05 moist 96.9 @ 8.5* Tan with olive green mottling; (0,25,75) 1:07 moist 33.8 @ 10 Red brown and tan with olive green mottling; 1:09 (0,30,70) 11 moist 12.7 @ 12* Low plasticity; high toughness; medium stiff; odor; 1:11 (0,40,60)Clayey sand; red brown and tan; black specs; moist 20.6 @ 13.5 medium soft; slightly cemented but crumbles 1:14 easily; poorly graded; no plasticity; high toughness; sand fine to medium; moist; odor; moist 21 @ 15* (0,55,45)1:16 Red brown with black specs; (0,70,35) 16 ∇ wet 4.1 @ 17* Olive green and tan; some gray staining; loose; 1:19 sand medium to coarse; wet; (0,65,35) CL Lean clay with sand; red brown with black 15 wet specs; sand fine grain; medium stiff; medium plasticity and toughness; wet; odor; (0,40,60) 20 wet 3.4 Moist; slight odor; (0,30,70) moist 1.8 With fine to medium gravel; coarse sand; low

Well Completion Static Water Level		Location: 4276 MacArthur Blvd Testing Oakland, CA Hole Diameter: 4" Hole Depth: 35' Well Diameter: NA Well Depth: NA First Water Depth: 17' Northing Easting Sample	Boring No: SB-6 Date Drilled: 10/31/07 Page 2 of 2
Neat Cement E	moist 1.8 @ 24.5 1:30 moist 1.4 moist 0.8 moist 0.6 @ 30.5 1:43 moist 0.9	23	brown speca; medium plasticity; ecs; medium soft; no plasticity; fine brown sand; high toughness; d tan; stiff; some black staining; ,60) d tan; fine to medium sand; trace ry stiff; some black specs but no
		36	D = 35 feet bgs

:

		D	N	C101155			C11 -		Ph:///	<u>-</u> :	ln : " CD 7	
		Project Logged		C101156 S. Mening		lorgan			ocoPhillips 4276 MacArthur B	lvd	Boring No: SB-7 Date Drilled: 07/09/09	
			Gregg D		gci/ C. M	organ			nd, California	. 74.	Page 1 of 2	
Del	ta			Macrocor	e			Diame	· ·		130 - 0	
	LU			d: Contin				Depth:	-	▽ =	First Water	
Consult	ants	Casing		N/A			First	Water	r Depth: 23.5			
		Slot Siz		N/A					r Depth: 6.21	=	Static Groundwater	
		Gravel	Pack: Elevatio	N/A	T	Northi		Depth:	N/A Easting			
			Lictudio	···		140161711	''y		Lasting			
Boring Completion			19	5	Ξ.	Sam	nle					
·	Static	Moisture Content	PID Reading (ppm)	ple	Depth (feet)	1	· I	Soil Type	_			
Backfill	Water Level	lois	Re (pp	Sam	듚	×	lyze	Ē	LITHO	LOGY /	DESCRIPTION	
Вас	2070	Συ	PIC	Sample Identification	Deg .	Recovery	Analyzed	Ň				
					ł	+	1 	CL	Lean Clay wit	th Sand	; light olive green to	
						1	\Box				um plastic, hydro-	
					1 —				carbon odor pr	resent.		
		ا به ا		ife	2—	ļ	$\perp \perp$					
_		Moist		Å	-	+	\vdash					
		ے ا		Air-Knife	3—	 	╫┤					
					, -	1	1-1					
			3.9		4							
			ppm		5—	ļ	Ш	۵.				
-					-	 	+	CL			; olive green-brown, ne to medium grained	
	▼				6—	+	╁─┤		sand, strong h	vdrocarl	oon odor, visible	
							+				medium plastic.	
ا ابر					7					,		
Neat Cement					8—		\bowtie					
			405			├ ──						
at (ppm		9-		╂	CL	l ean Clay wi	th Sand	; same as above	
Ne –							+-1	<u> </u>	Eculi City Wi	ui Suiiu	y same as above	
					10							
					11							
					-	 						
			6.5		12	-	+	CL	Lean Clay wi	th Sand	; same as above, with	
			ppm		-	1	+-	ŲL.			ible contamination,	
		;;			13—						hydrocarbon odor.	
		Moist			14—							
					-	ļ	\dashv					
					15—	+	╁┈┤		<u> </u>			
					-	1	X					
			64.1		16—		T					
			ppm		17—							
					-	_	igspace	CL	Lean Clay wi	th Sand	; brown to red brown,	
					18-	 	\vdash				sand, low plasticity	
					-	 	+		slight hydroca		t, increasing moisture,	
					19		+		Singile Hydroca	i Don Out	77, 30111	
					20—							
		,	6.7		20-							
			ppm		21—	-	\sqcup	<u>.</u>	1 01 1	th C	; same as above with	
					1	1	1	CL	ı 💎 Lean Clav wi	to Sand	r same as above with	
					22—	+	+-1				nt; very stiff to hard.	

		T									T		
		Project		C101156					ocoPhillips		Boring No: SB-7		
		Logged	ву: Gregg D		ger/ C. M	orga	Loca	tion:	4276 MacArthur B	ıva.	Date Drilled: 07/09/09		
Del	+ >			Macrocor			Hala	Diama	311		Page 2 of 2		
DCI	la	_		d: Contin				Diame		┌ .	- Finel Webs.		
Consul	tante	Casing	-	N/A	uous			Depth:	Depth: 23.5		= First Water		
Consu	tants	Slot Siz		N/A					r Depth: 6.5'	▼ :	= Static Groundwater		
		Gravel		N/A				Depth:	· ·		- Static Grandwater		
			Elevatio	n		Norti			Easting	!			
Boring			D	۔		Γ							
Completion	Static	Moisture Content	PID Reading (ppm)	Sample Identification	Depth (feet)		nple	Soil Type					
<u>=</u>	Water	oist	Rei	amı	£	l e	/zec	Ī	LITH	OLOGY	//DESCRIPTION		
Backfill	Level	Σ٥	(원)	den	Geb	Recovery	Analyzed	So					
	-			-		-~	-						
- الع	\Box \Box	St			23—		\boxtimes	CL			; same as above; very		
Neat Cement		Moist	0.5		24	ļ		sc	strong hydroca				
- G	_	-	0.5		-	-	\vdash				medium to coarse		
at (-	ر با	ppm		25—	┝	-				/, medium dense to some olive green		
- Ně	-	Wet				\vdash	 		smearing.	o wet, s	one onve græn		
	-				26	\vdash		SM		own, w	et, medium to coarse		
_					27—			-	grained, strong				
		St			2/			CL			; brown, low to medium		
	_	Moist			28				plastic, stiff, h	ydroærl	bon odor.		
-		_			_	ļ					·		
					29	┝	-	SP	Boorly Cundo	d C- 4	le light brown		
-	-				-	┢	-	32	Poorly Grade	u Sanu	i; light brown.		
8998					30—	-			Total Depth o	of Borir	na = 30' bas.		
_	_				31—	\vdash					.g _ 00 250.		
-					31—				Soil Sample St	3-7@ 7.	.5-8' collected at 15:05		
	_				32—	ļ			7/9/2009.				
_	-				_	1	<u>. </u>			3-7@ 1	5.5-16' collected at 15:10		
_	_				33	-			7/9/2009.	2 7 6 2	23-23.5' collected at 15:15		
_	-				-	\vdash	 		7/9/2009.	5-7 W Z	23-23.5 Collected at 15:15		
	-				34—	┢╾			77372003.				
_					35—		-				· · · · · · · · · · · · · · · · · · ·		
	_				-	<u> </u>							
					36	-							
					37—								
_	_				-	↓							
**	-				38	╁	ļ						
					39—								
-	+				-	┼—	-						
					40—								
	_				41	F							
_	-				-	\vdash	 	1					
				}	42 —			1					
	-				43	\vdash	_						
_					44			j					
						Π	Γ]		700			

ŧ

		Project		C101156			Client: ConocoPhillips Location: 4276 MacArthur Blvd. Boring No: SB-8 Date Drilled: 07/10/09						
		Logged		S. Mening	ger/ C. M	organ	Loca			Ivd.	Date Drilled: 07/10/09		
	+-	•	Gregg I	_					ınd, California		Page 1 of 1		
Del	lα			Macrocor				Diame		l _			
			-	od: Contin	uous			Depth		⊻ =	First Water		
Consult	ants	Casing		N/A					Depth: N/A	_			
		Slot Siz		N/A					er Depth: N/A	_ ▼ =	Static Groundwater		
	Gravel Pack: N/A Elevation North						Depth	: N/A Easting	ł				
			Lievatii	JII		NOTETT	iig		Lasting				
Boring Completion			0	5	Ω.	Sam	nle						
·	Static	Moisture Content	ğ -	agi e	fe e			Soil Type					
€	Water	ᄩ	Readii (ppm)	I I I	Ē	é	zec.	E	LITHO	LOGY /	DESCRIPTION		
Backfill	Level	žΰ	PID Reading (ppm)	Sample Identification	Depth (feet)	Recovery	Analyzed	So					
	<u> </u>					αž	_ <						
	1				l –	 	+	CL			; thumb to fist sized		
	1			덜	1	 	+	1			e pumice fill and black hydrocarbon odor.		
	1			무무	-	 	+	1	mies, myn pet	. oreum I	nyurocarbon odor.		
	1	st		Knife & F Augered	2	 	1						
	1	Moist		ge Fe	l	 	+-						
۳ ایا پ	1	~		Air-Knife & Hand Augered	3	1		1					
Jer	1	l		 	_ ا	l		1					
Sen]			•	4]					
Neat Cement					5			L					
lea _								GP			fine to medium grained		
Z		장			l 6—						ble compressed		
_	1	Very Moist				ļ	\bot		asphalt; visible	e black p	product; very moist.		
	-	- -			7	ļ	\downarrow	l					
		\ e	1453		- 1								
	-	_	ppm		8	-	+	l					
					1 , -		+		Total Depth	of Borin	g = 8.5' bgs.		
]				9			1			minated at 8.5' bgs		
					10-				due to drilling c	onditions.	. At 7'bgs drillers		
_					10						nce was felt on the		
					11-	<u> </u>					gh and drop was		
_		[┞	丄	ļ			ancing from 8.0-8.5'		
	-				12	ļ	ـ	l		oint a vibi	rating feel in the rod		
_	1				_	_	+-		was felt.				
	-				13	 	+	1	Coil comple C		7 El collocte d' - 13:34		
_	-				_	 	+	ł	7/10/2009.	o-o@ /-	7.5' collected at 13:21		
	1				14	 	+-	ł	// 10/ 2009.				
-	1				l	 	+	1					
	1		i		15 —		+	1					
_	1				1.0	†		1					
]				16		\top	1	-				
					17								
					'								
			1		18—			1					
_						ļ	\perp	1					
					19		╄-	1					
_					-		┿	1					
	-				20			-					
_					-	₩	+	1					
	1				21 —	 	+-	1					
-	1					 		1					
					22	1	+	1					
			1	<u> </u>	J.	1		i .	I				

		Project Logged		C101156 S. Mening	er/ C. M	organ			ocoPhillips 4276 MacArthur Bl	vd.	Boring No: SB-9 Date Drilled: 07/08/09
D-01	+ ~	Driller:	Gregg I	Orilling		or guil		Oakla	nd, California		Page 1 of 2
Del [*]			ng Metho Type: :e:	Macrocore od: Continu N/A N/A N/A			Hole First Stat		: 26.5' Depth: 26' r Depth: 24		= First Water = Static Groundwater
			Elevatio			Northi		Береп	Easting		
Boring Completion Egg Ba	Static Water Level	Moisture Content	PID Reading (ppm)	Sample Identification	Depth (feet)	Recovery S	Analyzed	Soil Type			/ DESCRIPTION
_					-		+	CL	Lean clay wit bronw, mediun		; light olive green to dtv. thick.
				Hand	1					, p	
				(nife & H Augered	2						
				Air-Knife & Hand Augered	з—		+				·
				Air-	4						
					5 						
					6						
ـــــــــــــــــــــــــــــــــــــ					7—			CL		contam	; same as above with ination, and mild on odors.
men		:	3.6		8—						
Neat Cement			ppm		9					•	
Nea					10—						
_					-	 					
					11						
			2.5		12			CL			; brown to orange
			ppm		13	 	+		brown, dry, m	edium p	plasticity, firm.
					14—		-				
					15	1	$ \downarrow $				
					16—		上				
					17—		_	CL	Same as abou	ve.	4
					-						
					18— -		1				
					19—						
					20—	+	+-	CL	Same as abo	ve.	
					21—		1				
					22—	1					
					22]			

D - !!	Project No: Logged By: S. N Driller: Gregg I				on: 42	ocoPhillips 176 MacArthur Blvd. Dakland, CA	Boring No: SB-9 Date Drilled: 07/08/09 Page 2 of 2	
Delta	Drilling Method: Sampling Metho Casing Type: N/ Slot Size: N/A Gravel Pack: N/	d: Contini 'A			Depth: Vater I Water	26' Depth: 26' Depth: 24'	☑ = First Water ☑ = Static Groundwater	
	Elevatio	on	Nor	thing		Easting		
Boring Completion Static Water Level	Moisture Content PID Reading (ppm)	Sample Identification	Depth (feet)	Analyzed ald	Soil Type	LITHO	DLOGY / DESCRIPTION	
Neat Cement			232425		CL	Same as abov	ve , with increased sands.	
			26				of Boring = 26' bgs.	
			27			Soil Sample SE 07/08/09.	3-9@26' collected @ 18:40	
			41					
			43					
			44	++				

		Project	No:	C101156			Clier	nt: Cor	nocoPhillips		Boring No: SB-10			
		Logged	Ву:	S. Mening	jer/ C. Mo	rgan			4276 MacArthur Bl	vd.	Date Drilled: 07/08/09			
			Gregg [_				Oakla	and, California		Page 1 of 2			
Del	la	_		Macrocore			Hole Diameter: 3" Hole Depth: 23'							
Consult		Samplin Casing		id: Continu N/A	ous				n: 23' Depth: 16	✓ = First Water				
Consuit	ants	Slot Siz		N/A					er Depth: 6.21	·				
		Gravel I		N/A				Depth	· '		State Stoutiumate.			
			Elevatio	on		Northi	ng		Easting					
Boring Completion			<u></u> б	uo	it)	Sam	ple	41			······································			
•	Static Water	Moisture Content	PID Reading (ppm)	Sample Identification	Depth (feet)	≥	10	Soil Type	1.774	OL OCY	/ DECORPTION			
Backfill	Level	Yois	9 G	San	pth	Recovery	Analyzed	- lio		OLUGI	/ DESCRIPTION			
89			Ы	Jde	De	Rec	Ans	01						
_	Moist	ure Co	ntent		_			CL			oilve green to			
	1			рu	1		+				c, medium stiff, r; possible fill material.			
-	1			Air-Knife & Hand Augered			+		mila nyarocart	on odol	, possible fill material.			
		냃		Cnife & H Augered	2									
		Moist		nife	3—									
_		-		Ϋ́	-									
				Ai	4		+							
					5									
_]]	•		GP			ay, fine to medium			
		E			6				gravel with fine	e to me	dium grained sand,			
_		for			_		+		no odor.	тысегы	I from former UST pit,			
t		.⊆			7		+		no odon					
Neat Cement]	Wet- Perched water in former UST pit.			8									
– Jen		ed wate UST pit.	1.8		Ŭ -		-							
at (1	US	ppm		9 —									
Ne		קַ			10			SP	Poorly Grade	d Sand	with Gravel; gray to			
_		4									lium grained sand,			
		/et			11		-		loose, wet, ver	y strong	g hydrocarbon odor.			
_		>			_									
			899		12-		\forall	CL	Lean Clay wit	th Sand	; Olive green to brown,			
			ppm		13				medium stiff, I	ow to m	nedium plastic, moist,			
_		ا پہ			-				slight hydrocar	rbon odd	or, visible contamination,			
-		Moist			14		+							
_		2					+							
		-			15									
	∇		- -		16—									
_			7.6		_									
-			ppm		17		+	sc	Clavey Sand:	Dark o	ray, loose, wet, fine to			
					10 -						, very strong hydrocarbor			
_			545		18 —		\times		odor, visible co	ontamin	ation, trace fine gravel.			
		ا پر	ppm	· .	19—		ļ	ŀ						
		Moist			-		+							
		2.	6.6		20		+	CL	Lean Clay wit	th Sand	; brown with olive			
	[ppm		21 —]	green mottling	, stiff, l	ow to medium plastic,			
]	fine to coarse		sand, slight odor, trace			
1000					22 —		1		fine gravel.					

		Project		C101156		Client: ConocoPhillips Boring No: SB-10							
				leninger/	C. Morga	ın			276 MacArthur Blvd.	Date Drilled:			
	1+-		Gregg D					•	California	Page 2 of 2			
De	Ild			Macrocor				Diame					
				d: Contin	uous			Depth:		∇ = First Water			
Consu	itants	Slot Siz	Type: N/	А					Depth: 16'	Chabin Consum describes			
		1	e: N/A Pack: N/A	٨				c wate Depth:	r Depth:28'	\underline{lack} = Static Groundwater			
		Graver	Elevatio			Norti		рерит.	Easting				
							9		Lusting				
Boring			9	u.	5	C	1-						
Completion	Static		PID Reading (ppm)	Sample Identification	Depth (feet)	1	nple	Soil Type					
Backfill	Water	onte	Rei	am tific	E .	Recovery	Analyzed	<u>-</u>	LITHO	LOGY / DESCRIPTION			
3ach	Level	ğΰ	Ĕ,	den 🤃	Je Di	6	yla	So					
		ļ	4.	Ä	,	1 %	ک						
		ma!-	, ,		23-	 	rightarrow	٥.	C	we with incompany and			
int .		moist			-	+	+	CL	Same as abov	ve, with increased sands.			
me —	_ ▼		ppm		24—	+	+						
Neat Cement	-				-	+	+						
at	-				25	1	+						
Ne			l		126								
					26—								
					1 27 —				Total Depth o	of Boring =			
	_				2 /								
_	_				28-		$ldsymbol{oxed}$			3-10@ 12-12.5' collected at 7:55			
					-	₩	-		07/10/09.	2 400 40 40 51 11 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1			
i. —	-	:			29	+-	-			3-10@ 18-18.5' collected at 8:00			
-	-				-	+	+		07/10/09.	3-10@ 22.5-23' collected at 8:05			
	_				30—	+	+		07/10/09.	3-10@ 22.3-23 conected at 8.03			
•	_					+	1		07/10/03.				
					31 —	T	1						
					32-								
					32								
_	4				33	<u> </u>	<u> </u>						
	4				-	1	₩.						
_	_				34—	-	+						
-	-				-		+						
[-	-				35	+	+						
	-				-	T	t						
					36—				-	· · · · · · · · · · · · · · · · · · ·			
					37—								
					3/								
_	_			1	38	1	1						
	4				-	4	↓						
	-]	39—	+	+						
-	-	1			-	+	+	1					
_	-	1		1	40	╅┈	+						
-	1					+	+						
	1]	41 —	+	+	1					
-	1				43 -	1	1	1					
					42—			1					
					43—]					
]	_												
_	_				44-			1					
					1								

	Project No:	C101156		Clie	nt: Con	ocoPhillips	Boring No: SB-11		
	Logged By:		ger/ C. Morgan			4276 MacArthur Bl			
	Driller: Gregg I		, ,		Oakland, California Page 1 of 2				
Delta	Drilling Method	: Macrocore	е	Hole	e Diame	· .			
	Sampling Metho			Hole	Hole Depth: 44' ∑ = First Water				
Consultants	Casing Type:	N/A		Firs	t Water	Depth: 42'			
	Slot Size:	N/A		Stat	tic Wate	er Depth:N/A	Static Groundwater		
	Gravel Pack:	N/A			l Depth				
	Elevati	on	No	rthing		Easting			
Boring	 	T -					·		
Completion Static	Moisture Content PID Reading (ppm)	Sample Identification	s get	ample	l ĕ				
	Moisture Content ID Readin (ppm)	mpl fica	Depth (feet)	و ج	Soil Type	LITH	OLOGY / DESCRIPTION		
Water See Bee Water	S O S O	Sal	ept	recovery Analyzed	Soil				
ă	[P	ا م	A A	"				
					CL		n sand; light olive green to		
		و ا	1	_			stiff to stiff, low to medium		
		lan l				plasticity.			
		ed R	2——	_ _	4				
		(nife & F Augered	+	 -	-				
		Aug Aug	3		1				
		Air-Knife & Hand Augered	I . —	-	1				
		⋖	4		1				
			5]				
					1				
			6						
			+-		CL		h sand; olive green, gray,		
			7 —		1	trace fine to	medium coarse grained sand; edium grained gravel; low		
			_ +-	-	1	plasticity: mois	t; strong hydrocarbon odor.		
Neat Cement	405		8	- (`	1	plasticity, illois	c, strong myarocarbon odor.		
	ppm		, +		1				
eat			9		CL		h sand; entirely green in color,		
ĭ ž 📗			10]	very stiff to ha	rd.		
	6.8		~		1				
	ppm		11		4				
			+	$-\!\!\!\!+\!\!\!\!\!-$	-				
	16.7		12		CL	Lean clay with	h sand; brown and olive		
	ppm	1	-	-	₹		rery stiff to hard, very strong		
		1	13-	-	1	hydrocarbon o	dor, low to medium plastic.		
			,, +		1	,,			
			14——		1				
		-	15]				
	100	}	16——	<u> </u> ×	١.,		Land dament		
	108		+-		CL		h sand; decreasing sand		
	ppm		17-	+	-		m to high plasticity, increasing t hydrocarbon odor, very stiff		
			_ +		1		fine gravel, visible contamination.		
		1	18	-	1		very hard direct pushing.		
			10.		1	25, (3,50)	, 2. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2.		
			19]				
			20						
	12.1				CL		h sand; brown with green mottlin		
	ppm		21-		1		, trace fine gravel, slight odor,		
					4	increasing mos	iture.		
		1	22		-				
					<u> </u>	<u> </u>			

		Project	No.	C101156			Clion	ti Con	oco Dhilling	Parina Nat CR-11
				C1U1156 leninger/		ın			ocoPhillips 4276 MacArthur B	Boring No: SB-11 Vd. Date Drilled: 07/10/09
D . I			Gregg D		3			land, C		Page 2 of 2
Del	та			Macrocoi			Hole	Diame	ter: 3"	
				d: Contin	uous			Depth:		
Consul	tants		Type: N/	Ά					Depth: 42'	
		Slot Siz	e: N/A Pack: N/A	۸				ic Wate Depth:	r Depth: N/A	▼ = Static Groundwater
		Graves	Elevatio		T	North		Берит.	Easting	
Boring Completion			ق	5	ਦੁ	San	anla			
· ·	Static Water	Moisture Content	PID Reading (ppm)	ple	Depth (feet)	1	•	Soil Type		
Backfill	Level	10is	8 d	Sarr	뒱) ver	/ze	[LITIM	DLOGY / DESCRIPTION
Ва		2 0	뒽	Sample Identification	2	Recovery	Analyzed	S		
	†				23—	† <u> </u>	Ė			
		Wet	5.8		23 —			CL		d sand; brown, wet, no odor.
	_		ppm		24	ļ			Wetness in sm	all portion-Not first water.
-	-				_		-	CL	Same as abo	/e; less visible contamination,
	-				25 —	1	-	CL	increasing san	
	1				-		 	1	micreasing san	a content.
	1				26—					
l	4				27	ļ				
_	4				-	-	┝	ł		
	-		6.7		28		\vdash	CL	l ean clay wit	h sand; brownand olive green,
	1		ppm			t	\vdash			sture, less visible contamination.
			` `		29—					
	_				30-					
-	-				-	-	├	-		
	-				31	 	-	1		
_	1				32	†	<u> </u>	1		
= ' ' '			6.8		32			CL		ve; increasing sand content,
E	-		ppm		33	-	_		visible contam	ination, red brown.
Neat Cement	-				-	╁	-	ł	•••	
sat	1				34	 	\vdash	1		
ž	1				-	†		1		
		1	1		35—]		
	-		F -3		36	 	\vdash	١	<u> </u>	
_	-		5.7 ppm	'	-	┼	\vdash	CL	conent.	ve; increasing moisture
	-		וווקק		37	+	\vdash	1	COHOLIC.	
					38			1		
_	-			1	-					
					39		 	4		
-	-				-	-	┼	┨		
			7.5		40	+	\vdash	1		
			ppm		11 -	1	T	CL	Same as abo	ve; wet.
		1			41		\boxtimes]		
	-	∇			42	ļ	L	4		
_	-				-	+	-	-		
	-				43	+	+	1		
	<u></u>			<u> </u>],, -	†	t	1		
					44	1	1			of Boring = 44' bgs.
	<u> </u>						L		SB-11 samples	collected at 10:50, 10:55 & 11:00

.

			Project	No:	C101156			Clier	nt: Con	ocoPhillips		Boring No: SB-12
			Logged	Ву:	A.Buehler					4276 MacArthur B	lvd.	Date Drilled: 06/14/10
		L_		Gregg D						Oakland, CA		Page 1 of 3
ーレ	el	ta		Method:					Diame			
1				ng Metho	d:				Depth			= First Water
1 6	nsulta	ants	Casing Slot Siz				First Water Depth: Static Water Depth:				▼ = Static Groundwater	
			Gravel						Depth			- Static Groundwater
				Elevatio	n		Northing Easti				1	
Bo	ring			i					1		<u> </u>	
	oletion	Charl's	يبوا	PID Reading (ppm)	Sample Identification	et)	San	nple	e e			
		Static Water	Moisture Content	(ead	mpl	Depth (feet)	e Z	Analyzed	Soil Type	LITHO	DLOGY	/ DESCRIPTION
}	Backfill	Level	Mo.	0 g	Sar	eptł	Recovery	alyz	Soil			,
	Δ			<u>a.</u>	PI	۵	Re	An				
						_						
						1 —						
)e.c	-		_				
					əbn	2—	+					
					J A	3						
	_				Hand Augered			_				
					工	4—	-	 				
						5						
						6—]_			
				5.2	SB-12				CL	Sandy lean clay with	h gravel	; brown with
					@ 12 9:44	7 —	1000	├	-	visible green contar	nination	; moist.
ent					"'	-	100					
em						8—						
Neat Cement						9_						
lea							-	<u> </u>	ł			
				30.1	SB-12	10 —			CL	Sandy lean clay clay	v: liaht l	brown: wet.
					@ 10	 11 <i>-</i>]		, ,g	
			i		9:58]			
						12—	-	<u> </u>				
						-						
						13 —		-	1			
						14—]			
	· —						_	ļ	1			
				NA	SB-12	15	-		CL	Same as above. Sa	turated	
				INA	@ 15	.				Same as above. Same	turated.	
					@ 15 10:25	16			1			
						17 —]			
						¯′ .		<u> </u>	1			
						18		\vdash	1			
									1			
						19—			1			
				647	GD 15	20 —						
				64.7	SB-12 @ 20			12.5	CL	Sandy lean clay; br	own; m	oist.
					10:36	21 —	-		1			
					-5.55	22 .			†			
						22 —						

		Project No: Logged By:	C101156 A. Buehle		nt: Con ation:	ocoPhillips 4276 MacArthur B	Boring No: SB-12 Date Drilled:			
	Dalta	Driller: Gregg [Oakland, CA	Page 2 of 3			
	Delta	Drilling Method: Sampling Metho Casing Type: Slot Size:		Hol Firs	e Diame e Depth: it Water tic Wate					
ľ		Gravel Pack: Elevation	on .	We Northing	Il Depth:	Easting				
ŀ	Boring	 	1		1	Lasting				
	Completion Static Water Level	Moisture Content PID Reading (ppm)	Sample Identification	Depth (feet) Recovery S Analyzed		LITHO	DLOGY / DESCRIPTION			
	Neat Cement Back	10.2 NA 3.5	SB-12 @ 26 10:45 SB-12 @ 30 10:47 SB-12 @ 35 10:58	23	CL CL	Same as above; dar Same as above; dar Same as above.	y stiff with large gravel			
			11:42	43 —						

	Project N	No:	C101156	Client	: Con	ocoPhillips	Boring No: SB-12	
	Logged E	Ву:	A. Buehl			4276 MacArthur Blvd		
	Driller: (Oakland, CA	Page 3 of 3	
	Drilling N			Hole [
	Sampling		d:	Hole [◯ = First Water	
	Casing T Slot Size					Depth: r Depth:	▼ = Static Groundwater	
	Gravel P			Well [- Static Groundwater	
		Elevation	า	Northing	Easting			
								
Boring Completion Static Water Do Level	Moisture Content	PID Reading (ppm)	Sample Identification	Depth (feet) Recovery was analyzed a	Soil Type	LITHOL	LOGY / DESCRIPTION	
nt 		NA	SB-12	45	CL	Same as above with 20	% gravel; 10%	
ne —			@ 45 11:45	46		sand; damp. Sandy clay; light browr	200/ cand no	
Neat Cement			11.40	 		odor.	1, 20 /0 Sanu, NO	
sat				47				
🖁 📗 📗				48				
				49		Camp as above with 11	EO/ graval and 1EO/	
	ľ			 	CL	Same as above, with 1! sand.	5% graver and 15%	
		3.3	SB-12	50— 		Boring terminated at	50 feet bas.	
			@ 50	51				
			11:54	31				
	:			52				
				 				
				53				
				54				
				J4				
				55				
				- - - 				
				56				
				F7 -				
				57				
				58			\	
				59				
				60				
				61				
				++				
				62				
				62				
				63				
				64				
				65				
				66				
manth .				·		<u> </u>		

_	ls	.	0101156		Clien				Ja
	Project Logged		C101156 A.Buehlei				nocoPhillips 4276 MacArthur B	lvd	Boring No: SB-13
		ву: Gregg I		ı	LOCE	idon:	Oakland, CA	iva.	Date Drilled: 06/18/10 Page 1 of 1
Delta	Drilling				Hole	Diame			page I of I
		ng Metho				Depth		∇	= First Water
Consultants	Casing			First Water De					- That Water
Consumants	Slot Siz				Static Water Depth:			▼ = Static Groundwater	
	Gravel I			Well Depth:				-	state a varianate
		Elevatio	n	[Northing		Easting		
Boring Completion Static Water Y Level	Moisture Content	PID Reading (ppm)	Sample Identification	Depth (feet)	Recovery by Manalyzed all	Soil Type	LITHO	DLOGY	/ DESCRIPTION
				_					
			þe	1 —					
			Hand Augered	2—					
			gn/						
t			d A	з —					
l m m			lan	-	 				
Neat Cement				4	+				
at M] .			-	 				
N N N]		SB-13	5			Black, sandy, granu	ılar tar	-like material verv
			@ 6	_			strong odor	iiai, tai	ince material, very
			8:45	6—				nated	at 6 feet bgs due to
_			01.10				refusal.	iiacca ·	ar o reer bys due to
				7					
				, -				· · · · · · · · · · · · · · · · · · ·	
				8 —					
				9					
				10 —					
				-					
				11	.				
				-					
				12	 				
				-					
I —				13	 				
				-	 				
				14 —	 				
						1			110-11-11-11-11-11-11-11-11-11-11-11-11-
				15 —		1			
				16					
I 🗐									
				17		ļ			
					 			· · · · · · · · · · · · · · · · · · ·	
				18	 				`
				-	 	1			
				19 —	╁┈┼┈				
I ⊢				-	 	1			
				20 —	 	1			
				-	 	1			
				21	 				
					 	1			
				22 —	 -	1			
	<u></u>					1			

	Project No:	C101156	Cl		ocoPhillips	Boring No: SB-14			
	Logged By:	C. Morgai	n Lo	Location: 4276 MacArthur Blvd. Date Drilled: 06/17/10					
Delta	Driller: Greg Drilling Metho		u.		Oakland, CA er: 3"	Page 1 of 3			
	Sampling Metho			Hole Diameter: 3" Hole Depth: $\nabla = \text{First Water}$					
Consultants	Casing Type:			First Water Depth:					
	Slot Size:			atic Water	•	▼ = Static Groundwater			
	Gravel Pack:			ell Depth:					
	Eleva	ition	Northin	g	Easting				
Boring		Ē	(t) Sampl						
Completion Static	ent ent adin	atio Be	ا قرا	&					
Water Vo Level	Moisture Content PID Reading	jam jami	Depth (feet) Recovery S	Soil Type	LITHO	LOGY / DESCRIPTION			
Вас	[™] ∩ GI	Sample Identification	Deg	N N					
		<u> </u>		CL	Clay; green, vi	sible contamination; with			
			1			k and white gravel.			
		red	-	┙┞					
		Ige	2	-					
		Hand Augered] , ++	⊣		:			
		 pug	3 1] [
		≟	4	_ [
			+						
			5						
	}		6						
] [
			7	-					
ent –	į.		l -	┥. ┡					
Neat Cement	333	5 SB-14	8		Lean Clay with	sand; gray with visible green			
J J		@ 8	9 1			strong odor; moist.			
eat		11:50							
	555	3 SB-14	10	-					
		@ 10	l - -	_					
		11:50		-					
			12						
				⊣ ∣					
			13	-					
			 						
			14-						
	107	.5 SB-14	15			e, with small coarse grained			
		@15 11:54	- 	CL		gravel at 16.5 to 18 feet bgs;			
		11:54	16	-	moist.				
			1, ++	-					
			17						
			18	[
			19	-					
			120 1	ㅋ					
	11.		20	CL		e, with increased fines at 21			
\square		@ 20	21 -	_ [feet bgs.				
1944 —		12:01			Same as abov	e, with continued increased			
			22	- _{GC}	fines; gravel a	iso present. with sand, thumb-sized white			
	<u> </u>		.1	اعدا	Clayey Graver	with Sand, thumb-Sized White			

Project No: C101156 Client: ConocoPhillips Boring No: SB-14 Logged By: C.Morgan 4276 MacArthur Blvd. Location: Date Drilled: 06/17/10 Driller: Gregg Drilling Oakland, CA Page 2 of 3 Delta Drilling Method: Hole Diameter: Sampling Method: Hole Depth: Casing Type: **Consultants** First Water Depth: Slot Size: ▼ = Static Groundwater Static Water Depth: Gravel Pack: Well Depth: Elevation Northing Easting Boring PID Reading (ppm) Sample Identification Depth (feet) Completion Sample Moisture Content Soil Type Static Analyzed Backfill Water LITHOLOGY / DESCRIPTION Level rock present; less odor then at previous 23 depths. Neat Cement 24 25 26 11.9 SB-14 CH Sandy fat clay with gravel; gray, tan, @ 26 27 12:07 28-29 30 NA SB-14 СН Same as above. @ 30 31 12:07 32 33 34 35 SB-14 10.5 CL Lean clay; light brown to tan; some small @ 35 grained gravel; firm; slight odor; moist. 36 12:16 37 38 39 40 18.5 SB-14 CL Same as above, with increased moisture @ 40 and softness. 41 12:22 42 43

		Project	No:	C101156	5	Clier	nt: Con	ocoPhillips		Boring No: SB-14
		Logged		C.Morga	n	Loca	tion:	4276 MacArthur Blv	d.	Date Drilled: 06/17/10
	L _	Driller:	Gregg [Prilling				Oakland, CA		Page 3 of 3
Del ⁻	га	Drilling	Method:			Hole	Diame	ter:		
	CG	Sampli	ng Metho	d:		Hole	Depth	:	<u> </u>	First Water
Consulta	ants	Casing	Type:			First	Water	Depth:	_	
		Slot Siz	ze:			Stat	ic Wate	r Depth:	W =	Static Groundwater
		Gravel	Pack:			Well	Depth:	:		
			Elevatio	n		Northing		Easting		
Baring	1	 	· · · · · · ·	1						
Boring Completion			Б	Sample Identification	ੂ ਦੂ	Sample				
	Static	Moisture Content	بق ق	ple	(fe		Soil Type			
I ■	Water	oist	Re	am	ŧ.	ver /ze(-	LITHO	LOGY /	DESCRIPTION
Backfill	Level	ΣΟ	PID Reading (ppm)	der	Depth (feet)	Recovery Analyzed	νχ			
ш	ļ	<u> </u>		Ä		A A		·		
	∇		l		45—			Possible seco	nd wate	er bearing zone.
t -	4		14.5	SB-14	`` ,	+	CL	Sandy lean cl	ay with	silt to 48 feet bgs,
lue	4			@45	46		1		n sand a	and gravel to bottom
Neat Cement		ļ		12:28				of boring.		
t	-				47 —					
les —	1				.					
-	1	i			48	- - - 				
	<u>.</u>						1			
	1				49 —	+	1			
							1			
			10.6	SB-14	50 —					
	İ	j		@ 50	•		 	Boring term	inated	at 50.5 feet bgs.
	1			12:28	51—		1	2011119 (01111	matoa	at Joil leat bgs.
	1					 	1			
	1				52—		1			
]				53 —					
]				55 —					
]				54—					
_					~~ .]			
					55					
-]				1012	
					56 				·	
_										
				ļ	57—		ł			
-							ļ			
					58 —					
		1								
					59 —	+	1			
-					'	 	1			
					60	 	1			
					٠. ا	11				
					61—		1			
					62]			
					62—					
					63 —					
					"]			
					64—]			
					0-7					
					65—	\bot	1			
						1 1	1			
					66—					
					-		<u></u>			

Delta	Drilling Me Sampling I Casing Tyr Slot Size: Gravel Pac	v: C. Morga regg Drilling ethod: Sonic Method: pe:	n	Location: 4	: Depth: or Depth:	Boring No: SB-15 Date Drilled: 06/17/10 Page 1 of 2
Boring Completion Stati Wate	istt. inte Rea Spm opm		Depth (feet)	Recovery Solaria Manalyzed and Soil Type	LITHO	DLOGY / DESCRIPTION
Neat Cement	1	14.8 SB-15 @ 5 2:01 2:01	1 — 2 — 3 — 4 — — 5	CH	approx 8 feet	with fine grained sand; at bgs, color had orange mottling stant lithology to 11.5 feet.
		6.3 SB-15 @ 15 2:04	14————————————————————————————————————	CH CL GC	Sandy lean cla moisture.	ve to 16 feet bgs. ay; fine grained; increased with clay from 17.5 to 18 feet; ed.
	1	12.3 SB-15 @ 21 2:10	21 —	GC	Same as abov to subangular	ve, with thumb-sized, angular gravel.

Delta Consultants Boring Completion Static	Project No: Logged By: Driller: Gregg I Drilling Method: Sampling Metho Casing Type: Slot Size: Gravel Pack: Elevation	on	Loca Hole Hole First Stati Well Northing Sample	Diame Depth: Water c Wate Depth:	Depth: r Depth:	Boring No: SB-15 Date Drilled: 06/17/10 Page 2 of 2
nent Backfill	Moisture Content PID Reading (ppm)	Sample Identification	Sample Sa	Soil Type	LITHO	DLOGY / DESCRIPTION
Neat Cement	5.2	SB-15 @ 26.5 2:18 SB-15 @ 30 2:18	25	GC	grained sands	e. ay with with gravel, fine and gravel, more saturated e to sluff during
	10.7	SB-15 @ 35 2:24	33 34 35 36 37 38 38 38 38 38 38 38 38 38 38 38 38 38	CL	Same as abov	e, moist.
	2.6	SB-15 @ 40 2:40	39 — 40 — 41 — 42 — 43 — 44 — 44 — 44 — 44 — 44 — 44	CL	Same as abov Boring temir refusal.	nated at 41 ft due to

Project No: C101156 Client: ConocoPhillips Boring No: SB-16 Logged By: A. Buehler 4276 Mac Arthur Blvd. Date Drilled: 6/17/10 Driller: Gregg Drilling Oakland, CA Page 1 of Delta Drilling Method: Sonic Hole Diameter: Sampling Method: Direct Push ∇ = First Water Hole Depth: 5.5' **Consultants** Casing Type: First Water Depth: Slot Size: Static Water Depth: ▼ = Static Groundwater Gravel Pack: Well Depth: Elevation Northing Easting Boring PID Reading (ppm) Sample Identification Completion Sample Depth (feet) Moisture Content Soil Type Static Analyzed Recovery Water LITHOLOGY / DESCRIPTION Level Air-Knife 53.4 **Neat Cement** moist SB-16 CL Lean clay; brown with green mottling, 5% @ sand, moist, strong odor. 8' 12:46 moist 90.1 SB-16 11 10' moist 10:49 CL Lean clay; light brown, <5% fine grained 12 sand, very dense/firm, moist, strong odor. 13.7 SB-16 CL Same as above, with light brown and orange mottling to 16 feet bgs. 16 15' 12:55 17 18 CL Same as above to 21 feet bgs. 19 20 SB-16 12.0 ĞC Clayey gravel with sand, bown, wet @ 20' 1:00 22:

Project No: C101156 Client: ConocoPhillips Boring No: SB-16 Logged By: A. Buehler Location: 4276 Mac Arthur Blvd. Date Drilled: 6/17/10 Driller: Gregg Drilling Oakland, CA Page 2 of 3 Delta Drilling Method: Sonic Hole Diameter: 3" Sampling Method: Direct Push Hole Depth: 5.5' **Consultants** Casing Type: First Water Depth: Slot Size: ▼ = Static Groundwater Static Water Depth: Gravel Pack: Well Depth: Elevation Northing Easting Boring PID Reading (ppm) Sample Identification Completion Depth (feet) Sample Moisture Content Soil Type Static Analyzed Water LITHOLOGY / DESCRIPTION Level CL Sandy Lean clay, brown, 15% sand, damp Neat Cement 24 CL Sandy lean clay; brown, wet. 9.3 SB-16 At 25' bgs, clay contains more gravels, and @ is more firm, damp. 26 25' 1:10 27 28 29 30 12.3 SB-16 @ 31 30' 1:10 32 33 34 CL Sandy lean clay with gravel; brown and some orange mottling; <5% gravel and 35 7.7 SB-16 <15% sand, damp. @ 36 34' 1:25 37 38 39 CL Same as above. 40 12.2 B-16 @ 41 40' 1:37

Project No: C101156 Client: ConocoPhillips Boring No: SB-16 Logged By: A. Buehler Location: 4276 Mac Arthur Blvd. Date Drilled: 6/17/10 Driller: Gregg Drilling Oakland, CA Page 3 of 3 Delta Drilling Method: Sonic Hole Diameter: Sampling Method: Direct Push Hole Depth: 5.5' **Consultants** Casing Type: First Water Depth: ▼ = Static Groundwater Slot Size: Static Water Depth: Gravel Pack: Well Depth: Elevation Northing Easting Boring Sample Identification PID Reading (ppm) Depth (feet) Completion Sample Moisture Content Static Analyzed Water LITHOLOGY / DESCRIPTION Level 45-11.5 Neat Cement 46 SB-16 CL Clay; brown with <5% coarse grained sand @ very dense; moist. 47-46' 1:46 48 Clay; tan with orange mottling <10% sand CL with some gravel; moist; very dense/firm. 49 8.3 SB-16 閾 50 50' Boring Terminated @ 50' bgs. 1:48 51. 52 54 55 56 57 58 59 60 61 63 64 66

Boring Completion Static Water Level	Project No: Logged By: Driller: Gregg Drilling Method Sampling Methot Casing Type: Slot Size: Gravel Pack: Elevati (bdd) (bdd)	: Sonic od: Direct F	Push Ho Fi St W Northin	ample				
Neat Cement	259.0	SB-17 @ 5 10:25 SB-17 @ 10 10:30	1 2 3 4 4	CL CL CL CL	Sandy lean classized gravel, chydrocarbon comore coarse grandy lean classized gravel white and red more coarse grandy lean classized gravel coarse grandy lean classized gravel coarse grandy lean classized gravel coarse grandy lean classized gravel coarse grandy lean classized grandy lean classized grandy lean classized grandy lean classized grandy lean classized grandy lean classized grandy lean classized grandy lean classized grandy lean classized grandy lean classized grandy lean classized grandy lean classized grandy lean classized grandy lean classized grandy lean classized grandy lean classized grandy lean classized grandy lean classized grandy lean classical grandy le	ay; gray with visible green; trace ammount of wood rese grained sand, pea to ravel from 6-8 feet bgs. e, however sand becomes Clay has more tan and orange nints of green contamination. Eurn hydrocarbon odor. ay with gravel, pea to thumb green and gray, moist, strong odor. a sand; tan, orange and some mottling; more firm, and grained sand; moist. ay with gravel, green, and ots; rounded to subrounded, gravel, very moist.		

Delta Consultants	Casing Type: Slot Size: Gravel Pack: Elevation	Sonic od: Direct F	n Loca Oak Hole Push Hole First Stat Wel Northing	ation: (land, Care) (a Diamet (a Depth: (b Water) (c Water) (c Depth:		Boring No: SB-17 Date Drilled: 06/16/10 Page 2 of 3
Completion Static Water Ay Begin March Static Water Level	Moisture Content PID Reading (ppm)	Sample Identification	Depth (feet) Recovery & S Analyzed al	Soil Type	LITHO	DLOGY / DESCRIPTION
Neat Cement Ba	NA 12.5	SB-17 @ 25 10:17 SB-17 @ 30 10:20	23	CL CL	Same as above Same as above	
	10.5	SB-17 @ 40 10:44	37 38 39 40 41 42 43 44 44 44	CL	Same as above	е.

Client: ConocoPhillips Project No: C101156 Boring No: SB-17 Logged By: Location: 4276 Mac Arthur Blvd. Date Drilled: 06/16/10 C. Morgan Driller: Gregg Drilling Oakland, California Page 3 of 3 Delta Drilling Method: Sonic Hole Diameter: Sampling Method: Direct Push Hole Depth: **Consultants** Casing Type: First Water Depth: **▼**= Static Groundwater Slot Size: Static Water Depth: Gravel Pack: Well Depth: Elevation Northing Easting Boring PID Reading (ppm) Sample Identification Completion Depth (feet) Sample Moisture Content Soil Type Static Recovery Analyzed Water LITHOLOGY / DESCRIPTION Backfill Level 45 Neat Cement 36 SB-17 CL same as above. @ 47 48 11:02 49 50 9.2 SB-17 @ 50 Boring terminated at 50.5 feet bgs. 51 11:03 52 53 54 55 56 58 59 60 61 62 63 65 66

Delta Orifice (Forgo Diffling Orificing Methods: Sonic Sampling Hethod: Sonic Sampling Hethod: Sonic Sampling Hethod: Sonic Sampling Hethod: Sonic Sampling Hethod: Sonic Sampling Hethod: Sonic Sampling Hethod: Sonic Sampling Hethod: Sonic Sampling Hethod: Sonic Sampling Hethod: Sonic Sampling Hethod: Sonic Sampling Hethod: Sonic Soni				Project	No:	C101156		Clie	nt: Con	ocoPhillips		Boring No: SB-18		
Delta Consultants Consu				Logged	Ву:	C. Morgan	ı	Loca	ition:	4276 MacArthur Bl	lvd.	Date Drilled: 06/14/10		
Consultants Single Single Static Size: Static Water Depth: Static Water Depth: Static Water Depth: Static Grownheater S		D - 14-		Driller:	Gregg D	rilling				Oakland, California				
Consultants Single Single Static Size: Static Water Depth: Static Water Depth: Static Water Depth: Static Grownheater S]) (PI:	Γ	Drilling	Method:	Soni c		Hole	· · · · · · · · · · · · · · · · · · ·					
Static Pack			CG	Samplir	ng Metho	d:		Hole	Depth	:	▽ =	= First Water		
Boring Completion Static Well Depth: Easting Easting	Consultants			Casing	Type:			First	•					
Bonna Static water Little Static water Little				Slot Siz	e:			Stat	ic Wate	er Depth:				
Boring Completion Static Water Level Static W				Gravel	Pack:					:				
Static Water Stat					Elevatio	n	Northing			Easting				
Static Water Stat		ring			I	Γ								
12.5 SB-18					ا ق	E	ਦ੍ਹ	Sample	٠,					
12.5 SB-18	1			ent	adji (r	ple	(fee		, y pe					
12.5 SB-18 @ 10		KĘ		ont	Re	am Itifi	£	ver	⊨	LITHO	LOGY /	DESCRIPTION		
12.5 SB-18 @ 10		Bac	Level	Συ	[일	S der)ep	ec la	S					
12.5 SB-18 8 CL Fat clay, gray and green, some thumb sized white gravel/rock, moist. 15.1 SB-18 @ 10 3:13 11 12 12 13 14 15 SB-18 @ 15 3:19 16 CH Fat clay with sand; black, saturated, very strong odor contamination. 16. CH Fat clay, gray and green, some thumb sized white gravel/rock, moist. Fine grained silty sand; black, saturated, very strong odor contamination. 16. CH Fat clay, gray and green, some thumb sized white gravel/rock, moist. Fine grained silty sand; black, saturated, very strong odor contamination. Clay with silt and sand, tan and gray, visible contamination. Clay with silt and sand; tan to gray; increased moisture; fine grained sand more abundant in bottom of sample with tan and orange coloring. Boring terminated at 20 feet bgs.	L					Η		~ ∢				·		
12.5 SB-18 8 CL Fat clay, gray and green, some thumb sized white gravel/rock, moist. 15.1 SB-18 @ 10 3:13 11 12 12 13 14 15 SB-18 @ 15 3:19 16 CH Fat clay with sand; black, saturated, very strong odor contamination. 16. CH Fat clay, gray and green, some thumb sized white gravel/rock, moist. Fine grained silty sand; black, saturated, very strong odor contamination. 16. CH Fat clay, gray and green, some thumb sized white gravel/rock, moist. Fine grained silty sand; black, saturated, very strong odor contamination. Clay with silt and sand, tan and gray, visible contamination. Clay with silt and sand; tan to gray; increased moisture; fine grained sand more abundant in bottom of sample with tan and orange coloring. Boring terminated at 20 feet bgs.							_							
12.5 SB-18							1					<u> </u>		
12.5 SB-18						l ĕ	_							
12.5 SB-18						ge	2	+	ļ					
12.5 SB-18		_				Au A	-	+ +-	1					
12.5 SB-18						ğ	3 —	 						
12.5 SB-18						- 	-	+	1	<u></u>				
12.5 SB-18 @ 7.5 3:05 9 CL Fat clay, gray and green, some thumb sized white gravel/rock, moist. 25.1 SB-18 @ 10 3:13 11 12 12 13 12 14 14 14 15 15 SM very strong odor Fat clay with saint, tan and gray, visible contamination. 476.0 SB-18 @ 15 SM very strong odor Fat clay with saint, tan and gray, visible contamination. SB-18 11.1 @ 20 3:26 CL 3:26 CL Orange coloring. Boring terminated at 20 feet bgs.				İ		-	4—	+	1					
12.5 SB-18 @ 7.5 3:05 9 CL Fat clay, gray and green, some thumb sized white gravel/rock, moist. 25.1 SB-18 @ 10 3:13 11 12 12 13 12 14 14 14 15 15 SM very strong odor Fat clay with saint, tan and gray, visible contamination. 476.0 SB-18 @ 15 SM very strong odor Fat clay with saint, tan and gray, visible contamination. SB-18 11.1 @ 20 3:26 CL 3:26 CL Orange coloring. Boring terminated at 20 feet bgs.								+ + -	1					
The property of the property o							5—		1					
The property of the property o														
The property of the property o							6—	1.	1					
The property of the property o							_, -		1					
25.1 SB-18	ا با						/—	1 1						
25.1 SB-18	e e				12.5	SB-18								
25.1 SB-18	e l]CL					
25.1 SB-18	Ö					3:05	a			white gravel/re	ock, moi	st.		
25.1 SB-18	eat					<u> </u>	_							
476.0 SB-18	Ž				l		10							
3:13 12 13 14 15 SM very strong odor very strong odor sangle with sand, tan and gray, visible contamination. 17 18 Clay with silt and sand; tan to gray; increased moisture; fine grained sand more abundant in bottom of sample with tan and orange coloring. SB-18 11.1 20 3:26 20 CL Boring terminated at 20 feet bgs.					25.1		" -							
476.0 SB-18							l 11							
476.0 SB-18 0 15 3:19 13 14 15 SM very strong odor very strong odor very strong odor contamination. 16 CH Fat clay with sand, tan and gray, visible contamination. 17 18 Clay with silt and sand; tan to gray; increased moisture; fine grained sand more abundant in bottom of sample with tan and orange coloring. 20 3:26 CL orange coloring. Boring terminated at 20 feet bgs.						3:13	-							
Fine grained silty sand; black, saturated, very strong odor 16 SB-18 16 CH Fat clay with sand, tan and gray, visible contamination. SB-18 11.1 @ 20 3:26 CL SB-18 11.1							12				· · · · · · · · · · · · · · · · · · ·			
Fine grained silty sand; black, saturated, very strong odor 16 SB-18 16 CH Fat clay with sand, tan and gray, visible contamination. SB-18 11.1 @ 20 3:26 CL SB-18 11.1							-		ł					
Fine grained silty sand; black, saturated, very strong odor SB-18 SB-18 SB-18 11.1 20 3:26 Fine grained silty sand; black, saturated, very strong odor Fat clay with sand, tan and gray, visible contamination. Clay with silt and sand; tan to gray; increased moisture; fine grained sand more abundant in bottom of sample with tan and orange coloring. Boring terminated at 20 feet bgs.							13		1					
Fine grained silty sand; black, saturated, very strong odor SB-18 SB-18 SB-18 11.1 20 3:26 Fine grained silty sand; black, saturated, very strong odor Fat clay with sand, tan and gray, visible contamination. Clay with silt and sand; tan to gray; increased moisture; fine grained sand more abundant in bottom of sample with tan and orange coloring. Boring terminated at 20 feet bgs.						-	-	+	1					
476.0 SB-18				·			14—	+	1					
476.0 SB-18							-	+ + -	1	Fine grained c	ilty sand	: black, saturated		
© 15 3:19 16 CH Fat clay with sand, tan and gray, visible contamination. 17 18 Clay with silt and sand; tan to gray; increased moisture; fine grained sand more abundant in bottom of sample with tan and orange coloring. 3:26 16 CH Fat clay with sand, tan and gray, visible contamination. Clay with silt and sand; tan to gray; increased moisture; fine grained sand more abundant in bottom of sample with tan and gray, visible contamination. Clay with silt and sand; tan to gray; increased moisture; fine grained sand more abundant in bottom of sample with tan and gray, visible contamination.					476.0	SB-18	15 —	N. 1	SM			, sidery sucurated,		
SB-18 Output					'' 3.3	I	-					and gray visible		
SB-18 (a) 20 3:26 17							16	+	1 ॅॅ'			Tana gray, VISIDIE		
SB-18 11.1 SB-18 0 20 3:26 Clay with silt and sand; tan to gray; increased moisture; fine grained sand more abundant in bottom of sample with tan and orange coloring. Boring terminated at 20 feet bgs.								 	1	2311411111411011	•			
SB-18 Q 20 3:26 Clay with silt and sand; tan to gray; increased moisture; fine grained sand more abundant in bottom of sample with tan and orange coloring. Boring terminated at 20 feet bgs.							17 —		1			-		
SB-18 Q 20 3:26 Clay with silt and sand; tan to gray; increased moisture; fine grained sand more abundant in bottom of sample with tan and orange coloring. Boring terminated at 20 feet bgs.									1					
SB-18 @ 20 3:26 19							18—		1	Clay with silt a	and sand	l; tan to grav:		
SB-18 @ 20 3:26 CL orange coloring. Boring terminated at 20 feet bgs.							10		1					
11.1 @ 20 3:26 20 CL orange coloring. Boring terminated at 20 feet bgs.						SB-18	19—		1					
3:26 Boring terminated at 20 feet bgs.					11.1		20		CL					
	"					1	20—		† -			t 20 feet bas.		
							, .		1			<u></u>		
			,				21]					
							22_]					
						<u></u>								

Delta Consultants Boring Completion Static	Logged By: Driller: Gregg D Drilling Method: Sampling Method Casing Type: Slot Size: Gravel Pack: Elevatio	Soni c d:	Hol Hol Firs Sta Wel Northing	e Diamet e Depth: it Water tic Water II Depth:	20' Depth: Depth:	MacArthur Blvd. d, California 3" 20' □ First Water ■ Static Groundwater		
Water Your Level	1 201 62	Sample Identification	Depth (feet) Recovery BY Analyzed ald	Soil Type	LITHO	DLOGY / DESCRIPTION		
Neat Cement	33.7 26.9 55.3	SB-19 @ 7.5 2:30 SB-19 @ 10 2:30 SB-19 @ 15 2:30	15 — 16 — 17 — 18 — — —	CL	Same as above Sandy lean cla green contami moist. Fat clay with g increased moi	y with visible green , some gravel. e. ay; light brown to tan; some ination present; very firm; gravel; gray and some orange sture; slight odor. inated at 20 feet bgs.		

	Transack N	24 24 47				- Oli				
		o: C1011						ocoPhillips Boring: SV-1		
			inger/C	C. Morgan				akland, CA Page 1 of 1		
Dalta	Drilling M	Driller: Gregg Drilling Method: Hand Auger Sampling Method: Hand Drive						: 7/7/2009 Location Map		
Delta	Campling M							ter: 3.5"		
Consultants	Jamping			rive		Hole Depth: 5' Well Diameter: N/A				
Consultants	Casing Ty Slot Size		N/A N/A				Depth:	,		
	Gravel Pa		3.5' - !	5'	\blacksquare			Depth: N/A		
		Siaver Pack. S.5 - 5						r Depth: N/A		
Well		ے		T						
Sackfill onipalduno on water Level	는 보	PID Reading (ppm)	Sample Identification	Depth (feet)	Sam	nple	pe			
l ≡ ₹	Moisture Content	Readi (ppm)	m fica	E	ڇ	ā	Soil Type	LITHOLOGY / DESCRIPTION		
Backfill Water L	ΰος	ا ت ق	Sa	ebtt	Recovery	Interval	Soil			
8 5		E E	<u> </u>	ا ۵	Rec	Ë	· ·			
Asphalt								Sand with Gravel (SM) - Possible fill		
				, -			SM	material, brown to red brown, moist, medium		
Bent.	Moist			1 —				dense to dense, medium to coarse sand		
Grout				2				**************************************		
Bent.				3 —			SM	Silty Sand (SM) - Light brown, moist,		
Chips	1						314	medium dense, fine to coarse grained sand		
#2/12 —	Moist			4	<u> </u>			medium dense, fine to course grained sand		
Sand					**************************************					
		<u> </u>	V-1-S	5—				Daving Tamaingtod of Ellips		
				_				Boring Terminated at 5' bgs. Groundwater Not Enountered		
				6		 		Groundwater Not Errountered		
				_		╫		Soil Sample SV-1-S collected at 10:15 7/7/2009		
] -				7	1	 		3011 30111ptc 30 1 3 conceced at 10:13 7/7/2009		
					t		1			
				8-		T				
- - -				9]			
				_						
				10-	<u> </u>	<u> </u>				
					<u> </u>	<u> </u>				
				11	<u> </u>	 	-			
				-		<u> </u>	1			
	1			12-			ł			
				_	<u> </u>	ļ	1			
				13—						
_				–			1			
				14—			1			
		1		15_						
			1	15—						
				16—						
				10 _						
				17—		<u> </u>				
				_		-				
				18-	1	<u> </u>	ł			
				-	-	 	ł			
		·		19—	1	 	1			
_					+	\vdash	1			
				20			1			
<u> </u>		1		3, -			1			
				21	L		1			
				22—						

			Drojact N	~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~	-6202			Clier	Can	mistilita-a	In : 014 n	
				o: C10115		· Morgan				ocoPhillips akland, CA	Boring: SV-2	
	_		Logged By: S. Meninger/C. Morgan Driller: Gregg							: 7/7/2009	Page 1 of 1	
	Delta		Drilling Method: Hand Auger								Location Map	
				Method: I				Hole Diameter: 3.5" Hole Depth: 5'				
Consultants			Casing Type: N/A						Diame			
			Slot Size: N/A						Depth:	N/A		
				Gravel Pack: 3' - 4'						Depth: N/A		
Wel			∇					Static Water Depth: N/A				
Comple		ē	a	би	Sample Identification	l Fi	Sam	nple	d)			
		Water Level	Moisture Content	PID Reading (ppm)	icati	Depth (feet)	Ι.		Soil Type		OLOGY / DESCRIPTION	
Backfill		ater	10is Coni	Re (pp	Sam	l fi] Se	Interval	oii.	LILI	OLOGY / DESCRIPTION	
Ba		×	20	PI	Ide	De	Recovery	Inte	S			
Asphalt	\neg				-		 -					
	_					, -						
Bent. Grout			Moist			1 —				Silty Sand y	vith Gravel (SM) - Brown, moist,	
						2			SM		se, no odor, fine to coarse sand,	
Bent.									31.		ine to medium grained gravel	
Chips			Majat		İ	3		 —		rran gradea i	me to mediam granted graver	
#2/12 Sand			Moist		 V-2-S	-			ł			
Sallu 1					<u>v-2-3</u>	4	3000		_	Boring Terminated	at 4' has	
	-									Groundwater Not E	Enountered	
			:			5—			1			
						6—]	Soil Sample SV-2-9	S collected at 14:05 7/7/2009	
						7	 		ļ			
						_		 	ł			
						8	 	 	ł			
						9	<u> </u>	-				
						9						
						10	ļ	ļ				
							ļ		ļ			
						11	 					
						-	 		ł			
						12	 					
						13			1			
i						13—						
						14	_					
	-					-	\vdash	-	ļ			
						15—						
							<u> </u>					
						16—	<u> </u>		1			
						17	ļ					
	4					l	<u> </u>					
	\dashv					18—			-			
	-					-	┼	 	1			
						19—	 		1		_	
						20 -	L		1			
						20—]			
						21—	ļ		1			
	\dashv							<u> </u>	4			
	\dashv					22	\vdash		1			
					L	1	1	I	I	I	+	

			Project No	o: C1011	6202		-	Clion	t. Can	ocoPhillips	Paring: CV 5		
1			1			. Manaa					Boring: SV-3		
			Logged By: S. Meninger/C. Morgan							akland, CA	Page 1 of 1		
D - 11-		Driller: Gregg Drilling Method: Hand Auger						Drilled	l: 7/7/2009	Location Map			
11)(Delta							Hole	Diame	ter: 3.5"			
'	U !	CG	Sampling	Method: I	land Di	rive		Hole	Hole Depth: 5'				
l Con	sulta	nts	Casing Ty	pe:	N/A			Well	Diame	ter: N/A			
			Slot Size:		N/A			Well	Depth:	•			
			Gravel Pa		3.5' - !	5'					·		
			Sis 5					First Water Depth: N/A Static Water Depth: N/A					
We				I	T"		T	Juli	C Wate	r Depuit N/A	<u> </u>		
Comple		ē		PID Reading (ppm)	Sample Identification	<u>ਜ਼</u>	Sam	nple	a)	•			
		Water Level	Moisture Content	ig G	ple	Depth (feet)	_	_	Туре				
Backfill		ē	l is t	Re	E E	Ē	Recovery	Interval	<u> -</u>	LITH	OLOGY / DESCRIPTION		
act		Vat	žٽ		is en	e p	8	ter	Soil				
۳		>		Δ.	=		%	ı					
Asphalt										Silty Sand w	vith Gravel (SM) - Dark brown,		
	1 =					-	—		SM		se, moist, no odor, fine to		
Bent.			Moist	17.2		1	 		**************		ned sand, possible fill material		
Grout			1 10.50	-/		-				, inculum gran	neu sanu, possible illi illateriai		
Grout						2	┼	\vdash					
Bent.	┨		ĺ			-	\vdash			Loan Class	tith Sand (CL) Danie haracon		
						ј з—	-		CL		vith Sand (CL) - Dark brown,		
Chips				70.0		_					m plastic, stiff, hydrocarbon odo		
#2/12			Moist	78.9		4				lenses of olive	re green		
Sand						_ · _							
Sana			ļ	S	V-3-S	5—							
						_				Boring Terminated			
						6—			ļ	Groundwater Not E	nountered		
						0—							
										Soil Sample SV-3-9	S collected at 13:25 7/7/2009		
			İ			7 —		ļ					
+	•												
						8							
						9—		 					
	_					-			l				
						10	 		1				
						<u> </u>	-		ł				
						11	┼		ł				
						-		_	l				
						12-	-		l				
						_	<u> </u>						
						13		ļ					
					1	_ آ		<u> </u>	Į .				
					1	14]				
					1			L					
						15.							
1						15]				
1						16 -			1				
1						16	T	1	1				
	一						† · · · ·	 	1				
						17		T	1				
1	\neg				1		t -	t	1				
						18	 		1				
1	\dashv					-	 	\vdash	1				
1	\dashv				1	19	 	 	-				
]	\dashv				1	-	 	 	ł				
1	-				1	20 —	 		ł				
1						-	 	 	ł				
1						21	 	 	-				
1	_						<u> </u>	├					
1						22—	<u> </u>	<u> </u>					
								<u></u>			•		

			Project No	: C1011 5	56203			Clion	t. Con	ocoPhillips	Boring: SV-4
				y: S. Men		Morga				akland, CA	_
					iligei / C	Piorgai	•				Page 1 of 1
	۔ ا	L ~	Driller: G							: 7/7/2009	Location Map
D	ЭΙ.	ld		ethod: Ha						ter: 3.5 "	
				Method: I	Hand Di	rive		Hole	Depth	5'	
Con	sulta	ants	Casing Ty	pe:	N/A			Well	Diame	ter: N/A	
ŀ			Slot Size:		N/A			Well	Depth:	N/A	
l			Gravel Pa	ck:	3.5' - !	5'	lacksquare	First	Water	Depth: N/A	
							∇			r Depth: N/A	
We		_		-	_						
Comple	etion	Water Level	اج ہ	PID Reading (ppm)	Sample Identification	Depth (feet)	Sar	nple	e e		
=		, Le	Moisture Content) Readi (ppm)	달일	<u> </u>	چ	-	Туре	ITTL	OLOGY / DESCRIPTION
茶		ıte.	lois No.	P. (P.	l jar	t a	l š	Ž	Soil		OLOGI / DESCRIPTION
Backfill		×		PIC	[§ 6	De	Recovery	Interval	S		
	_						~				
Asphalt	! _					_					
						l 1—		<u> </u>	CL		CL) - Dark brown with black
Bent.	1 _		Moist	14.8		• _			\ _	mottling, mo	ist, stiff, medium plastic
Grout						2		<u></u>			
										Sandy Loan	Clay (CL) - Dark olive green to
Bent.						っ -					
Chips						3		1	CL		medium stiff, medium plastic,
	1 7		Moist	21.6						slight hydrod	
#2/12						4		T		Clavey Silt	(ML) - light brown with black
Sand				S	v-4-s	<u>-</u>			ML	mottling me	oist, very dense, non-plastic
	L				i i	5 —				Boring Terminated	at 5' has
						-	+	┼──		Groundwater Not	
						6—	+	+-	i	Groundwater Not i	Litountered
						-	+	+	1	Soil Cample CV 4	S collected at 12:40 7/7/2009
						7 <i>—</i>	+	1	1	Soli Sample SV-4-	3 collected at 12.40 ////2009
						-	+	+-	1		
						8—	-	├ ─	1		
	-					-		┼	1	-	
						9—	+		ļ		
						_	+	ļ	ł		
						10—		ļ	l		
	_							↓	l		
					1	11—		ļ			<u> </u>
					1				!		
					1	12		<u> </u>			
								<u>L</u>			
						13—					
						12—]		
						,,			1		
						14 —			1		
1						,		 	1		
						15—		 	1		
							—		1		
1						16 —		 	1		
	\neg					l	T	1			
						17	\top	 			
1	\dashv	i				-	+		1		
						18—	+	+	1		
	-				1	-	+-	+	ł		
						19 —	+-	+	1		
						-	+	1	ł		
						20 —		╂—	ł		
						-	4—	-	ł		
						21 —		1	ļ		
	_						<u></u>	 			
						22		4			
									l .		

	_		I Duniant Na		-6303	=		Cl:			
				: C10115						ocoPhillips	Boring: SV-5
					inger/C	C. Morgan				akland, CA	Page 1 of 1
		T	Driller: G ı	regg				Date	Drilled	: 7/7/2009	Location Map
De	וום	ra	Drilling M	ethod: Ha	nd Aug	er		Hole	Diame	ter: 3.5 "	
」レ い		CG		Method: I				Hole	Depth:	: 5'	
Con	sulta	nte	Casing Ty		N/A	•			Diame		
"	Suita	11115	Slot Size:		-						•
					N/A				Depth:		
			Gravel Pa	CK;	3.5' - !	5				Depth: N/A	
							∇	Stati	c Wate	r Depth: N/A	
Wel		75		6	<u> </u>	l					
Comple	etion	Water Level	Moisture Content	PID Reading (ppm)	Sample Identification	Depth (feet)	Sam	ipie	be		
I≡		ت	stu	eac	E 2	ا ا	<u>></u>	a	Soil Type	LTTH	OLOGY / DESCRIPTION
<u> </u>		ate	Aoi:) R (p	Sar	[8	₽r∨	oi Ii		101001 / DESCRIE 11014
Backfill		Š	~ ~	PIC	÷: 9	De	Recovery	Interval	S		
							<u>~</u>				
Asphalt	_					_			GW		d Gravel with Sand (GW) - light
						1 —			011	brown, dense	e, medium grained, moist,
Bent.			Moist	27.3		1 -				possible fill n	naterial
Grout										** Maldone content page and content page content	
						2 —					
Bent.						_				J ean Clay (CL) - Gray/black to olive green,
						3 —			CL		im stiff, medium, plastic,
Chips_	-		Maiak	227		_	\vdash	-			
#2/12			Moist	237		4	_			hydrocarbon	odor
Sand					ļ	_	***************************************				
Juna				S	<u>V-5-S</u>	5					
										Boring Terminated	
						6-				Groundwater Not E	nountered
					l	0-					
									İ	Soil Sample SV-5-	S collected at 11:00 7/7/2009
						7 —	1		1	Com Campic CV C	5 00.1100 de 11.00 7/7/2005
	-					_			1		
						8		_	1		
						_		-	1		
						9 —			ļ		
						_			1		
						10		L	1		
i						10 _			•		
						1.			1		
<u> </u>						11-			1		
						l			1		
						12	1	T	1		
	\dashv					_	 	 	1		
					1	13	+	\vdash	•		
	_					_	 	-			
						14					<u></u>
	_					_			į		
						15—	<u> </u>	<u> </u>			
						_]		
						16—					
	ļ.					10					
İ						, , _					
						17—			1		
							† · · · ·	T	1		
1						18	† · · ·	†	1		
						_	 	 	1		
						19 —	 	├	1		
						-	+	├	1	· · · · · · · · · · · · · · · · · · ·	
						20-	 	 	1		
	_				1	_	 	ļ			
						21-	ļ	<u> </u>	1		
					1]		
						22					
					1	22—			1		

			I Dunada at M	. 61844	6000			Ol:			
				: C10115		C. Morgan				ocoPhillips Boring: S	
			Driller: G		inger/C	J. Morgan	ı			akland, CA Page 1 of 1 : 7/7/2009 Location Map	<u> </u>
	\sim 1 \cdot	+->		ethod: Ha	nd Aug					: 7/7/2009 Location Map	
D	CI	La		ethod: na Method: i						· ·	
					rive			Depth			
Con	sulta	ants	Casing Ty		N/A				Diame	•	
			Slot Size: Gravel Pa		N/A 3.5' - !		_		Depth:	· · · · · · · · · · · · · · · · · · ·	
			Graver Pa	CK;	3.5 - :	5				Depth: N/A r Depth: N/A	
We	TT:	1			T	Τ	$\frac{}{1}$	Stat	ic wate	Deptil. N/A	
Comple		ē	a	PID Reading (ppm)	Sample Identification	FF (San	nple	. 62		
		Water Level	Moisture Content	m)	ple cat	Depth (feet)	>	_	Soil Type	1 TTUO 1 0 CV / D T C C D T	S
至		ţ.	ois	Re (pp	ar Itifi	듔	Ş	څ	I	LITHOLOGY / DESCRI	PITON
Backfill		× ×	Συ	PIO	Ger (Dep	Recovery	Interval	Ň		
L		ļ					<u> </u>				
Asphalt						_		ļ	GW	Well-Graded Gravel with San	
<u>_</u> .	l —		l			1	<u> </u>	ļ		brown, dense, medium grained,	dry to moist,
Bent.	_		Moist			_	 			possible fill material	***************************************
Grout	l —					2-	-	-			
Bent.	-					-	+		ļ	Loon Clay with Sand (CL)	the alive aver-
		ļ.				3	-		CL	Lean Clay with Sand (CL) - lig	
Chips	-		Moist			_	+	-		moist, soft to stiff, low plastic, s	crong
#2/12			MOISE			4 —	+		ł	hydrocarbon odor	
Sand		1	-		। V-6-S	_			-		
	Ь				V-0-3	5				Boring Terminated at 5' bgs.	
						-	+	┢┈	1	Groundwater Not Enountered	
						6-	+		1	Groundwater Not Endantered	
	-					-		l	1	Soil Sample SV-6-S collected at 9:45	7/7/2009
						7 —	†		1	Con Cample CV C C Concessed at 5. 10	17772003
	_								1		
						8—			†		
•									1		
						9—			1	,	
					1	10—]		
	_					1 10]		
						11	<u> </u>	ļ			
							ļ		1		
1						12—	ــــــ	<u> </u>	4		
	_						 	ļ	1		
						13—	-	<u> </u>	4		
	_					-	- 	ļ	1		
						14	 	-	4		
1	_				İ	_	+	-	4		
						15	+-	-	1		
	_					-	+	╁	1		
						16—	+	1	1		
	_					l	 	 	-		
						17—	+	†	1		
1						10 -	1		1		
						18—	1		1		
						19—]		
						19—					
						20—					
1						20					
1						21—	<u> </u>				
1						""	<u></u>	_			
						22 —	<u> </u>		1		
1			1		j			1	1		

			Project No	o: C1011	56203			Clien	t Con	ocoPhillips	Boring: SV-7	
						. Morgan				akland, CA	Page 1 of 1	
İ	_		Driller: G i		mgc., -	n norgan				l: 7/7/2009		
	\sim l \cdot	L \(\)	Drilling M		nd Aug					ter: 3.5 "	Location Map	
D(ロロ	ιa										
			Sampling			rive			Depth			
Con	sulta	ints	Casing Ty		N/A				Diame			
			Slot Size:		N/A		_		Depth:			
			Gravel Pa	ck:	3.5' - !	5'				Depth: N/A		
							∇	Stati	ic Wate	r Depth: N/A		
We		-E.		б	ءِ ا		C	1-				
Comple	etion	Water Level	Moisture Content	PID Reading (ppm)	Sample Identification	Depth (feet)	Sam	ipie	Soil Type			
=		ت ب	stu	kea pm	m Fic	5	e√	'al		LITH	IOLOGY / DESCRIPTION	
Backfill		ate	Moi Co	9	Sa	l pr	8	Interval	ioi		,	
Ba		>		PI	ğ	ă	Recovery	In	0,			
Asphalt								$\overline{}$				
Asphalt	l H							\vdash		Gravelly Sa	nd with Clay (SM) - Brown to	
Bent.			Moist	25.9		1 —	-	\vdash	SM			
	_		MOISE	25.9		-		\vdash	314		, medium dense to dense, mediu	ım
Grout						2 —	ļ	_		grained grav	el, possible fill material	
Dant								ļ				
Bent.						l з—	ļ	ļ			613 5 1	
Chips	4					_	ļ	<u> </u>			CL) - Blue-gray to light olive	
#2/12			Moist	54.5		4			CL		, stiff, medium plastic, slight	
Sand					ļ	l	***************************************			hydrocarbon	odor	
Suna				S	V-7-S	5—	**	a.				
						l			1	Boring Terminated		
						6				Groundwater Not E	Enountered	
					1	l						
						l 7—				Soil Sample SV-7-	S collected at 11:30 7/7/2009	
						/						
						。			1			
						8-			1			
									1			
						9—			1			
									1			
	,					10			i			
									1		-	
						11				3.1.1.1.1.1.1.1		
						l	1		1			
						12			1			
	\dashv					_	\vdash					
						13			1			
	-					-	\vdash	┢──	1			
						14	┼		1			
	\dashv				,	-	┿	 	1			
						15—	 	 	ł	-		
	-					-	├	├	ł			
	-					16	-	 				-
l						-	1	├	ł			=
						17	<u> </u>	-	-			
1					-	-	-	├	-			
			,			18	 	┢				
	-					_	<u> </u>	-	-			
						19—		ļ	4			
	4					_		ļ.,	4		·	
						20	1		1			
							ļ	<u> </u>	1			
						21]			
]			
						22.						
l						22—						

		Project	No:	C101156			Clier	it:	COP Boring/Well No: SVW-1
		Logged		Alan Bueh	ler				Oakland Page 1 of 2
		Driller:		Gregg Dri				Drilled	
Delt	- 2			Hand Aug				Diame	· · · · · · · · · · · · · · · · · · ·
	JU		ng Method					Depth	
Consultar	nts	Casing		1/4" Tubir	na			Diame	
		Slot Siz		_,	-3			Depth	
		Gravel		#30					Depth:
									er Depth:
		Elevation	on:		Northing	j:			Easting:
Well Completion	-		50						
	e e	말받	di Ç	<u>a</u> ig	eet	1	nple	pe	
≣ ₽	7	istu	gea bu	E E	٦	<u> </u>	ল	₹	LITHOLOGY / DESCRIPTION
Backfill	Water Level	Moisture Content	PID Reading (ppm)	Sample Identification	Depth (feet)	Į	Interval	Soil Type	
1 m 0	5		ā.	Ř	Ŏ	Recovery	Ē	٠,	
	***************************************					\vdash			
See						\vdash			
Construction					1	H	\neg		
Detail					-				
***************************************					2			CL	Brown lean clay with sand and gravel, moist
					3			•	
,,,							$\neg \neg$		
			'		4			<u> </u>	
						l		CH	Green/gray fat clay
					5—				Total Depth = 5'
					6				
									THE PROPERTY OF THE PROPERTY O
					7				The state of the s
					8				
	i	ĺ			9				
	I	ĺ			9				
year and an annual greekings.		ļ			10				
	İ				10				The second secon
		l			11				
	- 1				4.1.				A PARAMA A A LL L
	1				12				
					13				
****	i				14				
***********									THE RESIDENCE OF THE PROPERTY
100000000000000000000000000000000000000		İ	I		15	\Box			The control of the co
	1	- 1	l						
		1			16				
		- 1	į		*****				
			ĺ		17				All of the control of
									takkalannyy ja pite teletiteten en en en en en en en en en en en en e
					18—				
					-				
					19—				
					-			}	and the state of t
					20 —				
								1	
					21-		-	1	
		1						ŀ	
E fact to a south subsite one bridge	-		1		22		\dashv		A 2 4 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7

		Project	No:	C101156			Clier	it:	COP Boring/Well No: SVW-2
		Logged		Alan Bueh	ler				
	l	Driller:		Gregg Dri				Drillec	
Delt	\mathbf{a}			Hand Aug				Diame	•
	LU		ng Method					Depth	l l
Consultar	nts	Casing		1/4" Tubir	na			Diame	
		Slot Siz		,	•			Depth:	
		Gravel		#30		\blacksquare			r Depth:
						∇			er Depth:
	·	Elevation	on:		Northing):			Easting:
Well Completion	₇₆		Ō.	<u> </u>	Ξ.	l	nple		
	Į š	Moisture Content	ا ق	atic Se	ee ee			Soil Type	
≣ E		oista onte	Rea	Ei Si	ا ج	ē	ζą.	Ę	LITHOLOGY / DESCRIPTION
Backfill Casing	Water Level	žΰ	PID Reading (ppm)	Sample Identification	Depth (feet)	Recovery	Interval	Soi	
8 0	>		Δ.	_ ₽		8	ᆵ		
See					, _		П		
Construction					1				
Detail								Ć.	Brown/green lean clay with sand and gravel, 20%
					2			CL	sand, some gravel, cobbles, moist
					, -				1
					3 —				
					1 1				
					"-			СН	Green/gray clay
					5			OH	
I									Total Depth = 5'
·					6				NAVA NAVA NAVA NAVA NAVA NAVA NAVA NAVA
						L			
					7				
						<u> </u>			
					8	ļ			· · · · · · · · · · · · · · · · · · ·
					_				Million Control of the Control of th
					9				And the second s
					10				
		1				-			
***************************************					11		-		
					_				
					12				and the second s
***************************************					-				
					13 —				
						П			
					14				A STATE OF THE STA
					1 5				A STATE OF THE STA
	I	- 1			15				Visit in the second sec
	İ		ĺ		16				
	ļ				10				
					17—			l	
		- 1							
	ļ	- 1			18]		
A	1		İ		~ _				
A1-1112-2-1112-1111-2-2-2-2-2-2-2-2-2-2-			ļ		19—				
			İ		20			J	
		1	ļ		_				
***************************************					21-				The state of the s
]		j					
		1			22-		\dashv		

		Project	: No:	C101156			Clier	nt:	COP	· 1	Boring/Wel	No: SVW-3
		Logged	d By:	Alan Bueh	ıler			tion:	Oakland		Page 1 of	2
I 11		Driller:		Gregg Dri				: Drilled		/9/2010		
Delt	- 2			Hand Aug				Diame		6"		
	LU		ng Method		V 1			Depth				
Consultar	ate	Casing		1/4" Tubli	na.			Diame		/4"		
Consultar	165	Slot Siz		1/4 (000	ıy			Depth:				
		Gravei		#30		\blacksquare			Depth:	,		
		Graver	rack,	#30		7	rirst	water	Depth:			
İ		Elevation	on:		Northing	_ <u></u>	Stati	c wate	Easting:			
111.11.00		Lievati		<u> </u>	Moreting	-			casting:			
Well Completion	Water Level	ب رہ ا	PID Reading (ppm)	Sample Identification	(f	Sar	nple	w				
	<u>ച</u>	ter	β E Deg E	Cat	(fe	>	-	Гур				
in Sin	ŢĘ.	Moisture Content	8 g	iti ju	븄	Ιĕ	١٤	Soil Type		LIIH	OLOGY /	DESCRIPTION
Backfill	×	1 2 0		de o	Depth (feet)	Recovery	Interval	ഗ്				
					_	N.						
See					1							
Construction								CL		/green lean d	lay with	sand and gravel, strong
Detail					2			CL	odor			
					3							
					ر							
								CLI	Craule	حصلت ينسلم ممم	a ada.	
					4			Сп	Gray/gre	een clay, stror	ig odor	
					5—							
					5				Т	otal Depth =	± 5'	
					6					the first tender to the threshood and the transport to the same of		
					_				***************************************			
					7							
		1			8					PP\$ SPP 23 PP Charles and a structure of the control of the contro	·A44441110000411141141111111111111111111	
		Ì			9			i	***************************************		Applicação de presentado de las las parameiros e y ladir e y 4,4 d	
					9—					***************************************		
		ŀ			٦, ٦						······································	
					10 —			ı				
],, ¬				·/	·····		
	I	i			11-			i		*****	***************************************	
					I,, T				*******			and the second s
		ĺ			12							
					1, 7				·			
	[13							
		1			1,, 7			ı			~~~~	
					14							
		Ì	İ		1, 5					***************************************	 .	
		-	,		15							
					16-					1000 000 00 1 100 00 00 00 00 00 00 00 0		
		1	İ		10			•		TOTAL PROGRAMMENT TO A SECTION AND A SECTION ASSESSMENT	*****************************	
***************************************					17							
	l				1/						************************	
	l	- 1			10.			l	***************************************			
					18-					****		
				İ	₁₀ _							
					19 —			l	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	***********************************	and the state of t	
		-		ļ	30 T	\neg	一		to the transfer of the second section of the second second section of the section of the section of t			
		- 1			20			Ì	TO THE ST STORY OF THE STORY CONTRACTOR	eterbala a con un managa des temperary menegen desta de grade parte.	and controls about the standard and decide	The second secon
		- 1			, 	\neg	\dashv					
, and any and any and any any and any	1		1		21	一		ŀ				
						\dashv	-					
10 40 40 40 40 10 10 10 10 10 10 10 10 10 10 10 10 10		-			22			ŀ				

		Projec	t No:	C101156			Clier	nt:	COP Boring/Well No: SVW-4
		Logge		Alan Bueh	ıler				Oakland Page 1 of 2
		Driller		Gregg Dri				Drillec	
Delt	- 2			Hand Aug				Diame	
	-u		ing Method		. .			Depth	· · · · · · · · · · · · · · · · · · ·
Consultar	nts		туре:	1/4" Tubir	na			Diame	
		Slot Si		,	.5			Depth:	
		Gravel	Pack:	#30		\mathbf{Y}			Depth:
									r Depth:
		Elevat	ion:	,	Northing);			Easting:
Well Completion	70		0	Ę	۵ ا	L	nple		
	ě	l a ta	ح قِ ا	at Se	l e			,pe	
Backfill	Water Level	Moisture Content	PID Reading (ppm)	Sample Identification	Depth (feet)	Recovery	Interval	Soil Type	LITHOLOGY / DESCRIPTION
ack	٧at	ا≆ٽ		en Si	ept	8	ter	Soi	
aa O				<u> </u>	^	ag.	Ä		
See		1			1				
Construction			İ					CL	Dark brown/greenish lean clay with sand, strong
Detail					2		Ш		odor
		l	1						
1,000,000,000,000,000					3				
		1			4		Ш	СН	Green/brown clay, stong odor
					_				
					5	ļ			Talal Davids Pl
					ļ				Total Depth = 5'
					6		\vdash		
							\vdash		
					7 —	-	 		
					_ —				
\$					8 —	 -	**********		
									ANNIAN AND AND AND AND AND AND AND AND AND A
					9				
					10-				
					10				
					11				
							\Box		
					12				
					13				
			i		_				
·					14				
					15				The second secon
					16				***************************************
					,			Ì	
					17		$\neg \neg$		MARKET PER TENER TO THE
	1		l		10				The state of the s
					18			Ī	
					19		\Box	ĺ	
					20				
					→	\Box		Į.	THE COLUMN TO TH
	1				21].	
	- 1				ŀ	_].	
]				22 —			.	
					1		- 1		`

	Project	No:	C101156			Clien	nt:	COP	Boring/Well No: SVW-5
	Logged		Alan Bueh	ler				Oakland	Page 1 of 2
D - 14-	Driller:	Gregg Dril	ling			Drilled			
Delta	Drilling	Method:	Hand Auge			Hole	Diame		
		ng Methoc		•		Hole	Depth	: 5'	
Consultants	Casing		1/4" Tubin	g			Diame	•	
	Slot Siz				_		Depth:		
·	Gravel	Pack:	#30					Depth:	
	Elevation	nn:		Northing	∇	Stati	c Wate	r Depth: Easting:	-
Well Completion	Licyan	T	Ι		' -			casting.	
Sackfill and Casing Casing Water Level	₽ +	PID Reading (ppm)	Sample Identification	Depth (feet)	Sar	nple	e e		
ii e	Stu	рш	npd fica	(\$)	<u>></u>	<u> 75</u>	7,	LITH	OLOGY / DESCRIPTION
Backfill Casing Water L	Moisture Content	ا ق 9	Sa	ED#	Recovery	Interval	Soil Type		,
<u>i</u> i i i i i i i i i i i i i i i i i i		<u>G</u>	P	۵	æ	Ë	•		
See				1 —					
Construction				_			CL	Green/gray/black	lean clay with sand, some gravel,
Detail				2—				wood debris, stron	ıg odor
				3					
						$\vdash \vdash$			
***************************************	I			4			СН	Greenish gray clay, s	strong odor
				3				Total Depth	= 5'
				6				Mad (1939) 200-10-1-10-10-10-10-10-10-10-10-10-10-10	
				_	<u> </u>				
Terreserve de des constru				7 —				***************************************	
				8	-	\dashv			
	1					П			
				9 —					
				10					
				_		\longrightarrow		falance-t-real real real real real real real real	
w 				11	ļ				
				-					
	1			12		-			
						-		THE THE PARTY OF T	
				13		\neg			
				14					
				± 1				The state of the s	
				15					


		}		16					
WWW.				17—				···	
				18			- 1		
		l		10					
			Ì	19				The state of the s	
		-	ļ	•			ļ		
				20				The state of the s	
		1			\dashv	\dashv		***************************************	
				21	\dashv	\dashv		~~~	
				,,		\neg	l		
				22 —			Ì		


		Project	No:	C101156			Clien	t:	COP Borin	ng/Well No: SVW-6
		Logged		Alan Bueh	ler		Loca		Dakland Page	
		Driller:		Gregg Dri				Drillec		101 2
Delt	-			Hand Aug				Diame		
一つして	_u		ng Method		Çi			Depth	5'	
Consultar	nts	Casing		 1/4" Tubii	ng			Diame		
		Slot Si					Well	Depth:	5'	
		Gravel	Pack:	#30					Depth:	
İ				***************************************		<u>X</u>	Stati	c Wate	Depth:	
		Elevati	on:		Northing:	:			Easting:	
Well Completion	কৃ		PID Reading (ppm)	Sample Identification	g	Sam	nole			
	Ę	Moisture Content	ng Gi	ati e	l fee			Soil Type		
iii g	ē	a si	Re	ti ji	ا ق	é.	Ś	=	LITHOLO	GY / DESCRIPTION
Backfill	Water Level	žŬ	۾ ا	le so	Depth (feet)	Recovery	Interval	So		
ш			Ω.			ď	- ⊢			
See		1			1 1					
Construction					1 1					
Detail					2—			CL		ith sand, some gravel, some
nuncuant.					1 - 4	_		OL.	odor, asphault debris	
					3—					,
					4-					
					-	_		СН	Green/brown clay, strong o	odor
					5	\dashv				
					+				Total Depth = 5'	
					6-				*****	
any assessments.					+					
					7	-+				
					8	-			AND ALL OF SECURE SEC.	
					+	\dashv	-		Parties and the second	
	i				9-		-			
			i		-		\neg			
	ı	- 1			10-					
		1		:],, 🕇	_			VIVIAL	A STATE OF THE STA
	ļ	İ			11-		\neg			
					1,, 🕇					The state of the s
	i				12				77.77.70	
		1			13-					
	ł]			13					
	ĺ	1			14					
					14-					
					15					
	1				1" 4	_			Matthews	
	- 1				16					
		J				_				
		1			17					
					-				- 14 - 11 - 11 - 11 - 12 - 12 - 12 - 12	
I			ļ		18-		\dashv	ı		
,					+	\dashv	\dashv			
	- 1				19 —	+		l	***************************************	
					+	-			0	,
E papamage y tour and a service		1		-	20		\dashv			
					- 	+	\dashv			
					21 —	\dashv	\dashv		Additional to the second secon	
						\dashv	\dashv		Wathhama	and Alastonia and Alastonia and Alastonia and Alastonia and Alastonia and Alastonia and Alastonia and Alastonia
		ļ			22	\dashv	-			
L							1			


Attachment C

Cross Sections

Chevron Site 351645 November 2012







LEGEND . MONITORING WELL/SOIL BORING WELL CASING/EXPLORATORY BORING WELL SCREEN TOTAL DEPTH (DRILLING DATE) (9/12/84) ∇ ___ DEPTH TO FIRST WATER DEPTH TO GROUNDWATER (STATIC) 1000,70,2 SOIL SAMPLE LOCATION WITH ANALYTICAL DATA: TPPH, BENZENE, MTBE (mg/kg) GROUNDWATER SAMPLE LOCATION WITH 200/29/14 ANALYTICAL DATA: TPPH, BENZENE, MTBE (ug/L) MONITORING WELL GROUNDWATER SAMPLE DATE (7/19/07 Q) Q=QUARTERLY SAMPLE **ASPHALT** CONCRETE CLAY AND/OR SILT (CH,CL,ML) SAND WITH CLAY (SC) APPROXIMATE STRATIGRAPHIC BOUNDARY

NOTES:

- 1) <0.50=BELOW LABORATORY REPORTING LIMITS TPPH=TOTAL PURGEABLE PETROLEUM HYDROCARBONS MTBE=METHYL TERT BUTYL ETHER ug/L=MICROGRAMS PER LITER mg/kg=MILLIGRAMS PER KILOGRAM
- 2) STRATIGRAPHY BETWEEN BORINGS IS INTERPRETIVE.
- 3) GROUNDWATER SAMPLES FROM BORINGS WERE COLLECTED ON THE DRILLING DATE.
- 4) DEPTH TO FIRST WATER IN WELLS WAS MEASURED ON THE DRILLING DATE. DEPTH TO STATIC WATER IN WELLS MEASURED DURING MOST RECENT QUARTERLY SAMPLING EVENT.




FIGURE 4 GEOLOGIC CROSS SECTION B-B'

76 SERVICE STATION 1156 4276 MACARTHUR BOULEVARD OAKLAND, CALIFORNIA

PROJECT NO.	PREPARED BY	DRAWN BY	
C101156	мн	JH	
DATE	REVIEWED BY	FILE NAME	
12/26/07		1156-CrosB	DELTA

Attachment D

Historical Data Tables

Chevron Site 351645 November 2012

TABLE 1
Soil Analytical Results - 1998 through 2009
76 Service Station No. 1156
4276 MacArthur Boulevard, Oakland, California

	Sample ID	Date	Sample	TPH-G	TPH-D	Total Oil &	Benzene	Toluene	Ethyl-benzene	Total Xylenes	MTBE	TBA	ETBE	TAME	DIPE	1,2-DCA	EDB	Ethanol
			Depth (feet)	((1)	((1)	Grease	(mg/kg)	((1)	((1)	((1)	(//)	((1)	((1)	((1)	((1)	((1)	((1)	((1)
Soil			(reet)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)
3011	S-6-T1N	3/23/98	6	1,200			0.90	ND	14	100								
	S-9.5-T1S	3/23/98	9.5	590			1.5	ND	5.6	33								
	S-7-T2S	3/23/98	7.0	670			1.0	0.74	6.8	51								
Inc.	S-6-T2N	3/23/98	6	83			ND	ND	0.15	0.41								
=	S-6.5-T35*	3/23/98	6.5	130	78,000	_	0.55	1.3	1.2	11								
Ś	S-2-D1	4/9/98	2	ND			ND	ND	ND	ND								
Ĕ	S-3-D2	4/9/98	3	16			ND	ND	ND	0.13								
ξi	S-3-D3	4/9/98	3	590			1.6	15	18	99								
ū	S-3-D4 S-3-PL1	4/9/98 4/9/98	3	ND 160			ND ND	ND ND	ND ND	0.07 8.4								
So	S-3.5-PL2	4/9/98	3.5	63			ND ND	ND	ND ND	0.45								
Resolutions	S-4.5-T3W	4/9/98	4.5	5.0	2.3		ND	0.066	ND	0.011								
	S-3-T3S	4/9/98	3	1.6	ND		0.043	ND	0.0091	ND								
ta	S-6-T3S	4/9/98	6	81	560		0.64	1.4	1.1	5.9								
<u>0</u>	S-10.5-B1 (MW-1)	7/16/99	10.5	6,800			2.6	25	110	470	ND							
Ě	S-10.5-B2 (MW-2)	7/16/99	10.5	ND			ND	ND	ND	ND	ND							
Ę	S-10.5-B3 (MW-3)	7/16/99	10.5	16			0.32	0.43	0.28	1.8	0.60							
Environmental	S-10.5-B4 (MW-4)	7/16/99	10.5	22			1.1	0.32	0.46	1.3	0.71							
۶ ا	S-20.5-B4 (MW-4)	7/16/99	20.5	ND			ND	ND	0.0069	ND	ND							
ū	S-5-MW5	8/29/01	5	<1.0			< 0.005	< 0.005	< 0.005	< 0.005	<0.005							
	S-5-MW6 S-5-MW7	8/29/01 8/29/01	5 5	<1.0 <1.0			<0.005 <0.005	<0.005 <0.005	<0.005 <0.005	<0.005 <0.005	<0.005 <0.005							
	S-10-MW7	8/29/01	10	<5.0			0.18	<0.005	0.085	0.234	<0.005							
	MW-8-10	10/30/07	10	<0.20		220	< 0.005	< 0.005	< 0.005	<0.01	<0.005							
	MW-8-15	10/30/07	15	<0.20		<50	< 0.005	< 0.005	< 0.005	<0.01	<0.005							
	MW-8-20	10/30/07	20	<0.20		<50	< 0.005	< 0.005	< 0.005	<0.01	<0.005							
	SB-1-7	11/6/07	7	360		<50	<0.25	<0.25	4.2	17	<0.25							
	SB-1-12	11/6/07	12	20		<50	<0.025	< 0.025	1.7	2.2	< 0.025							
	SB-1-18.5	11/6/07	8.5	2.3		<50	<0.005	< 0.005	0.067	0.30	< 0.005							
	SB-1-33.5	11/6/07	33.5	3.1		<50	<0.005	0.012	0.26	0.14	< 0.005							
	SB-2-8.5	11/5/07	8.5	1,200		<50	7.8	51	24	120	<2.5							
	SB-2-12	11/5/07	12	120		<50	1.2	< 0.25	2.3	12	1.2							
	SB-2-20	11/5/07	20	0.29		<50	0.016	0.011	0.0079	0.029	0.029							
	SB-2-25	11/5/07	25	< 0.20		<50	< 0.005	< 0.005	< 0.005	< 0.01	< 0.005							
ıts	SB-3-7	11/2/07	7	< 0.20		<50	< 0.005	< 0.005	< 0.005	< 0.01	0.015							
ä	SB-3-15	11/2/07	15	<0.20		<50	< 0.005	< 0.005	< 0.005	<0.01	< 0.005							
I 👯	SB-3-20	11/2/07	20	0.33		<50	<0.005	< 0.005	< 0.005	< 0.01	0.34							
181	SB-3-25	11/2/07	25	0.27		<50	< 0.005	< 0.005	< 0.005	< 0.01	0.24							
Consultants	SB-4-8	10/30/07	8	0.96		<50	<0.005	< 0.005	< 0.005	< 0.01	< 0.005							
	SB-4-11	10/30/07	11	< 0.20		<50	< 0.005	< 0.005	< 0.005	< 0.01	< 0.005							
Ita	SB-4-16	10/30/07	16	< 0.20		<50	< 0.005	< 0.005	< 0.005	< 0.01	< 0.005							
Delta	SB-4-27	10/30/07	27	< 0.20		<50	< 0.005	< 0.005	< 0.005	< 0.01	< 0.005							
	SB-5-7	11/1/07	7	150		<50	0.28	0.31	1.7	8.6	< 0.12							
	SB-5-12	11/1/07	12	6.0		< 50	< 0.025	< 0.025	< 0.025	< 0.05	< 0.025							
	SB-5-17	11/1/07	17	1,700		<50	3.0	13	28	99	<1.0							
	SB-5-22	11/1/07	22	< 0.20		<50	0.009	< 0.005	< 0.005	< 0.01	< 0.005							
	SB-5-30	11/1/07	30	< 0.20		<50	0.0087	< 0.005	< 0.005	< 0.01	< 0.005							
	SB-6-5	10/31/07	5	72		<50	< 0.025	< 0.025	0.047	< 0.01	< 0.025							
	SB-6-8.5	10/31/07	8.5	2.0		<50	0.016	< 0.005	0.016	< 0.01	0.016							
	SB-6-12	10/31/07	12	< 0.20		<50	< 0.005	< 0.005	< 0.005	< 0.01	0.016							
	SB-6-15	10/31/07	15	< 0.20		<50	< 0.005	< 0.005	< 0.005	< 0.01	0.029							
	SB-6-17	10/31/07	17	< 0.20		<50	< 0.005	< 0.005	< 0.005	< 0.01	< 0.005							
	SB-6-30.5	10/31/07	30.5	< 0.20		<50	< 0.005	< 0.005	< 0.005	< 0.01	< 0.005							
<u> </u>					Ⅎ										·		·	

TABLE 1

Soil Analytical Results - 1998 through 2009

76 Service Station No. 1156

4276 MacArthur Boulevard, Oakland, California

	Sample ID	Date	Sample	TPH-G	TPH-D	Total Oil &	Benzene	Toluene	Ethyl-benzene	Total Xylenes	MTBE	TBA	ETBE	TAME	DIPE	1,2-DCA	EDB	Ethanol
			Depth			Grease												
			(feet)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)
Soil																		
	SV-1-S	7/7/09	4.5	< 0.20			< 0.005	< 0.005	< 0.005	< 0.01	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	<1.0
	SV-2-S	7/7/09	3	< 0.20			< 0.005	< 0.005	< 0.005	< 0.01	< 0.005	< 0.5	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	<1.0
	SV-3-S	7/7/09	4.5	17			< 0.025	< 0.025	< 0.025	0.15	< 0.025	< 0.25	< 0.025	< 0.025	< 0.025	< 0.025	< 0.005	<5.0
	SV-4-S	7/7/09	4.5	0.23			0.027	< 0.005	< 0.005	< 0.01	0.02	0.16	< 0.005	<0.005	< 0.005	< 0.005	< 0.005	<1.0
	SV-5-S	7/7/09	4.5	24			< 0.05	< 0.05	< 0.05	0.15	< 0.05	< 0.5	< 0.50	< 0.50	< 0.50	< 0.50	< 0.005	<10
ts	SV-6-S	7/7/09	4.5	< 0.20			< 0.005	< 0.005	< 0.005	< 0.01	< 0.005	< 0.05	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	<1.0
<u>۾</u>	SV-7-S	7/7/09	4.5	4.6			< 0.005	< 0.005	< 0.005	<1.0	< 0.005	< 0.05	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	<1.0
l ≝	SB-7 @ 7.5-8	7/9/09	7.5-8	260			< 0.50	< 0.50	5.7	32	< 0.50	< 5.0	< 0.50	< 0.50	< 0.50	< 0.50	< 0.005	<100
l s	SB-7 @ 15.5-16	7/9/09	15.5-16	1.3			0.008	< 0.005	< 0.005	0.023	0.0085	< 0.05	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	<1.0
<u> </u>	SB-7 @ 23-23.5	7/9/09	23-23.5	< 0.20			< 0.005	< 0.005	< 0.005	< 0.01	< 0.005	< 0.05	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	<1.0
ပိ	SB-8 @ 7.0-7.5	7/10/09	7.0-7.5	760			< 0.50	< 0.50	7.7	<1.0	< 0.50	<10	< 0.50	< 0.50	< 0.50	< 0.50	< 0.005	<250
Ö	SB-9 @ 15.5-16	7/8/09	15.5-16	< 0.20			< 0.005	< 0.005	< 0.005	< 0.01	0.019	< 0.05	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	<1.0
<u>=</u>	SB-9 @ 26	7/8/09	26	< 0.20			< 0.005	< 0.005	< 0.005	< 0.01	< 0.005	< 0.05	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	<1.0
Ŏ	SB-10 @ 12-12.5	7/10/09	12-12.5	400			< 0.50	< 0.50	6.1	46	< 0.50	<5.0	< 0.50	< 0.50	< 0.50	< 0.50	< 0.005	<100
	SB-10 @ 18-18.5	7/10/09	18-18.5	290			< 0.50	< 0.50	5	34	< 0.50	< 5.0	< 0.50	< 0.50	< 0.50	< 0.50	< 0.005	<100
	SB-10 @ 22.5-23	7/10/09	22.5-23	0.78			< 0.005	< 0.005	< 0.005	0.056	< 0.005	< 0.05	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	<1.0
	SB-11 @ 7.5-8	7/10/09	7.5-8	41			< 0.05	< 0.50	0.5	0.77	< 0.50	< 0.50	< 0.50	< 0.50	< 0.50	< 0.50	< 0.005	<10
	SB-11 @ 15.5-16	7/10/09	15.5-16	200			0.26	0.0094	< 0.005	0.015	< 0.005	< 0.50	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	<1.0
	SB-11 @ 41-41.5	7/10/09	41-41.5	< 0.20			< 0.005	< 0.005	< 0.005	< 0.01	< 0.005	< 0.05	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	<1.0

TPH-G = total purgeable petroleum hydrocarbons as gasoline by EPA Method 8260B TPH-D = total purgeable petroleum hydrocarbons as diesel by EPA Method 8015M TOG = total oil and grease by EPA Method 1664

TOG = total oil and grease by EPA Method 1664
BTEX = benzene, toluene, ethylbenzene, total xylenes by EPA Method 8260B
MTBE = methyl tertiary butyl ether by EPA Method 8260B
TBA = tertiary butyl alcohol by EPA Method 8260B
ETBE = ethyl tertiary butyl ether by EPA Method 8260B
TAME = tertiary amyl methyl ether by EPA Method 8260B
DIPE = di-isopropyl ether by EPA Method 8260B

1,2-DCA = 1,2-Dichloroethane (also known as ethylene dichloride) by EPA Method 8260B EDB = ethylene dibromide (also known as 1,2-Dibromoethane) by EPA method 8260B Ethanol was analyzed by EPA Method 8260B

mg/kg = milligrams per kilogram

ND = not detected above the laboratory detection limit

Bold = detected compound concentration

EPA = US Environmental Protection Agency

* = Overexcavated on April 9, 1989

Table 2a

Soil Analytical Results - August 2010 76 Service Station No. 1156

76 Service Station No. 1156 4276 MacArthur Boulevard Oakland, California

Boring	Depth	Date	TPHg (8015M)	TPHd	TPHmo	Benzene	Toluene	Ethylbenzene	Total Xylenes	MTBE	EDB	1,2-DCA	TAME	TBA	DIPE	ETBE	Ethanol
	(ft)		(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)
	6	6/15/2010	3.8	<2.0	28	0.11	<0.0050	0.37	0.44	<0.0050	< 0.0050	< 0.0050	< 0.0050	0.11	< 0.0050	< 0.0050	<1.0
	10	6/15/2010	<5	<2.0	<10	0.081	<0.0050	0.43	0.5	<0.0050	<0.0050	< 0.0050	< 0.0050	0.091	< 0.0050	< 0.0050	<1.0
	15	6/15/2010	1.7	<100	830	0.29	<0.0050	0.45	0.58	<0.0050	<0.0050	<0.0050	<0.0050	0.062	<0.0050	<0.0050	<1.0
	20	6/15/2010	<5.0	<2.0	11	0.052	<0.0050	0.41	0.72	< 0.0050	< 0.0050	< 0.0050	< 0.0050	0.05	< 0.0050	<0.0050	<1.0
SB-12	26	6/15/2010	<5.0	<2.0	<10	<0.0050	<0.0050	<0.0050	<0.010	<0.0050	<0.0050	<0.0050	<0.0050	< 0.050	<0.0050	<0.0050	<1.0
05 12	30	6/15/2010	<1.0	<2.0	<10	< 0.0050	<0.0050	<0.0050	<0.010	<0.0050	<0.0050	<0.0050	<0.0050	<0.050	<0.0050	<0.0050	<1.0
	35	6/15/2010	<1.0	<2.0	<10	<0.0050	<0.0050	0.0068	<0.010	<0.0050	<0.0050	<0.0050	<0.0050	<0.050	<0.0050	<0.0050	<1.0
	41	6/15/2010	<1.0	<2.0	12	<0.025	<0.025	<0.025	<0.050	<0.025	<0.025	<0.025	<0.025	<0.25	<0.025	<0.025	<5.0
	45	6/15/2010	<1.0	<2.0	<10	<0.0050	<0.0050	<0.0050	<0.010	<0.0050	<0.0050	<0.0050	<0.0050	<0.050	<0.0050	<0.0050	<1.0
	50	6/15/2010	<1.0	<2.0	24	<0.0050	<0.0050	<0.0050	<0.010	<0.0050	<0.0050	<0.0050	<0.0050	<0.050	<0.0050	<0.0050	<1.0
SB-13	6	6/18/10	680	76	<100	<0.50	< 0.50	4.4	<1.0	<0.50	<0.50	<0.50	<0.50	<5.0	<0.50	<0.50	<100
	8	6/17/10	9.9	<2.0	<10	0.073	0.26	1.7	8	0.0088	<0.0050	<0.0050	<0.0050	<0.050	<0.0050	<0.0050	<1.0
-	10	6/17/10	35	<2.0	<10	0.28	0.21	1.7	7.9	0.033	<0.0050	<0.0050	<0.0050	0.093	<0.0050	<0.0050	<1.0
-	15	6/17/10	<1.0	<10	100	0.097	<0.0050	0.031	0.051	0.031	<0.0050	<0.0050	<0.0050	0.081	<0.0050	<0.0050	<1.0
-	20	6/17/10	<1.0	<2.0	17 31	0.0064	0.0099	0.05	0.24	<0.0050	<0.0050	<0.0050	<0.0050	<0.050	<0.0050	<0.0050	<1.0
SB-14	26 30	6/17/10 6/17/10	<1.0 <1.0	<2.0 <2.0	<10	0.0076 < 0.0050	0.012 < 0.0050	0.085 < 0.0050	0.36 <0.0050	<0.0050 <0.0050	<0.0050 <0.0050	<0.0050 <0.0050	<0.0050 <0.0050	<0.050 <0.050	<0.0050 <0.0050	<0.0050 <0.0050	<1.0 <1.0
-	35	6/17/10	<1.0	<2.0	<10	<0.0050	<0.0050	<0.0050	<0.0050	<0.0050	<0.0050	<0.0050	<0.0050	<0.050	<0.0050	<0.0050	<1.0
=	40	6/17/10	<1.0	<2.0	19	<0.0050	<0.0050	0.014	0.079	<0.0050	<0.0050	<0.0050	<0.0050	<0.050	<0.0050	<0.0050	<1.0
-	45	6/17/10	6.8	<2.0	20	0.018	<0.0050	0.27	1	<0.0050	<0.0050	<0.0050	<0.0050	<0.050	<0.0050	<0.0050	<1.0
	50	6/17/10	<1.0	<2.0	<10	<0.0050	<0.0050	<0.0050	<0.0050	<0.0050	<0.0050	<0.0050	<0.0050	<0.050	<0.0050	<0.0050	<1.0
	5	6/18/10	<1.0	<2.0	<10	<0.0050	<0.0050	<0.0050	<0.010	<0.0050	<0.0050	<0.0050	<0.0050	<0.050	<0.0050	<0.0050	<1.0
	10	6/18/10	<1.0	<2.0	<10	<0.0050	<0.0050	<0.0050	<0.010	<0.0050	<0.0050	<0.0050	<0.0050	<0.050	<0.0050	<0.0050	<1.0
-	15	6/18/10	<1.0	<2.0	<10	<0.0050	<0.0050	<0.0050	<0.010	<0.0050	<0.0050	<0.0050	<0.0050	<0.050	<0.0050	<0.0050	<1.0
	21.5	6/18/10	<1.0	<2.0	<10	<0.0050	<0.0050	<0.0050	<0.010	<0.0050	<0.0050	<0.0050	<0.0050	<0.050	<0.0050	<0.0050	<1.0
SB-15	26.5	6/18/10	<1.0	<2.0	<10	<0.0050	<0.0050	<0.0050	<0.010	<0.0050	<0.0050	<0.0050	<0.0050	<0.050	<0.0050	<0.0050	<1.0
-	30	6/18/10	<1.0	<2.0	<10	<0.0050	<0.0050	<0.0050	<0.010	<0.0050	<0.0050	<0.0050	<0.0050	< 0.050	<0.0050	<0.0050	<1.0
-	35	6/18/10	<1.0	<2.0	<10	< 0.0050	<0.0050	< 0.0050	<0.010	<0.0050	<0.0050	<0.0050	<0.0050	< 0.050	<0.0050	<0.0050	<1.0
-	40	6/18/10	<1.0	<2.0	<10	< 0.0050	<0.0050	< 0.0050	<0.010	<0.0050	<0.0050	< 0.0050	<0.0050	< 0.050	< 0.0050	<0.0050	<1.0
	8	6/16/10	<1.0	<2.0	<10	<0.025	< 0.025	< 0.025	< 0.050	<0.025	< 0.025	<0.025	< 0.025	<0.25	< 0.025	<0.025	<5.0
-	10	6/16/10	<1.0	<2.0	<10	< 0.0050	<0.0050	< 0.0050	<0.010	<0.0050	<0.0050	< 0.0050	<0.0050	< 0.050	< 0.0050	<0.0050	<1.0
	15	6/16/10	<1.0	<99	<500	<0.010	<0.010	<0.010	<0.010	<0.010	<0.010	<0.010	<0.010	<0.10	<0.010	<0.010	<2.0
	20	6/16/10	<1.0	<2.0	<10	<0.0050	<0.0050	<0.0050	<0.010	<0.0050	<0.0050	<0.0050	<0.0050	< 0.050	<0.0050	<0.0050	<1.0
SB-16	25	6/16/10	<1.0	<2.0	30	<0.0050	<0.0050	<0.0050	<0.010	<0.0050	<0.0050	<0.0050	<0.0050	<0.050	<0.0050	<0.0050	<1.0
05 10	30	6/16/10	<1.0	<2.0	<10	<0.0050	<0.0050	<0.0050	<0.010	0.041	<0.0050	<0.0050	<0.0050	<0.050	<0.0050	<0.0050	<1.0
	35	6/16/10	<1.0	<2.0	<10	<0.0050	<0.0050	<0.0050	<0.010	<0.0050	<0.0050	<0.0050	<0.0050	<0.050	<0.0050	<0.0050	<1.0
	40	6/16/10	<1.0	<2.0	<10	<0.0050	<0.0050	<0.0050	<0.010	<0.0050	<0.0050	<0.0050	<0.0050	<0.050	<0.0050	<0.0050	<1.0
-	46	6/16/10	<1.0	<2.0	<10	<0.0050	<0.0050	<0.0050	<0.010	<0.0050	<0.0050	<0.0050	<0.0050	<0.050	<0.0050	<0.0050	<1.0
	50	6/16/10	<1.0	<2.0	<10	<0.0050	<0.0050	<0.0050	<0.010	<0.0050	<0.0050	<0.0050	<0.0050	<0.050	<0.0050	<0.0050	<1.0
-	5	6/16/10	530	<2.0	40	<0.0050	<0.0050	<0.0050	<0.010	<0.0050	<0.0050	<0.0050	<0.0050	<0.050	<0.0050	<0.0050	<1.0
-	10	6/16/10	130	<2.0	<10	0.021	<0.0050	0.0081	<0.010	0.024	<0.0050	<0.0050	<0.0050	0.17	<0.0050	<0.0050	<1.0
	15	6/16/10	<1.0	<2.0	<10 130	<0.0050	<0.0050	<0.0050	<0.010	<0.0050 0.011	<0.0050	<0.0050	<0.0050	0.13	<0.0050	<0.0050	<1.0
]	20 25	6/16/10 6/16/10	9.8	<2.0 <20	<100	0.11	0.0093 < 0.0050	0.5 0.031	0.058		<0.0050	<0.0050	<0.0050	<0.050 <0.050	<0.0050	<0.0050 <0.0050	<1.0 <1.0
SB-17	30	6/16/10	<1.0 <1.0			<0.0050 <0.0050			<0.010	<0.0050	<0.0050	<0.0050	<0.0050	<0.050	<0.0050		<1.0 <1.0
-	35	6/16/10	<1.0	<2.0 <2.0	<10 <10	<0.0050	<0.0050 <0.0050	<0.0050 <0.0050	<0.010	<0.0050 <0.0050	<0.0050 <0.0050	<0.0050 <0.0050	<0.0050 <0.0050	<0.050	<0.0050 <0.0050	<0.0050 <0.0050	<1.0
	40	6/16/10	<1.0	<2.0	<10	<0.0050	<0.0050	<0.0050	<0.010 <0.010	<0.0050	<0.0050	<0.0050	<0.0050	<0.050	<0.0050	<0.0050	<1.0
	47	6/16/10	17	<2.0	<10	0.005 0	<0.0050	0.49	<0.010	<0.050	<0.050	<0.050	<0.050	<0.050	<0.050	<0.050	<1.0
	50	6/16/10	<1.0	<2.0 <2.0	<10	<0.0050	<0.050	<0.0050	<0.10	<0.050	<0.050	<0.050	<0.050	<0.050	<0.050	<0.050	<1.0
11	50	0/10/10	<1.0	<2.0	<10	<0.0050	VCUU.U>	<0.0050	<0.010	<0.0050	<0.0000	<0.0000	<0.0050	<0.000	<0.0050	<0.0050	<1.0

Table 2a

Soil Analytical Results - August 2010

76 Service Station No. 1156 4276 MacArthur Boulevard Oakland, California

Boring	Depth	Date	TPHg (8015M)	TPHd	TPHmo	Benzene	Toluene	Ethylbenzene	Total Xylenes	MTBE	EDB	1,2-DCA	TAME	TBA	DIPE	ETBE	Ethanol
	(ft)		(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)
	7.5	6/15/10	<1.0	<200	<1000	< 0.0050	< 0.0050	< 0.0050	< 0.010	< 0.0050	< 0.0050	< 0.0050	< 0.0050	< 0.050	< 0.0050	<0.0050	<1.0
SB-18	10	6/15/10	2.6	<2.0	<10	<0.0050	< 0.050	0.081	<0.10	< 0.050	< 0.050	< 0.050	< 0.050	< 0.50	< 0.050	< 0.050	<10
2B-18	15	6/15/10	<1.0	6.7	<10	5	25	51	210	<0.25	<0.25	<0.25	<0.25	<2.5	<0.25	<0.25	<50
	20	6/15/10	<1.0	<2.0	<10	< 0.0050	< 0.0050	< 0.0050	<0.010	< 0.0050	< 0.0050	< 0.0050	< 0.0050	< 0.050	< 0.0050	< 0.0050	<1.0
	7.5	6/15/10	1.5	<2.0	<10	< 0.050	< 0.050	< 0.050	<0.10	< 0.050	<0.050	< 0.050	< 0.050	<0.50	< 0.050	< 0.050	<10
SB-19	10	6/15/10	1.6	<2.0	<10	< 0.050	< 0.050	< 0.050	<0.10	< 0.050	< 0.050	< 0.050	< 0.050	< 0.50	< 0.050	< 0.050	<10
30-19	15	6/15/10	<1.0	<2.0	39	< 0.0050	< 0.0050	< 0.0050	<0.010	0.017	< 0.0050	< 0.0050	< 0.0050	< 0.050	< 0.0050	<0.0050	<1.0
	20	6/15/10	<1.0	<2.0	11	< 0.0050	<0.0050	< 0.0050	< 0.010	0.013	< 0.0050	< 0.0050	< 0.0050	< 0.050	< 0.0050	<0.0050	<1.0
	5	8/17/2010	210	31		1.1	0.054	4.5	0.48	<0.0050	<0.0050	0.031	<0.0050	< 0.050	<0.0050	<0.0050	<1.0
	10	8/17/2010	<1.0	2.7		3	9.8	57	220	0.3	<2.5	<2.5	<2.5	<25	<2.5	<2.5	<500
MW-1B	15	8/17/2010	270	110		<2.5	6.2	38	150	<2.5	<2.5	<2.5	<2.5	<25	<2.5	<2.5	<500
	20	8/17/2010	200	<200		0.23	0.15	2.4	0.88	0.061	<0.010	<0.010	<0.010	<0.10	<0.010	<0.010	<2.0
	25	8/17/2010	<1.0	<2.0		<0.0050	0.0085	0.012	0.056	< 0.0050	<0.0050	<0.0050	<0.0050	< 0.050	<0.0050	<0.0050	<1.0
	5	8/16/2010	<1.0	<200		0.009	< 0.0050	0.011	0.12	0.03	<0.0050	<0.0050	<0.0050	<0.050	<0.0050	<0.0050	<1.0
	10	8/16/2010	54	<2.0		<0.0050	0.02	0.28	0.84	0.0085	<0.0050	<0.0050	<0.0050	<0.050	<0.0050	<0.0050	<1.0
MW-2B	15	8/16/2010	55	<200		<0.0050	< 0.0050	0.32	0.69	0.25	<0.0050	<0.0050	<0.0050	<0.050	<0.0050	<0.0050	<1.0
	20	8/16/2010	4.4	<1200		0.076	0.18	1.1	3.3	0.099	<0.025	<0.025	<0.025	<0.25	< 0.025	<0.025	<5
	25	8/16/2010	<1.0	2		<0.0050	< 0.0050	<0.0050	<0.010	<0.0050	<0.0050	<0.0050	<0.0050	< 0.050	<0.0050	<0.0050	<1.0
	5	8/16/2010	<1.0	<20		<0.0050	< 0.0050	<0.0050	<0.010	<0.0050	<0.0050	<0.0050	<0.0050	<0.050	<0.0050	<0.0050	<1.0
	10	8/16/2010	1.3	<20		0.018	0.075	0.1	0.54	<0.0050	<0.0050	<0.0050	<0.0050	<0.050	<0.0050	<0.0050	<1.0
MW-3B	15	8/16/2010	310	150		<5	20	33	180	<5	<5	<5	<5	<50	<5	<5	<1000
	20	8/16/2010	<1.0	<20		<0.12	0.46	0.38	2	<0.12	<0.12	<0.12	<0.12	<1.2	<0.12	<0.12	<25
	25	8/16/2010	4.6	<2.0		<0.0050	0.042	0.061	0.37	< 0.0050	<0.0050	<0.0050	<0.0050	< 0.050	<0.0050	<0.0050	<1.0
	5	8/13/2010	<1.0	<20		<0.0050	<0.0050	0.025	<0.010	<0.0050	<0.0050	<0.0050	<0.0050	< 0.050	<0.0050	<0.0050	<1.0
	10	8/13/2010	15	27	<10	<0.025	<0.025	0.43	0.15	<0.025	<0.025	<0.025	< 0.025	<0.25	<0.025	< 0.025	<5
MW-4B	15	8/13/2010	840	15		<0.50	0.89	41	170	<0.50	< 0.50	<0.50	<0.50	<5	<0.50	< 0.50	100
	20	8/13/2010	1.1	<2.0		<0.50	<0.50	0.76	4.3	<0.50	<0.50	<0.50	<0.50	<5	<0.50	<0.50	100
	25	8/13/2010	150	4.4		<0.12	<0.12	0.39	2.4	<0.12	<0.12	<0.12	<0.12	<1.2	<0.12	<0.12	<25

TPHg = total petroleum hydrocarbons as gaoline TPHd = total petroleum hydrocarbons as gaoline TPHd = total petroleum hydrocarbons as motor oil EDB = ethylene dibromide 1,2-DCA = 1,2 dichloroethane MTBE = mety; tert butyl ether TAME = tert amyl methyl ether TBA = tert butyl alcohol DIPE = diisopropyl ether ETBE = ethyl tert butyl ether ug/L = micrograms per liter bold = above laboratory reporting limits

Table 2b

Additional Soil Analytical Results - August 2010

76 Service Station No. 1156 4276 MacArthur Boulevard Oakland, California

Boring	Depth	Date	TPHIn	TPHag	TPHss	TPHhn	TPHg (8260B)	TPHjf4	TPHjf5	TPHjf8	TPHk	TPHfo	TPHco	TPHwd40	TOG
	(ft)		mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg
SB-13	6	6/18/10	<200	<200	<100	<50	<100	<20	<20	<20	<20	<20	<100	<20	140
SB-18	15	6/14/10	<20	<20	<10	<5	<10	<20	<20	<20	<20	<20	<10	<20	<50
MW-4B	10	8/13/10													<50

TPHIn = total petroleum hydrocarbons as light naptha TPHag = TPH as aviation gas TPHss = TPH as stoddard solvent TPHhn = TPH as heavy naptha TPHg = TPH as gasoline TPHjf4 = TPH as JP4 jet fuel TPHjf5 = TPH as JP5 jet fuel TPHjf8 = TPH as JP5 jet fuel TPHjf8 = TPH as JP6 jet fuel TPHk = TPH as kerosene TPHf0 = TPH as fuel oil TPHc0 = TPH as crude oil TPHwd40 = TPH as WD-40 TOG = total oil and grease

Table 3
Historical Groundwater Monitoring Data and Analytical Results
76 Service Station #1156 (Chevron Site #351645)
4276 MacArthur Boulevard
Oakland, California

WELL ID	DATE SAMPLED	TOC*	DTW (ft)	LNAPL THICKNESS	GWE*	TOTAL OIL AND GREASE	TPH-d (µg/L)	TPH-g 8015	TPH-g (GC/MS)	Β (μg/L)	Τ (μg/L)	E (µg/L)	Χ (μg/L)	Comments
MW-1	7/20/1999	<u>π)</u> 174.86	7.50	(ft) 0	<u>π)</u> 167.36	(μg/L) 	(μg/L) 16,000	(μ g/L) 120,000	(µg/L) 	(μg/L) 11,000	(μg/L) 27,000	3,300	(μ g/L) 18,000	
141 4 4 - 1	9/28/1999	174.86	8.75	0	166.11		2,410	6,020		1,030	1,040	68.5	412	
	1/7/2000	174.86	9.05	0.02	165.82		7,870	72,700		7,410	13,900	2,070	9,620	GWE corrected
	3/31/2000	174.86	7.18	0	167.68		3,600	92,000		10,000	23,000	3,200	14,000	GVVE CONTECTED
	7/14/2000	174.86	7.68	0	167.18		8,580	108,000		8,250	18,700	3,750	17,800	
	10/3/2000	174.86	7.99	0	166.87		9,260	96,000		8,760	20,000	3,350	15,600	
	1/3/2001	174.86	9.18	0	165.68		11,000	37,000		5,800	13,000	1,700	8,100	
	4/4/2001	174.86	8.05	0	166.81		14,000	86,900		7,780	18,500	2,470	11,800	
	7/17/2001	174.86	7.01	0	167.85		2,200	79,000		5,600	11,000	2,800	12,000	
	10/3/2001	177.54	7.89	0	169.65			99,000		8,200	18,000	3,000	16,000	
	10/5/2001	177.54	7.91	0	169.63		13,000							
	1/28/2002	177.54	5.98	0	171.56		4,400	110,000		8,900	19,000	2,600	12,000	
	4/25/2002	177.54	6.19	0	171.35		9,000	93,000		8,100	18,000	3,000	15,000	
	7/18/2002	177.54	6.99	0	170.55		9,200	69,000		5,400	10,000	2,100	10,000	
	10/7/2002	177.54	7.73	0	169.81		3,400	82,000		9,200	20,000	2,600	13,000	
	1/6/2003	177.54	5.48	0	172.06		5,100	82,000		6,500	18,000	2,700	11,000	
	4/7/2003	177.54	6.30	0	171.24		2,800	74,000		7,000	15,000	2,400	11,000	
	7/7/2003	177.54	6.47	0	171.07		7,000	60,000		6,400	11,000	2,600	11,000	
	10/9/2003	177.54	7.85	0	169.69		4,300	91,000	81,000	8,100	17,000	3,200	14,000	Sampled for TPH-G by 8015M on 11/14/2003
	1/14/2004	177.54	6.69	0	170.85		6,200	98,000		8,000	21,000	2,600	15,000	Campica for 1111 C by Co Tolki Cit 111112000
	4/28/2004	177.54	6.43	0	171.11			93,000		9,000	20,000	1,300	10,000	
	7/12/2004	177.54	7.44	0	170.10		270	57,000		6,900	7,200	1,600	580	
	10/25/2004	177.54	7.54	0	170.00		5,100	66,000		7,300	19,000	2,700	14,000	
	1/17/2005	177.54	5.79	0	171.75		6,400	86,000		8,600	21,000	3,200	15,000	
	4/6/2005	177.54	4.93	0	172.61		2,800	85,000		8,400	20,000	3,200	16,000	
	7/8/2005	177.54	5.35	0	172.19		6,400	69,000		7,100	17,000	2,700	14,000	
	10/7/2005	177.54	5.96	0	171.58		5,500	68,000		5,900	8,300	1,800	8,300	
	1/27/2006	177.54	5.08	0	172.46		9,000	94,000		7,400	19,000	3,700	14,000	
	4/28/2006	177.54	4.85	0	172.69		9,200	74,000		6,400	13,000	2,300	10,000	
	7/28/2006	177.54	5.32	0	172.22		5,100	74,000		6,600	12,000	3,100	13,000	
	10/27/2006	177.54	6.13	0	171.41		4,600	100,000		8,300	20,000	3,600	16,000	
	1/10/2007	177.54	5.47	0	172.07		12,000	84,000		7,100	15,000	2,600	13,000	
	4/13/2007	177.54	5.60	0	171.94		8,400	27,000		5,600	840	2,300	3,200	
	7/19/2007	177.54	5.69	0	171.85		10,000	83,000		6,000	15,000	2,600	13,000	
	10/8/2007	177.54												Gate locked; no key available
	1/9/2008	177.54	5.15	0	172.39		12,000	40,000		6,000	4,800	2,600	5,100	Gauged on 1/18/2008
	4/4/2008	177.54	5.25	0	172.29		15,000	71,000		6,800	12,000	3,300	13,000	3
	7/3/2008	177.54	6.00	0	171.54		9,300	92,000		7,000	16,000	3,500	15,000	,000 ,000
	10/3/2008	177.54	7.16	0	170.38		4,400	69,000		7,200	18,000	3,500	14,000	
	1/22/2009	177.54	6.61	0	170.93		8,000	45,000		410	720	2,400	9,600	
	4/13/2009	177.54	5.11	0	172.43		4,800	5,400		300	640	300	940	
	7/23/2009	177.54	6.04	0	171.50		2,800	85,000		5,800	15,000	3,500	13,000	
	2/1/2010	177.54	4.86	0	172.68	ND<5,000	3,900	74,000		7,000	11,000	3,100	10,000	
	8/2/2010	177.54	5.68	0	171.86	ND<5,000	3,900	71,000		7,000	11,000	3,300		
	8/24/2010			-		,0		NDONED		.,	,	-,	,	

Table 3
Historical Groundwater Monitoring Data and Analytical Results
76 Service Station #1156 (Chevron Site #351645)
4276 MacArthur Boulevard
Oakland, California

WELL ID	DATE SAMPLED	TOC* (ft)	DTW (ft)	LNAPL THICKNESS (ft)	GWE*	TOTAL OIL AND GREASE (µg/L)	TPH-d (µg/L)	TPH-g 8015 (µg/L)	TPH-g (GC/MS) (μg/L)	B (µg/L)	Τ (μg/L)	E (μg/L)	Χ (μg/L)	Comments
MW-1B	11/1/2010	174.05	7.15	0	166.90	ND<5,000	ND<50	99		3.0	0.30	ND<0.30	ND<0.60	
	1/31/2011	174.05	6.62	0	167.43	ND<5,000	ND<50	170		6.7	0.64	0.33	ND<0.60	
	4/26/2011	174.05	6.14	0	167.91	ND<5,000	ND<50	220		7.3	0.55	0.32	0.69	
	7/25/2011	174.05	6.69	0	167.36	ND<5,000	ND<40	140		7.8	0.35	ND<0.30	ND<0.60	
	10/7/2011	174.06	6.86	0	167.20	ND<5,000	ND<40	120		5.7	ND<0.30	ND<0.30	ND<0.60	
	1/23/2012	174.06	6.96	0	167.10	ND<5,000	ND<40	89		3.6	ND<0.30	ND<0.30	ND<0.60	
	4/6/2012	174.06	5.89	0	168.17	ND<5,000	ND<40	110		4.5	ND<0.30	ND<0.30	ND<0.60	
	7/24/2012	174.06	6.98	0	167.08	ND<5,000	ND<40	130		6.2	ND<0.30	ND<0.30	ND<0.60	
MW-2	7/20/1999	173.01	5.40		167.61			ND		ND	ND	ND	ND	
	9/28/1999	173.01	5.60	0	167.41			1,390		124	ND	62.9	43.1	
	1/7/2000	173.01	5.92	0	167.09			1,450		99	ND	23.8	16	
	3/31/2000	173.01	5.23	0	167.78			ND		42	ND	ND	ND	
	7/14/2000	173.01	5.52	0	167.49			ND		44.7	ND	ND	ND	
	10/3/2000	173.01	6.04	0	166.97			ND		56.7	ND	ND	ND	
	1/3/2001	173.01	6.42	0	166.59			ND		ND	ND	ND	ND	
	4/4/2001	173.01	6.14	0	166.87			ND		ND	ND	ND	ND	
	7/17/2001	173.01	5.30	0	167.71			ND		ND	ND	ND	ND	
	10/3/2001	173.50	7.38	0	166.12			ND<250		2.7	ND<2.5	ND<2.5	ND<2.5	
	1/28/2002	173.50	5.68	0	167.82			ND<250		2.5	4.4	2.8	7.4	
	4/25/2002	173.50	5.82	0	167.68			ND<50		ND<0.50	ND<0.50	ND<0.50	ND<0.50	
	7/18/2002	173.50	6.90	0	166.60			ND<500		ND<5.0	ND<5.0	ND<5.0	ND<5.0	
	10/7/2002	173.50	7.54	0	165.96			4,300		ND<10	27	21	75	
	1/6/2003	173.50	6.79	0	166.71			5,900		ND<5.0	ND<5.0	ND<5.0	ND<5.0	
	4/7/2003	173.50	6.49	0	167.01			1,500		ND<10	14	11	38	
	7/7/2003	173.50	6.72	0	166.78			ND<2,500		ND<25	ND<25	ND<25	ND<25	
	10/9/2003	173.50	7.16	0	166.34			3,500	ND<5,000	ND<50	ND<50	ND<50	ND<100	Sampled for TPH-G by 8015M on 11/14/2003
	1/14/2004	173.50	5.53	0	167.97			3,200		ND<25	ND<25	ND<25	ND<25	
	4/28/2004	173.50	5.21	0	168.29			22,000		ND<3	9.2	ND<3	ND<6	
	7/12/2004	173.50	5.83	0	167.67			1,700		3.8	18	2.6	16	
	10/25/2004	173.50	6.89	0	166.61			3,400		ND<25	ND<25	ND<25	ND<25	
	1/17/2005	173.50	5.70	0	167.80			1,700		ND<10	ND<10	ND<10	ND<10	
	4/6/2005	173.50	4.50	0	169.00			3,000		ND<20	ND<20	ND<20	ND<20	
	7/8/2005	173.50	4.69	0	168.81			ND<2,000		ND<20	ND<20	ND<20	ND<20	
	10/7/2005	173.50	4.61	0	168.89			7,500		6.7	6.6	ND<3.0	ND<6.0	
	1/27/2006	173.50	4.10	0	169.40			2,500		1.0	2.6	ND<0.30	ND<0.60	
	4/28/2006	173.50	3.75	0	169.75			3,100		9.4	3.6	0.94	3.4	
	7/28/2006	173.50	4.34	0	169.16			3,000		2.0	ND<1.5	ND<1.5	ND<3.0	
	10/27/2006	173.50	5.62	0	167.88			1,800		1.5	ND<1.5	ND<1.5	ND<3.0	
	1/10/2007	173.50	4.02	0	169.48			2,100		1.1	ND<0.60	ND<0.60	ND<1.2	
	4/13/2007	173.50	4.03	0	169.47			3,300		12	1.6	0.46	1.1	
	7/19/2007	173.50	4.41	0	169.09			2,500		21	0.64	5.1	1.5	
	10/8/2007	173.50	4.93	0	168.57			3,400		38	1.6	13	2.1	
	1/9/2008	173.50	3.03	0	170.47			1,700		6.2	2.5	0.61	0.91	Gauged on 1/18/2008
	4/4/2008	173.50	3.52	0	169.98			1,400		15	2.1	0.76	ND<0.60	55555 OH 1/10/2000
	7/3/2008	173.50	4.70	0	168.80			1,100		14	1.1	2.0	1.2	

Table 3
Historical Groundwater Monitoring Data and Analytical Results
76 Service Station #1156 (Chevron Site #351645)
4276 MacArthur Boulevard
Oakland, California

WELL ID	DATE SAMPLED	TOC* (ft)	DTW (ft)	LNAPL THICKNESS (ft)	GWE*	TOTAL OIL AND GREASE (µg/L)	TPH-d (µg/L)	TPH-g 8015 (μg/L)	TPH-g (GC/MS) (µg/L)	B (µg/L)	Τ (μg/L)	E (µg/L)	Χ (μg/L)	Comments
MW-2 cont.	10/3/2008	173.50	5.57	0	167.93		ND<50	740		14	ND<0.30	4.5	6.9	
	1/22/2009	173.50	5.03	0	168.47		ND<50	640		4.6	ND<0.30	ND<0.30	ND<0.60	
	4/13/2009	173.50	3.73	0	169.77		ND<50	940		7.1	ND<0.30	ND<0.30	ND<0.60	
	7/23/2009	173.50	4.39	0	169.11		230	700		12	6.0	5.4	13	
	2/1/2010	173.50	4.33	0	169.17		140	860		17	13	0.83	2.4	
	8/2/2010	173.50	5.16	0	168.34		210	1,200		9.5	32	1.4	2.4	
	8/24/2010						ABA	NDONED						
MW-2B	11/1/2010	173.55	11.27	0	162.28		57	550		7.8	2.7	2.1	0.99	
	1/31/2011	173.55	7.79	0	165.76		ND<50	420		1.7	0.47	0.59	ND<0.60	
	4/26/2011	173.55	9.09	0	164.46		ND<50	390		ND<0.30	ND<0.30	ND<0.30	ND<0.60	
	7/25/2011	173.55	3.91	0	169.64		ND<40	210		1.7	ND<0.30	ND<0.30	ND<0.60	
	10/7/2011	173.55	4.50	0	169.05		52	110		1.0	ND<0.30	ND<0.30	ND<0.60	
	1/23/2012	173.55	6.96	0	166.59		ND<40	110		0.73	ND<0.30	ND<0.30	ND<0.60	
	4/6/2012	173.55	5.67	0	167.88		ND<40	120		0.36	ND<0.30	ND<0.30	ND<0.60	
	7/24/2012	173.55	5.33	0	168.22		ND<40	73		ND<0.30	ND<0.30	ND<0.30	ND<0.60	
MW-3	7/20/1999	178.44	8.50		169.94			1,000		76	52	79	76	
	9/28/1999	178.44	8.31	0	170.13			1,860		174	95.4	71.8	135	
	1/7/2000	178.44	8.56	0	169.88			28,400		2,450	3,090	1,560	3,910	
	3/31/2000	178.44	8.42	0	170.02			26,000		1,300	2,900	2,600	3,500	
	7/14/2000	178.44	8.61	0	169.83			24,500		1,850	2,630	2,750	3,900	
	10/3/2000	178.44	9.14	0	169.30			22,000		1,910	2,020	2,400	2,680	
	1/3/2001	178.44	9.06	0	169.38			14,000		1,600	1,100	2,300	1,400	
	4/4/2001	178.44	8.98	0	169.46			19,600		1,150	1,470	2,100	1,820	
	7/17/2001	178.44	7.46	0	170.98			26,000		1,500	2,100	2,100	3,400	
	10/3/2001	178.13	9.81	0	168.32			22,000		830	1,900	1,700	3,000	
	1/28/2002	178.13	7.39	0	170.74			30,000		880	2,600	1,800	4,300	
	4/25/2002	178.13	7.86	0	170.27			18,000		500	2,000	1,300	3,800	
	7/18/2002	178.13	8.83	0	169.30			37,000		1,800	3,800	2,200	8,000	
	10/7/2002	178.13	9.71	0	168.42			26,000		600	2,000	1,800	6,400	
	1/6/2003	178.13	7.40	0	170.73			27,000		800	2,100	2,000	6,400	
	4/7/2003	178.13	8.17	0	169.96			28,000		660	2,200	1,900	6,300	
	7/7/2003	178.13	8.35	0	169.78			33,000		1,200	2,500	2,700	8,300	
	10/9/2003	178.13	9.39	0	168.74			3,800	6,000	120	260	390	1,200	Sampled for TPH-G by 8015M on 11/14/2003
	1/14/2004	178.13	6.86	0	171.27			5,100		120	240	310	720	
	4/28/2004	178.13	6.63	0	171.50			7,300		250	440	580	1300	
	7/12/2004	178.13	7.41	0	170.72			5,500		350	310	120	350	
	10/25/2004	178.13	8.81	0	169.32			3,300		96	140	270	490	
	1/17/2005	178.13	6.37	0	171.76			3,400		150	270	360	750	
	4/6/2005	178.13	4.69	0	173.44			14,000		420	1,300	1,000	3,100	
	7/8/2005	178.13	5.23	0	172.90			5,000		180	290	500	800	
	10/7/2005	178.13	6.35	0	171.78			6,800		270	120	ND<0.30	210	
	1/27/2006	178.13	5.24	0	172.89			3,200		120	140	270	460	
	4/28/2006	178.13	5.01	0	173.12			4,500		130	250	380	670	
	7/28/2006	178.13	6.21	0	171.92			4,700		160	240	510	730	

Table 3
Historical Groundwater Monitoring Data and Analytical Results
76 Service Station #1156 (Chevron Site #351645)
4276 MacArthur Boulevard
Oakland, California

WELL ID	DATE SAMPLED	TOC*	DTW (ft)	LNAPL THICKNESS (ft)	GWE*	TOTAL OIL AND GREASE (µg/L)	TPH-d (µg/L)	TPH-g 8015 (μg/L)	TPH-g (GC/MS) (μg/L)	Β (μg/L)	T (µg/L)	E (µg/L)	Χ (μg/L)	Comments
MW-3 cont.	10/27/2006	178.13	6.93	0	171.20	(µg, _,	(Pg/L)	3,700	(Pg/L)	150	160	460	530	
	1/10/2007	178.13	5.93	0	172.20			4,800		180	160	550	600	
	4/13/2007	178.13	6.10	0	172.03			5,100		180	240	550	710	
	7/19/2007	178.13	6.51	0	171.62			2,000		110	64	220	190	
	10/8/2007	178.13	7.05	0	171.08			2,100		72	65	180	290	
	1/9/2008	178.13	3.65	0	174.48			4,200		200	160	510	580	Gauged on 1/18/2008
	4/4/2008	178.13	5.69	0	172.44			7,500		270	390	810	1,200	
	7/3/2008	178.13	7.28	0	170.85			2,300		99	66	210	220	
	10/3/2008	178.13	8.40	0	169.73		1,200	12,000		740	620	1,500	2,700	
	1/22/2009	178.13	7.68	0	170.45		270	2,000		120	79	290	290	
	4/13/2009	178.13	6.28	0	171.85		150	3,600		110	150	180	510	
	7/23/2009	178.13	7.20	0	170.93		310	3,400		180	150	360	650	
	2/1/2010	178.13	5.29	0	172.84		390	6,500		180	92	300	250	
	8/2/2010	178.13	6.83	0	171.30		540	8,600		140	110	320	1,000	
	8/24/2010						ABA	NDONED						
MW-3B	11/1/2010	177.77	6.82	0	170.95		58	990		31	32	47	50	
	1/31/2011	177.77	5.30	0	172.47		65	2,800		32	20	39	47	
	4/26/2011	177.77	4.64	0	173.13		93	2,800		36	55	80	82	
	7/25/2011	177.77	5.53	0	172.24		100	1,700		28	33	80	73	
	10/7/2011	177.77	6.08	0	171.69		81	1,700		32	20	88	47	
	1/23/2012	177.77	6.90	0	170.87		120	1,800		39	17	75	20	
	4/6/2012	177.77	4.23	0	173.54		ND<40	1,200		36	25	80	41	
	7/24/2012	177.77	6.42	0	171.35		190	1,500	-	66	10	76	39	
MW-4	7/20/1999	179.10	7.40		171.70			69		2.7	0.77	ND	7.1	
	9/28/1999	179.10	7.19	0	171.91			4,050		1,250	72	51.3	133	
	1/7/2000	179.10	8.98	0	170.12			7,010		2,260	167	271	276	
	3/31/2000	179.10	7.26	0	171.84			5,500		1,800	230	330	400	
	7/14/2000	179.10	7.67	0	171.43			7,940		2,810	332	450	247	
	10/3/2000	179.10	8.12	0	170.98			11,400		3,110	437	519	816	
	1/3/2001	179.10	9.10	0	170.00			8,600		2,500	340	480	960	
	4/4/2001	179.10	8.63	0	170.47			9,950		2,380	126	416	725	
	7/17/2001	179.10	6.49	0	172.61			10,000		2,300	110	410	800	
	10/3/2001	178.96	7.01	0	171.95			7,800		2,100	85	380	390	
	1/28/2002	178.96	6.21	0	172.75			12,000		2,100	130	350	670	
	4/25/2002	178.96	5.49	0	173.47			3,300		1,300	42	270	250	
	7/18/2002	178.96	8.28	0	170.68			4,800		1,300	71	290	220	
	10/7/2002	178.96	7.49	0	171.47			5,100		1,400	110	330	380	
	1/6/2003	178.96	6.36	0	172.60			5,600		1,100	57	260	320	
	4/7/2003	178.96	6.24	0	172.72			5,100		1,100	55	190	370	
	7/7/2003	178.96	6.43	0	172.53			3,000		920	28	170	330	
	10/9/2003	178.96	7.97	0	170.99			530	700	100	2.2	5.4	14	Sampled for TPH-G by 8015M on 11/14/2003
	1/14/2004	178.96	6.30	0	172.66			530		88	4.1	9.9	11	
	4/28/2004	178.96	5.68	0	173.28			1,200		200	5.3	21	13	
	7/12/2004	178.96	6.48	0	172.48			3,600		1,000	14	260	72	

Table 3
Historical Groundwater Monitoring Data and Analytical Results
76 Service Station #1156 (Chevron Site #351645)
4276 MacArthur Boulevard
Oakland, California

WELL ID	DATE SAMPLED	TOC* (ft)	DTW (ft)	LNAPL THICKNESS (ft)	GWE*	TOTAL OIL AND GREASE (µg/L)	TPH-d (µg/L)	TPH-g 8015 (μg/L)	TPH-g (GC/MS) (μg/L)	B (µg/L)	Τ (μg/L)	E (µg/L)	Χ (μg/L)	Comments
MW-4 cont.	10/25/2004	178.96	6.85	0	172.11			490		34	ND<2.5	ND<2.5	ND<2.5	
	1/17/2005	178.96	4.56	0	174.40			620		100	2.6	15	8.0	
	4/6/2005	178.96	2.90	0	176.06			630		81	9.6	16	41	
	7/8/2005	178.96	3.74	0	175.22			980		170	24	44	140	
	10/7/2005	178.96	4.24	0	174.72			4,900		1,100	11	110	110	
	1/27/2006	178.96	3.65	0	175.31			2,800		580	20	130	230	
	4/28/2006	178.96	3.94	0	175.02			710		110	2.4	21	22	
	7/28/2006	178.96	4.63	0	174.33			550		120	2.1	12	19	
	10/27/2006	178.96	5.19	0	173.77			260		37	2.0	1.9	6.7	
	1/10/2007	178.96	4.82	0	174.14			270		29	0.72	1.8	2.7	
	4/13/2007	178.96	4.25	0	174.71			390		53	1.2	3.1	4.1	
	7/19/2007	178.96	5.35	0	173.61			210		8.0	1.0	1.4	4.5	
	10/8/2007	178.96	5.48	0	173.48			290		17	2.3	3.8	14	
	1/9/2008	178.96	3.40	0	175.56			770		190	5.9	21	40	Gauged on 1/18/2008
	4/4/2008	178.96	4.20	0	174.76			180		11	2.0	0.67	2.9	
	7/3/2008	178.96	5.89	0	173.07			140		4.5	1.3	ND<0.30	ND<0.60	
	10/3/2008	178.96	7.34	0	171.62		96	430		29	3.4	9.6	20	
	1/22/2009	178.96	6.75	0	172.21		ND<50	190		25	1.7	0.87	1.5	
	4/13/2009	178.96	4.74	0	174.22		110	290		17	2.1	4.4	12	
	7/23/2009	178.96	6.01	0	174.22		85	360		33	2.3	5.4	18	
	2/1/2010	178.96	6.42	0	172.53		80	490		35	3.1	2.7	5.5	
	8/2/2010	178.96	5.92	0	173.04		120	470		17	3.4	2.5	12	
	8/24/2010	170.50	5.92	Ü	173.04			NDONED		17	5.4	2.5	12	
MW-4B	11/1/2010	179.07	7.20	0	171.87		ND<50	230		ND<0.30	2.1	1.3	43	
	1/31/2011	179.07	4.49	0	174.58		ND<50	68		ND<0.30	ND<0.30	ND<0.30	2.0	
	4/26/2011	179.07	4.32	0	174.75		ND<50	52		ND<0.30	ND<0.30	ND<0.30	ND<0.60	
	7/25/2011	179.07	5.52	0	173.55		ND<40	ND<50		ND<0.30	ND<0.30	ND<0.30	ND<0.60	
	10/7/2011	179.07	6.04	0	173.03		ND<40	ND<50		ND<0.30	0.46	ND<0.30	ND<0.60	
	1/23/2012	179.07	6.58	0	172.49		ND<40	ND<50		ND<0.30	0.36	0.87	ND<0.60	
	4/6/2012	179.07	4.41	0	174.66		ND<40	ND<50		ND<0.30	ND<0.30	ND<0.30	ND<0.60	
	7/24/2012	179.07	6.20	0	172.87		ND<40	75		ND<0.30	ND<0.30	ND<0.30	ND<0.60	
MW-5	10/3/2001	169.18	2.81	0	166.37			ND<50		ND<0.50	ND<0.50	ND<0.50	ND<0.50	
	1/28/2002	169.18	1.88	0	167.30			ND<50		ND<0.50	ND<0.50	ND<0.50	ND<0.50	
	4/25/2002	169.18	1.99	0	167.19			ND<50		ND<0.50	ND<0.50	ND<0.50	ND<0.50	
	7/18/2002	169.18	2.49	0	166.69			ND<50		ND<0.50	ND<0.50	ND<0.50	ND<0.50	
	10/7/2002	169.18	2.80	0	166.38			140		ND<0.50	ND<0.50	ND<0.50	ND<0.50	
	1/6/2003	169.18	1.86	0	167.32		ND<50	120		ND<0.50	ND<0.50	ND<0.50	ND<0.50	
	4/7/2003	169.18	2.15	0	167.03			220		0.53	ND<0.50	ND<0.50	ND<0.50	
	7/7/2003	169.18	2.26	0	166.92			120		ND<1.2	ND<1.2	ND<1.2	ND<1.2	
	10/9/2003	169.18	2.72	0	166.46			560	210	ND<1.0	ND<1.0	ND<1.0	ND<2.0	Sampled for TPH-G by 8015M on 11/14/2003
	1/14/2004	169.18	2.00	0	167.18			560		ND<2.5	ND<2.5	ND<2.5	ND<2.5	,
	4/28/2004	169.18	2.01	0	167.17			760		ND<0.3	1.8	ND<0.3	ND<0.6	
	7/12/2004	169.18	2.56	0	166.62			96		1.8	3.3	0.54	3.6	

Table 3
Historical Groundwater Monitoring Data and Analytical Results
76 Service Station #1156 (Chevron Site #351645)
4276 MacArthur Boulevard
Oakland, California

WELL ID	DATE SAMPLED	TOC* (ft)	DTW (ft)	LNAPL THICKNESS (ft)	GWE*	TOTAL OIL AND GREASE (µg/L)	TPH-d (µg/L)	TPH-g 8015 (μg/L)	TPH-g (GC/MS) (μg/L)	B (µg/L)	Τ (μg/L)	E (µg/L)	Χ (μg/L)	Comments
MW-5 cont.	1/17/2005	169.18	1.49	0	167.69			720		ND<5.0	ND<5.0	ND<5.0	ND<5.0	
	4/6/2005	169.18	0.95	0	168.23			830		ND<5.0	ND<5.0	ND<5.0	ND<5.0	
	7/8/2005	169.18	1.49	0	167.69			ND<500		ND<5.0	ND<5.0	ND<5.0	ND<5.0	
	10/7/2005	169.18	1.92	0	167.26			540		ND<0.30	ND<0.30	ND<0.30	ND<0.60	
	1/27/2006	169.18	2.03	0	167.15			490		ND<0.30	ND<0.30	ND<0.30	ND<0.60	
	4/28/2006	169.18	1.02	0	168.16			430		ND<0.30	ND<0.30	ND<0.30	ND<0.60	
	7/28/2006	169.18	1.57	0	167.61			480		0.34	ND<0.30	ND<0.30	ND<0.60	
	10/27/2006	169.18	2.20	0	166.98			420		0.34	ND<0.30	ND<0.30	ND<0.60	
	1/10/2007	169.18	1.57	0	167.61			390		ND<0.30	ND<0.30	ND<0.30	ND<0.60	
	4/13/2007	169.18	1.89	0	167.29			170		3.8	5.9	1.5	3.8	
	7/19/2007	169.18	1.92	0	167.26			ND<50		ND<0.30	ND<0.30	ND<0.30	ND<0.60	
	10/8/2007	169.18	2.28	0	166.90			200		ND<0.30	ND<0.30	ND<0.30	ND<0.60	
	1/9/2008	169.18	1.09	0	168.09			150		ND<0.30	ND<0.30	ND<0.30	ND<0.60	Gauged on 1/18/2008
	4/4/2008	169.18	1.72	0	167.46			210		ND<0.30	ND<0.30	ND<0.30	ND<0.60	
	7/3/2008	169.18	2.27	0	166.91			260		ND<0.30	ND<0.30	ND<0.30	ND<0.60	
	10/3/2008	169.18	2.80	0	166.38		60	200		ND<0.30	ND<0.30	ND<0.30	ND<0.60	
	1/22/2009	169.18	2.45	0	166.73		ND<50	130		ND<0.30	ND<0.30	ND<0.30	ND<0.60	
	4/13/2009	169.18	1.81	0	167.37		ND<50	190		ND<0.30	ND<0.30	ND<0.30	ND<0.60	
	7/23/2009	169.18	2.33	0	166.85		ND<50	210		ND<0.30	ND<0.30	ND<0.30	ND<0.60	
	2/1/2010	169.18	1.32	0	167.86		ND<50	170		ND<0.30	ND<0.30	ND<0.30	ND<0.60	
	8/2/2010	169.18	2.20	0	166.98		ND<50	64		ND<0.30	ND<0.30	ND<0.30	ND<0.60	
	11/1/2010	169.18	3.92	0	165.26									Sampled Q1 and Q3 only
	1/31/2011	169.18	1.63	0	167.55		ND<50	160		ND<0.30	ND<0.30	ND<0.30	ND<0.60	
	4/26/2011	169.18	1.32	0	167.86									Sampled Q1 and Q3 only
	7/25/2011	169.18	1.79	0	167.39		ND<40	140		ND<0.30	ND<0.30	ND<0.30	ND<0.60	
	10/7/2011	169.18	2.18	0	167.00									Sampled Q1 and Q3 only
	1/23/2012	169.18	1.98	0	167.20		ND<40	ND<50		ND<0.30	ND<0.30	ND<0.30	ND<0.60	
	4/6/2012	169.18	1.18	0	168.00									Sampled Q1 and Q3 only
	7/24/2012	169.18	1.90	0	167.28		ND<40	ND<50		ND<0.30	ND<0.30	ND<0.30	ND<0.60	
MW-6	10/3/2001	169.04	2.87	0	166.17			ND<50		ND<0.50	ND<0.50	ND<0.50	ND<0.50	
	1/28/2002	169.04	1.82	0	167.22			ND<50		ND<0.50	ND<0.50	ND<0.50	ND<0.50	
	4/25/2002	169.04	2.01	0	167.03			ND<50		ND<0.50	ND<0.50	ND<0.50	ND<0.50	
	7/18/2002	169.04	2.44	0	166.60			ND<50		ND<0.50	ND<0.50	ND<0.50	ND<0.50	
	10/7/2002	169.04	2.72	0	166.32			ND<50		ND<0.50	ND<0.50	ND<0.50	ND<0.50	
	1/6/2003	169.04	1.90	0	167.14			ND<50		0.62	1.2	1.2	3.5	
	4/7/2003	169.04	2.02	0	167.02			ND<50		ND<0.50	ND<0.50	ND<0.50	ND<0.50	
	7/7/2003	169.04	2.21	0	166.83			ND<50		ND<0.50	ND<0.50	ND<0.50	ND<0.50	
	10/9/2003	169.04	2.71	0	166.33			ND<50	ND<50	0.95	3.0	1.4	5.5	Sampled for TPH-G by 8015M on 11/14/2003
	1/14/2004	169.04	2.00	0	167.04			ND<50		ND<0.50	0.57	ND<0.50	0.64	
	4/28/2004	169.04	2.18	0	166.86			ND<50		0.39	0.78	ND<0.3	ND<0.6	
	7/12/2004	169.04	2.69	0	166.35			ND<50		ND<0.3	ND<0.3	ND<0.3	ND<0.6	
	10/25/2004	169.04	2.46	0	166.58			ND<50		ND<0.50	ND<0.50	ND<0.50	ND<0.50	
	1/17/2005	169.04	1.54	0	167.50			ND<50		ND<0.50	ND<0.50	ND<0.50	ND<0.50	
	4/6/2005	169.04	1.15	0	167.89			ND<50		ND<0.50	ND<0.50	ND<0.50	ND<0.50	
	7/8/2005	169.04	1.05	0	167.99			ND<50		ND<0.50	ND<0.50	ND<0.50	ND<0.50	

Table 3
Historical Groundwater Monitoring Data and Analytical Results
76 Service Station #1156 (Chevron Site #351645)
4276 MacArthur Boulevard
Oakland, California

WELL ID	DATE SAMPLED	TOC*	DTW	LNAPL THICKNESS	GWE*	TOTAL OIL AND GREASE	TPH-d	TDU 0045	TPH-g (GC/MS)	В	т	E	x	Comments
WELL ID	SAMPLED	(ft)	(ft)	(ft)	GWE^ (ft)	GREASE (μg/L)	(µg/L)	TPH-g 8015 (μg/L)	(GC/MS) (µg/L)	Β (μg/L)	ι (μg/L)	Ε (μg/L)	χ (μg/L)	Comments
MW-6 cont.	10/7/2005	169.04	1.90	0	167.14	(Pg, L)	(Pg/L)	ND<50	(µg, _)	ND<0.30	ND<0.30	ND<0.30	ND<0.60	
	1/27/2006	169.04	1.32	0	167.72			ND<50		ND<0.30	ND<0.30	ND<0.30	ND<0.60	
	4/28/2006	169.04	0.00	0	169.04			ND<50		ND<0.30	ND<0.30	ND<0.30	ND<0.60	
	7/28/2006	169.04	1.68	0	167.36			ND<50		ND<0.30	ND<0.30	ND<0.30	ND<0.60	
	10/27/2006	169.04	1.98	0	167.06			ND<50		ND<0.30	ND<0.30	ND<0.30	ND<0.60	
	1/10/2007	169.04	1.60	0	167.44			ND<50		ND<0.30	ND<0.30	ND<0.30	ND<0.60	
	4/13/2007	169.04	2.01	0	167.03			ND<50		ND<0.30	ND<0.30	ND<0.30	ND<0.60	
	7/19/2007	169.04	1.96	0	167.08			ND<50		ND<0.30	ND<0.30	ND<0.30	ND<0.60	
	10/8/2007	169.04	2.35	0	166.69			ND<50		ND<0.30	ND<0.30	ND<0.30	ND<0.60	
	1/9/2008	169.04	1.10	0	167.94			ND<50		ND<0.30	ND<0.30	ND<0.30		Gauged on 1/18/2008
	4/4/2008	169.04	1.60	0	167.44			ND<50		ND<0.30	0.40	ND<0.30	0.71	•
	7/3/2008	169.04	2.19	0	166.85			ND<50		ND<0.30	ND<0.30	ND<0.30	ND<0.60	
	10/3/2008	169.04	2.78	0	166.26		ND<50	ND<50		ND<0.30	ND<0.30	ND<0.30	ND<0.60	
	1/22/2009	169.04	2.35	0	166.69		ND<50	ND<50		ND<0.30	ND<0.30	ND<0.30	ND<0.60	
	4/13/2009	169.04	1.81	0	167.23		ND<50	ND<50		ND<0.30	ND<0.30	ND<0.30	ND<0.60	
	7/23/2009	169.04												Paved over
	2/1/2010	169.04												Paved over
	8/2/2010	169.04												Paved over
	8/24/2010						ABA	NDONED						
MW-7	10/3/2001	171.64	7.62	0	164.02			10,000		210	ND<50	ND<50	800	
	1/28/2002	171.64	7.21	0	164.43			ND<1,000		ND<10	ND<10	ND<10	ND<10	
	4/25/2002	171.64	7.25	0	164.39			ND<5,000		660	ND<50	ND<50	ND<50	
	7/18/2002	171.64	8.12	0	163.52			ND<5,000		130	ND<50	ND<50	ND<50	
	10/7/2002	171.64	7.71	0	163.93			18,000		ND<50	ND<50	ND<50	ND<50	
	1/6/2003	171.64	7.63	0	164.01		ND<50	410		0.61	1.0	0.89	2.9	
	4/7/2003	171.64	7.58	0	164.06			13,000		ND<20	ND<20	ND<20	ND<20	
	7/7/2003	171.64	7.56	0	164.08			990		8.2	ND<0.50	1.2	ND<0.50	
	10/9/2003	171.64	7.72	0	163.92			6,800	ND<13,000	ND<130	ND<130	ND<130	ND<250	Sampled for TPH-G by 8015M on 11/14/2003
	1/14/2004	171.64	6.97	0	164.67			19,000		ND<100	ND<100	ND<100	ND<100	,
	4/28/2004	171.64	8.70	0	162.94			19,000		ND<3	ND<3	ND<3	ND<6	
	7/12/2004	171.64	9.44	0	162.20			12,000		28	14	330	200	
	10/25/2004	171.64	7.23	0	164.41			28,000		ND<250	ND<250	ND<250	ND<250	
	1/17/2005	171.64	6.30	0	165.34			15,000		ND<100	ND<100	ND<100	ND<100	
	4/6/2005	171.64	5.96	0	165.68			13,000		ND<100	ND<100	ND<100	ND<100	
	7/8/2005	171.64	6.45	0	165.19			ND<10,000		ND<100	ND<100	ND<100	ND<100	
	10/7/2005	171.64	6.78	0	164.86			13,000		ND<3.0	ND<3.0	ND<3.0	ND<6.0	
	1/27/2006	171.64	5.82	0	165.82			8,200		0.64	1.6	ND<0.30	ND<0.60	
	4/28/2006	171.64	5.57	0	166.07			6,900		0.88	1.5	0.34	1.0	
	7/28/2006	171.64	6.67	0	164.97			5,400		5.2	ND<3.0	ND<3.0	ND<6.0	
	10/27/2006	171.64	6.93	0	164.71			4,500		ND<1.5	ND<1.5	ND<1.5	ND<3.0	
	1/10/2007	171.64	6.41	0	165.23		12,000	4,000		ND<1.2	ND<1.2	ND<1.2	ND<2.4	
	4/13/2007	171.64												Paved over
	7/19/2007	171.64	7.10	0	164.54			2,700		0.57	ND<0.30	ND<0.30	ND<0.60	
	10/8/2007	171.64	7.42	0	164.22			1,600		0.47	0.49	ND<0.30	ND<0.60	
	1/9/2008	171.64	5.98	0	165.66			1,500		0.45	0.49	ND<0.30		Gauged on 1/18/2008

Table 3
Historical Groundwater Monitoring Data and Analytical Results
76 Service Station #1156 (Chevron Site #351645)
4276 MacArthur Boulevard
Oakland, California

						TOTAL OIL								
	DATE			LNAPL		AND			TPH-g					
WELL ID	SAMPLED	TOC*	DTW	THICKNESS	GWE*	GREASE	TPH-d	TPH-g 8015	(GC/MS)	В	T	E	X	Comments
		(ft)	(ft)	(ft)	(ft)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	
MW-7 cont.	4/4/2008	171.64	6.80	0	164.84			1,800		0.72	0.58	ND<0.30	ND<0.60	
	7/3/2008	171.64	7.31	0	164.33			1,600		0.45	ND<0.30	ND<0.30	ND<0.60	
	10/3/2008	171.64	7.79	0	163.85		ND<50	1,300		0.53	0.59	ND<0.30	ND<0.60	
	1/22/2009	171.64	7.26	0	164.38		ND<50	890		0.43	0.49	ND<0.30	ND<0.60	
	4/13/2009	171.64	6.83	0	164.81		ND<50	1,100		0.46	0.30	ND<0.30	ND<0.60	
	7/23/2009	171.64	7.32	0	164.32		ND<50	920		ND<0.30	0.73	ND<0.30	ND<0.60	
	2/1/2010	171.64	6.21	0	165.43		53	1,000		5.6	4.0	1.2	2.0	
	8/2/2010	171.64	7.08	0	164.56		ND<50	880		ND<0.30	0.62	ND<0.30	ND<0.60	
	11/1/2010	172.11	6.97	0	165.14									Sampled Q1 and Q3 only
	1/31/2011	172.11	6.58	0	165.53		ND<50	730		0.31	0.59	ND<0.30	ND<0.60	
	4/26/2011	172.11	5.21	0	166.90									Sampled Q1 and Q3 only
	7/25/2011	172.11	6.89	0	165.22		ND<40	610		2.5	ND<0.30	ND<0.30	ND<0.60	
	10/7/2011	172.11	7.15	0	164.96									Sampled Q1 and Q3 only
	1/23/2012	172.11	6.92	0	165.19		ND<40	300		ND<0.30	0.55	ND<0.30	ND<0.60	
	4/6/2012	172.11	6.01	0	166.10									Sampled Q1 and Q3 only
	7/24/2012	172.11	7.25	0	164.86		ND<40	270	-	ND<0.30	ND<0.30	ND<0.30	ND<0.60	
MW-8	1/18/2008	167.97	0.43	0	167.54			ND<50		ND<0.30	ND<0.30	ND<0.30	ND<0.60	
	4/4/2008	167.97	0.55	0	167.42			ND<50		0.76	1.6	0.72	2.3	
	7/3/2008	167.97	0.91	0	167.06			ND<50		ND<0.30	ND<0.30	ND<0.30	ND<0.60	
	10/3/2008	167.97	1.71	0	166.26		ND<50	ND<50		ND<0.30	ND<0.30	ND<0.30	ND<0.60	
	1/22/2009	167.97	1.59	0	166.38		64	ND<50		ND<0.30	ND<0.30	ND<0.30	ND<0.60	
	4/13/2009	167.97	0.08	0	167.89		ND<50	ND<50		ND<0.30	ND<0.30	ND<0.30	ND<0.60	
	7/23/2009	167.97	1.10	0	166.87		ND<50	ND<50		ND<0.30	ND<0.30	ND<0.30	ND<0.60	
	2/1/2010	167.97	0.65	0	167.32		ND<50	ND<50		ND<0.30	ND<0.30	ND<0.30	ND<0.60	
	8/2/2010	167.97												Paved over
	8/24/2010						ABA	NDONED						

NOTES:

TOC = top of casing

DTW = depth to water

LNAPL = Liquid non-aqueous phase liquid

GWE = groundwater elevation

ND<# = Analyte not detected below indicated practical quantitation limit

-- = Not available/not sampled

μg/L = Micrograms per liter

GC/MS = Gas chromatograph/mass spectrometer

* TOC and GWE are in feet above mean sea level.

Oxygenate compounds analyzed by U.S. EPA Method 8260B

TPH-d = Total petroleum hydrocarbons as diesel

TPH-g = Total petroleum hydrocarbons as gasoline

B = Benzene

T = Toluene

E = Ethylbenzene

X = Xylenes

Table 4
Historical Groundwater Analytical Results - Oxygenate Compounds
76 Service Station #1156 (Chevron Site #351645)
4276 MacArthur Boulevard
Oakland, California

WELL ID	DATE	MTBE (8021B) (μg/L)	MTBE (8260B) (μg/L)	TBA (μg/L)	Ethanol (8260B) (µg/L)	Ethanol (8015B) (µg/L)	EDB (µg/L)	EDB (504) (μg/L)	EDC (μg/L)	DIPE (μg/L)	ETBE (µg/L)	TAME (μg/L)
MW-1	7/20/1999	ND										
	9/28/1999	321	333	ND						ND	ND	ND
	1/7/2000	ND										
	3/31/2000	ND										
	7/14/2000	ND										
	10/3/2000	ND										
	1/3/2001	2,200										
	4/4/2001	ND	481	ND		ND	ND		ND	ND	ND	ND
	7/17/2001	ND	230	ND		ND	ND		ND	ND	ND	ND
	10/3/2001	ND<2,500										
	10/5/2001											
	1/28/2002	3,000	440									
	4/25/2002	810	670									
	7/18/2002	ND<500	620	ND<100		ND<2,500,000	ND<10		ND<10	ND<10	ND<10	ND<10
	10/7/2002	1,300	760	ND<10,000		ND<50,000,000	ND<200		ND<200	ND<200	ND<200	ND<200
	1/6/2003	ND<1,000	790	ND<20,000		ND<100,000,000	ND<400		ND<400	ND<400	ND<400	ND<400
	4/7/2003	1,000	800	ND<10,000		ND<50,000,000	ND<200		ND<200	ND<200	ND<200	ND<200
	7/7/2003	600	530	ND<25,000	ND<120000		ND<500		ND<500	ND<500	ND<500	ND<500
	10/9/2003		660	ND<2,0000		ND<100,000	ND<400		ND<400	ND<400	ND<400	ND<400
	1/14/2004	ND<1,300	ND<800	ND<40,000		ND<200,000	ND<800		ND<800	ND<800	ND<800	ND<800
	4/28/2004	1,400	560	800		ND<1,000	ND<50		ND<50	ND<1	ND<1	ND<1
	7/12/2004	490	440	1,100		ND<20,000	ND<10		ND<10	ND<20	ND<20	ND<20
	10/25/2004	ND<1,300	330	ND<2,000		ND<20,000	ND<200		ND<200	ND<400	ND<200	ND<200
	1/17/2005	ND<1,300	570	3,100		ND<20,000	ND<200		ND<200	ND<400	ND<200	ND<200
	4/6/2005	ND<1,300	580	1,500		ND<10,000	ND<100		ND<100	ND<100	ND<100	ND<100
	7/8/2005	ND<1,300	290	ND<1,300		ND<13,000	ND<130		3.8	ND<130	ND<130	ND<130
	10/7/2005	330	250	680		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	1/27/2006	450	360	ND<500		ND<12,000	ND<25		ND<25	ND<25	ND<25	ND<25
	4/28/2006	460	280	ND<500		ND<12,000	ND<25		ND<25	ND<25	ND<25	ND<25
	7/28/2006	330	220	ND<10		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	10/27/2006	280	250	ND<2,500		ND<62,000	ND<120		ND<120	ND<120	ND<120	ND<120
	1/10/2007	350	260	ND<1,000		ND<25,000	ND<50		ND<50	ND<50	ND<50	ND<50
	4/13/2007	270	220	730		ND<250	ND<0.50		0.68	ND<0.50	ND<0.50	ND<0.5
	7/19/2007	1,000	200	ND<1,000		ND<25,000	ND<50		ND<50	ND<50	ND<50	ND<50
	10/8/2007											
	1/9/2008	840	170	ND<250		ND<6,200	ND<12		ND<12	ND<12	ND<12	ND<12
	4/4/2008		160	770		ND<5,200 ND<5,000	ND<12 ND<10		ND<12 ND<10	ND<12 ND<10	ND<12 ND<10	ND<12
W-1 cont.	7/3/2008		110	770 ND<250		ND<5,000 ND<6,200	ND<10 ND<12		ND<10 ND<12	ND<10	ND<10 ND<12	ND<10
W-1 COIIL.	10/3/2008			ND<200		*	ND<12 ND<10					ND<12 ND<10
	1/22/2009		180 160	ND<200 ND<500		ND<5,000 ND<12,000	ND<10 ND<25		ND<10 ND<25	ND<10 ND<25	ND<10 ND<25	ND<10 ND<25

60249149 9 of 97 AECOM

Table 4
Historical Groundwater Analytical Results - Oxygenate Compounds
76 Service Station #1156 (Chevron Site #351645)
4276 MacArthur Boulevard
Oakland, California

WELL ID	DATE	MTBE (8021B) (µg/L)	MTBE (8260B) (μg/L)	TBA (μg/L)	Ethanol (8260B) (μg/L)	Ethanol (8015Β) (μg/L)	EDB (µg/L)	EDB (504) (μg/L)	EDC (µg/L)	DIPE (µg/L)	ETBE (μg/L)	TAME (μg/L)
	4/13/2009		150	280		ND<1,200	ND<2.5		ND<2.5	ND<2.5	ND<2.5	ND<2.5
	7/23/2009		140	ND<2,000		ND<50,000	ND<100		ND<100	ND<100	ND<100	ND<100
	2/1/2010		ND<50									
	8/2/2010		ND<10				ND<10	ND<10	ND<10			
	8/24/2010											
MW-1B	11/1/2010		30	ND<10		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	1/31/2011		46	28		ND<250	ND<0.50		0.76	ND<0.50	ND<0.50	ND<0.50
	4/26/2011		44	33		ND<250	ND<0.50		0.82	ND<0.50	ND<0.50	ND<0.50
	7/25/2011		47	28		ND<250	ND<0.50		0.75	ND<0.50	ND<0.50	ND<0.50
	10/7/2011		41	30		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	1/23/2012		32	23		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	4/6/2012		55	18		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	7/24/2012		46	27		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
MW-2	7/20/1999	4,500	11,000									
	9/28/1999	5,280	6,150	ND						ND	ND	ND
	1/7/2000	33,100										
	3/31/2000	17,000										
	7/14/2000	66,500										
	10/3/2000	57,500										
	1/3/2001	49,000										
	4/4/2001	38,700	37,800	ND		ND	ND		ND	ND	ND	ND
	7/17/2001	65,000	56,000	ND		ND	ND		ND	ND	ND	ND
	10/3/2001	14,000	18,000									
	1/28/2002	11,000	10,000									
	4/25/2002	8,400	8,100									
	7/18/2002	4,300	8,800	ND<1,000		ND<25,000,000	ND<100		ND<100	ND<100	ND<100	ND<100
	10/7/2002	7,100	5,900	ND<20,000		ND<100,000,000	ND<400		ND<400	ND<400	ND<400	ND<400
	1/6/2003	31,000	35,000	ND<50,000		ND<250,000,000	ND<1,000		ND<1,000	ND<1,000	ND<1,000	ND<1,00
	4/7/2003	2,000	1,500	ND<2,000		ND<10,000,000	ND<40		ND<40	ND<40	ND<40	ND<40
	7/7/2003	5,500	8,300	ND<5,000		ND<25,000,000	ND<100		ND<100	ND<100	ND<100	ND<100
	10/9/2003		8,500	ND<10,000		ND<50,000	ND<200		ND<200	ND<200	ND<200	ND<200
	1/14/2004	2,600	3,200	ND<2,500		ND<13,000	ND<50		ND<50	ND<50	ND<50	ND<50
IW-2 cont.	4/28/2004	35,000	22,000	13,000		ND<1,000	ND<0.5		ND<0.5	ND<1	ND<1	11
	7/12/2004	3,000	3,000	110		ND<4,000	ND<3		ND<3	ND<5	ND<5	ND<5
	10/25/2004	1,800	1,600	1,100		ND<1,300	ND<13		ND<13	ND<25	ND<13	ND<13
	1/17/2005	1,600	1,500	1,200		ND<1,300	ND<13		ND<13	ND<25	ND<13	ND<13
	4/6/2005	2,500	3,200	2,800		ND<2,500	ND<25		ND<25	ND<25	ND<25	ND<25
	7/8/2005	2,900	3,100	4,300		ND<2,500	ND<25		ND<25	ND<25	ND<25	ND<25

60249149 10 of 97 AECOM

Table 4
Historical Groundwater Analytical Results - Oxygenate Compounds
76 Service Station #1156 (Chevron Site #351645)
4276 MacArthur Boulevard
Oakland, California

WELL ID	DATE	MTBE (8021B) (μg/L)	MTBE (8260B) (μg/L)	TBA (μg/L)	Ethanol (8260B) (μg/L)	Ethanol (8015B) (μg/L)	EDB (µg/L)	EDB (504) (μg/L)	EDC (µg/L)	DIPE (μg/L)	ETBE (μg/L)	TAME (μg/L)
	10/7/2005	5,900	5,200	8,700		ND<250	ND<0.50		1.4	ND<0.50	ND<0.50	ND<0.50
	1/27/2006	2,600	2,800	5,200		ND<12,000	ND<25		ND<25	ND<25	ND<25	ND<25
	4/28/2006	3,700	3,600	6,700		ND<250	ND<0.50		1.4	ND<0.50	ND<0.50	1.6
	7/28/2006	3,000	2,900	5,100		ND<6,200	ND<12		ND<12	ND<12	ND<12	ND<12
	10/27/2006	1,600	1,300	6,600		ND<1,200	ND<2.5		ND<2.5	ND<2.5	ND<2.5	ND<2.5
	1/10/2007	2,300	2,000	6,000		ND<1,200	ND<2.5		ND<2.5	ND<2.5	ND<2.5	ND<2.5
	4/13/2007	3,600	3,200	7,400		ND<6,200	ND<12		ND<12	ND<12	ND<12	ND<12
	7/19/2007	2,000	2,000	6,200		ND<2,500	ND<5.0		ND<5.0	ND<5.0	ND<5.0	ND<5.0
	10/8/2007	5,000	4,000	20,000		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	1/9/2008	2,100	2,200	9,900		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	4/4/2008		2,100	5,800		ND<1,200	ND<2.5		ND<2.5	ND<2.5	ND<2.5	ND<2.5
	7/3/2008		1,400	8,300		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	10/3/2008		750	5,900		ND<1,200	ND<2.5		ND<2.5	ND<2.5	ND<2.5	ND<2.5
	1/22/2009		850	7,400		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	4/13/2009		990	5,500		ND<2,500	ND<5.0		ND<5.0	ND<5.0	ND<5.0	ND<5.0
	7/23/2009		390	5,000		ND<2,500	ND<5.0		ND<5.0	ND<5.0	ND<5.0	ND<5.0
	2/1/2010		290									
	8/2/2010		140				ND<1.0	ND<1.0	ND<1.0			
	8/24/2010	-					-					
MW-2B	11/1/2010		250	2,000		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	1/31/2011		310	1,300		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	4/26/2011		240	770		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	7/25/2011		170	1,100		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	10/7/2011		100	840		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	1/23/2012		95	370		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	4/6/2012		140	310		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	7/24/2012		53	270		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
MW-3	7/20/1999	330										
	9/28/1999	443	288	ND						ND	ND	8.80
MW-3 cont.	1/7/2000	1,940										
	3/31/2000	2,800										
	7/14/2000	548										
	10/3/2000	965										
	1/3/2001	3,300										
	4/4/2001	1,050	450	ND		ND	ND		ND	ND	ND	ND
	7/17/2001	ND	350	ND		ND	ND		ND	ND	ND	ND
	10/3/2001	ND<1000										
	1/28/2002	3,200	210									

60249149 11 of 97 AECOM

Table 4
Historical Groundwater Analytical Results - Oxygenate Compounds
76 Service Station #1156 (Chevron Site #351645)
4276 MacArthur Boulevard
Oakland, California

WELL ID	DATE	MTBE (8021B) (μg/L)	MTBE (8260B) (μg/L)	TBΑ (μg/L)	Ethanol (8260Β) (μg/L)	Ethanol (8015Β) (μg/L)	EDB (µg/L)	EDB (504) (μg/L)	EDC (μg/L)	DIPE (μg/L)	ETBE (µg/L)	TAME (µg/L)
	4/25/2002	500	260									
	7/18/2002	ND<250	270	ND<50		ND<1,200,000	ND<5.0		ND<5.0	ND<5.0	ND<5.0	ND<5.0
	10/7/2002	ND<120	ND<200	ND<10,000		ND<50,000,000	ND<200		ND<200	ND<200	ND<200	ND<200
	1/6/2003	440	110	ND<4,000		23,000,000	ND<80		ND<80	ND<80	ND<80	ND<80
	4/7/2003	440	100	ND<4,000		ND<20,000,000	ND<80		ND<80	ND<80	ND<80	ND<80
	7/7/2003	280	100	ND<2,000		ND<10,000,000	ND<40		ND<40	ND<40	ND<40	ND<40
	10/9/2003		190	ND<1,000		ND<5,000	ND<20		ND<20	ND<20	ND<20	ND<20
	1/14/2004	190	230	ND<1,000		ND<5,000	ND<20		ND<20	ND<20	ND<20	ND<20
	4/28/2004	740	240	ND<12		ND<1,000	ND<3		ND<3	ND<1	ND<1	ND<1
	7/12/2004	180	100	350		ND<20,000	ND<10		ND<10	ND<20	ND<20	ND<20
	10/25/2004	94	260	39		ND<250	ND<2.5		ND<2.5	ND<5.0	ND<2.5	ND<2.5
	1/17/2005	55	200	120		ND<250	ND<2.5		ND<2.5	ND<5.0	ND<2.5	ND<2.5
	4/6/2005	ND<250	200	150		ND<1,000	ND<10		ND<10	ND<10	ND<10	ND<10
	7/8/2005	ND<250	150	64		ND<250	ND<2.5		ND<2.5	ND<2.5	ND<2.5	ND<2.5
	10/7/2005	260	180	ND<200		ND<5,000	ND<10		ND<10	ND<10	ND<10	ND<10
	1/27/2006	280	250	ND<10		ND<250	ND<0.50		1.5	ND<0.50	ND<0.50	ND<0.50
	4/28/2006	230	180	190		ND<250	ND<0.50		0.63	ND<0.50	ND<0.50	ND<0.50
	7/28/2006	250	150	ND<10		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	10/27/2006	250	140	ND<10		ND<250	ND<0.50		1.3	ND<0.50	ND<0.50	ND<0.50
	1/10/2007	230	150	66		ND<250	ND<0.50		1.4	ND<0.50	ND<0.50	ND<0.50
	4/13/2007	230	160	ND<10		ND<250	ND<0.50		1.2	ND<0.50	ND<0.50	ND<0.50
	7/19/2007	190	180	ND<10		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	10/8/2007	180	120	ND<20		ND<500	ND<1.0		1.1	ND<1.0	ND<1.0	ND<1.0
	1/9/2008	290	120	ND<20		ND<500	ND<1.0		ND<1.0	ND<1.0	ND<1.0	ND<1.0
	4/4/2008		120	ND<50		ND<1,200	ND<2.5		ND<2.5	ND<2.5	ND<2.5	ND<2.5
	7/3/2008		190	ND<10		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	10/3/2008		71	ND<100		ND<2,500	ND<5.0		ND<5.0	ND<5.0	ND<5.0	ND<5.0
	1/22/2009		130	ND<20		ND<500	ND<1.0		ND<1.0	ND<1.0	ND<1.0	ND<1.0
MW-3 cont.	4/13/2009		120	ND<10		ND<250	ND<0.50		1.0	ND<0.50	ND<0.50	ND<0.50
	7/23/2009		120	ND<100		ND<2,500	ND<5.0		ND<5.0	ND<5.0	ND<5.0	ND<5.0
	2/1/2010		97									
	8/2/2010		89				ND<0.50		ND<0.50			
	8/24/2010											
MW-3B	11/1/2010		46	ND<10		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	1/31/2011		73	ND<10		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	4/26/2011		52	ND<10		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	7/25/2011		62	47		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	10/7/2011		61	64		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	1/23/2012		56	ND<10		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50

60249149 12 of 97 AECOM

Table 4
Historical Groundwater Analytical Results - Oxygenate Compounds
76 Service Station #1156 (Chevron Site #351645)
4276 MacArthur Boulevard
Oakland, California

WELL ID	DATE	MTBE (8021B) (μg/L)	MTBE (8260B) (μg/L)	TBA (µg/L)	Ethanol (8260Β) (μg/L)	Ethanol (8015Β) (μg/L)	EDB (µg/L)	EDB (504) (μg/L)	EDC (µg/L)	DIPE (µg/L)	ETBE (µg/L)	TAME (μg/L)
	4/6/2012		68	ND<10		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	7/24/2012		54	ND<10		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
MW-4	7/20/1999	100										
	9/28/1999	416	459	ND						ND	ND	ND
	1/7/2000	764										
	3/31/2000	1,000										
	7/14/2000	1,530										
	10/3/2000	1,040										
	1/3/2001	850										
	4/4/2001	1,140	819	ND		ND	ND		ND	ND	ND	ND
	7/17/2001	1,200	900	ND		ND	ND		ND	ND	ND	ND
	10/3/2001	580	820									
	1/28/2002	1,100	500									
	4/25/2002	680	600									
	7/18/2002	530	760	ND<100		ND<2,500,000	ND<10		49	ND<10	ND<10	ND<10
	10/7/2002	650	540	ND<10,000		ND<50,000,000	ND<200		ND<200	ND<200	ND<200	ND<200
	1/6/2003	370	520	ND<1,000		ND<5,000,000	ND<20		ND<20	ND<20	ND<20	ND<20
	4/7/2003	550	420	ND<1,000		ND<5,000,000	ND<20		ND<20	ND<20	ND<20	ND<20
	7/7/2003	480	450	ND<1,000		ND<5,000,000	ND<20		ND<20	ND<20	ND<20	ND<20
	10/9/2003		270	ND<200		ND<1,000	ND<4.0		ND<4.0	ND<4.0	ND<4.0	ND<4.0
	1/14/2004	150	180	ND<200		ND<1,000	ND<4.0		6.5	ND<4.0	ND<4.0	ND<4.0
	4/28/2004	490	310	150		ND<1,000	ND<0.5		ND<0.5	ND<1	ND<1	ND<1
	7/12/2004	710	470	210		ND<4,000	ND<3		14	ND<5	ND<5	ND<5
	10/25/2004	200	170	38		ND<100	ND<1.0		2.0	ND<2.0	ND<1.0	ND<1.0
MW-4 cont.	1/17/2005	240	200	110		ND<100	ND<1.0		3.6	ND<2.0	ND<1.0	ND<1.0
	4/6/2005	ND<25	26	ND<25		73,000	ND<2.5		ND<2.5	ND<2.5	ND<2.5	ND<2.5
	7/8/2005	ND<25	64	29		ND<50	ND<0.50		1.2	ND<0.50	ND<0.50	ND<0.50
	10/7/2005	370	310	210		ND<250	ND<0.50		26	ND<0.50	ND<0.50	ND<0.50
	1/27/2006	320	240	280		ND<2,500	ND<5.0		ND<5.0	ND<5.0	ND<5.0	ND<5.0
	4/28/2006	140	140	130		ND<250	ND<0.50		0.97	ND<0.50	ND<0.50	ND<0.50
	7/28/2006	170	150	64		ND<250	ND<0.50		5.8	ND<0.50	ND<0.50	ND<0.50
	10/27/2006	130	130	54		ND<250	ND<0.50		1.5	ND<0.50	ND<0.50	ND<0.50
	1/10/2007	160	150	33		310	ND<0.50		1.9	ND<0.50	ND<0.50	ND<0.50
	4/13/2007	210	160	82		ND<250	ND<0.50		0.77	ND<0.50	ND<0.50	ND<0.50
	7/19/2007	120	130	13		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	10/8/2007	160	150	ND<20		ND<500	ND<1.0		ND<1.0	ND<1.0	ND<1.0	ND<1.0
	1/9/2008	210	220	ND<20		ND<500	ND<1.0		ND<1.0	ND<1.0	ND<1.0	ND<1.0
	4/4/2008		110	27		ND<250	ND<0.50		1.0	ND<0.50	ND<0.50	ND<0.50
	7/3/2008		100	27		ND<250	ND<0.50		1.4	ND<0.50	ND<0.50	ND<0.50

60249149 13 of 97 AECOM

Table 4
Historical Groundwater Analytical Results - Oxygenate Compounds
76 Service Station #1156 (Chevron Site #351645)
4276 MacArthur Boulevard
Oakland, California

WELL ID	DATE	MTBE (8021B) (μg/L)	MTBE (8260B) (μg/L)	TBA (µg/L)	Ethanol (8260B) (μg/L)	Ethanol (8015B) (µg/L)	EDB (µg/L)	EDB (504) (μg/L)	EDC (µg/L)	DIPE (μg/L)	ETBE (μg/L)	TAME (µg/L)
	10/3/2008		100	ND<10		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	1/22/2009		96	ND<10		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	4/13/2009		88	39		ND<250	ND<0.50		1.4	ND<0.50	ND<0.50	ND<0.50
	7/23/2009		92	42		ND<250	ND<0.50		1.5	ND<0.50	ND<0.50	ND<0.50
	2/1/2010		51									
	8/2/2010		48				ND<0.50	ND<1.0	1.4			
	8/24/2010											
MW-4B	11/1/2010		20	ND<10		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	1/31/2011		30	ND<10		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	4/26/2011		26	25		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	7/25/2011		28	ND<10		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	10/7/2011		25	25		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	1/23/2012		17	ND<10		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	4/6/2012		21	ND<10		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	7/24/2012		24	ND<10		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
MW-5	10/3/2001	1,800	2,100									
	1/28/2002	650	550									
	4/25/2002	2,200	2,400									
	7/18/2002	530	690	ND<20		ND<500,000	ND<2.0		ND<2.0	ND<2.0	ND<2.0	ND<2.0
	10/7/2002	300	330	ND<100		ND<500,000	ND<2.0		ND<2.0	ND<2.0	ND<2.0	ND<2.0
MW-5 cont.	1/6/2003	410	350	ND<100		ND<500,000	ND<2.0		ND<2.0	ND<2.0	ND<2.0	ND<2.0
	4/7/2003	450	420	ND<500		ND<2,500,000	ND<10		ND<10	ND<10	ND<10	ND<10
	7/7/2003	220	200	ND<200		ND<1,000,000	ND<4.0		ND<4.0	ND<4.0	ND<4.0	ND<4.0
	10/9/2003		290	ND<200		ND<1,000	ND<4.0		ND<4.0	ND<4.0	ND<4.0	ND<4.0
	1/14/2004	670	760	ND<2,000		ND<10,000	ND<40		ND<40	ND<40	ND<40	ND<40
	4/28/2004	1,200	790	ND<12		ND<1,000	ND<0.5		1.8	ND<1	ND<1	ND<1
	7/12/2004	2.8	ND<0.5	ND<12		ND<800	ND<0.5		0.76	ND<1	ND<1	ND<1
	10/25/2004	780	1100	ND<500		ND<5,000	ND<50		ND<50	ND<100	ND<50	ND<50
	1/17/2005	530	550	100		ND<250	ND<2.5		ND<2.5	ND<5.0	ND<2.5	ND<2.5
	4/6/2005	600	760	7.6		ND<50	ND<0.50		1.4	ND<0.50	ND<0.50	ND<0.50
	7/8/2005	570	630	180		ND<500	ND<5.0		ND<5.0	ND<5.0	ND<5.0	ND<5.0
	10/7/2005	530	490	ND<10		ND<250	ND<0.50		1.0	ND<0.50	ND<0.50	ND<0.50
	1/27/2006	580	610	1,000		ND<2,500	ND<5.0		ND<5.0	ND<5.0	ND<5.0	ND<5.0
	4/28/2006	590	520	130		ND<250	ND<0.50		0.95	ND<0.50	ND<0.50	ND<0.50
	7/28/2006	440	420	ND<100		ND<2,500	ND<5.0		ND<5.0	ND<5.0	ND<5.0	ND<5.0
	10/27/2006	460	390	43		ND<250	ND<0.50		1.5	ND<0.50	ND<0.50	ND<0.50
	1/10/2007	430	420	28		ND<250	ND<0.50		1.7	ND<0.50	ND<0.50	ND<0.50
	4/13/2007	160	120	ND<10		ND<250	ND<0.50		0.84	ND<0.50	ND<0.50	ND<0.50

60249149 14 of 97 AECOM

Table 4
Historical Groundwater Analytical Results - Oxygenate Compounds
76 Service Station #1156 (Chevron Site #351645)
4276 MacArthur Boulevard
Oakland, California

WELL ID	DATE	MTBE (8021B) (µg/L)	MTBE (8260B) (μg/L)	TBA (µg/L)	Ethanol (8260Β) (μg/L)	Ethanol (8015Β) (μg/L)	EDB (µg/L)	EDB (504) (μg/L)	EDC (µg/L)	DIPE (µg/L)	ETBE (µg/L)	TAME (µg/L)
	7/19/2007	19	23	ND<10		ND<250	ND<0.50		ND<5.0	ND<0.50	ND<0.50	ND<0.50
	10/8/2007	310	280	ND<10		ND<250	ND<0.50		1.3	ND<0.50	ND<0.50	ND<0.50
	1/9/2008	170	170	ND<10		ND<250	ND<0.50		1.2	ND<0.50	ND<0.50	ND<0.50
	4/4/2008		260	ND<10		ND<250	ND<0.50		1.4	ND<0.50	ND<0.50	ND<0.50
	7/3/2008		360	ND<10		ND<250	ND<0.50		1.5	ND<0.50	ND<0.50	ND<0.50
	10/3/2008		240	ND<10		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	1/22/2009		170	ND<10		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	4/13/2009		190	ND<10		ND<250	ND<0.50		1.2	ND<0.50	ND<0.50	ND<0.50
	7/23/2009		210	ND<10		ND<250	ND<0.50		1.8	ND<0.50	ND<0.50	ND<0.50
	2/1/2010		120									
	8/2/2010		42				ND<0.50		ND<0.50			
	11/1/2010											
	1/31/2011		130	ND<10		ND<250	ND<0.50		1.6	ND<0.50	ND<0.50	ND<0.50
	4/26/2011											
	7/25/2011		130	ND<10		ND<250	ND<0.50		1.6	ND<0.50	ND<0.50	ND<0.50
	10/7/2011											
	1/23/2012		52	22		ND<250	ND<0.50		0.92	ND<0.50	ND<0.50	ND<0.50
	4/6/2012											
	7/24/2012	-	81	20		ND<250	ND<0.50		1.4	ND<0.50	ND<0.50	ND<0.50
MW-6	10/3/2001	200	270									
	1/28/2002	ND<2.5										
	4/25/2002	ND<2.5										
	7/18/2002	ND<2.5	ND<2.0	ND<20		ND<500,000	ND<2.0		ND<2.0	ND<2.0	ND<2.0	ND<2.0
	10/7/2002	ND<2.5	ND<2.0	ND<100		ND<500,000	ND<2.0		ND<2.0	ND<2.0	ND<2.0	ND<2.0
	1/6/2003	ND<2.0	ND<2.0	ND<100		ND<500,000	ND<2.0		ND<2.0	ND<2.0	ND<2.0	ND<2.0
	4/7/2003	46	46	ND<100		ND<500,000	ND<2.0		ND<2.0	ND<2.0	ND<2.0	ND<2.0
	7/7/2003	ND<2.0	ND<2.0	ND<100		ND<500,000	ND<2.0		ND<2.0	ND<2.0	ND<2.0	ND<2.0
	10/9/2003		ND<2.0	ND<100		ND<500	ND<2.0		ND<2.0	ND<2.0	ND<2.0	ND<2.0
	1/14/2004	ND<5.0	ND<2.0	ND<100		ND<500	ND<2.0		ND<2.0	ND<2.0	ND<2.0	ND<2.0
	4/28/2004	ND<1	ND<0.5	ND<12		ND<1,000	ND<0.5		ND<0.5	ND<1	ND<1	ND<1
	7/12/2004	6.4	ND<0.5	ND<12		ND<800	ND<0.5		ND<0.5	ND<1	ND<1	ND<1
	10/25/2004	ND<5.0	0.57	ND<5.0		ND<50	ND<0.50		ND<0.50	ND<1.0	ND<0.50	ND<0.50
	1/17/2005	ND<5.0	ND<0.50	ND<5.0		ND<50	ND<0.50		ND<0.50	ND<1.0	ND<0.50	ND<0.50
	4/6/2005	ND<5.0	ND<0.50	ND<5.0		ND<50	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	7/8/2005	ND<5.0	ND<0.50	ND<5.0		ND<50	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	10/7/2005	ND<1.0	ND<0.50	ND<10		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	1/27/2006	ND<1.0	ND<0.50	ND<10		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	4/28/2006	ND<1.0	ND<0.50	ND<10		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	7/28/2006	ND<1.0	ND<0.50	ND<10		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50

60249149 15 of 97 AECOM

Table 4
Historical Groundwater Analytical Results - Oxygenate Compounds
76 Service Station #1156 (Chevron Site #351645)
4276 MacArthur Boulevard
Oakland, California

WELL ID	DATE	MTBE (8021B) (μg/L)	MTBE (8260B) (μg/L)	TBA (μg/L)	Ethanol (8260B) (μg/L)	Ethanol (8015B) (μg/L)	EDB (µg/L)	EDB (504) (µg/L)	EDC (μg/L)	DIPE (µg/L)	ETBE (μg/L)	TAME (μg/L)
	10/27/2006	ND<1.0	ND<0.50	ND<10	(F9: -) 	ND<250	ND<0.50	(F9·-)	ND<0.50	ND<0.50	ND<0.50	ND<0.50
	1/10/2007	ND<1.0	ND<0.50	ND<10		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	4/13/2007	ND<1.0	ND<0.50	ND<10		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	7/19/2007	ND<1.0	ND<0.50	ND<10		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	10/8/2007	ND<1.0	0.80	ND<10		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	1/9/2008	ND<1.0	ND<0.50	ND<10		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	4/4/2008		ND<0.50	ND<10		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	7/3/2008		1.4	ND<10		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	10/3/2008		1.8	ND<10		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	1/22/2009		1.2	ND<10		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	4/13/2009		0.72	ND<10		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	7/23/2009											
	2/1/2010											
	8/2/2010											
	8/24/2010									-		
MW-7	10/3/2001	35,000	40,000									
	1/28/2002	42,000	38,000									
	4/25/2002	42,000	45,000									
	7/18/2002	51,000	53,000	33,000		ND<5,000,000	ND<20		ND<20	ND<20	ND<20	ND<20
	10/7/2002	33,000	38,000	26,000		ND<100,000,000	ND<400		ND<400	ND<400	ND<400	ND<400
	1/6/2003	3,900	3,100	ND<10,000		ND<50,000,000	ND<200		ND<200	ND<200	ND<200	ND<200
	4/7/2003	32,000	28,000	ND<40,000		ND<200,000,000	ND<800		ND<800	ND<800	ND<800	ND<800
	7/7/2003	36,000	45,000	27,000		ND<100,000,000	ND<400		ND<400	ND<400	ND<400	ND<400
	10/9/2003		20,000	ND<25,000		ND<130,000	ND<500		ND<500	ND<500	ND<500	ND<500
	1/14/2004	20,000	25,000	ND<40,000		ND<200,000	ND<800		ND<800	ND<800	ND<800	ND<800
	4/28/2004	30,000	21,000	9,200		ND<1,000	ND<0.5		6.8	ND<1	ND<1	12
	7/12/2004	12,000	11,000	4,600		ND<8,000	ND<5		5.1	ND<10	ND<10	ND<10
	10/25/2004	13,000	14,000	3,900		ND<5,000	ND<50		ND<50	ND<100	ND<50	ND<50
	1/17/2005	17,000	16,000	4,200		ND<5,000	ND<50		ND<50	ND<100	ND<50	ND<50
	4/6/2005	14,000	17,000	4,200		ND<10,000	ND<0.50		6.4	ND<0.50	ND<0.50	9.3
	7/8/2005	8,600	11,000	4,300		ND<5,000	ND<50		ND<50	ND<50	ND<50	ND<50
	10/7/2005	9,400	9,800	1,100		ND<12,000	ND<25		ND<25	ND<25	ND<25	ND<25
	1/27/2006	9,900	7,900	1,600		ND<25,000	ND<50		ND<50	ND<50	ND<50	ND<50
	4/28/2006	9,600	11,000	2,900		ND<250	ND<0.50		3.4	ND<0.50	ND<0.50	6.3
	7/28/2006	5,000	5,300	1,300		ND<6,200	ND<12		ND<12	ND<12	ND<12	ND<12
	10/27/2006	4,700	3,700	1,700		ND<2,500	ND<5.0		ND<5.0	ND<5.0	ND<5.0	ND<5.0
	1/10/2007	4,400	4,400	1,300		ND<2,500	ND<5.0		ND<5.0	ND<5.0	ND<5.0	ND<5.0
	4/13/2007											
	7/19/2007	2,700	3,300	ND<100		ND<2,500	ND<5.0		ND<5.0	ND<5.0	ND<5.0	ND<5.0

60249149 16 of 97 AECOM

Table 4
Historical Groundwater Analytical Results - Oxygenate Compounds
76 Service Station #1156 (Chevron Site #351645)
4276 MacArthur Boulevard
Oakland, California

WELL ID	DATE	MTBE (8021B) (µg/L)	MTBE (8260B) (μg/L)	TBA (µg/L)	Ethanol (8260B) (µg/L)	Ethanol (8015Β) (μg/L)	EDB (µg/L)	EDB (504) (μg/L)	EDC (µg/L)	DIPE (µg/L)	ETBE (µg/L)	TAME (μg/L)
	10/8/2007	2,500	2,200	ND<500		ND<12,000	ND<25	-	ND<25	ND<25	ND<25	ND<25
	1/9/2008	1,900	1,900	2,700		ND<250	ND<0.50		1.2	ND<0.50	ND<0.50	1.1
	4/4/2008		2,700	1,400		ND<6,200	ND<12		ND<12	ND<12	ND<12	ND<12
	7/3/2008		2,300	940		ND<250	ND<0.50		2.2	ND<0.50	ND<0.50	1.2
	10/3/2008		1,800	540		ND<1,200	ND<2.5		ND<2.5	ND<2.5	ND<2.5	ND<2.5
	1/22/2009		1,300	370		ND<1,200	ND<2.5		ND<2.5	ND<2.5	ND<2.5	ND<2.5
	4/13/2009		1,200	420		ND<5,000	ND<10		ND<10	ND<10	ND<10	ND<10
	7/23/2009		900	370		ND<2,500	ND<5.0		ND<5.0	ND<5.0	ND<5.0	ND<5.0
	2/1/2010		720									
	8/2/2010		770				ND<0.50		1.9			
	11/1/2010											
	1/31/2011		600	160		ND<250	ND<0.50		1.3	ND<0.50	ND<0.50	ND<0.50
	4/26/2011											
MW-7 cont.	7/25/2011		620	220		ND<250	ND<0.50		1.6	ND<0.50	ND<0.50	ND<0.50
	10/7/2011											
	1/23/2012		390	190		ND<250	ND<0.50		1.2	ND<0.50	ND<0.50	ND<0.50
	4/6/2012											
	7/24/2012		300	160		ND<250	ND<0.50		1.5	ND<0.50	ND<0.50	ND<0.50
MW-8	1/18/2008	ND<1.0	ND<0.50	ND<10		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	4/4/2008		ND<0.50	ND<10		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	7/3/2008		ND<0.50	ND<10		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	10/3/2008		ND<0.50	ND<10		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	1/22/2009		ND<0.50	ND<10		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	4/13/2009		ND<0.50	ND<10		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	7/23/2009		ND<0.50	ND<10		ND<250	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50
	2/1/2010		ND<0.50									
	8/2/2010											
	8/24/2010											

NOTES:

Oxygenate compounds analyzed by U.S. EPA Method 8260B ND<# = Analyte not detected below indicated practical quantitation limit

μg/L = Micrograms per liter

-- = Not available

MTBE = Methyl tertiary butyl ether

TBA = Tertiary butyl alcohol

EDB = 1,2-Dibromoethane

EDC = 1,2-Dichloroethane

DIPE = Di-isopropyl ether

ETBE = Ethyl tertiary butyl ether

TAME = Tertiary amyl methyl ether

1,1-DCA = 1,1-Dichloroethane

WELL ID	DATE	Acenaph- thylene (μg/l)	Bromo- dichloro- methane (μg/l)	Bromo- form (μg/l)	Bromo- methane (μg/l)	Carbon Tetra- chloride (µg/l)	Chloro- benzene (µg/l)	Chloro- ethane (µg/l)	Chloroform (μg/l)	Chloro- methane (µg/l)	Dibromo- chloro- methane (μg/l)	1,2- Dichloro- benzene (µg/l)	1,3- Dichlord benzend (µg/l)
MW-1	7/20/1999						12					3.9	
	9/28/1999												
	1/7/2000												
	3/31/2000											6.2	
	7/14/2000												
	10/3/2000												
	1/3/2001												
	4/4/2001						5.6					4.6	
	7/17/2001											18	
	10/5/2001												
	1/28/2002												
	4/25/2002												
	7/18/2002						5.9	1.1				5.8	
	10/7/2002												
	1/6/2003												
	4/7/2003												
	7/7/2003						ND<120						
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004	ND<2	ND<10	ND<10	ND<20	ND<10	ND<10	ND<10	ND<10	ND<10	ND<10	ND<2	ND<2
	10/25/2004												
	1/17/2005												
	4/6/2005												
	7/8/2005		ND<0.50	ND<2.0	ND<1.0	ND<0.50	12	1.0	ND<0.50	ND<1.0	ND<0.50	9.0	ND<0.5
	10/7/2005												
	1/27/2006												
	4/28/2006												
	7/28/2006		ND<0.50	ND<0.50	ND<1.0	ND<0.50	ND<0.50	ND<0.50	ND<0.50	ND<0.50	ND<0.50	ND<0.50	ND<0.5
	10/27/2006												
	1/10/2007												
	4/13/2007												
	7/19/2007		ND<50	ND<50	ND<100	ND<50	ND<50	ND<50	ND<50	ND<50	ND<50	ND<50	ND<50
	1/9/2008												
	4/4/2008												
	7/3/2008		ND<12	ND<12	ND<25	ND<12	ND<12	ND<12	ND<12	ND<12	ND<12	ND<12	ND<12
	10/3/2008												
	1/22/2009												
	4/13/2009												
MW-1 cont.	7/23/2009												

2/1/20 8/2/20 MW-1B 11/1/20 1/31/20 4/26/20 7/25/20 10/7/20 4/6/20 7/24/20 MW-2 9/28/19 4/4/20 7/17/20 10/7/20 10/9/20 11/14/20 4/28/20 7/12/20 10/25/2 1/17/20 10/25/2 1/17/20 4/6/20 7/8/20 10/7/20 4/6/20 7/8/20	010 010 011 011 011 011 012 012						 	 	 			
MW-1B 11/1/20 1/31/20 4/26/20 7/25/20 10/7/20 1/23/20 4/6/20 7/24/20 MW-2 9/28/19 4/4/20 7/17/20 10/7/20 10/9/20 10/9/20 10/1/20 10/25/2 1/17/20 10/25/2 1/17/20 10/25/2 1/17/20 10/25/2 1/17/20 10/7/20 11/27/20 10/7/20 11/27/20 11/	010 011 011 011 011 012 012 012 999 001 001 002				- - - - - - -	- - - - - - - - -	 	 	 	- - - - - - -	- - - - - - - -	
1/31/20 4/26/20 7/25/20 10/7/20 11/23/20 4/6/20 7/24/20 MW-2 9/28/18 4/4/20 7/17/20 10/7/20 11/6/20 4/7/20 10/9/20 11/14/20 4/28/20 10/25/2 11/17/20 4/6/20 7/8/20 10/7/20	011 011 011 011 012 012 012 0999 001 001 002			 	 	 	 	 	 	- - - - - -	-	
1/31/20 4/26/20 7/25/20 10/7/20 11/23/20 4/6/20 7/24/20 MW-2 9/28/18 4/4/20 7/17/20 10/7/20 11/6/20 4/7/20 10/9/20 11/14/20 4/28/20 10/25/2 11/17/20 4/6/20 7/8/20 10/7/20	011 011 011 011 012 012 012 0999 001 001 002			 	 	- - - - - - -	 - - - - - -	 	 		- - - - - -	
4/26/20 7/25/20 10/7/20 11/23/20 4/6/20 7/24/20 MW-2 9/28/18 4/4/20 7/17/20 10/7/20 11/6/20 4/7/20 10/9/20 11/14/20 4/28/20 11/17/20 10/25/2 1/17/20 4/6/20 7/8/20 10/7/20	011 011 011 012 012 012 012 999 001 001 002			 	 	- - - - - -	 - - - - - -	 	- - - - - -		- - - - - -	
7/25/20 10/7/20 1/23/20 4/6/20 7/24/20 MW-2 9/28/18 4/4/20 7/17/20 10/7/20 10/9/20 1/14/20 4/28/20 10/25/2 1/17/20 4/6/20 7/8/20 10/7/20	011 011 012 012 012 012 999 001 0001 000		 		 	- - - - -	 - - - -		 		- - - -	- - - - -
10/7/20 1/23/20 4/6/20 7/24/20 MW-2 9/28/18 4/4/20 7/17/20 7/18/20 10/9/20 10/9/20 1/14/20 4/28/20 10/25/2 1/17/20 4/6/20 7/8/20	011 012 012 012 012 999 001 001 002	 	 	 	 	- - - - -	 - - - -		 		- - - -	-
1/23/20 4/6/20 7/24/20 7/24/20 7/14/20 7/17/20 7/18/20 1/6/20 4/7/20 10/9/20 1/14/20 7/12/20 10/25/2 1/17/20 4/6/20 7/8/20	012 012 012 999 001 001 002	- - - - - -	 	 	 	- - - -	 - - - -		 - - - -		- - - -	
4/6/20 7/24/20 7/24/20 7/24/20 7/17/20 7/18/20 10/7/20 10/9/20 1/14/20 4/28/20 7/17/20 10/25/2 10/25/2 1/17/20 4/6/20 7/8/20 10/7/20	999 001 001 001 002 002	 	 	- - - -		 	 - - - -	 	 		 	
7/24/20 MW-2 9/28/19 4/4/20 7/17/20 7/18/20 1/6/20 4/7/20 7/7/20 10/9/20 1/14/20 4/28/20 7/1/20 10/25/2 1/17/20 4/6/20 7/8/20 10/7/20	999 001 001 002 002	 	 	- - - -		 	 - - - -	 	 		 	
MW-2 9/28/18 4/4/20 7/17/20 7/18/20 10/7/20 1/6/20 4/7/20 10/9/20 1/14/20 4/28/20 7/12/20 10/25/2 11/17/20 4/6/20 7/8/20 10/7/20	999 001 001 002 002	 	 	 		 	 	 	 		- - - -	
4/4/20 7/17/20 7/18/20 10/7/20 1/6/20 4/7/20 7/7/20 10/9/20 1/14/20 4/28/20 7/12/20 10/25/2 1/17/20 4/6/20 7/8/20 10/7/20	001 001 002 002	 	 	 		 	 	 	 		 	
7/17/20 7/18/20 10/7/20 1/6/20 4/7/20 7/7/20 10/9/20 1/14/20 4/28/20 7/12/20 10/25/2 1/17/20 4/6/20 7/8/20 10/7/20	001 002 002	 	 	 	 	 	 			 	 	
7/18/20 10/7/20 1/6/20 4/7/20 7/7/20 10/9/20 1/14/20 4/28/20 7/12/20 10/25/2 1/17/20 4/6/20 7/8/20	002 002	 	 	 	 		 	 		 		
10/7/20 1/6/20 4/7/20 7/7/20 10/9/20 1/14/20 4/28/20 7/12/20 10/25/2 1/17/20 4/6/20 7/8/20	002	 	 		 			 				
1/6/20 4/7/20 7/7/20 10/9/20 1/14/20 4/28/20 7/12/20 10/25/2 1/17/20 4/6/20 7/8/20 10/7/20							 					
4/7/20 7/7/20 10/9/20 1/14/20 4/28/20 7/12/20 10/25/2 1/17/20 4/6/20 7/8/20 10/7/20	003											
7/7/20 10/9/20 1/14/20 4/28/20 7/12/20 10/25/2 1/17/20 4/6/20 7/8/20 10/7/20							 					
10/9/20 1/14/20 4/28/20 7/12/20 10/25/2 1/17/20 4/6/20 7/8/20 10/7/20	003						 					
1/14/2(4/28/2(7/12/2(10/25/2 1/17/2(4/6/20 7/8/20 10/7/2(1/27/2(003						 					
4/28/20 7/12/20 10/25/2 1/17/20 4/6/20 7/8/20 10/7/20 1/27/20	003						 					
7/12/20 10/25/2 1/17/20 4/6/20 7/8/20 10/7/20 1/27/20	004						 					
10/25/2 1/17/20 4/6/20 7/8/20 10/7/20 1/27/20	004						 					
10/25/2 1/17/20 4/6/20 7/8/20 10/7/20 1/27/20							 					
1/17/20 4/6/20 7/8/20 10/7/20 1/27/20							 					
4/6/20 7/8/20 10/7/20 1/27/20							 					
7/8/20 10/7/20 1/27/20							 					
10/7/20 1/27/20							 					
1/27/20							 					
							 					
7/28/20							 					
10/27/2							 					
1/10/20							 					
4/13/20							 					-
	007						 					
7/19/20							 					
10/8/20	007						 					-
1/9/20	007 007						 					
W-2 cont. 4/4/20 7/3/20	007 007 008						 					

			Bromo-			Carbon					Dibromo-	1,2-	1,3-
WELL ID	DATE	Acenaph- thylene	dichloro- methane	Bromo- form	Bromo- methane	Tetra- chloride	Chloro- benzene	Chloro- ethane	Chloroform	Chloro- methane	chloro- methane	Dichloro- benzene	Dichlor benzen
		(µg/l)	(µg/l)	(µg/l)	(µg/l)	(µg/l)	(µg/l)	(µg/l)	(µg/l)	(µg/l)	(µg/l)	(µg/l)	(µg/I)
	10/3/2008												
	1/22/2009												
	4/13/2009												
	7/23/2009												
	2/1/2010												
	8/2/2010												
MW-2B	11/1/2010												
	1/31/2011												
	4/26/2011												
	7/25/2011												
	10/7/2011												
	1/23/2012												
	4/6/2012												
	7/24/2012												
B414/ O	0/00/4000												
MW-3	9/28/1999												
	4/4/2001												
	7/17/2001												
	7/18/2002												
	10/7/2002												-
	1/6/2003												
	4/7/2003												-
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004												
	10/25/2004												
	1/17/2005												
	4/6/2005												
	7/8/2005												
	10/7/2005												
	1/27/2006												
	4/28/2006												
	7/28/2006												
	10/27/2006												
IW-3 cont.	1/10/2007												
	4/13/2007												
	7/19/2007												

WELL ID	DATE	Acenaph- thylene (µg/l)	Bromo- dichloro- methane (µg/l)	Bromo- form (µg/l)	Bromo- methane (μg/l)	Carbon Tetra- chloride (µg/l)	Chloro- benzene (µg/l)	Chloro- ethane (µg/l)	Chloroform (µg/l)	Chloro- methane (µg/l)	Dibromo- chloro- methane (μg/l)	1,2- Dichloro- benzene (µg/l)	1,3- Dichlord benzene (µg/l)
	10/8/2007												
	1/9/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009												
	7/23/2009												
	2/1/2010												
	8/2/2010	-	-										
MW-3B	11/1/2010												
	1/31/2011												
	4/26/2011												
	7/25/2011												
	10/7/2011												
	1/23/2012												
	4/6/2012												
	7/24/2012	-							-				
MW-4	9/28/1999												
	4/4/2001												
	7/17/2001												
	7/18/2002												
	10/7/2002												
	1/6/2003												
	4/7/2003												
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004												
	10/25/2004												
	1/17/2005												
	4/6/2005												
	7/8/2005												
W-4 cont.	10/7/2005												
4 00110.	1/27/2006												
	4/28/2006												
	1 /20/2000												

WELL ID	DATE	Acenaph- thylene (µg/l)	Bromo- dichloro- methane (μg/l)	Bromo- form (µg/l)	Bromo- methane (µg/l)	Carbon Tetra- chloride (µg/l)	Chloro- benzene (µg/l)	Chloro- ethane (µg/l)	Chloroform (μg/l)	Chloro- methane (µg/l)	Dibromo- chloro- methane (µg/l)	1,2- Dichloro- benzene (µg/l)	1,3- Dichloro- benzene (µg/l)
	10/27/2006												
	1/10/2007												
	4/13/2007												
	7/19/2007												
	10/8/2007												
	1/9/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009												
	7/23/2009												
	2/1/2010												
	8/2/2010												
MW-4B	11/1/2010												
	1/31/2011												
	4/26/2011												
	7/25/2011												
	10/7/2011												
	1/23/2012												
	4/6/2012												
	7/24/2012	-							-			-	
MW-5	7/18/2002								_			_	
	10/7/2002												
	1/6/2003						ND<0.50						
	4/7/2003												
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004												
	10/25/2004												
	1/17/2005												
/IW-5 cont.	4/6/2005												
	7/8/2005												
	10/7/2005												
	1/27/2006												
	4/28/2006												

10/27/2006	WELL ID	DATE	Acenaph- thylene (μg/l)	Bromo- dichloro- methane (μg/l)	Bromo- form (µg/l)	Bromo- methane (µg/l)	Carbon Tetra- chloride (µg/l)	Chloro- benzene (µg/l)	Chloro- ethane (µg/l)	Chloroform (μg/l)	Chloro- methane (µg/l)	Dibromo- chloro- methane (µg/l)	1,2- Dichloro- benzene (µg/l)	1,3- Dichloro benzene (µg/l)
11/02/2007		7/28/2006												
### 4132007		10/27/2006												
7/19/2007		1/10/2007												
108/2007		4/13/2007												
19/2008		7/19/2007												
44/2008		10/8/2007												
7/3/2008		1/9/2008												
10/3/2008		4/4/2008												
1/22/2009		7/3/2008												
### ### ##############################		10/3/2008												
T/23/2009		1/22/2009												
2/1/2010		4/13/2009												
8/2/2010 - - - - - - - - -		7/23/2009												
8/2/2010 - - - - - - - - -														
1/31/2011 - - - - - - - - -														
4/26/2011														
7/25/2011														
10/7/2011														
1/23/2012														
4/6/2012														
MW-6 7/18/2002														
MW-6 7/18/2002														
10/7/2002														
10/7/2002	MW-6	7/18/2002												
1/6/2003														
4/7/2003														
7/7/2003														
10/9/2003														
1/14/2004				_						_				
4/28/2004														_
7/12/2004														
10/25/2004														
1/17/2005														
VIW-6 cont. 4/6/2005														
7/8/2005	MW-6 cont													<u></u>
10/7/2005	WIVY-O COIIL.													
1/27/2006														
4/28/2006														

WELL ID	DATE	Acenaph- thylene (μg/l)	Bromo- dichloro- methane (µg/l)	Bromo- form (µg/l)	Bromo- methane (μg/l)	Carbon Tetra- chloride (μg/l)	Chloro- benzene (µg/l)	Chloro- ethane (µg/l)	Chloroform (μg/l)	Chloro- methane (µg/l)	Dibromo- chloro- methane (μg/l)	1,2- Dichloro- benzene (µg/l)	1,3- Dichlord benzend (µg/l)
	10/27/2006												
	1/10/2007												
	4/13/2007												
	7/19/2007												
	10/8/2007												
	1/9/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009		-										
MW-7	7/18/2002												
	10/7/2002												
	1/6/2003						ND<50						
	4/7/2003												
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004												
	10/25/2004												
	1/17/2005												
	4/6/2005												
	7/8/2005												
	10/7/2005												
	1/27/2006												
	4/28/2006												
	7/28/2006												
	10/27/2006												
	1/10/2007												
	7/19/2007												
	10/8/2007												
IW-7 cont.	1/9/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009												
	7/23/2009												

WELL ID	DATE	Acenaph- thylene (µg/l)	Bromo- dichloro- methane (µg/l)	Bromo- form (µg/l)	Bromo- methane (µg/l)	Carbon Tetra- chloride (µg/l)	Chloro- benzene (µg/l)	Chloro- ethane (µg/l)	Chloroform (μg/l)	Chloro- methane (µg/l)	Dibromo- chloro- methane (µg/l)	1,2- Dichloro- benzene (µg/l)	1,3- Dichloro- benzene (µg/l)
	2/1/2010												
	8/2/2010												
	1/31/2011												
	4/26/2011												
	7/25/2011												
	10/7/2011												
	1/23/2012												
	4/6/2012												
	7/24/2012								-				
MW-8	1/18/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009												
	7/23/2009												
	2/1/2010												

NOTES:

ND<# = Analyte not detected below indicated practical quantitation limit

-- = Not sampled

μg/L = Micrograms per liter

WELL ID	DATE	1,4- Dichloro- benzene (µg/l)	Dichloro- difluoro- methane (µg/l)	1,1-DCA (μg/l)	1,1-DCE (μg/l)	cis- 1,2-DCE (μg/l)	trans- 1,2-DCE (μg/l)	1,2- Dichloro- propane (µg/l)	cis-1,3- Dichloro- propene (µg/l)	trans-1,3- Dichloro- propene (µg/l)	Hexa- chloro- butadiene (µg/l)	Methylene chloride (µg/l)	Naph thaler (µg/l
MW-1	7/20/1999			2.0		3.6		0.92					600
	9/28/1999												534
	1/7/2000												1,050
	3/31/2000												140
	7/14/2000												690
	10/3/2000												361
	1/3/2001												400
	4/4/2001					3.4							490
	7/17/2001												740
	10/5/2001												
	1/28/2002												
	4/25/2002												
	7/18/2002	1.3				1.3							910
	10/7/2002												
	1/6/2003												
	4/7/2003												
	7/7/2003					ND<120							850
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004	ND<2	ND<10	ND<10	ND<10	ND<10	ND<10	ND<10	ND<10	ND<10	ND<2	ND<20	450
	10/25/2004												
	1/17/2005												
	4/6/2005												
	7/8/2005	1.2	ND<1.0	1.3	ND<0.50	3.1	ND<0.50	ND<0.50	ND<0.50	ND<0.50	ND<20	ND<5.0	250
	10/7/2005												
	1/27/2006												
	4/28/2006												
	7/28/2006	ND<0.50	ND<0.50	ND<0.50	ND<0.50	4.5	ND<0.50	ND<0.50	ND<0.50	ND<0.50		ND<1.0	
	10/27/2006												
	1/10/2007												
	4/13/2007												
	7/19/2007	ND<50	ND<50	ND<50	ND<50	ND<50	ND<50	ND<50	ND<50	ND<50		ND<100	
	1/9/2008												
	4/4/2008												
	7/3/2008	ND<12	ND<12	ND<12	ND<12	ND<12	ND<12	ND<12	ND<12	ND<12		ND<25	
	10/3/2008												
	1/22/2009												
	4/13/2009												
IW-1 cont.	7/23/2009												

WELL ID	DATE	1,4- Dichloro- benzene (µg/l)	Dichloro- difluoro- methane (µg/l)	1,1-DCA (μg/l)	1,1-DCE (μg/l)	cis- 1,2-DCE (µg/l)	trans- 1,2-DCE (µg/l)	1,2- Dichloro- propane (µg/l)	cis-1,3- Dichloro- propene (µg/l)	trans-1,3- Dichloro- propene (µg/l)	Hexa- chloro- butadiene (µg/l)	Methylene chloride (µg/l)	Naph- thalene (µg/l)
	2/1/2010												
	8/2/2010							-					
MW-1B	11/1/2010												
	1/31/2011												
	4/26/2011												
	7/25/2011												
	10/7/2011												
	1/23/2012												
	4/6/2012							_				_	
	7/24/2012												
	1124/2012	-		-			-		-				-
MW-2	9/28/1999												
	4/4/2001												
	7/17/2001												
	7/18/2002												
	10/7/2002												
	1/6/2003												
	4/7/2003												
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004												
	10/25/2004												
	1/17/2005												
	4/6/2005												
	7/8/2005			_								_	_
	10/7/2005											_	_
	1/27/2006												
	4/28/2006												
	7/28/2006												
	10/27/2006												
	1/10/2007												
	4/13/2007												
	7/19/2007												
	10/8/2007												
	1/9/2008												
W-2 cont.	4/4/2008												
	7/3/2008												

WELL ID	DATE	1,4- Dichloro- benzene (µg/l)	Dichloro- difluoro- methane (μg/l)	1,1-DCA (μg/l)	1,1-DCE (μg/l)	cis- 1,2-DCE (μg/l)	trans- 1,2-DCE (µg/l)	1,2- Dichloro- propane (µg/l)	cis-1,3- Dichloro- propene (µg/l)	trans-1,3- Dichloro- propene (µg/l)	Hexa- chloro- butadiene (μg/l)	Methylene chloride (µg/l)	Naph- thalene (µg/l)
	10/3/2008												
	1/22/2009												
	4/13/2009												
	7/23/2009												
	2/1/2010												
	8/2/2010							-	-			-	
MW-2B	11/1/2010												
	1/31/2011												
	4/26/2011												
	7/25/2011												
	10/7/2011												
	1/23/2012												
	4/6/2012												
	7/24/2012												
MW-3	9/28/1999												
	4/4/2001												
	7/17/2001												
	7/18/2002												
	10/7/2002												
	1/6/2003												
	4/7/2003												
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004												
	10/25/2004												
	1/17/2005												
	4/6/2005												
	7/8/2005												
	10/7/2005												
	1/27/2006												
	4/28/2006												
	7/28/2006												
	10/27/2006												
/IW-3 cont.	1/10/2007												
	4/13/2007												
	7/19/2007												

WELL ID	DATE	1,4- Dichloro- benzene (µg/l)	Dichloro- difluoro- methane (μg/l)	1,1-DCA (μg/l)	1,1-DCE (μg/l)	cis- 1,2-DCE (μg/l)	trans- 1,2-DCE (µg/l)	1,2- Dichloro- propane (µg/l)	cis-1,3- Dichloro- propene (µg/l)	trans-1,3- Dichloro- propene (µg/l)	Hexa- chloro- butadiene (µg/l)	Methylene chloride (μg/l)	Naph- thalene (µg/l)
	10/8/2007	-	-	-				-	-	-	-	-	-
	1/9/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009												
	7/23/2009												
	2/1/2010												
	8/2/2010									-	-		
MW-3B	11/1/2010												
	1/31/2011												
	4/26/2011												
	7/25/2011												
	10/7/2011												
	1/23/2012												
	4/6/2012												
	7/24/2012												
MW-4	9/28/1999												
	4/4/2001												
	7/17/2001												
	7/18/2002												
	10/7/2002												
	1/6/2003												
	4/7/2003												
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004												
	10/25/2004												
	1/17/2005												
	4/6/2005												
	7/8/2005												
IW-4 cont.	10/7/2005												
	1/27/2006												
	4/28/2006												
	7/28/2006												

WELL ID	DATE	1,4- Dichloro- benzene (µg/l)	Dichloro- difluoro- methane (μg/l)	1,1-DCA (μg/l)	1,1-DCE (μg/l)	cis- 1,2-DCE (μg/l)	trans- 1,2-DCE (µg/l)	1,2- Dichloro- propane (µg/l)	cis-1,3- Dichloro- propene (µg/l)	trans-1,3- Dichloro- propene (µg/l)	Hexa- chloro- butadiene (µg/l)	Methylene chloride (μg/l)	Naph- thalene (µg/l)
	10/27/2006												
	1/10/2007												
	4/13/2007												
	7/19/2007												
	10/8/2007												
	1/9/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009												
	7/23/2009												
	2/1/2010												
	8/2/2010												
MW-4B	11/1/2010												
	1/31/2011												
	4/26/2011												
	7/25/2011												
	10/7/2011												
	1/23/2012												
	4/6/2012												
	7/24/2012												
	172-172012												
MW-5	7/18/2002												
	10/7/2002												
	1/6/2003					ND<0.50		_		_			ND<10
	4/7/2003												
	7/7/2003												
	10/9/2003							_		_		_	
	1/14/2004												
	4/28/2004								<u></u>	<u></u>			
	7/12/2004												
	10/25/2004												
	1/17/2005												
MW-5 cont.													
vivv-ə cont.	4/6/2005												
	7/8/2005												
	10/7/2005												
	1/27/2006												
	4/28/2006												-

WELL ID	DATE	1,4- Dichloro- benzene (µg/l)	Dichloro- difluoro- methane (μg/l)	1,1-DCA (μg/l)	1,1-DCE (μg/l)	cis- 1,2-DCE (μg/l)	trans- 1,2-DCE (µg/l)	1,2- Dichloro- propane (µg/l)	cis-1,3- Dichloro- propene (µg/l)	trans-1,3- Dichloro- propene (µg/l)	Hexa- chloro- butadiene (µg/l)	Methylene chloride (μg/l)	Naph- thalen (µg/l)
	7/28/2006												
	10/27/2006												
	1/10/2007												
	4/13/2007												
	7/19/2007												
	10/8/2007												
	1/9/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009												
	7/23/2009												
	2/1/2010												
	8/2/2010												
	1/31/2011												
	4/26/2011												
	7/25/2011												
	10/7/2011												
	1/23/2012												
	4/6/2012												
	7/24/2012												
MW-6	7/18/2002												
	10/7/2002												
	1/6/2003												
	4/7/2003												
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004												
	10/25/2004												
	1/17/2005												
IW-6 cont.	4/6/2005												
	7/8/2005												
	10/7/2005												
	1/27/2006												
	4/28/2006												
	+12012000												

WELL ID	DATE	1,4- Dichloro- benzene (µg/l)	Dichloro- difluoro- methane (μg/l)	1,1-DCA (μg/l)	1,1-DCE (μg/l)	cis- 1,2-DCE (μg/l)	trans- 1,2-DCE (μg/l)	1,2- Dichloro- propane (µg/l)	cis-1,3- Dichloro- propene (µg/l)	trans-1,3- Dichloro- propene (µg/l)	Hexa- chloro- butadiene (μg/l)	Methylene chloride (µg/l)	Naph- thalen (µg/l)
	10/27/2006												
	1/10/2007												
	4/13/2007												
	7/19/2007												
	10/8/2007												
	1/9/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009							-		-		-	
MW-7	7/18/2002												
	10/7/2002												
	1/6/2003					ND<50							ND<1
	4/7/2003												
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004												
	10/25/2004												
	1/17/2005												
	4/6/2005												
	7/8/2005												
	10/7/2005												
	1/27/2006												
	4/28/2006												
	7/28/2006												
	10/27/2006												
	1/10/2007												
	7/19/2007												
	10/8/2007												
IW-7 cont.	1/9/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009												
	7/23/2009												

WELL ID	DATE	1,4- Dichloro- benzene (µg/l)	Dichloro- difluoro- methane (µg/l)	1,1-DCA (µg/l)	1,1-DCE (µg/l)	cis- 1,2-DCE (µg/l)	trans- 1,2-DCE (µg/l)	1,2- Dichloro- propane (µg/l)	cis-1,3- Dichloro- propene (µg/l)	trans-1,3- Dichloro- propene (µg/l)	Hexa- chloro- butadiene (µg/l)	Methylene chloride (μg/l)	Naph- thalene (µg/l)
	2/1/2010							-	-				
	8/2/2010												
	1/31/2011												
	4/26/2011												
	7/25/2011												
	10/7/2011												
	1/23/2012												
	4/6/2012												
	7/24/2012		-				-						
MW-8	1/18/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009												
	7/23/2009												
	2/1/2010												

NOTES:

ND<# = Analyte not detected below indicated practical quantitation limit

-- = Not sampled

μg/L = Micrograms per liter

WELL ID	DATE	n-Propyl- benzene (µg/l)	1,1,2,2- Tetrachloro- ethane (µg/l)	Tetrachloro- ethene (PCE) (μg/l)	Trichloro- trifluoro- ethane (µg/l)	1,2,4- Trichloro- benzene (µg/l)	1,1,1- Trichloro- ethane (µg/l)	1,1,2- Trichloro- ethane (µg/l)	Trichloro- ethene (TCE) (µg/l)	Trichloro- fluoro- methane (μg/l)	1,2,4- Trimethyl- benzene (µg/l)	1,3,5- Trimethyl- benzene (μg/l)	Vinyl chloride (µg/l)
MW-1	7/20/1999												
	9/28/1999										1240	318	
	1/7/2000	371									2210	597	
	3/31/2000												
	7/14/2000			334									
	10/3/2000												
	1/3/2001												
	4/4/2001												
	7/17/2001												
	10/5/2001												
	1/28/2002												
	4/25/2002												
	7/18/2002			ND<0.60									
	10/7/2002												
	1/6/2003												
	4/7/2003												
	7/7/2003			ND<120									
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004		ND<10	ND<10	ND<10	ND<2	ND<10	ND<10	ND<10	ND<10			ND<10
	10/25/2004												
	1/17/2005												
	4/6/2005												
	7/8/2005		ND<0.50	ND<0.50	ND<0.50	ND<20	ND<0.50	ND<0.50	0.73	ND<1.0			ND<0.5
	10/7/2005												
	1/27/2006												
	4/28/2006												
	7/28/2006		ND<0.50	ND<0.50	ND<0.50		ND<0.50	ND<0.50	ND<0.50	ND<0.50			ND<0.5
	10/27/2006												
	1/10/2007												
	4/13/2007												
	7/19/2007		ND<50	ND<50	ND<50		ND<50	ND<50	ND<50	ND<50			ND<50
	1/9/2008												
	4/4/2008												
	7/3/2008		ND<12	ND<12	ND<12		ND<12	ND<12	ND<12	ND<12			ND<12
	10/3/2008												
	1/22/2009												
	4/13/2009												
MW-1 cont.	7/23/2009												

WELL ID	DATE	n-Propyl- benzene (µg/l)	1,1,2,2- Tetrachloro- ethane (µg/l)	Tetrachloro- ethene (PCE) (μg/l)	Trichloro- trifluoro- ethane (µg/l)	1,2,4- Trichloro- benzene (µg/l)	1,1,1- Trichloro- ethane (µg/l)	1,1,2- Trichloro- ethane (µg/l)	Trichloro- ethene (TCE) (µg/l)	Trichloro- fluoro- methane (µg/l)	1,2,4- Trimethyl- benzene (µg/l)	1,3,5- Trimethyl- benzene (µg/l)	Vinyl chloride (µg/l)
	2/1/2010												
	8/2/2010		-										
MW-1B	11/1/2010												
	1/31/2011												
	4/26/2011												
	7/25/2011					_					_		
	10/7/2011												
	1/23/2012												
	4/6/2012												
	7/24/2012		-	-			-			-			-
MW-2	9/28/1999		-										
	4/4/2001												
	7/17/2001												
	7/18/2002												
	10/7/2002												
	1/6/2003												
	4/7/2003												
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004												
	10/25/2004												
	1/17/2005												
	4/6/2005												
	7/8/2005												
	10/7/2005												
	1/27/2006	 											
	4/28/2006												
	7/28/2006												
	10/27/2006												
	1/10/2007												
	4/13/2007												
	7/19/2007												
	10/8/2007												
	1/9/2008												
MW-2 cont.	4/4/2008												
	7/3/2008												

WELL ID	DATE	n-Propyl- benzene (µg/l)	1,1,2,2- Tetrachloro- ethane (µg/l)	Tetrachloro- ethene (PCE) (μg/l)	Trichloro- trifluoro- ethane (µg/l)	1,2,4- Trichloro- benzene (µg/l)	1,1,1- Trichloro- ethane (µg/l)	1,1,2- Trichloro- ethane (µg/l)	Trichloro- ethene (TCE) (μg/l)	Trichloro- fluoro- methane (μg/l)	1,2,4- Trimethyl- benzene (µg/l)	1,3,5- Trimethyl- benzene (μg/l)	Vinyl chloride (µg/l)
	10/3/2008												
	1/22/2009												
	4/13/2009												
	7/23/2009												
	2/1/2010												
	8/2/2010												
MW-2B	11/1/2010												
	1/31/2011												
	4/26/2011												
	7/25/2011												
	10/7/2011												
	1/23/2012												
	4/6/2012												
	7/24/2012								-				
MW-3	9/28/1999												
	4/4/2001												
	7/17/2001												
	7/18/2002												
	10/7/2002												
	1/6/2003												
	4/7/2003												
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004												
	10/25/2004												
	1/17/2005												
	4/6/2005									<u></u>			
	7/8/2005												
	10/7/2005												
	1/27/2006					<u></u>				<u></u>			
	4/28/2006												
	7/28/2006												
	10/27/2006												
W-3 cont.	1/10/2007						-			-			
**-5 COIII.	4/13/2007												
	4/13/200/												

WELL ID	DATE	n-Propyl- benzene (µg/l)	1,1,2,2- Tetrachloro- ethane (µg/l)	Tetrachloro- ethene (PCE) (μg/l)	Trichloro- trifluoro- ethane (μg/l)	1,2,4- Trichloro- benzene (µg/l)	1,1,1- Trichloro- ethane (µg/l)	1,1,2- Trichloro- ethane (µg/l)	Trichloro- ethene (TCE) (µg/l)	Trichloro- fluoro- methane (µg/l)	1,2,4- Trimethyl- benzene (µg/l)	1,3,5- Trimethyl- benzene (µg/l)	Vinyl chloride (µg/l)
	10/8/2007												
	1/9/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009												
	7/23/2009												
	2/1/2010												
	8/2/2010												
MW-3B	11/1/2010												
	1/31/2011												
	4/26/2011												
	7/25/2011												
	10/7/2011												
	1/23/2012												
	4/6/2012												
	7/24/2012		-		-			-			-		
MW-4	9/28/1999												
	4/4/2001												
	7/17/2001												
	7/18/2002												
	10/7/2002												
	1/6/2003												
	4/7/2003												
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004												
	10/25/2004												
	1/17/2005												
	4/6/2005												
	7/8/2005												
MW-4 cont.	10/7/2005												
	1/27/2006												
	4/28/2006												
	7/28/2006												

WELL ID	DATE	n-Propyl- benzene (µg/l)	1,1,2,2- Tetrachloro- ethane (µg/l)	Tetrachloro- ethene (PCE) (μg/l)	Trichloro- trifluoro- ethane (µg/l)	1,2,4- Trichloro- benzene (µg/l)	1,1,1- Trichloro- ethane (µg/l)	1,1,2- Trichloro- ethane (µg/l)	Trichloro- ethene (TCE) (µg/l)	Trichloro- fluoro- methane (µg/l)	1,2,4- Trimethyl- benzene (µg/l)	1,3,5- Trimethyl- benzene (µg/l)	Vinyl chloride (µg/l)
	10/27/2006												
	1/10/2007												
	4/13/2007												
	7/19/2007												
	10/8/2007												
	1/9/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009												
	7/23/2009												
	2/1/2010												
	8/2/2010						-						
MW-4B	11/1/2010												
	1/31/2011												
	4/26/2011												
	7/25/2011												
	10/7/2011												
	1/23/2012												
	4/6/2012												
	7/24/2012												
MW-5	7/18/2002							-					
	10/7/2002												
	1/6/2003			ND<0.50									
	4/7/2003												
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004												
	10/25/2004												
	1/17/2005												
MW-5 cont.	4/6/2005												
	7/8/2005												
	10/7/2005												
	1/27/2006												
	4/28/2006												

1783/006 1	7/28/2006	
1100007	1/10/2007	
### ### #### #### #### #### #### #### ####		
1719/2007	4/13/2007	
108/2007		
19/2008	7/19/2007	
44/2008 44/2008 7/3/2008	10/8/2007	
7/3/2008	1/9/2008	
10/3/2008	4/4/2008	
1/22/2009	7/3/2008	
413/2009 - - - - - - - - -	10/3/2008	
7/23/2009	1/22/2009	
2/1/2010 - - - - - - - - -	4/13/2009	
8/2/2010 - - - - - - - - -	7/23/2009	
8/2/2010 - - - - - - - - -		
1/31/2011		
4/26/2011		
7/25/2011 - - - - - - - - -		
10/7/2011 - - - - - - - - -		
1/23/2012		
MW-6 cont. 4/6/2012		
MW-6 7/18/2002		
MW-6 7/18/2002		
10/7/2002	··- · · ·	
10/7/2002	/W-6 7/18/2002	
1/6/2003		
4/7/2003		
7/7/2003		
10/9/2003		
1/14/2004		
4/28/2004		
7/12/2004		
10/25/2004		
1/17/2005		
MW-6 cont. 4/6/2005		
7/8/2005		
10/7/2005 <td></td> <td></td>		
1/27/2006		
4/28/2006		
7/28/2006		

WELL ID	DATE	n-Propyl- benzene (µg/l)	1,1,2,2- Tetrachloro- ethane (µg/l)	Tetrachloro- ethene (PCE) (μg/l)	Trichloro- trifluoro- ethane (µg/l)	1,2,4- Trichloro- benzene (µg/l)	1,1,1- Trichloro- ethane (μg/l)	1,1,2- Trichloro- ethane (μg/l)	Trichloro- ethene (TCE) (μg/l)	Trichloro- fluoro- methane (μg/l)	1,2,4- Trimethyl- benzene (µg/l)	1,3,5- Trimethyl- benzene (µg/l)	Vinyl chlorid (µg/l)
	10/27/2006												
	1/10/2007												
	4/13/2007												
	7/19/2007												
	10/8/2007												
	1/9/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009												
MW-7	7/18/2002								_				
	10/7/2002												
	1/6/2003			ND<50									
	4/7/2003												
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004												
	10/25/2004												
	1/17/2005												
	4/6/2005												
	7/8/2005												
	10/7/2005												
	1/27/2006												
	4/28/2006												
	7/28/2006												
	10/27/2006												
	1/10/2007												
	7/19/2007												
	10/8/2007												
IW-7 cont.	1/9/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009												
	+/13/2009												

WELL ID	DATE	n-Propyl- benzene (µg/l)	1,1,2,2- Tetrachloro- ethane (µg/l)	Tetrachloro- ethene (PCE) (µg/l)	Trichloro- trifluoro- ethane (μg/l)	1,2,4- Trichloro- benzene (μg/l)	1,1,1- Trichloro- ethane (µg/l)	1,1,2- Trichloro- ethane (µg/l)	Trichloro- ethene (TCE) (μg/l)	Trichloro- fluoro- methane (µg/l)	1,2,4- Trimethyl- benzene (µg/l)	1,3,5- Trimethyl- benzene (μg/l)	Vinyl chloride (µg/l)
	2/1/2010												
	8/2/2010												
	1/31/2011												
	4/26/2011												
	7/25/2011												
	10/7/2011												
	1/23/2012												
	4/6/2012												
	7/24/2012				-								
MW-8	1/18/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009												
	7/23/2009												
	2/1/2010												

NOTES:

ND<# = Analyte not detected below indicated practical quantitation limit

-- = Not sampled

μg/L = Micrograms per liter

WELL ID	DATE	Acena- phthene (μg/l)	Acena- phthylene (svoc) (μg/l)	Anthra- cene (µg/l)	Benzo[a]- anthracene (μg/l)	Benzo[a]- pyrene (µg/l)	Benzo[b]- fluor- anthene (μg/l)	Benzo- [g,h,l]- perylene (μg/l)	Benzo[k]- fluor- anthene (μg/l)	Benzoic Acid (μg/l)	Benzyl Alcohol (μg/l)	Bis(2-chloro- ethoxy) methane (μg/l)	Bis(2-chlor ethyl) ether (μg/l)
MW-1	7/20/1999												
	9/28/1999												
	1/7/2000												
	3/31/2000												
	7/14/2000												
	10/3/2000												
	1/3/2001												
	4/4/2001												
	7/17/2001												
	10/5/2001												
	1/28/2002												
	4/25/2002												
	7/18/2002												
	10/7/2002												
	1/6/2003												
	4/7/2003												
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004	ND<2		ND<2	ND<2	ND<2	ND<2	ND<2	ND<2				
	10/25/2004												
	1/17/2005												
	4/6/2005												
	7/8/2005												
	10/7/2005												
	1/27/2006												
	4/28/2006												
	7/28/2006	ND<10	ND<10	ND<10	ND<10	ND<10	ND<10	ND<10	ND<10	ND<50	ND<10	ND<10	ND<10
	10/27/2006												
	1/10/2007												
	4/13/2007												
	7/19/2007	ND<2.2	ND<2.2	ND<2.2	ND<2.2	ND<2.2	ND<2.2	ND<2.2	ND<2.2	ND<11	ND<2.2	ND<2.2	ND<2.2
	1/9/2008												
	4/4/2008												
	7/3/2008	ND<20	ND<20	ND<20	ND<20	ND<20	ND<20	ND<20	ND<20	ND<100	ND<20	ND<20	ND<20
	10/3/2008												
	1/22/2009												
	4/13/2009												
MW-1 cont.	7/23/2009												

WELL ID	DATE	Acena- phthene (µg/l)	Acena- phthylene (svoc) (μg/l)	Anthra- cene (µg/l)	Benzo[a]- anthracene (µg/l)	Benzo[a]- pyrene (µg/l)	Benzo[b]- fluor- anthene (μg/l)	Benzo- [g,h,l]- perylene (µg/l)	Benzo[k]- fluor- anthene (μg/l)	Benzoic Acid (µg/l)	Benzyl Alcohol (µg/l)	Bis(2-chloro- ethoxy) methane (μg/l)	Bis(2-chlord ethyl) ether (μg/l)
	2/1/2010												
	8/2/2010				-								
MW-1B	11/1/2010												
	1/31/2011												
	4/26/2011												
	7/25/2011												
	10/7/2011												
	1/23/2012												
	4/6/2012												
	7/24/2012												
MW-2	9/28/1999												
	4/4/2001												
	7/17/2001												
	7/18/2002				_								
	10/7/2002								_				
	1/6/2003		-		_								
	4/7/2003												
	7/7/2003			 									
	10/9/2003			 									
	1/14/2004												-
	4/28/2004												
	7/12/2004												
	10/25/2004												
	1/17/2005												
	4/6/2005												
	7/8/2005												
	10/7/2005												
	1/27/2006												
	4/28/2006												
	7/28/2006												
	10/27/2006												
	1/10/2007												
	4/13/2007												
	7/19/2007												
	10/8/2007												
	1/9/2008												
W-2 cont.	4/4/2008												
	7/3/2008												

WELL ID	DATE	Acena- phthene (μg/l)	Acena- phthylene (svoc) (μg/l)	Anthra- cene (µg/l)	Benzo[a]- anthracene (μg/l)	Benzo[a]- pyrene (µg/l)	Benzo[b]- fluor- anthene (μg/l)	Benzo- [g,h,l]- perylene (µg/l)	Benzo[k]- fluor- anthene (μg/l)	Benzoic Acid (μg/l)	Benzyl Alcohol (µg/l)	Bis(2-chloro- ethoxy) methane (μg/l)	Bis(2-chlord ethyl) ether (μg/l)
	10/3/2008												
	1/22/2009												
	4/13/2009												
	7/23/2009												
	2/1/2010												
	8/2/2010												
MW-2B	11/1/2010												
	1/31/2011												
	4/26/2011												
	7/25/2011												
	10/7/2011												
	1/23/2012												
	4/6/2012												
	7/24/2012		-	-	-	-	-	-	-		-		
MW-3	9/28/1999												
	4/4/2001												
	7/17/2001												
	7/18/2002												
	10/7/2002												
	1/6/2003												
	4/7/2003												
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004												
	10/25/2004												
	1/17/2005												
	4/6/2005												
	7/8/2005												
	10/7/2005												
	1/27/2006												
	4/28/2006												
	7/28/2006												
	10/27/2006												
IW-3 cont.	1/10/2007												
0 00111.	4/13/2007												
	7/19/2007												

WELL ID	DATE	Acena- phthene (µg/l)	Acena- phthylene (svoc) (μg/l)	Anthra- cene (µg/l)	Benzo[a]- anthracene (µg/l)	Benzo[a]- pyrene (µg/l)	Benzo[b]- fluor- anthene (μg/l)	Benzo- [g,h,l]- perylene (µg/l)	Benzo[k]- fluor- anthene (μg/l)	Benzoic Acid (µg/l)	Benzyl Alcohol (µg/l)	Bis(2-chloro- ethoxy) methane (μg/l)	Bis(2-chloro ethyl) ether (μg/l)
	10/8/2007												
	1/9/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009												
	7/23/2009												
	2/1/2010												
	8/2/2010												
MW-3B	11/1/2010							_					
	1/31/2011												
	4/26/2011												
	7/25/2011												
	10/7/2011												
	1/23/2012												
	4/6/2012												
	7/24/2012	-	-	-	-	-	-	-	-	-			
MW-4	9/28/1999												
	4/4/2001												
	7/17/2001												
	7/18/2002												
	10/7/2002												
	1/6/2003												
	4/7/2003												
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004												
	10/25/2004												
	1/17/2005												
	4/6/2005												
	7/8/2005												
IW-4 cont.	10/7/2005												
	1/27/2006												
	4/28/2006												
	7/28/2006												

WELL ID	DATE	Acena- phthene (µg/l)	Acena- phthylene (svoc) (µg/l)	Anthra- cene (µg/l)	Benzo[a]- anthracene (µg/l)	Benzo[a]- pyrene (µg/l)	Benzo[b]- fluor- anthene (µg/l)	Benzo- [g,h,l]- perylene (µg/l)	Benzo[k]- fluor- anthene (µg/l)	Benzoic Acid (µg/l)	Benzyl Alcohol (μg/l)	Bis(2-chloro- ethoxy) methane (μg/l)	Bis(2-chloro- ethyl) ether (µg/l)
	10/27/2006												
	1/10/2007												
	4/13/2007												
	7/19/2007												
	10/8/2007												
	1/9/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009												
	7/23/2009												
	2/1/2010												
	8/2/2010		-										
MW-4B	11/1/2010		-										
	1/31/2011												
	4/26/2011												
	7/25/2011												
	10/7/2011												
	1/23/2012												
	4/6/2012												
	7/24/2012		-	-	-	-	-	-	-	-	-	-	-
MW-5	7/18/2002												
	10/7/2002												
	1/6/2003												
	4/7/2003												
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004												
	10/25/2004												
	1/17/2005												
MW-5 cont.	4/6/2005												
-	7/8/2005												
	10/7/2005												
	1/27/2006												
	4/28/2006		<u></u>										
	4/20/2000												

WELL ID	DATE	Acena- phthene (µg/l)	Acena- phthylene (svoc) (μg/l)	Anthra- cene (µg/l)	Benzo[a]- anthracene (μg/l)	Benzo[a]- pyrene (µg/l)	Benzo[b]- fluor- anthene (µg/l)	Benzo- [g,h,l]- perylene (µg/l)	Benzo[k]- fluor- anthene (µg/l)	Benzoic Acid (µg/l)	Benzyl Alcohol (μg/l)	Bis(2-chloro- ethoxy) methane (μg/l)	Bis(2-chloro ethyl) ether (μg/l)
	7/28/2006							-	-				-
	10/27/2006												
	1/10/2007												
	4/13/2007												
	7/19/2007												
	10/8/2007												
	1/9/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009												
	7/23/2009												
	2/1/2010												
	8/2/2010												
	1/31/2011												
	4/26/2011												
	7/25/2011												
	10/7/2011												
	1/23/2012												
	4/6/2012												
	7/24/2012												
MW-6	7/18/2002												
	10/7/2002												
	1/6/2003												
	4/7/2003												
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004												
	10/25/2004												
	1/17/2005												
/IW-6 cont.	4/6/2005												
	7/8/2005												
	10/7/2005												
	1/27/2006												
	4/28/2006												
	7/28/2006												

WELL ID	DATE	Acena- phthene (µg/l)	Acena- phthylene (svoc) (μg/l)	Anthra- cene (µg/l)	Benzo[a]- anthracene (µg/l)	Benzo[a]- pyrene (µg/l)	Benzo[b]- fluor- anthene (μg/l)	Benzo- [g,h,l]- perylene (µg/l)	Benzo[k]- fluor- anthene (μg/l)	Benzoic Acid (µg/l)	Benzyl Alcohol (µg/l)	Bis(2-chloro- ethoxy) methane (μg/l)	Bis(2-chloro- ethyl) ether (µg/l)
	10/27/2006												
	1/10/2007												
	4/13/2007												
	7/19/2007												
	10/8/2007												
	1/9/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009							-					
MW-7	7/18/2002												
	10/7/2002												
	1/6/2003												
	4/7/2003												
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004												
	10/25/2004												
	1/17/2005												
	4/6/2005												
	7/8/2005												
	10/7/2005												
	1/27/2006												
	4/28/2006												
	7/28/2006												
	10/27/2006												
	1/10/2007												
	7/19/2007												
	10/8/2007												
IW-7 cont.	1/9/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009												
	11 1012003												

WELL ID	DATE	Acena- phthene (µg/l)	Acena- phthylene (svoc) (μg/l)	Anthra- cene (µg/l)	Benzo[a]- anthracene (μg/l)	Benzo[a]- pyrene (µg/l)	Benzo[b]- fluor- anthene (μg/l)	Benzo- [g,h,l]- perylene (µg/l)	Benzo[k]- fluor- anthene (μg/l)	Benzoic Acid (µg/l)	Benzyl Alcohol (µg/l)	Bis(2-chloro- ethoxy) methane (μg/l)	Bis(2-chloro- ethyl) ether (µg/l)
	2/1/2010									-			
	8/2/2010												
	1/31/2011												
	4/26/2011												
	7/25/2011												
	10/7/2011												
	1/23/2012												
	4/6/2012												
	7/24/2012				-			-	-				
MW-8	1/18/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009												
	7/23/2009												
	2/1/2010												

NOTES:

ND<# = Analyte not detected below indicated practical quantitation limit

-- = Not sampled

μg/L = Micrograms per liter

WELL ID	DATE	Bis(2-chloro- isopropyl)- ether (μg/l)	Bis(2-ethyl- hexyl) phthalate (μg/l)	4-Bromo- pheny phe- nyl ether (μg/l)	Butyl- benzyl phthalate (µg/l)	4-Chloro- 3-methyl- phenol (μg/l)	4-Chloro- aniline (μg/l)	2-Chloro- naphtha- lene (µg/l)	2-Chloro- phenol (μg/l)	4-Chloro- phenyl phenyl ether (μg/l)	Chrysene (µg/l)	Dibenzo- [a,h]- anthracene (μg/l)	Dibenzo furan (µg/l)
MW-1	7/20/1999			1 1									
	9/28/1999												
	1/7/2000												
	3/31/2000		10										
	7/14/2000												
	10/3/2000		51.6										
	1/3/2001												
	4/4/2001		55										
	7/17/2001		400										
	10/5/2001												
	1/28/2002												
	4/25/2002												
	7/18/2002		120										
	10/7/2002												
	1/6/2003												
	4/7/2003												
	7/7/2003		70										
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004		ND<5								ND<2	ND<3	
	10/25/2004												
	1/17/2005												
	4/6/2005												
	7/8/2005												
	10/7/2005												
	1/27/2006												
	4/28/2006												
	7/28/2006	ND<10	33	ND<10	ND<10	ND<25	ND<10	ND<10	ND<10	ND<10	ND<10	ND<15	ND<10
	10/27/2006												
	1/10/2007												
	4/13/2007												
	7/19/2007	ND<2.2	ND<4.4	ND<2.2	ND<2.2	ND<5.5	ND<2.2	ND<2.2	ND<2.2	ND<2.2	ND<2.2	ND<3.3	ND<2.
	1/9/2008												
	4/4/2008												
	7/3/2008	ND<20	ND<40	ND<20	ND<20	ND<50	ND<20	ND<20	ND<20	ND<20	ND<20	ND<30	ND<20
	10/3/2008												
	1/22/2009												
	4/13/2009												
MW-1 cont.	7/23/2009												

WELL ID	DATE	Bis(2-chloro- isopropyl)- ether (μg/l)	Bis(2-ethyl- hexyl) phthalate (µg/l)	4-Bromo- pheny phe- nyl ether (μg/l)	Butyl- benzyl phthalate (µg/l)	4-Chloro- 3-methyl- phenol (µg/l)	4-Chloro- aniline (µg/l)	2-Chloro- naphtha- lene (µg/l)	2-Chloro- phenol (μg/l)	4-Chloro- phenyl phenyl ether (μg/l)	Chrysene (µg/l)	Dibenzo- [a,h]- anthracene (μg/l)	Dibenzo furan (μg/l)
	2/1/2010												
	8/2/2010												
MW-1B	11/1/2010												
	1/31/2011	<u></u>											
	4/26/2011												
	7/25/2011												
	10/7/2011												
	1/23/2012												
	4/6/2012				-								
	7/24/2012	-		-									
MW-2	9/28/1999												
	4/4/2001												
	7/17/2001												
	7/18/2002												
	10/7/2002												
	1/6/2003												
	4/7/2003												
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004												
	10/25/2004												
	1/17/2005												
	4/6/2005												
	7/8/2005	<u></u>					<u></u>	<u></u>	<u></u>				
	10/7/2005												
	1/27/2006	 			-								
	4/28/2006												
	4/28/2006 7/28/2006												
	10/27/2006												
	1/10/2007												
	4/13/2007												
	7/19/2007												
	10/8/2007												
	1/9/2008												
W-2 cont.	4/4/2008												
	7/3/2008												

WELL ID	DATE	Bis(2-chloro- isopropyl)- ether (μg/l)	Bis(2-ethyl- hexyl) phthalate (μg/l)	4-Bromo- pheny phe- nyl ether (μg/l)	Butyl- benzyl phthalate (µg/l)	4-Chloro- 3-methyl- phenol (μg/l)	4-Chloro- aniline (μg/l)	2-Chloro- naphtha- lene (µg/l)	2-Chloro- phenol (μg/l)	4-Chloro- phenyl phenyl ether (μg/l)	Chrysene (μg/l)	Dibenzo- [a,h]- anthracene (μg/l)	Dibenzo furan (µg/l)
	10/3/2008												
	1/22/2009												
	4/13/2009												
	7/23/2009												
	2/1/2010												
	8/2/2010												
MW-2B	11/1/2010												
	1/31/2011												
	4/26/2011												
	7/25/2011												
	10/7/2011												
	1/23/2012												
	4/6/2012												
	7/24/2012												
MW-3	9/28/1999												
	4/4/2001												
	7/17/2001												
	7/18/2002												
	10/7/2002												
	1/6/2003												
	4/7/2003												
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004												
	10/25/2004												
	1/17/2005												
	4/6/2005					<u></u>							
	7/8/2005												
	10/7/2005					<u></u>							
	1/27/2006					<u></u>		<u></u>					
	4/28/2006												
	7/28/2006												
	10/27/2006												
W-3 cont.	1/10/2007												
TT-0 COIIL.	4/13/2007												
	4/13/200/												

WELL ID	DATE	Bis(2-chloro- isopropyl)- ether (μg/l)	Bis(2-ethyl- hexyl) phthalate (μg/l)	4-Bromo- pheny phe- nyl ether (μg/l)	Butyl- benzyl phthalate (µg/l)	4-Chloro- 3-methyl- phenol (µg/l)	4-Chloro- aniline (µg/l)	2-Chloro- naphtha- lene (µg/l)	2-Chloro- phenol (µg/l)	4-Chloro- phenyl phenyl ether (μg/l)	Chrysene (µg/l)	Dibenzo- [a,h]- anthracene (μg/l)	Dibenzo- furan (µg/l)
	10/8/2007												
	1/9/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009												
	7/23/2009												
	2/1/2010												
	8/2/2010												
MW-3B	11/1/2010												
	1/31/2011												
	4/26/2011												
	7/25/2011												
	10/7/2011												
	1/23/2012												
	4/6/2012												
	7/24/2012												
MW-4	9/28/1999												
	4/4/2001												
	7/17/2001												
	7/18/2002												
	10/7/2002												
	1/6/2003												
	4/7/2003												
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004												
	10/25/2004												
	1/17/2005												
	4/6/2005												
	7/8/2005												
IW-4 cont.	10/7/2005												
	1/27/2006												
	4/28/2006												
	7/28/2006												

WELL ID	DATE	Bis(2-chloro- isopropyl)- ether (μg/l)	Bis(2-ethyl- hexyl) phthalate (µg/l)	4-Bromo- pheny phe- nyl ether (μg/l)	Butyl- benzyl phthalate (µg/l)	4-Chloro- 3-methyl- phenol (μg/l)	4-Chloro- aniline (µg/l)	2-Chloro- naphtha- lene (µg/l)	2-Chloro- phenol (μg/l)	4-Chloro- phenyl phenyl ether (μg/l)	Chrysene (µg/l)	Dibenzo- [a,h]- anthracene (μg/l)	Dibenzo- furan (µg/l)
	10/27/2006												
	1/10/2007												
	4/13/2007												
	7/19/2007												
	10/8/2007												
	1/9/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009												
	7/23/2009												
	2/1/2010												
	8/2/2010												
MM 45	44440040												
MW-4B	11/1/2010												
	1/31/2011												
	4/26/2011												
	7/25/2011												
	10/7/2011												
	1/23/2012												
	4/6/2012												
	7/24/2012		-		-								-
MW-5	7/18/2002												
	10/7/2002												
	1/6/2003		ND<5.0										
	4/7/2003												
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004												
	10/25/2004												
	1/17/2005												
/IW-5 cont.	4/6/2005												
	7/8/2005												
	10/7/2005												
	1/27/2006												
	4/28/2006												

WELL ID	DATE	Bis(2-chloro- isopropyl)- ether (μg/l)	Bis(2-ethyl- hexyl) phthalate (µg/l)	4-Bromo- pheny phe- nyl ether (μg/l)	Butyl- benzyl phthalate (µg/l)	4-Chloro- 3-methyl- phenol (μg/l)	4-Chloro- aniline (µg/l)	2-Chloro- naphtha- lene (µg/l)	2-Chloro- phenol (μg/l)	4-Chloro- phenyl phenyl ether (μg/l)	Chrysene (µg/l)	Dibenzo- [a,h]- anthracene (μg/l)	Dibenzo furan (μg/l)
	7/28/2006												
	10/27/2006												
	1/10/2007												
	4/13/2007												
	7/19/2007												
	10/8/2007												
	1/9/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009												
	7/23/2009												
	2/1/2010												
	8/2/2010												
	1/31/2011												
	4/26/2011												
	7/25/2011												
	10/7/2011												
	1/23/2012												
	4/6/2012												
	7/24/2012												
MW-6	7/18/2002												
	10/7/2002												
	1/6/2003												
	4/7/2003												
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004												
	10/25/2004												
	1/17/2005												
IW-6 cont.	4/6/2005												
	7/8/2005	<u></u>				<u></u>							
	10/7/2005												
	1/27/2006												
		- -		- <u>-</u>									
	4/28/2006												

WELL ID	DATE	Bis(2-chloro- isopropyl)- ether (μg/l)	Bis(2-ethyl- hexyl) phthalate (µg/l)	4-Bromo- pheny phe- nyl ether (μg/l)	Butyl- benzyl phthalate (µg/l)	4-Chloro- 3-methyl- phenol (μg/l)	4-Chloro- aniline (μg/l)	2-Chloro- naphtha- lene (µg/l)	2-Chloro- phenol (μg/l)	4-Chloro- phenyl phenyl ether (μg/l)	Chrysene (µg/l)	Dibenzo- [a,h]- anthracene (μg/l)	Dibenzo furan (μg/l)
	10/27/2006												
	1/10/2007												
	4/13/2007												
	7/19/2007												
	10/8/2007												
	1/9/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009												
MW-7	7/18/2002												
	10/7/2002												
	1/6/2003		ND<5.0										
	4/7/2003												
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004												
	10/25/2004												
	1/17/2005												
	4/6/2005												
	7/8/2005												
	10/7/2005												
	1/27/2006												
	4/28/2006												
	7/28/2006												
	10/27/2006												
	1/10/2007												
	7/19/2007												
	10/8/2007												
/IW-7 cont.	1/9/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009												
	7/23/2009												

WELL ID	DATE	Bis(2-chloro- isopropyl)- ether (μg/l)	Bis(2-ethyl- hexyl) phthalate (µg/l)	4-Bromo- pheny phe- nyl ether (μg/l)	Butyl- benzyl phthalate (µg/l)	4-Chloro- 3-methyl- phenol (µg/l)	4-Chloro- aniline (µg/l)	2-Chloro- naphtha- lene (µg/l)	2-Chloro- phenol (μg/l)	4-Chloro- phenyl phenyl ether (μg/l)	Chrysene (µg/l)	Dibenzo- [a,h]- anthracene (μg/l)	Dibenzo furan (μg/l)
	2/1/2010												
	8/2/2010												
	1/31/2011												
	4/26/2011												
	7/25/2011												
	10/7/2011												
	1/23/2012												
	4/6/2012												
	7/24/2012												
MW-8	1/18/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009												
	7/23/2009												
	2/1/2010												

NOTES:

ND<# = Analyte not detected below indicated practical quantitation limit

-- = Not sampled

 μ g/L = Micrograms per liter

WELL ID	DATE	1,2-Dichloro- benzene (svoc) (µg/l)	1,3-Dichloro- benzene (svoc) (µg/l)	1,4-Dichloro- benzene (svoc) (µg/l)	3,3-Dichloro- benzidine (µg/l)	2,4-Dichloro- phenol (µg/l)	Diethyl phthalate (µg/l)	2,4-Dimethyl- phenol (μg/l)	Dimethyl phthalate (µg/l)	Di-n-butyl phthalate (μg/l)	2,4-Dinitro- phenol (μg/l)	2,4-Dinitro- toluene (μg/l)	2,6-Dinitro toluene (µg/l)
MW-1	7/20/1999									-			
	9/28/1999												
	1/7/2000												
	3/31/2000												
	7/14/2000												
	10/3/2000												
	1/3/2001												
	4/4/2001												
	7/17/2001												
	10/5/2001												
	1/28/2002												
	4/25/2002												
	7/18/2002												
	10/7/2002												
	1/6/2003												
	4/7/2003												
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004												
	10/25/2004												
	1/17/2005												
	4/6/2005												
	7/8/2005												
	10/7/2005												
	1/27/2006												
	4/28/2006												
	7/28/2006	ND<10	ND<10	ND<10	ND<50	ND<10	ND<10	ND<10	ND<10	ND<10	ND<50	ND<10	ND<10
	10/27/2006												
	1/10/2007												
	4/13/2007												
	7/19/2007	ND<2.2	ND<2.2	ND<2.2	ND<11	ND<2.2	ND<2.2	ND<2.2	ND<2.2	ND<2.2	ND<11	ND<2.2	ND<2.2
	1/9/2008												
	4/4/2008												
	7/3/2008	ND<20	ND<20	ND<20	ND<100	ND<20	ND<20	ND<20	ND<20	ND<20	ND<100	ND<20	ND<20
	10/3/2008												
	1/22/2009												
	4/13/2009												
IW-1 cont.	7/23/2009												

WELL ID	DATE	1,2-Dichloro- benzene (svoc) (µg/l)	1,3-Dichloro- benzene (svoc) (µg/l)	1,4-Dichloro- benzene (svoc) (µg/l)	3,3-Dichloro- benzidine (µg/l)	2,4-Dichloro- phenol (μg/l)	Diethyl phthalate (µg/l)	2,4-Dimethyl- phenol (μg/l)	Dimethyl phthalate (µg/l)	Di-n-butyl phthalate (µg/l)	2,4-Dinitro- phenol (μg/l)	2,4-Dinitro- toluene (µg/I)	2,6-Dinitro toluene (µg/l)
	2/1/2010												
	8/2/2010												
MW-1B	11/1/2010												
	1/31/2011												
	4/26/2011												
	7/25/2011												
	10/7/2011												
	1/23/2012												
	4/6/2012	<u></u>		<u></u>									
	7/24/2012						-						
	772472012	-	-	-	-		-	-			-	-	-
MW-2	9/28/1999												
	4/4/2001												
	7/17/2001												
	7/18/2002												
	10/7/2002												
	1/6/2003												
	4/7/2003												
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004												
	10/25/2004												
	1/17/2005												
	4/6/2005												
	7/8/2005												
	10/7/2005				_	_	_				_		
	1/27/2006	<u></u>											
	4/28/2006												
	7/28/2006												
	10/27/2006												
	1/10/2007												
	4/13/2007												
	7/19/2007												
	10/8/2007												
	1/9/2008												
MW-2 cont.	4/4/2008												
	7/3/2008												

WELL ID	DATE	1,2-Dichloro- benzene (svoc) (µg/I)	1,3-Dichloro- benzene (svoc) (µg/l)	1,4-Dichloro- benzene (svoc) (µg/l)	3,3-Dichloro- benzidine (µg/l)	2,4-Dichloro- phenol (μg/l)	Diethyl phthalate (µg/l)	2,4-Dimethyl- phenol (μg/l)	Dimethyl phthalate (µg/l)	Di-n-butyl phthalate (μg/l)	2,4-Dinitro- phenol (μg/l)	2,4-Dinitro- toluene (μg/l)	2,6-Dinitr toluene (µg/l)
	10/3/2008					-					-		-
	1/22/2009												
	4/13/2009												
	7/23/2009												
	2/1/2010												
	8/2/2010					-							
MW-2B	11/1/2010												
	1/31/2011												
	4/26/2011												
	7/25/2011												
	10/7/2011												
	1/23/2012												
	4/6/2012												
	7/24/2012												
MW-3	9/28/1999												
	4/4/2001												
	7/17/2001												
	7/18/2002												
	10/7/2002												
	1/6/2003												
	4/7/2003												
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004											<u></u>	
	10/25/2004												
	1/17/2005												
	4/6/2005												
	7/8/2005												
	10/7/2005												
	1/27/2006											<u></u>	
	4/28/2006												
	7/28/2006								_				
	10/27/2006												
IW-3 cont.	1/10/2007												
144-3 COIII.	4/13/2007										-		
	4/13/2007												

WELL ID	DATE	1,2-Dichloro- benzene (svoc) (μg/l)	1,3-Dichloro- benzene (svoc) (µg/l)	1,4-Dichloro- benzene (svoc) (µg/l)	3,3-Dichloro- benzidine (µg/l)	2,4-Dichloro- phenol (μg/l)	Diethyl phthalate (µg/l)	2,4-Dimethyl- phenol (μg/l)	Dimethyl phthalate (µg/l)	Di-n-butyl phthalate (μg/l)	2,4-Dinitro- phenol (μg/l)	2,4-Dinitro- toluene (µg/l)	2,6-Dinitro toluene (µg/l)
	10/8/2007												
	1/9/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009												
	7/23/2009												
	2/1/2010												
	8/2/2010												
MW-3B	11/1/2010									_			
	1/31/2011												
	4/26/2011												
	7/25/2011												
	10/7/2011												
	1/23/2012												
	4/6/2012												
	7/24/2012												
MW-4	9/28/1999												
	4/4/2001												
	7/17/2001												
	7/18/2002												
	10/7/2002												
	1/6/2003												
	4/7/2003												
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004												
	10/25/2004												
	1/17/2005												
	4/6/2005												
	7/8/2005												
IW-4 cont.	10/7/2005												
	1/27/2006												
	4/28/2006												
	1,20,2000												

WELL ID	DATE	1,2-Dichloro- benzene (svoc) (µg/I)	1,3-Dichloro- benzene (svoc) (µg/I)	1,4-Dichloro- benzene (svoc) (µg/l)	3,3-Dichloro- benzidine (µg/l)	2,4-Dichloro- phenol (μg/l)	Diethyl phthalate (µg/l)	2,4-Dimethyl- phenol (μg/l)	Dimethyl phthalate (µg/l)	Di-n-butyl phthalate (µg/l)	2,4-Dinitro- phenol (μg/l)	2,4-Dinitro- toluene (µg/l)	2,6-Dinitro- toluene (µg/l)
	10/27/2006												
	1/10/2007												
	4/13/2007												
	7/19/2007												
	10/8/2007												
	1/9/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009												
	7/23/2009												
	2/1/2010												
	8/2/2010					-				-			
MW-4B	11/1/2010												
	1/31/2011												
	4/26/2011												
	7/25/2011												
	10/7/2011												
	1/23/2012												
	4/6/2012												
	7/24/2012			-				-					
MW-5	7/18/2002												
	10/7/2002												
	1/6/2003												
	4/7/2003												
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004												
	10/25/2004												
	1/17/2005												
IW-5 cont.	4/6/2005												
	7/8/2005												
	10/7/2005												
	1/27/2006												
	4/28/2006												

WELL ID	DATE	1,2-Dichloro- benzene (svoc) (µg/l)	1,3-Dichloro- benzene (svoc) (µg/l)	1,4-Dichloro- benzene (svoc) (µg/l)	3,3-Dichloro- benzidine (µg/l)	2,4-Dichloro- phenol (µg/l)	Diethyl phthalate (µg/l)	2,4-Dimethyl- phenol (µg/l)	Dimethyl phthalate (µg/l)	Di-n-butyl phthalate (µg/l)	2,4-Dinitro- phenol (µg/l)	2,4-Dinitro- toluene (µg/l)	2,6-Dinitro- toluene (μg/l)
	7/28/2006												
	10/27/2006												
	1/10/2007												
	4/13/2007												
	7/19/2007												
	10/8/2007												
	1/9/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009												
	7/23/2009												
	2/1/2010												
	8/2/2010												
	1/31/2011												
	4/26/2011												
	7/25/2011												
	10/7/2011												
	1/23/2012												
	4/6/2012												
	7/24/2012												
MW-6	7/18/2002												
	10/7/2002												
	1/6/2003												
	4/7/2003												
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004												
	10/25/2004												
	1/17/2005												
MW-6 cont.	4/6/2005	<u></u>											
5 50116.	7/8/2005												
	10/7/2005			-									
	1/27/2006												
	4/28/2006												
	7/28/2006												

WELL ID	DATE	1,2-Dichloro- benzene (svoc) (µg/I)	1,3-Dichloro- benzene (svoc) (µg/l)	1,4-Dichloro- benzene (svoc) (µg/l)	3,3-Dichloro- benzidine (µg/l)	2,4-Dichloro- phenol (μg/l)	Diethyl phthalate (µg/l)	2,4-Dimethyl- phenol (μg/l)	Dimethyl phthalate (µg/l)	Di-n-butyl phthalate (μg/l)	2,4-Dinitro- phenol (μg/l)	2,4-Dinitro- toluene (µg/l)	2,6-Dinitro toluene (µg/l)
	10/27/2006												
	1/10/2007												
	4/13/2007												
	7/19/2007												
	10/8/2007												
	1/9/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009	-				-				-			
MW-7	7/18/2002			_								_	
	10/7/2002												
	1/6/2003												
	4/7/2003												
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004												
	10/25/2004												
	1/17/2005												
	4/6/2005												
	7/8/2005												
	10/7/2005												
	1/27/2006												
	4/28/2006												
	7/28/2006												
	10/27/2006												
	1/10/2007												
	7/19/2007												
	10/8/2007												
IW-7 cont.	1/9/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009												
	11012003												

WELL ID	DATE	1,2-Dichloro- benzene (svoc) (µg/l)	1,3-Dichloro- benzene (svoc) (µg/l)	1,4-Dichloro- benzene (svoc) (µg/l)	3,3-Dichloro- benzidine (µg/l)	2,4-Dichloro- phenol (µg/l)	Diethyl phthalate (µg/l)	2,4-Dimethyl- phenol (μg/l)	Dimethyl phthalate (µg/l)	Di-n-butyl phthalate (µg/l)	2,4-Dinitro- phenol (µg/l)	2,4-Dinitro- toluene (µg/l)	2,6-Dinitro- toluene (µg/l)
	2/1/2010												
	8/2/2010												
	1/31/2011												
	4/26/2011												
	7/25/2011												
	10/7/2011												
	1/23/2012												
	4/6/2012												
	7/24/2012					-							
MW-8	1/18/2008					_							
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009												
	7/23/2009												
	2/1/2010												

NOTES:

ND<# = Analyte not detected below indicated practical quantitation limit

-- = Not sampled

μg/L = Micrograms per liter

	DATE	Di-n-octyl phthalate (µg/l)	Fluoran- thene (µg/l)	Fluorene (µg/l)	chloro- benzene (µg/l)	HCBD (svoc) (µg/l)	Hexachloro cyclopenta- diene (µg/l)	Hexachloro -ethane (µg/l)	[1,2,3-c,d] pyrene (µg/l)	Isophorone (μg/l)	4,6-dinitro- phenol (μg/l)	naphtha- lene (μg/l)	2-Methy phenol (µg/l)
MW-1	7/20/1999		-									240	
	9/28/1999											87.4	26.4
	1/7/2000											315	
	3/31/2000											73	31
	7/14/2000											300	
	10/3/2000											98.1	
	1/3/2001											180	
	4/4/2001											78	
	7/17/2001											290	47
	10/5/2001												
	1/28/2002												
	4/25/2002												
	7/18/2002											420	13
	10/7/2002												
	1/6/2003												
	4/7/2003												
	7/7/2003											260	ND<5.
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004		ND<2	ND<2					ND<2				
	10/25/2004												
	1/17/2005												
	4/6/2005												
	7/8/2005												
	10/7/2005				_		_			_	_		
	1/27/2006												
	4/28/2006									<u></u>			
	7/28/2006	ND<10	ND<10	ND<10	ND<10	ND<5.0	ND<10	ND<10	ND<10	ND<10		280	ND<1
	10/27/2006												
	1/10/2007												
	4/13/2007												
	7/19/2007	ND<2.2	ND<2.2	ND<2.2	ND<2.2	ND<1.1	ND<2.2	ND<2.2	ND<2.2	ND<2.2	ND<11	230	29
	1/9/2008												
	4/4/2008												
	7/3/2008	 ND<20	 ND<20	 ND<20	ND<20	ND<20	 ND<20	 ND<20	ND<20	ND<20	 ND<100	270	ND<2
	10/3/2008	ND<20 	ND<20 	ND<20 	ND<20	ND<20 	ND<20	ND<20	ND~20 	ND<20	ND<100	270 	ND^2
	1/22/2009												
/IW-1 cont.	4/13/2009 7/23/2009												

2/1/2010 8/2/2010 MW-1B 11/1/2010 1/31/2011 4/26/2011 7/25/2011 10/7/2011 1/23/2012 4/6/2012 7/24/2012 MW-2 9/28/1999 4/4/2001 7/17/2001 7/18/2002 10/7/2002 1/6/2003 4/7/2003 10/9/2003 1/14/2004 4/28/2004 7/12/2004 10/25/2004 1/17/2005 4/6/2005 7/8/2005 10/7/2005 1/27/2006 4/28/2006 1/28/2006 1/28/2006 1/28/2006 1/28/2006 1/28/2006 1/28/2006 1/28/2006 1/28/2006 1/28/2006 1/28/2006 1/28/2006 1/28/2006 1/28/2006 1/28/2006 1/28/2006 1/28/2006 1/28/2007 1/19/2007	Di-n-octyl phthalate (µg/l)	Fluoran- thene (µg/l)	Fluorene (µg/l)	Hexa- chloro- benzene (µg/l)	HCBD (svoc) (µg/l)	Hexachloro cyclopenta- diene (µg/l)	Hexachloro -ethane (µg/l)	Indeno- [1,2,3-c,d] pyrene (µg/l)	Isophorone (μg/l)	2-Methyl- 4,6-dinitro- phenol (μg/l)	2-Methyl- naphtha- lene (µg/l)	2-Methy phenol (µg/l)
MW-1B 11/1/2010 1/31/2011 4/26/2011 7/25/2011 10/7/2011 1/23/2012 4/6/2012 7/24/2012 MW-2 9/28/1999 4/4/2001 7/17/2001 7/18/2002 10/7/2002 1/6/2003 4/7/2003 7/7/2003 10/9/2003 1/14/2004 4/28/2004 7/12/2004 10/25/2004 10/25/2004 1/17/2005 4/6/2005 7/8/2005 10/7/2006 4/28/2006 7/28/2006 10/27/2006 1/10/2007 4/13/2007 7/19/2007												
1/31/2011 4/26/2011 7/25/2011 10/7/2011 11/23/2012 4/6/2012 7/24/2012 MW-2 9/28/1999 4/4/2001 7/18/2002 10/7/2002 11/6/2003 4/7/2003 11/14/2004 4/28/2004 7/12/2004 10/25/2004 11/17/2005 4/6/2005 7/8/2005 10/7/2005 11/27/2006 11/27/2006 11/0/2007 4/13/2007 7/19/2007			-						-			
1/31/2011 4/26/2011 7/25/2011 10/7/2011 11/23/2012 4/6/2012 7/24/2012 MW-2 9/28/1999 4/4/2001 7/17/2001 7/18/2002 10/7/2002 1/6/2003 4/7/2003 10/9/2003 11/14/2004 4/28/2004 7/12/2004 10/25/2004 1/17/2005 4/6/2005 7/8/2005 10/7/2005 11/27/2006 4/28/2006 7/28/2006 10/27/2006 1/10/2007 4/13/2007 7/19/2007												
4/26/2011 7/25/2011 10/7/2011 11/23/2012 4/6/2012 7/24/2012 MW-2 9/28/1999 4/4/2001 7/17/2001 7/18/2002 10/7/2002 1/6/2003 4/7/2003 10/9/2003 11/14/2004 4/28/2004 7/12/2004 10/25/2004 1/17/2005 4/6/2005 7/8/2005 10/7/2005 11/27/2006 4/28/2006 10/27/2006 11/0/2007 4/13/2007 7/19/2007												
7/25/2011 10/7/2011 1/23/2012 4/6/2012 7/24/2012 MW-2 9/28/1999 4/4/2001 7/17/2001 7/18/2002 10/7/2002 1/6/2003 4/7/2003 7/7/2003 10/9/2003 1/14/2004 4/28/2004 7/12/2004 10/25/2004 11/17/2005 4/6/2005 7/8/2005 10/7/2005 1/27/2006 4/28/2006 10/27/2006 1/10/2007 4/13/2007 7/19/2007												
10/7/2011 1/23/2012 4/6/2012 7/24/2012 MW-2 9/28/1999 4/4/2001 7/17/2001 7/18/2002 10/7/2002 1/6/2003 4/7/2003 10/9/2003 1/14/2004 4/28/2004 7/12/2004 10/25/2004 1/17/2005 1/6/2005 7/8/2005 1/27/2006 4/28/2006 10/27/2006 11/0/2007 4/13/2007												
1/23/2012 4/6/2012 7/24/2012 MW-2 9/28/1999 4/4/2001 7/17/2001 7/18/2002 10/7/2002 1/6/2003 4/7/2003 10/9/2003 10/9/2003 11/14/2004 4/28/2004 7/12/2004 10/25/2004 1/17/2005 1/6/2005 7/8/2005 10/7/2006 4/28/2006 10/27/2006 11/10/2007 4/13/2007 7/19/2007												
4/6/2012 7/24/2012 MW-2 9/28/1999 4/4/2001 7/17/2001 7/18/2002 10/7/2002 1/6/2003 4/7/2003 1/14/2004 4/28/2004 7/12/2004 10/25/2004 1/17/2005 1/6/2005 7/8/2005 1/07/2006 1/27/2006 1/27/2006 1/10/2007 4/13/2007												
7/24/2012 MW-2 9/28/1999 4/4/2001 7/17/2001 7/18/2002 10/7/2002 1/6/2003 4/7/2003 1/7/2003 10/9/2003 1/14/2004 4/28/2004 7/12/2004 10/25/2004 1/17/2005 4/6/2005 7/8/2005 1/07/2005 1/27/2006 4/28/2006 10/27/2006 11/0/2007 4/13/2007				_		_		_		_		
MW-2 9/28/1999 4/4/2001 7/17/2001 7/18/2002 10/7/2002 11/6/2003 4/7/2003 10/9/2003 11/4/2004 4/28/2004 7/12/2004 10/25/2004 1/17/2005 4/6/2005 7/8/2005 10/7/2005 11/27/2006 4/28/2006 10/27/2006 11/10/2007 4/13/2007 7/19/2007												
4/4/2001 7/17/2001 7/18/2002 10/7/2002 1/6/2003 4/7/2003 10/9/2003 11/4/2004 4/28/2004 7/12/2004 10/25/2004 11/17/2005 4/6/2005 7/8/2005 10/7/2006 4/28/2006 10/27/2006 11/10/2007 4/13/2007 7/19/2007	-		-	-		-	-	-	-	-	-	
7/17/2001 7/18/2002 10/7/2002 1/6/2003 4/7/2003 7/7/2003 10/9/2003 1/14/2004 4/28/2004 7/12/2004 10/25/2004 11/17/2005 4/6/2005 7/8/2005 10/7/2006 4/28/2006 10/27/2006 11/10/2007 4/13/2007 7/19/2007												
7/18/2002 10/7/2002 1/6/2003 4/7/2003 7/7/2003 10/9/2003 11/4/2004 4/28/2004 7/12/2004 10/25/2004 11/17/2005 4/6/2005 7/8/2005 10/7/2006 4/28/2006 10/27/2006 10/27/2006 11/10/2007 4/13/2007 7/19/2007												
10/7/2002 1/6/2003 4/7/2003 7/7/2003 10/9/2003 1/14/2004 4/28/2004 7/12/2004 10/25/2004 1/17/2005 7/8/2005 7/8/2005 1/27/2006 4/28/2006 7/28/2006 10/27/2006 1/10/2007 4/13/2007 7/19/2007												
1/6/2003 4/7/2003 7/7/2003 10/9/2003 11/4/2004 4/28/2004 7/12/2004 10/25/2004 11/17/2005 4/6/2005 7/8/2005 10/7/2006 4/28/2006 7/28/2006 10/27/2006 11/10/2007 4/13/2007 7/19/2007												
4/7/2003 7/7/2003 10/9/2003 11/4/2004 4/28/2004 7/12/2004 10/25/2004 1/17/2005 4/6/2005 7/8/2005 10/7/2006 4/28/2006 10/27/2006 10/27/2006 11/10/2007 4/13/2007 7/19/2007												
7/7/2003 10/9/2003 11/14/2004 4/28/2004 7/12/2004 10/25/2004 11/17/2005 4/6/2005 7/8/2005 10/7/2005 1/27/2006 4/28/2006 7/28/2006 10/27/2006 11/10/2007 4/13/2007												
10/9/2003 1/14/2004 4/28/2004 7/12/2004 10/25/2004 1/17/2005 4/6/2005 7/8/2005 10/7/2006 4/28/2006 7/28/2006 10/27/2006 1/10/2007 4/13/2007 7/19/2007												
1/14/2004 4/28/2004 7/12/2004 10/25/2004 1/17/2005 4/6/2005 7/8/2005 10/7/2006 4/28/2006 7/28/2006 10/27/2006 1/10/2007 4/13/2007 7/19/2007												
4/28/2004 7/12/2004 10/25/2004 1/17/2005 4/6/2005 7/8/2005 10/7/2005 1/27/2006 4/28/2006 7/28/2006 10/27/2006 1/10/2007 4/13/2007												
7/12/2004 10/25/2004 1/17/2005 4/6/2005 7/8/2005 10/7/2005 1/27/2006 4/28/2006 7/28/2006 10/27/2006 1/10/2007 4/13/2007 7/19/2007												
10/25/2004 1/17/2005 4/6/2005 7/8/2005 10/7/2005 1/27/2006 4/28/2006 7/28/2006 10/27/2006 1/10/2007 4/13/2007 7/19/2007												
10/25/2004 1/17/2005 4/6/2005 7/8/2005 10/7/2005 1/27/2006 4/28/2006 7/28/2006 10/27/2006 1/10/2007 4/13/2007 7/19/2007												
1/17/2005 4/6/2005 7/8/2005 10/7/2005 1/27/2006 4/28/2006 7/28/2006 10/27/2006 1/10/2007 4/13/2007 7/19/2007												
4/6/2005 7/8/2005 10/7/2005 1/27/2006 4/28/2006 7/28/2006 10/27/2006 1/10/2007 4/13/2007 7/19/2007												
7/8/2005 10/7/2005 1/27/2006 4/28/2006 7/28/2006 10/27/2006 1/10/2007 4/13/2007 7/19/2007												
10/7/2005 1/27/2006 4/28/2006 7/28/2006 10/27/2006 1/10/2007 4/13/2007 7/19/2007												
1/27/2006 4/28/2006 7/28/2006 10/27/2006 1/10/2007 4/13/2007 7/19/2007												
4/28/2006 7/28/2006 10/27/2006 1/10/2007 4/13/2007 7/19/2007				_		_	_			_		
7/28/2006 10/27/2006 1/10/2007 4/13/2007 7/19/2007												
10/27/2006 1/10/2007 4/13/2007 7/19/2007												
1/10/2007 4/13/2007 7/19/2007												
4/13/2007 7/19/2007					 							
7/19/2007												-
10/8/2007												
1/9/2008												
W-2 cont. 4/4/2008 7/3/2008												

WELL ID	DATE	Di-n-octyl phthalate (μg/l)	Fluoran- thene (µg/l)	Fluorene (μg/l)	Hexa- chloro- benzene (µg/l)	HCBD (svoc) (µg/l)	Hexachloro cyclopenta- diene (µg/l)	Hexachloro -ethane (μg/l)	Indeno- [1,2,3-c,d] pyrene (µg/l)	Isophorone (μg/I)	2-Methyl- 4,6-dinitro- phenol (μg/l)	2-Methyl- naphtha- lene (µg/l)	2-Methyl phenol (µg/l)
	10/3/2008												
	1/22/2009												
	4/13/2009												
	7/23/2009												
	2/1/2010												
	8/2/2010												
MW-2B	11/1/2010												
	1/31/2011												
	4/26/2011												
	7/25/2011												
	10/7/2011												
	1/23/2012												
	4/6/2012												
	7/24/2012												
MW-3	9/28/1999												
	4/4/2001												
	7/17/2001												
	7/18/2002												
	10/7/2002												
	1/6/2003												
	4/7/2003												
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004												
	10/25/2004												
	1/17/2005												
	4/6/2005												
	7/8/2005												
	10/7/2005												
	1/27/2006												
	4/28/2006												
	7/28/2006										_		
	10/27/2006												
W-3 cont.	1/10/2007												
***-5 COIIL.	4/13/2007											 	
	4/13/2007												

108/2007	WELL ID	DATE	Di-n-octyl phthalate (µg/l)	Fluoran- thene (µg/l)	Fluorene (μg/l)	Hexa- chloro- benzene (μg/l)	HCBD (svoc) (µg/l)	Hexachloro cyclopenta- diene (μg/l)	Hexachloro -ethane (μg/l)	Indeno- [1,2,3-c,d] pyrene (µg/l)	Isophorone (μg/l)	2-Methyl- 4,6-dinitro- phenol (μg/l)	2-Methyl- naphtha- lene (µg/l)	2-Methyl phenol (µg/l)
### 44/2008		10/8/2007						-						
7/3/2008		1/9/2008												
10/3/2008		4/4/2008												
1/22/2009		7/3/2008												
### ### #### #########################		10/3/2008												
7/33/2009		1/22/2009												
2/1/2010		4/13/2009												
2/1/2010		7/23/2009												
MW-3B 11/1/2010														
1/31/2011		8/2/2010												
1/31/2011	MW-3B	11/1/2010												
A 26/2011 - - - - - - - - -														
7725/2011														
10/7/2011														
1/23/2012														
### ### #### #########################														
MW-4 9/28/1999														
4/4/2001														
4/4/2001	MW-4	9/28/1999												
7/17/2001														
7/18/2002														
10/7/2002						_				_	_			
1/6/2003														
4/7/2003														
7/7/2003														
10/9/2003														
1/14/2004														
4/28/2004														
7/12/2004														
10/25/2004														
1/17/2005														
4/6/2005														
7/8/2005														
/IW-4 cont. 10/7/2005														
1/27/2006	MW-4 cont													
4/28/2006	TTT-4 COIIL.													
		4/28/2006 7/28/2006		 					 					

WELL ID	DATE	Di-n-octyl phthalate (μg/l)	Fluoran- thene (µg/l)	Fluorene (μg/l)	Hexa- chloro- benzene (μg/l)	HCBD (svoc) (µg/l)	Hexachloro cyclopenta- diene (µg/l)	Hexachloro -ethane (μg/l)	Indeno- [1,2,3-c,d] pyrene (µg/l)	Isophorone (μg/l)	2-Methyl- 4,6-dinitro- phenol (μg/l)	2-Methyl- naphtha- lene (µg/l)	2-Methyl- phenol (μg/l)
	10/27/2006				-			-			-		
	1/10/2007												
	4/13/2007												
	7/19/2007												
	10/8/2007												
	1/9/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009												
	7/23/2009												
	2/1/2010												
	8/2/2010			-						-			
MW-4B	11/1/2010												
	1/31/2011												
	4/26/2011												
	7/25/2011												
	10/7/2011												
	1/23/2012												
	4/6/2012												
	7/24/2012												
MW-5	7/18/2002												
	10/7/2002												
	1/6/2003											ND<5.0	ND<5.0
	4/7/2003												
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004												
	10/25/2004												
	1/17/2005												
IW-5 cont.	4/6/2005												
····	7/8/2005												
	10/7/2005												
	1/27/2006												
	4/28/2006												

WELL ID	DATE	Di-n-octyl phthalate (μg/l)	Fluoran- thene (µg/l)	Fluorene (μg/l)	Hexa- chloro- benzene (μg/l)	HCBD (svoc) (µg/l)	Hexachloro cyclopenta- diene (µg/l)	Hexachloro -ethane (µg/l)	Indeno- [1,2,3-c,d] pyrene (µg/l)	Isophorone (μg/l)	2-Methyl- 4,6-dinitro- phenol (μg/l)	2-Methyl- naphtha- lene (µg/l)	2-Methy phenol (µg/l)
	7/28/2006												-
	10/27/2006												
	1/10/2007												
	4/13/2007												
	7/19/2007												
	10/8/2007												
	1/9/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009												
	7/23/2009												
	2/1/2010												
	8/2/2010												
	1/31/2011												
	4/26/2011												
	7/25/2011												
	10/7/2011												
	1/23/2012												
	4/6/2012												
	7/24/2012												
	772472012												-
MW-6	7/18/2002												
10100-0	10/7/2002				_				_	_	_		
	1/6/2003				-					-	-		
	4/7/2003												
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004												
	10/25/2004												-
	1/17/2005												
MW-6 cont.	4/6/2005												
	7/8/2005												-
	10/7/2005												
	1/27/2006												
	4/28/2006												
	7/28/2006												

WELL ID	DATE	Di-n-octyl phthalate (µg/l)	Fluoran- thene (µg/l)	Fluorene (μg/l)	Hexa- chloro- benzene (µg/l)	HCBD (svoc) (µg/l)	Hexachloro cyclopenta- diene (μg/l)	Hexachloro -ethane (µg/l)	Indeno- [1,2,3-c,d] pyrene (µg/l)	Isophorone (μg/l)	2-Methyl- 4,6-dinitro- phenol (μg/l)	2-Methyl- naphtha- lene (µg/l)	2-Methy pheno (µg/l)
	10/27/2006												
	1/10/2007												
	4/13/2007												
	7/19/2007												
	10/8/2007												
	1/9/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009				-								
MW-7	7/18/2002												
	10/7/2002												
	1/6/2003											ND<5.0	ND<5.0
	4/7/2003												
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004												
	10/25/2004												
	1/17/2005												
	4/6/2005												
	7/8/2005												
	10/7/2005												
	1/27/2006												
	4/28/2006												
	7/28/2006												
	10/27/2006												
	1/10/2007												
	7/19/2007												
	10/8/2007												
IW-7 cont.	1/9/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009												
	7/23/2009												

WELL ID	DATE	Di-n-octyl phthalate (µg/l)	Fluoran- thene (µg/l)	Fluorene (µg/l)	Hexa- chloro- benzene (µg/l)	HCBD (svoc) (µg/l)	Hexachloro cyclopenta- diene (μg/l)	Hexachloro -ethane (µg/l)	Indeno- [1,2,3-c,d] pyrene (µg/l)	Isophorone (μg/l)	2-Methyl- 4,6-dinitro- phenol (µg/l)	2-Methyl- naphtha- lene (µg/l)	2-Methyl- phenol (µg/l)
	2/1/2010	-			-				-				
	8/2/2010												
	1/31/2011												
	4/26/2011												
	7/25/2011												
	10/7/2011												
	1/23/2012												
	4/6/2012												
	7/24/2012									-			
MW-8	1/18/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009												
	7/23/2009												
	2/1/2010												

NOTES:

ND<# = Analyte not detected below indicated practical quantitation limit

-- = Not sampled

μg/L = Micrograms per liter

WELL ID	DATE	4-Methyl- phenol (μg/l)	Naphtha- lene (svoc) (μg/l)	2-Nitro- aniline (µg/l)	3-Nitro- aniline (μg/l)	4-Nitro- aniline (µg/l)	Nitro- benzene (µg/l)	2-Nitro- phenol (µg/l)	4-Nitro- phenol (μg/l)	N-nitrosodi- n-propyl- amine (μg/l)	N-Nitro- sodiphenyl- amine (μg/l)	Penta- chloro- phenol (µg/l)	Phen- anthren (µg/l)
MW-1	7/20/1999	27											
	9/28/1999	35.6											
	1/7/2000												
	3/31/2000	18											
	7/14/2000												
	10/3/2000	28.9											
	1/3/2001												
	4/4/2001												
	7/17/2001	25											
	10/5/2001												
	1/28/2002												
	4/25/2002												
	7/18/2002	25											
	10/7/2002												
	1/6/2003												
	4/7/2003												
	7/7/2003	22											
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004												ND<2
	10/25/2004												
	1/17/2005												
	4/6/2005												
	7/8/2005												
	10/7/2005												
	1/27/2006												
	4/28/2006												
	7/28/2006		660	ND<10	ND<10	ND<25	ND<10	ND<10	ND<10	ND<10	ND<10	ND<50	ND<10
	10/27/2006												
	1/10/2007												
	4/13/2007												
	7/19/2007		770	ND<2.2	ND<2.2	ND<5.5	ND<2.2	ND<2.2	ND<2.2	ND<2.2	ND<2.2	ND<11	ND<2.
	1/9/2008												
	4/4/2008												
	7/3/2008		750	ND<20	ND<20	ND<50	ND<20	ND<20	ND<20	ND<20	ND<20	ND<100	ND<20
	10/3/2008												
	1/22/2009												
	4/13/2009												
MW-1 cont.	7/23/2009												

WELL ID	DATE	4-Methyl- phenol (μg/l)	Naphtha- lene (svoc) (µg/l)	2-Nitro- aniline (µg/l)	3-Nitro- aniline (µg/l)	4-Nitro- aniline (µg/l)	Nitro- benzene (µg/l)	2-Nitro- phenol (µg/l)	4-Nitro- phenol (μg/l)	N-nitrosodi- n-propyl- amine (µg/l)	N-Nitro- sodiphenyl- amine (µg/l)	Penta- chloro- phenol (µg/l)	Phen- anthren (µg/l)
	2/1/2010												
	8/2/2010												
MW-1B	11/1/2010												
	1/31/2011												
	4/26/2011												
	7/25/2011												
	10/7/2011		_										
	1/23/2012												
	4/6/2012		-										
	7/24/2012	-		-		-			-	-	-	-	
MW-2	9/28/1999												
	4/4/2001												
	7/17/2001												
	7/18/2002												
	10/7/2002												
	1/6/2003												
	4/7/2003												
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004												
	10/25/2004												
	1/17/2005												
	4/6/2005												
	7/8/2005							<u></u>					
	10/7/2005												
	1/27/2006		-										
	4/28/2006												
	4/28/2006 7/28/2006												
	10/27/2006												
	1/10/2007												
	4/13/2007												
	7/19/2007												
	10/8/2007												
	1/9/2008												
W-2 cont.	4/4/2008												
	7/3/2008												

10/32/008	WELL ID	DATE	4-Methyl- phenol (µg/l)	Naphtha- lene (svoc) (µg/l)	2-Nitro- aniline (µg/l)	3-Nitro- aniline (µg/l)	4-Nitro- aniline (μg/l)	Nitro- benzene (µg/l)	2-Nitro- phenol (µg/l)	4-Nitro- phenol (μg/l)	N-nitrosodi- n-propyl- amine (μg/l)	N-Nitro- sodiphenyl- amine (µg/l)	Penta- chloro- phenol (µg/l)	Phen- anthrene (µg/l)
### 4/13/2009		10/3/2008		-							-	-		
MW-2B		1/22/2009												
MW-2B		4/13/2009												
MW-2B 11/1/2010 - - - - - - - - -		7/23/2009												
MW-2B		2/1/2010												
1/31/2011		8/2/2010						-		-		-		
1/31/2011	MW-2B	11/1/2010												
7/25/2011		1/31/2011												
7/25/2011														
10/7/2011														
1/23/2012														
MW-3 9/28/1999 - - - - -														
MW-3 9/28/1999														
4/4/2001				-	-		-	-	-	-		-		
4/4/2001	MW-3	0/28/1000	_	_	_	_	_	_		_	_	_		
7/17/2001	11111-0													
7/18/2002														
10/7/2002														
1/6/2003														
4/7/2003														
7/7/2003														
10/9/2003														
1/14/2004													_	
4/28/2004													_	_
7/12/2004														
10/25/2004														
1/17/2005														
4/6/2005														
7/8/2005														
10/7/2005														
1/27/2006														
4/28/2006														
7/28/2006														
10/27/2006														
MW-3 cont. 1/10/2007														
	MM 3 cont													
	vivv-3 COIIL.													
4/13/2007		4/13/2007												

WELL ID	DATE	4-Methyl- phenol (μg/l)	Naphtha- lene (svoc) (µg/l)	2-Nitro- aniline (µg/l)	3-Nitro- aniline (µg/l)	4-Nitro- aniline (µg/l)	Nitro- benzene (µg/l)	2-Nitro- phenol (µg/l)	4-Nitro- phenol (μg/l)	N-nitrosodi- n-propyl- amine (µg/l)	N-Nitro- sodiphenyl- amine (µg/l)	Penta- chloro- phenol (µg/l)	Phen- anthrene (µg/l)
	10/8/2007		-	-									
	1/9/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009												
	7/23/2009												
	2/1/2010												
	8/2/2010												
MW-3B	11/1/2010												
	1/31/2011												
	4/26/2011												
	7/25/2011												
	10/7/2011												
	1/23/2012												
	4/6/2012												
	7/24/2012												
MW-4	9/28/1999												
	4/4/2001												
	7/17/2001												
	7/18/2002												
	10/7/2002												
	1/6/2003												
	4/7/2003												
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004												
	10/25/2004												
	1/17/2005												
	4/6/2005												
	7/8/2005												
IW-4 cont.	10/7/2005												
	1/27/2006												
	4/28/2006												
	7/28/2006												

WELL ID	DATE	4-Methyl- phenol (μg/l)	Naphtha- lene (svoc) (µg/l)	2-Nitro- aniline (µg/l)	3-Nitro- aniline (µg/l)	4-Nitro- aniline (µg/l)	Nitro- benzene (µg/l)	2-Nitro- phenol (µg/l)	4-Nitro- phenol (μg/l)	N-nitrosodi- n-propyl- amine (μg/l)	N-Nitro- sodiphenyl- amine (μg/l)	Penta- chloro- phenol (µg/l)	Phen- anthrene (µg/l)
	10/27/2006												
	1/10/2007												
	4/13/2007												
	7/19/2007												
	10/8/2007												
	1/9/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009												
	7/23/2009												
	2/1/2010												
	8/2/2010												
MW-4B	11/1/2010												
	1/31/2011												
	4/26/2011												
	7/25/2011												
	10/7/2011												
	1/23/2012												
	4/6/2012												
	7/24/2012												
MW-5	7/18/2002												
	10/7/2002												
	1/6/2003	ND<5.0											
	4/7/2003											-	
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004												
	10/25/2004												
	1/17/2005												
MW-5 cont.	4/6/2005												
	7/8/2005												
	10/7/2005												
	1/27/2006												
	4/28/2006												

WELL ID	DATE	4-Methyl- phenol (μg/l)	Naphtha- lene (svoc) (μg/l)	2-Nitro- aniline (μg/l)	3-Nitro- aniline (μg/l)	4-Nitro- aniline (μg/l)	Nitro- benzene (μg/l)	2-Nitro- phenol (µg/l)	4-Nitro- phenol (μg/l)	N-nitrosodi- n-propyl- amine (μg/l)	N-Nitro- sodiphenyl- amine (µg/l)	Penta- chloro- phenol (µg/l)	Phen- anthrend (µg/l)
	7/28/2006												
	10/27/2006												
	1/10/2007												
	4/13/2007												
	7/19/2007												
	10/8/2007												
	1/9/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009												
	7/23/2009												
	2/1/2010												
	8/2/2010												
	1/31/2011												
	4/26/2011												
	7/25/2011												
	10/7/2011												
	1/23/2012												
	4/6/2012												
	7/24/2012												
MW-6	7/18/2002												
	10/7/2002												
	1/6/2003												
	4/7/2003												
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004												
	10/25/2004												
	1/17/2005				<u></u>	<u></u>				<u></u>			
IW-6 cont.	4/6/2005												
0 00110	7/8/2005									 			
	10/7/2005												
	1/27/2006												
	4/28/2006												
	4/20/2000												

WELL ID	DATE	4-Methyl- phenol (μg/l)	Naphtha- lene (svoc) (μg/l)	2-Nitro- aniline (μg/l)	3-Nitro- aniline (μg/l)	4-Nitro- aniline (μg/l)	Nitro- benzene (μg/l)	2-Nitro- phenol (µg/l)	4-Nitro- phenol (μg/l)	N-nitrosodi- n-propyl- amine (μg/l)	N-Nitro- sodiphenyl- amine (µg/l)	Penta- chloro- phenol (µg/l)	Phen- anthrend (µg/l)
	10/27/2006		-	-									
	1/10/2007												
	4/13/2007												
	7/19/2007												
	10/8/2007												
	1/9/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009												
MW-7	7/18/2002												
	10/7/2002												
	1/6/2003	ND<5.0											
	4/7/2003												
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004												
	10/25/2004												
	1/17/2005												
	4/6/2005												
	7/8/2005												
	10/7/2005												
	1/27/2006												
	4/28/2006												
	7/28/2006												
	10/27/2006												
	1/10/2007												
	7/19/2007												
	10/8/2007												
IW-7 cont.	1/9/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009					<u></u>							
	7/23/2009												

WELL ID	DATE	4-Methyl- phenol (µg/l)	Naphtha- lene (svoc) (µg/l)	2-Nitro- aniline (μg/l)	3-Nitro- aniline (μg/l)	4-Nitro- aniline (µg/l)	Nitro- benzene (µg/l)	2-Nitro- phenol (µg/l)	4-Nitro- phenol (μg/l)	N-nitrosodi- n-propyl- amine (μg/l)	N-Nitro- sodiphenyl- amine (μg/l)	Penta- chloro- phenol (µg/l)	Phen- anthrene (µg/l)
	2/1/2010	(F5:-) 	(F5··)	(F5:-) 	(F-5/-/	(FS··)	(F5:-) 	(F5 ^{, ,})	(FS··)	(FS:-) 	(F3:-) 	(F-9··)	(F-9··)
	8/2/2010												
	1/31/2011												
	4/26/2011	<u></u>		<u></u>			<u></u>	<u></u>					
	7/25/2011	<u></u>		<u></u>			<u></u>	<u></u>					
	10/7/2011	<u></u>		<u></u>			<u></u>	<u></u>					
	1/23/2012							 					
	4/6/2012			<u></u>			<u></u>						
	7/24/2012											 	
	1724/2012												
MW-8	1/18/2008									_			
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009												
	7/23/2009												
	2/1/2010												

NOTES:

ND<# = Analyte not detected below indicated practical quantitation limit

-- = Not sampled

μg/L = Micrograms per liter

WELL ID	DATE	Phenol (μg/l)	Pyrene (µg/l)	1,2,4- Trichloro- benzene (svoc) (µg/l)	2,4,6- Trichloro- phenol (µg/l)	2,4,5- Trichloro- phenol (µg/l)	Carbon (organic, total) (µg/l)	Chromium VI (µg/l)	Chromium (total) (µg/l)	lron Ferrous (µg/l)	Manganese (dissolved) (µg/l)	Manganese (total) (μg/l)	Molyb denur (total (μg/l)
MW-1	7/20/1999												
	9/28/1999												
	1/7/2000												
	3/31/2000												
	7/14/2000												
	10/3/2000												
	1/3/2001												
	4/4/2001												
	7/17/2001												
	10/5/2001												
	1/28/2002												
	4/25/2002												
	7/18/2002												
	10/7/2002												
	1/6/2003												
	4/7/2003												
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004		ND<2										
	10/25/2004												
	1/17/2005												
	4/6/2005												
	7/8/2005												
	10/7/2005												
	1/27/2006												
	4/28/2006												
	7/28/2006	ND<10	ND<10	ND<10	ND<25	ND<25							
	10/27/2006												
	1/10/2007												
	4/13/2007												
	7/19/2007	ND<2.2	ND<2.2	ND<2.2	ND<5.5	ND<5.5							
	1/9/2008												
	4/4/2008												
	7/3/2008	ND<20	ND<20	ND<20	ND<50	ND<50							
	10/3/2008												
	1/22/2009												
	4/13/2009						26	ND<2.0	ND<3.0	280	160	200	8.6

WELL ID	DATE	Phenol (μg/l)	Pyrene (µg/l)	1,2,4- Trichloro- benzene (svoc) (µg/l)	2,4,6- Trichloro- phenol (µg/l)	2,4,5- Trichloro- phenol (µg/l)	Carbon (organic, total) (µg/l)	Chromium VI (µg/I)	Chromium (total) (µg/l)	Iron Ferrous (µg/l)	Manganese (dissolved) (µg/l)	Manganese (total) (μg/l)	Molyb denun (total) (μg/l)
MW-1 cont.	7/23/2009												
	2/1/2010												
	8/2/2010												
MW-1B	11/1/2010			_				_					
	1/31/2011												
	4/26/2011												
	7/25/2011												
	10/7/2011												
	1/23/2012												
	4/6/2012												
	7/24/2012		-	-	-	-	-	-	-	-	-	-	
MW-2	9/28/1999												
	4/4/2001												
	7/17/2001												
	7/18/2002												
	10/7/2002												
	1/6/2003												
	4/7/2003												
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004	_											_
	7/12/2004												
	10/25/2004												
	1/17/2005												
	4/6/2005												
	7/8/2005												
	10/7/2005												
	1/27/2006												
	4/28/2006												
	4/28/2006 7/28/2006												
	10/27/2006												
		-											
	1/10/2007												
	4/13/2007												
	7/19/2007												
	10/8/2007												
	1/9/2008												

WELL ID	DATE	Phenol (μg/l)	Pyrene (µg/l)	1,2,4- Trichloro- benzene (svoc) (µg/l)	2,4,6- Trichloro- phenol (µg/l)	2,4,5- Trichloro- phenol (µg/l)	Carbon (organic, total) (µg/l)	Chromium VI (µg/l)	Chromium (total) (µg/l)	Iron Ferrous (µg/l)	Manganese (dissolved) (µg/l)	Manganese (total) (μg/l)	Molyb denun (total) (μg/l)
MW-2 cont.	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009						4.4	ND<2.0	9.3	740	110	230	1.1
	7/23/2009												
	2/1/2010												
	8/2/2010												
MW-2B	11/1/2010												
	1/31/2011												
	4/26/2011												
	7/25/2011												
	10/7/2011												
	1/23/2012												
	4/6/2012												
	7/24/2012												
MW-3	9/28/1999												
	4/4/2001												
	7/17/2001												
	7/18/2002												
	10/7/2002												
	1/6/2003												
	4/7/2003												
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004												
	10/25/2004												
	1/17/2005												
	4/6/2005												
	7/8/2005												
	10/7/2005												
	1/27/2006												
	4/28/2006												
	7/28/2006												
	10/27/2006												

WELL ID	DATE	Phenol (μg/l)	Pyrene (µg/l)	1,2,4- Trichloro- benzene (svoc) (µg/l)	2,4,6- Trichloro- phenol (µg/l)	2,4,5- Trichloro- phenol (µg/l)	Carbon (organic, total) (µg/l)	Chromium VI (µg/I)	Chromium (total) (µg/l)	lron Ferrous (µg/l)	Manganese (dissolved) (µg/l)	Manganese (total) (μg/l)	Molyb denun (total) (μg/l)
MW-3 cont.	1/10/2007												
	4/13/2007												
	7/19/2007												
	10/8/2007												
	1/9/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009						3.0	ND<2.0	14	1,800	2,800	2,500	4.7
	7/23/2009												
	2/1/2010												
	8/2/2010											<u></u>	
	0/2/2010												
MW-3B	11/1/2010												
III 11 - OB	1/31/2011												
	4/26/2011												
	7/25/2011												
	10/7/2011												
	1/23/2012												
	4/6/2012									 			
	7/24/2012			 		 		 	 		 		
	772472012												-
MW-4	9/28/1999			_				_	_		_		
11111-4	4/4/2001												_
	7/17/2001												_
	7/17/2001												
	10/7/2002				 					 			
	1/6/2003												
	4/7/2003												
	7/7/2003												_
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004												
	10/25/2004												
	1/17/2005												
	4/6/2005												
	7/8/2005												

WELL ID	DATE	Phenol (μg/l)	Pyrene (µg/l)	1,2,4- Trichloro- benzene (svoc) (µg/l)	2,4,6- Trichloro- phenol (µg/l)	2,4,5- Trichloro- phenol (µg/l)	Carbon (organic, total) (µg/l)	Chromium VI (µg/l)	Chromium (total) (µg/l)	lron Ferrous (µg/l)	Manganese (dissolved) (µg/l)	Manganese (total) (μg/l)	Molyk denur (total (µg/l)
MW-4 cont.	10/7/2005			-						-			-
	1/27/2006												
	4/28/2006												
	7/28/2006												
	10/27/2006												
	1/10/2007												
	4/13/2007												
	7/19/2007												
	10/8/2007												
	1/9/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009						1.9	ND<2.0	8.1	1,500	2,000	3,500	7.2
	7/23/2009												
	2/1/2010												
	8/2/2010		-						-	-			
MW-4B	11/1/2010												
	1/31/2011												
	4/26/2011												
	7/25/2011												
	10/7/2011												
	1/23/2012												
	4/6/2012												
	7/24/2012		-	-			-	-	-				
MW-5	7/18/2002			_				_					
	10/7/2002												
	1/6/2003												
	4/7/2003												
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004												
	10/25/2004												
	1/17/2005												

WELL ID	DATE	Phenol (μg/l)	Pyrene (µg/l)	1,2,4- Trichloro- benzene (svoc) (µg/l)	2,4,6- Trichloro- phenol (µg/l)	2,4,5- Trichloro- phenol (µg/l)	Carbon (organic, total) (µg/l)	Chromium VI (µg/I)	Chromium (total) (µg/l)	Iron Ferrous (µg/l)	Manganese (dissolved) (μg/l)	Manganese (total) (µg/l)	Molyk denur (total (µg/l)
MW-5 cont.	4/6/2005	(F5··)	(F-9··/	(F-9··) 	(F9··)	(F5··)	(F5:-) 	(F9··)	(FS··)	(F5:-) 	(F9··)	(F3··)	\ r-3
0 00	7/8/2005												
	10/7/2005			_				_	_		_		
	1/27/2006				<u></u>								
	4/28/2006												
	7/28/2006												
	10/27/2006							-	-	-			
	1/10/2007												
	4/13/2007												
	7/19/2007												
	10/8/2007												
	1/9/2008												
	4/4/2008												
	7/3/2008												-
	10/3/2008												
	1/22/2009												
	4/13/2009						1.4	ND<2.0	19	ND<500	1.4	650	1.2
	7/23/2009												
	2/1/2010												
	8/2/2010												
	1/31/2011												
	4/26/2011												
	7/25/2011												
	10/7/2011												
	1/23/2012												
	4/6/2012												
	7/24/2012												
MW-6	7/18/2002												
	10/7/2002												
	1/6/2003												
	4/7/2003												
	7/7/2003												
	10/9/2003												
	1/14/2004				<u></u>								
	4/28/2004				<u></u>								
	7/12/2004		-							_			
	10/25/2004												
	10/25/2004												

WELL ID	DATE	Phenol (μg/l)	Pyrene (µg/l)	1,2,4- Trichloro- benzene (svoc) (µg/l)	2,4,6- Trichloro- phenol (µg/l)	2,4,5- Trichloro- phenol (µg/l)	Carbon (organic, total) (µg/l)	Chromium VI (µg/I)	Chromium (total) (µg/l)	Iron Ferrous (µg/l)	Manganese (dissolved) (µg/l)	Manganese (total) (μg/l)	Molyb denun (total) (μg/l)
MW-6 cont.	4/6/2005												
	7/8/2005												
	10/7/2005												
	1/27/2006												
	4/28/2006												
	7/28/2006												
	10/27/2006												
	1/10/2007												
	4/13/2007												
	7/19/2007												
	10/8/2007												
	1/9/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009						1.4	ND<2.0	32	ND<500	14	530	2.6
MW-7	7/18/2002			_				_			_		
	10/7/2002												
	1/6/2003												
	4/7/2003												
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004												
	10/25/2004												
	1/17/2005												
	4/6/2005												
	7/8/2005												
	10/7/2005												
	1/27/2006												
	4/28/2006												
	7/28/2006												
	10/27/2006												
	1/10/2007												
	7/19/2007												
	10/8/2007												

WELL ID	DATE	Phenol (μg/l)	Pyrene (µg/l)	1,2,4- Trichloro- benzene (svoc) (µg/l)	2,4,6- Trichloro- phenol (µg/l)	2,4,5- Trichloro- phenol (µg/l)	Carbon (organic, total) (µg/l)	Chromium VI (µg/I)	Chromium (total) (µg/l)	Iron Ferrous (µg/l)	Manganese (dissolved) (µg/l)	Manganese (total) (μg/l)	Molyb denun (total) (μg/l)
MW-7 cont.	1/9/2008			-								-	
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009						2.3	ND<2.0	100	3,200	960	2,300	1.1
	7/23/2009												
	2/1/2010												
	8/2/2010												
	1/31/2011												
	4/26/2011												
	7/25/2011												
	10/7/2011												
	1/23/2012												
	4/6/2012												
	7/24/2012		-	-								-	-
MW-8	1/18/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009						0.48	ND<2.0	3.3	130	ND<1.0	47	1.2
	7/23/2009												
	2/1/2010												

NOTES:

ND<# = Analyte not detected below indicated practical quantitation limit

-- = Not sampled

μg/L = Micrograms per liter

WELL ID	DATE	Molyb- denum (dissolved) (μg/l)	Selenium (total) (µg/l)	Selenium (dissolved) (µg/l)	Vanadium (total) (µg/l)	Vanadium (dissolved) (μg/l)	Bromate (μg/l)	Bromide (μg/l)	Chloride (μg/l)	Nitrogen as Nitrate (μg/l)	Sulfate (µg/l)	Alkalinity (total) (μg/l)	Specific Con- ductance (µg/l)
MW-1	7/20/1999												
	9/28/1999												
	1/7/2000												
	3/31/2000												
	7/14/2000												
	10/3/2000												
	1/3/2001												
	4/4/2001												
	7/17/2001												
	10/5/2001												
	1/28/2002												
	4/25/2002												
	7/18/2002												
	10/7/2002												
	1/6/2003												
	4/7/2003												
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004												
	10/25/2004												
	1/17/2005												
	4/6/2005												
	7/8/2005												
	10/7/2005												
	1/27/2006												
	4/28/2006												
	7/28/2006												
	10/27/2006												
	1/10/2007												
	4/13/2007												
	7/19/2007												
	1/9/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009	7.5	ND<2.0	ND<2.0	ND<3.0	ND<3.0	ND<25	0.77	23	ND<0.44	ND<1.0	390	750
/IW-1 cont.	7/23/2009												

WELL ID	DATE	Molyb- denum (dissolved) (μg/l)	Selenium (total) (µg/l)	Selenium (dissolved) (µg/l)	Vanadium (total) (µg/l)	Vanadium (dissolved) (μg/l)	Bromate (μg/l)	Bromide (µg/l)	Chloride (µg/l)	Nitrogen as Nitrate (µg/l)	Sulfate (µg/l)	Alkalinity (total) (μg/l)	Specific Con- ductanc (μg/l)
	2/1/2010						-					-	
	8/2/2010										-	-	
MW-1B	11/1/2010												
	1/31/2011												
	4/26/2011												
	7/25/2011												
	10/7/2011												
	1/23/2012												
	4/6/2012												
	7/24/2012												
MW-2	9/28/1999												
11111-2	4/4/2001		<u></u>				_						
	7/17/2001												
	7/18/2001												
	10/7/2002												-
	1/6/2003												-
													-
	4/7/2003 7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004												
	10/25/2004												
	1/17/2005												
	4/6/2005												
	7/8/2005												
	10/7/2005												
	1/27/2006												
	4/28/2006												
	7/28/2006												
	10/27/2006												
	1/10/2007												
	4/13/2007												
	7/19/2007												
	10/8/2007												
	1/9/2008												
IW-2 cont.	4/4/2008												
	7/3/2008												

WELL ID	DATE	Molyb- denum (dissolved) (μg/l)	Selenium (total) (µg/l)	Selenium (dissolved) (µg/l)	Vanadium (total) (µg/l)	Vanadium (dissolved) (μg/l)	Bromate (µg/I)	Bromide (µg/l)	Chloride (μg/l)	Nitrogen as Nitrate (µg/l)	Sulfate (µg/l)	Alkalinity (total) (μg/l)	Specific Con- ductance (µg/l)
	10/3/2008	-					-			-		-	
	1/22/2009												
	4/13/2009	ND<1.0	ND<2.0	ND<2.0	31	12	ND<25	0.40	25	0.85	14	350	688
	7/23/2009												
	2/1/2010												
	8/2/2010												
MW-2B	11/1/2010												
	1/31/2011												
	4/26/2011												
	7/25/2011												
	10/7/2011												
	1/23/2012												
	4/6/2012												
	7/24/2012												
MW-3	9/28/1999												
IVIVV-3	4/4/2001												
	7/17/2001 7/18/2002												
	10/7/2002												
	1/6/2003												
	4/7/2003												
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												-
	7/12/2004												
	10/25/2004												
	1/17/2005												
	4/6/2005												
	7/8/2005												
	10/7/2005												
	1/27/2006												
	4/28/2006												
	7/28/2006												
	10/27/2006												
IW-3 cont.	1/10/2007												
	4/13/2007												
	7/19/2007												

WELL ID	DATE	Molyb- denum (dissolved) (μg/l)	Selenium (total) (µg/l)	Selenium (dissolved) (μg/l)	Vanadium (total) (µg/l)	Vanadium (dissolved) (μg/l)	Bromate (µg/l)	Bromide (μg/l)	Chloride (μg/l)	Nitrogen as Nitrate (μg/l)	Sulfate (µg/l)	Alkalinity (total) (μg/l)	Specific Con- ductance (µg/l)
	10/8/2007										-		
	1/9/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009	3.7	ND<2.0	ND<2.0	22	ND<3.0	ND<25	0.41	30	2.9	16	360	681
	7/23/2009												
	2/1/2010												
	8/2/2010										-		
MW-3B	11/1/2010												
	1/31/2011												
	4/26/2011												
	7/25/2011												
	10/7/2011												
	1/23/2012												
	4/6/2012												
	7/24/2012												
MW-4	9/28/1999												
	4/4/2001												
	7/17/2001												
	7/18/2002												
	10/7/2002												
	1/6/2003												
	4/7/2003												
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004												
	10/25/2004												
	1/17/2005												
	4/6/2005												
	7/8/2005												
W-4 cont.	10/7/2005												
	1/27/2006												
	4/28/2006												
	7/28/2006												

WELL ID	DATE	Molyb- denum (dissolved) (μg/l)	Selenium (total) (µg/l)	Selenium (dissolved) (µg/l)	Vanadium (total) (µg/l)	Vanadium (dissolved) (μg/l)	Bromate (µg/l)	Bromide (µg/l)	Chloride (µg/l)	Nitrogen as Nitrate (µg/l)	Sulfate (µg/l)	Alkalinity (total) (μg/l)	Specific Con- ductance (µg/l)
	10/27/2006												
	1/10/2007												
	4/13/2007												
	7/19/2007												
	10/8/2007												
	1/9/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009	6.4	ND<2.0	ND<2.0	13	3.4	ND<25	0.40	37	4.4	23	320	704
	7/23/2009												
	2/1/2010												
	8/2/2010												
MW-4B	11/1/2010												
	1/31/2011												
	4/26/2011												
	7/25/2011												
	10/7/2011												
	1/23/2012												
	4/6/2012												
	7/24/2012	-	-	-	-	-	-				-		
MW-5	7/18/2002												
	10/7/2002												
	1/6/2003												
	4/7/2003												
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004												
	10/25/2004												
	1/17/2005												
/IW-5 cont.	4/6/2005												
	7/8/2005												
	10/7/2005												
	1/27/2006												

WELL ID	DATE	Molyb- denum (dissolved) (µg/l)	Selenium (total) (µg/l)	Selenium (dissolved) (µg/l)	Vanadium (total) (µg/l)	Vanadium (dissolved) (μg/l)	Bromate (µg/l)	Bromide (μg/l)	Chloride (µg/l)	Nitrogen as Nitrate (µg/l)	Sulfate (µg/l)	Alkalinity (total) (μg/l)	Specific Con- ductance (µg/l)
	7/28/2006												
	10/27/2006												
	1/10/2007												
	4/13/2007												
	7/19/2007												
	10/8/2007												
	1/9/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009	1.5	ND<2.0	ND<2.0	59	6.1	ND<25	0.71	68	5.7	26	350	860
	7/23/2009												
	2/1/2010												
	8/2/2010												
	1/31/2011												
	4/26/2011												
	7/25/2011												
	10/7/2011												
	1/23/2012												
	4/6/2012												
	7/24/2012												
MW-6	7/18/2002												
	10/7/2002												
	1/6/2003												
	4/7/2003												
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004						<u></u>						
	10/25/2004												
	1/17/2005												
MW-6 cont.	4/6/2005												
www-o cont.	7/8/2005				 								
	10/7/2005												
	1/27/2006												
	4/28/2006												
	7/28/2006												

WELL ID	DATE	Molyb- denum (dissolved) (µg/l)	Selenium (total) (µg/l)	Selenium (dissolved) (µg/l)	Vanadium (total) (µg/l)	Vanadium (dissolved) (μg/l)	Bromate (μg/l)	Bromide (μg/l)	Chloride (μg/l)	Nitrogen as Nitrate (μg/l)	Sulfate (µg/l)	Alkalinity (total) (μg/l)	Specific Con- ductanc (μg/l)
	10/27/2006												
	1/10/2007												
	4/13/2007												
	7/19/2007												
	10/8/2007												
	1/9/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009	2.9	ND<2.0	ND<2.0	80	5.2	ND<25	0.58	72	8.9	37	280	754
MW-7	7/18/2002												
	10/7/2002												
	1/6/2003												
	4/7/2003												
	7/7/2003												
	10/9/2003												
	1/14/2004												
	4/28/2004												
	7/12/2004												
	10/25/2004												
	1/17/2005												
	4/6/2005												
	7/8/2005												
	10/7/2005												
	1/27/2006												
	4/28/2006												
	7/28/2006												
	10/27/2006												
	1/10/2007												
	7/19/2007												
	10/8/2007												
IW-7 cont.	1/9/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009	1.3	ND<2.0	ND<2.0	190	5.6	ND<25	0.50	37	ND<0.44	9.3	430	848
	7/23/2009				100					110 .0.17	0.0		

WELL ID	DATE	Molyb- denum (dissolved)	Selenium (total)	Selenium (dissolved)	Vanadium (total)	Vanadium (dissolved)	Bromate	Bromide	Chloride	Nitrogen as Nitrate	Sulfate	Alkalinity (total)	Specific Con- ductance
		(μg/l)	(µg/l)	(µg/l)	(µg/l)	(µg/l)	(µg/l)	(μg/l)	(µg/l)	(µg/l)	(µg/l)	(µg/l)	(µg/l)
	2/1/2010												
	8/2/2010												
	1/31/2011												
	4/26/2011												
	7/25/2011												
	10/7/2011												
	1/23/2012												
	4/6/2012												
	7/24/2012							-					
MW-8	1/18/2008												
	4/4/2008												
	7/3/2008												
	10/3/2008												
	1/22/2009												
	4/13/2009	1.2	ND<2.0	ND<2.0	12	4.5	ND<25	ND<0.10	81	19	40	210	690
	7/23/2009												
	2/1/2010												

NOTES:

ND<# = Analyte not detected below indicated practical quantitation limit

-- = Not sampled

μg/L = Micrograms per liter

Table 6

Grab Groundwater Analytical Results - July 2009

76 Service Station No. 1156

4276 MacArthur Boulevard, Oakland, California

Sample ID	Date	Time	TPH-G	TPH-D	Benzene	Toluene	Ethyl-	Total	MTBE	TBA	ETBE	TAME	DIPE	1,2-DCA	EDB	Ethanol
			(110/1)	(110/1)	(119/1)	(119/1)	benzene	Xylenes	(110/1)	(110/11)	(110/11)	(110/1)	(110/11)	(110/11)	(110/11)	(ua/L)
			(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)
Groundwater																
SB-7	7/9/09	15:25	7,900	1,400	16	6.8	270	1,400	21	ND<100	ND<5.0	ND<5.0	ND<5.0	ND<5.0	ND<5.0	ND<250
SB-9	7/8/09	18:58	630	350	62	3.9	3.8	29	50	ND<10	ND<0.50	ND<0.50	ND<0.50	ND<0.50	ND<0.50	ND<250
SB-11	7/10/09	11:55	310	230	27	1.4	9.7	7.1	25	79	ND<0.50	ND<0.50	ND<0.50	ND<0.50	ND<0.50	ND<250
1156-CompB	7/10/09	13:45	73		ND<0.50	ND<0.50	0.87	4.7	ND<0.50	ND<10	0.87	ND<0.50	ND<0.50	ND<0.50	ND<0.50	ND<250

TPH-G = total petroleum hydrocarbons as gasoline by EPA Method 8260B TPH-D total petroleum hydrocarbons as diesel by EPA Method 8260B

MTBE = methyl tertiary butyl ether by EPA Method 8260B

TBA = tertiary butyl alcohol by EPA Method 8260B
ETBE = ethyl tertiary butyl ether by EPA Method 8260B

TAME = tertiary amyl methyl ether by EPA Method 8260B

DIPE = di-isopropyl ether by EPA Method 8260B

1,2-DCA = 1,2-Dichloroethane (also known as ethylene dichloride) by EPA Method 8260B

EDB = ethylene dibromide (also known as 1,2-Dibromoethane) by EPA method 8260B

Ethanol was analyzed by EPA Method 8260B

μg/L = micrograms per liter

ND = not detected above the laboratory detection limit

Bold = detected compound concentration

EPA = US Environmental Protection Agency

Table 7

Discrete Groundwater Analytical Results - June 2010

76 Service Station No. 1156 4276 MacArthur Boulevard Oakland, California

Boring	Depth	Date	TPHg	TPHd	TPHmo	Benzene	Toluene	Ethylbenzene	Total Xylenes	MTBE	EDB	1,2-DCA	TAME	TBA	DIPE	ETBE	Ethanol
			ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L
SB-15	19-24	6/18/2010	<50	54	<200	<0.50	<0.50	<0.50	<1.0	29	<0.50	<0.50	<0.50	<10	<0.50	<0.50	<250
SB-16	20-25	6/17/2010	<50	150	<200	140	7.5	14	7.8	460	<0.50	23	<0.50	730	<0.50	<0.50	<250
SB-17	14-19	6/17/2010	260	260	<290	8.7	0.51	6.6	1.6	82	<0.50	14	<0.50	640	<0.50	<0.50	<250
SB-18	15-20	6/16/2010	1900	720	480	94	4.1	4.8	12	180	<0.50	<0.50	<0.50	<10	<0.50	<0.50	<250
SB-19	15-20	6/16/2010	1100	230	230	8.6	1.2	4.3	9.5	93	<0.50	<0.50	<0.50	<10	<0.50	< 0.50	<250

TPHg = total petroleum hydrocarbons as gaoline TPHd = total petroleum hydrocarbons as diesel TPHmo = total petroleum hydrocarbons as motor oil EDB = ethylene dibromide 1,2-DCA = 1,2 dichloroethane MTBE = mety; tert butyl ether TAME = tert amyl methyl ether TBA = tert butyl alcohol DIPE = diisopropyl ether ETBE = ethyl tert butyl ether ug/L = micrograms per liter bold = above laboratory reporting limits

Table 8

Soil Gas Analytical Results - August 2009 and September 2010

Chevron Site #351645 (76 Station No. 1156) Oakland, California

Sample	e ID	Date	Time	Sample	TPH-G	Benzene	Toluene	Ethyl-	m,p-Xylenes	0-	Total	MTBE	TBA	ETBE	TAME	DIPE	EDB	1,2-DCA	Ethanol	1,1 DFA	IPA	Oxygen	Carbon	Methane
				Depth				benzene		Xylenes	Xylenes												Dioxide	
				(feet)	(µg/m³)	(µg/m³)	(µg/m³)	(µg/m³)	(µg/m³)	(µg/m ³)	(µg/m³)	(µg/m ³)	(µg/m³)	(µg/m³)	(µg/m³)	(µg/m³)	(µg/m³)	(µg/m³)	(µg/m³)	(µg/m³)	(µg/m³)	(% Vol)	(% Vol)	(ppmV)
Soil Gas																								
SV-	2	8/11/09	14:43	5	23	350	370	370	380	140		<100	<10,000	<100	<100	<100				<10,000		11	5.1	<500
SV-	4	8/11/09	13:49	3.5	67,000,000	1,100	<200	17,000	6,200	<100		<100	<10,000	<100	<100	<100				<10,000		5.2	9.5	20,000
SV-	6	8/11/09	10:40	5	3,000,000	2,000	<200	2,700	2,200	<100		<100	<10,000	<100	<100	<100				<10,000		20	<1.0	<500
SV-	7	8/11/09	12:09	3.5	82,000,000	120,000	<200	32,000	330	130		<100	<10,000	<100	<100	<100				<10,000		21	<1.0	24,000
SVW	<i>'</i> -1	9/8/10		4.5	4,700	<22	<17	<20			<20	<15	<92	<17	<17	<17	<31	<25	<190		<56	11	4.4	<0.00040
SVW	1-2	9/8/10		4.5	78,000,000	<20,000	19,000	35,000			99,000	<15,000	<94,000	<17,000	<17,000	<17,000	<32,000	<25,000	<190,000		<51,000	1.3	14	8.1
SVW	/-3	9/8/10		4.5	250,000,000	1,100,000	<18,000	610,000			820,000	<18,000	<110,000	<20,000	<20,000	<20,000	<37,000	<30,000	<230,000		<60,000	1.1	11	38
SVW	/-4	9/8/10		4.5																				
SVW	/-5	9/8/10		4.5	320,000,000	540,000	<28,000	23,000			<32,000	<27,000	<170,000	<31,000	<31,000	<31,000	<57,000	<45,000	<350,000		<3,700	1.4	13	7.5
SVW	/-6	9/8/10		4.5	420,000,000	1,000,000	<38,000	240,000			170,000	<37,000	<230,000	<43,000	<43,000	<43,000	<78,000	<62,000	<480,000		<130,000	1.1	16	27
Sh	Shallow Soil Gas CHHSLs for Residential Land Use				NE	36.2	135,000	NE	319,000	315,000	NE	4,000	NE	NE	NE	NE	NE	49.6	NE					
Sha	Shallow Soil Gas CHHSLs for Commercial Land Use					122	378,000	NE	887,000	879,000	NE	13,400	NE	NE	NE	NE	NE	167	NE					
	Lowest Residential Shallow Soil Gas ESLs					84	63,000	980	NE	NE	21,000	9,400	NE	NE	NE	NE	4.1	94	NE					
	Lowest Commercial Shallow Soil Gas ESLs			29,000	280	180,000	3,300	NE	NE	58,000	31,000	NE	NE	NE	NE	140	310	NE						

TPH-G = total petroleum hydrocarbons as gasoline by EPA Method 8260B

MTBE = TBA = methyl tertiary butyl ether by EPA Method 8260B tertiary butyl alcohol by EPA Method 8260B

ETBE = TAME = ethyl tertiary butyl ether by EPA Method 8260B tertiary amyl methyl ether by EPA Method 8260B

California Human Health Screening Levels set by the California EPA (January 2005)

CHHSLs = ESLs = Environmental Screening Levels set by the San Francisco Bay Regional Water Quality Control Board (November 2007)

DIPE = di-isopropyl ether by EPA Method 8260B

EDB = ethylene dibromide (also known as 1,2-Dibromoethane) by EPA method TO-15

Ethanol was analyzed by EPA Method TO-15

1,2-DCA = 1,2-Dichloroethane (also known as ethylene dichloride) by EPA MethodTO-15

1,1-DFA = 1,1 - Difluoroethane (leak check)

IPA = Isopropyl Alcohol (Leak Detection Compound) dup = duplicate sample

 $\mu g/m^3 =$ micrograms per cubic meter ppmV parts per million by volume

% Vol = percent by volume

Compound concentrations above reporting limit Bold =

Sample analyzed by EPA Method TO-15


NE = Not Established


No Sample/No Data


Attachment E


Hydrographs


Chevron Site 351645 November 2012
































APPENDIX C

Standard Operating Procedures

SOP NUMBER: 7115

Subsurface Soil Sampling by

Split Spoon

Date: 3rd Qtr. 1994

Revision Number:

Author: Charles Martin

Discipline: Geosciencies

1.0 PURPOSE AND APPLICABILITY

1.1 Purpose and Applicability

This Standard Operating Procedure (SOP) describes the methods used in obtaining subsurface soil samples for physical and/or chemical analysis. Subsurface soil samples are obtained in conjunction with soil boring programs and provide information as to the physical and/or chemical makeup of the subsurface environment.

The purpose of this SOP is to provide a description of a specific method or procedure to be used in the collection of subsurface soil samples. Subsurface soil is defined as unconsolidated material which may consist of one or a mixture of the following materials: sand, gravel, silt, clay, peat (or other organic soils), and fill material. Subsurface soil sampling, conducted in accordance with this SOP will promote consistency in sampling and provide a basis for sample representativeness.

This SOP covers subsurface soil sampling by split-spoon only, as this is the means most often used for obtained samples of unconsolidated deposits. Other types of equipment are available for use in subsurface soil sampling, including thin-wall tube samplers (Shelby tubes), piston samplers, and continuous core barrel samplers. Information on the use of these other sampling devices may be found in several available drilling handbooks and respective state and/or federal agency technical guidance documents. The American Society for Testing and Materials (ASTM) also provides procedures for use of split-spoon and other sampling devices.

Deviations from this SOP to accommodate other regulatory requirements should be reviewed in advance of the field program, should be explained in the project work plan, and must be documented in the field project notebook when they occur.

1.2 General Principles

Split-spoon subsurface soil sampling generally requires use of a drilling rig and typically the hollow-stem auger or other common drilling method to generate a borehole in which to use the split-spoon sampler. The split-spoon sampler is

inserted through the augers (or other type of drill casing) then is driven into the subsurface soil with a weighted hammer. The sampler is then retrieved and opened to reveal the recovered soil sample. Soil samples may be collected at a continuous interval or at pre-selected vertically spaced intervals within the borehole.

1.3 Quality Assurance Planning Considerations

Sampling personnel should follow specific quality assurance guidelines as outlined in the site-specific Quality Assurance Project Plan (QAPP). Proper quality assurance requirements should be provided which will allow for collection of representative samples from representative sampling points. Quality assurance requirements outlined in the QAPP typically suggest the collection of a sufficient quantity of field duplicate, field blank, and other samples.

1.4 Health and Safety Considerations

Subsurface soil sampling may involve chemical hazards associated with the types of contaminants potentially encountered and will always involve potential physical hazards associated with use of drilling equipment. When sampling is performed in materials which may contain hazardous constituents, or when the quality assurance objectives of the project require the use of hazardous solvents, adequate Health and Safety measures must be taken to protect sampling personnel. These measures must be addressed in the project Health and Safety Plan (HASP). This plan must be approved by the project Health and Safety Officer before work commences, must be distributed to all personnel performing sampling, and must be adhered to as field activities are performed.

2.0 RESPONSIBILITIES

2.1 Drilling Subcontractor

It will be the responsibility of the drilling subcontractor to provide the necessary materials for obtaining subsurface soil samples. This generally includes one or more split-spoon samplers in good operating condition and sample containers used for stratigraphic characterization samples (sample containers for environmental samples should be provided by the designated analytical laboratory). It is the drilling subcontractor's responsibility to provide and maintain their own boring logs if desired. Equipment decontamination materials should also be supplied by the subcontractor and should meet project specifications.

2.2 Project Geologist/Sampling Engineer

It will be the responsibility of the project geologist/sampling engineer to conduct subsurface soil sampling in a manner which is consistent with this SOP. The project geologist/sampling engineer will observe all activities pertaining to subsurface soil sampling to ensure that the SOP is followed, and to record all pertinent data onto a boring log. It is also the project geologist/sampling engineer's responsibility to indicate the specific targeted sampling depth or sampling interval to the drilling subcontractor. The project geologist/sampling engineer is also responsible for the collection of representative environmental or stratigraphic characterization samples once the sampling device has been retrieved and opened. Additional sample collection responsibilities include labeling, handling, and storage of samples until further chain-of-custody procedures are implemented.

3.0 REQUIRED MATERIALS

In addition to those materials provided by the subcontractor, the project geologist/sampling engineer will require:

- Project Sampling Plan, QAPP, and HASP
- Boring logs
- Teaspoon or spatula (stainless steel is recommended)
- Sample kit (bottles, labels, custody records and tape, cooler)
- Sample collection pen
- Folding rule or tape measure
- Equipment decontamination materials
- Health and safety equipment (as required by HASP)
- Field project notebook/pen

4.0 METHOD

4.1 General Method Description

Split-spoon sampling devices are typically constructed of steel and are most commonly available in lengths of 18 and 24 inches and diameters of 1.5 to 3 inches. The split-spoon consists of a tubular body with two halves that split apart lengthwise, a drive head on the upper end with a ball-check valve for venting, and a hardened steel cutting shoe at the bottom. The soil sample enters the split-spoon through the cutting shoe as the device is driven into the ground. A replaceable plastic or metal basket is often inserted into the shoe to assist with retaining samples. Once the

sampler is retrieved, the drive head and cutting shoes are removed and the splitspoon halves are then separated, revealing the sample.

Sample depth intervals are usually defined on a project-specific basis with these requirements specified in the project sampling plan. Sampling intervals typically range from one (1) sample per five (5) feet of drilling to continuous sampling where the entire drilled interval is sampled.

Subsurface soil sampling is usually accomplished as part of a drilling program where a soil boring is advanced with drilling equipment to the designated depth prior to collection of a representative sample. The general procedures outlined briefly in the following section provide requirements for advancing drill casing/augers in preparation for sampling.

4.2 General Procedures - Borehole Preparation

4.2.1 Advancing Casing/Augers

Soil borings that are completed for soil sampling purposes are typically advanced using hollow-stem augers and sometimes drive-and-wash or other casing methods. The casing/augers must be of sufficient diameter to allow for soil sampling at a minimum. The casing/augers will be advanced according to project requirements to the required depth for sampling. If hollow-stem augers are used, a temporary plug shall be used in the lead auger to prevent the auger from becoming filled with drill cuttings while drilling is in progress.

4.2.2 Obstructions

For those borings which encounter obstructions, the casing/augers will be advanced past or through the obstruction if possible. Caution should be exercised when obstructions are encountered and an effort made to identify the obstruction before drilling is continued. If the obstruction is not easily drilled through or removed, the boring should be relocated to an adjacent location.

4.2.3 Use of Added Water

The use of added or recirculated water during drilling is permitted when necessary. Use of extraneous water should be minimized or avoided if possible as it may impact sample quality. Water usage should be documented in the field notebook. Sampling and analysis of added or

recirculated water may be required for quality assurance purposes (refer to QAPP). If a well is installed within the completed borehole, removal of the added water may be required.

4.3 Sampling Procedure

4.3.1 Equipment Decontamination

Each split-spoon must be decontaminated prior to its initial use and following collection of each soil sample. Site-specific requirements for equipment decontamination should be outlined within the Project Sampling Plan. Equipment decontamination procedures are also outlined within SOP 7600 - Decontamination of Equipment.

4.3.2 Standard Penetration Test

The drilling subcontractor will lower the split-spoon into the borehole. Samples are generally obtained using the Standard Penetration Test (SPT) in accordance with ASTM standards (ASTM D 1586-84). Following this method, the sampler will be driven using the 140-pound hammer with a vertical free drop of 30 inches using two turns of the rope on the cathead. The number of hammer blows required for every 6 inches of penetration will be recorded on the boring log. Blowcount information is used as an indicator of soil density for geotechnical as well as stratigraphic logging purposes. Once the split-spoon has been driven to its fullest extent, or to refusal, it will be removed from the borehole.

4.3.3 Sample Recovery

The split-spoon will be immediately opened upon removal from the casing/auger. The open sampler shall then be screened for volatile organics with a photoionization device (PID) if required by the Project Sampling Plan. If the Sampling Plan also requires individual soil sample headspace screening for volatile organic compounds, then a small portion of the split-spoon sample shall be removed and properly contained for that purpose.

Sample recovery will be determined by the project geologist/sampling engineer who will examine the soil core once the sampler is opened. The length of sample shall then be measured with a folding rule or tape measure. Any portion of the split-spoon contents which are not considered part of the true sample (i.e., heaved soils) will be discarded. If the sample recovery is considered inadequate for sample characterization or analytical testing

purposes, another sample should be collected from the next vertical interval if possible before drilling is reinitiated.

Adequate sample recovery for stratigraphic logging purposes and/or headspace organic vapor testing purposes should be approximately 6 inches. Adequate sample recovery for analytical testing purposes should be a minimum of 12 inches and is somewhat dependent on the type of analytical testing required. In some cases, continuous sampling over a short interval, and compositing of the sample, may be required to satisfy analytical testing requirements. Larger diameter samplers may be used if large volumes of soil are required for analytical testing.

4.3.4 Sample Containment - General

Once retrieved, the sample will be removed from the split-spoon with a teaspoon or spatula and placed into the appropriate sample container. The sample will be split if necessary to meet sampling program requirements. Sample splitting may be necessary to provide individual samples for headspace testing, visual characterization, physical testing, analytical testing, or simply for archiving purposes. In general, most sampling programs are structured around environmental characterization needs; therefore, sample portions required for analytical testing should be collected first. The Project Sampling Plan and QAPP provides specific sample container requirements for each type of sample and should be referred to for guidance.

Once filled, the sample containers should be properly capped, cleaned, and labeled, and chain-of-custody and sample preservation procedures initiated. Sampling equipment should then be properly decontaminated.

4.3.5 Sample Containment - Volatile Organic Analyses

Collection of subsurface soil samples for volatile organic analysis (VOA) is slightly more complex than collection of samples for other routine chemical or physical testing primarily because of the concern for the potential loss of volatiles during the sample collection procedure. To limit the potential for loss of volatiles, the soil sample needs to be obtained as quickly and as directly as possible from the split-spoon. This generally means that the VOA sample is to be collected and placed into the appropriate sample container first. The VOA sample should also be obtained from a discrete portion of the entire sample interval and not composited or homogenized. The remainder of the recovered sample can then be composited, homogenized or split to meet the other testing requirements. The boring log and/or sample logbook should be

SOP NUMBER: 7115

filled out to indicate actual sample collection depths for both VOA samples and other portions of the sample which may have been composited over a larger vertical interval.

5.0 QUALITY CONTROL

Quality control requirements are dependent on project-specific sampling objectives. The QAPP will provide requirements for sample preservation and holding times, sample container types, sample packaging and shipment, as well as requirements for the collection of various quality assurance samples such as trip blanks, field blanks, equipment blanks, and field duplicate samples.

6.0 DOCUMENTATION

Various forms are required to ensure that adequate documentation is made of sample collection activities. These forms include:

- Boring logs
- Field log books
- Sample collection records
- Chain-of-custody records
- Shipping labels

Boring logs (Figure 1) will provide visual and descriptive information for each sample collected and are often the most critical form of documentation generated during a sampling program. The field log book is kept as a general log of activities. Chain-of-custody forms are transmitted with the samples to the laboratory for sample tracking purposes. Shipping labels are required if sample coolers are to be transported to the laboratory by a third party (courier service). Original copies of these records should be maintained in the appropriate project files.

7.0 REFERENCES

ASTM D 1586-84

								Sheet 1 of
					В	ORING LOG		
Project No	o		Da	ate – St	art	Finish	Boring	
Project Na	ame					Drilling Co.		
Location _			7			Drilling Method		
Total Dep			Inspect	or		Reviewer		
Remarks								
Depth Feet	Type &	Sampl Blows per	e Depth	Rec.	Graphic Log	Litho	ologic Description	Equipment Installed
	No.	6 in.	Range					
<u> </u>								_
_								
								<u> </u>
								_
								_
_								
								_
								_
_								_
								_
_								_

SOP NUMBER: 7220

Monitoring Well Construction and Installation

Date: 3rd Qtr., 1995

Revision Number:

Author: Charles Martin

Discipline: Geosciences

1.0 PURPOSE AND APPLICABILITY

1.1 Purpose and Applicability

This SOP provides guidance for installing groundwater monitoring wells. Monitoring wells are installed to monitor the depth to groundwater, to measure aquifer properties, and to obtain samples of groundwater for chemical analysis.

This SOP is applicable to installation of single monitoring wells within a borehole. The construction and installation of nested, multilevel or other special well designs is not covered within this SOP as these type of wells are not frequently constructed. This SOP applies to both overburden and bedrock monitoring wells.

Some states and EPA Regions have promulgated comprehensive guidelines for monitoring well construction and for subsurface investigation procedures. Deviations from this SOP to accommodate other regulatory requirements should be reviewed in advance of the field program, should be explained in the project work plan, and must be documented in the field project notebook when they occur.

1.2 General Principles

Monitoring well construction and installation generally involves drilling a borehole using conventional drilling equipment, installing commercially available well construction and filter/sealing materials, and development of the well prior to sampling. This SOP covers well construction and installation methods only. Borehole drilling and well development methods are covered under SOP-7115 (Subsurface Soil Sampling) and SOP-7221 (Monitoring Well Development), respectively.

1.3 Quality Assurance Planning Considerations

Field personnel should follow specific quality assurance guidelines as outlined in the site-specific QAPP.

The following aspects of monitoring well design and installation procedures depend on project-specific objectives which should be addressed in the QAPP and in the project work plan:

- Borehole drilling method and diameter,
- Type of construction materials for well screen, riser, filter pack and seals,
- Diameter of well materials,
- Length of well screen,
- Location, thickness, and composition of annular seals, and
- Well completion and surface protection requirements.

1.4 Health and Safety Considerations

Monitoring well installation may involve chemical hazards associated with materials in the soil or groundwater being investigated; and always involves physical hazards associated with drilling equipment and well construction methods. When wells are to be installed in locations where the aquifer and/or overlying materials may contain chemical hazards, a Health and Safety Plan (HASP) must be prepared and approved by the Health and Safety Officer before field work commences. This plan must be distributed to all field personnel and must be adhered to as field activities are performed.

2.0 RESPONSIBILITIES

2.1 Drilling Subcontractor

It is the responsibility of the drilling subcontractor to provide the necessary equipment for well construction and installation. Well construction materials should be consistent with project requirements.

2.2 Surveying Subcontractor

It is the responsibility of the surveying subcontractor to provide one or more of the following well measurements as specified in the project work plan: ground surface elevation, horizontal well coordinates, top of well casing elevation (i.e., top-of-casing, or measuring point elevation), and/or top of protective casing elevation.

2.3 Project Geologist/Engineer

It is the responsibility of the Project Geologist/Engineer to directly oversee the construction and installation of the monitoring well by the drilling subcontractor to ensure that the well-installation specifications defined in the project work plan are adhered to, and that all pertinent data are recorded on the appropriate forms.

2.4 Project Manager

It is the responsibility of the Project Manager to ensure that each project involving monitoring well installation is properly planned and executed.

3.0 REQUIRED MATERIAL

3.1 Well Construction Materials

Well construction materials are usually provided by the drilling subcontractor and most often consist of commercially available flush-threaded well screen and riser pipe constructed of PVC or stainless steel with a minimum 2-inch inside diameter. The length of the screen and the size of the screen slots should be specified in the project work plan.

3.2 Well Completion Materials

Well completion materials include silica sand, bentonite, cement, protective casings and locks. Completion materials are generally provided by the drilling subcontractor.

3.3 Other required materials include the following:

- Potable water supply
- Fiberglass or steel measuring tape
- Water level indicator
- Well construction diagrams (Figure 1)
- Waterproof marker or paint (to label wells)
- Health and Safety supplies

- Equipment decontamination materials
- Field project notebook/pen

4.0 METHOD

4.1 General Preparation

4.1.1 Borehole Preparation

Standard drilling methods should be used to achieve the desired drilling/well installation depths specified in the project work plan. Soil sampling, if conducted, should be conducted in accordance with ENSR SOP-7115 (Subsurface Soil Sampling).

The diameter of the borehole must be a minimum of 2 inches greater than the outside diameter of the well screen or riser pipe used to construct the well. This is necessary so that sufficient annular space is available to install filter packs, bentonite seals, and grout seals. Bedrock wells may require reaming after coring in order to provide a large enough borehole diameter for well installation.

Rotary drilling methods requiring bentonite-based drilling fluids, if selected, should be used with caution to drill boreholes that will be used for monitoring well installation. The bentonite mud builds up on the borehole walls as a filter cake and permeates the adjacent formation, potentially reducing the permeability of the material adjacent to the well screen.

If water or other drilling fluids have been introduced into the boring during drilling or well installation, samples of these fluids should be obtained and analyzed for chemical constituents that may be of interest at the site. In addition, an attempt should be made to recover the quantity of fluid or water that was introduced, either by flushing the borehole prior to well installation and/or by overpumping the well during development.

4.1.2 Well Material Decontamination

Although new well materials (well screen and riser pipe) generally arrive at the site boxed and sealed within plastic bags, it is sometimes necessary to decontaminate the materials prior to their use. Well materials should be inspected by the project geologist/engineer upon delivery to check cleanliness. If the well materials appear dirty, or if local or regional regulatory guidance requires decontamination, then well material decontamination should be performed by the drilling subcontractor in accordance with ENSR SOP-7600 (Decontamination of Equipment).

4.2 Well Construction Procedure

4.2.1 Depth Measurement

Once the target drilling depth has been reached, the drilling subcontractor will measure the total open depth of the borehole with a weighted, calibrated tape measure. Adjustments of borehole depth can be made at this time by drilling further or installing a small amount of sand filter material to achieve the desired depth. If drilling fluids were used during the drilling process, the borehole should be flushed at this time using potable water. The water table depth may also be checked with a water level indicator if this measurement cannot be obtained with the calibrated tape.

4.2.2 Centralizers

In order to install a well which is centered within the borehole, it is recommended that centralizers be used. Centralizers are especially helpful for deep well installations where it may be difficult to position the well by hand. Centralizers may not be necessary on shallow water table well installations where the well completion depth is within 25 feet of the ground surface.

4.2.3 Well Construction

The well screen and riser pipe generally are assembled by hand as they are lowered into the borehole. Before the well screen is inserted into the borehole, the full length of the slotted portion of the well screen as well as the unslotted portion of the bottom of the screen should be measured with the measuring tape. These measurements should be recorded on the well construction diagram.

After the above measurement has been taken, the drilling subcontractor may begin assembling the well. As the assembled well is lowered, care should be taken to ensure that it is centered in the hole if centralizers are not used. The well should be temporarily capped before filter sand and other annular materials are installed.

4.2.4 Filter Sand Installation

The drilling subcontractor should fill the annular space surrounding the screened section of the monitoring well to at least 1 foot above the top of the screen with an appropriately graded, clean sand or fine gravel. In general, the filter pack should not extend more than 3 feet above the top of the screen to limit the thickness of the monitoring zone. If coarse filter materials are used, an additional 1-foot thick layer of fine sand should be placed immediately above the filter pack to prevent the infiltration of sealing components (bentonite or grout) into the filter pack. As the filter pack is placed, a weighted tape should be lowered in the annular space to verify the depth to the top of the layer. Depending upon depth, some time may be required for these materials to settle. If necessary, to eliminate possible bridging or creation of voids, placement of the sand pack may require the use of a tremie pipe. Tremie pipe sandpack installations are generally suggested for deep water table wells and for wells which are screened some distance beneath the water table.

4.2.5 Bentonite Seal Installation

A minimum 2-foot thick layer of bentonite pellets or slurry seal will be installed by the drilling subcontractor immediately above the well screen filter pack in all monitoring wells. The purpose of the seal is to provide a barrier to vertical flow of water in the annular space between the borehole and the well casing. Bentonite is used because it swells significantly upon contact with water. Pellets generally can be installed in shallow boreholes by pouring them very slowly from the surface. If they are poured too quickly, they may bridge at some shallow, undesired depth. As an option, powdered bentonite may be mixed with water into a very thick slurry and a tremie pipe used to inject the seal to the desired depth.

4.2.6 Annular Grout Seal Installation

This grout seal should consist of a bentonite/cement mix with a ratio of bentonite to cement of between 1:5 and 1:20. The grout ratio should be chosen based on site conditions with a higher percentage of bentonite generally used for formations with higher porosity. A mud balance should be used if a specific mud density is required at a particular site. Grout slurry should be pumped into the annular space using a side-discharging tremie pipe located about 2 feet above the sand pack. Side discharge will help preserve the integrity of the sand pack.

In situations where the monitoring well screen straddles the water table, the seal will be in the unsaturated zone and pure bentonites (pellets or powder) will not work effectively as seals without hydration. Dry bentonite may be used if sufficient time to hydrate the seal is allowed. Seal hydration requires the periodic addition of clean water. Optionally, seals in this situation may be a cement/bentonite mixture containing up to 10 percent bentonite by weight. This type of mixture shall be tremied to the desired depth in the borehole.

The borehole annulus will be grouted with seal materials to within 3 feet of the ground surface. Drill cuttings, even those known not to be contaminated, will not be used as backfill material.

4.2.7 Well Completion

The drilling subcontractor will cut the top of the well to the desired height and install a vented (if possible), locking cap. The upper portion of the well casing can optionally be drilled to allow venting. Well casings are usually cut to be a certain height above ground surface (typically 2.5 to 3 feet) or are cut to be flush with the ground surface.

4.2.8 Protective Casing/Concrete Pad Installation

The drilling subcontractor will install a steel guard pipe on the well as a protective casing. The borehole around the guard pipe will be dug out to an approximate 2 to 3-foot radius to a minimum depth of 1 foot at the center and 6 inches at the edges. After installing the protective casing, the excavation will be filled with a concrete/sand mix. The surface of the concrete pad will be sloped so that drainage occurs away from the well. Flush-mount protective casings may not require an extensive concrete pad and should be completed such that they are slightly mounded above the surrounding surface to prevent surface water from running over or ponding on top of the casing. It should be noted, however, that in areas subject to snowfall, flush-mount casings may have to be installed so that they are entirely flush with the ground surface as they may be damaged by snow plows.

Above-ground protective casings should also be vented or should have non-air tight caps. Road box installations should not be vented. Installation of additional guard pipes may be necessary around above-ground well completions in traffic areas. Protective casings should be lockable to prevent unauthorized access.



4.2.9 Well Numbering

The project geologist/engineer will number each well casing with an indelible marker or paint to identify the well. This is particularly important with nested or paired wells to distinguish between shallow and deep wells. The well should be labeled on both the outside of the protective casing and inside beneath the protective casing lid.

4.2.10 Measuring Point Identification

The project geologist/engineer will mark the measuring point from which water level measurements will be made at a specific location along the upper edge of the well casing. PVC wells can easily be notched with a pocket knife or saw. Stainless steel wells (or PVC wells) can be marked with a waterproof marker on the outside of the well casing with an arrow pointing to the measuring point location. The measuring point is the point which will require surveying during the well elevation survey task.

4.2.11 Well Measurements

Upon completion, the following well measurements should be taken by the project geologist/engineer and recorded on the well construction diagram (Figure 1):

- Depth to static water level if water level has stabilized,
- Total length of well measured from top-of-well casing,
- Height of well casing above ground surface,
- Height of protective casing above ground surface,
- Depth of bottom of protective casing below ground surface (may be estimated).

Well screen filter pack, bentonite seal and annular seal thicknesses and depths should also be recorded on the well construction diagram.



4.2.12 Disposal of Drilling Wastes

Drill cuttings and other investigation-derived wastes such as drilling mud or well development/purge water must be properly contained and disposed of. Site-specific requirements for collection and removal of these waste materials should be outlined within the project work plan. Containment of these materials should be performed by the drilling subcontractor.

4.2.13 Well Development

At some point after installation of a well and prior to use of the well for water-level measurements or collection of water quality samples, development of the well shall be undertaken in accordance with ENSR SOP-7221 (Monitoring Well Development). Well development may be performed by the drilling subcontractor if contracted to do so, or by the project geologist/engineer or other project staff.

4.2.14 Well Elevation Survey

At the completion of the well installation program, all monitoring wells are usually surveyed to provide, at a minimum, the top-of-casing measuring point elevation for water level monitoring purposes. Other surveyed points which may be required by the project work plan include: ground surface elevation, top of protective casing elevation, and well coordinate position. Well elevation surveys are usually conducted by a surveying subcontractor.

5.0 QUALITY CONTROL

Certain quality control measures should be taken to ensure proper well completion.

- 5.1 The borehole will be checked for total open depth, and extended by further drilling or shortened by backfilling, if necessary, before any well construction materials are placed.
- Water level and non-aqueous phase liquid (NAPL) presence will be checked during well installation to ensure that the positions of well screen, sand pack, and seal, relative to water level, conform to project requirements.
- 5.3 The depth to the top of each layer of packing (i.e., sand, bentonite, grout, etc.) will be verified and adjusted if necessary to conform to project requirements before the next layer is placed.



5.4 If water or other drilling fluids have been introduced into the boring during drilling or well installation, samples of these fluids may be required for analysis of chemical constituents of interest at the site.

6.0 DOCUMENTATION

All well construction data will be recorded on the Monitoring Well Construction Detail form (Figure 1). All wells will be referenced onto the appropriate site map. A field notebook and/or boring log will be used as additional means of recording data. In no case will the notebook or boring log take the place of the well construction diagram.

7.0 TRAINING/QUALIFICATIONS

Well construction and installation requires a moderate degree of training and experience as numerous drilling situations may occur which will require field decisions to be made. It is recommended that inexperienced personnel be supervised for several well installations before working on their own. Experienced drillers are also of great assistance with problem resolution in the field. Field personnel should be health and safety certified as specified by OSHA (29 CFR 1910.120(e)(3)(i)) to work on sites where hazardous waste materials are considered to be present.

8.0 REFERENCES

1. Standard References for Monitoring Wells, Massachusetts Department of Environmental Protection, WSC-310-91, 1991.



APPENDIX: DEFINITIONS

Annulus: The measured width between the borehole wall and the outside of the well screen or riser pipe.

Bentonite Seal: A granular, chip, or pellet-size bentonite material that is often used to provide an annular seal above the well screen filter pack. This seal is typically installed dry followed by in-place hydration with or without the addition of water. Hydrated bentonite is sometimes used as a grout seal.

Bottom Cap/Plug: Threaded or slip-on cap placed at the bottom of the well prior to installation. Often serves as a sump for accumulation of silt which settles within the well. The measured length from the lowermost well screen slot to the bottom of the bottom cap is known as the sump or tail pipe portion of the well.


Centralizers: Stainless steel expansion clamps which, when fitted to well screens or riser pipe, expand to contact the borehole walls positioning the well centrally within the open borehole. Centralizers assist with even positioning and distribution of filter pack and sealant materials and assist with maintaining well plumbness.

Expansion Cap/Well Cap: Cap used to cover the opening at the top of the well riser pipe. Expansion caps are equipped with a rubber gasket and threaded wing nut which, when turned, provides a watertight seal. Expansion caps may also be locked, and generally are recommended for use with flush-constructed wells where road box protective casings are also used. Other well caps may include slip-on or threaded caps made of the same material as the well casing.

Filter Pack: A well-graded, clean sand or gravel placed around the well screen to act as a filter in preventing the entry of very fine soil particles into the well.

Grout Seal: A cement/bentonite mixture used to seal a borehole that has been drilled to a depth greater than the final well installation depth or to seal the remaining borehole annulus once the well has been installed. Occasionally, pure cement or pure bentonite is used as a grout seal.

Measuring Point: A selected point at the top of the well casing (riser pipe) used for obtaining periodic water-level measurements. The measuring point should consist of either a notch or indelibly marked point on the upper surface of the casing. Typically, the highest point on the casing (if not level) is used as the measuring point. The measuring point is also the point that is surveyed when well elevation data is obtained.





Protective Casing: A locking metal casing, placed around that portion of the well riser pipe that extends above the ground surface. The protective casing is generally cemented in place when the concrete pad is constructed around the well.

Riser Pipe: The section of unperforated well casing material used to connect the well screen with the ground surface. Frequently, it is made of the same material and has the same diameter as the well screen. Riser pipe is typically available pre-cleaned and pre-threaded for immediate use.

Road Box: A protective casing that is flush-mounted with the ground around a well installation. Road boxes are used in areas where the monitoring well cannot extend above the ground surface for traffic or security reasons. Road boxes usually require a special key to open.


Tremie Pipe: A small diameter pipe which fits in the open borehole annulus and is used to inject filter sands or hydrated seal materials under pressure.

Well Screen: That portion of the well casing material that is perforated in some manner so as to provide a hydraulic connection to the aquifer. Typically a well screen is purchased pre-slotted, pre-cleaned, and pre-threaded for immediate use.

Vent Hole: Small diameter hole drilled in the upper portion of the well riser pipe which provides atmospheric venting of the well. Allows for constant equilibration of the water level with changing atmospheric conditions. In flood-prone areas, or with flush-mount wells, vent holes should not be used.



Figure 1 Monitoring Well Construction Detail





Monitoring Well Development

Date: 4th Qtr., 1994

Revision Number: 2

Author: Charles Martin

Discipline: Geosciences

1.0 PURPOSE AND APPLICABILITY

1.1 Purpose and Applicability

This SOP describes the methods used for developing newly installed monitoring wells and/or existing wells which may require redevelopment/rehabilitation. This SOP is applicable to monitoring wells and/or small diameter recovery wells and piezometers.

Monitoring well development and/or redevelopment is necessary for several reasons:

- To improve/restore hydraulic conductivity of the surrounding formations as they
 have likely been disturbed during the drilling process, or may have become
 partially plugged with silt,
- To remove drilling fluids (water, mud), when used, from the borehole and surrounding formations, and
- To remove residual fines from well filter materials and reduce turbidity of groundwater, therefore, reducing the chance of chemical alteration of groundwater samples caused by suspended sediments.

Respective state or federal agency (regional offices) regulations may require specific types of equipment for use or variations in the indicated method of well development. Deviations from this SOP to accommodate other regulatory requirements should be reviewed in advance of the field program, should be explained in the project work plan, and must be documented in the field project notebook when they occur.

1.2 General Principles

Well development generally involves withdrawal of an un-specified volume of water from a well using a pump, surge block or other suitable method such that, when completed effectively, the well is in good or restored hydraulic connection with the surrounding water bearing unit and is suitable for obtaining representative groundwater samples or for other testing purposes.



1.3 Quality Assurance Planning Considerations

Field project personnel should follow specific quality assurance guidelines as outlined in the site-specific Quality Assurance Project Plan (QAPP) and/or Sampling Plan. The plan should indicate the preferred method of well development at a particular site based on project objectives, aquifer conditions, and agency requirements. Specific well performance criteria such as low turbidity values to be achieved following well development should also be specified as well as any requirements for collection/containerization and disposal of well development water.

1.4 Health and Safety Considerations

Monitoring well development may involve chemical hazards associated with materials in the soil or aquifer being characterized and may involve physical hazards associated with use of well development equipment. When wells are to be installed and developed on hazardous waste investigation sites, a Health and Safety Plan must be prepared and approved by the Health and Safety Officer before field work commences. This plan must be approved by the project Health and Safety Officer before work commences, must be distributed to all field project personnel, and must be adhered to as field activities are performed.

2.0 RESPONSIBILITIES

2.1 Project Geologist/Engineer

Development or oversight of development of new monitoring wells is the responsibility of the project geologist/engineer involved in the original installation of the well. Records of well development methods and results will be retained in the project file.

2.2 Project Manager

The project manager is responsible for ensuring that the appropriate method of well development has been chosen which best meets project objectives, site hydrogeologic conditions, and/or relevant regulatory requirements.

3.0 REQUIRED MATERIALS

Well development can be performed using a variety of methods and equipment. The specific method chosen for development of any given well is governed by the purpose of the



well, well diameter and materials, depth, accessibility, geologic conditions, static water level in the well, and type of contaminants present, if any.

The following list of equipment, each with their own particular application, may be used to develop and/or purge monitoring wells.

3.1 Bailer Purging

A bailer is used to purge silt-laden water from wells after using other devices such as a surge block. In some situations, the bailer can be used to develop a well by bailing and surging, often accompanied with pumping. A bailer should be used for purging in situations where the depth to static water is greater than 25 feet and/or where insufficient hydraulic head is available for use of other development methods.

3.2 Surge Block Development

Surge blocks are commercially available for use with Waterra[™]-type pumping systems or may be manufactured using a rubber or teflon "plunger" attached to a rod or pipe of sufficient length to reach the bottom of the well. Well drillers usually can provide surge blocks if requested. A recommended design is shown in Figure 1.

3.3 Pump Development

A pump is often necessary to remove large quantities of silt-laden ground water from a well after using the surge block. In some situations, the pump alone can be used to develop the well and remove the fines by overpumping. Since the purpose of well development is to remove suspended solids from a well and surrounding filter pack, the pump must be capable of moving some solids without damage. The preferred pump is a submersible pump which can be used in both shallow and deep ground water situations. A centrifugal pump may be used in shallow wells but will work only where the depth to static ground water is less than approximately 25 feet. Pumping may not be successful in low-yielding aquifer materials or in wells with insufficient hydraulic head.

3.4 Compressed Gas Development

Compressed gas, generally nitrogen from a tank or compressed air through a compressor, can be used to both surge and develop a monitoring well. The method works by injection of compressed gas at the bottom of the water column, driving sediment-laden water to the surface. Compressed gas can also be used for "jetting" - a process by which the gas is directed at the slots in the well screen to cause



turbulence (thereby disturbing fine materials in the adjacent filter pack). Compressed gas is not limited by any depth range.

Since the compressed gas will be used to "lift" water from the monitoring well, provisions must be made for controlling the discharge from contaminated wells. This is generally accomplished by attaching a "tee" discharge to the top of the casing and providing drums to contain the discharged water. Gas-lifting should never be done in contaminated wells without providing a means to control discharge.

3.5 Other Required Materials:

- Well development records (Figure 2)
- Health and Safety equipment
- Equipment decontamination materials
- Water quality instrumentation: nephelometer, pH, temperature, specific conductance meters, as required
- Field project notebook/pen

4.0 METHOD

- **4.1** General Preparation
 - **4.1.1** Well Records Review: Well completion diagrams should be reviewed to determine well construction characteristics. Formation characteristics should also be determined from review of available boring logs.
 - 4.1.2 Site Preparation: Well development, similar to groundwater sampling, should be conducted in as clean an environment as possible. This usually requires, at a minimum, placing sheet plastic on the ground to provide a clean working area for development equipment.
 - 4.1.3 IDW Containment: Provisions should be in place for collection and management of investigation-derived wastes (IDW), specifically well development water and miscellaneous expendable materials generated during the development process. The collection of IDW in drums or tanks may be required depending on project-specific requirements. The QAPP should specify the requirements for IDW containment.



- 4.1.4 Water Level/Well Depth Measurement: The water level and well depth should be measured with a water level indicator and written on the well development record. This information is used to calculate the volume of standing water (i.e., the well volume) within the well.
- **4.1.5** Equipment Decontamination: All down-well equipment should be decontaminated prior to use in accordance with ENSR SOP-7600 (Decontamination of Equipment).
- 4.1.6 Removal of Drilling Fluids: Drilling fluids such as mud or water, if used during the drilling and well installation process, should be removed during the well development procedure. It is recommended that a minimum of 1.5 times the volume of added fluid be removed from the well during development. Drilling muds should initially have been flushed from the drilling casing during the well installation procedure with water added during the flushing process. If the quantity of added fluid is not known or could not be reasonably estimated, removal of a minimum of 10 well volumes of water is recommended during the development procedure.

4.2 Development Procedures

4.2.1 Development Method Selection

The construction details of each well shall be used to define the most suitable method of well development. Some consideration should be given to the potential degree of contamination in each well as this will impact IDW containment requirements.

The criteria for selecting a well development method include well diameter, total well depth, static water depth, screen length, the likelihood and level of contamination, and characteristics of the geologic formation adjacent to the screened interval.

The limitations, if any, of a specific procedure are discussed within each of the following procedures.

4.2.2 General Water Quality Measurements

Measure and record water temperature, pH, specific conductance, and turbidity periodically during development using the available water quality instruments. These measurements will aid in determining whether well



development is proceeding efficiently, will assist in identifying when well development is complete, will determine whether the development process is effective or not with any given well and, potentially, may identify well construction irregularities (i.e., grout in well, poor well screen slot-size selection). Water quality parameters should be checked a minimum of 3 to 5 times during the development process.

4.2.3 Bailer Procedure

- As stated previously, bailers shall preferably not be used for well development but may be used in combination with a surge block to remove silt-laden water from the well.
- When using a bailer to purge well water; select the appropriate bailer, then tie a length of bailer cord onto the end of it.
- Lower the bailer into the screened interval of the monitoring well. Silt, if present, will generally accumulate within the lower portions of the well screen.
- The bailer may be raised and lowered repeatedly in the screened interval to further simulate the action of a surge block and pull silt through the well screen.
- Remove the bailer from the well and empty it into the appropriate storage container.
- Continue surging/bailing the well until sediment-free water is obtained.
 If moderate to heavy siltation is still present, the surge block procedure should be repeated and followed again with bailing.
- Check water quality parameters periodically.

4.2.4 Surge Block Procedure

A surge block effectively develops most monitoring wells. This device
first forces water within the well through the well screen and out into the
formation, and then pulls water back through the screen into the well
along with fine soil particles. Surge blocks may be manufactured to
meet the design criteria shown in the example (Figure 1) or may be



purchased as an adaptor to fit commercially available well purging systems such as the Waterra system.

- Insert the surge block into the well and lower it slowly to the level of static water. Start the surge action slowly and gently above the well screen using the water column to transmit the surge action to the screened interval. A slow initial surging, using plunger strokes of approximately 3 feet, will allow material which is blocking the screen to separate and become suspended.
- After 5 to 10 plunger strokes, remove the surge block and purge the well using a pump or bailer. The returned water should be heavily laden with suspended silt and clay particles. Discharge the purged water into the appropriate storage container.
- Repeat the process. As development continues, slowly increase the
 depth of surging to the bottom of the well screen. For monitoring wells
 with long screens (greater than 10 feet) surging should be undertaken
 along the entire screen length in short intervals (2 to 3 feet) at a time.
 Continue this cycle of surging and purging until the water yielded by the
 well is free of visible suspended material.
- Check water quality parameters periodically.

4.2.5 Pump Procedure

- Well development using only a pump is most effective in monitoring wells that will yield water continuously. Theoretically, pumping will increase the hydraulic gradient and velocity of groundwater near the well by drawing the water level down. The increased velocity will move residual fine soil particles into the well and clear the well screen of this material. Effective development cannot be accomplished if the pump has to be shut off to allow the well to recharge.
- When using a submersible pump or surface pump, set the intake of the pump or intake line in the center of the screened interval of the monitoring well.
- Pump a minimum of three well volumes of water from the well and raise and lower the pump line through the screened interval to remove any silt/laden water.



- Continue pumping water from the well until sediment-free water is obtained. This method may be combined with the manual surge block method if well yield is not rapid enough to extract silt from the surrounding formations.
- Check water quality parameters periodically.

4.2.6 Compressed Gas Procedure

- Although the equipment used to develop a well using this method is more difficult to obtain and use, well development using compressed gas is considered to be a very effective method. This method is also not limited by well depth, well diameter, or depth to static water. Caution must be exercised, however, in highly permeable formations not to inject gas into the formation. Drilling subcontractors will often provide the necessary materials as well as perform this method, if requested. When using a compressor, an oil-less compressor should be used, or an oil trap/filter should be placed on the air discharge line which enters the well.
- Lower the gas line into the well, setting it near the bottom of the screened interval. Install the discharge control equipment (i.e., tee fitting) at the well head.
- Set the gas flow rate to allow continuous discharge of water from the well.
- At intervals during gas-lifting, especially when the discharge begins to contain less suspended material, shut off the air flow and allow the water in the well to backflush through the screened interval to disturb any bridging that may have occurred. Re-establish the gas flow when the water level in the well has returned to the pre-development level.
- Continue gas-lifting and/or jetting until the discharged water is free from suspended material.
- Check water quality parameters periodically.



5.0 QUALITY CONTROL

A well has been successfully developed when one or more of the following criteria are met:

- The sediment load in the well has been eliminated or greatly reduced. Regulatory requirements may be in place which state that water turbidity values ranging from 5 to 50 NTU must be achieved at the end of the development procedure. Use of a nephelometer is required during the well development procedure to measure water turbidity if meeting a specific turbidity value is required by the regulations. Attaining low turbidity values in fine-grained formations may be difficult to achieve.
- Permeability tests conducted in accordance with ENSR SOP-7720 (Hydraulic Conductivity Testing) yield repeatable hydraulic conductivity values.

6.0 DOCUMENTATION

The Monitoring Well Development Record (Figure 2) will be completed by the geologist or hydrogeologist conducting the development. In addition, a field project notebook should be maintained detailing any problems or unusual conditions which may have occurred during the development process.

7.0 TRAINING/QUALIFICATIONS

Well development procedures vary in complexity. It is recommended that initial development attempts be supervised by more experienced personnel. Field personnel should be health and safety certified as specified by OSHA (29 CFR 1910.120(e)(3)(i)) to work on sites where hazardous waste materials are considered to be present.

8.0 REFERENCES

<u>Standard References for Monitoring Wells</u>, Massachusetts Department of Environmental Protection, WSC-310-91, 1991.



APPENDIX: DEFINITIONS

Bridging: A condition within the filter pack outside the well screen whereby the smaller particles are wedged together in a manner that causes blockage of pore spaces.

Hydraulic Conductivity: a characteristic property of aquifer materials which describes the permeability of the material with respect to flow of water.

Hydraulic Connection: A properly installed and developed monitoring well should have good hydraulic connection with the aquifer. The well screen and filter material should not provide any restriction to the flow of water from the aquifer into the well.

Permeability Test: Used to determine the hydraulic conductivity of the aquifer formation near a well screen. Generally conducted by displacing the water level in a well and monitoring the rate of recovery of the water level as it returns to equilibrium. Various methods of analysis are available to calculate the hydraulic conductivity from these data.

Static Water Level: The water level in a well that represents an equilibrium or stabilized condition, usually with respect to atmospheric conditions in the case of monitoring wells.

Well Surging: That process of moving water in and out of a well screen to remove fine sand, silt and clay size particles from the adjacent formation.

Well Purging: The process of removing standing water from a well to allow surrounding formation water to enter the well.

Well Screen: That portion of the well casing material that is perforated in some manner so as to provide a hydraulic connection to the aquifer. The perforated, or slotted, portion of a well is also known as the screened interval.



Figure 1 Recommended Surge Block Design

SURGE BLOCK DESIGN (Not to Scale)

Steel washers should be 1/2" to 3/4" smaller in diameter than the well ID. Gasket can be rubber or leather and should be the same diameter or 1/8" smaller than the well ID to compensate for swelling of the leather/ Rod can be steel, fiberglass, or plastic but must be strong and lightweight.






Figure 2 Well Development Record

PROJECT NUMBER:		WELL I.D.:	LOCATION:	
		DEVELOPER:		
ORIGINAL DEVELOPMENT	REDEVELOPMENT	ORIGINAL DEVELOPMEN	IT DATE:	
	Geology at Screened I			
Well Diameter:				
Total Well Depth:	Likely Contaminants:			
Double to Transf Course				
Depth to Top of Screen:				
Depth to Bottom of Screen:	Purge Water & Sedim	Purge Water & Sediment Disposal Method:		
Depth to Static Water Level:				
DEVELOPMENT METHOD	PURG	E METHOD	PERMEABILITY TEST RESULTS	
	ACCEPTA	NCE CRITERIA		