

# El Dorado Environmental, Inc.

---

2221 Goldorado Trail, El Dorado, California 95623

(916) 626-3898  
Fax (916) 626-3899

January 29, 1997

Mr. Terrence A. Fox  
Senior Project Manager  
Ultramar Inc.  
525 West Third Street  
Hanford, California 93230

Subject: **Fourth Quarter 1996 Ground Water Monitoring Report**  
Beacon Station #604  
1619 West First Street, Livermore, California

Dear Mr. Fox:

El Dorado Environmental, Inc. (EDE) has prepared this report to document the results of quarterly ground water monitoring conducted on December 2, 1996 at the subject site (Figure 1). Field work, conducted by Doulos Environmental (Doulos), included measurements of depth to ground water, subjective analysis of ground water in wells for the presence or absence of free petroleum product, well purging, and collection of ground water samples. Doulos reports that all field activities were conducted in accordance with field procedures described in Attachment A.

## GROUND WATER ELEVATIONS

Prior to well purging, Doulos measured the depth to ground water in each well at the site. Ground water elevation data collected at the site since June 1993 are compiled in Table 1. Copies of Doulos' field data sheets are contained in Attachment B. Current depth to ground water measurements indicate directions of ground water flow toward the northeast and the northwest (Figure 2) at gradients of approximately 0.02 foot per foot. Historically, the direction of ground water flow has consistently been toward the northwest. Ground water elevations beneath the site have increased an average of 3.77 feet since the previous monitoring event.

## GROUND WATER SAMPLING AND ANALYSIS

Ground water samples were collected from five monitoring wells at the site. Each sample collected was analyzed for concentrations of dissolved:

- benzene, toluene, ethylbenzene, and total xylenes (BTEX), by EPA method 602
- total petroleum hydrocarbons as gasoline (TPHg), by modified EPA method 8015

Analytical results since June 1993 are compiled in Table 2; copies of certified analytical reports for ground water samples collected during the current monitoring event are contained in Attachment C. Benzene was not present at detectable concentrations in the ground water sample collected from monitoring well MW-1. Dissolved benzene concentrations decreased in the ground water samples collected from monitoring wells MW-5, MW-6, and MW-7 and increased in the sample collected from monitoring well MW-2 compared to the most recent sampling event.. Figure 3 illustrates the current interpreted distribution of dissolved benzene in ground water underlying the site.

A copy of this quarterly monitoring report should be submitted to:

Ms. Eva Chu  
Department of Environmental Health  
Alameda County Health Care Services  
80 Swan Way, Room 20  
Oakland, California 94612

Mr. Cecil Fox  
California Regional Water Quality Control  
Board, San Francisco Bay Region  
2101 Webster Street, Room 500  
Oakland, California 94612

The interpretations and/or conclusions contained in this report represent our professional opinions. These opinions are based on currently available information. Other than this, no warranty is implied nor intended. This report has been prepared solely for the use of Ultramar Inc. Any reliance upon or use of this report by third parties will be at such parties' sole risk.

If you have any comments or questions, please contact the undersigned at (916) 626-3898.

Regards,


EL DORADO ENVIRONMENTAL, INC.



Dale A. van Dam, R.G.  
Hydrogeologist

DAvD/davd

Attachments



**FIGURES:**

FIGURE 1 ..... SITE LOCATION MAP

FIGURE 2 ..... GROUND WATER CONTOUR MAP  
DECEMBER 2, 1996

FIGURE 3 ..... DISSOLVED BENZENE DISTRIBUTION MAP  
DECEMBER 2, 1996

**TABLES:**

TABLE 1 ..... GROUND WATER ELEVATION DATA


TABLE 2 ..... GROUND WATER ANALYTICAL RESULTS

**ATTACHMENTS:**

A ..... ULTRAMAR FIELD PROCEDURES


B ..... DOULOS ENVIRONMENTAL  
FIELD DATA SHEETS

C ..... LABORATORY REPORT AND  
CHAIN-OF-CUSTODY FORM



SOURCE: STREET ATLAS U.S.A., DeLORNE MAPPING, 1994

<b>SITE LOCATION MAP</b>		<b>FIGURE 1</b>
BEACON STATION #604 1619 WEST FIRST STREET LIVERMORE, CALIFORNIA		PROJECT NUMBER: U013.01
		DRAWN BY: D.A.V.D.
EL DORADO ENVIRONMENTAL, INC.		CHECKED BY: DJD




### EXPLANATION

- SB-4 ● Soil Boring Location and Number
- VW-3 ● Vadose Well Location and Number
- MW-5 ● Monitoring Well Location and Number
- [71.86] Ground Water Elevation in Feet
- - - 72.00 - - - Line of Equal Elevation of Ground Water Measured in Feet
- ↗ Inferred Direction of Ground Water Flow




SOURCE: FIGURE MODIFIED FROM DRAWING PROVIDED BY ACTON-MICKELSON-ENVIRONMENTAL, INC.

GROUND WATER CONTOUR MAP, DECEMBER 2, 1996	FIGURE 2
BEACON STATION #604 1619 WEST FIRST STREET LIVERMORE, CALIFORNIA	PROJECT NUMBER U013.01
	DRAWN BY: D.A.V.D.
EL DORADO ENVIRONMENTAL, INC.	CHECKED BY: D.V.D.



### EXPLANATION

- SB-4 ● Soil Boring Location and Number
- VW-3 ● Vadose Well Location and Number
- MW-5 ● Monitoring Well Location and Number
- [1.1] Benzene Concentration in Micrograms/Liter
- [NS] Monitoring Well Not Sampled
- - - 50 - - - Benzene Isoconcentration Line in Micrograms per Liter



SOURCE: FIGURE MODIFIED FROM DRAWING PROVIDED BY ACTON\*MICKELSON\*ENVIRONMENTAL, INC.

DISSOLVED BENZENE DISTRIBUTION MAP, DECEMBER 2, 1996		FIGURE 3
BEACON STATION #604 1619 WEST FIRST STREET LIVERMORE, CALIFORNIA		PROJECT NUMBER: U013.01
		DRAWN BY: D.A.v.D.
EL DORADO ENVIRONMENTAL, INC.		CHECKED BY: D.v.D.

**TABLE 1  
GROUND WATER ELEVATION DATA**

**Beacon Station #604  
1619 West First Street, Livermore, California**

Monitoring Well	Top of Riser (feet)	Depth to Top/Bottom of Screened Interval (feet)	Monitoring Date	Depth to Water (feet)	Ground Water Elevation (feet)	Physical Observation
MW-1	100.00	34/54	06/01/93	37.50	62.50	No Product
			06/22/93	38.46	61.54	No Product
			10/06/93	42.22	57.78	No Product
			01/13/94	34.52	65.48	No Product
			03/30/94	31.93	68.07	No Product
			04/25/94	33.49	66.51	No Product
			08/12/94	41.03	58.97	No Product
			12/14/94	38.63	61.37	No Product
			02/10/95	30.80	69.20	No Product
			06/15/95	25.46	74.54	No Product
			09/26/95	31.05	68.95	No Product
			12/15/95	28.11	71.89	No Product
			03/21/96	17.67	82.33	No Product
			06/13/96	22.86	77.14	No Product
09/16/96	30.04	69.96	No Product			
12/02/96	26.74	73.26	No Product			
MW-2	98.68	34/54	06/01/93	38.02	60.66	No Product
			06/22/93	39.07	59.61	No Product
			10/06/93	43.72	54.96	No Product
			01/13/94	35.85	62.83	No Product
			03/30/94	32.82	65.86	No Product
			04/25/94	34.76	63.92	No Product
			08/12/94	44.33	54.35	No Product
			12/14/94	40.00	58.68	No Product
			02/10/95	32.16	66.52	No Product
			06/15/95	25.93	72.75	No Product
			09/26/95	32.42	66.26	No Product
			12/15/95	29.41	69.27	No Product
			03/21/96	17.47	81.21	No Product
			06/13/96	23.69	74.99	No Product
09/16/96	31.24	67.44	No Product			
12/02/96	26.90	71.78	No Product			

See notes at end of table



**TABLE 1  
GROUND WATER ELEVATION DATA**

**Beacon Station #604  
1619 West First Street, Livermore, California**

Monitoring Well	Top of Riser (feet)	Depth to Top/Bottom of Screened Interval (feet)	Monitoring Date	Depth to Water (feet)	Ground Water Elevation (feet)	Physical Observation
MW-3	97.08	33/53	06/01/93	36.18	60.90	No Product
			06/22/93	37.11	59.97	No Product
			10/06/93	41.15	55.93	No Product
			01/13/94	33.95	63.13	No Product
			03/30/94	30.97	66.11	No Product
			04/25/94	32.46	64.62	No Product
			08/12/94	41.72	55.36	No Product
			12/14/94	37.62	59.46	No Product
			02/10/95	29.96	67.12	No Product
			06/15/95	23.66	73.42	No Product
			09/26/95	29.62	67.46	No Product
			12/15/95	27.10	69.98	No Product
			03/21/96	15.85	81.23	No Product
			06/13/96	21.31	75.77	No Product
09/16/96	28.62	68.46	No Product			
12/02/96	25.55	71.53	No Product			
MW-4	99.35	27/47	03/30/94	31.56	67.79	No Product
			04/25/94	32.73	66.62	No Product
			08/12/94	41.61	57.74	No Product
			12/14/94	38.11	61.24	No Product
			02/10/95	30.50	68.85	No Product
			06/15/95	23.63	75.72	No Product
			09/26/95	29.70	69.65	No Product
			12/15/95	27.56	71.79	No Product
			03/21/96	15.63	83.72	No Product
			06/13/96	21.07	78.28	No Product
			09/16/96	28.99	68.09	No Product
12/02/96	26.04	71.04	No Product			

See notes at end of table

**TABLE 1  
GROUND WATER ELEVATION DATA**

**Beacon Station #604  
1619 West First Street, Livermore, California**

Monitoring Well	Top of Riser (feet)	Depth to Top/Bottom of Screened Interval (feet)	Monitoring Date	Depth to Water (feet)	Ground Water Elevation (feet)	Physical Observation
MW-5	98.37	27/47	03/30/94	32.07	66.30	No Product
			04/25/94	33.65	64.72	No Product
			08/12/94	42.73	55.64	No Product
			12/14/94	38.89	59.48	No Product
			02/10/95	31.44	66.93	No Product
			06/15/95	24.99	73.38	No Product
			09/26/95	30.20	68.17	No Product
			12/15/95	28.56	69.81	No Product
			03/21/96	16.82	81.55	No Product
			06/13/96	22.61	75.76	No Product
			09/16/96	29.78	68.59	No Product
12/02/96	26.51	71.86	No Product			
MW-6	97.62	28/48	03/30/94	33.38	64.24	No Product
			04/25/94	35.49	62.13	No Product
			08/12/94	45.14	52.48	No Product
			12/14/94	40.99	56.63	No Product
			02/10/95	33.34	64.28	No Product
			06/15/95	26.88	70.74	No Product
			09/26/95	33.55	64.07	No Product
			12/15/95	30.32	67.30	No Product
			03/21/96	18.89	78.73	No Product
			06/13/96	24.62	73.00	No Product
			09/16/96	32.64	65.73	No Product
12/02/96	27.42	70.95	No Product			

See notes at end of table

**TABLE 1  
GROUND WATER ELEVATION DATA**

**Beacon Station #604  
1619 West First Street, Livermore, California**

Monitoring Well	Top of Riser (feet)	Depth to Top/Bottom of Screened Interval (feet)	Monitoring Date	Depth to Water (feet)	Ground Water Elevation (feet)	Physical Observation
MW-7	98.03	27/47	03/30/94	31.98	66.05	No Product
			04/25/94	33.56	64.47	No Product
			08/12/94	43.35	54.68	No Product
			12/14/94	39.34	58.69	No Product
			02/10/95	32.11	65.92	No Product
			06/15/95	25.51	72.52	No Product
			09/26/95	31.43	66.60	No Product
			12/15/95	28.97	69.06	No Product
			03/21/96	17.36	80.67	No Product
			06/13/96	23.47	74.56	No Product
			09/16/96	31.35	67.02	No Product
			12/02/96	27.11	71.26	No Product

Note: Monitoring well casing elevations were surveyed relative to an arbitrary bench mark at the top of the casing of monitoring well MW-1 with an assumed elevation of 100.00 feet.

**TABLE 2  
GROUND WATER ANALYTICAL RESULTS**

**Beacon Station #604  
1619 West First Street, Livermore, California  
Concentrations in micrograms per Liter**

Monitoring Well	Monitoring Date	Benzene	Toluene	Ethylbenzene	Xylenes	Total Petroleum Hydrocarbons as Gasoline
MW-1	06/01/93	2200	400	< 50	4900	27000
	06/22/93	8000	10000	260	10000	87000
	10/06/93	4700	6500	740	5300	40000
	01/13/94	1300	950	110	850	9400
	04/25/94	1500	1800	290	1700	11000
	08/12/94	550	330	260	1400	11000
	12/14/94	1000	1200	320	1500	11000
	02/10/95	1200	1500	280	1500	9300
	06/15/95	5.6	< 0.50	< 0.50	< 0.50	140
	09/26/95	140	< 0.50	< 0.50	43	410
	12/15/95	250	< 1.3	< 1.3	87	740
	03/21/96	0.52	< 0.50	< 0.50	0.51	< 50
	06/13/96	< 0.50	< 0.50	< 0.50	< 0.50	240*
	09/16/96	70	< 0.50	1.0	5.1	720
	12/02/96	< 0.50	< 0.50	< 0.50	< 0.50	< 50
MW-2	06/01/93	20000	21000	3300	18000	170000
	06/22/93	19000	22000	3500	18000	160000
	10/06/93	17000	17000	3000	15000	110000
	01/13/94	20000	19000	2300	14000	93000
	04/25/94	9600	7300	840	7800	41000
	08/12/94	11000	11000	2300	11000	59000
	12/14/94	13000	13000	2200	12000	63000
	02/10/95	12000	12000	2200	11000	63000
	06/15/95	11000	12000	1900	11000	61000
	09/26/95	9400	11000	2300	12000	61000
	12/15/95	8000	8300	2200	12000	48000
	03/21/96	8000	7700	2400	12000	48000
	06/13/96	7300	8800	1900	12000	33000
	09/16/96	510	640	180	1300	8600
	12/02/96	4400	4000	1300	6100	29000

See notes at end of table

**TABLE 2  
GROUND WATER ANALYTICAL RESULTS**

**Beacon Station #604  
1619 West First Street, Livermore, California  
Concentrations in micrograms per Liter**

Monitoring Well	Monitoring Date	Benzene	Toluene	Ethylbenzene	Xylenes	Total Petroleum Hydrocarbons as Gasoline
MW-3	06/01/93	4.6	<0.50	<0.50	1.9	270
	06/22/93	8.2	<0.50	<0.50	0.72	160
	10/06/93	57	110	24	120	740
	01/13/94	2.6	0.67	0.78	4.2	83
	04/25/94	0.75	3.2	0.50	3.6	60
	08/12/94	7.3	14	2.6	13	310
	12/14/94	<0.50	<0.50	<0.50	<0.50	75
	02/10/95	1.4	<0.50	<0.50	1.8	96
	06/15/95	<0.50	<0.50	<0.50	<0.50	<50
	09/26/95	<0.50	<0.50	<0.50	<0.50	<50
	12/15/95	<0.50	<0.50	<0.50	<0.50	<50
	03/21/96	NS	NS	NS	NS	NS
	06/13/96	NS	NS	NS	NS	NS
	09/16/96	NS	NS	NS	NS	NS
	12/02/96	NS	NS	NS	NS	NS
MW-4	03/30/94	4.2	15	2.5	26	120
	04/25/94	<0.50	1.8	<0.50	2.1	65
	08/12/94	<0.50	<0.50	<0.50	<0.50	<50
	12/14/94	<0.50	<0.50	<0.50	<0.50	<50
	02/10/95	<0.50	<0.50	<0.50	<0.50	<50
	06/15/95	<0.50	<0.50	<0.50	<0.50	<50
	09/26/95	<0.50	<0.50	<0.50	<0.50	<50
	12/15/95	<0.50	<0.50	<0.50	<0.50	<50
	03/21/96	NS	NS	NS	NS	NS
	06/13/96	NS	NS	NS	NS	NS
	09/16/96	NS	NS	NS	NS	NS
12/02/96	NS	NS	NS	NS	NS	

See notes at end of table

**TABLE 2**  
**GROUND WATER ANALYTICAL RESULTS**

**Beacon Station #604**  
**1619 West First Street, Livermore, California**  
**Concentrations in micrograms per Liter**

Monitoring Well	Monitoring Date	Benzene	Toluene	Ethylbenzene	Xylenes	Total Petroleum Hydrocarbons as Gasoline
MW-5	03/30/94	1300	20	< 13	160	7500
	04/25/94	1100	41	130	740	6500
	08/12/94	420	2.9	41	98	4000
	12/14/94	660	<2.5	33	13	4800
	02/10/95	490	< 13	23	19	5200
	06/15/95	<0.50	<0.50	<0.50	<0.50	460
	09/26/95	61	<0.50	3.1	<0.50	1400
	12/15/95	77	1.5	10	1.5	2100
	03/21/96	35	2.0	2.0	18.00	930
	06/13/96	38	0.72	1.9	2.0	610
	09/16/96	29	<0.50	0.95	<0.50	380
	12/02/96	1.1	0.64	<0.50	<0.50	200
	MW-6	03/30/94	21000	8600	1700	12000
04/25/94		22000	12000	2300	16000	77000
08/12/94		12000	8100	2200	16000	65000
12/14/94		18000	9500	2200	14000	65000
02/10/95		21000	8400	2000	14000	63000
06/15/95		20000	11000	2100	15000	75000
09/26/95		15000	9600	1700	12000	62000
12/15/95		15000	9000	2300	15000	61000
03/21/96		18000	9800	2400	16000	65000
06/13/96		8600	3300	2200	12000	29000
09/16/96		6400	1800	2100	11000	42000
12/02/96		3000	1100	970	8300	28000

See notes at end of table

**TABLE 2  
GROUND WATER ANALYTICAL RESULTS**

**Beacon Station #604  
1619 West First Street, Livermore, California  
Concentrations in micrograms per Liter**

Monitoring Well	Monitoring Date	Benzene	Toluene	Ethylbenzene	Xylenes	Total Petroleum Hydrocarbons as Gasoline
MW-7	03/30/94	7200	2400	1600	11000	43000
	04/25/94	3900	1000	940	6900	30000
	08/12/94	3800	1400	1300	7500	30000
	12/14/94	3600	1200	900	6400	31000
	02/10/95	4000	900	890	5100	27000
	06/15/95	920	680	740	4100	17000
	09/26/95	200	150	170	810	7000
	12/15/95	350	170	540	1900	11000
	03/21/96	320	100	730	2500	12000
	06/13/96	98	19	370	620	5900
	09/16/96	140	43	440	590	7800
	12/02/96	87	29	290	430	6300

NS = Well Not Sampled on This Date.

\* = Product is not typical gasoline.

**ATTACHMENT A**  
**ULTRAMAR FIELD PROCEDURES**



## ATTACHMENT A - ULTRAMAR FIELD PROCEDURES

The following section describes procedures used by field personnel in the performance of ground water sampling at Ultramar Inc. sites.

### Ground Water Level and Total Depth Determination

A water level indicator is lowered down the well and a measurement of the depth to water from an established reference point on the casing is taken. The indicator probe is used to sound the bottom of the well and a measurement of the total depth of the well is taken. Both the water level and total depth measurements are taken to the nearest 0.01-foot.

### Visual Analysis of Ground Water

Prior to purging and sampling ground water monitoring wells, a water sample is collected from each well for subjective analysis. The visual analysis involves gently lowering a clean, disposable, polyethylene bailer to approximately one-half the bailer length past the water table interface. The bailer is then retrieved, and the sample contained within the bailer is examined for floating product or the appearance of a petroleum product sheen. If measurable free product is noted in the bailer, a water/product interface probe is used to determine the thickness of the free product to the nearest 0.01-foot. The thickness of free product is determined by subtracting the depth to product from the depth to water.

### Monitoring Well Purging and Sampling

Monitoring wells are purged by removing approximately four casing volumes of water from the well using a clean disposable bailer or electrical submersible purge pump. Purge volumes are calculated prior to purging. During purging, the temperature, pH, and electric conductivity of the purge water are monitored. The well is considered to be sufficiently purged when: The four casing volumes have been removed; the temperature, pH, and conductivity values have stabilized to within 10% of the initial readings; and the ground water being removed is relatively free of suspended solids. After purging, ground water levels are allowed to stabilize to within 80% of the initial water level reading. A water sample is then collected from each well with a clean, disposable polyethylene bailer. If the well is bailed or pumped dry prior to removing the minimum volume of water, the ground water is allowed to recharge. If the well has recharged to within 80% of the initial depth to water reading within two hours, the well will continue to be purged until the minimum volume of water has been removed. If the well has not recharged to at least 80% of the initial depth to water reading within two hours, the well is considered to contain formational water and a ground water sample is collected. Ground water removed from the well is stored in 55-gallon drums at the site and labeled pending disposal.

In wells where free product is detected, the wells will be bailed to remove the free product. An estimate of the volume of product and water well be recorded. If the free product thickness is reduced to the point where a measurable thickness is no longer present in the well, a ground water sample will be collected. If free product persists throughout the purging process, a final free product thickness measurement will be taken and a ground water sample will not be collected.

Ground water samples are stored in 40-milliliter vials so that air passage through the sample is minimized (to prevent volatilization of the sample). The vial is tilted and filled slowly until an upward convex meniscus forms over the mouth of the vial. The Teflon™ side of the septum (in cap) is then placed against the meniscus, and the cap is screwed on tightly. The sample is then inverted and the bottle is tapped lightly to check for air bubbles. If an air bubble is present in the vial, the cap is removed and more sample is transferred from the bailer. The vial is then resealed and rechecked for air bubbles. The sample is then appropriately labeled and stored on ice from the time of collection through the time of delivery to the laboratory. The Chain-of-Custody form is completed to ensure sample integrity. Ground water samples are transported to a state-certified laboratory and analyzed within the U.S. Environmental Protection Agency-specified hold times for the specified analytes.

**ATTACHMENT B**

**DOULOS ENVIRONMENTAL FIELD DATA SHEETS**

**DOULOS ENVIRONMENTAL COMPANY  
GROUNDWATER/LIQUID LEVEL DATA  
(measurements in feet)**

Project Address: Beacon #604, 1619 West First Street

Date: 12-2-96

Livermore, CA

Project No.: 94-604-01

Recorded by: Hal Hansen

Well No	Time	Well Elev. TOC	Depth to Gr. Water	Measured Total Depth	Gr. Water Elevation	Depth to Product	Product Thickness	Comments
MW-1	4:02		26.74	54.12				Petroleum odor no spec
MW-2	4:25		26.90	53.73				Petroleum odor no spec
MW-3	4:06		25.55	52.50				_____
MW-4	4:10		26.04	46.64				_____
MW-5	4:13		26.51	46.31				no odor no spec
MW-6	4:21		27.42	47.51				Petroleum odor no spec
MW-7	4:17		27.11	46.58				Petroleum odor no spec

Notes:

Client: Ultramar

Sampling Date: 12-2-96

Site: Beacon #604

Project No.: 95-604-01

1619 West First Street

Well Designation: MW- 1

Livermore, CA

Is setup of traffic control devices required?  NO  YES time: \_\_\_\_\_ hours  
 Is there standing water in well box?  NO  YES Above TOC Below TOC  
 Is top of casing cut level?  NO  YES If no, see remarks  
 Is well cap sealed and locked?  NO  YES If no, see remarks  
 Height of well casing riser (in inches): \_\_\_\_\_  
 Well cover type: 8" UV \_\_\_\_\_ 12" UV \_\_\_\_\_ 12" EMCO \_\_\_\_\_ 8" BK \_\_\_\_\_  
 12" BK \_\_\_\_\_ 12" DWP \_\_\_\_\_ 12" CNI  36" CNI \_\_\_\_\_ Other \_\_\_\_\_  
 General condition of wellhead assembly: Excellent  Good Fair Poor

Purging Equipment: \_\_\_\_\_ 2" disposable bailer \_\_\_\_\_ Submersible pump  
 \_\_\_\_\_ 2" PVC bailer \_\_\_\_\_ Dedicated bailer  
 \_\_\_\_\_ 4" PVC bailer  Centrifugal pump

Sampled with: Disposable bailer:  Teflon bailer: \_\_\_\_\_

Well Diameter: 2" \_\_\_\_\_ 4"  6" \_\_\_\_\_ 8" \_\_\_\_\_

Purge Vol. Multiplier: 0.16 0.65 1.47 2.61 gal/ft.  
 Initial Measurement Recharge Measurement  
 Time: 4:02 Time: 5:07  
 Depth of well: 54.12 Depth to water: 28.10 Calculated purge: 71.8  
 Depth to water: 26.74 Actual purge: 71.8

start purge: 4:30 Sampling time: 5:08

Time	Temp.	E.C.	pH	Turbidity	Volume
4:37	64.2	1260	7.41	—	1
4:43	64.1	1131	7.36	—	2
4:55	68.2	1125	7.34	—	3
5:05	68.1	1121	7.30	—	4

Sample appearance: Clear Lock: Dolphin

Equipment replaced: (Check all that apply) Note condition of replaced item  
 2" Locking Cap: \_\_\_\_\_ Lock #3753: \_\_\_\_\_ 7/32 Allenhead: \_\_\_\_\_  
 4" Locking Cap: \_\_\_\_\_ Lock-Dolphin: \_\_\_\_\_ 9/16 Bolt: \_\_\_\_\_  
 6" Locking Cap: \_\_\_\_\_ Pinned Allenhead (DWP): \_\_\_\_\_

Remarks: \_\_\_\_\_

Signature: [Signature]

Client: Ultramar Sampling Date: 12-2-96  
 Site: Beacon #604 Project No.: 95-604-01  
1619 West First Street Well Designation: MW- 9  
Livermore, CA

Is setup of traffic control devices required?  NO  YES time: \_\_\_\_\_ hours  
 Is there standing water in well box?  NO  YES Above TOC Below TOC  
 Is top of casing cut level?  NO  YES If no, see remarks  
 Is well cap sealed and locked?  NO  YES If no, see remarks  
 Height of well casing riser (in inches): \_\_\_\_\_  
 Well cover type: 8" UV \_\_\_\_\_ 12" UV \_\_\_\_\_ 12" EMCO \_\_\_\_\_ 8" BK \_\_\_\_\_  
 12" BK \_\_\_\_\_ 12" DWP \_\_\_\_\_ 12" CNI  36" CNI \_\_\_\_\_ Other \_\_\_\_\_  
 General condition of wellhead assembly: Excellent  Good  Fair  Poor

Purging Equipment: \_\_\_\_\_ 2" disposable bailer \_\_\_\_\_ Submersible pump  
 \_\_\_\_\_ 2" PVC bailer \_\_\_\_\_ Dedicated bailer  
 \_\_\_\_\_ 4" PVC bailer  Centrifugal pump

Sampled with: Disposable bailer:  Teflon bailer: \_\_\_\_\_

Well Diameter: 2" \_\_\_\_\_ 4"  6" \_\_\_\_\_ 8" \_\_\_\_\_

Purge Vol. Multiplier: 0.16 0.65 1.47 2.61 gal/ft.  
Initial Measurement Recharge Measurement  
 Time: 4:25 Time: 6:35 Calculated purge: 69.7  
 Depth of well: 53.73 Depth to water: 27.18 Actual purge: 69.7  
 Depth to water: 26.90

Start purge: 5:51 Sampling time: 6:40

Time	Temp.	E.C.	pH	Turbidity	Volume
5:59	63.1	1236	7.70	—	1
6:08	64.3	1220	7.10	—	2
6:19	64.4	1190	7.09	—	3
6:30	64.1	1187	7.08	—	4

Sample appearance: clear Lock: Dolphin

Equipment replaced: (Check all that apply) Note condition of replaced item  
 2" Locking Cap: \_\_\_\_\_ Lock #3753: \_\_\_\_\_ 7/32 Allenhead: \_\_\_\_\_  
 4" Locking Cap: \_\_\_\_\_ Lock-Dolphin: \_\_\_\_\_ 9/16 Bolt: \_\_\_\_\_  
 6" Locking Cap: \_\_\_\_\_ Pinned Allenhead (DWP): \_\_\_\_\_

Remarks: \_\_\_\_\_

Signature: [Handwritten Signature]

Client: Ultramar

Sampling Date: 12-2-96

Site: Beacon #604

Project No.: 95-604-01

1619 West First Street

Well Designation: MW-5

Livermore, CA

Is setup of traffic control devices required?  NO YES time: \_\_\_\_\_ hours  
 Is there standing water in well box?  NO YES Above TOC Below TOC  
 Is top of casing cut level? NO  YES If no, see remarks  
 Is well cap sealed and locked? NO  YES If no, see remarks  
 Height of well casing riser (in inches): 4  
 Well cover type: 8" UV  12" UV \_\_\_\_\_ 12" EMCO \_\_\_\_\_ 8" BK \_\_\_\_\_  
 12" BK \_\_\_\_\_ 12" DWP \_\_\_\_\_ 12" CNI \_\_\_\_\_ 36" CNI \_\_\_\_\_ Other \_\_\_\_\_  
 General condition of wellhead assembly: Excellent  GOOD Fair Poor

Purging Equipment: \_\_\_\_\_ 2" disposable bailer \_\_\_\_\_ Submersible pump  
 \_\_\_\_\_ 2" PVC bailer \_\_\_\_\_ Dedicated bailer  
 \_\_\_\_\_ 4" PVC bailer  Centrifugal pump

Sampled with: Disposable bailer:  Teflon bailer: \_\_\_\_\_

Well Diameter: 2"  4" \_\_\_\_\_ 6" \_\_\_\_\_ 8" \_\_\_\_\_

Purge Vol. Multiplier: 0.16 0.65 1.47 2.61 gal/ft.

Initial Measurement Recharge Measurement  
 Time: 4:13 Time: 5:15 Calculated purge: 12.6  
 Depth of well: 46.31 Depth to water: 26.81 Actual purge: 12.6  
 Depth to water: 26.51

Start purge: 5:10 Sampling time: 5:16

Time	Temp.	E.C.	pH	Turbidity	Volume
5:10	64.0	1200	7.21	—	1
5:11	64.0	1131	7.15	—	2
5:12	63.9	1127	7.11	—	3
5:13	63.4	1130	7.08	—	4

Sample appearance: Clear Lock: Dolphin

Equipment replaced: (Check all that apply) Note condition of replaced item  
 2" Locking Cap: \_\_\_\_\_ Lock #3753: \_\_\_\_\_ 7/32 Allenhead: \_\_\_\_\_  
 4" Locking Cap: \_\_\_\_\_ Lock-Dolphin: \_\_\_\_\_ 9/16 Bolt: \_\_\_\_\_  
 6" Locking Cap: \_\_\_\_\_ Pinned Allenhead (DWP): \_\_\_\_\_

Remarks: \_\_\_\_\_

Signature: Hal Kanan

Client: Ultramar

Sampling Date: 12-2-96

Site: Beacon #604

Project No.: 95-604-01

1619 West First Street

Well Designation: MW-6

Livermore, CA

Is setup of traffic control devices required?  NO YES time: \_\_\_\_\_ hours  
 Is there standing water in well box?  NO YES Above TOC Below TOC  
 Is top of casing cut level? NO  YES If no, see remarks  
 Is well cap sealed and locked? NO  YES If no, see remarks  
 Height of well casing riser (in inches): 4  
 Well cover type: 8" UV  12" UV \_\_\_\_\_ 12" EMCO \_\_\_\_\_ 8" BK \_\_\_\_\_  
 12" BK \_\_\_\_\_ 12" DWP \_\_\_\_\_ 12" CNI \_\_\_\_\_ 36" CNI \_\_\_\_\_ Other \_\_\_\_\_  
 General condition of wellhead assembly: Excellent  Good Fair Poor

Purging Equipment: \_\_\_\_\_ 2" disposable bailer \_\_\_\_\_ Submersible pump  
 \_\_\_\_\_ 2" PVC bailer \_\_\_\_\_ Dedicated bailer  
 \_\_\_\_\_ 4" PVC bailer  Centrifugal pump

Sampled with: Disposable bailer:  Teflon bailer: \_\_\_\_\_

Well Diameter: 2"  4" \_\_\_\_\_ 6" \_\_\_\_\_ 8" \_\_\_\_\_

Purge Vol. Multiplier: 0.16 0.65 1.47 2.61 gal/ft.  
Initial Measurement Recharge Measurement  
 Time: 4:21 Time: 5:45 Calculated purge: 12.8  
 Depth of well: 47.51 Depth to water: 27.80 Actual purge: 12.8  
 Depth to water: 27.42

Start purge: 5:35 Sampling time: 5:47

Time	Temp.	E.C.	pH	Turbidity	Volume
5:36	63.7	1127	7.35	—	1
5:37	64.0	1120	7.31	—	2
5:39	64.1	1090	7.20	—	3
5:41	64.3	1087	7.17	—	4

Sample appearance: Clear Lock: Dolphin

Equipment replaced: (Check all that apply) Note condition of replaced item  
 2" Locking Cap: \_\_\_\_\_ Lock #3753: \_\_\_\_\_ 7/32 Allenhead: \_\_\_\_\_  
 4" Locking Cap: \_\_\_\_\_ Lock-Dolphin: \_\_\_\_\_ 9/16 Bolt: \_\_\_\_\_  
 6" Locking Cap: \_\_\_\_\_ Pinned Allenhead (DWP): \_\_\_\_\_

Remarks: \_\_\_\_\_

Signature: Karl Hansen

Client: Ultramar  
 Site: Beacon #604  
1619 West First Street  
Livermore, CA

Sampling Date: 12-2-96  
 Project No.: 95-604-01  
 Well Designation: MW- 7

Is setup of traffic control devices required?  NO YES time: \_\_\_\_\_ hours  
 Is there standing water in well box?  NO YES Above TOC Below TOC  
 Is top of casing cut level? NO  YES If no, see remarks  
 Is well cap sealed and locked? NO  YES If no, see remarks  
 Height of well casing riser (in inches): 10  
 Well cover type: 8" UV  12" UV \_\_\_\_\_ 12" EMCO \_\_\_\_\_ 8" BK \_\_\_\_\_  
 12" BK \_\_\_\_\_ 12" DWP \_\_\_\_\_ 12" CNI \_\_\_\_\_ 36" CNI \_\_\_\_\_ Other \_\_\_\_\_  
 General condition of wellhead assembly: Excellent  GOOD Fair Poor

Purging Equipment: \_\_\_\_\_ 2" disposable bailer \_\_\_\_\_ Submersible pump  
 \_\_\_\_\_ 2" PVC bailer \_\_\_\_\_ Dedicated bailer  
 \_\_\_\_\_ 4" PVC bailer  Centrifugal pump

Sampled with: Disposable bailer:  Teflon bailer: \_\_\_\_\_

Well Diameter: 2"  4" \_\_\_\_\_ 6" \_\_\_\_\_ 8" \_\_\_\_\_

Purge Vol. Multiplier: 0.16 0.65 1.47 2.61 gal/ft.  
Initial Measurement Recharge Measurement  
 Time: 4:17 Time: 5:30 Calculated purge: 12.4  
 Depth of well: 46.58 Depth to water: 28.10 Actual purge: 12.4  
 Depth to water: 27.11

Start purge: 5:19 Sampling time: 5:32

Time	Temp.	E.C.	pH	Turbidity	Volume
5:20	64.2	1210	7.54	—	1
5:22	64.0	1149	7.47	—	2
5:23	63.7	1140	7.31	—	3
5:25	63.0	1131	7.28	—	4

Sample appearance: Clear Lock: Valve

Equipment replaced: (Check all that apply) Note condition of replaced item  
 2" Locking Cap: \_\_\_\_\_ Lock #3753: \_\_\_\_\_ 7/32 Allenhead: \_\_\_\_\_  
 4" Locking Cap: \_\_\_\_\_ Lock-Dolphin: \_\_\_\_\_ 9/16 Bolt: \_\_\_\_\_  
 6" Locking Cap: \_\_\_\_\_ Pinned Allenhead (DWP): \_\_\_\_\_

Remarks: \_\_\_\_\_

Signature: Neil Hansen



**ATTACHMENT C**

**LABORATORY REPORT AND  
CHAIN-OF-CUSTODY FORM**

December 12, 1996  
Sample Log 16053

Dale van Dam  
El Dorado Environmental  
2221 Goldorado Trail  
El Dorado, CA 95623

Subject: Analytical Results for 5 Water Samples  
Identified as: Beacon 604 (Proj. # 94-604-01)  
Received: 12/04/96

Dear Mr. van Dam:


Analysis of the sample(s) referenced above has been completed. This report is written to confirm results communicated on December 12, 1996 and describes procedures used to analyze the samples.

Sample(s) were analyzed using the following method(s):

"BTEX" (EPA Method 602/Purge-and-Trap)  
"TPH as Gasoline" (Modified EPA Method 8015/Purge-and-Trap)

Please refer to the following table(s) for summarized analytical results and contact us at 916-753-9500 if you have questions regarding procedures or results. The chain-of-custody document is enclosed.

Approved by:



---

Joel Kiff  
Senior Chemist

MTBE (Methyl-t-butyl ether) By EPA Method 8020/602

From : Beacon 604 (Proj. # 94-604-01)


Sampled : 12/02/96

Received : 12/04/96

Matrix : Water

MTBE	(MRL) $\mu\text{g/L}$	Measured Value $\mu\text{g/L}$
MW-1	(5.0)	<5.0
MW-2	(130)	<130
MW-5	(5.0)	<5.0
MW-6	(500)	<500
MW-7	(50)	<50

Approved By:

  
\_\_\_\_\_  
Joel Kiff  
Senior Chemist

Sample: MW-1

From : Beacon 604 (Proj. # 94-604-01)


Sampled : 12/02/96

Dilution : 1:1

QC Batch : 6179U

Matrix : Water

Parameter	(MRL) ug/L	Measured Value ug/L
Benzene	(.50)	<.50
Toluene	(.50)	<.50
Ethylbenzene	(.50)	<.50
Total Xylenes	(.50)	<.50
TPH as Gasoline	(50)	<50
Surrogate Recovery		98 %



Date Analyzed: 12-11-96  
 Column : 0.53mm ID X 60m Restek Rtx-1701

*Joel Kiff*  
 Joel Kiff  
 Senior Chemist

Sample: MW-2

From : Beacon 604 (Proj. # 94-604-01)


Sampled : 12/02/96

Dilution : 1:25

QC Batch : 6179U

Matrix : Water

Parameter	(MRL) ug/L	Measured Value ug/L
Benzene	(13)	4400
Toluene	(13)	4000
Ethylbenzene	(13)	1300
Total Xylenes	(13)	6100
TPH as Gasoline	(1300)	29000
Surrogate Recovery		106 %



Date Analyzed: 12-11-96  
 Column : 0.53mm ID X 60m Restek Rtx-1701

*Jdel Kiff*  
 Jdel Kiff  
 Senior Chemist

Sample: MW-5

From : Beacon 604 (Proj. # 94-604-01)


Sampled : 12/02/96

Dilution : 1:1

QC Batch : 6179U

Matrix : Water

Parameter	(MRL) ug/L	Measured Value ug/L
Benzene	(.50)	1.1
Toluene	(.50)	.64
Ethylbenzene	(.50)	<.50
Total Xylenes	(.50)	<.50
TPH as Gasoline	(50)	200
Surrogate Recovery		112 %



Date Analyzed: 12-11-96  
 Column : 0.53mm ID X 60m Restek Rtx-1701

*Joel Kiff*  
 Joel Kiff  
 Senior Chemist

Sample: MW-6

From : Beacon 604 (Proj. # 94-604-01)


Sampled : 12/02/96

Dilution : 1:100

QC Batch : 6179U

Matrix : Water

Parameter	(MRL) ug/L	Measured Value ug/L
Benzene	(50)	3000
Toluene	(50)	1100
Ethylbenzene	(50)	970
Total Xylenes	(50)	8300
TPH as Gasoline	(5000)	28000
Surrogate Recovery		106 %



Date Analyzed: 12-11-96  
 Column : 0.53mm ID X 60m Restek Rtx-1701

*Joel Kiff*  
 Joel Kiff  
 Senior Chemist

Sample: MW-7

From : Beacon 604 (Proj. # 94-604-01)


Sampled : 12/02/96

Dilution : 1:10


QC Batch : 6179U

Matrix : Water

Parameter	(MRL) $\mu\text{g/L}$	Measured Value $\mu\text{g/L}$
Benzene	(5.0)	87
Toluene	(5.0)	29
Ethylbenzene	(5.0)	290
Total Xylenes	(5.0)	430
TPH as Gasoline	(500)	6300
Surrogate Recovery		95 %



Date Analyzed: 12-11-96  
 Column : 0.53mm ID X 60m Restek Rtx-1701

  
 Joel Kiff  
 Senior Chemist





**Ultramar Inc.**  
**CHAIN OF CUSTODY REPORT**

**BEACON**

Beacon Station No. <b>604</b>		Sampler (Print Name) <b>Mq Hansen</b>			ANALYSES				Date <b>12-2-96</b>	Form No. <b>1 of 1</b>	
Project No. <b>94-604-01</b>		Sampler (Signature) <i>[Signature]</i>			BTEX	TPH (gasoline)	TPH (diesel)	No. of Containers	<b>Standard JAT</b>		
Project Location <b>Silverdale</b>		Affiliation <b>Doulos Env.</b>									
Sample No./Identification	Date	Time	Lab No.	BTEX	TPH (gasoline)	TPH (diesel)	No. of Containers	REMARKS			
<b>MW-1</b>	<b>12-2-96</b>	<b>508</b>	<b>16053-01</b>	X	X		<b>2</b>				
<b>MW-2</b>		<b>640</b>	<b>-02</b>								
<b>MW-5</b>		<b>516</b>	<b>03</b>								
<b>MW-6</b>		<b>547</b>	<b>04</b>								
<b>MW-7</b>	<b>✓</b>	<b>532</b>	<b>05</b>	<b>✓</b>	<b>✓</b>		<b>✓</b>	RECEIVED DATE <b>12/4/96</b> TIME <b>1530</b>			
								TEMP <b>0°</b>			
								INITIAL <b>SW</b>			
								WEST. LAB			
Relinquished by: (Signature/Affiliation) <i>[Signature]</i> <b>Doulos Env.</b>		Date <b>12/4/96</b>	Time <b>1430</b>	Received by: (Signature/Affiliation) <i>[Signature]</i> <b>West</b>				Date <b>12/4/96</b>	Time <b>1430</b>		
Relinquished by: (Signature/Affiliation) <i>[Signature]</i> <b>West</b>		Date <b>12/4/96</b>	Time <b>1525</b>	Received by: (Signature/Affiliation)				Date	Time		
Relinquished by: (Signature/Affiliation)		Date	Time	Received by: (Signature/Affiliation)				Date	Time		
Report To: <b>Dale Vandam</b>				Bill to: ULTRAMAR INC. 525 West Third Street Hanford, CA 93230 Attention: <b>Tony Fox</b>				Date <b>12/4/96</b>	Time <b>1525</b>		

WHITE: Return to Client with Report

YELLOW: Laboratory Copy

PINK: Originator Copy